

Recognizing Co-Speech Gestures in-the-Wild

Sindhu B Hegde, K R Prajwal, and Andrew Zisserman

Visual Geometry Group, Dept. of Engineering Science, University of Oxford
 {sindhu,prajwal,az}@robots.ox.ac.uk
<https://www.robots.ox.ac.uk/~vgg/research/grw>

Abstract. While humans naturally gesture during speech, only a sparse subset of these movements are visually depictive and semantically linked to specific spoken words. Current multimodal models struggle to capture these semantic co-speech gestures, heavily bottlenecked by a lack of precisely annotated training data. To address this, we introduce the Gesture Recognition in the Wild (GRW) dataset, the first large-scale benchmark designed to map unconstrained human gestures to specific words with frame-accurate temporal boundaries. Comprising 156,688 manually annotated video clips, GRW spans a highly diverse 150-word taxonomy of physical actions, spatial descriptors, and abstract concepts. We leverage GRW to train video models to (a) classify gestures as semantic or not, (b) recognize the word corresponding to a co-speech gesture, and (c) temporally localize the gesture. We also use GRW to establish benchmarks for these three tasks.

Keywords: gesture recognition · gesture localization

1 Introduction




Fig. 1: Semantic vs. non-semantic co-speech gestures. **(Top)** Obama performs an iconic semantic gesture for the word “massive”. Notice the significant temporal offset between the physical gesture and the spoken word. **(Bottom)** There are no semantic gestures around the word “beginning”. This paper focuses on building a dataset and models that can automatically recognize and localize semantic gestures in real-world clips.

Humans naturally move their hands and upper body while speaking, yet only a sparse subset of these movements are *meaning-bearing*. In this work, we focus on **semantic co-speech gestures**, i.e. instances where a speaker produces a clear, visually depictive (iconic, deictic, or metaphoric) movement directly attributable to a specific spoken word (e.g., tracing a *circle* while saying ‘circle’, or moving the hands *apart* while saying ‘massive’ in Fig 1). Humans also make other gestures while speaking, such as *beat* gestures (rhythmic emphasis) and incidental motions (fidgeting, resting hands), but these are considered *non-semantic*.

Unfortunately, no large-scale dataset currently exists that has annotations for these semantic co-speech gestures in unconstrained situations. Distinguishing these semantic gestures in-the-wild is challenging: they are relatively sparse in time, highly variable in form, and often require integrating both linguistic and visual context. Consequently, while recent multimodal foundation models for video understanding [21, 35, 37] excel at generic recognition and retrieval, they remain remarkably brittle when tasked with recognizing specific, fine-grained gestures. To address this critical gap, we make the following contributions:

Gesture Recognition in the Wild (GRW) Dataset: We introduce the first large-scale, unconstrained benchmark for semantic co-speech gestures. GRW features manually curated annotations for over 156K video clips across 12K unique identities, indicating whether or not a semantic gesture is present. For semantic instances, we provide precise word labels and frame-accurate temporal boundaries for both the speech and the corresponding gesture, explicitly accounting for the natural temporal misalignment between the two.

Insights into dynamics of gesture & spoken words: Leveraging the diversity of our data, we provide a comprehensive analysis of how humans gesture in the wild. We reveal fundamental insights into the temporal envelope of gestures (is the word gestured before it is spoken or after?) and the relative likelihood of words to elicit a semantic gesture (which words are most often gestured?)

New models for three core gesture tasks: We formalize three core gesture tasks: (i) semantic gesture classification – is the gesture semantic or not? (ii) word-level gesture recognition, and (iii) temporal gesture localization; and devise and train models for these tasks using the GRW dataset. We show the benefit in modeling extended temporal motion context for semantic gesture classification. Finally, we show that our models outperform existing state-of-the-art vision-language models, establishing a new foundation for multimodal gesture research.

2 Related Work

Human gestures are studied across multimodal machine learning, HCI, graphics, and linguistics. Existing resources vary significantly in gesture type (isolated commands vs. co-speech vs. sign language), sensing modality (RGB/RGB-D, 2D/3D pose), and supervision granularity.

Gesture Datasets. Many datasets focus on predefined, isolated command gestures (e.g., swipes, thumbs-up) for HCI applications. Examples include Jester (27 classes) [25], EgoGesture (83 classes) [36], NVGesture [26], and the ChaLearn LAP challenges (IsoGD/ConGD) scaling to hundreds of categories [33]. While

Table 1: Comparison of gesture datasets. Our dataset uniquely provides verified semantic word labels and precise temporal gesture boundaries for in-the-wild co-speech gestures while supporting diverse multimodal inputs.

Dataset	Modality	# Identities	Hours	In-the-wild?	Gestured word labels	Temporal Bounds
Isolated / Command-Style						
Jester [25]	RGB	1,376	~123	✗	✗	✓
EgoGesture [36]	RGB-D	50	24	✗	✗	✓
NVGesture [26]	RGB-D+IR	20	~10	✗	✗	✓
ChaLearn LAP [33]	RGB-D	21	~14	✗	✗	✓
Co-Speech Gestures						
Trinity [10]	Mocap+Audio	1	4	✗	✗	✗
TalkingWithHands [19]	Mocap+Audio	50	150	✗	✗	✗
BEAT [22]	Mocap+Audio	30	76	✗	✓	✗
Speech2Gesture [12]	2D+Audio	10	144	✓	✗	✗
PATS [2]	2D+Audio+Text	25	251	✓	✗	✗
AVS-Spot [16]	RGB+Audio+Text	384	0.4	✓	✓	✗
SeamlessInteraction [1]	RGB+Audio+Text	4,000	4,065	✗	✗	✗
Ours (GRW)	RGB+Audio+Text	12,010	174	✓	✓	✓

valuable, these datasets model gestures-as-commands and lack the spoken-word grounding and linguistic alignment necessary for co-speech semantic modeling.

Sign language datasets: Corpora like BOBSL [3], How2Sign [7], WLASL [20], and YouTube-ASL [32] benchmark sign language recognition and generation. Here, hand shape and motion are the primary communication channel rather than an auxiliary speech accompaniment. Although annotated at the word level, their discrete linguistic structure differs fundamentally from co-speech gestures, which are optional, highly variable, and only partially aligned with lexical items, preventing the direct transfer of methods.

Co-speech gesture datasets: High-fidelity 3D motion capture datasets, such as Trinity Speech-Gesture [10] and Talking With Hands [19], provide clean trajectories, but lack diverse speakers and contexts. The BEAT dataset [22] adds emotion and semantic-relevance annotations, categorizing beats, iconic, deictic, and metaphoric gestures. But, these datasets are limited by scale and diversity. A recent large-scale dataset, Seamless Interaction [1] is massive in scale (4000+ speakers, 4000+ hours) but it is recorded in laboratory settings where dialogues are enacted with instructions to the actors, and do not contain gestured word labels either. There are also “in-the-wild” datasets used in gesture synthesis works, that source videos from TED talks and TV shows. For example, Speech2Gesture [12] (144 hours, 10 speakers) and PATS [2] (251 hours, 25 speakers) aggregate auto-detected poses, audio, and transcripts. While critical for scaling generation models, these datasets lead to models that do not generate semantic gestures well, due to lack of specific annotations for the same [28].

Gesture Recognition and Understanding. Historically treated as an action recognition sub-problem, early gesture recognition employs 2D/3D CNNs and sequence models evaluated on isolated datasets [18, 26, 30]. Analyzing co-speech gestures, however, requires detecting their presence and segmenting temporal boundaries. Only recently, JEGAL [16] formalized tasks such as gesture-based retrieval and word spotting using tri-modal (video, speech, text) representations.

While aligned with modeling semantics, these benchmarks focus on representation learning and retrieval rather than explicitly recognizing and segmenting semantic gestures with precise, word-level boundaries.

Gesture Synthesis. Gesture generation has historically included rule-based and procedural systems inspired by linguistics. In recent years, data-driven models dominate, enabled by large gesture data and progress in sequence modeling. Speech2Gesture [12] was a seminal work that learned personalized patterns from in-the-wild monologues using auto-extracted poses. Subsequent modern generative models like StyleGestures [4] and ExpressGesture [11] improved realism, control, and coverage. Audio-driven models capture prosody well but struggle with semantic gestures. Incorporating transcripts or text embeddings has been a step towards addressing this. Rhythmic Gesticulator [5] structures explicit rhythm and semantics, while ConvoFusion [27] uses diffusion to emphasize specific words. However, these models still predominantly rely on speech stress and prosody, noting that sparse semantic gestures remain difficult to capture due to a lack of non-beat annotations in training data.

3 The GRW Dataset



Fig. 2: Samples from the **GRW** dataset. (a) Lexical and kinematic diversity of semantic gestures. (b) Even when gesturing the same conceptual word (“SPIRAL”), speakers employ different physical motions. The dataset captures these gestures across a wide variety of speakers, poses, and camera angles.

The GRW dataset comprises 156,688 manually annotated video clips curated from diverse, in-the-wild speaker environments. The core dataset features 17,473 precisely localized positive instances of semantic gestures, distributed across a broad vocabulary of 150 conceptual words. The dataset also comprises 139,215 verified negative samples where a target vocabulary word is spoken, but no corresponding semantic gesture is physically performed. Finally, we also include an automatically labeled set of 61,141 clips with word labels and approximate gesture boundaries that can be used for large-scale pre-training.

In Fig 2, we show a few representative samples from the dataset. Unlike laboratory-recorded isolated gesture datasets, GRW captures gestures in completely unconstrained, in-the-wild conditions with natural intra- and inter-class variations. Fig. 3 details our 150-word vocabulary across semantic domains ranging from literal actions (‘Translational’, ‘Pointing’) to complex concepts

Table 2: Overview of the GRW dataset splits. It contains manually verified data for rigorous evaluation and finetuning, and large-scale pseudo-labeled data for pre-training.

Task / Split	Total Clips	Hours	Vocab	Semantic	Non-Semantic
Semantic Gesture Classification					
Train Split	152,688	169.65	150	15,473	137,215
Test Split	4,000	4.44	100	2,000	2,000
Total	156,688	174.09	150	17,473	139,215
Word Recognition & Localization					
Pre-train Split (noisy)	61,141	67.93	150	61,141	-
Train Split (clean)	15,473	17.19	150	15,473	-
Test Split (clean)	2,000	2.22	100	2,000	-
Total (clean)	17,473	19.41	150	17,473	-

(‘State/process’, ‘Physical’). Node sizes (reflecting frequency) confirm a robust distribution across common anchors (e.g., ‘bye’, ‘together’) and nuanced descriptors (e.g., ‘spiral’, ‘expand’), establishing GRW as a comprehensive benchmark for real-world gesture understanding. Each sample provides video, audio, word-level transcripts, and a binary semantic gesture label; positive samples additionally include the lemmatized target word w and its precise temporal gesture boundary $\mathcal{B}$.

4 Dataset Curation Pipeline

In this section we describe the pipeline used to curate the GRW word-level semantic gesture dataset and benchmark. The principal steps are: (i) large-scale automatic mining and filtering from a word-aligned speech corpus; and (ii) multi-stage human annotation with redundancy and verification. Table 3 shows the number of clips and yield for semantic gestures at the stages of the pipeline.

4.1 Mining and filtering to obtain candidate video clips

The objective is to obtain a large set of word-aligned video clips potentially containing associated co-speech gestures.

Video data source. We use the English subset of MultiVSR [29], a large-scale multilingual visual speech recognition dataset with word-aligned transcripts, as our in-the-wild video pool. Sourced from YouTube, MultiVSR contains extended full-length versions of the AVSpeech [9] videos. The videos exhibit




Fig. 3: Semantic Taxonomy of the GRW Dataset. We organize our 150-word vocabulary into a three-tiered hierarchy, radiating from five high-level semantic domains to specific target words (leaf nodes). Node size is strictly proportional to the frequency of annotated clips per word.

Table 3: Overview of the GRW dataset curation pipeline. We detail the progression of our data from raw video filtering to final manual annotation. After rigorous quality checks, we obtain over 17k annotated semantic clips.

Pipeline Stage	Total Clips	Yield	Hours	Vocab	Non-Semantic	Notes
Raw videos	1,529,572	-	1,699.52	200	n/a	Sourced from MultiVSR
Mining and filtering	525,226	-	583.58	185	n/a	Keypoint filtering
Assigned for manual labeling	161,828	-	179.80	185	n/a	Output of Section 4.1
After recognition annotations	19,195	11.8%	21.33	150	139,215	Output of Section 4.2
After localization annotation	17,473	10.7%	19.41	150	n/a	Output of Section 4.3

substantial real-world variability across lighting, viewpoints, backgrounds, and speaker demographics. We pre-process the videos to obtain stable upper-body gesture crops. Details on pre-processing are given in the supplementary.

Lexicon of gesturable words. Given the MultiVSR English vocabulary, we target *plausibly gesturable words* for iconic, metaphoric, or deictic gestures (e.g., motion verbs, spatial relations, size/shape adjectives), excluding high-frequency function words that rarely elicit semantic depiction. To systematically construct this lexicon, we extract the most frequent lemmas from the dataset’s transcripts and prompted an LLM (Gemini [13]) to score each word based on its likelihood to elicit a semantic gesture. The top-scoring candidates are then manually verified, yielding a final set of 200 English lemmas expected to induce distinctive gestures. For every match in the dataset to a lemma on this list, we extract a 4-second temporal window centered around the word timestamp. This yields a large collection of candidate clips (1.5M clips), potentially containing semantic gestures. However, this initial pool contains both true positives and substantial noise (e.g., no-gesture segments, beat-only motion, hands out of frame).

Visual filtering for gestures. To reduce annotation cost and improve positive sample yield, we apply automatic pose keypoint filtering [23]. For each candidate clip, we compute: (i) the fraction of frames with confident hand/wrist detections, and (ii) the mean temporal hand displacement (velocity), $|p_t - p_{t-1}|_2$, with p_t denoting the frame t hand centroid. Candidates failing minimum visibility or motion thresholds are discarded. This keypoint-based filtering retains approximately 525K candidates across 185 target words. As the mined distribution is highly long-tailed, naive sampling would over-represent high-frequency words. We therefore construct a semi-balanced $\approx 162K$ clip subset for manual annotation, sampling 100 to 1500 instances per word to ensure low-frequency lemma coverage and prevent high-frequency dominance.

4.2 Manual annotation for word recognition

The objective is to partition the 161,828 candidate clips into two sets: those containing a co-speech gesture corresponding to a target word, and those that don’t (e.g., beat or random gestures). Both sets are retained for subsequent model training.

Stage-1: Annotating semantic gestures. The annotators assign a binary label to each of the candidate samples, indicating the presence of a corresponding semantic gesture for a target word. The annotators are trained to only mark a

clip as ‘Positive’ if there is a clearly identifiable gesture that depicts the target word. We developed a custom web-based interface using (VIA) [8] (details in supplementary). For each target word, annotators review a grid of associated video clips (with audio playback) and assign the binary label. This selection stage required approximately 1,000 annotation hours.

Stage-1: Quality control. Each sample is independently labeled by five annotators, screened using a held-out set of 500 gesture clips. To reduce mistakes post-annotation, we aggregate labels via majority voting, discarding words with high disagreement, yielding roughly 19K semantic videos (11.8% positive rate).

4.3 Manual annotation for word localization

Stage-2: Annotating temporal gesture boundaries. The input to this stage is the set of 19K output semantic gesture clips obtained from Section 4.2. For each clip, annotators mark the start-end timestamps of the gesture corresponding to the target word. This task is more demanding than binary recognition, as it requires precise temporal localization through scrubbing, frame stepping, and repeated viewing. The interface and detailed annotation guidelines are provided in the supplementary material. This stage required approximately 500 hours of annotation efforts.

Stage-2: Quality control. To ensure gesture boundary reliability, we retain only those samples for which *at least three annotators* provide start-end timestamps that differ by less than 1-second. This filtering yields 17,473 samples containing semantically grounded gestures with reliable word-level temporal boundaries, which becomes our final GRW semantic dataset. This amounts to 19.41 hours of clean data.

4.4 Curating a pre-train set

To scale downstream word recognition and temporal localization without prohibitive manual annotation costs, we employ a pseudo-labeling strategy. By applying a strict confidence threshold to the classifier’s predicted probability of a semantic gesture (≥ 0.9) to our trained semantic classifier (Section 6.2), we automatically mine 61,141 high-confidence positive clips from the ~ 363 K unannotated candidates (Table 3). For weak localization labels, we pad each clip’s speech boundaries using word-specific average start-end frame offsets derived from the clean GRW train split. This weakly-labeled set is then used to pre-train our recognition and localization models.

5 Dataset Analysis

In this section we present an initial analysis of the co-speech gestures in the GRW dataset. We are interested in three questions: (i) how likely a given word is to be accompanied by a semantically meaningful gesture; (ii) how the timing of the gesture segment relates to the spoken word segment; and (iii) how variable the gestures are for the same word across speakers and context. Prior works [16, 22] have investigated some of these questions, but have been in laboratory settings or with limited scale and diversity of the data – potentially restricting the scope and generality of their findings.

5.1 How likely are the words to be gestured?

Fig 4 shows the proportion of gestured instances among all clips submitted for annotation. The likelihood that a word is accompanied by a semantically meaningful gesture varies dramatically across the lexicon. While some words are gestured very frequently, for example, ‘bye’ is gestured approximately 66%, while others are rarely depicted. At the extreme low end, ‘look’ is gestured in less than 1% of cases. This long-tailed distribution highlights the sparsity of semantic gestures in natural discourse and motivates the need for large-scale filtering and careful annotation to obtain high-quality gesture–word pairs.




Fig. 4: Not all words are gestured equally: We plot the likelihood that a spoken word is accompanied by a depictive semantic gesture. Abstract concepts and common verbs (left inset) rarely elicit semantic gestures ($< 2\%$), whereas inherently spatial or physical actions like push, below, and bye (right inset) are gestured with high frequency.

5.2 Gesture vs. speech boundaries

We analyze the temporal relationship between the spoken words and their semantic gestures at a larger scale and find that gesture–speech alignment is loose and highly variable. The Violin plot in Fig 5(a) shows that the average duration of spoken word segments is much shorter than their corresponding gesture segments across all annotated words. Fig 5 (b) quantifies this mismatch. Gestures start before the spoken word (96.6%) and end after the spoken word (89.7%). Finally, Fig 5 (c) visualizes averaged activation heatmaps for a few word classes, showing that a gesture is often distributed asymmetrically around the speech center. Together, these analyses highlight that gesture boundaries are loosely aligned with speech, making word-level gesture recognition and gesture localization particularly challenging.

5.3 Variations in gestures

Co-speech gestures vary substantially across speakers and contexts: a single word can elicit multiple distinct movements, and different words may share visually similar gestures. For example (Fig. 2), speakers depict ‘spiral’ using one or both hands, via vertical or horizontal motions. Similarly, ‘zoom’ elicits spreading palms, opening fingers, or moving hands apart. Conversely, ‘shrink’ is gestured by bringing hands inward, pinching fingers, or pressing palms together. More examples are in the supplementary material.




Fig. 5: Gesture-speech temporal alignment. Semantic gestures rarely align perfectly with spoken words. As shown in (a), gestures are significantly longer in duration than speech. (b) The vast majority of gestures start before (96.6%) and end after (89.7%) the target word is spoken. (c) Activation heatmaps (aggregated across all samples for a specific word) visually confirm this “envelope” effect.

6 Recognizing Co-speech Gestures

We introduce two complementary co-speech gesture recognition models that are trained on GRW: (i) a **semantic gesture classification** model that predicts whether a short video clip contains a clear semantic (iconic, deitic, metaphoric) gesture or not, and (ii) a **gestured word recognition & localization** model that (a) predicts the gestured word class, and (b) localizes the gesture segment in time within a short clip. The architecture and training of the two models is illustrated in Fig 6. Both models are built on top of a frozen visual backbone pretrained to extract per-frame hand shape and position features. The features are then ingested by a series of transformer blocks for task-specific temporal modeling and prediction. In the following we first describe the common visual backbone, and then the two task specific transformer architectures.

6.1 Gesture backbone

Given a video clip $V \in \mathbb{R}^{T \times H \times W \times 3}$, we extract frame-level features using SHuBERT [14] as our pretrained gesture backbone. Pretrained on large-scale sign-language data [32], SHuBERT provides robust visual features that inherently capture fine-grained hand shapes and semantically distinctive motions. We extract the hidden states from L layers of this Transformer-based model to construct a multi-layer sequence tensor $f_{\text{multi}} \in \mathbb{R}^{L \times T \times d_{in}}$. Here, $d_{in} = 768$ represents the feature dimension, and T is the number of frames (corresponding to approximately 4 to 10 seconds of video).

Weighted layerwise feature aggregation. To optimally fuse SHuBERT’s layers, an MLP processes f_{multi} to generate L scalar scores, which are softmax-normalized into mixing weights α . A weighted sum across the layer dimension then collapses this into a single sequence $f \in \mathbb{R}^{T \times d_{in}}$, serving as the direct input to our downstream task-specific models (details in supplementary).




Fig. 6: (a) A binary semantic gesture classifier for a query clip. The model uses cross-attention between a target query clip and a broader temporal motion context. (b) The word recognition and localization model is trained in two stages: first, pre-trained on auto-generated pseudo-labels with weak boundary supervision, and then fine-tuned on manually annotated clean data for precise temporal localization.

6.2 Semantic Co-speech Gesture Classification

The semantic gesture classifier is designed to answer: *Does a video clip contain a clear semantic gesture or not, given the surrounding motion context?* Note that the “motion-context” is important here to spot semantic gestures in a reliable way in unconstrained co-speech gestures.

Intuition. Semantic gestures are typically sparse, arbitrary, and highly variable across different words and are not necessarily unique to a person. In contrast, non-semantic beat gestures are frequent, repetitive and serve as a person’s default gesturing rhythm. By encoding a long temporal window, the model learns the speaker’s baseline kinematics for non-semantic beat gestures and for their random gestures. This context makes it significantly easier for the model to contrast, isolate, and identify the sparse, unique semantic gestures, as such gestures physically deviate from the speaker’s established baseline.

Task formulation. Given a *long* context video $\mathbf{f}$ and a *query interval* $q = [s, e]$ with length $l = e - s + 1$, the goal is to predict a binary label $y \in \{0, 1\}$, where $y = 1$ indicates that the query interval contains a *clear semantic gesture* and $y = 0$ indicates no semantic gesture.

Architecture. Visual features f are projected to d_{model} via a 2-layer MLP (LayerNorm, ReLU) and processed by a Transformer Encoder. To model relative motion timing across the long context (up to 10s), we apply Rotary Position Embeddings (RoPE) [31], yielding a context-aware memory $M \in \mathbb{R}^{T \times d_{model}}$. Features spanning the target interval $[t_{start}, t_{end}]$ are extracted to form a query sequence $q \in \mathbb{R}^{l \times d_{model}}$. This query cross-attends to the full memory M within a Transformer Decoder, effectively referencing the full motion context when interpreting the query interval. Finally, the decoder output is temporally mean-

pooled and passed through an MLP with a sigmoid activation to yield the binary semantic probability p_{sem} .

Training. We train the semantic gesture classifier using the ‘Semantic Gesture Classification’ split of the GRW dataset in Table 2, consisting of 152,688 training examples, which exhibits a natural class imbalance (15,473 positive semantic gesture samples and 137,215 negative samples). To address this, we use class-balanced sampling to upsample positive class data in each batch, and additionally apply a class-weighting to the loss (assigns higher weight to positive samples). During training, we extract a long temporal context of $T = 250$ frames (10 seconds) and define a target query interval of $Q = 100$ frames (4 seconds). The model is optimized using a Binary Cross-Entropy (BCE) loss.

6.3 Co-speech Gesture Word Recognition and Localization

Given a *short* clip containing a semantic gesture somewhere inside it, the goal is to predict: (i) the class of the word: $c \in \{1, \dots, C\}$ corresponding to the co-speech gesture, and (ii) per-frame gesture presence: $\mathbf{a} = [a_1, \dots, a_T]$, $a_t \in \{0, 1\}$, where $a_t = 1$ indicates that frame t lies within the gesture interval and $a_t = 0$ otherwise. We use the SHuBERT features f_{multi} , which are then aggregated layer-wise to obtain $f \in \mathbb{R}^{T \times d_{in}}$, both same as in Section 6.1. These features are then temporally encoded using a Transformer encoder to get f_{enc} .

Word classification. We mean-pool the Transformer output features f_{enc} across the temporal dimension T to form a single, global video representation. A classification head consisting of a two-layer MLP projects this global embedding to produce softmax probabilities p_{rec} over the C semantic word classes.

Gesture localization. To achieve precise temporal localization without requiring complex region-proposal pipelines, we formulate the alignment task as a dense, frame-level binary classification. An MLP + sigmoid operates directly on per-frame encoder features f_{enc} to get per-frame probabilities p_{loc} .

6.4 Training the Word Recognition and Localization Model

The training is divided into two steps: (i) the model is pre-trained on the pseudo-labeled GRW pre-training data (61k samples) – this is weak supervision because the pseudo-labeled data only has approximate gesture boundaries (only the word is known); (ii) the model is fine-tuned on the manually annotated GRW word recognition training dataset (15k samples) – this is strong supervision as the gesture boundaries are annotated.

Weakly-supervised pre-training. We pre-train the word recognition and localization model on the 61K pseudo-labeled positive samples. Frames falling within the padded speech boundaries are treated as positives, and the rest are negative frames. The model is supervised using frame-level BCE loss for temporal localization, combined with a categorical cross-entropy loss for gestured word classification:

$$\mathcal{L} = - \sum_{c=1}^C y_c \log(p_{rec,c}) - \lambda_{loc} \frac{1}{T} \sum_{t=1}^T [a_t \log(p_{loc,t}) + (1 - a_t) \log(1 - p_{loc,t})]$$

Table 4: Semantic gesture classification performance. Our approach surpasses existing baselines, especially at high confidence thresholds (≥ 0.9). This validates its utility for extracting clean semantic gestures from unlabeled data.

Method	Accuracy (%)	Precision (%)	Recall (%)	Semantic class accuracy (%) for high-conf samples
Random	50.00	50.00	50.00	n/a
Frozen features				
Clip4Clip [24]	59.26	53.13	48.32	65.88
SemanticMoments [17]	60.57	58.97	49.87	69.42
Fine-tuned features				
GestSync [15]	63.40	59.68	53.57	68.67
JEGAL [16]	65.60	61.33	56.37	73.33
SOTA VLMs				
Gemini [13]	<u>66.64</u>	<u>63.36</u>	61.81	<u>74.02</u>
Ours	70.25	75.96	<u>59.72</u>	91.62

where y_c is the one-hot word label, $p_{rec,c}$ is the predicted word class probability, a_t is the ‘ground-truth’ binary frame label, and $p_{loc,t}$ is the predicted frame-level gesture probability at timestep t .

Fine-tuning on clean data. Finally, we fine-tune the recognition and localization model exclusively on the manually verified train split of 15,473 samples (Table 2). We use the same loss functions as in the pre-training stage.

7 Results

In this section we evaluate on the unseen test set of GRW for semantic gesture classification in Section 7.1, and gestured word recognition & localization in Section 7.2. In addition to evaluating on the test sets of GRW, we also evaluate the gesture classifier on unseen words, and the localization ability of the gesture recognizer on the test set of [16]. We first describe the baseline models we compare against. The metrics are task specific, and are described in each subsection.

Baselines. We evaluate on a diverse set of baselines, starting with strong pre-trained video-language representations as *fixed* feature extractors, training only a lightweight classifier on top. We use Clip4Clip [24] and SemanticMoments [17] to measure how far generic pretrained representations go *without* end-to-end adaptation. Next, we compare with the recent state-of-the-art co-speech gesture models that learn dense frame-level representations. We finetune GestSync [15] and JEGAL [16] with additional task-specific prediction heads on the exact same data as our approach. Finally, we evaluate a production-grade VLM, Gemini-3 in a prompted setting: given a video clip and a list of candidate word classes, the model is asked to: (i) recognize the gestured word and (ii) localize the temporal boundaries (start and end time) of the corresponding gesture instance. Detailed prompts are provided in the supplementary.

7.1 Semantic Gesture Classification

Metrics: We evaluate performance using *Accuracy*, *Precision*, and *Recall* to account for inherent class imbalance. Additionally, to evaluate the classifier’s

Table 5: Word-level gesture recognition & localization performance. Our model outperforms baselines on top- k recognition accuracy and temporal localization (mIoU).

Method	Recognition			Localization
	Acc @ 1	Acc @ 5	Acc @ 10	mIoU
Random	1.00	5.00	10.00	0.1975
Frozen features				
Clip4Clip [24]	8.60	19.67	28.60	n/a
SemanticMoments [17]	9.22	21.73	29.40	n/a
Fine-tuned features				
GestSync [15]	10.05	22.37	33.18	0.5174
JEGAL [16]	11.12	24.41	33.89	<u>0.5471</u>
SOTA VLMs				
Gemini [13]	<u>14.36</u>	<u>30.00</u>	<u>41.72</u>	0.4179
Ours	18.57	37.51	52.16	0.6643

reliability for generating pseudo-labels, we report its accuracy specifically on high-confidence predictions ($p_{sem} \geq 0.9$).

Results: Table 4 demonstrates that our model outperforms baseline methods across the board. Notably, it excels at high-confidence prediction, confirming that utilizing a ≥ 0.9 threshold effectively isolates semantic gestures in unlabeled data with minimal label noise.

Is the semantic classifier word-class agnostic? We evaluate this aspect by creating a test set with unseen words. Specifically, we manually annotate 500 more clips with binary labels indicating whether the clips contain a semantic gesture or not. We ensure that these clips do not contain any words that are present in the GRW dataset. We measure semantic class accuracy at high confidence thresholds for both our model and Gemini, which comes out to be 85.1% and 63.78% respectively. This indicates that our model generalizes across word classes and can be used for large-scale semantic gesture mining in future works.

7.2 Word Recognition and Localization

Metrics: We report top- k accuracy for recognition on the unseen test set of 100 word classes, for $k \in \{1, 5, 10\}$. For localization, we report mIOU to measure the overlap between the ground-truth and predicted gesture segment.

Results: Table 5 shows the word recognition and localization results. We clearly see that we outperform all the baselines for both the tasks by a large margin. Gemini is particularly weaker for fine-grained frame-level tasks like localization. We also note that Acc @ 5 is more indicative of the model’s performance due to the ambiguity between the classes, e.g. (bye, hello), (little, less, few) are gestured in a similar manner. We also provide qualitative results in Fig 7.

Generalization to other datasets. We also evaluate on the AVS-Spot benchmark [16], which contains 500 samples with approximate temporal boundary annotations. The goal is to localize the semantic gesture in time, and the prediction is treated as correct if the predicted gesture segment has any overlap with the ground-truth segment. We obtain the gesture timestamps from our model’s localization head, and compare the semantic gesture spotting accuracy directly with JEGAL [16]. We achieve an accuracy of **79.8%** compared to JEGAL’s 63.6%, which is a significant improvement on an existing gesture benchmark.



Fig. 7: We visualize sample predictions for joint word recognition and localization. In both instances, our model correctly assigns the target word (together, bye) and closely matches the ground truth temporal bounds. Notably, the right example illustrates our model’s ability to accurately localize anticipatory gestures that occur well before the corresponding speech is uttered.

Table 6: Providing a temporal context of 10s (250 frames) to make a prediction for a 4s (100 frames) target interval improves the accuracy by 5.3%.

	100 frames	150 frames	200 frames	250 frames	300 frames
High-conf Acc. (%)	86.29	89.11	90.10	91.62	91.05

7.3 Ablation Studies

Impact of context length. For the semantic classification task, our approach processes a much longer context to judge a short clip for the presence of a semantic gesture. In Table 6, we show that providing a temporal context of 10s to make a prediction for a 4s target segment improves the accuracy by 5.3%.

Impact of pre-training. In Table 7, we show that pre-training on the noisy pre-train set improves the recognition and localization performance. There is also a clear benefit of using manually verified labels. Interestingly, using zero manual labels for recognition and localization already gives decent scores across the board, hinting that large-scale weakly supervised pre-training can be a viable approach for these tasks.

Table 7: Pre-training before fine-tuning on the clean train set gives a clear performance improvement across all the metrics.

Method	Recognition			Localization mIoU
	Acc @ 1	Acc @ 5	Acc @ 10	
Train using Pre-train	12.51	25.61	37.11	0.5617
Train using Clean	16.32	35.87	50.40	0.6373
Pre-train + FT on clean	18.57	37.51	52.16	0.6643

8 Conclusion

We introduced the GRW dataset, providing a large-scale benchmark for analysing, and training and evaluating models for in-the-wild co-speech gestures. We study the temporal offsets between speech and gestures, and also propose new models for three downstream gesture tasks using the dataset. We acknowledge, however, that our findings are conditioned on the nature of our source material – since GRW is derived from public-facing discourse such as lectures, talk shows, and interviews, the observed behaviors may reflect a specific register of formal communication. The gesture patterns may be slightly different in social settings or private conversations [6]. Despite this caveat, GRW represents a significant leap

in scale and annotation granularity over existing benchmarks, enabling models to associate semantic gestures with spoken words.

Acknowledgements. The authors would like to thank Taein Kwon, Piyush Bagad, Jaesung Hugh, and Paul Engstler for their valuable discussions. The authors also extend their thanks to Abhishek Dutta, Prasanna Sridhar and David Pinto for setting up the data annotation tool and to Ashish Thandavan for his support with the infrastructure. This research is funded by EPSRC Programme Grant VisualAI EP/T028572/1 and a Royal Society Research Professorship RSRP\R\241003. Sindhu is supported by a Google PhD Fellowship.

References

1. Agrawal, V., Akinyemi, A., Alvero, K., Behrooz, M., Buffalini, J., Carlucci, F.M., Chen, J., Chen, J., Chen, Z., Cheng, S., et al.: Seamless interaction: Dyadic audio-visual motion modeling and large-scale dataset. arXiv preprint arXiv:2506.22554 (2025)
2. Ahuja, C., Lee, D.W., Ishii, R., Morency, L.P.: No gestures left behind: Learning relationships between spoken language and freeform gestures. In: Findings of the association for computational linguistics: EMNLP 2020. pp. 1884–1895 (2020)
3. Albanie, S., Varol, G., Momeni, L., Bull, H., Afouras, T., Chowdhury, H., Fox, N., Woll, B., Cooper, R., McParland, A., Zisserman, A.: BOBSL: BBC-Oxford British Sign Language Dataset. arXiv (2021)
4. Alexanderson, S., Henter, G.E., Kucherenko, T., Beskow, J.: Style-controllable speech-driven gesture synthesis using normalising flows **39**(2), 487–496 (2020)
5. Ao, T., Gao, Q., Lou, Y., Chen, B., Liu, L.: Rhythmic gesticulator: Rhythm-aware co-speech gesture synthesis with hierarchical neural embeddings. ACM Transactions on Graphics (TOG) **41**(6), 1–19 (2022)
6. Bavelas, J.B., Chovil, N., Coates, L., Roe, L.: Gestures specialized for dialogue. Personality and social psychology bulletin **21**(4), 394–405 (1995)
7. Duarte, A., Palaskar, S., Ventura, L., Ghadiyaram, D., DeHaan, K., Metze, F., Torres, J., Giro-i Nieto, X.: How2sign: a large-scale multimodal dataset for continuous american sign language. In: Proceedings of the IEEE/CVF conference on computer vision and pattern recognition. pp. 2735–2744 (2021)
8. Dutta, A., Zisserman, A.: The VIA annotation software for images, audio and video. In: Proceedings of the 27th ACM International Conference on Multimedia. MM ’19, ACM, New York, NY, USA (2019). <https://doi.org/10.1145/3343031.3350535>, <https://doi.org/10.1145/3343031.3350535>
9. Ephrat, A., Mosseri, I., Lang, O., Dekel, T., Wilson, K., Hassidim, A., Freeman, W.T., Rubinstein, M.: Looking to listen at the cocktail party: a speaker-independent audio-visual model for speech separation. ACM Transactions on Graphics (TOG) **37**(4), 1–11 (2018)
10. Ferstl, Y., McDonnell, R.: Investigating the use of recurrent motion modelling for speech gesture generation. In: Proceedings of the 18th international conference on intelligent virtual agents. pp. 93–98 (2018)
11. Ferstl, Y., Neff, M., McDonnell, R.: Expressgesture: Expressive gesture generation from speech through database matching. Computer Animation and Virtual Worlds **32**(3-4), e2016 (2021)

12. Ginosar, S., Bar, A., Kohavi, G., Chan, C., Owens, A., Malik, J.: Learning individual styles of conversational gesture. In: Proceedings of the IEEE/CVF conference on computer vision and pattern recognition. pp. 3497–3506 (2019)
13. Google: Gemini 3. <https://blog.google/products-and-platforms/products/gemini/gemini-3/> (2026), accessed: 2026-03-06
14. Gueuwou, S., Du, X., Shakhnarovich, G., Livescu, K., Liu, A.H.: Shubert: Self-supervised sign language representation learning via multi-stream cluster prediction. In: Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers) (2025)
15. Hegde, S., Zisserman, A.: Gestsync: Determining who is speaking without a talking head. In: BMVC (2023)
16. Hegde, S.B., Prajwal, K., Kwon, T., Zisserman, A.: Understanding co-speech gestures in-the-wild. In: Proceedings of the IEEE/CVF International Conference on Computer Vision. pp. 9977–9987 (2025)
17. Huberman, S., Goldberg, K., Patashnik, O., Benaim, S., Mokady, R.: Semanticmoments: Training-free motion similarity via third moment features. arXiv preprint arXiv:2602.09146 (2026)
18. Köpüklü, O., Gunduz, A., Kose, N., Rigoll, G.: Real-time hand gesture detection and classification using convolutional neural networks. In: 2019 14th IEEE international conference on automatic face & gesture recognition (FG 2019). IEEE (2019)
19. Lee, G., Deng, Z., Ma, S., Shiratori, T., Srinivasa, S.S., Sheikh, Y.: Talking with hands 16.2 m: A large-scale dataset of synchronized body-finger motion and audio for conversational motion analysis and synthesis. In: Proceedings of the IEEE/CVF International Conference on Computer Vision. pp. 763–772 (2019)
20. Li, D., Rodriguez, C., Yu, X., Li, H.: Word-level deep sign language recognition from video: A new large-scale dataset and methods comparison. In: Proceedings of the IEEE/CVF winter conference on applications of computer vision. pp. 1459–1469 (2020)
21. Lin, B., Ye, Y., Zhu, B., Cui, J., Ning, M., Jin, P., Yuan, L.: Video-llava: Learning united visual representation by alignment before projection. In: Proceedings of the 2024 conference on empirical methods in natural language processing. pp. 5971–5984 (2024)
22. Liu, H., Zhu, Z., Iwamoto, N., Peng, Y., Li, Z., Zhou, Y., Bozkurt, E., Zheng, B.: Beat: A large-scale semantic and emotional multi-modal dataset for conversational gestures synthesis. In: European conference on computer vision. pp. 612–630. Springer (2022)
23. Lugaresi, C., Tang, J., Nash, H., McClanahan, C., Uboweja, E., Hays, M., Zhang, F., Chang, C.L., Yong, M.G., Lee, J., et al.: Mediapipe: A framework for building perception pipelines. arXiv preprint arXiv:1906.08172 (2019)
24. Luo, H., Ji, L., Zhong, M., Chen, Y., Lei, W., Duan, N., Li, T.: Clip4clip: An empirical study of clip for end to end video clip retrieval and captioning. *Neurocomputing* **508**, 293–304 (2022)
25. Materzynska, J., Berger, G., Bax, I., Memisevic, R.: The jester dataset: A large-scale video dataset of human gestures. In: Proceedings of the IEEE/CVF international conference on computer vision workshops (2019)
26. Molchanov, P., Yang, X., Gupta, S., Kim, K., Tyree, S., Kautz, J.: Online detection and classification of dynamic hand gestures with recurrent 3d convolutional neural network. In: Proceedings of the IEEE conference on computer vision and pattern recognition. pp. 4207–4215 (2016)

27. Mughal, M.H., Dabral, R., Habibie, I., Donatelli, L., Habermann, M., Theobalt, C.: ConvoFusion: Multi-modal conversational diffusion for co-speech gesture synthesis. In: Proceedings of the IEEE/CVF conference on computer vision and pattern recognition. pp. 1388–1398 (2024)
28. Nyatsanga, S., Kucherenko, T., Ahuja, C., Henter, G.E., Neff, M.: A comprehensive review of data-driven co-speech gesture generation **42**(2), 569–596 (2023)
29. Prajwal, K., Hegde, S., Zisserman, A.: Scaling multilingual visual speech recognition. In: ICASSP 2025-2025 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). pp. 1–5. IEEE (2025)
30. Quiros, L.C., Tax, D.M.J., Hung, H.: Gestures in-the-wild: Detecting conversational hand gestures in crowded scenes using a multimodal fusion of bags of video trajectories and body worn acceleration. *IEEE Trans. Multim.* **22**(1), 138–147 (2020). <https://doi.org/10.1109/TMM.2019.2922122>, <https://doi.org/10.1109/TMM.2019.2922122>
31. Su, J., Lu, Y., Pan, S., Wen, B., Liu, Y.: Roformer: Enhanced transformer with rotary position embedding. *CoRR* **abs/2104.09864** (2021), <https://arxiv.org/abs/2104.09864>
32. Uthus, D., Tanzer, G., Georg, M.: Youtube-asl: A large-scale, open-domain american sign language-english parallel corpus. *Advances in Neural Information Processing Systems* pp. 29029–29047 (2023)
33. Wan, J., Zhao, Y., Zhou, S., Guyon, I., Escalera, S., Li, S.Z.: Chalearn looking at people rgb-d isolated and continuous datasets for gesture recognition. In: Proceedings of the IEEE conference on computer vision and pattern recognition workshops. pp. 56–64 (2016)
34. Wang, C.Y., Yeh, I.H., Mark Liao, H.Y.: Yolov9: Learning what you want to learn using programmable gradient information. In: European conference on computer vision. pp. 1–21. Springer (2024)
35. Wang, Y., Li, K., Li, Y., He, Y., Huang, B., Zhao, Z., Yin, H., Chen, J., Jin, T., Wu, J., et al.: Internvideo2: Scaling video foundation models for multimodal video understanding. In: European Conference on Computer Vision. Springer (2024)
36. Zhang, Y., Cao, C., Cheng, J., Lu, H.: Egogesture: A new dataset and benchmark for egocentric hand gesture recognition. *IEEE Transactions on Multimedia* pp. 1038–1050 (2018)
37. Zhu, B., Lin, B., Ning, M., Yan, Y., Cui, J., Wang, H., Pang, Y., Jiang, W., Zhang, J., Li, Z., et al.: Languagebind: Extending video-language pretraining to n-modality by language-based semantic alignment. *arXiv preprint arXiv:2310.01852* (2023)

A Dataset

A.1 Data samples

Fig 8 illustrates representative samples from the semantic subset of our manually annotated GRW dataset. The dataset comprises 150 unique words, carefully curated to capture a diverse range of clear, well-defined, and semantically meaningful gestures. Video samples can be found in the supplementary video.

A.2 Dataset bias

Our dataset is derived from MultiVSR [29], which consists primarily of celebrity interviews, television shows, lectures, and conversational videos. While this source provides coverage across a wide range of topics and speaking styles, it may nevertheless introduce inherent biases. For instance, the distribution of speakers, settings, and interaction contexts may not be representative of the broader population. Gestural behavior in media settings, such as interviews or staged discussions, can differ from spontaneous, everyday communication, potentially influencing the types and frequency of gestures captured in the dataset. Moreover, all videos in GRW are in English. As a result, the dataset predominantly reflects gesture patterns of English-speaking individuals, many of whom may share similar cultural norms. These factors should be considered when interpreting results and analysis made on the GRW dataset.

B Annotation

We provide additional details on the annotation process below.

B.1 Obtaining candidate words

The following is the prompt provided to Gemini, together with a list of highly frequent words in the dataset that need to be scored on how likely they are to induce a semantic gesture.



Fig.8: Data samples from the GRW dataset. The dataset encompasses a diverse vocabulary of 150 conceptual words, ranging from numbers (‘two’) and spatial descriptors (‘little’, ‘back’) to physical actions (‘grasp’, ‘stack’) and conversational anchors (‘hello’). For each positive instance, we provide precise, frame-accurate temporal boundaries marking the start and end of the semantic gesture (highlighted by the green outlines), distinguishing the meaning-bearing motion from surrounding frames.

Prompt to obtain our dataset lexicon

Role: You are an expert linguist and researcher specializing in human co-speech gesture understanding and multimodal communication.

Task: You will be provided with a plain text file containing a list of English lemmas (one per line). Your objective is to evaluate each word’s “gesturability”: the likelihood that a speaker will naturally induce a visually depictive, semantic co-speech gesture when uttering this word in unconstrained, natural discourse.

Definitions to apply:

- **Iconic:** Gestures that physically depict the shape, size, or action of the target word (e.g., drawing a circle in the air for “round”).
- **Metaphoric:** Gestures that represent abstract concepts as physical objects or spaces (e.g., moving hands forward to represent the “future”, or moving hands apart to show “difference”).
- **Deictic:** Gestures that point to spatial locations, objects, or people (e.g., pointing down for “here”, or pointing outward for “them”).
- **Beat / Non-Semantic:** Rhythmic hand motions that align with speech prosody but carry no visual meaning. Words that primarily elicit beat gestures should be heavily penalized in your scoring.

Instructions for each word:

1. **Score (1-5):** Assign a Gesturability Score from 1 to 5.
 - 1 = Almost never accompanied by a semantic gesture (mostly beat or no gesture).
 - 5 = Highly likely to consistently elicit a distinct, semantic gesture.
2. **Categorize:** Identify the primary gesture type it induces (Iconic, Metaphoric, or Deictic). If the score is 1 or 2, output “Beat/None”.
3. **Pattern:** Provide a short, 2-to-5 word phrase describing the core kinematic motion. (Write “N/A” if Beat/None).
4. **Description:** Provide a detailed 1-to-2 sentence explanation of how the hands/body physically move to convey the word’s semantics. (Write “N/A” if Beat/None).

Output Format: Provide the results strictly in comma-separated values (CSV) format. Do not include any introductory or concluding text outside of the CSV. You must enclose the Pattern and Description fields in double quotes to prevent internal commas from breaking the CSV structure.

Use the following header row:

Word,Gesturability Score,Gesture Category,Kinematic Pattern,Detailed Description

Examples of expected output:

"big",5,"Iconic","Hands move outward","The speaker typically starts with hands held neutrally and pushes the palms outward laterally to physically demonstrate a large spatial volume."
 "however",1,"Beat/None","N/A","N/A"

B.2 Pre-processing for stable gesture crops

MultiVSR [29] metadata provides the temporal boundaries of relevant speech segments. Unlike rigid face tracking, upper-body bounding boxes vary drastically with gesture articulation (e.g., wide arm movements). Consequently, standard frame-by-frame cropping and resizing introduces severe aspect-ratio fluctuations and motion jitter. To address this, we design a stabilization pipeline to preserve true gesture dynamics. For each segment, we extract temporally consistent person tracks using YOLOv9 [34] and an IoU-based greedy tracker. To prevent jitter, rather than cropping frames independently, we compute a single global crop per track from the aggregated bounding boxes and apply it uniformly. Since detections may include full bodies, we apply a leg-visibility heuristic to remove lower-body regions, yielding temporally stable, upper-body crops.

B.3 Word recognition annotation

The goal of this annotation is to obtain semantic vs. non-semantic labels for word clips. The input to the annotators is a set of 161,828 candidate clips, where a clip is a 4-second video containing the target word. We recruit annotators and train them using curated examples and detailed written guidelines. A central instruction is to adopt a “conservative positive labeling” strategy:

- Mark a sample as *Good* only if there is a **clearly identifiable gesture that depicts the target word** in a way that would be recognizable even without audio.
- Mark beat and random gestures without depictive content as *Bad*.
- Mark gestures that are ambiguous, off-screen, or unrelated to the target word as *Bad*.

We develop a custom in-house annotation interface built on VIA [8]. Fig 9 shows a sample page from the word recognition annotation tool. Each page contains up to 100 samples arranged in a grid format, and there may be multiple pages for each word depending on the total number of instances. Each clip loops continuously, and audio playback is triggered on hover to facilitate inspection of the spoken context. By default, all clips are initialized as *Bad* to minimize errors in the semantic annotations. Annotators assign a binary label indicating whether the target word is accompanied by a semantically meaningful gesture in the clip.

B.4 Word localization annotation

The input to this stage consists of the set of clips labeled as semantic gestures during the preceding recognition annotation. Specifically, we obtain 19,195 clips marked as *Good*, which are known to contain semantic gestures and are passed to the localization stage. The annotators’ task is to identify the temporal boundaries of the gesture by marking its start and end times. This task is more challenging than recognition, as it requires careful inspection of the entire clip, often through repeated viewing, to precisely determine the gesture boundaries corresponding to the target word. The instructions given to the annotators are as follows:

- The start time should capture the moment just before the gesture begins (i.e., when the speaker leaves the rest position) or transitions from a previous gesture.
- The end time should correspond to the point at which the gesture is fully completed, either when the speaker returns to rest or transitions into another gesture.

We customize the annotation interface based on VIA [8]. A sample annotation page is shown in Fig 10. Each page displays a single video clip, allowing annotators to replay it multiple times, zoom in for clearer visual inspection, and adjust the playback speed as needed.

We obtain 17,473 video clips as the output of the localization annotation, which constitute the semantic subset of the GRW dataset. To ensure data quality, all clips in this set are independently reviewed and validated by one of the authors.




Fig.9: Stage-1: Semantic Gesture Annotation Interface. We developed a custom web-based tool built upon the VIA framework to efficiently collect binary labels. For a given target word (e.g., ‘together’, shown at the top left), annotators are presented with a grid of candidate video clips. Annotators can play the audio and video for each clip, subsequently selecting “Good” if a clear, visually depictive semantic gesture is present, or “Bad” if the motion is non-semantic or absent. Hovering over each video also plays the audio as well, further assisting the annotator to judge and assign the correct label. After this stage, we obtain the set of semantic clips, and also the word label for each of the semantic clips.

B.5 Annotator details

We hired a total of 40 annotators through a professional annotation company. Prior to beginning the task, all annotators completed mandatory training sessions designed to familiarize them with the annotation guidelines, task objectives, and quality expectations. To ensure a consistent understanding of the criteria, annotators were required to complete a set of qualification test cases, which were reviewed before granting access to the full dataset. Throughout the annotation process, quality was monitored through periodic checks and feedback. All annotators were compensated at rates above the industry average to ensure fair pay and to promote careful, high-quality work.




Fig. 10: Stage-2: Temporal Boundary Annotation Interface. Using an adapted VIA interface, annotators precisely localize the start and end frames of a semantic gesture. For clips verified as positive in Stage-1, annotators utilize fine-grained playback speed controls and a draggable timeline to define the exact temporal envelope of the physical movement (e.g., localizing the gesture for the word ‘four’ as shown here by the orange block). The interface pre-populates the temporal boundaries based on speech-timestamps for the target word, allowing annotators to subsequently adjust them to match the observed gesture after reviewing the video.

C Model Details

We provide more details on the proposed models and the training configuration.

C.1 Details on SHuBERT

As discussed in Section 6.1 of the main paper, SHuBERT [14] serves as the gesture backbone. Given an input video $V \in \mathbb{R}^{T \times H \times W \times 3}$, the left and right hands are cropped and processed using a DINO-v2 encoder fine-tuned on hand data and subsequently frozen, producing per-frame features of size $T \times 384$ for each hand. In parallel, body keypoints are extracted to obtain a $T \times 14$ representation. SHuBERT can additionally incorporate facial features when available; however, in our setup, facial cues are omitted to focus exclusively on hand-driven information. The modality-specific features are independently projected to a shared space, concatenated, and further projected to $T \times 768$ before being fed into a 12-layer Transformer encoder, whose contextualized outputs constitute our final gesture backbone features, $f_{\text{multi}} \in \mathbb{R}^{L \times T \times d_{in}}$, where $L = 12$, $d_{in} = 768$.

The next step in our setup is to aggregate the 12 Transformer layers from f_{multi} to obtain a unified representation $f \in \mathbb{R}^{T \times d_{in}}$. Several strategies can be considered for this aggregation: (i) using only the final layer’s output, (ii) averaging representations across all layers, or (iii) learning a weighted combination of the layer-wise features. Empirically, we found the third approach to yield the best performance. Specifically, we have a fully-connected layer that inputs d_{in} -dimensional feature vectors of $f_{\text{multi}} \in \mathbb{R}^{L \times T \times d_{in}}$ and outputs a scalar for each of the feature vector: $\mathbb{R}^{L \times T \times 1}$. We get per-layer scores after averaging the feature-level scalars across the temporal dimension T : $\mathbb{R}^{L \times 1}$. These layer-wise scores are softmax-normalized over L , and a weighted sum across the layers to reduce $f_{\text{multi}} \in \mathbb{R}^{L \times T \times d_{in}}$ to $f \in \mathbb{R}^{T \times d_{in}}$.

C.2 Architecture

In Table 8, we provide detailed architecture description for our two models: (i) semantic classification and (ii) word recognition and localization. The code and trained models will be released to support future research.

C.3 Training hyper-parameters

All our models are implemented in PyTorch. We train both models until validation loss does not improve for 5 epochs. The hyper-parameters for each of the individual models are stated below.

Semantic gesture classification. We use 3 transformer encoder layers and 3 transformer decoder layers. We use an initial learning rate of $1e^{-4}$ and decrease it by a factor of 5 every time the validation loss plateaus for 2 epochs. Since the data is heavily class imbalanced (15,473 positive semantic gesture samples and

Table 8: Detailed Architectural Specifications. Layer-by-layer breakdown of the input and output tensor shapes for our two proposed task-specific models. Notation: T represents the number of frames in the extended temporal context, l denotes the number of frames in the shorter query interval (target clip), L is the number of intermediate hidden layers extracted from the pre-trained gesture backbone, and N is the total number of semantic word classes for the recognition task. Both models process 224×224 spatial RGB crops and project backbone features to a Transformer hidden dimension (d_{model}) of 512.

Model	Layer/Module	Input Shape	Output Shape
Semantic Classification			
	Gesture backbone	$3 \times T \times 224 \times 224$	$L \times T \times 768$
	Layerwise feature aggregation	$L \times T \times 768$	$T \times 768$
	Projection MLP		
	- Linear	$T \times 768$	$T \times 512$
	- LayerNorm	$T \times 512$	$T \times 512$
	- ReLU	$T \times 512$	$T \times 512$
	- Linear	$T \times 512$	$T \times 512$
	Transformer Encoder		
	- Self-Attention	$T \times 512$	$T \times 512$
	- Feed Forward	$T \times 512$	$T \times 512$
	Transformer Decoder		
	- Self-Attention	$l \times 512$	$l \times 512$
	- Cross-Attention	$l \times 512 \mid T \times 512$	$l \times 512$
	- Feed Forward	$l \times 512$	$l \times 512$
	Binary Classification		
	- Mean Pooling	$l \times 512$	512
	- Output Projection	512	512
	- Classification	512	1
Word Recognition and Localization			
	Gesture backbone	$3 \times l \times 224 \times 224$	$L \times l \times 768$
	Layerwise feature aggregation	$L \times l \times 768$	$l \times 768$
	Projection MLP		
	- Linear	$l \times 768$	$l \times 512$
	- LayerNorm	$l \times 512$	$l \times 512$
	- ReLU	$l \times 512$	$l \times 512$
	- Linear	$l \times 512$	$l \times 512$
	Transformer Encoder		
	- Self-Attention	$l \times 512$	$l \times 512$
	- Feed Forward	$l \times 512$	$l \times 512$
	Classification Head		
	- Mean Pooling	$l \times 512$	512
	- Output Projection	512	512
	- Classification	512	N
	Localization Head		
	- MLP	$l \times 512$	$l \times 512$
	- Localization	$l \times 512$	l

137, 215 negative samples), we use class-balanced sampling to upsample positive class data in each batch, and additionally apply a class-weighting to the loss (assigns higher weight to positive samples). We also apply the following feature-level temporal augmentation during training: (i) dropping frames, (ii) shifting frames, and (iii) changing the speed of video by interpolating frames. We use a batch size of 128 and train the model with AdamW optimizer on a single GPU.

Word recognition and localization. We use 6 transformer encoder layers. We use an initial learning rate of $1e^{-4}$ and decrease it by a factor of 5 every time the validation loss plateaus for 2 epochs. We use a batch size of 128 and train the model with AdamW optimizer on a single GPU.

D Gemini Prompts for Evalutation

We provide detailed prompts that are used to evaluate Gemini-3 on the gesture tasks. We run the following prompts for all the samples in our test set for the both the tasks.

Prompt for Semantic Gesture Classification

Role: You are an expert in gesture recognition.

Task: Analyze the provided short video clip and determine whether the person makes a clear iconic / deictic / metaphoric hand gesture.

Guidelines:

- Focus only on hand movements, shapes, and orientation changes. Ignore body posture, facial expressions, or background.
- A gesture may occur anytime in the duration of the input video.
- Random continuous hand movements or beat gestures cannot be considered as “Good”.
- If there is no clear hand gesture present in the full video, output “No gesture found”.
- Be precise and confident only if the gesture is clear and is depictive of a word. Example: arms widening to indicate “massive”, hands moving in a circular manner to indicate “round”.

Steps to Follow:

- Carefully examine the hand movements throughout the video.
- Check if any movement could potentially strongly correspond to semantic gestures, i.e., iconic / deictic / metaphoric gestures.
- The following are different possibilities:
 1. No semantic gestures present in the video.
 2. Semantic gesture may be present, but is not clear and/or is not fully visible.
 3. Semantic gesture present, and is clearly visible.
- Make a decision: “Yes” (gesture found) or “No” (gesture not found). The decision will be “Yes” only if category 3 occurs as explained above.
- Give the confidence score between 0 and 1, 0 being the least confident and 1 being the most confident.
- Provide a short reasoning.

Output Format:

Gesture present: <Yes or No>

Confidence: <0.0 to 1.0>

Reasoning: <Brief explanation of the decision>

Prompt for Word Recognition and Localization

Role: You are an expert in gesture recognition and localization.

Task: You will be given a short video clip with a person speaking. Your job is to:

1. Analyze all the frames of the video together and produce one final gesture description that best represents what the hands are gesturing throughout these frames.
2. Based on the description, rank a given set of 100 possible word classes with confidence scores (between 0 and 1) such that they sum to approximately 1.0.
3. Predict the start and end time of the gesture in seconds (gesture boundary) for the recognized target word.

Classes: bye, below, push, move, direction, specific, together, whole, hello, straight, above, switch, five, turn, expand, throw, open, huge, raise, large, tiny, long, mix, circle, no, two, three, entire, top, four, lower, full, press, small, grab, grow, separate, wrap, wide, roll, block, combine, high, big, round, increase, flip, force, close, develop, lift, narrow, hold, broad, connect, begin, global, build, reduce, process, spin, front, focus, cross, layer, count, wave, curve, short, shake, loop, height, strong, stop, us, run, little, stretch, track, zoom, condense, evolve, around, interaction, twist, transition, back, less, walk, absorb, quick, bottom, her, descend, peak, join, perfect, transform, decrease, stack.

Step 1: Gesture Description Guidelines

- Look at the hand shapes, positions, and movement across the frames.
- Focus only on hand gestures, ignore background or person details (e.g., clothing, gender, facial expressions).
- Summarize the gesture as a single concise description, not frame-by-frame.
- If the gesture evolves across frames, capture that motion pattern in the final description (e.g., “raising hand then pointing forward”).
- If uncertain, provide the most plausible interpretation based on the sequence.
- Use short, clear, natural language (e.g., “hands forming a circle”, “index finger pointing to the right”).

Step 2: Gesture Recognition Guidelines

- Carefully analyze the gesture description and reason about its likely meaning.
- Assign a confidence score between 0 and 1 for each of the 100 classes based on how likely it matches the gesture.
- The most likely class gets the highest confidence, followed by others in descending order.
- If none of the classes match perfectly, rank and distribute class-wise probabilities regardless.
- Ensure the sum of all confidence scores approximately equals 1.0.

Step 3: Gesture Localization Guidelines

- Carefully analyze the gesture description and the output top recognized word (top-confident word above).
- Focus only on this target word, this is the word to be localized.
- Determine the start time when the gesture for this particular target word begins (e.g., hand moves or shapes start forming) or transitions from a previous gesture. The start time should capture the moment just before the gesture begins (i.e., when the speaker leaves the rest position).
- Determine the end time when the gesture for this particular target word completes (e.g., hand returns to neutral or stops moving). The end time can either be when the speaker returns to rest position or transitions into another gesture.

Output Format:

Gesture description: <final description>

Ranked classes with confidence:

```
{
<class-1> - <confidence>
<class-2> - <confidence>
...
<class-100> - <confidence>
}
```

Gesture start: <start time in seconds>

Gesture end: <end time in seconds>

Localization confidence: <0.0 to 1.0>

E Failure cases

An analysis of the word recognition model’s failure modes highlights the natural ambiguity of human co-speech gesticulation. As illustrated in Fig. 11, misclassifications typically occur between words that share nearly identical physical expressions. Rather than producing random predictions, the model often selects valid synonyms, such as predicting “raise” instead of “peak”, or “tiny” instead of “little”. These semantically related predictions demonstrate that the model successfully captures the underlying visual meaning, even if it misses the exact lexical ground truth. This also underscores why top- k metrics, where $k = 5, 10$ are essential for evaluating unconstrained gesture recognition.



Fig. 11: Analysis of typical failure cases. The word recognition model occasionally misclassifies gestures into semantically and visually synonymous categories. **(Top)** The model predicts “raise” instead of the ground-truth “peak” as the speaker moves his hand upward. **(Bottom)** A classic finger-pinching motion results in a prediction of “tiny” rather than the ground-truth “little”. These examples highlight the inherent ambiguity in word-level gesture recognition, where different lexical items share nearly identical physical expressions.