

CoFiDA-M: Concept-Aware Feature Modulation for Cross-Domain Adaptation with Image-Only Inference

Nurjahan Sultana, Moi Hoon Yap, Xinqi Fan, Wenqi Lu[†]

Department of Computing and Mathematics, Manchester Metropolitan University
Dalton Building, Chester Street, M1 5GD Manchester, UK

nurjahan.sultana@stu.mmu.ac.uk; {m.yap, x.fan, w.lu}@mmu.ac.uk

Abstract

Models for AI-based skin cancer screening suffer a severe performance drop when shifting from expert dermoscopic (source) images to consumer-grade clinical (target) images, hindering real-world deployment. Existing domain adaptation methods often ignore crucial semantic invariants, such as clinical concepts. While new foundation models like MONET can provide this semantic information as dense, probabilistic scores, this metadata is unavailable at test time, creating a deployment paradox for practical image-only screening tools. We address this gap by proposing CoFiDA-M, a privileged information framework that learns from concepts at training time but deploys as an image-only model. Our method trains a teacher network that uses MONET concept probabilities to guide a FiLM modulator, transforming visual features into a semantically “edited” feature space. A lightweight, image-only student is then trained to reproduce this edited representation, not just the teacher’s final predictions. This distillation “bakes” the clinical reasoning into the student’s weights. On a challenging multi-dataset benchmark, our image-only student significantly outperforms state-of-the-art approaches, especially in melanoma recall. Our work provides a practical and generalizable framework for leveraging noisy, probabilistic metadata as privileged information, demonstrating strong cross-dataset robustness and potential for real-world deployment beyond dermatology. Implementation code is available at [GitHub](#).

1. Introduction

The promise of AI for accessible skin cancer screening on mobile phones is hindered by a critical domain shift, as models trained on expert dermoscopic images degrade sharply on clinical smartphone photos [3, 29, 35]. This is not a static gap that can be solved by simply adding more




Figure 1. CoFiDA-M resolves the *Deployment Paradox*: metadata are available at training but absent in the real world. A concept-guided teacher trained with noisy metadata transfers its reasoning to an image-only student that generalizes to unseen clinical data.

clinical images to the training set. Every new camera, lighting condition, and patient population effectively behaves as a novel domain, causing models to fail when encountering these unseen variations [23, 28]. For AI to be reliably deployed in the wild, it must learn domain invariant features ensuring robust performance across all target distributions.

To bridge this domain gap, Unsupervised Domain Adaptation (UDA) methods aim to adapt a model from a labeled source domain to an unlabeled target domain. Many classical approaches achieve this by forcing the source and target feature distributions to become indistinguishable, often by using adversarial training [11] or directly matching statistical moments like covariance [30] and the maximum mean discrepancy [12] across multiple layers. The shared goal of these methods is to learn a single, unified feature space for both source and target data.

However, in high stakes medical domains, this global alignment is often insufficient. It ignores crucial semantic invariants, high level clinical concepts that are shared across domains even when the low level pixel data differs. A clinical concept like ‘ulceration’ or a ‘pigment network’ remains the same, whether viewed in a dermoscopic image or a standard clinical photo. A model that aligns domains based on these shared medical concepts would be more robust and interpretable than one that simply matches global statistics. This aligns with findings in multimodal medical AI, where

[†]Corresponding author: w.lu@mmu.ac.uk

This is the arXiv version of a paper accepted to CVPR 2026.

grounding models in clinical knowledge and concepts, as seen in MedCLIP [37] or PanDerm [39], has proven critical for building robust systems.

Recent research has increasingly utilized language and high-level conceptual information to inform and guide the adaptation process, as exemplified by the PØDA framework [9], which shows that a simple text prompt (“driving at night”) can steer features to adapt to a new, unseen domain in a zero-shot fashion. LAGUNA [7] takes this further by using language to align the relative geometry of the class structure between domains, rather than forcing an absolute feature overlap. While powerful, these methods have limitations, i.e., PØDA is designed for text prompted zero shot transfer, and LAGUNA critically relies on having text captions available for the target domain during adaptation [7]. In dermatology, concept-based models such as MAKE [38] inject structured expert clinical knowledge during pre-training to enable zero shot lesion recognition, but they do not solve unsupervised domain adaptation between dermoscopic and clinical images. This gap is particularly acute in specialized fields like medicine, where recent tools like MONET [15], a foundation model grounded in medical literature, can now provide dense, probabilistic scores for high level concepts (e.g., ‘ulceration’, ‘pigmentation’). Such fine grained, probabilistic metadata offers a much richer supervisory signal than simple text prompts, but has been largely overlooked by domain adaptation research, likely due to its prior unavailability. The availability of such rich metadata, however, gives rise to a deployment paradox. Although these detailed annotations can enhance model performance during training, the ultimate goal of accessible mobile screening necessitates a simple, image-only model, since patients cannot supply expert-level metadata at inference time. Consequently, a key practical challenge remains. While this problem falls under the Privileged Information (PI) setting recently formalized for UDA by DALUPI [2], its proposed two-stage “hallucination” pipeline is not designed for our specific challenge. How to apply PI effectively in our medical context is not fully addressed. The key challenges are: (1) the concepts are available only during training, (2) the PI is a “messy” and noisy probability vector, not clean text or attributes, and (3) the final model must be a lightweight, image-only model that works on an unlabeled target domain.

To address this specific gap, we introduce CoFiDA-M: Confidence Gated Feature Editing for Domain Adaptation. We propose a teacher-student framework that leverages external concept probabilities (like MONET scores) as privileged information during training, while ensuring the final student model is image-only at inference. Figure 1 illustrates the deployment paradox and a high-level overview of our proposed solution. Our key contributions are:

- We introduce CoFiDA-M, a novel framework that inte-

grates MONET-derived dermatological concepts into a FiLM based modulation mechanism, aligning visual features with semantic clinical context during training.

- We propose a novel distillation scheme where the student learns to match not only the teacher’s final predictions (logits) but also its edited feature, allowing the student to learn the reasoning process, not just the final prediction.
- Unlike previous concept based models that require concept inputs at test time, CoFiDA-M transfers the semantic alignment into a concept-independent student. At inference, only image inputs are required, enabling faster and more practical deployment while maintaining both interpretability and accuracy without concept supervision.
- Our model demonstrates superior generalization and interpretability: validated on a challenging out-of-domain benchmark of six unseen datasets, our image-only student outperforms state-of-the-art methods with significant improvements in AUROC and melanoma recall, while preserving interpretability through the learned concept feature modulation dynamics.

2. Related Work

Recent multimodal domain adaptation leverages language and expert concepts to steer visual representations across shifts. Vision language pre-training (VLP) provides a shared image text space that can be adapted with lightweight prompts, enabling transfer without full target supervision. In medical imaging, this idea appears in general VLMs [17], radiology-specific models like MedCLIP [37], and comprehensive multimodal reasoning systems like MIMO [4]. Dermatology specific resources further strengthen this route by pairing images with rich text and structured clinical descriptors, as seen in the PanDerm foundation model [39] and the MM-Skin/SkinVL dataset [40], improving the zero shot baselines that many Domain Adaptation (DA) pipelines build upon. Standard classification models also show that combining skin lesion images with clinical metadata improves multimodal learning [6, 41].

Building on the use of language, prompt-driven adaptation uses textual cues to shift decision boundaries, “steering” features towards a new domain without target labels. This strategy shows that a global text prompt can deliver zero shot gains under appearance change [9]. More advanced methods use language to align the relative geometry of class structures [7] or learn domain-agnostic representations through mutual text visual prompting [8]. While powerful, these approaches typically require clean text prompts or target domain captions, and do not provide per-image, calibrated evidence to supervise finer, concept level edits.

A complementary line of research conditions the visual pathway directly on concepts or attributes. This approach aligns with the learning using PI paradigm, recently formalized for UDA as DALUPI [2]. This framework lever-

ages auxiliary data (such as concepts) that is available only during training to improve adaptation [2]. However, the method proposed by DALUPI relies on a two-stage pipeline, where one model learns to “hallucinate” the PI ($X \rightarrow W$), and a second model predicts from that hallucination ($W \rightarrow Y$) [2]. In contrast, we propose a more direct and unified strategy. Our CoFiDA-M framework uses the privileged concepts to directly modulate the visual feature space via a FiLM-based teacher network [24]. Critically, we introduce a novel distillation scheme where an image-only student learns to reproduce the teacher’s entire semantically-edited feature representation, rather than just mimicking its final predictions. This conditioning logic is also actively used in contemporary medical VLP, such as in the knowledge enhanced modules of models like MAKE for zero shot dermatology assessment [38].

Beyond multimodal approaches, other UDA methods address alternative data constraints. A prominent direction focuses on Source-Free Domain Adaptation (SFDA), where a pre-trained source model is adapted using only unlabeled target data, a key constraint in medical applications. These approaches often rely on generating pseudo-labels by discovering target class prototypes, as in CPD [42], or by freezing the source classifier and training the feature encoder with information maximization, a method known as “hypothesis transfer” or SHOT [18]. Other SFDA methods adapt from black box APIs by distilling predictions, like DINE [20], or, for segmentation, synthesize source like images by matching the source model’s BatchNorm statistics to enable knowledge transfer (SFDA) [22]. Concurrently, classical UDA methods (which retain access to source data) also continue to evolve, with IT-RUDA [26] aligning source and target features using a robust α -divergence that down-weights outliers and stabilizes transfer under label or sample imbalance [26].

A related setting is Test-Time Adaptation (TTA), where the model adapts during inference as new target data arrives. A widely used consistency framework is the mean-teacher model, which forms a teacher by exponential moving average of the student’s weights and trains the student to match the teacher’s predictions on unlabeled data [32]. The foundational TTA method, TENT [34], minimizes prediction entropy by only updating normalization layer parameters. Building on this, CoTTA [36] addresses adaptation in continually changing environments by using a mean teacher for stable pseudo-labels and stochastically restoring weights to prevent catastrophic forgetting. Complementary to these, the Wisdom-of-Crowds filter retains only samples whose confidence increases relative to the frozen source model, improving robustness under open set and streaming conditions [16].

Our work bridges two strands of multimodal domain adaptation: prompt or language guided transfer [7, 9, 17,

37] and concept conditioned feature editing via lightweight modulation [24, 38]. We train with calibrated clinical concept probabilities to supervise edits in the multimodal teacher and then distil this behavior into an efficient, image-only student for deployment, framing the hand off as knowledge distillation [13]. This directly addresses the common gap between multimodal training signals and unimodal test-time constraints.

3. Methodology

Our proposed CoFiDA-M uses concept probabilities from MONET [15] as PI during training to guide feature editing. The model learns how such concepts reshape the internal representation in a concept-guided teacher, and transfers this ability to an image-only student through distillation, enabling robust generalization without test-time adaptation. As described in Figure 2, the proposed framework consists of three stages:

- Teacher training: a MONET conditioned teacher edits image features via FiLM modulation and is trained with both labeled source and unlabeled target data.
- Knowledge distillation: a student model learns to mimic the teacher’s concept-aware predictions and representations using only image inputs.
- Inference: the distilled student model performs image-only classification.

3.1. Problem Setup

We consider a labeled *source* domain $\mathcal{D}_s = \{(x_s^{(i)}, s_s^{(i)}, y_s^{(i)})\}_{i=1}^{N_s}$ consisting of dermoscopic images $x_s^{(i)} \in \mathbb{R}^{3 \times H \times W}$ together with MONET concept probabilities and binary melanoma labels. The *target* domain $\mathcal{D}_t = \{(x_t^{(j)}, s_t^{(j)})\}_{j=1}^{N_t}$ contains clinical images with associated MONET probabilities but no labels. An EfficientNet-B2 backbone [31] f_θ embeds each image into a $d = 1408$ -dimensional penultimate feature space, $\mathbf{v} = f_\theta(x)$. Our goal is to exploit the labeled source data and the unlabeled target data to train a model that can predict the melanoma label y for target images x_t , while operating with image-only inputs at inference.

3.2. Confidence-Gated MONET Embedding

Each MONET attribute a provides a probability $s_a \in [0, 1]$ representing the likelihood of concept presence. Instead of using s_a directly, we form a two-state probability vector

$$\mathbf{q}_a = \begin{bmatrix} 1 - s_a \\ s_a \end{bmatrix} \in \mathbb{R}^2, \quad (1)$$

which retains information about both concept presence and absence. To reflect uncertainty, we introduce a confidence gate embedding module (CGEM) on Gini impurity [1]

$$g_a = s_a^2 + (1 - s_a)^2, \quad (2)$$




Figure 2. **Overview of the CoFiDA-M Framework.** Our method has three parts. (A) & (B) Stage 1: Teacher Training. A concept-guided Teacher model is trained using labeled source data (A) and unlabeled target data (B). The target branch uses a Mean Teacher framework to align domains via multi-level consistency. (C) Stage 2: Distillation & Stage 3: Inference. The “expert” Teacher is frozen ($\ast$) and its knowledge is distilled ($\mathcal{L}_{distill}$) into a lightweight Image-Only Student, which replaces the FiLM module with a residual edit head and is used for final inference.

so that uncertain concepts ($s_a \approx 0.5$) contribute less. Each concept has a learnable embedding table $\mathbf{E}_a \in \mathbb{R}^{2 \times 32}$, which is gated and projected using its query $\mathbf{q}_a$ and gate g_a . Concatenating these gated concept embeddings and passing them through a two-layer MLP yields the clinical conditioning vector

$$\mathbf{c}_t = \text{MLP}(\text{concat}_a \{ g_a(\mathbf{E}_a^\top \mathbf{q}_a) \}) \in \mathbb{R}^{256}, \quad (3)$$

which summarizes the high-level clinical semantics.

3.3. Concept-Guided Feature Editing (Teacher)

Within the teacher, clinical context from MONET guides the feature-editing operation preceding classification. The context vector $\mathbf{c}_t$ is used to modulate the image feature $\mathbf{v}$ through a Feature wise Linear Modulation (FiLM)[24] based editing network. Specifically, a conditioning function $\psi : \mathbb{R}^{256} \rightarrow \mathbb{R}^{2d}$ is used to predict clinical feature conditioned affine parameters

$$\gamma, \beta = \text{split}(\psi(\mathbf{c}_t)) \quad (4)$$

which are split into two d -dimensional vectors controlling scaling and shifting of $\mathbf{v}$. With these two affine parameters, the clinical edited image feature $\mathbf{u}$

$$\mathbf{u} = \gamma \odot \mathbf{v} + \beta, \quad (5)$$

where $\odot$ denotes element-wise multiplication. This affine modulation allows external clinical concepts to adjust internal activations without modifying the backbone. The edit vector $\mathbf{e}$, which contains clinical representations, can be obtained as $\mathbf{e} = \mathbf{u} - \mathbf{v} \in \mathbb{R}^d$.

A two-layer MLP classifier h then operates on $\mathbf{u}$ to predict logits ℓ , followed by the softmax operation to get class predicted probabilities p

$$\ell = h(\mathbf{u}), \quad p = \text{softmax}(\ell) \in [0, 1]^2. \quad (6)$$

Given confident MONET attributes, the network is designed to learn to amplify feature channels associated with relevant concepts while attenuating others, yielding concept-consistent representations across domains.

3.4. Stage 1: Teacher Training

The teacher network is trained on both labeled source data and unlabeled target data. The training loss combines the supervised loss on the source domain and the consistency-based UDA losses on the target domain

$$\mathcal{L}_{\text{teacher}} = \mathcal{L}_{\text{source}} + \mathcal{L}_{\text{target}} \quad (7)$$

3.4.1. Source Supervision

To address class imbalance and emphasize hard examples, we adopt the focal loss [21] which is a variant of cross-

entropy that down-weights easy, high-confidence samples and places more weight on hard ones.

$$\mathcal{L}_{\text{sup}} = -\frac{1}{|\mathcal{B}|} \sum_{i \in \mathcal{B}} \alpha_{y^{(i)}} (1 - p_{y^{(i)}})^{\gamma_f} \log p_{y^{(i)}} \quad (8)$$

where $\gamma_f = 1.5$ and class weight $\alpha = 0.9$, interpreted as $\alpha_0 = 0.1$ and $\alpha_1 = 0.9$ for classes $\{0, 1\}$. $\mathcal{B}$ denotes the mini-batch of labeled samples used in one training step and the loss is averaged across all samples in the current batch.

During the training process, the FiLM edit vector $\mathbf{e}$ is further regularized to maintain stable and interpretable feature edits. First, an orthogonality constraint $\mathcal{L}_{\perp}$ is used to penalize edits that align with the classifier’s decision directions, preventing FiLM from trivially amplifying class-discriminative components rather than encoding clinical cues.

$$\mathcal{L}_{\perp} = \text{MSE}((\mathbf{e} \mathbf{W}_{\text{cls}}^{\top}) \mathbf{W}_{\text{cls}}, \mathbf{0}) \quad (9)$$

where $\mathbf{W}_{\text{cls}}$ denotes the weight matrix of the final linear classifier h and MSE is mean squared error.

Additionally, a soft-norm constraint $\mathcal{L}_{\text{norm}}$ is used to limit the overall edit magnitude, ensuring FiLM performs small, controlled adjustments to the feature representation rather than large distortions.

$$\mathcal{L}_{\text{norm}} = \max(0, \|\mathbf{e}\|_2 - R_{\text{max}}), \quad R_{\text{max}} = 2.0 \quad (10)$$

Together, these regularizers encourage FiLM to make clinically meaningful refinements without altering the classifier boundary directly.

The supervised training loss for the source domain is then

$$\mathcal{L}_{\text{source}} = \mathcal{L}_{\text{sup}} + \lambda_{\perp} \mathcal{L}_{\perp} + \lambda_{\text{norm}} \mathcal{L}_{\text{norm}} \quad (11)$$

where $\lambda_{\perp} = \lambda_{\text{norm}} = 0.01$.

EMA teacher is a running average of the online model [32]. It acts as a stable target during training by smoothing short-term noise from recent updates. This improves consistency in pseudo-labels and makes training more stable.

We maintain a teacher network as an exponential moving average (EMA) of the online parameters θ . At the start of training we set $\bar{\theta}_0 \leftarrow \theta_0$, and after every optimizer update we perform

$$\bar{\theta} \leftarrow \alpha_{\text{ema}} \bar{\theta} + (1 - \alpha_{\text{ema}}) \theta, \quad \alpha_{\text{ema}} = 0.999,$$

with stop-gradient on the teacher and no optimizer applied to $\bar{\theta}$. α_{ema} is the decay rate which defines how quickly the teacher model follows the online model. Here we set α_{ema} to 0.999 to make sure that the teacher updates slowly, providing temporally smoothed predictions that suppress short-term training noise while still tracking long-term improvements of the online model. All model parameters (backbone, FiLM, head) are included in the EMA.

3.4.2. Target Consistency Learning

To stabilize adaptation on unlabeled target data, we adopt a two-view consistency strategy between the EMA teacher

and the online MONET-guided model. For each target image, two augmentations are generated: a weak view preserving global structure and a strong view with larger appearance perturbations [27]. As both views share the same MONET-based context, we encourage agreement between weak/strong views of the same target image and stabilize the edited representation by matching both the logits and the edited features.

The EMA teacher processes the weak view to produce a stable pseudo-label, while the online model predicts from the strong view. With temperature sharpening $\tau = 0.6$, logits are converted to soft prediction $p = \text{softmax}(\ell/\tau)$. Consistency is enforced by minimizing the divergence between the EMA teacher’s weak-view prediction $\bar{p}_w$ and the model’s strong-view prediction p_s .

$$\mathcal{L}_{\text{KL}} = 0.5 (\text{KL}(p_s \parallel \bar{p}_w) + \text{KL}(\bar{p}_w \parallel p_s)) \quad (12)$$

Feature- and edit-level consistencies are also maintained using MSE losses

$$\mathcal{L}_{\text{feat}} = \text{MSE}(\mathbf{u}_s, \bar{\mathbf{u}}_w), \quad \mathcal{L}_{\text{edit}} = \text{MSE}(\mathbf{e}_s, \bar{\mathbf{e}}_w). \quad (13)$$

To reduce noise from unreliable pseudo-labels, only target samples with sufficiently confident predictions are used in the loss. In this paper, we use a dynamic confidence threshold $t(\text{epoch})$ to control sample selection. Early in training, $t(0) = 0.95$ is set to restrict learning to high-confidence examples and the threshold gradually decays to 0.70 as the teacher becomes more stable. This strategy prevents error propagation at the start and increases data utilization over time.

Then the total target loss combines the masked, two-view consistency terms

$$\mathcal{L}_{\text{target}} = w_{\text{kl}} \mathcal{L}_{\text{KL}} + w_{\text{feat}} \mathcal{L}_{\text{feat}} + w_{\text{edit}} \mathcal{L}_{\text{edit}} \quad (14)$$

with $w_{\text{kl}} = 0.6$, $w_{\text{feat}} = 0.1$, and $w_{\text{edit}} = 0.1$. These losses encourage the online model to match the EMA teacher’s stable weak-view predictions under strong perturbations, yielding robust, domain-invariant representations.

3.5. Stage 2: Image-Only Student Distillation

After training the concept-guided EMA teacher, an image-only student network is trained to reproduce the teacher’s behavior without MONET inputs. We denote the teacher by T and the student by S . The teacher parameters $\bar{\theta}$ are frozen while the student parameters θ_S are trained independently to imitate the teacher using only image input. Given an image x , the EMA teacher produces the concept-guided feature $\mathbf{u}_T$ and corresponding logits ℓ_T . The student network shares the same backbone and classifier but replaces the FiLM module with a lightweight residual edit head ψ_{edit} that predicts its edited feature directly from the image

$$\mathbf{v}_S = f_{\theta_S}(\mathbf{x}), \quad \mathbf{u}_S = \mathbf{v}_S + \psi_{\text{edit}}(\mathbf{v}_S). \quad (15)$$

Then the student classifier outputs logits $\ell_S = h(\mathbf{u}_S)$ and the teacher and student logits are converted into soft probability distributions p_S, p_T using a temperature-scaled soft-

max where the temperature τ set to 2.0 to smooth the distributions to reveal relative class confidence [13]. The student loss is

$$\mathcal{L}_{\text{distill}} = \text{KL}(p_S \| p_T) \tau^2 + \lambda_{\text{feat}} \text{MSE}(\mathbf{u}_S, \mathbf{u}_T) \quad (16)$$

with $\lambda_{\text{feat}} = 0.1$. The KL-divergence loss transfers the teacher’s class-probability structure, and the feature-matching term encourages the student to reproduce the teacher’s concept-aware representation. Through this process, the student inherits the teacher’s clinically informed reasoning yet remains independent of MONET at inference, enabling efficient and domain-robust image-only prediction.

3.6. Stage 3: Image-Only Inference and Evaluation

At inference time, the image-only student model is used. The predicted melanoma probability p_1 determines the final label, where melanoma is predicted if $p_1 \geq 0.5$. Neither MONET concept inputs nor EMA teacher updates are required during inference, ensuring a lightweight and fully image-based inference.

4. Results and Discussion

Datasets: We use eight public skin lesion datasets encompassing two capture styles, Dermoscopic and Clinical, with examples shown in Figure 3 and a detailed summary in Table 1. During training, image-level concept probabilities derived from the clinical decision-support tool (MONET) are incorporated as supervision. These concept probabilities are not used during inference.

Evaluation Protocol: We train on a single source–target pair, **MILK Dermoscopic** $\rightarrow$ **MILK Clinical**. After training the teacher and student model separately, the resulting image-only student model is frozen and evaluated directly on the test partitions of six unseen external datasets. This is a strict out-of-domain evaluation. Results are reported using AUROC and melanoma recall (sensitivity), with high recall being critical to ensure potential melanomas are not missed during screening.

Reproducibility: All experiments are run end-to-end with five random seeds. Models train for up to 50 epochs with early stopping on validation AUROC using development data only, ensuring strict separation from the test sets. Inference uses images only. Both teacher and student models use batch size 32, an EfficientNet-B2 backbone [31], AdamW (lr 3×10^{-4} , weight decay 10^{-4}), and cosine annealing to 10^{-6} . Weak and strong augmentations (crop, flip, color jitter, Gaussian blur) are applied uniformly across methods. Additional metrics, plots, ablations, and implementation details are provided in the supplementary material. Experiments are performed on an Apple Mac Studio

(M3 Ultra, 28-core CPU, 60-core GPU, 32-core Neural Engine) with 96 GB of unified memory.




Figure 3. Eight dataset examples across dermoscopic and clinical capture. Dermoscopic images are close and uniform with fine texture. Clinical images include wider context, varied lighting, and common artefacts such as hair, rulers, and shadows. These differences create a clear domain gap for the same lesion classes.

Table 1. Dataset summary across eight datasets. Bold* datasets denote unseen evaluation sets that are never used for training or adaptation. **Mel** counts all melanoma subtypes, and **Other** includes all remaining diagnostic categories. The training dataset is split 70:15:15 into training, validation, and test partitions. Each unseen dataset uses all available images exclusively for test-time inference with the image-only model.

Dataset	Domain	Mel	Other
MILK10K (Md / Mc)[25]	Dermoscopic and Clinical	452	4,792
Derm7pt* (D7d / D7c)[14]	Dermoscopic and Clinical	254	762
Fitzpatrick (Fitz)*[10]	Clinical	344	11,259
HAM10000* (HAM)[33]	Dermoscopic	780	6,232
MIDAS* (MID.d)[5]	Dermoscopic	96	952
MIDAS* (MID.c)[5]	Clinical	186	1,915

Baselines: We compare our approach to ‘source-only’ training and a wide range of domain-adaptation and adaptation-free baselines, including DANN [11], Deep CORAL [30], MMD [12], Mean Teacher [32], IT-RUDA [26], SHOT++ [19], SFDA [22], CPD [42], DINE [20], CoTTA [36], WoC [16], TENT [34], DAMP [8], and DALUPI [2]. Training data, augmentation policies, and schedules are matched where applicable. Unless otherwise stated, all reported results correspond to the final image-only student model.

Comparison with other Methods: We evaluate our distilled image-only student (CoFiDA-M) against the source only baseline and competing UDA methods (Tables 2). As shown in Table 2(B), our method achieves the highest average AUROC on the clinical target domain at 67.50%. This represents a +9.11% absolute improvement over the source only baseline (58.39%) and significantly exceeds other strategies, including the strongest test-time method, TENT (62.32%), and the privileged information baseline, DALUPI (54.54%).

Table 2. AUROC (%) mean $\pm$ std over 5 seeds. Left: **Dermoscopic** (A), macro-average across Dermoscopic and Right **Clinical** (B), macro-average across Clinical. MIDd, MIDc, D7d, D7c, HAM and Fitz are unseen test datasets.

Setting / Method	(A) Dermoscopic					(B) Clinical				
	Md	MIDd*	D7d*	HAM*	Avg	Mc	MIDc*	D7c*	Fitz*	Avg
Classical / Standard										
DANN [11]	78.37 $\pm$ 0.05	72.29 $\pm$ 0.08	69.40 $\pm$ 0.07	72.09 $\pm$ 0.09	73.04	76.81 $\pm$ 0.05	56.43 $\pm$ 0.07	43.84 $\pm$ 0.06	55.23 $\pm$ 0.09	58.08
DeepCoral [30]	79.20 $\pm$ 0.05	69.55 $\pm$ 0.07	52.39 $\pm$ 0.04	76.87 $\pm$ 0.06	69.50	77.30 $\pm$ 0.06	50.41 $\pm$ 0.12	49.37 $\pm$ 0.07	48.76 $\pm$ 0.04	56.46
MMD [12]	78.23 $\pm$ 0.09	75.83 $\pm$ 0.10	62.15 $\pm$ 0.16	80.10 $\pm$ 0.17	74.08	79.58 $\pm$ 0.04	52.25 $\pm$ 0.05	46.74 $\pm$ 0.12	56.10 $\pm$ 0.09	58.67
MeanTeacher [32]	62.06 $\pm$ 0.26	45.34 $\pm$ 0.13	51.22 $\pm$ 0.10	65.27 $\pm$ 0.12	55.97	53.08 $\pm$ 0.20	48.81 $\pm$ 0.05	47.46 $\pm$ 0.09	46.30 $\pm$ 0.08	48.91
IT-RUDA [26]	86.27 $\pm$ 0.07	67.16 $\pm$ 0.02	67.19 $\pm$ 0.05	82.79 $\pm$ 0.06	75.85	63.34 $\pm$ 0.06	51.68 $\pm$ 0.05	57.39 $\pm$ 0.08	53.65 $\pm$ 0.01	56.52
Modern Source Free										
SHOT++ [19]	65.17 $\pm$ 0.14	52.57 $\pm$ 0.09	62.19 $\pm$ 0.19	61.45 $\pm$ 0.15	60.35	55.88 $\pm$ 0.03	57.39 $\pm$ 0.02	51.10 $\pm$ 0.11	39.01 $\pm$ 0.09	50.84
DINE [20]	70.32 $\pm$ 0.13	71.80 $\pm$ 0.12	65.39 $\pm$ 0.12	79.81 $\pm$ 0.10	71.83	66.54 $\pm$ 0.15	52.93 $\pm$ 0.08	41.22 $\pm$ 0.07	56.94 $\pm$ 0.07	54.41
SFDA [22]	58.49 $\pm$ 0.11	55.76 $\pm$ 0.16	55.95 $\pm$ 0.03	54.12 $\pm$ 0.19	56.08	44.91 $\pm$ 0.12	47.27 $\pm$ 0.05	45.39 $\pm$ 0.07	51.42 $\pm$ 0.10	47.25
CPD [42]	59.87 $\pm$ 0.09	59.87 $\pm$ 0.06	57.05 $\pm$ 0.02	69.24 $\pm$ 0.07	61.51	46.14 $\pm$ 0.05	51.40 $\pm$ 0.06	52.83 $\pm$ 0.05	42.54 $\pm$ 0.07	48.23
Modern Test Time										
CoTTA [36]	62.43 $\pm$ 0.13	53.60 $\pm$ 0.22	55.79 $\pm$ 0.01	54.61 $\pm$ 0.07	56.61	51.99 $\pm$ 0.14	50.55 $\pm$ 0.15	53.71 $\pm$ 0.06	52.75 $\pm$ 0.09	52.25
TENT [34]	80.21 $\pm$ 0.16	65.30 $\pm$ 0.04	70.08 $\pm$ 0.09	63.21 $\pm$ 0.16	69.70	81.76 $\pm$ 0.11	55.09 $\pm$ 0.17	55.78 $\pm$ 0.15	56.63 $\pm$ 0.07	62.32
WoC [16]	66.29 $\pm$ 0.18	58.19 $\pm$ 0.10	61.05 $\pm$ 0.20	54.71 $\pm$ 0.14	60.06	49.76 $\pm$ 0.13	43.57 $\pm$ 0.16	60.73 $\pm$ 0.12	41.87 $\pm$ 0.02	48.98
Multimodal										
DAMP [8]	87.32 $\pm$ 0.09	65.57 $\pm$ 0.02	69.02 $\pm$ 0.01	80.08 $\pm$ 0.01	75.50	63.59 $\pm$ 0.01	43.52 $\pm$ 0.03	61.14 $\pm$ 0.04	53.68 $\pm$ 0.05	55.48
DALUPI [2]	87.38 $\pm$ 0.01	62.69 $\pm$ 0.03	70.26 $\pm$ 0.07	83.97 $\pm$ 0.01	76.07	58.18 $\pm$ 0.02	47.71 $\pm$ 0.03	62.50 $\pm$ 0.08	49.78 $\pm$ 0.02	54.54
Source Only	84.67 $\pm$ 0.06	65.94 $\pm$ 0.03	54.76 $\pm$ 0.05	74.48 $\pm$ 0.01	69.96	75.02 $\pm$ 0.04	51.51 $\pm$ 0.02	52.85 $\pm$ 0.08	54.20 $\pm$ 0.01	58.39
Ours (CoFiDA-M)	89.70 $\pm$ 0.09	76.15 $\pm$ 0.07	61.69 $\pm$ 0.04	78.45 $\pm$ 0.05	76.50	83.94 $\pm$ 0.01	69.67 $\pm$ 0.04	50.48 $\pm$ 0.07	65.91 $\pm$ 0.09	67.50

Table 3. Recall for melanoma (%) mean $\pm$ std over 5 seeds. Left: **Dermoscopic** (A), macro-average across Dermoscopic and Right **Clinical** (B), macro-average across Clinical. MIDd, MIDc, D7d, D7c, HAM and Fitz are unseen test datasets.

Setting / Method	(A) Dermoscopic					(B) Clinical				
	Md	MIDd*	D7d*	HAM*	Avg	Mc	MIDc*	D7c*	Fitz*	Avg
Classical / Standard										
DANN [11]	40.29 $\pm$ 0.17	70.89 $\pm$ 0.02	38.30 $\pm$ 0.09	62.87 $\pm$ 0.03	53.09	21.59 $\pm$ 0.05	49.86 $\pm$ 0.12	20.45 $\pm$ 0.06	3.47 $\pm$ 0.06	23.84
DeepCoral [30]	79.20 $\pm$ 0.24	69.55 $\pm$ 0.19	52.39 $\pm$ 0.31	76.87 $\pm$ 0.22	69.50	31.82 $\pm$ 0.02	10.97 $\pm$ 0.04	50.00 $\pm$ 0.02	14.86 $\pm$ 0.05	26.91
MMD [12]	43.69 $\pm$ 0.24	55.70 $\pm$ 0.01	51.06 $\pm$ 0.02	86.46 $\pm$ 0.07	59.23	30.68 $\pm$ 0.07	5.81 $\pm$ 0.01	27.27 $\pm$ 0.02	9.46 $\pm$ 0.10	18.31
MeanTeacher [32]	74.91 $\pm$ 0.32	70.89 $\pm$ 0.04	65.96 $\pm$ 0.08	44.31 $\pm$ 0.07	64.02	77.27 $\pm$ 0.01	88.71 $\pm$ 0.04	70.45 $\pm$ 0.07	74.23 $\pm$ 0.05	77.67
IT-RUDA [26]	49.28 $\pm$ 0.02	12.66 $\pm$ 0.01	12.62 $\pm$ 0.09	47.90 $\pm$ 0.01	30.62	9.77 $\pm$ 0.06	7.56 $\pm$ 0.07	12.34 $\pm$ 0.09	22.00 $\pm$ 0.10	12.92
Modern Source Free										
SHOT++ [19]	72.61 $\pm$ 0.09	64.56 $\pm$ 0.01	39.26 $\pm$ 0.19	68.260 $\pm$ 0.008	61.17	65.91 $\pm$ 0.01	57.42 $\pm$ 0.03	52.94 $\pm$ 0.01	54.05 $\pm$ 0.01	57.58
DINE [20]	2.27 $\pm$ 0.01	8.86 $\pm$ 0.02	9.80 $\pm$ 0.05	38.92 $\pm$ 0.03	14.96	2.27 $\pm$ 0.01	3.58 $\pm$ 0.03	1.96 $\pm$ 0.01	1.35 $\pm$ 0.02	2.29
SFDA [22]	24.53 $\pm$ 0.21	22.09 $\pm$ 0.13	20.10 $\pm$ 0.09	19.77 $\pm$ 0.15	21.62	6.31 $\pm$ 0.06	10.67 $\pm$ 0.12	15.91 $\pm$ 0.01	9.34 $\pm$ 0.10	10.56
CPD [42]	57.95 $\pm$ 0.01	35.44 $\pm$ 0.06	70.86 $\pm$ 0.06	62.28 $\pm$ 0.09	56.63	55.68 $\pm$ 0.04	68.23 $\pm$ 0.06	71.52 $\pm$ 0.02	47.52 $\pm$ 0.19	60.74
Modern Test Time										
CoTTA [36]	68.29 $\pm$ 0.07	59.49 $\pm$ 0.03	58.82 $\pm$ 0.04	69.58 $\pm$ 0.09	64.05	56.82 $\pm$ 0.01	63.23 $\pm$ 0.03	52.94 $\pm$ 0.08	59.46 $\pm$ 0.05	58.11
TENT [34]	76.11 $\pm$ 0.10	67.24 $\pm$ 0.09	50.22 $\pm$ 0.27	69.37 $\pm$ 0.17	65.74	75.00 $\pm$ 0.06	61.10 $\pm$ 0.29	48.30 $\pm$ 0.20	38.22 $\pm$ 0.11	55.65
WoC [16]	52.45 $\pm$ 0.07	34.18 $\pm$ 0.01	68.09 $\pm$ 0.05	38.92 $\pm$ 0.09	48.41	37.50 $\pm$ 0.02	9.03 $\pm$ 0.01	61.36 $\pm$ 0.07	5.41 $\pm$ 0.05	28.33
Multimodal										
DAMP [8]	35.23 $\pm$ 0.07	15.19 $\pm$ 0.03	13.25 $\pm$ 0.02	35.93 $\pm$ 0.06	24.90	1.14 $\pm$ 0.05	9.32 $\pm$ 0.03	7.28 $\pm$ 0.05	5.57 $\pm$ 0.06	5.83
DALUPI [2]	53.41 $\pm$ 0.07	29.11 $\pm$ 0.05	25.83 $\pm$ 0.09	52.10 $\pm$ 0.10	40.11	4.55 $\pm$ 0.06	7.74 $\pm$ 0.05	12.58 $\pm$ 0.08	13.99 $\pm$ 0.01	9.72
Source Only	72.37 $\pm$ 0.04	62.70 $\pm$ 0.22	58.64 $\pm$ 0.02	60.48 $\pm$ 0.12	63.55	65.91 $\pm$ 0.03	65.94 $\pm$ 0.03	55.78 $\pm$ 0.14	35.45 $\pm$ 0.04	55.77
Ours (CoFiDA-M)	81.56 $\pm$ 0.11	75.95 $\pm$ 0.01	89.36 $\pm$ 0.02	92.81 $\pm$ 0.07	84.92	86.36 $\pm$ 0.02	74.84 $\pm$ 0.01	90.91 $\pm$ 0.02	59.46 $\pm$ 0.03	77.89

For the critical screening metric of melanoma recall Table 3, the improvement is more pronounced. On the clinical target domain Table 3(B), CoFiDA-M achieves an average recall of 77.89%, a +22.12% absolute gain over the source only baseline (55.77%). Notably, while the standard UDA method Mean Teacher achieves a similar high recall (77.67%), its clinical AUROC (58.67%) remains near the baseline. In contrast, our method yields substantial improvements on both target-domain metrics. Importantly, the gain does not arise from a trade-off: our method also achieves the highest average recall on the source dermoscopic domain Table 2(A) reaching 84.92% compared to 63.55% for the source-only baseline. These results indicate

that our model learns a more robust, domain-invariant representation of the minority class, enabling safer and more reliable cross-domain generalization.




Figure 4. Ablation on Teacher Knowledge on MILK (Clinical). The image-only student is distilled from three fixed teachers: a fully trained Frozen Teacher (FT), a Random-weight Teacher (RT), and a Zero-weight Teacher (ZT).

Table 4. Ablation study. Each metric reflects the average percentage score across the four Dermoscopic (d) and four Clinical (c) datasets. Section A compares image-only frameworks, Section B varies the teacher architecture, and Section C examines student distillation using the same frozen teacher.

Sec.	Family	Variant	AUROC _d ↑	AUROC _c ↑	Recall _d ↑	Recall _c ↑
A	Baselines / Student	Source-Only	69.96	58.39	63.55	55.77
		Standard UDA (no MONET)	76.07	62.32	69.50	77.67
		Ours: Student (image-only)	76.50	67.50	84.92	77.89
B	Teacher design	Full Teacher (Gating + FiLM)	85.35	83.81	87.81	86.36
		w/o Confidence-Gating	78.32	75.24	47.70	43.20
		w/o FiLM (Concat)	84.18	81.51	80.68	73.86
C	Knowledge distillation (fixed Teacher)	Logit KD Only	63.80	64.10	72.49	64.53
		Logit KD + Align $\mathbf{v}_T$ (pre-edit)	70.68	66.45	79.12	75.74
		Logit KD + Align $\mathbf{u}_T$ (post-edit)	76.50	67.50	84.92	77.89




Figure 5. Qualitative Validation of the CoFiDA-M Framework. (a) Student’s implicit concept learning via edit magnitude correlation. (b) Teacher’s feature-editing mechanism transforming feature space. (c) Causal proof of concept-guided feature steering. (d) Successful distillation via Student-Teacher feature alignment.

Ablation Study: Table 4 validates our core design choices. Section A shows our image-only student outperforms both the ‘Source-Only’ baseline and standard UDA (without PI), confirming that distilling MONET-derived concepts provides a stronger training signal than raw unlabeled data alone. Section B analyzes the teacher’s architecture. Removing the confidence-gating mechanism causes a drastic drop in melanoma recall, demonstrating the necessity of filtering noisy concept scores. Replacing FiLM-based modulation with naïve concatenation also degrades performance, confirming that explicitly editing the feature space is superior to simple feature augmentation. Finally, Section C isolates our distillation strategy. Training with only logit-based KD is insufficient. Aligning the student to the teacher’s pre-edit features ($\mathbf{v}_T$) improves performance, but aligning to the post-edit, concept-adjusted

features ($\mathbf{u}_T$) yields the best results. This confirms our primary hypothesis: the student must learn to reproduce the teacher’s concept-adjusted representation. This finding is validated by a sanity check, Figure 4, where distilling from a random-weight teacher (RT) or zero-weight teacher (ZT) fails to converge ($FT \gg RT \approx ZT$), achieving only chance-level performance. The student’s gains thus arise from the teacher’s learned semantic edits, not the distillation process itself. The violin plot shows that the FT-based student achieves distinctly higher and tighter feature separation. RT and ZT collapse near the random baseline, which is evidence that only the trained teacher imparts meaningful semantic structure to the student’s embeddings.

Feature Space and Reliability Analysis: Figure 5(a) shows that the image-only student has internalized the teacher’s concept guided behavior: the MONET concept score (ground truth) correlates strongly and positively with the student’s self-generated edit magnitude $\|\mathbf{u}_S - \mathbf{v}_S\|_2$. Figure 5(b) visualizes the MONET-guided teacher FiLM edit ($\mathbf{v}_T \rightarrow \mathbf{u}_T$) correcting the feature space and moving scattered samples into two well-separated clusters. Figure 5(c) provides intervention based evidence: increasing melanoma like concept input moves the FiLM-edited feature towards the melanoma cluster. Figure 5(d) confirms successful distillation, with the image-only student (open circles) reproducing the teacher’s (filled dots) corrected, separated manifold.

5. Conclusion

We introduced a practical domain adaptation framework that learns from privileged, high-level concepts during training but deploys as a lightweight, image-only model. Our method uses a MONET-conditioned, FiLM-based teacher to shape the feature space using clinical semantics. We then distill not only the final logits but also the edited feature representation into a student, effectively embedding expert knowledge into its weights to enable robust, concept-free generalization at inference time. Our analysis shows that alignment with the edited semantic space is

critical for transferring the teacher’s knowledge. While we demonstrated this with MONET in dermatology, the core privileged-information framework is general. The main limitation lies in its dependency on the quality of training-time concepts, which future work could address by learning concepts end-to-end or extending the framework to other specialized domains.

References

- [1] Leo Breiman, Jerome Friedman, Richard A Olshen, and Charles J Stone. *Classification and regression trees*. Chapman and Hall/CRC, 2017. 3
- [2] Adam Breitholtz, Anton Matsson, and Fredrik D. Johansson. Unsupervised domain adaptation by learning using privileged information. *Transactions on Machine Learning Research*, 2024. Published 16 September 2024. 2, 3, 6, 7
- [3] Sireesha Chamarthi, Katharina Fogelberg, Titus J Brinker, and Julia Niebling. Mitigating the influence of domain shift in skin lesion classification: A benchmark study of unsupervised domain adaptation methods. *Informatics in Medicine Unlocked*, 44:101430, 2024. 1
- [4] Yanyuan Chen, Dexuan Xu, Yu Huang, Songkun Zhan, Hanpin Wang, Dongxue Chen, Xueping Wang, Meikang Qiu, and Hang Li. Mimo: A medical vision language model with visual referring multimodal input and pixel grounding multimodal output. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 24732–24741, 2025. 2
- [5] Albert S Chiou, Jesutofunmi A Omiye, Haiwen Gui, Susan M Swetter, Justin M Ko, Brian Gastman, Joshua Arbesman, Zhuo Ran Cai, Olivier Gevaert, Christoph Sadée, et al. Multimodal image dataset for ai-based skin cancer (midas) benchmarking. *NEJM AI*, 2(6): AIdbp2400732, 2025. 6
- [6] Dionysis Christopoulos, Sotiris Spanos, Eirini Baltzi, Valsamis Ntouskos, and Konstantinos Karantzas. Skin lesion phenotyping via nested multi-modal contrastive learning. *arXiv preprint arXiv:2505.23709*, 2025. 2
- [7] Anxhelo Diko, Antonino Furnari, Luigi Cinque, and Giovanni Maria Farinella. Laguna: Language guided unsupervised adaptation with structured spaces. *arXiv preprint arXiv:2411.15557*, 2024. 2, 3
- [8] Zhekai Du, Xinyao Li, Fengling Li, Ke Lu, Lei Zhu, and Jingjing Li. Domain-agnostic mutual prompting for unsupervised domain adaptation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 23375–23384, 2024. 2, 6, 7
- [9] Mohammad Fahes, Tuan-Hung Vu, Andrei Bursuc, Patrick Pérez, and Raoul De Charette. Poda: Prompt-driven zero-shot domain adaptation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 18623–18633, 2023. 2, 3
- [10] Thomas B. Fitzpatrick. The validity and practicality of sun-reactive skin types i through vi. *Archives of Dermatology*, 124(6):869–871, 1988. 6
- [11] Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario March, and Victor Lempitsky. Domain-adversarial training of neural networks. *Journal of machine learning research*, 17(59):1–35, 2016. 1, 6, 7
- [12] Arthur Gretton, Karsten M Borgwardt, Malte J Rasch, Bernhard Schölkopf, and Alexander Smola. A kernel two-sample test. *The journal of machine learning research*, 13(1):723–773, 2012. 1, 6, 7
- [13] Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015. 3, 6
- [14] Jeremy Kawahara, Sara Daneshvar, Giuseppe Argenziano, and Ghassan Hamarneh. Seven-point checklist and skin lesion classification using multitask multimodal neural nets. *IEEE Journal of Biomedical and Health Informatics*, 23(2):538–546, 2019. 6
- [15] Chanwoo Kim, Soham U Gadgil, Alex J DeGrave, Jesutofunmi A Omiye, Zhuo Ran Cai, Roxana Daneshjou, and Su-In Lee. Transparent medical image ai via an image–text foundation model grounded in medical literature. *Nature medicine*, 30(4):1154–1165, 2024. 2, 3
- [16] Jungsoo Lee, Debasmit Das, Jaegul Choo, and Sungha Choi. Towards open-set test-time adaptation utilizing the wisdom of crowds in entropy minimization. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 16380–16389, 2023. 3, 6, 7
- [17] Junnan Li, Dongxu Li, Caiming Xiong, and Steven Hoi. Blip: Bootstrapping language-image pre-training for unified vision-language understanding and generation. In *International conference on machine learning*, pages 12888–12900. PMLR, 2022. 2, 3
- [18] Jian Liang, Dapeng Hu, and Jiashi Feng. Do we really need to access the source data? source hypothesis transfer for unsupervised domain adaptation. In *International conference on machine learning*, pages 6028–6039. PMLR, 2020. 3
- [19] Jian Liang, Dapeng Hu, Yunbo Wang, Ran He, and Jiashi Feng. Source data-absent unsupervised domain adaptation through hypothesis transfer and labeling transfer. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 44(11):8602–8617, 2021. 6, 7
- [20] Jian Liang, Dapeng Hu, Jiashi Feng, and Ran He. Dine: Domain adaptation from single and multiple black-box predictors. In *Proceedings of the*

- IEEE/CVF conference on computer vision and pattern recognition*, pages 8003–8013, 2022. 3, 6, 7
- [21] Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. In *Proceedings of the IEEE international conference on computer vision*, pages 2980–2988, 2017. 4
- [22] Yuang Liu, Wei Zhang, and Jun Wang. Source-free domain adaptation for semantic segmentation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 1215–1224, 2021. 3, 6, 7
- [23] Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, David Sculley, Sebastian Nowozin, Joshua Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model’s uncertainty? evaluating predictive uncertainty under dataset shift. *Advances in neural information processing systems*, 32, 2019. 1
- [24] Ethan Perez, Florian Strub, Harm De Vries, Vincent Dumoulin, and Aaron Courville. Film: Visual reasoning with a general conditioning layer. In *Proceedings of the AAAI conference on artificial intelligence*, 2018. 3, 4
- [25] Philipp Tschandl, Akay Nisa Bengü, Rosendahl Cliff, Rotemberg Veronica, Todorovska Verche, Weber Jochen, Wolber Anna Katharina, Müller Christoph, Kurtansky Nicholas, Halpern Allan, et al. Milk10k: A hierarchical multimodal imaging learning toolkit for diagnosing pigmented and non-pigmented skin cancer and its simulators. *Journal of Investigative Dermatology*, 2025. 6
- [26] Shima Rashidi, Ruwan Tennakoon, Aref Miri Reka-vandi, Papangkorn Jessadatavornwong, Amanda Freis, Garret Huff, Mark Easton, Adrian Mouritz, Reza Hoseinnezhad, and Alireza Bab-Hadiashar. It-ruda: Information theory-assisted robust unsupervised domain adaptation. *ACM Transactions on Intelligent Systems and Technology*, 16(4):1–17, 2025. 3, 6, 7
- [27] Kihyuk Sohn, David Berthelot, Nicholas Carlini, Zizhao Zhang, Han Zhang, Colin Raffel, Ekin Dogus Cubuk, Alexey Kurakin, and Chun-Liang Li. Fix-Match: Simplifying semi-supervised learning with consistency and confidence. In *Advances in Neural Information Processing Systems*, 2020. 5
- [28] Nurjahan Sultana, Wenqi Lu, Xinqi Fan, and Moi Hoon Yap. Domain adaptation for skin lesion: Evaluating real-world generalisation. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 3433–3443, 2025. 1
- [29] Nurjahan Sultana, Wenqi Lu, Xinqi Fan, and Moi Hoon Yap. Selective alignment transfer for domain adaptation in skin lesion analysis. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 596–606. Springer, 2025. 1
- [30] Baochen Sun and Kate Saenko. Deep coral: Correlation alignment for deep domain adaptation. In *European conference on computer vision*, pages 443–450. Springer, 2016. 1, 6, 7
- [31] Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International conference on machine learning*, pages 6105–6114. PMLR, 2019. 3, 6
- [32] Antti Tarvainen and Harri Valpola. Mean teachers are better role models: Weight-averaged consistency targets improve semi-supervised deep learning results. *Advances in neural information processing systems*, 30, 2017. 3, 5, 6, 7
- [33] Philipp Tschandl, Cliff Rosendahl, and Harald Kittler. The ham10000 dataset, a large collection of multi-source dermatoscopic images of common pigmented skin lesions. *Scientific data*, 5(1):1–9, 2018. 6
- [34] Dequan Wang, Evan Shelhamer, Shaoteng Liu, Bruno Olshausen, and Trevor Darrell. Tent: Fully test-time adaptation by entropy minimization. In *International Conference on Learning Representations (ICLR)*, 2021. Spotlight. 3, 6, 7
- [35] Janet Wang, Yunbei Zhang, Zhengming Ding, and Jihun Hamm. Achieving reliable and fair skin lesion diagnosis via unsupervised domain adaptation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5157–5166, 2024. 1
- [36] Qin Wang, Olga Fink, Luc Van Gool, and Dengxin Dai. Continual test-time domain adaptation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 7201–7211, 2022. 3, 6, 7
- [37] Zifeng Wang, Zhenbang Wu, Dinesh Agarwal, and Jiemeng Sun. Medclip: Contrastive learning from unpaired medical images and text. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing. Conference on Empirical Methods in Natural Language Processing*, page 3876, 2022. 2, 3
- [38] Siyuan Yan, Xieji Li, Ming Hu, Yiwen Jiang, Zhen Yu, and Zongyuan Ge. Make: Multi-aspect knowledge-enhanced vision-language pretraining for zero-shot dermatological assessment. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 369–379. Springer, 2025. 2, 3
- [39] Siyuan Yan, Zhen Yu, Clare Primiero, Cristina Vico-Alonso, Zhonghua Wang, Litao Yang, Philipp Tschandl, Ming Hu, Lie Ju, Gin Tan, et al. A mul-

- timodal vision foundation model for clinical dermatology. *Nature Medicine*, pages 1–12, 2025. [2](#)
- [40] Wenqi Zeng, Yuqi Sun, Chenxi Ma, Weimin Tan, and Bo Yan. Mm-skin: Enhancing dermatology vision-language model with an image-text dataset derived from textbooks. In *Proceedings of the 33rd ACM International Conference on Multimedia*, pages 3769–3778, 2025. [2](#)
- [41] Yilan Zhang, Fengying Xie, and Jianqi Chen. Tformer: A throughout fusion transformer for multi-modal skin lesion diagnosis. *Computers in biology and medicine*, 157:106712, 2023. [2](#)
- [42] Lihua Zhou, Nianxin Li, Mao Ye, Xiatian Zhu, and Song Tang. Source-free domain adaptation with class prototype discovery. *Pattern recognition*, 145:109974, 2024. [3](#), [6](#), [7](#)