

MPCoT: Reward-Guided Multi-Path Latent Reasoning for Test-Time Scalable Vision-Language-Action

Boyang Zhang

Department of Electrical and Computer Engineering
Boston University
Boston, MA 02215, USA
theostnc@bu.edu

Lianlei Shan

Department of Computer Science
Tsinghua University
Beijing 100084, China
shanlianlei18@ucas.edu.cn

Abstract: Vision-Language-Action (VLA) policies remain brittle in long-horizon and high-uncertainty control, where one-pass action decoding provides limited inference-time deliberation. Explicit chain-of-thought can increase reasoning depth, but introduces token latency and an indirect text-to-action interface. We propose *MPCoT*, a reward-guided multi-path latent reasoning framework that initializes M hypotheses, refines them for K weight-tied steps, and softly aggregates them before action decoding. A training-only path-preference objective evaluates candidate action branches with expert-action consistency, world-model/VLM-based progress, and success feedback to align the latent path scorer with downstream execution quality. MPCoT preserves the original 8-step action interface, generates zero reasoning tokens, and exposes configurable inference controls (K, M). Under matched protocols on LIBERO and CALVIN, MPCoT improves long-horizon performance, with ablations confirming depth-width effects, confidence-weighted aggregation, and reward-guided path supervision.

Keywords: vision-language-action, latent reasoning, test-time scaling

Code and videos: <https://github.com/EDGSCOUT/MPCoT>

1 INTRODUCTION

Vision-Language-Action (VLA) policies unify perception, language grounding, and action generation for robot manipulation [1, 2, 3], while open frameworks such as OpenVLA and OpenVLA-OFT make this paradigm reproducible on benchmarks such as LIBERO [4, 5, 6]. Yet long-horizon execution, compositional instructions, and uncertainty remain brittle: a fixed one-pass action decoder provides little inference-time deliberation, and small early errors can compound across later action chunks.

This exposes a tension between reasoning depth and control efficiency. Explicit CoT can improve multi-step reasoning in language models and VLA control [7, 8], but textual or visual traces add latency, memory overhead, and an indirect interface to continuous actions. Purely implicit policies are efficient but often reduce difficult decisions to one-pass mappings. Here, we use “latent reasoning” to mean iterative refinement and selection of continuous latent control hypotheses, rather than explicit symbolic reasoning or decoded rationales. Latent reasoning offers a middle ground: continuous CoT, latent compression, SoftCoT, and recurrent-depth VLA show that deliberation can occur without decoding intermediate text and can benefit robotic policies [9, 10, 11, 12]. This motivates an internal VLA compute mechanism with depth/width controls and an unchanged action interface, making gains attributable to repeated correction, hypothesis coverage, or learned path selection rather than an opaque backbone change.




Figure 1: Conceptual comparison between standard VLA, explicit CoT VLA, and MPCoT. MPCoT keeps deliberation in continuous latent space, enabling multi-step/multi-path reasoning without changing the action interface or generating reasoning tokens.

We propose *MPCoT*, a multi-path latent reasoning module for VLA decision making. Given an observation and instruction, MPCoT instantiates multiple latent hypotheses from the same grounded state, refines each branch with a weight-tied operator for depth K , and softly aggregates M branches before action decoding. Beyond single-trajectory latent refinement, MPCoT preserves parallel latent hypotheses and learns execution-aware preferences. At deployment, a chosen configuration spends compute through refinement steps or active hypotheses without changing the policy interface. A training-only reward-guided objective aligns the scorer with downstream execution quality while preserving reward-free action decoding. At inference, MPCoT is reward-free, token-free, and interface-preserving: an internal deliberation layer before the unchanged action head, not a backbone replacement. Fig. 1 contrasts standard VLA, explicit CoT VLA, and MPCoT.

Contributions. The main contributions are fourfold:

- We frame VLA reasoning as an embodied test-time compute allocation problem between high-cost explicit reasoning and shallow one-pass control.
- We introduce MPCoT, a recurrent multi-path latent reasoning module with explicit depth/width controls (K, M) , zero reasoning tokens, and an unchanged action interface.
- We introduce reward-guided path preference learning to align latent branch scores with downstream execution quality using action consistency, VLM progress, and success feedback.
- We validate MPCoT on LIBERO/CALVIN, showing benchmark gains, depth/width complementarity, efficient scaling, and reward-supervised path preference learning.

2 RELATED WORK

Open VLA policies and benchmarks. VLA research has progressed from language-grounded affordance selection and robot transformers to open VLA backbones and efficient fine-tuning frameworks [13, 1, 2, 3, 4, 5]. OpenVLA-OFT is our reference backbone because it provides a strong reproducible 8-step action-chunk interface. Recent methods such as π_0 , UnifiedVLA, FLOWER, VLA-Adapter, and AVA-VLA improve VLA policies through stronger action modeling, architecture design, or adaptation strategies [14, 15, 16, 17, 18]. MPCoT is orthogonal to these advances: it inserts lightweight latent deliberation before the unchanged action head and evaluates this internal compute mechanism on LIBERO and CALVIN, acting as an internal reasoning layer rather than a backbone replacement.




Figure 2: MPCoT architecture with training-time path supervision. Multiple latent branches are refined for K shared steps, scored, and softly aggregated before action decoding. During training only, candidate action branches receive action, world-model/VLM progress, and success feedback to supervise the scorer; this reward branch is removed at inference.

Reasoning-augmented VLA and latent test-time compute. Explicit reasoning methods such as CoT-VLA, TraceVLA, and WorldVLA make intermediate deliberation visible, but textual, visual, or trace-based steps can introduce token/intermediate-prediction overhead and do not always align naturally with continuous closed-loop control [8, 19, 20]. Continuous and compressed reasoning methods instead show that deliberation can occur in hidden space without decoding intermediate text [9, 10, 21, 22, 23], and SoftCoT motivates soft hypothesis preservation and confidence-weighted selection under uncertainty [11]. Closest to MPCoT, recurrent-depth VLA studies how repeated latent updates improve a single refinement trajectory [12], while broader test-time-compute work analyzes accuracy–latency trade-offs [24]. MPCoT treats latent inference compute as depth–width allocation. Depth K repeatedly corrects each hypothesis with shared weights, whereas width M maintains grounded latent hypotheses before one unchanged policy head. The scorer selects among execution-aware hypotheses, so width is not an ensemble, extra action heads, action-token expansion, inference-time rollout, or an external evaluator. Reward feedback trains only this scorer and is removed at inference.

3 METHOD

Overview. Fig. 2 details the MPCoT architecture and its training-time path supervision. At each control step, MPCoT initializes M latent hypotheses, applies K shared refinement steps, and aggregates the refined branches with confidence-aware soft weights before action decoding [11]. MPCoT is neither a multi-policy ensemble nor inference-time search: it runs one policy head with lightweight latent refinement. All intermediate reasoning remains in continuous latent space [9, 10, 21, 22, 23], avoiding rationale tokens. During training only, candidate branches receive reward feedback that supervises the scorer used later for reward-free inference. This modular placement attributes improvements to latent reasoning before the same action head, with inference overhead captured by reported latency rather than hidden in reward search.

3.1 Problem Setup and Design Targets

At each control step t , the policy receives observation o_t and instruction l and predicts action chunk a_t . We apply a latent reasoning module $\mathcal{R}_\theta$ before the policy decoder π_0 :

$$\bar{z}_t = \mathcal{R}_\theta(o_t, l; K, M), \quad a_t \sim \pi_0(a \mid \bar{z}_t), \quad (1)$$

$\mathcal{R}_\theta$ refines the same perception-language evidence before policy decoding. We instantiate π_0 with OpenVLA-OFT [5] and enforce an unchanged action interface, explicit compute control, and small

overhead through weight tying. Here K controls how many times the same recurrent refiner is applied, and M controls how many hypotheses are instantiated from the same context; $(K, M) = (0, 1)$ recovers direct decoding and $M = 1$ reduces MPCoT to single-path latent iterative reasoning. This separation tests whether gains come from depth, width, or their combination before the same decoder.

3.2 Backbone Interface and Latent Hypothesis Initialization

Let $f_v(\cdot)$, $f_l(\cdot)$, and $f_{\text{mm}}(\cdot)$ denote the visual encoder, language encoder, and multimodal fusion block. The fused latent context is

$$c_t = f_{\text{mm}}(f_v(o_t), f_l(l)), \quad c_t \in \mathbb{R}^d. \quad (2)$$

Here d follows the OpenVLA-OFT latent width. All paths start from the same grounded context, so differences reflect latent control-hypothesis specialization rather than perceptual changes. To create M parallel reasoning hypotheses, we initialize

$$z_{t,m}^{(0)} = c_t + e_m + \epsilon_{t,m}, \quad m = 1, \dots, M, \quad (3)$$

where $e_m \in \mathbb{R}^d$ is a learnable hypothesis code from a fixed maximum path pool and $\epsilon_{t,m}$ is a small training-time perturbation (zero for deterministic inference). The active width M selects hypotheses from this pool without new policy heads or inference-only parameters; e_m encourages specialization, while $\epsilon_{t,m}$ discourages collapse during training.

3.3 Weight-Tied Multi-Step Latent Refinement

For each path, we unroll a shared refinement operator F_θ for K steps:

$$r_{t,m}^{(k)} = F_\theta \left([\text{LN}(z_{t,m}^{(k-1)}); c_t] \right), \quad (4)$$

$$z_{t,m}^{(k)} = z_{t,m}^{(k-1)} + r_{t,m}^{(k)}, \quad k = 1, \dots, K. \quad (5)$$

Eq. (4) predicts a correction direction, and Eq. (5) applies it as a residual update. All paths are processed in parallel, while the same F_θ is reused across steps. Thus changing K increases computation but not parameter count. Conditioning each update on context c_t prevents instruction drift and keeps refinement aligned with current perception-language evidence.

3.4 Reward-Guided Path Preference Learning

After K refinement steps, MPCoT obtains M candidate latent branches $z_{t,m}^{(K)}$. A lightweight scorer assigns path logits and soft selection probabilities:

$$s_{t,m} = h_\omega(z_{t,m}^{(K)}), \quad p_\omega(m | o_t, l) = \frac{\exp(s_{t,m}/\tau)}{\sum_{j=1}^M \exp(s_{t,j}/\tau)}. \quad (6)$$

The same probabilities serve as aggregation weights:

$$\bar{z}_t^{(K)} = \sum_{m=1}^M p_\omega(m | o_t, l) z_{t,m}^{(K)}. \quad (7)$$

To make the scorer execution-aware, MPCoT uses a training-only path-preference signal. Each refined branch is decoded into a candidate action chunk by the unchanged policy head. During training, candidate branches are independently scored by a fixed world-model/VLM progress evaluator, or equivalent branch evaluator, on predicted or evaluated after-action progress. Together with expert-action consistency and success labels, this yields the composite branch reward:

$$r_{t,m} = \beta_a r_{t,m}^{\text{act}} + \beta_p r_{t,m}^{\text{prog}} + \beta_s r_{t,m}^{\text{succ}}. \quad (8)$$

These rewards are converted into detached path advantages and used to train h_ω with an advantage-weighted path-selection objective. The objective supervises which latent hypothesis should be

trusted under the observation and instruction, rather than replacing behavior cloning or injecting reward search. For this reward-preference term, gradients pass only through the differentiable scorer logits, not through the evaluator, reward computation, or returns. The learned scorer therefore becomes a reward-free proxy for execution quality at deployment rather than a test-time reward search. At inference, MPCoT never rolls out candidate branches, queries the world-model/VLM evaluator, or accesses rewards and success labels; it only uses the learned scorer and Eq. (7). Appendix B gives the full reward definitions, return/baseline objective, and training-side evaluation protocol.

3.5 Action Decoding and Training Objective

The aggregated latent is decoded by the unchanged policy head into the same 8-step action chunk:

$$a_t \sim \pi_0(a \mid \bar{z}_t^{(K)}). \quad (9)$$

MPCoT is trained end-to-end with behavior cloning, reward-guided path preference, and a diversity regularizer that discourages path collapse:

$$\mathcal{L} = \mathcal{L}_{\text{BC}} + \lambda_{\text{RL}} \mathcal{L}_{\text{RL}} + \lambda_{\text{div}} \mathcal{L}_{\text{div}}. \quad (10)$$

During optimization, K and M define the training configuration used to form branch rewards and aggregation. It supervises the refiner and scorer only; it is not a train-to-test budget schedule. With compute dropout, we sample sub-configurations $\hat{K} \leq K$ and $\hat{M} \leq M$ within this configuration. At deployment, MPCoT uses the reported inference configuration without reward evaluation, rollout, or VLM/world-model queries. Appendix B provides the loss terms.

3.6 Architecture and Complexity

All quantitative results use fixed configurations to isolate latent depth and width; the adaptive budget controller is described in Appendix A and is not used in the reported numbers. F_θ is a lightweight weight-tied residual MLP, h_ω is a two-layer path scorer, and hypothesis codes are learned jointly. MPCoT adds about 2.7% parameters relative to the backbone, while inference cost scales approximately linearly with $K \times M$ because refinement weights are shared across steps. This cost is measured in Table 4; no VLM/world-model evaluator is used at inference. Appendix C gives details.

4 EXPERIMENTS

4.1 Experimental Setup, Metrics, and Protocol

We insert MPCoT into OpenVLA-OFT and use official evaluation code and splits. Unless noted, training/evaluation follow OpenVLA-OFT defaults [5]; MPCoT preserves same 8-step action interface. Main results use fixed inference $(K, M) = (5, 4)$; other settings appear in depth K /width M ablations. They change latent steps and hypotheses only, not backbone, decoder, action horizon, splits, or observations. Training-side candidate evaluation supervises path preference, not train-to-test scheduling. Settings are in Appendix A. LIBERO is a near-ceiling compatibility benchmark, while CALVIN ABC→D and mechanism ablations provide primary evidence for sequential robustness, depth/width scaling, and reward-guided path supervision.

Metrics. For LIBERO, we report suite-level and average success rates (SR). For CALVIN ABC→D, we report 1–5-step SR and average successful sequence length, reflecting error accumulation over longer instruction chains. For reward-supervision analysis, Path Consistency measures agreement between the scorer-preferred path and the highest-return path; Appendix B gives the definition. Mechanism ablations additionally report path similarity and stability.

Protocol and comparability. In all tables, **MPCoT (Ours)** denotes **OpenVLA-OFT + MPCoT**. At inference, MPCoT receives only observation/language inputs, outputs the same fixed 8-step action chunk, and never accesses rewards, VLM-progress evaluators, or success labels. Reward signals

Table 1: Comparison on LIBERO. (a) One policy for all 4 suites. (b) One policy per suite.

(a) One policy for all 4 suites.					
Method	Spatial SR (%)	Object SR (%)	Goal SR (%)	Long SR (%)	Average SR (%)
TraceVLA [19]	84.6	85.2	75.1	54.1	74.8
WorldVLA [20]	87.6	96.2	83.4	60.0	81.8
π_0 [14]	96.8	98.8	95.8	85.2	94.2
π_0 -FAST [25]	96.4	96.8	88.6	60.2	85.5
UnifiedVLA [15]	95.4	98.8	93.6	94.0	95.5
OpenVLA-OFT [5]	97.7	98.0	96.1	95.3	96.8
AVA-VLA [18]	97.4	99.4	97.4	97.6	98.0
MPCoT (Ours)	98.2	99.7	98.6	98.9	98.9

(b) One policy per suite.					
Method	Spatial SR (%)	Object SR (%)	Goal SR (%)	Long SR (%)	Average SR (%)
OpenVLA [4]	84.7	88.4	79.2	53.7	76.5
SpatialVLA [26]	88.2	89.9	78.6	55.5	78.1
CoT-VLA [8]	87.5	91.6	87.6	69.0	83.9
NORA [27]	92.2	95.4	89.4	74.6	87.9
PD-VLA [28]	95.5	96.7	94.9	91.7	94.7
UniVLA [29]	96.5	96.8	95.6	92.0	95.2
OpenVLA-OFT [5]	97.6	98.4	97.9	94.5	97.1
FLOWER [16]	97.5	99.1	96.1	94.9	96.9
VLA-Adapter [17]	97.8	99.2	97.2	95.0	97.3
RIPT-VLA [30]	99.0	98.6	98.6	93.8	97.5
AVA-VLA [18]	99.2	99.6	98.2	96.2	98.3
MPCoT (Ours)	99.5	99.8	99.0	97.8	99.0

are auxiliary training-side supervision for the path scorer; otherwise, training/evaluation settings and benchmark splits follow OpenVLA-OFT. The “Textual CoT + Policy” row in Table 4 uses the same OpenVLA-OFT backbone and evaluation protocol, replacing MPCoT’s latent deliberation with a standard explicit textual CoT step; it serves as a matched reasoning-form baseline for comparing explicit-token and latent-token-free deliberation.

4.2 Main Benchmark Results on LIBERO

Table 1 evaluates MPCoT on LIBERO under both all-suite and suite-specific protocols. MPCoT improves OpenVLA-OFT from 96.8 to 98.9 average SR and from 95.3 to 98.9 Long SR in the all-suite setting, and reaches 99.0 average SR and 97.8 Long SR in the suite-specific setting. Because recent LIBERO systems are near ceiling, we interpret these gains mainly as compatibility evidence rather than the sole long-horizon claim.

4.3 Long-Horizon Generalization on CALVIN ABC→D

Table 2 evaluates CALVIN ABC→D, where policies train on A/B/C and test on held-out D, stressing sequential decision stability and cross-environment generalization.

MPCoT leads from 1-step through 5-step, with the largest gains appearing at longer horizons. At 4/5-step SR, MPCoT reaches 93.7/89.4, outperforming AVA-VLA by 3.8/5.3 points and OpenVLA-OFT by 13.3/16.5 points. This horizon-dependent improvement suggests that MPCoT does more than improve local action prediction: latent refinement and multi-path aggregation help maintain stable execution as early errors propagate. These results provide the main evidence that test-time latent reasoning is most beneficial under long-horizon uncertainty.

Table 2: Comparison on CALVIN ABC→D benchmark. Columns 1-step to 5-step report success rate (SR, %), and Avg. len reports average successful sequence length.

Method	1-step SR (%)	2-step SR (%)	3-step SR (%)	4-step SR (%)	5-step SR (%)	Avg. len
OpenVLA [4]	91.3	77.8	62.0	52.1	43.5	3.27
UniVLA [29]	95.5	85.8	75.4	66.9	56.5	3.80
UnifiedVLA [15]	98.9	94.8	89.0	82.8	75.1	4.41
OpenVLA-OFT [5]	96.9	92.0	85.7	80.4	72.9	4.28
FLOWER [16]	99.4	95.8	90.7	84.9	77.8	4.53
VLA-Adapter [17]	99.1	94.6	88.8	82.8	76.5	4.42
Seer [31]	96.3	91.6	86.1	80.3	74.0	4.28
AVA-VLA [18]	99.6	97.6	94.1	89.9	84.1	4.65
MPCoT (Ours)	99.8	98.9	96.8	93.7	89.4	4.92

Table 3: Effect of latent reasoning depth (K) and width (M). The CALVIN column reports 3-step success rate.

Variant	K	M	Agg.	LIBERO Avg	LIBERO Long	CALVIN 3-step SR (%)
OpenVLA-OFT (Direct)	0	1	–	96.8	95.3	85.7
Latent CoT	1	1	–	98.2	97.9	94.8
Latent CoT	3	1	–	98.4	98.1	95.6
Latent CoT	5	1	–	98.6	98.4	96.3
Multi-path Latent CoT	3	2	Soft	98.5	98.3	95.9
Multi-path Latent CoT	3	4	Soft	98.7	98.6	96.5
Multi-path Latent CoT	5	4	Soft	98.9	98.9	96.8

4.4 Latent Reasoning Structure Ablations

We next isolate MPCoT’s structural components: Table 3 varies reasoning depth K and width M , while Table A.3 studies aggregation and diversity.

Table 3 shows complementary effects of depth and width. With $M = 1$, increasing K from 1 to 5 improves LIBERO average/Long SR from 98.2/97.9 to 98.6/98.4, indicating that repeated latent correction improves a single control hypothesis. At fixed $K = 3$, increasing M to 4 further improves Long SR to 98.6, suggesting that parallel paths provide alternative hypotheses. The best $(K, M) = (5, 4)$ reaches 98.9 average SR, 98.9 Long SR, and 96.8 CALVIN 3-step SR. Appendix E further shows that soft aggregation with diversity regularization reduces path similarity from 0.91 to 0.66 and stability std from 0.41 to 0.18, indicating non-duplicated branches.

4.5 Test-Time Scaling and Reasoning Efficiency

Table 4 tests whether MPCoT scales test-time compute through latent depth and width while avoiding explicit-CoT token overhead.

Comparing fixed inference configurations, $(K, M) = (5, 4)$ improves LIBERO Long from 98.3 to 98.9 over $(3, 2)$, while increasing measured latency from 31ms to 38ms and preserving zero reasoning-token overhead. The matched textual CoT baseline reaches 98.2 Long SR but incurs 110–160ms latency, supporting the efficiency advantage of keeping deliberation in latent space. Thus MPCoT adds only the reported latent-refinement cost at inference, not a reward/world-model/VLM evaluation loop, while improving long-horizon control.

4.6 Reward-Guided Path Preference Supervision

Table 5 evaluates whether reward-guided path preference makes multi-path reasoning execution-aware. Removing reward supervision still yields a strong multi-path model but lowers Path

Table 4: Inference-configuration (K, M) scaling and reasoning-type comparison under the main reported evaluation protocol. “Latency” reports wall-clock milliseconds measured under the same runtime stack for comparison.

Reasoning Type	Inference (K, M)	Token Overhead	Latency	LIBERO Long (%)
OpenVLA-OFT (Direct)	–	0	24ms	95.3
Latent CoT	(3,1)	0	29ms	98.1
Latent CoT	(5,1)	0	33ms	98.4
Multi-path Latent CoT	(3,2)	0	31ms	98.3
Multi-path Latent CoT	(5,4)	0	38ms	98.9
Textual CoT + Policy	–	High	110–160ms	98.2

Table 5: Main reward-guided path preference ablation. Avg and Long denote LIBERO success rates. The table keeps all single reward components in the main text and reports the strongest pairwise setting; full pairwise results are in Appendix D.

Variant	Rewards	Avg	Long	CALVIN 3-step	CALVIN 4-step	Path Cons. (%)
w/o Reward	BC only	98.4	97.6	94.7	90.8	68.5
Action Only	r^{act}	98.6	98.0	95.3	91.7	73.2
Progress Only	r^{prog}	98.6	98.2	95.6	92.1	74.8
Success Only	r^{succ}	98.5	98.1	95.1	91.5	72.4
Best Pair	$r^{\text{prog}} + r^{\text{succ}}$	98.8	98.6	96.3	93.1	81.2
Full Reward (Ours)	$r^{\text{act}} + r^{\text{prog}} + r^{\text{succ}}$	98.9	98.9	96.8	93.7	84.3

Consistency; individual rewards help, the strongest pair improves further, and the full action+progress+success design performs best.

The full reward design raises Path Consistency from 68.5 to 84.3 and improves horizon metrics. Path Consistency is a training-side alignment diagnostic, and its increase indicates that the scorer is not merely learning a generic confidence prior but becomes aligned with higher-return branches. The trend from single rewards to the strongest pair and full reward suggests that action consistency, progress feedback, and episode success provide complementary path-scoring supervision. Appendix D reports all pairwise reward combinations.

5 CONCLUSION

We introduced MPCoT, a reward-guided multi-path latent reasoning module that supports VLA inference compute through repeated latent refinement depth K and active hypothesis width M while preserving the original action interface and generating zero reasoning tokens. On LIBERO and CALVIN, two standardized and widely used VLA benchmarks, MPCoT improves long-horizon performance over strong baselines; the ablations further support the roles of depth/width scaling, soft diverse aggregation, and training-only path preference learning.

6 LIMITATIONS

Our results are obtained on controlled benchmark environments, which are appropriate for isolating the latent reasoning mechanism and comparing against prior VLA methods under reproducible protocols. However, benchmarks do not fully capture embodiment variation, sensing noise, hardware latency, and contact-rich failures in real robots. At the same time, isolated real-robot demonstrations can also be task- and platform-specific, and are not automatically more representative than standardized benchmarks. The next step is therefore controlled hardware validation that preserves the same protocol discipline while testing robustness under real deployment conditions. MPCoT also relies on a training-side world-model/VLM evaluator for path preference supervision, although this evaluator is never queried at inference. We will release code, reward-evaluation details, configurations, latency scripts, and evaluation commands to support independent verification.

References

- [1] A. Brohan, N. Brown, J. Carbajal, Y. Chebotar, J. Dabis, C. Finn, K. Gopalakrishnan, K. Hausman, A. Herzog, J. Hsu, J. Ibarz, B. Ichter, A. Irpan, T. Jackson, S. Jesmonth, N. J. Joshi, R. Julian, D. Kalashnikov, Y. Kuang, I. Leal, K.-H. Lee, S. Levine, Y. Lu, U. Malla, D. Manjunath, I. Mordatch, O. Nachum, C. Parada, J. Peralta, E. Perez, K. Pertsch, J. Quiambao, K. Rao, M. Ryoo, G. Salazar, P. Sanketi, K. Sayed, J. Singh, S. Sontakke, A. Stone, C. Tan, H. Tran, V. Vanhoucke, S. Vega, Q. Vuong, F. Xia, T. Xiao, P. Xu, S. Xu, T. Yu, and B. Zitkovich. RT-1: Robotics transformer for real-world control at scale. In *Proc. Robot.: Sci. Syst. (RSS)*, 2023.
- [2] D. Driess, F. Xia, M. S. M. Sajjadi, C. Lynch, A. Chowdhery, B. Ichter, A. Wahid, J. Tompson, Q. Vuong, T. Yu, W. Huang, Y. Chebotar, P. Sermanet, D. Duckworth, S. Levine, V. Vanhoucke, K. Hausman, M. Toussaint, K. Greff, A. Zeng, I. Mordatch, and P. Florence. PaLM-E: An embodied multimodal language model. In *Proc. Int. Conf. Mach. Learn. (ICML)*, 2023.
- [3] A. Brohan, N. Brown, J. Carbajal, Y. Chebotar, X. Chen, K. Choromanski, T. Ding, D. Driess, A. Dubey, C. Finn, P. Florence, C. Fu, M. G. Arenas, K. Gopalakrishnan, K. Han, K. Hausman, A. Herzog, J. Hsu, B. Ichter, A. Irpan, N. Joshi, R. Julian, D. Kalashnikov, Y. Kuang, I. Leal, L. Lee, T.-W. E. Lee, S. Levine, Y. Lu, H. Michalewski, I. Mordatch, K. Pertsch, K. Rao, K. Reymann, M. Ryoo, G. Salazar, P. Sanketi, P. Sermanet, J. Singh, A. Singh, R. Soricut, H. Tran, V. Vanhoucke, Q. Vuong, A. Wahid, S. Welker, P. Wohlhart, J. Wu, F. Xia, T. Xiao, P. Xu, S. Xu, T. Yu, and B. Zitkovich. RT-2: Vision-language-action models transfer web knowledge to robotic control. In *Proc. Conf. Robot Learn. (CoRL)*, 2023.
- [4] M. J. Kim, K. Pertsch, S. Karamcheti, T. Xiao, A. Balakrishna, S. Nair, R. Rafailov, E. Foster, G. Lam, P. Sanketi, Q. Vuong, T. Kollar, B. Burchfiel, R. Tedrake, D. Sadigh, S. Levine, P. Liang, and C. Finn. OpenVLA: An open-source vision-language-action model. In *Proc. Conf. Robot Learn. (CoRL)*, 2024.
- [5] M. J. Kim, C. Finn, and P. Liang. Fine-tuning vision-language-action models: Optimizing speed and success. In *Proc. Robot.: Sci. Syst. (RSS)*, 2025.
- [6] B. Liu, Y. Zhu, C. Gao, Y. Feng, Q. Liu, Y. Zhu, and P. Stone. LIBERO: Benchmarking knowledge transfer for lifelong robot learning. In *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, 2023.
- [7] J. Wei, X. Wang, D. Schuurmans, M. Bosma, B. Ichter, F. Xia, E. Chi, Q. Le, and D. Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, 2022.
- [8] Q. Zhao, Y. Lu, M. J. Kim, Z. Fu, Z. Zhang, Y. Wu, Z. Li, Q. Ma, S. Han, C. Finn, A. Handa, M.-Y. Liu, D. Xiang, G. Wetzstein, and T.-Y. Lin. CoT-VLA: Visual chain-of-thought reasoning for vision-language-action models. In *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2025.
- [9] Y. Hao and S. Sukbaatar. Training large language models to reason in a continuous latent space, 2024. arXiv:2412.06769.
- [10] Z. Shen, H. Yan, L. Zhang, Z. Hu, Y. Du, and Y. He. CODI: Compressing chain-of-thought into continuous space via self-distillation. In *Proc. Conf. Empir. Methods Nat. Lang. Process. (EMNLP)*, 2025.
- [11] Y. Xu, X. Guo, Z. Zeng, and C. Miao. SoftCoT: Soft chain-of-thought for efficient reasoning with LLMs. In *Proc. Annu. Meeting Assoc. Comput. Linguist. (ACL)*, 2025.
- [12] Y. Tur, J. Naghiyev, H. Fang, W.-C. Tsai, J. Duan, D. Fox, and R. Krishna. Recurrent-depth VLA: Implicit test-time compute scaling of vision-language-action models via latent iterative reasoning, 2026. arXiv:2602.07845.

- [13] M. Ahn, A. Brohan, N. Brown, Y. Chebotar, O. Cortes, B. David, C. Finn, C. Fu, K. Gopalakrishnan, K. Hausman, A. Herzog, D. Ho, J. Hsu, J. Ibarz, B. Ichter, A. Irpan, E. Jang, R. J. Ruano, K. Jeffrey, S. Jesmonth, N. J. Joshi, R. Julian, D. Kalashnikov, Y. Kuang, K.-H. Lee, S. Levine, Y. Lu, L. Luu, C. Parada, P. Pastor, J. Quiambao, K. Rao, J. Rettinghouse, D. Reyes, P. Sermanet, N. Sievers, C. Tan, A. Toshev, V. Vanhoucke, F. Xia, T. Xiao, P. Xu, S. Xu, M. Yan, and A. Zeng. Do as I can, not as I say: Grounding language in robotic affordances. In *Proc. Conf. Robot Learn. (CoRL)*, 2022.
- [14] K. Black, N. Brown, D. Driess, A. Esmail, M. Equi, C. Finn, N. Fusai, L. Groom, K. Hausman, B. Ichter, S. Jakubczak, T. Jones, L. Ke, S. Levine, A. Li-Bell, M. Mothukuri, S. Nair, K. Pertsch, L. X. Shi, J. Tanner, Q. Vuong, A. Walling, H. Wang, and U. Zhilinsky. π_0 : A vision-language-action flow model for general robot control, 2024. arXiv:2410.24164.
- [15] Y. Wang, X. Li, W. Wang, J. Zhang, Y. Li, Y. Chen, X. Wang, and Z. Zhang. Unified vision-language-action model, 2025. arXiv:2506.19850.
- [16] M. Reuss, H. Zhou, M. Ruhle, O. E. Yagmurlu, F. Otto, and R. Lioutikov. FLOWER: Democratizing generalist robot policies with efficient vision-language-action flow policies, 2025. arXiv:2509.04996.
- [17] Y. Wang, P. Ding, L. Li, C. Cui, Z. Ge, X. Tong, W. Song, H. Zhao, W. Zhao, P. Hou, S. Huang, Y. Tang, W. Wang, R. Zhang, J. Liu, and D. Wang. VLA-Adapter: An effective paradigm for tiny-scale vision-language-action model, 2025. arXiv:2509.09372.
- [18] L. Xiao, J. Li, J. Gao, F. Ye, Y. Jin, J. Qian, J. Zhang, Y. Wu, and X. Yu. AVA-VLA: Improving vision-language-action models with active visual attention, 2025. arXiv:2511.18960.
- [19] R. Zheng, Y. Liang, S. Huang, J. Gao, H. Daume, A. Kolobov, F. Huang, and J. Yang. TraceVLA: Visual trace prompting enhances spatial-temporal awareness for generalist robotic policies. In *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2025.
- [20] J. Cen, C. Yu, H. Yuan, Y. Jiang, S. Huang, J. Guo, X. Li, Y. Song, H. Luo, F. Wang, D. Zhao, and H. Chen. WorldVLA: Towards autoregressive action world model, 2025. arXiv:2506.21539.
- [21] J. Cheng and B. V. Durme. Compressed chain of thought: Efficient reasoning through dense representations, 2024. arXiv:2412.13171.
- [22] X. Shen, Y. Wang, X. Shi, Y. Wang, P. Zhao, and J. Gu. Efficient reasoning with hidden thinking, 2025. arXiv:2501.19201.
- [23] D. Su, H. Zhu, Y. Xu, J. Jiao, Y. Tian, and Q. Zheng. Token assorted: Mixing latent and text tokens for improved language model reasoning. In *Proc. Int. Conf. Mach. Learn. (ICML)*, 2025.
- [24] Z. Lin, Z. Fu, Z. Chen, C. Chen, L. Xie, W. Wang, D. Cai, Z. Wang, and J. Ye. Controlling thinking speed in reasoning models, 2025. arXiv:2507.03704.
- [25] K. Pertsch, K. Stachowicz, B. Ichter, D. Driess, S. Nair, Q. Vuong, O. Mees, C. Finn, and S. Levine. FAST: Efficient action tokenization for vision-language-action models, 2025. arXiv:2501.09747.
- [26] D. Qu, H. Song, Q. Chen, Y. Yao, X. Ye, Y. Ding, Z. Wang, J. Gu, B. Zhao, D. Wang, and X. Li. SpatialVLA: Exploring spatial representations for visual-language-action models. In *Proc. Robot.: Sci. Syst. (RSS)*, 2025.
- [27] C.-Y. Hung, Q. Sun, P. Hong, A. Zadeh, C. Li, U.-X. Tan, N. Majumder, and S. Poria. NORA: A small open-sourced generalist vision language action model for embodied tasks, 2025. arXiv:2504.19854.

- [28] W. Song, J. Chen, P. Ding, H. Zhao, W. Zhao, Z. Zhong, Z. Ge, Z. Li, D. Wang, J. Ma, L. Wang, and H. Li. PD-VLA: Accelerating vision-language-action model integrated with action chunking via parallel decoding. In *Proc. IEEE/RSJ Int. Conf. Intell. Robots Syst. (IROS)*, 2025.
- [29] Q. Bu, Y. Yang, J. Cai, S. Gao, G. Ren, M. Yao, P. Luo, and H. Li. UniVLA: Learning to act anywhere with task-centric latent actions, 2025. arXiv:2505.06111.
- [30] S. Tan, K. Dou, Y. Zhao, and P. Krahenbuhl. Interactive post-training for vision-language-action models, 2025. arXiv:2505.17016.
- [31] Y. Tian, S. Yang, J. Zeng, P. Wang, D. Lin, H. Dong, and J. Pang. Predictive inverse dynamics models are scalable learners for robotic manipulation. In *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2025.

Appendix

A Implementation and Experimental Settings

We summarize implementation and training settings in Table A.1, followed by reward evaluation and optional adaptive budgeting details.

Table A.1: OpenVLA-OFT and MPCoT settings.

Item	Value
Backbone	OpenVLA-OFT (7B)
Fine-tuning	LoRA r=32; parallel decoding; L1 continuous action
Inputs	2 views + lang + proprio, 224×224
Inference	8-step chunk (predict 8, exec 8 open-loop)
Optim	LR 5×10^{-4} ; decay to 5×10^{-5} @100K; BS=64
Train steps	150K (S/O/L); 50K (Goal)
Training-side candidate-evaluation config	$K = 3$, $M = 2$ for auxiliary path-preference supervision
Main inference reasoning config	$K = 5$, $M = 4$ for the main reported MPCoT results
Max hypothesis pool	$M_{\max} = 4$
τ ; λ_{div} , γ	0.7; 0.05, $d/4$
Reward evaluator	World-model/VLM progress evaluator (training only; fixed across reward ablations)
Reward weights (Full)	$\beta_a = \beta_p = \beta_s = 1$
λ_{RL} ; RL baseline	1.0; path-average baseline
β_K , β_M	4, 3

Clarification of training-side and inference-side configurations. The training-side candidate-evaluation configuration and the inference reasoning configuration serve different purposes. The former controls how many candidate branches are used to compute auxiliary path-preference supervision during optimization, while the latter controls how many latent refinement steps and active hypotheses are used by the deployed policy during evaluation. They are reported separately for reproducibility and should not be interpreted as a progressive train-to-test budget schedule.

Training-side reward evaluation. The progress evaluator is an auxiliary world-model/VLM module used only during training. Given the current scene, instruction, and a candidate action branch, it predicts or scores the after-action scene and returns a scalar progress signal. Its role is to provide detached relative preference supervision for the path scorer; it is not the deployed policy, is not queried at inference, and is kept fixed across reward ablations.

Optional adaptive budget rule. Although all quantitative results use fixed inference (K, M) configurations, MPCoT can optionally allocate compute using previous-step uncertainty:

$$K_t = \min(K_{\max}, K_{\min} + \lfloor \beta_K u_{t-1} \rfloor), \quad (\text{A.1})$$

$$M_t = \min(M_{\max}, M_{\min} + \lfloor \beta_M u_{t-1} \rfloor), \quad (\text{A.2})$$

where u_0 is initialized by a default budget. This optional controller is a deployment extension and is not used in reported results.

B Reward-Objective Details

Path consistency metric. For reward-supervision analysis, we report

$$\text{PathConsistency} = \frac{1}{N} \sum_{i=1}^N \mathbf{1} \left[\arg \max_m s_{i,m} = \arg \max_m R_{i,m} \right]. \quad (\text{A.3})$$

Path-conditioned candidate evaluation. During training, each refined branch $z_{t,m}^{(K)}$ is decoded into a candidate action chunk using the unchanged policy head:

$$a_{t,m} \sim \pi_0(a \mid z_{t,m}^{(K)}). \quad (\text{A.4})$$

Candidate action branches are then evaluated independently by the training-only world-model/VLM evaluator or branch rollout. Thus reward differences reflect the decoded action induced by each latent branch rather than the final action chosen at inference.

Reward components. The action reward provides local expert-action consistency,

$$r_{t,m}^{\text{act}} = -\|a_{t,m} - a_t^*\|_2^2. \quad (\text{A.5})$$

The progress reward is estimated by the auxiliary world-model/VLM evaluator. Let $\hat{\xi}_{t+1,m} = W_\phi(\xi_t, g, a_{t,m})$ denote the predicted or evaluated after-action scene for branch m ; then

$$r_{t,m}^{\text{prog}} = P_\phi(\hat{\xi}_{t+1,m}, g) - P_\phi(\xi_t, g), \quad (\text{A.6})$$

where P_ϕ maps a scene and task goal to a scalar progress score. The sparse success reward uses the branch-level success label,

$$r_{t,m}^{\text{succ}} = \mathbb{I}[\text{branch } m \text{ is labeled successful}]. \quad (\text{A.7})$$

All reward components train only the path scorer and are removed at inference.

Path return and scorer objective. We define the discounted path return, path-average baseline, and advantage as

$$R_{t,m} = \sum_{\ell=t}^T \gamma^{\ell-t} r_{\ell,m}, \quad (\text{A.8})$$

$$b_t = \frac{1}{M} \sum_{j=1}^M R_{t,j}, \quad (\text{A.9})$$

$$A_{t,m} = R_{t,m} - b_t. \quad (\text{A.10})$$

The reward-guided path-preference loss is

$$\mathcal{L}_{\text{RL}} = -\mathbb{E}_{m \sim p_\omega} [\text{sg}(A_{t,m}) \log p_\omega(m \mid o_t, l)], \quad (\text{A.11})$$

where $\text{sg}(\cdot)$ denotes stop-gradient. Gradients are stopped through reward, return, baseline, and advantage computation; the objective updates only the differentiable path-selection logits.

Behavior cloning and diversity regularization. The behavior-cloning term is

$$\mathcal{L}_{\text{BC}} = \mathbb{E}_{(o_t, l, a_t^*)} \left[\ell \left(\pi_0(\cdot \mid \bar{z}_t^{(K)}), a_t^* \right) \right]. \quad (\text{A.12})$$

To reduce path collapse, we use

$$\mathcal{L}_{\text{div}} = \frac{1}{M(M-1)} \sum_{m \neq j} \exp \left(-\frac{\|z_{t,m}^{(K)} - z_{t,j}^{(K)}\|_2^2}{\gamma} \right). \quad (\text{A.13})$$

C Architecture and Complexity Details

The refinement operator F_θ is a lightweight weight-tied residual MLP with LayerNorm, expansion ratio 4, GELU, and dropout 0.1. The path scorer h_ω is a two-layer MLP over final path states, and hypothesis codes are learned jointly to encourage specialization. Let C_{base} denote backbone cost, C_{ref} per-step refinement cost, and C_{score} per-path scoring cost. For fixed (K, M) ,

$$C_{\text{test}} \approx C_{\text{base}} + KM C_{\text{ref}} + M C_{\text{score}}. \quad (\text{A.14})$$

Thus inference compute scales approximately linearly with $K \times M$, while parameter growth remains small because refinement weights are shared across steps and memory overhead is dominated by storing M latent states, $\mathcal{O}(Md)$.

D Full Reward-Guided Path Preference Ablation

Table A.2: Ablation of reward-guided path preference supervision under the same protocol as the main results. Avg and Long denote LIBERO success rates. In all reward ablations, $(\beta_a, \beta_p, \beta_s)$ are switched on/off according to the selected reward components; the full setting uses $\beta_a = \beta_p = \beta_s = 1$, with all other training and evaluation settings fixed. Path Consistency measures agreement between the path preferred by the learned scorer and the path with the highest reward-defined return.

Variant	Rewards	Avg	Long	CALVIN 3-step	CALVIN 4-step	Path Cons. (%)
w/o Reward	BC only	98.4	97.6	94.7	90.8	68.5
Action Reward Only	r^{act}	98.6	98.0	95.3	91.7	73.2
Progress Reward Only	r^{prog}	98.6	98.2	95.6	92.1	74.8
Success Reward Only	r^{succ}	98.5	98.1	95.1	91.5	72.4
Action + Progress	$r^{\text{act}} + r^{\text{prog}}$	98.7	98.5	96.1	92.8	79.6
Action + Success	$r^{\text{act}} + r^{\text{succ}}$	98.7	98.4	95.9	92.6	78.9
Progress + Success	$r^{\text{prog}} + r^{\text{succ}}$	98.8	98.6	96.3	93.1	81.2
Full Reward (Ours)	$r^{\text{act}} + r^{\text{prog}} + r^{\text{succ}}$	98.9	98.9	96.8	93.7	84.3

E Additional Mechanism Ablations

Table A.3: Multi-path reasoning mechanism ablation. Lower similarity indicates more diverse hypotheses.

Variant	Soft	Div.	Sim. ↓	Avg. (%)	Long (%)	Std ↓
Single-path Latent CoT ($K=3, M=1$)	No	No	–	98.4	98.1	0.52
Multi-path (Hard argmax)	No	No	0.90	98.5	98.2	0.84
Multi-path (Uniform avg)	Yes	No	0.83	98.6	98.4	0.53
Multi-path (Soft, no reg)	Yes	No	0.91	98.7	98.6	0.41
Multi-path (Ours, $K=3, M=4$)	Yes	Yes	0.66	98.7	98.6	0.18