
IDOL: Inverse-Dynamics-Guided Future Prediction for End-to-End Autonomous Driving

Chenghao Zhang, Timin Li, Dongmei Li

Department of Electronic Engineering, Tsinghua University

zhangch24@mails.tsinghua.edu.cn, litm22@mails.tsinghua.edu.cn, lidmei@tsinghua.edu.cn

Abstract

End-to-end autonomous driving has emerged as a compelling paradigm for learning planning directly from sensor observations, while recent world-model-based approaches further enrich this paradigm by enabling explicit reasoning about how the scene may evolve in the future. Yet future prediction alone does not guarantee better planning unless the predicted evolution can be converted into planning-relevant trajectory updates. Many current methods still forecast future scene states without explicitly decoding the motion implications hidden in state transitions. As a result, future reasoning often remains descriptively useful but only weakly coupled to executable motion generation. To address this limitation, we propose **IDOL**, an inverse-dynamics-guided future prediction framework for world-model-based end-to-end planning in latent BEV space, where inverse dynamics serves as the key bridge between future prediction and trajectory optimization. IDOL first predicts multiple future latent scene states with a BEV world model, then applies an inverse dynamics model to adjacent latent futures to decode transition-aware trajectory features and recover planning-relevant motion deltas that explain how the latent world evolves over time. These inverse-dynamics-derived signals are used to optimize the planned trajectory, turning future forecasting from passive scene anticipation into actionable planning guidance. A lightweight closed-loop refinement module further improves long-horizon consistency by reusing the optimized trajectory for another round of future-aware reasoning. By introducing inverse dynamics into latent future reasoning, IDOL tightens the coupling between world modeling and planning. Extensive experiments on the NAVSIM v1 and NAVSIM v2 benchmarks show that IDOL achieves state-of-the-art performance among comparable methods.

1 Introduction

Autonomous driving[27, 5, 55, 40, 46, 14, 22, 58] has advanced significantly in recent years, driven by a paradigm shift from modular perception-prediction-planning pipelines to unified end-to-end learning frameworks. Recent advances have further expanded this paradigm toward future-aware, world-model-guided planning[78, 68], scalable sim-real training[59], and video-centric pretraining[52], leading to markedly stronger robustness and planning performance on realistic benchmarks such as nuScenes[2] and NAVSIM[9]. At the same time, multimodal and generative formulations[70, 45, 35, 80] have shown that planning quality can benefit substantially from moving beyond deterministic single-pass regression. More recently, VLA-based systems[32, 25, 47] extended the scope of future-aware decision making by injecting language-grounded reasoning, action abstraction, and reflective post-training into driving systems.

For trajectory planning, traditional end-to-end autonomous driving methods[57, 62] typically rely on the current state, which constitutes a form of passive planning, as illustrated in Figure 1(a). Subsequently, many approaches[28, 29] have introduced world models into end-to-end planning,




Figure 1: Comparison of three planning paradigms. (a) Traditional methods directly map sensor inputs to a predicted trajectory. (b) World-model-based methods additionally predict future latent BEV states to support planning, but these predicted futures are only loosely connected to motion generation. (c) In contrast, IDOL further applies an inverse dynamics model to adjacent future latent BEV states to extract transition-aware motion cues for trajectory refinement, making future prediction more actionable for planning.

adopting the predict-decide paradigm to make decision-making more foresighted, as illustrated in Figure 1(b).

Yet a fundamental bottleneck remains: even when future prediction is available, current methods[38, 77] still leave a weak and poorly interpretable bridge between forecasting how the scene may evolve and using that evolution to produce dynamically meaningful trajectory updates. Consequently, predicted futures may be informative without being sufficiently actionable. The planner may know what could happen next, yet still lack a principled mechanism for determining how the current trajectory should be revised so that it remains executable, dynamically coherent, and robust over long horizons. This gap becomes especially harmful in safety-critical driving, where future reasoning must ultimately serve motion generation rather than remain passive forecasting. Our key insight is that *the missing signal lies not only in the predicted future states themselves, but more importantly in the transitions between them*. As illustrated in Figure 1(c), inverse dynamics provides a natural way to decode this signal: unlike forward world modeling, which predicts how the scene will evolve given a motion hypothesis, inverse dynamics asks the complementary question of *what motion-relevant change is implied by the evolution from one state to the next*. In latent Bird’s Eye View space, adjacent predicted futures encode how the ego vehicle and surrounding scene are expected to evolve under a particular planning hypothesis, and the transition from one latent future to the next therefore contains recoverable motion semantics that implicitly reflect the trajectory adjustment most consistent with the predicted scene evolution. Rather than treating future latent states as static planning features, we decode adjacent latent transitions with an inverse dynamics model to extract transition-aware trajectory features and infer motion deltas for planning optimization. In this way, inverse dynamics becomes the explicit bridge between world modeling and trajectory generation, turning future prediction from *passive scene forecasting* into *planning-aware transition reasoning*.

Based on this perspective, we propose **IDOL**, a world-model-based end-to-end planner that operates in latent BEV space and tightly couples future reasoning with trajectory optimization. IDOL first predicts multiple future latent scene states with a BEV world model, giving the planner access to anticipated scene evolution beyond the current observation. It then applies an inverse dynamics model to each pair of adjacent latent futures to infer motion-aware transition features and planning-relevant trajectory deltas that explain the predicted evolution. These inverse-dynamics-derived signals are aggregated and injected into the planning process to optimize the anchor trajectory, enabling the planner to revise its motion according to the dynamics implied by future state transitions rather than according to future context alone. A lightweight closed-loop refinement module is further introduced as a supplementary mechanism to re-evaluate the updated trajectory and improve long-horizon consistency.

In summary, our contributions are as follows:

- i. We identify a fundamental gap in recent end-to-end and world-model-based planners: current methods still lack a sufficiently explicit and interpretable mechanism for converting predicted future evolution into planning-relevant trajectory updates, which limits the actionability of future reasoning for executable motion generation.
- ii. We propose IDOL, a world-model-based end-to-end planner in latent BEV space that introduces inverse dynamics into latent future reasoning, thereby establishing an explicit bridge between world modeling and executable motion generation. We further design a lightweight closed-loop refinement module to improve long-horizon consistency through another round of future-aware reasoning.
- iii. We conduct extensive experiments on both NAVSIM v1 and NAVSIM v2, including comprehensive comparisons and analysis, and show that our method consistently achieves state-of-the-art performance among comparable methods. These results validate the effectiveness of our design in improving planning quality across different benchmark settings.

2 Related work

2.1 End-to-end autonomous driving

End-to-end autonomous driving[77, 41, 10, 34, 47, 4, 11] aims to map sensor observations directly to waypoints, trajectories, or low-level control actions, thereby avoiding error accumulation and hand-crafted interfaces in modular perception-prediction-planning pipelines. Early methods[7] largely followed imitation learning, with planning-oriented formulations[13, 67, 73, 24, 23, 54, 31] later becoming dominant. TransFuser[7] established a strong transformer-based sensor-fusion baseline for end-to-end driving. UniAD[21] explicitly organized perception and prediction around downstream planning, reframing full-stack driving as a planning-oriented unified architecture. DriveMamba[53] further improved efficiency and scalability through a task-centric state-space architecture. LEAD[48] revisited imitation-based end-to-end driving from the perspective of learner-expert asymmetry. DiffusionDrive[44] and GoalFlow[69] moved from deterministic decoding to generative planning, using truncated diffusion and flow matching, respectively, to better model multimodal trajectories. In recent work, VLA-based end-to-end driving[81, 51, 70, 61] has extended this line of research toward language-grounded action generation and post-training alignment. DriveVLA-W0[37] showed that adding world-model objectives to VLA training supplies dense supervision and improves scaling with data. AutoDrive- R^2 [75] introduced chain-of-thought reasoning, self-reflection, and GRPO-based post-training for physically plausible trajectory generation. Despite these advances, most end-to-end planners still couple planning primarily to the current scene or to output-level multimodality, leaving the connection between future state transitions and action generation largely implicit.

2.2 World model in autonomous driving

World models in autonomous driving[6, 64, 36, 28] learn to predict future scene dynamics and are increasingly used for forecasting, planning, simulation, and long-horizon decision support. Dreamer[15–17] introduced latent world modeling for long-horizon planning via imagined rollouts. GAIA-1[20] cast autonomous driving world modeling as action-conditioned generative sequence modeling over multimodal signals. Vista[12] advanced controllable driving world modeling with an emphasis on diversity of environments and controllability. WoTE[38] predicts future BEV states to evaluate candidate trajectories. SeerDrive[77] explicitly coupled future scene evolution and trajectory planning through iterative bidirectional refinement. DriveLaW[68] unified video generation and motion planning in a shared latent driving world so that generator latents directly support closed-loop planning.

Despite this rapid progress, the central difficulty is no longer whether future states can be predicted, but how those predicted futures meaningfully shape decisions. Several recent methods[65, 82, 77] explicitly note that world modeling and planning may be jointly trained. However, existing work still do not adequately provide a reasonable explanation for the inherent correlation between future scene modeling and motion planning. For our setting, this is the unresolved point. We are interested not merely in predicting future latent BEV states, but in making those transitions action-relevant, so that planning is constrained by how the world is expected to evolve and by what control signal is implied by that evolution.




Figure 2: Overview of the proposed IDOL framework. (a) The closed-loop refinement module rolls out future latent BEV states with the BEV world model and refines the planning query through inverse-dynamics feedback. (b) The planning network fuses the refined query with trajectory anchors, predicts candidate trajectories, and selects the best one by scoring and ranking. (c) The inverse-dynamics-guided refinement network decodes adjacent future BEV states into spatial and global dynamics cues, which are fused to update the ego query.

2.3 Inverse dynamics models

Inverse dynamics models[19, 49, 30, 1] originate from physics, control, and reinforcement learning, where the goal is to infer the action or control input that caused a transition between two states. This viewpoint is useful because it makes action semantics explicit: an inverse dynamics model can identify which aspects of a transition are action-relevant, recover latent controls when actions are unavailable or noisy, and encourage representations that preserve controllable structure rather than merely appearance. Recent machine learning work[60] has employed inverse dynamics for model-based control, representation learning, and general sequential decision-making.

In autonomous driving, however, inverse dynamics remains comparatively underexplored. When it appears, it is often auxiliary: ReSim[71] uses an inverse dynamics model to convert predicted videos into executable trajectories and to assess controllability, while FutureSightDrive[76] explicitly frames planning as recovering actions from current observations and imagined future scenes. These examples are suggestive. They imply that inverse dynamics can serve as the missing bridge between “what future state is predicted” and “what action should be taken,” especially when future reasoning is already available through a world model. Existing driving world-model methods typically stop at latent future forecasting, trajectory evaluation, or reward-guided selection; they rarely learn an explicit transition-to-action mapping over adjacent predicted states. Our method builds on this observation. By introducing an inverse dynamics module on top of predicted future latent BEV states, we make the coupling between state evolution and planning explicit, so that trajectory generation is aligned not only with anticipated futures but also with the action-consistent transitions that connect them.

3 Methodology

3.1 Preliminary

End-to-end autonomous driving. End-to-end autonomous driving formulates trajectory planning as learning a direct mapping from raw sensory observations and ego-state inputs to future ego motion, without relying on a manually designed modular stack. Recent world-model-based methods further

improve this paradigm by explicitly modeling future scene evolution and using the predicted futures to guide planning.

Inverse dynamics model. Inverse dynamics model infers the latent action or motion representation that explains the transition between two adjacent states. In its general form, given two consecutive states ξ_t and ξ_{t+1} , inverse dynamics seeks a compact transition descriptor

$$d_t = f_{\text{idm}}(\xi_t, \xi_{t+1}), \quad (1)$$

which captures the motion-consistent change from ξ_t to ξ_{t+1} . This formulation is particularly suitable for autonomous driving, since adjacent future states naturally encode how ego motion interacts with scene evolution. In our setting, the two states are imagined BEV latent states produced by the world model. Therefore, inverse dynamics provides a natural bridge from *future state transition* to *trajectory-related motion features*, making it well suited for refining trajectories from consecutive imagined BEV frames.

3.2 Scene representation

As illustrated in Figure 2, our method predicts the final trajectory by coupling anchor-based planning, latent future simulation, inverse-dynamics feedback, and candidate selection. We first encode the current scene with a multi-modal image-LiDAR backbone following TransFuser[7], and obtain a compact BEV representation B . In parallel, we maintain an offline trajectory-anchor vocabulary $\mathcal{A} = \{\tau_k\}_{k=1}^K$, where each anchor $\tau_k \in \mathbb{R}^{S \times 3}$ represents a candidate future motion[5, 40]. Each anchor is encoded into an anchor feature a_k , which is concatenated with the ego-state feature z to form an anchor-conditioned ego query

$$e_k^{(0)} = \phi([z, a_k]), \quad k = 1, \dots, K. \quad (2)$$

Here, $e_k^{(0)}$ serves as the candidate-specific planning query for downstream future imagination and trajectory refinement.

3.3 Latent BEV world model

For each candidate k , we construct a candidate-conditioned latent scene by combining the current latent BEV features with the anchor-conditioned ego query $e_k^{(u)}$. At rollout step u , the ego query is injected into the latent BEV feature map, yielding candidate-conditioned BEV features $\tilde{B}_k^{(u)}$. We then form the scene feature sequence

$$X_k^{(u)} = [e_k^{(u)}, \tilde{B}_k^{(u)}], \quad (3)$$

which is updated by a transformer-based latent world model:

$$\hat{X}_k^{(u+1)} = \text{BEVWorldModel}(X_k^{(u)}). \quad (4)$$

The first output element is taken as the next ego query $e_k^{(u+1)}$, while the remaining features correspond to the next imagined latent BEV state $B_k^{(u+1)}$.

To maintain candidate consistency during rollout, the updated ego query is re-injected into the latent imagined BEV state at the corresponding future anchor location, producing the next candidate-conditioned BEV features $\tilde{B}_k^{(u+1)}$. Repeating this process yields a candidate-specific latent future trajectory in BEV space,

$$\{(e_k^{(u)}, \tilde{B}_k^{(u)})\}_{u=0}^U, \quad (5)$$

which is subsequently used by the inverse dynamics module and the planning head.

3.4 Inverse-dynamics-guided refinement network

3.4.1 Inverse dynamics model

While the world model predicts future latent scenes, planning still requires a mechanism that translates those imagined transitions into motion-relevant updates. To bridge this gap, we introduce an inverse

dynamics model (IDM). For each pair of adjacent latent imagined BEV states $(\tilde{B}_k^{(u)}, \tilde{B}_k^{(u+1)})$, IDM produces two complementary outputs:

$$(S_k^{(u)}, g_k^{(u)}) = \text{IDM}(\tilde{B}_k^{(u)}, \tilde{B}_k^{(u+1)}), \quad (6)$$

where $S_k^{(u)} \in \mathbb{R}^{H \times W \times C}$ is a spatial dynamics map that preserves position-wise motion variations across the latent BEV feature map, and $g_k^{(u)} \in \mathbb{R}^C$ is a pooled global dynamics feature that summarizes the overall transition. When multiple rollout transitions are available, we aggregate them by averaging:

$$S_k = \frac{1}{U} \sum_{u=0}^{U-1} S_k^{(u)}, \quad g_k = \frac{1}{U} \sum_{u=0}^{U-1} g_k^{(u)}. \quad (7)$$

The key idea is that future transitions should provide not only *what* changes globally, but also *where* critical changes occur in the imagined scene. A purely pooled inverse dynamics feature is often too coarse for planning, since only a subset of spatial changes are truly relevant to the current trajectory hypothesis. By preserving both spatial and global dynamics, IDM provides a more informative interface between future imagination and motion refinement.

3.4.2 Closed-loop query refinement

We refine the current ego query by combining the spatial and global dynamics in a dual-branch manner. First, spatial cross-attention lets the ego query retrieve candidate-relevant local motion evidence from the imagined BEV transition:

$$\tilde{e}_k^{(\ell)} = \text{LN}\left(e_{k,\text{in}}^{(\ell)} + \text{CrossAttn}\left(e_{k,\text{in}}^{(\ell)}, S_k^{(\ell)}, S_k^{(\ell)}\right)\right), \quad (8)$$

where ℓ indexes the outer closed-loop iteration. We then fuse the global dynamics feature with the refined query through an MLN[63] for further calibration:

$$\bar{e}_k^{(\ell)} = \text{MLN}_{\text{idm}}\left(\tilde{e}_k^{(\ell)}, g_k^{(\ell)}\right). \quad (9)$$

This yields a simple but effective dual-branch fusion: the spatial branch identifies where the relevant future changes occur, while the global branch provides coarse holistic calibration. As a result, the feedback passed from imagined futures to planning becomes more spatially selective and more informative than using only pooled inverse dynamics.

To prevent iterative drift, the second and later iterations re-anchor the current query to the initial anchor-conditioned query:

$$e_{k,\text{in}}^{(\ell)} = \text{MLN}_{\text{cl}}\left(e_k^{(0)}, \bar{e}_k^{(\ell-1)}\right), \quad \ell \geq 1, \quad (10)$$

while for the first iteration we simply set

$$e_{k,\text{in}}^{(0)} = e_k^{(0)}. \quad (11)$$

After the final refinement iteration, the resulting refined query is fed into the planning network, where a transformer decoder followed by an MLP head predicts an offset for each trajectory anchor. The refined trajectory candidates are then ranked by a reward model [38] to select the final output.

3.5 Training loss

Our network is trained with a mixture of offset regression, reward supervision, and semantic BEV supervision. Concretely, training combines a standard winner-take-all trajectory offset regression loss, imitation reward supervision over the anchor set, simulator-metric reward supervision, and auxiliary BEV semantic supervision for both the current and imagined future states. The current and future semantic losses help stabilize scene encoding and latent future prediction, while the reward-related losses supervise trajectory ranking in the same manner as previous methods.

The overall objective is written as

$$\mathcal{L} = \lambda_{\text{off}} \mathcal{L}_{\text{off}} + \lambda_{\text{off-im}} \mathcal{L}_{\text{off-im}} + \lambda_{\text{im}} \mathcal{L}_{\text{im}} + \lambda_{\text{sim}} \mathcal{L}_{\text{sim}} + \lambda_{\text{map}} \mathcal{L}_{\text{map}}, \quad (12)$$

where $\mathcal{L}_{\text{off}}$ denotes the trajectory offset loss, $\mathcal{L}_{\text{off-im}}$ and $\mathcal{L}_{\text{im}}$ denote the auxiliary and main imitation-reward losses, $\mathcal{L}_{\text{sim}}$ denotes the simulator-metric loss, and $\mathcal{L}_{\text{map}}$ denotes the BEV semantic supervision.

Table 1: Performance comparison on the NAVSIM v1 navtest split with closed-loop metrics. “C” and “L” denote camera and LiDAR inputs, respectively. For fair comparison, all listed results are reported under the ResNet-34 image-backbone setting. Bold and underlined values indicate the best and second-best results, respectively. ResWorld* denotes the historical-frame variant that uses historical frames to obtain temporal residuals, and DiffE2E[†] denotes the variant with a ResNet-34 image encoder.

Method	Img. Backbone	Input	NC $\uparrow$	DAC $\uparrow$	TTC $\uparrow$	Comf. $\uparrow$	EP $\uparrow$	PDMS $\uparrow$
VADv2 [5]	ResNet-34	C & L	97.2	89.1	91.6	100	76.0	80.9
UniAD [21]	ResNet-34	Camera	97.8	91.9	92.9	100	78.8	83.4
PARA-Drive [66]	ResNet-34	Camera	97.9	92.4	93.0	99.8	79.3	84.0
TransFuser [7]	ResNet-34	C & L	97.7	92.8	92.8	100	79.2	84.0
LAW [36]	ResNet-34	Camera	96.4	95.4	88.7	<u>99.9</u>	81.7	84.6
DiffusionDrive [44]	ResNet-34	C & L	98.2	96.2	94.7	100	82.2	88.1
WoTE [38]	ResNet-34	C & L	98.5	96.8	94.9	<u>99.9</u>	81.9	88.3
SeerDrive [77]	ResNet-34	C & L	98.4	<u>97.0</u>	94.9	<u>99.9</u>	83.2	88.9
ResWorld* [78]	ResNet-34	C & L	<u>98.9</u>	96.5	95.6	100	83.1	89.0
MeanFuser [62]	ResNet-34	Camera	98.6	<u>97.0</u>	95.0	100	82.8	89.0
DiffE2E [†] [80]	ResNet-34	C & L	99.2	96.8	96.7	100	<u>83.6</u>	<u>89.8</u>
IDOL	ResNet-34	C & L	98.8	97.6	<u>95.9</u>	100	83.8	90.0

4 Experiments

4.1 Benchmark

We evaluate our method on the NAVSIM benchmarks. On NAVSIM v1 [9], we report results on the navtest split using the Predictive Driver Model Score (PDMS), which aggregates five planning criteria: no-collision (NC), drivable area compliance (DAC), time-to-collision within bound (TTC), comfort, and ego progress (EP). We further evaluate on NAVSIM v2 [3], including the challenging navhard split under the two-stage pseudo-simulation protocol. Its primary metric is the Extended Predictive Driver Model Score (EPDMS), which extends the evaluation with driving direction compliance (DDC), traffic light compliance (TLC), lane keeping (LK), history comfort (HC), and extended comfort (EC), in addition to NC, DAC, EP, and TTC. All results are reported under the official closed-loop evaluation protocol.

4.2 Implementation details

We use a planning horizon of 4 s with a sampling interval of 0.5 s, resulting in 8 future waypoints. Our model adopts a ResNet34-based TransFuser backbone for multi-modal fusion, where the stitched front-view image input is resized to 256×1024 . The latent feature dimension is set to 256. In the current implementation, the BEV representation is flattened into 64 latent queries, with $H_{\text{BEV}} \times W_{\text{BEV}} = 8 \times 8$, and trajectory planning is performed over 256 trajectory anchors. The resulting model contains 69.36M parameters and achieves 17.65 FPS on a single NVIDIA RTX 3090 GPU with batch size 1, indicating that IDOL maintains practical inference efficiency while introducing inverse-dynamics-guided future reasoning.

Training is conducted on 4 NVIDIA GeForce RTX 3090 GPUs with a batch size of 4 per GPU for approximately 24 hours. We use AdamW with an initial learning rate of 2×10^{-4} and weight decay of 1×10^{-4} .

4.3 Comparison with SOTA

Table 1 compares IDOL with recent end-to-end planners on the NAVSIM navtest split under the ResNet-34 [18] image-backbone setting. IDOL achieves the best PDMS of 90.0, outperforming prior strong baselines. Table 2 further evaluates IDOL on the more challenging NAVSIM v2 navhard split. IDOL achieves the highest final EPDMS of 38.0 among all comparable methods, substantially outperforming the strongest baseline WoTE by 10.1 points.

Table 2: Performance comparison on the NAVSIM v2 navhard split. PDM-Closed is listed separately as a privileged planner using ground-truth perception.

Method	Backbone	Stage	NC $\uparrow$	DAC $\uparrow$	DDC $\uparrow$	TLC $\uparrow$	EP $\uparrow$	TTC $\uparrow$	LK $\uparrow$	HC $\uparrow$	EC $\uparrow$	EPDMS $\uparrow$
PDM-Closed [8]	-	Stage 1	94.4	98.8	100.0	99.5	100.0	93.5	99.3	87.7	36.0	51.3
		Stage 2	88.1	90.6	96.3	98.5	100.0	83.1	73.7	91.5	25.4	
LTF [50]	ResNet34	Stage 1	96.2	79.5	99.1	99.5	84.1	95.1	94.2	97.5	79.1	23.1
		Stage 2	77.7	70.2	84.2	98.0	85.1	75.6	45.4	95.7	75.9	
GTRS-DP [42]	ResNet34	Stage 1	94.7	78.8	96.1	99.5	83.0	94.4	92.0	97.5	72.8	23.8
		Stage 2	80.3	74.4	84.9	98.0	81.9	78.8	45.4	96.7	70.1	
DiffusionDrive [44]	ResNet34	Stage 1	96.0	79.7	97.4	99.5	81.3	93.1	90.8	96.8	73.8	24.2
		Stage 2	82.1	72.2	88.5	98.7	85.1	78.8	49.2	89.3	71.2	
GuideFlow [45]	ResNet34	Stage 1	96.6	80.5	96.3	99.3	82.3	94.9	91.5	97.7	67.8	27.1
		Stage 2	87.3	76.7	88.8	99.2	84.3	85.1	49.7	93.1	44.5	
WoTE [38]	ResNet34	Stage 1	97.4	88.2	97.7	99.3	82.7	96.4	90.8	97.3	68.0	27.9
		Stage 2	81.2	77.7	84.8	98.1	85.9	78.5	46.2	96.6	63.3	
IDOL	ResNet34	Stage 1	97.2	89.6	98.0	99.6	82.3	96.9	95.3	97.6	72.9	38.0
		Stage 2	84.9	81.7	87.7	98.5	84.7	81.1	50.0	95.4	64.0	

Beyond the main comparisons, Table 8 reports the extended NAVSIM v2 navtest benchmark. IDOL achieves 89.6 EPDMS, ranking first among learned methods and remaining competitive with the human agent. Table 9 further evaluates the more challenging navhard stage-1-only setting, where IDOL achieves the best performance with 76.2 EPDMS, surpassing Hydra-MDP[†] by 3.1 points and WoTE by 9.5 points. Across NAVSIM v1 navtest, NAVSIM v2 navtest, navhard stage-1, and the two-stage navhard evaluation, IDOL consistently achieves state-of-the-art performance among comparable learned planners, demonstrating the robustness and stability of inverse-dynamics-guided future reasoning under both standard and challenging long-tail driving scenarios.

4.4 Ablation study

We conduct ablation studies on the NAVSIM navtest split to analyze the contribution of each design in IDOL. We report PDMS and its five component metrics. Additional ablation results and analyses are provided in Appendix D.

Effect of inverse dynamics and closed-loop refinement. Table 3 studies the main components of IDOL. Without IDM, future BEV states lack explicit transition-to-motion feedback, limiting their effect on trajectory refinement. Introducing IDM improves PDMS from 87.3 to 89.2 by converting latent future transitions into motion-aware query updates. Closed-loop refinement further raises PDMS to 90.0 by feeding the updated query back into future reasoning. The best result is obtained with two iterations, while three iterations slightly reduce performance, suggesting possible over-correction.

Table 3: Main ablation of inverse dynamics and closed-loop refinement on the NAVSIM navtest split. IDM denotes the inverse dynamics model, and CL denotes closed-loop refinement.

IDM	CL iters.	NC $\uparrow$	DAC $\uparrow$	TTC $\uparrow$	Comf. $\uparrow$	EP $\uparrow$	PDMS $\uparrow$
$\times$	$\times$	98.5	95.0	95.2	100	81.5	87.3
$\checkmark$	$\times$	98.6	97.0	95.4	100	83.3	89.2
$\checkmark$	2	98.8	97.6	95.9	100	83.8	90.0
$\checkmark$	3	98.6	97.3	95.2	100	83.5	89.4

Temporal design of IDM. Table 4 compares different temporal inputs for IDM. The two-frame design directly decodes adjacent BEV transitions, while the four-frame variant uses a longer window that may dilute local transition cues for immediate refinement. The better performance of the two-frame setting shows that adjacent transitions provide a more compact and effective basis for planning-oriented motion refinement.

Table 4: Ablation of temporal decoding in the inverse dynamics model. The two-frame variant decodes adjacent BEV transitions, while the four-frame variant uses a longer future window.

IDM temporal input	NC $\uparrow$	DAC $\uparrow$	TTC $\uparrow$	Comf. $\uparrow$	EP $\uparrow$	PDMS $\uparrow$
4 frame	98.7	97.3	95.6	100	83.7	89.6
2 frame	98.8	97.6	95.9	100	83.8	90.0

Effect of spatial and global dynamics branches. Table 5 analyzes the dual-branch design. The global branch captures holistic transition patterns but lacks spatial selectivity, while the spatial branch preserves local transition evidence but lacks global calibration. Combining both branches provides spatially selective and globally calibrated future-to-planning feedback, achieving the best overall PDMS.

Table 5: Ablation of the spatial and global dynamics branches in the inverse-dynamics-guided refinement network.

Dynamics Branch	NC $\uparrow$	DAC $\uparrow$	TTC $\uparrow$	Comf. $\uparrow$	EP $\uparrow$	PDMS $\uparrow$
w/o spatial branch	98.8	96.9	95.8	100	83.2	89.3
w/o global branch	98.7	97.2	95.3	100	83.9	89.5
dual-branch IDM	98.8	97.6	95.9	100	83.8	90.0

4.5 Visualization

To better understand inverse-dynamics-guided refinement, we visualize a representative NAVSIM navtest case in Fig. 3. Panels (a)–(c) show the latent BEV change, the corresponding IDM spatial response, and the refinement-query attention, respectively. The white contour marks high-change regions extracted from Panel (a). The visualization shows that IDM indeed concentrates on the motion-informative parts within the latent BEV change regions, rather than unrelated background variations, and the query attends to these motion-aware cues during refinement. Panel (d) compares the original, refined, and expert trajectories, where the refined trajectory better aligns with the expert, suggesting that IDM converts latent future transitions into actionable planning updates. More qualitative results are provided in Appendix E.




Figure 3: Qualitative visualization of inverse-dynamics-guided refinement on the NAVSIM navtest split.

5 Conclusion

In this work, we proposed IDOL, an inverse-dynamics-guided future prediction framework for end-to-end autonomous driving. By decoding adjacent latent BEV futures, IDOL converts predicted scene evolution into transition-aware motion cues and refines trajectory planning through a lightweight closed-loop process. This explicitly bridges world modeling and executable motion generation, making future prediction more actionable for planning. Experiments on NAVSIM v1 and NAVSIM v2 show that IDOL achieves state-of-the-art performance on major benchmarks, including navtest, navhard stage-1, and the two-stage navhard evaluation, demonstrating the effectiveness and generality of inverse-dynamics-guided future reasoning.

References

- [1] J Angeles, Ou Ma, and A Rojas. An algorithm for the inverse dynamics of n-axis general manipulators using kane’s equations. *Computers & Mathematics with Applications*, 17(12):1545–1561, 1989.
- [2] Holger Caesar, Varun Bankiti, Alex H Lang, Sourabh Vora, Venice Erin Liong, Qiang Xu, Anush Krishnan, Yu Pan, Giancarlo Baldan, and Oscar Beijbom. nuscenes: A multimodal dataset for autonomous driving. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 11621–11631, 2020.
- [3] Wei Cao, Marcel Hallgarten, Tianyu Li, Daniel Dauner, Xunjiang Gu, Caojun Wang, Yakov Miron, Marco Aiello, Hongyang Li, Igor Gilitschenski, et al. Pseudo-simulation for autonomous driving. *arXiv preprint arXiv:2506.04218*, 2025.
- [4] Li Chen, Penghao Wu, Kashyap Chitta, Bernhard Jaeger, Andreas Geiger, and Hongyang Li. End-to-end autonomous driving: Challenges and frontiers. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 46(12):10164–10183, 2024.
- [5] Shaoyu Chen, Bo Jiang, Hao Gao, Bencheng Liao, Qing Xu, Qian Zhang, Chang Huang, Wenyu Liu, and Xinggang Wang. Vadv2: End-to-end vectorized autonomous driving via probabilistic planning. *arXiv preprint arXiv:2402.13243*, 2024.
- [6] Yuntao Chen, Yuqi Wang, and Zhaoxiang Zhang. Drivinggpt: Unifying driving world modeling and planning with multi-modal autoregressive transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 26890–26900, 2025.
- [7] Kashyap Chitta, Aditya Prakash, Bernhard Jaeger, Zehao Yu, Katrin Renz, and Andreas Geiger. Transfuser: Imitation with transformer-based sensor fusion for autonomous driving. *IEEE transactions on pattern analysis and machine intelligence*, 45(11):12878–12895, 2022.
- [8] Daniel Dauner, Marcel Hallgarten, Andreas Geiger, and Kashyap Chitta. Parting with misconceptions about learning-based vehicle motion planning. In *Conference on Robot Learning*, pages 1268–1281. PMLR, 2023.
- [9] Daniel Dauner, Marcel Hallgarten, Tianyu Li, Xinshuo Weng, Zhiyu Huang, Zetong Yang, Hongyang Li, Igor Gilitschenski, Boris Ivanovic, Marco Pavone, et al. Navsim: Data-driven non-reactive autonomous vehicle simulation and benchmarking. *Advances in Neural Information Processing Systems*, 37:28706–28719, 2024.
- [10] Lan Feng, Yang Gao, Eloi Zablocki, Quanyi Li, Wuyang Li, Sichao Liu, Matthieu Cord, and Alexandre Alahi. Rap: 3d rasterization augmented end-to-end planning. *arXiv preprint arXiv:2510.04333*, 2025.
- [11] Renju Feng, Ning Xi, Duanfeng Chu, Rukang Wang, Zejian Deng, Anzheng Wang, Liping Lu, Jinxiang Wang, and Yanjun Huang. Artemis: Autoregressive end-to-end trajectory planning with mixture of experts for autonomous driving. *IEEE Robotics and Automation Letters*, 11(1):226–233, 2025.
- [12] Shenyuan Gao, Jiazhi Yang, Li Chen, Kashyap Chitta, Yihang Qiu, Andreas Geiger, Jun Zhang, and Hongyang Li. Vista: A generalizable driving world model with high fidelity and versatile controllability. *Advances in Neural Information Processing Systems*, 37:91560–91596, 2024.
- [13] Ke Guo, Haochen Liu, Xiaojun Wu, Jia Pan, and Chen Lv. ipad: Iterative proposal-centric end-to-end autonomous driving. *arXiv preprint arXiv:2505.15111*, 2025.
- [14] Mingzhe Guo, Yixiang Yang, Chuanrong Han, Rufeng Zhang, Shirui Li, Ji Wan, and Zhipeng Zhang. Flowad: Ego-scene interactive modeling for autonomous driving. *arXiv preprint arXiv:2603.13399*, 2026.
- [15] Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. *arXiv preprint arXiv:1912.01603*, 2019.
- [16] Danijar Hafner, Timothy Lillicrap, Mohammad Norouzi, and Jimmy Ba. Mastering atari with discrete world models. *arXiv preprint arXiv:2010.02193*, 2020.
- [17] Danijar Hafner, Jurgis Pasukonis, Jimmy Ba, and Timothy Lillicrap. Mastering diverse domains through world models. *arXiv preprint arXiv:2301.04104*, 2023.
- [18] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

- [19] John M Hollerbach. A recursive lagrangian formulation of manipulator dynamics and a comparative study of dynamics formulation complexity. *IEEE Transactions on Systems, Man, and Cybernetics*, 10(11): 730–736, 2007.
- [20] Anthony Hu, Lloyd Russell, Hudson Yeo, Zak Murez, George Fedoseev, Alex Kendall, Jamie Shotton, and Gianluca Corrado. Gaia-1: A generative world model for autonomous driving. *arXiv preprint arXiv:2309.17080*, 2023.
- [21] Yihan Hu, Jiazhi Yang, Li Chen, Keyu Li, Chonghao Sima, Xizhou Zhu, Siqi Chai, Senyao Du, Tianwei Lin, Wenhai Wang, et al. Planning-oriented autonomous driving. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 17853–17862, 2023.
- [22] Zhao Huang, Bowen Zhang, Zhongzhu Li, and Di Lin. Occdriver: Future occupancy guided dual-branch trajectory planner in autonomous driving. In *The Fourteenth International Conference on Learning Representations*.
- [23] Zhiyu Huang, Xinshuo Weng, Maximilian Igl, Yuxiao Chen, Yulong Cao, Boris Ivanovic, Marco Pavone, and Chen Lv. Gen-drive: Enhancing diffusion generative driving policies with reward modeling and reinforcement learning fine-tuning. In *2025 IEEE International Conference on Robotics and Automation (ICRA)*, pages 3445–3451. IEEE, 2025.
- [24] Jyh-Jing Hwang, Runsheng Xu, Hubert Lin, Wei-Chih Hung, Jingwei Ji, Kristy Choi, Di Huang, Tong He, Paul Covington, Benjamin Sapp, et al. Emma: End-to-end multimodal model for autonomous driving. *arXiv preprint arXiv:2410.23262*, 2024.
- [25] Anqing Jiang, Yu Gao, Zhigang Sun, Yiru Wang, Jijun Wang, Jinghao Chai, Qian Cao, Yuweng Heng, Hao Jiang, Yunda Dong, et al. Diffvla: Vision-language guided diffusion planning for autonomous driving. *arXiv preprint arXiv:2505.19381*, 2025.
- [26] Anqing Jiang, Yu Gao, Yiru Wang, Zhigang Sun, Shuo Wang, Yuwen Heng, Hao Sun, Shichen Tang, Lijuan Zhu, Jinhao Chai, et al. Irl-vla: Training an vision-language-action policy via reward world model. *arXiv preprint arXiv:2508.06571*, 2025.
- [27] Bo Jiang, Shaoyu Chen, Qing Xu, Bencheng Liao, Jiajie Chen, Helong Zhou, Qian Zhang, Wenyu Liu, Chang Huang, and Xinggang Wang. Vad: Vectorized scene representation for efficient autonomous driving. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 8340–8350, 2023.
- [28] Guangfeng Jiang, Yueru Luo, Jun Liu, Yi Huang, Yiyao Zhu, Zhan Qu, Dave Zhenyu Chen, Bingbing Liu, and Xu Yan. Wpt: World-to-policy transfer via online world model distillation. *arXiv preprint arXiv:2511.20095*, 2025.
- [29] Jungho Kim, Jiyong Oh, Seunghoon Yu, Hongjae Shin, Donghyuk Kwak, and Jun Won Choi. Safedrive: Fine-grained safety reasoning for end-to-end driving in a sparse world. *arXiv preprint arXiv:2602.18887*, 2026.
- [30] Bart Koopman, Henk J Grootenboer, and Henk J De Jongh. An inverse dynamics model for the analysis, reconstruction and prediction of bipedal walking. *Journal of biomechanics*, 28(11):1369–1376, 1995.
- [31] Jingyu Li, Bozhou Zhang, Xin Jin, Jiankang Deng, Xiatian Zhu, and Li Zhang. Imagidrive: A unified imagination-and-planning framework for autonomous driving. *arXiv preprint arXiv:2508.11428*, 2025.
- [32] Jingyu Li, Junjie Wu, Dongnan Hu, Xiangkai Huang, Bin Sun, Zhihui Hao, Xianpeng Lang, Xiatian Zhu, and Li Zhang. Sgdrive: Scene-to-goal hierarchical world cognition for autonomous driving. *arXiv preprint arXiv:2601.05640*, 2026.
- [33] Kailin Li, Zhenxin Li, Shiyi Lan, Yuan Xie, Zhizhong Zhang, Jiayi Liu, Zuxuan Wu, Zhiding Yu, and Jose M Alvarez. Hydra-mdp++: Advancing end-to-end driving via expert-guided hydra-distillation. *arXiv preprint arXiv:2503.12820*, 2025.
- [34] Peidong Li and Dixiao Cui. Navigation-guided sparse scene representation for end-to-end autonomous driving. *arXiv preprint arXiv:2409.18341*, 2024.
- [35] Pengxiang Li, Yinan Zheng, Yue Wang, Huimin Wang, Hang Zhao, Jingjing Liu, Xianyu Zhan, Kun Zhan, and Xianpeng Lang. Discrete diffusion for reflective vision-language-action models in autonomous driving. *arXiv preprint arXiv:2509.20109*, 2025.
- [36] Yingyan Li, Lue Fan, Jiawei He, Yuqi Wang, Yuntao Chen, Zhaoxiang Zhang, and Tieniu Tan. Enhancing end-to-end autonomous driving with latent world model. *arXiv preprint arXiv:2406.08481*, 2024.

- [37] Yingyan Li, Shuyao Shang, Weisong Liu, Bing Zhan, Haochen Wang, Yuqi Wang, Yuntao Chen, Xiaoman Wang, Yasong An, Chufeng Tang, et al. Drivevla-w0: World models amplify data scaling law in autonomous driving. *arXiv preprint arXiv:2510.12796*, 2025.
- [38] Yingyan Li, Yuqi Wang, Yang Liu, Jiawei He, Lue Fan, and Zhaoxiang Zhang. End-to-end driving with online trajectory evaluation via bev world model. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 27137–27146, 2025.
- [39] Yongkang Li, Kaixin Xiong, Xiangyu Guo, Fang Li, Sixu Yan, Gangwei Xu, Lijun Zhou, Long Chen, Haiyang Sun, Bing Wang, et al. Recogdrive: A reinforced cognitive framework for end-to-end autonomous driving. *arXiv preprint arXiv:2506.08052*, 2025.
- [40] Zhenxin Li, Kailin Li, Shihao Wang, Shiyi Lan, Zhiding Yu, Yishen Ji, Zhiqi Li, Ziyue Zhu, Jan Kautz, Zuxuan Wu, et al. Hydra-mdp: End-to-end multimodal planning with multi-target hydra-distillation. *arXiv preprint arXiv:2406.06978*, 2024.
- [41] Zhenxin Li, Shihao Wang, Shiyi Lan, Zhiding Yu, Zuxuan Wu, and Jose M Alvarez. Hydra-next: Robust closed-loop driving with open-loop training. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 27305–27314, 2025.
- [42] Zhenxin Li, Wenhao Yao, Zi Wang, Xinglong Sun, Joshua Chen, Nadine Chang, Maying Shen, Zuxuan Wu, Shiyi Lan, and Jose M Alvarez. Generalized trajectory scoring for end-to-end multimodal planning. *arXiv preprint arXiv:2506.06664*, 2025.
- [43] Zhiqi Li, Zhiding Yu, Shiyi Lan, Jiahan Li, Jan Kautz, Tong Lu, and Jose M Alvarez. Is ego status all you need for open-loop end-to-end autonomous driving? In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14864–14873, 2024.
- [44] Bencheng Liao, Shaoyu Chen, Haoran Yin, Bo Jiang, Cheng Wang, Sixu Yan, Xinbang Zhang, Xiangyu Li, Ying Zhang, Qian Zhang, et al. Diffusiondrive: Truncated diffusion model for end-to-end autonomous driving. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 12037–12047, 2025.
- [45] Lin Liu, Caiyan Jia, Guanyi Yu, Ziyang Song, JunQiao Li, Feiyang Jia, Peiliang Wu, Xiaoshuai Hao, and Yadan Luo. Guideflow: Constraint-guided flow matching for planning in end-to-end autonomous driving. *arXiv preprint arXiv:2511.18729*, 2025.
- [46] Shu Liu, Wenlin Chen, Weihao Li, Zheng Wang, Lijin Yang, Jianing Huang, Yipin Zhang, Zhongzhan Huang, Ze Cheng, and Hao Yang. Bridgedrive: Diffusion bridge policy for closed-loop trajectory planning in autonomous driving. *arXiv preprint arXiv:2509.23589*, 2025.
- [47] Yuechen Luo, Fang Li, Shaoqing Xu, Zhiyi Lai, Lei Yang, Qimao Chen, Ziang Luo, Zixun Xie, Shengyin Jiang, Jiaxin Liu, et al. Adathinkdrive: Adaptive thinking via reinforcement learning for autonomous driving. *arXiv preprint arXiv:2509.13769*, 2025.
- [48] Long Nguyen, Micha Fauth, Bernhard Jaeger, Daniel Dauner, Maximilian Igl, Andreas Geiger, and Kashyap Chitta. Lead: Minimizing learner-expert asymmetry in end-to-end driving. *arXiv preprint arXiv:2512.20563*, 2025.
- [49] Egbert Otten. Inverse and forward dynamics: models of multi-body systems. *Philosophical Transactions of the Royal Society of London. Series B: Biological Sciences*, 358(1437):1493–1500, 2003.
- [50] Aditya Prakash, Kashyap Chitta, and Andreas Geiger. Multi-modal fusion transformer for end-to-end autonomous driving. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 7077–7087, 2021.
- [51] Ishaan Rawal, Shubh Gupta, Yihan Hu, and Wei Zhan. Nord: A data-efficient vision-language-action model that drives without reasoning. *arXiv preprint arXiv:2602.21172*, 2026.
- [52] Matthew Strong, Wei-Jer Chang, Quentin Herau, Jiezhi Yang, Yihan Hu, Chensheng Peng, and Wei Zhan. Learning to drive is a free gift: Large-scale label-free autonomy pretraining from unposed in-the-wild videos. *arXiv preprint arXiv:2602.22091*, 2026.
- [53] Haisheng Su, Wei Wu, Feixiang Song, Junjie Zhang, Zhenjie Yang, and Junchi Yan. Drivemamba: Task-centric scalable state space model for efficient end-to-end autonomous driving. *arXiv preprint arXiv:2602.13301*, 2026.

- [54] Bin Sun, Yaoguang Cao, Yan Wang, Rui Wang, Jiachen Shang, Xiejie Feng, Jiayi Lu, Jia Shi, Shichun Yang, Xiaoyu Yan, et al. Minddrive: An all-in-one framework bridging world models and vision-language model for end-to-end autonomous driving. *arXiv preprint arXiv:2512.04441*, 2025.
- [55] Wenchao Sun, Xuewu Lin, Yining Shi, Chuang Zhang, Haoran Wu, and Sifa Zheng. Sparsedrive: End-to-end autonomous driving via sparse scene representation. In *2025 IEEE International Conference on Robotics and Automation (ICRA)*, pages 8795–8801. IEEE, 2025.
- [56] Zhigang Sun, Yiru Wang, Anqing Jiang, Shuo Wang, Yu Gao, Yuwen Heng, Shouyi Zhang, An He, Hao Jiang, Jinhao Chai, et al. Diffsemanticfusion: Semantic raster bev fusion for autonomous driving via online map diffusion. *IEEE Robotics and Automation Letters*, 11(3):2354–2361, 2026.
- [57] Jiacheng Tang, Zhiyuan Zhou, Zhuolin He, Jia Zhang, Kai Zhang, and Jian Pu. Causalvad: De-confounding end-to-end autonomous driving via causal intervention. *arXiv preprint arXiv:2603.18561*, 2026.
- [58] Xiaolong Tang, Meina Kan, Shiguang Shan, and Xilin Chen. Plan-r1: Safe and feasible trajectory planning as language modeling. *arXiv preprint arXiv:2505.17659*, 2025.
- [59] Haochen Tian, Tianyu Li, Haochen Liu, Jiazhi Yang, Yihang Qiu, Guang Li, Junli Wang, Yinfeng Gao, Zhang Zhang, Liang Wang, et al. Simscale: Learning to drive via real-world simulation at scale. *arXiv preprint arXiv:2511.23369*, 2025.
- [60] Yang Tian, Sizhe Yang, Jia Zeng, Ping Wang, Dahua Lin, Hao Dong, and Jiangmiao Pang. Predictive inverse dynamics models are scalable learners for robotic manipulation. *arXiv preprint arXiv:2412.15109*, 2024.
- [61] Jie Wang, Guang Li, Zhijian Huang, Chenxu Dang, Hangjun Ye, Yahong Han, and Long Chen. Vggdrive: Empowering vision-language models with cross-view geometric grounding for autonomous driving. *arXiv preprint arXiv:2602.20794*, 2026.
- [62] Junli Wang, Yinan Zheng, Xueyi Liu, Zebin Xing, Pengfei Li, Guang Li, Kun Ma, Guang Chen, Hangjun Ye, Zhongpu Xia, et al. Meanfuser: Fast one-step multi-modal trajectory generation and adaptive reconstruction via meanflow for end-to-end autonomous driving. *arXiv preprint arXiv:2602.20060*, 2026.
- [63] Shihao Wang, Yingfei Liu, Tiancai Wang, Ying Li, and Xiangyu Zhang. Exploring object-centric temporal modeling for efficient multi-view 3d object detection. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 3621–3631, 2023.
- [64] Xiaofeng Wang, Zheng Zhu, Guan Huang, Xinze Chen, Jiagang Zhu, and Jiwen Lu. Drivedreamer: Towards real-world-drive world models for autonomous driving. In *European conference on computer vision*, pages 55–72. Springer, 2024.
- [65] Yuqi Wang, Jiawei He, Lue Fan, Hongxin Li, Yuntao Chen, and Zhaoxiang Zhang. Driving into the future: Multiview visual forecasting and planning with world model for autonomous driving. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14749–14759, 2024.
- [66] Xinshuo Weng, Boris Ivanovic, Yan Wang, Yue Wang, and Marco Pavone. Para-drive: Parallelized architecture for real-time autonomous driving. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15449–15458, 2024.
- [67] Maciej K Wozniak, Lianhang Liu, Yixi Cai, and Patric Jensfelt. Prix: Learning to plan from raw pixels for end-to-end autonomous driving. *arXiv preprint arXiv:2507.17596*, 2025.
- [68] Tianze Xia, Yongkang Li, Lijun Zhou, Jingfeng Yao, Kaixin Xiong, Haiyang Sun, Bing Wang, Kun Ma, Guang Chen, Hangjun Ye, et al. Drivelaw: Unifying planning and video generation in a latent driving world. *arXiv preprint arXiv:2512.23421*, 2025.
- [69] Zebin Xing, Xingyu Zhang, Yang Hu, Bo Jiang, Tong He, Qian Zhang, Xiaoxiao Long, and Wei Yin. Goalflow: Goal-driven flow matching for multimodal trajectories generation in end-to-end autonomous driving. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 1602–1611, 2025.
- [70] Yifang Xu, Jiahao Cui, Feipeng Cai, Zhihao Zhu, Hanlin Shang, Shan Luan, Mingwang Xu, Neng Zhang, Yaoyi Li, Jia Cai, et al. Wam-flow: Parallel coarse-to-fine motion planning via discrete flow matching for autonomous driving. *arXiv preprint arXiv:2512.06112*, 2025.
- [71] Jiazhi Yang, Kashyap Chitta, Shenyuan Gao, Long Chen, Yuqian Shao, Xiaosong Jia, Hongyang Li, Andreas Geiger, Xiangyu Yue, and Li Chen. Resim: Reliable world simulation for autonomous driving. *arXiv preprint arXiv:2506.09981*, 2025.

- [72] Pengxuan Yang, Ben Lu, Zhongpu Xia, Chao Han, Yinfeng Gao, Teng Zhang, Kun Zhan, XianPeng Lang, Yupeng Zheng, and Qichao Zhang. Worldrft: Latent world model planning with reinforcement fine-tuning for autonomous driving. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pages 11649–11657, 2026.
- [73] Wenhao Yao, Zhenxin Li, Shiyi Lan, Zi Wang, Xinglong Sun, Jose M Alvarez, and Zuxuan Wu. Drivesuprim: Towards precise trajectory selection for end-to-end planning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pages 11910–11918, 2026.
- [74] Liuhan Yin, Runkun Ju, Guodong Guo, and Erkang Cheng. Diffrefiner: Coarse to fine trajectory planning via diffusion refinement with semantic interaction for end to end autonomous driving. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pages 12009–12017, 2026.
- [75] Zhenlong Yuan, Chengxuan Qian, Jing Tang, Rui Chen, Zijian Song, Lei Sun, Xiangxiang Chu, Yujun Cai, Dapeng Zhang, and Shuo Li. Autodrive- r^2 : Incentivizing reasoning and self-reflection capacity for vla model in autonomous driving. *arXiv preprint arXiv:2509.01944*, 2025.
- [76] Shuang Zeng, Xinyuan Chang, Mengwei Xie, Xinran Liu, Yifan Bai, Zheng Pan, Mu Xu, Xing Wei, and Ning Guo. Futuresightdrive: Thinking visually with spatio-temporal cot for autonomous driving. *arXiv preprint arXiv:2505.17685*, 2025.
- [77] Bozhou Zhang, Nan Song, Jingyu Li, Xiatian Zhu, Jiankang Deng, and Li Zhang. Future-aware end-to-end driving: Bidirectional modeling of trajectory planning and scene evolution. *arXiv preprint arXiv:2510.11092*, 2025.
- [78] Jinqing Zhang, Zehua Fu, Zelin Xu, Wenying Dai, Qingjie Liu, and Yunhong Wang. Resworld: Temporal residual world model for end-to-end autonomous driving. *arXiv preprint arXiv:2602.10884*, 2026.
- [79] Kaiwen Zhang, Zhenyu Tang, Xiaotao Hu, Xingang Pan, Xiaoyang Guo, Yuan Liu, Jingwei Huang, Li Yuan, Qian Zhang, Xiao-Xiao Long, et al. Epona: Autoregressive diffusion world model for autonomous driving. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 27220–27230, 2025.
- [80] Rui Zhao, Yuze Fan, Ziguao Chen, Fei Gao, and Zhenhai Gao. Diffe2e: Rethinking end-to-end driving with a hybrid diffusion-regression-classification policy. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025.
- [81] Weicheng Zheng, Xiaofei Mao, Nanfei Ye, Pengxiang Li, Kun Zhan, Xianpeng Lang, and Hang Zhao. Driveagent-r1: Advancing vlm-based autonomous driving with active perception and hybrid thinking. *arXiv preprint arXiv:2507.20879*, 2025.
- [82] Yupeng Zheng, Pengxuan Yang, Zebin Xing, Qichao Zhang, Yuhang Zheng, Yinfeng Gao, Pengfei Li, Teng Zhang, Zhongpu Xia, Peng Jia, et al. World4drive: End-to-end autonomous driving via intention-aware physical latent world model. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 28632–28642, 2025.
- [83] Jialv Zou, Shaoyu Chen, Bencheng Liao, Zhiyu Zheng, Yuehao Song, Lefei Zhang, Qian Zhang, Wenyu Liu, and Xinggang Wang. Diffusiondrivev2: Reinforcement learning-constrained truncated diffusion modeling in end-to-end autonomous driving. *arXiv preprint arXiv:2512.07745*, 2025.

A Implementation details

Hyperparameters. Table 6 summarizes the key hyperparameters used in IDOL. The trajectory-anchor vocabulary is constructed offline and kept fixed during training and evaluation. For ablation studies, all settings are unchanged unless the corresponding component is explicitly modified.

Table 6: Hyperparameters of IDOL.

Parameter	Value
Epochs	30
Image input size	256×1024
BEV latent resolution	8×8
Number of BEV queries	64
Latent feature dimension	256
Planning horizon	4 s
Waypoint interval	0.5 s
Number of future waypoints	8
Trajectory-anchor vocabulary size	256
Closed-loop refinement iterations	2
Learning rate	2×10^{-4}
Weight decay	1×10^{-4}

Inverse dynamics model. IDOL adopts a lightweight MLP-based inverse dynamics model to convert adjacent imagined BEV states into motion-aware transition cues. Given two consecutive latent BEV states, the model first forms a transition representation by concatenating their query features along the channel dimension. A three-stage MLP transition encoder is then applied: an initial fusion stage compresses the paired-state representation into the latent feature space, followed by residual MLP transformations that refine query-wise transition patterns while preserving the original spatial layout. The resulting query-wise representation can be viewed as a *spatial dynamics map*, which captures local motion-relevant changes across BEV queries. IDOL further aggregates this spatial dynamics map into a compact *global dynamics feature*, which serves as a trajectory-level motion condition for modulating the anchor-conditioned ego planning feature through an MLN layer before trajectory offset prediction. This design keeps the inverse dynamics branch lightweight while allowing the planner to exploit both local transition patterns and global motion context from adjacent imagined futures.

Loss configuration. IDOL is optimized with trajectory offset regression, imitation reward supervision, simulator-metric reward supervision, and BEV semantic supervision. The loss terms follow the same definitions as in the main paper. Table 7 lists the role of each loss term for reproducibility.

Table 7: Loss terms used for training IDOL.

Loss term	Role
$\mathcal{L}_{\text{off}}$	Winner-take-all trajectory offset regression
$\mathcal{L}_{\text{off-im}}$	Auxiliary imitation-guided offset supervision
$\mathcal{L}_{\text{im}}$	Imitation-based trajectory ranking supervision
$\mathcal{L}_{\text{sim}}$	Simulator-metric reward supervision
$\mathcal{L}_{\text{map}}$	BEV semantic supervision for latent scene features

B Benchmark and metrics details

Benchmark. All models are trained on the NAVSIM training split. We evaluate IDOL on the NAVSIM benchmark. The *navtest* split is the standard test split used to evaluate closed-loop planning performance under common urban driving scenarios. The *navhard* split is a more challenging subset designed to stress-test planners under difficult cases such as complex interactions, stricter

route following, and long-tail driving conditions. For NAVSIM v2, navhard is evaluated under the pseudo-simulation protocol, including the stage-1-only setting and the two-stage setting. The former measures the quality of the initially generated trajectory, while the latter further evaluates the trajectory after pseudo-simulation rollout and therefore reflects closed-loop robustness more directly. Since point-cloud inputs are unavailable in the second stage of navhard, we replace the LiDAR branch with Latent TransFuser (LTF) for this setting, which preserves the latent fusion pipeline without relying on inaccessible LiDAR observations.

PDMS. For NAVSIM v1, we report the Predictive Driver Model Score (PDMS), which evaluates trajectory quality after non-reactive simulation. PDMS uses no-collision (NC) and drivable area compliance (DAC) as multiplicative safety constraints, and combines ego progress (EP), time-to-collision within bound (TTC), and comfort (C) as weighted quality terms:

$$\text{PDMS} = \text{NC} \cdot \text{DAC} \cdot \frac{5\text{EP} + 5\text{TTC} + 2\text{C}}{12}. \quad (13)$$

All component metrics are normalized to $[0, 1]$, and the final reported PDMS is averaged over all evaluated scenarios and expressed as a percentage.

EPDMS. For NAVSIM v2, we report the Extended Predictive Driver Model Score (EPDMS). Compared with PDMS, EPDMS adds driving direction compliance (DDC) and traffic light compliance (TLC) as multiplicative rule-compliance constraints, and further introduces lane keeping (LK), history comfort (HC), and extended comfort (EC) into the weighted quality term. Following the NAVSIM v2 metric definition, we write the filtered value of each metric as $\tilde{m}$, where human-trajectory violations are filtered to avoid false-positive penalties. EPDMS is computed as

$$\text{EPDMS} = \tilde{\text{NC}} \cdot \tilde{\text{DAC}} \cdot \tilde{\text{DDC}} \cdot \tilde{\text{TLC}} \cdot \frac{5\tilde{\text{EP}} + 5\tilde{\text{TTC}} + 2\tilde{\text{LK}} + 2\tilde{\text{HC}} + 2\tilde{\text{EC}}}{16}. \quad (14)$$

EPDMS therefore extends PDMS from basic safety and progress evaluation to stricter rule compliance, lane keeping, and pseudo-closed-loop consistency, making it more suitable for NAVSIM v2 and the challenging navhard split.

C Additional evaluation on NAVSIM v2

We further report extended NAVSIM v2 results on both the standard navtest split and the more challenging navhard stage-1 setting. For completeness, several additional reproduced baseline results are collected from publicly available papers[26, 54, 56, 45]. As shown in Table 8, IDOL achieves an EPDMS of 89.6 on navtest, ranking first among learned methods and remaining competitive with the human agent, while maintaining consistently strong safety, rule-compliance, and comfort-related metrics.

On the navhard stage-1 protocol in Table 9, IDOL obtains 76.2 EPDMS, outperforming prior learned planners including Hydra-MDP and WoTE. These results indicate that the proposed inverse-dynamics-guided future reasoning does not only improve performance under standard evaluation, but also provides stable gains under harder long-tail scenarios, demonstrating the robustness and generality of IDOL across different NAVSIM v2 settings.

D Additional ablation studies

We provide additional ablation studies to further examine the design choices in IDOL. These experiments focus on two questions : whether learned inverse dynamics provides more effective transition-aware guidance than simpler future-state alternatives, and how global inverse-dynamics features should be fused with the refined planning query.

Ablation on transition-aware future modeling. We first compare different ways of using imagined future BEV states for planning refinement. The future-state-only variant uses predicted future BEV features without explicitly modeling transitions between adjacent states. The latent-difference variant replaces the learned inverse dynamics model with a direct feature difference between adjacent future BEV states. In contrast, IDOL adopts a learned inverse dynamics model to decode transition-aware

Table 8: Performance comparison on the NAVSIM v2 navtest split using extended closed-loop metrics. The best and second-best results among learned methods are highlighted in bold and underlined, respectively. Superscripts indicate methods using additional training signals or settings beyond standard imitation learning: * denotes VLA/VLM-based methods, † denotes reinforcement learning, reward-guided training, or reinforcement fine-tuning, and ‡ denotes extra synthetic, pseudo-expert, or QA-style data.

Method	NC↑	DAC↑	DDC↑	TLC↑	EP↑	TTC↑	LK↑	HC↑	EC↑	EPDMS↑
Human Agent	100.0	100.0	99.8	100.0	87.4	100.0	100.0	98.1	90.1	90.3
Ego Status MLP [43]	93.1	77.9	92.7	99.6	86.0	91.5	89.4	98.3	85.4	64.0
TransFuser [7]	96.9	89.9	97.8	99.7	87.1	95.4	92.7	98.3	87.2	76.7
Hydra-MDP++ [33]	97.2	97.5	99.4	99.6	83.1	96.5	94.4	<u>98.2</u>	70.9	81.4
DriveSuprim [73]	97.5	96.5	99.4	99.6	88.4	96.6	95.5	98.3	77.0	83.1
ReCogDrive ^{*,†} [39]	98.3	95.2	99.5	<u>99.8</u>	87.1	97.5	96.6	98.3	86.5	83.6
DiffusionDrive [44]	98.2	95.9	99.4	<u>99.8</u>	87.5	97.3	96.8	98.3	87.7	84.5
GTRS-Dense + SimScale ^{‡,†} [59]	98.4	98.8	99.4	99.9	87.9	98.1	96.4	97.6	58.8	84.6
World4Drive [82]	97.8	96.3	99.4	<u>99.8</u>	88.3	97.1	97.7	98.0	53.9	84.8
Epona [79]	97.1	95.7	99.3	99.7	<u>88.6</u>	96.3	97.0	98.0	67.8	85.1
DiffusionDriveV2 [†] [83]	97.7	96.6	99.2	<u>99.8</u>	88.9	97.2	96.0	97.8	91.0	85.5
VADv2 [5]	98.0	98.3	99.4	<u>99.8</u>	87.1	96.8	95.2	98.3	88.1	85.8
DriveVLA-W0* [37]	98.5	99.1	98.0	<u>99.7</u>	86.4	98.1	93.2	97.9	58.9	86.1
SGDrive ^{*,‡} [32]	98.6	94.3	99.5	99.9	86.0	97.9	96.1	98.3	85.9	86.2
DiffRefiner [74]	98.5	97.4	<u>99.6</u>	<u>99.8</u>	87.6	97.7	97.7	98.3	86.2	86.2
WorldRFT [†] [72]	97.8	96.5	99.5	<u>99.8</u>	88.5	97.0	97.4	98.1	69.1	86.7
SafeDrive [29]	99.5	<u>99.0</u>	99.7	99.9	<u>88.6</u>	98.9	<u>97.5</u>	<u>98.2</u>	81.9	87.5
MeanFuser [62]	98.3	97.2	<u>99.6</u>	<u>99.8</u>	87.6	97.4	97.3	98.3	<u>88.2</u>	<u>89.5</u>
IDOL	<u>98.8</u>	97.6	99.5	<u>99.8</u>	87.1	<u>98.3</u>	96.3	98.3	85.5	89.6

Table 9: Performance comparison on the NAVSIM-v2 navhard split under the stage-1-only protocol. Bold and underlined values indicate the best and second-best results, respectively, for each metric. † indicates results reported with the V2-99 backbone.

Method	NC↑	DAC↑	DDC↑	TLC↑	EP↑	TTC↑	LK↑	HC↑	EC↑	EPDMS↑
TransFuser[7]	96.3	74.6	98.4	99.3	82.9	93.7	92.7	97.5	<u>78.2</u>	60.5
LTF[7]	96.2	79.5	<u>99.1</u>	99.5	<u>84.1</u>	95.1	94.2	97.5	79.1	62.3
DiffusionDrive[44]	95.9	84.0	98.6	99.8	84.4	96.0	<u>95.1</u>	<u>97.6</u>	71.1	63.2
WoTE[38]	<u>97.4</u>	88.2	97.8	99.3	82.7	96.4	90.9	97.3	68.0	66.7
Hydra-MDP [†] [40]	97.6	96.4	99.2	99.3	80.2	96.9	94.9	97.8	58.7	<u>73.1</u>
IDOL	97.2	<u>89.6</u>	98.0	<u>99.6</u>	82.3	96.9	95.3	<u>97.6</u>	72.9	76.2

motion cues from adjacent latent futures. As shown in Table 10, both transition-based variants outperform the future-state-only baseline, confirming that future-state changes contain useful motion-relevant information for planning. This verifies that IDOL benefits not merely from accessing imagined future states, but from learning an explicit transition-to-motion mapping that converts future evolution into actionable planning guidance.

Table 10: Ablation of transition-aware future modeling strategies on the NAVSIM navtest split. Future state only uses imagined future BEV states without explicit transition decoding, while latent difference replaces the inverse dynamics model with direct adjacent-feature differences.

Transition Modeling	NC ↑	DAC ↑	TTC ↑	Comf. ↑	EP ↑	PDMS ↑
Future State Only	98.4	96.6	95.2	100	82.6	88.6
Latent Difference	98.6	96.8	95.7	100	82.8	89.0
IDM	98.8	97.6	95.9	100	83.8	90.0

Ablation on global dynamics fusion. We further study how to fuse the global dynamics feature produced by the inverse dynamics model. In the inverse-dynamics-guided refinement network,

the global dynamics feature provides holistic calibration for the query refined by spatial transition evidence. We compare three simple fusion strategies: additive fusion, which directly injects the projected global feature into the query; concat-MLP fusion, which learns a nonlinear fusion from the concatenated query and global feature; and the MLN-based fusion used in IDOL. As shown in Table 11, all variants obtain strong performance, indicating that the global inverse-dynamics cue is consistently beneficial for query refinement. These results verify that IDOL’s performance is not only due to using inverse-dynamics features, but also benefits from an effective query-calibration mechanism that better integrates global transition information into planning.

Table 11: Ablation of global dynamics fusion strategies in the inverse-dynamics-guided refinement network on the NAVSIM navtest split. All variants use the same spatial branch and only replace the fusion operation between the refined ego query and the global dynamics feature.

Fusion Strategy	NC $\uparrow$	DAC $\uparrow$	TTC $\uparrow$	Comf. $\uparrow$	EP $\uparrow$	PDMS $\uparrow$
Additive	98.7	97.2	95.7	100	83.5	89.5
Concat-MLP	98.7	97.6	95.5	100	83.8	89.8
MLN	98.8	97.6	95.9	100	83.8	90.0

E Additional qualitative visualization

To further demonstrate the effectiveness of our proposed method, we expand the qualitative visualization experiments with additional representative driving scenarios. Figure 4 presents representative visualization results on the NAVSIM navtest split under three driving maneuvers, including straight driving, left turn, and right turn. Each example contains four panels that illustrate how the proposed IDM module extracts spatial dynamics from latent BEV transitions and uses them to refine the trajectory prediction.

Panel (a) shows the latent BEV change between two adjacent imagined BEV states produced by the world model. The highlighted regions indicate where the scene representation changes most significantly from frame t to frame $t + 1$. Therefore, this panel serves as the reference evidence for spatially localized future dynamics, such as ego-motion-induced changes, nearby traffic participants, and lane-level scene evolution.

Panel (b) visualizes the spatial dynamics inferred by the IDM from the same adjacent BEV pair. Instead of directly displaying a semantic map, this panel shows the inverse-dynamics response over BEV queries. The white contour marks the high-change regions extracted from Panel (a), and is overlaid as a reference for comparing IDM responses with latent BEV transitions. The regions with stronger activation correspond to locations where IDM considers the transition between the two BEV states informative for explaining the underlying motion. The visual consistency between Panel (a) and Panel (b) suggests that IDM is not responding to arbitrary static background features, but is sensitive to the spatial regions where the latent scene actually evolves.

Panel (c) further shows the attention distribution from the trajectory query to the IDM spatial dynamics. While Panel (b) indicates where inverse-dynamics information is extracted, Panel (c) reveals which dynamic regions are actually attended to by the refinement query. The concentration of attention around the changing BEV regions demonstrates that the refinement process actively uses the IDM-derived spatial evidence, rather than treating IDM as an isolated auxiliary branch.

Panel (d) compares the original trajectory, the expert trajectory, and the refined trajectory. The original trajectory is decoded before applying the IDM-based closed-loop refinement, while the refined trajectory is decoded after the query has absorbed inverse-dynamics information through the IDM attention and fusion modules. Across straight, left-turn, and right-turn cases, the refined trajectory is visually better aligned with the expert trajectory, showing that the IDM-guided update helps correct the initial prediction toward a more plausible future motion.

Overall, these qualitative results provide direct visual evidence for the effectiveness of the IDM module. The latent BEV transition identifies where the future scene changes, the IDM spatial response recovers dynamics from those changing regions, and the query attention confirms that such information is used by the planner. The resulting trajectory refinement illustrates the practical value of this mechanism: IDM helps the model focus on motion-relevant spatial changes and improves




Figure 4: Qualitative visualization of inverse-dynamics refinement under three representative driving maneuvers on the NAVSIM navtest split. From top to bottom: straight driving, left turn, and right turn. In each row, panels (a)–(d) show the latent BEV change, the IDM dynamics inferred from adjacent BEV states, the IDM attention on dynamic queries, and the resulting refined trajectory, respectively.

the final trajectory prediction in different driving maneuvers. This supports our hypothesis that inverse-dynamics reasoning provides a meaningful bridge between latent world-model prediction and trajectory-level decision refinement.

F Failure Cases

We further analyze two representative failure cases on navtest, as shown in Fig 5. Each row contains the front-view camera image and the corresponding BEV trajectory comparison. The refined trajectory denotes the final prediction after IDM-based refinement, and the expert trajectory is used as the reference.

In the first case, the ego vehicle approaches a turning area with ambiguous road geometry. The refined trajectory deviates clearly from the expert trajectory and follows an incorrect spatial direction. This indicates that when the model fails to infer the correct maneuver intention, IDM refinement alone may not fully recover the desired path.

In the second case, the scene involves a complex intersection or roundabout-like structure. Although the refined trajectory captures part of the motion trend, it remains spatially offset from the expert trajectory. This suggests that topology-sensitive scenarios still require more precise reasoning about lane connectivity, road curvature, and maneuver timing.

These cases show that IDM provides useful dynamic cues, but its effectiveness depends on whether such cues can be correctly fused with scene topology and trajectory intent. Future work may improve these limitations with stronger topology-aware constraints and uncertainty-aware refinement.



Figure 5: Representative failure cases on navtest.

G Limitations and future work

Although IDOL shows strong performance across NAVSIM benchmarks, several limitations remain.

Model capacity. Our inverse dynamics model is designed to be lightweight, which keeps the framework efficient but may limit its ability to capture more complex long-horizon interactions and subtle motion patterns. Future work could scale the IDM with larger temporal contexts, stronger transition modeling, or pretraining on broader driving sequences.

Dependence on latent future prediction. IDOL relies on the quality of the imagined latent BEV futures produced by the world model. When future prediction is inaccurate in highly ambiguous or rare scenarios, the decoded inverse-dynamics cues may also become less reliable. Improving the robustness of latent world modeling is therefore an important direction.

Fixed refinement strategy. The current closed-loop refinement uses a fixed refinement setting, while different scenes may require different levels of future-aware reasoning. Adaptive refinement strategies could further improve stability and avoid unnecessary iterative updates.

Broader evaluation. Although our experiments cover both standard and challenging NAVSIM settings, future work will further evaluate inverse-dynamics-guided planning in more interactive, long-tail, and real-world driving scenarios.