

GA3T: A Ground-Aerial Terrain Traversability Dataset for Heterogeneous Robot Teams in Unstructured Environments

Siwei Cai^{*}, Knut Peterson^{*}, Quan Tran, Christian Ricks, Dhanush Parthasarathy, Amir Kaidarov, Neil Deshpande, Sukaina Najm, David Han, and Lifeng Zhou[†]

Drexel University, Philadelphia, USA

{sc3568, kp3275, qdt26, car438, dp3355, amk537, nsd68, sn992, dkh42, lz457}@drexel.edu

^{*}Equal contribution. [†]Corresponding author.

Abstract. Heterogeneous air-ground robot teams combine complementary sensing modalities, mobility characteristics, and spatial viewpoints that can significantly enhance perception in complex outdoor environments. However, progress in multi-robot collaborative perception has been constrained by the lack of real-world datasets featuring overlapping multi-modal observations from platforms operating in unstructured terrain. We present **GA3T** (**G**round-**A**erial **T**eam for **T**errain **T**raversal), a real-world multi-robot collaborative perception dataset collected using a Clearpath Husky UGV and an Autel EVO II UAV across diverse unstructured environments, including forest trails, rocky paths, muddy terrain, snow piles, and grass-covered fields. The ground platform provides 3D LiDAR, stereo camera, IMU, and GPS data, while the aerial platform contributes RGB imagery, thermal/infrared observations, and GPS from a complementary overhead viewpoint, allowing for rich cross-modal and cross-view perception. The dataset is collected in 4 unique environments, with over 13,000 synchronized frames across approximately 29 minutes of operation, and includes both SAM 3-based zero-shot segmentation and over 8,000 manually labeled images. A unique aspect of the dataset is its early-spring collection period, during which sparse tree canopies allow the aerial robot to partially observe the ground robot and terrain through the trees, allowing for occlusion-aware collaborative perception. Unlike prior multi-robot datasets that focus on SLAM or simulated cooperative driving, GA3T is specifically designed to support research on cross-view perception, air-ground viewpoint fusion, traversability estimation, and collaborative scene understanding in real off-road environments. **Dataset and Videos:** [Project Page](#)

1 Introduction

Robot perception in unstructured outdoor environments has advanced rapidly in recent years, driven by progress in deep learning, increasingly capable on-

board computing, and rich sensor suites [22,8,11]. However, most prior perception research has focused on single-robot systems in structured settings such as urban roads and highways. In contrast, **multi-robot collaborative perception**, where heterogeneous robots with different sensing modalities, mobility constraints, and viewpoints jointly observe unstructured environments, remains relatively underexplored. Such collaboration can improve robustness, spatial coverage, and sensing redundancy compared with any single-platform solution, making it especially attractive for challenging field environments.

Among heterogeneous robot teams, the combination of Unmanned Ground Vehicles (UGVs) and Unmanned Aerial Vehicles (UAVs) is particularly compelling. Ground robots such as the Clearpath Husky can carry heavier sensing payloads including 3D LiDAR, providing dense geometric observations of the local environment. Small aerial platforms, by contrast, are constrained by Size, Weight, and Power (SWaP) limitations and typically rely on lightweight sensors such as cameras and Inertial Measurement Units (IMUs), yet they offer a broader overhead perspective that is unavailable from the ground. This air-ground complementarity is especially valuable in unstructured outdoor environments with severe occlusions and irregular terrain, where a single viewpoint is often insufficient for reliable perception.

Despite growing interest in multi-robot systems, most existing multi-robot datasets are designed primarily for Simultaneous Localization and Mapping (SLAM) [4,20,27,7,19], emphasizing broad spatial coverage rather than overlapping views that support perception fusion. Many multi-agent perception datasets are also generated in simulation [17,12], which does not capture the sensor noise, calibration drift, and environmental disturbances of real deployments. In autonomous driving, vehicle-to-vehicle (V2V) and vehicle-to-infrastructure (V2X) datasets [23,1,24,9] have advanced cooperative perception, but they remain restricted to on-road scenarios. The CoPeD dataset [25] represents an important step toward real-world heterogeneous air-ground perception, yet it focuses on relatively open environments. In contrast, our dataset targets cluttered off-road settings with dense vegetation, irregular terrain, richer surface variation, thermal sensing, control logs, and substantial manual perception annotation, all of which are important for studying collaborative perception in real field conditions.

Meanwhile, datasets tailored to off-road or unstructured environments have largely centered on single ground robots, without aerial viewpoints or heterogeneous collaboration [22,8,11,17,6]. To the best of our knowledge, no existing dataset simultaneously provides: (i) real-world heterogeneous air-ground multi-robot data collected across diverse off-road environments, (ii) mixed terrain and surface conditions such as mud, grass, shoreline, forest, and snow piles, (iii) overlapping multi-modal sensor streams including thermal imagery, and (iv) seasonal conditions that naturally expose partial visibility through sparse tree canopies for systematic study of occlusion-aware perception. The thermal modality is particularly valuable in this setting because it can improve robustness under strong illumination changes, help distinguish biological targets such as animals




Fig. 1: Multi-robot collaborative data collection. The heterogeneous aerial and ground robots collect complementary views, including thermal, RGB, GPS, and LiDAR data. RGB images are annotated with dense class segmentations.

or pedestrians, and reveal water-related or visually ambiguous regions that may be difficult to identify reliably from RGB imagery alone.

To address this gap, we present **GA3T** (**G**round-**A**erial **T**eam for **T**errain **T**raversal), a heterogeneous multi-robot perception dataset collected in diverse unstructured outdoor environments. Our platform pairs a Clearpath Husky UGV equipped with a stereo camera, 3D LiDAR, IMU, and GPS with an Autel EVO II UAV carrying RGB, thermal, IMU, and GPS sensors. The ground robot is tele-operated through challenging terrain including muddy ground, grassy fields, gravel paths, and rough hiking trails, while the aerial robot provides a complementary overhead viewpoint for observing scene structure, terrain layout, and robot-environment interactions. An overview of the sensing platforms, collected modalities, and annotation pipeline is shown in Fig. 1. In addition to synchronized sensor streams, the dataset also records joystick control commands, enabling future study of demonstration-based driving policies and perception-conditioned visuomotor learning in off-road environments. Distinctively, because of the early-spring collection period, the trees present during data collection were largely bare of leaves, allowing the UAV to partially observe the ground scene and UGV through the trees, with occlusions and environmental complexity. As a result, the dataset provides a unique opportunity to study collaborative perception under partial visibility, where aerial sensing can complement ground-level blind spots, and vice versa. A summary of the contributions of this paper are as follows:

- We introduce **GA3T**, a real-world heterogeneous air-ground multi-robot dataset for collaborative perception in diverse off-road unstructured environments. The dataset provides complementary aerial and ground viewpoints with 3D LiDAR, stereo and RGB cameras, thermal imagery, IMU, GPS, and joystick control inputs from both platforms.
- We provide accurate pose estimation by fusing KISS-ICP [21] LiDAR odometry with GPS measurements, together with high-quality perception annota-

tions comprising SAM 3-based [3] zero-shot segmentation and 8,000 manually labeled images.

- We design the dataset to support concrete downstream tasks enabled by heterogeneous air-ground sensing, including cross-view semantic prediction, collaborative traversability estimation, path planning with synchronized UAV–UGV context, and broader collaborative scene understanding beyond the BEV assumptions common in existing cooperative perception research.
- By recording synchronized teleoperation commands alongside perception data, the dataset also supports emerging directions such as learning from demonstration and visuomotor policy learning for off-road robot navigation.

GA3T provides real-world multi-modal data for developing and benchmarking collaborative perception algorithms for heterogeneous robot teams operating in challenging unstructured outdoor environments.

2 Related Work

2.1 Off-Road Robotic Perception Datasets

Datasets for off-road robotic perception have played an important role in advancing autonomy in unstructured outdoor environments. RUGD [22] is an early benchmark that highlights the visual complexity of natural terrain from the viewpoint of a ground robot, with a strong emphasis on semantic segmentation and terrain understanding in unstructured scenes. RELLIS-3D [8] further expands this direction by introducing a richer multimodal benchmark with RGB, LiDAR, and semantic annotations for challenging outdoor environments. These datasets have been highly valuable for studying perception and scene understanding in off-road settings, especially from the perspective of a single ground platform. However, they do not address heterogeneous multi-robot perception, aerial-ground viewpoint complementarity, or collaborative sensing across distributed robotic platforms.

2.2 Heterogeneous and Air-Ground Multi-Robot Datasets

Several recent datasets have begun to explore heterogeneous robot teams and collaborative sensing. CoPeD [25] is a notable real-world dataset for collaborative perception with multiple ground robots and an aerial robot, providing an important step toward heterogeneous air-ground perception in realistic settings. The Istanbul Technical University (ITU) heterogeneous robot team dataset [2] also considers aerial-ground robotic platforms and provides 3D sensing data useful for mapping and localization research. These efforts demonstrate the growing importance of multi-robot sensing beyond single-platform autonomy. However, existing heterogeneous datasets are typically less focused on dense off-road scene understanding in cluttered natural environments, and they provide limited support for studying terrain-centric semantics under vegetation occlusion, mixed surface conditions, and strong viewpoint differences between UAV and UGV observations.

2.3 Air-Ground Cooperation and Cross-View Robotics

Another closely related direction studies cooperative air-ground robotics, especially for localization, navigation, and viewpoint assistance. Cristofalo et al. [5] show how UAVs can support UGV localization in GPS-denied environments, illustrating the practical value of complementary aerial and ground viewpoints. More broadly, this line of work motivates the use of UAVs as mobile sensing platforms that can extend perception beyond the limited field of view of a ground robot. However, most prior efforts in this area are primarily algorithmic, focusing on specific localization or navigation methods rather than providing broadly usable benchmark datasets for collaborative perception, cross-view understanding, and multi-modal scene interpretation.

2.4 Aerial Vision Benchmarks

Large-scale aerial vision benchmarks such as VisDrone [26] or the LRDD datasets [16,15,13] have significantly advanced UAV-based perception research, especially in object detection and aerial scene analysis. These benchmarks are valuable for developing robust aerial visual models, but they are not designed for joint UAV–UGV robotic perception. In particular, they do not provide synchronized air-ground observations, ground robot trajectories, or terrain-centric multi-modal sensing for collaborative robotic autonomy in unstructured environments.

2.5 Position of This Work

Our work lies at the intersection of off-road robotic perception, heterogeneous multi-robot sensing, and air-ground collaborative robotics. Compared with prior off-road datasets, we incorporate complementary aerial and ground viewpoints rather than relying on a ground platform alone. Compared with existing heterogeneous multi-robot datasets, we place greater emphasis on cluttered off-road environments with dense vegetation, shoreline regions, mixed terrain conditions such as mud, grass, water-adjacent areas, and snow piles, as well as partial visibility through sparse early-spring tree canopies. In addition, our dataset includes thermal imagery, synchronized GPS-grounded observations, teleoperation control logs, and 8,000 manually labeled images together with zero-shot segmentation annotations. These characteristics make our dataset particularly suitable for studying cross-view semantic understanding, collaborative traversability estimation, air-ground path planning, perception-conditioned control, and broader collaborative autonomy in complex outdoor environments.

3 Dataset

3.1 Robots and Equipment

Our dataset is collected using one ground robot and one aerial robot operating in real off-road environments, as shown in Fig. 2. The hardware and sensing




Fig. 2: The equipment used for data collection. (a) Autel Robotics EVO II Dual 640T V3, (b) Clearpath Husky A200, (c) Husky sensor tower, including a Velodyne VLP-32C Puck 32 LiDAR, a ZED 2 stereo camera with a built-in IMU.

configurations of both platforms are summarized in Table 1. The ground platform is a Clearpath Husky A200 UGV equipped with a Velodyne VLP-32C Puck 32 LiDAR, a ZED 2 stereo camera with a built-in IMU, and a Garmin GPS receiver. Onboard computation is provided by an NVIDIA Jetson Orin NX 16GB running ROS 1 Noetic. During data collection, the ground robot is teleoperated using a Sony PS5 controller connected via Bluetooth, and the control commands are logged together with the sensor streams.

The aerial platform is an Autel Robotics EVO II Dual 640T V3 thermal drone. It provides both RGB and thermal aerial observations together with GPS measurements. The visible camera uses a high-resolution CMOS sensor and supports video capture up to 8K resolution, while the thermal camera is based on an uncooled VOx microbolometer with a resolution of 640×512 . The drone has a maximum rated flight time of 38 min and includes an omnidirectional binocular sensing system for obstacle awareness. As summarized in Table 1, the two platforms provide complementary sensing capabilities: the UGV captures terrain-level geometric and visual observations, while the UAV supplies broader overhead RGB and thermal context.

To align the aerial and ground data streams in both time and space, we use GPS measurements available on both platforms as a shared reference. The Clearpath Husky A200 is equipped with a Garmin GPS receiver, while the Autel EVO II Dual 640T V3 provides GPS telemetry together with the captured aerial imagery. All sensor data are timestamped using GPS time, which improves the consistency of associating asynchronous measurements from heterogeneous sensors such as LiDAR, stereo cameras, IMU, aerial RGB imagery, and thermal imagery. Although a hardware-level trigger is not utilized, the maximum synchronization offset is maintained within 200 ms. To compensate for this, we provide temporally-aligned data pairs by interpolating the high-frequency UGV odometry and LiDAR frames to match the UAV video timestamps, ensuring multimodal consistency for perception tasks. GPS also provides a common global frame for coarse spatial alignment between UAV and UGV trajectories, enabling aerial observations to be matched with nearby ground-level measurements dur-

Table 1: Sensor and computing specifications of the ground and aerial platforms in GA3T.

Type	Model	Key Specs	Specifications	Accuracy / Notes
Ground Platform				
LiDAR	Velodyne VLP-32C	32 channels	Range up to 200 m, 360° horizontal FoV, 40° vertical FoV, 5–20 Hz	Range accuracy up to ± 3 cm
Stereo Camera	Stereolabs ZED 2	Stereo baseline 120 mm	RGB up to 2208×1242 , FoV 110° (H) $\times 70^\circ$ (V) $\times 120^\circ$ (D), image rate up to 100 fps	Depth accuracy $< 0.8\%$ at 2 m, $< 4\%$ at 12 m
IMU	Integrated ZED 2 IMU	Accelerometer ± 8 g	Gyroscope ± 1000 dps, 400 Hz	Gyro sensitivity error $\pm 0.4\%$
GPS	Garmin GPS 18x 5Hz	WAAS-enabled GPS receiver	NMEA 0183 output, 5 Hz	Position acc. < 3 m
Computer	NVIDIA Jetson Orin NX 16GB	Onboard computer	Running ROS 1 Noetic	–
Tele-operation	Sony PS5 Controller	Bluetooth controller	Joystick commands logged with sensor streams	Event-based
Aerial Platform				
RGB Camera	Autel EVO II Dual 640T V3 visible camera	0.8'' CMOS, 50 MP	Aperture $f/1.9$, 23 mm eq. lens , FoV 85° , up to 8K video	–
Thermal Camera	FLIR LWIR thermal camera	Uncooled VOx microbolometer	12 μ m pixel pitch, 8–14 μ m wavelength, 640×512 , FoV 33° (H) $\times 26^\circ$ (V), 30 fps	Temperature accuracy $\pm 3^\circ\text{C}$ or $\pm 3\%$
GNSS / Telemetry	Autel onboard GNSS	GPS telemetry	Used for geo-referencing and synchronization	–
Obstacle Sensing	Binocular sensing system	Omnidirectional sensing	Obstacle awareness sensing	–
Flight Platform	Autel EVO II Dual 640T V3	Maximum rated flight time	38 min	–

ing post-processing. Although this approach does not aim for centimeter-level relative localization, it provides a practical solution for organizing multimodal air-ground data in large-scale outdoor environments.

3.2 Dataset content

Our outdoor sequences are collected in three types of real off-road environments using one ground robot and one aerial robot. Unlike structured outdoor scenes, these environments contain uneven terrain, dense vegetation, natural obstacles, and substantial uncertainty in traversability. During data collection, the Husky is driven by a human operator to traverse the environment, while the aerial drone is flown by a human pilot to record broader overhead RGB and thermal scene context. This setup allows the dataset to capture complementary air-ground viewpoints in realistic off-road conditions without assuming autonomous coordination between the two platforms. An overview of the dataset contents is shown in Table 2. Subfolders are named according to the time of recording in <YYYY><MM><DD>_<hh><mm><ss> format.

Table 2: Overview of dataset contents. Data was collected at four locations, resulting in a total of 13,326 Husky and Drone images and metadata, including 8k manually annotated images and a wide range of traversed terrains.

Dataset Folder	# Frames	Data Length	Area (m ²)	Annotation Type	Terrains Driven On
Forest Trail (20260318_142502)	2044	264.93 sec.	$\approx 3,464$	SAM3	Dirt, rocks, mud, underbrush
Forest Road (20260318_141807)	1702	217.50 sec.	$\approx 8,308$	SAM3	Gravel road, hiking trail, mud
Riverbank (20260318_140904)	1582	206.89 sec.	$\approx 4,513$	SAM3	Rock path, gravel road, concrete, mud
Field (20260320_125939)	7998	1,030.87 sec.	$\approx 13,616$	Manual	Grass, mud, mulch, metal dock, snow

The first environment is a narrow forest trail with dense canopy, steep slopes, rocks, and irregular obstacles. The ground robot experiences highly uneven terrain, while the aerial robot captures a broader view but is often occluded by trees, resulting in complementary yet only partially overlapping perspectives. The second environment is a flatter forest path with dense vegetation, ditches, and holes. Although less steep, it presents ambiguous traversability, as visually similar regions may correspond to different ground conditions, making perception challenging. The third environment is a rocky riverbank with large stones, gravel, and dirt. With less tree cover, the robot is more visible from above, but traversability varies due to differing surface traction and obstacles like large rocks. The fourth environment is a muddy field with sparse trees, puddles, gullies, snow patches, and vegetation. Notably, the muddy areas of the terrain included deep mud trenches from vehicle treads, which were so extreme that the Husky robot nearly flipped over when traversing them. This highlights their key challenges of the terrain, with a wide mix of easy and difficult scenarios.

Overall, these environments capture key challenges in off-road air-ground perception, including occlusion, partial viewpoint overlap, uneven and deformable terrain, and ambiguity in traversability, supporting research in realistic, human-operated settings.

3.3 Data Processing and Annotation

To prepare the dataset for cross-view association, multimodal fusion, and semantic labeling, we perform three stages of processing. First, we refine the UGV trajectory by aligning LiDAR odometry with GPS measurements to obtain a globally consistent ground reference. Second, we align the UAV RGB and thermal image streams to enable multimodal aerial analysis and visualization. Third, we generate semantic segmentation annotations through a foundation-model-assisted human-in-the-loop pipeline.




Fig. 3: Example of RGB–thermal alignment from the UAV. The thermal image is overlaid on the RGB frame using the *inferno* colormap. The visible hotspot corresponds to the UGV, showing how thermal sensing can help localization under vegetation occlusion.

UGV Trajectory Refinement and Ground Truth Generation To obtain a globally consistent trajectory for the ground platform, we refine the UGV poses by combining LiDAR odometry with GPS measurements. We first estimate local motion using KISS-ICP [21], which provides low-drift relative odometry from the 3D LiDAR stream. We then align the LiDAR trajectory to the global coordinate system using GPS measurements.

Specifically, the raw GPS coordinates (latitude and longitude) are converted into a local East-North-Up (ENU) metric frame. Let $\mathbf{k}_i$ denote the relative displacement estimated by KISS-ICP and $\mathbf{g}_i$ the corresponding displacement derived from GPS. We solve for the planar rotation θ that minimizes the residual error:

$$\min_{\theta} \sum_i \|R(\theta)\mathbf{k}_i - \mathbf{g}_i\|^2, \quad (1)$$

where $R(\theta)$ is the $SO(2)$ rotation matrix.

This yields the heading offset between the LiDAR odometry frame and the GPS-referenced global frame, allowing the LiDAR-consistent trajectory to be rotated and anchored to the global coordinate system. The refined poses retain the local consistency of LiDAR odometry while correcting long-term drift with GPS measurements. These geo-referenced poses support downstream tasks such as cross-view association, collaborative mapping, and air-ground spatial matching.

Cross-Modal Aerial Alignment We align the UAV RGB and thermal streams in the image plane by using the RGB image as the template and warping the thermal image with a gradient-domain matching pipeline. Since no pre-calibrated




Fig. 4: Examples of annotations for paired Husky and Drone images. Images are densely annotated with segmentation labels in the COCO segmentation format.

extrinsic transformation is available, we first apply CLAHE [14] and Sobel gradient magnitude extraction [18] to both modalities to emphasize shared structural boundaries. We then estimate the alignment with a coarse-to-fine search: a coarse pass on downsampled images over scale ratios of approximately 0.3–0.8 of the RGB image width and translations up to ± 120 pixels, followed by full-resolution refinement around the best coarse solution. The alignment is obtained by:

$$\hat{\mathcal{T}} = \arg \max_{\mathcal{T}} \left(\text{NCC}(\nabla I_{\text{rgb}}, \mathcal{T}(\nabla I_{\text{ir}})) - \lambda d(\mathcal{T}) \right), \quad (2)$$

where $\mathcal{T}$ is a similarity transform with scale and translation, $\text{NCC}(\cdot, \cdot)$ denotes normalized cross-correlation between two gradient images, $d(\mathcal{T})$ is a normalized Euclidean penalty on the offset between the transformed thermal image center and the RGB image center, and $\lambda = 0.03$. The aligned streams support thermal overlays such as white-hot and inferno renderings (Fig. 3) and help identify the UGV thermal signature in aerial imagery, providing an additional cue for cross-view robot association under vegetation or partial canopy occlusion.

Foundation-Model-Assisted Segmentation Annotation Our dataset provides semantic segmentation annotations through a foundation-model-assisted human-in-the-loop pipeline. Instead of relying on either fully manual labeling or fully automatic prediction, we first generate mask proposals and then refine them through human correction. In this workflow, annotators primarily assign semantic classes and correct local mask errors, which substantially reduces annotation effort compared with drawing pixel-accurate segmentations from scratch.

We adopt SAM3 [3] for mask pre-labeling due to its ability to generate high-quality segmentation masks and support of interactive refinement. Un-

like detection-oriented models such as Grounding DINO [10] which produce bounding-box-level localization, SAM3 is well-suited for pixel-level annotation. This is crucial in off-road environments, where elements like vegetation, mud boundaries, and irregular terrain rarely conform to rectangular priors. By providing accurate initial mask proposals for these complex shapes, SAM3 significantly reduces the manual correction effort required during the annotation process.

To support efficient human correction, we build our own annotation tools and service pipeline. Annotators can inspect the SAM3-generated masks, assign semantic categories, and correct local errors where needed. This design preserves the efficiency of automatic pre-labeling while maintaining the quality required for the final dataset release. After manual correction, the refined labels are used to further train an updated SAM3 model adapted to our off-road domain. This iterative process improves the quality of subsequent pre-label generation and further reduces annotation effort in later stages. Overall, the pipeline provides a practical compromise between fully automatic and fully manual annotation, enabling scalable, high-quality segmentation labeling for challenging scenes.

4 Dataset Benchmarking

To evaluate the usefulness of GA3T for collaborative perception, we conduct a terrain segmentation benchmark using the SAM3 foundation model. We use the 20260320_125939 subset, which contains around 8,000 manually annotated images from both UAV and UGV viewpoints. Fine-tuning is performed on a cluster of 4× NVIDIA H200 GPUs. We use an 85/15 train-validation split and a two-stage training strategy.

Phase 1 (head-only adaptation): We freeze the vision and text encoders and train only the mask decoder for 40 epochs. The learning rate is set to 6×10^{-4} with an effective batch size of 64. This stage adapts the decoder to the off-road domain while keeping the pretrained backbone fixed.

Phase 2 (backbone fine-tuning): Starting from the best Phase 1 checkpoint, we unfreeze the vision encoder and fine-tune it with a restricted learning-rate ratio of 0.01, corresponding to $LR_{backbone} = 1 \times 10^{-6}$. Training continues for 20 additional epochs. Because unfreezing the vision encoder substantially increases memory usage, we use a batch size of 4 with 8 gradient accumulation steps, giving an effective batch size of 128. We optimize a composite loss:

$$L = \lambda_{\text{cls}} L_{\text{focal}} + \lambda_{\text{box}} L_{\text{L1}} + \lambda_{\text{giou}} L_{\text{giou}} + \lambda_{\text{mask}} L_{\text{BCE}} + \lambda_{\text{dice}} L_{\text{dice}} + \lambda_{\text{pres}} L_{\text{pres}} \quad (3)$$

where λ_{mask} and λ_{dice} are both set to 3.0, and λ_{pres} denotes the presence classification weight.

Benchmark Results We compare the zero-shot SAM3 baseline with models adapted on GA3T using our two-stage training pipeline. The results are sum-

Table 3: Class-conditioned mask IoU on the GA3T test set for a zero-shot SAM3 baseline and models fine-tuned on GA3T using class-prompted segmentation.

Model Strategy	UGV View IoU	UAV View IoU	Overall IoU
Baseline (Zero-shot)	0.7030	0.5043	0.5615
SAM3 Phase 1 (Head)	0.7429	0.6880	0.7153
SAM3 Phase 2 (Full)	0.7314	0.7270	0.7287

marized in Table 3. We report class-conditioned mask IoU, computed by accumulating per-class intersections and unions over the test set and then averaging IoU across semantic classes. The overall score is obtained by first merging the UAV and UGV per-class values and then recomputing the class-wise mean IoU.

Discussion The results show that GA3T is a meaningful benchmark for class-conditioned off-road segmentation across heterogeneous viewpoints. The zero-shot SAM3 baseline performs reasonably well on UGV imagery but is noticeably weaker on UAV imagery, reflecting the added difficulty of aerial perception under viewpoint shift, partial canopy occlusion, and weaker local perspective structure.

Adaptation on GA3T improves performance on both views, with the largest gains on the UAV data. This indicates that the dataset captures domain characteristics that are not sufficiently covered by generic pretrained segmentation priors. Head-only adaptation already provides a strong improvement over the zero-shot baseline, while the second stage of backbone fine-tuning further improves UAV and overall performance. These results suggest that GA3T supports both effective domain adaptation and challenging evaluation for collaborative air-ground perception in unstructured outdoor environments.

5 Conclusion

GA3T is a comprehensive collaborative perception dataset tailored for UAV-UGV teams navigating diverse off-road environments. Collected in four unique environments, the dataset contains forest trails, rocky paths, muddy trenches, grass-covered fields, standing water, and large snow piles. With data from a wide number of sensors, including 3D LiDAR, stereo camera, GPS, and RGB+IR imagery, GA3T provides a unique set of capabilities with wide range of potential applications. Additionally, the paired ground and aerial camera views include over 8,000 frames with dense semantic segmentation annotations, allowing for terrain identification from multiple viewpoints, with potential applications ranging from multi-view SLAM to terrain-optimized path planning. Together, these features produce a dataset that is uniquely positioned to enable multi-robot collaboration, and stands out as a comprehensive resource for future work in heterogeneous multi-robot coordination.

Acknowledgments

Computational resources were provided in part through NSF MRI Award Number 2320600.

References

1. Arnold, E., Dianati, M., de Temple, R., Fallah, S.: Cooperative perception for 3d object detection in driving scenarios using infrastructure sensors. *IEEE Transactions on Intelligent Transportation Systems* **23**(3), 1852–1864 (2020)
2. Aybakan, A., Haddeler, G., Akay, M.C., Ervan, O., Temeltas, H.: A 3d lidar dataset of itu heterogeneous robot team. In: *Proceedings of the 5th International Conference on Robotics and Artificial Intelligence*. pp. 12–17 (2019)
3. Carion, N., Gustafson, L., Hu, Y.T., Debnath, S., Hu, R., Suris, D., Ryali, C., Alwala, K.V., Khedr, H., Huang, A., et al.: Sam 3: Segment anything with concepts. *arXiv preprint arXiv:2511.16719* (2025)
4. Chang, Y., Ebadi, K., Denniston, C.E., Ginting, M.F., Rosinol, A., Reinke, A., Palieri, M., Shi, J., Chatterjee, A., Morrell, B., et al.: Lamp 2.0: A robust multi-robot slam system for operation in challenging large-scale underground environments. *IEEE Robotics and Automation Letters* **7**(4), 9175–9182 (2022)
5. Cristofalo, E., Leahy, K., Vasile, C.I., Montijano, E., Schwager, M., Belta, C.: Localization of a ground robot by aerial robots for gps-deprived control with temporal logic constraints. In: *International symposium on experimental robotics*. pp. 525–537. Springer (2016)
6. Datar, A., Pokhrel, A., Nazeri, M., Rao, M.B., Rangwala, H., Pan, C., Zhang, Y., Harrison, A., Wigness, M., Osteen, P.R., et al.: M2p2: A multi-modal passive perception dataset for off-road mobility in extreme low-light conditions. In: *2025 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*. pp. 13690–13696. IEEE (2025)
7. Feng, D., Qi, Y., Zhong, S., Chen, Z., Jiao, Y., Chen, Q., Jiang, T., Chen, H.: S3e: A large-scale multimodal dataset for collaborative slam. *arXiv preprint arXiv:2210.13723* (2022)
8. Jiang, P., Osteen, P., Wigness, M., Saripalli, S.: Rellis-3d dataset: Data, benchmarks and analysis. In: *2021 IEEE international conference on robotics and automation (ICRA)*. pp. 1110–1116. IEEE (2021)
9. Li, Y., Ma, D., An, Z., Wang, Z., Zhong, Y., Chen, S., Feng, C.: V2x-sim: Multi-agent collaborative perception dataset and benchmark for autonomous driving. *IEEE Robotics and Automation Letters* **7**(4), 10914–10921 (2022)
10. Liu, S., Zeng, Z., Ren, T., Li, F., Zhang, H., Yang, J., Jiang, Q., Li, C., Yang, J., Su, H., et al.: Grounding dino: Marrying dino with grounded pre-training for open-set object detection. In: *European conference on computer vision*. pp. 38–55. Springer (2024)
11. Mortimer, P., Hagmanns, R., Granero, M., Luettel, T., Petereit, J., Wuensche, H.J.: The goose dataset for perception in unstructured environments. In: *2024 IEEE International Conference on Robotics and Automation (ICRA)*. pp. 14838–14844. IEEE (2024)
12. Patel, M., Yang, F., Qiu, Y., Cadena, C., Scherer, S., Hutter, M., Wang, W.: Tartanground: A large-scale dataset for ground robot perception and navigation. In: *2025 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*. pp. 20524–20531. IEEE (2025)

13. Peterson, K., Mayers, Z., Yousuf, A., Chowdhury, P., Zaczepinski, A., Arezoomandan, S., Maarefdoust, R., Han, D.: Lrddv3: High-resolution long-range drone detection dataset with range information and thermal data. In: 2026 IEEE International Conference on Robotics and Automation (ICRA) (2026)
14. Pizer, S.M.: Contrast-limited adaptive histogram equalization: Speed and effectiveness stephen m. pizer, r. eugene johnston, james p. ericksen, bonnie c. yankaskas, keith e. muller medical image display research group. In: Proceedings of the first conference on visualization in biomedical computing, Atlanta, Georgia. vol. 337, p. 2 (1990)
15. Rouhi, A., Patel, S., McCarthy, N., Khan, S., Khorsand, H., Lefkowitz, K., Han, D.: Lrddv2: Enhanced long-range drone detection dataset with range information and comprehensive real-world challenges. In: 2024 International Symposium of Robotics Research (ISRR) (2024)
16. Rouhi, A., Umare, H., Patal, S., Kapoor, R., Deshpande, N., Arezoomandan, S., Shah, P., Han, D.: Long-range drone detection dataset. In: 2024 IEEE International Conference on Consumer Electronics (ICCE) (2024). <https://doi.org/10.1109/ICCE59016.2024.10444135>
17. Sivaprakasam, M., Maheshwari, P., Castro, M.G., Triest, S., Nye, M., Willits, S., Saba, A., Wang, W., Scherer, S.: Tartandrive 2.0: More modalities and better infrastructure to further self-supervised learning research in off-road driving tasks. In: 2024 IEEE International Conference on Robotics and Automation (ICRA). pp. 12606–12606. IEEE (2024)
18. Sobel, I., Feldman, G., et al.: A 3x3 isotropic gradient operator for image processing. a talk at the Stanford Artificial Project in **1968**, 271–272 (1968)
19. Tian, Y., Chang, Y., Quang, L., Schang, A., Nieto-Granda, C., How, J.P., Carlone, L.: Resilient and distributed multi-robot visual slam: Datasets, experiments, and lessons learned. arXiv preprint arXiv:2304.04362 (2023)
20. Tranzatto, M., Dharmadhikari, M., Bernreiter, L., Camurri, M., Khattak, S., Masciarich, F., Pfreundschuh, P., Wisth, D., Zimmermann, S., Kulkarni, M., et al.: Team cerberus wins the darpa subterranean challenge: Technical overview and lessons learned. arXiv preprint arXiv:2207.04914 (2022)
21. Vizzo, I., Guadagnino, T., Mersch, B., Wiesmann, L., Behley, J., Stachniss, C.: Kiss-icp: In defense of point-to-point icp—simple, accurate, and robust registration if done the right way. IEEE Robotics and Automation Letters **8**(2), 1029–1036 (2023)
22. Wigness, M., Eum, S., Rogers, J.G., Han, D., Kwon, H.: A rugd dataset for autonomous navigation and visual perception in unstructured outdoor environments. In: 2019 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS). pp. 5000–5007. IEEE (2019)
23. Xu, R., Xiang, H., Xia, X., Han, X., Li, J., Ma, J.: Opv2v: An open benchmark dataset and fusion pipeline for perception with vehicle-to-vehicle communication. In: IEEE International Conference on Robotics and Automation (ICRA). pp. 2583–2589 (2022)
24. Yu, H., Luo, Y., Shu, M., Huo, Y., Yang, Z., Shi, Y., Guo, Z., Li, H., Hu, X., Yuan, J., et al.: Dair-v2x: A large-scale dataset for vehicle-infrastructure cooperative 3d object detection. In: IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR). pp. 21361–21370 (2022)
25. Zhou, Y., Quang, L., Nieto-Granda, C., Loianno, G.: Coped-advancing multi-robot collaborative perception: A comprehensive dataset in real-world environments. IEEE Robotics and Automation Letters **9**(7), 6416–6423 (2024)

26. Zhu, P., Wen, L., Du, D., Bian, X., Fan, H., Hu, Q., Ling, H.: Detection and tracking meet drones challenge. *IEEE transactions on pattern analysis and machine intelligence* **44**(11), 7380–7399 (2021)
27. Zhu, Y., Kong, Y., Jie, Y., Xu, S., Cheng, H.: Graco: A multimodal dataset for ground and aerial cooperative localization and mapping. *IEEE Robotics and Automation Letters* **8**(2), 966–973 (2023)