

Superposition Is Not Necessary:

A Mechanistic Interpretability Analysis of Transformer Representations for Time Series Forecasting

Alper Yıldırım*

Abstract

Transformer architectures have been widely adopted for time series forecasting, yet whether the representational mechanisms that make them powerful in NLP actually engage on time series data remains unexplored. The persistent competitiveness of simple linear models such as DLinear has fueled ongoing debate, but no mechanistic explanation for this phenomenon has been offered. We address this gap by applying sparse autoencoders (SAEs), a tool from mechanistic interpretability, to probe the internal representations of PatchTST. We first establish that a single-layer, narrow-dimensional transformer matches the forecasting performance of deeper configurations across commonly used benchmarks. We then train SAEs on the post-GELU intermediate FFN activations with dictionary sizes ranging from $0.5\times$ to $4.0\times$ the native dimensionality. Expanding the dictionary yields negligible downstream performance change (average 0.214%), with large portions of overcomplete dictionaries remaining inactive. Targeted causal interventions on dominant latent features produce minimal forecast perturbation. Across all evaluated settings, we observe no empirical evidence that the analyzed FFN representations rely on strong superposition. Instead, the representations remain sparse, stable under aggressive dictionary expansion, and largely insensitive to latent interventions. These results demonstrate that superposition is not necessary for competitive performance on standard forecasting benchmarks, suggesting they may not demand the rich compositional representations that drive transformer success in language modeling, and helping explain the persistent competitiveness of simple linear models.

Keywords: mechanistic interpretability, time series forecasting, sparse autoencoders, transformers, superposition

1 Introduction

The success of transformers in natural language processing [Vaswani et al., 2017] has motivated their widespread adoption for time series forecasting. Models such as Informer [Zhou et al., 2021], Autoformer [Wu et al., 2021], FEDformer [Zhou et al., 2022], PatchTST [Nie et al., 2023], and iTransformer [Liu et al., 2024] have progressively imported architectural innovations from the language modeling domain, each proposing new attention mechanisms or input representations tailored to temporal data. Yet a fundamental question remains largely unexamined: do the representational mechanisms that make transformers powerful in NLP — particularly the ability to compose and compress rich features through superposition — actually engage on time series forecasting tasks?

This question is not merely theoretical. Zeng et al. [2023] demonstrated that DLinear, a simple single-layer linear model, matches or outperforms many transformer-based forecasters on standard benchmarks, igniting an ongoing debate about whether transformer complexity is justified for time series. Subsequent work has responded with improved architectures [Wu et al., 2023, Liu et al., 2024], yet the debate has remained confined to benchmark comparisons: each side proposes a model, reports metrics, and draws architectural conclusions. What has been conspicuously absent is *mechanistic* evidence — an examination of what transformers actually learn internally when applied to time series data, and whether this differs fundamentally from the representations they build for language.

In parallel, the field of mechanistic interpretability has developed powerful tools for understanding the internal representations of neural networks. The superposition hypothesis [Elhage et al., 2022] proposes that neural networks represent more features than they have dimensions by encoding them

*Corresponding author: yildirim.alper.dev@gmail.com
ORCID: 0009-0004-8029-1772

in overlapping, superimposed directions. Sparse autoencoders (SAEs) have emerged as a primary tool for decomposing these superimposed representations into interpretable sparse features, with notable success in large language models [Bricken et al., 2023, Templeton et al., 2024, Cunningham et al., 2024]. In LLMs, SAE analysis consistently reveals dense superposition: expanding the dictionary uncovers progressively more monosemantic features, and intervening on individual latents produces measurable behavioral changes. However, these tools have seen virtually no application to time series transformers, leaving a significant gap in our understanding of how these models represent temporal patterns.

We bridge these two open questions by applying SAE-based mechanistic analysis to PatchTST [Nie et al., 2023], the canonical channel-independent patch-based transformer for time series forecasting and a central reference point in the DLinear debate. Our choice of PatchTST is deliberate: it is not merely one architecture among many, but the model whose design most directly inherits the representational machinery of NLP transformers. If its internal representations do not rely on superposition to achieve competitive forecasting performance, this constitutes evidence that the task itself does not demand it, rather than reflecting a limitation of one particular architecture.

Our analysis proceeds in three steps. First, we establish that a single-layer, narrow-dimensional PatchTST — modernized with rotary position embeddings [Su et al., 2024] and RMSNorm [Zhang and Sennrich, 2019] — matches the forecasting performance of deeper configurations across eight commonly used benchmarks, demonstrating that minimal transformer capacity suffices for these tasks. Second, we train SAEs on the post-GELU intermediate FFN activations of these models with dictionary sizes ranging from $0.5\times$ to $4.0\times$ the native dimensionality. We find that expanding the dictionary yields negligible changes in downstream forecasting performance, that expanded dictionary capacity provides no functional benefit, and that targeted causal interventions on dominant latent features produce minimal forecast perturbation. Third, we synthesize these findings into a mechanistic argument: superposition is not necessary for competitive performance on standard time series forecasting benchmarks.

Crucially, our claim is not that no time series transformer could ever employ superposition, nor that superposition cannot exist within these models. Rather, we demonstrate that competitive forecasting performance is achievable without it, which suggests that the standard benchmarks driving the DLinear debate may not contain the representational richness that would require — or reward — the complex feature composition that transformers uniquely enable in language. This offers a mechanistic explanation, rather than a purely empirical one, for why simple linear models remain competitive: the underlying data may simply not demand what transformers are best at.

2 Related Work

2.1 Transformers for Time Series Forecasting

The application of transformer architectures to time series forecasting has progressed rapidly, beginning with Informer [Zhou et al., 2021], which introduced sparse attention for long-sequence efficiency, followed by Autoformer [Wu et al., 2021] and FEDformer [Zhou et al., 2022], which incorporated decomposition and frequency-domain mechanisms respectively. PatchTST [Nie et al., 2023] introduced channel-independent patching, treating each variate as a separate token sequence and segmenting it into subseries-level patches, achieving strong performance with a simpler design. More recently, iTransformer [Liu et al., 2024] inverted the standard approach by embedding across variates rather than time steps. Throughout this progression, each model has imported architectural innovations from NLP — attention variants, positional encodings, normalization schemes — without examining whether the representational mechanisms that make these components powerful in language actually engage on temporal data.

2.2 The Linear Model Debate

Zeng et al. [2023] challenged the transformer paradigm by demonstrating that DLinear, a single-layer linear model with seasonal-trend decomposition, matches or outperforms transformer-based forecasters across standard benchmarks. This finding ignited an ongoing debate about whether transformer complexity is justified for time series. Subsequent work has responded with improved architectures [Wu et al., 2023, Liu et al., 2024], and practitioners have noted that transformers offer advantages when covariates and cross-variate dependencies are important. More recently, Xu et al. [2024] pushed this finding considerably further: their FITS model matches PatchTST across standard long-term forecasting benchmarks using only $\sim 10k$ – $50k$ parameters via a single complex-valued linear layer in the frequency

domain — more than two orders of magnitude smaller than transformer baselines, and roughly an order of magnitude smaller than DLinear itself. However, the debate has remained confined to benchmark comparisons: each side proposes a model, reports metrics, and draws architectural conclusions. No prior work has offered *mechanistic* evidence — an examination of what transformers actually learn internally — to explain why simple linear models remain competitive on standard forecasting benchmarks.

2.3 Mechanistic Interpretability and Sparse Autoencoders

The superposition hypothesis [Elhage et al., 2022] proposes that neural networks represent more features than they have dimensions by encoding them in overlapping, superimposed directions. Sparse autoencoders (SAEs) have emerged as the primary tool for decomposing these superimposed representations into interpretable sparse features. In large language models, SAE analysis has consistently revealed dense superposition: expanding the dictionary uncovers progressively more monosemantic features, and intervening on individual latents produces measurable behavioral changes [Bricken et al., 2023, Templeton et al., 2024, Cunningham et al., 2024]. SAEs have also been applied to vision transformers, where they successfully extract interpretable visual features [Pach et al., 2025], establishing that the methodology transfers beyond language.

Work on understanding the internal structure of NLP transformers extends beyond superposition analysis. Tenney et al. [2019] demonstrated that BERT’s layers resolve linguistic abstractions in a progression mirroring the classical NLP pipeline — from POS tagging in early layers to coreference in later layers — providing evidence that depth serves a clear functional purpose in language models. Niu et al. [2022] subsequently challenged the simplicity of this pipeline interpretation, showing through their GridLoc probe that BERT’s linguistic structure is distributed across both layers and token positions in a more complex pattern than a strict pipeline would predict. In either interpretation, NLP transformers exhibit rich internal representational structure that requires and utilizes multiple layers.

An important methodological consideration is raised by Heap et al. [2025], who demonstrated that SAEs can extract seemingly interpretable features even from randomly initialized, untrained transformers. This finding suggests that some SAE results may reflect statistical properties of input data rather than learned computations. Our work addresses this concern by focusing on *downstream functional impact* — dictionary scaling effects on forecasting performance and causal intervention effects on model outputs — rather than relying solely on feature interpretability.

The most closely related concurrent work applies SAEs to large pretrained time series foundation models: Mishra [2026] on Chronos-T5-Large and Divo et al. [2026] on Chronos-2, both recovering interpretable feature structure within these models. Kalnāre et al. [2026] apply attribution-based analysis to transformer-based time series *classification* without using SAEs. Our work targets a complementary question: whether superposition is *necessary* for competitive forecasting performance on the standard benchmarks driving the DLinear debate. We study a small, task-specific transformer rather than a pre-trained foundation model, and probe for superposition through dictionary scaling and causal interventions rather than characterizing learned features — finding, in contrast to TSFM work, no superposition signatures.

3 Methodology

3.1 Base Architecture

We adopt PatchTST [Nie et al., 2023] as our base forecasting model, retaining its core channel-independent patching design: each input variate is treated as an independent univariate sequence, segmented into overlapping patches of length 16 with stride 8, and projected into a shared transformer backbone. The model applies Reversible Instance Normalization (RevIN) [Kim et al., 2022] at the input and output boundaries to handle distribution shift.

We make two architectural modernizations relative to the original PatchTST configuration. First, we replace the learned absolute positional embeddings with Rotary Position Embeddings (RoPE) [Su et al., 2024], which encode relative position directly within the attention computation. This choice is motivated both by improved position generalization and by compatibility with SAE analysis: RoPE avoids entangling positional information into the residual stream, producing cleaner activation distributions at the FFN layer. Second, we replace BatchNorm with RMSNorm [Zhang and Sennrich, 2019], following modern transformer practice.

Critically, we use a single transformer layer (depth=1) with narrow model dimensions. The per-dataset d_{model} values range from 16 (Exchange, ETT variants) to 128 (Electricity), with an FFN intermediate dimension of $2 \times d_{\text{model}}$ via a standard GELU-activated feed-forward network. The original PatchTST paper evaluated depths of 3 to 6 layers but did not explore minimal configurations. As we demonstrate in Section 4.1, this single-layer configuration matches published PatchTST performance across all eight benchmarks, establishing that minimal transformer capacity suffices for these tasks.

3.2 Training Protocol

We evaluate on eight commonly used long-term forecasting benchmarks: Weather, Electricity, and Traffic [Wu et al., 2021], Exchange [Lai et al., 2018], and ETTh1/h2/m1/m2 [Zhou et al., 2021], obtained via the Time Series Library. For the ETT datasets, we use the standard fixed splits (train/val/test). For all other datasets, we apply a 70/10/20 chronological split. All variates are normalized using a StandardScaler fitted on the training partition only.

Models are trained with a lookback window of 336 time steps and evaluated at four prediction horizons: 96, 192, 336, and 720. We use AdamW with a learning rate of 2×10^{-4} and no weight decay, MSE loss, dropout of 0.2, and gradient clipping at norm 1.0. Training proceeds for up to 80 epochs with a patience of 15 on validation loss, using ReduceLROnPlateau scheduling (factor 0.5, patience 3). All training is performed with bfloat16 mixed precision. Each configuration is trained with a fixed random seed.

3.3 Sparse Autoencoder Design

To probe for superposition within the transformer’s feed-forward network, we train sparse autoencoders (SAEs) on the post-GELU intermediate FFN activations. The hook is placed at the output of the GELU nonlinearity, capturing the intermediate representation after the up-projection and activation but before the down-projection. This is the standard hook location used in LLM SAE studies [Bricken et al., 2023, Cunningham et al., 2024]. We verify that these activations are functionally active — rather than an inert component — via zero ablation in Appendix B. The SAE architecture consists of a linear encoder mapping from the FFN intermediate dimension d_{ff} to a latent dimension d_{hidden} , followed by a ReLU activation, and a linear decoder mapping back to d_{ff} . The decoder columns are constrained to unit norm after each optimization step, following standard practice [Bricken et al., 2023]. We train SAEs at three dictionary scales: $0.5\times$, $1.0\times$, and $4.0\times$ the native FFN dimensionality, producing undercomplete, matched, and overcomplete dictionaries respectively.

Activations are harvested by running the frozen base model over training data, collecting post-GELU outputs up to a maximum of 10^6 patch-level activation vectors. The SAE is then trained on these harvested activations using Adam with a learning rate of 10^{-3} , minimizing a combined reconstruction and sparsity objective:

$$\mathcal{L} = \|\mathbf{x} - \hat{\mathbf{x}}\|_2^2 + \lambda \|\mathbf{f}\|_1 \quad (1)$$

where $\mathbf{x}$ is the original activation, $\hat{\mathbf{x}}$ is the SAE reconstruction, $\mathbf{f}$ is the latent activation vector, and $\lambda = 0.01$. Training runs for up to 50 epochs with early stopping (patience of 3, improvement threshold of 0.1%).

3.4 Evaluation Protocol

Our evaluation targets three distinct signatures of superposition, each designed to test a specific prediction that strong sparse-feature compression would produce:

Dictionary Scaling Analysis. If the FFN activations contain substantial superposed structure, expanding the SAE dictionary should progressively disentangle hidden features, improving reconstruction fidelity and preserving downstream behavior. We test this by replacing the original post-GELU activations with SAE reconstructions during inference and measuring the resulting forecasting degradation (percentage change in test MSE) across all dictionary scales. Under strong superposition, we would expect the $4.0\times$ dictionary to substantially outperform the $0.5\times$ dictionary. A flat degradation profile across scales indicates that additional dictionary capacity is not uncovering meaningful hidden structure.

Dead Latent Analysis. If the model is compressing many sparse features into limited dimensions, an overcomplete dictionary should activate a large number of additional latents to represent the newly disentangled features. We measure dead latent rates in the $4.0\times$ SAE by tracking which latents exceed an activation threshold of 10^{-5} across the full test set. High dead latent rates indicate that the expanded dictionary capacity is not being utilized, suggesting that the native representations do not contain large quantities of compressed sparse features awaiting recovery.

Causal Latent Interventions. If the SAE has recovered functionally important sparse features, intervening on individual latents should produce measurable downstream effects. For each benchmark, we identify the top 10 most highly activated latents in the $4.0\times$ dictionary (ranked by total activation magnitude across the full test set) and amplify each by a factor of $5.0\times$ during inference. The resulting prediction shift is measured as the MAE between the original and intervened forecasts. Small intervention effects suggest that individual sparse features do not serve as dominant causal directions controlling the forecast output.

4 Results

4.1 Single-Layer Sufficiency

Before probing for superposition, we first establish that a shallow transformer with a unified hyperparameter configuration remains competitive on standard long-term forecasting benchmarks. Despite using only a single transformer layer, a shared hyperparameter configuration, and substantially narrower model dimensions, our model achieves broadly comparable performance to the published PatchTST/42 results [Nie et al., 2023]. While this minimal configuration serves primarily as a simplified model for our interpretability analysis, its strong performance indicates that it is a sufficient representative of the architecture’s capabilities (see Appendix A for full forecasting results).

This observation motivates the central question of this work: if relatively shallow transformers already capture most of the achievable performance, what representational mechanisms — if any — does the FFN layer actually employ?

4.2 Minimal Sparse-Feature Scaling Under Dictionary Expansion

This section reports results for the dictionary scaling and dead latent analyses described in Section 3.4.

To test whether PatchTST FFN representations contain recoverable sparse structure hidden through superposition, we trained Sparse Autoencoders (SAEs) on post-GELU FFN activations with dictionary sizes ranging from $0.5\times$ to $4.0\times$ the native FFN dimensionality. During inference, the original activations were replaced with SAE reconstructions and downstream forecasting degradation was measured across all benchmarks and prediction horizons.

Despite the substantial increase in representational capacity, dictionary expansion produced only marginal downstream effects. Across all datasets and horizons, the average performance difference between the $0.5\times$ and $4.0\times$ dictionaries was only 0.214%. In many cases, degradation remained nearly constant across scales, with several benchmarks even showing slight improvements consistent with mild denoising effects.

Latent utilization statistics support this result. Dead latent rates varied across datasets, exceeding 60% on Traffic while remaining below 7% on most benchmarks. Together, these findings indicate that expanding sparse latent capacity does not uncover substantial additional functionally relevant structure within the analyzed FFN activations.

Unlike the strong sparse-feature scaling commonly reported in LLM SAE studies, the PatchTST representations examined here remain stable under aggressive dictionary expansion, suggesting weak sparse-feature pressure within the probed FFN layer. Although the $4.0\times$ dictionary consistently achieves lower reconstruction MSE than the $0.5\times$ dictionary (Table 2), this improved internal fidelity does not translate into downstream forecasting gains.

A potential concern is that most datasets still show 95%+ of $4.0\times$ latents firing above threshold. However, activity alone is not diagnostic: high latent activity combined with negligible downstream scaling (0.214%) and minimal causal sensitivity (≈ 0.031 MAE; Section 4.3) suggests these latents capture reconstruction-relevant but functionally inert structure rather than superposed features awaiting disentanglement.

Table 1: Sparse autoencoder analysis across eight standard forecasting benchmarks. Performance degradation remains stable despite 800% expansion of the latent dictionary, and causally amplifying the top-10 most active latents by 500% yields negligible downstream shift, suggesting that superposition is not necessary for competitive forecasting performance. Full SAE fidelity metrics (L0 sparsity and reconstruction MSE) are reported in Table 2.

Dataset	Horizon	Base MSE	Dead Latents	0.5x Deg.	1.0x Deg.	4.0x Deg.	Causal Shift MAE
Weather	96	0.1480	0.2%	+0.42%	+0.57%	+0.23%	0.0293
	192	0.1927	0.8%	+0.02%	−0.09%	+0.07%	0.0292
	336	0.2482	1.6%	−0.03%	−0.08%	−0.08%	0.0208
	720	0.3221	0.2%	+0.00%	−0.11%	−0.16%	0.0297
Electricity	96	0.1303	4.1%	+3.28%	+3.01%	+2.89%	0.0446
	192	0.1491	5.3%	+2.36%	+2.30%	+2.11%	0.0508
	336	0.1680	2.2%	+2.82%	+2.60%	+2.59%	0.0614
	720	0.2049	6.2%	+1.99%	+1.74%	+1.71%	0.0561
Traffic	96	0.3895	0.3%	+0.49%	+0.31%	+0.31%	0.0517
	192	0.4174	54.9%	+1.79%	+1.67%	+1.32%	0.0542
	336	0.4282	65.8%	+2.99%	+1.69%	+1.23%	0.0516
	720	0.4566	63.5%	+1.78%	+1.42%	+1.10%	0.0395
Exchange	96	0.0963	7.0%	+0.98%	+0.61%	+0.93%	0.0127
	192	0.1911	3.9%	+0.28%	+0.49%	+0.63%	0.0375
	336	0.3723	6.2%	−0.49%	−0.35%	−0.20%	0.0183
	720	0.9783	4.7%	+1.71%	+1.50%	+1.38%	0.0336
ETTh1	96	0.3779	4.7%	+0.01%	−0.01%	−0.00%	0.0218
	192	0.4230	5.5%	−0.09%	−0.13%	−0.11%	0.0223
	336	0.4524	3.9%	+0.04%	−0.03%	−0.02%	0.0251
	720	0.4774	4.7%	−0.28%	−0.26%	−0.24%	0.0254
ETTh2	96	0.2923	3.9%	−0.48%	−0.74%	−0.45%	0.0254
	192	0.3562	3.1%	−0.47%	−0.34%	−0.44%	0.0240
	336	0.3839	3.1%	−0.94%	−0.96%	−0.93%	0.0312
	720	0.4090	4.7%	+0.04%	−0.06%	−0.02%	0.0175
ETTM1	96	0.3070	1.6%	+0.37%	+0.34%	+0.28%	0.0223
	192	0.3384	0.8%	+0.43%	+0.29%	+0.37%	0.0234
	336	0.3655	0.0%	+0.14%	+0.37%	+0.39%	0.0205
	720	0.4288	1.6%	−0.21%	−0.19%	−0.15%	0.0216
ETTM2	96	0.1710	0.8%	+0.01%	+0.03%	−0.06%	0.0213
	192	0.2269	0.0%	−0.33%	−0.29%	−0.36%	0.0230
	336	0.2885	0.0%	−0.02%	−0.11%	−0.07%	0.0175
	720	0.3706	0.8%	−1.00%	−0.62%	−0.74%	0.0240

4.3 Limited Downstream Sensitivity to Latent Interventions

This section reports results for the causal latent intervention protocol described in Section 3.4.

To evaluate the functional influence of SAE-derived sparse features, we performed targeted causal interventions on the learned latent representations. For each dataset, we identified the top 10 most highly activated latents within the $4.0\times$ overcomplete SAE dictionary and amplified each latent by a factor of $5.0\times$ during inference on the full test set.

Despite these aggressive interventions, downstream forecasting behavior remained largely stable. Across all benchmarks, the average intervention-induced prediction shift remained approximately 0.031 MAE, while the maximum observed shift reached only 0.061. These comparatively small output changes persisted across all datasets and prediction horizons, despite the large magnitude of the latent perturbations.

The intervention results suggest that the dominant SAE features identified within the analyzed post-GELU FFN activations do not individually exert strong control over the final forecast outputs. Instead, the forecasting computation appears comparatively robust to localized sparse latent perturbations, potentially indicating distributed, redundancy-tolerant, or smoothly shared internal representations rather than highly dominant sparse causal directions. Although we cannot rule out that alternative SAE

training regimes, sparsity penalties, or decomposition methods might recover stronger sparse structure, the present results provide no evidence for strong superposition within the probed representations.

Table 2: Internal sparse autoencoder fidelity metrics. The $4.0\times$ overcomplete dictionary consistently achieves lower reconstruction MSE than the $0.5\times$ dictionary, yet this improved internal fidelity does not translate into downstream forecasting gains (see Table 1), suggesting the additionally recovered structure is not functionally relevant.

Dataset	Horizon	L0 (0.5 $\times$)	L0 (1.0 $\times$)	L0 (4.0 $\times$)	Recon MSE (0.5 $\times$)	Recon MSE (1.0 $\times$)	Recon MSE (4.0 $\times$)
Weather	96	4.1	4.8	6.3	0.0375	0.0339	0.0278
	192	4.0	5.2	6.1	0.0334	0.0287	0.0262
	336	2.2	2.7	3.1	0.0191	0.0174	0.0162
	720	3.7	4.4	5.2	0.0265	0.0234	0.0228
Electricity	96	2.5	2.9	3.2	0.0449	0.0428	0.0402
	192	2.1	2.3	2.7	0.0355	0.0344	0.0320
	336	1.8	1.9	2.1	0.0265	0.0259	0.0252
	720	0.6	0.9	1.0	0.0207	0.0194	0.0190
Traffic	96	1.5	2.1	2.7	0.0346	0.0289	0.0272
	192	1.0	1.2	1.6	0.0278	0.0252	0.0213
	336	0.3	1.2	1.6	0.0392	0.0239	0.0204
	720	0.6	1.0	1.5	0.0301	0.0243	0.0198
Exchange	96	3.5	4.7	6.8	0.0065	0.0054	0.0042
	192	3.6	4.7	7.1	0.0071	0.0061	0.0056
	336	3.6	4.1	7.3	0.0085	0.0068	0.0055
	720	4.0	5.8	9.3	0.0113	0.0083	0.0066
ETTh1	96	3.4	4.7	7.0	0.0111	0.0087	0.0073
	192	4.0	4.8	7.8	0.0113	0.0092	0.0071
	336	4.5	5.8	9.5	0.0128	0.0097	0.0075
	720	3.6	4.9	6.7	0.0101	0.0079	0.0065
ETTh2	96	4.6	6.2	10.4	0.0165	0.0117	0.0085
	192	4.3	6.3	10.0	0.0145	0.0103	0.0076
	336	4.3	6.0	9.1	0.0120	0.0098	0.0080
	720	4.3	6.0	8.9	0.0106	0.0089	0.0069
ETTm1	96	3.4	4.0	6.4	0.0073	0.0061	0.0052
	192	3.8	5.0	7.9	0.0095	0.0083	0.0064
	336	4.1	5.6	9.2	0.0128	0.0096	0.0074
	720	3.0	4.5	6.3	0.0075	0.0062	0.0055
ETTm2	96	4.1	5.8	9.4	0.0125	0.0095	0.0072
	192	4.5	5.9	8.7	0.0128	0.0094	0.0072
	336	4.1	5.8	8.5	0.0108	0.0082	0.0063
	720	4.0	5.9	8.5	0.0138	0.0098	0.0074

5 SAE Sparsity Calibration

To verify that our fixed sparsity penalty ($\lambda = 0.01$) does not artificially suppress valid features, we swept $\lambda \in \{0.1, 0.01, 0.001, 0.0001\}$ for both the $0.5\times$ and $4.0\times$ dictionaries across all eight benchmarks and four prediction horizons (256 SAE training runs total). Table 3 reports average L_0 (active latents per token) as a function of λ , averaged across horizons. As λ decreases, L_0 increases smoothly across all datasets for both dictionary sizes, confirming that the SAE responds appropriately to reduced sparsity pressure. Notably, the $4.0\times$ dictionary consistently achieves higher L_0 than the $0.5\times$ dictionary at each λ , demonstrating that the larger dictionary does utilize some additional capacity — yet as shown in our main results (Table 1), this additional activation does not translate into downstream forecasting improvements. The combination of proper SAE calibration (this table) with flat downstream scaling (Table 1) and dead latent patterns observed across the full test set (Table 1) confirms that the absence of recoverable superposition is genuine, not an artifact of the sparsity penalty.

Table 3: SAE sparsity calibration: average L_0 (active latents per token) across λ values, averaged over all prediction horizons. Both dictionary sizes respond smoothly to reduced sparsity pressure, confirming the SAE instrument is properly calibrated.

Dataset	d_{ff}	0.5× Dictionary L_0				4.0× Dictionary L_0			
		$\lambda=0.1$	$\lambda=0.01$	$\lambda=0.001$	$\lambda=0.0001$	$\lambda=0.1$	$\lambda=0.01$	$\lambda=0.001$	$\lambda=0.0001$
Weather	128	0.0	3.7	19.8	53.5	0.0	5.3	32.6	143.5
Electricity	256	0.0	1.7	20.5	84.1	0.0	2.4	32.6	176.1
Traffic	192	0.0	0.9	12.7	55.5	0.0	1.9	18.7	95.8
Exchange	32	0.0	3.5	10.0	15.2	0.1	7.3	23.8	60.6
ETTh1	32	0.0	3.8	12.0	15.2	0.0	8.0	28.3	69.5
ETTh2	32	0.0	4.5	11.9	15.3	0.0	9.3	33.1	79.5
ETTm1	32	0.0	3.6	11.4	15.3	0.0	7.4	26.2	65.1
ETTm2	32	0.0	4.0	12.2	15.6	0.0	8.8	30.5	75.3

6 Discussion

Our goal is not to demonstrate that all time series transformers are free of superposition — such a claim would require exhaustive analysis across every architecture and is neither feasible nor necessary. Instead, we demonstrate that superposition is *not necessary* for competitive forecasting performance on standard benchmarks. PatchTST remains one of the strongest forecasting architectures, with recent large-scale evaluations confirming that no single model consistently dominates [Brigato et al., 2026]. If strong superposition were functionally important for these tasks, it should be detectable in the architecture that most closely mirrors the NLP transformers where superposition has been extensively documented.

The single-layer sufficiency result carries implications beyond architecture design. A task solvable by one transformer layer with d_{model} as small as 16 has very low intrinsic dimensionality. The superposition hypothesis [Elhage et al., 2022] predicts that superposition arises when a model must compress more features than it has dimensions. When there are fewer features than dimensions, no compression pressure exists. Our SAE results confirm this: expanding the dictionary does not uncover substantial hidden structure, overcomplete dictionaries provide no functional benefit, and improved reconstruction fidelity (Table 2) does not translate into downstream gains.

This stands in stark contrast to NLP, where depth serves a clear functional purpose. Tenney et al. [2019] showed that BERT’s layers resolve linguistic abstractions progressively — from POS tagging to coreference — and even Niu et al. [2022], who challenged this pipeline interpretation, found rich linguistically motivated structure distributed across layers and token positions. Time series forecasting on standard benchmarks exhibits no analogous hierarchy: a single layer suffices, and its representations show no evidence of dense superimposed structure.

The persistent competitiveness of simple models — DLinear [Zeng et al., 2023], and more strikingly FITS [Xu et al., 2024], which matches PatchTST using only $\sim 10\text{k}$ parameters via a single complex-valued frequency-domain layer — follows naturally from this picture. Chen et al. [2023] reinforce this from the data side: their TMix-Only ablation shows that cross-variate mixing provides essentially no benefit on these benchmarks, suggesting the data lacks the cross-feature interactions that complex architectures are designed to exploit. If the underlying data does not require complex feature composition, transformer capacity goes largely unused, and progressively simpler models capture what there is to capture. The question may be better reframed: do standard forecasting benchmarks contain the representational richness that would justify transformer complexity? Our results suggest they do not, and the field may benefit from developing benchmarks with greater intrinsic complexity to meaningfully differentiate architectural advances.

7 Limitations

We probe only the post-GELU intermediate FFN activations, a commonly used hook location in LLM SAE studies. Attention heads and residual stream representations may encode additional structure not captured by this analysis and represent a natural direction for future work. However, the FFN intermediate is the network’s most expanded working space ($2\times$ the residual stream width), where sparse features would be expected to disentangle most easily and superposition pressure should be weakest. The absence of strong superposition signatures even in this expanded representation is therefore

informative about the network’s overall compression regime. Our goal is not to exhaustively characterize every transformer component, but to use mechanistic analysis to probe the representational demands of the underlying forecasting tasks themselves. The absence of strong FFN superposition suggests that these benchmarks do not exert the kind of feature-compression pressure commonly associated with transformer advantages in language modeling, helping explain the persistent competitiveness of simple linear models such as DLinear.

8 Conclusion

We applied sparse autoencoders to probe the internal representations of PatchTST, providing the first mechanistic interpretability analysis of a time series forecasting transformer. After establishing that a single-layer configuration achieves competitive performance across eight standard benchmarks, we showed that its post-GELU FFN activations exhibit no evidence of strong superposition: dictionary expansion yields negligible downstream improvement (0.214% average), overcomplete dictionaries remain largely inactive, and causal amplification of dominant latents produces minimal forecast perturbation. These findings demonstrate that superposition is not necessary for competitive time series forecasting on standard benchmarks, offering a mechanistic explanation for the persistent competitiveness of simple linear models and suggesting that the representational demands of these tasks are fundamentally lower than those of language.

9 Broader Impact and Future Work

While our analysis reveals that standard forecasting benchmarks do not demand complex sparse representations, this finding points toward domains where the opposite may hold. Medical time series — such as EEG recordings preceding epileptic seizures, ECG signals before cardiac events, or intracranial pressure traces prior to stroke — may exhibit precisely the kind of representational complexity that these benchmarks lack. Transformers trained on such data may need to compress subtle, clinically meaningful physiological patterns into their representations, potentially giving rise to genuine superposition.

In such settings, the SAE methodology demonstrated here could serve as a bridge between model predictions and clinical understanding. If a transformer reliably forecasts an impending seizure, SAE decomposition could isolate the specific latent features that activate in the pre-ictal period. These latents could then be mapped back to input channels and temporal windows, producing candidate biomarkers for neurologists to investigate. Rather than treating the model as an opaque predictor, clinicians could use SAE-derived features as interpretable hypotheses about physiological correlates that are invisible to unaided observation.

Financial time series present another promising domain. Asset returns exhibit regime-dependent dynamics, cross-instrument contagion, and macroeconomic dependencies that jointly create representational demands far exceeding those of the benchmarks studied here. Models such as Temporal Fusion Transformers [Lim et al., 2021] have shown that interpretable attention improves both performance and practitioner trust in financial settings. SAE decomposition could reveal whether transformers trained on multi-asset portfolios compress regime indicators and cross-asset dependencies into superimposed directions, surfacing latent features that analysts could map to actionable risk factors.

Code Availability

The complete codebase for reproducing the experiments in this study is publicly available at <https://github.com/AlperYildirim1/TS-MechInterp>.

References

- Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermy, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, et al. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*, 2023. URL <https://transformer-circuits.pub/2023/monosemantic-features/index.html>.
- Lorenzo Brigato, Rafael Morand, Knut Strømme, Maria Panagiotou, Markus Schmidt, and Stavroula Mougiakakou. There are no champions in supervised long-term time series forecasting. *arXiv preprint arXiv:2502.14045*, 2026.
- Si-An Chen, Chun-Liang Li, Nate Yoder, Sercan O. Arik, and Tomas Pfister. TSMixer: An all-MLP architecture for time series forecasting. *Transactions on Machine Learning Research*, 2023.
- Hoagy Cunningham, Aidan Ewart, Logan Riggs, Robert Huben, and Lee Sharkey. Sparse autoencoders find highly interpretable linguistic features in language models. In *International Conference on Learning Representations (ICLR)*, 2024.
- Felix Divo, Maurice Kraus, Ruben Härle, Patrick Ahrend, and Kristian Kersting. Finding the zeitgeist in time series foundation models. In *ICLR 2026 Workshop on Time Series in the Age of Large Models (TSALM)*, 2026.
- Nelson Elhage, Tristan Hume, Catherine Olsson, Nicholas Schiefer, Tom Henighan, Shauna Kravec, Zac Hatfield-Dodds, Robert Lasenby, Dawn Drain, Carol Chen, et al. Toy models of superposition. *Transformer Circuits Thread*, 2022. URL https://transformer-circuits.pub/2022/toy_model/index.html.
- Thomas Heap, Tim Lawson, Lucy Farnik, and Laurence Aitchison. Sparse autoencoders can interpret randomly initialized transformers. *arXiv preprint arXiv:2501.17727*, 2025.
- Matīss Kalnāre, Sofoklis Kitharidis, Thomas Bäck, and Niki van Stein. Mechanistic interpretability for transformer-based time series classification. In *Communications in Computer and Information Science*. Springer, 2026.
- Taesung Kim, Jinhee Kim, Yunwon Tae, Cheonbok Park, Jang-Ho Choi, and Jaegul Choo. Reversible instance normalization for accurate time-series forecasting against distribution shift. In *International Conference on Learning Representations (ICLR)*, 2022.
- Guokun Lai, Wei-Cheng Chang, Yiming Yang, and Hanxiao Liu. Modeling long- and short-term temporal patterns with deep neural networks. In *The 41st International ACM SIGIR Conference on Research & Development in Information Retrieval*, pages 95–104, 2018.
- Bryan Lim, Sercan Ö. Arik, Nicolas Loeff, and Tomas Pfister. Temporal fusion transformers for interpretable multi-horizon time series forecasting. In *International Journal of Forecasting*, volume 37, pages 1748–1764, 2021.
- Yong Liu, Tengge Hu, Haoran Zhang, Haixu Wu, Shiyu Wang, Lintao Ma, and Mingsheng Long. iTransformer: Inverted transformers are effective for time series forecasting. In *International Conference on Learning Representations (ICLR)*, 2024.
- Anurag Mishra. Dissecting chronos: Sparse autoencoders reveal causal feature hierarchies in time series foundation models. *arXiv preprint arXiv:2603.10071*, 2026.
- Yuqi Nie, Nam H Nguyen, Phanwadee Sinthong, and Jayant Kalagnanam. A time series is worth 64 words: Long-term forecasting with transformers. In *International Conference on Learning Representations (ICLR)*, 2023.
- Jingcheng Niu, Wenjie Lu, and Gerald Penn. Does BERT rediscover a classical NLP pipeline? In *Proceedings of the 29th International Conference on Computational Linguistics (COLING)*, 2022.
- Mateusz Pach, Shyamgopal Karthik, Quentin Bouniot, Serge Belongie, and Zeynep Akata. Sparse autoencoders learn monosemantic features in vision-language models. *arXiv preprint arXiv:2504.02821*, 2025.

- Jianlin Su, Yu Lu, Shengfeng Pan, Ahmed Murtadha, Bo Wen, and Yunfeng Liu. RoFormer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568, 2024.
- Adly Templeton, Tom Conerly, Jonathan Marcus, Jack Lindsey, Trenton Bricken, Brian Chen, Adam Pearce, Craig Citro, Emmanuel Ameber, Andy Jones, et al. Scaling monosemanticity: Extracting interpretable features from Claude 3 Sonnet. *Transformer Circuits Thread*, 2024. URL <https://transformer-circuits.pub/2024/scaling-monosemanticity/index.html>.
- Ian Tenney, Dipanjan Das, and Ellie Pavlick. BERT rediscovers the classical NLP pipeline. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2019.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.
- Haixu Wu, Jiehui Xu, Jianmin Wang, and Mingsheng Long. Autoformer: Decomposition transformers with auto-correlation for long-term series forecasting. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.
- Haixu Wu, Tengge Hu, Yong Liu, Hang Zhou, Jianmin Wang, and Mingsheng Long. TimesNet: Temporal 2d-variation modeling for general time series analysis. In *International Conference on Learning Representations (ICLR)*, 2023.
- Zhijian Xu, Ailing Zeng, and Qiang Xu. FITS: Modeling time series with 10k parameters. In *International Conference on Learning Representations (ICLR)*, 2024. URL <https://openreview.net/forum?id=bWcnvZ3qMb>.
- Ailing Zeng, Muxi Chen, Lei Zhang, and Qiang Xu. Are transformers effective for time series forecasting? In *AAAI Conference on Artificial Intelligence*, 2023.
- Biao Zhang and Rico Sennrich. Root mean square layer normalization. *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.
- Haoyi Zhou, Shanghang Zhang, Jieqi Peng, Shuai Zhang, Jianxin Li, Hui Xiong, and Wancai Zhang. Informer: Beyond efficient transformer for long sequence time-series forecasting. In *AAAI Conference on Artificial Intelligence*, 2021.
- Tian Zhou, Ziqing Ma, Qingsong Wen, Xue Wang, Liang Sun, and Rong Jin. FEDformer: Frequency enhanced decomposed transformer for long-term series forecasting. In *International Conference on Machine Learning (ICML)*, 2022.

A Single-Layer Base Model Performance

Table 4 compares our single-layer model against the published PatchTST/42 results [Nie et al., 2023], which use 3 transformer layers together with extensive per-dataset tuning. On Weather and Electricity, the results are nearly identical, while on ETTm1 and ETTm2 the differences remain modest. Larger gaps appear on Traffic and ETTh2, likely reflecting the absence of dataset-specific tuning rather than a clear failure of shallow architectures. Notably, Traffic exhibits over 60% dead latents even at the larger $d_{\text{model}} = 96$ configuration used in our experiments, suggesting that increasing representational capacity alone does not substantially benefit this dataset.

Taken together, these results indicate that strong forecasting performance on standard benchmarks does not appear to require substantial transformer depth or highly specialized configurations.

Table 4: Forecasting performance comparison between our single-layer model (unified configuration, no per-dataset tuning) and the published PatchTST/42 [Nie et al., 2023] (3 layers, per-dataset tuning). Exchange is excluded as it was not evaluated in the original PatchTST paper.

Dataset	Horizon	PatchTST/42 [Nie et al., 2023]		Ours (1 Layer)	
		MSE	MAE	MSE	MAE
Weather	96	0.152	0.199	0.148	0.199
	192	0.197	0.243	0.193	0.244
	336	0.249	0.283	0.248	0.285
	720	0.320	0.335	0.322	0.338
Electricity	96	0.130	0.222	0.130	0.226
	192	0.148	0.240	0.149	0.242
	336	0.167	0.261	0.168	0.262
	720	0.202	0.291	0.205	0.296
Traffic	96	0.367	0.251	0.390	0.263
	192	0.385	0.259	0.417	0.293
	336	0.398	0.265	0.428	0.297
	720	0.434	0.287	0.457	0.310
ETTh1	96	0.375	0.399	0.378	0.398
	192	0.414	0.421	0.423	0.424
	336	0.431	0.436	0.452	0.446
	720	0.449	0.466	0.477	0.486
ETTh2	96	0.274	0.336	0.292	0.352
	192	0.339	0.379	0.356	0.392
	336	0.331	0.380	0.384	0.413
	720	0.379	0.422	0.409	0.440
ETTm1	96	0.290	0.342	0.307	0.350
	192	0.332	0.369	0.338	0.368
	336	0.366	0.392	0.366	0.393
	720	0.420	0.424	0.429	0.418
ETTm2	96	0.165	0.255	0.171	0.260
	192	0.220	0.292	0.227	0.298
	336	0.278	0.329	0.289	0.337
	720	0.367	0.385	0.371	0.395

A natural question is whether the modest performance gaps on datasets such as Traffic and ETTh2 reflect representational structure that our single-layer model fails to capture. While we cannot rule out that closing the final $\sim 2\%$ MSE gap might involve richer internal representations, including potentially superposition, the burden of this argument is considerable: it would require that superposition contributes nothing to the first 98% of performance and emerges only in the narrow margin between our model and the tuned baseline. We consider this unlikely, but emphasize that our claim does not depend on resolving this question. The demonstrated result — that competitive forecasting performance is achievable without detectable superposition — stands regardless.

B FFN Functional Validation

A prerequisite for interpreting SAE-based superposition analysis is confirming that the probed component performs meaningful computation. If the post-GELU FFN activations were functionally inert, the absence of superposition signatures would be trivially explained — one cannot find compressed features in a component that contributes nothing to the output. To rule this out, we perform a zero ablation: during inference, all post-GELU intermediate activations are replaced with zeros, effectively removing the FFN’s additive contribution to the residual stream while leaving the attention output and skip connection intact.

Table 5 reports the resulting forecasting degradation across all eight benchmarks and four prediction horizons. The FFN is clearly functionally active, with zero ablation producing substantial MSE increases in the majority of settings. The effect is most pronounced on the higher-dimensional datasets: Electricity exhibits degradation of +131.4% at $H=96$ and Traffic +40.3%, reflecting the greater computational load carried by their wider FFN layers ($d_{\text{ff}} = 256$ and 192 respectively). Weather shows a similar pattern, with +55.2% degradation at the shortest horizon. Even the narrow-dimensional ETT benchmarks ($d_{\text{ff}} = 32$) show consistent positive degradation in most configurations, typically ranging from +1% to +8%.

A small number of dataset-horizon pairs exhibit near-zero or slightly negative degradation, most notably Exchange at $H=192$ (-6.6%) and ETTh2 at $H=336$ and 720 (-0.9% , -0.7%). These cases suggest that for certain configurations, the FFN’s contribution is marginal or mildly harmful — consistent with our broader finding that these benchmarks do not demand substantial nonlinear feature composition. Importantly, even in these cases, the SAE analysis in Section 4 remains informative: the dictionary scaling and causal intervention results characterize whatever structure the FFN *does* encode, whether or not that structure is net-beneficial at every horizon.

Across the full set of 32 evaluations, 28 show positive degradation upon FFN removal, with a median degradation of $+6.8\%$. This confirms that the post-GELU hook is a suitable and informative site for SAE-based analysis: the representations being probed are, in the large majority of settings, functionally active, and the superposition findings reported in Section 4 reflect properties of a working component.

Table 5: FFN zero ablation: forecasting degradation when post-GELU activations are replaced with zeros during inference. The FFN is functionally active across the large majority of settings, with degradation most pronounced on higher-dimensional datasets.

Dataset	Horizon	Base MSE	Ablated MSE	Degradation (%)
Weather	96	0.1480	0.2297	+55.2
	192	0.1927	0.2365	+22.7
	336	0.2482	0.2656	+7.0
	720	0.3221	0.3599	+11.7
Electricity	96	0.1303	0.3015	+131.4
	192	0.1491	0.2708	+81.7
	336	0.1680	0.2540	+51.2
	720	0.2049	0.2569	+25.4
Traffic	96	0.3895	0.5465	+40.3
	192	0.4174	0.4754	+13.9
	336	0.4282	0.4806	+12.3
	720	0.4566	0.4793	+5.0
Exchange	96	0.0963	0.1099	+14.1
	192	0.1911	0.1785	-6.6
	336	0.3723	0.3801	+2.1
	720	0.9783	1.0428	+6.6
ETTh1	96	0.3779	0.4045	+7.0
	192	0.4230	0.4332	+2.4
	336	0.4524	0.4636	+2.5
	720	0.4774	0.4841	+1.4
ETTh2	96	0.2923	0.3132	+7.2
	192	0.3562	0.3587	+0.7
	336	0.3839	0.3803	-0.9
	720	0.4090	0.4063	-0.7
ETTm1	96	0.3070	0.3108	+1.2
	192	0.3384	0.3503	+3.5
	336	0.3655	0.3717	+1.7
	720	0.4288	0.4347	+1.4
ETTm2	96	0.1710	0.1770	+3.5
	192	0.2269	0.2458	+8.3
	336	0.2885	0.2938	+1.8
	720	0.3706	0.3712	+0.2