

Releases

[Core](#) [API](#) [CLI](#) [Bundler](#) [TAO](#) [WRY](#) [create-tauri-app](#)

[View releases on GitHub](#)

▼ 2.0.0-alpha.16

New Features

- [c085adda](#) (#8009) Added `set_progress_bar` to `Window`.
- [c1ec0f15](#) (#7933) Added `Window::set_always_on_bottom` and the `always_on_bottom` option when creating a window.
- [880266a7](#) (#8031) Bump the MSRV to 1.70.
- [ed32257d](#) (#7794) On Windows, add `Effect::Tabbed`, `Effect::TabbedDark` and `Effect::TabbedLight` effects.

Enhancements

- [46dcb941](#) (#8006) Include mobile on docs.rs targets.

What's Changed

- [fb10b879](#) (#8039) Added the `app` plugin back into core.
- [c9a9246c](#) (#8007) Added the `window` plugin back into core.

Dependencies

- Upgraded to `tauri-runtime@1.0.0-alpha.3`
- Upgraded to `tauri-runtime-wry@1.0.0-alpha.4`
- Upgraded to `tauri-utils@2.0.0-alpha.9`
- Upgraded to `tauri-build@2.0.0-alpha.10`
- Upgraded to `tauri-macros@2.0.0-alpha.9`

Breaking Changes

- [a63e71f9](#) (#7942) The initialization script for `Builder::invoke_system` now must initialize the `window.__TAURI_INTERNALS__.postMessage` function instead of `window.__TAURI_POST_MESSAGE__`.
- [12b8d18b](#) (#7875) - Removed `tauri::path::Error` and added its variants to `tauri::Error`
 - Removed `tauri::path::Result` and `tauri::plugin::Result` aliases, you should use `tauri::Result` or your own `Result` type.

- [8b166e9b](#) (#7949) Changed `TAURI_AUTOMATION` to `TAURI_WEBVIEW_AUTOMATION`
- [2558fab8](#) (#7939) This release contains a number of breaking changes to improve the consistency of tauri internals and the public facing APIs and simplifying the types where applicable:
 - Removed `EventHandler` type.
 - Added `EventId` type
 - Changed `Manager::listen_global` and `Window::listen` to return the new `EventId` type instead of `EventHandler`.
 - Removed the return type of `Manager::once_global` and `Window::once`
 - Changed `Manager::unlisten` and `Window::unlisten` to take the new `EventId` type.
 - Added `tauri::scope::ScopeEventId`
 - Changed `FsScope::listen` to return the new `ScopeEventId` instead of `Uuid`.
 - Added `FsScope::unlisten`

► **2.0.0-alpha.15**

► **2.0.0-alpha.14**

► **2.0.0-alpha.13**

► **2.0.0-alpha.12**

► **2.0.0-alpha.11**

► **2.0.0-alpha.10**

► **2.0.0-alpha.9**

► **2.0.0-alpha.8**

► **2.0.0-alpha.7**

► **2.0.0-alpha.6**

► **2.0.0-alpha.5**

► **2.0.0-alpha.4**

► **2.0.0-alpha.3**

► **2.0.0-alpha.2**

► **2.0.0-alpha.1**

► **2.0.0-alpha.0**

► **1.5.2**

► **1.5.1**

► **1.5.0**

► **1.4.1**

► **1.4.0**

► **1.3.0**

► **1.2.5**

- ▶ **1.2.4**
- ▶ **1.2.3**
- ▶ **1.2.2**
- ▶ **1.2.1**
- ▶ **1.2.0**
- ▶ **1.1.4**
- ▶ **1.1.3**
- ▶ **1.1.2**
- ▶ **1.1.1**
- ▶ **1.1.0**
- ▶ **1.0.9**
- ▶ **1.0.8**
- ▶ **1.0.7**
- ▶ **1.0.6**
- ▶ **1.0.5**
- ▶ **1.0.4**
- ▶ **1.0.3**
- ▶ **1.0.2**
- ▶ **1.0.1**
- ▶ **1.0.0**
- ▶ **1.0.0-rc.17**
- ▶ **1.0.0-rc.16**
- ▶ **1.0.0-rc.15**
- ▶ **1.0.0-rc.14**
- ▶ **1.0.0-rc.13**
- ▶ **1.0.0-rc.12**
- ▶ **1.0.0-rc.11**
- ▶ **1.0.0-rc.10**
- ▶ **1.0.0-rc.9**
- ▶ **1.0.0-rc.8**
- ▶ **1.0.0-rc.7**
- ▶ **1.0.0-rc.6**
- ▶ **1.0.0-rc.5**
- ▶ **1.0.0-rc.4**
- ▶ **1.0.0-rc.3**

- ▶ **1.0.0-rc.2**
- ▶ **1.0.0-rc.1**
- ▶ **1.0.0-rc.0**
- ▶ **1.0.0-beta.8**
- ▶ **1.0.0-beta.7**
- ▶ **1.0.0-beta.6**
- ▶ **1.0.0-beta.5**
- ▶ **1.0.0-beta.4**
- ▶ **1.0.0-beta.3**
- ▶ **1.0.0-beta.2**
- ▶ **1.0.0-beta.1**
- ▶ **1.0.0-beta.0**
- ▶ **1.0.0-beta-rc.4**
- ▶ **1.0.0-beta-rc.3**
- ▶ **1.0.0-beta-rc.2**
- ▶ **1.0.0-beta-rc.1**
- ▶ **1.0.0-beta-rc.0**
- ▶ **0.11.1**
- ▶ **0.11.0**
- ▶ **0.10.0**
- ▶ **0.9.2**
- ▶ **0.9.1**
- ▶ **0.9.0**
- ▶ **0.8.0**
- ▶ **0.7.5**
- ▶ **0.7.4**
- ▶ **0.7.3**
- ▶ **0.7.2**
- ▶ **0.7.1**
- ▶ **0.7.0**
- ▶ **0.6.2**
- ▶ **0.6.0**