




Map Reduce on YARN Overview

Originals of Slides and Source Code for Examples:

<http://www.coreservlets.com/hadoop-tutorial/>

Customized Java EE Training: <http://courses.coreservlets.com/>

Hadoop, Java, JSF 2, PrimeFaces, Servlets, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Android.
Developed and taught by well-known author and developer. At public venues or onsite at *your* location.



For live Hadoop training, please see courses at <http://courses.coreservlets.com/>.

Taught by the author of this Hadoop tutorial. Available at public venues, or customized versions can be held on-site at your organization.

- Courses developed and taught by Marty Hall
 - JSF 2, PrimeFaces, servlets/JSP, Ajax, jQuery, Android development, Java 6 or 7 programming, custom mix of topics
 - Ajax courses can concentrate on 1 library (jQuery, Prototype/Scriptaculous, Ext-JS, Dojo, etc.) or survey several
 - Courses developed and taught by coreservlets.com experts (edited by Marty)
 - **Hadoop**, Spring, Hibernate/JPA, GWT, SOAP-based and RESTful Web Services
- Contact hall@coreservlets.com for details**

Agenda

- **MapReduce Introduction**
- **MapReduce Model**
- **YARN and MapReduce 2.0 Daemons**
- **MapReduce on YARN single node installation**
- **MapReduce and YARN command line tools**


4

Hadoop MapReduce

- **Model for processing large amounts of data in parallel**
 - On commodity hardware
 - Lots of nodes
- **Derived from functional programming**
 - Map and reduce functions
- **Can be implemented in multiple languages**
 - Java, C++, Ruby, Python (etc...)

5

Hadoop MapReduce History




6

MapReduce Model

- **Imposes key-value input/output**
- **Defines map and reduce functions**
 $\text{map: } (K1, V1) \rightarrow \text{list } (K2, V2)$
 $\text{reduce: } (K2, \text{list}(V2)) \rightarrow \text{list } (K3, V3)$
 1. Map function is applied to every input key-value pair
 2. Map function generates intermediate key-value pairs
 3. Intermediate key-values are sorted and grouped by key
 4. Reduce is applied to sorted and grouped intermediate key-values
 5. Reduce emits result key-values

7

MapReduce Model/Framework



8

Source: Jimmy Lin, Chris Dyer. *Data-Intensive Text Processing with MapReduce*. Morgan & Claypool. 2010.

MapReduce Framework

- **Takes care of distributed processing and coordination**
- **Scheduling**
 - Jobs are broken down into smaller chunks called tasks. These tasks are scheduled
- **Task Localization with Data**
 - Framework strives to place tasks on the nodes that host the segment of data to be processed by that specific task
 - Code is moved to where the data is

9

Source: Jimmy Lin, Chris Dyer. *Data-Intensive Text Processing with MapReduce*. Morgan & Claypool. 2010.

MapReduce Framework

- **Error Handling**
 - Failures are an expected behavior so tasks are automatically re-tried on other machines
- **Data Synchronization**
 - Shuffle and Sort barrier re-arranges and moves data between machines
 - Input and output are coordinated by the framework

10

Map Reduce 2.0 on YARN

- **Yet Another Resource Negotiator (YARN)**
- **Various applications can run on YARN**
 - MapReduce is just one choice (the main choice at this point)
 - <http://wiki.apache.org/hadoop/PoweredByYarn>
- **YARN was designed to address issues with MapReduce1**
 - Scalability issues (max ~4,000 machines)
 - Inflexible Resource Management
 - MapReduce1 had slot based model

11

MapReduce1 vs. YARN

- **MapReduce1 runs on top of JobTracker and TaskTracker daemons**
 - JobTracker schedules tasks, matches task with TaskTrackers
 - JobTracker manages MapReduce Jobs, monitors progress
 - JobTracker recovers from errors, restarts failed and slow tasks
- **MapReduce1 has inflexible slot-based memory management model**
 - Each TaskTracker is configured at start-up to have N slots
 - A task is executed in a single slot
 - Slots are configured with maximum memory on cluster start-up
 - The model is likely to cause over and under utilization issues

12

MapReduce1 vs. YARN

- **YARN addresses shortcomings of MapReduce1**
 - JobTracker is split into 2 daemons
 - ResourceManager - administers resources on the cluster
 - ApplicationMaster - manages applications such as MapReduce
 - Fine-Grained memory management model
 - ApplicationMaster requests resources by asking for “containers” with a certain memory limit (ex 2G)
 - YARN administers these containers and enforces memory usage
 - Each Application/Job has control of how much memory to request

13

Daemons

- **YARN Daemons**


- Node Manager
 - Manages resources of a single node
 - There is one instance per node in the cluster
- Resource Manager
 - Manages Resources for a Cluster
 - Instructs Node Manager to allocate resources
 - Application negotiates for resources with Resource Manager
 - There is only one instance of Resource Manager

- **MapReduce Specific Daemon**

- MapReduce History Server
 - Archives Jobs' metrics and meta-data

14

Sample YARN Daemons Deployments with HDFS and HBase



15

Old vs. New Java API

- There are two flavors of MapReduce API which became known as Old and New
- Old API classes reside under
 - org.apache.hadoop.mapred
- New API classes can be found under
 - org.apache.hadoop.mapreduce
 - org.apache.hadoop.mapreduce.lib
- We will use new API exclusively
- New API was re-designed for easier evolution
- Early Hadoop versions deprecated old API but recently deprecation was removed
- Do not mix new and old API

16

YARN with MapReduce 2.0 Installation

- **Single Node Installation**
 - Mimics Fully-Distributed Cluster but runs on just one host
 - Good for testing, debugging and prototyping
 - Not production use or performance benchmarking!
 - Used in this class
- **Cluster**
 - Run YARN on many nodes
 - Great for production and development clusters

17

Set Up Pseudo-Distributed Mode

- 1. Verify Prerequisites**
 - Java, SSH, etc...
- 2. Configure YARN**
 - Settings inside of yarn-site.xml and yarn-env.sh
- 3. Configure MapReduce**
 - Settings inside of mapred-site.xml
- 4. Start YARN and MapReduce History Server**

18

1: Verify Prerequisites

- **Java version 6+**
 - It is written in Java after all
 - Oracle JDK is the most popular
- **Linux is the only production platform**
- **Supports all other Operating Systems for development**
 - Windows, OS X
 - Cygwin is required for Windows development
- **Password-less SSH is setup**
 - Already had to do this for HDFS



19

2: Configure YARN

- **Configuration Files are discovered by looking in the directory specified in YARN_CONF_DIR environment property**
 - `export YARN_CONF_DIR=$HADOOP_CONF_DIR`

20

2: Configure YARN

Config File	Description
yarn-env.sh	A bash script where YARN environment variables are specified. For example, configure log directory here.
yarn-site.xml	Hadoop configuration file where majority of properties are specified for YARN daemons. Configures Resource Manager, Node Manager and History Server.
slaves	A list of nodes where Node Manager daemons are started; one host per line.
mapred-site.xml	MapReduce specific properties go here. This is the application specific configuration file; an application is MapReduce in this case.

Note: YARN will also utilize core-site.xml and hadoop-env.sh which were covered in HDFS lecture

21

2: Configure YARN - yarn-env.sh

- **Bash Script executed by YARN start script**
- **Sets things like daemons'**
 - heap size
 - log location(s)
 - pid file locations
 - etc...

```
export YARN_LOG_DIR=/home/hadoop/Training/logs/yarn
export YARN_PID_DIR=$TRAINING_HOME/hadoop_work/pids
```

22

2: Configure YARN - yarn-site.xml

- **Configure host and ports for daemons, data output locations, auxiliary services, security, etc....**
 - Configure hosts and ports for Resource Manager, Node Manager and MapReduce History Server
 - Configure local storage directories for Node Managers
 - Configure any application specific services

23

2: Configure YARN - yarn-site.xml

```
<property>
  <name>yarn.resourcemanager.address</name>
  <value>localhost:10040</value>
  <description>In Server specified the port that Resource
Manager will run on. In client is used for connecting to
Resource Manager</description>
</property>

<property>
  <name>yarn.resourcemanager.resource-tracker.address</name>
  <value>localhost:8025</value>
  <description>Utilized by Node Manager for communication
with Resource Manager</description>
</property>
```

24

2: Configure YARN - yarn-site.xml

```
<property>
  <name>yarn.resourcemanager.scheduler.address</name>
  <value>localhost:8030</value>
  <description>Utilized by Application Masters to
communicate with Resource Manager; in our case for
MRAppMaster (MapReduce Application Master) to communicate
with Resource Manager</description>
</property>

<property>
  <name>yarn.resourcemanager.admin.address</name>
  <value>localhost:8141</value>
  <description>Utilized by administrative clients ($yarn
rmadmin) to communicate with Resource Manager</description>
</property>
```

25

2: Configure YARN - yarn-site.xml

```
<property>
  <name>yarn.nodemanager.local-dirs</name>
  <value>/home/hadoop/Training/hadoop_work/mapred/nodemanager</value>
  <final>true</final>
  <description>Comma separated list of directories, where
local data is persisted by Node Manager</description>
</property>

<property>
  <name>yarn.nodemanager.aux-services</name>
  <value>mapreduce.shuffle</value>
  <description>Long running service which executes on Node
Manager(s) and provides MapReduce Sort and Shuffle
functionality.</description>
</property>
```

26

2: Configure YARN - yarn-site.xml

```
<property>
  <name>yarn.log-aggregation-enable</name>
  <value>true</value>
  <description>Enable log aggregation so application logs are
moved onto hdfs and are viewable via web UI after the
application completed. The default location on hdfs is '/log'
and can be changed via yarn.nodemanager.remote-app-log-dir
property</description>
</property>

<property>
  <name>hadoop.security.authorization</name>
  <value>>false</value>
  <description>Disable authorization for development and
clusters that do not require security</description>
</property>
```

27

3: Configure MapReduce - mapred-site.xml

```
<configuration>
  <property>
    <name>mapreduce.cluster.temp.dir</name>
    <value>/home/hadoop/Training/hadoop_work/mapred/temp</value>
    <final>true</final>
  </property>

  <property>
    <name>mapreduce.cluster.local.dir</name>
    <value>/home/hadoop/Training/hadoop_work/mapred/local</value>
    <final>true</final>
  </property>

  <property>
    <name>mapreduce.framework.name</name>
    <value>yarn</value>
    <description>Use YARN as the servicer of MapReduce, if
not specified Local Job Runner is used</description>
  </property>
</configuration>
```

28

4: Start YARN and MapReduce History Server

```
$ cd $HADOOP_HOME/sbin
$ ./start-yarn.sh
$ ./mr-jobhistory-daemon.sh start historyserver
```

- **start-yarn.sh script starts all the YARN related daemons on the cluster**
 - Resource Manager is started on the machine that start-yarn.sh script is executed on
 - Delegates to \$yarn-daemon.sh start resourcemanager
 - Node Manager is started for each machine specified in the <YARN_CONF_DIR>/slaves
 - Delegates to \$yarn-daemon.sh start nodemanager

29

YARN Web-UI

- **Resource Manager Web-UI**
 - Cluster resource usage, job scheduling, and current running jobs
 - Runs on port 8088 by default
- **Application Proxy Web-UI**
 - Provides information about the current job
 - Runs as a part of Resource Manager Web-UI by default
 - After completion, jobs get exposed by History Server
- **Node Manager Web-UI**
 - Single Node information and current containers being executed
 - Runs on port 8042 by default
- **MapReduce History Server Web-UI**
 - Provides history and details of past MapReduce jobs
 - Runs on port 19888 by default

30

MapReduce 2.0 Web-UI

The screenshot displays the Hadoop MapReduce 2.0 Web-UI interface. The top navigation bar includes the Hadoop logo and the title 'All Applications'. The main content area is divided into two sections: 'Cluster Metrics' and 'JobHistory'.

Cluster Metrics:

Apps Submitted	Apps Pending	Apps Running	Apps Completed	Containers Running	Memory Used	Memory Total	Memory Reserved	Active Nodes	Decommissioned Nodes	Lost Nodes	Unhealthy Nodes	Rebooted Nodes
2	0	1	1	3	3.5 GB	8 GB	0 KB	1	0	0	0	0

JobHistory:

Start Time	Finish Time	Job ID	Name	User	Queue	State	Maps Total	Maps Completed	Reducers Total	Reducers Completed
2012-06-15 23:27:48 EDT	2012-06-15 23:28:06 EDT	job_1339817050993_0001	StartsWithCount-HBase	hadoop	default	SUCCEEDED	2	2	1	1
2012-06-16 01:07:01 EDT	2012-06-16 01:07:22 EDT	job_1339817050993_0002	StartsWithCount	hadoop	default	FAILED	0	0	0	0
2012-06-16 01:09:48 EDT	2012-06-16 01:10:08 EDT	job_1339817050993_0003	StartsWithCount	hadoop	default	FAILED	0	0	0	0
2012-06-16 01:12:54 EDT	2012-06-16 01:13:14 EDT	job_1339817050993_0004	StartsWithCount	hadoop	default	FAILED	0	0	0	0
2012-06-16 01:15:55 EDT	2012-06-16 01:16:09 EDT	job_1339817050993_0005	StartsWithCount	hadoop	default	SUCCEEDED	1	1	1	1
2012-06-16 01:18:23 EDT	2012-06-16 01:18:43 EDT	job_1339817050993_0006	StartsWithCount	hadoop	default	FAILED	0	0	0	0
2012-06-16 01:19:04 EDT	2012-06-16 01:19:25 EDT	job_1339817050993_0007	StartsWithCount	hadoop	default	FAILED	0	0	0	0
2012-06-16 01:20:13 EDT	2012-06-16 01:20:44 EDT	job_1339817050993_0008	StartsWithCount	hadoop	default	SUCCEEDED	1	1	1	1

31

Command Line Tools

- **<hadoop_install>/bin/yarn**
 - Execute code with a jar
 - \$yarn jar jarFile [mainClass] args...
 - Print out CLASSPATH: \$yarn classpath
 - Resource Manager admin: \$yarn rmadmin
- **<hadoop_install>/bin/mapred**
 - \$mapred job
 - Get information about jobs
 - Kill Jobs

32

\$ yarn jar jarFile [mainClass] args...

- **Execute code in the provided jar**

```
$ yarn jar
$HADOOP_HOME/share/hadoop/mapreduce/hadoop-
mapreduce-examples-2.0.0-cdh4.0.0.jar pi 5 5
```

Examples jar files shipped with hadoop

pi is the program that computes pi

Specify number of mappers

Number of samples; artifact of pi application

33

\$ yarn radmin

- **Runs ResourceManager admin client**
- **Allows to refresh and clear resources**

```
$ yarn radmin -refreshNodes
```

Resource Manager will refresh its information
about all the Node Managers

34

\$mapred job

- **Command line interface to view job's attributes**
- **Most of the information is available on Web-UI**

```
$ mapred job -list
```


List Jobs that are currently running

```
$ mapred job -status job_1340417316008_0001
```

Retrieve job's status by Job ID

35

Resources: Books



Hadoop: The Definitive Guide


Tom White (Author)

O'Reilly Media; 3rd Edition (May 6, 2012)

Hadoop in Action

Chuck Lam (Author)

Manning Publications; 1st Edition (December, 2010)



MapReduce Design Patterns

Donald Miner (Author), Adam Shook (Author)

O'Reilly Media (November 22, 2012)

36

Resources: Books



HBase: The Definitive Guide


Lars George (Author)

O'Reilly Media; 1 edition (September 20, 2011)

Hadoop Operations

Eric Sammer (Author)

O'Reilly Media (October 22, 2012)



Data-Intensive Text Processing with MapReduce


Jimmy Lin and Chris Dyer (Authors) (April, 2010)

Download for FREE:

<http://lintool.github.com/MapReduceAlgorithms/index.html>

37

Resources: Books



Hadoop in Practice

Alex Holmes (Author)

Manning Publications; (October 10, 2012)

Resources

- **Home Page**
 - <http://hadoop.apache.org>
- **Mailing Lists**
 - http://hadoop.apache.org/mailling_lists.html
- **Wiki**
 - <http://wiki.apache.org/hadoop>
- **Documentation:**
 - <http://hadoop.apache.org/docs/r2.0.2-alpha>



Wrap-Up

Customized Java EE Training: <http://courses.coreservlets.com/>

Hadoop, Java, JSF 2, PrimeFaces, Servlets, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Android.
Developed and taught by well-known author and developer. At public venues or onsite at *your* location.

Summary

- **We learned about**
 - MapReduce Model
 - YARN/MapReduce 2.0 Daemons
 - MapReduce on YARN single node installation
 - MapReduce and YARN command line tools



Questions?

[JSF 2, PrimeFaces, Java 7, Ajax, jQuery, Hadoop, RESTful Web Services, Android, Spring, Hibernate, Servlets, JSP, GWT, and other Java EE training.](#)

Customized Java EE Training: <http://courses.coreservlets.com/>

Hadoop, Java, JSF 2, PrimeFaces, Servlets, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Android.
Developed and taught by well-known author and developer. At public venues or onsite at *your* location.