



UNIVERSITÀ
DEGLI STUDI DI BARI
ALDO MORO



DIPARTIMENTO
DI INFORMATICA



Big Data analytics for knowledge transfer among organisms while reconstructing Gene Regulatory Networks

Paolo Mignone (1,2), Gianvito Pio (1,2)
Domenica D'Elia (3), Michelangelo Ceci (1,2,4)

1 Department of Computer Science, University of Bari Aldo Moro, Bari 70125, Italy


2 National Interuniversity Consortium for Informatics (CINI), Roma 00185, Italy

3 CNR - Institute for Biomedical Technologies, Bari 70126, Italy

4 Department of Knowledge Technologies, Jozef Stefan Institute, Ljubljana 1000, Slovenia

The EMBnet logo is displayed in a large, white, stylized font with a blue outline, set against a dark blue curved background that occupies the bottom right portion of the slide.

Reconstruction of Gene Regulatory Networks




- A gene (or genetic) regulatory network (GRN) is a collection of molecular regulators that interact with each other and with other substances in the cell to govern the gene expression levels of mRNA and proteins
- When some control mechanisms are compromised, cells undergo a series of modifications that can bring to their transformation in **cancerous cells**

Motivations


- Support biologists in the identification of new gene interactions for the better **understanding of diseases** related to gene network functions
- Existing methods suffer the limited number of **labelled examples** (i.e., validated interactions) and the absence of **negative examples** (i.e., confirmed absent interactions)

Goal

- Reconstructing the **Human Gene Network** using information from the **Mouse Gene Network** (via transfer learning)



Mouse «source domain»




Human «target domain»

The problem from a data mining perspective




- **Nodes:** genes
- **Edges:** gene interactions
- **Task:** gene network reconstruction via link prediction
- **Binary classification:**
 - ✓ – the link exists – **POSITIVE LABEL**
 - ✗ – the link does not exist – **NEGATIVE LABEL**
- **Training set:**
 - ✓ – known existing links (ground truth)
 - ? – no information about non-existing links
 - positive-unlabelled learning setting

Proposed Method



Gene Network Reconstruction
solved as a
Link Prediction Task
supported by
Transfer Learning
in a
Positive-Unlabelled Learning Setting

Stage 1 – Clustering




- **Clustering algorithm** on positive (i.e., validated) interactions on both the domains, separately, to obtain n and m clusters respectively

Stage 1 – Why clustering?

- 1) to distinguish the possible various concepts underlying the notion of **positive interaction**
- 2) to summarize the concept of positive interactions to simplify the weighting phase
 - computational **effort reduced** when computing distances between unlabelled instances and centroids w.r.t. to compare them to all the positive examples


Stage 2 – Weighting



- Weighting of unlabelled interactions of the **source domain S** and the **target domain T** according to their distance with respect to the centroids


Stage 3 – Training

- Training of a classifier (SVM-based) that is **able to exploit weights** on the instances: **Weighted SVM (WSVM)**



Stage 3 – Training

- Training of two different WSVM classifiers for the source and the target domains separately
- **WSVM source domain model**
- **WSVM target domain model**



Stage 4 – Model Combination



- Compute the **bisector hyperplane**
- Perform a hyperplane combination based on data driven coefficient substitutions

- **Input:**

- source coefficients
- target coefficients
- bisector coefficients

- **Output:**

- new combined hyperplane



Experiments

- Gene interactions dataset



	Positive*	Unlabelled**
<i>Mouse (source)</i>	14613	235706
<i>Human (target)</i>	235706	235706

*BIOGRID - <https://thebiogrid.org/>

** Gene Expression Omnibus - <https://www.ncbi.nlm.nih.gov/geo/>

Experiments

- Gene representation

Features: average gene expression levels measured for specific tissues in **control samples**



e_1



e_2



e_3



e_4



e_5




e_6

$$e_i \in [0,1]$$

Experiments

- Gene interaction representation



Experiments

We compared our method, indicated as **BioSfer** in the results, with two baselines:

- **no_transfer**: WSVM with Platt scaling, learned only from the target network (i.e., from the human gene network). Allows us to evaluate the **contribution of the source domain**
- **union**: WSVM with Platt scaling, learned from a single dataset consisting of the union of the instances coming from both mouse and human. Allows us to evaluate the **effect of our weighting strategy**

Experiments

Transfer Learning Competitors

- **JGSA** hang, J., Li, W., and Ogunbona, P. (2017). Joint geometrical and statistical alignment for visual domain adaptation. Proceedings - 30th IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017.
- **BDA** Wang, J., Chen, Y., Hao, S., Feng, W., and Shen, Z. (2017). Balanced distribution adaptation for transfer learning. In ICDM 2017
- **TJM** Long, M., Wang, J., Ding, G., Sun, J., and Yu, P. S. (2014). Transfer joint matching for unsupervised domain adaptation. In CVPR 2014


Gene Regulatory Network Reconstruction Competitor

- **GENIE3** Vân Anh Huynh-Thu, Alexandre Irrthum, Louis Wehenkel, Pierre Geurts. Inferring Regulatory Networks from Expression Data Using Tree-Based Methods. In PLOS ONE September 28, 2010, <https://doi.org/10.1371/journal.pone.0012776>

Experimental Setting

- Evaluation measures:
 - Recall@k
 - Area Under Recall@K curve (AUR@K)
 - Area Under ROC curve (AUROC)
 - Area Under Precision Recall curve (AUPR)
- Clustering setting: $k_s, k_t \in \{2, 3, 4\}$
- 10 fold cross-validation


Results



— BioSfer
- - union

Results

Comparison between **BioSfer** and competitors with the **best configuration**



Qualitative Analysis

- Top-1 Ranked Predicted Interaction: **NBPF8P - ND4**, score: 0.948
- Top-2 Ranked Predicted Interaction: **LINC00657 - RPL39**, score: 0.945
- Not identified by **g:Profiler** (<https://biit.cs.ut.ee/gprofiler/gost>)

NBPF8P - ND4

Since the correlation between the **impaired mitochondrial respiratory chain** function and the pathogenesis of several **neurological diseases** is well-known [A], the prediction provided by BioSfer is **biologically reasonable**

LINC00657 - RPL3

The relationship between these two genes is plausible because of the recent discovery of the existence of **ribosome-associated non-coding RNAs (rancRNAs)**. Ribosomes can be the target for numerous small and long non-coding RNAs in various organisms [B]

[A] R. K. Chaturvedi and M. F. Beal. **Mitochondrial diseases of the brain**. Free Radical Biology and Medicine, 63:1–29, oct 2013.

[B] A. Pircher, J. Gebetsberger, and N. Polacek. **Ribosome-associated ncRNAs: An emerging class of translation regulators**. RNA Biology, 11(11):1335–1339, nov 2014.

Conclusion

- The knowledge about the mouse gene network is helpful to **better reconstruct** the human gene network
- BioSfer is able to exploit the information of unlabelled gene pairs in order to better identify a set of **existing gene interactions**

Future Works

- **Multiple source networks** for the reconstruction of the target network



UNIVERSITÀ
DEGLI STUDI DI BARI
ALDO MORO



DIPARTIMENTO
DI INFORMATICA



Thanks for your attention
