

EE 547 (PMP) Lab 3

Wednesday, January 21, 2015

Professor Linda Bushnell, UW EE

Demo Problem 1 (Matrix Exponential of an LTI Systems) Given a square matrix A as (1). Please write a MATLAB script to :

$$A = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 2 & 2 & 0 & 0 \\ 0 & 0 & 3 & 3 \\ 0 & 0 & 0 & 4 \end{bmatrix} \quad (1)$$

- (a) Compute the determinant of matrix A, define matrix (sI-A) and find (sI-A)⁻¹.
- (b) Compute matrix exponential e^{At}. (Hint: expm)
- (c) Repeat step (b) by using inverse Laplace transform of (sI-A)⁻¹. (Hint: ilaplace)
- (d) Compute the characteristic polynomial and eigenvalues of matrix A.
- (e) Evaluate and plot diagonal terms of e^{At}.

Individual Problem 1 Consider a system as (2) with initial condition x₁(0) = 1 and x₂(0) = 0.5.

$$\dot{x} = \begin{bmatrix} 0 & -2 \\ 2 & -4 \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} \quad (2)$$

- (a) The solution of this system is of a unique form: x = e^{At}x(0). As you learned in the lecture, matrix exponential is the state transition matrix. Please compute e^{At} by appropriate functions.
- (b) Please derive the eigenvalues and characteristic polynomial of this matrix A by MATLAB script.
- (c) Please evaluate and plot x₁(t) and x₂(t). The tspan is set as [0:0.01:5].
(Hint: use functions **eval** and **subs** to evaluate a function with symbol.)

Now consider system (3) with an impulse input.

$$\begin{aligned} \dot{x} &= \begin{bmatrix} 0 & -2 \\ 2 & -4 \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} + \begin{bmatrix} 1 \\ -2 \end{bmatrix} \delta(t) \\ y &= \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} \end{aligned} \quad (3)$$

- (d) Please use **impulse** function and the method we learned in step (c) to plot system's output. (Note: **impulse** function in MATLAB assumes zero initial state values)

Solution to Demo Problem 1:

(a) Initial set up:

i. Define parameters and symbols

syms s

syms t

ii. Define A matrix

(b) Compute the determinant of matrix A and find $(sI-A)^{-1}$.

detA = det(A)

ChaMatrix = inv(s*eye(size(A))-A);

(c) Compute matrix exponential e^{At} .

expAt = expm(A*t)

(d) Inverse Laplace transform of $(sI-A)^{-1}$.

DexpAt = ilaplace(ChaMatrix,s,t)

(e) Derive characteristic polynomial and eigenvalues of matrix A

ChaPoly = poly(A);

This returns the coefficients of characteristic polynomial in descending power.

[V,D]=eig(A);

This returns eigenvectors as column vector of matrix V. D is a diagonal matrix with diagonal terms as eigenvalues.

(f) Evaluate and plot diagonal terms of e^{At} .

eval(subs(expAt(1,1),t,tspan))

Since e^{At} is a matrix, the element to be plotted has to be defined clearly. **subs** is to replace symbol t with the values defined in tspan. Please note after **subs**, the class of output is *sym*, not *double*. **eval** is to return the function output in terms of *double*.

(g) The specific outputs are plotted in Figure 1.




Figure 1 Diagonal terms of e^{At} . Please note e^{At} is a 4 by 4 matrix in this case.

MATLAB Code:

```
%% Lab 3: Matrix exponential and inverse Laplace transformation
%% Developer: HRLin

close all;
clear all;
clc;
%% Define parameters for individual problem
tspan = 0:0.01:1;
syms s; % to create symbole s for Laplace transform
syms t; % to create symbole t for time

%% Define A matrix
A = [1 0 0 0; 2 2 0 0; 0 0 3 3; 0 0 0 4]

%% MATLAB function practice
detA = det(A); % determinant of matrix A

ChaMatrix = inv(s*eye(size(A))-A);

expAt = expm(A*t); %calculate exponential of matrix At

DexpAt = ilaplace(ChaMatrix,s,t); %derive exp(At) by inverse Laplace

ChaPoly = poly(A);

[V,D] = eig(A);
%% Define input
u = cos(tspan);

%% Output Figures

figure(1)
plot(tspan,eval(subs(expAt(1,1),t,tspan)),tspan,eval(subs(expAt(2,2),t,tspan)
)...

,tspan,eval(subs(expAt(3,3),t,tspan)),tspan,eval(subs(expAt(4,4),t,tspan)))
title('e^A^t');
xlabel ('Time (second)');
legend('e^A^t(1,1)', 'e^A^t(2,2)', 'e^A^t(3,3)', 'e^A^t(4,4)')
print -djpeg 'e^(At).jpeg'
```