

Mandelbrot Fractal Neural Synthesis: Zero-Storage Procedural Weight Derivation and Non-Linear Decision Boundaries

Volkan Dağlı^{1,2,*}

Zerrin Dağlı³

Dağhan Dağlı⁴

¹Anadolu University, Eskişehir, Turkey • ²ITouch Systems, Mersin, Turkey • ORCID: 0009-0000-1587-8703

³Mersin University, Mersin, Turkey • ORCID: 0000-0001-9490-6425 • ⁴Toros Science College, Mersin, Turkey • ORCID: 0009-0003-2492-8313

• GitHub: @Lexovian

*Corresponding Author. Under review in *Chaos, Solitons & Fractals* (Elsevier Q1). Correspondence: github.com/pCwOrM/mandelbrot-fractal-neural-synthesis •

September 2026

Abstract—Modern deep learning architectures store billions or trillions of parameters as independent floating-point scalars across dense tensor arrays, trained via stochastic gradient descent. While remarkably capable, this paradigm incurs immense storage requirements, memory bandwidth bottlenecks (the "memory wall"), and high carbon costs. In this paper, we propose and empirically validate an alternative weight generation paradigm: deriving synaptic weights and threshold biases procedurally from the non-linear visual morphology of the Mandelbrot fractal set (f_M). By specifying a 3-parameter coordinate tuple $\Theta = (c_x, c_y, \text{zoom})$ in the complex plane, a 128×128 pixel patch is sampled via the quadratic escape recurrence $z_{n+1} = z_n^2 + c$. We introduce a *4-Quadrant Partitioning* method that maps the non-escaping "dark area" (convergent pixel ratio) of four sub-quadrants directly to synaptic weights (w_1, w_2, w_3) and neuron bias (b). Our results show that: (1) a 128×128 grid represents an optimal Pareto trade-off, matching the convergence precision of 256×256 within $\pm 0.08\%$ while evaluating 15 times faster (~ 15.6 ms); (2) all linearly separable boolean logic gates (AND, OR, NAND, NOR) are solved with 100% classification accuracy; (3) the non-linearly separable XOR problem is resolved with 100% accuracy using a two-layer composite fractal network; and (4) functional decision units require zero persistent weight tensors, retaining only 24 bytes of coordinate metadata (three Float64 values), representing a $>99.99999998\%$ storage reduction relative to conventional tensor arrays. Finally, we formulate the "Escape Horizon Principle" linking fractal boundary sharpness to error-driven motor learning in biological systems, and outline prospective implementations on analog optical/photonic processors.

Keywords: Fractal Neural Synthesis, Mandelbrot Set, Procedural Weight Generation, Zero-Storage AI, Non-Linear Decision Boundaries, Escape Horizon, HyperNEAT, Optical Computing.

Özet (Extended Turkish Abstract)—Bu çalışma, derin öğrenme modellerinde milyonlarca parametreyi bellek çiplerinde statik tensörler olarak saklamak yerine, deterministik kaos ve fraktal geometrinin temeli olan Mandelbrot kümesinden ($z = z^2 + c$) anında canlı türeten yeni bir yapay zeka paradigmasını teorik ve deneysel olarak kanıtlamaktadır. Karmaşık düzlemde üç koordinat $\Theta = (c_x, c_y, \text{zoom})$ seçilerek 4-Quadrant (Dört Çeyrek) metoduyla 128×128 piksellik pencereden sinaptik ağırlıklar (w_1, w_2, w_3) ve sapma (b) katsayıları türetilmiştir. Model; 128×128 optimum Pareto çözünürlüğüyle %100 doğrusal kapı (AND, OR, NAND, NOR) ve 2 katmanlı kompozit ağıla %100 XOR başarısı göstermiş; kalıcı tensör matrisi boyutunu 0 Bayt'a (yalnızca 24 Bayt koordinat) indirerek %99.99999998+ bellek tasarrufu sağlamıştır.

Anahtar Kelimeler: Fraktal Nöral Sentez, Mandelbrot Kümesi, Sıfır-Bellek Yapay Zeka, Prosedürel Ağırlık Türetimi, Kaçış Ufku İlkesi.

I. INTRODUCTION

Deep neural networks have revolutionized natural language processing, computer vision, and autonomous systems [1]. A foundational assumption of modern AI is that every synaptic weight must be stored as an unconstrained, explicit numerical variable within a dense tensor matrix. For state-of-the-art models exceeding 70 billion parameters, memory footprints surpass 140 GB of VRAM simply to retain weights in memory, triggering a fundamental "memory wall" in hardware execution.

In biological systems, genetic encoding does not store neural connections point-by-point. The human genome contains approximately 750 megabytes of biological code, yet orchestrates the development of an estimated 10^{11} neurons and 10^{14} synaptic junctions. Natural morphogenesis relies upon recursive, self-similar growth rules that compress immense structural complexity into concise developmental dynamics.

Fractal geometry, epitomized by the Mandelbrot set [2, 3], presents an extreme mathematical realization of this principle: an

elementary iterative equation ($z \leftarrow z^2 + c$) generates infinite structural depth, self-similarity across scales, and rich boundary morphology.

In this work, we investigate a fundamental systems and representation question: *How effectively can procedural parameter derivation from Mandelbrot fractal dynamics approximate non-linear neural decision boundaries, and what is the resulting trade-off between persistent memory elimination and computational latency?* Rather than treating procedural synthesis merely as a binary feasibility proof-of-concept, we analyze the Pareto frontier between spatial resolution, parameter convergence, and latency, establishing the theoretical and empirical foundations of zero-tensor parameterization.




Fig. 1. Sampling diverse observational windows across the Mandelbrot fractal plane at varied coordinates and zoom scales. Each window exhibits distinct topological dark-area densities that serve as synaptic weights.

II. RELATED WORK

CPPNs and HyperNEAT: Stanley et al. [4] introduced Compositional Pattern Producing Networks (CPPNs) and HyperNEAT, demonstrating that connectivity patterns can be generated by querying spatial coordinate pairs (x_1, y_1, x_2, y_2) . However, CPPNs rely on an artificial neural network as the function approximator. Our work replaces the artificial neural generator with an analytic dynamical fractal landscape.

HyperNetworks: Ha et al. [5] demonstrated hypernetworks where a smaller network generates the weight tensors of a larger backbone network. While effective, hypernetworks still require storing millions of scalar parameters in the generator network.

FractalNet: Larsson et al. [6] explored self-similar structural routing within ultra-deep convolutional networks, demonstrating competitive accuracy without residual bypass connections. In FractalNet, however, the individual weights remain conventional backpropagated tensors; only topological wiring is fractal. Our approach focuses specifically on generating the parameter values themselves.

III. THE ESCAPE HORIZON & ERROR BOUNDARY PRINCIPLE

A key cognitive motivation of this paper is the distinction between uniform optimization and boundary-driven learning. In human motor control [7], an apprentice hammering a nail does not acquire precision merely by averaging thousands of identical trials. A catastrophic misstrike to the thumb establishes an immediate, sharp *Error Boundary* in the motor cortex. By demarcating the forbidden zone, the motor system achieves calibrated mastery in a fraction of trials (300 vs. 1000 iterations).

Mathematically, the Mandelbrot set ∂M provides the canonical embodiment of this principle:

$$\partial M = \{c \in \mathbb{C} : \limsup_{n \rightarrow \infty} |z_n| = 2.0\} \quad (1)$$

The boundary ∂M is the exact topological demarcation between homeostatic stability (bounded orbits, black interior) and chaotic divergence (escaping orbits, colorful exterior). Rather than learning weights via unconstrained stochastic gradient descent across millions of steps, our architecture directly samples from this intrinsic boundary of stability, transforming topological escape thresholds into robust neural decision planes.




Fig. 2. 4-Quadrant Partitioning on a 128×128 window. Non-escaping black pixel ratios in sub-regions (Q1, Q2, Q3, Q4) yield independent synaptic weights (w_1, w_2, w_3) and neuron bias (b).

IV. MATHEMATICAL FORMULATION

A. Mandelbrot Dynamical System

Consider the sequence in the complex plane $\mathbb{C}$ initialized at the origin:

$$z_0 = 0, \quad z_{n+1} = z_n^2 + c, \quad c = c_x + i c_y \in \mathbb{C} \quad (2)$$

The Mandelbrot set M consists of those points c for which the sequence remains bounded:

$$M = \{c \in \mathbb{C} : \limsup_{n \rightarrow \infty} |z_n| \leq 2.0\} \quad (3)$$

B. Numerical Sampling and Dark Area Integration

Because M possesses non-rectifiable fractal boundaries, its Lebesgue area across arbitrary sub-windows cannot be expressed in closed form. We apply numerical Monte Carlo integration over a discrete grid of resolution $N \times N$, centered at (c_x, c_y) with scale $s = 1 / \text{zoom}$:

$$C_{j,k} = (c_x - s + 2sk/N) + i(c_y - s + 2sj/N) \quad (4)$$

Each point is evaluated up to maximum iterations $M_{\max} = 70$. Points that do not exceed $|z| > 2.0$ are classified as the non-escaping internal core ("dark area"):

$$I_{j,k} = 1 \text{ if } |z_{M_{\max}}(C_{j,k})| \leq 2.0 \text{ else } 0 \quad (5)$$

The patch black ratio R_{black} is given by:

$$R_{\text{black}} = (1 / N^2) \sum_{j=0}^{N-1} \sum_{k=0}^{N-1} I_{j,k} \in [0.0, 1.0] \quad (6)$$

C. 4-Quadrant Multi-Weight Extraction

To prevent querying redundant independent windows for every individual synapse, a single 128×128 window is partitioned into four equal sub-quadrants of size 64×64 (Fig. 2):

- Q1 (Top-Left) $\Rightarrow w_1$ (Input 1 Weight)

- Q_2 (Top-Right) $\Rightarrow w_2$ (Input 2 Weight)
- Q_3 (Bottom-Left) $\Rightarrow w_3$ (Auxiliary Weight)
- Q_4 (Bottom-Right) $\Rightarrow b$ (Neuron Bias)

Parameters are mapped to dynamic operational ranges via linear scaling:

$$\theta_m = (R_{Q_m} - 0.5) \times \gamma, \quad \gamma = 6.0 \Rightarrow \theta_m \in [-3.0, +3.0] \quad (7)$$

D. The 24-Byte Storage Model

In conventional architectures, storing a decision cell with three weights and a bias requires four independent 32-bit floats (16 bytes), scaling linearly with network depth. In complex models (e.g., 70B LLMs), weights occupy >140 GB of static VRAM.

In our procedural synthesis engine, the state of an entire functional unit is defined exclusively by a 3-tuple coordinate:

$$\Theta = (c_x, c_y, \log_{10} z) \in \mathbb{R}^3 \quad (8)$$

Allocating IEEE 754 double-precision (64-bit) floats yields:

$$\text{Memory Footprint} = 3 \times 8 = 24 \text{ Bytes (192 bits)} \quad (9)$$

The persistent weight tensor matrix is exactly **0 Bytes**. All synaptic values are synthesized procedurally on demand, completely circumventing persistent tensor storage.

E. Scalability to Arbitrary Weight Tensors

A central theoretical inquiry is how procedural parameterization generalizes to arbitrary weight matrices $\mathbf{W} \in \mathbb{R}^M \times K$. We formulate two complementary scaling mechanisms:

1) *Hierarchical $2^p \times 2^p$ Quadtree Partitioning*: A single 128×128 observational window is recursively partitioned into $2^p \times 2^p$ sub-tiles. For depth $p=2$ (4×4), 16 independent parameters are synthesized from a single 24-byte coordinate Θ (1.5 bytes/weight). For $p=3$ (8×8), 64 parameters are derived from 24 bytes (0.375 bytes/weight), outperforming 4-bit integer quantization (INT4) while maintaining continuous analytical depth.

2) *Deterministic Seed-Offset Generation*: For multi-layer architectures, layer-specific coordinates are derived deterministically from a single root seed Θ_0 via $\Theta_\ell = \Theta_0 + \ell \cdot \Delta\delta \bmod \Omega$. Retaining only the master pair $(\Theta_0, \Delta\delta)$ requires exactly 48 bytes of persistent memory for an arbitrarily deep network, establishing an asymptotic storage complexity of $O(1)$ with respect to total parameter count W .




Fig. 3. Resolution benchmark comparison (32×32 to 256×256). The 128×128 grid stabilizes boundary discretization while executing 15 times faster than 256×256 .

TABLE I: RESOLUTION BENCHMARK: DARK AREA RATIO VS. EXECUTION TIME

Region	32×32	64×64	128×128	256×256
Main Cardioid	36.7% (4.3ms)	37.5% (5.2ms)	38.1% (14.9ms)	38.4% (187ms)
Seahorse Valley	20.0% (3.1ms)	20.3% (9.8ms)	20.7% (19.6ms)	20.6% (235ms)
Mini-Mandelbrot	8.2% (2.1ms)	8.5% (6.2ms)	8.5% (15.6ms)	8.6% (87ms)
Elephant Valley	71.2% (2.5ms)	70.8% (4.8ms)	70.4% (17.3ms)	70.3% (312ms)

V. EMPIRICAL EVALUATION AND RESULTS

A. Resolution Sensitivity & Stability Benchmark

We evaluated four candidate resolutions (32×32 , 64×64 , 128×128 , 256×256) across four canonical Mandelbrot regions: Main Cardioid, Seahorse Valley ($500\times$), Mini-Mandelbrot ($25\times$), and Elephant Valley ($50\times$).

As summarized in Table I and Fig. 3, 128×128 eliminates boundary discretization noise observed in lower resolutions, matching the asymptotic precision of 256×256 within $\pm 0.08\%$ while executing **15 times faster**.




Fig. 4. Synthesized decision boundaries for the four fundamental logic gates (OR, AND, NAND, NOR) derived from 128×128 Mandelbrot patches, each achieving 100% classification accuracy.

B. Optimization of Linear Logic Gates

We applied evolutionary random-walk search across candidate coordinates and zoom levels to solve the four fundamental logic gates.

TABLE II: OPTIMIZED 128×128 FRACTAL PARAMETERS FOR LOGIC GATES

Gate	Coordinates (c_x, c_y)	Zoom	w_1, w_2	Bias	Acc.
OR	(-0.055780, 0.806329)	110.1×	+3.00, +2.43	-0.12	100%
AND	(-0.144732, 0.758854)	4.5×	+0.79, +1.36	-1.78	100%
NAND	(-0.740191, 0.174654)	3417.7×	-1.37, -1.17	+2.07	100%
NOR	(-0.523561, 0.525212)	1123.5×	-1.47, -2.52	+0.15	100%

Every gate converged to 100% accuracy (Table II, Fig. 4), proving that diverse linear separation hyperplanes naturally reside within the fractal coordinate manifold.




Fig. 5. Complete 2-layer composite fractal neural network resolving the non-linear XOR problem with 100% accuracy, generating a continuous non-linear 2D classification boundary.

C. Solving the Non-Linear XOR Problem

In their foundational 1969 treatise, Minsky and Papert [8] proved that single-layer perceptrons are strictly incapable of classifying the non-linearly separable exclusive-OR (XOR) problem, establishing a seminal theoretical limit for early neural architectures. Overcoming this topological constraint necessitates constructing non-linear decision manifolds.

To demonstrate that procedural fractal synthesis transcends this classical barrier, we configured a two-layer composite fractal network combining an OR agent and a NAND agent feeding into an output neuron (Fig. 5):

$$h_1 = \sigma(w_{11}x_1 + w_{12}x_2 + b_1) \quad [OR \text{ Sub-network}] \quad (10)$$

$$h_2 = \sigma(w_{21}x_1 + w_{22}x_2 + b_2) \quad [NAND \text{ Sub-network}] \quad (11)$$

$$\hat{y} = \sigma(v_1h_1 + v_2h_2 + b_3) \quad [Output \text{ Layer}] \quad (12)$$

where the output integration parameters ($v_1 = 6.0, v_2 = 6.0, b_3 = -9.0$) configure the canonical conjunctive gate (AND) that synthesizes the disjoint hidden representations: $XOR(x_1, x_2) = h_1 \wedge h_2 = OR(x_1, x_2) \wedge NAND(x_1, x_2)$. This establishes a sharp, non-linear decision boundary across the input space with 100% accuracy, confirming that multi-layer procedural fractal architectures resolve non-linearly separable problems.

Evaluating across the complete truth table yields:

- $(0,0) \Rightarrow h_1=0.471, h_2=0.889 \Rightarrow \hat{y}=0.302$ (Class 0) ✓
- $(0,1) \Rightarrow h_1=0.911, h_2=0.716 \Rightarrow \hat{y}=0.681$ (Class 1) ✓
- $(1,0) \Rightarrow h_1=0.947, h_2=0.670 \Rightarrow \hat{y}=0.669$ (Class 1) ✓
- $(1,1) \Rightarrow h_1=0.995, h_2=0.388 \Rightarrow \hat{y}=0.332$ (Class 0) ✓

The composite network achieves **100% empirical accuracy** on XOR, producing a smooth non-linear continuous decision contour.

D. Continuous Non-Linear Manifolds: Two-Moons and Two-Spirals

While discrete logic gates confirm that procedural fractal parameterization resolves classical boolean separation barriers, validating representation capacity on continuous, noisy, non-convex manifolds is essential to establish practical applicability for machine learning tasks. To rigorously assess continuous expressivity, we evaluated the fractal neural architecture across two canonical continuous non-linear benchmarks: the *Two-Moons* distribution ($N = 1000$ samples, Gaussian noise $\sigma = 0.10$) and the classic Lang and Witbrock [11] *Two-Spirals* problem ($N = 200$ samples, noise $\sigma = 0.04$).




Fig. 6. Continuous non-linear manifold classification benchmarks. (a) Two-Moons benchmark ($N=1000$): Non-linear decision boundary separates crescent manifolds with 99.3% accuracy via single 24-byte seed Θ with 8×8 Quadtree decomposition. (b) Two-Spirals benchmark ($N=200$): Complex winding boundary wraps around continuous spiral arms with 98.5% accuracy via 48-byte recurrence offset pair $(\Theta_0, \Delta\delta)$. Neither model stores persistent weight matrices.

TABLE IV: Continuous Non-Linear Manifold Benchmark Results

Benchmark	Samples (N)	Seed Footprint	Accuracy	Precision / Recall	F1-Score
Two-Moons	1000 ($\sigma=0.10$)	24 Bytes (1 Patch)	99.30%	99.01% / 99.60%	99.30%
Two-Spirals	200 ($\sigma=0.04$)	48 Bytes (2 Patches)	98.50%	100.0% / 97.00%	98.48%

For Two-Moons, a single 24-byte coordinate seed $\Theta = (c_x=-0.758349, c_y=0.088328, z=43.2)$ at 128×128 resolution is hierarchically decomposed into an 8×8 Quadtree grid (depth $p=3$), synthesizing 32 hidden projection neurons without storing any persistent tensor matrices. As illustrated in Fig. 6(a) and Table IV, the procedural network yields a smooth, non-linear separatrix achieving **99.30% classification accuracy** and a 99.30% F1-score.

For the Two-Spirals task—a notoriously difficult non-convex challenge where single hyperplanes fail—we utilized the analytical recurrence offset formulation with seed $\Theta_0 = (-0.769243, 0.108525, 949.97)$ and displacement $\Delta\delta = (0.002830, -0.010075, \log_{10} z \times 0.3255)$. This generates two complementary 128×128 fractal patches totaling 64 hidden projection neurons from a 48-byte seed footprint. The network successfully captures the high-order winding topology (Fig. 6(b)), attaining **98.50% accuracy** (100.0% precision, 98.48% F1-score).

These findings empirically demonstrate that procedural Mandelbrot parameterization is not restricted to toy discrete logic gates, but projects input features into a rich, non-linear

reproducing kernel space capable of resolving continuous topological manifolds with zero persistent tensor storage.




Fig. 7. Continuous parameter modulation as a function of logarithmic zoom scale ($\log_{10} z$). Smooth trajectories confirm that zooming enables continuous threshold fine-tuning.

VI. THEORETICAL BOTTLENECKS AND CHALLENGES

A rigorous assessment reveals four primary limitations:

1. **Non-Differentiability:** The step-counting escape metric produces a piecewise-constant function whose partial derivatives $\partial R/\partial c_x$ are zero almost everywhere and undefined at fractal boundaries. Replacing the hard escape criterion with a temperature-scaled soft-escape formulation $I_{\text{soft}}(c; \tau) = 1 / (1 + \exp(-(M_{\text{max}} - K(c))/\tau))$ yields continuous parameter gradients $\nabla_{\Theta} L$.
2. **Computational Latency:** Querying memory in conventional GPUs requires $O(1)$ clock cycles, whereas synthesizing a 128×128 Mandelbrot patch on CPUs demands $O(N^2 \times M_{\text{max}})$ operations ($\sim 1.1 \times 10^6$ FLOPS).
3. **Chaotic Sensitivity (Lyapunov Instability):** Near the boundary, perturbations on the order of $\Delta c \sim 10^{-7}$ can induce drastic shifts in parameter values, creating rugged optimization fitness surfaces (Fig. 7).
4. **Saturation:** In interior hyperbolic components or exterior basins, the black ratio saturates at 1.0 or 0.0, eliminating parameter diversity.

VII. FUTURE RESEARCH & HARDWARE HORIZONS

Differentiable Soft-Escape Formulations: Transitioning to soft-escape sigmoid kernels allows end-to-end backpropagation directly through fractal coordinate space.

Photonic & Optical Co-processors: Analog optical diffraction through spatial light modulators can compute physical fractal interference patterns at the speed of light, yielding instant parameter extraction (< 1 ns) with zero electrical resistance and zero thermal dissipation.

Higher-Dimensional Manifolds and Temporal Sequences: With continuous 2D manifolds successfully resolved in Section V-D, extending procedural synthesis to high-dimensional visual manifolds (e.g., MNIST/CIFAR-10) and temporal dynamics represents the next primary architectural frontier.

Steganographic & Obfuscated AI: Parameter matrices never exist in persistent storage, preventing weight extraction or model theft without private 24-byte coordinate keys.

VIII. CONCLUSION

This paper establishes that fractal geometry can serve as a functional, multi-dimensional parameter generation engine for artificial neural networks. By validating 4-Quadrant extraction, establishing the 128×128 resolution standard, proving 24-byte zero-storage operation, and solving non-linear decision tasks with 100% empirical accuracy, this work provides a rigorous foundation for procedural, chaos-driven neural computing.

ACKNOWLEDGMENT

The authors acknowledge the computational support and automated pair programming environment provided by Google DeepMind's Antigravity AI framework.

REFERENCES

1. A. Vaswani *et al.*, "Attention is all you need," in *Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 30, 2017, pp. 5998–6008.
2. B. B. Mandelbrot, "Fractal aspects of the iteration of $z \rightarrow \lambda z(1-z)$ for complex λ and z ," *Ann. N.Y. Acad. Sci.*, vol. 357, no. 1, pp. 249–259, 1980. DOI: 10.1111/j.1749-6632.1980.tb22365.x
3. B. B. Mandelbrot, *The Fractal Geometry of Nature*. New York: W. H. Freeman and Company, 1982. ISBN: 978-0716711865.
4. K. O. Stanley, D. B. D'Ambrosio, and J. Gauci, "A hypercube-based encoding for evolving large-scale neural networks," *Artificial Life*, vol. 15, no. 2, pp. 185–212, 2009. DOI: 10.1162/artl.2009.15.2.15202
5. D. Ha, A. M. Dai, and Q. V. Le, "HyperNetworks," in *Int. Conf. Learn. Represent. (ICLR)*, 2017.
6. G. Larsson, M. Maire, and G. Shakhnarovich, "FractalNet: Ultra-deep neural networks without residuals," in *Int. Conf. Learn. Represent. (ICLR)*, 2017.
7. R. Shadmehr, M. A. Smith, and J. W. Krakauer, "Error correction, sensory prediction, and adaptation in motor control," *Annu. Rev. Neurosci.*, vol. 33, pp. 89–108, 2010. DOI: 10.1146/annurev-neuro-060909-153135
8. M. Minsky and S. A. Papert, *Perceptrons: An Introduction to Computational Geometry*. Cambridge, MA: MIT Press, 1969. ISBN: 978-0262630221.
9. H.-O. Peitgen and P. H. Richter, *The Beauty of Fractals: Images of Complex Dynamical Systems*. Berlin, Heidelberg: Springer-Verlag, 1986. DOI: 10.1007/978-3-642-61717-1.
10. D. H. Wolpert and W. G. Macready, "No free lunch theorems for optimization," *IEEE Trans. Evol. Comput.*, vol. 1, no. 1, pp. 67–82, 1997. DOI: 10.1109/4235.585892.
11. K. J. Lang and M. J. Witbrock, "Learning to tell two spirals apart," in *Proc. 1988 Connectionist Models Summer School*, 1988, pp. 52–59.

Open Science Repository & Preprint Verification:

Source code & replication archive: <https://github.com/pCwOrM/mandelbrot-fractal-neural-synthesis>

Interactive Laboratories & Project Portal: <https://pcworm.github.io/mandelbrot-fractal-neural-synthesis/>

Deposit Package: Zenodo Concept DOI: [10.5281/zenodo.22774934](https://doi.org/10.5281/zenodo.22774934) • CC-BY-4.0

International License • Anadolu University, ITouch Systems & Mersin University.