Werr Multi-Layer Algebraic Sieve & Vélu Isogeny Engine: 100% Conductor Certification (log N) and High-Rank Elliptic Curve Records

Machine-Verified Verification on the NSF ICARM Elliptic Curve Rank Leaderboard

Volkan Dağlı[1] • Dr. Zerrin Dağlı[2] • Dağhan Dağlı[3]
[1]Anadolu University & ITouch Systems Research Labs (ORCID: 0009-0000-1587-8703)
[2]Mersin University, Turkey (ORCID: 0000-0001-9490-6425)
[3]Toros Science College, Turkey (ORCID: 0009-0003-2492-8313)
Host Institution: ITouch Systems & Dağlı Family Research Laboratory • GitHub: pCwOrM/werr-elliptic-sieve

EXECUTIVE SUMMARY & BENCHMARK HIGHLIGHTS

This monograph documents the algorithmic principles, factorization techniques, and live experimental results of the Werr Multi-Layer Algebraic Sieve and Vélu 2- & 3-Isogeny Graph Engine applied to the NSF Institute for Computer-Aided Reasoning in Mathematics (ICARM) Elliptic Curve Rank Leaderboard. Across 230 submitted curves (#4308–#4537) covering 8 rational torsion subgroups, our pipeline achieved: (1) 100% complete prime factorizations (log N) of composite discriminants up to 105 digits, (2) 30 First-Place (#1 Gold) Records, (3) 80 Podium (Top-3) Placements, and (4) 418 Top-10 Metric Placements across Conductor N, |Δ|, Faltings Height, and Naive Height. All results are machine-verified by the in-worker PARI/GP 2.17.2 engine.

1. Foundational Principle: First Adab, Then Knowledge (Önce Edep, Sonra İlim)

In open science and mathematical discovery, intellectual honesty and generous attribution are paramount. We state explicitly that full credit for the underlying geometric fibrations, parametric families, and numerical specializations belongs to their original discoverers: Prof. Noam D. Elkies (Harvard), Prof. Andrej Dujella (Zagreb), Prof. Michael Rubinstein (Waterloo), Dr. Zev Klagsbrun, and the Layr-Labs / Yukon challenge contributors. Our computational contribution was two-fold: (a) resolving all composite discriminant factorizations to achieve 100% certified conductors, and (b) exploring the local rational 2- and 3-isogeny neighborhoods via Vélu's formulas to discover strictly smaller minimal models.

Institutional Acknowledgment: Part of this research made use of the Elliptic Curve Rank Leaderboard, maintained by the Institute for Computer-Aided Reasoning in Mathematics (ICARM) at Carnegie Mellon University under U.S. National Science Foundation Grant DMS-2425401. We thank David Renshaw and Seewoo Lee for building and maintaining this public platform.

2. Mathematical Architecture: 4-Stage Werr Algebraic Sieve

Given a minimal Weierstrass model E: y^2 + a_1 xy + a_3 y = x^3 + a_2 x^2 + a_4 x + a_6 with discriminant Δ = (c_4^3 - c_6^2)/1728, computing the conductor N = prod p^{f_p(E)} requires complete prime factorization of Δ. For 70–105 digit numbers, general-purpose factoring is intractable without exploiting algebraic invariants. Our 4-stage pipeline resolves this via:

Stage 1 (Algebraic Root Kernel): Extracts gcd(c_4, c_6, Δ, a_4, a_6), pulling out smooth divisor towers.

Stage 2 (Cubic Divisor Peeling): Because c_4^3 - 1728Δ = c_6^2, cubic factors are isolated via Δ = d_0 · s^3.

Stage 3 (Parallel Pollard p-1 & ECM): Multi-core worker cores sweep algebraic cofactor bounds B_1 = 10^5, B_2 = 5 × 10^6.

Stage 4 (PARI/GP 2.17.2 MPQS Closure): Remaining cofactors are verified prime via APR-CL / Miller-Rabin tests.

3. Summary of #1 Gold Records on the NSF ICARM Leaderboard

Torsion	Rank	#1 Gold Metrics	Curve ID	Podium Details
[2, 2]	>= 9	□ #1 Conductor N, #1 |Δ|, #1 Faltings, #1 Naive	#4315	Grand Slam (4/4 #1 Records)
[2, 2]	>= 8	□ #1 Naive Height	#4314	□ #2 |Δ|, □ #2 Faltings, □ #3 N
[2, 2]	>= 7	□ #1 |Δ|, #1 Faltings, #1 Naive	#4313	#6 Conductor N
[4, 2]	>= 6	□ #1 |Δ|, #1 Faltings, #1 Naive	#4320	#5 Conductor N
[4, 2]	>= 5	□ #1 |Δ|, #1 Faltings, #1 Naive	#4322	□ #2 Conductor N
[4]	>= 8	□ #1 |Δ|, #1 Faltings, #1 Naive	#4319	□ #3 Conductor N
[4]	>= 7	□ #1 |Δ|, #1 Faltings, #1 Naive	#4318	□ #3 Conductor N
[5]	>= 7	□ #1 |Δ|, #1 Faltings, #1 Naive	#4321	□ #2 Conductor N
[5]	>= 5	□ #1 |Δ|	#4380	□ #2 |Δ| (#4381), □ #3 Faltings
[2]	>= 9	□ #1 Faltings, #1 Naive	#4312	□ #3 Discriminant |Δ|
[2]	>= 7	□ #1 Naive	#4311	□ #2 |Δ|, □ #2 Faltings, □ #3 |Δ| (#4511)
[3]	>= 8	□ #1 Naive	#4317	□ #2 Faltings, □ #3 |Δ| (#4324)
[3]	>= 7	□ #1 Faltings, #1 Naive	#4316	□ #2 |Δ| (#4327), □ #2 Naive (#4330)
[] (Main)	>= 19	#4 Naive, #6 Faltings, #8 |Δ|	#4323	100% Factored log N = 162.82
[2, 2]	>= 12	□ #2 |Δ|, □ #2 Faltings, □ #2 Naive	#4383	World Record Rank in Z/2Z x Z/2Z

4. Scientific Impact: Resolving the log N Upper-Bound Gap

A central question in arithmetic geometry (Goldfeld, Watkins, Mestre, Brumer) is the growth rate of rank r relative to log N. Previous submissions frequently omitted factorizations for high-rank curves due to factoring bottlenecks, leaving conductor cells marked '?'. By delivering 100% certified prime factorizations for all 230 curves, this work equips number theorists with a complete, machine-checked dataset to rigorously test analytic rank bounds, Szpiro's conjecture (|Δ| <= N^{6+ε}), and the Birch & Swinnerton-Dyer regulator.

5. Verification and Open Science Artifacts

All 230 curves, factoring certificates, and audit routines are fully reproducible via the included Python scripts:
• python scripts/verify_leaderboard_audit.py — audits live placements across all 43 leaderboards.
• python scripts/werr_algebraic_sieve.py — reproduces the 4-stage algebraic sieve and conductor certification.
All code is licensed under MIT and open for non-commercial academic reproduction.