

Storage Account

Big scalable disk inside Microsoft Cloud used to store files

- **Region** - where geographically the disk is located. Storage Account and Databricks Workspace should be located in the same region to eliminate latency and costs
- **Redundancy** - this parameter specifies how to store copies of data in order to prevent data loss in case of emergency
 - LRS - Azure creates 3 copies of the data inside one local data center. Cheap and good for learning
 - GRS - creates 3 copies locally as well as LRS but also creates another 3 copies in another region. More expensive but safer in production.
- **Hierarchical namespace** - this option changes regular Blob Storage (data is not structured in folders) into ADLS Gen2 (generates a hierarchical structure of files). This option is much faster and optimized
- **Access Tier** - defines how often the data will be used. Has an impact on cost
 - Hot - the data is actively analyzed and queried. High storage cost, low access cost
 - Cool - data is queried less frequently. Low storage cost, higher access cost
 - Cold - data is archived and not queried. Very low storage cost and very high access cost
- **Public network access** - defines which networks can access storage
 - Enabled from all networks - every network can access with correct tokens
 - Disabled / Selected networks - only selected or none networks can access

Create a storage account ...

Basics Advanced Networking Data protection Security Encryption Tags Review + create

Azure Storage is a Microsoft-managed service providing cloud storage that is highly available, secure, durable, scalable, and redundant. Azure Storage includes Azure Blobs (objects), Azure Data Lake Storage Gen2, Azure Files, Azure Queues, and Azure Tables. The cost of your storage account depends on the usage and the options you choose below.
[Learn more about Azure storage accounts](#)

Project details

Select the subscription in which to create the new storage account. Choose a new or existing resource group to organize and manage your storage account together with other resources.

Subscription *

Resource group *
[Create new](#)

Instance details

Storage account name *

Region *
[Deploy to an Azure Extended Zone](#)

Primary service *

☒ This helps us provide relevant guidance. It doesn't restrict your storage to this resource type. [Learn more](#)

Performance * ☐

☒ Standard: Recommended for most scenarios (general-purpose v2 account)

☐ Premium: Recommended for scenarios that require low latency.

Redundancy *

Create a storage account ...

Azure Blob Storage

These are settings which apply to only Azure Blob storage

- Enable hierarchical namespace  ☒
- Enable SFTP  ☐
- Allow cross-tenant replication  ☐
 Cross-tenant replication and hierarchical namespace cannot be enabled simultaneously.
- Access tier  ☒ Hot
Optimized for frequently accessed data and everyday usage scenarios
- ☐ Cool
Optimized for infrequently accessed data and backup scenarios
- ☐ Cold
Optimized for rarely accessed data and backup scenarios

Azure Files

These are settings which apply to only Azure Files

- Enable network file system v3  ☐
-  The current combination of storage account kind, performance, and replication does not support SMB Multichannel.
- Enable Managed Identity for SMB  ☐
- Require Encryption in Transit for SMB *  ☒
- Require Encryption in Transit for NFS *  ☐
 The current combination of storage account kind, performance, replication, and location does not support encryption in transit for NFS.

Create a storage account ...

Public access

Access your resource from anywhere through a public network.

Note: Allowing access to your resource through a public network increases security risk. [Learn more](#) 

- Public network access *  ☒ Enable
Allow inbound and outbound access with the option to restrict select inbound access using resource access configurations for this resource.
- ☐ Disable
Restrict inbound access while allowing outbound access.
- ☐ Secure by perimeter (Most restricted)
Restrict inbound and outbound access using a network security perimeter. Secure by perimeter offers the greatest level of inbound and outbound restriction to secure your resource.
- Public network access scope * ☐ Enable from all networks
- ☒ Enable from selected virtual networks and IP addresses

Virtual networks

Only the selected network will be able to access this storage account. [Learn more](#) 

- Virtual network subscription 
- Virtual network 
[Create virtual network](#)

Home > PL_24_Databricks

sttrezio2005 Storage account

Help me connect my application to this storage account. Does this storage account follow security best practices? Harden this storage account.

Search

Upload Open in Explorer Delete Move Refresh Open in mobile CLI / PS Feedback

Overview

- Activity log
- Tags
- Diagnose and solve problems
- Access Control (IAM)
- Data migration
- Events
- Storage browser
- Partner solutions
- Resource visualizer
- Data storage
 - Containers
 - Classic file shares
 - Queues
 - Tables
- Security + networking
 - Data management
 - Settings
 - Monitoring
 - Automation
- Help

Essentials

Resource group (move)	: PL_24_Databricks	Performance	: Standard
Location	: westeurope	Replication	: Locally redundant storage (LRS)
Subscription (move)	: subscr-ita-vkoldov	Account kind	: StorageV2 (general purpose v2)
Subscription ID	: 419d681c-4d7e-48a1-ba31-24afe1f4e486	Provisioning state	: Succeeded
Disk state	: Available	Created	: 19.07.2026, 15:53:36
Tags (edit)	: Add tags		

Properties Monitoring Capabilities (5) Recommendations (0) Tutorials Tools + SDKs

Data Lake Storage

Hierarchical namespace	Enabled
Default access tier	Hot
Blob anonymous access	Disabled
Blob soft delete	Enabled (7 days)
Container soft delete	Enabled (7 days)
Versioning	Disabled
Change feed	Disabled
NFS v3	Disabled
SFTP	Disabled
Storage tasks assignments	None

File service

Identity-based access	Not configured
Default share-level permissions	Disabled
Soft delete	Enabled (7 days)
Require Encryption in Transit for SMB	Enabled

Security

Require secure transfer for REST API operations	Enabled
Storage account key access	Enabled
Minimum TLS version	Version 1.2
Infrastructure encryption	Disabled

Networking

Public network access	Enabled
Public network access scope	Enabled from selected virtual networks and IP addresses
Private endpoint connections	0
Network routing	Microsoft network routing
Endpoint type	Standard

Add or remove Services by pressing Ctrl+L and PL L F

KeyVault

Virtual, secure vault inside Microsoft Cloud. Designed to store confidential data like passwords, keys, API, tokens. You can retrieve those secrets directly from the code.

- **Permission Model** - defines how to manage the data and who has access
 - Azure RBAC - role based access control, can be changed globally
 - Vault access policy - rules are set locally directly inside Key Vault
- **Soft delete** - when data is deleted it is transferred to the temporary folder where it is held for specific amount of time (for example 90 days) and then permanently deleted
- **Purge protection** - disables the ability to manually delete files from the temporary bin

Create a key vault ...

Project details

Select the subscription to manage deployed resources and costs. Use resource groups like folders to organize and manage all your resources.

Subscription *

Resource group * [Create new](#)

Instance details

Key vault name *

Region *

Pricing tier *

Recovery options

Soft delete protection will automatically be enabled on this key vault. This feature allows you to recover or permanently delete a key vault and secrets for the duration of the retention period. This protection applies to the key vault and the secrets stored within the key vault.

To enforce a mandatory retention period and prevent the permanent deletion of key vaults or secrets prior to the retention period elapsing, you can turn on purge protection. When purge protection is enabled, secrets cannot be purged by users or by Microsoft.

Soft-delete ☐ Enabled

Days to retain deleted vaults *

Purge protection ☐

☒ Disable purge protection (allow key vault and objects to be purged during retention period)

☐ Enable purge protection (enforce a mandatory retention period for deleted vaults and vault objects)

Basics Access configuration Networking Tags Review + create

Configure data plane access for this key vault

To access a key vault in data plane, all callers (users or applications) must have proper authentication

Permission model

Grant data plane access by using a [Azure RBAC](#) or [Key Vault access policy](#)

☒ Azure role-based access control (recommended) ⓘ

☐ Vault access policy ⓘ

Resource access

☐ Azure Virtual Machines for deployment ⓘ

☐ Azure Resource Manager for template deployment ⓘ

☐ Azure Disk Encryption for volume encryption ⓘ

kv-trezio2005 | Overview

Delete
Cancel
Redeploy
Download
Refresh

Overview
Inputs
Outputs
Template

Your deployment is complete

Deployment name : kv-trezio2005
Subscription : subscr-ita-vkoldov
Resource group : PL_24_Databricks

Start time : 7/19/2026, 4:12:05 PM
Correlation ID : 0a803180-37e1-4f2e-9fc5-6517dbdf6a82

Deployment details

Next steps

Go to resource

Give feedback

Tell us about your experience with deployment

Databricks Workspace

environment for data analytics and calculations. Here we write code, analyze data, manage the clusters. Provides the computing power

Create an Azure Databricks workspace

Project Details

Select the subscription to manage deployed resources and costs. Use resource groups like folders to organize and manage all your resources.

Subscription * ⓘ

subscr-ita-vkoldov

Resource group * ⓘ

PL_24_Databricks

[Create new](#)

Instance Details

Workspace name *

dbw-trezio2005

Region *

West Europe

Pricing Tier * ⓘ

Premium (+ Role-based access controls)

We selected the recommended pricing tier for your workspace. You can change the tier based on your needs.

Workspace type

- ☐ Serverless
No setup required. Uses Databricks-managed default storage and serverless compute. Connect to your cloud storage at any time. [Learn more](#)
- ☒ Hybrid
Requires access to compute and storage in your Azure account. Supports custom compute.

Managed Resource Group name

Enter name for managed resource group

Create an Azure Databricks workspace ...

✓ Validation Succeeded

Basics

Workspace name	dbw-trezio2005
Subscription	subscr-ita-vkoldov
Resource group	PL_24_Databricks
Region	West Europe
Pricing Tier	premium
Workspace type	Hybrid
Managed Resource Group name	

Networking

Deploy Azure Databricks workspace with Secure Cluster Connectivity (No Public IP)	Yes
Deploy Azure Databricks workspace in your own Virtual Network (VNet)	No

Encryption

Enable Infrastructure Encryption	No
Enable CMK for Managed Disks	No
Enable CMK for Managed Services	No

Security & compliance

Compliance Security Profile	No
Compliance Standards	
Enhanced Security Monitoring	No
Automatic Cluster Update	No

Home

PL_24_Databricks_dbw-trezio2005 | Overview ...

Deployment

Search X « Delete Cancel Redeploy Download Refresh

Overview

Inputs

Outputs

Template

✓ Your deployment is complete

Deployment name : PL_24_Databricks_dbw-trezio2005
Subscription : subscr-ita-vkoldov
Resource group : PL_24_Databricks

Start time : 7/19/2026, 4:23:03 PM
Correlation ID : 3a0edfc8-c6d0-4f33-be3f-a8d020eb637a

> Deployment details

Next steps

Go to resource

Give feedback

Tell us about your experience with deployment