

Task on s3

1. Create an S3 bucket and upload some objects to S3.

Buckets

General purpose buckets All AWS Regions Directory buckets

General purpose buckets (1/2) [info](#)

Buckets are containers for data stored in S3.

Name	AWS Region	Creation date
account-b-cross-access-2026	Europe (Stockholm) eu-north-1	October 7, 2026, 13:26:10 (UTC+05:30)
pranay-s3-demo-20261008	Europe (Stockholm) eu-north-1	October 8, 2026, 13:01:00 (UTC+05:30)

Account snapshot [info](#) [View dashboard](#)

Updated daily

Storage Lens provides visibility into storage usage and activity trends.

External access summary [info](#)

Updated daily

External access findings help you identify bucket permissions that allow public access or access from other AWS accounts.

Amazon S3

Upload succeeded

For more information, see the Files and folders table.

Upload: status [Close](#)

After you navigate away from this page, the following information is no longer available.

Summary

Destination s3://pranay-s3-demo-20261008	Succeeded 3 files, 2.0 MB (100.00%)	Failed 0 files, 0 B (0%)
--	---	------------------------------------

Files and folders [Configuration](#)

Files and folders (3 total, 2.0 MB)

Name	Folder	Type	Size	Status	Error
Linux tasks 23 to 42.docx	-	application/vnd.openxmlformats-...	397.5 KB	Succeeded	-
Screenshot 2026-09-28 234232.png	-	image/png	178.8 KB	Succeeded	-
IAM Task.pdf	-	application/pdf	1.4 MB	Succeeded	-

2. Deploy a static website in the S3 bucket.

Objects [Metadata](#) [Properties](#) [Permissions](#) [Metrics](#) [Management](#) [File systems](#) [Access Points](#)

Objects (1)

Objects are the fundamental entities stored in Amazon S3. You can use [Amazon S3 inventory](#) to get a list of all objects in your bucket. For others to access your objects, you'll need to explicitly grant them permissions. [Learn more](#)

Name	Type	Last modified	Size	Storage class
index.html	html	October 8, 2026, 13:24:41 (UTC+05:30)	202.0 B	Standard

Object Lock

Store objects using a write-once-read-many (WORM) model to help you prevent objects from being deleted or overwritten for a fixed amount of time or indefinitely. Object Lock works only in versioned buckets. [Learn more](#)

Object Lock

Disabled

Edit

Requester pays

When enabled, the requester pays for requests and data transfer costs, and anonymous access to this bucket is disabled. [Learn more](#)

Requester pays

Disabled

Edit

Static website hosting

Use this bucket to host a website or redirect requests. [Learn more](#)

We recommend using AWS Amplify Hosting for static website hosting

Deploy a fast, secure, and reliable website quickly with AWS Amplify Hosting. Learn more about [Amplify Hosting](#) or [View your existing Amplify apps](#)

Create Amplify app

S3 static website hosting

Enabled

Hosting type

Bucket hosting

Bucket website endpoint

When you configure your bucket as a static website, the website is available at the AWS Region-specific website endpoint of the bucket. [Learn more](#)

<http://abhishek-static-website1.s3-website.eu-north-1.amazonaws.com>

Edit

CloudShellAgent Toolkit for AWSFeedbackConsole Mobile App

© 2026, Amazon Web Services, Inc. or its affiliates. PrivacyTermsCookie preferences

Abhishek S3 Websiteabhishek-static-website1 - S3

Ask Gemini

←→↻

Not secure

abhishek-static-website1.s3-website.eu-north-1.amazonaws.com

☆🔍📄👤⋮

All Bookmarks

Welcome to static Website

This website is hosted on Amazon S3 Bucket.

3. Enable cross-region replication on S3 buckets.

abhishek-source-20261008

Info

ObjectsMetadataPropertiesPermissionsMetricsManagementFile systemsAccess Points

Objects (1)

↻Copy S3 URICopy URLDownloadOpenDeleteActionsCreate folderUpload

Objects are the fundamental entities stored in Amazon S3. You can use [Amazon S3 inventory](#) to get a list of all objects in your bucket. For others to access your objects, you'll need to explicitly grant them permissions. [Learn more](#)

Find objects by prefix

Show versions

< 1 >⚙

☐	Name	Type	Last modified	Size	Storage class
☐	index.html	html	October 8, 2026, 15:15:45 (UTC+05:30)	202.0 B	Standard

Replication configuration settings

Configuration settings affect all replication rules in the bucket.

Source bucket

abhishek-source-20261008

Source Region

Europe (Stockholm) eu-north-1

IAM role

[s3cm_role_for_abhishek-source-20261008](#)

Replication rules (1)

Use replication rules to define options you want Amazon S3 to apply during replication such as server-side encryption, replica ownership, transitioning replicas to another storage class, and more. Replication also includes any annotations attached to your objects. [Learn more](#)

Replication rule name	Status	Destination bucket	Destination Region	Priority	Scope	Storage class	Replica owner	Replication Time Control	KMS-encrypted objects (SSE-KMS or DSSE-KMS)	Replica modification sync
replicate-to-ap-south-1	Enabled	s3://abhishek-destination-20261008	US East (Ohio) us-east-2	0	Entire bucket	Same as source	Same as source	Disabled	Do not replicate	Disabled

abhishek-destination-20261008

Info

Objects

Metadata

Properties

Permissions

Metrics

Management

File systems

Access Points

Objects (2)

Copy S3 URI

Copy URL

Download

Open

Delete

Actions

Create folder

Upload

Objects are the fundamental entities stored in Amazon S3. You can use [Amazon S3 inventory](#) to get a list of all objects in your bucket. For others to access your objects, you'll need to explicitly grant them permissions. [Learn more](#)

Find objects by prefix

Show versions

Name	Type	Last modified	Size	Storage class
Index.html	html	October 8, 2026, 15:15:45 (UTC+05:30)	202.0 B	Standard
job-6122f496-5263-49dd-a469-3910cc1a5c4e/	Folder	-	-	-

4. Configure a bucket policy so only the Admin user can see the objects of the S3 bucket.

Policy

Public access is blocked because Block Public Access settings are turned on for this bucket

To determine which settings are turned on, check your [Block Public Access settings for this bucket](#). Learn more about [using Amazon S3 Block Public Access](#).

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

```
"Version": "2012-10-17",
"Statement": [
  {
    "Sid": "AllowAdminToListBucket",
    "Effect": "Allow",
    "Principal": {
      "AWS": "arn:aws:iam::814787354428:user/Admin"
    },
    "Action": "s3:ListBucket",
    "Resource": "arn:aws:s3:::abhishek-source-20261008"
  },
  {
    "Sid": "AllowAdminToReadObjects",
    "Effect": "Allow",
    "Principal": {
      "AWS": "arn:aws:iam::814787354428:user/Admin"
    },
    "Action": "s3:GetObject",
    "Resource": "arn:aws:s3:::abhishek-source-20261008/*"
  }
]
```

Buckets

General purpose buckets

All AWS Regions

Directory buckets

General purpose buckets (2) Info

Copy ARN

Empty

Delete

Create bucket

Buckets are containers for data stored in S3.

Find buckets by name

<

1

>

	Name	AWS Region	Creation date
☐	abhishek-destination-20261008	US East (Ohio) us-east-2	October 8, 2026, 15:09:52 (UTC+05:30)
☐	abhishek-source-20261008	Europe (Stockholm) eu-north-1	October 8, 2026, 15:09:30 (UTC+05:30)

Objects (1)

[Copy S3 URI](#) [Copy URL](#) [Download](#) [Open](#) [Delete](#) [Actions](#) [Create folder](#) [Upload](#)

Objects are the fundamental entities stored in Amazon S3. You can use [Amazon S3 inventory](#) to get a list of all objects in your bucket. For others to access your objects, you'll need to explicitly grant them permissions. [Learn more](#)

Find objects by prefix	☐ Show versions	< 1 >	Settings
☐ Name	☐ Type	☐ Last modified	☐ Size
☐ Index.html	html	October 8, 2026, 15:15:45 (UTC+05:30)	202.0 B Standard

5.Set up lifecycle policies to automatically transition or delete objects based on specific criteria.

Transition current versions of objects between storage classes

Choose transitions to move current versions of objects between storage classes based on your use case scenario and performance access requirements. These transitions start from when the objects are created and are consecutively applied. [Learn more](#)

Choose storage class transitions	Days after object creation	
Standard-IA	30	Remove
Intelligent-Tiering	60	Remove
One Zone-IA	90	Remove
Add transition		

Delete expired object delete markers or incomplete multipart uploads

Expired object delete markers

This action will remove expired object delete markers and may improve performance. An expired object delete marker is removed if all noncurrent versions of an object expire after deleting a versioned object. This action is not available when "Expire current versions of objects" is selected. [Learn more](#)

☒ Delete expired object delete markers

Incomplete multipart uploads

This action will stop all incomplete multipart uploads, and the parts associated with the multipart upload will be deleted. [Learn more](#)

☒ Delete incomplete multipart uploads

Number of days

Integer must be greater than 0.

Review transition and expiration actions

Current version actions

Day 0

- Objects uploaded

↓

Day 30

- Objects move to Standard-IA

↓

Day 60

- Objects move to Intelligent-Tiering

↓

Day 90

- Objects move to One Zone-IA

Noncurrent versions actions

Day 0

No actions defined.

🟢 The rule "Archive old object" has been successfully added and the lifecycle configuration has been updated. It may take some time for the configuration to be updated. Refresh the lifecycle rules list if changes to the configuration aren't displayed.

Lifecycle configuration

To manage your objects so that they are stored cost effectively throughout their lifecycle, configure their lifecycle. A lifecycle configuration is a set of rules that define actions that Amazon S3 applies to a group of objects. Lifecycle rules run once per day.

Default minimum object size for transitions
All storage classes 128K

Lifecycle rules (1)

Use lifecycle rules to define actions you want Amazon S3 to take during an object's lifetime such as transitioning objects to another storage class, archiving them, or deleting them after a specified period of time. [Learn more](#)

Find lifecycle rules by name

Lifecycle rule name	Status	Scope	Current version actions	Noncurrent versions ac...	Expired object delete ...	Incomplete multipart u...
Archive old object	Enabled	Entire bucket	Transition to Standard-IA, then 1		Permanently delete	Permanently delete

6.Push some objects to S3 using the AWS CLI.

Access keys (1)

Use access keys to send programmatic calls to AWS from the AWS CLI, AWS Tools for PowerShell, AWS SDKs, or direct AWS API calls. You can have a maximum of two access keys (active or inactive) at a time. [Learn more](#)

AKIA33NI4L46EAN653NC

Description

-

Last used

None

Last used region

N/A

Status

Active

Created

Now

Last used service

N/A

```
HP@abhishek UCRT64 ~/Downloads (master)
$ aws --version
aws-cli/2.37.4 Python/3.14.6 Windows/11 exe/AMD64

HP@abhishek UCRT64 ~/Downloads (master)
$ aws configure
AWS Access Key ID [*****PKN6]: AKIA33NI4L46EAN653NC
AWS Secret Access Key [*****04nY]: 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
Default region name [us-east-1]: us-east-1
Default output format [json]: json

HP@abhishek UCRT64 ~/Downloads (master)
$ aws s3 ls

aws: [ERROR]: An error occurred (AccessDenied) when calling the ListBuckets operation: User:
entity-based policy allows the s3:ListAllMyBuckets action

HP@abhishek UCRT64 ~/Downloads (master)
$ aws sts get-caller-identity
{
  "UserId": "AIDA33NI4L46HVX5TT0BC",
  "Account": "814787354428",
  "Arn": "arn:aws:iam::814787354428:user/S3-CrossAccount-User"
}

HP@abhishek UCRT64 ~/Downloads (master)
$ aws s3 ls

aws: [ERROR]: An error occurred (AccessDenied) when calling the ListBuckets operation: User:
entity-based policy allows the s3:ListAllMyBuckets action

HP@abhishek UCRT64 ~/Downloads (master)
$ |
```

7. Write a Bash script to create an S3 bucket.

```
HP@abhishek UCRT64 ~/Downloads (master)
$ aws sts get-caller-identity
{
  "UserId": "AIDA33NI4L46HVX5TT0BC",
  "Account": "814787354428",
  "Arn": "arn:aws:iam::814787354428:user/S3-CrossAccount-User"
}

HP@abhishek UCRT64 ~/Downloads (master)
$ ./create_bucket.sh
{
  "Location": "http://abhishek-bash-s3-20261008.s3.amazonaws.com/",
  "BucketArn": "arn:aws:s3:::abhishek-bash-s3-20261008"
}

s3 bucket created successfully: abhishek-bash-s3-20261008 Created successfully

HP@abhishek UCRT64 ~/Downloads (master)
$ aws s3 ls
2026-10-08 17:01:08 abhishek-bash-s3-20261008
2026-10-08 15:09:30 abhishek-source-20261008

HP@abhishek UCRT64 ~/Downloads (master)
$
```

```
HP@abhishek UCRT64 ~/Downloads (master)
$ cat create_bucket.sh
#!/bin/bash

BUCKET_NAME="abhishek-bash-s3-20261008"
REGION="eu-north-1"

aws s3api create-bucket \
  --bucket "$BUCKET_NAME" \
  --region "$REGION" \
  --create-bucket-configuration LocationConstraint="$REGION"

if [ $? -eq 0 ]; then
  echo "S3 bucket created successfully: $BUCKET_NAME Created successfully"
else
  echo "not created s3 bucket."
  exit 1
fi

HP@abhishek UCRT64 ~/Downloads (master)
$ |
```

8. Upload a 1 GB file to S3 using the CLI.

```

HP@abhishek UCRT64 ~/Downloads (master)
$ aws --version
aws-cli/2.37.4 Python/3.14.6 Windows/11 exe/AMD64

HP@abhishek UCRT64 ~/Downloads (master)
$ aws configure
AWS Access Key ID [*****53NC]: AKIA33NI4L46EAN653NC
AWS Secret Access Key [*****H42G]: 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
Default region name [us-east-1]: us-east-1
Default output format [json]: json

HP@abhishek UCRT64 ~/Downloads (master)
$ aws sts get-caller-identity
{
  "UserId": "AIDA33NI4L46HVX5TTOBC",
  "Account": "814787354428",
  "Arn": "arn:aws:iam::814787354428:user/S3-CrossAccount-User"
}

HP@abhishek UCRT64 ~/Downloads (master)
$ aws s3 ls
2026-10-08 17:01:08 abhishek-bash-s3-20261008
2026-10-08 15:09:30 abhishek-source-20261008

HP@abhishek UCRT64 ~/Downloads (master)
$ dd if=/dev/zero of=largefile.bin bs=1M count=1024
1024+0 records in
1024+0 records out
1073741824 bytes (1.1 GB, 1.0 GiB) copied, 5.13708 s, 209 MB/s

HP@abhishek UCRT64 ~/Downloads (master)
$ ls -lh largefile.bin
-rw-r--r-- 1 HP 197121 1.0G Oct  8 17:08 largefile.bin

```

```

HP@abhishek UCRT64 ~/Downloads (master)
$ aws s3 ls
2026-10-08 17:01:08 abhishek-bash-s3-20261008
2026-10-08 15:09:30 abhishek-source-20261008

HP@abhishek UCRT64 ~/Downloads (master)
$ aws s3 cp largefile.bin s3://abhishek-bash-s3-20261008/
upload: .\largefile.bin to s3://abhishek-bash-s3-20261008/largefile.bin

HP@abhishek UCRT64 ~/Downloads (master)
$ aws s3 ls s3://abhishek-bash-s3-20261008/
2026-10-08 17:22:34 1073741824 largefile.bin

HP@abhishek UCRT64 ~/Downloads (master)
$

```

abhishek-bash-s3-20261008 [Info](#)

[Objects](#) | [Metadata](#) | [Properties](#) | [Permissions](#) | [Metrics](#) | [Management](#) | [File systems](#) | [Access Points](#)

Objects (1)

Objects are the fundamental entities stored in Amazon S3. You can use [Amazon S3 inventory](#) to get a list of all objects in your bucket. For others to access your objects, you'll need to explicitly grant them permissions. [Learn more](#)

Find objects by prefix

☐	Name	Type	Last modified	Size	Storage class
☐	largefile.bin	bin	October 8, 2026, 17:22:34 (UTC+05:30)	1.0 GB	Standard