



Metasploitable

Report generated by Nessus™

Wed, 10 Jan 2024 11:16:28 EST

TABLE OF CONTENTS

Vulnerabilities by Plugin

• 20007 (2) - SSL Version 2 and 3 Protocol Detection.....	7
• 32321 (2) - Debian OpenSSH/OpenSSL Package Random Number Generator Weakness (SSL check).....	10
• 11356 (1) - NFS Exported Share Information Disclosure.....	12
• 32314 (1) - Debian OpenSSH/OpenSSL Package Random Number Generator Weakness.....	14
• 33850 (1) - Unix Operating System Unsupported Version Detection.....	16
• 51988 (1) - Bind Shell Backdoor Detection.....	17
• 61708 (1) - VNC Server 'password' Password.....	18
• 171340 (1) - Apache Tomcat SEoL (<= 5.5.x).....	19
• 42873 (2) - SSL Medium Strength Cipher Suites Supported (SWEET32).....	20
• 10205 (1) - rlogin Service Detection.....	22
• 42256 (1) - NFS Shares World Readable.....	23
• 90509 (1) - Samba Badlock Vulnerability.....	24
• 136769 (1) - ISC BIND Service Downgrade / Reflected DoS.....	26
• 15901 (2) - SSL Certificate Expiry.....	28
• 45411 (2) - SSL Certificate with Wrong Hostname.....	30
• 51192 (2) - SSL Certificate Cannot Be Trusted.....	32
• 57582 (2) - SSL Self-Signed Certificate.....	34
• 65821 (2) - SSL RC4 Cipher Suites Supported (Bar Mitzvah).....	36
• 104743 (2) - TLS Version 1.0 Protocol Detection.....	39
• 11213 (1) - HTTP TRACE / TRACK Methods Allowed.....	41
• 12085 (1) - Apache Tomcat Default Files.....	44
• 26928 (1) - SSL Weak Cipher Suites Supported.....	46
• 31705 (1) - SSL Anonymous Cipher Suites Supported.....	48
• 42263 (1) - Unencrypted Telnet Server.....	50
• 52611 (1) - SMTP Service STARTTLS Plaintext Command Injection.....	52
• 57608 (1) - SMB Signing not required.....	54
• 81606 (1) - SSL/TLS EXPORT_RSA <= 512-bit Cipher Suites Supported (FREAK).....	56

• 89058 (1) - SSL DROWN Attack Vulnerability (Decrypting RSA with Obsolete and Weakened eNcryption).....	58
• 90317 (1) - SSH Weak Algorithms Supported.....	60
• 136808 (1) - ISC BIND Denial of Service.....	61
• 139915 (1) - ISC BIND 9.x < 9.11.22, 9.12.x < 9.16.6, 9.17.x < 9.17.4 DoS.....	63
• 78479 (2) - SSLv3 Padding Oracle On Downgraded Legacy Encryption Vulnerability (POODLE).....	65
• 10407 (1) - X Server Detection.....	67
• 70658 (1) - SSH Server CBC Mode Ciphers Enabled.....	68
• 71049 (1) - SSH Weak MAC Algorithms Enabled.....	70
• 83738 (1) - SSL/TLS EXPORT_DHE <= 512-bit Export Cipher Suites Supported (Logjam).....	71
• 83875 (1) - SSL/TLS Diffie-Hellman Modulus <= 1024 Bits (Logjam).....	73
• 153953 (1) - SSH Weak Key Exchange Algorithms Enabled.....	75
• 11219 (25) - Nessus SYN scanner.....	77
• 11111 (10) - RPC Services Enumeration.....	80
• 22964 (9) - Service Detection.....	83
• 11154 (3) - Unknown Service Detection: Banner Retrieval.....	85
• 10092 (2) - FTP Server Detection.....	87
• 10107 (2) - HTTP Server Type and Version.....	88
• 10863 (2) - SSL Certificate Information.....	89
• 11002 (2) - DNS Server Detection.....	92
• 11011 (2) - Microsoft Windows SMB Service Detection.....	93
• 21643 (2) - SSL Cipher Suites Supported.....	94
• 22227 (2) - RMI Registry Detection.....	96
• 24260 (2) - HyperText Transfer Protocol (HTTP) Information.....	97
• 45410 (2) - SSL Certificate 'commonName' Mismatch.....	100
• 50845 (2) - OpenSSL Detection.....	101
• 56984 (2) - SSL / TLS Versions Supported.....	102
• 57041 (2) - SSL Perfect Forward Secrecy Cipher Suites Supported.....	103
• 62563 (2) - SSL Compression Methods Supported.....	105
• 70544 (2) - SSL Cipher Block Chaining Cipher Suites Supported.....	106

• 156899 (2) - SSL/TLS Recommended Cipher Suites.....	108
• 10028 (1) - DNS Server BIND version Directive Remote Version Detection.....	111
• 10114 (1) - ICMP Timestamp Request Remote Date Disclosure.....	112
• 10150 (1) - Windows NetBIOS / SMB Remote Host Information Disclosure.....	113
• 10223 (1) - RPC portmapper Service Detection.....	114
• 10263 (1) - SMTP Server Detection.....	115
• 10267 (1) - SSH Server Type and Version Information.....	116
• 10281 (1) - Telnet Server Detection.....	117
• 10287 (1) - Traceroute Information.....	118
• 10342 (1) - VNC Software Detection.....	119
• 10397 (1) - Microsoft Windows SMB LanMan Pipe Server Listing Disclosure.....	120
• 10437 (1) - NFS Share Export List.....	121
• 10719 (1) - MySQL Server Detection.....	122
• 10785 (1) - Microsoft Windows SMB NativeLanManager Remote System Information Disclosure.....	123
• 10881 (1) - SSH Protocol Versions Supported.....	124
• 11153 (1) - Service Detection (HELP Request).....	125
• 11422 (1) - Web Server Unconfigured - Default Install Page Present.....	126
• 11424 (1) - WebDAV Detection.....	127
• 11819 (1) - TFTP Daemon Detection.....	128
• 11936 (1) - OS Identification.....	129
• 17975 (1) - Service Detection (GET request).....	131
• 18261 (1) - Apache Banner Linux Distribution Disclosure.....	132
• 19288 (1) - VNC Server Security Type Detection.....	133
• 19506 (1) - Nessus Scan Information.....	134
• 20108 (1) - Web Server / Application favicon.ico Vendor Fingerprinting.....	136
• 21745 (1) - OS Security Patch Assessment Failed.....	137
• 25220 (1) - TCP/IP Timestamps Supported.....	138
• 25240 (1) - Samba Server Detection.....	139
• 26024 (1) - PostgreSQL Server Detection.....	140

• 35371 (1) - DNS Server hostname.bind Map Hostname Disclosure.....	141
• 35716 (1) - Ethernet Card Manufacturer Detection.....	142
• 39446 (1) - Apache Tomcat Detection.....	143
• 39519 (1) - Backported Security Patch Detection (FTP).....	144
• 39520 (1) - Backported Security Patch Detection (SSH).....	145
• 39521 (1) - Backported Security Patch Detection (WWW).....	146
• 42088 (1) - SMTP Service STARTTLS Command Support.....	147
• 45590 (1) - Common Platform Enumeration (CPE).....	149
• 48204 (1) - Apache HTTP Server Version.....	151
• 48243 (1) - PHP Version Detection.....	152
• 51891 (1) - SSL Session Resume Supported.....	153
• 52703 (1) - vsftpd Detection.....	154
• 53335 (1) - RPC portmapper (TCP).....	155
• 54615 (1) - Device Type.....	156
• 65792 (1) - VNC Server Unencrypted Communication Detection.....	157
• 66334 (1) - Patch Report.....	158
• 70657 (1) - SSH Algorithms and Languages Supported.....	159
• 84574 (1) - Backported Security Patch Detection (PHP).....	161
• 86420 (1) - Ethernet MAC Addresses.....	162
• 96982 (1) - Server Message Block (SMB) Protocol Version 1 Enabled (uncredentialed check).....	163
• 100871 (1) - Microsoft Windows SMB Versions Supported (remote check).....	165
• 104410 (1) - Target Credential Status by Authentication Protocol - Failure for Provided Credentials.....	166
• 104887 (1) - Samba Version.....	168
• 106716 (1) - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check).....	169
• 118224 (1) - PostgreSQL STARTTLS Support.....	170
• 135860 (1) - WMI Not Available.....	172
• 149334 (1) - SSH Password Authentication Accepted.....	173
• 153588 (1) - SSH SHA-1 HMAC Algorithms Enabled.....	174
• 181418 (1) - OpenSSH Detection.....	175

Vulnerabilities by Plugin

20007 (2) - SSL Version 2 and 3 Protocol Detection

Synopsis

The remote service encrypts traffic using a protocol with known weaknesses.

Description

The remote service accepts connections encrypted using SSL 2.0 and/or SSL 3.0. These versions of SSL are affected by several cryptographic flaws, including:

- An insecure padding scheme with CBC ciphers.
- Insecure session renegotiation and resumption schemes.

An attacker can exploit these flaws to conduct man-in-the-middle attacks or to decrypt communications between the affected service and clients.

Although SSL/TLS has a secure means for choosing the highest supported version of the protocol (so that these versions will be used only if the client or server support nothing better), many web browsers implement this in an unsafe way that allows an attacker to downgrade a connection (such as in POODLE). Therefore, it is recommended that these protocols be disabled entirely.

NIST has determined that SSL 3.0 is no longer acceptable for secure communications. As of the date of enforcement found in PCI DSS v3.1, any version of SSL will not meet the PCI SSC's definition of 'strong cryptography'.

See Also

<https://www.schneier.com/academic/paperfiles/paper-ssl.pdf>

<http://www.nessus.org/u?b06c7e95>

<http://www.nessus.org/u?247c4540>

<https://www.openssl.org/~bodo/ssl-poodle.pdf>

<http://www.nessus.org/u?5d15ba70>

<https://www.imperialviolet.org/2014/10/14/poodle.html>

<https://tools.ietf.org/html/rfc7507>

<https://tools.ietf.org/html/rfc7568>

Solution

Consult the application's documentation to disable SSL 2.0 and 3.0.

Use TLS 1.2 (with approved cipher suites) or higher instead.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C/I:C/A:C)

Plugin Information

Published: 2005/10/12, Modified: 2022/04/04

Plugin Output

192.168.100.22 (tcp/25/smtp)

- SSLv2 is enabled and the server supports at least one cipher.

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EXP-RC2-CBC-MD5		RSA (512)	RSA	RC2-CBC (40)	MD5
export					
EXP-RC4-MD5		RSA (512)	RSA	RC4 (40)	MD5
export					

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DES-CBC3-MD5		RSA	RSA	3DES-CBC (168)	MD5

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
RC4-MD5		RSA	RSA	RC4 (128)	MD5

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

- SSLv3 is enabled and the server supports at least one cipher.

Explanation: TLS 1.0 and SSL 3.0 cipher suites may be used with SSLv3

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EXP-EDH-RSA-DES-CBC-SHA		DH (512)	RSA	DES-CBC (40)	
SHA1 export					
EDH-RSA-DES-CBC-SHA		DH	RSA	DES-CBC (56)	SHA
[...]					

- SSLv3 is enabled and the server supports at least one cipher.
 Explanation: TLS 1.0 and SSL 3.0 cipher suites may be used with SSLv3

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
EDH-RSA-DES-CBC3-SHA		DH	RSA	3DES-CBC (168)	
SHA1					
DES-CBC3-SHA		RSA	RSA	3DES-CBC (168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
DHE-RSA-AES128-SHA		DH	RSA	AES-CBC (128)	
SHA1					
DHE-RSA-AES256-SHA		DH	RSA	AES-CBC (256)	
SHA1					
AES128-SHA		RSA	RSA	AES-CBC (128)	
SHA1					
AES256-SHA		RSA	RSA	AES-CBC (256)	
SHA1					
RC4-SHA		RSA	RSA	RC4 (128)	
SHA1					

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

32321 (2) - Debian OpenSSH/OpenSSL Package Random Number Generator Weakness (SSL check)

Synopsis

The remote SSL certificate uses a weak key.

Description

The remote x509 certificate on the remote SSL server has been generated on a Debian or Ubuntu system which contains a bug in the random number generator of its OpenSSL library.

The problem is due to a Debian packager removing nearly all sources of entropy in the remote version of OpenSSL.

An attacker can easily obtain the private part of the remote key and use this to decipher the remote session or set up a man in the middle attack.

See Also

<http://www.nessus.org/u?107f9bdc>

<http://www.nessus.org/u?f14f4224>

Solution

Consider all cryptographic material generated on the remote host to be guessable. In particular, all SSH, SSL and OpenVPN key material should be re-generated.

Risk Factor

Critical

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	29179
CVE	CVE-2008-0166
XREF	CWE:310

Exploitable With

Core Impact (true)

Plugin Information

Published: 2008/05/15, Modified: 2020/11/16

Plugin Output

192.168.100.22 (tcp/25/smtp)
192.168.100.22 (tcp/5432/postgresql)

11356 (1) - NFS Exported Share Information Disclosure

Synopsis

It is possible to access NFS shares on the remote host.

Description

At least one of the NFS shares exported by the remote server could be mounted by the scanning host. An attacker may be able to leverage this to read (and possibly write) files on remote host.

Solution

Configure NFS on the remote host so that only authorized hosts can mount its remote shares.

Risk Factor

Critical

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

References

CVE	CVE-1999-0170
CVE	CVE-1999-0211
CVE	CVE-1999-0554

Exploitable With

Metasploit (true)

Plugin Information

Published: 2003/03/12, Modified: 2023/08/30

Plugin Output

192.168.100.22 (udp/2049/rpc-nfs)

The following NFS shares could be mounted :

```
+ /
+ Contents of / :
- .
- ..
- bin
- boot
```

- cdrom
- dev
- etc
- home
- initrd
- initrd.img
- lib
- lost+found
- media
- mnt
- nohup.out
- opt
- proc
- root
- sbin
- srv
- sys
- tmp
- usr
- var
- vmlinuz

32314 (1) - Debian OpenSSH/OpenSSL Package Random Number Generator Weakness

Synopsis

The remote SSH host keys are weak.

Description

The remote SSH host key has been generated on a Debian or Ubuntu system which contains a bug in the random number generator of its OpenSSL library.

The problem is due to a Debian packager removing nearly all sources of entropy in the remote version of OpenSSL.

An attacker can easily obtain the private part of the remote key and use this to set up decipher the remote session or set up a man in the middle attack.

See Also

<http://www.nessus.org/u?107f9bdc>

<http://www.nessus.org/u?f14f4224>

Solution

Consider all cryptographic material generated on the remote host to be guessable. In particular, all SSH, SSL and OpenVPN key material should be re-generated.

Risk Factor

Critical

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	29179
CVE	CVE-2008-0166
XREF	CWE:310

Exploitable With

Core Impact (true)

Plugin Information

Published: 2008/05/14, Modified: 2018/11/15

Plugin Output

192.168.100.22 (tcp/22/ssh)

33850 (1) - Unix Operating System Unsupported Version Detection

Synopsis

The operating system running on the remote host is no longer supported.

Description

According to its self-reported version number, the Unix operating system running on the remote host is no longer supported.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it is likely to contain security vulnerabilities.

Solution

Upgrade to a version of the Unix operating system that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C/I:C/A:C)

References

XREF IAVA:0001-A-0502

XREF IAVA:0001-A-0648

Plugin Information

Published: 2008/08/08, Modified: 2023/10/18

Plugin Output

192.168.100.22 (tcp/0)

```
Ubuntu 8.04 support ended on 2011-05-12 (Desktop) / 2013-05-09 (Server).  
Upgrade to Ubuntu 23.04 / LTS 22.04 / LTS 20.04 .
```

For more information, see : <https://wiki.ubuntu.com/Releases>

51988 (1) - Bind Shell Backdoor Detection

Synopsis

The remote host may have been compromised.

Description

A shell is listening on the remote port without any authentication being required. An attacker may use it by connecting to the remote port and sending commands directly.

Solution

Verify if the remote host has been compromised, and reinstall the system if necessary.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2011/02/15, Modified: 2022/04/11

Plugin Output

192.168.100.22 (tcp/1524/wild_shell)

```
Nessus was able to execute the command "id" using the
following request :
```

```
This produced the following truncated output (limited to 10 lines) :
----- snip -----
root@metasploitable:/# uid=0(root) gid=0(root) groups=0(root)
root@metasploitable:/#
----- snip -----
```

61708 (1) - VNC Server 'password' Password

Synopsis

A VNC server running on the remote host is secured with a weak password.

Description

The VNC server running on the remote host is secured with a weak password. Nessus was able to login using VNC authentication and a password of 'password'. A remote, unauthenticated attacker could exploit this to take control of the system.

Solution

Secure the VNC service with a strong password.

Risk Factor

Critical

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2012/08/29, Modified: 2015/09/24

Plugin Output

192.168.100.22 (tcp/5900/vnc)

```
Nessus logged in using a password of "password".
```

171340 (1) - Apache Tomcat SEoL (<= 5.5.x)

Synopsis

An unsupported version of Apache Tomcat is installed on the remote host.

Description

According to its version, Apache Tomcat is less than or equal to 5.5.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

See Also

<https://tomcat.apache.org/tomcat-55-eol.html>

Solution

Upgrade to a version of Apache Tomcat that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2023/02/10, Modified: 2023/11/03

Plugin Output

192.168.100.22 (tcp/8180/www)

```
URL : http://192.168.100.22:8180/
Installed version : 5.5
Security End of Life : September 30, 2012
Time since Security End of Life (Est.) : >= 11 years
```

42873 (2) - SSL Medium Strength Cipher Suites Supported (SWEET32)

Synopsis

The remote service supports the use of medium strength SSL ciphers.

Description

The remote host supports the use of SSL ciphers that offer medium strength encryption. Nessus regards medium strength as any encryption that uses key lengths at least 64 bits and less than 112 bits, or else that uses the 3DES encryption suite.

Note that it is considerably easier to circumvent medium strength encryption if the attacker is on the same physical network.

See Also

<https://www.openssl.org/blog/blog/2016/08/24/sweet32/>

<https://sweet32.info>

Solution

Reconfigure the affected application if possible to avoid use of medium strength ciphers.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

References

CVE CVE-2016-2183

Plugin Information

Published: 2009/11/23, Modified: 2021/02/03

Plugin Output

192.168.100.22 (tcp/25/smtp)

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DES-CBC3-MD5	0x07, 0x00, 0xC0	RSA	RSA	3DES-CBC(168)	MD5
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DH	RSA	3DES-CBC(168)	
SHA1					
ADH-DES-CBC3-SHA	0x00, 0x1B	DH	None	3DES-CBC(168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	
SHA1					

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

192.168.100.22 (tcp/5432/postgresql)

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DH	RSA	3DES-CBC(168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	
SHA1					

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

10205 (1) - rlogin Service Detection

Synopsis

The rlogin service is running on the remote host.

Description

The rlogin service is running on the remote host. This service is vulnerable since data is passed between the rlogin client and server in cleartext. A man-in-the-middle attacker can exploit this to sniff logins and passwords. Also, it may allow poorly authenticated logins without passwords. If the host is vulnerable to TCP sequence number guessing (from any network) or IP spoofing (including ARP hijacking on a local network) then it may be possible to bypass authentication.

Finally, rlogin is an easy way to turn file-write access into full logins through the .rhosts or rhosts.equiv files.

Solution

Comment out the 'login' line in /etc/inetd.conf and restart the inetd process. Alternatively, disable this service and use SSH instead.

Risk Factor

High

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0651

Exploitable With

Metasploit (true)

Plugin Information

Published: 1999/08/30, Modified: 2022/04/11

Plugin Output

192.168.100.22 (tcp/513/rlogin)

42256 (1) - NFS Shares World Readable

Synopsis

The remote NFS server exports world-readable shares.

Description

The remote NFS server is exporting one or more shares without restricting access (based on hostname, IP, or IP range).

See Also

<http://www.tldp.org/HOWTO/NFS-HOWTO/security.html>

Solution

Place the appropriate restrictions on all NFS shares.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2009/10/26, Modified: 2020/05/05

Plugin Output

192.168.100.22 (tcp/2049/rpc-nfs)

The following shares have no access restrictions :

/ *

90509 (1) - Samba Badlock Vulnerability

Synopsis

An SMB server running on the remote host is affected by the Badlock vulnerability.

Description

The version of Samba, a CIFS/SMB server for Linux and Unix, running on the remote host is affected by a flaw, known as Badlock, that exists in the Security Account Manager (SAM) and Local Security Authority (Domain Policy) (LSAD) protocols due to improper authentication level negotiation over Remote Procedure Call (RPC) channels. A man-in-the-middle attacker who is able to intercept the traffic between a client and a server hosting a SAM database can exploit this flaw to force a downgrade of the authentication level, which allows the execution of arbitrary Samba network calls in the context of the intercepted user, such as viewing or modifying sensitive security data in the Active Directory (AD) database or disabling critical services.

See Also

<http://badlock.org>

<https://www.samba.org/samba/security/CVE-2016-2118.html>

Solution

Upgrade to Samba version 4.2.11 / 4.3.8 / 4.4.2 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:R/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:U/RL:OF/RC:C)

References

BID	86002
CVE	CVE-2016-2118
XREF	CERT:813296

Plugin Information

Published: 2016/04/13, Modified: 2019/11/20

Plugin Output

192.168.100.22 (tcp/445/cifs)

```
Nessus detected that the Samba Badlock patch has not been applied.
```

136769 (1) - ISC BIND Service Downgrade / Reflected DoS

Synopsis

The remote name server is affected by Service Downgrade / Reflected DoS vulnerabilities.

Description

According to its self-reported version, the instance of ISC BIND 9 running on the remote name server is affected by performance downgrade and Reflected DoS vulnerabilities. This is due to BIND DNS not sufficiently limiting the number fetches which may be performed while processing a referral response.

An unauthenticated, remote attacker can exploit this to cause degrade the service of the recursive server or to use the affected server as a reflector in a reflection attack.

See Also

<https://kb.isc.org/docs/cve-2020-8616>

Solution

Upgrade to the ISC BIND version referenced in the vendor advisory.

Risk Factor

Medium

CVSS v3.0 Base Score

8.6 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

7.5 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2020-8616
XREF	IAVA:2020-A-0217-S

Plugin Information

Published: 2020/05/22, Modified: 2020/06/26

Plugin Output

192.168.100.22 (udp/53/dns)

```
Installed version : 9.4.2
Fixed version    : 9.11.19
```

15901 (2) - SSL Certificate Expiry

Synopsis

The remote server's SSL certificate has already expired.

Description

This plugin checks expiry dates of certificates associated with SSL- enabled services on the target and reports whether any have already expired.

Solution

Purchase or generate a new SSL certificate to replace the existing one.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

Plugin Information

Published: 2004/12/03, Modified: 2021/02/03

Plugin Output

192.168.100.22 (tcp/25/smtp)

```
The SSL certificate has already expired :
```

```
Subject      : C=XX, ST=There is no such thing outside US, L=Everywhere, O=OCOSA,
OU=Office for Complication of Otherwise Simple Affairs, CN=ubuntu804-base.localdomain,
emailAddress=root@ubuntu804-base.localdomain
Issuer       : C=XX, ST=There is no such thing outside US, L=Everywhere, O=OCOSA,
OU=Office for Complication of Otherwise Simple Affairs, CN=ubuntu804-base.localdomain,
emailAddress=root@ubuntu804-base.localdomain
Not valid before : Mar 17 14:07:45 2010 GMT
Not valid after  : Apr 16 14:07:45 2010 GMT
```

192.168.100.22 (tcp/5432/postgresql)

```
The SSL certificate has already expired :
```

```
Subject      : C=XX, ST=There is no such thing outside US, L=Everywhere, O=OCOSA,  
OU=Office for Complication of Otherwise Simple Affairs, CN=ubuntu804-base.localdomain,  
emailAddress=root@ubuntu804-base.localdomain  
Issuer       : C=XX, ST=There is no such thing outside US, L=Everywhere, O=OCOSA,  
OU=Office for Complication of Otherwise Simple Affairs, CN=ubuntu804-base.localdomain,  
emailAddress=root@ubuntu804-base.localdomain  
Not valid before : Mar 17 14:07:45 2010 GMT  
Not valid after  : Apr 16 14:07:45 2010 GMT
```

45411 (2) - SSL Certificate with Wrong Hostname

Synopsis

The SSL certificate for this service is for a different host.

Description

The 'commonName' (CN) attribute of the SSL certificate presented for this service is for a different machine.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

Plugin Information

Published: 2010/04/03, Modified: 2020/04/27

Plugin Output

192.168.100.22 (tcp/25/smtp)

```
The identities known by Nessus are :
```

```
192.168.100.22
192.168.100.22
```

```
The Common Name in the certificate is :
```

```
ubuntu804-base.localdomain
```

192.168.100.22 (tcp/5432/postgresql)

```
The identities known by Nessus are :
```

```
192.168.100.22
192.168.100.22
```

The Common Name in the certificate is :

ubuntu804-base.localdomain

51192 (2) - SSL Certificate Cannot Be Trusted

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2010/12/15, Modified: 2020/04/27

Plugin Output

192.168.100.22 (tcp/25/smtp)

The following certificate was part of the certificate chain sent by the remote host, but it has expired :

```
| -Subject   : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain  
| -Not After : Apr 16 14:07:45 2010 GMT
```

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

```
| -Subject : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain  
| -Issuer  : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain
```

192.168.100.22 (tcp/5432/postgresql)

The following certificate was part of the certificate chain sent by the remote host, but it has expired :

```
| -Subject   : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain  
| -Not After : Apr 16 14:07:45 2010 GMT
```

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

```
| -Subject : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain  
| -Issuer  : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain
```

57582 (2) - SSL Self-Signed Certificate

Synopsis

The SSL certificate chain for this service ends in an unrecognized self-signed certificate.

Description

The X.509 certificate chain for this service is not signed by a recognized certificate authority. If the remote host is a public host in production, this nullifies the use of SSL as anyone could establish a man-in-the-middle attack against the remote host.

Note that this plugin does not check for certificate chains that end in a certificate that is not self-signed, but is signed by an unrecognized certificate authority.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2012/01/17, Modified: 2022/06/14

Plugin Output

192.168.100.22 (tcp/25/smtp)

The following certificate was found at the top of the certificate chain sent by the remote host, but is self-signed and was not found in the list of known certificate authorities :

```
| -Subject : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain
```

192.168.100.22 (tcp/5432/postgresql)

The following certificate was found at the top of the certificate chain sent by the remote host, but is self-signed and was not found in the list of known certificate authorities :

```
|-Subject : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain
```

65821 (2) - SSL RC4 Cipher Suites Supported (Bar Mitzvah)

Synopsis

The remote service supports the use of the RC4 cipher.

Description

The remote host supports the use of RC4 in one or more cipher suites.

The RC4 cipher is flawed in its generation of a pseudo-random stream of bytes so that a wide variety of small biases are introduced into the stream, decreasing its randomness.

If plaintext is repeatedly encrypted (e.g., HTTP cookies), and an attacker is able to obtain many (i.e., tens of millions) ciphertexts, the attacker may be able to derive the plaintext.

See Also

<https://www.rc4nomore.com/>

<http://www.nessus.org/u?ac7327a0>

<http://cr.yp.to/talks/2013.03.12/slides.pdf>

<http://www.isg.rhul.ac.uk/tls/>

https://www.imperva.com/docs/HII_Attacking_SSL_when_using_RC4.pdf

Solution

Reconfigure the affected application, if possible, to avoid use of RC4 ciphers. Consider using TLS 1.2 with AES-GCM suites subject to browser and web server support.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

5.4 (CVSS:3.0/E:U/RL:X/RC:C)

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:ND/RC:C)

References

BID	58796
BID	73684
CVE	CVE-2013-2566
CVE	CVE-2015-2808

Plugin Information

Published: 2013/04/05, Modified: 2021/02/03

Plugin Output

192.168.100.22 (tcp/25/smtp)

List of RC4 cipher suites supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
EXP-RC4-MD5 export	0x02, 0x00, 0x80	RSA (512)	RSA	RC4 (40)	MD5
EXP-ADH-RC4-MD5 export	0x00, 0x17	DH (512)	None	RC4 (40)	MD5
EXP-RC4-MD5 export	0x00, 0x03	RSA (512)	RSA	RC4 (40)	MD5

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
RC4-MD5	0x01, 0x00, 0x80	RSA	RSA	RC4 (128)	MD5
ADH-RC4-MD5	0x00, 0x18	DH	None	RC4 (128)	MD5
RC4-MD5	0x00, 0x04	RSA	RSA	RC4 (128)	MD5
RC4-SHA	0x00, 0x05	RSA	RSA	RC4 (128)	MD5

SHA1

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

192.168.100.22 (tcp/5432/postgresql)

List of RC4 cipher suites supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
RC4-SHA	0x00, 0x05	RSA	RSA	RC4 (128)	

SHA1

The fields above are :

```
{Tenable ciphername}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}
```

104743 (2) - TLS Version 1.0 Protocol Detection

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.0. TLS 1.0 has a number of cryptographic design flaws. Modern implementations of TLS 1.0 mitigate these problems, but newer versions of TLS like 1.2 and 1.3 are designed against these flaws and should be used whenever possible.

As of March 31, 2020, Endpoints that aren't enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

PCI DSS v3.2 requires that TLS 1.0 be disabled entirely by June 30, 2018, except for POS POI terminals (and the SSL/TLS termination points to which they connect) that can be verified as not being susceptible to any known exploits.

See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

Solution

Enable support for TLS 1.2 and 1.3, and disable support for TLS 1.0.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

CVSS v2.0 Base Score

6.1 (CVSS2#AV:N/AC:H/Au:N/C:C/I:P/A:N)

References

XREF CWE:327

Plugin Information

Published: 2017/11/22, Modified: 2023/04/19

Plugin Output

192.168.100.22 (tcp/25/smtp)

```
TLsv1 is enabled and the server supports at least one cipher.
```

192.168.100.22 (tcp/5432/postgresql)

```
TLsv1 is enabled and the server supports at least one cipher.
```


11213 (1) - HTTP TRACE / TRACK Methods Allowed

Synopsis

Debugging functions are enabled on the remote web server.

Description

The remote web server supports the TRACE and/or TRACK methods. TRACE and TRACK are HTTP methods that are used to debug web server connections.

See Also

<http://www.nessus.org/u?e979b5cb>

<http://www.apacheweek.com/issues/03-01-24>

<https://download.oracle.com/sunalerts/1000718.1.html>

Solution

Disable these HTTP methods. Refer to the plugin output for more information.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	9506
BID	9561
BID	11604

BID	33374
BID	37995
CVE	CVE-2003-1567
CVE	CVE-2004-2320
CVE	CVE-2010-0386
XREF	CERT:288308
XREF	CERT:867593
XREF	CWE:16
XREF	CWE:200

Plugin Information

Published: 2003/01/23, Modified: 2023/10/27

Plugin Output

192.168.100.22 (tcp/80/www)

To disable these methods, add the following lines for each virtual host in your configuration file :

```
RewriteEngine on
RewriteCond %{REQUEST_METHOD} ^(TRACE|TRACK)
RewriteRule .* - [F]
```

Alternatively, note that Apache versions 1.3.34, 2.0.55, and 2.2 support disabling the TRACE method natively via the 'TraceEnable' directive.

Nessus sent the following TRACE request : \n\n----- snip
-----\nTRACE /Nessus1014433880.html HTTP/1.1

Connection: Close
Host: 192.168.100.22
Pragma: no-cache
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
Accept-Language: en
Accept-Charset: iso-8859-1,*,utf-8

----- snip -----\n\nand received the
following response from the remote server : \n\n----- snip
-----\nHTTP/1.1 200 OK

Date: Wed, 10 Jan 2024 08:32:30 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
Keep-Alive: timeout=15, max=100
Connection: Keep-Alive
Transfer-Encoding: chunked
Content-Type: message/http

TRACE /Nessus1014433880.html HTTP/1.1
Connection: Keep-Alive
Host: 192.168.100.22
Pragma: no-cache
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
Accept-Language: en
Accept-Charset: iso-8859-1,*,utf-8

```
----- snip -----\n
```

12085 (1) - Apache Tomcat Default Files

Synopsis

The remote web server contains default files.

Description

The default error page, default index page, example JSPs and/or example servlets are installed on the remote Apache Tomcat server. These files should be removed as they may help an attacker uncover information about the remote Tomcat install or host itself.

See Also

<http://www.nessus.org/u?4cb3b4dd>

https://www.owasp.org/index.php/Securing_tomcat

Solution

Delete the default index page and remove the example JSP and servlets. Follow the Tomcat or OWASP instructions to replace or modify the default error page.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2004/03/02, Modified: 2019/08/12

Plugin Output

192.168.100.22 (tcp/8180/www)

The following default files were found :

<http://192.168.100.22:8180/tomcat-docs/index.html>

The server is not configured to return a custom page in the event of a client requesting a non-existent resource.

This may result in a potential disclosure of sensitive information about the server to attackers.

26928 (1) - SSL Weak Cipher Suites Supported

Synopsis

The remote service supports the use of weak SSL ciphers.

Description

The remote host supports the use of SSL ciphers that offer weak encryption.

Note: This is considerably easier to exploit if the attacker is on the same physical network.

See Also

<http://www.nessus.org/u?6527892d>

Solution

Reconfigure the affected application, if possible to avoid the use of weak ciphers.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

References

XREF	CWE:326
XREF	CWE:327
XREF	CWE:720
XREF	CWE:753
XREF	CWE:803
XREF	CWE:928
XREF	CWE:934

Plugin Information

Published: 2007/10/08, Modified: 2021/02/03

Plugin Output

192.168.100.22 (tcp/25/smtp)

Here is the list of weak SSL ciphers supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EXP-RC2-CBC-MD5 export	0x04, 0x00, 0x80	RSA (512)	RSA	RC2-CBC (40)	MD5
EXP-RC4-MD5 export	0x02, 0x00, 0x80	RSA (512)	RSA	RC4 (40)	MD5
EXP-EDH-RSA-DES-CBC-SHA SHA1 export	0x00, 0x14	DH (512)	RSA	DES-CBC (40)	
EDH-RSA-DES-CBC-SHA SHA1	0x00, 0x15	DH	RSA	DES-CBC (56)	
EXP-ADH-DES-CBC-SHA SHA1 export	0x00, 0x19	DH (512)	None	DES-CBC (40)	
EXP-ADH-RC4-MD5 export	0x00, 0x17	DH (512)	None	RC4 (40)	MD5
ADH-DES-CBC-SHA SHA1	0x00, 0x1A	DH	None	DES-CBC (56)	
EXP-DES-CBC-SHA SHA1 export	0x00, 0x08	RSA (512)	RSA	DES-CBC (40)	
EXP-RC2-CBC-MD5 export	0x00, 0x06	RSA (512)	RSA	RC2-CBC (40)	MD5
EXP-RC4-MD5 export	0x00, 0x03	RSA (512)	RSA	RC4 (40)	MD5
DES-CBC-SHA SHA1	0x00, 0x09	RSA	RSA	DES-CBC (56)	

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

31705 (1) - SSL Anonymous Cipher Suites Supported

Synopsis

The remote service supports the use of anonymous SSL ciphers.

Description

The remote host supports the use of anonymous SSL ciphers. While this enables an administrator to set up a service that encrypts traffic without having to generate and configure SSL certificates, it offers no way to verify the remote host's identity and renders the service vulnerable to a man-in-the-middle attack.

Note: This is considerably easier to exploit if the attacker is on the same physical network.

See Also

<http://www.nessus.org/u?3a040ada>

Solution

Reconfigure the affected application if possible to avoid use of weak ciphers.

Risk Factor

Low

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

5.2 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	28482
CVE	CVE-2007-1858

Plugin Information

Published: 2008/03/28, Modified: 2023/10/27

Plugin Output

192.168.100.22 (tcp/25/smtp)

The following is a list of SSL anonymous ciphers supported by the remote TCP server :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EXP-ADH-DES-CBC-SHA SHA1 export	0x00, 0x19	DH (512)	None	DES-CBC (40)	
EXP-ADH-RC4-MD5 export	0x00, 0x17	DH (512)	None	RC4 (40)	MD5
ADH-DES-CBC-SHA SHA1	0x00, 0x1A	DH	None	DES-CBC (56)	

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
ADH-DES-CBC3-SHA SHA1	0x00, 0x1B	DH	None	3DES-CBC (168)	

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
ADH-AES128-SHA SHA1	0x00, 0x34	DH	None	AES-CBC (128)	
ADH-AES256-SHA SHA1	0x00, 0x3A	DH	None	AES-CBC (256)	
ADH-RC4-MD5	0x00, 0x18	DH	None	RC4 (128)	MD5

The fields above are :

```
{Tenable ciphertype}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

42263 (1) - Unencrypted Telnet Server

Synopsis

The remote Telnet server transmits traffic in cleartext.

[illegible]

The remote host is running a Telnet server over an unencrypted channel.

Using Telnet over an unencrypted channel is not recommended as logins, passwords, and commands are transferred in cleartext. This allows a remote, man-in-the-middle attacker to eavesdrop on a Telnet session to obtain credentials or other sensitive information and to modify traffic exchanged between a client and server.

SSH is preferred over Telnet since it protects credentials from eavesdropping and can tunnel additional data streams such as an X11 session.

Solution

Disable the Telnet service and use SSH instead.

Risk Factor	Impact	Control
1. Lack of industry connections	Reduced opportunities for partnerships and collaborations	Actively seek out and build relationships with industry leaders and potential partners
2. Limited marketing budget	Reduced visibility and awareness of the startup	Implement cost-effective marketing strategies, such as social media and content marketing
3. Limited product differentiation	Increased competition and lower profit margins	Conduct thorough market research to identify unique selling points and differentiate the product
4. Limited customer base	Reduced revenue and potential for growth	Implement targeted marketing campaigns and offer incentives to attract new customers
5. Limited cash flow	Reduced ability to fund operations and growth	Implement strict financial controls and seek out alternative funding sources

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2009/10/27, Modified: 2020/06/12

Plugin Output

192.168.100.22 (tcp/23/telnet)

```

Nessus collected the following banner from the remote Telnet server :

----- snip -----
_ _ _ _ _ | _ _ _ _ _ | _ _ _ _ _ | _ _ _ _ _ |
| ' _ _ _ _ _ / _ _ _ _ _ / _ _ _ _ _ | ' _ _ _ _ _ / _ _ _ _ _ | | | | | | | | | | | | | |
| | | | | _ _ _ _ _ | | | | | _ _ _ _ _ | | | | | _ _ _ _ _ |
| | | | | _ _ _ _ _ | . _ _ _ _ _ / | | | | | _ _ _ _ _ | . _ _ _ _ _ / |
| | | | | _ _ _ _ _ |

```

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

metasploitable login:

----- snip -----

52611 (1) - SMTP Service STARTTLS Plaintext Command Injection

Synopsis

The remote mail service allows plaintext command injection while negotiating an encrypted communications channel.

Description

The remote SMTP service contains a software flaw in its STARTTLS implementation that could allow a remote, unauthenticated attacker to inject commands during the plaintext protocol phase that will be executed during the ciphertext protocol phase.

Successful exploitation could allow an attacker to steal a victim's email or associated SASL (Simple Authentication and Security Layer) credentials.

See Also

<https://tools.ietf.org/html/rfc2487>

<https://www.securityfocus.com/archive/1/516901/30/0/threaded>

Solution

Contact the vendor to see if an update is available.

Risk Factor

Medium

CVSS v2.0 Base Score

4.0 (CVSS2#AV:N/AC:H/Au:N/C:P/I:P/A:N)

CVSS v2.0 Temporal Score

3.1 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	46767
CVE	CVE-2011-0411
CVE	CVE-2011-1430
CVE	CVE-2011-1431
CVE	CVE-2011-1432
CVE	CVE-2011-1506
CVE	CVE-2011-2165
XREF	CERT:555316

Plugin Information

Published: 2011/03/10, Modified: 2019/03/06

Plugin Output

192.168.100.22 (tcp/25/smtp)

```
Nessus sent the following two commands in a single packet :
```

```
STARTTLS\r\nRSET\r\n
```

```
And the server sent the following two responses :
```

```
220 2.0.0 Ready to start TLS
```

```
250 2.0.0 Ok
```

57608 (1) - SMB Signing not required

Synopsis

Signing is not required on the remote SMB server.

Description

Signing is not required on the remote SMB server. An unauthenticated, remote attacker can exploit this to conduct man-in-the-middle attacks against the SMB server.

See Also

<http://www.nessus.org/u?df39b8b3>

<http://technet.microsoft.com/en-us/library/cc731957.aspx>

<http://www.nessus.org/u?74b80723>

<https://www.samba.org/samba/docs/current/man-html/smb.conf.5.html>

<http://www.nessus.org/u?a3cac4ea>

Solution

Enforce message signing in the host's configuration. On Windows, this is found in the policy setting 'Microsoft network server: Digitally sign communications (always)'. On Samba, the setting is called 'server signing'. See the 'see also' links for further details.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

Plugin Information

Published: 2012/01/19, Modified: 2022/10/05

Plugin Output

192.168.100.22 (tcp/445/cifs)

81606 (1) - SSL/TLS EXPORT_RSA <= 512-bit Cipher Suites Supported (FREAK)

Synopsis

The remote host supports a set of weak ciphers.

Description

The remote host supports EXPORT_RSA cipher suites with keys less than or equal to 512 bits. An attacker can factor a 512-bit RSA modulus in a short amount of time.

A man-in-the-middle attacker may be able to downgrade the session to use EXPORT_RSA cipher suites (e.g. CVE-2015-0204). Thus, it is recommended to remove support for weak cipher suites.

See Also

<https://www.smacktls.com/#freak>

<https://www.openssl.org/news/secadv/20150108.txt>

<http://www.nessus.org/u?b78da2c4>

Solution

Reconfigure the service to remove support for EXPORT_RSA cipher suites.

Risk Factor

Medium

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

BID	71936
CVE	CVE-2015-0204
XREF	CERT:243585

Plugin Information

Published: 2015/03/04, Modified: 2021/02/03

Plugin Output

192.168.100.22 (tcp/25/smtp)

EXPORT_RSA cipher suites supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EXP-DES-CBC-SHA SHA1 export	0x00, 0x08	RSA (512)	RSA	DES-CBC (40)	
EXP-RC2-CBC-MD5 export	0x00, 0x06	RSA (512)	RSA	RC2-CBC (40)	MD5
EXP-RC4-MD5 export	0x00, 0x03	RSA (512)	RSA	RC4 (40)	MD5

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

89058 (1) - SSL DROWN Attack Vulnerability (Decrypting RSA with Obsolete and Weakened eNcryption)

Synopsis

The remote host may be affected by a vulnerability that allows a remote attacker to potentially decrypt captured TLS traffic.

Description

The remote host supports SSLv2 and therefore may be affected by a vulnerability that allows a cross-protocol Bleichenbacher padding oracle attack known as DROWN (Decrypting RSA with Obsolete and Weakened eNcryption). This vulnerability exists due to a flaw in the Secure Sockets Layer Version 2 (SSLv2) implementation, and it allows captured TLS traffic to be decrypted. A man-in-the-middle attacker can exploit this to decrypt the TLS connection by utilizing previously captured traffic and weak cryptography along with a series of specially crafted connections to an SSLv2 server that uses the same private key.

See Also

<https://drownattack.com/>

<https://drownattack.com/drown-attack-paper.pdf>

Solution

Disable SSLv2 and export grade cryptography cipher suites. Ensure that private keys are not used anywhere with server software that supports SSLv2 connections.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

5.2 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

BID 83733
CVE CVE-2016-0800
XREF CERT:583776

Plugin Information

Published: 2016/03/01, Modified: 2019/11/20

Plugin Output

192.168.100.22 (tcp/25/smtp)

The remote host is affected by SSL DROWN and supports the following vulnerable cipher suites :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
EXP-RC2-CBC-MD5 export	0x04, 0x00, 0x80	RSA(512)	RSA	RC2-CBC(40)	MD5
EXP-RC4-MD5 export	0x02, 0x00, 0x80	RSA(512)	RSA	RC4(40)	MD5

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
RC4-MD5	0x01, 0x00, 0x80	RSA	RSA	RC4(128)	MD5

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

90317 (1) - SSH Weak Algorithms Supported

Synopsis

The remote SSH server is configured to allow weak encryption algorithms or no algorithm at all.

Description

Nessus has detected that the remote SSH server is configured to use the Arcfour stream cipher or no cipher at all. RFC 4253 advises against using Arcfour due to an issue with weak keys.

See Also

<https://tools.ietf.org/html/rfc4253#section-6.3>

Solution

Contact the vendor or consult product documentation to remove the weak ciphers.

Risk Factor

Medium

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2016/04/04, Modified: 2016/12/14

Plugin Output

192.168.100.22 (tcp/22/ssh)

The following weak server-to-client encryption algorithms are supported :

```
arcfour
arcfour128
arcfour256
```

The following weak client-to-server encryption algorithms are supported :

```
arcfour
arcfour128
arcfour256
```

136808 (1) - ISC BIND Denial of Service

Synopsis

The remote name server is affected by an assertion failure vulnerability.

Description

A denial of service (DoS) vulnerability exists in ISC BIND versions 9.11.18 / 9.11.18-S1 / 9.12.4-P2 / 9.13 / 9.14.11 / 9.15 / 9.16.2 / 9.17 / 9.17.1 and earlier. An unauthenticated, remote attacker can exploit this issue, via a specially-crafted message, to cause the service to stop responding.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/docs/cve-2020-8617>

Solution

Upgrade to the patched release most closely related to your current version of BIND.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

5.3 (CVSS:3.0/E:P/RL:O/RC:C)

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.4 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2020-8617
XREF	IAVA:2020-A-0217-S

Plugin Information

Published: 2020/05/22, Modified: 2023/03/23

Plugin Output

192.168.100.22 (udp/53/dns)

```
Installed version : 9.4.2
Fixed version    : 9.11.19
```

139915 (1) - ISC BIND 9.x < 9.11.22, 9.12.x < 9.16.6, 9.17.x < 9.17.4 DoS

Synopsis

The remote name server is affected by a denial of service vulnerability.

Description

According to its self-reported version number, the installation of ISC BIND running on the remote name server is version 9.x prior to 9.11.22, 9.12.x prior to 9.16.6 or 9.17.x prior to 9.17.4. It is, therefore, affected by a denial of service (DoS) vulnerability due to an assertion failure when attempting to verify a truncated response to a TSIG-signed request. An authenticated, remote attacker can exploit this issue by sending a truncated response to a TSIG-signed request to trigger an assertion failure, causing the server to exit.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/docs/cve-2020-8622>

Solution

Upgrade to BIND 9.11.22, 9.16.6, 9.17.4 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

5.7 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

4.0 (CVSS2#AV:N/AC:L/Au:S/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.0 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2020-8622
XREF	IAVA:2020-A-0385-S

Plugin Information

Published: 2020/08/27, Modified: 2021/06/03

Plugin Output

192.168.100.22 (udp/53/dns)

```
Installed version : 9.4.2
Fixed version    : 9.11.22, 9.16.6, 9.17.4 or later
```


78479 (2) - SSLv3 Padding Oracle On Downgraded Legacy Encryption Vulnerability (POODLE)

Synopsis

It is possible to obtain sensitive information from the remote host with SSL/TLS-enabled services.

Description

The remote host is affected by a man-in-the-middle (MitM) information disclosure vulnerability known as POODLE. The vulnerability is due to the way SSL 3.0 handles padding bytes when decrypting messages encrypted using block ciphers in cipher block chaining (CBC) mode.

MitM attackers can decrypt a selected byte of a cipher text in as few as 256 tries if they are able to force a victim application to repeatedly send the same data over newly created SSL 3.0 connections.

As long as a client and service both support SSLv3, a connection can be 'rolled back' to SSLv3, even if TLSv1 or newer is supported by the client and service.

The TLS Fallback SCSV mechanism prevents 'version rollback' attacks without impacting legacy clients; however, it can only protect connections when the client and service support the mechanism. Sites that cannot disable SSLv3 immediately should enable this mechanism.

This is a vulnerability in the SSLv3 specification, not in any particular SSL implementation. Disabling SSLv3 is the only way to completely mitigate the vulnerability.

See Also

<https://www.imperialviolet.org/2014/10/14/poodle.html>

<https://www.openssl.org/~bodo/ssl-poodle.pdf>

<https://tools.ietf.org/html/draft-ietf-tls-downgrade-scsv-00>

Solution

Disable SSLv3.

Services that must support SSLv3 should enable the TLS Fallback SCSV mechanism until SSLv3 can be disabled.

Risk Factor

Medium

CVSS v3.0 Base Score

3.4 (CVSS:3.0/AV:N/AC:H/PR:N/UI:R/S:C/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

3.1 (CVSS:3.0/E:P/RL:O/RC:C)

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.4 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	70574
CVE	CVE-2014-3566
XREF	CERT:577193

Plugin Information

Published: 2014/10/15, Modified: 2023/06/23

Plugin Output

192.168.100.22 (tcp/25/smtp)

Nessus determined that the remote server supports SSLv3 with at least one CBC cipher suite, indicating that this server is vulnerable.

It appears that TLSv1 or newer is supported on the server. However, the Fallback SCSV mechanism is not supported, allowing connections to be "rolled back" to SSLv3.

192.168.100.22 (tcp/5432/postgresql)

Nessus determined that the remote server supports SSLv3 with at least one CBC cipher suite, indicating that this server is vulnerable.

It appears that TLSv1 or newer is supported on the server. However, the Fallback SCSV mechanism is not supported, allowing connections to be "rolled back" to SSLv3.

10407 (1) - X Server Detection

Synopsis

An X11 server is listening on the remote host

Description

The remote host is running an X11 server. X11 is a client-server protocol that can be used to display graphical applications running on a given host on a remote client.

Since the X11 traffic is not ciphered, it is possible for an attacker to eavesdrop on the connection.

Solution

Restrict access to this port. If the X11 client/server facility is not used, disable TCP support in X11 entirely (-nolisten tcp).

Risk Factor

Low

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2000/05/12, Modified: 2019/03/05

Plugin Output

192.168.100.22 (tcp/6000/x11)

```
X11 Version : 11.0
```

70658 (1) - SSH Server CBC Mode Ciphers Enabled

Synopsis

The SSH server is configured to use Cipher Block Chaining.

Description

The SSH server is configured to support Cipher Block Chaining (CBC) encryption. This may allow an attacker to recover the plaintext message from the ciphertext.

Note that this plugin only checks for the options of the SSH server and does not check for vulnerable software versions.

Solution

Contact the vendor or consult product documentation to disable CBC mode cipher encryption, and enable CTR or GCM cipher mode encryption.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	32319
CVE	CVE-2008-5161
XREF	CERT:958563
XREF	CWE:200

Plugin Information

Published: 2013/10/28, Modified: 2023/10/27

Plugin Output

192.168.100.22 (tcp/22/ssh)

The following client-to-server Cipher Block Chaining (CBC) algorithms are supported :

```
3des-cbc
aes128-cbc
aes192-cbc
aes256-cbc
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

The following server-to-client Cipher Block Chaining (CBC) algorithms are supported :

```
3des-cbc
aes128-cbc
aes192-cbc
aes256-cbc
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

71049 (1) - SSH Weak MAC Algorithms Enabled

Synopsis

The remote SSH server is configured to allow MD5 and 96-bit MAC algorithms.

Description

The remote SSH server is configured to allow either MD5 or 96-bit MAC algorithms, both of which are considered weak.

Note that this plugin only checks for the options of the SSH server, and it does not check for vulnerable software versions.

Solution

Contact the vendor or consult product documentation to disable MD5 and 96-bit MAC algorithms.

Risk Factor

Low

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2013/11/22, Modified: 2016/12/14

Plugin Output

192.168.100.22 (tcp/22/ssh)

```
The following client-to-server Message Authentication Code (MAC) algorithms
are supported :
```

```
  hmac-md5
  hmac-md5-96
  hmac-sha1-96
```

```
The following server-to-client Message Authentication Code (MAC) algorithms
are supported :
```

```
  hmac-md5
  hmac-md5-96
  hmac-sha1-96
```

83738 (1) - SSL/TLS EXPORT_DHE <= 512-bit Export Cipher Suites Supported (Logjam)

Synopsis

The remote host supports a set of weak ciphers.

Description

The remote host supports EXPORT_DHE cipher suites with keys less than or equal to 512 bits. Through cryptanalysis, a third party can find the shared secret in a short amount of time.

A man-in-the middle attacker may be able to downgrade the session to use EXPORT_DHE cipher suites. Thus, it is recommended to remove support for weak cipher suites.

See Also

<https://weakdh.org/>

Solution

Reconfigure the service to remove support for EXPORT_DHE cipher suites.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

3.2 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

2.2 (CVSS2#E:U/RL:ND/RC:C)

References

BID	74733
CVE	CVE-2015-4000
XREF	CEA-ID:CEA-2021-0004

Plugin Information

Published: 2015/05/21, Modified: 2022/12/05

Plugin Output

192.168.100.22 (tcp/25/smtp)

EXPORT_DHE cipher suites supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EXP-EDH-RSA-DES-CBC-SHA SHA1 export	0x00, 0x14	DH(512)	RSA	DES-CBC(40)	
EXP-ADH-DES-CBC-SHA SHA1 export	0x00, 0x19	DH(512)	None	DES-CBC(40)	
EXP-ADH-RC4-MD5 export	0x00, 0x17	DH(512)	None	RC4(40)	MD5

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

83875 (1) - SSL/TLS Diffie-Hellman Modulus <= 1024 Bits (Logjam)

Synopsis

The remote host allows SSL/TLS connections with one or more Diffie-Hellman moduli less than or equal to 1024 bits.

Description

The remote host allows SSL/TLS connections with one or more Diffie-Hellman moduli less than or equal to 1024 bits. Through cryptanalysis, a third party may be able to find the shared secret in a short amount of time (depending on modulus size and attacker resources). This may allow an attacker to recover the plaintext or potentially violate the integrity of connections.

See Also

<https://weakdh.org/>

Solution

Reconfigure the service to use a unique Diffie-Hellman moduli of 2048 bits or greater.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

3.2 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	74733
CVE	CVE-2015-4000
XREF	CEA-ID:CEA-2021-0004

Plugin Information

Published: 2015/05/28, Modified: 2022/12/05

Plugin Output

192.168.100.22 (tcp/25/smtp)

Vulnerable connection combinations :

```
SSL/TLS version  : SSLv3
Cipher suite     : TLS1_CK_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA
Diffie-Hellman MODP size (bits) : 512
Logjam attack difficulty : Easy (could be carried out by individuals)
```

```
SSL/TLS version  : TLSv1.0
Cipher suite     : TLS1_CK_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA
Diffie-Hellman MODP size (bits) : 512
Logjam attack difficulty : Easy (could be carried out by individuals)
```

153953 (1) - SSH Weak Key Exchange Algorithms Enabled

Synopsis

The remote SSH server is configured to allow weak key exchange algorithms.

Description

The remote SSH server is configured to allow key exchange algorithms which are considered weak.

This is based on the IETF draft document Key Exchange (KEX) Method Updates and Recommendations for Secure Shell (SSH) draft-ietf-curdle-ssh-kex-sha2-20. Section 4 lists guidance on key exchange algorithms that SHOULD NOT and MUST NOT be enabled. This includes:

diffie-hellman-group-exchange-sha1

diffie-hellman-group1-sha1

gss-gex-sha1-*

gss-group1-sha1-*

gss-group14-sha1-*

rsa1024-sha1

Note that this plugin only checks for the options of the SSH server, and it does not check for vulnerable software versions.

See Also

<http://www.nessus.org/u?b02d91cd>

<https://datatracker.ietf.org/doc/html/rfc8732>

Solution

Contact the vendor or consult product documentation to disable the weak algorithms.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2021/10/13, Modified: 2021/10/13

Plugin Output

192.168.100.22 (tcp/22/ssh)

The following weak key exchange algorithms are enabled :

```
diffie-hellman-group-exchange-sha1
diffie-hellman-group1-sha1
```

11219 (25) - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2023/09/25

Plugin Output

192.168.100.22 (tcp/21/ftp)

```
Port 21/tcp was found to be open
```

192.168.100.22 (tcp/22/ssh)

```
Port 22/tcp was found to be open
```

192.168.100.22 (tcp/23/telnet)

```
Port 23/tcp was found to be open
```

192.168.100.22 (tcp/25/smtp)

```
Port 25/tcp was found to be open
```

192.168.100.22 (tcp/53/dns)

Port 53/tcp was found to be open

192.168.100.22 (tcp/80/www)

Port 80/tcp was found to be open

192.168.100.22 (tcp/111/rpc-portmapper)

Port 111/tcp was found to be open

192.168.100.22 (tcp/139/smb)

Port 139/tcp was found to be open

192.168.100.22 (tcp/445/cifs)

Port 445/tcp was found to be open

192.168.100.22 (tcp/512)

Port 512/tcp was found to be open

192.168.100.22 (tcp/513/rlogin)

Port 513/tcp was found to be open

192.168.100.22 (tcp/514)

Port 514/tcp was found to be open

192.168.100.22 (tcp/1099/rmi_registry)

Port 1099/tcp was found to be open

192.168.100.22 (tcp/1524/wild_shell)

Port 1524/tcp was found to be open

192.168.100.22 (tcp/2049/rpc-nfs)

Port 2049/tcp was found to be open

192.168.100.22 (tcp/2121/ftp)

Port 2121/tcp was found to be open

192.168.100.22 (tcp/3306/mysql)

Port 3306/tcp was found to be open

192.168.100.22 (tcp/3632)

Port 3632/tcp was found to be open

192.168.100.22 (tcp/5432/postgresql)

Port 5432/tcp was found to be open

192.168.100.22 (tcp/5900/vnc)

Port 5900/tcp was found to be open

192.168.100.22 (tcp/6000/x11)

Port 6000/tcp was found to be open

192.168.100.22 (tcp/6667/irc)

Port 6667/tcp was found to be open

192.168.100.22 (tcp/8009)

Port 8009/tcp was found to be open

192.168.100.22 (tcp/8180/www)

Port 8180/tcp was found to be open

192.168.100.22 (tcp/8787)

Port 8787/tcp was found to be open

11111 (10) - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

192.168.100.22 (tcp/111/rpc-portmapper)

```
The following RPC services are available on TCP port 111 :
```

```
- program: 100000 (portmapper), version: 2
```

192.168.100.22 (udp/111/rpc-portmapper)

```
The following RPC services are available on UDP port 111 :
```

```
- program: 100000 (portmapper), version: 2
```

192.168.100.22 (tcp/2049/rpc-nfs)

```
The following RPC services are available on TCP port 2049 :
```

```
- program: 100003 (nfs), version: 2  
- program: 100003 (nfs), version: 3  
- program: 100003 (nfs), version: 4
```

192.168.100.22 (udp/2049/rpc-nfs)

The following RPC services are available on UDP port 2049 :

- program: 100003 (nfs), version: 2
- program: 100003 (nfs), version: 3
- program: 100003 (nfs), version: 4

192.168.100.22 (udp/33909/rpc-mountd)

The following RPC services are available on UDP port 33909 :

- program: 100005 (mountd), version: 1
- program: 100005 (mountd), version: 2
- program: 100005 (mountd), version: 3

192.168.100.22 (tcp/46812/rpc-status)

The following RPC services are available on TCP port 46812 :

- program: 100024 (status), version: 1

192.168.100.22 (tcp/50116/rpc-nlockmgr)

The following RPC services are available on TCP port 50116 :

- program: 100021 (nlockmgr), version: 1
- program: 100021 (nlockmgr), version: 3
- program: 100021 (nlockmgr), version: 4

192.168.100.22 (tcp/55199/rpc-mountd)

The following RPC services are available on TCP port 55199 :

- program: 100005 (mountd), version: 1
- program: 100005 (mountd), version: 2
- program: 100005 (mountd), version: 3

192.168.100.22 (udp/57420/rpc-status)

The following RPC services are available on UDP port 57420 :

- program: 100024 (status), version: 1

192.168.100.22 (udp/58295/rpc-nlockmgr)

The following RPC services are available on UDP port 58295 :

- program: 100021 (nlockmgr), version: 1
- program: 100021 (nlockmgr), version: 3

```
- program: 100021 (nlockmgr), version: 4
```

22964 (9) - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2023/07/10

Plugin Output

192.168.100.22 (tcp/21/ftp)

```
An FTP server is running on this port.
```

192.168.100.22 (tcp/22/ssh)

```
An SSH server is running on this port.
```

192.168.100.22 (tcp/23/telnet)

```
A telnet server is running on this port.
```

192.168.100.22 (tcp/25/smtp)

```
An SMTP server is running on this port.
```

192.168.100.22 (tcp/80/www)

```
A web server is running on this port.
```

192.168.100.22 (tcp/1524/wild_shell)

A shell server (Metasploitable) is running on this port.

192.168.100.22 (tcp/2121/ftp)

An FTP server is running on this port.

192.168.100.22 (tcp/5900/vnc)

A vnc server is running on this port.

192.168.100.22 (tcp/8180/www)

A web server is running on this port.

11154 (3) - Unknown Service Detection: Banner Retrieval

Synopsis

There is an unknown service running on the remote host.

Description

Nessus was unable to identify a service on the remote host even though it returned a banner of some type.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/11/18, Modified: 2022/07/26

Plugin Output

192.168.100.22 (tcp/512)

If you know what this service is and think the banner could be used to identify it, please send a description of the service along with the following output to svc-signatures@nessus.org :

```
Port      : 512
Type      : spontaneous
Banner    :
0x00:  01 57 68 65 72 65 20 61 72 65 20 79 6F 75 3F 0A    .Where are you?.
      0x10:
```

192.168.100.22 (tcp/514)

If you know what this service is and think the banner could be used to identify it, please send a description of the service along with the following output to svc-signatures@nessus.org :

```
Port      : 514
Type      : spontaneous
Banner    :
0x00:  01 67 65 74 6E 61 6D 65 69 6E 66 6F 3A 20 54 65    .getnameinfo: Te
      0x10:  6D 70 6F 72 61 72 79 20 66 61 69 6C 75 72 65 20    mporary failure
      0x20:  69 6E 20 6E 61 6D 65 20 72 65 73 6F 6C 75 74 69    in name resoluti
      0x30:  6F 6E 0A                                           on.
```

192.168.100.22 (tcp/8787)

If you know what this service is and think the banner could be used to identify it, please send a description of the service along with the following output to svc-signatures@nessus.org :

```
Port      : 8787
Type      : get_http
Banner    :
0x0000:  00 00 00 03 04 08 46 00 00 03 A1 04 08 6F 3A 16      .....F.....O:..
0x0010:  44 52 62 3A 3A 44 52 62 43 6F 6E 6E 45 72 72 6F      DRb::DRbConnErro
0x0020:  72 07 3A 07 62 74 5B 17 22 2F 2F 75 73 72 2F 6C      r...bt["//usr/l
0x0030:  69 62 2F 72 75 62 79 2F 31 2E 38 2F 64 72 62 2F      ib/ruby/1.8/drb/
0x0040:  64 72 62 2E 72 62 3A 35 37 33 3A 69 6E 20 60 6C      drb.rb:573:in `l
0x0050:  6F 61 64 27 22 37 2F 75 73 72 2F 6C 69 62 2F 72      oad'"7/usr/lib/r
0x0060:  75 62 79 2F 31 2E 38 2F 64 72 62 2F 64 72 62 2E      uby/1.8/drb/drb.
0x0070:  72 62 3A 36 31 32 3A 69 6E 20 60 72 65 63 76 5F      rb:612:in `recv_
0x0080:  72 65 71 75 65 73 74 27 22 37 2F 75 73 72 2F 6C      request'"7/usr/l
0x0090:  69 62 2F 72 75 62 79 2F 31 2E 38 2F 64 72 62 2F      ib/ruby/1.8/drb/
0x00A0:  64 72 62 2E 72 62 3A 39 31 31 3A 69 6E 20 60 72      drb.rb:911:in `r
0x00B0:  65 63 76 5F 72 65 71 75 65 73 74 27 22 3C 2F 75      ecv_request'"</u
0x00C0:  73 72 2F 6C 69 62 2F 72 75 62 79 2F 31 2E 38 2F      sr/lib/ruby/1.8/
0x00D0:  64 72 62 2F 64 72 62 2E 72 62 3A 31 35 33 30 3A      drb/drb.rb:1530:
0x00E0:  69 6E 20 60 69 6E 69 74 5F 77 69 74 68 5F 63 6C      in `init_with_cl
0x00F0:  69 65 6E 74 27 22 39 2F 75 73 72 2F 6C 69 62 2F      ient'"9/usr/lib/
0x0100:  72 75 62 79 2F 31 2E 38 2F 64 72 62 2F 64 72 62      ruby/1.8/drb/drb
0x0110:  2E 72 62 3A 31 35 34 32 3A 69 6E 20 60 73 65 74      .rb:1542:in `set
0x0120:  75 70 5F 6D 65 73 73 61 67 65 27 22 33 2F 75 73      up_message'"3/us
0x0130:  72 2F 6C 69 62 2F 72 75 62 79 2F 31 2E 38 2F 64      r/lib/ruby/1.8/d
0x0140:  72 62 2F 64 72 62 2E 72 62 3A 31 34 39 34      [...]
```

10092 (2) - FTP Server Detection

Synopsis

An FTP server is listening on a remote port.

Description

It is possible to obtain the banner of the remote FTP server by connecting to a remote port.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0030

XREF IAVT:0001-T-0943

Plugin Information

Published: 1999/10/12, Modified: 2023/08/17

Plugin Output

192.168.100.22 (tcp/21/ftp)

```
The remote FTP banner is :
```

```
220 (vsFTPd 2.3.4)
```

192.168.100.22 (tcp/2121/ftp)

```
The remote FTP banner is :
```

```
220 ProFTPD 1.3.1 Server (Debian) [::ffff:192.168.100.22]
```

10107 (2) - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

192.168.100.22 (tcp/80/www)

```
The remote web server type is :
```

```
Apache/2.2.8 (Ubuntu) DAV/2
```

192.168.100.22 (tcp/8180/www)

```
The remote web server type is :
```

```
Apache-Coyote/1.1
```


10863 (2) - SSL Certificate Information

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

Plugin Output

192.168.100.22 (tcp/25/smtp)

```
Subject Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Issuer Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Serial Number: 00 FA F9 3A 4C 7F B6 B9 CC

Version: 1

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Mar 17 14:07:45 2010 GMT
Not Valid After: Apr 16 14:07:45 2010 GMT

Public Key Info:
```

```

Algorithm: RSA Encryption
Key Length: 1024 bits
Public Key: 00 D6 B4 13 36 33 9A 95 71 7B 1B DE 7C 83 75 DA 71 B1 3C A9
            7F FE AD 64 1B 77 E9 4F AE BE CA D4 F8 CB EF AE BB 43 79 24
            73 FF 3C E5 9E 3B 6D FC C8 B1 AC FA 4C 4D 5E 9B 4C 99 54 0B
            D7 A8 4A 50 BA A9 DE 1D 1F F4 E4 6B 02 A3 F4 6B 45 CD 4C AF
            8D 89 62 33 8F 65 BB 36 61 9F C4 2C 73 C1 4E 2E A0 A8 14 4E
            98 70 46 61 BB D1 B9 31 DF 8C 99 EE 75 6B 79 3C 40 A0 AE 97
            00 90 9D DC 99 0D 33 A4 B5
Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits
Signature: 00 92 A4 B4 B8 14 55 63 25 51 4A 0B C3 2A 22 CF 3A F8 17 6A
            0C CF 66 AA A7 65 2F 48 6D CD E3 3E 5C 9F 77 6C D4 44 54 1F
            1E 84 4F 8E D4 8D DD AC 2D 88 09 21 A8 DA 56 2C A9 05 3C 49
            68 35 19 75 0C DA 53 23 88 88 19 2D 74 26 C1 22 65 EE 11 68
            83 6A 53 4A 9C 27 CB A0 B4 E9 8D 29 0C B2 3C 18 5C 67 CC 53
            A6 1E 30 D0 AA 26 7B 1E AE 40 B9 29 01 6C 2E BC A2 19 94 7C
            15 6E 8D 30 38 F6 CA 2E 75

Fingerprints :

SHA-256 Fingerprint: E7 A7 FA 0D 63 E4 57 C7 C4 A5 9B 38 B7 08 49 C6 A7 0B DA 6F
                    83 0C 7A F1 E3 2D EE 43 6D E8 13 CC
SHA-1 Fingerprint: ED 09 30 88 70 66 03 BF D5 DC 23 73 99 B4 98 DA 2D [...]

```

192.168.100.22 (tcp/5432/postgresql)

```

Subject Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Issuer Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Serial Number: 00 FA F9 3A 4C 7F B6 B9 CC

Version: 1

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Mar 17 14:07:45 2010 GMT
Not Valid After: Apr 16 14:07:45 2010 GMT

Public Key Info:

Algorithm: RSA Encryption
Key Length: 1024 bits
Public Key: 00 D6 B4 13 36 33 9A 95 71 7B 1B DE 7C 83 75 DA 71 B1 3C A9
            7F FE AD 64 1B 77 E9 4F AE BE CA D4 F8 CB EF AE BB 43 79 24
            73 FF 3C E5 9E 3B 6D FC C8 B1 AC FA 4C 4D 5E 9B 4C 99 54 0B
            D7 A8 4A 50 BA A9 DE 1D 1F F4 E4 6B 02 A3 F4 6B 45 CD 4C AF
            8D 89 62 33 8F 65 BB 36 61 9F C4 2C 73 C1 4E 2E A0 A8 14 4E
            98 70 46 61 BB D1 B9 31 DF 8C 99 EE 75 6B 79 3C 40 A0 AE 97
            00 90 9D DC 99 0D 33 A4 B5

```

Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits

Signature: 00 92 A4 B4 B8 14 55 63 25 51 4A 0B C3 2A 22 CF 3A F8 17 6A
0C CF 66 AA A7 65 2F 48 6D CD E3 3E 5C 9F 77 6C D4 44 54 1F
1E 84 4F 8E D4 8D DD AC 2D 88 09 21 A8 DA 56 2C A9 05 3C 49
68 35 19 75 0C DA 53 23 88 88 19 2D 74 26 C1 22 65 EE 11 68
83 6A 53 4A 9C 27 CB A0 B4 E9 8D 29 0C B2 3C 18 5C 67 CC 53
A6 1E 30 D0 AA 26 7B 1E AE 40 B9 29 01 6C 2E BC A2 19 94 7C
15 6E 8D 30 38 F6 CA 2E 75

Fingerprints :

SHA-256 Fingerprint: E7 A7 FA 0D 63 E4 57 C7 C4 A5 9B 38 B7 08 49 C6 A7 0B DA 6F
83 0C 7A F1 E3 2D EE 43 6D E8 13 CC

SHA-1 Fingerprint: ED 09 30 88 70 66 03 BF D5 DC 23 73 99 B4 98 DA 2D [...]

11002 (2) - DNS Server Detection

Synopsis

A DNS server is listening on the remote host.

Description

The remote service is a Domain Name System (DNS) server, which provides a mapping between hostnames and IP addresses.

See Also

https://en.wikipedia.org/wiki/Domain_Name_System

Solution

Disable this service if it is not needed or restrict access to internal hosts only if the service is available externally.

Risk Factor

None

Plugin Information

Published: 2003/02/13, Modified: 2017/05/16

Plugin Output

192.168.100.22 (tcp/53/dns)
192.168.100.22 (udp/53/dns)

11011 (2) - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

192.168.100.22 (tcp/139/smb)

```
An SMB server is running on this port.
```

192.168.100.22 (tcp/445/cifs)

```
A CIFS server is running on this port.
```

21643 (2) - SSL Cipher Suites Supported

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffced>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/06/05, Modified: 2023/07/10

Plugin Output

192.168.100.22 (tcp/25/smtp)

Here is the list of SSL ciphers supported by the remote server :
Each group is reported per SSL Version.

SSL Version : TLSv1

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
EXP-EDH-RSA-DES-CBC-SHA SHA1 export	0x00, 0x14	DH (512)	RSA	DES-CBC (40)	
EDH-RSA-DES-CBC-SHA SHA1	0x00, 0x15	DH	RSA	DES-CBC (56)	
EXP-ADH-DES-CBC-SHA SHA1 export	0x00, 0x19	DH (512)	None	DES-CBC (40)	
EXP-ADH-RC4-MD5 export	0x00, 0x17	DH (512)	None	RC4 (40)	MD5
ADH-DES-CBC-SHA SHA1	0x00, 0x1A	DH	None	DES-CBC (56)	
EXP-DES-CBC-SHA SHA1 export	0x00, 0x08	RSA (512)	RSA	DES-CBC (40)	
EXP-RC2-CBC-MD5 export	0x00, 0x06	RSA (512)	RSA	RC2-CBC (40)	MD5

EXP-RS4-MD5 export	0x00, 0x03	RSA (512)	RSA	RC4 (40)	MD5
DES-CBC-SHA SHA1	0x00, 0x09	RSA	RSA	DES-CBC (56)	
Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)					
Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DH	RSA	3DES-CBC (168)	
ADH-DES-CBC3-SHA SHA1	0x00, 0x1B	DH	None	3DES-CBC (168)	
DES-CBC3-SHA SHA1	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	
High Strength Ciphers (>= 112-bit key)					
Name	Code	KEX	Auth	[...]	
-----	-----	---	----		

192.168.100.22 (tcp/5432/postgresql)

Here is the list of SSL ciphers supported by the remote server :
Each group is reported per SSL Version.

SSL Version : TLSv1

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DH	RSA	3DES-CBC (168)	
DES-CBC3-SHA SHA1	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DHE-RSA-AES128-SHA SHA1	0x00, 0x33	DH	RSA	AES-CBC (128)	
DHE-RSA-AES256-SHA SHA1	0x00, 0x39	DH	RSA	AES-CBC (256)	
AES128-SHA SHA1	0x00, 0x2F	RSA	RSA	AES-CBC (128)	
AES256-SHA SHA1	0x00, 0x35	RSA	RSA	AES-CBC (256)	
RC4-SHA SHA1	0x00, 0x05	RSA	RSA	RC4 (128)	

SSL Version : SSLv3

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DH	RSA	3DES-CBC (168)	
DES-CBC3-SHA SHA1	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	[...]		

22227 (2) - RMI Registry Detection

Synopsis

An RMI registry is listening on the remote host.

Description

The remote host is running an RMI registry, which acts as a bootstrap naming service for registering and retrieving remote objects with simple names in the Java Remote Method Invocation (RMI) system.

See Also

<https://docs.oracle.com/javase/1.5.0/docs/guide/rmi/spec/rmiTOC.html>

<http://www.nessus.org/u?b6fd7659>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/08/16, Modified: 2022/06/01

Plugin Output

192.168.100.22 (tcp/1099/rmi_registry)
192.168.100.22 (tcp/1099/rmi_registry)

```
Valid response recieved for port 1099:
0x00:  51 AC ED 00 05 77 0F 01 7E 75 E1 7C 00 00 01 8C   Q...w...~u.|....
0x10:  F2 81 B0 DD 80 02 75 72 00 13 5B 4C 6A 61 76 61   .....ur..[Ljava
0x20:  2E 6C 61 6E 67 2E 53 74 72 69 6E 67 3B AD D2 56   .lang.String;..V
0x30:  E7 E9 1D 7B 47 02 00 00 70 78 70 00 00 00 00   ...{G...pxp....
```


|_ |

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

```
</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></li>
<li><a href="/dav/">WebDAV</a></li>
</ul>
</body>
</html>
```

192.168.100.22 (tcp/8180/www)

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

SSL : no

Keep-Alive : no

Options allowed : GET, HEAD, POST, PUT, DELETE, TRACE, OPTIONS

Headers :

Server: Apache-Coyote/1.1
Content-Type: text/html; charset=ISO-8859-1
Date: Wed, 10 Jan 2024 08:33:08 GMT
Connection: close

Response Body :

```
<!--
Licensed to the Apache Software Foundation (ASF) under one or more
contributor license agreements. See the NOTICE file distributed with
this work for additional information regarding copyright ownership.
The ASF licenses this file to You under the Apache License, Version 2.0
(the "License"); you may not use this file except in compliance with
the License. You may obtain a copy of the License at
```

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

```
-->
```

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">
```

```
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en">
<head>
<title>Apache Tomcat/5.5</title>
<style type="text/css">
/**/
body {
color: #000000;
background-color: #FFFFFF;</pre></div><div data-bbox="88 936 456 952" data-label="Page-Footer"><p>24260 (2) - HyperText Transfer Protocol (HTTP) Information</p></div><div data-bbox="889 936 915 951" data-label="Page-Footer"><p>98</p></div>
```

```
font-family: Arial, "Times New Roman", Times, serif;
    margin: 10px 0px;
}

img {
    border: none;
}

a:link, a:visited {
    color: blue
}

th {
    font-family: Verdana, "Times New Roman", Times, serif;
    font-size: 110%;
    font-weight: normal;
    font-style: italic;
    background: #D2A41C;
    text-align: left;
}

td {
    color: #000000;
font-family: Arial, Helvetica, sans-serif;
}

td.menu {
    background: #FFDC75;
}

.center [...]
```

45410 (2) - SSL Certificate 'commonName' Mismatch

Synopsis

The 'commonName' (CN) attribute in the SSL certificate does not match the hostname.

Description

The service running on the remote host presents an SSL certificate for which the 'commonName' (CN) attribute does not match the hostname on which the service listens.

Solution

If the machine has several names, make sure that users connect to the service through the DNS hostname that matches the common name in the certificate.

Risk Factor

None

Plugin Information

Published: 2010/04/03, Modified: 2021/03/09

Plugin Output

192.168.100.22 (tcp/25/smtp)

The host name known by Nessus is :

metasploitable

The Common Name in the certificate is :

ubuntu804-base.localdomain

192.168.100.22 (tcp/5432/postgresql)

The host name known by Nessus is :

metasploitable

The Common Name in the certificate is :

ubuntu804-base.localdomain

50845 (2) - OpenSSL Detection

Synopsis

The remote service appears to use OpenSSL to encrypt traffic.

Description

Based on its response to a TLS request with a specially crafted server name extension, it seems that the remote service is using the OpenSSL library to encrypt traffic.

Note that this plugin can only detect OpenSSL implementations that have enabled support for TLS extensions (RFC 4366).

See Also

<https://www.openssl.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/11/30, Modified: 2020/06/12

Plugin Output

192.168.100.22 (tcp/25/smtp)
192.168.100.22 (tcp/5432/postgresql)

56984 (2) - SSL / TLS Versions Supported

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/01, Modified: 2023/07/10

Plugin Output

192.168.100.22 (tcp/25/smtp)

```
This port supports SSLv2/SSLv3/TLSv1.0.
```

192.168.100.22 (tcp/5432/postgresql)

```
This port supports SSLv3/TLSv1.0.
```

57041 (2) - SSL Perfect Forward Secrecy Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange

https://en.wikipedia.org/wiki/Perfect_forward_secrecy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

Plugin Output

192.168.100.22 (tcp/25/smtp)

Here is the list of SSL PFS ciphers supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EXP-EDH-RSA-DES-CBC-SHA SHA1 export	0x00, 0x14	DH(512)	RSA	DES-CBC(40)	
EDH-RSA-DES-CBC-SHA SHA1	0x00, 0x15	DH	RSA	DES-CBC(56)	

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---

```

    EDH-RSA-DES-CBC3-SHA      0x00, 0x16    DH      RSA      3DES-CBC(168)
SHA1

    High Strength Ciphers (>= 112-bit key)

    Name                      Code          KEX      Auth      Encryption      MAC
    -----
    DHE-RSA-AES128-SHA      0x00, 0x33    DH      RSA      AES-CBC(128)
SHA1
    DHE-RSA-AES256-SHA      0x00, 0x39    DH      RSA      AES-CBC(256)
SHA1

The fields above are :

    {Tenable ciphername}
    {Cipher ID code}
    Kex={key exchange}
    Auth={authentication}
    Encrypt={symmetric encryption method}
    MAC={message authentication code}
    {export flag}

```

192.168.100.22 (tcp/5432/postgresql)

Here is the list of SSL PFS ciphers supported by the remote server :

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DH	RSA	3DES-CBC(168)	

SHA1

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
DHE-RSA-AES128-SHA	0x00, 0x33	DH	RSA	AES-CBC(128)	
DHE-RSA-AES256-SHA	0x00, 0x39	DH	RSA	AES-CBC(256)	

SHA1

The fields above are :

```

    {Tenable ciphername}
    {Cipher ID code}
    Kex={key exchange}
    Auth={authentication}
    Encrypt={symmetric encryption method}
    MAC={message authentication code}
    {export flag}

```


62563 (2) - SSL Compression Methods Supported

Synopsis

The remote service supports one or more compression methods for SSL connections.

Description

This script detects which compression methods are supported by the remote service for SSL connections.

See Also

<http://www.iana.org/assignments/comp-meth-ids/comp-meth-ids.xml>

<https://tools.ietf.org/html/rfc3749>

<https://tools.ietf.org/html/rfc3943>

<https://tools.ietf.org/html/rfc5246>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2012/10/16, Modified: 2022/04/11

Plugin Output

192.168.100.22 (tcp/25/smtp)

```
Nessus was able to confirm that the following compression method is
supported by the target :
```

```
DEFLATE (0x01)
```

192.168.100.22 (tcp/5432/postgresql)

```
Nessus was able to confirm that the following compression method is
supported by the target :
```

```
DEFLATE (0x01)
```

70544 (2) - SSL Cipher Block Chaining Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Cipher Block Chaining ciphers, which combine previous blocks with subsequent ones.

Description

The remote host supports the use of SSL ciphers that operate in Cipher Block Chaining (CBC) mode. These cipher suites offer additional security over Electronic Codebook (ECB) mode, but have the potential to leak information if used improperly.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

<http://www.nessus.org/u?cc4a822a>

<https://www.openssl.org/~bodo/tls-cbc.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/22, Modified: 2021/02/03

Plugin Output

192.168.100.22 (tcp/25/smtp)

Here is the list of SSL CBC ciphers supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EXP-RC2-CBC-MD5 export	0x04, 0x00, 0x80	RSA(512)	RSA	RC2-CBC(40)	MD5
EXP-EDH-RSA-DES-CBC-SHA SHA1 export	0x00, 0x14	DH(512)	RSA	DES-CBC(40)	
EDH-RSA-DES-CBC-SHA SHA1	0x00, 0x15	DH	RSA	DES-CBC(56)	
EXP-ADH-DES-CBC-SHA SHA1 export	0x00, 0x19	DH(512)	None	DES-CBC(40)	
ADH-DES-CBC-SHA SHA1	0x00, 0x1A	DH	None	DES-CBC(56)	

EXP-DES-CBC-SHA SHA1 export	0x00, 0x08	RSA (512)	RSA	DES-CBC (40)	
EXP-RC2-CBC-MD5 export	0x00, 0x06	RSA (512)	RSA	RC2-CBC (40)	MD5
DES-CBC-SHA SHA1	0x00, 0x09	RSA	RSA	DES-CBC (56)	

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DES-CBC3-MD5	0x07, 0x00, 0xC0	RSA	RSA	3DES-CBC (168)	MD5
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DH	RSA	3DES-CBC (168)	
ADH-DES-CBC3-SHA SHA1	0x00, 0x1B	DH	None	3DES-CBC (168)	
DES-CBC3-SHA SHA1	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----				

192.168.100.22 (tcp/5432/postgresql)

Here is the list of SSL CBC ciphers supported by the remote server :

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DH	RSA	3DES-CBC (168)	
DES-CBC3-SHA SHA1	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DHE-RSA-AES128-SHA SHA1	0x00, 0x33	DH	RSA	AES-CBC (128)	
DHE-RSA-AES256-SHA SHA1	0x00, 0x39	DH	RSA	AES-CBC (256)	
AES128-SHA SHA1	0x00, 0x2F	RSA	RSA	AES-CBC (128)	
AES256-SHA SHA1	0x00, 0x35	RSA	RSA	AES-CBC (256)	

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

156899 (2) - SSL/TLS Recommended Cipher Suites

Synopsis

The remote host advertises discouraged SSL/TLS ciphers.

Description

The remote host has open SSL/TLS ports which advertise discouraged cipher suites. It is recommended to only enable support for the following cipher suites:

TLSv1.3:

- 0x13,0x01 TLS13_AES_128_GCM_SHA256
- 0x13,0x02 TLS13_AES_256_GCM_SHA384
- 0x13,0x03 TLS13_CHACHA20_POLY1305_SHA256

TLSv1.2:

- 0xC0,0x2B ECDHE-ECDSA-AES128-GCM-SHA256
- 0xC0,0x2F ECDHE-RSA-AES128-GCM-SHA256
- 0xC0,0x2C ECDHE-ECDSA-AES256-GCM-SHA384
- 0xC0,0x30 ECDHE-RSA-AES256-GCM-SHA384
- 0xCC,0xA9 ECDHE-ECDSA-CHACHA20-POLY1305
- 0xCC,0xA8 ECDHE-RSA-CHACHA20-POLY1305
- 0x00,0x9E DHE-RSA-AES128-GCM-SHA256
- 0x00,0x9F DHE-RSA-AES256-GCM-SHA384

This is the recommended configuration for the vast majority of services, as it is highly secure and compatible with nearly every client released in the last five (or more) years.

See Also

https://wiki.mozilla.org/Security/Server_Side_TLS

<https://ssl-config.mozilla.org/>

Solution

Only enable support for recommended cipher suites.

Risk Factor

None

Plugin Information

Published: 2022/01/20, Modified: 2023/07/10

Plugin Output

192.168.100.22 (tcp/25/smtp)

The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
EXP-RC2-CBC-MD5 export	0x04, 0x00, 0x80	RSA(512)	RSA	RC2-CBC(40)	MD5
EXP-RC4-MD5 export	0x02, 0x00, 0x80	RSA(512)	RSA	RC4(40)	MD5
EXP-EDH-RSA-DES-CBC-SHA SHA1 export	0x00, 0x14	DH(512)	RSA	DES-CBC(40)	
EDH-RSA-DES-CBC-SHA SHA1	0x00, 0x15	DH	RSA	DES-CBC(56)	
EXP-ADH-DES-CBC-SHA SHA1 export	0x00, 0x19	DH(512)	None	DES-CBC(40)	
EXP-ADH-RC4-MD5 export	0x00, 0x17	DH(512)	None	RC4(40)	MD5
ADH-DES-CBC-SHA SHA1	0x00, 0x1A	DH	None	DES-CBC(56)	
EXP-DES-CBC-SHA SHA1 export	0x00, 0x08	RSA(512)	RSA	DES-CBC(40)	
EXP-RC2-CBC-MD5 export	0x00, 0x06	RSA(512)	RSA	RC2-CBC(40)	MD5
EXP-RC4-MD5 export	0x00, 0x03	RSA(512)	RSA	RC4(40)	MD5
DES-CBC-SHA SHA1	0x00, 0x09	RSA	RSA	DES-CBC(56)	

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
DES-CBC3-MD5	0x07, 0x00, 0xC0	RSA	RSA	3DES-CBC(168)	MD5
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DH	RSA	3DES-CBC(168)	
ADH-DE [...]					

192.168.100.22 (tcp/5432/postgresql)

The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DH	RSA	3DES-CBC(168)	
DES-CBC3-SHA SHA1	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
DHE-RSA-AES128-SHA SHA1	0x00, 0x33	DH	RSA	AES-CBC(128)	

DHE-RSA-AES256-SHA	0x00, 0x39	DH	RSA	AES-CBC(256)
SHA1				
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)
SHA1				
AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC(256)
SHA1				
RC4-SHA	0x00, 0x05	RSA	RSA	RC4(128)
SHA1				

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

10028 (1) - DNS Server BIND version Directive Remote Version Detection

Synopsis

It is possible to obtain the version number of the remote DNS server.

Description

The remote host is running BIND or another DNS server that reports its version number when it receives a special request for the text 'version.bind' in the domain 'chaos'.

This version is not necessarily accurate and could even be forged, as some DNS servers send the information based on a configuration file.

Solution

It is possible to hide the version number of BIND by using the 'version' directive in the 'options' section in named.conf.

Risk Factor

None

References

XREF IAVT:0001-T-0583

Plugin Information

Published: 1999/10/12, Modified: 2022/10/12

Plugin Output

192.168.100.22 (udp/53/dns)

Version : 9.4.2

10114 (1) - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

None

CVSS v3.0 Base Score

0.0 (CVSS:3.0/AV:L/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:N)

CVSS v2.0 Base Score

0.0 (CVSS2#AV:L/AC:L/Au:N/C:N/I:N/A:N)

References

CVE CVE-1999-0524

XREF CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2023/04/27

Plugin Output

192.168.100.22 (icmp/0)

```
The difference between the local and remote clocks is 26506 seconds.
```


10150 (1) - Windows NetBIOS / SMB Remote Host Information Disclosure

Synopsis

It was possible to obtain the network name of the remote host.

Description

The remote host is listening on UDP port 137 or TCP port 445, and replies to NetBIOS nbtscan or SMB requests.

Note that this plugin gathers information to be used in other plugins, but does not itself generate a report.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2021/02/10

Plugin Output

192.168.100.22 (udp/137/netbios-ns)

The following 7 NetBIOS names have been gathered :

METASPLOITABLE	= Computer name
METASPLOITABLE	= Messenger Service
METASPLOITABLE	= File Server Service
__MSBROWSE__	= Master Browser
WORKGROUP	= Workgroup / Domain name
WORKGROUP	= Master Browser
WORKGROUP	= Browser Service Elections

This SMB server seems to be a Samba server - its MAC address is NULL.

10223 (1) - RPC portmapper Service Detection

Synopsis

An ONC RPC portmapper is running on the remote host.

Description

The RPC portmapper is running on this port.

The portmapper allows someone to get the port number of each RPC service running on the remote host by sending either multiple lookup requests or a DUMP request.

Solution

n/a

Risk Factor

None

CVSS v3.0 Base Score

0.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:N)

CVSS v2.0 Base Score

0.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:N)

References

CVE CVE-1999-0632

Plugin Information

Published: 1999/08/19, Modified: 2019/10/04

Plugin Output

192.168.100.22 (udp/111/rpc-portmapper)

10263 (1) - SMTP Server Detection

Synopsis

An SMTP server is listening on the remote port.

Description

The remote host is running a mail (SMTP) server on this port.

Since SMTP servers are the targets of spammers, it is recommended you disable it if you do not use it.

Solution

Disable this service if you do not use it, or filter incoming traffic to this port.

Risk Factor

None

References

XREF IAVT:0001-T-0932

Plugin Information

Published: 1999/10/12, Modified: 2020/09/22

Plugin Output

192.168.100.22 (tcp/25/smtp)

Remote SMTP server banner :

220 metasploitable.localdomain ESMTP Postfix (Ubuntu)

10267 (1) - SSH Server Type and Version Information

Synopsis

An SSH server is listening on this port.

Description

It is possible to obtain information about the remote SSH server by sending an empty authentication request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0933

Plugin Information

Published: 1999/10/12, Modified: 2020/09/22

Plugin Output

192.168.100.22 (tcp/22/ssh)

```
SSH version : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
SSH supported authentication : publickey,password
```

10281 (1) - Telnet Server Detection

Synopsis

A Telnet server is listening on the remote port.

Category	Description
1	...
2	...
3	...
4	...
5	...
6	...
7	...
8	...
9	...
10	...
11	...
12	...
13	...
14	...
15	...
16	...
17	...
18	...
19	...
20	...
21	...
22	...
23	...
24	...
25	...
26	...
27	...
28	...
29	...
30	...
31	...
32	...
33	...
34	...
35	...
36	...
37	...
38	...
39	...
40	...
41	...
42	...
43	...
44	...
45	...
46	...
47	...
48	...
49	...
50	...
51	...
52	...
53	...
54	...
55	...
56	...
57	...
58	...
59	...
60	...
61	...
62	...
63	...
64	...
65	...
66	...
67	...
68	...
69	...
70	...
71	...
72	...
73	...
74	...
75	...
76	...
77	...
78	...
79	...
80	...
81	...
82	...
83	...
84	...
85	...
86	...
87	...
88	...
89	...
90	...
91	...
92	...
93	...
94	...
95	...
96	...
97	...
98	...
99	...
100	...

The remote host is running a Telnet server, a remote terminal server.

Solution

Disable this service if you do not use it.

Risk Factor	Impact	Control
1. Lack of industry connections	Reduced visibility and networking opportunities	Attend industry conferences and seminars
2. Limited marketing budget	Reduced reach and brand awareness	Utilize social media and content marketing
3. Niche or specialized services	Reduced market demand	Offer a range of services to attract a wider audience
4. Limited geographic reach	Reduced potential for growth	Expand to new markets or regions
5. Limited product or service differentiation	Reduced competitive advantage	Invest in research and development to create unique offerings
6. Limited customer loyalty	Reduced repeat business and referrals	Implement a customer loyalty program
7. Limited financial resources	Reduced ability to invest in growth and innovation	Seek external funding or investors
8. Limited talent pool	Reduced ability to execute business plan	Recruit and retain top talent
9. Limited brand recognition	Reduced customer trust and loyalty	Build a strong brand identity and reputation
10. Limited market research	Reduced understanding of customer needs and market trends	Conduct regular market research and analysis

None

Plugin Information

Published: 1999/10/12, Modified: 2020/06/12

Plugin Output

192.168.100.22 (tcp/23/telnet)

[illegible][illegible]

```
Here is the banner from the remote Telnet server :

----- snip -----

 _ _ _ _ _ | _ _ _ _ _ _ _ | _ _ ( ) _ _ _ _ _ | _ _ _ _ _ \
| ' _ _ _ _ _ / _ _ _ _ _ _ _ / _ _ | ' _ _ _ _ _ | / _ _ _ _ _ | ' _ _ _ _ _ | / _ _ _ _ _ \
| | | | | | _ _ | | ( ) \ _ _ | | | | ( ) | | | | ( ) | | | | _ _ / _ _ |
|_| |_| |_| \ _ _ | \ _ _ _ , |_ _ | . _ / | | \ _ _ | | \ _ _ _ , | _ . _ / | | \ _ _ | _ _ |
                                     |_|

Warning: Never expose this VM to an untrusted network!
Contact: msfdev[at]metasploit.com
Login with msfadmin/msfadmin to get started
metasploitable login:

----- snip -----
```

10287 (1) - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2023/12/04

Plugin Output

192.168.100.22 (udp/0)

```
For your information, here is the traceroute from 192.168.100.24 to 192.168.100.22 :  
192.168.100.24  
192.168.100.22
```

```
Hop Count: 1
```

10342 (1) - VNC Software Detection

Synopsis

The remote host is running a remote display software (VNC).

Description

The remote host is running VNC (Virtual Network Computing), which uses the RFB (Remote Framebuffer) protocol to provide remote access to graphical user interfaces and thus permits a console on the remote host to be displayed on another.

See Also

<https://en.wikipedia.org/wiki/Vnc>

Solution

Make sure use of this software is done in accordance with your organization's security policy and filter incoming traffic to this port.

Risk Factor

None

Plugin Information

Published: 2000/03/07, Modified: 2017/06/12

Plugin Output

192.168.100.22 (tcp/5900/vnc)

```
The highest RFB protocol version supported by the server is :
```

```
3.3
```

10397 (1) - Microsoft Windows SMB LanMan Pipe Server Listing Disclosure

Synopsis

It is possible to obtain network information.

Description

It was possible to obtain the browse list of the remote Windows system by sending a request to the LANMAN pipe. The browse list is the list of the nearest Windows systems of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2000/05/09, Modified: 2022/02/01

Plugin Output

192.168.100.22 (tcp/445/cifs)

```
Here is the browse list of the remote host :
```

```
METASPLOITABLE ( os : 0.0 )
```


10437 (1) - NFS Share Export List

Synopsis

The remote NFS server exports a list of shares.

Description

This plugin retrieves the list of NFS exported shares.

See Also

<http://www.tldp.org/HOWTO/NFS-HOWTO/security.html>

Solution

Ensure each share is intended to be exported.

Risk Factor

None

Plugin Information

Published: 2000/06/07, Modified: 2019/10/04

Plugin Output

192.168.100.22 (tcp/2049/rpc-nfs)

```
Here is the export list of 192.168.100.22 :
```

```
/ *
```

10719 (1) - MySQL Server Detection

Synopsis

A database server is listening on the remote port.

Description

The remote host is running MySQL, an open source database server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0802

Plugin Information

Published: 2001/08/13, Modified: 2022/10/12

Plugin Output

192.168.100.22 (tcp/3306/mysql)

```
Version : 5.0.51a-3ubuntu5
Protocol : 10
Server Status : SERVER_STATUS_AUTOCOMMIT
Server Capabilities :
  CLIENT_LONG_FLAG (Get all column flags)
  CLIENT_CONNECT_WITH_DB (One can specify db on connect)
  CLIENT_COMPRESS (Can use compression protocol)
  CLIENT_PROTOCOL_41 (New 4.1 protocol)
  CLIENT_SSL (Switch to SSL after handshake)
  CLIENT_TRANSACTIONS (Client knows about transactions)
  CLIENT_SECURE_CONNECTION (New 4.1 authentication)
```

10785 (1) - Microsoft Windows SMB NativeLanManager Remote System Information Disclosure

Synopsis

It was possible to obtain information about the remote operating system.

Description

Nessus was able to obtain the remote operating system name and version (Windows and/or Samba) by sending an authentication request to port 139 or 445. Note that this plugin requires SMB to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/10/17, Modified: 2021/09/20

Plugin Output

192.168.100.22 (tcp/445/cifs)

```
The remote Operating System is : Unix
The remote native LAN manager is : Samba 3.0.20-Debian
The remote SMB Domain Name is : METASPLOITABLE
```

10881 (1) - SSH Protocol Versions Supported

Synopsis

A SSH server is running on the remote host.

Description

This plugin determines the versions of the SSH protocol supported by the remote SSH daemon.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/03/06, Modified: 2021/01/19

Plugin Output

192.168.100.22 (tcp/22/ssh)

```
The remote SSH daemon supports the following versions of the  
SSH protocol :
```

- 1.99
- 2.0

11153 (1) - Service Detection (HELP Request)

Synopsis

The remote service could be identified.

Description

It was possible to identify the remote service by its banner or by looking at the error message it sends when it receives a 'HELP' request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/11/18, Modified: 2018/11/26

Plugin Output

192.168.100.22 (tcp/3306/mysql)

```
A MySQL server is running on this port.
```

11422 (1) - Web Server Unconfigured - Default Install Page Present

Synopsis

The remote web server is not configured or is improperly configured.

Description

The remote web server uses its default welcome page. Therefore, it's probable that this server is not used at all or is serving content that is meant to be hidden.

Solution

Disable this service if you do not use it.

Risk Factor

None

Plugin Information

Published: 2003/03/20, Modified: 2018/08/15

Plugin Output

192.168.100.22 (tcp/8180/www)

The default welcome page is from Tomcat.

11424 (1) - WebDAV Detection

Synopsis

The remote server is running with WebDAV enabled.

Description

WebDAV is an industry standard extension to the HTTP specification.

It adds a capability for authorized users to remotely add and manage the content of a web server.

If you do not use this extension, you should disable it.

Solution

<http://support.microsoft.com/default.aspx?kbid=241520>

Risk Factor

None

Plugin Information

Published: 2003/03/20, Modified: 2011/03/14

Plugin Output

192.168.100.22 (tcp/80/www)

11819 (1) - TFTP Daemon Detection

Synopsis

A TFTP server is listening on the remote port.

Description

The remote host is running a TFTP (Trivial File Transfer Protocol) daemon. TFTP is often used by routers and diskless hosts to retrieve their configuration. It can also be used by worms to propagate.

Solution

Disable this service if you do not use it.

Risk Factor

None

Plugin Information

Published: 2003/08/13, Modified: 2022/12/28

Plugin Output

192.168.100.22 (udp/69/tftp)

11936 (1) - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2023/11/08

Plugin Output

192.168.100.22 (tcp/0)

```
Remote operating system : Linux Kernel 2.6 on Ubuntu 8.04 (gutsy)
Confidence level : 95
Method : HTTP
```

Not all fingerprints could give a match. If you think some or all of the following could be used to identify the host's operating system, please email them to os-signatures@nessus.org. Be sure to include a brief description of the host itself, such as the actual operating system or product / model names.

```
SSH:SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
```

```
SinFP:
```

```
P1:B10113:F0x12:W5840:00204ffff:M1460:
```

```
P2:B10113:F0x12:W5792:00204ffff0402080affffff4445414401030307:M1460:
```

```
P3:B00000:F0x00:W0:00:M0
```

```
P4:190704_7_p=2121
```

```
SMTP:!:220 metasploitable.localdomain ESMTP Postfix (Ubuntu)
```

```
SSLcert:!:i/CN:ubuntu804-base.localdomaini/O:OCOSAI/OU:Office for Complication of Otherwise Simple
Affairss/CN:ubuntu804-base.localdomains/O:OCOSAs/OU:Office for Complication of Otherwise Simple
Affairs
```

```
ed093088706603bfd5dc237399b498da2d4d31c6
```

```
i/CN:ubuntu804-base.localdomaini/O:OCOSAI/OU:Office for Complication of Otherwise Simple Affairss/
CN:ubuntu804-base.localdomains/O:OCOSAs/OU:Office for Complication of Otherwise Simple Affairs
```

```
ed093088706603bfd5dc237399b498da2d4d31c6
```

The remote host is running Linux Kernel 2.6 on Ubuntu 8.04 (gutsy)

17975 (1) - Service Detection (GET request)

Synopsis

The remote service could be identified.

Description

It was possible to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0935

Plugin Information

Published: 2005/04/06, Modified: 2021/10/27

Plugin Output

192.168.100.22 (tcp/6667/irc)

```
An IRC daemon is listening on this port.
```

18261 (1) - Apache Banner Linux Distribution Disclosure

Synopsis

The name of the Linux distribution running on the remote host was found in the banner of the web server.

Description

Nessus was able to extract the banner of the Apache web server and determine which Linux distribution the remote host is running.

Solution

If you do not wish to display this information, edit 'httpd.conf' and set the directive 'ServerTokens Prod' and restart Apache.

Risk Factor

None

Plugin Information

Published: 2005/05/15, Modified: 2022/03/21

Plugin Output

192.168.100.22 (tcp/0)

```
The Linux distribution detected was :  
- Ubuntu 8.04 (gutsy)
```

19288 (1) - VNC Server Security Type Detection

Synopsis

A VNC server is running on the remote host.

Description

This script checks the remote VNC server protocol version and the available 'security types'.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/07/22, Modified: 2021/07/13

Plugin Output

192.168.100.22 (tcp/5900/vnc)

```
\n\nThe remote VNC server chose security type #2 (VNC authentication)
```

19506 (1) - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2023/07/31

Plugin Output

192.168.100.22 (tcp/0)

Information about this scan :

```
Nessus version : 10.6.4
Nessus build : 20005
Plugin feed version : 202401091856
Scanner edition used : Nessus Home
Scanner OS : LINUX
Scanner distribution : ubuntu1404-x86-64
Scan type : Normal
```

```
Scan name : Metasploitable
Scan policy used : Basic Network Scan
Scanner IP : 192.168.100.24
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 200.454 ms
Thorough tests : no
Experimental tests : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin launched)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2024/1/10 10:50 EST
Scan duration : 1448 sec
Scan for malware : no
```

20108 (1) - Web Server / Application favicon.ico Vendor Fingerprinting

Synopsis

The remote web server contains a graphic image that is prone to information disclosure.

Description

The 'favicon.ico' file found on the remote web server belongs to a popular web server. This may be used to fingerprint the web server.

Solution

Remove the 'favicon.ico' file or create a custom one for your site.

Risk Factor

None

Plugin Information

Published: 2005/10/28, Modified: 2020/06/12

Plugin Output

192.168.100.22 (tcp/8180/www)

```
MD5 fingerprint : 4644f2d45601037b8423d45e13194c93
Web server      : Apache Tomcat or Alfresco Community
```


21745 (1) - OS Security Patch Assessment Failed

Synopsis

Errors prevented OS Security Patch Assessment.

Description

OS Security Patch Assessment is not available for this host because either the credentials supplied in the scan policy did not allow Nessus to log into it or some other problem occurred.

Solution

Fix the problem(s) so that OS Security Patch Assessment is possible.

Risk Factor

None

References

XREF IAVB:0001-B-0501

Plugin Information

Published: 2006/06/23, Modified: 2021/07/12

Plugin Output

192.168.100.22 (tcp/0)

The following service errors were logged :

```
- Plugin      : ssh_get_info2.nasl
  Plugin ID   : 97993
  Plugin Name : OS Identification and Installed Software Enumeration over SSH v2 (Using New SSH
  Library)
  Protocol    : SSH
  Message     :
Unable to login to remote host with supplied credential sets.
Errors:
- No supplied credential sets succeeded on any of the ssh ports

- Plugin      : ssh_get_info.nasl
  Plugin ID   : 12634
  Plugin Name : Authenticated Check : OS Name and Installed Package Enumeration
  Protocol    : SSH
  Message     : Public key authentication failed.
```

25220 (1) - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

192.168.100.22 (tcp/0)

25240 (1) - Samba Server Detection

Synopsis

An SMB server is running on the remote host.

Description

The remote host is running Samba, a CIFS/SMB server for Linux and Unix.

See Also

<https://www.samba.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2022/10/12

Plugin Output

192.168.100.22 (tcp/445/cifs)

26024 (1) - PostgreSQL Server Detection

Synopsis

A database service is listening on the remote host.

Description

The remote service is a PostgreSQL database server, or a derivative such as EnterpriseDB.

See Also

<https://www.postgresql.org/>

Solution

Limit incoming traffic to this port if desired.

Risk Factor

None

Plugin Information

Published: 2007/09/14, Modified: 2023/05/24

Plugin Output

192.168.100.22 (tcp/5432/postgresql)

35371 (1) - DNS Server hostname.bind Map Hostname Disclosure

Synopsis

The DNS server discloses the remote host name.

Description

It is possible to learn the remote host name by querying the remote DNS server for 'hostname.bind' in the CHAOS domain.

Solution

It may be possible to disable this feature. Consult the vendor's documentation for more information.

Risk Factor

None

Plugin Information

Published: 2009/01/15, Modified: 2011/09/14

Plugin Output

192.168.100.22 (udp/53/dns)

```
The remote host name is :  
metasploitable
```

35716 (1) - Ethernet Card Manufacturer Detection

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

<https://standards.ieee.org/faqs/regauth.html>

<http://www.nessus.org/u?794673b4>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

192.168.100.22 (tcp/0)

The following card manufacturers were identified :

08:00:27:CB:47:6C : PCS Systemtechnik GmbH

39446 (1) - Apache Tomcat Detection

Synopsis

The remote web server is an Apache Tomcat server.

Description

Nessus was able to detect a remote Apache Tomcat web server.

See Also

<https://tomcat.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0535

Plugin Information

Published: 2009/06/18, Modified: 2023/05/24

Plugin Output

192.168.100.22 (tcp/8180/www)

```
URL      : http://192.168.100.22:8180/
Version  : 5.5
backported : 0
source    : Apache Tomcat/5.5
```

39519 (1) - Backported Security Patch Detection (FTP)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote FTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2015/07/07

Plugin Output

192.168.100.22 (tcp/2121/ftp)

Give Nessus credentials to perform local checks.

39520 (1) - Backported Security Patch Detection (SSH)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote SSH server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2015/07/07

Plugin Output

192.168.100.22 (tcp/22/ssh)

Give Nessus credentials to perform local checks.

39521 (1) - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2015/07/07

Plugin Output

192.168.100.22 (tcp/80/www)

Give Nessus credentials to perform local checks.

42088 (1) - SMTP Service STARTTLS Command Support

Synopsis

The remote mail service supports encrypting traffic.

Description

The remote SMTP service supports the use of the 'STARTTLS' command to switch from a cleartext to an encrypted communications channel.

See Also

<https://en.wikipedia.org/wiki/STARTTLS>

<https://tools.ietf.org/html/rfc2487>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/10/09, Modified: 2019/03/20

Plugin Output

192.168.100.22 (tcp/25/smtp)

```
Here is the SMTP service's SSL certificate that Nessus was able to
collect after sending a 'STARTTLS' command :
```

```
----- snip -----
```

```
Subject Name:
```

```
Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain
```

```
Issuer Name:
```

```
Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
```

```
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Serial Number: 00 FA F9 3A 4C 7F B6 B9 CC

Version: 1

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Mar 17 14:07:45 2010 GMT
Not Valid After: Apr 16 14:07:45 2010 GMT

Public Key Info:

Algorithm: RSA Encryption
Key Length: 1024 bits
Public Key: 00 D6 B4 13 36 33 9A 95 71 7B 1B DE 7C 83 75 DA 71 B1 3C A9
             7F FE AD 64 1B 77 E9 4F AE BE CA D4 F8 CB EF AE BB 43 79 24
             73 FF 3C E5 9E 3B 6D FC C8 B1 AC FA 4C 4D 5E 9B 4C 99 54 0B
             D7 A8 4A 50 BA A9 DE 1D 1F F4 E4 6B 02 A3 F4 6B 45 CD 4C AF
             8D 89 62 33 8F 65 BB 36 61 9F C4 2C 73 C1 4E 2E A0 A8 14 4E
             98 70 46 61 BB D1 B9 31 DF 8C 99 EE 75 6B 79 3C 40 A0 AE 97
             00 90 9D DC 99 0D 33 A4 B5
Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits
Signature: 00 92 A4 B4 B8 14 55 63 25 51 4A 0B C3 2A 22 CF 3A F8 17 6A
           0C CF 66 AA A7 65 2F 48 6D CD E3 3E 5C 9F 77 6C D4 44 54 1F
           1E 84 4F 8E D4 8D DD AC 2D 88 09 21 A8 DA 56 2C A9 05 3C 49
           68 35 19 75 0C DA 53 23 88 88 19 2D 74 26 C1 22 65 EE 11 68
           83 6A 53 4A 9C 27 CB A0 B4 E9 8D 29 0C B2 3C 18 5C 67 CC 53
           A6 1E 30 D0 AA 26 7B 1E AE 40 B9 29 01 6C 2E BC A2 19 94 7C
           15 6E 8D 30 38 F6 CA 2E 75

----- snip ----- [...]
```

45590 (1) - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2023/12/27

Plugin Output

192.168.100.22 (tcp/0)

The remote operating system matched the following CPE :

cpe:/o:canonical:ubuntu_linux:8.04 -> Canonical Ubuntu Linux

Following application CPE's matched on the remote system :

cpe:/a:apache:http_server:2.2.8 -> Apache Software Foundation Apache HTTP Server
cpe:/a:apache:http_server:2.2.99 -> Apache Software Foundation Apache HTTP Server
cpe:/a:apache:tomcat:5.5 -> Apache Software Foundation Tomcat
cpe:/a:isc:bind:9.4. -> ISC BIND
cpe:/a:isc:bind:9.4.2 -> ISC BIND
cpe:/a:mysql:mysql:5.0.51a-3ubuntu5 -> MySQL MySQL
cpe:/a:openbsd:openssh:4.7 -> OpenBSD OpenSSH
cpe:/a:openbsd:openssh:4.7p1 -> OpenBSD OpenSSH
cpe:/a:php:php:5.2.4 -> PHP PHP
cpe:/a:php:php:5.2.4-2ubuntu5.10 -> PHP PHP
cpe:/a:postgresql:postgresql -> PostgreSQL

```
cpe:/a:samba:samba:3.0.20 -> Samba Samba
```

48204 (1) - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0030

XREF IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2023/08/17

Plugin Output

192.168.100.22 (tcp/80/www)

```
URL      : http://192.168.100.22/
Version  : 2.2.99
Source   : Server: Apache/2.2.8 (Ubuntu) DAV/2
backported : 1
modules  : DAV/2
os       : ConvertedUbuntu
```

48243 (1) - PHP Version Detection

Synopsis

It was possible to obtain the version number of the remote PHP installation.

Description

Nessus was able to determine the version of PHP available on the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0936

Plugin Information

Published: 2010/08/04, Modified: 2022/10/12

Plugin Output

192.168.100.22 (tcp/80/www)

Nessus was able to identify the following PHP version information :

Version : 5.2.4-2ubuntu5.10
Source : X-Powered-By: PHP/5.2.4-2ubuntu5.10

51891 (1) - SSL Session Resume Supported

Synopsis

The remote host allows resuming SSL sessions.

Description

This script detects whether a host allows resuming SSL sessions by performing a full SSL handshake to receive a session ID, and then reconnecting with the previously used session ID. If the server accepts the session ID in the second connection, the server maintains a cache of sessions that can be resumed.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/02/07, Modified: 2021/09/13

Plugin Output

192.168.100.22 (tcp/25/smtp)

```
This port supports resuming SSLv3 sessions.
```

52703 (1) - vsftpd Detection

Synopsis

An FTP server is listening on the remote port.

Description

The remote host is running vsftpd, an FTP server for UNIX-like systems written in C.

See Also

<http://vsftpd.beasts.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/03/17, Modified: 2019/11/22

Plugin Output

192.168.100.22 (tcp/21/ftp)

```
Source  : 220 (vsFTPd 2.3.4)
Version : 2.3.4
```

53335 (1) - RPC portmapper (TCP)

Synopsis

An ONC RPC portmapper is running on the remote host.

Description

The RPC portmapper is running on this port.

The portmapper allows someone to get the port number of each RPC service running on the remote host by sending either multiple lookup requests or a DUMP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/04/08, Modified: 2011/08/29

Plugin Output

192.168.100.22 (tcp/111/rpc-portmapper)

54615 (1) - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2022/09/09

Plugin Output

192.168.100.22 (tcp/0)

```
Remote device type : general-purpose  
Confidence level : 95
```

65792 (1) - VNC Server Unencrypted Communication Detection

Synopsis

A VNC server with one or more unencrypted 'security-types' is running on the remote host.

Description

This script checks the remote VNC server protocol version and the available 'security types' to determine if any unencrypted 'security-types' are in use or available.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/04/03, Modified: 2014/03/12

Plugin Output

192.168.100.22 (tcp/5900/vnc)

The remote VNC server supports the following security type
which does not perform full data communication encryption :

2 (VNC authentication)

66334 (1) - Patch Report

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2024/01/02

Plugin Output

192.168.100.22 (tcp/0)

. You need to take the following 2 actions :

[ISC BIND 9.x < 9.11.22, 9.12.x < 9.16.6, 9.17.x < 9.17.4 DoS (139915)]

+ Action to take : Upgrade to BIND 9.11.22, 9.16.6, 9.17.4 or later.

+Impact : Taking this action will resolve 3 different vulnerabilities (CVEs).

[Samba Badlock Vulnerability (90509)]

+ Action to take : Upgrade to Samba version 4.2.11 / 4.3.8 / 4.4.2 or later.

70657 (1) - SSH Algorithms and Languages Supported

Synopsis

An SSH server is listening on this port.

Description

This script detects which algorithms and languages are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/28, Modified: 2017/08/28

Plugin Output

192.168.100.22 (tcp/22/ssh)

```
Nessus negotiated the following encryption algorithm with the server :
```

```
The server supports the following options for kex_algorithms :
```

```
diffie-hellman-group-exchange-sha1
diffie-hellman-group-exchange-sha256
diffie-hellman-group1-sha1
diffie-hellman-group14-sha1
```

```
The server supports the following options for server_host_key_algorithms :
```

```
ssh-dss
ssh-rsa
```

```
The server supports the following options for encryption_algorithms_client_to_server :
```

```
3des-cbc
aes128-cbc
aes128-ctr
aes192-cbc
aes192-ctr
aes256-cbc
aes256-ctr
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
```

```
rijndael-cbc@lysator.liu.se
```

The server supports the following options for `encryption_algorithms_server_to_client` :

```
3des-cbc
aes128-cbc
aes128-ctr
aes192-cbc
aes192-ctr
aes256-cbc
aes256-ctr
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

The server supports the following options for `mac_algorithms_client_to_server` :

```
hmac-md5
hmac-md5-96
hmac-ripemd160
hmac-ripemd160@openssh.com
hmac-sha1
hmac-sha1-96
umac-64@openssh.com
```

The server supports the following options for `mac_algorithms_server_to_client` :

```
hmac-md5
hmac-md5-96
hmac-ripemd160
hmac-ripemd160@openssh.com
hmac-sha1
hmac-sha1-96
umac-64@openssh.com
```

The server supports the following options for `compression_algorithms_client_to_server` :

```
none
zlib@openssh.com
```

The server supports the following options for `compression_algorithms_server_to_client` :

```
none
zlib@openssh.com
```


84574 (1) - Backported Security Patch Detection (PHP)

Synopsis

Security patches have been backported.

Description

Security patches may have been 'backported' to the remote PHP install without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/07/07, Modified: 2022/04/11

Plugin Output

192.168.100.22 (tcp/80/www)

Give Nessus credentials to perform local checks.

86420 (1) - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2020/05/13

Plugin Output

192.168.100.22 (tcp/0)

```
The following is a consolidated list of detected MAC addresses:  
- 08:00:27:CB:47:6C
```

96982 (1) - Server Message Block (SMB) Protocol Version 1 Enabled (uncredentialed check)

Synopsis

The remote Windows host supports the SMBv1 protocol.

Description

The remote Windows host supports Server Message Block Protocol version 1 (SMBv1). Microsoft recommends that users discontinue the use of SMBv1 due to the lack of security features that were included in later SMB versions. Additionally, the Shadow Brokers group reportedly has an exploit that affects SMB; however, it is unknown if the exploit affects SMBv1 or another version. In response to this, US-CERT recommends that users disable SMBv1 per SMB best practices to mitigate these potential issues.

See Also

<https://blogs.technet.microsoft.com/filecab/2016/09/16/stop-using-smb1/>

<https://support.microsoft.com/en-us/help/2696547/how-to-detect-enable-and-disable-smbv1-smbv2-and-smbv3-in-windows-and>

<http://www.nessus.org/u?8dcab5e4>

<http://www.nessus.org/u?234f8ef8>

<http://www.nessus.org/u?4c7e0cf3>

Solution

Disable SMBv1 according to the vendor instructions in Microsoft KB2696547. Additionally, block SMB directly by blocking TCP port 445 on all network boundary devices. For SMB over the NetBIOS API, block TCP ports 137 / 139 and UDP ports 137 / 138 on all network boundary devices.

Risk Factor

None

References

XREF IAVT:0001-T-0710

Plugin Information

Published: 2017/02/03, Modified: 2020/09/22

Plugin Output

192.168.100.22 (tcp/445/cifs)

The remote host supports SMBv1.

100871 (1) - Microsoft Windows SMB Versions Supported (remote check)

Synopsis

It was possible to obtain information about the version of SMB running on the remote host.

Description

Nessus was able to obtain the version of SMB running on the remote host by sending an authentication request to port 139 or 445.

Note that this plugin is a remote check and does not work on agents.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/06/19, Modified: 2019/11/22

Plugin Output

192.168.100.22 (tcp/445/cifs)

```
The remote host supports the following versions of SMB :  
SMBv1
```

104410 (1) - Target Credential Status by Authentication Protocol - Failure for Provided Credentials

Synopsis

Nessus was unable to log into the detected authentication protocol, using the provided credentials, in order to perform credentialed checks.

Description

Nessus failed to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials.

There may have been a failure in protocol negotiation or communication that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may have been invalid. A protocol failure may indicate a compatibility issue with the protocol configuration. A protocol failure due to an environmental issue such as resource or congestion issues may also prevent valid credentials from being identified. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.
- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

Address the reported problem(s) so that credentialed checks can be executed.

Risk Factor

None

References

XREF IAVB:0001-B-0503

Plugin Information

Published: 2017/11/06, Modified: 2020/10/19

Plugin Output

Nessus was unable to log into the following host for which credentials have been provided :

Protocol : SSH
Port : 22
Failure details :

- User : msfadmin

- Plugin : ssh_rate_limiting.nasl
Plugin ID : 122501
Plugin Name : SSH Rate Limited Device
Message :

Failed to authenticate using publickey authentication.

- Plugin : netstat_portscan.nasl
Plugin ID : 14272
Plugin Name : Netstat Portscanner (SSH)
Message :

Failed to authenticate using publickey authentication.

- Plugin : ssh_check_compression.nasl
Plugin ID : 104411
Plugin Name : SSH Compression Error Checking
Message :

Failed to authenticate using publickey authentication.

- Plugin : ssh_get_info2.nasl
Plugin ID : 97993
Plugin Name : OS Identification and Installed Software Enumeration over SSH v2 (Using New SSH Library)
Message :

Failed to authenticate using publickey authentication.

- Plugin : ssh_get_info.nasl
Plugin ID : 12634
Plugin Name : Authenticated Check : OS Name and Installed Package Enumeration
Message : Public key authentication failed.

104887 (1) - Samba Version

Synopsis

It was possible to obtain the samba version from the remote operating system.

Description

Nessus was able to obtain the samba version from the remote operating by sending an authentication request to port 139 or 445. Note that this plugin requires SMB1 to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/11/30, Modified: 2019/11/22

Plugin Output

192.168.100.22 (tcp/445/cifs)

```
The remote Samba Version is : Samba 3.0.20-Debian
```


106716 (1) - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check)

Synopsis

It was possible to obtain information about the dialects of SMB2 and SMB3 available on the remote host.

Description

Nessus was able to obtain the set of SMB2 and SMB3 dialects running on the remote host by sending an authentication request to port 139 or 445.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/02/09, Modified: 2020/03/11

Plugin Output

192.168.100.22 (tcp/445/cifs)

```
The remote host does NOT support the following SMB dialects :
_version_  _introduced in windows version_
2.0.2      Windows 2008
2.1        Windows 7
2.2.2      Windows 8 Beta
2.2.4      Windows 8 Beta
3.0        Windows 8
3.0.2      Windows 8.1
3.1        Windows 10
3.1.1      Windows 10
```

118224 (1) - PostgreSQL STARTTLS Support

Synopsis

The remote service supports encrypting traffic.

Description

The remote PostgreSQL server supports the use of encryption initiated during pre-login to switch from a cleartext to an encrypted communications channel.

See Also

<https://www.postgresql.org/docs/9.2/protocol-flow.html#AEN96066>

<https://www.postgresql.org/docs/9.2/protocol-message-formats.html>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/10/19, Modified: 2022/04/11

Plugin Output

192.168.100.22 (tcp/5432/postgresql)

```
Here is the PostgreSQL's SSL certificate that Nessus
was able to collect after sending a pre-login packet :
```

```
----- snip -----
Subject Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Issuer Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
```

Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Serial Number: 00 FA F9 3A 4C 7F B6 B9 CC

Version: 1

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Mar 17 14:07:45 2010 GMT

Not Valid After: Apr 16 14:07:45 2010 GMT

Public Key Info:

Algorithm: RSA Encryption

Key Length: 1024 bits

Public Key: 00 D6 B4 13 36 33 9A 95 71 7B 1B DE 7C 83 75 DA 71 B1 3C A9
7F FE AD 64 1B 77 E9 4F AE BE CA D4 F8 CB EF AE BB 43 79 24
73 FF 3C E5 9E 3B 6D FC C8 B1 AC FA 4C 4D 5E 9B 4C 99 54 0B
D7 A8 4A 50 BA A9 DE 1D 1F F4 E4 6B 02 A3 F4 6B 45 CD 4C AF
8D 89 62 33 8F 65 BB 36 61 9F C4 2C 73 C1 4E 2E A0 A8 14 4E
98 70 46 61 BB D1 B9 31 DF 8C 99 EE 75 6B 79 3C 40 A0 AE 97
00 90 9D DC 99 0D 33 A4 B5

Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits

Signature: 00 92 A4 B4 B8 14 55 63 25 51 4A 0B C3 2A 22 CF 3A F8 17 6A
0C CF 66 AA A7 65 2F 48 6D CD E3 3E 5C 9F 77 6C D4 44 54 1F
1E 84 4F 8E D4 8D DD AC 2D 88 09 21 A8 DA 56 2C A9 05 3C 49
68 35 19 75 0C DA 53 23 88 88 19 2D 74 26 C1 22 65 EE 11 68
83 6A 53 4A 9C 27 CB A0 B4 E9 8D 29 0C B2 3C 18 5C 67 CC 53
A6 1E 30 D0 AA 26 7B 1E AE 40 B9 29 01 6C 2E BC A2 19 94 7C
15 6E 8D 30 38 F6 CA 2E 75

----- snip ----- [...]

135860 (1) - WMI Not Available

Synopsis

WMI queries could not be made against the remote host.

Description

WMI (Windows Management Instrumentation) is not available on the remote host over DCOM. WMI queries are used to gather information about the remote host, such as its current state, network interface configuration, etc.

Without this information Nessus may not be able to identify installed software or security vulnerabilities that exist on the remote host.

See Also

<https://docs.microsoft.com/en-us/windows/win32/wmisdk/wmi-start-page>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2020/04/21, Modified: 2023/11/14

Plugin Output

192.168.100.22 (tcp/445/cifs)

```
Can't connect to the 'root\CIMV2' WMI namespace.
```

149334 (1) - SSH Password Authentication Accepted

Synopsis

The SSH server on the remote host accepts password authentication.

Description

The SSH server on the remote host accepts password authentication.

See Also

<https://tools.ietf.org/html/rfc4252#section-8>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/05/07, Modified: 2021/05/07

Plugin Output

192.168.100.22 (tcp/22/ssh)

153588 (1) - SSH SHA-1 HMAC Algorithms Enabled

Synopsis

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Description

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Although NIST has formally deprecated use of SHA-1 for digital signatures, SHA-1 is still considered secure for HMAC as the security of HMAC does not rely on the underlying hash function being resistant to collisions.

Note that this plugin only checks for the options of the remote SSH server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/09/23, Modified: 2022/04/05

Plugin Output

192.168.100.22 (tcp/22/ssh)

```
The following client-to-server SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :
```

```
hmac-sha1
hmac-sha1-96
```

```
The following server-to-client SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :
```

```
hmac-sha1
hmac-sha1-96
```

181418 (1) - OpenSSH Detection

Synopsis

An OpenSSH-based SSH server was detected on the remote host.

Description

An OpenSSH-based SSH server was detected on the remote host.

See Also

<https://www.openssh.com/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/09/14, Modified: 2023/12/27

Plugin Output

192.168.100.22 (tcp/22/ssh)

```
Path      : /  
Version   : 4.7p1  
Distribution : debian-8ubuntu1
```