Rajalakshmi Engineering College

Name: Paarthiv suriya sundaram nagarajan

Email: 240701376@rajalakshmi.edu.in

Roll no: 240701376 Phone: 9445142850

Branch: REC

Department: I CSE FD

Batch: 2028

Degree: B.E - CSE



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_MCQ_Updated

Attempt : 1 Total Mark : 20

Marks Obtained: 19

Section 1: MCQ

1. In what order will they be removed If the elements "A", "B", "C" and "D" are placed in a queue and are deleted one at a time

Answer

ABCD

Status: Correct Marks: 1/1

2. Insertion and deletion operation in the queue is known as

Answer

Enqueue and Dequeue

Status: Correct

Marks : 1/1

3. After performing this set of operations, what does the final list look to contain?

InsertFront(10); InsertFront(20); InsertRear(30); DeleteFront(); InsertRear(40); InsertRear(10); DeleteRear();

InsertRear(15);

Answer

display();

AO 10 30 10 15

Status: Wrong Marks: 0/1

4. Which one of the following is an application of Queue Data Structure?

Answer

All of the mentioned options

Status: Correct Marks: 1/1

5. What does the front pointer in a linked list implementation of a queue contain?

Answer

The address of the first element

Status: Correct Marks: 1/1

6. Which of the following can be used to delete an element from the front end of the queue?

Answer

public Object deleteFront() throws emptyDEQException{if(isEmpty())throw new emptyDEQException("Empty");else{Node temp = head.getNext();Node cur = temp.getNext();Object e = temp.getEle();head.setNext(cur);size--;return e;}}

Status: Correct Marks: 1/1

7. What will be the output of the following code?

```
#include <stdio.h>
#include <stdlib.h>
#define MAX_SIZE 5
typedef struct {
  int* arr;
int front;
  int rear:
  int size;
} Queue;
Queue* createQueue() {
  Queue* queue = (Queue*)malloc(sizeof(Queue));
  queue->arr = (int*)malloc(MAX_SIZE * sizeof(int));
  queue->front = -1;
  queue->rear = -1;
  queue->size = 0;
  return queue;
int isEmpty(Queue* queue) {
  return (queue->size == 0);
int main() {
  Queue* queue = createQueue();
  printf("Is the queue empty? %d", isEmpty(queue));
  return 0:
}
Answer
Is the queue empty? 1
Status: Correct
```

```
8. What will the output of the following code?
#include <stdio.h>
   #include <stdlib.h>
   typedef struct {
      int* arr;
      int front;
      int rear;
      int size;
   } Queue;
   Queue* createQueue() {
      Queue* queue = (Queue*)malloc(sizeof(Queue));
      queue->arr = (int*)malloc(5 * sizeof(int));
    queue -> front = 0;
      queue->rear = -1;
      queue->size = 0;
      return queue;
   int main() {
      Queue* queue = createQueue();
      printf("%d", queue->size);
      return 0;
   }
   Answer
   Status: Correct
                                                                      Marks: 1
   9. What is the functionality of the following piece of code?
   public void function(Object item)
      Node temp=new Node(item,trail);
      if(isEmpty())
        head.setNext(temp);
        temp.setNext(trail);
```

```
else
    Node cur=head.getNext();
    while(cur.getNext()!=trail)
       cur=cur.getNext();
    cur.setNext(temp);
  }
  size++;
Answer
Insert at the rear end of the dequeue
Status: Correct
```

10. The process of accessing data stored in a serial access memory is similar to manipulating data on a

Answer

Queue

Status: Correct Marks: 1/1

11. A normal queue, if implemented using an array of size MAX_SIZE, gets full when

Answer

Rear = MAX_SIZE - 1

Status: Correct Marks: 1/1

12. The essential condition that is checked before insertion in a queue is?

Answer

Overflow

Status: Correct Marks: 1/1

```
13. What will be the output of the following code?
 #include <stdio.h>
#define MAX_SIZE 5
typedef struct {
   int arr[MAX_SIZE];
   int front;
   int rear;
   int size;
 } Queue;
void enqueue(Queue* queue, int data) {
   if (queue->size == MAX_SIZE) {
     return;
   queue->rear = (queue->rear + 1) % MAX_SIZE;
   queue->arr[queue->rear] = data;
   queue->size++;
int dequeue(Queue* queue) {
   if (queue->size == 0) {
     return -1;
   int data = queue->arr[queue->front];
   queue->front = (queue->front + 1) % MAX_SIZE;
   queue->size--;
   return data;
 }
int main() {
   Queue queue;
   queue.front = 0;
   queue.rear = -1;
   queue.size = 0;
   enqueue(&queue, 1);
   enqueue(&queue, 2);
   enqueue(&queue, 3);
```

```
printf("%d ", dequeue(&queue));
printf("%d ", dequeue(&queue));
enqueue(&queue, 4);
enqueue(&queue, 5);
printf("%d ", dequeue(&queue));
printf("%d ", dequeue(&queue));
return 0;
}
Answer
1 2 3 4
Status : Correct
```

14. Which operations are performed when deleting an element from an array-based queue?

Marks: 1/1

Answer

Dequeue

Status: Correct Marks: 1/1

15. What are the applications of dequeue?

Answer

All the mentioned options

Status: Correct Marks: 1/1

16. In linked list implementation of a queue, the important condition for a queue to be empty is?

Answer

FRONT is null

Status: Correct Marks: 1/1

17. Which of the following properties is associated with a queue?

Answer

First In First Out

Status: Correct Marks: 1/1

18. In a linked list implementation of a queue, front and rear pointers are tracked. Which of these pointers will change during an insertion into a non-empty queue?

Answer

Only rear pointer

Status: Correct Marks: 1/1

19. Front and rear pointers are tracked in the linked list implementation of a queue. Which of these pointers will change during an insertion into the EMPTY queue?

Answer

Both front and rear pointer

Status: Correct Marks: 1/1

20. When new data has to be inserted into a stack or queue, but there is no available space. This is known as

Answer

overflow

Status: Correct Marks: 1/1

240101316

240101316