Assignment No. <4.2>	
<Bubble sort>	
Course Code: CPE007	**Program:** Computer Engineering
Course Title: Programming logic and design	**Date Performed:9/11/2025**
Section: CPE11S1	**Date Submitted:9/11/2025**
Name(s): Hanz Rhayven M. Pabalan	**Instructor: Engr. Jimlord Quejado**
6. Output	

CODE:

main.cpp

Share

```cpp
#include <iostream>
using namespace std;

int main() {
    int num[] = {5, 3, 4, 1, 2};
    int n = 5;

    cout << "Normal: ";
    for (int i = 0; i < n; i++) cout << num[i] << " ";
    cout << endl;

    // Bubble sort
    for (int i = 0; i < n - 1; i++) {
        for (int j = 0; j < n - i - 1; j++) {
            if (num[j] > num[j+1]) {
                int temp = num[j];
                num[j] = num[j+1];
                num[j+1] = temp;
            }
        }
    }

    cout << "Bubble Sorted: ";
    for (int i = 0; i < n; i++) cout << num[i] << " ";
    cout << endl;

    return 0;
}
```

OUTPUT:

Output

```
Normal: 5 3 4 1 2
Bubble Sorted: 1 2 3 4 5


=== Code Execution Successful ===
```

2. A comprehensive discussion of how bubble sort works

- bubble sort make the original works different or the opposite, it makes more faster if you need the opposite of your code or target.

7. Supplementary Activity
8. Conclusion
My conclusion about bubble sort is it makes the output easy because you can swap them or make the original opposite, and the use of it I think this boost my skills a little bit because every task sir gave us essential learnings and skill.
9. Assessment Rubric