

Seatwork No. <4.2>	
<Pointers >	
Course Code: CPE007	Program: Computer Engineering
Course Title: Programming logic and design	Date Performed: 9/18/2025
Section: CPE11S1	Date Submitted:9/18/2025
Name(s): Hanz Rhayven M, Pabalan	Instructor: Engr. Jimlord Quejado

6. Output

```
MONDAY.cpp chest.cpp basic.cpp
1  #include <iostream>
2  using namespace std;
3
4  int main() {
5      const int size = 10;
6      int scores [size] = {95, 85, 78, 88, 92, 80, 75, 80, 89, 91};
7      cout<<"scores array: ";
8      for(int i=0; i <size; i++){
9          cout<<scores[i]<<" ";
10
11
12      }
13      cout <<endl<<endl;
14      for(int i = 0; i <size; i++) {
15
16          cout<<"address of element "<<i<<": "<<&scores[i]<<endl;
17      }
18
19      cout<<endl<<endl;
20      int *scorePtr;
21      scorePtr = &scores[0];
22
23      cout<<"The adress of the array[0]: "<<*scorePtr<<endl;
24      cout<<"The deferenced pointer: "<<scorePtr<<endl;
25      cout<<endl<<endl;
26
27
28      int numBytes = sizeof(scores);
29      cout<<"The number of bytes of the array is:"<<numBytes<<endl;
30      return 0;
31
32 }
```

Output:

```
C:\Users\hanz\OneDrive\Docu  X + v
scores array: 95 85 78 88 92 80 75 80 89 91

address of element 0: 0x6ffdf0
address of element 1: 0x6ffdf4
address of element 2: 0x6ffdf8
address of element 3: 0x6ffdfc
address of element 4: 0x6ffe00
address of element 5: 0x6ffe04
address of element 6: 0x6ffe08
address of element 7: 0x6ffe0c
address of element 8: 0x6ffe10
address of element 9: 0x6ffe14

The address of the array[0]: 95
The deferenced pointer: 0x6ffdf0

The number of bytes of the array is:40

-----
Process exited after 1.972 seconds with return value 0
Press any key to continue . . . |
```

7. Supplementary Activity

Explanation: First, I put a constant int to have a steady **SIZE** value. Then, use int to initiate the scores then I put [SIZE] only because I already declare the value of **size** in the constant int, then I put the numbers. Next, I create **cout** to print the “scores array”. Then I create a for loop, inside of parenthesis I put 0 so it starts at 0 and I put <size; because the value of size is 10. Then I put **cout** so I can put the scores in it, then I put “ “ to have a space, and then I stop it with **endl**; then I create another for and I just did what I did in the first loop and, I put **cout** to print the “address element” then put the value in it. Then I assign the *scorePtr then I type scorePtr = &scores [0] to get the first value the address and the number, then I use cout to print the text inside, then I end it with endl; And I use int again to determine the bytes, so I put the name and sizeof (scores); the meaning of this is it will print the bytes of the whole scores so the output must be 40 bytes. Then I use cout again to have a text then endl; to stop the code.

8. Conclusion

This is my new knowledge the (const int, *scorePtr, and last the bytes) in the const int it is very helpful to know because you don't need to make value one by one because when you put const in it will make the value steady so you can just put the name of the variable to identify its value. Then in the *scorePtr its helpful to know as well because at first its kind of confusing but Sir. Jimlord explains it well that's why I understand it, because you can assign what number you will get and the address, and in the numbytes it makes the value get together it will multiply the value, And overall I have a new knowledge about this topic and will improve more by listening to sir.

9. Assessment Rubric