

# enumext

ENUMERATE EXERCISE SHEETS

V1.0 2024-10-04<sup>\*</sup>

©2024 by Pablo González<sup>†</sup>

CTAN: <https://www.ctan.org/pkg/enumext>

 <https://github.com/pablgonz/enumext>

## Abstract

This package provides enumerated list environments compatible with L<sup>A</sup>T<sub>E</sub>X tagging PDF for creating “simple exercise sheets” along with “multiple choice questions”, storing the “answers” to these in memory using `multicol` and `scontents` packages and the `l3seq` and `l3prop` modules.

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>	<b>6</b>	<b>The storage system</b>	<b>11</b>
1.1	Description and usage	3	6.1	Keys for storage system	11
1.2	The concept of left margin	3	6.1.1	Keys for <code>label</code> and <code>ref</code>	12
1.3	User interface	4	6.1.2	Keys for <code>wrap</code> and <code>display</code>	12
1.3.1	Internal counters	4	6.1.3	Keys for <code>debug</code> and <code>checking</code>	12
1.3.2	Public dimension	4	6.2	The command <code>\anskey</code>	12
1.3.3	Support for <code>multicol</code>	4	6.2.1	Keys for <code>\anskey</code>	13
1.3.4	Support for <code>minipage</code>	4	6.3	The environment <code>anskey*</code>	13
1.3.5	The <code>\label</code> and <code>\ref</code> system	4	6.3.1	Keys for <code>anskey*</code>	13
1.3.6	Support for <code>\footnote</code>	4	6.4	The environment <code>keyans</code>	14
<b>2</b>	<b>The environments provided</b>	<b>5</b>	6.4.1	The <code>\item*</code> in <code>keyans</code>	14
2.1	The environment <code>enumext</code>	5	6.5	The environment <code>keyanspic</code>	15
2.2	The environment <code>enumext*</code>	5	6.5.1	The command <code>\anspic</code>	15
2.3	The command <code>\item*</code>	5	6.6	Printing stored content	17
2.3.1	Keys for <code>\item*</code>	6	6.6.1	The command <code>\getkeyans</code>	17
2.4	The command <code>\item</code> in <code>enumext*</code>	6	6.6.2	The command <code>\foreachkeyans</code>	17
<b>3</b>	<b>The command <code>\setenumext</code></b>	<b>6</b>	6.6.3	The command <code>\printkeyans</code>	17
<b>4</b>	<b>The command <code>\setenumextmeta</code></b>	<b>6</b>	<b>7</b>	<b>Full examples</b>	<b>18</b>
<b>5</b>	<b>The <code>keyval</code> system</b>	<b>7</b>	<b>8</b>	<b>Tagged PDF examples</b>	<b>21</b>
5.1	Keys for <code>label</code> and <code>ref</code>	7	<b>9</b>	<b>The way of non-enumerated lists</b>	<b>21</b>
5.2	Keys for spaces	8	<b>10</b>	<b>References</b>	<b>23</b>
5.2.1	Vertical spaces	8	<b>11</b>	<b>Change history</b>	<b>24</b>
5.2.2	Horizontal spaces	9	<b>12</b>	<b>Index of Documentation</b>	<b>25</b>
5.3	Keys for <code>add code</code>	9	<b>13</b>	<b>Implementation</b>	<b>27</b>
5.4	Keys for <code>start</code> , <code>series</code> and <code>resume</code>	10	<b>14</b>	<b>Index of Implementation</b>	<b>141</b>
5.5	Keys for <code>multicols</code>	10			
5.6	Keys for <code>minipage</code>	10			
5.6.1	The command <code>\miniright</code>	10			
5.6.2	The key <code>mini-right</code>	11			

## Motivation and acknowledgments

Usually it is enough to use the classic `enumerate` environment to generate “simple exercise sheets” or “multiple choice questions”, the basic idea behind `enumext` is to cover three points:

1. To have a simple interface to be able to write “lists of exercises” with “answers”.
2. To have a simple interface for writing “multiple choice questions”.
3. To have a simple interface for placing “columns” and “drawings” or “tables”.

This package would not be possible without Phelype Oleinik who has collaborated and adapted a large part of the code and all L<sup>A</sup>T<sub>E</sub>X team for their great work and to the different members of the TeX-SX community who have provided great answers and ideas. Here a note of the main ones:

1. Answer given by Alan Munn in `\topsep`, `\itemsep`, `\partopsep`, `\parsep` - what do they each mean (and what about the bottom)?
2. Answer given by Enrico Gregorio in `Understanding minipages` - aligning at top
3. Answer given by Ulrich Diez in `Different mechanics of hyperlink vs. hyperref`
4. Answer given by Enrico Gregorio in `Minipage and multicols`, vertical alignment

<sup>\*</sup>This file describes a documentation for v1.0, last revised 2024-10-04.

<sup>†</sup>E-mail: [pablgonz@educarchile.cl](mailto:pablgonz@educarchile.cl).

License and Requirements

Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License (lpp), version 1.3 or later (<https://www.latex-project.org/lppl.txt>). The software has the status “maintained”.  
The enumext package loads and requires multicol[3] and scontents[4] packages, need to have a modern T<sub>E</sub>X distribution such as T<sub>E</sub>X Live or MiK<sub>T</sub>E<sub>X</sub>. It has been tested with the standard classes provided by L<sup>A</sup>T<sub>E</sub>X: book, report, article and letter on 10pt, 11pt and 12pt.

1 Introduction

In the L<sup>A</sup>T<sub>E</sub>X world there are many useful packages and classes for creating “lists of exercises”, “worksheets” or “multiple choice questions”, classes like exam[1] and packages like xsim[2] do the job perfectly, but they don’t always fit the basic day to day needs.

In my work (and in the work of many teachers) it is common to use “simple exercise sheets” also known as “informal lists of exercises”, as an example:

1. Factor  $x^2 - 2x + 1$

2. Factor  $3x + 3y + 3z$

3. True False

(a)  $\alpha > \delta$

(b) L<sup>A</sup>T<sub>E</sub>X is cool?

4. Related to Linux
- (a) You use linux?

(b) Usually uses the package manager?

(c) Rate the following package and class

i. xsim-exam

ii. xsim

iii. exsheets

Sometimes we are also interested in showing the “answers” along with the questions:

1. Factor  $x^2 - 2x + 1$

\* 

$(x - 1)^2$

2. Factor  $3x + 3y + 3z$

\* 

$3(x + y + z)$

3. True False

(a)  $\alpha > \delta$

\* 

False

(b) L<sup>A</sup>T<sub>E</sub>X is cool?

\* 

Very True!

4. Related to Linux
- (a) You use linux?

\* 

Yes

(b) Usually uses the package manager?

\* 

Yes, dnf

(c) Rate the following package and class

i. xsim-exam

\* 

doesn't exist for now :(

ii. xsim

\* 

very good

iii. exsheets

\* 

obsolete

Or we are interested in referring to a specific question and its “answer”, for example:

The answer to 3.(b) is “Very True!” and the answer to 4.(c).ii is “very good”.

Or we are interested in printing all the “answers”:

1.  $(x - 1)^2$

2.  $3(x + y + z)$

3. (a) False

(b) Very True!

4. (a) Yes
- ⌘ (b) Yes, dnf

⌘ (c) i. doesn't exist for now :(

⌘ ii. very good

⌘ iii. obsolete

⌘

Another very common thing to use in my work is “multiple choice questions”, for example:

1. First type of questions

A) value

B) correct

C) value

D) value

2. Second type of questions

I.  $2\alpha + 2\delta = 90^\circ$

II.  $\alpha = \delta$

III.  $\angle EDF = 45^\circ$

A) I only

B) II only

C) I and II only

D) I and III only

E) I, II, and III

\* 3. Third type of questions

(1)  $2\alpha + 2\delta = 90^\circ$

(2)  $\angle EDF = 45^\circ$

A) value

B) value

C) value

D) value

E) value
4. Question with image and label below:

A

A)

B


B)

A

C)

A

D)



E)

5. Question with image on left side:

A) value

B) value

C) value

D) correct

E) value

B
- Where what we are interested in the *label* and a “short note” that we leave as an explanation, and then print them:
- ©2024 by Pablo González L
- 2 / 156

1. B)  $x = 5$

2. D)

3. C) some note
- ⌘ 4. E) A duck

⌘ 5. D) “other note”

⌘
- ⌘

⌘

⌘

These “*simple worksheets*” or “*multiple choice questions*” appear to be easy to obtain using a combination of the `enumerate`, `minipage` and `multicols` environments, but like many things, what “*looks simple*” is not so simple.

The `enumext` package was created and designed to meet these small requirements in the creation of “*simple worksheets*” and “*multiple choice questions*”.

1.1 Description and usage

The `enumext` package defines enumerated environments using the `list` environment provided by  $\text{\LaTeX}$ , but “*does not redefine*” any internal commands associated with it such as `\list`, `\endlist` or `\item` outside of the “*scope*” in which they are defined.

- 🟢

This package is NOT intend to replace the `enumerate` environment nor replace the powerful `enumitem`[6], the approach is intended to work without hindering either of them.

This package can be used with `xelatex`, `lualatex`, `pdflatex` and the classical `latex»dvips»ps2pdf` and is present in  $\text{\TeX}$  Live and  $\text{\MiKTeX}$ , use the package manager to install. For manual installation, download `enumext.zip` and unzip it, run `lualatex enumext.dtx` and move all files to appropriate locations, then run `mktexlsr`. To produce the documentation run `lualatex enumext.dtx` two times.

enumext.sty

enumext.pdf

README.md

enumext.dtx

»

»

»

»

TDS:tex/latex/enumext/

TDS:doc/latex/enumext/

TDS:doc/latex/enumext/

TDS:source/latex/enumext/

The package is loaded in the usual way:

\usepackage{enumext}

1.2 The concept of left margin

There is a direct relationship between the parameters `\leftmargin`, `\itemindent`, `\labelwidth` and `\labelsep` plus an “*extra space*” that makes it difficult to obtain the desired *horizontal spaces* in a `list` environment.

Usually we don’t want the `list` to go beyond the left margin of the page, but since these four values are related, that causes a problem. The `enumitem`[6] package adds the `\labelindent` parameter to solve some of these problems. A simplified representation of this in the figure 1.



Figure 1: Representation of horizontal lengths in `enumitem`.

The `enumext` package does NOT provide a user interface to set the values for `\leftmargin` and `\itemindent`, instead it provides the keys `list-offset` and `list-indent` which internally set the values for `\leftmargin` and `\itemindent`. The concepts of `\leftmargin` and `\itemindent` are different in `enumext`. The figure 2 shows the visual representation of idea.



Figure 2: Representation of horizontal lengths concept in `enumext`.

In this way we reduce a *little* the amount of parameters we have to pass. With the default values of keys `list-offset`, `list-indent`, `labelwidth` and `labelsep` the lists will have the (usually) expected output for “*simple worksheets*”. The figure 3 shows the visual representation.




Figure 3: Default horizontal lengths `list-offset=0pt`, `list-indent=\labelwidth+\labelsep` in `enumext`.

### 1.3 User interface

The user interface consists of two main list environments `enumext` (vertical) and `enumext*` (horizontal), the environment `anskey*` and the command `\anskey` to “store content” and the environments `keyans`, `keyans*` and `keyanspic` for multiple choice. It also provides the commands `\getkeyans` to print individual *stored content*, `\printkeyans` to print all *stored content*, `\miniright` for `minipage` and `\setenumext` to config all `[key = val]` options.

#### 1.3.1 Internal counters

The package `enumext` uses internally the `enumXi`, `enumXii`, `enumXiii`, `enumXiv` counters for the four nesting levels of the `enumext` environment, the `enumXv` counter for the `keyans` environment, the `enumXvi` counter for the `keyanspic` environment, the counter `enumXvii` for `enumext*` environment and the counter `enumXviii` for `keyans*` environment.

- If any package defines these counters or they are user-defined in the document, the package will return a fatal error and abort the load.

#### 1.3.2 Public dimension

The package `enumext` only provides a single public dimension `\itemwidth` and is intended for user convenience only and is not for internal use as such. The dimension `\itemwidth` is *rigid length* and contains the “width of the content” of each `\item` regardless of `labelwidth` and `labelsep`.

- If any package defines `\itemwidth` or they are user-defined `\itemwidth` in the document, the package will overwrite it without warning.

#### 1.3.3 Support for multicol

The package provides direct support for using the `multicol`[3] package. This allows to obtain directly a two-column output as shown in the figure 4.




Figure 4: Representation of the two column output for a nested level in `enumext` environment.

The “non starred” version of the `multicols` environment is always used together with the `\raggedcolumns` command and is controlled by `columns` and `columns-sep` keys. It can be used in all nesting levels of the environment `enumext` and the environment `keyans` and can together with the `mini-env` key. If you need to force a start a new column `\columnbreak` must be used (see §5.5).

- The `\columnseprule` command is not available as a key and is set to “zero” for the inner levels and the `keyans` environment. If the value of this is set inside the document, it will affect “all environments” that use the `columns` key.

#### 1.3.4 Support for minipage

The package provides direct support for `minipage` environment, this allows you to obtain an output like the one shown in figure 5.



Figure 5: Representation of the `mini-env` output for a nested level `enumext` environment.

The `minipage` environments on “left side” and “right side” is always used with “aligned on top” `[t]`. It can be used in all nesting levels of the environment `enumext` and the environment `keyans` and is controlled by `mini-env` and `mini-sep` keys. In order to switch from the “left” side `minipage` environment to the “right” side one must use the command `\miniright` (see §5.6).

#### 1.3.5 The \label and \ref system

This package provides a user interface like the `enumitem`[6] package to customize the references which is activated by the `ref` key (§5.1), the standard  $\TeX$  `\label` and `\ref` commands work as usual. It also provides an “internal reference” system for the “stored content” by means of the key `save-ref` (§6.1.1) when the key `save-ans` (§6.1) is active.

#### 1.3.6 Support for \footnote

This package provides an internal implementation for the `\footnote` command which is compatible with the `hyperref` package for the `enumext*` and `keyans*` environments, but will not produce the expected links, and if the `mini-env` key is used in `enumext` or `keyans` environments the output will look like the classic way they are displayed in the environment `minipage`.

The best way to solve this is to use Jean-François Burnol `footnotehyper`[9] package, it will support keeping the links if `hyperref` is loaded with the `hyperfootnotes=true` option (default) and will show the output numbered at the bottom of the page (as opposed to how it is displayed in the `minipage` environment). The way to load it is as follows:

```
\usepackage{footnotehyper}
\makesavenoteenv{enumext}
\makesavenoteenv{enumext*}
```

At the moment the `footnotehyper` package is not compatible with *tagged* PDF.

## 2 The environments provided

The package `enumext` provides two main list environments, the *vertical* environment `enumext` and the *horizontal* environment `enumext*`.

<code>enumext</code>	<code>\begin{enumext}[\langle keyval list \rangle]</code>	<code>\begin{enumext*}[\langle keyval list \rangle]</code>
<code>enumext*</code>	<code>\item \langle item content \rangle</code>	<code>\item \langle item content \rangle</code>
	<code>\item [\langle custom \rangle] \langle item content \rangle</code>	<code>\item [\langle custom \rangle] \langle item content \rangle</code>
	<code>\item* [\langle symbol \rangle] [\langle offset \rangle] \langle item content \rangle</code>	<code>\item* [\langle symbol \rangle] [\langle offset \rangle] \langle item content \rangle</code>
	<code>\end{enumext}</code>	<code>\end{enumext*}</code>

### 2.1 The environment `enumext`

The `enumext` is an environment that works in the same way as the standard `enumerate` environment provided by L<sup>A</sup>T<sub>E</sub>X, `\item` and `\item[\langle custom \rangle]` commands work in the usual way. The environment can be nested with at most “four levels” and the options can be configured globally using `\setenumext` command and locally using `[\langle key = val \rangle]` in the environment.

Example with `columns=2`

1. This text is in the first level.
- A. This text is in the fourth level.
- (a) This text is in the second level.
- X This text is in the first level.
- i. This text is in the third level.
- \* 2. This text is in the first level.

### 2.2 The environment `enumext*`

The `enumext*` is a *horizontal list environment* similar to the `enumerate*` environment provided by the `enumitem` package or `task` environment provided by the `task` package, `\item` and `\item[\langle custom \rangle]` work as usual. The options can be configured globally using `\setenumext` command and locally using `[\langle key = val \rangle]` in the environment.

Some considerations to take into account for this environment:

- The environment cannot be nested within itself or in the environment `keyans*`, but it can be nested within `enumext` and vice versa.
- Each “*item content*” in the environment is placed within a `minipage` environment whose *width* is stored in the dimension `\itemwidth` that NOT includes `labelwidth`, `labelsep`, only the *width of the content*.
- You cannot have floating environments like `figure` or `table` but `\footnote` with `hyperref` support is supported if the `footnotehyper` package is loaded.
- You cannot have any standard list environments like `itemize`, `enumerate`, `description`, `quote`, `quotation`, `verse`, `center`, `flushleft`, `flushright`, `verbatim`, `tabbing`, `trivlist`, `list` and all environments created with `\newtheorem`.

Example with `columns=2`

1. This text is in the first level.
2. This text is in the first level.
- X This text is in the first level.
- \* 4. This text is in the first level.

### 2.3 The command `\item*`

```
\item* \item*
\item* [\langle symbol \rangle]
\item* [\langle symbol \rangle] [\langle offset \rangle]
```

The `\item*`, `\item*[\langle symbol \rangle]` and `\item*[\langle symbol \rangle][\langle offset \rangle]` works like the numbered `\item`, but placing a `\langle symbol \rangle` to the “left” of the `\langle label \rangle` separated from it by the `\langle offset \rangle` set by the the *second optional argument*. The default values for `\langle symbol \rangle` and `\langle offset \rangle` are `\textasteriskcentered *` and the value set by `labelsep` key.

The *starred argument* “`*`” cannot be separated by spaces “`␣`” from the command, i.e. `\item*` and the *first optional argument* does “NOT” support *verbatim content*. Can be configure with the keys `item-sym*` and `item-pos*` locally in the environment or globally using `\setenumext` command (§3).

The behavior of `\item*` in the `enumext` and `enumext*` environments is NOT the same as in the `keyans` and `keyans*` environments.

2.3.1 Keys for \item\*

`item-sym*` = {<symbol>} default: \textasteriskcentered  
Sets the *symbol* to be displayed in the “left” of the box containing the current <label> set by `labelwidth` key for `\item*` in `enumext` and `enumext*`. The *symbol* can be in *text* or *math* mode, for example `item-sym*={\star}`.  
`item-pos*` = {<rigid length>} default: by levels  
Sets the *offset* between the box containing the current <label> defined by `labelwidth` key and the <symbol> set by `item-sym*` key. The default values are set by `labelsep` key at each level. If positive values are passed it will *offset to the left* and if negative values are passed it will *offset to the right*.

2.4 The command \item in enumext\*

The `\item` command for the `enumext*` environment provides an “first optional argument” `\item(<columns>)` which “joins items” between columns. Let’s consider the following examples adapted directly from the `task` package:

```
\begin{enumext*}[widest=10,columns=4]
  \item The first
  \item* The second
  \item The third
  \item The fourth
  \item(3)* The fifth item is way too long for this and needs three columns
  \item The sixth
  \item The seventh
  \item(2)[X] The eighth item is way too long for this and needs two columns
    (\the\itemwidth)
  \item The ninth
  \item[Z] The tenth (\the\itemwidth)
\end{enumext*}
```

1. The first
- \* 2. The second
3. The third
4. The fourth
- \* 5. The fifth item is way too long for this and needs three columns
6. The sixth
7. The seventh
- X The eighth item is way too long for this and needs two columns (196.17749pt)
9. The ninth
- Z The tenth (89.28171pt)

3 The command \setenumext

<code>\setenumext</code>	<code>\setenumext{&lt;key = val&gt;}</code>	<code>\setenumext[&lt;keyans*&gt;]{&lt;key = val&gt;}</code>
	<code>\setenumext[&lt;enumext, level&gt;]{&lt;key = val&gt;}</code>	<code>\setenumext[&lt;print, level&gt;]{&lt;key = val&gt;}</code>
	<code>\setenumext[&lt;enumext*&gt;]{&lt;key = val&gt;}</code>	<code>\setenumext[&lt;print, *&gt;]{&lt;key = val&gt;}</code>
	<code>\setenumext[&lt;keyans&gt;]{&lt;key = val&gt;}</code>	<code>\setenumext[&lt;print*&gt;]{&lt;key = val&gt;}</code>

The command `\setenumext` sets the <keys> on a global basis for environments `enumext`, `enumext*`, `keyans`, `keyans*` and the `\printkeyans` command. It can be used both in the preamble and in the body of the document as many times as desired.

The <keys> set in the *optional argument* of environments and commands have the *highest precedence*, overriding both options passed by `\setenumext`. If the *optional argument* is not passed, the first level of the environment `enumext` will be taken by default.

- The key `save-ans` that activate the “storage system” must NOT be passed through this command and must be passed directly in the *optional argument* of the “first level” of the environment in which they are executed.

4 The command \setenumextmeta

<code>\setenumextmeta</code>	<code>\setenumextmeta {&lt;key name&gt;}{&lt;key-one = val, key-two = val, ...&gt;}</code>
	<code>\setenumextmeta*{&lt;key name&gt;}{&lt;key-one = val, key-two = val, ...&gt;}</code>
	<code>\setenumextmeta [ &lt;enumext*&gt; ]{&lt;key name&gt;}{&lt;key-one = val, key-two = val, ...&gt;}</code>
	<code>\setenumextmeta [ &lt;enumext, level&gt; ]{&lt;key name&gt;}{&lt;key-one = val, key-two = val, ...&gt;}</code>

The command `\setenumextmeta` adds a new “meta-key” for the environments `enumext` and `enumext*`, the {<key name>} must be different from those defined by the package. If the *optional argument* is not passed, the new “meta-key” will be created for the “first level” of the environment `enumext`.

The *starred argument* ‘\*’ will create the new “meta-key” for the environment `enumext*` and for all levels of the environment `enumext`. For example: `\setenumextmeta*{midsep}{topsep=3pt, partopsep=0pt}` will create a new key `midsep` available for all levels of the `enumext` environment and the `enumext*` environment and we can use it like any other key so `\begin{enumext}[midsep]` and `\begin{enumext*}[midsep]` will be valid.



## 5 The keyval system

The  $\langle key = val \rangle$  system used by the `enumext` package is implemented using `l3keys` so it must be taken into consideration that those keys marked as “*value forbidden*”, that is  $\langle key \rangle$  is different from  $\langle key = \rangle$ .

All  $\langle keys \rangle$  described in this section are available for the `enumext`, `enumext*`, `keyans` and `keyans*` environments with the exception of the keys `series`, `resume`, `resume*` which are only available for the “*first level*” of the environments `enumext` and `enumext*`; and the keys `mini-right`, `mini-right*` which are only available for the `enumext*` and `keyans*` environments.

All  $\langle keys \rangle$  related to vertical or horizontal spacing accept a “*skip*” or “*dim*” expression if passed between braces, i.e. you do not need to use `\dimeval` or `\dimexpr` to perform calculations.

- It should be kept in mind that using any  $\langle key \rangle$  that sets a *rubber lengths* or *rigid lengths* for vertical or horizontal space on a level will influence the vertical and horizontal space for *inners levels* and `keyans`, `keyans*` and `keyanspic` environments.

### 5.1 Keys for label and ref

`label = { $\langle \backslash\alpha^* | \backslash\Alpha^* | \backslash\arabic^* | \backslash\roman^* | \backslash\Roman^* \rangle$ }` default: *by levels*

Sets the  $\langle label \rangle$  that will be printed at the *current level*. The default value for the first level of the environments `enumext` and `enumext*` are `\arabic^*`, for second level are `(\alph^*)`, for third level are `\roman^*`. and for fourth level are `\Alpha^*`. For `keyans` and `keyans*` environments the default value is `\Alpha^*`.

- This key is intended to give the basic structure with which the  $\langle label \rangle$  will be displayed, and the form in which it is used by standard “*label and ref*” and the “*internal label and ref*” system with the `save-ref` key. You cannot use commands with  $\langle label \rangle$  as an argument, for example `\emph{\langle\alph^*\rangle}` will return an error. For full customization of how  $\langle label \rangle$  is displayed use the `font`, `wrap-label` and/or `wrap-label*` keys.

`labelsep = { $\langle rigid length \rangle$ }` default: `0.3333em`

Sets the *horizontal space* between the box containing the current  $\langle label \rangle$  defined by `label` key and the text of an item on the first line. Internally sets the value of `\labelsep` for the current level.

`labelwidth = { $\langle rigid length \rangle$ }` default: *by label*

Sets the *width* of the box containing the current  $\langle label \rangle$  set by `label` key. Internally sets the value of `\labelwidth` for the current level. The default values are calculated by means of the *width* of a box by setting a *value* to the current counter using ‘0’ for `\arabic^*`, ‘M’ for `\Alpha^*`, ‘m’ for `\alph^*`, ‘VIII’ for `\Roman^*` and ‘viii’ for `\roman^*`.

`widest = { $\langle integer | string \rangle$ }` default: *empty*

Sets the `labelwidth` key pass the  $\langle integer \rangle$  or converting the  $\langle string \rangle$  of the form `\Alpha`, `\alph`, `\Roman` or `\roman` to a *value* for the current counter defined by `label` key, then calculating the *width* by means of a box. For example `widest={XXIII}` or `widest={23}` are equivalent. This key is useful when the default values of the `labelwidth` key are smaller than those actually used.

`font = { $\langle font commands \rangle$ }` default: *empty*

Sets the *font style* for the current  $\langle label \rangle$  defined by `label` key. For example `font={\bfseries\small}`.

`align = { $\langle left | right | center \rangle$ }` default: *left*

Sets the *aligned* of  $\langle label \rangle$  defined by `label` key on the current level in the label box.

`wrap-label = { $\langle code \{ \#1 \} \text{ more code } \rangle$ }` default: *empty*

Wraps the *current*  $\langle label \rangle$  defined by `label` key referenced by  $\{ \#1 \}$ . The  $\{ \langle code \rangle \}$  must be passed between braces. This key does not modify the value set by the `labelwidth` key and is applied only on `\item` and `\item*`. When using it in the `\setenumext` command it is necessary to use the *double hash* ‘ $\{ \# \#1 \}$ ’. For example `wrap-label={\fbox{\#1}}` or you can create a command:

```
\NewDocumentCommand \labelbx { s +m }
{%
  \IfBooleanTF{\#1}
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedright{\#2}}}}%
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{\#2}}}}%
}
```

and then pass it through the key `wrap-label={\labelbx{\#1}}` or `wrap-label={\labelbx*{\#1}}`.

`wrap-label* = { $\langle code \{ \#1 \} \text{ more code } \rangle$ }` default: *empty*

The same as the `wrap-label` key but also applies on `\item[custom]`.

- By default all the  $\langle keys \rangle$  described above are executed inside `\makebox` in the `enumext*` and `keyans*` environments.
- For compatibility with tagged PDF all  $\langle keys \rangle$  described above are executed inside `\makebox` in the `enumext` and `keyans` environments, this means that the document output may *not look* the same when `\DocumentMetadata` is active. If you use the `wrap-label` or `wrap-label*` keys you can add conditional code using `\IfDocumentMetadataTF`.

`ref = { $\langle code \{ \backslash\alpha^* | \backslash\Alpha^* | \backslash\arabic^* | \backslash\roman^* | \backslash\Roman^* \} \text{ more code } \rangle$ }` default: *empty*

Modifies the way *cross references* are displayed. The `label` key sets the default form of the *cross references*, by using this key you can define a different format, for example: `ref=\emph{\langle\alph^*\rangle}` is valid.

Internally it renews the command associated with each counter when it is executed, i.e., in the environment `enumext` the command `\theenumXi` is modified when the key is executed at the first level, `\theenumXii` when it is executed at the second level and `\theenumXiii` together with `\theenumXiv` when it is executed at the third and fourth levels.

- This must be kept in mind, since the values set by the `label` and `ref` keys are not cumulative by levels, so if you have used the `ref` key in the first level and then want to associate the counter with `label` or `ref` in the second level you must use the direct commands, i.e. `\arabic{enumXi}` to indicate the count of the first level instead of using `\theenumXi`.

## 5.2 Keys for spaces

`show-length = {⟨true | false⟩}`

default: *false*

Displays on the terminal the values for *all list parameters* at the current level. For *vertical spaces* show the values of `\topsep`, `\itemsep`, `\parsep` and `\partopsep`. For *horizontal spaces* show the values of `\labelwidth`, `\labelsep`, `\itemindent`, `\listparindent` and `\leftmargin`.

### 5.2.1 Vertical spaces

`topsep = {⟨rubber length | rigid length⟩}`

default: *by levels*

Set the *vertical space* added to both the top and bottom of the list. Internally sets the value of `\topsep` for the current level. The default value for the first level of the environments `enumext` and `enumext*` are `8.0pt` plus `2.0pt` minus `4.0pt`, for second level are `4.0pt` plus `2.0pt` minus `1.0pt`, for third and fourth level are `2.0pt` plus `1.0pt` minus `1.0pt`. For `keyans` and `keyans*` environments the default value is `4.0pt` plus `2.0pt` minus `1.0pt`.

`parsep = {⟨rubber length | rigid length⟩}`

default: *by levels*

Set the *vertical space* between paragraphs within an item. Internally sets the value of `\parsep` for the current level. The default value for the first level of the environments `enumext` and `enumext*` are `4.0pt` plus `2.0pt` minus `1.0pt`, for second level are `2.0pt` plus `1.0pt` minus `1.0pt`, for third and fourth level are `0pt`. For `keyans` and `keyans*` environments the default value is `2.0pt` plus `1.0pt` minus `1.0pt`.

- In the `enumext*` and `keyans*` environments this value is passed to `\parskip` within the `minipage` environment where “item content” is placed.

`partopsep = {⟨rubber length | rigid length⟩}`

default: *by levels*

Set the *vertical space* added, beyond `topsep`, to the “top” and “bottom” of the entire environment if the environment instance is preceded by a “blank line” or `\par` command. Internally sets the value of `\partopsep` for the current level. The default values for first and second level in environment `enumext` are `2.0pt` plus `1.0pt` minus `1.0pt`, for third and fourth level are `1.0pt` minus `1.0pt`. For the `keyans` environment the default value is `2.0pt` plus `1.0pt` minus `1.0pt`, and for the `keyans*` and `enumext*` environments it is available but *without* effect.

- The value of this parameter also affects the *inner levels* and the environments `keyans`, `keyanspic` and `keyans*`. Caution should be taken with “blank lines” or `\par` command “before” each environment or nested level when formatting the source code of document.  $\TeX$  will enter *⟨vertical mode⟩* and apply this value to the “top” and “bottom” the environment or nested level.

`itemsep = {⟨rubber length | rigid length⟩}`

default: *by levels*

Set the *vertical space* between items, beyond the `parsep`. Internally sets the value of `\itemsep` for the current level. The default value for the first level of the environments `enumext` and `enumext*` are `4.0pt` plus `2.0pt` minus `1.0pt`, for the rest of the levels are `2.0pt` plus `1.0pt` minus `1.0pt`. For `keyans` and `keyans*` environments the default value is `4.0pt` plus `2.0pt` minus `1.0pt`.

- In the `enumext*` and `keyans*` environments this value corresponds to the separation between rows.

`noitemsep` *⟨value forbidden⟩*

default: *not used*

This is a “meta-key” that does not receive an argument. Set `itemsep` and `parsep` equal to `0pt` the entire level of environment.

`nosep` *⟨value forbidden⟩*

default: *not used*

This is a “meta-key” that does not receive an argument. Sets all keys for vertical spacing equal to `0pt` the entire level of environment.

`base-fix` *⟨value forbidden⟩*

default: *not used*

This is a “meta-key” that does not receive an argument available *only* for the “first level” of environment `enumext`. Fix the *baseline* when an environment `enumext` is nested in `enumext*` and there is no material between the `\item` and the start of the environment for example `\item \begin{enumext}` within the environment `enumext*`. Internally sets the keys `topsep`, `above` and `above*` at `0pt`.

- The following *⟨keys⟩* should be used with “caution”, they are intended to be used at the “top” and “bottom” of the environment when the `columns` or `mini-env` keys do not provide adequate *vertical spaces*. The values passed can be *rubber* or *rigid* lengths, the way they are applied is the way you differ, using the star ‘\*’ *⟨keys⟩* applies `\vspace*` so that  $\TeX$  does *not discard* this space at page break.

`above = {⟨rubber length | rigid length⟩}`

default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the top of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space “above” the environment without hindering the value of the `topsep` key. The space is added with `\vspace` so is “discardable”.



`above*` = { $\langle rubber\ length \mid rigid\ length \rangle$ } default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the top of the entire level of environment. This key is intended to give a “*fine adjustment*” of the vertical space “*above*” the environment without hindering the value of the `topsep` key. The space is added with `\vspace*` so is “*not discardable*”.

`below` = { $\langle rubber\ length \mid rigid\ length \rangle$ } default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the bottom of the entire level of environment. This key is intended to give a “*fine adjustment*” of the vertical space on the “*below*” the environment without hindering the value of the `topsep` key. The space is added with `\vspace` so is “*discardable*”.

`below*` = { $\langle rubber\ length \mid rigid\ length \rangle$ } default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the bottom of the entire level of environment. This key is intended to give a “*fine adjustment*” of the vertical space on the “*below*” the environment without hindering the value of the `topsep` key. The space is added with `\vspace*` so is “*not discardable*”.

### 5.2.2 Horizontal spaces

`itemindent` = { $\langle rigid\ length \rangle$ } default: *0pt*

Extra *horizontal indentation*, beyond `labelsep`, of the “*first line*” off each item. This value must be greater than or equal to *0pt* and is applied internally using `\hspace` without modifying the value of `\itemindent`.

`rightmargin` = { $\langle rigid\ length \rangle$ } default: *0pt*

Set the *horizontal space* between the right margin of the environment and the right margin of the enclosing environment, the value it takes must be greater than or equal to *0pt*. Internally sets the value of `\rightmargin` for the current level.

`listparindent` = { $\langle rigid\ length \rangle$ } default: *0pt*

Sets the *horizontal space* indentation, beyond `list-indent`, for second and subsequent paragraphs within a list item. Internally sets the value of `\listparindent` for the current level.

`list-offset` = { $\langle rigid\ length \rangle$ } default: *0pt*

Sets the *horizontal translation* of the entire environment level from the left edge of the box defined by the `labelwidth` key. Internally sets the values of `\leftmargin` and `\itemindent` for the current level.

`list-indent` = { $\langle rigid\ length \rangle$ } default: *labelwidth + labelsep*

Sets the *indentation* of the whole environment under the box defined by `labelwidth` and `labelsep` keys. Internally sets the value of `\leftmargin` and `\itemindent` for the current level.

If `list-indent=0pt` is set in the environment `enumext` the  $\langle label \rangle$  will be part of the text, separated by the value of the `labelsep` key and the *first word*, in simple terms it will look like a “*common paragraph*”. This setting is equivalent (more or less) to the `wide` key provided by the `enumitem` package.

🔗 For the `enumext*` and `keyans*` environments the keys `list-indent` and `list-offset` have the same effect.

## 5.3 Keys for add code

The following  $\langle keys \rangle$  should be used with “*caution*”, they are intended to inject  $\{\langle code \rangle\}$  into different parts of the defined environments. We must keep in mind that the defined environments are based on the `list` base environment provided by `TeX` which is defined (simplified) as plain form `\list{\langle arg one \rangle}{\langle arg two \rangle}`. Using the `before*` key does not allow access to the `list` parameters defined by  $[\langle key = val \rangle]$ .

`before` = { $\langle code \rangle$ } default: *not used*

Execute  $\{\langle code \rangle\}$  “*before*” the environment starts. The  $\{\langle code \rangle\}$  must be passed between braces, is executed “*after*” performing all calculations related to the *list parameters* in the environment and the parameters sets by  $[\langle key = val \rangle]$  that is, in the second argument of the list after setting all the parameters `\begin{list}{\langle arg one \rangle}{\langle arg two \rangle}\{\langle code \rangle\}`.

`before*` = { $\langle code \rangle$ } default: *not used*

Execute  $\{\langle code \rangle\}$  “*before*” the environment starts. The  $\{\langle code \rangle\}$  must be passed between braces, is executed “*before*” performing all calculations related to the *list parameters* and  $[\langle key = val \rangle]$  sets in the environment that is, before the arguments defining the environment are executed:  $\{\langle code \rangle\}\backslash\begin{list}{\langle arg one \rangle}{\langle arg two \rangle}\{\langle arg two \rangle\}$ .

`first` = { $\langle code \rangle$ } default: *not used*

Executes  $\{\langle code \rangle\}$  when “*starting*” the environment. The  $\{\langle code \rangle\}$  must be passed between braces, is executed right “*after*” all *list parameters* are done, after the second argument of list, just before the first occurrence of `\item: \begin{list}{\langle arg one \rangle}{\langle arg two \rangle}\{\langle code \rangle\}\item.`

🔗 Keep in mind that the code set in this key will affect the entire “*body*” of the environment and therefore the inner levels of the list and the `keyans` environment. It is recommended to set this key per level. In the `enumext*` and `keyans*` environments this key is executed within the `minipage` environment in which “*item content*” is placed.

`after` = { $\langle code \rangle$ } default: *not used*

Execute  $\{\langle code \rangle\}$  “*after*” finishing the environment. The  $\{\langle code \rangle\}$  must be passed between braces.

## 5.4 Keys for start, series and resume

`start = {⟨integer | integer expression⟩}` default: 1  
Sets the *start value* of the numbering on the current level. The {⟨integer expression⟩} must be passed between braces, internally is evaluated and pass to the counter defined by `label` key on the current level, i.e. it is equivalent to enter `start={\dimeval{100*\value{chapter}}` or `start={100*\value{chapter}}`.

`start* = {⟨integer | string⟩}` default: not used  
Sets the *start value* of the numbering on the current level. Internally ⟨string⟩ is converted and passed as value to the counter defined by `label` key on the current level, i.e. it is equivalent to enter `start=5`, `start=E` or `start=v`.

The following ⟨keys⟩ are “only” available for the `enumext*` environment and the “first level” of the `enumext` environment and are ignored if set when nested within each other.

`series = {⟨series name⟩}` default: not used  
Stores the *keys* of the *optional argument* of the “first level” of the environment in which it is executed in {⟨series name⟩} which is used as an argument in the key `resume`. The ⟨keys⟩ stored in {⟨series name⟩} are not cumulative and are overwritten if the same {⟨series name⟩} is used again.

`resume = {⟨series name⟩}` default: not used  
Sets the *start value* and *options* for the “first level” continuing the numbering of the environment in which the `series={⟨series name⟩}` key was executed. If passed *without value* this will only set *start value* continue the numbering from the last environment in which `series={⟨series name⟩}` or `resume={⟨series name⟩}` is not present and if the `save-ans` key is active it will continue the numbering from the last environment in which it was executed. The *start value* can be overwritten using `start` or `start*` keys.

`resume* ⟨value forbidden⟩` default: not used  
Sets the *start value* and *options* for the “first level” continuing the numbering of the environment in which the `series={⟨series name⟩}` or `resume={⟨series name⟩}` keys are NOT present, if the `save-ans` key is active it will continue the numbering from the last environment in which it was executed. The *start value* can be overwritten using `start` or `start*` keys.

- For security reasons the `series` key will never save in {⟨series name⟩} the keys `series`, `resume`, `resume*`, `save-ans`, `save-key`, `start*` and `start`. When using the key `resume={⟨series name⟩}` it will have hierarchy in the ⟨keys⟩ that are saved in {⟨series name⟩}, in order to establish the value of a ⟨key⟩ already saved in {⟨series name⟩} it must be placed to the “right” of `resume={⟨series name⟩}`, the same thing happens with the `resume*` key, the exception is the `save-ans` key that must be placed on the “left” if you want to start the numbering with its value. The `resume` key passed “without value” must be exactly “without value”, i.e. `resume=` cannot be used and if executed before `resume*` it will affect the *start value*.

## 5.5 Keys for multicol

`columns = {⟨integer⟩}` default: 1  
Set the *number of columns* to be used by the `multicol` environment within the environment. The value must be a positive integer less than or equal to 10.

`columns-sep = {⟨rigid length⟩}` default: by level  
Set the *space between columns* used by the `multicol` environment within the environment. Internally sets the value of `\columnsep`, by default its value is equal to the sum of the values set in the keys `labelwidth` and `labelsep` of the current level.

- The `\footnote{⟨text⟩}` command in the nested levels of `multicol` will not work as expected, prefer the use of `\footnotemark[⟨number⟩]` inside the environment and `\footnotetext[⟨number⟩]{⟨text⟩}` outside the environment or via the after key.

## 5.6 Keys for minipage

`mini-env = {⟨rigid length⟩}` default: not used  
Sets the *width* of the `minipage` environment on the “right side”. This value added to the value set by the `mini-sep` key to determines the *width* of the `minipage` environment on the “left side”, taking `\linewidth` as the maximum reference value.

`mini-sep = {⟨rigid length⟩}` default: 0.3333em  
Sets the *space between* the `minipage` environment on the “left side” and the `minipage` environment on the “right side”. This separation is applied together with `\hfill`.

### 5.6.1 The command \miniright

---

```
\miniright \begin{enumext}[mini-env=⟨rigid length⟩] ⟨item's before⟩ \item \miniright ⟨content⟩ \end{enumext}
\begin{enumext}[mini-env=⟨rigid length⟩] ⟨item's before⟩ \item \miniright*⟨content⟩ \end{enumext}
```

---

The `\miniright` command close the `minipage` environment on the “left side” and opens the `minipage` environment on the “right side” by starting it with the `\centering` command. It must be placed “after” the last `\item` of the current environment and “before” starting the material to be placed on the “right side”.

The starred argument ‘\*’ inhibits the use of `\centering` command i.e. the usual L<sup>A</sup>T<sub>E</sub>X justification is maintained in the `minipage` on the “right side”.

- The `\footnote{⟨text⟩}` command in `minipage` environment will work as usual. If you prefer the footnotes to be numbered (not lowercase) and outside the environment, use `\footnotemark[⟨number⟩]` inside the environment and `\footnotetext[⟨number⟩]{⟨text⟩}` outside the environment or via the `after` key (see §1.3.6 for full support).

### 5.6.2 The key mini-right

In the horizontal list environments `enumext*` and `keyans*` it is not possible to use the `\miniright` command and the `mini-right` key must be used instead.

`mini-right = {⟨content⟩}` default: *not used*

Set the *content* for the drawing or tabular to be placed in the `minipage` environment on the “right side” by starting it with `\centering`. The `{⟨content⟩}` must be passed between braces.

`mini-right* = {⟨content⟩}` default: *not used*

Same as above, but *without* starting with `\centering`.

## 6 The storage system

The entire mechanism for “storing content” it is activated according to `save-ans` key on the “first level” of `enumext` or `enumext*` environments and it is ignored if they are established when they are nested inside each other. Only when this `⟨key⟩` is “active” the `\anskey` command and the environments `anskey*`, `keyans`, `keyans*` and `keyanspic` are available.

<pre>\begin{enumext}[save-ans={⟨store name⟩}]   \item Text \anskey{answer}   \item Text     \begin{keyans}       ...     \end{keyans} \end{enumext}</pre>	<pre>\begin{enumext}[save-ans={⟨store name⟩}]   \item Text \anskey{answer}   \item Text     \begin{keyanspic}       ...     \end{keyanspic} \end{enumext}</pre>
---	---

By executing the key `save-ans={⟨store name⟩}` the entire “structure” of the environment (excluding the *first level*) including the *optional argument* passed to the inner levels or the environment nested in it, along with the `⟨content⟩` passed to `\anskey` or `anskey*`, the current `⟨labels⟩` for `\item*` and `\anspic*` in the environments `keyans`, `keyans*` and `keyanspic` will be “stored” in a *sequence* `{⟨store name⟩}` and at the same time will be “stored” (without the “structure” or *optional argument*) in a *prop list* `{⟨store name⟩}`.

- For security reasons the *optional argument* of the inner levels or the nested environment are *filtered* by excluding all `⟨keys⟩` related to the “storage system” (§6.1) along with the `⟨keys⟩` `mini-env`, `mini-sep`, `mini-right`, `mini-right*`, `series`, `resume` and `resume*` when storing in *sequence* `{⟨store name⟩}` set by `save-ans` key.

### 6.1 Keys for storage system

- The only `⟨keys⟩` available for all levels of the `enumext` environment and the `enumext*` environment are `no-store` and `save-key`, the rest of the `⟨keys⟩` described in this section must be passed directly in the *optional argument* of the “first level” of the environment in which the key `save-ans` is executed. The key `save-ans` should NOT be passed with the command `\setenumext`.

`save-ans = {⟨store name⟩}` default: *not set*

Sets the *name* of the *sequence* and *prop list* in which the `{⟨contents⟩}` will be “stored” by `\anskey` and `anskey*` in `enumext` and `enumext*` environments and the current `⟨labels⟩` for `\item*` and `\anspic*` in the environments `keyans`, `keyans*` and `keyanspic`. If the *sequence* or *prop list* `{⟨store name⟩}` does not exist, it will be created globally and will not be *overwritten* if the key is used again.

`save-key = {⟨key list⟩}` default: *not set*

This key *overrides* the default “stored keys” of the *optional argument* of the inner levels or nested environment that will be passed to the *sequence*. The `⟨key list⟩` passed to this key ignores any `⟨keys⟩` in the “stored structure” and must be passed between braces. For example, if we execute at a second level:

```
\begin{enumext}[save-ans={⟨store name⟩}]
  \item Text \anskey{answer}
  \item Text
    \begin{enumext}[nosep, columns=2, save-key={columns=3}]
      ...
    \end{enumext}
\end{enumext}
```

The “stored keys” by default in the *sequence* `{⟨store name⟩}` would be `nosep`, `columns=2`, but using the key `save-key={columns=3}` will overwrite and the “stored key” in the *sequence* `{⟨store name⟩}` are only `columns=3` ignoring all the others.

`save-sep = {⟨text symbol⟩}` default: `{,}`

Sets the *text symbol* that will separate the current `⟨label⟩` to the *optional argument* passed to the `\item*` and `\anspic*` in the environments `keyans`, `keyans*` and `keyanspic` and storing them in the *sequence* and *prop list* `{⟨store name⟩}` set by `save-ans` key. The `{⟨text symbol⟩}` must always be passed between braces, whitespace ‘`␣`’ is preserved within the braces and only affects the “stored content” and not what is displayed when using the `show-ans` or `show-pos` keys.

### 6.1.1 Keys for label and ref

`save-ref` = {`<true | false>`} default: `false`  
 Activates the “*internal label and ref*” mechanism for referencing “*stored content*” in *prop list* {`<store name>`} set by `save-ans` key. To reference the location of the “*stored content*” within the environment you must use `\ref{<store name>:position}`, where `<position>` corresponds to the position occupied by the “*stored content*” in the *prop list* {`<store name>`} returned by the `show-pos` key. For example `\ref{test:4}` will return 3. (b) which corresponds to the location of the “*stored content*” at position 4 in *prop list* `test` within the environment in which the key `save-ans=test` was set.

`mark-ref` = {`<symbol>`} default: `\%`  
 Sets the *symbol* that will be displayed by the `\printkeyans` command only if the `hyperref` package is detected and the `save-ref` key are active. This “*symbol*” is used as a “*link*” between the environment in which the `save-ans` key was used and the place where the command is executed.

### 6.1.2 Keys for wrap and display

`wrap-ans` = {`<code> {#1} more code`} default: `\fbox+\parbox{#1}`  
 Wraps the *argument* passed to the `\anskey` and the *body* in `anskey*` environment referenced by {#1} when using the `show-ans` or `show-pos` keys. The {`<code>`} must be passed between braces and only affects the *argument* or *body* and NOT the “*stored content*” in the *sequence* and *prop list* {`<store name>`} set by `save-ans` key. If this key is passed using `\setenumext` it is necessary to use double ‘{#1}’.

`wrap-opt` = {`<code> {#1} more code`} default: `[{#1}]`  
 Wraps the *optional argument* passed to the `\item*` and `\anspic*` referenced by {#1} in the `keyans`, `keyans*` and `keyanspic` environments when using the `show-ans` or `show-pos` keys. The {`<code>`} must be passed between braces and only affects the current *optional argument* and NOT the “*stored content*” in the *sequence* and *prop list* {`<store name>`} set by `save-ans` key. If this key is passed using `\setenumext` it is necessary to use double ‘{#1}’.

`show-ans` = {`<true | false>`} default: `false`  
 Displays the *argument* passed to the `\anskey`, the *body* for `anskey*` environment, the `<label>` for `\item*` and `\anspic*` at the place where it is executed. If the *optional argument* is present in `\item*` or `\anspic*` it will be shown using `wrap-opt` key.

`mark-ans` = {`<symbol>`} default: `\textasteriskcentered`  
 Sets the *symbol* to be displayed in the left margin for `\anskey`, `anskey*`, `\item*` and `\anspic*` in the place where they are executed when using the key `show-ans`.

`mark-pos` = {`<left | right>`} default: `left`  
 Sets the *aligned* of the *symbol* defined by `mark-ans` key. The “*symbol*” is aligned in a box with the same dimensions of the label box defined by `labelwidth` key on the current level and separated by the value of the `labelsep` key.

### 6.1.3 Keys for debug and checking

`show-pos` = {`<true | false>`} default: `false`  
 Displays the *position* occupied by the “*stored content*” by `\anskey`, `anskey*`, `\item*` and `\anspic*` in the *prop list* {`<store name>`} set by `save-ans` key. This position is used by the `\getkeyans` command and by the `\ref` command if the `save-ref` key is active.

`check-ans` = {`<true | false>`} default: `false`  
 Enables the *checking answer* mechanism displaying an appropriate message on the terminal. This key works under the logic that each `\item` or `\item*` that does not open an inner level or nested environment contains “*only one answer*” or “*only one execution*” of the `\anskey` or `anskey*`. It is intended to be used in conjunction with the `no-store` key.

`no-store` `<value forbidden>` default: `not used`  
 This is a *meta-key* that does not receive an argument and disables the structure stored in the *sequence* {`<store name>`} set by `save-ans` key at the entire level or a nested environment in which it runs. This key is intended for use in internal levels or nested `enumext` or `enumext*` environments in which you want to use `enumext` or `enumext*` but “*without*” using the `\anskey`, “*without*” use `anskey*`, “*without*” interfering with the `check-ans` key and “*without*” storing an unwanted structure in the *sequence* {`<store name>`}.

## 6.2 The command `\anskey`

---

`\anskey` `\anskey[<keys>]{<content>}`

---

The command `\anskey` takes a mandatory non empty argument {`<content>`} and “*stores*” it in the *sequence* and *prop list* {`<store name>`} set by `save-ans` key. By design the command cannot be nested or passed *verbatim material* in the argument and it is assumed that each *numbered* `\item` or `\item*` within the environment in which it is active it has a “*single execution*” of `\anskey` unless `\item` or `\item*` open a nested level or use the `no-store` key.

If `save-ref` key are active and the `hyperref`[8] package is detected, `\hyperlink` and `\hypertarget` will be used, otherwise the usual “*label and ref*” system provided by L<sup>A</sup>T<sub>E</sub>X will be used.



The `\anskey` command is available for all levels of the `enumext` environment and the `enumext*` environment, but is disabled for the `keyans`, `keyans*` and `keyanspic` environments.

6.2.1 Keys for `\anskey`

By default the  $\langle content \rangle$  passed to `\anskey` when “storing” in the *sequence*  $\{ \langle store name \rangle \}$  has the form `\item  $\langle content \rangle$` , the following *keys* allow modifying the way in which it is “stored” in the *sequence*.

- `break-col`  $\langle value forbidden \rangle$  default: *not used*
- Stores  $\{ \langle content \rangle \}$  in the *sequence*  $\{ \langle store name \rangle \}$  of the form `\columnbreak \item  $\langle content \rangle$` .
- `item-join` =  $\{ \langle columns \rangle \}$  default: *not set*
- Set the *number of columns* to be used for `\item`( $\langle columns \rangle$ ) and stores  $\{ \langle content \rangle \}$  in the *sequence*  $\{ \langle store name \rangle \}$  of the form `\item`( $\langle columns \rangle$ )  $\langle content \rangle$ .
- `item-star`  $\langle value forbidden \rangle$  default: *not used*
- Stores  $\{ \langle content \rangle \}$  in the *sequence*  $\{ \langle store name \rangle \}$  of the form `\item*`  $\langle content \rangle$ .
- `item-sym*` =  $\{ \langle symbol \rangle \}$  default: *not set*
- Sets the *symbol* for `\item*` when using the key `item-star` and stores  $\{ \langle content \rangle \}$  in the *sequence*  $\{ \langle store name \rangle \}$  of the form `\item*`[ $\langle symbol \rangle$ ]  $\langle content \rangle$ . The *symbol* can be in text or math mode, for example `item-sym*={\ast}` stores `\item*`[ $\ast$ ]  $\langle content \rangle$ .
- `item-pos*` =  $\{ \langle rigid length \rangle \}$  default: *not set*
- Sets the *offset* for `\item*` when using the keys `item-star` and `item-sym*` and stores  $\{ \langle content \rangle \}$  in the *sequence*  $\{ \langle store name \rangle \}$  of the form `\item*`[ $\langle symbol \rangle$ ][ $\langle offset \rangle$ ]  $\langle content \rangle$ .

Example

```
\begin{enumext}[save-ans=test,show-ans=true]
  \item* Text containing our instructions or questions. \anskey{\first answer}
  \item Text containing our instructions or questions.
    \begin{enumext}
      \item Question.\anskey{\second answer}
    \end{enumext}
  \item Text containing our instructions or questions. \anskey{\third answer}
  \item Text containing our instructions or questions. \anskey{\fourth answer}
\end{enumext}
```

1. Text containing our instructions or questions.

\* first answer
2. Text containing our instructions or questions.

(a) Question.

\* second answer
3. Text containing our instructions or questions.

\* third answer
4. Text containing our instructions or questions.

\* fourth answer

6.3 The environment `anskey*`

`anskey*` `\begin{anskey*}[\langle key = val \rangle] \langle body content \rangle \end{anskey*}`

The environment `anskey*` takes a mandatory  $\{ \langle body content \rangle \}$  and “stores” it in the *sequence* and *prop list*  $\{ \langle store name \rangle \}$  set by `save-ans` key. If `save-ref` key are active and the `hyperref`[8] package is detected, `\hyperLink` and `\hypertarget` will be used, otherwise the usual “*label and ref*” system provided by  $\LaTeX$  will be used.

By design the environment cannot be nested but full supports “*verbatim material*” in the body and it is assumed that each numbered `\item` or `\item*` within the environment in which it is active it has a “*single execution*” unless `\item` or `\item*` open a nested level or use the `no-store` key.

The `anskey*` environment is implemented using the `scontents` package, for the correct operation `\begin{anskey*}` and `\end{anskey*}` must be in different lines, all *keys* must be passed separated by commas and “without separation” of the start of the environment. Comments “%” or “any character” after `\begin{anskey*}` or `[\langle key = val \rangle]` on the same line are NOT supported, the package `scontents` will return an “error” message if this happens. In a similar way comments “%” or “any character” after `\end{anskey*}` on the same line the package `scontents` will return a “warning” message.

6.3.1 Keys for `anskey*`

The `anskey*` environment uses the same *keys* as the `\anskey` command next to the keys inherited from package `scontents`. The environment is available for all levels of the `enumext` environment and the `enumext*` environment, but it is disabled for the `keyans`, `keyans*` and `keyanspic` environments.

- `write-env` =  $\{ \langle file.ext \rangle \}$  default: *not used*
- Sets the name of the  $\langle external file \rangle$  in which the  $\langle contents \rangle$  of the environment will be written. The  $\langle file.ext \rangle$  will be created in the working directory, relative or absolute paths are not supported. If  $\langle file.ext \rangle$  does not exist, it will be created or overwritten if the `overwrite` key is used.



`overwrite` = { $\langle true | false \rangle$ } default: *false*  
 Sets whether the  $\langle file.ext \rangle$  generated by `write-env` from the `anskey*` environment will be rewritten.

`force-eol` = { $\langle true | false \rangle$ } default: *false*  
 Sets if the *end of line* for the  $\langle stored content \rangle$  is hidden or not. This key is necessary only if the last line is the closing of some environment defined by the `fancyvrb` package as `\end{Verbatim}` or another environment that does not support a comments “%” after closing `\end{Verbatim}`%.  
 For security reasons the keys `store-env`, `print-env` and `write-out` they have been left disabled. It is recommended that you review the `scontents`[4] documentation to understand how the keys described here work.

### Example

```
\begin{enumext}[save-ans=test,show-pos=true,start=5]
  \item* Text containing our instructions or questions.
  \begin{anskey*}[item-star]
    \first answer
  \end{anskey*}
  \item Text containing our instructions or questions.
  \begin{enumext}
    \item Question.
    \begin{anskey*}
      \second answer
    \end{anskey*}
  \end{enumext}
  \item Text containing our instructions or questions.
  \begin{anskey*}
    \third answer
  \end{anskey*}
  \item Text containing our instructions or questions.
  \begin{anskey*}
    \fourth answer
  \end{anskey*}
\end{enumext}
```

- |  |   |
|--|---|
| * 5. Text containing our instructions or questions.<br>[5] First answer with verbatim<br>6. Text containing our instructions or questions.<br>(a) Question.<br>[6] second answer | 7. Text containing our instructions or questions.<br>[7] third answer<br>8. Text containing our instructions or questions.<br>[8] fourth answer |
|--|---|

## 6.4 The environments `keyans` and `keyans*`

<code>keyans</code>	<code>\begin{keyans}[<math>\langle key = val \rangle</math>] \item \item[<math>\langle custom \rangle</math>] \item* \item*[<math>\langle content \rangle</math>] \end{keyans}</code>
<code>keyans*</code>	<code>\begin{keyans*}[<math>\langle key = val \rangle</math>] \item \item[<math>\langle custom \rangle</math>] \item* \item*[<math>\langle content \rangle</math>] \end{keyans*}</code>

The `keyans` and `keyans*` environments are “*enumerated list*” environments designed for “*multiple choice*” questions activated by the `save-ans` key. This environments can NOT be nested and must always be at the “*first level*” of the `enumext` environment, the commands `\item` and `\item[ $\langle custom \rangle$ ]` work in the usual and the command `\item[ $\langle columns \rangle$ ]` is available for the `keyans*` environment.

<pre>\begin{enumext}[save-ans=test]   \item \item content   \begin{keyans}[<math>\langle key = val \rangle</math>]     \item \item content     \item [<math>\langle custom \rangle</math>] \item content     \item* \item content     \item* [<math>\langle content \rangle</math>] \item content   \end{keyans} \end{enumext}</pre>	<pre>\begin{enumext}[save-ans=test]   \item \item content   \begin{keyans*}[<math>\langle key = val \rangle</math>]     \item \item content     \item [<math>\langle custom \rangle</math>] \item content     \item* \item content     \item* [<math>\langle content \rangle</math>] \item content   \end{keyans*} \end{enumext}</pre>
--	--

The  $\langle keys \rangle$  set in the *optional argument* of the environment are the same (almost) as those of the `enumext` and `enumext*` environments and have *higher precedence* than those set by `\setenumext[ $\langle keyans \rangle$ ]{ $\langle key = val \rangle$ }` or `\setenumext[ $\langle keyans* \rangle$ ]{ $\langle key = val \rangle$ }`. If the *optional argument* is not passed or the  $\langle keys \rangle$  are not set by `\setenumext`, the default values will be the same as the “*second level*” of the `enumext` environment with the difference in the  $\langle label \rangle$  which will be set to `label=\Alph*`.

### 6.4.1 The `\item*` in `keyans` and `keyans*`

<code>\item*</code>	<code>\item*</code>
	<code>\item*[<math>\langle content \rangle</math>]</code>

The `\item*` and `\item*[ $\langle content \rangle$ ]` command “*store*” the current  $\langle label \rangle$  set by `label` key next to the *optional argument*  $\langle content \rangle$  in *sequence and prop list* { $\langle store name \rangle$ } set by `save-ans` key in the “*first level*” of the `enumext` or `enumext*` environments.

The *starred argument* ‘\*’ cannot be separated by spaces ‘ ’ from the command, i.e. `\item*` and the *optional argument* does “NOT” support *verbatim content*. By design it is assumed that the `\item*` will only appear “once” within the environment.

- The behavior of `\item*` in `keyans` and `keyans*` environments is NOT the same as in the `enumext` or `enumext*` environments.

Example

```
\begin{enumext}[save-ans=test,columns=2,show-ans=true]
  \item Text containing a question.
  \begin{keyans*}[nosep,columns=2]
    \item Choice
    \item* Correct choice
    \item Choice
    \item Choice
    \item Choice
  \end{keyans*}
  \item Text containing a question and image.
  \begin{keyans}[nosep,mini-env={0.4\linewidth}]
    \item Choice
    \item Choice
    \item Choice
    \item Choice
    \item*[\textit{note}] Correct choice
    \miniright
    \includegraphics[scale=0.25]{example-image-a}
    Some text
  \end{keyans}
\end{enumext}
```

1. Text containing a question.

A) Choice

\* B) Correct choice

C) Choice

D) Choice

E) Choice

2. Text containing a question and image.


A) Choice

B) Choice

C) Choice

D) Choice

\* E) [note] Correct choice



Some text

6.5 The environment keyanspic

keyanspic

```
\begin{keyanspic}*[\textit{n° upper, n° lower}]\anspic{\textit{drawing}}\anspic*[\textit{content}]{\textit{drawing or tabular}}
```

The `keyanspic` environment is an “*enumerated list*” environment activated by the `save-ans` key that has the same settings as the `keyans` environment that uses the `\anspic` command instead of `\item`. It is intended for placing drawings or tables with `\label` centered *above* or *below* in a *single line* or *upper and lower* layout. A representation of the output can be seen in the figure 6.




Figure 6: Representation of the `keyanspic` environment with optional argument [3,2] in `enumext`.

When the `keyanspic` environment is used *without arguments* the `\label` are centered *below* the drawings or tabular in a *single line* layout. The *starred argument* ‘\*’ places `\label` centered *above* the drawings or tabular. The *optional argument* determines the number drawings or tabular placed at *upper and lower* in the environment. If the *optional argument* or the `\textit{n° lower}` is omitted the drawings or tabular will be put on a *single line*. The vertical separation between “*upper*” and “*lower*” part is controlled by the values set by `parsep` key passed to `keyans` environment.

6.5.1 The command \anspic

\anspic

```
\anspic{\textit{drawing or tabular}}
\anspic*[\textit{content}]{\textit{drawing or tabular}}
```

The `\anspic` command take three arguments, the *starred argument* ‘\*’ store the current `\label` next to the *optional argument* `\textit{content}` in *sequence* and *prop list* `{\textit{store name}}` set by `save-ans` key.

The *starred argument* ‘\*’ cannot be separated by spaces ‘ ’ from the command, i.e. `\anspic*` and the *optional argument* does “NOT” support *verbatim content*. By design it is assumed that the *starred argument* ‘\*’ will only appear “once” within the environment.

Example

```
\begin{enumext}[save-ans=test,show-ans,nosep]
  \item Question with images.

  \begin{keyanspic}[layout-sty={3,2}]
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-b}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic*[note]{\includegraphics[scale=0.15]{example-image-a}}
  \end{keyanspic}


  \item Question with images.

  \begin{keyanspic}[label-pos=above, layout-sty={3,2}]
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-b}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic*[note]{\includegraphics[scale=0.15]{example-image-a}}
  \end{keyanspic}


  \item Question with images.

  \begin{keyanspic}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-b}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic*[note]{\includegraphics[scale=0.15]{example-image-a}}
  \end{keyanspic}
\end{enumext}
```


1. Question with images.




A)




B)



C)




D)




\* E)[note]


2. Question with images.




A)




B)



C)




D)




\* E)[note]


3. Question with images.




A)




B)



C)



D)



\* E)[note]

## 6.6 Printing stored content

### 6.6.1 The command \getkeyans

---

`\getkeyans`

`\getkeyans{<store name> : <position>}`

The command `\getkeyans` prints the “stored content” in *prop list* `{<store name>}` defined by `save-ans` key in the `<position>` returned by the `show-pos` key. The “stored content” can only be accessed *after* it is stored, if `{<store name>}` does not exist the command will return an error.

The form taken by the argument `{<store name> : <position>}` is the same as that used to generate the “internal label and ref” system when `save-ref` key are active, so to refer to a “stored content”. For example `\getkeyans{test:4}` will return the “stored content” at position 4 of the environment in which the key `save-ans=test` was set.

### 6.6.2 The command \foreachkeyans

---

`\foreachkeyans`

`\foreachkeyans[<key = val>]{<store name>}`

The command `\foreachkeyans` goes through and executes the command `\getkeyans` on the contents in *prop list* `{<store name>}`. If you pass without options run `\getkeyans` on all contents in *prop list* `{<store name>}`.

#### Options for command

`sep = {<code>}`

default: `{;}`

Establishes the *separation* between “each” `{<content>}` stored in *prop list* `{<store name>}`. For example, you can use `sep={\[\ 10pt]}` for vertical separation of stored contents.

`step = {<integer>}`

default: `1`

Sets the *step* (increment) applied to the value set by key `start` for each `{<content>}` stored in *prop list* `{<store name>}`. The value must be a *positive integer*.

`start = {<integer>}`

default: `1`

Sets the *position* of the *prop list* `{<store name>}` from which execution will start. The value must be a *positive integer*.

`stop = {<integer>}`

default: `0`

Sets the *position* of the *prop list* `{<store name>}` from which execution it will finish executing. The value must be a *positive integer*.

`before = {<code>}`

default: *empty*

Sets the `{<code>}` that will be executed *before* each `{<content>}` stored in *prop list* `{<store name>}`. The `{<code>}` must be passed between braces.

`after = {<code>}`

default: *empty*

Sets the `{<code>}` that will be executed *after* each `{<content>}` stored in *prop list* `{<store name>}`. The `{<code>}` must be passed between braces.

`wrapper = {<code> {#1} more code}`

default: *empty*

Wraps the `{<content>}` stored in *prop list* `{<store name>}` referenced by `{#1}`. The `{<code>}` must be passed between braces. For example `\foreachkeyans[wrapper={\makebox[1em][l]{#1}}]{<store name>}`.

### 6.6.3 The command \printkeyans

---

`\printkeyans`

`\printkeyans{<store name>}`  
`\printkeyans[<keys>]{<store name>}`  
`\printkeyans*[<keys>]{<store name>}`

The command `\printkeyans` prints “all stored content” in *sequence* `{<store name>}` defined by `save-ans` key placing this inside the `enumext` environment by default or the `enumext*` environment if the *starred argument* `‘*’` is used.

The “stored content” can only be accessed *after* it is stored in the *sequence*, if `{<store name>}` does not exist the command will return an error.

The *optional argument* allows managing the `<keys>` in the “first level” of the environment in which the “stored content” of the *sequence* `{<store name>}` will be printed, if the *starred argument* `‘*’` is used it will be `enumext*` otherwise `enumext`.

The default values for the “first level” are the same as the default values for the `enumext` and `enumext*` environments along with the keys `nosep`, `first=\small`, `font=\small` and `columns=2`. For the inner levels of the environment `enumext` saved in the *sequence* `{<store name>}` the default values are the same as those established for the second, third and fourth levels plus the keys `nosep`, `first=\small`, `font=\small`. If the environment `enumext*` is saved within the *sequence* `{<store name>}` it will have the same default values plus the keys `nosep`, `first=\small`, `font=\small`.

Since the command encapsulates by default the `enumext` environment or the `enumext*` environment, we must take some considerations:

- If we execute `\printkeyans*{<store name>}` and the *sequence* `{<store name>}` already contains any `enumext*` environment an error will be returned as we cannot nest.

- If we execute `\printkeyans*{⟨store name⟩}` and the *sequence*  $\{⟨store name⟩\}$  contains any `enumext` environments, they will start with the  $\langle keys \rangle$  set for the first level unless they are set in the *optional argument* or `save-key` is used to modify it.
- If we execute `\printkeyans{⟨store name⟩}` and the *sequence*  $\{⟨store name⟩\}$  contains any environment `enumext*`, they will start with the  $\langle keys \rangle$  set by default unless they are set in the *optional argument* or `save-key` is used to modify it.

The default values for the “first level” of `\printkeyans` commands and `\printkeyans*` are established using `\setenumext[⟨print , 1⟩]{⟨keys⟩}` and `\setenumext[⟨print*⟩]{⟨keys⟩}`.

If we need to set the  $\langle keys \rangle$  for the environment `enumext` “saved” in the *sequence*  $\{⟨store name⟩\}$  we will use `\setenumext[⟨print , level⟩]{⟨keys⟩}` and if we need to set the  $\langle keys \rangle$  for the environment `enumext*` “saved” in the *sequence*  $\{⟨store name⟩\}$  we will use `\setenumext[⟨print , *⟩]{⟨keys⟩}`.

Example

```
\begin{enumext}[save-ans=sample,columns=1,show-pos=true,nosep,save-ref=true]
  \item Factor  $3x+3y+3z$ . \anskey{ $3(x+y+z)$ }
  \item True False

  \begin{enumext}[nosep]
    \item \LaTeXe\ is cool? \anskey{Very True!}
  \end{enumext}

  \item Related to Linux

  \begin{enumext}[nosep]
    \item You use linux? \anskey{Yes}
    \item Rate the following package and class
      \begin{enumext}[nosep]
        \item \texttt{xsim} \anskey{very good}
        \item \texttt{exsheets} \anskey{obsolete}
      \end{enumext}
    \end{enumext}
  \end{enumext}
```

The answer to `\ref{sample:4}` is `\getkeyans{sample:4}` and the answers to all the worksheets are as follows:

```
\printkeyans{sample}
```

1. Factor  $3x + 3y + 3z$ .

[1]

2. True False

(a) ~~LaTeXe~~ is cool?

[2]

3. Related to Linux

(a) You use linux?

[3]

(b) Rate the following package and class

i. `xsim`

[4]

ii. `exsheets`

[5]

The answer to 3.(b).i is very good and the answers to all the worksheets are as follows:

1.  $3(x + y + z)$  ✖
2. (a) Very True! ✖
3. (a) Yes ✖
- (b) i. very good ✖
- ii. obsolete ✖

7 Full examples

Here I will leave as an example some adaptations questions taken from `TeX-SX`. The examples are attached to this documentation and can be extracted from your PDF viewer or from the command line by running:

```
$ pdftdetach -saveall enumext.pdf
```

and then you can use the excellent `arara`<sup>1</sup> tool to compile them.


<sup>1</sup>The cool `TeX` automation tool: <https://www.ctan.org/pkg/arara>

©2024 by Pablo González L

18 / 156



Example 1

Adapted from the response given by Enrico Gregorio in [Squares for answer choice options and perfect alignment to mathematical answers](#) .

1. La velocità di  $1,00 \times 10^2$  m/s espressa in km/h è:

A

 36 km/h.

B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$  km/h.
2. In fisica nucleare si usa l'angstrom (simbolo:  $1 \text{ \AA} = 1 \times 10^{-10}$  m) e il fermi o femtometro ( $1 \text{ fm} = 1 \times 10^{-15}$  m). Qual è la relazione tra queste due unità di misura?

A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$ .

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$ .

C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$ .

D

 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$ .
3. La velocità di  $1,00 \times 10^2$  m/s espressa in km/h è:

A

 36 km/h.

B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$  km/h.
4. In fisica nucleare si usa l'angstrom (simbolo:  $1 \text{ \AA} = 1 \times 10^{-10}$  m) e il fermi o femtometro ( $1 \text{ fm} = 1 \times 10^{-15}$  m). Qual è la relazione tra queste due unità di misura?

A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$ .

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$ .

C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$ .

D


 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$ .
1. B

2. A

3. B

4. A

Example 2

Adapted from the response given by Florent Rougon in [Multiple choice questions with proposed answers in random order — addition of automatic correction \(cross mark\)](#) .

1. La velocità di  $1,00 \times 10^2$  m/s espressa in km/h è:

A

 36 km/h.

☒ B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$  km/h.
2. In fisica nucleare si usa l'angstrom (simbolo:  $1 \text{ \AA} = 1 \times 10^{-10}$  m) e il fermi o femtometro ( $1 \text{ fm} = 1 \times 10^{-15}$  m). Qual è la relazione tra queste due unità di misura?

☒ A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$ .

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$ .

C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$ .

D

 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$ .
3. La velocità di  $1,00 \times 10^2$  m/s espressa in km/h è:

A

 36 km/h.

☒ B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$  km/h.
4. In fisica nucleare si usa l'angstrom (simbolo:  $1 \text{ \AA} = 1 \times 10^{-10}$  m) e il fermi o femtometro ( $1 \text{ fm} = 1 \times 10^{-15}$  m). Qual è la relazione tra queste due unità di misura?

☒ A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$ .

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$ .

C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$ .

D


 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$ .
1. B

☒ 2. A

3. B

☒ 4. A

Example 3

A “simple multiple choice” test .

1. First type of questions

A) value

C) value

B) correct

D) value
2. Second type of questions

I.  $2\alpha + 2\delta = 90^\circ$

II.  $\alpha = \delta$

III.  $\angle EDF = 45^\circ$

☒ A

 I only

☒ B

 II only

☒ C

 I and II only

☒ D

 I and III only

☒ E

 I, II, and III
3. Third type of questions

(1)  $2\alpha + 2\delta = 90^\circ$

(2)  $\angle EDF = 45^\circ$

☒ A

 value

☒ B

 value

☒ C






 value

☒ D

 value

☒ E

 value
4. Question with image and label below:



5. Question with image on left side:

- (A) value
- (B) value
- (C) value
- (D) correct
- (E) value



Test keys

1. B),  $x = 5$

2. D

3. C, some note
- ✖ 4. E, A duck

✖ 5. D, other note

✖
- ✖

✖

✖

Example 4

A “simple worksheet” using ducks :)

Factor  $x^2 - 2x + 1$

Factor  $3x + 3y + 3z$

The following questions need to be cuaqtified :)

True False

- (a)  $\alpha > \delta$
- (b) ~~ET~~Xze is cool?

Related to Linux

- (a) You use linux?
- (b) Usually uses the package manager?
- (c) Rate the following package and class
  - i. `xsim-exam`
  - ii. `xsim`
  - iii. `exsheets`

The answer to 1 is  $(x - 1)^2$  and the answer to 3.(a) is False.

1.  $(x - 1)^2$

2.  $3(x + y + z)$

3. (a) False

(b) Very True!

4. (a) Yes
- ✖ (b) Yes, dnf

✖ (c) i. doesn't exist for now :(

✖ ii. very good

✖ iii. obsolete

✖
- ✖

✖

✖

✖

Example 5











Adapted from the response given by Stephen in SAT like question format .

<div>1</div> <div>Which choice best describes what happens in the passage?</div> <div>A) One character argues with another character who intrudes on her home.</div> <div>B) One character receives a surprising request from another character.</div> <div>C) One character reminisces about choices she has made over the years.</div> <div>D) One character criticizes another character for pursuing an unexpected course of action.</div>	<div>3</div> <div>Which choice best describes what happens in the passage?</div> <div>A) One character argues with another character who intrudes on her home.</div> <div>B) One character receives a surprising request from another character.</div> <div>C) One character reminisces about choices she has made over the years.</div> <div>D) One character criticizes another character for pursuing an unexpected course of action.</div>
<div>2</div> <div>Which choice best describes what happens in the passage?</div> <div>A) One character argues with another character who intrudes on her home.</div> <div>B) One character receives a surprising request from another character.</div> <div>C) One character reminisces about choices she has made over the years.</div> <div>D) One character criticizes another character for pursuing an unexpected course of action.</div>	<div>4</div> <div>Which choice best describes what happens in the passage?</div> <div>A) One character argues with another character who intrudes on her home.</div> <div>B) One character receives a surprising request from another character.</div> <div>C) One character reminisces about choices she has made over the years.</div> <div>D) One character criticizes another character for pursuing an unexpected course of action.</div>
1. A)	3. B)
2. C)	4. D)

## 8 Tagged PDF examples

This section is just to show the compatibility of `enumext` with *tagged* PDF using `lualatex`. The attached files here are just for testing and are intended as examples and, in a way, to simplify the time of Matthew Bertucci (@mbertucci) when he sees this excellent package and adds it to [The LaTeX Tagged PDF repository](#).

To compile the tests with `lualatex-dev` the packages `multicol`, `scontents`, `unicode-math`, `geometry`, `graphicx` and `hyperref` are required.

- The file `enumext-01.tex` contains the basic tests for the `enumext` and `enumet*` environments and the nesting between them plus the use of the `label`, `labelwidth`, `labelsep`, `ref`, `align` and `wrap-label` keys. Source file  and *tagged* PDF .
- The file `enumext-01.tex` contains the tests for the `enumext` and `enumet*` environments and the support for `minipage` and `multicols` environments using the keys `columns`, `columns-sep`, `mini-env`, `mini-right` and `\miniright` command. Source file  and *tagged* PDF .
- The file `enumext-03.tex` contains the tests for the `enumext` and `keyanspic` environments activated by the `save-ans` key together with the `save-sep` and `save-ref` keys and the `\printkeyans` command. Source file  and *tagged* PDF .
- The file `enumext-04.tex` contains the tests for the `\anskey` command and the `anskey*` environment activated by the `save-ans` key along with the `\getkeyans` and `\printkeyans` commands. Source file  and *tagged* PDF .
- The file `enumext-05.tex` contains the tests for the environments `keyans`, `keyans*` and `keyanspic` activated by the key `save-ans` together with the keys `no-store` and `show-ans` and the commands `\setenumext`, `\setenumextmeta`, `\printkeyans` and `\foreachkeyans`. Source file  and *tagged* PDF .

## 9 The way of non-enumerated lists

It is possible to use (or abuse) the `enumext` environment to mimic *non-enumerated* list environments such as `itemize` and `description`, clearly the `(keys)` to “store answers”, the `keyans` and `keyanspic` environments lose their sense and it is not the focus of the main of this package, but, why not to do it?

Here I leave as an example other uses of the `enumext` environment that can be helpful for specific purposes. The “trick” to generate these *fake environments* is set `label={}` or `label={\some}` and play with the `list-indent`, `list-offset`, `font` and `wrap-label` keys.

### Fake itemize environment

Here we set the `label` key using the default settings in  $\TeX$  for the four levels `\textbullet`, `\textendash`, `\textasteriskcentered` and `\textperiodcentered` together with the `nosep` key to reduce the vertical spaces in the left side example and set the `label` key in *mathematical mode* for the right side as `\ast`, `\diamond`, `\circ` and `\star` for the four levels together with the `nosep` key

- |                     |                     |
|---------------------|---------------------|
| • First level item  | * First level item  |
| – Second level item | ◇ Second level item |
| • Third level item  | ◦ Third level item  |
| · Fourth level item | ★ Fourth level item |
| • First level item  | * First level item  |

### Fake description environment

Here we set `label={}` and `list-indent=2.5em`, `font=\bfseries`.

**Something** A short one-line description.

This is an entry *without* a label.

**Something** A short *one-line* description text.

**Something long** A much *longer* description text may take more than one line or more than one paragraph.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

If we add `list-indent=0pt` you get *widest style*:

**Something** A short one-line description.

This is an entry *without* a label.

**Something** A short *one-line* description text.

**Something long** A much *longer* description text may take more than one line or more than one paragraph.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

- The small space at the beginning of the “unlabeled entry” corresponds to `\labelsep` and can be removed using `\hspace{-\labelsep}` at the beginning of the line.

Description indented by label

Here we set `label={}` and we will give a convenient value to `labelsep` and `labelwidth`, for example we can take as reference our *longest label* and pass it as value using:

```
\newlength{\descitemwd}
\settowidth{\descitemwd}{\textbf{Something long}}
```

and then use `labelsep=4pt, labelwidth=\descitemwd, font=\bfseries`.

- Something** A short one-line description.  
This is an entry *without* a label.
- Something** A short one-line description.
- Something long** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

The environment can be translated so that the `<labels>` are on the left margin calculating the value passed to the `list-offset` key, in this case it will be equal to the sum of the values set by the `labelwidth` and `labelsep` keys finally resulting as `list-offset={-\descitemwd - 4pt}`.

- Something** A short one-line description.  
This is an entry *without* a label.
  - Something** A short one-line description.
  - Something long** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.
- If we add `align=right` it will look like this:

- Something** A short one-line description.  
This is an entry *without* a label.
- Something** A short one-line description.
- Something long** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

At this point we have used `list-offset={-\descitemwd - 4pt}` instead of `list-offset={-\labelwidth - \labelsep}`, this is because the parameters `\labelwidth` and `\labelsep` take the default values, as if we had not set `label`.

Description with multi-line labels

The `label` key does not accept *multiline material*, this is where the `wrap-label` and `wrap-label*` keys comes into play. Unlike the `enumitem` package, the `align` key only supports three options, so what we will do is create a command in the style `\parleft` of `enumitem` that allows us to place *multiline labels* using `\parbox`.

```
\NewDocumentCommand \labelbx { s +m }
{%
  \IfBooleanTF{#1}
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedright{#2}}}}%
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{#2}}}}%
}
```

Now we just need to set `wrap-label*={\labelbx{#1}}`.

- Something** A short one-line description.  
This is an entry *without* a label.
- Something** A short one-line description.
- Something long** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.  
Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.
- SoMeThInG LoNg** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

Final notes

The original implementation (if you can call it that) of the ideas that led to the creation of `enumext` were some macros using the `enumerate[5]` package for personal use created in early 2003, the code was quite questionable, but functional for these simple requirements.

With the great answers given by Christian Hupfer in [Create a fake label ref using list](#) and the answer given by David Carlisle in [Change the use of label ref by data save in an array \(list\)](#) I managed to create a more solid code than the original version, now using the `l3prop[11]` and `l3seq[11]` modules together with the `hyperref[8]` and `enumitem[6]` packages, which did the job, but with some limitations.

As time went by I took these limitations as a personal challenge which I called “*reinventing the wheel*”, since there were packages and classes that did more or less what I was looking for, but did not fit my simple requirements. This “*reinventing the wheel*” finally ended up becoming `enumext`.

### Why list environments?

The answer is simple, first I love the beauty of its syntax and many of what I had already written used the `enumerate` environment or lists created using the `enumitem` package. In my mind I thought: how complicated could it be to write a package that looked like `enumitem`? It seemed simple enough, of course I didn't have in mind the mess I was getting into working with `list` environments, `minipage` and adding support for the `multicol` and `hyperref` packages.

Of course, seeing the final result of the experiment “*reinventing the wheel*” I am quite satisfied.

### Why not random questions and other utilities

The “*random*” type questions I love and hate them at the same time, although they simplify a lot the work when creating a multiple choice test, but you lose the beauty of typesetting a document with  $\text{\LaTeX}$ , that is to say the output does not always look as nice as it should, even if they are only alternatives these must follow a certain order when presented either numerical or presentation, that said handling that using *nested lists* is quite complicated so I do not classify to be implemented.

### Why has it taken so long?

One of the setbacks, beyond my laziness, was including compatibility with *tagged* PDF. To be honest, it's something I never considered at any point, but I firmly believe that being able to create *accessible documents* provides a great opportunity in the world of mathematics education. From my perspective as a *high school* teacher, beyond theorems and deep mathematics, the use of exercise lists is one of the most common things. Being able to open the way to work in parallel with those who have different abilities is really important and I regret not having looked into this in the past. I hope that `enumext` serves this purpose and inspires more users and authors to follow this path.

## 10 References

- [1] HIRSCHHORN, PHILIP. “Using the exam document class”. Available from CTAN, <https://www.ctan.org/pkg/exam>, 2023.
- [2] NIEDERBERGER, CLEMENS. “xsim – eXercise Sheets IMproved”. Available from CTAN, <https://www.ctan.org/pkg/xsim>, 2023.
- [3] MITTELBACH, FRANK. “An environment for multicolumn output”. Available from CTAN, <https://www.ctan.org/pkg/multicol>, 2024.
- [4] GONZÁLEZ, PABLO. “scontents - Stores  $\text{\LaTeX}$  contents in memory or files”. Available from CTAN, <https://www.ctan.org/pkg/scontents>, 2024.
- [5] The  $\text{\LaTeX}$  Project. “enumerate – Enumerate with redefinable labels”. Available from CTAN, <https://www.ctan.org/pkg/enumerate>, 2024.
- [6] BEZOS, JAVIER. “Customizing lists with the enumitem package”. Available from CTAN, <https://www.ctan.org/pkg/enumitem>, 2019.
- [7] BERRY, KARL. “ $\text{\LaTeX} 2_{\epsilon}$ : An Unofficial Reference Manual”. Available from CTAN, <https://ctan.org/pkg/latex2e-help-texinfo>, 2024.
- [8] The  $\text{\LaTeX}$  Project. “Extensive support for hypertext in  $\text{\LaTeX}$ ”. Available from CTAN, <https://www.ctan.org/pkg/hyperref>, 2024.
- [9] BURNOL, JEAN-FRANÇOIS. “The footnotehyper package”. Available from CTAN, <https://www.ctan.org/pkg/footnotehyper>, 2021.
- [10] The  $\text{\LaTeX}$  Project. “The expl3 package”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2024.
- [11] The  $\text{\LaTeX}$  Project. “The  $\text{\LaTeX} 3$  Interfaces”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2024.
- [12] The  $\text{\LaTeX}$  Project. “The  $\text{\LaTeX} 2_{\epsilon}$  sources”. Available from CTAN, <https://ctan.org/tex-archive/macros/latex/base>, 2024.
- [13] The  $\text{\LaTeX}$  Project. “ $\text{\LaTeX}$  for authors current version”. Available from CTAN, <https://ctan.org/pkg/latex-base>, 2024.
- [14] GUNDLACH, PATRICK. “The lua-visual-debug package”. Available from CTAN, <https://www.ctan.org/pkg/lua-visual-debug>, 2023.
- [15] LEMVIG, MOGENS. “The shortlst package”. Available from CTAN, <https://www.ctan.org/pkg/shortlst>, 1998.
- [16] NIEDERBERGER, CLEMENS. “tasks – Horizontally columned lists”. Available from CTAN, <https://www.ctan.org/pkg/tasks>, 2022.



# 11 Change history

**v1.0 2024-10-04** – First public release.

12 Index of Documentation

The italic numbers denote the pages where the corresponding entry is described.

<b>C</b>		<b>F</b>	
Document class:		\footnote	5
article	2	<b>I</b>	
book	2	\itemsep	8
exam	2	<b>K</b>	
letter	2	Keys for \anskey provide by enumext:	
report	2	break-col	13
\columnbreak	4, 13	item-join	13
\columnsep	10	item-pos*	13
Commands provide by enumext:		item-star	13
\anskey	11–13	item-sym*	13
\anspic	11, 12, 15, 16	Keys for \foreachkeyans provide by enumext:	
\foreachkeyans	17	after	17
\getkeyans	12, 17	before	17
\item*	5–7, 11, 12, 14, 15	sep	17
\item	5–7, 9, 10, 12, 14	start	17
\miniright	10, 11	step	17
\printkeyans	6, 12, 17	stop	17
\setenumextmeta	6	wrapper	17
\setenumext	5–7, 11, 12, 14, 18	Keys for anskey* provide by enumext:	
Counters defined by enumext:		break-col	13
enumXiii	4	force-eol	14
enumXii	4	item-join	13
enumXiv	4	item-pos*	13
enumXi	4	item-star	13
enumXviii	4	item-sym*	13
enumXvii	4	overwrite	14
enumXvi	4	write-env	13
enumXv	4	Keys for environments provide by enumext:	
<b>E</b>		above*	9
Environments provide by enumext:		above	8
anskey*	11–14, 21	after	9–11
enumet*	21	align	7, 21, 22
enumext*	4–15, 17, 18	base-fix	8
enumext	4–15, 17, 18, 21	before*	9
keyans*	4–9, 11–15, 21	before	9
keyanspic	4, 7, 8, 11–13, 15, 21	below*	9
keyans	4–9, 11–15, 21	below	9
Environments:		check-ans	12
Verbatim	14	columns-sep	4, 10, 21
center	5	columns	4, 8, 10, 21
description	5, 21	first	9
enumerate	1, 3, 5, 23	font	7
figure	5	item-pos*	5, 6
flushleft	5	item-sym*	5, 6
flushright	5	itemindent	9
itemize	5, 21	itemsep	8
keyans	21	labelsep	3–7, 9, 10, 12, 21, 22
list	3, 5, 9, 23	labelwidth	3, 4, 6, 7, 9, 10, 12, 21, 22
minipage	3–5, 8–11, 21, 23	labelwith	5
multicols	3, 4, 10, 21	label	7, 8, 10, 14, 21, 22
quotation	5	list-indent	3, 9
quote	5	list-offset	3, 9, 22
tabbing	5	listparindent	9
table	5	mark-ans	12
task	5	mark-pos	12
trivlist	5	mark-ref	12
verbatim	5	mini-env	4, 8, 10, 11, 21
verse	5	mini-right*	7, 11

mini-right	7, 11, 21	\alph*	7
mini-sep	4, 10, 11	\arabic*	7
no-store	11–13, 21	\roman*	7
noitemsep	8	\labelsep	3, 7
nosep	8, 21	\labelwidth	3, 7
overwrite	13	\linewidth	10
parsep	8, 15	\listparindent	9
partopsep	8		
ref	4, 7, 8, 21	<b>P</b>	
resume*	7, 10, 11	Packages:	
resume	7, 10, 11	enumerate	22
rightmargin	9	enumext	1–5, 7, 15, 21–23
save-ans	4, 6, 10–15, 17, 21	enumitem	3–5, 9, 22, 23
save-key	10, 11, 18	fancyvrb	14
save-ref	4, 7, 12, 13, 17, 21	footnotehyper	5
save-sep	11, 21	geometry	21
series	7, 10, 11	graphicx	21
show-ans	11, 12, 21	hyperref	4, 5, 12, 13, 21–23
show-length	8	l3keys	7
show-pos	11, 12, 17	l3prop	1, 22
start*	10	l3seq	1, 22
start	10	multicol	1, 2, 4, 21, 23
topsep	8, 9	scontents	1, 2, 13, 14, 21
widest	7	task	5, 6
wrap-ans	12	unicode-math	21
wrap-label*	7, 22	xsim	2
wrap-label	7, 21, 22	\parsep	8
wrap-opt	12	\partopsep	8
write-env	14		
		<b>R</b>	
<b>L</b>		\raggedcolumns	4
\label	4	\ref	4
Labels provide by enumext:		\rightmargin	9
\Alph*	7, 14		
\Roman*	7	<b>T</b>	
		\topsep	8

## 13 Implementation

The most recent publicly released version of `enumext` is available at CTAN: <https://www.ctan.org/pkg/enumext>. While general feedback via email is welcomed, specific bugs or feature requests should be reported through the issue tracker: <https://github.com/pablgonz/enumext/issues>.

- The documentation presented here is far from professional, it contains a lot of obvious information that to the eye of a TeXpert are superfluous, but, after so many years developing this project is the only way to remember what does what.

### 13.1 General conventions

Variables containing `i`, `ii`, `iii` and `iv` are associated by level with the `enumext` environment, variables containing `v` are associated with the `keyans` environment, variables containing `vi` are associated with the `keyanspic` environment, variables containing `vii` are associated with the `enumext*` environment and variables containing `viii` are associated with the `keyans*` environment.

To simplify writing and documentation some variables and functions that are common to the different levels of the environments are described using a capital “X”.

The temporary function `\__enumext_tmp:n` is used in different parts of the package code for variable creation or execution of other functions that are grouped into this one.

All variables and functions defined in this package are private and are NOT intended to work or be used by another package or module.

### 13.2 Initial set up

Start the DocStrip guards.

```
1 <{*package>
```

Identify the internal prefix (L<sup>A</sup>T<sub>E</sub>X3 DocStrip convention) for l3doc class.

```
2 <@@=enumext>
```

### 13.3 Declaration of the package

First we will make sure we have a minimum (super updated) version of L<sup>A</sup>T<sub>E</sub>X to work correctly.

```
3 \NeedsTeXFormat{LaTeX2e}[2024-06-01]
```

Now declare the `enumext` package.

```
4 \ProvidesExplPackage
5   {enumext}
6   {2024-10-04}
7   {1.0}
8   {Enumerate exercise sheets}
```

Finally check if the `multicol` and `scontents` packages are loaded, if not we load it.

```
9 \hook_gput_code:nnn {begindocument} {enumext}
10 {
11   \IfPackageLoadedTF { multicol }
12   {
13     \msg_info:nnn { enumext } { package-load } { multicol }
14   }
15   {
16     \msg_info:nnn { enumext } { package-not-load } { multicol }
17     \RequirePackage{multicol}[2024-05-23]
18   }
19   \IfPackageLoadedTF { scontents }
20   {
21     \msg_info:nnn { enumext } { package-load } { scontents }
22   }
23   {
24     \msg_info:nnn { enumext } { package-not-load } { scontents }
25     \RequirePackage{scontents}
26   }
27 }
```

### 13.4 Definition of variables

Variables that do not appear in this section are created by means of `\keys_define:nn` or some function described below.

```

\l__enumext_level_int
\l__enumext_level_h_int
\l__enumext_anskey_level_int
\l__enumext_keyans_level_int
\l__enumext_keyans_level_h_int
\l__enumext_keyans_pic_level_int

```

Integer variables will control the nesting levels of the environments and `\anskey` command.

```

28 \int_new:N \l__enumext_level_int
29 \int_new:N \l__enumext_level_h_int
30 \int_new:N \l__enumext_anskey_level_int
31 \int_new:N \l__enumext_keyans_level_int
32 \int_new:N \l__enumext_keyans_level_h_int
33 \int_new:N \l__enumext_keyans_pic_level_int

```

(End of definition for `\l__enumext_level_int` and others.)

```

\l__enumext_starred_bool
\g__enumext_starred_bool
\l__enumext_starred_first_bool
\l__enumext_standar_bool
\g__enumext_standar_bool
\l__enumext_standar_first_bool
\l__enumext_anskey_env_bool
\l__enumext_keyans_env_bool
\g__enumext_start_line_tl
\g__enumext_envir_name_tl
\l__enumext_envir_name_tl

```

Internal variables used by functions `\__enumext_is_not_nested:`, `\__enumext_is_on_first_level:` and `\__enumext_keyans_name_and_start:` (§13.5.1).

```

34 \bool_new:N \l__enumext_starred_bool
35 \bool_new:N \g__enumext_starred_bool
36 \bool_new:N \l__enumext_starred_first_bool
37 \bool_new:N \l__enumext_standar_bool
38 \bool_new:N \g__enumext_standar_bool
39 \bool_new:N \l__enumext_standar_first_bool
40 \bool_new:N \l__enumext_anskey_env_bool
41 \bool_new:N \l__enumext_keyans_env_bool
42 \tl_new:N \g__enumext_start_line_tl
43 \tl_new:N \g__enumext_envir_name_tl
44 \tl_new:N \l__enumext_envir_name_tl

```

(End of definition for `\l__enumext_starred_bool` and others.)

```

\l__enumext_counter_i_tl
\l__enumext_counter_ii_tl
\l__enumext_counter_iii_tl
\l__enumext_counter_iv_tl
\l__enumext_counter_v_tl
\l__enumext_counter_vi_tl
\l__enumext_counter_vii_tl
\l__enumext_counter_viii_tl

```

Variables to store the “*name of the counters*” `enumXi`, `enumXii`, `enumXiii` and `enumXiv` for `enumext` environment, `enumXv` for `keyans` environment and `enumXvi` for the `keyanspic` environment. The counters `enumXvii` and `enumXviii` are used by `enumext*` and `keyans*` environments.

The initial values of these variables are set by the function `\__enumext_define_counters:Nn` (§13.10) and then modified by the function `\__enumext_label_style:Nnn` used by `label` key (§13.13).

```

45 \cs_set_protected:Npn \__enumext_tmp:n #1
46 {
47   \tl_new:c { l__enumext_counter_#1_tl }
48 }
49 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_counter_i_tl` and others.)

```

\c__enumext_counter_style_tl
\l__enumext_ref_key_arg_tl
\l__enumext_ref_the_count_tl
\l__enumext_the_counter_X_tl
\l__enumext_renew_the_count_X_tl

```

Internal variables used by `ref` key (§13.13).

```

50 \tl_const:Nn \c__enumext_counter_style_tl
51 { { arabic } { roman } { Roman } { alph } { Alph } }
52 \tl_new:N \l__enumext_ref_key_arg_tl
53 \tl_new:N \l__enumext_ref_the_count_tl
54 \cs_set_protected:Npn \__enumext_tmp:n #1
55 {
56   \tl_new:c { l__enumext_renew_the_count_#1_tl }
57   \tl_new:c { l__enumext_the_counter_#1_tl }
58   \tl_set:ce { l__enumext_the_counter_#1_tl } { \exp_not:c { theenumX#1 } }
59 }
60 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\c__enumext_counter_style_tl` and others.)

```

\g__enumext_resume_int
\g__enumext_resume_vii_int
\l__enumext_resume_name_tl
\l__enumext_resume_active_bool
\g__enumext_starred_series_tl
\g__enumext_standar_series_tl

```

Internal variables used by `resume`, `resume*` and `series` keys (§13.24).

```

61 \int_new:N \g__enumext_resume_int
62 \int_new:N \g__enumext_resume_vii_int
63 \tl_new:N \l__enumext_resume_name_tl
64 \bool_new:N \l__enumext_resume_active_bool
65 \tl_new:N \g__enumext_standar_series_tl
66 \tl_new:N \g__enumext_starred_series_tl

```

(End of definition for `\g__enumext_resume_int` and others.)

```

\l__enumext_current_widest_dim
\g__enumext_counter_styles_tl
\g__enumext_widest_label_tl
\l__enumext_label_width_by_box

```

The variable `\l__enumext_current_widest_dim` stores the current label width, the variable `\g__enumext_counter_styles_tl` stores the default *⟨label style⟩* and the variable `\g__enumext_widest_label_tl` the label width. These variables are used by `widest` (§13.14) and `label` (§13.12) keys.

```

67 \dim_new:N \l__enumext_current_widest_dim
68 \tl_new:N \g__enumext_counter_styles_tl
69 \tl_new:N \g__enumext_widest_label_tl
70 \box_new:N \l__enumext_label_width_by_box

```



(End of definition for `\__enumext_current_widest_dim` and others.)

```
\__enumext_leftmargin_tmp_X_bool
\__enumext_leftmargin_tmp_X_dim
\__enumext_leftmargin_X_dim
\__enumext_itemindent_X_dim
```

The boolean variable `\__enumext_leftmargin_tmp_X_bool` and the dimensional variable `\__enumext_leftmargin_tmp_X_dim` are used by the `list-indent` key (§13.17). The variables `\__enumext_leftmargin_X_dim` and `\__enumext_itemindent_X_dim` are used and set by the function `\__enumext_calc_hspace:NNNNNNNNNN` (§13.37.1).

```
71 \cs_set_protected:Npn \__enumext_tmp:n #1
72 {
73   \bool_new:c { \__enumext_leftmargin_tmp_#1_bool }
74   \dim_new:c { \__enumext_leftmargin_tmp_#1_dim }
75   \dim_new:c { \__enumext_leftmargin_#1_dim }
76   \dim_new:c { \__enumext_itemindent_#1_dim }
77 }
78 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\__enumext_leftmargin_tmp_X_bool` and others.)

```
\__enumext_multicols_above_X_skip
\__enumext_multicols_below_X_skip
\g__enumext_multicols_right_X_skip
\__enumext_align_label_pos_X_str
```

Internal variables used by `columns` key (§13.21) and `align` key (§13.12).

```
79 \cs_set_protected:Npn \__enumext_tmp:n #1
80 {
81   \skip_new:c { \__enumext_multicols_above_#1_skip }
82   \skip_new:c { \__enumext_multicols_below_#1_skip }
83   \skip_new:c { \g__enumext_multicols_right_#1_skip }
84   \str_new:c { \__enumext_align_label_pos_#1_str }
85 }
86 \clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }
```

(End of definition for `\__enumext_multicols_above_X_skip` and others.)

```
\g__enumext_minipage_stat_int
\__enumext_minipage_temp_skip
\__enumext_minipage_left_skip
\__enumext_minipage_right_skip
\__enumext_minipage_after_skip
\g__enumext_minipage_right_skip
\g__enumext_minipage_after_skip
\__enumext_minipage_left_X_dim
\__enumext_minipage_active_X_bool
```

Internal variables used by `\miniright` command (§13.22.4) and the keys `mini-right`, `mini-right*`, `mini-env` and `mini-sep` (§13.20, §13.22).

```
87 \int_new:N \g__enumext_minipage_stat_int
88 \skip_new:N \__enumext_minipage_temp_skip
89 \skip_new:N \__enumext_minipage_left_skip
90 \skip_new:N \__enumext_minipage_right_skip
91 \skip_new:N \__enumext_minipage_after_skip
92 \skip_new:N \g__enumext_minipage_right_skip
93 \skip_new:N \g__enumext_minipage_after_skip
94 \cs_set_protected:Npn \__enumext_tmp:n #1
95 {
96   \dim_new:c { \__enumext_minipage_left_#1_dim }
97   \bool_new:c { \__enumext_minipage_active_#1_bool }
98 }
99 \clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\g__enumext_minipage_stat_int` and others.)

```
\__enumext_wrap_label_X_bool
\__enumext_wrap_label_opt_X_bool
\__enumext_start_X_int
\__enumext_fake_item_indent_X_tl
\__enumext_label_fill_left_X_tl
\__enumext_label_fill_right_X_tl
\__enumext_vspace_a_star_X_bool
\__enumext_vspace_b_star_X_bool
```

The bool vars `\__enumext_wrap_label_X_bool` and `\__enumext_wrap_label_opt_X_bool` are used by `wrap-label` and `wrap-label*` keys (§13.12), the integer `\__enumext_start_X_int` are used by the `start` and `start*` keys (§13.14), the token list `\__enumext_fake_item_indent_X_tl` is used by `itemindent` key (§13.17.1), the variables `\__enumext_label_fill_left_X_tl` and `\__enumext_label_fill_right_X_tl` are used by the `align` key (§13.12). The boolean vars `\__enumext_vspace_a_star_X_bool`, `\__enumext_vspace_b_star_X_bool` are used by `above`, `above*`, `below` and `below*` keys (§13.19).

```
100 \cs_set_protected:Npn \__enumext_tmp:n #1
101 {
102   \bool_new:c { \__enumext_wrap_label_#1_bool }
103   \bool_new:c { \__enumext_wrap_label_opt_#1_bool }
104   \int_new:c { \__enumext_start_#1_int }
105   \tl_new:c { \__enumext_fake_item_indent_#1_tl }
106   \tl_new:c { \__enumext_label_fill_left_#1_tl }
107   \tl_new:c { \__enumext_label_fill_right_#1_tl }
108   \bool_new:c { \__enumext_vspace_a_star_#1_bool }
109   \bool_new:c { \__enumext_vspace_b_star_#1_bool }
110 }
111 \clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\__enumext_wrap_label_X_bool` and others.)

```

\l__enumext_store_active_bool
\l__enumext_store_name_tl
\g__enumext_store_name_tl
\l__enumext_store_anskey_arg_tl
\l__enumext_store_anskey_env_tl
\l__enumext_store_anskey_opt_tl
\l__enumext_store_current_label_tl
\l__enumext_store_current_opt_arg_tl
\l__enumext_store_current_label_tmp_tl

```

The variable `\l__enumext_store_active_bool` setting by `save-ans` key (§13.25.1) activates all the mechanism related to `\anskey`, `anskey*`, `keyans`, `keyans*` and `keyanspic` environments.

The variable `\l__enumext_store_name_tl` saves the  $\{\langle store\ name\rangle\}$  set by the `save-ans` key of the *sequence* and *prop list* in which we will store, the variable `\g__enumext_store_name_tl` it's just a global copy of  $\{\langle store\ name\rangle\}$  used by different functions.

The variable `\l__enumext_store_anskey_arg_tl` save the *argument* of `\anskey` (§13.29) and the variables `\l__enumext_store_anskey_env_tl` and `\l__enumext_store_anskey_opt_tl` save the  $\langle body\rangle$  and the  $\langle keys\rangle$  of the environment `anskey*` (§13.30).

The variables `\l__enumext_store_current_label_tl` and `\l__enumext_store_current_opt_arg_tl` save the *current label* and *optional argument* of `\item*` (§13.36) and `\anspic*` (§13.41.2) for the `keyans`, `keyans*` and `keyanspic` environments.

The variable `\l__enumext_store_current_label_tmp_tl` is a temporary variable used by `keyans`, `keyans*` and `keyanspic` at various points.

```

112 \bool_new:N \l__enumext_store_active_bool
113 \tl_new:N \l__enumext_store_name_tl
114 \tl_new:N \g__enumext_store_name_tl
115 \tl_new:N \l__enumext_store_anskey_arg_tl
116 \tl_new:N \l__enumext_store_anskey_env_tl
117 \tl_new:N \l__enumext_store_anskey_opt_tl
118 \tl_new:N \l__enumext_store_current_label_tl
119 \tl_new:N \l__enumext_store_current_opt_arg_tl
120 \tl_new:N \l__enumext_store_current_label_tmp_tl

```

(End of definition for `\l__enumext_store_active_bool` and others.)

```

\l__enumext_setkey_tmpa_tl
\l__enumext_setkey_tmpb_tl
\l__enumext_setkey_tmpa_int
\l__enumext_setkey_tmpa_seq
\l__enumext_setkey_tmpb_seq

```

Internal variables used by the command `\setenumext` (§13.47).

```

121 \tl_new:N \l__enumext_setkey_tmpa_tl
122 \tl_new:N \l__enumext_setkey_tmpb_tl
123 \int_new:N \l__enumext_setkey_tmpa_int
124 \seq_new:N \l__enumext_setkey_tmpa_seq
125 \seq_new:N \l__enumext_setkey_tmpb_seq

```

(End of definition for `\l__enumext_setkey_tmpa_tl` and others.)

```

\l__enumext_meta_path_tl
\l__enumext_foreach_print_seq
\l__enumext_foreach_name_prop_tl
\g__enumext_foreach_default_keys_tl

```

Internal variables used by the `\printkeyans` command (§13.46) and `\foreachkeyans` command (§13.49).

```

126 \tl_new:N \l__enumext_meta_path_tl
127 \seq_new:N \l__enumext_foreach_print_seq
128 \tl_new:N \l__enumext_foreach_name_prop_tl
129 \tl_new:N \g__enumext_foreach_default_keys_tl

```

(End of definition for `\l__enumext_meta_path_tl` and others.)

```

\l__enumext_print_keyans_starred_tl
\l__enumext_print_keyans_star_bool
\l__enumext_mark_position_str
\g__enumext_item_symbol_aux_tl
\l__enumext_print_keyans_X_tl
\l__enumext_store_save_key_X_tl
\l__enumext_store_save_key_X_bool
\l__enumext_store_upper_level_X_bool

```

Internal variables used by command `\printkeyans` (§13.46), `show-pos` key (§13.26), `item-sym*` key (§13.34), `save-key` key (§13.26.2) and “*storing structure*”.

```

130 \tl_new:N \l__enumext_print_keyans_starred_tl
131 \bool_new:N \l__enumext_print_keyans_star_bool
132 \str_new:N \l__enumext_mark_position_str
133 \tl_new:N \g__enumext_item_symbol_aux_tl
134 \cs_set_protected:Npn \__enumext_tmp:n #1
135 {
136   \tl_new:c { \l__enumext_print_keyans_#1_tl }
137   \tl_new:c { \l__enumext_store_save_key_#1_tl }
138   \bool_new:c { \l__enumext_store_save_key_#1_bool }
139   \bool_new:c { \l__enumext_store_upper_level_#1_bool }
140 }
141 \clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_print_keyans_starred_tl` and others.)

```

\l__enumext_anspic_args_seq
\l__enumext_anspic_mini_width_dim
\l__enumext_anspic_above_int
\l__enumext_anspic_below_int
\l__enumext_anspic_label_above_bool
\l__enumext_anspic_mini_pos_str
\g__enumext_keyans_pic_parsep_skip
\l__enumext_anspic_label_box
\l__enumext_anspic_body_box
\l__enumext_anspic_label_htdp_dim
\l__enumext_anspic_body_htdp_dim

```

Internal variables used by `keyanspic` environment and `\anspic` command (§13.41.1).

```

142 \seq_new:N \l__enumext_anspic_args_seq
143 \dim_new:N \l__enumext_anspic_mini_width_dim
144 \int_new:N \l__enumext_anspic_above_int
145 \int_new:N \l__enumext_anspic_below_int
146 \bool_new:N \l__enumext_anspic_label_above_bool
147 \str_new:N \l__enumext_anspic_mini_pos_str
148 \skip_new:N \g__enumext_keyans_pic_parsep_skip
149 \box_new:N \l__enumext_anspic_label_box
150 \box_new:N \l__enumext_anspic_body_box
151 \dim_new:N \l__enumext_anspic_label_htdp_dim
152 \dim_new:N \l__enumext_anspic_body_htdp_dim

```

(End of definition for `\l__enumext_anspic_args_seq` and others.)

Internal variables used by “*internal check answer*” mechanism (§13.25.3) used by the `check-ans` and `no-store` keys and check for starred commands `\item*` in `keyans` and `keyans*` environments and `\anspic*` in `keyanspic` environment.

```

153 \bool_new:N \l__enumext_check_answers_bool
154 \bool_new:N \g__enumext_check_ans_key_bool
155 \tl_new:N \l__enumext_check_start_line_env_tl
156 \int_new:N \g__enumext_check_starred_cmd_int
157 \int_new:N \g__enumext_item_anskey_int
158 \int_new:N \g__enumext_item_number_int
159 \bool_new:N \l__enumext_item_number_bool
160 \int_new:N \g__enumext_item_answer_diff_int

```

(End of definition for `\l__enumext_check_answers_bool` and others.)

The boolean variable `\l__enumext_hyperref_bool` will determine if the `hyperref` package is present or load in memory (§13.8). The boolean variable `\l__enumext_footnotes_key_bool` determine if `hyperref` is load with key `hyperfootnotes=true`.

```

161 \bool_new:N \l__enumext_hyperref_bool
162 \bool_new:N \l__enumext_footnotes_key_bool

```

(End of definition for `\l__enumext_hyperref_bool` and `\l__enumext_footnotes_key_bool`.)

Internal variables used by `save-ref` key (§13.26). The variables `\l__enumext_label_copy_X_tl` correspond to temporary copies of the  $\langle labels \rangle$  defined by level on which operations will be performed.

The variables `\l__enumext_newlabel_arg_one_tl` and `\l__enumext_newlabel_arg_two_tl` will be used to form the arguments passed to the function `\__enumext_newlabel:nn` (§13.8) and the variable `\l__enumext_write_aux_file_tl` will be in charge of executing the writing code in the `.aux` file.

```

163 \tl_new:N \l__enumext_newlabel_arg_one_tl
164 \tl_new:N \l__enumext_newlabel_arg_two_tl
165 \tl_new:N \l__enumext_write_aux_file_tl
166 \cs_set_protected:Npn \__enumext_tmp:n #1
167 {
168   \tl_new:c { l__enumext_label_copy_#1_tl }
169 }
170 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_newlabel_arg_one_tl` and others.)

Internal variables used for redefinition of `\footnote` (§13.42.4).

```

171 \int_new:N \g__enumext_footnote_int
172 \seq_new:N \g__enumext_footnote_arg_seq
173 \seq_new:N \g__enumext_footnote_int_seq

```

(End of definition for `\g__enumext_footnote_int`, `\g__enumext_footnote_arg_seq`, and `\g__enumext_footnote_int_seq`.)

Internal variables used by `enumext*` and `keyans*` environments.

```

174 \cs_set_protected:Npn \__enumext_tmp:n #1
175 {
176   \bool_new:c { l__enumext_item_starred_#1_bool }
177   \int_new:c { l__enumext_item_column_pos_#1_int }
178   \int_new:c { g__enumext_item_count_all_#1_int }
179   \int_new:c { l__enumext_joined_item_#1_int }
180   \int_new:c { l__enumext_joined_item_aux_#1_int }
181   \int_new:c { l__enumext_tmpa_#1_int }
182   \dim_new:c { l__enumext_tmpa_#1_dim }
183   \box_new:c { l__enumext_item_text_#1_box }
184   \dim_new:c { l__enumext_joined_width_#1_dim }
185   \dim_new:c { l__enumext_item_width_#1_dim }
186   \tl_new:c { g__enumext_item_symbol_aux_#1_tl }
187   \str_new:c { l__enumext_align_label_#1_str }
188   \bool_new:c { g__enumext_minipage_active_#1_bool }
189   \box_new:c { l__enumext_miniright_code_#1_box }
190   \bool_new:c { g__enumext_minipage_center_#1_bool }
191   \dim_new:c { g__enumext_minipage_right_#1_dim }
192   \skip_new:c { g__enumext_minipage_right_#1_skip }
193 }
194 \clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\__enumext_item_starred_X_bool` and others.)

`\c__enumext_all_envs_clist` An internal `clist-var` variable to run with `\__enumext_tmp:n`.

```

195 \clist_const:Nn \c__enumext_all_envs_clist
196 {
197   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv},
198   {keyans}{v}, {enumext*}{vii}, {keyans*}{viii}
199 }
```

(End of definition for `\c__enumext_all_envs_clist`.)

### 13.5 Some utility functions

`\keys_precompile:neN` Non-standard kernel variants used by the `\printkeyans` command (§13.46) and `\foreachkeyans` command (§13.49).

`\seq_use:NV`

```

200 \cs_generate_variant:Nn \keys_precompile:nnN { neN }
201 \cs_generate_variant:Nn \seq_use:Nn { NV }
```

(End of definition for `\keys_precompile:neN` and `\seq_use:NV`.)

`\__enumext_at_begin_document:n` A internal “hook” function used for copying plain `list` and `minipage` environments definition and `hyperref` detection.

```

202 \cs_new_protected:Npn \__enumext_at_begin_document:n #1
203 {
204   \hook_gput_code:nnn {begindocument} {enumext} { #1 }
205 }
```

(End of definition for `\__enumext_at_begin_document:n`.)

`\__enumext_after_env:nn` A internal “hook” functions for execute code `mini-right` and `mini-right*` keys outside the `enumext*` and `keyans*` environments and print `check-ans` outside the `enumext` and `enumext*` environments.

`\__enumext_before_env:nn`

```

206 \cs_new_protected:Npn \__enumext_after_env:nn #1 #2
207 {
208   \hook_gput_code:nnn {env/#1/after} {enumext} {#2}
209 }
210 \cs_new_protected:Npn \__enumext_before_env:nn #1 #2
211 {
212   \hook_gput_code:nnn {env/#1/before} {enumext} {#2}
213 }
```

(End of definition for `\__enumext_after_env:nn` and `\__enumext_before_env:nn`.)

`\__enumext_level:` Function for check current level in `enumext`.

```

214 \cs_new:Nn \__enumext_level:
215 {
216   \int_to_roman:n { \__enumext_level_int }
217 }
```

(End of definition for `\__enumext_level:`.)

`\__enumext_if_is_int:nT` A conditional function to know if the variable we are passing is an integer used by `start` and `widest` keys.

`\__enumext_if_is_int:nF`

`\__enumext_if_is_int:nTF`

This function is taken directly from the answer given by Henri Menke in [How to test if an expl3 function argument is an integer expression?](#).

```

218 \prg_new_protected_conditional:Npnn \__enumext_if_is_int:n #1 { T, F, TF }
219 {
220   \regex_match:nnTF { ^[\+|-]?[\d]+$ } {#1} % $
221   { \prg_return_true: }
222   { \prg_return_false: }
223 }
```

(End of definition for `\__enumext_if_is_int:nT`, `\__enumext_if_is_int:nF`, and `\__enumext_if_is_int:nTF`.)

`\__enumext_regex_counter_style:`

The internal function `\__enumext_regex_counter_style:` replace the ‘`*`’ with the actual counter of the running level and is used by the `ref` key. It loops through the defined counter styles in `\c__enumext_counter_style_tl` and replace ‘`*`’ by real command, for example, looking for `\arabic*` and replacing that by `\arabic{<counter>}` defined on the current level.

```

224 \cs_new_protected:Nn \__enumext_regex_counter_style:
225 {
226   \tl_map_inline:Nn \c__enumext_counter_style_tl
227   {
228     \regex_replace_once:nnN { \c{##1}\* }
229     { \c{##1}\cB{\u{\l__enumext_ref_the_count_tl}\cE} } \l__enumext_ref_key_arg_tl
230   }
231 }
```

(End of definition for `\__enumext_regex_counter_style:`.)

`\__enumext_show_length:nnn`

Internal function used by `show-length` key to show “*all lengths*” calculated and use in `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```

232 \cs_new:Npn \__enumext_show_length:nnn #1 #2 #3
233 {
234     * ~ #2
235     \prg_replicate:nn { 14 - \str_count:n {#2} } { ~ }
236     = ~ \use:c { #1_use:c } { \__enumext_#2_#3_#1 } \\
237 }

```

(End of definition for `\__enumext_show_length:nnn`.)

`\__enumext_unskip_unkern:`

The function `\__enumext_unskip_unkern:` will remove the last `<skip>` or `<kern>` at execution time using the values `11` and `12` of `\lastnodetype` to apply `\unskip` or `\unkern` according to the case.

```

238 \cs_new_protected:Nn \__enumext_unskip_unkern:
239 {
240     \int_case:nnT { \lastnodetype }
241     {
242         { 11 }
243         {
244             % \typeout{SKIP} \typeout{\the\lastskip}
245             \unskip
246         }
247         { 12 }
248         {
249             % \typeout{KERN} \typeout{\the\lastkern}
250             \unkern
251         }
252     }
253 }

```

(End of definition for `\__enumext_unskip_unkern:`.)

### 13.5.1 Utilities for environments and levels

`\__enumext_is_not_nested:`

The function `\__enumext_is_not_nested:` set the variables `\g__enumext_standar_bool` and `\g__enumext_starred_bool` to “*true*” only if the environments `enumext` and `enumext*` are nested in each other and save the environment name in `\l__enumext_envir_name_tl`.

`\__enumext_is_on_first_level:`

```

254 \cs_new_protected:Nn \__enumext_is_not_nested:
255 {
256     \str_case:en { \@currenvir }
257     {
258         {enumext}
259         {
260             \tl_set:Nn \l__enumext_envir_name_tl { enumext }
261             \bool_lazy_and:nnT
262             { \bool_not_p:n { \g__enumext_standar_bool } }
263             { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
264             {
265                 \bool_gset_true:N \g__enumext_standar_bool
266             }
267         }
268         {enumext*}
269         {
270             \tl_set:Nn \l__enumext_envir_name_tl { enumext* }
271             \bool_lazy_and:nnT
272             { \bool_not_p:n { \g__enumext_starred_bool } }
273             { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
274             {
275                 \bool_gset_true:N \g__enumext_starred_bool
276             }
277         }
278     }
279 }

```

The function `\__enumext_is_on_first_level:` will set the variables `\l__enumext_standar_first_bool` (§13.25.1), `\l__enumext_starred_first_bool` (§13.25.1) and `\l__enumext_anskey_env_bool` (§13.30) to “*true*” only if the environment is not nested and we are in the “*first level*” of it . We will also save the *start line number* of each environment in the variable `\g__enumext_start_line_tl` and the *name* of each environment in the variable `\g__enumext_envir_name_tl` to use in messages related to the `check-ans` key and `.log` file.

```

280 \cs_new_protected:Nn \__enumext_is_on_first_level:
281 {
282   \bool_lazy_all:nT
283   {
284     { \bool_if_p:N \g__enumext_standar_bool }
285     { \int_compare_p:nNn { \l__enumext_level_int } = { 1 } }
286     { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
287   }
288   {
289     \bool_set_true:N \l__enumext_standar_first_bool
290     \bool_set_true:N \l__enumext_anskey_env_bool
291     \tl_gset:Nn \g__enumext_envir_name_tl { enumext }
292     \tl_gset:Ne \g__enumext_start_line_tl
293     {
294       on ~ line ~ \exp_not:V \inputlineno
295     }
296   }
297   \bool_lazy_all:nT
298   {
299     { \bool_if_p:N \g__enumext_starred_bool }
300     { \int_compare_p:nNn { \l__enumext_level_h_int } = { 1 } }
301     { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
302   }
303   {
304     \bool_set_true:N \l__enumext_starred_first_bool
305     \bool_set_true:N \l__enumext_anskey_env_bool
306     \tl_gset:Nn \g__enumext_envir_name_tl { enumext* }
307     \tl_gset:Ne \g__enumext_start_line_tl
308     {
309       on ~ line ~ \exp_not:V \inputlineno
310     }
311   }
312 }

```

(End of definition for \\_\_enumext\_is\_not\_nested: and \\_\_enumext\_is\_on\_first\_level:.)

\\_\_enumext\_keyans\_name\_and\_start:

The function \\_\_enumext\_keyans\_name\_and\_start: will save the start line number and name of the environments `keyans`, `keyans*` and `keyanspic` in the variables `\l__enumext_check_start_line_env_tl` and `\l__enumext_envir_name_tl` to use in the `\__enumext_check_starred_cmd:n` function.

```

313 \cs_new_protected:Nn \__enumext_keyans_name_and_start:
314 {
315   \str_case:en { \@currenvir }
316   {
317     {keyans}
318     {
319       \tl_set:Nn \l__enumext_envir_name_tl { keyans }
320       \tl_set:Ne \l__enumext_check_start_line_env_tl
321       {
322         in ~ 'keyans' ~ start ~ on ~ line ~ \exp_not:V \inputlineno
323       }
324     }
325     {keyans*}
326     {
327       \tl_set:Nn \l__enumext_envir_name_tl { keyans* }
328       \tl_set:Ne \l__enumext_check_start_line_env_tl
329       {
330         in ~ 'keyans*' ~ start ~ on ~ line ~ \exp_not:V \inputlineno
331       }
332     }
333     {keyanspic}
334     {
335       \tl_set:Nn \l__enumext_envir_name_tl { keyanspic }
336       \tl_set:Ne \l__enumext_check_start_line_env_tl
337       {
338         in ~ 'keyanspic' ~ start ~ on ~ line ~ \exp_not:V \inputlineno
339       }
340     }
341   }
342 }

```

(End of definition for \\_\_enumext\_keyans\_name\_and\_start:.)



### 13.5.2 Utilities for log and terminal

The function `\__enumext_reset_global_vars:` will be passed to the function `\__enumext_execute_after_env:` and will return the global variables to their default values after being used.

```

343 \cs_new_protected:Nn \__enumext_reset_global_vars:
344 {
345   \__enumext_reset_global_int:
346   \__enumext_reset_global_bool:
347   \__enumext_reset_global_tl:
348 }
349 \cs_new_protected:Nn \__enumext_reset_global_int:
350 {
351   \int_gzero:N \g__enumext_item_number_int
352   \int_gzero:N \g__enumext_item_anskey_int
353   \int_gzero:N \g__enumext_item_answer_diff_int
354 }
355 \cs_new_protected:Nn \__enumext_reset_global_bool:
356 {
357   \bool_gset_false:N \g__enumext_check_ans_key_bool
358   \bool_gset_false:N \g__enumext_standar_bool
359   \bool_gset_false:N \g__enumext_starred_bool
360 }
361 \cs_new_protected:Nn \__enumext_reset_global_tl:
362 {
363   \tl_gclear:N \g__enumext_store_name_tl
364   \tl_gclear:N \g__enumext_start_line_tl
365   \tl_gclear:N \g__enumext_envir_name_tl
366 }

```

(End of definition for `\__enumext_reset_global_vars:` and others.)

The function `\__enumext_log_global_vars:` will be passed to the function `\__enumext_execute_after_env:` and write to the `.log` file the number of elements saved in the *prop list* and *sequence* created by the *save-ans* key along with the value of the integer variable created for the *resume* key.

```

367 \cs_new_protected:Nn \__enumext_log_global_vars:
368 {
369   \msg_log:nneeee { enumext } { prop-seq-int-hook }
370   { \g__enumext_store_name_tl }
371   { \prop_count:c { g__enumext_ \g__enumext_store_name_tl _prop } }
372   { \seq_count:c { g__enumext_ \g__enumext_store_name_tl _seq } }
373   { \int_use:c { g__enumext_resume_ \g__enumext_store_name_tl _int } }
374 }

```

The function `\__enumext_log_answer_vars:` will be passed to the function `\__enumext_execute_after_env:` and write to the `.log` file the number of items and answers along with the difference between them.

```

375 \cs_new_protected:Nn \__enumext_log_answer_vars:
376 {
377   \msg_log:nneee { enumext } { item-answer-hook }
378   { \int_use:N \g__enumext_item_number_int }
379   { \int_use:N \g__enumext_item_anskey_int }
380   { \int_eval:n { \g__enumext_item_number_int - \g__enumext_item_anskey_int } }
381 }

```

(End of definition for `\__enumext_log_global_vars:` and `\__enumext_log_answer_vars:`.)

## 13.6 Copying list and minipage environments

The `list` environment provided by  $\text{\LaTeX}$  has the following plain form:

```

\list{⟨arg one⟩}{⟨arg two⟩}
  \item[⟨opt⟩]
\endlist

```

And `minipage` environment provided by  $\text{\LaTeX}$  has the following (simplified) plain form:

```

\minipage[⟨pos⟩][⟨height⟩][⟨inner-pos⟩]{⟨width⟩}
  ⟨internal implement⟩
\endminipage

```

As a precaution we copy them using `\__enumext_at_begin_document:n` in case any package redefines the `list` environment or a related command.

- For compatibility with *tagged* PDF we should use `\NewCommandCopy` and not `\cs_new_eq:NN` for `\item`. When *tagged* PDF is active `\item` is redefined using `\ltxcmd` (see `latex-lab-block`).

```

\__enumext_start_list:nn
\__enumext_stop_list:
\__enumext_item_std:w
\__enumext_minipage:w
\__enumext_endminipage:

```

The functions `\__enumext_start_list:nn` and `\__enumext_stop_list:` correspond to copies of `\list` and `\endlist` from plain definition of `list`, the function `\__enumext_item_std:w` is a copy of the `\item` command.

```

382 \__enumext_at_begin_document:n
383 {
384     \cs_new_eq:NN \__enumext_start_list:nn \list
385     \cs_new_eq:NN \__enumext_stop_list: \endlist
386     \NewCommandCopy \__enumext_item_std:w \item
387 }

```

The functions `\__enumext_minipage:w` and `\__enumext_endminipage:` correspond to copies of `\minipage` and `\endminipage` from plain definition of `minipage` environment.

```

388 \__enumext_at_begin_document:n
389 {
390     \cs_new_eq:NN \__enumext_minipage:w \minipage
391     \cs_new_eq:NN \__enumext_endminipage: \endminipage
392 }

```

(End of definition for `\__enumext_start_list:nn` and others.)

### 13.7 The internal minipage environment

```

\__enumext_internal_mini_page:
__enumext_mini_env*

```

The function `\__enumext_internal_mini_page:` creates a internal `__enumext_mini_page` environment (*custom version* of `minipage`) setting the `\if@minipage` switch to “false” to allow spaces at the “above” of the environment, plus we will add `\skip_vertical:N \c_zero_skip` to maintain alignment on “top” in the first part and `\skip_vertical:N \c_zero_skip` in the second part to allow spaces “below”. This environment will be used internally by the `mini-env` key, it is not documented in the user interface and is for internal use only. This function is passed to the function `\__enumext_safe_exec:` in the `enumext` environment definition (§13.38) and `\__enumext_safe_exec_vii:` in the `enumext*` environment definition (§13.43)

```

393 \cs_new_protected:Nn \__enumext_internal_mini_page:
394 {
395     \int_compare:nNnT { \__enumext_level_int } = { 0 }
396     {
397         \DeclareDocumentEnvironment{__enumext_mini_page}{ m }
398         {
399             \__enumext_minipage:w [ t ] { ##1 }
400             \legacy_if_gset_false:n { @minipage }
401             \skip_vertical:N \c_zero_skip
402         }
403         {
404             \skip_vertical:N \c_zero_skip
405             \__enumext_endminipage:
406         }
407     }
408 }

```

(End of definition for `\__enumext_internal_mini_page:` and `__enumext_mini_env*`.)

### 13.8 Compatibility with hyperref and footnotehyper

First we define the necessary rules using “hooks” to determine if the `hyperref` package is loaded.

```

409 \hook_gput_code:nnn { begindocument } { enumext } { \__enumext_after_hyperref: }
410 \hook_gset_rule:nnnn { begindocument } { enumext } { after } { hyperref }

```

```

\__enumext_after_hyperref:
\__enumext_hypertarget:nn
\__enumext_phantomsection:

```

The function `\__enumext_after_hyperref:` sets the state of the boolean variable `\l__enumext_hyperref_bool` to “true” if the package is loaded. At this point we will use the public macro `\IfHyperBoolean` to determine if the `hyperfootnotes=true` key is present, if so, we set the state of the boolean variable `\__enumext_footnotes_key_bool` to “true”.

```

411 \cs_new_protected:Nn \__enumext_after_hyperref:
412 {
413     \IfPackageLoadedTF { hyperref }
414     {
415         \msg_info:nnn { enumext } { package-load } { hyperref }
416         \bool_set_true:N \l__enumext_hyperref_bool
417         \IfHyperBoolean{hyperfootnotes}
418         {
419             % \typeout{hyperfootnotes=true}
420             \bool_set_true:N \l__enumext_footnotes_key_bool
421         }
422     }

```

```

423         % \typeout{hyperfootnotes=false}
424     }
425 }
426 { }

```

If the state of the variable `\l__enumext_footnotes_key_bool` is true we will check if the package `footnotehyper` is loaded, in case it is not present, we will set the value of `\l__enumext_footnotes_key_bool` to false and we will redefine `\footnote`.

```

427 \bool_if:NT \l__enumext_footnotes_key_bool
428 {
429     \IfPackageLoadedTF { footnotehyper }
430     {
431         \msg_info:nnn { enumext } { package-load } { footnotehyper }
432     }
433     {
434         % \typeout{No ~ footnotehyper ~ load}
435         % \typeout{Load ~ and ~ use ~ \string\makesavenoteenv{enumext*}}
436         \bool_set_false:N \l__enumext_footnotes_key_bool
437     }
438 }

```

The functions `\__enumext_hypertarget:nn` and `\__enumext_phantomsection:` correspond to the internal copies of `\hypertarget` and `\phantomsection`. If the boolean variable `\l__enumext_hyperref_bool` is false the functions `\__enumext_hypertarget:nn` and `\__enumext_phantomsection:` will be disabled.

```

439 \bool_if:NTF \l__enumext_hyperref_bool
440 {
441     \cs_new_eq:NN \__enumext_hypertarget:nn \hypertarget
442     \cs_new_eq:NN \__enumext_phantomsection: \phantomsection
443 }
444 {
445     \cs_new_eq:NN \__enumext_hypertarget:nn \use_none:nn
446     \cs_new_eq:NN \__enumext_phantomsection: \prg_do_nothing:
447 }
448 }

```

(End of definition for `\__enumext_after_hyperref:`, `\__enumext_hypertarget:nn`, and `\__enumext_phantomsection:`.)

`\__enumext_newlabel:nn`

The function `\__enumext_newlabel:nn` write the information to the `.aux` file when using the `save-ref` key. The arguments taken by the function are:

#1: `\l__enumext_newlabel_arg_one_tl`  
 #2: `\l__enumext_newlabel_arg_two_tl`

- The trick here is to manage the number of arguments passed to `\newlabel{#1}{#2}` according to the presence of the `hyperref` package.

```

449 \cs_new_protected:Npn \__enumext_newlabel:nn #1 #2
450 {
451     \protected@write \@auxout { }
452     {
453         \token_to_str:N \newlabel {#1}
454         {
455             {#2}
456             \bool_if:NT \l__enumext_hyperref_bool
457             { { \thepage } {#2} {#1} }
458             { }
459         }
460     }
461     \__enumext_hypertarget:nn {#1} { }
462     \__enumext_phantomsection:
463 }

```

(End of definition for `\__enumext_newlabel:nn`.)

## 13.9 Definition of public dimension

The package `enumext` only provides a single public dimension `\itemwidth` and is intended for user convenience only and is not for internal use as such. This dimension is set in all environments and is only used by the `wrap-ans` key at its default value.

```

464 \dim_zero_new:N \itemwidth

```

### 13.10 Definition of counters

```
\__enumext_define_counters:Nn
\__enumext_define_counters:cn
```

To create the necessary “counters” we must first make sure that they are not already defined by the user or a package such as **enumitem**, otherwise a error will be returned and the package loading will be aborted. The arguments taken by the function are:

- #1 : A token list `\__enumext_counter_X_tl` for “store” the counter’s name.
- #2 : The counter’s name.

```
465 \cs_new_protected:Npn \__enumext_define_counters:Nn #1 #2
466 {
467   \cs_if_exist:cTF { c@ #2 }
468   { \msg_fatal:nnn { enumext } { counters }{ #2 } }
469   {
470     \tl_set:Nn #1 { #2 }
471     \newcounter { #2 }
472   }
473 }
```

(End of definition for `\__enumext_define_counters:Nn`.)

The counters created here are `enumXi`, `enumXii`, `enumXiii` and `enumXiv` for **enumext** environment, `enumXv` for **keyans** environment, `enumXvi` for **keyanspic** environment, `enumXvii` for **enumext\*** and `enumXviii` for the **keyans\*** environments.

```
enumXi 474 \__enumext_define_counters:Nn \__enumext_counter_i_tl { enumXi }
enumXii 475 \__enumext_define_counters:Nn \__enumext_counter_ii_tl { enumXii }
enumXiii 476 \__enumext_define_counters:Nn \__enumext_counter_iii_tl { enumXiii }
enumXiv 477 \__enumext_define_counters:Nn \__enumext_counter_iv_tl { enumXiv }
enumXv 478 \__enumext_define_counters:Nn \__enumext_counter_v_tl { enumXv }
enumXvi 479 \__enumext_define_counters:Nn \__enumext_counter_vi_tl { enumXvi }
enumXvii 480 \__enumext_define_counters:Nn \__enumext_counter_vii_tl { enumXvii }
enumXviii 481 \__enumext_define_counters:Nn \__enumext_counter_viii_tl { enumXviii }
```

(End of definition for `enumXi` and others.)

### 13.11 Definition of labels

This part of the code is inspired by the **enumitem** package. The idea is to be able to access the counters using `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` to use them in the `label` key.

```
\__enumext_register_counter_style:Nn
```

These *counters* will be used as default *labels* if the `label` key is not used for the different levels of the **enumext**, **enumext\***, **keyans** and **keyans\*** environments, so it is necessary to get a default value for `labelwidth` from these *labels* at the same time.

```
482 \cs_new_protected:Npn \__enumext_register_counter_style:Nn #1 #2
483 {
484   \tl_const:cn { c__enumext_widest_ \cs_to_str:N #1 _tl } {#2}
485   \tl_gput_right:Nn \g__enumext_counter_styles_tl {#1}
486 }
487 \__enumext_register_counter_style:Nn \arabic { 0 }
488 \__enumext_register_counter_style:Nn \Alph { M }
489 \__enumext_register_counter_style:Nn \alph { m }
490 \__enumext_register_counter_style:Nn \Roman { VIII }
491 \__enumext_register_counter_style:Nn \roman { viii }
```

(End of definition for `\__enumext_register_counter_style:Nn`.)

```
\__enumext_label_width_by_box:Nn
\__enumext_label_width_by_box:cv
```

The function `\__enumext_label_width_by_box:Nn` set the default `\labelwidth` using a box width if no `labelwidth` key is passed.

```
492 \cs_new_protected:Npn \__enumext_label_width_by_box:Nn #1 #2
493 {
494   \hbox_set:Nn \l__enumext_label_width_by_box {#2}
495   \dim_set:Nn #1 { \box_wd:N \l__enumext_label_width_by_box }
496 }
497 \cs_generate_variant:Nn \__enumext_label_width_by_box:Nn { cv }
```

(End of definition for `\__enumext_label_width_by_box:Nn`.)

```
\__enumext_label_style:Nnn
\__enumext_label_style:cvn
```

The function `\__enumext_label_style:Nnn` is used by the `label` key to creates the variables containing the *label style* and will allow to use `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` as arguments. It loops through the defined counter styles in `\g__enumext_counter_styles_tl` (`\arabic`, `\alph`, `\Alph`, `\roman`, and `\Roman`) for example, looking for `\roman*` and replacing that by `\roman{<counter>}`, and doing the same for the `\g__enumext_widest_label_tl` to keep both in sync.

```
498 \cs_new_protected:Npn \__enumext_label_style:Nnn #1 #2 #3
```

```

499 {
500   \tl_clear_new:N #1
501   \tl_put_right:Ne #1 { \tl_trim_spaces:n {#3} }
502   \tl_gset_eq:NN \g__enumext_widest_label_tl #1
503   \tl_map_inline:Nn \g__enumext_counter_styles_tl
504     {
505       \tl_replace_all:Nne #1 { ##1* } { \exp_not:N ##1 {#2} }
506       \tl_greplace_all:Nne \g__enumext_widest_label_tl { ##1* }
507       { \tl_use:c { c__enumext_widest_ \cs_to_str:N ##1 _tl } }
508     }
509   \__enumext_label_width_by_box:Nn \__enumext_current_widest_dim
510   { \tl_use:N \g__enumext_widest_label_tl }
511   \tl_set_eq:cN { the #2 } #1
512 }
513 \cs_generate_variant:Nn \__enumext_label_style:Nnn { cvn }

```

(End of definition for `\__enumext_label_style:Nnn`.)

### 13.12 Setting keys associated with label

When *tagged* PDF is active `\make_label` is redefined using `\make_box` to work correctly (§13.33). From the user side it is convenient to have a key that allows using this redefinition with `\make_box` without having `\IfDocumentMetadataTF` active.

`mode-box` We define the key `mode-box` only for the “first level” of `enumext` environment.

```

514 \keys_define:nn { enumext / level-1 }
515 {
516   mode-box .bool_set:N = \l__enumext_mode_box_bool,
517   mode-box .initial:n = false,
518   mode-box .value_forbidden:n = true,
519 }

```

(End of definition for `mode-box`.)

`font` Definition of keys `font`, `labelsep`, `labelwidth`, `wrap-label` and `wrap-label*` keys for `enumext` and `keyans` environments.

```

520 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
521 {
522   \keys_define:nn { enumext / #1 }
523   {
524     font .tl_set:c = { l__enumext_label_font_style_#2_tl },
525     font .value_required:n = true,
526     labelsep .dim_set:c = { l__enumext_labelsep_#2_dim },
527     labelsep .initial:n = {0.3333em},
528     labelsep .value_required:n = true,
529     labelwidth .dim_set:c = { l__enumext_labelwidth_#2_dim },
530     labelwidth .value_required:n = true,
531     wrap-label .cs_set_protected:cp = { __enumext_wrapper_label_#2:n } ##1,
532     wrap-label .initial:n = {##1},
533     wrap-label .value_required:n = true,
534     wrap-label* .code:n = {
535       \bool_set_true:c { l__enumext_wrap_label_opt_#2_bool }
536       \keys_set:nn { enumext / #1 } { wrap-label = {##1} }
537     },
538     wrap-label* .value_required:n = true,
539   }
540 }
541 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `font` and others.)

• In this point, the following are set `\__enumext_wrapper_label_X:n` which will be used by `\__enumext_make_label:` for the different levels of the `enumext` environment and is set to `\__enumext_wrapper_label_v:n` which will be used by `\__enumext_keyans_make_label:` for `keyans` and `keyanspic` environments.

`align` The `align` key is implemented differently for “starred” and “non starred” environments. For compatibility with *tagged* PDF we must set `\l__enumext_align_label_pos_X_str`.

```

542 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
543 {
544   \keys_define:nn { enumext / #1 }
545   {
546     align .choice:,

```

```

547         align / left .code:n =
548             {
549                 \tl_clear:c { l__enumext_label_fill_left_#2_tl }
550                 \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
551                 \str_set:cn { l__enumext_align_label_pos_#2_str } { l }
552             },
553         align / right .code:n =
554             {
555                 \tl_set:cn { l__enumext_label_fill_left_#2_tl } { \hfill }
556                 \tl_clear:c { l__enumext_label_fill_right_#2_tl }
557                 \str_set:cn { l__enumext_align_label_pos_#2_str } { r }
558             },
559         align / center .code:n =
560             {
561                 \tl_set:cn { l__enumext_label_fill_left_#2_tl } { \hfill }
562                 \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
563                 \str_set:cn { l__enumext_align_label_pos_#2_str } { c }
564             },
565         align / unknown .code:n =
566             \msg_error:nneee { enumext } { unknown-choice }
567             { align } { left, ~ right, ~ center } { \exp_not:n {##1} },
568         align .initial:n = left,
569         align .value_required:n = true,
570     }
571 }
572 \clist_map_inline:nn
573 {
574     {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {keyans}{v}
575 }
576 { \__enumext_tmp:nn #1 }

577 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
578 {
579     \keys_define:nn { enumext / #1 }
580     {
581         align .choice:,
582         align / left .code:n = \str_set:cn { l__enumext_align_label_#2_str } { l },
583         align / right .code:n = \str_set:cn { l__enumext_align_label_#2_str } { r },
584         align / center .code:n = \str_set:cn { l__enumext_align_label_#2_str } { c },
585         align / unknown .code:n =
586             \msg_error:nneee { enumext } { unknown-choice }
587             { align } { left, ~ right, ~ center } { \exp_not:n {##1} },
588         align .initial:n = left,
589         align .value_required:n = true,
590     }
591 }
592 \clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }

```

(End of definition for align.)

### 13.13 Setting label and ref keys

The implementation of the keys `label` and `ref` are part of the core of the package `enumext`, here the default values for `<label>`, the value of the variables `\l__enumext_label_X_tl`, the default values for `\labelwidth` and the “*label and ref*” system.

#### 13.13.1 Define and set label and ref keys for enumext environment

Here we set the default `<labels>` of the *four levels* of `enumext` environment, along with the default value for `labelwidth` key and `ref` key.

```

\l__enumext_label_i_tl
\l__enumext_label_ii_tl
\l__enumext_label_iii_tl
\l__enumext_label_iv_tl

593 \cs_set_protected:Npn \__enumext_tmp:nnn #1 #2 #3
594 {
595     \keys_define:nn { enumext / #1 }
596     {
597         label .code:n = {
598             \__enumext_label_style:cnv { l__enumext_label_#2_tl }
599             { l__enumext_counter_#2_tl } {##1}
600             \dim_set_eq:cN { l__enumext_labelwidth_#2_dim }
601             \l__enumext_current_widest_dim
602         },
603         label .initial:n = #3,
604         label .value_required:n = true,
605         ref .code:n = \__enumext_standar_ref:n {##1},

```



```

606         ref .value_required:n = true,
607     }
608 }
609 \__enumext_tmp:nnn { level-1 } { i } { \arabic*.}
610 \__enumext_tmp:nnn { level-2 } { ii } { (\alph*) }
611 \__enumext_tmp:nnn { level-3 } { iii } { \roman*. }
612 \__enumext_tmp:nnn { level-4 } { iv } { \Alph*. }

```

(End of definition for `label` and others.)

\\_\_enumext\_standar\_ref:n  
 \\_\_enumext\_standar\_ref:

The `\__enumext_standar_ref:n` first we will pass the key argument to `\l__enumext_ref_key_arg_tl` and we will analyze its state, if it is not *empty* we will make a copy of the current counter in `\l__enumext_ref_the_count_tl` and we will execute the function `\__enumext_regex_counter_style:` which will return the modified `\l__enumext_ref_key_arg_tl` and we make the value of `\l__enumext_ref_the_count_tl` the same as that `\l__enumext_the_counter_X_tl` which contains `\theenumX` and finally we set `\l__enumext_renew_the_count_X_tl` with the renewed command.

```

613 \cs_new_protected:Npn \__enumext_standar_ref:n #1
614 {
615     \tl_set:Nn \l__enumext_ref_key_arg_tl {#1}
616     \tl_if_empty:NTF \l__enumext_ref_key_arg_tl
617     {
618         \msg_error:nnn { enumext } { key-ref-empty } { enumext }
619     }
620     {
621         \tl_set_eq:Nc
622         \l__enumext_ref_the_count_tl { \l__enumext_counter_ \__enumext_level: _tl }
623         \__enumext_regex_counter_style:
624         \tl_set_eq:Nc
625         \l__enumext_ref_the_count_tl { \l__enumext_the_counter_ \__enumext_level: _tl }
626         \tl_put_right:ce { \l__enumext_renew_the_count_ \__enumext_level: _tl }
627         {
628             \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_the_count_tl } { \exp_not:V \l__
629         }
630     }
631 }

```

Finally the function `\__enumext_standar_ref:` will execute the modification for the reference system in the second argument of the environment definition `enumext`.

```

632 \cs_new_protected:Npn \__enumext_standar_ref:
633 {
634     \tl_if_empty:cF { \l__enumext_renew_the_count_ \__enumext_level: _tl }
635     {
636         \tl_use:c { \l__enumext_renew_the_count_ \__enumext_level: _tl }
637     }
638 }

```

(End of definition for `\__enumext_standar_ref:n` and `\__enumext_standar_ref:`.)

### 13.13.2 Define and set `label` and `ref` keys for `enumext*` and `keyans*` environments

Here we set the default *⟨labels⟩* for `enumext*` and `keyans*` environments, along with the default value for `labelwidth` key and `ref` key.

```

\l__enumext_label_vii_tl
\l__enumext_label_viii_tl
639 \cs_set_protected:Npn \__enumext_tmp:nnn #1 #2 #3
640 {
641     \keys_define:nn { enumext / #1 }
642     {
643         label .code:n = {
644             \__enumext_label_style:cvn { \l__enumext_label_#2_tl }
645             { \l__enumext_counter_#2_tl } {##1}
646             \dim_set_eq:cN { \l__enumext_labelwidth_#2_dim }
647             \l__enumext_current_widest_dim
648         },
649         label .initial:n = #3,
650         label .value_required:n = true,
651         ref .code:n = \__enumext_starred_ref:n {##1},
652         ref .value_required:n = true,
653     }
654 }
655 \__enumext_tmp:nnn { enumext* } { vii } { \arabic*.}
656 \__enumext_tmp:nnn { keyans* } { viii } { \Alph*.}

```

(End of definition for `label` and others.)

\\\_enumext\_starred\_ref:n  
\\\_enumext\_starred\_ref:

The implementation of \\\_enumext\_starred\_ref:n is the same as that used for the environment `enumext`.

```

657 \cs_new_protected:Npn \\_enumext_starred_ref:n #1
658 {
659   \tl_set:Nn \\_enumext_ref_key_arg_tl {#1}
660   \int_compare:nNnT { \\_enumext_level_h_int } = { 1 }
661   {
662     \tl_if_empty:NTF \\_enumext_ref_key_arg_tl
663     {
664       \msg_error:nnn { enumext } { key-ref-empty } { enumext* }
665     }
666     {
667       \tl_set_eq:NN \\_enumext_ref_the_count_tl \\_enumext_counter_vii_tl
668       \\_enumext_regex_counter_style:
669       \tl_set_eq:NN \\_enumext_ref_the_count_tl \\_enumext_the_counter_vii_tl
670       \tl_put_right:Ne \\_enumext_renew_the_count_vii_tl
671       {
672         \exp_not:N \renewcommand { \exp_not:V \\_enumext_ref_the_count_tl } { \exp_not:V
673       }
674     }
675   }
676   \int_compare:nNnT { \\_enumext_keyans_level_h_int } = { 1 }
677   {
678     \tl_if_empty:NTF \\_enumext_ref_key_arg_tl
679     {
680       \msg_error:nnn { enumext } { key-ref-empty } { keyans* }
681     }
682     {
683       \tl_set_eq:NN \\_enumext_ref_the_count_tl \\_enumext_counter_viii_tl
684       \\_enumext_regex_counter_style:
685       \tl_set_eq:NN \\_enumext_ref_the_count_tl \\_enumext_the_counter_viii_tl
686       \tl_put_right:Ne \\_enumext_renew_the_count_viii_tl
687       {
688         \exp_not:N \renewcommand { \exp_not:V \\_enumext_ref_the_count_tl } { \exp_not:V
689       }
690     }
691   }
692 }

```

Finally the function \\\_enumext\_starred\_ref: will execute the modification for the reference system in the second argument of the `enumext*` and `keyans*` environment definition.

```

693 \cs_new_protected:Npn \\_enumext_starred_ref:
694 {
695   \int_compare:nNnT { \\_enumext_level_h_int } = { 1 }
696   {
697     \tl_if_empty:NF \\_enumext_renew_the_count_vii_tl
698     {
699       \tl_use:N \\_enumext_renew_the_count_vii_tl
700     }
701   }
702   \int_compare:nNnT { \\_enumext_keyans_level_h_int } = { 1 }
703   {
704     \tl_if_empty:NF \\_enumext_renew_the_count_viii_tl
705     {
706       \tl_use:N \\_enumext_renew_the_count_viii_tl
707     }
708   }
709 }

```

(End of definition for \\\_enumext\_starred\_ref:n and \\\_enumext\_starred\_ref:.)

### 13.13.3 Define and set label and ref keys for keyans and keyanspic environments

Here we set the default  $\langle label \rangle$  for `keyans` and `keyanspic` environment, along with the default value for `labelwidth` and `ref` key. The `keyanspic` environment use the same  $\langle label \rangle$  as the `keyans` environment.

\\\_enumext\_label\_v\_tl  
\\\_enumext\_label\_vi\_tl

```

710 \keys_define:nn { enumext / keyans }
711 {
712   label .code:n = {
713     \\_enumext_label_style:cvn { \\_enumext_label_v_tl }
714     { \\_enumext_counter_v_tl } {#1}
715     \\dim_set_eq:cN { \\_enumext_labelwidth_v_dim }
716     \\_enumext_current_widest_dim
717     \\_enumext_label_style:cvn { \\_enumext_label_vi_tl }

```

```

718             { l__enumext_counter_vi_tl } {#1}
719             \dim_set_eq:cN { l__enumext_labelwidth_v_dim }
720             \l__enumext_current_widest_dim
721         },
722     label .initial:n = \Alph*),
723     label .value_required:n = true,
724     ref .code:n = \__enumext_keyans_ref:n {#1},
725     ref .value_required:n = true,
726 }

```

(End of definition for `label` and others.)

\\_\_enumext\_keyans\_ref:n  
 \\_\_enumext\_keyans\_ref:

The implementation of `\__enumext_keyans_ref:n` is the same as that used for the environment `enumext`.

```

727 \cs_new_protected:Npn \__enumext_keyans_ref:n #1
728 {
729     \tl_set:Nn \l__enumext_ref_key_arg_tl {#1}
730     \tl_if_empty:NTF \l__enumext_ref_key_arg_tl
731     {
732         \msg_error:nnn { enumext } { key-ref-empty } { keyans }
733     }
734     {
735         \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_counter_v_tl
736         \__enumext_regex_counter_style:
737         \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_the_counter_v_tl
738         \tl_put_right:Ne \l__enumext_renew_the_count_v_tl
739         {
740             \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_the_count_tl } { \exp_not:V \l__
741         }
742     }
743 }

```

Finally the function `\__enumext_keyans_ref:` will execute the modification for the reference system in the second argument of the `keyans*` environment definition.

```

744 \cs_new_protected:Nn \__enumext_keyans_ref:
745 {
746     \tl_if_empty:NF \l__enumext_renew_the_count_v_tl
747     {
748         \tl_use:N \l__enumext_renew_the_count_v_tl
749     }
750 }

```

(End of definition for `\__enumext_keyans_ref:n` and `\__enumext_keyans_ref:`.)

### 13.14 Setting start, start\* and widest keys

\\_\_enumext\_start\_from:NNn  
 \\_\_enumext\_start\_from:ccn  
 \\_\_enumext\_start\_from:cce

The function `\__enumext_start_from:NNn` used by `start` and `start*` keys take three arguments:

#1: `\l__enumext_label_X_tl`  
 #2: `\l__enumext_start_X_int`  
 #3: *⟨integer or string⟩*

The first argument of this function are the “*counter style*” set by `label` key, the second argument is returned by the function, the third argument can be an *⟨integer⟩* or *⟨string⟩* of the form `\Alph`, `\alph`, `\Roman` or `\roman`. This effectively allows `start=A` or `start=1` to be used.

```

751 \cs_new_protected:Npn \__enumext_start_from:NNn #1 #2 #3
752 {
753     \__enumext_if_is_int:nTF { #3 }
754     {
755         \int_set:Nn #2 {#3}
756     }
757     {
758         \regex_match:nVT { \c{Alph} | \c{alph} } {#1}
759         { \int_set:Nn #2 { \int_from_alph:n {#3} } }
760         \regex_match:nVT { \c{Roman} | \c{roman} } {#1}
761         { \int_set:Nn #2 { \int_from_roman:n {#3} } }
762     }
763 }
764 \cs_generate_variant:Nn \__enumext_start_from:NNn { ccn, cce }

```

(End of definition for `\__enumext_start_from:NNn`.)

\\_\_enumext\_widest\_from:nNNn  
 \\_\_enumext\_widest\_from:nccn

The function `\__enumext_widest_from:nNNn` used by the `widest` key take four arguments:

#1: The counter associated with the environment level  
 #2: `\l__enumext_label_X_tl`

#3: `\__enumext_labelwidth_X_dim`  
 #4: `<integer or string>`

The second and third arguments of this function are the values set by `label` and `labelwidth` keys, the four argument can be an `<integer>` or `<string>` of the form `\Alph`, `\alph`, `\Roman` or `\roman`. The value of the four argument is set temporarily for the identified counter in this point (level), then the value is expanded into a “box” and the “width” of the “box” is returned.

```

765 \cs_new_protected:Npn \__enumext_widest_from:nNNn #1 #2 #3 #4
766 {
767   \__enumext_if_is_int:nTF {#4}
768   {
769     \setcounter{enumX#1} { #4 }
770   }
771   {
772     \regex_match:nVT { \c{Alph} | \c{alph} } {#2}
773     { \setcounter{enumX#1} { \int_from_alph:n {#4} } }
774     \regex_match:nVT { \c{Roman} | \c{roman} } {#2}
775     { \setcounter{enumX#1} { \int_from_roman:n {#4} } }
776   }
777   \__enumext_label_width_by_box:cv
778   { \__enumext_labelwidth_#1_dim } { \__enumext_label_#1_tl }
779 }
780 \cs_generate_variant:Nn \__enumext_widest_from:nNNn { nccn }

```

(End of definition for `\__enumext_widest_from:nNNn`.)

Now define and set `start*`, `start` and `widest` keys for `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```

781 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
782 {
783   \keys_define:nn { enumext / #1 }
784   {
785     start* .code:n = {
786       \__enumext_start_from:ccn
787       { \__enumext_label_#2_tl }
788       { \__enumext_start_#2_int } {##1}
789     },
790     start* .value_required:n = true,
791     start .code:n = {
792       \__enumext_start_from:cce
793       { \__enumext_label_#2_tl }
794       { \__enumext_start_#2_int } { \int_eval:n {##1} }
795     },
796     start .initial:n = 1,
797     start .value_required:n = true,
798     widest .code:n = {
799       \__enumext_widest_from:nccn {#2}
800       { \__enumext_label_#2_tl }
801       { \__enumext_labelwidth_#2_dim } {##1}
802     },
803     widest .value_required:n = true,
804   }
805 }
806 \clist_map_inline:Nn \__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `start`, `start*`, and `widest`.)

### 13.15 Setting keys for vertical spaces

Define and set `topsep`, `partopsep`, `parsep`, `itemsep`, `noitemsep` and `nosep` keys for `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```

807 \cs_set_protected:Npn \__enumext_tmp:nnnnnn #1 #2 #3 #4 #5 #6
808 {
809   \keys_define:nn { enumext / #1 }
810   {
811     topsep .skip_set:c = { \__enumext_topsep_#2_skip },
812     topsep .initial:n = {#3},
813     topsep .value_required:n = true,
814     partopsep .skip_set:c = { \__enumext_partopsep_#2_skip },
815     partopsep .initial:n = {#4},
816     partopsep .value_required:n = true,

```

```

817     parsep      .skip_set:c = { l__enumext_parsep_#2_skip },
818     parsep      .initial:n  = {#5},
819     parsep      .value_required:n = true,
820     itemsep     .skip_set:c = { l__enumext_itemsep_#2_skip },
821     itemsep     .initial:n  = {#6},
822     itemsep     .value_required:n = true,
823     noitemsep   .meta:n      = { itemsep = 0pt, parsep = 0pt },
824     noitemsep   .value_forbidden:n = true,
825     nosepe     .meta:n      = {
826                                     itemsep = 0pt, parsep= 0pt,
827                                     topsep = 0pt, partopsep = 0pt,
828                                     },
829     nosepe     .value_forbidden:n = true,
830   }
831 }

```

Now we set the values based on standard `article` class in `10pt`.

```

832 \__enumext_tmp:nnnnnn { level-1 } { i } { 8.0pt plus 2.0pt minus 4.0pt }
833   { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
834   { 4.0pt plus 2.0pt minus 1.0pt }
835 \__enumext_tmp:nnnnnn { level-2 } { ii } { 4.0pt plus 2.0pt minus 1.0pt }
836   { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
837   { 2.0pt plus 1.0pt minus 1.0pt }
838 \__enumext_tmp:nnnnnn { level-3 } { iii } { 2.0pt plus 1.0pt minus 1.0pt }
839   { 1.0pt minus 1.0pt } { 0pt } { 2.0pt plus 1.0pt minus 1.0pt }
840 \__enumext_tmp:nnnnnn { level-4 } { iv } { 2.0pt plus 1.0pt minus 1.0pt }
841   { 1.0pt minus 1.0pt } { 0pt } { 2.0pt plus 1.0pt minus 1.0pt }
842 \__enumext_tmp:nnnnnn { keyans } { v } { 4.0pt plus 2.0pt minus 1.0pt }
843   { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
844   { 2.0pt plus 1.0pt minus 1.0pt }
845 \__enumext_tmp:nnnnnn { enumext* } { vii } { 8.0pt plus 2.0pt minus 4.0pt }
846   { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
847   { 4.0pt plus 2.0pt minus 1.0pt }
848 \__enumext_tmp:nnnnnn { keyans* } { viii } { 4.0pt plus 2.0pt minus 1.0pt }
849   { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
850   { 2.0pt plus 1.0pt minus 1.0pt }

```

(End of definition for `topsep` and others.)

### 13.16 Setting base-fix key

When nesting starting right after `\item` (without material between them) there is a problem with the alignment of the *baseline* between the two environments. One way to get around this problem is to place `\mode_leave_vertical:` apply `\vspace{-\baselineskip}` and set `\topsep=0pt` for the “first level” of the nested `enumext` environment.

base-fix We define the key `base-fix` only for the “first level” of `enumext` environment.

```

\__enumext_nested_base_line_fix:
851 \keys_define:nn { enumext / level-1 }
852   {
853     base-fix .bool_set:N = \l__enumext_base_line_fix_bool,
854     base-fix .initial:n  = false,
855     base-fix .value_forbidden:n = true,
856   }

```

The function `\__enumext_nested_base_line_fix:` passed to the `\__enumext_parse_keys:n` function in the definition of the `enumext` environment (§13.38) will be responsible for applying the *baseline correction* and adjusting the *keys* for the `enumext` environment and the `\printkeyans` with *starred argument* ‘\*’ (§13.46).

We will first implement the function code from the user side of the `base-fix` key, that is, only the user knows when it is necessary to apply it within the document in which case the variable `\l__enumext_print_keyans_star_bool` set by the `\printkeyans` command is false and the variable `\l__enumext_base_line_fix_bool` is true.

```

857 \cs_new_protected:Nn \__enumext_nested_base_line_fix:
858   {
859     \bool_lazy_all:nT
860       {
861         { \bool_if_p:N \l__enumext_starred_first_bool }
862         { \bool_if_p:N \l__enumext_base_line_fix_bool }
863         { \bool_not_p:n { \l__enumext_print_keyans_star_bool } }
864       }
865     {
866       \mode_leave_vertical:

```

```

867     \vspace { -\dim_eval:n { \baselineskip + \parsep } }
868 }

```

When we are running the `\printkeyans` command with the *starred argument* ‘\*’ the variable `\l__enumext_print_keyans_star_bool` is true and we can run a simplified version of `\vspace` using `\skip_vertical:n`.

```

869 \bool_lazy_and:nnT
870 { \bool_if_p:N \l__enumext_starred_first_bool }
871 { \bool_if_p:N \l__enumext_print_keyans_star_bool }
872 {
873     \mode_leave_vertical:
874     \skip_vertical:n { -\baselineskip }
875     \skip_vertical:N \c_zero_skip
876 }

```

Finally we set the values of the keys `topsep`, `above` and `above*` for the “first level” of `enumext` environment equal to `0pt` and set the variable `\l__enumext_base_line_fix_bool` to false.

```

877 \keys_set:nn { enumext / level-1 }
878 {
879     topsep = 0pt, above = 0pt, above* = 0pt,
880 }
881 \bool_set_false:N \l__enumext_base_line_fix_bool
882 }

```

(End of definition for `base-fix` and `\l__enumext_nested_base_line_fix:`.)

### 13.17 Setting keys for horizontal spaces

Define and set `itemindent`, `rightmargin`, `listparindent`, `list-offset` and `list-indent` keys for `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```

itemindent 883 \cs_set_protected:Npn \l__enumext_tmp:nn #1 #2
rightmargin 884 {
listparindent 885     \keys_define:nn { enumext / #1 }
list-offset 886     {
list-indent 887         itemindent .dim_set:c = { \l__enumext_fake_item_indent_#2_dim },
888         itemindent .value_required:n = true,
889         rightmargin .dim_set:c = { \l__enumext_rightmargin_#2_dim },
890         rightmargin .value_required:n = true,
891         listparindent .dim_set:c = { \l__enumext_listparindent_#2_dim },
892         listparindent .value_required:n = true,
893         list-offset .dim_set:c = { \l__enumext_listoffset_#2_dim },
894         list-offset .value_required:n = true,
895         list-indent .code:n =
896             \bool_set_true:c { \l__enumext_leftmargin_tmp_#2_bool }
897             \dim_set:cn { \l__enumext_leftmargin_tmp_#2_dim } {##1},
898         list-indent .value_required:n = true,
899     }
900 }
901 \clist_map_inline:nn
902 {
903     {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {keyans}{v}
904 }
905 { \l__enumext_tmp:nn #1 }

```

(End of definition for `itemindent` and others.)

For `enumext*` and `keyans*` environments the situation is a bit different, the `list-indent` key behaves like the `list-offset` key.

```

906 \cs_set_protected:Npn \l__enumext_tmp:nn #1 #2
907 {
908     \keys_define:nn { enumext / #1 }
909     {
910         itemindent .dim_set:c = { \l__enumext_fake_item_indent_#2_dim },
911         itemindent .value_required:n = true,
912         rightmargin .dim_set:c = { \l__enumext_rightmargin_#2_dim },
913         rightmargin .value_required:n = true,
914         listparindent .dim_set:c = { \l__enumext_listparindent_#2_dim },
915         listparindent .value_required:n = true,
916         list-offset .dim_set:c = { \l__enumext_listoffset_#2_dim },
917         list-offset .value_required:n = true,
918         list-indent .meta:n = { list-offset = ##1 },
919         list-indent .value_required:n = true,
920     }

```



```

921   }
922   \clist_map_inline:nn
923   {
924     {enumext*}{vii}, {keyans*}{viii}
925   }
926   { \__enumext_tmp:nn #1 }

```

### 13.17.1 Functions for setting the fake itemindent

The `itemindent` key does not set the value of `\itemindent`, it only sets the value of the *horizontal space* applied using `\skip_horizontal:N`. We will store this value in the variable and only apply it when it is greater than `\opt`. Here I will need to place `\mode_leave_vertical:` and the plain TeX macro `\ignorespaces` to avoid unwanted extra space when using the `itemindent` key.

```

927 \cs_set_protected:Nn \__enumext_fake_item_indent:
928 {
929   \dim_compare:nNnT
930   { \dim_use:c { \__enumext_fake_item_indent_ \__enumext_level: _dim } }
931   >
932   { \c_zero_dim }
933   {
934     \tl_set:ce { \__enumext_fake_item_indent_ \__enumext_level: _tl }
935     {
936       \exp_not:N \mode_leave_vertical:
937       \exp_not:n { \skip_horizontal:n }
938       { \dim_use:c { \__enumext_fake_item_indent_ \__enumext_level: _dim } }
939       \exp_not:N \ignorespaces
940     }
941   }
942 }
943 \cs_set_protected:Nn \__enumext_keyans_fake_item_indent:
944 {
945   \dim_compare:nNnT
946   { \l__enumext_fake_item_indent_v_dim } > { \c_zero_dim }
947   {
948     \tl_set:Nc \l__enumext_fake_item_indent_v_tl
949     {
950       \exp_not:N \mode_leave_vertical:
951       \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_v_dim
952       \exp_not:N \ignorespaces
953     }
954   }
955 }
956 \cs_set_protected:Nn \__enumext_fake_item_indent_vii:
957 {
958   \dim_compare:nNnT
959   { \l__enumext_fake_item_indent_vii_dim } > { \c_zero_dim }
960   {
961     \tl_set:Nc \l__enumext_fake_item_indent_vii_tl
962     {
963       \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_vii_dim
964       \exp_not:N \ignorespaces
965     }
966   }
967 }
968 \cs_set_protected:Nn \__enumext_fake_item_indent_viii:
969 {
970   \dim_compare:nNnT
971   { \l__enumext_fake_item_indent_viii_dim } > { \c_zero_dim }
972   {
973     \tl_set:Nc \l__enumext_fake_item_indent_viii_tl
974     {
975       \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_viii_dim
976       \exp_not:N \ignorespaces
977     }
978   }
979 }

```

(End of definition for `\__enumext_fake_item_indent:` and others.)

### 13.18 Setting show-length key

show-length

Define and set `show-length` key for `enumext`, `enumext*`, `keyans` and `keyans*` environments. The function sets the boolean variable `\l__enumext_show_length_X_bool` used in the definition of all environments to

“true” and calls the function `\__enumext_show_length:nn` which prints all the values of the “vertical” and “horizontal” parameters calculated and used.

```

980 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
981 {
982   \keys_define:nn { enumext / #1 }
983   {
984     show-length .bool_set:c = { l__enumext_show_length_#2_bool },
985     show-length .initial:n = false,
986   }
987 }
988 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `show-length`.)

### 13.19 Setting before, after and first keys

Define and set `before`, `before*`, `after` and `first` keys for `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```

989 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
990 {
991   \keys_define:nn { enumext / #1 }
992   {
993     before .tl_set:c = { l__enumext_before_no_starred_key_#2_tl },
994     before .value_required:n = true,
995     before* .tl_set:c = { l__enumext_before_starred_key_#2_tl },
996     before* .value_required:n = true,
997     after .tl_set:c = { l__enumext_after_stop_list_#2_tl },
998     after .value_required:n = true,
999     first .tl_set:c = { l__enumext_after_list_args_#2_tl },
1000     first .value_required:n = true,
1001   }
1002 }
1003 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `before` and others.)

#### 13.19.1 Functions for before, after and first keys in enumext

The function `\__enumext_before_args_exec:` executes the `{\code}` set by the `before*` key “before” the `enumext` environment is started. The `{\code}` is executed “without” knowing any definition of the `{\arg two}` of the list: `{\code}\list{\arg one}{\arg two}`.

```

1004 \cs_new_protected:Nn \__enumext_before_args_exec:
1005 {
1006   \tl_use:c { l__enumext_before_starred_key_ \__enumext_level: _tl }
1007 }

```

The function `\__enumext_before_keys_exec:` executes the `{\code}` set by the `before` key “before” the `enumext` environment is started in *second argument* of the list. The `{\code}` is executed “knowing” all definition and values provides by `\keys: \list{\arg one}{\arg two}{\code}`.

```

1008 \cs_new_protected:Nn \__enumext_before_keys_exec:
1009 {
1010   \tl_use:c { l__enumext_before_no_starred_key_ \__enumext_level: _tl }
1011 }

```

The function `\__enumext_after_stop_list:` executes the `{\code}` set by the `after` key “after” the `enumext` environment has finished: `\endlist{\code}`.

```

1012 \cs_new_protected:Nn \__enumext_after_stop_list:
1013 {
1014   \tl_use:c { l__enumext_after_stop_list_ \__enumext_level: _tl }
1015 }

```

The function `\__enumext_after_args_exec:` executes the `{\code}` set by the `first` key after the end of the second argument of the list defining the `enumext` environment, just before the first occurrence of `\item: \list{\arg one}{\arg two}{\code}\item`.

```

1016 \cs_new_protected:Nn \__enumext_after_args_exec:
1017 {
1018   \tl_use:c { l__enumext_after_list_args_ \__enumext_level: _tl }
1019 }

```

(End of definition for `\__enumext_before_args_exec:` and others.)

### 13.19.2 Functions for before, after and first keys in keyans

Same implementation as the one used in the [enumext](#) environment.

```

__enumext_before_args_exec_v:
__enumext_before_keys_exec_v:
__enumext_after_stop_list_v:
__enumext_after_args_exec_v:
1020 \cs_new_protected:Nn __enumext_before_args_exec_v:
1021 {
1022   \tl_use:N \l__enumext_before_starred_key_v_tl
1023 }
1024 \cs_new_protected:Nn __enumext_before_keys_exec_v:
1025 {
1026   \tl_use:N \l__enumext_before_no_starred_key_v_tl
1027 }
1028 \cs_new_protected:Nn __enumext_after_stop_list_v:
1029 {
1030   \tl_use:N \l__enumext_after_stop_list_v_tl
1031 }
1032 \cs_new_protected:Nn __enumext_after_args_exec_v:
1033 {
1034   \tl_use:N \l__enumext_after_list_args_v_tl
1035 }

```

(End of definition for `\__enumext_before_args_exec_v:` and others.)

### 13.19.3 Functions for before, after and first keys in enumext\* and keyans\*

Same implementation as the one used in the [enumext](#) environment.

```

__enumext_before_args_exec_vii:
__enumext_before_keys_exec_vii
__enumext_after_stop_list_vii:
__enumext_after_args_exec_vii:
1036 \cs_new_protected:Nn __enumext_before_args_exec_vii:
1037 {
1038   \tl_use:N \l__enumext_before_starred_key_vii_tl
1039 }
1040 \cs_new_protected:Nn __enumext_before_args_exec_viii:
1041 {
1042   \tl_use:N \l__enumext_before_starred_key_viii_tl
1043 }
1044 \cs_new_protected:Nn __enumext_before_keys_exec_vii:
1045 {
1046   \tl_use:N \l__enumext_before_no_starred_key_vii_tl
1047 }
1048 \cs_new_protected:Nn __enumext_before_keys_exec_viii:
1049 {
1050   \tl_use:N \l__enumext_before_no_starred_key_viii_tl
1051 }
1052 \cs_new_protected:Nn __enumext_after_stop_list_vii:
1053 {
1054   \tl_use:N \l__enumext_after_stop_list_vii_tl
1055 }
1056 \cs_new_protected:Nn __enumext_after_stop_list_viii:
1057 {
1058   \tl_use:N \l__enumext_after_stop_list_viii_tl
1059 }
1060 \cs_new_protected:Nn __enumext_after_args_exec_vii:
1061 {
1062   \tl_use:N \l__enumext_after_list_args_vii_tl
1063 }
1064 \cs_new_protected:Nn __enumext_after_args_exec_viii:
1065 {
1066   \tl_use:N \l__enumext_after_list_args_viii_tl
1067 }

```

(End of definition for `\__enumext_before_args_exec_vii:` and others.)

## 13.20 Setting keys for multicols and minipage

The default value of the `columns-sep` key is handled by the state of the boolean variable `\l__enumext_columns_sep_X_bool` which is handled in the internal definition of the [enumext](#) and [keyans](#) environments. Define and set `mini-env`, `mini-sep`, `columns-sep` and `columns` keys for [enumext](#), [enumext\\*](#), [keyans](#) and [keyans\\*](#) environments.

```

1068 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
1069 {
1070   \keys_define:nn { enumext / #1 }
1071   {
1072     mini-env .dim_set:c = { l__enumext_minipage_right_#2_dim },
1073     mini-env .value_required:n = true,
1074     mini-sep .dim_set:c = { l__enumext_minipage_hsep_#2_dim },

```

```

1075     mini-sep .initial:n = 0.3333em,
1076     mini-sep .value_required:n = true,
1077     columns-sep .dim_set:c = { l__enumext_columns_sep_#2_dim },
1078     columns-sep .value_required:n = true,
1079     columns .int_set:c = { l__enumext_columns_#2_int },
1080     columns .initial:n = 1,
1081     columns .value_required:n = true,
1082   }
1083 }
1084 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

For `enumext*` and `keyans*` environments the situation is a bit different, the command `\miniright` is not available, so we will add the keys `mini-right` and `mini-right*` to implement support for `minipage` environment.

```

1085 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
1086 {
1087   \keys_define:nn { enumext / #1 }
1088   {
1089     mini-right .tl_gset:c = { g__enumext_miniright_code_#2_tl },
1090     mini-right .value_required:n = true,
1091     mini-right* .code:n = {
1092       \bool_gset_true:c { g__enumext_minipage_center_#2_bool }
1093       \keys_set:nn { enumext / #1 } { mini-right = {##1} }
1094     },
1095     mini-right* .value_required:n = true,
1096   }
1097 }
1098 \clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }

```

(End of definition for `mini-env` and others.)

### 13.21 Adjustment of vertical spaces for multicols

When nesting a “list environment” inside the `multicols` environment, the values of the “vertical spaces” are lost, basically the `multicols` environment takes control over them. Graphically it can be seen like in the figure 7.




Figure 7: Representation of the vertical space in `multicols` for a nested level.

To keep the desired spaces *above* and *below* in the “list environment” (`\topsep` + `[\partopsep]`) it is necessary to “adjust” the spaces added by the `multicols` environment. The most appropriate option in this case is to use a “context sensitive” vertical space with `\addvspace`.

🔗 I should make it clear that the implementation here is a “bit questionable”. At first glance doing `\multicolsep=\topsep` seemed right, but the results were not always as expected. An almost *imperceptible* detail is that in some cases the `\itemsep` values of are “stretched”, possibly due to the use of `\raggedcolumns` and this affects the lower space when closing the environment, which is “smaller” than expected. My attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

#### 13.21.1 Adjustment of vertical spaces for multicols in enumext

`\__enumext_multi_set_vskip:` The function `\__enumext_multi_set_vskip:` will take care of determining the “adjusted spaces” that we will apply “above” and “below” the `multicols` environment in `enumext`.

We will set the default values taking into account that  $\TeX$  is in *horizontal mode*, then we will make the settings for the *vertical mode* in which `\partopsep` comes into play.

Set the values of `\l__enumext_multicols_above_X_skip` and `\l__enumext_multicols_below_X_skip` equal to the value of `\topsep` in the *current level*.

```

1099 \cs_new_protected:Npn \__enumext_multi_set_vskip:
1100 {
1101   \skip_set:cn { l__enumext_multicols_above_ \__enumext_level: _skip }
1102   {
1103     \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
1104   }
1105   \skip_set:cn { l__enumext_multicols_below_ \__enumext_level: _skip }
1106   {
1107     \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
1108   }

```

```

1109   \__enumext_add_pre_parsep:
1110   }

```

(End of definition for \\_\_enumext\_multi\_set\_vskip:.)

\\_\_enumext\_add\_pre\_parsep: The function \\_\_enumext\_add\_pre\_parsep: “adjusted” the value of \l\_\_enumext\_multicols\_above\_X\_skip detecting the value of \parsep from the previous level. This is necessary since \parsep from the previous level affects the *vertical spaces*.

```

1111 \cs_new_protected:Nn \__enumext_add_pre_parsep:
1112 {
1113   \int_case:nn { \l__enumext_level_int }
1114   {
1115     { 2 }{
1116       \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip }
1117       {
1118         \skip_add:Nn \l__enumext_multicols_above_ii_skip
1119         {
1120           \l__enumext_parsep_i_skip
1121         }
1122       }
1123     }
1124     { 3 }{
1125       \skip_if_eq:nnF { \l__enumext_parsep_ii_skip } { \c_zero_skip }
1126       {
1127         \skip_add:Nn \l__enumext_multicols_above_iii_skip
1128         {
1129           \l__enumext_parsep_ii_skip
1130         }
1131       }
1132     }
1133     { 4 }{
1134       \skip_if_eq:nnF { \l__enumext_parsep_iii_skip } { \c_zero_skip }
1135       {
1136         \skip_add:Nn \l__enumext_multicols_above_iv_skip
1137         {
1138           \l__enumext_parsep_iii_skip
1139         }
1140       }
1141     }
1142   }
1143 }

```

(End of definition for \\_\_enumext\_add\_pre\_parsep:.)

\\_\_enumext\_multi\_addvspace: The function \\_\_enumext\_multi\_addvspace: will apply the spaces set using \addvspace “above” the multicols environment in enumext, taking into account whether TeX is in *horizontal mode* or *vertical mode*.

```

1144 \cs_new_protected:Nn \__enumext_multi_addvspace:
1145 {
1146   \__enumext_multi_set_vskip:
1147   \mode_if_vertical:T
1148   {
1149     \skip_add:cn { \l__enumext_multicols_above_ \l__enumext_level: _skip }
1150     {
1151       \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1152     }
1153     \skip_add:cn { \l__enumext_multicols_below_ \l__enumext_level: _skip }
1154     {
1155       \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1156     }
1157   }
1158   \par\nopagebreak
1159   \addvspace{ \skip_use:c { \l__enumext_multicols_above_ \l__enumext_level: _skip } }
1160 }

```

(End of definition for \\_\_enumext\_multi\_addvspace:.)

### 13.21.2 Adjustment of vertical spaces for multicols in keyans

`\__enumext_keyans_multi_set_vskip:`  
`\__enumext_keyans_multi_addvspace:`

The function `\__enumext_keyans_multi_set_vskip:` will take care of determining the “adjusted spaces” that we will apply “above” and “below” the `multicols` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

```

1161 \cs_new_protected:Nn \__enumext_keyans_multi_set_vskip:
1162 {
1163   \skip_set:Nn \l__enumext_multicols_above_v_skip
1164   {
1165     \l__enumext_topsep_v_skip
1166   }
1167   \skip_set:Nn \l__enumext_multicols_below_v_skip
1168   {
1169     \l__enumext_topsep_v_skip
1170   }
1171 }
1172 \cs_new_protected:Nn \__enumext_keyans_multi_addvspace:
1173 {
1174   \__enumext_keyans_multi_set_vskip:
1175   \mode_if_vertical:T
1176   {
1177     \skip_add:Nn \l__enumext_multicols_above_v_skip
1178     {
1179       \skip_use:N \l__enumext_partopsep_v_skip
1180     }
1181     \skip_add:Nn \l__enumext_multicols_below_v_skip
1182     {
1183       \skip_use:N \l__enumext_partopsep_v_skip
1184     }
1185   }
1186   \par\nopagebreak
1187   \addvspace{ \l__enumext_multicols_above_v_skip }
1188 }

```

(End of definition for `\__enumext_keyans_multi_set_vskip:` and `\__enumext_keyans_multi_addvspace:`.)

### 13.22 Adjustment of vertical spaces for minipage

When nesting a “list environment” within the `minipage` environment, the values of the “vertical spaces” are lost. Graphically it can be seen like in the figure 8.



Figure 8: Representation of the `minipage` spacing adjustment for a nested level.

Since we want to keep the “left” and “right” environments “aligned on top”, preserving the `\baselineskip` and keep the desired “spaces” (`\topsep` + `\partopsep`) it is necessary to “adjust” the “vertical spaces” for `minipage` environments.

Here there are several complications that we must circumvent, the `minipage` environment eliminates the “top” spaces, the `multicols` environment can be nested in the `minipage` environment, the “top” and “bottom” spaces are affected when `topsep=0pt` and to this is added the `\partopsep` parameter that comes into action according to whether  $\TeX$  is in *horizontal mode* or *vertical mode*. Depending on these cases, small adjustments must be made using `\vspace` and `\addvspace` to obtain the “desired vertical spacing”.

- Again I must make clear that the implementation here is a “bit questionable”, but hunting the spaces (glue) produced by the `minipage` environment is quite complicated, even more if `multicols` is nested. The setting of the values was more “trial and error” (aprox to `\strutbox`), using the help of the `lua-visual-debug`[14] package, again my attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

#### 13.22.1 Adjustment of vertical spaces for minipage in enumext

`\__enumext_minipage_set_skip:`  
`\__enumext_minipage_add_space:`

The function `\__enumext_minipage_set_skip:` will take care of determining the “adjust” spaces that we will apply “above” and “below” the `__enumext_mini_page` environment in `enumext`.

First we will set the value of `\l__enumext_minipage_right_skip` equal to `\topsep`, then we will see if  $\TeX$  is in *vertical mode* and we will add `\partopsep`, followed by that we set the value of `\l__enumext_minipage_after_skip`.

```

1189 \cs_new_protected:Nn \__enumext_minipage_set_skip:
1190 {
1191   \skip_set:Nn \l__enumext_minipage_right_skip

```



```

1192     {
1193       \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
1194     }
1195     \mode_if_vertical:T
1196     {
1197       \skip_add:Nn \l__enumext_minipage_right_skip
1198       {
1199         \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
1200       }
1201     }
1202     \skip_set_eq:NN \l__enumext_minipage_after_skip \l__enumext_minipage_right_skip

```

We will adjust the values `\l__enumext_multicols_above_X_skip` and `\l__enumext_multicols_below_X_skip` and call the function `\__enumext_pre_itemsep_skip:`.

```

1203     \skip_set_eq:cN
1204     { l__enumext_multicols_above_ \__enumext_level: _skip } \l__enumext_minipage_right_skip
1205     \skip_set_eq:cN
1206     { l__enumext_multicols_below_ \__enumext_level: _skip } \l__enumext_minipage_right_skip
1207     \__enumext_pre_itemsep_skip:

```

If the environment `multicols` is active, we set `\topskip=0pt` and then we make `\multicolsep` have the same value as `\l__enumext_multicols_above_X_skip`.

```

1208     \int_compare:nNnT
1209     { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
1210     {
1211       \skip_zero:N \topskip
1212       \skip_set_eq:Nc \multicolsep { l__enumext_multicols_above_ \__enumext_level: _skip }
1213     }
1214 }

```

The function `\__enumext_minipage_add_space:` will apply the spaces on the “left side” using `\addvspace` “above” the `\__enumext_mini_page` environment, taking into account whether  $\text{\TeX}$  is in  $\langle horizontal\ mode\rangle$  or  $\langle vertical\ mode\rangle$ . Here we use the plain  $\text{\TeX}$  macro `\nointerlineskip` to prevent baseline “glue” being added between the next pair of boxes in a *vertical list*. For the latter we will make some adjustments since the `\partopsep` parameter comes into play and this affects the *vertical spacing*.

```

1215 \cs_new_protected:Nn \__enumext_minipage_add_space:
1216 {
1217   \__enumext_minipage_set_skip:
1218   \__enumext_unskip_unkern:
1219   \mode_if_vertical:TF
1220   {
1221     \nopagebreak\nointerlineskip
1222   }
1223   {
1224     \par\nopagebreak\nointerlineskip
1225     \skip_zero:c { l__enumext_partopsep_ \__enumext_level: _skip }
1226   }
1227   \int_compare:nNnTF
1228   { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
1229   {
1230     \addvspace{ 0.445\box_ht:N \strutbox }
1231   }
1232   {
1233     \addvspace{ 0.250\box_ht:N \strutbox }
1234   }
1235 }

```

(End of definition for `\__enumext_minipage_set_skip:` and `\__enumext_minipage_add_space:`.)

`\__enumext_pre_itemsep_skip:` The function `\__enumext_pre_itemsep_skip:` will adjust the spaces below the environment `minipage` and the environment `multicols` if it is nested in it, taking into account the value of `\itemsep` from the previous level.

```

1236 \cs_new_protected:Nn \__enumext_pre_itemsep_skip:
1237 {
1238   \int_case:nn { \l__enumext_level_int }
1239   {
1240     { 2 }{
1241       \skip_if_eq:nnTF
1242       { \l__enumext_itemsep_i_skip } { \l__enumext_minipage_after_skip }
1243       {
1244         \skip_set:Nn \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1245         \skip_set:Nn \l__enumext_multicols_below_ii_skip { 0.350\box_ht:N \strutbox }

```

```

1246     }
1247     {
1248         \dim_compare:nNnT
1249         { \l__enumext_itemsep_i_skip } < { \l__enumext_minipage_after_skip }
1250         {
1251             \skip_sub:Nn
1252             \l__enumext_minipage_after_skip { \l__enumext_itemsep_i_skip }
1253             \skip_sub:Nn
1254             \l__enumext_multicols_below_ii_skip { \l__enumext_itemsep_i_skip }
1255             \skip_add:Nn
1256             \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1257             \skip_add:Nn
1258             \l__enumext_multicols_below_ii_skip { 0.350\box_ht:N \strutbox }
1259         }
1260         \dim_compare:nNnT
1261         { \l__enumext_itemsep_i_skip } > { \l__enumext_minipage_after_skip }
1262         {
1263             \skip_set:Nn \l__enumext_minipage_temp_skip
1264             {
1265                 \l__enumext_itemsep_i_skip - \l__enumext_minipage_after_skip
1266             }
1267             \skip_sub:Nn
1268             \l__enumext_minipage_after_skip { \l__enumext_itemsep_i_skip }
1269             \skip_sub:Nn
1270             \l__enumext_multicols_below_ii_skip { \l__enumext_itemsep_i_skip }
1271             \skip_add:Nn
1272             \l__enumext_minipage_after_skip
1273             { 0.150\box_ht:N \strutbox + \l__enumext_minipage_temp_skip }
1274             \skip_add:Nn
1275             \l__enumext_multicols_below_ii_skip
1276             { 0.350\box_ht:N \strutbox + \l__enumext_minipage_temp_skip }
1277         }
1278     }
1279 }
1280 { 3 }{
1281     \skip_if_eq:nnTF
1282     { \l__enumext_itemsep_ii_skip } { \c_zero_skip }
1283     {
1284         \skip_set:Nn \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1285         \skip_set:Nn \l__enumext_multicols_below_iii_skip { 0.350\box_ht:N \strutbox }
1286     }
1287     {
1288         \dim_compare:nNnT
1289         { \l__enumext_itemsep_ii_skip } < { \l__enumext_minipage_after_skip }
1290         {
1291             \skip_sub:Nn
1292             \l__enumext_minipage_after_skip { \l__enumext_itemsep_ii_skip }
1293             \skip_sub:Nn
1294             \l__enumext_multicols_below_iii_skip { \l__enumext_itemsep_ii_skip }
1295             \skip_add:Nn
1296             \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1297             \skip_add:Nn
1298             \l__enumext_multicols_below_iii_skip { 0.350\box_ht:N \strutbox }
1299         }
1300         \dim_compare:nNnT
1301         { \l__enumext_itemsep_ii_skip } > { \l__enumext_minipage_after_skip }
1302         {
1303             \skip_set:Nn \l__enumext_minipage_temp_skip
1304             {
1305                 \l__enumext_itemsep_ii_skip - \l__enumext_minipage_after_skip
1306             }
1307             \skip_sub:Nn
1308             \l__enumext_minipage_after_skip { \l__enumext_itemsep_ii_skip }
1309             \skip_sub:Nn
1310             \l__enumext_multicols_below_iii_skip { \l__enumext_itemsep_ii_skip }
1311             \skip_add:Nn
1312             \l__enumext_minipage_after_skip
1313             { 0.150\box_ht:N \strutbox + \l__enumext_minipage_temp_skip }
1314             \skip_add:Nn
1315             \l__enumext_multicols_below_iii_skip
1316             { 0.350\box_ht:N \strutbox + \l__enumext_minipage_temp_skip }

```

```

1317     }
1318   }
1319 }
1320 { 4 }{
1321   \skip_if_eq:nnTF { \l__enumext_itemsep_iii_skip } { \c_zero_skip }
1322   {
1323     \skip_set:Nn \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1324     \skip_set:Nn \l__enumext_multicols_below_iv_skip { 0.350\box_ht:N \strutbox }
1325   }
1326   {
1327     \dim_compare:nNnT
1328     { \l__enumext_itemsep_iii_skip } < { \l__enumext_minipage_after_skip }
1329     {
1330       \skip_sub:Nn
1331       \l__enumext_minipage_after_skip { \l__enumext_itemsep_iii_skip }
1332       \skip_sub:Nn
1333       \l__enumext_multicols_below_iv_skip { \l__enumext_itemsep_iii_skip }
1334       \skip_add:Nn
1335       \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1336       \skip_add:Nn
1337       \l__enumext_multicols_below_iv_skip { 0.350\box_ht:N \strutbox }
1338     }
1339     \dim_compare:nNnT
1340     { \l__enumext_itemsep_iii_skip } > { \l__enumext_minipage_after_skip }
1341     {
1342       \skip_set:Nn \l__enumext_minipage_temp_skip
1343       {
1344         \l__enumext_itemsep_iii_skip - \l__enumext_minipage_after_skip
1345       }
1346       \skip_sub:Nn
1347       \l__enumext_minipage_after_skip { \l__enumext_itemsep_iii_skip }
1348       \skip_sub:Nn
1349       \l__enumext_multicols_below_iv_skip { \l__enumext_itemsep_iii_skip }
1350       \skip_add:Nn
1351       \l__enumext_minipage_after_skip
1352       { 0.150\box_ht:N \strutbox + \l__enumext_minipage_temp_skip }
1353       \skip_add:Nn
1354       \l__enumext_multicols_below_iv_skip
1355       { 0.350\box_ht:N \strutbox + \l__enumext_minipage_temp_skip }
1356     }
1357   }
1358 }
1359 }
1360 }

```

(End of definition for `\__enumext_pre_itemsep_skip`.)

### 13.22.2 Adjustment of vertical spaces for minipage in keyans

```

\__enumext_keyans_minipage_set_skip:
\__enumext_keyans_minipage_add_space:
\__enumext_keyans_pre_itemsep_skip:

```

The function `\__enumext_keyans_mini_set_vskip:` will take care of determining the “adjusted” spaces that we will apply “*above*” and “*below*” the `\__enumext_mini_page` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

```

1361 \cs_new_protected:Nn \__enumext_keyans_minipage_set_skip:
1362 {
1363   \skip_zero:N \l__enumext_minipage_after_skip
1364   \skip_zero:N \l__enumext_minipage_left_skip
1365   \skip_zero:N \l__enumext_minipage_right_skip
1366   \skip_set:Nn \l__enumext_minipage_right_skip
1367   {
1368     \l__enumext_topsep_v_skip
1369   }
1370   \mode_if_vertical:T
1371   {
1372     \skip_add:Nn \l__enumext_minipage_right_skip
1373     {
1374       \l__enumext_partopsep_v_skip
1375     }
1376   }
1377   \skip_set_eq:NN \l__enumext_minipage_after_skip \l__enumext_minipage_right_skip
1378   \skip_set_eq:NN \l__enumext_multicols_above_v_skip \l__enumext_minipage_right_skip
1379   \skip_set_eq:NN \l__enumext_multicols_below_v_skip \l__enumext_minipage_right_skip
1380   \__enumext_keyans_pre_itemsep_skip:

```

```

1381 \int_compare:nNt { \__enumext_columns_v_int } > { 1 }
1382 {
1383   \skip_zero:N \topskip
1384   \skip_set_eq:NN \multicolsep \__enumext_minipage_right_skip
1385 }
1386 }
1387 \cs_new_protected:Nn \__enumext_keyans_minipage_add_space:
1388 {
1389   \__enumext_keyans_minipage_set_skip:
1390   \__enumext_unskip_unkern:
1391   \mode_if_vertical:TF
1392   {
1393     \nopagebreak\nointerlineskip
1394   }
1395   {
1396     \par\nopagebreak\nointerlineskip
1397     \skip_zero:N \__enumext_partopsep_v_skip
1398   }
1399   \int_compare:nNtTF { \__enumext_columns_v_int } > { 1 }
1400   {
1401     \addvspace{ 0.445\box_ht:N \strutbox }
1402   }
1403   {
1404     \addvspace{ 0.250\box_ht:N \strutbox }
1405   }
1406 }
1407 \cs_new_protected:Nn \__enumext_keyans_pre_itemsep_skip:
1408 {
1409   \skip_if_eq:nnTF
1410   { \__enumext_itemsep_i_skip } { \__enumext_minipage_after_skip }
1411   {
1412     \skip_set:Nn \__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1413     \skip_set:Nn \__enumext_multicols_below_v_skip { 0.350\box_ht:N \strutbox }
1414   }
1415   {
1416     \dim_compare:nNt
1417     { \__enumext_itemsep_i_skip } < { \__enumext_minipage_after_skip }
1418     {
1419       \skip_sub:Nn \__enumext_minipage_after_skip { \__enumext_itemsep_i_skip }
1420       \skip_sub:Nn \__enumext_multicols_below_v_skip { \__enumext_itemsep_i_skip }
1421       \skip_add:Nn \__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1422       \skip_add:Nn \__enumext_multicols_below_v_skip { 0.350\box_ht:N \strutbox }
1423     }
1424     \dim_compare:nNt
1425     { \__enumext_itemsep_i_skip } > { \__enumext_minipage_after_skip }
1426     {
1427       \skip_set:Nn \__enumext_minipage_temp_skip
1428       {
1429         \__enumext_itemsep_i_skip - \__enumext_minipage_after_skip
1430       }
1431       \skip_sub:Nn \__enumext_minipage_after_skip { \__enumext_itemsep_i_skip }
1432       \skip_sub:Nn \__enumext_multicols_below_v_skip { \__enumext_itemsep_i_skip }
1433       \skip_add:Nn \__enumext_minipage_after_skip
1434       { 0.150\box_ht:N \strutbox + \__enumext_minipage_temp_skip }
1435       \skip_add:Nn \__enumext_multicols_below_v_skip
1436       { 0.350\box_ht:N \strutbox + \__enumext_minipage_temp_skip }
1437     }
1438   }
1439 }

```

(End of definition for `\__enumext_keyans_minipage_set_skip:`, `\__enumext_keyans_minipage_add_space:`, and `\__enumext_keyans_pre_itemsep_skip:`.)

### 13.22.3 Adjustment of vertical spaces for minipage in enumext\* and keyans\*

`\__enumext_mini_set_vskip_vii:`  
`\__enumext_mini_set_vskip_viii:`

The functions `\__enumext_mini_set_vskip_vii:` and `\__enumext_mini_set_vskip_viii:` will take care of determining the “adjusted” spaces that we will apply “above” and “below” the `\__enumext_mini_page` environment in `enumext*` and `keyans*`.

```

1440 \cs_new_protected:Nn \__enumext_mini_set_vskip_vii:
1441 {
1442   \skip_zero_new:N \__enumext_minipage_left_skip
1443   \skip_gzero_new:N \__enumext_minipage_right_skip

```

```

1444 \skip_gzero_new:N \g__enumext_minipage_after_skip
1445 \skip_if_eq:nnTF { \l__enumext_topsep_vii_skip } { \c_zero_skip }
1446 {
1447   \skip_set:Nn \l__enumext_minipage_left_skip { 0.5\box_dp:N \strutbox }
1448   \skip_gset:Nn \g__enumext_minipage_right_skip { 0.325\box_dp:N \strutbox }
1449 }
1450 {
1451   \skip_set:Nn \l__enumext_minipage_left_skip { 0.5875\box_dp:N \strutbox }
1452   \skip_gset:Nn \g__enumext_minipage_right_skip
1453   {
1454     \l__enumext_topsep_vii_skip
1455   }
1456   \skip_gset:Nn \g__enumext_minipage_after_skip
1457   {
1458     0.325\box_dp:N \strutbox + \l__enumext_topsep_vii_skip
1459   }
1460 }
1461 }
1462 \cs_new_protected:Nn \__enumext_mini_set_vskip_viii:
1463 {
1464   \skip_zero_new:N \l__enumext_minipage_after_skip
1465   \skip_zero_new:N \l__enumext_minipage_left_skip
1466   \skip_zero_new:N \l__enumext_minipage_right_skip
1467   \skip_if_eq:nnTF { \l__enumext_topsep_viii_skip } { \c_zero_skip }
1468   {
1469     \skip_set:Nn \l__enumext_minipage_left_skip
1470     {
1471       0.5\box_dp:N \strutbox
1472     }
1473     \skip_set:Nn \l__enumext_minipage_right_skip
1474     {
1475       \l__enumext_partopsep_viii_skip
1476     }
1477     \skip_set:Nn \l__enumext_minipage_after_skip
1478     {
1479       1.6\box_dp:N \strutbox
1480     }
1481   }
1482   {
1483     \skip_set:Nn \l__enumext_minipage_left_skip
1484     {
1485       0.5875\box_dp:N \strutbox
1486     }
1487     \skip_set:Nn \l__enumext_minipage_right_skip
1488     {
1489       \l__enumext_topsep_viii_skip
1490     }
1491     \skip_set:Nn \l__enumext_minipage_after_skip
1492     {
1493       0.325\box_dp:N \strutbox + \l__enumext_topsep_viii_skip
1494     }
1495   }
1496 }

```

(End of definition for `\__enumext_mini_set_vskip_vii:` and `\__enumext_mini_set_vskip_viii:`)

`\__enumext_mini_addvspace_vii:`  
`\__enumext_mini_addvspace_viii:`

The functions `\__enumext_mini_addvspace_vii:` and `\__enumext_mini_addvspace_viii:` will apply the vertical space “only above” the `\__enumext_mini_page` environment on the *left side* when the *mini-right* key is active in the `enumext*` and `keyans*` environments.

Here we will NOT take into account whether TeX is in *horizontal mode* or *vertical mode*, since `\partopsep` is equal to `0pt` in both environments.

```

1497 \cs_new_protected:Nn \__enumext_mini_addvspace_vii:
1498 {
1499   \__enumext_mini_set_vskip_vii:
1500   \par\nopagebreak
1501   \addvspace { \l__enumext_minipage_left_skip }
1502 }
1503 \cs_new_protected:Nn \__enumext_mini_addvspace_viii:
1504 {
1505   \__enumext_mini_set_vskip_viii:
1506   \par\nopagebreak

```

```

1507 \addvspace { \l__enumext_minipage_left_skip }
1508 }

```

(End of definition for \l\_\_enumext\_mini\_addvspace\_vii: and \l\_\_enumext\_mini\_addvspace\_viii:.)

### 13.22.4 The command \miniright

The command `\miniright` will close the `__enumext_mini_page` environment on the “left side”, open the `__enumext_mini_page` environment on the “right side” adding the *adjusted vertical space*. By default we will add `\centering` when starting the “right side” environment. The *starred argument* ‘\*’ inhibits the use of `\centering` command i.e. the usual  $\text{\LaTeX}$  justification is maintained in the `__enumext_mini_page` on the “right side”.

`\miniright` First we will perform some checks to prevent the command from being executed outside the `enumext` environment or somewhere inappropriate then we will call the internal functions to execute it in the `enumext` and `keyans` environments.

```

1509 \NewDocumentCommand \miniright { s }
1510 {
1511   \int_compare:nNt { \l__enumext_keyans_pic_level_int } = { 1 }
1512   {
1513     \msg_error:nnn { enumext } { wrong-miniright-place }
1514   }
1515   % outside
1516   \bool_lazy_and:nnT
1517   { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
1518   { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
1519   {
1520     \msg_error:nnn { enumext } { wrong-miniright-place }
1521   }
1522   % starred env
1523   \bool_if:NT \l__enumext_starred_bool
1524   {
1525     \msg_error:nnn { enumext } { wrong-miniright-starred }
1526   }
1527   \int_compare:nNtF { \l__enumext_keyans_level_int } = { 1 }
1528   {
1529     __enumext_keyans_mini_right_cmd:n {#1}
1530   }
1531   { __enumext_mini_right_cmd:n {#1} }
1532 }

```

(End of definition for \miniright. This function is documented on page 10.)

`__enumext_mini_right_cmd:n` The function `__enumext_mini_right_cmd:n` takes as argument the *starred* ‘\*’ of the `\miniright` command in the `enumext` environment. We check if the `mini-env` key is active via the variable `\l__enumext_minipage_right_X_dim`, if so we close the `multicols` environment with the `__enumext_mini_page` environment on the “left side”, then we open the `__enumext_mini_page` environment on the “right side”, apply our adjusted “vertical spaces”, followed by adding the `\centering` command when the *starred argument* ‘\*’ is not present and set zero `\g__enumext_minipage_stat_int`, otherwise we return an error.

```

1533 \cs_new_protected:Npn \__enumext_mini_right_cmd:n #1
1534 {
1535   \dim_compare:nNtF
1536   { \dim_use:c { \l__enumext_minipage_right_ \l__enumext_level: _dim } } > { \c_zero_dim }
1537   {
1538     __enumext_multicols_stop:
1539     \int_compare:nNtF
1540     { \int_use:c { \l__enumext_columns_ \l__enumext_level: _int } } = { 1 }
1541     {
1542       \par\addvspace{ \l__enumext_minipage_after_skip }
1543     }
1544     \end__enumext_mini_page
1545     \hfill
1546     __enumext_mini_page{ \dim_use:c { \l__enumext_minipage_right_ \l__enumext_level: _dim } }
1547     \par\nointerlineskip
1548     \addvspace { \l__enumext_minipage_right_skip }
1549     \bool_if:nF {#1}
1550     {
1551       \centering
1552     }
1553     \int_gzero:N \g__enumext_minipage_stat_int
1554   }

```

```

1555     { \msg_error:nnn { enumext } { wrong-miniright-use } }
1556 % paranoia
1557 \RenewDocumentCommand \miniright { s }
1558 {
1559     \msg_error:nn { enumext } { many-miniright-used }
1560 }
1561 }

```

(End of definition for `\__enumext_mini_right_cmd:n`.)

`\__enumext_keyans_mini_right_cmd:n`

The function `\__enumext_keyans_mini_right_cmd:n` takes as argument the *starred* ‘`*`’ of the `\miniright` command in the `keyans` environment. The implementation of this function is the same as that of the `\__enumext_mini_right_cmd:n` function of the `enumext` environment.

```

1562 \cs_new_protected:Npn \__enumext_keyans_mini_right_cmd:n #1
1563 {
1564     \dim_compare:nNnTF { \__enumext_minipage_right_v_dim } > { \c_zero_dim }
1565     {
1566         \__enumext_keyans_multicols_stop:
1567         \int_compare:nNnT { \__enumext_columns_v_int } = { 1 }
1568         {
1569             \par\addvspace{ \__enumext_minipage_after_skip }
1570         }
1571         \end__enumext_mini_page
1572         \hfill
1573         \__enumext_mini_page{ \__enumext_minipage_right_v_dim }
1574         \par\nointerlineskip
1575         \addvspace { \__enumext_minipage_right_skip }
1576         \bool_if:nF {#1}
1577         {
1578             \centering
1579         }
1580         \int_gzero:N \g__enumext_minipage_stat_int
1581     }
1582     { \msg_error:nnn { enumext } { wrong-miniright-use } }
1583 % paranoia
1584 \RenewDocumentCommand \miniright { s }
1585 {
1586     \msg_error:nn { enumext } { many-miniright-used }
1587 }
1588 }

```

(End of definition for `\__enumext_keyans_mini_right_cmd:n`.)

### 13.23 Setting above and below keys

While having controlled the *vertical spaces* within the `enumext` and `keyans` environments when using the `columns` or `mini-env` keys, sometimes the “*vertical spaces above*” or “*vertical spaces below*” the environments are not as expected and it is necessary to be able to apply a “*fine correction*” to these. As I have not been able to correct these *glitches*, the best option is to leave a couple of *keys* dedicated to this purpose, in this case it is best to use `\vspace` or `\vspace*` when convenient.

Define `above`, `above*`, `below` and `below*` keys for `enumext` and `keyans` environments.

```

1589 \cs_set_protected:Npn \__enumext_tmp:n #1 #2
1590 {
1591     \keys_define:nn { enumext / #1 }
1592     {
1593         above .skip_set:c = { \__enumext_vspace_above_#2_skip },
1594         above .value_required:n = true,
1595         above* .code:n = \bool_set_true:c { \__enumext_vspace_a_star_#2_bool }
1596             \keys_set:nn { enumext / #1 } { above = {##1} },
1597         above* .value_required:n = true,
1598         below .skip_set:c = { \__enumext_vspace_below_#2_skip },
1599         below .value_required:n = true,
1600         below* .code:n = \bool_set_true:c { \__enumext_vspace_b_star_#2_bool }
1601             \keys_set:nn { enumext / #1 } { below = {##1} },
1602         below* .value_required:n = true,
1603     }
1604 }
1605 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:n #1 }

```

(End of definition for `above` and others.)



### 13.23.1 Functions for above and below keys in enumext

`\__enumext_vspace_above:` The function `\__enumext_vspace_above:` apply the *vertical space above* the `enumext` environment set by the `above*` and `above` keys.

```

1606 \cs_new_protected:Nn \__enumext_vspace_above:
1607 {
1608   \skip_if_eq:nnF
1609   { \skip_use:c { \__enumext_vspace_above_ \__enumext_level: _skip } } { \c_zero_skip }
1610   {
1611     \bool_if:cTF { \__enumext_vspace_a_star_ \__enumext_level: _bool }
1612     {
1613       \vspace*{ \skip_use:c { \__enumext_vspace_above_ \__enumext_level: _skip } }
1614     }
1615     {
1616       \vspace { \skip_use:c { \__enumext_vspace_above_ \__enumext_level: _skip } }
1617     }
1618   }
1619 }

```

(End of definition for `\__enumext_vspace_above:`.)

`\__enumext_vspace_below:` The function `\__enumext_vspace_below:` apply the *vertical space below* the `enumext` environment set by the `below*` and `below` keys.

```

1620 \cs_new_protected:Nn \__enumext_vspace_below:
1621 {
1622   \skip_if_eq:nnF
1623   { \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } } { \c_zero_skip }
1624   {
1625     \bool_if:cTF { \__enumext_vspace_b_star_ \__enumext_level: _bool }
1626     {
1627       \vspace*{ \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } }
1628     }
1629     {
1630       \vspace { \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } }
1631     }
1632   }
1633 }

```

(End of definition for `\__enumext_vspace_below:`.)

### 13.23.2 Functions for above and below keys in keyans

`\__enumext_vspace_above_v:` The function `\__enumext_vspace_above_v:` apply the *vertical space above* the `keyans` environment set by the `above` and `above*` keys.

```

1634 \cs_new_protected:Nn \__enumext_vspace_above_v:
1635 {
1636   \skip_if_eq:nnF { \l__enumext_vspace_above_v_skip } { \c_zero_skip }
1637   {
1638     \bool_if:NTF \l__enumext_vspace_a_star_v_bool
1639     {
1640       \vspace*{ \l__enumext_vspace_above_v_skip }
1641     }
1642     { \vspace { \l__enumext_vspace_above_v_skip } }
1643   }
1644 }

```

(End of definition for `\__enumext_vspace_above_v:`.)

`\__enumext_vspace_below_v:` The function `\__enumext_vspace_below_v:` apply the *vertical space below* the `keyans` environment set by the `below*` and `below` keys.

```

1645 \cs_new_protected:Nn \__enumext_vspace_below_v:
1646 {
1647   \skip_if_eq:nnF { \l__enumext_vspace_below_v_skip } { \c_zero_skip }
1648   {
1649     \bool_if:NTF \l__enumext_vspace_b_star_v_bool
1650     {
1651       \vspace*{ \l__enumext_vspace_below_v_skip }
1652     }
1653     { \vspace { \l__enumext_vspace_below_v_skip } }
1654   }
1655 }

```

(End of definition for `\__enumext_vspace_below_v:`.)

### 13.23.3 Functions for above and below keys in enumext\* keyans\*

The functions `\__enumext_vspace_above_vii:` and `\__enumext_vspace_above_viii:` apply the *vertical space above* the `enumext*` and `keyans*` environments set by the `above` and `above*` keys.

```

1656 \cs_new_protected:Nn \__enumext_vspace_above_vii:
1657 {
1658   \skip_if_eq:nnF { \l__enumext_vspace_above_vii_skip } { \c_zero_skip }
1659   {
1660     \bool_if:NTF \l__enumext_vspace_a_star_vii_bool
1661     {
1662       \vspace*{ \l__enumext_vspace_above_vii_skip }
1663     }
1664     { \vspace { \l__enumext_vspace_above_vii_skip } }
1665   }
1666 }
1667 \cs_new_protected:Nn \__enumext_vspace_above_viii:
1668 {
1669   \skip_if_eq:nnF { \l__enumext_vspace_above_viii_skip } { \c_zero_skip }
1670   {
1671     \bool_if:NTF \l__enumext_vspace_a_star_viii_bool
1672     {
1673       \vspace*{ \l__enumext_vspace_above_viii_skip }
1674     }
1675     { \vspace { \l__enumext_vspace_above_viii_skip } }
1676   }
1677 }

```

(End of definition for `\__enumext_vspace_above_vii:` and `\__enumext_vspace_above_viii:`.)

The functions `\__enumext_vspace_below_vii:` and `\__enumext_vspace_below_viii:` apply the *vertical space below* the `enumext*` and `keyans*` environments set by the `below` and `below` keys.

```

1678 \cs_new_protected:Nn \__enumext_vspace_below_vii:
1679 {
1680   \skip_if_eq:nnF { \l__enumext_vspace_below_vii_skip } { \c_zero_skip }
1681   {
1682     \bool_if:NTF \l__enumext_vspace_b_star_vii_bool
1683     {
1684       \vspace*{ \l__enumext_vspace_below_vii_skip }
1685     }
1686     { \vspace { \l__enumext_vspace_below_vii_skip } }
1687   }
1688 }
1689 \cs_new_protected:Nn \__enumext_vspace_below_viii:
1690 {
1691   \skip_if_eq:nnF { \l__enumext_vspace_below_viii_skip } { \c_zero_skip }
1692   {
1693     \bool_if:NTF \l__enumext_vspace_b_star_viii_bool
1694     {
1695       \vspace*{ \l__enumext_vspace_below_viii_skip }
1696     }
1697     { \vspace { \l__enumext_vspace_below_viii_skip } }
1698   }
1699 }

```

(End of definition for `\__enumext_vspace_below_vii:` and `\__enumext_vspace_below_viii:`.)

### 13.24 Setting series, resume and resume\* keys

The `series` key is responsible for the whole process of the `resume` and `resume*` keys. The idea behind this is to be able to absorb the  $\langle keys \rangle$  passed to the *optional argument* of the “first level” of the environments `enumext` and `enumext*`, but, discarding some specific  $\langle keys \rangle$ . This implementation is adapted directly from the code provided by Jonathan P. Spratte (@Skillmon) in `chat-Tex-SX`

We define the keys `series`, `resume` and `resume*` only for the “first level” of `enumext` and `enumext*`.

```

series
resume
resume*
1700 \cs_set_protected:Npn \__enumext_tmp:n #1
1701 {
1702   \keys_define:nn { enumext / #1 }
1703   {
1704     series .str_set:N = \l__enumext_series_str,
1705     series .value_required:n = true,
1706     resume .code:n = \__enumext_resume_series:n {##1},
1707     resume* .code:n = \__enumext_resume_starred:,

```

```

1708         resume* .value_forbidden:n = true,
1709     }
1710 }
1711 \clist_map_inline:nn { level-1, enumext* } { \__enumext_tmp:n {#1} }

```

(End of definition for `series`, `resume`, and `resume*`.)

### 13.24.1 Internal functions for series key

The function `\__enumext_filter_series:n` will be in charge of filtering the *⟨keys⟩* we want to store where *{#1}* represents the *optional argument* passed to the environment.

```

\__enumext_filter_series:n
  \__enumext_filter_series_key:n
  \__enumext_filter_series_pair:nn
1712 \cs_new:Npn \__enumext_filter_series:n #1
1713 {
1714     \use:e
1715     {
1716         \keyval_parse:NNn
1717         \__enumext_filter_series_key:n
1718         \__enumext_filter_series_pair:nn {#1}
1719     }
1720 }

```

The function `\__enumext_filter_series_key:n` will be responsible for filtering the *⟨keys⟩* that are passed “without value” by excluding the `resume`, `resume*` and `base-fix` keys.

```

1721 \cs_new:Npn \__enumext_filter_series_key:n #1
1722 {
1723     \str_case:nnF {#1}
1724     {
1725         { resume } {} { resume* } {} { base-fix } {}
1726     }
1727     { , { \exp_not:n {#1} } }
1728 }

```

The function `\__enumext_filter_series_pair:nn` will be responsible for filtering the *⟨keys⟩* that are passed “with value” by excluding the `series`, `resume`, `start`, `start*`, `save-ans` and `save-key` keys.

```

1729 \cs_new:Npn \__enumext_filter_series_pair:nn #1#2
1730 {
1731     \str_case:nnF {#1}
1732     {
1733         { series } {} { resume } {} { start } {}
1734         { start* } {} { save-ans } {} { save-key } {}
1735     }
1736     { , { \exp_not:n {#1} } } = { \exp_not:n {#2} } }
1737 }

```

(End of definition for `\__enumext_filter_series:n`, `\__enumext_filter_series_key:n`, and `\__enumext_filter_series_pair:nn`.)

The function `\__enumext_parse_series:n` will be responsible for storing the filtered *⟨keys⟩* in the global variable `\g__enumext_series_⟨series name⟩_tl` along with the creation of the integer variable `\g__enumext_series_⟨series name⟩_int` when the key is passed as an argument; otherwise, it will check the state of the boolean variable `\l__enumext_resume_active_bool` set by the keys `resume` and `resume*` and will call the function `\__enumext_resume_last:n`.

🔴 The value of boolean variable `\l__enumext_resume_active_bool` is set to true by the function `\__enumext_resume_counter:n` which is used by the keys `resume` and `resume*`, in this case we must Make sure it is set to false so that it does not overwrite the default filtered *⟨keys⟩*. This function is passed to the function `\__enumext_parse_keys:n` in the `enumext` environment definition (§13.38) and to the function `\__enumext_parse_keys_vii:n` in the `enumext*` environment definition (§13.43).

```

1738 \cs_new_protected:Npn \__enumext_parse_series:n #1
1739 {
1740     \str_if_empty:NTF \l__enumext_series_str
1741     {
1742         \bool_if:NF \l__enumext_resume_active_bool
1743         {
1744             \__enumext_resume_last:n {#1}
1745         }
1746     }
1747     {
1748         \tl_gclear_new:c { g__enumext_series_ \l__enumext_series_str _tl }
1749         \tl_gset:ce { g__enumext_series_ \l__enumext_series_str _tl }
1750         { \__enumext_filter_series:n {#1} }
1751         \int_if_exist:cF { g__enumext_series_ \l__enumext_series_str _int }
1752         {

```

```

1753         \int_new:c { g__enumext_series_ \l__enumext_series_str _int }
1754     }
1755 }
1756 }

```

The function `\__enumext_resume_last:n` will be in charge of saving the filtering (*keys*) when the *series* key is *not used* and will save them in the variable `\g__enumext_standar_series_tl` for the *enumext* environment and in the variable `\g__enumext_starred_series_tl` for the *enumext\** environment.

```

1757 \cs_new_protected:Npn \__enumext_resume_last:n #1
1758 {
1759     \bool_if:NT \l__enumext_standar_first_bool
1760     {
1761         \tl_gclear:N \g__enumext_standar_series_tl
1762         \tl_gset:Ne \g__enumext_standar_series_tl { \__enumext_filter_series:n {#1} }
1763     }
1764     \bool_if:NT \l__enumext_starred_first_bool
1765     {
1766         \tl_gclear:N \g__enumext_starred_series_tl
1767         \tl_gset:Ne \g__enumext_starred_series_tl { \__enumext_filter_series:n {#1} }
1768     }
1769 }

```

(End of definition for `\__enumext_parse_series:n` and `\__enumext_resume_last:n`)

### 13.24.2 Internal function to save counter value

`\__enumext_resume_save_counter:` The `\__enumext_resume_save_counter:` function will save the last counter value to `\g__enumext_series_⟨series name⟩_int` if the *series*={⟨series name⟩} key has been passed, to `\g__enumext_resume_⟨series name⟩_int` if it has passed the key *resume without value* and the key *series* is not active, in `\g__enumext_series_⟨series name⟩_int` if the key *resume*={⟨series name⟩} has been passed and in `\g__enumext_series_⟨store name⟩_int` if the key has been passed *save-ans*={⟨store name⟩}.

The variables `\l__enumext_series_str` and `\l__enumext__resume_name_tl` contain the same {⟨series name⟩} but are executed at different moments, the integer variable with `\l__enumext_series_str` sets the value when execute *series*={⟨series name⟩} and the integer variable with `\l__enumext__resume_name_tl` sets the subsequent values when use *resume*={⟨series name⟩}. This function is passed to the *enumext* environment definition (§13.38) and the *enumext\** environment definition (§13.43).

```

1770 \cs_new_protected:Npn \__enumext_resume_save_counter:
1771 {
1772     \bool_if:NT \g__enumext_standar_bool
1773     {
1774         \tl_if_empty:NF \l__enumext_series_str
1775         {
1776             \int_gset_eq:cN
1777             { g__enumext_series_ \l__enumext_series_str _int } \value{enumXi}
1778         }
1779         \tl_if_empty:NTF \l__enumext_resume_name_tl
1780         {
1781             \str_if_empty:NT \l__enumext_series_str
1782             {
1783                 \int_gset_eq:NN \g__enumext_resume_int \value{enumXi}
1784             }
1785         }
1786         {
1787             \int_if_exist:cT { g__enumext_series_ \l__enumext_resume_name_tl _int }
1788             {
1789                 \int_gset_eq:cN
1790                 { g__enumext_series_ \l__enumext_resume_name_tl _int } \value{enumXi}
1791             }
1792         }
1793         \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl _int }
1794         {
1795             \int_gset_eq:cN
1796             { g__enumext_resume_ \l__enumext_store_name_tl _int } \value{enumXi}
1797         }
1798     }
1799     \bool_if:NT \g__enumext_starred_bool
1800     {
1801         \tl_if_empty:NF \l__enumext_series_str
1802         {
1803             \int_gset_eq:cN
1804             { g__enumext_series_ \l__enumext_series_str _int } \value{enumXvii}

```

```

1805     }
1806     \tl_if_empty:NTF \l__enumext_resume_name_tl
1807     {
1808         \str_if_empty:NT \l__enumext_series_str
1809         {
1810             \int_gset_eq:NN \g__enumext_resume_vii_int \value{enumXvii}
1811         }
1812     }
1813     {
1814         \int_if_exist:cT { g__enumext_series_ \l__enumext_resume_name_tl _int }
1815         {
1816             \int_gset_eq:cN
1817             { g__enumext_series_ \l__enumext_resume_name_tl _int } \value{enumXvii}
1818         }
1819     }
1820     \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl _int }
1821     {
1822         \int_gset_eq:cN
1823         { g__enumext_resume_ \l__enumext_store_name_tl _int } \value{enumXvii}
1824     }
1825 }
1826 }

```

(End of definition for \\_\_enumext\_resume\_save\_counter:.)

### 13.24.3 Internal functions for resume key

\\_\_enumext\_resume\_series:n

The function \\_\_enumext\_resume\_series:n will handle the argument passed to the `resume` key in `enumext` and `enumext*` environments. If the key is passed *without value* the function \\_\_enumext\_resume\_counter: is executed which will set the counter according to the numbering of the last `enumext` or `enumext*` environments in which `series={⟨series name⟩}` key is not present, if the `save-ans` key is active it will set the counter according to the value of the integer variable created by that key, otherwise it will verify that the `\g__enumext_series_⟨series name⟩_tl` variable set by the `series` key exists, if so it will pass these keys to the *first level* of the environment, otherwise it will return an error.

```

1827 \cs_new_protected:Npn \__enumext_resume_series:n #1
1828 {
1829     \tl_if_empty:NTF {#1}
1830     {
1831         \__enumext_resume_counter:n { }
1832     }
1833     {
1834         \tl_if_exist:cTF { g__enumext_series_ \tl_to_str:n {#1} _tl }
1835         {
1836             \__enumext_resume_counter:n {#1}
1837             \bool_if:NT \g__enumext_standar_bool
1838             {
1839                 \keys_set:nv { enumext / level-1 }
1840                 { g__enumext_series_ \tl_to_str:n {#1} _tl }
1841             }
1842             \bool_if:NT \g__enumext_starred_bool
1843             {
1844                 \keys_set:nv { enumext / enumext* }
1845                 { g__enumext_series_ \tl_to_str:n {#1} _tl }
1846             }
1847         }
1848         {
1849             \bool_if:NT \g__enumext_standar_bool
1850             {
1851                 \msg_error:nnn { enumext } { unknown-series } {#1}
1852             }
1853             \bool_if:NT \g__enumext_starred_bool
1854             {
1855                 \msg_error:nnn { enumext } { unknown-series } {#1}
1856             }
1857         }
1858     }
1859 }

```

(End of definition for \\_\_enumext\_resume\_series:n)

\\_\_enumext\_resume\_counter:n

\\_\_enumext\_resume\_counter:

\\_\_enumext\_resume\_counter\_series:

\\_\_enumext\_resume\_counter\_save\_ans:

The function \\_\_enumext\_resume\_counter:n will set the variable \l\_\_enumext\_resume\_active\_bool to true and pass the value of the key `resume` to the variable \l\_\_enumext\_series\_name\_tl which will

contain the  $\{\langle series\ name\rangle\}$ . If the variable `\l__enumext_series_name_tl` is empty, that is, we are passing the key *resume without value*, we will execute the function `\__enumext_resume_counter:`; otherwise, when we pass `resume=\{\langle series\ name\rangle\}` we will execute the function `\__enumext_resume_counter_series:`, finally we will execute the function `\__enumext_resume_counter_save_ans:` which is associated with the key *save-ans*.

```

1860 \cs_new_protected:Npn \__enumext_resume_counter:n #1
1861 {
1862   \bool_set_true:N \l__enumext_resume_active_bool
1863   \tl_set:Nn \l__enumext_resume_name_tl {#1}
1864   \tl_if_empty:NTF \l__enumext_resume_name_tl
1865   {
1866     \__enumext_resume_counter:
1867   }
1868   {
1869     \__enumext_resume_counter_series:
1870   }
1871   \__enumext_resume_counter_save_ans:
1872 }

```

The `\__enumext_resume_counter:` function is executed when the *resume* key is used *without value*, only the counters for the “*first level*” of the environments will be set.

```

1873 \cs_new_protected:Nn \__enumext_resume_counter:
1874 {
1875   \bool_if:NT \g__enumext_standar_bool
1876   {
1877     \int_gincr:N \g__enumext_resume_int
1878     \int_set_eq:NN \l__enumext_start_i_int \g__enumext_resume_int
1879   }
1880   \bool_if:NT \g__enumext_starred_bool
1881   {
1882     \int_gincr:N \g__enumext_resume_vii_int
1883     \int_set_eq:NN \l__enumext_start_vii_int \g__enumext_resume_vii_int
1884   }
1885 }

```

The function `\__enumext_resume_counter_series:` will be executed when the `resume=\{\langle series\ name\rangle\}` key is active, setting the counters for the “*first level*” of the environments according to the value of the integer variables created by the *series* key.

```

1886 \cs_new_protected:Nn \__enumext_resume_counter_series:
1887 {
1888   \bool_if:NT \g__enumext_standar_bool
1889   {
1890     \int_set:Nn \l__enumext_start_i_int
1891     {
1892       \int_use:c { g__enumext_series_ \l__enumext_resume_name_tl _int } + 1
1893     }
1894   }
1895   \bool_if:NT \g__enumext_starred_bool
1896   {
1897     \int_set:Nn \l__enumext_start_vii_int
1898     {
1899       \int_use:c { g__enumext_series_ \l__enumext_resume_name_tl _int } + 1
1900     }
1901   }
1902 }

```

The function `\__enumext_resume_counter_save_ans:` will be executed when the *save-ans* key is active along with the *resume* key, setting the counters for the “*first level*” of the environments according to the value of the integer variables created by the *save-ans* key.

```

1903 \cs_new_protected:Nn \__enumext_resume_counter_save_ans:
1904 {
1905   \bool_lazy_and:nnT
1906   { \bool_if_p:N \l__enumext_standar_first_bool }
1907   { \bool_if_p:N \l__enumext_store_active_bool }
1908   {
1909     \int_set:Nn \l__enumext_start_i_int
1910     {
1911       \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int } + 1
1912     }
1913   }
1914   \bool_lazy_and:nnT

```

```

1915     { \bool_if_p:N \__enumext_starred_first_bool }
1916     { \bool_if_p:N \__enumext_store_active_bool }
1917     {
1918         \int_set:Nn \__enumext_start_vii_int
1919         {
1920             \int_use:c { g__enumext_resume_ \__enumext_store_name_tl _int } + 1
1921         }
1922     }
1923 }

```

(End of definition for `\__enumext_resume_counter:n` and others.)

#### 13.24.4 Internal function for resume\* key

`\__enumext_resume_starred:` The function `\__enumext_resume_starred:` will handle the `resume*` key in the `enumext` and `enumext*` environments. This function will execute the filtered `(keys)` in the last one and will continue with the numbering according to the last execution of the environment `enumext` or `enumext*` in which the keys `resume={⟨series name⟩}` or `series={⟨series name⟩}` were not active.

```

1924 \cs_new_protected:Nn \__enumext_resume_starred:
1925 {
1926     \bool_if:NT \g__enumext_standar_bool
1927     {
1928         \tl_if_empty:NF \g__enumext_standar_series_tl
1929         {
1930             \__enumext_resume_counter:n { }
1931             \keys_set:nV { enumext / level-1 } \g__enumext_standar_series_tl
1932         }
1933     }
1934     \bool_if:NT \g__enumext_starred_bool
1935     {
1936         \tl_if_empty:NF \g__enumext_starred_series_tl
1937         {
1938             \__enumext_resume_counter:n { }
1939             \keys_set:nV { enumext / enumext* } \g__enumext_starred_series_tl
1940         }
1941     }
1942 }

```

(End of definition for `\__enumext_resume_starred:`.)

### 13.25 Setting save-ans, check-ans and no-store keys

The key `save-ans` is directly associated with the keys `check-ans`, `no-store`, `resume` and `resume*`, this will activate the entire “storage system” in the `enumext` package.

#### 13.25.1 Setting save-ans key

`save-ans` We define the keys `save-ans` only for the “first level” of `enumext` and `enumext*`.

```

1943 \cs_set_protected:Npn \__enumext_tmp:n #1
1944 {
1945     \keys_define:nn { enumext / #1 }
1946     {
1947         save-ans .code:n = \__enumext_storing_set:n {##1},
1948         save-ans .value_required:n = true,
1949     }
1950 }
1951 \clist_map_inline:nn { level-1, enumext* } { { \__enumext_tmp:n {#1} } }

```

(End of definition for `save-ans`.)

#### 13.25.2 Internal functions for save-ans key

`\__enumext_start_save_ans_msg:` and `\__enumext_stop_save_ans_msg:` will display in the terminal and `.log` file the environment in which the `save-ans` key was executed along with the line at the beginning and end of it. The function `\__enumext_start_save_ans_msg:` will be passed to `\__enumext_storing_set:n` and the function `\__enumext_stop_save_ans_msg:` will be passed to the function `\__enumext_execute_after_env:`.

```

1952 \cs_new_protected:Nn \__enumext_start_save_ans_msg:
1953 {
1954     \msg_term:nnVV { enumext } { save-ans-log }
1955     \g__enumext_envir_name_tl \__enumext_store_name_tl
1956 }
1957 \cs_new_protected:Nn \__enumext_stop_save_ans_msg:
1958 {

```



```

1959     \msg_term:nnVV { enumext } { save-ans-log-hook }
1960     \g__enumext_envir_name_tl \g__enumext_store_name_tl
1961 }

```

(End of definition for \\_\_enumext\_start\_save\_ans\_msg: and \\_\_enumext\_stop\_save\_ans\_msg:.)

```

\__enumext_storing_set:n
\__enumext_storing_exec:

```

The function \\_\_enumext\_storing\_set:n first pass the value of the `save-ans` key to the variable \l\_\_enumext\_store\_name\_tl which will contain the  $\langle store\ name \rangle$  of the *sequence* and *prop list* we will use. If \l\_\_enumext\_store\_name\_tl is *empty* we return an error message, otherwise will return the appropriate message \\_\_enumext\_start\_save\_ans\_msg: and proceed to execute the function \\_\_enumext\_storing\_exec: for `enumext` and `enumext*` environments.

```

1962 \cs_new_protected:Npn \__enumext_storing_set:n #1
1963 {
1964     \tl_set:Nx \l__enumext_store_name_tl {#1}
1965     \tl_if_empty:NTF \l__enumext_store_name_tl
1966     {
1967         \bool_lazy_or:nnT
1968         { \l__enumext_standar_first_bool } { \l__enumext_starred_first_bool }
1969         {
1970             \msg_error:nnV { enumext } { save-ans-empty } \g__enumext_envir_name_tl
1971         }
1972     }
1973     {
1974         \bool_lazy_or:nnT
1975         { \l__enumext_standar_first_bool } { \l__enumext_starred_first_bool }
1976         {
1977             \__enumext_start_save_ans_msg:
1978             \__enumext_storing_exec:
1979         }
1980     }
1981 }

```

The function \\_\_enumext\_storing\_exec: will set to true the variable \l\_\_enumext\_store\_active\_bool which activates the use of the `\anskey` command and the `anskey*`, `keyans`, `keyans*` and `keyanspic` environments and will set to “true” the variable \l\_\_enumext\_check\_answers\_bool used for internal checking answers mechanism set by the `check-ans` and `no-store` keys, copy  $\langle store\ name \rangle$  into the variable \g\_\_enumext\_store\_name\_tl and execute the function \\_\_enumext\_anskey\_env\_make:V creating the environment `anskey*` (§13.30).

```

1982 \cs_new_protected:Nn \__enumext_storing_exec:
1983 {
1984     \bool_set_true:N \l__enumext_store_active_bool
1985     \bool_set_true:N \l__enumext_check_answers_bool
1986     \tl_gset:NV \g__enumext_store_name_tl \l__enumext_store_name_tl
1987     \__enumext_anskey_env_make:V \l__enumext_store_name_tl

```

The *prop list* \g\_\_enumext\_series\_⟨store name⟩\_prop and the *sequence* \g\_\_enumext\_series\_⟨store name⟩\_seq will be created globally to “store content” in case they do not exist together with the integer variable \g\_\_enumext\_series\_⟨store name⟩\_int used by the keys `resume` and `resume*`.

```

1988     \prop_if_exist:cF { g__enumext_ \l__enumext_store_name_tl _prop }
1989     {
1990         \msg_log:nnV { enumext } { store-prop } \l__enumext_store_name_tl
1991         \prop_new:c { g__enumext_ \l__enumext_store_name_tl _prop }
1992     }
1993     \seq_if_exist:cF { g__enumext_ \l__enumext_store_name_tl _seq }
1994     {
1995         \msg_log:nnV { enumext } { store-seq } \l__enumext_store_name_tl
1996         \seq_new:c { g__enumext_ \l__enumext_store_name_tl _seq }
1997     }
1998     \int_if_exist:cF { g__enumext_resume_ \l__enumext_store_name_tl _int }
1999     {
2000         \msg_log:nnV { enumext } { store-int } \l__enumext_store_name_tl
2001         \int_new:c { g__enumext_resume_ \l__enumext_store_name_tl _int }
2002     }
2003 }

```

(End of definition for \\_\_enumext\_storing\_set:n and \\_\_enumext\_storing\_exec:.)

### 13.25.3 The check answer mechanism

The internal mechanism for “checking answers” follows this logic:

If the line begins with `\item` or `\item*` and does NOT *open a nested environment*, each `\item` or `\item*` must contain a *single* execution of the `\anskey` command, i.e. the counter of the executions of the `\anskey` command must be equal to the counter associated with the sum of executions of `\item` and `\item*`.

If the line begins with `\item` or `\item*` and *opens a nested environment* each `\item` or `\item*` in the nested environment must have a *single* execution of the `\anskey` command and the counter associated to the sum of `\item` and `\item*` executions must decrementing by “one” to maintain equality.

In order for the mechanism for the check-answer to work (not counting `keyans`, `keyans*` and `keyanspic`) we need:

1. We must keep track of the total number of `\item` and `\item*` (enumerated) that appear within the environment including the nested levels.
2. We must keep track of the total number of `\item` and `\item*` (enumerated) that appear per level of nesting.
3. Keeping track of the number of times the environment nests.

The integer variable associated to the sum of each `\item` and `\item*` in the environment `\g__enumext_item_number_int` must match the integer variable `\g__enumext_item_anskey_int` associated to the execution of the command `\anskey`. We analyze the cases:

- a) If the list only has one level the number of `\item` + `\item*` = `\anskey`
- b) If the list has *nested levels*, for each level of nesting we need to decrementing by one (for the `\item` or `\item*` that opens the nest) so that the account remains the same.

With `keyans`, `keyans*` and `keyanspic` it is enough to increase in one the integer of `\anskey`. The integers created must be global if they are not lost in the interior levels of nesting and to execute the test we will use a “hook” function after closing the *first level* of the environment.

### 13.25.4 Setting check-ans and no-store keys

Now we define the keys `check-ans` and `no-store` for all levels of `enumext` and `enumext*` environments.

```

check-ans 2004 \cs_set_protected:Npn \__enumext_tmp:n #1
no-store   2005 {
            2006   \keys_define:nn { enumext / #1 }
            2007   {
            2008     check-ans .bool_set:N = \__enumext_check_ans_key_bool,
            2009     check-ans .initial:n = false,
            2010     check-ans .value_required:n = true,
            2011     no-store .code:n = {
            2012               \bool_set_false:N \__enumext_check_answers_bool
            2013               \bool_set_false:N \__enumext_check_ans_key_bool
            2014             },
            2015     no-store .value_forbidden:n = true,
            2016   }
            2017 }
2018 \clist_map_inline:nn
2019 {
2020   level-1, level-2, level-3, level-4, enumext*
2021 }
2022 { \__enumext_tmp:n {#1} }
```

(End of definition for `check-ans` and `no-store`.)

### 13.25.5 Set-up check answer mechanism

The function `\__enumext_check_ans_active:` will first check the state of the variable `\l__enumext_store_name_tl`, that is, the `save-ans` key is active, if so it will check the state of the variable `\l__enumext_check_answers_bool` handled by the key `no-store` and will execute the function `\__enumext_check_ans_level:` only if “true”, i.e. the key `no-store` is not active.

```

2023 \cs_new_protected:Nn \__enumext_check_ans_active:
2024 {
2025   \tl_if_empty:NF \l__enumext_store_name_tl
2026   {
2027     \bool_if:NT \l__enumext_check_answers_bool
2028     {
2029       \__enumext_check_ans_level:
2030     }
2031   }
2032 }
```

The function `\__enumext_check_ans_level:` will decrement by “one” the value of the variable `\g__enumext_item_number_int` which keeps track of the executions of `\item` and `\item*` for each level of nesting of the environment `enumext`, taking into account whether it is nested within `enumext*` or the opposite and set `\l__enumext_item_number_bool` to “false”.

```

2033 \cs_new_protected:Nn \__enumext_check_ans_level:
2034 {
2035   \int_case:nn { \l__enumext_level_int }
2036   {
2037     { 1 }{
2038       \bool_lazy_all:nT
2039       {
2040         { \bool_if_p:N \g__enumext_starred_bool }
2041         { \int_compare_p:nNn { \l__enumext_level_h_int } = { 1 } }
2042       }
2043       {
2044         \int_gdecr:N \g__enumext_item_number_int
2045         \bool_set_false:N \l__enumext_item_number_bool
2046       }
2047     }
2048     { 2 }{
2049       \int_gdecr:N \g__enumext_item_number_int
2050       \bool_set_false:N \l__enumext_item_number_bool
2051     }
2052     { 3 }{
2053       \int_gdecr:N \g__enumext_item_number_int
2054       \bool_set_false:N \l__enumext_item_number_bool
2055     }
2056     { 4 }{
2057       \int_gdecr:N \g__enumext_item_number_int
2058       \bool_set_false:N \l__enumext_item_number_bool
2059     }
2060   }

```

We should only execute this if `enumext*` is nested in the “first level” of `enumext`, for the rest of the cases the value of `\g__enumext_item_number_int` is already decreased.

```

2061   \int_case:nn { \l__enumext_level_h_int }
2062   {
2063     { 1 }{
2064       \bool_lazy_all:nT
2065       {
2066         { \bool_if_p:N \g__enumext_standar_bool }
2067         { \int_compare_p:nNn { \l__enumext_level_int } = { 1 } }
2068       }
2069       {
2070         \int_gdecr:N \g__enumext_item_number_int
2071         \bool_set_false:N \l__enumext_item_number_bool
2072       }
2073     }
2074   }
2075 }

```

(End of definition for `\__enumext_check_ans_active:` and `\__enumext_check_ans_level:`)

`\__enumext_check_ans_key_hook:`

The function `\__enumext_check_ans_key_hook:` will *export* the status of the local variable `\l__enumext_check_ans_key_bool` to the global variable `\g__enumext_check_ans_key_bool` only if the key `check-ans` is active.

```

2076 \cs_new_protected:Nn \__enumext_check_ans_key_hook:
2077 {
2078   \bool_lazy_and:nnT
2079   { \bool_if_p:N \l__enumext_check_ans_key_bool }
2080   { \bool_if_p:N \g__enumext_standar_bool }
2081   {
2082     \bool_gset_true:N \g__enumext_check_ans_key_bool
2083   }
2084   \bool_lazy_and:nnT
2085   { \bool_if_p:N \l__enumext_check_ans_key_bool }
2086   { \bool_if_p:N \g__enumext_starred_bool }
2087   {
2088     \bool_gset_true:N \g__enumext_check_ans_key_bool
2089   }
2090 }

```

(End of definition for `\__enumext_check_ans_key_hook:`.)

`\__enumext_item_answer_diff:` The function `\__enumext_item_answer_diff:` will set the value of the variable `\g__enumext_item_answer_diff_int` which is used by the functions `\__enumext_check_ans_show:` for the key `save-ans` and by the function `\__enumext_check_ans_log:` by the internal “*check answer*” mechanism. This function will be passed to the function `\__enumext_execute_after_env:`.

```
2091 \cs_new_protected:Nn \__enumext_item_answer_diff:
2092 {
2093   \int_gset:Nn \g__enumext_item_answer_diff_int
2094   {
2095     \int_sign:n { \g__enumext_item_number_int - \g__enumext_item_anskey_int }
2096   }
2097 }
```

(End of definition for `\__enumext_item_answer_diff:`.)

`\__enumext_check_ans_show:` The function `\__enumext_check_ans_show:` will be executed within the function `\__enumext_execute_after_env:` when the key `check-ans` is active, that is, when `\g__enumext_check_ans_key_bool` is “*true*” and will return the appropriate message according to the value of `\g__enumext_item_answer_diff_int` set by the function `\__enumext_item_answer_diff:`.

```
2098 \cs_new_protected:Nn \__enumext_check_ans_show:
2099 {
2100   \int_case:nn { \g__enumext_item_answer_diff_int }
2101   {
2102     { -1 } { \__enumext_check_ans_msg_less: }
2103     { 0 } { \__enumext_check_ans_msg_same_ok: }
2104     { 1 } { \__enumext_check_ans_msg_greater: }
2105   }
2106 }
2107 \cs_new_protected:Nn \__enumext_check_ans_msg_less:
2108 {
2109   \msg_warning:nnee { enumext } { item-less-answer } { \g__enumext_store_name_tl }
2110   { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
2111 }
2112 \cs_new_protected:Nn \__enumext_check_ans_msg_same_ok:
2113 {
2114   \msg_term:nnee { enumext } { items-same-answer } { \g__enumext_store_name_tl }
2115   { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
2116 }
2117 \cs_new_protected:Nn \__enumext_check_ans_msg_greater:
2118 {
2119   \msg_warning:nnee { enumext } { item-greater-answer } { \g__enumext_store_name_tl }
2120   { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
2121 }
```

(End of definition for `\__enumext_check_ans_show:` and others.)

`\__enumext_check_ans_log:` The function `\__enumext_check_ans_log:` will be executed within the function `\__enumext_execute_after_env:` when the key `check-ans` is not active, that is, when `\g__enumext_check_ans_key_bool` is “*false*” and write in the log the appropriate message according to the value of `\g__enumext_item_answer_diff_int` set by the function `\__enumext_item_answer_diff:`.

```
2122 \cs_new_protected:Nn \__enumext_check_ans_log:
2123 {
2124   \int_case:nn { \g__enumext_item_answer_diff_int }
2125   {
2126     { -1 } { \__enumext_check_ans_log_msg_less: }
2127     { 0 } { \__enumext_check_ans_log_msg_same_ok: }
2128     { 1 } { \__enumext_check_ans_log_msg_greater: }
2129   }
2130 }
2131 \cs_new_protected:Nn \__enumext_check_ans_log_msg_less:
2132 {
2133   \msg_log:nnee { enumext } { item-less-answer } { \g__enumext_store_name_tl }
2134   { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
2135 }
2136 \cs_new_protected:Nn \__enumext_check_ans_log_msg_same_ok:
2137 {
2138   \msg_log:nnee { enumext } { items-same-answer } { \g__enumext_store_name_tl }
2139   { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
2140 }
```

```

2141 \cs_new_protected:Nn \__enumext_check_ans_log_msg_greater:
2142 {
2143   \msg_log:nneee { enumext } { item-greater-answer } { \g__enumext_store_name_tl }
2144   { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
2145 }

```

(End of definition for `\__enumext_check_ans_log:` and others.)

### 13.25.6 Check for `\item*` and `\anspic*` commands

`\__enumext_check_starred_cmd:n`

The function `\__enumext_check_starred_cmd:n` performs an *extra check* for the `keyans`, `keyans*` and `keyanspic` environments. Unlike the *check* executed by `check-ans` key this one is not controlled by any key, it is intended to prevent the forgetting of `\item*` or `\anspic*` in these environments.

```

2146 \cs_new_protected:Npn \__enumext_check_starred_cmd:n #1
2147 {
2148   \int_compare:nNnT
2149     { \g__enumext_check_starred_cmd_int } = { 0 }
2150     {
2151       \msg_warning:nnnV
2152         { enumext } { missing-starred } { #1 } \l__enumext_check_start_line_env_tl
2153     }
2154   \int_compare:nNnT
2155     { \g__enumext_check_starred_cmd_int } > { 1 }
2156     {
2157       \msg_warning:nnnV
2158         { enumext } { many-starred } { #1 } \l__enumext_check_start_line_env_tl
2159     }
2160   \int_gzero:N \g__enumext_check_starred_cmd_int
2161   \tl_clear:N \l__enumext_check_start_line_env_tl
2162 }

```

(End of definition for `\__enumext_check_starred_cmd:n`.)

### 13.26 Keys and functions associated with storage

wrap-ans  
wrap-opt  
save-sep  
mark-ans  
mark-pos  
show-ans  
mark-ref  
save-ref

We add the keys `wrap-ans`, `wrap-opt`, `save-sep`, `mark-ans`, `mark-pos`, `show-ans`, `show-pos`, `mark-ref` and `save-ref` related to the “*storage system*” and internal mechanism of “*label and ref*” only at the *first level* of `enumext` and `enumext*`.

```

2163 \cs_set_protected:Npn \__enumext_tmp:n #1
2164 {
2165   \keys_define:nn { enumext / #1 }
2166   {
2167     wrap-ans .cs_set_protected:Np = \__enumext_anskey_wrapper:n ##1,
2168     wrap-ans .initial:n =
2169       {
2170         \fbox{\parbox[t]{\dimeval{\itemwidth -2\fboxsep -2\fboxrule}}{##1}}
2171       },
2172     wrap-ans .value_required:n = true,
2173     wrap-opt .cs_set_protected:Np = \__enumext_keyans_wrapper_opt:n ##1,
2174     wrap-opt .initial:n = [{##1}],
2175     wrap-opt .value_required:n = true,
2176     save-sep .tl_set:N = \l__enumext_store_keyans_item_opt_sep_tl,
2177     save-sep .initial:n = {, ~ },
2178     save-sep .value_required:n = true,
2179     mark-ans .tl_set:N = \l__enumext_mark_answer_sym_tl,
2180     mark-ans .initial:n = \textasteriskcentered,
2181     mark-ans .value_required:n = true,
2182     mark-pos .choice:,
2183     mark-pos / left .code:n = \str_set:Nn \l__enumext_mark_position_str { l },
2184     mark-pos / right .code:n = \str_set:Nn \l__enumext_mark_position_str { r },
2185     mark-pos / unknown .code:n =
2186       \msg_error:nneee { enumext } { unknown-choice }
2187       { mark-pos } { left, ~ right } { \exp_not:n {##1} },
2188     mark-pos .initial:n = right,
2189     mark-pos .value_required:n = true,
2190     show-ans .bool_set:N = \l__enumext_show_answer_bool,
2191     show-ans .initial:n = false,
2192     show-ans .value_required:n = true,
2193     show-pos .bool_set:N = \l__enumext_show_position_bool,
2194     show-pos .initial:n = false,
2195     show-pos .value_required:n = true,
2196     mark-ref .tl_set:N = \l__enumext_mark_ref_sym_tl,

```

```

2197         mark-ref .initial:n = \textreferencemark,
2198         mark-ref .value_required:n = true,
2199         save-ref .bool_set:N = \l__enumext_store_ref_key_bool,
2200         save-ref .initial:n = false,
2201         save-ref .value_required:n = true,
2202     }
2203 }
2204 \clist_map_inline:nn { level-1, enumext* } { \l__enumext_tmp:n {#1} }

```

(End of definition for wrap-ans and others.)

mark-pos For the `keyans` and `keyans*` environments we will only add the keys mark-pos, show-ans and show-pos.

```

show-ans 2205 \cs_set_protected:Npn \l__enumext_tmp:n #1
show-pos 2206 {
2207     \keys_define:nn { enumext / #1 }
2208     {
2209         mark-pos .choice:,
2210         mark-pos / left .code:n = \str_set:Nn \l__enumext_mark_position_str { l },
2211         mark-pos / right .code:n = \str_set:Nn \l__enumext_mark_position_str { r },
2212         mark-pos .initial:n = right,
2213         mark-pos .value_required:n = true,
2214         show-ans .bool_set:N = \l__enumext_show_answer_bool,
2215         show-ans .initial:n = false,
2216         show-ans .value_required:n = true,
2217         show-pos .bool_set:N = \l__enumext_show_position_bool,
2218         show-pos .initial:n = false,
2219         show-pos .value_required:n = true,
2220     }
2221 }
2222 \clist_map_inline:nn { keyans, keyans* } { \l__enumext_tmp:n {#1} }

```

(End of definition for mark-pos, show-ans, and show-pos.)

### 13.26.1 Storing structure of the environments

The idea behind “*storing structure*” in the *sequence* is to have a copy of the *structure of the environment* in which the key `save-ans` is being executed so we must capture the *optional argument* passed to the levels of the environment in which it is executed and “*storing*” this in the *sequence*.

```

\__enumext_store_active_keys:n
\__enumext_store_active_keys_vii:n

```

The functions `\__enumext_store_active_keys:n` and `\__enumext_store_active_keys_vii:n` will be responsible for the “*storing keys*” filtered from the *optional argument* of the environment in which the key `save-ans` is executed and the levels within this for the `enumext` and `enumext*` environments. We will execute this function only if the variable `\l__enumext_store_save_key_X_bool` is false, that is, the key `store-key` is not active, establishing the variable `\l__enumext_store_save_key_X_tl` with the filtered *⟨keys⟩*.

```

2223 \cs_new_protected:Npn \__enumext_store_active_keys:n #1
2224 {
2225     \bool_if:cF { \l__enumext_store_save_key_ \__enumext_level: _bool }
2226     {
2227         \tl_clear:c { \l__enumext_save_key_ \__enumext_level: _tl }
2228         \tl_set:ce
2229             { \l__enumext_store_save_key_ \__enumext_level: _tl }
2230             { \__enumext_filter_save_key:n {#1} }
2231     }
2232 }
2233 \cs_new_protected:Npn \__enumext_store_active_keys_vii:n #1
2234 {
2235     \bool_if:NF \l__enumext_store_save_key_vii_bool
2236     {
2237         \tl_clear:N \l__enumext_store_save_key_vii_tl
2238         \tl_set:Ne \l__enumext_store_save_key_vii_tl { \__enumext_filter_save_key:n {#1} }
2239     }
2240 }

```

(End of definition for `\__enumext_store_active_keys:n` and `\__enumext_store_active_keys_vii:n`.)

### 13.26.2 Setting save-key key

Since this “*storing structure*” in the *sequence* established by the `save-ans` key when executing `\anskey` or `anskey*`, we will not be able to modify it. The best thing here is to have a key that allows you to modify the *optional argument* of the “*storing structure*” in the *sequence*.

`save-key` The values set by this key passed in the *optional argument* of the `enumext` and `enumext*` environments will override the values of the `\l__enumext_store_save_key_X_tl` variable set by the functions `\__enumext_store_active_keys:n` and `\__enumext_store_active_keys_vii:n`. Now define the key `save-key` for all levels of `enumext` and `enumext*` environments.

```

2241 \cs_set_protected:Npn \__enumext_tmp:n #1
2242 {
2243   \keys_define:nn { enumext / enumext* }
2244   {
2245     save-key .code:n = \__enumext_parse_save_key_vii:n {##1},
2246     save-key .value_required:n = true,
2247   }
2248   \keys_define:nn { enumext / #1 }
2249   {
2250     save-key .code:n = \__enumext_parse_save_key:n {##1},
2251     save-key .value_required:n = true,
2252   }
2253 }
2254 \clist_map_inline:nn { level-1, level-2, level-3, level-4 } { \__enumext_tmp:n {#1} }

```

(End of definition for `save-key`.)

```

\__enumext_parse_save_key:n
\__enumext_parse_save_key_vii:n

```

The functions `\__enumext_parse_save_key:n` and `\__enumext_parse_save_key_vii:n` will be responsible for “*storing keys*” in the variable `\l__enumext_store_save_key_X_tl` for `enumext` and `enumext*`.

```

2255 \cs_new_protected:Npn \__enumext_parse_save_key:n #1
2256 {
2257   \bool_set_true:c { l__enumext_store_save_key_ \__enumext_level: _bool }
2258   \tl_clear:c { l__enumext_save_key_ \__enumext_level: _tl }
2259   \tl_set:ce
2260   { l__enumext_store_save_key_ \__enumext_level: _tl }
2261   { \__enumext_filter_save_key:n {#1} }
2262 }
2263 \cs_new_protected:Npn \__enumext_parse_save_key_vii:n #1
2264 {
2265   \bool_set_true:N \l__enumext_store_save_key_vii_bool
2266   \tl_clear:N \l__enumext_store_save_key_vii_tl
2267   \tl_set:Ne \l__enumext_store_save_key_vii_tl { \__enumext_filter_save_key:n {#1} }
2268 }

```

(End of definition for `\__enumext_parse_save_key:n` and `\__enumext_parse_save_key_vii:n`.)

### 13.26.3 Internal functions to store optional arguments

```

\__enumext_filter_save_key:n
\__enumext_filter_save_key_key:n
\__enumext_filter_save_key_pair:nn

```

The function `\__enumext_filter_save_key:n` will be in charge of “*filtering keys*” we want to *stored in sequence* where `{#1}` represents the *optional argument* passed to the environment.

```

2269 \cs_new:Npn \__enumext_filter_save_key:n #1
2270 {
2271   \use:e
2272   {
2273     \keyval_parse:NNn
2274     \__enumext_filter_save_key_key:n
2275     \__enumext_filter_save_key_pair:nn {#1}
2276   }
2277 }

```

The function `\__enumext_filter_save_key_key:n` will be responsible for “*filtering keys*” that are passed “*without value*” by excluding the `resume`, `resume*`, `no-store` and `base-fix` keys.

```

2278 \cs_new:Npn \__enumext_filter_save_key_key:n #1
2279 {
2280   \str_case:nnF {#1}
2281   {
2282     { resume } {} { resume* } {} { no-store } {} { base-fix } {}
2283   }
2284   { , { \exp_not:n {#1} } }
2285 }

```



The function `\__enumext_filter_save_key_pair:nn` will be responsible for “*filtering keys*” that are passed “*with value*” by excluding the `series`, `resume`, `save-ans`, `save-ref`, `check-ans`, `show-ans`, `save-pos`, `wrap-ans`, `mark-ans`, `wrap-opt`, `save-sep`, `mark-ref`, `mini-env`, `mini-sep`, `mini-right` and `mini-right*` keys.

```

2286 \cs_new:Npn \__enumext_filter_save_key_pair:nn #1#2
2287 {
2288   \str_case:nnF {#1}
2289   {
2290     { series } {} { resume } {} { save-ans } {} { save-ref } {}
2291     { save-key } {} { check-ans } {} { show-ans } {} { show-pos } {}
2292     { wrap-ans } {} { mark-ans } {} { wrap-opt } {} { save-sep } {}
2293     { mark-ref } {} { mini-env } {} { mini-sep } {} { mini-right } {}
2294     { mini-right* } {}
2295   }
2296   { , { \exp_not:n {#1} } = { \exp_not:n {#2} } }
2297 }

```

(End of definition for `\__enumext_filter_save_key:n`, `\__enumext_filter_save_key_key:n`, and `\__enumext_filter_save_key_pair:nn`.)

### 13.26.4 Function for storing content in prop list

```

\__enumext_store_addto_prop:n
\__enumext_store_addto_prop:V

```

The function `\__enumext_store_addto_prop:n` stores the `{\content}` in *prop list* defined by `save-ans` key. The “*stored content*” is retrieved by means of the `\getkeyans` command.

The form in which the `{\content}` is “*stored*” in the *prop list* is `{\position}{\content}`. This function is used by `\anskey` in `enumext` and `enumext*` environments, `\item*` in `keyans` and `keyans*` environments and `\anspic*` in `keyanspic` environment.

```

2298 \cs_new_protected:Npn \__enumext_store_addto_prop:n #1
2299 {
2300   \prop_gput_if_not_in:cen { g__enumext_ \__enumext_store_name_tl _prop }
2301   {
2302     \int_eval:n { \prop_count:c { g__enumext_ \__enumext_store_name_tl _prop } + 1 }
2303   }
2304   { #1 }
2305 }
2306 \cs_generate_variant:Nn \__enumext_store_addto_prop:n { V }

```

(End of definition for `\__enumext_store_addto_prop:n`.)

### 13.26.5 Function for storing content in sequence

```

\__enumext_store_addto_seq:n
\__enumext_store_addto_seq:v
\__enumext_store_addto_seq:V

```

The function `\__enumext_store_addto_seq:n` stores the `{\content}` in *sequence* defined by `save-ans` key. This function is used by `\anskey` in `enumext`, `\item*` in `keyans` and `\anspic` in `keyanspic`.

The form in which the `{\content}` is stored in *sequence* is in a internal `enumext` or `enumext*` environments with the “*same structure*” in which the command was executed.

The “*stored content*” is retrieved by means of the `\printkeyans` command.

```

2307 \cs_new_protected:Npn \__enumext_store_addto_seq:n #1
2308 {
2309   \seq_gput_right:cn { g__enumext_ \__enumext_store_name_tl _seq } { #1 }
2310 }
2311 \cs_generate_variant:Nn \__enumext_store_addto_seq:n { v, V }

```

(End of definition for `\__enumext_store_addto_seq:n`.)

### 13.26.6 Functions for storing structure in the sequence

```

\__enumext_store_level_open:
\__enumext_store_level_close:

```

The “*storing structure*” is handled by the functions `\__enumext_store_level_open:` and `\__enumext_store_level_close:` which are executed per level within the `enumext` environment.

```

2312 \cs_new_protected:Nn \__enumext_store_level_open:
2313 {
2314   \bool_if:NT \__enumext_check_answers_bool
2315   {
2316     \tl_if_empty:cTF { l__enumext_store_save_key_ \__enumext_level: _tl }
2317     {
2318       \__enumext_store_addto_seq:n
2319       {
2320         \item \begin{enumext}
2321       }
2322     }
2323     {
2324       \tl_put_left:cn { l__enumext_store_save_key_ \__enumext_level: _tl }
2325       {

```

```

2326         \item \begin{enumext} [
2327         ]
2328         \tl_put_right:cn { l__enumext_store_save_key_ \_tl }
2329         {
2330         ]
2331         }
2332         \__enumext_store_addto_seq:v { l__enumext_store_save_key_ \_tl }
2333     }
2334 }
2335 }
2336 \cs_new_protected:Nn \__enumext_store_level_close:
2337 {
2338     \bool_if:NT \l__enumext_check_answers_bool
2339     {
2340         \__enumext_store_addto_seq:n { \end{enumext} }
2341     }
2342 }

```

(End of definition for \\_\_enumext\_store\_level\_open: and \\_\_enumext\_store\_level\_close:.)

\\_\_enumext\_store\_level\_open\_vii:  
 \\_\_enumext\_store\_level\_close\_vii:

The “storing structure” is handled by the functions \\_\_enumext\_store\_level\_open\_vii: and \\_\_enumext\_store\_level\_close\_vii: which are executed in the `enumext*` environment.

```

2343 \cs_new_protected:Nn \__enumext_store_level_open_vii:
2344 {
2345     \bool_if:NT \l__enumext_check_answers_bool
2346     {
2347         \tl_if_empty:NTF \l__enumext_store_save_key_vii_tl
2348         {
2349             \__enumext_store_addto_seq:n
2350             {
2351                 \item \begin{enumext*}
2352             }
2353         }
2354         {
2355             \tl_put_left:Nn \l__enumext_store_save_key_vii_tl
2356             {
2357                 \item \begin{enumext*}[
2358             }
2359             \tl_put_right:Nn \l__enumext_store_save_key_vii_tl
2360             {
2361             ]
2362             }
2363             \__enumext_store_addto_seq:V \l__enumext_store_save_key_vii_tl
2364         }
2365     }
2366 }
2367 \cs_new_protected:Nn \__enumext_store_level_close_vii:
2368 {
2369     \bool_if:NT \l__enumext_check_answers_bool
2370     {
2371         \__enumext_store_addto_seq:n { \end{enumext*} }
2372     }
2373 }

```

(End of definition for \\_\_enumext\_store\_level\_open\_vii: and \\_\_enumext\_store\_level\_close\_vii:.)

### 13.26.7 Function for show marks and position

\\_\_enumext\_print\_keyans\_box:NN  
 \\_\_enumext\_print\_keyans\_box:cc

The function \\_\_enumext\_print\_keyans\_box:NN print a box in the left margin with \l\_\_enumext\_mark\_answer\_sym\_tl used by the `wrap-ans`, `show-ans` and `show-pos` keys. The function takes two arguments:

#1: \l\_\_enumext\_labelwidth\_X\_dim  
 #2: \l\_\_enumext\_labelsep\_X\_dim

```

2374 \cs_new_protected:Nn \__enumext_print_keyans_box:NN
2375 {
2376     \mode_leave_vertical:
2377     \skip_horizontal:n { -\dim_use:N #2 }
2378     \makebox[0pt][ r ]
2379     {
2380         \makebox[ \dim_use:N #1 ][ \l__enumext_mark_position_str ]
2381         {
2382             \tl_use:N \l__enumext_mark_answer_sym_tl

```

```

2383     }
2384   }
2385   \skip_horizontal:n { \dim_use:N #2 }
2386 }
2387 \cs_generate_variant:Nn \__enumext_print_keyans_box:NN { cc }

```

(End of definition for `\__enumext_print_keyans_box:NN`.)

### 13.27 The internal label and ref

The function `\__enumext_store_internal_ref:` handles the “*internal label and ref*” system used by the `save-ref` and `mark-ref` keys for `\anskey` will allow to execute `\ref{⟨store name : position⟩}` and will return `1.(a).i.A.`

`\__enumext_store_internal_ref:`

First we will remove the dots “.” from the current `⟨labels⟩`, we do not want to get double dots in our references, then we will place this in the variable `\l__enumext_newlabel_arg_two_tl`.

```

2388 \cs_new_protected:Nn \__enumext_store_internal_ref:
2389 {
2390   \cs_set_protected:Npn \__enumext_tmp:n ##1
2391   {
2392     \tl_set_eq:cc { \l__enumext_label_copy_##1_tl } { \l__enumext_label_##1_tl }
2393     \tl_reverse:c { \l__enumext_label_copy_##1_tl }
2394     \tl_remove_once:cn { \l__enumext_label_copy_##1_tl } { . }
2395     \tl_reverse:c { \l__enumext_label_copy_##1_tl }
2396   }
2397   \clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {##1} }
2398   \cs_set:Npn \__enumext_tmp:n ##1
2399   { . \tl_use:c { \l__enumext_label_copy_ \int_to_roman:n {##1} _tl } }

```

Here we need to analyse the cases where the environment is started with `enumext*` and if `\anskey` or `anskey*` is running alone in it or if it is running in a nested `enumext` environment within the starting environment.

```

2400   \bool_lazy_all:nT
2401   {
2402     { \bool_if_p:N \g__enumext_starred_bool }
2403     { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
2404   }
2405   {
2406     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2407     { \tl_use:N \l__enumext_label_copy_vii_tl }
2408   }
2409   \bool_lazy_all:nT
2410   {
2411     { \bool_not_p:n { \g__enumext_standar_bool } }
2412     { \bool_if_p:N \l__enumext_standar_bool }
2413     { \int_compare_p:nNn { \l__enumext_level_int } > { 0 } }
2414   }
2415   {
2416     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2417     {
2418       \tl_use:N \l__enumext_label_copy_vii_tl
2419       \int_step_function:nnN { 1 } { \l__enumext_level_int } \__enumext_tmp:n
2420     }
2421   }

```

If started with `enumext` and if `\anskey` or `anskey*` is running alone in it or if it is running in a nested `enumext*` environment within the starting environment.

```

2422   \bool_lazy_all:nT
2423   {
2424     { \bool_if_p:N \g__enumext_standar_bool }
2425     { \int_compare_p:nNn { \l__enumext_level_int } > { 0 } }
2426     { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
2427   }
2428   {
2429     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2430     {
2431       \tl_use:N \l__enumext_label_copy_i_tl
2432       \int_step_function:nnN { 2 } { \l__enumext_level_int } \__enumext_tmp:n
2433     }
2434   }
2435   \cs_set:Npn \__enumext_tmp:n ##1
2436   { \tl_use:c { \l__enumext_label_copy_ \int_to_roman:n {##1} _tl } . }
2437   \bool_lazy_all:nT

```

```

2438     {
2439       { \bool_if_p:N \g__enumext_standar_bool }
2440       { \bool_if_p:N \l__enumext_starred_bool }
2441       { \int_compare_p:nNn { \l__enumext_level_int } > { 0 } }
2442     }
2443     {
2444       \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2445       {
2446         \int_step_function:nnN { 1 } { \l__enumext_level_int } \l__enumext_tmp:n
2447         \tl_use:N \l__enumext_label_copy_vii_tl
2448       }
2449     }

```

Now we set the variable `\l__enumext_newlabel_arg_one_tl` which will contain  $\{\langle store\ name : position \rangle\}$ .

```

2450     \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
2451     {
2452       \l__enumext_store_name_tl \c_colon_str
2453       \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
2454     }

```

Now execute the function `\__enumext_newlabel:nn` and save the result in the variable `\l__enumext_write_aux_file_tl` and finally we write in the `.aux` file.

```

2455     \tl_put_right:Ne \l__enumext_write_aux_file_tl
2456     {
2457       \__enumext_newlabel:nn
2458       { \exp_not:V \l__enumext_newlabel_arg_one_tl }
2459       { \l__enumext_newlabel_arg_two_tl }
2460     }
2461     \l__enumext_write_aux_file_tl
2462   }

```

(End of definition for `\__enumext_store_internal_ref:`)

### 13.28 Common functions for `\anskey` and `anskey*` environment

`\__enumext_store_anskey_code:n`

The internal function `\__enumext_store_anskey_code:n` first we pass the  $\{\langle argument \rangle\}$  to the *prop list*, then checks the state of the variable `\l__enumext_store_ref_key_bool` handled by the *save-ref* key and will call the function `\__enumext_store_internal_ref:` for the “*internal label and ref*” system. Followed by this if the *show-ans* or *show-pos* keys are active we will show the “*wrapped*”  $\{\langle argument \rangle\}$ .

```

2463 \cs_new_protected:Npn \__enumext_store_anskey_code:n #1
2464 {
2465   \int_gincr:N \g__enumext_item_anskey_int
2466   \__enumext_store_addto_prop:n {#1}
2467   \bool_if:NT \l__enumext_store_ref_key_bool
2468   {
2469     \__enumext_store_internal_ref:
2470   }
2471   \__enumext_anskey_show_wrap_left:n { #1 }

```

Now we start processing the  $[\langle key = val \rangle]$  passed to the command to build our `\item` in the variable `\l__enumext_store_anskey_arg_tl` which we will “*store*” in the *sequence*. First we clear the variable `\l__enumext_store_anskey_arg_tl` and process the  $\langle keys \rangle$ , if the *break-col* key is present and the command is running under *enumext* (not in *enumext\**) we will add `\columnbreak` and then `\item`.

```

2472   \tl_clear:N \l__enumext_store_anskey_arg_tl
2473   \bool_lazy_and:nnT
2474   { \bool_if_p:N \l__enumext_store_columns_break_bool }
2475   { \bool_not_p:n { \l__enumext_starred_bool } }
2476   {
2477     \tl_put_left:Nn \l__enumext_store_anskey_arg_tl { \columnbreak }
2478   }
2479   \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { \item }

```

If the *item-join* key is present and the command is running under *enumext\** we will add  $\langle \langle number \rangle \rangle$  to `\l__enumext_store_anskey_arg_tl`.

```

2480   \bool_lazy_and:nnT
2481   { \bool_not_p:n { \l__enumext_starred_bool } }
2482   { \int_compare_p:nNn { \l__enumext_store_item_join_int } > { 1 } }
2483   {
2484     \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2485     {
2486       ( \exp_not:V \l__enumext_store_item_join_int )
2487     }
2488   }

```

And now we will review the keys `item-star`, `item-sym*` and `item-pos*` and pass them to `\l__enumext_store_anskey_arg_tl` along with the  $\langle argument \rangle$  for `\anskey` or  $\langle body \rangle$  for `anskey*`.

```

2489 \bool_if:NTF \l__enumext_store_item_star_bool
2490 {
2491   \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { * }
2492   \tl_if_empty:NF \l__enumext_store_item_symbol_tl
2493   {
2494     \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2495     {
2496       [ \exp_not:V \l__enumext_store_item_symbol_tl ]
2497     }
2498   }
2499   \dim_compare:nT
2500   {
2501     \l__enumext_store_item_symbol_sep_dim != \c_zero_dim
2502   }
2503   {
2504     \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2505     {
2506       [ \exp_not:V \l__enumext_store_item_symbol_sep_dim ]
2507     }
2508   }
2509   \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#1}
2510 }
2511 {
2512   \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#1}
2513 }

```

Finally we check if the `save-ref` key are active along with the `hyperref` package load, if both conditions are met, it will create the `\hyperlink` with “*symbol*” set by `mark-ref` key and then store in *sequence*.

```

2514 \bool_lazy_and:nnT
2515 { \bool_if_p:N \l__enumext_store_ref_key_bool }
2516 { \bool_if_p:N \l__enumext_hyperref_bool }
2517 {
2518   \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2519   {
2520     \hfill \exp_not:N \hyperlink { \exp_not:V \l__enumext_newlabel_arg_one_tl }
2521     { \exp_not:V \l__enumext_mark_ref_sym_tl }
2522   }
2523 }
2524 \l__enumext_store_addto_seq:V \l__enumext_store_anskey_arg_tl
2525 }

```

(End of definition for `\l__enumext_store_anskey_code:n`.)

`\l__enumext_anskey_show_wrap_arg:n`

The function `\l__enumext_anskey_show_wrap_arg:n` “wraps” the  $\langle argument \rangle$  passed to `\anskey` and the  $\langle body \rangle$  for `anskey*` when using the `wrap-ans` key.

```

2526 \cs_new_protected:Npn \l__enumext_anskey_show_wrap_arg:n #1
2527 {
2528   \par
2529   \bool_if:NTF \l__enumext_starred_bool
2530   {
2531     \l__enumext_print_keyans_box:NN
2532     \l__enumext_labelwidth_vii_dim \l__enumext_labelsep_vii_dim
2533   }
2534   {
2535     \l__enumext_print_keyans_box:cc
2536     { \l__enumext_labelwidth_ \l__enumext_level: _dim }
2537     { \l__enumext_labelsep_ \l__enumext_level: _dim }
2538   }
2539   \l__enumext_anskey_wrapper:n { #1 }
2540 }

```

(End of definition for `\l__enumext_anskey_show_wrap_arg:n`.)

`\l__enumext_anskey_show_wrap_left:n`

The function `\l__enumext_anskey_show_wrap_left:n` will show the “*mark*” defined by the `mark-ans` key or the “*position*” of the  $\langle content \rangle$  stored in the *prop list* when using the `show-pos` key on the left margin next to the “wraps”  $\langle argument \rangle$  passed to `\anskey` and the  $\langle body \rangle$  in `anskey*` on the right side when using the `show-ans` key.

```

2541 \cs_new_protected:Npn \l__enumext_anskey_show_wrap_left:n #1
2542 {

```

```

2543 \bool_if:NT \l__enumext_show_answer_bool
2544 {
2545   \__enumext_anskey_show_wrap_arg:n { #1 }
2546 }
2547 \bool_if:NT \l__enumext_show_position_bool
2548 {
2549   \tl_set:Nx \l__enumext_mark_answer_sym_tl
2550   {
2551     \group_begin:
2552     \exp_not:N \normalfont
2553     \exp_not:N \footnotesize [ \int_eval:n
2554       {
2555         \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
2556       }
2557     ]
2558     \group_end:
2559   }
2560   \__enumext_anskey_show_wrap_arg:n { #1 }
2561 }
2562 }

```

(End of definition for \\_\_enumext\_anskey\_show\_wrap\_left:n.)

### 13.29 The command \anskey

Since we will be “*storing content*” in a `list` environment within *sequences* and can (more or less) manage the options passed to each level, it is necessary that we have a little more control over `\item` when storing.

The `\anskey` command will cover this point and give it similar behaviour to that of `\item` in the `enumext` and `enumext*` environments executed as follows `\anskey[⟨key = val⟩]{⟨content⟩}`.

First we’ll add the keys `break-col`, `item-join`, `item-star`, `item-sym*` and `item-pos*`.

```

2563 \keys_define:nn { enumext / anskey }
2564 {
2565   break-col .bool_set:N = \l__enumext_store_columns_break_bool,
2566   break-col .default:n = true,
2567   break-col .value_forbidden:n = true,
2568   item-join .int_set:N = \l__enumext_store_item_join_int,
2569   item-join .value_required:n = true,
2570   item-star .bool_set:N = \l__enumext_store_item_star_bool,
2571   item-star .default:n = true,
2572   item-star .value_forbidden:n = true,
2573   item-sym* .tl_set:N = \l__enumext_store_item_symbol_tl,
2574   item-sym* .value_required:n = true,
2575   item-pos* .dim_set:N = \l__enumext_store_item_symbol_sep_dim,
2576   item-pos* .value_required:n = true,
2577   unknown .code:n = { \__enumext_anskey_unknown:n {#1} },
2578 }

```

The `⟨keys⟩` are stored in `\l_keys_key_str` and the value (if any) is passed as an argument to the function `\__enumext_anskey_unknown:n`.

```

2579 \cs_new_protected:Npn \__enumext_anskey_unknown:n #1
2580 {
2581   \exp_args:NV \__enumext_anskey_unknown:nn \l_keys_key_str {#1}
2582 }
2583 \cs_new_protected:Npn \__enumext_anskey_unknown:nn #1 #2
2584 {
2585   \tl_if_blank:nTF {#2}
2586   {
2587     \msg_error:nnn { enumext } { anskey-cmd-key-unknown } {#1}
2588   }
2589   {
2590     \msg_error:nnnn { enumext } { anskey-cmd-key-value-unknown } {#1} {#2}
2591   }
2592 }

```

(End of definition for \\_\_enumext\_anskey\_unknown:n and \\_\_enumext\_anskey\_unknown:nn.)

- 🔗 The `\anskey` command will only be present when using the `save-ans` key in `enumext` and `enumext*` environments, otherwise it will return an error.

**\anskey** We will first call the function `\__enumext_anskey_safe_outer:` to be sure where we execute the command, then we will check the state of the variable `\l__enumext_check_answers_bool` set by the key `no-store`, if is true we will increment `\g__enumext_item_anskey_int` for the internal “*check answer*” system and

execute the function `\__enumext_anskey_safe_inner:n` to ensure that the command is not nested and that the argument is not empty, finally search the `[⟨key = val⟩]` and call the function `\__enumext_store_anskey_code:n`.

```

2593 \NewDocumentCommand \anskey { o +m }
2594 {
2595   \__enumext_anskey_safe_outer:
2596   \group_begin:
2597     \bool_if:NT \l__enumext_check_answers_bool
2598     {
2599       \tl_if_novalue:nF {#1}
2600       {
2601         \keys_set:nn { enumext / anskey } {#1}
2602       }
2603       \tl_if_blank:nTF {#2}
2604       {
2605         \msg_error:nn { enumext } { anskey-empty-arg }
2606       }
2607       {
2608         \__enumext_anskey_safe_inner:
2609         \__enumext_store_anskey_code:n {#2}
2610       }
2611     }
2612   \group_end:
2613 }

```

(End of definition for `\anskey`. This function is documented on page 12.)

### 13.29.1 Internal functions for the command

`\__enumext_anskey_safe_outer:`  
`\__enumext_anskey_safe_inner:`

The `\__enumext_store_anskey_safe_outer:` function will return the appropriate messages when the command is executed outside the environment in which the `save-ans` key was activated.

```

2614 \cs_new_protected:Nn \__enumext_anskey_safe_outer:
2615 {
2616   \bool_if:NF \l__enumext_store_active_bool
2617   {
2618     \msg_error:nnnn { enumext } { anskey-wrong-place } { anskey } { enumext }
2619   }
2620   \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
2621   {
2622     \msg_error:nnnn { enumext } { command-wrong-place } { anskey } { keyans }
2623   }
2624   \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
2625   {
2626     \msg_error:nnnn { enumext } { command-wrong-place } { anskey } { keyans* }
2627   }
2628   \int_compare:nNnT { \l__enumext_keyans_pic_level_int } = { 1 }
2629   {
2630     \msg_error:nnnn { enumext } { command-wrong-place } { anskey } { keyanspic }
2631   }
2632 }

```

The `\__enumext_anskey_safe_inner:` function will first check if the command is nested, if preceded by a not numbered `\item` or if it is in *math mode* returning the appropriate messages.

```

2633 \cs_new_protected:Nn \__enumext_anskey_safe_inner:
2634 {
2635   \int_incr:N \l__enumext_anskey_level_int
2636   \int_compare:nNnT { \l__enumext_anskey_level_int } > { 1 }
2637   {
2638     \msg_error:nn { enumext } { anskey-nested }
2639   }
2640   \bool_if:NF \l__enumext_item_number_bool
2641   {
2642     \msg_error:nn { enumext } { anskey-unnumber-item }
2643   }
2644   \mode_if_math:T
2645   {
2646     \msg_error:nne { enumext } { anskey-math-mode } { \c_backslash_str anskey }
2647   }
2648 }

```

(End of definition for `\__enumext_anskey_safe_outer:` and `\__enumext_anskey_safe_inner:`.)



### 13.30 The environment anskey\*

Managing *verbatim content* in an environment is quite complicated, I learned that when creating the `scontents` package, so to be able to have support at this point it is best to play a little with the internal code of `scontents` and `hooks`. Some considerations I should have here before implementing this:

- If some package, class or user has defined the environment with the same name somewhere in the document it would be a problem, you would not know what argument has been passed to `store-env`, if you are using the key `print-env` or the `write-out` key, sure, I can detect and modify it within the `enumext` and `enumext*` environments, but it would look strange not to have some keys available when running within these environments.
- A better (perhaps a bit paranoid) option is to define it within the environment in which the `save-ans` key is executed. and have it available only when that key is executed, here I would have absolute control of the `(keys)` and I make sure that `write-out` is not used, then using `hooks after` I undefine it and using `hook before` I check if it has been created by any package, class or user and I return a error, then the user will have to see how to solve the problem.

`\__enumext_undefine_anskey_env:` The function `\__enumext_undefine_anskey_env:` will undefine the environment `anskey*` and will be passed to the function `\__enumext_execute_after_env:` (§13.31) which is executed after the environment in which the key `save-ans` is active.

```
2649 \cs_new_protected:Nn \__enumext_undefine_anskey_env:
2650 {
2651   \cs_undefine:c { anskey* }
2652   \cs_undefine:c { endanskey* }
2653   \cs_undefine:c { __scontents_anskey*_env_begin: }
2654   \cs_undefine:c { __scontents_anskey*_env_end: }
2655 }
```

Detection of the `anskey*` environment outside the `enumext` and `enumext*` environments.

```
2656 \__enumext_before_env:nn { enumext }
2657 {
2658   \bool_lazy_and:nnT
2659     { \int_compare_p:nNn { \__enumext_level_int } = { 0 } }
2660     { \int_compare_p:nNn { \__enumext_level_h_int } = { 0 } }
2661     {
2662       \cs_if_free:cF { __scontents_anskey*_env_begin: }
2663       {
2664         \msg_error:nnn { enumext } { anskey-env-error } { anskey* }
2665       }
2666     }
2667 }
2668 \__enumext_before_env:nn { enumext* }
2669 {
2670   \bool_lazy_and:nnT
2671     { \int_compare_p:nNn { \__enumext_level_int } = { 0 } }
2672     { \int_compare_p:nNn { \__enumext_level_h_int } = { 0 } }
2673     {
2674       \cs_if_free:cF { __scontents_anskey*_env_begin: }
2675       {
2676         \msg_error:nnn { enumext } { anskey-env-error } { anskey* }
2677       }
2678     }
2679 }
```

Detection of the `anskey*` environment inside the `keyans`, `keyans*` and `keyanspic` environments, if preceded by a not numbered `\item` or if it is in *math mode* returning the appropriate messages.

```
2680 \__enumext_before_env:nn { anskey* }
2681 {
2682   \int_compare:nNnT { \__enumext_keyans_level_int } = { 1 }
2683   {
2684     \msg_error:nnn { enumext } { anskey-env-wrong } { keyans }
2685   }
2686   \int_compare:nNnT { \__enumext_keyans_level_h_int } = { 1 }
2687   {
2688     \msg_error:nnn { enumext } { anskey-env-wrong } { keyans* }
2689   }
2690   \int_compare:nNnT { \__enumext_keyans_pic_level_int } = { 1 }
2691   {
2692     \msg_error:nnn { enumext } { anskey-env-wrong } { keyanspic }
2693   }
2694   \bool_if:NF \__enumext_item_number_bool
2695   {
```

```

2696         \msg_error:nn { enumext } { anskey-unnumber-item }
2697     }
2698     \mode_if_math:T
2699     {
2700         \msg_error:nnn { enumext } { anskey-math-mode } { anskey* }
2701     }
2702 }

```

(End of definition for `\__enumext_undefine_anskey_env:`)

**anskey\***

The function `\__enumext_anskey_env_make:n` creates the environment **anskey\*** (*custom version of `scontents` environment*) by setting the initial keys `store-env={⟨store name⟩}` and `print-env=false`.

To maintain the *scope* of the environment and that it is only active when the key `save-ans` is active we will pass this function to the function `\__enumext_storing_exec:` (§13.25.1) and we will execute it only if the variable `\l__enumext_anskey_env_bool` is true, with this we prevent it from being executed again when the environment is nested and the key `save-ans` is active, which returns an error for part of the package **scontents**.

```

2703 \cs_new_protected:Npn \__enumext_anskey_env_make:n #1
2704 {
2705     \bool_if:NT \l__enumext_anskey_env_bool
2706     {
2707         \newenvsc{anskey*}[store-env=#1,print-env=false]
2708         \__enumext_anskey_env_exec:
2709     }
2710 }
2711 \cs_generate_variant:Nn \__enumext_anskey_env_make:n { V }

```

The function `\__enumext_anskey_env_define_keys:` will add the keys `break-col`, `item-join`, `item-join`, `item-star`, `item-sym*` and `item-pos*` and will leave the keys `print-env`, `store-env` and `write-out` undefined. We will apply this function using the *hook* function `\__enumext_before_env:nn`.

```

2712 \cs_new_protected:Nn \__enumext_anskey_env_define_keys:
2713 {
2714     \keys_define:nn { scontents / scontents }
2715     {
2716         break-col .bool_gset:N = \g__enumext_store_columns_break_bool,
2717         break-col .default:n = true,
2718         break-col .value_forbidden:n = true,
2719         item-join .int_gset:N = \g__enumext_store_item_join_int,
2720         item-join .value_required:n = true,
2721         item-star .bool_gset:N = \g__enumext_store_item_star_bool,
2722         item-star .default:n = true,
2723         item-star .value_forbidden:n = true,
2724         item-sym* .tl_gset:N = \g__enumext_store_item_symbol_tl,
2725         item-sym* .value_required:n = true,
2726         item-pos* .dim_gset:N = \g__enumext_store_item_symbol_sep_dim,
2727         item-pos* .value_required:n = true,
2728         print-env .undefine:,
2729         store-env .undefine:,
2730         write-out .undefine:,
2731         unknown .code:n = { \__enumext_anskey_env_unknown:n {##1} },
2732     }
2733 }

```

The *⟨keys⟩* are stored in `\l_keys_key_str` and the value (if any) is passed as an argument to the function `\__enumext_anskey_env_unknown:n`.

```

2734 \cs_new_protected:Npn \__enumext_anskey_env_unknown:n #1
2735 {
2736     \exp_args:NV \__enumext_anskey_env_unknown:nn \l_keys_key_str {#1}
2737 }
2738 \cs_new_protected:Npn \__enumext_anskey_env_unknown:nn #1#2
2739 {
2740     \tl_if_blank:nTF {#2}
2741     {
2742         \msg_error:nnn { enumext } { anskey-env-key-unknown } {#1}
2743     }
2744     {
2745         \msg_error:nnnn { enumext } { anskey-env-key-value-unknown } {#1} {#2}
2746     }
2747 }

```

The function `\__enumext_anskey_env_reset_keys:` will leave the keys `break-col`, `item-join`, `item-join`, `item-star`, `item-sym*` and `item-pos*` undefined. We will apply this function using the *hook* function `\__enumext_after_env:nn`.

```

2748 \cs_new_protected:Nn \__enumext_anskey_env_reset_keys:
2749 {
2750   \keys_define:nn { scontents / scontents }
2751   {
2752     break-col .undefine:,
2753     item-join .undefine:,
2754     item-star .undefine:,
2755     item-sym* .undefine:,
2756     item-pos* .undefine:,
2757     write-out .code:n = {
2758       \bool_set_false:N \l__scontents_storing_bool
2759       \bool_set_true:N \l__scontents_writing_bool
2760       \tl_set:Nn \l__scontents_fname_out_tl {##1}
2761     },
2762     write-out .value_required:n = true,
2763     print-env .meta:nn = { scontents } { print-env = ##1 },
2764     print-env .default:n = true,
2765     store-env .meta:nn = { scontents } { store-env = ##1 },
2766     unknown .code:n = { \__scontents_parse_environment_keys:n {##1} },
2767   }
2768 }

```

The function `\__enumext_rescan_anskey_env:n` will be responsible for bringing the *(body)* of the environment saved in the sequence `\g__scontents_name_⟨store name⟩_seq` to pass it to our *sequence* and *prop list*.

```

2769 \cs_new_protected:Npn \__enumext_rescan_anskey_env:n #1
2770 {
2771   \group_begin:
2772   \int_set:Nn \tex_newlinechar:D { `^^J }
2773   \__scontents_rescan_tokens:x
2774   {
2775     \endgroup % This assumes \catcode`\=0... Things might go off otherwise.
2776     #1
2777   }
2778 }

```

(End of definition for *anskey\** and others. This function is documented on page 13.)

`\__enumext_anskey_env_exec:`

The function `\__enumext_anskey_env_exec:` will be responsible for processing all the code necessary for the execution of the environment. The first thing will be to add our *(keys)*.

```

2779 \cs_new_protected:Nn \__enumext_anskey_env_exec:
2780 {
2781   \__enumext_before_env:nn { anskey* }
2782   {
2783     \__enumext_anskey_env_define_keys:
2784   }

```

Now we will execute our actions after the *anskey\** environment is closed. We'll fetch the contents of the *environment body* that is now saved in `\g__scontents_name_⟨store name⟩_seq` and store it in the variable `\l__enumext_store_anskey_env_tl` then we execute the rest of the functions.

```

2785   \hook_if_empty:nF {env/anskey*/after}
2786   {
2787     \hook_gremove_code:nn {env/anskey*/after} { * }
2788   }
2789   \__enumext_after_env:nn { anskey* }
2790   {
2791     \__enumext_anskey_env_save_keys:
2792     \tl_clear:N \l__enumext_store_anskey_env_tl
2793     \tl_clear:N \l__enumext_store_anskey_opt_tl
2794     \bool_if:NT \l__enumext_check_answers_bool
2795     {
2796       \tl_gset:Ne \l__enumext_store_anskey_env_tl
2797       {
2798         \seq_item:ce { g__scontents_name_ \l__enumext_store_name_tl _seq } { -1 }
2799       }
2800       \regex_match:nVTF
2801       { ^\s* \z | ^\s* \u{c__scontents_hidden_space_str} \z }
2802       \l__enumext_store_anskey_env_tl

```

```

2803         {
2804             \msg_error:nn { enumext } { anskey-empty-arg }
2805         }
2806         {
2807             \__enumext_anskey_env_store:
2808         }
2809     }
2810     \__enumext_anskey_env_clean_vars:
2811     \__enumext_anskey_env_reset_keys:
2812 }
2813 }

```

• The use of `\hook_gremove_code:nn` is necessary here, otherwise the `{\code}` passed to `\__enumext_after_env:nn{anskey*}` will be accumulated for each execution. The last function `\__enumext_anskey_env_reset_keys:` is necessary so as not to hinder any `scontents` environment running within `enumext` or `enumext*`.

(End of definition for `\__enumext_anskey_env_exec:.`)

```

\__enumext_anskey_env_save_keys:
\__enumext_anskey_env_store:
\__enumext_anskey_env_clean_vars:

```

The function `\__enumext_anskey_env_save_keys:` processing the `[key = val]` passed to the environment and save this in the variable `\l__enumext_store_anskey_opt_tl`. If the `break-col` key is present and the environment is running under `enumext` (not in `enumext*`) we will add the key `break-col`.

```

2814 \cs_new_protected:Nn \__enumext_anskey_env_save_keys:
2815 {
2816     \bool_lazy_and:nnT
2817     { \bool_if_p:N \g__enumext_store_columns_break_bool }
2818     { \bool_not_p:n { \l__enumext_starred_bool } }
2819     {
2820         \tl_put_left:Ne \l__enumext_store_anskey_opt_tl { ,break-col, }
2821     }

```

If the `item-join` key is present and the command is running under `enumext*` we will add to `\l__enumext_store_anskey_opt_tl`.

```

2822     \bool_lazy_and:nnT
2823     { \bool_not_p:n { \l__enumext_starred_bool } }
2824     { \int_compare_p:nNn { \g__enumext_store_item_join_int } > { 1 } }
2825     {
2826         \tl_put_left::Ne \l__enumext_store_anskey_opt_tl
2827         {
2828             ,item-join = \exp_not:V \g__enumext_store_item_join_int,
2829         }
2830     }

```

And now we will review the keys `item-star`, `item-sym*` and `item-pos*` and pass them to `\l__enumext_store_anskey_opt_tl`.

```

2831     \bool_if:NT \g__enumext_store_item_star_bool
2832     {
2833         \tl_put_left:Ne \l__enumext_store_anskey_opt_tl
2834         {
2835             ,item-star,
2836         }
2837         \tl_if_empty:NF \g__enumext_store_item_symbol_tl
2838         {
2839             \tl_put_left:Ne \l__enumext_store_anskey_opt_tl
2840             {
2841                 ,item-sym* = \exp_not:V \g__enumext_store_item_symbol_tl,
2842             }
2843         }
2844         \dim_compare:nT
2845         {
2846             \g__enumext_store_item_symbol_sep_dim != \c_zero_dim
2847         }
2848         {
2849             \tl_put_left:Ne \l__enumext_store_anskey_opt_tl
2850             {
2851                 ,item-pos* = \exp_not:V \g__enumext_store_item_symbol_sep_dim,
2852             }
2853         }
2854     }
2855 }

```

The function `\__enumext_anskey_env_store:` will be responsible for storing the content of the environment using the functions `\__enumext_store_anskey_code:n` and `\__enumext_rescan_anskey_env:n`.

```

2856 \cs_new_protected:Nn \__enumext_anskey_env_store:

```

```

2857 {
2858   \group_begin:
2859   \tl_if_empty:NTF \l__enumext_store_anskey_opt_tl
2860   {
2861     \exp_args:Ne
2862     \__enumext_store_anskey_code:n
2863     {
2864       \__enumext_rescan_anskey_env:n { \l__enumext_store_anskey_env_tl }
2865     }
2866   }
2867   {
2868     \keys_set_known:nV { enumext / anskey } \l__enumext_store_anskey_opt_tl
2869     \exp_args:Ne
2870     \__enumext_store_anskey_code:n
2871     {
2872       \__enumext_rescan_anskey_env:n { \l__enumext_store_anskey_env_tl }
2873     }
2874   }
2875   \group_end:
2876 }

```

The function `\__enumext_anskey_env_clean_vars:` will return the global variables used by the `(keys)` to their initial state.

```

2877 \cs_new_protected:Nn \__enumext_anskey_env_clean_vars:
2878 {
2879   \bool_gset_false:N \g__enumext_store_columns_break_bool
2880   \int_gzero:N \g__enumext_store_item_join_int
2881   \bool_gset_false:N \g__enumext_store_item_star_bool
2882   \tl_gclear:N \g__enumext_store_item_symbol_tl
2883   \dim_gzero:N \g__enumext_store_item_symbol_sep_dim
2884 }

```

(End of definition for `\__enumext_anskey_env_save_keys:`, `\__enumext_anskey_env_store:`, and `\__enumext_anskey_env_clean_vars:`.)

### 13.31 Executing anskey\*, check-ans and write .log

`\__enumext_execute_after_env:`

The `\__enumext_execute_after_env:` function will first return the appropriate message for the end of the environment in which the `save-ans` key is being executed, then call the `\__enumext_item_answer_diff:` function and then will write the values of the global variables used to the `.log` file. If the key `check-ans` is active it will execute the function `\__enumext_check_ans_show:` and show the result in the terminal, otherwise it will execute the function `\__enumext_check_ans_log:` and write the results in the `.log` file, undefine the environment `anskey*` (§13.30) through the function `\__enumext_undefine_anskey_env:` and finally we execute the function `\__enumext_reset_global_vars:` returning the used variables to their original state.

```

2885 \cs_new_protected:Nn \__enumext_execute_after_env:
2886 {
2887   \int_compare:nNtT { \l__enumext_level_int } = { 0 }
2888   {
2889     \tl_if_empty:NF \g__enumext_store_name_tl
2890     {
2891       \__enumext_stop_save_ans_msg:
2892       \__enumext_item_answer_diff:
2893       \__enumext_log_global_vars:
2894       \__enumext_log_answer_vars:
2895       \bool_if:NTF \g__enumext_check_ans_key_bool
2896       {
2897         \__enumext_check_ans_show:
2898       }
2899       { \__enumext_check_ans_log: }
2900       \__enumext_undefine_anskey_env:
2901     }
2902     \__enumext_reset_global_vars:
2903   }
2904 }

```

(End of definition for `\__enumext_execute_after_env:`.)

- This function is passed to the function `\__enumext_after_env:nn` for the environments `enumext` (§13.38) and `enumext*` (§13.43) and it is executed only when the environments are not nested or at some level of these..

### 13.32 Common functions for keyans, keyans\* and keyanspic

#### 13.32.1 Storing content in prop list

`\__enumext_keyans_addto_prop:n`

The function `\__enumext_keyans_addto_prop:n` will pass the the current  $\langle label \rangle$  for  $\backslash item^*$  in `keyans` environment and the current  $\langle label \rangle$  for  $\backslash anspic^*$  in `keyanspic` environment followed by the  $\langle contents \rangle$  of the *optional argument* of both commands to the `\l__enumext_store_current_label_tl` variable, which will be stored to the *prop list* defined by the `save-ans` key using the function `\__enumext_store_addto_prop:V`.

```

2905 \cs_new_protected:Npn \__enumext_keyans_addto_prop:n #1
2906 {
2907   \tl_clear:N \l__enumext_store_current_label_tl
2908   \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
2909   {
2910     \tl_put_right:Ne \l__enumext_store_current_label_tl { \l__enumext_label_vi_tl }
2911   }
2912   {
2913     \tl_put_right:Ne \l__enumext_store_current_label_tl { \l__enumext_label_v_tl }
2914   }

```

If the *optional argument* is present and the `save-sep` key is not empty, we save it.

```

2915   \tl_if_novalue:nF { #1 }
2916   {
2917     \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_tl
2918     {
2919       \tl_put_right:Ne \l__enumext_store_current_label_tl
2920       {
2921         \l__enumext_store_keyans_item_opt_sep_tl
2922       }
2923     }
2924     \tl_put_right:Ne \l__enumext_store_current_label_tl { #1 }
2925   }
2926   \__enumext_store_addto_prop:V \l__enumext_store_current_label_tl
2927 }

```

(End of definition for `\__enumext_keyans_addto_prop:n`.)

#### 13.32.2 The save-ref key for keyans, keyans\* and keyanspic

The “*internal label and ref*” system for the `keyans`, `keyans*` and `keyanspic` environments has *slight differences* with the one implemented for `\anskey` basically because in this environments the interest is in the current  $\langle label \rangle$  for  $\backslash item^*$  and  $\backslash anspic^*$  with the  $\langle contents \rangle$  of the *optional argument*. The mechanism defined here will allow to execute `\ref{⟨store name : position⟩}` and will return `1.` (A).

`\__enumext_keyans_store_ref:`  
`\__enumext_keyans_store_ref_aux_i:`  
`\enumext_keyans_store_ref_aux_ii:`

The function `\__enumext_keyans_store_ref:` handles the “*internal label and ref*” system used by the `save-ref` key for  $\backslash item^*$  and  $\backslash anspic^*$  commands. First we will create copies of the current  $\langle labels \rangle$  and remove the dots “.” from them, we do not want to get double dots in references.

```

2928 \cs_new_protected:Nn \__enumext_keyans_store_ref:
2929 {
2930   \bool_if:NT \l__enumext_store_ref_key_bool
2931   {
2932     \cs_set_protected:Npn \__enumext_tmp:n ##1
2933     {
2934       \tl_set_eq:cc { l__enumext_label_copy_##1_tl } { l__enumext_label_##1_tl }
2935       \tl_reverse:c { l__enumext_label_copy_##1_tl }
2936       \tl_remove_once:cn { l__enumext_label_copy_##1_tl } { . }
2937       \tl_reverse:c { l__enumext_label_copy_##1_tl }
2938     }
2939     \clist_map_inline:nn { i, v, vi, vii, viii } { \__enumext_tmp:n {##1} }
2940     \__enumext_keyans_store_ref_aux_i:
2941   }
2942 }

```

The auxiliary function `\__enumext_keyans_store_ref_aux_i:` set the variable `\l__enumext_newlabel_arg_one_tl` which will contain  $\{ \langle store name : position \rangle \}$  analyzing whether the environment in which they are executed is `enumext*` or `enumext`.

```

2943 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_i:
2944 {
2945   \bool_if:NT \g__enumext_starred_bool
2946   {
2947     \tl_set_eq:NN \l__enumext_label_copy_i_tl \l__enumext_label_copy_vii_tl
2948   }
2949   \int_compare:nNnT { \l__enumext_keyans_pic_level_int } = { 1 }

```

```

2950     {
2951       \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2952       { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_vi_tl }
2953     }
2954     \int_compare:nNt { \l__enumext_keyans_level_int } = { 1 }
2955     {
2956       \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2957       { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_v_tl }
2958     }
2959     \int_compare:nNt { \l__enumext_keyans_level_h_int } = { 1 }
2960     {
2961       \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2962       { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_viii_tl }
2963     }
2964     \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
2965     {
2966       \l__enumext_store_name_tl \c_colon_str
2967       \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
2968     }
2969     \__enumext_keyans_store_ref_aux_ii:
2970   }

```

Now auxiliary function `\__enumext_keyans_store_ref_aux_ii:` save the result in the variable `\l__enumext_write_aux_file_tl` and finally we write in the `.aux` file.

```

2971 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_ii:
2972 {
2973   \tl_put_right:Ne \l__enumext_write_aux_file_tl
2974   {
2975     \__enumext_newlabel:nn
2976     { \exp_not:V \l__enumext_newlabel_arg_one_tl }
2977     { \l__enumext_newlabel_arg_two_tl }
2978   }
2979   \l__enumext_write_aux_file_tl
2980 }

```

(End of definition for `\__enumext_keyans_store_ref:`, `\__enumext_keyans_store_ref_aux_ii:`, and `\__enumext_keyans_store_ref_aux_ii:`.)

### 13.32.3 Storing content in sequence

`\__enumext_keyans_addto_seq:n`  
`\__enumext_keyans_addto_seq_link:`

The function `\__enumext_keyans_addto_seq:n` will pass the contents of the current *⟨label⟩* `\l__enumext_label_v_tl` for the `keyans` environment and the `\l__enumext_label_vi_tl` for the `keyanspic` environment when using `\item*` and `\anspic*`, followed by the *⟨contents⟩* of the *optional argument* of both commands to the `\l__enumext_store_current_label_tl` variable to the sequence defined by the `save-ans` key.

```

2981 \cs_new_protected:Npn \__enumext_keyans_addto_seq:n #1
2982 {
2983   \tl_clear:N \l__enumext_store_current_label_tl
2984   \int_compare:nNtF { \l__enumext_keyans_pic_level_int } = { 1 }
2985   {
2986     \tl_put_right:Ne \l__enumext_store_current_label_tl { \item \l__enumext_label_vi_tl }
2987   }
2988   {
2989     \tl_put_right:Ne \l__enumext_store_current_label_tl { \item \l__enumext_label_v_tl }
2990   }
2991   \tl_if_novalue:nF { #1 }
2992   {
2993     \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_tl
2994     {
2995       \tl_put_right:Ne \l__enumext_store_current_label_tl
2996       {
2997         \l__enumext_store_keyans_item_opt_sep_tl
2998       }
2999     }
3000     \tl_put_right:Ne \l__enumext_store_current_label_tl { #1 }
3001   }
3002   \__enumext_keyans_addto_seq_link:
3003 }

```

Checks if the `save-ref` key is active along with the `hyperref` package load, if both conditions are met, it will create the `\hyperlink` and then store using the `\__enumext_store_addto_seq:V` function. Finally, copy the contents of the variable `\l__enumext_store_current_label_tl` into the global variable `\g__enumext_check_ans_item_tl` to be used by the function `\__enumext_check_starred_cmd:n` and



increment the value of the integer variable `\g__enumext_item_anskey_int` handled by the `check-ans` key.

```

3004 \cs_new_protected:Nn \__enumext_keyans_addto_seq_link:
3005 {
3006   \bool_lazy_and:nnT
3007     { \bool_if_p:N \l__enumext_store_ref_key_bool }
3008     { \bool_if_p:N \l__enumext_hyperref_bool }
3009     {
3010       \tl_put_right:Ne \l__enumext_store_current_label_tl
3011       {
3012         \hfill \exp_not:N \hyperlink
3013         {
3014           \exp_not:V \l__enumext_newlabel_arg_one_tl
3015         }
3016         { \exp_not:V \l__enumext_mark_ref_sym_tl }
3017       }
3018     }
3019     \__enumext_store_addto_seq:V \l__enumext_store_current_label_tl
3020     \bool_if:NT \l__enumext_check_answers_bool
3021     {
3022       \int_gincr:N \g__enumext_item_anskey_int
3023     }
3024 }

```

(End of definition for `\__enumext_keyans_addto_seq:n` and `\__enumext_keyans_addto_seq_link:.`)

### 13.32.4 The `show-ans` and `show-pos` keys for `keyans` and `keyanspic`

The code is very similar to the `\anskey` code, but, if I change the order of the operations the counter off `(label)` are incorrect.

```

\__enumext_keyans_show_left:n
\__enumext_keyans_show_ans:
\__enumext_keyans_show_pos:
\__enumext_keyans_show_item_opt:

```

Common function to show *starred commands* `\item*` and `(position)` of stored content in *prop list* for `keyans` and `keyanspic`. Need add `1` to `\g__enumext_⟨store name⟩_prop` for `show-pos` key.

```

3025 \cs_new_protected:Npn \__enumext_keyans_show_left:n #1
3026 {
3027   \tl_if_novalue:nF { #1 }
3028   {
3029     \tl_set:Ne \l__enumext_store_current_opt_arg_tl { #1 }
3030   }
3031   \bool_if:NT \l__enumext_show_answer_bool
3032   {
3033     \__enumext_keyans_show_ans:
3034   }
3035   \bool_if:NT \l__enumext_show_position_bool
3036   {
3037     \__enumext_keyans_show_pos:
3038   }
3039 }
3040 \cs_new_protected:Nn \__enumext_keyans_show_item_opt:
3041 {
3042   \tl_if_empty:NF \l__enumext_store_current_opt_arg_tl
3043   {
3044     \bool_lazy_or:nnT
3045       { \bool_if_p:N \l__enumext_show_answer_bool }
3046       { \bool_if_p:N \l__enumext_show_position_bool }
3047       {
3048         \__enumext_keyans_wrapper_opt:n { \l__enumext_store_current_opt_arg_tl } \c_space_tl
3049       }
3050   }
3051 }
3052 \cs_new_protected:Nn \__enumext_keyans_show_ans:
3053 {
3054   \bool_if:NT \l__enumext_starred_bool
3055   {
3056     \dim_set_eq:NN \l__enumext_labelwidth_i_dim \l__enumext_labelwidth_vii_dim
3057     \dim_set_eq:NN \l__enumext_labelsep_i_dim \l__enumext_labelsep_vii_dim
3058   }
3059   \tl_put_left:Nn \l__enumext_label_v_tl
3060   {
3061     \__enumext_print_keyans_box:NN
3062     \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
3063   }

```

```

3064 }
3065 \cs_new_protected:Nn \__enumext_keyans_show_pos:
3066 {
3067   \bool_if:NT \l__enumext_starred_bool
3068   {
3069     \dim_set_eq:NN \l__enumext_labelwidth_i_dim \l__enumext_labelwidth_vii_dim
3070     \dim_set_eq:NN \l__enumext_labelsep_i_dim \l__enumext_labelsep_vii_dim
3071   }
3072   \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
3073   {
3074     \tl_set:Ne \l__enumext_mark_answer_sym_tl
3075     {
3076       \group_begin:
3077       \exp_not:N \normalfont
3078       \exp_not:N \footnotesize [ \int_eval:n
3079       {
3080         \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
3081       }
3082       ]
3083       \group_end:
3084     }
3085   }
3086   {
3087     \tl_set:Ne \l__enumext_mark_answer_sym_tl
3088     {
3089       \group_begin:
3090       \exp_not:N \normalfont
3091       \exp_not:N \footnotesize [ \int_eval:n
3092       {
3093         \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } + 1
3094       }
3095       ]
3096       \group_end:
3097     }
3098   }
3099   \tl_put_left:Nn \l__enumext_label_v_tl
3100   {
3101     \__enumext_print_keyans_box:NN
3102     \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
3103   }
3104 }

```

(End of definition for `\__enumext_keyans_show_left:n` and others.)

### 13.33 Redefining `\item` and `\makeLabel` in `enumext`

Redefining the `\item` command is not as simple as I thought. This command works in conjunction with the `\makeLabel` command so I have to redefine both of them, in addition to this, we will have to use a couple of *global* variables to pass the values from one command to the other.

The `\item` and `\item[custom]` commands work in the usual way on `enumext` and we will add `\item*`, `\item*[symbol]` and `\item*[symbol][offset]`.

`\__enumext_default_item:n`

First we will see if the *optional argument* is present, if it is NOT present we will check the state of the variable `\l__enumext_check_answers_bool` set by the key `no-store`, set the boolean variable `\l__enumext_wrap_label_X_bool` to “true” for the key `wrap-label` and execute `\__enumext_item_std:w` and the key `itemindent`, otherwise we will check the state of the boolean variable `\l__enumext_wrap_label_opt_X_bool` set by the key `wrap-label*` and execute `\__enumext_item_std:w` with the *optional argument* and the key `itemindent`.

```

3105 \cs_new_protected:Npn \__enumext_default_item:n #1
3106 {
3107   \tl_if_novalue:nTF {#1}
3108   {
3109     \bool_if:NT \l__enumext_check_answers_bool
3110     {
3111       \int_gincr:N \g__enumext_item_number_int
3112       \bool_set_true:N \l__enumext_item_number_bool
3113     }
3114     \bool_set_true:c { l__enumext_wrap_label_ \__enumext_level: _bool }
3115     \__enumext_item_std:w \tl_use:c { l__enumext_fake_item_indent_ \__enumext_level: _tl }
3116   }
3117   {

```

```

3118         \bool_set_eq:cc
3119         { \l__enumext_wrap_label_ \l__enumext_level: _bool }
3120         { \l__enumext_wrap_label_opt_ \l__enumext_level: _bool }
3121         \l__enumext_item_std:w [#1] \tl_use:c { \l__enumext_fake_item_indent_ \l__enumext_level: _tl
3122     }
3123 }

```

(End of definition for `\l__enumext_default_item:n`.)

`\l__enumext_starred_item:nn`  
`\l__enumext_item_star_exec:`

The `\item*`, `\item*[\langle symbol \rangle]` and `\item*[\langle symbol \rangle][\langle offset \rangle]` works like the *numbered* `\item`, but placing a `\langle symbol \rangle` to the “left” of the `\langle label \rangle` separated from it by the value the second *optional argument* `\langle offset \rangle`.

#1: `\l__enumext_item_symbol_X_tl`

#2: `\l__enumext_item_symbol_sep_X_dim`

First we will make a copy of `\l__enumext_item_symbol_X_tl` which is set by the key `item-sym*` or passed as “first” *optional argument* in the global variable `\g__enumext_item_symbol_aux_tl`, followed by setting the variable `\l__enumext_item_symbol_sep_X_dim` set by the key `item-pos*` or by the “second” *optional argument*, then we will see the state of the variable `\l__enumext_check_answers_bool` set by the key `no-store`, set the boolean variable `\l__enumext_wrap_label_X_bool` to “true” for the key `wrap-label` and execute `\l__enumext_item_std:w` and the key `itemindent`.

```

3124 \cs_new_protected:Npn \l__enumext_starred_item:nn #1 #2
3125 {
3126     \tl_if_novalue:nTF {#1}
3127     {
3128         \tl_gset_eq:Nc
3129         \g__enumext_item_symbol_aux_tl { \l__enumext_item_symbol_ \l__enumext_level: _tl }
3130     }
3131     {
3132         \tl_gset:Nn \g__enumext_item_symbol_aux_tl {#1}
3133     }
3134     \tl_if_novalue:nTF {#2}
3135     {
3136         \dim_set_eq:cc
3137         { \l__enumext_item_symbol_sep_ \l__enumext_level: _dim }
3138         { \l__enumext_labelsep_ \l__enumext_level: _dim }
3139     }
3140     {
3141         \dim_set:cn { \l__enumext_item_symbol_sep_ \l__enumext_level: _dim } {#2}
3142     }
3143     \bool_if:NT \l__enumext_check_answers_bool
3144     {
3145         \int_gincr:N \g__enumext_item_number_int
3146         \bool_set_true:N \l__enumext_item_number_bool
3147     }
3148     \bool_set_true:c { \l__enumext_wrap_label_ \l__enumext_level: _bool }
3149     \l__enumext_item_std:w \tl_use:c { \l__enumext_fake_item_indent_ \l__enumext_level: _tl }
3150 }

```

The function `\l__enumext_item_star_exec:` will be responsible for executing `\item*` for the `enumext` environment.

```

3151 \cs_new_protected:Nn \l__enumext_item_star_exec:
3152 {
3153     \tl_if_empty:cF { \l__enumext_item_symbol_ \l__enumext_level: _tl }
3154     {
3155         \mode_leave_vertical:
3156         \skip_horizontal:n { -\dim_use:c { \l__enumext_item_symbol_sep_ \l__enumext_level: _dim } }
3157         \hbox_overlap_left:n { \g__enumext_item_symbol_aux_tl }
3158         \skip_horizontal:n { \dim_use:c { \l__enumext_item_symbol_sep_ \l__enumext_level: _dim } }
3159     }
3160 }

```

(End of definition for `\l__enumext_starred_item:nn` and `\l__enumext_item_star_exec:`.)

`\l__enumext_redefine_item:`

The function `\l__enumext_redefine_item:` will redefine the `\item` command in the `enumext` environment adding `\item*`. This function are passed to `\l__enumext_list_arg_two_X:` used in the definition of the `enumext` environment (§13.38).

```

3161 \cs_new_protected:Nn \l__enumext_redefine_item:
3162 {
3163     \RenewDocumentCommand \item { s o o }
3164     {

```

```

3165         \bool_if:nTF {##1}
3166         {
3167             \__enumext_starred_item:nn {##2} {##3}
3168         }
3169         { \__enumext_default_item:n {##2} }
3170     }
3171 }

```

(End of definition for `\__enumext_redefine_item:`)

When *tagged* PDF is active `\makeLabel` is redefined as `\hss #1` and the only way to get the `align` key to work correctly is by using `\makebox`. The solution here is to redefine `\makeLabel` conditionally using `\IfDocumentMetadataTF`.

```

\__enumext_make_label:
\__enumext_make_label_std:
\__enumext_make_label_box:

```

The function `\__enumext_make_label:` redefine `\makeLabel` for the keys `align`, `font`, `wrap-label`, `wrap-label*` and `\item*` for `enumext` environment. This function are passed to `\__enumext_list_arg_two_X:` used in the definition of the `enumext` environment (§13.38).

```

3172 \cs_new_protected:Nn \__enumext_make_label:
3173 {
3174     \IfDocumentMetadataTF
3175     {
3176         \__enumext_make_label_box:
3177     }
3178     {
3179         \bool_if:NTF \l__enumext_mode_box_bool
3180         {
3181             \__enumext_make_label_box:
3182         }
3183         {
3184             \__enumext_make_label_std:
3185         }
3186     }
3187 }

```

Standard definition when `\DocumentMetadata` is not active.

```

3188 \cs_new_protected:Nn \__enumext_make_label_std:
3189 {
3190     \RenewDocumentCommand \makeLabel { m }
3191     {
3192         \tl_use:c { l__enumext_label_fill_left_ \__enumext_level: _tl }
3193         \tl_use:c { l__enumext_label_font_style_ \__enumext_level: _tl }
3194         \bool_if:cTF { l__enumext_wrap_label_ \__enumext_level: _bool }
3195         {
3196             \__enumext_item_star_exec:
3197             \use:c { __enumext_wrapper_label_ \__enumext_level: :n } { ##1 }
3198         }
3199         { ##1 }
3200         \tl_use:c { l__enumext_label_fill_right_ \__enumext_level: _tl }
3201         \tl_gclear:N \g__enumext_item_symbol_aux_tl
3202     }
3203 }

```

Definition using `\makebox` when `\DocumentMetadata` is active.

```

3204 \cs_new_protected:Nn \__enumext_make_label_box:
3205 {
3206     \RenewDocumentCommand \makeLabel { m }
3207     {
3208         \makebox
3209         [ \dim_use:c { l__enumext_labelwidth_ \__enumext_level: _dim } ]
3210         [ \str_use:c { l__enumext_align_label_pos_ \__enumext_level: _str } ]
3211         {
3212             \tl_use:c { l__enumext_label_font_style_ \__enumext_level: _tl }
3213             \bool_if:cTF { l__enumext_wrap_label_ \__enumext_level: _bool }
3214             {
3215                 \__enumext_item_star_exec:
3216                 \use:c { __enumext_wrapper_label_ \__enumext_level: :n } { ##1 }
3217             }
3218             { ##1 }
3219             \tl_gclear:N \g__enumext_item_symbol_aux_tl
3220         }
3221     }
3222 }

```

(End of definition for `\__enumext_make_label:`, `\__enumext_make_label_std:`, and `\__enumext_make_label_box:`.)

### 13.34 Setting `item-sym*` and `item-pos*` keys

In order to have a cleaner implementation of `\item*` for the `enumext` and `enumext*` environments it is best to define a couple of keys that allow us to control and set by default the `<symbol>` and its `<offset>`.

```

item-sym* Define and set item-sym* and item-pos* keys for enumext and enumext*.
item-pos*
3223 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
3224 {
3225   \keys_define:nn { enumext / #1 }
3226   {
3227     item-sym* .tl_set:c = { l__enumext_item_symbol_#2_tl },
3228     item-sym* .value_required:n = true,
3229     item-sym* .initial:n = {\textasteriskcentered},
3230     item-pos* .dim_set:c = { l__enumext_item_symbol_sep_#2_dim },
3231     item-pos* .value_required:n = true,
3232   }
3233 }
3234 \clist_map_inline:nn
3235 {
3236   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {enumext*}{vii}
3237 }
3238 { \__enumext_tmp:nn #1 }
```

(End of definition for `item-sym*` and `item-pos*`.)

### 13.35 Handling unknown keys

At this point in the code I already know that I will not add more `<keys>` and since I have already been quite *paranoid and restrictive* with the definitions of environments and commands, the only thing left to do is do it with the `<keys>` (you have to be consistent in life).

#### 13.35.1 Handling unknown keys for `keyans` and `keyans*`

Define and set `unknown` key for `keyans` and `keyans*` environments.

```

__enumext_keyans_unknown_keys:n
__enumext_keyans_unknown_keys:nn
3239 \cs_set_protected:Npn \__enumext_tmp:n #1
3240 {
3241   \keys_define:nn { enumext / #1 }
3242   {
3243     unknown .code:n = { \__enumext_keyans_unknown_keys:n {##1} }
3244   }
3245 }
3246 \clist_map_inline:nn { keyans, keyans* } { \__enumext_tmp:n {#1} }
```

Internal functions for handling `unknown` key.

```

3247 \cs_new_protected:Npn \__enumext_keyans_unknown_keys:n #1
3248 {
3249   \exp_args:NV \__enumext_keyans_unknown_keys:nn \l_keys_key_str {#1}
3250 }
3251 \cs_new_protected:Npn \__enumext_keyans_unknown_keys:nn #1#2
3252 {
3253   \tl_if_blank:nTF {#2}
3254   {
3255     \msg_error:nnn { enumext } { keyans-unknown-key } {#1}
3256   }
3257   {
3258     \msg_error:nnnn { enumext } { keyans-unknown-key-value } {#1} {#2}
3259   }
3260 }
```

(End of definition for `unknown`, `\__enumext_keyans_unknown_keys:n`, and `\__enumext_keyans_unknown_keys:nn`.)

#### 13.35.2 Handling unknown keys for `enumext*`

Define and set `unknown` key for `enumext*` environment.

```

__enumext_starred_unknown_keys:n
__enumext_starred_unknown_keys:nn
3261 \keys_define:nn { enumext / enumext* }
3262 {
3263   unknown .code:n = { \__enumext_starred_unknown_keys:n {#1} }
3264 }
```

Internal functions for handling `unknown` key.

```

3265 \cs_new_protected:Npn \__enumext_starred_unknown_keys:n #1
3266 {
3267   \exp_args:NV \__enumext_starred_unknown_keys:nn \l_keys_key_str {#1}
3268 }
3269 \cs_new_protected:Npn \__enumext_starred_unknown_keys:nn #1#2
3270 {
3271   \tl_if_blank:nTF {#2}
3272   {
3273     \msg_error:nnn { enumext } { starred-unknown-key } {#1}
3274   }
3275   {
3276     \msg_error:nnnn { enumext } { starred-unknown-key-value } {#1} {#2}
3277   }
3278 }

```

(End of definition for `unknown`, `\__enumext_starred_unknown_keys:n`, and `\__enumext_starred_unknown_keys:nn`.)

### 13.35.3 Handling unknown keys for enumext

Defines and set the key `unknown` for `enumext` environment.

```

unknown
\__enumext_standar_unknown_keys:n
\__enumext_standar_unknown_keys:nn
3279 \cs_set_protected:Npn \__enumext_tmp:n #1
3280 {
3281   \keys_define:nn { enumext / #1 }
3282   {
3283     unknown .code:n = { \__enumext_standar_unknown_keys:n {##1} }
3284   }
3285 }
3286 \clist_map_inline:nn { level-1,level-2,level-3,level-4 } { \__enumext_tmp:n {#1} }

```

Internal functions for handling `unknown` key.

```

3287 \cs_new_protected:Npn \__enumext_standar_unknown_keys:n #1
3288 {
3289   \exp_args:NV \__enumext_standar_unknown_keys:nn \l_keys_key_str {#1}
3290 }
3291 \cs_new_protected:Npn \__enumext_standar_unknown_keys:nn #1#2
3292 {
3293   \tl_if_blank:nTF {#2}
3294   {
3295     \msg_error:nnn { enumext } { standar-unknown-key } {#1}
3296   }
3297   {
3298     \msg_error:nnnn { enumext } { standar-unknown-key-value } {#1} {#2}
3299   }
3300 }

```

(End of definition for `unknown`, `\__enumext_standar_unknown_keys:n`, and `\__enumext_standar_unknown_keys:nn`.)

### 13.36 Redefining `\item` and `\makeLabel` in keyans

The `\item` and `\item[⟨custom⟩]` commands work in the usual way in `keyans`, but the `\item*` and `\item*[⟨content⟩]` commands *store* the current `⟨label⟩` next to the `⟨content⟩` if it is present in the *sequence* and *prop list* defined by `save-ans` key.

The function `\__enumext_keyans_default_item:n` executes the original behavior of the `\item` along with the keys `wrap-label`, `wrap-label*` and `itemindent`.

```

3301 \cs_new_protected:Npn \__enumext_keyans_default_item:n #1
3302 {
3303   \tl_if_novalue:nTF { #1 }
3304   {
3305     \bool_set_true:N \__enumext_wrap_label_v_bool
3306     \__enumext_item_std:w \tl_use:N \__enumext_fake_item_indent_v_tl
3307   }
3308   {
3309     \bool_set_eq:NN \__enumext_wrap_label_v_bool \__enumext_wrap_label_opt_v_bool
3310     \__enumext_item_std:w [#1] \tl_use:N \__enumext_fake_item_indent_v_tl
3311   }
3312 }

```

(End of definition for `\__enumext_keyans_default_item:n`.)

`\__enumext_keyans_starred_item:n` The function `\__enumext_keyans_starred_item:n` which will make a temporary copy of the current `<label>`, execute the `show-ans` or `show-pos` keys using the function `\__enumext_keyans_show_left:n` and will display the `<contents>` of that item using the internal copy `\__enumext_item_std:w`, this is necessary to prevent incrementing the current “counter” of the original `<label>`, followed by this it will execute function `\__enumext_keyans_show_item_opt:` handled by `wrap-opt` key.

```

3313 \cs_new_protected:Npn \__enumext_keyans_starred_item:n #1
3314 {
3315     \tl_set_eq:NN \l__enumext_store_current_label_tmp_tl \l__enumext_label_v_tl
3316     \__enumext_keyans_show_left:n { #1 }
3317     \bool_set_true:N \l__enumext_wrap_label_v_bool
3318     \__enumext_item_std:w \tl_use:N \l__enumext_fake_item_indent_v_tl
3319     \__enumext_keyans_show_item_opt:

```

Recover the original value of the current `<label>` and store it first in the *prop list* (including the *optional argument*), run the internal “label and ref” system if the `save-ref` key is active, store it in the *sequence* and finally increments `\g__enumext_check_starred_cmd_int` for internal check system.

```

3320     \tl_set_eq:NN \l__enumext_label_v_tl \l__enumext_store_current_label_tmp_tl
3321     \__enumext_keyans_addto_prop:n { #1 }
3322     \__enumext_keyans_store_ref:
3323     \__enumext_keyans_addto_seq:n { #1 }
3324     \int_gincr:N \g__enumext_check_starred_cmd_int
3325 }

```

(End of definition for `\__enumext_keyans_starred_item:n`.)

`\item*` The function `\__enumext_keyans_redefine_item:` is responsible for adding the *starred argument* and *optional argument* by the `\__enumext_list_arg_two_v:` function in the definition of the `keyans` environment. Here we need to use `\peek_remove_spaces:n` to prevent an unwanted space when using `\item*` in conjunction with the `itemindent` key. This function are passed to `\__enumext_list_arg_two_v:` used in the definition of the `keyans` environment (§13.37.2).

`\__enumext_keyans_redefine_item:`

```

3326 \cs_new_protected:Nn \__enumext_keyans_redefine_item:
3327 {
3328     \RenewDocumentCommand \item { s o }
3329     {
3330         \bool_if:NTF {##1}
3331         {
3332             \peek_remove_spaces:n
3333             {
3334                 \__enumext_keyans_starred_item:n {##2}
3335             }
3336         }
3337         {
3338             \__enumext_keyans_default_item:n {##2}
3339         }
3340     }
3341 }

```

(End of definition for `\item*` and `\__enumext_keyans_redefine_item:`. This function is documented on page 14.)

`\__enumext_keyans_make_label:`  
`\__enumext_keyans_make_label_std:`  
`\__enumext_keyans_make_label_box:`

The function `\__enumext_keyans_make_label:` redefine `\makeLabel` for the keys `align`, `font`, `wrap-label`, `wrap-label*` and `\item*` for `keyans` environment. This function are passed to `\__enumext_list_arg_two_v:` used in the definition of the `keyans` environment (§13.37.2).

```

3342 \cs_new_protected:Nn \__enumext_keyans_make_label:
3343 {
3344     \IfDocumentMetadataTF
3345     {
3346         \__enumext_keyans_make_label_box:
3347     }
3348     {
3349         \bool_if:NTF \l__enumext_mode_box_bool
3350         {
3351             \__enumext_keyans_make_label_box:
3352         }
3353         {
3354             \__enumext_keyans_make_label_std:
3355         }
3356     }
3357 }

```



Standard definition when `\DocumentMetadata` is not active.

```

3358 \cs_new_protected:Nn \__enumext_keyans_make_label_std:
3359 {
3360   \RenewDocumentCommand \makeLabel { m }
3361   {
3362     \tl_use:N \l__enumext_label_fill_left_v_tl
3363     \tl_use:N \l__enumext_label_font_style_v_tl
3364     \bool_if:NTF \l__enumext_wrap_label_v_bool
3365     {
3366       \__enumext_wrapper_label_v:n { ##1 }
3367     }
3368     { ##1 }
3369     \tl_use:N \l__enumext_label_fill_right_v_tl
3370   }
3371 }

```

Definition using `\makebox` when `\DocumentMetadata` is active.

```

3372 \cs_new_protected:Nn \__enumext_keyans_make_label_box:
3373 {
3374   \RenewDocumentCommand \makeLabel { m }
3375   {
3376     \makebox[ \l__enumext_labelwidth_v_dim ][ \l__enumext_align_label_pos_v_str ]
3377     {
3378       \tl_use:N \l__enumext_label_font_style_v_tl
3379       \bool_if:NTF \l__enumext_wrap_label_v_bool
3380       {
3381         \__enumext_wrapper_label_v:n { ##1 }
3382       }
3383       { ##1 }
3384     }
3385   }
3386 }

```

(End of definition for `\__enumext_keyans_make_label:`, `\__enumext_keyans_make_label_std:`, and `\__enumext_keyans_make_label_box:`.)

### 13.37 Second argument of the lists

At this point of the code we have already programmed most the necessary tools to create a custom `list` environment, remember that the function `\__enumext_start_list:nn` takes two arguments, the first one we have ready, the second one we will define for all the levels of the environment `enumext` and the environment `keyans`.

#### 13.37.1 Calculation of `\leftmargin` and `\itemindent`

Consider the figure 9 where the default margins (on the left) of a list are represented.




Figure 9: Representation of standard horizontal lengths in `list` environment.

The idea is to have control over these margins so that our list does not overlap the left margin of the page. The *key* relationship is that the right edge of the `\labelsep` equals the right edge of the `\itemindent`, so that the left edge of the *label box* is at `\leftmargin + \itemindent` minus `\labelwidth + \labelsep`. Thus, the handling of the margins by the package will be as shown in the figure 10.




Figure 10: Representation of horizontal lengths concept in list in `enumext`.


Where the default values will look like in the figure 11.

```

\__enumext_calc_hspace:NNNNNNN
\__enumext_calc_hspace:ccccc

```

The function `\__enumext_calc_hspace:NNNNNNN` takes seven arguments to be able to determine horizontal spaces for all list environment:

Figure 11: Default horizontal lengths in `enumext`.

```

#1: \l__enumext_labelwidth_X_dim          #2: \l__enumext_labelsep_X_dim
#3: \l__enumext_listoffset_X_dim          #4: \l__enumext_leftmargin_tmp_X_dim
#5: \l__enumext_leftmargin_X_dim          #6: \l__enumext_itemindent_X_dim
#7: \l__enumext_leftmargin_tmp_X_bool

```

And returns the “adjusted” values of `\leftmargin` and `\itemindent`.

This function is passed to `\__enumext_list_arg_two_X`: which is used in the definition of the `enumext` and `keyans` environments (§13.37.2).

```

3387 \cs_new_protected:Npn \__enumext_calc_hspace:NNNNNNN #1 #2 #3 #4 #5 #6 #7
3388 {
3389   \dim_compare:nNnT { #1 } < { \c_zero_dim }
3390   {
3391     \msg_warning:nnnV { enumext } { width-non-positive } { labelwidth } { #1 }
3392     \dim_set:Nn #1 { \dim_abs:n { #1 } }
3393   }
3394   \dim_compare:nNnT { #2 } < { \c_zero_dim }
3395   {
3396     \msg_warning:nnnV { enumext } { width-negative } { labelsep } { #2 }
3397     \dim_set:Nn #2 { \dim_abs:n { #2 } }
3398   }

```

If no value has been passed to the `labelwidth` and `labelsep` keys we set the default values for `\l__enumext_leftmargin_tmp_X_dim`.

```

3399   \bool_if:nF #7 { \dim_set:Nn #4 { #1 + #2 } }

```

We now analyze the cases and set the values for `\leftmargin` and `\itemindent`.

```

3400   \dim_compare:nNnTF { #4 } < { \c_zero_dim }
3401   {
3402     \dim_set:Nn #6 { #1 + #2 - #4 }
3403     \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
3404   }
3405   {
3406     \dim_compare:nNnT { #4 } = { #1 + #2 }
3407     { \dim_set:Nn #6 { \c_zero_dim } }
3408     \dim_compare:nNnT { #4 } < { #1 + #2 }
3409     { \dim_set:Nn #6 { #1 + #2 - #4 } }
3410     \dim_compare:nNnT { #4 } > { #1 + #2 }
3411     {
3412       \dim_set:Nn #6 { -#1 - #2 + #4 }
3413       \dim_set:Nn #6 { #6*-1 }
3414     }
3415     \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
3416   }
3417 }
3418 \cs_generate_variant:Nn \__enumext_calc_hspace:NNNNNNN { ccccccc }

```

(End of definition for `\__enumext_calc_hspace:NNNNNNN`.)

### 13.37.2 Setting second argument of the lists

We will “not set” `\leftmargini`, `\leftmarginii`, `\leftmarginiii` or `\leftmarginiv`, in this case, we will directly set the parameters for vertical and horizontal list spacing per level.

```

\__enumext_list_arg_two_i:
\__enumext_list_arg_two_ii:
\__enumext_list_arg_two_iii:
\__enumext_list_arg_two_iv:
\__enumext_list_arg_two_v:
3419 \cs_set_protected:Npn \__enumext_tmp:n #1
3420 {
3421   \cs_new_protected:cpn { __enumext_list_arg_two_#1: }
3422   {
3423     \__enumext_calc_hspace:ccccccc
3424     { \__enumext_labelwidth_#1_dim } { \__enumext_labelsep_#1_dim }
3425     { \__enumext_listoffset_#1_dim } { \__enumext_leftmargin_tmp_#1_dim }
3426     { \__enumext_leftmargin_#1_dim } { \__enumext_itemindent_#1_dim }
3427     { \__enumext_leftmargin_tmp_#1_bool }

```

```

3428 \clist_map_inline:nn
3429 { labelsep, labelwidth, itemindent, leftmargin, rightmargin, listparindent }
3430 { \dim_set_eq:cc {####1} { \__enumext_####1_#1_dim } }
3431 \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
3432 { \skip_set_eq:cc {####1} { \__enumext_####1_#1_skip } }
3433 \usecounter { enumX#1 }
3434 \setcounter { enumX#1 } { \int_eval:n { \int_use:c { \__enumext_start_#1_int } - 1 } }
3435 \str_if_eq:nnTF {#1} { v }
3436 {
3437   \__enumext_keyans_redefine_item:
3438   \__enumext_keyans_make_label:
3439   \__enumext_keyans_ref:
3440   \__enumext_keyans_fake_item_indent:
3441   \bool_if:cT { \__enumext_show_length_#1_bool }
3442   {
3443     \msg_term:nnnn { enumext } { list-lengths-not-nested } { v } { keyans }
3444   }
3445 }
3446 {
3447   \__enumext_redefine_item:
3448   \__enumext_make_label:
3449   \__enumext_standar_ref:
3450   \__enumext_fake_item_indent:
3451   \bool_if:cT { \__enumext_show_length_#1_bool }
3452   {
3453     \msg_term:nnne { enumext } { list-lengths } {#1}
3454     { \int_use:N \__enumext_level_int }
3455   }
3456 }
3457 }
3458 }
3459 \clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }

```

(End of definition for \\_\_enumext\_list\_arg\_two\_i: and others.)

```

\__enumext_list_arg_two_vii:
\__enumext_list_arg_two_viii:

```

For the horizontal environments `enumext*` and `keyans*` the implementation is similar, but, the value of `\partopsep` is always `0pt`. At this point we will modify the `parsep` key to make it take the value of the `itemsep` key and later, in the environment definition, we will modify `parindent` to make it set the value of `lisparindent` and `parsep` to set the value of `\parskip` locally.

```

3460 \cs_set_protected:Npn \__enumext_tmp:n #1
3461 {
3462   \cs_new_protected:cpn { __enumext_list_arg_two_#1: }
3463   {
3464     \bool_set_true:c { \__enumext_leftmargin_tmp_#1_bool }
3465     \dim_zero:c { \__enumext_leftmargin_tmp_#1_dim }
3466     \__enumext_calc_hspace:cccccc
3467     { \__enumext_labelwidth_#1_dim } { \__enumext_labelsep_#1_dim }
3468     { \__enumext_listoffset_#1_dim } { \__enumext_leftmargin_tmp_#1_dim }
3469     { \__enumext_leftmargin_#1_dim } { \__enumext_itemindent_#1_dim }
3470     { \__enumext_leftmargin_tmp_#1_bool }
3471   \clist_map_inline:nn
3472   { labelsep, labelwidth, itemindent, leftmargin, rightmargin, listparindent }
3473   { \dim_set_eq:cc {####1} { \__enumext_####1_#1_dim } }
3474   \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
3475   { \skip_set_eq:cc {####1} { \__enumext_####1_#1_skip } }
3476   \skip_set_eq:Nc \parsep { \__enumext_itemsep_#1_skip }
3477   \skip_zero:N \partopsep
3478   \usecounter { enumX#1 }
3479   \setcounter { enumX#1 } { \int_eval:n { \int_use:c { \__enumext_start_#1_int } - 1 } }
3480   \__enumext_starred_ref:
3481   \str_if_eq:nnTF {#1} { vii }
3482   {
3483     \__enumext_fake_item_indent_vii:
3484     \bool_if:cT { \__enumext_show_length_vii_bool }
3485     { \msg_term:nnnn { enumext } { list-lengths-not-nested } { vii } { enumext* } }
3486   }
3487   {
3488     \__enumext_fake_item_indent_viii:
3489     \bool_if:cT { \__enumext_show_length_#1_bool }
3490     { \msg_term:nnnn { enumext } { list-lengths-not-nested } { #1 } { keyans* } }
3491   }

```

```

3492     }
3493 }
3494 \clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for \\_\_enumext\_list\_arg\_two\_vii: and \\_\_enumext\_list\_arg\_two\_viii:.)

### 13.38 The environment enumext

\\_\_enumext\_safe\_exec: The \\_\_enumext\_safe\_exec: function first call the function \\_\_enumext\_internal\_mini\_page: to create the environment `\__enumext_mini_page`, then the function \\_\_enumext\_is\_not\_nested: which sets \g\_\_enumext\_standar\_bool to “true” if we are not nested within `enumext*`, we will increment \l\_\_enumext\_level\_int to restrict nesting of the environment, set \l\_\_enumext\_standar\_bool to “true” and finally call the function \\_\_enumext\_is\_on\_first\_level: which sets \l\_\_enumext\_standar\_first\_bool to “true” only if the environment is not nested and we are at the “first level”.

```

3495 \cs_new_protected:Nn \__enumext_safe_exec:
3496 {
3497   \__enumext_internal_mini_page:
3498   \__enumext_is_not_nested:
3499   \int_incr:N \l__enumext_level_int
3500   \int_compare:nNt { \l__enumext_level_int } > { 4 }
3501   { \msg_fatal:nn { enumext } { list-too-deep } }
3502   \bool_set_true:N \l__enumext_standar_bool
3503   \bool_set_false:N \l__enumext_starred_bool
3504   \__enumext_is_on_first_level:
3505 }

```

(End of definition for \\_\_enumext\_safe\_exec:.)

\\_\_enumext\_parse\_keys:n The \\_\_enumext\_parse\_store\_keys:n function first we will clear the variable \l\_\_enumext\_series\_str used by the key `series` and then we check if we are at the “first level”, if so we process the *⟨keys⟩* and then execute the function \\_\_enumext\_parse\_series:n used by the key `series` and call the function \\_\_enumext\_nested\_base\_line\_fix: used by the key `base-fix`, otherwise we will pass the *⟨keys⟩* to the inner levels of the environment then we execute the function \\_\_enumext\_store\_active\_keys:n and reprocess the *⟨keys⟩* to pass them to the *sequence* if the key `save-key` is not active.

```

3506 \cs_new_protected:Npn \__enumext_parse_keys:n #1
3507 {
3508   \tl_if_novalue:nF {#1}
3509   {
3510     \str_clear:N \l__enumext_series_str
3511     \int_compare:nNtF { \l__enumext_level_int } = { 1 }
3512     {
3513       \keys_set:nn { enumext / level-1 } {#1}
3514       \__enumext_parse_series:n {#1}
3515       \__enumext_nested_base_line_fix:
3516     }
3517     {
3518       \exp_args:Ne \keys_set:nn
3519       { enumext / level-\int_use:N \l__enumext_level_int } {#1}
3520     }
3521     \__enumext_store_active_keys:n {#1}
3522   }
3523 }

```

(End of definition for \\_\_enumext\_parse\_keys:n.)

\\_\_enumext\_start\_store\_level: The \\_\_enumext\_start\_store\_level: function activate the “storing structure” mechanism in the *sequence* for the command \anskey and the environment `anskey*`.

```

3524 \cs_new_protected:Nn \__enumext_start_store_level:
3525 {
3526   \bool_lazy_all:nT
3527   {
3528     { \bool_if_p:N \l__enumext_store_active_bool }
3529     { \bool_not_p:n { \l__enumext_keyans_env_bool } }
3530     { \bool_if_p:N \g__enumext_standar_bool }
3531   }
3532   {
3533     \int_compare:nNt { \l__enumext_level_int } > { 1 }
3534     {
3535       \bool_set_true:c { l__enumext_store_upper_level_ \__enumext_level: _bool }
3536       \__enumext_store_level_open:
3537     }
3538   }

```

If `enumext` are nested in `enumext*` add `\__enumext_store_level_open:` to preserve the “*storing structure*”.

```

3539   \bool_lazy_all:nT
3540   {
3541     { \bool_if_p:N \__enumext_store_active_bool }
3542     { \bool_not_p:n { \__enumext_keyans_env_bool } }
3543     { \int_compare_p:nNn { \__enumext_level_h_int } = { 1 } }
3544   }
3545   {
3546     \int_compare:nNnT { \__enumext_level_int } > { 0 }
3547     {
3548       \bool_set_true:c { \__enumext_store_upper_level_ \__enumext_level: _bool }
3549       \__enumext_store_level_open:
3550     }
3551   }
3552 }

```

(End of definition for `\__enumext_start_store_level:`.)

`\__enumext_stop_store_level:` The `\__enumext_stop_store_level:` function stop the “*storing structure*” mechanism in the *sequence* for the command `\anskey` and the environment `anskey*`.

```

3553 \cs_new_protected:Nn \__enumext_stop_store_level:
3554 {
3555   \bool_if:cT { \__enumext_store_upper_level_ \__enumext_level: _bool }
3556   {
3557     \__enumext_store_level_close:
3558   }
3559 }

```

(End of definition for `\__enumext_stop_store_level:`.)

`\__enumext_multicols_start:` The function `\__enumext_multicols_start:` will start the `multicols` environment according to the value passed by the `columns` key, then set the default value for `\columnsep` when `columns-sep=opt` and set the value of `\multicolsep` equal to zero and leave `\columnseprule` equal to zero for inner levels.

```

3560 \cs_new_protected:Nn \__enumext_multicols_start:
3561 {
3562   \int_compare:nNnT
3563   { \int_use:c { \__enumext_columns_ \__enumext_level: _int } } > { 1 }
3564   {
3565     \dim_compare:nNnT
3566     { \dim_use:c { \__enumext_columns_sep_ \__enumext_level: _dim } } = { \c_zero_dim }
3567     {
3568       \dim_set:cn { \__enumext_columns_sep_ \__enumext_level: _dim }
3569       {
3570         ( \dim_use:c { \__enumext_labelwidth_ \__enumext_level: _dim }
3571         + \dim_use:c { \__enumext_labelsep_ \__enumext_level: _dim }
3572         ) / \int_use:c { \__enumext_columns_ \__enumext_level: _int }
3573         - \dim_use:c { \__enumext_listoffset_ \__enumext_level: _dim }
3574       }
3575     }
3576     \dim_set_eq:Nc \columnsep { \__enumext_columns_sep_ \__enumext_level: _dim }
3577     \int_compare:nNnT { \__enumext_level_int } > { 1 }
3578     {
3579       \dim_zero:N \columnseprule
3580     }
3581   }
3582 }

```

We will calculate the *vertical spacing* settings for the `multicols` environment using the function `\__enumext_multi_addvspace:`, apply our “*vertical adjust spacing*”, then start the `multicols` environment.

```

3581   \bool_if:cF { \__enumext_minipage_active_ \__enumext_level: _bool }
3582   {
3583     \skip_zero:N \multicolsep
3584     \__enumext_multi_addvspace:
3585   }
3586   \raggedcolumns
3587   \begin{multicols}{ \int_use:c { \__enumext_columns_ \__enumext_level: _int } }
3588 }
3589 }

```

(End of definition for `\__enumext_multicols_start:`.)

`\__enumext_multicols_stop:` The function `\__enumext_multicols_stop:` will stop the `multicols` environment and apply our “vertical adjust” spacing. For compatibility with *tagged* PDF, the closing of the `list` environment is executed here along with `\__enumext_stop_store_level:`.

```

3590 \cs_new_protected:Nn \__enumext_multicols_stop:
3591 {
3592   \int_compare:nNtF
3593     { \int_use:c { \__enumext_columns_ \__enumext_level: _int } } > { 1 }
3594   {
3595     \__enumext_stop_list:
3596     \__enumext_stop_store_level:
3597     \end{multicols}
3598     \__enumext_unskip_unkern:
3599     \__enumext_unskip_unkern:
3600     \par\addvspace{ \skip_use:c { \__enumext_multicols_below_ \__enumext_level: _skip } }
3601   }
3602   {
3603     \__enumext_stop_list:
3604     \__enumext_stop_store_level:
3605   }
3606 }

```

(End of definition for `\__enumext_multicols_stop:`)

`\__enumext_before_list:` The function `\__enumext_before_list:` first calls the function `\__enumext_vspace_above:` used by the keys `above` and `above*`, then calls the function `\__enumext_before_args_exec:` used by the key `before*` and finally execute the function `\__enumext_check_ans_active:` for the check answer mechanism.

```

3607 \cs_new_protected:Nn \__enumext_before_list:
3608 {
3609   \__enumext_vspace_above:
3610   \__enumext_before_args_exec:
3611   \__enumext_check_ans_active:

```

When the `mini-env` key is active it will set the value of the `\l__enumext_minipage_right_X_dim` to be the *width* of the `__enumext_mini_page` environment on the “right side”, using this value together with the value of the `\l__enumext_minipage_hsep_X_dim` set by the `mini-sep` key, the value of `\l__enumext_minipage_left_X_dim` will be set, which will be the *width* of `__enumext_mini_page` environment on the “left side”, always having a current `\linewidth` as *maximum width* between them.

```

3612 \dim_compare:nNt
3613   { \dim_use:c { \__enumext_minipage_right_ \__enumext_level: _dim } } > { \c_zero_dim }
3614   {
3615     \dim_set:cn { \__enumext_minipage_left_ \__enumext_level: _dim }
3616     {
3617       \linewidth
3618       - \dim_use:c { \__enumext_minipage_right_ \__enumext_level: _dim }
3619       - \dim_use:c { \__enumext_minipage_hsep_ \__enumext_level: _dim }
3620     }

```

The boolean variable `\l__enumext_minipage_active_X_bool` will be activated and the integer variable `\g__enumext_minipage_stat_int` used by the `\miniright` command will be incremented, then the function `\__enumext_minipage_add_space:` is called and the `__enumext_mini_page` environment on the “left side” will be initialized followed by the “vertical spacing” applied to preserve the “baseline” between the *left* and *right* side environments. After these actions, the function `\__enumext_multicols_start:` is called to handle the `multicols` environment.

```

3621   \bool_set_true:c { \__enumext_minipage_active_ \__enumext_level: _bool }
3622   \int_gincr:N \g__enumext_minipage_stat_int
3623   \__enumext_minipage_add_space:
3624   \noindent
3625   \__enumext_mini_page{ \dim_use:c { \__enumext_minipage_left_ \__enumext_level: _dim } }
3626 }
3627 \__enumext_multicols_start:
3628 }

```

(End of definition for `\__enumext_before_list:`)

`\__enumext_second_part:` The function `\__enumext_second_part:` first check the state of the boolean variable `\l__enumext_minipage_active_X_bool`, if it is “true” a small test will be executed to check if we have omitted the use of `\miniright` (the `__enumext_mini_page` environment has not been closed), then close `__enumext_mini_page` and add the *adjusted vertical space* `\l__enumext_minipage_after_skip`, otherwise we will close the `multicols` environment.

```

3629 \cs_new_protected:Nn \__enumext_second_part:

```

```

3630 {
3631   \bool_if:cTF { l__enumext_minipage_active_ \__enumext_level: _bool }
3632   {
3633     \int_compare:nNt { \g__enumext_minipage_stat_int } = { 1 }
3634     {
3635       \msg_warning:nn { enumext } { missing-miniright }
3636       \miniright
3637     }
3638     \int_gzero:N \g__enumext_minipage_stat_int
3639     \__enumext_unskip_unkern: % remove topsep + [partopsep]
3640     \end__enumext_mini_page
3641   }
3642   {
3643     \__enumext_multicols_stop:
3644   }

```

Now we will execute the functions `\__enumext_after_stop_list:` used by the key `after`, `\__enumext_check_ans_key_hook:` used by the key `check-ans`, `\__enumext_vspace_below:` used by the keys `below` and `below*`. Finally set `\l__enumext_standar_bool` to false and call the function `\__enumext_resume_save_counter:` used by the `series`, `resume` and `resume*` keys.

```

3645   \__enumext_after_stop_list:
3646   \__enumext_check_ans_key_hook:
3647   \__enumext_vspace_below:
3648   \bool_set_false:N \l__enumext_standar_bool
3649   \__enumext_resume_save_counter:
3650 }

```

(End of definition for `\__enumext_second_part:`.)

`\__enumext_set_item_width:` The function `\__enumext_set_item_width:` will set the value of `\itemwidth` taking into account the value established by the `list-offset` key for each level of the environment.

```

3651 \cs_new_protected:Nn \__enumext_set_item_width:
3652 {
3653   \dim_set:Nn \itemwidth { \linewidth }
3654   \dim_compare:nT
3655   {
3656     \dim_use:c { l__enumext_listoffset_ \__enumext_level: _dim } != \c_zero_dim
3657   }
3658   {
3659     \dim_sub:Nn \itemwidth
3660     {
3661       \dim_use:c { l__enumext_listoffset_ \__enumext_level: _dim }
3662     }
3663   }
3664 }

```

(End of definition for `\__enumext_set_item_width:`.)

**enumext** Now create the `enumext` environment based on `list` environment by levels.

```

3665 \NewDocumentEnvironment{enumext}{0}{}
3666 {
3667   \__enumext_safe_exec:
3668   \__enumext_parse_keys:n {#1}
3669   \__enumext_before_list:
3670   \__enumext_start_store_level:
3671   \__enumext_start_list:nn
3672   { \tl_use:c { l__enumext_label_ \__enumext_level: _tl } }
3673   {
3674     \use:c { __enumext_list_arg_two_ \__enumext_level: : }
3675     \__enumext_before_keys_exec:
3676   }
3677   \__enumext_set_item_width:
3678   \__enumext_after_args_exec:
3679 }
3680 {
3681   \__enumext_second_part:
3682 }

```

(End of definition for `enumext`. This function is documented on page 5.)

As we don't want our check to be executed `check-ans` by levels but on the complete list, we will take it out of the `enumext` environment using the “hook” function `\__enumext_after_env:nn`.



```

3683 \__enumext_after_env:nn {enumext}
3684 {
3685   \__enumext_execute_after_env:
3686 }

```

### 13.39 The environment keyans

The environment `keyans` also based on lists. The main differences with the `enumext` environment are the *nesting* and the way the *answers* (choice) will be stored and checked, this environment is intended exclusively for “multiple choice questions”.

The `keyans` environment will only be available if the `save-ans` key is active and can only be used at the “first level” within the `enumext` environment. We do not want the environment to be nested, so we will set a maximum at this point. If the conditions are not met, an error message will be returned.

```

3687 \cs_new_protected:Nn \__enumext_keyans_safe_exec:
3688 {
3689   \bool_if:NF \l__enumext_store_active_bool
3690   {
3691     \msg_error:nnnn { enumext } { wrong-place } { keyans } { save-ans }
3692   }
3693   \int_incr:N \l__enumext_keyans_level_int
3694   \bool_set_true:N \l__enumext_keyans_env_bool
3695   \__enumext_keyans_name_and_start:
3696   % Set false for interfering with enumext nested in keyans (yes, its possible and crayze)
3697   \bool_set_false:N \l__enumext_store_active_bool
3698   \int_compare:nNnT { \l__enumext_keyans_level_int } > { 1 }
3699   {
3700     \msg_error:nn { enumext } { keyans-nested }
3701   }
3702   \int_compare:nNnT { \l__enumext_level_int } > { 1 }
3703   {
3704     \msg_error:nn { enumext } { keyans-wrong-level }
3705   }
3706 }

```

(End of definition for `\__enumext_keyans_safe_exec:`)

`\__enumext_keyans_parse_keys:n`

Parse [`⟨key = val⟩`] for `keyans` environment.

```

3707 \cs_new_protected:Npn \__enumext_keyans_parse_keys:n #1
3708 {
3709   \keys_set:nn { enumext / keyans } {#1}
3710 }

```

(End of definition for `\__enumext_keyans_parse_keys:n`)

`\__enumext_before_list_v:`

Same implementation as the one used in the `enumext` environment.

`\__enumext_keyans_multicols_start:`

```

3711 \cs_new_protected:Nn \__enumext_before_list_v:

```

`\__enumext_keyans_multicols_stop:`

```

3712 {
3713   \__enumext_vspace_above_v:
3714   \__enumext_before_args_exec_v:
3715   \dim_compare:nNnT { \l__enumext_minipage_right_v_dim } > { \c_zero_dim }
3716   {
3717     \dim_set:Nn \l__enumext_minipage_left_v_dim
3718     {
3719       \linewidth - \l__enumext_minipage_right_v_dim - \l__enumext_minipage_hsep_v_dim
3720     }
3721     \bool_set_true:N \l__enumext_minipage_active_v_bool
3722     \int_gincr:N \g__enumext_minipage_stat_int
3723     \__enumext_keyans_minipage_add_space:
3724     \__enumext_mini_page{ \l__enumext_minipage_left_v_dim }
3725   }
3726   \__enumext_keyans_multicols_start:
3727 }
3728 \cs_new_protected:Nn \__enumext_keyans_multicols_start:
3729 {
3730   \int_compare:nNnT { \l__enumext_columns_v_int } > { 1 }
3731   {
3732     \dim_compare:nNnT { \l__enumext_columns_sep_v_dim } = { \c_zero_dim }
3733     {
3734       \dim_set:Nn \l__enumext_columns_sep_v_dim
3735     }

```

```

3736         (
3737             \l__enumext_labelwidth_v_dim + \l__enumext_labelsep_v_dim
3738         ) / \l__enumext_columns_v_int
3739         - \l__enumext_listoffset_v_dim
3740     }
3741 }
3742 \dim_set_eq:NN \columnsep \l__enumext_columns_sep_v_dim
3743 \dim_zero:N \columnseprule % no rule here
3744 \bool_if:NF \l__enumext_minipage_active_v_bool
3745 {
3746     \skip_zero:N \multicolsep
3747     \__enumext_keyans_multi_addvspace:
3748 }
3749 \raggedcolumns
3750 \begin{multicols}{\l__enumext_columns_v_int}
3751 }
3752 }
3753 \cs_new_protected:Nn \__enumext_keyans_multicols_stop:
3754 {
3755     \int_compare:nNnTF { \l__enumext_columns_v_int } > { 1 }
3756     {
3757         \__enumext_stop_list:
3758         \end{multicols}
3759         \__enumext_unskip_unkern:
3760         \__enumext_unskip_unkern:
3761         \par\addvspace{ \l__enumext_multicols_below_v_skip }
3762     }
3763     {
3764         \__enumext_stop_list:
3765     }
3766 }
3767 \cs_new_protected:Nn \__enumext_second_part_v:
3768 {
3769     \bool_if:NTF \l__enumext_minipage_active_v_bool
3770     {
3771         \int_compare:nNnT { \g__enumext_minipage_stat_int } = { 1 }
3772         {
3773             \msg_warning:nn { enumext } { missing-miniright }
3774             \miniright
3775         }
3776         \int_gzero:N \g__enumext_minipage_stat_int
3777         \__enumext_unskip_unkern: % remove \topsep + [\partopsep]
3778         \end__enumext_mini_page
3779         \par\addvspace{ \l__enumext_minipage_after_skip }
3780     }
3781     {
3782         \__enumext_keyans_multicols_stop:
3783     }
3784     \bool_set_false:N \l__enumext_keyans_env_bool
3785     \__enumext_after_stop_list_v:
3786     \__enumext_vspace_below_v:
3787 }

```

(End of definition for `\__enumext_before_list_v:` and others.)

`\__enumext_keyans_set_item_width:`

The function `\__enumext_keyans_set_item_width:` will set the value of `\itemwidth` taking into account the value established by the `list-offset` key.

```

3788 \cs_new_protected:Nn \__enumext_keyans_set_item_width:
3789 {
3790     \dim_set:Nn \itemwidth { \linewidth }
3791     \dim_compare:nT
3792     {
3793         \l__enumext_listoffset_v_dim != \c_zero_dim
3794     }
3795     {
3796         \dim_sub:Nn \itemwidth { \l__enumext_listoffset_v_dim }
3797     }
3798 }

```

(End of definition for `\__enumext_keyans_set_item_width:`.)

**keyans** Now we define the environment **keyans** also based on lists.

```

3799 \NewDocumentEnvironment{keyans}{0}{ }
3800 {
3801   \__enumext_keyans_safe_exec:
3802   \__enumext_keyans_parse_keys:n {#1}
3803   \__enumext_before_list_v:
3804   \__enumext_start_list:nn
3805   { \tl_use:N \__enumext_label_v_tl }
3806   {
3807     \__enumext_list_arg_two_v:
3808     \__enumext_before_keys_exec_v:
3809   }
3810   \__enumext_keyans_set_item_width:
3811   \__enumext_after_args_exec_v:
3812 }
3813 {
3814   \__enumext_check_starred_cmd:n { item }
3815   \__enumext_second_part_v:
3816 }

```

(End of definition for *keyans*. This function is documented on page 14.)

### 13.40 Tagging PDF support for non-standart list environments

The  $\TeX$  release 2022-06-01 brings automatic support for *tagged* PDF in several aspects, including the standard *list environments* and the **list** environment. Unfortunately non-standard *list environments* like **keyanspic** or the horizontal list environments **enumext\*** and **keyans\*** are not structured in a nice way, i.e. the expected result in the PDF file is the expected one, but the underlying structure is not correct. In simple terms, for *tagged* PDF a **list** environment is a **list** environment, no matter what it looks like in the PDF file.

To maintain a correct **list** structure when `\DocumentMetadata` is active, it is necessary to do some things manually. This implementation is an adaptation of my answer thanks to Ulrike Fischer's comments in [How can I modify my \item redefinition to be compatible with tagging-pdf](#).

#### 13.40.1 Socket for tagging support in **enumext\*** and **keyans\***

We will first define the necessary sockets and their behavior for **enumext\*** and **keyans\***.

```

start-list-tags
stop-start-tags
stop-list-tags
\__enumext_start_list_tag:n
\__enumext_stop_start_list_tag:
\__enumext_stop_list_tag:n
3817 \socket_new:nn {tagsupport/enumext/starred}{ 1 }
3818 \socket_new_plug:nnn {tagsupport/enumext/starred} {start-list-tags}
3819 {
3820   \tag_resume:n {#1}
3821   \tag_struct_begin:n {tag=LI}
3822   \tag_struct_begin:n {tag=Lbl}
3823   \tag_mc_begin:n {tag=Lbl}
3824 }
3825 \socket_new_plug:nnn {tagsupport/enumext/starred} {stop-start-tags}
3826 {
3827   \tag_mc_end:
3828   \tag_struct_end:n {tag=Lbl}
3829   \tag_struct_begin:n {tag=LBody}
3830   \tag_struct_begin:n {tag=text-unit}
3831   \tag_struct_begin:n {tag=text}
3832 }
3833 \socket_new_plug:nnn {tagsupport/enumext/starred} {stop-list-tags}
3834 {
3835   \tag_struct_end:n {tag=text}
3836   \tag_struct_end:n {tag=text-unit}
3837   \tag_struct_end:n {tag=LBody}
3838   \tag_struct_end:n {tag=LI}
3839   \tag_suspend:n {#1}
3840 }

```

And now we'll wrap them so that they're only active when `\DocumentMetadata` is present.

```

3841 \cs_new_protected_nopar:Npn \__enumext_start_list_tag:n #1
3842 {
3843   \IfDocumentMetadataTF
3844   {
3845     \socket_assign_plug:nn {tagsupport/enumext/starred} {start-list-tags}
3846     \socket_use:n {tagsupport/enumext/starred} {#1}
3847   } {}
3848 }
3849 \cs_new_protected_nopar:Nn \__enumext_stop_start_list_tag:
3850 {

```

```

3851 \IfDocumentMetadataTF
3852 {
3853     \socket_assign_plug:nn {tagsupport/enumext/starred} {stop-start-tags}
3854     \socket_use:nn {tagsupport/enumext/starred} { }
3855 } {}
3856 }
3857 \cs_new_protected_nopar:Npn \__enumext_stop_list_tag:n #1
3858 {
3859     \IfDocumentMetadataTF
3860     {
3861         \socket_assign_plug:nn {tagsupport/enumext/starred} {stop-list-tags}
3862         \socket_use:nn {tagsupport/enumext/starred} {#1}
3863     } {}
3864 }

```

(End of definition for start-list-tags and others.)

### 13.40.2 Socket for tagging support in keyanspic

We will first define the necessary sockets and their behavior for `keyanspic` environment.

start-list-tags  
stop-start-tags  
stop-list-tags  
\_\_enumext\_anspic\_start\_list\_tag:  
\_\_enumext\_anspic\_stop\_start\_list\_tag:  
\_\_enumext\_anspic\_stop\_list\_tag:

```

3865 \socket_new:nn {tagsupport/enumext/keyanspic}{ 0 }
3866 \socket_new_plug:nnn {tagsupport/enumext/keyanspic} {start-list-tags}
3867 {
3868     \tag_resume:n {keyanspic}
3869     \tag_struct_begin:n {tag=LI}
3870     \tag_struct_begin:n {tag=Lbl}
3871     \tag_mc_begin:n {tag=Lbl}
3872 }
3873 \socket_new_plug:nnn {tagsupport/enumext/keyanspic} {stop-start-tags}
3874 {
3875     \tag_mc_end:
3876     \tag_struct_end:n {tag=Lbl}
3877     \tag_struct_begin:n {tag=LBody}
3878     \tag_struct_begin:n {tag=text-unit}
3879     \tag_struct_begin:n {tag=text}
3880     \tag_mc_begin:n {tag=text}
3881 }
3882 \socket_new_plug:nnn {tagsupport/enumext/keyanspic} {stop-list-tags}
3883 {
3884     \tag_mc_end:
3885     \tag_struct_end:n {tag=text-unit}
3886     \tag_struct_end:n {tag=text}
3887     \tag_struct_end:n {tag=LBody}
3888     \tag_struct_end:n {tag=LI}
3889     \tag_suspend:n {keyanspic}
3890 }

```

And now we'll wrap them so that they're only active when `\DocumentMetadata` is present.

```

3891 \cs_new_protected_nopar:Nn \__enumext_anspic_start_list_tag:
3892 {
3893     \IfDocumentMetadataTF
3894     {
3895         \socket_assign_plug:nn {tagsupport/enumext/keyanspic} {start-list-tags}
3896         \socket_use:n {tagsupport/enumext/keyanspic}
3897     } {}
3898 }
3899 \cs_new_protected_nopar:Nn \__enumext_anspic_stop_start_list_tag:
3900 {
3901     \IfDocumentMetadataTF
3902     {
3903         \socket_assign_plug:nn {tagsupport/enumext/keyanspic} {stop-start-tags}
3904         \socket_use:nn {tagsupport/enumext/keyanspic}
3905     } {}
3906 }
3907 \cs_new_protected_nopar:Nn \__enumext_anspic_stop_list_tag:
3908 {
3909     \IfDocumentMetadataTF
3910     {
3911         \socket_assign_plug:nn {tagsupport/enumext/keyanspic} {stop-list-tags}
3912         \socket_use:nn {tagsupport/enumext/keyanspic}
3913     } {}
3914 }

```

(End of definition for `start-list-tags` and others.)

### 13.41 The environment `keyanspic` and `\anspic`

The `keyanspic` environment is a `list` based environment that uses the same configuration for “*spacing*” and `<label>` as the `keyans` environment, but it does not use `\item`. The `<contents>` are passed to the environment by means of the `\anspic` command as replacement for `\item` command and placed inside `minipage` environments, with the `<label>` centered “*above*” or “*below*”, adjusting *widths* and *position* according to the options passed to the environment.




Figure 12: Representation of the `keyanspic` spacing in `enumext`.

- One of the complications here to make the `keyanspic` environment compatible with *tagged* PDF is the position of `<label>`, the `\anspic` command processes the arguments in order, where #1 and #2 correspond to `<label>` and #3 to the mandatory argument and puts all this inside a `minipage` environment. If #1 and #2, that is `<label>`, is above #3 there are no problems with *tagged* PDF, but if #3 comes first the list created with *tagged* PDF will not be correct.

#### 13.41.1 The environment `keyanspic`

In order for the `keyanspic` environment and the `\anspic` command to work correctly, we need to set and export some variables in the first part of the environment definition and pass them to `\anspic` which is executed in the second part of the environment. This implementation is adapted from the answer given by Enrico Gregorio (@egreg) in [How to process the body of an environment and divide it by a \macro?](#).

First we define the key that allows us to process the position of the `<label>` centered “*above*” or “*below*” which will be `label-pos`, the vertical separation of these from *drawing or tabular* will be handled with the key `label-sep`. The “*layout style*” will be handled with the key `layout-sty` will take two values separated by comma {*n° upper, n° lower*} and will determine the number of `minipage` environments in which all arguments of `\anspic` will be printed at the “*upper*” and “*lower*” within the environments separated by the value of the key `layout-sep`. The vertical space “*top*” and “*bottom*” of the environment will be handled with the key `layout-top`.

```

3915 \tl_new:N \l__enumext_anspic_layout_tl
3916 \keys_define:nn { enumext / keyanspic }
3917 {
3918   label-pos .choice:,
3919   label-pos / above .code:n =
3920                       \bool_set_true:N \l__enumext_anspic_label_above_bool
3921                       \str_set:Nn \l__enumext_anspic_mini_pos_str { t },
3922   label-pos / below .code:n =
3923                       \bool_set_false:N \l__enumext_anspic_label_above_bool
3924                       \str_set:Nn \l__enumext_anspic_mini_pos_str { b },
3925   label-pos / unknown .code:n =
3926                       \msg_error:nnee { enumext } { unknown-choice }
3927                       { label-pos } { above,~ below } { \exp_not:n {#1} },
3928   label-pos .initial:n = below,
3929   label-pos .value_required:n = true,
3930   label-sep .skip_set:N = \l__enumext_anspic_label_sep_skip,
3931   label-sep .value_required:n = true,
3932   layout-sty .tl_set:N = \l__enumext_anspic_layout_tl,
3933   layout-sty .value_required:n = true,
3934   layout-sep .code:n = \keys_set:nn { enumext / keyans } { parsep = #1 },
3935   layout-sep .value_required:n = true,
3936   layout-top .code:n = \keys_set:nn { enumext / keyans } { topsep = #1 },
3937   layout-top .value_required:n = true,
3938   %unknown .code:n = { \l__enumext_keyans_unknown_keys:n {#1} }
3939 }

```

(End of definition for `label-pos` and others.)

The function `\__enumext_keyans_pic_safe_exec:` check the nested level position inside the `enumext` environment.

```

\__enumext_keyans_pic_parse_keys:n
\__enumext_keyans_pic_skip_abs:N
\__enumext_keyans_pic_arg_two:
3940 \cs_new_protected:Nn \__enumext_keyans_pic_safe_exec:

```

```

3941 {
3942   \int_incr:N \l__enumext_keyans_pic_level_int
3943   \int_compare:nNtT { \l__enumext_keyans_pic_level_int } > { 1 }
3944   {
3945     \msg_error:nn { enumext } { keyanspic-nested }
3946   }
3947   \__enumext_keyans_name_and_start:
3948 }

3949 \cs_new_protected:Npn \__enumext_keyans_pic_parse_keys:n #1
3950 {
3951   \tl_if_novalue:nF {#1}
3952   {
3953     \keys_set:nn { enumext / keyanspic } {#1}
3954   }
3955 }

```

The function `\__enumext_keyans_pic_skip_abs:N` will return a positive value `\parsep`.

```

3956 \cs_new_protected:Npn \__enumext_keyans_pic_skip_abs:N #1
3957 {
3958   \dim_compare:nNtT { #1 } < { \c_zero_dim }
3959   {
3960     \skip_set:Nn #1 { -#1 }
3961   }
3962 }

```

The `\__enumext_keyans_pic_arg_two:` function will be used in the *second argument* of the `list` environment that defines the `keyanspic` environment, with this we will take the configuration of the “spaces” and the `(keys)` label and `wrap-label` from the `keyans` environment.

The first thing we need to do is set the boolean variable `\l__enumext_leftmargin_tmp_v_bool` handled by the `list-indent` key to “false”, then copy the definition of the second list argument from the `keyans` environment definition and make sure that `\parsep` does not have a negative value.

```

3963 \cs_new_protected:Npn \__enumext_keyans_pic_arg_two:
3964 {
3965   \bool_set_false:N \l__enumext_leftmargin_tmp_v_bool
3966   \__enumext_list_arg_two_v:
3967   \__enumext_keyans_pic_skip_abs:N \parsep

```

Now we increment the counter `enumXv` of the `keyans` environment and save the *total height* of the `(label)` in `\l__enumext_anspic_label_htdp_dim` used by `\anspic` and we will adjust the values of `\parsep` only if the *starred argument* “\*” is NOT present.

```

3968   \bool_if:NF \l__enumext_anspic_label_above_bool
3969   {
3970     \stepcounter { enumXv }
3971     \hbox_set:Nn \l__enumext_anspic_label_box { \l__enumext_label_v_tl }
3972     \dim_set:Nn \l__enumext_anspic_label_htdp_dim
3973     {
3974       \box_ht_plus_dp:N \l__enumext_anspic_label_box
3975     }
3976     \skip_add:Nn \parsep
3977     {
3978       \l__enumext_anspic_label_htdp_dim
3979       + \box_dp:N \strutbox
3980       + \l__enumext_anspic_label_sep_skip
3981     }
3982   }

```

Finally we adjust the value of `\leftmargin` and `\topsep` then set `\listparindent`, `\partopsep` and `\itemsep` to zero so that the *horizontal* and *vertical* space is not affected.

```

3983   \dim_add:Nn \leftmargin { -\labelwidth - \labelsep }
3984   \skip_add:Nn \topsep { 0.5\box_dp:N \strutbox }
3985   \dim_zero:N \listparindent
3986   \skip_zero:N \partopsep
3987   \skip_zero:N \itemsep
3988 }

```

(End of definition for `\__enumext_keyans_pic_safe_exec:` and others.)

**keyanspic** Now we define the environment `keyanspic`. For compatibility with *tagged* PDF we must use the `\begin{list}` form and a lot of conditional code using `\IfDocumentMetadataTF`.

```

3989 \NewDocumentEnvironment{keyanspic}{0}
3990 {

```

```

3991 \__enumext_keyans_pic_safe_exec:
3992 \__enumext_keyans_pic_parse_keys:n {#1}
3993 \begin{list} { } { \__enumext_keyans_pic_arg_two: }
3994 \IfDocumentMetadataTF
3995 {
3996   \tag_suspend:n {list}
3997 }{}
3998 \item[] \scan_stop:
3999 % paranoia
4000 \RenewDocumentCommand \item {}
4001 {
4002   \msg_error:nn { enumext } { keyanspic-item-cmd }
4003 }
4004 \IfDocumentMetadataTF
4005 {
4006   \tag_resume:n {keyanspic}
4007   \tag_tool:n {para/tagging=false}
4008   \tag_suspend:n {keyanspic}
4009 } { }
4010 }
4011 {
4012   \IfDocumentMetadataTF
4013   {
4014     \tag_resume:n {keyanspic}
4015     \tag_struct_begin:n {tag=L,attribute=enumerate}
4016   } { }

```

Now we process the command `\anspic`, if the *optional argument* is not present, the number of times the `\anspic` command appears will be counted from `\l__enumext_anspic_args_seq` and placed a single line.

```

4017 \__enumext_anspic_exec:
4018 \IfDocumentMetadataTF
4019 {
4020   \tag_suspend:n {keyanspic}
4021 } { }
4022 \end{list}
4023 \IfDocumentMetadataTF
4024 {
4025   \tag_struct_end:
4026   \tag_struct_end:
4027 } { }

```

Finally we check if `\anspic*` has been used, set the counter to zero and apply our “adjusted” vertical space below the environment.

```

4028 \__enumext_check_starred_cmd:n { anspic }
4029 \setcounter { enumXvi } { 0 }
4030 \bool_if:NTF \l__enumext_anspic_label_above_bool
4031 {
4032   \par\addvspace{ 0.5\box_dp:N \strutbox }
4033 }
4034 {
4035   \par
4036   \addvspace
4037   {
4038     \dim_eval:n
4039     {
4040       \l__enumext_anspic_label_htdp_dim + \box_ht_plus_dp:N \strutbox
4041       + \l__enumext_anspic_label_sep_skip + \l__enumext_topsep_v_skip
4042     }
4043   }
4044 }
4045 %\bool_set_false:N \l__enumext_store_active_bool
4046 }

```

(End of definition for `keyanspic`. This function is documented on page 15.)

### 13.41.2 The command `\anspic`

The `\anspic` command take three arguments, the *starred versions* `\anspic*[\langle content \rangle]` store the current *label* next to the *optional argument* `[\langle content \rangle]` in the *sequence* and *prop list* defined by `save-ans` key. The third *mandatory argument* `{\langle drawing or tabular \rangle}` is NOT stored in the *sequence* or *prop list*.

`\anspic`

We check that the command is active in the `keyanspic` environment only if the `save-ans` key is present, otherwise we return an error. The three arguments are handled by the function `\__enumext_anspic_args:nnn`



and stored in the sequence `\__enumext_anspic_args_seq` which is processed by the `keyanspic` environment.

```

4047 \NewDocumentCommand \anspic { s o +m }
4048 {
4049   \bool_if:NF \__enumext_store_active_bool
4050   {
4051     \msg_error:nnnn { enumext } { wrong-place } { keyanspic } { save-ans }
4052   }
4053   \int_compare:nNnT { \__enumext_level_int } > { 1 }
4054   {
4055     \msg_error:nn { enumext } { keyanspic-wrong-level }
4056   }
4057   \int_compare:nNnT { \__enumext_keyans_level_int } = { 1 }
4058   {
4059     \msg_error:nnnn { enumext } { command-wrong-place } { anspic } { keyans }
4060   }
4061   \seq_put_right:Nn \__enumext_anspic_args_seq
4062   {
4063     \__enumext_anspic_args:nnn { #1 } { #2 } { #3 }
4064   }
4065 }

```

The `\__enumext_anspic_body_dim:n` function will set the value of `\__enumext_anspic_body_htdp_dim` equal to the height and depth of the mandatory argument if the `keyanspic*` environment is used with the *starred argument* ‘\*’.

```

4066 \cs_new_protected:Npn \__enumext_anspic_body_dim:n #1
4067 {
4068   \bool_if:NF \__enumext_anspic_label_above_bool
4069   {
4070     \IfDocumentMetadataTF
4071     {
4072       \tag_suspend:n {keyanspic}
4073     } { }
4074     \vbox_set:Nn \__enumext_anspic_body_box { #1 }
4075     \dim_set:Nn \__enumext_anspic_body_htdp_dim
4076     {
4077       \box_ht_plus_dp:N \__enumext_anspic_body_box
4078     }
4079     \IfDocumentMetadataTF
4080     {
4081       \tag_resume:n {keyanspic}
4082     } { }
4083   }
4084 }

```

The `\__enumext_anspic_label:nn` function will process inside `\makebox` the *starred argument* ‘\*’ and *optional argument* passed to the command. Here we will store the `<label>` and *optional argument* in *prop list* and *sequence* and execute the `show-ans`, `show-pos`, `font`, `wrap-label` and `wrap-opt` keys.

```

4085 \cs_new_protected:Npn \__enumext_anspic_label:nn #1 #2
4086 {
4087   \makebox[ \__enumext_anspic_mini_width_dim ][ c ]
4088   {
4089     \bool_if:nT { #1 }
4090     {
4091       \__enumext_keyans_addto_prop:n { #2 }
4092       \__enumext_keyans_store_ref:
4093       \__enumext_keyans_addto_seq:n { #2 }
4094       \int_gincr:N \__enumext_check_starred_cmd_int
4095       \bool_lazy_or:nnT
4096       { \bool_if_p:N \__enumext_show_answer_bool }
4097       { \bool_if_p:N \__enumext_show_position_bool }
4098       {
4099         \tl_set_eq:NN \__enumext_label_v_tl \__enumext_label_vi_tl
4100         \__enumext_keyans_show_left:n { #2 }
4101         \tl_set_eq:NN \__enumext_label_vi_tl \__enumext_label_v_tl
4102       }
4103     }
4104     \tl_use:N \__enumext_label_font_style_v_tl
4105     \__enumext_wrapper_label_v:n { \__enumext_label_vi_tl }
4106     \__enumext_keyans_show_item_opt:
4107   }
4108 }

```

The function `\__enumext_anspic_label_pos:nnn` will be in charge of handling the “*counter*” and the position of the `<label>`, which will have the same configuration as the `keyans` environment.

```

4109 \cs_new_protected:Npn \__enumext_anspic_label_pos:nnn #1 #2 #3
4110 {
4111   \stepcounter { enumXvi }
4112   \__enumext_anspic_body_dim:n { #3 }
4113   \bool_if:NTF \__enumext_anspic_label_above_bool
4114   {
4115     \__enumext_anspic_label:nn { #1 } { #2 }
4116   }
4117   {
4118     \raisebox
4119     {
4120       -\dim_eval:n
4121       {
4122         \__enumext_anspic_label_htdp_dim
4123         + \__enumext_anspic_body_htdp_dim
4124         + \box_dp:N \strutbox
4125         + \__enumext_anspic_label_sep_skip
4126       }
4127     }
4128     [ opt ] [ opt ]
4129     {
4130       \__enumext_anspic_label:nn { #1 } { #2 }
4131     }
4132   }
4133 }
4134 %

```

The `\__enumext_anspic_args:nnn` function will be responsible for placing the code compatible with *tagged* PDF and the arguments within the `\__enumext_anspic_args_seq` sequence which will be processed by the `\__enumext_anspic_print:n` function in the second part of the definition of the `keyanspic` environment.

```

4135 \cs_new_protected:Nn \__enumext_anspic_args:nnn
4136 {
4137   \__enumext_anspic_start_list_tag:
4138   \__enumext_anspic_label_pos:nnn { #1 } { #2 } { #3 }
4139   \__enumext_anspic_stop_start_list_tag:
4140   \bool_if:NTF \__enumext_anspic_label_above_bool
4141   {
4142     \[\__enumext_anspic_label_sep_skip] #3
4143   }
4144   {
4145     \[ #3
4146   }
4147   \__enumext_anspic_stop_list_tag:
4148 }

```

The *optional argument* `[<n°upper, n°lower>]` passed to the `keyanspic` environment is split by comma and is handled directly by the function `\__enumext_anspic_print:n` and passed to the function `\__enumext_anspic_row:n`.

```

4149 \cs_new_protected:Nn \__enumext_anspic_print:n
4150 {
4151   \clist_map_function:nN { #1 } \__enumext_anspic_row:n
4152 }
4153 \cs_generate_variant:Nn \__enumext_anspic_print:n { e, V }

```

The function `\__enumext_anspic_row:n` will set the *widths* for the `minipage` environments and place *all arguments* passed to `\anspic saved` in the `\__enumext_anspic_args_seq` sequence inside them.

```

4154 \cs_new_protected:Nn \__enumext_anspic_row:n
4155 {
4156   \dim_set:Nn \__enumext_anspic_mini_width_dim { \linewidth / #1 }
4157   \int_set:Nn \__enumext_anspic_above_int { \__enumext_anspic_below_int }
4158   \int_set:Nn \__enumext_anspic_below_int { \__enumext_anspic_above_int + #1 }
4159   \int_step_inline:nnn
4160   { \__enumext_anspic_above_int + 1 }
4161   { \__enumext_anspic_below_int }
4162   {
4163     \IfDocumentMetadataTF
4164     {
4165       \tag_suspend:n {minipage}
4166     } { }
4167     \begin{minipage}[ \__enumext_anspic_mini_pos_str ]{ \__enumext_anspic_mini_width_dim }

```

```

4168         \centering
4169         \seq_item:Nn \l__enumext_anspic_args_seq { ##1 }
4170     \end{minipage}
4171     \IfDocumentMetadataTF
4172     {
4173         \tag_resume:n {minipage}
4174     } { }
4175 }
4176 \par
4177 }
4178 \cs_new_protected:Nn \__enumext_anspic_exec:
4179 {
4180     \tl_if_empty:NTF \l__enumext_anspic_layout_tl
4181     {
4182         \__enumext_anspic_print:e { \seq_count:N \l__enumext_anspic_args_seq }
4183     }
4184     {
4185         \__enumext_anspic_print:V \l__enumext_anspic_layout_tl
4186     }
4187 }

```

(End of definition for `\anspic` and others. This function is documented on page 15.)

### 13.42 The horizontal environments

Generating *horizontal list environments* is NOT as simple as standard  $\TeX$  list environments. The fundamental part of the code is adapted from the `shortlist` package to a more modern version using `expl3`. It is not possible to redefine `\item` and `\makeLabel` using `\RenewDocumentCommand` as in the vertical *non starred* versions.

To achieve the *horizontal list environments* we will capture the `\item` command and the  $\langle content \rangle$  of this in *horizontal box* using `\makebox` for the `label` and a `minipage` environment for the  $\langle content \rangle$  passed to `\item`, we will also add the *optional argument* ( $\langle number \rangle$ ) to `\item` to be able to *join columns* horizontally, in simple terms, we want `\item` to behave in the same way as in the `enumext` environment but adding an *first optional argument* ( $\langle number \rangle$ ).

A side effect is the limitation of using `\item` in this way *without* using `\RenewDocumentCommand`, which loses the original definition and affects the *standard list environments* provided by  $\TeX$  and any environment defined using base `list` environment, including: `itemize`, `enumerate`, `description`, `quote`, `quotation`, `verse`, `center`, `flushleft`, `flushright`, `verbatim`, `tabbing`, `trivlist`, `list` and all environments created with `\newtheorem`.

- One way to get around this is to use something like:

```
\AddToHook{env/enumerate/before}{recover original \item definition}
```

inside `minipage`, but in my partial tests this does not have the desired effect and the vertical and horizontal spacing is distorted. For now this will remain as a limitation and I will see if it is feasible to implement it in the future.

- For compatibility with the *tagged* PDF we close the environments according to the presence or not of the `mini-env` key.

#### 13.42.1 Functions for item box width

We set the default value for the *width of the box* containing the  $\langle content \rangle$  of the items for `enumext*` environment.

```

\__enumext_starred_columns_set_vii:
\__enumext_starred_columns_set_viii:
4188 \cs_new_protected:Nn \__enumext_starred_columns_set_vii:
4189 {
4190     \dim_compare:nNnT { \l__enumext_columns_sep_vii_dim } = { \c_zero_dim }
4191     {
4192         \dim_set:Nn \l__enumext_columns_sep_vii_dim
4193         {
4194             ( \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim )
4195             / \l__enumext_columns_vii_int
4196         }
4197     }
4198     \int_set:Nn \l__enumext_tmpa_vii_int { \l__enumext_columns_vii_int - 1 }
4199     \dim_set:Nn \l__enumext_item_width_vii_dim
4200     {
4201         ( \linewidth - \l__enumext_columns_sep_vii_dim * \l__enumext_tmpa_vii_int )
4202         / \l__enumext_columns_vii_int
4203         - \l__enumext_labelwidth_vii_dim
4204         - \l__enumext_labelsep_vii_dim
4205     }

```

When the key `rightmargin` is active we must adjust the values.

```

4206 \dim_compare:nNtT { \l__enumext_rightmargin_vii_dim } > { \c_zero_dim }
4207 {
4208   \dim_sub:Nn \l__enumext_item_width_vii_dim
4209   {
4210     ( \l__enumext_rightmargin_vii_dim * \l__enumext_tmpa_vii_int )
4211     / \l__enumext_columns_vii_int
4212   }
4213   \dim_add:Nn \l__enumext_columns_sep_vii_dim
4214   {
4215     \l__enumext_rightmargin_vii_dim
4216   }
4217 }
4218 }
```

Same implementation for the `keyans*` environment.

```

4219 \cs_new_protected:Nn \__enumext_starred_columns_set_viii:
4220 {
4221   \dim_compare:nNtT { \l__enumext_columns_sep_viii_dim } = { \c_zero_dim }
4222   {
4223     \dim_set:Nn \l__enumext_columns_sep_viii_dim
4224     {
4225       ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim )
4226       / \l__enumext_columns_viii_int
4227     }
4228   }
4229   \int_set:Nn \l__enumext_tmpa_viii_int { \l__enumext_columns_viii_int - 1 }
4230   \dim_set:Nn \l__enumext_item_width_viii_dim
4231   {
4232     ( \linewidth - \l__enumext_columns_sep_viii_dim * \l__enumext_tmpa_viii_int )
4233     / \l__enumext_columns_viii_int
4234     - \l__enumext_labelwidth_viii_dim
4235     - \l__enumext_labelsep_viii_dim
4236   }
4237   \dim_compare:nNtT { \l__enumext_rightmargin_viii_dim } > { \c_zero_dim }
4238   {
4239     \dim_sub:Nn \l__enumext_item_width_viii_dim
4240     {
4241       ( \l__enumext_rightmargin_viii_dim * \l__enumext_tmpa_vii_int )
4242       / \l__enumext_columns_viii_int
4243     }
4244     \dim_add:Nn \l__enumext_columns_sep_viii_dim
4245     {
4246       \l__enumext_rightmargin_viii_dim
4247     }
4248   }
4249 }
```

(End of definition for `\__enumext_starred_columns_set_vii:` and `\__enumext_starred_columns_set_viii:`.)

### 13.42.2 Functions for join item columns

`\__enumext_starred_joined_item_vii:n`  
`\__enumext_starred_joined_item_viii:n`

The functions `\__enumext_starred_joined_item_vii:n` and `\__enumext_starred_joined_item_viii:n` will set the *width* of the box in which the *(content)* passed to `\item(<columns>)` will be stored together with the value of `\itemwidth` for the `enumext*` environment.

```

4250 \cs_new_protected:Npn \__enumext_starred_joined_item_vii:n #1
4251 {
4252   \int_set:Nn \l__enumext_joined_item_vii_int {#1}
4253   \int_compare:nNtT { \l__enumext_joined_item_vii_int } > { \l__enumext_columns_vii_int }
4254   {
4255     \msg_warning:nnee { enumext } { item-joined }
4256     { \int_use:N \l__enumext_joined_item_vii_int }
4257     { \int_use:N \l__enumext_columns_vii_int }
4258     \int_set:Nn \l__enumext_joined_item_vii_int
4259     {
4260       \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1
4261     }
4262   }
4263   \int_compare:nNtT
4264   { \l__enumext_joined_item_vii_int }
4265   >
4266   { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1 }
```

```

4267     {
4268         \msg_warning:nnee { enumext } { item-joined-columns }
4269         { \int_use:N \l__enumext_joined_item_vii_int }
4270         {
4271             \int_eval:n
4272             { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1 }
4273         }
4274         \int_set:Nn \l__enumext_joined_item_vii_int
4275         {
4276             \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1
4277         }
4278     }
4279     \int_compare:nNnTF { \l__enumext_joined_item_vii_int } > { 1 }
4280     {
4281         \int_set_eq:NN \l__enumext_joined_item_aux_vii_int \l__enumext_joined_item_vii_int
4282         \int_decr:N \l__enumext_joined_item_aux_vii_int
4283         \int_add:Nn \l__enumext_item_column_pos_vii_int { \l__enumext_joined_item_aux_vii_int }
4284         \int_gadd:Nn \g__enumext_item_count_all_vii_int { \l__enumext_joined_item_aux_vii_int }
4285         \dim_set:Nn \l__enumext_joined_width_vii_dim
4286         {
4287             \l__enumext_item_width_vii_dim * \l__enumext_joined_item_vii_int
4288             + ( \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim
4289               + \l__enumext_columns_sep_vii_dim
4290             ) * \l__enumext_joined_item_aux_vii_int
4291         }
4292         \dim_set_eq:NN \itemwidth \l__enumext_joined_width_vii_dim
4293     }
4294     {
4295         \dim_set_eq:NN \l__enumext_joined_width_vii_dim \l__enumext_item_width_vii_dim
4296         \dim_set_eq:NN \itemwidth \l__enumext_item_width_vii_dim
4297     }
4298 }

```

Same implementation for the [keyans\\*](#) environment.

```

4299 \cs_new_protected:Npn \__enumext_starred_joined_item_viii:n #1
4300 {
4301     \int_set:Nn \l__enumext_joined_item_viii_int {#1}
4302     \int_compare:nNnT { \l__enumext_joined_item_viii_int } > { \l__enumext_columns_viii_int }
4303     {
4304         \msg_warning:nnee { enumext } { item-joined }
4305         { \int_use:N \l__enumext_joined_item_viii_int }
4306         { \int_use:N \l__enumext_columns_viii_int }
4307         \int_set:Nn \l__enumext_joined_item_viii_int
4308         {
4309             \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1
4310         }
4311     }
4312     \int_compare:nNnT
4313     { \l__enumext_joined_item_viii_int }
4314     >
4315     { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1 }
4316     {
4317         \msg_warning:nnee { enumext } { item-joined-columns }
4318         { \int_use:N \l__enumext_joined_item_viii_int }
4319         {
4320             \int_eval:n
4321             { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1 }
4322         }
4323         \int_set:Nn \l__enumext_joined_item_viii_int
4324         {
4325             \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1
4326         }
4327     }
4328     \int_compare:nNnTF { \l__enumext_joined_item_viii_int } > { 1 }
4329     {
4330         \int_set_eq:NN \l__enumext_joined_item_aux_viii_int \l__enumext_joined_item_viii_int
4331         \int_decr:N \l__enumext_joined_item_aux_viii_int
4332         \int_add:Nn \l__enumext_item_column_pos_viii_int { \l__enumext_joined_item_aux_viii_int }
4333         \int_gadd:Nn \g__enumext_item_count_all_viii_int { \l__enumext_joined_item_aux_viii_int }
4334         \dim_set:Nn \l__enumext_joined_width_viii_dim
4335         {
4336             \l__enumext_item_width_viii_dim * \l__enumext_joined_item_viii_int

```

```

4337         + ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim
4338           + \l__enumext_columns_sep_viii_dim
4339           )*\l__enumext_joined_item_aux_viii_int
4340     }
4341     \dim_set_eq:NN \itemwidth \l__enumext_joined_width_viii_dim
4342   }
4343   {
4344     \dim_set_eq:NN \l__enumext_joined_width_viii_dim \l__enumext_item_width_viii_dim
4345     \dim_set_eq:NN \itemwidth \l__enumext_item_width_viii_dim
4346   }
4347 }

```

(End of definition for \l\_\_enumext\_starred\_joined\_item\_vii:n and \l\_\_enumext\_starred\_joined\_item\_viii:n)

### 13.42.3 Functions for mini-env, mini-right and mini-right\* keys

```

\__enumext_start_mini_vii:
\__enumext_stop_mini_vii:

```

The implementation of the `mini-env` key support is almost identical to the one used in the `enumext` and `keyans` environments, the difference is that the `\__enumext_mini_page` environment on the “right side” is executed “after” closing the environment, so it is necessary to make a global copy of the variable `\l__enumext_minipage_right_vii_dim` in the variable `\g__enumext_minipage_right_vii_dim`.

```

4348 \cs_new_protected:Nn \__enumext_start_mini_vii:
4349 {
4350   \dim_compare:nNnT { \l__enumext_minipage_right_vii_dim } > { \c_zero_dim }
4351   {
4352     \dim_set:Nn \l__enumext_minipage_left_vii_dim
4353     {
4354       \linewidth
4355       - \l__enumext_minipage_right_vii_dim
4356       - \l__enumext_minipage_hsep_vii_dim
4357     }
4358     \bool_set_true:N \l__enumext_minipage_active_vii_bool
4359     \dim_gset_eq:NN
4360       \g__enumext_minipage_right_vii_dim
4361       \l__enumext_minipage_right_vii_dim
4362     \__enumext_mini_addvspace_vii:
4363     \nointerlineskip\noindent
4364     \__enumext_mini_page{ \l__enumext_minipage_left_vii_dim }
4365   }
4366 }

```

The function `\__enumext_stop_mini_vii:` closes the `\__enumext_mini_page` environment on the “left side”, applies `\hfill` and set the variable `\g__enumext_minipage_active_vii_bool` to “true” which will be used in the function `\__enumext_after_env:n` to execute the `minipage` on the “right side”. At this point we will execute the `\__enumext_stop_list:` and `\__enumext_stop_store_level_vii:` functions stopping the `list` environment and the level saving mechanism for storage in *sequence* of the `\anskey` command and `anskey*` environment. This function is passed to the `\__enumext_after_list_vii:` function in the second part of the `enumext*` environment definition (§13.43).

```

4367 \cs_new_protected:Nn \__enumext_stop_mini_vii:
4368 {
4369   \bool_if:NTF \l__enumext_minipage_active_vii_bool
4370   {
4371     \__enumext_stop_list:
4372     \__enumext_stop_store_level_vii:
4373     \IfDocumentMetadataTF { \tag_resume:n {enumext*} } { }
4374     \end__enumext_mini_page
4375     \hfill
4376     \bool_gset_true:N \g__enumext_minipage_active_vii_bool
4377   }
4378   {
4379     \__enumext_stop_list:
4380     \__enumext_stop_store_level_vii:
4381   }
4382 }

```

(End of definition for \\_\_enumext\_start\_mini\_vii: and \\_\_enumext\_stop\_mini\_vii:.)

Finally we execute the `{\code}` passed to the `mini-right` or `mini-right*` keys stored in the variable `\g__enumext_miniright_code_vii_tl` in the `minipage` environment on the “right side”. For compatibility with the `caption` package and possibly other `{\code}` passed to this key, we will pass it to a box and then print it.

```

4383 \__enumext_after_env:n {enumext*}
4384 {

```

```

4385 \bool_if:NT \g__enumext_minipage_active_vii_bool
4386 {
4387   \__enumext_minipage:w [ t ] { \g__enumext_minipage_right_vii_dim }
4388   \legacy_if_gset_false:n { @minipage }
4389   \skip_vertical:N \c_zero_skip
4390   \par\addvspace { \g__enumext_minipage_right_skip }
4391   \bool_if:NF \g__enumext_minipage_center_vii_bool
4392   {
4393     \tl_put_left:Nn \g__enumext_miniright_code_vii_tl
4394     {
4395       \centering
4396     }
4397   }
4398   \vbox_set_top:Nn \l__enumext_miniright_code_vii_box
4399   {
4400     \tl_use:N \g__enumext_miniright_code_vii_tl
4401   }
4402   \box_use_drop:N \l__enumext_miniright_code_vii_box
4403   \skip_vertical:N \c_zero_skip
4404   \__enumext_endminipage:
4405   \par\addvspace{ \g__enumext_minipage_after_skip }
4406 }
4407 \bool_gset_false:N \g__enumext_minipage_active_vii_bool
4408 \bool_gset_true:N \g__enumext_minipage_center_vii_bool
4409 \tl_gclear:N \g__enumext_miniright_code_vii_tl
4410 \dim_gzero:N \g__enumext_minipage_right_vii_dim
4411 \bool_gset_false:N \g__enumext_starred_bool
4412 }

```

```

\__enumext_start_mini_viii:
\__enumext_stop_mini_viii:

```

The implementation of the `mini-env`, `mini-right` and `mini-right*` keys is identical to the one used in the `enumext*` environment.

```

4413 \cs_new_protected:Nn \__enumext_start_mini_viii:
4414 {
4415   \dim_compare:nNnT { \l__enumext_minipage_right_viii_dim } > { \c_zero_dim }
4416   {
4417     \dim_set:Nn \l__enumext_minipage_left_viii_dim
4418     {
4419       \linewidth
4420       - \l__enumext_minipage_right_viii_dim
4421       - \l__enumext_minipage_hsep_viii_dim
4422     }
4423     \bool_set_true:N \l__enumext_minipage_active_viii_bool
4424     \dim_gset_eq:NN
4425     \g__enumext_minipage_right_viii_dim
4426     \l__enumext_minipage_right_viii_dim
4427     \__enumext_mini_addvspace_viii:
4428     \nointerlineskip\noindent
4429     \__enumext_mini_page{ \l__enumext_minipage_left_viii_dim }
4430   }
4431 }
4432 \cs_new_protected:Nn \__enumext_stop_mini_viii:
4433 {
4434   \bool_if:NTF \l__enumext_minipage_active_viii_bool
4435   {
4436     \__enumext_stop_list:
4437     \IfDocumentMetadataTF { \tag_resume:n {keyans*} } { }
4438     \end__enumext_mini_page
4439     \hfill
4440     \bool_gset_true:N \g__enumext_minipage_active_viii_bool
4441   }
4442   {
4443     \__enumext_stop_list:
4444   }
4445 }
4446 \__enumext_after_env:nn {keyans*}
4447 {
4448   \bool_if:NT \g__enumext_minipage_active_viii_bool
4449   {
4450     \__enumext_mini_page{ \g__enumext_minipage_right_viii_dim }
4451     \par\addvspace { \g__enumext_minipage_right_skip }
4452     \bool_if:NF \g__enumext_minipage_center_viii_bool

```



```

4453         {
4454             \tl_put_left:Nn \g__enumext_miniright_code_viii_tl
4455             {
4456                 \centering
4457             }
4458         }
4459         \vbox_set_top:Nn \l__enumext_miniright_code_viii_box
4460         {
4461             \tl_use:N \g__enumext_miniright_code_viii_tl
4462         }
4463         \box_use_drop:N \l__enumext_miniright_code_viii_box
4464         \end__enumext_mini_page
4465         \par\addvspace{ \g__enumext_minipage_after_skip }
4466     }
4467     \bool_gset_false:N \g__enumext_minipage_active_viii_bool
4468     \bool_gset_true:N \g__enumext_minipage_center_viii_bool
4469     \tl_gclear:N \g__enumext_miniright_code_viii_tl
4470     \dim_gzero:N \g__enumext_minipage_right_viii_dim
4471 }

```

(End of definition for \\_\_enumext\_start\_mini\_viii: and \\_\_enumext\_stop\_mini\_viii:.)

### 13.42.4 Redefining \footnote command

\\_\_enumext\_footnotetext:nn \\_\_enumext\_renew\_footnote: \\_\_enumext\_print\_footnote: To keep the correct numbering of \footnote and to make it work correctly in the `enumext*` and `keyans*` environments, it is necessary to redefine the command. This implementation is adapted from the answer given by Clea F. Rees (@cfr) in [footnotes in boxes compatible with hyperref](#).

```

4472 \cs_new_protected:Nn \__enumext_footnotetext:nn
4473 {
4474     \footnotetext[#1]{#2}
4475 }
4476 \cs_new_protected:Nn \__enumext_renew_footnote:
4477 {
4478     \seq_gclear:N \g__enumext_footnote_arg_seq
4479     \seq_gclear:N \g__enumext_footnote_int_seq
4480     \RenewDocumentCommand \footnote { o +m }
4481     {
4482         \tl_if_novalue:nTF {##1}
4483         {
4484             \stepcounter{footnote}
4485             \int_gset_eq:Nc \g__enumext_footnote_int { c@footnote }
4486         }
4487         {
4488             \int_gset:Nn \g__enumext_footnote_int { ##1 }
4489         }
4490         \footnotemark [ \g__enumext_footnote_int ]
4491         \seq_gput_right:Nn \g__enumext_footnote_arg_seq { ##2 }
4492         \seq_gput_right:NV \g__enumext_footnote_int_seq \g__enumext_footnote_int
4493     }
4494 }
4495 \cs_new_protected:Nn \__enumext_print_footnote:
4496 {
4497     \seq_if_empty:NF \g__enumext_footnote_int_seq
4498     {
4499         \seq_map_pairwise_function:NNN
4500         \g__enumext_footnote_int_seq
4501         \g__enumext_footnote_arg_seq
4502         \__enumext_footnotetext:nn
4503     }
4504 }

```

(End of definition for \\_\_enumext\_footnotetext:nn, \\_\_enumext\_renew\_footnote:, and \\_\_enumext\_print\_footnote:.)

### 13.43 The environment enumext\*

`enumext*` First we will generate the environment and we will give a temporary definition to \\_\_enumext\_stop\_item\_tmp\_vii: equal to \\_\_enumext\_first\_item\_tmp\_vii: and next to \item equal to \\_\_enumext\_start\_item\_tmp\_vii: which we will redefine later. Unlike the implementation used by the `shortlst` package, we will not set the values of \rightskip and \@rightskip equal to \@flushglue whose value is 0.0pt plus 1.0 fil, in the tests I have performed this fails in some circumstances and different results are obtained when using pdfTeX and LuaTeX.

```

4505 \NewDocumentEnvironment{enumext*}{ o }

```

```

4506 {
4507     \__enumext_safe_exec_vii:
4508     \__enumext_parse_keys_vii:n {#1}
4509     \__enumext_before_list_vii:
4510     \__enumext_start_store_level_vii:
4511     \__enumext_start_list:nn { }
4512     {
4513         \__enumext_list_arg_two_vii:
4514         \__enumext_before_keys_exec_vii:
4515     }
4516     \IfDocumentMetadataTF { \tag_suspend:n {enumext*} } { }
4517     \__enumext_starred_columns_set_vii:
4518     \item[] \scan_stop:
4519     \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \__enumext_first_item_tmp_vii:
4520     \cs_set_eq:NN \item \__enumext_start_item_tmp_vii:
4521     \ignorespaces
4522 }
4523 {
4524     \IfDocumentMetadataTF { \tag_struct_end:n {tag=text-unit} } { }
4525     \__enumext_stop_item_tmp_vii:
4526     \__enumext_remove_extra_parsep_vii:
4527     \__enumext_after_list_vii:
4528 }

```

(End of definition for enumext\*. This function is documented on page 5.)

\\_\_enumext\_safe\_exec\_vii:

We will first call the function \\_\_enumext\_internal\_mini\_page: to create the environment `\__enumext--mini_page`, then the function \\_\_enumext\_is\_not\_nested: which sets \g\_\_enumext\_starred\_bool to true if we are not nested within `enumext`, we will increment \l\_\_enumext\_level\_h\_int to restrict nesting of the environment, set \l\_\_enumext\_starred\_bool to true and finally call the function \\_\_enumext\_is\_on\_first\_level: which sets \l\_\_enumext\_starred\_first\_bool to true if we are not nested, allowing the “storage system” to be used.

```

4529 \cs_new_protected:Nn \__enumext_safe_exec_vii:
4530 {
4531     \__enumext_internal_mini_page:
4532     \__enumext_is_not_nested:
4533     \int_incr:N \l__enumext_level_h_int
4534     \int_compare:nNnT { \l__enumext_level_h_int } > { 1 }
4535     {
4536         \msg_error:nn { enumext } { nested }
4537     }
4538     \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
4539     {
4540         \msg_error:nnn { enumext } { nested-horizontal } { keyans*}
4541     }
4542     \bool_set_true:N \l__enumext_starred_bool
4543     \bool_set_false:N \l__enumext_standar_bool
4544     \__enumext_is_on_first_level:
4545 }

```

(End of definition for \\_\_enumext\_safe\_exec\_vii:.)

\\_\_enumext\_parse\_keys\_vii:n

First we will clear the variable \l\_\_enumext\_series\_str used by the key `series`, process the environment `[⟨key = val⟩]` and execute the function \\_\_enumext\_parse\_series:n and used by the key `series`, then we execute the function \\_\_enumext\_store\_active\_keys\_vii:n and reprocess the `⟨keys⟩` to pass them to the storage `sequence` if the key `save-key` is not active.

```

4546 \cs_new_protected:Npn \__enumext_parse_keys_vii:n #1
4547 {
4548     \tl_if_novalue:nF {#1}
4549     {
4550         \str_clear:N \l__enumext_series_str
4551         \keys_set:nn { enumext / enumext* } {#1}
4552         \__enumext_parse_series:n {#1}
4553         \__enumext_store_active_keys_vii:n {#1}
4554     }
4555 }

```

(End of definition for \\_\_enumext\_parse\_keys\_vii:n.)

`\__enumext_before_list_vii:` The function `\__enumext_before_list_vii:` first calls the function `\__enumext_vspace_above_vii:` used by the keys `above` and `above*`, then calls the function `\__enumext_check_ans_active:` for the check answer mechanism and finally calls the functions `\__enumext_before_args_exec:` and `\__enumext_start_mini_vii:` used by the keys `before*`, `mini-env`, `mini-right` and `mini-right*`.

```

4556 \cs_new_protected:Nn \__enumext_before_list_vii:
4557 {
4558     \__enumext_vspace_above_vii:
4559     \__enumext_check_ans_active:
4560     \__enumext_before_args_exec_vii:
4561     \__enumext_start_mini_vii:
4562 }

```

(End of definition for `\__enumext_before_list_vii:`.)

`\__enumext_after_list_vii:` The function `\__enumext_after_list_vii:` first calls the function `\__enumext_stop_mini_vii:` which internally calls `\__enumext_stop_list:` and `\__enumext_stop_store_level_vii:` (§13.42.3) used by the keys `mini-env`, `mini-right` and `mini-right*`, then to the functions `\__enumext_after_stop_list_vii:` used by the key `after`, `\__enumext_check_ans_key_hook:` used by the key `check-ans`, `\__enumext_vspace_below_vii:` used by the keys `below` and `below*`. Finally set `\__enumext_starred_bool` to false and call the `\__enumext_resume_save_counter:` function used by the `series`, `resume` and `resume*` keys.

```

4563 \cs_new_protected:Nn \__enumext_after_list_vii:
4564 {
4565     \__enumext_stop_mini_vii:
4566     \__enumext_after_stop_list_vii:
4567     \__enumext_check_ans_key_hook:
4568     \__enumext_vspace_below_vii:
4569     \bool_set_false:N \__enumext_starred_bool
4570     \__enumext_resume_save_counter:
4571 }

```

(End of definition for `\__enumext_after_list_vii:`.)

`\__enumext_start_store_level_vii:` and `\__enumext_stop_store_level_vii:` functions activate the “storing structure” mechanism in *sequence* for `\anskey` command and `anskey*` environment if `enumext*` are nested in `enumext`.

```

4572 \cs_new_protected:Nn \__enumext_start_store_level_vii:
4573 {
4574     \bool_if:NT \__enumext_store_active_bool
4575     {
4576         \int_compare:nNnT { \__enumext_level_int } > { 0 }
4577         {
4578             \__enumext_store_level_open_vii:
4579         }
4580     }
4581 }
4582 \cs_new_protected:Nn \__enumext_stop_store_level_vii:
4583 {
4584     \bool_if:NT \__enumext_store_active_bool
4585     {
4586         \int_compare:nNnT { \__enumext_level_int } > { 0 }
4587         {
4588             \__enumext_store_level_close_vii:
4589         }
4590     }
4591 }

```

(End of definition for `\__enumext_start_store_level_vii:` and `\__enumext_stop_store_level_vii:`.)

### 13.43.1 The command `\item` in `enumext*`

`\__enumext_first_item_tmp_vii:` The `\__enumext_first_item_tmp_vii:` function will remove horizontal space equal to `\labelwidth` plus `\labelsep` to the left of the “first” `\item` in the environment at the point of execution of this function, where it is equal to the `\__enumext_stop_item_tmp_vii:` function inside the environment body definition.

```

4592 \cs_new_protected_nopar:Nn \__enumext_first_item_tmp_vii:
4593 {
4594     \skip_horizontal:n
4595     {
4596         -\__enumext_labelwidth_vii_dim - \__enumext_labelsep_vii_dim
4597     }
4598     \ignorespaces
4599 }

```

(End of definition for `\__enumext_first_item_tmp_vii:`)

```
\__enumext_start_item_tmp_vii:
\__enumext_item_peek_args_vii:
\__enumext_joined_item_vii:w
\__enumext_standar_item_vii:w
\__enumext_starred_item_vii:w
\__enumext_starred_item_vii_aux_i:w
\__enumext_starred_item_vii_aux_ii:w
\__enumext_starred_item_vii_aux_iii:w
```

First we will call the function `\__enumext_stop_item_tmp_vii:` that we will redefine later, we will increment the value of `\l__enumext_item_column_pos_vii_int` that will count the item's by rows and the value of `\g__enumext_item_count_all_vii_int` that will count the total of item's in the environment. After that we will call the function `\__enumext_item_peek_args_vii:` that will handle the arguments passed to `\item`.

```
4600 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_vii:
4601 {
4602   \__enumext_stop_item_tmp_vii:
4603   \int_incr:N \l__enumext_item_column_pos_vii_int
4604   \int_gincr:N \g__enumext_item_count_all_vii_int
4605   \__enumext_item_peek_args_vii:
4606 }
```

The function `\__enumext_item_peek_args_vii:` will handle the `\item(<number>)`. Look for the argument “(”, if it is present we will call the function `\__enumext_joined_item_vii:w (<number>)`, which is in charge of joining the item's in the same row, in case they are not present we will set the default value (1).

```
4607 \cs_new_protected:Nn \__enumext_item_peek_args_vii:
4608 {
4609   \peek_meaning:NTF (
4610     { \__enumext_joined_item_vii:w }
4611     { \__enumext_joined_item_vii:w (1) }
4612 }
```

The function `\__enumext_joined_item_vii:w` will first call the function `\__enumext_starred_joined_item_vii:n` in charge of setting the *width* of the box that will store the content passed to `\item`. Then we will look for the argument “\*”, if it is present we will call the function `\__enumext_starred_item_vii:w` otherwise we will call the function `\__enumext_standar_item_vii:w`.

```
4613 \cs_new_protected:Npn \__enumext_joined_item_vii:w (#1)
4614 {
4615   \__enumext_starred_joined_item_vii:n {#1}
4616   \peek_meaning_remove:NTF *
4617   { \__enumext_starred_item_vii:w }
4618   { \__enumext_standar_item_vii:w }
4619 }
```

The function `\__enumext_standar_item_vii:w` will first look for the argument “[”, if present it will set the state of the variable `\l__enumext_wrap_label_opt_vii_bool` equal to the state of the variable `\l__enumext_wrap_label_opt_vii_bool` handled by the key `wrap-label*` and finally execute the *non-enumerated* version `\item[<custom>]` by means of the function `\__enumext_start_item_vii:w`, otherwise we will set the value of the variable `\l__enumext_wrap_label_vii_bool` handled by the `wrap-label` key to true and set the switch `\if@noitemarg` to true to execute the enumerated version of `\item` by means of the function `\__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]`.

```
4620 \cs_new_protected:Npn \__enumext_standar_item_vii:w
4621 {
4622   \bool_set_false:N \l__enumext_item_starred_vii_bool
4623   \peek_meaning:NTF [
4624     {
4625       \bool_set_eq:NN \l__enumext_wrap_label_vii_bool \l__enumext_wrap_label_opt_vii_bool
4626       \__enumext_start_item_vii:w
4627     }
4628     {
4629       \bool_set_true:N \l__enumext_wrap_label_vii_bool
4630       \legacy_if_set_true:n { @noitemarg }
4631       \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ] \ignorespaces
4632     }
4633 }
```

The function `\__enumext_starred_item_vii:w` together with the specified auxiliary functions `aux_i:w`, `aux_ii:w`, and `aux_iii:w` execute `\item*`, `\item* [<symbol>]` and `\item* [<symbol>] [<offset>]`.

```
4634 \cs_new_protected:Npn \__enumext_starred_item_vii:w
4635 {
4636   \bool_set_true:N \l__enumext_item_starred_vii_bool
4637   \bool_set_true:N \l__enumext_wrap_label_vii_bool
4638   \peek_meaning:NTF [
4639     { \__enumext_starred_item_vii_aux_i:w }
4640     { \__enumext_starred_item_vii_aux_ii:w }
4641   }
4642   \cs_new_protected:Npn \__enumext_starred_item_vii_aux_i:w [#1]
4643   {
```

```

4644 \tl_gset:Nn \g__enumext_item_symbol_aux_vii_tl {#1}
4645 \__enumext_starred_item_vii_aux_ii:w
4646 }
4647 \cs_new_protected:Npn \__enumext_starred_item_vii_aux_ii:w
4648 {
4649   \peek_meaning:NTF [
4650     { \__enumext_starred_item_vii_aux_iii:w }
4651     {
4652       \dim_set_eq:NN \l__enumext_item_symbol_sep_vii_dim \l__enumext_labelsep_vii_dim
4653       \legacy_if_set_true:n { @noitemarg }
4654       \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ] \ignorespaces
4655     }
4656   }
4657 \cs_new_protected:Npn \__enumext_starred_item_vii_aux_iii:w [#1]
4658 {
4659   \dim_set:Nn \l__enumext_item_symbol_sep_vii_dim {#1}
4660   \legacy_if_set_true:n { @noitemarg }
4661   \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ] \ignorespaces
4662 }

```

(End of definition for `\__enumext_start_item_tmp_vii:` and others.)

`\__enumext_fake_make_label_vii:n`

The `\__enumext_fake_make_label_vii:n` function will be in charge of handling our definition of `\item`. First we increment the counter `enumXvii` for the enumerated items and activate support for the *check answers* mechanism, followed by support for `\item*[\langle symbol \rangle][\langle offset \rangle]` if present, then the `wrap-label` and `wrap-label*` keys which we execute using `\makebox` whose width will be given by the `labelwidth` key and position by the `align` key, inside the argument of this we will execute the `font` key together with the function defined by the `wrap-label` or `wrap-label*` keys. Finally we execute the `labelsep` key applying a `\skip_horizontal:N` and `\ignorespaces`.

- For compatibility with *tagged* PDF and `hyperref` when an environment `enumext` is nested in `enumext*` and the key `save-ans` is not active need setting the `\if@hyper@item` switch to “true”. The explanation for this is given by the master Heiko Oberdiek on `\refstepcounter{enumi}` twice (or more) creates destination with the same identifier. This patch is only needed if you are running `pdflatex` and not if you are running `lualatex`

```

4663 \cs_new_protected_nopar:Npn \__enumext_fake_make_label_vii:n #1
4664 {
4665   \legacy_if:nT { @noitemarg }
4666   {
4667     \legacy_if_set_false:n { @noitemarg }
4668     \legacy_if:nT { @nmbrrlist }
4669     {
4670       \IfDocumentMetadataTF
4671       {
4672         \bool_if:NT \l__enumext_hyperref_bool
4673         {
4674           \legacy_if_set_true:n { @hyper@item }
4675         }
4676       } { }
4677       \refstepcounter{enumXvii}
4678       \bool_if:NT \l__enumext_check_answers_bool
4679       {
4680         \int_gincr:N \g__enumext_item_number_int
4681         \bool_set_true:N \l__enumext_item_number_bool
4682       }
4683     }
4684   }
4685   \bool_if:NT \l__enumext_item_starred_vii_bool
4686   {
4687     \tl_if_blank:VT \g__enumext_item_symbol_aux_vii_tl
4688     {
4689       \tl_gset_eq:NN
4690       \g__enumext_item_symbol_aux_vii_tl \l__enumext_item_symbol_vii_tl
4691     }
4692     \mode_leave_vertical:
4693     \skip_horizontal:n { -\l__enumext_item_symbol_sep_vii_dim }
4694     \hbox_overlap_left:n { \g__enumext_item_symbol_aux_vii_tl }
4695     \skip_horizontal:N \l__enumext_item_symbol_sep_vii_dim
4696     \tl_gclear:N \g__enumext_item_symbol_aux_vii_tl
4697   }
4698   \makebox[ \l__enumext_labelwidth_vii_dim ][ \l__enumext_align_label_vii_str ]
4699   {

```

```

4700         \tl_use:N \l__enumext_label_font_style_vii_tl
4701         \bool_if:NTF \l__enumext_wrap_label_vii_bool
4702         {
4703             \__enumext_wrapper_label_vii:n {#1}
4704         }
4705         { #1 }
4706     }
4707     \skip_horizontal:N \l__enumext_labelsep_vii_dim \ignorespaces
4708 }

```

(End of definition for `\__enumext_fake_make_label_vii:n`.)

### 13.43.2 Real definition of `\item` in `enumext*`

The functions `\__enumext_start_item_vii:w` and `\__enumext_stop_item_vii:` executing the true definition of `\item` inside the `enumext*` environment, unlike the implementation in `shortlst` we will NOT use an extra group and the plain form of the `lrbox` environment.

```

\__enumext_start_item_vii:w
\__enumext_stop_item_vii:

```

The first thing we will do is set the value of `\__enumext_stop_item_tmp_vii:` equal to `\__enumext_stop_item_vii:` which we will define later, after that we will start capturing `\item` and “*item content*” in a *horizontal box* where the width will be `\itemwidth` plus `\labelwidth` plus `\labelsep`.

```

4709 \cs_new_protected_nopar:Npn \__enumext_start_item_vii:w [#1]
4710 {
4711     \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \__enumext_stop_item_vii:
4712     \hbox_set_to_wd:Nnw \l__enumext_item_text_vii_box
4713     {
4714         \l__enumext_joined_width_vii_dim + \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim
4715     }

```

If `\DocumentMetadata` is not active and the state of the variable `\l__enumext_footnotes_key_bool` is false, we will redefine the `\footnote` command.

```

4716     \IfDocumentMetadataTF { }
4717     {
4718         \bool_if:NF \l__enumext_footnotes_key_bool
4719         {
4720             \__enumext_renew_footnote:
4721         }
4722     }

```

Now we insert our *sockets* for *tagging* PDF support and run `\item`.

```

4723     \__enumext_start_list_tag:n {enumext*}
4724     \__enumext_fake_make_label_vii:n {#1}
4725     \__enumext_stop_start_list_tag:

```

Finally we open the `minipage` environment, capture the “*item content*” and execute `first` and `itemindent` keys, then `listparindent` key which will be equal to `\parindent`, then `parsep` key which will be equal to `\parskip`.

```

4726     \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_vii_dim }
4727     \dim_set_eq:NN \parindent \l__enumext_listparindent_vii_dim
4728     \skip_set_eq:NN \parskip \l__enumext_parsep_vii_skip
4729     \__enumext_unskip_unkern:
4730     \__enumext_unskip_unkern:
4731     \skip_horizontal:n { -\l__enumext_listparindent_vii_dim } \ignorespaces\noindent
4732     \tl_use:N \l__enumext_fake_item_indent_vii_tl
4733     \tl_use:N \l__enumext_after_list_args_vii_tl
4734 }

```

The `\__enumext_stop_item_vii:` function will finish the fetching `\item` and “*item content*” by closing the `minipage` environment, the *sockets* for *tagging* PDF and the *horizontal box*.

```

4735 \cs_new_protected_nopar:Nn \__enumext_stop_item_vii:
4736 {
4737     \__enumext_endminipage:
4738     \__enumext_stop_list_tag:n {enumext*}
4739     \hbox_set_end:

```

Here we will reduce the *warnings* a bit by setting the value of `\hbadness` to `10000`, print `\item` and “*item content*” from the *horizontal box* and *footnotes* if it was redefined.

```

4740     \int_set:Nn \hbadness { 10000 }
4741     \box_use_drop:N \l__enumext_item_text_vii_box
4742     \IfDocumentMetadataTF { }
4743     {
4744         \bool_if:NF \l__enumext_footnotes_key_bool
4745         {

```

```

4746         \__enumext_print_footnote:
4747     }
4748 }

```

Finally apply the *vertical space* between rows set by `itemsep` key passed to `\parsep` using `\par\noindent` and *horizontal space* between columns set by `columns-sep` key using `\skip_horizontal:N`.

```

4749 \int_compare:nNnTF
4750 { \__enumext_item_column_pos_vii_int } = { \__enumext_columns_vii_int }
4751 {
4752     \par\noindent
4753     \int_zero:N \__enumext_item_column_pos_vii_int
4754 }
4755 {
4756     \skip_horizontal:N \__enumext_columns_sep_vii_dim
4757 }
4758 }

```

(End of definition for `\__enumext_start_item_vii:w` and `\__enumext_stop_item_vii:.`)

`\__enumext_remove_extra_parsep_vii:`

Remove the extra *vertical space* equal to `\parsep=\itemsep` when the total number of `\item` is divisible by the number of `\item` in the last row of the environment. Here the use of `\unskip` or `\removeatlastskip` fails and does not obtain the expected result, using `\vspace` is the option and in this case, we can use a simplified version since we are always in (*vertical mode*).

```

4759 \cs_new_protected:Nn \__enumext_remove_extra_parsep_vii:
4760 {
4761     \int_compare:nNnT
4762     {
4763         \int_mod:nn
4764         { \__enumext_item_count_all_vii_int } { \__enumext_columns_vii_int }
4765     }
4766     =
4767     { 0 }
4768     {
4769         \para_end:
4770         \skip_vertical:n { -\__enumext_itemsep_vii_skip }
4771         \skip_vertical:N \c_zero_skip
4772         \int_gzero:N \__enumext_item_count_all_vii_int
4773     }
4774 }

```

(End of definition for `\__enumext_remove_extra_parsep_vii:.`)

As we don't want our check to be executed `check-ans` by levels but on the complete list, we will take it out of the `enumext*` environment using the “hook” function `\__enumext_after_env:nn`.

```

4775 \__enumext_after_env:nn {enumext*}
4776 {
4777     \__enumext_execute_after_env:
4778 }

```

### 13.44 The environment `keyans*`

`keyans*`

The implementation of `keyans*` environment is the similar as that used by the `enumext*` environment except for the `\__enumext_check_starred_cmd:n` function added in the second part.

```

4779 \NewDocumentEnvironment{keyans*}{ o }
4780 {
4781     \__enumext_safe_exec_viii:
4782     \__enumext_parse_keys_viii:n {#1}
4783     \__enumext_before_list_viii:
4784     \__enumext_start_list:nn { }
4785     {
4786         \__enumext_list_arg_two_viii:
4787         \__enumext_before_keys_exec_viii:
4788     }
4789     \IfDocumentMetadataTF { \tag_suspend:n {keyans*} } { } { }
4790     \__enumext_starred_columns_set_viii:
4791     \item[] \scan_stop:
4792     \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \__enumext_first_item_tmp_viii:
4793     \cs_set_eq:NN \item \__enumext_start_item_tmp_viii:
4794     \ignorespaces
4795 }
4796 {
4797     \IfDocumentMetadataTF { \tag_struct_end:n {tag=text-unit} } { } { }

```



```

4798     \__enumext_stop_item_tmp_viii:
4799     \__enumext_remove_extra_parsep_viii:
4800     \__enumext_check_starred_cmd:n { item }
4801     \__enumext_after_list_viii:
4802 }

```

(End of definition for `keyans*`. This function is documented on page 14.)

`\__enumext_safe_exec_viii:`

The `\__enumext_safe_exec_viii:` function will first check if the `save-ans` key is active and only when this is true the environment will be available, it will increment the value of `\__enumext_keyans_level_h_int` and return an error message when we are nesting the environment, then it will call the `\__enumext_keyans_name_and_start:` function in charge of saving the name of the environment and the line it is running on, then it will check if we are trying to nest `keyans*` in `enumext*` returning an error and we will set `\__enumext_starred_bool` to true, finally we will check if we are within the appropriate level within the `enumext` environment.

```

4803 \cs_new_protected:Nn \__enumext_safe_exec_viii:
4804 {
4805     \bool_if:NF \__enumext_store_active_bool
4806     {
4807         \msg_error:nnnn { enumext } { wrong-place } { keyans* } { save-ans }
4808     }
4809     \int_incr:N \__enumext_keyans_level_h_int
4810     \int_compare:nNnT { \__enumext_keyans_level_h_int } > { 1 }
4811     {
4812         \msg_error:nn { enumext } { nested }
4813     }
4814     \__enumext_keyans_name_and_start:
4815     \bool_if:NT \__enumext_starred_bool
4816     {
4817         \msg_error:nnn { enumext } { nested-horizontal } { enumext* }
4818     }
4819     \bool_set_true:N \__enumext_starred_bool
4820     % Set false for interfering with enumext nested in keyans* (yes, its possible and crayze)
4821     \bool_set_false:N \__enumext_store_active_bool
4822     \int_compare:nNnT { \__enumext_level_int } > { 1 }
4823     {
4824         \msg_error:nn { enumext } { keyans-wrong-level }
4825     }
4826 }

```

(End of definition for `\__enumext_safe_exec_viii:`.)

`\__enumext_parse_keys_viii:n`

Parse [`key = val`] for `keyans*`.

```

4827 \cs_new_protected:Npn \__enumext_parse_keys_viii:n #1
4828 {
4829     \tl_if_novalue:nF {#1}
4830     {
4831         \keys_set:nn { enumext / keyans* } {#1}
4832     }
4833 }

```

(End of definition for `\__enumext_parse_keys_viii:n`.)

`\__enumext_before_list_viii:`

The function `\__enumext_before_list_viii:` will add the vertical spacing on the environment if the `above` key is active next to the `{code}` defined by the `before*` key if it is active, the call the function `\__enumext_start_mini_viii:` handle by `mini-env`.

```

4834 \cs_new_protected:Nn \__enumext_before_list_viii:
4835 {
4836     \__enumext_vspace_above_viii:
4837     \__enumext_before_args_exec_viii:
4838     \__enumext_start_mini_viii:
4839 }

```

(End of definition for `\__enumext_before_list_viii:`.)

`\__enumext_after_list_viii:`

The function `\__enumext_after_list_viii:` first call the function `\__enumext_stop_mini_viii:`, then apply the `{code}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```

4840 \cs_new_protected:Nn \__enumext_after_list_viii:
4841 {

```

```

4842     \__enumext_stop_mini_viii:
4843     \__enumext_after_stop_list_viii:
4844     \__enumext_vspace_below_viii:
4845 }

```

(End of definition for \\_\_enumext\_after\_list\_viii:.)

### 13.44.1 The command \item in keyans\*

The idea here is to make the `\item` command behave in the same way as in the `keyans` environment with the difference of the *optional argument* (`<number>`) which works in the same way as in the `enumext*` environment. In simple terms we want to store the `<label>` next to the `[<content>]` if it is present in the *sequence* and *prop list* defined by `save-ans` key for `\item*`, `\item*<content>`, `\item(<number>)*` and `\item(<number>)*<content>` commands.

`\__enumext_first_item_tmp_viii:` The `\__enumext_first_item_tmp_viii:` function will remove horizontal space equal to `\labelwidth` plus `\labelsep` to the left of the “first” `\item` in the environment at the point of execution of this function, where it is equal to the `\__enumext_stop_item_tmp_viii:` function inside the environment body definition.

```

4846 \cs_new_protected_nopar:Nn \__enumext_first_item_tmp_viii:
4847 {
4848     \skip_horizontal:n
4849     {
4850         -\__enumext_labelwidth_viii_dim - \__enumext_labelsep_viii_dim
4851     }
4852     \ignorespaces
4853 }

```

(End of definition for \\_\_enumext\_first\_item\_tmp\_viii:.)

`\__enumext_start_item_tmp_viii:` First we will call the function `\__enumext_stop_item_tmp_viii:` that we will redefine later, we will increment the value of `\l__enumext_item_column_pos_viii_int` that will count the item’s by rows and `\g__enumext_item_count_all_viii_int` that will count the total of item’s in the environment. `\__enumext_item_peek_args_viii:` After that we will call the function `\__enumext_item_peek_args_viii:` that will handle the arguments passed to `\item`.

```

4854 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_viii:
4855 {
4856     \__enumext_stop_item_tmp_viii:
4857     \int_incr:N \l__enumext_item_column_pos_viii_int
4858     \int_gincr:N \g__enumext_item_count_all_viii_int
4859     \__enumext_item_peek_args_viii:
4860 }

```

The function `\__enumext_item_peek_args_viii:` will handle the `\item(<number>)`. Look for the argument “(”, if it is present we will call the function `\__enumext_joined_item_viii:w (<number>)`, which is in charge of joining the item’s in the same row, in case they are not present we will set the default value (1).

```

4861 \cs_new_protected:Nn \__enumext_item_peek_args_viii:
4862 {
4863     \peek_meaning:NTF (
4864         { \__enumext_joined_item_viii:w }
4865         { \__enumext_joined_item_viii:w (1) }
4866     }

```

The function `\__enumext_joined_item_viii:w` will first call the function `\__enumext_starred_joined_item_viii:n` in charge of setting the *width* of the box that will store the content passed to `\item`. Then we will look for the argument “\*”, if it is present we will call the function `\__enumext_starred_item_viii:w` otherwise we will call the function `\__enumext_standar_item_viii:w`.

```

4867 \cs_new_protected:Npn \__enumext_joined_item_viii:w (#1)
4868 {
4869     \__enumext_starred_joined_item_viii:n {#1}
4870     \peek_meaning_remove:NTF *
4871     { \__enumext_starred_item_viii:w }
4872     { \__enumext_standar_item_viii:w }
4873 }

```

The function `\__enumext_standar_item_viii:w` will first look for the argument “[”, if present it will set the state of the variable `\l__enumext_wrap_label_opt_viii_bool` equal to the state of the variable `\l__enumext_wrap_label_opt_viii_bool` handled by the key `wrap-label*` and finally execute the *non-enumerated* version `\item[<custom>]` by means of the function `\__enumext_start_item_viii:w`, otherwise we will set the value of the variable `\l__enumext_wrap_label_viii_bool` handled by the `wrap-label` key to true and set the switch `\if@noitemarg` to true to execute the enumerated version of `\item` by means of the function `\__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ]`.

```

4874 \cs_new_protected:Npn \__enumext_standar_item_viii:w
4875 {
4876   \bool_set_false:N \l__enumext_item_starred_viii_bool
4877   \peek_meaning:NTF [
4878     {
4879       \bool_set_eq:NN \l__enumext_wrap_label_viii_bool \l__enumext_wrap_label_opt_viii_bool
4880       \__enumext_start_item_viii:w
4881     }
4882     {
4883       \bool_set_true:N \l__enumext_wrap_label_viii_bool
4884       \legacy_if_set_true:n { @noitemarg }
4885       \__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ] \ignorespaces
4886     }
4887   }

```

(End of definition for \\_\_enumext\_start\_item\_tmp\_viii: and others.)

```

\__enumext_starred_item_viii:w
\__enumext_starred_item_viii_aux_i:w
\__enumext_starred_item_viii_aux_ii:w
\__enumext_starred_item_exec:

```

The function \\_\_enumext\_starred\_item\_viii:w together with the specified auxiliary functions `aux_i:w` and `aux_ii:w` execute `\item*` and `\item*[\langle content \rangle]`.

```

4888 \cs_new_protected:Npn \__enumext_starred_item_viii:w
4889 {
4890   \bool_set_true:N \l__enumext_item_starred_viii_bool
4891   \bool_set_true:N \l__enumext_wrap_label_viii_bool
4892   \peek_meaning:NTF [
4893     { \__enumext_starred_item_viii_aux_i:w }
4894     { \__enumext_starred_item_viii_aux_ii:w }
4895   }

```

The function \\_\_enumext\_starred\_item\_viii\_aux\_i:w will save the *optional argument* to `\item*` in `\l__enumext_store_current_opt_arg_tl` and will save this argument along with the spacing set by the key `save-sep` in variable `\l__enumext_store_current_label_tl` if present, then call the function `\__enumext_starred_item_viii_aux_ii:w`.

```

4896 \cs_new_protected:Npn \__enumext_starred_item_viii_aux_i:w [#1]
4897 {
4898   \tl_clear:N \l__enumext_store_current_label_tl
4899   \tl_if_no_value:nF { #1 }
4900   {
4901     \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_tl
4902     {
4903       \tl_put_right:Ne \l__enumext_store_current_label_tl
4904       {
4905         \l__enumext_store_keyans_item_opt_sep_tl
4906       }
4907       \tl_put_right:Ne \l__enumext_store_current_label_tl { #1 }
4908     }
4909     \tl_set:Ne \l__enumext_store_current_opt_arg_tl { #1 }
4910   }
4911   \__enumext_starred_item_viii_aux_ii:w
4912 }
4913 \cs_new_protected:Npn \__enumext_starred_item_viii_aux_ii:w
4914 {
4915   \legacy_if_set_true:n { @noitemarg }
4916   \__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ] \ignorespaces
4917 }

```

The function \\_\_enumext\_starred\_item\_exec: will be in charge of storing the current *label* for `\item*` followed by the `[\langle content \rangle]` for `\item*[\langle content \rangle]` if present in the *sequence* and *prop list* set by the `save-ans` key. In this same function the keys `show-ans`, `show-pos` and `save-ref` are implemented.

```

4918 \cs_new_protected:Nn \__enumext_starred_item_exec:
4919 {
4920   \tl_put_left:Ne \l__enumext_store_current_label_tl { \l__enumext_label_viii_tl }
4921   \__enumext_store_addto_prop:V \l__enumext_store_current_label_tl
4922   \__enumext_keyans_store_ref:
4923   \tl_put_left:Ne \l__enumext_store_current_label_tl { \item }
4924   \__enumext_keyans_addto_seq_link:
4925   \int_gincr:N \g__enumext_check_starred_cmd_int
4926   \bool_if:NT \l__enumext_show_answer_bool
4927   {
4928     \__enumext_print_keyans_box:NN \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
4929   }
4930   \bool_if:NT \l__enumext_show_position_bool

```

```

4931     {
4932         \tl_set:Nc \l__enumext_mark_answer_sym_tl
4933         {
4934             \group_begin:
4935             \exp_not:N \normalfont
4936             \exp_not:N \footnotesize [ \int_eval:n
4937             {
4938                 \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
4939             }
4940             ]
4941             \group_end:
4942         }
4943         \__enumext_print_keyans_box:NN \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
4944     }
4945 }

```

(End of definition for \\_\_enumext\_starred\_item\_viii:w and others.)

\\_\_enumext\_fake\_make\_label\_viii:n

The implementation at this is very similar to that of the `enumext*` environment.

```

4946 \cs_new_protected_nopar:Npn \__enumext_fake_make_label_viii:n #1
4947 {
4948     \legacy_if:nT { @noitemarg }
4949     {
4950         \legacy_if_set_false:n { @noitemarg }
4951         \legacy_if:nT { @nmbrlist }
4952         {
4953             \refstepcounter{enumXviii}
4954         }
4955     }
4956     \bool_if:NT \l__enumext_item_starred_viii_bool
4957     {
4958         \__enumext_starred_item_exec:
4959     }
4960     \makebox[ \l__enumext_labelwidth_viii_dim ][ \l__enumext_align_label_viii_str ]
4961     {
4962         \tl_use:N \l__enumext_label_font_style_viii_tl
4963         \bool_if:NTF \l__enumext_wrap_label_viii_bool
4964         {
4965             \__enumext_wrapper_label_viii:n {#1}
4966         }
4967         { #1 }
4968     }
4969     \skip_horizontal:N \l__enumext_labelsep_viii_dim \ignorespaces
4970 }

```

(End of definition for \\_\_enumext\_fake\_make\_label\_viii:n.)

### 13.44.2 Real definition of \item in keyans\*

\\_\_enumext\_start\_item\_viii:w

The implementation at this is very similar to that of the `enumext*` environment.

\\_\_enumext\_stop\_item\_viii:

```

4971 \cs_new_protected_nopar:Npn \__enumext_start_item_viii:w [#1]
4972 {
4973     \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \__enumext_stop_item_viii:
4974     \hbox_set_to_wd:Nnw \l__enumext_item_text_viii_box
4975     {
4976         \l__enumext_joined_width_viii_dim
4977         + \l__enumext_labelwidth_viii_dim
4978         + \l__enumext_labelsep_viii_dim
4979     }
4980     \IfDocumentMetadataTF { }
4981     {
4982         \bool_if:NF \l__enumext_footnotes_key_bool
4983         {
4984             \__enumext_renew_footnote:
4985         }
4986     }
4987     \__enumext_start_list_tag:n {keyans*}
4988     \__enumext_fake_make_label_viii:n {#1}
4989     \__enumext_stop_start_list_tag:
4990     \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_viii_dim }
4991     \dim_set_eq:NN \parindent \l__enumext_listparindent_viii_dim
4992     \skip_set_eq:NN \parskip \l__enumext_parsep_viii_skip

```

```

4993     \__enumext_unskip_unkern:
4994     \__enumext_unskip_unkern:
4995     \skip_horizontal:n { -\l__enumext_listparindent_viii_dim } \ignorespaces\noindent
4996     \tl_use:N \l__enumext_fake_item_indent_viii_tl
4997     \bool_if:NT \l__enumext_item_starred_viii_bool
4998     {
4999         \__enumext_keyans_show_item_opt:
5000     }
5001     \tl_use:N \l__enumext_after_list_args_viii_tl
5002 }
5003 \cs_new_protected_nopar:Nn \__enumext_stop_item_viii:
5004 {
5005     \__enumext_endminipage:
5006     \__enumext_stop_list_tag:n {keyans*}
5007     \hbox_set_end:
5008     \int_set:Nn \hbadness { 10000 }
5009     \box_use_drop:N \l__enumext_item_text_viii_box
5010     \IfDocumentMetadataTF { }
5011     {
5012         \bool_if:NF \l__enumext_footnotes_key_bool
5013         {
5014             \__enumext_print_footnote:
5015         }
5016     }
5017     \int_compare:nNnTF
5018     { \l__enumext_item_column_pos_viii_int } = { \l__enumext_columns_viii_int }
5019     {
5020         \par\noindent
5021         \int_zero:N \l__enumext_item_column_pos_viii_int
5022     }
5023     {
5024         \skip_horizontal:N \l__enumext_columns_sep_viii_dim
5025     }
5026 }

```

(End of definition for \\_\_enumext\_start\_item\_viii:w and \\_\_enumext\_stop\_item\_viii:.)

\\_\_enumext\_remove\_extra\_parsep\_viii:

The implementation at this is very similar to that of the `enumext*` environment.

```

5027 \cs_new_protected:Nn \__enumext_remove_extra_parsep_viii:
5028 {
5029     \int_compare:nNnT
5030     {
5031         \int_mod:nn
5032         { \g__enumext_item_count_all_viii_int }
5033         { \l__enumext_columns_viii_int }
5034     }
5035     =
5036     { 0 }
5037     {
5038         \para_end:
5039         \skip_vertical:n { -\l__enumext_itemsep_viii_skip }
5040         \skip_vertical:N \c_zero_skip
5041         \int_gzero:N \g__enumext_item_count_all_viii_int
5042     }
5043 }

```

(End of definition for \\_\_enumext\_remove\_extra\_parsep\_viii:.)

### 13.45 The command \getkeyans

\getkeyans  
\\_\_enumext\_getkeyans\_aux:n  
\\_\_enumext\_getkeyans:n

The `\getkeyans` command takes a *mandatory argument* of the form  $\langle \textit{store name} : \textit{position} \rangle$ . Retrieve a “single content” stored by `\anskey`, `\anspic*` and `\item*` and `anskey*` from *prop list* defined by `save-ans` key.

```

5044 \NewDocumentCommand \getkeyans { m }
5045 {
5046     \exp_args:Ne \__enumext_getkeyans_aux:n
5047     { \tl_to_str:e { \text_expand:n {#1} } }
5048 }

```

The internal function `\__enumext_getkeyans_aux:n` is in charge of *splitting* the *mandatory argument* using “.”. If “.” is omitted it will return an error.

```

5049 \cs_new_protected:Npn \__enumext_getkeyans_aux:n #1

```

```

5050 {
5051   \str_if_in:nnTF {#1} { : }
5052   {
5053     \use:e
5054     {
5055       \cs_set:Npn \exp_not:N \__enumext_tmp:w #1 \c_colon_str ##2 \scan_stop:
5056       { {##1} {##2} }
5057     }
5058     \exp_after:wN \__enumext_getkeyans:nn \__enumext_tmp:w #1 \scan_stop:
5059   }
5060   { \msg_error:nnn { enumext } { missing-colon } {#1} }
5061 }

```

The internal function `\__enumext_getkeyans:nn` will check for the existence of the *prop list*, if it does not exist it will return an error message, then it will fetch the content specified by the *second argument* from *prop list*.

```

5062 \cs_new_protected:Npn \__enumext_getkeyans:nn #1 #2
5063 {
5064   \prop_if_exist:cTF { g__enumext_#1_prop }
5065   {
5066     \prop_item:cn { g__enumext_#1_prop }{#2}
5067   }
5068   {
5069     \msg_error:nnn { enumext } { undefined-storage-anskey } {#1}
5070   }
5071 }

```

(End of definition for `\getkeyans`, `\__enumext_getkeyans_aux:n`, and `\__enumext_getkeyans:nn`. This function is documented on page 17.)

### 13.46 The command `\printkeyans`

The `\printkeyans` command prints “all stored content” in the *sequence* defined by the `save-ans` key.

The first thing we will do is define a set of *filtered keys* with which we will control the options of the different nesting levels for the environment `enumext` and `enumext*` by storing their values in the list of tokens `\l__enumext_print_keyans_X_tl`.

The variable `\l__enumext_print_keyans_starred_tl` will have the default *keys* for `\printkeyans*` and will be set by `\setenumext[⟨print*⟩]` and the variable `\l__enumext_print_keyans_vii_tl` will have the default keys for the environment `enumext*` nested within the *sequence* and will be set by `\setenumext[⟨print,*⟩]`, the rest of the variables will be for the environment `enumext` and will be set by `\setenumext[⟨print,level⟩]`.

```

5072 \keys_define:nn { enumext / print }
5073 {
5074   print* .code:n      = \keys_precompile:neN { enumext / enumext* }
5075                   { \__enumext_filter_save_key:n {#1} }
5076                   \l__enumext_print_keyans_starred_tl, % starred cmd
5077   print* .initial:n   = { nosep, label=\arabic*, columns=2, first=\small, font=\small },
5078   print-1 .code:n     = \keys_precompile:neN { enumext / level-1 }
5079                   { \__enumext_filter_save_key:n {#1} }
5080                   \l__enumext_print_keyans_i_tl,
5081   print-1 .initial:n  = { nosep, label=\arabic*, columns=2, first=\small, font=\small },
5082   print-2 .code:n     = \keys_precompile:neN { enumext / level-2 }
5083                   { \__enumext_filter_save_key:n {#1} }
5084                   \l__enumext_print_keyans_ii_tl,
5085   print-2 .initial:n  = { nosep, label=\alph*, first=\small, font=\small },
5086   print-3 .code:n     = \keys_precompile:neN { enumext / level-3 }
5087                   { \__enumext_filter_save_key:n {#1} }
5088                   \l__enumext_print_keyans_iii_tl,
5089   print-3 .initial:n  = { nosep, label=\roman*, first=\small, font=\small },
5090   print-4 .code:n     = \keys_precompile:neN { enumext / level-4 }
5091                   { \__enumext_filter_save_key:n {#1} }
5092                   \l__enumext_print_keyans_iv_tl,
5093   print-4 .initial:n  = { nosep, label=\Alph*, first=\small, font=\small },
5094   print-* .code:n     = \keys_precompile:neN { enumext / enumext* }
5095                   { \__enumext_filter_save_key:n {#1} }
5096                   \l__enumext_print_keyans_vii_tl, % starred nested
5097   print-* .initial:n  = { nosep, label=\arabic*, first=\small, font=\small },
5098 }

```

- The reason for storing *keys* in token lists using `\keys_precompile:neN` is because the keys are set via `\setenumext` but are later executed by running the command `\printkeyans` and they are not handled directly by its *optional argument*, except those related to the *first* opening level.

```
\printkeyans
\__enumext_printkeyans:nnn
```

Create a user command to print “*all stored content*” in *sequence* for `\anskey`, `anskey*`, `\item*` and `\anspic*`. Within a group we will run our “*precompiled keys*” and then call the internal function `\__enumext_printkeyans:nnn`.

```
5099 \NewDocumentCommand \printkeyans { s O{} m }
5100 {
5101   \group_begin:
5102     \tl_use:N \l__enumext_print_keyans_i_tl
5103     \tl_use:N \l__enumext_print_keyans_ii_tl
5104     \tl_use:N \l__enumext_print_keyans_iii_tl
5105     \tl_use:N \l__enumext_print_keyans_iv_tl
5106     \tl_use:N \l__enumext_print_keyans_vii_tl
5107     \__enumext_printkeyans:nnn { #1 } { #2 } { #3 }
5108   \group_end:
5109 }
```

The internal function `\__enumext_printkeyans:nnn` will check for the existence of the *sequence*, if it does not exist it will return an error message, then it will check if not empty.

```
5110 \cs_new_protected:Npn \__enumext_printkeyans:nnn #1 #2 #3
5111 {
5112   \seq_if_exist:cTF { g__enumext_#3_seq }
5113   {
5114     \seq_if_empty:cF { g__enumext_#3_seq }
5115     {
```

If the *starred argument* ‘*\**’ is present we will check that the environment `enumext*` is not saved in the *sequence*, then execute the variable `\l__enumext_print_keyans_starred_tl` that contains the default `⟨keys⟩` for the environment `enumext*`, we set `\l__enumext_base_line_fix_bool` and `\l__enumext_print_keyans_star_bool` to true for *baseline correction*, open the `enumext*` environment passing the *optional argument* and map the *sequence*, then set `\l__enumext_base_line_fix_bool` and `\l__enumext_print_keyans_star_bool` to false.

```
5116       \bool_if:nTF {#1}
5117       {
5118         \seq_if_in:cnTF { g__enumext_#3_seq } { \end{enumext*} }
5119         {
5120           \msg_error:nnnn { enumext } { print-starred } { #3 } { enumext* }
5121         }
5122         {
5123           \tl_use:N \l__enumext_print_keyans_starred_tl
5124           \bool_set_true:N \l__enumext_base_line_fix_bool
5125           \bool_set_true:N \l__enumext_print_keyans_star_bool
5126           \begin{enumext*}[#2]
5127             \seq_map_inline:cn { g__enumext_#3_seq } { ##1 }
5128             \end{enumext*}
5129           \bool_set_false:N \l__enumext_base_line_fix_bool
5130           \bool_set_false:N \l__enumext_print_keyans_star_bool
5131         }
5132       }
```

Otherwise it will open the environment `enumext` passing the *optional argument* to the “*first level*” then map the *sequence*.

```
5133       {
5134         \begin{enumext}[#2]
5135         \seq_map_inline:cn { g__enumext_#3_seq } { ##1 }
5136         \end{enumext}
5137       }
5138     }
5139   }
5140   {
5141     \msg_error:nnn { enumext } { undefined-storage-anskey } { #3 }
5142   }
5143 }
```

(End of definition for `\printkeyans` and `\__enumext_printkeyans:nnn`. This function is documented on page 17.)

### 13.47 The command `\setenumext`

The command `\setenumext` will be in charge of managing the `⟨keys⟩` passed to all environments and to the `\printkeyans` command. We must take precautions with the `enumext*` environment and “*first level*” of the `enumext` environment so as not to capture `⟨keys⟩` that complicate us.

```
\__enumext_filter_first_level:n
\__enumext_filter_first_level_key:n
\__enumext_filter_first_level_pair:nn
```

The function `\__enumext_filter_first_level:n` will be in charge of filtering the `⟨keys⟩` passed to the environment `enumext*` and “*first level*” of the environment `enumext`.



```

5144 \cs_new:Npn \__enumext_filter_first_level:n #1
5145 {
5146   \use:e
5147   {
5148     \keyval_parse:NNn
5149     \__enumext_filter_first_level_key:n
5150     \__enumext_filter_first_level_pair:nn {#1}
5151   }
5152 }

```

The function `\__enumext_filter_first_level_key:n` will be responsible for filtering the *⟨keys⟩* that are passed “without value” by excluding the keys `resume` and `resume*`.

```

5153 \cs_new:Npn \__enumext_filter_first_level_key:n #1
5154 {
5155   \str_case:nnF {#1}
5156   {
5157     { resume } {}
5158     { resume* } {}
5159   }
5160   { , { \exp_not:n {#1} } }
5161 }

```

The function `\__enumext_filter_first_level_pair:nn` will be responsible for filtering the *⟨keys⟩* that are passed “with value” by excluding the `series`, `resume` and `save-ans` keys.

```

5162 \cs_new:Npn \__enumext_filter_first_level_pair:nn #1#2
5163 {
5164   \str_case:nnF {#1}
5165   {
5166     { series } {}
5167     { resume } {}
5168     { save-ans } {}
5169   }
5170   { , { \exp_not:n {#1} } = { \exp_not:n {#2} } }
5171 }

```

(End of definition for `\__enumext_filter_first_level:n`, `\__enumext_filter_first_level_key:n`, and `\__enumext_filter_first_level_pair:nn`.)

Now define a “meta families” of *⟨keys⟩* to access from `\setenumext`.

```

5172 \keys_define:nn { enumext / meta-families }
5173 {
5174   enumext-1 .code:n =
5175   {
5176     \keys_set:ne { enumext / level-1 }
5177     {
5178       \__enumext_filter_first_level:n {#1}
5179     }
5180   } ,
5181   enumext-2 .code:n = { \keys_set:nn { enumext / level-2 } {#1} } ,
5182   enumext-3 .code:n = { \keys_set:nn { enumext / level-3 } {#1} } ,
5183   enumext-4 .code:n = { \keys_set:nn { enumext / level-4 } {#1} } ,
5184   keyans .code:n = { \keys_set:nn { enumext / keyans } {#1} } ,
5185   enumext* .code:n =
5186   {
5187     \keys_set:ne { enumext / enumext* }
5188     {
5189       \__enumext_filter_first_level:n {#1}
5190     }
5191   } ,
5192   keyans* .code:n = { \keys_set:nn { enumext / keyans* } {#1} } ,
5193   print* .code:n = { \keys_set:nn { enumext / print } { print* = {#1} } } ,
5194   print-1 .code:n = { \keys_set:nn { enumext / print } { print-1 = {#1} } } ,
5195   print-2 .code:n = { \keys_set:nn { enumext / print } { print-2 = {#1} } } ,
5196   print-3 .code:n = { \keys_set:nn { enumext / print } { print-3 = {#1} } } ,
5197   print-4 .code:n = { \keys_set:nn { enumext / print } { print-4 = {#1} } } ,
5198   print-* .code:n = { \keys_set:nn { enumext / print } { print-* = {#1} } } ,
5199   unknown .code:n = { \msg_error:nn { enumext } { unknown-key-family } } ,
5200 }

```

We store them in the constant sequence `\c__enumext_all_families_seq` separated by commas.

```

5201 \seq_const_from_clist:Nn \c__enumext_all_families_seq
5202 {
5203   enumext-1, enumext-2, enumext-3, enumext-4, keyans, enumext*,

```

```

5204     keyans*, print-1, print-2, print-3, print-4, print-*, print*,
5205 }

```

`\setenumext` Now we define the user command `\setenumext`.

```

\__enumext_set_parse:n
\__enumext_set_error:nn
5206 \NewDocumentCommand \setenumext { 0{enumext,1} +m }
5207 {
5208     \seq_clear:N \l__enumext_setkey_tmpa_seq
5209     \seq_set_from_clist:Nn \l__enumext_setkey_tmpb_seq {#1}
5210     \int_set:Nn \l__enumext_setkey_tmpa_int
5211     {
5212         \seq_count:N \l__enumext_setkey_tmpb_seq
5213     }
5214     \int_compare:nNnTF { \l__enumext_setkey_tmpa_int } > { 1 }
5215     {
5216         \seq_pop_left:NN \l__enumext_setkey_tmpb_seq \l__enumext_setkey_tmpa_tl
5217         \seq_map_function:NN \l__enumext_setkey_tmpb_seq \__enumext_set_parse:n
5218         \seq_set_map_e:NNn \l__enumext_setkey_tmpa_seq \l__enumext_setkey_tmpa_seq
5219         {
5220             \tl_use:N \l__enumext_setkey_tmpa_tl - ##1
5221         }
5222     }
5223     {
5224         \seq_put_right:Ne \l__enumext_setkey_tmpa_seq { \tl_trim_spaces:n {#1} }
5225     }
5226     \seq_if_empty:NNTF \l__enumext_setkey_tmpa_seq
5227     { \seq_map_inline:Nn \c__enumext_all_families_seq }
5228     { \seq_map_inline:Nn \l__enumext_setkey_tmpa_seq }
5229     {
5230         \keys_set:nn { enumext / meta-families } { ##1 = {#2} }
5231     }
5232 }

```

Internal functions used by the `\setenumext` command.

```

5233 \cs_new_protected:Npn \__enumext_set_parse:n #1
5234 {
5235     \tl_set:Ne \l__enumext_setkey_tmpb_tl { \tl_trim_spaces:n {#1} }
5236     \clist_map_inline:nn { 0, 1, 2, 3, 4, * } % <- max level
5237     { \tl_remove_all:Nn \l__enumext_setkey_tmpb_tl {##1} }
5238     \tl_if_empty:NNTF \l__enumext_setkey_tmpb_tl
5239     {
5240         \seq_put_right:Ne \l__enumext_setkey_tmpa_seq
5241         { \tl_trim_spaces:n {#1} }
5242     }
5243     { \__enumext_set_error:nn {#1} { } }
5244 }
5245 \cs_new_protected:Npn \__enumext_set_error:nn #1 #2
5246 { \msg_error:nnn { enumext } { invalid-key } {#1} {#2} }

```

(End of definition for `\setenumext`, `\__enumext_set_parse:n`, and `\__enumext_set_error:nn`. This function is documented on page 6.)

### 13.48 The command `\setenumextmeta`

The command `\setenumextmeta` will be responsible for adding new “meta-keys” for the `enumext` and `enumext*` environments. The implementation code was given by Jonathan P. Spratte (@Skillmon) answer in [Add .meta key to existing keys \(l3keys\)](#).

`\setenumextmeta` First we will create a prop list `\c__enumext_meta_paths_prop` to handle the *optional argument*.

```

\c__enumext_meta_paths_prop
\__enumext_add_meta_key:nnn
\__enumext_def_meta_key:nnn
\__enumext_def_meta_key:Vnn
5247 \prop_const_from_keyval:Nn \c__enumext_meta_paths_prop
5248 {
5249     {enumext,1} = level-1,
5250     {enumext,2} = level-2,
5251     {enumext,3} = level-3,
5252     {enumext,4} = level-4,
5253     {enumext*} = enumext*
5254 }

```

Now we create the user command taking care that unknown cannot be passed as an argument.

```

5255 \NewDocumentCommand \setenumextmeta { s 0{enumext,1} m +m }
5256 {
5257     \str_if_eq:eeTF { \tl_trim_spaces:n {#3} } { unknown }
5258     { \msg_error:nn { enumext } { prohibited-unknown } }

```

```

5259     {
5260         \bool_if:nTF {#1}
5261         {
5262             \int_step_inline:nn { 4 }
5263             { \__enumext_add_meta_key:nnn { enumext, ##1 } {#3} {#4} }
5264             \__enumext_add_meta_key:nnn { enumext* } {#3} {#4}
5265         }
5266         { \__enumext_add_meta_key:nnn {#2} {#3} {#4} }
5267     }
5268 }

```

The internal functions `\__enumext_add_meta_key:nnn` and `\__enumext_def_meta_key:nnn` will check the *optional argument* and create the “*meta-key*”.

```

5269 \cs_new_protected:Npn \__enumext_add_meta_key:nnn #1
5270 {
5271     \tl_set:Nn \l__enumext_meta_path_tl {#1}
5272     \tl_replace_all:Nnn \l__enumext_meta_path_tl { ~ } {}
5273     \prop_get:NVNTF
5274     \c__enumext_meta_paths_prop \l__enumext_meta_path_tl \l__enumext_meta_path_tl
5275     { \__enumext_def_meta_key:Vnn \l__enumext_meta_path_tl }
5276     {
5277         \msg_error:nnn { enumext } { unknown-set } {#1}
5278         \use_none:nn
5279     }
5280 }
5281 \cs_new_protected:Npn \__enumext_def_meta_key:nnn #1#2#3
5282 {
5283     \bool_lazy_or:nnTF
5284     { \keys_if_exist_p:nn { enumext / #1 } {#2} }
5285     { \keys_if_exist_p:nn { enumext / enumext* } {#2} }
5286     { \msg_error:nnn { enumext } { already-defined } {#2} }
5287     {
5288         \keys_define:nn { enumext / #1 }
5289         {
5290             #2 .meta:n = {#3},
5291             #2 .value_forbidden:n = true
5292         }
5293     }
5294 }
5295 \cs_generate_variant:Nn \__enumext_def_meta_key:nnn { V }

```

(End of definition for `\setenumextmeta` and others. This function is documented on page 6.)

### 13.49 The command `\foreachkeyans`

The command `\foreachkeyans` will execute a *loop* over the *prop list* and return its contents. The implementation code is adapted from the answer provided by Enrico Gregorio (@egreg) in [Expand a .cs defined by key inside the function](#).

`\foreachkeyans`

`\__enumext_parse_foreach_keys:nn`

`\__enumext_parse_foreach_keys:n`

`\__enumext_foreach_keyans:nn`

`\__enumext_foreach_add_body:n`

We define a set of *⟨keys⟩* for command and we will save the default values of these in `\g__enumext_foreach_default_keys_tl` to avoid the use of group.

```

5296 \keys_define:nn { enumext / foreach }
5297 {
5298     before .tl_set:N = \l__enumext_foreach_before_tl,
5299     before .value_required:n = true,
5300     after .tl_set:N = \l__enumext_foreach_after_tl,
5301     after .value_required:n = true,
5302     start .int_set:N = \l__enumext_foreach_start_int,
5303     start .value_required:n = true,
5304     stop .int_set:N = \l__enumext_foreach_stop_int,
5305     stop .value_required:n = true,
5306     step .int_set:N = \l__enumext_foreach_step_int,
5307     step .value_required:n = true,
5308     wrapper .cs_set_protected:Np = \__enumext_foreach_wrapper:n #1,
5309     wrapper .value_required:n = true,
5310     sep .tl_set:N = \l__enumext_foreach_sep_tl,
5311     sep .value_required:n = true,
5312     unknown .code:n = { \__enumext_parse_foreach_keys:n {#1} }
5313 }
5314 \keys_precompile:nnN { enumext / foreach }
5315 {
5316     before={},after={},start=1,step=1,stop=0,wrapper=#1,sep={; }

```

```

5317 }
5318 \g__enumext_foreach_default_keys_tl

```

Functions for handling unknown  $\langle keys \rangle$ .

```

5319 \cs_new_protected:Npn \__enumext_parse_foreach_keys:nn #1#2
5320 {
5321   \tl_if_blank:nTF {#2}
5322   {
5323     \msg_error:nnn { enumext } { for-key-unknown } {#1}
5324   }
5325   {
5326     \msg_error:nnnn { enumext } { for-key-value-unknown } {#1} {#2}
5327   }
5328 }
5329 \cs_new_protected:Npn \__enumext_parse_foreach_keys:n #1
5330 {
5331   \exp_args:NV \__enumext_parse_foreach_keys:nn \l_keys_key_str {#1}
5332 }

```

We create the command.

```

5333 \NewDocumentCommand \foreachkeyans { +0{} m }
5334 {
5335   \__enumext_foreach_keyans:nn {#1} {#2}
5336 }

```

Finally the internal functions  $\backslash\_enumext\_foreach\_keyans:nn$  and  $\backslash\_enumext\_foreach\_add\_body:n$  will loop through the prop list and print the contents.

```

5337 \cs_new_protected:Npn \__enumext_foreach_keyans:nn #1 #2
5338 {
5339   \tl_use:N \g__enumext_foreach_default_keys_tl
5340   \keys_set:nn { enumext / foreach } {#1}
5341   \tl_set:Nn \l__enumext_foreach_name_prop_tl {#2}
5342   \prop_if_exist:cF { g__enumext_#2_prop }
5343   {
5344     \msg_error:nnn { enumext } { undefined-storage-anskey } {#2}
5345   }
5346   \int_compare:nNt { \l__enumext_foreach_stop_int } = { 0 }
5347   {
5348     \int_set:Nn \l__enumext_foreach_stop_int
5349     { \prop_count:c { g__enumext_#2_prop } }
5350   }
5351   \seq_clear:N \l__enumext_foreach_print_seq
5352   \int_step_function:nnnN
5353   { \l__enumext_foreach_start_int }
5354   { \l__enumext_foreach_step_int }
5355   { \l__enumext_foreach_stop_int }
5356   \__enumext_foreach_add_body:n
5357   \seq_use:NV \l__enumext_foreach_print_seq \l__enumext_foreach_sep_tl
5358 }
5359 \cs_new_protected:Npn \__enumext_foreach_add_body:n #1
5360 {
5361   \seq_put_right:Ne \l__enumext_foreach_print_seq
5362   {
5363     \exp_not:V \l__enumext_foreach_before_tl
5364     \__enumext_foreach_wrapper:n
5365     {
5366       \prop_item:cn { g__enumext_ \l__enumext_foreach_name_prop_tl _prop }{#1}
5367     }
5368     \exp_not:V \l__enumext_foreach_after_tl
5369   }
5370 }

```

(End of definition for  $\backslash foreachkeyans$  and others. This function is documented on page 17.)

### 13.50 Messages

Message used by package-load for **multicol** and **hyperref** packages.

```

5371 \msg_new:nnn { enumext } { package-load }
5372 {
5373   The ~ '#1' ~ package ~ is ~ already ~ loaded.
5374 }
5375 \msg_new:nnn { enumext } { package-not-load }
5376 {

```

```

5377     The ~ '#1' ~ package ~ will ~ be ~ loaded ~ as ~ a ~ dependency.
5378 }
5379 \msg_new:nnn { enumext } { package-load-foot }
5380 {
5381     The ~ '#1' ~ package ~ is ~ loaded ~ with ~ the ~ option ~ '#2'.
5382 }

```

Message used in the creation of counters by `enumext` package.

```

5383 \msg_new:nnn { enumext } { counters }
5384 {
5385     The ~ counter ~ '#1' ~ is ~ already ~ defined ~ by ~ some ~ \\
5386     package ~ or ~ macro, ~ it ~ cannot ~ be ~ continued.
5387 }

```

Message used by `align` and `mark-pos` keys.

```

5388 \msg_new:nnn { enumext } { unknown-choice }
5389 {
5390     The ~ value ~ '#3' ~ for ~ '#1' ~ key ~ is ~ invalid ~ use ~ ('#2').
5391 }

```

Message used by reserved `anskey*` environment by `enumext` package.

```

5392 \msg_new:nnnn { enumext } { anskey-env-error }
5393 {
5394     The ~ '#1' ~ environment ~is~ ~ reserved ~ by ~\\
5395     'enumext' ~ package, ~ It~ is~ already~ defined.
5396 }
5397 {
5398     The ~ anskey* ~ environment ~ is ~ defined ~ internally ~
5399     for ~ the ~ 'save-ans' ~ key.\\
5400 }

```

Message used in the creation of *prop list* by `enumext` package.

```

5401 \msg_new:nnn { enumext } { store-prop }
5402 {
5403     * ~ Package ~ enumext: ~ Creating ~
5404     \c_backslash_str g__enumext_#1_prop ~ \msg_line_context:.
5405 }
5406 \msg_new:nnn { enumext } { store-seq }
5407 {
5408     * ~ Package ~ enumext: ~ Creating ~
5409     \c_backslash_str g__enumext_#1_seq ~ \msg_line_context:.
5410 }
5411 \msg_new:nnn { enumext } { store-int }
5412 {
5413     * ~ Package ~ enumext: ~ Creating ~
5414     \c_backslash_str g__enumext_resume_#1_int ~ \msg_line_context:.
5415 }
5416 \msg_new:nnn { enumext } { prop-seq-int-hook }
5417 {
5418     * ~ Package ~ enumext: ~ Elements ~ in ~
5419     \c_backslash_str g__enumext_#1_prop ~ = ~ #2.\\
5420     * ~ Package ~ enumext: ~ Elements ~ in ~
5421     \c_backslash_str g__enumext_#1_seq ~ = ~ #3.\\
5422     * ~ Package ~ enumext: ~ Value ~ off ~
5423     \c_backslash_str g__enumext_resume_#1_int ~ = ~ #4.
5424 }
5425 \msg_new:nnn { enumext } { item-answer-hook }
5426 {
5427     * ~ Package ~ enumext: ~ Value ~ off ~
5428     \c_backslash_str g__enumext_item_number_int ~ = ~ #1.\\
5429     * ~ Package ~ enumext: ~ Value ~ off ~
5430     \c_backslash_str g__enumext_item_anskey_int ~ = ~ #2.\\
5431     * ~ Package ~ enumext: ~ Difference ~ item_number_int ~ - ~ item_anskey_int ~ = ~ #3.
5432 }

```

Message used by [`(key = val)`] system and `\setenumext` command.

```

5433 \msg_new:nnn { enumext } { invalid-key }
5434 {
5435     The ~ key ~ '#1' ~ is ~ not ~ know ~ the ~ level ~ #2.
5436 }
5437 \msg_new:nnn { enumext } { unknown-key-family }
5438 {
5439     Unknown~key~family~`\l_keys_key_str'~for~enumext.
5440 }

```

Messages used in length calculation.

```

5441 \msg_new:nnn { enumext } { width-negative }
5442 {
5443   Ignoring ~ negative ~ value ~ '#1=#2' ~ \msg_line_context:.\
5444   The ~ key ~ '#1'~ accepts ~ values ~ >= ~ opt.
5445 }
5446 \msg_new:nnn { enumext } { width-zero }
5447 {
5448   Invalid ~ '#1=#2' ~ \msg_line_context:.\
5449   The ~ key ~ '#1'~ accepts ~ values ~ > ~ opt.
5450 }

```

Messages used by `show-length` key in `enumext`.

```

5451 \msg_new:nnn { enumext } { list-lengths }
5452 {
5453   **** ~ Lengths ~ used ~ by ~ 'enumext' ~ level ~ '#2' ~ \msg_line_context:~\c_space_tl ****\
5454   \__enumext_show_length:nnn { dim } { labelsep } {#1}
5455   \__enumext_show_length:nnn { dim } { labelwidth } {#1}
5456   \__enumext_show_length:nnn { dim } { itemindent } {#1}
5457   \__enumext_show_length:nnn { dim } { leftmargin } {#1}
5458   \__enumext_show_length:nnn { dim } { rightmargin } {#1}
5459   \__enumext_show_length:nnn { dim } { listparindent } {#1}
5460   \__enumext_show_length:nnn { skip } { topsep } {#1}
5461   \__enumext_show_length:nnn { skip } { parsep } {#1}
5462   \__enumext_show_length:nnn { skip } { partopsep } {#1}
5463   \__enumext_show_length:nnn { skip } { itemsep } {#1}
5464   ****
5465 }

```

Messages used by `show-length` key in `enumext*`, `keyans*` and `keyans`.

```

5466 \msg_new:nnn { enumext } { list-lengths-not-nested }
5467 {
5468   **** ~ Lengths ~ used ~ by ~ '#2' ~ environment ~ \msg_line_context:~\c_space_tl ****\
5469   \__enumext_show_length:nnn { dim } { labelsep } {#1}
5470   \__enumext_show_length:nnn { dim } { labelwidth } {#1}
5471   \__enumext_show_length:nnn { dim } { itemindent } {#1}
5472   \__enumext_show_length:nnn { dim } { leftmargin } {#1}
5473   \__enumext_show_length:nnn { dim } { rightmargin } {#1}
5474   \__enumext_show_length:nnn { dim } { listparindent } {#1}
5475   \__enumext_show_length:nnn { skip } { topsep } {#1}
5476   \__enumext_show_length:nnn { skip } { parsep } {#1}
5477   \__enumext_show_length:nnn { skip } { partopsep } {#1}
5478   \__enumext_show_length:nnn { skip } { itemsep } {#1}
5479   ****
5480 }

```

Messages used by `ref` key.

```

5481 \msg_new:nnn { enumext } { key-ref-empty }
5482 {
5483   Key ~ 'ref' ~ need ~ a ~ value ~ in ~ '#1'~ \msg_line_context:.
5484 }

```

Messages used by `save-ans` key.

```

5485 \msg_new:nnn { enumext } { save-ans-empty }
5486 {
5487   Key ~ 'save-ans' ~ need ~ a ~ value ~ in ~ '#1'~ \msg_line_context:.
5488 }
5489 \msg_new:nnn { enumext } { save-ans-log }
5490 {
5491   * ~ Package ~ enumext: ~ Start ~ #1\c_space_tl with ~ save-ans=#2 ~ \msg_line_context:.
5492 }
5493 \msg_new:nnn { enumext } { save-ans-log-hook }
5494 {
5495   * ~ Package ~ enumext: ~ Stop ~ #1\c_space_tl with ~ save-ans=#2 ~ \msg_line_context:.
5496 }
5497 \msg_new:nnn { enumext } { save-ans-hook }
5498 {
5499   Stop ~ storing ~ for ~ 'save-ans=#1' ~ \msg_line_context:.
5500 }

```

Messages used by the internal system to check answer used by `check-ans` key.

```

5501 \msg_new:nnn { enumext } { need-save-ans }
5502 {

```

```

5503     Key ~ '#1' ~ works ~ only ~ with ~ the ~ 'save-ans' ~ key ~ in ~ '#2' ~ \msg_line_context:.
5504 }
5505 \msg_new:nnn { enumext } { items-same-answer }
5506 {
5507     *****\
5508     * ~ Package ~ enumext: ~ Checking ~ answers ~ in ~ '#1' ~
5509     for ~ \c_left_brace_str #2 \c_right_brace_str\
5510     * ~ started ~ #3 ~ and ~ close ~ \msg_line_context: : ~
5511     'OK', ~ all ~ items ~ with ~ answer.\
5512     *****
5513 }
5514 \msg_new:nnn { enumext } { item-greater-answer }
5515 {
5516     Checking ~ answers ~ in ~ '#1' ~ for ~ \c_left_brace_str #2 \c_right_brace_str\
5517     started ~ #3 ~ and ~ close ~ \msg_line_context: : ~ 'NOT ~ OK'\
5518     Items ~ > ~ Answers.
5519 }
5520 \msg_new:nnn { enumext } { item-less-answer }
5521 {
5522     Checking ~ answers ~ in ~ '#1' ~ for ~ \c_left_brace_str #2 \c_right_brace_str\
5523     started ~ #3 ~ and ~ close ~ \msg_line_context: : ~ 'NOT ~ OK'\
5524     Items ~ < ~ Answers.
5525 }

```

Messages used by the internal system to check for “starred” `\item*` and `\anspic*` commands.

```

5526 \msg_new:nnn { enumext } { missing-starred }
5527 {
5528     Missing ~ '\c_backslash_str #1*' ~ #2.
5529 }
5530 \msg_new:nnn { enumext } { many-starred }
5531 {
5532     Many ~ '\c_backslash_str #1*' ~ #2.
5533 }

```

Messages used by `\printkeyans*` command.

```

5534 \msg_new:nnn { enumext } { print-starred }
5535 {
5536     \c_backslash_str printkeyans*:~ The ~ sequence ~ '#1' ~ already ~ contains ~
5537     #2 ~ environment ~ \msg_line_context:.
5538 }

```

Message for the nesting depth of the environment `enumext`.

```

5539 \msg_new:nnn { enumext } { list-too-deep }
5540 {
5541     Too ~ deep ~ nesting ~ for ~ 'enumext' ~ \msg_line_context:~ \
5542     The ~ maximum ~ level ~ of ~ nesting ~ is ~ 4.
5543 }

```

Messages used by `\anskey`, `anskey*` and `\anspic` commands.

```

5544 \msg_new:nnn { enumext } { anskey-unnumber-item }
5545 {
5546     Can't ~ store ~ with ~ a ~ unnumbered ~ \c_backslash_str item ~ \msg_line_context:.
5547 }
5548 \msg_new:nnn { enumext } { anskey-already-stored }
5549 {
5550     Content ~ already ~ stored ~ for ~ this ~ \c_backslash_str item ~ \msg_line_context:.
5551 }
5552 \msg_new:nnn { enumext } { anskey-empty-arg }
5553 {
5554     Can't ~ store ~ empty ~ content ~ \msg_line_context:.
5555 }
5556 \msg_new:nnn { enumext } { anskey-wrong-place }
5557 {
5558     Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \
5559     '\c_backslash_str #1' ~ works ~ in ~ the ~ environment ~ '#2'.
5560 }
5561 \msg_new:nnn { enumext } { anskey-nested }
5562 {
5563     The ~ command ~ \c_backslash_str anskey~ can't ~ be ~ nested ~ \msg_line_context:.
5564 }
5565 \msg_new:nnn { enumext } { anskey-math-mode }
5566 {
5567     #1 ~ can't ~ work ~ in ~ math ~ mode ~ \msg_line_context:.

```



```

5568     }
5569     \msg_new:nnn { enumext } { anskey-env-wrong }
5570     {
5571         The ~ environment ~ anskey* ~ cannot ~ use ~ in ~ '#1' ~ \msg_line_context:.
5572     }
5573     \msg_new:nnn { enumext } { ansPIC-wrong-place }
5574     {
5575         Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
5576         '\c_backslash_str #1' ~ works ~ in ~ the ~ environment ~ '#2'.
5577     }
5578     \msg_new:nnn { enumext } { command-wrong-place }
5579     {
5580         Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
5581         '\c_backslash_str #1' ~ works ~ outside ~ the ~ environment ~ '#2'.
5582     }
5583     \msg_new:nnnn { enumext } { anskey-env-key-unknown }
5584     {
5585         The ~ key ~ '#1' ~ is ~ unknown ~ by ~ environment~
5586         'anskey*' ~ and ~ is ~ being ~ ignored.
5587     }
5588     {
5589         The ~ environment ~ 'anskey*' ~ does ~ not ~ have ~ a ~ key ~ called ~'#1'.\\
5590         Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5591     }
5592     \msg_new:nnnn { enumext } { anskey-env-key-value-unknown }
5593     {
5594         The ~ key ~ '#1=#2' ~ is ~ unknown ~ by ~ environment ~
5595         'anskey*' ~ and ~ is ~ being ~ ignored.
5596     }
5597     {
5598         The ~ environment ~ 'anskey*' ~ does ~ not ~ have ~ a ~ key ~ called ~'#1'.\\
5599         Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5600     }
5601     \msg_new:nnnn { enumext } { anskey-cmd-key-unknown }
5602     { The ~ key ~ '#1' ~ is ~ unknown ~ by ~ '\c_backslash_str anskey' ~ and ~ is ~ being ~ ignored.}
5603     {
5604         The ~ command ~ '\c_backslash_str anskey' ~ does ~ not ~ have ~ a ~ key ~ called ~'#1'.\\
5605         Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5606     }
5607     \msg_new:nnnn { enumext } { anskey-cmd-key-value-unknown }
5608     { The ~ key ~ '#1=#2' ~ is ~ unknown ~ by ~ '\c_backslash_str anskey' ~ and ~ is ~ being ~ ignored.}
5609     {
5610         The ~ command ~ '\c_backslash_str anskey' ~ does ~ not ~ have ~ a ~ key ~ called ~'#1'.\\
5611         Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5612     }

```

Messages used by [keyans](#), [keyans\\*](#) and [keyansPIC](#) environment.

```

5613     \msg_new:nnn { enumext } { keyans-nested }
5614     {
5615         The ~ environment ~ 'keyans' ~ can't ~ be ~ nested ~ \msg_line_context:.
5616     }
5617     \msg_new:nnn { enumext } { keyans-wrong-level }
5618     {
5619         Wrong ~ level ~ position ~ for ~ 'keyans' ~ \msg_line_context:~ \\
5620         The ~ environment ~ 'keyans' ~ can ~ only ~ be ~ in ~ the ~ first ~ level.
5621     }
5622     \msg_new:nnn { enumext } { wrong-place }
5623     {
5624         Wrong ~ place ~ for ~ '#1' ~ environment ~\msg_line_context:~ \\
5625         '#1' ~ is ~ only ~ found ~ with ~ '#2' ~ in ~ 'enumext.
5626     }
5627     \msg_new:nnn { enumext } { keyansPIC-nested }
5628     {
5629         The ~ environment ~ 'keyansPIC' ~ can't ~ be ~ nested~ \msg_line_context:~.
5630     }
5631     \msg_new:nnn { enumext } { keyansPIC-wrong-level }
5632     {
5633         Wrong ~ level ~ position ~ for ~ 'keyansPIC' ~ \msg_line_context:~ \\
5634         The ~ environment ~ 'keyans' ~ can ~ only ~ be ~ in ~ the ~ first ~ level.
5635     }
5636     \msg_new:nnn { enumext } { keyansPIC-item-cmd }
5637     {

```

```

5638     Can't ~ use ~ \c_backslash_str item ~ in ~ keyanspic ~ \msg_line_context:.
5639 }
5640 \msg_new:nnnn { enumext } { keyans-unknown-key }
5641 {
5642     The ~ key ~ '#1' ~ is ~ unknown ~ by ~ environment~
5643     '\l__enumext_envir_name_tl' ~ and ~ is ~ being ~ ignored.
5644 }
5645 {
5646     The ~ environment ~ '\l__enumext_envir_name_tl' ~ does ~ not
5647     ~ have ~ a ~ key ~ called ~'#1'.\\
5648     Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5649 }
5650 \msg_new:nnnn { enumext } { keyans-unknown-key-value }
5651 {
5652     The ~ key ~ '#1=#2' ~ is ~ unknown ~ by ~ environment ~
5653     '\l__enumext_envir_name_tl' ~ and ~ is ~ being ~ ignored.
5654 }
5655 {
5656     The ~ environment ~ '\l__enumext_envir_name_tl' ~ does ~ not
5657     ~ have ~ a ~ key ~ called ~'#1'.\\
5658     Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5659 }

```

Message used by unknown *⟨keys⟩* in *enumext\**. environment.

```

5660 \msg_new:nnnn { enumext } { starred-unknown-key }
5661 {
5662     The ~ key ~ '#1' ~ is ~ unknown ~ by ~ environment~
5663     '\l__enumext_envir_name_tl' ~ and ~ is ~ being ~ ignored.
5664 }
5665 {
5666     The ~ environment ~ '\l__enumext_envir_name_tl' ~ does ~ not
5667     ~ have ~ a ~ key ~ called ~'#1'.\\
5668     Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5669 }
5670 \msg_new:nnnn { enumext } { starred-unknown-key-value }
5671 {
5672     The ~ key ~ '#1=#2' ~ is ~ unknown ~ by ~ environment ~
5673     '\l__enumext_envir_name_tl' ~ and ~ is ~ being ~ ignored.
5674 }
5675 {
5676     The ~ environment ~ '\l__enumext_envir_name_tl' ~ does ~ not
5677     ~ have ~ a ~ key ~ called ~'#1'.\\
5678     Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5679 }

```

Message used by unknown *⟨keys⟩* in *enumext* environment.

```

5680 \msg_new:nnnn { enumext } { standar-unknown-key }
5681 {
5682     The ~ key ~ '#1' ~ is ~ unknown ~ by ~ environment ~ '\l__enumext_envir_name_tl' \c_space_tl
5683     ~ on ~ level ~ \int_use:N \l__enumext_level_int \c_space_tl and ~ is ~ being ~ ignored.
5684 }
5685 {
5686     The ~ environment ~ '\l__enumext_envir_name_tl' ~ does ~ not
5687     ~ have ~ a ~ key ~ called ~'#1' ~ on ~ level ~ \int_use:N \l__enumext_level_int.\\
5688     Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5689 }
5690 \msg_new:nnnn { enumext } { standar-unknown-key-value }
5691 {
5692     The ~ key ~ '#1=#2' ~ is ~ unknown ~ by ~ environment ~ '\l__enumext_envir_name_tl' \c_space_
5693     ~ on ~ level ~ \int_use:N \l__enumext_level_int \c_space_tl and ~ is ~ being ~ ignored.
5694 }
5695 {
5696     The ~ environment ~ '\l__enumext_envir_name_tl' ~ does ~ not
5697     ~ have ~ a ~ key ~ called ~'#1' ~ on ~ level ~ \int_use:N \l__enumext_level_int.\\
5698     Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5699 }

```

Message used by unknown *⟨keys⟩* in *\foreachkeyans*.

```

5700 \msg_new:nnnn { enumext } { for-key-unknown }
5701 { The~key~'#1'~is~unknown~by~'\c_backslash_str foreachkeyans'~and~is~being~ignored.}
5702 {
5703     The~command~'\c_backslash_str foreachkeyans'~does~not~have~a~key~called~'#1'.\\

```

```

5704     Check~that~you~have~spelled~the~key~name~correctly.
5705 }
5706 \msg_new:nnnn { enumext } { for-key-value-unknown }
5707 { The~key~'#1=#2'~is~unknown~by~'\c_backslash_str foreachkeyans'~and~is~being~ignored. }
5708 {
5709     The~command~'\c_backslash_str foreachkeyans'~does~not~have~a~key~called~'#1'.\\
5710     Check~that~you~have~spelled~the~key~name~correctly.
5711 }

```

Messages used by `\getkeyans` command.

```

5712 \msg_new:nnn { enumext } { undefined-storage-anskey }
5713 {
5714     Storage ~ named ~ '#1' ~ is ~ not ~ defined ~ \msg_line_context:.
5715 }

```

Messages used by `\miniright` command.

```

5716 \msg_new:nnn { enumext } { missing-miniright }
5717 {
5718     Missing ~ '\c_backslash_str miniright' ~ in ~ \msg_line_context:.\\
5719     The ~ key ~ 'mini-env' ~ need ~ '\c_backslash_str miniright'.
5720 }
5721 \msg_new:nnn { enumext } { wrong-miniright-place }
5722 {
5723     Wrong ~ place ~ for ~ '\c_backslash_str miniright' ~ \msg_line_context:~ \\
5724     Works ~ in ~ 'enumext' ~ and ~ 'keyans' ~ with ~ key ~ 'mini-env'.
5725 }
5726 \msg_new:nnn { enumext } { wrong-miniright-use }
5727 {
5728     Wrong ~ use ~ for ~ '\c_backslash_str miniright' ~ \msg_line_context:~ \\
5729     '\c_backslash_str miniright' ~ need ~ a ~ key ~ 'mini-env'.
5730 }
5731 \msg_new:nnn { enumext } { wrong-miniright-starred }
5732 {
5733     Can't ~ use ~ \c_backslash_str miniright ~ in ~ starred ~ environments ~ \msg_line_context:.
5734 }
5735 \msg_new:nnn { enumext } { many-miniright-used }
5736 {
5737     Can't ~ use ~ \c_backslash_str miniright ~ more ~ than ~ once ~ \msg_line_context:.
5738 }

```

Messages used by `\setenumextmeta` command.

```

5739 \msg_new:nnn { enumext } { unknown-set }
5740 {
5741     Argument ~ [#1] ~ is ~ unknown ~ by ~ \c_backslash_str setenumextmeta ~ \msg_line_context:.
5742 }
5743 \msg_new:nnn { enumext } { already-defined }
5744 {
5745     The ~ key ~ '#1' ~ is ~ already ~ defined ~ \msg_line_context:.
5746 }
5747 \msg_new:nnn { enumext } { prohibited-unknown }
5748 {
5749     The ~ name ~ 'unknown' ~ can't ~ be ~ chosen~ for ~ a ~ meta ~ key ~ \msg_line_context:.
5750 }

```

Messages used by `enumext*` and `keyans*` environments.

```

5751 \msg_new:nnn { enumext } { nested }
5752 {
5753     The ~ environment ~ \l__enumext_envir_name_tl \c_space_tl can't ~ be ~ nested ~ \msg_line_context:.
5754 }
5755 \msg_new:nnn { enumext } { nested-horizontal }
5756 {
5757     The ~ environment ~ \l__enumext_envir_name_tl \c_space_tl can't ~ be ~ nested ~ in ~ '#1' ~
5758 }
5759 \msg_new:nnn { enumext } { item-joined }
5760 {
5761     Items ~ joined ~ (#1) ~ > ~ #2 ~ columns ~ \msg_line_context:.
5762 }
5763 \msg_new:nnn { enumext } { item-joined-columns }
5764 {
5765     Not ~ space ~ to ~ join ~ items ~ (#1) ~ > ~ #2 ~ \msg_line_context:.
5766 }

```

13.51 Finish package

Finish package implementation.

```
5767 \file_input_stop:
5768 </package>
```

# 14 Index of Implementation

The *italic* numbers denote the pages where the corresponding entry is described, the numbers underlined and all others indicate the line on which they are implemented in the package code.

Symbols	
\*	228
\+	220
\-	220
\\	236, 2775, 4142, 4145, 5385, 5394, 5399, 5419, 5421, 5428, 5430, 5443, 5448, 5453, 5468, 5507, 5509, 5511, 5516, 5517, 5522, 5523, 5541, 5558, 5575, 5580, 5589, 5598, 5604, 5610, 5619, 5624, 5633, 5647, 5657, 5667, 5677, 5687, 5697, 5703, 5709, 5718, 5723, 5728
A	
above	1589
above*	1589
\addvspace	1159, 1187, 1230, 1233, 1401, 1404, 1501, 1507, 1542, 1548, 1569, 1575, 3600, 3761, 3779, 4032, 4036, 4390, 4405, 4451, 4465
after	989
align	542
\Alph	38, 43, 44
\Alph	488, 612, 656, 722, 5093
\alph	38, 43, 44
\alph	489, 610, 5085
\anskey	12, 77, 79, 2593
anskey*	13, 2703
\anspic	15, 106, 108, 4047
\anspic*	71
\arabic	32, 38
\arabic	487, 609, 655, 5077, 5081, 5097
B	
base-fix	851
\baselineskip	52
\baselineskip	867, 874
before	989
before*	989
below	1589
below*	1589
bool commands:	
\bool_gset_false:N	357, 358, 359, 2879, 2881, 4407, 4411, 4467
\bool_gset_true:N	265, 275, 1092, 2082, 2088, 4376, 4408, 4440, 4468
\bool_if:NTF	427, 439, 456, 1523, 1611, 1625, 1638, 1649, 1660, 1671, 1682, 1693, 1742, 1759, 1764, 1772, 1799, 1837, 1842, 1849, 1853, 1875, 1880, 1888, 1895, 1926, 1934, 2027, 2225, 2235, 2314, 2338, 2345, 2369, 2467, 2489, 2529, 2543, 2547, 2597, 2616, 2640, 2694, 2705, 2794, 2831, 2895, 2930, 2945, 3020, 3031, 3035, 3054, 3067, 3109, 3143, 3179, 3194, 3213, 3349, 3364, 3379, 3441, 3451, 3484, 3489, 3555, 3581, 3631, 3689, 3744, 3769, 3968, 4030, 4049, 4068, 4113, 4140, 4369, 4385, 4391, 4434, 4448, 4452, 4574, 4584, 4672, 4678, 4685, 4701, 4718, 4744, 4805, 4815, 4926, 4930, 4956, 4963, 4982, 4997, 5012
\bool_if:nTF	1549, 1576, 3165, 3330, 3399, 4089, 5116, 5260
\bool_if_p:N	284, 299, 861, 862, 870, 871, 1906, 1907, 1915, 1916, 2040, 2066, 2079, 2080, 2085, 2086, 2402, 2412, 2424, 2439, 2440, 2474, 2515, 2516, 2817, 3007, 3008, 3045, 3046, 3528, 3530, 3541, 4096, 4097
\bool_lazy_all:nTF	282, 297, 859, 2038, 2064, 2400, 2409, 2422, 2437, 3526, 3539
\bool_lazy_and:nnTF	261, 271, 869, 1516, 1905, 1914, 2078, 2084, 2473, 2480, 2514, 2658, 2670, 2816, 2822, 3006
\bool_lazy_or:nnTF	1967, 1974, 3044, 4095, 5283
\bool_new:N	34, 35, 36, 37, 38, 39, 40, 41, 64, 73, 97, 102, 103, 108, 109, 112, 131, 138, 139, 146, 153, 154, 159, 161, 162, 176, 188, 190
\bool_not_p:n	262, 272, 863, 2411, 2475, 2481, 2818, 2823, 3529, 3542
\bool_set_eq:NN	3118, 3309, 4625, 4879
\bool_set_false:N	436, 881, 2012, 2013, 2045, 2050, 2054, 2058, 2071, 2758, 3503, 3648, 3697, 3784, 3923, 3965, 4045, 4543, 4569, 4622, 4821, 4876, 5129, 5130
\bool_set_true:N	289, 290, 304, 305, 416, 420, 535, 896, 1595, 1600, 1862, 1984, 1985, 2257, 2265, 2759, 3112, 3114, 3146, 3148, 3305, 3317, 3464, 3502, 3535, 3548, 3621, 3694, 3721, 3920, 4358, 4423, 4542, 4629, 4636, 4637, 4681, 4819, 4883, 4890, 4891, 5124, 5125
box commands:	
\box_dp:N	1447, 1448, 1451, 1458, 1471, 1479, 1485, 1493, 3979, 3984, 4032, 4124
\box_ht:N	1230, 1233, 1244, 1245, 1256, 1258, 1273, 1276, 1284, 1285, 1296, 1298, 1313, 1316, 1323, 1324, 1335, 1337, 1352, 1355, 1401, 1404, 1412, 1413, 1421, 1422, 1434, 1436
\box_ht_plus_dp:N	3974, 4040, 4077
\box_new:N	70, 149, 150, 183, 189
\box_use_drop:N	4402, 4463, 4741, 5009
\box_wd:N	495
C	
\c	228, 229, 758, 760, 772, 774
\catcode	2775
\cB	229
\cE	229
\centering	1551, 1578, 4168, 4395, 4456
check-ans	2004
Document class:	
article	45
clist commands:	
\clist_const:Nn	195
\clist_map_function:nN	4151
\clist_map_inline:Nn	541, 806, 988, 1003, 1084, 1605
\clist_map_inline:nn	49, 60, 78, 86, 99, 111, 141, 170, 194, 572, 592, 901, 922, 1098, 1711, 1951, 2018, 2204, 2222, 2254, 2397, 2939, 3234, 3246, 3286, 3428, 3431, 3459, 3471, 3474, 3494, 5236
\columnbreak	77
\columnbreak	2477
columns	1068
columns-sep	1068
\columnsep	99
\columnsep	3576, 3742
\columnseprule	99
\columnseprule	3579, 3743

Commands provide by **enumext**:

\anskey 30, 67, 68, 73, 74, 76, 78, 79, 86, 88, 98, 99, 118,  
127, 129, 136  
\anspic\* 30, 31, 71, 74, 86, 87, 108, 127, 129  
\anspic 30, 74, 106, 108, 136  
\foreachkeyans 132, 138  
\getkeyans 74, 127, 139  
\item\* 30, 31, 71, 74, 86, 87, 89, 90, 93, 119, 120, 125, 127,  
129  
\item 89, 93, 112, 119, 121, 124  
\miniright 29, 50, 58, 59, 100, 139  
\printkeyans\* 128  
\printkeyans 30, 74, 128  
\setenumextmeta 131, 139  
\setenumext 30, 128, 130, 131, 134

Counters defined by **enumext**:

enumXiii 28, 38  
enumXii 28, 38  
enumXiv 28, 38  
enumXi 28, 38  
enumXviii 28, 38  
enumXvii 28, 38, 120  
enumXvi 28, 38  
enumXv 28, 38

cs commands:

\cs\_generate\_variant:Nn 200, 201, 497, 513, 764,  
780, 2306, 2311, 2387, 2711, 3418, 4153, 5295  
\cs\_if\_exist:NTF 467  
\cs\_if\_free:NTF 2662, 2674  
\cs\_new:Nn 214  
\cs\_new:Npn 232, 1712, 1721, 1729, 2269, 2278, 2286,  
5144, 5153, 5162  
\cs\_new\_eq:NN 384, 385, 390, 391, 441, 442, 445, 446  
\cs\_new\_protected:Nn 224, 238, 254, 280, 313, 343,  
349, 355, 361, 367, 375, 393, 411, 632, 693, 744, 857,  
1004, 1008, 1012, 1016, 1020, 1024, 1028, 1032, 1036,  
1040, 1044, 1048, 1052, 1056, 1060, 1064, 1099, 1111,  
1144, 1161, 1172, 1189, 1215, 1236, 1361, 1387, 1407,  
1440, 1462, 1497, 1503, 1606, 1620, 1634, 1645, 1656,  
1667, 1678, 1689, 1770, 1873, 1886, 1903, 1924, 1952,  
1957, 1982, 2023, 2033, 2076, 2091, 2098, 2107, 2112,  
2117, 2122, 2131, 2136, 2141, 2312, 2336, 2343, 2367,  
2374, 2388, 2614, 2633, 2649, 2712, 2748, 2779, 2814,  
2856, 2877, 2885, 2928, 2943, 2971, 3004, 3040, 3052,  
3065, 3151, 3161, 3172, 3188, 3204, 3326, 3342, 3358,  
3372, 3495, 3524, 3553, 3560, 3590, 3607, 3629, 3651,  
3687, 3711, 3728, 3753, 3767, 3788, 3940, 4135, 4149,  
4154, 4178, 4188, 4219, 4348, 4367, 4413, 4432, 4472,  
4476, 4495, 4529, 4556, 4563, 4572, 4582, 4607, 4759,  
4803, 4834, 4840, 4861, 4918, 5027  
\cs\_new\_protected:Npn 202, 206, 210, 449, 465, 482,  
492, 498, 613, 657, 727, 751, 765, 1533, 1562, 1738,  
1757, 1827, 1860, 1962, 2146, 2223, 2233, 2255, 2263,  
2298, 2307, 2463, 2526, 2541, 2579, 2583, 2703, 2734,  
2738, 2769, 2905, 2981, 3025, 3105, 3124, 3247, 3251,  
3265, 3269, 3287, 3291, 3301, 3313, 3387, 3421, 3462,  
3506, 3707, 3949, 3956, 3963, 4066, 4085, 4109, 4250,  
4299, 4546, 4613, 4620, 4634, 4642, 4647, 4657, 4827,  
4867, 4874, 4888, 4896, 4913, 5049, 5062, 5110, 5233,  
5245, 5269, 5281, 5319, 5329, 5337, 5359  
\cs\_new\_protected\_nopar:Nn 3849, 3891, 3899,  
3907, 4592, 4600, 4735, 4846, 4854, 5003  
\cs\_new\_protected\_nopar:Npn 3841, 3857, 4663,  
4709, 4946, 4971  
\cs\_set:Npn 2398, 2435, 5055

\cs\_set\_eq:NN 4519, 4520, 4711, 4792, 4793, 4973  
\cs\_set\_protected:Nn 927, 943, 956, 968  
\cs\_set\_protected:Npn 45, 54, 71, 79, 94, 100, 134,  
166, 174, 520, 542, 577, 593, 639, 781, 807, 883, 906,  
980, 989, 1068, 1085, 1589, 1700, 1943, 2004, 2163,  
2205, 2241, 2390, 2932, 3223, 3239, 3279, 3419, 3460  
\cs\_to\_str:N 484, 507  
\cs\_undefine:N 2651, 2652, 2653, 2654

## D

\d 220  
\DeclareDocumentEnvironment 397  
dim commands:  
\dim\_abs:n 3392, 3397  
\dim\_add:Nn 3983, 4213, 4244  
\dim\_compare:nNnTF 929, 945, 958, 970, 1248, 1260,  
1288, 1300, 1327, 1339, 1416, 1424, 1535, 1564, 3389,  
3394, 3400, 3406, 3408, 3410, 3565, 3612, 3715, 3732,  
3958, 4190, 4206, 4221, 4237, 4350, 4415  
\dim\_compare:nTF 2499, 2844, 3654, 3791  
\dim\_eval:n 867, 4038, 4120  
\dim\_gset\_eq:NN 4359, 4424  
\dim\_gzero:N 2883, 4410, 4470  
\dim\_new:N 67, 74, 75, 76, 96, 143, 151, 152, 182, 184,  
185, 191  
\dim\_set:Nn 495, 897, 3141, 3392, 3397, 3399, 3402,  
3403, 3407, 3409, 3412, 3413, 3415, 3568, 3615, 3653,  
3717, 3734, 3790, 3972, 4075, 4156, 4192, 4199, 4223,  
4230, 4285, 4334, 4352, 4417, 4659  
\dim\_set\_eq:NN 600, 646, 715, 719, 3056, 3057, 3069,  
3070, 3136, 3430, 3473, 3576, 3742, 4292, 4295, 4296,  
4341, 4344, 4345, 4652, 4727, 4991  
\dim\_sub:Nn 3659, 3796, 4208, 4239  
\dim\_use:N 930, 938, 1536, 1546, 2377, 2380, 2385, 3156,  
3158, 3209, 3566, 3570, 3571, 3573, 3613, 3618, 3619,  
3625, 3656, 3661  
\dim\_zero:N 3465, 3579, 3743, 3985  
\dim\_zero\_new:N 464  
\c\_zero\_dim 932, 946, 959, 971, 1536, 1564, 2501, 2846,  
3389, 3394, 3400, 3407, 3566, 3613, 3656, 3715, 3732,  
3793, 3958, 4190, 4206, 4221, 4237, 4350, 4415  
\dimeval 2170

## E

\end 2340, 2371, 3597, 3758, 4022, 4170, 5118, 5128, 5136  
end internal commands:  
\end\_\_enumxt\_\_mini\_page 1544, 1571, 3640, 3778,  
4374, 4438, 4464  
\endgroup 2775  
\endlist 385  
\endminipage 391  
enumext 5, 3665  
enumxt internal commands:  
\l\_\_enumxt\_\_ref\_the\_count\_tl 41  
\l\_\_enumxt\_\_resume\_name\_tl 63  
\\_\_enumxt\_add\_meta\_key:nnn 132, 5247, 5263,  
5264, 5266, 5269  
\\_\_enumxt\_add\_pre\_parsep: 51, 1109, 1111, 1111  
\\_\_enumxt\_after\_args\_exec: 48, 1004, 1016, 3678  
\\_\_enumxt\_after\_args\_exec\_v: 1020, 1032, 3811  
\\_\_enumxt\_after\_args\_exec\_vii: 1036, 1060  
\\_\_enumxt\_after\_args\_exec\_viii: 1064  
\\_\_enumxt\_after\_env:nn 83-85, 101, 114, 122, 206,  
206, 2789, 3683, 4383, 4446, 4775  
\\_\_enumxt\_after\_hyperref: 36, 409, 411, 411  
\l\_\_enumxt\_after\_list\_args\_v\_tl 1034

```

\l__enumext_after_list_args_vii_tl 1062, 4733
\l__enumext_after_list_args_viii_tl .. 1066,
    5001
\__enumext_after_list_vii: 114, 118, 4527, 4563,
    4563
\__enumext_after_list_viii: ... 123, 4801, 4840,
    4840
\__enumext_after_stop_list: 48, 101, 1004, 1012,
    3645
\__enumext_after_stop_list_v: 1020, 1028, 3785
\l__enumext_after_stop_list_v_tl ..... 1030
\__enumext_after_stop_list_vii: .. 118, 1036,
    1052, 4566
\l__enumext_after_stop_list_vii_tl ... 1054
\__enumext_after_stop_list_viii: . 1056, 4843
\l__enumext_after_stop_list_viii_tl ... 1058
\l__enumext_align_label_pos_v_str .... 3376
\l__enumext_align_label_pos_X_str ..... 79
\l__enumext_align_label_vii_str ..... 4698
\l__enumext_align_label_viii_str ..... 4960
\l__enumext_align_label_X_str ..... 174
\c__enumext_all_envs_clist .. 195, 541, 806, 988,
    1003, 1084, 1605
\c__enumext_all_families_seq .. 130, 5201, 5227
\l__enumext_anskey_env_bool 33, 82, 34, 290, 305,
    2705
\__enumext_anskey_env_clean_vars: . 85, 2810,
    2814, 2877
\__enumext_anskey_env_define_keys: 82, 2703,
    2712, 2783
\__enumext_anskey_env_exec: 83, 2708, 2779, 2779
\__enumext_anskey_env_make:n 67, 82, 1987, 2703,
    2703, 2711
\__enumext_anskey_env_reset_keys: 83, 84, 2748,
    2811
\__enumext_anskey_env_reset_keys:\__-
    enumext_rescan_anskey_env:n ..... 2703
\__enumext_anskey_env_save_keys: .. 84, 2791,
    2814, 2814
\__enumext_anskey_env_store: .. 84, 2807, 2814,
    2856
\__enumext_anskey_env_unknown:n 82, 2731, 2734
\__enumext_anskey_env_unknown:nn . 2736, 2738
\l__enumext_anskey_level_int .. 28, 2635, 2636
\__enumext_anskey_safe_inner:.. 80, 2608, 2614,
    2633
\__enumext_anskey_safe_inner:n ..... 80
\__enumext_anskey_safe_outer: . 79, 2595, 2614,
    2614
\__enumext_anskey_show_wrap_arg:n . 78, 2526,
    2526, 2545, 2560
\__enumext_anskey_show_wrap_left:n 78, 2471,
    2541, 2541
\__enumext_anskey_unknown:n 79, 2563, 2577, 2579
\__enumext_anskey_unknown:nn . 2563, 2581, 2583
\__enumext_anskey_wrapper:n ..... 2167, 2539
\l__enumext_anspic_above_int . 142, 4157, 4158,
    4160
\__enumext_anspic_args:nnn 108, 110, 4047, 4063,
    4135
\l__enumext_anspic_args_seq 108–110, 142, 4061,
    4169, 4182
\l__enumext_anspic_below_int . 142, 4157, 4158,
    4161
\l__enumext_anspic_body_box ... 142, 4074, 4077
\__enumext_anspic_body_dim:n .. 109, 4047, 4066,
    4112
\l__enumext_anspic_body_htdp_dim .. 109, 142,
    4075, 4123
\__enumext_anspic_exec: ..... 4017, 4178
\__enumext_anspic_label:nn 109, 4047, 4085, 4115,
    4130
\l__enumext_anspic_label_above_bool ... 142,
    3920, 3923, 3968, 4030, 4068, 4113, 4140
\l__enumext_anspic_label_box .. 142, 3971, 3974
\l__enumext_anspic_label_htdp_dim . 107, 142,
    3972, 3978, 4040, 4122
\__enumext_anspic_label_pos:nnn .. 110, 4047,
    4109, 4138
\l__enumext_anspic_label_sep_skip 3930, 3980,
    4041, 4125, 4142
\l__enumext_anspic_layout_tl . 3915, 3932, 4180,
    4185
\l__enumext_anspic_mini_pos_str .. 142, 3921,
    3924, 4167
\l__enumext_anspic_mini_width_dim 142, 4087,
    4156, 4167
\__enumext_anspic_print:n 110, 4047, 4149, 4153,
    4182, 4185
\__enumext_anspic_row:n .. 110, 4047, 4151, 4154
\__enumext_anspic_start_list_tag: 3865, 3891,
    4137
\__enumext_anspic_stop_list_tag: . 3865, 3907,
    4147
\__enumext_anspic_stop_start_list_tag: 3865,
    3899, 4139
\__enumext_at_begin_document:n .. 35, 202, 202,
    382, 388
\l__enumext_base_line_fix_bool 45, 46, 129, 853,
    862, 881, 5124, 5129
\__enumext_before_args_exec: 48, 100, 118, 1004,
    1004, 3610
\__enumext_before_args_exec_v: 1020, 1020, 3714
\__enumext_before_args_exec_vii: . 1036, 1036,
    4560
\__enumext_before_args_exec_viii: 1040, 4837
\__enumext_before_env:nn 82, 206, 210, 2656, 2668,
    2680, 2781
\__enumext_before_keys_exec: .. 48, 1004, 1008,
    3675
\__enumext_before_keys_exec_v: 1020, 1024, 3808
\__enumext_before_keys_exec_vii ..... 1036
\__enumext_before_keys_exec_vii: . 1044, 4514
\__enumext_before_keys_exec_viii: 1048, 4787
\__enumext_before_list: .. 100, 3607, 3607, 3669
\__enumext_before_list_v: ... 3711, 3711, 3803
\__enumext_before_list_vii: ... 118, 4509, 4556,
    4556
\__enumext_before_list_viii: .. 123, 4783, 4834,
    4834
\l__enumext_before_no_starred_key_v_tl 1026
\l__enumext_before_no_starred_key_vii_-
    tl ..... 1046
\l__enumext_before_no_starred_key_viii_-
    tl ..... 1050
\l__enumext_before_starred_key_v_tl ... 1022
\l__enumext_before_starred_key_vii_tl . 1038
\l__enumext_before_starred_key_viii_tl 1042
\__enumext_calc_hspace:NNNNNNN 95, 3387, 3387,
    3418, 3423, 3466

```



\\_\_enumext\_check\_ans\_active: 68, 100, 118, 2023, 2023, 3611, 4559  
 \g\_\_enumext\_check\_ans\_item\_tl . . . . . 87  
 \g\_\_enumext\_check\_ans\_key\_bool 69, 70, 153, 357, 2082, 2088, 2895  
 \l\_\_enumext\_check\_ans\_key\_bool 69, 2008, 2013, 2079, 2085  
 \\_\_enumext\_check\_ans\_key\_hook: . . 69, 101, 118, 2076, 2076, 3646, 4567  
 \\_\_enumext\_check\_ans\_level: . 68, 69, 2023, 2029, 2033  
 \\_\_enumext\_check\_ans\_log: 70, 85, 2122, 2122, 2899  
 \\_\_enumext\_check\_ans\_log\_msg\_greater: 2122, 2128, 2141  
 \\_\_enumext\_check\_ans\_log\_msg\_less: 2122, 2126, 2131  
 \\_\_enumext\_check\_ans\_log\_msg\_same\_ok: 2122, 2127, 2136  
 \\_\_enumext\_check\_ans\_msg\_greater: 2098, 2104, 2117  
 \\_\_enumext\_check\_ans\_msg\_less: 2098, 2102, 2107  
 \\_\_enumext\_check\_ans\_msg\_same\_ok: 2098, 2103, 2112  
 \\_\_enumext\_check\_ans\_show: . . 70, 85, 2098, 2098, 2897  
 \l\_\_enumext\_check\_answers\_bool 67, 68, 79, 89, 90, 153, 1985, 2012, 2027, 2314, 2338, 2345, 2369, 2597, 2794, 3020, 3109, 3143, 4678  
 \\_\_enumext\_check\_starred\_cmd:n 34, 71, 87, 122, 2146, 2146, 3814, 4028, 4800  
 \g\_\_enumext\_check\_starred\_cmd\_int . . 94, 153, 2149, 2155, 2160, 3324, 4094, 4925  
 \l\_\_enumext\_check\_start\_line\_env\_tl . 34, 153, 320, 328, 336, 2152, 2158, 2161  
 \l\_\_enumext\_columns\_sep\_v\_dim 3732, 3734, 3742  
 \l\_\_enumext\_columns\_sep\_vii\_dim . . 4190, 4192, 4201, 4213, 4289, 4756  
 \l\_\_enumext\_columns\_sep\_viii\_dim . 4221, 4223, 4232, 4244, 4338, 5024  
 \l\_\_enumext\_columns\_v\_int 1381, 1399, 1567, 3730, 3738, 3750, 3755  
 \l\_\_enumext\_columns\_vii\_int . . 4195, 4198, 4202, 4211, 4253, 4257, 4260, 4266, 4272, 4276, 4750, 4764  
 \l\_\_enumext\_columns\_viii\_int . 4226, 4229, 4233, 4242, 4302, 4306, 4309, 4315, 4321, 4325, 5018, 5033  
 \l\_\_enumext\_counter\_i\_tl . . . . . 45, 474  
 \l\_\_enumext\_counter\_ii\_tl . . . . . 45, 475  
 \l\_\_enumext\_counter\_iii\_tl . . . . . 45, 476  
 \l\_\_enumext\_counter\_iv\_tl . . . . . 45, 477  
 \c\_\_enumext\_counter\_style\_tl . . . . . 32, 50, 226  
 \g\_\_enumext\_counter\_styles\_tl . 28, 38, 67, 485, 503  
 \l\_\_enumext\_counter\_v\_tl . . . . . 45, 478, 735  
 \l\_\_enumext\_counter\_vi\_tl . . . . . 45, 479  
 \l\_\_enumext\_counter\_vii\_tl . . . . . 45, 480, 667  
 \l\_\_enumext\_counter\_viii\_tl . . . . . 45, 481, 683  
 \l\_\_enumext\_current\_widest\_dim 28, 67, 509, 601, 647, 716, 720  
 \\_\_enumext\_def\_meta\_key:nnn . . 132, 5247, 5275, 5281, 5295  
 \\_\_enumext\_default\_item:n . . . 3105, 3105, 3169  
 \\_\_enumext\_define\_counters:Nn 28, 465, 465, 474, 475, 476, 477, 478, 479, 480, 481  
 \\_\_enumext\_endminipage: . 36, 382, 391, 405, 4404, 4737, 5005  
 \g\_\_enumext\_envir\_name\_tl 33, 34, 291, 306, 365, 1955, 1960, 1970, 2110, 2115, 2120, 2134, 2139, 2144  
 \l\_\_enumext\_envir\_name\_tl . 33, 34, 34, 260, 270, 319, 327, 335, 5643, 5646, 5653, 5656, 5663, 5666, 5673, 5676, 5682, 5686, 5692, 5696, 5753, 5757  
 \\_\_enumext\_execute\_after\_env: 35, 66, 70, 81, 85, 2885, 2885, 3685, 4777  
 \\_\_enumext\_fake\_item\_indent: . . 927, 927, 3450  
 \l\_\_enumext\_fake\_item\_indent\_v\_dim 946, 951  
 \l\_\_enumext\_fake\_item\_indent\_v\_tl 948, 3306, 3310, 3318  
 \\_\_enumext\_fake\_item\_indent\_vii: . . 927, 956, 3483  
 \l\_\_enumext\_fake\_item\_indent\_vii\_dim 959, 963  
 \l\_\_enumext\_fake\_item\_indent\_vii\_tl 961, 4732  
 \\_\_enumext\_fake\_item\_indent\_viii: . 927, 968, 3488  
 \l\_\_enumext\_fake\_item\_indent\_viii\_dim . 971, 975  
 \l\_\_enumext\_fake\_item\_indent\_viii\_tl . . 973, 4996  
 \l\_\_enumext\_fake\_item\_indent\_X\_tl . . . . 100  
 \\_\_enumext\_fake\_make\_label\_vii:n . 120, 4663, 4663, 4724  
 \\_\_enumext\_fake\_make\_label\_viii:n 4946, 4946, 4988  
 \\_\_enumext\_filter\_first\_level:n . . 129, 5144, 5144, 5178, 5189  
 \\_\_enumext\_filter\_first\_level\_key:n 130, 5144, 5149, 5153  
 \\_\_enumext\_filter\_first\_level\_pair:nn . 130, 5144, 5150, 5162  
 \\_\_enumext\_filter\_save\_key:n . . 73, 2230, 2238, 2261, 2267, 2269, 2269, 5075, 5079, 5083, 5087, 5091, 5095  
 \\_\_enumext\_filter\_save\_key\_key:n . . 73, 2269, 2274, 2278  
 \\_\_enumext\_filter\_save\_key\_pair:nn 74, 2269, 2275, 2286  
 \\_\_enumext\_filter\_series:n 62, 1712, 1712, 1750, 1762, 1767  
 \\_\_enumext\_filter\_series\_key:n 62, 1712, 1717, 1721  
 \\_\_enumext\_filter\_series\_pair:nn . . 62, 1712, 1718, 1729  
 \\_\_enumext\_first\_item\_tmp\_vii: 116, 118, 4519, 4592, 4592  
 \\_\_enumext\_first\_item\_tmp\_viii: . . 124, 4792, 4846, 4846  
 \g\_\_enumext\_footnote\_arg\_seq . 171, 4478, 4491, 4501  
 \g\_\_enumext\_footnote\_int . 171, 4485, 4488, 4490, 4492  
 \g\_\_enumext\_footnote\_int\_seq . 171, 4479, 4492, 4497, 4500  
 \\_\_enumext\_footnotes\_key\_bool . . . . . 36  
 \l\_\_enumext\_footnotes\_key\_bool 31, 37, 121, 161, 420, 427, 436, 4718, 4744, 4982, 5012  
 \\_\_enumext\_footnotetext:nn . . . 4472, 4472, 4502  
 \\_\_enumext\_foreach\_add\_body:n . 133, 5296, 5356, 5359  
 \l\_\_enumext\_foreach\_after\_tl . . . . . 5300, 5368  
 \l\_\_enumext\_foreach\_before\_tl . . . . 5298, 5363  
 \g\_\_enumext\_foreach\_default\_keys\_tl 132, 126,

[5318](#), [5339](#)  
[\\\_\\_enumext\\_foreach\\_keyans:nn](#) .. [133](#), [5296](#), [5335](#), [5337](#)  
[\l\\_\\_enumext\\_foreach\\_name\\_prop\\_tl](#) . [126](#), [5341](#), [5366](#)  
[\l\\_\\_enumext\\_foreach\\_print\\_seq](#) [126](#), [5351](#), [5357](#), [5361](#)  
[\l\\_\\_enumext\\_foreach\\_sep\\_tl](#) ..... [5310](#), [5357](#)  
[\l\\_\\_enumext\\_foreach\\_start\\_int](#) .... [5302](#), [5353](#)  
[\l\\_\\_enumext\\_foreach\\_step\\_int](#) .... [5306](#), [5354](#)  
[\l\\_\\_enumext\\_foreach\\_stop\\_int](#) . [5304](#), [5346](#), [5348](#), [5355](#)  
[\\\_\\_enumext\\_foreach\\_wrapper:n](#) ..... [5308](#), [5364](#)  
[\\\_\\_enumext\\_getkeyans:nn](#) .. [128](#), [5044](#), [5058](#), [5062](#)  
[\\\_\\_enumext\\_getkeyans\\_aux:n](#) [127](#), [5044](#), [5046](#), [5049](#)  
[\l\\_\\_enumext\\_hyperref\\_bool](#) . [31](#), [36](#), [37](#), [161](#), [416](#), [439](#), [456](#), [2516](#), [3008](#), [4672](#)  
[\\\_\\_enumext\\_hypertarget:nn](#) [37](#), [411](#), [441](#), [445](#), [461](#)  
[\\\_\\_enumext\\_if\\_is\\_int:n](#) ..... [218](#)  
[\\\_\\_enumext\\_if\\_is\\_int:nTF](#) ..... [218](#), [753](#), [767](#)  
[\\\_\\_enumext\\_internal\\_mini\\_page:](#) [36](#), [98](#), [117](#), [393](#), [393](#), [3497](#), [4531](#)  
[\\\_\\_enumext\\_is\\_not\\_nested:](#) [28](#), [33](#), [98](#), [117](#), [254](#), [254](#), [3498](#), [4532](#)  
[\\\_\\_enumext\\_is\\_on\\_first\\_level:](#) . [28](#), [33](#), [98](#), [117](#), [254](#), [280](#), [3504](#), [4544](#)  
[\g\\_\\_enumext\\_item\\_anskey\\_int](#) [79](#), [88](#), [153](#), [352](#), [379](#), [380](#), [2095](#), [2465](#), [3022](#)  
[\\\_\\_enumext\\_item\\_answer\\_diff:](#) [70](#), [85](#), [2091](#), [2091](#), [2892](#)  
[\g\\_\\_enumext\\_item\\_answer\\_diff\\_int](#) [70](#), [153](#), [353](#), [2093](#), [2100](#), [2124](#)  
[\l\\_\\_enumext\\_item\\_column\\_pos\\_vii\\_int](#) [119](#), [4260](#), [4266](#), [4272](#), [4276](#), [4283](#), [4603](#), [4750](#), [4753](#)  
[\l\\_\\_enumext\\_item\\_column\\_pos\\_viii\\_int](#) .. [124](#), [4309](#), [4315](#), [4321](#), [4325](#), [4332](#), [4857](#), [5018](#), [5021](#)  
[\l\\_\\_enumext\\_item\\_column\\_pos\\_X\\_int](#) ..... [174](#)  
[\g\\_\\_enumext\\_item\\_count\\_all\\_vii\\_int](#) [119](#), [4284](#), [4604](#), [4764](#), [4772](#)  
[\g\\_\\_enumext\\_item\\_count\\_all\\_viii\\_int](#) [124](#), [4333](#), [4858](#), [5032](#), [5041](#)  
[\g\\_\\_enumext\\_item\\_count\\_all\\_X\\_int](#) ..... [174](#)  
[\g\\_\\_enumext\\_item\\_number\\_bool](#) ..... [153](#)  
[\l\\_\\_enumext\\_item\\_number\\_bool](#) [69](#), [159](#), [2045](#), [2050](#), [2054](#), [2058](#), [2071](#), [2640](#), [2694](#), [3112](#), [3146](#), [4681](#)  
[\g\\_\\_enumext\\_item\\_number\\_int](#) .. [69](#), [153](#), [351](#), [378](#), [380](#), [2044](#), [2049](#), [2053](#), [2057](#), [2070](#), [2095](#), [3111](#), [3145](#), [4680](#)  
[\\\_\\_enumext\\_item\\_peek\\_args\\_vii:](#) [119](#), [4600](#), [4605](#), [4607](#)  
[\\\_\\_enumext\\_item\\_peek\\_args\\_viii:](#) .. [124](#), [4854](#), [4859](#), [4861](#)  
[\\\_\\_enumext\\_item\\_star\\_exec:](#) [90](#), [3124](#), [3151](#), [3196](#), [3215](#)  
[\l\\_\\_enumext\\_item\\_starred\\_vii\\_bool](#) [4622](#), [4636](#), [4685](#)  
[\l\\_\\_enumext\\_item\\_starred\\_viii\\_bool](#) [4876](#), [4890](#), [4956](#), [4997](#)  
[\l\\_\\_enumext\\_item\\_starred\\_X\\_bool](#) ..... [174](#)  
[\\\_\\_enumext\\_item\\_std:w](#) [36](#), [89](#), [90](#), [94](#), [382](#), [386](#), [3115](#), [3121](#), [3149](#), [3306](#), [3310](#), [3318](#)  
[\g\\_\\_enumext\\_item\\_symbol\\_aux\\_tl](#) . [90](#), [130](#), [3129](#), [3132](#), [3157](#), [3201](#), [3219](#)  
[\g\\_\\_enumext\\_item\\_symbol\\_aux\\_vii\\_tl](#) [4644](#), [4687](#), [4690](#), [4694](#), [4696](#)  
[\g\\_\\_enumext\\_item\\_symbol\\_aux\\_X\\_tl](#) ..... [174](#)  
[\l\\_\\_enumext\\_item\\_symbol\\_sep\\_vii\\_dim](#) .. [4652](#), [4659](#), [4693](#), [4695](#)  
[\l\\_\\_enumext\\_item\\_symbol\\_vii\\_tl](#) ..... [4690](#)  
[\l\\_\\_enumext\\_item\\_text\\_vii\\_box](#) .... [4712](#), [4741](#)  
[\l\\_\\_enumext\\_item\\_text\\_viii\\_box](#) ... [4974](#), [5009](#)  
[\l\\_\\_enumext\\_item\\_text\\_X\\_box](#) ..... [174](#)  
[\l\\_\\_enumext\\_item\\_width\\_vii\\_dim](#) ... [4199](#), [4208](#), [4287](#), [4295](#), [4296](#)  
[\l\\_\\_enumext\\_item\\_width\\_viii\\_dim](#) .. [4230](#), [4239](#), [4336](#), [4344](#), [4345](#)  
[\l\\_\\_enumext\\_item\\_width\\_X\\_dim](#) ..... [174](#)  
[\l\\_\\_enumext\\_itemindent\\_X\\_dim](#) ..... [71](#)  
[\l\\_\\_enumext\\_itemsep\\_i\\_skip](#) ... [1242](#), [1249](#), [1252](#), [1254](#), [1261](#), [1265](#), [1268](#), [1270](#), [1410](#), [1417](#), [1419](#), [1420](#), [1425](#), [1429](#), [1431](#), [1432](#)  
[\l\\_\\_enumext\\_itemsep\\_ii\\_skip](#) .. [1282](#), [1289](#), [1292](#), [1294](#), [1301](#), [1305](#), [1308](#), [1310](#)  
[\l\\_\\_enumext\\_itemsep\\_iii\\_skip](#) . [1321](#), [1328](#), [1331](#), [1333](#), [1340](#), [1344](#), [1347](#), [1349](#)  
[\l\\_\\_enumext\\_itemsep\\_vii\\_skip](#) ..... [4770](#)  
[\l\\_\\_enumext\\_itemsep\\_viii\\_skip](#) ..... [5039](#)  
[\l\\_\\_enumext\\_joined\\_item\\_aux\\_vii\\_int](#) .. [4281](#), [4282](#), [4283](#), [4284](#), [4290](#)  
[\l\\_\\_enumext\\_joined\\_item\\_aux\\_viii\\_int](#) . [4330](#), [4331](#), [4332](#), [4333](#), [4339](#)  
[\l\\_\\_enumext\\_joined\\_item\\_aux\\_X\\_int](#) .... [174](#)  
[\\\_\\_enumext\\_joined\\_item\\_vii:w](#) .. [119](#), [4600](#), [4610](#), [4611](#), [4613](#)  
[\l\\_\\_enumext\\_joined\\_item\\_vii\\_int](#) .. [4252](#), [4253](#), [4256](#), [4258](#), [4264](#), [4269](#), [4274](#), [4279](#), [4281](#), [4287](#)  
[\\\_\\_enumext\\_joined\\_item\\_viii:w](#) [124](#), [4854](#), [4864](#), [4865](#), [4867](#)  
[\l\\_\\_enumext\\_joined\\_item\\_viii\\_int](#) . [4301](#), [4302](#), [4305](#), [4307](#), [4313](#), [4318](#), [4323](#), [4328](#), [4330](#), [4336](#)  
[\l\\_\\_enumext\\_joined\\_item\\_X\\_int](#) ..... [174](#)  
[\l\\_\\_enumext\\_joined\\_width\\_vii\\_dim](#) . [4285](#), [4292](#), [4295](#), [4714](#), [4726](#)  
[\l\\_\\_enumext\\_joined\\_width\\_viii\\_dim](#) [4334](#), [4341](#), [4344](#), [4976](#), [4990](#)  
[\l\\_\\_enumext\\_joined\\_width\\_X\\_dim](#) ..... [174](#)  
[\\\_\\_enumext\\_keyans\\_addto\\_prop:n](#) [86](#), [2905](#), [2905](#), [3321](#), [4091](#)  
[\\\_\\_enumext\\_keyans\\_addto\\_seq:n](#) . [87](#), [2981](#), [2981](#), [3323](#), [4093](#)  
[\\\_\\_enumext\\_keyans\\_addto\\_seq\\_link:](#) [2981](#), [3002](#), [3004](#), [4924](#)  
[\\\_\\_enumext\\_keyans\\_default\\_item:n](#) .. [93](#), [3301](#), [3301](#), [3338](#)  
[\l\\_\\_enumext\\_keyans\\_env\\_bool](#) [34](#), [3529](#), [3542](#), [3694](#), [3784](#)  
[\\\_\\_enumext\\_keyans\\_fake\\_item\\_indent:](#) [927](#), [943](#), [3440](#)  
[\l\\_\\_enumext\\_keyans\\_level\\_h\\_int](#) .. [123](#), [28](#), [676](#), [702](#), [2624](#), [2686](#), [2959](#), [4538](#), [4809](#), [4810](#)  
[\l\\_\\_enumext\\_keyans\\_level\\_int](#) .. [28](#), [1527](#), [2620](#), [2682](#), [2954](#), [3693](#), [3698](#), [4057](#)  
[\\\_\\_enumext\\_keyans\\_make\\_label:](#) [39](#), [94](#), [3342](#), [3342](#), [3438](#)  
[\\\_\\_enumext\\_keyans\\_make\\_label\\_box:](#) [3342](#), [3346](#), [3351](#), [3372](#)  
[\\\_\\_enumext\\_keyans\\_make\\_label\\_std:](#) [3342](#), [3354](#), [3358](#)  
[\\\_\\_enumext\\_keyans\\_mini\\_right\\_cmd:n](#) [59](#), [1529](#), [1562](#), [1562](#)

```

\__enumext_keyans_mini_set_vskip: . . . . . 55
\__enumext_keyans_minipage_add_space: 1361,
1387, 3723
\__enumext_keyans_minipage_set_skip: . 1361,
1361, 1389
\__enumext_keyans_multi_addvspace: 1161, 1172,
3747
\__enumext_keyans_multi_set_vskip: 52, 1161,
1161, 1174
\__enumext_keyans_multicols_start: 3711, 3726,
3728
\__enumext_keyans_multicols_stop: 1566, 3711,
3753, 3782
\__enumext_keyans_name_and_start: 28, 34, 123,
313, 313, 3695, 3947, 4814
\__enumext_keyans_parse_keys:n 3707, 3707, 3802
\__enumext_keyans_pic_arg_two: 107, 3940, 3963,
3993
\l__enumext_keyans_pic_level_int .. 28, 1511,
2628, 2690, 2908, 2949, 2984, 3072, 3942, 3943
\__enumext_keyans_pic_parse_keys:n 3940, 3949,
3992
\g__enumext_keyans_pic_parsep_skip ... 142
\__enumext_keyans_pic_safe_exec: . 106, 3940,
3940, 3991
\__enumext_keyans_pic_skip_abs:N . 107, 3940,
3956, 3967
\__enumext_keyans_pre_itemsep_skip: .. 1361,
1380, 1407
\__enumext_keyans_redefine_item: .. 94, 3326,
3326, 3437
\__enumext_keyans_ref: . . . . . 43, 727, 744, 3439
\__enumext_keyans_ref:n . . . . . 43, 724, 727, 727
\__enumext_keyans_safe_exec: . 3687, 3687, 3801
\__enumext_keyans_set_item_width: 103, 3788,
3788, 3810
\__enumext_keyans_show_ans: .. 3025, 3033, 3052
\__enumext_keyans_show_item_opt: .. 94, 3025,
3040, 3319, 4106, 4999
\__enumext_keyans_show_left:n . 94, 3025, 3025,
3316, 4100
\__enumext_keyans_show_pos: .. 3025, 3037, 3065
\__enumext_keyans_starred_item:n .. 94, 3313,
3313, 3334
\__enumext_keyans_store_ref: .. 86, 2928, 2928,
3322, 4092, 4922
\__enumext_keyans_store_ref_aux_i: 86, 2928,
2940, 2943
\__enumext_keyans_store_ref_aux_ii: 87, 2928,
2969, 2971
\__enumext_keyans_unknown_keys:n . 3239, 3243,
3247, 3938
\__enumext_keyans_unknown_keys:nn 3239, 3249,
3251
\__enumext_keyans_wrapper_opt:n .. 2173, 3048
\l__enumext_label_copy_i_tl .. 2431, 2947, 2952,
2957, 2962
\l__enumext_label_copy_v_tl . . . . . 2957
\l__enumext_label_copy_vi_tl . . . . . 2952
\l__enumext_label_copy_vii_tl 2407, 2418, 2447,
2947
\l__enumext_label_copy_viii_tl . . . . . 2962
\l__enumext_label_copy_X_tl . . . . . 163
\l__enumext_label_fill_left_v_tl . . . . . 3362
\l__enumext_label_fill_left_X_tl . . . . . 100
\l__enumext_label_fill_right_v_tl . . . . 3369
\l__enumext_label_fill_right_X_tl . . . . 100
\l__enumext_label_font_style_v_tl 3363, 3378,
4104
\l__enumext_label_font_style_vii_tl ... 4700
\l__enumext_label_font_style_viii_tl .. 4962
\l__enumext_label_i_tl . . . . . 593
\l__enumext_label_ii_tl . . . . . 593
\l__enumext_label_iii_tl . . . . . 593
\l__enumext_label_iv_tl . . . . . 593
\__enumext_label_style:Nnn 28, 38, 498, 498, 513,
598, 644, 713, 717
\l__enumext_label_v_tl 87, 710, 2913, 2989, 3059,
3099, 3315, 3320, 3805, 3971, 4099, 4101
\l__enumext_label_vi_tl 87, 710, 2910, 2986, 4099,
4101, 4105
\l__enumext_label_vii_tl . 639, 4631, 4654, 4661
\l__enumext_label_viii_tl 639, 4885, 4916, 4920
\l__enumext_label_width_by_box .. 67, 494, 495
\__enumext_label_width_by_box:Nn 38, 492, 492,
497, 509, 777
\l__enumext_labelsep_i_dim ... 3057, 3062, 3070,
3102, 4928, 4943
\l__enumext_labelsep_v_dim . . . . . 3737
\l__enumext_labelsep_vii_dim . 2532, 3057, 3070,
4194, 4204, 4288, 4596, 4652, 4707, 4714
\l__enumext_labelsep_viii_dim 4225, 4235, 4337,
4850, 4969, 4978
\l__enumext_labelwidth_i_dim . 3056, 3062, 3069,
3102, 4928, 4943
\l__enumext_labelwidth_v_dim . . . . . 3376, 3737
\l__enumext_labelwidth_vii_dim ... 2532, 3056,
3069, 4194, 4203, 4288, 4596, 4698, 4714
\l__enumext_labelwidth_viii_dim .. 4225, 4234,
4337, 4850, 4960, 4977
\l__enumext_leftmargin_tmp_v_bool . 107, 3965
\l__enumext_leftmargin_tmp_X_bool . . . . . 71
\l__enumext_leftmargin_tmp_X_dim . . . . . 71
\l__enumext_leftmargin_X_dim . . . . . 71
\__enumext_level: 214, 214, 622, 625, 626, 634, 636,
930, 934, 938, 1006, 1010, 1014, 1018, 1101, 1103,
1105, 1107, 1149, 1151, 1153, 1155, 1159, 1193, 1199,
1204, 1206, 1209, 1212, 1225, 1228, 1536, 1540, 1546,
1609, 1611, 1613, 1616, 1623, 1625, 1627, 1630, 2225,
2227, 2229, 2257, 2258, 2260, 2316, 2324, 2328, 2332,
2536, 2537, 3114, 3115, 3119, 3120, 3121, 3129, 3137,
3138, 3141, 3148, 3149, 3153, 3156, 3158, 3192, 3193,
3194, 3197, 3200, 3209, 3210, 3212, 3213, 3216, 3535,
3548, 3555, 3563, 3566, 3568, 3570, 3571, 3572, 3573,
3576, 3581, 3587, 3593, 3600, 3613, 3615, 3618, 3619,
3621, 3625, 3631, 3656, 3661, 3672, 3674
\l__enumext_level_h_int 117, 28, 263, 286, 300, 660,
695, 1518, 2041, 2061, 2426, 2660, 2672, 3543, 4533,
4534
\l__enumext_level_int . 98, 28, 216, 273, 285, 301,
395, 1113, 1238, 1517, 2035, 2067, 2403, 2413, 2419,
2425, 2432, 2441, 2446, 2659, 2671, 2887, 3454, 3499,
3500, 3511, 3519, 3533, 3546, 3577, 3702, 4053, 4576,
4586, 4822, 5683, 5687, 5693, 5697
\__enumext_list_arg_two_i: . . . . . 3419
\__enumext_list_arg_two_ii: . . . . . 3419
\__enumext_list_arg_two_iii: . . . . . 3419
\__enumext_list_arg_two_iv: . . . . . 3419
\__enumext_list_arg_two_v: . 94, 3419, 3807, 3966

```

```

\__enumext_list_arg_two_vii: . . . . . 3460, 4513
\__enumext_list_arg_two_viii: . . . . 3460, 4786
\l__enumext_listoffset_v_dim . 3739, 3793, 3796
\l__enumext_listparindent_vii_dim 4727, 4731
\l__enumext_listparindent_viii_dim 4991, 4995
\__enumext_log_answer_vars: . 35, 367, 375, 2894
\__enumext_log_global_vars: . 35, 367, 367, 2893
\__enumext_make_label: . 39, 91, 3172, 3172, 3448
\__enumext_make_label_box: . . 3172, 3176, 3181,
    3204
\__enumext_make_label_std: . . 3172, 3184, 3188
\l__enumext_mark_answer_sym_tl 75, 2179, 2382,
    2549, 3074, 3087, 4932
\l__enumext_mark_position_str 130, 2183, 2184,
    2210, 2211, 2380
\l__enumext_mark_ref_sym_tl . 2196, 2521, 3016
\l__enumext_meta_path_tl . 126, 5271, 5272, 5274,
    5275
\c__enumext_meta_paths_prop . . . . . 131, 5247
\__enumext_mini_addvspace_vii: 57, 1497, 1497,
    4362
\__enumext_mini_addvspace_viii: 57, 1497, 1503,
    4427
__enumext_mini_env* . . . . . 393
\__enumext_mini_page 1546, 1573, 3625, 3724, 4364,
    4429, 4450
\__enumext_mini_right_cmd:n . 58, 59, 1531, 1533,
    1533
\__enumext_mini_set_vskip_vii: 56, 1440, 1440,
    1499
\__enumext_mini_set_vskip_viii: 56, 1440, 1462,
    1505
\__enumext_minipage:w 36, 382, 390, 399, 4387, 4726,
    4990
\l__enumext_minipage_active_v_bool 3721, 3744,
    3769
\g__enumext_minipage_active_vii_bool . 114,
    4376, 4385, 4407
\l__enumext_minipage_active_vii_bool . 4358,
    4369
\g__enumext_minipage_active_viii_bool 4440,
    4448, 4467
\l__enumext_minipage_active_viii_bool 4423,
    4434
\g__enumext_minipage_active_X_bool . . 174
\l__enumext_minipage_active_X_bool . . . 87
\__enumext_minipage_add_space: . 53, 100, 1189,
    1215, 3623
\g__enumext_minipage_after_skip 87, 1444, 1456,
    4405, 4465
\l__enumext_minipage_after_skip . 52, 100, 87,
    1202, 1242, 1244, 1249, 1252, 1256, 1261, 1265, 1268,
    1272, 1284, 1289, 1292, 1296, 1301, 1305, 1308, 1312,
    1323, 1328, 1331, 1335, 1340, 1344, 1347, 1351, 1363,
    1377, 1410, 1412, 1417, 1419, 1421, 1425, 1429, 1431,
    1433, 1464, 1477, 1491, 1542, 1569, 3779
\g__enumext_minipage_center_vii_bool . 4391,
    4408
\g__enumext_minipage_center_viii_bool 4452,
    4468
\g__enumext_minipage_center_X_bool . . 174
\l__enumext_minipage_hsep_v_dim . . . . . 3719
\l__enumext_minipage_hsep_vii_dim . . . 4356
\l__enumext_minipage_hsep_viii_dim . . 4421
\l__enumext_minipage_left_skip 87, 1364, 1442,
    1447, 1451, 1465, 1469, 1483, 1501, 1507
\l__enumext_minipage_left_v_dim . 3717, 3724
\l__enumext_minipage_left_vii_dim 4352, 4364
\l__enumext_minipage_left_viii_dim 4417, 4429
\l__enumext_minipage_left_X_dim . . . . . 87
\g__enumext_minipage_right_skip 87, 1443, 1448,
    1452, 4390, 4451
\l__enumext_minipage_right_skip . 52, 87, 1191,
    1197, 1202, 1204, 1206, 1365, 1366, 1372, 1377, 1378,
    1379, 1384, 1466, 1473, 1487, 1548, 1575
\l__enumext_minipage_right_v_dim . 1564, 1573,
    3715, 3719
\g__enumext_minipage_right_vii_dim 114, 4360,
    4387, 4410
\l__enumext_minipage_right_vii_dim 114, 4350,
    4355, 4361
\g__enumext_minipage_right_viii_dim . 4425,
    4450, 4470
\l__enumext_minipage_right_viii_dim . 4415,
    4420, 4426
\g__enumext_minipage_right_X_dim . . . . . 174
\g__enumext_minipage_right_X_skip . . . 174
\__enumext_minipage_set_skip: . 52, 1189, 1189,
    1217
\g__enumext_minipage_stat_int . . 100, 87, 1553,
    1580, 3622, 3633, 3638, 3722, 3771, 3776
\l__enumext_minipage_temp_skip 87, 1263, 1273,
    1276, 1303, 1313, 1316, 1342, 1352, 1355, 1427, 1434,
    1436
\l__enumext_miniright_code_vii_box 4398, 4402
\g__enumext_miniright_code_vii_tl 114, 4393,
    4400, 4409
\l__enumext_miniright_code_viii_box . 4459,
    4463
\g__enumext_miniright_code_viii_tl 4454, 4461,
    4469
\l__enumext_miniright_code_X_box . . . . . 174
\l__enumext_mode_box_bool . . . 516, 3179, 3349
\__enumext_multi_addvspace: . 51, 99, 1144, 1144,
    3584
\__enumext_multi_set_vskip: 50, 1099, 1099, 1146
\l__enumext_multicols_above_ii_skip . . 1118
\l__enumext_multicols_above_iii_skip . . 1127
\l__enumext_multicols_above_iv_skip . . 1136
\l__enumext_multicols_above_v_skip 1163, 1177,
    1187, 1378
\l__enumext_multicols_above_X_skip . . . . 79
\l__enumext_multicols_below_ii_skip . 1245,
    1254, 1258, 1270, 1275
\l__enumext_multicols_below_iii_skip . 1285,
    1294, 1298, 1310, 1315
\l__enumext_multicols_below_iv_skip . . 1324,
    1333, 1337, 1349, 1354
\l__enumext_multicols_below_v_skip 1167, 1181,
    1379, 1413, 1420, 1422, 1432, 1435, 3761
\l__enumext_multicols_below_X_skip . . . . 79
\g__enumext_multicols_right_X_skip . . . 79
\__enumext_multicols_start: 99, 100, 3560, 3560,
    3627
\__enumext_multicols_stop: 100, 1538, 3590, 3590,
    3643
\__enumext_nested_base_line_fix: . 45, 98, 851,
    857, 3515

```



\\_\_enumext\_newlabel:nn 31, 37, 77, [449](#), 449, 2457, [2975](#)  
 \l\_\_enumext\_newlabel\_arg\_one\_tl 31, 37, 77, 86, [163](#), 2450, 2458, 2520, 2964, 2976, 3014  
 \l\_\_enumext\_newlabel\_arg\_two\_tl 31, 37, 76, [163](#), [2406](#), 2416, 2429, 2444, 2459, 2951, 2956, 2961, 2977  
 \\_\_enumext\_parse\_foreach\_keys:n .. [5296](#), 5312, [5329](#)  
 \\_\_enumext\_parse\_foreach\_keys:nn . [5296](#), 5319, [5331](#)  
 \\_\_enumext\_parse\_keys:n 45, 62, [3506](#), 3506, 3668  
 \\_\_enumext\_parse\_keys\_vii:n 62, 4508, [4546](#), 4546  
 \\_\_enumext\_parse\_keys\_viii:n . 4782, [4827](#), 4827  
 \\_\_enumext\_parse\_save\_key:n 73, 2250, 2255, 2255  
 \\_\_enumext\_parse\_save\_key\_vii:n 73, 2245, [2255](#), [2263](#)  
 \\_\_enumext\_parse\_series:n 62, 98, 117, [1738](#), 1738, [3514](#), 4552  
 \\_\_enumext\_parse\_store\_keys:n ..... 98  
 \l\_\_enumext\_parsep\_i\_skip ..... 1116, 1120  
 \l\_\_enumext\_parsep\_ii\_skip ..... 1125, 1129  
 \l\_\_enumext\_parsep\_iii\_skip ..... 1134, 1138  
 \l\_\_enumext\_parsep\_vii\_skip ..... 4728  
 \l\_\_enumext\_parsep\_viii\_skip ..... 4992  
 \l\_\_enumext\_partopsep\_v\_skip . 1179, 1183, 1374, [1397](#)  
 \l\_\_enumext\_partopsep\_viii\_skip ..... 1475  
 \\_\_enumext\_phantomsection: 37, [411](#), 442, 446, 462  
 \\_\_enumext\_pre\_itemsep\_skip: .. 53, 1207, [1236](#), [1236](#)  
 \\_\_enumext\_print\_footnote: ... [4472](#), 4495, 4746, [5014](#)  
 \\_\_enumext\_print\_keyans\_box:NN 75, [2374](#), 2374, [2387](#), 2531, 2535, 3061, 3101, 4928, 4943  
 \l\_\_enumext\_print\_keyans\_i\_tl .... 5080, 5102  
 \l\_\_enumext\_print\_keyans\_ii\_tl ... 5084, 5103  
 \l\_\_enumext\_print\_keyans\_iii\_tl .. 5088, 5104  
 \l\_\_enumext\_print\_keyans\_iv\_tl ... 5092, 5105  
 \l\_\_enumext\_print\_keyans\_star\_bool 45, 46, 129, [130](#), 863, 871, 5125, 5130  
 \l\_\_enumext\_print\_keyans\_starred\_tl 128, 129, [130](#), 5076, 5123  
 \l\_\_enumext\_print\_keyans\_vii\_tl 128, 5096, 5106  
 \l\_\_enumext\_print\_keyans\_X\_tl ..... [130](#)  
 \\_\_enumext\_printkeyans:nnn 129, [5099](#), 5107, 5110  
 \\_\_enumext\_redefine\_item: . 90, [3161](#), 3161, 3447  
 \l\_\_enumext\_ref\_key\_arg\_tl 41, 50, 229, 615, 616, 628, 659, 662, 672, 678, 688, 729, 730, 740  
 \l\_\_enumext\_ref\_the\_count\_tl . 41, 50, 622, 625, 628, 667, 669, 672, 683, 685, 688, 735, 737, 740  
 \\_\_enumext\_regex\_counter\_style: .. 32, 41, [224](#), [224](#), 623, 668, 684, 736  
 \\_\_enumext\_register\_counter\_style:Nn .. [482](#), [482](#), 487, 488, 489, 490, 491  
 \\_\_enumext\_remove\_extra\_parsep\_vii: .. 4526, [4759](#), 4759  
 \\_\_enumext\_remove\_extra\_parsep\_viii: . 4799, [5027](#), 5027  
 \\_\_enumext\_renew\_footnote: ... [4472](#), 4476, 4720, [4984](#)  
 \l\_\_enumext\_renew\_the\_count\_v\_tl 738, 746, 748  
 \l\_\_enumext\_renew\_the\_count\_vii\_tl 670, 697, [699](#)  
 \l\_\_enumext\_renew\_the\_count\_viii\_tl 686, 704, [706](#)  
 \l\_\_enumext\_renew\_the\_count\_X\_tl ..... [50](#)  
 \\_\_enumext\_rescan\_anskey\_env:n .. 83, 84, 2769, [2864](#), 2872  
 \\_\_enumext\_reset\_global\_bool: .. [343](#), 346, 355  
 \\_\_enumext\_reset\_global\_int: ... [343](#), 345, 349  
 \\_\_enumext\_reset\_global\_tl: .... [343](#), 347, 361  
 \\_\_enumext\_reset\_global\_vars: . 35, 85, [343](#), 343, [2902](#)  
 \l\_\_enumext\_resume\_active\_bool 62, 64, [61](#), 1742, [1862](#)  
 \\_\_enumext\_resume\_counter: .. 64, 65, [1860](#), 1866, [1873](#)  
 \\_\_enumext\_resume\_counter:n . 62, 64, 1831, 1836, [1860](#), 1860, 1930, 1938  
 \\_\_enumext\_resume\_counter\_save\_ans: 65, [1860](#), [1871](#), 1903  
 \\_\_enumext\_resume\_counter\_series: . 65, [1860](#), [1869](#), 1886  
 \g\_\_enumext\_resume\_int ... [61](#), 1783, 1877, 1878  
 \\_\_enumext\_resume\_last:n 62, 63, [1738](#), 1744, 1757  
 \l\_\_enumext\_resume\_name\_tl [61](#), 1779, 1787, 1790, [1806](#), 1814, 1817, 1863, 1864, 1892, 1899  
 \\_\_enumext\_resume\_save\_counter: . 63, 101, 118, [1770](#), 1770, 3649, 4570  
 \\_\_enumext\_resume\_series:n . 64, 1706, [1827](#), 1827  
 \\_\_enumext\_resume\_starred: . 66, 1707, [1924](#), 1924  
 \g\_\_enumext\_resume\_vii\_int [61](#), 1810, 1882, 1883  
 \l\_\_enumext\_rightmargin\_vii\_dim .. 4206, 4210, [4215](#)  
 \l\_\_enumext\_rightmargin\_viii\_dim . 4237, 4241, [4246](#)  
 \\_\_enumext\_safe\_exec: .. 36, 98, [3495](#), 3495, 3667  
 \\_\_enumext\_safe\_exec\_vii: . 36, 4507, [4529](#), 4529  
 \\_\_enumext\_safe\_exec\_viii: 123, 4781, [4803](#), 4803  
 \\_\_enumext\_second\_part: .. 100, [3629](#), 3629, 3681  
 \\_\_enumext\_second\_part\_v: ... [3711](#), 3767, 3815  
 \l\_\_enumext\_series\_name\_tl ..... 64, 65  
 \l\_\_enumext\_series\_str .. 63, 98, 117, 1704, 1740, 1748, 1749, 1751, 1753, 1774, 1777, 1781, 1801, 1804, 1808, 3510, 4550  
 \\_\_enumext\_set\_error:nn ..... [5206](#), 5243, 5245  
 \\_\_enumext\_set\_item\_width: 101, [3651](#), 3651, 3677  
 \\_\_enumext\_set\_parse:n ..... [5206](#), 5217, 5233  
 \l\_\_enumext\_setkey\_tmpa\_int ... [121](#), 5210, 5214  
 \l\_\_enumext\_setkey\_tmpa\_seq .. [121](#), 5208, 5218, [5224](#), 5226, 5228, 5240  
 \l\_\_enumext\_setkey\_tmpa\_tl .... [121](#), 5216, 5220  
 \l\_\_enumext\_setkey\_tmpb\_seq .. [121](#), 5209, 5212, [5216](#), 5217  
 \l\_\_enumext\_setkey\_tmpb\_tl [121](#), 5235, 5237, 5238  
 \l\_\_enumext\_show\_answer\_bool . 2190, 2214, 2543, [3031](#), 3045, 4096, 4926  
 \\_\_enumext\_show\_length:nnn .. 48, 232, 232, 5454, 5455, 5456, 5457, 5458, 5459, 5460, 5461, 5462, 5463, 5469, 5470, 5471, 5472, 5473, 5474, 5475, 5476, 5477, 5478  
 \l\_\_enumext\_show\_position\_bool ... 2193, 2217, [2547](#), 3035, 3046, 4097, 4930  
 \g\_\_enumext\_standar\_bool 33, 98, [34](#), 262, 265, 284, 358, 1772, 1837, 1849, 1875, 1888, 1926, 2066, 2080, [2411](#), 2424, 2439, 3530  
 \l\_\_enumext\_standar\_bool 98, 101, [34](#), 2412, 3502, [3648](#), 4543

```

\l__enumext_standar_first_bool 33, 98, 34, 289,
    1759, 1906, 1968, 1975
\__enumext_standar_item_vii:w . 119, 4600, 4618,
    4620
\__enumext_standar_item_viii:w 124, 4854, 4872,
    4874
\__enumext_standar_ref: . . . . 41, 613, 632, 3449
\__enumext_standar_ref:n . . . . 41, 605, 613, 613
\g__enumext_standar_series_tl . 61, 1761, 1762,
    1928, 1931
\__enumext_standar_unknown_keys:n 3279, 3283,
    3287
\__enumext_standar_unknown_keys:nn 3279, 3289,
    3291
\g__enumext_starred_bool 33, 117, 34, 272, 275, 299,
    359, 1799, 1842, 1853, 1880, 1895, 1934, 2040, 2086,
    2402, 2945, 4411
\l__enumext_starred_bool 117, 118, 123, 34, 1523,
    2440, 2475, 2481, 2529, 2818, 2823, 3054, 3067, 3503,
    4542, 4569, 4815, 4819
\__enumext_starred_columns_set_vii: . . 4188,
    4188, 4517
\__enumext_starred_columns_set_viii: . 4188,
    4219, 4790
\l__enumext_starred_first_bool 33, 117, 34, 304,
    861, 870, 1764, 1915, 1968, 1975
\__enumext_starred_item:nn . . 3124, 3124, 3167
\__enumext_starred_item_exec: . 125, 4888, 4918,
    4958
\__enumext_starred_item_vii:w . 119, 4600, 4617,
    4634
\__enumext_starred_item_vii_aux_i:w . . 4600,
    4639, 4642
\__enumext_starred_item_vii_aux_ii:w . 4600,
    4640, 4645, 4647
\__enumext_starred_item_vii_aux_iii:w 4600,
    4650, 4657
\__enumext_starred_item_viii:w 124, 125, 4871,
    4888, 4888
\__enumext_starred_item_viii_aux_i:w . . 125,
    4888, 4893, 4896
\__enumext_starred_item_viii_aux_ii:w . 125,
    4888, 4894, 4911, 4913
\__enumext_starred_joined_item_vii:n 112, 119,
    4250, 4250, 4615
\__enumext_starred_joined_item_viii:n . 112,
    124, 4250, 4299, 4869
\__enumext_starred_ref: . . . . 42, 657, 693, 3480
\__enumext_starred_ref:n . . . . 42, 651, 657, 657
\g__enumext_starred_series_tl . 61, 1766, 1767,
    1936, 1939
\__enumext_starred_unknown_keys:n 3261, 3263,
    3265
\__enumext_starred_unknown_keys:nn 3261, 3267,
    3269
\__enumext_start_from:NNn 43, 751, 751, 764, 786,
    792
\l__enumext_start_i_int . . . . . 1878, 1890, 1909
\__enumext_start_item_tmp_vii: 116, 4520, 4600,
    4600
\__enumext_start_item_tmp_viii: . . 4793, 4854,
    4854
\__enumext_start_item_vii:w 119, 121, 4626, 4631,
    4654, 4661, 4709, 4709
\__enumext_start_item_viii:w . 124, 4880, 4885,
    4916, 4971, 4971
\g__enumext_start_line_tl 33, 34, 292, 307, 364,
    2110, 2115, 2120, 2134, 2139, 2144
\__enumext_start_list:nn . 36, 95, 382, 384, 3671,
    3804, 4511, 4784
\__enumext_start_list_tag:n . . 3817, 3841, 4723,
    4987
\__enumext_start_mini_vii: 118, 4348, 4348, 4561
\__enumext_start_mini_viii: . . . 123, 4413, 4413,
    4838
\__enumext_start_save_ans_msg: . . 66, 67, 1952,
    1952, 1977
\__enumext_start_store_level: . 98, 3524, 3524,
    3670
\__enumext_start_store_level_vii: 118, 4510,
    4572, 4572
\l__enumext_start_vii_int . . . 1883, 1897, 1918
\l__enumext_start_X_int . . . . . 100
\__enumext_stop_item_tmp_vii: 116, 118, 119, 121,
    4519, 4525, 4602, 4711
\__enumext_stop_item_tmp_viii: 124, 4792, 4798,
    4856, 4973
\__enumext_stop_item_vii: 121, 4709, 4711, 4735
\__enumext_stop_item_viii: . . . 4971, 4973, 5003
\__enumext_stop_list: 36, 114, 118, 382, 385, 3595,
    3603, 3757, 3764, 4371, 4379, 4436, 4443
\__enumext_stop_list_tag:n . . . 3817, 3857, 4738,
    5006
\__enumext_stop_mini_vii: 114, 118, 4348, 4367,
    4565
\__enumext_stop_mini_viii: 123, 4413, 4432, 4842
\__enumext_stop_save_ans_msg: . 66, 1952, 1957,
    2891
\__enumext_stop_start_list_tag: . . 3817, 3849,
    4725, 4989
\__enumext_stop_store_level: 99, 100, 3553, 3553,
    3596, 3604
\__enumext_stop_store_level_vii: . . 114, 118,
    4372, 4380, 4572, 4582
\l__enumext_store_active_bool 30, 67, 112, 1907,
    1916, 1984, 2616, 3528, 3541, 3689, 3697, 4045, 4049,
    4574, 4584, 4805, 4821
\__enumext_store_active_keys:n 72, 73, 98, 2223,
    2223, 3521
\__enumext_store_active_keys_vii:n 72, 73, 117,
    2223, 2233, 4553
\__enumext_store_addto_prop:n 74, 86, 2298, 2298,
    2306, 2466, 2926, 4921
\__enumext_store_addto_seq:n 74, 87, 2307, 2307,
    2311, 2318, 2332, 2340, 2349, 2363, 2371, 2524, 3019
\l__enumext_store_anskey_arg_tl 30, 77, 78, 112,
    2472, 2477, 2479, 2484, 2491, 2494, 2504, 2509, 2512,
    2518, 2524
\__enumext_store_anskey_code:n 77, 80, 84, 2463,
    2463, 2609, 2862, 2870
\l__enumext_store_anskey_env_tl . . 30, 83, 112,
    2792, 2796, 2802, 2864, 2872
\l__enumext_store_anskey_opt_tl . . 30, 84, 112,
    2793, 2820, 2826, 2833, 2839, 2849, 2859, 2868
\__enumext_store_anskey_safe_outer: . . . . 80
\g__enumext_store_columns_break_bool . 2716,
    2817, 2879
\l__enumext_store_columns_break_bool . 2474,
    2565

```

`\l__enumext_store_current_label_tl` 30, 86, 87, 125, 112, 2907, 2910, 2913, 2919, 2924, 2926, 2983, 2986, 2989, 2995, 3000, 3010, 3019, 4898, 4903, 4907, 4920, 4921, 4923  
`\l__enumext_store_current_label_tmp_tl` . 30, 112, 3315, 3320  
`\l__enumext_store_current_opt_arg_tl` 30, 125, 112, 3029, 3042, 3048, 4909  
`\__enumext_store_internal_ref:` .. 76, 77, 2388, 2388, 2469  
`\g__enumext_store_item_join_int` .. 2719, 2824, 2828, 2880  
`\l__enumext_store_item_join_int` .. 2482, 2486, 2568  
`\g__enumext_store_item_star_bool` . 2721, 2831, 2881  
`\l__enumext_store_item_star_bool` . 2489, 2570  
`\g__enumext_store_item_symbol_sep_dim` 2726, 2846, 2851, 2883  
`\l__enumext_store_item_symbol_sep_dim` 2501, 2506, 2575  
`\g__enumext_store_item_symbol_tl` . 2724, 2837, 2841, 2882  
`\l__enumext_store_item_symbol_tl` . 2492, 2496, 2573  
`\l__enumext_store_keyans_item_opt_sep_tl` .... 2176, 2917, 2921, 2993, 2997, 4901, 4905  
`\__enumext_store_level_close:` . 74, 2312, 2336, 3557  
`\__enumext_store_level_close_vii:` . 75, 2343, 2367, 4588  
`\__enumext_store_level_open:` 74, 99, 2312, 2312, 3536, 3549  
`\__enumext_store_level_open_vii:` .. 75, 2343, 2343, 4578  
`\g__enumext_store_name_tl` 30, 67, 112, 363, 370, 371, 372, 373, 1960, 1986, 2109, 2114, 2119, 2133, 2138, 2143, 2889  
`\l__enumext_store_name_tl` 30, 67, 68, 112, 1793, 1796, 1820, 1823, 1911, 1920, 1955, 1964, 1965, 1986, 1987, 1988, 1990, 1991, 1993, 1995, 1996, 1998, 2000, 2001, 2025, 2300, 2302, 2309, 2452, 2453, 2555, 2798, 2966, 2967, 3080, 3093, 4938  
`\l__enumext_store_ref_key_bool` 77, 2199, 2467, 2515, 2930, 3007  
`\l__enumext_store_save_key_vii_bool` .. 2235, 2265  
`\l__enumext_store_save_key_vii_tl` 2237, 2238, 2266, 2267, 2347, 2355, 2359, 2363  
`\l__enumext_store_save_key_X_bool` .. 72, 130  
`\l__enumext_store_save_key_X_tl` .. 72, 73, 130  
`\l__enumext_store_upper_level_X_bool` .. 130  
`\__enumext_storing_exec:` 67, 82, 1962, 1978, 1982  
`\__enumext_storing_set:n` 66, 67, 1947, 1962, 1962  
`\l__enumext_the_counter_v_tl` ..... 737  
`\l__enumext_the_counter_vii_tl` ..... 669  
`\l__enumext_the_counter_viii_tl` ..... 685  
`\l__enumext_the_counter_X_tl` ..... 50  
`\__enumext_tmp:n` 45, 49, 54, 60, 71, 78, 79, 86, 94, 99, 100, 111, 134, 141, 166, 170, 174, 194, 1700, 1711, 1943, 1951, 2004, 2022, 2163, 2204, 2205, 2222, 2241, 2254, 2390, 2397, 2398, 2419, 2432, 2435, 2446, 2932, 2939, 3239, 3246, 3279, 3286, 3419, 3459, 3460, 3494  
`\__enumext_tmp:nn` 520, 541, 542, 576, 577, 592, 781, 806, 883, 905, 906, 926, 980, 988, 989, 1003, 1068, 1084, 1085, 1098, 1589, 1605, 3223, 3238  
`\__enumext_tmp:nnn` 593, 609, 610, 611, 612, 639, 655, 656  
`\__enumext_tmp:nnnnnn` 807, 832, 835, 838, 840, 842, 845, 848  
`\__enumext_tmp:w` ..... 5055, 5058  
`\l__enumext_tmpa_vii_int` 4198, 4201, 4210, 4241  
`\l__enumext_tmpa_viii_int` ..... 4229, 4232  
`\l__enumext_tmpa_X_dim` ..... 174  
`\l__enumext_tmpa_X_int` ..... 174  
`\l__enumext_topsep_v_skip` 1165, 1169, 1368, 4041  
`\l__enumext_topsep_vii_skip` .. 1445, 1454, 1458  
`\l__enumext_topsep_viii_skip` . 1467, 1489, 1493  
`\__enumext_undefine_anskey_env:` . 81, 85, 2649, 2649, 2900  
`\__enumext_unskip_unkern:` .. 33, 238, 238, 1218, 1390, 3598, 3599, 3639, 3759, 3760, 3777, 4729, 4730, 4993, 4994  
`\l__enumext_vspace_a_star_v_bool` ..... 1638  
`\l__enumext_vspace_a_star_vii_bool` ... 1660  
`\l__enumext_vspace_a_star_viii_bool` ... 1671  
`\l__enumext_vspace_a_star_X_bool` ..... 100  
`\__enumext_vspace_above:` 60, 100, 1606, 1606, 3609  
`\__enumext_vspace_above_v:` . 60, 1634, 1634, 3713  
`\l__enumext_vspace_above_v_skip` .. 1636, 1640, 1642  
`\__enumext_vspace_above_vii:` 61, 118, 1656, 1656, 4558  
`\l__enumext_vspace_above_vii_skip` 1658, 1662, 1664  
`\__enumext_vspace_above_viii:` . 61, 1656, 1667, 4836  
`\l__enumext_vspace_above_viii_skip` 1669, 1673, 1675  
`\l__enumext_vspace_b_star_v_bool` ..... 1649  
`\l__enumext_vspace_b_star_vii_bool` ... 1682  
`\l__enumext_vspace_b_star_viii_bool` ... 1693  
`\l__enumext_vspace_b_star_X_bool` ..... 100  
`\__enumext_vspace_below:` 60, 101, 1620, 1620, 3647  
`\__enumext_vspace_below_v:` . 60, 1645, 1645, 3786  
`\l__enumext_vspace_below_v_skip` .. 1647, 1651, 1653  
`\__enumext_vspace_below_vii:` 61, 118, 1678, 1678, 4568  
`\l__enumext_vspace_below_vii_skip` 1680, 1684, 1686  
`\__enumext_vspace_below_viii:` . 61, 1678, 1689, 4844  
`\l__enumext_vspace_below_viii_skip` 1691, 1695, 1697  
`\__enumext_widest_from:nnnn` .. 43, 765, 765, 780, 799  
`\g__enumext_widest_label_tl` 28, 38, 67, 502, 506, 510  
`\l__enumext_wrap_label_opt_v_bool` .... 3309  
`\l__enumext_wrap_label_opt_vii_bool` 119, 4625  
`\l__enumext_wrap_label_opt_viii_bool` .. 124, 4879  
`\l__enumext_wrap_label_opt_X_bool` .... 100  
`\l__enumext_wrap_label_v_bool` 3305, 3309, 3317, 3364, 3379  
`\l__enumext_wrap_label_vii_bool` .. 119, 4625, 4629, 4637, 4701  
`\l__enumext_wrap_label_viii_bool` . 124, 4879, 4883, 4891, 4963



<code>\l_enumext_wrap_label_X_bool</code> . . . . .	100
<code>\_enumext_wrapper_label_v:n</code> . . . . .	3366, 3381, 4105
<code>\_enumext_wrapper_label_vii:n</code> . . . . .	4703
<code>\_enumext_wrapper_label_viii:n</code> . . . . .	4965
<code>\l_enumext_write_aux_file_tl</code> . . . . .	31, 77, 87, 163, 2455, 2461, 2973, 2979
<code>enumext*</code> . . . . .	5, 4505
<code>enumXi</code> . . . . .	474
<code>enumXii</code> . . . . .	474
<code>enumXiii</code> . . . . .	474
<code>enumXiv</code> . . . . .	474
<code>enumXv</code> . . . . .	474
<code>enumXvi</code> . . . . .	474
<code>enumXvii</code> . . . . .	474
<code>enumXviii</code> . . . . .	474
Environments provide by <b>enumext</b> :	
<code>anskey*</code> . . . . .	30, 67, 73, 76, 78, 81–83, 85, 98, 99, 118, 127, 129, 134, 136
<code>enumext*</code> . . . . .	27, 28, 31–33, 36, 38, 41, 42, 44, 46–50, 56, 57, 61–64, 66–69, 71–77, 79, 81, 84–86, 92, 97–99, 104, 111, 112, 114–116, 118, 120–124, 126–129, 131, 135, 138, 139
<code>enumext</code> . . . . .	27, 28, 32, 33, 36, 38–52, 55, 58–64, 66–69, 71–74, 76, 77, 79, 81, 84–86, 89–93, 95, 96, 99, 101, 102, 106, 111, 114, 117, 118, 120, 123, 128, 129, 131, 135, 136, 138
<code>keyans*</code> . . . . .	27, 28, 30–34, 38, 41–44, 46–50, 56, 57, 61, 67, 68, 71, 72, 74, 81, 86, 92, 97, 104, 112, 113, 116, 122, 123, 135, 137, 139
<code>keyanspic</code> . . . . .	27, 28, 30, 31, 34, 38, 39, 42, 67, 68, 71, 74, 81, 86–88, 104–110, 137
<code>keyans</code> . . . . .	27, 28, 30, 31, 33, 34, 38, 39, 42, 44, 46–49, 52, 55, 58–60, 67, 68, 71, 72, 74, 81, 86–88, 92–96, 102, 104, 106, 107, 110, 114, 124, 135, 137
Environments:	
<code>center</code> . . . . .	111
<code>description</code> . . . . .	111
<code>enumerate</code> . . . . .	111
<code>flushleft</code> . . . . .	111
<code>flushright</code> . . . . .	111
<code>itemize</code> . . . . .	111
<code>list</code> . . . . .	32, 35, 36, 79, 95, 100, 101, 104, 106, 107, 111, 114
<code>lrbox</code> . . . . .	121
<code>minipage</code> . . . . .	32, 35, 36, 50, 52, 53, 106, 110, 111, 114, 121
<code>multicols</code> . . . . .	50–53, 58, 99, 100
<code>quotation</code> . . . . .	111
<code>quote</code> . . . . .	111
<code>scontents</code> . . . . .	82, 84
<code>tabbing</code> . . . . .	111
<code>trivlist</code> . . . . .	111
<code>verbatim</code> . . . . .	111
<code>verse</code> . . . . .	111
exp commands:	
<code>\exp_after:wN</code> . . . . .	5058
<code>\exp_args:Ne</code> . . . . .	2861, 2869, 3518, 5046
<code>\exp_args:Nv</code> . . . . .	2581, 2736, 3249, 3267, 3289, 5331
<code>\exp_not:N</code> . . . . .	58, 505, 628, 672, 688, 740, 936, 939, 950, 951, 952, 963, 964, 975, 976, 2520, 2552, 2553, 3012, 3077, 3078, 3090, 3091, 4935, 4936, 5055
<code>\exp_not:n</code> . . . . .	294, 309, 322, 330, 338, 567, 587, 628, 672, 688, 740, 937, 1727, 1736, 2187, 2284, 2296, 2458, 2486, 2496, 2506, 2520, 2521, 2828, 2841, 2851, 2976, 3014, 3016, 3927, 5160, 5170, 5363, 5368
<b>F</b>	
<code>\fbox</code> . . . . .	2170
<code>\fboxrule</code> . . . . .	2170
<code>\fboxsep</code> . . . . .	2170
file commands:	
<code>\file_input_stop:</code> . . . . .	5767
<code>first</code> . . . . .	989
<code>font</code> . . . . .	520
<code>\footnote</code> . . . . .	116
<code>\footnote</code> . . . . .	116, 4480
<code>\footnotemark</code> . . . . .	4490
<code>\footnotesize</code> . . . . .	2553, 3078, 3091, 4936
<code>\footnotetext</code> . . . . .	4474
<code>\foreachkeyans</code> . . . . .	17, 132, 5296
<b>G</b>	
<code>\getkeyans</code> . . . . .	17, 127, 5044
group commands:	
<code>\group_begin:</code> . . . . .	2551, 2596, 2771, 2858, 3076, 3089, 4934, 5101
<code>\group_end:</code> . . . . .	2558, 2612, 2875, 3083, 3096, 4941, 5108
<b>H</b>	
<code>\hbadness</code> . . . . .	4740, 5008
hbox commands:	
<code>\hbox_overlap_left:n</code> . . . . .	3157, 4694
<code>\hbox_set:Nn</code> . . . . .	494, 3971
<code>\hbox_set_end:</code> . . . . .	4739, 5007
<code>\hbox_set_to_wd:Nnw</code> . . . . .	4712, 4974
<code>\hfill</code> . . . . .	550, 555, 561, 562, 1545, 1572, 2520, 3012, 4375, 4439
hook commands:	
<code>\hook_gput_code:nnn</code> . . . . .	9, 204, 208, 212, 409
<code>\hook_gremove_code:nn</code> . . . . .	84, 2787
<code>\hook_gset_rule:nnnn</code> . . . . .	410
<code>\hook_if_empty:nTF</code> . . . . .	2785
<code>\hyperlink</code> . . . . .	78, 87
<code>\hyperlink</code> . . . . .	2520, 3012
<code>\hypertarget</code> . . . . .	37
<code>\hypertarget</code> . . . . .	441
<b>I</b>	
<code>\IfDocumentMetadataTF</code> . . . . .	3174, 3344, 3843, 3851, 3859, 3893, 3901, 3909, 3994, 4004, 4012, 4018, 4023, 4070, 4079, 4163, 4171, 4373, 4437, 4516, 4524, 4670, 4716, 4742, 4789, 4797, 4980, 5010
<code>\IfHyperBoolean</code> . . . . .	417
<code>\IfPackageLoadedTF</code> . . . . .	11, 19, 413, 429
<code>\ignorespaces</code> . . . . .	939, 952, 964, 976, 4521, 4598, 4631, 4654, 4661, 4707, 4731, 4794, 4852, 4885, 4916, 4969, 4995
<code>\inputlineno</code> . . . . .	294, 309, 322, 330, 338
int commands:	
<code>\int_add:Nn</code> . . . . .	4283, 4332
<code>\int_case:nn</code> . . . . .	1113, 1238, 2035, 2061, 2100, 2124
<code>\int_case:nnTF</code> . . . . .	240
<code>\int_compare:nNnTF</code> . . . . .	395, 660, 676, 695, 702, 1208, 1227, 1381, 1399, 1511, 1527, 1539, 1567, 2148, 2154, 2620, 2624, 2628, 2636, 2682, 2686, 2690, 2887, 2908, 2949, 2954, 2959, 2984, 3072, 3500, 3511, 3533, 3546, 3562, 3577, 3592, 3633, 3698, 3702, 3730, 3755, 3771, 3943, 4053, 4057, 4253, 4263, 4279, 4302, 4312, 4328, 4534, 4538, 4576, 4586, 4749, 4761, 4810, 4822, 5017, 5029, 5214, 5346
<code>\int_compare_p:nNn</code> . . . . .	263, 273, 285, 286, 300, 301, 1517, 1518, 2041, 2067, 2403, 2413, 2425, 2426, 2441, 2482, 2659, 2660, 2671, 2672, 2824, 3543
<code>\int_decr:N</code> . . . . .	4282, 4331
<code>\int_eval:n</code> . . . . .	380, 794, 2302, 2453, 2553, 2967, 3078, 3091, 3434, 3479, 4271, 4320, 4936

<code>\int_from_alph:n</code> .....	759, 773
<code>\int_from_roman:n</code> .....	761, 775
<code>\int_gadd:Nn</code> .....	4284, 4333
<code>\int_gdecr:N</code> .....	2044, 2049, 2053, 2057, 2070
<code>\int_gincr:N</code> 1877, 1882, 2465, 3022, 3111, 3145, 3324, 3622, 3722, 4094, 4604, 4680, 4858, 4925	
<code>\int_gset:Nn</code> .....	2093, 4488
<code>\int_gset_eq:NN</code> 1776, 1783, 1789, 1795, 1803, 1810, 1816, 1822, 4485	
<code>\int_gzero:N</code> . 351, 352, 353, 1553, 1580, 2160, 2880, 3638, 3776, 4772, 5041	
<code>\int_if_exist:NTF</code> 1751, 1787, 1793, 1814, 1820, 1998	
<code>\int_incr:N</code> 2635, 3499, 3693, 3942, 4533, 4603, 4809, 4857	
<code>\int_mod:nn</code> .....	4763, 5031
<code>\int_new:N</code> . 28, 29, 30, 31, 32, 33, 61, 62, 87, 104, 123, 144, 145, 156, 157, 158, 160, 171, 177, 178, 179, 180, 181, 1753, 2001	
<code>\int_set:Nn</code> 755, 759, 761, 1890, 1897, 1909, 1918, 2772, 4157, 4158, 4198, 4229, 4252, 4258, 4274, 4301, 4307, 4323, 4740, 5008, 5210, 5348	
<code>\int_set_eq:NN</code> .....	1878, 1883, 4281, 4330
<code>\int_sign:n</code> .....	2095
<code>\int_step_function:nnN</code> .....	2419, 2432, 2446
<code>\int_step_function:nnnN</code> .....	5352
<code>\int_step_inline:nn</code> .....	5262
<code>\int_step_inline:nnn</code> .....	4159
<code>\int_to_roman:n</code> .....	216, 2399, 2436
<code>\int_use:N</code> 373, 378, 379, 1209, 1228, 1540, 1892, 1899, 1911, 1920, 3434, 3454, 3479, 3519, 3563, 3572, 3587, 3593, 4256, 4257, 4269, 4305, 4306, 4318, 5683, 5687, 5693, 5697	
<code>\int_zero:N</code> .....	4753, 5021
<code>\item</code> . 89, 93, 118, 121, 124, 126, 386, 2320, 2326, 2351, 2357, 2479, 2986, 2989, 3163, 3328, 3998, 4000, 4518, 4520, 4791, 4793, 4923	
<code>\item*</code> .....	5, 14, 71, 3326
<code>item-pos*</code> .....	3223
<code>item-sym*</code> .....	3223
<code>\itemindent</code> .....	96
<code>\itemindent</code> .....	95
<code>itemindent</code> .....	883
<code>\itemsep</code> .....	3987
<code>\itemwidth</code> . 464, 2170, 3653, 3659, 3790, 3796, 4292, 4296, 4341, 4345	

K

<code>keyans</code> .....	14, 3799
<code>keyans*</code> .....	14, 4779
<code>keyanspic</code> .....	15, 3989

Keys for `\anskey` provide by [enumext](#):

<code>break-col</code> .....	77, 79, 82–84
<code>item-join</code> .....	77, 79, 82–84
<code>item-pos*</code> .....	78, 79, 82–84
<code>item-star</code> .....	78, 79, 82–84
<code>item-sym*</code> .....	78, 79, 82–84

Keys for `anskey*` provide by [enumext](#):

<code>break-col</code> .....	77, 79, 82–84
<code>item-join</code> .....	77, 79, 82–84
<code>item-pos*</code> .....	78, 79, 82–84
<code>item-star</code> .....	78, 79, 82–84
<code>item-sym*</code> .....	78, 79, 82–84

Keys for environments provide by [enumext](#):

<code>above*</code> .....	29, 46, 59–61, 100, 118
<code>above</code> .....	29, 46, 59–61, 100, 118, 123

<code>after</code> .....	48, 101, 118, 123
<code>align</code> .....	29, 39, 91, 94, 120, 134
<code>base-fix</code> .....	45, 62, 73, 98
<code>before*</code> .....	48, 100, 118, 123
<code>before</code> .....	48
<code>below*</code> .....	29, 59–61, 101, 118
<code>below</code> .....	29, 59–61, 101, 118, 123
<code>check-ans</code> . 31–33, 66–71, 74, 85, 88, 101, 118, 122, 135	
<code>columns-sep</code> .....	49, 99, 122
<code>columns</code> .....	29, 49, 59, 99
<code>first</code> .....	48, 121
<code>font</code> .....	39, 91, 94, 109, 120
<code>item-pos*</code> .....	90, 92
<code>item-sym*</code> .....	30, 90, 92
<code>itemindent</code> .....	29, 46, 47, 89, 90, 93, 94, 121
<code>itemsep</code> .....	44, 97, 122
<code>label-pos</code> .....	106
<code>label-sep</code> .....	106
<code>labelsep</code> .....	39, 96, 120
<code>labelwidth</code> .....	38–42, 44, 96, 120
<code>label</code> .....	28, 38, 40, 43, 44, 107, 111
<code>layout-sep</code> .....	106
<code>layout-sty</code> .....	106
<code>layout-top</code> .....	106
<code>lisparindent</code> .....	97
<code>list-indent</code> .....	29, 46, 107
<code>list-offset</code> .....	46, 101, 103
<code>listparindent</code> .....	46, 121
<code>mark-ans</code> .....	71, 74, 78
<code>mark-pos</code> .....	71, 72, 134
<code>mark-ref</code> .....	71, 74, 76, 78
<code>mini-env</code> 29, 36, 49, 58, 59, 74, 100, 111, 114, 115, 118, 123	
<code>mini-right*</code> .....	29, 32, 50, 74, 114, 115, 118
<code>mini-right</code> .....	29, 32, 50, 57, 74, 114, 115, 118
<code>mini-sep</code> .....	29, 49, 74, 100
<code>mode-box</code> .....	39
<code>no-store</code> .....	31, 66–68, 73, 79, 89, 90
<code>noitemsep</code> .....	44
<code>nosep</code> .....	44
<code>parindent</code> .....	97
<code>parsep</code> .....	44, 97, 121
<code>partopsep</code> .....	44
<code>ref</code> .....	28, 32, 40–42, 135
<code>resume*</code> .....	28, 61, 62, 66, 67, 73, 101, 118, 130
<code>resume</code> .....	28, 35, 61–67, 73, 74, 101, 118, 130
<code>rightmargin</code> .....	46, 112
<code>save-ans</code> 30, 35, 62–68, 70, 72–74, 79–82, 85–87, 93, 102, 108, 120, 123–125, 127, 128, 130, 135	
<code>save-key</code> .....	30, 62, 73, 98, 117
<code>save-pos</code> .....	74
<code>save-ref</code> .....	31, 37, 71, 74, 76–78, 86, 87, 94, 125
<code>save-sep</code> .....	71, 74, 86, 125
<code>series</code> .....	28, 61–66, 74, 98, 101, 117, 118, 130
<code>show-ans</code> .....	71, 72, 74, 75, 77, 78, 94, 109, 125
<code>show-length</code> .....	33, 47, 135
<code>show-pos</code> .....	30, 71, 72, 75, 77, 78, 88, 94, 109, 125
<code>start*</code> .....	29, 43, 44, 62
<code>start</code> .....	29, 32, 43, 44, 62
<code>store-key</code> .....	72
<code>topsep</code> .....	44, 46
<code>widest</code> .....	28, 32, 43, 44
<code>wrap-ans</code> .....	37, 71, 74, 75, 78
<code>wrap-label*</code> .....	29, 39, 89, 91, 93, 94, 119, 120, 124
<code>wrap-label</code> 29, 39, 89–91, 93, 94, 107, 109, 119, 120, 124	
<code>wrap-opt</code> .....	71, 74, 94, 109

keys commands:

\keys\_define:nn 514, 522, 544, 579, 595, 641, 710, 783, 809, 851, 885, 908, 982, 991, 1070, 1087, 1591, 1702, 1945, 2006, 2165, 2207, 2243, 2248, 2563, 2714, 2750, 3225, 3241, 3261, 3281, 3916, 5072, 5172, 5288, 5296

\keys\_if\_exist\_p:nn ..... 5284, 5285

\l\_keys\_key\_str 79, 82, 2581, 2736, 3249, 3267, 3289, 5331, 5439

\keys\_precompile:nnN .. 128, 200, 200, 5074, 5078, 5082, 5086, 5090, 5094, 5314

\keys\_set:nn . 536, 877, 1093, 1596, 1601, 1839, 1844, 1931, 1939, 2601, 3513, 3518, 3709, 3934, 3936, 3953, 4551, 4831, 5176, 5181, 5182, 5183, 5184, 5187, 5192, 5193, 5194, 5195, 5196, 5197, 5198, 5230, 5340

\keys\_set\_known:nn ..... 2868

keyval commands:

\keyval\_parse:NNn ..... 1716, 2273, 5148

L

label ..... 593, 639, 710

label-pos ..... 3915

label-sep ..... 3915

Labels provide by enumext:

\Alph\* ..... 38

\Roman\* ..... 38

\alph\* ..... 38

\arabic\* ..... 32, 38

\roman\* ..... 38

\labelsep ..... 3983

labelsep ..... 520

\labelwidth ..... 38

\labelwidth ..... 3983

labelwidth ..... 520

\lastkern ..... 249

\lastnodetype ..... 240

\lastskip ..... 244

layout-sep ..... 3915

layout-sty ..... 3915

layout-top ..... 3915

\leftmargin ..... 96

\leftmargin ..... 95, 3983

legacy commands:

\legacy\_if:nTF ..... 4665, 4668, 4948, 4951

\legacy\_if\_gset\_false:n ..... 400, 4388

\legacy\_if\_set\_false:n ..... 4667, 4950

\legacy\_if\_set\_true:n 4630, 4653, 4660, 4674, 4884, 4915

\linewidth ..... 100

\linewidth 3617, 3653, 3719, 3790, 4156, 4201, 4232, 4354, 4419

\list ..... 384

list-indent ..... 883

list-offset ..... 883

\listparindent ..... 3985

listparindent ..... 883

M

\makebox ..... 111

\makebox ..... 2378, 2380, 3208, 3376, 4087, 4698, 4960

\makelabel ..... 89, 91, 94, 111

\makelabel ..... 89, 93, 3190, 3206, 3360, 3374

\makesavenoteenv ..... 435

mark-ans ..... 2163

mark-pos ..... 2163, 2205

mark-ref ..... 2163

mini-env ..... 1068

mini-sep ..... 1068

\minipage ..... 390

\miniright ..... 10, 58, 1509, 1557, 1584, 3636, 3774

mode commands:

\mode\_if\_math:TF ..... 2644, 2698

\mode\_if\_vertical:TF 1147, 1175, 1195, 1219, 1370, 1391

\mode\_leave\_vertical: .. 866, 873, 936, 950, 2376, 3155, 4692

mode-box ..... 514

msg commands:

\msg\_error:nn .. 1559, 1586, 2605, 2638, 2642, 2696, 2804, 3700, 3704, 3945, 4002, 4055, 4536, 4812, 4824, 5199, 5258

\msg\_error:nnn 618, 664, 680, 732, 1513, 1520, 1525, 1555, 1582, 1851, 1855, 1970, 2587, 2646, 2664, 2676, 2684, 2688, 2692, 2700, 2742, 3255, 3273, 3295, 4540, 4817, 5060, 5069, 5141, 5246, 5277, 5286, 5323, 5344

\msg\_error:nnnn 2590, 2618, 2622, 2626, 2630, 2745, 3258, 3276, 3298, 3691, 4051, 4059, 4807, 5120, 5326

\msg\_error:nnnnn ..... 566, 586, 2186, 3926

\msg\_fatal:nn ..... 3501

\msg\_fatal:nnn ..... 468

\msg\_info:nnn ..... 13, 16, 21, 24, 415, 431

\msg\_line\_context: .. 5404, 5409, 5414, 5443, 5448, 5453, 5468, 5483, 5487, 5491, 5495, 5499, 5503, 5510, 5517, 5523, 5537, 5541, 5546, 5550, 5554, 5558, 5563, 5567, 5571, 5575, 5580, 5615, 5619, 5624, 5629, 5633, 5638, 5714, 5718, 5723, 5728, 5733, 5737, 5741, 5745, 5749, 5753, 5757, 5761, 5765

\msg\_log:nnn ..... 1990, 1995, 2000

\msg\_log:nnnnn ..... 377, 2133, 2138, 2143

\msg\_log:nnnnnn ..... 369

\msg\_new:nnn 5371, 5375, 5379, 5383, 5388, 5401, 5406, 5411, 5416, 5425, 5433, 5437, 5441, 5446, 5451, 5466, 5481, 5485, 5489, 5493, 5497, 5501, 5505, 5514, 5520, 5526, 5530, 5534, 5539, 5544, 5548, 5552, 5556, 5561, 5565, 5569, 5573, 5578, 5613, 5617, 5622, 5627, 5631, 5636, 5712, 5716, 5721, 5726, 5731, 5735, 5739, 5743, 5747, 5751, 5755, 5759, 5763

\msg\_new:nnnn .. 5392, 5583, 5592, 5601, 5607, 5640, 5650, 5660, 5670, 5680, 5690, 5700, 5706

\msg\_term:nnnn . 1954, 1959, 3443, 3453, 3485, 3490

\msg\_term:nnnnn ..... 2114

\msg\_warning:nn ..... 3635, 3773

\msg\_warning:nnnn 2151, 2157, 3391, 3396, 4255, 4268, 4304, 4317

\msg\_warning:nnnnn ..... 2109, 2119

\multicolsep ..... 99

\multicolsep ..... 1212, 1384, 3583, 3746

N

\NeedsTeXFormat ..... 3

\NewCommandCopy ..... 386

\newcounter ..... 471

\NewDocumentCommand 1509, 2593, 4047, 5044, 5099, 5206, 5255, 5333

\NewDocumentEnvironment . 3665, 3799, 3989, 4505, 4779

\newenvsc ..... 2707

\newlabel ..... 37

\newlabel ..... 453

no-store ..... 2004

\noindent ..... 3624, 4363, 4428, 4731, 4752, 4995, 5020

\nointerlineskip 1221, 1224, 1393, 1396, 1547, 1574, 4363, 4428

noitemsep ..... 807

\nopagebreak 1158, 1186, 1221, 1224, 1393, 1396, 1500, 1506

\normalfont ..... 2552, 3077, 3090, 4935

nosep ..... 807

P

Packages:

caption ..... 114

enumext ..... 27, 37, 40, 66, 95, 96, 106, 134

enumitem ..... 38

expl3 ..... 111

footnotehyper ..... 37

hyperref ..... 31, 32, 36, 37, 78, 87, 120, 133

ltxcmd ..... 35

lua-visual-debug ..... 52

multicol ..... 27, 133

scontents ..... 27, 81, 82

shortlst ..... 111, 116, 121

\par .. 1158, 1186, 1224, 1396, 1500, 1506, 1542, 1547, 1569, 1574, 2528, 3600, 3761, 3779, 4032, 4035, 4176, 4390, 4405, 4451, 4465, 4752, 5020

para commands:

\para\_end: ..... 4769, 5038

\parbox ..... 2170

\parindent ..... 4727, 4991

\parsep ..... 51, 107

\parsep ..... 867, 3476, 3967, 3976

parsep ..... 807

\parskip ..... 4728, 4992

\partopsep ..... 3477, 3777, 3986

partopsep ..... 807

peek commands:

\peek\_meaning:NTF 4609, 4623, 4638, 4649, 4863, 4877, 4892

\peek\_meaning\_remove:NTF ..... 4616, 4870

\peek\_remove\_spaces:n ..... 3332

\phantomsection ..... 37

\phantomsection ..... 442

prg commands:

\prg\_do\_nothing: ..... 446

\prg\_new\_protected\_conditional:Npnn ... 218

\prg\_replicate:nn ..... 235

\prg\_return\_false: ..... 222

\prg\_return\_true: ..... 221

\printkeyans ..... 17, 128, 5099

prop commands:

\prop\_const\_from\_keyval:Nn ..... 5247

\prop\_count:N 371, 2302, 2453, 2555, 2967, 3080, 3093, 4938, 5349

\prop\_get:NnNTF ..... 5273

\prop\_gput\_if\_not\_in:Nnn ..... 2300

\prop\_if\_exist:NTF ..... 1988, 5064, 5342

\prop\_item:Nn ..... 5066, 5366

\prop\_new:N ..... 1991

\ProvidesExplPackage ..... 4

R

\raggedcolumns ..... 3586, 3749

\raisebox ..... 4118

\ref ..... 76, 86

ref ..... 593, 639, 710

\refstepcounter ..... 4677, 4953

regex commands:

\regex\_match:nnTF .. 220, 758, 760, 772, 774, 2800

\regex\_replace\_once:nnN ..... 228

\renewcommand ..... 628, 672, 688, 740

\RenewDocumentCommand 1557, 1584, 3163, 3190, 3206, 3328, 3360, 3374, 4000, 4480

\RequirePackage ..... 17, 25

resume ..... 1700

resume\* ..... 1700

rightmargin ..... 883

\Roman ..... 38, 43, 44

\Roman ..... 490

\roman ..... 38, 43, 44

\roman ..... 491, 611, 5089

S

\s ..... 2801

save-ans ..... 1943

save-key ..... 2241

save-ref ..... 2163

save-sep ..... 2163

scan commands:

\scan\_stop: ..... 3998, 4518, 4791, 5055, 5058

scontents internal commands:

\l\_scontents\_fname\_out\_tl ..... 2760

\\_scontents\_parse\_environment\_keys:n . 2766

\\_scontents\_rescan\_tokens:n ..... 2773

\l\_scontents\_storing\_bool ..... 2758

\l\_scontents\_writing\_bool ..... 2759

seq commands:

\seq\_clear:N ..... 5208, 5351

\seq\_const\_from\_clist:Nn ..... 5201

\seq\_count:N ..... 372, 4182, 5212

\seq\_gclear:N ..... 4478, 4479

\seq\_gput\_right:Nn ..... 2309, 4491, 4492

\seq\_if\_empty:NTF ..... 4497, 5114, 5226

\seq\_if\_exist:NTF ..... 1993, 5112

\seq\_if\_in:NnNTF ..... 5118

\seq\_item:Nn ..... 2798, 4169

\seq\_map\_function:NN ..... 5217

\seq\_map\_inline:Nn ..... 5127, 5135, 5227, 5228

\seq\_map\_pairwise\_function:NNN ..... 4499

\seq\_new:N ..... 124, 125, 127, 142, 172, 173, 1996

\seq\_pop\_left:NN ..... 5216

\seq\_put\_right:Nn ..... 4061, 5224, 5240, 5361

\seq\_set\_from\_clist:Nn ..... 5209

\seq\_set\_map\_e:NNn ..... 5218

\seq\_use:Nn ..... 200, 201, 5357

series ..... 1700

\setcounter ..... 769, 773, 775, 3434, 3479, 4029

\setenumext ..... 6, 129, 5206

\setenumextmeta ..... 6, 131, 5247

show-ans ..... 2163, 2205

show-length ..... 980

show-pos ..... 2205

skip commands:

\skip\_add:Nn 1118, 1127, 1136, 1149, 1153, 1177, 1181, 1197, 1255, 1257, 1271, 1274, 1295, 1297, 1311, 1314, 1334, 1336, 1350, 1353, 1372, 1421, 1422, 1433, 1435, 3976, 3984

\skip\_gset:Nn ..... 1448, 1452, 1456

\skip\_gzero\_new:N ..... 1443, 1444

\skip\_horizontal:N 951, 963, 975, 4695, 4707, 4756, 4969, 5024

\skip\_horizontal:n ... 937, 2377, 2385, 3156, 3158, 4594, 4693, 4731, 4848, 4995

\skip\_if\_eq:nnTF 1116, 1125, 1134, 1241, 1281, 1321, 1409, 1445, 1467, 1608, 1622, 1636, 1647, 1658, 1669, 1680, 1691

<code>\skip_new:N</code>	81, 82, 83, 88, 89, 90, 91, 92, 93, 148, 192
<code>\skip_set:Nn</code>	1101, 1105, 1163, 1167, 1191, 1244, 1245, 1263, 1284, 1285, 1303, 1323, 1324, 1342, 1366, 1412, 1413, 1427, 1447, 1451, 1469, 1473, 1477, 1483, 1487, 1491, 3960
<code>\skip_set_eq:NN</code>	1202, 1203, 1205, 1212, 1377, 1378, 1379, 1384, 3432, 3475, 3476, 4728, 4992
<code>\skip_sub:Nn</code>	1251, 1253, 1267, 1269, 1291, 1293, 1307, 1309, 1330, 1332, 1346, 1348, 1419, 1420, 1431, 1432
<code>\skip_use:N</code>	1103, 1107, 1151, 1155, 1159, 1179, 1183, 1193, 1199, 1609, 1613, 1616, 1623, 1627, 1630, 3600
<code>\skip_vertical:N</code>	401, 404, 875, 4389, 4403, 4771, 5040
<code>\skip_vertical:n</code>	874, 4770, 5039
<code>\skip_zero:N</code>	1211, 1225, 1363, 1364, 1365, 1383, 1397, 3477, 3583, 3746, 3986, 3987
<code>\skip_zero_new:N</code>	1442, 1464, 1465, 1466
<code>\c_zero_skip</code>	401, 404, 875, 1116, 1125, 1134, 1282, 1321, 1445, 1467, 1609, 1623, 1636, 1647, 1658, 1669, 1680, 1691, 4389, 4403, 4771, 5040
<code>\small</code>	5077, 5081, 5085, 5089, 5093, 5097
socket commands:	
<code>\socket_assign_plug:nn</code>	3845, 3853, 3861, 3895, 3903, 3911
<code>\socket_new:nn</code>	3817, 3865
<code>\socket_new_plug:nnn</code>	3818, 3825, 3833, 3866, 3873, 3882
<code>\socket_use:n</code>	3846, 3896
<code>\socket_use:nn</code>	3854, 3862, 3904, 3912
<code>start</code>	781
<code>start*</code>	781
<code>start-list-tags</code>	3817, 3865
<code>\stepcounter</code>	3970, 4111, 4484
<code>stop-list-tags</code>	3817, 3865
<code>stop-start-tags</code>	3817, 3865
str commands:	
<code>\c_backslash_str</code>	2646, 5404, 5409, 5414, 5419, 5421, 5423, 5428, 5430, 5528, 5532, 5536, 5546, 5550, 5558, 5559, 5563, 5575, 5576, 5580, 5581, 5602, 5604, 5608, 5610, 5638, 5701, 5703, 5707, 5709, 5718, 5719, 5723, 5728, 5729, 5733, 5737, 5741
<code>\c_colon_str</code>	2452, 2966, 5055
<code>\c_left_brace_str</code>	5509, 5516, 5522
<code>\c_right_brace_str</code>	5509, 5516, 5522
<code>\str_case:nn</code>	256, 315
<code>\str_case:nnTF</code>	1723, 1731, 2280, 2288, 5155, 5164
<code>\str_clear:N</code>	3510, 4550
<code>\str_count:n</code>	235
<code>\str_if_empty:NTF</code>	1740, 1781, 1808
<code>\str_if_eq:nnTF</code>	3435, 3481, 5257
<code>\str_if_in:nnTF</code>	5051
<code>\str_new:N</code>	84, 132, 147, 187
<code>\str_set:Nn</code>	551, 557, 563, 582, 583, 584, 2183, 2184, 2210, 2211, 3921, 3924
<code>\str_use:N</code>	3210
<code>\string</code>	435
<code>\strutbox</code>	1230, 1233, 1244, 1245, 1256, 1258, 1273, 1276, 1284, 1285, 1296, 1298, 1313, 1316, 1323, 1324, 1335, 1337, 1352, 1355, 1401, 1404, 1412, 1413, 1421, 1422, 1434, 1436, 1447, 1448, 1451, 1458, 1471, 1479, 1485, 1493, 3979, 3984, 4032, 4040, 4124

T

tag commands:	
<code>\tag_mc_begin:n</code>	3823, 3871, 3880

<code>\tag_mc_end:</code>	3827, 3875, 3884
<code>\tag_resume:n</code>	3820, 3868, 4006, 4014, 4081, 4173, 4373, 4437
<code>\tag_struct_begin:n</code>	3821, 3822, 3829, 3830, 3831, 3869, 3870, 3877, 3878, 3879, 4015
<code>\tag_struct_end:</code>	4025, 4026
<code>\tag_struct_end:n</code>	3828, 3835, 3836, 3837, 3838, 3876, 3885, 3886, 3887, 3888, 4524, 4797
<code>\tag_suspend:n</code>	3839, 3889, 3996, 4008, 4020, 4072, 4165, 4516, 4789
<code>\tag_tool:n</code>	4007
TeX and L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> commands:	
<code>\@auxout</code>	451
<code>\@currentenv</code>	256, 315
<code>\protected@write</code>	451
tex commands:	
<code>\tex_newlinechar:D</code>	2772
text commands:	
<code>\text_expand:n</code>	5047
<code>\textasteriskcentered</code>	2180, 3229
<code>\textreferencemark</code>	2197
<code>\the</code>	244, 249
<code>\thepage</code>	457
tl commands:	
<code>\c_space_tl</code>	3048, 5453, 5468, 5491, 5495, 5682, 5683, 5692, 5693, 5753, 5757
<code>\tl_clear:N</code>	549, 556, 2161, 2227, 2237, 2258, 2266, 2472, 2792, 2793, 2907, 2983, 4898
<code>\tl_clear_new:N</code>	500
<code>\tl_const:Nn</code>	50, 484
<code>\tl_gclear:N</code>	363, 364, 365, 1761, 1766, 2882, 3201, 3219, 4409, 4469, 4696
<code>\tl_gclear_new:N</code>	1748
<code>\tl_gput_right:Nn</code>	485
<code>\tl_greplace_all:Nnn</code>	506
<code>\tl_gset:Nn</code>	291, 292, 306, 307, 1749, 1762, 1767, 1986, 2796, 3132, 4644
<code>\tl_gset_eq:NN</code>	502, 3128, 4689
<code>\tl_if_blank:nTF</code>	2585, 2603, 2740, 3253, 3271, 3293, 4687, 5321
<code>\tl_if_empty:NTF</code>	616, 634, 662, 678, 697, 704, 730, 746, 1774, 1779, 1801, 1806, 1864, 1928, 1936, 1965, 2025, 2316, 2347, 2492, 2837, 2859, 2889, 2917, 2993, 3042, 3153, 4180, 4901, 5238
<code>\tl_if_empty:nTF</code>	1829
<code>\tl_if_exist:NTF</code>	1834
<code>\tl_if_novalue:nTF</code>	2599, 2915, 2991, 3027, 3107, 3126, 3134, 3303, 3508, 3951, 4482, 4548, 4829, 4899
<code>\tl_map_inline:Nn</code>	226, 503
<code>\tl_new:N</code>	42, 43, 44, 47, 52, 53, 56, 57, 63, 65, 66, 68, 69, 105, 106, 107, 113, 114, 115, 116, 117, 118, 119, 120, 121, 122, 126, 128, 129, 130, 133, 136, 137, 155, 163, 164, 165, 168, 186, 3915
<code>\tl_put_left::Ne</code>	2826
<code>\tl_put_left:Nn</code>	2324, 2355, 2477, 2820, 2833, 2839, 2849, 3059, 3099, 4393, 4454, 4920, 4923
<code>\tl_put_right:Nn</code>	501, 626, 670, 686, 738, 2328, 2359, 2406, 2416, 2429, 2444, 2450, 2455, 2479, 2484, 2491, 2494, 2504, 2509, 2512, 2518, 2910, 2913, 2919, 2924, 2951, 2956, 2961, 2964, 2973, 2986, 2989, 2995, 3000, 3010, 4903, 4907
<code>\tl_remove_all:Nn</code>	5237
<code>\tl_remove_once:Nn</code>	2394, 2936
<code>\tl_replace_all:Nnn</code>	505, 5272
<code>\tl_reverse:N</code>	2393, 2395, 2935, 2937

<code>\tl_set:Nn</code> .	58, 260, 270, 319, 320, 327, 328, 335, 336, 470, 550, 555, 561, 562, 615, 659, 729, 934, 948, 961, 973, 1863, 1964, 2228, 2238, 2259, 2267, 2549, 2760, 3029, 3074, 3087, 4909, 4932, 5235, 5271, 5341
<code>\tl_set_eq:NN</code>	511, 621, 624, 667, 669, 683, 685, 735, 737, 2392, 2934, 2947, 3315, 3320, 4099, 4101
<code>\tl_to_str:n</code> . . . . .	1834, 1840, 1845, 5047
<code>\tl_trim_spaces:n</code> . . .	501, 5224, 5235, 5241, 5257
<code>\tl_use:N</code>	507, 510, 636, 699, 706, 748, 1006, 1010, 1014, 1018, 1022, 1026, 1030, 1034, 1038, 1042, 1046, 1050, 1054, 1058, 1062, 1066, 2382, 2399, 2407, 2418, 2431, 2436, 2447, 3115, 3121, 3149, 3192, 3193, 3200, 3212, 3306, 3310, 3318, 3362, 3363, 3369, 3378, 3672, 3805, 4104, 4400, 4461, 4700, 4732, 4733, 4962, 4996, 5001, 5102, 5103, 5104, 5105, 5106, 5123, 5220, 5339
token commands:	
<code>\token_to_str:N</code> . . . . .	453
<code>\topsep</code> . . . . .	3777, 3984
<code>topsep</code> . . . . .	807
<code>\topskip</code> . . . . .	1211, 1383
<code>\typeout</code> . . . . .	244, 249, 419, 423, 434, 435
<b>U</b>	
<code>\u</code> . . . . .	229, 2801
<code>\unkern</code> . . . . .	250
<code>unknown</code> . . . . .	3239, 3261, 3279
<code>\unskip</code> . . . . .	245
use commands:	
<code>\use:N</code> . . . . .	236, 3197, 3216, 3674
<code>\use:n</code> . . . . .	1714, 2271, 5053, 5146
<code>\use_none:nn</code> . . . . .	445, 5278
<code>\usecounter</code> . . . . .	3433, 3478
<b>V</b>	
<code>\value</code> . . . .	1777, 1783, 1790, 1796, 1804, 1810, 1817, 1823
vbox commands:	
<code>\vbox_set:Nn</code> . . . . .	4074
<code>\vbox_set_top:Nn</code> . . . . .	4398, 4459
<code>\vspace</code>	867, 1613, 1616, 1627, 1630, 1640, 1642, 1651, 1653, 1662, 1664, 1673, 1675, 1684, 1686, 1695, 1697
<b>W</b>	
<code>widest</code> . . . . .	781
<code>wrap-ans</code> . . . . .	2163
<code>wrap-label</code> . . . . .	520
<code>wrap-label*</code> . . . . .	520
<code>wrap-opt</code> . . . . .	2163
<b>Z</b>	
<code>\z</code> . . . . .	2801