

enumext

ENUMERATE EXERCISE SHEETS

V1.0 2024-05-06*

©2024 by Pablo González†

CTAN: <https://www.ctan.org/pkg/enumext>

 <https://github.com/pablgonz/enumext>

Abstract

This package provides “*enumerated list*” environments for creating “*simple exercise sheets*” along with “*multiple choice questions*”, storing the *answers* to these in memory using the **multicol** package and the **l3seq** and **l3prop** modules.

Contents

1	Introduction	2	4	The storage system	9
1.1	Description and usage	3	4.1	Keys for storage	10
1.2	The concept of left margin	3	4.2	Keys for internal label and ref	10
1.3	User interface	3	4.3	Keys for check answers	10
1.3.1	Internal counters	3	4.4	The command <code>\anskey</code>	10
1.3.2	Support for multicol	4	4.5	The environment keyans	11
1.3.3	Support for minipage	4	4.5.1	The <code>\item*</code> in keyans	11
1.3.4	The <code>\label</code> and <code>\ref</code> system	4	4.6	The environment keyanspic	12
1.3.5	Support for <code>\footnote</code>	4	4.6.1	The command <code>\anspic</code>	12
2	The environment enumext	4	4.7	Printing stored content	13
2.1	The <code>\item*</code> in enumext	5	4.7.1	The command <code>\getkeyans</code>	13
2.1.1	Keys for <code>\item*</code> in enumext	5	4.7.2	The command <code>\printkeyans</code>	13
3	The command \setenumext	5	5	Full examples	14
3.1	Keys for label and ref	6	6	The way of non-enumerated lists	16
3.2	Keys for spaces	6	7	References	18
3.2.1	Vertical spaces	7	8	Change history	18
3.2.2	Horizontal spaces	8	9	Index of Documentation	19
3.3	Keys for add code	8	10	Implementation	21
3.4	Keys for start and resume	9	11	Index of Implementation	102
3.5	Keys for multicol	9			
3.6	Keys for minipage	9			
3.6.1	The command <code>\miniright</code>	9			

Motivation and acknowledgments

Usually it is enough to use the classic **enumerate** environment to generate “*simple exercise sheets*” or “*multiple choice questions*”, the basic idea behind **enumext** is to cover three points:

1. To have a simple interface to be able to write “*lists of exercises*” with “*answers*”.
2. To have a simple interface for writing “*multiple choice questions*”.
3. To have a simple interface for placing “*columns*” and “*drawings*” or “*tables*”.

This package would not be possible without Phelype Oleinik who has collaborated and adapted a large part of the code and all \TeX team for their great work and to the different members of the **TeX-SX** community who have provided great answers and ideas. Here a note of the main ones:

1. Answer given by Alan Munn in `\topsep`, `\itemsep`, `\partopsep`, `\parsep` - what do they each mean (and what about the bottom)?
2. Answer given by Enrico Gregorio in Understanding minipages - aligning at top
3. Answer given by Ulrich Diez in Different mechanics of hyperlink vs. hyperref
4. Answer given by Enrico Gregorio in Minipage and multicol, vertical alignment

License and Requirements

Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License (lpl), version 1.3 or later (<https://www.latex-project.org/lpl.txt>). The software has the status “maintained”.

The **enumext** package loads and requires **multicol**[3] package, need to have a modern \TeX distribution such as \TeX Live or Mi \TeX . It has been tested with the standard classes provided by \TeX : **book**, **report**, **article** and **letter** on 10pt, 11pt and 12pt.

*This file describes a documentation for v1.0, last revised 2024-05-06.

†E-mail: pablgonz@educarchile.cl.

1 Introduction

In the \LaTeX world there are many useful packages and classes for creating “lists of exercises”, “worksheets” or “multiple choice questions”, classes like `exam`[1] and packages like `xsim`[2] do the job perfectly, but they don’t always fit the basic day to day needs.

In my work (and in the work of many teachers) it is common to use “simple exercise sheets” also known as “informal lists of exercises”, as an example:

1. Factor $x^2 - 2x + 1$

2. Factor $3x + 3y + 3z$

3. True False

(a) $\alpha > \delta$

(b) \LaTeX 2e is cool?

4. Related to Linux
- (a) You use linux?

(b) Usually uses the package manager?

(c) Rate the following package and class

i. `xsim-exam`

ii. `xsim`

iii. `exsheets`

Sometimes we are also interested in showing the “answers” along with the questions:

1. Factor $x^2 - 2x + 1$

*

$(x - 1)^2$

2. Factor $3x + 3y + 3z$

*

$3(x + y + z)$

3. True False

(a) $\alpha > \delta$

*

False

(b) \LaTeX 2e is cool?

*

Very True!

4. Related to Linux
- (a) You use linux?

*

Yes

(b) Usually uses the package manager?

*

Yes, dnf

(c) Rate the following package and class

i. `xsim-exam`

*

doesn’t exist for now :(

ii. `xsim`

*

very good

iii. `exsheets`

*

obsolete
- Or we are interested in referring to a specific question and its “answer”, for example:
- The answer to 3.(b) is “Very True!” and the answer to 4.(c).ii is “very good”.
- Or we are interested in printing all the “answers”:
1. (a) $(x - 1)^2$

*

ii. Yes, dnf

*

(b) $3(x + y + z)$

*

iii. A. doesn’t exist

*

(c) i. False

*

for now :(

*

ii. Very True!

*

B. very good

*

(d) i. Yes

*

C. obsolete

*
- Another very common thing to use in my work is “multiple choice questions”, for example:
1. First type of questions

4. Question with image and label below:
- (A) value

(C) value

(B) correct

(D) value
2. Second type of questions
- I. $2\alpha + 2\delta = 90^\circ$

II. $\alpha = \delta$

III. $\angle EDF = 45^\circ$
- (A) I only

(D) I and III only

(B) II only

(E) I, II, and III

(C) I and II only
- * 3. Third type of questions
- (1) $2\alpha + 2\delta = 90^\circ$

(2) $\angle EDF = 45^\circ$
- (A) value

(D) value

(B) value

(E) value

(C) value
-
5. Question with image on left side:
- (A) value

(B) value

(C) value

(D) correct

(E) value
-
- Where what we are interested in the `<label>` and a “short note” that we leave as an explanation, and then print them:
1. (a) (B) $x = 5$

*

(e) (C) some note

*

(b)

*

(f) (B)

*

(c) (D)

*

(g) (D) “other note”

*

(d)
- These “simple worksheets” or “multiple choice questions” appear to be easy to obtain using a combination of the `enumerate`, `minipage` and `multicols` environments, but like many things, what “looks simple” is not so simple.
- The `enumext` package was created and designed to meet these small requirements in the creation of “simple worksheets” and “multiple choice questions”.
- ©2024 by Pablo González L
- 2 / 113

1.1 Description and usage

The `enumext` package defines enumerated environments using the `list` environment provided by \LaTeX , but “does not redefine” any internal commands associated with it such as `\list`, `\endlist` or `\item` outside of the “scope” in which they are defined.

- This package is NOT intend to replace the `enumerate` environment nor replace the powerful `enumitem`[5], the approach is intended to work without hindering either of them.
This package can be used with `xelatex`, `lualatex`, `pdflatex` and the classical `latex>dvips>ps2pdf` and is present in \TeX Live and \MiKTeX , use the package manager to install. For manual installation, download `enumext.zip` and unzip it, run `lualatex enumext.dtx` and move all files to appropriate locations, then run `mktxlsr`. To produce the documentation run `lualatex enumext.dtx` two times.

```
enumext.sty  » TDS:tex/latex/enumext/
enumext.pdf  » TDS:doc/latex/enumext/
README.md   » TDS:doc/latex/enumext/
enumext.dtx  » TDS:source/latex/enumext/
```

The package is loaded in the usual way:

```
\usepackage{enumext}
```

1.2 The concept of left margin

There is a direct relationship between the parameters `\leftmargin`, `\itemindent`, `\labelwidth` and `\labelsep` plus an “extra space” that makes it difficult to obtain the desired *horizontal spaces* in a `list` environment.

Usually we don’t want the `list` to go beyond the left margin of the page, but since these four values are related, that causes a problem. The `enumitem`[5] package adds the `\labelindent` parameter to solve some of these problems. A simplified representation of this in the figure 1.




Figure 1: Representation of horizontal lengths in `enumitem`.

The `enumext` package does NOT provide a user interface to set the values for `\leftmargin` and `\itemindent`, instead it provides the keys `list-offset` and `list-indent` which internally set the values for `\leftmargin` and `\itemindent`. The concepts of `\leftmargin` and `\itemindent` are different in `enumext`. The figure 2 shows the visual representation of idea.




Figure 2: Representation of horizontal lengths concept in `enumext`.

In this way we reduce a *little* the amount of parameters we have to pass. With the default values of keys `list-offset`, `list-indent`, `labelwidth` and `labelsep` the lists will have the (usually) expected output for “*simple worksheets*”. The figure 3 shows the visual representation.



Figure 3: Default horizontal lengths `list-offset=0pt`, `list-indent=\labelwidth+\labelsep` in `enumext`.

1.3 User interface

The user interface consists in `enumext`, `enumext*`, `keyans`, `keyans*` and `keyanspic` environments, `\anskey`, `\item*` and `\anspic*` commands to \langle stored content \rangle , `\getkeyans` command to get the individual \langle stored content \rangle , `\printkeyans` to print all \langle stored content \rangle , `\miniright` for `minipage` and `\setenumext` to config all $[(key = val)]$ options.

1.3.1 Internal counters

The package `enumext` uses internally the `enumXi`, `enumXii`, `enumXiii`, `enumXiv` counters for the four nesting levels of the `enumext` environment, the `enumXv` counter for the `keyans` environment, the `enumXvi` counter for the `keyanspic` environment, the counter `enumXvii` for `enumext*` environment and the counter `enumXviii` for `keyans*` environment.

- If any package defines these counters or they are user-defined in the document, the package will return a missing error and abort the load.

1.3.2 Support for multicol

The package provides direct support for using the `multicol`[3] package. This allows to obtain directly a two-column output as shown in the figure 4.




Figure 4: Representation of the two column output for a nested level in `enumext` environment.

The “non starred” version of the `multicols` environment is always used together with the `\raggedcolumns` command and is controlled by `columns` and `columns-sep` keys. The environment is available for all nesting levels, and can can together with the `mini-env` key. If you need to force a start a new column `\columnbreak` must be used (see §3.5).

- The `\columnseprule` command is not available as a key and is set to “zero” for the inner levels and the `keyans` environment. If the value of this is set inside the document, it will affect “all environments” that use the `columns` key.

1.3.3 Support for minipage

The package provides direct support for `minipage` environment, this allows you to obtain an output like the one shown in figure 5.



Figure 5: Representation of the `mini-env` output for a nested level `enumext` environment.

The `minipage` environments (left and right) is always used with “aligned on top” [`t`], the `minipage` environment on the “right side” always starts with `\centering`. It can be used at all nesting levels and is controlled by `mini-env` and `mini-sep` keys. In order to switch from the “left” side `minipage` environment to the “right” side one must use the command `\miniright` (see §3.6).

1.3.4 The \label and \ref system

This package provides a user interface like the `enumitem`[5] package to customize the references which is activated by the `ref` key (§3.1), the standard \TeX `\label` and `\ref` commands work as usual. It also provides an “internal reference” system for the “stored content” by means of the key `store-ref` (§4.2) when the key `save-ans`(§4.1) is active.

- The implementation of `\label` and `\ref` together with the `store-ref` key are compatible with the `hyperref`[7] package.

1.3.5 Support for \footnote

This package provides an internal implementation for the `\footnote` command which is compatible with the `hyperref` package, but, it will not produce the expected links, and when using the `mini-env` key or the starred environments `enumext*` and `keyans*` the output will look like the classic way they are displayed in the `minipage` environment.

The best way to solve this is to use Jean-François Burnol `footnotehyper`[8] package, it will support keeping the links if `hyperref` is loaded with the `hyperfootnotes=true` option (default) and will show the output numbered at the bottom of the page (as opposed to how it is displayed in the `minipage` environment). The way to load it is as follows:

```
\usepackage{footnotehyper}
\makesavenoteenv{enumext}
\makesavenoteenv{enumext*}
```

2 The environment enumext

<code>enumext</code>	<code>\begin{enumext} [⟨keyval list⟩]</code>	<code>\begin{enumext*} [⟨keyval list⟩]</code>
<code>enumext*</code>	<code>\item ⟨item content⟩</code>	<code>\item ⟨item content⟩</code>
	<code>\item [⟨custom⟩] ⟨item content⟩</code>	<code>\item [⟨custom⟩] ⟨item content⟩</code>
	<code>\item* [⟨symbol⟩] [⟨offset⟩] ⟨item content⟩</code>	<code>\item* [⟨symbol⟩] [⟨offset⟩] ⟨item content⟩</code>
	<code>\end{enumext}</code>	<code>\end{enumext*}</code>

The `enumext` is an “*enumerated list*” environment that works in the same way as the standard `enumerate` environment provided by L^AT_EX, `\item` and `\item[⟨custom⟩]` commands work in the usual way.

The environment can be nested with at most “*four levels*” and the options can be configured globally using `\setenumext` command and locally using `[⟨key = val⟩]` in the environment.

Example

1. This text is in the first level.
 - (a) This text is in the second level.
 - i. This text is in the third level.
 - A. This text is in the fourth level.
- X This text is in the first level.
- ★ 2. This text is in the first level.

```
\begin{enumext}
  \item This text is in the first level.
  \begin{enumext}
    \item This text is in the second level.
    \begin{enumext}
      \item This text is in the third level.
      \begin{enumext}
        \item This text is in the fourth level.
      \end{enumext}
    \end{enumext}
  \end{enumext}
  \item[X] This text is in the first level.
  \item* This text is in the first level.
\end{enumext}
```

2.1 The \item* in enumext

```
\item* \item*
\item*[⟨symbol⟩]
\item*[⟨symbol⟩][⟨offset⟩]
```

The `\item*`, `\item*[⟨symbol⟩]` and `\item*[⟨symbol⟩][⟨offset⟩]` works like the numbered `\item`, but placing a `⟨symbol⟩` to the “*left*” of the `⟨label⟩` separated from it by the value set by the `labelsep` key and can be `⟨offset⟩` using the second optional argument. The default values for `⟨symbol⟩` and `⟨offset⟩` are `\star` ‘★’ and the value set by `labelsep` key.

The *starred version* ‘★’ cannot be separated by spaces ‘’ from the command, i.e. `\item*` and the first optional argument does “*not support*” verbatim content. Can be configure with the keys `item-sym*` and `item-pos*` locally in the environment or globally using `\setenumext` command (§3).

🔗 The behavior of `\item*` in the `enumext` environment is NOT the same as in the `keyans` environment.

2.1.1 Keys for \item* in enumext

`item-sym*` = {`⟨symbol⟩`} default: `\star`
 Sets the `symbol` to be displayed in the “*left*” of the box containing the current `⟨label⟩` set by `labelwidth` key for `\item*` in `enumext`. The `symbol` can be in text or math mode, for example `item-sym*={\ast}`.

`item-pos*` = {`⟨rigid length | dim expression⟩`} default: *by levels*
 Sets the `offset` between the box containing the current `⟨label⟩` defined by `labelwidth` key and the `⟨symbol⟩` set by `item-sym*` key. The default values are set by `labelsep` key at each level. If positive values are passed it will *offset to the left* and if negative values are passed it will *offset to the right*.

3 The command \setenumext

```
\setenumext \setenumext[⟨enumext, level⟩]{⟨key = val⟩} \setenumext[⟨enumext*⟩]{⟨key = val⟩}
\setenumext[⟨print, level⟩]{⟨key = val⟩} \setenumext[⟨keyans*⟩]{⟨key = val⟩}
\setenumext[⟨keyans⟩]{⟨key = val⟩} \setenumext[⟨print*⟩]{⟨key = val⟩}
```

The command `\setenumext` sets the `⟨keys⟩` on a global basis for environment `enumext`, the `\printkeyans` command and the `keyans` environment. It can be used both in the preamble and in the body of the document as many times as desired.

The `⟨keys⟩` set in the optional arguments of environments and commands have the highest precedence, overriding both options passed by `\setenumext`. If the optional argument is not passed, the first level of the environment `enumext` will be taken by default.

- It should be kept in mind that using any *key* that sets a *rubber or rigid lengths* for vertical or horizontal space on a level will influence the vertical and horizontal space for *inners levels* and *keyans* and *keyanspic* environments. All *keys* related to vertical or horizontal spacing accept a “*skip*” or “*dim*” expression if passed between braces, i.e. you do not need to use `\dimexpr` or `\dimeval` to perform calculations.

3.1 Keys for label and ref

`label = {⟨\alph* | \Alph* | \arabic* | \roman* | \Roman*⟩}` default: *by levels*

Sets the *label* that will be printed at the *current level*. The default value for first level are `\arabic*`, for second level are `(\alph*)`, for third level are `\roman*`, and for fourth level are `\Alph*`.

- This key is intended to give the basic structure with which the *label* will be displayed, and the and the form in which it is used by standard “*label and ref*” and the “*internal reference*” system with the `store-ref` key. You cannot use commands with *label* as an argument, for example `\emph{⟨\alph*⟩}` will return an error. For full customization of how *label* is displayed use the `font` or `wrap-label` keys.

`ref = {⟨code {⟨\alph* | \Alph* | \arabic* | \roman* | \Roman*⟩ more code⟩}` default: *empty*

Modifies the way *cross references* are displayed. The `label` key sets the default form of the *cross references*, by using this key you can define a different format, for example: `ref=\emph{⟨\alph*⟩}` is valid.

- Internally, it renews the command associated with each counter when it is executed, i.e., `\theenumxi` is modified when the key is executed at the first level, `\theenumxii` when it is executed at the second level and `\theenumxiii` together with `\theenumxiv` when it is executed at the third and fourth levels.

This must be kept in mind, since the values set by the `label` and `ref` keys are not cumulative by levels, so if you have used the `ref` key in the first level and then want to associate the counter with `label` or `ref` in the second level you must use the direct commands, i.e. `\arabic{enumxi}` to indicate the count of the first level instead of using `\theenumxi`.

`labelsep = {⟨rigid length⟩}` default: `0.3333em`

Sets the *horizontal space* between the box containing the current *label* defined by `label` key and the text of an item on the first line. Internally sets the value of `\labelsep` for the current level.

`labelwidth = {⟨rigid length⟩}` default: *by label*

Sets the *width* of the box containing the current *label* set by `label` key. Internally sets the value of `\labelwidth` for the current level. The default values are calculated by means of the *width* of a box by setting a *value* to the current counter using ‘0’ for `\arabic*`, ‘M’ for `\Alph*`, ‘m’ for `\alph*`, ‘VIII’ for `\Roman*` and ‘viii’ for `\roman*`.

`widest = {⟨integer | string⟩}` default: *empty*

Sets the `labelwidth` key pass the *integer* or converting the *string* of the form `\Alph`, `\alph`, `\Roman` or `\roman` to a *value* for the current counter defined by `label` key, then calculating the *width* by means of a box. For example `widest={XXIII}` or `widest={23}` are equivalent. This key is useful when the default values of the `labelwidth` key are smaller than those actually used.

`font = {⟨font commands⟩}` default: *empty*

Sets the *font style* for the current *label* defined by `label` key. For example `font={\bfseries\small}`.

`align = {⟨left | right | center⟩}` default: *left*

Sets the *aligned* of *label* defined by `label` key on the current level in the label box.

`wrap-label = {⟨code {#1} more code⟩}` default: *empty*

Wraps the current *label* defined by `label` key referenced by `{#1}`. The `{⟨code⟩}` must be passed between braces. This key does not modify the value set by the `labelwidth` key and is applied only on `\item` and `\item*`. When using it in the `\setenumext` command it is necessary to use the *double hash* ‘`{#1}`’. For example `wrap-label={\fbox{#1}}` or you can create a command:

```
\NewDocumentCommand \itembx { s +m }
{
  %
  \IfBooleanTF{#1}
  {
    {\strut\smash{\parbox[t]{\labelwidth}{\raggedright{#2}}}}%
    {\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{#2}}}}%
  }
}
```

and then pass it through the key `wrap-label={\itembx{#1}}` or `wrap-label={\itembx*{#1}}`.

`wrap-label* = {⟨code {#1} more code⟩}` default: *empty*

The same as the `wrap-label` key but also applies on `\item[⟨custom⟩]`.

3.2 Keys for spaces

`show-length = {⟨true | false⟩}` default: *false*

Displays on the terminal the values for *all list parameters* at the current level. For *vertical spaces* show the values of `\topsep`, `\itemsep`, `\parsep` and `\partopsep`. For *horizontal spaces* show the values of `\labelwidth`, `\labelsep`, `\itemindent`, `\listparindent` and `\leftmargin`.

3.2.1 Vertical spaces

`topsep = {⟨rubber length | rigid length⟩}`

default: *by levels*

Set the *vertical space* added to both the top and bottom of the list. Internally sets the value of `\topsep` for the current level. The default values for first level are 8.0pt plus 2.0pt minus 4.0pt, for second level are 4.0pt plus 2.0pt minus 1.0pt, for third and fourth level are 2.0pt plus 1.0pt minus 1.0pt.

`parsep = {⟨rubber length | rigid length⟩}`

default: *by levels*

Set the *vertical space* between paragraphs within an item. Internally sets the value of `\parsep` for the current level. The default values for first level are 4.0pt plus 2.0pt minus 1.0pt, for second level are 2.0pt plus 1.0pt minus 1.0pt, for third and fourth level are 0pt.

`partopsep = {⟨rubber length | rigid length⟩}`

default: *by levels*

Set the *vertical space* added, beyond `topsep`, to the “top” and “bottom” of the entire environment if the environment instance is preceded by a “blank line” or `\par` command. Internally sets the value of `\partopsep` for the current level. The default values for first and second level are 2.0pt plus 1.0pt minus 1.0pt, for third and fourth level are 1.0pt minus 1.0pt.

- The value of this parameter also affects the *inner levels* and the *keyans* environment. Caution should be taken with “blank lines” or `\par` command “before” each environment or nested level when formatting the source code of document. T_EX will enter *vertical mode* and apply this value to the “top” and “bottom” the environment or nested level.

`itemsep` = {*<rubber length | rigid length>*} default: *by levels*

Set the *vertical space* between items, beyond the `parsep`. Internally sets the value of `\itemsep` for the current level. The default values for first level are `4.0pt` plus `2.0pt` minus `1.0pt`, for the rest of the levels are `2.0pt` plus `1.0pt` minus `1.0pt`.

`noitemsep` *<value forbidden>* default: *not used*

This is a “meta-key” that does not receive an argument. Set `itemsep` and `parsep` equal to `0pt` the entire level of environment.

`nosep` *<value forbidden>* default: *not used*

This is a “meta-key” that does not receive an argument. Sets all keys for vertical spacing equal to `0pt` the entire level of environment.

- The following *<keys>* should be used with “caution”, they are intended to be used at the “top” and “bottom” of the environment when the `columns` or `mini-env` keys do not provide adequate *vertical spaces*. The values passed can be *rubber* or *rigid* lengths, the way they are applied is the way you differ, using the star ‘*’ *<keys>* applies `\vspace*` so that \LaTeX does *not discard* this space at page break.

`above` = {*<rubber length | rigid length>*} default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the top of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “above” the environment without hindering the value of the `topsep` key. The space is added with `\vspace` so is “discardable”.

`above*` = {*<rubber length | rigid length>*} default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the top of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “above” the environment without hindering the value of the `topsep` key. The space is added with `\vspace*` so is “not discardable”.

`below` = {*<rubber length | rigid length>*} default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the bottom of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “below” the environment without hindering the value of the `topsep` key. The space is added with `\vspace` so is “discardable”.

`below*` = {*<rubber length | rigid length>*} default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the bottom of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “below” the environment without hindering the value of the `topsep` key. The space is added with `\vspace*` so is “not discardable”.

3.2.2 Horizontal spaces

`itemindent` = {*<rigid length>*} default: `0pt`

Extra *horizontal indentation*, beyond `labelsep`, of the “first line” off each item. This value is applied internally using `\hspace` and does not modify the value of `\itemindent`.

`rightmargin` = {*<rigid length>*} default: `0pt`

Set the *horizontal space* between the right margin of the environment and the right margin of the enclosing environment, the value it takes must be greater than or equal to `0pt`. Internally sets the value of `\rightmargin` for the current level.

`listparindent` = {*<rigid length>*} default: `0pt`

Sets the *horizontal space* indentation, beyond `list-indent`, for second and subsequent paragraphs within a list item. Internally sets the value of `\listparindent` for the current level.

`list-offset` = {*<rigid length>*} default: `0pt`

Sets the *horizontal translation* of the entire environment level from the left edge of the box defined by the `labelwidth` key. Internally sets the values of `\leftmargin` and `\itemindent` for the current level.

`list-indent` = {*<rigid length>*} default: `labelwidth + labelsep`

Sets the *indentation* of the whole environment under the box defined by `labelwidth` and `labelsep` keys. Internally sets the value of `\leftmargin` and `\itemindent` for the current level.

- If `list-indent=0pt` the *<label>* will be part of the text, separated by the value of the `labelsep` key and the *first word*, in simple terms it will look like a “common paragraph”. This setting is equivalent (more or less) to the `wide` key provided by the `enumitem` package.

3.3 Keys for add code

- The following *<keys>* should be used with “caution”, they are intended to inject *{<code>}* into different parts of the defined environments. We must keep in mind that the defined environments are based on the `list` base environment provided by \LaTeX which is defined (simplified) as plain form `\list{<arg one>}{<arg two>}`. Using the `before*` key does not allow access to the `list` parameters defined by [*<key = val>*].

`before` = {*<code>*} default: *not used*

Execute *{<code>}* “before” the environment starts. The *{<code>}* is executed “after” performing all calculations related to the *list parameters* in the environment and the parameters sets by [*<key = val>*] that is, in the second argument of the list after setting all the parameters `\list{<arg one>}{<arg two>}{<code>}`. The *{<code>}* must be passed between braces.

`before*` = {*<code>*} default: *not used*

Execute `{\code}` “before” the environment starts. The `{\code}` is executed “before” performing all calculations related to the *list parameters* and `[\key = val]` sets in the environment that is, before the arguments defining the environment are executed: `{\code}\list{\arg one}{\arg two}`. The `{\code}` must be passed between braces.

`first = {\code}` default: *not used*
 Executes `{\code}` when “starting” the environment. The `{\code}` must be passed between braces, is executed right “after” all *list parameters* are done, after the second argument of `list`, just before the first occurrence of `\item`: `\list{\arg one}{\arg two}{\code}\item`.

- Keep in mind that the code set in this key will affect the entire “body” of the environment and therefore the inner levels of the `list` and the `keyans` environment. It is recommended to set this key per level.

`after = {\code}` default: *not used*
 Execute `{\code}` “after” finishing the environment. The `{\code}` must be passed between braces.

3.4 Keys for start and resume

`start = {\integer | string}` default: `1`
 Sets the *start value* of the numbering on the current level. Internally `\string` is passed as value to the counter defined by `label` key on the current level, i.e. it is equivalent to enter `start=5`, `start=E` or `start=v`.

`resume \value forbidden` default: *not used*
 Sets the *start* to value from the previous of the counter defined by `label` key for the “first level”. This `\key` does not receive an argument. The `\key` can be overwritten using the `start` key. If the `save-ans` key is present and `{\store name}` exist, the numbering will continue according to this key. This key is “only” available for the “first level” of `enumext`.

3.5 Keys for multicol

`columns = {\integer}` default: `1`
 Set the *number of columns* to be used by the `multicol` environment within the environment. The value must be a positive integer less than or equal to `10`.

`columns-sep = {\rigid length}` default: *by level*
 Set the *space between columns* used by the `multicol` environment within the environment. Internally sets the value of `\columnsep`, by default its value is equal to the sum of the values set in the keys `labelwidth` and `labelsep` of the current level.

- The `\footnote{\text}` command in the nested levels of `multicol` will not work as expected, prefer the use of `\footnotemark[\number]` inside the environment and `\footnotetext[\number]{\text}` outside the environment or via the `after` key.

3.6 Keys for minipage

`mini-env = {\rigid length}` default: *not used*
 Sets the *width* of the `minipage` environment on the “right side”. This value added to the value set by the `mini-sep` key to determines the *width* of the `minipage` environment on the “left side”, taking `\linewidth` as the maximum reference value.

`mini-sep = {\rigid length}` default: `0.3333em`
 Sets the *space between* the `minipage` environment on the “left side” and the `minipage` environment on the “right side”. This separation is applied together with `\hfill`.

3.6.1 The command `\miniright`

`\miniright` The `\miniright` command close the `minipage` environment on the “left side” and opens the `minipage`
`\miniright*` environment on the “right side” by starting it with the `\centering` command. It must be placed “after” the last `\item` of the current environment and “before” starting the material to be placed on the “right side”. The starred version ‘`*`’ inhibits the use of `\centering` command i.e. the usual L^AT_EX justification is maintained in the `minipage` on the “right side”.

- The `\footnote{\text}` command in `minipage` environment will work as usual. If you prefer the footnotes to be numbered (not lowercase) and outside the environment, use `\footnotemark[\number]` inside the environment and `\footnotetext[\number]{\text}` outside the environment or via the `after` key.

4 The storage system

The entire mechanism for “storing content” it is activated according to `save-ans` key on the “first level” of `enumext` environment. Only when this `\key` is “active” the `\anskey` command and the environments `keyans` and `keyanspic` are available.

<pre>\begin{enumext}[save-ans={\store name}] \item Text \begin{keyans} ... \end{keyans} \end{enumext}</pre>	<pre>\begin{enumext}[save-ans={\store name}] \item Text \begin{keyanspic} ... \end{keyanspic} \end{enumext}</pre>
---	---

4.1 Keys for storage

- save-ans = { <store name> }

default: not set

Sets the “name” of the <sequence> and <prop list> in which the contents will be “stored” by \anskey in enumext environment, \item* in keyans environment and \anspic* in keyanspic environment. If the <sequence> or <prop list> does not exist, it will be created globally.
- wrap-ans = { <code {#1} more code> }

default: \fbox

Wraps the current <argument> passed \anskey command to referenced by {#1}. The {<code>} must be passed between braces. This <key> only affects the current <argument> passed to \anskey and NOT the “stored content” in the <store name> set by save-ans key. If this key is passed using the \setenumext command it is necessary to use double ‘{##1}’.
- mark-ans = { <symbol> }

default: \textasteriskcentered

Sets the symbol to be displayed in the left margin of the “stored content” in <store name> set by save-ans key when using show-ans key.
- mark-pos = { <left | right> }

default: left

Sets the aligned of the symbol defined by mark-ans key. The “symbol” is aligned in a box with the same dimensions of the label box defined by labelwidth key on the current level and separated by the value of the labelsep key.
- show-ans = { <true | false> }

default: false

Displays the current <argument> passed to \anskey in enumext environment, the current <label> for \item* in keyans environment and the current <label> for \anspic* in keyanspic environment at the place where it is executed. If the optional argument is present in \item* or \anspic* it will be shown in square brackets.
- show-pos = { <true | false> }

default: false

Displays the position occupied by the “stored content” by \anskey in enumext environment, \item* in keyans environment and \anspic* in keyanspic environment in <store name> set by save-ans key. This position is used by the \getkeyans command and by the \ref command if the store-ref key is active.

4.2 Keys for internal label and ref

- store-ref = { <true | false> }

default: false

Activates the internal “label and ref” mechanism for referencing “stored content” in <store name> set by save-ans key. To reference the location of the “stored content” within the environment you must use \ref{<store name: position>}, where <position> corresponds to the position occupied by the “stored content” in the <store name> returned by the show-pos key. For example \ref{test:4} will return 3. (b) which corresponds to the location of the “stored content” at position 4 within the environment in which the key save-ans=test was set.
- mark-ref = { <symbol> }

default: \textasteriskcentered

Sets the symbol that will be displayed by the \printkeyans command only if the hyperref package is detected and the store-ref key are active. This “symbol” is used as a “link” between the environment in which the save-ans key was used and the place where the command is executed.

4.3 Keys for check answers

- check-ans = { <true | false> }

default: false

Enables the “checking answer” mechanism. This key works under the logic that each question will contain “only one answer”, it is intended to be used in conjunction with no-store key.
- no-store <value forbidden>

default: not used

This is a “meta-key” that does not receive an argument. This key is used in conjunction with check-ans and is designed to be used with nested levels of enumext in which the \anskey command will not be used.

4.4 The command \anskey

\anskey \anskey{<content>}

The \anskey command takes a mandatory argument and is triggered by save-ans key. The “content” are “stored” in <store name> set by save-ans key. The command does “not support” verbatim content and must NOT be nested. By design it is assumed that each \item or \item* will have a “single” occurrence of the command unless a nested level is opened or the no-store key is used. If store-ref key are active and the hyperref[7] package is detected, \hyperLink and \hypertarget will be used, otherwise the usual “label and ref” system provided by L^AT_EX will be used.

Example

- ★ 1. Text containing our instructions or questions.

*

first answer

2. Text containing our instructions or questions.

(a) Question.

*

second answer
3. Text containing our instructions or questions.

*

third answer

4. Text containing our instructions or questions.

*

fourth answer

```
\begin{enumext}[save-ans=test,show-ans]
  \item* Text containing our instructions or questions. \anskey{\first answer}
  \item Text containing our instructions or questions.
    \begin{enumext}
      \item Question.\anskey{\second answer}
    \end{enumext}
  \item Text containing our instructions or questions. \anskey{\third answer}
  \item Text containing our instructions or questions. \anskey{\fourth answer}
\end{enumext}
```

4.5 The environment keyans

```
keyans \begin{keyans}[\key = val] \item \item[\langle custom \rangle] \item* \item*[\langle content \rangle] \end{keyans}
keyans* \begin{keyans*}[\key = val] \item \item[\langle custom \rangle] \item* \item*[\langle content \rangle] \end{keyans*}
```

The `keyans` is an “*enumerated list*” environment designed for “*multiple choice*” questions activated by the `save-ans` key. This environment can NOT be nested and must always be at the “*first level*” of the `enumext` environment, the commands `\item` and `\item[\langle custom \rangle]` work in the usual.

```
\begin{enumext}[save-ans=test]
  \item \langle item content \rangle
    \begin{keyans}[\key = val]
      \item \langle item content \rangle
      \item [\langle custom \rangle] \langle item content \rangle
      \item* \langle item content \rangle
      \item* [\langle content \rangle] \langle item content \rangle
    \end{keyans}
\end{enumext}
```

The `\keys` set in the optional argument of the environment are the same (almost) as those of the `enumext` environment and have higher precedence than those set by `\setenumext[\keys]{\key = val}`. If the optional argument is not passed or the `\keys` are not set by `\setenumext`, the default values will be the same as the second level of the `enumext` environment with the difference in the `\label` which will be set to `label=(\Alph*)`.

4.5.1 The `\item*` in `keyans`

```
\item* \item*
\item* [\langle content \rangle]
```

The `\item*` and `\item*[\langle content \rangle]` command store the current `\label` set by `label` key next to the `\content` (if it is present) in `\store name` set by `save-ans` key in the “*first level*” of the `enumext` environment.

The *starred version* ‘`*`’ cannot be separated by spaces ‘`␣`’ from the command, i.e. `\item*` and the optional argument does “*not support*” verbatim content. By design it is assumed that the *starred version* ‘`*`’ will only appear “*once*” within the environment.

🔗 The behavior of `\item*` in `keyans` environment is NOT the same as in the `enumext` environment.

Example

```
\begin{enumext}[save-ans=test,columns=2,show-ans]
  \item Text containing a question.
    \begin{keyans}[nosep]
      \item Choice
      \item* Correct choice
      \item Choice
      \item Choice
    \end{keyans}

  \item Text containing a question and image.
    \begin{keyans}[nosep,mini-env={0.4\linewidth}]
      \item Choice
      \item Choice
      \item Choice
      \item Choice
      \item*[\note] Correct choice
      \miniright
      \includegraphics[scale=0.25]{example-image-a}

      Some text
    \end{keyans}
\end{enumext}
```

1. Text containing a question.

(A) Choice

* (B) Correct choice

(C) Choice

(D) Choice
2. Text containing a question and image.

(A) Choice

(B) Choice

(C) Choice

(D) Choice

* (E) [note] Correct choice



4.6 The environment keyanspic

keyanspic

`\begin{keyanspic}[\langle number above, number below \rangle]\anspic{\langle drawing \rangle}\anspic*[\langle content \rangle]{\langle drawing \rangle}`

The `keyanspic` is a “fake enumerated list” environment that which uses the `\anspic` command instead of `\item`. It is activated by the `save-ans` key and has the same settings as the `keyans` environment. It is intended for placing “drawings” or “tabular” with an in-line or *above* and *below* layout. A representation of the output can be seen in the figure 6.




Figure 6: Representation of the `keyanspic` environment with optional argument `[3,2]` in `enumext`.

The optional argument determines the number drawings or tabular “above” and “below” within the environment. The vertical separation between “above” and “below” is controlled by the values set by `parsep` and `itemsep` keys passed to `keyans` environment. If the optional argument or the second part of it is omitted the drawings or tabular will be put on a single line.

4.6.1 The command \anspic

\anspic

`\anspic{\langle drawing or tabular \rangle}`
`\anspic*[\langle content \rangle]{\langle drawing or tabular \rangle}`


The `\anspic` command take three arguments, the *starred version* “*” store the current `\label` next to the `\content` (if it is present) in `\store name` set by `save-ans` key.

The *starred version* “*” cannot be separated by spaces “ ” from the command, i.e. `\anspic*` and the optional argument does “not support” verbatim content. By design it is assumed that the *starred version* “*” will only appear “once” within the environment.

Example

```
\begin{enumext}[save-ans=test,show-ans,nosep]
  \item Question with images.
  \begin{keyanspic}[3,2]
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-b}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic*[note]{\includegraphics[scale=0.15]{example-image-a}}
  \end{keyanspic}
\end{enumext}
```

1. Question with images.



4.7 Printing stored content

4.7.1 The command \getkeyans

`\getkeyans` `\getkeyans{<store name> : <position>}`

The command `\getkeyans` prints the “only stored content” in `<store name>` defined by `save-ans` key in the `<position>` returned by the `show-pos` key.

The “content” can only be accessed “after” it is stored, if the `<store name>` does not exist the command will return an error. The form taken by the argument `<store name> : <position>` is the same as that used to generate the internal “label and ref” system when `store-ref` key are active, so to refer to a stored “content”. For example `\getkeyans{test:4}` will return the “stored content” at position 4 of the environment in which the key `save-ans=test` was set.

4.7.2 The command \printkeyans

`\printkeyans` `\printkeyans[<keys>]{<store name>}`

The command `\printkeyans` prints “all stored content” in `{<store name>}` defined by `save-ans` key. The “content” can only be accessed “after” it is stored, if `<store name>` does not exist the command will return an error.

Internally it places the “stored content” inside the `enumext` environment with default values for `label` key are the same as those of the `enumext` environment along with the keys: `nosep`, `first=\small`, `font=\small` for all levels, except for the first one that adds the `columns=2` key.

The optional argument allows to handle the `<keys>` “on the first level” of the `enumext` environment encapsulated by the command. If need to pass options for nested levels use `\setenumext[<print> , <level>]{<store name>}`.

Example

```
\begin{enumext}[save-ans=sample,columns=2,show-pos,nosep,store-ref]
  \item Factor  $3x+3y+3z$ . \anskey{$3(x+y+z)}
  \item True False

  \begin{enumext}[nosep]
    \item \LaTeXe is cool? \anskey{Very True!}
  \end{enumext}

  \item Related to Linux

  \begin{enumext}[nosep]
    \item You use linux? \anskey{Yes}
    \item Rate the following package and class
      \begin{enumext}[nosep]
        \item \texttt{xsim} \anskey{very good}
        \item \texttt{exsheets} \anskey{obsolete}
      \end{enumext}
    \end{enumext}
  \end{enumext}
```

The answer to `\ref{sample:4}` is `\getkeyans{sample:4}` and the answers to all the worksheets are as follows:

```
\printkeyans{sample}
```

1. Factor $3x + 3y + 3z$.

[1] $3(x + y + z)$

2. True False

(a) \LaTeXe is cool?

[2] Very True!

3. Related to Linux

(a) You use linux?
- [3] Yes

(b) Rate the following package and class

i. `xsim`

[4] very good

ii. `exsheets`

[5] obsolete
- The answer to 3.(b).i is very good and the answers to all the worksheets are as follows:

1. (a) $3(x + y + z)$

(b) i. Very True!

(c) i. Yes

ii. A. very good

B. obsolete


5 Full examples

Here I will leave as an example some adaptations questions taken from [TeX-SX](#). The examples are attached to this documentation and can be extracted from your PDF viewer or from the command line by running:

```
$ pdfdetach -saveall enumext.pdf
```

and then you can use the excellent [arara](#)¹ tool to compile them.

Example 1

Adapted from the response given by Enrico Gregorio in [Squares for answer choice options and perfect alignment to mathematical answers](#) .

1. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

A

 36 km/h.

B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$ km/h.
2. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?

A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.

C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

D

 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$.
3. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

A

 36 km/h.

B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$ km/h.
4. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?

A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.

C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

D


 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$.

1. (a) B

(b) A
- (c) B

(d) A

Example 2

Adapted from the response given by Florent Rougon in [Multiple choice questions with proposed answers in random order — addition of automatic correction \(cross mark\)](#) .

1. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

A

 36 km/h.

☒ B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$ km/h.
2. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?

☒ A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.

C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

D

 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$.
3. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

A

 36 km/h.

☒ B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$ km/h.
4. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?

☒ A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.

C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

D

 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$.
1. (a) B

(b) A

(c) B

(d) A
- *


*

*

*

¹The cool TeX automation tool: <https://www.ctan.org/pkg/arara>

Example 3

A “simple multiple choice” test .

1. First type of questions
- A value

B correct

C value

D value
2. Second type of questions
- I. $2\alpha + 2\delta = 90^\circ$

II. $\alpha = \delta$

III. $\angle EDF = 45^\circ$

A I only

B II only

C I and II only
3. Third type of questions
- (1) $2\alpha + 2\delta = 90^\circ$

(2) $\angle EDF = 45^\circ$

A value

B value

C value
4. Question with image and label below:



A




D



B



C



E

5. Question with image on left side:
- A value

B value

C value

D correct

E value



Test keys

1. (a) B $x = 5$
- (b)
- (c) D
- (d)

- *

(e) C some note

*
- *


(f) B

*
- *

(g) D other note

*

Example 4

A “simple worksheet” using ducks :) .



Factor $x^2 - 2x + 1$



Factor $3x + 3y + 3z$

The following questions need to be cuaqtified :)



True False

- (a) $\alpha > \delta$
- (b) ~~ETX~~ze is cool?



Related to Linux

- (a) You use linux?
- (b) Usually uses the package manager?
- (c) Rate the following package and class
- i. `xsim-exam`

ii. `xsim`

iii. `exsheets`

The answer to 1 is $(x - 1)^2$ and the answer to 3.(a) is False.

1. (a) $(x - 1)^2$

(b) $3(x + y + z)$

(c) i. False

ii. Very True!

(d) i. Yes
- ii. Yes, dnf

iii. A. doesn't exist for now :(

B. very good

C. obsolete

Example 5

Adapted from the response given by Stephen in SAT like question format .

1

Which choice best describes what happens in the passage?

- A) One character argues with another character who intrudes on her home.
- B) One character receives a surprising request from another character.
- C) One character reminisces about choices she has made over the years.
- D) One character criticizes another character for pursuing an unexpected course of action.

2

Which choice best describes what happens in the passage?

- A) One character argues with another character who intrudes on her home.
- B) One character receives a surprising request from another character.
- C) One character reminisces about choices she has made over the years.
- D) One character criticizes another character for pursuing an unexpected course of action.

3

Which choice best describes what happens in the passage?

- A) One character argues with another character who intrudes on her home.
- B) One character receives a surprising request from another character.
- C) One character reminisces about choices she has made over the years.
- D) One character criticizes another character for pursuing an unexpected course of action.

4

Which choice best describes what happens in the passage?

- A) One character argues with another character who intrudes on her home.
- B) One character receives a surprising request from another character.
- C) One character reminisces about choices she has made over the years.
- D) One character criticizes another character for pursuing an unexpected course of action.

1. (a) A) (c) B)
(b) C) (d) D)

6 The way of non-enumerated lists

It is possible to use (or abuse) the `enumext` environment to mimic *non-enumerated* list environments such as `itemize` and `description`, clearly the `<keys>` to “store answers”, the `keyans` and `keyanspic` environments lose their sense and it is not the focus of the main of this package, but, why not to do it?. Here I leave as an example other uses of the `enumext` environment that can be helpful for specific purposes. The “trick” to generate these *fake environments* is set `label={}` or `label={\some}` and play with the `list-indent`, `list-offset`, `font` and `wrap-label` keys.

Fake itemize environment

Here we set the `label` key using the default settings in \LaTeX for the four levels `\textbullet`, `\textendash`, `\textasteriskcentered` and `\textperiodcentered` together with the `nosep` key to reduce the vertical spaces in the left side example and set the `label` key in *mathematical mode* for the right side as `\ast`, `\diamond`, `\circ` and `\star` for the four levels together with the `nosep` key

- First level item
 - Second level item
 - * Third level item
 - Fourth level item
 - First level item
- * First level item
 - ◇ Second level item
 - Third level item
 - ★ Fourth level item
 - * First level item

Fake description environment

Here we set `label={}` and `list-indent=2.5em`, `font=\bfseries`.

- SomeThing** A short one-line description.
This is an entry *without* a label.

Something A short *one-line* description text.

Something long A much *longer* description text may take more than one line or more than one paragraph.
Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

If we add `list-indent=0pt` you get *widest style*:

- SomeThing** A short one-line description.
This is an entry *without* a label.

Something A short *one-line* description text.

Something long A much *longer* description text may take more than one line or more than one paragraph. Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

- The small space at the beginning of the “*unlabeled entry*” corresponds to `\labelsep` and can be removed using `\hspace{-\labelsep}` at the beginning of the line.

Description indented by label

Here we set `label={}` and we will give a convenient value to `labelsep` and `labelwidth`, for example we can take as reference our *longest label* and pass it as value using:

```
\newlength{\descitemwd}
\settowidth{\descitemwd}{\textbf{Something long}}
```

and then use `labelsep=4pt, labelwidth=\descitemwd, font=\bfseries`.

Something A short one-line description.

This is an entry *without* a label.

Something A short one-line description.

Something long A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

The environment can be translated so that the *(labels)* are on the left margin calculating the value passed to the `list-offset` key, in this case it will be equal to the sum of the values set by the `labelwidth` and `labelsep` keys finally resulting as `list-offset={-\descitemwd - 4pt}`.

Something A short one-line description.

This is an entry *without* a label.

Something A short one-line description.

Something long A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

If we add `align=right` it will look like this:

Something A short one-line description.

This is an entry *without* a label.

Something A short one-line description.

Something long A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

- At this point we have used `list-offset={-\descitemwd - 4pt}` instead of `list-offset={-\labelwidth - \labelsep}`, this is because the parameters `\labelwidth` and `\labelsep` take the default values, as if we had not set `label`.

Description with multi-line labels

The `label` key does not accept *multiline material*, this is where the `wrap-label*` key comes into play. Unlike the `enumitem` package, the `align` key only supports three options, so what we will do is create a command in the style `\parleft` of `enumitem` that allows us to place *multiline labels* using `\parbox`.

```
\NewDocumentCommand \itembx { s +m }
{%
  \IfBooleanTF{#1}
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedright{#2}}}}%
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{#2}}}}%
}
```

Now we just need to set `wrap-label*={\itembx{#1}}`.

Something A short one-line description.

This is an entry *without* a label.

Something A short one-line description.

Something A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

long vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

>Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

SoMeThInG A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit,

LoNg vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

Final notes

The original implementation (if you can call it that) of the ideas that led to the creation of `enumext` were some macros using the `enumerate[4]` package for personal use created in early 2003, the code was quite questionable, but functional for these simple requirements.

With the great answers given by Christian Hupfer in [Create a fake label ref using list](#) and the answer given by David Carlisle in [Change the use of label ref by data save in an array \(list\)](#) I managed to create a more solid code than the original version, now using the `l3prop`[10] and `l3seq`[10] modules together with the `hyperref`[7] and `enumitem`[5] packages, which did the job, but with some limitations.

As time went by I took these limitations as a personal challenge which I called “*reinventing the wheel*”, since there were packages and classes that did more or less what I was looking for, but did not fit my simple requirements. This “*reinventing the wheel*” finally ended up becoming `enumext`.

Why list environments?

The answer is simple, first I love the beauty of its syntax and many of what I had already written used the `enumerate` environment or lists created using the `enumitem` package. In my mind I thought: how complicated could it be to write a package that looked like `enumitem`? It seemed simple enough, of course I didn’t have in mind the mess I was getting into working with `list` environments, `minipage` and adding support for the `multicol` and `hyperref` packages.

Of course, seeing the final result of the experiment “*reinventing the wheel*” I am quite satisfied.

Why not random questions and other utilities

The “*random*” type questions I love and hate them at the same time, although they simplify a lot the work when creating a multiple choice test, but you lose the beauty of typesetting a document with \LaTeX , that is to say the output does not always look as nice as it should, even if they are only alternatives these must follow a certain order when presented either numerical or presentation, that said handling that using *nested lists* is quite complicated so I do not classify to be implemented.

7 References

- [1] HIRSCHHORN, PHILIP. “Using the exam document class”. Available from CTAN, <https://www.ctan.org/pkg/exam>, 2023.
- [2] NIEDERBERGER, CLEMENS. “xsim – eXercise Sheets IMproved”. Available from CTAN, <https://www.ctan.org/pkg/xsim>, 2023.
- [3] MITTELBACH, FRANK. “An environment for multicolumn output”. Available from CTAN, <https://www.ctan.org/pkg/multicol>, 2024.
- [4] The \LaTeX Project. “enumerate – Enumerate with redefinable labels”. Available from CTAN, <https://www.ctan.org/pkg/enumerate>, 2024.
- [5] BEZOS, JAVIER. “Customizing lists with the enumitem package”. Available from CTAN, <https://www.ctan.org/pkg/enumitem>, 2019.
- [6] BERRY, KARL. “ \LaTeX 2_ε: An Unofficial Reference Manual”. Available from CTAN, <https://ctan.org/pkg/latex2e-help-texinfo>, 2024.
- [7] The \LaTeX Project. “Extensive support for hypertext in \LaTeX ”. Available from CTAN, <https://www.ctan.org/pkg/hyperref>, 2024.
- [8] BURNOL, JEAN-FRANÇOIS. “The footnotehyper package”. Available from CTAN, <https://www.ctan.org/pkg/footnotehyper>, 2021.
- [9] The \LaTeX Project. “The expl3 package”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2024.
- [10] The \LaTeX Project. “The \LaTeX 3 Interfaces”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2024.
- [11] The \LaTeX Project. “The xparse package”. Available from CTAN, <https://www.ctan.org/pkg/xparse>, 2024.
- [12] GUNDLACH, PATRICK. “The lua-visual-debug package”. Available from CTAN, <https://www.ctan.org/pkg/lua-visual-debug>, 2023.
- [13] LEMVIG, MOGENS. “The shortlst package”. Available from CTAN, <https://www.ctan.org/pkg/shortlst>, 1998.
- [14] NIEDERBERGER, CLEMENS. “tasks – Horizontally columned lists”. Available from CTAN, <https://www.ctan.org/pkg/tasks>, 2022.

8 Change history

v1.0 2024-05-06 – First public release.

9 Index of Documentation

The italic numbers denote the pages where the corresponding entry is described.

C

Document class:

article 1

book 1

exam 2

letter 1

report 1

\columnbreak 4

\columnsep 9

Commands provide by enumext:

\anskey 3, 9–11

\anspic* 3, 10, 12

\anspic 12

\getkeyans 3, 10, 13

\item* 3–6, 10, 11

\item 5, 6, 9–11

\miniright 3, 4, 9

\printkeyans 3, 5, 10, 13

\setenumext 3, 5, 6, 10, 11, 13

Counters defined by enumext:

enumXiii 3

enumXii 3

enumXiv 3

enumXi 3

enumXviii 3

enumXvii 3

enumXvi 3

enumXv 3

E

Environments provide by enumext:

enumext* 3, 4

enumext 3–5, 9–11, 13, 16

keyans* 3, 4

keyanspic 3, 6, 9, 10, 12, 16

keyans 3–7, 9–12, 16

Environments:

enumerate 1–3, 5, 18

list 3, 8, 18

minipage 2–4, 9, 18

multicols 2, 4, 9

I

\item 3, 4

\itemsep 8

K

Keys for environments provide by enumext:

above* 8

above 8

after 9

align 6, 17

before* 8

before 8

below* 8

below 8

check-ans 10

columns-sep 4, 9

columns 4, 8, 9

first 9

font 6

item-pos* 5

item-sym* 5

itemindent 8

itemsep 8, 12

labelsep 3, 5, 6, 8–10, 17

labelwidth 3, 5, 6, 8–10, 17

label 6, 9, 11, 13, 16, 17

list-indent 3, 8

list-offset 3, 8, 17

listparindent 8

mark-ans 10

mark-pos 10

mark-ref 10

mini-env 4, 8, 9

mini-sep 4, 9

no-store 10

noitemsep 8

nosep 8, 16

parsep 7, 8, 12

partopsep 7

ref 4, 6

resume 9

rightmargin 8

save-ans 4, 9–13

show-ans 10

show-length 6

show-pos 10, 13

start 9

store-ref 4, 6, 10, 13

topsep 7, 8

widest 6

wrap-ans 10

wrap-label* 6, 17

wrap-label 6

L

\label 4

Labels provide by enumext:

\Alph* 6, 11

\Roman* 6

\alph* 6

\arabic* 6

\roman* 6

\labelsep 3, 6

\labelwidth 3, 6

\linewidth 9

\listparindent 8

P

Packages:

enumerate 17

enumext 1–3, 12, 17, 18

enumitem 3, 4, 8, 17, 18

footnotehyper 4

hyperref 4, 10, 18

l3prop 1, 18

l3seq 1, 18

multicol 1, 4, 18

xsim 2

\parsep 7

\partopsep 7

©2024 by Pablo González L

19 / 113

R	\rightmargin 8
\raggedcolumns 4	T
\ref 4	\topsep 7

10 Implementation

The most recent publicly released version of `enumext` is available at CTAN: <https://www.ctan.org/pkg/enumext>. While general feedback via email is welcomed, specific bugs or feature requests should be reported through the issue tracker: <https://github.com/pablgonz/enumext/issues>.

- The documentation presented here is far from professional, it contains a lot of obvious information that to the eye of a T_EXpert are superfluous, but, after so many years developing this project is the only way to remember what does what.

10.1 General conventions

Variables containing `i`, `ii`, `iii` and `iv` are associated by level with the `enumext` environment, variables containing `v` are associated with the `keyans` environment, variables containing `vi` are associated with the `keyanspic` environment, variables containing `vii` are associated with the `enumext*` environment and variables containing `viii` are associated with the `keyans*` environment.

To simplify writing and documentation some variables and functions that are common to the different levels of the environments are described using a capital “X”.

The temporary function `__enumext_tmp:n` is used in different parts of the package code for variable creation or execution of other functions that are grouped into this one.

All variables and functions defined in this package are private and are NOT intended to work or be used by another package or module.

10.2 Initial set up

Start the DocStrip guards.

```
1 <*package>
```

Identify the internal prefix (L^AT_EX3 DocStrip convention) for l3doc class.

```
2 <@@=enumext>
```

10.3 Declaration of the package

First we will make sure we have a minimum (super updated) version of L^AT_EX to work correctly.

```
3 \NeedsTeXFormat{LaTeX2e}[2023-11-01]
```

Now declare the `enumext` package.

```
4 \ProvidesExplPackage
5   {enumext}
6   {2024-05-06}
7   {1.0}
8   {Enumerate exercise sheets}
```

Finally check if the `multicol` package is loaded, if not we load it.

```
9 \hook_gput_code:nnn {begindocument} {enumext}
10 {
11   \IfPackageLoadedTF { multicol }
12   {
13     \msg_info:nnn { enumext } { package-load } { multicol }
14   }
15   {
16     \msg_info:nnn { enumext } { package-not-load } { multicol }
17     \RequirePackage{multicol}[2023-03-30]
18   }
19 }
```

10.4 Definition of variables

Variables that do not appear in this section are created by means of `\keys_define:nn` or some function described below.

Integer variables will control the nesting levels of the environments and boolean variables will be used to determine if they are present (nested) in each other. The boolean variables `\g__enumext_starred_bool` and `\g__enumext_standar_bool` will be set to “true” when the `enumext` and `enumext*` environments are not nested with each other.

```
20 \int_new:N \__enumext_level_int
21 \int_new:N \__enumext_level_h_int
22 \int_new:N \__enumext_keyans_level_int
23 \int_new:N \__enumext_keyans_level_h_int
24 \int_new:N \__enumext_keyans_pic_level_int
25 \bool_new:N \__enumext_starred_bool
26 \bool_new:N \g__enumext_starred_bool
```

```

27 \bool_new:N \l__enumext_standar_bool
28 \bool_new:N \g__enumext_standar_bool
29 \bool_new:N \l__enumext_keyans_env_bool

```

(End of definition for `\l__enumext_level_int` and others.)

```

\l__enumext_counter_i_tl
\l__enumext_counter_ii_tl
\l__enumext_counter_iii_tl
\l__enumext_counter_iv_tl
\l__enumext_counter_v_tl
\l__enumext_counter_vi_tl
\l__enumext_counter_vii_tl
\l__enumext_counter_viii_tl

```

Variables to store the “*name of the counters*” `enumXi`, `enumXii`, `enumXiii` and `enumXiv` for `enumext` environment, `enumXv` for `keyans` environment and `enumXvi` for the `keyanspic` environment.

The counters `enumXvii` and `enumXviii` are used by `enumext*` and `keyans*` environments.

The initial values of these variables are set by the function `__enumext_define_counters:Nn` and then modified by the function `__enumext_label_style:Nnn` used by `label` key (§10.8).

```

30 \cs_set_protected:Npn \__enumext_tmp:n #1
31 {
32   \tl_new:c { l__enumext_counter_#1_tl }
33 }
34 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_counter_i_tl` and others.)

```

\l__enumext_resume_bool
\g__enumext_resume_int
\l__enumext_resume_vii_bool
\g__enumext_resume_vii_int
\g__enumext_item_symbol_tl

```

The boolean variable `\l__enumext_resume_bool` is used by `resume` key, the value from which the environment’s will start is stored in the integer variable `\g__enumext_resume_int` (§10.21). The global token list `\g__enumext_item_symbol_tl` is used by `item-sym*` key (§10.26).

```

35 \bool_new:N \l__enumext_resume_bool
36 \int_new:N \g__enumext_resume_int
37 \bool_new:N \l__enumext_resume_vii_bool
38 \int_new:N \g__enumext_resume_vii_int
39 \tl_new:N \g__enumext_item_symbol_tl

```

(End of definition for `\l__enumext_resume_bool` and others.)

```

\l__enumext_current_widest_dim
\g__enumext_counter_styles_tl
\g__enumext_widest_label_tl
\l__enumext_label_width_by_box

```

The variable `\l__enumext_current_widest_dim` stores the current label width, the variable `\g__enumext_counter_styles_tl` stores the default *⟨label style⟩* and the variable `\g__enumext_widest_label_tl` the label width. These variables are used by `widest` (§10.12) and `label` (§10.10) keys.

```

40 \dim_new:N \l__enumext_current_widest_dim
41 \tl_new:N \g__enumext_counter_styles_tl
42 \tl_new:N \g__enumext_widest_label_tl
43 \box_new:N \l__enumext_label_width_by_box

```

(End of definition for `\l__enumext_current_widest_dim` and others.)

```

\l__enumext_leftmargin_tmp_X_bool
\l__enumext_leftmargin_tmp_X_dim
\l__enumext_leftmargin_X_dim
\l__enumext_itemindent_X_dim

```

The boolean variable `\l__enumext_leftmargin_tmp_X_bool` and the dimensional variable `\l__enumext_leftmargin_tmp_X_dim` are used by the `list-indent` key (§10.14).

The variables `\l__enumext_leftmargin_X_dim` and `\l__enumext_itemindent_X_dim` are used (and set) by the function `__enumext_calc_hspace:NNNNNNNNNN` (§10.30) which determines the internal values for `\leftmargin` and `\itemindent`.

```

44 \cs_set_protected:Npn \__enumext_tmp:n #1
45 {
46   \bool_new:c { l__enumext_leftmargin_tmp_#1_bool }
47   \dim_new:c { l__enumext_leftmargin_tmp_#1_dim }
48   \dim_new:c { l__enumext_leftmargin_#1_dim }
49   \dim_new:c { l__enumext_itemindent_#1_dim }
50 }
51 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_leftmargin_tmp_X_bool` and others.)

```

\l__enumext_multicols_above_X_skip
\l__enumext_multicols_below_X_skip

```

Internal variables used by `columns` key §10.18).

```

52 \cs_set_protected:Npn \__enumext_tmp:n #1
53 {
54   \skip_new:c { l__enumext_multicols_above_#1_skip }
55   \skip_new:c { l__enumext_multicols_below_#1_skip }
56 }
57 \clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_multicols_above_X_skip` and `\l__enumext_multicols_below_X_skip`.)

```
\g__enumext_minipage_stat_int
\l__enumext_minipage_left_skip
\l__enumext_minipage_right_skip
\l__enumext_minipage_after_skip
\g__enumext_minipage_right_skip
\g__enumext_minipage_after_skip
\l__enumext_minipage_left_X_dim
\l__enumext_minipage_active_X_bool
```

Internal variables used by `\miniright` command (§10.19.4) and the keys `miniright`, `miniright*`, `mini-env` and `mini-sep` (§10.17, §10.19).

```
58 \int_new:N \g__enumext_minipage_stat_int
59 \skip_new:N \l__enumext_minipage_left_skip
60 \skip_new:N \l__enumext_minipage_right_skip
61 \skip_new:N \l__enumext_minipage_after_skip
62 \skip_new:N \g__enumext_minipage_right_skip
63 \skip_new:N \g__enumext_minipage_after_skip
64 \cs_set_protected:Npn \__enumext_tmp:n #1
65 {
66   \dim_new:c { \l__enumext_minipage_left_#1_dim }
67   \bool_new:c { \l__enumext_minipage_active_#1_bool }
68 }
69 \clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\g__enumext_minipage_stat_int` and others.)

```
\l__enumext_wrap_label_X_bool
\l__enumext_wrap_label_opt_X_bool
\l__enumext_start_X_int
\l__enumext_fake_item_indent_X_tl
\l__enumext_label_fill_left_X_tl
\l__enumext_label_fill_right_X_tl
\l__enumext_vspace_a_star_X_bool
\l__enumext_vspace_b_star_X_bool
```

The integer variable `\l__enumext_start_X_int` are used by the `start` key (§10.12), the token list `\l__enumext_fake_item_indent_X_tl` is used by `itemindent` key, the variables `\l__enumext_label_fill_left_X_tl` and `\l__enumext_label_fill_right_X_tl` are used by the `align` key (§10.10). The boolean vars `\l__enumext_vspace_a_star_X_bool`, `\l__enumext_vspace_b_star_X_bool` are used by `above`, `above*`, `below` and `below*` keys

```
70 \cs_set_protected:Npn \__enumext_tmp:n #1
71 {
72   \bool_new:c { \l__enumext_wrap_label_#1_bool }
73   \bool_new:c { \l__enumext_wrap_label_opt_#1_bool }
74   \int_new:c { \l__enumext_start_#1_int }
75   \tl_new:c { \l__enumext_fake_item_indent_#1_tl }
76   \tl_new:c { \l__enumext_label_fill_left_#1_tl }
77   \tl_new:c { \l__enumext_label_fill_right_#1_tl }
78   \bool_new:c { \l__enumext_vspace_a_star_#1_bool }
79   \bool_new:c { \l__enumext_vspace_b_star_#1_bool }
80 }
81 \clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\l__enumext_wrap_label_X_bool` and others.)

```
\l__enumext_store_active_bool
\l__enumext_store_name_tl
\g__enumext_store_name_tl
\l__enumext_store_anskey_arg_tl
\l__enumext_store_columns_join_int
\l__enumext_store_keyans_label_tl
\l__enumext_keyans_tmpa_tl
\l__enumext_keyans_tmpb_tl
\l__enumext_keyans_tmpa_dim
```

The boolean variable `\l__enumext_store_active_bool` setting by `save-ans` key (§10.21) activates all the mechanism related to `\anskey`, `keyans`, `keyans*` and `keyanspic`.

The variable `\l__enumext_store_name_tl` sets the name for the storage in *sequence* and *prop list*, the variable `\g__enumext_store_name_tl` is just a copy of the storage name used by the `check-ans` key (§10.21).

The variable `\l__enumext_store_anskey_arg_tl` stores the contents of `\anskey` (§10.24) and the variable `\l__enumext_store_keyans_label_tl` stores the contents of `\item*` (§10.28.2) for the `keyans` and `keyans*` environments and the contents of `\anspic*` (§10.34.1) for the `keyanspic` environment.

The variable `\l__enumext_keyans_tmpa_tl` is a temporary variable used by `keyans` and `keyanspic` at various points.

```
82 \bool_new:N \l__enumext_store_active_bool
83 \tl_new:N \l__enumext_store_name_tl
84 \tl_new:N \g__enumext_store_name_tl
85 \tl_new:N \l__enumext_store_anskey_arg_tl
86 \int_new:N \l__enumext_store_columns_join_int
87 \tl_new:N \l__enumext_store_keyans_label_tl
88 \tl_new:N \l__enumext_keyans_tmpa_tl
89 \tl_new:N \l__enumext_keyans_tmpb_tl
90 \dim_new:N \l__enumext_keyans_tmpa_dim
```

(End of definition for `\l__enumext_store_active_bool` and others.)

```
\l__enumext_setkey_tmpa_tl
\l__enumext_setkey_tmpb_tl
\l__enumext_setkey_tmpa_int
\l__enumext_setkey_tmpa_seq
\l__enumext_setkey_tmpb_seq
```

Internal variables used by the command `\setenumext` (§10.39).

```
91 \tl_new:N \l__enumext_setkey_tmpa_tl
92 \tl_new:N \l__enumext_setkey_tmpb_tl
93 \int_new:N \l__enumext_setkey_tmpa_int
94 \seq_new:N \l__enumext_setkey_tmpa_seq
95 \seq_new:N \l__enumext_setkey_tmpb_seq
```

(End of definition for `\l__enumext_setkey_tmpa_tl` and others.)

```
\l__enumext_store_opt_X_tl
\l__enumext_print_keyans_X_tl
\l__enumext_store_columns_X_bool
\l__enumext_store_columns_X_int
\l__enumext_store_columns_sep_X_bool
\l__enumext_store_columns_sep_X_dim
\l__enumext_store_upper_level_X_bool
```

Internal variables used by [$\langle key = val \rangle$] in `enumext` and `enumext*` environment, the command `\printkeyans` (§10.38) and the keys `columns*` and `columns-sep*`.

```
96 \cs_set_protected:Npn \l__enumext_tmp:n #1
97 {
98   \tl_new:c { \l__enumext_store_opt_#1_tl }
99   \tl_new:c { \l__enumext_print_keyans_#1_tl }
100  \bool_new:c { \l__enumext_store_columns_#1_bool }
101  \int_new:c { \l__enumext_store_columns_#1_int }
102  \bool_new:c { \l__enumext_store_columns_sep_#1_bool }
103  \dim_new:c { \l__enumext_store_columns_sep_#1_dim }
104  \bool_new:c { \l__enumext_store_upper_level_#1_bool }
105 }
106 \clist_map_inline:nn { i, ii, iii, iv, vii } { \l__enumext_tmp:n {#1} }
```

(End of definition for `\l__enumext_store_opt_X_tl` and others.)

```
\l__enumext_show_answer_bool
\l__enumext_show_position_bool
\l__enumext_mark_ref_sym_tl
\l__enumext_mark_answer_sym_tl
\l__enumext_mark_position_str
```

Internal variables for “storage system” mechanism used by `\anskey` (§10.24), `keyans` and `keyanspic` environments. These variables are used by `show-ans`, `show-pos`, `mark-ans`, `save-key` and `mark-ref` keys (§10.23).

```
107 \bool_new:N \l__enumext_show_answer_bool
108 \bool_new:N \l__enumext_show_position_bool
109 \tl_new:N \l__enumext_mark_ref_sym_tl
110 \tl_new:N \l__enumext_mark_answer_sym_tl
111 \str_new:N \l__enumext_mark_position_str
```

(End of definition for `\l__enumext_show_answer_bool` and others.)

```
\l__enumext_keyans_pic_body_seq
\l__enumext_keyans_pic_width_dim
\l__enumext_keyans_pic_above_int
\l__enumext_keyans_pic_below_int
\l__enumext_keyans_pic_above_skip
```

Internal variables used by `keyanspic` environment (§10.34.2).

```
112 \seq_new:N \l__enumext_keyans_pic_body_seq
113 \dim_new:N \l__enumext_keyans_pic_width_dim
114 \int_new:N \l__enumext_keyans_pic_above_int
115 \int_new:N \l__enumext_keyans_pic_below_int
116 \skip_new:N \l__enumext_keyans_pic_above_skip
```

(End of definition for `\l__enumext_keyans_pic_body_seq` and others.)

```
\l__enumext_store_ans_bool
\l__enumext_check_ans_bool
\g__enumext_check_ans_show_bool
\g__enumext_check_ans_show_h_bool
\g__enumext_check_ans_item_tl
\g__enumext_count_item_anskey_int
\g__enumext_count_item_number_int
```

Internal variables used by “check answer” mechanism (§10.22.1) controlled by the `check-ans` and `no-store` keys.

```
117 \bool_new:N \l__enumext_store_ans_bool
118 \bool_new:N \l__enumext_check_ans_bool
119 \bool_new:N \g__enumext_check_ans_show_bool
120 \bool_new:N \g__enumext_check_ans_show_h_bool
121 \tl_new:N \g__enumext_check_ans_item_tl
122 \int_new:N \g__enumext_count_item_anskey_int
123 \int_new:N \g__enumext_count_item_number_int
124 \int_new:N \g__enumext_standar_star_env_int
125 \int_new:N \g__enumext_starred_star_env_int
126 \int_new:N \g__enumext_starred_keyans_star_env_int
127 \int_new:N \g__enumext_standar_keyans_star_env_int
128 \int_new:N \g__enumext_standar_keyans_pic_star_env_int
```

(End of definition for `\l__enumext_store_ans_bool` and others.)

```
\l__enumext_hyperref_bool
\l__enumext_footnotes_key_bool
```

The boolean variable `\l__enumext_hyperref_bool` will determine if the `hyperref` package is present or load in memory (§10.7). The boolean variable `\l__enumext_footnotes_key_bool` determine if `hyperref` is load with `key hyperfootnotes=true`.

```
129 \bool_new:N \l__enumext_hyperref_bool
130 \bool_new:N \l__enumext_footnotes_key_bool
```

(End of definition for `\l__enumext_hyperref_bool` and `\l__enumext_footnotes_key_bool`.)

```
\l__enumext_newlabel_arg_one_tl
\l__enumext_newlabel_arg_two_tl
\l__enumext_store_write_aux_file_tl
\l__enumext_label_copy_X_tl
```

Internal variables are used when executing the `store-ref` key. The variables `\l__enumext_label_copy_X_tl` correspond to temporary copies of the labels defined by level on which operations will be performed.

The variables `\l__enumext_newlabel_arg_one_tl` and `\l__enumext_newlabel_arg_two_tl` will be used to form the arguments passed to the function `__enumext_newlabel:nn` and the variable `\l__enumext_store_write_aux_file_tl` will be in charge of executing the writing code in the `.aux` file.

```
131 \tl_new:N \l__enumext_newlabel_arg_one_tl
132 \tl_new:N \l__enumext_newlabel_arg_two_tl
```

```

133 \tl_new:N \l__enumext_store_write_aux_file_tl
134 \cs_set_protected:Npn \__enumext_tmp:n #1
135 {
136   \tl_new:c { l__enumext_label_copy_#1_tl }
137 }
138 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_newlabel_arg_one_tl` and others.)

`\g__enumext_footnote_int`

Internal variables used for redefinition of `\footnote`.

`\g__enumext_footnote_arg_seq`
`\g__enumext_footnote_int_seq`

```

139 \int_new:N \g__enumext_footnote_int
140 \seq_new:N \g__enumext_footnote_arg_seq
141 \seq_new:N \g__enumext_footnote_int_seq

```

(End of definition for `\g__enumext_footnote_int`, `\g__enumext_footnote_arg_seq`, and `\g__enumext_footnote_int_seq`.)

`\c__enumext_counter_style_tl`
`\l__enumext_ref_key_arg_tl`
`\l__enumext_ref_aux_tl`
`\l__enumext_the_counter_X_tl`
`\l__enumext_counter_style_for_ref_X_tl`

Internal variables used by `ref` key (§10.17, §10.18).

```

142 \tl_const:Nn \c__enumext_counter_style_tl
143 { { arabic } { roman } { Roman } { alph } { Alph } }
144 \tl_new:N \l__enumext_ref_key_arg_tl
145 \tl_new:N \l__enumext_ref_aux_tl
146 \cs_set_protected:Npn \__enumext_tmp:n #1
147 {
148   \tl_new:c { l__enumext_counter_style_for_ref_#1_tl }
149   \tl_new:c { l__enumext_the_counter_#1_tl }
150   \tl_set:ce { l__enumext_the_counter_#1_tl } { \exp_not:c { theenumX#1 } }
151 }
152 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\c__enumext_counter_style_tl` and others.)

`\l__enumext_item_starred_X_bool`
`\l__enumext_item_column_pos_X_int`
`\g__enumext_item_count_all_X_int`
`\l__enumext_joined_item_X_int`
`\l__enumext_joined_item_aux_X_int`
`\l__enumext_tmpa_X_int`
`\l__enumext_item_text_X_box`
`\l__enumext_joined_width_X_dim`
`\l__enumext_item_width_X_dim`
`\g__enumext_item_symbol_aux_X_tl`
`\l__enumext_align_label_X_str`
`\g__enumext_minipage_active_X_bool`
`\g__enumext_miniright_code_X_tl`
`\g__enumext_minipage_center_X_bool`
`\g__enumext_minipage_right_X_dim`
`\g__enumext_minipage_right_X_skip`

Internal variables used by `enumext*` and `keyans*` environments.

```

153 \cs_set_protected:Npn \__enumext_tmp:n #1
154 {
155   \bool_new:c { l__enumext_item_starred_#1_bool }
156   \int_new:c { l__enumext_item_column_pos_#1_int }
157   \int_new:c { g__enumext_item_count_all_#1_int }
158   \int_new:c { l__enumext_joined_item_#1_int }
159   \int_new:c { l__enumext_joined_item_aux_#1_int }
160   \int_new:c { l__enumext_tmpa_#1_int }
161   \box_new:c { l__enumext_item_text_#1_box }
162   \dim_new:c { l__enumext_joined_width_#1_dim }
163   \dim_new:c { l__enumext_item_width_#1_dim }
164   \tl_new:c { g__enumext_item_symbol_aux_#1_tl }
165   \str_new:c { l__enumext_align_label_#1_str }
166   \bool_new:c { g__enumext_minipage_active_#1_bool }
167   \tl_new:c { g__enumext_miniright_code_#1_tl }
168   \bool_new:c { g__enumext_minipage_center_#1_bool }
169   \dim_new:c { g__enumext_minipage_right_#1_dim }
170   \skip_new:c { g__enumext_minipage_right_#1_skip }
171 }
172 \clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_item_starred_X_bool` and others.)

`\c__enumext_all_envs_clist`

An internal `clist-var` variable to run with `__enumext_tmp:n`.

```

173 \clist_const:Nn \c__enumext_all_envs_clist
174 {
175   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv},
176   {keyans}{v}, {enumext*}{vii}, {keyans*}{viii}
177 }

```

(End of definition for `\c__enumext_all_envs_clist`.)

10.5 Some utility functions

`__enumext_at_begin_document:n`

A internal “hook” function used for copying plain `list` and `minipage` environments definition and `hyperref` detection.

```
178 \cs_new_protected:Npn \__enumext_at_begin_document:n #1
179 {
180   \hook_gput_code:nnn {begindocument} {enumext} { #1 }
181 }
```

(End of definition for `__enumext_at_begin_document:n`.)

`__enumext_after_env:nn`

A internal “hook” function for execute code `miniright` and `miniright*` keys outside the `enumext*` and `keyans*` environments and print `check-ans` outside the `enumext` and `enumext*` environments.

```
182 \cs_new_protected:Npn \__enumext_after_env:nn #1 #2
183 {
184   \hook_gput_code:nnn {env/#1/after} {enumext} {#2}
185 }
```

(End of definition for `__enumext_after_env:nn`.)

`__enumext_level:`

Function for check current level in `enumext`.

```
186 \cs_new:Nn \__enumext_level:
187 {
188   \int_to_roman:n { \__enumext_level_int }
189 }
```

(End of definition for `__enumext_level:.`)

`__enumext_if_is_int:nT`

`__enumext_if_is_int:nF`

`__enumext_if_is_int:nTF`

A conditional function to know if the variable we are passing is an integer used by `start` and `widest` keys. This function is taken directly from the answer given by Henri Menke in [How to test if an expl3 function argument is an integer expression?](#).

```
190 \prg_new_protected_conditional:Npnn \__enumext_if_is_int:n #1 { T, F, TF }
191 {
192   \regex_match:nnTF { ^[\+|-]?[\d]+$ } {#1} % $
193   { \prg_return_true: }
194   { \prg_return_false: }
195 }
```

(End of definition for `__enumext_if_is_int:nT`, `__enumext_if_is_int:nF`, and `__enumext_if_is_int:nTF`.)

`__enumext_show_length:nnn`

Internal function used by `show-length` key to show “all lengths” calculated and use in `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```
196 \cs_new:Npn \__enumext_show_length:nnn #1 #2 #3
197 {
198   * ~ #2
199   \prg_replicate:nn { 14 - \str_count:n {#2} } { ~ }
200   = ~ \use:c { #1_use:c } { \__enumext_#2_#3_#1 } \\
201 }
```

(End of definition for `__enumext_show_length:nnn`.)

`__enumext_zero_count_level:`

Internal function used by `check-ans` key.

```
202 \cs_set_protected:Nn \__enumext_zero_count_level:
203 {
204   \cs_set_protected:Npn \__enumext_tmp:n ##1
205   {
206     \int_gzero:c { g__enumext_count_level_##1_int }
207   }
208   \clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {##1} }
209 }
```

(End of definition for `__enumext_zero_count_level:.`)

10.6 Copying list and minipage environments

The `list` environment provided by \LaTeX has the following plain form:

```
\list{⟨arg one⟩}{⟨arg two⟩}
  \item[⟨opt⟩]
\endlist
```

As a precaution we copy them using `__enumext_at_begin_document:n` in case any package redefines the `list` environment or a related command.

```
\__enumext_start_list:nn
  \__enumext_stop_list:
  \__enumext_item_std:w
```

The functions `__enumext_start_list:nn`, `__enumext_stop_list:` and `__enumext_item_std:w` correspond to copies of `\list`, `\endlist` and `\item` from plain definition of `list` environment.

```
210 \__enumext_at_begin_document:n
211 {
212   \cs_new_eq:NN \__enumext_start_list:nn \list
213   \cs_new_eq:NN \__enumext_stop_list: \endlist
214   \cs_new_eq:NN \__enumext_item_std:w \item
215 }
```

(End of definition for `__enumext_start_list:nn`, `__enumext_stop_list:`, and `__enumext_item_std:w`.)

The `minipage` environment provided by \LaTeX has the following (simplified) plain form:

```
\minipage[⟨pos⟩][⟨height⟩][⟨inner-pos⟩]{⟨width⟩}
  ⟨internal implement⟩
\endminipage
```

As a precaution we copy them using `__enumext_at_begin_document:n` in case any package redefines the `minipage` environment or a related command.

```
\__enumext_minipage:w
  \__enumext_endminipage:
```

The functions `__enumext_minipage:w`, `__enumext_endminipage:` and correspond to copies of `\minipage`, `\endminipage` from plain definition of `minipage` environment.

```
216 \__enumext_at_begin_document:n
217 {
218   \cs_new_eq:NN \__enumext_minipage:w \minipage
219   \cs_new_eq:NN \__enumext_endminipage: \endminipage
220 }
```

(End of definition for `__enumext_minipage:w` and `__enumext_endminipage:.`)

10.7 Compatibility with hyperref and footnotehyper

First we define the necessary rules using “hooks” to determine if the `hyperref` package is loaded.

```
221 \hook_gput_code:nnn { begindocument } { enumext } { \__enumext_after_hyperref: }
222 \hook_gset_rule:nnnn { begindocument } { enumext } { after } { hyperref }
```

```
\__enumext_after_hyperref:
  \__enumext_hypertarget:nn
  \__enumext_phantomsection:
```

The function `__enumext_after_hyperref:` sets the state of the boolean variable `\l__enumext_hyperref_bool` to “true” if the package is loaded. At this point we will use the public macro `\IfHyperBoolean` to determine if the `hyperfootnotes=true` key is present, if so, we set the state of the boolean variable `__enumext_footnotes_key_bool` to “true”.

```
223 \cs_new_protected:Nn \__enumext_after_hyperref:
224 {
225   \IfPackageLoadedTF { hyperref }
226   {
227     \msg_info:nnn { enumext } { package-load } { hyperref }
228     \bool_set_true:N \l__enumext_hyperref_bool
229     \IfHyperBoolean{hyperfootnotes}
230     {
231       \typeout{hyperfootnotes=true}
232       \bool_set_true:N \l__enumext_footnotes_key_bool
233     }
234     { \typeout{hyperfootnotes=false} }
235   }
236   { }
```

If the state of the variable `\l__enumext_footnotes_key_bool` is true we will check if the package `footnotehyper` is loaded, in case it is not present, we will set the value of `\l__enumext_footnotes_key_bool` to false and we will redefine `\footnote`.

```
237 \bool_if:NT \l__enumext_footnotes_key_bool
238 {
239   \IfPackageLoadedTF { footnotehyper }
240   {
```

```

241         \msg_info:nnn { enumext } { package-load } { footnotehyper }
242     }
243     {
244         \typeout{No ~ footnotehyper ~ load}
245         \typeout{Load ~ and ~ use ~ \string\makesavenoteenv{enumext*}}
246         \bool_set_false:N \l__enumext_footnotes_key_bool
247     }
248 }

```

The functions `__enumext_hypertarget:nn` and `__enumext_phantomsection:` correspond to the internal copies of `\hypertarget` and `\phantomsection`. If the boolean variable `\l__enumext_hyperref_bool` is false the functions `__enumext_hypertarget:nn` and `__enumext_phantomsection:` will be disabled.

```

249     \bool_if:NTF \l__enumext_hyperref_bool
250     {
251         \cs_new_eq:NN \__enumext_hypertarget:nn \hypertarget
252         \cs_new_eq:NN \__enumext_phantomsection: \phantomsection
253     }
254     {
255         \cs_new_eq:NN \__enumext_hypertarget:nn \use_none:nn
256         \cs_new_eq:NN \__enumext_phantomsection: \prg_do_nothing:
257     }
258 }

```

(End of definition for `__enumext_after_hyperref:`, `__enumext_hypertarget:nn`, and `__enumext_phantomsection:`.)

`__enumext_newlabel:nn`

The function `__enumext_newlabel:nn` write the information to the `.aux` file when using the `store-ref` key. The arguments taken by the function are:

- #1: `\l__enumext_newlabel_arg_one_tl`
- #2: `\l__enumext_newlabel_arg_two_tl`

🔗 The trick here is to manage the number of arguments passed to `\newlabel{#1}{#2}` according to the presence of the `hyperref` package.

```

259 \cs_new_protected:Npn \__enumext_newlabel:nn #1 #2
260 {
261     \protected@write \@auxout { }
262     {
263         \token_to_str:N \newlabel {#1}
264         {
265             {#2}
266             \bool_if:NT \l__enumext_hyperref_bool
267             { { \thepage } {#2} {#1} }
268             { }
269         }
270     }
271     \__enumext_hypertarget:nn {#1} { }
272     \__enumext_phantomsection:
273 }

```

(End of definition for `__enumext_newlabel:nn`.)

10.8 Definition of counters

`__enumext_define_counters:Nn`

`__enumext_define_counters:cn`

To create the necessary “counters” we must first make sure that they are not already defined by the user or a package such as `enumitem`, otherwise a error will be returned and the package loading will be aborted.

The arguments taken by the function are:

- #1: A token list `\l__enumext_counter_X_tl` for “store” the counter’s name.
- #2: The counter’s name.

```

274 \cs_new_protected:Npn \__enumext_define_counters:Nn #1 #2
275 {
276     \cs_if_exist:cTF { c@ #2 }
277     { \msg_fatal:nnn { enumext } { counters } { #2 } }
278     {
279         \tl_set:Nn #1 { #2 }
280         \newcounter { #2 }
281     }
282 }

```

(End of definition for `__enumext_define_counters:Nn`.)

```

enumXi    The counters created here are enumXi, enumXii, enumXiii and enumXiv for enumext environment,
enumXii   enumXv for keyans environment, enumXvi for keyanspic environment, enumXvii for enumext* and
enumXiii  enumXviii for the keyans* environments.
enumXiv   283 \__enumext_define_counters:Nn \__enumext_counter_i_tl { enumXi }
enumXv    284 \__enumext_define_counters:Nn \__enumext_counter_ii_tl { enumXii }
enumXvi   285 \__enumext_define_counters:Nn \__enumext_counter_iii_tl { enumXiii }
enumXvii  286 \__enumext_define_counters:Nn \__enumext_counter_iv_tl { enumXiv }
enumXviii 287 \__enumext_define_counters:Nn \__enumext_counter_v_tl { enumXv }
          288 \__enumext_define_counters:Nn \__enumext_counter_vi_tl { enumXvi }
          289 \__enumext_define_counters:Nn \__enumext_counter_vii_tl { enumXvii }
          290 \__enumext_define_counters:Nn \__enumext_counter_viii_tl { enumXviii }

```

(End of definition for enumXi and others.)

10.9 Definition of labels

This part of the code is inspired by the `enumitem` package. The idea is to be able to access the counters using `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` to use them in the `label` key.

```
\__enumext_register_counter_style:Nn
```

These *counters* will be used as default *labels* if the `label` key is not used for the different levels of the `enumext` environment and the `keyans` environment, so it is necessary to get a default value for `labelwidth` from these *labels* at the same time.

```

291 \cs_new_protected:Npn \__enumext_register_counter_style:Nn #1 #2
292 {
293   \tl_const:cn { c__enumext_widest_ \cs_to_str:N #1 _tl } {#2}
294   \tl_gput_right:Nn \g__enumext_counter_styles_tl {#1}
295 }
296 \__enumext_register_counter_style:Nn \arabic { 0 }
297 \__enumext_register_counter_style:Nn \Alph { M }
298 \__enumext_register_counter_style:Nn \alph { m }
299 \__enumext_register_counter_style:Nn \Roman { VIII }
300 \__enumext_register_counter_style:Nn \roman { viii }

```

(End of definition for __enumext_register_counter_style:Nn.)

```

\__enumext_label_width_by_box:Nn
\__enumext_label_width_by_box:cv

```

The function `__enumext_label_width_by_box:Nn` set the default `\labelwidth` using a box width if no `labelwidth` key is passed.

```

301 \cs_new_protected:Npn \__enumext_label_width_by_box:Nn #1 #2
302 {
303   \hbox_set:Nn \l__enumext_label_width_by_box {#2}
304   \dim_set:Nn #1 { \box_wd:N \l__enumext_label_width_by_box }
305 }
306 \cs_generate_variant:Nn \__enumext_label_width_by_box:Nn { cv }

```

(End of definition for __enumext_label_width_by_box:Nn.)

```

\__enumext_label_style:Nnn
\__enumext_label_style:cvn

```

The function `__enumext_label_style:Nnn` is used by the `label` key to creates the variables containing the *label style* and will allow to use `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` as arguments. It loops through the defined counter styles in `\g__enumext_counter_styles_tl` (`\arabic`, `\alph`, `\Alph`, `\roman`, and `\Roman`) for example, looking for `\roman*` and replacing that by `\roman{<counter>}`, and doing the same for the `\g__enumext_widest_label_tl` to keep both in sync.

```

307 \cs_new_protected:Npn \__enumext_label_style:Nnn #1 #2 #3
308 {
309   \tl_clear_new:N #1
310   \tl_put_right:Ne #1 { \tl_trim_spaces:n {#3} }
311   \tl_gset_eq:NN \g__enumext_widest_label_tl #1
312   \tl_map_inline:Nn \g__enumext_counter_styles_tl
313   {
314     \tl_replace_all:Nne #1 { ##1* } { \exp_not:N ##1 {#2} }
315     \tl_greplace_all:Nne \g__enumext_widest_label_tl { ##1* }
316     { \tl_use:c { c__enumext_widest_ \cs_to_str:N ##1 _tl } }
317   }
318   \__enumext_label_width_by_box:Nn \l__enumext_current_widest_dim
319   { \tl_use:N \g__enumext_widest_label_tl }
320   \tl_set_eq:cN { the #2 } #1
321 }
322 \cs_generate_variant:Nn \__enumext_label_style:Nnn { cvn }

```

(End of definition for __enumext_label_style:Nnn.)

10.10 Setting keys associated with label

font Definition of keys `font`, `labelsep`, `labelwidth`, `wrap-label` and `wrap-label*` keys for `enumext` and `keyans` environments.

```

323 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
324 {
325   \keys_define:nn { enumext / #1 }
326   {
327     font .tl_set:c = { l__enumext_label_font_style_#2_tl },
328     font .value_required:n = true,
329     labelsep .dim_set:c = { l__enumext_labelsep_#2_dim },
330     labelsep .initial:n = {0.3333em},
331     labelsep .value_required:n = true,
332     labelwidth .dim_set:c = { l__enumext_labelwidth_#2_dim },
333     labelwidth .value_required:n = true,
334     wrap-label .cs_set_protected:cp = { __enumext_wrapper_label_#2:n } ##1,
335     wrap-label .initial:n = {##1},
336     wrap-label .value_required:n = true,
337     wrap-label* .code:n = {
338       \bool_set_true:c { l__enumext_wrap_label_opt_#2_bool }
339       \keys_set:nn { enumext / #1 } { wrap-label = {##1} }
340     },
341     wrap-label* .value_required:n = true,
342   }
343 }
344 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `font` and others.)

- In this point, the following are set `__enumext_wrapper_label_X:n` which will be used by `__enumext_make_label:` for the different levels of the `enumext` environment and is set to `__enumext_wrapper_label_v:n` which will be used by `__enumext_keyans_make_label:` for `keyans` and `keyanspic` environments.

`align` The `align` key is implemented differently for “starred” and “non starred” environments.

```

345 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
346 {
347   \keys_define:nn { enumext / #1 }
348   {
349     align .choice:,
350     align / left .code:n =
351       {
352         \tl_clear:c { l__enumext_label_fill_left_#2_tl }
353         \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
354       },
355     align / right .code:n =
356       {
357         \tl_set:cn { l__enumext_label_fill_left_#2_tl } { \hfill }
358         \tl_clear:c { l__enumext_label_fill_right_#2_tl }
359       },
360     align / center .code:n =
361       {
362         \tl_set:cn { l__enumext_label_fill_left_#2_tl } { \hfill }
363         \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
364       },
365     align .initial:n = left,
366     align .value_required:n = true,
367   }
368 }
369 \clist_map_inline:nn
370 {
371   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {keyans}{v}
372 }
373 { \__enumext_tmp:nn #1 }

```

Definition of `align` key for `enumext*` and `keyans*` environments.

```

374 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
375 {
376   \keys_define:nn { enumext / #1 }
377   {
378     align .choice:,
379     align / left .code:n = \str_set:cn { l__enumext_align_label_#2_str } { l },
380     align / right .code:n = \str_set:cn { l__enumext_align_label_#2_str } { r },

```

```

381         align / center .code:n = \str_set:cn { l__enumext_align_label_#2_str } { c },
382         align .initial:n = left,
383         align .value_required:n = true,
384     }
385 }
386 \clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { l__enumext_tmp:nn #1 }

```

(End of definition for `align`.)

10.11 Setting label and ref keys

`l__enumext_regex_label_ref_key:`

The internal function `l__enumext_regex_label_ref_key:` replace the `*` with the actual counter of the running level and is used by the `l__enumext_set_label_ref:n` function.

It loops through the defined counter styles in `l__enumext_counter_style_tl` and replace `*` by real command, for example, looking for `\arabic*` and replacing that by `\arabic{<counter>}` defined on the current level.

```

387 \cs_new_protected:Nn l__enumext_regex_label_ref_key:
388 {
389     \tl_map_inline:Nn l__enumext_counter_style_tl
390     {
391         \regex_replace_once:nnN { \c{##1}\* }
392         { \c{##1}\cB{\u{l__enumext_ref_aux_tl}\cE} } l__enumext_ref_key_arg_tl
393     }
394 }

```

(End of definition for `l__enumext_regex_label_ref_key:.`)

`l__enumext_set_label_ref:n`

The `l__enumext_set_label_ref:n` function controlled by the `ref` key is in charge of handling the customization of the reference system.

First we will set the variable `l__enumext_the_counter_X_tl` according to the command created for *each counter*, apply the `regex` function `l__enumext_regex_label_ref_key:` and then renew the command and save it in the variable `l__enumext_counter_style_for_ref_X_tl`.

```

395 \cs_new_protected:Npn l__enumext_set_label_ref:n #1
396 {
397     \tl_set:Nn l__enumext_ref_key_arg_tl {#1}
398     \tl_set_eq:Nc l__enumext_ref_aux_tl { l__enumext_counter_ l__enumext_level: _tl }
399     l__enumext_regex_label_ref_key:
400     \tl_set_eq:Nc l__enumext_ref_aux_tl { l__enumext_the_counter_ l__enumext_level: _tl }
401     \tl_put_right:ce { l__enumext_counter_style_for_ref_ l__enumext_level: _tl }
402     {
403         \exp_not:N \renewcommand { \exp_not:V l__enumext_ref_aux_tl }
404         { \exp_not:V l__enumext_ref_key_arg_tl }
405     }
406 }

```

(End of definition for `l__enumext_set_label_ref:n`.)

`l__enumext_use_key_ref:`

Finally the function `l__enumext_use_key_ref:` will execute the modification for the reference system in the second argument of the environment definition `enumext`.

```

407 \cs_new_protected:Nn l__enumext_use_key_ref:
408 {
409     \tl_if_empty:cF { l__enumext_counter_style_for_ref_ l__enumext_level: _tl }
410     {
411         \tl_use:c { l__enumext_counter_style_for_ref_ l__enumext_level: _tl }
412     }
413 }

```

(End of definition for `l__enumext_use_key_ref:.`)

For `enumext*` and `keyans*` environments the situation is a bit different since `hyperref` interferes here (I am not clear why), so we will define a new function to execute the task.

To handle that we will look at the nesting level of the starred environments, later I will run the constraint functions to make everything OK.

`l__enumext_set_label_ref_h:n`

The `l__enumext_set_label_ref_h:n` function controlled by the `ref` key is in charge of handling the customization of the reference system.

First we will set the variable `l__enumext_the_counter_X_tl` according to the command created for *each counter*, apply the `regex` function `l__enumext_regex_label_ref_key:` and then renew the command and save it in the variable `l__enumext_counter_style_for_ref_X_tl`.

```

414 \cs_new_protected:Npn l__enumext_set_label_ref_h:n #1
415 {

```

```

416 \tl_set:Nn \l__enumext_ref_key_arg_tl {#1}
417 \int_compare:nNnTF { \l__enumext_level_h_int } = { 1 }
418 {
419   \tl_set_eq:NN \l__enumext_ref_aux_tl \l__enumext_counter_vii_tl
420   \__enumext_regex_label_ref_key:
421   \tl_set_eq:NN \l__enumext_ref_aux_tl \l__enumext_the_counter_vii_tl
422   \tl_put_right:Ne \l__enumext_counter_style_for_ref_vii_tl
423   {
424     \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_aux_tl }
425     { \exp_not:V \l__enumext_ref_key_arg_tl }
426   }
427 }
428 {
429   \tl_set_eq:NN \l__enumext_ref_aux_tl \l__enumext_counter_viii_tl
430   \__enumext_regex_label_ref_key:
431   \tl_set_eq:NN \l__enumext_ref_aux_tl \l__enumext_the_counter_viii_tl
432   \tl_put_right:Ne \l__enumext_counter_style_for_ref_viii_tl
433   {
434     \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_aux_tl }
435     { \exp_not:V \l__enumext_ref_key_arg_tl }
436   }
437 }
438 }

```

(End of definition for `__enumext_set_label_ref_h:n`.)

`__enumext_use_key_ref_h:` Finally the function `__enumext_use_key_ref_h:` will execute the modification for the reference system in the second argument of the environment definition `enumext*` and `keyans*`.

```

439 \cs_new_protected:Nn \__enumext_use_key_ref_h:
440 {
441   \int_compare:nNnTF { \l__enumext_level_h_int } = { 1 }
442   {
443     \tl_if_empty:NF \l__enumext_counter_style_for_ref_vii_tl
444     {
445       \tl_use:N \l__enumext_counter_style_for_ref_vii_tl
446     }
447   }
448   {
449     \tl_if_empty:NF \l__enumext_counter_style_for_ref_viii_tl
450     {
451       \tl_use:N \l__enumext_counter_style_for_ref_viii_tl
452     }
453   }
454 }

```

(End of definition for `__enumext_use_key_ref_h:`.)

10.11.1 Define and set label key for enumext environment

label Here we set the default `<labels>` of the four levels of `enumext` environment, along with the default value for `labelwidth` key.

```

\l__enumext_label_i_tl 455 \cs_set_protected:Npn \__enumext_tmp:nnn #1 #2 #3
\l__enumext_label_ii_tl 456 {
\l__enumext_label_iii_tl 457   \keys_define:nn { enumext / #1 }
\l__enumext_label_iv_tl 458   {
459     label .code:n = {
460       \__enumext_label_style:cnv { l__enumext_label_#2_tl }
461       { l__enumext_counter_#2_tl } {##1}
462       \dim_set_eq:cn { l__enumext_labelwidth_#2_dim }
463       \l__enumext_current_widest_dim
464     },
465     label .initial:n = #3,
466     label .value_required:n = true,
467     ref .code:n = \__enumext_set_label_ref:n {##1},
468     ref .value_required:n = true,
469   }
470 }
471 \__enumext_tmp:nnn { level-1 } { i } { \arabic*. }
472 \__enumext_tmp:nnn { level-2 } { ii } { (\alph*) }
473 \__enumext_tmp:nnn { level-3 } { iii } { \roman*. }
474 \__enumext_tmp:nnn { level-4 } { iv } { \Alph*. }

```

(End of definition for `label` and others.)

10.11.2 Define and set label key for enumext* and keyans* environments

label Here we set the default $\langle label \rangle$ for `enumext*` and `keyans*` environments, along with the default value
 ref for `labelwidth` key.

```

\l__enumext_label_vii_tl 475 \cs_set_protected:Npn \__enumext_tmp:nnn #1 #2 #3
\l__enumext_label_viii_tl 476 {
477   \keys_define:nn { enumext / #1 }
478   {
479     label .code:n = {
480       \__enumext_label_style:cvn { \l__enumext_label_#2_tl }
481       { \l__enumext_counter_#2_tl } {##1}
482       \dim_set_eq:cN { \l__enumext_labelwidth_#2_dim }
483       \l__enumext_current_widest_dim
484     },
485     label .initial:n = #3,
486     label .value_required:n = true,
487     ref .code:n = \__enumext_set_label_ref_h:n {##1},
488     ref .value_required:n = true,
489   }
490 }
491 \__enumext_tmp:nnn { enumext* } { vii } { \arabic*.}
492 \__enumext_tmp:nnn { keyans* } { viii } { (\Alph*) }
```

(End of definition for `label` and others.)

10.11.3 Define and set label key for keyans and keyanspic environment

label Here we set the default $\langle label \rangle$ for `keyans` and `keyanspic` environment, along with the default value for
 $\l__enumext_label_v_tl$ `labelwidth`. The `keyanspic` environment use the same $\langle label \rangle$ as the `keyans` environment.
 $\l__enumext_label_vii_tl$ Define and set `label` key for `keyans` environment.

```

493 \keys_define:nn { enumext / keyans }
494 {
495   label .code:n = {
496     \__enumext_label_style:cvn { \l__enumext_label_v_tl }
497     { \l__enumext_counter_v_tl } {##1}
498     \dim_set_eq:cN { \l__enumext_labelwidth_v_dim }
499     \l__enumext_current_widest_dim
500     \__enumext_label_style:cvn { \l__enumext_label_vii_tl }
501     { \l__enumext_counter_vii_tl } {##1}
502     \dim_set_eq:cN { \l__enumext_labelwidth_v_dim }
503     \l__enumext_current_widest_dim
504   },
505   label .initial:n = (\Alph*),
506   label .value_required:n = true,
507 }
```

(End of definition for `label`, $\l__enumext_label_v_tl$, and $\l__enumext_label_vii_tl$.)

10.12 Setting start and widest keys

$\l__enumext_start_from:NNn$ The function `__enumext_start_from:NNn` used by the `start` key take three arguments:

$\l__enumext_start_from:ccn$ #1: $\l__enumext_label_X_tl$
 #2: $\l__enumext_start_X_int$
 #3: $\langle integer \text{ or } string \rangle$

The first argument of this function are the “*counter style*” set by `label` key, the second argument is returned by the function, the third argument can be an $\langle integer \rangle$ or $\langle string \rangle$ of the form `\Alph`, `\alph`, `\Roman` or `\roman`. This effectively allows `start=A` or `start=1` to be used.

```

508 \cs_new_protected:Npn \__enumext_start_from:NNn #1 #2 #3
509 {
510   \__enumext_if_is_int:nTF { #3 }
511   {
512     \int_set:Nn #2 {##3}
513   }
514   {
515     \regex_match:nVT { \c{Alph} | \c{alph} } {##1}
516     { \int_set:Nn #2 { \int_from_alph:n {##3} } }
517     \regex_match:nVT { \c{Roman} | \c{roman} } {##1}
518     { \int_set:Nn #2 { \int_from_roman:n {##3} } }
519   }
520 }
521 \cs_generate_variant:Nn \__enumext_start_from:NNn { ccn }
```

(End of definition for `__enumext_start_from:NNn`.)

`__enumext_widest_from:nNNn`
`__enumext_widest_from:nccn`

The function `__enumext_widest_from:nNNn` used by the `widest` key take four arguments:

- #1: The counter associated with the environment level
- #2: `\l__enumext_label_X_tl`
- #3: `\l__enumext_labelwidth_X_dim`
- #4: $\langle integer \text{ or } string \rangle$

The second and third arguments of this function are the values set by `label` and `labelwidth` keys, the four argument can be an $\langle integer \rangle$ or $\langle string \rangle$ of the form `\Alph`, `\alph`, `\Roman` or `\roman`. The value of the four argument is set temporarily for the identified counter in this point (level), then the value is expanded into a “box” and the “width” of the “box” is returned.

```

522 \cs_new_protected:Npn \__enumext_widest_from:nNNn #1 #2 #3 #4
523 {
524   \__enumext_if_is_int:nTF {#4}
525   {
526     \setcounter{enumX#1} { #4 }
527   }
528   {
529     \regex_match:nVT { \c{Alph} | \c{alph} } {#2}
530     { \setcounter{enumX#1} { \int_from_alph:n {#4} } }
531     \regex_match:nVT { \c{Roman} | \c{roman} } {#2}
532     { \setcounter{enumX#1} { \int_from_roman:n {#4} } }
533   }
534   \__enumext_label_width_by_box:cv
535   { \l__enumext_labelwidth_#1_dim } { \l__enumext_label_#1_tl }
536 }
537 \cs_generate_variant:Nn \__enumext_widest_from:nNNn { nccn }

```

(End of definition for `__enumext_widest_from:nNNn`.)

`start`
`widest`

Now define and set `start` and `widest` keys for `enumext` and `keyans` environments.

`\l__enumext_start_X_int`

```

538 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
539 {
540   \keys_define:nn { enumext / #1 }
541   {
542     start .code:n = {
543       \__enumext_start_from:ccn
544       { \l__enumext_label_#2_tl }
545       { \l__enumext_start_#2_int } {##1}
546     },
547     start .initial:n = 1,
548     widest .code:n = {
549       \__enumext_widest_from:nccn {#2}
550       { \l__enumext_label_#2_tl }
551       { \l__enumext_labelwidth_#2_dim } {##1}
552     },
553     widest .value_required:n = true,
554     start .value_required:n = true,
555   }
556 }
557 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `start`, `widest`, and `\l__enumext_start_X_int`.)

10.13 Setting keys for vertical spaces

`topsep`
`partopsep`
`parsep`
`noitemsep`
`nosep`

Define and set `topsep`, `partopsep`, `parsep`, `itemsep`, `noitemsep` and `nosep` keys for `enumext` and `keyans` environments.

```

558 \cs_set_protected:Npn \__enumext_tmp:nnnnn #1 #2 #3 #4 #5 #6
559 {
560   \keys_define:nn { enumext / #1 }
561   {
562     topsep .skip_set:c = { \l__enumext_topsep_#2_skip },
563     topsep .initial:n = {#3},
564     topsep .value_required:n = true,
565     partopsep .skip_set:c = { \l__enumext_partopsep_#2_skip },
566     partopsep .initial:n = {#4},
567     partopsep .value_required:n = true,
568     parsep .skip_set:c = { \l__enumext_parsep_#2_skip },
569     parsep .initial:n = {#5},

```

```

570     parsep      .value_required:n = true,
571     itemsep     .skip_set:c = { l__enumext_itemsep_#2_skip },
572     itemsep     .initial:n = {#6},
573     itemsep     .value_required:n = true,
574     noitemsep   .meta:n = { itemsep = 0pt, parsep = 0pt },
575     noitemsep   .value_forbidden:n = true,
576     nosepe     .meta:n = {
577         itemsep = 0pt, parsep= 0pt,
578         topsep = 0pt, partopsep = 0pt,
579     },
580     nosepe     .value_forbidden:n = true,
581 }
582 }

```

Now we set the values based on standard `article` class in 10pt.

```

583 \__enumext_tmp:nnnnnn { level-1 } { i } { 8.0pt plus 2.0pt minus 4.0pt }
584 { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
585 { 4.0pt plus 2.0pt minus 1.0pt }
586 \__enumext_tmp:nnnnnn { level-2 } { ii } { 4.0pt plus 2.0pt minus 1.0pt }
587 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
588 { 2.0pt plus 1.0pt minus 1.0pt }
589 \__enumext_tmp:nnnnnn { level-3 } { iii } { 2.0pt plus 1.0pt minus 1.0pt }
590 { 1.0pt minus 1.0pt } { 0pt } { 2.0pt plus 1.0pt minus 1.0pt }
591 \__enumext_tmp:nnnnnn { level-4 } { iv } { 2.0pt plus 1.0pt minus 1.0pt }
592 { 1.0pt minus 1.0pt } { 0pt } { 2.0pt plus 1.0pt minus 1.0pt }
593 \__enumext_tmp:nnnnnn { keyans } { v } { 4.0pt plus 2.0pt minus 1.0pt }
594 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
595 { 2.0pt plus 1.0pt minus 1.0pt }
596 \__enumext_tmp:nnnnnn { enumext* } { vii } { 8.0pt plus 2.0pt minus 4.0pt }
597 { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
598 { 4.0pt plus 2.0pt minus 1.0pt }
599 \__enumext_tmp:nnnnnn { keyans* } { viii } { 4.0pt plus 2.0pt minus 1.0pt }
600 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
601 { 2.0pt plus 1.0pt minus 1.0pt }

```

(End of definition for `topsep` and others.)

10.14 Setting keys for horizontal spaces

Define and set `itemindent`, `rightmargin`, `listparindent`, `list-offset` and `list-indent` keys for `enumext` and `keyans` environments.

```

602 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
603 {
604     \keys_define:nn { enumext / #1 }
605     {
606         itemindent .dim_set:c = { l__enumext_fake_item_indent_#2_dim },
607         itemindent .value_required:n = true,
608         rightmargin .dim_set:c = { l__enumext_rightmargin_#2_dim },
609         rightmargin .value_required:n = true,
610         listparindent .dim_set:c = { l__enumext_listparindent_#2_dim },
611         listparindent .value_required:n = true,
612         list-offset .dim_set:c = { l__enumext_listoffset_#2_dim },
613         list-offset .value_required:n = true,
614         list-indent .code:n =
615             \bool_set_true:c { l__enumext_leftmargin_tmp_#2_bool }
616             \dim_set:cn { l__enumext_leftmargin_tmp_#2_dim } {##1},
617         list-indent .value_required:n = true,
618     }
619 }
620 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `itemindent` and others.)

For `enumext*` and `keyans*` environments the situation is a bit different, the `list-indent` key behaves like the `list-offset` key.

```

621 \cs_set_protected:Npn \__enumext_tmp:n #1
622 {
623     \keys_define:nn { enumext / #1 } { list-indent .initial:n = 0pt, }
624 }
625 \clist_map_inline:nn { enumext*, keyans* } { \__enumext_tmp:n {#1} }

```

10.14.1 Functions for setting the fake itemindent

The `itemindent` key does not set the value of `\itemindent`, it only sets the value of the *horizontal space* applied using `\skip_horizontal:N`. We will store this value in the variable and only apply it when it is greater than `\opt`. Here I will need to place `\mode_leave_vertical:` and the plain TeX macro `\ignorespaces` to avoid unwanted extra space when using the `itemindent` key.

```

626 \cs_set_protected:Nn \__enumext_fake_item:
627 {
628   \dim_compare:nNnT
629     { \dim_use:c { l__enumext_fake_item_indent_ \__enumext_level: _dim } }
630     >
631     { \c_zero_dim }
632   {
633     \tl_set:ce { l__enumext_fake_item_indent_ \__enumext_level: _tl }
634     {
635       \exp_not:N \mode_leave_vertical:
636       \exp_not:n { \skip_horizontal:n }
637       { \dim_use:c { l__enumext_fake_item_indent_ \__enumext_level: _dim } }
638       \ignorespaces
639     }
640   }
641 }
642 \cs_set_protected:Nn \__enumext_keyans_fake_item:
643 {
644   \dim_compare:nNnT
645     { \l__enumext_fake_item_indent_v_dim } > { \c_zero_dim }
646     {
647       \tl_set:Nc \l__enumext_fake_item_indent_v_tl
648       {
649         \exp_not:N \mode_leave_vertical:
650         \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_v_dim
651       }
652     }
653 }
654 \cs_set_protected:Nn \__enumext_fake_item_vii:
655 {
656   \dim_compare:nNnT
657     { \l__enumext_fake_item_indent_vii_dim } > { \c_zero_dim }
658     {
659       \tl_set:Nc \l__enumext_fake_item_indent_vii_tl
660       {
661         \exp_not:N \mode_leave_vertical:
662         \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_vii_dim
663       }
664     }
665 }
666 \cs_set_protected:Nn \__enumext_fake_item_viii:
667 {
668   \dim_compare:nNnT
669     { \l__enumext_fake_item_indent_viii_dim } > { \c_zero_dim }
670     {
671       \tl_set:Nc \l__enumext_fake_item_indent_viii_tl
672       {
673         \exp_not:N \mode_leave_vertical:
674         \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_viii_dim
675       }
676     }
677 }

```

(End of definition for `__enumext_fake_item:` and others.)

10.15 Setting show-length key

show-length

Define and set `show-length` key for `enumext`, `enumext*`, `keyans` and `keyans*` environments. The function sets the boolean variable `\l__enumext_show_length_X_bool` used in the definition of all environments to “true” and calls the function `__enumext_show_length:nnn` which prints all the values of the “vertical” and “horizontal” parameters calculated and used.

```

678 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
679 {
680   \keys_define:nn { enumext / #1 }
681   {
682     show-length .bool_set:c = { l__enumext_show_length_#2_bool },

```

```

683         show-length .initial:n = false,
684     }
685 }
686 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `show-length`.)

10.16 Setting before, after and first keys

Define and set `before`, `before*`, `after` and `first` keys for `enumext` and `keyans` environments.

```

before* 687 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
after    688 {
first    689     \keys_define:nn { enumext / #1 }
        690     {
        691         before .tl_set:c = { l__enumext_before_no_starred_key_#2_tl },
        692         before .value_required:n = true,
        693         before* .tl_set:c = { l__enumext_before_starred_key_#2_tl },
        694         before* .value_required:n = true,
        695         after .tl_set:c = { l__enumext_after_stop_list_#2_tl },
        696         after .value_required:n = true,
        697         first .tl_set:c = { l__enumext_after_list_args_#2_tl },
        698         first .value_required:n = true,
        699     }
        700 }
        701 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `before` and others.)

10.16.1 Functions for before, after and first keys in enumext

The function `__enumext_before_args_exec:` executes the `{⟨code⟩}` set by the `before*` key “before” the `enumext` environment is started. The `{⟨code⟩}` is executed “without” knowing any definition of the *second argument* of the list.

```

__enumext_before_args_exec:
__enumext_before_keys_exec:
__enumext_after_stop_list:
__enumext_after_args_exec:
702 \cs_new_protected:Nn \__enumext_before_args_exec:
703 {
704     \tl_use:c { l__enumext_before_starred_key_ \__enumext_level: _tl }
705 }

```

The function `__enumext_before_keys_exec:` executes the `{⟨code⟩}` set by the `before` key “before” the `enumext` environment is started in *second argument* of the list. The `{⟨code⟩}` is executed “knowing” all definition and values provides by `⟨keys⟩`.

```

706 \cs_new_protected:Nn \__enumext_before_keys_exec:
707 {
708     \tl_use:c { l__enumext_before_no_starred_key_ \__enumext_level: _tl }
709 }

```

The function `__enumext_after_stop_list:` executes the `{⟨code⟩}` set by the `after` key “after” the `enumext` environment has finished.

```

710 \cs_new_protected:Nn \__enumext_after_stop_list:
711 {
712     \tl_use:c { l__enumext_after_stop_list_ \__enumext_level: _tl }
713 }

```

The function `__enumext_after_args_exec:` executes the `{⟨code⟩}` set by the `first` key after the end of the second argument of the list defining the `enumext` environment, just before the first occurrence of `\item`.

```

714 \cs_new_protected:Nn \__enumext_after_args_exec:
715 {
716     \tl_use:c { l__enumext_after_list_args_ \__enumext_level: _tl }
717 }

```

(End of definition for `__enumext_before_args_exec:` and others.)

10.16.2 Functions for before, after and first keys in keyans

The function `__enumext_before_args_exec_v:` executes the `{⟨code⟩}` set by the `before*` key “before” the `keyans` environment is started. The `{⟨code⟩}` is executed “without” knowing any definition of the `{⟨arg two⟩}` of the list.

```

__enumext_before_args_exec_v:
__enumext_before_keys_exec_v:
__enumext_after_stop_list_v:
__enumext_after_args_exec_v:
718 \cs_new_protected:Nn \__enumext_before_args_exec_v:
719 {
720     \tl_use:N \l__enumext_before_starred_key_v_tl
721 }

```

The function `__enumext_before_keys_exec_v`: executes the `{⟨code⟩}` set by the `before` key “before” the `keyans` environment is started in `{⟨arg two⟩}` of the list. The `{⟨code⟩}` is executed “knowing” all definition and values provides by `⟨keys⟩`.

```

722 \cs_new_protected:Nn \__enumext_before_keys_exec_v:
723 {
724   \tl_use:N \l__enumext_before_no_starred_key_v_tl
725 }

```

The function `__enumext_after_stop_list_v`: executes the `{⟨code⟩}` set by the `after` key “after” the `keyans` environment has finished.

```

726 \cs_new_protected:Nn \__enumext_after_stop_list_v:
727 {
728   \tl_use:N \l__enumext_after_stop_list_v_tl
729 }

```

The function `__enumext_after_args_exec_v`: executes the `{⟨code⟩}` set by the `first` key after the end of `{⟨arg two⟩}` of the list defining the `keyans` environment, just before the first occurrence of `\item`.

```

730 \cs_new_protected:Nn \__enumext_after_args_exec_v:
731 {
732   \tl_use:N \l__enumext_after_list_args_v_tl
733 }

```

(End of definition for `__enumext_before_args_exec_v`: and others.)

10.16.3 Functions for before, after and first keys in `enumext*` and `keyans*`

```

\__enumext_before_args_exec_vii:
\__enumext_before_keys_exec_vii
\__enumext_after_stop_list_vii:
\__enumext_after_args_exec_vii:

```

The function `__enumext_before_args_exec_v`: executes the `{⟨code⟩}` set by the `before*` key “before” the `keyans` environment is started. The `{⟨code⟩}` is executed “without” knowing any definition of the `{⟨arg two⟩}` of the list.

```

734 \cs_new_protected:Nn \__enumext_before_args_exec_vii:
735 {
736   \tl_use:N \l__enumext_before_starred_key_vii_tl
737 }
738 \cs_new_protected:Nn \__enumext_before_args_exec_viii:
739 {
740   \tl_use:N \l__enumext_before_starred_key_viii_tl
741 }

```

The functions `__enumext_before_keys_exec_vii:` and `__enumext_before_keys_exec_viii:` executes the `{⟨code⟩}` set by the `before` key “before” in `enumext*` and `keyans*` environments is started in `{⟨arg two⟩}` of the list. The `{⟨code⟩}` is executed “knowing” all definition and values provides by `⟨keys⟩`.

```

742 \cs_new_protected:Nn \__enumext_before_keys_exec_vii:
743 {
744   \tl_use:N \l__enumext_before_no_starred_key_vii_tl
745 }
746 \cs_new_protected:Nn \__enumext_before_keys_exec_viii:
747 {
748   \tl_use:N \l__enumext_before_no_starred_key_viii_tl
749 }

```

The function `__enumext_after_stop_list`: executes the `{⟨code⟩}` set by the `after` key “after” the `keyans` environment has finished.

```

750 \cs_new_protected:Nn \__enumext_after_stop_list_vii:
751 {
752   \tl_use:N \l__enumext_after_stop_list_vii_tl
753 }
754 \cs_new_protected:Nn \__enumext_after_stop_list_viii:
755 {
756   \tl_use:N \l__enumext_after_stop_list_viii_tl
757 }

```

The function `__enumext_after_args_exec_v`: executes the `{⟨code⟩}` set by the `first` key after the end of `{⟨arg two⟩}` of the list defining the `keyans` environment, just before the first occurrence of `\item`.

```

758 \cs_new_protected:Nn \__enumext_after_args_exec_vii:
759 {
760   \tl_use:N \l__enumext_after_list_args_vii_tl
761 }
762 \cs_new_protected:Nn \__enumext_after_args_exec_viii:
763 {
764   \tl_use:N \l__enumext_after_list_args_viii_tl
765 }

```

(End of definition for `__enumext_before_args_exec_vii`: and others.)

10.17 Setting keys for multicols and minipage

mini-env The default value of the `columns-sep` key is handled by the state of the boolean variable `\l__enumext_columns_sep_X_bool` which is handled in the internal definition of the `enumext` and `keyans` environments.

mini-sep

columns-sep Define and set `mini-env`, `mini-sep`, `columns-sep` and `columns` keys for `enumext` and `keyans` environments.

columns

```

766 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
767 {
768   \keys_define:nn { enumext / #1 }
769   {
770     mini-env .dim_set:c = { \__enumext_minipage_right_#2_dim },
771     mini-env .value_required:n = true,
772     mini-sep .dim_set:c = { \__enumext_minipage_hsep_#2_dim },
773     mini-sep .initial:n = 0.3333em,
774     mini-sep .value_required:n = true,
775     columns-sep .dim_set:c = { \__enumext_columns_sep_#2_dim },
776     columns-sep .value_required:n = true,
777     columns .int_set:c = { \__enumext_columns_#2_int },
778     columns .initial:n = 1,
779     columns .value_required:n = true,
780   }
781 }
782 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

For `enumext*` and `keyans*` environments the situation is a bit different, the default value for `columns` key are `2` and the command `\miniright` is not available, so we will add the keys `miniright` and `miniright*` to implement support for `minipage`.

```

783 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
784 {
785   \keys_define:nn { enumext / #1 }
786   {
787     columns .initial:n = 2,
788     miniright .tl_gset:c = { g__enumext_miniright_code_#2_tl },
789     miniright .value_required:n = true,
790     miniright* .code:n = {
791       \bool_gset_true:c { g__enumext_minipage_center_#2_bool }
792       \keys_set:nn { enumext / #1 } { miniright = {##1} }
793     },
794     miniright* .value_required:n = true,
795   }
796 }
797 \clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }

```

(End of definition for `mini-env` and others.)

10.18 Adjustment of vertical spaces for multicols

When nesting a “*list environment*” inside the `multicols` environment, the values of the “*vertical spaces*” are lost, basically the `multicols` environment takes control over them. Graphically it can be seen like in the figure 7.




Figure 7: Representation of the vertical space in `multicols` for a nested level.

To keep the desired spaces *above* and *below* in the “*list environment*” (`\topsep` + `[\partopsep]`) it is necessary to “*adjust*” the spaces added by the `multicols` environment. The most appropriate option in this case is to use a “*context sensitive*” vertical space with `\addvspace`.

- I should make it clear that the implementation here is a “*bit questionable*”. At first glance doing `\multicolsep=\topsep` seemed right, but the results were not always as expected. An almost *imperceptible* detail is that in some cases the `\itemsep` values of are “*stretched*”, possibly due to the use of `\raggedcolumns` and this affects the lower space when closing the environment, which is “*smaller*” than expected. My attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

10.18.1 Adjustment of vertical spaces for multicol in enumext

`__enumext_multi_set_vskip:` The function `__enumext_multi_set_vskip:` will take care of determining the “adjusted spaces” that we will apply “above” and “below” the `multicol` environment in `enumext`.

We will set the default values taking into account that \TeX is in *horizontal mode*, then we will make the settings for the *vertical mode* in which `\partopsep` comes into play.

Set the values of `\l__enumext_multicols_above_X_skip` and `\l__enumext_multicols_below_X_skip` equal to the value of `\topsep` in the *current level*.

```

798 \cs_new_protected:Nn \__enumext_multi_set_vskip:
799 {
800   \skip_set:cn { \l__enumext_multicols_above_ \__enumext_level: _skip }
801   {
802     \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip }
803   }
804   \skip_set:cn { \l__enumext_multicols_below_ \__enumext_level: _skip }
805   {
806     \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip }
807   }
808   \__enumext_add_pre_parsep:
809 }
```

(End of definition for `__enumext_multi_set_vskip:`.)

`__enumext_add_pre_parsep:` The function `__enumext_add_pre_parsep:` “adjusted” the value of `\l__enumext_multicols_above_X_skip` detecting the value of `\parsep` from the previous level. This is necessary since `\parsep` from the previous level affects the *vertical spaces*.

```

810 \cs_new_protected:Nn \__enumext_add_pre_parsep:
811 {
812   \int_case:nn { \l__enumext_level_int }
813   {
814     { 2 }{
815       \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip }
816       {
817         \skip_add:Nn \l__enumext_multicols_above_ii_skip { \l__enumext_parsep_i_skip }
818       }
819     }
820     { 3 }{
821       \skip_if_eq:nnF { \l__enumext_parsep_ii_skip } { \c_zero_skip }
822       {
823         \skip_add:Nn \l__enumext_multicols_above_iii_skip { \l__enumext_parsep_ii_skip }
824       }
825     }
826     { 4 }{
827       \skip_if_eq:nnF { \l__enumext_parsep_iii_skip } { \c_zero_skip }
828       {
829         \skip_add:Nn \l__enumext_multicols_above_iv_skip { \l__enumext_parsep_iii_skip }
830       }
831     }
832   }
833 }
```

(End of definition for `__enumext_add_pre_parsep:`.)

`__enumext_multi_addvspace:` The function `__enumext_multi_addvspace:` will apply the spaces set using `\addvspace` “above” the `multicol` environment in `enumext`, taking into account whether \TeX is in *horizontal mode* or *vertical mode*.

```

834 \cs_new_protected:Nn \__enumext_multi_addvspace:
835 {
836   \__enumext_multi_set_vskip:
837   \mode_if_vertical:T
838   {
839     \skip_add:cn { \l__enumext_multicols_above_ \__enumext_level: _skip }
840     {
841       \skip_use:c { \l__enumext_partopsep_ \__enumext_level: _skip }
842     }
843     \skip_add:cn { \l__enumext_multicols_below_ \__enumext_level: _skip }
844     {
845       \skip_use:c { \l__enumext_partopsep_ \__enumext_level: _skip }
846     }
847   }
```

```

848 \par\nopagebreak
849 \addvspace{ \skip_use:c { \l__enumext_multicols_above_ \l__enumext_level: \skip } }
850 }

```

(End of definition for `\l__enumext_multi_addvspace:`.)

10.18.2 Adjustment of vertical spaces for multicols in keyans

`\l__enumext_keyans_multi_set_vskip:` The function `\l__enumext_keyans_multi_set_vskip:` will take care of determining the “adjusted spaces” that we will apply “above” and “below” the `\multicols` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

```

851 \cs_new_protected:Nn \l__enumext_keyans_multi_set_vskip:
852 {
853   \skip_set:Nn \l__enumext_multicols_above_v_skip
854   {
855     \l__enumext_topsep_v_skip
856   }
857   \skip_set:Nn \l__enumext_multicols_below_v_skip
858   {
859     \l__enumext_topsep_v_skip
860   }
861 }
862 \cs_new_protected:Nn \l__enumext_keyans_multi_addvspace:
863 {
864   \l__enumext_keyans_multi_set_vskip:
865   \mode_if_vertical:T
866   {
867     \skip_add:Nn \l__enumext_multicols_above_v_skip
868     {
869       \skip_use:N \l__enumext_partopsep_v_skip
870     }
871     \skip_add:Nn \l__enumext_multicols_below_v_skip
872     {
873       \skip_use:N \l__enumext_partopsep_v_skip
874     }
875   }
876   \par\nopagebreak
877   \addvspace{ \l__enumext_multicols_above_v_skip }
878 }

```

(End of definition for `\l__enumext_keyans_multi_set_vskip:` and `\l__enumext_keyans_multi_addvspace:`.)

10.19 Adjustment of vertical spaces for minipage

When nesting a “list environment” within the `minipage` environment, the values of the “vertical spaces” are lost. Graphically it can be seen like in the figure 8.




Figure 8: Representation of the `minipage` spacing adjustment for a nested level.

Since we want to keep the “left” and “right” environments “aligned on top”, preserving the `\baselineskip` and keep the desired “spaces” (`\topsep` + `[\partopsep]`) it is necessary to “adjust” the “vertical spaces” for `minipage` environments.

Here there are several complications that we must circumvent, the `minipage` environment eliminates the “top” spaces, the `\multicols` environment can be nested in the `minipage` environment, the “top” and “bottom” spaces are affected when `\topsep=0pt` and to this is added the `\partopsep` parameter that comes into action according to whether \TeX is in *horizontal mode* or *vertical mode*. Depending on these cases, small adjustments must be made using `\vspace` and `\addvspace` to obtain the “desired vertical spacing”.

Again I must make clear that the implementation here is a “bit questionable”, but hunting the spaces (`\glue`) produced by the `minipage` environment is quite complicated, even more if `\multicols` it is nested. The setting of the values was more “trial and error” (aprox to `\strutbox`), using the help of the `lua-visual-debug` [12] package, again my attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

`\l__enumext_mini_env*` Creates a `\l__enumext_mini_env*` environment (custom version of `minipage`) setting the `\if@minipage` switch to “false” to allow spaces at the “above” of the environment, plus we will add `\vspace{0pt}` to maintain alignment on “top”. This environment will be used internally by the `mini-env` key, it is not documented in the user interface and is for internal use only.

```

879 \DeclareDocumentEnvironment{__enumext_mini_env*}{ m }
880 {
881     \__enumext_minipage:w [ t ] { #1 }
882     \legacy_if_gset_false:n { @minipage }
883     \vspace { 0pt }
884 }
885 { \__enumext_endminipage: }

```

(End of definition for `__enumext_mini_env*`.)

10.19.1 Adjustment of vertical spaces for minipage in enumext

`__enumext_mini_set_vskip:` The function `__enumext_mini_set_vskip:` will take care of determining the “*adjust*” spaces that we will apply “*above*” and “*below*” the `__enumext_mini_env*` environment in `enumext`.

We will set the default values taking into account that T_EX is in (*horizontal mode*), then we will make the settings for the (*vertical mode*) in which `\partopsep` comes into play.

First determine if the `multicols` environment is active by comparing the value of the `\l__enumext_columns_X_int` variable handled by the `columns` key, according to this comparison we set the adjusted values for `\l__enumext_minipage_left_skip`, `\l__enumext_minipage_right_skip` and `\l__enumext_minipage_after_skip`.

```

886 \cs_new_protected:Nn \__enumext_mini_set_vskip:
887 {
888     \int_compare:nNnTF
889     { \int_use:c { \l__enumext_columns_ \__enumext_level: _int } } > { 1 }
890     {

```

If `multicols` environment is nested in `__enumext_mini_env*` environment, we will apply a correction factor to the *vertical spaces* taking into account the value of `\topsep` of the current level and the value of `\parsep` of the previous level, if these are zero we will use `\strutbox` as the basis for the calculations.

```

891     \skip_if_eq:nnTF
892     { \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip } } { \c_zero_skip }
893     {
894         \skip_set:Nn \l__enumext_minipage_left_skip
895         {
896             -0.150\box_dp:N \strutbox
897         }
898         \skip_set:Nn \l__enumext_minipage_right_skip
899         {
900             0.695\box_dp:N \strutbox
901         }
902         \skip_set:Nn \l__enumext_minipage_after_skip
903         {
904             \box_dp:N \strutbox
905         }
906         \__enumext_zero_parsep:
907     }
908     {
909         \skip_set:Nn \l__enumext_minipage_left_skip
910         {
911             \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip }
912         }
913         \skip_set:Nn \l__enumext_minipage_right_skip
914         {
915             0.695\box_dp:N \strutbox
916         }
917         \skip_set:Nn \l__enumext_minipage_after_skip
918         {
919             1.85\box_dp:N \strutbox
920             + \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip }
921         }
922     }
923 }
924 {

```

If only `enumext` environment is nested in `__enumext_mini_env*` environment, we will apply a correction factor to the *vertical spaces* taking into account the value of `\topsep`, if this is zero we will use `\strutbox` as the basis for the calculations.

```

925     \skip_if_eq:nnTF
926     { \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip } } { \c_zero_skip }
927     {
928         \skip_set:Nn \l__enumext_minipage_left_skip

```

```

929         {
930             0.5\box_dp:N \strutbox
931             - \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
932         }
933     \skip_set:Nn \l__enumext_minipage_right_skip
934     {
935         \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
936     }
937     \skip_set:Nn \l__enumext_minipage_after_skip
938     {
939         1.6\box_dp:N \strutbox
940     }
941 }
942 {
943     \skip_set:Nn \l__enumext_minipage_left_skip
944     {
945         0.5875\box_dp:N \strutbox
946         - \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
947     }
948     \skip_set:Nn \l__enumext_minipage_right_skip
949     {
950         + \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
951         + \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
952     }
953     \skip_set:Nn \l__enumext_minipage_after_skip
954     {
955         0.325\box_dp:N \strutbox
956         + \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
957     }
958 }
959 }
960 }

```

(End of definition for `__enumext_mini_set_vskip:`)

`__enumext_zero_parsep:` The function `__enumext_zero_parsep:` “adjusted” the value of `\l__enumext_minipage_after_skip` detecting the value of `\parsep` from the previous level. This is necessary since `\parsep` from the previous level affects the *vertical spaces* and this is noticeable when using the `nosep` or `noitemsep` keys.

```

961 \cs_new_protected:Nn \__enumext_zero_parsep:
962 {
963     \int_case:nn { \l__enumext_level_int }
964     {
965         { 2 } {
966             \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip }
967             {
968                 \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
969             }
970         }
971         { 3 } {
972             \skip_if_eq:nnF { \l__enumext_parsep_ii_skip } { \c_zero_skip }
973             {
974                 \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
975             }
976         }
977         { 4 } {
978             \skip_if_eq:nnF { \l__enumext_parsep_iii_skip } { \c_zero_skip }
979             {
980                 \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
981             }
982         }
983     }
984 }

```

(End of definition for `__enumext_zero_parsep:`)

`__enumext_mini_addvspace:` The function `__enumext_mini_addvspace:` will apply the spaces set using `\addvspace` “above” the `__enumext_mini_env*` environment in `enumext`, taking into account whether \TeX is in *(horizontal mode)* or *(vertical mode)*. For the latter we will make some adjustments since the `\partopsep` parameter comes into play and this affects the *vertical spacing*.

```

985 \cs_new_protected:Nn \__enumext_mini_addvspace:
986 {

```

```

987 \__enumext_mini_set_vskip:
988 \mode_if_vertical:T
989 {
990   \skip_add:Nn \l__enumext_minipage_left_skip
991   {
992     \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
993   }
994   \skip_add:Nn \l__enumext_minipage_after_skip
995   {
996     \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
997   }
998 }
999 \par\nopagebreak
1000 \addvspace { \l__enumext_minipage_left_skip }
1001 }

```

(End of definition for __enumext_mini_addvspace:.)

10.19.2 Adjustment of vertical spaces for minipage in keyans

__enumext_keyans_mini_set_vskip:

The function __enumext_keyans_mini_set_vskip: will take care of determining the “adjusted” spaces that we will apply “above” and “below” the `__enumext_mini_env*` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

```

1002 \cs_new_protected:Nn \__enumext_keyans_mini_set_vskip:
1003 {
1004   \skip_zero_new:N \l__enumext_minipage_after_skip
1005   \skip_zero_new:N \l__enumext_minipage_left_skip
1006   \skip_zero_new:N \l__enumext_minipage_right_skip
1007   \int_compare:nNnTF { \l__enumext_columns_v_int } > { 1 }
1008   {
1009     \skip_if_eq:nnTF { \l__enumext_topsep_v_skip } { \c_zero_skip }
1010     {
1011       \skip_set:Nn \l__enumext_minipage_left_skip { -0.25\box_dp:N \strutbox }
1012       \skip_set:Nn \l__enumext_minipage_right_skip { 0.705\box_dp:N \strutbox }
1013       \skip_set:Nn \l__enumext_minipage_after_skip { \box_dp:N \strutbox }
1014       \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip }
1015       {
1016         \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
1017       }
1018     }
1019     {
1020       \skip_set:Nn \l__enumext_minipage_left_skip
1021       {
1022         \skip_use:N \l__enumext_topsep_v_skip
1023       }
1024       \skip_set:Nn \l__enumext_minipage_right_skip
1025       {
1026         0.705\box_dp:N \strutbox
1027       }
1028       \skip_set:Nn \l__enumext_minipage_after_skip
1029       {
1030         1.85\box_dp:N \strutbox + \l__enumext_topsep_v_skip
1031       }
1032     }
1033   }
1034   {
1035     \skip_if_eq:nnTF { \l__enumext_topsep_v_skip } { \c_zero_skip }
1036     {
1037       \skip_set:Nn \l__enumext_minipage_left_skip
1038       {
1039         0.5\box_dp:N \strutbox
1040         + \l__enumext_partopsep_v_skip
1041       }
1042       \skip_set:Nn \l__enumext_minipage_right_skip
1043       {
1044         \l__enumext_partopsep_v_skip
1045       }
1046       \skip_set:Nn \l__enumext_minipage_after_skip { 1.6\box_dp:N \strutbox }
1047     }
1048     {
1049       \skip_set:Nn \l__enumext_minipage_left_skip
1050       {

```

```

1051         0.5875\box_dp:N \strutbox - \l__enumext_partopsep_v_skip
1052     }
1053     \skip_set:Nn \l__enumext_minipage_right_skip
1054     {
1055         \l__enumext_topsep_v_skip + \l__enumext_partopsep_v_skip
1056     }
1057     \skip_set:Nn \l__enumext_minipage_after_skip
1058     {
1059         0.325\box_dp:N \strutbox + \l__enumext_topsep_v_skip
1060     }
1061 }
1062 }
1063 }

```

(End of definition for `__enumext_keyans_mini_set_vskip:`)

`__enumext_keyans_mini_addvspace:`

The function `__enumext_keyans_mini_addvspace:` will apply the spaces set using `\addvspace` “above” the `__enumext_mini_env*` environment in `keyans`, taking into account whether \TeX is in *horizontal mode* or *vertical mode*. For the latter we will make some adjustments since the `\partopsep` parameter comes into play and this affects the *vertical spacing*. The implementation of this function is the same as the one used in `enumext`.

```

1064 \cs_new_protected:Nn \__enumext_keyans_mini_addvspace:
1065 {
1066     \__enumext_keyans_mini_set_vskip:
1067     \mode_if_vertical:T
1068     {
1069         \skip_add:Nn \l__enumext_minipage_left_skip
1070         {
1071             \l__enumext_partopsep_v_skip
1072         }
1073         \skip_add:Nn \l__enumext_minipage_after_skip
1074         {
1075             \l__enumext_partopsep_v_skip
1076         }
1077     }
1078     \par\nopagebreak
1079     \addvspace { \l__enumext_minipage_left_skip }
1080 }

```

(End of definition for `__enumext_keyans_mini_addvspace:`)

10.19.3 Adjustment of vertical spaces for minipage in `enumext*` and `keyans*`

`__enumext_mini_set_vskip_vii:`

`__enumext_mini_set_vskip_viii:`

The functions `__enumext_mini_set_vskip_vii:` and `__enumext_mini_set_vskip_viii:` will take care of determining the “adjusted” spaces that we will apply “above” and “below” the `__enumext_mini_env*` environment in `enumext*` and `keyans*`.

```

1081 \cs_new_protected:Nn \__enumext_mini_set_vskip_vii:
1082 {
1083     \skip_zero_new:N \l__enumext_minipage_left_skip
1084     \skip_gzero_new:N \g__enumext_minipage_right_skip
1085     \skip_gzero_new:N \g__enumext_minipage_after_skip
1086     \skip_if_eq:nnTF { \l__enumext_topsep_vii_skip } { \c_zero_skip }
1087     {
1088         \skip_set:Nn \l__enumext_minipage_left_skip { 0.5\box_dp:N \strutbox }
1089         \skip_gset:Nn \g__enumext_minipage_right_skip { 0.325\box_dp:N \strutbox }
1090     }
1091     {
1092         \skip_set:Nn \l__enumext_minipage_left_skip { 0.5875\box_dp:N \strutbox }
1093         \skip_gset:Nn \g__enumext_minipage_right_skip
1094         {
1095             \l__enumext_topsep_vii_skip
1096         }
1097         \skip_gset:Nn \g__enumext_minipage_after_skip
1098         {
1099             0.325\box_dp:N \strutbox + \l__enumext_topsep_vii_skip
1100         }
1101     }
1102 }
1103 \cs_new_protected:Nn \__enumext_mini_set_vskip_viii:
1104 {
1105     \skip_zero_new:N \l__enumext_minipage_after_skip

```

```

1106 \skip_zero_new:N \l__enumext_minipage_left_skip
1107 \skip_zero_new:N \l__enumext_minipage_right_skip
1108 \skip_if_eq:nnTF { \l__enumext_topsep_viii_skip } { \c_zero_skip }
1109 {
1110   \skip_set:Nn \l__enumext_minipage_left_skip
1111   {
1112     0.5\box_dp:N \strutbox
1113   }
1114   \skip_set:Nn \l__enumext_minipage_right_skip
1115   {
1116     \l__enumext_partopsep_viii_skip
1117   }
1118   \skip_set:Nn \l__enumext_minipage_after_skip
1119   {
1120     1.6\box_dp:N \strutbox
1121   }
1122 }
1123 {
1124   \skip_set:Nn \l__enumext_minipage_left_skip
1125   {
1126     0.5875\box_dp:N \strutbox
1127   }
1128   \skip_set:Nn \l__enumext_minipage_right_skip
1129   {
1130     \l__enumext_topsep_viii_skip
1131   }
1132   \skip_set:Nn \l__enumext_minipage_after_skip
1133   {
1134     0.325\box_dp:N \strutbox + \l__enumext_topsep_viii_skip
1135   }
1136 }
1137 }

```

(End of definition for `__enumext_mini_set_vskip_vii:` and `__enumext_mini_set_vskip_viii:`.)

`__enumext_mini_addvspace_vii:`
`__enumext_mini_addvspace_viii:`

The functions `__enumext_mini_addvspace_vii:` and `__enumext_mini_addvspace_viii:` will apply the vertical space “only above” the `__enumext_mini_env*` environment on the *left side* when the `\miniright` key is active in the `enumext*` and `keyans*` environments.

Here we will NOT take into account whether \TeX is in *horizontal mode* or *vertical mode*, since `\partopsep` is equal to `0pt` in both environments.

```

1138 \cs_new_protected:Nn \__enumext_mini_addvspace_vii:
1139 {
1140   \__enumext_mini_set_vskip_vii:
1141   \par\nopagebreak
1142   \addvspace { \l__enumext_minipage_left_skip }
1143 }
1144 \cs_new_protected:Nn \__enumext_mini_addvspace_viii:
1145 {
1146   \__enumext_mini_set_vskip_viii:
1147   \par\nopagebreak
1148   \addvspace { \l__enumext_minipage_left_skip }
1149 }

```

(End of definition for `__enumext_mini_addvspace_vii:` and `__enumext_mini_addvspace_viii:`.)

10.19.4 The command `\miniright`

The command `\miniright` will close the `__enumext_mini_env*` environment on the “left side”, open the `__enumext_mini_env*` environment on the “right side” adding the *adjusted vertical space*. By default we will add `\centering` when starting the “right side” environment. The *starred version* ‘`*`’ inhibits the use of `\centering` command i.e. the usual \TeX justification is maintained in the `__enumext_mini_env*` on the “right side”.

`\miniright`

First we will perform some checks to prevent the command from being executed outside the `enumext` environment or from being executed inside the `keyanspic` environment, then we call the internal functions for the `enumext` and `keyans` environments.

```

1150 \NewDocumentCommand \miniright { s }
1151 {
1152   \int_compare:nNt { \l__enumext_keyans_pic_level_int } = { 1 }
1153   {
1154     \msg_error:nnn { enumext } { wrong-miniright-place }

```



```

1155     }
1156     \int_compare:nNt { \__enumext_level_int } = { 0 }
1157     {
1158         \msg_error:nnn { enumext } { wrong-miniright-place }
1159     }
1160     \int_compare:nNtF { \__enumext_keyans_level_int } = { 1 }
1161     {
1162         \__enumext_keyans_mini_right_cmd:n {#1}
1163     }
1164     { \__enumext_mini_right_cmd:n {#1} }
1165 }

```

(End of definition for \miniright. This function is documented on page 9.)

__enumext_mini_right_cmd:n

The function __enumext_mini_right_cmd:n takes as argument the *starred version* ‘*’ of the \miniright command in the enumext environment. We check if the mini-env key is active via the variable __enumext_minipage_right_X_dim, if so we close the multicols environment with the __enumext-mini_env* environment on the “left side”, then we open the __enumext_mini_env* environment on the “right side”, apply our adjusted “vertical spaces”, followed by adding the \centering command when the starred argument ‘*’ is not present and set zero \g__enumext_minipage_stat_int, otherwise we return an error.

```

1166 \cs_new_protected:Npn \__enumext_mini_right_cmd:n #1
1167 {
1168     \dim_compare:nNtF
1169     { \dim_use:c { \__enumext_minipage_right_ \__enumext_level: _dim } } > { \c_zero_dim }
1170     {
1171         \__enumext_multicols_stop:
1172         \end{__enumext_mini_env*}
1173         \hfill
1174         \begin{__enumext_mini_env*}
1175         { \dim_use:c { \__enumext_minipage_right_ \__enumext_level: _dim } }
1176         \par\addvspace { \__enumext_minipage_right_skip }
1177         \bool_if:nF {#1}
1178         {
1179             \centering
1180         }
1181         \int_gzero:N \g__enumext_minipage_stat_int
1182     }
1183     { \msg_error:nnn { enumext } { wrong-miniright-use } }
1184 }

```

(End of definition for __enumext_mini_right_cmd:n.)

__enumext_keyans_mini_right_cmd:n

The function __enumext_keyans_mini_right_cmd:n takes as argument the *starred version* ‘*’ of the \miniright command in the keyans environment. The implementation of this function is the same as that of the __enumext_mini_right_cmd:n function of the enumext environment.

```

1185 \cs_new_protected:Npn \__enumext_keyans_mini_right_cmd:n #1
1186 {
1187     \dim_compare:nNtF { \__enumext_minipage_right_v_dim } > { \c_zero_dim }
1188     {
1189         \__enumext_keyans_multicols_stop:
1190         \end{__enumext_mini_env*}
1191         \hfill
1192         \begin{__enumext_mini_env*}{ \__enumext_minipage_right_v_dim }
1193         \par\addvspace { \__enumext_minipage_right_skip }
1194         \bool_if:nF {#1}
1195         {
1196             \centering
1197         }
1198         \int_gzero:N \g__enumext_minipage_stat_int
1199     }
1200     { \msg_error:nnn { enumext } { wrong-miniright-use } }
1201 }

```

(End of definition for __enumext_keyans_mini_right_cmd:n.)

10.20 Setting above and below keys

While having controlled the *vertical spaces* within the `enumext` and `keyans` environments when using the `columns` or `mini-env` keys, sometimes the “*vertical spaces above*” or “*vertical spaces below*” the environments are not as expected and it is necessary to be able to apply a “*fine correction*” to these. As I have not been able to correct these *glitches*, the best option is to leave a couple of *keys* dedicated to this purpose, in this case it is best to use `\vspace` or `\vspace*` when convenient.

Define `above`, `above*`, `below` and `below*` keys for `enumext` and `keyans` environments.

```

above* 1202 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
below 1203 {
below* 1204 \keys_define:nn { enumext / #1 }
1205 {
1206     above .skip_set:c = { l__enumext_vspace_above_#2_skip },
1207     above .value_required:n = true,
1208     above* .code:n = \bool_set_true:c { l__enumext_vspace_a_star_#2_bool }
1209             \keys_set:nn { enumext / #1 } { above = {##1} },
1210     above* .value_required:n = true,
1211     below .skip_set:c = { l__enumext_vspace_below_#2_skip },
1212     below .value_required:n = true,
1213     below* .code:n = \bool_set_true:c { l__enumext_vspace_b_star_#2_bool }
1214             \keys_set:nn { enumext / #1 } { below = {##1} },
1215     below* .value_required:n = true,
1216 }
1217 }
1218 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `above` and others.)

10.20.1 Functions for above and below keys in enumext

`__enumext_vspace_above:` The function `__enumext_vspace_above:` apply the *vertical space above* the `enumext` environment set by the `above*` and `above` keys.

```

1219 \cs_new_protected:Nn \__enumext_vspace_above:
1220 {
1221     \skip_if_eq:nnF
1222     { \skip_use:c { l__enumext_vspace_above_ \__enumext_level: _skip } } { \c_zero_skip }
1223     {
1224         \bool_if:cTF { l__enumext_vspace_a_star_ \__enumext_level: _bool }
1225         {
1226             \vspace*{ \skip_use:c { l__enumext_vspace_above_ \__enumext_level: _skip } }
1227         }
1228         {
1229             \vspace { \skip_use:c { l__enumext_vspace_above_ \__enumext_level: _skip } }
1230         }
1231     }
1232 }

```

(End of definition for `__enumext_vspace_above:`.)

`__enumext_vspace_below:` The function `__enumext_vspace_below:` apply the *vertical space below* the `enumext` environment set by the `below*` and `below` keys.

```

1233 \cs_new_protected:Nn \__enumext_vspace_below:
1234 {
1235     \skip_if_eq:nnF
1236     { \skip_use:c { l__enumext_vspace_below_ \__enumext_level: _skip } } { \c_zero_skip }
1237     {
1238         \bool_if:cTF { l__enumext_vspace_b_star_ \__enumext_level: _bool }
1239         {
1240             \vspace*{ \skip_use:c { l__enumext_vspace_below_ \__enumext_level: _skip } }
1241         }
1242         {
1243             \vspace { \skip_use:c { l__enumext_vspace_below_ \__enumext_level: _skip } }
1244         }
1245     }
1246 }

```

(End of definition for `__enumext_vspace_below:`.)

10.20.2 Functions for above and below keys in keyans

`__enumext_vspace_above_v:`

The function `__enumext_vspace_above_v:` apply the *vertical space above* the **keyans** environment set by the *above** and *above** keys.

```

1247 \cs_new_protected:Nn \__enumext_vspace_above_v:
1248 {
1249   \skip_if_eq:nnF { \l__enumext_vspace_above_v_skip } { \c_zero_skip }
1250   {
1251     \bool_if:NTF \l__enumext_vspace_a_star_v_bool
1252     {
1253       \vspace*{ \l__enumext_vspace_above_v_skip }
1254     }
1255     { \vspace { \l__enumext_vspace_above_v_skip } }
1256   }
1257 }
```

(End of definition for `__enumext_vspace_above_v:`.)

`__enumext_vspace_below_v:`

The function `__enumext_vspace_below_v:` apply the *vertical space below* the **keyans** environment set by the *below** and *below* keys.

```

1258 \cs_new_protected:Nn \__enumext_vspace_below_v:
1259 {
1260   \skip_if_eq:nnF { \l__enumext_vspace_below_v_skip } { \c_zero_skip }
1261   {
1262     \bool_if:NTF \l__enumext_vspace_b_star_v_bool
1263     {
1264       \vspace*{ \l__enumext_vspace_below_v_skip }
1265     }
1266     { \vspace { \l__enumext_vspace_below_v_skip } }
1267   }
1268 }
```

(End of definition for `__enumext_vspace_below_v:`.)

10.20.3 Functions for above and below keys in enumext* keyans*

`__enumext_vspace_above_vii:`

The functions `__enumext_vspace_above_vii:` and `__enumext_vspace_above_viii:` apply the *vertical space above* the **enumext*** and **keyans*** environments set by the *above* and *above** keys.

`__enumext_vspace_above_viii:`

```

1269 \cs_new_protected:Nn \__enumext_vspace_above_vii:
1270 {
1271   \skip_if_eq:nnF { \l__enumext_vspace_above_vii_skip } { \c_zero_skip }
1272   {
1273     \bool_if:NTF \l__enumext_vspace_a_star_vii_bool
1274     {
1275       \vspace*{ \l__enumext_vspace_above_vii_skip }
1276     }
1277     { \vspace { \l__enumext_vspace_above_vii_skip } }
1278   }
1279 }
1280 \cs_new_protected:Nn \__enumext_vspace_above_viii:
1281 {
1282   \skip_if_eq:nnF { \l__enumext_vspace_above_viii_skip } { \c_zero_skip }
1283   {
1284     \bool_if:NTF \l__enumext_vspace_a_star_viii_bool
1285     {
1286       \vspace*{ \l__enumext_vspace_above_viii_skip }
1287     }
1288     { \vspace { \l__enumext_vspace_above_viii_skip } }
1289   }
1290 }
```

(End of definition for `__enumext_vspace_above_vii:` and `__enumext_vspace_above_viii:`.)

`__enumext_vspace_below_vii:`

The functions `__enumext_vspace_below_vii:` and `__enumext_vspace_below_viii:` apply the *vertical space below* the **enumext*** and **keyans*** environments set by the *below** and *below* keys.

`__enumext_vspace_below_viii:`

```

1291 \cs_new_protected:Nn \__enumext_vspace_below_vii:
1292 {
1293   \skip_if_eq:nnF { \l__enumext_vspace_below_vii_skip } { \c_zero_skip }
1294   {
1295     \bool_if:NTF \l__enumext_vspace_b_star_vii_bool
1296     {
1297       \vspace*{ \l__enumext_vspace_below_vii_skip }
1298     }
1299     { \vspace { \l__enumext_vspace_below_vii_skip } }
1300   }
1301 }
```

```

1298     }
1299     { \vspace { \l__enumext_vspace_below_vii_skip } }
1300   }
1301 }
1302 \cs_new_protected:Nn \__enumext_vspace_below_viii:
1303 {
1304   \skip_if_eq:nnF { \l__enumext_vspace_below_viii_skip } { \c_zero_skip }
1305   {
1306     \bool_if:NTF \l__enumext_vspace_b_star_viii_bool
1307     {
1308       \vspace*{ \l__enumext_vspace_below_viii_skip }
1309     }
1310     { \vspace { \l__enumext_vspace_below_viii_skip } }
1311   }
1312 }

```

(End of definition for __enumext_vspace_below_vii: and __enumext_vspace_below_viii:.)

10.21 Setting save-ans and resume keys

The key `save-ans` is directly associated with the key `resume`, this will activate the entire “storage system” in the `enumext` package.

We define the keys `save-ans` and `resume` only for the “first level” of `enumext` and `enumext*`.

```

save-ans
resume
resume*
1313 \keys_define:nn { enumext / level-1 }
1314 {
1315   save-ans .code:n = \__enumext_storing_set:n {#1},
1316   save-ans .value_required:n = true,
1317   resume .code:n = \__enumext_resume_counter:,
1318   resume .value_forbidden:n = true,
1319   resume* .code:n = \__enumext_resume_counter_star:,
1320   resume* .value_forbidden:n = true,
1321 }
1322 \keys_define:nn { enumext / enumext* }
1323 {
1324   save-ans .code:n = \__enumext_storing_set:n {#1},
1325   save-ans .value_required:n = true,
1326   resume .code:n = \__enumext_resume_counter_vii:,
1327   resume .value_forbidden:n = true,
1328 }

```

(End of definition for `save-ans`, `resume`, and `resume*`.)

__enumext_storing_set:n

The function `__enumext_storing_set:n` executed by the `save-ans` key sets the parameters for the operation of `\anskey`, `keyans` and `keyanspic`. The variable `\l__enumext_store_name_tl` will have the “store name” with which the *⟨sequence⟩* and *⟨prop list⟩* will be created, if it does not exist it will create it globally.

The boolean var `\l__enumext_store_active_bool` will be set to true activating the entire internal *storage mechanism*, then the integer variable for the `resume` key will be created (if not exist), finally the function `__enumext_check_ans_int:n` will be called to activate the internal mechanism for checking the answers if the boolean variable `\l__enumext_check_ans_bool` set by `check-ans` key are active.

```

1329 \cs_new_protected:Npn \__enumext_storing_set:n #1
1330 {
1331   \tl_set:Nx \l__enumext_store_name_tl {#1}
1332   \prop_if_exist:cF { g__enumext_ \l__enumext_store_name_tl _prop }
1333   {
1334     \prop_new:c { g__enumext_ \l__enumext_store_name_tl _prop }
1335   }
1336   \seq_if_exist:cF { g__enumext_ \l__enumext_store_name_tl _seq }
1337   {
1338     \seq_new:c { g__enumext_ \l__enumext_store_name_tl _seq }
1339   }
1340   \bool_set_true:N \l__enumext_store_active_bool
1341   \int_if_exist:cF { g__enumext_resume_#1_int }
1342   {
1343     \int_new:c { g__enumext_resume_#1_int }
1344   }
1345 }

```

(End of definition for `__enumext_storing_set:n`.)

`__enumext_resume_counter:` The functions `__enumext_resume_counter:` and `__enumext_resume_counter_vii:` used by `resume` key in `enumext` and `enumext*`. If `save-ans` key present then set the start value from integer created by `__enumext_storing_set:n`.

```

1346 \cs_new_protected:Nn \__enumext_resume_counter:
1347 {
1348   \bool_if:NT \l__enumext_store_active_bool
1349   {
1350     \int_gset:Nn \g__enumext_resume_int
1351     {
1352       \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int }
1353     }
1354   }
1355   \bool_set_true:N \l__enumext_resume_bool
1356 }
1357 \cs_new_protected:Nn \__enumext_resume_counter_vii:
1358 {
1359   \bool_if:NT \l__enumext_store_active_bool
1360   {
1361     \int_gset:Nn \g__enumext_resume_int
1362     {
1363       \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int }
1364     }
1365   }
1366   \bool_set_true:N \l__enumext_resume_vii_bool
1367 }

```

(End of definition for `__enumext_resume_counter:` and `__enumext_resume_counter_vii:`.)

10.22 Setting check-ans key

The mechanism for checking that all questions are answered follows this logic:

If the line begins with `\item` or `\item*` and does NOT *open a nested environment*, each `\item` or `\item*` must contain a *single* execution of the `\anskey` command, i.e. the counter of the executions of the `\anskey` command must be equal to the counter associated with the sum of executions of `\item` and `\item*`.

If the line begins with `\item` or `\item*` and *opens a nested environment* each `\item` or `\item*` in the nested environment must have a *single* execution of the `\anskey` command and the counter associated to the sum of `\item` and `\item*` executions must increment by “one” to maintain equality.

In order for the mechanism for the check-answer to work (not counting `keyans`, `keyans*` and `keyanspic`) we need:

1. We must keep track of the total number of `\item` and `\item*` (enumerated) that appear within the environment including the nested levels.
2. We must keep track of the total number of `\item` and `\item*` (enumerated) that appear per level of nesting.
3. Keeping track of the number of times the environment nests.

The integer variable associated to the sum of each `\item` and `\item*` in the environment `\g__enumext_count_item_all_int` must match the integer variable `\g__enumext_count_item_ans_int` associated to the execution of the command `\anskey`. We analyze the cases:

- a) If the list only has one level the number of `\item` + `\item*` = `\anskey`
- b) If the list has *nested levels*, for each level of nesting we need to increase by one (for the `\item` or `\item*` that opens the nest) so that the account remains the same.
- c) If there is the option `no-store` we must add the items within this level plus one to maintain the equality.

With `keyans`, `keyans*` and `keyanspic` it is enough to increase in one the integer of `\anskey`. The integers created must be global if they are not lost in the interior levels of nesting and to execute the test we will use a “hook” function after closing the first level of the environment.

10.22.1 The check answer mechanism

Now we define the keys `check-ans` and `no-store` for all levels of `enumext` and `enumext*` environments.

```

check-ans
no-store
1368 \cs_set_protected:Npn \__enumext_tmp:n #1
1369 {
1370   \keys_define:nn { enumext / #1 }
1371   {
1372     check-ans .bool_set:N = \l__enumext_check_ans_bool,

```

```

1373     check-ans .initial:n = false,
1374     no-store .code:n = {
1375         \bool_set_false:N \l__enumext_store_ans_bool
1376         \bool_set_false:N \l__enumext_check_ans_bool
1377     },
1378     no-store .value_forbidden:n = true,
1379 }
1380 }
1381 \clist_map_inline:nn
1382 {
1383     level-1, level-2, level-3, level-4, enumext*
1384 }
1385 { \__enumext_tmp:n {#1} }

```

(End of definition for `check-ans` and `no-store`.)

`__enumext_current_env:` Function to detect in which environment you are working.

```

1386 \cs_new_protected:Nn \__enumext_current_env:
1387 {
1388     \str_case:en { \@currenvir }
1389     {
1390         {enumext}
1391         {
1392             \int_compare:nNnT { \l__enumext_level_h_int } = { \c_zero_int }
1393             {
1394                 \bool_gset_true:N \g__enumext_standar_bool
1395                 \int_gset:Nn \g__enumext_standar_star_env_int { \inputlineno }
1396                 \typeout{working-on-enumext}
1397                 % \int_show:N \g__enumext_standar_star_env_int
1398             }
1399         }
1400         {enumext*}
1401         {
1402             \int_compare:nNnT { \l__enumext_level_int } = { \c_zero_int }
1403             {
1404                 \bool_gset_true:N \g__enumext_starred_bool
1405                 \int_gset:Nn \g__enumext_starred_star_env_int { \inputlineno }
1406                 \typeout{working-on-enumext* ~ \g__enumext_starred_star_env_int}
1407             }
1408         }
1409     }
1410 }

```

(End of definition for `__enumext_current_env:.`)

`__enumext_check_ans_set_int_level:` The function `__enumext_check_ans_set_int_level:` will adjust the value of the variable `\g__enumext_count_item_number_int` by decrementing its value by one each time you open a nested level `enumext` environment.

```

1411 \cs_new_protected:Nn \__enumext_check_ans_set_int_level:
1412 {
1413     \int_case:nn { \l__enumext_level_int }
1414     {
1415         { 1 }{
1416             \bool_lazy_all:nT
1417             {
1418                 { \l__enumext_starred_bool }
1419                 { \int_compare_p:nNn { \l__enumext_level_int } = { \c_zero_int } }
1420             }
1421             {
1422                 \int_gdecr:N \g__enumext_count_item_number_int
1423                 \typeout{ENUMEXT ~ STANDAR ~ NEEEEEEEEEEEEESTED}
1424             }
1425         }
1426         { 2 }{
1427             \int_gdecr:N \g__enumext_count_item_number_int
1428         }
1429         { 3 }{
1430             \int_gdecr:N \g__enumext_count_item_number_int
1431         }
1432         { 4 }{
1433             \int_gdecr:N \g__enumext_count_item_number_int

```

```

1434         }
1435     }
1436     \int_case:nn { \l__enumext_level_h_int }
1437     {
1438         { 1 }{
1439             \bool_if:NT \l__enumext_standar_bool
1440             {
1441                 \int_gdecr:N \g__enumext_count_item_number_int
1442                 \typeout{ENUMEXT ~ STARRED ~ NEEEEEEEEEEEEESTED}
1443             }
1444         }
1445     }
1446 }

```

(End of definition for `__enumext_check_ans_set_int_level:`.)

10.22.2 Set-up check answer mechanism

`__enumext_check_ans_count:` The function `__enumext_check_ans_count:` will count the number of times the `\item` and `\item*` commands appears per level within the `enumext` environment. The boolean variable `\l__enumext_store_ans_bool` controlled by the `no-store` key will increment the integer variable of the level counter by 1 to preserve the equality that we will use in the final comparison of the process.

```

1447 \cs_new_protected:Nn \__enumext_check_ans_count:
1448 {
1449     \bool_if:NT \l__enumext_check_ans_bool
1450     {
1451         \__enumext_check_ans_set_int_level:
1452     }
1453 }

```

(End of definition for `__enumext_check_ans_count:`.)

`__enumext_check_ans_active:` The function `__enumext_check_ans_active:` compare all `\item`'s plus `\item*`'s and `\item`'s with answer for checking answer mechanism and display the appropriate message on the terminal. After the function is executed, we set the integer variables to zero.

```

1454 \cs_new_protected:Nn \__enumext_check_ans_active:
1455 {
1456     \int_compare:nNnTF
1457     { \g__enumext_count_item_number_int } = { \g__enumext_count_item_anskey_int }
1458     {
1459         \msg_term:nnV { enumext } { items-same-answer } \g__enumext_store_name_tl
1460     }
1461     {
1462         \msg_warning:nnV { enumext } { item-different-answer } \g__enumext_store_name_tl
1463     }
1464     \int_gzero:N \g__enumext_count_item_number_int
1465     \int_gzero:N \g__enumext_count_item_anskey_int
1466 }

```

(End of definition for `__enumext_check_ans_active:`.)

10.23 Keys and functions associated with storage

We add the keys `wrap-ans`, `mark-ans`, `mark-pos`, `show-ans`, `show-pos`, `mark-ref` and `store-ref` related to the “storage system” and internal mechanism of “label and ref” only at the first level of `enumext` and `enumext*`.

```

1467 \cs_set_protected:Npn \__enumext_tmp:n #1
1468 {
1469     \keys_define:nn { enumext / #1 }
1470     {
1471         wrap-ans .cs_set_protected:Np = \__enumext_anskey_wrapper:n ##1,
1472         wrap-ans .initial:n = \fbox{##1},
1473         wrap-ans .value_required:n = true,
1474         mark-ans .code:n = \tl_set:Nn \l__enumext_mark_answer_sym_tl {##1},
1475         mark-ans .initial:n = \textasteriskcentered,
1476         mark-ans .value_required:n = true,
1477         mark-pos .choice:,
1478         mark-pos / left .code:n = \str_set:Nn \l__enumext_mark_position_str { l },
1479         mark-pos / right .code:n = \str_set:Nn \l__enumext_mark_position_str { r },
1480         mark-pos .initial:n = right,
1481         mark-pos .value_required:n = true,
1482         show-ans .code:n = \bool_set_true:N \l__enumext_show_answer_bool

```



```

1483                                     \bool_set_false:N \__enumext_show_position_bool,
1484     show-ans .value_forbidden:n = true,
1485     show-pos .code:n = \bool_set_true:N \__enumext_show_position_bool
1486                                     \bool_set_false:N \__enumext_show_answer_bool,
1487     show-pos .value_forbidden:n = true,
1488     mark-ref .code:n = \tl_set:Nn \__enumext_mark_ref_sym_tl {##1},
1489     mark-ref .initial:n = \textasteriskcentered,
1490     mark-ref .value_required:n = true,
1491     store-ref .bool_set:N = \__enumext_store_ref_key_bool,
1492     store-ref .initial:n = false,
1493   }
1494 }
1495 \clist_map_inline:nn { level-1, enumext* } { \__enumext_tmp:n {#1} }

```

(End of definition for wrap-ans and others.)

mark-pos For the **keyans** and **keyans*** environments we will only add the keys mark-pos, show-ans and show-pos.
show-ans

```

1496 \cs_set_protected:Npn \__enumext_tmp:n #1
1497 {
1498   \keys_define:nn { enumext / #1 }
1499   {
1500     mark-pos .choice:,
1501     mark-pos / left .code:n = \str_set:Nn \__enumext_mark_position_str { l },
1502     mark-pos / right .code:n = \str_set:Nn \__enumext_mark_position_str { r },
1503     mark-pos .initial:n = right,
1504     mark-pos .value_required:n = true,
1505     show-ans .code:n = \bool_set_true:N \__enumext_show_answer_bool
1506                                     \bool_set_false:N \__enumext_show_position_bool,
1507     show-ans .value_forbidden:n = true,
1508     show-pos .code:n = \bool_set_true:N \__enumext_show_position_bool
1509                                     \bool_set_false:N \__enumext_show_answer_bool,
1510     show-pos .value_forbidden:n = true,
1511   }
1512 }
1513 \clist_map_inline:nn { keyans, keyans* } { \__enumext_tmp:n {#1} }

```

(End of definition for mark-pos and show-ans.)

columns* For the **enumext** and **enumext*** environments we will only add the keys **columns*** and **columns-sep***.
columns-sep* The values set by these keys will be passed as optional arguments to the “inner levels” of the **enumext** and **enumext*** environments via the `__enumext_store_level_open:` function used by the “storage system” to preserve the structure and then used by the `\printkeyans` command.

```

1514 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
1515 {
1516   \keys_define:nn { enumext / #1 }
1517   {
1518     columns* .code:n = \bool_set_true:c { l__enumext_store_columns_#2_bool }
1519                                     \int_set:cn { l__enumext_store_columns_#2_int } {##1}
1520                                     \tl_put_right:ce { l__enumext_store_opt_#2_tl }
1521                                     {
1522                                       columns = \exp_not:v { l__enumext_store_columns_#2_int },
1523                                     },,
1524     columns* .value_required:n = true,
1525     columns-sep* .code:n = \bool_set_true:c { l__enumext_store_columns_sep_#2_bool }
1526                                     \dim_set:cn { l__enumext_store_columns_sep_#2_dim } {##1}
1527                                     \tl_put_right:ce { l__enumext_store_opt_#2_tl }
1528                                     {
1529                                       columns-sep = \exp_not:v { l__enumext_store_columns_sep_#2_dim },
1530                                     },
1531     columns-sep* .value_required:n = true,
1532   }
1533 }
1534 \clist_map_inline:nn
1535 {
1536   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {enumext*}{vii}
1537 }
1538 { \__enumext_tmp:nn #1 }

```

(End of definition for columns* and columns-sep*.)

10.23.1 Function for storing content in prop list

```
\__enumext_store_addto_prop:n
\__enumext_store_addto_prop:V
```

The function `__enumext_store_addto_prop:n` stores the content in *⟨prop list⟩* defined by `save-ans` key. The “stored content” is retrieved by means of the `\getkeyans` command.

The form in which the content is “stored” in the *⟨prop list⟩* is $\{\langle position \rangle\}\{\langle content \rangle\}$. This function is used by `\anskey` in `enumext` and `enumext*` environments, `\item*` in `keyans` and `keyans*` environments and `\anspic` in `keyanspic` environment.

```
1539 \cs_generate_variant:Nn \prop_gput_if_not_in:Nnn { cen }
1540 \cs_new_protected:Npn \__enumext_store_addto_prop:n #1
1541 {
1542   \prop_gput_if_not_in:cen { g__enumext_ \l__enumext_store_name_tl _prop }
1543   {
1544     \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } + 1 }
1545   }
1546   { #1 }
1547 }
1548 \cs_generate_variant:Nn \__enumext_store_addto_prop:n { V }
```

(End of definition for `__enumext_store_addto_prop:n`.)

10.23.2 Function for storing content in sequence

```
\__enumext_store_addto_seq:n
\__enumext_store_addto_seq:v
\__enumext_store_addto_seq:V
```

The function `__enumext_store_addto_seq:n` stores the content in *⟨sequence⟩* defined by `save-ans` key. This function is used by `\anskey` in `enumext`, `\item*` in `keyans` and `\anspic` in `keyanspic`.

The form in which the content is stored in *⟨sequence⟩* is in a internal `enumext` or `enumext*` environments with the *same structure* in which the command was executed.

The “stored content” is retrieved by means of the `\printkeyans` command.

```
1549 \cs_new_protected:Npn \__enumext_store_addto_seq:n #1
1550 {
1551   \seq_gput_right:cn { g__enumext_ \l__enumext_store_name_tl _seq } { #1 }
1552 }
1553 \cs_generate_variant:Nn \__enumext_store_addto_seq:n { v, V }
```

(End of definition for `__enumext_store_addto_seq:n`.)

10.23.3 Functions for storing the list structure in the sequence

```
\__enumext_store_level_open:
\__enumext_store_level_close:
```

The memorization structure of the list is handled by the functions `__enumext_store_level_open:` and `__enumext_store_level_close:` which are executed per level within the `enumext` environment. As this structure will be stored in the sequence set by the `save-ans` key, we will not be able to modify it locally, so it is better to take only two copies of the values set by the `columns` and `columns-sep` keys if they are present when changing levels within the `enumext` environment when executing `\anskey`. We will store these values in the variable `\l__enumext_store_columns_X_tl` if they are different from `0` and `0pt` and pass them as an optional argument to the environment stored in the sequence `enumext`.

```
1554 \cs_new_protected:Nn \__enumext_store_level_open:
1555 {
1556   \bool_if:NF \l__enumext_store_ans_bool
1557   {
1558     \tl_if_empty:cTF { l__enumext_store_opt_ \__enumext_level: _tl }
1559     {
1560       \__enumext_store_addto_seq:n
1561       {
1562         \item \begin{enumext}
1563       }
1564     }
1565     {
1566       \tl_put_left:cn { l__enumext_store_opt_ \__enumext_level: _tl }
1567       {
1568         \item \begin{enumext} [
1569       }
1570       \tl_put_right:cn { l__enumext_store_opt_ \__enumext_level: _tl }
1571       {
1572       ]
1573     }
1574     \__enumext_store_addto_seq:v { l__enumext_store_opt_ \__enumext_level: _tl }
1575   }
1576 }
1577 }
1578 \cs_new_protected:Nn \__enumext_store_level_close:
1579 {
1580   \bool_if:NF \l__enumext_store_ans_bool
1581   {
```

```

1582     \__enumext_store_addto_seq:n { \end{enumext} }
1583   }
1584 }

```

(End of definition for __enumext_store_level_open: and __enumext_store_level_close:.)

```

\__enumext_store_level_open_vii:
\__enumext_store_level_close_vii:

```

When nesting the `enumext*` environment in `enumext` starting right after `\item` (without material between them) there is a problem with the alignment of the labels with the baseline between the two environments. One way to get around this problem is to place `\mode_leave_vertical:` and then apply `\vspace` taking into account `\baselineskip`, the value of `\parsep` of the current level of `enumext` and the value of `\topsep` of the `enumext*` environment.

```

1585 \cs_new_protected:Nn \__enumext_store_level_open_vii:
1586 {
1587   \bool_if:NF \l__enumext_store_ans_bool
1588   {
1589     \tl_if_empty:NTF \l__enumext_store_opt_vii_tl
1590     {
1591       \__enumext_store_addto_seq:n
1592       {
1593         \item \mode_leave_vertical:
1594         \vspace { -\skip_eval:n { \baselineskip + \parsep } }
1595         \begin{enumext*}[before={\setlength{\topsep}{\opt}},]
1596       }
1597     }
1598     {
1599       \tl_put_left:Nn \l__enumext_store_opt_vii_tl
1600       {
1601         \item \mode_leave_vertical:
1602         \vspace { -\skip_eval:n { \baselineskip + \parsep } }
1603         \begin{enumext*}[before={\setlength{\topsep}{\opt}},
1604       ]
1605       \tl_put_right:Nn \l__enumext_store_opt_vii_tl
1606       {
1607         ]
1608       }
1609       \__enumext_store_addto_seq:V \l__enumext_store_opt_vii_tl
1610     }
1611   }
1612 }
1613 \cs_new_protected:Nn \__enumext_store_level_close_vii:
1614 {
1615   \bool_if:NF \l__enumext_store_ans_bool
1616   {
1617     \__enumext_store_addto_seq:n { \end{enumext*} }
1618   }
1619 }

```

(End of definition for __enumext_store_level_open_vii: and __enumext_store_level_close_vii:.)

10.23.4 Function for show marks and position

```

\__enumext_print_keyans_box:NN
\__enumext_print_keyans_box:cc

```

The function `__enumext_print_keyans_box:NN` print a box in the left margin with `\l__enumext_mark_answer_sym_tl` used by the `wrap-ans`, `show-ans` and `show-pos` keys. The function takes two arguments:

#1: `\l__enumext_labelwidth_X_dim`
#2: `\l__enumext_labelsep_X_dim`

```

1620 \cs_new_protected:Nn \__enumext_print_keyans_box:NN
1621 {
1622   \mode_leave_vertical:
1623   \skip_horizontal:n { -\dim_use:N #2 }
1624   \makebox[\opt][ r ]
1625   {
1626     \makebox[ \dim_use:N #1 ][ \l__enumext_mark_position_str ]
1627     {
1628       \tl_use:N \l__enumext_mark_answer_sym_tl
1629     }
1630   }
1631   \skip_horizontal:n { \dim_use:N #2 }
1632 }
1633 \cs_generate_variant:Nn \__enumext_print_keyans_box:NN { cc }

```

(End of definition for __enumext_print_keyans_box:NN.)

10.24 The command `\anskey` and internal label and ref

Since we will be “*storing content*” in a list environment within `\sequences` and can (more or less) manage the options passed to each level, it is necessary that we have a little more control over `\item` when storing. The `\anskey` command will cover this point and give it very similar behaviour to that of `\item` in the `enumext` and `enumext*` environments.

`\anskey` We want the command to be executed as follows: `\anskey(\langle number \rangle)*[\langle key = val \rangle]{\langle content \rangle}` so first we’ll add the keys `item-sym*`, `item-pos*` and `store-brk`.

```

1634 \keys_define:nn { enumext / anskey }
1635 {
1636   item-sym* .tl_set:N = \l__enumext_store_item_symbol_tl,
1637   item-sym* .value_required:n = true,
1638   item-pos* .dim_set:N = \l__enumext_store_item_symbol_sep_dim,
1639   item-pos* .value_required:n = true,
1640   store-brk .bool_set:N = \l__enumext_store_columns_break_bool,
1641   store-brk .default:n = true,
1642   store-brk .value_forbidden:n = true,
1643 }

```

This command `\anskey` will only be present when using the `save-ans` key in `enumext` and `enumext*` environments, otherwise it will return an error. If the `check-ans` key is active, increment `\g__enumext_count_item_with_ans_int`, then call internal function `__enumext_store_anskey_code:nnnn` will “*store content*” in the `\sequence` and in the `\prop list`.

```

1644 \NewDocumentCommand \anskey { d() s o +m }
1645 {
1646   \bool_if:NF \l__enumext_store_active_bool
1647   {
1648     \msg_error:nnnn { enumext } { anskey-wrong-place } { anskey } { enumext }
1649   }
1650   \int_compare:nNt { \l__enumext_keyans_level_int } = { 1 }
1651   {
1652     \msg_error:nnnn { enumext } { command-wrong-place } { anskey } { keyans }
1653   }
1654   \int_compare:nNt { \l__enumext_keyans_pic_level_int } = { 1 }
1655   {
1656     \msg_error:nnnn { enumext } { command-wrong-place } { anskey } { keyanspic }
1657   }
1658   \group_begin:
1659     \bool_if:NF \l__enumext_store_ans_bool
1660     {
1661       \bool_if:NT \l__enumext_check_ans_bool
1662       {
1663         \int_gincr:N \g__enumext_count_item_anskey_int
1664       }
1665       \__enumext_store_anskey_code:nnnn {#1} {#2} {#3} {#4}
1666     }
1667   \group_end:
1668 }

```

(End of definition for `\anskey`. This function is documented on page 10.)

`__enumext_store_anskey_code:nnnn`

The internal function `__enumext_store_anskey_code:nnnn` first we pass the command `\argument` to the `\prop list`, then checks the state of the variable `\l__enumext_store_ref_key_bool` handled by the `store-ref` key and will call the function `__enumext_store_internal_ref:` for the internal “*label and ref*” system. Followed by this if the `show-ans` or `show-pos` keys are active we will show the “*wrapped*” `\argument` passed to the command.

```

1669 \cs_new_protected:Npn \__enumext_store_anskey_code:nnnn #1 #2 #3 #4
1670 {
1671   \__enumext_store_addto_prop:n {#4}
1672   \bool_if:NT \l__enumext_store_ref_key_bool
1673   {
1674     \__enumext_store_internal_ref:
1675   }
1676   \__enumext_store_anskey_show_left:n { #4 }

```

Now we start processing the optional arguments passed to the command to build our `\item` in the variable `\l__enumext_store_anskey_arg_tl` which we will “*store*” in the `\sequence`. First we clear the variable `\l__enumext_store_anskey_arg_tl` and process `[\langle key = val \rangle]`, if the `store-brk` key is present and the command is running under `enumext` (not in the starred version) we will add `\columnbreak` and then `\item`.

```

1677 \tl_clear:N \l__enumext_store_anskey_arg_tl
1678 \tl_if_novalue:nF {#3}
1679 {
1680   \keys_set:nn { enumext / anskey } {#3}
1681 }
1682 \bool_lazy_and:nnT
1683 { \l__enumext_store_columns_break_bool }
1684 { \bool_not_p:n { \l__enumext_starred_bool } }
1685 {
1686   \tl_put_left:Nn \l__enumext_store_anskey_arg_tl { \columnbreak }
1687 }
1688 \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { \item }

```

Now we will check the (*number*) argument and add it to `\l__enumext_store_anskey_arg_tl` if the command is running under `enumext*` (starred version).

```

1689 \tl_if_novalue:nF {#1}
1690 {
1691   \int_set:Nn \l__enumext_store_columns_join_int {#1}
1692   \bool_if:NT \l__enumext_starred_bool
1693   {
1694     \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
1695     {
1696       ( \exp_not:V \l__enumext_store_columns_join_int )
1697     }
1698   }
1699 }

```

And now we will review the starred argument `*` together with the keys `item-sym*` and `item-pos*` and pass them to `\l__enumext_store_anskey_arg_tl`.

```

1700 \bool_if:nTF {#2}
1701 {
1702   \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { * }
1703   \tl_if_empty:NF \l__enumext_store_item_symbol_tl
1704   {
1705     \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
1706     {
1707       [ \exp_not:V \l__enumext_store_item_symbol_tl ]
1708     }
1709   }
1710   \dim_compare:nT
1711   {
1712     \l__enumext_store_item_symbol_sep_dim != \c_zero_dim
1713   }
1714   {
1715     \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
1716     {
1717       [ \exp_not:V \l__enumext_store_item_symbol_sep_dim ]
1718     }
1719   }
1720   \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#4}
1721 }
1722 {
1723   \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#4}
1724 }

```

Finally we check if the `store-ref` key is active along with the `hyperref` package load, if both conditions are met, it will create the `\hyperlink` and then store in (*sequence*).

```

1725 \bool_lazy_and:nnT
1726 { \l__enumext_store_ref_key_bool }
1727 { \l__enumext_hyperref_bool }
1728 {
1729   \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
1730   {
1731     \hfill \exp_not:N \hyperlink { \exp_not:V \l__enumext_newlabel_arg_one_tl }
1732     { \exp_not:V \l__enumext_mark_ref_sym_tl }
1733   }
1734 }
1735 \l__enumext_store_addto_seq:V \l__enumext_store_anskey_arg_tl
1736 }

```

(End of definition for `\l__enumext_store_anskey_code:nnnn`.)

`__enumext_store_internal_ref:` The function `__enumext_store_internal_ref:` handles the internal “*label and ref*” system used by the `store-ref` and `mark-ref` keys for `\anskey` will allow to execute `\ref{⟨store name: position⟩}` and will return `1.(a).i.A`.

First we will remove the dots “.” from the current `⟨labels⟩`, we do not want to get double dots in our references, then we will place this in the variable `__enumext_newlabel_arg_two_tl`.

```

1737 \cs_new_protected:Nn \__enumext_store_internal_ref:
1738 {
1739   \cs_set_protected:Npn \__enumext_tmp:n ##1
1740   {
1741     \tl_set_eq:cc { \__enumext_label_copy_##1_tl } { \__enumext_label_##1_tl }
1742     \tl_reverse:c { \__enumext_label_copy_##1_tl }
1743     \tl_remove_once:cn { \__enumext_label_copy_##1_tl } { . }
1744     \tl_reverse:c { \__enumext_label_copy_##1_tl }
1745   }
1746   \clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {##1} }
1747   \cs_set:Npn \__enumext_tmp:n ##1
1748   { . \tl_use:c { \__enumext_label_copy_ \int_to_roman:n {##1} _tl } }

```

Here we need to analyse the cases where the environment is started with `enumext*` and if `\anskey` is running alone in it or if it is running in a nested `enumext` environment within the starting environment.

```

1749   \bool_lazy_all:nT
1750   {
1751     { \g__enumext_starred_bool }
1752     { \int_compare_p:nNn { \__enumext_level_int } = { \c_zero_int } }
1753   }
1754   {
1755     \tl_put_right:Ne \__enumext_newlabel_arg_two_tl
1756     { \tl_use:N \__enumext_label_copy_vii_tl }
1757   }
1758   \bool_lazy_all:nT
1759   {
1760     { \l__enumext_standar_bool }
1761     { \g__enumext_starred_bool }
1762     { \int_compare_p:nNn { \__enumext_level_int } > { \c_zero_int } }
1763   }
1764   {
1765     \tl_put_right:Ne \__enumext_newlabel_arg_two_tl
1766     {
1767       \tl_use:N \__enumext_label_copy_vii_tl
1768       \int_step_function:nnN { 1 } { \__enumext_level_int } \__enumext_tmp:n
1769     }
1770   }

```

If started with `enumext` and if `\anskey` is running alone in it or if it is running in a nested `enumext*` environment within the starting environment.

```

1771   \bool_lazy_all:nT
1772   {
1773     { \l__enumext_standar_bool }
1774     { \int_compare_p:nNn { \__enumext_level_int } > { \c_zero_int } }
1775     { \int_compare_p:nNn { \__enumext_level_h_int } = { \c_zero_int } }
1776     { \bool_not_p:n { \__enumext_starred_bool } }
1777   }
1778   {
1779     \tl_put_right:Ne \__enumext_newlabel_arg_two_tl
1780     {
1781       \tl_use:N \__enumext_label_copy_i_tl
1782       \int_step_function:nnN { 2 } { \__enumext_level_int } \__enumext_tmp:n
1783     }
1784   }
1785   \cs_set:Npn \__enumext_tmp:n ##1
1786   { \tl_use:c { \__enumext_label_copy_ \int_to_roman:n {##1} _tl } }
1787   \bool_lazy_all:nT
1788   {
1789     { \l__enumext_standar_bool }
1790     { \int_compare_p:nNn { \__enumext_level_int } > { \c_zero_int } }
1791     { \bool_not_p:n { \g__enumext_starred_bool } }
1792     { \int_compare_p:nNn { \__enumext_level_h_int } > { \c_zero_int } }
1793   }
1794   {
1795     \tl_put_right:Ne \__enumext_newlabel_arg_two_tl
1796     {

```

```

1797         \int_step_function:nnN { 1 } { \l__enumext_level_int } \l__enumext_tmp:n
1798         . \tl_use:N \l__enumext_label_copy_vii_tl
1799     }
1800 }

```

Now we set the variable `\l__enumext_newlabel_arg_one_tl` which will contain $\langle \textit{store name} : \textit{position} \rangle$.

```

1801     \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
1802     {
1803         \l__enumext_store_name_tl \c_colon_str
1804         \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
1805     }

```

Now execute the function `\l__enumext_newlabel:nn` and save the result in the variable `\l__enumext_store_write_aux_file_tl` and finally we write in the `.aux` file.

```

1806     \tl_put_right:Ne \l__enumext_store_write_aux_file_tl
1807     {
1808         \l__enumext_newlabel:nn
1809         { \exp_not:V \l__enumext_newlabel_arg_one_tl }
1810         { \l__enumext_newlabel_arg_two_tl }
1811     }
1812     \l__enumext_store_write_aux_file_tl
1813 }

```

(End of definition for `\l__enumext_store_internal_ref:.`)

`\l__enumext_store_anskey_show_wrap:n`

The function `\l__enumext_store_anskey_show_wrap:n` “wraps” the $\langle \textit{argument} \rangle$ passed to `\anskey` when using the `wrap-ans` key.

```

1814 \cs_new_protected:Npn \l__enumext_store_anskey_show_wrap:n #1
1815 {
1816     \par
1817     \bool_if:NT \l__enumext_starred_bool
1818     {
1819         \cs_set:Nn \l__enumext_level: { vii }
1820     }
1821     \l__enumext_print_keyans_box:cc
1822     { \l__enumext_labelwidth_ \l__enumext_level: _dim }
1823     { \l__enumext_labelsep_ \l__enumext_level: _dim }
1824     \l__enumext_anskey_wrapper:n { #1 }
1825 }

```

(End of definition for `\l__enumext_store_anskey_show_wrap:n`.)

`\l__enumext_store_anskey_show_left:n`

The function `\l__enumext_store_anskey_show_left:n` will show the “mark” defined by the `mark-ans` key or the “position” of the content stored in the $\langle \textit{prop list} \rangle$ when using the `show-pos` key on the left margin next to the “wraps” $\langle \textit{argument} \rangle$ passed to `\anskey` on the right side when using the `show-ans` key.

```

1826 \cs_new_protected:Npn \l__enumext_store_anskey_show_left:n #1
1827 {
1828     \bool_if:NT \l__enumext_show_answer_bool
1829     {
1830         \l__enumext_store_anskey_show_wrap:n { #1 }
1831     }
1832     \bool_if:NT \l__enumext_show_position_bool
1833     {
1834         \tl_set:Ne \l__enumext_mark_answer_sym_tl
1835         {
1836             \group_begin:
1837             \exp_not:N \normalfont
1838             \exp_not:N \footnotesize [ \int_eval:n
1839             {
1840                 \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
1841             }
1842             ]
1843             \group_end:
1844         }
1845         \l__enumext_store_anskey_show_wrap:n { #1 }
1846     }
1847 }

```

(End of definition for `\l__enumext_store_anskey_show_left:n`.)

10.25 Common functions for keyans, keyans* and keyanspic

10.25.1 Storing content in prop list

`__enumext_keyans_addto_prop:n`

The function `__enumext_keyans_addto_prop:n` will pass the contents of the current $\langle label \rangle$ `\l__enumext_label_v_tl` for the `keyans` environment and the current $\langle label \rangle$ `\l__enumext_label_vi_tl` for the `keyanspic` environment when using `\item*` and `\anspic*`, followed by the *contents* of the optional argument of both commands to the `\l__enumext_store_keyans_label_tl` variable, which will be passed to the $\langle prop list \rangle$ defined by the `save-ans` key using the `__enumext_store_addto_prop:V`.

```

1848 \cs_new_protected:Npn \__enumext_keyans_addto_prop:n #1
1849 {
1850   \tl_clear:N \l__enumext_store_keyans_label_tl
1851   \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
1852   {
1853     \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \l__enumext_label_vi_tl }
1854   }
1855   {
1856     \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \l__enumext_label_v_tl }
1857   }
1858   \tl_if_no_value:nF { #1 }
1859   {
1860     \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \c_space_tl #1 }
1861   }
1862   \__enumext_store_addto_prop:V \l__enumext_store_keyans_label_tl
1863 }

```

(End of definition for `__enumext_keyans_addto_prop:n`.)

10.25.2 The store-ref key for keyans, keyans* and keyanspic

The internal “*label and ref*” system for the `keyans`, `keyans*` and `keyanspic` environments has slight differences with the one implemented for the `\anskey` command, basically because in this environments we are interested in the current $\langle label \rangle$. The mechanism defined here will allow to execute `\ref{\langle store name : position \rangle}` and will return `1`. (A).

`__enumext_keyans_store_ref:`

`__enumext_keyans_store_ref_aux_i:`

`__enumext_keyans_store_ref_aux_ii:`

The function `__enumext_keyans_store_ref:` handles the internal “*label and ref*” system used by the `store-ref` key for `\item*` and `\anspic*` commands. First we will create copies of the current $\langle labels \rangle$ and remove the dots “.” from them, we do not want to get double dots in our references.

```

1864 \cs_new_protected:Nn \__enumext_keyans_store_ref:
1865 {
1866   \bool_if:NT \l__enumext_store_ref_key_bool
1867   {
1868     \cs_set_protected:Npn \__enumext_tmp:n ##1
1869     {
1870       \tl_set_eq:cc { \l__enumext_label_copy_##1_tl } { \l__enumext_label_##1_tl }
1871       \tl_reverse:c { \l__enumext_label_copy_##1_tl }
1872       \tl_remove_once:cn { \l__enumext_label_copy_##1_tl } { . }
1873       \tl_reverse:c { \l__enumext_label_copy_##1_tl }
1874     }
1875     \clist_map_inline:nn { i, v, vi, vii, viii } { \__enumext_tmp:n {##1} }
1876     \__enumext_keyans_store_ref_aux_i:
1877   }
1878 }

```

The auxiliary function `__enumext_keyans_store_ref_aux_i:` set the variable `\l__enumext_newlabel_arg_one_tl` which will contain $\{\langle store name : position \rangle\}$ analyzing whether the environment in which they are executed is `enumext*` or `enumext`.

```

1879 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_i:
1880 {
1881   \bool_if:NT \g__enumext_starred_bool
1882   {
1883     \tl_set_eq:NN \l__enumext_label_copy_i_tl \l__enumext_label_copy_vii_tl
1884   }
1885   \int_compare:nNnT { \l__enumext_keyans_pic_level_int } = { 1 }
1886   {
1887     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
1888     { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_vi_tl }
1889   }
1890   \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
1891   {
1892     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl

```

```

1893         { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_v_tl }
1894     }
1895     \int_compare:nNt { \l__enumext_keyans_level_h_int } = { 1 }
1896     {
1897         \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
1898         { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_viii_tl }
1899     }
1900     \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
1901     {
1902         \l__enumext_store_name_tl \c_colon_str
1903         \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
1904     }
1905     \__enumext_keyans_store_ref_aux_ii:
1906 }

```

Now auxiliary function `__enumext_keyans_store_ref_aux_ii:` save the result in the variable `\l__enumext_store_write_aux_file_tl` and finally we write in the `.aux` file.

```

1907 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_ii:
1908 {
1909     \tl_put_right:Ne \l__enumext_store_write_aux_file_tl
1910     {
1911         \__enumext_newlabel:nn
1912         { \exp_not:V \l__enumext_newlabel_arg_one_tl }
1913         { \l__enumext_newlabel_arg_two_tl }
1914     }
1915     \l__enumext_store_write_aux_file_tl
1916 }

```

(End of definition for `__enumext_keyans_store_ref:`, `__enumext_keyans_store_ref_aux_i:`, and `__enumext_keyans_store_ref_aux_ii:`.)

10.25.3 Storing content in sequence

```

\__enumext_keyans_addto_seq:n
\__enumext_keyans_addto_seq_link:

```

The function `__enumext_keyans_addto_seq:n` will pass the contents of the current *⟨label⟩* `\l__enumext_label_v_tl` for the `keyans` environment and the `\l__enumext_label_vi_tl` for the `keyanspic` environment when using `\item*` and `\anspic*`, followed by the *⟨contents⟩* of the optional argument of both commands to the `\l__enumext_store_keyans_label_tl` variable to the sequence defined by the `save-ans` key.

```

1917 \cs_new_protected:Npn \__enumext_keyans_addto_seq:n #1
1918 {
1919     \tl_clear:N \l__enumext_store_keyans_label_tl
1920     \int_compare:nNtF { \l__enumext_keyans_pic_level_int } = { 1 }
1921     {
1922         \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \item \l__enumext_label_vi_tl }
1923     }
1924     {
1925         \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \item \l__enumext_label_v_tl }
1926     }
1927     \tl_if_no_value:nF { #1 }
1928     {
1929         \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \c_space_tl #1 }
1930     }
1931     \__enumext_keyans_addto_seq_link:
1932 }

```

Checks if the `store-ref` key is active along with the `hyperref` package load, if both conditions are met, it will create the `\hyperlink` and then store using the `__enumext_store_addto_seq:V` function. Finally, copy the contents of the variable `\l__enumext_store_keyans_label_tl` into the global variable `\g__enumext_check_ans_item_tl` to be used by the function `__enumext_keyans_check_ans:nn` and increment the value of the integer variable `\g__enumext_count_item_number_int` handled by the `check-ans` key.

```

1933 \cs_new_protected:Nn \__enumext_keyans_addto_seq_link:
1934 {
1935     \bool_lazy_and:nnT
1936     { \l__enumext_store_ref_key_bool }
1937     { \l__enumext_hyperref_bool }
1938     {
1939         \tl_put_right:Ne \l__enumext_store_keyans_label_tl
1940         {
1941             \hfill \exp_not:N \hyperlink
1942             {
1943                 \exp_not:V \l__enumext_newlabel_arg_one_tl

```

```

1944         }
1945         { \exp_not:V \l__enumext_mark_ref_sym_tl }
1946     }
1947 }
1948 \__enumext_store_addto_seq:V \l__enumext_store_keyans_label_tl
1949 \tl_gset:NV \g__enumext_check_ans_item_tl \l__enumext_store_keyans_label_tl
1950 \bool_if:NT \l__enumext_check_ans_bool
1951 {
1952     \int_gincr:N \g__enumext_count_item_number_int
1953 }
1954 }

```

(End of definition for `__enumext_keyans_addto_seq:n` and `__enumext_keyans_addto_seq_link:.`)

10.25.4 Check for starred commands

`__enumext_keyans_check_ans:nn`

The function `__enumext_keyans_check_ans:nn` performs an extra check for the `keyans` and `keyanspic` environments. Unlike the check executed by `check-ans` key this one is not controlled by any key, it is intended to prevent the forgetting of `\item*` or `\anspic*` in these environments.

```

1955 \cs_new_protected:Npn \__enumext_keyans_check_ans:nn #1 #2
1956 {
1957     \tl_if_empty:NTF \g__enumext_check_ans_item_tl
1958     {
1959         \msg_warning:nnnn { enumext } { missing-starred }{ #1 }{ #2 }
1960     }
1961     { \tl_gclear:N \g__enumext_check_ans_item_tl }
1962 }

```

(End of definition for `__enumext_keyans_check_ans:nn`.)

10.25.5 The show-ans and show-pos keys for keyans and keyanspic

The code is very similar to the `\anskey` code, but, if I change the order of the operations the counter off `<label>` are incorrect.

`__enumext_keyans_show_left:n`

Common function to show *starred commands* `\item*` and `<position>` of stored content in `<prop list>` for `keyans` and `keyanspic`. Need add 1 to `\l__enumext_show_position_bool` for `keyans` environment.

```

1963 \cs_new_protected:Npn \__enumext_keyans_show_left:n #1
1964 {
1965     \bool_if:NT \l__enumext_show_answer_bool
1966     {
1967         \tl_put_left:Nn \l__enumext_label_v_tl
1968         {
1969             \__enumext_print_keyans_box:NN
1970             \l__enumext_labelwidth_i_dim
1971             \l__enumext_labelsep_i_dim
1972         }
1973         \tl_if_novalue:nF { #1 }
1974         { \tl_put_right:Nn \l__enumext_label_v_tl { \c_space_tl [ #1 ] } }
1975     }
1976     \bool_if:NT \l__enumext_show_position_bool
1977     {
1978         \tl_set:Ne \l__enumext_mark_answer_sym_tl
1979         {
1980             \group_begin:
1981             \exp_not:N \normalfont
1982             \exp_not:N \footnotesize [ \int_eval:n
1983             {
1984                 \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } + \c_one_int
1985             }
1986             ]
1987             \group_end:
1988         }
1989         \tl_put_left:Nn \l__enumext_label_v_tl
1990         {
1991             \__enumext_print_keyans_box:NN
1992             \l__enumext_labelwidth_i_dim
1993             \l__enumext_labelsep_i_dim
1994         }
1995         \tl_if_novalue:nF { #1 }
1996         { \tl_put_right:Nn \l__enumext_label_v_tl { \c_space_tl [ #1 ] } }
1997     }
1998 }

```

(End of definition for `__enumext_keyans_show_left:n`.)

10.26 Setting `item-sym*` and `item-pos*` keys

In order to have a cleaner implementation of `\item*` it is best to define a couple of keys that allow us to control and set by default the `\symbol` and its `\offset`.

```

item-sym* Define and set item-sym* and item-pos* keys for enumext and enumext*.
item-pos*
1999 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
2000 {
2001   \keys_define:nn { enumext / #1 }
2002   {
2003     item-sym* .tl_set:c = { l__enumext_item_symbol_#2_tl },
2004     item-sym* .value_required:n = true,
2005     item-sym* .initial:n = { $\star$ },
2006     item-pos* .dim_set:c = { l__enumext_item_symbol_sep_#2_dim },
2007     item-pos* .value_required:n = true,
2008   }
2009 }
2010 \clist_map_inline:nn
2011 {
2012   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {enumext*}{vii}
2013 }
2014 { \__enumext_tmp:nn #1 }
```

(End of definition for `item-sym*` and `item-pos*`.)

10.27 Redefining `\footnote` command

`__enumext_footnotetext:nn` To keep the correct numbering of `\footnote` and to make it work correctly with the `mini-env` key and in the `enumext*` and `keyans*` environments, it is necessary to redefine the command. This implementation is adapted from the answer given by Clea F. Rees (@cfr) in [footnotes in boxes compatible with hyperref](#).

```

2015 \cs_new_protected:Nn \__enumext_footnotetext:nn
2016 {
2017   \footnotetext[#1]{#2}
2018 }
2019 \cs_new_protected:Nn \__enumext_renew_footnote:
2020 {
2021   \seq_gclear:N \g__enumext_footnote_arg_seq
2022   \seq_gclear:N \g__enumext_footnote_int_seq
2023   \RenewDocumentCommand \footnote { o +m }
2024   {
2025     \tl_if_novalue:nTF {##1}
2026     {
2027       \stepcounter{footnote}
2028       \int_gset_eq:Nc \g__enumext_footnote_int { c@footnote }
2029     }
2030     {
2031       \int_gset:Nn \g__enumext_footnote_int { ##1 }
2032     }
2033     \footnotemark [ \g__enumext_footnote_int ]
2034     \seq_gput_right:Nn \g__enumext_footnote_arg_seq { ##2 }
2035     \seq_gput_right:NV \g__enumext_footnote_int_seq \g__enumext_footnote_int
2036   }
2037 }
2038 \cs_new_protected:Nn \__enumext_print_footnote:
2039 {
2040   \seq_if_empty:NF \g__enumext_footnote_int_seq
2041   {
2042     \seq_map_pairwise_function:NNN
2043     \g__enumext_footnote_int_seq
2044     \g__enumext_footnote_arg_seq
2045     \__enumext_footnotetext:nn
2046   }
2047 }
```

(End of definition for `__enumext_footnotetext:nn`, `__enumext_renew_footnote:`, and `__enumext_print_footnote:`.)

10.28 Redefining `\item` command

Redefining the `\item` command is not as simple as I thought. This command works in conjunction with the `\makeLabel` command so I have to redefine both of them, in addition to this, we will have to use a couple of *global* variables to pass the values from one command to the other.

10.28.1 The `\item` command in enumext

`__enumext_default_item:n`

The `\item` and `\item[<custom>]` commands work in the usual way on `enumext`.

First we will see if the optional argument is present, if it is NOT present we will check the state of the variable `\l__enumext_check_ans_bool` set by the key `check-ans`, set the boolean variable `\l__enumext_wrap_label_X_bool` to “true” and execute `__enumext_item_std:w`.

Otherwise we will check the state of the boolean variable `\l__enumext_wrap_label_opt_X_bool` set by the key `wrap-label*` and execute `__enumext_item_std:w` with the optional argument.

The boolean variable `\l__enumext_wrap_label_X_bool` is used by the function `__enumext_make_label: (§10.29)`.

```

2048 \cs_new_protected:Npn \__enumext_default_item:n #1
2049 {
2050   \tl_if_novalue:nTF {#1}
2051   {
2052     \bool_if:NT \l__enumext_check_ans_bool
2053     {
2054       \int_gincr:N \g__enumext_count_item_number_int
2055     }
2056     \bool_set_true:c { \l__enumext_wrap_label_ \__enumext_level: _bool }
2057     \__enumext_item_std:w \tl_use:c { \l__enumext_fake_item_indent_ \__enumext_level: _tl }
2058   }
2059   {
2060     \bool_set_eq:cc
2061     { \l__enumext_wrap_label_ \__enumext_level: _bool }
2062     { \l__enumext_wrap_label_opt_ \__enumext_level: _bool }
2063     \__enumext_item_std:w [#1] \tl_use:c { \l__enumext_fake_item_indent_ \__enumext_level: _tl }
2064   }
2065 }

```

(End of definition for `__enumext_default_item:n`.)

`__enumext_starred_item:nn`

The `\item*`, `\item*[<symbol>]` and `\item*[<symbol>][<offset>]` works like the numbered `\item`, but placing a `[<symbol>]` to the “left” of the `<label>` separated from it by the value set by the `labelsep` key and can be *offset* using the second optional argument `[<offset>]`.

#1: `\l__enumext_item_symbol_X_tl`

#2: `\l__enumext_item_symbol_sep_X_dim`

First we will make a copy of `\l__enumext_item_symbol_X_tl` which is set by the key `item-sym*` or passed as optional argument in the global variable `\g__enumext_item_symbol_tl`, followed by setting the variable `\l__enumext_item_symbol_sep_X_dim` set by the key `item*-sep` or by the second optional argument.

Then we will see the state of the variable `\l__enumext_check_ans_bool` set by the key `check-ans`, set the boolean variable `\l__enumext_wrap_label_X_bool` to “true” and execute `__enumext_item_std:w`.

In this function the optional argument of `__enumext_item_std:w` is omitted, we only want it to be numbered.

The boolean variable `\l__enumext_wrap_label_X_bool` and the vars `\l__enumext_item_symbol_sep_X_dim`, `\g__enumext_item_symbol_tl` are used by the function `__enumext_make_label: (§10.29)`.

```

2066 \cs_new_protected:Npn \__enumext_starred_item:nn #1 #2
2067 {
2068   \tl_if_novalue:nF {#1}
2069   {
2070     \tl_set:cn { \l__enumext_item_symbol_ \__enumext_level: _tl } {#1}
2071   }
2072   \tl_gset_eq:Nc \g__enumext_item_symbol_tl { \l__enumext_item_symbol_ \__enumext_level: _tl }
2073   \tl_if_novalue:nTF {#2}
2074   {
2075     \dim_set_eq:cc
2076     { \l__enumext_item_symbol_sep_ \__enumext_level: _dim }
2077     { \l__enumext_labelsep_ \__enumext_level: _dim }
2078   }
2079   {
2080     \dim_set:cn { \l__enumext_item_symbol_sep_ \__enumext_level: _dim } {#2}
2081   }
2082   \bool_if:NT \l__enumext_check_ans_bool
2083   {
2084     \int_gincr:N \g__enumext_count_item_number_int

```

```

2085     }
2086     \bool_set_true:c { \__enumext_wrap_label_ \__enumext_level: _bool }
2087     \__enumext_item_std:w \tl_use:c { \__enumext_fake_item_indent_ \__enumext_level: _tl }
2088 }

```

(End of definition for __enumext_starred_item:nn.)

`__enumext_redefine_item:` The function `__enumext_redefine_item:` will redefine the `\item` command in the `enumext` environment for the internal mechanism of check-answers for `check-ans` key and adding the starred `\item*` version.

This function is passed to `__enumext_list_arg_two_X:` which is used in the definition of the `enumext` environment (§10.31).

```

2089 \cs_new_protected:Nn \__enumext_redefine_item:
2090 {
2091     \RenewDocumentCommand \item { s o o }
2092     {
2093         \bool_if:nTF {##1}
2094         {
2095             \__enumext_starred_item:nn {##2} {##3}
2096         }
2097         { \__enumext_default_item:n {##2} }
2098     }
2099 }

```

(End of definition for __enumext_redefine_item:.)

10.28.2 The `\item` command in keyans

The `\item*` and `\item*[\langle content \rangle]` commands store the current `\label` next to the `[\langle content \rangle]` if it is present in the `\sequence` and `\prop list` defined by `save-ans` key.

`__enumext_keyans_default_item:n` The function `__enumext_keyans_default_item:n` executes the original behavior of the `\item`.

```

2100 \cs_new_protected:Npn \__enumext_keyans_default_item:n #1
2101 {
2102     \tl_if_novalue:nTF { #1 }
2103     {
2104         \bool_set_true:N \l__enumext_wrap_label_v_bool
2105         \__enumext_item_std:w \tl_use:N \l__enumext_fake_item_indent_v_tl
2106     }
2107     {
2108         \bool_set_eq:NN \l__enumext_wrap_label_v_bool \l__enumext_wrap_label_opt_v_bool
2109         \__enumext_item_std:w [#1] \tl_use:N \l__enumext_fake_item_indent_v_tl
2110     }
2111 }

```

(End of definition for __enumext_keyans_default_item:n.)

`__enumext_keyans_starred_item:n` The function `__enumext_keyans_starred_item:n` which will make a temporary copy of the current `\label`, execute the `show-ans` or `show-pos` keys using the function `__enumext_keyans_show_left:n` and will display the contents of that item using the internal copy `__enumext_item_std:w`, this is necessary to prevent incrementing the current “counter” of the original `\label`.

```

2112 \cs_new_protected:Npn \__enumext_keyans_starred_item:n #1
2113 {
2114     \tl_set_eq:NN \l__enumext_keyans_tmpa_tl \l__enumext_label_v_tl
2115     \__enumext_keyans_show_left:n { #1 }
2116     \bool_set_true:N \l__enumext_wrap_label_v_bool
2117     \__enumext_item_std:w \tl_use:N \l__enumext_fake_item_indent_v_tl

```

Recover the original value of the current `\label` and store it first in the `\prop list` (including the optional argument), run the internal “label and ref” system if the `store-ref` key is active and finally store it in the `\sequence`.

```

2118     \tl_set_eq:NN \l__enumext_label_v_tl \l__enumext_keyans_tmpa_tl
2119     \__enumext_keyans_addto_prop:n { #1 }
2120     \__enumext_keyans_store_ref:
2121     \__enumext_keyans_addto_seq:n { #1 }
2122 }

```

(End of definition for __enumext_keyans_starred_item:n.)

`\item*` The function `__enumext_keyans_redefine_item:` is responsible for adding the *starred* and *optional* argument by the `__enumext_list_arg_two_v:` function in the definition of the `keyans` environment. Here we need to use `\peek_remove_spaces:n` to prevent an unwanted space when using `\item*` in conjunction with the `itemindent` key.

This function is passed to `__enumext_list_arg_two_v:` which is used in the definition of the `keyans` environment (§10.31).

```

2123 \cs_new_protected:Nn \__enumext_keyans_redefine_item:
2124 {
2125   \RenewDocumentCommand \item { s o }
2126   {
2127     \bool_if:nTF {##1}
2128     {
2129       \peek_remove_spaces:n
2130       {
2131         \__enumext_keyans_starred_item:n {##2}
2132       }
2133     }
2134     {
2135       \__enumext_keyans_default_item:n {##2}
2136     }
2137   }
2138 }

```

(End of definition for `\item*` and `__enumext_keyans_redefine_item:`. This function is documented on page 11.)

10.29 Redefining `\makeLabel` command

Redefine `\makeLabel` for the keys `align`, `font`, `wrap-label`, `wrap-label*` and `\item*` for `enumext` and `keyans` environments.

10.29.1 Redefining `\makeLabel` for `enumext`

`__enumext_item_starred:` The function `__enumext_item_starred:` will be responsible for executing `\item*` for the `enumext` environment.

```

2139 \cs_new_protected:Nn \__enumext_item_starred:
2140 {
2141   \tl_if_empty:cF { \__enumext_item_symbol_ \__enumext_level: _tl }
2142   {
2143     \mode_leave_vertical:
2144     \skip_horizontal:n { -\dim_use:c { \__enumext_item_symbol_sep_ \__enumext_level: _dim } }
2145     \makebox[ 0pt ][ r ]{ \g__enumext_item_symbol_tl }
2146     \skip_horizontal:n { \dim_use:c { \__enumext_item_symbol_sep_ \__enumext_level: _dim } }
2147   }
2148 }

```

(End of definition for `__enumext_item_starred:`.)

`__enumext_make_label:` The function `__enumext_make_label:` redefine `\makeLabel` for the `enumext` environment.

This function is passed to `__enumext_list_arg_two_X:` which is used in the definition of the `enumext` environment (§10.31).

```

2149 \cs_new_protected:Nn \__enumext_make_label:
2150 {
2151   \RenewDocumentCommand \makeLabel { m }
2152   {
2153     \tl_use:c { \__enumext_label_fill_left_ \__enumext_level: _tl }
2154     \tl_use:c { \__enumext_label_font_style_ \__enumext_level: _tl }
2155     \bool_if:cTF { \__enumext_wrap_label_ \__enumext_level: _bool }
2156     {
2157       \__enumext_item_starred:
2158       \use:c { __enumext_wrapper_label_ \__enumext_level: :n } { ##1 }
2159     }
2160     { ##1 }
2161     \tl_use:c { \__enumext_label_fill_right_ \__enumext_level: _tl }
2162     \tl_gclear:N \g__enumext_item_symbol_tl
2163   }
2164 }

```

(End of definition for `__enumext_make_label:`.)

10.29.2 Redefining `\makeLabel` for `keyans`

`__enumext_keyans_make_label:` The function `__enumext_keyans_make_label:` redefine `\makeLabel` for `keyans` environment. This function is passed to `__enumext_list_arg_two_v:` which is used in the definition of the `keyans` environment (§10.31).

```

2165 \cs_new_protected:Nn \__enumext_keyans_make_label:
2166 {
2167   \RenewDocumentCommand \makeLabel { m }
2168   {
2169     \tl_use:N \l__enumext_label_fill_left_v_tl
2170     \tl_use:N \l__enumext_label_font_style_v_tl
2171     \bool_if:NTF \l__enumext_wrap_label_v_bool
2172     {
2173       \__enumext_wrapper_label_v:n { ##1 }
2174     }
2175     { ##1 }
2176     \tl_use:N \l__enumext_label_fill_right_v_tl
2177   }
2178 }

```

(End of definition for `__enumext_keyans_make_label:`.)

10.30 Calculation of `\leftmargin` and `\itemindent`

Consider the figure 9 where the default margins (on the left) of a list are represented.




Figure 9: Representation of standard horizontal lengths in `list` environment.

The idea is to have control over these margins so that our list does not overlap the left margin of the page. The *key* relationship is that the right edge of the `\labelsep` equals the right edge of the `\itemindent`, so that the left edge of the *label box* is at `\leftmargin + \itemindent` minus `\labelwidth + \labelsep`. Thus, the handling of the margins by the package will be as shown in the figure 10.




Figure 10: Representation of horizontal lengths concept in list in `enumext`.

Where the default values will look like in the figure 11.




Figure 11: Default horizontal lengths in `enumext`.

```

\__enumext_calc_hspace:NNNNNNN
\__enumext_calc_hspace:ccccccc

```

The function `__enumext_calc_hspace:NNNNNNN` takes seven arguments to be able to determine horizontal spaces for all list environment:

```

#1: \l__enumext_labelwidth_X_dim      #2: \l__enumext_labelsep_X_dim
#3: \l__enumext_listoffset_X_dim      #4: \l__enumext_leftmargin_tmp_X_dim
#5: \l__enumext_leftmargin_X_dim      #6: \l__enumext_itemindent_X_dim
#7: \l__enumext_leftmargin_tmp_X_bool

```

And returns the “adjusted” values of `\leftmargin` and `\itemindent`.

This function is passed to `__enumext_list_arg_two_X:` which is used in the definition of the `enumext` and `keyans` environments (§10.31).

```

2179 \cs_new_protected:Npn \__enumext_calc_hspace:NNNNNNN #1 #2 #3 #4 #5 #6 #7
2180 {
2181   \dim_compare:nNnT { #1 } < { \c_zero_dim }

```

```

2182     {
2183       \msg_warning:nnnV { enumext } { width-non-positive }{ labelwidth }{ #1 }
2184       \dim_set:Nn #1 { \dim_abs:n { #1 } }
2185     }
2186     \dim_compare:nNnT { #2 } < { \c_zero_dim }
2187     {
2188       \msg_warning:nnnV { enumext } { width-negative }{ labelsep }{ #2 }
2189       \dim_set:Nn #2 { \dim_abs:n { #2 } }
2190     }

```

If no value has been passed to the `labelwidth` and `labelsep` keys we set the default values for `\l__enumext_leftmargin_tmp_X_dim`.

```

2191     \bool_if:nF #7 { \dim_set:Nn #4 { #1 + #2 } }

```

We now analyze the cases and set the values for `\leftmargin` and `\itemindent`.

```

2192     \dim_compare:nNnTF { #4 } < { \c_zero_dim }
2193     {
2194       \dim_set:Nn #6 { #1 + #2 - #4 }
2195       \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
2196     }
2197     {
2198       \dim_compare:nNnT { #4 } = { #1 + #2 }
2199       { \dim_set:Nn #6 { \c_zero_dim } }
2200       \dim_compare:nNnT { #4 } < { #1 + #2 }
2201       { \dim_set:Nn #6 { #1 + #2 - #4 } }
2202       \dim_compare:nNnT { #4 } > { #1 + #2 }
2203       {
2204         \dim_set:Nn #6 { -#1 - #2 + #4 }
2205         \dim_set:Nn #6 { #6*-1 }
2206       }
2207       \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
2208     }
2209   }
2210   \cs_generate_variant:Nn \__enumext_calc_hspace:NNNNNNN { ccccccc }

```

(End of definition for `__enumext_calc_hspace:NNNNNNN`.)

10.31 Setting second argument of the lists

At this point of the code we have already programmed the necessary tools to create a custom `list` environment, remember that the function `__enumext_start_list:nn` takes two arguments, the first one we have ready, the second one we will define for all the levels of the environment `enumext` and the environment `keyans`.

In this function for the second list argument we will implement the keys `start`, `resume` and `show-length` together with the redefinition of `\item` for `enumext` and `keyans` environments. We will “not set” `\leftmargini`, `\leftmarginii`, `\leftmarginiii` or `\leftmarginiv`, in this case, we will directly set the parameters for vertical and horizontal list spacing per level.

```

2211   \cs_set_protected:Npn \__enumext_tmp:n #1
2212   {
2213     \cs_new_protected:cpn { __enumext_list_arg_two_#1: }
2214     {
2215       \__enumext_calc_hspace:cccccc
2216       { \__enumext_labelwidth_#1_dim } { \__enumext_labelsep_#1_dim }
2217       { \__enumext_listoffset_#1_dim } { \__enumext_leftmargin_tmp_#1_dim }
2218       { \__enumext_leftmargin_#1_dim } { \__enumext_itemindent_#1_dim }
2219       { \__enumext_leftmargin_tmp_#1_bool }
2220       \clist_map_inline:nn
2221       { labelsep, labelwidth, itemindent, leftmargin, rightmargin, listparindent }
2222       { \dim_set_eq:cc {####1} { \__enumext_####1_#1_dim } }
2223       \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
2224       { \skip_set_eq:cc {####1} { \__enumext_####1_#1_skip } }
2225       \usecounter { enumX#1 }
2226       \bool_lazy_and:nnTF
2227       { \str_if_eq_p:nn {#1} { i } }
2228       { \bool_if_p:N \__enumext_resume_bool }
2229       { \setcounter { enumXi } { \int_eval:n { \g__enumext_resume_int } } }
2230       {
2231         \setcounter { enumX#1 }
2232         { \int_eval:n { \int_use:c { \__enumext_start_#1_int } - 1 } }
2233       }
2234       \str_if_eq:nnTF {#1} { v }

```

```

2235     {
2236         \__enumext_keyans_redefine_item:
2237         \__enumext_keyans_make_label:
2238         \__enumext_keyans_fake_item:
2239         \bool_if:cT { \__enumext_show_length_#1_bool }
2240         {
2241             \msg_term:nnnn { enumext } { list-lengths-not-nested } { v } { keyans }
2242         }
2243     }
2244     {
2245         \__enumext_redefine_item:
2246         \__enumext_make_label:
2247         \__enumext_use_key_ref:
2248         \__enumext_fake_item:
2249         \bool_if:cT { \__enumext_show_length_#1_bool }
2250         {
2251             \msg_term:nnne { enumext } { list-lengths } {#1} { \int_use:N \__enumext_level\i
2252         }
2253     }
2254 }
2255 }
2256 \clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }

```

(End of definition for __enumext_list_arg_two_i: and others.)

```

\__enumext_list_arg_two_vii:
\__enumext_list_arg_two_viii:

```

For the horizontal environments `enumext*` and `keyans*` the implementation is similar, but, the value of `\partopsep` is always `\opt`. At this point we will modify the `\parsep` key to make it take the value of the `\itemsep` key and later, in the environment definition, we will modify `\parindent` to make it set the value of `\lisparindent` and `\parsep` to set the value of `\parskip` locally.

```

2257 \cs_set_protected:Npn \__enumext_tmp:n #1
2258 {
2259     \cs_new_protected:cpn { __enumext_list_arg_two_#1: }
2260     {
2261         \__enumext_calc_hspace:ccccc
2262         { \__enumext_labelwidth_#1_dim } { \__enumext_labelsep_#1_dim }
2263         { \__enumext_listoffset_#1_dim } { \__enumext_leftmargin_tmp_#1_dim }
2264         { \__enumext_leftmargin_#1_dim } { \__enumext_itemindent_#1_dim }
2265         { \__enumext_leftmargin_tmp_#1_bool }
2266         \clist_map_inline:nn
2267         { labelsep, labelwidth, itemindent, leftmargin, rightmargin, listparindent }
2268         { \dim_set_eq:cc {####1} { \__enumext_####1_#1_dim } }
2269         \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
2270         { \skip_set_eq:cc {####1} { \__enumext_####1_#1_skip } }
2271         \skip_set_eq:Nc \parsep { \__enumext_itemsep_#1_skip }
2272         \skip_zero:N \partopsep
2273         \usecounter { enumX#1 }
2274         \bool_lazy_and:nnTF
2275         { \str_if_eq_p:nn {#1} { vii } } { \bool_if_p:N \__enumext_resume_vii_bool }
2276         { \setcounter { enumXvii } { \int_eval:n { \g__enumext_resume_vii_int } } }
2277         {
2278             \setcounter { enumX#1 }
2279             { \int_eval:n { \int_use:c { \__enumext_start_#1_int } - 1 } }
2280         }
2281         \__enumext_use_key_ref_h:
2282         \str_if_eq:nnTF {#1} { vii }
2283         {
2284             \__enumext_fake_item_vii:
2285             \bool_if:cT { \__enumext_show_length_vii_bool }
2286             { \msg_term:nnnn { enumext } { list-lengths-not-nested } { vii } { enumext* } }
2287         }
2288         {
2289             \__enumext_fake_item_viii:
2290             \bool_if:cT { \__enumext_show_length_#1_bool }
2291             { \msg_term:nnnn { enumext } { list-lengths-not-nested } { #1 } { keyans* } }
2292         }
2293     }
2294 }
2295 \clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for __enumext_list_arg_two_vii: and __enumext_list_arg_two_viii:.)

10.32 The environment enumext

enumext We create the **enumext** environment based on **list** environment by levels.

```

2296 \NewDocumentEnvironment{enumext}{0}{}
2297 {
2298   \__enumext_current_env:
2299   \__enumext_safe_exec:
2300   \__enumext_parse_keys:n {#1}
2301   \__enumext_before_list:
2302   \__enumext_start_store_level:
2303   \__enumext_start_list:nn
2304   { \tl_use:c { l__enumext_label_ \__enumext_level: _tl } }
2305   {
2306     \use:c { __enumext_list_arg_two_ \__enumext_level: : }
2307     \__enumext_before_keys_exec:
2308   }
2309   \__enumext_after_args_exec:
2310 }
2311 {
2312   \__enumext_stop_list:
2313   \__enumext_stop_store_level:
2314   \__enumext_after_list:
2315 }

```

(End of definition for enumext. This function is documented on page 4.)

__enumext_safe_exec: First check the maximum nesting level for the **enumext** environment and set the state of the booleans **\l__enumext_standar_bool** and **\g__enumext_standar_bool** to “true”, the latter only if the environment is NOT nested in the **enumext*** environment.

```

2316 \cs_new_protected:Nn \__enumext_safe_exec:
2317 {
2318   \int_incr:N \l__enumext_level_int
2319   \int_compare:nNnT { \l__enumext_level_int } > { 4 }
2320   { \msg_fatal:nn { enumext } { list-too-deep } }
2321   \bool_set_true:N \l__enumext_standar_bool
2322 }

```

(End of definition for __enumext_safe_exec:.)

__enumext_parse_keys:n Parse [*key = val*] by levels in **enumext**. If the variable **\l__enumext_store_active_bool** is true it will call the function **__enumext_parse_store_keys:n** and reprocess the *keys* to pass them to the storage sequence.

```

2323 \cs_new_protected:Npn \__enumext_parse_keys:n #1
2324 {
2325   \exp_args:Ne \keys_set:nn
2326   { enumext / level-\int_use:N \l__enumext_level_int } {#1}
2327   \bool_if:NT \l__enumext_store_active_bool
2328   {
2329     \__enumext_parse_store_keys:n {#1}
2330   }
2331 }

```

(End of definition for __enumext_parse_keys:n.)

__enumext_parse_store_keys:n The function **__enumext_parse_store_keys:n** searches for the values of the **columns** and **columns-sep** keys in the optional arguments per-level in **enumext** environment as long as the starred versions of the **columns*** and **columns-sep*** keys are not active. The captured values are stored in the variable **\l__enumext_store_opt_X_tl** which is used by the function **__enumext_store_level_open:**.

```

2332 \cs_new_protected:Npn \__enumext_parse_store_keys:n #1
2333 {
2334   \bool_if:cF { l__enumext_store_columns_ \__enumext_level: _bool }
2335   {
2336     \regex_match:nnT { \b columns\b } {#1}
2337     {
2338       \int_set_eq:cc
2339       { l__enumext_store_columns_ \__enumext_level: _int }
2340       { l__enumext_columns_ \__enumext_level: _int }
2341       \tl_put_right:ce { l__enumext_store_opt_ \__enumext_level: _tl }
2342       {
2343         columns = \exp_not:v { l__enumext_store_columns_ \__enumext_level: _int },
2344       }
2345     }
2346   }

```

```

2345     }
2346   }
2347   \bool_if:cF { \__enumext_store_columns_sep_ \__enumext_level: _bool }
2348   {
2349     \regex_match:nnT { \b columns-sep \b } {#1}
2350     {
2351       \dim_set_eq:cc
2352       { \__enumext_store_columns_sep_ \__enumext_level: _dim }
2353       { \__enumext_columns_sep_ \__enumext_level: _dim }
2354       \tl_put_right:ce { \__enumext_store_opt_ \__enumext_level: _tl }
2355       {
2356         columns-sep = \exp_not:v { \__enumext_store_columns_sep_ \__enumext_level: _dim }
2357       }
2358     }
2359   }
2360 }

```

(End of definition for __enumext_parse_store_keys:n.)

__enumext_start_store_level: The __enumext_start_store_level: and __enumext_stop_store_level: functions activate the level saving mechanism for storage in *sequence* of the \anskey command.
 __enumext_stop_store_level: If enumext are nested in enumext* add __enumext_store_level_open: to preserve the stored structure.

```

2361 \cs_new_protected:Nn \__enumext_start_store_level:
2362 {
2363   %\bool_lazy_and:nnT
2364   %{ \__enumext_store_active_bool }
2365   %{ \bool_not_p:n { \__enumext_keyans_env_bool } }
2366   %{
2367     %\int_compare:nNnT { \__enumext_level_h_int } = { 1 }
2368     %{
2369       %\bool_set_true:c { \__enumext_store_upper_level_ \__enumext_level: _bool }
2370       %\__enumext_store_level_open:
2371     }
2372     %\int_compare:nNnT { \__enumext_level_int } > { 1 }
2373     %{
2374       \bool_set_true:c { \__enumext_store_upper_level_ \__enumext_level: _bool }
2375       \__enumext_store_level_open:
2376     }
2377   }
2378 }
2379 \cs_new_protected:Nn \__enumext_stop_store_level:
2380 {
2381   \bool_if:cT { \__enumext_store_upper_level_ \__enumext_level: _bool }
2382   {
2383     \__enumext_store_level_close:
2384   }
2385 }

```

(End of definition for __enumext_start_store_level: and __enumext_stop_store_level:.)

__enumext_before_list: The function __enumext_before_list: will add the vertical spacing on the environment if the above key is active next to the *{code}* defined by the before* key if it is active.

```

2386 \cs_new_protected:Nn \__enumext_before_list:
2387 {
2388   \__enumext_vspace_above:
2389   \__enumext_before_args_exec:

```

The function __enumext_check_ans_count: will handle the check answer mechanism, which will be activated with the check-ans key.

```

2390 \__enumext_check_ans_count:

```

When the mini-env key is active it will set the value of the __enumext_minipage_right_X_dim to be the *width* of the __enumext_mini_env* environment on the “right side”, using this value together with the value of the __enumext_minipage_hsep_X_dim set by the mini-sep key, the value of __enumext_minipage_left_X_dim will be set, which will be the *width* of __enumext_mini_env* environment on the “left side”, always having a current \linewidth as *maximum width* between them.

```

2391 \dim_compare:nNnT
2392 { \dim_use:c { \__enumext_minipage_right_ \__enumext_level: _dim } } > { \c_zero_dim }
2393 {
2394   \dim_set:cn { \__enumext_minipage_left_ \__enumext_level: _dim }

```

```

2395     {
2396         \linewidth
2397         - \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim }
2398         - \dim_use:c { l__enumext_minipage_hsep_ \__enumext_level: _dim }
2399     }

```

The boolean variable `\l__enumext_minipage_active_X_bool` will be activated and the integer variable `\g__enumext_minipage_stat_int` used by the `\miniright` command will be incremented, then the function `__enumext_mini_addvspace:` is called and the `__enumext_mini_env*` environment on the “left side” will be initialized followed by the “vertical spacing” applied to preserve the “baseline” between the *left* and *right* side environments. After these actions, the function `__enumext_multicols_start:` is called to handle the `multicols` environment.

Here we use the plain TeX macro `\nointerlineskip` to prevent baseline “glue” being added between the next pair of boxes in a *vertical list*.

```

2400     \bool_set_true:c { l__enumext_minipage_active_ \__enumext_level: _bool }
2401     \int_gincr:N \g__enumext_minipage_stat_int
2402     \__enumext_mini_addvspace:
2403     \nointerlineskip\noindent
2404     \begin{\__enumext_mini_env*}
2405     { \dim_use:c { l__enumext_minipage_left_ \__enumext_level: _dim } }
2406   }
2407   \__enumext_multicols_start:
2408 }

```

(End of definition for `__enumext_before_list:`)

`__enumext_multicols_start:` The function `__enumext_multicols_start:` will start the `multicols` environment according to the value passed by the `columns` key, then set the default value for `\columnsep` when `columns-sep=opt` and set the value of `\multicolsep` equal to zero and leave `\columnseprule` equal to zero for inner levels.

```

2409 \cs_new_protected:Nn \__enumext_multicols_start:
2410 {
2411   \int_compare:nNnT
2412   { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
2413   {
2414     \dim_compare:nNnT
2415     { \dim_use:c { l__enumext_columns_sep_ \__enumext_level: _dim } } = { \c_zero_dim }
2416     {
2417       \dim_set:cn { l__enumext_columns_sep_ \__enumext_level: _dim }
2418       {
2419         ( \dim_use:c { l__enumext_labelwidth_ \__enumext_level: _dim }
2420         + \dim_use:c { l__enumext_labelsep_ \__enumext_level: _dim }
2421         ) / \int_use:c { l__enumext_columns_ \__enumext_level: _int }
2422         - \dim_use:c { l__enumext_listoffset_ \__enumext_level: _dim }
2423       }
2424     }
2425     \dim_set_eq:Nc \columnsep { l__enumext_columns_sep_ \__enumext_level: _dim }
2426     \skip_zero:N \multicolsep
2427     \int_compare:nNnT { \l__enumext_level_int } > { 1 }
2428     {
2429       \dim_zero:N \columnseprule
2430     }
2431   }

```

We will calculate the *vertical spacing* settings for the `multicols` environment using the function `__enumext_multi_addvspace:`, apply our “vertical adjust spacing”, then start the `multicols` environment.

```

2431     \bool_if:cF { l__enumext_minipage_active_ \__enumext_level: _bool }
2432     {
2433       \__enumext_multi_addvspace:
2434     }
2435     \raggedcolumns
2436     \begin{multicols}{ \int_use:c { l__enumext_columns_ \__enumext_level: _int } }
2437   }
2438 }

```

(End of definition for `__enumext_multicols_start:`)

`__enumext_multicols_stop:` The function `__enumext_multicols_stop:` will stop the `multicols` environment. If the boolean variable `\l__enumext_minipage_active_X_bool` is false (not nested in `__enumext_mini_env*`) we will apply our “vertical adjust” spacing.

```

2439 \cs_new_protected:Nn \__enumext_multicols_stop:

```

```

2440 {
2441   \int_compare:nNt
2442   { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
2443   {
2444     \end{multicols}
2445     \bool_if:cF { l__enumext_minipage_active_ \__enumext_level: _bool }
2446     {
2447       \par\addvspace{ \skip_use:c { l__enumext_multicols_below_ \__enumext_level: _skip } }
2448     }
2449   }

```

If the `check-ans` key is active, we set the boolean variable `\g__enumext_check_ans_show_bool` to true and copy the stored name to the variable `\g__enumext_store_name_tl`. These variables will be used by the function `__enumext_after_env:n` to display the result of the internal check answer mechanism in the terminal.

```

2450   \bool_lazy_and:nnT
2451   { \l__enumext_check_ans_bool }
2452   { \bool_not_p:n { \g__enumext_starred_bool } }
2453   {
2454     \bool_gset_true:N \g__enumext_check_ans_show_bool
2455     \tl_gset:NV \g__enumext_store_name_tl \l__enumext_store_name_tl
2456   }
2457 }

```

(End of definition for `__enumext_multicols_stop:`.)

`__enumext_after_list:` The function `__enumext_after_list:` will check the state of the boolean variable `\l__enumext_minipage_active_X_bool`, if it is “true” a small test will be executed to check if we have omitted the use of `\miniright` (the `__enumext_mini_env*` environment has not been closed), then close `__enumext_mini_env*` and add the *adjusted vertical space* `\l__enumext_minipage_after_skip`, otherwise we will close the `multicols` environment.

```

2458 \cs_new_protected:Nn \__enumext_after_list:
2459 {
2460   \bool_if:cTF { l__enumext_minipage_active_ \__enumext_level: _bool }
2461   {
2462     \int_compare:nNt { \g__enumext_minipage_stat_int } = { 1 }
2463     {
2464       \msg_warning:nn { enumext } { missing-miniright }
2465       \miniright
2466     }
2467     \int_gzero:N \g__enumext_minipage_stat_int
2468     \end{\__enumext_mini_env*}
2469     \par\addvspace { \l__enumext_minipage_after_skip }
2470   }
2471   { \__enumext_multicols_stop: }

```

Now apply the `{\code}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```

2472   \__enumext_after_stop_list:
2473   \__enumext_vspace_below:

```

Finally save the *current value* of the counter in `\g__enumext_resume_int` for the `resume` key. If the `save-ans` key is active, it will create the integer variable for the `resume` key, we only have to assign it the value of the current counter.

```

2474   \bool_set_false:N \l__enumext_standar_bool
2475   \bool_gset_false:N \g__enumext_standar_bool
2476   \int_gset_eq:NN \g__enumext_resume_int \value{enumXi}
2477   \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl _int }
2478   {
2479     \int_gset_eq:cN
2480     { g__enumext_resume_ \l__enumext_store_name_tl _int }
2481     { \value{enumXi} }
2482   }
2483 }

```

(End of definition for `__enumext_after_list:`.)

As we don’t want our check to be executed `check-ans` by levels but on the complete list, we will take it out of the `enumext` environment using the “hook” function `__enumext_after_env:nn`.

```

2484 \__enumext_after_env:nn {enumext}
2485 {
2486   \bool_if:NT \g__enumext_check_ans_show_bool

```



```

2487     {
2488         \int_compare:nNnT { \l__enumext_level_int } = { 0 }
2489         {
2490             \__enumext_check_ans_active:
2491         }
2492     }
2493     \bool_gset_false:N \g__enumext_check_ans_show_bool
2494     \tl_gc_clear:N \g__enumext_store_name_tl
2495 }

```

10.33 The environment keyans

The environment `keyans` also based on lists. The main differences with the `enumext` environment are the *nesting* and the way the *answers* (choice) will be stored and checked, this environment is intended exclusively for “multiple choice questions”.

`keyans` Now we define the environment `keyans` also based on lists.

```

2496 \NewDocumentEnvironment{keyans}{0} { }
2497 {
2498     \__enumext_keyans_safe_exec:
2499     \__enumext_keyans_parse_keys:n {#1}
2500     \__enumext_before_list_v:
2501     \__enumext_start_list:nn
2502     { \tl_use:N \l__enumext_label_v_tl }
2503     {
2504         \__enumext_list_arg_two_v:
2505         \__enumext_before_keys_exec_v:
2506     }
2507     \__enumext_after_args_exec_v:
2508 }
2509 {
2510     \__enumext_keyans_check_ans:nn { item } { keyans }
2511     \__enumext_stop_list:
2512     \__enumext_after_list_v:
2513 }

```

(End of definition for `keyans`. This function is documented on page 11.)

`__enumext_keyans_safe_exec:`

The `keyans` environment will only be available if the `save-ans` key is active and can only be used at the first level within the `enumext` environment. We do not want the environment to be nested, so we will set a maximum at this point. If the conditions are not met, an error message will be returned.

```

2514 \cs_new_protected:Nn \__enumext_keyans_safe_exec:
2515 {
2516     \bool_if:NF \l__enumext_store_active_bool
2517     {
2518         \msg_error:nnnn { enumext } { wrong-place } { keyans } { save-ans }
2519     }
2520     \int_incr:N \l__enumext_keyans_level_int
2521     \bool_set_true:N \l__enumext_keyans_env_bool
2522     % Set false for interfering with enumext nested in keyans (yes, its possible and crayze)
2523     \bool_set_false:N \l__enumext_store_active_bool
2524     \int_compare:nNnT { \l__enumext_keyans_level_int } > { 1 }
2525     {
2526         \msg_error:nn { enumext } { keyans-nested }
2527     }
2528     \int_compare:nNnT { \l__enumext_level_int } > { 1 }
2529     {
2530         \msg_error:nn { enumext } { keyans-wrong-level }
2531     }
2532 }

```

(End of definition for `__enumext_keyans_safe_exec:`.)

`__enumext_keyans_parse_keys:n`

Parse [`key = val`] for `keyans` environment.

```

2533 \cs_new_protected:Npn \__enumext_keyans_parse_keys:n #1
2534 {
2535     \keys_set:nn { enumext / keyans } {#1}
2536 }

```

(End of definition for `__enumext_keyans_parse_keys:n`.)

`__enumext_before_list_v:` The function `__enumext_before_list_v:` will add the *vertical spacing above* the environment if the *above* key is active next to the *(code)* defined by the *before* key if it is active.

```

2537 \cs_new_protected:Nn \__enumext_before_list_v:
2538 {
2539   \__enumext_vspace_above_v:
2540   \__enumext_before_args_exec_v:

```

When the *mini-env* key is active it will set the value of the `\l__enumext_minipage_right_v_dim` to be the *width* of the `__enumext_mini_env*` environment on the *left side*, using this value together with the value of the `\l__enumext_minipage_hsep_v_dim` set by the *mini-sep* key, the value of `\l__enumext_minipage_left_v_dim` will be set, which will be the *width* of `__enumextt_mini_env*` environment on the *right side*, always having `\linewidth` as the maximum width between them.

```

2541   \dim_compare:nNnT { \l__enumext_minipage_right_v_dim } > { \c_zero_dim }
2542   {
2543     \dim_set:Nn \l__enumext_minipage_left_v_dim
2544     {
2545       \linewidth - \l__enumext_minipage_right_v_dim - \l__enumext_minipage_hsep_v_dim
2546     }

```

The boolean variable `\l__enumext_minipage_active_v_bool` will be activated and the integer variable `\g__enumext_minipage_stat_int` used by the `\miniright` command will be incremented, then the function `__enumext_keyans_mini_addvspace:` is called and the `__enumext_mini_env*` environment on *left side* will be initialized followed by the *vertical spacing* `\l__enumext_minipage_left_skip`. Here we use the plain TeX macro `\nointerlineskip` to prevent baseline “glue” being added between the next pair of boxes in a *vertical list*.

```

2547   \bool_set_true:N \l__enumext_minipage_active_v_bool
2548   \int_gincr:N \g__enumext_minipage_stat_int
2549   \__enumext_keyans_mini_addvspace:
2550   \nointerlineskip\noindent
2551   \begin{\__enumext_mini_env*}{ \l__enumext_minipage_left_v_dim }
2552   }

```

After these actions, the `__enumext_keyans_multicols_start:` function is called to handle the *multicols* environment.

```

2553   \__enumext_keyans_multicols_start:
2554   }

```

(End of definition for `__enumext_before_list_v:`)

`__enumext_keyans_multicols_start:` The function `__enumext_keyans_multicols_start:` will start the *multicols* environment according to the value passed by the *columns* key.

```

2555 \cs_new_protected:Nn \__enumext_keyans_multicols_start:
2556 {
2557   \int_compare:nNnT { \l__enumext_columns_v_int } > { 1 }
2558   {

```

Set the default value for `\columnsep` when *columns-sep* key is *opt*.

```

2559     \dim_compare:nNnT { \l__enumext_columns_sep_v_dim } = { \c_zero_dim }
2560     {
2561       \dim_set:Nn \l__enumext_columns_sep_v_dim
2562       {
2563         (
2564           \l__enumext_labelwidth_v_dim + \l__enumext_labelsep_v_dim
2565         ) / \l__enumext_columns_v_int
2566         - \l__enumext_listoffset_v_dim
2567       }
2568     }
2569     \dim_set_eq:NN \columnsep \l__enumext_columns_sep_v_dim

```

Then we will set the value of `\multicolsep` and `\columnseprule` equal to zero (we do not want a vertical rule in this environment).

```

2570     \skip_zero:N \multicolsep
2571     \dim_zero:N \columnseprule

```

We will calculate the *vertical spacing* settings for the *multicols* environment using the function `__enumext_keyans_multi_addvspace:` and apply our “*vertical adjust spacing*”, then start the *multicols* environment.

```

2572     \bool_if:NF \l__enumext_minipage_active_v_bool
2573     {
2574       \__enumext_keyans_multi_addvspace:
2575     }
2576     \raggedcolumns

```

```

2577     \begin{multicols}{\l__enumext_columns_v_int }
2578   }
2579 }

```

(End of definition for `__enumext_keyans_multicols_start:`)

`__enumext_keyans_multicols_stop:` The function `__enumext_keyans_multicols_stop:` will stop the `multicols` environment. If the boolean variable `\l__enumext_minipage_active_v_bool` is false (not nested in `__enumext_mini-env*`) we will apply our vertical “adjust” spacing.

```

2580 \cs_new_protected:Nn \__enumext_keyans_multicols_stop:
2581 {
2582   \int_compare:nNtT { \l__enumext_columns_v_int } > { 1 }
2583   {
2584     \end{multicols}
2585     \bool_if:NF \l__enumext_minipage_active_v_bool
2586     {
2587       \par\addvspace{ \l__enumext_multicols_below_v_skip }
2588     }
2589   }
2590 }

```

(End of definition for `__enumext_keyans_multicols_stop:`)

`__enumext_after_list_v:` The function `__enumext_after_list_v:` will check the state of the boolean variable `\l__enumext_minipage_active_v_bool`, if it is “true” a small test will be executed to check if we have omitted the use of `\miniright` (the `__enumext_mini-env*` environment has not been closed), then close `__enumext_mini-env*` and add the vertical adjustment space `\l__enumext_minipage_after_skip`, otherwise we will close the `multicols` environment.

```

2591 \cs_new_protected:Nn \__enumext_after_list_v:
2592 {
2593   \bool_if:NTF \l__enumext_minipage_active_v_bool
2594   {
2595     \int_compare:nNtT { \g__enumext_minipage_stat_int } = { 1 }
2596     {
2597       \msg_warning:nn { enumext } { missing-miniright }
2598       \miniright
2599     }
2600     \int_gzero:N \g__enumext_minipage_stat_int
2601     \end{\__enumext_mini-env*}
2602     \par\addvspace{ \l__enumext_minipage_after_skip }
2603   }
2604   { \__enumext_keyans_multicols_stop: }

```

Finally we will apply the `{\code}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```

2605   \bool_set_false:N \l__enumext_keyans_env_bool
2606   \__enumext_after_stop_list_v:
2607   \__enumext_vspace_below_v:
2608 }

```

(End of definition for `__enumext_after_list_v:`)


10.34 The environment `keyanspic` and `\anspic`

The `keyanspic` environment is a list-based environment that uses the same configuration for “*spacing*” and `\label` as the `keyans` environment, but it does not use `\item`.

The contents are passed to the environment by means of the `\anspic` command and are placed inside `minipage` environments, with the `\label` underneath, adjusting widths according to the options passed to the environment.

Again it is necessary to “adjust” the spacing, both vertical and horizontal, to obtain an output like the one shown in the figure 12.

This implementation is adapted from the answer given by Enrico Gregorio in [How to process the body of an environment and divide it by a \macro?](#).

Figure 12: Representation of the `keyanspic` spacing in `enumext`.

10.34.1 The command `\anspic`

`\anspic` The `\anspic` command take three arguments, the starred (*) versions `\anspic*` and `\anspic*[\langle content \rangle]` store the current `\label` next to the `[\langle content \rangle]` if it is present in the `\langle sequence \rangle` and `\langle prop list \rangle` defined by `save-ans` key. This command is used as a replacement for `\item` in the `keyanspic` environment.

```
2609 \NewDocumentCommand \anspic { s o +m }
2610 {
```

We check that the command is active in the `keyanspic` environment only if the `save-ans` key is present, otherwise we return an error.

```
2611   \bool_if:NF \l__enumext_store_active_bool
2612   {
2613     \msg_error:nnnn { enumext } { wrong-place } { keyanspic } { save-ans }
2614   }
2615   \int_compare:nNnT { \l__enumext_level_int } > { 1 }
2616   {
2617     \msg_error:nn { enumext } { keyanspic-wrong-level }
2618   }
2619   \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
2620   {
2621     \msg_error:nnnn { enumext } { command-wrong-place } { anspic } { keyans }
2622   }
```

The three arguments are handled by the function `__enumext_keyans_anspic_code:nnn` and stored in the sequence `\l__enumext_keyans_pic_body_seq` which is processed by the `keyanspic` environment.

```
2623   \seq_put_right:Nn \l__enumext_keyans_pic_body_seq
2624   {
2625     \__enumext_keyans_anspic_code:nnn { #1 } { #2 } { #3 }
2626   }
2627 }
```

(End of definition for `\anspic`. This function is documented on page 12.)

`__enumext_keyans_anspic_code:nnn`

The function `__enumext_keyans_anspic_code:nnn` will be in charge of handling the “counter” and `\label`, which will have the same configuration as the `keyans` environment.

```
2628 \cs_new_protected:Nn \__enumext_keyans_anspic_code:nnn
2629 {
2630   \stepcounter { enumXvi }
2631   #3 \\\
2632   \bool_if:nT { #1 }
2633   {
2634     \__enumext_keyans_addto_prop:n { #2 }
2635     \__enumext_keyans_store_ref:
2636     \__enumext_keyans_addto_seq:n { #2 }
2637     \bool_lazy_or:nnT
2638     { \l__enumext_show_answer_bool }
2639     { \l__enumext_show_position_bool }
2640     {
2641       \tl_set_eq:NN \l__enumext_label_v_tl \l__enumext_label_vi_tl
2642       \__enumext_keyans_show_left:n { #2 }
2643       \tl_set_eq:NN \l__enumext_label_vi_tl \l__enumext_label_v_tl
2644     }
2645   }
2646   \tl_use:N \l__enumext_label_font_style_v_tl
2647   \__enumext_wrapper_label_v:n { \l__enumext_label_vi_tl }
2648 }
```

(End of definition for `__enumext_keyans_anspic_code:nnn`.)

10.34.2 The environment keyanspic

`keyanspic` Now we define the environment `keyanspic` based on `list`. The optional argument [*number above, number below*] will determine the number of `minipage` environments that will be above and below separated by `\parsep+\itemsep` within it.

```
2649 \NewDocumentEnvironment{keyanspic}{ o }
2650 {
2651   \__enumext_keyans_pic_safe_exec:
2652   \__enumext_start_list:nn
2653   { }
2654   {
2655     \__enumext_keyans_pic_arg_two:
2656   }
```

We apply the “adjusted” vertical spacing above the environment

```
2657   \vspace { \__enumext_keyans_pic_above_skip }
2658 }
```

If the optional argument is not present, the number of times the `\anspic` command appears will be counted from `\l__enumext_keyans_pic_body_seq` and placed in `minipage` environments on a single line. Finally we check if `\anspic*` has been used, set the counter to zero and apply our “adjusted” vertical space below the environment.

```
2659 {
2660   \tl_if_novalue:nTF { #1 }
2661   {
2662     \__enumext_keyans_pic_do:e { \seq_count:N \l__enumext_keyans_pic_body_seq }
2663   }
2664   { \__enumext_keyans_pic_do:n { #1 } }
2665   \__enumext_stop_list:
2666   \__enumext_keyans_check_ans:nn { anspic } { keyanspic }
2667   \setcounter { enumXvi } { 0 }
2668   \vspace { \__enumext_topsep_v_skip }
2669   %\bool_set_false:N \l__enumext_store_active_bool
2670 }
```

(End of definition for `keyanspic`. This function is documented on page 12.)

`__enumext_keyans_pic_safe_exec:` The function `__enumext_keyans_pic_safe_exec:` check nested and level position inside the `enumext` environment.

```
2671 \cs_new_protected:Nn \__enumext_keyans_pic_safe_exec:
2672 {
2673   \int_incr:N \l__enumext_keyans_pic_level_int
2674   \int_compare:nNnT { \l__enumext_keyans_pic_level_int } > { 1 }
2675   {
2676     \msg_error:nn { enumext } { keyanspic-nested }
2677   }
2678 }
```

(End of definition for `__enumext_keyans_pic_safe_exec:`.)

`__enumext_keyans_pic_skip_abs:N` The function `__enumext_keyans_pic_skip_abs:N` will return a positive value `\parsep`.

```
2679 \cs_new_protected:Npn \__enumext_keyans_pic_skip_abs:N #1
2680 {
2681   \dim_compare:nNnT { #1 } < { 0pt }
2682   { \skip_set:Nn #1 { -#1 } }
2683 }
```

(End of definition for `__enumext_keyans_pic_skip_abs:N`.)

`__enumext_keyans_pic_arg_two:` The function `__enumext_keyans_pic_arg_two:` will be used in the second argument of the `__enumext_start_list:nn` function that defines the `keyanspic` environment, it will handle the setting of spaces.

```
2684 \cs_new_protected:Nn \__enumext_keyans_pic_arg_two:
2685 {
```

The first thing to do is to set the boolean variable `\l__enumext_leftmargin_tmp_v_bool` handled by the `list-indent` key to false, then we copy the definition of the second list argument from the `keyans` environment.

```
2686   \bool_set_false:N \l__enumext_leftmargin_tmp_v_bool
2687   \__enumext_list_arg_two_v:
```

We will add the value of `\itemsep` to `\parsep` which we will use as vertical spacing between the above and below `minipage` environments. and adjust the value of `\leftmargin`, the label and counter are handled directly by the `\anspic` command. Then we make equal to zero `\labelwidth`, `\labelsep`, `\partopsep` and `\itemsep` so that the horizontal and vertical spacing is not affected.

```

2688 \skip_add:Nn \parsep { \itemsep }
2689 \dim_add:Nn \leftmargin { -\labelwidth - \labelsep }
2690 \dim_zero:N \labelwidth
2691 \dim_zero:N \listparindent
2692 \dim_zero:N \labelsep
2693 \skip_zero:N \partopsep
2694 \skip_zero:N \itemsep

```

We set the value of `\l__enumxt_keyans_pic_above_skip` which we will use to apply our “adjust” space above `keyanspic`, finally we call `__enumxt_item_std:w` followed by `\scan_stop:` to prevent the error message returned by \TeX when not using the `\item` command.

```

2695 \__enumxt_keyans_pic_skip_abs:N \parsep
2696 \skip_set:Nn \l__enumxt_keyans_pic_above_skip
2697 {
2698   \box_dp:N \strutbox
2699   + \l__enumxt_topsep_v_skip
2700   - \parsep
2701 }
2702 \__enumxt_item_std:w \scan_stop:
2703 }

```

(End of definition for `__enumxt_keyans_pic_arg_two:.`)

```

\__enumxt_keyans_pic_do:n
\__enumxt_keyans_pic_do:e

```

The optional argument is split by comma and is handled directly by the function `__enumxt_keyans_pic_do:n` and passed to the function `__enumxt_keyans_pic_row:n`.

```

2704 \cs_new_protected:Nn \__enumxt_keyans_pic_do:n
2705 {
2706   \clist_map_function:nN { #1 } \__enumxt_keyans_pic_row:n
2707 }
2708 \cs_generate_variant:Nn \__enumxt_keyans_pic_do:n { e }

```

(End of definition for `__enumxt_keyans_pic_do:n`.)

```
\__enumxt_keyans_pic_row:n
```

The function `__enumxt_keyans_pic_row:n` will set the widths for the `minipage` environments and place the content $\langle stored \rangle$ by `\anspic*` in the `\l__enumxt_keyans_pic_body_seq` sequence inside them.

```

2709 \cs_new_protected:Nn \__enumxt_keyans_pic_row:n
2710 {
2711   \dim_set:Nn \l__enumxt_keyans_pic_width_dim { \linewidth / #1 }
2712   \int_set:Nn \l__enumxt_keyans_pic_above_int { \l__enumxt_keyans_pic_below_int }
2713   \int_set:Nn \l__enumxt_keyans_pic_below_int { \l__enumxt_keyans_pic_above_int + #1 }
2714   \int_step_inline:nnn
2715     { \l__enumxt_keyans_pic_above_int + 1 }
2716     { \l__enumxt_keyans_pic_below_int }
2717     {
2718       \__enumxt_minipage:w [ b ]{ \l__enumxt_keyans_pic_width_dim }
2719       \centering
2720       \seq_item:Nn \l__enumxt_keyans_pic_body_seq { ##1 }
2721       \__enumxt_endminipage:
2722     }
2723   \par
2724 }

```

(End of definition for `__enumxt_keyans_pic_row:n`.)

10.35 The enumxt* environment

Generating horizontal list environments is NOT as simple as standard \TeX list environments. The fundamental part of the code is adapted from the `shortlst` package to a more modern version using `expl3`. It is not possible to redefine `\item` and `\makelabel` as in the non starred versions (at least I have not achieved it) and as we will make it behave differently, we have no other option than to define a cascade of functions.

To achieve the horizontal list environment we will capture the `\item` command and the content of this in an plain `lrbox` box using `\makebox` for the `label` and a `minipage` environment for the content passed to `\item`, we will also add the optional argument ($\langle number \rangle$) to `\item` to be able to *join columns* horizontally, in simple terms, we want `\item` to behave in the same way as in the `enumext` environment but adding an optional first argument ($\langle number \rangle$).

10.35.1 Functions for item box width

_enumext_starred_columns_set_vii:

We set the default value for the width of the box containing the content of the items and create `\itemwidth` in a public form.

```

2725 \cs_new_protected:Nn \__enumext_starred_columns_set_vii:
2726 {
2727   \dim_compare:nNnT { \l__enumext_columns_sep_vii_dim } = { \c_zero_dim }
2728   {
2729     \dim_set:Nn \l__enumext_columns_sep_vii_dim
2730     {
2731       ( \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim )
2732       / \l__enumext_columns_vii_int
2733     }
2734   }
2735   \int_set:Nn \l__enumext_tmpa_vii_int { \l__enumext_columns_vii_int - \c_one_int }
2736   \dim_set:Nn \l__enumext_item_width_vii_dim
2737   {
2738     ( \linewidth - \l__enumext_columns_sep_vii_dim * \l__enumext_tmpa_vii_int )
2739     / \l__enumext_columns_vii_int - \l__enumext_labelwidth_vii_dim
2740     - \l__enumext_labelsep_vii_dim
2741   }
2742   \dim_zero_new:N \itemwidth
2743 }

```

(End of definition for _enumext_starred_columns_set_vii:.)

_enumext_starred_joined_item_vii:n

The function `_enumext_starred_joined_item_vii:n` will set the *width* of the box in which the content passed to `\item(<number>)` will be stored together with the value of `\itemwidth`.

```

2744 \cs_new_protected:Npn \__enumext_starred_joined_item_vii:n #1
2745 {
2746   \int_set:Nn \l__enumext_joined_item_vii_int {#1}
2747   \int_compare:nNnT { \l__enumext_joined_item_vii_int } > { \l__enumext_columns_vii_int }
2748   {
2749     \msg_warning:nnee { enumext } { item-joined }
2750     { \int_use:N \l__enumext_joined_item_vii_int }
2751     { \int_use:N \l__enumext_columns_vii_int }
2752     \int_set:Nn \l__enumext_joined_item_vii_int
2753     {
2754       \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int
2755     }
2756   }
2757   \int_compare:nNnT
2758   { \l__enumext_joined_item_vii_int }
2759   >
2760   { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int }
2761   {
2762     \msg_warning:nnee { enumext } { item-joined-columns }
2763     { \int_use:N \l__enumext_joined_item_vii_int }
2764     {
2765       \int_eval:n
2766       { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int }
2767     }
2768     \int_set:Nn \l__enumext_joined_item_vii_int
2769     {
2770       \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int
2771     }
2772   }

```

Only need if #1 >> 1 (default are set before).

```

2773   \int_compare:nNnTF { \l__enumext_joined_item_vii_int } > { \c_one_int }
2774   {
2775     \int_set_eq:NN \l__enumext_joined_item_aux_vii_int \l__enumext_joined_item_vii_int
2776     \int_decr:N \l__enumext_joined_item_aux_vii_int
2777     \int_add:Nn \l__enumext_item_column_pos_vii_int { \l__enumext_joined_item_aux_vii_int }
2778     \int_gadd:Nn \g__enumext_item_count_all_vii_int { \l__enumext_joined_item_aux_vii_int }
2779     \dim_set:Nn \l__enumext_joined_width_vii_dim
2780     {
2781       \l__enumext_item_width_vii_dim * \l__enumext_joined_item_vii_int
2782       + ( \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim
2783         + \l__enumext_columns_sep_vii_dim
2784         ) * \l__enumext_joined_item_aux_vii_int

```



```

2785     }
2786     \dim_set_eq:NN \itemwidth \l__enumext_joined_width_vii_dim
2787   }
2788   {
2789     \dim_set_eq:NN \l__enumext_joined_width_vii_dim \l__enumext_item_width_vii_dim
2790     \dim_set_eq:NN \itemwidth \l__enumext_item_width_vii_dim
2791   }
2792 }

```

(End of definition for `__enumext_starred_joined_item_vii:n`.)

`__enumext_start_mini_vii:` The implementation of the `mini-env` key support is almost identical to the one used in the `enumext` and `keyans` environments, the difference is that the `__enumext_mini_env*` environment on the “*right side*” is executed “*after*” closing the environment, so it is necessary to make a global copy of the variable `\l__enumext_minipage_right_vii_dim` in the variable `\g__enumext_minipage_right_vii_dim`.

```

2793 \cs_new_protected:Nn \__enumext_start_mini_vii:
2794 {
2795   \dim_compare:nNnT { \l__enumext_minipage_right_vii_dim } > { \c_zero_dim }
2796   {
2797     \dim_set:Nn \l__enumext_minipage_left_vii_dim
2798     {
2799       \linewidth
2800       - \l__enumext_minipage_right_vii_dim
2801       - \l__enumext_minipage_hsep_vii_dim
2802     }
2803     \bool_set_true:N \l__enumext_minipage_active_vii_bool
2804     \dim_gset_eq:NN
2805       \g__enumext_minipage_right_vii_dim
2806       \l__enumext_minipage_right_vii_dim
2807     \__enumext_mini_addvspace_vii:
2808     \nointerlineskip\nindent
2809     \begin{__enumext_mini_env*}{ \l__enumext_minipage_left_vii_dim }
2810   }
2811 }

```

(End of definition for `__enumext_start_mini_vii:`.)

`__enumext_stop_mini_vii:` The function `__enumext_stop_mini_vii:` closes the `__enumext_mini_env*` environment on the left side, applies `\hfill` and sets the value of the variable `\g__enumext_minipage_active_vii_bool` to true which will be used in the function `__enumext_after_star_env:nn` to execute the `__enumext_mini_env*` on the “*right side*”.

```

2812 \cs_new_protected:Nn \__enumext_stop_mini_vii:
2813 {
2814   \bool_if:NT \l__enumext_minipage_active_vii_bool
2815   {
2816     \end{__enumext_mini_env*}
2817     \hfill
2818     \bool_gset_true:N \g__enumext_minipage_active_vii_bool
2819   }
2820 }

```

Finally we execute code passed to the `miniright` key stored in the variable `\g__enumext_miniright_code_vii_tl` in the `__enumext_mini_env*` environment on the “*right side*”.

```

2821 \__enumext_after_env:nn {enumext*}
2822 {
2823   \bool_if:NT \g__enumext_minipage_active_vii_bool
2824   {
2825     \begin{__enumext_mini_env*}{ \g__enumext_minipage_right_vii_dim }
2826     \par\addvspace { \g__enumext_minipage_right_skip }
2827     \bool_if:NF \g__enumext_minipage_center_vii_bool
2828     {
2829       \centering
2830     }
2831     \tl_use:N \g__enumext_miniright_code_vii_tl % the code
2832     \end{__enumext_mini_env*}
2833     \par\addvspace{ \g__enumext_minipage_after_skip }
2834   }
2835   \bool_gset_false:N \g__enumext_minipage_active_vii_bool
2836   \bool_gset_true:N \g__enumext_minipage_center_vii_bool
2837   \tl_gclear:N \g__enumext_miniright_code_vii_tl
2838   \dim_gzero:N \g__enumext_minipage_right_vii_dim
2839 }

```

(End of definition for `__enumext_stop_mini_vii:`.)

`enumext*` First we will generate the environment and we will give a temporary definition to `__enumext_stop_item_tmp_vii:` equal to `\noindent` and next to `\item` equal to `__enumext_start_item_tmp_vii:` which we will redefine later.

```

2840 \NewDocumentEnvironment{enumext*}{o }
2841 {
2842   \__enumext_current_env:
2843   \__enumext_safe_exec_vii:
2844   \__enumext_parse_keys_vii:n {#1}
2845   \__enumext_before_list_vii:
2846   \__enumext_start_store_level_vii:
2847   \__enumext_start_list:nn { }
2848   {
2849     \__enumext_list_arg_two_vii:
2850     \__enumext_before_keys_exec_vii:
2851   }
2852   \__enumext_starred_columns_set_vii:
2853   \item[] \scan_stop:
2854   \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \noindent
2855   \cs_set_eq:NN \item \__enumext_start_item_tmp_vii:
2856 }
2857 {
2858   \__enumext_stop_item_tmp_vii:
2859   \__enumext_remove_extra_parsep_vii:
2860   \__enumext_stop_list:
2861   \__enumext_stop_store_level_vii:
2862   \__enumext_after_list_vii:
2863 }

```

(End of definition for `enumext*`. This function is documented on page 4.)

`__enumext_safe_exec_vii:` First check the maximum nesting level for the `enumext*` environment then set the vars `\l__enumext_starred_bool` and `\g__enumext_starred_bool`.

```

2864 \cs_new_protected:Nn \__enumext_safe_exec_vii:
2865 {
2866   \int_incr:N \l__enumext_level_h_int
2867   \int_compare:nNnT { \l__enumext_level_h_int } > { 1 }
2868   {
2869     \msg_error:nn { enumext } { nested }
2870   }
2871   \bool_set_true:N \l__enumext_starred_bool
2872 }

```

(End of definition for `__enumext_safe_exec_vii:`.)

`__enumext_parse_keys_vii:n` Parse `[<key = val>]` for `enumext*`. If the variable `\l__enumext_store_active_bool` is true it will call the function `__enumext_parse_store_keys_vii:n` and reprocess the keys to pass them to the storage sequence.

```

2873 \cs_new_protected:Npn \__enumext_parse_keys_vii:n #1
2874 {
2875   \tl_if_novalue:nF {#1}
2876   {
2877     \keys_set:nn { enumext / enumext* } {#1}
2878     \bool_if:NT \l__enumext_store_active_bool
2879     {
2880       \__enumext_parse_store_keys_vii:n {#1}
2881     }
2882   }
2883 }

```

(End of definition for `__enumext_parse_keys_vii:n`.)

`__enumext_parse_store_keys_vii:n` The function `__enumext_parse_store_keys_vii:n` searches for the values of the `columns` and `columns-sep` keys in the optional argument in `enumext*` environment as long as the starred versions of the `columns*` and `columns-sep*` keys are not active. The captured values are stored in the variable `\l__enumext_store_opt_vii_tl` which is used by the function `__enumext_store_level_open_vii:`.

```

2884 \cs_new_protected:Npn \__enumext_parse_store_keys_vii:n #1
2885 {

```

```

2886 \bool_if:NF \l__enumext_store_columns_vii_bool
2887 {
2888   \regex_match:nnT { \b columns\b } {#1}
2889   {
2890     \int_set_eq:NN
2891       \l__enumext_store_columns_vii_int
2892       \l__enumext_columns_vii_int
2893     \tl_put_right:Ne \l__enumext_store_opt_vii_tl
2894     {
2895       columns = \exp_not:V \l__enumext_store_columns_vii_int ,
2896     }
2897   }
2898 }
2899 \bool_if:NF \l__enumext_store_columns_sep_vii_bool
2900 {
2901   \regex_match:nnT { \b columns-sep\b } {#1}
2902   {
2903     \dim_set_eq:NN
2904       \l__enumext_store_columns_sep_vii_dim
2905       \l__enumext_columns_sep_vii_dim
2906     \tl_put_right:Ne \l__enumext_store_opt_vii_tl
2907     {
2908       columns-sep = \exp_not:V \l__enumext_store_columns_sep_vii_dim,
2909     }
2910   }
2911 }
2912 }

```

(End of definition for \l__enumext_parse_store_keys_vii:n.)

`__enumext_before_list_vii:` The function `__enumext_before_list_vii:` will add the vertical spacing on the environment if the `above` key is active next to the `{\code}` defined by the `before*` key if it is active, the call the function `__enumext_start_mini_vii:` handle by `mini-env`.

```

2913 \cs_new_protected:Nn \__enumext_before_list_vii:
2914 {
2915   \__enumext_vspace_above_vii:
2916   \__enumext_check_ans_count: % need by chek-ans
2917   \__enumext_before_args_exec_vii:
2918   \__enumext_start_mini_vii:
2919 }

```

(End of definition for __enumext_before_list_vii:.)

`__enumext_after_list_vii:` The function `__enumext_after_list:` first call the function `__enumext_stop_mini_vii:`, then apply the `{\code}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present. Finally set false the vars `\g__enumext_starred_bool` and `\l__enumext_starred_bool`, save the *current value* of the counter in `\g__enumext_resume_vii_int` for the `resume` key. If the `save-ans` key is active, it will create the integer variable for the `resume` key, we only have to assign it the value of the current counter.

```

2920 \cs_new_protected:Nn \__enumext_after_list_vii:
2921 {
2922   \__enumext_stop_mini_vii:
2923   \__enumext_after_stop_list_vii:
2924   \__enumext_vspace_below_vii:
2925   \int_gset_eq:NN \g__enumext_resume_vii_int \value{enumXvii}
2926   \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl _int }
2927   {
2928     \int_gset_eq:cN
2929       { g__enumext_resume_ \l__enumext_store_name_tl _int }
2930     { \value{enumXvii} }
2931   }
2932   \bool_lazy_and:nnT { \g__enumext_starred_bool } { \l__enumext_check_ans_bool }
2933   {
2934     \bool_gset_true:N \g__enumext_check_ans_show_h_bool
2935     \tl_gset:NV \g__enumext_store_name_tl \l__enumext_store_name_tl
2936   }
2937   \bool_gset_false:N \g__enumext_starred_bool
2938   \bool_set_false:N \l__enumext_starred_bool
2939 }

```

(End of definition for __enumext_after_list_vii:.)

__enumext_start_store_level_vii:
 __enumext_stop_store_level_vii:

The __enumext_start_store_level_vii: and __enumext_stop_store_level_vii: functions activate the level saving mechanism for storage in *(sequence)* of the \anskey command if enumext* are nested in enumext.

```

2940 \cs_new_protected:Nn \__enumext_start_store_level_vii:
2941 {
2942   \bool_if:NT \l__enumext_store_active_bool
2943   {
2944     \int_compare:nNt { \l__enumext_level_int } > { \c_zero_int }
2945     {
2946       \__enumext_store_level_open_vii:
2947     }
2948   }
2949 }
2950 \cs_new_protected:Nn \__enumext_stop_store_level_vii:
2951 {
2952   \bool_if:NT \l__enumext_store_active_bool
2953   {
2954     \int_compare:nNt { \l__enumext_level_int } > { \c_zero_int }
2955     {
2956       \__enumext_store_level_close_vii:
2957     }
2958   }
2959 }
```

(End of definition for __enumext_start_store_level_vii: and __enumext_stop_store_level_vii:.)

10.35.2 The command \item in enumext*

__enumext_start_item_tmp_vii:

First we will call the function __enumext_stop_item_tmp_vii: that we will redefine later, we will increment the value of \l__enumext_item_column_pos_vii_int that will count the item's by rows and the value of \g__enumext_item_count_all_vii_int that will count the total of item's in the environment. After that we will call the function __enumext_item_peek_args_vii: that will handle the arguments passed to \item.

```

2960 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_vii:
2961 {
2962   \__enumext_stop_item_tmp_vii:
2963   \int_incr:N \l__enumext_item_column_pos_vii_int
2964   \int_gincr:N \g__enumext_item_count_all_vii_int
2965   \__enumext_item_peek_args_vii:
2966 }
```

(End of definition for __enumext_start_item_tmp_vii:.)

__enumext_item_peek_args_vii:

The function __enumext_item_peek_args_vii: will handle the \item(*(number)*). Look for the argument “(”, if it is present we will call the function __enumext_joined_item_vii:w (*(number)*), which is in charge of joining the item's in the same row, in case they are not present we will set the default value (1).

```

2967 \cs_new_protected:Nn \__enumext_item_peek_args_vii:
2968 {
2969   \peek_meaning:NTF (
2970     { \__enumext_joined_item_vii:w }
2971     { \__enumext_joined_item_vii:w (1) }
2972   }
```

(End of definition for __enumext_item_peek_args_vii:.)

__enumext_joined_item_vii:w

The function __enumext_joined_item_vii:w will first call the function __enumext_starred_joined_item_vii:n in charge of setting the *width* of the box that will store the content passed to \item. Then we will look for the argument “*”, if it is present we will call the function __enumext_starred_item_vii:w otherwise we will call the function __enumext_standard_item_vii:w.

```

2973 \cs_new_protected:Npn \__enumext_joined_item_vii:w (#1)
2974 {
2975   \__enumext_starred_joined_item_vii:n {#1}
2976   \peek_meaning_remove:NTF *
2977   { \__enumext_starred_item_vii:w }
2978   { \__enumext_standard_item_vii:w }
2979 }
```

(End of definition for __enumext_joined_item_vii:w.)

__enumext_standard_item_vii:w

The function __enumext_standard_item_vii:w will first look for the argument “[”, if present it will set the state of the variable \l__enumext_wrap_label_opt_vii_bool equal to the state of the variable \l__enumext_wrap_label_opt_vii_bool handled by the key `wrap-label*` and finally execute the *non-enumerated* version `\item[⟨custom⟩]` by means of the function __enumext_start_item_vii:w, otherwise we will set the value of the variable \l__enumext_wrap_label_vii_bool handled by the `wrap-label` key to true and set the switch \if@noitemarg to true to execute the enumerated version of `\item` by means of the function __enumext_start_item_vii:w [\l__enumext_label_vii_tl].

```
2980 \cs_new_protected:Npn \__enumext_standard_item_vii:w
2981 {
2982   \bool_set_false:N \l__enumext_item_starred_vii_bool
2983   \peek_meaning:NTF [
2984     {
2985       \bool_set_eq:NN
2986         \l__enumext_wrap_label_vii_bool
2987         \l__enumext_wrap_label_opt_vii_bool
2988       \__enumext_start_item_vii:w
2989     }
2990     {
2991       \bool_set_true:N \l__enumext_wrap_label_vii_bool
2992       \legacy_if_set_true:n { @noitemarg }
2993       \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
2994     }
2995   }
```

(End of definition for __enumext_standard_item_vii:w.)

__enumext_starred_item_vii:w
 __enumext_starred_item_vii_aux_i:w
 __enumext_starred_item_vii_aux_ii:w
 __enumext_starred_item_vii_aux_iii:w

The function __enumext_starred_item_vii:w together with the specified auxiliary functions `aux_i:w`, `aux_ii:w`, and `aux_iii:w` execute `\item*`, `\item*[⟨symbol⟩]` and `\item*[⟨symbol⟩][⟨offset⟩]`.

```
2996 \cs_new_protected:Npn \__enumext_starred_item_vii:w
2997 {
2998   \bool_set_true:N \l__enumext_item_starred_vii_bool
2999   \bool_set_true:N \l__enumext_wrap_label_vii_bool
3000   \peek_meaning:NTF [
3001     { \__enumext_starred_item_vii_aux_i:w }
3002     { \__enumext_starred_item_vii_aux_ii:w }
3003   }
3004   \cs_new_protected:Npn \__enumext_starred_item_vii_aux_i:w [#1]
3005   {
3006     \tl_gset:Nn \g__enumext_item_symbol_aux_vii_tl {#1}
3007     \__enumext_starred_item_vii_aux_ii:w
3008   }
3009   \cs_new_protected:Npn \__enumext_starred_item_vii_aux_ii:w
3010   {
3011     \peek_meaning:NTF [
3012       { \__enumext_starred_item_vii_aux_iii:w }
3013       {
3014         \dim_set_eq:NN
3015           \l__enumext_item_symbol_sep_vii_dim
3016           \l__enumext_labelsep_vii_dim
3017         \legacy_if_set_true:n { @noitemarg }
3018         \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
3019       }
3020     }
3021   \cs_new_protected:Npn \__enumext_starred_item_vii_aux_iii:w [#1]
3022   {
3023     \dim_set:Nn \l__enumext_item_symbol_sep_vii_dim {#1}
3024     \legacy_if_set_true:n { @noitemarg }
3025     \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
3026   }
```

(End of definition for __enumext_starred_item_vii:w and others.)

10.35.3 Real definition of \item in enumext*

__enumext_start_item_vii:w

The functions __enumext_start_item_vii:w and __enumext_stop_item_vii: executing the true definition of `\item` inside the `enumext*` environment.

The first thing we will do is set the value of __enumext_stop_item_tmp_vii: equal to the value of __enumext_stop_item_vii: which we will define later and add the `hyperref` compatible `enumxvii` counter, after that we will start capturing the item content in a box. Here need setting the \if@hyper@item

switch to “true” for `hyperref` compatible. The explanation for this is given by the master Heiko Oberdiek on `\refstepcounter{enumi}` twice (or more) creates destination with the same identifier.

```

3027 \cs_new_protected_nopar:Npn \__enumext_start_item_vii:w [#1]
3028 {
3029   \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \__enumext_stop_item_vii:
3030   \legacy_if:nT { @noitemarg }
3031   {
3032     \legacy_if_set_false:n { @noitemarg }
3033     \legacy_if:nT { @nmbrlist }
3034     {
3035       \bool_if:NT \l__enumext_hyperref_bool
3036       {
3037         \legacy_if_set_true:n { @hyper@item }
3038       }
3039       \refstepcounter{enumXvii}
3040       \bool_if:NT \l__enumext_check_ans_bool
3041       {
3042         \int_gincr:N \g__enumext_count_item_number_int
3043       }
3044     }
3045   }

```

Here we start capturing `\item` and its contents into a group using the plain form of the `lrbox` environment. If the state of the variable `\l__enumext_footnotes_key_bool` is false, we will redefine the command `\footnote`, followed by printing the $\langle symbol \rangle$ defined for `\item*` if it is present and open a new group inside which we execute `font key` next to `\item` and the keys `wrap-label`, `wrap-label*`, `align`, close the group and execute the key `labelsep` and then the key `first`. Finally we open the `minipage` environment and execute the `listparindent` key which will be equal to `\parindent`, the `parsep` key which will be equal to `\parskip` and the `itemindent` key.

```

3046   \group_begin:
3047   \lrbox{ \l__enumext_item_text_vii_box }
3048   \bool_if:NF \l__enumext_footnotes_key_bool
3049   {
3050     \__enumext_renew_footnote:
3051   }
3052   \bool_if:NT \l__enumext_item_starred_vii_bool
3053   {
3054     \tl_if_blank:VT \g__enumext_item_symbol_aux_vii_tl
3055     {
3056       \tl_gset_eq:NN
3057       \g__enumext_item_symbol_aux_vii_tl \l__enumext_item_symbol_vii_tl
3058     }
3059     \mode_leave_vertical:
3060     \skip_horizontal:n { -\l__enumext_item_symbol_sep_vii_dim }
3061     \makebox[ 0pt ][ r ]{ \g__enumext_item_symbol_aux_vii_tl }
3062     \skip_horizontal:N \l__enumext_item_symbol_sep_vii_dim
3063     \tl_gclear:N \g__enumext_item_symbol_aux_vii_tl
3064   }
3065   \group_begin:
3066   \tl_use:N \l__enumext_label_font_style_vii_tl
3067   \bool_if:NTF \l__enumext_wrap_label_vii_bool
3068   {
3069     \makebox[ \l__enumext_labelwidth_vii_dim ][ \l__enumext_align_label_vii_str ]
3070     { \__enumext_wrapper_label_vii:n {#1} }
3071   }
3072   {
3073     \makebox[ \l__enumext_labelwidth_vii_dim ][ \l__enumext_align_label_vii_str ]{ #1 }
3074   }
3075   \group_end:
3076   \skip_horizontal:N \l__enumext_labelsep_vii_dim
3077   \tl_use:N \l__enumext_after_list_args_vii_tl
3078   \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_vii_dim }
3079   \skip_set_eq:NN \parindent \l__enumext_listparindent_vii_dim
3080   \skip_set_eq:NN \parskip \l__enumext_parsep_vii_skip
3081   \tl_use:N \l__enumext_fake_item_indent_vii_tl
3082 }

```

(End of definition for `__enumext_start_item_vii:w`.)

`__enumext_stop_item_vii:` The function `__enumext_stop_item_vii:` shall terminate with the capture of `\item` and its $\langle contents \rangle$. Close the environments `minipage`, `lrbox` and the group. Then we only have to set the width of the box

and print it next to `\footnote`, and add the horizontal and vertical separation between the boxes.

```

3083 \cs_new_protected_nopar:Nn \__enumext_stop_item_vii:
3084 {
3085     \__enumext_endminipage:
3086     \endlrbox
3087     \group_end:
3088     \box_set_wd:Nn \l__enumext_item_text_vii_box
3089     {
3090         \l__enumext_joined_width_vii_dim
3091         + \l__enumext_labelwidth_vii_dim
3092         + \l__enumext_labelsep_vii_dim
3093     }
3094     \int_set:Nn \hbadness { 10000 }
3095     \box_use:N \l__enumext_item_text_vii_box
3096     \bool_if:NF \l__enumext_footnotes_key_bool
3097     {
3098         \__enumext_print_footnote:
3099     }
3100     \int_compare:nNnTF { \l__enumext_item_column_pos_vii_int } = { \l__enumext_columns_vii_int }
3101     {
3102         \par\noindent
3103         \int_zero:N \l__enumext_item_column_pos_vii_int
3104     }
3105     { \hspace{ \l__enumext_columns_sep_vii_dim } }
3106 }

```

(End of definition for `__enumext_stop_item_vii:`.)

`__enumext_remove_extra_parsep_vii:`

Finally we will remove the vertical space equal to `\parsep` when the total number of items is divisible by the number of items in the last row of the environment.

```

3107 \cs_new_protected:Nn \__enumext_remove_extra_parsep_vii:
3108 {
3109     \int_compare:nNnT
3110     {
3111         \int_mod:nn { \g__enumext_item_count_all_vii_int } { \l__enumext_columns_vii_int }
3112     }
3113     =
3114     { \c_zero_int }
3115     {
3116         \par
3117         \vspace{ -\l__enumext_itemsep_vii_skip }
3118         \int_gzero:N \g__enumext_item_count_all_vii_int
3119     }
3120 }

```

(End of definition for `__enumext_remove_extra_parsep_vii:`.)

As we don't want our check to be executed `check-ans` by levels but on the complete list, we will take it out of the `enumext*` environment using the “hook” function `__enumext_after_env:nn`.

```

3121 \__enumext_after_env:nn {enumext*}
3122 {
3123     \bool_if:NT \g__enumext_check_ans_show_h_bool
3124     {
3125         \int_compare:nNnT { \l__enumext_level_int } = { 0 }
3126         {
3127             \__enumext_check_ans_active:
3128         }
3129     }
3130     \bool_gset_false:N \g__enumext_check_ans_show_h_bool
3131     \tl_gclear:N \g__enumext_store_name_tl
3132 }

```

10.36 The `keyans*` environment

10.36.1 Functions for item box width

`__enumext_starred_columns_set_viii:`

We set the default value for the width of the box containing the content of the items and create `\itemwidth` in a public form.

```

3133 \cs_new_protected:Nn \__enumext_starred_columns_set_viii:
3134 {
3135     \dim_compare:nNnT { \l__enumext_columns_sep_viii_dim } = { \c_zero_dim }
3136     {

```



```

3137         \dim_set:Nn \l__enumext_columns_sep_viii_dim
3138         {
3139             ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim )
3140             / \l__enumext_columns_viii_int
3141         }
3142     }
3143     \int_set:Nn \l__enumext_tmpa_viii_int { \l__enumext_columns_viii_int - \c_one_int }
3144     \dim_set:Nn \l__enumext_item_width_viii_dim
3145     {
3146         ( \linewidth - \l__enumext_columns_sep_viii_dim * \l__enumext_tmpa_viii_int )
3147         / \l__enumext_columns_viii_int - \l__enumext_labelwidth_viii_dim
3148         - \l__enumext_labelsep_viii_dim
3149     }
3150     \dim_zero_new:N \itemwidth
3151 }

```

(End of definition for \l__enumext_starred_columns_set_viii:.)

\l__enumext_starred_joined_item_viii:n

The function \l__enumext_starred_joined_item_viii:n will set the *width* of the box in which the content passed to \item(<number>) will be stored together with the value of \itemwidth.

```

3152 \cs_new_protected:Npn \l__enumext_starred_joined_item_viii:n #1
3153 {
3154     \int_set:Nn \l__enumext_joined_item_viii_int {#1}
3155     \int_compare:nNnT { \l__enumext_joined_item_viii_int } > { \l__enumext_columns_viii_int }
3156     {
3157         \msg_warning:nnee { enumext } { item-joined }
3158         { \int_use:N \l__enumext_joined_item_viii_int }
3159         { \int_use:N \l__enumext_columns_viii_int }
3160         \int_set:Nn \l__enumext_joined_item_viii_int
3161         {
3162             \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int
3163         }
3164     }
3165     \int_compare:nNnT
3166     { \l__enumext_joined_item_viii_int }
3167     >
3168     { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int }
3169     {
3170         \msg_warning:nnee { enumext } { item-joined-columns }
3171         { \int_use:N \l__enumext_joined_item_viii_int }
3172         {
3173             \int_eval:n
3174             { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int }
3175         }
3176         \int_set:Nn \l__enumext_joined_item_viii_int
3177         {
3178             \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int
3179         }
3180     }
3181     \int_compare:nNnTF { \l__enumext_joined_item_viii_int } > { \c_one_int }
3182     {
3183         \int_set_eq:NN \l__enumext_joined_item_aux_viii_int \l__enumext_joined_item_viii_int
3184         \int_decr:N \l__enumext_joined_item_aux_viii_int
3185         \int_add:Nn \l__enumext_item_column_pos_viii_int { \l__enumext_joined_item_aux_viii_int }
3186         \int_gadd:Nn \g__enumext_item_count_all_viii_int { \l__enumext_joined_item_aux_viii_int }
3187         \dim_set:Nn \l__enumext_joined_width_viii_dim
3188         {
3189             \l__enumext_item_width_viii_dim * \l__enumext_joined_item_viii_int
3190             + ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim
3191                 + \l__enumext_columns_sep_viii_dim
3192             ) * \l__enumext_joined_item_aux_viii_int
3193         }
3194         \dim_set_eq:NN \itemwidth \l__enumext_joined_width_viii_dim
3195     }
3196     {
3197         \dim_set_eq:NN \l__enumext_joined_width_viii_dim \l__enumext_item_width_viii_dim
3198         \dim_set_eq:NN \itemwidth \l__enumext_item_width_viii_dim
3199     }
3200 }

```

(End of definition for \l__enumext_starred_joined_item_viii:n)

`__enumext_start_mini_viii:` The implementation of the `mini-env` key is identical to the one used in the `enumext*` environment.

```

3201 \cs_new_protected:Nn \__enumext_start_mini_viii:
3202 {
3203   \dim_compare:nNnT { \__enumext_minipage_right_viii_dim } > { \c_zero_dim }
3204   {
3205     \dim_set:Nn \__enumext_minipage_left_viii_dim
3206     {
3207       \linewidth
3208       - \__enumext_minipage_right_viii_dim
3209       - \__enumext_minipage_hsep_viii_dim
3210     }
3211     \bool_set_true:N \__enumext_minipage_active_viii_bool
3212     \dim_gset_eq:NN
3213     \g__enumext_minipage_right_viii_dim
3214     \__enumext_minipage_right_viii_dim
3215     \__enumext_mini_addvspace_viii:
3216     \nointerlineskip\noindent
3217     \begin{__enumext_mini_env*}{ \__enumext_minipage_left_viii_dim }
3218   }
3219 }
3220 \cs_new_protected:Nn \__enumext_stop_mini_viii:
3221 {
3222   \bool_if:NT \__enumext_minipage_active_viii_bool
3223   {
3224     \end{__enumext_mini_env*}
3225     \hfill
3226     \bool_gset_true:N \g__enumext_minipage_active_viii_bool
3227   }
3228 }
3229 \__enumext_after_env:nn {keyans*}
3230 {
3231   \bool_if:NT \g__enumext_minipage_active_viii_bool
3232   {
3233     \begin{__enumext_mini_env*}{ \g__enumext_minipage_right_viii_dim }
3234     \par\addvspace { \g__enumext_minipage_right_skip }
3235     \bool_if:NF \g__enumext_minipage_center_viii_bool
3236     {
3237       \centering
3238     }
3239     \tl_use:N \g__enumext_miniright_code_viii_tl % the code
3240     \end{__enumext_mini_env*}
3241     \par\addvspace{ \g__enumext_minipage_after_skip }
3242   }
3243   \bool_gset_false:N \g__enumext_minipage_active_viii_bool
3244   \bool_gset_true:N \g__enumext_minipage_center_viii_bool
3245   \tl_gclear:N \g__enumext_miniright_code_viii_tl
3246   \dim_gzero:N \g__enumext_minipage_right_viii_dim
3247 }

```

(End of definition for `__enumext_start_mini_viii:` and `__enumext_stop_mini_viii:`.)

keyans* First we will generate the environment and we will give a temporary definition to `__enumext_stop_item_tmp_viii:` equal to `\noindent` and next to `\item` equal to `__enumext_start_item_tmp_viii:` which we will redefine later.

```

3248 \NewDocumentEnvironment{keyans*}{ o }
3249 {
3250   \__enumext_safe_exec_viii:
3251   \__enumext_parse_keys_viii:n {#1}
3252   \__enumext_before_list_viii:
3253   \__enumext_start_list:nn { }
3254   {
3255     \__enumext_list_arg_two_viii:
3256     \__enumext_before_keys_exec_viii:
3257   }
3258   \__enumext_starred_columns_set_viii:
3259   \item[] \scan_stop:
3260   \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \noindent
3261   \cs_set_eq:NN \item \__enumext_start_item_tmp_viii:
3262 }
3263 {

```

```

3264     \__enumext_stop_item_tmp_viii:
3265     \__enumext_remove_extra_parsep_viii:
3266     \__enumext_keyans_check_ans:nn { item }{ keyans* }
3267     \__enumext_stop_list:
3268     \__enumext_after_list_viii:
3269 }

```

(End of definition for `keyans*`. This function is documented on page 11.)

`__enumext_safe_exec_viii:` First check the maximum nesting level for the `keyans*` environment.

```

3270 \cs_new_protected:Nn \__enumext_safe_exec_viii:
3271 {
3272   \int_incr:N \l__enumext_keyans_level_h_int
3273   \int_compare:nNnT { \l__enumext_keyans_level_h_int } > { 1 }
3274   {
3275     \msg_error:nn { enumext } { nested }
3276   }
3277   % Set false for interfering with enumext nested in keyans* (yes, its possible and crayze)
3278   \bool_set_false:N \l__enumext_store_active_bool
3279   \int_compare:nNnT { \l__enumext_level_int } > { 1 }
3280   {
3281     \msg_error:nn { enumext } { keyans-wrong-level }
3282   }
3283 }

```

(End of definition for `__enumext_safe_exec_viii:`.)

`__enumext_parse_keys_viii:n` Parse [`<key = val>`] for `keyans*`.

```

3284 \cs_new_protected:Npn \__enumext_parse_keys_viii:n #1
3285 {
3286   \tl_if_novalue:nF {#1}
3287   {
3288     \keys_set:nn { enumext / keyans* } {#1}
3289   }
3290 }

```

(End of definition for `__enumext_parse_keys_viii:n`.)

`__enumext_before_list_viii:` The function `__enumext_before_list_viii:` will add the vertical spacing on the environment if the `above` key is active next to the `{<code>}` defined by the `before*` key if it is active, the call the function `__enumext_start_mini_viii:` handle by `mini-env`.

```

3291 \cs_new_protected:Nn \__enumext_before_list_viii:
3292 {
3293   \__enumext_vspace_above_viii:
3294   \__enumext_before_args_exec_viii:
3295   \__enumext_start_mini_viii:
3296 }

```

(End of definition for `__enumext_before_list_viii:`.)

`__enumext_after_list_viii:` The function `__enumext_after_list:` first call the function `__enumext_stop_mini_viii:`, then apply the `{<code>}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```

3297 \cs_new_protected:Nn \__enumext_after_list_viii:
3298 {
3299   \__enumext_stop_mini_viii:
3300   \__enumext_after_stop_list_viii:
3301   \__enumext_vspace_below_viii:
3302 }

```

(End of definition for `__enumext_after_list_viii:`.)

10.36.2 The command `\item` in `keyans*`

The idea here is to make the `\item` command behave in the same way as in the `keyans` environment with the difference of the optional argument (`<number>`) which works in the same way as in the `enumext*` environment. In simple terms we want to store the `<label>` next to the `[<content>]` if it is present in the `<sequence>` and `<prop list>` defined by `save-ans` key for `\item*`, `\item* [<content>]`, `\item(<number>)*` and `\item(<number>)* [<content>]` commands.

`__enumext_start_item_tmp_viii:`

First we will call the function `__enumext_stop_item_tmp_viii:` that we will redefine later, we will increment the value of `\l__enumext_item_column_pos_viii_int` that will count the item's by rows and the value of `\g__enumext_item_count_all_viii_int` that will count the total of item's in the environment. After that we will call the function `__enumext_item_peek_args_viii:` that will handle the arguments passed to `\item`.

```
3303 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_viii:
3304 {
3305   \__enumext_stop_item_tmp_viii:
3306   \int_incr:N \l__enumext_item_column_pos_viii_int
3307   \int_gincr:N \g__enumext_item_count_all_viii_int
3308   \__enumext_item_peek_args_viii:
3309 }
```

(End of definition for `__enumext_start_item_tmp_viii:`.)

`__enumext_item_peek_args_viii:`

The function `__enumext_item_peek_args_viii:` will handle the `\item(<number>)`. Look for the argument “(”, if it is present we will call the function `__enumext_joined_item_viii:w (<number>)`, which is in charge of joining the item's in the same row, in case they are not present we will set the default value (1).

```
3310 \cs_new_protected:Nn \__enumext_item_peek_args_viii:
3311 {
3312   \peek_meaning:NTF (
3313     { \__enumext_joined_item_viii:w }
3314     { \__enumext_joined_item_viii:w (1) }
3315 }
```

(End of definition for `__enumext_item_peek_args_viii:`.)

`__enumext_joined_item_viii:w`

The function `__enumext_joined_item_viii:w` will first call the function `__enumext_starred_joined_item_viii:n` in charge of setting the *width* of the box that will store the content passed to `\item`. Then we will look for the argument “*”, if it is present we will call the function `__enumext_starred_item_viii:w` otherwise we will call the function `__enumext_standard_item_viii:w`.

```
3316 \cs_new_protected:Npn \__enumext_joined_item_viii:w (#1)
3317 {
3318   \__enumext_starred_joined_item_viii:n {#1}
3319   \peek_meaning_remove:NTF *
3320     { \__enumext_starred_item_viii:w }
3321     { \__enumext_standard_item_viii:w }
3322 }
```

(End of definition for `__enumext_joined_item_viii:w`.)

`__enumext_standard_item_viii:w`

The function `__enumext_standard_item_viii:w` will first look for the argument “[”, if present it will set the state of the variable `\l__enumext_wrap_label_opt_viii_bool` equal to the state of the variable `\l__enumext_wrap_label_opt_viii_bool` handled by the key `wrap-label*` and finally execute the *non-enumerated* version `\item[<custom>]` by means of the function `__enumext_start_item_viii:w`, otherwise we will set the value of the variable `\l__enumext_wrap_label_viii_bool` handled by the `wrap-label` key to true and set the switch `\if@noitemarg` to true to execute the enumerated version of `\item` by means of the function `__enumext_start_item_viii:w [__enumext_label_viii_tl]`.

```
3323 \cs_new_protected:Npn \__enumext_standard_item_viii:w
3324 {
3325   \bool_set_false:N \l__enumext_item_starred_viii_bool
3326   \peek_meaning:NTF [
3327     {
3328       \bool_set_eq:NN
3329       \l__enumext_wrap_label_viii_bool
3330       \l__enumext_wrap_label_opt_viii_bool
3331       \__enumext_start_item_viii:w
3332     }
3333     {
3334       \bool_set_true:N \l__enumext_wrap_label_viii_bool
```

```

3335         \legacy_if_set_true:n { @noitemarg }
3336         \__enumext_start_item_viii:w [ \__enumext_label_viii_tl ]
3337     }
3338 }

```

(End of definition for __enumext_standard_item_viii:w.)

```

\__enumext_starred_item_viii:w
\__enumext_starred_item_viii_aux_i:w
\__enumext_starred_item_viii_aux_ii:w

```

The function __enumext_starred_item_viii:w together with the specified auxiliary functions `aux_i:w` and `aux_ii:w` execute `\item*` and `\item*[\langle content \rangle]`.

```

3339 \cs_new_protected:Npn \__enumext_starred_item_viii:w
3340 {
3341     \bool_set_true:N \__enumext_item_starred_viii_bool
3342     \bool_set_true:N \__enumext_wrap_label_viii_bool
3343     \peek_meaning:NTF [
3344         { \__enumext_starred_item_viii_aux_i:w }
3345         { \__enumext_starred_item_viii_aux_ii:w }
3346     }

```

The optional argument will be captured in the variables `__enumext_keyans_tmpa_tl` and `__enumext_keyans_tmppb_tl` which we will use later for the implementation of the `show-ans` and `show-pos` keys together with the stored in `\sequence` and `\prop list`.

```

3347 \cs_new_protected:Npn \__enumext_starred_item_viii_aux_i:w [#1]
3348 {
3349     \tl_clear:N \__enumext_store_keyans_label_tl
3350     \tl_if_no_value:nF { #1 }
3351     {
3352         \tl_set:Ne \__enumext_keyans_tmpa_tl { \c_space_tl [#1] }
3353         \tl_set:Ne \__enumext_keyans_tmppb_tl { \c_space_tl #1 }
3354     }
3355     \__enumext_starred_item_viii_aux_ii:w
3356 }
3357 \cs_new_protected:Npn \__enumext_starred_item_viii_aux_ii:w
3358 {
3359     \legacy_if_set_true:n { @noitemarg }
3360     \__enumext_start_item_viii:w [ \__enumext_label_viii_tl ]
3361 }

```

(End of definition for __enumext_starred_item_viii:w, __enumext_starred_item_viii_aux_i:w, and __enumext_starred_item_viii_aux_ii:w.)

```
\__enumext_starred_item_exec:
```

The function __enumext_starred_item_exec: will be in charge of storing the current `\label` for `\item*` followed by the `[\langle content \rangle]` for `\item*[\langle content \rangle]` if present in the `\sequence` and `\prop list` set by the `save-ans` key. In this same function the keys `show-ans`, `show-pos` and `store-ref` are implemented.

```

3362 \cs_new_protected:Nn \__enumext_starred_item_exec:
3363 {
3364     \tl_put_left:Ne \__enumext_store_keyans_label_tl { \__enumext_label_viii_tl }
3365     \tl_if_blank:VF \__enumext_keyans_tmppb_tl
3366     {
3367         \tl_put_right:Ne \__enumext_store_keyans_label_tl { \__enumext_keyans_tmppb_tl }
3368     }
3369     \__enumext_store_addto_prop:V \__enumext_store_keyans_label_tl
3370     \__enumext_keyans_store_ref:
3371     \tl_put_left:Ne \__enumext_store_keyans_label_tl { \item }
3372     \__enumext_keyans_addto_seq_link:
3373     \bool_if:NT \__enumext_show_answer_bool
3374     {
3375         \tl_if_blank:VF \__enumext_keyans_tmpa_tl
3376         {
3377             \tl_put_right:Ne \__enumext_label_viii_tl { \__enumext_keyans_tmpa_tl }
3378             \__enumext_label_width_by_box:Nn \__enumext_keyans_tmpa_dim { \__enumext_keyans_tmpa_dim }
3379             \dim_add:Nn \__enumext_fake_item_indent_viii_dim { \__enumext_keyans_tmpa_dim }
3380         }
3381         \__enumext_print_keyans_box:NN \__enumext_labelwidth_i_dim \__enumext_labelsep_i_dim
3382     }
3383     \bool_if:NT \__enumext_show_position_bool
3384     {
3385         \tl_set:Ne \__enumext_mark_answer_sym_tl
3386         {
3387             \group_begin:
3388             \exp_not:N \normalfont

```

```

3389         \exp_not:N \footnotesize [ \int_eval:n
3390         {
3391             \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
3392         }
3393     ]
3394     \group_end:
3395 }
3396 \tl_if_blank:VF \l__enumext_keyans_tmpa_tl
3397 {
3398     \tl_put_right:Ne \l__enumext_label_viii_tl { \l__enumext_keyans_tmpa_tl }
3399     \__enumext_label_width_by_box:Nn \l__enumext_keyans_tmpa_dim { \l__enumext_keyans_tmpa_dim }
3400     \dim_add:Nn \l__enumext_fake_item_indent_viii_dim { \l__enumext_keyans_tmpa_dim }
3401 }
3402 \__enumext_print_keyans_box:NN \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
3403 }
3404 }

```

(End of definition for `__enumext_starred_item_exec:`)

Real definition of `\item` in `keyans*`

The implementation at this point is very similar to that of the `enumext*` environment.

`__enumext_start_item_viii:w`

```

3405 \cs_new_protected_nopar:Npn \__enumext_start_item_viii:w [#1]
3406 {
3407     \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \__enumext_stop_item_viii:
3408     \legacy_if:nT { @noitemarg }
3409     {
3410         \legacy_if_set_false:n { @noitemarg }
3411         \legacy_if:nT { @nمبرlist }
3412         {
3413             \bool_if:NT \l__enumext_hyperref_bool
3414             {
3415                 \legacy_if_set_true:n { @hyper@item }
3416             }
3417             \refstepcounter{enumXviii}
3418         }
3419     }

```

Here we start capturing `\item` and its contents into a group using the plain form of the `lrbox` environment.

```

3420     \group_begin:
3421     \lrbox{ \l__enumext_item_text_viii_box }
3422     \bool_if:NF \l__enumext_footnotes_key_bool
3423     {
3424         \__enumext_renew_footnote:
3425     }
3426     \bool_if:NT \l__enumext_item_starred_viii_bool
3427     {
3428         \__enumext_starred_item_exec:
3429     }
3430     \group_begin:
3431     \tl_use:N \l__enumext_label_font_style_viii_tl
3432     \bool_if:NTF \l__enumext_wrap_label_viii_bool
3433     {
3434         \makebox[ \l__enumext_labelwidth_viii_dim ][ \l__enumext_align_label_viii_str ]
3435         { \__enumext_wrapper_label_viii:n {#1} }
3436     }
3437     {
3438         \makebox[ \l__enumext_labelwidth_viii_dim ][ \l__enumext_align_label_viii_str ]{ #1
3439     }
3440     \group_end:
3441     \skip_horizontal:N \l__enumext_labelsep_viii_dim
3442     \tl_use:N \l__enumext_after_list_args_viii_tl
3443     \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_viii_dim }
3444     \skip_set_eq:NN \parindent \l__enumext_listparindent_viii_dim
3445     \skip_set_eq:NN \parskip \l__enumext_parsep_viii_skip
3446     \tl_use:N \l__enumext_fake_item_indent_viii_tl
3447 }

```

(End of definition for `__enumext_start_item_viii:w`)

`__enumext_stop_item_viii:` The function `__enumext_stop_item_viii:` shall terminate with the capture of `\item` and its *contents*. Close the environments `minipage`, `lrbox` and the group. Then we only have to set the width of the box and print it next to `\footnote`, and add the horizontal and vertical separation between the boxes.

```

3448 \cs_new_protected_nopar:Nn \__enumext_stop_item_viii:
3449 {
3450     \__enumext_endminipage:
3451     \endlrbox
3452     \group_end:
3453     \box_set_wd:Nn \l__enumext_item_text_viii_box
3454     {
3455         \l__enumext_joined_width_viii_dim
3456         + \l__enumext_labelwidth_viii_dim
3457         + \l__enumext_labelsep_viii_dim
3458     }
3459     \int_set:Nn \hbadness { 10000 }
3460     \box_use:N \l__enumext_item_text_viii_box
3461     \bool_if:NF \l__enumext_footnotes_key_bool
3462     {
3463         \__enumext_print_footnote:
3464     }
3465     \int_compare:nNnTF { \l__enumext_item_column_pos_viii_int } = { \l__enumext_columns_viii_int }
3466     {
3467         \par\noindent
3468         \int_zero:N \l__enumext_item_column_pos_viii_int
3469     }
3470     { \hspace{ \l__enumext_columns_sep_viii_dim } }
3471 }

```

(End of definition for `__enumext_stop_item_viii:`.)

`__enumext_remove_extra_parsep_viii:` Finally we will remove the vertical space equal to `\parsep` when the total number of items is divisible by the number of items in the last row of the environment.

```

3472 \cs_new_protected:Nn \__enumext_remove_extra_parsep_viii:
3473 {
3474     \int_compare:nNnT
3475     {
3476         \int_mod:nn { \g__enumext_item_count_all_viii_int } { \l__enumext_columns_viii_int }
3477     }
3478     =
3479     { \c_zero_int }
3480     {
3481         \par
3482         \vspace{ -\l__enumext_itemsep_viii_skip }
3483         \int_gzero:N \g__enumext_item_count_all_viii_int
3484     }
3485 }

```

(End of definition for `__enumext_remove_extra_parsep_viii:`.)

10.37 The command `\getkeyans`

`\getkeyans` The `\getkeyans` command takes a mandatory argument of the form $\langle \textit{store name} : \textit{position} \rangle$. Retrieve a “single” content stored by `\anskey`, `\anspic*` and `\item*` from *prop list* defined by `save-ans` key.

```

3486 \NewDocumentCommand \getkeyans { m }
3487 {
3488     \exp_args:Ne \__enumext_getkeyans_aux:n
3489     { \tl_to_str:e { \text_expand:n {#1} } }
3490 }

```

(End of definition for `\getkeyans`. This function is documented on page 13.)

`__enumext_getkeyans_aux:n` The internal function `__enumext_getkeyans_aux:n` is in charge of *splitting* the *argument* using “:”. If “:” is omitted it will return an error.

```

3491 \cs_new_protected:Npn \__enumext_getkeyans_aux:n #1
3492 {
3493     \str_if_in:nnTF {#1} { : }
3494     {
3495         \use:e
3496         {
3497             \cs_set:Npn \exp_not:N \__enumext_tmp:w ##1 \c_colon_str ##2 \scan_stop:
3498             { {##1} {##2} }

```

```

3499     }
3500     \exp_after:wN \__enumext_getkeyans:nn \__enumext_tmp:w #1 \scan_stop:
3501   }
3502   { \msg_error:nnn { enumext } { missing-colon } {#1} }
3503 }

```

(End of definition for __enumext_getkeyans_aux:n.)

__enumext_getkeyans:nn The internal function __enumext_getkeyans:nn will check for the existence of the *⟨prop list⟩*, if it does not exist it will return an error message, then it will fetch the content specified by the second *⟨argument⟩* from *⟨prop list⟩*.

```

3504 \cs_new_protected:Npn \__enumext_getkeyans:nn #1 #2
3505 {
3506   \prop_if_exist:cF { g__enumext_#1_prop }
3507   { \msg_error:nnn { enumext } { undefined-storage-anskey } {#1} }
3508   \group_begin:
3509     \prop_item:cn { g__enumext_#1_prop }{#2}
3510   \group_end:
3511 }

```

(End of definition for __enumext_getkeyans:nn.)

10.38 The command \printkeyans

The \printkeyans command prints “all stored content” in the *⟨sequence⟩* defined by the save-ans key. The first thing we will do is to define a set of *⟨keys⟩* with which we will control the options of the different nesting levels for the enumext and enumext* environment by storing the values of these in the token list variables \l__enumext_print_keyans_X_tl.

```

3512 \keys_define:nn { keyanskey / print }
3513 {
3514   level-1 .code:n = \tl_put_right:Nn \l__enumext_print_keyans_i_tl
3515                   {
3516                     \setenumext[level,1] {#1} \setenumext[print,1] {#1}
3517                   },
3518   level-1 .initial:n = { label=\arabic*. , nosep, columns=2, first=\small, font=\small },
3519   level-2 .code:n = \tl_put_right:Nn \l__enumext_print_keyans_ii_tl
3520                   {
3521                     \setenumext[level,2] {#1} \setenumext[print,2] {#1}
3522                   },
3523   level-2 .initial:n = { nosep, label=(\alph*.), first=\small, font=\small },
3524   level-3 .code:n = \tl_put_right:Nn \l__enumext_print_keyans_iii_tl
3525                   {
3526                     \setenumext[level,3] {#1} \setenumext[print,3] {#1}
3527                   },
3528   level-3 .initial:n = { nosep, label=\roman*. , first=\small, font=\small },
3529   level-4 .code:n = \tl_put_right:Nn \l__enumext_print_keyans_iv_tl
3530                   {
3531                     \setenumext[level,4] {#1} \setenumext[print,4] {#1}
3532                   },
3533   level-4 .initial:n = { nosep, label=\Alph*. , first=\small, font=\small },
3534   level-* .code:n = \tl_put_right:Nn \l__enumext_print_keyans_vii_tl % starred
3535                   {
3536                     \setenumext[enumext*] {#1} %%\setenumext[print,*] {#1}
3537                   },
3538   level-* .initial:n = { label=\arabic*. , nosep, columns=2, first=\small, font=\small },
3539 }

```

\printkeyans Create a user command to print “all stored content” in *⟨sequence⟩* for \anskey, \item* and \anspic*.

```

3540 \NewDocumentCommand \printkeyans { s O{} m }
3541 {
3542   \group_begin:
3543     \tl_use:N \l__enumext_print_keyans_i_tl
3544     \tl_use:N \l__enumext_print_keyans_ii_tl
3545     \tl_use:N \l__enumext_print_keyans_iii_tl
3546     \tl_use:N \l__enumext_print_keyans_iv_tl
3547     \tl_use:N \l__enumext_print_keyans_vii_tl
3548     \__enumext_printkeyans:nnn { #1 } { #2 } { #3 }
3549   \group_end:
3550 }

```

(End of definition for \printkeyans. This function is documented on page 13.)

`__enumext_printkeyans:nnn`

The internal function `__enumext_printkeyans:nnn` will check for the existence of the *sequence*, if it does not exist it will return an error message, then it will fetch the content specified by the first argument mapping the *sequence*.

#1: starred
#2: key-val
#3: seq-name

```

3551 \cs_new_protected:Npn \__enumext_printkeyans:nnn #1 #2 #3
3552 {
3553   \seq_if_exist:cTF { g__enumext_#3_seq }
3554   {
3555     \seq_if_empty:cF { g__enumext_#3_seq }
3556     {
3557       %%\seq_show:c { g__enumext_#3_seq }
3558       \bool_if:nTF {#1}
3559       {
3560         \begin{enumext*}[#2]
3561         \seq_map_inline:cn { g__enumext_#3_seq } { ##1 }
3562         \end{enumext*}
3563       }
3564       {
3565         \begin{enumext}[#2]
3566         \seq_map_inline:cn { g__enumext_#3_seq } { ##1 }
3567         \end{enumext}
3568       }
3569     }
3570   }
3571   {
3572     \msg_error:nnn { enumext } { undefined-storage-anskey } {#3}
3573   }
3574 }

```

(End of definition for `__enumext_printkeyans:nnn`.)

10.39 The command `\setenumext`

First we define a “meta families” of *keys* to access from `\setenumext`.

```

3575 \keys_define:nn { enumext / meta-families }
3576 {
3577   level-1 .code:n = { \keys_set:nn { enumext / level-1 } {#1} } ,
3578   level-2 .code:n = { \keys_set:nn { enumext / level-2 } {#1} } ,
3579   level-3 .code:n = { \keys_set:nn { enumext / level-3 } {#1} } ,
3580   level-4 .code:n = { \keys_set:nn { enumext / level-4 } {#1} } ,
3581   keyans .code:n = { \keys_set:nn { enumext / keyans } {#1} } ,
3582   enumext* .code:n = { \keys_set:nn { enumext / enumext* } {#1} } ,
3583   keyans* .code:n = { \keys_set:nn { enumext / keyans* } {#1} } ,
3584   print-1 .code:n = { \keys_set:nn { keyanskey / print } { level-1 = {#1} } } ,
3585   print-2 .code:n = { \keys_set:nn { keyanskey / print } { level-2 = {#1} } } ,
3586   print-3 .code:n = { \keys_set:nn { keyanskey / print } { level-3 = {#1} } } ,
3587   print-4 .code:n = { \keys_set:nn { keyanskey / print } { level-4 = {#1} } } ,
3588   print-* .code:n = { \keys_set:nn { keyanskey / print } { level-* = {#1} } } ,
3589   unknown .code:n = { \msg_error:nn { enumext } { unknown-key-family } } ,
3590 }

```

We store them in the constant sequence `\c__enumext_all_families_seq` separated by commas.

```

3591 \seq_const_from_clist:Nn \c__enumext_all_families_seq
3592 {
3593   level-1 , level-2 , level-3 , level-4 , keyans , enumext* ,
3594   keyans* , print-1 , print-2 , print-3 , print-4 , print-* ,
3595 }

```

`\setenumext`

Now we define the user command `\setenumext`.

```

3596 \NewDocumentCommand \setenumext { o +m }
3597 {
3598   \tl_if_novalue:nTF {#1}
3599   {
3600     \seq_map_inline:Nn \c__enumext_all_families_seq
3601     {
3602       \seq_clear:N \l__enumext_setkey_tmpa_seq
3603       \seq_set_from_clist:Nn \l__enumext_setkey_tmpb_seq {#1}
3604       \int_set:Nn \l__enumext_setkey_tmpa_int

```

```

3606         {
3607             \seq_count:N \l__enumext_setkey_tmpb_seq
3608         }
3609         \int_compare:nNnTF { \l__enumext_setkey_tmpa_int } > { 1 }
3610         {
3611             \seq_pop_left:NN \l__enumext_setkey_tmpb_seq \l__enumext_setkey_tmpa_tl
3612             \seq_map_function:NN \l__enumext_setkey_tmpb_seq \l__enumext_set_parse:n
3613             \seq_set_map_e:NNn \l__enumext_setkey_tmpa_seq \l__enumext_setkey_tmpa_seq
3614             {
3615                 \tl_use:N \l__enumext_setkey_tmpa_tl - ##1
3616             }
3617         }
3618         {
3619             \seq_put_right:Ne \l__enumext_setkey_tmpa_seq { \tl_trim_spaces:n {#1} }
3620         }
3621         \seq_if_empty:NTF \l__enumext_setkey_tmpa_seq
3622         { \seq_map_inline:Nn \c__enumext_all_families_seq }
3623         { \seq_map_inline:Nn \l__enumext_setkey_tmpa_seq }
3624     }
3625     {
3626         \keys_set:nn { enumext / meta-families } { ##1 = {#2} }
3627     }
3628 }

```

(End of definition for `\setenumext`. This function is documented on page 5.)

`__enumext_set_parse:n`
`__enumext_set_error:nn`

Internal functions used by the `\setenumext` command.

```

3629 \cs_new_protected:Npn \__enumext_set_parse:n #1
3630 {
3631     \tl_set:Ne \l__enumext_setkey_tmpb_tl { \tl_trim_spaces:n {#1} }
3632     \int_step_inline:nnn { 0 } { 4 } %<- max level
3633     { \tl_remove_all:Nn \l__enumext_setkey_tmpb_tl {##1} }
3634     \tl_if_empty:NTF \l__enumext_setkey_tmpb_tl
3635     {
3636         \seq_put_right:Ne \l__enumext_setkey_tmpa_seq
3637         { \tl_trim_spaces:n {#1} }
3638     }
3639     { \__enumext_set_error:nn {#1} { } }
3640 }
3641 \cs_new_protected:Npn \__enumext_set_error:nn #1 #2
3642 { \msg_error:nnn { enumext } { invalid-key } {#1} {#2} }

```

(End of definition for `__enumext_set_parse:n` and `__enumext_set_error:nn`.)

10.40 Messages

Message used by package-load for `multicol` and `hyperref` packages.

```

3643 \msg_new:nnn { enumext } { package-load }
3644 {
3645     The ~ '#1' ~ package ~ is ~ already ~ loaded.
3646 }
3647 \msg_new:nnn { enumext } { package-not-load }
3648 {
3649     The ~ '#1' ~ package ~ will ~ be ~ loaded ~ as ~ a ~ dependency.
3650 }
3651 \msg_new:nnn { enumext } { package-load-foot }
3652 {
3653     The ~ '#1' ~ package ~ is ~ loaded ~ with ~ the ~ option ~ '#2'.
3654 }

```

Message used in the creation of counters by `enumext` package.

```

3655 \msg_new:nnn { enumext } { counters }
3656 {
3657     The ~ counter ~ '#1' ~ is ~ already ~ defined ~ by ~ some ~ \\
3658     package ~ or ~ macro, ~ it ~ cannot ~ be ~ continued.
3659 }

```

Message used by `[⟨key = val⟩]` system and `\setenumext` command.

```

3660 \msg_new:nnn { enumext } { invalid-key }
3661 {
3662     The ~ key ~ '#1' ~ is ~ not ~ know ~ the ~ level ~ #2.

```

```

3663     }
3664     \msg_new:nnn { enumext } { unknown-key-family }
3665     {
3666         Unknown~key~family~`\l_keys_key_str'~for~enumext.
3667     }

```

Messages used in length calculation.

```

3668     \msg_new:nnn { enumext } { width-negative }
3669     {
3670         Ignoring ~ negative ~ value ~ '#1=#2' ~ \msg_line_context:.\
3671         The ~ key ~ '#1'~ accepts ~ values ~ >= ~ opt.
3672     }
3673     \msg_new:nnn { enumext } { width-zero }
3674     {
3675         Invalid ~ '#1=#2' ~ \msg_line_context:.\
3676         The ~ key ~ '#1'~ accepts ~ values ~ > ~ opt.
3677     }

```

Messages used by `show-length` key in `enumext`.

```

3678     \msg_new:nnn { enumext } { list-lengths }
3679     {
3680         **** ~ Lengths ~ used ~ by ~ 'enumext' ~ level ~ '#2' ~ \msg_line_context:~\c_space_tl ****\
3681         \__enumext_show_length:nnn { dim } { labelsep } {#1}
3682         \__enumext_show_length:nnn { dim } { labelwidth } {#1}
3683         \__enumext_show_length:nnn { dim } { itemindent } {#1}
3684         \__enumext_show_length:nnn { dim } { leftmargin } {#1}
3685         \__enumext_show_length:nnn { dim } { rightmargin } {#1}
3686         \__enumext_show_length:nnn { dim } { listparindent } {#1}
3687         \__enumext_show_length:nnn { skip } { topsep } {#1}
3688         \__enumext_show_length:nnn { skip } { parsep } {#1}
3689         \__enumext_show_length:nnn { skip } { partopsep } {#1}
3690         \__enumext_show_length:nnn { skip } { itemsep } {#1}
3691         ****~
3692     }

```

Messages used by `show-length` key in `enumext*`, `keyans*` and `keyans`.

```

3693     \msg_new:nnn { enumext } { list-lengths-not-nested }
3694     {
3695         **** ~ Lengths ~ used ~ by ~ '#2' ~ environment ~ \msg_line_context:~\c_space_tl ****\
3696         \__enumext_show_length:nnn { dim } { labelsep } {#1}
3697         \__enumext_show_length:nnn { dim } { labelwidth } {#1}
3698         \__enumext_show_length:nnn { dim } { itemindent } {#1}
3699         \__enumext_show_length:nnn { dim } { leftmargin } {#1}
3700         \__enumext_show_length:nnn { dim } { rightmargin } {#1}
3701         \__enumext_show_length:nnn { dim } { listparindent } {#1}
3702         \__enumext_show_length:nnn { skip } { topsep } {#1}
3703         \__enumext_show_length:nnn { skip } { parsep } {#1}
3704         \__enumext_show_length:nnn { skip } { partopsep } {#1}
3705         \__enumext_show_length:nnn { skip } { itemsep } {#1}
3706         ****~
3707     }

```

Messages used by the internal system to check answer used by `check-ans` key.

```

3708     \msg_new:nnn { enumext } { items-same-answer }
3709     {
3710         *****~Checking~answers~on~'#1'~OK~*****\
3711         **~ All ~ items ~ stored ~ in ~ sequence ~ '#1' ~ have ~ an ~ answer. \
3712         *****~
3713         \prg_replicate:nn { 7 + \str_count:n {#1} } { * }
3714     }
3715     \msg_new:nnn { enumext } { item-different-answer }
3716     {
3717         Number ~ of ~ items ~ different ~ of ~ number ~ of ~
3718         answer ~ in ~ sequence ~ '#1'~ closed ~ \msg_line_context:.
3719     }

```

Messages used by the internal system to check for “starred” `\item*` commands.

```

3720     \msg_new:nnn { enumext } { missing-starred }
3721     {
3722         Missing ~ '\c_backslash_str #1*' ~ in ~ '#2' ~ \msg_line_context:.
3723     }

```

Message for the nesting depth of the environment `enumext`.

```
3724 \msg_new:nnn { enumext } { list-too-deep }
3725 {
3726     Too ~ deep ~ nesting ~ for ~ 'enumext' ~ \msg_line_context:~ \\
3727     The ~ maximum ~ level ~ of ~ nesting ~ is ~ 4.
3728 }
```

Messages used by `\anskey` and `\anspic` commands.

```
3729 \msg_new:nnn { enumext } { anskey-wrong-place }
3730 {
3731     Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
3732     '\c_backslash_str #1' ~ works ~ in ~ the ~ environment ~ '#2'.
3733 }
3734 \msg_new:nnn { enumext } { ansPIC-wrong-place }
3735 {
3736     Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
3737     '\c_backslash_str #1' ~ works ~ in ~ the ~ environment ~ '#2'.
3738 }
3739 \msg_new:nnn { enumext } { command-wrong-place }
3740 {
3741     Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
3742     '\c_backslash_str #1' ~ works ~ outside ~ the ~ environment ~ '#2'.
3743 }
```

Messages used by `keyans` and `keyanspic` environment.

```
3744 \msg_new:nnn { enumext } { keyans-nested }
3745 {
3746     The ~ environment ~ 'keyans' ~ can't ~ be ~ nested ~ \msg_line_context:.
3747 }
3748 \msg_new:nnn { enumext } { keyans-wrong-level }
3749 {
3750     Wrong ~ level ~ position ~ for ~ 'keyans' ~ \msg_line_context:~ \\
3751     The ~ environment ~ 'keyans' ~ can ~ only ~ be ~ in ~ the ~ first ~ level.
3752 }
3753 \msg_new:nnn { enumext } { wrong-place }
3754 {
3755     Wrong ~ place ~ for ~ '#1' ~ environment ~ \msg_line_context:~ \\
3756     '#1' ~ is ~ only ~ found ~ with ~ '#2' ~ in ~ 'enumext'.
3757 }
3758 \msg_new:nnn { enumext } { keyanspic-nested }
3759 {
3760     The ~ environment ~ 'keyanspic' ~ can't ~ be ~ nested ~ \msg_line_context:~.
3761 }
3762 \msg_new:nnn { enumext } { keyanspic-wrong-level }
3763 {
3764     Wrong ~ level ~ position ~ for ~ 'keyanspic' ~ \msg_line_context:~ \\
3765     The ~ environment ~ 'keyans' ~ can ~ only ~ be ~ in ~ the ~ first ~ level.
3766 }
```

Messages used by `\getkeyans` command.

```
3767 \msg_new:nnn { enumext } { undefined-storage-anskey }
3768 {
3769     Storage ~ named ~ '#1' ~ is ~ not ~ defined ~ \msg_line_context:.
3770 }
```

Messages used by `\miniright` command.

```
3771 \msg_new:nnn { enumext } { missing-miniright }
3772 {
3773     Missing ~ '\c_backslash_str miniright' ~ in ~ \msg_line_context:~ \\
3774     The ~ key ~ 'mini-env' ~ need ~ '\c_backslash_str miniright'.
3775 }
3776 \msg_new:nnn { enumext } { wrong-miniright-place }
3777 {
3778     Wrong ~ place ~ for ~ '\c_backslash_str miniright' ~ \msg_line_context:~ \\
3779     Works ~ in ~ 'enumext' ~ and ~ 'keyans' ~ with ~ key ~ 'mini-env'.
3780 }
3781 \msg_new:nnn { enumext } { wrong-miniright-use }
3782 {
3783     Wrong ~ use ~ for ~ '\c_backslash_str miniright' ~ \msg_line_context:~ \\
3784     '\c_backslash_str miniright' ~ need ~ a ~ key ~ 'mini-env'.
3785 }
```

Messages used by `enumext*` and `keyans*` environments.

```
3786 \msg_new:nnn { enumext } { nested }
3787 {
3788   The ~ starred ~ environment ~ can't ~ be ~ nested ~ \msg_line_context:.
3789 }
3790 \msg_new:nnn { enumext } { item-joined }
3791 {
3792   Items ~ joined ~ (#1) ~ > ~ #2 ~ columns ~\msg_line_context:.
3793 }
3794 \msg_new:nnn { enumext } { item-joined-columns }
3795 {
3796   Not ~ space ~ to ~ join ~ items ~ (#1) ~ > ~ #2 ~\msg_line_context:.
3797 }
```

10.41 Finish package

Finish package implementation.

```
3798 \file_input_stop:
3799 </package>
```

11 Index of Implementation

The italic numbers denote the pages where the corresponding entry is described, the numbers underlined and all others indicate the line on which they are implemented in the package code.

Symbols	
<code>*</code>	391
<code>\+</code>	192
<code>\-</code>	192
<code>\\</code>	200, 2631, 3657, 3670, 3675, 3680, 3695, 3710, 3711, 3726, 3731, 3736, 3741, 3750, 3755, 3764, 3773, 3778, 3783
A	
<code>above</code>	<u>1202</u>
<code>above*</code>	<u>1202</u>
<code>\addvspace</code>	849, 877, 1000, 1079, 1142, 1148, 1176, 1193, 2447, 2469, 2587, 2602, 2826, 2833, 3234, 3241
<code>after</code>	<u>687</u>
<code>align</code>	<u>345</u>
<code>\Alph</code>	29, 33, 34
<code>\Alph</code>	297, 474, 492, 505, 3533
<code>\alph</code>	29, 33, 34
<code>\alph</code>	298, 472, 3523
<code>\anskey</code>	10, 57, <u>1634</u>
<code>\anspic</code>	12, 77, 78, <u>2609</u>
<code>\arabic</code>	29, 31
<code>\arabic</code>	296, 471, 491, 3518, 3538
B	
<code>\b</code>	2336, 2349, 2888, 2901
<code>\baselineskip</code>	<u>41</u>
<code>\baselineskip</code>	1594, 1602
<code>before</code>	<u>687</u>
<code>before*</code>	<u>687</u>
<code>below</code>	<u>1202</u>
<code>below*</code>	<u>1202</u>
bool commands:	
<code>\bool_gset_false:N</code>	2475, 2493, 2835, 2937, 3130, 3243
<code>\bool_gset_true:N</code>	791, 1394, 1404, 2454, 2818, 2836, 2934, 3226, 3244
<code>\bool_if:NTF</code>	237, 249, 266, 1224, 1238, 1251, 1262, 1273, 1284, 1295, 1306, 1348, 1359, 1439, 1449, 1556, 1580, 1587, 1615, 1646, 1659, 1661, 1672, 1692, 1817, 1828, 1832, 1866, 1881, 1950, 1965, 1976, 2052, 2082, 2155, 2171, 2239, 2249, 2285, 2290, 2327, 2334, 2347, 2381, 2431, 2445, 2460, 2486, 2516, 2572, 2585, 2593, 2611, 2814, 2823, 2827, 2878, 2886, 2899, 2942, 2952, 3035, 3040, 3048, 3052, 3067, 3096, 3123, 3222, 3231, 3235, 3373, 3383, 3413, 3422, 3426, 3432, 3461
<code>\bool_if:nTF</code>	1177, 1194, 1700, 2093, 2127, 2191, 2632, 3558
<code>\bool_if_p:N</code>	2228, 2275
<code>\bool_lazy_all:nTF</code>	1416, 1749, 1758, 1771, 1787
<code>\bool_lazy_and:nnTF</code>	1682, 1725, 1935, 2226, 2274, 2363, 2450, 2932
<code>\bool_lazy_or:nnTF</code>	2637
<code>\bool_new:N</code>	25, 26, 27, 28, 29, 35, 37, 46, 67, 72, 73, 78, 79, 82, 100, 102, 104, 107, 108, 117, 118, 119, 120, 129, 130, 155, 166, 168
<code>\bool_not_p:n</code>	1684, 1776, 1791, 2365, 2452
<code>\bool_set_eq:NN</code>	2060, 2108, 2985, 3328
<code>\bool_set_false:N</code>	246, 1375, 1376, 1483, 1486, 1506, 1509, 2474, 2523, 2605, 2669, 2686, 2938, 2982, 3278, 3325
<code>\bool_set_true:N</code> 228, 232, 338, 615, 1208, 1213, 1340, 1355, 1366, 1482, 1485, 1505, 1508, 1518, 1525, 2056, 2086, 2104, 2116, 2321, 2369, 2374, 2400, 2521, 2547, 2803, 2871, 2991, 2998, 2999, 3211, 3334, 3341, 3342	
box commands:	
<code>\box_dp:N</code>	896, 900, 904, 915, 919, 930, 939, 945, 955, 968, 974, 980, 1011, 1012, 1013, 1016, 1026, 1030, 1039, 1046, 1051, 1059, 1088, 1089, 1092, 1099, 1112, 1120, 1126, 1134, 2698
<code>\box_new:N</code>	43, 161
<code>\box_set_wd:Nn</code>	3088, 3453
<code>\box_use:N</code>	3095, 3460
<code>\box_wd:N</code>	304
C	
<code>\c</code>	391, 392, 515, 517, 529, 531
<code>\cB</code>	392
<code>\cE</code>	392
<code>\centering</code>	1179, 1196, 2719, 2829, 3237
<code>check-ans</code>	<u>1368</u>
Document class:	
<code>article</code>	35
clist commands:	
<code>\clist_const:Nn</code>	173
<code>\clist_map_function:nN</code>	2706
<code>\clist_map_inline:Nn</code>	344, 557, 620, 686, 701, 782, 1218
<code>\clist_map_inline:nn</code>	34, 51, 57, 69, 81, 106, 138, 152, 172, 208, 369, 386, 625, 797, 1381, 1495, 1513, 1534, 1746, 1875, 2010, 2220, 2223, 2256, 2266, 2269, 2295
<code>\columnbreak</code>	57
<code>\columnbreak</code>	1686
<code>columns</code>	<u>766</u>
<code>columns*</code>	<u>1514</u>
<code>columns-sep</code>	<u>766</u>
<code>columns-sep*</code>	<u>1514</u>
<code>\columnsep</code>	73, 76
<code>\columnsep</code>	2425, 2569
<code>\columnseprule</code>	73, 76
<code>\columnseprule</code>	2429, 2571
Commands provide by enumext :	
<code>\anskey</code>	23, 24, 50, 51, 55, 57, 59–61, 63, 72, 85, 95, 96, 100
<code>\anspic*</code>	23, 61–63, 78–80, 95, 96
<code>\anspic</code>	55, 77–80, 100
<code>\getkeyans</code>	55, 95, 100
<code>\item*</code>	23, 55, 61–63, 65, 66, 86, 93, 95, 96
<code>\itemwidth</code>	81, 88, 89
<code>\item</code>	65, 66, 81, 85, 86, 89, 92
<code>\miniright</code>	23, 39, 46, 47, 73, 74, 76, 77, 100
<code>\printkeyans</code>	24, 55, 96
<code>\setenumext</code>	23, 97, 98
Counters defined by enumext :	
<code>enumXiii</code>	22, 29
<code>enumXii</code>	22, 29
<code>enumXiv</code>	22, 29
<code>enumXi</code>	22, 29
<code>enumXviii</code>	22, 29
<code>enumXvii</code>	22, 29, 86
<code>enumXvi</code>	22, 29

enumXv 22, 29

cs commands:

\cs_generate_variant:Nn 306, 322, 521, 537, 1539, 1548, 1553, 1633, 2210, 2708

\cs_if_exist:NTF 276

\cs_new:Nn 186

\cs_new:Npn 196

\cs_new_eq:NN 212, 213, 214, 218, 219, 251, 252, 255, 256

\cs_new_protected:Nn . 223, 387, 407, 439, 702, 706, 710, 714, 718, 722, 726, 730, 734, 738, 742, 746, 750, 754, 758, 762, 798, 810, 834, 851, 862, 886, 961, 985, 1002, 1064, 1081, 1103, 1138, 1144, 1219, 1233, 1247, 1258, 1269, 1280, 1291, 1302, 1346, 1357, 1386, 1411, 1447, 1454, 1554, 1578, 1585, 1613, 1620, 1737, 1864, 1879, 1907, 1933, 2015, 2019, 2038, 2089, 2123, 2139, 2149, 2165, 2316, 2361, 2379, 2386, 2409, 2439, 2458, 2514, 2537, 2555, 2580, 2591, 2628, 2671, 2684, 2704, 2709, 2725, 2793, 2812, 2864, 2913, 2920, 2940, 2950, 2967, 3107, 3133, 3201, 3220, 3270, 3291, 3297, 3310, 3362, 3472

\cs_new_protected:Npn 178, 182, 259, 274, 291, 301, 307, 395, 414, 508, 522, 1166, 1185, 1329, 1540, 1549, 1669, 1814, 1826, 1848, 1917, 1955, 1963, 2048, 2066, 2100, 2112, 2179, 2213, 2259, 2323, 2332, 2533, 2679, 2744, 2873, 2884, 2973, 2980, 2996, 3004, 3009, 3021, 3152, 3284, 3316, 3323, 3339, 3347, 3357, 3491, 3504, 3551, 3629, 3641

\cs_new_protected_nopar:Nn . . . 2960, 3083, 3303, 3448

\cs_new_protected_nopar:Npn 3027, 3405

\cs_set:Nn 1819

\cs_set:Npn 1747, 1785, 3497

\cs_set_eq:NN . . 2854, 2855, 3029, 3260, 3261, 3407

\cs_set_protected:Nn 202, 626, 642, 654, 666

\cs_set_protected:Npn . 30, 44, 52, 64, 70, 96, 134, 146, 153, 204, 323, 345, 374, 455, 475, 538, 558, 602, 621, 678, 687, 766, 783, 1202, 1368, 1467, 1496, 1514, 1739, 1868, 1999, 2211, 2257

\cs_to_str:N 293, 316

D

\d 192

\DeclareDocumentEnvironment 879

dim commands:

\dim_abs:n 2184, 2189

\dim_add:Nn 2689, 3379, 3400

\dim_compare:nNnTF . 628, 644, 656, 668, 1168, 1187, 2181, 2186, 2192, 2198, 2200, 2202, 2391, 2414, 2541, 2559, 2681, 2727, 2795, 3135, 3203

\dim_compare:nTF 1710

\dim_gset_eq:NN 2804, 3212

\dim_gzero:N 2838, 3246

\dim_new:N 40, 47, 48, 49, 66, 90, 103, 113, 162, 163, 169

\dim_set:Nn . . 304, 616, 1526, 2080, 2184, 2189, 2191, 2194, 2195, 2199, 2201, 2204, 2205, 2207, 2394, 2417, 2543, 2561, 2711, 2729, 2736, 2779, 2797, 3023, 3137, 3144, 3187, 3205

\dim_set_eq:NN 462, 482, 498, 502, 2075, 2222, 2268, 2351, 2425, 2569, 2786, 2789, 2790, 2903, 3014, 3194, 3197, 3198

\dim_use:N 629, 637, 1169, 1175, 1623, 1626, 1631, 2144, 2146, 2392, 2397, 2398, 2405, 2415, 2419, 2420, 2422

\dim_zero:N 2429, 2571, 2690, 2691, 2692

\dim_zero_new:N 2742, 3150

\c_zero_dim 631, 645, 657, 669, 1169, 1187, 1712, 2181, 2186, 2192, 2199, 2392, 2415, 2541, 2559, 2727, 2795, 3135, 3203

E

\end . . 1172, 1190, 1582, 1617, 2444, 2468, 2584, 2601, 2816, 2832, 3224, 3240, 3562, 3567

\endlist 27

\endlist 213

\endlrbox 3086, 3451

\endminipage 27

\endminipage 219

enumext 4, 2296

enumext internal commands:

__enumext_add_pre_parsep: . . . 40, 808, 810, 810

__enumext_after_args_exec: . 37, 702, 714, 2309

__enumext_after_args_exec_v: 38, 718, 730, 2507

__enumext_after_args_exec_vii: . . . 734, 758

__enumext_after_args_exec_viii: 762

__enumext_after_env:n 74

__enumext_after_env:nn . . 74, 88, 182, 182, 2484, 2821, 3121, 3229

__enumext_after_hyperref: . . . 27, 221, 223, 223

__enumext_after_list: 74, 84, 91, 2314, 2458, 2458

\l__enumext_after_list_args_v_tl 732

\l__enumext_after_list_args_vii_tl 760, 3077

\l__enumext_after_list_args_viii_tl 764, 3442

__enumext_after_list_v: . . 77, 2512, 2591, 2591

__enumext_after_list_vii: . . . 2862, 2920, 2920

__enumext_after_list_viii: . . 3268, 3297, 3297

__enumext_after_star_env:nn 82

__enumext_after_stop_list: . . . 37, 38, 702, 710, 2472

__enumext_after_stop_list_v: 38, 718, 726, 2606

\l__enumext_after_stop_list_v_tl 728

__enumext_after_stop_list_vii: 734, 750, 2923

\l__enumext_after_stop_list_vii_tl . . . 752

__enumext_after_stop_list_viii: . 754, 3300

\l__enumext_after_stop_list_viii_tl . . . 756

\l__enumext_align_label_vii_str . . 3069, 3073

\l__enumext_align_label_viii_str . 3434, 3438

\l__enumext_align_label_X_str 153

\c__enumext_all_envs_clist . . 173, 344, 557, 620, 686, 701, 782, 1218

\c__enumext_all_families_seq . . 97, 3591, 3600, 3622

__enumext_anskey_wrapper:n 1471, 1824

__enumext_at_begin_document:n . . 27, 178, 178, 210, 216

__enumext_before_args_exec: 37, 702, 702, 2389

__enumext_before_args_exec_v: 37, 38, 718, 718, 2540

__enumext_before_args_exec_vii: . . 734, 734, 2917

__enumext_before_args_exec_viii: 738, 3294

__enumext_before_keys_exec: 37, 702, 706, 2307

__enumext_before_keys_exec_v: . . 38, 718, 722, 2505

__enumext_before_keys_exec_vii 734

__enumext_before_keys_exec_vii: 38, 742, 2850

__enumext_before_keys_exec_viii: . . 38, 746, 3256

__enumext_before_list: . . . 72, 2301, 2386, 2386

__enumext_before_list_v: . 76, 2500, 2537, 2537


```

\__enumext_before_list_vii: 84, 2845, 2913, 2913
\__enumext_before_list_viii: .. 91, 3252, 3291,
    3291
\l__enumext_before_no_starred_key_v_tl 724
\l__enumext_before_no_starred_key_vii_-
    tl ..... 744
\l__enumext_before_no_starred_key_viii_-
    tl ..... 748
\l__enumext_before_starred_key_v_tl ... 720
\l__enumext_before_starred_key_vii_tl . 736
\l__enumext_before_starred_key_viii_tl 740
\__enumext_calc_hspace:NNNNNNN 68, 2179, 2179,
    2210, 2215, 2261
\__enumext_check_ans_active: .. 53, 1454, 1454,
    2490, 3127
\l__enumext_check_ans_bool ... 50, 65, 117, 1372,
    1376, 1449, 1661, 1950, 2052, 2082, 2451, 2932, 3040
\__enumext_check_ans_count: . 53, 72, 1447, 1447,
    2390, 2916
\__enumext_check_ans_int:n ..... 50
\g__enumext_check_ans_item_tl .. 62, 117, 1949,
    1957, 1961
\__enumext_check_ans_set_int_level: 52, 1411,
    1411, 1451
\g__enumext_check_ans_show_bool 74, 117, 2454,
    2486, 2493
\g__enumext_check_ans_show_h_bool 117, 2934,
    3123, 3130
\l__enumext_columns_sep_v_dim 2559, 2561, 2569
\l__enumext_columns_sep_vii_dim .. 2727, 2729,
    2738, 2783, 2905, 3105
\l__enumext_columns_sep_viii_dim . 3135, 3137,
    3146, 3191, 3470
\l__enumext_columns_v_int 1007, 2557, 2565, 2577,
    2582
\l__enumext_columns_vii_int .. 2732, 2735, 2739,
    2747, 2751, 2754, 2760, 2766, 2770, 2892, 3100, 3111
\l__enumext_columns_viii_int . 3140, 3143, 3147,
    3155, 3159, 3162, 3168, 3174, 3178, 3465, 3476
\g__enumext_count_item_anskey_int 117, 1457,
    1465, 1663
\g__enumext_count_item_number_int .. 62, 117,
    1422, 1427, 1430, 1433, 1441, 1457, 1464, 1952, 2054,
    2084, 3042
\g__enumext_count_item_with_ans_int .... 57
\l__enumext_counter_i_tl ..... 30, 283
\l__enumext_counter_ii_tl ..... 30, 284
\l__enumext_counter_iii_tl ..... 30, 285
\l__enumext_counter_iv_tl ..... 30, 286
\l__enumext_counter_style_for_ref_vii_-
    tl ..... 422, 432, 443, 445
\l__enumext_counter_style_for_ref_viii_-
    tl ..... 449, 451
\l__enumext_counter_style_for_ref_X_tl 142
\c__enumext_counter_style_tl .... 31, 142, 389
\g__enumext_counter_styles_tl . 22, 29, 40, 294,
    312
\l__enumext_counter_v_tl ..... 30, 287
\l__enumext_counter_vi_tl ..... 30, 288
\l__enumext_counter_vii_tl ..... 30, 289, 419
\l__enumext_counter_viii_tl ..... 30, 290, 429
\__enumext_current_env: . 1386, 1386, 2298, 2842
\l__enumext_current_widest_dim 22, 40, 318, 463,
    483, 499, 503
\__enumext_default_item:n ... 2048, 2048, 2097
\__enumext_define_counters:Nn 22, 274, 274, 283,
    284, 285, 286, 287, 288, 289, 290
\__enumext_endminipage: . 27, 216, 219, 885, 2721,
    3085, 3450
\__enumext_fake_item: ..... 626, 626, 2248
\l__enumext_fake_item_indent_v_dim 645, 650
\l__enumext_fake_item_indent_v_tl 647, 2105,
    2109, 2117
\l__enumext_fake_item_indent_vii_dim 657, 662
\l__enumext_fake_item_indent_vii_tl 659, 3081
\l__enumext_fake_item_indent_viii_dim . 669,
    674, 3379, 3400
\l__enumext_fake_item_indent_viii_tl .. 671,
    3446
\l__enumext_fake_item_indent_X_tl ..... 70
\__enumext_fake_item_vii: .... 626, 654, 2284
\__enumext_fake_item_viii: .... 626, 666, 2289
\g__enumext_footnote_arg_seq . 139, 2021, 2034,
    2044
\g__enumext_footnote_int . 139, 2028, 2031, 2033,
    2035
\g__enumext_footnote_int_seq . 139, 2022, 2035,
    2040, 2043
\__enumext_footnotes_key_bool ..... 27
\l__enumext_footnotes_key_bool 24, 27, 87, 129,
    232, 237, 246, 3048, 3096, 3422, 3461
\__enumext_footnotetext:nn ... 2015, 2015, 2045
\__enumext_getkeyans:nn ... 96, 3500, 3504, 3504
\__enumext_getkeyans_aux:n . 95, 3488, 3491, 3491
\l__enumext_hyperref_bool . 24, 27, 28, 129, 228,
    249, 266, 1727, 1937, 3035, 3413
\__enumext_hypertarget:nn 28, 223, 251, 255, 271
\__enumext_if_is_int:n ..... 190
\__enumext_if_is_int:nTF ..... 190, 510, 524
\l__enumext_item_column_pos_vii_int 85, 2754,
    2760, 2766, 2770, 2777, 2963, 3100, 3103
\l__enumext_item_column_pos_viii_int ... 92,
    3162, 3168, 3174, 3178, 3185, 3306, 3465, 3468
\l__enumext_item_column_pos_X_int ..... 153
\g__enumext_item_count_all_vii_int 85, 2778,
    2964, 3111, 3118
\g__enumext_item_count_all_viii_int 92, 3186,
    3307, 3476, 3483
\g__enumext_item_count_all_X_int ..... 153
\__enumext_item_peek_args_vii: 85, 2965, 2967,
    2967
\__enumext_item_peek_args_viii: 92, 3308, 3310,
    3310
\__enumext_item_starred: .. 67, 2139, 2139, 2157
\l__enumext_item_starred_vii_bool 2982, 2998,
    3052
\l__enumext_item_starred_viii_bool 3325, 3341,
    3426
\l__enumext_item_starred_X_bool ..... 153
\__enumext_item_std:w 27, 65, 66, 80, 210, 214, 2057,
    2063, 2087, 2105, 2109, 2117, 2702
\g__enumext_item_symbol_aux_vii_tl 3006, 3054,
    3057, 3061, 3063
\g__enumext_item_symbol_aux_X_tl ..... 153
\l__enumext_item_symbol_sep_vii_dim .. 3015,
    3023, 3060, 3062
\g__enumext_item_symbol_tl 22, 65, 35, 2072, 2145,
    2162
\l__enumext_item_symbol_vii_tl ..... 3057

```


<code>\l__enumext_item_text_vii_box</code>	3047, 3088, 3095
<code>\l__enumext_item_text_viii_box</code>	3421, 3453, 3460
<code>\l__enumext_item_text_X_box</code>	153
<code>\l__enumext_item_width_vii_dim</code>	2736, 2781, 2789, 2790
<code>\l__enumext_item_width_viii_dim</code>	3144, 3189, 3197, 3198
<code>\l__enumext_item_width_X_dim</code>	153
<code>\l__enumext_itemindent_X_dim</code>	44
<code>\l__enumext_itemsep_vii_skip</code>	3117
<code>\l__enumext_itemsep_viii_skip</code>	3482
<code>\l__enumext_joined_item_aux_vii_int</code>	2775, 2776, 2777, 2778, 2784
<code>\l__enumext_joined_item_aux_viii_int</code>	3183, 3184, 3185, 3186, 3192
<code>\l__enumext_joined_item_aux_X_int</code>	153
<code>__enumext_joined_item_vii:w</code>	85, 2970, 2971, 2973, 2973
<code>\l__enumext_joined_item_vii_int</code>	2746, 2747, 2750, 2752, 2758, 2763, 2768, 2773, 2775, 2781
<code>__enumext_joined_item_viii:w</code>	92, 3313, 3314, 3316, 3316
<code>\l__enumext_joined_item_viii_int</code>	3154, 3155, 3158, 3160, 3166, 3171, 3176, 3181, 3183, 3189
<code>\l__enumext_joined_item_X_int</code>	153
<code>\l__enumext_joined_width_vii_dim</code>	2779, 2786, 2789, 3078, 3090
<code>\l__enumext_joined_width_viii_dim</code>	3187, 3194, 3197, 3443, 3455
<code>\l__enumext_joined_width_X_dim</code>	153
<code>__enumext_keyans_addto_prop:n</code>	61, 1848, 1848, 2119, 2634
<code>__enumext_keyans_addto_seq:n</code>	62, 1917, 1917, 2121, 2636
<code>__enumext_keyans_addto_seq_link:</code>	1917, 1931, 1933, 3372
<code>__enumext_keyans_anspic_code:nnn</code>	78, 2625, 2628, 2628
<code>__enumext_keyans_check_ans:nn</code>	62, 63, 1955, 1955, 2510, 2666, 3266
<code>__enumext_keyans_default_item:n</code>	66, 2100, 2100, 2135
<code>\l__enumext_keyans_env_bool</code>	20, 2365, 2521, 2605
<code>__enumext_keyans_fake_item:</code>	626, 642, 2238
<code>\l__enumext_keyans_level_h_int</code>	20, 1895, 3272, 3273
<code>\l__enumext_keyans_level_int</code>	20, 1160, 1650, 1890, 2520, 2524, 2619
<code>__enumext_keyans_make_label:</code>	30, 68, 2165, 2165, 2237
<code>__enumext_keyans_mini_addvspace:</code>	45, 76, 1064, 1064, 2549
<code>__enumext_keyans_mini_right_cmd:n</code>	47, 1162, 1185, 1185
<code>__enumext_keyans_mini_set_vskip:</code>	44, 1002, 1002, 1066
<code>__enumext_keyans_multi_addvspace:</code>	76, 851, 862, 2574
<code>__enumext_keyans_multi_set_vskip:</code>	41, 851, 851, 864
<code>__enumext_keyans_multicols_start:</code>	76, 2553, 2555, 2555
<code>__enumext_keyans_multicols_stop:</code>	77, 1189, 2580, 2580, 2604
<code>__enumext_keyans_parse_keys:n</code>	2499, 2533, 2533
<code>\l__enumext_keyans_pic_above_int</code>	112, 2712, 2713, 2715
<code>\l__enumext_keyans_pic_above_skip</code>	80, 112, 2657, 2696
<code>__enumext_keyans_pic_arg_two:</code>	79, 2655, 2684, 2684
<code>\l__enumext_keyans_pic_below_int</code>	112, 2712, 2713, 2716
<code>\l__enumext_keyans_pic_body_seq</code>	78–80, 112, 2623, 2662, 2720
<code>__enumext_keyans_pic_do:n</code>	80, 2662, 2664, 2704, 2704, 2708
<code>\l__enumext_keyans_pic_level_int</code>	20, 1152, 1654, 1851, 1885, 1920, 2673, 2674
<code>__enumext_keyans_pic_row:n</code>	80, 2706, 2709, 2709
<code>__enumext_keyans_pic_safe_exec:</code>	79, 2651, 2671, 2671
<code>__enumext_keyans_pic_skip_abs:N</code>	79, 2679, 2679, 2695
<code>\l__enumext_keyans_pic_width_dim</code>	112, 2711, 2718
<code>__enumext_keyans_redefine_item:</code>	67, 2123, 2123, 2236
<code>__enumext_keyans_safe_exec:</code>	2498, 2514, 2514
<code>__enumext_keyans_show_left:n</code>	66, 1963, 1963, 2115, 2642
<code>__enumext_keyans_starred_item:n</code>	66, 2112, 2112, 2131
<code>__enumext_keyans_store_ref:</code>	61, 1864, 1864, 2120, 2635, 3370
<code>__enumext_keyans_store_ref_aux_i:</code>	61, 1864, 1876, 1879
<code>__enumext_keyans_store_ref_aux_ii:</code>	62, 1864, 1905, 1907
<code>\l__enumext_keyans_tmpa_dim</code>	82, 3378, 3379, 3399, 3400
<code>\l__enumext_keyans_tmpa_tl</code>	23, 93, 82, 2114, 2118, 3352, 3375, 3377, 3378, 3396, 3398, 3399
<code>\l__enumext_keyans_tmpb_tl</code>	93, 82, 3353, 3365, 3367
<code>\l__enumext_label_copy_i_tl</code>	1781, 1883, 1888, 1893, 1898
<code>\l__enumext_label_copy_v_tl</code>	1893
<code>\l__enumext_label_copy_vi_tl</code>	1888
<code>\l__enumext_label_copy_vii_tl</code>	1756, 1767, 1798, 1883
<code>\l__enumext_label_copy_viii_tl</code>	1898
<code>\l__enumext_label_copy_X_tl</code>	131
<code>\l__enumext_label_fill_left_v_tl</code>	2169
<code>\l__enumext_label_fill_left_X_tl</code>	70
<code>\l__enumext_label_fill_right_v_tl</code>	2176
<code>\l__enumext_label_fill_right_X_tl</code>	70
<code>\l__enumext_label_font_style_v_tl</code>	2170, 2646
<code>\l__enumext_label_font_style_vii_tl</code>	3066
<code>\l__enumext_label_font_style_viii_tl</code>	3431
<code>\l__enumext_label_i_tl</code>	455
<code>\l__enumext_label_ii_tl</code>	455
<code>\l__enumext_label_iii_tl</code>	455
<code>\l__enumext_label_iv_tl</code>	455
<code>__enumext_label_style:Nnn</code>	22, 29, 307, 307, 322, 460, 480, 496, 500
<code>\l__enumext_label_v_tl</code>	61, 62, 493, 1856, 1925, 1967, 1974, 1989, 1996, 2114, 2118, 2502, 2641, 2643

```

\l__enumext_label_vi_tl . 61, 62, 493, 1853, 1922,
    2641, 2643, 2647
\l__enumext_label_vii_tl . 475, 2993, 3018, 3025
\l__enumext_label_viii_tl 475, 3336, 3360, 3364,
    3377, 3398
\l__enumext_label_width_by_box .. 40, 303, 304
\__enumext_label_width_by_box:Nn 29, 301, 301,
    306, 318, 534, 3378, 3399
\l__enumext_labelsep_i_dim ... 1971, 1993, 3381,
    3402
\l__enumext_labelsep_v_dim ..... 2564
\l__enumext_labelsep_vii_dim . 2731, 2740, 2782,
    3016, 3076, 3092
\l__enumext_labelsep_viii_dim 3139, 3148, 3190,
    3441, 3457
\l__enumext_labelwidth_i_dim . 1970, 1992, 3381,
    3402
\l__enumext_labelwidth_v_dim ..... 2564
\l__enumext_labelwidth_vii_dim ... 2731, 2739,
    2782, 3069, 3073, 3091
\l__enumext_labelwidth_viii_dim .. 3139, 3147,
    3190, 3434, 3438, 3456
\l__enumext_leftmargin_tmp_v_bool . 79, 2686
\l__enumext_leftmargin_tmp_X_bool ..... 44
\l__enumext_leftmargin_tmp_X_dim ..... 44
\l__enumext_leftmargin_X_dim ..... 44
\__enumext_level: 186, 186, 398, 400, 401, 409, 411,
    629, 633, 637, 704, 708, 712, 716, 800, 802, 804, 806,
    839, 841, 843, 845, 849, 889, 892, 911, 920, 926, 931,
    935, 946, 950, 951, 956, 992, 996, 1169, 1175, 1222,
    1224, 1226, 1229, 1236, 1238, 1240, 1243, 1558, 1566,
    1570, 1574, 1819, 1822, 1823, 2056, 2057, 2061, 2062,
    2063, 2070, 2072, 2076, 2077, 2080, 2086, 2087, 2141,
    2144, 2146, 2153, 2154, 2155, 2158, 2161, 2304, 2306,
    2334, 2339, 2340, 2341, 2343, 2347, 2352, 2353, 2354,
    2356, 2369, 2374, 2381, 2392, 2394, 2397, 2398, 2400,
    2405, 2412, 2415, 2417, 2419, 2420, 2421, 2422, 2425,
    2431, 2436, 2442, 2445, 2447, 2460
\l__enumext_level_h_int 20, 417, 441, 1392, 1436,
    1775, 1792, 2367, 2866, 2867
\l__enumext_level_int 20, 188, 812, 963, 1156, 1402,
    1413, 1419, 1752, 1762, 1768, 1774, 1782, 1790, 1797,
    2251, 2318, 2319, 2326, 2372, 2427, 2488, 2528, 2615,
    2944, 2954, 3125, 3279
\__enumext_list_arg_two_i: ..... 2211
\__enumext_list_arg_two_ii: ..... 2211
\__enumext_list_arg_two_iii: ..... 2211
\__enumext_list_arg_two_iv: ..... 2211
\__enumext_list_arg_two_v: . 67, 2211, 2504, 2687
\__enumext_list_arg_two_vii: ..... 2257, 2849
\__enumext_list_arg_two_viii: ..... 2257, 3255
\l__enumext_listoffset_v_dim ..... 2566
\l__enumext_listparindent_vii_dim .... 3079
\l__enumext_listparindent_viii_dim ... 3444
\__enumext_make_label: 30, 65, 67, 2149, 2149, 2246
\l__enumext_mark_answer_sym_tl . 56, 107, 1474,
    1628, 1834, 1978, 3385
\l__enumext_mark_position_str 107, 1478, 1479,
    1501, 1502, 1626
\l__enumext_mark_ref_sym_tl .. 107, 1488, 1732,
    1945
\__enumext_mini_addvspace: 43, 73, 985, 985, 2402
\__enumext_mini_addvspace_vii: 46, 1138, 1138,
    2807
\__enumext_mini_addvspace_viii: 46, 1138, 1144,
    3215
__enumext_mini_env* ..... 879
\__enumext_mini_right_cmd:n 47, 1164, 1166, 1166
\__enumext_mini_set_vskip: ... 42, 886, 886, 987
\__enumext_mini_set_vskip_vii: 45, 1081, 1081,
    1140
\__enumext_mini_set_vskip_viii: 45, 1081, 1103,
    1146
\__enumext_minipage:w 27, 216, 218, 881, 2718, 3078,
    3443
\l__enumext_minipage_active_v_bool .. 76, 77,
    2547, 2572, 2585, 2593
\g__enumext_minipage_active_vii_bool ... 82,
    2818, 2823, 2835
\l__enumext_minipage_active_vii_bool . 2803,
    2814
\g__enumext_minipage_active_viii_bool 3226,
    3231, 3243
\l__enumext_minipage_active_viii_bool 3211,
    3222
\g__enumext_minipage_active_X_bool ... 153
\l__enumext_minipage_active_X_bool .... 58
\g__enumext_minipage_after_skip 58, 1085, 1097,
    2833, 3241
\l__enumext_minipage_after_skip 42, 43, 74, 77,
    58, 902, 917, 937, 953, 968, 974, 980, 994, 1004, 1013,
    1016, 1028, 1046, 1057, 1073, 1105, 1118, 1132, 2469,
    2602
\g__enumext_minipage_center_vii_bool . 2827,
    2836
\g__enumext_minipage_center_viii_bool 3235,
    3244
\g__enumext_minipage_center_X_bool ... 153
\l__enumext_minipage_hsep_v_dim ... 76, 2545
\l__enumext_minipage_hsep_vii_dim .... 2801
\l__enumext_minipage_hsep_viii_dim ... 3209
\l__enumext_minipage_left_skip 42, 76, 58, 894,
    909, 928, 943, 990, 1000, 1005, 1011, 1020, 1037, 1049,
    1069, 1079, 1083, 1088, 1092, 1106, 1110, 1124, 1142,
    1148
\l__enumext_minipage_left_v_dim 76, 2543, 2551
\l__enumext_minipage_left_vii_dim 2797, 2809
\l__enumext_minipage_left_viii_dim 3205, 3217
\l__enumext_minipage_left_X_dim ..... 58
\g__enumext_minipage_right_skip 58, 1084, 1089,
    1093, 2826, 3234
\l__enumext_minipage_right_skip .. 42, 58, 898,
    913, 933, 948, 1006, 1012, 1024, 1042, 1053, 1107,
    1114, 1128, 1176, 1193
\l__enumext_minipage_right_v_dim .. 76, 1187,
    1192, 2541, 2545
\g__enumext_minipage_right_vii_dim 82, 2805,
    2825, 2838
\l__enumext_minipage_right_vii_dim 82, 2795,
    2800, 2806
\g__enumext_minipage_right_viii_dim .. 3213,
    3233, 3246
\l__enumext_minipage_right_viii_dim .. 3203,
    3208, 3214
\g__enumext_minipage_right_X_dim ..... 153
\g__enumext_minipage_right_X_skip .... 153
\g__enumext_minipage_stat_int . 73, 76, 58, 1181,
    1198, 2401, 2462, 2467, 2548, 2595, 2600
\g__enumext_miniright_code_vii_tl . 82, 2831,
    2837

```

```

\g__enumext_miniright_code_viii_tl 3239, 3245
\g__enumext_miniright_code_X_tl ..... 153
\__enumext_multi_addvspace: ... 40, 73, 834, 834,
    2433
\__enumext_multi_set_vskip: .. 40, 798, 798, 836
\l__enumext_multicols_above_ii_skip ... 817
\l__enumext_multicols_above_iii_skip .. 823
\l__enumext_multicols_above_iv_skip ... 829
\l__enumext_multicols_above_v_skip 853, 867,
    877
\l__enumext_multicols_above_X_skip .... 52
\l__enumext_multicols_below_v_skip 857, 871,
    2587
\l__enumext_multicols_below_X_skip .... 52
\__enumext_multicols_start: 73, 2407, 2409, 2409
\__enumext_multicols_stop: 73, 1171, 2439, 2439,
    2471
\__enumext_newlabel:nn 24, 28, 60, 259, 259, 1808,
    1911
\l__enumext_newlabel_arg_one_tl 24, 28, 60, 61,
    131, 1731, 1801, 1809, 1900, 1912, 1943
\l__enumext_newlabel_arg_two_tl 24, 28, 59, 131,
    1755, 1765, 1779, 1795, 1810, 1887, 1892, 1897, 1913
\__enumext_parse_keys:n ..... 2300, 2323, 2323
\__enumext_parse_keys_vii:n .. 2844, 2873, 2873
\__enumext_parse_keys_viii:n . 3251, 3284, 3284
\__enumext_parse_store_keys:n . 71, 2329, 2332,
    2332
\__enumext_parse_store_keys_vii:n . 83, 2880,
    2884, 2884
\l__enumext_parsep_i_skip . 815, 817, 966, 1014
\l__enumext_parsep_ii_skip ..... 821, 823, 972
\l__enumext_parsep_iii_skip .... 827, 829, 978
\l__enumext_parsep_vii_skip ..... 3080
\l__enumext_parsep_viii_skip ..... 3445
\l__enumext_partopsep_v_skip .. 869, 873, 1040,
    1044, 1051, 1055, 1071, 1075
\l__enumext_partopsep_viii_skip ..... 1116
\__enumext_phantomsection: 28, 223, 252, 256, 272
\__enumext_print_footnote: ... 2015, 2038, 3098,
    3463
\__enumext_print_keyans_box:NN 56, 1620, 1620,
    1633, 1821, 1969, 1991, 3381, 3402
\l__enumext_print_keyans_i_tl .... 3514, 3543
\l__enumext_print_keyans_ii_tl ... 3519, 3544
\l__enumext_print_keyans_iii_tl .. 3524, 3545
\l__enumext_print_keyans_iv_tl ... 3529, 3546
\l__enumext_print_keyans_vii_tl .. 3534, 3547
\l__enumext_print_keyans_X_tl ..... 96
\__enumext_printkeyans:nnn . 97, 3548, 3551, 3551
\__enumext_redefine_item: . 66, 2089, 2089, 2245
\l__enumext_ref_aux_tl 142, 398, 400, 403, 419, 421,
    424, 429, 431, 434
\l__enumext_ref_key_arg_tl .. 142, 392, 397, 404,
    416, 425, 435
\__enumext_regex_label_ref_key: . 31, 387, 387,
    399, 420, 430
\__enumext_register_counter_style:Nn .. 291,
    291, 296, 297, 298, 299, 300
\__enumext_remove_extra_parsep_vii: .. 2859,
    3107, 3107
\__enumext_remove_extra_parsep_viii: . 3265,
    3472, 3472
\__enumext_renew_footnote: ... 2015, 2019, 3050,
    3424
\l__enumext_resume_bool .... 22, 35, 1355, 2228
\__enumext_resume_counter: . 51, 1317, 1346, 1346
\__enumext_resume_counter_star: ..... 1319
\__enumext_resume_counter_vii: 51, 1326, 1346,
    1357
\g__enumext_resume_int 22, 74, 35, 1350, 1361, 2229,
    2476
\l__enumext_resume_vii_bool ... 35, 1366, 2275
\g__enumext_resume_vii_int .. 84, 35, 2276, 2925
\__enumext_safe_exec: ..... 2299, 2316, 2316
\__enumext_safe_exec_vii: ... 2843, 2864, 2864
\__enumext_safe_exec_viii: ... 3250, 3270, 3270
\__enumext_set_error:nn ..... 3629, 3639, 3641
\__enumext_set_label_ref:n ... 31, 395, 395, 467
\__enumext_set_label_ref_h:n . 31, 414, 414, 487
\__enumext_set_parse:n ..... 3612, 3629, 3629
\l__enumext_setkey_tmpa_int ... 91, 3605, 3609
\l__enumext_setkey_tmpa_seq 91, 3603, 3613, 3619,
    3621, 3623, 3636
\l__enumext_setkey_tmpa_tl .... 91, 3611, 3615
\l__enumext_setkey_tmpb_seq 91, 3604, 3607, 3611,
    3612
\l__enumext_setkey_tmpb_tl 91, 3631, 3633, 3634
\l__enumext_show_answer_bool . 107, 1482, 1486,
    1505, 1509, 1828, 1965, 2638, 3373
\__enumext_show_length:nnn .. 36, 196, 196, 3681,
    3682, 3683, 3684, 3685, 3686, 3687, 3688, 3689, 3690,
    3696, 3697, 3698, 3699, 3700, 3701, 3702, 3703, 3704,
    3705
\l__enumext_show_position_bool . 63, 107, 1483,
    1485, 1506, 1508, 1832, 1976, 2639, 3383
\g__enumext_standar_bool ..... 20, 1394, 2475
\l__enumext_standar_bool . 20, 1439, 1760, 1773,
    1789, 2321, 2474
\g__enumext_standar_keyans_pic_star_env_-
    int ..... 128
\g__enumext_standar_keyans_star_env_int 127
\g__enumext_standar_star_env_int . 124, 1395,
    1397
\__enumext_standard_item_vii:w .. 85, 86, 2978,
    2980, 2980
\__enumext_standard_item_viii:w 92, 3321, 3323,
    3323
\g__enumext_starred_bool . 83, 84, 20, 1404, 1751,
    1761, 1791, 1881, 2452, 2932, 2937
\l__enumext_starred_bool . 83, 84, 20, 1418, 1684,
    1692, 1776, 1817, 2871, 2938
\__enumext_starred_columns_set_vii: .. 2725,
    2725, 2852
\__enumext_starred_columns_set_viii: . 3133,
    3133, 3258
\__enumext_starred_item:nn ... 2066, 2066, 2095
\__enumext_starred_item_exec: . 93, 3362, 3362,
    3428
\__enumext_starred_item_vii:w 85, 86, 2977, 2996,
    2996
\__enumext_starred_item_vii_aux_i:w .. 2996,
    3001, 3004
\__enumext_starred_item_vii_aux_ii:w . 2996,
    3002, 3007, 3009
\__enumext_starred_item_vii_aux_iii:w 2996,
    3012, 3021

```

__enumext_starred_item_viii:w . . 92, 93, 3320, 3339, 3339
 __enumext_starred_item_viii_aux_i:w . 3339, 3344, 3347
 __enumext_starred_item_viii_aux_ii:w 3339, 3345, 3355, 3357
 __enumext_starred_joined_item_vii:n . 81, 85, 2744, 2744, 2975
 __enumext_starred_joined_item_viii:n 89, 92, 3152, 3152, 3318
 \g__enumext_starred_keyans_star_env_int 126
 \g__enumext_starred_star_env_int . 125, 1405, 1406
 __enumext_start_from:NNn 33, 508, 508, 521, 543
 __enumext_start_item_tmp_vii: 83, 2855, 2960, 2960
 __enumext_start_item_tmp_viii: 90, 3261, 3303, 3303
 __enumext_start_item_vii:w 86, 2988, 2993, 3018, 3025, 3027, 3027
 __enumext_start_item_viii:w . . 92, 3331, 3336, 3360, 3405, 3405
 __enumext_start_list:nn 27, 69, 79, 210, 212, 2303, 2501, 2652, 2847, 3253
 __enumext_start_mini_vii: . 84, 2793, 2793, 2918
 __enumext_start_mini_viii: 91, 3201, 3201, 3295
 __enumext_start_store_level: . 72, 2302, 2361, 2361
 __enumext_start_store_level_vii: . 85, 2846, 2940, 2940
 \l__enumext_start_X_int 70, 538
 __enumext_stop_item_tmp_vii: . 83, 85, 86, 2854, 2858, 2962, 3029
 __enumext_stop_item_tmp_viii: . . 90, 92, 3260, 3264, 3305, 3407
 __enumext_stop_item_vii: 86, 87, 3029, 3083, 3083
 __enumext_stop_item_viii: . 95, 3407, 3448, 3448
 __enumext_stop_list: . . 27, 210, 213, 2312, 2511, 2665, 2860, 3267
 __enumext_stop_mini_vii: 82, 84, 2812, 2812, 2922
 __enumext_stop_mini_viii: . 91, 3201, 3220, 3299
 __enumext_stop_store_level: . . 72, 2313, 2361, 2379
 __enumext_stop_store_level_vii: . . 85, 2861, 2940, 2950
 \l__enumext_store_active_bool 23, 50, 71, 83, 82, 1340, 1348, 1359, 1646, 2327, 2364, 2516, 2523, 2611, 2669, 2878, 2942, 2952, 3278
 __enumext_store_addto_prop:n 55, 61, 1539, 1540, 1548, 1671, 1862, 3369
 __enumext_store_addto_seq:n 55, 62, 1549, 1549, 1553, 1560, 1574, 1582, 1591, 1609, 1617, 1735, 1948
 \l__enumext_store_ans_bool 117, 1375, 1556, 1580, 1587, 1615, 1659
 \l__enumext_store_anskey_arg_tl 23, 57, 58, 82, 1677, 1686, 1688, 1694, 1702, 1705, 1715, 1720, 1723, 1729, 1735
 __enumext_store_anskey_code:nnnn . 57, 1665, 1669, 1669
 __enumext_store_anskey_show_left:n 60, 1676, 1826, 1826
 __enumext_store_anskey_show_wrap:n 60, 1814, 1814, 1830, 1845
 \l__enumext_store_columns_break_bool . 1640, 1683
 \l__enumext_store_columns_join_int 82, 1691, 1696
 \l__enumext_store_columns_sep_vii_bool 2899
 \l__enumext_store_columns_sep_vii_dim 2904, 2908
 \l__enumext_store_columns_sep_X_bool . . . 96
 \l__enumext_store_columns_sep_X_dim 96
 \l__enumext_store_columns_vii_bool . . . 2886
 \l__enumext_store_columns_vii_int 2891, 2895
 \l__enumext_store_columns_X_bool 96
 \l__enumext_store_columns_X_int 96
 __enumext_store_internal_ref: . . 57, 59, 1674, 1737, 1737
 \l__enumext_store_item_symbol_sep_dim 1638, 1712, 1717
 \l__enumext_store_item_symbol_tl . 1636, 1703, 1707
 \l__enumext_store_keyans_label_tl 23, 61, 62, 82, 1850, 1853, 1856, 1860, 1862, 1919, 1922, 1925, 1929, 1939, 1948, 1949, 3349, 3364, 3367, 3369, 3371
 __enumext_store_level_close: . 55, 1554, 1578, 2383
 __enumext_store_level_close_vii: 1585, 1613, 2956
 __enumext_store_level_open: . . 54, 55, 71, 1554, 1554, 2370, 2375
 __enumext_store_level_open_vii: . . 83, 1585, 1585, 2946
 \g__enumext_store_name_tl 23, 74, 82, 1459, 1462, 2455, 2494, 2935, 3131
 \l__enumext_store_name_tl 23, 50, 82, 1331, 1332, 1334, 1336, 1338, 1352, 1363, 1542, 1544, 1551, 1803, 1804, 1840, 1902, 1903, 1984, 2455, 2477, 2480, 2926, 2929, 2935, 3391
 \l__enumext_store_opt_vii_tl . 1589, 1599, 1605, 1609, 2893, 2906
 \l__enumext_store_opt_X_tl 96
 \l__enumext_store_ref_key_bool 57, 1491, 1672, 1726, 1866, 1936
 \l__enumext_store_upper_level_X_bool . . . 96
 \l__enumext_store_write_aux_file_tl 24, 60, 62, 131, 1806, 1812, 1909, 1915
 __enumext_storing_set:n 50, 51, 1315, 1324, 1329, 1329
 \l__enumext_the_counter_vii_tl 421
 \l__enumext_the_counter_viii_tl 431
 \l__enumext_the_counter_X_tl 142
 __enumext_tmp:n 30, 34, 44, 51, 52, 57, 64, 69, 70, 81, 96, 106, 134, 138, 146, 152, 153, 172, 204, 208, 621, 625, 1368, 1385, 1467, 1495, 1496, 1513, 1739, 1746, 1747, 1768, 1782, 1785, 1797, 1868, 1875, 2211, 2256, 2257, 2295
 __enumext_tmp:nn 323, 344, 345, 373, 374, 386, 538, 557, 602, 620, 678, 686, 687, 701, 766, 782, 783, 797, 1202, 1218, 1514, 1538, 1999, 2014
 __enumext_tmp:nnn 455, 471, 472, 473, 474, 475, 491, 492
 __enumext_tmp:nnnnn 558, 583, 586, 589, 591, 593, 596, 599
 __enumext_tmp:w 3497, 3500
 \l__enumext_tmpa_vii_int 2735, 2738
 \l__enumext_tmpa_viii_int 3143, 3146
 \l__enumext_tmpa_X_int 153

`\l__enumext_topsep_v_skip` 855, 859, 1009, 1022, 1030, 1035, 1055, 1059, 2668, 2699

`\l__enumext_topsep_vii_skip` .. 1086, 1095, 1099

`\l__enumext_topsep_viii_skip` . 1108, 1130, 1134

`__enumext_use_key_ref:` 31, 407, 407, 2247

`__enumext_use_key_ref_h:` .. 32, 439, 439, 2281

`\l__enumext_vspace_a_star_v_bool` 1251

`\l__enumext_vspace_a_star_vii_bool` ... 1273

`\l__enumext_vspace_a_star_viii_bool` ... 1284

`\l__enumext_vspace_a_star_X_bool` 70

`__enumext_vspace_above:` .. 48, 1219, 1219, 2388

`__enumext_vspace_above_v:` . 49, 1247, 1247, 2539

`\l__enumext_vspace_above_v_skip` .. 1249, 1253, 1255

`__enumext_vspace_above_vii:` .. 49, 1269, 1269, 2915

`\l__enumext_vspace_above_vii_skip` 1271, 1275, 1277

`__enumext_vspace_above_viii:` . 49, 1269, 1280, 3293

`\l__enumext_vspace_above_viii_skip` 1282, 1286, 1288

`\l__enumext_vspace_b_star_v_bool` 1262

`\l__enumext_vspace_b_star_vii_bool` ... 1295

`\l__enumext_vspace_b_star_viii_bool` ... 1306

`\l__enumext_vspace_b_star_X_bool` 70

`__enumext_vspace_below:` .. 48, 1233, 1233, 2473

`__enumext_vspace_below_v:` . 49, 1258, 1258, 2607

`\l__enumext_vspace_below_v_skip` .. 1260, 1264, 1266

`__enumext_vspace_below_vii:` .. 49, 1291, 1291, 2924

`\l__enumext_vspace_below_vii_skip` 1293, 1297, 1299

`__enumext_vspace_below_viii:` . 49, 1291, 1302, 3301

`\l__enumext_vspace_below_viii_skip` 1304, 1308, 1310

`__enumext_widest_from:nNNn` .. 34, 522, 522, 537, 549

`\g__enumext_widest_label_tl` 22, 29, 40, 311, 315, 319

`\l__enumext_wrap_label_opt_v_bool` 2108

`\l__enumext_wrap_label_opt_vii_bool` 86, 2987

`\l__enumext_wrap_label_opt_viii_bool` 92, 3330

`\l__enumext_wrap_label_opt_X_bool` 70

`\l__enumext_wrap_label_v_bool` 2104, 2108, 2116, 2171

`\l__enumext_wrap_label_vii_bool` 86, 2986, 2991, 2999, 3067

`\l__enumext_wrap_label_viii_bool` .. 92, 3329, 3334, 3342, 3432

`\l__enumext_wrap_label_X_bool` 70

`__enumext_wrapper_label_v:n` 2173, 2647

`__enumext_wrapper_label_vii:n` 3070

`__enumext_wrapper_label_viii:n` 3435

`__enumext_zero_count_level:` 202, 202

`__enumext_zero_parsep:` 43, 906, 961, 961

`enumext*` 4, 2840

`enumXi` 283

`enumXii` 283

`enumXiii` 283

`enumXiv` 283

`enumXv` 283

`enumXvi` 283

`enumXvii` 283

`enumXviii` 283

Environments provide by `enumext`:

`enumext*` .. 21, 22, 24–26, 29–33, 35, 36, 38, 39, 45, 46, 49–51, 53–59, 61, 64, 71, 72, 83, 85, 86, 88, 90, 92, 94, 96, 99, 101

`enumext` 21, 22, 24, 26, 29–32, 34–37, 39–48, 50–57, 59, 61, 64–69, 71, 72, 74, 75, 79, 80, 82, 85, 96, 99, 100

`keyans*` 21–23, 25, 26, 29–33, 35, 36, 38, 39, 45, 46, 49, 51, 54, 55, 61, 64, 91, 99, 101

`keyanspic` 21–24, 29, 30, 33, 46, 50, 51, 55, 61–63, 77–80, 100

`keyans` 21–24, 26, 29, 30, 33–39, 41, 44–51, 54, 55, 61–63, 67–69, 75, 77–79, 82, 92, 99, 100

Environments:

`enumext*` 70

`keyans*` 70

`list` 26, 27, 68, 69, 71

`lrbox` 80, 87, 94, 95

`minipage` 26, 27, 39, 41, 77, 79, 80, 87, 95

`multicols` 39–42, 47, 73, 74, 76, 77

exp commands:

`\exp_after:wN` 3500

`\exp_args:Ne` 2325, 3488

`\exp_not:N` 150, 314, 403, 424, 434, 635, 649, 650, 661, 662, 673, 674, 1731, 1837, 1838, 1941, 1981, 1982, 3388, 3389, 3497

`\exp_not:n` 403, 404, 424, 425, 434, 435, 636, 1522, 1529, 1696, 1707, 1717, 1731, 1732, 1809, 1912, 1943, 1945, 2343, 2356, 2895, 2908

F

`\fbox` 1472

file commands:

`\file_input_stop:` 3798

`first` 687

`font` 323

`\footnote` 64

`\footnote` 64, 2023

`\footnotemark` 2033

`\footnotesize` 1838, 1982, 3389

`\footnotetext` 2017

G

`\getkeyans` 13, 95, 3486

group commands:

`\group_begin:` .. 1658, 1836, 1980, 3046, 3065, 3387, 3420, 3430, 3508, 3542

`\group_end:` 1667, 1843, 1987, 3075, 3087, 3394, 3440, 3452, 3510, 3549

H

`\hbadness` 3094, 3459

hbox commands:

`\hbox_set:Nn` 303

`\hfill` 353, 357, 362, 363, 1173, 1191, 1731, 1941, 2817, 3225

hook commands:

`\hook_gput_code:nnn` 9, 180, 184, 221

`\hook_gset_rule:nnnn` 222

`\hspace` 3105, 3470

`\hyperlink` 58, 62

`\hyperlink` 1731, 1941

`\hypertarget` 28

`\hypertarget` 251

I

\IfHyperBoolean 229

\IfPackageLoadedTF 11, 225, 239

\ignorespaces 638

\inputlineno 1395, 1405

int commands:

 \int_add:Nn 2777, 3185

 \int_case:nn 812, 963, 1413, 1436

 \int_compare:nNnTF 417, 441, 888, 1007, 1152, 1156,
 1160, 1392, 1402, 1456, 1650, 1654, 1851, 1885, 1890,
 1895, 1920, 2319, 2367, 2372, 2411, 2427, 2441, 2462,
 2488, 2524, 2528, 2557, 2582, 2595, 2615, 2619, 2674,
 2747, 2757, 2773, 2867, 2944, 2954, 3100, 3109, 3125,
 3155, 3165, 3181, 3273, 3279, 3465, 3474, 3609

 \int_compare_p:nNn .. 1419, 1752, 1762, 1774, 1775,
 1790, 1792

 \int_decr:N 2776, 3184

 \int_eval:n 1544, 1804, 1838, 1903, 1982, 2229, 2232,
 2276, 2279, 2765, 3173, 3389

 \int_from_alph:n 516, 530

 \int_from_roman:n 518, 532

 \int_gadd:Nn 2778, 3186

 \int_gdecr:N 1422, 1427, 1430, 1433, 1441

 \int_gincr:N 1663, 1952, 2054, 2084, 2401, 2548, 2964,
 3042, 3307

 \int_gset:Nn 1350, 1361, 1395, 1405, 2031

 \int_gset_eq:NN 2028, 2476, 2479, 2925, 2928

 \int_gzero:N 206, 1181, 1198, 1464, 1465, 2467, 2600,
 3118, 3483

 \int_if_exist:NnTF 1341, 2477, 2926

 \int_incr:N 2318, 2520, 2673, 2866, 2963, 3272, 3306

 \int_mod:nn 3111, 3476

 \int_new:N 20, 21, 22, 23, 24, 36, 38, 58, 74, 86, 93, 101,
 114, 115, 122, 123, 124, 125, 126, 127, 128, 139, 156,
 157, 158, 159, 160, 1343

 \int_set:Nn 512, 516, 518, 1519, 1691, 2712, 2713, 2735,
 2746, 2752, 2768, 3094, 3143, 3154, 3160, 3176, 3459,
 3605

 \int_set_eq:NN 2338, 2775, 2890, 3183

 \int_show:N 1397

 \int_step_function:nnN 1768, 1782, 1797

 \int_step_inline:nnn 2714, 3632

 \int_to_roman:n 188, 1748, 1786

 \int_use:N .. 889, 1352, 1363, 2232, 2251, 2279, 2326,
 2412, 2421, 2436, 2442, 2750, 2751, 2763, 3158, 3159,
 3171

 \int_zero:N 3103, 3468

 \c_one_int . 1984, 2735, 2754, 2760, 2766, 2770, 2773,
 3143, 3162, 3168, 3174, 3178, 3181

 \c_zero_int 1392, 1402, 1419, 1752, 1762, 1774, 1775,
 1790, 1792, 2944, 2954, 3114, 3479

\item 27, 37, 38, 56, 64, 77, 78, 80, 83, 90

\item 64–66, 85, 86, 92, 94, 214, 1562, 1568, 1593, 1601, 1688,
 1922, 1925, 2091, 2125, 2853, 2855, 3259, 3261, 3371

\item* 5, 11, 2123

item-pos* 1999

item-sym* 1999

\itemindent 22, 69

\itemindent 68

itemindent 602

\itemsep 79, 80

\itemsep 2688, 2694

\itemwidth 2742, 2786, 2790, 3150, 3194, 3198

K

keyans 11, 2496

keyans* 11, 3248

keyanspic 12, 2649

Keys for environments provide by **enumext**:

 above* 23, 48, 49

 above 23, 48, 49, 72, 76, 84, 91

 after 37, 38, 74, 77, 84, 91

 align 23, 30, 67, 87

 before* 37, 38, 72, 84, 91

 before 37, 38, 76

 below* 23, 48, 49

 below 23, 48, 49, 74, 77, 84, 91

 check-ans 23, 24, 26, 50, 51, 57, 62, 63, 65, 66, 72, 74, 88,
 99

 columns-sep* 24, 54, 71, 83

 columns-sep 39, 55, 71, 73, 76, 83

 columns* 24, 54, 71, 83

 columns 22, 39, 42, 48, 55, 71, 73, 76, 83

 first 37, 38, 87

 font 30, 67, 87

 item-pos* 57, 58, 64

 item-sym* 22, 57, 58, 64, 65

 item*-sep 65

 itemindent 23, 35, 36, 67, 87

 itemsep 34, 70

 labelsep 30, 65, 69, 87

 labelwidth 29, 30, 32–34, 69

 label 22, 29, 33, 34, 80

 lisparindent 70

 list-indent 22, 35, 79

 list-offset 35

 listparindent 35, 87

 mark-ans 24, 53, 60

 mark-pos 53, 54

 mark-ref 24, 53, 59

 mini-env .. 23, 39, 41, 47, 48, 64, 72, 76, 82, 84, 90, 91

 mini-sep 23, 39, 72, 76

 miniright* 23, 39

 miniright 23, 39, 46, 82

 minirigth* 26

 minirigth 26

 no-store 24, 51, 53

 noitemsep 34, 43

 nosep 34, 43

 parindent 70

 parsep 34, 70, 87

 partopsep 34

 ref 25, 31

 resume 22, 50, 51, 69, 74, 84

 rightmargin 35

 save-ans 23, 50, 51, 55, 57, 61, 62, 66, 74, 75, 78, 84, 92,
 93, 95, 96

 save-key 24

 show-ans 24, 53, 54, 56, 57, 60, 66, 93

 show-length 26, 36, 69, 99

 show-pos 24, 53, 54, 56, 57, 60, 66, 93

 start 23, 26, 33, 34, 69

 store-brk 57

 store-ref 24, 28, 53, 57–59, 61, 62, 66, 93

 topsep 34

 widest 22, 26, 34

 wrap-ans 53, 56, 60

 wrap-label* 30, 65, 67, 86, 87, 92

 wrap-label 30, 67, 86, 87, 92

keys commands:

<code>\keys_define:nn</code>	325, 347, 376, 457, 477, 493, 540, 560, 604, 623, 680, 689, 768, 785, 1204, 1313, 1322, 1370, 1469, 1498, 1516, 1634, 2001, 3512, 3575
<code>\l_keys_key_str</code>	3666
<code>\keys_set:nn</code>	339, 792, 1209, 1214, 1680, 2325, 2535, 2877, 3288, 3577, 3578, 3579, 3580, 3581, 3582, 3583, 3584, 3585, 3586, 3587, 3588, 3626

L

label	455, 475, 493
Labels provide by <code>enumext</code> :	
<code>\Alph*</code>	29
<code>\Roman*</code>	29
<code>\alph*</code>	29
<code>\arabic*</code>	29, 31
<code>\roman*</code>	29
<code>\labelsep</code>	80
<code>\labelsep</code>	2689, 2692
labelsep	323
<code>\labelwidth</code>	29, 80
<code>\labelwidth</code>	2689, 2690
labelwidth	323
<code>\leftmargin</code>	22, 69
<code>\leftmargin</code>	68, 2689
legacy commands:	
<code>\legacy_if:nTF</code>	3030, 3033, 3408, 3411
<code>\legacy_if_gset_false:n</code>	882
<code>\legacy_if_set_false:n</code>	3032, 3410
<code>\legacy_if_set_true:n</code>	2992, 3017, 3024, 3037, 3335, 3359, 3415
<code>\linewidth</code>	72, 76
<code>\linewidth</code>	2396, 2545, 2711, 2738, 2799, 3146, 3207
<code>\list</code>	27
<code>\list</code>	212
list-indent	602
list-offset	602
<code>\listparindent</code>	2691
listparindent	602
<code>\lrbox</code>	3047, 3421

M

<code>\makebox</code>	80
<code>\makebox</code>	1624, 1626, 2145, 3061, 3069, 3073, 3434, 3438
<code>\makelabel</code>	64, 67, 68, 80
<code>\makelabel</code>	67, 68, 2151, 2167
<code>\makesavenoteenv</code>	245
mark-ans	1467
mark-pos	1467, 1496
mark-ref	1467
mini-env	766
mini-sep	766
<code>\minipage</code>	27
<code>\minipage</code>	218
<code>\miniright</code>	9, 46, 1150, 2465, 2598
<code>\miniright*</code>	9
mode commands:	
<code>\mode_if_vertical:TF</code>	837, 865, 988, 1067
<code>\mode_leave_vertical:</code>	635, 649, 661, 673, 1593, 1601, 1622, 2143, 3059
msg commands:	
<code>\msg_error:nn</code>	2526, 2530, 2617, 2676, 2869, 3275, 3281, 3589
<code>\msg_error:nnn</code>	1154, 1158, 1183, 1200, 3502, 3507, 3572, 3642

<code>\msg_error:nnnn</code>	1648, 1652, 1656, 2518, 2613, 2621
<code>\msg_fatal:nn</code>	2320
<code>\msg_fatal:nnn</code>	277
<code>\msg_info:nnn</code>	13, 16, 227, 241
<code>\msg_line_context:</code>	3670, 3675, 3680, 3695, 3718, 3722, 3726, 3731, 3736, 3741, 3746, 3750, 3755, 3760, 3764, 3769, 3773, 3778, 3783, 3788, 3792, 3796
<code>\msg_new:nnn</code>	3643, 3647, 3651, 3655, 3660, 3664, 3668, 3673, 3678, 3693, 3708, 3715, 3720, 3724, 3729, 3734, 3739, 3744, 3748, 3753, 3758, 3762, 3767, 3771, 3776, 3781, 3786, 3790, 3794
<code>\msg_term:nnn</code>	1459
<code>\msg_term:nnnn</code>	2241, 2251, 2286, 2291
<code>\msg_warning:nn</code>	2464, 2597
<code>\msg_warning:nnn</code>	1462
<code>\msg_warning:nnnn</code>	1959, 2183, 2188, 2749, 2762, 3157, 3170
<code>\multicolsep</code>	73, 76
<code>\multicolsep</code>	2426, 2570

N

<code>\NeedsTeXFormat</code>	3
<code>\newcounter</code>	280
<code>\NewDocumentCommand</code>	1150, 1644, 2609, 3486, 3540, 3596
<code>\NewDocumentEnvironment</code>	2296, 2496, 2649, 2840, 3248
<code>\newlabel</code>	28
<code>\newlabel</code>	263
no-store	1368
<code>\noindent</code>	83, 90
<code>\noindent</code>	2403, 2550, 2808, 2854, 3102, 3216, 3260, 3467
<code>\nointerlineskip</code>	2403, 2550, 2808, 3216
noitemsep	558
<code>\nopagebreak</code>	848, 876, 999, 1078, 1141, 1147
<code>\normalfont</code>	1837, 1981, 3388
nosep	558

P

Packages:	
enumext	21, 50, 68, 78, 98
enumitem	28, 29
expl3	80
footnotehyper	27
hyperref	24, 26–28, 31, 58, 62, 86, 87, 98
lua-visual-debug	41
multicol	21, 98
shortlst	80
<code>\par</code>	848, 876, 999, 1078, 1141, 1147, 1176, 1193, 1816, 2447, 2469, 2587, 2602, 2723, 2826, 2833, 3102, 3116, 3234, 3241, 3467, 3481
<code>\parindent</code>	3079, 3444
<code>\parsep</code>	40, 43, 79, 80
<code>\parsep</code>	1594, 1602, 2271, 2688, 2695, 2700
parsep	558
<code>\parskip</code>	3080, 3445
<code>\partopsep</code>	80
<code>\partopsep</code>	2272, 2693
partopsep	558
peek commands:	
<code>\peek_meaning:NTF</code>	2969, 2983, 3000, 3011, 3312, 3326, 3343
<code>\peek_meaning_remove:NTF</code>	2976, 3319
<code>\peek_remove_spaces:n</code>	2129
<code>\phantomsection</code>	28
<code>\phantomsection</code>	252
prg commands:	
<code>\prg_do_nothing:</code>	256

\prg_new_protected_conditional:Npnn ... 190

\prg_replicate:nn 199, 3713

\prg_return_false: 194

\prg_return_true: 193

\printkeyans 13, 96, 3540

prop commands:

\prop_count:N .. 1544, 1804, 1840, 1903, 1984, 3391

\prop_gput_if_not_in:Nnn 1539, 1542

\prop_if_exist:NTF 1332, 3506

\prop_item:Nn 3509

\prop_new:N 1334

\ProvidesExplPackage 4

R

\raggedcolumns 2435, 2576

\ref 59, 61

ref 455, 475

\refstepcounter 3039, 3417

regex commands:

\regex_match:nnTF 192, 515, 517, 529, 531, 2336, 2349, 2888, 2901

\regex_replace_once:nnN 391

\renewcommand 403, 424, 434

\RenewDocumentCommand ... 2023, 2091, 2125, 2151, 2167

\RequirePackage 17

resume 1313

resume* 1313

rightmargin 602

\Roman 29, 33, 34

\Roman 299

\roman 29, 33, 34

\roman 300, 473, 3528

S

save-ans 1313

scan commands:

\scan_stop: 80, 2702, 2853, 3259, 3497, 3500

seq commands:

\seq_clear:N 3603

\seq_const_from_clist:Nn 3591

\seq_count:N 2662, 3607

\seq_gclear:N 2021, 2022

\seq_gput_right:Nn 1551, 2034, 2035

\seq_if_empty:NTF 2040, 3555, 3621

\seq_if_exist:NTF 1336, 3553

\seq_item:Nn 2720

\seq_map_function:NN 3612

\seq_map_inline:Nn .. 3561, 3566, 3600, 3622, 3623

\seq_map_pairwise_function:NNN 2042

\seq_new:N 94, 95, 112, 140, 141, 1338

\seq_pop_left:NN 3611

\seq_put_right:Nn 2623, 3619, 3636

\seq_set_from_clist:Nn 3604

\seq_set_map_e:NNn 3613

\seq_show:N 3557

\setcounter .. 526, 530, 532, 2229, 2231, 2276, 2278, 2667

\setenumext .. 5-8, 97, 3516, 3521, 3526, 3531, 3536, 3596

\setlength 1595, 1603

show-ans 1467, 1496

show-length 678

skip commands:

\skip_add:Nn . 817, 823, 829, 839, 843, 867, 871, 968, 974, 980, 990, 994, 1016, 1069, 1073, 2688

\skip_eval:n 1594, 1602

\skip_gset:Nn 1089, 1093, 1097

\skip_gzero_new:N 1084, 1085

\skip_horizontal:N 650, 662, 674, 3062, 3076, 3441

\skip_horizontal:n 636, 1623, 1631, 2144, 2146, 3060

\skip_if_eq:nnTF . 815, 821, 827, 891, 925, 966, 972, 978, 1009, 1014, 1035, 1086, 1108, 1221, 1235, 1249, 1260, 1271, 1282, 1293, 1304

\skip_new:N 54, 55, 59, 60, 61, 62, 63, 116, 170

\skip_set:Nn . 800, 804, 853, 857, 894, 898, 902, 909, 913, 917, 928, 933, 937, 943, 948, 953, 1011, 1012, 1013, 1020, 1024, 1028, 1037, 1042, 1046, 1049, 1053, 1057, 1088, 1092, 1110, 1114, 1118, 1124, 1128, 1132, 2682, 2696

\skip_set_eq:NN 2224, 2270, 2271, 3079, 3080, 3444, 3445

\skip_use:N 802, 806, 841, 845, 849, 869, 873, 892, 911, 920, 926, 931, 935, 946, 950, 951, 956, 992, 996, 1022, 1222, 1226, 1229, 1236, 1240, 1243, 2447

\skip_zero:N 2272, 2426, 2570, 2693, 2694

\skip_zero_new:N 1004, 1005, 1006, 1083, 1105, 1106, 1107

\c_zero_skip . 815, 821, 827, 892, 926, 966, 972, 978, 1009, 1014, 1035, 1086, 1108, 1222, 1236, 1249, 1260, 1271, 1282, 1293, 1304

\small 3518, 3523, 3528, 3533, 3538

\star 2005

start 538

\stepcounter 2027, 2630

store-ref 1467

str commands:

\c_backslash_str 3722, 3731, 3732, 3736, 3737, 3741, 3742, 3773, 3774, 3778, 3783, 3784

\c_colon_str 1803, 1902, 3497

\str_case:nn 1388

\str_count:n 199, 3713

\str_if_eq:nnTF 2234, 2282

\str_if_eq_p:nn 2227, 2275

\str_if_in:nnTF 3493

\str_new:N 111, 165

\str_set:Nn ... 379, 380, 381, 1478, 1479, 1501, 1502

\string 245

\strutbox 896, 900, 904, 915, 919, 930, 939, 945, 955, 968, 974, 980, 1011, 1012, 1013, 1016, 1026, 1030, 1039, 1046, 1051, 1059, 1088, 1089, 1092, 1099, 1112, 1120, 1126, 1134, 2698

T

TeX and LaTeX commands:

\@auxout 261

\@currenvir 1388

\protected@write 261

text commands:

\text_expand:n 3489

\textasteriskcentered 1475, 1489

\thepage 267

tl commands:

\c_space_tl 1860, 1929, 1974, 1996, 3352, 3353, 3680, 3695

\tl_clear:N 352, 358, 1677, 1850, 1919, 3349

\tl_clear_new:N 309

\tl_const:Nn 142, 293

\tl_gclear:N 1961, 2162, 2494, 2837, 3063, 3131, 3245

\tl_gput_right:Nn 294

\tl_greplace_all:Nnn 315

\tl_gset:Nn 1949, 2455, 2935, 3006

\tl_gset_eq:NN 311, 2072, 3056

<code>\tl_if_blank:nTF</code>	3054, 3365, 3375, 3396
<code>\tl_if_empty:NTF</code>	409, 443, 449, 1558, 1589, 1703, 1957, 2141, 3634
<code>\tl_if_novalue:nTF</code>	1678, 1689, 1858, 1927, 1973, 1995, 2025, 2050, 2068, 2073, 2102, 2660, 2875, 3286, 3350, 3598
<code>\tl_map_inline:Nn</code>	312, 389
<code>\tl_new:N</code> 32, 39, 41, 42, 75, 76, 77, 83, 84, 85, 87, 88, 89, 91, 92, 98, 99, 109, 110, 121, 131, 132, 133, 136, 144, 145, 148, 149, 164, 167	
<code>\tl_put_left:Nn</code> 1566, 1599, 1686, 1967, 1989, 3364, 3371	
<code>\tl_put_right:Nn</code> 310, 401, 422, 432, 1520, 1527, 1570, 1605, 1688, 1694, 1702, 1705, 1715, 1720, 1723, 1729, 1755, 1765, 1779, 1795, 1801, 1806, 1853, 1856, 1860, 1887, 1892, 1897, 1900, 1909, 1922, 1925, 1929, 1939, 1974, 1996, 2341, 2354, 2893, 2906, 3367, 3377, 3398, 3514, 3519, 3524, 3529, 3534	
<code>\tl_remove_all:Nn</code>	3633
<code>\tl_remove_once:Nn</code>	1743, 1872
<code>\tl_replace_all:Nnn</code>	314
<code>\tl_reverse:N</code>	1742, 1744, 1871, 1873
<code>\tl_set:Nn</code> 150, 279, 353, 357, 362, 363, 397, 416, 633, 647, 659, 671, 1331, 1474, 1488, 1834, 1978, 2070, 3352, 3353, 3385, 3631	
<code>\tl_set_eq:NN</code> 320, 398, 400, 419, 421, 429, 431, 1741, 1870, 1883, 2114, 2118, 2641, 2643	
<code>\tl_to_str:n</code>	3489
<code>\tl_trim_spaces:n</code>	310, 3619, 3631, 3637
<code>\tl_use:N</code>	316, 319, 411, 445, 451, 704, 708, 712, 716, 720, 724, 728, 732, 736, 740, 744, 748, 752, 756, 760, 764, 1628, 1748, 1756, 1767, 1781, 1786, 1798, 2057, 2063, 2087, 2105, 2109, 2117, 2153, 2154, 2161, 2169, 2170, 2176, 2304, 2502, 2646, 2831, 3066, 3077, 3081, 3239, 3431, 3442, 3446, 3543, 3544, 3545, 3546, 3547, 3615
token commands:	
<code>\token_to_str:N</code>	263
<code>\topsep</code>	1595, 1603
<code>topsep</code>	<u>558</u>
<code>\typeout</code>	231, 234, 244, 245, 1396, 1406, 1423, 1442
U	
<code>\u</code>	392
use commands:	
<code>\use:N</code>	200, 2158, 2306
<code>\use:n</code>	3495
<code>\use_none:nn</code>	255
<code>\usecounter</code>	2225, 2273
V	
<code>\value</code>	2476, 2481, 2925, 2930
<code>\vspace</code> 883, 1226, 1229, 1240, 1243, 1253, 1255, 1264, 1266, 1275, 1277, 1286, 1288, 1297, 1299, 1308, 1310, 1594, 1602, 2657, 2668, 3117, 3482	
W	
<code>widest</code>	<u>538</u>
<code>wrap-ans</code>	<u>1467</u>
<code>wrap-label</code>	<u>323</u>
<code>wrap-label*</code>	<u>323</u>