

enumext

ENUMERATE EXERCISE SHEETS

V1.0 2024-05-06^{*}

©2024 by Pablo González[†]

CTAN: <https://www.ctan.org/pkg/enumext>

 <https://github.com/pablgonz/enumext>

Abstract

This package provides “*enumerated list*” environments for creating “*simple exercise sheets*” along with “*multiple choice questions*”, storing the *(answers)* to these in memory using the **multicol** package and the **l3seq** and **l3prop** modules.

Contents

1 Introduction	2	4 The storage system	9
1.1 Description and usage	3	4.1 Keys for storage	10
1.2 The concept of left margin	3	4.2 Keys for internal label and ref	10
1.3 User interface	3	4.3 Keys for check answers	10
1.3.1 Internal counters	3	4.4 The command <code>\anskey</code>	10
1.3.2 Support for multicol	4	4.5 The environment keyans	11
1.3.3 Support for minipage	4	4.5.1 The <code>\item*</code> in keyans	11
1.3.4 The <code>\label</code> and <code>\ref</code> system	4	4.6 The environment keyanspic	12
1.3.5 Support for <code>\footnote</code>	4	4.6.1 The command <code>\anspic</code>	12
2 The environment <code>enumext</code>	4	4.7 Printing stored content	13
2.1 The <code>\item*</code> in <code>enumext</code>	5	4.7.1 The command <code>\getkeyans</code>	13
2.1.1 Keys for <code>\item*</code> in <code>enumext</code>	5	4.7.2 The command <code>\printkeyans</code>	13
3 The command <code>\setenumext</code>	5	5 Full examples	14
3.1 Keys for label and ref	6	6 The way of non-enumerated lists	16
3.2 Keys for spaces	6	7 References	18
3.2.1 Vertical spaces	7	8 Change history	18
3.2.2 Horizontal spaces	8	9 Index of Documentation	19
3.3 Keys for add code	8	10 Implementation	21
3.4 Keys for start and resume	9	11 Index of Implementation	102
3.5 Keys for multicol	9		
3.6 Keys for minipage	9		
3.6.1 The command <code>\miniright</code>	9		

Motivation and acknowledgments

Usually it is enough to use the classic **enumerate** environment to generate “*simple exercise sheets*” or “*multiple choice questions*”, the basic idea behind **enumext** is to cover three points:

1. To have a simple interface to be able to write “*lists of exercises*” with “*answers*”.
2. To have a simple interface for writing “*multiple choice questions*”.
3. To have a simple interface for placing “*columns*” and “*drawings*” or “*tables*”.

This package would not be possible without Phelype Oleinik who has collaborated and adapted a large part of the code and all \TeX team for their great work and to the different members of the **TeX-SX** community who have provided great answers and ideas. Here a note of the main ones:

1. Answer given by Alan Munn in `\topsep`, `\itemsep`, `\partopsep`, `\parsep` - what do they each mean (and what about the bottom)?
2. Answer given by Enrico Gregorio in Understanding minipages - aligning at top
3. Answer given by Ulrich Diez in Different mechanics of hyperlink vs. hyperref
4. Answer given by Enrico Gregorio in Minipage and multicol, vertical alignment

License and Requirements

Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License (lpl), version 1.3 or later (<https://www.latex-project.org/lpl.txt>). The software has the status “maintained”.

The **enumext** package loads and requires **multicol**[3] package, need to have a modern \TeX distribution such as \TeX Live or Mi \TeX . It has been tested with the standard classes provided by \TeX : **book**, **report**, **article** and **letter** on 10pt, 11pt and 12pt.

^{*}This file describes a documentation for v1.0, last revised 2024-05-06.

[†]E-mail: pablgonz@educarchile.cl.

1 Introduction

In the \LaTeX world there are many useful packages and classes for creating “lists of exercises”, “worksheets” or “multiple choice questions”, classes like `exam`[1] and packages like `xsim`[2] do the job perfectly, but they don’t always fit the basic day to day needs.

In my work (and in the work of many teachers) it is common to use “simple exercise sheets” also known as “informal lists of exercises”, as an example:

1. Factor $x^2 - 2x + 1$

2. Factor $3x + 3y + 3z$

3. True False

(a) $\alpha > \delta$

(b) \LaTeX 2e is cool?

4. Related to Linux
- (a) You use linux?

(b) Usually uses the package manager?

(c) Rate the following package and class

i. `xsim-exam`

ii. `xsim`

iii. `exsheets`

Sometimes we are also interested in showing the “answers” along with the questions:

1. Factor $x^2 - 2x + 1$

* `(x - 1)^2`

2. Factor $3x + 3y + 3z$

* `3(x + y + z)`

3. True False

(a) $\alpha > \delta$

* `False`

(b) \LaTeX 2e is cool?

* `Very True!`

4. Related to Linux
- (a) You use linux?

* `Yes`

(b) Usually uses the package manager?

* `Yes, dnf`

(c) Rate the following package and class

i. `xsim-exam`

* `doesn't exist for now :(`

ii. `xsim`

* `very good`

iii. `exsheets`

* `obsolete`

Or we are interested in referring to a specific question and its “answer”, for example:

The answer to 3.(b) is “Very True!” and the answer to 4.(c).ii is “very good”.

Or we are interested in printing all the “answers”:

1. $(x - 1)^2$

2. $3(x + y + z)$

3. (a) False

(b) Very True!

4. (a) Yes
- (b) Yes, dnf

(c) i. doesn't exist for now :(

ii. very good

iii. obsolete

Another very common thing to use in my work is “multiple choice questions”, for example:

1. First type of questions

(A) value

(B) correct

2. Second type of questions

I. $2\alpha + 2\delta = 90^\circ$

II. $\alpha = \delta$

III. $\angle EDF = 45^\circ$

(A) I only

(B) II only

(C) I and II only

(D) I and III only

(E) I, II, and III

★ 3. Third type of questions

(1) $2\alpha + 2\delta = 90^\circ$

(2) $\angle EDF = 45^\circ$

(A) value


(B) value

(C) value

(D) value

(E) value

4. Question with image and label below:



5. Question with image on left side:

- (A) value

(B) value

(C) value

(D) correct

(E) value
-

Where what we are interested in the `<label>` and a “short note” that we leave as an explanation, and then print them:

1. (B) $x = 5$

2. (D)

3. (C) some note
4. (B)

5. (D) “other note”

These “simple worksheets” or “multiple choice questions” appear to be easy to obtain using a combination of the `enumerate`, `minipage` and `multicols` environments, but like many things, what “looks simple” is not so simple.

The `enumext` package was created and designed to meet these small requirements in the creation of “simple worksheets” and “multiple choice questions”.

1.1 Description and usage

The `enumext` package defines enumerated environments using the `list` environment provided by \LaTeX , but “does not redefine” any internal commands associated with it such as `\list`, `\endlist` or `\item` outside of the “scope” in which they are defined.

- This package is NOT intend to replace the `enumerate` environment nor replace the powerful `enumitem`[5], the approach is intended to work without hindering either of them.
This package can be used with `xelatex`, `lualatex`, `pdflatex` and the classical `latex>dvips>ps2pdf` and is present in \TeX Live and \MiKTeX , use the package manager to install. For manual installation, download `enumext.zip` and unzip it, run `lualatex enumext.dtx` and move all files to appropriate locations, then run `mktxlsr`. To produce the documentation run `lualatex enumext.dtx` two times.

```
enumext.sty  » TDS:tex/latex/enumext/
enumext.pdf  » TDS:doc/latex/enumext/
README.md   » TDS:doc/latex/enumext/
enumext.dtx  » TDS:source/latex/enumext/
```

The package is loaded in the usual way:

```
\usepackage{enumext}
```

1.2 The concept of left margin

There is a direct relationship between the parameters `\leftmargin`, `\itemindent`, `\labelwidth` and `\labelsep` plus an “extra space” that makes it difficult to obtain the desired *horizontal spaces* in a `list` environment.

Usually we don’t want the `list` to go beyond the left margin of the page, but since these four values are related, that causes a problem. The `enumitem`[5] package adds the `\labelindent` parameter to solve some of these problems. A simplified representation of this in the figure 1.




Figure 1: Representation of horizontal lengths in `enumitem`.

The `enumext` package does NOT provide a user interface to set the values for `\leftmargin` and `\itemindent`, instead it provides the keys `list-offset` and `list-indent` which internally set the values for `\leftmargin` and `\itemindent`. The concepts of `\leftmargin` and `\itemindent` are different in `enumext`. The figure 2 shows the visual representation of idea.




Figure 2: Representation of horizontal lengths concept in `enumext`.

In this way we reduce a *little* the amount of parameters we have to pass. With the default values of keys `list-offset`, `list-indent`, `labelwidth` and `labelsep` the lists will have the (usually) expected output for “*simple worksheets*”. The figure 3 shows the visual representation.



Figure 3: Default horizontal lengths `list-offset=0pt`, `list-indent=\labelwidth+\labelsep` in `enumext`.

1.3 User interface

The user interface consists in `enumext`, `enumext*`, `keyans`, `keyans*` and `keyanspic` environments, `\anskey`, `\item*` and `\anspic*` commands to \langle stored content \rangle , `\getkeyans` command to get the individual \langle stored content \rangle , `\printkeyans` to print all \langle stored content \rangle , `\miniright` for `minipage` and `\setenumext` to config all [`key = val`] options.

1.3.1 Internal counters

The package `enumext` uses internally the `enumXi`, `enumXii`, `enumXiii`, `enumXiv` counters for the four nesting levels of the `enumext` environment, the `enumXv` counter for the `keyans` environment, the `enumXvi` counter for the `keyanspic` environment, the counter `enumXvii` for `enumext*` environment and the counter `enumXviii` for `keyans*` environment.

- If any package defines these counters or they are user-defined in the document, the package will return a missing error and abort the load.

1.3.2 Support for multicol

The package provides direct support for using the `multicol`[3] package. This allows to obtain directly a two-column output as shown in the figure 4.




Figure 4: Representation of the two column output for a nested level in `enumext` environment.

The “non starred” version of the `multicols` environment is always used together with the `\raggedcolumns` command and is controlled by `columns` and `columns-sep` keys. The environment is available for all nesting levels, and can can together with the `mini-env` key. If you need to force a start a new column `\columnbreak` must be used (see §3.5).

- The `\columnseprule` command is not available as a key and is set to “zero” for the inner levels and the `keyans` environment. If the value of this is set inside the document, it will affect “all environments” that use the `columns` key.

1.3.3 Support for minipage

The package provides direct support for `minipage` environment, this allows you to obtain an output like the one shown in figure 5.



Figure 5: Representation of the `mini-env` output for a nested level `enumext` environment.

The `minipage` environments (left and right) is always used with “aligned on top” [`t`], the `minipage` environment on the “right side” always starts with `\centering`. It can be used at all nesting levels and is controlled by `mini-env` and `mini-sep` keys. In order to switch from the “left” side `minipage` environment to the “right” side one must use the command `\mini-right` (see §3.6).

1.3.4 The \label and \ref system

This package provides a user interface like the `enumitem`[5] package to customize the references which is activated by the `ref` key (§3.1), the standard \TeX `\label` and `\ref` commands work as usual. It also provides an “internal reference” system for the “stored content” by means of the key `store-ref` (§4.2) when the key `save-ans`(§4.1) is active.

- The implementation of `\label` and `\ref` together with the `store-ref` key are compatible with the `hyperref`[7] package.

1.3.5 Support for \footnote

This package provides an internal implementation for the `\footnote` command which is compatible with the `hyperref` package, but, it will not produce the expected links, and when using the `mini-env` key or the starred environments `enumext*` and `keyans*` the output will look like the classic way they are displayed in the `minipage` environment.

The best way to solve this is to use Jean-François Burnol `footnotehyper`[8] package, it will support keeping the links if `hyperref` is loaded with the `hyperfootnotes=true` option (default) and will show the output numbered at the bottom of the page (as opposed to how it is displayed in the `minipage` environment). The way to load it is as follows:

```
\usepackage{footnotehyper}
\makesavenoteenv{enumext}
\makesavenoteenv{enumext*}
```

2 The environment enumext

<code>enumext</code>	<code>\begin{enumext} [⟨keyval list⟩]</code>	<code>\begin{enumext*} [⟨keyval list⟩]</code>
<code>enumext*</code>	<code>\item ⟨item content⟩</code>	<code>\item ⟨item content⟩</code>
	<code>\item [⟨custom⟩] ⟨item content⟩</code>	<code>\item [⟨custom⟩] ⟨item content⟩</code>
	<code>\item* [⟨symbol⟩] [⟨offset⟩] ⟨item content⟩</code>	<code>\item* [⟨symbol⟩] [⟨offset⟩] ⟨item content⟩</code>
	<code>\end{enumext}</code>	<code>\end{enumext*}</code>

The `enumext` is an “*enumerated list*” environment that works in the same way as the standard `enumerate` environment provided by L^AT_EX, `\item` and `\item[⟨custom⟩]` commands work in the usual way. The environment can be nested with at most “*four levels*” and the options can be configured globally using `\setenumext` command and locally using `[⟨key = val⟩]` in the environment.

Example

1. This text is in the first level.

(a) This text is in the second level.

i. This text is in the third level.

A. This text is in the fourth level.

X This text is in the first level.
- ★ 2. This text is in the first level.

```
\begin{enumext}
  \item This text is in the first level.
  \begin{enumext}
    \item This text is in the second level.
    \begin{enumext}
      \item This text is in the third level.
      \begin{enumext}
        \item This text is in the fourth level.
      \end{enumext}
    \end{enumext}
  \end{enumext}
  \item[X] This text is in the first level.
  \item* This text is in the first level.
\end{enumext}
```

2.1 The \item* in enumext

```
\item* \item*
\item*[⟨symbol⟩]
\item*[⟨symbol⟩][⟨offset⟩]
```

The `\item*`, `\item*[⟨symbol⟩]` and `\item*[⟨symbol⟩][⟨offset⟩]` works like the numbered `\item`, but placing a `⟨symbol⟩` to the “*left*” of the `⟨label⟩` separated from it by the value set by the `labelsep` key and can be `⟨offset⟩` using the second optional argument. The default values for `⟨symbol⟩` and `⟨offset⟩` are `\star ‘★’` and the value set by `labelsep` key.

The *starred version* ‘★’ cannot be separated by spaces ‘’ from the command, i.e. `\item*` and the first optional argument does “*not support*” verbatim content. Can be configure with the keys `item-sym*` and `item-pos*` locally in the environment or globally using `\setenumext` command (§3).

🔗 The behavior of `\item*` in the `enumext` environment is NOT the same as in the `keyans` environment.

2.1.1 Keys for \item* in enumext

- item-sym* = {⟨symbol⟩}

default: `\star`

Sets the *symbol* to be displayed in the “*left*” of the box containing the current `⟨label⟩` set by `labelwidth` key for `\item*` in `enumext`. The *symbol* can be in text or math mode, for example `item-sym*={\ast}`.
- item-pos* = {⟨rigid length | dim expression⟩}

default: *by levels*

Sets the *offset* between the box containing the current `⟨label⟩` defined by `labelwidth` key and the `⟨symbol⟩` set by `item-sym*` key. The default values are set by `labelsep` key at each level. If positive values are passed it will *offset to the left* and if negative values are passed it will *offset to the right*.

3 The command \setenumext

```
\setenumext \setenumext[⟨enumext, level⟩]{⟨key = val⟩} \setenumext[⟨enumext*⟩]{⟨key = val⟩}
\setenumext[⟨print, level⟩]{⟨key = val⟩} \setenumext[⟨keyans*⟩]{⟨key = val⟩}
\setenumext[⟨keyans⟩]{⟨key = val⟩} \setenumext[⟨print*⟩]{⟨key = val⟩}
```

The command `\setenumext` sets the `⟨keys⟩` on a global basis for environment `enumext`, the `\printkeyans` command and the `keyans` environment. It can be used both in the preamble and in the body of the document as many times as desired.

The `⟨keys⟩` set in the optional arguments of environments and commands have the highest precedence, overriding both options passed by `\setenumext`. If the optional argument is not passed, the first level of the environment `enumext` will be taken by default.

- It should be kept in mind that using any *key* that sets a *rubber or rigid lengths* for vertical or horizontal space on a level will influence the vertical and horizontal space for *inners levels* and *keyans* and *keyanspic* environments. All *keys* related to vertical or horizontal spacing accept a “*skip*” or “*dim*” expression if passed between braces, i.e. you do not need to use `\dimexpr` or `\dimeval` to perform calculations.

3.1 Keys for label and ref

`label = {⟨\alph* | \Alph* | \arabic* | \roman* | \Roman*⟩}` default: *by levels*

Sets the *label* that will be printed at the *current level*. The default value for first level are `\arabic*`, for second level are `(\alph*)`, for third level are `\roman*`, and for fourth level are `\Alph*`.

- This key is intended to give the basic structure with which the *label* will be displayed, and the and the form in which it is used by standard “*label and ref*” and the “*internal reference*” system with the `store-ref` key. You cannot use commands with *label* as an argument, for example `\emph{⟨\alph*⟩}` will return an error. For full customization of how *label* is displayed use the `font` or `wrap-label` keys.

`ref = {⟨code {⟨\alph* | \Alph* | \arabic* | \roman* | \Roman*⟩ more code⟩}` default: *empty*

Modifies the way *cross references* are displayed. The `label` key sets the default form of the *cross references*, by using this key you can define a different format, for example: `ref=\emph{⟨\alph*⟩}` is valid.

- Internally, it renews the command associated with each counter when it is executed, i.e., `\theenumxi` is modified when the key is executed at the first level, `\theenumxii` when it is executed at the second level and `\theenumxiii` together with `\theenumxiv` when it is executed at the third and fourth levels.

This must be kept in mind, since the values set by the `label` and `ref` keys are not cumulative by levels, so if you have used the `ref` key in the first level and then want to associate the counter with `label` or `ref` in the second level you must use the direct commands, i.e. `\arabic{enumxi}` to indicate the count of the first level instead of using `\theenumxi`.

`labelsep = {⟨rigid length⟩}` default: `0.3333em`

Sets the *horizontal space* between the box containing the current *label* defined by `label` key and the text of an item on the first line. Internally sets the value of `\labelsep` for the current level.

`labelwidth = {⟨rigid length⟩}` default: *by label*

Sets the *width* of the box containing the current *label* set by `label` key. Internally sets the value of `\labelwidth` for the current level. The default values are calculated by means of the *width* of a box by setting a *value* to the current counter using ‘0’ for `\arabic*`, ‘M’ for `\Alph*`, ‘m’ for `\alph*`, ‘VIII’ for `\Roman*` and ‘viii’ for `\roman*`.

`widest = {⟨integer | string⟩}` default: *empty*

Sets the `labelwidth` key pass the *integer* or converting the *string* of the form `\Alph`, `\alph`, `\Roman` or `\roman` to a *value* for the current counter defined by `label` key, then calculating the *width* by means of a box. For example `widest={XXIII}` or `widest={23}` are equivalent. This key is useful when the default values of the `labelwidth` key are smaller than those actually used.

`font = {⟨font commands⟩}` default: *empty*

Sets the *font style* for the current *label* defined by `label` key. For example `font={\bfseries\small}`.

`align = {⟨left | right | center⟩}` default: *left*

Sets the *aligned* of *label* defined by `label` key on the current level in the label box.

`wrap-label = {⟨code {#1} more code⟩}` default: *empty*

Wraps the current *label* defined by `label` key referenced by `{#1}`. The `{⟨code⟩}` must be passed between braces. This key does not modify the value set by the `labelwidth` key and is applied only on `\item` and `\item*`. When using it in the `\setenumext` command it is necessary to use the *double hash* ‘`{#1}`’. For example `wrap-label={\fbox{#1}}` or you can create a command:

```
\NewDocumentCommand \itembx { s +m }
{
  %
  \IfBooleanTF{#1}
  {
    {\strut\smash{\parbox[t]{\labelwidth}{\raggedright{#2}}}}%
    {\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{#2}}}}%
  }
}
```

and then pass it through the key `wrap-label={\itembx{#1}}` or `wrap-label={\itembx*{#1}}`.

`wrap-label* = {⟨code {#1} more code⟩}` default: *empty*

The same as the `wrap-label` key but also applies on `\item[⟨custom⟩]`.

3.2 Keys for spaces

`show-length = {⟨true | false⟩}` default: *false*

Displays on the terminal the values for *all list parameters* at the current level. For *vertical spaces* show the values of `\topsep`, `\itemsep`, `\parsep` and `\partopsep`. For *horizontal spaces* show the values of `\labelwidth`, `\labelsep`, `\itemindent`, `\listparindent` and `\leftmargin`.

3.2.1 Vertical spaces

`topsep = {⟨rubber length | rigid length⟩}`

default: *by levels*

Set the *vertical space* added to both the top and bottom of the list. Internally sets the value of `\topsep` for the current level. The default values for first level are 8.0pt plus 2.0pt minus 4.0pt, for second level are 4.0pt plus 2.0pt minus 1.0pt, for third and fourth level are 2.0pt plus 1.0pt minus 1.0pt.

`parsep = {⟨rubber length | rigid length⟩}`

default: *by levels*

Set the *vertical space* between paragraphs within an item. Internally sets the value of `\parsep` for the current level. The default values for first level are 4.0pt plus 2.0pt minus 1.0pt, for second level are 2.0pt plus 1.0pt minus 1.0pt, for third and fourth level are 0pt.

`partopsep = {⟨rubber length | rigid length⟩}`

default: *by levels*

Set the *vertical space* added, beyond `topsep`, to the “top” and “bottom” of the entire environment if the environment instance is preceded by a “blank line” or `\par` command. Internally sets the value of `\partopsep` for the current level. The default values for first and second level are 2.0pt plus 1.0pt minus 1.0pt, for third and fourth level are 1.0pt minus 1.0pt.

- The value of this parameter also affects the *inner levels* and the *keyans* environment. Caution should be taken with “blank lines” or `\par` command “before” each environment or nested level when formatting the source code of document. T_EX will enter *vertical mode* and apply this value to the “top” and “bottom” the environment or nested level.

`itemsep` = {*<rubber length>* | *<rigid length>*} default: *by levels*

Set the *vertical space* between items, beyond the `parsep`. Internally sets the value of `\itemsep` for the current level. The default values for first level are `4.0pt` plus `2.0pt` minus `1.0pt`, for the rest of the levels are `2.0pt` plus `1.0pt` minus `1.0pt`.

`noitemsep` *<value forbidden>* default: *not used*

This is a “*meta-key*” that does not receive an argument. Set `itemsep` and `parsep` equal to `0pt` the entire level of environment.

`nosep` *<value forbidden>* default: *not used*

This is a “*meta-key*” that does not receive an argument. Sets all keys for vertical spacing equal to `0pt` the entire level of environment.

- The following *<keys>* should be used with “*caution*”, they are intended to be used at the “top” and “bottom” of the environment when the `columns` or `mini-env` keys do not provide adequate *vertical spaces*. The values passed can be *rubber* or *rigid* lengths, the way they are applied is the way you differ, using the star ‘*’ *<keys>* applies `\vspace*` so that L^AT_EX does *not discard* this space at page break.

`above` = {*<rubber length>* | *<rigid length>*} default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the top of the entire level of environment. This key is intended to give a “*fine adjustment*” of the vertical space on the “*above*” the environment without hindering the value of the `topsep` key. The space is added with `\vspace` so is “*discardable*”.

`above*` = {*<rubber length>* | *<rigid length>*} default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the top of the entire level of environment. This key is intended to give a “*fine adjustment*” of the vertical space on the “*above*” the environment without hindering the value of the `topsep` key. The space is added with `\vspace*` so is “*not discardable*”.

`below` = {*<rubber length>* | *<rigid length>*} default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the bottom of the entire level of environment. This key is intended to give a “*fine adjustment*” of the vertical space on the “*below*” the environment without hindering the value of the `topsep` key. The space is added with `\vspace` so is “*discardable*”.

`below*` = {*<rubber length>* | *<rigid length>*} default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the bottom of the entire level of environment. This key is intended to give a “*fine adjustment*” of the vertical space on the “*below*” the environment without hindering the value of the `topsep` key. The space is added with `\vspace*` so is “*not discardable*”.

3.2.2 Horizontal spaces

`itemindent` = {*<rigid length>*} default: `0pt`

Extra *horizontal indentation*, beyond `labelsep`, of the “*first line*” off each item. This value is applied internally using `\hspace` and does not modify the value of `\itemindent`.

`rightmargin` = {*<rigid length>*} default: `0pt`

Set the *horizontal space* between the right margin of the environment and the right margin of the enclosing environment, the value it takes must be greater than or equal to `0pt`. Internally sets the value of `\rightmargin` for the current level.

`listparindent` = {*<rigid length>*} default: `0pt`

Sets the *horizontal space* indentation, beyond `list-indent`, for second and subsequent paragraphs within a list item. Internally sets the value of `\listparindent` for the current level.

`list-offset` = {*<rigid length>*} default: `0pt`

Sets the *horizontal translation* of the entire environment level from the left edge of the box defined by the `labelwidth` key. Internally sets the values of `\leftmargin` and `\itemindent` for the current level.

`list-indent` = {*<rigid length>*} default: `labelwidth + labelsep`

Sets the *indentation* of the whole environment under the box defined by `labelwidth` and `labelsep` keys. Internally sets the value of `\leftmargin` and `\itemindent` for the current level.

- If `list-indent=0pt` the *<label>* will be part of the text, separated by the value of the `labelsep` key and the *first word*, in simple terms it will look like a “*common paragraph*”. This setting is equivalent (more or less) to the `wide` key provided by the `enumitem` package.

3.3 Keys for add code

- The following *<keys>* should be used with “*caution*”, they are intended to inject *{<code>}* into different parts of the defined environments. We must keep in mind that the defined environments are based on the `list` base environment provided by L^AT_EX which is defined (simplified) as plain form `\list{<arg one>}{<arg two>}`. Using the `before*` key does not allow access to the `list` parameters defined by `[<key = val>]`.

`before` = {*<code>*} default: *not used*

Execute *{<code>}* “*before*” the environment starts. The *{<code>}* is executed “*after*” performing all calculations related to the *list parameters* in the environment and the parameters sets by `[<key = val>]` that is, in the second argument of the list after setting all the parameters `\list{<arg one>}{<arg two>}{<code>}`. The *{<code>}* must be passed between braces.

`before*` = {*<code>*} default: *not used*

Execute `{\code}` “before” the environment starts. The `{\code}` is executed “before” performing all calculations related to the *list parameters* and `[\key = val]` sets in the environment that is, before the arguments defining the environment are executed: `{\code}\list{\arg one}{\arg two}`. The `{\code}` must be passed between braces.

`first = {\code}` default: *not used*
 Executes `{\code}` when “starting” the environment. The `{\code}` must be passed between braces, is executed right “after” all *list parameters* are done, after the second argument of `list`, just before the first occurrence of `\item`: `\list{\arg one}{\arg two}{\code}\item`.

- Keep in mind that the code set in this key will affect the entire “body” of the environment and therefore the inner levels of the `list` and the `keyans` environment. It is recommended to set this key per level.

`after = {\code}` default: *not used*
 Execute `{\code}` “after” finishing the environment. The `{\code}` must be passed between braces.

3.4 Keys for start and resume

`start = {\integer | string}` default: `1`
 Sets the *start value* of the numbering on the current level. Internally `\string` is passed as value to the counter defined by `label` key on the current level, i.e. it is equivalent to enter `start=5`, `start=E` or `start=v`.

`resume \value forbidden` default: *not used*
 Sets the *start* to value from the previous of the counter defined by `label` key for the “first level”. This `\key` does not receive an argument. The `\key` can be overwritten using the `start` key. If the `save-ans` key is present and `{\store name}` exist, the numbering will continue according to this key. This key is “only” available for the “first level” of `enumext`.

3.5 Keys for multicol

`columns = {\integer}` default: `1`
 Set the *number of columns* to be used by the `multicol` environment within the environment. The value must be a positive integer less than or equal to `10`.

`columns-sep = {\rigid length}` default: *by level*
 Set the *space between columns* used by the `multicol` environment within the environment. Internally sets the value of `\columnsep`, by default its value is equal to the sum of the values set in the keys `labelwidth` and `labelsep` of the current level.

- The `\footnote{\text}` command in the nested levels of `multicol` will not work as expected, prefer the use of `\footnotemark[\number]` inside the environment and `\footnotetext[\number]{\text}` outside the environment or via the `after` key.

3.6 Keys for minipage

`mini-env = {\rigid length}` default: *not used*
 Sets the *width* of the `minipage` environment on the “right side”. This value added to the value set by the `mini-sep` key to determines the *width* of the `minipage` environment on the “left side”, taking `\linewidth` as the maximum reference value.

`mini-sep = {\rigid length}` default: `0.3333em`
 Sets the *space between* the `minipage` environment on the “left side” and the `minipage` environment on the “right side”. This separation is applied together with `\hfill`.

3.6.1 The command `\miniright`

`\miniright` The `\miniright` command close the `minipage` environment on the “left side” and opens the `minipage`
`\miniright*` environment on the “right side” by starting it with the `\centering` command. It must be placed “after” the last `\item` of the current environment and “before” starting the material to be placed on the “right side”. The *starred version* ‘`*`’ inhibits the use of `\centering` command i.e. the usual \LaTeX justification is maintained in the `minipage` on the “right side”.

- The `\footnote{\text}` command in `minipage` environment will work as usual. If you prefer the footnotes to be numbered (not lowercase) and outside the environment, use `\footnotemark[\number]` inside the environment and `\footnotetext[\number]{\text}` outside the environment or via the `after` key.

4 The storage system

The entire mechanism for “storing content” it is activated according to `save-ans` key on the “first level” of `enumext` environment. Only when this `\key` is “active” the `\anskey` command and the environments `keyans` and `keyanspic` are available.

<pre>\begin{enumext}[save-ans={\store name}] \item Text \begin{keyans} ... \end{keyans} \end{enumext}</pre>	<pre>\begin{enumext}[save-ans={\store name}] \item Text \begin{keyanspic} ... \end{keyanspic} \end{enumext}</pre>
---	---

4.1 Keys for storage

- save-ans = { <store name> }

default: not set

Sets the “name” of the <sequence> and <prop list> in which the contents will be “stored” by \anskey in enumext environment, \item* in keyans environment and \anspic* in keyanspic environment. If the <sequence> or <prop list> does not exist, it will be created globally.
- wrap-ans = { <code {#1} more code> }

default: \fbox

Wraps the current <argument> passed \anskey command to referenced by {#1}. The {<code>} must be passed between braces. This <key> only affects the current <argument> passed to \anskey and NOT the “stored content” in the <store name> set by save-ans key. If this key is passed using the \setenumext command it is necessary to use double ‘{##1}’.
- mark-ans = { <symbol> }

default: \textasteriskcentered

Sets the symbol to be displayed in the left margin of the “stored content” in <store name> set by save-ans key when using show-ans key.
- mark-pos = { <left | right> }

default: left

Sets the aligned of the symbol defined by mark-ans key. The “symbol” is aligned in a box with the same dimensions of the label box defined by labelwidth key on the current level and separated by the value of the labelsep key.
- show-ans = { <true | false> }

default: false

Displays the current <argument> passed to \anskey in enumext environment, the current <label> for \item* in keyans environment and the current <label> for \anspic* in keyanspic environment at the place where it is executed. If the optional argument is present in \item* or \anspic* it will be shown in square brackets.
- show-pos = { <true | false> }

default: false

Displays the position occupied by the “stored content” by \anskey in enumext environment, \item* in keyans environment and \anspic* in keyanspic environment in <store name> set by save-ans key. This position is used by the \getkeyans command and by the \ref command if the store-ref key is active.

4.2 Keys for internal label and ref

- store-ref = { <true | false> }

default: false

Activates the internal “label and ref” mechanism for referencing “stored content” in <store name> set by save-ans key. To reference the location of the “stored content” within the environment you must use \ref{<store name: position>}, where <position> corresponds to the position occupied by the “stored content” in the <store name> returned by the show-pos key. For example \ref{test:4} will return 3. (b) which corresponds to the location of the “stored content” at position 4 within the environment in which the key save-ans=test was set.
- mark-ref = { <symbol> }

default: \textasteriskcentered

Sets the symbol that will be displayed by the \printkeyans command only if the hyperref package is detected and the store-ref key are active. This “symbol” is used as a “link” between the environment in which the save-ans key was used and the place where the command is executed.

4.3 Keys for check answers

- check-ans = { <true | false> }

default: false

Enables the “checking answer” mechanism. This key works under the logic that each question will contain “only one answer”, it is intended to be used in conjunction with no-store key.
- no-store <value forbidden>

default: not used

This is a “meta-key” that does not receive an argument. This key is used in conjunction with check-ans and is designed to be used with nested levels of enumext in which the \anskey command will not be used.

4.4 The command \anskey

\anskey \anskey{<content>}

The \anskey command takes a mandatory argument and is triggered by save-ans key. The “content” are “stored” in <store name> set by save-ans key. The command does “not support” verbatim content and must NOT be nested. By design it is assumed that each \item or \item* will have a “single” occurrence of the command unless a nested level is opened or the no-store key is used. If store-ref key are active and the hyperref[7] package is detected, \hyperLink and \hypertarget will be used, otherwise the usual “label and ref” system provided by L^AT_EX will be used.

Example

- ★ 1. Text containing our instructions or questions.

*

first answer

2. Text containing our instructions or questions.

(a) Question.

*

second answer
3. Text containing our instructions or questions.

*

third answer

4. Text containing our instructions or questions.

*

fourth answer

```
\begin{enumext}[save-ans=test,show-ans]
  \item* Text containing our instructions or questions. \anskey{\first answer}
  \item Text containing our instructions or questions.
    \begin{enumext}
      \item Question.\anskey{\second answer}
    \end{enumext}
  \item Text containing our instructions or questions. \anskey{\third answer}
  \item Text containing our instructions or questions. \anskey{\fourth answer}
\end{enumext}
```

4.5 The environment keyans

```
keyans \begin{keyans}[\key = val] \item \item[\langle custom \rangle] \item* \item*[\langle content \rangle] \end{keyans}
keyans* \begin{keyans*}[\key = val] \item \item[\langle custom \rangle] \item* \item*[\langle content \rangle] \end{keyans*}
```

The `keyans` is an “*enumerated list*” environment designed for “*multiple choice*” questions activated by the `save-ans` key. This environment can NOT be nested and must always be at the “*first level*” of the `enumext` environment, the commands `\item` and `\item[\langle custom \rangle]` work in the usual.

```
\begin{enumext}[save-ans=test]
  \item \langle item content \rangle
    \begin{keyans}[\key = val]
      \item \langle item content \rangle
      \item [\langle custom \rangle] \langle item content \rangle
      \item* \langle item content \rangle
      \item* [\langle content \rangle] \langle item content \rangle
    \end{keyans}
\end{enumext}
```

The `\keys` set in the optional argument of the environment are the same (almost) as those of the `enumext` environment and have higher precedence than those set by `\setenumext[\keys]{\key = val}`. If the optional argument is not passed or the `\keys` are not set by `\setenumext`, the default values will be the same as the second level of the `enumext` environment with the difference in the `\label` which will be set to `label=(\Alph*)`.

4.5.1 The `\item*` in `keyans`

```
\item* \item*
\item* [\langle content \rangle]
```

The `\item*` and `\item*[\langle content \rangle]` command store the current `\label` set by `label` key next to the `\content` (if it is present) in `\store name` set by `save-ans` key in the “*first level*” of the `enumext` environment.

The *starred version* ‘`*`’ cannot be separated by spaces ‘`␣`’ from the command, i.e. `\item*` and the optional argument does “*not support*” verbatim content. By design it is assumed that the *starred version* ‘`*`’ will only appear “*once*” within the environment.

🔗 The behavior of `\item*` in `keyans` environment is NOT the same as in the `enumext` environment.

Example

```
\begin{enumext}[save-ans=test,columns=2,show-ans]
  \item Text containing a question.
    \begin{keyans}[nosep]
      \item Choice
      \item* Correct choice
      \item Choice
      \item Choice
    \end{keyans}

  \item Text containing a question and image.
    \begin{keyans}[nosep,mini-env={0.4\linewidth}]
      \item Choice
      \item Choice
      \item Choice
      \item Choice
      \item*[\note] Correct choice
      \miniright
      \includegraphics[scale=0.25]{example-image-a}

      Some text
    \end{keyans}
\end{enumext}
```

1. Text containing a question.

(A) Choice

* (B) Correct choice

(C) Choice

(D) Choice
2. Text containing a question and image.

(A) Choice

(B) Choice

(C) Choice

(D) Choice

* (E) [note] Correct choice



4.6 The environment keyanspic

keyanspic

`\begin{keyanspic}[\langle number above, number below \rangle]\anspic{\langle drawing \rangle}\anspic*[\langle content \rangle]{\langle drawing \rangle}`

The `keyanspic` is a “fake enumerated list” environment that which uses the `\anspic` command instead of `\item`. It is activated by the `save-ans` key and has the same settings as the `keyans` environment. It is intended for placing “drawings” or “tabular” with an in-line or *above* and *below* layout. A representation of the output can be seen in the figure 6.




Figure 6: Representation of the `keyanspic` environment with optional argument `[3,2]` in `enumext`.

The optional argument determines the number drawings or tabular “above” and “below” within the environment. The vertical separation between “above” and “below” is controlled by the values set by `parsep` and `itemsep` keys passed to `keyans` environment. If the optional argument or the second part of it is omitted the drawings or tabular will be put on a single line.

4.6.1 The command \anspic

\anspic

`\anspic{\langle drawing or tabular \rangle}`
`\anspic*[\langle content \rangle]{\langle drawing or tabular \rangle}`


The `\anspic` command take three arguments, the *starred version* “*” store the current `\label` next to the `\content` (if it is present) in `\store name` set by `save-ans` key.

The *starred version* “*” cannot be separated by spaces “ ” from the command, i.e. `\anspic*` and the optional argument does “not support” verbatim content. By design it is assumed that the *starred version* “*” will only appear “once” within the environment.

Example

```
\begin{enumext}[save-ans=test,show-ans,nosep]
  \item Question with images.
  \begin{keyanspic}[3,2]
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-b}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic*[note]{\includegraphics[scale=0.15]{example-image-a}}
  \end{keyanspic}
\end{enumext}
```

1. Question with images.



4.7 Printing stored content

4.7.1 The command \getkeyans

`\getkeyans` `\getkeyans{<store name> : <position>}`

The command `\getkeyans` prints the “only stored content” in `<store name>` defined by `save-ans` key in the `<position>` returned by the `show-pos` key.

The “content” can only be accessed “after” it is stored, if the `<store name>` does not exist the command will return an error. The form taken by the argument `<store name> : <position>` is the same as that used to generate the internal “label and ref” system when `store-ref` key are active, so to refer to a stored “content”. For example `\getkeyans{test:4}` will return the “stored content” at position 4 of the environment in which the key `save-ans=test` was set.

4.7.2 The command \printkeyans

`\printkeyans` `\printkeyans[<keys>]{<store name>}`

The command `\printkeyans` prints “all stored content” in `{<store name>}` defined by `save-ans` key. The “content” can only be accessed “after” it is stored, if `<store name>` does not exist the command will return an error.

Internally it places the “stored content” inside the `enumext` environment with default values for `label` key are the same as those of the `enumext` environment along with the keys: `nosep`, `first=\small`, `font=\small` for all levels, except for the first one that adds the `columns=2` key.

The optional argument allows to handle the `<keys>` “on the first level” of the `enumext` environment encapsulated by the command. If need to pass options for nested levels use `\setenumext[<print> , <level>]{<store name>}`.

Example

```
\begin{enumext}[save-ans=sample,columns=2,show-pos,nosep,store-ref]
  \item Factor  $3x+3y+3z$ . \anskey{$3(x+y+z)}
  \item True False

  \begin{enumext}[nosep]
    \item \LaTeX2e\ is cool? \anskey{Very True!}
  \end{enumext}

  \item Related to Linux

  \begin{enumext}[nosep]
    \item You use linux? \anskey{Yes}
    \item Rate the following package and class
      \begin{enumext}[nosep]
        \item \texttt{xsim} \anskey{very good}
        \item \texttt{exsheets} \anskey{obsolete}
      \end{enumext}
    \end{enumext}
  \end{enumext}
```

The answer to `\ref{sample:4}` is `\getkeyans{sample:4}` and the answers to all the worksheets are as follows:

```
\printkeyans{sample}
```

1. Factor $3x + 3y + 3z$.

[1] $3(x + y + z)$
2. True False

(a) ~~LaTeX2e~~ is cool?

[2] Very True!
3. Related to Linux

(a) You use linux?
- [3] Yes

(b) Rate the following package and class

i. `xsim`

[4] very good

ii. `exsheets`

[5] obsolete

The answer to 3.(b).i is very good and the answers to all the worksheets are as follows:

1. $3(x + y + z)$

2. (a) Very True!

3. (a) Yes

(b) i. very good

ii. obsolete
- *

*

*

*

*

5 Full examples

Here I will leave as an example some adaptations questions taken from [TeX-SX](#). The examples are attached to this documentation and can be extracted from your PDF viewer or from the command line by running:

```
$ pdfdetach -saveall enumext.pdf
```

and then you can use the excellent [arara](#)¹ tool to compile them.

Example 1

Adapted from the response given by Enrico Gregorio in [Squares for answer choice options and perfect alignment to mathematical answers](#) .

1. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

A

 36 km/h.

B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$ km/h.
2. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?

A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.

C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

D

 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$.
3. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

A

 36 km/h.

B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$ km/h.
4. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?

A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.


C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

D

 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$.
1. B
2. A
3. B
4. A

Example 2

Adapted from the response given by Florent Rougon in [Multiple choice questions with proposed answers in random order — addition of automatic correction \(cross mark\)](#) .

1. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

A

 36 km/h.

☒ B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$ km/h.
2. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?

☒ A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.

C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

D

 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$.
3. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

A

 36 km/h.

☒ B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$ km/h.
4. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?

☒ A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.

C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

D

 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$.
1. B
2. A
3. B
4. A
- *
- *
- *
- *

¹The cool \TeX automation tool: <https://www.ctan.org/pkg/arara>

©2024 by Pablo González L

14 / 113

Example 3

A “simple multiple choice” test 📄.

1. First type of questions
- A

 value
- B

 correct
- C

 value
- D

 value
2. Second type of questions
- I. $2\alpha + 2\delta = 90^\circ$
- II. $\alpha = \delta$
- III. $\angle EDF = 45^\circ$
- A

 I only
- B

 II only
- C

 I and II only
3. Third type of questions
- (1) $2\alpha + 2\delta = 90^\circ$
- (2) $\angle EDF = 45^\circ$
- A

 value
- B

 value
- C

 value
4. Question with image and label below:



A




D



B



C



E



5. Question with image on left side:
- A

 value
- B

 value
- C

 value
- D

 correct
- E

 value

Test keys

1. $B \ x = 5$
2. D
3. C some note

- * 4. E A duck
- * 5. D other note
- *

*

*

*

Example 4

A “simple worksheet” using ducks :) 📄.



Factor $x^2 - 2x + 1$



Factor $3x + 3y + 3z$

The following questions need to be cuaqtified :)



True False

- (a) $\alpha > \delta$
- (b) ~~ETX~~ze is cool?



Related to Linux

- (a) You use linux?
- (b) Usually uses the package manager?
- (c) Rate the following package and class
- i. `xsim-exam`
- ii. `xsim`
- iii. `exsheets`

The answer to 1 is $(x - 1)^2$ and the answer to 3.(a) is False.

1. $(x - 1)^2$
2. $3(x + y + z)$
3. (a) False
- (b) Very True!
4. (a) Yes

- * (b) Yes, dnf
- * (c) i. doesn't exist for now :(
- * ii. very good
- * iii. obsolete
- *


*

*

*

*

Example 5

Adapted from the response given by Stephen in SAT like question format .

1	Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action.	3	Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action.
2	Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action.	4	Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action.

1. A) 2. C) 3. B) 4. D)

6 The way of non-enumerated lists

It is possible to use (or abuse) the enumext environment to mimic non-enumerated list environments such as itemize and description, clearly the <keys> to “store answers”, the keyans and keyanspic environments lose their sense and it is not the focus of the main of this package, but, why not to do it?. Here I leave as an example other uses of the enumext environment that can be helpful for specific purposes. The “trick” to generate these fake environments is set label={} or label={<some>} and play with the list-indent, list-offset, font and wrap-label keys.

Fake itemize environment

Here we set the label key using the default settings in L^AT_EX for the four levels \textbullet, \textendash, \textasteriskcentered and \textperiodcentered together with the nosepe key to reduce the vertical spaces in the left side example and set the label key in mathematical mode for the right side as \ast, \diamond, \circ and \star for the four levels together with the nosepe key

- First level item
 - Second level item
 - * Third level item
 - Fourth level item
 - First level item
- * First level item
 - ◇ Second level item
 - Third level item
 - ★ Fourth level item
 - * First level item

Fake description environment

Here we set label={} and list-indent=2.5em, font=\bfseries.

- Something** A short one-line description.
This is an entry without a label.

Something A short one-line description text.

Something long A much longer description text may take more than one line or more than one paragraph.
Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

If we add list-indent=0pt you get widest style:

- Something** A short one-line description.
This is an entry without a label.

Something A short one-line description text.

Something long A much *longer* description text may take more than one line or more than one paragraph. Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

- The small space at the beginning of the “*unlabeled entry*” corresponds to `\labelsep` and can be removed using `\hspace{-\labelsep}` at the beginning of the line.

Description indented by label

Here we set `label={}` and we will give a convenient value to `labelsep` and `labelwidth`, for example we can take as reference our *longest label* and pass it as value using:

```
\newlength{\descitemwd}
\settowidth{\descitemwd}{\textbf{Something long}}
```

and then use `labelsep=4pt, labelwidth=\descitemwd, font=\bfseries`.

SomeThing A short one-line description.
This is an entry *without* a label.

Something A short one-line description.

Something long A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

The environment can be translated so that the *(labels)* are on the left margin calculating the value passed to the `list-offset` key, in this case it will be equal to the sum of the values set by the `labelwidth` and `labelsep` keys finally resulting as `list-offset={-\descitemwd - 4pt}`.

SomeThing A short one-line description.
This is an entry *without* a label.

Something A short one-line description.

Something long A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

If we add `align=right` it will look like this:

SomeThing A short one-line description.
This is an entry *without* a label.

Something A short one-line description.

Something long A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

- At this point we have used `list-offset={-\descitemwd - 4pt}` instead of `list-offset={-\labelwidth - \labelsep}`, this is because the parameters `\labelwidth` and `\labelsep` take the default values, as if we had not set `label`.

Description with multi-line labels

The `label` key does not accept *multiline material*, this is where the `wrap-label*` key comes into play. Unlike the `enumitem` package, the `align` key only supports three options, so what we will do is create a command in the style `\parleft` of `enumitem` that allows us to place *multiline labels* using `\parbox`.

```
\NewDocumentCommand \itembx { s +m }
{%
  \IfBooleanTF{#1}
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedright{#2}}}}%
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{#2}}}}%
}
```

Now we just need to set `wrap-label*={\itembx{#1}}`.

SomeThing A short one-line description.
This is an entry *without* a label.

Something A short one-line description.

Something A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

long vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.
Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

SoMeThInG A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

LoNg vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

Final notes

The original implementation (if you can call it that) of the ideas that led to the creation of `enumext` were some macros using the `enumerate[4]` package for personal use created in early 2003, the code was quite questionable, but functional for these simple requirements.

With the great answers given by Christian Hupfer in [Create a fake label ref using list](#) and the answer given by David Carlisle in [Change the use of label ref by data save in an array \(list\)](#) I managed to create a more solid code than the original version, now using the `l3prop`[10] and `l3seq`[10] modules together with the `hyperref`[7] and `enumitem`[5] packages, which did the job, but with some limitations.

As time went by I took these limitations as a personal challenge which I called “*reinventing the wheel*”, since there were packages and classes that did more or less what I was looking for, but did not fit my simple requirements. This “*reinventing the wheel*” finally ended up becoming `enumext`.

Why list environments?

The answer is simple, first I love the beauty of its syntax and many of what I had already written used the `enumerate` environment or lists created using the `enumitem` package. In my mind I thought: how complicated could it be to write a package that looked like `enumitem`? It seemed simple enough, of course I didn’t have in mind the mess I was getting into working with `list` environments, `minipage` and adding support for the `multicol` and `hyperref` packages.

Of course, seeing the final result of the experiment “*reinventing the wheel*” I am quite satisfied.

Why not random questions and other utilities

The “*random*” type questions I love and hate them at the same time, although they simplify a lot the work when creating a multiple choice test, but you lose the beauty of typesetting a document with \LaTeX , that is to say the output does not always look as nice as it should, even if they are only alternatives these must follow a certain order when presented either numerical or presentation, that said handling that using *nested lists* is quite complicated so I do not classify to be implemented.

7 References

- [1] HIRSCHHORN, PHILIP. “Using the exam document class”. Available from CTAN, <https://www.ctan.org/pkg/exam>, 2023.
- [2] NIEDERBERGER, CLEMENS. “xsim – eXercise Sheets IMproved”. Available from CTAN, <https://www.ctan.org/pkg/xsim>, 2023.
- [3] MITTELBACH, FRANK. “An environment for multicolumn output”. Available from CTAN, <https://www.ctan.org/pkg/multicol>, 2024.
- [4] The \LaTeX Project. “enumerate – Enumerate with redefinable labels”. Available from CTAN, <https://www.ctan.org/pkg/enumerate>, 2024.
- [5] BEZOS, JAVIER. “Customizing lists with the enumitem package”. Available from CTAN, <https://www.ctan.org/pkg/enumitem>, 2019.
- [6] BERRY, KARL. “ \LaTeX 2_ε: An Unofficial Reference Manual”. Available from CTAN, <https://ctan.org/pkg/latex2e-help-texinfo>, 2024.
- [7] The \LaTeX Project. “Extensive support for hypertext in \LaTeX ”. Available from CTAN, <https://www.ctan.org/pkg/hyperref>, 2024.
- [8] BURNOL, JEAN-FRANÇOIS. “The footnotehyper package”. Available from CTAN, <https://www.ctan.org/pkg/footnotehyper>, 2021.
- [9] The \LaTeX Project. “The expl3 package”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2024.
- [10] The \LaTeX Project. “The \LaTeX 3 Interfaces”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2024.
- [11] The \LaTeX Project. “The xparse package”. Available from CTAN, <https://www.ctan.org/pkg/xparse>, 2024.
- [12] GUNDLACH, PATRICK. “The lua-visual-debug package”. Available from CTAN, <https://www.ctan.org/pkg/lua-visual-debug>, 2023.
- [13] LEMVIG, MOGENS. “The shortlst package”. Available from CTAN, <https://www.ctan.org/pkg/shortlst>, 1998.
- [14] NIEDERBERGER, CLEMENS. “tasks – Horizontally columned lists”. Available from CTAN, <https://www.ctan.org/pkg/tasks>, 2022.

8 Change history

v1.0 2024-05-06 – First public release.

9 Index of Documentation

The italic numbers denote the pages where the corresponding entry is described.

C

Document class:

article 1

book 1

exam 2

letter 1

report 1

\columnbreak 4

\columnsep 9

Commands provide by enumext:

\anskey 3, 9–11

\anspic* 3, 10, 12

\anspic 12

\getkeyans 3, 10, 13

\item* 3–6, 10, 11

\item 5, 6, 9–11

\miniright 3, 4, 9

\printkeyans 3, 5, 10, 13

\setenumext 3, 5, 6, 10, 11, 13

Counters defined by enumext:

enumXiii 3

enumXii 3

enumXiv 3

enumXi 3

enumXviii 3

enumXvii 3

enumXvi 3

enumXv 3

E

Environments provide by enumext:

enumext* 3, 4

enumext 3–5, 9–11, 13, 16

keyans* 3, 4

keyanspic 3, 6, 9, 10, 12, 16

keyans 3–7, 9–12, 16

Environments:

enumerate 1–3, 5, 18

list 3, 8, 18

minipage 2–4, 9, 18

multicols 2, 4, 9

I

\item 3, 4

\itemsep 8

K

Keys for environments provide by enumext:

above* 8

above 8

after 9

align 6, 17

before* 8

before 8

below* 8

below 8

check-ans 10

columns-sep 4, 9

columns 4, 8, 9

first 9

font 6

item-pos* 5

item-sym* 5

itemindent 8

itemsep 8, 12

labelsep 3, 5, 6, 8–10, 17

labelwidth 3, 5, 6, 8–10, 17

label 6, 9, 11, 13, 16, 17

list-indent 3, 8

list-offset 3, 8, 17

listparindent 8

mark-ans 10

mark-pos 10

mark-ref 10

mini-env 4, 8, 9

mini-sep 4, 9

no-store 10

noitemsep 8

nosep 8, 16

parsep 7, 8, 12

partopsep 7

ref 4, 6

resume 9

rightmargin 8

save-ans 4, 9–13

show-ans 10

show-length 6

show-pos 10, 13

start 9

store-ref 4, 6, 10, 13

topsep 7, 8

widest 6

wrap-ans 10

wrap-label* 6, 17

wrap-label 6

L

\label 4

Labels provide by enumext:

\Alph* 6, 11

\Roman* 6

\alph* 6

\arabic* 6

\roman* 6

\labelsep 3, 6

\labelwidth 3, 6

\linewidth 9

\listparindent 8

P

Packages:

enumerate 17

enumext 1–3, 12, 17, 18

enumitem 3, 4, 8, 17, 18

footnotehyper 4

hyperref 4, 10, 18

l3prop 1, 18

l3seq 1, 18

multicol 1, 4, 18

xsim 2

\parsep 7

\partopsep 7

©2024 by Pablo González L

19 / 113

R	\rightmargin 8
\raggedcolumns 4	T
\ref 4	\topsep 7

10 Implementation

The most recent publicly released version of `enumext` is available at CTAN: <https://www.ctan.org/pkg/enumext>. While general feedback via email is welcomed, specific bugs or feature requests should be reported through the issue tracker: <https://github.com/pablgonz/enumext/issues>.

- The documentation presented here is far from professional, it contains a lot of obvious information that to the eye of a T_EXpert are superfluous, but, after so many years developing this project is the only way to remember what does what.

10.1 General conventions

Variables containing `i`, `ii`, `iii` and `iv` are associated by level with the `enumext` environment, variables containing `v` are associated with the `keyans` environment, variables containing `vi` are associated with the `keyanspic` environment, variables containing `vii` are associated with the `enumext*` environment and variables containing `viii` are associated with the `keyans*` environment.

To simplify writing and documentation some variables and functions that are common to the different levels of the environments are described using a capital “X”.

The temporary function `__enumext_tmp:n` is used in different parts of the package code for variable creation or execution of other functions that are grouped into this one.

All variables and functions defined in this package are private and are NOT intended to work or be used by another package or module.

10.2 Initial set up

Start the DocStrip guards.

```
1 <*package>
```

Identify the internal prefix (L^AT_EX3 DocStrip convention) for l3doc class.

```
2 <@@=enumext>
```

10.3 Declaration of the package

First we will make sure we have a minimum (super updated) version of L^AT_EX to work correctly.

```
3 \NeedsTeXFormat{LaTeX2e}[2023-11-01]
```

Now declare the `enumext` package.

```
4 \ProvidesExplPackage
5   {enumext}
6   {2024-05-06}
7   {1.0}
8   {Enumerate exercise sheets}
```

Finally check if the `multicol` package is loaded, if not we load it.

```
9 \hook_gput_code:nnn {begindocument} {enumext}
10 {
11   \IfPackageLoadedTF { multicol }
12   {
13     \msg_info:nnn { enumext } { package-load } { multicol }
14   }
15   {
16     \msg_info:nnn { enumext } { package-not-load } { multicol }
17     \RequirePackage{multicol}[2023-03-30]
18   }
19 }
```

10.4 Definition of variables

Variables that do not appear in this section are created by means of `\keys_define:nn` or some function described below.

Integer variables will control the nesting levels of the environments and boolean variables will be used to determine if they are present (nested) in each other. The boolean variables `\g__enumext_starred_bool` and `\g__enumext_standar_bool` will be set to “true” when the `enumext` and `enumext*` environments are not nested with each other.

```
20 \int_new:N \__enumext_level_int
21 \int_new:N \__enumext_level_h_int
22 \int_new:N \__enumext_keyans_level_int
23 \int_new:N \__enumext_keyans_level_h_int
24 \int_new:N \__enumext_keyans_pic_level_int
25 \bool_new:N \__enumext_starred_bool
26 \bool_new:N \g__enumext_starred_bool
```

```

27 \bool_new:N \l__enumext_standar_bool
28 \bool_new:N \g__enumext_standar_bool
29 \bool_new:N \l__enumext_keyans_env_bool

```

(End of definition for `\l__enumext_level_int` and others.)

```

\l__enumext_counter_i_tl
\l__enumext_counter_ii_tl
\l__enumext_counter_iii_tl
\l__enumext_counter_iv_tl
\l__enumext_counter_v_tl
\l__enumext_counter_vi_tl
\l__enumext_counter_vii_tl
\l__enumext_counter_viii_tl

```

Variables to store the “*name of the counters*” `enumXi`, `enumXii`, `enumXiii` and `enumXiv` for `enumext` environment, `enumXv` for `keyans` environment and `enumXvi` for the `keyanspic` environment.

The counters `enumXvii` and `enumXviii` are used by `enumext*` and `keyans*` environments.

The initial values of these variables are set by the function `__enumext_define_counters:Nn` and then modified by the function `__enumext_label_style:Nnn` used by `label` key (§10.8).

```

30 \cs_set_protected:Npn \__enumext_tmp:n #1
31 {
32   \tl_new:c { l__enumext_counter_#1_tl }
33 }
34 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_counter_i_tl` and others.)

```

\l__enumext_resume_bool
\g__enumext_resume_int
\l__enumext_resume_vii_bool
\g__enumext_resume_vii_int
\g__enumext_item_symbol_tl

```

The boolean variable `\l__enumext_resume_bool` is used by `resume` key, the value from which the environment’s will start is stored in the integer variable `\g__enumext_resume_int` (§10.21). The global token list `\g__enumext_item_symbol_tl` is used by `item-sym*` key (§10.26).

```

35 \bool_new:N \l__enumext_resume_bool
36 \int_new:N \g__enumext_resume_int
37 \bool_new:N \l__enumext_resume_vii_bool
38 \int_new:N \g__enumext_resume_vii_int
39 \tl_new:N \g__enumext_item_symbol_tl

```

(End of definition for `\l__enumext_resume_bool` and others.)

```

\l__enumext_current_widest_dim
\g__enumext_counter_styles_tl
\g__enumext_widest_label_tl
\l__enumext_label_width_by_box

```

The variable `\l__enumext_current_widest_dim` stores the current label width, the variable `\g__enumext_counter_styles_tl` stores the default *⟨label style⟩* and the variable `\g__enumext_widest_label_tl` the label width. These variables are used by `widest` (§10.12) and `label` (§10.10) keys.

```

40 \dim_new:N \l__enumext_current_widest_dim
41 \tl_new:N \g__enumext_counter_styles_tl
42 \tl_new:N \g__enumext_widest_label_tl
43 \box_new:N \l__enumext_label_width_by_box

```

(End of definition for `\l__enumext_current_widest_dim` and others.)

```

\l__enumext_leftmargin_tmp_X_bool
\l__enumext_leftmargin_tmp_X_dim
\l__enumext_leftmargin_X_dim
\l__enumext_itemindent_X_dim

```

The boolean variable `\l__enumext_leftmargin_tmp_X_bool` and the dimensional variable `\l__enumext_leftmargin_tmp_X_dim` are used by the `list-indent` key (§10.14).

The variables `\l__enumext_leftmargin_X_dim` and `\l__enumext_itemindent_X_dim` are used (and set) by the function `__enumext_calc_hspace:NNNNNNNNNN` (§10.30) which determines the internal values for `\leftmargin` and `\itemindent`.

```

44 \cs_set_protected:Npn \__enumext_tmp:n #1
45 {
46   \bool_new:c { l__enumext_leftmargin_tmp_#1_bool }
47   \dim_new:c { l__enumext_leftmargin_tmp_#1_dim }
48   \dim_new:c { l__enumext_leftmargin_#1_dim }
49   \dim_new:c { l__enumext_itemindent_#1_dim }
50 }
51 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_leftmargin_tmp_X_bool` and others.)

```

\l__enumext_multicols_above_X_skip
\l__enumext_multicols_below_X_skip

```

Internal variables used by `columns` key §10.18).

```

52 \cs_set_protected:Npn \__enumext_tmp:n #1
53 {
54   \skip_new:c { l__enumext_multicols_above_#1_skip }
55   \skip_new:c { l__enumext_multicols_below_#1_skip }
56 }
57 \clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_multicols_above_X_skip` and `\l__enumext_multicols_below_X_skip`.)

```
\g__enumext_minipage_stat_int
\l__enumext_minipage_left_skip
\l__enumext_minipage_right_skip
\l__enumext_minipage_after_skip
\g__enumext_minipage_right_skip
\g__enumext_minipage_after_skip
\l__enumext_minipage_left_X_dim
\l__enumext_minipage_active_X_bool
```

Internal variables used by `\miniright` command (§10.19.4) and the keys `miniright`, `miniright*`, `mini-env` and `mini-sep` (§10.17, §10.19).

```
58 \int_new:N \g__enumext_minipage_stat_int
59 \skip_new:N \l__enumext_minipage_left_skip
60 \skip_new:N \l__enumext_minipage_right_skip
61 \skip_new:N \l__enumext_minipage_after_skip
62 \skip_new:N \g__enumext_minipage_right_skip
63 \skip_new:N \g__enumext_minipage_after_skip
64 \cs_set_protected:Npn \__enumext_tmp:n #1
65 {
66   \dim_new:c { \l__enumext_minipage_left_#1_dim }
67   \bool_new:c { \l__enumext_minipage_active_#1_bool }
68 }
69 \clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\g__enumext_minipage_stat_int` and others.)

```
\l__enumext_wrap_label_X_bool
\l__enumext_wrap_label_opt_X_bool
\l__enumext_start_X_int
\l__enumext_fake_item_indent_X_tl
\l__enumext_label_fill_left_X_tl
\l__enumext_label_fill_right_X_tl
\l__enumext_vspace_a_star_X_bool
\l__enumext_vspace_b_star_X_bool
```

The integer variable `\l__enumext_start_X_int` are used by the `start` key (§10.12), the token list `\l__enumext_fake_item_indent_X_tl` is used by `itemindent` key, the variables `\l__enumext_label_fill_left_X_tl` and `\l__enumext_label_fill_right_X_tl` are used by the `align` key (§10.10). The boolean vars `\l__enumext_vspace_a_star_X_bool`, `\l__enumext_vspace_b_star_X_bool` are used by `above`, `above*`, `below` and `below*` keys

```
70 \cs_set_protected:Npn \__enumext_tmp:n #1
71 {
72   \bool_new:c { \l__enumext_wrap_label_#1_bool }
73   \bool_new:c { \l__enumext_wrap_label_opt_#1_bool }
74   \int_new:c { \l__enumext_start_#1_int }
75   \tl_new:c { \l__enumext_fake_item_indent_#1_tl }
76   \tl_new:c { \l__enumext_label_fill_left_#1_tl }
77   \tl_new:c { \l__enumext_label_fill_right_#1_tl }
78   \bool_new:c { \l__enumext_vspace_a_star_#1_bool }
79   \bool_new:c { \l__enumext_vspace_b_star_#1_bool }
80 }
81 \clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\l__enumext_wrap_label_X_bool` and others.)

```
\l__enumext_store_active_bool
\l__enumext_store_name_tl
\g__enumext_store_name_tl
\l__enumext_store_anskey_arg_tl
\l__enumext_store_columns_join_int
\l__enumext_store_keyans_label_tl
\l__enumext_keyans_tmpa_tl
\l__enumext_keyans_tmppb_tl
\l__enumext_keyans_tmpa_dim
```

The boolean variable `\l__enumext_store_active_bool` setting by `save-ans` key (§10.21) activates all the mechanism related to `\anskey`, `keyans`, `keyans*` and `keyanspic`.

The variable `\l__enumext_store_name_tl` sets the name for the storage in *sequence* and *prop list*, the variable `\g__enumext_store_name_tl` is just a copy of the storage name used by the `check-ans` key (§10.21).

The variable `\l__enumext_store_anskey_arg_tl` stores the contents of `\anskey` (§10.24) and the variable `\l__enumext_store_keyans_label_tl` stores the contents of `\item*` (§10.28.2) for the `keyans` and `keyans*` environments and the contents of `\anspic*` (§10.34.1) for the `keyanspic` environment.

The variable `\l__enumext_keyans_tmpa_tl` is a temporary variable used by `keyans` and `keyanspic` at various points.

```
82 \bool_new:N \l__enumext_store_active_bool
83 \tl_new:N \l__enumext_store_name_tl
84 \tl_new:N \g__enumext_store_name_tl
85 \tl_new:N \l__enumext_store_anskey_arg_tl
86 \int_new:N \l__enumext_store_columns_join_int
87 \tl_new:N \l__enumext_store_keyans_label_tl
88 \tl_new:N \l__enumext_keyans_tmpa_tl
89 \tl_new:N \l__enumext_keyans_tmppb_tl
90 \dim_new:N \l__enumext_keyans_tmpa_dim
```

(End of definition for `\l__enumext_store_active_bool` and others.)

```
\l__enumext_setkey_tmpa_tl
\l__enumext_setkey_tmppb_tl
\l__enumext_setkey_tmpa_int
\l__enumext_setkey_tmpa_seq
\l__enumext_setkey_tmppb_seq
```

Internal variables used by the command `\setenumext` (§10.39).

```
91 \tl_new:N \l__enumext_setkey_tmpa_tl
92 \tl_new:N \l__enumext_setkey_tmppb_tl
93 \int_new:N \l__enumext_setkey_tmpa_int
94 \seq_new:N \l__enumext_setkey_tmpa_seq
95 \seq_new:N \l__enumext_setkey_tmppb_seq
```

(End of definition for `\l__enumext_setkey_tmpa_tl` and others.)

```
\l__enumext_store_opt_X_tl
\l__enumext_print_keyans_X_tl
\l__enumext_store_columns_X_bool
\l__enumext_store_columns_X_int
\l__enumext_store_columns_sep_X_bool
\l__enumext_store_columns_sep_X_dim
\l__enumext_store_upper_level_X_bool
```

Internal variables used by [$\langle key = val \rangle$] in `enumext` and `enumext*` environment, the command `\printkeyans` (§10.38) and the keys `columns*` and `columns-sep*`.

```
96 \cs_set_protected:Npn \l__enumext_tmp:n #1
97 {
98   \tl_new:c { \l__enumext_store_opt_#1_tl }
99   \tl_new:c { \l__enumext_print_keyans_#1_tl }
100  \bool_new:c { \l__enumext_store_columns_#1_bool }
101  \int_new:c { \l__enumext_store_columns_#1_int }
102  \bool_new:c { \l__enumext_store_columns_sep_#1_bool }
103  \dim_new:c { \l__enumext_store_columns_sep_#1_dim }
104  \bool_new:c { \l__enumext_store_upper_level_#1_bool }
105 }
106 \clist_map_inline:nn { i, ii, iii, iv, vii } { \l__enumext_tmp:n {#1} }
```

(End of definition for `\l__enumext_store_opt_X_tl` and others.)

```
\l__enumext_show_answer_bool
\l__enumext_show_position_bool
\l__enumext_mark_ref_sym_tl
\l__enumext_mark_answer_sym_tl
\l__enumext_mark_position_str
```

Internal variables for “storage system” mechanism used by `\anskey` (§10.24), `keyans` and `keyanspic` environments. These variables are used by `show-ans`, `show-pos`, `mark-ans`, `save-key` and `mark-ref` keys (§10.23).

```
107 \bool_new:N \l__enumext_show_answer_bool
108 \bool_new:N \l__enumext_show_position_bool
109 \tl_new:N \l__enumext_mark_ref_sym_tl
110 \tl_new:N \l__enumext_mark_answer_sym_tl
111 \str_new:N \l__enumext_mark_position_str
```

(End of definition for `\l__enumext_show_answer_bool` and others.)

```
\l__enumext_keyans_pic_body_seq
\l__enumext_keyans_pic_width_dim
\l__enumext_keyans_pic_above_int
\l__enumext_keyans_pic_below_int
\l__enumext_keyans_pic_above_skip
```

Internal variables used by `keyanspic` environment (§10.34.2).

```
112 \seq_new:N \l__enumext_keyans_pic_body_seq
113 \dim_new:N \l__enumext_keyans_pic_width_dim
114 \int_new:N \l__enumext_keyans_pic_above_int
115 \int_new:N \l__enumext_keyans_pic_below_int
116 \skip_new:N \l__enumext_keyans_pic_above_skip
```

(End of definition for `\l__enumext_keyans_pic_body_seq` and others.)

```
\l__enumext_store_ans_bool
\l__enumext_check_ans_bool
\g__enumext_check_ans_show_bool
\g__enumext_check_ans_show_h_bool
\g__enumext_check_ans_item_tl
\g__enumext_count_item_anskey_int
\g__enumext_count_item_number_int
```

Internal variables used by “check answer” mechanism (§10.22) controlled by the `check-ans` and `no-store` keys.

```
117 \bool_new:N \l__enumext_store_ans_bool
118 \bool_new:N \l__enumext_check_ans_bool
119 \bool_new:N \g__enumext_check_ans_show_bool
120 \bool_new:N \g__enumext_check_ans_show_h_bool
121 \tl_new:N \g__enumext_check_ans_item_tl
122 \int_new:N \g__enumext_count_item_anskey_int
123 \int_new:N \g__enumext_count_item_number_int
124 \int_new:N \g__enumext_standar_star_env_int
125 \int_new:N \g__enumext_starred_star_env_int
126 \int_new:N \g__enumext_starred_keyans_star_env_int
127 \int_new:N \g__enumext_standar_keyans_star_env_int
128 \int_new:N \g__enumext_standar_keyans_pic_star_env_int
```

(End of definition for `\l__enumext_store_ans_bool` and others.)

```
\l__enumext_hyperref_bool
\l__enumext_footnotes_key_bool
```

The boolean variable `\l__enumext_hyperref_bool` will determine if the `hyperref` package is present or load in memory (§10.7). The boolean variable `\l__enumext_footnotes_key_bool` determine if `hyperref` is load with `key hyperfootnotes=true`.

```
129 \bool_new:N \l__enumext_hyperref_bool
130 \bool_new:N \l__enumext_footnotes_key_bool
```

(End of definition for `\l__enumext_hyperref_bool` and `\l__enumext_footnotes_key_bool`.)

```
\l__enumext_newlabel_arg_one_tl
\l__enumext_newlabel_arg_two_tl
\l__enumext_store_write_aux_file_tl
\l__enumext_label_copy_X_tl
```

Internal variables are used when executing the `store-ref` key. The variables `\l__enumext_label_copy_X_tl` correspond to temporary copies of the labels defined by level on which operations will be performed.

The variables `\l__enumext_newlabel_arg_one_tl` and `\l__enumext_newlabel_arg_two_tl` will be used to form the arguments passed to the function `__enumext_newlabel:nn` and the variable `\l__enumext_store_write_aux_file_tl` will be in charge of executing the writing code in the `.aux` file.

```
131 \tl_new:N \l__enumext_newlabel_arg_one_tl
132 \tl_new:N \l__enumext_newlabel_arg_two_tl
```

```

133 \tl_new:N \l__enumext_store_write_aux_file_tl
134 \cs_set_protected:Npn \__enumext_tmp:n #1
135 {
136   \tl_new:c { l__enumext_label_copy_#1_tl }
137 }
138 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_newlabel_arg_one_tl` and others.)

`\g__enumext_footnote_int`

Internal variables used for redefinition of `\footnote`.

`\g__enumext_footnote_arg_seq`
`\g__enumext_footnote_int_seq`

```

139 \int_new:N \g__enumext_footnote_int
140 \seq_new:N \g__enumext_footnote_arg_seq
141 \seq_new:N \g__enumext_footnote_int_seq

```

(End of definition for `\g__enumext_footnote_int`, `\g__enumext_footnote_arg_seq`, and `\g__enumext_footnote_int_seq`.)

`\c__enumext_counter_style_tl`
`\l__enumext_ref_key_arg_tl`
`\l__enumext_ref_aux_tl`
`\l__enumext_the_counter_X_tl`
`\l__enumext_counter_style_for_ref_X_tl`

Internal variables used by `ref` key (§10.17, §10.18).

```

142 \tl_const:Nn \c__enumext_counter_style_tl
143 { { arabic } { roman } { Roman } { alph } { Alph } }
144 \tl_new:N \l__enumext_ref_key_arg_tl
145 \tl_new:N \l__enumext_ref_aux_tl
146 \cs_set_protected:Npn \__enumext_tmp:n #1
147 {
148   \tl_new:c { l__enumext_counter_style_for_ref_#1_tl }
149   \tl_new:c { l__enumext_the_counter_#1_tl }
150   \tl_set:ce { l__enumext_the_counter_#1_tl } { \exp_not:c { theenumX#1 } }
151 }
152 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\c__enumext_counter_style_tl` and others.)

`\l__enumext_item_starred_X_bool`
`\l__enumext_item_column_pos_X_int`
`\g__enumext_item_count_all_X_int`
`\l__enumext_joined_item_X_int`
`\l__enumext_joined_item_aux_X_int`
`\l__enumext_tmpa_X_int`
`\l__enumext_item_text_X_box`
`\l__enumext_joined_width_X_dim`
`\l__enumext_item_width_X_dim`
`\g__enumext_item_symbol_aux_X_tl`
`\l__enumext_align_label_X_str`
`\g__enumext_minipage_active_X_bool`
`\g__enumext_miniright_code_X_tl`
`\g__enumext_minipage_center_X_bool`
`\g__enumext_minipage_right_X_dim`
`\g__enumext_minipage_right_X_skip`

Internal variables used by `enumext*` and `keyans*` environments.

```

153 \cs_set_protected:Npn \__enumext_tmp:n #1
154 {
155   \bool_new:c { l__enumext_item_starred_#1_bool }
156   \int_new:c { l__enumext_item_column_pos_#1_int }
157   \int_new:c { g__enumext_item_count_all_#1_int }
158   \int_new:c { l__enumext_joined_item_#1_int }
159   \int_new:c { l__enumext_joined_item_aux_#1_int }
160   \int_new:c { l__enumext_tmpa_#1_int }
161   \box_new:c { l__enumext_item_text_#1_box }
162   \dim_new:c { l__enumext_joined_width_#1_dim }
163   \dim_new:c { l__enumext_item_width_#1_dim }
164   \tl_new:c { g__enumext_item_symbol_aux_#1_tl }
165   \str_new:c { l__enumext_align_label_#1_str }
166   \bool_new:c { g__enumext_minipage_active_#1_bool }
167   \tl_new:c { g__enumext_miniright_code_#1_tl }
168   \bool_new:c { g__enumext_minipage_center_#1_bool }
169   \dim_new:c { g__enumext_minipage_right_#1_dim }
170   \skip_new:c { g__enumext_minipage_right_#1_skip }
171 }
172 \clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_item_starred_X_bool` and others.)

`\c__enumext_all_envs_clist`

An internal `clist-var` variable to run with `__enumext_tmp:n`.

```

173 \clist_const:Nn \c__enumext_all_envs_clist
174 {
175   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv},
176   {keyans}{v}, {enumext*}{vii}, {keyans*}{viii}
177 }

```

(End of definition for `\c__enumext_all_envs_clist`.)

10.5 Some utility functions

`__enumext_at_begin_document:n`

A internal “hook” function used for copying plain `list` and `minipage` environments definition and `hyperref` detection.

```
178 \cs_new_protected:Npn \__enumext_at_begin_document:n #1
179 {
180   \hook_gput_code:nnn {begindocument} {enumext} { #1 }
181 }
```

(End of definition for `__enumext_at_begin_document:n`.)

`__enumext_after_env:nn`

A internal “hook” function for execute code `minirigth` and `minirigth*` keys outside the `enumext*` and `keyans*` environments and print check-ans outside the `enumext` and `enumext*` environments.

```
182 \cs_new_protected:Npn \__enumext_after_env:nn #1 #2
183 {
184   \hook_gput_code:nnn {env/#1/after} {enumext} {#2}
185 }
```

(End of definition for `__enumext_after_env:nn`.)

`__enumext_level:`

Function for check current level in `enumext`.

```
186 \cs_new:Nn \__enumext_level:
187 {
188   \int_to_roman:n { \l__enumext_level_int }
189 }
```

(End of definition for `__enumext_level:.`)

`__enumext_if_is_int:nT`

A conditional function to know if the variable we are passing is an integer used by `start` and `widest` keys. This function is taken directly from the answer given by Henri Menke in [How to test if an expl3 function argument is an integer expression?](#).

`__enumext_if_is_int:nF`
`__enumext_if_is_int:nTF`

```
190 \prg_new_protected_conditional:Npnn \__enumext_if_is_int:n #1 { T, F, TF }
191 {
192   \regex_match:nnTF { ^[\+-]?[\d]+$ } {#1} % $
193   { \prg_return_true: }
194   { \prg_return_false: }
195 }
```

(End of definition for `__enumext_if_is_int:nT`, `__enumext_if_is_int:nF`, and `__enumext_if_is_int:nTF`.)

`__enumext_show_length:nnn`

Internal function used by `show-length` key to show “all lengths” calculated and use in `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```
196 \cs_new:Npn \__enumext_show_length:nnn #1 #2 #3
197 {
198   * ~ #2
199   \prg_replicate:nn { 14 - \str_count:n {#2} } { ~ }
200   = ~ \use:c { #1_use:c } { \l__enumext_#2_#3_#1 } \\
201 }
```

(End of definition for `__enumext_show_length:nnn`.)

`__enumext_zero_count_level:`

Internal function used by `check-ans` key.

```
202 \cs_set_protected:Nn \__enumext_zero_count_level:
203 {
204   \cs_set_protected:Npn \__enumext_tmp:n ##1
205   {
206     \int_gzero:c { g__enumext_count_level_##1_int }
207   }
208   \clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {##1} }
209 }
```

(End of definition for `__enumext_zero_count_level:.`)

`__enumext_current_env:`

The function `__enumext_current_env:` will set the global variables `\g__enumext_standar_bool` and `\g__enumext_starred_bool` with which we will distinguish whether the environments `enumext` and `enumext*` are nested in each other.

```
210 \cs_new_protected:Nn \__enumext_current_env:
211 {
212   \str_case:en { \@currenenv }
213   {
214     {enumext}
```



```

215         {
216             \int_compare:nNtT { \__enumext_level_h_int } = { \c_zero_int }
217             {
218                 \bool_gset_true:N \g__enumext_standar_bool
219                 \int_gset:Nn \g__enumext_standar_star_env_int { \inputlineno }
220                 \typeout{working-on-enumext}
221             }
222         }
223     {enumext*}
224     {
225         \int_compare:nNtT { \__enumext_level_int } = { \c_zero_int }
226         {
227             \bool_gset_true:N \g__enumext_starred_bool
228             \int_gset:Nn \g__enumext_starred_star_env_int { \inputlineno }
229             \typeout{working-on-enumext*}
230         }
231     }
232 }
233 }

```

(End of definition for `__enumext_current_env:`.)

10.6 Copying list and minipage environments

The `list` environment provided by \LaTeX has the following plain form:

```

\list{⟨arg one⟩}{⟨arg two⟩}
  \item[⟨opt⟩]
\endlist

```

As a precaution we copy them using `__enumext_at_begin_document:n` in case any package redefines the `list` environment or a related command.

```

\__enumext_start_list:nn
\__enumext_stop_list:
\__enumext_item_std:w

```

The functions `__enumext_start_list:nn`, `__enumext_stop_list:` and `__enumext_item_std:w` correspond to copies of `\list`, `\endlist` and `\item` from plain definition of `list` environment.

```

234 \__enumext_at_begin_document:n
235 {
236     \cs_new_eq:NN \__enumext_start_list:nn \list
237     \cs_new_eq:NN \__enumext_stop_list: \endlist
238     \cs_new_eq:NN \__enumext_item_std:w \item
239 }

```

(End of definition for `__enumext_start_list:nn`, `__enumext_stop_list:`, and `__enumext_item_std:w`.)

The `minipage` environment provided by \LaTeX has the following (simplified) plain form:

```

\minipage[⟨pos⟩][⟨height⟩][⟨inner-pos⟩]{⟨width⟩}
  ⟨internal implement⟩
\endminipage

```

As a precaution we copy them using `__enumext_at_begin_document:n` in case any package redefines the `minipage` environment or a related command.

```

\__enumext_minipage:w
\__enumext_endminipage:

```

The functions `__enumext_minipage:w`, `__enumext_endminipage:` and correspond to copies of `\minipage`, `\endminipage` from plain definition of `minipage` environment.

```

240 \__enumext_at_begin_document:n
241 {
242     \cs_new_eq:NN \__enumext_minipage:w \minipage
243     \cs_new_eq:NN \__enumext_endminipage: \endminipage
244 }

```

(End of definition for `__enumext_minipage:w` and `__enumext_endminipage:`.)

10.7 Compatibility with hyperref and footnotehyper

First we define the necessary rules using “hooks” to determine if the `hyperref` package is loaded.

```

245 \hook_gput_code:nnn { begindocument } { enumext } { \__enumext_after_hyperref: }
246 \hook_gset_rule:nnnn { begindocument } { enumext } { after } { hyperref }

```

```

\__enumext_after_hyperref:
\__enumext_hypertarget:nn
\__enumext_phantomsection:

```

The function `__enumext_after_hyperref:` sets the state of the boolean variable `\l__enumext_hyperref_bool` to “true” if the package is loaded. At this point we will use the public macro `\IfHyperBoolean` to determine if the `hyperfootnotes=true` key is present, if so, we set the state of the boolean variable `__enumext_footnotes_key_bool` to “true”.

```

247 \cs_new_protected:Nn \__enumext_after_hyperref:

```

```

248 {
249   \IfPackageLoadedTF { hyperref }
250   {
251     \msg_info:nnn { enumext } { package-load } { hyperref }
252     \bool_set_true:N \l__enumext_hyperref_bool
253     \IfHyperBoolean{hyperfootnotes}
254     {
255       \typeout{hyperfootnotes=true}
256       \bool_set_true:N \l__enumext_footnotes_key_bool
257     }
258     { \typeout{hyperfootnotes=false} }
259   }
260   { }

```

If the state of the variable `\l__enumext_footnotes_key_bool` is true we will check if the package `footnotehyper` is loaded, in case it is not present, we will set the value of `\l__enumext_footnotes_key_bool` to false and we will redefine `\footnote`.

```

261   \bool_if:NT \l__enumext_footnotes_key_bool
262   {
263     \IfPackageLoadedTF { footnotehyper }
264     {
265       \msg_info:nnn { enumext } { package-load } { footnotehyper }
266     }
267     {
268       \typeout{No ~ footnotehyper ~ load}
269       \typeout{Load ~ and ~ use ~ \string\makesavenoteenv{enumext*}}
270       \bool_set_false:N \l__enumext_footnotes_key_bool
271     }
272   }

```

The functions `__enumext_hypertarget:nn` and `__enumext_phantomsection:` correspond to the internal copies of `\hypertarget` and `\phantomsection`. If the boolean variable `\l__enumext_hyperref_bool` is false the functions `__enumext_hypertarget:nn` and `__enumext_phantomsection:` will be disabled.

```

273   \bool_if:NTF \l__enumext_hyperref_bool
274   {
275     \cs_new_eq:NN \__enumext_hypertarget:nn \hypertarget
276     \cs_new_eq:NN \__enumext_phantomsection: \phantomsection
277   }
278   {
279     \cs_new_eq:NN \__enumext_hypertarget:nn \use_none:nn
280     \cs_new_eq:NN \__enumext_phantomsection: \prg_do_nothing:
281   }
282 }

```

(End of definition for `__enumext_after_hyperref:`, `__enumext_hypertarget:nn`, and `__enumext_phantomsection:`.)

`__enumext_newlabel:nn` The function `__enumext_newlabel:nn` write the information to the `.aux` file when using the `store-ref` key. The arguments taken by the function are:

#1: `\l__enumext_newlabel_arg_one_tl`
 #2: `\l__enumext_newlabel_arg_two_tl`

🔗 The trick here is to manage the number of arguments passed to `\newlabel{#1}{#2}` according to the presence of the `hyperref` package.

```

283 \cs_new_protected:Npn \__enumext_newlabel:nn #1 #2
284 {
285   \protected@write \@auxout { }
286   {
287     \token_to_str:N \newlabel {#1}
288     {
289       {#2}
290       \bool_if:NT \l__enumext_hyperref_bool
291       { { \thepage } {#2} {#1} }
292       { }
293     }
294   }
295   \__enumext_hypertarget:nn {#1} { }
296   \__enumext_phantomsection:
297 }

```

(End of definition for `__enumext_newlabel:nn`.)

10.8 Definition of counters

```
\__enumext_define_counters:Nn
\__enumext_define_counters:cn
```

To create the necessary “counters” we must first make sure that they are not already defined by the user or a package such as `enumitem`, otherwise an error will be returned and the package loading will be aborted. The arguments taken by the function are:

- #1 : A token list `__enumext_counter_X_tl` for “store” the counter’s name.
- #2 : The counter’s name.

```
298 \cs_new_protected:Npn \__enumext_define_counters:Nn #1 #2
299 {
300   \cs_if_exist:cTF { c@ #2 }
301   { \msg_fatal:nnn { enumext } { counters } { #2 } }
302   {
303     \tl_set:Nn #1 { #2 }
304     \newcounter { #2 }
305   }
306 }
```

(End of definition for `__enumext_define_counters:Nn`.)

The counters created here are `enumXi`, `enumXii`, `enumXiii` and `enumXiv` for `enumext` environment, `enumXv` for `keyans` environment, `enumXvi` for `keyanspic` environment, `enumXvii` for `enumext*` and `enumXviii` for the `keyans*` environments.

```
enumXi      307 \__enumext_define_counters:Nn \__enumext_counter_i_tl { enumXi }
enumXii     308 \__enumext_define_counters:Nn \__enumext_counter_ii_tl { enumXii }
enumXiii    309 \__enumext_define_counters:Nn \__enumext_counter_iii_tl { enumXiii }
enumXiv     310 \__enumext_define_counters:Nn \__enumext_counter_iv_tl { enumXiv }
enumXv      311 \__enumext_define_counters:Nn \__enumext_counter_v_tl { enumXv }
enumXvii    312 \__enumext_define_counters:Nn \__enumext_counter_vii_tl { enumXvii }
enumXviii   313 \__enumext_define_counters:Nn \__enumext_counter_viii_tl { enumXviii }
314 \__enumext_define_counters:Nn \__enumext_counter_viii_tl { enumXviii }
```

(End of definition for `enumXi` and others.)

10.9 Definition of labels

This part of the code is inspired by the `enumitem` package. The idea is to be able to access the counters using `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` to use them in the `label` key.

```
\__enumext_register_counter_style:Nn
```

These *counters* will be used as default *labels* if the `label` key is not used for the different levels of the `enumext` environment and the `keyans` environment, so it is necessary to get a default value for `labelwidth` from these *labels* at the same time.

```
315 \cs_new_protected:Npn \__enumext_register_counter_style:Nn #1 #2
316 {
317   \tl_const:cn { c__enumext_widest_ \cs_to_str:N #1 _tl } {#2}
318   \tl_gput_right:Nn \g__enumext_counter_styles_tl {#1}
319 }
320 \__enumext_register_counter_style:Nn \arabic { 0 }
321 \__enumext_register_counter_style:Nn \Alph { M }
322 \__enumext_register_counter_style:Nn \alph { m }
323 \__enumext_register_counter_style:Nn \Roman { VIII }
324 \__enumext_register_counter_style:Nn \roman { viii }
```

(End of definition for `__enumext_register_counter_style:Nn`.)

```
\__enumext_label_width_by_box:Nn
\__enumext_label_width_by_box:cv
```

The function `__enumext_label_width_by_box:Nn` set the default `\labelwidth` using a box width if no `labelwidth` key is passed.

```
325 \cs_new_protected:Npn \__enumext_label_width_by_box:Nn #1 #2
326 {
327   \hbox_set:Nn \l__enumext_label_width_by_box {#2}
328   \dim_set:Nn #1 { \box_wd:N \l__enumext_label_width_by_box }
329 }
330 \cs_generate_variant:Nn \__enumext_label_width_by_box:Nn { cv }
```

(End of definition for `__enumext_label_width_by_box:Nn`.)

```
\__enumext_label_style:Nnn
\__enumext_label_style:cvn
```

The function `__enumext_label_style:Nnn` is used by the `label` key to creates the variables containing the *label style* and will allow to use `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` as arguments. It loops through the defined counter styles in `\g__enumext_counter_styles_tl` (`\arabic`, `\alph`, `\Alph`, `\roman`, and `\Roman`) for example, looking for `\roman*` and replacing that by `\roman{counter}`, and doing the same for the `\g__enumext_widest_label_tl` to keep both in sync.

```
331 \cs_new_protected:Npn \__enumext_label_style:Nnn #1 #2 #3
```

```

332 {
333   \tl_clear_new:N #1
334   \tl_put_right:Ne #1 { \tl_trim_spaces:n {#3} }
335   \tl_gset_eq:NN \g__enumext_widest_label_tl #1
336   \tl_map_inline:Nn \g__enumext_counter_styles_tl
337   {
338     \tl_replace_all:Nne #1 { ##1* } { \exp_not:N ##1 {#2} }
339     \tl_greplace_all:Nne \g__enumext_widest_label_tl { ##1* }
340     { \tl_use:c { c__enumext_widest_ \cs_to_str:N ##1 _tl } }
341   }
342   \__enumext_label_width_by_box:Nn \__enumext_current_widest_dim
343   { \tl_use:N \g__enumext_widest_label_tl }
344   \tl_set_eq:cN { the #2 } #1
345 }
346 \cs_generate_variant:Nn \__enumext_label_style:Nnn { cvn }

```

(End of definition for `__enumext_label_style:Nnn`.)

10.10 Setting keys associated with label

font Definition of keys `font`, `labelsep`, `labelwidth`, `wrap-label` and `wrap-label*` keys for `enumext` and
 labelsep `keyans` environments.
 labelwidth
 wrap-label
 wrap-label*

```

347 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
348 {
349   \keys_define:nn { enumext / #1 }
350   {
351     font .tl_set:c = { l__enumext_label_font_style_#2_tl },
352     font .value_required:n = true,
353     labelsep .dim_set:c = { l__enumext_labelsep_#2_dim },
354     labelsep .initial:n = {0.3333em},
355     labelsep .value_required:n = true,
356     labelwidth .dim_set:c = { l__enumext_labelwidth_#2_dim },
357     labelwidth .value_required:n = true,
358     wrap-label .cs_set_protected:cp = { __enumext_wrapper_label_#2:n } ##1,
359     wrap-label .initial:n = {##1},
360     wrap-label .value_required:n = true,
361     wrap-label* .code:n = {
362       \bool_set_true:c { l__enumext_wrap_label_opt_#2_bool }
363       \keys_set:nn { enumext / #1 } { wrap-label = {##1} }
364     },
365     wrap-label* .value_required:n = true,
366   }
367 }
368 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `font` and others.)

- In this point, the following are set `__enumext_wrapper_label_X:n` which will be used by `__enumext_make_label:` for the different levels of the `enumext` environment and is set to `__enumext_wrapper_label_v:n` which will be used by `__enumext_keyans_make_label:` for `keyans` and `keyanspic` environments.

align The `align` key is implemented differently for “starred” and “non starred” environments.

```

369 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
370 {
371   \keys_define:nn { enumext / #1 }
372   {
373     align .choice:,
374     align / left .code:n =
375     {
376       \tl_clear:c { l__enumext_label_fill_left_#2_tl }
377       \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
378     },
379     align / right .code:n =
380     {
381       \tl_set:cn { l__enumext_label_fill_left_#2_tl } { \hfill }
382       \tl_clear:c { l__enumext_label_fill_right_#2_tl }
383     },
384     align / center .code:n =
385     {
386       \tl_set:cn { l__enumext_label_fill_left_#2_tl } { \hfill }
387       \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
388     },

```

```

389     align .initial:n = left,
390     align .value_required:n = true,
391   }
392 }
393 \clist_map_inline:nn
394 {
395   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {keyans}{v}
396 }
397 { \__enumext_tmp:nn #1 }

```

Definition of `align` key for `enumext*` and `keyans*` environments.

```

398 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
399 {
400   \keys_define:nn { enumext / #1 }
401   {
402     align .choice:,
403     align / left .code:n = \str_set:cn { l__enumext_align_label_#2_str } { l },
404     align / right .code:n = \str_set:cn { l__enumext_align_label_#2_str } { r },
405     align / center .code:n = \str_set:cn { l__enumext_align_label_#2_str } { c },
406     align .initial:n = left,
407     align .value_required:n = true,
408   }
409 }
410 \clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }

```

(End of definition for `align`.)

10.11 Setting label and ref keys

`__enumext_regex_label_ref_key:`

The internal function `__enumext_regex_label_ref_key:` replace the `*` with the actual counter of the running level and is used by the `__enumext_set_label_ref:n` function.

It loops through the defined counter styles in `\c__enumext_counter_style_tl` and replace `*` by real command, for example, looking for `\arabic*` and replacing that by `\arabic{<counter>}` defined on the current level.

```

411 \cs_new_protected:Nn \__enumext_regex_label_ref_key:
412 {
413   \tl_map_inline:Nn \c__enumext_counter_style_tl
414   {
415     \regex_replace_once:nnN { \c{##1}}{*}
416     { \c{##1}\cB{\u{l__enumext_ref_aux_tl}\cE} } \__enumext_ref_key_arg_tl
417   }
418 }

```

(End of definition for `__enumext_regex_label_ref_key:`.)

`__enumext_set_label_ref:n`

The `__enumext_set_label_ref:n` function controlled by the `ref` key is in charge of handling the customization of the reference system.

First we will set the variable `\l__enumext_the_counter_X_tl` according to the command created for *each counter*, apply the `regex` function `__enumext_regex_label_ref_key:` and then renew the command and save it in the variable `\l__enumext_counter_style_for_ref_X_tl`.

```

419 \cs_new_protected:Npn \__enumext_set_label_ref:n #1
420 {
421   \tl_set:Nn \l__enumext_ref_key_arg_tl {#1}
422   \tl_set_eq:Nc \l__enumext_ref_aux_tl { l__enumext_counter_ \__enumext_level: _tl }
423   \__enumext_regex_label_ref_key:
424   \tl_set_eq:Nc \l__enumext_ref_aux_tl { l__enumext_the_counter_ \__enumext_level: _tl }
425   \tl_put_right:ce { l__enumext_counter_style_for_ref_ \__enumext_level: _tl }
426   {
427     \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_aux_tl }
428     { \exp_not:V \l__enumext_ref_key_arg_tl }
429   }
430 }

```

(End of definition for `__enumext_set_label_ref:n`.)

`__enumext_use_key_ref:`

Finally the function `__enumext_use_key_ref:` will execute the modification for the reference system in the second argument of the environment definition `enumext`.

```

431 \cs_new_protected:Nn \__enumext_use_key_ref:
432 {
433   \tl_if_empty:cF { l__enumext_counter_style_for_ref_ \__enumext_level: _tl }
434   {

```

```

435         \tl_use:c { l__enumext_counter_style_for_ref_ \__enumext_level: _tl }
436     }
437 }

```

(End of definition for `__enumext_use_key_ref:`.)

For `enumext*` and `keyans*` environments the situation is a bit different since `hyperref` interferes here (I am not clear why), so we will define a new function to execute the task.

To handle that we will look at the nesting level of the starred environments, later I will run the constraint functions to make everything OK.

The `__enumext_set_label_ref_h:n` function controlled by the `ref` key is in charge of handling the customization of the reference system.

First we will set the variable `\l__enumext_the_counter_X_tl` according to the command created for *each counter*, apply the `regex` function `__enumext_regex_label_ref_key:` and then renew the command and save it in the variable `\l__enumext_counter_style_for_ref_X_tl`.

```

438 \cs_new_protected:Npn \__enumext_set_label_ref_h:n #1
439 {
440     \tl_set:Nn \l__enumext_ref_key_arg_tl {#1}
441     \int_compare:nNnTF { \l__enumext_level_h_int } = { 1 }
442     {
443         \tl_set_eq:NN \l__enumext_ref_aux_tl \l__enumext_counter_vii_tl
444         \__enumext_regex_label_ref_key:
445         \tl_set_eq:NN \l__enumext_ref_aux_tl \l__enumext_the_counter_vii_tl
446         \tl_put_right:Ne \l__enumext_counter_style_for_ref_vii_tl
447         {
448             \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_aux_tl }
449             { \exp_not:V \l__enumext_ref_key_arg_tl }
450         }
451     }
452     {
453         \tl_set_eq:NN \l__enumext_ref_aux_tl \l__enumext_counter_viii_tl
454         \__enumext_regex_label_ref_key:
455         \tl_set_eq:NN \l__enumext_ref_aux_tl \l__enumext_the_counter_viii_tl
456         \tl_put_right:Ne \l__enumext_counter_style_for_ref_vii_tl
457         {
458             \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_aux_tl }
459             { \exp_not:V \l__enumext_ref_key_arg_tl }
460         }
461     }
462 }

```

(End of definition for `__enumext_set_label_ref_h:n`.)

Finally the function `__enumext_use_key_ref_h:` will execute the modification for the reference system in the second argument of the environment definition `enumext*` and `keyans*`.

```

463 \cs_new_protected:Npn \__enumext_use_key_ref_h:
464 {
465     \int_compare:nNnTF { \l__enumext_level_h_int } = { 1 }
466     {
467         \tl_if_empty:NF \l__enumext_counter_style_for_ref_vii_tl
468         {
469             \tl_use:N \l__enumext_counter_style_for_ref_vii_tl
470         }
471     }
472     {
473         \tl_if_empty:NF \l__enumext_counter_style_for_ref_viii_tl
474         {
475             \tl_use:N \l__enumext_counter_style_for_ref_viii_tl
476         }
477     }
478 }

```

(End of definition for `__enumext_use_key_ref_h:`.)

10.11.1 Define and set label key for enumext environment

Here we set the default *⟨labels⟩* of the four levels of `enumext` environment, along with the default value for `labelwidth` key.

```

\l__enumext_label_i_tl
\l__enumext_label_ii_tl
\l__enumext_label_iii_tl
\l__enumext_label_iv_tl
479 \cs_set_protected:Npn \__enumext_tmp:nnn #1 #2 #3
480 {
481     \keys_define:nn { enumext / #1 }

```



```

482     {
483       label .code:n = {
484         \__enumext_label_style:cvn { l__enumext_label_#2_tl }
485         { l__enumext_counter_#2_tl } {##1}
486         \dim_set_eq:cN { l__enumext_labelwidth_#2_dim }
487         \l__enumext_current_widest_dim
488       },
489       label .initial:n = #3,
490       label .value_required:n = true,
491       ref .code:n = \__enumext_set_label_ref:n {##1},
492       ref .value_required:n = true,
493     }
494   }
495   \__enumext_tmp:nnn { level-1 } { i } { \arabic*. }
496   \__enumext_tmp:nnn { level-2 } { ii } { (\alph*) }
497   \__enumext_tmp:nnn { level-3 } { iii } { \roman*. }
498   \__enumext_tmp:nnn { level-4 } { iv } { \Alph*. }

```

(End of definition for `label` and others.)

10.11.2 Define and set `label` key for `enumext*` and `keyans*` environments

Here we set the default `<label>` for `enumext*` and `keyans*` environments, along with the default value for `labelwidth` key.

```

\l__enumext_label_vii_tl
\l__enumext_label_viii_tl
499 \cs_set_protected:Npn \__enumext_tmp:nnn #1 #2 #3
500 {
501   \keys_define:nn { enumext / #1 }
502   {
503     label .code:n = {
504       \__enumext_label_style:cvn { l__enumext_label_#2_tl }
505       { l__enumext_counter_#2_tl } {##1}
506       \dim_set_eq:cN { l__enumext_labelwidth_#2_dim }
507       \l__enumext_current_widest_dim
508     },
509     label .initial:n = #3,
510     label .value_required:n = true,
511     ref .code:n = \__enumext_set_label_ref_h:n {##1},
512     ref .value_required:n = true,
513   }
514 }
515 \__enumext_tmp:nnn { enumext* } { vii } { \arabic*. }
516 \__enumext_tmp:nnn { keyans* } { viii } { (\Alph*) }

```

(End of definition for `label` and others.)

10.11.3 Define and set `label` key for `keyans` and `keyanspic` environment

Here we set the default `<label>` for `keyans` and `keyanspic` environment, along with the default value for `labelwidth`. The `keyanspic` environment use the same `<label>` as the `keyans` environment.

Define and set `label` key for `keyans` environment.

```

517 \keys_define:nn { enumext / keyans }
518 {
519   label .code:n = {
520     \__enumext_label_style:cvn { l__enumext_label_v_tl }
521     { l__enumext_counter_v_tl } {##1}
522     \dim_set_eq:cN { l__enumext_labelwidth_v_dim }
523     \l__enumext_current_widest_dim
524     \__enumext_label_style:cvn { l__enumext_label_vi_tl }
525     { l__enumext_counter_vi_tl } {##1}
526     \dim_set_eq:cN { l__enumext_labelwidth_v_dim }
527     \l__enumext_current_widest_dim
528   },
529   label .initial:n = (\Alph*),
530   label .value_required:n = true,
531 }

```

(End of definition for `label`, `\l__enumext_label_v_tl`, and `\l__enumext_label_vi_tl`.)

10.12 Setting start and widest keys

The function `__enumext_start_from:NNn` used by the `start` key take three arguments:

```

#1: \l__enumext_label_X_tl
#2: \l__enumext_start_X_int

```

#3: *<integer or string>*

The first argument of this function are the “*counter style*” set by `label` key, the second argument is returned by the function, the third argument can be an *<integer>* or *<string>* of the form `\Alph`, `\alph`, `\Roman` or `\roman`. This effectively allows `start=A` or `start=1` to be used.

```

532 \cs_new_protected:Npn \__enumext_start_from:NNn #1 #2 #3
533 {
534   \__enumext_if_is_int:nTF { #3 }
535   {
536     \int_set:Nn #2 {#3}
537   }
538   {
539     \regex_match:nVT { \c{Alph} | \c{alph} } {#1}
540     { \int_set:Nn #2 { \int_from_alph:n {#3} } }
541     \regex_match:nVT { \c{Roman} | \c{roman} } {#1}
542     { \int_set:Nn #2 { \int_from_roman:n {#3} } }
543   }
544 }
545 \cs_generate_variant:Nn \__enumext_start_from:NNn { ccn }

```

(End of definition for `__enumext_start_from:NNn`.)

```

\__enumext_widest_from:nNNn
\__enumext_widest_from:nccn

```

The function `__enumext_widest_from:nNNn` used by the `widest` key take four arguments:

- #1: The counter associated with the environment level
- #2: `\l__enumext_label_X_tl`
- #3: `\l__enumext_labelwidth_X_dim`
- #4: *<integer or string>*

The second and third arguments of this function are the values set by `label` and `labelwidth` keys, the four argument can be an *<integer>* or *<string>* of the form `\Alph`, `\alph`, `\Roman` or `\roman`. The value of the four argument is set temporarily for the identified counter in this point (level), then the value is expanded into a “*box*” and the “*width*” of the “*box*” is returned.

```

546 \cs_new_protected:Npn \__enumext_widest_from:nNNn #1 #2 #3 #4
547 {
548   \__enumext_if_is_int:nTF {#4}
549   {
550     \setcounter{enumX#1} { #4 }
551   }
552   {
553     \regex_match:nVT { \c{Alph} | \c{alph} } {#2}
554     { \setcounter{enumX#1} { \int_from_alph:n {#4} } }
555     \regex_match:nVT { \c{Roman} | \c{roman} } {#2}
556     { \setcounter{enumX#1} { \int_from_roman:n {#4} } }
557   }
558   \__enumext_label_width_by_box:cv
559   { \l__enumext_labelwidth_#1_dim } { \l__enumext_label_#1_tl }
560 }
561 \cs_generate_variant:Nn \__enumext_widest_from:nNNn { nccn }

```

(End of definition for `__enumext_widest_from:nNNn`.)

Now define and set `start` and `widest` keys for `enumext` and `keyans` environments.

```

start
widest
\l__enumext_start_X_int
562 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
563 {
564   \keys_define:nn { enumext / #1 }
565   {
566     start .code:n = {
567       \__enumext_start_from:ccn
568       { \l__enumext_label_#2_tl }
569       { \l__enumext_start_#2_int } {##1}
570     },
571     start .initial:n = 1,
572     widest .code:n = {
573       \__enumext_widest_from:nccn {#2}
574       { \l__enumext_label_#2_tl }
575       { \l__enumext_labelwidth_#2_dim } {##1}
576     },
577     widest .value_required:n = true,
578     start .value_required:n = true,
579   }
580 }
581 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `start`, `widest`, and `\l__enumext_start_X_int`.)

10.13 Setting keys for vertical spaces

Define and set `topsep`, `partopsep`, `parsep`, `itemsep`, `noitemsep` and `nosep` keys for `enumext` and `keyans` environments.

```

topsep
partopsep
parsep
noitemsep
nosep
582 \cs_set_protected:Npn \__enumext_tmp:nnnnnn #1 #2 #3 #4 #5 #6
583 {
584   \keys_define:nn { enumext / #1 }
585   {
586     topsep      .skip_set:c = { l__enumext_topsep_#2_skip },
587     topsep      .initial:n   = {#3},
588     topsep      .value_required:n = true,
589     partopsep   .skip_set:c = { l__enumext_partopsep_#2_skip },
590     partopsep   .initial:n   = {#4},
591     partopsep   .value_required:n = true,
592     parsep      .skip_set:c = { l__enumext_parsep_#2_skip },
593     parsep      .initial:n   = {#5},
594     parsep      .value_required:n = true,
595     itemsep     .skip_set:c = { l__enumext_itemsep_#2_skip },
596     itemsep     .initial:n   = {#6},
597     itemsep     .value_required:n = true,
598     noitemsep   .meta:n      = { itemsep = 0pt, parsep = 0pt },
599     noitemsep   .value_forbidden:n = true,
600     nosep       .meta:n      = {
601                                   itemsep = 0pt, parsep= 0pt,
602                                   topsep = 0pt, partopsep = 0pt,
603                                   },
604     nosep       .value_forbidden:n = true,
605   }
606 }
```

Now we set the values based on standard `article` class in `10pt`.

```

607 \__enumext_tmp:nnnnnn { level-1 } { i } { 8.0pt plus 2.0pt minus 4.0pt }
608 { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
609 { 4.0pt plus 2.0pt minus 1.0pt }
610 \__enumext_tmp:nnnnnn { level-2 } { ii } { 4.0pt plus 2.0pt minus 1.0pt }
611 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
612 { 2.0pt plus 1.0pt minus 1.0pt }
613 \__enumext_tmp:nnnnnn { level-3 } { iii } { 2.0pt plus 1.0pt minus 1.0pt }
614 { 1.0pt minus 1.0pt } { 0pt } { 2.0pt plus 1.0pt minus 1.0pt }
615 \__enumext_tmp:nnnnnn { level-4 } { iv } { 2.0pt plus 1.0pt minus 1.0pt }
616 { 1.0pt minus 1.0pt } { 0pt } { 2.0pt plus 1.0pt minus 1.0pt }
617 \__enumext_tmp:nnnnnn { keyans } { v } { 4.0pt plus 2.0pt minus 1.0pt }
618 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
619 { 2.0pt plus 1.0pt minus 1.0pt }
620 \__enumext_tmp:nnnnnn { enumext* } { vii } { 8.0pt plus 2.0pt minus 4.0pt }
621 { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
622 { 4.0pt plus 2.0pt minus 1.0pt }
623 \__enumext_tmp:nnnnnn { keyans* } { viii } { 4.0pt plus 2.0pt minus 1.0pt }
624 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
625 { 2.0pt plus 1.0pt minus 1.0pt }
```

(End of definition for `topsep` and others.)

10.14 Setting keys for horizontal spaces

Define and set `itemindent`, `rightmargin`, `listparindent`, `list-offset` and `list-indent` keys for `enumext` and `keyans` environments.

```

626 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
627 {
628   \keys_define:nn { enumext / #1 }
629   {
630     itemindent   .dim_set:c = { l__enumext_fake_item_indent_#2_dim },
631     itemindent   .value_required:n = true,
632     rightmargin  .dim_set:c = { l__enumext_rightmargin_#2_dim },
633     rightmargin  .value_required:n = true,
634     listparindent .dim_set:c = { l__enumext_listparindent_#2_dim },
635     listparindent .value_required:n = true,
636     list-offset  .dim_set:c = { l__enumext_listoffset_#2_dim },
637     list-offset  .value_required:n = true,
638     list-indent  .code:n      =
```

```

639             \bool_set_true:c { l__enumext_leftmargin_tmp_#2_bool }
640             \dim_set:cn { l__enumext_leftmargin_tmp_#2_dim } {##1},
641     list-indent .value_required:n = true,
642   }
643 }
644 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `itemindent` and others.)

For `enumext*` and `keyans*` environments the situation is a bit different, the `list-indent` key behaves like the `list-offset` key.

```

645 \cs_set_protected:Npn \__enumext_tmp:n #1
646 {
647   \keys_define:nn { enumext / #1 } { list-indent .initial:n = 0pt, }
648 }
649 \clist_map_inline:nn { enumext*, keyans* } { \__enumext_tmp:n {#1} }

```

10.14.1 Functions for setting the fake `itemindent`

The `itemindent` key does not set the value of `\itemindent`, it only sets the value of the *horizontal space* applied using `\skip_horizontal:N`. We will store this value in the variable and only apply it when it is greater than `0pt`. Here I will need to place `\mode_leave_vertical:` and the plain \TeX macro `\ignorespaces` to avoid unwanted extra space when using the `itemindent` key.

```

650 \cs_set_protected:Nn \__enumext_fake_item:
651 {
652   \dim_compare:nNnT
653     { \dim_use:c { l__enumext_fake_item_indent_ \__enumext_level: _dim } }
654     >
655     { \c_zero_dim }
656   {
657     \tl_set:ce { l__enumext_fake_item_indent_ \__enumext_level: _tl }
658     {
659       \exp_not:N \mode_leave_vertical:
660       \exp_not:n { \skip_horizontal:n }
661       { \dim_use:c { l__enumext_fake_item_indent_ \__enumext_level: _dim } }
662       \ignorespaces
663     }
664   }
665 }
666 \cs_set_protected:Nn \__enumext_keyans_fake_item:
667 {
668   \dim_compare:nNnT
669     { \l__enumext_fake_item_indent_v_dim } > { \c_zero_dim }
670   {
671     \tl_set:Ne \l__enumext_fake_item_indent_v_tl
672     {
673       \exp_not:N \mode_leave_vertical:
674       \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_v_dim
675     }
676   }
677 }
678 \cs_set_protected:Nn \__enumext_fake_item_vii:
679 {
680   \dim_compare:nNnT
681     { \l__enumext_fake_item_indent_vii_dim } > { \c_zero_dim }
682   {
683     \tl_set:Ne \l__enumext_fake_item_indent_vii_tl
684     {
685       \exp_not:N \mode_leave_vertical:
686       \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_vii_dim
687     }
688   }
689 }
690 \cs_set_protected:Nn \__enumext_fake_item_viii:
691 {
692   \dim_compare:nNnT
693     { \l__enumext_fake_item_indent_viii_dim } > { \c_zero_dim }
694   {
695     \tl_set:Ne \l__enumext_fake_item_indent_viii_tl
696     {
697       \exp_not:N \mode_leave_vertical:
698       \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_viii_dim

```

```

699     }
700   }
701 }

```

(End of definition for `__enumext_fake_item:` and others.)

10.15 Setting show-length key

show-length

Define and set `show-length` key for `enumext`, `enumext*`, `keyans` and `keyans*` environments. The function sets the boolean variable `__enumext_show_length_X_bool` used in the definition of all environments to “*true*” and calls the function `__enumext_show_length:nnn` which prints all the values of the “*vertical*” and “*horizontal*” parameters calculated and used.

```

702 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
703 {
704   \keys_define:nn { enumext / #1 }
705   {
706     show-length .bool_set:c = { l__enumext_show_length_#2_bool },
707     show-length .initial:n = false,
708   }
709 }
710 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `show-length`.)

10.16 Setting before, after and first keys

before
before*
after
first

Define and set `before`, `before*`, `after` and `first` keys for `enumext` and `keyans` environments.

```

711 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
712 {
713   \keys_define:nn { enumext / #1 }
714   {
715     before .tl_set:c = { l__enumext_before_no_starred_key_#2_tl },
716     before .value_required:n = true,
717     before* .tl_set:c = { l__enumext_before_starred_key_#2_tl },
718     before* .value_required:n = true,
719     after .tl_set:c = { l__enumext_after_stop_list_#2_tl },
720     after .value_required:n = true,
721     first .tl_set:c = { l__enumext_after_list_args_#2_tl },
722     first .value_required:n = true,
723   }
724 }
725 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `before` and others.)

10.16.1 Functions for before, after and first keys in enumext

`__enumext_before_args_exec:` The function `__enumext_before_args_exec:` executes the $\{\langle code \rangle\}$ set by the `before*` key “*before*” the `enumext` environment is started. The $\{\langle code \rangle\}$ is executed “*without*” knowing any definition of the *second argument* of the list.

```

726 \cs_new_protected:Nn \__enumext_before_args_exec:
727 {
728   \tl_use:c { l__enumext_before_starred_key_ \__enumext_level: _tl }
729 }

```

The function `__enumext_before_keys_exec:` executes the $\{\langle code \rangle\}$ set by the `before` key “*before*” the `enumext` environment is started in *second argument* of the list. The $\{\langle code \rangle\}$ is executed “*knowing*” all definition and values provides by $\langle keys \rangle$.

```

730 \cs_new_protected:Nn \__enumext_before_keys_exec:
731 {
732   \tl_use:c { l__enumext_before_no_starred_key_ \__enumext_level: _tl }
733 }

```

The function `__enumext_after_stop_list:` executes the $\{\langle code \rangle\}$ set by the `after` key “*after*” the `enumext` environment has finished.

```

734 \cs_new_protected:Nn \__enumext_after_stop_list:
735 {
736   \tl_use:c { l__enumext_after_stop_list_ \__enumext_level: _tl }
737 }

```

The function `__enumext_after_args_exec`: executes the $\{\langle code \rangle\}$ set by the `first` key after the end of the second argument of the list defining the `enumext` environment, just before the first occurrence of `\item`.

```
738 \cs_new_protected:Nn \__enumext_after_args_exec:
739 {
740   \tl_use:c { l__enumext_after_list_args_ \__enumext_level: _tl }
741 }
```

(End of definition for `__enumext_before_args_exec`: and others.)

10.16.2 Functions for before, after and first keys in keyans

`__enumext_before_args_exec_v`: The function `__enumext_before_args_exec_v`: executes the $\{\langle code \rangle\}$ set by the `before*` key “before” the `keyans` environment is started. The $\{\langle code \rangle\}$ is executed “without” knowing any definition of the $\{\langle arg two \rangle\}$ of the list.

```
\__enumext_before_keys_exec_v:
\__enumext_after_stop_list_v:
\__enumext_after_args_exec_v:
742 \cs_new_protected:Nn \__enumext_before_args_exec_v:
743 {
744   \tl_use:N \l__enumext_before_starred_key_v_tl
745 }
```

The function `__enumext_before_keys_exec_v`: executes the $\{\langle code \rangle\}$ set by the `before` key “before” the `keyans` environment is started in $\{\langle arg two \rangle\}$ of the list. The $\{\langle code \rangle\}$ is executed “knowing” all definition and values provides by $\langle keys \rangle$.

```
746 \cs_new_protected:Nn \__enumext_before_keys_exec_v:
747 {
748   \tl_use:N \l__enumext_before_no_starred_key_v_tl
749 }
```

The function `__enumext_after_stop_list_v`: executes the $\{\langle code \rangle\}$ set by the `after` key “after” the `keyans` environment has finished.

```
750 \cs_new_protected:Nn \__enumext_after_stop_list_v:
751 {
752   \tl_use:N \l__enumext_after_stop_list_v_tl
753 }
```

The function `__enumext_after_args_exec_v`: executes the $\{\langle code \rangle\}$ set by the `first` key after the end of $\{\langle arg two \rangle\}$ of the list defining the `keyans` environment, just before the first occurrence of `\item`.

```
754 \cs_new_protected:Nn \__enumext_after_args_exec_v:
755 {
756   \tl_use:N \l__enumext_after_list_args_v_tl
757 }
```

(End of definition for `__enumext_before_args_exec_v`: and others.)

10.16.3 Functions for before, after and first keys in enumext* and keyans*

`__enumext_before_args_exec_vii`: The function `__enumext_before_args_exec_v`: executes the $\{\langle code \rangle\}$ set by the `before*` key “before” the `keyans` environment is started. The $\{\langle code \rangle\}$ is executed “without” knowing any definition of the $\{\langle arg two \rangle\}$ of the list.

```
\__enumext_before_keys_exec_vii:
\__enumext_after_stop_list_vii:
\__enumext_after_args_exec_vii:
758 \cs_new_protected:Nn \__enumext_before_args_exec_vii:
759 {
760   \tl_use:N \l__enumext_before_starred_key_vii_tl
761 }
762 \cs_new_protected:Nn \__enumext_before_args_exec_viii:
763 {
764   \tl_use:N \l__enumext_before_starred_key_viii_tl
765 }
```

The functions `__enumext_before_keys_exec_vii`: and `__enumext_before_keys_exec_viii`: executes the $\{\langle code \rangle\}$ set by the `before` key “before” in `enumext*` and `keyans*` environments is started in $\{\langle arg two \rangle\}$ of the list. The $\{\langle code \rangle\}$ is executed “knowing” all definition and values provides by $\langle keys \rangle$.

```
766 \cs_new_protected:Nn \__enumext_before_keys_exec_vii:
767 {
768   \tl_use:N \l__enumext_before_no_starred_key_vii_tl
769 }
770 \cs_new_protected:Nn \__enumext_before_keys_exec_viii:
771 {
772   \tl_use:N \l__enumext_before_no_starred_key_viii_tl
773 }
```

The function `__enumext_after_stop_list`: executes the `{\code}` set by the `after` key “after” the `keyans` environment has finished.

```

774 \cs_new_protected:Nn \__enumext_after_stop_list_vii:
775 {
776   \tl_use:N \l__enumext_after_stop_list_vii_tl
777 }
778 \cs_new_protected:Nn \__enumext_after_stop_list_viii:
779 {
780   \tl_use:N \l__enumext_after_stop_list_viii_tl
781 }

```

The function `__enumext_after_args_exec_v`: executes the `{\code}` set by the `first` key after the end of `{\arg two}` of the list defining the `keyans` environment, just before the first occurrence of `\item`.

```

782 \cs_new_protected:Nn \__enumext_after_args_exec_vii:
783 {
784   \tl_use:N \l__enumext_after_list_args_vii_tl
785 }
786 \cs_new_protected:Nn \__enumext_after_args_exec_viii:
787 {
788   \tl_use:N \l__enumext_after_list_args_viii_tl
789 }

```

(End of definition for `__enumext_before_args_exec_vii`: and others.)

10.17 Setting keys for multicols and minipage

The default value of the `columns-sep` key is handled by the state of the boolean variable `\l__enumext_columns_sep_X_bool` which is handled in the internal definition of the `enumext` and `keyans` environments.

Define and set `mini-env`, `mini-sep`, `columns-sep` and `columns` keys for `enumext` and `keyans` environments.

```

790 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
791 {
792   \keys_define:nn { enumext / #1 }
793   {
794     mini-env .dim_set:c = { \l__enumext_minipage_right_#2_dim },
795     mini-env .value_required:n = true,
796     mini-sep .dim_set:c = { \l__enumext_minipage_hsep_#2_dim },
797     mini-sep .initial:n = 0.3333em,
798     mini-sep .value_required:n = true,
799     columns-sep .dim_set:c = { \l__enumext_columns_sep_#2_dim },
800     columns-sep .value_required:n = true,
801     columns .int_set:c = { \l__enumext_columns_#2_int },
802     columns .initial:n = 1,
803     columns .value_required:n = true,
804   }
805 }
806 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

For `enumext*` and `keyans*` environments the situation is a bit different, the default value for `columns` key are `2` and the command `\miniright` is not available, so we will add the keys `miniright` and `miniright*` to implement support for `minipage`.

```

807 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
808 {
809   \keys_define:nn { enumext / #1 }
810   {
811     columns .initial:n = 2,
812     miniright .tl_gset:c = { g__enumext_miniright_code_#2_tl },
813     miniright .value_required:n = true,
814     miniright* .code:n = {
815       \bool_gset_true:c { g__enumext_minipage_center_#2_bool }
816       \keys_set:nn { enumext / #1 } { miniright = {##1} }
817     },
818     miniright* .value_required:n = true,
819   }
820 }
821 \clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }

```

(End of definition for `mini-env` and others.)

10.18 Adjustment of vertical spaces for multicol

When nesting a “list environment” inside the `multicol` environment, the values of the “vertical spaces” are lost, basically the `multicol` environment takes control over them. Graphically it can be seen like in the figure 7.



Figure 7: Representation of the vertical space in `multicol` for a nested level.

To keep the desired spaces *above* and *below* in the “list environment” (`\topsep` + `[\partopsep]`) it is necessary to “adjust” the spaces added by the `multicol` environment. The most appropriate option in this case is to use a “context sensitive” vertical space with `\addvspace`.

I should make it clear that the implementation here is a “bit questionable”. At first glance doing `\multicolsep=\topsep` seemed right, but the results were not always as expected. An almost *imperceptible* detail is that in some cases the `\itemsep` values of are “stretched”, possibly due to the use of `\raggedcolumns` and this affects the lower space when closing the environment, which is “smaller” than expected. My attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

10.18.1 Adjustment of vertical spaces for multicol in enumext

`__enumext_multi_set_vskip:`

The function `__enumext_multi_set_vskip:` will take care of determining the “adjusted spaces” that we will apply “above” and “below” the `multicol` environment in `enumext`.

We will set the default values taking into account that \TeX is in (*horizontal mode*), then we will make the settings for the (*vertical mode*) in which `\partopsep` comes into play.

Set the values of `__enumext_multicol_above_X_skip` and `__enumext_multicol_below_X_skip` equal to the value of `\topsep` in the *current level*.

```

822 \cs_new_protected:Nn \__enumext_multi_set_vskip:
823 {
824   \skip_set:cn { \__enumext_multicol_above_ \__enumext_level: } _skip {
825     {
826       \skip_use:c { \__enumext_topsep_ \__enumext_level: } _skip {
827       }
828     }
829   \skip_set:cn { \__enumext_multicol_below_ \__enumext_level: } _skip {
830     {
831       \skip_use:c { \__enumext_topsep_ \__enumext_level: } _skip {
832     }
833   }

```

(End of definition for `__enumext_multi_set_vskip:`)

`__enumext_add_pre_parsep:`

The function `__enumext_add_pre_parsep:` “adjusted” the value of `__enumext_multicol_above_X_skip` detecting the value of `\parsep` from the previous level. This is necessary since `\parsep` from the previous level affects the *vertical spaces*.

```

834 \cs_new_protected:Nn \__enumext_add_pre_parsep:
835 {
836   \int_case:nn { \__enumext_level_int }
837   {
838     { 2 }{
839       \skip_if_eq:nnF { \__enumext_parsep_i_skip } { \c_zero_skip } {
840         {
841           \skip_add:Nn \__enumext_multicol_above_ii_skip { \__enumext_parsep_i_skip }
842         }
843       }
844     { 3 }{
845       \skip_if_eq:nnF { \__enumext_parsep_ii_skip } { \c_zero_skip } {
846         {
847           \skip_add:Nn \__enumext_multicol_above_iii_skip { \__enumext_parsep_ii_skip }
848         }
849       }
850     { 4 }{
851       \skip_if_eq:nnF { \__enumext_parsep_iii_skip } { \c_zero_skip } {
852         {
853           \skip_add:Nn \__enumext_multicol_above_iv_skip { \__enumext_parsep_iii_skip }
854         }
855       }

```

```

856     }
857 }

```

(End of definition for `__enumext_add_pre_parse:`)

`__enumext_multi_addvspace:` The function `__enumext_multi_addvspace:` will apply the spaces set using `\addvspace` “above” the `multicols` environment in `enumext`, taking into account whether TeX is in *(horizontal mode)* or *(vertical mode)*.

```

858 \cs_new_protected:Nn \__enumext_multi_addvspace:
859 {
860   \__enumext_multi_set_vskip:
861   \mode_if_vertical:T
862   {
863     \skip_add:cn { \__enumext_multicols_above_ \__enumext_level: _skip }
864     {
865       \skip_use:c { \__enumext_partopsep_ \__enumext_level: _skip }
866     }
867     \skip_add:cn { \__enumext_multicols_below_ \__enumext_level: _skip }
868     {
869       \skip_use:c { \__enumext_partopsep_ \__enumext_level: _skip }
870     }
871   }
872   \par\nopagebreak
873   \addvspace{ \skip_use:c { \__enumext_multicols_above_ \__enumext_level: _skip } }
874 }

```

(End of definition for `__enumext_multi_addvspace:`)

10.18.2 Adjustment of vertical spaces for multicols in keyans

`__enumext_keyans_multi_set_vskip:` The function `__enumext_keyans_multi_set_vskip:` will take care of determining the “adjusted spaces” that we will apply “above” and “below” the `multicols` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

`__enumext_keyans_multi_addvspace:`

```

875 \cs_new_protected:Nn \__enumext_keyans_multi_set_vskip:
876 {
877   \skip_set:Nn \__enumext_multicols_above_v_skip
878   {
879     \__enumext_topsep_v_skip
880   }
881   \skip_set:Nn \__enumext_multicols_below_v_skip
882   {
883     \__enumext_topsep_v_skip
884   }
885 }
886 \cs_new_protected:Nn \__enumext_keyans_multi_addvspace:
887 {
888   \__enumext_keyans_multi_set_vskip:
889   \mode_if_vertical:T
890   {
891     \skip_add:Nn \__enumext_multicols_above_v_skip
892     {
893       \skip_use:N \__enumext_partopsep_v_skip
894     }
895     \skip_add:Nn \__enumext_multicols_below_v_skip
896     {
897       \skip_use:N \__enumext_partopsep_v_skip
898     }
899   }
900   \par\nopagebreak
901   \addvspace{ \__enumext_multicols_above_v_skip }
902 }


```

(End of definition for `__enumext_keyans_multi_set_vskip:` and `__enumext_keyans_multi_addvspace:`)

10.19 Adjustment of vertical spaces for minipage

When nesting a “list environment” within the `minipage` environment, the values of the “vertical spaces” are lost. Graphically it can be seen like in the figure 8.

Since we want to keep the “left” and “right” environments “aligned on top”, preserving the `\baselineskip` and keep the desired “spaces” (`\topsep` + `[\partopsep]`) it is necessary to “adjust” the “vertical spaces” for `minipage` environments.

Figure 8: Representation of the `minipage` spacing adjustment for a nested level.

Here there are several complications that we must circumvent, the `minipage` environment eliminates the “top” spaces, the `multicols` environment can be nested in the `minipage` environment, the “top” and “bottom” spaces are affected when `topsep=0pt` and to this is added the `\partopsep` parameter that comes into action according to whether \TeX is in *horizontal mode* or *vertical mode*. Depending on these cases, small adjustments must be made using `\vspace` and `\addvspace` to obtain the “desired vertical spacing”.

Again I must make clear that the implementation here is a “bit questionable”, but hunting the spaces (glue) produced by the `minipage` environment is quite complicated, even more if `multicols` it is nested. The setting of the values was more “trial and error” (aprox to `\strutbox`), using the help of the `lua-visual-debug`[12] package, again my attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

`__enumext_mini_env*` Creates a `__enumext_mini_env*` environment (custom version of `minipage`) setting the `\if@minipage` switch to “false” to allow spaces at the “above” of the environment, plus we will add `\vspace{0pt}` to maintain alignment on “top”. This environment will be used internally by the `mini-env` key, it is not documented in the user interface and is for internal use only.

```

903 \DeclareDocumentEnvironment{__enumext_mini_env*}{ m }
904 {
905     \__enumext_minipage:w [ t ] { #1 }
906     \legacy_if_gset_false:n { @minipage }
907     \vspace { 0pt }
908 }
909 { \__enumext_endminipage: }
```

(End of definition for `__enumext_mini_env*`.)

10.19.1 Adjustment of vertical spaces for minipage in enumext

`__enumext_mini_set_vskip:` The function `__enumext_mini_set_vskip:` will take care of determining the “adjust” spaces that we will apply “above” and “below” the `__enumext_mini_env*` environment in `enumext`.

We will set the default values taking into account that \TeX is in *horizontal mode*, then we will make the settings for the *vertical mode* in which `\partopsep` comes into play.

First determine if the `multicols` environment is active by comparing the value of the `\l__enumext_columns_X_int` variable handled by the `columns` key, according to this comparison we set the adjusted values for `\l__enumext_minipage_left_skip`, `\l__enumext_minipage_right_skip` and `\l__enumext_minipage_after_skip`.

```

910 \cs_new_protected:Nn \__enumext_mini_set_vskip:
911 {
912     \int_compare:nNnTF
913     { \int_use:c { \l__enumext_columns_ \__enumext_level: _int } } > { 1 }
914     {
```

If `multicols` environment is nested in `__enumext_mini_env*` environment, we will apply a correction factor to the vertical spaces taking into account the value of `\topsep` of the current level and the value of `\partopsep` of the previous level, if these are zero we will use `\strutbox` as the basis for the calculations.

```

915     \skip_if_eq:nnTF
916     { \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip } } { \c_zero_skip }
917     {
918         \skip_set:Nn \l__enumext_minipage_left_skip
919         {
920             -0.150\box_dp:N \strutbox
921         }
922         \skip_set:Nn \l__enumext_minipage_right_skip
923         {
924             0.695\box_dp:N \strutbox
925         }
926         \skip_set:Nn \l__enumext_minipage_after_skip
927         {
928             \box_dp:N \strutbox
929         }
930         \__enumext_zero_parsep:
931     }
```

```

932     {
933       \skip_set:Nn \l__enumext_minipage_left_skip
934       {
935         \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
936       }
937       \skip_set:Nn \l__enumext_minipage_right_skip
938       {
939         0.695\box_dp:N \strutbox
940       }
941       \skip_set:Nn \l__enumext_minipage_after_skip
942       {
943         1.85\box_dp:N \strutbox
944         + \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
945       }
946     }
947   }
948   {

```

If only `enumext` environment is nested in `__enumext_mini_env*` environment, we will apply a correction factor to the *vertical spaces* taking into account the value of `\topsep`, if this is zero we will use `\strutbox` as the basis for the calculations.

```

949   \skip_if_eq:nnTF
950   { \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip } } { \c_zero_skip }
951   {
952     \skip_set:Nn \l__enumext_minipage_left_skip
953     {
954       0.5\box_dp:N \strutbox
955       - \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
956     }
957     \skip_set:Nn \l__enumext_minipage_right_skip
958     {
959       \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
960     }
961     \skip_set:Nn \l__enumext_minipage_after_skip
962     {
963       1.6\box_dp:N \strutbox
964     }
965   }
966   {
967     \skip_set:Nn \l__enumext_minipage_left_skip
968     {
969       0.5875\box_dp:N \strutbox
970       - \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
971     }
972     \skip_set:Nn \l__enumext_minipage_right_skip
973     {
974       + \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
975       + \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
976     }
977     \skip_set:Nn \l__enumext_minipage_after_skip
978     {
979       0.325\box_dp:N \strutbox
980       + \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
981     }
982   }
983 }
984 }

```

(End of definition for `__enumext_mini_set_vskip:`)

`__enumext_zero_parsep:` The function `__enumext_zero_parsep:` “adjusted” the value of `\l__enumext_minipage_after_skip` detecting the value of `\parsep` from the previous level. This is necessary since `\parsep` from the previous level affects the *vertical spaces* and this is noticeable when using the `nosep` or `noitemsep` keys.

```

985 \cs_new_protected:Nn \__enumext_zero_parsep:
986 {
987   \int_case:nn { \l__enumext_level_int }
988   {
989     { 2 }{
990       \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip }
991       {
992         \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }

```

```

993         }
994     }
995     { 3 }{
996         \skip_if_eq:nnF { \l__enumext_parsep_ii_skip } { \c_zero_skip }
997         {
998             \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
999         }
1000     }
1001     { 4 }{
1002         \skip_if_eq:nnF { \l__enumext_parsep_iii_skip } { \c_zero_skip }
1003         {
1004             \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
1005         }
1006     }
1007 }
1008 }

```

(End of definition for `__enumext_zero_parsep:`.)

`__enumext_mini_addvspace:` The function `__enumext_mini_addvspace:` will apply the spaces set using `\addvspace` “above” the `__enumext_mini_env*` environment in `enumext`, taking into account whether \TeX is in *horizontal mode* or *vertical mode*. For the latter we will make some adjustments since the `\partopsep` parameter comes into play and this affects the *vertical spacing*.

```

1009 \cs_new_protected:Nn \__enumext_mini_addvspace:
1010 {
1011     \__enumext_mini_set_vskip:
1012     \mode_if_vertical:T
1013     {
1014         \skip_add:Nn \l__enumext_minipage_left_skip
1015         {
1016             \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1017         }
1018         \skip_add:Nn \l__enumext_minipage_after_skip
1019         {
1020             \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1021         }
1022     }
1023     \par\nopagebreak
1024     \addvspace { \l__enumext_minipage_left_skip }
1025 }

```

(End of definition for `__enumext_mini_addvspace:`.)

10.19.2 Adjustment of vertical spaces for minipage in keyans

`__enumext_keyans_mini_set_vskip:` The function `__enumext_keyans_mini_set_vskip:` will take care of determining the “adjusted” spaces that we will apply “above” and “below” the `__enumext_mini_env*` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

```

1026 \cs_new_protected:Nn \__enumext_keyans_mini_set_vskip:
1027 {
1028     \skip_zero_new:N \l__enumext_minipage_after_skip
1029     \skip_zero_new:N \l__enumext_minipage_left_skip
1030     \skip_zero_new:N \l__enumext_minipage_right_skip
1031     \int_compare:nNnTF { \l__enumext_columns_v_int } > { 1 }
1032     {
1033         \skip_if_eq:nnTF { \l__enumext_topsep_v_skip } { \c_zero_skip }
1034         {
1035             \skip_set:Nn \l__enumext_minipage_left_skip { -0.25\box_dp:N \strutbox }
1036             \skip_set:Nn \l__enumext_minipage_right_skip { 0.705\box_dp:N \strutbox }
1037             \skip_set:Nn \l__enumext_minipage_after_skip { \box_dp:N \strutbox }
1038             \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip }
1039             {
1040                 \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
1041             }
1042         }
1043     }
1044     \skip_set:Nn \l__enumext_minipage_left_skip
1045     {
1046         \skip_use:N \l__enumext_topsep_v_skip
1047     }
1048     \skip_set:Nn \l__enumext_minipage_right_skip

```

```

1049         {
1050             0.705\box_dp:N \strutbox
1051         }
1052         \skip_set:Nn \l__enumext_minipage_after_skip
1053         {
1054             1.85\box_dp:N \strutbox + \l__enumext_topsep_v_skip
1055         }
1056     }
1057 }
1058 {
1059     \skip_if_eq:nnTF { \l__enumext_topsep_v_skip } { \c_zero_skip }
1060     {
1061         \skip_set:Nn \l__enumext_minipage_left_skip
1062         {
1063             0.5\box_dp:N \strutbox
1064             + \l__enumext_partopsep_v_skip
1065         }
1066         \skip_set:Nn \l__enumext_minipage_right_skip
1067         {
1068             \l__enumext_partopsep_v_skip
1069         }
1070         \skip_set:Nn \l__enumext_minipage_after_skip { 1.6\box_dp:N \strutbox }
1071     }
1072     {
1073         \skip_set:Nn \l__enumext_minipage_left_skip
1074         {
1075             0.5875\box_dp:N \strutbox - \l__enumext_partopsep_v_skip
1076         }
1077         \skip_set:Nn \l__enumext_minipage_right_skip
1078         {
1079             \l__enumext_topsep_v_skip + \l__enumext_partopsep_v_skip
1080         }
1081         \skip_set:Nn \l__enumext_minipage_after_skip
1082         {
1083             0.325\box_dp:N \strutbox + \l__enumext_topsep_v_skip
1084         }
1085     }
1086 }
1087 }

```

(End of definition for `\l__enumext_keyans_mini_set_vskip:`)

`\l__enumext_keyans_mini_addvspace:`

The function `\l__enumext_keyans_mini_addvspace:` will apply the spaces set using `\addvspace` “above” the `\l__enumext_mini_env*` environment in `keyans`, taking into account whether \TeX is in *horizontal mode* or *vertical mode*. For the latter we will make some adjustments since the `\partopsep` parameter comes into play and this affects the *vertical spacing*. The implementation of this function is the same as the one used in `enumext`.

```

1088 \cs_new_protected:Nn \l__enumext_keyans_mini_addvspace:
1089 {
1090     \l__enumext_keyans_mini_set_vskip:
1091     \mode_if_vertical:T
1092     {
1093         \skip_add:Nn \l__enumext_minipage_left_skip
1094         {
1095             \l__enumext_partopsep_v_skip
1096         }
1097         \skip_add:Nn \l__enumext_minipage_after_skip
1098         {
1099             \l__enumext_partopsep_v_skip
1100         }
1101     }
1102     \par\nopagebreak
1103     \addvspace { \l__enumext_minipage_left_skip }
1104 }

```

(End of definition for `\l__enumext_keyans_mini_addvspace:`)

10.19.3 Adjustment of vertical spaces for minipage in `enumext*` and `keyans*`

`\l__enumext_mini_set_vskip_vii:`

`\l__enumext_mini_set_vskip_viii:`

The functions `\l__enumext_mini_set_vskip_vii:` and `\l__enumext_mini_set_vskip_viii:` will take care of determining the “adjusted” spaces that we will apply “above” and “below” the `\l__enumext_mini_env*` environment in `enumext*` and `keyans*`.

```

1105 \cs_new_protected:Nn \__enumext_mini_set_vskip_vii:
1106 {
1107   \skip_zero_new:N \l__enumext_minipage_left_skip
1108   \skip_gzero_new:N \g__enumext_minipage_right_skip
1109   \skip_gzero_new:N \g__enumext_minipage_after_skip
1110   \skip_if_eq:nnTF { \l__enumext_topsep_vii_skip } { \c_zero_skip }
1111   {
1112     \skip_set:Nn \l__enumext_minipage_left_skip { 0.5\box_dp:N \strutbox }
1113     \skip_gset:Nn \g__enumext_minipage_right_skip { 0.325\box_dp:N \strutbox }
1114   }
1115   {
1116     \skip_set:Nn \l__enumext_minipage_left_skip { 0.5875\box_dp:N \strutbox }
1117     \skip_gset:Nn \g__enumext_minipage_right_skip
1118       {
1119         \l__enumext_topsep_vii_skip
1120       }
1121     \skip_gset:Nn \g__enumext_minipage_after_skip
1122       {
1123         0.325\box_dp:N \strutbox + \l__enumext_topsep_vii_skip
1124       }
1125   }
1126 }
1127 \cs_new_protected:Nn \__enumext_mini_set_vskip_viii:
1128 {
1129   \skip_zero_new:N \l__enumext_minipage_after_skip
1130   \skip_zero_new:N \l__enumext_minipage_left_skip
1131   \skip_zero_new:N \l__enumext_minipage_right_skip
1132   \skip_if_eq:nnTF { \l__enumext_topsep_viii_skip } { \c_zero_skip }
1133   {
1134     \skip_set:Nn \l__enumext_minipage_left_skip
1135       {
1136         0.5\box_dp:N \strutbox
1137       }
1138     \skip_set:Nn \l__enumext_minipage_right_skip
1139       {
1140         \l__enumext_partopsep_viii_skip
1141       }
1142     \skip_set:Nn \l__enumext_minipage_after_skip
1143       {
1144         1.6\box_dp:N \strutbox
1145       }
1146   }
1147   {
1148     \skip_set:Nn \l__enumext_minipage_left_skip
1149       {
1150         0.5875\box_dp:N \strutbox
1151       }
1152     \skip_set:Nn \l__enumext_minipage_right_skip
1153       {
1154         \l__enumext_topsep_viii_skip
1155       }
1156     \skip_set:Nn \l__enumext_minipage_after_skip
1157       {
1158         0.325\box_dp:N \strutbox + \l__enumext_topsep_viii_skip
1159       }
1160   }
1161 }

```

(End of definition for `__enumext_mini_set_vskip_vii:` and `__enumext_mini_set_vskip_viii:`.)

`__enumext_mini_addvspace_vii:`
`__enumext_mini_addvspace_viii:`

The functions `__enumext_mini_addvspace_vii:` and `__enumext_mini_addvspace_viii:` will apply the vertical space “only above” the `__enumext_mini_env*` environment on the *left side* when the `miniright` key is active in the `enumext*` and `keyans*` environments. Here we will NOT take into account whether T_EX is in *horizontal mode* or *vertical mode*, since `\partopsep` is equal to `0pt` in both environments.

```

1162 \cs_new_protected:Nn \__enumext_mini_addvspace_vii:
1163 {
1164   \__enumext_mini_set_vskip_vii:
1165   \par\nopagebreak
1166   \addvspace { \l__enumext_minipage_left_skip }
1167 }

```



```

1168 \cs_new_protected:Nn \__enumext_mini_addvspace_viii:
1169 {
1170   \__enumext_mini_set_vskip_viii:
1171   \par\nopagebreak
1172   \addvspace { \__enumext_minipage_left_skip }
1173 }

```

(End of definition for __enumext_mini_addvspace_vii: and __enumext_mini_addvspace_viii:.)

10.19.4 The command \miniright

The command `\miniright` will close the `__enumext_mini_env*` environment on the “left side”, open the `__enumext_mini_env*` environment on the “right side” adding the *adjusted vertical space*. By default we will add `\centering` when starting the “right side” environment. The *starred version* ‘*’ inhibits the use of `\centering` command i.e. the usual L^AT_EX justification is maintained in the `__enumext_mini_env*` on the “right side”.

`\miniright` First we will perform some checks to prevent the command from being executed outside the `enumext` environment or from being executed inside the `keyanspic` environment, then we call the internal functions for the `enumext` and `keyans` environments.

```

1174 \NewDocumentCommand \miniright { s }
1175 {
1176   \int_compare:nNt { \__enumext_keyans_pic_level_int } = { 1 }
1177   {
1178     \msg_error:nnn { enumext } { wrong-miniright-place }
1179   }
1180   \int_compare:nNt { \__enumext_level_int } = { 0 }
1181   {
1182     \msg_error:nnn { enumext } { wrong-miniright-place }
1183   }
1184   \int_compare:nNtF { \__enumext_keyans_level_int } = { 1 }
1185   {
1186     \__enumext_keyans_mini_right_cmd:n {#1}
1187   }
1188   { \__enumext_mini_right_cmd:n {#1} }
1189 }

```

(End of definition for \miniright. This function is documented on page 9.)

`__enumext_mini_right_cmd:n` The function `__enumext_mini_right_cmd:n` takes as argument the *starred version* ‘*’ of the `\miniright` command in the `enumext` environment. We check if the `mini-env` key is active via the variable `__enumext_minipage_right_X_dim`, if so we close the `multicols` environment with the `__enumext__mini_env*` environment on the “left side”, then we open the `__enumext_mini_env*` environment on the “right side”, apply our adjusted “vertical spaces”, followed by adding the `\centering` command when the starred argument ‘*’ is not present and set zero `\g__enumext_minipage_stat_int`, otherwise we return an error.

```

1190 \cs_new_protected:Npn \__enumext_mini_right_cmd:n #1
1191 {
1192   \dim_compare:nNtF
1193   { \dim_use:c { \__enumext_minipage_right_ \__enumext_level: _dim } } > { \c_zero_dim }
1194   {
1195     \__enumext_multicols_stop:
1196     \end{__enumext_mini_env*}
1197     \hfill
1198     \begin{__enumext_mini_env*}
1199     { \dim_use:c { \__enumext_minipage_right_ \__enumext_level: _dim } }
1200     \par\addvspace { \__enumext_minipage_right_skip }
1201     \bool_if:nF {#1}
1202     {
1203       \centering
1204     }
1205     \int_gzero:N \g__enumext_minipage_stat_int
1206   }
1207   { \msg_error:nnn { enumext } { wrong-miniright-use } }
1208 }

```

(End of definition for __enumext_mini_right_cmd:n.)

_enumext_keyans_mini_right_cmd:n

The function _enumext_keyans_mini_right_cmd:n takes as argument the *starred version* ‘*’ of the _mini_right command in the keyans environment. The implementation of this function is the same as that of the _enumext_mini_right_cmd:n function of the enumext environment.

```

1209 \\cs_new_protected:Npn \\_enumext_keyans_mini_right_cmd:n #1
1210 {
1211   \\dim_compare:nNnTF { \\_enumext_minipage_right_v_dim } > { \\c_zero_dim }
1212   {
1213     \\_enumext_keyans_multicols_stop:
1214     \\end{\\_enumext_mini_env*}
1215     \\hfill
1216     \\begin{\\_enumext_mini_env*}{ \\_enumext_minipage_right_v_dim }
1217     \\par\\addvspace { \\_enumext_minipage_right_skip }
1218     \\bool_if:nF {#1}
1219     {
1220       \\centering
1221     }
1222     \\int_gzero:N \\g__enumext_minipage_stat_int
1223   }
1224   { \\msg_error:nnn { enumext } { wrong-miniright-use } }
1225 }

```

(End of definition for _enumext_keyans_mini_right_cmd:n.)

10.20 Setting above and below keys

While having controlled the *vertical spaces* within the enumext and keyans environments when using the columns or mini-env keys, sometimes the “vertical spaces above” or “vertical spaces below” the environments are not as expected and it is necessary to be able to apply a “fine correction” to these. As I have not been able to correct these *glitches*, the best option is to leave a couple of *keys* dedicated to this purpose, in this case it is best to use \\vspace or \\vspace* when convenient.

above Define above, above*, below and below* keys for enumext and keyans environments.

```

above*
below
below*
1226 \\cs_set_protected:Npn \\_enumext_tmp:nn #1 #2
1227 {
1228   \\keys_define:nn { enumext / #1 }
1229   {
1230     above .skip_set:c = { \\_enumext_vspace_above_#2_skip },
1231     above .value_required:n = true,
1232     above* .code:n = \\bool_set_true:c { \\_enumext_vspace_a_star_#2_bool }
1233     \\keys_set:nn { enumext / #1 } { above = {##1} },
1234     above* .value_required:n = true,
1235     below .skip_set:c = { \\_enumext_vspace_below_#2_skip },
1236     below .value_required:n = true,
1237     below* .code:n = \\bool_set_true:c { \\_enumext_vspace_b_star_#2_bool }
1238     \\keys_set:nn { enumext / #1 } { below = {##1} },
1239     below* .value_required:n = true,
1240   }
1241 }
1242 \\clist_map_inline:Nn \\c__enumext_all_envs_clist { \\_enumext_tmp:nn #1 }

```

(End of definition for above and others.)

10.20.1 Functions for above and below keys in enumext

_enumext_vspace_above:

The function _enumext_vspace_above: apply the *vertical space above* the enumext environment set by the above* and above keys.

```

1243 \\cs_new_protected:Nn \\_enumext_vspace_above:
1244 {
1245   \\skip_if_eq:nnF
1246   { \\skip_use:c { \\_enumext_vspace_above_ \\_enumext_level: _skip } } { \\c_zero_skip }
1247   {
1248     \\bool_if:cTF { \\_enumext_vspace_a_star_ \\_enumext_level: _bool }
1249     {
1250       \\vspace*{ \\skip_use:c { \\_enumext_vspace_above_ \\_enumext_level: _skip } }
1251     }
1252     {
1253       \\vspace { \\skip_use:c { \\_enumext_vspace_above_ \\_enumext_level: _skip } }
1254     }
1255   }
1256 }

```

(End of definition for _enumext_vspace_above:.)

`__enumext_vspace_below`: The function `__enumext_vspace_below`: apply the *vertical space below* the `enumext` environment set by the `below*` and `below` keys.

```

1257 \cs_new_protected:Nn \__enumext_vspace_below:
1258 {
1259   \skip_if_eq:nnF
1260     { \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } } { \c_zero_skip }
1261   {
1262     \bool_if:cTF { \__enumext_vspace_b_star_ \__enumext_level: _bool }
1263     {
1264       \vspace*{ \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } }
1265     }
1266     {
1267       \vspace { \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } }
1268     }
1269   }
1270 }

```

(End of definition for `__enumext_vspace_below`.)

10.20.2 Functions for above and below keys in keyans

`__enumext_vspace_above_v`: The function `__enumext_vspace_above_v`: apply the *vertical space above* the `keyans` environment set by the `above` and `above*` keys.

```

1271 \cs_new_protected:Nn \__enumext_vspace_above_v:
1272 {
1273   \skip_if_eq:nnF { \l__enumext_vspace_above_v_skip } { \c_zero_skip }
1274   {
1275     \bool_if:NTF \l__enumext_vspace_a_star_v_bool
1276     {
1277       \vspace*{ \l__enumext_vspace_above_v_skip }
1278     }
1279     { \vspace { \l__enumext_vspace_above_v_skip } }
1280   }
1281 }

```

(End of definition for `__enumext_vspace_above_v`.)

`__enumext_vspace_below_v`: The function `__enumext_vspace_below_v`: apply the *vertical space below* the `keyans` environment set by the `below*` and `below` keys.

```

1282 \cs_new_protected:Nn \__enumext_vspace_below_v:
1283 {
1284   \skip_if_eq:nnF { \l__enumext_vspace_below_v_skip } { \c_zero_skip }
1285   {
1286     \bool_if:NTF \l__enumext_vspace_b_star_v_bool
1287     {
1288       \vspace*{ \l__enumext_vspace_below_v_skip }
1289     }
1290     { \vspace { \l__enumext_vspace_below_v_skip } }
1291   }
1292 }

```

(End of definition for `__enumext_vspace_below_v`.)

10.20.3 Functions for above and below keys in enumext* keyans*

`__enumext_vspace_above_vii`: The functions `__enumext_vspace_above_vii`: and `__enumext_vspace_above_viii`: apply the *vertical space above* the `enumext*` and `keyans*` environments set by the `above` and `above*` keys.

`__enumext_vspace_above_viii`:

```

1293 \cs_new_protected:Nn \__enumext_vspace_above_vii:
1294 {
1295   \skip_if_eq:nnF { \l__enumext_vspace_above_vii_skip } { \c_zero_skip }
1296   {
1297     \bool_if:NTF \l__enumext_vspace_a_star_vii_bool
1298     {
1299       \vspace*{ \l__enumext_vspace_above_vii_skip }
1300     }
1301     { \vspace { \l__enumext_vspace_above_vii_skip } }
1302   }
1303 }
1304 \cs_new_protected:Nn \__enumext_vspace_above_viii:
1305 {
1306   \skip_if_eq:nnF { \l__enumext_vspace_above_viii_skip } { \c_zero_skip }
1307   {

```

```

1308         \bool_if:NTF \l__enumext_vspace_a_star_viii_bool
1309         {
1310             \vspace*{ \l__enumext_vspace_above_viii_skip }
1311         }
1312         { \vspace { \l__enumext_vspace_above_viii_skip } }
1313     }
1314 }

```

(End of definition for \l__enumext_vspace_above_vii: and \l__enumext_vspace_above_viii:.)

The functions \l__enumext_vspace_below_vii: and \l__enumext_vspace_below_viii: apply the *vertical space below* the `enumext*` and `keyans*` environments set by the `below*` and `below` keys.

```

1315 \cs_new_protected:Nn \l__enumext_vspace_below_vii:
1316 {
1317     \skip_if_eq:nnF { \l__enumext_vspace_below_vii_skip } { \c_zero_skip }
1318     {
1319         \bool_if:NTF \l__enumext_vspace_b_star_vii_bool
1320         {
1321             \vspace*{ \l__enumext_vspace_below_vii_skip }
1322         }
1323         { \vspace { \l__enumext_vspace_below_vii_skip } }
1324     }
1325 }
1326 \cs_new_protected:Nn \l__enumext_vspace_below_viii:
1327 {
1328     \skip_if_eq:nnF { \l__enumext_vspace_below_viii_skip } { \c_zero_skip }
1329     {
1330         \bool_if:NTF \l__enumext_vspace_b_star_viii_bool
1331         {
1332             \vspace*{ \l__enumext_vspace_below_viii_skip }
1333         }
1334         { \vspace { \l__enumext_vspace_below_viii_skip } }
1335     }
1336 }

```

(End of definition for \l__enumext_vspace_below_vii: and \l__enumext_vspace_below_viii:.)

10.21 Setting save-ans and resume keys

The key `save-ans` is directly associated with the key `resume`, this will activate the entire “storage system” in the `enumext` package.

We define the keys `save-ans` and `resume` only for the “first level” of `enumext` and `enumext*`.

```

save-ans \keys_define:nn { enumext / level-1 }
resume {
resume*   save-ans .code:n = \l__enumext_storing_set:n {#1},
          save-ans .value_required:n = true,
          resume .code:n = \l__enumext_resume_counter:,
          resume .value_forbidden:n = true,
          resume* .code:n = \l__enumext_resume_counter_star:,
          resume* .value_forbidden:n = true,
1345      }
1346 \keys_define:nn { enumext / enumext* }
1347 {
1348     save-ans .code:n = \l__enumext_storing_set:n {#1},
1349     save-ans .value_required:n = true,
1350     resume .code:n = \l__enumext_resume_counter_vii:,
1351     resume .value_forbidden:n = true,
1352 }

```

(End of definition for `save-ans`, `resume`, and `resume*`.)

The function `\l__enumext_storing_set:n` executed by the `save-ans` key sets the parameters for the operation of `\anskey`, `keyans` and `keyanspic`. The variable `\l__enumext_store_name_tl` will have the “store name” with which the *⟨sequence⟩* and *⟨prop list⟩* will be created, if it does not exist it will create it globally.

The boolean var `\l__enumext_store_active_bool` will be set to true activating the entire internal *storage mechanism*, then the integer variable for the `resume` key will be created (if not exist), finally the function `\l__enumext_check_ans_int:n` will be called to activate the internal mechanism for checking the answers if the boolean variable `\l__enumext_check_ans_bool` set by `check-ans` key are active.

```

1353 \cs_new_protected:Npn \__enumext_storing_set:n #1
1354 {
1355   \tl_set:Nx \l__enumext_store_name_tl {#1}
1356   \prop_if_exist:cF { g__enumext_ \l__enumext_store_name_tl _prop }
1357   {
1358     \prop_new:c { g__enumext_ \l__enumext_store_name_tl _prop }
1359   }
1360   \seq_if_exist:cF { g__enumext_ \l__enumext_store_name_tl _seq }
1361   {
1362     \seq_new:c { g__enumext_ \l__enumext_store_name_tl _seq }
1363   }
1364   \bool_set_true:N \l__enumext_store_active_bool
1365   \bool_set_true:N \l__enumext_store_ans_bool
1366   \int_if_exist:cF { g__enumext_resume_#1_int }
1367   {
1368     \int_new:c { g__enumext_resume_#1_int }
1369   }
1370 }

```

(End of definition for __enumext_storing_set:n.)

__enumext_resume_counter: The functions __enumext_resume_counter: and __enumext_resume_counter_vii: used by
 __enumext_resume_counter_vii: resume key in enumext and enumext*. If save-ans key present then set the start value from integer created by __enumext_storing_set:n.

```

1371 \cs_new_protected:Nn \__enumext_resume_counter:
1372 {
1373   \bool_if:NT \l__enumext_store_active_bool
1374   {
1375     \int_gset:Nn \g__enumext_resume_int
1376     {
1377       \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int }
1378     }
1379   }
1380   \bool_set_true:N \l__enumext_resume_bool
1381 }
1382 \cs_new_protected:Nn \__enumext_resume_counter_vii:
1383 {
1384   \bool_if:NT \l__enumext_store_active_bool
1385   {
1386     \int_gset:Nn \g__enumext_resume_int
1387     {
1388       \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int }
1389     }
1390   }
1391   \bool_set_true:N \l__enumext_resume_vii_bool
1392 }

```

(End of definition for __enumext_resume_counter: and __enumext_resume_counter_vii:.)

10.22 The check answer mechanism

The mechanism for checking that all questions are answered follows this logic:

If the line begins with \item or \item* and does NOT open a nested environment, each \item or \item* must contain a single execution of the \anskey command, i.e. the counter of the executions of the \anskey command must be equal to the counter associated with the sum of executions of \item and \item*.

If the line begins with \item or \item* and opens a nested environment each \item or \item* in the nested environment must have a single execution of the \anskey command and the counter associated to the sum of \item and \item* executions must decrementing by “one” to maintain equality.

In order for the mechanism for the check-answer to work (not counting keyans, keyans* and keyanspic) we need:

1. We must keep track of the total number of \item and \item* (enumerated) that appear within the environment including the nested levels.
2. We must keep track of the total number of \item and \item* (enumerated) that appear per level of nesting.
3. Keeping track of the number of times the environment nests.

The integer variable associated to the sum of each `\item` and `\item*` in the environment `\g__enumext_count_item_number_int` must match the integer variable `\g__enumext_count_item_anskey_int` associated to the execution of the command `\anskey`. We analyze the cases:

- If the list only has one level the number of `\item` + `\item*` = `\anskey`
- If the list has *nested levels*, for each level of nesting we need to decrementing by one (for the `\item` or `\item*` that opens the nest) so that the account remains the same.

With `keyans`, `keyans*` and `keyanspic` it is enough to increase in one the integer of `\anskey`. The integers created must be global if they are not lost in the interior levels of nesting and to execute the test we will use a “hook” function after closing the first level of the environment.

10.22.1 Setting check-ans key

Now we define the keys `check-ans` and `no-store` for all levels of `enumext` and `enumext*` environments.

```
check-ans 1393 \cs_set_protected:Npn \__enumext_tmp:n #1
no-store 1394 {
1395   \keys_define:nn { enumext / #1 }
1396   {
1397     check-ans .bool_set:N = \__enumext_check_ans_bool,
1398     check-ans .initial:n = false,
1399     no-store .code:n = {
1400       \bool_set_false:N \__enumext_store_ans_bool
1401       \bool_set_false:N \__enumext_check_ans_bool
1402     },
1403     no-store .value_forbidden:n = true,
1404   }
1405 }
1406 \clist_map_inline:nn
1407 {
1408   level-1, level-2, level-3, level-4, enumext*
1409 }
1410 { \__enumext_tmp:n {#1} }
```

(End of definition for `check-ans` and `no-store`.)

10.22.2 Set-up check answer mechanism

`__enumext_check_ans_set:` The function `__enumext_check_ans_set:` will adjust the value of the variable `\g__enumext_count_item_number_int` by decrementing its value by one each time you open a nested level `enumext` environment.

```
1411 \cs_new_protected:Nn \__enumext_check_ans_set:
1412 {
1413   \int_case:nn { \__enumext_level_int }
1414   {
1415     { 1 }{
1416       \bool_lazy_all:nT
1417       {
1418         { \bool_if_p:N \g__enumext_starred_bool }
1419         { \int_compare_p:nNn { \__enumext_level_h_int } = { \c_one_int } }
1420       }
1421       {
1422         \int_gdecr:N \g__enumext_count_item_number_int
1423         \typeout{ENUMEXT ~ STANDAR ~ NEEEEEEEEEEEEESTED}
1424       }
1425     }
1426     { 2 }{
1427       \int_gdecr:N \g__enumext_count_item_number_int
1428     }
1429     { 3 }{
1430       \int_gdecr:N \g__enumext_count_item_number_int
1431     }
1432     { 4 }{
1433       \int_gdecr:N \g__enumext_count_item_number_int
1434     }
1435   }
1436   \int_case:nn { \__enumext_level_h_int }
1437   {
1438     { 1 }{
1439       \bool_if:NT \g__enumext_standar_bool
1440       {
1441         \int_gdecr:N \g__enumext_count_item_number_int
1442         \typeout{ENUMEXT ~ STARRED ~ NEEEEEEEEEEEEESTED}
```

```

1443         }
1444     }
1445 }
1446 }

```

(End of definition for `__enumext_check_ans_set:`.)

`__enumext_check_ans_exec:` The function `__enumext_check_ans_exec:` will count the number of times the `\item` and `\item*` commands appears per level within the `enumext` environment. The boolean variable `\l__enumext_store_ans_bool` controlled by the `no-store` key will increment the integer variable of the level counter by 1 to preserve the equality that we will use in the final comparison of the process.

```

1447 \cs_new_protected:Nn \__enumext_check_ans_exec:
1448 {
1449     \bool_if:NT \l__enumext_check_ans_bool
1450     {
1451         \__enumext_check_ans_set:
1452     }
1453 }

```

(End of definition for `__enumext_check_ans_exec:`.)

`__enumext_check_ans_show:` The function `__enumext_check_ans_show:` compares all executions of `\item` and `\item*` with the executions of `\anskey`. After the function is executed, we set the integer variables to zero.

```

1454 \cs_new_protected:Nn \__enumext_check_ans_show:
1455 {
1456     \int_compare:nNnTF
1457     { \g__enumext_count_item_number_int } = { \g__enumext_count_item_anskey_int }
1458     {
1459         \msg_term:nnV { enumext } { items-same-answer } \g__enumext_store_name_tl
1460     }
1461     {
1462         \msg_warning:nnV { enumext } { item-different-answer } \g__enumext_store_name_tl
1463     }
1464     \int_gzero:N \g__enumext_count_item_number_int
1465     \int_gzero:N \g__enumext_count_item_anskey_int
1466 }

```

(End of definition for `__enumext_check_ans_show:`.)

10.23 Keys and functions associated with storage

We add the keys `wrap-ans`, `mark-ans`, `mark-pos`, `show-ans`, `show-pos`, `mark-ref` and `store-ref` related to the “storage system” and internal mechanism of “label and ref” only at the first level of `enumext` and `enumext*`.

```

1467 \cs_set_protected:Npn \__enumext_tmp:n #1
1468 {
1469     \keys_define:nn { enumext / #1 }
1470     {
1471         wrap-ans .cs_set_protected:Np = \__enumext_anskey_wrapper:n #1,
1472         wrap-ans .initial:n = \fbox{##1},
1473         wrap-ans .value_required:n = true,
1474         mark-ans .code:n = \tl_set:Nn \l__enumext_mark_answer_sym_tl {##1},
1475         mark-ans .initial:n = \textasteriskcentered,
1476         mark-ans .value_required:n = true,
1477         mark-pos .choice:,
1478         mark-pos / left .code:n = \str_set:Nn \l__enumext_mark_position_str { l },
1479         mark-pos / right .code:n = \str_set:Nn \l__enumext_mark_position_str { r },
1480         mark-pos .initial:n = right,
1481         mark-pos .value_required:n = true,
1482         show-ans .code:n = \bool_set_true:N \l__enumext_show_answer_bool
1483                     \bool_set_false:N \l__enumext_show_position_bool,
1484         show-ans .value_forbidden:n = true,
1485         show-pos .code:n = \bool_set_true:N \l__enumext_show_position_bool
1486                     \bool_set_false:N \l__enumext_show_answer_bool,
1487         show-pos .value_forbidden:n = true,
1488         mark-ref .code:n = \tl_set:Nn \l__enumext_mark_ref_sym_tl {##1},
1489         mark-ref .initial:n = \textasteriskcentered,
1490         mark-ref .value_required:n = true,
1491         store-ref .bool_set:N = \l__enumext_store_ref_key_bool,
1492         store-ref .initial:n = false,
1493     }

```



```

1494 }
1495 \clist_map_inline:nn { level-1, enumext* } { \__enumext_tmp:n {#1} }

```

(End of definition for wrap-ans and others.)

mark-pos For the `keyans` and `keyans*` environments we will only add the keys `mark-pos`, `show-ans` and `show-pos`.

```

1496 \cs_set_protected:Npn \__enumext_tmp:n #1
1497 {
1498   \keys_define:nn { enumext / #1 }
1499   {
1500     mark-pos .choice:,
1501     mark-pos / left .code:n = \str_set:Nn \__enumext_mark_position_str { l },
1502     mark-pos / right .code:n = \str_set:Nn \__enumext_mark_position_str { r },
1503     mark-pos .initial:n = right,
1504     mark-pos .value_required:n = true,
1505     show-ans .code:n = \bool_set_true:N \__enumext_show_answer_bool
1506                      \bool_set_false:N \__enumext_show_position_bool,
1507     show-ans .value_forbidden:n = true,
1508     show-pos .code:n = \bool_set_true:N \__enumext_show_position_bool
1509                      \bool_set_false:N \__enumext_show_answer_bool,
1510     show-pos .value_forbidden:n = true,
1511   }
1512 }
1513 \clist_map_inline:nn { keyans, keyans* } { \__enumext_tmp:n {#1} }

```

(End of definition for mark-pos and show-ans.)

columns* For the `enumext` and `enumext*` environments we will only add the keys `columns*` and `columns-sep*`.
columns-sep* The values set by these keys will be passed as optional arguments to the “inner levels” of the `enumext` and `enumext*` environments via the `__enumext_store_level_open:` function used by the “storage system” to preserve the structure and then used by the `\printkeyans` command.

```

1514 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
1515 {
1516   \keys_define:nn { enumext / #1 }
1517   {
1518     columns* .code:n = \bool_set_true:c { \__enumext_store_columns_#2_bool }
1519                      \int_set:cn { \__enumext_store_columns_#2_int } {##1}
1520                      \tl_put_right:ce { \__enumext_store_opt_#2_tl }
1521                      {
1522                        columns = \exp_not:v { \__enumext_store_columns_#2_int },
1523                      },,
1524     columns* .value_required:n = true,
1525     columns-sep* .code:n = \bool_set_true:c { \__enumext_store_columns_sep_#2_bool }
1526                      \dim_set:cn { \__enumext_store_columns_sep_#2_dim } {##1}
1527                      \tl_put_right:ce { \__enumext_store_opt_#2_tl }
1528                      {
1529                        columns-sep = \exp_not:v { \__enumext_store_columns_sep_#2_dim },
1530                      },
1531     columns-sep* .value_required:n = true,
1532   }
1533 }
1534 \clist_map_inline:nn
1535 {
1536   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {enumext*}{vii}
1537 }
1538 { \__enumext_tmp:nn #1 }

```

(End of definition for columns* and columns-sep*.)

10.23.1 Function for storing content in prop list

`__enumext_store_addto_prop:n` The function `__enumext_store_addto_prop:n` stores the content in $\langle prop list \rangle$ defined by `save-ans` key. The “stored content” is retrieved by means of the `\getkeyans` command.

The form in which the content is “stored” in the $\langle prop list \rangle$ is $\{\langle position \rangle\}\{\langle content \rangle\}$. This function is used by `\anskey` in `enumext` and `enumext*` environments, `\item*` in `keyans` and `keyans*` environments and `\anspic` in `keyanspic` environment.

```

1539 \cs_generate_variant:Nn \prop_gput_if_not_in:Nnn { cen }
1540 \cs_new_protected:Npn \__enumext_store_addto_prop:n #1
1541 {
1542   \prop_gput_if_not_in:cen { g__enumext_ \__enumext_store_name_tl _prop }

```

```

1543     {
1544         \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } + 1 }
1545     }
1546     { #1 }
1547 }
1548 \cs_generate_variant:Nn \__enumext_store_addto_prop:n { V }

```

(End of definition for `__enumext_store_addto_prop:n`.)

10.23.2 Function for storing content in sequence

The function `__enumext_store_addto_seq:n` stores the content in *sequence* defined by `save-ans` key. This function is used by `\anskey` in `enumext`, `\item*` in `keyans` and `\anspic` in `keyanspic`.

The form in which the content is stored in *sequence* is in a internal `enumext` or `enumext*` environments with the *same structure* in which the command was executed.

The “*stored content*” is retrieved by means of the `\printkeyans` command.

```

1549 \cs_new_protected:Npn \__enumext_store_addto_seq:n #1
1550 {
1551     \seq_gput_right:cn { g__enumext_ \l__enumext_store_name_tl _seq } { #1 }
1552 }
1553 \cs_generate_variant:Nn \__enumext_store_addto_seq:n { v, V }

```

(End of definition for `__enumext_store_addto_seq:n`.)

10.23.3 Functions for storing the list structure in the sequence

The memorization structure of the list is handled by the functions `__enumext_store_level_open:` and `__enumext_store_level_close:` which are executed per level within the `enumext` environment. As this structure will be stored in the sequence set by the `save-ans` key, we will not be able to modify it locally, so it is better to take only two copies of the values set by the `columns` and `columns-sep` keys if they are present when changing levels within the `enumext` environment when executing `\anskey`. We will store these values in the variable `\l__enumext_store_columns_X_tl` if they are different from `0` and `0pt` and pass them as an optional argument to the environment stored in the sequence `enumext`.

```

1554 \cs_new_protected:Nn \__enumext_store_level_open:
1555 {
1556     \bool_if:NT \l__enumext_store_ans_bool
1557     {
1558         \tl_if_empty:cTF { l__enumext_store_opt_ \__enumext_level: _tl }
1559         {
1560             \__enumext_store_addto_seq:n
1561             {
1562                 \item \begin{enumext}
1563             }
1564         }
1565         {
1566             \tl_put_left:cn { l__enumext_store_opt_ \__enumext_level: _tl }
1567             {
1568                 \item \begin{enumext} [
1569             }
1570             \tl_put_right:cn { l__enumext_store_opt_ \__enumext_level: _tl }
1571             {
1572                 ]
1573             }
1574             \__enumext_store_addto_seq:v { l__enumext_store_opt_ \__enumext_level: _tl }
1575         }
1576     }
1577 }
1578 \cs_new_protected:Nn \__enumext_store_level_close:
1579 {
1580     \bool_if:NT \l__enumext_store_ans_bool
1581     {
1582         \__enumext_store_addto_seq:n { \end{enumext} }
1583     }
1584 }

```

(End of definition for `__enumext_store_level_open:` and `__enumext_store_level_close:`.)

```

\__enumext_store_level_open_vii:
\__enumext_store_level_close_vii:

```

When nesting the `enumext*` environment in `enumext` starting right after `\item` (without material between them) there is a problem with the alignment of the labels with the baseline between the two environments. One way to get around this problem is to place `\mode_leave_vertical:` and then apply `\vspace` taking into account `\baselineskip`, the value of `\parsep` of the current level of `enumext` and the value of `\topsep` of the `enumext*` environment.

```

1585 \cs_new_protected:Nn \__enumext_store_level_open_vii:
1586 {
1587   \bool_if:NT \l__enumext_store_ans_bool
1588   {
1589     \tl_if_empty:NTF \l__enumext_store_opt_vii_tl
1590     {
1591       \__enumext_store_addto_seq:n
1592       {
1593         \item \mode_leave_vertical:
1594         \vspace { -\skip_eval:n { \baselineskip + \parsep } }
1595         \begin{enumext*}[before={\setlength{\topsep}{\opt}},]
1596       }
1597     }
1598   }
1599   \tl_put_left:Nn \l__enumext_store_opt_vii_tl
1600   {
1601     \item \mode_leave_vertical:
1602     \vspace { -\skip_eval:n { \baselineskip + \parsep } }
1603     \begin{enumext*}[before={\setlength{\topsep}{\opt}},
1604   ]
1605   \tl_put_right:Nn \l__enumext_store_opt_vii_tl
1606   {
1607   ]
1608   }
1609   \__enumext_store_addto_seq:V \l__enumext_store_opt_vii_tl
1610 }
1611 }
1612 }
1613 \cs_new_protected:Nn \__enumext_store_level_close_vii:
1614 {
1615   \bool_if:NT \l__enumext_store_ans_bool
1616   {
1617     \__enumext_store_addto_seq:n { \end{enumext*} }
1618   }
1619 }

```

(End of definition for __enumext_store_level_open_vii: and __enumext_store_level_close_vii:.)

10.23.4 Function for show marks and position

```

\__enumext_print_keyans_box:NN
\__enumext_print_keyans_box:cc

```

The function `__enumext_print_keyans_box:NN` print a box in the left margin with `\l__enumext_mark_answer_sym_tl` used by the `wrap-ans`, `show-ans` and `show-pos` keys. The function takes two arguments:

#1: `\l__enumext_labelwidth_X_dim`
 #2: `\l__enumext_labelsep_X_dim`

```

1620 \cs_new_protected:Nn \__enumext_print_keyans_box:NN
1621 {
1622   \mode_leave_vertical:
1623   \skip_horizontal:n { -\dim_use:N #2 }
1624   \makebox[\opt][ r ]
1625   {
1626     \makebox[ \dim_use:N #1 ][ \l__enumext_mark_position_str ]
1627     {
1628       \tl_use:N \l__enumext_mark_answer_sym_tl
1629     }
1630   }
1631   \skip_horizontal:n { \dim_use:N #2 }
1632 }
1633 \cs_generate_variant:Nn \__enumext_print_keyans_box:NN { cc }

```

(End of definition for __enumext_print_keyans_box:NN.)

10.24 The command \anskey and internal label and ref

Since we will be “*storing content*” in a list environment within *⟨sequences⟩* and can (more or less) manage the options passed to each level, it is necessary that we have a little more control over `\item` when storing. The `\anskey` command will cover this point and give it very similar behaviour to that of `\item` in the `enumext` and `enumext*` environments.

`\anskey` We want the command to be executed as follows: `\anskey(⟨number⟩)*[⟨key = val⟩]{⟨content⟩}` so first we’ll add the keys `item-sym*`, `item-pos*` and `store-brk`.

```

1634 \keys_define:nn { enumext / anskey }
1635 {
1636   item-sym* .tl_set:N = \l__enumext_store_item_symbol_tl,
1637   item-sym* .value_required:n = true,
1638   item-pos* .dim_set:N = \l__enumext_store_item_symbol_sep_dim,
1639   item-pos* .value_required:n = true,
1640   store-brk .bool_set:N = \l__enumext_store_columns_break_bool,
1641   store-brk .default:n = true,
1642   store-brk .value_forbidden:n = true,
1643 }

```

This command `\anskey` will only be present when using the `save-ans` key in `enumext` and `enumext*` environments, otherwise it will return an error. If the `check-ans` key is active, increment `\g__enumext_count_item_with_ans_int`, then call internal function `__enumext_store_anskey_code:nnnn` will “store content” in the `<sequence>` and in the `<prop list>`.

```

1644 \NewDocumentCommand \anskey { d() s o +m }
1645 {
1646   \bool_if:NF \l__enumext_store_active_bool
1647   {
1648     \msg_error:nnnn { enumext } { anskey-wrong-place } { anskey } { enumext }
1649   }
1650   \int_compare:nNt { \l__enumext_keyans_level_int } = { 1 }
1651   {
1652     \msg_error:nnnn { enumext } { command-wrong-place } { anskey } { keyans }
1653   }
1654   \int_compare:nNt { \l__enumext_keyans_pic_level_int } = { 1 }
1655   {
1656     \msg_error:nnnn { enumext } { command-wrong-place } { anskey } { keyanspic }
1657   }
1658   \group_begin:
1659     \bool_if:NT \l__enumext_store_ans_bool
1660     {
1661       \bool_if:NT \l__enumext_check_ans_bool
1662       {
1663         \int_gincr:N \g__enumext_count_item_anskey_int
1664       }
1665       \__enumext_store_anskey_code:nnnn {#1} {#2} {#3} {#4}
1666     }
1667   \group_end:
1668 }

```

(End of definition for `\anskey`. This function is documented on page 10.)

`__enumext_store_anskey_code:nnnn`

The internal function `__enumext_store_anskey_code:nnnn` first we pass the command `<argument>` to the `<prop list>`, then checks the state of the variable `\l__enumext_store_ref_key_bool` handled by the `store-ref` key and will call the function `__enumext_store_internal_ref:` for the internal “label and ref” system. Followed by this if the `show-ans` or `show-pos` keys are active we will show the “wrapped” `<argument>` passed to the command.

```

1669 \cs_new_protected:Npn \__enumext_store_anskey_code:nnnn #1 #2 #3 #4
1670 {
1671   \__enumext_store_addto_prop:n {#4}
1672   \bool_if:NT \l__enumext_store_ref_key_bool
1673   {
1674     \__enumext_store_internal_ref:
1675   }
1676   \__enumext_store_anskey_show_left:n { #4 }

```

Now we start processing the optional arguments passed to the command to build our `\item` in the variable `\l__enumext_store_anskey_arg_tl` which we will “store” in the `<sequence>`. First we clear the variable `\l__enumext_store_anskey_arg_tl` and process `[<key = val>]`, if the `store-brk` key is present and the command is running under `enumext` (not in the starred version) we will add `\columnbreak` and then `\item`.

```

1677   \tl_clear:N \l__enumext_store_anskey_arg_tl
1678   \tl_if_novalue:nF {#3}
1679   {
1680     \keys_set:nn { enumext / anskey } {#3}
1681   }
1682   \bool_lazy_and:nnT
1683   { \bool_if_p:N \l__enumext_store_columns_break_bool }
1684   { \bool_not_p:n { \l__enumext_starred_bool } }
1685   {

```

```

1686     \tl_put_left:Nn \l__enumext_store_anskey_arg_tl { \columnbreak }
1687   }
1688   \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { \item }

```

Now we will check the $\langle number \rangle$ argument and add it to `\l__enumext_store_anskey_arg_tl` if the command is running under `enumext*` (starred version).

```

1689   \tl_if_novalue:nF {#1}
1690   {
1691     \int_set:Nn \l__enumext_store_columns_join_int {#1}
1692     \bool_if:NT \l__enumext_starred_bool
1693     {
1694       \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
1695       {
1696         ( \exp_not:V \l__enumext_store_columns_join_int )
1697       }
1698     }
1699   }

```

And now we will review the starred argument `*` together with the keys `item-sym*` and `item-pos*` and pass them to `\l__enumext_store_anskey_arg_tl`.

```

1700   \bool_if:nTF {#2}
1701   {
1702     \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { * }
1703     \tl_if_empty:NF \l__enumext_store_item_symbol_tl
1704     {
1705       \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
1706       {
1707         [ \exp_not:V \l__enumext_store_item_symbol_tl ]
1708       }
1709     }
1710     \dim_compare:nT
1711     {
1712       \l__enumext_store_item_symbol_sep_dim != \c_zero_dim
1713     }
1714     {
1715       \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
1716       {
1717         [ \exp_not:V \l__enumext_store_item_symbol_sep_dim ]
1718       }
1719     }
1720     \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#4}
1721   }
1722   {
1723     \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#4}
1724   }

```

Finally we check if the `store-ref` key is active along with the `hyperref` package load, if both conditions are met, it will create the `\hyperlink` and then store in $\langle sequence \rangle$.

```

1725   \bool_lazy_and:nnT
1726   { \bool_if_p:N \l__enumext_store_ref_key_bool }
1727   { \bool_if_p:N \l__enumext_hyperref_bool }
1728   {
1729     \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
1730     {
1731       \hfill \exp_not:N \hyperlink { \exp_not:V \l__enumext_newlabel_arg_one_tl }
1732       { \exp_not:V \l__enumext_mark_ref_sym_tl }
1733     }
1734   }
1735   \__enumext_store_addto_seq:V \l__enumext_store_anskey_arg_tl
1736 }

```

(End of definition for `__enumext_store_anskey_code:nnnn`.)

`__enumext_store_internal_ref:`

The function `__enumext_store_internal_ref:` handles the internal “*label and ref*” system used by the `store-ref` and `mark-ref` keys for `\anskey` will allow to execute `\ref{\langle store name : position \rangle}` and will return `1.(a).i.A`.

First we will remove the dots “.” from the current $\langle labels \rangle$, we do not want to get double dots in our references, then we will place this in the variable `\l__enumext_newlabel_arg_two_tl`.

```

1737 \cs_new_protected:Nn \__enumext_store_internal_ref:
1738 {
1739   \cs_set_protected:Npn \__enumext_tmp:n ##1
1740   {

```

```

1741     \tl_set_eq:cc { l__enumext_label_copy_##1_tl } { l__enumext_label_##1_tl }
1742     \tl_reverse:c { l__enumext_label_copy_##1_tl }
1743     \tl_remove_once:cn { l__enumext_label_copy_##1_tl } { . }
1744     \tl_reverse:c { l__enumext_label_copy_##1_tl }
1745   }
1746   \clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {##1} }
1747   \cs_set:Npn \__enumext_tmp:n ##1
1748     { . \tl_use:c { l__enumext_label_copy_ \int_to_roman:n {##1} _tl } }

```

Here we need to analyse the cases where the environment is started with `enumext*` and if `\anskey` is running alone in it or if it is running in a nested `enumext` environment within the starting environment.

```

1749   \bool_lazy_all:nT
1750   {
1751     { \bool_if_p:N \g__enumext_starred_bool }
1752     { \int_compare_p:nNn { \l__enumext_level_int } = { \c_zero_int } }
1753   }
1754   {
1755     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
1756       { \tl_use:N \l__enumext_label_copy_vii_tl }
1757   }
1758   \bool_lazy_all:nT
1759   {
1760     { \bool_if_p:N \l__enumext_standar_bool }
1761     { \bool_if_p:N \g__enumext_starred_bool }
1762     { \int_compare_p:nNn { \l__enumext_level_int } > { \c_zero_int } }
1763   }
1764   {
1765     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
1766       {
1767         \tl_use:N \l__enumext_label_copy_vii_tl
1768         \int_step_function:nnN { 1 } { \l__enumext_level_int } \__enumext_tmp:n
1769       }
1770   }

```

If started with `enumext` and if `\anskey` is running alone in it or if it is running in a nested `enumext*` environment within the starting environment.

```

1771   \bool_lazy_all:nT
1772   {
1773     { \bool_if_p:N \l__enumext_standar_bool }
1774     { \int_compare_p:nNn { \l__enumext_level_int } > { \c_zero_int } }
1775     { \int_compare_p:nNn { \l__enumext_level_h_int } = { \c_zero_int } }
1776     { \bool_not_p:n { \l__enumext_starred_bool } }
1777   }
1778   {
1779     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
1780       {
1781         \tl_use:N \l__enumext_label_copy_i_tl
1782         \int_step_function:nnN { 2 } { \l__enumext_level_int } \__enumext_tmp:n
1783       }
1784   }
1785   \cs_set:Npn \__enumext_tmp:n ##1
1786     { \tl_use:c { l__enumext_label_copy_ \int_to_roman:n {##1} _tl } }
1787   \bool_lazy_all:nT
1788   {
1789     { \bool_if_p:N \l__enumext_standar_bool }
1790     { \int_compare_p:nNn { \l__enumext_level_int } > { \c_zero_int } }
1791     { \bool_not_p:n { \g__enumext_starred_bool } }
1792     { \int_compare_p:nNn { \l__enumext_level_h_int } > { \c_zero_int } }
1793   }
1794   {
1795     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
1796       {
1797         \int_step_function:nnN { 1 } { \l__enumext_level_int } \__enumext_tmp:n
1798         . \tl_use:N \l__enumext_label_copy_vii_tl
1799       }
1800   }

```

Now we set the variable `\l__enumext_newlabel_arg_one_tl` which will contain $\langle \textit{store name} : \textit{position} \rangle$.

```

1801   \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
1802   {
1803     \l__enumext_store_name_tl \c_colon_str

```

```

1804         \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
1805     }

```

Now execute the function `__enumext_newlabel:nn` and save the result in the variable `\l__enumext_store_write_aux_file_tl` and finally we write in the `.aux` file.

```

1806     \tl_put_right:Ne \l__enumext_store_write_aux_file_tl
1807     {
1808         \__enumext_newlabel:nn
1809         { \exp_not:V \l__enumext_newlabel_arg_one_tl }
1810         { \l__enumext_newlabel_arg_two_tl }
1811     }
1812     \l__enumext_store_write_aux_file_tl
1813 }

```

(End of definition for `__enumext_store_internal_ref:.`)

`__enumext_store_anskey_show_wrap:n`

The function `__enumext_store_anskey_show_wrap:n` “wraps” the *argument* passed to `\anskey` when using the `wrap-ans` key.

```

1814 \cs_new_protected:Npn \__enumext_store_anskey_show_wrap:n #1
1815 {
1816     \par
1817     \bool_if:NT \l__enumext_starred_bool
1818     {
1819         \cs_set:Nn \__enumext_level: { vii }
1820     }
1821     \__enumext_print_keyans_box:cc
1822     { \l__enumext_labelwidth_ \__enumext_level: _dim }
1823     { \l__enumext_labelsep_ \__enumext_level: _dim }
1824     \__enumext_anskey_wrapper:n { #1 }
1825 }

```

(End of definition for `__enumext_store_anskey_show_wrap:n`.)

`__enumext_store_anskey_show_left:n`

The function `__enumext_store_anskey_show_left:n` will show the “mark” defined by the `mark-ans` key or the “position” of the content stored in the *prop list* when using the `show-pos` key on the left margin next to the “wraps” *argument* passed to `\anskey` on the right side when using the `show-ans` key.

```

1826 \cs_new_protected:Npn \__enumext_store_anskey_show_left:n #1
1827 {
1828     \bool_if:NT \l__enumext_show_answer_bool
1829     {
1830         \__enumext_store_anskey_show_wrap:n { #1 }
1831     }
1832     \bool_if:NT \l__enumext_show_position_bool
1833     {
1834         \tl_set:Ne \l__enumext_mark_answer_sym_tl
1835         {
1836             \group_begin:
1837             \exp_not:N \normalfont
1838             \exp_not:N \footnotesize [ \int_eval:n
1839             {
1840                 \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
1841             }
1842             ]
1843             \group_end:
1844         }
1845         \__enumext_store_anskey_show_wrap:n { #1 }
1846     }
1847 }

```

(End of definition for `__enumext_store_anskey_show_left:n`.)

10.25 Common functions for keyans, keyans* and keyanspic

10.25.1 Storing content in prop list

`__enumext_keyans_addto_prop:n`

The function `__enumext_keyans_addto_prop:n` will pass the contents of the current *label* `\l__enumext_label_v_tl` for the `keyans` environment and the current *label* `\l__enumext_label_vi_tl` for the `keyanspic` environment when using `\item*` and `\anspic*`, followed by the *contents* of the optional argument of both commands to the `\l__enumext_store_keyans_label_tl` variable, which will be passed to the *prop list* defined by the `save-ans` key using the `__enumext_store_addto_prop:V`.


```

1848 \cs_new_protected:Npn \__enumext_keyans_addto_prop:n #1
1849 {
1850   \tl_clear:N \l__enumext_store_keyans_label_tl
1851   \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
1852   {
1853     \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \l__enumext_label_vi_tl }
1854   }
1855   {
1856     \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \l__enumext_label_v_tl }
1857   }
1858   \tl_if_novalue:nF { #1 }
1859   {
1860     \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \c_space_tl #1 }
1861   }
1862   \__enumext_store_addto_prop:V \l__enumext_store_keyans_label_tl
1863 }

```

(End of definition for `__enumext_keyans_addto_prop:n`.)

10.25.2 The store-ref key for keyans, keyans* and keyanspic

The internal “*label and ref*” system for the `keyans`, `keyans*` and `keyanspic` environments has slight differences with the one implemented for the `\anskey` command, basically because in this environments we are interested in the current *⟨label⟩*. The mechanism defined here will allow to execute `\ref{⟨store name : position⟩}` and will return `1`. (A).

`__enumext_keyans_store_ref:` The function `__enumext_keyans_store_ref:` handles the internal “*label and ref*” system used by the `store-ref` key for `\item*` and `\anspic*` commands. First we will create copies of the current *⟨labels⟩* and remove the dots “.” from them, we do not want to get double dots in our references.

```

1864 \cs_new_protected:Nn \__enumext_keyans_store_ref:
1865 {
1866   \bool_if:NT \l__enumext_store_ref_key_bool
1867   {
1868     \cs_set_protected:Npn \__enumext_tmp:n ##1
1869     {
1870       \tl_set_eq:cc { \l__enumext_label_copy_##1_tl } { \l__enumext_label_##1_tl }
1871       \tl_reverse:c { \l__enumext_label_copy_##1_tl }
1872       \tl_remove_once:cn { \l__enumext_label_copy_##1_tl } { . }
1873       \tl_reverse:c { \l__enumext_label_copy_##1_tl }
1874     }
1875     \clist_map_inline:nn { i, v, vi, vii, viii } { \__enumext_tmp:n {##1} }
1876     \__enumext_keyans_store_ref_aux_i:
1877   }
1878 }

```

The auxiliary function `__enumext_keyans_store_ref_aux_i:` set the variable `\l__enumext_newlabel_arg_one_tl` which will contain *⟨{store name : position}⟩* analyzing whether the environment in which they are executed is `enumext*` or `enumext`.

```

1879 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_i:
1880 {
1881   \bool_if:NT \g__enumext_starred_bool
1882   {
1883     \tl_set_eq:NN \l__enumext_label_copy_i_tl \l__enumext_label_copy_vii_tl
1884   }
1885   \int_compare:nNnT { \l__enumext_keyans_pic_level_int } = { 1 }
1886   {
1887     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
1888     { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_vi_tl }
1889   }
1890   \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
1891   {
1892     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
1893     { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_v_tl }
1894   }
1895   \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
1896   {
1897     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
1898     { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_viii_tl }
1899   }
1900   \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
1901   {
1902     \l__enumext_store_name_tl \c_colon_str

```

```

1903         \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
1904     }
1905     \__enumext_keyans_store_ref_aux_ii:
1906 }

```

Now auxiliary function `__enumext_keyans_store_ref_aux_ii`: save the result in the variable `\l__enumext_store_write_aux_file_tl` and finally we write in the `.aux` file.

```

1907 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_ii:
1908 {
1909     \tl_put_right:Ne \l__enumext_store_write_aux_file_tl
1910     {
1911         \__enumext_newlabel:nn
1912         { \exp_not:V \l__enumext_newlabel_arg_one_tl }
1913         { \l__enumext_newlabel_arg_two_tl }
1914     }
1915     \l__enumext_store_write_aux_file_tl
1916 }

```

(End of definition for `__enumext_keyans_store_ref:`, `__enumext_keyans_store_ref_aux_i:`, and `__enumext_keyans_store_ref_aux_ii:`.)

10.25.3 Storing content in sequence

```

\__enumext_keyans_addto_seq:n
\__enumext_keyans_addto_seq_link:

```

The function `__enumext_keyans_addto_seq:n` will pass the contents of the current *⟨label⟩* `\l__enumext_label_v_tl` for the `keyans` environment and the `\l__enumext_label_vi_tl` for the `keyanspic` environment when using `\item*` and `\anspic*`, followed by the *⟨contents⟩* of the optional argument of both commands to the `\l__enumext_store_keyans_label_tl` variable to the sequence defined by the `save-ans` key.

```

1917 \cs_new_protected:Npn \__enumext_keyans_addto_seq:n #1
1918 {
1919     \tl_clear:N \l__enumext_store_keyans_label_tl
1920     \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
1921     {
1922         \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \item \l__enumext_label_vi_tl }
1923     }
1924     {
1925         \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \item \l__enumext_label_v_tl }
1926     }
1927     \tl_if_novalue:nF { #1 }
1928     {
1929         \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \c_space_tl #1 }
1930     }
1931     \__enumext_keyans_addto_seq_link:
1932 }

```

Checks if the `store-ref` key is active along with the `hyperref` package load, if both conditions are met, it will create the `\hyperlink` and then store using the `__enumext_store_addto_seq:V` function. Finally, copy the contents of the variable `\l__enumext_store_keyans_label_tl` into the global variable `\g__enumext_check_ans_item_tl` to be used by the function `__enumext_keyans_check_ans:nn` and increment the value of the integer variable `\g__enumext_count_item_anskey_int` handled by the `check-ans` key.

```

1933 \cs_new_protected:Nn \__enumext_keyans_addto_seq_link:
1934 {
1935     \bool_lazy_and:nnT
1936     { \bool_if_p:N \l__enumext_store_ref_key_bool }
1937     { \bool_if_p:N \l__enumext_hyperref_bool }
1938     {
1939         \tl_put_right:Ne \l__enumext_store_keyans_label_tl
1940         {
1941             \hfill \exp_not:N \hyperlink
1942             {
1943                 \exp_not:V \l__enumext_newlabel_arg_one_tl
1944             }
1945             { \exp_not:V \l__enumext_mark_ref_sym_tl }
1946         }
1947     }
1948     \__enumext_store_addto_seq:V \l__enumext_store_keyans_label_tl
1949     \tl_gset:NV \g__enumext_check_ans_item_tl \l__enumext_store_keyans_label_tl
1950     \bool_if:NT \l__enumext_check_ans_bool
1951     {
1952         \int_gincr:N \g__enumext_count_item_anskey_int
1953     }
1954 }

```

(End of definition for `__enumext_keyans_addto_seq:n` and `__enumext_keyans_addto_seq_link:.`)

10.25.4 Check for starred commands

`__enumext_keyans_check_ans:nn`

The function `__enumext_keyans_check_ans:nn` performs an extra check for the `keyans` and `keyanspic` environments. Unlike the check executed by `check-ans` key this one is not controlled by any key, it is intended to prevent the forgetting of `\item*` or `\anspic*` in these environments.

```

1955 \cs_new_protected:Npn \__enumext_keyans_check_ans:nn #1 #2
1956 {
1957   \tl_if_empty:NTF \g__enumext_check_ans_item_tl
1958   {
1959     \msg_warning:nnnn { enumext } { missing-starred } { #1 } { #2 }
1960   }
1961   { \tl_gclear:N \g__enumext_check_ans_item_tl }
1962 }

```

(End of definition for `__enumext_keyans_check_ans:nn`.)

10.25.5 The show-ans and show-pos keys for keyans and keyanspic

The code is very similar to the `\anskey` code, but, if I change the order of the operations the counter off `⟨label⟩` are incorrect.

`__enumext_keyans_show_left:n`

Common function to show *starred commands* `\item*` and `⟨position⟩` of stored content in `⟨prop list⟩` for `keyans` and `keyanspic`. Need add 1 to `\l__enumext_show_position_bool` for `keyans` environment.

```

1963 \cs_new_protected:Npn \__enumext_keyans_show_left:n #1
1964 {
1965   \bool_if:NT \l__enumext_show_answer_bool
1966   {
1967     \tl_put_left:Nn \l__enumext_label_v_tl
1968     {
1969       \__enumext_print_keyans_box:NN
1970       \l__enumext_labelwidth_i_dim
1971       \l__enumext_labelsep_i_dim
1972     }
1973     \tl_if_novalue:nF { #1 }
1974     { \tl_put_right:Nn \l__enumext_label_v_tl { \c_space_tl [ #1 ] } }
1975   }
1976   \bool_if:NT \l__enumext_show_position_bool
1977   {
1978     \tl_set:Ne \l__enumext_mark_answer_sym_tl
1979     {
1980       \group_begin:
1981       \exp_not:N \normalfont
1982       \exp_not:N \footnotesize [ \int_eval:n
1983       {
1984         \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } + \c_one_int
1985       }
1986       ]
1987       \group_end:
1988     }
1989     \tl_put_left:Nn \l__enumext_label_v_tl
1990     {
1991       \__enumext_print_keyans_box:NN
1992       \l__enumext_labelwidth_i_dim
1993       \l__enumext_labelsep_i_dim
1994     }
1995     \tl_if_novalue:nF { #1 }
1996     { \tl_put_right:Nn \l__enumext_label_v_tl { \c_space_tl [ #1 ] } }
1997   }
1998 }

```

(End of definition for `__enumext_keyans_show_left:n`.)

10.26 Setting item-sym* and item-pos* keys

In order to have a cleaner implementation of `\item*` it is best to define a couple of keys that allow us to control and set by default the `⟨symbol⟩` and its `⟨offset⟩`.

`item-sym*`

Define and set `item-sym*` and `item-pos*` keys for `enumext` and `enumext*`.

`item-pos*`

```

1999 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
2000 {
2001   \keys_define:nn { enumext / #1 }

```

```

2002     {
2003       item-sym* .tl_set:c = { l__enumext_item_symbol_#2_tl },
2004       item-sym* .value_required:n = true,
2005       item-sym* .initial:n = { $\star$ },
2006       item-pos* .dim_set:c = { l__enumext_item_symbol_sep_#2_dim },
2007       item-pos* .value_required:n = true,
2008     }
2009   }
2010 \clist_map_inline:nn
2011   {
2012     {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {enumext*}{vii}
2013   }
2014   { \__enumext_tmp:nn #1 }

```

(End of definition for `item-sym*` and `item-pos*`.)

10.27 Redefining `\footnote` command

```

\__enumext_footnotetext:nn
\__enumext_renew_footnote:
\__enumext_print_footnote:

```

To keep the correct numbering of `\footnote` and to make it work correctly with the `mini-env` key and in the `enumext*` and `keyans*` environments, it is necessary to redefine the command. This implementation is adapted from the answer given by Clea F. Rees (@cfr) in [footnotes in boxes compatible with hyperref](#).

```

2015 \cs_new_protected:Nn \__enumext_footnotetext:nn
2016   {
2017     \footnotetext[#1]{#2}
2018   }
2019 \cs_new_protected:Nn \__enumext_renew_footnote:
2020   {
2021     \seq_gclear:N \g__enumext_footnote_arg_seq
2022     \seq_gclear:N \g__enumext_footnote_int_seq
2023     \RenewDocumentCommand \footnote { o +m }
2024     {
2025       \tl_if_novalue:nTF {##1}
2026       {
2027         \stepcounter{footnote}
2028         \int_gset_eq:Nc \g__enumext_footnote_int { c@footnote }
2029       }
2030       {
2031         \int_gset:Nn \g__enumext_footnote_int { ##1 }
2032       }
2033       \footnotemark [ \g__enumext_footnote_int ]
2034       \seq_gput_right:Nn \g__enumext_footnote_arg_seq { ##2 }
2035       \seq_gput_right:NV \g__enumext_footnote_int_seq \g__enumext_footnote_int
2036     }
2037   }
2038 \cs_new_protected:Nn \__enumext_print_footnote:
2039   {
2040     \seq_if_empty:NF \g__enumext_footnote_int_seq
2041     {
2042       \seq_map_pairwise_function:NNN
2043       \g__enumext_footnote_int_seq
2044       \g__enumext_footnote_arg_seq
2045       \__enumext_footnotetext:nn
2046     }
2047   }

```

(End of definition for `__enumext_footnotetext:nn`, `__enumext_renew_footnote:`, and `__enumext_print_footnote:`.)

10.28 Redefining `\item` command

Redefining the `\item` command is not as simple as I thought. This command works in conjunction with the `\makeLabel` command so I have to redefine both of them, in addition to this, we will have to use a couple of *global* variables to pass the values from one command to the other.

10.28.1 The `\item` command in `enumext`

```
\__enumext_default_item:n
```

The `\item` and `\item[custom]` commands work in the usual way on `enumext`.

First we will see if the optional argument is present, if it is NOT present we will check the state of the variable `\l__enumext_check_ans_bool` set by the key `check-ans`, set the boolean variable `\l__enumext_wrap_label_X_bool` to “true” and execute `__enumext_item_std:w`.

Otherwise we will check the state of the boolean variable `\l__enumext_wrap_label_opt_X_bool` set by the key `wrap-label*` and execute `__enumext_item_std:w` with the optional argument.

The boolean variable `\l__enumext_wrap_label_X_bool` is used by the function `__enumext_make_label:` (§10.29).

```

2048 \cs_new_protected:Npn \__enumext_default_item:n #1
2049 {
2050   \tl_if_novalue:nTF {#1}
2051   {
2052     \bool_if:NT \l__enumext_check_ans_bool
2053     {
2054       \int_gincr:N \g__enumext_count_item_number_int
2055     }
2056     \bool_set_true:c { \l__enumext_wrap_label_ \__enumext_level: _bool }
2057     \__enumext_item_std:w \tl_use:c { \l__enumext_fake_item_indent_ \__enumext_level: _tl }
2058   }
2059   {
2060     \bool_set_eq:cc
2061     { \l__enumext_wrap_label_ \__enumext_level: _bool }
2062     { \l__enumext_wrap_label_opt_ \__enumext_level: _bool }
2063     \__enumext_item_std:w [#1] \tl_use:c { \l__enumext_fake_item_indent_ \__enumext_level: _tl }
2064   }
2065 }

```

(End of definition for `__enumext_default_item:n`.)

`__enumext_starred_item:nn`

The `\item*`, `\item*[\langle symbol \rangle]` and `\item*[\langle symbol \rangle][\langle offset \rangle]` works like the numbered `\item`, but placing a `[\langle symbol \rangle]` to the “left” of the `\langle label \rangle` separated from it by the value set by the `labelsep` key and can be *offset* using the second optional argument `[\langle offset \rangle]`.

#1: `\l__enumext_item_symbol_X_tl`

#2: `\l__enumext_item_symbol_sep_X_dim`

First we will make a copy of `\l__enumext_item_symbol_X_tl` which is set by the key `item-sym*` or passed as optional argument in the global variable `\g__enumext_item_symbol_tl`, followed by setting the variable `\l__enumext_item_symbol_sep_X_dim` set by the key `item*-sep` or by the second optional argument.

Then we will see the state of the variable `\l__enumext_check_ans_bool` set by the key `check-ans`, set the boolean variable `\l__enumext_wrap_label_X_bool` to “true” and execute `__enumext_item_std:w`.

In this function the optional argument of `__enumext_item_std:w` is omitted, we only want it to be numbered.

The boolean variable `\l__enumext_wrap_label_X_bool` and the vars `\l__enumext_item_symbol_sep_X_dim`, `\g__enumext_item_symbol_tl` are used by the function `__enumext_make_label:` (§10.29).

```

2066 \cs_new_protected:Npn \__enumext_starred_item:nn #1 #2
2067 {
2068   \tl_if_novalue:nF {#1}
2069   {
2070     \tl_set:cn { \l__enumext_item_symbol_ \__enumext_level: _tl } {#1}
2071   }
2072   \tl_gset_eq:Nc \g__enumext_item_symbol_tl { \l__enumext_item_symbol_ \__enumext_level: _tl }
2073   \tl_if_novalue:nTF {#2}
2074   {
2075     \dim_set_eq:cc
2076     { \l__enumext_item_symbol_sep_ \__enumext_level: _dim }
2077     { \l__enumext_labelsep_ \__enumext_level: _dim }
2078   }
2079   {
2080     \dim_set:cn { \l__enumext_item_symbol_sep_ \__enumext_level: _dim } {#2}
2081   }
2082   \bool_if:NT \l__enumext_check_ans_bool
2083   {
2084     \int_gincr:N \g__enumext_count_item_number_int
2085   }
2086   \bool_set_true:c { \l__enumext_wrap_label_ \__enumext_level: _bool }
2087   \__enumext_item_std:w \tl_use:c { \l__enumext_fake_item_indent_ \__enumext_level: _tl }
2088 }

```

(End of definition for `__enumext_starred_item:nn`.)

`__enumext_redefine_item:` The function `__enumext_redefine_item:` will redefine the `\item` command in the `enumext` environment for the internal mechanism of check-answers for `check-ans` key and adding the starred `\item*` version.

This function is passed to `__enumext_list_arg_two_X:` which is used in the definition of the `enumext` environment (§10.31).

```
2089 \cs_new_protected:Nn \__enumext_redefine_item:
2090 {
2091   \RenewDocumentCommand \item { s o o }
2092   {
2093     \bool_if:nTF {##1}
2094     {
2095       \__enumext_starred_item:nn {##2} {##3}
2096     }
2097     { \__enumext_default_item:n {##2} }
2098   }
2099 }
```

(End of definition for `__enumext_redefine_item:`.)

10.28.2 The `\item` command in keyans

The `\item*` and `\item*[\langle content \rangle]` commands *store* the current $\langle label \rangle$ next to the $[\langle content \rangle]$ if it is present in the $\langle sequence \rangle$ and $\langle prop list \rangle$ defined by `save-ans` key.

`__enumext_keyans_default_item:n` The function `__enumext_keyans_default_item:n` executes the original behavior of the `\item`.

```
2100 \cs_new_protected:Npn \__enumext_keyans_default_item:n #1
2101 {
2102   \tl_if_novalue:nTF { #1 }
2103   {
2104     \bool_set_true:N \l__enumext_wrap_label_v_bool
2105     \__enumext_item_std:w \tl_use:N \l__enumext_fake_item_indent_v_tl
2106   }
2107   {
2108     \bool_set_eq:NN \l__enumext_wrap_label_v_bool \l__enumext_wrap_label_opt_v_bool
2109     \__enumext_item_std:w [#1] \tl_use:N \l__enumext_fake_item_indent_v_tl
2110   }
2111 }
```

(End of definition for `__enumext_keyans_default_item:n`.)

`__enumext_keyans_starred_item:n` The function `__enumext_keyans_starred_item:n` which will make a temporary copy of the current $\langle label \rangle$, execute the `show-ans` or `show-pos` keys using the function `__enumext_keyans_show_left:n` and will display the contents of that item using the internal copy `__enumext_item_std:w`, this is necessary to prevent incrementing the current “counter” of the original $\langle label \rangle$.

```
2112 \cs_new_protected:Npn \__enumext_keyans_starred_item:n #1
2113 {
2114   \tl_set_eq:NN \l__enumext_keyans_tmpa_tl \l__enumext_label_v_tl
2115   \__enumext_keyans_show_left:n { #1 }
2116   \bool_set_true:N \l__enumext_wrap_label_v_bool
2117   \__enumext_item_std:w \tl_use:N \l__enumext_fake_item_indent_v_tl
```

Recover the original value of the current $\langle label \rangle$ and *store* it first in the $\langle prop list \rangle$ (including the optional argument), run the internal “*label and ref*” system if the `store-ref` key is active and finally *store* it in the $\langle sequence \rangle$.

```
2118   \tl_set_eq:NN \l__enumext_label_v_tl \l__enumext_keyans_tmpa_tl
2119   \__enumext_keyans_addto_prop:n { #1 }
2120   \__enumext_keyans_store_ref:
2121   \__enumext_keyans_addto_seq:n { #1 }
2122 }
```

(End of definition for `__enumext_keyans_starred_item:n`.)

`\item*` The function `__enumext_keyans_redefine_item:` is responsible for adding the *starred* and *optional* argument by the `__enumext_list_arg_two_v:` function in the definition of the `keyans` environment. Here we need to use `\peek_remove_spaces:n` to prevent an unwanted space when using `\item*` in conjunction with the `itemindent` key.

`__enumext_keyans_redefine_item:`

This function is passed to `__enumext_list_arg_two_v:` which is used in the definition of the `keyans` environment (§10.31).

```
2123 \cs_new_protected:Nn \__enumext_keyans_redefine_item:
2124 {
```

```

2125 \RenewDocumentCommand \item { s o }
2126 {
2127   \bool_if:nTF {##1}
2128   {
2129     \peek_remove_spaces:n
2130     {
2131       \__enumext_keyans_starred_item:n {##2}
2132     }
2133   }
2134   {
2135     \__enumext_keyans_default_item:n {##2}
2136   }
2137 }
2138 }

```

(End of definition for `\item*` and `__enumext_keyans_redefine_item:`. This function is documented on page 11.)

10.29 Redefining `\makelabel` command

Redefine `\makelabel` for the keys `align`, `font`, `wrap-label`, `wrap-label*` and `\item*` for `enumext` and `keyans` environments.

10.29.1 Redefining `\makelabel` for `enumext`

`__enumext_item_starred:` The function `__enumext_item_starred:` will be responsible for executing `\item*` for the `enumext` environment.

```

2139 \cs_new_protected:Nn \__enumext_item_starred:
2140 {
2141   \tl_if_empty:cF { \__enumext_item_symbol_ \__enumext_level: _tl }
2142   {
2143     \mode_leave_vertical:
2144     \skip_horizontal:n { -\dim_use:c { \__enumext_item_symbol_sep_ \__enumext_level: _dim } }
2145     \makebox[ 0pt ][ r ]{ \g__enumext_item_symbol_tl }
2146     \skip_horizontal:n { \dim_use:c { \__enumext_item_symbol_sep_ \__enumext_level: _dim } }
2147   }
2148 }

```

(End of definition for `__enumext_item_starred:`.)

`__enumext_make_label:` The function `__enumext_make_label:` redefine `\makelabel` for the `enumext` environment.

This function is passed to `__enumext_list_arg_two_X:` which is used in the definition of the `enumext` environment (§10.31).

```

2149 \cs_new_protected:Nn \__enumext_make_label:
2150 {
2151   \RenewDocumentCommand \makelabel { m }
2152   {
2153     \tl_use:c { \__enumext_label_fill_left_ \__enumext_level: _tl }
2154     \tl_use:c { \__enumext_label_font_style_ \__enumext_level: _tl }
2155     \bool_if:cTF { \__enumext_wrap_label_ \__enumext_level: _bool }
2156     {
2157       \__enumext_item_starred:
2158       \use:c { __enumext_wrapper_label_ \__enumext_level: :n } { ##1 }
2159     }
2160     { ##1 }
2161     \tl_use:c { \__enumext_label_fill_right_ \__enumext_level: _tl }
2162     \tl_gclear:N \g__enumext_item_symbol_tl
2163   }
2164 }

```

(End of definition for `__enumext_make_label:`.)

10.29.2 Redefining `\makelabel` for `keyans`

`__enumext_keyans_make_label:` The function `__enumext_keyans_make_label:` redefine `\makelabel` for `keyans` environment.

This function is passed to `__enumext_list_arg_two_v:` which is used in the definition of the `keyans` environment (§10.31).

```

2165 \cs_new_protected:Nn \__enumext_keyans_make_label:
2166 {
2167   \RenewDocumentCommand \makelabel { m }
2168   {
2169     \tl_use:N \l__enumext_label_fill_left_v_tl
2170     \tl_use:N \l__enumext_label_font_style_v_tl
2171     \bool_if:NTF \l__enumext_wrap_label_v_bool

```



```

2172     {
2173         \__enumext_wrapper_label_v:n { ##1 }
2174     }
2175     { ##1 }
2176     \tl_use:N \__enumext_label_fill_right_v_tl
2177 }
2178 }

```

(End of definition for `__enumext_keyans_make_label:`)

10.30 Calculation of `\leftmargin` and `\itemindent`

Consider the figure 9 where the default margins (on the left) of a list are represented.



Figure 9: Representation of standard horizontal lengths in `list` environment.

The idea is to have control over these margins so that our list does not overlap the left margin of the page. The *key* relationship is that the right edge of the `\labelsep` equals the right edge of the `\itemindent`, so that the left edge of the *label box* is at `\leftmargin + \itemindent` minus `\labelwidth + \labelsep`. Thus, the handling of the margins by the package will be as shown in the figure 10.




Figure 10: Representation of horizontal lengths concept in list in `enumext`.

Where the default values will look like in the figure 11.




Figure 11: Default horizontal lengths in `enumext`.

```

\__enumext_calc_hspace:NNNNNNN
\__enumext_calc_hspace:ccccccc

```

The function `__enumext_calc_hspace:NNNNNNN` takes seven arguments to be able to determine horizontal spaces for all list environment:

```

#1: \__enumext_labelwidth_X_dim      #2: \__enumext_labelsep_X_dim
#3: \__enumext_listoffset_X_dim      #4: \__enumext_leftmargin_tmp_X_dim
#5: \__enumext_leftmargin_X_dim      #6: \__enumext_itemindent_X_dim
#7: \__enumext_leftmargin_tmp_X_bool

```

And returns the “adjusted” values of `\leftmargin` and `\itemindent`.

This function is passed to `__enumext_list_arg_two_X:` which is used in the definition of the `enumext` and `keyans` environments (§10.31).

```

2179 \cs_new_protected:Npn \__enumext_calc_hspace:NNNNNNN #1 #2 #3 #4 #5 #6 #7
2180 {
2181     \dim_compare:nNt { #1 } < { \c_zero_dim }
2182     {
2183         \msg_warning:nnnV { enumext } { width-non-positive } { labelwidth } { #1 }
2184         \dim_set:Nn #1 { \dim_abs:n { #1 } }
2185     }
2186     \dim_compare:nNt { #2 } < { \c_zero_dim }
2187     {
2188         \msg_warning:nnnV { enumext } { width-negative } { labelsep } { #2 }
2189         \dim_set:Nn #2 { \dim_abs:n { #2 } }
2190     }
2191 }

```

If no value has been passed to the `labelwidth` and `labelsep` keys we set the default values for `__enumext_leftmargin_tmp_X_dim`.

```

2191     \bool_if:nF #7 { \dim_set:Nn #4 { #1 + #2 } }

```

We now analyze the cases and set the values for `\leftmargin` and `\itemindent`.

```

2192   \dim_compare:nNnTF { #4 } < { \c_zero_dim }
2193   {
2194     \dim_set:Nn #6 { #1 + #2 - #4 }
2195     \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
2196   }
2197   {
2198     \dim_compare:nNnT { #4 } = { #1 + #2 }
2199     { \dim_set:Nn #6 { \c_zero_dim } }
2200     \dim_compare:nNnT { #4 } < { #1 + #2 }
2201     { \dim_set:Nn #6 { #1 + #2 - #4 } }
2202     \dim_compare:nNnT { #4 } > { #1 + #2 }
2203     {
2204       \dim_set:Nn #6 { -#1 - #2 + #4 }
2205       \dim_set:Nn #6 { #6*-1 }
2206     }
2207     \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
2208   }
2209 }
2210 \cs_generate_variant:Nn \__enumext_calc_hspace:NNNNNNN { cccccc }

```

(End of definition for `__enumext_calc_hspace:NNNNNNN`.)

10.31 Setting second argument of the lists

At this point of the code we have already programmed the necessary tools to create a custom `list` environment, remember that the function `__enumext_start_list:n` takes two arguments, the first one we have ready, the second one we will define for all the levels of the environment `enumext` and the environment `keyans`.

In this function for the second list argument we will implement the keys `start`, `resume` and `show-length` together with the redefinition of `\item` for `enumext` and `keyans` environments.

We will “not set” `\leftmargini`, `\leftmarginii`, `\leftmarginiii` or `\leftmarginiv`, in this case, we will directly set the parameters for vertical and horizontal list spacing per level.

```

2211 \cs_set_protected:Npn \__enumext_tmp:n #1
2212 {
2213   \cs_new_protected:cpn { __enumext_list_arg_two_#1: }
2214   {
2215     \__enumext_calc_hspace:ccccc
2216     { \__enumext_labelwidth_#1_dim } { \__enumext_labelsep_#1_dim }
2217     { \__enumext_listoffset_#1_dim } { \__enumext_leftmargin_tmp_#1_dim }
2218     { \__enumext_leftmargin_#1_dim } { \__enumext_itemindent_#1_dim }
2219     { \__enumext_leftmargin_tmp_#1_bool }
2220     \clist_map_inline:nn
2221     { labelsep, labelwidth, itemindent, leftmargin, rightmargin, listparindent }
2222     { \dim_set_eq:cc {####1} { \__enumext_####1_#1_dim } }
2223     \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
2224     { \skip_set_eq:cc {####1} { \__enumext_####1_#1_skip } }
2225     \usecounter { enumX#1 }
2226     \bool_lazy_and:nnTF
2227     { \str_if_eq_p:nn {#1} { i } }
2228     { \bool_if_p:N \__enumext_resume_bool }
2229     { \setcounter { enumXi } { \int_eval:n { \g__enumext_resume_int } } }
2230     {
2231       \setcounter { enumX#1 }
2232       { \int_eval:n { \int_use:c { \__enumext_start_#1_int } - 1 } }
2233     }
2234     \str_if_eq:nnTF {#1} { v }
2235     {
2236       \__enumext_keyans_redefine_item:
2237       \__enumext_keyans_make_label:
2238       \__enumext_keyans_fake_item:
2239       \bool_if:cT { \__enumext_show_length_#1_bool }
2240       {
2241         \msg_term:nnnn { enumext } { list-lengths-not-nested } { v } { keyans }
2242       }
2243     }
2244     {
2245       \__enumext_redefine_item:
2246       \__enumext_make_label:
2247       \__enumext_use_key_ref:

```

```

2248         \__enumext_fake_item:
2249         \bool_if:cT { \__enumext_show_length_#1_bool }
2250         {
2251             \msg_term:nne { enumext } { list-lengths } {#1} { \int_use:N \__enumext_level_i
2252         }
2253     }
2254 }
2255 }
2256 \clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }

```

(End of definition for __enumext_list_arg_two_i: and others.)

```

\__enumext_list_arg_two_vii:
\__enumext_list_arg_two_viii:

```

For the horizontal environments `enumext*` and `keyans*` the implementation is similar, but, the value of `\partopsep` is always `\opt`. At this point we will modify the `parsep` key to make it take the value of the `itemsep` key and later, in the environment definition, we will modify `parindent` to make it set the value of `lisparindent` and `parsep` to set the value of `\parskip` locally.

```

2257 \cs_set_protected:Npn \__enumext_tmp:n #1
2258 {
2259     \cs_new_protected:cpn { \__enumext_list_arg_two_#1: }
2260     {
2261         \__enumext_calc_hspace:ccccc
2262         { \__enumext_labelwidth_#1_dim } { \__enumext_labelsep_#1_dim }
2263         { \__enumext_listoffset_#1_dim } { \__enumext_leftmargin_tmp_#1_dim }
2264         { \__enumext_leftmargin_#1_dim } { \__enumext_itemindent_#1_dim }
2265         { \__enumext_leftmargin_tmp_#1_bool }
2266         \clist_map_inline:nn
2267         { labelsep, labelwidth, itemindent, leftmargin, rightmargin, listparindent }
2268         { \dim_set_eq:cc {####1} { \__enumext_####1_#1_dim } }
2269         \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
2270         { \skip_set_eq:cc {####1} { \__enumext_####1_#1_skip } }
2271         \skip_set_eq:Nc \parsep { \__enumext_itemsep_#1_skip }
2272         \skip_zero:N \partopsep
2273         \usecounter { enumX#1 }
2274         \bool_lazy_and:nnTF
2275         { \str_if_eq_p:nn {#1} { vii } } { \bool_if_p:N \__enumext_resume_vii_bool }
2276         { \setcounter { enumXvii } { \int_eval:n { \g__enumext_resume_vii_int } } }
2277         {
2278             \setcounter { enumX#1 }
2279             { \int_eval:n { \int_use:c { \__enumext_start_#1_int } - 1 } }
2280         }
2281         \__enumext_use_key_ref_h:
2282         \str_if_eq:nnTF {#1} { vii }
2283         {
2284             \__enumext_fake_item_vii:
2285             \bool_if:cT { \__enumext_show_length_vii_bool }
2286             { \msg_term:nnnn { enumext } { list-lengths-not-nested } { vii } { enumext* } }
2287         }
2288         {
2289             \__enumext_fake_item_viii:
2290             \bool_if:cT { \__enumext_show_length_#1_bool }
2291             { \msg_term:nnnn { enumext } { list-lengths-not-nested } { #1 } { keyans* } }
2292         }
2293     }
2294 }
2295 \clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for __enumext_list_arg_two_vii: and __enumext_list_arg_two_viii:.)

10.32 The environment enumext

`enumext` We create the `enumext` environment based on `list` environment by levels.

```

2296 \NewDocumentEnvironment{enumext}{0} {
2297     {
2298         \__enumext_current_env:
2299         \__enumext_safe_exec:
2300         \__enumext_parse_keys:n {#1}
2301         \__enumext_before_list:
2302         \__enumext_start_store_level:
2303         \__enumext_start_list:nn
2304         { \tl_use:c { \__enumext_label_ \__enumext_level: _tl } }
2305         {
2306             \use:c { \__enumext_list_arg_two_ \__enumext_level: : }

```

```

2307     \__enumext_before_keys_exec:
2308     }
2309     \__enumext_after_args_exec:
2310     }
2311     {
2312     \__enumext_stop_list:
2313     \__enumext_stop_store_level:
2314     \__enumext_after_list:
2315     }

```

(End of definition for enumext. This function is documented on page 4.)

`__enumext_safe_exec:` First check the maximum nesting level for the `enumext` environment and set the state of the booleans `\l__enumext_standar_bool` and `\g__enumext_standar_bool` to “true”, the latter only if the environment is NOT nested in the `enumext*` environment.

```

2316 \cs_new_protected:Nn \__enumext_safe_exec:
2317 {
2318     \int_incr:N \l__enumext_level_int
2319     \int_compare:nNnT { \l__enumext_level_int } > { 4 }
2320     { \msg_fatal:nn { enumext } { list-too-deep } }
2321     \bool_set_true:N \l__enumext_standar_bool
2322 }

```

(End of definition for `__enumext_safe_exec:`)

`__enumext_parse_keys:n` Parse [`<key = val>`] by levels in `enumext`. If the variable `\l__enumext_store_active_bool` is true it will call the function `__enumext_parse_store_keys:n` and reprocess the `<keys>` to pass them to the storage sequence.

```

2323 \cs_new_protected:Npn \__enumext_parse_keys:n #1
2324 {
2325     \exp_args:Ne \keys_set:nn
2326     { enumext / level-\int_use:N \l__enumext_level_int } {#1}
2327     \bool_if:NT \l__enumext_store_active_bool
2328     {
2329         \__enumext_parse_store_keys:n {#1}
2330     }
2331 }

```

(End of definition for `__enumext_parse_keys:n`)

`__enumext_parse_store_keys:n` The function `__enumext_parse_store_keys:n` searches for the values of the `columns` and `columns-sep` keys in the optional arguments per-level in `enumext` environment as long as the starred versions of the `columns*` and `columns-sep*` keys are not active. The captured values are stored in the variable `\l__enumext_store_opt_X_tl` which is used by the function `__enumext_store_level_open:`.

```

2332 \cs_new_protected:Npn \__enumext_parse_store_keys:n #1
2333 {
2334     \bool_if:cF { l__enumext_store_columns_ \__enumext_level: _bool }
2335     {
2336         \regex_match:nnT { \b columns\b } {#1}
2337         {
2338             \int_set_eq:cc
2339             { l__enumext_store_columns_ \__enumext_level: _int }
2340             { l__enumext_columns_ \__enumext_level: _int }
2341             \tl_put_right:ce { l__enumext_store_opt_ \__enumext_level: _tl }
2342             {
2343                 columns = \exp_not:v { l__enumext_store_columns_ \__enumext_level: _int },
2344             }
2345         }
2346     }
2347     \bool_if:cF { l__enumext_store_columns_sep_ \__enumext_level: _bool }
2348     {
2349         \regex_match:nnT { \b columns-sep\b } {#1}
2350         {
2351             \dim_set_eq:cc
2352             { l__enumext_store_columns_sep_ \__enumext_level: _dim }
2353             { l__enumext_columns_sep_ \__enumext_level: _dim }
2354             \tl_put_right:ce { l__enumext_store_opt_ \__enumext_level: _tl }
2355             {
2356                 columns-sep = \exp_not:v { l__enumext_store_columns_sep_ \__enumext_level: _dim }
2357             }
2358         }
2359     }

```

```

2358     }
2359   }
2360 }

```

(End of definition for `__enumext_parse_store_keys:n`)

```

\__enumext_start_store_level:
\__enumext_stop_store_level:

```

The `__enumext_start_store_level:` and `__enumext_stop_store_level:` functions activate the level saving mechanism for storage in *sequence* of the `\anskey` command. If `enumext` are nested in `enumext*` add `__enumext_store_level_open:` to preserve the stored structure.

```

2361 \cs_new_protected:Nn \__enumext_start_store_level:
2362 {
2363   \bool_lazy_all:nT
2364   {
2365     { \bool_if_p:N \l__enumext_store_active_bool }
2366     { \bool_not_p:n { \l__enumext_keyans_env_bool } }
2367     { \bool_not_p:n { \g__enumext_starred_bool } }
2368   }
2369   {
2370     \int_compare:nNnT { \l__enumext_level_int } > { 1 }
2371     {
2372       \bool_set_true:c { l__enumext_store_upper_level_ \__enumext_level: _bool }
2373       \__enumext_store_level_open:
2374     }
2375   }
2376   \bool_lazy_all:nT
2377   {
2378     { \bool_if_p:N \l__enumext_store_active_bool }
2379     { \bool_not_p:n { \l__enumext_keyans_env_bool } }
2380     { \bool_if_p:N \g__enumext_starred_bool }
2381   }
2382   {
2383     \int_compare:nNnT { \l__enumext_level_int } > { 0 }
2384     {
2385       \bool_set_true:c { l__enumext_store_upper_level_ \__enumext_level: _bool }
2386       \__enumext_store_level_open:
2387     }
2388   }
2389 }
2390 \cs_new_protected:Nn \__enumext_stop_store_level:
2391 {
2392   \bool_if:cT { l__enumext_store_upper_level_ \__enumext_level: _bool }
2393   {
2394     \__enumext_store_level_close:
2395   }
2396 }

```

(End of definition for `__enumext_start_store_level:` and `__enumext_stop_store_level:`)

```
\__enumext_before_list:
```

The function `__enumext_before_list:` will add the vertical spacing on the environment if the `above` key is active next to the `{code}` defined by the `before*` key if it is active.

```

2397 \cs_new_protected:Nn \__enumext_before_list:
2398 {
2399   \__enumext_vspace_above:
2400   \__enumext_before_args_exec:

```

The function `__enumext_check_ans_exec:` will handle the check answer mechanism, which will be activated with the `check-ans` key.

```
2401 \__enumext_check_ans_exec:
```

When the `mini-env` key is active it will set the value of the `\l__enumext_minipage_right_X_dim` to be the *width* of the `__enumext_mini-env*` environment on the “right side”, using this value together with the value of the `\l__enumext_minipage_hsep_X_dim` set by the `mini-sep` key, the value of `\l__enumext_minipage_left_X_dim` will be set, which will be the *width* of `__enumext_mini-env*` environment on the “left side”, always having a current `\linewidth` as *maximum width* between them.

```

2402 \dim_compare:nNnT
2403 { \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim } } > { \c_zero_dim }
2404 {
2405   \dim_set:cn { l__enumext_minipage_left_ \__enumext_level: _dim }
2406   {
2407     \linewidth

```

```

2408         - \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim }
2409         - \dim_use:c { l__enumext_minipage_hsep_ \__enumext_level: _dim }
2410     }

```

The boolean variable `\l__enumext_minipage_active_X_bool` will be activated and the integer variable `\g__enumext_minipage_stat_int` used by the `\miniright` command will be incremented, then the function `__enumext_mini_addvspace:` is called and the `__enumext_mini_env*` environment on the “left side” will be initialized followed by the “vertical spacing” applied to preserve the “baseline” between the left and right side environments. After these actions, the function `__enumext_multicols_start:` is called to handle the `multicols` environment.

- Here we use the plain T_EX macro `\nointerlineskip` to prevent baseline “glue” being added between the next pair of boxes in a vertical list.

```

2411     \bool_set_true:c { l__enumext_minipage_active_ \__enumext_level: _bool }
2412     \int_gincr:N \g__enumext_minipage_stat_int
2413     \__enumext_mini_addvspace:
2414     \nointerlineskip\noindent
2415     \begin{\__enumext_mini_env*}
2416         { \dim_use:c { l__enumext_minipage_left_ \__enumext_level: _dim } }
2417     }
2418     \__enumext_multicols_start:
2419 }

```

(End of definition for `__enumext_before_list:`)

`__enumext_multicols_start:` The function `__enumext_multicols_start:` will start the `multicols` environment according to the value passed by the `columns` key, then set the default value for `\columnsep` when `columns-sep=opt` and set the value of `\multicolsep` equal to zero and leave `\columnseprule` equal to zero for inner levels.

```

2420 \cs_new_protected:Nn \__enumext_multicols_start:
2421 {
2422     \int_compare:nNt
2423     { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
2424     {
2425         \dim_compare:nNt
2426         { \dim_use:c { l__enumext_columns_sep_ \__enumext_level: _dim } } = { \c_zero_dim }
2427         {
2428             \dim_set:cn { l__enumext_columns_sep_ \__enumext_level: _dim }
2429             {
2430                 ( \dim_use:c { l__enumext_labelwidth_ \__enumext_level: _dim }
2431                   + \dim_use:c { l__enumext_labelsep_ \__enumext_level: _dim }
2432                 ) / \int_use:c { l__enumext_columns_ \__enumext_level: _int }
2433                 - \dim_use:c { l__enumext_listoffset_ \__enumext_level: _dim }
2434             }
2435         }
2436         \dim_set_eq:Nc \columnsep { l__enumext_columns_sep_ \__enumext_level: _dim }
2437         \skip_zero:N \multicolsep
2438         \int_compare:nNt { \l__enumext_level_int } > { 1 }
2439         {
2440             \dim_zero:N \columnseprule
2441         }
2442     }
2443 }

```

We will calculate the *vertical spacing* settings for the `multicols` environment using the function `__enumext_multi_addvspace:`, apply our “vertical adjust spacing”, then start the `multicols` environment.

```

2442     \bool_if:cF { l__enumext_minipage_active_ \__enumext_level: _bool }
2443     {
2444         \__enumext_multi_addvspace:
2445     }
2446     \raggedcolumns
2447     \begin{multicols}{ \int_use:c { l__enumext_columns_ \__enumext_level: _int } }
2448 }
2449 }

```

(End of definition for `__enumext_multicols_start:`)

`__enumext_multicols_stop:` The function `__enumext_multicols_stop:` will stop the `multicols` environment. If the boolean variable `\l__enumext_minipage_active_X_bool` is false (not nested in `__enumext_mini_env*`) we will apply our “vertical adjust” spacing.

```

2450 \cs_new_protected:Nn \__enumext_multicols_stop:
2451 {
2452     \int_compare:nNt

```

```

2453     { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
2454     {
2455         \end{multicols}
2456         \bool_if:cF { l__enumext_minipage_active_ \__enumext_level: _bool }
2457         {
2458             \par\addvspace{ \skip_use:c { l__enumext_multicols_below_ \__enumext_level: _skip } }
2459         }
2460     }

```

If the `check-ans` key is active, we set the boolean variable `\g__enumext_check_ans_show_bool` to true and copy the stored name to the variable `\g__enumext_store_name_tl`. These variables will be used by the function `__enumext_after_env:n` to display the result of the internal check answer mechanism in the terminal.

```

2461     \bool_lazy_and:nnT
2462     { \bool_if_p:N \l__enumext_check_ans_bool }
2463     { \bool_not_p:n { \g__enumext_starred_bool } }
2464     {
2465         \bool_gset_true:N \g__enumext_check_ans_show_bool
2466         \tl_gset:NV \g__enumext_store_name_tl \l__enumext_store_name_tl
2467     }
2468 }

```

(End of definition for `__enumext_multicols_stop:`.)

`__enumext_after_list:` The function `__enumext_after_list:` will will check the state of the boolean variable `\l__enumext_minipage_active_X_bool`, if it is “true” a small test will be executed to check if we have omitted the use of `\miniright` (the `__enumext_mini_env*` environment has not been closed), then close `__enumext_mini_env*` and add the *adjusted vertical space* `\l__enumext_minipage_after_skip`, otherwise we will close the `multicols` environment.

```

2469 \cs_new_protected:Nn \__enumext_after_list:
2470 {
2471     \bool_if:cTF { l__enumext_minipage_active_ \__enumext_level: _bool }
2472     {
2473         \int_compare:nNnT { \g__enumext_minipage_stat_int } = { 1 }
2474         {
2475             \msg_warning:nn { enumext } { missing-miniright }
2476             \miniright
2477         }
2478         \int_gzero:N \g__enumext_minipage_stat_int
2479         \end{\__enumext_mini_env*}
2480         \par\addvspace { \l__enumext_minipage_after_skip }
2481     }
2482     { \__enumext_multicols_stop: }

```

Now apply the `{\code}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```

2483     \__enumext_after_stop_list:
2484     \__enumext_vspace_below:

```

Finally save the *current value* of the counter in `\g__enumext_resume_int` for the `resume` key. If the `save-ans` key is active, it will create the integer variable for the `resume` key, we only have to assign it the value of the current counter.

```

2485     \bool_set_false:N \l__enumext_standar_bool
2486     \int_gset_eq:NN \g__enumext_resume_int \value{enumXi}
2487     \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl _int }
2488     {
2489         \int_gset_eq:cN
2490         { g__enumext_resume_ \l__enumext_store_name_tl _int }
2491         { \value{enumXi} }
2492     }
2493 }

```

(End of definition for `__enumext_after_list:`.)

As we don’t want our check to be executed `check-ans` by levels but on the complete list, we will take it out of the `enumext` environment using the “hook” function `__enumext_after_env:nn`.

```

2494 \__enumext_after_env:nn {enumext}
2495 {
2496     \int_compare:nNnT { \l__enumext_level_int } = { 0 }
2497     {
2498         \bool_if:NT \g__enumext_check_ans_show_bool
2499         {

```



```

2500         \__enumext_check_ans_show:
2501     }
2502     \bool_gset_false:N \__enumext_standar_bool
2503     \bool_gset_false:N \__enumext_check_ans_show_bool
2504     \tl_gclear:N \__enumext_store_name_tl
2505 }
2506 }

```

10.33 The environment keyans

The environment `keyans` also based on lists. The main differences with the `enumext` environment are the *nesting* and the way the *answers* (choice) will be stored and checked, this environment is intended exclusively for “multiple choice questions”.

`keyans` Now we define the environment `keyans` also based on lists.

```

2507 \NewDocumentEnvironment{keyans}{ 0{ } }
2508 {
2509     \__enumext_keyans_safe_exec:
2510     \__enumext_keyans_parse_keys:n {#1}
2511     \__enumext_before_list_v:
2512     \__enumext_start_list:nn
2513     { \tl_use:N \l__enumext_label_v_tl }
2514     {
2515         \__enumext_list_arg_two_v:
2516         \__enumext_before_keys_exec_v:
2517     }
2518     \__enumext_after_args_exec_v:
2519 }
2520 {
2521     \__enumext_keyans_check_ans:nn { item }{ keyans }
2522     \__enumext_stop_list:
2523     \__enumext_after_list_v:
2524 }

```

(End of definition for `keyans`. This function is documented on page 11.)

`__enumext_keyans_safe_exec:`

The `keyans` environment will only be available if the `save-ans` key is active and can only be used at the first level within the `enumext` environment. We do not want the environment to be nested, so we will set a maximum at this point. If the conditions are not met, an error message will be returned.

```

2525 \cs_new_protected:Nn \__enumext_keyans_safe_exec:
2526 {
2527     \bool_if:NF \l__enumext_store_active_bool
2528     {
2529         \msg_error:nnnn { enumext } { wrong-place }{ keyans }{ save-ans }
2530     }
2531     \int_incr:N \l__enumext_keyans_level_int
2532     \bool_set_true:N \l__enumext_keyans_env_bool
2533     % Set false for interfering with enumext nested in keyans (yes, its possible and crayze)
2534     \bool_set_false:N \l__enumext_store_active_bool
2535     \int_compare:nNt { \l__enumext_keyans_level_int } > { 1 }
2536     {
2537         \msg_error:nn { enumext } { keyans-nested }
2538     }
2539     \int_compare:nNt { \l__enumext_level_int } > { 1 }
2540     {
2541         \msg_error:nn { enumext } { keyans-wrong-level }
2542     }
2543 }

```

(End of definition for `__enumext_keyans_safe_exec:`)

`__enumext_keyans_parse_keys:n`

Parse [`<key = val>`] for `keyans` environment.

```

2544 \cs_new_protected:Npn \__enumext_keyans_parse_keys:n #1
2545 {
2546     \keys_set:nn { enumext / keyans } {#1}
2547 }

```

(End of definition for `__enumext_keyans_parse_keys:n`.)

`__enumext_before_list_v:` The function `__enumext_before_list_v:` will add the *vertical spacing above* the environment if the *above* key is active next to the *(code)* defined by the *before* key if it is active.

```

2548 \cs_new_protected:Nn \__enumext_before_list_v:
2549 {
2550   \__enumext_vspace_above_v:
2551   \__enumext_before_args_exec_v:

```

When the *mini-env* key is active it will set the value of the `\l__enumext_minipage_right_v_dim` to be the *width* of the `__enumext_mini_env*` environment on the *left side*, using this value together with the value of the `\l__enumext_minipage_hsep_v_dim` set by the *mini-sep* key, the value of `\l__enumext_minipage_left_v_dim` will be set, which will be the *width* of `__enumextt_mini_env*` environment on the *right side*, always having `\linewidth` as the maximum width between them.

```

2552   \dim_compare:nNnT { \l__enumext_minipage_right_v_dim } > { \c_zero_dim }
2553   {
2554     \dim_set:Nn \l__enumext_minipage_left_v_dim
2555     {
2556       \linewidth - \l__enumext_minipage_right_v_dim - \l__enumext_minipage_hsep_v_dim
2557     }

```

The boolean variable `\l__enumext_minipage_active_v_bool` will be activated and the integer variable `\g__enumext_minipage_stat_int` used by the `\miniright` command will be incremented, then the function `__enumext_keyans_mini_addvspace:` is called and the `__enumext_mini_env*` environment on *left side* will be initialized followed by the *vertical spacing* `\l__enumext_minipage_left_skip`. Here we use the plain TeX macro `\nointerlineskip` to prevent baseline “glue” being added between the next pair of boxes in a *vertical list*.

```

2558     \bool_set_true:N \l__enumext_minipage_active_v_bool
2559     \int_gincr:N \g__enumext_minipage_stat_int
2560     \__enumext_keyans_mini_addvspace:
2561     \nointerlineskip\noindent
2562     \begin{\__enumext_mini_env*}{ \l__enumext_minipage_left_v_dim }
2563   }

```

After these actions, the `__enumext_keyans_multicols_start:` function is called to handle the *multicols* environment.

```

2564   \__enumext_keyans_multicols_start:
2565 }

```

(End of definition for `__enumext_before_list_v:`)

`__enumext_keyans_multicols_start:` The function `__enumext_keyans_multicols_start:` will start the *multicols* environment according to the value passed by the *columns* key.

```

2566 \cs_new_protected:Nn \__enumext_keyans_multicols_start:
2567 {
2568   \int_compare:nNnT { \l__enumext_columns_v_int } > { 1 }
2569   {

```

Set the default value for `\columnsep` when *columns-sep* key is *opt*.

```

2570     \dim_compare:nNnT { \l__enumext_columns_sep_v_dim } = { \c_zero_dim }
2571     {
2572       \dim_set:Nn \l__enumext_columns_sep_v_dim
2573       {
2574         (
2575           \l__enumext_labelwidth_v_dim + \l__enumext_labelsep_v_dim
2576         ) / \l__enumext_columns_v_int
2577         - \l__enumext_listoffset_v_dim
2578       }
2579     }
2580     \dim_set_eq:NN \columnsep \l__enumext_columns_sep_v_dim

```

Then we will set the value of `\multicolsep` and `\columnseprule` equal to zero (we do not want a vertical rule in this environment).

```

2581     \skip_zero:N \multicolsep
2582     \dim_zero:N \columnseprule

```

We will calculate the *vertical spacing* settings for the *multicols* environment using the function `__enumext_keyans_multi_addvspace:` and apply our “*vertical adjust spacing*”, then start the *multicols* environment.

```

2583     \bool_if:NF \l__enumext_minipage_active_v_bool
2584     {
2585       \__enumext_keyans_multi_addvspace:
2586     }
2587     \raggedcolumns

```

```

2588     \begin{multicols}{\l__enumext_columns_v_int }
2589   }
2590 }

```

(End of definition for `__enumext_keyans_multicols_start:`)

`__enumext_keyans_multicols_stop:` The function `__enumext_keyans_multicols_stop:` will stop the `multicols` environment. If the boolean variable `\l__enumext_minipage_active_v_bool` is false (not nested in `__enumext_mini-env*`) we will apply our vertical “adjust” spacing.

```

2591 \cs_new_protected:Nn \__enumext_keyans_multicols_stop:
2592 {
2593   \int_compare:nNt { \l__enumext_columns_v_int } > { 1 }
2594   {
2595     \end{multicols}
2596     \bool_if:NF \l__enumext_minipage_active_v_bool
2597     {
2598       \par\addvspace{ \l__enumext_multicols_below_v_skip }
2599     }
2600   }
2601 }

```

(End of definition for `__enumext_keyans_multicols_stop:`)

`__enumext_after_list_v:` The function `__enumext_after_list_v:` will check the state of the boolean variable `\l__enumext_minipage_active_v_bool`, if it is “true” a small test will be executed to check if we have omitted the use of `\miniright` (the `__enumext_mini-env*` environment has not been closed), then close `__enumext_mini-env*` and add the vertical adjustment space `\l__enumext_minipage_after_skip`, otherwise we will close the `multicols` environment.

```

2602 \cs_new_protected:Nn \__enumext_after_list_v:
2603 {
2604   \bool_if:NTF \l__enumext_minipage_active_v_bool
2605   {
2606     \int_compare:nNt { \g__enumext_minipage_stat_int } = { 1 }
2607     {
2608       \msg_warning:nn { enumext } { missing-miniright }
2609       \miniright
2610     }
2611     \int_gzero:N \g__enumext_minipage_stat_int
2612     \end{\__enumext_mini-env*}
2613     \par\addvspace{ \l__enumext_minipage_after_skip }
2614   }
2615   { \__enumext_keyans_multicols_stop: }

```

Finally we will apply the `{\code}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```

2616   \bool_set_false:N \l__enumext_keyans_env_bool
2617   \__enumext_after_stop_list_v:
2618   \__enumext_vspace_below_v:
2619 }

```

(End of definition for `__enumext_after_list_v:`)


10.34 The environment `keyanspic` and `\anspic`

The `keyanspic` environment is a list-based environment that uses the same configuration for “spacing” and `\label` as the `keyans` environment, but it does not use `\item`.

The contents are passed to the environment by means of the `\anspic` command and are placed inside `minipage` environments, with the `\label` underneath, adjusting widths according to the options passed to the environment.

Again it is necessary to “adjust” the spacing, both vertical and horizontal, to obtain an output like the one shown in the figure 12.

This implementation is adapted from the answer given by Enrico Gregorio in [How to process the body of an environment and divide it by a \macro?](#).

Figure 12: Representation of the `keyanspic` spacing in `enumext`.

10.34.1 The command `\anspic`

`\anspic` The `\anspic` command take three arguments, the starred (*) versions `\anspic*` and `\anspic*[\langle content \rangle]` store the current `\label` next to the `[\langle content \rangle]` if it is present in the `\langle sequence \rangle` and `\langle prop list \rangle` defined by `save-ans` key. This command is used as a replacement for `\item` in the `keyanspic` environment.

```
2620 \NewDocumentCommand \anspic { s o +m }
2621 {
```

We check that the command is active in the `keyanspic` environment only if the `save-ans` key is present, otherwise we return an error.

```
2622   \bool_if:NF \l__enumext_store_active_bool
2623   {
2624     \msg_error:nnnn { enumext } { wrong-place } { keyanspic } { save-ans }
2625   }
2626   \int_compare:nNnT { \l__enumext_level_int } > { 1 }
2627   {
2628     \msg_error:nn { enumext } { keyanspic-wrong-level }
2629   }
2630   \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
2631   {
2632     \msg_error:nnnn { enumext } { command-wrong-place } { anspic } { keyans }
2633   }
```

The three arguments are handled by the function `__enumext_keyans_anspic_code:nnn` and stored in the sequence `\l__enumext_keyans_pic_body_seq` which is processed by the `keyanspic` environment.

```
2634   \seq_put_right:Nn \l__enumext_keyans_pic_body_seq
2635   {
2636     \__enumext_keyans_anspic_code:nnn { #1 } { #2 } { #3 }
2637   }
2638 }
```

(End of definition for `\anspic`. This function is documented on page 12.)

`__enumext_keyans_anspic_code:nnn`

The function `__enumext_keyans_anspic_code:nnn` will be in charge of handling the “counter” and `\label`, which will have the same configuration as the `keyans` environment.

```
2639 \cs_new_protected:Nn \__enumext_keyans_anspic_code:nnn
2640 {
2641   \stepcounter { enumXvi }
2642   #3 \\\
2643   \bool_if:nT { #1 }
2644   {
2645     \__enumext_keyans_addto_prop:n { #2 }
2646     \__enumext_keyans_store_ref:
2647     \__enumext_keyans_addto_seq:n { #2 }
2648     \bool_lazy_or:nnT
2649     { \bool_if_p:N \l__enumext_show_answer_bool }
2650     { \bool_if_p:N \l__enumext_show_position_bool }
2651     {
2652       \tl_set_eq:NN \l__enumext_label_v_tl \l__enumext_label_vi_tl
2653       \__enumext_keyans_show_left:n { #2 }
2654       \tl_set_eq:NN \l__enumext_label_vi_tl \l__enumext_label_v_tl
2655     }
2656   }
2657   \tl_use:N \l__enumext_label_font_style_v_tl
2658   \__enumext_wrapper_label_v:n { \__enumext_label_vi_tl }
2659 }
```

(End of definition for `__enumext_keyans_anspic_code:nnn`.)

10.34.2 The environment keyanspic

`keyanspic` Now we define the environment `keyanspic` based on `list`. The optional argument [*number above, number below*] will determine the number of `minipage` environments that will be above and below separated by `\parsep+\itemsep` within it.

```

2660 \NewDocumentEnvironment{keyanspic}{ o }
2661 {
2662   \__enumext_keyans_pic_safe_exec:
2663   \__enumext_start_list:nn
2664   { }
2665   {
2666     \__enumext_keyans_pic_arg_two:
2667   }

```

We apply the “adjusted” vertical spacing above the environment

```

2668   \vspace { \__enumext_keyans_pic_above_skip }
2669 }

```

If the optional argument is not present, the number of times the `\anspic` command appears will be counted from `\l__enumext_keyans_pic_body_seq` and placed in `minipage` environments on a single line. Finally we check if `\anspic*` has been used, set the counter to zero and apply our “adjusted” vertical space below the environment.

```

2670 {
2671   \tl_if_novalue:nTF { #1 }
2672   {
2673     \__enumext_keyans_pic_do:e { \seq_count:N \l__enumext_keyans_pic_body_seq }
2674   }
2675   { \__enumext_keyans_pic_do:n { #1 } }
2676   \__enumext_stop_list:
2677   \__enumext_keyans_check_ans:nn { anspic } { keyanspic }
2678   \setcounter { enumXvi } { 0 }
2679   \vspace { \__enumext_topsep_v_skip }
2680   %\bool_set_false:N \l__enumext_store_active_bool
2681 }

```

(End of definition for `keyanspic`. This function is documented on page 12.)

`__enumext_keyans_pic_safe_exec:` The function `__enumext_keyans_pic_safe_exec:` check nested and level position inside the `enumext` environment.

```

2682 \cs_new_protected:Nn \__enumext_keyans_pic_safe_exec:
2683 {
2684   \int_incr:N \l__enumext_keyans_pic_level_int
2685   \int_compare:nNnT { \l__enumext_keyans_pic_level_int } > { 1 }
2686   {
2687     \msg_error:nn { enumext } { keyanspic-nested }
2688   }
2689 }

```

(End of definition for `__enumext_keyans_pic_safe_exec:`.)

`__enumext_keyans_pic_skip_abs:N` The function `__enumext_keyans_pic_skip_abs:N` will return a positive value `\parsep`.

```

2690 \cs_new_protected:Npn \__enumext_keyans_pic_skip_abs:N #1
2691 {
2692   \dim_compare:nNnT { #1 } < { 0pt }
2693   { \skip_set:Nn #1 { -#1 } }
2694 }

```

(End of definition for `__enumext_keyans_pic_skip_abs:N`.)

`__enumext_keyans_pic_arg_two:` The function `__enumext_keyans_pic_arg_two:` will be used in the second argument of the `__enumext_start_list:nn` function that defines the `keyanspic` environment, it will handle the setting of spaces.

```

2695 \cs_new_protected:Nn \__enumext_keyans_pic_arg_two:
2696 {

```

The first thing to do is to set the boolean variable `\l__enumext_leftmargin_tmp_v_bool` handled by the `list-indent` key to false, then we copy the definition of the second list argument from the `keyans` environment.

```

2697   \bool_set_false:N \l__enumext_leftmargin_tmp_v_bool
2698   \__enumext_list_arg_two_v:

```

We will add the value of `\itemsep` to `\parsep` which we will use as vertical spacing between the above and below `minipage` environments. and adjust the value of `\leftmargin`, the label and counter are handled directly by the `\anspic` command. Then we make equal to zero `\labelwidth`, `\labelsep`, `\partopsep` and `\itemsep` so that the horizontal and vertical spacing is not affected.

```

2699 \skip_add:Nn \parsep { \itemsep }
2700 \dim_add:Nn \leftmargin { -\labelwidth - \labelsep }
2701 \dim_zero:N \labelwidth
2702 \dim_zero:N \listparindent
2703 \dim_zero:N \labelsep
2704 \skip_zero:N \partopsep
2705 \skip_zero:N \itemsep

```

We set the value of `\l__enumxt_keyans_pic_above_skip` which we will use to apply our “adjust” space above `keyanspic`, finally we call `__enumxt_item_std:w` followed by `\scan_stop:` to prevent the error message returned by \TeX when not using the `\item` command.

```

2706 \__enumxt_keyans_pic_skip_abs:N \parsep
2707 \skip_set:Nn \l__enumxt_keyans_pic_above_skip
2708 {
2709     \box_dp:N \strutbox
2710     + \l__enumxt_topsep_v_skip
2711     - \parsep
2712 }
2713 \__enumxt_item_std:w \scan_stop:
2714 }

```

(End of definition for `__enumxt_keyans_pic_arg_two:.`)

```

\__enumxt_keyans_pic_do:n
\__enumxt_keyans_pic_do:e

```

The optional argument is split by comma and is handled directly by the function `__enumxt_keyans_pic_do:n` and passed to the function `__enumxt_keyans_pic_row:n`.

```

2715 \cs_new_protected:Nn \__enumxt_keyans_pic_do:n
2716 {
2717     \clist_map_function:nN { #1 } \__enumxt_keyans_pic_row:n
2718 }
2719 \cs_generate_variant:Nn \__enumxt_keyans_pic_do:n { e }

```

(End of definition for `__enumxt_keyans_pic_do:n`.)

```
\__enumxt_keyans_pic_row:n
```

The function `__enumxt_keyans_pic_row:n` will set the widths for the `minipage` environments and place the content $\langle stored \rangle$ by `\anspic*` in the `\l__enumxt_keyans_pic_body_seq` sequence inside them.

```

2720 \cs_new_protected:Nn \__enumxt_keyans_pic_row:n
2721 {
2722     \dim_set:Nn \l__enumxt_keyans_pic_width_dim { \linewidth / #1 }
2723     \int_set:Nn \l__enumxt_keyans_pic_above_int { \l__enumxt_keyans_pic_below_int }
2724     \int_set:Nn \l__enumxt_keyans_pic_below_int { \l__enumxt_keyans_pic_above_int + #1 }
2725     \int_step_inline:nnn
2726     { \l__enumxt_keyans_pic_above_int + 1 }
2727     { \l__enumxt_keyans_pic_below_int }
2728     {
2729         \__enumxt_minipage:w [ b ]{ \l__enumxt_keyans_pic_width_dim }
2730         \centering
2731         \seq_item:Nn \l__enumxt_keyans_pic_body_seq { ##1 }
2732         \__enumxt_endminipage:
2733     }
2734     \par
2735 }

```

(End of definition for `__enumxt_keyans_pic_row:n`.)

10.35 The `enumxt*` environment

Generating horizontal list environments is NOT as simple as standard \TeX list environments. The fundamental part of the code is adapted from the `shortlst` package to a more modern version using `expl3`. It is not possible to redefine `\item` and `\makelabel` as in the non starred versions (at least I have not achieved it) and as we will make it behave differently, we have no other option than to define a cascade of functions.

To achieve the horizontal list environment we will capture the `\item` command and the content of this in an plain `lrbox` box using `\makebox` for the `label` and a `minipage` environment for the content passed to `\item`, we will also add the optional argument ($\langle number \rangle$) to `\item` to be able to *join columns* horizontally, in simple terms, we want `\item` to behave in the same way as in the `enumext` environment but adding an optional first argument ($\langle number \rangle$).

10.35.1 Functions for item box width

_enumext_starred_columns_set_vii:

We set the default value for the width of the box containing the content of the items and create `\itemwidth` in a public form.

```

2736 \cs_new_protected:Nn \__enumext_starred_columns_set_vii:
2737 {
2738   \dim_compare:nNnT { \l__enumext_columns_sep_vii_dim } = { \c_zero_dim }
2739   {
2740     \dim_set:Nn \l__enumext_columns_sep_vii_dim
2741     {
2742       ( \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim )
2743       / \l__enumext_columns_vii_int
2744     }
2745   }
2746   \int_set:Nn \l__enumext_tmpa_vii_int { \l__enumext_columns_vii_int - \c_one_int }
2747   \dim_set:Nn \l__enumext_item_width_vii_dim
2748   {
2749     ( \linewidth - \l__enumext_columns_sep_vii_dim * \l__enumext_tmpa_vii_int )
2750     / \l__enumext_columns_vii_int - \l__enumext_labelwidth_vii_dim
2751     - \l__enumext_labelsep_vii_dim
2752   }
2753   \dim_zero_new:N \itemwidth
2754 }

```

(End of definition for _enumext_starred_columns_set_vii:.)

_enumext_starred_joined_item_vii:n

The function `_enumext_starred_joined_item_vii:n` will set the *width* of the box in which the content passed to `\item(<number>)` will be stored together with the value of `\itemwidth`.

```

2755 \cs_new_protected:Npn \__enumext_starred_joined_item_vii:n #1
2756 {
2757   \int_set:Nn \l__enumext_joined_item_vii_int {#1}
2758   \int_compare:nNnT { \l__enumext_joined_item_vii_int } > { \l__enumext_columns_vii_int }
2759   {
2760     \msg_warning:nnee { enumext } { item-joined }
2761     { \int_use:N \l__enumext_joined_item_vii_int }
2762     { \int_use:N \l__enumext_columns_vii_int }
2763     \int_set:Nn \l__enumext_joined_item_vii_int
2764     {
2765       \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int
2766     }
2767   }
2768   \int_compare:nNnT
2769   { \l__enumext_joined_item_vii_int }
2770   >
2771   { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int }
2772   {
2773     \msg_warning:nnee { enumext } { item-joined-columns }
2774     { \int_use:N \l__enumext_joined_item_vii_int }
2775     {
2776       \int_eval:n
2777       { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int }
2778     }
2779     \int_set:Nn \l__enumext_joined_item_vii_int
2780     {
2781       \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int
2782     }
2783   }

```

Only need if #1 >> 1 (default are set before).

```

2784   \int_compare:nNnTF { \l__enumext_joined_item_vii_int } > { \c_one_int }
2785   {
2786     \int_set_eq:NN \l__enumext_joined_item_aux_vii_int \l__enumext_joined_item_vii_int
2787     \int_decr:N \l__enumext_joined_item_aux_vii_int
2788     \int_add:Nn \l__enumext_item_column_pos_vii_int { \l__enumext_joined_item_aux_vii_int }
2789     \int_gadd:Nn \g__enumext_item_count_all_vii_int { \l__enumext_joined_item_aux_vii_int }
2790     \dim_set:Nn \l__enumext_joined_width_vii_dim
2791     {
2792       \l__enumext_item_width_vii_dim * \l__enumext_joined_item_vii_int
2793       + ( \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim
2794         + \l__enumext_columns_sep_vii_dim
2795         ) * \l__enumext_joined_item_aux_vii_int

```



```

2796     }
2797     \dim_set_eq:NN \itemwidth \l__enumext_joined_width_vii_dim
2798   }
2799   {
2800     \dim_set_eq:NN \l__enumext_joined_width_vii_dim \l__enumext_item_width_vii_dim
2801     \dim_set_eq:NN \itemwidth \l__enumext_item_width_vii_dim
2802   }
2803 }

```

(End of definition for `__enumext_starred_joined_item_vii:n`.)

`__enumext_start_mini_vii:` The implementation of the `mini-env` key support is almost identical to the one used in the `enumext` and `keyans` environments, the difference is that the `__enumext_mini_env*` environment on the “right side” is executed “after” closing the environment, so it is necessary to make a global copy of the variable `\l__enumext_minipage_right_vii_dim` in the variable `\g__enumext_minipage_right_vii_dim`.

```

2804 \cs_new_protected:Nn \__enumext_start_mini_vii:
2805 {
2806   \dim_compare:nNnT { \l__enumext_minipage_right_vii_dim } > { \c_zero_dim }
2807   {
2808     \dim_set:Nn \l__enumext_minipage_left_vii_dim
2809     {
2810       \linewidth
2811       - \l__enumext_minipage_right_vii_dim
2812       - \l__enumext_minipage_hsep_vii_dim
2813     }
2814     \bool_set_true:N \l__enumext_minipage_active_vii_bool
2815     \dim_gset_eq:NN
2816       \g__enumext_minipage_right_vii_dim
2817       \l__enumext_minipage_right_vii_dim
2818     \__enumext_mini_addvspace_vii:
2819     \nointerlineskip\noindent
2820     \begin{__enumext_mini_env*}{ \l__enumext_minipage_left_vii_dim }
2821   }
2822 }

```

(End of definition for `__enumext_start_mini_vii:`.)

`__enumext_stop_mini_vii:` The function `__enumext_stop_mini_vii:` closes the `__enumext_mini_env*` environment on the left side, applies `\hfill` and sets the value of the variable `\g__enumext_minipage_active_vii_bool` to true which will be used in the function `__enumext_after_star_env:nn` to execute the `__enumext_mini_env*` on the “right side”.

```

2823 \cs_new_protected:Nn \__enumext_stop_mini_vii:
2824 {
2825   \bool_if:NT \l__enumext_minipage_active_vii_bool
2826   {
2827     \end{__enumext_mini_env*}
2828     \hfill
2829     \bool_gset_true:N \g__enumext_minipage_active_vii_bool
2830   }
2831 }

```

Finally we execute code passed to the `miniright` key stored in the variable `\g__enumext_miniright_code_vii_tl` in the `__enumext_mini_env*` environment on the “right side”.

```

2832 \__enumext_after_env:nn {enumext*}
2833 {
2834   \bool_if:NT \g__enumext_minipage_active_vii_bool
2835   {
2836     \begin{__enumext_mini_env*}{ \g__enumext_minipage_right_vii_dim }
2837     \par\addvspace { \g__enumext_minipage_right_skip }
2838     \bool_if:NF \g__enumext_minipage_center_vii_bool
2839     {
2840       \centering
2841     }
2842     \tl_use:N \g__enumext_miniright_code_vii_tl % the code
2843     \end{__enumext_mini_env*}
2844     \par\addvspace{ \g__enumext_minipage_after_skip }
2845   }
2846   \bool_gset_false:N \g__enumext_minipage_active_vii_bool
2847   \bool_gset_true:N \g__enumext_minipage_center_vii_bool
2848   \tl_gclear:N \g__enumext_miniright_code_vii_tl
2849   \dim_gzero:N \g__enumext_minipage_right_vii_dim
2850 }

```

(End of definition for `__enumext_stop_mini_vii:`.)

`enumext*` First we will generate the environment and we will give a temporary definition to `__enumext_stop_item_tmp_vii:` equal to `\noindent` and next to `\item` equal to `__enumext_start_item_tmp_vii:` which we will redefine later.

```

2851 \NewDocumentEnvironment{enumext*}{o }
2852 {
2853   \__enumext_current_env:
2854   \__enumext_safe_exec_vii:
2855   \__enumext_parse_keys_vii:n {#1}
2856   \__enumext_before_list_vii:
2857   \__enumext_start_store_level_vii:
2858   \__enumext_start_list:nn { }
2859   {
2860     \__enumext_list_arg_two_vii:
2861     \__enumext_before_keys_exec_vii:
2862   }
2863   \__enumext_starred_columns_set_vii:
2864   \item[] \scan_stop:
2865   \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \noindent
2866   \cs_set_eq:NN \item \__enumext_start_item_tmp_vii:
2867 }
2868 {
2869   \__enumext_stop_item_tmp_vii:
2870   \__enumext_remove_extra_parsep_vii:
2871   \__enumext_stop_list:
2872   \__enumext_stop_store_level_vii:
2873   \__enumext_after_list_vii:
2874 }

```

(End of definition for `enumext*`. This function is documented on page 4.)

`__enumext_safe_exec_vii:` First check the maximum nesting level for the `enumext*` environment then set the vars `\l__enumext_starred_bool` and `\g__enumext_starred_bool`.

```

2875 \cs_new_protected:Nn \__enumext_safe_exec_vii:
2876 {
2877   \int_incr:N \l__enumext_level_h_int
2878   \int_compare:nNnT { \l__enumext_level_h_int } > { 1 }
2879   {
2880     \msg_error:nn { enumext } { nested }
2881   }
2882   \bool_set_true:N \l__enumext_starred_bool
2883 }

```

(End of definition for `__enumext_safe_exec_vii:`.)

`__enumext_parse_keys_vii:n` Parse `[<key = val>]` for `enumext*`. If the variable `\l__enumext_store_active_bool` is true it will call the function `__enumext_parse_store_keys_vii:n` and reprocess the keys to pass them to the storage sequence.

```

2884 \cs_new_protected:Npn \__enumext_parse_keys_vii:n #1
2885 {
2886   \tl_if_novalue:nF {#1}
2887   {
2888     \keys_set:nn { enumext / enumext* } {#1}
2889     \bool_if:NT \l__enumext_store_active_bool
2890     {
2891       \__enumext_parse_store_keys_vii:n {#1}
2892     }
2893   }
2894 }

```

(End of definition for `__enumext_parse_keys_vii:n`.)

`__enumext_parse_store_keys_vii:n` The function `__enumext_parse_store_keys_vii:n` searches for the values of the `columns` and `columns-sep` keys in the optional argument in `enumext*` environment as long as the starred versions of the `columns*` and `columns-sep*` keys are not active. The captured values are stored in the variable `\l__enumext_store_opt_vii_tl` which is used by the function `__enumext_store_level_open_vii:`.

```

2895 \cs_new_protected:Npn \__enumext_parse_store_keys_vii:n #1
2896 {

```

```

2897 \bool_if:NF \l__enumext_store_columns_vii_bool
2898 {
2899   \regex_match:nnT { \b columns\b } {#1}
2900   {
2901     \int_set_eq:NN
2902       \l__enumext_store_columns_vii_int
2903       \l__enumext_columns_vii_int
2904     \tl_put_right:Ne \l__enumext_store_opt_vii_tl
2905       {
2906         columns = \exp_not:V \l__enumext_store_columns_vii_int ,
2907       }
2908   }
2909 }
2910 \bool_if:NF \l__enumext_store_columns_sep_vii_bool
2911 {
2912   \regex_match:nnT { \b columns-sep\b } {#1}
2913   {
2914     \dim_set_eq:NN
2915       \l__enumext_store_columns_sep_vii_dim
2916       \l__enumext_columns_sep_vii_dim
2917     \tl_put_right:Ne \l__enumext_store_opt_vii_tl
2918       {
2919         columns-sep = \exp_not:V \l__enumext_store_columns_sep_vii_dim,
2920       }
2921   }
2922 }
2923 }

```

(End of definition for \l__enumext_parse_store_keys_vii:n.)

`__enumext_before_list_vii:` The function `__enumext_before_list_vii:` will add the vertical spacing on the environment if the `above` key is active next to the `{\code}` defined by the `before*` key if it is active, the call the function `__enumext_start_mini_vii:` handle by `mini-env`.

```

2924 \cs_new_protected:Nn \__enumext_before_list_vii:
2925 {
2926   \__enumext_vspace_above_vii:
2927   \__enumext_check_ans_exec: % need by chek-ans
2928   \__enumext_before_args_exec_vii:
2929   \__enumext_start_mini_vii:
2930 }

```

(End of definition for __enumext_before_list_vii:.)

`__enumext_after_list_vii:` The function `__enumext_after_list:` first call the function `__enumext_stop_mini_vii:`, then apply the `{\code}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present. Finally set false the vars `\g__enumext_starred_bool` and `\l__enumext_starred_bool`, save the *current value* of the counter in `\g__enumext_resume_vii_int` for the `resume` key. If the `save-ans` key is active, it will create the integer variable for the `resume` key, we only have to assign it the value of the current counter.

```

2931 \cs_new_protected:Nn \__enumext_after_list_vii:
2932 {
2933   \__enumext_stop_mini_vii:
2934   \__enumext_after_stop_list_vii:
2935   \__enumext_vspace_below_vii:
2936   \int_gset_eq:NN \g__enumext_resume_vii_int \value{enumXvii}
2937   \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl _int }
2938   {
2939     \int_gset_eq:cN
2940       { g__enumext_resume_ \l__enumext_store_name_tl _int }
2941       { \value{enumXvii} }
2942   }
2943   \bool_lazy_and:nnT
2944     { \bool_if_p:N \g__enumext_starred_bool }
2945     { \bool_if_p:N \l__enumext_check_ans_bool }
2946     {
2947       \bool_gset_true:N \g__enumext_check_ans_show_h_bool
2948       \tl_gset:NV \g__enumext_store_name_tl \l__enumext_store_name_tl
2949     }
2950   %\bool_gset_false:N \g__enumext_starred_bool
2951   \bool_set_false:N \l__enumext_starred_bool
2952 }

```

(End of definition for `__enumext_after_list_vii:`)

`__enumext_start_store_level_vii:`
`__enumext_stop_store_level_vii:`

The `__enumext_start_store_level_vii:` and `__enumext_stop_store_level_vii:` functions activate the level saving mechanism for storage in *(sequence)* of the `\anskey` command if `enumext*` are nested in `enumext`.

```
2953 \cs_new_protected:Nn \__enumext_start_store_level_vii:
2954 {
2955   \bool_if:NT \l__enumext_store_active_bool
2956   {
2957     \int_compare:nNnT { \l__enumext_level_int } > { \c_zero_int }
2958     {
2959       \__enumext_store_level_open_vii:
2960     }
2961   }
2962 }
2963 \cs_new_protected:Nn \__enumext_stop_store_level_vii:
2964 {
2965   \bool_if:NT \l__enumext_store_active_bool
2966   {
2967     \int_compare:nNnT { \l__enumext_level_int } > { \c_zero_int }
2968     {
2969       \__enumext_store_level_close_vii:
2970     }
2971   }
2972 }
```

(End of definition for `__enumext_start_store_level_vii:` and `__enumext_stop_store_level_vii:`)

10.35.2 The command `\item` in `enumext*`

`__enumext_start_item_tmp_vii:`

First we will call the function `__enumext_stop_item_tmp_vii:` that we will redefine later, we will increment the value of `\l__enumext_item_column_pos_vii_int` that will count the item's by rows and the value of `\g__enumext_item_count_all_vii_int` that will count the total of item's in the environment. After that we will call the function `__enumext_item_peek_args_vii:` that will handle the arguments passed to `\item`.

```
2973 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_vii:
2974 {
2975   \__enumext_stop_item_tmp_vii:
2976   \int_incr:N \l__enumext_item_column_pos_vii_int
2977   \int_gincr:N \g__enumext_item_count_all_vii_int
2978   \__enumext_item_peek_args_vii:
2979 }
```

(End of definition for `__enumext_start_item_tmp_vii:`)

`__enumext_item_peek_args_vii:`

The function `__enumext_item_peek_args_vii:` will handle the `\item(<number>)`. Look for the argument “(”, if it is present we will call the function `__enumext_joined_item_vii:w (<number>)`, which is in charge of joining the item's in the same row, in case they are not present we will set the default value (1).

```
2980 \cs_new_protected:Nn \__enumext_item_peek_args_vii:
2981 {
2982   \peek_meaning:NTF (
2983     { \__enumext_joined_item_vii:w }
2984     { \__enumext_joined_item_vii:w (1) }
2985   }
```

(End of definition for `__enumext_item_peek_args_vii:`)

`__enumext_joined_item_vii:w`

The function `__enumext_joined_item_vii:w` will first call the function `__enumext_starred_joined_item_vii:n` in charge of setting the *width* of the box that will store the content passed to `\item`. Then we will look for the argument “*”, if it is present we will call the function `__enumext_starred_item_vii:w` otherwise we will call the function `__enumext_standard_item_vii:w`.

```
2986 \cs_new_protected:Npn \__enumext_joined_item_vii:w (#1)
2987 {
2988   \__enumext_starred_joined_item_vii:n {#1}
2989   \peek_meaning_remove:NTF *
2990     { \__enumext_starred_item_vii:w }
2991     { \__enumext_standard_item_vii:w }
2992 }
```

(End of definition for `__enumext_joined_item_vii:w`)

__enumext_standard_item_vii:w

The function __enumext_standard_item_vii:w will first look for the argument “[”, if present it will set the state of the variable \l__enumext_wrap_label_opt_vii_bool equal to the state of the variable \l__enumext_wrap_label_opt_vii_bool handled by the key `wrap-label*` and finally execute the *non-enumerated* version `\item[⟨custom⟩]` by means of the function __enumext_start_item_vii:w, otherwise we will set the value of the variable \l__enumext_wrap_label_vii_bool handled by the `wrap-label` key to true and set the switch \if@noitemarg to true to execute the enumerated version of `\item` by means of the function __enumext_start_item_vii:w [\l__enumext_label_vii_tl].

```

2993 \cs_new_protected:Npn \__enumext_standard_item_vii:w
2994 {
2995   \bool_set_false:N \l__enumext_item_starred_vii_bool
2996   \peek_meaning:NTF [
2997     {
2998       \bool_set_eq:NN
2999         \l__enumext_wrap_label_vii_bool
3000         \l__enumext_wrap_label_opt_vii_bool
3001       \__enumext_start_item_vii:w
3002     }
3003     {
3004       \bool_set_true:N \l__enumext_wrap_label_vii_bool
3005       \legacy_if_set_true:n { @noitemarg }
3006       \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
3007     }
3008   }

```

(End of definition for __enumext_standard_item_vii:w.)

__enumext_starred_item_vii:w
 __enumext_starred_item_vii_aux_i:w
 __enumext_starred_item_vii_aux_ii:w
 __enumext_starred_item_vii_aux_iii:w

The function __enumext_starred_item_vii:w together with the specified auxiliary functions `aux_i:w`, `aux_ii:w`, and `aux_iii:w` execute `\item*`, `\item*[⟨symbol⟩]` and `\item*[⟨symbol⟩][⟨offset⟩]`.

```

3009 \cs_new_protected:Npn \__enumext_starred_item_vii:w
3010 {
3011   \bool_set_true:N \l__enumext_item_starred_vii_bool
3012   \bool_set_true:N \l__enumext_wrap_label_vii_bool
3013   \peek_meaning:NTF [
3014     { \__enumext_starred_item_vii_aux_i:w }
3015     { \__enumext_starred_item_vii_aux_ii:w }
3016   }
3017   \cs_new_protected:Npn \__enumext_starred_item_vii_aux_i:w [#1]
3018   {
3019     \tl_gset:Nn \g__enumext_item_symbol_aux_vii_tl {#1}
3020     \__enumext_starred_item_vii_aux_ii:w
3021   }
3022   \cs_new_protected:Npn \__enumext_starred_item_vii_aux_ii:w
3023   {
3024     \peek_meaning:NTF [
3025       { \__enumext_starred_item_vii_aux_iii:w }
3026       {
3027         \dim_set_eq:NN
3028           \l__enumext_item_symbol_sep_vii_dim
3029           \l__enumext_labelsep_vii_dim
3030         \legacy_if_set_true:n { @noitemarg }
3031         \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
3032       }
3033     }
3034   \cs_new_protected:Npn \__enumext_starred_item_vii_aux_iii:w [#1]
3035   {
3036     \dim_set:Nn \l__enumext_item_symbol_sep_vii_dim {#1}
3037     \legacy_if_set_true:n { @noitemarg }
3038     \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
3039   }

```

(End of definition for __enumext_starred_item_vii:w and others.)

10.35.3 Real definition of \item in enumext*

__enumext_start_item_vii:w

The functions __enumext_start_item_vii:w and __enumext_stop_item_vii: executing the true definition of `\item` inside the `enumext*` environment.

The first thing we will do is set the value of __enumext_stop_item_tmp_vii: equal to the value of __enumext_stop_item_vii: which we will define later and add the `hyperref` compatible `enumxvii` counter, after that we will start capturing the item content in a box. Here need setting the \if@hyper@item

switch to “true” for `hyperref` compatible. The explanation for this is given by the master Heiko Oberdiek on `\refstepcounter{enumi}` twice (or more) creates destination with the same identifier.

```

3040 \cs_new_protected_nopar:Npn \__enumext_start_item_vii:w [#1]
3041 {
3042   \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \__enumext_stop_item_vii:
3043   \legacy_if:nT { @noitemarg }
3044   {
3045     \legacy_if_set_false:n { @noitemarg }
3046     \legacy_if:nT { @nmbrlist }
3047     {
3048       \bool_if:NT \l__enumext_hyperref_bool
3049       {
3050         \legacy_if_set_true:n { @hyper@item }
3051       }
3052       \refstepcounter{enumXvii}
3053       \bool_if:NT \l__enumext_check_ans_bool
3054       {
3055         \int_gincr:N \g__enumext_count_item_number_int
3056       }
3057     }
3058   }

```

Here we start capturing `\item` and its contents into a group using the plain form of the `lrbox` environment. If the state of the variable `\l__enumext_footnotes_key_bool` is false, we will redefine the command `\footnote`, followed by printing the $\langle symbol \rangle$ defined for `\item*` if it is present and open a new group inside which we execute `font key` next to `\item` and the keys `wrap-label`, `wrap-label*`, `align`, close the group and execute the key `labelsep` and then the key `first`. Finally we open the `minipage` environment and execute the `listparindent` key which will be equal to `\parindent`, the `parsep` key which will be equal to `\parskip` and the `itemindent` key.

```

3059   \group_begin:
3060   \lrbox{ \l__enumext_item_text_vii_box }
3061   \bool_if:NF \l__enumext_footnotes_key_bool
3062   {
3063     \__enumext_renew_footnote:
3064   }
3065   \bool_if:NT \l__enumext_item_starred_vii_bool
3066   {
3067     \tl_if_blank:VT \g__enumext_item_symbol_aux_vii_tl
3068     {
3069       \tl_gset_eq:NN
3070       \g__enumext_item_symbol_aux_vii_tl \l__enumext_item_symbol_vii_tl
3071     }
3072     \mode_leave_vertical:
3073     \skip_horizontal:n { -\l__enumext_item_symbol_sep_vii_dim }
3074     \makebox[ 0pt ][ r ]{ \g__enumext_item_symbol_aux_vii_tl }
3075     \skip_horizontal:N \l__enumext_item_symbol_sep_vii_dim
3076     \tl_gclear:N \g__enumext_item_symbol_aux_vii_tl
3077   }
3078   \group_begin:
3079   \tl_use:N \l__enumext_label_font_style_vii_tl
3080   \bool_if:NTF \l__enumext_wrap_label_vii_bool
3081   {
3082     \makebox[ \l__enumext_labelwidth_vii_dim ][ \l__enumext_align_label_vii_str ]
3083     { \__enumext_wrapper_label_vii:n {#1} }
3084   }
3085   {
3086     \makebox[ \l__enumext_labelwidth_vii_dim ][ \l__enumext_align_label_vii_str ]{ #1 }
3087   }
3088   \group_end:
3089   \skip_horizontal:N \l__enumext_labelsep_vii_dim
3090   \tl_use:N \l__enumext_after_list_args_vii_tl
3091   \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_vii_dim }
3092   \skip_set_eq:NN \parindent \l__enumext_listparindent_vii_dim
3093   \skip_set_eq:NN \parskip \l__enumext_parsep_vii_skip
3094   \tl_use:N \l__enumext_fake_item_indent_vii_tl
3095 }

```

(End of definition for `__enumext_start_item_vii:w`.)

`__enumext_stop_item_vii:` The function `__enumext_stop_item_vii:` shall terminate with the capture of `\item` and its $\langle contents \rangle$. Close the environments `minipage`, `lrbox` and the group. Then we only have to set the width of the box

and print it next to `\footnote`, and add the horizontal and vertical separation between the boxes.

```

3096 \cs_new_protected_nopar:Nn \__enumext_stop_item_vii:
3097 {
3098     \__enumext_endminipage:
3099     \endlrbox
3100     \group_end:
3101     \box_set_wd:Nn \l__enumext_item_text_vii_box
3102     {
3103         \l__enumext_joined_width_vii_dim
3104         + \l__enumext_labelwidth_vii_dim
3105         + \l__enumext_labelsep_vii_dim
3106     }
3107     \int_set:Nn \hbadness { 10000 }
3108     \box_use:N \l__enumext_item_text_vii_box
3109     \bool_if:NF \l__enumext_footnotes_key_bool
3110     {
3111         \__enumext_print_footnote:
3112     }
3113     \int_compare:nNnTF { \l__enumext_item_column_pos_vii_int } = { \l__enumext_columns_vii_int }
3114     {
3115         \par\noindent
3116         \int_zero:N \l__enumext_item_column_pos_vii_int
3117     }
3118     { \hspace{ \l__enumext_columns_sep_vii_dim } }
3119 }

```

(End of definition for `__enumext_stop_item_vii:`.)

`__enumext_remove_extra_parsep_vii:`

Finally we will remove the vertical space equal to `\parsep` when the total number of items is divisible by the number of items in the last row of the environment.

```

3120 \cs_new_protected:Nn \__enumext_remove_extra_parsep_vii:
3121 {
3122     \int_compare:nNnT
3123     {
3124         \int_mod:nn { \g__enumext_item_count_all_vii_int } { \l__enumext_columns_vii_int }
3125     }
3126     =
3127     { \c_zero_int }
3128     {
3129         \par
3130         \vspace{ -\l__enumext_itemsep_vii_skip }
3131         \int_gzero:N \g__enumext_item_count_all_vii_int
3132     }
3133 }

```

(End of definition for `__enumext_remove_extra_parsep_vii:`.)

As we don't want our check to be executed `check-ans` by levels but on the complete list, we will take it out of the `enumext*` environment using the “hook” function `__enumext_after_env:nn`.

```

3134 \__enumext_after_env:nn {enumext*}
3135 {
3136     \int_compare:nNnT { \l__enumext_level_int } = { 0 }
3137     {
3138         \bool_if:NT \g__enumext_check_ans_show_h_bool
3139         {
3140             \__enumext_check_ans_show:
3141         }
3142         \bool_gset_false:N \g__enumext_starred_bool
3143         \bool_gset_false:N \g__enumext_check_ans_show_h_bool
3144         \tl_gclear:N \g__enumext_store_name_tl
3145     }
3146 }

```

10.36 The keyans* environment

10.36.1 Functions for item box width

`__enumext_starred_columns_set_viii:`

We set the default value for the width of the box containing the content of the items and create `\itemwidth` in a public form.

```

3147 \cs_new_protected:Nn \__enumext_starred_columns_set_viii:
3148 {
3149     \dim_compare:nNnT { \l__enumext_columns_sep_viii_dim } = { \c_zero_dim }

```



```

3150     {
3151         \dim_set:Nn \l__enumext_columns_sep_viii_dim
3152         {
3153             ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim )
3154             / \l__enumext_columns_viii_int
3155         }
3156     }
3157     \int_set:Nn \l__enumext_tmpa_viii_int { \l__enumext_columns_viii_int - \c_one_int }
3158     \dim_set:Nn \l__enumext_item_width_viii_dim
3159     {
3160         ( \linewidth - \l__enumext_columns_sep_viii_dim * \l__enumext_tmpa_viii_int )
3161         / \l__enumext_columns_viii_int - \l__enumext_labelwidth_viii_dim
3162         - \l__enumext_labelsep_viii_dim
3163     }
3164     \dim_zero_new:N \itemwidth
3165 }

```

(End of definition for __enumext_starred_columns_set_viii:.)

__enumext_starred_joined_item_viii:n

The function __enumext_starred_joined_item_viii:n will set the *width* of the box in which the content passed to \item⟨⟨*number*⟩⟩ will be stored together with the value of \itemwidth.

```

3166 \cs_new_protected:Npn \__enumext_starred_joined_item_viii:n #1
3167 {
3168     \int_set:Nn \l__enumext_joined_item_viii_int {#1}
3169     \int_compare:nNnT { \l__enumext_joined_item_viii_int } > { \l__enumext_columns_viii_int }
3170     {
3171         \msg_warning:nnee { enumext } { item-joined }
3172         { \int_use:N \l__enumext_joined_item_viii_int }
3173         { \int_use:N \l__enumext_columns_viii_int }
3174         \int_set:Nn \l__enumext_joined_item_viii_int
3175         {
3176             \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int
3177         }
3178     }
3179     \int_compare:nNnT
3180     { \l__enumext_joined_item_viii_int }
3181     >
3182     { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int }
3183     {
3184         \msg_warning:nnee { enumext } { item-joined-columns }
3185         { \int_use:N \l__enumext_joined_item_viii_int }
3186         {
3187             \int_eval:n
3188             { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int }
3189         }
3190         \int_set:Nn \l__enumext_joined_item_viii_int
3191         {
3192             \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int
3193         }
3194     }
3195     \int_compare:nNnTF { \l__enumext_joined_item_viii_int } > { \c_one_int }
3196     {
3197         \int_set_eq:NN \l__enumext_joined_item_aux_viii_int \l__enumext_joined_item_viii_int
3198         \int_decr:N \l__enumext_joined_item_aux_viii_int
3199         \int_add:Nn \l__enumext_item_column_pos_viii_int { \l__enumext_joined_item_aux_viii_int }
3200         \int_gadd:Nn \g__enumext_item_count_all_viii_int { \l__enumext_joined_item_aux_viii_int }
3201         \dim_set:Nn \l__enumext_joined_width_viii_dim
3202         {
3203             \l__enumext_item_width_viii_dim * \l__enumext_joined_item_viii_int
3204             + ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim
3205                 + \l__enumext_columns_sep_viii_dim
3206                 ) * \l__enumext_joined_item_aux_viii_int
3207         }
3208         \dim_set_eq:NN \itemwidth \l__enumext_joined_width_viii_dim
3209     }
3210     {
3211         \dim_set_eq:NN \l__enumext_joined_width_viii_dim \l__enumext_item_width_viii_dim
3212         \dim_set_eq:NN \itemwidth \l__enumext_item_width_viii_dim
3213     }
3214 }

```

(End of definition for `__enumext_starred_joined_item_viii:n`)

`__enumext_start_mini_viii:` The implementation of the `mini-env` key is identical to the one used in the `enumext*` environment.

```

3215 \cs_new_protected:Nn \__enumext_start_mini_viii:
3216 {
3217   \dim_compare:nNt { \__enumext_minipage_right_viii_dim } > { \c_zero_dim }
3218   {
3219     \dim_set:Nn \__enumext_minipage_left_viii_dim
3220     {
3221       \linewidth
3222       - \__enumext_minipage_right_viii_dim
3223       - \__enumext_minipage_hsep_viii_dim
3224     }
3225     \bool_set_true:N \__enumext_minipage_active_viii_bool
3226     \dim_gset_eq:NN
3227       \__enumext_minipage_right_viii_dim
3228       \__enumext_minipage_right_viii_dim
3229     \__enumext_mini_addvspace_viii:
3230     \nointerlineskip\noindent
3231     \begin{__enumext_mini_env*}{ \__enumext_minipage_left_viii_dim }
3232   }
3233 }
3234 \cs_new_protected:Nn \__enumext_stop_mini_viii:
3235 {
3236   \bool_if:NT \__enumext_minipage_active_viii_bool
3237   {
3238     \end{__enumext_mini_env*}
3239     \hfill
3240     \bool_gset_true:N \__enumext_minipage_active_viii_bool
3241   }
3242 }
3243 \__enumext_after_env:nn {keyans*}
3244 {
3245   \bool_if:NT \__enumext_minipage_active_viii_bool
3246   {
3247     \begin{__enumext_mini_env*}{ \__enumext_minipage_right_viii_dim }
3248     \par\addvspace { \__enumext_minipage_right_skip }
3249     \bool_if:NF \__enumext_minipage_center_viii_bool
3250     {
3251       \centering
3252     }
3253     \tl_use:N \__enumext_miniright_code_viii_tl % the code
3254     \end{__enumext_mini_env*}
3255     \par\addvspace{ \__enumext_minipage_after_skip }
3256   }
3257   \bool_gset_false:N \__enumext_minipage_active_viii_bool
3258   \bool_gset_true:N \__enumext_minipage_center_viii_bool
3259   \tl_gclear:N \__enumext_miniright_code_viii_tl
3260   \dim_gzero:N \__enumext_minipage_right_viii_dim
3261 }

```

(End of definition for `__enumext_start_mini_viii:` and `__enumext_stop_mini_viii:.`)

keyans* First we will generate the environment and we will give a temporary definition to `__enumext_stop_item_tmp_viii:` equal to `\noindent` and next to `\item` equal to `__enumext_start_item_tmp_viii:` which we will redefine later.

```

3262 \NewDocumentEnvironment{keyans*}{ o }
3263 {
3264   \__enumext_safe_exec_viii:
3265   \__enumext_parse_keys_viii:n {#1}
3266   \__enumext_before_list_viii:
3267   \__enumext_start_list:nn { }
3268   {
3269     \__enumext_list_arg_two_viii:
3270     \__enumext_before_keys_exec_viii:
3271   }
3272   \__enumext_starred_columns_set_viii:
3273   \item[] \scan_stop:
3274   \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \noindent
3275   \cs_set_eq:NN \item \__enumext_start_item_tmp_viii:
3276 }

```

```

3277 {
3278   \__enumext_stop_item_tmp_viii:
3279   \__enumext_remove_extra_parsep_viii:
3280   \__enumext_keyans_check_ans:nn { item }{ keyans* }
3281   \__enumext_stop_list:
3282   \__enumext_after_list_viii:
3283 }

```

(End of definition for `keyans*`. This function is documented on page 11.)

`__enumext_safe_exec_viii:` First check the maximum nesting level for the `keyans*` environment.

```

3284 \cs_new_protected:Nn \__enumext_safe_exec_viii:
3285 {
3286   \int_incr:N \l__enumext_keyans_level_h_int
3287   \int_compare:nNnT { \l__enumext_keyans_level_h_int } > { 1 }
3288   {
3289     \msg_error:nn { enumext } { nested }
3290   }
3291   % Set false for interfering with enumext nested in keyans* (yes, its possible and crayze)
3292   \bool_set_false:N \l__enumext_store_active_bool
3293   \int_compare:nNnT { \l__enumext_level_int } > { 1 }
3294   {
3295     \msg_error:nn { enumext } { keyans-wrong-level }
3296   }
3297 }

```

(End of definition for `__enumext_safe_exec_viii:`.)

`__enumext_parse_keys_viii:n` Parse [`<key = val>`] for `keyans*`.

```

3298 \cs_new_protected:Npn \__enumext_parse_keys_viii:n #1
3299 {
3300   \tl_if_novalue:nF {#1}
3301   {
3302     \keys_set:nn { enumext / keyans* } {#1}
3303   }
3304 }

```

(End of definition for `__enumext_parse_keys_viii:n`.)

`__enumext_before_list_viii:` The function `__enumext_before_list_viii:` will add the vertical spacing on the environment if the `above` key is active next to the `{<code>}` defined by the `before*` key if it is active, the call the function `__enumext_start_mini_viii:` handle by `mini-env`.

```

3305 \cs_new_protected:Nn \__enumext_before_list_viii:
3306 {
3307   \__enumext_vspace_above_viii:
3308   \__enumext_before_args_exec_viii:
3309   \__enumext_start_mini_viii:
3310 }

```

(End of definition for `__enumext_before_list_viii:`.)

`__enumext_after_list_viii:` The function `__enumext_after_list:` first call the function `__enumext_stop_mini_viii:`, then apply the `{<code>}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```

3311 \cs_new_protected:Nn \__enumext_after_list_viii:
3312 {
3313   \__enumext_stop_mini_viii:
3314   \__enumext_after_stop_list_viii:
3315   \__enumext_vspace_below_viii:
3316 }

```

(End of definition for `__enumext_after_list_viii:`.)

10.36.2 The command `\item` in `keyans*`

The idea here is to make the `\item` command behave in the same way as in the `keyans` environment with the difference of the optional argument (`<number>`) which works in the same way as in the `enumext*` environment. In simple terms we want to store the `<label>` next to the `[<content>]` if it is present in the `<sequence>` and `<prop list>` defined by `save-ans` key for `\item*`, `\item* [<content>]`, `\item(<number>)*` and `\item(<number>)* [<content>]` commands.

`__enumext_start_item_tmp_viii:`

First we will call the function `__enumext_stop_item_tmp_viii:` that we will redefine later, we will increment the value of `\l__enumext_item_column_pos_viii_int` that will count the item's by rows and the value of `\g__enumext_item_count_all_viii_int` that will count the total of item's in the environment. After that we will call the function `__enumext_item_peek_args_viii:` that will handle the arguments passed to `\item`.

```
3317 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_viii:
3318 {
3319     \__enumext_stop_item_tmp_viii:
3320     \int_incr:N \l__enumext_item_column_pos_viii_int
3321     \int_gincr:N \g__enumext_item_count_all_viii_int
3322     \__enumext_item_peek_args_viii:
3323 }
```

(End of definition for `__enumext_start_item_tmp_viii:`.)

`__enumext_item_peek_args_viii:`

The function `__enumext_item_peek_args_viii:` will handle the `\item(<number>)`. Look for the argument “(”, if it is present we will call the function `__enumext_joined_item_viii:w (<number>)`, which is in charge of joining the item's in the same row, in case they are not present we will set the default value (1).

```
3324 \cs_new_protected:Nn \__enumext_item_peek_args_viii:
3325 {
3326     \peek_meaning:NTF (
3327         { \__enumext_joined_item_viii:w }
3328         { \__enumext_joined_item_viii:w (1) }
3329     }
```

(End of definition for `__enumext_item_peek_args_viii:`.)

`__enumext_joined_item_viii:w`

The function `__enumext_joined_item_viii:w` will first call the function `__enumext_starred_joined_item_viii:n` in charge of setting the *width* of the box that will store the content passed to `\item`. Then we will look for the argument “*”, if it is present we will call the function `__enumext_starred_item_viii:w` otherwise we will call the function `__enumext_standard_item_viii:w`.

```
3330 \cs_new_protected:Npn \__enumext_joined_item_viii:w (#1)
3331 {
3332     \__enumext_starred_joined_item_viii:n {#1}
3333     \peek_meaning_remove:NTF *
3334     { \__enumext_starred_item_viii:w }
3335     { \__enumext_standard_item_viii:w }
3336 }
```

(End of definition for `__enumext_joined_item_viii:w`.)

`__enumext_standard_item_viii:w`

The function `__enumext_standard_item_viii:w` will first look for the argument “[”, if present it will set the state of the variable `\l__enumext_wrap_label_opt_viii_bool` equal to the state of the variable `\l__enumext_wrap_label_opt_viii_bool` handled by the key `wrap-label*` and finally execute the *non-enumerated* version `\item[<custom>]` by means of the function `__enumext_start_item_viii:w`, otherwise we will set the value of the variable `\l__enumext_wrap_label_viii_bool` handled by the `wrap-label` key to true and set the switch `\if@noitemarg` to true to execute the enumerated version of `\item` by means of the function `__enumext_start_item_viii:w [__enumext_label_viii_tl]`.

```
3337 \cs_new_protected:Npn \__enumext_standard_item_viii:w
3338 {
3339     \bool_set_false:N \l__enumext_item_starred_viii_bool
3340     \peek_meaning:NTF [
3341     {
3342         \bool_set_eq:NN
3343         \l__enumext_wrap_label_viii_bool
3344         \l__enumext_wrap_label_opt_viii_bool
3345         \__enumext_start_item_viii:w
3346     }
3347     {
3348         \bool_set_true:N \l__enumext_wrap_label_viii_bool
```

```

3349         \legacy_if_set_true:n { @noitemarg }
3350         \__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ]
3351     }
3352 }

```

(End of definition for __enumext_standard_item_viii:w.)

```

\__enumext_starred_item_viii:w
\__enumext_starred_item_viii_aux_i:w
\__enumext_starred_item_viii_aux_ii:w

```

The function __enumext_starred_item_viii:w together with the specified auxiliary functions `aux_i:w` and `aux_ii:w` execute `\item*` and `\item*[\langle content \rangle]`.

```

3353 \cs_new_protected:Npn \__enumext_starred_item_viii:w
3354 {
3355     \bool_set_true:N \l__enumext_item_starred_viii_bool
3356     \bool_set_true:N \l__enumext_wrap_label_viii_bool
3357     \peek_meaning:NTF [
3358         { \__enumext_starred_item_viii_aux_i:w }
3359         { \__enumext_starred_item_viii_aux_ii:w }
3360     }

```

The optional argument will be captured in the variables `\l__enumext_keyans_tmpa_tl` and `\l__enumext_keyans_tmpp_tl` which we will use later for the implementation of the `show-ans` and `show-pos` keys together with the stored in `\sequence` and `\prop list`.

```

3361 \cs_new_protected:Npn \__enumext_starred_item_viii_aux_i:w [#1]
3362 {
3363     \tl_clear:N \l__enumext_store_keyans_label_tl
3364     \tl_if_no_value:nF { #1 }
3365     {
3366         \tl_set:Nx \l__enumext_keyans_tmpa_tl { \c_space_tl [#1] }
3367         \tl_set:Nx \l__enumext_keyans_tmpp_tl { \c_space_tl #1 }
3368     }
3369     \__enumext_starred_item_viii_aux_ii:w
3370 }
3371 \cs_new_protected:Npn \__enumext_starred_item_viii_aux_ii:w
3372 {
3373     \legacy_if_set_true:n { @noitemarg }
3374     \__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ]
3375 }

```

(End of definition for __enumext_starred_item_viii:w, __enumext_starred_item_viii_aux_i:w, and __enumext_starred_item_viii_aux_ii:w.)

```
\__enumext_starred_item_exec:
```

The function __enumext_starred_item_exec: will be in charge of storing the current `\label` for `\item*` followed by the `[\langle content \rangle]` for `\item*[\langle content \rangle]` if present in the `\sequence` and `\prop list` set by the `save-ans` key. In this same function the keys `show-ans`, `show-pos` and `store-ref` are implemented.

```

3376 \cs_new_protected:Nn \__enumext_starred_item_exec:
3377 {
3378     \tl_put_left:Nx \l__enumext_store_keyans_label_tl { \l__enumext_label_viii_tl }
3379     \tl_if_blank:VF \l__enumext_keyans_tmpp_tl
3380     {
3381         \tl_put_right:Nx \l__enumext_store_keyans_label_tl { \l__enumext_keyans_tmpp_tl }
3382     }
3383     \__enumext_store_addto_prop:V \l__enumext_store_keyans_label_tl
3384     \__enumext_keyans_store_ref:
3385     \tl_put_left:Nx \l__enumext_store_keyans_label_tl { \item }
3386     \__enumext_keyans_addto_seq_link:
3387     \bool_if:NT \l__enumext_show_answer_bool
3388     {
3389         \tl_if_blank:VF \l__enumext_keyans_tmpa_tl
3390         {
3391             \tl_put_right:Nx \l__enumext_label_viii_tl { \l__enumext_keyans_tmpa_tl }
3392             \__enumext_label_width_by_box:Nn \l__enumext_keyans_tmpa_dim { \l__enumext_keyans_tmpp_dim }
3393             \dim_add:Nn \l__enumext_fake_item_indent_viii_dim { \l__enumext_keyans_tmpa_dim }
3394         }
3395         \__enumext_print_keyans_box:NN \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
3396     }
3397     \bool_if:NT \l__enumext_show_position_bool
3398     {
3399         \tl_set:Nx \l__enumext_mark_answer_sym_tl
3400         {
3401             \group_begin:
3402             \exp_not:N \normalfont

```

```

3403         \exp_not:N \footnotesize [ \int_eval:n
3404         {
3405             \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
3406         }
3407     ]
3408     \group_end:
3409 }
3410 \tl_if_blank:VF \l__enumext_keyans_tmpa_tl
3411 {
3412     \tl_put_right:Ne \l__enumext_label_viii_tl { \l__enumext_keyans_tmpa_tl }
3413     \__enumext_label_width_by_box:Nn \l__enumext_keyans_tmpa_dim { \l__enumext_keyans_tmpa_dim }
3414     \dim_add:Nn \l__enumext_fake_item_indent_viii_dim { \l__enumext_keyans_tmpa_dim }
3415 }
3416 \__enumext_print_keyans_box:NN \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
3417 }
3418 }

```

(End of definition for `__enumext_starred_item_exec:`)

Real definition of `\item` in `keyans*`

The implementation at this point is very similar to that of the `enumext*` environment.

`__enumext_start_item_viii:w`

```

3419 \cs_new_protected_nopar:Npn \__enumext_start_item_viii:w [#1]
3420 {
3421     \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \__enumext_stop_item_viii:
3422     \legacy_if:nT { @noitemarg }
3423     {
3424         \legacy_if_set_false:n { @noitemarg }
3425         \legacy_if:nT { @nمبرlist }
3426         {
3427             \bool_if:NT \l__enumext_hyperref_bool
3428             {
3429                 \legacy_if_set_true:n { @hyper@item }
3430             }
3431             \refstepcounter{enumXviii}
3432         }
3433     }

```

Here we start capturing `\item` and its contents into a group using the plain form of the `lrbox` environment.

```

3434     \group_begin:
3435     \lrbox{ \l__enumext_item_text_viii_box }
3436     \bool_if:NF \l__enumext_footnotes_key_bool
3437     {
3438         \__enumext_renew_footnote:
3439     }
3440     \bool_if:NT \l__enumext_item_starred_viii_bool
3441     {
3442         \__enumext_starred_item_exec:
3443     }
3444     \group_begin:
3445     \tl_use:N \l__enumext_label_font_style_viii_tl
3446     \bool_if:NTF \l__enumext_wrap_label_viii_bool
3447     {
3448         \makebox[ \l__enumext_labelwidth_viii_dim ][ \l__enumext_align_label_viii_str ]
3449         { \__enumext_wrapper_label_viii:n {#1} }
3450     }
3451     {
3452         \makebox[ \l__enumext_labelwidth_viii_dim ][ \l__enumext_align_label_viii_str ]{ #1 }
3453     }
3454     \group_end:
3455     \skip_horizontal:N \l__enumext_labelsep_viii_dim
3456     \tl_use:N \l__enumext_after_list_args_viii_tl
3457     \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_viii_dim }
3458     \skip_set_eq:NN \parindent \l__enumext_listparindent_viii_dim
3459     \skip_set_eq:NN \parskip \l__enumext_parsep_viii_skip
3460     \tl_use:N \l__enumext_fake_item_indent_viii_tl
3461 }

```

(End of definition for `__enumext_start_item_viii:w`)

`__enumext_stop_item_viii:` The function `__enumext_stop_item_viii:` shall terminate with the capture of `\item` and its *contents*. Close the environments `minipage`, `lrbox` and the group. Then we only have to set the width of the box and print it next to `\footnote`, and add the horizontal and vertical separation between the boxes.

```

3462 \cs_new_protected_nopar:Nn \__enumext_stop_item_viii:
3463 {
3464     \__enumext_endminipage:
3465     \endlrbox
3466     \group_end:
3467     \box_set_wd:Nn \l__enumext_item_text_viii_box
3468     {
3469         \l__enumext_joined_width_viii_dim
3470         + \l__enumext_labelwidth_viii_dim
3471         + \l__enumext_labelsep_viii_dim
3472     }
3473     \int_set:Nn \hbadness { 10000 }
3474     \box_use:N \l__enumext_item_text_viii_box
3475     \bool_if:NF \l__enumext_footnotes_key_bool
3476     {
3477         \__enumext_print_footnote:
3478     }
3479     \int_compare:nNnTF { \l__enumext_item_column_pos_viii_int } = { \l__enumext_columns_viii_int }
3480     {
3481         \par\noindent
3482         \int_zero:N \l__enumext_item_column_pos_viii_int
3483     }
3484     { \hspace{ \l__enumext_columns_sep_viii_dim } }
3485 }

```

(End of definition for `__enumext_stop_item_viii:`)

`__enumext_remove_extra_parsep_viii:` Finally we will remove the vertical space equal to `\parsep` when the total number of items is divisible by the number of items in the last row of the environment.

```

3486 \cs_new_protected:Nn \__enumext_remove_extra_parsep_viii:
3487 {
3488     \int_compare:nNnT
3489     {
3490         \int_mod:nn { \g__enumext_item_count_all_viii_int } { \l__enumext_columns_viii_int }
3491     }
3492     =
3493     { \c_zero_int }
3494     {
3495         \par
3496         \vspace{ -\l__enumext_itemsep_viii_skip }
3497         \int_gzero:N \g__enumext_item_count_all_viii_int
3498     }
3499 }

```

(End of definition for `__enumext_remove_extra_parsep_viii:`)

10.37 The command `\getkeyans`

`\getkeyans` The `\getkeyans` command takes a mandatory argument of the form $\langle \textit{store name} : \textit{position} \rangle$. Retrieve a “single” content stored by `\anskey`, `\anspic*` and `\item*` from *prop list* defined by `save-ans` key.

```

3500 \NewDocumentCommand \getkeyans { m }
3501 {
3502     \exp_args:Ne \__enumext_getkeyans_aux:n
3503     { \tl_to_str:e { \text_expand:n {#1} } }
3504 }

```

(End of definition for `\getkeyans`. This function is documented on page 13.)

`__enumext_getkeyans_aux:n` The internal function `__enumext_getkeyans_aux:n` is in charge of *splitting* the *argument* using “:”. If “:” is omitted it will return an error.

```

3505 \cs_new_protected:Npn \__enumext_getkeyans_aux:n #1
3506 {
3507     \str_if_in:nnTF {#1} { : }
3508     {
3509         \use:e
3510         {
3511             \cs_set:Npn \exp_not:N \__enumext_tmp:w ##1 \c_colon_str ##2 \scan_stop:
3512             { {##1} {##2} }

```

```

3513     }
3514     \exp_after:wN \__enumext_getkeyans:nn \__enumext_tmp:w #1 \scan_stop:
3515   }
3516   { \msg_error:nnn { enumext } { missing-colon } {#1} }
3517 }

```

(End of definition for __enumext_getkeyans_aux:n.)

__enumext_getkeyans:nn The internal function __enumext_getkeyans:nn will check for the existence of the *⟨prop list⟩*, if it does not exist it will return an error message, then it will fetch the content specified by the second *⟨argument⟩* from *⟨prop list⟩*.

```

3518 \cs_new_protected:Npn \__enumext_getkeyans:nn #1 #2
3519 {
3520   \prop_if_exist:cF { g__enumext_#1_prop }
3521   { \msg_error:nnn { enumext } { undefined-storage-anskey } {#1} }
3522   \group_begin:
3523     \prop_item:cn { g__enumext_#1_prop }{#2}
3524   \group_end:
3525 }

```

(End of definition for __enumext_getkeyans:nn.)

10.38 The command \printkeyans

The \printkeyans command prints “all stored content” in the *⟨sequence⟩* defined by the save-ans key. The first thing we will do is to define a set of *⟨keys⟩* with which we will control the options of the different nesting levels for the enumext and enumext* environment by storing the values of these in the token list variables \l__enumext_print_keyans_X_tl.

```

3526 \keys_define:nn { keyanskey / print }
3527 {
3528   level-1 .code:n = \tl_put_right:Nn \l__enumext_print_keyans_i_tl
3529                 {
3530                   \setenumext[level,1] {#1} \setenumext[print,1] {#1}
3531                 },
3532   level-1 .initial:n = { label=\arabic*., nosep, columns=2, first=\small, font=\small },
3533   level-2 .code:n = \tl_put_right:Nn \l__enumext_print_keyans_ii_tl
3534                 {
3535                   \setenumext[level,2] {#1} \setenumext[print,2] {#1}
3536                 },
3537   level-2 .initial:n = { nosep, label=(\alph*), first=\small, font=\small },
3538   level-3 .code:n = \tl_put_right:Nn \l__enumext_print_keyans_iii_tl
3539                 {
3540                   \setenumext[level,3] {#1} \setenumext[print,3] {#1}
3541                 },
3542   level-3 .initial:n = { nosep, label=\roman*., first=\small, font=\small },
3543   level-4 .code:n = \tl_put_right:Nn \l__enumext_print_keyans_iv_tl
3544                 {
3545                   \setenumext[level,4] {#1} \setenumext[print,4] {#1}
3546                 },
3547   level-4 .initial:n = { nosep, label=\Alph*., first=\small, font=\small },
3548   level-* .code:n = \tl_put_right:Nn \l__enumext_print_keyans_vii_tl % starred
3549                 {
3550                   \setenumext[enumext*] {#1} %%\setenumext[print,*] {#1}
3551                 },
3552   level-* .initial:n = { label=\arabic*., nosep, columns=2, first=\small, font=\small },
3553 }

```

\printkeyans Create a user command to print “all stored content” in *⟨sequence⟩* for \anskey, \item* and \anspic*.

```

3554 \NewDocumentCommand \printkeyans { s O{} m }
3555 {
3556   \group_begin:
3557     \tl_use:N \l__enumext_print_keyans_i_tl
3558     \tl_use:N \l__enumext_print_keyans_ii_tl
3559     \tl_use:N \l__enumext_print_keyans_iii_tl
3560     \tl_use:N \l__enumext_print_keyans_iv_tl
3561     \tl_use:N \l__enumext_print_keyans_vii_tl
3562     \__enumext_printkeyans:nnn { #1 } { #2 } { #3 }
3563   \group_end:
3564 }

```

(End of definition for \printkeyans. This function is documented on page 13.)

__enumext_printkeyans:nnn

The internal function __enumext_printkeyans:nnn will check for the existence of the *sequence*, if it does not exist it will return an error message, then it will fetch the content specified by the first argument mapping the *sequence*.

#1: starred
#2: key-val
#3: seq-name

```

3565 \cs_new_protected:Npn \__enumext_printkeyans:nnn #1 #2 #3
3566 {
3567   \seq_if_exist:cTF { g__enumext_#3_seq }
3568   {
3569     \seq_if_empty:cF { g__enumext_#3_seq }
3570     {
3571       %%\seq_show:c { g__enumext_#3_seq }
3572       \bool_if:nTF {#1}
3573       {
3574         \begin{enumext*}[#2]
3575         \seq_map_inline:cn { g__enumext_#3_seq } { ##1 }
3576         \end{enumext*}
3577       }
3578       {
3579         \begin{enumext}[#2]
3580         \seq_map_inline:cn { g__enumext_#3_seq } { ##1 }
3581         \end{enumext}
3582       }
3583     }
3584   }
3585   {
3586     \msg_error:nnn { enumext } { undefined-storage-anskey } {#3}
3587   }
3588 }

```

(End of definition for __enumext_printkeyans:nnn.)

10.39 The command \setenumext

First we define a “meta families” of *keys* to access from \setenumext.

```

3589 \keys_define:nn { enumext / meta-families }
3590 {
3591   level-1 .code:n = { \keys_set:nn { enumext / level-1 } {#1} } ,
3592   level-2 .code:n = { \keys_set:nn { enumext / level-2 } {#1} } ,
3593   level-3 .code:n = { \keys_set:nn { enumext / level-3 } {#1} } ,
3594   level-4 .code:n = { \keys_set:nn { enumext / level-4 } {#1} } ,
3595   keyans .code:n = { \keys_set:nn { enumext / keyans } {#1} } ,
3596   enumext* .code:n = { \keys_set:nn { enumext / enumext* } {#1} } ,
3597   keyans* .code:n = { \keys_set:nn { enumext / keyans* } {#1} } ,
3598   print-1 .code:n = { \keys_set:nn { keyanskey / print } { level-1 = {#1} } } ,
3599   print-2 .code:n = { \keys_set:nn { keyanskey / print } { level-2 = {#1} } } ,
3600   print-3 .code:n = { \keys_set:nn { keyanskey / print } { level-3 = {#1} } } ,
3601   print-4 .code:n = { \keys_set:nn { keyanskey / print } { level-4 = {#1} } } ,
3602   print-* .code:n = { \keys_set:nn { keyanskey / print } { level-* = {#1} } } ,
3603   unknown .code:n = { \msg_error:nn { enumext } { unknown-key-family } } ,
3604 }

```

We store them in the constant sequence \c__enumext_all_families_seq separated by commas.

```

3605 \seq_const_from_clist:Nn \c__enumext_all_families_seq
3606 {
3607   level-1 , level-2 , level-3 , level-4 , keyans , enumext* ,
3608   keyans* , print-1 , print-2 , print-3 , print-4 , print-* ,
3609 }

```

\setenumext

Now we define the user command \setenumext.

```

3610 \NewDocumentCommand \setenumext { o +m }
3611 {
3612   \tl_if_novalue:nTF {#1}
3613   {
3614     \seq_map_inline:Nn \c__enumext_all_families_seq
3615     {
3616       \seq_clear:N \l__enumext_setkey_tmpa_seq
3617       \seq_set_from_clist:Nn \l__enumext_setkey_tmpb_seq {#1}
3618       \int_set:Nn \l__enumext_setkey_tmpa_int

```

```

3620     {
3621       \seq_count:N \l__enumext_setkey_tmpb_seq
3622     }
3623     \int_compare:nNnTF { \l__enumext_setkey_tmpa_int } > { 1 }
3624     {
3625       \seq_pop_left:NN \l__enumext_setkey_tmpb_seq \l__enumext_setkey_tmpa_tl
3626       \seq_map_function:NN \l__enumext_setkey_tmpb_seq \l__enumext_set_parse:n
3627       \seq_set_map_e:NNn \l__enumext_setkey_tmpa_seq \l__enumext_setkey_tmpa_seq
3628       {
3629         \tl_use:N \l__enumext_setkey_tmpa_tl - ##1
3630       }
3631     }
3632     {
3633       \seq_put_right:Ne \l__enumext_setkey_tmpa_seq { \tl_trim_spaces:n {#1} }
3634     }
3635     \seq_if_empty:NTF \l__enumext_setkey_tmpa_seq
3636     { \seq_map_inline:Nn \c__enumext_all_families_seq }
3637     { \seq_map_inline:Nn \l__enumext_setkey_tmpa_seq }
3638   }
3639   {
3640     \keys_set:nn { enumext / meta-families } { ##1 = {#2} }
3641   }
3642 }

```

(End of definition for `\setenumext`. This function is documented on page 5.)

`__enumext_set_parse:n`
`__enumext_set_error:nn`

Internal functions used by the `\setenumext` command.

```

3643 \cs_new_protected:Npn \__enumext_set_parse:n #1
3644 {
3645   \tl_set:Ne \l__enumext_setkey_tmpb_tl { \tl_trim_spaces:n {#1} }
3646   \int_step_inline:nnn { 0 } { 4 } %<- max level
3647   { \tl_remove_all:Nn \l__enumext_setkey_tmpb_tl {##1} }
3648   \tl_if_empty:NTF \l__enumext_setkey_tmpb_tl
3649   {
3650     \seq_put_right:Ne \l__enumext_setkey_tmpa_seq
3651     { \tl_trim_spaces:n {#1} }
3652   }
3653   { \__enumext_set_error:nn {#1} { } }
3654 }
3655 \cs_new_protected:Npn \__enumext_set_error:nn #1 #2
3656 { \msg_error:nnn { enumext } { invalid-key } {#1} {#2} }

```

(End of definition for `__enumext_set_parse:n` and `__enumext_set_error:nn`.)

10.40 Messages

Message used by package-load for `multicol` and `hyperref` packages.

```

3657 \msg_new:nnn { enumext } { package-load }
3658 {
3659   The ~ '#1' ~ package ~ is ~ already ~ loaded.
3660 }
3661 \msg_new:nnn { enumext } { package-not-load }
3662 {
3663   The ~ '#1' ~ package ~ will ~ be ~ loaded ~ as ~ a ~ dependency.
3664 }
3665 \msg_new:nnn { enumext } { package-load-foot }
3666 {
3667   The ~ '#1' ~ package ~ is ~ loaded ~ with ~ the ~ option ~ '#2'.
3668 }

```

Message used in the creation of counters by `enumext` package.

```

3669 \msg_new:nnn { enumext } { counters }
3670 {
3671   The ~ counter ~ '#1' ~ is ~ already ~ defined ~ by ~ some ~ \
3672   package ~ or ~ macro, ~ it ~ cannot ~ be ~ continued.
3673 }

```

Message used by `[⟨key = val⟩]` system and `\setenumext` command.

```

3674 \msg_new:nnn { enumext } { invalid-key }
3675 {
3676   The ~ key ~ '#1' ~ is ~ not ~ know ~ the ~ level ~ #2.

```

```

3677     }
3678     \msg_new:nnn { enumext } { unknown-key-family }
3679     {
3680         Unknown~key~family~`\l_keys_key_str'~for~enumext.
3681     }

```

Messages used in length calculation.

```

3682     \msg_new:nnn { enumext } { width-negative }
3683     {
3684         Ignoring ~ negative ~ value ~ '#1=#2' ~ \msg_line_context:.\
3685         The ~ key ~ '#1'~ accepts ~ values ~ >= ~ opt.
3686     }
3687     \msg_new:nnn { enumext } { width-zero }
3688     {
3689         Invalid ~ '#1=#2' ~ \msg_line_context:.\
3690         The ~ key ~ '#1'~ accepts ~ values ~ > ~ opt.
3691     }

```

Messages used by `show-length` key in `enumext`.

```

3692     \msg_new:nnn { enumext } { list-lengths }
3693     {
3694         **** ~ Lengths ~ used ~ by ~ 'enumext' ~ level ~ '#2' ~ \msg_line_context:~\c_space_tl ****\
3695         \__enumext_show_length:nnn { dim } { labelsep } {#1}
3696         \__enumext_show_length:nnn { dim } { labelwidth } {#1}
3697         \__enumext_show_length:nnn { dim } { itemindent } {#1}
3698         \__enumext_show_length:nnn { dim } { leftmargin } {#1}
3699         \__enumext_show_length:nnn { dim } { rightmargin } {#1}
3700         \__enumext_show_length:nnn { dim } { listparindent } {#1}
3701         \__enumext_show_length:nnn { skip } { topsep } {#1}
3702         \__enumext_show_length:nnn { skip } { parsep } {#1}
3703         \__enumext_show_length:nnn { skip } { partopsep } {#1}
3704         \__enumext_show_length:nnn { skip } { itemsep } {#1}
3705         ****~
3706     }

```

Messages used by `show-length` key in `enumext*`, `keyans*` and `keyans`.

```

3707     \msg_new:nnn { enumext } { list-lengths-not-nested }
3708     {
3709         **** ~ Lengths ~ used ~ by ~ '#2' ~ environment ~ \msg_line_context:~\c_space_tl ****\
3710         \__enumext_show_length:nnn { dim } { labelsep } {#1}
3711         \__enumext_show_length:nnn { dim } { labelwidth } {#1}
3712         \__enumext_show_length:nnn { dim } { itemindent } {#1}
3713         \__enumext_show_length:nnn { dim } { leftmargin } {#1}
3714         \__enumext_show_length:nnn { dim } { rightmargin } {#1}
3715         \__enumext_show_length:nnn { dim } { listparindent } {#1}
3716         \__enumext_show_length:nnn { skip } { topsep } {#1}
3717         \__enumext_show_length:nnn { skip } { parsep } {#1}
3718         \__enumext_show_length:nnn { skip } { partopsep } {#1}
3719         \__enumext_show_length:nnn { skip } { itemsep } {#1}
3720         ****~
3721     }

```

Messages used by the internal system to check answer used by `check-ans` key.

```

3722     \msg_new:nnn { enumext } { items-same-answer }
3723     {
3724         *****~Checking~answers~on~'#1'~OK~*****\
3725         **~ All ~ items ~ stored ~ in ~ sequence ~ '#1' ~ have ~ an ~ answer. \
3726         *****~
3727         \prg_replicate:nn { 7 + \str_count:n {#1} } { * }
3728     }
3729     \msg_new:nnn { enumext } { item-different-answer }
3730     {
3731         Number ~ of ~ items ~ different ~ of ~ number ~ of ~
3732         answer ~ in ~ sequence ~ '#1'~ closed ~ \msg_line_context:.
3733     }

```

Messages used by the internal system to check for “starred” `\item*` commands.

```

3734     \msg_new:nnn { enumext } { missing-starred }
3735     {
3736         Missing ~ '\c_backslash_str #1*' ~ in ~ '#2' ~ \msg_line_context:.
3737     }

```

Message for the nesting depth of the environment `enumext`.

```
3738 \msg_new:nnn { enumext } { list-too-deep }
3739 {
3740     Too ~ deep ~ nesting ~ for ~ 'enumext' ~ \msg_line_context:~ \\
3741     The ~ maximum ~ level ~ of ~ nesting ~ is ~ 4.
3742 }
```

Messages used by `\anskey` and `\anspic` commands.

```
3743 \msg_new:nnn { enumext } { anskey-wrong-place }
3744 {
3745     Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
3746     '\c_backslash_str #1' ~ works ~ in ~ the ~ environment ~ '#2'.
3747 }
3748 \msg_new:nnn { enumext } { ansPIC-wrong-place }
3749 {
3750     Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
3751     '\c_backslash_str #1' ~ works ~ in ~ the ~ environment ~ '#2'.
3752 }
3753 \msg_new:nnn { enumext } { command-wrong-place }
3754 {
3755     Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
3756     '\c_backslash_str #1' ~ works ~ outside ~ the ~ environment ~ '#2'.
3757 }
```

Messages used by `keyans` and `keyanspic` environment.

```
3758 \msg_new:nnn { enumext } { keyans-nested }
3759 {
3760     The ~ environment ~ 'keyans' ~ can't ~ be ~ nested ~ \msg_line_context:.
3761 }
3762 \msg_new:nnn { enumext } { keyans-wrong-level }
3763 {
3764     Wrong ~ level ~ position ~ for ~ 'keyans' ~ \msg_line_context:~ \\
3765     The ~ environment ~ 'keyans' ~ can ~ only ~ be ~ in ~ the ~ first ~ level.
3766 }
3767 \msg_new:nnn { enumext } { wrong-place }
3768 {
3769     Wrong ~ place ~ for ~ '#1' ~ environment ~ \msg_line_context:~ \\
3770     '#1' ~ is ~ only ~ found ~ with ~ '#2' ~ in ~ 'enumext'.
3771 }
3772 \msg_new:nnn { enumext } { keyanspic-nested }
3773 {
3774     The ~ environment ~ 'keyanspic' ~ can't ~ be ~ nested ~ \msg_line_context:~.
3775 }
3776 \msg_new:nnn { enumext } { keyanspic-wrong-level }
3777 {
3778     Wrong ~ level ~ position ~ for ~ 'keyanspic' ~ \msg_line_context:~ \\
3779     The ~ environment ~ 'keyans' ~ can ~ only ~ be ~ in ~ the ~ first ~ level.
3780 }
```

Messages used by `\getkeyans` command.

```
3781 \msg_new:nnn { enumext } { undefined-storage-anskey }
3782 {
3783     Storage ~ named ~ '#1' ~ is ~ not ~ defined ~ \msg_line_context:.
3784 }
```

Messages used by `\miniright` command.

```
3785 \msg_new:nnn { enumext } { missing-miniright }
3786 {
3787     Missing ~ '\c_backslash_str miniright' ~ in ~ \msg_line_context:~ \\
3788     The ~ key ~ 'mini-env' ~ need ~ '\c_backslash_str miniright'.
3789 }
3790 \msg_new:nnn { enumext } { wrong-miniright-place }
3791 {
3792     Wrong ~ place ~ for ~ '\c_backslash_str miniright' ~ \msg_line_context:~ \\
3793     Works ~ in ~ 'enumext' ~ and ~ 'keyans' ~ with ~ key ~ 'mini-env'.
3794 }
3795 \msg_new:nnn { enumext } { wrong-miniright-use }
3796 {
3797     Wrong ~ use ~ for ~ '\c_backslash_str miniright' ~ \msg_line_context:~ \\
3798     '\c_backslash_str miniright' ~ need ~ a ~ key ~ 'mini-env'.
3799 }
```

Messages used by `enumext*` and `keyans*` environments.

```
3800 \msg_new:nnn { enumext } { nested }
3801 {
3802   The ~ starred ~ environment ~ can't ~ be ~ nested ~ \msg_line_context:.
3803 }
3804 \msg_new:nnn { enumext } { item-joined }
3805 {
3806   Items ~ joined ~ (#1) ~ > ~ #2 ~ columns ~\msg_line_context:.
3807 }
3808 \msg_new:nnn { enumext } { item-joined-columns }
3809 {
3810   Not ~ space ~ to ~ join ~ items ~ (#1) ~ > ~ #2 ~\msg_line_context:.
3811 }
```

10.41 Finish package

Finish package implementation.

```
3812 \file_input_stop:
3813 </package>
```

11 Index of Implementation

The *italic* numbers denote the pages where the corresponding entry is described, the numbers underlined and all others indicate the line on which they are implemented in the package code.

Symbols	
<code>*</code>	415
<code>\+</code>	192
<code>\-</code>	192
<code>\\</code> 200, 2642, 3671, 3684, 3689, 3694, 3709, 3724, 3725, 3740, 3745, 3750, 3755, 3764, 3769, 3778, 3787, 3792, 3797	
A	
<code>above</code>	<u>1226</u>
<code>above*</code>	<u>1226</u>
<code>\addvspace</code> .. 873, 901, <u>1024</u> , 1103, 1166, 1172, 1200, 1217, 2458, 2480, 2598, 2613, 2837, 2844, 3248, 3255	
<code>after</code>	<u>711</u>
<code>align</code>	<u>369</u>
<code>\Alph</code>	29, <u>34</u>
<code>\Alph</code>	321, 498, 516, 529, 3547
<code>\alph</code>	29, <u>34</u>
<code>\alph</code>	322, 496, 3537
<code>\anskey</code>	<u>10</u> , <u>56</u> , <u>1634</u>
<code>\anspic</code>	<u>12</u> , <u>77</u> , <u>78</u> , <u>2620</u>
<code>\arabic</code>	29, <u>31</u>
<code>\arabic</code>	320, 495, 515, 3532, 3552
B	
<code>\b</code>	2336, 2349, 2899, 2912
<code>\baselineskip</code>	<u>41</u>
<code>\baselineskip</code>	1594, 1602
<code>before</code>	<u>711</u>
<code>before*</code>	<u>711</u>
<code>below</code>	<u>1226</u>
<code>below*</code>	<u>1226</u>
bool commands:	
<code>\bool_gset_false:N</code> .. 2502, 2503, 2846, 2950, 3142, 3143, 3257	
<code>\bool_gset_true:N</code> 218, 227, 815, 2465, 2829, 2847, 2947, 3240, 3258	
<code>\bool_if:NTF</code> . 261, 273, 290, 1248, 1262, 1275, 1286, 1297, 1308, 1319, 1330, 1373, 1384, 1439, 1449, 1556, 1580, 1587, 1615, 1646, 1659, 1661, 1672, 1692, 1817, 1828, 1832, 1866, 1881, 1950, 1965, 1976, 2052, 2082, 2155, 2171, 2239, 2249, 2285, 2290, 2327, 2334, 2347, 2392, 2442, 2456, 2471, 2498, 2527, 2583, 2596, 2604, 2622, 2825, 2834, 2838, 2889, 2897, 2910, 2955, 2965, 3048, 3053, 3061, 3065, 3080, 3109, 3138, 3236, 3245, 3249, 3387, 3397, 3427, 3436, 3440, 3446, 3475	
<code>\bool_if:nTF</code> 1201, 1218, 1700, 2093, 2127, 2191, 2643, 3572	
<code>\bool_if_p:N</code> 1418, 1683, 1726, 1727, 1751, 1760, 1761, 1773, 1789, 1936, 1937, 2228, 2275, 2365, 2378, 2380, 2462, 2649, 2650, 2944, 2945	
<code>\bool_lazy_all:nTF</code> .. 1416, 1749, 1758, 1771, 1787, 2363, 2376	
<code>\bool_lazy_and:nnTF</code> . 1682, 1725, 1935, 2226, 2274, 2461, 2943	
<code>\bool_lazy_or:nnTF</code>	2648
<code>\bool_new:N</code> 25, 26, 27, 28, 29, 35, 37, 46, 67, 72, 73, 78, 79, 82, 100, 102, 104, 107, 108, 117, 118, 119, 120, 129, 130, 155, 166, 168	
<code>\bool_not_p:n</code> 1684, 1776, 1791, 2366, 2367, 2379, 2463	
<code>\bool_set_eq:NN</code>	2060, 2108, 2998, 3342
<code>\bool_set_false:N</code> 270, 1400, 1401, 1483, 1486, 1506, 1509, 2485, 2534, 2616, 2680, 2697, 2951, 2995, 3292, 3339	
<code>\bool_set_true:N</code> 252, 256, 362, 639, 1232, 1237, 1364, 1365, 1380, 1391, 1482, 1485, 1505, 1508, 1518, 1525, 2056, 2086, 2104, 2116, 2321, 2372, 2385, 2411, 2532, 2558, 2814, 2882, 3004, 3011, 3012, 3225, 3348, 3355, 3356	
box commands:	
<code>\box_dp:N</code> . 920, 924, 928, 939, 943, 954, 963, 969, 979, 992, 998, 1004, 1035, 1036, 1037, 1040, 1050, 1054, 1063, 1070, 1075, 1083, 1112, 1113, 1116, 1123, 1136, 1144, 1150, 1158, 2709	
<code>\box_new:N</code>	43, 161
<code>\box_set_wd:Nn</code>	3101, 3467
<code>\box_use:N</code>	3108, 3474
<code>\box_wd:N</code>	328
C	
<code>\c</code>	415, 416, 539, 541, 553, 555
<code>\cB</code>	416
<code>\cE</code>	416
<code>\centering</code>	1203, 1220, 2730, 2840, 3251
<code>check-ans</code>	<u>1393</u>
Document class:	
<code>article</code>	35
clist commands:	
<code>\clist_const:Nn</code>	173
<code>\clist_map_function:nN</code>	2717
<code>\clist_map_inline:Nn</code> . 368, 581, 644, 710, 725, 806, 1242	
<code>\clist_map_inline:nn</code> . 34, 51, 57, 69, 81, 106, 138, 152, 172, 208, 393, 410, 649, 821, 1406, 1495, 1513, 1534, 1746, 1875, 2010, 2220, 2223, 2256, 2266, 2269, 2295	
<code>\columnbreak</code>	57
<code>\columnbreak</code>	1686
<code>columns</code>	<u>790</u>
<code>columns*</code>	<u>1514</u>
<code>columns-sep</code>	<u>790</u>
<code>columns-sep*</code>	<u>1514</u>
<code>\columnsep</code>	73, <u>76</u>
<code>\columnsep</code>	2436, 2580
<code>\columnseprule</code>	73, <u>76</u>
<code>\columnseprule</code>	2440, 2582
Commands provide by enumext :	
<code>\anskey</code> .. 23, 24, 50, 52, 54–61, 63, 72, 85, 95, 96, 100	
<code>\anspic*</code>	23, 60–63, 78–80, 95, 96
<code>\anspic</code>	54, 55, 77–80, 100
<code>\getkeyans</code>	54, 95, 100
<code>\item*</code>	23, 54, 55, 60–63, 65, 66, 86, 93, 95, 96
<code>\itemwidth</code>	81, 88, 89
<code>\item</code>	64, 66, 81, 85, 86, 89, 92
<code>\miniright</code>	23, 39, 47, 48, 73, 74, 76, 77, 100
<code>\printkeyans</code>	24, 55, 96
<code>\setenumext</code>	23, 97, 98
Counters defined by enumext :	
<code>enumXiii</code>	22, 29
<code>enumXii</code>	22, 29
<code>enumXiv</code>	22, 29

enumXi 22, 29
enumXviii 22, 29
enumXvii 22, 29, 86
enumXvi 22, 29
enumXv 22, 29

cs commands:

\cs_generate_variant:Nn 330, 346, 545, 561, 1539, 1548, 1553, 1633, 2210, 2719
\cs_if_exist:NTF 300
\cs_new:Nn 186
\cs_new:Npn 196
\cs_new_eq:NN 236, 237, 238, 242, 243, 275, 276, 279, 280
\cs_new_protected:Nn . 210, 247, 411, 431, 463, 726, 730, 734, 738, 742, 746, 750, 754, 758, 762, 766, 770, 774, 778, 782, 786, 822, 834, 858, 875, 886, 910, 985, 1009, 1026, 1088, 1105, 1127, 1162, 1168, 1243, 1257, 1271, 1282, 1293, 1304, 1315, 1326, 1371, 1382, 1411, 1447, 1454, 1554, 1578, 1585, 1613, 1620, 1737, 1864, 1879, 1907, 1933, 2015, 2019, 2038, 2089, 2123, 2139, 2149, 2165, 2316, 2361, 2390, 2397, 2420, 2450, 2469, 2525, 2548, 2566, 2591, 2602, 2639, 2682, 2695, 2715, 2720, 2736, 2804, 2823, 2875, 2924, 2931, 2953, 2963, 2980, 3120, 3147, 3215, 3234, 3284, 3305, 3311, 3324, 3376, 3486
\cs_new_protected:Npn 178, 182, 283, 298, 315, 325, 331, 419, 438, 532, 546, 1190, 1209, 1353, 1540, 1549, 1669, 1814, 1826, 1848, 1917, 1955, 1963, 2048, 2066, 2100, 2112, 2179, 2213, 2259, 2323, 2332, 2544, 2690, 2755, 2884, 2895, 2986, 2993, 3009, 3017, 3022, 3034, 3166, 3298, 3330, 3337, 3353, 3361, 3371, 3505, 3518, 3565, 3643, 3655
\cs_new_protected_nopar:Nn ... 2973, 3096, 3317, 3462
\cs_new_protected_nopar:Npn 3040, 3419
\cs_set:Nn 1819
\cs_set:Npn 1747, 1785, 3511
\cs_set_eq:NN .. 2865, 2866, 3042, 3274, 3275, 3421
\cs_set_protected:Nn 202, 650, 666, 678, 690
\cs_set_protected:Npn . 30, 44, 52, 64, 70, 96, 134, 146, 153, 204, 347, 369, 398, 479, 499, 562, 582, 626, 645, 702, 711, 790, 807, 1226, 1393, 1467, 1496, 1514, 1739, 1868, 1999, 2211, 2257
\cs_to_str:N 317, 340

D

\d 192
\DeclareDocumentEnvironment 903

dim commands:

\dim_abs:n 2184, 2189
\dim_add:Nn 2700, 3393, 3414
\dim_compare:nNnTF . 652, 668, 680, 692, 1192, 1211, 2181, 2186, 2192, 2198, 2200, 2202, 2402, 2425, 2552, 2570, 2692, 2738, 2806, 3149, 3217
\dim_compare:nTF 1710
\dim_gset_eq:NN 2815, 3226
\dim_gzero:N 2849, 3260
\dim_new:N 40, 47, 48, 49, 66, 90, 103, 113, 162, 163, 169
\dim_set:Nn .. 328, 640, 1526, 2080, 2184, 2189, 2191, 2194, 2195, 2199, 2201, 2204, 2205, 2207, 2405, 2428, 2554, 2572, 2722, 2740, 2747, 2790, 2808, 3036, 3151, 3158, 3201, 3219
\dim_set_eq:NN 486, 506, 522, 526, 2075, 2222, 2268, 2351, 2436, 2580, 2797, 2800, 2801, 2914, 3027, 3208, 3211, 3212

\dim_use:N 653, 661, 1193, 1199, 1623, 1626, 1631, 2144, 2146, 2403, 2408, 2409, 2416, 2426, 2430, 2431, 2433
\dim_zero:N 2440, 2582, 2701, 2702, 2703
\dim_zero_new:N 2753, 3164
\c_zero_dim 655, 669, 681, 693, 1193, 1211, 1712, 2181, 2186, 2192, 2199, 2403, 2426, 2552, 2570, 2738, 2806, 3149, 3217

E

\end .. 1196, 1214, 1582, 1617, 2455, 2479, 2595, 2612, 2827, 2843, 3238, 3254, 3576, 3581
\endlist 27
\endlist 237
\endlrbox 3099, 3465
\endminipage 27
\endminipage 243
enumext 4, 2296

enumext internal commands:

__enumext_add_pre_parsep: ... 40, 832, 834, 834
__enumext_after_args_exec: . 38, 726, 738, 2309
__enumext_after_args_exec_v: . 38, 39, 742, 754, 2518
__enumext_after_args_exec_vii: ... 758, 782
__enumext_after_args_exec_viii: 786
__enumext_after_env:n 74
__enumext_after_env:nn .. 74, 88, 182, 182, 2494, 2832, 3134, 3243
__enumext_after_hyperref: ... 27, 245, 247, 247
__enumext_after_list: 74, 84, 91, 2314, 2469, 2469
\l__enumext_after_list_args_v_tl 756
\l__enumext_after_list_args_vii_tl 784, 3090
\l__enumext_after_list_args_viii_tl 788, 3456
__enumext_after_list_v: .. 77, 2523, 2602, 2602
__enumext_after_list_vii: ... 2873, 2931, 2931
__enumext_after_list_viii: .. 3282, 3311, 3311
__enumext_after_star_env:nn 82
__enumext_after_stop_list: ... 37, 39, 726, 734, 2483
__enumext_after_stop_list_v: 38, 742, 750, 2617
\l__enumext_after_stop_list_v_tl 752
__enumext_after_stop_list_vii: 758, 774, 2934
\l__enumext_after_stop_list_vii_tl ... 776
__enumext_after_stop_list_viii: . 778, 3314
\l__enumext_after_stop_list_viii_tl ... 780
\l__enumext_align_label_vii_str .. 3082, 3086
\l__enumext_align_label_viii_str . 3448, 3452
\l__enumext_align_label_X_str 153
\c_enumext_all_envs_clist .. 173, 368, 581, 644, 710, 725, 806, 1242
\c_enumext_all_families_seq .. 97, 3605, 3614, 3636
__enumext_anskey_wrapper:n 1471, 1824
__enumext_at_begin_document:n .. 27, 178, 178, 234, 240
__enumext_before_args_exec: 37, 726, 726, 2400
__enumext_before_args_exec_v: .. 38, 742, 742, 2551
__enumext_before_args_exec_vii: .. 758, 758, 2928
__enumext_before_args_exec_viii: 762, 3308
__enumext_before_keys_exec: 37, 726, 730, 2307
__enumext_before_keys_exec_v: .. 38, 742, 746, 2516
__enumext_before_keys_exec_vii 758


```

\__enumext_before_keys_exec_vii: 38, 766, 2861
\__enumext_before_keys_exec_viii: .. 38, 770,
    3270
\__enumext_before_list: ... 72, 2301, 2397, 2397
\__enumext_before_list_v: . 76, 2511, 2548, 2548
\__enumext_before_list_vii: 84, 2856, 2924, 2924
\__enumext_before_list_viii: .. 91, 3266, 3305,
    3305
\l__enumext_before_no_starred_key_v_tl 748
\l__enumext_before_no_starred_key_vii_-
    tl ..... 768
\l__enumext_before_no_starred_key_viii_-
    tl ..... 772
\l__enumext_before_starred_key_v_tl ... 744
\l__enumext_before_starred_key_vii_tl . 760
\l__enumext_before_starred_key_viii_tl 764
\__enumext_calc_hspace:NNNNNNN 68, 2179, 2179,
    2210, 2215, 2261
\l__enumext_check_ans_bool 50, 64, 65, 117, 1397,
    1401, 1449, 1661, 1950, 2052, 2082, 2462, 2945, 3053
\__enumext_check_ans_exec: .. 53, 72, 1447, 1447,
    2401, 2927
\__enumext_check_ans_int:n ..... 50
\g__enumext_check_ans_item_tl .. 62, 117, 1949,
    1957, 1961
\__enumext_check_ans_set: . 52, 1411, 1411, 1451
\__enumext_check_ans_show: 53, 1454, 1454, 2500,
    3140
\g__enumext_check_ans_show_bool 74, 117, 2465,
    2498, 2503
\g__enumext_check_ans_show_h_bool 117, 2947,
    3138, 3143
\l__enumext_columns_sep_v_dim 2570, 2572, 2580
\l__enumext_columns_sep_vii_dim .. 2738, 2740,
    2749, 2794, 2916, 3118
\l__enumext_columns_sep_viii_dim . 3149, 3151,
    3160, 3205, 3484
\l__enumext_columns_v_int 1031, 2568, 2576, 2588,
    2593
\l__enumext_columns_vii_int .. 2743, 2746, 2750,
    2758, 2762, 2765, 2771, 2777, 2781, 2903, 3113, 3124
\l__enumext_columns_viii_int . 3154, 3157, 3161,
    3169, 3173, 3176, 3182, 3188, 3192, 3479, 3490
\g__enumext_count_item_anskey_int .. 62, 117,
    1457, 1465, 1663, 1952
\g__enumext_count_item_number_int 117, 1422,
    1427, 1430, 1433, 1441, 1457, 1464, 2054, 2084, 3055
\g__enumext_count_item_with_ans_int .... 57
\l__enumext_counter_i_tl ..... 30, 307
\l__enumext_counter_ii_tl ..... 30, 308
\l__enumext_counter_iii_tl ..... 30, 309
\l__enumext_counter_iv_tl ..... 30, 310
\l__enumext_counter_style_for_ref_vii_-
    tl ..... 446, 456, 467, 469
\l__enumext_counter_style_for_ref_viii_-
    tl ..... 473, 475
\l__enumext_counter_style_for_ref_X_tl 142
\c__enumext_counter_style_tl .... 31, 142, 413
\g__enumext_counter_styles_tl . 22, 29, 40, 318,
    336
\l__enumext_counter_v_tl ..... 30, 311
\l__enumext_counter_vi_tl ..... 30, 312
\l__enumext_counter_vii_tl ..... 30, 313, 443
\l__enumext_counter_viii_tl ..... 30, 314, 453
\__enumext_current_env: 26, 210, 210, 2298, 2853
\l__enumext_current_widest_dim 22, 40, 342, 487,
    507, 523, 527
\__enumext_default_item:n ... 2048, 2048, 2097
\__enumext_define_counters:Nn 22, 298, 298, 307,
    308, 309, 310, 311, 312, 313, 314
\__enumext_endminipage: . 27, 240, 243, 909, 2732,
    3098, 3464
\__enumext_fake_item: ..... 650, 650, 2248
\l__enumext_fake_item_indent_v_dim 669, 674
\l__enumext_fake_item_indent_v_tl 671, 2105,
    2109, 2117
\l__enumext_fake_item_indent_vii_dim 681, 686
\l__enumext_fake_item_indent_vii_tl 683, 3094
\l__enumext_fake_item_indent_viii_dim . 693,
    698, 3393, 3414
\l__enumext_fake_item_indent_viii_tl .. 695,
    3460
\l__enumext_fake_item_indent_X_tl ..... 70
\__enumext_fake_item_vii: .... 650, 678, 2284
\__enumext_fake_item_viii: .... 650, 690, 2289
\g__enumext_footnote_arg_seq . 139, 2021, 2034,
    2044
\g__enumext_footnote_int . 139, 2028, 2031, 2033,
    2035
\g__enumext_footnote_int_seq . 139, 2022, 2035,
    2040, 2043
\__enumext_footnotes_key_bool ..... 27
\l__enumext_footnotes_key_bool 24, 28, 87, 129,
    256, 261, 270, 3061, 3109, 3436, 3475
\__enumext_footnotetext:nn ... 2015, 2015, 2045
\__enumext_getkeyans:nn ... 96, 3514, 3518, 3518
\__enumext_getkeyans_aux:n . 95, 3502, 3505, 3505
\l__enumext_hyperref_bool . 24, 27, 28, 129, 252,
    273, 290, 1727, 1937, 3048, 3427
\__enumext_hypertarget:nn 28, 247, 275, 279, 295
\__enumext_if_is_int:n ..... 190
\__enumext_if_is_int:nTF ..... 190, 534, 548
\l__enumext_item_column_pos_vii_int 85, 2765,
    2771, 2777, 2781, 2788, 2976, 3113, 3116
\l__enumext_item_column_pos_viii_int ... 92,
    3176, 3182, 3188, 3192, 3199, 3320, 3479, 3482
\l__enumext_item_column_pos_X_int ..... 153
\g__enumext_item_count_all_vii_int 85, 2789,
    2977, 3124, 3131
\g__enumext_item_count_all_viii_int 92, 3200,
    3321, 3490, 3497
\g__enumext_item_count_all_X_int ..... 153
\__enumext_item_peek_args_vii: 85, 2978, 2980,
    2980
\__enumext_item_peek_args_viii: 92, 3322, 3324,
    3324
\__enumext_item_starred: .. 67, 2139, 2139, 2157
\l__enumext_item_starred_vii_bool 2995, 3011,
    3065
\l__enumext_item_starred_viii_bool 3339, 3355,
    3440
\l__enumext_item_starred_X_bool ..... 153
\__enumext_item_std:w 27, 64-66, 80, 234, 238, 2057,
    2063, 2087, 2105, 2109, 2117, 2713
\g__enumext_item_symbol_aux_vii_tl 3019, 3067,
    3070, 3074, 3076
\g__enumext_item_symbol_aux_X_tl ..... 153
\l__enumext_item_symbol_sep_vii_dim .. 3028,

```


[3036](#), [3073](#), [3075](#)
`\g__enumext_item_symbol_tl` [22](#), [65](#), [35](#), [2072](#), [2145](#), [2162](#)
`\l__enumext_item_symbol_vii_tl` [3070](#)
`\l__enumext_item_text_vii_box` [3060](#), [3101](#), [3108](#)
`\l__enumext_item_text_viii_box` [3435](#), [3467](#), [3474](#)
`\l__enumext_item_text_X_box` [153](#)
`\l__enumext_item_width_vii_dim` [2747](#), [2792](#), [2800](#), [2801](#)
`\l__enumext_item_width_viii_dim` [3158](#), [3203](#), [3211](#), [3212](#)
`\l__enumext_item_width_X_dim` [153](#)
`\l__enumext_itemindent_X_dim` [44](#)
`\l__enumext_itemsep_vii_skip` [3130](#)
`\l__enumext_itemsep_viii_skip` [3496](#)
`\l__enumext_joined_item_aux_vii_int` [2786](#), [2787](#), [2788](#), [2789](#), [2795](#)
`\l__enumext_joined_item_aux_viii_int` [3197](#), [3198](#), [3199](#), [3200](#), [3206](#)
`\l__enumext_joined_item_aux_X_int` [153](#)
`__enumext_joined_item_vii:w` [85](#), [2983](#), [2984](#), [2986](#), [2986](#)
`\l__enumext_joined_item_vii_int` [2757](#), [2758](#), [2761](#), [2763](#), [2769](#), [2774](#), [2779](#), [2784](#), [2786](#), [2792](#)
`__enumext_joined_item_viii:w` [92](#), [3327](#), [3328](#), [3330](#), [3330](#)
`\l__enumext_joined_item_viii_int` [3168](#), [3169](#), [3172](#), [3174](#), [3180](#), [3185](#), [3190](#), [3195](#), [3197](#), [3203](#)
`\l__enumext_joined_item_X_int` [153](#)
`\l__enumext_joined_width_vii_dim` [2790](#), [2797](#), [2800](#), [3091](#), [3103](#)
`\l__enumext_joined_width_viii_dim` [3201](#), [3208](#), [3211](#), [3457](#), [3469](#)
`\l__enumext_joined_width_X_dim` [153](#)
`__enumext_keyans_addto_prop:n` [60](#), [1848](#), [1848](#), [2119](#), [2645](#)
`__enumext_keyans_addto_seq:n` [62](#), [1917](#), [1917](#), [2121](#), [2647](#)
`__enumext_keyans_addto_seq_link:` [1917](#), [1931](#), [1933](#), [3386](#)
`__enumext_keyans_anspic_code:nnn` [78](#), [2636](#), [2639](#), [2639](#)
`__enumext_keyans_check_ans:nn` [62](#), [63](#), [1955](#), [1955](#), [2521](#), [2677](#), [3280](#)
`__enumext_keyans_default_item:n` [66](#), [2100](#), [2100](#), [2135](#)
`\l__enumext_keyans_env_bool` [20](#), [2366](#), [2379](#), [2532](#), [2616](#)
`__enumext_keyans_fake_item:` [650](#), [666](#), [2238](#)
`\l__enumext_keyans_level_h_int` [20](#), [1895](#), [3286](#), [3287](#)
`\l__enumext_keyans_level_int` [20](#), [1184](#), [1650](#), [1890](#), [2531](#), [2535](#), [2630](#)
`__enumext_keyans_make_label:` [30](#), [67](#), [2165](#), [2165](#), [2237](#)
`__enumext_keyans_mini_addvspace:` [45](#), [76](#), [1088](#), [1088](#), [2560](#)
`__enumext_keyans_mini_right_cmd:n` [48](#), [1186](#), [1209](#), [1209](#)
`__enumext_keyans_mini_set_vskip:` [44](#), [1026](#), [1026](#), [1090](#)
`__enumext_keyans_multi_addvspace:` [76](#), [875](#), [886](#), [2585](#)
`__enumext_keyans_multi_set_vskip:` [41](#), [875](#), [875](#), [888](#)
`__enumext_keyans_multicols_start:` [76](#), [2564](#), [2566](#), [2566](#)
`__enumext_keyans_multicols_stop:` [77](#), [1213](#), [2591](#), [2591](#), [2615](#)
`__enumext_keyans_parse_keys:n` [2510](#), [2544](#), [2544](#)
`\l__enumext_keyans_pic_above_int` [112](#), [2723](#), [2724](#), [2726](#)
`\l__enumext_keyans_pic_above_skip` [80](#), [112](#), [2668](#), [2707](#)
`__enumext_keyans_pic_arg_two:` [79](#), [2666](#), [2695](#), [2695](#)
`\l__enumext_keyans_pic_below_int` [112](#), [2723](#), [2724](#), [2727](#)
`\l__enumext_keyans_pic_body_seq` [78–80](#), [112](#), [2634](#), [2673](#), [2731](#)
`__enumext_keyans_pic_do:n` [80](#), [2673](#), [2675](#), [2715](#), [2715](#), [2719](#)
`\l__enumext_keyans_pic_level_int` [20](#), [1176](#), [1654](#), [1851](#), [1885](#), [1920](#), [2684](#), [2685](#)
`__enumext_keyans_pic_row:n` [80](#), [2717](#), [2720](#), [2720](#)
`__enumext_keyans_pic_safe_exec:` [79](#), [2662](#), [2682](#), [2682](#)
`__enumext_keyans_pic_skip_abs:N` [79](#), [2690](#), [2690](#), [2706](#)
`\l__enumext_keyans_pic_width_dim` [112](#), [2722](#), [2729](#)
`__enumext_keyans_redefine_item:` [66](#), [2123](#), [2123](#), [2236](#)
`__enumext_keyans_safe_exec:` [2509](#), [2525](#), [2525](#)
`__enumext_keyans_show_left:n` [66](#), [1963](#), [1963](#), [2115](#), [2653](#)
`__enumext_keyans_starred_item:n` [66](#), [2112](#), [2112](#), [2131](#)
`__enumext_keyans_store_ref:` [61](#), [1864](#), [1864](#), [2120](#), [2646](#), [3384](#)
`__enumext_keyans_store_ref_aux_i:` [61](#), [1864](#), [1876](#), [1879](#)
`__enumext_keyans_store_ref_aux_ii:` [62](#), [1864](#), [1905](#), [1907](#)
`\l__enumext_keyans_tmpa_dim` [82](#), [3392](#), [3393](#), [3413](#), [3414](#)
`\l__enumext_keyans_tmpa_tl` [23](#), [93](#), [82](#), [2114](#), [2118](#), [3366](#), [3389](#), [3391](#), [3392](#), [3410](#), [3412](#), [3413](#)
`\l__enumext_keyans_tmpb_tl` [93](#), [82](#), [3367](#), [3379](#), [3381](#)
`\l__enumext_label_copy_i_tl` [1781](#), [1883](#), [1888](#), [1893](#), [1898](#)
`\l__enumext_label_copy_v_tl` [1893](#)
`\l__enumext_label_copy_vi_tl` [1888](#)
`\l__enumext_label_copy_vii_tl` [1756](#), [1767](#), [1798](#), [1883](#)
`\l__enumext_label_copy_viii_tl` [1898](#)
`\l__enumext_label_copy_X_tl` [131](#)
`\l__enumext_label_fill_left_v_tl` [2169](#)
`\l__enumext_label_fill_left_X_tl` [70](#)
`\l__enumext_label_fill_right_v_tl` [2176](#)
`\l__enumext_label_fill_right_X_tl` [70](#)
`\l__enumext_label_font_style_v_tl` [2170](#), [2657](#)
`\l__enumext_label_font_style_vii_tl` [3079](#)
`\l__enumext_label_font_style_viii_tl` [3445](#)
`\l__enumext_label_i_tl` [479](#)
`\l__enumext_label_ii_tl` [479](#)
`\l__enumext_label_iii_tl` [479](#)

```

\l__enumext_label_iv_tl . . . . . 479
\__enumext_label_style:Nnn 22, 29, 331, 331, 346,
    484, 504, 520, 524
\l__enumext_label_v_tl . . 60, 62, 517, 1856, 1925,
    1967, 1974, 1989, 1996, 2114, 2118, 2513, 2652, 2654
\l__enumext_label_vi_tl . 60, 62, 517, 1853, 1922,
    2652, 2654, 2658
\l__enumext_label_vii_tl . 499, 3006, 3031, 3038
\l__enumext_label_viii_tl 499, 3350, 3374, 3378,
    3391, 3412
\l__enumext_label_width_by_box . . 40, 327, 328
\__enumext_label_width_by_box:Nn 29, 325, 325,
    330, 342, 558, 3392, 3413
\l__enumext_labelsep_i_dim . . . 1971, 1993, 3395,
    3416
\l__enumext_labelsep_v_dim . . . . . 2575
\l__enumext_labelsep_vii_dim . 2742, 2751, 2793,
    3029, 3089, 3105
\l__enumext_labelsep_viii_dim 3153, 3162, 3204,
    3455, 3471
\l__enumext_labelwidth_i_dim . 1970, 1992, 3395,
    3416
\l__enumext_labelwidth_v_dim . . . . . 2575
\l__enumext_labelwidth_vii_dim . . . 2742, 2750,
    2793, 3082, 3086, 3104
\l__enumext_labelwidth_viii_dim . . 3153, 3161,
    3204, 3448, 3452, 3470
\l__enumext_leftmargin_tmp_v_bool . 79, 2697
\l__enumext_leftmargin_tmp_X_bool . . . . 44
\l__enumext_leftmargin_tmp_X_dim . . . . . 44
\l__enumext_leftmargin_X_dim . . . . . 44
\__enumext_level: 186, 186, 422, 424, 425, 433, 435,
    653, 657, 661, 728, 732, 736, 740, 824, 826, 828, 830,
    863, 865, 867, 869, 873, 913, 916, 935, 944, 950, 955,
    959, 970, 974, 975, 980, 1016, 1020, 1193, 1199, 1246,
    1248, 1250, 1253, 1260, 1262, 1264, 1267, 1558, 1566,
    1570, 1574, 1819, 1822, 1823, 2056, 2057, 2061, 2062,
    2063, 2070, 2072, 2076, 2077, 2080, 2086, 2087, 2141,
    2144, 2146, 2153, 2154, 2155, 2158, 2161, 2304, 2306,
    2334, 2339, 2340, 2341, 2343, 2347, 2352, 2353, 2354,
    2356, 2372, 2385, 2392, 2403, 2405, 2408, 2409, 2411,
    2416, 2423, 2426, 2428, 2430, 2431, 2432, 2433, 2436,
    2442, 2447, 2453, 2456, 2458, 2471
\l__enumext_level_h_int . 20, 216, 441, 465, 1419,
    1436, 1775, 1792, 2877, 2878
\l__enumext_level_int 20, 188, 225, 836, 987, 1180,
    1413, 1752, 1762, 1768, 1774, 1782, 1790, 1797, 2251,
    2318, 2319, 2326, 2370, 2383, 2438, 2496, 2539, 2626,
    2957, 2967, 3136, 3293
\__enumext_list_arg_two_i: . . . . . 2211
\__enumext_list_arg_two_ii: . . . . . 2211
\__enumext_list_arg_two_iii: . . . . . 2211
\__enumext_list_arg_two_iv: . . . . . 2211
\__enumext_list_arg_two_v: . 66, 2211, 2515, 2698
\__enumext_list_arg_two_vii: . . . . 2257, 2860
\__enumext_list_arg_two_viii: . . . . 2257, 3269
\l__enumext_listoffset_v_dim . . . . . 2577
\l__enumext_listparindent_vii_dim . . . 3092
\l__enumext_listparindent_viii_dim . . . 3458
\__enumext_make_label: 30, 65, 67, 2149, 2149, 2246
\l__enumext_mark_answer_sym_tl . 56, 107, 1474,
    1628, 1834, 1978, 3399
\l__enumext_mark_position_str 107, 1478, 1479,
    1501, 1502, 1626
\l__enumext_mark_ref_sym_tl . . 107, 1488, 1732,
    1945
\__enumext_mini_addvspace: . . 44, 73, 1009, 1009,
    2413
\__enumext_mini_addvspace_vii: 46, 1162, 1162,
    2818
\__enumext_mini_addvspace_viii: 46, 1162, 1168,
    3229
__enumext_mini_env* . . . . . 903
\__enumext_mini_right_cmd:n . 47, 48, 1188, 1190,
    1190
\__enumext_mini_set_vskip: . . 42, 910, 910, 1011
\__enumext_mini_set_vskip_vii: 45, 1105, 1105,
    1164
\__enumext_mini_set_vskip_viii: 45, 1105, 1127,
    1170
\__enumext_minipage:w 27, 240, 242, 905, 2729, 3091,
    3457
\l__enumext_minipage_active_v_bool . . 76, 77,
    2558, 2583, 2596, 2604
\g__enumext_minipage_active_vii_bool . . . 82,
    2829, 2834, 2846
\l__enumext_minipage_active_vii_bool . 2814,
    2825
\g__enumext_minipage_active_viii_bool 3240,
    3245, 3257
\l__enumext_minipage_active_viii_bool 3225,
    3236
\g__enumext_minipage_active_X_bool . . . 153
\l__enumext_minipage_active_X_bool . . . . 58
\g__enumext_minipage_after_skip 58, 1109, 1121,
    2844, 3255
\l__enumext_minipage_after_skip 42, 43, 74, 77,
    58, 926, 941, 961, 977, 992, 998, 1004, 1018, 1028,
    1037, 1040, 1052, 1070, 1081, 1097, 1129, 1142, 1156,
    2480, 2613
\g__enumext_minipage_center_vii_bool . 2838,
    2847
\g__enumext_minipage_center_viii_bool 3249,
    3258
\g__enumext_minipage_center_X_bool . . . 153
\l__enumext_minipage_hsep_v_dim . . . 76, 2556
\l__enumext_minipage_hsep_vii_dim . . . . 2812
\l__enumext_minipage_hsep_viii_dim . . . 3223
\l__enumext_minipage_left_skip 42, 76, 58, 918,
    933, 952, 967, 1014, 1024, 1029, 1035, 1044, 1061,
    1073, 1093, 1103, 1107, 1112, 1116, 1130, 1134, 1148,
    1166, 1172
\l__enumext_minipage_left_v_dim 76, 2554, 2562
\l__enumext_minipage_left_vii_dim 2808, 2820
\l__enumext_minipage_left_viii_dim 3219, 3231
\l__enumext_minipage_left_X_dim . . . . . 58
\g__enumext_minipage_right_skip 58, 1108, 1113,
    1117, 2837, 3248
\l__enumext_minipage_right_skip . . 42, 58, 922,
    937, 957, 972, 1030, 1036, 1048, 1066, 1077, 1131,
    1138, 1152, 1200, 1217
\l__enumext_minipage_right_v_dim . . 76, 1211,
    1216, 2552, 2556
\g__enumext_minipage_right_vii_dim 82, 2816,
    2836, 2849
\l__enumext_minipage_right_vii_dim 82, 2806,
    2811, 2817
\g__enumext_minipage_right_viii_dim . . 3227,
    3247, 3260

```

`\l__enumext_minipage_right_viii_dim` .. 3217, 3222, 3228
`\g__enumext_minipage_right_X_dim` 153
`\g__enumext_minipage_right_X_skip` 153
`\g__enumext_minipage_stat_int` . 73, 76, 58, 1205, 1222, 2412, 2473, 2478, 2559, 2606, 2611
`\g__enumext_miniright_code_vii_tl` . 82, 2842, 2848
`\g__enumext_miniright_code_viii_tl` 3253, 3259
`\g__enumext_miniright_code_X_tl` 153
`__enumext_multi_addvspace`: ... 41, 73, 858, 858, 2444
`__enumext_multi_set_vskip`: .. 40, 822, 822, 860
`\l__enumext_multicols_above_ii_skip` ... 841
`\l__enumext_multicols_above_iii_skip` .. 847
`\l__enumext_multicols_above_iv_skip` ... 853
`\l__enumext_multicols_above_v_skip` 877, 891, 901
`\l__enumext_multicols_above_X_skip` 52
`\l__enumext_multicols_below_v_skip` 881, 895, 2598
`\l__enumext_multicols_below_X_skip` 52
`__enumext_multicols_start`: 73, 2418, 2420, 2420
`__enumext_multicols_stop`: 73, 1195, 2450, 2450, 2482
`__enumext_newlabel:nn` 24, 28, 60, 283, 283, 1808, 1911
`\l__enumext_newlabel_arg_one_tl` 24, 28, 59, 61, 131, 1731, 1801, 1809, 1900, 1912, 1943
`\l__enumext_newlabel_arg_two_tl` 24, 28, 58, 131, 1755, 1765, 1779, 1795, 1810, 1887, 1892, 1897, 1913
`__enumext_parse_keys:n` 2300, 2323, 2323
`__enumext_parse_keys_vii:n` .. 2855, 2884, 2884
`__enumext_parse_keys_viii:n` . 3265, 3298, 3298
`__enumext_parse_store_keys:n` . 71, 2329, 2332, 2332
`__enumext_parse_store_keys_vii:n` . 83, 2891, 2895, 2895
`\l__enumext_parsep_i_skip` . 839, 841, 990, 1038
`\l__enumext_parsep_ii_skip` 845, 847, 996
`\l__enumext_parsep_iii_skip` ... 851, 853, 1002
`\l__enumext_parsep_vii_skip` 3093
`\l__enumext_parsep_viii_skip` 3459
`\l__enumext_partopsep_v_skip` .. 893, 897, 1064, 1068, 1075, 1079, 1095, 1099
`\l__enumext_partopsep_viii_skip` 1140
`__enumext_phantomsection`: 28, 247, 276, 280, 296
`__enumext_print_footnote`: ... 2015, 2038, 3111, 3477
`__enumext_print_keyans_box:NN` 56, 1620, 1620, 1633, 1821, 1969, 1991, 3395, 3416
`\l__enumext_print_keyans_i_tl` 3528, 3557
`\l__enumext_print_keyans_ii_tl` ... 3533, 3558
`\l__enumext_print_keyans_iii_tl` .. 3538, 3559
`\l__enumext_print_keyans_iv_tl` ... 3543, 3560
`\l__enumext_print_keyans_vii_tl` .. 3548, 3561
`\l__enumext_print_keyans_X_tl` 96
`__enumext_printkeyans:nnn` . 97, 3562, 3565, 3565
`__enumext_redefine_item`: . 66, 2089, 2089, 2245
`\l__enumext_ref_aux_tl` 142, 422, 424, 427, 443, 445, 448, 453, 455, 458
`\l__enumext_ref_key_arg_tl` .. 142, 416, 421, 428, 440, 449, 459
`__enumext_regex_label_ref_key`: .. 31, 32, 411, 411, 423, 444, 454
`__enumext_register_counter_style:Nn` .. 315, 315, 320, 321, 322, 323, 324
`__enumext_remove_extra_parsep_vii`: .. 2870, 3120, 3120
`__enumext_remove_extra_parsep_viii`: . 3279, 3486, 3486
`__enumext_renew_footnote`: ... 2015, 2019, 3063, 3438
`\l__enumext_resume_bool` 22, 35, 1380, 2228
`__enumext_resume_counter`: . 51, 1341, 1371, 1371
`__enumext_resume_counter_star`: 1343
`__enumext_resume_counter_vii`: 51, 1350, 1371, 1382
`\g__enumext_resume_int` 22, 74, 35, 1375, 1386, 2229, 2486
`\l__enumext_resume_vii_bool` ... 35, 1391, 2275
`\g__enumext_resume_vii_int` .. 84, 35, 2276, 2936
`__enumext_safe_exec`: 2299, 2316, 2316
`__enumext_safe_exec_vii`: ... 2854, 2875, 2875
`__enumext_safe_exec_viii`: ... 3264, 3284, 3284
`__enumext_set_error:nn` 3643, 3653, 3655
`__enumext_set_label_ref:n` ... 31, 419, 419, 491
`__enumext_set_label_ref_h:n` . 32, 438, 438, 511
`__enumext_set_parse:n` 3626, 3643, 3643
`\l__enumext_setkey_tmpa_int` ... 91, 3619, 3623
`\l__enumext_setkey_tmpa_seq` 91, 3617, 3627, 3633, 3635, 3637, 3650
`\l__enumext_setkey_tmpa_tl` 91, 3625, 3629
`\l__enumext_setkey_tmpb_seq` 91, 3618, 3621, 3625, 3626
`\l__enumext_setkey_tmpb_tl` 91, 3645, 3647, 3648
`\l__enumext_show_answer_bool` . 107, 1482, 1486, 1505, 1509, 1828, 1965, 2649, 3387
`__enumext_show_length:nnn` .. 37, 196, 196, 3695, 3696, 3697, 3698, 3699, 3700, 3701, 3702, 3703, 3704, 3710, 3711, 3712, 3713, 3714, 3715, 3716, 3717, 3718, 3719
`\l__enumext_show_position_bool` . 63, 107, 1483, 1485, 1506, 1508, 1832, 1976, 2650, 3397
`\g__enumext_standar_bool` 26, 20, 218, 1439, 2502
`\l__enumext_standar_bool` . 20, 1760, 1773, 1789, 2321, 2485
`\g__enumext_standar_keyans_pic_star_env_int` 128
`\g__enumext_standar_keyans_star_env_int` 127
`\g__enumext_standar_star_env_int` .. 124, 219
`__enumext_standard_item_vii:w` .. 85, 86, 2991, 2993, 2993
`__enumext_standard_item_viii:w` 92, 3335, 3337, 3337
`\g__enumext_starred_bool` 26, 83, 84, 20, 227, 1418, 1751, 1761, 1791, 1881, 2367, 2380, 2463, 2944, 2950, 3142
`\l__enumext_starred_bool` . 83, 84, 20, 1684, 1692, 1776, 1817, 2882, 2951
`__enumext_starred_columns_set_vii`: .. 2736, 2736, 2863
`__enumext_starred_columns_set_viii`: . 3147, 3147, 3272
`__enumext_starred_item:nn` ... 2066, 2066, 2095
`__enumext_starred_item_exec`: . 93, 3376, 3376, 3442

```

\__enumext_starred_item_vii:w 85, 86, 2990, 3009,
    3009
\__enumext_starred_item_vii_aux_i:w .. 3009,
    3014, 3017
\__enumext_starred_item_vii_aux_ii:w . 3009,
    3015, 3020, 3022
\__enumext_starred_item_vii_aux_iii:w 3009,
    3025, 3034
\__enumext_starred_item_viii:w .. 92, 93, 3334,
    3353, 3353
\__enumext_starred_item_viii_aux_i:w . 3353,
    3358, 3361
\__enumext_starred_item_viii_aux_ii:w 3353,
    3359, 3369, 3371
\__enumext_starred_joined_item_vii:n . 81, 85,
    2755, 2755, 2988
\__enumext_starred_joined_item_viii:n 89, 92,
    3166, 3166, 3332
\g__enumext_starred_keyans_star_env_int 126
\g__enumext_starred_star_env_int .. 125, 228
\__enumext_start_from:NNn 33, 532, 532, 545, 567
\__enumext_start_item_tmp_vii: 83, 2866, 2973,
    2973
\__enumext_start_item_tmp_viii: 90, 3275, 3317,
    3317
\__enumext_start_item_vii:w 86, 3001, 3006, 3031,
    3038, 3040, 3040
\__enumext_start_item_viii:w .. 92, 3345, 3350,
    3374, 3419, 3419
\__enumext_start_list:nn 27, 69, 79, 234, 236, 2303,
    2512, 2663, 2858, 3267
\__enumext_start_mini_vii: . 84, 2804, 2804, 2929
\__enumext_start_mini_viii: 91, 3215, 3215, 3309
\__enumext_start_store_level: . 72, 2302, 2361,
    2361
\__enumext_start_store_level_vii: . 85, 2857,
    2953, 2953
\l__enumext_start_X_int ..... 70, 562
\__enumext_stop_item_tmp_vii: . 83, 85, 86, 2865,
    2869, 2975, 3042
\__enumext_stop_item_tmp_viii: .. 90, 92, 3274,
    3278, 3319, 3421
\__enumext_stop_item_vii: 86, 87, 3042, 3096, 3096
\__enumext_stop_item_viii: . 95, 3421, 3462, 3462
\__enumext_stop_list: .. 27, 234, 237, 2312, 2522,
    2676, 2871, 3281
\__enumext_stop_mini_vii: 82, 84, 2823, 2823, 2933
\__enumext_stop_mini_viii: . 91, 3215, 3234, 3313
\__enumext_stop_store_level: .. 72, 2313, 2361,
    2390
\__enumext_stop_store_level_vii: .. 85, 2872,
    2953, 2963
\l__enumext_store_active_bool 23, 50, 71, 83, 82,
    1364, 1373, 1384, 1646, 2327, 2365, 2378, 2527, 2534,
    2622, 2680, 2889, 2955, 2965, 3292
\__enumext_store_addto_prop:n 54, 60, 1539, 1540,
    1548, 1671, 1862, 3383
\__enumext_store_addto_seq:n 55, 62, 1549, 1549,
    1553, 1560, 1574, 1582, 1591, 1609, 1617, 1735, 1948
\l__enumext_store_ans_bool 117, 1365, 1400, 1556,
    1580, 1587, 1615, 1659
\l__enumext_store_anskey_arg_tl 23, 57, 58, 82,
    1677, 1686, 1688, 1694, 1702, 1705, 1715, 1720, 1723,
    1729, 1735
\__enumext_store_anskey_code:nnnn . 57, 1665,
    1669, 1669
\__enumext_store_anskey_show_left:n 60, 1676,
    1826, 1826
\__enumext_store_anskey_show_wrap:n 60, 1814,
    1814, 1830, 1845
\l__enumext_store_columns_break_bool . 1640,
    1683
\l__enumext_store_columns_join_int 82, 1691,
    1696
\l__enumext_store_columns_sep_vii_bool 2910
\l__enumext_store_columns_sep_vii_dim 2915,
    2919
\l__enumext_store_columns_sep_X_bool ... 96
\l__enumext_store_columns_sep_X_dim .... 96
\l__enumext_store_columns_vii_bool ... 2897
\l__enumext_store_columns_vii_int 2902, 2906
\l__enumext_store_columns_X_bool ..... 96
\l__enumext_store_columns_X_int ..... 96
\__enumext_store_internal_ref: .. 57, 58, 1674,
    1737, 1737
\l__enumext_store_item_symbol_sep_dim 1638,
    1712, 1717
\l__enumext_store_item_symbol_tl . 1636, 1703,
    1707
\l__enumext_store_keyans_label_tl 23, 60, 62,
    82, 1850, 1853, 1856, 1860, 1862, 1919, 1922, 1925,
    1929, 1939, 1948, 1949, 3363, 3378, 3381, 3383, 3385
\__enumext_store_level_close: . 55, 1554, 1578,
    2394
\__enumext_store_level_close_vii: 1585, 1613,
    2969
\__enumext_store_level_open: .. 54, 55, 71, 1554,
    1554, 2373, 2386
\__enumext_store_level_open_vii: .. 83, 1585,
    1585, 2959
\g__enumext_store_name_tl 23, 74, 82, 1459, 1462,
    2466, 2504, 2948, 3144
\l__enumext_store_name_tl 23, 50, 82, 1355, 1356,
    1358, 1360, 1362, 1377, 1388, 1542, 1544, 1551, 1803,
    1804, 1840, 1902, 1903, 1984, 2466, 2487, 2490, 2937,
    2940, 2948, 3405
\l__enumext_store_opt_vii_tl . 1589, 1599, 1605,
    1609, 2904, 2917
\l__enumext_store_opt_X_tl ..... 96
\l__enumext_store_ref_key_bool 57, 1491, 1672,
    1726, 1866, 1936
\l__enumext_store_upper_level_X_bool ... 96
\l__enumext_store_write_aux_file_tl 24, 60, 62,
    131, 1806, 1812, 1909, 1915
\__enumext_storing_set:n 50, 51, 1339, 1348, 1353,
    1353
\l__enumext_the_counter_vii_tl ..... 445
\l__enumext_the_counter_viii_tl ..... 455
\l__enumext_the_counter_X_tl ..... 142
\__enumext_tmp:n 30, 34, 44, 51, 52, 57, 64, 69, 70, 81,
    96, 106, 134, 138, 146, 152, 153, 172, 204, 208, 645,
    649, 1393, 1410, 1467, 1495, 1496, 1513, 1739, 1746,
    1747, 1768, 1782, 1785, 1797, 1868, 1875, 2211, 2256,
    2257, 2295
\__enumext_tmp:nn 347, 368, 369, 397, 398, 410, 562,
    581, 626, 644, 702, 710, 711, 725, 790, 806, 807, 821,
    1226, 1242, 1514, 1538, 1999, 2014
\__enumext_tmp:nnn 479, 495, 496, 497, 498, 499, 515,

```

516	
_enumext_tmp:nnnnn	582, 607, 610, 613, 615, 617, 620, 623
_enumext_tmp:w	3511, 3514
\l_enumext_tmpa_vii_int	2746, 2749
\l_enumext_tmpa_viii_int	3157, 3160
\l_enumext_tmpa_X_int	153
\l_enumext_topsep_v_skip	879, 883, 1033, 1046, 1054, 1059, 1079, 1083, 2679, 2710
\l_enumext_topsep_vii_skip	1110, 1119, 1123
\l_enumext_topsep_viii_skip	1132, 1154, 1158
_enumext_use_key_ref:	31, 431, 431, 2247
_enumext_use_key_ref_h:	32, 463, 463, 2281
\l_enumext_vspace_a_star_v_bool	1275
\l_enumext_vspace_a_star_vii_bool	1297
\l_enumext_vspace_a_star_viii_bool	1308
\l_enumext_vspace_a_star_X_bool	70
_enumext_vspace_above:	48, 1243, 1243, 2399
_enumext_vspace_above_v:	49, 1271, 1271, 2550
\l_enumext_vspace_above_v_skip	1273, 1277, 1279
_enumext_vspace_above_vii:	49, 1293, 1293, 2926
\l_enumext_vspace_above_vii_skip	1295, 1299, 1301
_enumext_vspace_above_viii:	49, 1293, 1304, 3307
\l_enumext_vspace_above_viii_skip	1306, 1310, 1312
\l_enumext_vspace_b_star_v_bool	1286
\l_enumext_vspace_b_star_vii_bool	1319
\l_enumext_vspace_b_star_viii_bool	1330
\l_enumext_vspace_b_star_X_bool	70
_enumext_vspace_below:	49, 1257, 1257, 2484
_enumext_vspace_below_v:	49, 1282, 1282, 2618
\l_enumext_vspace_below_v_skip	1284, 1288, 1290
_enumext_vspace_below_vii:	50, 1315, 1315, 2935
\l_enumext_vspace_below_vii_skip	1317, 1321, 1323
_enumext_vspace_below_viii:	50, 1315, 1326, 3315
\l_enumext_vspace_below_viii_skip	1328, 1332, 1334
_enumext_widest_from:nnNn	34, 546, 546, 561, 573
\g_enumext_widest_label_tl	22, 29, 40, 335, 339, 343
\l_enumext_wrap_label_opt_v_bool	2108
\l_enumext_wrap_label_opt_vii_bool	86, 3000
\l_enumext_wrap_label_opt_viii_bool	92, 3344
\l_enumext_wrap_label_opt_X_bool	70
\l_enumext_wrap_label_v_bool	2104, 2108, 2116, 2171
\l_enumext_wrap_label_vii_bool	86, 2999, 3004, 3012, 3080
\l_enumext_wrap_label_viii_bool	92, 3343, 3348, 3356, 3446
\l_enumext_wrap_label_X_bool	70
_enumext_wrapper_label_v:n	2173, 2658
_enumext_wrapper_label_vii:n	3083
_enumext_wrapper_label_viii:n	3449
_enumext_zero_count_level:	202, 202
_enumext_zero_parsep:	43, 930, 985, 985
enumext*	4, 2851
enumXi	307
enumXii	307
enumXiii	307
enumXiv	307
enumXv	307
enumXvi	307
enumXvii	307
enumXviii	307
Environments provide by enumext:	
enumext*	21, 22, 24–26, 29, 31–33, 36–39, 45, 46, 49–59, 61, 63, 64, 71, 72, 83, 85, 86, 88, 90, 92, 94, 96, 99, 101
enumext	21, 22, 24, 26, 29–32, 34, 35, 37–45, 47–57, 59, 61, 63, 64, 66–72, 74, 75, 79, 80, 82, 85, 96, 99, 100
keyans*	21–23, 25, 26, 29, 31–33, 36–39, 45, 46, 49–52, 54, 61, 64, 91, 99, 101
keyanspic	21–24, 29, 30, 33, 47, 50–52, 54, 55, 60–63, 77–80, 100
keyans	21–24, 26, 29, 30, 33–35, 37–39, 41, 44, 45, 47–52, 54, 55, 60–63, 66–69, 75, 77–79, 82, 92, 99, 100
Environments:	
enumext*	70
keyans*	70
list	26, 27, 68–70
lrbox	80, 87, 94, 95
minipage	26, 27, 39, 41, 42, 77, 79, 80, 87, 95
multicols	40–42, 47, 73, 74, 76, 77
exp commands:	
\exp_after:wN	3514
\exp_args:Ne	2325, 3502
\exp_not:N	150, 338, 427, 448, 458, 659, 673, 674, 685, 686, 697, 698, 1731, 1837, 1838, 1941, 1981, 1982, 3402, 3403, 3511
\exp_not:n	427, 428, 448, 449, 458, 459, 660, 1522, 1529, 1696, 1707, 1717, 1731, 1732, 1809, 1912, 1943, 1945, 2343, 2356, 2906, 2919
F	
\fbox	1472
file commands:	
\file_input_stop:	3812
first	711
font	347
\footnote	64
\footnote	64, 2023
\footnotemark	2033
\footnotesize	1838, 1982, 3403
\footnotetext	2017
G	
\getkeyans	13, 95, 3500
group commands:	
\group_begin:	1658, 1836, 1980, 3059, 3078, 3401, 3434, 3444, 3522, 3556
\group_end:	1667, 1843, 1987, 3088, 3100, 3408, 3454, 3466, 3524, 3563
H	
\hbadness	3107, 3473
hbox commands:	
\hbox_set:Nn	327
\hfill	377, 381, 386, 387, 1197, 1215, 1731, 1941, 2828, 3239
hook commands:	
\hook_gput_code:nnn	9, 180, 184, 245

\hook_gset_rule:nnnn	246
\hspace	3118, 3484
\hyperlink	58, 62
\hyperlink	1731, 1941
\hypertarget	28
\hypertarget	275
I	
\IfHyperBoolean	253
\IfPackageLoadedTF	11, 249, 263
\ignorespaces	662
\inputlineno	219, 228
int commands:	
\int_add:Nn	2788, 3199
\int_case:nn	836, 987, 1413, 1436
\int_compare:nNnTF ..	216, 225, 441, 465, 912, 1031, 1176, 1180, 1184, 1456, 1650, 1654, 1851, 1885, 1890, 1895, 1920, 2319, 2370, 2383, 2422, 2438, 2452, 2473, 2496, 2535, 2539, 2568, 2593, 2606, 2626, 2630, 2685, 2758, 2768, 2784, 2878, 2957, 2967, 3113, 3122, 3136, 3169, 3179, 3195, 3287, 3293, 3479, 3488, 3623
\int_compare_p:nNn ..	1419, 1752, 1762, 1774, 1775, 1790, 1792
\int_decr:N	2787, 3198
\int_eval:n	1544, 1804, 1838, 1903, 1982, 2229, 2232, 2276, 2279, 2776, 3187, 3403
\int_from_alph:n	540, 554
\int_from_roman:n	542, 556
\int_gadd:Nn	2789, 3200
\int_gdecr:N	1422, 1427, 1430, 1433, 1441
\int_gincr:N	1663, 1952, 2054, 2084, 2412, 2559, 2977, 3055, 3321
\int_gset:Nn	219, 228, 1375, 1386, 2031
\int_gset_eq:NN	2028, 2486, 2489, 2936, 2939
\int_gzero:N	206, 1205, 1222, 1464, 1465, 2478, 2611, 3131, 3497
\int_if_exist:NNTF	1366, 2487, 2937
\int_incr:N	2318, 2531, 2684, 2877, 2976, 3286, 3320
\int_mod:nn	3124, 3490
\int_new:N	20, 21, 22, 23, 24, 36, 38, 58, 74, 86, 93, 101, 114, 115, 122, 123, 124, 125, 126, 127, 128, 139, 156, 157, 158, 159, 160, 1368
\int_set:Nn	536, 540, 542, 1519, 1691, 2723, 2724, 2746, 2757, 2763, 2779, 3107, 3157, 3168, 3174, 3190, 3473, 3619
\int_set_eq:NN	2338, 2786, 2901, 3197
\int_step_function:nnN	1768, 1782, 1797
\int_step_inline:nnn	2725, 3646
\int_to_roman:n	188, 1748, 1786
\int_use:N ..	913, 1377, 1388, 2232, 2251, 2279, 2326, 2423, 2432, 2447, 2453, 2761, 2762, 2774, 3172, 3173, 3185
\int_zero:N	3116, 3482
\c_one_int ..	1419, 1984, 2746, 2765, 2771, 2777, 2781, 2784, 3157, 3176, 3182, 3188, 3192, 3195
\c_zero_int ..	216, 225, 1752, 1762, 1774, 1775, 1790, 1792, 2957, 2967, 3127, 3493
\item	27, 38, 39, 55, 64, 77, 78, 80, 83, 90
\item	64, 66, 85, 86, 92, 94, 238, 1562, 1568, 1593, 1601, 1688, 1922, 1925, 2091, 2125, 2864, 2866, 3273, 3275, 3385
\item*	5, 11, 2123
item-pos*	1999
item-sym*	1999
\itemindent	22, 69
\itemindent	68

itemindent	626
\itemsep	79, 80
\itemsep	2699, 2705
\itemwidth	2753, 2797, 2801, 3164, 3208, 3212

K

keyans	11, 2507
keyans*	11, 3262
keyanspic	12, 2660

Keys for environments provide by **enumext**:

above*	23, 48, 49
above	23, 48, 49, 72, 76, 84, 91
after	37–39, 74, 77, 84, 91
align	23, 30, 31, 67, 87
before*	37, 38, 72, 84, 91
before	37, 38, 76
below*	23, 48–50
below	23, 48–50, 74, 77, 84, 91
check-ans ..	23, 24, 26, 50, 52, 57, 62–66, 72, 74, 88, 99
columns-sep*	24, 54, 71, 83
columns-sep	39, 55, 71, 73, 76, 83
columns*	24, 54, 71, 83
columns	22, 39, 42, 48, 55, 71, 73, 76, 83
first	37–39, 87
font	30, 67, 87
item-pos*	56, 58, 63
item-sym*	22, 56, 58, 63, 65
item*-sep	65
itemindent	23, 35, 36, 66, 87
itemsep	35, 70
labelsep	30, 65, 68, 87
labelwidth	29, 30, 32–34, 68
label	22, 29, 33, 34, 80
lisparindent	70
list-indent	22, 35, 36, 79
list-offset	35, 36
listparindent	35, 87
mark-ans	24, 53, 60
mark-pos	53, 54
mark-ref	24, 53, 58
mini-env ..	23, 39, 42, 47, 48, 64, 72, 76, 82, 84, 90, 91
mini-sep	23, 39, 72, 76
miniright*	23, 39
miniright	23, 39, 46, 82
minirigth*	26
minirigth	26
no-store	24, 52, 53
noitemsep	35, 43
nosep	35, 43
parindent	70
parsep	35, 70, 87
partopsep	35
ref	25, 31, 32
resume	22, 50, 51, 69, 74, 84
rightmargin	35
save-ans ..	23, 50, 51, 54, 55, 57, 60, 62, 66, 74, 75, 78, 84, 92, 93, 95, 96
save-key	24
show-ans	24, 53, 54, 56, 57, 60, 66, 93
show-length	26, 37, 69, 99
show-pos	24, 53, 54, 56, 57, 60, 66, 93
start	23, 26, 33, 34, 69
store-brk	56, 57
store-ref	24, 28, 53, 57, 58, 61, 62, 66, 93
topsep	35

widest	22, 26, 34
wrap-ans	53, 56, 60
wrap-label*	30, 64, 67, 86, 87, 92
wrap-label	30, 67, 86, 87, 92
keys commands:	
\keys_define:nn	349, 371, 400, 481, 501, 517, 564, 584, 628, 647, 704, 713, 792, 809, 1228, 1337, 1346, 1395, 1469, 1498, 1516, 1634, 2001, 3526, 3589
\l_keys_key_str	3680
\keys_set:nn	363, 816, 1233, 1238, 1680, 2325, 2546, 2888, 3302, 3591, 3592, 3593, 3594, 3595, 3596, 3597, 3598, 3599, 3600, 3601, 3602, 3640
L	
label	479, 499, 517
Labels provide by enumext:	
\Alph*	29
\Roman*	29
\alph*	29
\arabic*	29, 31
\roman*	29
\labeledsep	80
\labelsep	2700, 2703
labelsep	347
\labelwidth	29, 80
\labelwidth	2700, 2701
labelwidth	347
\leftmargin	22, 69
\leftmargin	68, 2700
legacy commands:	
\legacy_if:nTF	3043, 3046, 3422, 3425
\legacy_if_gset_false:n	906
\legacy_if_set_false:n	3045, 3424
\legacy_if_set_true:n	3005, 3030, 3037, 3050, 3349, 3373, 3429
\linewidth	72, 76
\linewidth	2407, 2556, 2722, 2749, 2810, 3160, 3221
\list	27
\list	236
list-indent	626
list-offset	626
\listparindent	2702
listparindent	626
\lrbox	3060, 3435
M	
\makebox	80
\makebox	1624, 1626, 2145, 3074, 3082, 3086, 3448, 3452
\makelabel	64, 67, 80
\makelabel	67, 2151, 2167
\makesavenoteenv	269
mark-ans	1467
mark-pos	1467, 1496
mark-ref	1467
mini-env	790
mini-sep	790
\minipage	27
\minipage	242
\miniright	9, 47, 1174, 2476, 2609
\miniright*	9
mode commands:	
\mode_if_vertical:TF	861, 889, 1012, 1091
\mode_leave_vertical:	659, 673, 685, 697, 1593, 1601, 1622, 2143, 3072

msg commands:	
\msg_error:nn	2537, 2541, 2628, 2687, 2880, 3289, 3295, 3603
\msg_error:nnn	1178, 1182, 1207, 1224, 3516, 3521, 3586, 3656
\msg_error:nnnn	1648, 1652, 1656, 2529, 2624, 2632
\msg_fatal:nn	2320
\msg_fatal:nnn	301
\msg_info:nnn	13, 16, 251, 265
\msg_line_context:	3684, 3689, 3694, 3709, 3732, 3736, 3740, 3745, 3750, 3755, 3760, 3764, 3769, 3774, 3778, 3783, 3787, 3792, 3797, 3802, 3806, 3810
\msg_new:nnn	3657, 3661, 3665, 3669, 3674, 3678, 3682, 3687, 3692, 3707, 3722, 3729, 3734, 3738, 3743, 3748, 3753, 3758, 3762, 3767, 3772, 3776, 3781, 3785, 3790, 3795, 3800, 3804, 3808
\msg_term:nnn	1459
\msg_term:nnnn	2241, 2251, 2286, 2291
\msg_warning:nn	2475, 2608
\msg_warning:nnn	1462
\msg_warning:nnnn	1959, 2183, 2188, 2760, 2773, 3171, 3184
\multicolsep	73, 76
\multicolsep	2437, 2581
N	
\NeedsTeXFormat	3
\newcounter	304
\NewDocumentCommand	1174, 1644, 2620, 3500, 3554, 3610
\NewDocumentEnvironment	2296, 2507, 2660, 2851, 3262
\newlabel	28
\newlabel	287
no-store	1393
\noindent	83, 90
\noindent	2414, 2561, 2819, 2865, 3115, 3230, 3274, 3481
\nointerlineskip	2414, 2561, 2819, 3230
noitemsep	582
\nopagebreak	872, 900, 1023, 1102, 1165, 1171
\normalfont	1837, 1981, 3402
nosep	582
P	
Packages:	
enumext	21, 50, 68, 78, 98
enumitem	29
expl3	80
footnotehyper	28
hyperref	24, 26-28, 32, 58, 62, 86, 87, 98
lua-visual-debug	42
multicol	21, 98
shortlst	80
\par	872, 900, 1023, 1102, 1165, 1171, 1200, 1217, 1816, 2458, 2480, 2598, 2613, 2734, 2837, 2844, 3115, 3129, 3248, 3255, 3481, 3495
\parindent	3092, 3458
\parsep	40, 43, 79, 80
\parsep	1594, 1602, 2271, 2699, 2706, 2711
parsep	582
\parskip	3093, 3459
\partopsep	80
\partopsep	2272, 2704
partopsep	582
peek commands:	
\peek_meaning:NTF	2982, 2996, 3013, 3024, 3326, 3340, 3357
\peek_meaning_remove:NTF	2989, 3333

\peek_remove_spaces:n 2129

\phantomsection 28

\phantomsection 276

prg commands:

\prg_do_nothing: 280

\prg_new_protected_conditional:Npnn ... 190

\prg_replicate:nn 199, 3727

\prg_return_false: 194

\prg_return_true: 193

\printkeyans 13, 96, 3554

prop commands:

\prop_count:N .. 1544, 1804, 1840, 1903, 1984, 3405

\prop_gput_if_not_in:Nnn 1539, 1542

\prop_if_exist:NTF 1356, 3520

\prop_item:Nn 3523

\prop_new:N 1358

\ProvidesExplPackage 4

R

\raggedcolumns 2446, 2587

\ref 58, 61

ref 479, 499

\refstepcounter 3052, 3431

regex commands:

\regex_match:nnTF 192, 539, 541, 553, 555, 2336, 2349, 2899, 2912

\regex_replace_once:nnN 415

\renewcommand 427, 448, 458

\RenewDocumentCommand ... 2023, 2091, 2125, 2151, 2167

\RequirePackage 17

resume 1337

resume* 1337

rightmargin 626

\Roman 29, 34

\Roman 323

\roman 29, 34

\roman 324, 497, 3542

S

save-ans 1337

scan commands:

\scan_stop: 80, 2713, 2864, 3273, 3511, 3514

seq commands:

\seq_clear:N 3617

\seq_const_from_clist:Nn 3605

\seq_count:N 2673, 3621

\seq_gclear:N 2021, 2022

\seq_gput_right:Nn 1551, 2034, 2035

\seq_if_empty:NTF 2040, 3569, 3635

\seq_if_exist:NTF 1360, 3567

\seq_item:Nn 2731

\seq_map_function:NN 3626

\seq_map_inline:Nn .. 3575, 3580, 3614, 3636, 3637

\seq_map_pairwise_function:NNN 2042

\seq_new:N 94, 95, 112, 140, 141, 1362

\seq_pop_left:NN 3625

\seq_put_right:Nn 2634, 3633, 3650

\seq_set_from_clist:Nn 3618

\seq_set_map_e:NNn 3627

\seq_show:N 3571

\setcounter .. 550, 554, 556, 2229, 2231, 2276, 2278, 2678

\setenumext .. 5-8, 97, 3530, 3535, 3540, 3545, 3550, 3610

\setlength 1595, 1603

show-ans 1467, 1496

show-length 702

skip commands:

\skip_add:Nn . 841, 847, 853, 863, 867, 891, 895, 992, 998, 1004, 1014, 1018, 1040, 1093, 1097, 2699

\skip_eval:n 1594, 1602

\skip_gset:Nn 1113, 1117, 1121

\skip_gzero_new:N 1108, 1109

\skip_horizontal:N 674, 686, 698, 3075, 3089, 3455

\skip_horizontal:n 660, 1623, 1631, 2144, 2146, 3073

\skip_if_eq:nnTF . 839, 845, 851, 915, 949, 990, 996, 1002, 1033, 1038, 1059, 1110, 1132, 1245, 1259, 1273, 1284, 1295, 1306, 1317, 1328

\skip_new:N 54, 55, 59, 60, 61, 62, 63, 116, 170

\skip_set:Nn . 824, 828, 877, 881, 918, 922, 926, 933, 937, 941, 952, 957, 961, 967, 972, 977, 1035, 1036, 1037, 1044, 1048, 1052, 1061, 1066, 1070, 1073, 1077, 1081, 1112, 1116, 1134, 1138, 1142, 1148, 1152, 1156, 2693, 2707

\skip_set_eq:NN 2224, 2270, 2271, 3092, 3093, 3458, 3459

\skip_use:N 826, 830, 865, 869, 873, 893, 897, 916, 935, 944, 950, 955, 959, 970, 974, 975, 980, 1016, 1020, 1046, 1246, 1250, 1253, 1260, 1264, 1267, 2458

\skip_zero:N 2272, 2437, 2581, 2704, 2705

\skip_zero_new:N 1028, 1029, 1030, 1107, 1129, 1130, 1131

\c_zero_skip . 839, 845, 851, 916, 950, 990, 996, 1002, 1033, 1038, 1059, 1110, 1132, 1246, 1260, 1273, 1284, 1295, 1306, 1317, 1328

\small 3532, 3537, 3542, 3547, 3552

\star 2005

start 562

\stepcounter 2027, 2641

store-ref 1467

str commands:

\c_backslash_str 3736, 3745, 3746, 3750, 3751, 3755, 3756, 3787, 3788, 3792, 3797, 3798

\c_colon_str 1803, 1902, 3511

\str_case:nn 212

\str_count:n 199, 3727

\str_if_eq:nnTF 2234, 2282

\str_if_eq_p:nn 2227, 2275

\str_if_in:nnTF 3507

\str_new:N 111, 165

\str_set:Nn ... 403, 404, 405, 1478, 1479, 1501, 1502

\string 269

\strutbox 920, 924, 928, 939, 943, 954, 963, 969, 979, 992, 998, 1004, 1035, 1036, 1037, 1040, 1050, 1054, 1063, 1070, 1075, 1083, 1112, 1113, 1116, 1123, 1136, 1144, 1150, 1158, 2709

T

TeX and L^AT_EX 2_ε commands:

\@auxout 285

\@currenvir 212

\protected@write 285

text commands:

\text_expand:n 3503

\textasteriskcentered 1475, 1489

\thepage 291

tl commands:

\c_space_tl 1860, 1929, 1974, 1996, 3366, 3367, 3694, 3709

\tl_clear:N 376, 382, 1677, 1850, 1919, 3363

\tl_clear_new:N 333

\tl_const:Nn 142, 317

<code>\tl_gclear:N</code>	1961, 2162, 2504, 2848, 3076, 3144, 3259
<code>\tl_gput_right:Nn</code>	318
<code>\tl_greplace_all:Nnn</code>	339
<code>\tl_gset:Nn</code>	1949, 2466, 2948, 3019
<code>\tl_gset_eq:NN</code>	335, 2072, 3069
<code>\tl_if_blank:nTF</code>	3067, 3379, 3389, 3410
<code>\tl_if_empty:nTF</code>	433, 467, 473, 1558, 1589, 1703, 1957, 2141, 3648
<code>\tl_if_novalue:nTF</code>	1678, 1689, 1858, 1927, 1973, 1995, 2025, 2050, 2068, 2073, 2102, 2671, 2886, 3300, 3364, 3612
<code>\tl_map_inline:Nn</code>	336, 413
<code>\tl_new:N</code>	32, 39, 41, 42, 75, 76, 77, 83, 84, 85, 87, 88, 89, 91, 92, 98, 99, 109, 110, 121, 131, 132, 133, 136, 144, 145, 148, 149, 164, 167
<code>\tl_put_left:Nn</code>	1566, 1599, 1686, 1967, 1989, 3378, 3385
<code>\tl_put_right:Nn</code>	334, 425, 446, 456, 1520, 1527, 1570, 1605, 1688, 1694, 1702, 1705, 1715, 1720, 1723, 1729, 1755, 1765, 1779, 1795, 1801, 1806, 1853, 1856, 1860, 1887, 1892, 1897, 1900, 1909, 1922, 1925, 1929, 1939, 1974, 1996, 2341, 2354, 2904, 2917, 3381, 3391, 3412, 3528, 3533, 3538, 3543, 3548
<code>\tl_remove_all:Nn</code>	3647
<code>\tl_remove_once:Nn</code>	1743, 1872
<code>\tl_replace_all:Nnn</code>	338
<code>\tl_reverse:N</code>	1742, 1744, 1871, 1873
<code>\tl_set:Nn</code>	150, 303, 377, 381, 386, 387, 421, 440, 657, 671, 683, 695, 1355, 1474, 1488, 1834, 1978, 2070, 3366, 3367, 3399, 3645
<code>\tl_set_eq:NN</code>	344, 422, 424, 443, 445, 453, 455, 1741, 1870, 1883, 2114, 2118, 2652, 2654
<code>\tl_to_str:n</code>	3503
<code>\tl_trim_spaces:n</code>	334, 3633, 3645, 3651
<code>\tl_use:N</code>	340, 343, 435, 469, 475, 728, 732, 736, 740, 744, 748, 752, 756, 760, 764, 768, 772, 776, 780, 784, 788, 1628, 1748, 1756, 1767, 1781, 1786, 1798, 2057, 2063, 2087, 2105, 2109, 2117, 2153, 2154, 2161, 2169, 2170, 2176, 2304, 2513, 2657, 2842, 3079, 3090, 3094, 3253, 3445, 3456, 3460, 3557, 3558, 3559, 3560, 3561, 3629
token commands:	
<code>\token_to_str:N</code>	287
<code>\topsep</code>	1595, 1603
<code>topsep</code>	582
<code>\typeout</code>	220, 229, 255, 258, 268, 269, 1423, 1442
U	
<code>\u</code>	416
use commands:	
<code>\use:N</code>	200, 2158, 2306
<code>\use:n</code>	3509
<code>\use_none:nn</code>	279
<code>\usecounter</code>	2225, 2273
V	
<code>\value</code>	2486, 2491, 2936, 2941
<code>\vspace</code>	907, 1250, 1253, 1264, 1267, 1277, 1279, 1288, 1290, 1299, 1301, 1310, 1312, 1321, 1323, 1332, 1334, 1594, 1602, 2668, 2679, 3130, 3496
W	
<code>widest</code>	562
<code>wrap-ans</code>	1467
<code>wrap-label</code>	347
<code>wrap-label*</code>	347