

enumext

ENUMERATE EXERCISE SHEETS

V1.0 2024-09-25^{*}

©2024 by Pablo González[†]

CTAN: <https://www.ctan.org/pkg/enumext>

 <https://github.com/pablgonz/enumext>

Abstract

This package provides “*enumerated list*” environments compatible with tagging PDF for creating “*simple exercise sheets*” along with “*multiple choice questions*”, storing the `\answers` to these in memory using `multicol` and `scontents` packages and the `l3seq` and `l3prop` modules.

Contents

1	Introduction	1	6	The storage system	10
1.1	Description and usage	2	6.1	Keys for storage system	11
1.2	The concept of left margin	3	6.1.1	Keys for label and ref	11
1.3	User interface	3	6.1.2	Keys for wrap and display	11
1.3.1	Internal counters	3	6.1.3	Keys for debug and checking	12
1.3.2	Public dimension	3	6.2	The command <code>\anskey</code>	12
1.3.3	Support for <code>multicol</code>	3	6.2.1	Keys for <code>\anskey</code>	13
1.3.4	Support for <code>minipage</code>	4	6.3	The environment <code>anskey*</code>	13
1.3.5	The <code>\label</code> and <code>\ref</code> system	4	6.3.1	Keys for <code>anskey*</code>	13
1.3.6	Support for <code>\footnote</code>	4	6.4	The environment <code>keyans</code>	14
2	The environments provided	4	6.4.1	The <code>\item*</code> in <code>keyans</code>	14
2.1	The environment <code>enumext</code>	4	6.5	The environment <code>keyanspic</code>	15
2.2	The environment <code>enumext*</code>	5	6.5.1	The command <code>\anspic</code>	15
2.3	The command <code>\item*</code>	5	6.6	Printing stored content	16
2.3.1	Keys for <code>\item*</code>	5	6.6.1	The command <code>\getkeyans</code>	16
2.4	The command <code>\item</code> in <code>enumext*</code>	5	6.6.2	The command <code>\foreachkeyans</code>	16
3	The command <code>\setenumext</code>	6	6.6.3	The command <code>\printkeyans</code>	17
4	The command <code>\setenumextmeta</code>	6	7	Full examples	18
5	The <code>keyval</code> system	6	8	The way of non-enumerated lists	20
5.1	Keys for label and ref	6	9	References	22
5.2	Keys for spaces	7	10	Change history	23
5.2.1	Vertical spaces	7	11	Index of Documentation	24
5.2.2	Horizontal spaces	8	12	Implementation	26
5.3	Keys for add code	9	13	Index of Implementation	138
5.4	Keys for start, series and resume	9			
5.5	Keys for <code>multicols</code>	10			
5.6	Keys for <code>minipage</code>	10			
5.6.1	The command <code>\miniright</code>	10			
5.6.2	The key <code>mini-right</code>	10			

Motivation and acknowledgments

Usually it is enough to use the classic `enumerate` environment to generate “*simple exercise sheets*” or “*multiple choice questions*”, the basic idea behind `enumext` is to cover three points:

1. To have a simple interface to be able to write “*lists of exercises*” with “*answers*”.
2. To have a simple interface for writing “*multiple choice questions*”.
3. To have a simple interface for placing “*columns*” and “*drawings*” or “*tables*”.

This package would not be possible without Phelype Oleinik who has collaborated and adapted a large part of the code and all \LaTeX team for their great work and to the different members of the \TeX-SX community who have provided great answers and ideas. Here a note of the main ones:

1. Answer given by Alan Munn in `\topsep`, `\itemsep`, `\partopsep`, `\parsep` - what do they each mean (and what about the bottom)?
2. Answer given by Enrico Gregorio in `Understanding minipages` - aligning at top
3. Answer given by Ulrich Diez in `Different mechanics of hyperlink vs. hyperref`
4. Answer given by Enrico Gregorio in `Minipage and multicols`, vertical alignment

^{*}This file describes a documentation for v1.0, last revised 2024-09-25.

[†]E-mail: pablgonz@educarchile.cl.

License and Requirements

Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License (lpp), version 1.3 or later (<https://www.latex-project.org/lppl.txt>). The software has the status “maintained”.
The enumext package loads and requires multicol[3] and contents[4] packages, need to have a modern T_EX distribution such as T_EX Live or MiK_TE_X. It has been tested with the standard classes provided by L^AT_EX: book, report, article and letter on 10pt, 11pt and 12pt.

1 Introduction

In the L^AT_EX world there are many useful packages and classes for creating “lists of exercises”, “worksheets” or “multiple choice questions”, classes like exam[1] and packages like xsim[2] do the job perfectly, but they don’t always fit the basic day to day needs.

In my work (and in the work of many teachers) it is common to use “simple exercise sheets” also known as “informal lists of exercises”, as an example:

1. Factor $x^2 - 2x + 1$

2. Factor $3x + 3y + 3z$

3. True False

(a) $\alpha > \delta$

(b) L^AT_EXze is cool?

4. Related to Linux
- (a) You use linux?

(b) Usually uses the package manager?

(c) Rate the following package and class

i. xsim-exam

ii. xsim

iii. exsheets

Sometimes we are also interested in showing the “answers” along with the questions:

1. Factor $x^2 - 2x + 1$

*

$(x - 1)^2$

2. Factor $3x + 3y + 3z$

*

$3(x + y + z)$

3. True False

(a) $\alpha > \delta$

*

False

(b) L^AT_EXze is cool?

*

Very True!

4. Related to Linux
- (a) You use linux?

*

Yes

(b) Usually uses the package manager?

*

Yes, dnf

(c) Rate the following package and class

i. xsim-exam

*

doesn’t exist for now :(

ii. xsim

*

very good

iii. exsheets

*

obsolete

Or we are interested in referring to a specific question and its “answer”, for example:

The answer to 3.(b) is “Very True!” and the answer to 4.(c).ii is “very good”.

Or we are interested in printing all the “answers”:

1. $(x - 1)^2$

2. $3(x + y + z)$

3. (a) False

(b) Very True!

4. (a) Yes
- * (b) Yes, dnf

* (c) i. doesn’t exist for now :(

* ii. very good

* iii. obsolete

*

Another very common thing to use in my work is “multiple choice questions”, for example:

1. First type of questions

A) value

B) correct

C) value

D) value

2. Second type of questions

I. $2\alpha + 2\delta = 90^\circ$

II. $\alpha = \delta$

III. $\angle EDF = 45^\circ$

A) I only

B) II only

C) I and II only

D) I and III only

E) I, II, and III

★ 3. Third type of questions

(1) $2\alpha + 2\delta = 90^\circ$

(2) $\angle EDF = 45^\circ$

A) value

B) value

C) value

D) value

E) value
4. Question with image and label below:

A

A)

B


B)

A

C)

A

D)



E)

5. Question with image on left side:

A) value

B) value

C) value

D) correct

E) value

B
- Where what we are interested in the *label* and a “short note” that we leave as an explanation, and then print them:
- ©2024 by Pablo González L
- 2 / 153

1. B), $x = 5$

2. D)

3. C), some note
- * 4. E), A duck

* 5. D), “other note”

*

These “*simple worksheets*” or “*multiple choice questions*” appear to be easy to obtain using a combination of the `enumerate`, `minipage` and `multicols` environments, but like many things, what “*looks simple*” is not so simple.

The `enumext` package was created and designed to meet these small requirements in the creation of “*simple worksheets*” and “*multiple choice questions*”.

1.1 Description and usage

The `enumext` package defines enumerated environments using the `list` environment provided by \LaTeX , but “*does not redefine*” any internal commands associated with it such as `\list`, `\endlist` or `\item` outside of the “*scope*” in which they are defined.

- This package is NOT intend to replace the `enumerate` environment nor replace the powerful `enumitem`[6], the approach is intended to work without hindering either of them.

This package can be used with `xelatex`, `lualatex`, `pdflatex` and the classical `latex»dvips»ps2pdf` and is present in \TeX Live and \MiKTeX , use the package manager to install. For manual installation, download `enumext.zip` and unzip it, run `lualatex enumext.dtx` and move all files to appropriate locations, then run `mktexlsr`. To produce the documentation run `lualatex enumext.dtx` two times.

enumext.sty

enumext.pdf

README.md

enumext.dtx

»

»

»

»

TDS:tex/latex/enumext/

TDS:doc/latex/enumext/

TDS:doc/latex/enumext/

TDS:source/latex/enumext/

The package is loaded in the usual way:

\usepackage{enumext}

1.2 The concept of left margin

There is a direct relationship between the parameters `\leftmargin`, `\itemindent`, `\labelwidth` and `\labelsep` plus an “*extra space*” that makes it difficult to obtain the desired *horizontal spaces* in a `list` environment.

Usually we don’t want the `list` to go beyond the left margin of the page, but since these four values are related, that causes a problem. The `enumitem`[6] package adds the `\labelindent` parameter to solve some of these problems. A simplified representation of this in the figure 1.



Figure 1: Representation of horizontal lengths in `enumitem`.

The `enumext` package does NOT provide a user interface to set the values for `\leftmargin` and `\itemindent`, instead it provides the keys `list-offset` and `list-indent` which internally set the values for `\leftmargin` and `\itemindent`. The concepts of `\leftmargin` and `\itemindent` are different in `enumext`. The figure 2 shows the visual representation of idea.



Figure 2: Representation of horizontal lengths concept in `enumext`.

In this way we reduce a *little* the amount of parameters we have to pass. With the default values of keys `list-offset`, `list-indent`, `labelwidth` and `labelsep` the lists will have the (usually) expected output for “*simple worksheets*”. The figure 3 shows the visual representation.




Figure 3: Default horizontal lengths `list-offset=0pt`, `list-indent=\labelwidth+\labelsep` in `enumext`.

1.3 User interface

The user interface consists of two main list environments `enumext` (vertical) and `enumext*` (horizontal), the environment `anskey*` and the command `\anskey` to “store content” and the environments `keyans`, `keyans*` and `keyanspic` for multiple choice. It also provides the commands `\getkeyans` to print individual *stored content*, `\printkeyans` to print all *stored content*, `\miniright` for `minipage` and `\setenumext` to config all `[key = val]` options.

1.3.1 Internal counters

The package `enumext` uses internally the `enumXi`, `enumXii`, `enumXiii`, `enumXiv` counters for the four nesting levels of the `enumext` environment, the `enumXv` counter for the `keyans` environment, the `enumXvi` counter for the `keyanspic` environment, the counter `enumXvii` for `enumext*` environment and the counter `enumXviii` for `keyans*` environment.

- If any package defines these counters or they are user-defined in the document, the package will return a fatal error and abort the load.

1.3.2 Public dimension

The package `enumext` only provides a single public dimension `\itemwidth` and is intended for user convenience only and is not for internal use as such. The dimension `\itemwidth` is *rigid length* and contains the “width of the content” of each `\item` regardless of `labelwidth` and `labelsep`.

- If any package defines `\itemwidth` or they are user-defined `\itemwidth` in the document, the package will overwrite it without warning.

1.3.3 Support for multicol

The package provides direct support for using the `multicol`[3] package. This allows to obtain directly a two-column output as shown in the figure 4.



Figure 4: Representation of the two column output for a nested level in `enumext` environment.

The “non starred” version of the `multicols` environment is always used together with the `\raggedcolumns` command and is controlled by `columns` and `columns-sep` keys. It can be used in all nesting levels of the environment `enumext` and the environment `keyans` and can together with the `mini-env` key. If you need to force a start a new column `\columnbreak` must be used (see §5.5).

- The `\columnseprule` command is not available as a key and is set to “zero” for the inner levels and the `keyans` environment. If the value of this is set inside the document, it will affect “all environments” that use the `columns` key.

1.3.4 Support for minipage

The package provides direct support for `minipage` environment, this allows you to obtain an output like the one shown in figure 5.



Figure 5: Representation of the `mini-env` output for a nested level `enumext` environment.

The `minipage` environments on “left side” and “right side” is always used with “aligned on top” `[t]`. It can be used in all nesting levels of the environment `enumext` and the environment `keyans` and is controlled by `mini-env` and `mini-sep` keys. In order to switch from the “left” side `minipage` environment to the “right” side one must use the command `\miniright` (see §5.6).

1.3.5 The \label and \ref system

This package provides a user interface like the `enumitem`[6] package to customize the references which is activated by the `ref` key (§5.1), the standard \LaTeX `\label` and `\ref` commands work as usual. It also provides an “internal reference” system for the “stored content” by means of the key `save-ref` (§6.1.1) when the key `save-ans` (§6.1) is active.

- The implementation of `\label` and `\ref` together with the `save-ref` key are compatible with the `hyperref`[8] package.

1.3.6 Support for \footnote

This package provides an internal implementation for the `\footnote` command which is compatible with the `hyperref` package for the `enumext*` and `keyans*` environments, but will not produce the expected links, and if the `mini-env` key is used in `enumext` or `keyans` environments the output will look like the classic way they are displayed in the environment `minipage`.
The best way to solve this is to use Jean-François Burnol `footnotehyper`[9] package, it will support keeping the links if `hyperref` is loaded with the `hyperfootnotes=true` option (default) and will show the output numbered at the bottom of the page (as opposed to how it is displayed in the `minipage` environment). The way to load it is as follows:

```
\usepackage{footnotehyper}
\makesavenoteenv{enumext}
\makesavenoteenv{enumext*}
```

At the moment the `footnotehyper` package is not compatible with \LaTeX tagged PDF.

2 The environments provided

The package `enumext` provides two main list environments, the *vertical* environment `enumext` and the *horizontal* environment `enumext*`.

<code>enumext</code>	<code>\begin{enumext}[\langle keyval list \rangle]</code>	<code>\begin{enumext*}[\langle keyval list \rangle]</code>
<code>enumext*</code>	<code>\item \langle item content \rangle</code>	<code>\item \langle item content \rangle</code>
	<code>\item[\langle custom \rangle] \langle item content \rangle</code>	<code>\item[\langle custom \rangle] \langle item content \rangle</code>
	<code>\item*[\langle symbol \rangle][\langle offset \rangle] \langle item content \rangle</code>	<code>\item*[\langle symbol \rangle][\langle offset \rangle] \langle item content \rangle</code>
	<code>\end{enumext}</code>	<code>\end{enumext*}</code>

2.1 The environment enumext

The `enumext` is an environment that works in the same way as the standard `enumerate` environment provided by \LaTeX , `\item` and `\item[\langle custom \rangle]` commands work in the usual way. The environment can be nested with at most “four levels” and the options can be configured globally using `\setenumext` command and locally using `[\langle key = val \rangle]` in the environment.

Example with columns=2

1. This text is in the first level.
- A. This text is in the fourth level.
- (a) This text is in the second level.
- X This text is in the first level.
- i. This text is in the third level.
- ★ 2. This text is in the first level.

2.2 The environment enumext*

The `enumext*` is a *horizontal list environment* similar to the `enumerate*` environment provided by the `enumitem` package or `task` environment provided by the `task` package, `\item` and `\item[\langle custom \rangle]` work as usual. The options can be configured globally using `\setenumext` command and locally using `[\langle key = val \rangle]` in the environment.

Some considerations to take into account for this environment:

- The environment cannot be nested within itself or in the environment `keyans*`, but it can be nested within `enumext` and vice versa.
- Each “item” in the environment is placed within a `minipage` environment whose *width* is stored in the dimension `\itemwidth` that NOT includes `labelwidth`, `labelsep`, only the *width of the content*.
- You cannot have floating environments like `figure` or `table` but `\footnote` with `hyperref` support is supported if the `footnotehyper` package is loaded.
- You cannot have any standard list environments like `itemize`, `enumerate`, `description`, `quote`, `quotation`, `verse`, `center`, `flushleft`, `flushright`, `verbatim`, `tabbing`, `trivlist`, `list` and all environments created with `\newtheorem`.

Example with columns=2

1. This text is in the first level.
2. This text is in the first level.
- X This text is in the first level.
- ★ 4. This text is in the first level.

2.3 The command \item*

```
\item* \item*
\item*[\langle symbol \rangle]
\item*[\langle symbol \rangle][\langle offset \rangle]
```

The `\item*`, `\item*[\langle symbol \rangle]` and `\item*[\langle symbol \rangle][\langle offset \rangle]` works like the numbered `\item`, but placing a `\langle symbol \rangle` to the “left” of the `\langle label \rangle` separated from it by the `\langle offset \rangle` set by the the second optional argument. The default values for `\langle symbol \rangle` and `\langle offset \rangle` are `\$star$ ‘*’` and the value set by `labelsep` key.

The *starred argument* ‘*’ cannot be separated by spaces ‘ ’ from the command, i.e. `\item*` and the first optional argument does “not support” verbatim content. Can be configure with the keys `item-sym*` and `item-pos*` locally in the environment or globally using `\setenumext` command (§3).

- The behavior of `\item*` in the `enumext` and `enumext*` environments is NOT the same as in the `keyans` and `keyans*` environments.

2.3.1 Keys for \item*

`item-sym* = { \langle symbol \rangle }` default: `\$star$`
Sets the *symbol* to be displayed in the “left” of the box containing the current `\langle label \rangle` set by `labelwidth` key for `\item*` in `enumext` and `enumext*`. The *symbol* can be in text or math mode, for example `item-sym*={\ast}`.

`item-pos* = { \langle rigid length \rangle }` default: *by levels*
Sets the *offset* between the box containing the current `\langle label \rangle` defined by `labelwidth` key and the `\langle symbol \rangle` set by `item-sym*` key. The default values are set by `labelsep` key at each level. If positive values are passed it will *offset to the left* and if negative values are passed it will *offset to the right*.

2.4 The command \item in enumext*

The `\item` command for the `enumext*` environment provides an optional “first argument” `\item(\langle columns \rangle)` which “joins items” between columns. Let’s consider the following examples adapted directly from the `task` package:

```
\begin{enumext*}[widest=10,columns=4]
  \item The first
  \item* The second
  \item The third
  \item The fourth
  \item(3)* The fifth item is way too long for this and needs three columns
  \item The sixth
  \item The seventh
  \item(2)[X] The eighth item is way too long for this and needs two columns
    (\the\itemwidth)
  \item The ninth
  \item[Z] The tenth (\the\itemwidth)
\end{enumext*}
```

1. The first
- ★ 2. The second
3. The third
4. The fourth
- ★ 5. The fifth item is way too long for this and needs three columns
6. The sixth
7. The seventh
- X 8. The eighth item is way too long for this and needs two columns (196.17749pt)
9. The ninth
- Z 10. The tenth (89.28171pt)

3 The command \setenumext

```
\setenumext[\langle key = val \rangle]
\setenumext[\langle enumext, level \rangle][\langle key = val \rangle]
\setenumext[\langle enumext* \rangle][\langle key = val \rangle]
\setenumext[\langle keyans \rangle][\langle key = val \rangle]
\setenumext[\langle keyans* \rangle][\langle key = val \rangle]
\setenumext[\langle print, level \rangle][\langle key = val \rangle]
\setenumext[\langle print* \rangle][\langle key = val \rangle]
```

The command `\setenumext` sets the `\langle keys \rangle` on a global basis for environments `enumext`, `enumext*`, `keyans`, `keyans*` and the `\printkeyans` command. It can be used both in the preamble and in the body of the document as many times as desired.

The `\langle keys \rangle` set in the optional arguments of environments and commands have the *highest precedence*, overriding both options passed by `\setenumext`. If the optional argument is not passed, the first level of the environment `enumext` will be taken by default.

- The key `save-ans` that activate the “storage system” must NOT be passed through this command and must be passed directly in the optional argument of the “first level” of the environment in which they are executed.

4 The command `\setenumextmeta`

```
\setenumextmeta <key name> {<key-one = val, key-two = val, ...>}
\setenumextmeta* <key name> {<key-one = val, key-two = val, ...>}
\setenumextmeta [<enumext*>] <key name> {<key-one = val, key-two = val, ...>}
\setenumextmeta [<enumext, level>] <key name> {<key-one = val, key-two = val, ...>}
```

The command `\setenumextmeta` adds a new “meta-key” for the environments `enumext` and `enumext*`, the `{<key name>}` must be different from those defined by the package. If the optional argument is not passed, the new “meta-key” will be created for the first level of the environment `enumext`.

The starred version `*` will create the new “meta-key” for the environment `enumext*` and for all levels of the environment `enumext`.

5 The keyval system

The `<key = val>` system used by the `enumext` package is implemented using `l3keys` so it must be taken into consideration that those keys marked as “value forbidden”, that is `<key>` is different from `<key=>`.

All `<keys>` described in this section are available for the `enumext`, `enumext*`, `keyans` and `keyans*` environments with the exception of the keys `series`, `resume`, `resume*` which are only available for the “first level” of the environments `enumext` and `enumext*`; and the keys `mini-right`, `mini-right*` which are only available for the `enumext*` and `keyans*` environments.

All `<keys>` related to vertical or horizontal spacing accept a “skip” or “dim” expression if passed between braces, i.e. you do not need to use `\dimeval` or `\dimexpr` to perform calculations.

It should be kept in mind that using any `<key>` that sets a *rubber lengths* or *rigid lengths* for vertical or horizontal space on a level will influence the vertical and horizontal space for *inners levels* and `keyans`, `keyans*` and `keyanspic` environments.

5.1 Keys for label and ref

```
label = {<\alph* | \Alph* | \arabic* | \roman* | \Roman*>} default: by levels
```

Sets the `<label>` that will be printed at the *current level*. The default value for the first level of the environments `enumext` and `enumext*` are `\arabic*`, for second level are `(\alph*)`, for third level are `\roman*`, and for fourth level are `\Alph*`. For `keyans` and `keyans*` environments the default value is `\lph*`.

- This key is intended to give the basic structure with which the `<label>` will be displayed, and the form in which it is used by standard “label and ref” and the “internal reference” system with the `save-ref` key. You cannot use commands with `<label>` as an argument, for example `\emph{\alph*}` will return an error. For full customization of how `<label>` is displayed use the `font` or `wrap-label` keys.

```
ref = {<code {<\alph* | \Alph* | \arabic* | \roman* | \Roman*> more code}>} default: empty
```

Modifies the way *cross references* are displayed. The `label` key sets the default form of the *cross references*, by using this key you can define a different format, for example: `ref=\emph{\alph*}` is valid.

Internally it renews the command associated with each counter when it is executed, i.e., in the environment `enumext` the command `\theenumXi` is modified when the key is executed at the first level, `\theenumXii` when it is executed at the second level and `\theenumXiii` together with `\theenumXiv` when it is executed at the third and fourth levels.

- This must be kept in mind, since the values set by the `label` and `ref` keys are not cumulative by levels, so if you have used the `ref` key in the first level and then want to associate the counter with `label` or `ref` in the second level you must use the direct commands, i.e. `\arabic{enumXi}` to indicate the count of the first level instead of using `\theenumXi`.

```
labelsep = {<rigid length>} default: 0.3333em
```

Sets the *horizontal space* between the box containing the current `<label>` defined by `label` key and the text of an item on the first line. Internally sets the value of `\labelsep` for the current level.

```
labelwidth = {<rigid length>} default: by label
```

Sets the *width* of the box containing the current `<label>` set by `label` key. Internally sets the value of `\labelwidth` for the current level. The default values are calculated by means of the *width* of a box by setting a *value* to the current counter using ‘0’ for `\arabic*`, ‘M’ for `\Alph*`, ‘m’ for `\alph*`, ‘VIII’ for `\Roman*` and ‘viii’ for `\roman*`.

```
widest = {<integer | string>} default: empty
```

Sets the `labelwidth` key pass the `<integer>` or converting the `<string>` of the form `\Alph`, `\alph`, `\Roman` or `\roman` to a *value* for the current counter defined by `label` key, then calculating the *width* by means of a box. For example `widest={XXIII}` or `widest={23}` are equivalent. This key is useful when the default values of the `labelwidth` key are smaller than those actually used.

```
font = {<font commands>} default: empty
```

Sets the *font style* for the current `<label>` defined by `label` key. For example `font={\bfseries\small}`.

```
align = {<left | right | center>} default: left
```

Sets the *aligned* of `<label>` defined by `label` key on the current level in the label box.

`wrap-label` = {*code* {#1} *more code*} default: *empty*
 Wraps the *current* *label* defined by `label` key referenced by {#1}. The {*code*} must be passed between braces. This key does not modify the value set by the `labelwidth` key and is applied only on `\item` and `\item*`. When using it in the `\setenumext` command it is necessary to use the *double hash* ‘{#1}’. For example `wrap-label={\fbox{#1}}` or you can create a command:

```
\NewDocumentCommand \labelbx { s +m }
{%
  \IfBooleanTF{#1}
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedright{#2}}}}%
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{#2}}}}%
}
```

and then pass it through the key `wrap-label={\labelbx{#1}}` or `wrap-label={\labelbx*{#1}}`.

`wrap-label*` = {*code* {#1} *more code*} default: *empty*
 The same as the `wrap-label` key but also applies on `\item[custom]`.

5.2 Keys for spaces

`show-length` = {*true* | *false*} default: *false*
 Displays on the terminal the values for *all list parameters* at the current level. For *vertical spaces* show the values of `\topsep`, `\itemsep`, `\parsep` and `\partopsep`. For *horizontal spaces* show the values of `\labelwidth`, `\labelsep`, `\itemindent`, `\listparindent` and `\leftmargin`.

5.2.1 Vertical spaces

`topsep` = {*rubber length* | *rigid length*} default: *by levels*
 Set the *vertical space* added to both the top and bottom of the list. Internally sets the value of `\topsep` for the current level. The default value for the first level of the environments `enumext` and `enumext*` are 8.0pt plus 2.0pt minus 4.0pt, for second level are 4.0pt plus 2.0pt minus 1.0pt, for third and fourth level are 2.0pt plus 1.0pt minus 1.0pt. For `keyans` and `keyans*` environments the default value is 4.0pt plus 2.0pt minus 1.0pt.

`parsep` = {*rubber length* | *rigid length*} default: *by levels*
 Set the *vertical space* between paragraphs within an item. Internally sets the value of `\parsep` for the current level. The default value for the first level of the environments `enumext` and `enumext*` are 4.0pt plus 2.0pt minus 1.0pt, for second level are 2.0pt plus 1.0pt minus 1.0pt, for third and fourth level are 0pt. For `keyans` and `keyans*` environments the default value is 2.0pt plus 1.0pt minus 1.0pt.

`partopsep` = {*rubber length* | *rigid length*} default: *by levels*
 Set the *vertical space* added, beyond `topsep`, to the “top” and “bottom” of the entire environment if the environment instance is preceded by a “blank line” or `\par` command. Internally sets the value of `\partopsep` for the current level. The default values for first and second level in environment `enumext` are 2.0pt plus 1.0pt minus 1.0pt, for third and fourth level are 1.0pt minus 1.0pt. For the `keyans` environment the default value is 2.0pt plus 1.0pt minus 1.0pt, and for the `keyans*` and `enumext*` environments it is available but *without effect*.

- The value of this parameter also affects the *inner levels* and the environments `keyans`, `keyanspic` and `keyans*`. Caution should be taken with “blank lines” or `\par` command “before” each environment or nested level when formatting the source code of document. T_EX will enter *vertical mode* and apply this value to the “top” and “bottom” the environment or nested level.

`itemsep` = {*rubber length* | *rigid length*} default: *by levels*
 Set the *vertical space* between items, beyond the `parsep`. Internally sets the value of `\itemsep` for the current level. The default value for the first level of the environments `enumext` and `enumext*` are 4.0pt plus 2.0pt minus 1.0pt, for the rest of the levels are 2.0pt plus 1.0pt minus 1.0pt. For `keyans` and `keyans*` environments the default value is 4.0pt plus 2.0pt minus 1.0pt.

`noitemsep` *<value forbidden>* default: *not used*
 This is a “meta-key” that does not receive an argument. Set `itemsep` and `parsep` equal to 0pt the entire level of environment.

`nosep` *<value forbidden>* default: *not used*
 This is a “meta-key” that does not receive an argument. Sets all keys for vertical spacing equal to 0pt the entire level of environment.

`base-fix` *<value forbidden>* default: *not used*
 This is a “meta-key” that does not receive an argument available only for the *first level* of environment `enumext` and environment `enumext*`. Fix the *baseline* when an environment `enumext` is nested in `enumext*` or vice versa and there is no material between the `\item` and the start of the environment for example `\item \begin{enumext*}` within the environment `enumext`. Internally sets the keys `topsep`, `above` and `above*` at 0pt.

- The following *<keys>* should be used with “caution”, they are intended to be used at the “top” and “bottom” of the environment when the `columns` or `mini-env` keys do not provide adequate *vertical spaces*. The values passed can be

rubber or *rigid* lengths, the way they are applied is the way you differ, using the *star* ‘*’ $\langle keys \rangle$ applies `\vspace*` so that \LaTeX does *not discard* this space at page break.

`above = { $\langle rubber length \mid rigid length \rangle$ }` default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the top of the entire level of environment. This key is intended to give a “*fine adjustment*” of the vertical space on the “*above*” the environment without hindering the value of the `topsep` key. The space is added with `\vspace` so is “*discordable*”.

`above* = { $\langle rubber length \mid rigid length \rangle$ }` default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the top of the entire level of environment. This key is intended to give a “*fine adjustment*” of the vertical space on the “*above*” the environment without hindering the value of the `topsep` key. The space is added with `\vspace*` so is “*not discordable*”.

`below = { $\langle rubber length \mid rigid length \rangle$ }` default: *not used*

Set the *extra vertical space* space added, beyond `topsep`, to the bottom of the entire level of environment. This key is intended to give a “*fine adjustment*” of the vertical space on the “*below*” the environment without hindering the value of the `topsep` key. The space is added with `\vspace` so is “*discordable*”.

`below* = { $\langle rubber length \mid rigid length \rangle$ }` default: *not used*

Set the *extra vertical space* space added, beyond `topsep`, to the bottom of the entire level of environment. This key is intended to give a “*fine adjustment*” of the vertical space on the “*below*” the environment without hindering the value of the `topsep` key. The space is added with `\vspace*` so is “*not discordable*”.

5.2.2 Horizontal spaces

`itemindent = { $\langle rigid length \rangle$ }` default: `0pt`

Extra *horizontal indentation*, beyond `labelsep`, of the “*first line*” off each item. This value is applied internally using `\hspace` and does not modify the value of `\itemindent`.

`rightmargin = { $\langle rigid length \rangle$ }` default: `0pt`

Set the *horizontal space* between the right margin of the environment and the right margin of the enclosing environment, the value it takes must be greater than or equal to `0pt`. Internally sets the value of `\rightmargin` for the current level.

`listparindent = { $\langle rigid length \rangle$ }` default: `0pt`

Sets the *horizontal space* indentation, beyond `list-indent`, for second and subsequent paragraphs within a list item. Internally sets the value of `\listparindent` for the current level.

`list-offset = { $\langle rigid length \rangle$ }` default: `0pt`

Sets the *horizontal translation* of the entire environment level from the left edge of the box defined by the `labelwidth` key. Internally sets the values of `\leftmargin` and `\itemindent` for the current level.

`list-indent = { $\langle rigid length \rangle$ }` default: `labelwidth + labelsep`

Sets the *indentation* of the whole environment under the box defined by `labelwidth` and `labelsep` keys. Internally sets the value of `\leftmargin` and `\itemindent` for the current level.

If `list-indent=0pt` is set in the environment `enumext` the $\langle label \rangle$ will be part of the text, separated by the value of the `labelsep` key and the *first word*, in simple terms it will look like a “*common paragraph*”. This setting is equivalent (more or less) to the `wide` key provided by the `enumitem` package.

🟢 For the `enumext*` and `keyans*` environments the keys `list-indent` and `list-offset` have the same effect.

5.3 Keys for add code

🟢 The following $\langle keys \rangle$ should be used with “*caution*”, they are intended to inject $\{ \langle code \rangle \}$ into different parts of the defined environments. We must keep in mind that the defined environments are based on the `list` base environment provided by \LaTeX which is defined (simplified) as plain form `\list{ $\langle arg one \rangle$ }{ $\langle arg two \rangle$ }`. Using the `before*` key does not allow access to the `list` parameters defined by $[\langle key = val \rangle]$.

`before = { $\langle code \rangle$ }` default: *not used*

Execute $\{ \langle code \rangle \}$ “*before*” the environment starts. The $\{ \langle code \rangle \}$ must be passed between braces, is executed “*after*” performing all calculations related to the *list parameters* in the environment and the parameters sets by $[\langle key = val \rangle]$ that is, in the second argument of the list after setting all the parameters `\begin{list}{ $\langle arg one \rangle$ }{ $\langle arg two \rangle$ }{ $\langle code \rangle$ }`.

`before* = { $\langle code \rangle$ }` default: *not used*

Execute $\{ \langle code \rangle \}$ “*before*” the environment starts. The $\{ \langle code \rangle \}$ must be passed between braces, is executed “*before*” performing all calculations related to the *list parameters* and $[\langle key = val \rangle]$ sets in the environment that is, before the arguments defining the environment are executed: `\{ \langle code \rangle \} \begin{list}{ $\langle arg one \rangle$ }{ $\langle arg two \rangle$ }`.

`first = { $\langle code \rangle$ }` default: *not used*

Executes $\{ \langle code \rangle \}$ when “*starting*” the environment. The $\{ \langle code \rangle \}$ must be passed between braces, is executed right “*after*” all *list parameters* are done, after the second argument of list, just before the first occurrence of `\item: \begin{list}{ $\langle arg one \rangle$ }{ $\langle arg two \rangle$ }{ $\langle code \rangle$ }\item`.

🟢 Keep in mind that the code set in this key will affect the entire “*body*” of the environment and therefore the inner levels of the list and the `keyans` environment. It is recommended to set this key per level.

`after = { $\langle code \rangle$ }` default: *not used*

Execute $\{ \langle code \rangle \}$ “*after*” finishing the environment. The $\{ \langle code \rangle \}$ must be passed between braces.

5.4 Keys for start, series and resume

`start = {⟨integer | integer expression⟩}` default: 1

Sets the *start value* of the numbering on the current level. The {⟨integer expression⟩} must be passed between braces, internally is evaluated and pass to the counter defined by `label` key on the current level, i.e. it is equivalent to enter `start={\dimeval{100*\value{chapter}}` or `start={100*\value{chapter}}`.

`start* = {⟨integer | string⟩}` default: not used

Sets the *start value* of the numbering on the current level. Internally ⟨string⟩ is converted and passed as value to the counter defined by `label` key on the current level, i.e. it is equivalent to enter `start=5`, `start=E` or `start=v`.

- The following ⟨keys⟩ are “only” available for the `enumext*` environment and the “first level” of the `enumext` environment and are ignored if set when nested within each other.

`series = {⟨series name⟩}` default: not used

Stores the *keys* of the optional argument of the “first level” of the environment in which it is executed in {⟨series name⟩} which is used as an argument in the key `resume`. The ⟨keys⟩ stored in {⟨series name⟩} are not cumulative and are overwritten if the same {⟨series name⟩} is used again.

`resume = {⟨series name⟩}` default: not used

Sets the *start value* and *options* for the “first level” continuing the numbering of the environment in which the `series={⟨series name⟩}` key was executed. If passed *without value* this will only set *start value* continue the numbering from the last environment in which `series={⟨series name⟩}` or `resume={⟨series name⟩}` is not present and if the `save-ans` key is active it will continue the numbering from the last environment in which it was executed. The *start value* can be overwritten using `start` or `start*` keys.

`resume* ⟨value forbidden⟩` default: not used

Sets the *start value* and *options* for the “first level” continuing the numbering of the environment in which the `series={⟨series name⟩}` or `resume={⟨series name⟩}` keys are NOT present, if the `save-ans` key is active it will continue the numbering from the last environment in which it was executed. The *start value* can be overwritten using `start` or `start*` keys.

- For security reasons the `series` key will never save in {⟨series name⟩} the keys `series`, `resume`, `resume*`, `save-ans`, `save-key`, `start*` and `start`. When using the key `resume={⟨series name⟩}` it will have hierarchy in the ⟨keys⟩ that are saved in {⟨series name⟩}, in order to establish the value of a ⟨key⟩ already saved in {⟨series name⟩} it must be placed to the “right” of `resume={⟨series name⟩}`, the same thing happens with the `resume*` key, the exception is the `save-ans` key that must be placed on the “left” if you want to start the numbering with its value. The `resume` key passed “without value” must be exactly “without value”, i.e. `resume=` cannot be used and if executed before `resume*` it will affect the *start value*.

5.5 Keys for multicol

`columns = {⟨integer⟩}` default: 1

Set the *number of columns* to be used by the `multicol` environment within the environment. The value must be a positive integer less than or equal to 10.

`columns-sep = {⟨rigid length⟩}` default: by level

Set the *space between columns* used by the `multicol` environment within the environment. Internally sets the value of `\columnsep`, by default its value is equal to the sum of the values set in the keys `labelwidth` and `labelsep` of the current level.

- The `\footnote{⟨text⟩}` command in the nested levels of `multicol` will not work as expected, prefer the use of `\footnotemark[⟨number⟩]` inside the environment and `\footnotetext[⟨number⟩]{⟨text⟩}` outside the environment or via the after key.

5.6 Keys for minipage

`mini-env = {⟨rigid length⟩}` default: not used

Sets the *width* of the `minipage` environment on the “right side”. This value added to the value set by the `mini-sep` key to determines the *width* of the `minipage` environment on the “left side”, taking `\linewidth` as the maximum reference value.

`mini-sep = {⟨rigid length⟩}` default: 0.3333em

Sets the *space between* the `minipage` environment on the “left side” and the `minipage` environment on the “right side”. This separation is applied together with `\hfill`.

5.6.1 The command \miniright

```
\miniright \begin{enumext}[mini-env=⟨rigid length⟩] ⟨item's before⟩ \item \miniright ⟨content⟩ \end{enumext}
\begin{enumext}[mini-env=⟨rigid length⟩] ⟨item's before⟩ \item \miniright*⟨content⟩ \end{enumext}
```

The `\miniright` command close the `minipage` environment on the “left side” and opens the `minipage` environment on the “right side” by starting it with the `\centering` command. It must be placed “after” the last `\item` of the current environment and “before” starting the material to be placed on the “right side”.

The *starred argument* ‘*’ inhibits the use of `\centering` command i.e. the usual \TeX justification is maintained in the `minipage` on the “right side”.

- The `\footnote{⟨text⟩}` command in `minipage` environment will work as usual. If you prefer the footnotes to be numbered (not lowercase) and outside the environment, use `\footnotemark[⟨number⟩]` inside the environment and `\footnotetext[⟨number⟩]{⟨text⟩}` outside the environment or via the `after` key (see §1.3.6 for full support).

5.6.2 The key `mini-right`

In the horizontal list environments `enumext*` and `keyans*` it is not possible to use the `\miniright` command and the `mini-right` key must be used instead.

`mini-right = {⟨content⟩}` default: *not used*

Set the `content` for the drawing or tabular to be placed in the `minipage` environment on the “right side” by starting it with `\centering`. The `{⟨content⟩}` must be passed between braces.

`mini-right* = {⟨content⟩}` default: *not used*

Same as above, but *without* starting with `\centering`.

6 The storage system

The entire mechanism for “storing content” it is activated according to `save-ans` key on the “first level” of `enumext` or `enumext*` environments and it is ignored if they are established when they are nested inside each other. Only when this `⟨key⟩` is “active” the `\anskey` command and the environments `anskey*`, `keyans`, `keyans*` and `keyanspic` are available.

<pre>\begin{enumext}[save-ans={⟨store name⟩}] \item Text \anskey{answer} \item Text \begin{keyans} ... \end{keyans} \end{enumext}</pre>	<pre>\begin{enumext}[save-ans={⟨store name⟩}] \item Text \anskey{answer} \item Text \begin{keyanspic} ... \end{keyanspic} \end{enumext}</pre>
-----------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------

By executing the key `save-ans={⟨store name⟩}` the entire structure of the environment (excluding the first level) including the optional arguments passed to the inner levels or the environment nested in it, along with the content passed to `\anskey`, the current `⟨labels⟩` for `\item*` and `\anspic*` in the environments `keyans`, `keyans*` and `keyanspic` will be stored in a `⟨sequence⟩` and at the same time will be stored (without the environment structure or optional arguments) in a `⟨prop list⟩`.

The optional arguments of the inner levels or the nested environment are filtered by excluding all `⟨keys⟩` related to the “stored system” along with the keys `series`, `resume` and `resume*` when storing in `⟨sequence⟩`.

6.1 Keys for storage system

- The only `⟨keys⟩` available for all levels of the `enumext` environment and the `enumext*` environment are `no-store` and `save-key`, the rest of the `⟨keys⟩` described in this section must be passed directly in the optional argument of the “first level” of the environment in which the key `save-ans` is executed. The key `save-ans` should NOT be passed with the command `\setenumext`.

`save-ans = {⟨store name⟩}` default: *not set*

Sets the `name` of the `⟨sequence⟩` and `⟨prop list⟩` in which the contents will be “stored” by `\anskey` and `anskey*` in `enumext` and `enumext*` environments, `\item*` in `keyans` and `keyans*` environments and `\anspic*` in `keyanspic` environment. If the `⟨sequence⟩` or `⟨prop list⟩` does not exist, it will be created globally and will not be overwritten if the key is used again.

`save-key = {⟨key list⟩}` default: *not set*

This key *overrides* the default “stored keys” of the optional arguments of the inner levels or nested environment that will be passed to the `⟨sequence⟩`. The `⟨key list⟩` passed to this key ignores any `⟨keys⟩` in the “stored system” and must be passed between braces. For example, if we execute at a second level:

```
\begin{enumext}[save-ans={⟨store name⟩}]
  \item Text \anskey{answer}
  \item Text
    \begin{enumext}[nosep, columns=2, save-key={columns=3}]
      ...
    \end{enumext}
\end{enumext}
```

The `⟨keys⟩` that will be stored by default in the `⟨sequence⟩` would be `nosep`, `columns=2`, but using the key `save-key={columns=3}` will overwrite this and store it in the `⟨sequence⟩` only the key `columns=3` ignoring all the others.

`save-sep = {⟨text symbol⟩}` default: `{,}`

Sets the `text symbol` that will separate the current `⟨label⟩` to the *optional argument* passed to the `\item*` and `\anspic*` in the `keyans`, `keyans*` and `keyanspic` environments and storing them in the `⟨store name⟩` defined by the `save-ans` key. The `{⟨text symbol⟩}` must always be passed between braces, whitespace ‘`␣`’ is preserved within the braces and only affects the “stored content” and not what is displayed when using the `show-ans` or `show-pos` keys.

6.1.1 Keys for label and ref

`save-ref` = { $\langle true | false \rangle$ } default: *false*
 Activates the “*internal label and ref*” mechanism for referencing “*stored content*” in $\langle store\ name \rangle$ set by `save-ans` key. To reference the location of the “*stored content*” within the environment you must use $\backslash ref\{\langle store\ name : position \rangle\}$, where $\langle position \rangle$ corresponds to the position occupied by the “*stored content*” in the $\langle store\ name \rangle$ returned by the `show-pos` key. For example $\backslash ref\{test:4\}$ will return 3. (b) which corresponds to the location of the “*stored content*” at position 4 within the environment in which the key `save-ans=test` was set.

`mark-ref` = { $\langle symbol \rangle$ } default: *\textasteriskcentered*
 Sets the *symbol* that will be displayed by the `\printkeyans` command only if the `hyperref` package is detected and the `save-ref` key are active. This “*symbol*” is used as a “*link*” between the environment in which the `save-ans` key was used and the place where the command is executed.

6.1.2 Keys for wrap and display

`wrap-ans` = { $\langle code\ \{\#1\}\ more\ code \rangle$ } default: *\fbox+\parbox\{#1\}*
 Wraps the *argument* passed to the `\anskey` and the *body* in `anskey*` environment referenced by $\{\#1\}$ when using the `show-ans` or `show-pos` keys. The $\{\langle code \rangle\}$ must be passed between braces and only affects the *argument* or *body* and NOT the “*stored content*” in the *sequence* and *prop list* $\{\langle store\ name \rangle\}$ set by `save-ans` key. If this key is passed using `\setenumext` it is necessary to use double ‘ $\{\#1\}$ ’.

`wrap-opt` = { $\langle code\ \{\#1\}\ more\ code \rangle$ } default: *[\{#1\}]*
 Wraps the *optional argument* passed to the `\item*` and `\anspic*` referenced by $\{\#1\}$ in the `keyans`, `keyans*` and `keyanspic` environments when using the `show-ans` or `show-pos` keys. The $\{\langle code \rangle\}$ must be passed between braces and only affects the current *optional argument* and NOT the “*stored content*” in the *sequence* and *prop list* $\{\langle store\ name \rangle\}$ set by `save-ans` key. If this key is passed using `\setenumext` it is necessary to use double ‘ $\{\#1\}$ ’.

`show-ans` = { $\langle true | false \rangle$ } default: *false*
 Displays the *argument* passed to the `\anskey`, the *body* for `anskey*` environment, the $\langle label \rangle$ for `\item*` and `\anspic*` at the place where it is executed. If the optional argument is present in `\item*` or `\anspic*` it will be shown using `wrap-opt` key.

`mark-ans` = { $\langle symbol \rangle$ } default: *\textasteriskcentered*
 Sets the *symbol* to be displayed in the left margin for `\anskey`, `anskey*`, `\item*` and `\anspic*` in the place where they are executed when using the key `show-ans`.

`mark-pos` = { $\langle left | right \rangle$ } default: *left*
 Sets the *aligned* of the symbol defined by `mark-ans` key. The “*symbol*” is aligned in a box with the same dimensions of the label box defined by `labelwidth` key on the current level and separated by the value of the `labelsep` key.

6.1.3 Keys for debug and checking

`show-pos` = { $\langle true | false \rangle$ } default: *false*
 Displays the *position* occupied by the “*stored content*” by `\anskey`, `anskey*`, `\item*` and `\anspic*` in the *prop list* $\{\langle store\ name \rangle\}$ set by `save-ans` key. This position is used by the `\getkeyans` command and by the `\ref` command if the `save-ref` key is active.

`check-ans` = { $\langle true | false \rangle$ } default: *false*
 Enables the *checking answer* mechanism displaying an appropriate message on the terminal. This key works under the logic that each `\item` or `\item*` that does not open an inner level or nested environment contains “*only one answer*” or “*only one execution*” of the `\anskey` or `anskey*`. It is intended to be used in conjunction with the `no-store` key.

`no-store` $\langle value\ forbidden \rangle$ default: *not used*
 This is a *meta-key* that does not receive an argument and disables the structure stored in the *sequence* $\{\langle store\ name \rangle\}$ set by `save-ans` key at the entire level or a nested environment in which it runs. This key is intended for use in internal levels or nested `enumext` or `enumext*` environments in which you want to use `enumext` or `enumext*` but “*without*” using the `\anskey`, “*without*” use `anskey*`, “*without*” interfering with the `check-ans` key and “*without*” storing an unwanted structure in the *sequence* $\{\langle store\ name \rangle\}$.

6.2 The command \anskey

`\anskey` $\backslash anskey[\langle keys \rangle][\langle content \rangle]$

The command `\anskey` takes a mandatory non empty argument $\{\langle content \rangle\}$ and “*stores*” it in the *sequence* and *prop list* $\{\langle store\ name \rangle\}$ set by `save-ans` key. By design the command cannot be nested or passed *verbatim material* in the argument and it is assumed that each *numbered* `\item` or `\item*` within the environment in which it is active it has a “*single execution*” of `\anskey` unless `\item` or `\item*` open a nested level or use the `no-store` key.

If `save-ref` key are active and the `hyperref`[8] package is detected, `\hyperlink` and `\hypertarget` will be used, otherwise the usual “*label and ref*” system provided by L^AT_EX will be used.

The `\anskey` command is available for all levels of the `enumext` environment and the `enumext*` environment, but is disabled for the `keyans`, `keyans*` and `keyanspic` environments.

6.2.1 Keys for \anskey

By default the $\langle content \rangle$ passed to `\anskey` when “storing” in the *sequence* $\langle store name \rangle$ has the form `\item $\langle content \rangle$` , the following *keys* allow modifying the way in which it is “stored” in the *sequence*.

`break-col` $\langle value forbidden \rangle$ default: not used

Stores $\langle content \rangle$ in the *sequence* $\langle store name \rangle$ of the form `\columnbreak \item $\langle content \rangle$` .

`item-join` = $\langle columns \rangle$ default: not set

Set the *number of columns* to be used for `\item $\langle columns \rangle$` and stores $\langle content \rangle$ in the *sequence* $\langle store name \rangle$ of the form `\item $\langle columns \rangle$ $\langle content \rangle$` .

`item-star` $\langle value forbidden \rangle$ default: not used

Stores $\langle content \rangle$ in the *sequence* $\langle store name \rangle$ of the form `\item* $\langle content \rangle$` .

`item-sym*` = $\langle symbol \rangle$ default: $\$star\$$

Sets the *symbol* for `\item*` when using the key `item-star` and stores $\langle content \rangle$ in the *sequence* $\langle store name \rangle$ of the form `\item* $\langle symbol \rangle$ $\langle content \rangle$` . The *symbol* can be in text or math mode, for example `item-sym* = $\$ast\$$` stores `\item* $\$ast\$$ $\langle content \rangle$` .

`item-pos*` = $\langle rigid length \rangle$ default: not set

Sets the *offset* for `\item*` when using the keys `item-star` and `item-sym*` and stores $\langle content \rangle$ in the *sequence* $\langle store name \rangle$ of the form `\item* $\langle symbol \rangle$ [$\langle offset \rangle$] $\langle content \rangle$` .

Example

```
\begin{enumext}[save-ans=test,show-ans=true]
  \item* Text containing our instructions or questions. \anskey{first answer}
  \item Text containing our instructions or questions.
    \begin{enumext}
      \item Question.\anskey{second answer}
    \end{enumext}
  \item Text containing our instructions or questions. \anskey{third answer}
  \item Text containing our instructions or questions. \anskey{fourth answer}
\end{enumext}
```

* 1. Text containing our instructions or questions.

*

2. Text containing our instructions or questions.

(a) Question.

*

3. Text containing our instructions or questions.

*

4. Text containing our instructions or questions.

*

6.3 The environment anskey*

`anskey*` `\begin{anskey*} [$\langle key = val \rangle$] $\langle body content \rangle$ \end{anskey*}`

The environment `anskey*` takes a mandatory $\langle body content \rangle$ and “stores” it in the *sequence* and *prop list* $\langle store name \rangle$ set by `save-ans` key. If `save-ref` key are active and the `hyperref`[8] package is detected, `\hyperLink` and `\hypertarget` will be used, otherwise the usual “*label and ref*” system provided by \LaTeX will be used.

By design the environment cannot be nested but full supports “*verbatim material*” in the body and it is assumed that each numbered `\item` or `\item*` within the environment in which it is active it has a “*single execution*” unless `\item` or `\item*` open a nested level or use the `no-store` key.

The `anskey*` environment is implemented using the `scontents` package, for the correct operation `\begin{anskey*}` and `\end{anskey*}` must be in different lines, all *keys* must be passed separated by commas and “without separation” of the start of the environment. Comments “%” or “any character” after `\begin{anskey*}` or `[$\langle key = val \rangle$]` on the same line are NOT supported, the package `scontents` will return an “error” message if this happens. In a similar way comments “%” or “any character” after `\end{anskey*}` on the same line the package `scontents` will return a “warning” message.

6.3.1 Keys for anskey*

The `anskey*` environment uses the same *keys* as the `\anskey` command next to the keys inherited from package `scontents`. The environment is available for all levels of the `enumext` environment and the `enumext*` environment, but it is disabled for the `keyans`, `keyans*` and `keyanspic` environments.

`write-env` = $\langle file.ext \rangle$ default: not used

Sets the name of the $\langle external file \rangle$ in which the $\langle contents \rangle$ of the environment will be written. The $\langle file.ext \rangle$ will be created in the working directory, relative or absolute paths are not supported. If $\langle file.ext \rangle$ does not exist, it will be created or overwritten if the `overwrite` key is used.

`overwrite` = $\langle true | false \rangle$ default: false

Sets whether the $\langle file.ext \rangle$ generated by `write-env` from the `anskey*` environment will be rewritten.

force-eol = { $\langle true \mid false \rangle$ }

default: *false*

Sets if the *end of line* for the $\langle stored\ content \rangle$ is hidden or not. This key is necessary only if the last line is the closing of some environment defined by the `fancyvrb` package as `\end{Verbatim}` or another environment that does not support a comments “%” after closing `\end{Verbatim}`%.
 For security reasons the keys `store-env`, `print-env` and `write-out` they have been left disabled. It is recommended that you review the `scontents`[4] documentation to understand how the keys described here work.

Example

```
\begin{enumext}[save-ans=test,show-pos=true,start=5]
  \item* Text containing our instructions or questions.
  \begin{anskey*}[item-star]
    \first answer
  \end{anskey*}
  \item Text containing our instructions or questions.
  \begin{enumext}
    \item Question.
    \begin{anskey*}
      \second answer
    \end{anskey*}
  \end{enumext}
  \item Text containing our instructions or questions.
  \begin{anskey*}
    \third answer
  \end{anskey*}
  \item Text containing our instructions or questions.
  \begin{anskey*}
    \fourth answer
  \end{anskey*}
\end{enumext}
```

★ 5. Text containing our instructions or questions.

[5] First answer with verbatim

6. Text containing our instructions or questions.

(a) Question.

[6] second answer

7. Text containing our instructions or questions.

[7] third answer

8. Text containing our instructions or questions.

[8] fourth answer

6.4 The environments `keyans` and `keyans*`

<code>keyans</code> <code>keyans*</code>	<pre>\begin{keyans}[\langle key = val \rangle] \item \item[\langle custom \rangle] \item* \item*[\langle content \rangle] \end{keyans} \begin{keyans*}[\langle key = val \rangle] \item \item[\langle custom \rangle] \item* \item*[\langle content \rangle] \end{keyans*}</pre>
---------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

The `keyans` and `keyans*` environments are “*enumerated list*” environments designed for “*multiple choice*” questions activated by the `save-ans` key. This environments can NOT be nested and must always be at the “*first level*” of the `enumext` environment, the commands `\item` and `\item[\langle custom \rangle]` work in the usual and the command `\item[\langle columns \rangle]` is available for the `keyans*` environment.

<pre>\begin{enumext}[save-ans=test] \item \item content \begin{keyans}[\langle key = val \rangle] \item \item content \item [\langle custom \rangle] \item content \item* \item content \item*[\langle content \rangle] \item content \end{keyans} \end{enumext}</pre>	<pre>\begin{enumext}[save-ans=test] \item \item content \begin{keyans*}[\langle key = val \rangle] \item \item content \item [\langle custom \rangle] \item content \item* \item content \item*[\langle content \rangle] \item content \end{keyans*} \end{enumext}</pre>
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

The $\langle keys \rangle$ set in the optional argument of the environment are the same (almost) as those of the `enumext` and `enumext*` environments and have higher precedence than those set by `\setenumext[\langle keyans \rangle]{\langle key = val \rangle}` or `\setenumext[\langle keyans* \rangle]{\langle key = val \rangle}`. If the optional argument is not passed or the $\langle keys \rangle$ are not set by `\setenumext`, the default values will be the same as the second level of the `enumext` environment with the difference in the $\langle label \rangle$ which will be set to `label=\Alph*`.

6.4.1 The `\item*` in `keyans` and `keyans*`

<code>\item*</code> <code>\item*</code>	<pre>\item* \item*[\langle content \rangle]</pre>
--------------------------------------------	---------------------------------------------------

The `\item*` and `\item*[\langle content \rangle]` command “*store*” the current $\langle label \rangle$ set by `label` key next to the $\langle content \rangle$ (if it is present) in *sequence* and *prop list* $\{\langle store\ name \rangle\}$ set by `save-ans` key in the “*first level*” of the `enumext` or `enumext*` environments.

The *starred argument* ‘*’ cannot be separated by spaces ‘␣’ from the command, i.e. `\item*` and the optional argument does “*not support*” verbatim content. By design it is assumed that the `\item*` will only appear “*once*” within the environment.

- The behavior of `\item*` in `keyans` and `keyans*` environments is NOT the same as in the `enumext` or `enumext*` environments.

Example

```
\begin{enumext}[save-ans=test,columns=2,show-ans=true]
  \item Text containing a question.
  \begin{keyans*}[nosep,columns=2]
    \item Choice
    \item* Correct choice
    \item Choice
    \item Choice
    \item Choice
  \end{keyans*}
  \item Text containing a question and image.
  \begin{keyans}[nosep,mini-env={0.4\linewidth}]
    \item Choice
    \item Choice
    \item Choice
    \item Choice
    \item*[\textit{note}] Correct choice
    \miniright
    \includegraphics[scale=0.25]{example-image-a}
    Some text
  \end{keyans}
\end{enumext}
```

1. Text containing a question.

A) Choice

C) Choice

E) Choice

* B) Correct choice

D) Choice
2. Text containing a question and image.


A) Choice

B) Choice

C) Choice

D) Choice

* E) [note] Correct choice



Some text

6.5 The environment keyanspic

keyanspic

```
\begin{keyanspic}*[\textit{n}° above, \textit{n}° below]\anspic{\textit{drawing}}\anspic*[\textit{content}]{\textit{drawing}}
```

The `keyanspic` is a “fake enumerated list” environment that which uses the `\anspic` command instead of `\item`. It is activated by the `save-ans` key and has the same settings as the `keyans` environment. It is intended for placing “drawings” or “tabular” with an *in-line* or *above* and *below* layout. A representation of the output can be seen in the figure 6.




Figure 6: Representation of the `keyanspic` environment with optional argument `[3,2]` in `enumext`.

The *starred argument* ‘*’ places `\labels` “above” the drawings or tabular, the optional argument determines the number drawings or tabular “above” and “below” within the environment. The vertical separation between “above” and “below” is controlled by the values set by `parsep` key passed to `keyans` environment. If the optional argument or the second part of it is omitted the drawings or tabular will be put on a *single line*.

6.5.1 The command \anspic

\anspic

```
\anspic{\textit{drawing or tabular}}
\anspic*[\textit{content}]{\textit{drawing or tabular}}
```

The `\anspic` command take three arguments, the *starred argument* ‘*’ store the current `\label` next to the `\content` (if it is present) in *sequence* and *prop list* `{\textit{store name}}` set by `save-ans` key.

The *starred argument* ‘*’ cannot be separated by spaces ‘␣’ from the command, i.e. `\anspic*` and the optional argument does “*not support*” verbatim content. By design it is assumed that the *starred argument* ‘*’ will only appear “*once*” within the environment.


Example

```
\begin{enumext}[save-ans=test,show-ans,nosep]
  \item Question with images.
  \begin{keyanspic}[3,2]
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-b}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic*[note]{\includegraphics[scale=0.15]{example-image-a}}
  \end{keyanspic}
\end{enumext}
```

1. Question with images.



A)



B)



C)



D)



* E)[note]

6.6 Printing stored content

6.6.1 The command `\getkeyans`

```
\getkeyans \getkeyans{<store name> : <position>}
```

The command `\getkeyans` prints the “stored content” in *prop list* `{<store name>}` defined by `save-ans` key in the `<position>` returned by the `show-pos` key. The “stored content” can only be accessed *after* it is stored, if `{<store name>}` does not exist the command will return an error.

The form taken by the argument `{<store name> : <position>}` is the same as that used to generate the “internal label and ref” system when `save-ref` key are active, so to refer to a “stored content”. For example `\getkeyans{test:4}` will return the “stored content” at position 4 of the environment in which the key `save-ans=test` was set.

6.6.2 The command `\foreachkeyans`

```
\foreachkeyans \foreachkeyans[<key = val>]{<store name>}
```

The command `\foreachkeyans` goes through and executes the command `\getkeyans` on the contents in *prop list* `{<store name>}`. If you pass without options run `\getkeyans` on all contents in *prop list* `{<store name>}`.

Options for command

- `sep = {<code>}` default: *empty*
Establishes the separation between *each* content stored in *prop list* `{<store name>}`. For example, you can use `sep={\\[10pt]}` for vertical separation of stored contents.
- `step = {<integer>}` default: *1*
Sets the increment (`<step>`) applied to the value set by key `start` for each element stored in *prop list* `{<store name>}`. The value must be a *positive integer*.
- `start = {<integer>}` default: *1*
Sets the *position* of the *prop list* `{<store name>}` from which execution will start. The value must be a *positive integer*.
- `stop = {<integer>}` default: *0*
Sets the *position* of the *prop list* `{<store name>}` from which execution it will finish executing. The value must be a *positive integer*.
- `before = {<code>}` default: *empty*
Sets the `{<code>}` that will be executed *before* each content stored in *prop list* `{<store name>}`. The `{<code>}` must be passed between braces.
- `after = {<code>}` default: *empty*
Sets the `{<code>}` that will be executed *after* each content stored in *prop list* `{<store name>}`. The `{<code>}` must be passed between braces.
- `wrapper = {<code> {#1} more code}` default: *empty*
Wraps the content stored in *prop list* `{<store name>}` referenced by `{#1}`. The `{<code>}` must be passed between braces. For example `\foreachkeyans[wrapper={\makebox[1em][l]{#1}}]{<store name>}`.

6.6.3 The command \printkeyans

`\printkeyans` `\printkeyans*[\langle keys \rangle]{\langle store name \rangle}`

The command `\printkeyans` prints “all stored content” in sequence $\{\langle store name \rangle\}$ defined by `save-ans` key placing this inside the `enumext` environment or the `enumext*` environment if the *starred argument* ‘`*`’ is used. The “stored content” can only be accessed *after* it is stored in the *sequence*, if $\{\langle store name \rangle\}$ does not exist the command will return an error.

The optional argument allows managing the $\langle keys \rangle$ in the “first level” of the environment in which the “stored content” of the *sequence* $\{\langle store name \rangle\}$ will be printed, if the *starred argument* ‘`*`’ is used it will be `enumext*` otherwise `enumext`.

The default values for the “first level” are the same as the default values for the `enumext` and `enumext*` environments along with the keys `nosep`, `first=\small`, `font=\small` and `columns=2`. For the inner levels of the environment `enumext` saved in the *sequence* $\{\langle store name \rangle\}$ the default values are the same as those established for the second, third and fourth levels plus the keys `nosep`, `first=\small`, `font=\small`. If the environment `enumext*` is saved within the *sequence* $\{\langle store name \rangle\}$ it will have the same default values plus the keys `nosep`, `first=\small`, `font=\small`.

Since the command encapsulates by default the `enumext` environment or the `enumext*` environment, we must take some considerations:

- If we execute `\printkeyans*{\langle store name \rangle}` and the *sequence* $\{\langle store name \rangle\}$ already contains any `enumext*` environment an error will be returned as we cannot nest.
- If we execute `\printkeyans*{\langle store name \rangle}` and the *sequence* $\{\langle store name \rangle\}$ contains any `enumext` environments, they will start with the $\langle keys \rangle$ set for the first level unless they are set in the optional argument or `save-key` is used to modify it.
- If we execute `\printkeyans{\langle store name \rangle}` and the *sequence* $\{\langle store name \rangle\}$ contains any environment `enumext*`, they will start with the $\langle keys \rangle$ set by default unless they are set in the optional argument or `save-key` is used to modify it.

The default values for the “first level” of `\printkeyans` commands and `\printkeyans*` are established using `\setenumext[\langle print \rangle, \langle i \rangle]{\langle keys \rangle}` and `\setenumext[\langle print* \rangle]{\langle keys \rangle}`. If we need to set the $\langle keys \rangle$ for the environment `enumext` “saved” in the *sequence* $\{\langle store name \rangle\}$ we will use `\setenumext[\langle print \rangle, \langle level \rangle]{\langle keys \rangle}` and if we need to set the $\langle keys \rangle$ for the environment `enumext*` “saved” in the *sequence* $\{\langle store name \rangle\}$ we will use `\setenumext[\langle print \rangle, *]{\langle keys \rangle}`.

Example

```
\begin{enumext}[save-ans=sample,columns=2,show-pos=true,nosep,save-ref=true]
  \item Factor  $3x+3y+3z$ . \anskey{\math{3}(x+y+z)}
  \item True False

  \begin{enumext}[nosep]
    \item \LaTeXe\ is cool? \anskey{Very True!}
  \end{enumext}

  \item Related to Linux

  \begin{enumext}[nosep]
    \item You use linux? \anskey{Yes}
    \item Rate the following package and class
      \begin{enumext}[nosep]
        \item \texttt{xsim} \anskey{very good}
        \item \texttt{exsheets} \anskey{obsolete}
      \end{enumext}
    \end{enumext}
\end{enumext}
```

The answer to `\ref{sample:4}` is `\getkeyans{sample:4}` and the answers to all the worksheets are as follows:

```
\printkeyans{sample}
```

1. Factor $3x + 3y + 3z$.

[1]

$3(x + y + z)$

2. True False

(a) \LaTeXe is cool?

[2]

Very True!

3. Related to Linux

(a) You use linux?

[3]

Yes

(b) Rate the following package and class

i. `xsim`

[4]

very good

ii. `exsheets`

[5]

obsolete

The answer to 3.(b).i is very good and the answers to all the worksheets are as follows:

1. $3(x + y + z)$

2. (a) Very True!

3. (a) Yes

(b) i. very good

ii. obsolete
- *

*

*

*

*

7 Full examples

Here I will leave as an example some adaptations questions taken from TeX-SX. The examples are attached to this documentation and can be extracted from your PDF viewer or from the command line by running:

```
$ pdftdetach -saveall enumext.pdf
```

and then you can use the excellent arara¹ tool to compile them.

Example 1

Adapted from the response given by Enrico Gregorio in Squares for answer choice options and perfect alignment to mathematical answers.

1. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

A 36 km/h.

B 360 km/h.

C 27,8 km/h.

D $3,60 \times 10^8$ km/h.
3. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

A 36 km/h.

B 360 km/h.

C 27,8 km/h.

D $3,60 \times 10^8$ km/h.
2. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?

A $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

B $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.

C $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

D $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$.
4. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?

A $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

B $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.

C $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

D $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$.
1. B

2. A

3. B

4. A

Example 2

Adapted from the response given by Florent Rougon in Multiple choice questions with proposed answers in random order — addition of automatic correction (cross mark).

1. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

A 36 km/h.

✓

B 360 km/h.

C 27,8 km/h.

D $3,60 \times 10^8$ km/h.
2. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?

✓

A $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

B $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.

C $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

D $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$.
3. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

A 36 km/h.

✓

B 360 km/h.

C 27,8 km/h.

D $3,60 \times 10^8$ km/h.
4. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?

✓

A $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

B $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.

C $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

D $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$.
1. B

*

¹The cool TeX automation tool: <https://www.ctan.org/pkg/arara>

2. A

3. B

4. A
- *

*

*

Example 3

A “simple multiple choice” test 📄.

1. First type of questions

A value

B correct

C value

D value
2. Second type of questions

I. $2\alpha + 2\delta = 90^\circ$

II. $\alpha = \delta$

III. $\angle EDF = 45^\circ$

A I only

B II only

C I and II only

D I and III only

E I, II, and III
3. Third type of questions

(1) $2\alpha + 2\delta = 90^\circ$

(2) $\angle EDF = 45^\circ$


A value

B value

C value

D value

E value
4. Question with image and label below:



5. Question with image on left side:

A value

B value

C value

D correct

E value

Test keys

1. B, $x = 5$

2. D

3. C, some note
- * 4. E, A duck

* 5. D, other note

*

Example 4

A “simple worksheet” using ducks :) 📄.

Factor $x^2 - 2x + 1$

Factor $3x + 3y + 3z$

The following questions need to be cuaqtified :)

True False

- (a) $\alpha > \delta$

(b) $\text{E}\text{T}\text{E}\text{X}$ is cool?

Related to Linux

- (a) You use linux?

(b) Usually uses the package manager?

(c) Rate the following package and class

i. `xsim-exam`

ii. `xsim`

iii. `exsheets`

The answer to 1 is $(x - 1)^2$ and the answer to 3.(a) is False.

1. $(x-1)^2$

2. $3(x+y+z)$

3. (a) False

(b) Very True!

4. (a) Yes
- *

*

*

*

*
- (b) Yes, dnf

(c) i. doesn't exist for now :(

ii. very good

iii. obsolete
- *


*

*

*

*

Example 5

Adapted from the response given by Stephen in SAT like question format .

1	Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action.	3	Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action.
2	Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action.	4	Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action.

1. A)

2. C)

3. B)

4. D)

8 The way of non-enumerated lists

It is possible to use (or abuse) the `enumext` environment to mimic *non-enumerated* list environments such as `itemize` and `description`, clearly the `(keys)` to “store answers”, the `keyans` and `keyanspic` environments lose their sense and it is not the focus of the main of this package, but, why not to do it?.

Here I leave as an example other uses of the `enumext` environment that can be helpful for specific purposes. The “trick” to generate these *fake environments* is set `label={}` or `label={\some}` and play with the `list-indent`, `list-offset`, `font` and `wrap-label` keys.

Fake itemize environment

Here we set the `label` key using the default settings in \LaTeX for the four levels `\textbullet`, `\textendash`, `\textasteriskcentered` and `\textperiodcentered` together with the `nosep` key to reduce the vertical spaces in the left side example and set the `label` key in *mathematical mode* for the right side as `\ast`, `\diamond`, `\circ` and `\star` for the four levels together with the `nosep` key

- First level item

– Second level item

* Third level item

· Fourth level item

• First level item
- * First level item

◇ Second level item

○ Third level item

★ Fourth level item

* First level item

Fake description environment

Here we set `label={}` and `list-indent=2.5em`, `font=\bfseries`.

- SomeThing** A short one-line description.

This is an entry *without* a label.

Something A short *one-line* description text.

Something long A much *longer* description text may take more than one line or more than one paragraph.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

If we add `list-indent=0pt` you get *widest style*:

SomeThing A short one-line description.

This is an entry *without* a label.
Something A short *one-line* description text.
Something long A much *longer* description text may take more than one line or more than one paragraph.
Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

- The small space at the beginning of the “*unlabeled entry*” corresponds to `\labelsep` and can be removed using `\hspace{-\labelsep}` at the beginning of the line.

Description indented by label

Here we set `label={}` and we will give a convenient value to `labelsep` and `labelwidth`, for example we can take as reference our *longest label* and pass it as value using:

```
\newlength{\descitemwd}  
\settowidth{\descitemwd}{\textbf{Something long}}  
  
and then use labelsep=4pt,labelwidth=\descitemwd,font=\bfseries.
```

SomeThing A short one-line description.
This is an entry *without* a label.
Something A short one-line description.
Something long A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

The environment can be translated so that the `<labels>` are on the left margin calculating the value passed to the `list-offset` key, in this case it will be equal to the sum of the values set by the `labelwidth` and `labelsep` keys finally resulting as `list-offset={-\descitemwd - 4pt}`.

SomeThing A short one-line description.
This is an entry *without* a label.
Something A short one-line description.
Something long A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

If we add `align=right` it will look like this:

SomeThing A short one-line description.
This is an entry *without* a label.
Something A short one-line description.
Something long A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

- At this point we have used `list-offset={-\descitemwd - 4pt}` instead of `list-offset={-\labelwidth - \labelsep}`, this is because the parameters `\labelwidth` and `\labelsep` take the default values, as if we had not set `label`.

Description with multi-line labels

The `label` key does not accept *multiline material*, this is where the `wrap-label*` key comes into play. Unlike the `enumitem` package, the `align` key only supports three options, so what we will do is create a command in the style `\parleft` of `enumitem` that allows us to place *multiline labels* using `\parbox`.

```
\NewDocumentCommand \labelbx { s +m }  
{%  
  \IfBooleanTF{#1}  
  {%\strut\smash{\parbox[t]{\labelwidth}{\raggedright{#2}}}}%  
  {%\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{#2}}}}%  
}
```

Now we just need to set `wrap-label*={\labelbx{#1}}`.

SomeThing A short one-line description.
This is an entry *without* a label.
Something A short one-line description.
Something A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum
long ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.
Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.
SoMeThInG A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum
LoNg ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

Final notes

The original implementation (if you can call it that) of the ideas that led to the creation of `enumext` were some macros using the `enumerate`[5] package for personal use created in early 2003, the code was quite questionable, but functional for these simple requirements.

With the great answers given by Christian Hupfer in [Create a fake label ref using list](#) and the answer given by David Carlisle in [Change the use of label ref by data save in an array \(list\)](#) I managed to create a more solid code than the original version, now using the `l3prop`[11] and `l3seq`[11] modules together with the `hyperref`[8] and `enumitem`[6] packages, which did the job, but with some limitations.

As time went by I took these limitations as a personal challenge which I called “*reinventing the wheel*”, since there were packages and classes that did more or less what I was looking for, but did not fit my simple requirements. This “*reinventing the wheel*” finally ended up becoming `enumext`.

Why list environments?

The answer is simple, first I love the beauty of its syntax and many of what I had already written used the `enumerate` environment or lists created using the `enumitem` package. In my mind I thought: how complicated could it be to write a package that looked like `enumitem`? It seemed simple enough, of course I didn’t have in mind the mess I was getting into working with `list` environments, `minipage` and adding support for the `multicol` and `hyperref` packages.

Of course, seeing the final result of the experiment “*reinventing the wheel*” I am quite satisfied.

Why not random questions and other utilities

The “*random*” type questions I love and hate them at the same time, although they simplify a lot the work when creating a multiple choice test, but you lose the beauty of typesetting a document with \LaTeX , that is to say the output does not always look as nice as it should, even if they are only alternatives these must follow a certain order when presented either numerical or presentation, that said handling that using *nested lists* is quite complicated so I do not classify to be implemented.

9 References

- [1] HIRSCHHORN, PHILIP. “Using the exam document class”. Available from CTAN, <https://www.ctan.org/pkg/exam>, 2023.
- [2] NIEDERBERGER, CLEMENS. “xsim – eXercise Sheets IMproved”. Available from CTAN, <https://www.ctan.org/pkg/xsim>, 2023.
- [3] MITTELBACH, FRANK. “An environment for multicolumn output”. Available from CTAN, <https://www.ctan.org/pkg/multicol>, 2024.
- [4] GONZÁLEZ, PABLO. “scontents - Stores \LaTeX contents in memory or files”. Available from CTAN, <https://www.ctan.org/pkg/scontents>, 2022.
- [5] The \LaTeX Project. “enumerate – Enumerate with redefinable labels”. Available from CTAN, <https://www.ctan.org/pkg/enumerate>, 2024.
- [6] BEZOS, JAVIER. “Customizing lists with the enumitem package”. Available from CTAN, <https://www.ctan.org/pkg/enumitem>, 2019.
- [7] BERRY, KARL. “ $\LaTeX 2_{\epsilon}$: An Unofficial Reference Manual”. Available from CTAN, <https://ctan.org/pkg/latex2e-help-texinfo>, 2024.
- [8] The \LaTeX Project. “Extensive support for hypertext in \LaTeX ”. Available from CTAN, <https://www.ctan.org/pkg/hyperref>, 2024.
- [9] BURNOL, JEAN-FRANÇOIS. “The footnotehyper package”. Available from CTAN, <https://www.ctan.org/pkg/footnotehyper>, 2021.
- [10] The \LaTeX Project. “The expl3 package”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2024.
- [11] The \LaTeX Project. “The $\LaTeX 3$ Interfaces”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2024.
- [12] The \LaTeX Project. “The $\LaTeX 2_{\epsilon}$ sources”. Available from CTAN, <https://ctan.org/tex-archive/macros/latex/base>, 2024.
- [13] The \LaTeX Project. “ \LaTeX for authors current version”. Available from CTAN, <https://ctan.org/pkg/latex-base>, 2024.
- [14] GUNDLACH, PATRICK. “The lua-visual-debug package”. Available from CTAN, <https://www.ctan.org/pkg/lua-visual-debug>, 2023.

- [15] LEMVIG, MOGENS. “The shortlst package”. Available from CTAN, <https://www.ctan.org/pkg/shortlst>, 1998.
- [16] NIEDERBERGER, CLEMENS. “tasks – Horizontally columned lists”. Available from CTAN, <https://www.ctan.org/pkg/tasks>, 2022.

10 Change history

v1.0 2024-09-25 – First public release.

11 Index of Documentation

The italic numbers denote the pages where the corresponding entry is described.

C		I	
Document class:		\itemsep	8
article	2	K	
book	2	Keys for \anskey provide by enumext:	
exam	2	break-col	13
letter	2	item-join	13
report	2	item-pos*	13
\columnbreak	4, 13	item-star	13
\columnsep	10	item-sym*	13
Commands provide by enumext:		Keys for \foreachkeyans provide by enumext:	
\anskey	11-13	after	16
\anspic	11, 12, 15	before	16
\foreachkeyans	16	sep	16
\getkeyans	12, 16	start	16
\item*	5, 6, 8, 11, 12, 14, 15	step	16
\item	5, 6, 8-10, 12, 14	stop	16
\miniright	10, 11	wrapper	16
\printkeyans	6, 12, 17	Keys for anskey* provide by enumext:	
\setenumextmeta	7	break-col	13
\setenumext	5, 6, 8, 11, 12, 14, 17	force-eol	14
Counters defined by enumext:		item-join	13
enumXiii	4	item-pos*	13
enumXii	4	item-star	13
enumXiv	4	item-sym*	13
enumXi	4	overwrite	13
enumXviii	4	write-env	13
enumXvii	4	Keys for environments provide by enumext:	
enumXvi	4	above*	9
enumXv	4	above	8, 9
E		after	9-11
Environments provide by enumext:		align	7, 21
anskey*	11-13	base-fix	8
enumext*	4-15, 17	before*	9
enumext	4-15, 17, 20	before	9
keyans*	4-9, 11-15	below*	9
keyanspic	4, 7, 8, 11-13, 15, 20	below	9
keyans	4-9, 11-15, 20	check-ans	12
Environments:		columns-sep	4, 10
Verbatim	14	columns	4, 8, 10
center	5	first	9
description	5	font	7
enumerate	1, 3, 5, 22	item-pos*	6
figure	5	item-sym*	6
flushleft	5	itemindent	9
flushright	5	itemsep	8
itemize	5	labelsep	3-7, 9, 10, 12, 21
list	3, 5, 9, 22	labelwidth	3, 4, 6-10, 12, 21
minipage	3-5, 10, 11, 22	labelwith	5
multicols	3, 4, 10	label	7, 8, 10, 14, 20, 21
quotation	5	list-indent	3, 9
quote	5	list-offset	3, 9, 21
tabbing	5	listparindent	9
table	5	mark-ans	12
task	5	mark-pos	12
trivlist	5	mark-ref	12
verbatim	5	mini-env	4, 5, 8, 10
verse	5	mini-right*	7, 11
F		mini-right	7, 11
\footnote	5	mini-sep	4, 10
		no-store	11-13

noitemsep	8	\alph*	7
nosep	8, 20	\arabic*	7
overwrite	13	\roman*	7
parsep	8, 15	\labelsep	3, 7
partopsep	8	\labelwidth	3, 7
ref	4, 7	\linewidth	10
resume*	7, 10, 11	\listparindent	9
resume	7, 10, 11		
rightmargin	9	P	
save-ans	4, 6, 10–17	Packages:	
save-key	10, 11, 17	enumerate	22
save-ref	4, 7, 12, 13, 16	enumext	1–5, 7, 15, 22
save-sep	11	enumitem	3–5, 9, 21, 22
series	7, 10, 11	fancyvrb	14
show-ans	11, 12	footnotehyper	5
show-length	8	hyperref	4, 5, 12, 13, 22
show-pos	11, 12, 16	l3keys	7
start*	10	l3prop	1, 22
start	10	l3seq	1, 22
topsep	8, 9	multicol	1, 2, 4, 22
widest	7	scontents	1, 2, 13, 14
wrap-ans	12	task	5, 6
wrap-label*	8, 21	xsim	2
wrap-label	7, 8	\parsep	8
wrap-opt	12	\partopsep	8
write-env	13		
		R	
L		\raggedcolumns	4
\label	4	\ref	4
Labels provide by enumext:		\rightmargin	9
\Alph*	7, 14		
\Roman*	7	T	
		\topsep	8

12 Implementation

The most recent publicly released version of `enumext` is available at CTAN: <https://www.ctan.org/pkg/enumext>. While general feedback via email is welcomed, specific bugs or feature requests should be reported through the issue tracker: <https://github.com/pablgonz/enumext/issues>.

- The documentation presented here is far from professional, it contains a lot of obvious information that to the eye of a TeXpert are superfluous, but, after so many years developing this project is the only way to remember what does what.

12.1 General conventions

Variables containing `i`, `ii`, `iii` and `iv` are associated by level with the `enumext` environment, variables containing `v` are associated with the `keyans` environment, variables containing `vi` are associated with the `keyanspic` environment, variables containing `vii` are associated with the `enumext*` environment and variables containing `viii` are associated with the `keyans*` environment.

To simplify writing and documentation some variables and functions that are common to the different levels of the environments are described using a capital “X”.

The temporary function `__enumext_tmp:n` is used in different parts of the package code for variable creation or execution of other functions that are grouped into this one.

All variables and functions defined in this package are private and are NOT intended to work or be used by another package or module.

12.2 Initial set up

Start the DocStrip guards.

```
1 <{*package>
```

Identify the internal prefix (L^AT_EX3 DocStrip convention) for l3doc class.

```
2 <@@=enumext>
```

12.3 Declaration of the package

First we will make sure we have a minimum (super updated) version of L^AT_EX to work correctly.

```
3 \NeedsTeXFormat{LaTeX2e}[2024-06-01]
```

Now declare the `enumext` package.

```
4 \ProvidesExplPackage
5   {enumext}
6   {2024-09-25}
7   {1.0}
8   {Enumerate exercise sheets}
```

Finally check if the `multicol` and `scontents` packages are loaded, if not we load it.

```
9 \hook_gput_code:nnn {begindocument} {enumext}
10 {
11   \IfPackageLoadedTF { multicol }
12   {
13     \msg_info:nnn { enumext } { package-load } { multicol }
14   }
15   {
16     \msg_info:nnn { enumext } { package-not-load } { multicol }
17     \RequirePackage{multicol}[2024-05-23]
18   }
19   \IfPackageLoadedTF { scontents }
20   {
21     \msg_info:nnn { enumext } { package-load } { scontents }
22   }
23   {
24     \msg_info:nnn { enumext } { package-not-load } { scontents }
25     \RequirePackage{scontents}
26   }
27 }
```

12.4 Definition of variables

Variables that do not appear in this section are created by means of `\keys_define:nn` or some function described below.


```

\l__enumext_level_int
\l__enumext_level_h_int
\l__enumext_anskey_level_int
\l__enumext_keyans_level_int
\l__enumext_keyans_level_h_int
\l__enumext_keyans_pic_level_int

```

Integer variables will control the nesting levels of the environments and `\anskey` command.

```

28 \int_new:N \l__enumext_level_int
29 \int_new:N \l__enumext_level_h_int
30 \int_new:N \l__enumext_anskey_level_int
31 \int_new:N \l__enumext_keyans_level_int
32 \int_new:N \l__enumext_keyans_level_h_int
33 \int_new:N \l__enumext_keyans_pic_level_int

```

(End of definition for `\l__enumext_level_int` and others.)

```

\l__enumext_starred_bool
\g__enumext_starred_bool
\l__enumext_starred_first_bool
\l__enumext_standar_bool
\g__enumext_standar_bool
\l__enumext_standar_first_bool
\l__enumext_anskey_env_bool
\l__enumext_keyans_env_bool
\g__enumext_start_line_tl
\g__enumext_envir_name_tl
\l__enumext_envir_name_tl

```

Internal variables used by functions `__enumext_is_not_nested:`, `__enumext_is_on_first_level:` and `__enumext_keyans_name_and_start:` (§12.5.1).

```

34 \bool_new:N \l__enumext_starred_bool
35 \bool_new:N \g__enumext_starred_bool
36 \bool_new:N \l__enumext_starred_first_bool
37 \bool_new:N \l__enumext_standar_bool
38 \bool_new:N \g__enumext_standar_bool
39 \bool_new:N \l__enumext_standar_first_bool
40 \bool_new:N \l__enumext_anskey_env_bool
41 \bool_new:N \l__enumext_keyans_env_bool
42 \tl_new:N \g__enumext_start_line_tl
43 \tl_new:N \g__enumext_envir_name_tl
44 \tl_new:N \l__enumext_envir_name_tl

```

(End of definition for `\l__enumext_starred_bool` and others.)

```

\l__enumext_counter_i_tl
\l__enumext_counter_ii_tl
\l__enumext_counter_iii_tl
\l__enumext_counter_iv_tl
\l__enumext_counter_v_tl
\l__enumext_counter_vi_tl
\l__enumext_counter_vii_tl
\l__enumext_counter_viii_tl

```

Variables to store the “*name of the counters*” `enumXi`, `enumXii`, `enumXiii` and `enumXiv` for `enumext` environment, `enumXv` for `keyans` environment and `enumXvi` for the `keyanspic` environment. The counters `enumXvii` and `enumXviii` are used by `enumext*` and `keyans*` environments.

The initial values of these variables are set by the function `__enumext_define_counters:Nn` (§12.10) and then modified by the function `__enumext_label_style:Nnn` used by `label` key (§12.13).

```

45 \cs_set_protected:Npn \__enumext_tmp:n #1
46 {
47   \tl_new:c { l__enumext_counter_#1_tl }
48 }
49 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_counter_i_tl` and others.)

```

\c__enumext_counter_style_tl
\l__enumext_ref_key_arg_tl
\l__enumext_ref_the_count_tl
\l__enumext_the_counter_X_tl
\l__enumext_renew_the_count_X_tl

```

Internal variables used by `ref` key (§12.13).

```

50 \tl_const:Nn \c__enumext_counter_style_tl
51 { { arabic } { roman } { Roman } { alph } { Alph } }
52 \tl_new:N \l__enumext_ref_key_arg_tl
53 \tl_new:N \l__enumext_ref_the_count_tl
54 \cs_set_protected:Npn \__enumext_tmp:n #1
55 {
56   \tl_new:c { l__enumext_renew_the_count_#1_tl }
57   \tl_new:c { l__enumext_the_counter_#1_tl }
58   \tl_set:ce { l__enumext_the_counter_#1_tl } { \exp_not:c { theenumX#1 } }
59 }
60 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\c__enumext_counter_style_tl` and others.)

```

\g__enumext_resume_int
\g__enumext_resume_vii_int
\l__enumext_resume_name_tl
\l__enumext_resume_active_bool
\g__enumext_starred_series_tl
\g__enumext_standar_series_tl

```

Internal variables used by `resume`, `resume*` and `series` keys (§12.24).

```

61 \int_new:N \g__enumext_resume_int
62 \int_new:N \g__enumext_resume_vii_int
63 \tl_new:N \l__enumext_resume_name_tl
64 \bool_new:N \l__enumext_resume_active_bool
65 \tl_new:N \g__enumext_standar_series_tl
66 \tl_new:N \g__enumext_starred_series_tl

```

(End of definition for `\g__enumext_resume_int` and others.)

```

\l__enumext_current_widest_dim
\g__enumext_counter_styles_tl
\g__enumext_widest_label_tl
\l__enumext_label_width_by_box

```

The variable `\l__enumext_current_widest_dim` stores the current label width, the variable `\g__enumext_counter_styles_tl` stores the default *⟨label style⟩* and the variable `\g__enumext_widest_label_tl` the label width. These variables are used by `widest` (§12.14) and `label` (§12.12) keys.

```

67 \dim_new:N \l__enumext_current_widest_dim
68 \tl_new:N \g__enumext_counter_styles_tl
69 \tl_new:N \g__enumext_widest_label_tl
70 \box_new:N \l__enumext_label_width_by_box

```

(End of definition for `\l__enumext_current_widest_dim` and others.)

```
\l__enumext_leftmargin_tmp_X_bool
\l__enumext_leftmargin_tmp_X_dim
\l__enumext_leftmargin_X_dim
\l__enumext_itemindent_X_dim
```

The boolean variable `\l__enumext_leftmargin_tmp_X_bool` and the dimensional variable `\l__enumext_leftmargin_tmp_X_dim` are used by the `list-indent` key (§12.17). The variables `\l__enumext_leftmargin_X_dim` and `\l__enumext_itemindent_X_dim` are used and set by the function `__enumext_calc_hspace`:NNNNNNNNNN (§12.37.1).

```
71 \cs_set_protected:Npn \__enumext_tmp:n #1
72 {
73   \bool_new:c { \l__enumext_leftmargin_tmp_#1_bool }
74   \dim_new:c { \l__enumext_leftmargin_tmp_#1_dim }
75   \dim_new:c { \l__enumext_leftmargin_#1_dim }
76   \dim_new:c { \l__enumext_itemindent_#1_dim }
77 }
78 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\l__enumext_leftmargin_tmp_X_bool` and others.)

```
\l__enumext_multicols_above_X_skip
\l__enumext_multicols_below_X_skip
\g__enumext_multicols_right_X_skip
\l__enumext_align_label_pos_X_str
```

Internal variables used by `columns` key (§12.21) and `align` key (§12.12).

```
79 \cs_set_protected:Npn \__enumext_tmp:n #1
80 {
81   \skip_new:c { \l__enumext_multicols_above_#1_skip }
82   \skip_new:c { \l__enumext_multicols_below_#1_skip }
83   \skip_new:c { \g__enumext_multicols_right_#1_skip }
84   \str_new:c { \l__enumext_align_label_pos_#1_str }
85 }
86 \clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }
```

(End of definition for `\l__enumext_multicols_above_X_skip` and others.)

```
\g__enumext_minipage_stat_int
\l__enumext_minipage_left_skip
\l__enumext_minipage_right_skip
\l__enumext_minipage_after_skip
\g__enumext_minipage_right_skip
\g__enumext_minipage_after_skip
\l__enumext_minipage_left_X_dim
\l__enumext_minipage_active_X_bool
```

Internal variables used by `\miniright` command (§12.22.4) and the keys `mini-right`, `mini-right*`, `mini-env` and `mini-sep` (§12.20, §12.22).

```
87 \int_new:N \g__enumext_minipage_stat_int
88 \skip_new:N \l__enumext_minipage_left_skip
89 \skip_new:N \l__enumext_minipage_right_skip
90 \skip_new:N \l__enumext_minipage_after_skip
91 \skip_new:N \g__enumext_minipage_right_skip
92 \skip_new:N \g__enumext_minipage_after_skip
93 \cs_set_protected:Npn \__enumext_tmp:n #1
94 {
95   \dim_new:c { \l__enumext_minipage_left_#1_dim }
96   \bool_new:c { \l__enumext_minipage_active_#1_bool }
97 }
98 \clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\g__enumext_minipage_stat_int` and others.)

```
\l__enumext_wrap_label_X_bool
\l__enumext_wrap_label_opt_X_bool
\l__enumext_start_X_int
\l__enumext_fake_item_indent_X_tl
\l__enumext_label_fill_left_X_tl
\l__enumext_label_fill_right_X_tl
\l__enumext_vspace_a_star_X_bool
\l__enumext_vspace_b_star_X_bool
```

The bool vars `\l__enumext_wrap_label_X_bool` and `\l__enumext_wrap_label_opt_X_bool` are used by `wrap-label` and `wrap-label*` keys (§12.12), the integer `\l__enumext_start_X_int` are used by the `start` and `start*` keys (§12.14), the token list `\l__enumext_fake_item_indent_X_tl` is used by `itemindent` key (§12.17.1), the variables `\l__enumext_label_fill_left_X_tl` and `\l__enumext_label_fill_right_X_tl` are used by the `align` key (§12.12). The boolean vars `\l__enumext_vspace_a_star_X_bool`, `\l__enumext_vspace_b_star_X_bool` are used by `above`, `above*`, `below` and `below*` keys (§12.19).

```
99 \cs_set_protected:Npn \__enumext_tmp:n #1
100 {
101   \bool_new:c { \l__enumext_wrap_label_#1_bool }
102   \bool_new:c { \l__enumext_wrap_label_opt_#1_bool }
103   \int_new:c { \l__enumext_start_#1_int }
104   \tl_new:c { \l__enumext_fake_item_indent_#1_tl }
105   \tl_new:c { \l__enumext_label_fill_left_#1_tl }
106   \tl_new:c { \l__enumext_label_fill_right_#1_tl }
107   \bool_new:c { \l__enumext_vspace_a_star_#1_bool }
108   \bool_new:c { \l__enumext_vspace_b_star_#1_bool }
109 }
110 \clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\l__enumext_wrap_label_X_bool` and others.)

```

\l__enumext_store_active_bool
\l__enumext_store_name_tl
\g__enumext_store_name_tl
\l__enumext_store_anskey_arg_tl
\l__enumext_store_anskey_env_tl
\l__enumext_store_anskey_opt_tl
\l__enumext_store_current_label_tl
\l__enumext_store_current_opt_arg_tl
\l__enumext_store_current_label_tmp_tl

```

The variable `\l__enumext_store_active_bool` setting by `save-ans` key (§12.25.1) activates all the mechanism related to `\anskey`, `anskey*`, `keyans`, `keyans*` and `keyanspic` environments.

The variable `\l__enumext_store_name_tl` saves the `{⟨store name⟩}` set by the `save-ans` key of the *sequence* and *prop list* in which we will store, the variable `\g__enumext_store_name_tl` it's just a global copy of `{⟨store name⟩}` used by different functions.

The variable `\l__enumext_store_anskey_arg_tl` save the *argument* of `\anskey` (§12.29) and the variables `\l__enumext_store_anskey_env_tl` and `\l__enumext_store_anskey_opt_tl` save the `⟨body⟩` and the `⟨keys⟩` of the environment `anskey*` (§12.30).

The variables `\l__enumext_store_current_label_tl` and `\l__enumext_store_current_opt_arg_tl` save the *current label* and *optional argument* of `\item*` (§12.36) and `\anspic*` (§12.41.2) for the `keyans`, `keyans*` and `keyanspic` environments.

The variable `\l__enumext_store_current_label_tmp_tl` is a temporary variable used by `keyans`, `keyans*` and `keyanspic` at various points.

```

111 \bool_new:N \l__enumext_store_active_bool
112 \tl_new:N \l__enumext_store_name_tl
113 \tl_new:N \g__enumext_store_name_tl
114 \tl_new:N \l__enumext_store_anskey_arg_tl
115 \tl_new:N \l__enumext_store_anskey_env_tl
116 \tl_new:N \l__enumext_store_anskey_opt_tl
117 \tl_new:N \l__enumext_store_current_label_tl
118 \tl_new:N \l__enumext_store_current_opt_arg_tl
119 \tl_new:N \l__enumext_store_current_label_tmp_tl

```

(End of definition for `\l__enumext_store_active_bool` and others.)

```

\l__enumext_setkey_tmpa_tl
\l__enumext_setkey_tmpb_tl
\l__enumext_setkey_tmpa_int
\l__enumext_setkey_tmpa_seq
\l__enumext_setkey_tmpb_seq

```

Internal variables used by the command `\setenumext` (§12.47).

```

120 \tl_new:N \l__enumext_setkey_tmpa_tl
121 \tl_new:N \l__enumext_setkey_tmpb_tl
122 \int_new:N \l__enumext_setkey_tmpa_int
123 \seq_new:N \l__enumext_setkey_tmpa_seq
124 \seq_new:N \l__enumext_setkey_tmpb_seq

```

(End of definition for `\l__enumext_setkey_tmpa_tl` and others.)

```

\l__enumext_meta_path_tl
\l__enumext_foreach_print_seq
\l__enumext_foreach_name_prop_tl
\g__enumext_foreach_default_keys_tl

```

Internal variables used by the `\printkeyans` command (§12.46) and `\foreachkeyans` command (§12.49).

```

125 \tl_new:N \l__enumext_meta_path_tl
126 \seq_new:N \l__enumext_foreach_print_seq
127 \tl_new:N \l__enumext_foreach_name_prop_tl
128 \tl_new:N \g__enumext_foreach_default_keys_tl

```

(End of definition for `\l__enumext_meta_path_tl` and others.)

```

\l__enumext_print_keyans_starred_tl
\l__enumext_mark_position_str
\g__enumext_item_symbol_aux_tl
\l__enumext_print_keyans_X_tl
\l__enumext_store_save_key_X_tl
\l__enumext_store_save_key_X_bool
\l__enumext_store_upper_level_X_bool

```

Internal variables used by command `\printkeyans` (§12.46), `show-pos` key (§12.26), `item-sym*` key (§12.34), `save-key` key (§12.26.2) and “*storage level system*”.

```

129 \tl_new:N \l__enumext_print_keyans_starred_tl
130 \str_new:N \l__enumext_mark_position_str
131 \tl_new:N \g__enumext_item_symbol_aux_tl
132 \cs_set_protected:Npn \__enumext_tmp:n #1
133 {
134   \tl_new:c { \l__enumext_print_keyans_#1_tl }
135   \tl_new:c { \l__enumext_store_save_key_#1_tl }
136   \bool_new:c { \l__enumext_store_save_key_#1_bool }
137   \bool_new:c { \l__enumext_store_upper_level_#1_bool }
138 }
139 \clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_print_keyans_starred_tl` and others.)

```

\l__enumext_keyans_pic_body_seq
\l__enumext_keyans_pic_width_dim
\l__enumext_keyans_pic_above_int
\l__enumext_keyans_pic_below_int
\l__enumext_keyans_pic_star_bool
\l__enumext_keyans_pic_label_pos_str
\g__enumext_keyans_pic_parsep_skip
\l__enumext_anspic_label_box
\l__enumext_anspic_body_box
\l__enumext_anspic_label_htdp_dim
\l__enumext_anspic_body_htdp_dim

```

Internal variables used by `keyanspic` environment and `\anspic` command (§12.41.1).

```

140 \seq_new:N \l__enumext_keyans_pic_body_seq
141 \dim_new:N \l__enumext_keyans_pic_width_dim
142 \int_new:N \l__enumext_keyans_pic_above_int
143 \int_new:N \l__enumext_keyans_pic_below_int
144 \bool_new:N \l__enumext_keyans_pic_star_bool
145 \str_new:N \l__enumext_keyans_pic_label_pos_str
146 \skip_new:N \g__enumext_keyans_pic_parsep_skip
147 \box_new:N \l__enumext_anspic_label_box
148 \box_new:N \l__enumext_anspic_body_box
149 \dim_new:N \l__enumext_anspic_label_htdp_dim
150 \dim_new:N \l__enumext_anspic_body_htdp_dim

```

(End of definition for `\l__enumext_keyans_pic_body_seq` and others.)

Internal variables used by “*internal check answer*” mechanism (§12.25.3) used by the `check-ans` and `no-store` keys and check for starred commands `\item*` in `keyans` and `keyans*` environments and `\anspic*` in `keyanspic` environment.

```

151 \bool_new:N \l__enumext_check_answers_bool
152 \bool_new:N \g__enumext_check_ans_key_bool
153 \tl_new:N \l__enumext_check_start_line_env_tl
154 \int_new:N \g__enumext_check_starred_cmd_int
155 \int_new:N \g__enumext_item_anskey_int
156 \int_new:N \g__enumext_item_number_int
157 \bool_new:N \l__enumext_item_number_bool
158 \int_new:N \g__enumext_item_answer_diff_int

```

(End of definition for `\l__enumext_check_answers_bool` and others.)

The boolean variable `\l__enumext_hyperref_bool` will determine if the `hyperref` package is present or load in memory (§12.8). The boolean variable `\l__enumext_footnotes_key_bool` determine if `hyperref` is load with key `hyperfootnotes=true`.

```

159 \bool_new:N \l__enumext_hyperref_bool
160 \bool_new:N \l__enumext_footnotes_key_bool

```

(End of definition for `\l__enumext_hyperref_bool` and `\l__enumext_footnotes_key_bool`.)

Internal variables used by `save-ref` key (§12.26). The variables `\l__enumext_label_copy_X_tl` correspond to temporary copies of the $\langle labels \rangle$ defined by level on which operations will be performed.

The variables `\l__enumext_newlabel_arg_one_tl` and `\l__enumext_newlabel_arg_two_tl` will be used to form the arguments passed to the function `__enumext_newlabel:nn` (§12.8) and the variable `\l__enumext_write_aux_file_tl` will be in charge of executing the writing code in the `.aux` file.

```

161 \tl_new:N \l__enumext_newlabel_arg_one_tl
162 \tl_new:N \l__enumext_newlabel_arg_two_tl
163 \tl_new:N \l__enumext_write_aux_file_tl
164 \cs_set_protected:Npn \__enumext_tmp:n #1
165 {
166   \tl_new:c { l__enumext_label_copy_#1_tl }
167 }
168 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_newlabel_arg_one_tl` and others.)

Internal variables used for redefinition of `\footnote` (§12.42.4).

```

169 \int_new:N \g__enumext_footnote_int
170 \seq_new:N \g__enumext_footnote_arg_seq
171 \seq_new:N \g__enumext_footnote_int_seq

```

(End of definition for `\g__enumext_footnote_int`, `\g__enumext_footnote_arg_seq`, and `\g__enumext_footnote_int_seq`.)

Internal variables used by `enumext*` and `keyans*` environments.

```

172 \cs_set_protected:Npn \__enumext_tmp:n #1
173 {
174   \bool_new:c { l__enumext_item_starred_#1_bool }
175   \int_new:c { l__enumext_item_column_pos_#1_int }
176   \int_new:c { g__enumext_item_count_all_#1_int }
177   \int_new:c { l__enumext_joined_item_#1_int }
178   \int_new:c { l__enumext_joined_item_aux_#1_int }
179   \int_new:c { l__enumext_tmpa_#1_int }
180   \dim_new:c { l__enumext_tmpa_#1_dim }
181   \box_new:c { l__enumext_item_text_#1_box }
182   \dim_new:c { l__enumext_joined_width_#1_dim }
183   \dim_new:c { l__enumext_item_width_#1_dim }
184   \tl_new:c { g__enumext_item_symbol_aux_#1_tl }
185   \str_new:c { l__enumext_align_label_#1_str }
186   \bool_new:c { g__enumext_minipage_active_#1_bool }
187   \box_new:c { l__enumext_miniright_code_#1_box }
188   \bool_new:c { g__enumext_minipage_center_#1_bool }
189   \dim_new:c { g__enumext_minipage_right_#1_dim }
190   \skip_new:c { g__enumext_minipage_right_#1_skip }
191 }
192 \clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_item_starred_X_bool` and others.)

```
\c__enumext_all_envs_clist An internal clist-var variable to run with \__enumext_tmp:n.
193 \clist_const:Nn \c__enumext_all_envs_clist
194 {
195     {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv},
196     {keyans}{v}, {enumext*}{vii}, {keyans*}{viii}
197 }
```

(End of definition for `\c__enumext_all_envs_clist`.)

12.5 Some utility functions

`\keys_precompile:neN` Non-standard kernel variants used by the `\printkeyans` command (§12.46) and `\foreachkeyans` command (§12.49).

```
\seq_use:NV
198 \cs_generate_variant:Nn \keys_precompile:nnN { neN }
199 \cs_generate_variant:Nn \seq_use:Nn { NV }
```

(End of definition for `\keys_precompile:neN` and `\seq_use:NV`.)

`__enumext_at_begin_document:n` A internal “hook” function used for copying plain `list` and `minipage` environments definition and `hyperref` detection.

```
200 \cs_new_protected:Npn \__enumext_at_begin_document:n #1
201 {
202     \hook_gput_code:nnn {begindocument} {enumext} { #1 }
203 }
```

(End of definition for `__enumext_at_begin_document:n`.)

`__enumext_after_env:nn` A internal “hook” functions for execute code `mini-right` and `mini-right*` keys outside the `enumext*` and `keyans*` environments and print `check-ans` outside the `enumext` and `enumext*` environments.

```
\__enumext_before_env:nn
204 \cs_new_protected:Npn \__enumext_after_env:nn #1 #2
205 {
206     \hook_gput_code:nnn {env/#1/after} {enumext} {#2}
207 }
208 \cs_new_protected:Npn \__enumext_before_env:nn #1 #2
209 {
210     \hook_gput_code:nnn {env/#1/before} {enumext} {#2}
211 }
```

(End of definition for `__enumext_after_env:nn` and `__enumext_before_env:nn`.)

`__enumext_level:` Function for check current level in `enumext`.

```
212 \cs_new:Nn \__enumext_level:
213 {
214     \int_to_roman:n { \__enumext_level_int }
215 }
```

(End of definition for `__enumext_level:`.)

`__enumext_if_is_int:nT` A conditional function to know if the variable we are passing is an integer used by `start` and `widest` keys. `__enumext_if_is_int:nF` This function is taken directly from the answer given by Henri Menke in [How to test if an expl3 function argument is an integer expression?](#) `__enumext_if_is_int:nTF`

```
216 \prg_new_protected_conditional:Npnn \__enumext_if_is_int:n #1 { T, F, TF }
217 {
218     \regex_match:nnTF { ^[\+|-]?[\d]+$ } {#1} % $
219     { \prg_return_true: }
220     { \prg_return_false: }
221 }
```

(End of definition for `__enumext_if_is_int:nT`, `__enumext_if_is_int:nF`, and `__enumext_if_is_int:nTF`.)

`__enumext_regex_counter_style:` The internal function `__enumext_regex_counter_style:` replace the ‘*’ with the actual counter of the running level and is used by the `ref` key. It loops through the defined counter styles in `\c__enumext_counter_style_tl` and replace ‘*’ by real command, for example, looking for `\arabic*` and replacing that by `\arabic{<counter>}` defined on the current level.

```
222 \cs_new_protected:Nn \__enumext_regex_counter_style:
223 {
224     \tl_map_inline:Nn \c__enumext_counter_style_tl
225     {
226         \regex_replace_once:nnN { \c{##1}\* }
227         { \c{##1}\cB{\u{\l__enumext_ref_the_count_tl}\cE} } \l__enumext_ref_key_arg_tl
228     }
229 }
```

(End of definition for `__enumext_regex_counter_style:`.)

`__enumext_show_length:nnn`

Internal function used by `show-length` key to show “*all lengths*” calculated and use in `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```

230 \cs_new:Npn \__enumext_show_length:nnn #1 #2 #3
231 {
232     * ~ #2
233     \prg_replicate:nn { 14 - \str_count:n {#2} } { ~ }
234     = ~ \use:c { #1_use:c } { \__enumext_#2_#3_#1 } \\
235 }

```

(End of definition for `__enumext_show_length:nnn`.)

`__enumext_unskip_unkern:`

The function `__enumext_unskip_unkern:` will remove the last *⟨skip⟩* or *⟨kern⟩* at execution time using the values `11` and `12` of `\lastnodetype` to apply `\unskip` or `\unkern` according to the case.

```

236 \cs_new_protected:Npn \__enumext_unskip_unkern:
237 {
238     \int_case:nnT { \lastnodetype }
239     {
240         { 11 }
241         {
242             % \typeout{SKIP}
243             \typeout{\the\lastskip}
244             \unskip
245         }
246         { 12 }
247         {
248             % \typeout{KERN}
249             \typeout{\the\lastkern}
250             \unkern
251         }
252     }
253 }

```

(End of definition for `__enumext_unskip_unkern:`.)

12.5.1 Utilities for environments and levels

`__enumext_is_not_nested:`

The function `__enumext_is_not_nested:` set the variables `\g__enumext_standar_bool` and `\g__enumext_starred_bool` to “*true*” only if the environments `enumext` and `enumext*` are nested in each other and save the environment name in `\l__enumext_envir_name_tl`.

`__enumext_is_on_first_level:`

```

254 \cs_new_protected:Nn \__enumext_is_not_nested:
255 {
256     \str_case:en { \@currenvir }
257     {
258         {enumext}
259         {
260             \tl_set:Nn \l__enumext_envir_name_tl { enumext }
261             \bool_lazy_and:nnT
262             { \bool_not_p:n { \g__enumext_standar_bool } }
263             { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
264             {
265                 \bool_gset_true:N \g__enumext_standar_bool
266             }
267         }
268         {enumext*}
269         {
270             \tl_set:Nn \l__enumext_envir_name_tl { enumext* }
271             \bool_lazy_and:nnT
272             { \bool_not_p:n { \g__enumext_starred_bool } }
273             { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
274             {
275                 \bool_gset_true:N \g__enumext_starred_bool
276             }
277         }
278     }
279 }

```

The function `__enumext_is_on_first_level:` will set the variables `\l__enumext_standar_first_bool` (§12.25.1), `\l__enumext_starred_first_bool` (§12.25.1) and `\l__enumext_anskey_env_bool` (§12.30) to “*true*” only if the environment is not nested and we are in the “*first level*” of it . We will also save the *start line number* of each environment in the variable `\g__enumext_start_line_tl` and the *name*

of each environment in the variable `\g__enumext_envir_name_tl` to use in messages related to the `check-ans` key and `.log` file.

```

280 \cs_new_protected:Nn \__enumext_is_on_first_level:
281 {
282   \bool_lazy_all:nT
283   {
284     { \bool_if_p:N \g__enumext_standar_bool }
285     { \int_compare_p:nNn { \l__enumext_level_int } = { 1 } }
286     { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
287   }
288   {
289     \bool_set_true:N \l__enumext_standar_first_bool
290     \bool_set_true:N \l__enumext_anskey_env_bool
291     \tl_gset:Nn \g__enumext_envir_name_tl { enumext }
292     \tl_gset:Ne \g__enumext_start_line_tl
293     {
294       on ~ line ~ \exp_not:V \inputlineno
295     }
296   }
297   \bool_lazy_all:nT
298   {
299     { \bool_if_p:N \g__enumext_starred_bool }
300     { \int_compare_p:nNn { \l__enumext_level_h_int } = { 1 } }
301     { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
302   }
303   {
304     \bool_set_true:N \l__enumext_starred_first_bool
305     \bool_set_true:N \l__enumext_anskey_env_bool
306     \tl_gset:Nn \g__enumext_envir_name_tl { enumext* }
307     \tl_gset:Ne \g__enumext_start_line_tl
308     {
309       on ~ line ~ \exp_not:V \inputlineno
310     }
311   }
312 }

```

(End of definition for `__enumext_is_not_nested:` and `__enumext_is_on_first_level:`)

`__enumext_keyans_name_and_start:`

The function `__enumext_keyans_name_and_start:` will save the start line number and name of the environments `keyans`, `keyans*` and `keyanspic` in the variables `\l__enumext_check_start_line_env_tl` and `\l__enumext_envir_name_tl` to use in the `__enumext_check_starred_cmd:n` function.

```

313 \cs_new_protected:Nn \__enumext_keyans_name_and_start:
314 {
315   \str_case:en { \@currentenvir }
316   {
317     {keyans}
318     {
319       \tl_set:Nn \l__enumext_envir_name_tl { keyans }
320       \tl_set:Ne \l__enumext_check_start_line_env_tl
321       {
322         in ~ 'keyans' ~ start ~ on ~ line ~ \exp_not:V \inputlineno
323       }
324     }
325     {keyans*}
326     {
327       \tl_set:Nn \l__enumext_envir_name_tl { keyans* }
328       \tl_set:Ne \l__enumext_check_start_line_env_tl
329       {
330         in ~ 'keyans*' ~ start ~ on ~ line ~ \exp_not:V \inputlineno
331       }
332     }
333     {keyanspic}
334     {
335       \tl_set:Nn \l__enumext_envir_name_tl { keyanspic }
336       \tl_set:Ne \l__enumext_check_start_line_env_tl
337       {
338         in ~ 'keyanspic' ~ start ~ on ~ line ~ \exp_not:V \inputlineno
339       }
340     }
341   }
342 }

```

(End of definition for `__enumext_keyans_name_and_start:`.)

12.5.2 Utilities for log and terminal

The function `__enumext_reset_global_vars:` will be passed to the function `__enumext_execute_after_env:` and will return the global variables to their default values after being used.

```

343 \cs_new_protected:Nn \__enumext_reset_global_vars:
344 {
345   \__enumext_reset_global_int:
346   \__enumext_reset_global_bool:
347   \__enumext_reset_global_tl:
348 }
349 \cs_new_protected:Nn \__enumext_reset_global_int:
350 {
351   \int_gzero:N \g__enumext_item_number_int
352   \int_gzero:N \g__enumext_item_anskey_int
353   \int_gzero:N \g__enumext_item_answer_diff_int
354 }
355 \cs_new_protected:Nn \__enumext_reset_global_bool:
356 {
357   \bool_gset_false:N \g__enumext_check_ans_key_bool
358   \bool_gset_false:N \g__enumext_standar_bool
359   \bool_gset_false:N \g__enumext_starred_bool
360 }
361 \cs_new_protected:Nn \__enumext_reset_global_tl:
362 {
363   \tl_gclear:N \g__enumext_store_name_tl
364   \tl_gclear:N \g__enumext_start_line_tl
365   \tl_gclear:N \g__enumext_envir_name_tl
366 }

```

(End of definition for `__enumext_reset_global_vars:` and others.)

The function `__enumext_log_global_vars:` will be passed to the function `__enumext_execute_after_env:` and write to the `.log` file the number of elements saved in the *(prop list)* and *(sequence)* created by the `save-ans` key along with the value of the integer variable created for the `resume` key.

```

367 \cs_new_protected:Nn \__enumext_log_global_vars:
368 {
369   \msg_log:nneeee { enumext } { prop-seq-int-hook }
370   { \g__enumext_store_name_tl }
371   { \prop_count:c { g__enumext_ \g__enumext_store_name_tl _prop } }
372   { \seq_count:c { g__enumext_ \g__enumext_store_name_tl _seq } }
373   { \int_use:c { g__enumext_resume_ \g__enumext_store_name_tl _int } }
374 }

```

The function `__enumext_log_answer_vars:` will be passed to the function `__enumext_execute_after_env:` and write to the `.log` file the number of items and answers along with the difference between them.

```

375 \cs_new_protected:Nn \__enumext_log_answer_vars:
376 {
377   \msg_log:nneee { enumext } { item-answer-hook }
378   { \int_use:N \g__enumext_item_number_int }
379   { \int_use:N \g__enumext_item_anskey_int }
380   { \int_eval:n { \g__enumext_item_number_int - \g__enumext_item_anskey_int } }
381 }

```

(End of definition for `__enumext_log_global_vars:` and `__enumext_log_answer_vars:`.)

12.6 Copying list and minipage environments

The `list` environment provided by \LaTeX has the following plain form:

```

\list{⟨arg one⟩}{⟨arg two⟩}
  \item[⟨opt⟩]
\endlist

```

As a precaution we copy them using `__enumext_at_begin_document:n` in case any package redefines the `list` environment or a related command.

For compatibility with \LaTeX tagged PDF we should use `\NewCommandCopy` and not `\cs_new_eq:NN`. When tagged PDF is active `\item` is redefined using `ltxcmd` (see `latex-lab-block`).

```

\__enumext_start_list:nn
\__enumext_stop_list:
\__enumext_item_std:w

```

The functions `__enumext_start_list:nn`, `__enumext_stop_list:` and `__enumext_item_std:w` correspond to copies of `\list`, `\endlist` and `\item` from plain definition of `list` environment.

```

382 \__enumext_at_begin_document:n
383 {
384   \cs_new_eq:NN \__enumext_start_list:nn \list
385   \cs_new_eq:NN \__enumext_stop_list: \endlist
386   \NewCommandCopy \__enumext_item_std:w \item
387 }

```

(End of definition for `__enumext_start_list:nn`, `__enumext_stop_list:`, and `__enumext_item_std:w`.)

The `minipage` environment provided by \TeX has the following (simplified) plain form:

```

\minipage[⟨pos⟩][⟨height⟩][⟨inner-pos⟩]{⟨width⟩}
⟨internal implement⟩
\endminipage

```

As a precaution we copy them using `__enumext_at_begin_document:n` in case any package redefines the `minipage` environment or a related command.

```

\__enumext_minipage:w
\__enumext_endminipage:

```

The functions `__enumext_minipage:w`, `__enumext_endminipage:` and correspond to copies of `\minipage`, `\endminipage` from plain definition of `minipage` environment.

```

388 \__enumext_at_begin_document:n
389 {
390   \cs_new_eq:NN \__enumext_minipage:w \minipage
391   \cs_new_eq:NN \__enumext_endminipage: \endminipage
392 }

```

(End of definition for `__enumext_minipage:w` and `__enumext_endminipage:.`)

12.7 The internal minipage environment

```

\__enumext_internal_mini_page:
__enumext_mini_env*

```

The function `__enumext_internal_mini_page:` creates a internal `__enumext_mini_page` environment (*custom version* of `minipage`) setting the `\if@minipage` switch to “false” to allow spaces at the “above” of the environment, plus we will add `\skip_vertical:N \c_zero_skip` to maintain alignment on “top” in the first part and `\skip_vertical:N \c_zero_skip` in the second part to allow spaces “below”. This environment will be used internally by the `mini-env` key, it is not documented in the user interface and is for internal use only. This function is passed to the function `__enumext_safe_exec:` in the `enumext` environment definition (§12.38) and `__enumext_safe_exec_vii:` in the `enumext*` environment definition (§12.43)

```

393 \cs_new_protected:Nn \__enumext_internal_mini_page:
394 {
395   \int_compare:nNnT { \__enumext_level_int } = { 0 }
396   {
397     \DeclareDocumentEnvironment{__enumext_mini_page}{ m }
398     {
399       \__enumext_minipage:w [ t ] { ##1 }
400       \legacy_if_gset_false:n { @minipage }
401       \skip_vertical:N \c_zero_skip
402     }
403     {
404       \skip_vertical:N \c_zero_skip
405       \__enumext_endminipage:
406     }
407   }
408 }

```

(End of definition for `__enumext_internal_mini_page:` and `__enumext_mini_env*`.)

12.8 Compatibility with hyperref and footnotehyper

First we define the necessary rules using “hooks” to determine if the `hyperref` package is loaded.

```

409 \hook_gput_code:nnn { begindocument } { enumext } { \__enumext_after_hyperref: }
410 \hook_gset_rule:nnnn { begindocument } { enumext } { after } { hyperref }

```

```

\__enumext_after_hyperref:
\__enumext_hypertarget:nn
\__enumext_phantomsection:

```

The function `__enumext_after_hyperref:` sets the state of the boolean variable `__enumext_hypertarget_bool` to “true” if the package is loaded. At this point we will use the public macro `\IfHyperBoolean` to determine if the `hyperfootnotes=true` key is present, if so, we set the state of the boolean variable `__enumext_footnotes_key_bool` to “true”.

```

411 \cs_new_protected:Nn \__enumext_after_hyperref:
412 {
413   \IfPackageLoadedTF { hyperref }

```

```

414     {
415       \msg_info:nnn { enumext } { package-load } { hyperref }
416       \bool_set_true:N \l__enumext_hyperref_bool
417       \IfHyperBoolean{hyperfootnotes}
418       {
419         % \typeout{hyperfootnotes=true}
420         \bool_set_true:N \l__enumext_footnotes_key_bool
421       }
422       {
423         % \typeout{hyperfootnotes=false}
424       }
425     }
426     { }

```

If the state of the variable `\l__enumext_footnotes_key_bool` is true we will check if the package `footnotehyper` is loaded, in case it is not present, we will set the value of `\l__enumext_footnotes_key_bool` to false and we will redefine `\footnote`.

```

427     \bool_if:NT \l__enumext_footnotes_key_bool
428     {
429       \IfPackageLoadedTF { footnotehyper }
430       {
431         \msg_info:nnn { enumext } { package-load } { footnotehyper }
432       }
433       {
434         % \typeout{No ~ footnotehyper ~ load}
435         % \typeout{Load ~ and ~ use ~ \string\makesavenoteenv{enumext*}}
436         \bool_set_false:N \l__enumext_footnotes_key_bool
437       }
438     }

```

The functions `__enumext_hypertarget:nn` and `__enumext_phantomsection:` correspond to the internal copies of `\hypertarget` and `\phantomsection`. If the boolean variable `\l__enumext_hyperref_bool` is false the functions `__enumext_hypertarget:nn` and `__enumext_phantomsection:` will be disabled.

```

439     \bool_if:NTF \l__enumext_hyperref_bool
440     {
441       \cs_new_eq:NN \__enumext_hypertarget:nn \hypertarget
442       \cs_new_eq:NN \__enumext_phantomsection: \phantomsection
443     }
444     {
445       \cs_new_eq:NN \__enumext_hypertarget:nn \use_none:nn
446       \cs_new_eq:NN \__enumext_phantomsection: \prg_do_nothing:
447     }
448   }

```

(End of definition for `__enumext_after_hyperref:`, `__enumext_hypertarget:nn`, and `__enumext_phantomsection:`.)

`__enumext_newlabel:nn` The function `__enumext_newlabel:nn` write the information to the `.aux` file when using the `save-ref` key. The arguments taken by the function are:

#1: `\l__enumext_newlabel_arg_one_tl`
 #2: `\l__enumext_newlabel_arg_two_tl`

🔗 The trick here is to manage the number of arguments passed to `\newlabel{#1}{#2}` according to the presence of the `hyperref` package.

```

449     \cs_new_protected:Npn \__enumext_newlabel:nn #1 #2
450     {
451       \protected@write \@auxout { }
452       {
453         \token_to_str:N \newlabel {#1}
454         {
455           {#2}
456           \bool_if:NT \l__enumext_hyperref_bool
457           { { \thepage } {#2} {#1} }
458           { }
459         }
460       }
461       \__enumext_hypertarget:nn {#1} { }
462       \__enumext_phantomsection:
463     }

```

(End of definition for `__enumext_newlabel:nn`.)

12.9 Definition of public dimension

The package `enumext` only provides a single public dimension `\itemwidth` and is intended for user convenience only and is not for internal use as such. This dimension is set in all environments and is only used by the `wrap-ans` key at its default value.

```
464 \dim_zero_new:N \itemwidth
```

12.10 Definition of counters

```
\__enumext_define_counters:Nn
\__enumext_define_counters:cn
```

To create the necessary “counters” we must first make sure that they are not already defined by the user or a package such as `enumitem`, otherwise a error will be returned and the package loading will be aborted. The arguments taken by the function are:

- #1 : A token list `__enumext_counter_X_tl` for “store” the counter’s name.
- #2 : The counter’s name.

```
465 \cs_new_protected:Npn \__enumext_define_counters:Nn #1 #2
466 {
467   \cs_if_exist:cTF { c@ #2 }
468   { \msg_fatal:nnn { enumext } { counters } { #2 } }
469   {
470     \tl_set:Nn #1 { #2 }
471     \newcounter { #2 }
472   }
473 }
```

(End of definition for `__enumext_define_counters:Nn`.)

The counters created here are `enumXi`, `enumXii`, `enumXiii` and `enumXiv` for `enumext` environment, `enumXv` for `keyans` environment, `enumXvi` for `keyanspic` environment, `enumXvii` for `enumext*` and `enumXviii` for the `keyans*` environments.

```
enumXi      474 \__enumext_define_counters:Nn \__enumext_counter_i_tl { enumXi }
enumXii     475 \__enumext_define_counters:Nn \__enumext_counter_ii_tl { enumXii }
enumXiii    476 \__enumext_define_counters:Nn \__enumext_counter_iii_tl { enumXiii }
enumXiv     477 \__enumext_define_counters:Nn \__enumext_counter_iv_tl { enumXiv }
enumXv      478 \__enumext_define_counters:Nn \__enumext_counter_v_tl { enumXv }
enumXvi     479 \__enumext_define_counters:Nn \__enumext_counter_vi_tl { enumXvi }
enumXvii    480 \__enumext_define_counters:Nn \__enumext_counter_vii_tl { enumXvii }
enumXviii   481 \__enumext_define_counters:Nn \__enumext_counter_viii_tl { enumXviii }
```

(End of definition for `enumXi` and others.)

12.11 Definition of labels

This part of the code is inspired by the `enumitem` package. The idea is to be able to access the counters using `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` to use them in the `label` key.

```
\__enumext_register_counter_style:Nn
```

These `<counters>` will be used as default `<labels>` if the `label` key is not used for the different levels of the `enumext` environment and the `keyans` environment, so it is necessary to get a default value for `labelwidth` from these `<labels>` at the same time.

```
482 \cs_new_protected:Npn \__enumext_register_counter_style:Nn #1 #2
483 {
484   \tl_const:cn { c__enumext_widest_ \cs_to_str:N #1 _tl } {#2}
485   \tl_gput_right:Nn \g__enumext_counter_styles_tl {#1}
486 }
487 \__enumext_register_counter_style:Nn \arabic { 0 }
488 \__enumext_register_counter_style:Nn \Alph { M }
489 \__enumext_register_counter_style:Nn \alph { m }
490 \__enumext_register_counter_style:Nn \Roman { VIII }
491 \__enumext_register_counter_style:Nn \roman { viii }
```

(End of definition for `__enumext_register_counter_style:Nn`.)

```
\__enumext_label_width_by_box:Nn
\__enumext_label_width_by_box:cv
```

The function `__enumext_label_width_by_box:Nn` set the default `\labelwidth` using a box width if no `labelwidth` key is passed.

```
492 \cs_new_protected:Npn \__enumext_label_width_by_box:Nn #1 #2
493 {
494   \hbox_set:Nn \__enumext_label_width_by_box {#2}
495   \dim_set:Nn #1 { \box_wd:N \__enumext_label_width_by_box }
496 }
497 \cs_generate_variant:Nn \__enumext_label_width_by_box:Nn { cv }
```

(End of definition for `__enumext_label_width_by_box:Nn`.)

`__enumext_label_style:Nnn`
`__enumext_label_style:cvn`

The function `__enumext_label_style:Nnn` is used by the `label` key to creates the variables containing the *label style* and will allow to use `\arabic*`, `\Alpha*`, `\alph*`, `\Roman*` and `\roman*` as arguments. It loops through the defined counter styles in `\g__enumext_counter_styles_tl` (`\arabic`, `\alph`, `\Alpha`, `\roman`, and `\Roman`) for example, looking for `\roman*` and replacing that by `\roman{<counter>}`, and doing the same for the `\g__enumext_widest_label_tl` to keep both in sync.

```

498 \cs_new_protected:Npn \__enumext_label_style:Nnn #1 #2 #3
499 {
500   \tl_clear_new:N #1
501   \tl_put_right:Ne #1 { \tl_trim_spaces:n {#3} }
502   \tl_gset_eq:NN \g__enumext_widest_label_tl #1
503   \tl_map_inline:Nn \g__enumext_counter_styles_tl
504     {
505       \tl_replace_all:Nne #1 { ##1* } { \exp_not:N ##1 {#2} }
506       \tl_greplace_all:Nne \g__enumext_widest_label_tl { ##1* }
507         { \tl_use:c { c__enumext_widest_ \cs_to_str:N ##1 _tl } }
508     }
509   \__enumext_label_width_by_box:Nn \__enumext_current_widest_dim
510   { \tl_use:N \g__enumext_widest_label_tl }
511   \tl_set_eq:cN { the #2 } #1
512 }
513 \cs_generate_variant:Nn \__enumext_label_style:Nnn { cvn }

```

(End of definition for `__enumext_label_style:Nnn`.)

12.12 Setting keys associated with label

`font`
`labelsep`
`labelwidth`
`wrap-label`
`wrap-label*`

Definition of keys `font`, `labelsep`, `labelwidth`, `wrap-label` and `wrap-label*` keys for `enumext` and `keyans` environments.

```

514 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
515 {
516   \keys_define:nn { enumext / #1 }
517   {
518     font      .tl_set:c   = { l__enumext_label_font_style_#2_tl },
519     font      .value_required:n = true,
520     labelsep  .dim_set:c   = { l__enumext_labelsep_#2_dim },
521     labelsep  .initial:n   = {0.3333em},
522     labelsep  .value_required:n = true,
523     labelwidth .dim_set:c   = { l__enumext_labelwidth_#2_dim },
524     labelwidth .value_required:n = true,
525     wrap-label .cs_set_protected:cp = { __enumext_wrapper_label_#2:n } ##1,
526     wrap-label .initial:n   = {##1},
527     wrap-label .value_required:n = true,
528     wrap-label* .code:n = {
529       \bool_set_true:c { l__enumext_wrap_label_opt_#2_bool }
530       \keys_set:nn { enumext / #1 } { wrap-label = {##1} }
531     },
532     wrap-label* .value_required:n = true,
533   }
534 }
535 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `font` and others.)

- In this point, the following are set `__enumext_wrapper_label_X:n` which will be used by `__enumext_make_label:` for the different levels of the `enumext` environment and is set to `__enumext_wrapper_label_v:n` which will be used by `__enumext_keyans_make_label:` for `keyans` and `keyanspic` environments.

`align` The `align` key is implemented differently for “starred” and “non starred” environments.

```

536 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
537 {
538   \keys_define:nn { enumext / #1 }
539   {
540     align .choice:,
541     align / left .code:n =
542       {
543         \tl_clear:c { l__enumext_label_fill_left_#2_tl }
544         \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
545         \str_set:cn { l__enumext_align_label_pos_#2_str } { l }
546       },
547     align / right .code:n =
548       {
549         \tl_set:cn { l__enumext_label_fill_left_#2_tl } { \hfill }

```



```

550         \tl_clear:c { l__enumext_label_fill_right_#2_tl }
551         \str_set:cn { l__enumext_align_label_pos_#2_str } { r }
552     },
553     align / center .code:n =
554     {
555         \tl_set:cn { l__enumext_label_fill_left_#2_tl } { \hfill }
556         \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
557         \str_set:cn { l__enumext_align_label_pos_#2_str } { c }
558     },
559     align / unknown .code:n =
560         \msg_error:nneee { enumext } { unknown-choice }
561         { align } { left, ~ right, ~ center } { \exp_not:n {##1} },
562     align .initial:n = left,
563     align .value_required:n = true,
564 }
565 }
566 \clist_map_inline:nn
567 {
568     {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {keyans}{v}
569 }
570 { \__enumext_tmp:nn #1 }

```

For compatibility with \LaTeX tagged PDF we must set `\l__enumext_align_label_pos_X_str`. When tagged PDF is active `\makeatlabel` is redefined and the only way to get the align key to work correctly is by using `\makebox`.

```

571 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
572 {
573     \keys_define:nn { enumext / #1 }
574     {
575         align .choice:,
576         align / left .code:n = \str_set:cn { l__enumext_align_label_#2_str } { l },
577         align / right .code:n = \str_set:cn { l__enumext_align_label_#2_str } { r },
578         align / center .code:n = \str_set:cn { l__enumext_align_label_#2_str } { c },
579         align / unknown .code:n =
580             \msg_error:nneee { enumext } { unknown-choice }
581             { align } { left, ~ right, ~ center } { \exp_not:n {##1} },
582         align .initial:n = left,
583         align .value_required:n = true,
584     }
585 }
586 \clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }

```

(End of definition for align.)

12.13 Setting label and ref keys

The implementation of the keys `label` and `ref` are part of the core of the package `enumext`, here the default values for $\langle label \rangle$, the value of the variables `\l__enumext_label_X_tl`, the default values for `\labelwidth` and the “label and ref” system.

12.13.1 Define and set label and ref keys for enumext environment

Here we set the default $\langle labels \rangle$ of the *four levels* of `enumext` environment, along with the default value for `labelwidth` key and `ref` key.

```

label
ref
\l__enumext_label_i_tl
\l__enumext_label_ii_tl
\l__enumext_label_iii_tl
\l__enumext_label_iv_tl
587 \cs_set_protected:Npn \__enumext_tmp:nnn #1 #2 #3
588 {
589     \keys_define:nn { enumext / #1 }
590     {
591         label .code:n = {
592             \__enumext_label_style:cnv { l__enumext_label_#2_tl }
593             { l__enumext_counter_#2_tl } {##1}
594             \dim_set_eq:cN { l__enumext_labelwidth_#2_dim }
595             \l__enumext_current_widest_dim
596         },
597         label .initial:n = #3,
598         label .value_required:n = true,
599         ref .code:n = \__enumext_standar_ref:n {##1},
600         ref .value_required:n = true,
601     }
602 }
603 \__enumext_tmp:nnn { level-1 } { i } { \arabic*. }
604 \__enumext_tmp:nnn { level-2 } { ii } { (\alph*. ) }
605 \__enumext_tmp:nnn { level-3 } { iii } { \roman*. }
606 \__enumext_tmp:nnn { level-4 } { iv } { \Alph*. }

```

(End of definition for `label` and others.)

`__enumext_standar_ref:n`
`__enumext_standar_ref:`

The `__enumext_standar_ref:n` first we will pass the key argument to `__enumext_ref_key_arg_tl` and we will analyze its state, if it is not *empty* we will make a copy of the current counter in `__enumext_ref_the_count_tl` and we will execute the function `__enumext_regex_counter_style:` which will return the modified `__enumext_ref_key_arg_tl` and we make the value of `__enumext_ref_the_count_tl` the same as that `__enumext_the_counter_X_tl` which contains `\theenumX` and finally we set `__enumext_renew_the_count_X_tl` with the renewed command.

```

607 \cs_new_protected:Npn \__enumext_standar_ref:n #1
608 {
609   \tl_set:Nn \__enumext_ref_key_arg_tl {#1}
610   \tl_if_empty:NTF \__enumext_ref_key_arg_tl
611   {
612     \msg_error:nnn { enumext } { key-ref-empty } { enumext }
613   }
614   {
615     \tl_set_eq:Nc
616       \__enumext_ref_the_count_tl { \__enumext_counter_ \__enumext_level: _tl }
617     \__enumext_regex_counter_style:
618     \tl_set_eq:Nc
619       \__enumext_ref_the_count_tl { \__enumext_the_counter_ \__enumext_level: _tl }
620     \tl_put_right:ce { \__enumext_renew_the_count_ \__enumext_level: _tl }
621     {
622       \exp_not:N \renewcommand { \exp_not:V \__enumext_ref_the_count_tl }
623       { \exp_not:V \__enumext_ref_key_arg_tl }
624     }
625   }
626 }

```

Finally the function `__enumext_standar_ref:` will execute the modification for the reference system in the second argument of the environment definition `enumext`.

```

627 \cs_new_protected:Nn \__enumext_standar_ref:
628 {
629   \tl_if_empty:cF { \__enumext_renew_the_count_ \__enumext_level: _tl }
630   {
631     \tl_use:c { \__enumext_renew_the_count_ \__enumext_level: _tl }
632   }
633 }

```

(End of definition for `__enumext_standar_ref:n` and `__enumext_standar_ref:`.)

12.13.2 Define and set `label` and `ref` keys for `enumext*` and `keyans*` environments

`label`
`ref`

Here we set the default *⟨labels⟩* for `enumext*` and `keyans*` environments, along with the default value for `labelwidth` key and `ref` key.

`__enumext_label_vii_tl`
`__enumext_label_viii_tl`

```

634 \cs_set_protected:Npn \__enumext_tmp:nnn #1 #2 #3
635 {
636   \keys_define:nn { enumext / #1 }
637   {
638     label .code:n = {
639       \__enumext_label_style:cvn { \__enumext_label_#2_tl }
640       { \__enumext_counter_#2_tl } {##1}
641       \dim_set_eq:cN { \__enumext_labelwidth_#2_dim }
642       \__enumext_current_widest_dim
643     },
644     label .initial:n = #3,
645     label .value_required:n = true,
646     ref .code:n = \__enumext_starred_ref:n {##1},
647     ref .value_required:n = true,
648   }
649 }
650 \__enumext_tmp:nnn { enumext* } { vii } { \arabic*. }
651 \__enumext_tmp:nnn { keyans* } { viii } { \Alph*. }

```

(End of definition for `label` and others.)

`__enumext_starred_ref:n`
`__enumext_starred_ref:`

The implementation of `__enumext_starred_ref:n` is the same as that used for the environment `enumext`.

```

652 \cs_new_protected:Npn \__enumext_starred_ref:n #1
653 {
654   \tl_set:Nn \__enumext_ref_key_arg_tl {#1}
655   \int_compare:nNnT { \__enumext_level_h_int } = { 1 }
656   {

```

```

657 \tl_if_empty:NTF \l__enumext_ref_key_arg_tl
658 {
659   \msg_error:nnn { enumext } { key-ref-empty } { enumext* }
660 }
661 {
662   \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_counter_vii_tl
663   \__enumext_regex_counter_style:
664   \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_the_counter_vii_tl
665   \tl_put_right:Ne \l__enumext_renew_the_count_vii_tl
666   {
667     \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_the_count_tl }
668     { \exp_not:V \l__enumext_ref_key_arg_tl }
669   }
670 }
671 }
672 \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
673 {
674   \tl_if_empty:NTF \l__enumext_ref_key_arg_tl
675   {
676     \msg_error:nnn { enumext } { key-ref-empty } { keyans* }
677   }
678   {
679     \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_counter_viii_tl
680     \__enumext_regex_counter_style:
681     \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_the_counter_viii_tl
682     \tl_put_right:Ne \l__enumext_renew_the_count_viii_tl
683     {
684       \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_the_count_tl }
685       { \exp_not:V \l__enumext_ref_key_arg_tl }
686     }
687   }
688 }
689 }

```

Finally the function `__enumext_starred_ref:` will execute the modification for the reference system in the second argument of the `enumext*` and `keyans*` environment definition.

```

690 \cs_new_protected:Nn \__enumext_starred_ref:
691 {
692   \int_compare:nNnT { \l__enumext_level_h_int } = { 1 }
693   {
694     \tl_if_empty:NF \l__enumext_renew_the_count_vii_tl
695     {
696       \tl_use:N \l__enumext_renew_the_count_vii_tl
697     }
698   }
699   \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
700   {
701     \tl_if_empty:NF \l__enumext_renew_the_count_viii_tl
702     {
703       \tl_use:N \l__enumext_renew_the_count_viii_tl
704     }
705   }
706 }

```

(End of definition for `__enumext_starred_ref:n` and `__enumext_starred_ref:`.)

12.13.3 Define and set label and ref keys for keyans and keyanspic environments

Here we set the default `<label>` for `keyans` and `keyanspic` environment, along with the default value for `labelwidth` and `ref` key. The `keyanspic` environment use the same `<label>` as the `keyans` environment.

```

\l__enumext_label_v_tl
\l__enumext_label_vi_tl
707 \keys_define:nn { enumext / keyans }
708 {
709   label .code:n = {
710     \__enumext_label_style:cvn { \l__enumext_label_v_tl }
711     { \l__enumext_counter_v_tl } {#1}
712     \dim_set_eq:cN { \l__enumext_labelwidth_v_dim }
713     \l__enumext_current_widest_dim
714     \__enumext_label_style:cvn { \l__enumext_label_vi_tl }
715     { \l__enumext_counter_vi_tl } {#1}
716     \dim_set_eq:cN { \l__enumext_labelwidth_v_dim }
717     \l__enumext_current_widest_dim
718   },

```

```

719     label .initial:n = \Alph*),
720     label .value_required:n = true,
721     ref .code:n = \__enumext_keyans_ref:n {#1},
722     ref .value_required:n = true,
723 }

```

(End of definition for `label` and others.)

The implementation of `__enumext_keyans_ref:n` is the same as that used for the environment `enumext`.

```

\__enumext_keyans_ref:n
\__enumext_keyans_ref:
724 \cs_new_protected:Npn \__enumext_keyans_ref:n #1
725 {
726   \tl_set:Nn \l__enumext_ref_key_arg_tl {#1}
727   \tl_if_empty:NTF \l__enumext_ref_key_arg_tl
728   {
729     \msg_error:nnn { enumext } { key-ref-empty } { keyans }
730   }
731   {
732     \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_counter_v_tl
733     \__enumext_regex_counter_style:
734     \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_the_counter_v_tl
735     \tl_put_right:Ne \l__enumext_renew_the_count_v_tl
736     {
737       \exp_not:N \renewcommand { \exp_not:N \l__enumext_ref_the_count_tl }
738       { \exp_not:N \l__enumext_ref_key_arg_tl }
739     }
740   }
741 }

```

Finally the function `__enumext_keyans_ref:` will execute the modification for the reference system in the second argument of the `keyans*` environment definition.

```

742 \cs_new_protected:Nn \__enumext_keyans_ref:
743 {
744   \tl_if_empty:NF \l__enumext_renew_the_count_v_tl
745   {
746     \tl_use:N \l__enumext_renew_the_count_v_tl
747   }
748 }

```

(End of definition for `__enumext_keyans_ref:n` and `__enumext_keyans_ref:`.)

12.14 Setting `start`, `start*` and widest keys

```

\__enumext_start_from:NNn
\__enumext_start_from:ccn
\__enumext_start_from:cce

```

The function `__enumext_start_from:NNn` used by `start` and `start*` keys take three arguments:

#1: `\l__enumext_label_X_tl`
 #2: `\l__enumext_start_X_int`
 #3: *⟨integer or string⟩*

The first argument of this function are the “*counter style*” set by `label` key, the second argument is returned by the function, the third argument can be an *⟨integer⟩* or *⟨string⟩* of the form `\Alph`, `\alph`, `\Roman` or `\roman`. This effectively allows `start=A` or `start=1` to be used.

```

749 \cs_new_protected:Npn \__enumext_start_from:NNn #1 #2 #3
750 {
751   \__enumext_if_is_int:nTF { #3 }
752   {
753     \int_set:Nn #2 {#3}
754   }
755   {
756     \regex_match:nVT { \c{Alph} | \c{alph} } {#1}
757     { \int_set:Nn #2 { \int_from_alph:n {#3} } }
758     \regex_match:nVT { \c{Roman} | \c{roman} } {#1}
759     { \int_set:Nn #2 { \int_from_roman:n {#3} } }
760   }
761 }
762 \cs_generate_variant:Nn \__enumext_start_from:NNn { ccn, cce }

```

(End of definition for `__enumext_start_from:NNn`.)

```

\__enumext_widest_from:nNNn
\__enumext_widest_from:nccn

```

The function `__enumext_widest_from:nNNn` used by the `widest` key take four arguments:

#1: The counter associated with the environment level
 #2: `\l__enumext_label_X_tl`
 #3: `\l__enumext_labelwidth_X_dim`
 #4: *⟨integer or string⟩*

The second and third arguments of this function are the values set by `label` and `labelwidth` keys, the four argument can be an *integer* or *string* of the form `\Alph`, `\alph`, `\Roman` or `\roman`. The value of the four argument is set temporarily for the identified counter in this point (level), then the value is expanded into a “box” and the “width” of the “box” is returned.

```

763 \cs_new_protected:Npn \__enumext_widest_from:nNNn #1 #2 #3 #4
764 {
765   \__enumext_if_is_int:nTF {#4}
766   {
767     \setcounter{enumX#1} { #4 }
768   }
769   {
770     \regex_match:nVT { \c{Alph} | \c{alph} } {#2}
771     { \setcounter{enumX#1} { \int_from_alph:n {#4} } }
772     \regex_match:nVT { \c{Roman} | \c{roman} } {#2}
773     { \setcounter{enumX#1} { \int_from_roman:n {#4} } }
774   }
775   \__enumext_label_width_by_box:cv
776   { l__enumext_labelwidth_#1_dim } { l__enumext_label_#1_tl }
777 }
778 \cs_generate_variant:Nn \__enumext_widest_from:nNNn { nccn }

```

(End of definition for `__enumext_widest_from:nNNn`.)

Now define and set `start*`, `start` and `widest` keys for `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```

779 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
780 {
781   \keys_define:nn { enumext / #1 }
782   {
783     start* .code:n = {
784       \__enumext_start_from:ccn
785       { l__enumext_label_#2_tl }
786       { l__enumext_start_#2_int } {##1}
787     },
788     start* .value_required:n = true,
789     start .code:n = {
790       \__enumext_start_from:cce
791       { l__enumext_label_#2_tl }
792       { l__enumext_start_#2_int } { \int_eval:n {##1} }
793     },
794     start .initial:n = 1,
795     start .value_required:n = true,
796     widest .code:n = {
797       \__enumext_widest_from:nccn {#2}
798       { l__enumext_label_#2_tl }
799       { l__enumext_labelwidth_#2_dim } {##1}
800     },
801     widest .value_required:n = true,
802   }
803 }
804 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `start`, `start*`, and `widest`.)

12.15 Setting keys for vertical spaces

Define and set `topsep`, `partopsep`, `parsep`, `itemsep`, `noitemsep` and `nosep` keys for `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```

805 \cs_set_protected:Npn \__enumext_tmp:nnnnnn #1 #2 #3 #4 #5 #6
806 {
807   \keys_define:nn { enumext / #1 }
808   {
809     topsep .skip_set:c = { l__enumext_topsep_#2_skip },
810     topsep .initial:n = {#3},
811     topsep .value_required:n = true,
812     partopsep .skip_set:c = { l__enumext_partopsep_#2_skip },
813     partopsep .initial:n = {#4},
814     partopsep .value_required:n = true,
815     parsep .skip_set:c = { l__enumext_parsep_#2_skip },
816     parsep .initial:n = {#5},
817     parsep .value_required:n = true,

```

```

818     itemsep .skip_set:c = { l__enumext_itemsep_#2_skip },
819     itemsep .initial:n = {#6},
820     itemsep .value_required:n = true,
821     noitemsep .meta:n = { itemsep = 0pt, parsep = 0pt },
822     noitemsep .value_forbidden:n = true,
823     nosepe .meta:n = {
824         itemsep = 0pt, parsep= 0pt,
825         topsep = 0pt, partopsep = 0pt,
826     },
827     nosepe .value_forbidden:n = true,
828 }
829 }

```

Now we set the values based on standard `article` class in 10pt.

```

830 \__enumext_tmp:nnnnnn { level-1 } { i } { 8.0pt plus 2.0pt minus 4.0pt }
831 { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
832 { 4.0pt plus 2.0pt minus 1.0pt }
833 \__enumext_tmp:nnnnnn { level-2 } { ii } { 4.0pt plus 2.0pt minus 1.0pt }
834 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
835 { 2.0pt plus 1.0pt minus 1.0pt }
836 \__enumext_tmp:nnnnnn { level-3 } { iii } { 2.0pt plus 1.0pt minus 1.0pt }
837 { 1.0pt minus 1.0pt } { 0pt } { 2.0pt plus 1.0pt minus 1.0pt }
838 \__enumext_tmp:nnnnnn { level-4 } { iv } { 2.0pt plus 1.0pt minus 1.0pt }
839 { 1.0pt minus 1.0pt } { 0pt } { 2.0pt plus 1.0pt minus 1.0pt }
840 \__enumext_tmp:nnnnnn { keyans } { v } { 4.0pt plus 2.0pt minus 1.0pt }
841 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
842 { 2.0pt plus 1.0pt minus 1.0pt }
843 \__enumext_tmp:nnnnnn { enumext* } { vii } { 8.0pt plus 2.0pt minus 4.0pt }
844 { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
845 { 4.0pt plus 2.0pt minus 1.0pt }
846 \__enumext_tmp:nnnnnn { keyans* } { viii } { 4.0pt plus 2.0pt minus 1.0pt }
847 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
848 { 2.0pt plus 1.0pt minus 1.0pt }

```

(End of definition for `topsep` and others.)

12.16 Setting base-fix key

When nesting starting right after `\item` (without material between them) there is a problem with the alignment of the baseline between the two environments. One way to get around this problem is to place `\mode_leave_vertical:` and then apply `\vspace{-\baselineskip}` and set `topsep=0pt` for the “first level” of the nested `enumext` or `enumext*` environments.

```

base-fix We define the key base-fix only for the “first level” of enumext and enumext*.
\__enumext_nested_base_line_fix:
849 \cs_set_protected:Npn \__enumext_tmp:n #1
850 {
851     \keys_define:nn { enumext / #1 }
852     {
853         base-fix .bool_set:N = \l__enumext_base_line_fix_bool,
854         base-fix .initial:n = false,
855         base-fix .value_forbidden:n = true,
856     }
857 }
858 \clist_map_inline:nn { level-1, enumext* } { \__enumext_tmp:n {#1} }

```

The function `__enumext_nested_base_line_fix:` will be in charge of applying the baseline correction and adjusting the *(keys)*. This function is passed to the function `__enumext_parse_keys:n` in the `enumext` environment definition (§12.38) and to the function `__enumext_parse_keys_vii:n` in the `enumext*` environment definition (§12.43)

🔗 This key is enabled by default in the command `\printkeyans` (§12.46).

```

859 \cs_new_protected:Nn \__enumext_nested_base_line_fix:
860 {
861     \bool_lazy_and:nnT
862     { \bool_if_p:N \l__enumext_standar_first_bool }
863     { \bool_if_p:N \l__enumext_base_line_fix_bool }
864     {
865         \mode_leave_vertical:
866         \vspace { -\baselineskip }
867         \keys_set:nn { enumext / level-1 }
868         {
869             topsep = 0pt, above = 0pt, above* = 0pt,
870         }
871     }
872 }

```



```

871     }
872     \bool_lazy_and:nnT
873     { \bool_if_p:N \__enumext_starred_first_bool }
874     { \bool_if_p:N \__enumext_base_line_fix_bool }
875     {
876         \mode_leave_vertical:
877         \vspace { -\baselineskip }
878         \keys_set:nn { enumext / enumext* }
879         {
880             topsep = 0pt, above = 0pt, above* = 0pt,
881         }
882     }
883     \bool_set_false:N \__enumext_base_line_fix_bool
884 }

```

(End of definition for `base-fix` and `__enumext_nested_base_line_fix:.`)

12.17 Setting keys for horizontal spaces

Define and set `itemindent`, `rightmargin`, `listparindent`, `list-offset` and `list-indent` keys for `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```

885 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
886 {
887     \keys_define:nn { enumext / #1 }
888     {
889         itemindent .dim_set:c = { l__enumext_fake_item_indent_#2_dim },
890         itemindent .value_required:n = true,
891         rightmargin .dim_set:c = { l__enumext_rightmargin_#2_dim },
892         rightmargin .value_required:n = true,
893         listparindent .dim_set:c = { l__enumext_listparindent_#2_dim },
894         listparindent .value_required:n = true,
895         list-offset .dim_set:c = { l__enumext_listoffset_#2_dim },
896         list-offset .value_required:n = true,
897         list-indent .code:n =
898             \bool_set_true:c { l__enumext_leftmargin_tmp_#2_bool }
899             \dim_set:cn { l__enumext_leftmargin_tmp_#2_dim } {##1},
900         list-indent .value_required:n = true,
901     }
902 }
903 \clist_map_inline:nn
904 {
905     {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {keyans}{v}
906 }
907 { \__enumext_tmp:nn #1 }

```

(End of definition for `itemindent` and others.)

For `enumext*` and `keyans*` environments the situation is a bit different, the `list-indent` key behaves like the `list-offset` key.

```

908 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
909 {
910     \keys_define:nn { enumext / #1 }
911     {
912         itemindent .dim_set:c = { l__enumext_fake_item_indent_#2_dim },
913         itemindent .value_required:n = true,
914         rightmargin .dim_set:c = { l__enumext_rightmargin_#2_dim },
915         rightmargin .value_required:n = true,
916         listparindent .dim_set:c = { l__enumext_listparindent_#2_dim },
917         listparindent .value_required:n = true,
918         list-offset .dim_set:c = { l__enumext_listoffset_#2_dim },
919         list-offset .value_required:n = true,
920         list-indent .meta:n = { list-offset = ##1 },
921         list-indent .value_required:n = true,
922     }
923 }
924 \clist_map_inline:nn
925 {
926     {enumext*}{vii}, {keyans*}{viii}
927 }
928 { \__enumext_tmp:nn #1 }

```

12.17.1 Functions for setting the fake itemindent

The `itemindent` key does not set the value of `\itemindent`, it only sets the value of the *horizontal space* applied using `\skip_horizontal:N`. We will store this value in the variable and only apply it when it is greater than `\opt`. Here I will need to place `\mode_leave_vertical:` and the plain TeX macro `\ignorespaces` to avoid unwanted extra space when using the `itemindent` key.

```

929 \cs_set_protected:Nn \__enumext_fake_item:
930 {
931   \dim_compare:nNnT
932     { \dim_use:c { \l__enumext_fake_item_indent_ \l__enumext_level: _dim } }
933     >
934     { \c_zero_dim }
935   {
936     \tl_set:ce { \l__enumext_fake_item_indent_ \l__enumext_level: _tl }
937     {
938       \exp_not:N \mode_leave_vertical:
939       \exp_not:n { \skip_horizontal:n }
940       { \dim_use:c { \l__enumext_fake_item_indent_ \l__enumext_level: _dim } }
941       \ignorespaces
942     }
943   }
944 }
945 \cs_set_protected:Nn \__enumext_keyans_fake_item:
946 {
947   \dim_compare:nNnT
948     { \l__enumext_fake_item_indent_v_dim } > { \c_zero_dim }
949     {
950       \tl_set:Ne \l__enumext_fake_item_indent_v_tl
951       {
952         \exp_not:N \mode_leave_vertical:
953         \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_v_dim
954         \ignorespaces
955       }
956     }
957 }
958 \cs_set_protected:Nn \__enumext_fake_item_vii:
959 {
960   \dim_compare:nNnT
961     { \l__enumext_fake_item_indent_vii_dim } > { \c_zero_dim }
962     {
963       \tl_set:Ne \l__enumext_fake_item_indent_vii_tl
964       {
965         \exp_not:N \mode_leave_vertical:
966         \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_vii_dim
967         \ignorespaces
968       }
969     }
970 }
971 \cs_set_protected:Nn \__enumext_fake_item_viii:
972 {
973   \dim_compare:nNnT
974     { \l__enumext_fake_item_indent_viii_dim } > { \c_zero_dim }
975     {
976       \tl_set:Ne \l__enumext_fake_item_indent_viii_tl
977       {
978         \exp_not:N \mode_leave_vertical:
979         \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_viii_dim
980         \ignorespaces
981       }
982     }
983 }

```

(End of definition for `__enumext_fake_item:` and others.)

12.18 Setting show-length key

show-length

Define and set `show-length` key for `enumext`, `enumext*`, `keyans` and `keyans*` environments. The function sets the boolean variable `\l__enumext_show_length_X_bool` used in the definition of all environments to “true” and calls the function `__enumext_show_length:nnn` which prints all the values of the “vertical” and “horizontal” parameters calculated and used.

```

984 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
985 {

```

```

986     \keys_define:nn { enumext / #1 }
987     {
988         show-length .bool_set:c = { l__enumext_show_length_#2_bool },
989         show-length .initial:n = false,
990     }
991 }
992 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for show-length.)

12.19 Setting before, after and first keys

Define and set `before`, `before*`, `after` and `first` keys for `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```

993 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
994 {
995     \keys_define:nn { enumext / #1 }
996     {
997         before .tl_set:c = { l__enumext_before_no_starred_key_#2_tl },
998         before .value_required:n = true,
999         before* .tl_set:c = { l__enumext_before_starred_key_#2_tl },
1000         before* .value_required:n = true,
1001         after .tl_set:c = { l__enumext_after_stop_list_#2_tl },
1002         after .value_required:n = true,
1003         first .tl_set:c = { l__enumext_after_list_args_#2_tl },
1004         first .value_required:n = true,
1005     }
1006 }
1007 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for before and others.)

12.19.1 Functions for before, after and first keys in enumext

The function `__enumext_before_args_exec:` executes the `{⟨code⟩}` set by the `before*` key “before” the `enumext` environment is started. The `{⟨code⟩}` is executed “without” knowing any definition of the `{⟨arg two⟩}` of the list: `{⟨code⟩}\list{⟨arg one⟩}{⟨arg two⟩}`.

```

1008 \cs_new_protected:Nn \__enumext_before_args_exec:
1009 {
1010     \tl_use:c { l__enumext_before_starred_key_ \__enumext_level: _tl }
1011 }

```

The function `__enumext_before_keys_exec:` executes the `{⟨code⟩}` set by the `before` key “before” the `enumext` environment is started in *second argument* of the list. The `{⟨code⟩}` is executed “knowing” all definition and values provides by `⟨keys⟩: \list{⟨arg one⟩}{⟨arg two⟩}{⟨code⟩}`

```

1012 \cs_new_protected:Nn \__enumext_before_keys_exec:
1013 {
1014     \tl_use:c { l__enumext_before_no_starred_key_ \__enumext_level: _tl }
1015 }

```

The function `__enumext_after_stop_list:` executes the `{⟨code⟩}` set by the `after` key “after” the `enumext` environment has finished: `\endlist{⟨code⟩}`.

```

1016 \cs_new_protected:Nn \__enumext_after_stop_list:
1017 {
1018     \tl_use:c { l__enumext_after_stop_list_ \__enumext_level: _tl }
1019 }

```

The function `__enumext_after_args_exec:` executes the `{⟨code⟩}` set by the `first` key after the end of the second argument of the list defining the `enumext` environment, just before the first occurrence of `\item: \list{⟨arg one⟩}{⟨arg two⟩}{⟨code⟩}\item.`

```

1020 \cs_new_protected:Nn \__enumext_after_args_exec:
1021 {
1022     \tl_use:c { l__enumext_after_list_args_ \__enumext_level: _tl }
1023 }

```

(End of definition for __enumext_before_args_exec: and others.)

12.19.2 Functions for before, after and first keys in keyans

Same implementation as the one used in the [enumext](#) environment.

```

__enumext_before_args_exec_v:
__enumext_before_keys_exec_v:
__enumext_after_stop_list_v:
__enumext_after_args_exec_v:
1024 \cs_new_protected:Nn __enumext_before_args_exec_v:
1025 {
1026   \tl_use:N \l__enumext_before_starred_key_v_tl
1027 }
1028 \cs_new_protected:Nn __enumext_before_keys_exec_v:
1029 {
1030   \tl_use:N \l__enumext_before_no_starred_key_v_tl
1031 }
1032 \cs_new_protected:Nn __enumext_after_stop_list_v:
1033 {
1034   \tl_use:N \l__enumext_after_stop_list_v_tl
1035 }
1036 \cs_new_protected:Nn __enumext_after_args_exec_v:
1037 {
1038   \tl_use:N \l__enumext_after_list_args_v_tl
1039 }

```

(End of definition for `__enumext_before_args_exec_v:` and others.)

12.19.3 Functions for before, after and first keys in enumext* and keyans*

Same implementation as the one used in the [enumext](#) environment.

```

__enumext_before_args_exec_vii:
__enumext_before_keys_exec_vii
__enumext_after_stop_list_vii:
__enumext_after_args_exec_vii:
1040 \cs_new_protected:Nn __enumext_before_args_exec_vii:
1041 {
1042   \tl_use:N \l__enumext_before_starred_key_vii_tl
1043 }
1044 \cs_new_protected:Nn __enumext_before_args_exec_viii:
1045 {
1046   \tl_use:N \l__enumext_before_starred_key_viii_tl
1047 }
1048 \cs_new_protected:Nn __enumext_before_keys_exec_vii:
1049 {
1050   \tl_use:N \l__enumext_before_no_starred_key_vii_tl
1051 }
1052 \cs_new_protected:Nn __enumext_before_keys_exec_viii:
1053 {
1054   \tl_use:N \l__enumext_before_no_starred_key_viii_tl
1055 }
1056 \cs_new_protected:Nn __enumext_after_stop_list_vii:
1057 {
1058   \tl_use:N \l__enumext_after_stop_list_vii_tl
1059 }
1060 \cs_new_protected:Nn __enumext_after_stop_list_viii:
1061 {
1062   \tl_use:N \l__enumext_after_stop_list_viii_tl
1063 }
1064 \cs_new_protected:Nn __enumext_after_args_exec_vii:
1065 {
1066   \tl_use:N \l__enumext_after_list_args_vii_tl
1067 }
1068 \cs_new_protected:Nn __enumext_after_args_exec_viii:
1069 {
1070   \tl_use:N \l__enumext_after_list_args_viii_tl
1071 }

```

(End of definition for `__enumext_before_args_exec_vii:` and others.)

12.20 Setting keys for multicols and minipage

The default value of the `columns-sep` key is handled by the state of the boolean variable `\l__enumext_columns_sep_X_bool` which is handled in the internal definition of the [enumext](#) and [keyans](#) environments. Define and set `mini-env`, `mini-sep`, `columns-sep` and `columns` keys for [enumext](#), [enumext*](#), [keyans](#) and [keyans*](#) environments.

```

1072 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
1073 {
1074   \keys_define:nn { enumext / #1 }
1075   {
1076     mini-env .dim_set:c = { l__enumext_minipage_right_#2_dim },
1077     mini-env .value_required:n = true,
1078     mini-sep .dim_set:c = { l__enumext_minipage_hsep_#2_dim },

```

```

1079     mini-sep .initial:n = 0.3333em,
1080     mini-sep .value_required:n = true,
1081     columns-sep .dim_set:c = { l__enumext_columns_sep_#2_dim },
1082     columns-sep .value_required:n = true,
1083     columns .int_set:c = { l__enumext_columns_#2_int },
1084     columns .initial:n = 1,
1085     columns .value_required:n = true,
1086   }
1087 }
1088 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

For `enumext*` and `keyans*` environments the situation is a bit different, the command `\miniright` is not available, so we will add the keys `mini-right` and `mini-right*` to implement support for `minipage` environment.

```

1089 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
1090 {
1091   \keys_define:nn { enumext / #1 }
1092   {
1093     mini-right .tl_gset:c = { g__enumext_miniright_code_#2_tl },
1094     mini-right .value_required:n = true,
1095     mini-right* .code:n = {
1096       \bool_gset_true:c { g__enumext_minipage_center_#2_bool }
1097       \keys_set:nn { enumext / #1 } { mini-right = {##1} }
1098     },
1099     mini-right* .value_required:n = true,
1100   }
1101 }
1102 \clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }

```

(End of definition for `mini-env` and others.)

12.21 Adjustment of vertical spaces for multicols

When nesting a “list environment” inside the `multicols` environment, the values of the “vertical spaces” are lost, basically the `multicols` environment takes control over them. Graphically it can be seen like in the figure 7.




Figure 7: Representation of the vertical space in `multicols` for a nested level.

To keep the desired spaces *above* and *below* in the “list environment” (`\topsep` + `[\partopsep]`) it is necessary to “adjust” the spaces added by the `multicols` environment. The most appropriate option in this case is to use a “context sensitive” vertical space with `\addvspace`.

I should make it clear that the implementation here is a “bit questionable”. At first glance doing `\multicolsep=\topsep` seemed right, but the results were not always as expected. An almost *imperceptible* detail is that in some cases the `\itemsep` values of are “stretched”, possibly due to the use of `\raggedcolumns` and this affects the lower space when closing the environment, which is “smaller” than expected. My attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

12.21.1 Adjustment of vertical spaces for multicols in enumext

`__enumext_multi_set_vskip:` The function `__enumext_multi_set_vskip:` will take care of determining the “adjusted spaces” that we will apply “above” and “below” the `multicols` environment in `enumext`.

We will set the default values taking into account that \TeX is in *horizontal mode*, then we will make the settings for the *vertical mode* in which `\partopsep` comes into play.

Set the values of `\l__enumext_multicols_above_X_skip` and `\l__enumext_multicols_below_X_skip` equal to the value of `\topsep` in the *current level*.

```

1103 \cs_new_protected:Nn \__enumext_multi_set_vskip:
1104 {
1105   \skip_set:cn { l__enumext_multicols_above_ \__enumext_level: _skip }
1106   {
1107     \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
1108   }
1109   \skip_set:cn { l__enumext_multicols_below_ \__enumext_level: _skip }
1110   {
1111     \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
1112   }

```

```

1113   \__enumext_add_pre_parsep:
1114   }

```

(End of definition for __enumext_multi_set_vskip:.)

__enumext_add_pre_parsep: The function __enumext_add_pre_parsep: “adjusted” the value of \l__enumext_multicols_above_X_skip detecting the value of \parsep from the previous level. This is necessary since \parsep from the previous level affects the *vertical spaces*.

```

1115 \cs_new_protected:Nn \__enumext_add_pre_parsep:
1116 {
1117   \int_case:nn { \l__enumext_level_int }
1118   {
1119     { 2 }{
1120       \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip }
1121       {
1122         \skip_add:Nn \l__enumext_multicols_above_ii_skip
1123         {
1124           \l__enumext_parsep_i_skip
1125         }
1126       }
1127     }
1128     { 3 }{
1129       \skip_if_eq:nnF { \l__enumext_parsep_ii_skip } { \c_zero_skip }
1130       {
1131         \skip_add:Nn \l__enumext_multicols_above_iii_skip
1132         {
1133           \l__enumext_parsep_ii_skip
1134         }
1135       }
1136     }
1137     { 4 }{
1138       \skip_if_eq:nnF { \l__enumext_parsep_iii_skip } { \c_zero_skip }
1139       {
1140         \skip_add:Nn \l__enumext_multicols_above_iv_skip
1141         {
1142           \l__enumext_parsep_iii_skip
1143         }
1144       }
1145     }
1146   }
1147 }

```

(End of definition for __enumext_add_pre_parsep:.)

__enumext_multi_addvspace: The function __enumext_multi_addvspace: will apply the spaces set using \addvspace “above” the multicols environment in enumext, taking into account whether TeX is in *horizontal mode* or *vertical mode*.

```

1148 \cs_new_protected:Nn \__enumext_multi_addvspace:
1149 {
1150   \__enumext_multi_set_vskip:
1151   \mode_if_vertical:T
1152   {
1153     \skip_add:cn { \l__enumext_multicols_above_ \l__enumext_level: _skip }
1154     {
1155       \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1156     }
1157     \skip_add:cn { \l__enumext_multicols_below_ \l__enumext_level: _skip }
1158     {
1159       \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1160     }
1161   }
1162   \__enumext_unskip_unkern: % revisar
1163   \par\nopagebreak
1164   \addvspace{ \skip_use:c { \l__enumext_multicols_above_ \l__enumext_level: _skip } }
1165 }

```

(End of definition for __enumext_multi_addvspace:.)

12.21.2 Adjustment of vertical spaces for multicol in keyans

`__enumext_keyans_multi_set_vskip:`
`__enumext_keyans_multi_addvspace:`

The function `__enumext_keyans_multi_set_vskip:` will take care of determining the “adjusted spaces” that we will apply “above” and “below” the `multicol` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

```

1166 \cs_new_protected:Nn \__enumext_keyans_multi_set_vskip:
1167 {
1168   \skip_set:Nn \l__enumext_multicol_above_v_skip
1169   {
1170     \l__enumext_topsep_v_skip
1171   }
1172   \skip_set:Nn \l__enumext_multicol_below_v_skip
1173   {
1174     \l__enumext_topsep_v_skip
1175   }
1176 }
1177 \cs_new_protected:Nn \__enumext_keyans_multi_addvspace:
1178 {
1179   \__enumext_keyans_multi_set_vskip:
1180   \mode_if_vertical:T
1181   {
1182     \skip_add:Nn \l__enumext_multicol_above_v_skip
1183     {
1184       \skip_use:N \l__enumext_partopsep_v_skip
1185     }
1186     \skip_add:Nn \l__enumext_multicol_below_v_skip
1187     {
1188       \skip_use:N \l__enumext_partopsep_v_skip
1189     }
1190   }
1191   \__enumext_unskip_unkern:
1192   \par\nopagebreak
1193   \addvspace{ \l__enumext_multicol_above_v_skip }
1194 }

```

(End of definition for `__enumext_keyans_multi_set_vskip:` and `__enumext_keyans_multi_addvspace:`.)

12.22 Adjustment of vertical spaces for minipage

When nesting a “list environment” within the `minipage` environment, the values of the “vertical spaces” are lost. Graphically it can be seen like in the figure 8.



Figure 8: Representation of the `minipage` spacing adjustment for a nested level.

Since we want to keep the “left” and “right” environments “aligned on top”, preserving the `\baselineskip` and keep the desired “spaces” (`\topsep` + `[\partopsep]`) it is necessary to “adjust” the “vertical spaces” for `minipage` environments.

Here there are several complications that we must circumvent, the `minipage` environment eliminates the “top” spaces, the `multicol` environment can be nested in the `minipage` environment, the “top” and “bottom” spaces are affected when `topsep=0pt` and to this is added the `\partopsep` parameter that comes into action according to whether \TeX is in $\langle\text{horizontal mode}\rangle$ or $\langle\text{vertical mode}\rangle$. Depending on these cases, small adjustments must be made using `\vspace` and `\addvspace` to obtain the “desired vertical spacing”.

Again I must make clear that the implementation here is a “bit questionable”, but hunting the spaces (`glue`) produced by the `minipage` environment is quite complicated, even more if `multicol` is nested. The setting of the values was more “trial and error” (aprox to `\strutbox`), using the help of the `lua-visual-debug`[14] package, again my attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

12.22.1 Adjustment of vertical spaces for minipage in enumext

`__enumext_minipage_set_skip:`
`__enumext_minipage_add_space:`

The function `__enumext_minipage_set_skip:` will take care of determining the “adjust” spaces that we will apply “above” and “below” the `__enumext_mini_page` environment in `enumext`.

First we will set the value of `\l__enumext_minipage_right_skip` equal to `\topsep`, then we will see if \TeX is in $\langle\text{vertical mode}\rangle$ and we will add `\partopsep`, followed by that we set the value of `\l__enumext_minipage_after_skip`.

```

1195 \cs_new_protected:Nn \__enumext_minipage_set_skip:
1196 {

```

```

1197 \skip_set:Nn \l__enumext_minipage_right_skip
1198 {
1199   \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
1200 }
1201 \mode_if_vertical:T
1202 {
1203   \skip_add:Nn \l__enumext_minipage_right_skip
1204   {
1205     \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
1206   }
1207 }
1208 \skip_set_eq:NN \l__enumext_minipage_after_skip \l__enumext_minipage_right_skip

```

We will adjust the values `\l__enumext_multicols_above_X_skip` and `\l__enumext_multicols_below_X_skip` and call the function `__enumext_pre_itemsep_skip:`.

```

1209 \skip_set_eq:cN
1210 { l__enumext_multicols_above_ \__enumext_level: _skip } \l__enumext_minipage_right_skip
1211 \skip_set_eq:cN
1212 { l__enumext_multicols_below_ \__enumext_level: _skip } \l__enumext_minipage_right_skip
1213 \__enumext_pre_itemsep_skip:

```

If the environment `multicols` is active, we set `\topskip=0pt` and then we make `\multicolsep` have the same value as `\l__enumext_multicols_above_X_skip`.

```

1214 \int_compare:nNnT
1215 { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
1216 {
1217   \skip_zero:N \topskip
1218   \skip_set_eq:Nc \multicolsep { l__enumext_multicols_above_ \__enumext_level: _skip }
1219 }
1220 }

```

The function `__enumext_minipage_add_space:` will apply the spaces on the “left side” using `\addvspace` “above” the `__enumext_mini_page` environment, taking into account whether T_EX is in *horizontal mode* or *vertical mode*. Here we use the plain T_EX macro `\nointerlineskip` to prevent baseline “glue” being added between the next pair of boxes in a *vertical list*. For the latter we will make some adjustments since the `\partopsep` parameter comes into play and this affects the *vertical spacing*.

```

1221 \cs_new_protected:Nn \__enumext_minipage_add_space:
1222 {
1223   \__enumext_minipage_set_skip:
1224   \__enumext_unskip_unkern:
1225   \mode_if_vertical:TF
1226   {
1227     \nopagebreak\nointerlineskip\noindent
1228   }
1229   {
1230     \par\nopagebreak\nointerlineskip\noindent
1231     \skip_zero:c { l__enumext_partopsep_ \__enumext_level: _skip }
1232   }
1233   \int_compare:nNnTF
1234   { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
1235   {
1236     \addvspace{ 0.445\box_ht:N \strutbox }
1237   }
1238   {
1239     \addvspace{ 0.250\box_ht:N \strutbox }
1240   }
1241 }

```

(End of definition for `__enumext_minipage_set_skip:` and `__enumext_minipage_add_space:`)

`__enumext_pre_itemsep_skip:`

The function `__enumext_pre_itemsep_skip:` will adjust the spaces below the environment `minipage` and the environment `multicols` if it is nested in it, taking into account the value of `\itemsep` from the previous level.

```

1242 \cs_new_protected:Nn \__enumext_pre_itemsep_skip:
1243 {
1244   \int_case:nn { \l__enumext_level_int }
1245   {
1246     { 2 }{
1247       \skip_if_eq:nnTF
1248       { \l__enumext_itemsep_i_skip } { \l__enumext_minipage_after_skip }
1249       {
1250         \skip_set:Nn \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1251       }
1252     }
1253   }

```

```

1251         \skip_set:Nn \l__enumext_multicols_below_ii_skip { 0.350\box_ht:N \strutbox }
1252     }
1253     {
1254         \dim_compare:nNnT
1255         { \l__enumext_itemsep_i_skip } < { \l__enumext_minipage_after_skip }
1256         {
1257             \skip_sub:Nn
1258             \l__enumext_minipage_after_skip { \l__enumext_itemsep_i_skip }
1259             \skip_sub:Nn
1260             \l__enumext_multicols_below_ii_skip { \l__enumext_itemsep_i_skip }
1261             \skip_add:Nn
1262             \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1263             \skip_add:Nn
1264             \l__enumext_multicols_below_ii_skip { 0.350\box_ht:N \strutbox }
1265         }
1266         \dim_compare:nNnT
1267         { \l__enumext_itemsep_i_skip } > { \l__enumext_minipage_after_skip }
1268         {
1269             \skip_set:Nn \l_tmpa_skip
1270             {
1271                 \l__enumext_itemsep_i_skip - \l__enumext_minipage_after_skip
1272             }
1273             \skip_sub:Nn
1274             \l__enumext_minipage_after_skip { \l__enumext_itemsep_i_skip }
1275             \skip_sub:Nn
1276             \l__enumext_multicols_below_ii_skip { \l__enumext_itemsep_i_skip }
1277             \skip_add:Nn
1278             \l__enumext_minipage_after_skip
1279             { 0.150\box_ht:N \strutbox + \l_tmpa_skip }
1280             \skip_add:Nn
1281             \l__enumext_multicols_below_ii_skip
1282             { 0.350\box_ht:N \strutbox + \l_tmpa_skip }
1283         }
1284     }
1285 }
1286 { 3 }{
1287     \skip_if_eq:nNnTF
1288     { \l__enumext_itemsep_ii_skip } { \c_zero_skip }
1289     {
1290         \skip_set:Nn \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1291         \skip_set:Nn \l__enumext_multicols_below_iii_skip { 0.350\box_ht:N \strutbox }
1292     }
1293     {
1294         \dim_compare:nNnT
1295         { \l__enumext_itemsep_ii_skip } < { \l__enumext_minipage_after_skip }
1296         {
1297             \skip_sub:Nn
1298             \l__enumext_minipage_after_skip { \l__enumext_itemsep_ii_skip }
1299             \skip_sub:Nn
1300             \l__enumext_multicols_below_iii_skip { \l__enumext_itemsep_ii_skip }
1301             \skip_add:Nn
1302             \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1303             \skip_add:Nn
1304             \l__enumext_multicols_below_iii_skip { 0.350\box_ht:N \strutbox }
1305         }
1306         \dim_compare:nNnT
1307         { \l__enumext_itemsep_ii_skip } > { \l__enumext_minipage_after_skip }
1308         {
1309             \skip_set:Nn \l_tmpa_skip
1310             {
1311                 \l__enumext_itemsep_ii_skip - \l__enumext_minipage_after_skip
1312             }
1313             \skip_sub:Nn
1314             \l__enumext_minipage_after_skip { \l__enumext_itemsep_ii_skip }
1315             \skip_sub:Nn
1316             \l__enumext_multicols_below_iii_skip { \l__enumext_itemsep_ii_skip }
1317             \skip_add:Nn
1318             \l__enumext_minipage_after_skip
1319             { 0.150\box_ht:N \strutbox + \l_tmpa_skip }
1320             \skip_add:Nn
1321             \l__enumext_multicols_below_iii_skip

```

```

1322         { 0.350\box_ht:N \strutbox + \l_tmpa_skip }
1323     }
1324 }
1325 }
1326 { 4 }{
1327     \skip_if_eq:nnTF { \l__enumext_itemsep_iii_skip } { \c_zero_skip }
1328     {
1329         \skip_set:Nn \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1330         \skip_set:Nn \l__enumext_multicols_below_iv_skip { 0.350\box_ht:N \strutbox }
1331     }
1332     {
1333         \dim_compare:nNnT
1334         { \l__enumext_itemsep_iii_skip } < { \l__enumext_minipage_after_skip }
1335         {
1336             \skip_sub:Nn
1337             \l__enumext_minipage_after_skip { \l__enumext_itemsep_iii_skip }
1338             \skip_sub:Nn
1339             \l__enumext_multicols_below_iv_skip { \l__enumext_itemsep_iii_skip }
1340             \skip_add:Nn
1341             \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1342             \skip_add:Nn
1343             \l__enumext_multicols_below_iv_skip { 0.350\box_ht:N \strutbox }
1344         }
1345         \dim_compare:nNnT
1346         { \l__enumext_itemsep_iii_skip } > { \l__enumext_minipage_after_skip }
1347         {
1348             \skip_set:Nn \l_tmpa_skip
1349             {
1350                 \l__enumext_itemsep_iii_skip - \l__enumext_minipage_after_skip
1351             }
1352             \skip_sub:Nn
1353             \l__enumext_minipage_after_skip { \l__enumext_itemsep_iii_skip }
1354             \skip_sub:Nn
1355             \l__enumext_multicols_below_iv_skip { \l__enumext_itemsep_iii_skip }
1356             \skip_add:Nn
1357             \l__enumext_minipage_after_skip
1358             { 0.150\box_ht:N \strutbox + \l_tmpa_skip }
1359             \skip_add:Nn
1360             \l__enumext_multicols_below_iv_skip
1361             { 0.350\box_ht:N \strutbox + \l_tmpa_skip }
1362         }
1363     }
1364 }
1365 }
1366 }

```

(End of definition for `\l__enumext_pre_itemsep_skip:`)

12.22.2 Adjustment of vertical spaces for minipage in keyans

```

\l__enumext_keyans_minipage_set_skip:
\l__enumext_keyans_minipage_add_space:
\l__enumext_keyans_pre_itemsep_skip:

```

The function `\l__enumext_keyans_mini_set_vskip:` will take care of determining the “adjusted” spaces that we will apply “*above*” and “*below*” the `\l__enumext_mini_page` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

```

1367 \cs_new_protected:Nn \l__enumext_keyans_minipage_set_skip:
1368 {
1369     \skip_zero:N \l__enumext_minipage_after_skip
1370     \skip_zero:N \l__enumext_minipage_left_skip
1371     \skip_zero:N \l__enumext_minipage_right_skip
1372     \skip_set:Nn \l__enumext_minipage_right_skip
1373     {
1374         \l__enumext_topsep_v_skip
1375     }
1376     \mode_if_vertical:T
1377     {
1378         \skip_add:Nn \l__enumext_minipage_right_skip
1379         {
1380             \l__enumext_partopsep_v_skip
1381         }
1382     }
1383     \skip_set_eq:NN \l__enumext_minipage_after_skip \l__enumext_minipage_right_skip
1384     \skip_set_eq:NN \l__enumext_multicols_above_v_skip \l__enumext_minipage_right_skip
1385     \skip_set_eq:NN \l__enumext_multicols_below_v_skip \l__enumext_minipage_right_skip

```

```

1386   \__enumext_keyans_pre_itemsep_skip:
1387   \int_compare:nNnT { \l__enumext_columns_v_int } > { 1 }
1388   {
1389     \skip_zero:N \topskip
1390     \skip_set_eq:NN \multicolsep \l__enumext_minipage_right_skip
1391   }
1392 }
1393 \cs_new_protected:Nn \__enumext_keyans_minipage_add_space:
1394 {
1395   \__enumext_keyans_minipage_set_skip:
1396   \__enumext_unskip_unkern:
1397   \mode_if_vertical:TF
1398   {
1399     \nopagebreak\nointerlineskip\noindent
1400   }
1401   {
1402     \par\nopagebreak\nointerlineskip\noindent
1403     \skip_zero:N \l__enumext_partopsep_v_skip
1404   }
1405   \int_compare:nNnTF { \l__enumext_columns_v_int } > { 1 }
1406   {
1407     \addvspace{ 0.445\box_ht:N \strutbox }
1408   }
1409   {
1410     \addvspace{ 0.250\box_ht:N \strutbox }
1411   }
1412 }
1413 \cs_new_protected:Nn \__enumext_keyans_pre_itemsep_skip:
1414 {
1415   \skip_if_eq:nnTF
1416   { \l__enumext_itemsep_i_skip } { \l__enumext_minipage_after_skip }
1417   {
1418     \skip_set:Nn \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1419     \skip_set:Nn \l__enumext_multicols_below_v_skip { 0.350\box_ht:N \strutbox }
1420   }
1421   {
1422     \dim_compare:nNnT
1423     { \l__enumext_itemsep_i_skip } < { \l__enumext_minipage_after_skip }
1424     {
1425       \skip_sub:Nn \l__enumext_minipage_after_skip { \l__enumext_itemsep_i_skip }
1426       \skip_sub:Nn \l__enumext_multicols_below_v_skip { \l__enumext_itemsep_i_skip }
1427       \skip_add:Nn \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
1428       \skip_add:Nn \l__enumext_multicols_below_v_skip { 0.350\box_ht:N \strutbox }
1429     }
1430     \dim_compare:nNnT
1431     { \l__enumext_itemsep_i_skip } > { \l__enumext_minipage_after_skip }
1432     {
1433       \skip_set:Nn \l_tmpa_skip
1434       {
1435         \l__enumext_itemsep_i_skip - \l__enumext_minipage_after_skip
1436       }
1437       \skip_sub:Nn \l__enumext_minipage_after_skip { \l__enumext_itemsep_i_skip }
1438       \skip_sub:Nn \l__enumext_multicols_below_v_skip { \l__enumext_itemsep_i_skip }
1439       \skip_add:Nn \l__enumext_minipage_after_skip
1440       { 0.150\box_ht:N \strutbox + \l_tmpa_skip }
1441       \skip_add:Nn \l__enumext_multicols_below_v_skip
1442       { 0.350\box_ht:N \strutbox + \l_tmpa_skip }
1443     }
1444   }
1445 }

```

(End of definition for `__enumext_keyans_minipage_set_skip:`, `__enumext_keyans_minipage_add_space:`, and `__enumext_keyans_pre_itemsep_skip:`.)

12.22.3 Adjustment of vertical spaces for minipage in enumext* and keyans*

`__enumext_mini_set_vskip_vii:`
`__enumext_mini_set_vskip_viii:`

The functions `__enumext_mini_set_vskip_vii:` and `__enumext_mini_set_vskip_viii:` will take care of determining the “adjusted” spaces that we will apply “above” and “below” the `__enumext_mini_page` environment in `enumext*` and `keyans*`.

```

1446 \cs_new_protected:Nn \__enumext_mini_set_vskip_vii:
1447 {
1448   \skip_zero_new:N \l__enumext_minipage_left_skip

```

```

1449 \skip_gzero_new:N \g__enumext_minipage_right_skip
1450 \skip_gzero_new:N \g__enumext_minipage_after_skip
1451 \skip_if_eq:nnTF { \l__enumext_topsep_vii_skip } { \c_zero_skip }
1452 {
1453   \skip_set:Nn \l__enumext_minipage_left_skip { 0.5\box_dp:N \strutbox }
1454   \skip_gset:Nn \g__enumext_minipage_right_skip { 0.325\box_dp:N \strutbox }
1455 }
1456 {
1457   \skip_set:Nn \l__enumext_minipage_left_skip { 0.5875\box_dp:N \strutbox }
1458   \skip_gset:Nn \g__enumext_minipage_right_skip
1459   {
1460     \l__enumext_topsep_vii_skip
1461   }
1462   \skip_gset:Nn \g__enumext_minipage_after_skip
1463   {
1464     0.325\box_dp:N \strutbox + \l__enumext_topsep_vii_skip
1465   }
1466 }
1467 }
1468 \cs_new_protected:Nn \__enumext_mini_set_vskip_viii:
1469 {
1470   \skip_zero_new:N \l__enumext_minipage_after_skip
1471   \skip_zero_new:N \l__enumext_minipage_left_skip
1472   \skip_zero_new:N \l__enumext_minipage_right_skip
1473   \skip_if_eq:nnTF { \l__enumext_topsep_viii_skip } { \c_zero_skip }
1474   {
1475     \skip_set:Nn \l__enumext_minipage_left_skip
1476     {
1477       0.5\box_dp:N \strutbox
1478     }
1479     \skip_set:Nn \l__enumext_minipage_right_skip
1480     {
1481       \l__enumext_partopsep_viii_skip
1482     }
1483     \skip_set:Nn \l__enumext_minipage_after_skip
1484     {
1485       1.6\box_dp:N \strutbox
1486     }
1487   }
1488   {
1489     \skip_set:Nn \l__enumext_minipage_left_skip
1490     {
1491       0.5875\box_dp:N \strutbox
1492     }
1493     \skip_set:Nn \l__enumext_minipage_right_skip
1494     {
1495       \l__enumext_topsep_viii_skip
1496     }
1497     \skip_set:Nn \l__enumext_minipage_after_skip
1498     {
1499       0.325\box_dp:N \strutbox + \l__enumext_topsep_viii_skip
1500     }
1501   }
1502 }

```

(End of definition for __enumext_mini_set_vskip_vii: and __enumext_mini_set_vskip_viii:.)

__enumext_mini_addvspace_vii:
 __enumext_mini_addvspace_viii:

The functions __enumext_mini_addvspace_vii: and __enumext_mini_addvspace_viii: will apply the vertical space “only above” the __enumext_mini_page environment on the *left side* when the mini-right key is active in the *enumext** and *keyans** environments.

Here we will NOT take into account whether TeX is in *horizontal mode* or *vertical mode*, since \partopsep is equal to 0pt in both environments.

```

1503 \cs_new_protected:Nn \__enumext_mini_addvspace_vii:
1504 {
1505   \__enumext_mini_set_vskip_vii:
1506   \par\nopagebreak
1507   \addvspace { \l__enumext_minipage_left_skip }
1508 }
1509 \cs_new_protected:Nn \__enumext_mini_addvspace_viii:
1510 {
1511   \__enumext_mini_set_vskip_viii:

```



```

1512     \par\nopagebreak
1513     \addvspace { \l__enumext_minipage_left_skip }
1514 }

```

(End of definition for __enumext_mini_addvspace_vii: and __enumext_mini_addvspace_viii:.)

12.22.4 The command \miniright

The command `\miniright` will close the `__enumext_mini_page` environment on the “left side”, open the `__enumext_mini_page` environment on the “right side” adding the *adjusted vertical space*. By default we will add `\centering` when starting the “right side” environment. The *starred argument* ‘*’ inhibits the use of `\centering` command i.e. the usual L^AT_EX justification is maintained in the `__enumext_mini_page` on the “right side”.

`\miniright`

First we will perform some checks to prevent the command from being executed outside the `enumext` environment or somewhere inappropriate then we will call the internal functions to execute it in the `enumext` and `keyans` environments.

```

1515 \NewDocumentCommand \miniright { s }
1516 {
1517     \int_compare:nNt { \l__enumext_keyans_pic_level_int } = { 1 }
1518     {
1519         \msg_error:nnn { enumext } { wrong-miniright-place }
1520     }
1521     % outside
1522     \bool_lazy_and:nnT
1523     { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
1524     { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
1525     {
1526         \msg_error:nnn { enumext } { wrong-miniright-place }
1527     }
1528     % starred env
1529     \bool_if:NT \l__enumext_starred_bool
1530     {
1531         \msg_error:nnn { enumext } { wrong-miniright-starred }
1532     }
1533     \int_compare:nNtF { \l__enumext_keyans_level_int } = { 1 }
1534     {
1535         \__enumext_keyans_mini_right_cmd:n {#1}
1536     }
1537     { \__enumext_mini_right_cmd:n {#1} }
1538 }

```

(End of definition for \miniright. This function is documented on page 10.)

`__enumext_mini_right_cmd:n`

The function `__enumext_mini_right_cmd:n` takes as argument the *starred* ‘*’ of the `\miniright` command in the `enumext` environment. We check if the `mini-env` key is active via the variable `\l__enumext_minipage_right_X_dim`, if so we close the `multicols` environment with the `__enumext_mini_page` environment on the “left side”, then we open the `__enumext_mini_page` environment on the “right side”, apply our adjusted “vertical spaces”, followed by adding the `\centering` command when the starred argument ‘*’ is not present and set zero `\g__enumext_minipage_stat_int`, otherwise we return an error.

```

1539 \cs_new_protected:Npn \__enumext_mini_right_cmd:n #1
1540 {
1541     \dim_compare:nNtF
1542     { \dim_use:c { \l__enumext_minipage_right_ \l__enumext_level: _dim } } > { \c_zero_dim }
1543     {
1544         \__enumext_multicols_stop:
1545         \int_compare:nNt
1546         { \int_use:c { \l__enumext_columns_ \l__enumext_level: _int } } = { 1 }
1547         {
1548             \par\addvspace{ \l__enumext_minipage_after_skip }
1549         }
1550         \end__enumext_mini_page
1551         \hfill
1552         \__enumext_mini_page{ \dim_use:c { \l__enumext_minipage_right_ \l__enumext_level: _dim } }
1553         \par\nointerlineskip
1554         \addvspace { \l__enumext_minipage_right_skip }
1555         \bool_if:nF {#1}
1556         {
1557             \centering
1558         }
1559         \int_gzero:N \g__enumext_minipage_stat_int

```

```

1560     }
1561     { \msg_error:nnn { enumext } { wrong-miniright-use } }
1562 % paranoia
1563 \RenewDocumentCommand \miniright { s }
1564 {
1565     \msg_error:nn { enumext } { many-miniright-used }
1566 }
1567 }

```

(End of definition for `__enumext_mini_right_cmd:n`.)

`__enumext_keyans_mini_right_cmd:n`

The function `__enumext_keyans_mini_right_cmd:n` takes as argument the starred `'*` of the `\miniright` command in the `keyans` environment. The implementation of this function is the same as that of the `__enumext_mini_right_cmd:n` function of the `enumext` environment.

```

1568 \cs_new_protected:Npn \__enumext_keyans_mini_right_cmd:n #1
1569 {
1570     \dim_compare:nNnTF { \__enumext_minipage_right_v_dim } > { \c_zero_dim }
1571     {
1572         \__enumext_keyans_multicols_stop:
1573         \int_compare:nNnT { \__enumext_columns_v_int } = { 1 }
1574         {
1575             \par\addvspace{ \__enumext_minipage_after_skip }
1576         }
1577         \end__enumext_mini_page
1578         \hfill
1579         \__enumext_mini_page{ \__enumext_minipage_right_v_dim }
1580         \par\nointerlineskip
1581         \addvspace { \__enumext_minipage_right_skip }
1582         \bool_if:nF {#1}
1583         {
1584             \centering
1585         }
1586         \int_gzero:N \g__enumext_minipage_stat_int
1587     }
1588     { \msg_error:nnn { enumext } { wrong-miniright-use } }
1589 % paranoia
1590 \RenewDocumentCommand \miniright { s }
1591 {
1592     \msg_error:nn { enumext } { many-miniright-used }
1593 }
1594 }

```

(End of definition for `__enumext_keyans_mini_right_cmd:n`.)

12.23 Setting above and below keys

While having controlled the *vertical spaces* within the `enumext` and `keyans` environments when using the `columns` or `mini-env` keys, sometimes the “vertical spaces above” or “vertical spaces below” the environments are not as expected and it is necessary to be able to apply a “fine correction” to these. As I have not been able to correct these *glitches*, the best option is to leave a couple of *keys* dedicated to this purpose, in this case it is best to use `\vspace` or `\vspace*` when convenient.

above

Define `above`, `above*`, `below` and `below*` keys for `enumext` and `keyans` environments.

above*

below

below*

```

1595 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
1596 {
1597     \keys_define:nn { enumext / #1 }
1598     {
1599         above .skip_set:c = { \__enumext_vspace_above_#2_skip },
1600         above .value_required:n = true,
1601         above* .code:n = \bool_set_true:c { \__enumext_vspace_a_star_#2_bool }
1602             \keys_set:nn { enumext / #1 } { above = {#1} },
1603         above* .value_required:n = true,
1604         below .skip_set:c = { \__enumext_vspace_below_#2_skip },
1605         below .value_required:n = true,
1606         below* .code:n = \bool_set_true:c { \__enumext_vspace_b_star_#2_bool }
1607             \keys_set:nn { enumext / #1 } { below = {#1} },
1608         below* .value_required:n = true,
1609     }
1610 }
1611 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `above` and others.)

12.23.1 Functions for above and below keys in enumext

`__enumext_vspace_above:` The function `__enumext_vspace_above:` apply the *vertical space above* the `enumext` environment set by the *above** and *above* keys.

```

1612 \cs_new_protected:Nn \__enumext_vspace_above:
1613 {
1614   \skip_if_eq:nnF
1615   { \skip_use:c { \__enumext_vspace_above_ \__enumext_level: _skip } } { \c_zero_skip }
1616   {
1617     \bool_if:cTF { \__enumext_vspace_a_star_ \__enumext_level: _bool }
1618     {
1619       \vspace*{ \skip_use:c { \__enumext_vspace_above_ \__enumext_level: _skip } }
1620     }
1621     {
1622       \vspace { \skip_use:c { \__enumext_vspace_above_ \__enumext_level: _skip } }
1623     }
1624   }
1625 }

```

(End of definition for `__enumext_vspace_above:`.)

`__enumext_vspace_below:` The function `__enumext_vspace_below:` apply the *vertical space below* the `enumext` environment set by the *below** and *below* keys.

```

1626 \cs_new_protected:Nn \__enumext_vspace_below:
1627 {
1628   \skip_if_eq:nnF
1629   { \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } } { \c_zero_skip }
1630   {
1631     \bool_if:cTF { \__enumext_vspace_b_star_ \__enumext_level: _bool }
1632     {
1633       \vspace*{ \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } }
1634     }
1635     {
1636       \vspace { \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } }
1637     }
1638   }
1639 }

```

(End of definition for `__enumext_vspace_below:`.)

12.23.2 Functions for above and below keys in keyans

`__enumext_vspace_above_v:` The function `__enumext_vspace_above_v:` apply the *vertical space above* the `keyans` environment set by the *above* and *above** keys.

```

1640 \cs_new_protected:Nn \__enumext_vspace_above_v:
1641 {
1642   \skip_if_eq:nnF { \l__enumext_vspace_above_v_skip } { \c_zero_skip }
1643   {
1644     \bool_if:NTF \l__enumext_vspace_a_star_v_bool
1645     {
1646       \vspace*{ \l__enumext_vspace_above_v_skip }
1647     }
1648     { \vspace { \l__enumext_vspace_above_v_skip } }
1649   }
1650 }

```

(End of definition for `__enumext_vspace_above_v:`.)

`__enumext_vspace_below_v:` The function `__enumext_vspace_below_v:` apply the *vertical space below* the `keyans` environment set by the *below** and *below* keys.

```

1651 \cs_new_protected:Nn \__enumext_vspace_below_v:
1652 {
1653   \skip_if_eq:nnF { \l__enumext_vspace_below_v_skip } { \c_zero_skip }
1654   {
1655     \bool_if:NTF \l__enumext_vspace_b_star_v_bool
1656     {
1657       \vspace*{ \l__enumext_vspace_below_v_skip }
1658     }
1659     { \vspace { \l__enumext_vspace_below_v_skip } }
1660   }
1661 }

```

(End of definition for `__enumext_vspace_below_v:`.)

12.23.3 Functions for above and below keys in enumext* keyans*

The functions `__enumext_vspace_above_vii:` and `__enumext_vspace_above_viii:` apply the *vertical space above* the `enumext*` and `keyans*` environments set by the `above` and `above*` keys.

```

1662 \cs_new_protected:Nn \__enumext_vspace_above_vii:
1663 {
1664   \skip_if_eq:nnF { \l__enumext_vspace_above_vii_skip } { \c_zero_skip }
1665   {
1666     \bool_if:NTF \l__enumext_vspace_a_star_vii_bool
1667     {
1668       \vspace*{ \l__enumext_vspace_above_vii_skip }
1669     }
1670     { \vspace { \l__enumext_vspace_above_vii_skip } }
1671   }
1672 }
1673 \cs_new_protected:Nn \__enumext_vspace_above_viii:
1674 {
1675   \skip_if_eq:nnF { \l__enumext_vspace_above_viii_skip } { \c_zero_skip }
1676   {
1677     \bool_if:NTF \l__enumext_vspace_a_star_viii_bool
1678     {
1679       \vspace*{ \l__enumext_vspace_above_viii_skip }
1680     }
1681     { \vspace { \l__enumext_vspace_above_viii_skip } }
1682   }
1683 }

```

(End of definition for `__enumext_vspace_above_vii:` and `__enumext_vspace_above_viii:`)

The functions `__enumext_vspace_below_vii:` and `__enumext_vspace_below_viii:` apply the *vertical space below* the `enumext*` and `keyans*` environments set by the `below` and `below` keys.

```

1684 \cs_new_protected:Nn \__enumext_vspace_below_vii:
1685 {
1686   \skip_if_eq:nnF { \l__enumext_vspace_below_vii_skip } { \c_zero_skip }
1687   {
1688     \bool_if:NTF \l__enumext_vspace_b_star_vii_bool
1689     {
1690       \vspace*{ \l__enumext_vspace_below_vii_skip }
1691     }
1692     { \vspace { \l__enumext_vspace_below_vii_skip } }
1693   }
1694 }
1695 \cs_new_protected:Nn \__enumext_vspace_below_viii:
1696 {
1697   \skip_if_eq:nnF { \l__enumext_vspace_below_viii_skip } { \c_zero_skip }
1698   {
1699     \bool_if:NTF \l__enumext_vspace_b_star_viii_bool
1700     {
1701       \vspace*{ \l__enumext_vspace_below_viii_skip }
1702     }
1703     { \vspace { \l__enumext_vspace_below_viii_skip } }
1704   }
1705 }

```

(End of definition for `__enumext_vspace_below_vii:` and `__enumext_vspace_below_viii:`)

12.24 Setting series, resume and resume* keys

The `series` key is responsible for the whole process of the `resume` and `resume*` keys. The idea behind this is to be able to absorb the `<keys>` passed to the optional argument of the “*first level*” of the environments `enumext` and `enumext*`, but, discarding some specific `<keys>`. This implementation is adapted directly from the code provided by Jonathan P. Spratte (@Skillmon) in `chat-Tex-SX`

We define the keys `series`, `resume` and `resume*` only for the “*first level*” of `enumext` and `enumext*`.

```

series
resume
resume*
1706 \cs_set_protected:Npn \__enumext_tmp:n #1
1707 {
1708   \keys_define:nn { enumext / #1 }
1709   {
1710     series .str_set:N = \l__enumext_series_str,
1711     series .value_required:n = true,
1712     resume .code:n = \__enumext_resume_series:n {##1},
1713     resume* .code:n = \__enumext_resume_starred:,

```

```

1714         resume* .value_forbidden:n = true,
1715     }
1716 }
1717 \clist_map_inline:nn { level-1, enumext* } { \__enumext_tmp:n {#1} }

```

(End of definition for `series`, `resume`, and `resume*`.)

12.24.1 Internal functions for series key

The function `__enumext_filter_series:n` will be in charge of filtering the *⟨keys⟩* we want to store where `{#1}` represents the optional value passed to the environment.

```

\__enumext_filter_series:n
  \__enumext_filter_series_key:n
  \__enumext_filter_series_pair:nn
1718 \cs_new:Npn \__enumext_filter_series:n #1
1719 {
1720     \use:e
1721     {
1722         \keyval_parse:NNn
1723         \__enumext_filter_series_key:n
1724         \__enumext_filter_series_pair:nn {#1}
1725     }
1726 }

```

The function `__enumext_filter_series_key:n` will be responsible for filtering the *⟨keys⟩* that are passed “without value” by excluding the `resume`, `resume*` and `base-fix` keys.

```

1727 \cs_new:Npn \__enumext_filter_series_key:n #1
1728 {
1729     \str_case:nnF {#1}
1730     {
1731         { resume } {} { resume* } {} { base-fix } {}
1732     }
1733     { , { \exp_not:n {#1} } }
1734 }

```

The function `__enumext_filter_series_pair:nn` will be responsible for filtering the *⟨keys⟩* that are passed “with value” by excluding the `series`, `resume`, `start`, `start*`, `save-ans` and `save-key` keys.

```

1735 \cs_new:Npn \__enumext_filter_series_pair:nn #1#2
1736 {
1737     \str_case:nnF {#1}
1738     {
1739         { series } {} { resume } {} { start } {}
1740         { start* } {} { save-ans } {} { save-key } {}
1741     }
1742     { , { \exp_not:n {#1} } } = { \exp_not:n {#2} } }
1743 }

```

(End of definition for `__enumext_filter_series:n`, `__enumext_filter_series_key:n`, and `__enumext_filter_series_pair:nn`.)

The function `__enumext_parse_series:n` will be responsible for storing the filtered *⟨keys⟩* in the global variable `\g__enumext_series_⟨series name⟩_tl` along with the creation of the integer variable `\g__enumext_series_⟨series name⟩_int` when the key is passed as an argument; otherwise, it will check the state of the boolean variable `\l__enumext_resume_active_bool` set by the keys `resume` and `resume*` and will call the function `__enumext_resume_last:n`.

- The value of boolean variable `\l__enumext_resume_active_bool` is set to true by the function `__enumext_resume_counter:n` which is used by the keys `resume` and `resume*`, in this case we must Make sure it is set to false so that it does not overwrite the default filtered *⟨keys⟩*. This function is passed to the function `__enumext_parse_keys:n` in the `enumext` environment definition (§12.38) and to the function `__enumext_parse_keys_vii:n` in the `enumext*` environment definition (§12.43).

```

1744 \cs_new_protected:Npn \__enumext_parse_series:n #1
1745 {
1746     \str_if_empty:NTF \l__enumext_series_str
1747     {
1748         \bool_if:NF \l__enumext_resume_active_bool
1749         {
1750             \__enumext_resume_last:n {#1}
1751         }
1752     }
1753     {
1754         \tl_gclear_new:c { g__enumext_series_ \l__enumext_series_str _tl }
1755         \tl_gset:ce { g__enumext_series_ \l__enumext_series_str _tl }
1756         { \__enumext_filter_series:n {#1} }
1757         \int_if_exist:cF { g__enumext_series_ \l__enumext_series_str _int }
1758         {

```

```

1759         \int_new:c { g__enumext_series_ \l__enumext_series_str _int }
1760     }
1761 }
1762 }

```

The function `__enumext_resume_last:n` will be in charge of saving the filtering (*keys*) when the *series* key is *not used* and will save them in the variable `\g__enumext_standar_series_tl` for the `enumext` environment and in the variable `\g__enumext_starred_series_tl` for the `enumext*` environment. Here we must use `\bool_lazy_all:nT` to make sure that the default values are not overwritten when the environment is nested and the *series* key is not being used.

```

1763 \cs_new_protected:Npn \__enumext_resume_last:n #1
1764 {
1765     \bool_if:NT \l__enumext_standar_first_bool
1766     {
1767         \tl_gclear:N \g__enumext_standar_series_tl
1768         \tl_gset:Ne \g__enumext_standar_series_tl { \__enumext_filter_series:n {#1} }
1769     }
1770     \bool_if:NT \l__enumext_starred_first_bool
1771     {
1772         \tl_gclear:N \g__enumext_starred_series_tl
1773         \tl_gset:Ne \g__enumext_starred_series_tl { \__enumext_filter_series:n {#1} }
1774     }
1775 }

```

(End of definition for `__enumext_parse_series:n` and `__enumext_resume_last:n`)

12.24.2 Internal function to save counter value

`__enumext_resume_save_counter:`

The `__enumext_resume_save_counter:` function will save the last counter value to `\g__enumext_series_⟨series name⟩_int` if the `series={⟨series name⟩}` key has been passed, to `\g__enumext_resume_⟨series name⟩_int` if it has passed the key `resume without value` and the key `series` is not active, in `\g__enumext_series_⟨series name⟩_int` if the key `resume={⟨series name⟩}` has been passed and in `\g__enumext_series_⟨store name⟩_int` if the key has been passed `save-ans={⟨store name⟩}`.

- The variables `\l__enumext_series_str` and `\l__enumext__resume_name_tl` contain the same `{⟨series name⟩}` but are executed at different moments, the integer variable with `\l__enumext_series_str` sets the value when execute `series={⟨series name⟩}` and the integer variable with `\l__enumext__resume_name_tl` sets the subsequent values when use `resume={⟨series name⟩}`. This function is passed to the `enumext` environment definition (§12.38) and the `enumext*` environment definition (§12.43).

```

1776 \cs_new_protected:Npn \__enumext_resume_save_counter:
1777 {
1778     \bool_if:NT \g__enumext_standar_bool
1779     {
1780         \tl_if_empty:NF \l__enumext_series_str
1781         {
1782             \int_gset_eq:cN
1783             { g__enumext_series_ \l__enumext_series_str _int } \value{enumXi}
1784         }
1785         \tl_if_empty:NTF \l__enumext_resume_name_tl
1786         {
1787             \str_if_empty:NT \l__enumext_series_str
1788             {
1789                 \int_gset_eq:NN \g__enumext_resume_int \value{enumXi}
1790             }
1791         }
1792         {
1793             \int_if_exist:cT { g__enumext_series_ \l__enumext_resume_name_tl _int }
1794             {
1795                 \int_gset_eq:cN
1796                 { g__enumext_series_ \l__enumext_resume_name_tl _int } \value{enumXi}
1797             }
1798         }
1799         \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl _int }
1800         {
1801             \int_gset_eq:cN
1802             { g__enumext_resume_ \l__enumext_store_name_tl _int } \value{enumXi}
1803         }
1804     }
1805     \bool_if:NT \g__enumext_starred_bool
1806     {
1807         \tl_if_empty:NF \l__enumext_series_str
1808         {

```

```

1809         \int_gset_eq:cN
1810         { g__enumext_series_ \l__enumext_series_str_int } \value{enumXvii}
1811     }
1812     \tl_if_empty:NTF \l__enumext_resume_name_tl
1813     {
1814         \str_if_empty:NT \l__enumext_series_str
1815         {
1816             \int_gset_eq:NN \g__enumext_resume_vii_int \value{enumXvii}
1817         }
1818     }
1819     {
1820         \int_if_exist:cT { g__enumext_series_ \l__enumext_resume_name_tl_int }
1821         {
1822             \int_gset_eq:cN
1823             { g__enumext_series_ \l__enumext_resume_name_tl_int } \value{enumXvii}
1824         }
1825     }
1826     \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl_int }
1827     {
1828         \int_gset_eq:cN
1829         { g__enumext_resume_ \l__enumext_store_name_tl_int } \value{enumXvii}
1830     }
1831 }
1832 }

```

(End of definition for __enumext_resume_save_counter:.)

12.24.3 Internal functions for resume key

__enumext_resume_series:n

The function __enumext_resume_series:n will handle the argument passed to the `resume` key in `enumext` and `enumext*` environments. If the key is passed *without value* the function __enumext_resume_counter: is executed which will set the counter according to the numbering of the last `enumext` or `enumext*` environments in which `series={⟨series name⟩}` key is not present, if the `save-ans` key is active it will set the counter according to the value of the integer variable created by that key, otherwise it will verify that the `\g__enumext_series_⟨series name⟩_tl` variable set by the `series` key exists, if so it will pass these keys to the *first level* of the environment, otherwise it will return an error.

```

1833 \cs_new_protected:Npn \__enumext_resume_series:n #1
1834 {
1835     \tl_if_empty:NTF {#1}
1836     {
1837         \__enumext_resume_counter:n { }
1838     }
1839     {
1840         \tl_if_exist:cTF { g__enumext_series_ \tl_to_str:n {#1} _tl }
1841         {
1842             \__enumext_resume_counter:n {#1}
1843             \bool_if:NT \g__enumext_standar_bool
1844             {
1845                 \keys_set:nv { enumext / level-1 }
1846                 { g__enumext_series_ \tl_to_str:n {#1} _tl }
1847             }
1848             \bool_if:NT \g__enumext_starred_bool
1849             {
1850                 \keys_set:nv { enumext / enumext* }
1851                 { g__enumext_series_ \tl_to_str:n {#1} _tl }
1852             }
1853         }
1854         {
1855             \bool_if:NT \g__enumext_standar_bool
1856             {
1857                 \msg_error:nnn { enumext } { unknown-series } {#1}
1858             }
1859             \bool_if:NT \g__enumext_starred_bool
1860             {
1861                 \msg_error:nnn { enumext } { unknown-series } {#1}
1862             }
1863         }
1864     }
1865 }

```

(End of definition for __enumext_resume_series:n)


```

\__enumext_resume_counter:n
\__enumext_resume_counter:
  \__enumext_resume_counter_series:
  \__enumext_resume_counter_save_ans:

```

The function `__enumext_resume_counter:n` will set the variable `\l__enumext_resume_active_bool` to true and pass the value of the key `resume` to the variable `\l__enumext_series_name_tl` which will contain the `{\series name}`. If the variable `\l__enumext_series_name_tl` is empty, that is, we are passing the key `resume` *without value*, we will execute the function `__enumext_resume_counter:`; otherwise, when we pass `resume={\series name}` we will execute the function `__enumext_resume_counter_series:`, finally we will execute the function `__enumext_resume_counter_save_ans:` which is associated with the key `save-ans`.

```

1866 \cs_new_protected:Npn \__enumext_resume_counter:n #1
1867 {
1868   \bool_set_true:N \l__enumext_resume_active_bool
1869   \tl_set:Nn \l__enumext_resume_name_tl {#1}
1870   \tl_if_empty:NTF \l__enumext_resume_name_tl
1871   {
1872     \__enumext_resume_counter:
1873   }
1874   {
1875     \__enumext_resume_counter_series:
1876   }
1877   \__enumext_resume_counter_save_ans:
1878 }

```

The `__enumext_resume_counter:` function is executed when the `resume` key is used *without value*, only the counters for the “*first level*” of the environments will be set.

```

1879 \cs_new_protected:Nn \__enumext_resume_counter:
1880 {
1881   \bool_if:NT \g__enumext_standar_bool
1882   {
1883     \int_gincr:N \g__enumext_resume_int
1884     \int_set_eq:NN \l__enumext_start_i_int \g__enumext_resume_int
1885   }
1886   \bool_if:NT \g__enumext_starred_bool
1887   {
1888     \int_gincr:N \g__enumext_resume_vii_int
1889     \int_set_eq:NN \l__enumext_start_vii_int \g__enumext_resume_vii_int
1890   }
1891 }

```

The function `__enumext_resume_counter_series:` will be executed when the `resume={\series name}` key is active, setting the counters for the “*first level*” of the environments according to the value of the integer variables created by the `series` key.

```

1892 \cs_new_protected:Nn \__enumext_resume_counter_series:
1893 {
1894   \bool_if:NT \g__enumext_standar_bool
1895   {
1896     \int_set:Nn \l__enumext_start_i_int
1897     {
1898       \int_use:c { g__enumext_series_ \l__enumext_resume_name_tl _int } + 1
1899     }
1900   }
1901   \bool_if:NT \g__enumext_starred_bool
1902   {
1903     \int_set:Nn \l__enumext_start_vii_int
1904     {
1905       \int_use:c { g__enumext_series_ \l__enumext_resume_name_tl _int } + 1
1906     }
1907   }
1908 }

```

The function `__enumext_resume_counter_save_ans:` will be executed when the `save-ans` key is active along with the `resume` key, setting the counters for the “*first level*” of the environments according to the value of the integer variables created by the `save-ans` key.

```

1909 \cs_new_protected:Nn \__enumext_resume_counter_save_ans:
1910 {
1911   \bool_lazy_and:nnT
1912   { \bool_if_p:N \l__enumext_standar_first_bool }
1913   { \bool_if_p:N \l__enumext_store_active_bool }
1914   {
1915     \int_set:Nn \l__enumext_start_i_int
1916     {
1917       \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int } + 1
1918     }

```

```

1919     }
1920     \bool_lazy_and:nnT
1921     { \bool_if_p:N \__enumext_starred_first_bool }
1922     { \bool_if_p:N \__enumext_store_active_bool }
1923     {
1924         \int_set:Nn \__enumext_start_vii_int
1925         {
1926             \int_use:c { g__enumext_resume_ \__enumext_store_name_tl _int } + 1
1927         }
1928     }
1929 }

```

(End of definition for `__enumext_resume_counter:n` and others.)

12.24.4 Internal function for resume* key

`__enumext_resume_starred:`

The function `__enumext_resume_starred:` will handle the `resume*` key in the `enumext` and `enumext*` environments. This function will execute the filtered `<keys>` in the last one and will continue with the numbering according to the last execution of the environment `enumext` or `enumext*` in which the keys `resume={<series name>}` or `series={<series name>}` were not active.

```

1930 \cs_new_protected:Nn \__enumext_resume_starred:
1931 {
1932     \bool_if:NT \g__enumext_standar_bool
1933     {
1934         \tl_if_empty:NF \g__enumext_standar_series_tl
1935         {
1936             \__enumext_resume_counter:n { }
1937             \keys_set:nV { enumext / level-1 } \g__enumext_standar_series_tl
1938         }
1939     }
1940     \bool_if:NT \g__enumext_starred_bool
1941     {
1942         \tl_if_empty:NF \g__enumext_starred_series_tl
1943         {
1944             \__enumext_resume_counter:n { }
1945             \keys_set:nV { enumext / enumext* } \g__enumext_starred_series_tl
1946         }
1947     }
1948 }

```

(End of definition for `__enumext_resume_starred:`.)

12.25 Setting save-ans, check-ans and no-store keys

The key `save-ans` is directly associated with the keys `check-ans`, `no-store`, `resume` and `resume*`, this will activate the entire “storage system” in the `enumext` package.

12.25.1 Setting save-ans key

`save-ans`

We define the keys `save-ans` only for the “first level” of `enumext` and `enumext*`.

```

1949 \cs_set_protected:Npn \__enumext_tmp:n #1
1950 {
1951     \keys_define:nn { enumext / #1 }
1952     {
1953         save-ans .code:n = \__enumext_storing_set:n {##1},
1954         save-ans .value_required:n = true,
1955     }
1956 }
1957 \clist_map_inline:nn { level-1, enumext* } { { \__enumext_tmp:n {#1} } }

```

(End of definition for `save-ans`.)

12.25.2 Internal functions for save-ans key

`__enumext_start_save_ans_msg:`

`__enumext_stop_save_ans_msg:`

The functions `__enumext_start_save_ans_msg:` and `__enumext_stop_save_ans_msg:` will display in the terminal and `.log` file the environment in which the `save-ans` key was executed along with the line at the beginning and end of it. The function `__enumext_start_save_ans_msg:` will be passed to `__enumext_storing_set:n` and the function `__enumext_stop_save_ans_msg:` will be passed to the function `__enumext_execute_after_env:`.

```

1958 \cs_new_protected:Nn \__enumext_start_save_ans_msg:
1959 {
1960     \msg_term:nnVV { enumext } { save-ans-log }
1961     \g__enumext_envir_name_tl \__enumext_store_name_tl
1962 }

```

```

1963 \cs_new_protected:Nn \__enumext_stop_save_ans_msg:
1964 {
1965     \msg_term:nnVV { enumext } { save-ans-log-hook }
1966     \g__enumext_envir_name_tl \g__enumext_store_name_tl
1967 }

```

(End of definition for __enumext_start_save_ans_msg: and __enumext_stop_save_ans_msg:.)

```

\__enumext_storing_set:n
\__enumext_storing_exec:

```

The function __enumext_storing_set:n first pass the value of the `save-ans` key to the variable \l__enumext_store_name_tl which will contain the “store name” of the *sequence* and *prop list* we will use. If \l__enumext_store_name_tl is *empty* we return an error message, otherwise will return the appropriate message __enumext_start_save_ans_msg: and proceed to execute the function __enumext_storing_exec: for `enumext` and `enumext*` environments.

```

1968 \cs_new_protected:Npn \__enumext_storing_set:n #1
1969 {
1970     \tl_set:Nx \l__enumext_store_name_tl {#1}
1971     \tl_if_empty:NTF \l__enumext_store_name_tl
1972     {
1973         \bool_lazy_or:nnT
1974         { \l__enumext_standar_first_bool } { \l__enumext_starred_first_bool }
1975         {
1976             \msg_error:nnV { enumext } { save-ans-empty } \g__enumext_envir_name_tl
1977         }
1978     }
1979     {
1980         \bool_lazy_or:nnT
1981         { \l__enumext_standar_first_bool } { \l__enumext_starred_first_bool }
1982         {
1983             \__enumext_start_save_ans_msg:
1984             \__enumext_storing_exec:
1985         }
1986     }
1987 }

```

The function __enumext_storing_exec: will set to true the variable \l__enumext_store_active_bool which activates the use of the `\anskey` command and the `keyans`, `keyans*` and `keyanspic` environments and will set to true the variable \l__enumext_check_answers_bool used for checking answers by the `check-ans` and `no-store` keys, copy {*store name*} into the global variable \g__enumext_store_name_tl and execute the function __enumext_anskey_env_make:V creating the environment `anskey*` (§12.30). The *prop list* \g__enumext_series_<store name>_prop and the *sequence* \g__enumext_series_<store name>_seq will be created globally to “store content” in case they do not exist together with the integer variable \g__enumext_series_<store name>_int used by the keys `resume` and `resume*`.

```

1988 \cs_new_protected:Nn \__enumext_storing_exec:
1989 {
1990     \bool_set_true:N \l__enumext_store_active_bool
1991     \bool_set_true:N \l__enumext_check_answers_bool
1992     \tl_gset:NV \g__enumext_store_name_tl \l__enumext_store_name_tl
1993     \__enumext_anskey_env_make:V \l__enumext_store_name_tl
1994     \prop_if_exist:cF { g__enumext_ \l__enumext_store_name_tl _prop }
1995     {
1996         \msg_log:nnV { enumext } { store-prop } \l__enumext_store_name_tl
1997         \prop_new:c { g__enumext_ \l__enumext_store_name_tl _prop }
1998     }
1999     \seq_if_exist:cF { g__enumext_ \l__enumext_store_name_tl _seq }
2000     {
2001         \msg_log:nnV { enumext } { store-seq } \l__enumext_store_name_tl
2002         \seq_new:c { g__enumext_ \l__enumext_store_name_tl _seq }
2003     }
2004     \int_if_exist:cF { g__enumext_resume_ \l__enumext_store_name_tl _int }
2005     {
2006         \msg_log:nnV { enumext } { store-int } \l__enumext_store_name_tl
2007         \int_new:c { g__enumext_resume_ \l__enumext_store_name_tl _int }
2008     }
2009 }

```

(End of definition for __enumext_storing_set:n and __enumext_storing_exec:.)

12.25.3 The check answer mechanism

The mechanism for checking that all questions are answered follows this logic:

If the line begins with `\item` or `\item*` and does NOT *open a nested environment*, each `\item` or `\item*` must contain a *single* execution of the `\anskey` command, i.e. the counter of the executions of the `\anskey` command must be equal to the counter associated with the sum of executions of `\item` and `\item*`.

If the line begins with `\item` or `\item*` and *opens a nested environment* each `\item` or `\item*` in the nested environment must have a *single* execution of the `\anskey` command and the counter associated to the sum of `\item` and `\item*` executions must decrementing by “one” to maintain equality.

In order for the mechanism for the check-answer to work (not counting `keyans`, `keyans*` and `keyanspic`) we need:

1. We must keep track of the total number of `\item` and `\item*` (enumerated) that appear within the environment including the nested levels.
2. We must keep track of the total number of `\item` and `\item*` (enumerated) that appear per level of nesting.
3. Keeping track of the number of times the environment nests.

The integer variable associated to the sum of each `\item` and `\item*` in the environment `\g__enumext_item_number_int` must match the integer variable `\g__enumext_item_anskey_int` associated to the execution of the command `\anskey`. We analyze the cases:

- a) If the list only has one level the number of `\item` + `\item*` = `\anskey`
- b) If the list has *nested levels*, for each level of nesting we need to decrementing by one (for the `\item` or `\item*` that opens the nest) so that the account remains the same.

With `keyans`, `keyans*` and `keyanspic` it is enough to increase in one the integer of `\anskey`. The integers created must be global if they are not lost in the interior levels of nesting and to execute the test we will use a “hook” function after closing the first level of the environment.

12.25.4 Setting check-ans and no-store keys

Now we define the keys `check-ans` and `no-store` for all levels of `enumext` and `enumext*` environments.

```

check-ans 2010 \cs_set_protected:Npn \__enumext_tmp:n #1
no-store 2011 {
2012   \keys_define:nn { enumext / #1 }
2013   {
2014     check-ans .bool_set:N = \__enumext_check_ans_key_bool,
2015     check-ans .initial:n = false,
2016     check-ans .value_required:n = true,
2017     no-store .code:n = {
2018       \bool_set_false:N \__enumext_check_answers_bool
2019       \bool_set_false:N \__enumext_check_ans_key_bool
2020     },
2021     no-store .value_forbidden:n = true,
2022   }
2023 }
2024 \clist_map_inline:nn
2025 {
2026   level-1, level-2, level-3, level-4, enumext*
2027 }
2028 { \__enumext_tmp:n {#1} }
```

(End of definition for `check-ans` and `no-store`.)

12.25.5 Set-up check answer mechanism

The function `__enumext_check_ans_active:` will first check the state of the variable `\l__enumext_store_name_tl`, that is, the `save-ans` key is active, if so it will check the state of the variable `\l__enumext_check_answers_bool` handled by the key `no-store` and will execute the function `__enumext_check_ans_level:` only if “true”, i.e. the key `no-store` is not active.

```

2029 \cs_new_protected:Nn \__enumext_check_ans_active:
2030 {
2031   \tl_if_empty:NF \l__enumext_store_name_tl
2032   {
2033     \bool_if:NT \l__enumext_check_answers_bool
2034     {
2035       \__enumext_check_ans_level:
2036     }
2037   }
2038 }
```

The function `__enumext_check_ans_level:` will decrement by “one” the value of the variable `\g__enumext_item_number_int` which keeps track of the executions of `\item` and `\item*` for each level of nesting of the environment `enumext`, taking into account whether it is nested within `enumext*` or the opposite and set `\l__enumext_item_number_bool` to “false”.

```

2039 \cs_new_protected:Nn \__enumext_check_ans_level:
2040 {
2041   \int_case:nn { \l__enumext_level_int }
2042   {
2043     { 1 }{
2044       \bool_lazy_all:nT
2045       {
2046         { \bool_if_p:N \g__enumext_starred_bool }
2047         { \int_compare_p:nNn { \l__enumext_level_h_int } = { 1 } }
2048       }
2049       {
2050         \int_gdecr:N \g__enumext_item_number_int
2051         \bool_set_false:N \l__enumext_item_number_bool
2052       }
2053     }
2054     { 2 }{
2055       \int_gdecr:N \g__enumext_item_number_int
2056       \bool_set_false:N \l__enumext_item_number_bool
2057     }
2058     { 3 }{
2059       \int_gdecr:N \g__enumext_item_number_int
2060       \bool_set_false:N \l__enumext_item_number_bool
2061     }
2062     { 4 }{
2063       \int_gdecr:N \g__enumext_item_number_int
2064       \bool_set_false:N \l__enumext_item_number_bool
2065     }
2066   }

```

We should only execute this if `enumext*` is nested in the first level of `enumext`, for the rest of the cases the value of `\g__enumext_item_number_int` is already decreased.

```

2067   \int_case:nn { \l__enumext_level_h_int }
2068   {
2069     { 1 }{
2070       \bool_lazy_all:nT
2071       {
2072         { \bool_if_p:N \g__enumext_standar_bool }
2073         { \int_compare_p:nNn { \l__enumext_level_int } = { 1 } }
2074       }
2075       {
2076         \int_gdecr:N \g__enumext_item_number_int
2077         \bool_set_false:N \l__enumext_item_number_bool
2078       }
2079     }
2080   }
2081 }

```

(End of definition for `__enumext_check_ans_active:` and `__enumext_check_ans_level:`.)

`__enumext_check_ans_key_hook:`

The function `__enumext_check_ans_key_hook:` will *export* the status of the local variable `\l__enumext_check_ans_key_bool` to the global variable `\g__enumext_check_ans_key_bool` only if the key `check-ans` is active.

```

2082 \cs_new_protected:Nn \__enumext_check_ans_key_hook:
2083 {
2084   \bool_lazy_and:nnT
2085   { \bool_if_p:N \l__enumext_check_ans_key_bool }
2086   { \bool_if_p:N \g__enumext_standar_bool }
2087   {
2088     \bool_gset_true:N \g__enumext_check_ans_key_bool
2089   }
2090   \bool_lazy_and:nnT
2091   { \bool_if_p:N \l__enumext_check_ans_key_bool }
2092   { \bool_if_p:N \g__enumext_starred_bool }
2093   {
2094     \bool_gset_true:N \g__enumext_check_ans_key_bool
2095   }
2096 }

```

(End of definition for `__enumext_check_ans_key_hook:`.)

`__enumext_item_answer_diff:` The function `__enumext_item_answer_diff:` will set the value of the variable `\g__enumext_item_answer_diff_int` which is used by the functions `__enumext_check_ans_show:` for the key `save-ans` and by the function `__enumext_check_ans_log:` by the internal “*check answer*” mechanism. This function will be passed to the function `__enumext_execute_after_env:`.

```
2097 \cs_new_protected:Nn \__enumext_item_answer_diff:
2098 {
2099     \int_gset:Nn \g__enumext_item_answer_diff_int
2100     {
2101         \int_sign:n { \g__enumext_item_number_int - \g__enumext_item_anskey_int }
2102     }
2103 }
```

(End of definition for `__enumext_item_answer_diff:`.)

`__enumext_check_ans_show:` The function `__enumext_check_ans_show:` will be executed within the function `__enumext_execute_after_env:` when the key `check-ans` is active, that is, when `\g__enumext_check_ans_key_bool` is “*true*” and will return the appropriate message according to the value of `\g__enumext_item_answer_diff_int` set by the function `__enumext_item_answer_diff:`.

```
2104 \cs_new_protected:Nn \__enumext_check_ans_show:
2105 {
2106     \int_case:nn { \g__enumext_item_answer_diff_int }
2107     {
2108         { -1 } { \__enumext_check_ans_msg_less: }
2109         { 0 } { \__enumext_check_ans_msg_same_ok: }
2110         { 1 } { \__enumext_check_ans_msg_greater: }
2111     }
2112 }
2113 \cs_new_protected:Nn \__enumext_check_ans_msg_less:
2114 {
2115     \msg_warning:nnee { enumext } { item-less-answer } { \g__enumext_store_name_tl }
2116     { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
2117 }
2118 \cs_new_protected:Nn \__enumext_check_ans_msg_same_ok:
2119 {
2120     \msg_term:nnee { enumext } { items-same-answer } { \g__enumext_store_name_tl }
2121     { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
2122 }
2123 \cs_new_protected:Nn \__enumext_check_ans_msg_greater:
2124 {
2125     \msg_warning:nnee { enumext } { item-greater-answer } { \g__enumext_store_name_tl }
2126     { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
2127 }
```

(End of definition for `__enumext_check_ans_show:` and others.)

`__enumext_check_ans_log:` The function `__enumext_check_ans_log:` will be executed within the function `__enumext_execute_after_env:` when the key `check-ans` is not active, that is, when `\g__enumext_check_ans_key_bool` is “*false*” and write in the log the appropriate message according to the value of `\g__enumext_item_answer_diff_int` set by the function `__enumext_item_answer_diff:`.

```
2128 \cs_new_protected:Nn \__enumext_check_ans_log:
2129 {
2130     \int_case:nn { \g__enumext_item_answer_diff_int }
2131     {
2132         { -1 } { \__enumext_check_ans_log_msg_less: }
2133         { 0 } { \__enumext_check_ans_log_msg_same_ok: }
2134         { 1 } { \__enumext_check_ans_log_msg_greater: }
2135     }
2136 }
2137 \cs_new_protected:Nn \__enumext_check_ans_log_msg_less:
2138 {
2139     \msg_log:nnee { enumext } { item-less-answer } { \g__enumext_store_name_tl }
2140     { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
2141 }
2142 \cs_new_protected:Nn \__enumext_check_ans_log_msg_same_ok:
2143 {
2144     \msg_log:nnee { enumext } { items-same-answer } { \g__enumext_store_name_tl }
2145     { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
2146 }
```

```

2147 \cs_new_protected:Nn \__enumext_check_ans_log_msg_greater:
2148 {
2149   \msg_log:nneee { enumext } { item-greater-answer } { \g__enumext_store_name_tl }
2150   { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
2151 }

```

(End of definition for `__enumext_check_ans_log:` and others.)

12.25.6 Check for `\item*` and `\anspic*` commands

`__enumext_check_starred_cmd:n`

The function `__enumext_check_starred_cmd:n` performs an extra check for the `keyans`, `keyans*` and `keyanspic` environments. Unlike the check executed by `check-ans key` this one is not controlled by any key, it is intended to prevent the forgetting of `\item*` or `\anspic*` in these environments.

```

2152 \cs_new_protected:Npn \__enumext_check_starred_cmd:n #1
2153 {
2154   \int_compare:nNnT
2155     { \g__enumext_check_starred_cmd_int } = { 0 }
2156     {
2157       \msg_warning:nnnV
2158         { enumext } { missing-starred }{ #1 } \l__enumext_check_start_line_env_tl
2159     }
2160   \int_compare:nNnT
2161     { \g__enumext_check_starred_cmd_int } > { 1 }
2162     {
2163       \msg_warning:nnnV
2164         { enumext } { many-starred }{ #1 } \l__enumext_check_start_line_env_tl
2165     }
2166   \int_gzero:N \g__enumext_check_starred_cmd_int
2167   \tl_clear:N \l__enumext_check_start_line_env_tl
2168 }

```

(End of definition for `__enumext_check_starred_cmd:n`.)

12.26 Keys and functions associated with storage

wrap-ans
wrap-opt
save-sep
mark-ans
mark-pos
show-ans
mark-ref
save-ref

We add the keys `wrap-ans`, `wrap-opt`, `save-sep`, `mark-ans`, `mark-pos`, `show-ans`, `show-pos`, `mark-ref` and `save-ref` related to the “storage system” and internal mechanism of “label and ref” only at the *first level* of `enumext` and `enumext*`.

```

2169 \cs_set_protected:Npn \__enumext_tmp:n #1
2170 {
2171   \keys_define:nn { enumext / #1 }
2172   {
2173     wrap-ans .cs_set_protected:Np = \__enumext_anskey_wrapper:n ##1,
2174     wrap-ans .initial:n =
2175       {
2176         \fbox{\parbox[t]{\dimeval{\itemwidth -2\fboxsep -2\fboxrule}}{##1}}
2177       },
2178     wrap-ans .value_required:n = true,
2179     wrap-opt .cs_set_protected:Np = \__enumext_keyans_wrapper_opt:n ##1,
2180     wrap-opt .initial:n = [{##1}],
2181     wrap-opt .value_required:n = true,
2182     save-sep .tl_set:N = \l__enumext_store_keyans_item_opt_sep_tl,
2183     save-sep .initial:n = {, ~ },
2184     save-sep .value_required:n = true,
2185     mark-ans .tl_set:N = \l__enumext_mark_answer_sym_tl,
2186     mark-ans .initial:n = \textasteriskcentered,
2187     mark-ans .value_required:n = true,
2188     mark-pos .choice:,
2189     mark-pos / left .code:n = \str_set:Nn \l__enumext_mark_position_str { l },
2190     mark-pos / right .code:n = \str_set:Nn \l__enumext_mark_position_str { r },
2191     mark-pos / unknown .code:n =
2192       \msg_error:nneee { enumext } { unknown-choice }
2193       { mark-pos } { left, ~ right } { \exp_not:n {##1} },
2194     mark-pos .initial:n = right,
2195     mark-pos .value_required:n = true,
2196     show-ans .bool_set:N = \l__enumext_show_answer_bool,
2197     show-ans .initial:n = false,
2198     show-ans .value_required:n = true,
2199     show-pos .bool_set:N = \l__enumext_show_position_bool,
2200     show-pos .initial:n = false,
2201     show-pos .value_required:n = true,
2202     mark-ref .tl_set:N = \l__enumext_mark_ref_sym_tl,

```



```

2203     mark-ref .initial:n = \textasteriskcentered,
2204     mark-ref .value_required:n = true,
2205     save-ref .bool_set:N = \l__enumext_store_ref_key_bool,
2206     save-ref .initial:n = false,
2207     save-ref .value_required:n = true,
2208   }
2209 }
2210 \clist_map_inline:nn { level-1, enumext* } { \l__enumext_tmp:n {#1} }

```

(End of definition for wrap-ans and others.)

mark-pos For the `keyans` and `keyans*` environments we will only add the keys `mark-pos`, `show-ans` and `show-pos`.

```

2211 \cs_set_protected:Npn \l__enumext_tmp:n #1
2212 {
2213   \keys_define:nn { enumext / #1 }
2214   {
2215     mark-pos .choice:,
2216     mark-pos / left .code:n = \str_set:Nn \l__enumext_mark_position_str { l },
2217     mark-pos / right .code:n = \str_set:Nn \l__enumext_mark_position_str { r },
2218     mark-pos .initial:n = right,
2219     mark-pos .value_required:n = true,
2220     show-ans .bool_set:N = \l__enumext_show_answer_bool,
2221     show-ans .initial:n = false,
2222     show-ans .value_required:n = true,
2223     show-pos .bool_set:N = \l__enumext_show_position_bool,
2224     show-pos .initial:n = false,
2225     show-pos .value_required:n = true,
2226   }
2227 }
2228 \clist_map_inline:nn { keyans, keyans* } { \l__enumext_tmp:n {#1} }

```

(End of definition for mark-pos, show-ans, and show-pos.)

12.26.1 Store optional arguments of the environments

The idea behind “storing” in the *sequence* is to have a copy of the structure of the environment in which the key `save-ans` is being executed so we must capture the optional arguments passed to the levels of the environment in which it is executed and “storing” them.

```

\__enumext_store_active_keys:n
\__enumext_store_active_keys_vii:n

```

The functions `__enumext_store_active_keys:n` and `__enumext_store_active_keys_vii:n` will be responsible for “storing” the *keys* filtered from the optional arguments of the environment in which the key `save-ans` is executed and the levels within this for the `enumext` and `enumext*` environments. We will execute this function only if the variable `\l__enumext_store_save_key_X_bool` is false, that is, the key `store-key` is not active, establishing the variable `\l__enumext_store_save_key_X_tl` with the filtered *keys*.

```

2229 \cs_new_protected:Npn \__enumext_store_active_keys:n #1
2230 {
2231   \bool_if:cF { \l__enumext_store_save_key_ \__enumext_level: _bool }
2232   {
2233     \tl_clear:c { \l__enumext_save_key_ \__enumext_level: _tl }
2234     \tl_set:ce
2235       { \l__enumext_store_save_key_ \__enumext_level: _tl }
2236       { \__enumext_filter_save_key:n {#1} }
2237   }
2238 }
2239 \cs_new_protected:Npn \__enumext_store_active_keys_vii:n #1
2240 {
2241   \bool_if:NF \l__enumext_store_save_key_vii_bool
2242   {
2243     \tl_clear:N \l__enumext_store_save_key_vii_tl
2244     \tl_set:Ne \l__enumext_store_save_key_vii_tl { \__enumext_filter_save_key:n {#1} }
2245   }
2246 }

```

(End of definition for `__enumext_store_active_keys:n` and `__enumext_store_active_keys_vii:n`.)

12.26.2 Setting save-key key

Since this list structure will be stored in the *sequence* established by the *save-ans* key when executing *\anskey*, we will not be able to modify it. The best thing here is to have a key that allows you to modify the optional argument of the list stored in the *sequence*.

save-key The values set by this key passed in the optional arguments of the *enumext* and *enumext** environments will override the values of the `\l__enumext_store_save_key_X_tl` variable set by the functions `__enumext_store_active_keys:n` and `__enumext_store_active_keys_vii:n`.

Define the key *save-key* for all levels of *enumext* and *enumext** environments.

```

2247 \cs_set_protected:Npn \__enumext_tmp:n #1
2248 {
2249   \keys_define:nn { enumext / enumext* }
2250   {
2251     save-key .code:n = \__enumext_parse_save_key_vii:n {##1},
2252     save-key .value_required:n = true,
2253   }
2254   \keys_define:nn { enumext / #1 }
2255   {
2256     save-key .code:n = \__enumext_parse_save_key:n {##1},
2257     save-key .value_required:n = true,
2258   }
2259 }
2260 \clist_map_inline:nn { level-1, level-2, level-3, level-4 } { \__enumext_tmp:n {#1} }

```

(End of definition for *save-key*.)

```

\__enumext_parse_save_key:n
\__enumext_parse_save_key_vii:n

```

The functions `__enumext_parse_save_key:n` and `__enumext_parse_save_key_vii:n` will be responsible for storing the filtered *keys* in the variable `\l__enumext_store_save_key_X_tl` for *enumext* and *enumext**.

```

2261 \cs_new_protected:Npn \__enumext_parse_save_key:n #1
2262 {
2263   \bool_set_true:c { l__enumext_store_save_key_ \__enumext_level: _bool }
2264   \tl_clear:c { l__enumext_save_key_ \__enumext_level: _tl }
2265   \tl_set:ce
2266   { l__enumext_store_save_key_ \__enumext_level: _tl }
2267   { \__enumext_filter_save_key:n {#1} }
2268 }
2269 \cs_new_protected:Npn \__enumext_parse_save_key_vii:n #1
2270 {
2271   \bool_set_true:N \l__enumext_store_save_key_vii_bool
2272   \tl_clear:N \l__enumext_store_save_key_vii_tl
2273   \tl_set:Ne \l__enumext_store_save_key_vii_tl { \__enumext_filter_save_key:n {#1} }
2274 }

```

(End of definition for `__enumext_parse_save_key:n` and `__enumext_parse_save_key_vii:n`.)

12.26.3 Internal functions to store optional arguments

```

\__enumext_filter_save_key:n
\__enumext_filter_save_key_key:n
\__enumext_filter_save_key_pair:n

```

The function `__enumext_filter_save_key:n` will be in charge of filtering the *keys* we want to *store* in *sequence* where `{#1}` represents the optional value passed to the environment.

```

2275 \cs_new:Npn \__enumext_filter_save_key:n #1
2276 {
2277   \use:e
2278   {
2279     \keyval_parse:NNn
2280     \__enumext_filter_save_key_key:n
2281     \__enumext_filter_save_key_pair:n {#1}
2282   }
2283 }

```

The function `__enumext_filter_save_key_key:n` will be responsible for filtering the *keys* that are passed “without value” by excluding the *resume*, *resume**, *no-store* and *base-fix* keys.

```

2284 \cs_new:Npn \__enumext_filter_save_key_key:n #1
2285 {
2286   \str_case:nnF {#1}
2287   {
2288     { resume } {} { resume* } {} { no-store } {} { base-fix } {}
2289   }
2290   { , { \exp_not:n {#1} } }
2291 }

```

The function `__enumext_filter_save_key_pair:nn` will be responsible for filtering the *keys* that are passed “with value” by excluding the `series`, `resume`, `save-ans`, `save-ref`, `check-ans`, `show-ans`, `save-pos`, `wrap-ans`, `mark-ans`, `wrap-opt`, `save-sep`, `mark-ref`, `mini-env`, `mini-sep`, `mini-right` and `mini-right*` keys.

```

2292 \cs_new:Npn \__enumext_filter_save_key_pair:nn #1#2
2293 {
2294   \str_case:nnF {#1}
2295   {
2296     { series } {} { resume } {} { save-ans } {} { save-ref } {}
2297     { save-key } {} { check-ans } {} { show-ans } {} { show-pos } {}
2298     { wrap-ans } {} { mark-ans } {} { wrap-opt } {} { save-sep } {}
2299     { mark-ref } {} { mini-env } {} { mini-sep } {} { mini-right } {}
2300     { mini-right* } {}
2301   }
2302   { , { \exp_not:n {#1} } = { \exp_not:n {#2} } }
2303 }

```

(End of definition for `__enumext_filter_save_key:n`, `__enumext_filter_save_key_key:n`, and `__enumext_filter_save_key_pair:nn`.)

12.26.4 Function for storing content in prop list

```

\__enumext_store_addto_prop:n
\__enumext_store_addto_prop:V

```

The function `__enumext_store_addto_prop:n` stores the content in *prop list* defined by `save-ans` key. The “stored content” is retrieved by means of the `\getkeyans` command.

The form in which the content is “stored” in the *prop list* is $\{\langle position \rangle\}\{\langle content \rangle\}$. This function is used by `\anskey` in `enumext` and `enumext*` environments, `\item*` in `keyans` and `keyans*` environments and `\anspic*` in `keyanspic` environment.

```

2304 \cs_new_protected:Npn \__enumext_store_addto_prop:n #1
2305 {
2306   \prop_gput_if_not_in:cen { g__enumext_ \__enumext_store_name_tl _prop }
2307   {
2308     \int_eval:n { \prop_count:c { g__enumext_ \__enumext_store_name_tl _prop } + 1 }
2309   }
2310   { #1 }
2311 }
2312 \cs_generate_variant:Nn \__enumext_store_addto_prop:n { V, e }

```

(End of definition for `__enumext_store_addto_prop:n`.)

12.26.5 Function for storing content in sequence

```

\__enumext_store_addto_seq:n
\__enumext_store_addto_seq:v
\__enumext_store_addto_seq:V

```

The function `__enumext_store_addto_seq:n` stores the content in *sequence* defined by `save-ans` key. This function is used by `\anskey` in `enumext`, `\item*` in `keyans` and `\anspic` in `keyanspic`.

The form in which the content is stored in *sequence* is in a internal `enumext` or `enumext*` environments with the *same structure* in which the command was executed.

The “stored content” is retrieved by means of the `\printkeyans` command.

```

2313 \cs_new_protected:Npn \__enumext_store_addto_seq:n #1
2314 {
2315   \seq_gput_right:cn { g__enumext_ \__enumext_store_name_tl _seq } { #1 }
2316 }
2317 \cs_generate_variant:Nn \__enumext_store_addto_seq:n { v, V, e }

```

(End of definition for `__enumext_store_addto_seq:n`.)

12.26.6 Functions for storing the list structure in the sequence

```

\__enumext_store_level_open:
\__enumext_store_level_close:

```

The memorization structure of the list is handled by the functions `__enumext_store_level_open:` and `__enumext_store_level_close:` which are executed per level within the `enumext` environment.

```

2318 \cs_new_protected:Nn \__enumext_store_level_open:
2319 {
2320   \bool_if:NT \__enumext_check_answers_bool
2321   {
2322     \tl_if_empty:cTF { l__enumext_store_save_key_ \__enumext_level: _tl }
2323     {
2324       \__enumext_store_addto_seq:n
2325       {
2326         \item \begin{enumext}
2327       }
2328     }
2329     {
2330       \tl_put_left:cn { l__enumext_store_save_key_ \__enumext_level: _tl }
2331       {

```

```

2332         \item \begin{enumext} [
2333         ]
2334         \tl_put_right:cn { l__enumext_store_save_key_ \__enumext_level: _tl }
2335         {
2336         ]
2337         }
2338         \__enumext_store_addto_seq:v { l__enumext_store_save_key_ \__enumext_level: _tl }
2339     }
2340 }
2341 }
2342 \cs_new_protected:Nn \__enumext_store_level_close:
2343 {
2344     \bool_if:NT \l__enumext_check_answers_bool
2345     {
2346         \__enumext_store_addto_seq:n { \end{enumext} }
2347     }
2348 }

```

(End of definition for __enumext_store_level_open: and __enumext_store_level_close:.)

__enumext_store_level_open_vii:
 __enumext_store_level_close_vii:

The memorization structure of the list is handled by the functions __enumext_store_level_open_vii: and __enumext_store_level_close_vii: which are executed in the `enumext*` environment.

```

2349 \cs_new_protected:Nn \__enumext_store_level_open_vii:
2350 {
2351     \bool_if:NT \l__enumext_check_answers_bool
2352     {
2353         \tl_if_empty:NTF \l__enumext_store_save_key_vii_tl
2354         {
2355             \__enumext_store_addto_seq:n
2356             {
2357                 \item \begin{enumext*}
2358             }
2359         }
2360         {
2361             \tl_put_left:Nn \l__enumext_store_save_key_vii_tl
2362             {
2363                 \item \begin{enumext*}[
2364                 ]
2365             \tl_put_right:Nn \l__enumext_store_save_key_vii_tl
2366             {
2367                 ]
2368             }
2369             \__enumext_store_addto_seq:V \l__enumext_store_save_key_vii_tl
2370         }
2371     }
2372 }
2373 \cs_new_protected:Nn \__enumext_store_level_close_vii:
2374 {
2375     \bool_if:NT \l__enumext_check_answers_bool
2376     {
2377         \__enumext_store_addto_seq:n { \end{enumext*} }
2378     }
2379 }

```

(End of definition for __enumext_store_level_open_vii: and __enumext_store_level_close_vii:.)

12.26.7 Function for show marks and position

__enumext_print_keyans_box:NN
 __enumext_print_keyans_box:cc

The function __enumext_print_keyans_box:NN print a box in the left margin with \l__enumext_mark_answer_sym_tl used by the `wrap-ans`, `show-ans` and `show-pos` keys. The function takes two arguments:

#1: \l__enumext_labelwidth_X_dim
 #2: \l__enumext_labelsep_X_dim

```

2380 \cs_new_protected:Nn \__enumext_print_keyans_box:NN
2381 {
2382     \mode_leave_vertical:
2383     \skip_horizontal:n { -\dim_use:N #2 }
2384     \makebox[0pt][ r ]
2385     {
2386         \makebox[ \dim_use:N #1 ][ \l__enumext_mark_position_str ]
2387         {
2388             \tl_use:N \l__enumext_mark_answer_sym_tl

```

```

2389     }
2390   }
2391   \skip_horizontal:n { \dim_use:N #2 }
2392 }
2393 \cs_generate_variant:Nn \__enumext_print_keyans_box:NN { cc }

```

(End of definition for __enumext_print_keyans_box:NN.)

12.27 The internal label and ref

The function __enumext_store_internal_ref: handles the internal “*label and ref*” system used by the `save-ref` and `mark-ref` keys for \anskey will allow to execute `\ref{<store name : position>}` and will return 1.(a).i.A.

__enumext_store_internal_ref:

First we will remove the dots “.” from the current <labels>, we do not want to get double dots in our references, then we will place this in the variable \l__enumext_newlabel_arg_two_tl.

```

2394 \cs_new_protected:Nn \__enumext_store_internal_ref:
2395 {
2396   \cs_set_protected:Npn \__enumext_tmp:n ##1
2397   {
2398     \tl_set_eq:cc { l__enumext_label_copy_##1_tl } { l__enumext_label_##1_tl }
2399     \tl_reverse:c { l__enumext_label_copy_##1_tl }
2400     \tl_remove_once:cn { l__enumext_label_copy_##1_tl } { . }
2401     \tl_reverse:c { l__enumext_label_copy_##1_tl }
2402   }
2403   \clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {##1} }
2404   \cs_set:Npn \__enumext_tmp:n ##1
2405   { . \tl_use:c { l__enumext_label_copy_ \int_to_roman:n {##1} _tl } }

```

Here we need to analyse the cases where the environment is started with `enumext*` and if \anskey or `anskey*` is running alone in it or if it is running in a nested `enumext` environment within the starting environment.

```

2406   \bool_lazy_all:nT
2407   {
2408     { \bool_if_p:N \g__enumext_starred_bool }
2409     { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
2410   }
2411   {
2412     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2413     { \tl_use:N \l__enumext_label_copy_vii_tl }
2414   }
2415   \bool_lazy_all:nT
2416   {
2417     { \bool_not_p:n { \g__enumext_standar_bool } }
2418     { \bool_if_p:N \l__enumext_standar_bool }
2419     { \int_compare_p:nNn { \l__enumext_level_int } > { 0 } }
2420   }
2421   {
2422     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2423     {
2424       \tl_use:N \l__enumext_label_copy_vii_tl
2425       \int_step_function:nnN { 1 } { \l__enumext_level_int } \__enumext_tmp:n
2426     }
2427   }

```

If started with `enumext` and if \anskey or `anskey*` is running alone in it or if it is running in a nested `enumext*` environment within the starting environment.

```

2428   \bool_lazy_all:nT
2429   {
2430     { \bool_if_p:N \g__enumext_standar_bool }
2431     { \int_compare_p:nNn { \l__enumext_level_int } > { 0 } }
2432     { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
2433   }
2434   {
2435     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2436     {
2437       \tl_use:N \l__enumext_label_copy_i_tl
2438       \int_step_function:nnN { 2 } { \l__enumext_level_int } \__enumext_tmp:n
2439     }
2440   }
2441   \cs_set:Npn \__enumext_tmp:n ##1
2442   { \tl_use:c { l__enumext_label_copy_ \int_to_roman:n {##1} _tl } . }
2443   \bool_lazy_all:nT

```

```

2444     {
2445       { \bool_if_p:N \g__enumext_standar_bool }
2446       { \bool_if_p:N \l__enumext_starred_bool }
2447       { \int_compare_p:nNn { \l__enumext_level_int } > { 0 } }
2448     }
2449     {
2450       \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2451       {
2452         \int_step_function:nnN { 1 } { \l__enumext_level_int } \l__enumext_tmp:n
2453         \tl_use:N \l__enumext_label_copy_vii_tl
2454       }
2455     }

```

Now we set the variable `\l__enumext_newlabel_arg_one_tl` which will contain $\langle \textit{store name} : \textit{position} \rangle$.

```

2456     \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
2457     {
2458       \l__enumext_store_name_tl \c_colon_str
2459       \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
2460     }

```

Now execute the function `__enumext_newlabel:nn` and save the result in the variable `\l__enumext_write_aux_file_tl` and finally we write in the `.aux` file.

```

2461     \tl_put_right:Ne \l__enumext_write_aux_file_tl
2462     {
2463       \__enumext_newlabel:nn
2464       { \exp_not:V \l__enumext_newlabel_arg_one_tl }
2465       { \l__enumext_newlabel_arg_two_tl }
2466     }
2467     \l__enumext_write_aux_file_tl
2468   }

```

(End of definition for `__enumext_store_internal_ref:`)

12.28 Common functions for `\anskey` and `\anskey*` environment

`__enumext_store_anskey_code:n`

The internal function `__enumext_store_anskey_code:n` first we pass the $\langle \textit{argument} \rangle$ to the $\langle \textit{prop list} \rangle$, then checks the state of the variable `\l__enumext_store_ref_key_bool` handled by the `save-ref` key and will call the function `__enumext_store_internal_ref:` for the internal “*label and ref*” system. Followed by this if the `show-ans` or `show-pos` keys are active we will show the “*wrapped*” $\langle \textit{argument} \rangle$.

```

2469 \cs_new_protected:Npn \__enumext_store_anskey_code:n #1
2470 {
2471   \int_gincr:N \g__enumext_item_anskey_int
2472   \__enumext_store_addto_prop:n {#1}
2473   \bool_if:NT \l__enumext_store_ref_key_bool
2474   {
2475     \__enumext_store_internal_ref:
2476   }
2477   \__enumext_anskey_show_wrap_left:n { #1 }

```

Now we start processing the $[(key = val)]$ passed to the command to build our `\item` in the variable `\l__enumext_store_anskey_arg_tl` which we will “*store*” in the $\langle \textit{sequence} \rangle$. First we clear the variable `\l__enumext_store_anskey_arg_tl` and process the $\langle \textit{keys} \rangle$, if the `break-col` key is present and the command is running under `enumext` (not in `enumext*`) we will add `\columnbreak` and then `\item`.

```

2478   \tl_clear:N \l__enumext_store_anskey_arg_tl
2479   \bool_lazy_and:nnT
2480   { \bool_if_p:N \l__enumext_store_columns_break_bool }
2481   { \bool_not_p:n { \l__enumext_starred_bool } }
2482   {
2483     \tl_put_left:Nn \l__enumext_store_anskey_arg_tl { \columnbreak }
2484   }
2485   \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { \item }

```

If the `item-join` key is present and the command is running under `enumext*` we will add $\langle \textit{number} \rangle$ to `\l__enumext_store_anskey_arg_tl`.

```

2486   \bool_lazy_and:nnT
2487   { \bool_not_p:n { \l__enumext_starred_bool } }
2488   { \int_compare_p:nNn { \l__enumext_store_item_join_int } > { 1 } }
2489   {
2490     \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2491     {
2492       ( \exp_not:V \l__enumext_store_item_join_int )
2493     }
2494   }

```

And now we will review the keys `item-star`, `item-sym*` and `item-pos*` and pass them to `\l__enumext_store_anskey_arg_tl` along with the $\langle argument \rangle$ for `\anskey` or $\langle body \rangle$ for `anskey*`.

```

2495 \bool_if:NTF \l__enumext_store_item_star_bool
2496 {
2497   \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { * }
2498   \tl_if_empty:NF \l__enumext_store_item_symbol_tl
2499   {
2500     \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2501     {
2502       [ \exp_not:V \l__enumext_store_item_symbol_tl ]
2503     }
2504   }
2505   \dim_compare:nT
2506   {
2507     \l__enumext_store_item_symbol_sep_dim != \c_zero_dim
2508   }
2509   {
2510     \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2511     {
2512       [ \exp_not:V \l__enumext_store_item_symbol_sep_dim ]
2513     }
2514   }
2515   \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#1}
2516 }
2517 {
2518   \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#1}
2519 }

```

Finally we check if the `save-ref` key are active along with the `hyperref` package load, if both conditions are met, it will create the `\hyperlink` with `symbol` set by `mark-ref` key and then store in $\langle sequence \rangle$.

```

2520 \bool_lazy_and:nnT
2521 { \bool_if_p:N \l__enumext_store_ref_key_bool }
2522 { \bool_if_p:N \l__enumext_hyperref_bool }
2523 {
2524   \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2525   {
2526     \hfill \exp_not:N \hyperlink { \exp_not:V \l__enumext_newlabel_arg_one_tl }
2527     { \exp_not:V \l__enumext_mark_ref_sym_tl }
2528   }
2529 }
2530 \__enumext_store_addto_seq:V \l__enumext_store_anskey_arg_tl
2531 }

```

(End of definition for `__enumext_store_anskey_code:n`.)

`__enumext_anskey_show_wrap_arg:n`

The function `__enumext_anskey_show_wrap_arg:n` “wraps” the $\langle argument \rangle$ passed to `\anskey` and the $\langle body \rangle$ for `anskey*` when using the `wrap-ans` key.

```

2532 \cs_new_protected:Npn \__enumext_anskey_show_wrap_arg:n #1
2533 {
2534   \par
2535   \bool_if:NTF \l__enumext_starred_bool
2536   {
2537     \__enumext_print_keyans_box:NN \l__enumext_labelwidth_vii_dim \l__enumext_labelsep_vii_dim
2538   }
2539   {
2540     \__enumext_print_keyans_box:cc
2541     { \l__enumext_labelwidth_ \l__enumext_level: _dim }
2542     { \l__enumext_labelsep_ \l__enumext_level: _dim }
2543   }
2544   \__enumext_anskey_wrapper:n { #1 }
2545 }

```

(End of definition for `__enumext_anskey_show_wrap_arg:n`.)

`__enumext_anskey_show_wrap_left:n`

The function `__enumext_anskey_show_wrap_left:n` will show the “mark” defined by the `mark-ans` key or the “position” of the content stored in the $\langle prop list \rangle$ when using the `show-pos` key on the left margin next to the “wraps” $\langle argument \rangle$ passed to `\anskey` and the $\langle body \rangle$ in `anskey*` on the right side when using the `show-ans` key.

```

2546 \cs_new_protected:Npn \__enumext_anskey_show_wrap_left:n #1
2547 {
2548   \bool_if:NNT \l__enumext_show_answer_bool

```



```

2549     {
2550         \__enumext_anskey_show_wrap_arg:n { #1 }
2551     }
2552     \bool_if:NT \l__enumext_show_position_bool
2553     {
2554         \tl_set:Nx \l__enumext_mark_answer_sym_tl
2555         {
2556             \group_begin:
2557             \exp_not:N \normalfont
2558             \exp_not:N \footnotesize [ \int_eval:n
2559             {
2560                 \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
2561             }
2562             ]
2563             \group_end:
2564         }
2565         \__enumext_anskey_show_wrap_arg:n { #1 }
2566     }
2567 }

```

(End of definition for __enumext_anskey_show_wrap_left:n.)

12.29 The command \anskey

Since we will be “*storing content*” in a list environment within *(sequences)* and can (more or less) manage the options passed to each level, it is necessary that we have a little more control over \item when storing.

The \anskey command will cover this point and give it similar behaviour to that of \item in the enumext and enumext* environments executed as follows \anskey[⟨key = val⟩]{⟨content⟩}.

First we’ll add the keys break-col, item-join, item-star, item-sym* and item-pos*.

```

\__enumext_anskey_unknown:n
\__enumext_anskey_unknown:nn
2568 \keys_define:nn { enumext / anskey }
2569 {
2570     break-col .bool_set:N = \l__enumext_store_columns_break_bool,
2571     break-col .default:n = true,
2572     break-col .value_forbidden:n = true,
2573     item-join .int_set:N = \l__enumext_store_item_join_int,
2574     item-join .value_required:n = true,
2575     item-star .bool_set:N = \l__enumext_store_item_star_bool,
2576     item-star .default:n = true,
2577     item-star .value_forbidden:n = true,
2578     item-sym* .tl_set:N = \l__enumext_store_item_symbol_tl,
2579     item-sym* .value_required:n = true,
2580     item-pos* .dim_set:N = \l__enumext_store_item_symbol_sep_dim,
2581     item-pos* .value_required:n = true,
2582     unknown .code:n = { \__enumext_anskey_unknown:n {#1} },
2583 }

```

The *(keys)* are stored in \l_keys_key_str and the value (if any) is passed as an argument to the function __enumext_anskey_unknown:n.

```

2584 \cs_new_protected:Npn \__enumext_anskey_unknown:n #1
2585 {
2586     \exp_args:NV \__enumext_anskey_unknown:nn \l_keys_key_str {#1}
2587 }
2588 \cs_new_protected:Npn \__enumext_anskey_unknown:nn #1 #2
2589 {
2590     \tl_if_blank:nTF {#2}
2591     {
2592         \msg_error:nnn { enumext } { anskey-cmd-key-unknown } {#1}
2593     }
2594     {
2595         \msg_error:nnnn { enumext } { anskey-cmd-key-value-unknown } {#1} {#2}
2596     }
2597 }

```

(End of definition for __enumext_anskey_unknown:n and __enumext_anskey_unknown:nn.)

- The \anskey command will only be present when using the save-ans key in enumext and enumext* environments, otherwise it will return an error.

\anskey We will first call the function __enumext_anskey_safe_outer: to be sure where we execute the command, then we will check the state of the variable \l__enumext_check_answers_bool set by the key no-store, if is true we will increment \g__enumext_item_anskey_int for the internal “*check answer*” system and execute the function __enumext_anskey_safe_inner:n to ensure that the command is not nested and

that the argument is not empty, finally search the $\langle key = val \rangle$ and call the function `__enumext_store_anskey_code:n`.

```

2598 \NewDocumentCommand \anskey { o +m }
2599 {
2600   \__enumext_anskey_safe_outer:
2601   \group_begin:
2602     \bool_if:NT \l__enumext_check_answers_bool
2603     {
2604       \tl_if_novalue:nF {#1}
2605       {
2606         \keys_set:nn { enumext / anskey } {#1}
2607       }
2608       \tl_if_blank:nTF {#2}
2609       {
2610         \msg_error:nn { enumext } { anskey-empty-arg }
2611       }
2612       {
2613         \__enumext_anskey_safe_inner:
2614         \__enumext_store_anskey_code:n {#2}
2615       }
2616     }
2617   \group_end:
2618 }

```

(End of definition for `\anskey`. This function is documented on page 12.)

12.29.1 Internal functions for the command

`__enumext_anskey_safe_outer:` The `__enumext_store_anskey_safe_outer:` function will return the appropriate messages when the command is executed outside the environment in which the `save-ans` key was activated.

`__enumext_anskey_safe_inner:`

```

2619 \cs_new_protected:Nn \__enumext_anskey_safe_outer:
2620 {
2621   \bool_if:NF \l__enumext_store_active_bool
2622   {
2623     \msg_error:nnnn { enumext } { anskey-wrong-place } { anskey } { enumext }
2624   }
2625   \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
2626   {
2627     \msg_error:nnnn { enumext } { command-wrong-place } { anskey } { keyans }
2628   }
2629   \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
2630   {
2631     \msg_error:nnnn { enumext } { command-wrong-place } { anskey } { keyans* }
2632   }
2633   \int_compare:nNnT { \l__enumext_keyans_pic_level_int } = { 1 }
2634   {
2635     \msg_error:nnnn { enumext } { command-wrong-place } { anskey } { keyanspic }
2636   }
2637 }

```

The `__enumext_anskey_safe_inner:` function will first check if the command is nested, if preceded by a not numbered `\item` or if it is in *math mode* returning the appropriate messages.

```

2638 \cs_new_protected:Nn \__enumext_anskey_safe_inner:
2639 {
2640   \int_incr:N \l__enumext_anskey_level_int
2641   \int_compare:nNnT { \l__enumext_anskey_level_int } > { 1 }
2642   {
2643     \msg_error:nn { enumext } { anskey-nested }
2644   }
2645   \bool_if:NF \l__enumext_item_number_bool
2646   {
2647     \msg_error:nn { enumext } { anskey-unnumber-item }
2648   }
2649   \mode_if_math:T
2650   {
2651     \msg_error:nne { enumext } { anskey-math-mode } { \c_backslash_str anskey }
2652   }
2653 }

```

(End of definition for `__enumext_anskey_safe_outer:` and `__enumext_anskey_safe_inner:`)

12.30 The environment anskey*

Managing *verbatim content* in an environment is quite complicated, I learned that when creating the `scontents` package, so to be able to have support at this point it is best to play a little with the internal code of `scontents` and `hooks`. Some considerations I should have here before implementing this:

- If some package, class or user has defined the environment with the same name somewhere in the document it would be a problem, you would not know what argument has been passed to `store-env`, if you are using the key `print-env` or the `write-out` key, sure, I can detect and modify it within the `enumext` and `enumext*` environments, but it would look strange not to have some keys available when running within these environments.
- A better (perhaps a bit paranoid) option is to define it within the environment in which the `save-ans` key is executed. and have it available only when that key is executed, here I would have absolute control of the `(keys)` and I make sure that `write-out` is not used, then using `hooks after` I undefine it and using `hook before` I check if it has been created by any package, class or user and I return a error, then the user will have to see how to solve the problem.

`__enumext_undefine_anskey_env:` The function `__enumext_undefine_anskey_env:` will undefine the environment `anskey*` and will be passed to the function `__enumext_execute_after_env:` (§12.31) which is executed after the environment in which the key `save-ans` is active.

```

2654 \cs_new_protected:Nn \__enumext_undefine_anskey_env:
2655 {
2656   \cs_undefine:c { anskey* }
2657   \cs_undefine:c { endanskey* }
2658   \cs_undefine:c { __scontents_anskey*_env_begin: }
2659   \cs_undefine:c { __scontents_anskey*_env_end: }
2660 }
```

Detection of the `anskey*` environment outside the `enumext` and `enumext*` environments.

```

2661 \__enumext_before_env:nn { enumext }
2662 {
2663   \bool_lazy_and:nnT
2664   { \int_compare_p:nNn { \__enumext_level_int } = { 0 } }
2665   { \int_compare_p:nNn { \__enumext_level_h_int } = { 0 } }
2666   {
2667     \cs_if_free:cF { __scontents_anskey*_env_begin: }
2668     {
2669       \msg_error:nnn { enumext } { anskey-env-error } { anskey* }
2670     }
2671   }
2672 }
2673 \__enumext_before_env:nn { enumext* }
2674 {
2675   \bool_lazy_and:nnT
2676   { \int_compare_p:nNn { \__enumext_level_int } = { 0 } }
2677   { \int_compare_p:nNn { \__enumext_level_h_int } = { 0 } }
2678   {
2679     \cs_if_free:cF { __scontents_anskey*_env_begin: }
2680     {
2681       \msg_error:nnn { enumext } { anskey-env-error } { anskey* }
2682     }
2683   }
2684 }
```

Detection of the `anskey*` environment inside the `keyans`, `keyans*` and `keyanspic` environments, if preceded by a not numbered `\item` or if it is in *math mode* returning the appropriate messages.

```

2685 \__enumext_before_env:nn { anskey* }
2686 {
2687   \int_compare:nNnT { \__enumext_keyans_level_int } = { 1 }
2688   {
2689     \msg_error:nnn { enumext } { anskey-env-wrong } { keyans }
2690   }
2691   \int_compare:nNnT { \__enumext_keyans_level_h_int } = { 1 }
2692   {
2693     \msg_error:nnn { enumext } { anskey-env-wrong } { keyans* }
2694   }
2695   \int_compare:nNnT { \__enumext_keyans_pic_level_int } = { 1 }
2696   {
2697     \msg_error:nnn { enumext } { anskey-env-wrong } { keyanspic }
2698   }
2699   \bool_if:NF \__enumext_item_number_bool
2700   {
```

```

2701         \msg_error:nn { enumext } { anskey-unnumber-item }
2702     }
2703     \mode_if_math:T
2704     {
2705         \msg_error:nnn { enumext } { anskey-math-mode } { anskey* }
2706     }
2707 }

```

(End of definition for `__enumext_undefine_anskey_env:`)

anskey*

The function `__enumext_anskey_env_make:n` creates the environment **anskey*** (custom version of **scontents** environment) by setting the initial keys `store-env={⟨store name⟩}` and `print-env=false`.

To maintain the *scope* of the environment and that it is only active when the key `save-ans` is active we will pass this function to the function `__enumext_storing_exec:` (§12.25.1) and we will execute it only if the variable `\l__enumext_anskey_env_bool` is true, with this we prevent it from being executed again when the environment is nested and the key `save-ans` is active, which returns an error for part of the package **scontents**.

```

2708 \cs_new_protected:Npn \__enumext_anskey_env_make:n #1
2709 {
2710     \bool_if:NT \l__enumext_anskey_env_bool
2711     {
2712         \newenvsc{anskey*}[store-env=#1,print-env=false]
2713         \__enumext_anskey_env_exec:
2714     }
2715 }
2716 \cs_generate_variant:Nn \__enumext_anskey_env_make:n { V }

```

The function `__enumext_anskey_env_define_keys:` will add the keys `break-col`, `item-join`, `item-join`, `item-star`, `item-sym*` and `item-pos*` and will leave the keys `print-env`, `store-env` and `write-out` undefined. We will apply this function using the *hook* function `__enumext_before_env:nn`.

```

2717 \cs_new_protected:Nn \__enumext_anskey_env_define_keys:
2718 {
2719     \keys_define:nn { scontents / scontents }
2720     {
2721         break-col .bool_gset:N = \g__enumext_store_columns_break_bool,
2722         break-col .default:n   = true,
2723         break-col .value_forbidden:n = true,
2724         item-join .int_gset:N   = \g__enumext_store_item_join_int,
2725         item-join .value_required:n = true,
2726         item-star .bool_gset:N = \g__enumext_store_item_star_bool,
2727         item-star .default:n    = true,
2728         item-star .value_forbidden:n = true,
2729         item-sym* .tl_gset:N    = \g__enumext_store_item_symbol_tl,
2730         item-sym* .value_required:n = true,
2731         item-pos* .dim_gset:N   = \g__enumext_store_item_symbol_sep_dim,
2732         item-pos* .value_required:n = true,
2733         print-env .undefine:,
2734         store-env .undefine:,
2735         write-out .undefine:,
2736         unknown .code:n       = { \__enumext_anskey_env_unknown:n {##1} },
2737     }
2738 }

```

The *⟨keys⟩* are stored in `\l_keys_key_str` and the value (if any) is passed as an argument to the function `__enumext_anskey_env_unknown:n`.

```

2739 \cs_new_protected:Npn \__enumext_anskey_env_unknown:n #1
2740 {
2741     \exp_args:NV \__enumext_anskey_env_unknown:nn \l_keys_key_str {#1}
2742 }
2743 \cs_new_protected:Npn \__enumext_anskey_env_unknown:nn #1#2
2744 {
2745     \tl_if_blank:nTF {#2}
2746     {
2747         \msg_error:nnn { enumext } { anskey-env-key-unknown } {#1}
2748     }
2749     {
2750         \msg_error:nnnn { enumext } { anskey-env-key-value-unknown } {#1} {#2}
2751     }
2752 }

```

The function `__enumext_anskey_env_reset_keys:` will leave the keys `break-col`, `item-join`, `item-join`, `item-star`, `item-sym*` and `item-pos*` undefined. We will apply this function using the *hook* function `__enumext_after_env:nn`.

```

2753 \cs_new_protected:Nn \__enumext_anskey_env_reset_keys:
2754 {
2755   \keys_define:nn { scontents / scontents }
2756   {
2757     break-col .undefine:,
2758     item-join .undefine:,
2759     item-star .undefine:,
2760     item-sym* .undefine:,
2761     item-pos* .undefine:,
2762     write-out .code:n = {
2763       \bool_set_false:N \l__scontents_storing_bool
2764       \bool_set_true:N \l__scontents_writing_bool
2765       \tl_set:Nn \l__scontents_fname_out_tl {##1}
2766     },
2767     write-out .value_required:n = true,
2768     print-env .meta:nn = { scontents } { print-env = ##1 },
2769     print-env .default:n = true,
2770     store-env .meta:nn = { scontents } { store-env = ##1 },
2771     unknown .code:n = { \__scontents_parse_environment_keys:n {##1} },
2772   }
2773 }

```

The function `__enumext_rescan_anskey_env:n` will be responsible for bringing the *(body)* of the environment saved in the sequence `\g__scontents_name_⟨store name⟩_seq` to pass it to our *sequence* and *prop list*.

```

2774 \cs_new_protected:Npn \__enumext_rescan_anskey_env:n #1
2775 {
2776   \group_begin:
2777   \int_set:Nn \tex_newlinechar:D { `^^J }
2778   \__scontents_rescan_tokens:x
2779   {
2780     \endgroup % This assumes \catcode`\=0... Things might go off otherwise.
2781     #1
2782   }
2783 }

```

(End of definition for *anskey** and others. This function is documented on page 13.)

`__enumext_anskey_env_exec:`

The function `__enumext_anskey_env_exec:` will be responsible for processing all the code necessary for the execution of the environment. The first thing will be to add our *(keys)*.

```

2784 \cs_new_protected:Nn \__enumext_anskey_env_exec:
2785 {
2786   \__enumext_before_env:nn { anskey* }
2787   {
2788     \__enumext_anskey_env_define_keys:
2789   }

```

Now we will execute our actions after the *anskey** environment is closed. We'll fetch the contents of the *environment body* that is now saved in `\g__scontents_name_⟨store name⟩_seq` and store it in the variable `\l__enumext_store_anskey_env_tl` then we execute the rest of the functions.

```

2790   \hook_if_empty:nF {env/anskey*/after}
2791   {
2792     \hook_gremove_code:nn {env/anskey*/after} { * }
2793   }
2794   \__enumext_after_env:nn { anskey* }
2795   {
2796     \__enumext_anskey_env_save_keys:
2797     \tl_clear:N \l__enumext_store_anskey_env_tl
2798     \tl_clear:N \l__enumext_store_anskey_opt_tl
2799     \bool_if:NT \l__enumext_check_answers_bool
2800     {
2801       \tl_gset:Ne \l__enumext_store_anskey_env_tl
2802       {
2803         \seq_item:ce { g__scontents_name_ \l__enumext_store_name_tl _seq } { -1 }
2804       }
2805       \regex_match:nVTF
2806       { ^\s* \z | ^\s* \u{c__scontents_hidden_space_str} \z }
2807       \l__enumext_store_anskey_env_tl

```

```

2808         {
2809             \msg_error:nn { enumext } { anskey-empty-arg }
2810         }
2811         {
2812             \__enumext_anskey_env_store:
2813         }
2814     }
2815     \__enumext_anskey_env_clean_vars:
2816     \__enumext_anskey_env_reset_keys:
2817 }
2818 }

```

• The use of `\hook_gremove_code:nn` is necessary here, otherwise the `{\code}` passed to `__enumext_after_env:nn{anskey*}` will be accumulated for each execution. The last function `__enumext_anskey_env_reset_keys:` is necessary so as not to hinder any `scontents` environment running within `enumext` or `enumext*`.

(End of definition for `__enumext_anskey_env_exec:.`)

```

\__enumext_anskey_env_save_keys:
\__enumext_anskey_env_store:
\__enumext_anskey_env_clean_vars:

```

The function `__enumext_anskey_env_save_keys:` processing the `[key = val]` passed to the environment and save this in the variable `\l__enumext_store_anskey_opt_tl`. If the `break-col` key is present and the environment is running under `enumext` (not in `enumext*`) we will add the key `break-col`.

```

2819 \cs_new_protected:Nn \__enumext_anskey_env_save_keys:
2820 {
2821     \bool_lazy_and:nnT
2822     { \bool_if_p:N \g__enumext_store_columns_break_bool }
2823     { \bool_not_p:n { \l__enumext_starred_bool } }
2824     {
2825         \tl_put_left:Ne \l__enumext_store_anskey_opt_tl { ,break-col, }
2826     }

```

If the `item-join` key is present and the command is running under `enumext*` we will add to `\l__enumext_store_anskey_opt_tl`.

```

2827     \bool_lazy_and:nnT
2828     { \bool_not_p:n { \l__enumext_starred_bool } }
2829     { \int_compare_p:nNn { \g__enumext_store_item_join_int } > { 1 } }
2830     {
2831         \tl_put_left::Ne \l__enumext_store_anskey_opt_tl
2832         {
2833             ,item-join = \exp_not:V \g__enumext_store_item_join_int,
2834         }
2835     }

```

And now we will review the keys `item-star`, `item-sym*` and `item-pos*` and pass them to `\l__enumext_store_anskey_opt_tl`.

```

2836     \bool_if:NT \g__enumext_store_item_star_bool
2837     {
2838         \tl_put_left:Ne \l__enumext_store_anskey_opt_tl
2839         {
2840             ,item-star,
2841         }
2842         \tl_if_empty:NF \g__enumext_store_item_symbol_tl
2843         {
2844             \tl_put_left:Ne \l__enumext_store_anskey_opt_tl
2845             {
2846                 ,item-sym* = \exp_not:V \g__enumext_store_item_symbol_tl,
2847             }
2848         }
2849         \dim_compare:nT
2850         {
2851             \g__enumext_store_item_symbol_sep_dim != \c_zero_dim
2852         }
2853         {
2854             \tl_put_left:Ne \l__enumext_store_anskey_opt_tl
2855             {
2856                 ,item-pos* = \exp_not:V \g__enumext_store_item_symbol_sep_dim,
2857             }
2858         }
2859     }
2860 }

```

The function `__enumext_anskey_env_store:` will be responsible for storing the content of the environment using the functions `__enumext_store_anskey_code:n` and `__enumext_rescan_anskey_env:n`.

```

2861 \cs_new_protected:Nn \__enumext_anskey_env_store:

```

```

2862 {
2863   \group_begin:
2864   \tl_if_empty:NTF \l__enumext_store_anskey_opt_tl
2865   {
2866     \exp_args:Ne
2867     \__enumext_store_anskey_code:n
2868     {
2869       \__enumext_rescan_anskey_env:n { \l__enumext_store_anskey_env_tl }
2870     }
2871   }
2872   {
2873     \keys_set_known:nV { enumext / anskey } \l__enumext_store_anskey_opt_tl
2874     \exp_args:Ne
2875     \__enumext_store_anskey_code:n
2876     {
2877       \__enumext_rescan_anskey_env:n { \l__enumext_store_anskey_env_tl }
2878     }
2879   }
2880   \group_end:
2881 }

```

The function `__enumext_anskey_env_clean_vars:` will return the global variables used by the `(keys)` to their initial state.

```

2882 \cs_new_protected:Nn \__enumext_anskey_env_clean_vars:
2883 {
2884   \bool_gset_false:N \g__enumext_store_columns_break_bool
2885   \int_gzero:N \g__enumext_store_item_join_int
2886   \bool_gset_false:N \g__enumext_store_item_star_bool
2887   \tl_gclear:N \g__enumext_store_item_symbol_tl
2888   \dim_gzero:N \g__enumext_store_item_symbol_sep_dim
2889 }

```

(End of definition for `__enumext_anskey_env_save_keys:`, `__enumext_anskey_env_store:`, and `__enumext_anskey_env_clean_vars:`.)

12.31 Executing anskey*, check-ans and write .log

`__enumext_execute_after_env:`

The `__enumext_execute_after_env:` function will first return the appropriate message for the end of the environment in which the `save-ans` key is being executed, then call the `__enumext_item_answer_diff:` function and then will write the values of the global variables used to the `.log` file. If the key `check-ans` is active it will execute the function `__enumext_check_ans_show:` and show the result in the terminal, otherwise it will execute the function `__enumext_check_ans_log:` and write the results in the `.log` file, undefine the environment `anskey*` (§12.30) through the function `__enumext_undefine_anskey_env:` and finally we execute the function `__enumext_reset_global_vars:` returning the used variables to their original state.

```

2890 \cs_new_protected:Nn \__enumext_execute_after_env:
2891 {
2892   \int_compare:nNnT { \l__enumext_level_int } = { 0 }
2893   {
2894     \tl_if_empty:NF \g__enumext_store_name_tl
2895     {
2896       \__enumext_stop_save_ans_msg:
2897       \__enumext_item_answer_diff:
2898       \__enumext_log_global_vars:
2899       \__enumext_log_answer_vars:
2900       \bool_if:NTF \g__enumext_check_ans_key_bool
2901       {
2902         \__enumext_check_ans_show:
2903       }
2904       { \__enumext_check_ans_log: }
2905       \__enumext_undefine_anskey_env:
2906     }
2907     \__enumext_reset_global_vars:
2908   }
2909 }

```

(End of definition for `__enumext_execute_after_env:`.)

- This function is passed to the function `__enumext_after_env:nn` for the environments `enumext` (§12.38) and `enumext*` (§12.43) and it is executed only when the environments are not nested or at some level of these..

12.32 Common functions for keyans, keyans* and keyanspic

12.32.1 Storing content in prop list

`__enumext_keyans_addto_prop:n`

The function `__enumext_keyans_addto_prop:n` will pass the contents of the current $\langle label \rangle$ `\l__enumext_label_v_tl` for the `keyans` environment and the current $\langle label \rangle$ `\l__enumext_label_vi_tl` for the `keyanspic` environment when using `\item*` and `\anspic*`, followed by the *contents* of the optional argument of both commands to the `\l__enumext_store_current_label_tl` variable, which will be passed to the $\langle prop list \rangle$ defined by the `save-ans` key using the `__enumext_store_addto_prop:V`.

```

2910 \cs_new_protected:Npn \__enumext_keyans_addto_prop:n #1
2911 {
2912   \tl_clear:N \l__enumext_store_current_label_tl
2913   \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
2914   {
2915     \tl_put_right:Ne \l__enumext_store_current_label_tl { \l__enumext_label_vi_tl }
2916   }
2917   {
2918     \tl_put_right:Ne \l__enumext_store_current_label_tl { \l__enumext_label_v_tl }
2919   }
2920   \tl_if_novalue:nF { #1 }
2921   {
2922     % Set save-sep
2923     \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_tl
2924     {
2925       \tl_put_right:Ne \l__enumext_store_current_label_tl { \l__enumext_store_keyans_item_opt_sep_tl }
2926     }
2927     \tl_put_right:Ne \l__enumext_store_current_label_tl { #1 }
2928   }
2929   \__enumext_store_addto_prop:V \l__enumext_store_current_label_tl
2930 }

```

(End of definition for `__enumext_keyans_addto_prop:n`.)

12.32.2 The save-ref key for keyans, keyans* and keyanspic

The “*internal label and ref*” system for the `keyans`, `keyans*` and `keyanspic` environments has slight differences with the one implemented for the `\anskey` command, basically because in this environments we are interested in the current $\langle label \rangle$. The mechanism defined here will allow to execute `\ref{\langle store name : position \rangle}` and will return `1.(A)`.

`__enumext_keyans_store_ref:`
`__enumext_keyans_store_ref_aux_i:`
`__enumext_keyans_store_ref_aux_ii:`

The function `__enumext_keyans_store_ref:` handles the internal “*label and ref*” system used by the `save-ref` key for `\item*` and `\anspic*` commands. First we will create copies of the current $\langle labels \rangle$ and remove the dots “.” from them, we do not want to get double dots in our references.

```

2931 \cs_new_protected:Nn \__enumext_keyans_store_ref:
2932 {
2933   \bool_if:NT \l__enumext_store_ref_key_bool
2934   {
2935     \cs_set_protected:Npn \__enumext_tmp:n ##1
2936     {
2937       \tl_set_eq:cc { \l__enumext_label_copy_##1_tl } { \l__enumext_label_##1_tl }
2938       \tl_reverse:c { \l__enumext_label_copy_##1_tl }
2939       \tl_remove_once:cn { \l__enumext_label_copy_##1_tl } { . }
2940       \tl_reverse:c { \l__enumext_label_copy_##1_tl }
2941     }
2942     \clist_map_inline:nn { i, v, vi, vii, viii } { \__enumext_tmp:n {##1} }
2943     \__enumext_keyans_store_ref_aux_i:
2944   }
2945 }

```

The auxiliary function `__enumext_keyans_store_ref_aux_i:` set the variable `\l__enumext_newlabel_arg_one_tl` which will contain $\{\langle store name : position \rangle\}$ analyzing whether the environment in which they are executed is `enumext*` or `enumext`.

```

2946 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_i:
2947 {
2948   \bool_if:NT \g__enumext_starred_bool
2949   {
2950     \tl_set_eq:NN \l__enumext_label_copy_i_tl \l__enumext_label_copy_vii_tl
2951   }
2952   \int_compare:nNnT { \l__enumext_keyans_pic_level_int } = { 1 }
2953   {
2954     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2955     { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_vi_tl }

```

```

2956     }
2957     \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
2958     {
2959         \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2960         { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_v_tl }
2961     }
2962     \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
2963     {
2964         \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2965         { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_viii_tl }
2966     }
2967     \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
2968     {
2969         \l__enumext_store_name_tl \c_colon_str
2970         \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
2971     }
2972     \__enumext_keyans_store_ref_aux_ii:
2973 }

```

Now auxiliary function `__enumext_keyans_store_ref_aux_ii:` save the result in the variable `\l__enumext_write_aux_file_tl` and finally we write in the `.aux` file.

```

2974 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_ii:
2975 {
2976     \tl_put_right:Ne \l__enumext_write_aux_file_tl
2977     {
2978         \__enumext_newlabel:nn
2979         { \exp_not:V \l__enumext_newlabel_arg_one_tl }
2980         { \l__enumext_newlabel_arg_two_tl }
2981     }
2982     \l__enumext_write_aux_file_tl
2983 }

```

(End of definition for `__enumext_keyans_store_ref:`, `__enumext_keyans_store_ref_aux_i:`, and `__enumext_keyans_store_ref_aux_ii:`.)

12.32.3 Storing content in sequence

```

\__enumext_keyans_addto_seq:n
\__enumext_keyans_addto_seq_link:

```

The function `__enumext_keyans_addto_seq:n` will pass the contents of the current *⟨label⟩* `\l__enumext_label_v_tl` for the *keyans* environment and the `\l__enumext_label_vi_tl` for the *keyanspic* environment when using `\item*` and `\anspic*`, followed by the *⟨contents⟩* of the optional argument of both commands to the `\l__enumext_store_current_label_tl` variable to the sequence defined by the *save-ans* key.

```

2984 \cs_new_protected:Npn \__enumext_keyans_addto_seq:n #1
2985 {
2986     \tl_clear:N \l__enumext_store_current_label_tl
2987     \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
2988     {
2989         \tl_put_right:Ne \l__enumext_store_current_label_tl { \item \l__enumext_label_vi_tl }
2990     }
2991     {
2992         \tl_put_right:Ne \l__enumext_store_current_label_tl { \item \l__enumext_label_v_tl }
2993     }
2994     \tl_if_novalue:nF { #1 }
2995     {
2996         \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_tl
2997         {
2998             \tl_put_right:Ne \l__enumext_store_current_label_tl
2999             {
3000                 \l__enumext_store_keyans_item_opt_sep_tl
3001             }
3002         }
3003         \tl_put_right:Ne \l__enumext_store_current_label_tl { #1 }
3004     }
3005     \__enumext_keyans_addto_seq_link:
3006 }

```

Checks if the *save-ref* key is active along with the *hyperref* package load, if both conditions are met, it will create the `\hyperlink` and then store using the `__enumext_store_addto_seq:V` function. Finally, copy the contents of the variable `\l__enumext_store_current_label_tl` into the global variable `\g__enumext_check_ans_item_tl` to be used by the function `__enumext_check_starred_cmd:n` and increment the value of the integer variable `\g__enumext_item_anskey_int` handled by the *check-ans* key.

```

3007 \cs_new_protected:Nn \__enumext_keyans_addto_seq_link:
3008 {
3009   \bool_lazy_and:nnT
3010     { \bool_if_p:N \l__enumext_store_ref_key_bool }
3011     { \bool_if_p:N \l__enumext_hyperref_bool }
3012   {
3013     \tl_put_right:Ne \l__enumext_store_current_label_tl
3014     {
3015       \hfill \exp_not:N \hyperlink
3016       {
3017         \exp_not:V \l__enumext_newlabel_arg_one_tl
3018       }
3019       { \exp_not:V \l__enumext_mark_ref_sym_tl }
3020     }
3021   }
3022   \__enumext_store_addto_seq:V \l__enumext_store_current_label_tl
3023   \bool_if:NT \l__enumext_check_answers_bool
3024   {
3025     \int_gincr:N \g__enumext_item_anskey_int
3026   }
3027 }

```

(End of definition for `__enumext_keyans_addto_seq:n` and `__enumext_keyans_addto_seq_link:.`)

12.32.4 The show-ans and show-pos keys for keyans and keyanspic

The code is very similar to the `\anskey` code, but, if I change the order of the operations the counter off `\label` are incorrect.

```

\__enumext_keyans_show_left:n
\__enumext_keyans_show_ans:
\__enumext_keyans_show_pos:
\__enumext_keyans_show_item_opt:

```

Common function to show *starred commands* `\item*` and `\position` of stored content in `\prop list` for `keyans` and `keyanspic`. Need add `1` to `\g__enumext_<store name>_prop` for show-pos key.

```

3028 \cs_new_protected:Npn \__enumext_keyans_show_left:n #1
3029 {
3030   \tl_if_novalue:nF { #1 }
3031   {
3032     \tl_set:Ne \l__enumext_store_current_opt_arg_tl { #1 }
3033   }
3034   \bool_if:NT \l__enumext_show_answer_bool
3035   {
3036     \__enumext_keyans_show_ans:
3037   }
3038   \bool_if:NT \l__enumext_show_position_bool
3039   {
3040     \__enumext_keyans_show_pos:
3041   }
3042 }
3043 \cs_new_protected:Nn \__enumext_keyans_show_item_opt:
3044 {
3045   \tl_if_empty:NF \l__enumext_store_current_opt_arg_tl
3046   {
3047     \bool_lazy_or:nnT
3048       { \bool_if_p:N \l__enumext_show_answer_bool }
3049       { \bool_if_p:N \l__enumext_show_position_bool }
3050     {
3051       \__enumext_keyans_wrapper_opt:n { \l__enumext_store_current_opt_arg_tl } \c_space_tl
3052     }
3053   }
3054 }
3055 \cs_new_protected:Nn \__enumext_keyans_show_ans:
3056 {
3057   \bool_if:NT \l__enumext_starred_bool
3058   {
3059     \dim_set_eq:NN \l__enumext_labelwidth_i_dim \l__enumext_labelwidth_vii_dim
3060     \dim_set_eq:NN \l__enumext_labelsep_i_dim \l__enumext_labelsep_vii_dim
3061   }
3062   \tl_put_left:Nn \l__enumext_label_v_tl
3063   {
3064     \__enumext_print_keyans_box:NN
3065     \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
3066   }
3067 }
3068 \cs_new_protected:Nn \__enumext_keyans_show_pos:

```

```

3069 {
3070   \bool_if:NT \l__enumext_starred_bool
3071   {
3072     \dim_set_eq:NN \l__enumext_labelwidth_i_dim \l__enumext_labelwidth_vii_dim
3073     \dim_set_eq:NN \l__enumext_labelsep_i_dim \l__enumext_labelsep_vii_dim
3074   }
3075   \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
3076   {
3077     \tl_set:Ne \l__enumext_mark_answer_sym_tl
3078     {
3079       \group_begin:
3080       \exp_not:N \normalfont
3081       \exp_not:N \footnotesize [ \int_eval:n
3082         {
3083           \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
3084         }
3085       ]
3086       \group_end:
3087     }
3088   }
3089   {
3090     \tl_set:Ne \l__enumext_mark_answer_sym_tl
3091     {
3092       \group_begin:
3093       \exp_not:N \normalfont
3094       \exp_not:N \footnotesize [ \int_eval:n
3095         {
3096           \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } + 1
3097         }
3098       ]
3099       \group_end:
3100     }
3101   }
3102   \tl_put_left:Nn \l__enumext_label_v_tl
3103   {
3104     \__enumext_print_keyans_box:NN
3105     \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
3106   }
3107 }

```

(End of definition for `__enumext_keyans_show_left:n` and others.)

12.33 Redefining `\item` and `\makeLabel` in enumext

Redefining the `\item` command is not as simple as I thought. This command works in conjunction with the `\makeLabel` command so I have to redefine both of them, in addition to this, we will have to use a couple of *global* variables to pass the values from one command to the other.

The `\item` and `\item[⟨custom⟩]` commands work in the usual way on `enumext` and we will add `\item*`, `\item*[⟨symbol⟩]` and `\item*[⟨symbol⟩][⟨offset⟩]`.

`__enumext_default_item:n` First we will see if the optional argument is present, if it is NOT present we will check the state of the variable `\l__enumext_check_answers_bool` set by the key `no-store`, set the boolean variable `\l__enumext_wrap_label_X_bool` to “true” for the key `wrap-label` and execute `__enumext_item_std:w` and the key `itemindent`, otherwise we will check the state of the boolean variable `\l__enumext_wrap_label_opt_X_bool` set by the key `wrap-label*` and execute `__enumext_item_std:w` with the optional argument and the key `itemindent`.

```

3108 \cs_new_protected:Npn \__enumext_default_item:n #1
3109 {
3110   \tl_if_novalue:nTF {#1}
3111   {
3112     \bool_if:NT \l__enumext_check_answers_bool
3113     {
3114       \int_gincr:N \g__enumext_item_number_int
3115       \bool_set_true:N \l__enumext_item_number_bool
3116     }
3117     \bool_set_true:c { \l__enumext_wrap_label_ \__enumext_level: _bool }
3118     \__enumext_item_std:w \tl_use:c { \l__enumext_fake_item_indent_ \__enumext_level: _tl }
3119   }
3120   {
3121     \bool_set_eq:cc
3122     { \l__enumext_wrap_label_ \__enumext_level: _bool }

```

```

3123         { \__enumext_wrap_label_opt_ \__enumext_level: _bool }
3124         \__enumext_item_std:w [#1] \tl_use:c { \__enumext_fake_item_indent_ \__enumext_level: _tl
3125     }
3126 }

```

(End of definition for __enumext_default_item:n.)

__enumext_starred_item:nn
__enumext_item_star_exec:

The `\item*`, `\item*[\langle symbol \rangle]` and `\item*[\langle symbol \rangle][\langle offset \rangle]` works like the *numbered* `\item`, but placing a *\langle symbol \rangle* to the “left” of the *\langle label \rangle* separated from it by the value the second optional argument *\langle offset \rangle*.

#1: __enumext_item_symbol_X_tl

#2: __enumext_item_symbol_sep_X_dim

First we will make a copy of `__enumext_item_symbol_X_tl` which is set by the key `item-sym*` or passed as “first” optional argument in the global variable `\g__enumext_item_symbol_aux_tl`, followed by setting the variable `__enumext_item_symbol_sep_X_dim` set by the key `item-pos*` or by the “second” optional argument, then we will see the state of the variable `__enumext_check_answers_bool` set by the key `no-store`, set the boolean variable `__enumext_wrap_label_X_bool` to “true” for the key `wrap-label` and execute `__enumext_item_std:w` and the key `itemindent`.

```

3127 \cs_new_protected:Npn \__enumext_starred_item:nn #1 #2
3128 {
3129     \tl_if_novalue:nTF {#1}
3130     {
3131         \tl_gset_eq:Nc
3132         \g__enumext_item_symbol_aux_tl { \__enumext_item_symbol_ \__enumext_level: _tl }
3133     }
3134     {
3135         \tl_gset:Nn \g__enumext_item_symbol_aux_tl {#1}
3136     }
3137     \tl_if_novalue:nTF {#2}
3138     {
3139         \dim_set_eq:cc
3140         { \__enumext_item_symbol_sep_ \__enumext_level: _dim }
3141         { \__enumext_labelsep_ \__enumext_level: _dim }
3142     }
3143     {
3144         \dim_set:cn { \__enumext_item_symbol_sep_ \__enumext_level: _dim } {#2}
3145     }
3146     \bool_if:NT \__enumext_check_answers_bool
3147     {
3148         \int_gincr:N \g__enumext_item_number_int
3149         \bool_set_true:N \__enumext_item_number_bool
3150     }
3151     \bool_set_true:c { \__enumext_wrap_label_ \__enumext_level: _bool }
3152     \__enumext_item_std:w \tl_use:c { \__enumext_fake_item_indent_ \__enumext_level: _tl }
3153 }

```

The function `__enumext_item_star_exec:` will be responsible for executing `\item*` for the `enumext` environment.

```

3154 \cs_new_protected:Nn \__enumext_item_star_exec:
3155 {
3156     \tl_if_empty:cF { \__enumext_item_symbol_ \__enumext_level: _tl }
3157     {
3158         \mode_leave_vertical:
3159         \skip_horizontal:n { -\dim_use:c { \__enumext_item_symbol_sep_ \__enumext_level: _dim } }
3160         \hbox_overlap_left:n { \g__enumext_item_symbol_aux_tl }
3161         \skip_horizontal:n { \dim_use:c { \__enumext_item_symbol_sep_ \__enumext_level: _dim } }
3162     }
3163 }

```

(End of definition for __enumext_starred_item:nn and __enumext_item_star_exec:.)

__enumext_redefine_item:

The function `__enumext_redefine_item:` will redefine the `\item` command in the `enumext` environment adding `\item*`.

```

3164 \cs_new_protected:Nn \__enumext_redefine_item:
3165 {
3166     \RenewDocumentCommand \item { s o o }
3167     {
3168         \bool_if:nTF {##1}
3169         {
3170             \__enumext_starred_item:nn {##2} {##3}

```

```

3171     }
3172     { \__enumext_default_item:n {##2} }
3173   }
3174 }

```

(End of definition for __enumext_redefine_item:.)

__enumext_make_label:
 __enumext_make_label_std:
 __enumext_make_label_box:

The function __enumext_make_label: redefine \makeLabel for the keys align, font, wrap-label, wrap-label* and \item* for enumext environment.

```

3175 \cs_new_protected:Nn \__enumext_make_label:
3176 {
3177   \IfDocumentMetadataTF
3178   {
3179     \__enumext_make_label_box:
3180   }
3181   { \__enumext_make_label_std: }
3182 }
3183 \cs_new_protected:Nn \__enumext_make_label_std:
3184 {
3185   \RenewDocumentCommand \makeLabel { m }
3186   {
3187     \tl_use:c { l__enumext_label_fill_left_ \__enumext_level: _tl }
3188     \tl_use:c { l__enumext_label_font_style_ \__enumext_level: _tl }
3189     \bool_if:cTF { l__enumext_wrap_label_ \__enumext_level: _bool }
3190     {
3191       \__enumext_item_star_exec:
3192       \use:c { __enumext_wrapper_label_ \__enumext_level: :n } { ##1 }
3193     }
3194     { ##1 }
3195     \tl_use:c { l__enumext_label_fill_right_ \__enumext_level: _tl }
3196     \tl_gclear:N \g__enumext_item_symbol_aux_tl
3197   }
3198 }
3199 \cs_new_protected:Nn \__enumext_make_label_box:
3200 {
3201   \RenewDocumentCommand \makeLabel { m }
3202   {
3203     \makebox
3204     [ \dim_use:c { l__enumext_labelwidth_ \__enumext_level: _dim } ]
3205     [ \str_use:c { l__enumext_align_label_pos_ \__enumext_level: _str } ]
3206     {
3207       \tl_use:c { l__enumext_label_font_style_ \__enumext_level: _tl }
3208       \bool_if:cTF { l__enumext_wrap_label_ \__enumext_level: _bool }
3209       {
3210         \__enumext_item_star_exec:
3211         \use:c { __enumext_wrapper_label_ \__enumext_level: :n } { ##1 }
3212       }
3213       { ##1 }
3214       \tl_gclear:N \g__enumext_item_symbol_aux_tl
3215     }
3216   }
3217 }

```

(End of definition for __enumext_make_label:, __enumext_make_label_std:, and __enumext_make_label_box:.)

🔗 This functions are passed to __enumext_list_arg_two_X: used in the definition of the enumext environment (§12.38).

12.34 Setting item-sym* and item-pos* keys

In order to have a cleaner implementation of \item* for the enumext and enumext* environments it is best to define a couple of keys that allow us to control and set by default the ⟨symbol⟩ and its ⟨offset⟩.

item-sym*
 item-pos*

Define and set item-sym* and item-pos* keys for enumext and enumext*.

```

3218 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
3219 {
3220   \keys_define:nn { enumext / #1 }
3221   {
3222     item-sym* .tl_set:c = { l__enumext_item_symbol_#2_tl },
3223     item-sym* .value_required:n = true,
3224     item-sym* .initial:n = {${\star$}},
3225     item-pos* .dim_set:c = { l__enumext_item_symbol_sep_#2_dim },
3226     item-pos* .value_required:n = true,
3227   }

```

```

3228     }
3229     \clist_map_inline:nn
3230     {
3231         {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {enumext*}{vii}
3232     }
3233     { \__enumext_tmp:nn #1 }

```

(End of definition for `item-sym*` and `item-pos*`.)

12.35 Handling unknown keys

At this point in the code I already know that I will not add more `<keys>` and since I have already been quite *paranoid and restrictive* with the definitions of environments and commands, the only thing left to do is do it with the `<keys>` (you have to be consistent in life).

12.35.1 Handling unknown keys for `keyans` and `keyans*`

Define and set `unknown` key for `keyans` and `keyans*` environments.

```

unknown
\__enumext_keyans_unknown_keys:n
\__enumext_keyans_unknown_keys:nn
3234 \cs_set_protected:Npn \__enumext_tmp:n #1
3235 {
3236     \keys_define:nn { enumext / #1 }
3237     {
3238         unknown .code:n = { \__enumext_keyans_unknown_keys:n {#1} }
3239     }
3240 }
3241 \clist_map_inline:nn { keyans, keyans* } { \__enumext_tmp:n {#1} }

```

Internal functions for handling `unknown` key.

```

3242 \cs_new_protected:Npn \__enumext_keyans_unknown_keys:n #1
3243 {
3244     \exp_args:NV \__enumext_keyans_unknown_keys:nn \l_keys_key_str {#1}
3245 }
3246 \cs_new_protected:Npn \__enumext_keyans_unknown_keys:nn #1#2
3247 {
3248     \tl_if_blank:nTF {#2}
3249     {
3250         \msg_error:nnn { enumext } { keyans-unknown-key } {#1}
3251     }
3252     {
3253         \msg_error:nnnn { enumext } { keyans-unknown-key-value } {#1} {#2}
3254     }
3255 }

```

(End of definition for `unknown`, `__enumext_keyans_unknown_keys:n`, and `__enumext_keyans_unknown_keys:nn`.)

12.35.2 Handling unknown keys for `enumext*`

Define and set `unknown` key for `enumext*` environment.

```

unknown
\__enumext_starred_unknown_keys:n
\__enumext_starred_unknown_keys:nn
3256 \keys_define:nn { enumext / enumext* }
3257 {
3258     unknown .code:n = { \__enumext_starred_unknown_keys:n {#1} }
3259 }

```

Internal functions for handling `unknown` key.

```

3260 \cs_new_protected:Npn \__enumext_starred_unknown_keys:n #1
3261 {
3262     \exp_args:NV \__enumext_starred_unknown_keys:nn \l_keys_key_str {#1}
3263 }
3264 \cs_new_protected:Npn \__enumext_starred_unknown_keys:nn #1#2
3265 {
3266     \tl_if_blank:nTF {#2}
3267     {
3268         \msg_error:nnn { enumext } { starred-unknown-key } {#1}
3269     }
3270     {
3271         \msg_error:nnnn { enumext } { starred-unknown-key-value } {#1} {#2}
3272     }
3273 }

```

(End of definition for `unknown`, `__enumext_starred_unknown_keys:n`, and `__enumext_starred_unknown_keys:nn`.)

12.35.3 Handling unknown keys for enumext

unknown

Defines and set the key `unknown` for `enumext` environment.

```

3274 \cs_set_protected:Npn \__enumext_tmp:n #1
3275 {
3276   \keys_define:nn { enumext / #1 }
3277   {
3278     unknown .code:n = { \__enumext_standar_unknown_keys:n {##1} }
3279   }
3280 }
3281 \clist_map_inline:nn { level-1,level-2,level-3,level-4 } { \__enumext_tmp:n {#1} }

```

Internal functions for handling `unknown` key.

```

3282 \cs_new_protected:Npn \__enumext_standar_unknown_keys:n #1
3283 {
3284   \exp_args:NV \__enumext_standar_unknown_keys:nn \l_keys_key_str {#1}
3285 }
3286 \cs_new_protected:Npn \__enumext_standar_unknown_keys:nn #1#2
3287 {
3288   \tl_if_blank:nTF {#2}
3289   {
3290     \msg_error:nnn { enumext } { standar-unknown-key } {#1}
3291   }
3292   {
3293     \msg_error:nnnn { enumext } { standar-unknown-key-value } {#1} {#2}
3294   }
3295 }

```

(End of definition for `unknown`, `__enumext_standar_unknown_keys:n`, and `__enumext_standar_unknown_keys:nn`.)

12.36 Redefining `\item` and `\makeLabel` in keyans

The `\item` and `\item[⟨custom⟩]` commands work in the usual way in `keyans`, but the `\item*` and `\item*[⟨content⟩]` commands *store* the current `⟨label⟩` next to the `⟨content⟩` if it is present in the `⟨sequence⟩` and `⟨prop list⟩` defined by `save-ans` key.

`__enumext_keyans_default_item:n`

The function `__enumext_keyans_default_item:n` executes the original behavior of the `\item`.

```

3296 \cs_new_protected:Npn \__enumext_keyans_default_item:n #1
3297 {
3298   \tl_if_novalue:nTF { #1 }
3299   {
3300     \bool_set_true:N \__enumext_wrap_label_v_bool
3301     \__enumext_item_std:w \tl_use:N \__enumext_fake_item_indent_v_tl
3302   }
3303   {
3304     \bool_set_eq:NN \__enumext_wrap_label_v_bool \__enumext_wrap_label_opt_v_bool
3305     \__enumext_item_std:w [#1] \tl_use:N \__enumext_fake_item_indent_v_tl
3306   }
3307 }

```

(End of definition for `__enumext_keyans_default_item:n`.)

`__enumext_keyans_starred_item:n`

The function `__enumext_keyans_starred_item:n` which will make a temporary copy of the current `⟨label⟩`, execute the `show-ans` or `show-pos` keys using the function `__enumext_keyans_show_left:n` and will display the contents of that item using the internal copy `__enumext_item_std:w`, this is necessary to prevent incrementing the current “*counter*” of the original `⟨label⟩`.

```

3308 \cs_new_protected:Npn \__enumext_keyans_starred_item:n #1
3309 {
3310   \tl_set_eq:NN \__enumext_store_current_label_tmp_tl \__enumext_label_v_tl
3311   \__enumext_keyans_show_left:n { #1 }
3312   \bool_set_true:N \__enumext_wrap_label_v_bool
3313   \__enumext_item_std:w \tl_use:N \__enumext_fake_item_indent_v_tl \__enumext_keyans_show_item

```

Recover the original value of the current `⟨label⟩` and *store* it first in the `⟨prop list⟩` (including the optional argument), run the internal “*label and ref*” system if the `save-ref` key is active and finally *store* it in the `⟨sequence⟩`.

```

3314   \tl_set_eq:NN \__enumext_label_v_tl \__enumext_store_current_label_tmp_tl
3315   \__enumext_keyans_addto_prop:n { #1 }
3316   \__enumext_keyans_store_ref:
3317   \__enumext_keyans_addto_seq:n { #1 }
3318   \int_gincr:N \g__enumext_check_starred_cmd_int
3319 }

```

(End of definition for `__enumext_keyans_starred_item:n`.)

`\item*` The function `__enumext_keyans_redefine_item:` is responsible for adding the *starred* and *optional* argument by the `__enumext_list_arg_two_v:` function in the definition of the `keyans` environment. Here we need to use `\peek_remove_spaces:n` to prevent an unwanted space when using `\item*` in conjunction with the `itemindent` key.

```

3320 \cs_new_protected:Nn \__enumext_keyans_redefine_item:
3321 {
3322   \RenewDocumentCommand \item { s o }
3323   {
3324     \bool_if:nTF {##1}
3325     {
3326       \peek_remove_spaces:n
3327       {
3328         \__enumext_keyans_starred_item:n {##2}
3329       }
3330     }
3331     {
3332       \__enumext_keyans_default_item:n {##2}
3333     }
3334   }
3335 }

```

(End of definition for `\item*` and `__enumext_keyans_redefine_item:`. This function is documented on page 14.)

`__enumext_keyans_make_label:` The function `__enumext_keyans_make_label:` redefine `\makeLabel` for the keys `align`, `font`, `wrap-label`, `wrap-label*` and `\item*` for `keyans` environment.

```

\__enumext_keyans_make_label_std:
\__enumext_keyans_make_label_box:
3336 \cs_new_protected:Nn \__enumext_keyans_make_label:
3337 {
3338   \IfDocumentMetadataTF
3339   {
3340     \__enumext_keyans_make_label_box:
3341   }
3342   { \__enumext_keyans_make_label_std: }
3343 }
3344 \cs_new_protected:Nn \__enumext_keyans_make_label_std:
3345 {
3346   \RenewDocumentCommand \makeLabel { m }
3347   {
3348     \tl_use:N \__enumext_label_fill_left_v_tl
3349     \tl_use:N \__enumext_label_font_style_v_tl
3350     \bool_if:NTF \__enumext_wrap_label_v_bool
3351     {
3352       \__enumext_wrapper_label_v:n { ##1 }
3353     }
3354     { ##1 }
3355     \tl_use:N \__enumext_label_fill_right_v_tl
3356   }
3357 }
3358 \cs_new_protected:Nn \__enumext_keyans_make_label_box:
3359 {
3360   \RenewDocumentCommand \makeLabel { m }
3361   {
3362     \makebox[ \__enumext_labelwidth_v_dim ][ \__enumext_align_label_pos_v_str ]
3363     {
3364       \tl_use:N \__enumext_label_font_style_v_tl
3365       \bool_if:NTF \__enumext_wrap_label_v_bool
3366       {
3367         \__enumext_wrapper_label_v:n { ##1 }
3368       }
3369       { ##1 }
3370     }
3371   }
3372 }

```

(End of definition for `__enumext_keyans_make_label:`, `__enumext_keyans_make_label_std:`, and `__enumext_keyans_make_label_box:`.)

- This functions are passed to `__enumext_list_arg_two_v:` used in the definition of the `keyans` environment (§12.37.2).

12.37 Second argument of the lists

At this point of the code we have already programmed most the necessary tools to create a custom `list` environment, remember that the function `__enumext_start_list:nn` takes two arguments, the first one we have ready, the second one we will define for all the levels of the environment `enumext` and the environment `keyans`.

12.37.1 Calculation of `\leftmargin` and `\itemindent`

Consider the figure 9 where the default margins (on the left) of a list are represented.




Figure 9: Representation of standard horizontal lengths in `list` environment.

The idea is to have control over these margins so that our list does not overlap the left margin of the page. The key relationship is that the right edge of the `\labelsep` equals the right edge of the `\itemindent`, so that the left edge of the `label` box is at `\leftmargin + \itemindent` minus `\labelwidth + \labelsep`. Thus, the handling of the margins by the package will be as shown in the figure 10.




Figure 10: Representation of horizontal lengths concept in list in `enumext`.

Where the default values will look like in the figure 11.




Figure 11: Default horizontal lengths in `enumext`.

```
\__enumext_calc_hspace:NNNNNNN
\__enumext_calc_hspace:ccccccc
```

The function `__enumext_calc_hspace:NNNNNNN` takes seven arguments to be able to determine horizontal spaces for all list environment:

```
#1: \l__enumext_labelwidth_X_dim      #2: \l__enumext_labelsep_X_dim
#3: \l__enumext_listoffset_X_dim      #4: \l__enumext_leftmargin_tmp_X_dim
#5: \l__enumext_leftmargin_X_dim      #6: \l__enumext_itemindent_X_dim
#7: \l__enumext_leftmargin_tmp_X_bool
```

And returns the “adjusted” values of `\leftmargin` and `\itemindent`.

This function is passed to `__enumext_list_arg_two_X:` which is used in the definition of the `enumext` and `keyans` environments (§12.37.2).

```
3373 \cs_new_protected:Npn \__enumext_calc_hspace:NNNNNNN #1 #2 #3 #4 #5 #6 #7
3374 {
3375   \dim_compare:nNtT { #1 } < { \c_zero_dim }
3376   {
3377     \msg_warning:nnnV { enumext } { width-non-positive } { labelwidth } { #1 }
3378     \dim_set:Nn #1 { \dim_abs:n { #1 } }
3379   }
3380   \dim_compare:nNtT { #2 } < { \c_zero_dim }
3381   {
3382     \msg_warning:nnnV { enumext } { width-negative } { labelsep } { #2 }
3383     \dim_set:Nn #2 { \dim_abs:n { #2 } }
3384   }
3385 }
```

If no value has been passed to the `labelwidth` and `labelsep` keys we set the default values for `\l__enumext_leftmargin_tmp_X_dim`.

```
3385 \bool_if:nF #7 { \dim_set:Nn #4 { #1 + #2 } }
```

We now analyze the cases and set the values for `\leftmargin` and `\itemindent`.

```

3386 \dim_compare:nNnTF { #4 } < { \c_zero_dim }
3387 {
3388   \dim_set:Nn #6 { #1 + #2 - #4 }
3389   \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
3390 }
3391 {
3392   \dim_compare:nNnT { #4 } = { #1 + #2 }
3393   { \dim_set:Nn #6 { \c_zero_dim } }
3394   \dim_compare:nNnT { #4 } < { #1 + #2 }
3395   { \dim_set:Nn #6 { #1 + #2 - #4 } }
3396   \dim_compare:nNnT { #4 } > { #1 + #2 }
3397   {
3398     \dim_set:Nn #6 { -#1 - #2 + #4 }
3399     \dim_set:Nn #6 { #6*-1 }
3400   }
3401   \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
3402 }
3403 }
3404 \cs_generate_variant:Nn \__enumext_calc_hspace:NNNNNNN { cccccc }

```

(End of definition for `__enumext_calc_hspace:NNNNNNN`.)

12.37.2 Setting second argument of the lists

We will “not set” `\leftmargini`, `\leftmarginii`, `\leftmarginiii` or `\leftmarginiv`, in this case, we will directly set the parameters for vertical and horizontal list spacing per level.

```

3405 \cs_set_protected:Npn \__enumext_tmp:n #1
3406 {
3407   \cs_new_protected:cpn { __enumext_list_arg_two_#1: }
3408   {
3409     \__enumext_calc_hspace:ccccc
3410     { \__enumext_labelwidth_#1_dim } { \__enumext_labelsep_#1_dim }
3411     { \__enumext_listoffset_#1_dim } { \__enumext_leftmargin_tmp_#1_dim }
3412     { \__enumext_leftmargin_#1_dim } { \__enumext_itemindent_#1_dim }
3413     { \__enumext_leftmargin_tmp_#1_bool }
3414     \clist_map_inline:nn
3415       { labelsep, labelwidth, itemindent, leftmargin, rightmargin, listparindent }
3416       { \dim_set_eq:cc {####1} { \__enumext_####1_#1_dim } }
3417     \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
3418       { \skip_set_eq:cc {####1} { \__enumext_####1_#1_skip } }
3419     \usecounter { enumX#1 }
3420     \setcounter { enumX#1 } { \int_eval:n { \int_use:c { \__enumext_start_#1_int } - 1 } }
3421     \str_if_eq:nnTF {#1} { v }
3422     {
3423       \__enumext_keyans_redefine_item:
3424       \__enumext_keyans_make_label:
3425       \__enumext_keyans_ref:
3426       \__enumext_keyans_fake_item:
3427       \bool_if:cT { \__enumext_show_length_#1_bool }
3428       {
3429         \msg_term:nnnn { enumext } { list-lengths-not-nested } { v } { keyans }
3430       }
3431     }
3432     {
3433       \__enumext_redefine_item:
3434       \__enumext_make_label:
3435       \__enumext_standar_ref:
3436       \__enumext_fake_item:
3437       \bool_if:cT { \__enumext_show_length_#1_bool }
3438       {
3439         \msg_term:nnne { enumext } { list-lengths } {#1} { \int_use:N \__enumext_level_int }
3440       }
3441     }
3442   }
3443 }
3444 \clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }

```

(End of definition for `__enumext_list_arg_two_i: and others`.)

For the horizontal environments `enumext*` and `keyans*` the implementation is similar, but, the value of `\partopsep` is always `0pt`. At this point we will modify the `parsep` key to make it take the value of the

`itemsep` key and later, in the environment definition, we will modify `parindent` to make it set the value of `listparindent` and `parsep` to set the value of `\parskip` locally.

```

3445 \cs_set_protected:Npn \__enumext_tmp:n #1
3446 {
3447   \cs_new_protected:cpn { \__enumext_list_arg_two_#1: }
3448   {
3449     \bool_set_true:c { l__enumext_leftmargin_tmp_#1_bool }
3450     \dim_zero:c { l__enumext_leftmargin_tmp_#1_dim }
3451     \__enumext_calc_hspace:ccccc
3452     { l__enumext_labelwidth_#1_dim } { l__enumext_labelsep_#1_dim }
3453     { l__enumext_listoffset_#1_dim } { l__enumext_leftmargin_tmp_#1_dim }
3454     { l__enumext_leftmargin_#1_dim } { l__enumext_itemindent_#1_dim }
3455     { l__enumext_leftmargin_tmp_#1_bool }
3456     \clist_map_inline:nn
3457       { labelsep, labelwidth, itemindent, leftmargin, rightmargin, listparindent }
3458       { \dim_set_eq:cc {###1} { l__enumext_###1_#1_dim } }
3459     \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
3460       { \skip_set_eq:cc {###1} { l__enumext_###1_#1_skip } }
3461     \skip_set_eq:Nc \parsep { l__enumext_itemsep_#1_skip }
3462     \skip_zero:N \partopsep
3463     \usecounter { enumX#1 }
3464     \setcounter { enumX#1 } { \int_eval:n { \int_use:c { l__enumext_start_#1_int } - 1 } }
3465     \__enumext_starred_ref:
3466     \str_if_eq:nnTF {#1} { vii }
3467       {
3468         \__enumext_fake_item_vii:
3469         \bool_if:cT { l__enumext_show_length_vii_bool }
3470           { \msg_term:nnnn { enumext } { list-lengths-not-nested } { vii } { enumext* } }
3471       }
3472       {
3473         \__enumext_fake_item_viii:
3474         \bool_if:cT { l__enumext_show_length_#1_bool }
3475           { \msg_term:nnnn { enumext } { list-lengths-not-nested } { #1 } { keyans* } }
3476       }
3477   }
3478 }
3479 \clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `__enumext_list_arg_two_vii:` and `__enumext_list_arg_two_viii:`)

12.38 The environment `enumext`

`enumext` We create the `enumext` environment based on `list` environment by levels.

```

3480 \NewDocumentEnvironment{enumext}{0}{}
3481 {
3482   \__enumext_safe_exec:
3483   \__enumext_parse_keys:n {#1}
3484   \__enumext_before_list:
3485   \__enumext_start_store_level:
3486   \__enumext_start_list:nn
3487     { \tl_use:c { l__enumext_label_ \__enumext_level: _tl } }
3488     {
3489       \use:c { \__enumext_list_arg_two_ \__enumext_level: : }
3490       \__enumext_before_keys_exec:
3491     }
3492   \__enumext_set_item_width:
3493   \__enumext_after_args_exec:
3494 }
3495 {
3496   \__enumext_after_list:
3497 }

```

(End of definition for `enumext`. This function is documented on page 4.)

`__enumext_set_item_width:` The function `__enumext_set_item_width:` will set the value of `\itemwidth` taking into account the value established by the `list-offset` key for each level of the environment.

```

3498 \cs_new_protected:Nn \__enumext_set_item_width:
3499 {
3500   \dim_set:Nn \itemwidth
3501   {
3502     \linewidth

```

```

3503     }
3504     \dim_compare:nT
3505     {
3506         \dim_use:c { \l__enumext_listoffset_ \l__enumext_level: _dim } != \c_zero_dim
3507     }
3508     {
3509         \dim_sub:Nn \itemwidth
3510         {
3511             \dim_use:c { \l__enumext_listoffset_ \l__enumext_level: _dim }
3512         }
3513     }
3514 }

```

(End of definition for \l__enumext_set_item_width:.)

`\l__enumext_safe_exec:` The `\l__enumext_safe_exec:` function first call the function `\l__enumext_internal_mini_page:` to create the environment `\l__enumext_mini_page`, then the function `\l__enumext_is_not_nested:` which sets `\l__enumext_standar_bool` to “true” if we are not nested within `enumext*`, we will increment `\l__enumext_level_int` to restrict nesting of the environment, set `\l__enumext_standar_bool` to “true” and finally call the function `\l__enumext_is_on_first_level:` which sets `\l__enumext_standar_first_bool` to “true” only if the environment is not nested and we are at the “first level”.

```

3515 \cs_new_protected:Nn \l__enumext_safe_exec:
3516 {
3517     \l__enumext_internal_mini_page:
3518     \l__enumext_is_not_nested:
3519     \int_incr:N \l__enumext_level_int
3520     \int_compare:nNnT { \l__enumext_level_int } > { 4 }
3521     { \msg_fatal:nn { enumext } { list-too-deep } }
3522     \bool_set_true:N \l__enumext_standar_bool
3523     \bool_set_false:N \l__enumext_starred_bool
3524     \l__enumext_is_on_first_level:
3525 }

```

(End of definition for \l__enumext_safe_exec:.)

`\l__enumext_parse_keys:n` The `\l__enumext_parse_store_keys:n` function first we will clear the variable `\l__enumext_series_str` used by the key `series` and then we check if we are at the “first level”, if so we process the `⟨keys⟩` and then execute the function `\l__enumext_parse_series:n` used by the key `series` and call the function `\l__enumext_nested_base_line_fix:` used by the key `base-fix`, otherwise we will pass the `⟨keys⟩` to the inner levels of the environment then we execute the function `\l__enumext_store_active_keys:n` and reprocess the `⟨keys⟩` to pass them to the storage `⟨sequence⟩` if the key `save-key` is not active.

```

3526 \cs_new_protected:Npn \l__enumext_parse_keys:n #1
3527 {
3528     \tl_if_novalue:nF {#1}
3529     {
3530         \str_clear:N \l__enumext_series_str
3531         \int_compare:nNnTF { \l__enumext_level_int } = { 1 }
3532         {
3533             \keys_set:nn { enumext / level-1 } {#1}
3534             \l__enumext_parse_series:n {#1}
3535             \l__enumext_nested_base_line_fix:
3536         }
3537         {
3538             \exp_args:Ne \keys_set:nn
3539             { enumext / level-\int_use:N \l__enumext_level_int } {#1}
3540         }
3541         \l__enumext_store_active_keys:n {#1}
3542     }
3543 }

```

(End of definition for \l__enumext_parse_keys:n.)

`\l__enumext_start_store_level:` The `\l__enumext_start_store_level:` and `\l__enumext_stop_store_level:` functions activate the level saving mechanism for storage in `⟨sequence⟩` for the command `\anskey` and the environment `anskey*`.

```

3544 \cs_new_protected:Nn \l__enumext_start_store_level:
3545 {
3546     \bool_lazy_all:nT
3547     {
3548         { \bool_if_p:N \l__enumext_store_active_bool }
3549         { \bool_not_p:n { \l__enumext_keyans_env_bool } }

```

```

3550     { \bool_if_p:N \g__enumext_standar_bool }
3551   }
3552   {
3553     \int_compare:nNtT { \l__enumext_level_int } > { 1 }
3554     {
3555       \bool_set_true:c { l__enumext_store_upper_level_ \__enumext_level: _bool }
3556       \__enumext_store_level_open:
3557     }
3558   }

```

If `enumext` are nested in `enumext*` add `__enumext_store_level_open:` to preserve the stored structure.

```

3559   \bool_lazy_all:nT
3560   {
3561     { \bool_if_p:N \l__enumext_store_active_bool }
3562     { \bool_not_p:n { \l__enumext_keyans_env_bool } }
3563     { \int_compare_p:nNt { \l__enumext_level_h_int } = { 1 } }
3564   }
3565   {
3566     \int_compare:nNtT { \l__enumext_level_int } > { 0 }
3567     {
3568       \bool_set_true:c { l__enumext_store_upper_level_ \__enumext_level: _bool }
3569       \__enumext_store_level_open:
3570     }
3571   }
3572 }

```

Close the stored structure.

```

3573 \cs_new_protected:Nn \__enumext_stop_store_level:
3574 {
3575   \bool_if:cT { l__enumext_store_upper_level_ \__enumext_level: _bool }
3576   {
3577     \__enumext_store_level_close:
3578   }
3579 }

```

(End of definition for `__enumext_start_store_level:` and `__enumext_stop_store_level:.`)

`__enumext_before_list:` The function `__enumext_before_list:` first calls the function `__enumext_vspace_above:` used by the keys `above` and `above*`, then calls the function `__enumext_before_args_exec:` used by the key `before*` and finally execute the function `__enumext_check_ans_active:` for the check answer mechanism.

```

3580 \cs_new_protected:Nn \__enumext_before_list:
3581 {
3582   \__enumext_vspace_above:
3583   \__enumext_before_args_exec:
3584   \__enumext_check_ans_active:

```

When the `mini-env` key is active it will set the value of the `\l__enumext_minipage_right_X_dim` to be the *width* of the `__enumext_mini_page` environment on the “*right side*”, using this value together with the value of the `\l__enumext_minipage_hsep_X_dim` set by the `mini-sep` key, the value of `\l__enumext_minipage_left_X_dim` will be set, which will be the *width* of `__enumext_mini_page` environment on the “*left side*”, always having a current `\linewidth` as *maximum width* between them.

```

3585   \dim_compare:nNtT
3586   { \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim } } > { \c_zero_dim }
3587   {
3588     \dim_set:cn { l__enumext_minipage_left_ \__enumext_level: _dim }
3589     {
3590       \linewidth
3591       - \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim }
3592       - \dim_use:c { l__enumext_minipage_hsep_ \__enumext_level: _dim }
3593     }

```

The boolean variable `\l__enumext_minipage_active_X_bool` will be activated and the integer variable `\g__enumext_minipage_stat_int` used by the `\miniright` command will be incremented, then the function `__enumext_minipage_add_space:` is called and the `__enumext_mini_page` environment on the “*left side*” will be initialized followed by the “*vertical spacing*” applied to preserve the “*baseline*” between the *left* and *right* side environments. After these actions, the function `__enumext_multicols_start:` is called to handle the `multicols` environment.

```

3594   \bool_set_true:c { l__enumext_minipage_active_ \__enumext_level: _bool }
3595   \int_gincr:N \g__enumext_minipage_stat_int
3596   \__enumext_minipage_add_space:
3597   \noindent
3598   \__enumext_mini_page{ \dim_use:c { l__enumext_minipage_left_ \__enumext_level: _dim } }

```



```

3599     }
3600     \__enumext_multicols_start:
3601 }

```

(End of definition for __enumext_before_list:.)

`__enumext_multicols_start:` The function `__enumext_multicols_start:` will start the `multicols` environment according to the value passed by the `columns` key, then set the default value for `\columnsep` when `columns-sep=0pt` and set the value of `\multicolsep` equal to zero and leave `\columnseprule` equal to zero for inner levels.

```

3602 \cs_new_protected:Nn \__enumext_multicols_start:
3603 {
3604     \int_compare:nNnT
3605     { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
3606     {
3607         \dim_compare:nNnT
3608         { \dim_use:c { l__enumext_columns_sep_ \__enumext_level: _dim } } = { \c_zero_dim }
3609         {
3610             \dim_set:cn { l__enumext_columns_sep_ \__enumext_level: _dim }
3611             {
3612                 ( \dim_use:c { l__enumext_labelwidth_ \__enumext_level: _dim }
3613                   + \dim_use:c { l__enumext_labelsep_ \__enumext_level: _dim }
3614                   ) / \int_use:c { l__enumext_columns_ \__enumext_level: _int }
3615                   - \dim_use:c { l__enumext_listoffset_ \__enumext_level: _dim }
3616             }
3617         }
3618         \dim_set_eq:Nc \columnsep { l__enumext_columns_sep_ \__enumext_level: _dim }
3619         \int_compare:nNnT { \l__enumext_level_int } > { 1 }
3620         {
3621             \dim_zero:N \columnseprule
3622         }
3623     }
3624 }

```

We will calculate the *vertical spacing* settings for the `multicols` environment using the function `__enumext_multi_addvspace:`, apply our “vertical adjust spacing”, then start the `multicols` environment.

```

3623     \bool_if:cF { l__enumext_minipage_active_ \__enumext_level: _bool }
3624     {
3625         \skip_zero:N \multicolsep
3626         \__enumext_multi_addvspace:
3627     }
3628     \raggedcolumns
3629     \begin{multicols}{ \int_use:c { l__enumext_columns_ \__enumext_level: _int } }
3630 }
3631 }

```

(End of definition for __enumext_multicols_start:.)

`__enumext_multicols_stop:` The function `__enumext_multicols_stop:` will stop the `multicols` environment and apply our “vertical adjust” spacing.

```

3632 \cs_new_protected:Nn \__enumext_multicols_stop:
3633 {
3634     \int_compare:nNnTF
3635     { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
3636     {
3637         \__enumext_stop_list:
3638         \__enumext_stop_store_level:
3639         \end{multicols}
3640         \__enumext_unskip_unkern:
3641         \__enumext_unskip_unkern:
3642         \par\addvspace{ \skip_use:c { l__enumext_multicols_below_ \__enumext_level: _skip } }
3643     }
3644     {
3645         \__enumext_stop_list:
3646         \__enumext_stop_store_level:
3647     }
3648 }

```

(End of definition for __enumext_multicols_stop:.)

`__enumext_after_list:` The function `__enumext_after_list:` first check the state of the boolean variable `\l__enumext_minipage_active_X_bool`, if it is “true” a small test will be executed to check if we have omitted the

use of `\miniright` (the `__enumext_mini_page` environment has not been closed), then close `__enumext-mini_page` and add the *adjusted vertical space* `\l__enumext_minipage_after_skip`, otherwise we will close the `multicols` environment.

```

3649 \cs_new_protected:Nn \__enumext_after_list:
3650 {
3651   \bool_if:cTF { \l__enumext_minipage_active_ \__enumext_level: _bool }
3652   {
3653     \int_compare:nNt { \g__enumext_minipage_stat_int } = { 1 }
3654     {
3655       \msg_warning:nn { enumext } { missing-miniright }
3656       \miniright
3657     }
3658     \int_gzero:N \g__enumext_minipage_stat_int
3659     \__enumext_unskip_unkern: % remove topsep + [partopsep]
3660     \end__enumext_mini_page
3661   }
3662   {
3663     \__enumext_multicols_stop:
3664   }

```

Now we will execute the functions `__enumext_after_stop_list:` used by the key `after`, `__enumext-check_ans_key_hook:` used by the key `check-ans`, `__enumext_vspace_below:` used by the keys `below` and `below*`. Finally set `\l__enumext_standar_bool` to false and call the function `__enumext_resume-save_counter:` used by the `series`, `resume` and `resume*` keys.

```

3665   \__enumext_after_stop_list:
3666   \__enumext_check_ans_key_hook:
3667   \__enumext_vspace_below:
3668   \bool_set_false:N \l__enumext_standar_bool
3669   \__enumext_resume_save_counter:
3670 }

```

As we don't want our check to be executed `check-ans` by levels but on the complete list, we will take it out of the `enumext` environment using the “hook” function `__enumext_after_env:nn`.

```

3671 \__enumext_after_env:nn {enumext} { \__enumext_execute_after_env: }

```

(End of definition for `__enumext_after_list:.`)

12.39 The environment `keyans`

The environment `keyans` also based on lists. The main differences with the `enumext` environment are the *nesting* and the way the *answers* (choice) will be stored and checked, this environment is intended exclusively for “multiple choice questions”.

keyans Now we define the environment `keyans` also based on lists.

```

3672 \NewDocumentEnvironment{keyans}{0}{}
3673 {
3674   \__enumext_keyans_safe_exec:
3675   \__enumext_keyans_parse_keys:n {#1}
3676   \__enumext_before_list_v:
3677   \__enumext_start_list:nn
3678   { \tl_use:N \l__enumext_label_v_tl }
3679   {
3680     \__enumext_list_arg_two_v:
3681     \__enumext_before_keys_exec_v:
3682   }
3683   \__enumext_keyans_set_item_width:
3684   \__enumext_after_args_exec_v:
3685 }
3686 {
3687   \__enumext_check_starred_cmd:n { item }
3688   %%\__enumext_stop_list:
3689   \__enumext_after_list_v:
3690 }

```

(End of definition for `keyans`. This function is documented on page 14.)

`__enumext_keyans_set_item_width:`

The function `__enumext_keyans_set_item_width:` will set the value of `\itemwidth` taking into account the value established by the `list-offset` key.

```

3691 \cs_new_protected:Nn \__enumext_keyans_set_item_width:
3692 {
3693   \dim_set:Nn \itemwidth
3694   {

```

```

3695         \linewidth
3696     }
3697     \dim_compare:nT
3698     {
3699         \l__enumext_listoffset_v_dim != \c_zero_dim
3700     }
3701     {
3702         \dim_sub:Nn \itemwidth
3703         {
3704             \l__enumext_listoffset_v_dim
3705         }
3706     }
3707 }

```

(End of definition for `__enumext_keyans_set_item_width:`)

`__enumext_keyans_safe_exec:` The `keyans` environment will only be available if the `save-ans` key is active and can only be used at the “first level” within the `enumext` environment. We do not want the environment to be nested, so we will set a maximum at this point. If the conditions are not met, an error message will be returned.

```

3708 \cs_new_protected:Nn \__enumext_keyans_safe_exec:
3709 {
3710     \bool_if:NF \l__enumext_store_active_bool
3711     {
3712         \msg_error:nnnn { enumext } { wrong-place } { keyans } { save-ans }
3713     }
3714     \int_incr:N \l__enumext_keyans_level_int
3715     \bool_set_true:N \l__enumext_keyans_env_bool
3716     \__enumext_keyans_name_and_start:
3717     % Set false for interfering with enumext nested in keyans (yes, its possible and crayze)
3718     \bool_set_false:N \l__enumext_store_active_bool
3719     \int_compare:nNnT { \l__enumext_keyans_level_int } > { 1 }
3720     {
3721         \msg_error:nn { enumext } { keyans-nested }
3722     }
3723     \int_compare:nNnT { \l__enumext_level_int } > { 1 }
3724     {
3725         \msg_error:nn { enumext } { keyans-wrong-level }
3726     }
3727 }

```

(End of definition for `__enumext_keyans_safe_exec:`)

`__enumext_keyans_parse_keys:n` Parse [`key = val`] for `keyans` environment.

```

3728 \cs_new_protected:Npn \__enumext_keyans_parse_keys:n #1
3729 {
3730     \keys_set:nn { enumext / keyans } {#1}
3731 }

```

(End of definition for `__enumext_keyans_parse_keys:n`)

`__enumext_before_list_v:` Same implementation as the one used in the `enumext` environment.

```

\__enumext_keyans_multicols_start:
\__enumext_keyans_multicols_stop:
\__enumext_after_list_v:
3732 \cs_new_protected:Nn \__enumext_before_list_v:
3733 {
3734     \__enumext_vspace_above_v:
3735     \__enumext_before_args_exec_v:
3736     \dim_compare:nNnT { \l__enumext_minipage_right_v_dim } > { \c_zero_dim }
3737     {
3738         \dim_set:Nn \l__enumext_minipage_left_v_dim
3739         {
3740             \linewidth - \l__enumext_minipage_right_v_dim - \l__enumext_minipage_hsep_v_dim
3741         }
3742         \bool_set_true:N \l__enumext_minipage_active_v_bool
3743         \int_gincr:N \g__enumext_minipage_stat_int
3744         \__enumext_keyans_minipage_add_space:
3745         \__enumext_mini_page{ \l__enumext_minipage_left_v_dim }
3746     }
3747     \__enumext_keyans_multicols_start:
3748 }
3749 \cs_new_protected:Nn \__enumext_keyans_multicols_start:
3750 {
3751     \int_compare:nNnT { \l__enumext_columns_v_int } > { 1 }

```

```

3752 {
3753   \dim_compare:nNnT { \l__enumext_columns_sep_v_dim } = { \c_zero_dim }
3754   {
3755     \dim_set:Nn \l__enumext_columns_sep_v_dim
3756     {
3757       (
3758         \l__enumext_labelwidth_v_dim + \l__enumext_labelsep_v_dim
3759       ) / \l__enumext_columns_v_int
3760       - \l__enumext_listoffset_v_dim
3761     }
3762   }
3763   \dim_set_eq:NN \columnsep \l__enumext_columns_sep_v_dim
3764   \dim_zero:N \columnseprule % no rule here
3765   \bool_if:NF \l__enumext_minipage_active_v_bool
3766   {
3767     \skip_zero:N \multicolsep
3768     \__enumext_keyans_multi_addvspace:
3769   }
3770   \raggedcolumns
3771   \begin{multicols}{ \l__enumext_columns_v_int }
3772 }
3773 }
3774 \cs_new_protected:Nn \__enumext_keyans_multicols_stop:
3775 {
3776   \int_compare:nNnTF { \l__enumext_columns_v_int } > { 1 }
3777   {
3778     \__enumext_stop_list:
3779     \end{multicols}
3780     \__enumext_unskip_unkern:
3781     \__enumext_unskip_unkern:
3782     \par\addvspace{ \l__enumext_multicols_below_v_skip }
3783   }
3784   {
3785     \__enumext_stop_list:
3786   }
3787 }
3788 \cs_new_protected:Nn \__enumext_after_list_v:
3789 {
3790   \bool_if:NTF \l__enumext_minipage_active_v_bool
3791   {
3792     \int_compare:nNnT { \g__enumext_minipage_stat_int } = { 1 }
3793     {
3794       \msg_warning:nn { enumext } { missing-miniright }
3795       \miniright
3796     }
3797     \int_gzero:N \g__enumext_minipage_stat_int
3798     \__enumext_unskip_unkern: % remove topsep + [partopsep]
3799     \end__enumext_mini_page
3800     \par\addvspace{ \l__enumext_minipage_after_skip }
3801   }
3802   {
3803     \__enumext_keyans_multicols_stop:
3804   }
3805   \bool_set_false:N \l__enumext_keyans_env_bool
3806   \__enumext_after_stop_list_v:
3807   \__enumext_vspace_below_v:
3808 }

```

(End of definition for `__enumext_before_list_v:` and others.)

12.40 Tagging PDF support for non-standart list environments

The \LaTeX release 2022-06-01 brings automatic support for tagPDF in several aspects, including the standart *list environments* and the `list` environment. Unfortunately non-standard *list environments* like `keyanspic` or the horizontal list environments `enumext*` and `keyans*` are not structured in a nice way, i.e. the expected result in the PDF file is the expected one, but the underlying structure is not correct. In simple terms, for tagPDF a list environment is a list environment, no matter what it looks like in the PDF file.

To maintain a correct list structure when `\DocumentMetadata` is active, it is necessary to do some things manually. This implementation is an adaptation of my answer thanks to Ulrike Fischer's comments in [How can I modify my `\item` redefinition to be compatible with tagging-pdf.](#)

12.40.1 Socket for tagging support in enumext* and keyans*

```
start-list-tags
stop-start-tags
stop-list-tags
__enumext_start_list_tag:n
  __enumext_stop_start_list_tag:
__enumext_stop_list_tag:n
```

We will first define the necessary sockets and their behavior for `enumext*` and `keyans*`.

```
3809 \socket_new:nn {tagsupport/enumext/starred}{ 1 }
3810 \socket_new_plugin:nnn {tagsupport/enumext/starred} {start-list-tags}
3811 {
3812   \tag_resume:n {#1}
3813   \tag_struct_begin:n {tag=LI}
3814   \tag_struct_begin:n {tag=Lbl}
3815   \tag_mc_begin:n {tag=Lbl}
3816 }
3817 \socket_new_plugin:nnn {tagsupport/enumext/starred} {stop-start-tags}
3818 {
3819   \tag_mc_end:
3820   \tag_struct_end:n {tag=Lbl}
3821   \tag_struct_begin:n {tag=LBody}
3822   \tag_struct_begin:n {tag=text-unit}
3823   \tag_struct_begin:n {tag=text}
3824 }
3825 \socket_new_plugin:nnn {tagsupport/enumext/starred} {stop-list-tags}
3826 {
3827   \tag_struct_end:n {tag=text}
3828   \tag_struct_end:n {tag=text-unit}
3829   \tag_struct_end:n {tag=LBody}
3830   \tag_struct_end:n {tag=LI}
3831   \tag_suspend:n {#1}
3832 }
```

And now we'll wrap them so that they're only active when `\DocumentMetadata` is present.

```
3833 \cs_new_protected_nopar:Npn __enumext_start_list_tag:n #1
3834 {
3835   \IfDocumentMetadataTF
3836   {
3837     \socket_assign_plugin:nn {tagsupport/enumext/starred} {start-list-tags}
3838     \socket_use:n {tagsupport/enumext/starred} {#1}
3839   } {}
3840 }
3841 \cs_new_protected_nopar:Nn __enumext_stop_start_list_tag:
3842 {
3843   \IfDocumentMetadataTF
3844   {
3845     \socket_assign_plugin:nn {tagsupport/enumext/starred} {stop-start-tags}
3846     \socket_use:nn {tagsupport/enumext/starred} { }
3847   } {}
3848 }
3849 \cs_new_protected_nopar:Npn __enumext_stop_list_tag:n #1
3850 {
3851   \IfDocumentMetadataTF
3852   {
3853     \socket_assign_plugin:nn {tagsupport/enumext/starred} {stop-list-tags}
3854     \socket_use:nn {tagsupport/enumext/starred} {#1}
3855   } {}
3856 }
```

(End of definition for `start-list-tags` and others.)

12.40.2 Socket for tagging support in keyanspic

```
start-list-tags
stop-start-tags
stop-list-tags
__enumext_anspic_start_list_tag:
__enumext_anspic_stop_start_list_tag:
__enumext_anspic_stop_list_tag:
```

We will first define the necessary sockets and their behavior for `keyanspic`.

```
3857 \socket_new:nn {tagsupport/enumext/keyanspic}{ 0 }
3858 \socket_new_plugin:nnn {tagsupport/enumext/keyanspic} {start-list-tags}
3859 {
3860   \tag_resume:n {keyanspic}
3861   \tag_struct_begin:n {tag=LI}
3862   \tag_struct_begin:n {tag=Lbl}
3863   \tag_mc_begin:n {tag=Lbl}
3864 }
3865 \socket_new_plugin:nnn {tagsupport/enumext/keyanspic} {stop-start-tags}
3866 {
3867   \tag_mc_end:
3868   \tag_struct_end:n {tag=Lbl}
3869   \tag_struct_begin:n {tag=LBody}
3870   \tag_struct_begin:n {tag=text-unit}
```

```
3871 \tag_struct_begin:n {tag=text}
3872 \tag_mc_begin:n {tag=text}
3873 }
3874 \socket_new_plug:nnn {tagsupport/enumext/keyanspic} {stop-list-tags}
3875 {
3876 \tag_mc_end:
3877 \tag_struct_end:n {tag=text-unit}
3878 \tag_struct_end:n {tag=text}
3879 \tag_struct_end:n {tag=LBody}
3880 \tag_struct_end:n {tag=LI}
3881 \tag_suspend:n {keyanspic}
3882 }
```

And now we'll wrap them so that they're only active when `\DocumentMetadata` is present.

```
3883 \cs_new_protected_nopar:Nn \__enumext_anspic_start_list_tag:
3884 {
3885 \IfDocumentMetadataTF
3886 {
3887 \socket_assign_plug:nn {tagsupport/enumext/keyanspic} {start-list-tags}
3888 \socket_use:n {tagsupport/enumext/keyanspic}
3889 } {}
3890 }
3891 \cs_new_protected_nopar:Nn \__enumext_anspic_stop_start_list_tag:
3892 {
3893 \IfDocumentMetadataTF
3894 {
3895 \socket_assign_plug:nn {tagsupport/enumext/keyanspic} {stop-start-tags}
3896 \socket_use:nn {tagsupport/enumext/keyanspic}
3897 } {}
3898 }
3899 \cs_new_protected_nopar:Nn \__enumext_anspic_stop_list_tag:
3900 {
3901 \IfDocumentMetadataTF
3902 {
3903 \socket_assign_plug:nn {tagsupport/enumext/keyanspic} {stop-list-tags}
3904 \socket_use:nn {tagsupport/enumext/keyanspic}
3905 } {}
3906 }
```

(End of definition for `start-list-tags` and others.)

12.41 The environment `keyanspic` and `\anspic`

The `keyanspic` environment is a list-based environment that uses the same configuration for “*spacing*” and `<label>` as the `keyans` environment, but it does not use `\item`. The `<contents>` are passed to the environment by means of the `\anspic` command and are placed inside `minipage` environments, with the `<label>` underneath, adjusting widths according to the options passed to the environment.




Figure 12: Representation of the `keyanspic` spacing in `enumext`.

This implementation is adapted from the answer given by Enrico Gregorio in [How to process the body of an environment and divide it by a `\macro`?](#).

12.41.1 The environment `keyanspic`

The environment we wish to build will be based on the `list` environment and will take two optional arguments, the *starred argument* `*` will set the position of the `<label>` to the top if present and bottom otherwise, the second optional argument will process the number of *drawing* or *tabular* that will be on top, bottom or inline when present or not.

`__enumext_keyans_pic_safe_exec:n`

The function `__enumext_keyans_pic_safe_exec:n` check the starred argument and nested level position inside the `enumext` environment. We will set the state of the variable `\l__enumext_keyans_pic_star_bool` along with the value of the variable `\l__enumext_keyans_pic_label_pos_str` according to the presence of the starred argument.

```

3907 \cs_new_protected:Npn \__enumext_keyans_pic_safe_exec:n #1
3908 {
3909   \int_incr:N \l__enumext_keyans_pic_level_int
3910   \int_compare:nNnT { \l__enumext_keyans_pic_level_int } > { 1 }
3911   {
3912     \msg_error:nn { enumext } { keyanspic-nested }
3913   }
3914   \__enumext_keyans_name_and_start:
3915   \bool_if:nTF { #1 }
3916   {
3917     \bool_set_true:N \l__enumext_keyans_pic_star_bool
3918     \str_set:Nn \l__enumext_keyans_pic_label_pos_str { t }
3919   }
3920   {
3921     \str_set:Nn \l__enumext_keyans_pic_label_pos_str { b }
3922   }
3923 }

```

(End of definition for __enumext_keyans_pic_safe_exec:n.)

__enumext_keyans_pic_skip_abs:N The function __enumext_keyans_pic_skip_abs:N will return a positive value \parsep.

```

3924 \cs_new_protected:Npn \__enumext_keyans_pic_skip_abs:N #1
3925 {
3926   \dim_compare:nNnT { #1 } < { \c_zero_dim }
3927   {
3928     \skip_set:Nn #1 { -#1 }
3929   }
3930 }

```

(End of definition for __enumext_keyans_pic_skip_abs:N.)

__enumext_keyans_pic_arg_two:

The __enumext_keyans_pic_arg_two: function will be used in the second argument of the list environment that defines the `keyanspic` environment, with this we will take the configuration of the spaces and the keys `label` and `wrap-label` from the `keyans` environment.

The first thing we need to do is set the boolean variable `\l__enumext_leftmargin_tmp_v_bool` handled by the `list-indent` key to false, then copy the definition of the second list argument from the `keyans` environment and make sure that `\parsep` does not have a negative value.

```

3931 \cs_new_protected:Nn \__enumext_keyans_pic_arg_two:
3932 {
3933   \bool_set_false:N \l__enumext_leftmargin_tmp_v_bool
3934   \__enumext_list_arg_two_v:
3935   \__enumext_keyans_pic_skip_abs:N \parsep

```

Now we increment the `enumXv` counter of the `keyans` environment and save the total height of our `\label` in `\l__enumext_anspic_label_htdp_dim` and we will adjust the values of `\parsep` only if the starred argument is NOT present (default version).

```

3936   \bool_if:NF \l__enumext_keyans_pic_star_bool
3937   {
3938     \stepcounter { enumXv }
3939     \hbox_set:Nn \l__enumext_anspic_label_box { \l__enumext_label_v_tl }
3940     \dim_set:Nn \l__enumext_anspic_label_htdp_dim
3941     {
3942       \box_ht_plus_dp:N \l__enumext_anspic_label_box
3943     }
3944     \skip_add:Nn \parsep
3945     {
3946       \l__enumext_anspic_label_htdp_dim + \box_dp:N \strutbox
3947     }
3948     \skip_gset_eq:NN \g__enumext_keyans_pic_parsep_skip \parsep
3949   }

```

Finally we adjust the value of `\leftmargin` and `\topsep` then set `\labelwidth`, `\labelsep`, `\partopsep` and `\itemsep` to zero so that the horizontal and vertical space is not affected.

```

3950   \dim_add:Nn \leftmargin { -\labelwidth - \labelsep }
3951   \skip_add:Nn \topsep { 0.5\box_dp:N \strutbox }
3952   \dim_zero:N \labelwidth
3953   \dim_zero:N \listparindent
3954   \dim_zero:N \labelsep
3955   \skip_zero:N \partopsep
3956   \skip_zero:N \itemsep
3957 }

```


(End of definition for `__enumext_keyans_pic_arg_two:`)

`keyanspic` Now we define the environment `keyanspic` based on `list`. The starred argument will determine whether the *labels* will be displayed “above” or “below” the drawing or tabular. The second optional argument [*number above, number below*] will determine the number of `minipage` environments that will be above and below separated by `\parsep` within it.

```

3958 \NewDocumentEnvironment{keyanspic}{s o }
3959 {
3960   \__enumext_keyans_pic_safe_exec:n { #1 }
3961   \begin{list} { } { \__enumext_keyans_pic_arg_two: }
3962   \IfDocumentMetadataTF
3963   {
3964     \tag_suspend:n {list}
3965   }{}
3966   \item[] \scan_stop:
3967   % paranoia
3968   \RenewDocumentCommand \item {}
3969   {
3970     \msg_error:nn { enumext } { keyanspic-item-cmd }
3971   }
3972   \IfDocumentMetadataTF
3973   {
3974     \tag_resume:n {keyanspic}
3975     \tag_tool:n {para/tagging=false}
3976     \tag_suspend:n {keyanspic}
3977   } { }
3978 }

```

If the optional argument is not present, the number of times the `\anspic` command appears will be counted from `\l__enumext_keyans_pic_body_seq` and placed in `minipage` environments on a single line. Finally we check if `\anspic*` has been used, set the counter to zero and apply our “adjusted” vertical space below the environment.

```

3979 {
3980   \IfDocumentMetadataTF
3981   {
3982     \tag_resume:n {keyanspic}
3983     \tag_struct_begin:n {tag=L,attribute=enumerate}
3984   } { }
3985   \tl_if_novalue:nTF { #2 }
3986   {
3987     \__enumext_keyans_pic_do:e { \seq_count:N \l__enumext_keyans_pic_body_seq }
3988   }
3989   { \__enumext_keyans_pic_do:n { #2 } }
3990   \IfDocumentMetadataTF
3991   {
3992     \tag_suspend:n {keyanspic}
3993   } { }
3994   \end{list}
3995   \IfDocumentMetadataTF { \tag_struct_end: \tag_struct_end: } { }
3996   \__enumext_check_starred_cmd:n { anspic }
3997   \setcounter { enumXvi } { 0 }
3998   \bool_if:NTF \l__enumext_keyans_pic_star_bool
3999   {
4000     \par\addvspace{ 0.5\box_dp:N \strutbox }
4001   }
4002   {
4003     \par\addvspace{ \g__enumext_keyans_pic_parsep_skip }
4004   }
4005   %\bool_set_false:N \l__enumext_store_active_bool
4006 }

```

(End of definition for `keyanspic`. This function is documented on page 15.)

`__enumext_keyans_pic_do:n` The optional argument is split by comma and is handled directly by the function `__enumext_keyans_pic_do:n` and passed to the function `__enumext_keyans_pic_row:n`.

```

4007 \cs_new_protected:Nn \__enumext_keyans_pic_do:n
4008 {
4009   \clist_map_function:nN { #1 } \__enumext_keyans_pic_row:n
4010 }
4011 \cs_generate_variant:Nn \__enumext_keyans_pic_do:n { e }

```

(End of definition for `__enumext_keyans_pic_do:n`.)

`__enumext_keyans_pic_row:n` The function `__enumext_keyans_pic_row:n` will set the widths for the `minipage` environments and place the content `⟨stored⟩` by `\anspic*` in the `\l__enumext_keyans_pic_body_seq` sequence inside them.

```

4012 \cs_new_protected:Nn \__enumext_keyans_pic_row:n
4013 {
4014   \dim_set:Nn \l__enumext_keyans_pic_width_dim { \linewidth / #1 }
4015   \int_set:Nn \l__enumext_keyans_pic_above_int { \l__enumext_keyans_pic_below_int }
4016   \int_set:Nn \l__enumext_keyans_pic_below_int { \l__enumext_keyans_pic_above_int + #1 }
4017   \int_step_inline:nnn
4018     { \l__enumext_keyans_pic_above_int + 1 }
4019     { \l__enumext_keyans_pic_below_int }
4020     {
4021       \IfDocumentMetadataTF
4022         {
4023           \tag_suspend:n {minipage}
4024         } { }
4025       \begin{minipage}[ \l__enumext_keyans_pic_label_pos_str ]{ \l__enumext_keyans_pic_width_dim }
4026         \centering
4027         \seq_item:Nn \l__enumext_keyans_pic_body_seq { ##1 }
4028       \end{minipage}
4029       \IfDocumentMetadataTF
4030         {
4031           \tag_resume:n {minipage}
4032         } { }
4033     }
4034   \par
4035 }

```

(End of definition for `__enumext_keyans_pic_row:n`.)

12.41.2 The command `\anspic`

`\anspic` The `\anspic` command take three arguments, the starred (*) versions `\anspic*` and `\anspic* [⟨content⟩]` store the current `⟨label⟩` next to the `[⟨content⟩]` if it is present in the `⟨sequence⟩` and `⟨prop list⟩` defined by `save-ans` key. This command is used as a replacement for `\item` in the `keyanspic` environment.

```

4036 \NewDocumentCommand \anspic { s o +m }
4037 {

```

We check that the command is active in the `keyanspic` environment only if the `save-ans` key is present, otherwise we return an error.

```

4038   \bool_if:NF \l__enumext_store_active_bool
4039   {
4040     \msg_error:nnnn { enumext } { wrong-place }{ keyanspic }{ save-ans }
4041   }
4042   \int_compare:nNnT { \l__enumext_level_int } > { 1 }
4043   {
4044     \msg_error:nn { enumext } { keyanspic-wrong-level }
4045   }
4046   \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
4047   {
4048     \msg_error:nnnn { enumext } { command-wrong-place }{ anspic }{ keyans }
4049   }

```

The three arguments are handled by the function `__enumext_keyans_anspic_code:nnn` and stored in the sequence `\l__enumext_keyans_pic_body_seq` which is processed by the `keyanspic` environment.

```

4050   \seq_put_right:Nn \l__enumext_keyans_pic_body_seq
4051   {
4052     \__enumext_keyans_anspic_code:nnn { #1 } { #2 } { #3 }
4053   }
4054 }

```

(End of definition for `\anspic`. This function is documented on page 15.)

`__enumext_anspic_box_set_dim:n` The function `__enumext_keyans_anspic_code:nnn` will be in charge of handling the “counter” and `⟨label⟩`, which will have the same configuration as the `keyans` environment.

```

4055 \cs_new_protected:Npn \__enumext_anspic_box_set_dim:n #1
4056 {
4057   \bool_if:NF \l__enumext_keyans_pic_star_bool
4058   {
4059     \IfDocumentMetadataTF
4060     {

```

```

4061         \tag_suspend:n {keyanspic}
4062     } { }
4063     \vbox_set:Nn \l__enumext_anspic_body_box { #1 }
4064     \dim_set:Nn \l__enumext_anspic_body_htdp_dim
4065     {
4066         \box_ht_plus_dp:N \l__enumext_anspic_body_box
4067     }
4068     \IfDocumentMetadataTF
4069     {
4070         \tag_resume:n {keyanspic}
4071     } { }
4072 }
4073 }
4074 % process label
4075 \cs_new_protected:Npn \__enumext_anspic_label:nn #1 #2
4076 {
4077     \makebox[ \l__enumext_keyans_pic_width_dim ][ c ]
4078     {
4079         \bool_if:nT { #1 }
4080         {
4081             \__enumext_keyans_addto_prop:n { #2 }
4082             \__enumext_keyans_store_ref:
4083             \__enumext_keyans_addto_seq:n { #2 }
4084             \int_gincr:N \g__enumext_check_starred_cmd_int
4085             \bool_lazy_or:nnT
4086             { \bool_if_p:N \l__enumext_show_answer_bool }
4087             { \bool_if_p:N \l__enumext_show_position_bool }
4088             {
4089                 \tl_set_eq:NN \l__enumext_label_v_tl \l__enumext_label_vi_tl
4090                 \__enumext_keyans_show_left:n { #2 }
4091                 \tl_set_eq:NN \l__enumext_label_vi_tl \l__enumext_label_v_tl
4092             }
4093         }
4094         \tl_use:N \l__enumext_label_font_style_v_tl
4095         \__enumext_wrapper_label_v:n { \l__enumext_label_vi_tl }
4096         \__enumext_keyans_show_item_opt:
4097     }
4098 }
4099 \cs_new_protected:Npn \__enumext_keyans_anspic_label:nnn #1 #2 #3
4100 {
4101     \stepcounter { enumXvi }
4102     \__enumext_anspic_box_set_dim:n { #3 }
4103     \bool_if:NTF \l__enumext_keyans_pic_star_bool
4104     {
4105         \__enumext_anspic_label:nn { #1 } { #2 }
4106     }
4107     {
4108         \raisebox
4109         {
4110             -\dim_eval:n
4111             {
4112                 \l__enumext_anspic_label_htdp_dim
4113                 + \l__enumext_anspic_body_htdp_dim
4114                 + \box_dp:N \strutbox
4115             }
4116         }
4117         [ opt ] [ opt ]
4118         {
4119             \__enumext_anspic_label:nn { #1 } { #2 }
4120         }
4121     }
4122 }
4123 \cs_new_protected:Nn \__enumext_keyans_anspic_code:nnn
4124 {
4125     \__enumext_anspic_start_list_tag:
4126     \__enumext_keyans_anspic_label:nnn { #1 } { #2 } { #3 }
4127     \__enumext_anspic_stop_start_list_tag:
4128     \\ #3
4129     \__enumext_anspic_stop_list_tag:
4130 }

```

(End of definition for __enumext_anspic_box_set_dim:n, __enumext_keyans_anspic_label:nnn, and __enumext_keyans_

anspic_code:nnn.)

12.42 The horizontal environments

Generating *horizontal list environments* is NOT as simple as standard \TeX list environments. The fundamental part of the code is adapted from the `shortlst` package to a more modern version using `expl3`. It is not possible to redefine `\item` and `\makelabel` as in the vertical *non starred* versions.

12.42.1 Functions for item box width

To achieve the horizontal list environment we will capture the `\item` command and the $\langle content \rangle$ of this in *horizontal box* using `\makebox` for the `label` and a `minipage` environment for the $\langle content \rangle$ passed to `\item`, we will also add the optional argument ($\langle number \rangle$) to `\item` to be able to *join columns* horizontally, in simple terms, we want `\item` to behave in the same way as in the `enumext` environment but adding an optional first argument ($\langle number \rangle$).

We set the default value for the *width of the box* containing the $\langle content \rangle$ of the items for `enumext*` environment.

`__enumext_starred_columns_set_vii:`
`__enumext_starred_columns_set_viii:`

```

4131 \cs_new_protected:Nn \__enumext_starred_columns_set_vii:
4132 {
4133   \dim_compare:nNnT { \__enumext_columns_sep_vii_dim } = { \c_zero_dim }
4134   {
4135     \dim_set:Nn \__enumext_columns_sep_vii_dim
4136     {
4137       ( \__enumext_labelwidth_vii_dim + \__enumext_labelsep_vii_dim )
4138       / \__enumext_columns_vii_int
4139     }
4140   }
4141   \int_set:Nn \__enumext_tmpa_vii_int { \__enumext_columns_vii_int - 1 }
4142   \dim_set:Nn \__enumext_item_width_vii_dim
4143   {
4144     ( \linewidth - \__enumext_columns_sep_vii_dim * \__enumext_tmpa_vii_int )
4145     / \__enumext_columns_vii_int
4146     - \__enumext_labelwidth_vii_dim
4147     - \__enumext_labelsep_vii_dim
4148   }

```

When the key `rightmargin` is active we must adjust the values.

```

4149   \dim_compare:nNnT { \__enumext_rightmargin_vii_dim } > { \c_zero_dim }
4150   {
4151     \dim_sub:Nn \__enumext_item_width_vii_dim
4152     {
4153       ( \__enumext_rightmargin_vii_dim * \__enumext_tmpa_vii_int )
4154       / \__enumext_columns_vii_int
4155     }
4156     \dim_add:Nn \__enumext_columns_sep_vii_dim
4157     {
4158       \__enumext_rightmargin_vii_dim
4159     }
4160   }
4161 }

```

Same implementation for the `keyans*` environment.

```

4162 \cs_new_protected:Nn \__enumext_starred_columns_set_viii:
4163 {
4164   \dim_compare:nNnT { \__enumext_columns_sep_viii_dim } = { \c_zero_dim }
4165   {
4166     \dim_set:Nn \__enumext_columns_sep_viii_dim
4167     {
4168       ( \__enumext_labelwidth_viii_dim + \__enumext_labelsep_viii_dim )
4169       / \__enumext_columns_viii_int
4170     }
4171   }
4172   \int_set:Nn \__enumext_tmpa_viii_int { \__enumext_columns_viii_int - 1 }
4173   \dim_set:Nn \__enumext_item_width_viii_dim
4174   {
4175     ( \linewidth - \__enumext_columns_sep_viii_dim * \__enumext_tmpa_viii_int )
4176     / \__enumext_columns_viii_int
4177     - \__enumext_labelwidth_viii_dim
4178     - \__enumext_labelsep_viii_dim
4179   }
4180   \dim_compare:nNnT { \__enumext_rightmargin_viii_dim } > { \c_zero_dim }
4181   {
4182     \dim_sub:Nn \__enumext_item_width_viii_dim

```

```

4183         {
4184             ( \l__enumext_rightmargin_viii_dim * \l__enumext_tmpa_vii_int )
4185             / \l__enumext_columns_viii_int
4186         }
4187     \dim_add:Nn \l__enumext_columns_sep_viii_dim
4188     {
4189         \l__enumext_rightmargin_viii_dim
4190     }
4191 }
4192 }

```

(End of definition for \l__enumext_starred_columns_set_vii: and \l__enumext_starred_columns_set_viii:.)

12.42.2 Functions for join item columns

\l__enumext_starred_joined_item_vii:n
\l__enumext_starred_joined_item_viii:n

The functions \l__enumext_starred_joined_item_vii:n and \l__enumext_starred_joined_item_viii:n will set the *width* of the box in which the *content* passed to \item(*columns*) will be stored together with the value of \itemwidth for the enumext* environment.

```

4193 \cs_new_protected:Npn \l__enumext_starred_joined_item_vii:n #1
4194 {
4195     \int_set:Nn \l__enumext_joined_item_vii_int {#1}
4196     \int_compare:nNnT { \l__enumext_joined_item_vii_int } > { \l__enumext_columns_vii_int }
4197     {
4198         \msg_warning:nnee { enumext } { item-joined }
4199         { \int_use:N \l__enumext_joined_item_vii_int }
4200         { \int_use:N \l__enumext_columns_vii_int }
4201         \int_set:Nn \l__enumext_joined_item_vii_int
4202         {
4203             \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1
4204         }
4205     }
4206     \int_compare:nNnT
4207     { \l__enumext_joined_item_vii_int }
4208     >
4209     { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1 }
4210     {
4211         \msg_warning:nnee { enumext } { item-joined-columns }
4212         { \int_use:N \l__enumext_joined_item_vii_int }
4213         {
4214             \int_eval:n
4215             { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1 }
4216         }
4217         \int_set:Nn \l__enumext_joined_item_vii_int
4218         {
4219             \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1
4220         }
4221     }
4222     \int_compare:nNnTF { \l__enumext_joined_item_vii_int } > { 1 }
4223     {
4224         \int_set_eq:NN \l__enumext_joined_item_aux_vii_int \l__enumext_joined_item_vii_int
4225         \int_decr:N \l__enumext_joined_item_aux_vii_int
4226         \int_add:Nn \l__enumext_item_column_pos_viii_int { \l__enumext_joined_item_aux_vii_int }
4227         \int_gadd:Nn \g__enumext_item_count_all_vii_int { \l__enumext_joined_item_aux_vii_int }
4228         \dim_set:Nn \l__enumext_joined_width_vii_dim
4229         {
4230             \l__enumext_item_width_vii_dim * \l__enumext_joined_item_vii_int
4231             + ( \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim
4232               + \l__enumext_columns_sep_vii_dim
4233               ) * \l__enumext_joined_item_aux_vii_int
4234         }
4235         \dim_set_eq:NN \itemwidth \l__enumext_joined_width_vii_dim
4236     }
4237     {
4238         \dim_set_eq:NN \l__enumext_joined_width_vii_dim \l__enumext_item_width_vii_dim
4239         \dim_set_eq:NN \itemwidth \l__enumext_item_width_vii_dim
4240     }
4241 }

```

Same implementation for the keyans* environment.

```

4242 \cs_new_protected:Npn \l__enumext_starred_joined_item_viii:n #1
4243 {
4244     \int_set:Nn \l__enumext_joined_item_viii_int {#1}

```

```

4245 \int_compare:nNnT { \l__enumext_joined_item_viii_int } > { \l__enumext_columns_viii_int }
4246 {
4247   \msg_warning:nnee { enumext } { item-joined }
4248   { \int_use:N \l__enumext_joined_item_viii_int }
4249   { \int_use:N \l__enumext_columns_viii_int }
4250   \int_set:Nn \l__enumext_joined_item_viii_int
4251   {
4252     \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1
4253   }
4254 }
4255 \int_compare:nNnT
4256 { \l__enumext_joined_item_viii_int }
4257 >
4258 { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1 }
4259 {
4260   \msg_warning:nnee { enumext } { item-joined-columns }
4261   { \int_use:N \l__enumext_joined_item_viii_int }
4262   {
4263     \int_eval:n
4264     { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1 }
4265   }
4266   \int_set:Nn \l__enumext_joined_item_viii_int
4267   {
4268     \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1
4269   }
4270 }
4271 \int_compare:nNnTF { \l__enumext_joined_item_viii_int } > { 1 }
4272 {
4273   \int_set_eq:NN \l__enumext_joined_item_aux_viii_int \l__enumext_joined_item_viii_int
4274   \int_decr:N \l__enumext_joined_item_aux_viii_int
4275   \int_add:Nn \l__enumext_item_column_pos_viii_int { \l__enumext_joined_item_aux_viii_int }
4276   \int_gadd:Nn \g__enumext_item_count_all_viii_int { \l__enumext_joined_item_aux_viii_int }
4277   \dim_set:Nn \l__enumext_joined_width_viii_dim
4278   {
4279     \l__enumext_item_width_viii_dim * \l__enumext_joined_item_viii_int
4280     + ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim
4281         + \l__enumext_columns_sep_viii_dim
4282         ) * \l__enumext_joined_item_aux_viii_int
4283   }
4284   \dim_set_eq:NN \itemwidth \l__enumext_joined_width_viii_dim
4285 }
4286 {
4287   \dim_set_eq:NN \l__enumext_joined_width_viii_dim \l__enumext_item_width_viii_dim
4288   \dim_set_eq:NN \itemwidth \l__enumext_item_width_viii_dim
4289 }
4290 }

```

(End of definition for `__enumext_starred_joined_item_vii:n` and `__enumext_starred_joined_item_viii:n`)

12.42.3 Functions for mini-env, mini-right and mini-right* keys

To have compatibility with the tagPDF we close the environment according to the presence or not of the `mini-right` key.

```

\__enumext_start_mini_vii:
\__enumext_stop_mini_vii:

```

The implementation of the `mini-env` key support is almost identical to the one used in the `enumext` and `keyans` environments, the difference is that the `__enumext_mini_page` environment on the “right side” is executed “after” closing the environment, so it is necessary to make a global copy of the variable `__enumext_minipage_right_vii_dim` in the variable `\g__enumext_minipage_right_vii_dim`.

```

4291 \cs_new_protected:Nn \__enumext_start_mini_vii:
4292 {
4293   \dim_compare:nNnT { \l__enumext_minipage_right_vii_dim } > { \c_zero_dim }
4294   {
4295     \dim_set:Nn \l__enumext_minipage_left_vii_dim
4296     {
4297       \linewidth
4298       - \l__enumext_minipage_right_vii_dim
4299       - \l__enumext_minipage_hsep_vii_dim
4300     }
4301     \bool_set_true:N \l__enumext_minipage_active_vii_bool
4302     \dim_gset_eq:NN
4303     \g__enumext_minipage_right_vii_dim
4304     \l__enumext_minipage_right_vii_dim

```

```

4305     \__enumext_mini_addvspace_vii:
4306     \nointerlineskip\noindent
4307     \__enumext_mini_page{ \l__enumext_minipage_left_vii_dim }
4308   }
4309 }

```

The function `__enumext_stop_mini_vii:` closes the `__enumext_mini_page` environment on the “*left side*”, applies `\hfill` and set the variable `\g__enumext_minipage_active_vii_bool` to “*true*” which will be used in the function `__enumext_after_env:nn` to execute the `minipage` on the “*right side*”.

```

4310 \cs_new_protected:Nn \__enumext_stop_mini_vii:
4311 {
4312   \bool_if:NTF \l__enumext_minipage_active_vii_bool
4313   {
4314     \__enumext_stop_list:
4315     \__enumext_stop_store_level_vii:
4316     \IfDocumentMetadataTF { \tag_resume:n {enumext*} } { }
4317     \end__enumext_mini_page
4318     \hfill
4319     \bool_gset_true:N \g__enumext_minipage_active_vii_bool
4320   }
4321   {
4322     \__enumext_stop_list:
4323     \__enumext_stop_store_level_vii:
4324   }
4325 }

```

Finally we execute the `{\code}` passed to the `mini-right` or `mini-right*` keys stored in the variable `\g__enumext_miniright_code_vii_tl` in the `minipage` environment on the “*right side*”. For compatibility with the `caption` package and possibly other `{\code}` passed to this key, we will pass it to a box and then print it.

```

4326 \__enumext_after_env:nn {enumext*}
4327 {
4328   \bool_if:NT \g__enumext_minipage_active_vii_bool
4329   {
4330     \__enumext_minipage:w [ t ] { \g__enumext_minipage_right_vii_dim }
4331     \legacy_if_gset_false:n { @minipage }
4332     \skip_vertical:N \c_zero_skip
4333     \par\addvspace { \g__enumext_minipage_right_skip }
4334     \bool_if:NF \g__enumext_minipage_center_vii_bool
4335     {
4336       \tl_put_left:Nn \g__enumext_miniright_code_vii_tl
4337       {
4338         \centering
4339       }
4340     }
4341     \vbox_set_top:Nn \l__enumext_miniright_code_vii_box
4342     {
4343       \tl_use:N \g__enumext_miniright_code_vii_tl
4344     }
4345     \box_use_drop:N \l__enumext_miniright_code_vii_box
4346     \skip_vertical:N \c_zero_skip
4347     \__enumext_endminipage:
4348     \par\addvspace{ \g__enumext_minipage_after_skip }
4349   }
4350   \bool_gset_false:N \g__enumext_minipage_active_vii_bool
4351   \bool_gset_true:N \g__enumext_minipage_center_vii_bool
4352   \tl_gclear:N \g__enumext_miniright_code_vii_tl
4353   \dim_gzero:N \g__enumext_minipage_right_vii_dim
4354   \bool_gset_false:N \g__enumext_starred_bool
4355 }

```

(End of definition for `__enumext_start_mini_vii:` and `__enumext_stop_mini_vii:.`)

`__enumext_start_mini_viii:` The implementation of the `mini-env`, `mini-right` and `mini-right*` keys is identical to the one used in the `enumext*` environment.

```

4356 \cs_new_protected:Nn \__enumext_start_mini_viii:
4357 {
4358   \dim_compare:nNnT { \l__enumext_minipage_right_viii_dim } > { \c_zero_dim }
4359   {
4360     \dim_set:Nn \l__enumext_minipage_left_viii_dim
4361     {

```



```

4362         \linewidth
4363         - \l__enumext_minipage_right_viii_dim
4364         - \l__enumext_minipage_hsep_viii_dim
4365     }
4366     \bool_set_true:N \l__enumext_minipage_active_viii_bool
4367     \dim_gset_eq:NN
4368         \g__enumext_minipage_right_viii_dim
4369         \l__enumext_minipage_right_viii_dim
4370     \__enumext_mini_addvspace_viii:
4371     \nointerlineskip\noindent
4372     \__enumext_mini_page{ \l__enumext_minipage_left_viii_dim }
4373 }
4374 }
4375 \cs_new_protected:Nn \__enumext_stop_mini_viii:
4376 {
4377     \bool_if:NTF \l__enumext_minipage_active_viii_bool
4378     {
4379         \__enumext_stop_list:
4380         \IfDocumentMetadataTF { \tag_resume:n {keyans*} } { }
4381         \end__enumext_mini_page
4382         \hfill
4383         \bool_gset_true:N \g__enumext_minipage_active_viii_bool
4384     }
4385     {
4386         \__enumext_stop_list:
4387     }
4388 }
4389 \__enumext_after_env:nn {keyans*}
4390 {
4391     \bool_if:NT \g__enumext_minipage_active_viii_bool
4392     {
4393         \__enumext_mini_page{ \g__enumext_minipage_right_viii_dim }
4394         \par\addvspace { \g__enumext_minipage_right_skip }
4395         \bool_if:NF \g__enumext_minipage_center_viii_bool
4396         {
4397             \tl_put_left:Nn \g__enumext_miniright_code_viii_tl
4398             {
4399                 \centering
4400             }
4401         }
4402         \vbox_set_top:Nn \l__enumext_miniright_code_viii_box
4403         {
4404             \tl_use:N \g__enumext_miniright_code_viii_tl
4405         }
4406         \box_use_drop:N \l__enumext_miniright_code_viii_box
4407         \end__enumext_mini_page
4408         \par\addvspace{ \g__enumext_minipage_after_skip }
4409     }
4410     \bool_gset_false:N \g__enumext_minipage_active_viii_bool
4411     \bool_gset_true:N \g__enumext_minipage_center_viii_bool
4412     \tl_gclear:N \g__enumext_miniright_code_viii_tl
4413     \dim_gzero:N \g__enumext_minipage_right_viii_dim
4414 }

```

(End of definition for __enumext_start_mini_viii: and __enumext_stop_mini_viii:.)

12.42.4 Redefining \footnote command

```

\__enumext_footnotetext:nn
\__enumext_renew_footnote:
\__enumext_print_footnote:

```

To keep the correct numbering of \footnote and to make it work correctly in the enumext* and keyans* environments, it is necessary to redefine the command. This implementation is adapted from the answer given by Clea F. Rees (@cfr) in [footnotes in boxes compatible with hyperref](#).

```

4415 \cs_new_protected:Nn \__enumext_footnotetext:nn
4416 {
4417     \footnotetext[#1]{#2}
4418 }
4419 \cs_new_protected:Nn \__enumext_renew_footnote:
4420 {
4421     \seq_gclear:N \g__enumext_footnote_arg_seq
4422     \seq_gclear:N \g__enumext_footnote_int_seq
4423     \RenewDocumentCommand \footnote { o +m }
4424     {
4425         \tl_if_novalue:nTF {##1}

```

```

4426         {
4427             \stepcounter{footnote}
4428             \int_gset_eq:Nc \g__enumext_footnote_int { c@footnote }
4429         }
4430         {
4431             \int_gset:Nn \g__enumext_footnote_int { ##1 }
4432         }
4433         \footnotemark [ \g__enumext_footnote_int ]
4434         \seq_gput_right:Nn \g__enumext_footnote_arg_seq { ##2 }
4435         \seq_gput_right:NV \g__enumext_footnote_int_seq \g__enumext_footnote_int
4436     }
4437 }
4438 \cs_new_protected:Nn \__enumext_print_footnote:
4439 {
4440     \seq_if_empty:NF \g__enumext_footnote_int_seq
4441     {
4442         \seq_map_pairwise_function:NNN
4443         \g__enumext_footnote_int_seq
4444         \g__enumext_footnote_arg_seq
4445         \__enumext_footnotetext:nn
4446     }
4447 }

```

(End of definition for __enumext_footnotetext:nn, __enumext_renew_footnote:, and __enumext_print_footnote:.)

12.43 The environment enumext*

enumext* First we will generate the environment and we will give a temporary definition to __enumext_stop_item_tmp_vii: equal to __enumext_first_item_tmp_vii: and next to \item equal to __enumext_start_item_tmp_vii: which we will redefine later. Unlike the implementation used by the **shortlst** package, we will not set the values of \rightskip and \@rightskip equal to \@flushglue whose value is 0.0pt plus 1.0 fil, in the tests I have performed this fails in some circumstances and different results are obtained when using pdfTeX and LuaTeX.

```

4448 \NewDocumentEnvironment{enumext*}{o }
4449 {
4450     \__enumext_safe_exec_vii:
4451     \__enumext_parse_keys_vii:n {#1}
4452     \__enumext_before_list_vii:
4453     \__enumext_start_store_level_vii:
4454     \__enumext_start_list:nn { }
4455     {
4456         \__enumext_list_arg_two_vii:
4457         \__enumext_before_keys_exec_vii:
4458     }
4459     % Stop tagging
4460     \IfDocumentMetadataTF { \tag_suspend:n {enumext*} } { { }
4461     \__enumext_starred_columns_set_vii:
4462     \item[] \scan_stop:
4463     \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \__enumext_first_item_tmp_vii:
4464     \cs_set_eq:NN \item \__enumext_start_item_tmp_vii:
4465     \ignorespaces
4466 }
4467 {
4468     \IfDocumentMetadataTF { \tag_struct_end:n {tag=text-unit} } { { }
4469     \__enumext_stop_item_tmp_vii:
4470     \__enumext_remove_extra_parsep_vii:
4471     \__enumext_after_list_vii:
4472 }

```

(End of definition for enumext*. This function is documented on page 4.)

__enumext_safe_exec_vii:

We will first call the function __enumext_internal_mini_page: to create the environment __enumext-mini_page, then the function __enumext_is_not_nested: which sets \g__enumext_starred_bool to true if we are not nested within **enumext**, we will increment \l__enumext_level_h_int to restrict nesting of the environment, set \l__enumext_starred_bool to true and finally call the function __enumext_is_on_first_level: which sets \l__enumext_starred_first_bool to true if we are not nested, allowing the “storage system” to be used.

```

4473 \cs_new_protected:Nn \__enumext_safe_exec_vii:
4474 {
4475     \__enumext_internal_mini_page:
4476     \__enumext_is_not_nested:

```

```

4477 \int_incr:N \l__enumext_level_h_int
4478 \int_compare:nNtT { \l__enumext_level_h_int } > { 1 }
4479 {
4480   \msg_error:nn { enumext } { nested }
4481 }
4482 \int_compare:nNtT { \l__enumext_keyans_level_h_int } = { 1 }
4483 {
4484   \msg_error:nnn { enumext } { nested-horizontal } { keyans*}
4485 }
4486 \bool_set_true:N \l__enumext_starred_bool
4487 \bool_set_false:N \l__enumext_standar_bool
4488 \__enumext_is_on_first_level:
4489 }

```

(End of definition for __enumext_safe_exec_vii:.)

__enumext_parse_keys_vii:n

First we will clear the variable \l__enumext_series_str used by the key `series`, process the environment [`key = val`] and execute the function __enumext_parse_series:n and used by the key `series`, then we execute the function __enumext_store_active_keys_vii:n and reprocess the `keys` to pass them to the storage `sequence` if the key `save-key` is not active and finally we call the function __enumext_nested_base_line_fix: used by the key `base-fix`.

```

4490 \cs_new_protected:Npn \__enumext_parse_keys_vii:n #1
4491 {
4492   \tl_if_novalue:nF {#1}
4493   {
4494     \str_clear:N \l__enumext_series_str
4495     \keys_set:nn { enumext / enumext* } {#1}
4496     \__enumext_parse_series:n {#1}
4497     \__enumext_store_active_keys_vii:n {#1}
4498     \__enumext_nested_base_line_fix:
4499   }
4500 }

```

(End of definition for __enumext_parse_keys_vii:n.)

__enumext_before_list_vii:

The function __enumext_before_list_vii: first calls the function __enumext_vspace_above_vii: used by the keys `above` and `above*`, then calls the function __enumext_check_ans_active: for the check answer mechanism and finally calls the functions __enumext_before_args_exec: and __enumext_start_mini_vii: used by the keys `before*`, `mini-env`, `mini-right` and `mini-right*`.

```

4501 \cs_new_protected:Nn \__enumext_before_list_vii:
4502 {
4503   \__enumext_vspace_above_vii:
4504   \__enumext_check_ans_active:
4505   \__enumext_before_args_exec_vii:
4506   \__enumext_start_mini_vii:
4507 }

```

(End of definition for __enumext_before_list_vii:.)

__enumext_after_list_vii:

The function __enumext_after_list_vii: first calls the function __enumext_stop_mini_vii: used by the keys `mini-env`, `mini-right` and `mini-right*`, then to the functions __enumext_after_stop_list_vii: used by the key `after`, __enumext_check_ans_key_hook: used by the key `check-ans`, __enumext_vspace_below_vii: used by the keys `below` and `below*`. Finally set \l__enumext_starred_bool to false and call the __enumext_resume_save_counter: function used by the `series`, `resume` and `resume*` keys.

```

4508 \cs_new_protected:Nn \__enumext_after_list_vii:
4509 {
4510   \__enumext_stop_mini_vii:
4511   \__enumext_after_stop_list_vii:
4512   \__enumext_check_ans_key_hook:
4513   \__enumext_vspace_below_vii:
4514   \bool_set_false:N \l__enumext_starred_bool
4515   \__enumext_resume_save_counter:
4516 }

```

(End of definition for __enumext_after_list_vii:.)

_enumext_start_store_level_vii:
_enumext_stop_store_level_vii:

The _enumext_start_store_level_vii: and _enumext_stop_store_level_vii: functions activate the level saving mechanism for storage in $\langle sequence \rangle$ of the \anskey command and anskey* environment if enumext* are nested in enumext.

```

4517 \cs_new_protected:Nn \__enumext_start_store_level_vii:
4518 {
4519   \bool_if:NT \l__enumext_store_active_bool
4520   {
4521     \int_compare:nNnT { \l__enumext_level_int } > { 0 }
4522     {
4523       \__enumext_store_level_open_vii:
4524     }
4525   }
4526 }
4527 \cs_new_protected:Nn \__enumext_stop_store_level_vii:
4528 {
4529   \bool_if:NT \l__enumext_store_active_bool
4530   {
4531     \int_compare:nNnT { \l__enumext_level_int } > { 0 }
4532     {
4533       \__enumext_store_level_close_vii:
4534     }
4535   }
4536 }

```

(End of definition for _enumext_start_store_level_vii: and _enumext_stop_store_level_vii:.)

12.43.1 The command \item in enumext*

_enumext_first_item_tmp_vii:

The _enumext_first_item_tmp_vii: function will remove horizontal space equal to \labelwidth plus \labelsep to the left of the first \item in the environment at the point of execution of this function, where it is equal to the _enumext_stop_item_tmp_vii: function inside the environment body definition.

```

4537 \cs_new_protected_nopar:Nn \__enumext_first_item_tmp_vii:
4538 {
4539   \skip_horizontal:n { -\l__enumext_labelwidth_vii_dim - \l__enumext_labelsep_vii_dim }
4540 }

```

(End of definition for _enumext_first_item_tmp_vii:.)

_enumext_start_item_tmp_vii:

First we will call the function _enumext_stop_item_tmp_vii: that we will redefine later, we will increment the value of \l__enumext_item_column_pos_vii_int that will count the item's by rows and the value of \g__enumext_item_count_all_vii_int that will count the total of item's in the environment. After that we will call the function _enumext_item_peek_args_vii: that will handle the arguments passed to \item.

```

4541 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_vii:
4542 {
4543   \__enumext_stop_item_tmp_vii:
4544   \int_incr:N \l__enumext_item_column_pos_vii_int
4545   \int_gincr:N \g__enumext_item_count_all_vii_int
4546   \__enumext_item_peek_args_vii:
4547 }

```

(End of definition for _enumext_start_item_tmp_vii:.)

_enumext_item_peek_args_vii:

The function _enumext_item_peek_args_vii: will handle the \item($\langle number \rangle$). Look for the argument “(”, if it is present we will call the function _enumext_joined_item_vii:w($\langle number \rangle$), which is in charge of joining the item's in the same row, in case they are not present we will set the default value (1).

```

4548 \cs_new_protected:Nn \__enumext_item_peek_args_vii:
4549 {
4550   \peek_meaning:NTF (
4551     { \__enumext_joined_item_vii:w }
4552     { \__enumext_joined_item_vii:w (1) }
4553   }

```

(End of definition for _enumext_item_peek_args_vii:.)

_enumext_joined_item_vii:w

The function _enumext_joined_item_vii:w will first call the function _enumext_starred_joined_item_vii:n in charge of setting the width of the box that will store the content passed to \item. Then we will look for the argument “*”, if it is present we will call the function _enumext_starred_item_vii:w otherwise we will call the function _enumext_standard_item_vii:w.

```

4554 \cs_new_protected:Npn \__enumext_joined_item_vii:w (#1)
4555 {

```

```

4556     \__enumext_starred_joined_item_vii:n {#1}
4557     \peek_meaning_remove:NTF *
4558     { \__enumext_starred_item_vii:w }
4559     { \__enumext_standar_item_vii:w }
4560 }

```

(End of definition for __enumext_joined_item_vii:w.)

__enumext_standar_item_vii:w

The function __enumext_standar_item_vii:w will first look for the argument “[”, if present it will set the state of the variable \l__enumext_wrap_label_opt_vii_bool equal to the state of the variable \l__enumext_wrap_label_opt_vii_bool handled by the key `wrap-label*` and finally execute the *non-enumerated* version `\item[⟨custom⟩]` by means of the function __enumext_start_item_vii:w, otherwise we will set the value of the variable \l__enumext_wrap_label_vii_bool handled by the `wrap-label` key to true and set the switch `\if@noitemarg` to true to execute the enumerated version of `\item` by means of the function __enumext_start_item_vii:w [\l__enumext_label_vii_tl].

```

4561 \cs_new_protected:Npn \__enumext_standar_item_vii:w
4562 {
4563     \bool_set_false:N \l__enumext_item_starred_vii_bool
4564     \peek_meaning:NTF [
4565     {
4566         \bool_set_eq:NN \l__enumext_wrap_label_vii_bool \l__enumext_wrap_label_opt_vii_bool
4567         \__enumext_start_item_vii:w
4568     }
4569     {
4570         \bool_set_true:N \l__enumext_wrap_label_vii_bool
4571         \legacy_if_set_true:n { @noitemarg }
4572         \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
4573     }
4574 }

```

(End of definition for __enumext_standar_item_vii:w.)

__enumext_starred_item_vii:w

The function __enumext_starred_item_vii:w together with the specified auxiliary functions `aux_i:w`, `aux_ii:w`, and `aux_iii:w` execute `\item*`, `\item*[⟨symbol⟩]` and `\item*[⟨symbol⟩][⟨offset⟩]`.

__enumext_starred_item_vii_aux_i:w

__enumext_starred_item_vii_aux_ii:w

__enumext_starred_item_vii_aux_iii:w

```

4575 \cs_new_protected:Npn \__enumext_starred_item_vii:w
4576 {
4577     \bool_set_true:N \l__enumext_item_starred_vii_bool
4578     \bool_set_true:N \l__enumext_wrap_label_vii_bool
4579     \peek_meaning:NTF [
4580     { \__enumext_starred_item_vii_aux_i:w }
4581     { \__enumext_starred_item_vii_aux_ii:w }
4582 }
4583 \cs_new_protected:Npn \__enumext_starred_item_vii_aux_i:w [#1]
4584 {
4585     \tl_gset:Nn \g__enumext_item_symbol_aux_vii_tl {#1}
4586     \__enumext_starred_item_vii_aux_ii:w
4587 }
4588 \cs_new_protected:Npn \__enumext_starred_item_vii_aux_ii:w
4589 {
4590     \peek_meaning:NTF [
4591     { \__enumext_starred_item_vii_aux_iii:w }
4592     {
4593         \dim_set_eq:NN \l__enumext_item_symbol_sep_vii_dim \l__enumext_labelsep_vii_dim
4594         \legacy_if_set_true:n { @noitemarg }
4595         \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
4596     }
4597 }
4598 \cs_new_protected:Npn \__enumext_starred_item_vii_aux_iii:w [#1]
4599 {
4600     \dim_set:Nn \l__enumext_item_symbol_sep_vii_dim {#1}
4601     \legacy_if_set_true:n { @noitemarg }
4602     \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
4603 }

```

(End of definition for __enumext_starred_item_vii:w and others.)

__enumext_fake_make_label_vii:n

The __enumext_fake_make_label_vii:n function will be in charge of handling our definition of `\item`. First we increment the counter `enumxvii` for the enumerated items and activate support for the *check answers* mechanism, followed by support for `\item*[⟨symbol⟩][⟨offset⟩]` if present, then the `wrap-label` and `wrap-label*` keys which we execute using `\makebox` whose width will be given by the `labelwidth` key and

position by the `align` key, inside the argument of this we will execute the `font` key together with the function defined by the `wrap-label` or `wrap-label*` keys. Finally we execute the `labelsep` key applying a *horizontal space*.

```

4604 \cs_new_protected_nopar:Npn \__enumext_fake_make_label_vii:n #1
4605 {
4606   \legacy_if:nT { @noitemarg }
4607   {
4608     \legacy_if_set_false:n { @noitemarg }
4609     \legacy_if:nT { @nmbrrlist }
4610     {
4611       \refstepcounter{enumXvii}
4612       \bool_if:NT \l__enumext_check_answers_bool
4613       {
4614         \int_gincr:N \g__enumext_item_number_int
4615         \bool_set_true:N \l__enumext_item_number_bool
4616       }
4617     }
4618   }
4619   \bool_if:NT \l__enumext_item_starred_vii_bool
4620   {
4621     \tl_if_blank:VT \g__enumext_item_symbol_aux_vii_tl
4622     {
4623       \tl_gset_eq:NN
4624       \g__enumext_item_symbol_aux_vii_tl \l__enumext_item_symbol_vii_tl
4625     }
4626     \mode_leave_vertical:
4627     \skip_horizontal:n { -\l__enumext_item_symbol_sep_vii_dim }
4628     \hbox_overlap_left:n { \g__enumext_item_symbol_aux_vii_tl }
4629     \skip_horizontal:N \l__enumext_item_symbol_sep_vii_dim
4630     \tl_gclear:N \g__enumext_item_symbol_aux_vii_tl
4631   }
4632   \makebox[ \l__enumext_labelwidth_vii_dim ][ \l__enumext_align_label_vii_str ]
4633   {
4634     \tl_use:N \l__enumext_label_font_style_vii_tl
4635     \bool_if:NTF \l__enumext_wrap_label_vii_bool
4636     {
4637       \__enumext_wrapper_label_vii:n {#1}
4638     }
4639     { #1 }
4640   }
4641   \skip_horizontal:N \l__enumext_labelsep_vii_dim
4642 }

```

(End of definition for `__enumext_fake_make_label_vii:n`.)

12.43.2 Real definition of `\item` in `enumext*`

The functions `__enumext_start_item_vii:w` and `__enumext_stop_item_vii:` executing the true definition of `\item` inside the `enumext*` environment, unlike the implementation in `shortlst` we will NOT use an extra group and the plain form of the `lrbox` environment.

`__enumext_start_item_vii:w` The first thing we will do is set the value of `__enumext_stop_item_tmp_vii:` equal to `__enumext_stop_item_vii:` which we will define later, after that we will start capturing `\item` and its *contents* in a *horizontal box* where the width will be `\itemwidth` plus `\labelwidth` plus `\labelsep`.

```

4643 \cs_new_protected_nopar:Npn \__enumext_start_item_vii:w [#1]
4644 {
4645   \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \__enumext_stop_item_vii:
4646   \hbox_set_to_wd:Nnw \l__enumext_item_text_vii_box
4647   {
4648     \l__enumext_joined_width_vii_dim
4649     + \l__enumext_labelwidth_vii_dim
4650     + \l__enumext_labelsep_vii_dim
4651   }

```

If `\DocumentMetadata` is not active and the state of the variable `\l__enumext_footnotes_key_bool` is false, we will redefine the `\footnote` command.

```

4652 \IfDocumentMetadataTF { }
4653 {
4654   \bool_if:NF \l__enumext_footnotes_key_bool
4655   {
4656     \__enumext_renew_footnote:

```

```

4657     }
4658 }

```

Now we insert our *sockets* for the tagPDF support and print `\item`.

```

4659     \__enumext_start_list_tag:n {enumext*}
4660     \__enumext_fake_make_label_vii:n {#1}
4661     \__enumext_stop_start_list_tag:

```

Finally we open the `minipage` environment capture the $\langle item\ content \rangle$ and execute the `first` key, `listparindent` key which will be equal to `\parindent`, the `parsep` key which will be equal to `\parskip` and the `itemindent` key.

```

4662     \__enumext_minipage:w [ t ]{ \__enumext_joined_width_vii_dim }
4663     \tl_use:N \__enumext_after_list_args_vii_tl
4664     \dim_set_eq:NN \parindent \__enumext_listparindent_vii_dim
4665     \skip_set_eq:NN \parskip \__enumext_parsep_vii_skip
4666     \tl_use:N \__enumext_fake_item_indent_vii_tl
4667 }

```

(End of definition for `__enumext_start_item_vii:w`.)

`__enumext_stop_item_vii:`

The `__enumext_stop_item_vii:` function will finish the fetching `\item` and its $\langle content \rangle$ by closing the `minipage` environment, the *sockets* for the tagPDF and the *horizontal box*.

```

4668 \cs_new_protected_nopar:Nn \__enumext_stop_item_vii:
4669 {
4670     \__enumext_endminipage:
4671     \__enumext_stop_list_tag:n {enumext*}
4672     \hbox_set_end:

```

Here we will reduce the *warnings* a bit by setting the value of `\hbadness` to `10000`, print the $\langle contents \rangle$ of the *box* along with `\footnote`.

```

4673     \int_set:Nn \hbadness { 10000 }
4674     \box_use_drop:N \__enumext_item_text_vii_box
4675     \IfDocumentMetadataTF { }
4676     {
4677         \bool_if:NF \__enumext_footnotes_key_bool
4678         {
4679             \__enumext_print_footnote:
4680         }
4681     }

```

Finally set the *vertical* and *horizontal* spaces between rows and columns.

```

4682     \int_compare:nNnTF
4683     { \__enumext_item_column_pos_vii_int } = { \__enumext_columns_vii_int }
4684     {
4685         \par\noindent
4686         \int_zero:N \__enumext_item_column_pos_vii_int
4687     }
4688     {
4689         \skip_horizontal:N \__enumext_columns_sep_vii_dim
4690     }
4691 }

```

(End of definition for `__enumext_stop_item_vii:`.)

`__enumext_remove_extra_parsep_vii:`

Finally we will remove the vertical space equal to `\parsep=itemsep` when the total number of items is divisible by the number of items in the last row of the environment. Here the use of `\unskip` or `\removeatlastskip` fails and does not obtain the expected result, using `\vspace` is the option and in this case, we can use a simplified version since we are always in $\langle vertical\ mode \rangle$.

```

4692 \cs_new_protected:Nn \__enumext_remove_extra_parsep_vii:
4693 {
4694     \int_compare:nNnT
4695     {
4696         \int_mod:nn
4697         { \__enumext_item_count_all_vii_int } { \__enumext_columns_vii_int }
4698     }
4699     =
4700     { 0 }
4701     {
4702         \para_end:
4703         \skip_vertical:n { -\__enumext_itemsep_vii_skip }
4704         \skip_vertical:N \c_zero_skip
4705         \int_gzero:N \__enumext_item_count_all_vii_int

```



```

4706     }
4707 }

```

As we don't want our check to be executed `check-ans` by levels but on the complete list, we will take it out of the `enumext*` environment using the “hook” function `__enumext_after_env:nn`.

```

4708 \__enumext_after_env:nn {enumext*} { \__enumext_execute_after_env: }

```

(End of definition for `__enumext_remove_extra_parsep_viii:`)

12.44 The environment `keyans*`

`keyans*` First we will generate the environment and we will give a temporary definition to `__enumext_stop_item_tmp_viii:` equal to `__enumext_first_item_tmp_viii:` and next to `\item` equal to `__enumext_start_item_tmp_viii:` which we will redefine later. The implementation of this environment is the same as that used by the `enumext*` environment except for the `__enumext_check_starred_cmd:n` function added in the second part.

```

4709 \NewDocumentEnvironment{keyans*}{ o }
4710 {
4711   \__enumext_safe_exec_viii:
4712   \__enumext_parse_keys_viii:n {#1}
4713   \__enumext_before_list_viii:
4714   \__enumext_start_list:nn { }
4715   {
4716     \__enumext_list_arg_two_viii:
4717     \__enumext_before_keys_exec_viii:
4718   }
4719   \IfDocumentMetadataTF { \tag_suspend:n {keyans*} } { }
4720   \__enumext_starred_columns_set_viii:
4721   \item[] \scan_stop:
4722   \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \__enumext_first_item_tmp_viii:
4723   \cs_set_eq:NN \item \__enumext_start_item_tmp_viii:
4724   \ignorespaces
4725 }
4726 {
4727   \IfDocumentMetadataTF { \tag_struct_end: } { }
4728   \__enumext_stop_item_tmp_viii:
4729   \__enumext_remove_extra_parsep_viii:
4730   \__enumext_check_starred_cmd:n { item }
4731   \__enumext_after_list_viii:
4732 }

```

(End of definition for `keyans*`. This function is documented on page 14.)

`__enumext_safe_exec_viii:` The `__enumext_safe_exec_viii:` function will first check if the `save-ans` key is active and only when this is true the environment will be available, it will increment the value of `\l__enumext_keyans_level_h_int` and return an error message when we are nesting the environment, then it will call the `__enumext_keyans_name_and_start:` function in charge of saving the name of the environment and the line it is running on, then it will check if we are trying to nest `keyans*` in `enumext*` returning an error and we will set `\l__enumext_starred_bool` to true, finally we will check if we are within the appropriate level within the `enumext` environment.

```

4733 \cs_new_protected:Nn \__enumext_safe_exec_viii:
4734 {
4735   \bool_if:NF \l__enumext_store_active_bool
4736   {
4737     \msg_error:nnnn { enumext } { wrong-place } { keyans* } { save-ans }
4738   }
4739   \int_incr:N \l__enumext_keyans_level_h_int
4740   \int_compare:nNnT { \l__enumext_keyans_level_h_int } > { 1 }
4741   {
4742     \msg_error:nn { enumext } { nested }
4743   }
4744   \__enumext_keyans_name_and_start:
4745   \bool_if:NT \l__enumext_starred_bool
4746   {
4747     \msg_error:nnn { enumext } { nested-horizontal } { enumext* }
4748   }
4749   \bool_set_true:N \l__enumext_starred_bool
4750   % Set false for interfering with enumext nested in keyans* (yes, its possible and crayze)
4751   \bool_set_false:N \l__enumext_store_active_bool
4752   \int_compare:nNnT { \l__enumext_level_int } > { 1 }
4753   {

```

```

4754         \msg_error:nn { enumext } { keyans-wrong-level }
4755     }
4756 }

```

(End of definition for `__enumext_safe_exec_viii:`)

```

\__enumext_parse_keys_viii:n Parse [<key = val>] for keyans*.
4757 \cs_new_protected:Npn \__enumext_parse_keys_viii:n #1
4758 {
4759     \tl_if_novalue:nF {#1}
4760     {
4761         \keys_set:nn { enumext / keyans* } {#1}
4762     }
4763 }

```

(End of definition for `__enumext_parse_keys_viii:n`)

`__enumext_before_list_viii:` The function `__enumext_before_list_viii:` will add the vertical spacing on the environment if the `above` key is active next to the `{<code>}` defined by the `before*` key if it is active, the call the function `__enumext_start_mini_viii:` handle by `mini-env`.

```

4764 \cs_new_protected:Nn \__enumext_before_list_viii:
4765 {
4766     \__enumext_vspace_above_viii:
4767     \__enumext_before_args_exec_viii:
4768     \__enumext_start_mini_viii:
4769 }

```

(End of definition for `__enumext_before_list_viii:`)

`__enumext_after_list_viii:` The function `__enumext_after_list:` first call the function `__enumext_stop_mini_viii:`, then apply the `{<code>}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```

4770 \cs_new_protected:Nn \__enumext_after_list_viii:
4771 {
4772     \__enumext_stop_mini_viii:
4773     \__enumext_after_stop_list_viii:
4774     \__enumext_vspace_below_viii:
4775 }

```

(End of definition for `__enumext_after_list_viii:`)

12.44.1 The command `\item` in `keyans*`

The idea here is to make the `\item` command behave in the same way as in the `keyans` environment with the difference of the optional argument (`<number>`) which works in the same way as in the `enumext*` environment. In simple terms we want to store the `<label>` next to the `[<content>]` if it is present in the `<sequence>` and `<prop list>` defined by `save-ans` key for `\item*`, `\item* [<content>]`, `\item (<number>)*` and `\item (<number>)* [<content>]` commands.

`__enumext_first_item_tmp_viii:` The `__enumext_first_item_tmp_viii:` function will remove horizontal space equal to `\labelwidth` plus `\labelsep` to the left of the first `\item` in the environment at the point of execution of this function, where it is equal to the `__enumext_stop_item_tmp_viii:` function inside the environment body definition.

```

4776 \cs_new_protected_nopar:Nn \__enumext_first_item_tmp_viii:
4777 {
4778     \skip_horizontal:n { -\__enumext_labelwidth_viii_dim - \__enumext_labelsep_viii_dim }
4779 }

```

(End of definition for `__enumext_first_item_tmp_viii:`)

`__enumext_start_item_tmp_viii:` First we will call the function `__enumext_stop_item_tmp_viii:` that we will redefine later, we will increment the value of `__enumext_item_column_pos_viii_int` that will count the item's by rows and the value of `\g__enumext_item_count_all_viii_int` that will count the total of item's in the environment. After that we will call the function `__enumext_item_peek_args_viii:` that will handle the arguments passed to `\item`.

```

4780 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_viii:
4781 {
4782     \__enumext_stop_item_tmp_viii:
4783     \int_incr:N \__enumext_item_column_pos_viii_int
4784     \int_gincr:N \g__enumext_item_count_all_viii_int
4785     \__enumext_item_peek_args_viii:
4786 }

```

(End of definition for __enumext_start_item_tmp_viii:.)

__enumext_item_peek_args_viii:

The function __enumext_item_peek_args_viii: will handle the \item(<number>). Look for the argument “(”, if it is present we will call the function __enumext_joined_item_viii:w (<number>), which is in charge of joining the item’s in the same row, in case they are not present we will set the default value (1).

```
4787 \cs_new_protected:Nn \__enumext_item_peek_args_viii:
4788 {
4789   \peek_meaning:NTF (
4790     { \__enumext_joined_item_viii:w }
4791     { \__enumext_joined_item_viii:w (1) }
4792   }
```

(End of definition for __enumext_item_peek_args_viii:.)

__enumext_joined_item_viii:w

The function __enumext_joined_item_viii:w will first call the function __enumext_starred_joined_item_viii:n in charge of setting the *width* of the box that will store the content passed to \item. Then we will look for the argument “*”, if it is present we will call the function __enumext_starred_item_viii:w otherwise we will call the function __enumext_standar_item_viii:w.

```
4793 \cs_new_protected:Npn \__enumext_joined_item_viii:w (#1)
4794 {
4795   \__enumext_starred_joined_item_viii:n {#1}
4796   \peek_meaning_remove:NTF *
4797   { \__enumext_starred_item_viii:w }
4798   { \__enumext_standar_item_viii:w }
4799 }
```

(End of definition for __enumext_joined_item_viii:w.)

__enumext_standar_item_viii:w

The function __enumext_standar_item_viii:w will first look for the argument “[”, if present it will set the state of the variable __enumext_wrap_label_opt_viii_bool equal to the state of the variable __enumext_wrap_label_opt_viii_bool handled by the key `wrap-label*` and finally execute the *non-enumerated* version \item[<custom>] by means of the function __enumext_start_item_viii:w, otherwise we will set the value of the variable __enumext_wrap_label_viii_bool handled by the `wrap-label` key to true and set the switch \if@noitemarg to true to execute the enumerated version of \item by means of the function __enumext_start_item_viii:w [__enumext_label_viii_tl].

```
4800 \cs_new_protected:Npn \__enumext_standar_item_viii:w
4801 {
4802   \bool_set_false:N \__enumext_item_starred_viii_bool
4803   \peek_meaning:NTF [
4804     {
4805       \bool_set_eq:NN \__enumext_wrap_label_viii_bool \__enumext_wrap_label_opt_viii_bool
4806       \__enumext_start_item_viii:w
4807     }
4808     {
4809       \bool_set_true:N \__enumext_wrap_label_viii_bool
4810       \legacy_if_set_true:n { @noitemarg }
4811       \__enumext_start_item_viii:w [ \__enumext_label_viii_tl ]
4812     }
4813 }
```

(End of definition for __enumext_standar_item_viii:w.)

__enumext_starred_item_viii:w

The function __enumext_starred_item_viii:w together with the specified auxiliary functions aux_i:w and aux_ii:w execute \item* and \item*[<content>].

__enumext_starred_item_viii_aux_i:w

__enumext_starred_item_viii_aux_ii:w

```
4814 \cs_new_protected:Npn \__enumext_starred_item_viii:w
4815 {
4816   \bool_set_true:N \__enumext_item_starred_viii_bool
4817   \bool_set_true:N \__enumext_wrap_label_viii_bool
4818   \peek_meaning:NTF [
4819     { \__enumext_starred_item_viii_aux_i:w }
4820     { \__enumext_starred_item_viii_aux_ii:w }
4821   }
```

The function __enumext_starred_item_viii_aux_i:w will save the optional argument to \item* in __enumext_store_current_opt_arg_tl and will save this argument along with the spacing set by the key `save-sep` in variable __enumext_store_current_label_tl if present, then call the function __enumext_starred_item_viii_aux_ii:w.

```
4822 \cs_new_protected:Npn \__enumext_starred_item_viii_aux_i:w [#1]
4823 {
4824   \tl_clear:N \__enumext_store_current_label_tl
```

```

4825 \tl_if_novalue:nF { #1 }
4826 {
4827   \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_tl
4828   {
4829     \tl_put_right:Ne \l__enumext_store_current_label_tl
4830     {
4831       \l__enumext_store_keyans_item_opt_sep_tl
4832     }
4833     \tl_put_right:Ne \l__enumext_store_current_label_tl { #1 }
4834   }
4835   \tl_set:Ne \l__enumext_store_current_opt_arg_tl { #1 }
4836 }
4837 \__enumext_starred_item_viii_aux_ii:w
4838 }
4839 \cs_new_protected:Npn \__enumext_starred_item_viii_aux_ii:w
4840 {
4841   \legacy_if_set_true:n { @noitemarg }
4842   \__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ]
4843 }

```

(End of definition for __enumext_starred_item_viii:w, __enumext_starred_item_viii_aux_i:w, and __enumext_starred_item_viii_aux_ii:w.)

__enumext_starred_item_exec:

The function __enumext_starred_item_exec: will be in charge of storing the current *label* for \item* followed by the [*content*] for \item* [*content*] if present in the *sequence* and *prop list* set by the save-ans key. In this same function the keys show-ans, show-pos and save-ref are implemented.

```

4844 \cs_new_protected:Nn \__enumext_starred_item_exec:
4845 {
4846   \tl_put_left:Ne \l__enumext_store_current_label_tl { \l__enumext_label_viii_tl }
4847   \__enumext_store_addto_prop:V \l__enumext_store_current_label_tl
4848   \__enumext_keyans_store_ref:
4849   \tl_put_left:Ne \l__enumext_store_current_label_tl { \item }
4850   \__enumext_keyans_addto_seq_link:
4851   \int_gincr:N \g__enumext_check_starred_cmd_int
4852   \bool_if:NT \l__enumext_show_answer_bool
4853   {
4854     \__enumext_print_keyans_box:NN \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
4855   }
4856   \bool_if:NT \l__enumext_show_position_bool
4857   {
4858     \tl_set:Ne \l__enumext_mark_answer_sym_tl
4859     {
4860       \group_begin:
4861       \exp_not:N \normalfont
4862       \exp_not:N \footnotesize [ \int_eval:n
4863       {
4864         \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
4865       }
4866       ]
4867       \group_end:
4868     }
4869     \__enumext_print_keyans_box:NN \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
4870   }
4871 }

```

(End of definition for __enumext_starred_item_exec:.)

__enumext_fake_make_label_viii:n

The implementation at this is very similar to that of the enumext* environment.

```

4872 \cs_new_protected_nopar:Npn \__enumext_fake_make_label_viii:n #1
4873 {
4874   \legacy_if:nT { @noitemarg }
4875   {
4876     \legacy_if_set_false:n { @noitemarg }
4877     \legacy_if:nT { @nmbrrlist }
4878     {
4879       \refstepcounter{enumXviii}
4880     }
4881   }
4882   \bool_if:NT \l__enumext_item_starred_viii_bool
4883   {
4884     \__enumext_starred_item_exec:

```

```

4885     }
4886     \makebox[ \l__enumext_labelwidth_viii_dim ][ \l__enumext_align_label_viii_str ]
4887     {
4888         \tl_use:N \l__enumext_label_font_style_viii_tl
4889         \bool_if:NTF \l__enumext_wrap_label_viii_bool
4890         {
4891             \__enumext_wrapper_label_viii:n {#1}
4892         }
4893         { #1 }
4894     }
4895     \skip_horizontal:N \l__enumext_labelsep_viii_dim
4896 }

```

(End of definition for __enumext_fake_make_label_viii:n.)

12.44.2 Real definition of \item in keyans*

The implementation at this is very similar to that of the `enumext*` environment.

```

4897 \cs_new_protected_nopar:Npn \__enumext_start_item_viii:w [#1]
4898 {
4899     \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \__enumext_stop_item_viii:
4900     \hbox_set_to_wd:Nnw \l__enumext_item_text_viii_box
4901     {
4902         \l__enumext_joined_width_viii_dim
4903         + \l__enumext_labelwidth_viii_dim
4904         + \l__enumext_labelsep_viii_dim
4905     }
4906     \IfDocumentMetadataTF { }
4907     {
4908         \bool_if:NF \l__enumext_footnotes_key_bool
4909         {
4910             \__enumext_renew_footnote:
4911         }
4912     }
4913     \__enumext_start_list_tag:n {keyans*}
4914     \__enumext_fake_make_label_viii:n {#1}
4915     \__enumext_stop_start_list_tag:
4916     \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_viii_dim }
4917     \tl_use:N \l__enumext_after_list_args_viii_tl
4918     \dim_set_eq:NN \parindent \l__enumext_listparindent_viii_dim
4919     \skip_set_eq:NN \parskip \l__enumext_parsep_viii_skip
4920     \bool_if:NT \l__enumext_item_starred_viii_bool
4921     {
4922         \tl_use:N \l__enumext_fake_item_indent_viii_tl
4923         \__enumext_keyans_show_item_opt:
4924         \skip_horizontal:n { -\l__enumext_fake_item_indent_viii_dim - \l__enumext_labelsep_viii_dim }
4925     }
4926     {
4927         \tl_use:N \l__enumext_fake_item_indent_viii_tl
4928     }
4929 }

```

(End of definition for __enumext_start_item_viii:w.)

The `__enumext_stop_item_viii:` function will finish the fetching `\item` and its *content* by closing the `minipage` environment and the *horizontal box*. Here we will reduce the *warnings* a bit by setting the value of `\hbadness` to `10000`, print the *contents* of the *box* along with `\footnote` and finally set the vertical and horizontal spaces between rows and columns.

```

4930 \cs_new_protected_nopar:Nn \__enumext_stop_item_viii:
4931 {
4932     \__enumext_endminipage:
4933     \__enumext_stop_list_tag:n {keyans*}
4934     \hbox_set_end:
4935     \int_set:Nn \hbadness { 10000 }
4936     \box_use_drop:N \l__enumext_item_text_viii_box
4937     \IfDocumentMetadataTF { }
4938     {
4939         \bool_if:NF \l__enumext_footnotes_key_bool
4940         {
4941             \__enumext_print_footnote:
4942         }
4943     }

```

```

4944 \int_compare:nNnTF
4945 { \l__enumext_item_column_pos_viii_int } = { \l__enumext_columns_viii_int }
4946 {
4947   \par\noindent
4948   \int_zero:N \l__enumext_item_column_pos_viii_int
4949 }
4950 {
4951   \skip_horizontal:N \l__enumext_columns_sep_viii_dim
4952 }
4953 }

```

(End of definition for `__enumext_stop_item_viii:`)

`__enumext_remove_extra_parsep_viii:`

Finally we will remove the *vertical space* equal to `\parsep` when the total number of items is divisible by the number of items in the last row of the environment.

```

4954 \cs_new_protected:Nn \__enumext_remove_extra_parsep_viii:
4955 {
4956   \int_compare:nNnT
4957   {
4958     \int_mod:nn
4959     { \g__enumext_item_count_all_viii_int }
4960     { \l__enumext_columns_viii_int }
4961   }
4962   =
4963   { 0 }
4964   {
4965     \para_end:
4966     \skip_vertical:n { -\l__enumext_itemsep_viii_skip }
4967     \skip_vertical:N \c_zero_skip
4968     \int_gzero:N \g__enumext_item_count_all_viii_int
4969   }
4970 }

```

(End of definition for `__enumext_remove_extra_parsep_viii:`)

12.45 The command `\getkeyans`

`\getkeyans`

The `\getkeyans` command takes a mandatory argument of the form $\langle \textit{store name} : \textit{position} \rangle$. Retrieve a “single” content stored by `\anskey`, `\anspic*` and `\item*` from $\langle \textit{prop list} \rangle$ defined by `save-ans` key.

```

4971 \NewDocumentCommand \getkeyans { m }
4972 {
4973   \exp_args:Ne \__enumext_getkeyans_aux:n
4974   { \tl_to_str:e { \text_expand:n {#1} } }
4975 }

```

(End of definition for `\getkeyans`. This function is documented on page 16.)

`__enumext_getkeyans_aux:n`

The internal function `__enumext_getkeyans_aux:n` is in charge of *splitting* the $\langle \textit{argument} \rangle$ using “.”. If “.” is omitted it will return an error.

```

4976 \cs_new_protected:Npn \__enumext_getkeyans_aux:n #1
4977 {
4978   \str_if_in:nnTF {#1} { : }
4979   {
4980     \use:e
4981     {
4982       \cs_set:Npn \exp_not:N \__enumext_tmp:w ##1 \c_colon_str ##2 \scan_stop:
4983       { {##1} {##2} }
4984     }
4985     \exp_after:wN \__enumext_getkeyans:nn \__enumext_tmp:w #1 \scan_stop:
4986   }
4987   { \msg_error:nnn { enumext } { missing-colon } {#1} }
4988 }

```

(End of definition for `__enumext_getkeyans_aux:n`)

`__enumext_getkeyans:nn`

The internal function `__enumext_getkeyans:nn` will check for the existence of the $\langle \textit{prop list} \rangle$, if it does not exist it will return an error message, then it will fetch the content specified by the second $\langle \textit{argument} \rangle$ from $\langle \textit{prop list} \rangle$.

```

4989 \cs_new_protected:Npn \__enumext_getkeyans:nn #1 #2
4990 {
4991   \prop_if_exist:cTF { g__enumext_#1_prop }

```

```

4992     {
4993       \prop_item:cn { g__enumext_#1_prop }{#2}
4994     }
4995     {
4996       \msg_error:nnn { enumext } { undefined-storage-anskey } {#1}
4997     }
4998   }

```

(End of definition for `__enumext_getkeyans:nn`.)

12.46 The command `\printkeyans`

The `\printkeyans` command prints “all stored content” in the *sequence* defined by the `save-ans` key. The first thing we will do is define a set of *filtered keys* with which we will control the options of the different nesting levels for the environment `enumext` and `enumext*` by storing their values in the list of tokens `\l__enumext_print_keyans_X_tl`.

The variable `\l__enumext_print_keyans_starred_tl` will have the default *keys* for `\printkeyans*` and will be set by `\setenumext[print*]` and the variable `\l__enumext_print_keyans_vii_tl` will have the default keys for the environment `enumext*` nested within the *sequence* and will be set by `\setenumext[print,*]`, the rest of the variables will be for the environment `enumext` and will be set by `\setenumext[print, level]`.

```

4999 \keys_define:nn { enumext / print }
5000 {
5001   print* .code:n      = \keys_precompile:neN { enumext / enumext* }
5002                     { \__enumext_filter_save_key:n {#1} }
5003                     \l__enumext_print_keyans_starred_tl, % starred cmd
5004   print* .initial:n   = { nosep, label=\arabic*., columns=2, first=\small, font=\small },
5005   print-1 .code:n     = \keys_precompile:neN { enumext / level-1 }
5006                     { \__enumext_filter_save_key:n {#1} }
5007                     \l__enumext_print_keyans_i_tl,
5008   print-1 .initial:n  = { nosep, label=\arabic*., columns=2, first=\small, font=\small },
5009   print-2 .code:n     = \keys_precompile:neN { enumext / level-2 }
5010                     { \__enumext_filter_save_key:n {#1} }
5011                     \l__enumext_print_keyans_ii_tl,
5012   print-2 .initial:n  = { nosep, label=(\alph*), first=\small, font=\small },
5013   print-3 .code:n     = \keys_precompile:neN { enumext / level-3 }
5014                     { \__enumext_filter_save_key:n {#1} }
5015                     \l__enumext_print_keyans_iii_tl,
5016   print-3 .initial:n  = { nosep, label=\roman*., first=\small, font=\small },
5017   print-4 .code:n     = \keys_precompile:neN { enumext / level-4 }
5018                     { \__enumext_filter_save_key:n {#1} }
5019                     \l__enumext_print_keyans_iv_tl,
5020   print-4 .initial:n  = { nosep, label=\Alph*., first=\small, font=\small },
5021   print-* .code:n     = \keys_precompile:neN { enumext / enumext* }
5022                     { \__enumext_filter_save_key:n {#1} }
5023                     \l__enumext_print_keyans_vii_tl, % starred nested
5024   print-* .initial:n  = { nosep, label=\arabic*., first=\small, font=\small },
5025 }

```

🔗 The reason for storing *keys* in token lists using `\keys_precompile:neN` is because the keys are set via `\setenumext` but are later executed by running the command `\printkeyans` and they are not handled directly by its optional argument, except those related to the first opening level.

`\printkeyans` Create a user command to print “all stored content” in *sequence* for `\anskey`, `anskey*`, `\item*` and `\anspic*`. Within a group we will run our “precompiled keys” and then call the internal function `__enumext_printkeyans:nnn`.

```

5026 \NewDocumentCommand \printkeyans { s O{} m }
5027 {
5028   \group_begin:
5029     \tl_use:N \l__enumext_print_keyans_i_tl
5030     \tl_use:N \l__enumext_print_keyans_ii_tl
5031     \tl_use:N \l__enumext_print_keyans_iii_tl
5032     \tl_use:N \l__enumext_print_keyans_iv_tl
5033     \tl_use:N \l__enumext_print_keyans_vii_tl
5034     \__enumext_printkeyans:nnn { #1 } { #2 } { #3 }
5035   \group_end:
5036 }

```

(End of definition for `\printkeyans`. This function is documented on page 17.)


```
\__enumext_printkeyans:nnn
```

The internal function `__enumext_printkeyans:nnn` will check for the existence of the *sequence*, if it does not exist it will return an error message, then it will check if not empty.

```
5037 \cs_new_protected:Npn \__enumext_printkeyans:nnn #1 #2 #3
5038 {
5039   \seq_if_exist:cTF { g__enumext_#3_seq }
5040   {
5041     \seq_if_empty:cF { g__enumext_#3_seq }
5042     {
5043       %%\seq_show:c { g__enumext_#3_seq }
```

If the starred argument is present we will check that the environment `enumext*` is not saved in the *sequence*, then execute the variable `\l__enumext_print_keyans_starred_tl` that contains the default *keys* for the environment `enumext*`, it will open the environment `enumext*` passing the optional argument to the “first level”, set the key `base-fix` and then will map the *sequence*.

```
5044   \bool_if:nTF {#1}
5045   {
5046     \seq_if_in:cnTF { g__enumext_#3_seq } { \end{enumext*} }
5047     {
5048       \msg_error:nnnn { enumext } { print-starred } {#3} { enumext* }
5049     }
5050     {
5051       \tl_use:N \l__enumext_print_keyans_starred_tl
5052       % \IfDocumentMetadataTF { \tag_tool:n {para/flattened} } { }
5053       \begin{enumext*}[#2]
5054         \keys_set:nn { enumext / level-1 }{ base-fix }
5055         \seq_map_inline:cn { g__enumext_#3_seq } { ##1 }
5056         \end{enumext*}
5057       }
5058     }
```

Otherwise it will open the environment `enumext` passing the optional argument to the “first level”, set the key `base-fix` and then map the *sequence*.

```
5059     {
5060       \begin{enumext}[#2]
5061         \keys_set:nn { enumext / enumext* }{ base-fix }
5062         \seq_map_inline:cn { g__enumext_#3_seq } { ##1 }
5063         \end{enumext}
5064       }
5065     }
5066   }
5067   {
5068     \msg_error:nnn { enumext } { undefined-storage-anskey } {#3}
5069   }
5070 }
```

(End of definition for `__enumext_printkeyans:nnn`.)

12.47 The command `\setenumext`

The command `\setenumext` will be in charge of managing the *keys* passed to all environments and to the `\printkeyans` command. We must take precautions with the `enumext*` environment and “first level” of the `enumext` environment so as not to capture *keys* that complicate us.

```
\__enumext_filter_first_level:n
\__enumext_filter_first_level_key:n
\__enumext_filter_first_level_pair:nn
```

The function `__enumext_filter_first_level:n` will be in charge of filtering the *keys* passed to the environment `enumext*` and “first level” of the environment `enumext`.

```
5071 \cs_new:Npn \__enumext_filter_first_level:n #1
5072 {
5073   \use:e
5074   {
5075     \keyval_parse:NNn
5076     \__enumext_filter_first_level_key:n
5077     \__enumext_filter_first_level_pair:nn {#1}
5078   }
5079 }
```

The function `__enumext_filter_first_level_key:n` will be responsible for filtering the *keys* that are passed “without value” by excluding the keys `resume` and `resume*`.

```
5080 \cs_new:Npn \__enumext_filter_first_level_key:n #1
5081 {
5082   \str_case:nnF {#1}
5083   {
5084     { resume } {}
```

```

5085     { resume* } {}
5086   }
5087   { , { \exp_not:n {#1} } }
5088 }

```

The function `__enumext_filter_first_level_pair:nn` will be responsible for filtering the *⟨keys⟩* that are passed “with value” by excluding the `series`, `resume` and `save-ans` keys.

```

5089 \cs_new:Npn \__enumext_filter_first_level_pair:nn #1#2
5090 {
5091   \str_case:nnF {#1}
5092   {
5093     { series } {}
5094     { resume } {}
5095     { save-ans } {}
5096   }
5097   { , { \exp_not:n {#1} } = { \exp_not:n {#2} } }
5098 }

```

(End of definition for `__enumext_filter_first_level:n`, `__enumext_filter_first_level_key:n`, and `__enumext_filter_first_level_pair:nn`.)

Now define a “meta families” of *⟨keys⟩* to access from `\setenumext`.

```

5099 \keys_define:nn { enumext / meta-families }
5100 {
5101   enumext-1 .code:n =
5102   {
5103     \keys_set:ne { enumext / level-1 }
5104     {
5105       \__enumext_filter_first_level:n {#1}
5106     }
5107   } ,
5108   enumext-2 .code:n = { \keys_set:nn { enumext / level-2 } {#1} } ,
5109   enumext-3 .code:n = { \keys_set:nn { enumext / level-3 } {#1} } ,
5110   enumext-4 .code:n = { \keys_set:nn { enumext / level-4 } {#1} } ,
5111   keyans .code:n = { \keys_set:nn { enumext / keyans } {#1} } ,
5112   enumext* .code:n =
5113   {
5114     \keys_set:ne { enumext / enumext* }
5115     {
5116       \__enumext_filter_first_level:n {#1}
5117     }
5118   } ,
5119   keyans* .code:n = { \keys_set:nn { enumext / keyans* } {#1} } ,
5120   print* .code:n = { \keys_set:nn { enumext / print } { print* = {#1} } } ,
5121   print-1 .code:n = { \keys_set:nn { enumext / print } { print-1 = {#1} } } ,
5122   print-2 .code:n = { \keys_set:nn { enumext / print } { print-2 = {#1} } } ,
5123   print-3 .code:n = { \keys_set:nn { enumext / print } { print-3 = {#1} } } ,
5124   print-4 .code:n = { \keys_set:nn { enumext / print } { print-4 = {#1} } } ,
5125   print-* .code:n = { \keys_set:nn { enumext / print } { print-* = {#1} } } ,
5126   unknown .code:n = { \msg_error:nn { enumext } { unknown-key-family } } ,
5127 }

```

We store them in the constant sequence `\c__enumext_all_families_seq` separated by commas.

```

5128 \seq_const_from_clist:Nn \c__enumext_all_families_seq
5129 {
5130   enumext-1, enumext-2, enumext-3, enumext-4, keyans, enumext*,
5131   keyans*, print-1, print-2, print-3, print-4, print-*, print*,
5132 }

```

`\setenumext` Now we define the user command `\setenumext`.

```

5133 \NewDocumentCommand \setenumext { 0{enumext,1} +m }
5134 {
5135   \seq_clear:N \l__enumext_setkey_tmpa_seq
5136   \seq_set_from_clist:Nn \l__enumext_setkey_tmpb_seq {#1}
5137   \int_set:Nn \l__enumext_setkey_tmpa_int
5138   {
5139     \seq_count:N \l__enumext_setkey_tmpb_seq
5140   }
5141   \int_compare:nNnTF { \l__enumext_setkey_tmpa_int } > { 1 }
5142   {
5143     \seq_pop_left:NN \l__enumext_setkey_tmpb_seq \l__enumext_setkey_tmpa_tl
5144     \seq_map_function:NN \l__enumext_setkey_tmpb_seq \__enumext_set_parse:n

```

```

5145         \seq_set_map:e:NNn \l__enumext_setkey_tmpa_seq \l__enumext_setkey_tmpa_seq
5146         {
5147             \tl_use:N \l__enumext_setkey_tmpa_tl - ##1
5148         }
5149     }
5150     {
5151         \seq_put_right:Ne \l__enumext_setkey_tmpa_seq { \tl_trim_spaces:n {#1} }
5152     }
5153     \seq_if_empty:NTF \l__enumext_setkey_tmpa_seq
5154     { \seq_map_inline:Nn \c__enumext_all_families_seq }
5155     { \seq_map_inline:Nn \l__enumext_setkey_tmpa_seq }
5156     {
5157         \keys_set:nn { enumext / meta-families } { ##1 = {#2} }
5158     }
5159 }

```

(End of definition for `\setenumext`. This function is documented on page 6.)

`__enumext_set_parse:n`
`__enumext_set_error:nn`

Internal functions used by the `\setenumext` command.

```

5160 \cs_new_protected:Npn \__enumext_set_parse:n #1
5161 {
5162     \tl_set:Ne \l__enumext_setkey_tmpb_tl { \tl_trim_spaces:n {#1} }
5163     \clist_map_inline:nn { 0, 1, 2, 3, 4, * } % <- max level
5164     { \tl_remove_all:Nn \l__enumext_setkey_tmpb_tl {##1} }
5165     \tl_if_empty:NTF \l__enumext_setkey_tmpb_tl
5166     {
5167         \seq_put_right:Ne \l__enumext_setkey_tmpa_seq
5168         { \tl_trim_spaces:n {#1} }
5169     }
5170     { \__enumext_set_error:nn {#1} { } }
5171 }
5172 \cs_new_protected:Npn \__enumext_set_error:nn #1 #2
5173 { \msg_error:nnn { enumext } { invalid-key } {#1} {#2} }

```

(End of definition for `__enumext_set_parse:n` and `__enumext_set_error:nn`.)

12.48 The command `\setenumextmeta`

The command `\setenumextmeta` will be responsible for adding new “meta-keys” for the `enumext` and `enumext*` environments. The implementation code was given by Jonathan P. Spratte (@Skillmon) answer in [Add .meta key to existing keys \(l3keys\)](#).

`\setenumextmeta`

First we will create a prop list `\c__enumext_meta_paths_prop` to handle the optional argument.

`\c__enumext_meta_paths_prop`
`__enumext_add_meta_key:nnn`
`__enumext_def_meta_key:nnn`
`__enumext_def_meta_key:Vnn`

```

5174 \prop_const_from_keyval:Nn \c__enumext_meta_paths_prop
5175 {
5176     {enumext,1} = level-1,
5177     {enumext,2} = level-2,
5178     {enumext,3} = level-3,
5179     {enumext,4} = level-4,
5180     {enumext*} = enumext*
5181 }

```

Now we create the user command taking care that unknown cannot be passed as an argument.

```

5182 \NewDocumentCommand \setenumextmeta { s O{enumext,1} m +m }
5183 {
5184     \str_if_eq:eeTF { \tl_trim_spaces:n {#3} } { unknown }
5185     { \msg_error:nn { enumext } { prohibited-unknown } }
5186     {
5187         \bool_if:nTF {#1}
5188         {
5189             \int_step_inline:nn { 4 }
5190             { \__enumext_add_meta_key:nnn { enumext, ##1 } {#3} {#4} }
5191             \__enumext_add_meta_key:nnn { enumext* } {#3} {#4}
5192         }
5193         { \__enumext_add_meta_key:nnn {#2} {#3} {#4} }
5194     }
5195 }

```

The internal functions `__enumext_add_meta_key:nnn` and `__enumext_def_meta_key:nnn` will check the optional argument and create the “meta-key”.

```

5196 \cs_new_protected:Npn \__enumext_add_meta_key:nnn #1
5197 {
5198     \tl_set:Nn \l__enumext_meta_path_tl {#1}

```

```

5199 \tl_replace_all:Nnn \l__enumext_meta_path_tl { ~ } {}
5200 \prop_get:NVNTF
5201 \c__enumext_meta_paths_prop \l__enumext_meta_path_tl \l__enumext_meta_path_tl
5202 { \__enumext_def_meta_key:Vnn \l__enumext_meta_path_tl }
5203 {
5204   \msg_error:nnn { enumext } { unknown-set } {#1}
5205   \use_none:nn
5206 }
5207 }
5208 \cs_new_protected:Npn \__enumext_def_meta_key:nnn #1#2#3
5209 {
5210   \bool_lazy_or:nnTF
5211   { \keys_if_exist_p:nn { enumext / #1 } {#2} }
5212   { \keys_if_exist_p:nn { enumext / enumext* } {#2} }
5213   { \msg_error:nnn { enumext } { already-defined } {#2} }
5214   {
5215     \keys_define:nn { enumext / #1 }
5216     {
5217       #2 .meta:n = {#3},
5218       #2 .value_forbidden:n = true
5219     }
5220   }
5221 }
5222 \cs_generate_variant:Nn \__enumext_def_meta_key:nnn { V }

```

(End of definition for `\setenumextmeta` and others. This function is documented on page 6.)

12.49 The command `\foreachkeyans`

The command `\foreachkeyans` will execute a *loop* over the `<prop list>` and return its contents. The implementation code is adapted from the answer provided by Enrico Gregorio (@egreg) in [Expand a .cs defined by key inside the function](#).

We define a set of `<keys>` for command and we will save the default values of these in `\g__enumext_foreach_default_keys_tl` to avoid the use of group.

```

5223 \keys_define:nn { enumext / foreach }
5224 {
5225   before .tl_set:N = \l__enumext_foreach_before_tl,
5226   before .value_required:n = true,
5227   after .tl_set:N = \l__enumext_foreach_after_tl,
5228   after .value_required:n = true,
5229   start .int_set:N = \l__enumext_foreach_start_int,
5230   start .value_required:n = true,
5231   stop .int_set:N = \l__enumext_foreach_stop_int,
5232   stop .value_required:n = true,
5233   step .int_set:N = \l__enumext_foreach_step_int,
5234   step .value_required:n = true,
5235   wrapper .cs_set_protected:Np = \__enumext_foreach_wrapper:n #1,
5236   wrapper .value_required:n = true,
5237   sep .tl_set:N = \l__enumext_foreach_sep_tl,
5238   sep .value_required:n = true,
5239   unknown .code:n = { \__enumext_parse_foreach_keys:n {#1} }
5240 }
5241 \keys_precompile:nnN { enumext / foreach }
5242 {
5243   before={},after={},start=1,step=1,stop=0,wrapper=#1,sep=
5244 }
5245 \g__enumext_foreach_default_keys_tl

```

Functions for handling unknown `<keys>`.

```

5246 \cs_new_protected:Npn \__enumext_parse_foreach_keys:nn #1#2
5247 {
5248   \tl_if_blank:nTF {#2}
5249   {
5250     \msg_error:nnn { enumext } { for-key-unknown } {#1}
5251   }
5252   {
5253     \msg_error:nnnn { enumext } { for-key-value-unknown } {#1} {#2}
5254   }
5255 }
5256 \cs_new_protected:Npn \__enumext_parse_foreach_keys:n #1
5257 {

```

```

5258 \exp_args:NV \__enumext_parse_foreach_keys:nn \l_keys_key_str {#1}
5259 }

```

We create the command.

```

5260 \NewDocumentCommand \foreachkeyans { +0{} m }
5261 {
5262   \__enumext_foreach_keys:nn {#1} {#2}
5263 }

```

Finally the internal functions `__enumext_foreach_keys:nn` and `__enumext_foreach_add_body:n` will loop through the prop list and print the contents.

```

5264 \cs_new_protected:Npn \__enumext_foreach_keys:nn #1 #2
5265 {
5266   \tl_use:N \g__enumext_foreach_default_keys_tl
5267   \keys_set:nn { enumext / foreach } {#1}
5268   \tl_set:Nn \l__enumext_foreach_name_prop_tl {#2}
5269   \prop_if_exist:cF { g__enumext_#2_prop }
5270   {
5271     \msg_error:nnn { enumext } { undefined-storage-anskey } {#2}
5272   }
5273   \int_compare:nNt { \l__enumext_foreach_stop_int } = { 0 }
5274   {
5275     \int_set:Nn \l__enumext_foreach_stop_int
5276     { \prop_count:c { g__enumext_#2_prop } }
5277   }
5278   \seq_clear:N \l__enumext_foreach_print_seq
5279   \int_step_function:nnnN
5280   { \l__enumext_foreach_start_int }
5281   { \l__enumext_foreach_step_int }
5282   { \l__enumext_foreach_stop_int }
5283   \__enumext_foreach_add_body:n
5284   \seq_use:NV \l__enumext_foreach_print_seq \l__enumext_foreach_sep_tl
5285 }
5286 \cs_new_protected:Npn \__enumext_foreach_add_body:n #1
5287 {
5288   \seq_put_right:Ne \l__enumext_foreach_print_seq
5289   {
5290     \exp_not:V \l__enumext_foreach_before_tl
5291     \__enumext_foreach_wrapper:n
5292     {
5293       \prop_item:cn { g__enumext_ \l__enumext_foreach_name_prop_tl _prop }{#1}
5294     }
5295     \exp_not:V \l__enumext_foreach_after_tl
5296   }
5297 }

```

(End of definition for `\foreachkeyans` and others. This function is documented on page 16.)

12.50 Messages

Message used by package-load for `multicol` and `hyperref` packages.

```

5298 \msg_new:nnn { enumext } { package-load }
5299 {
5300   The ~ '#1' ~ package ~ is ~ already ~ loaded.
5301 }
5302 \msg_new:nnn { enumext } { package-not-load }
5303 {
5304   The ~ '#1' ~ package ~ will ~ be ~ loaded ~ as ~ a ~ dependency.
5305 }
5306 \msg_new:nnn { enumext } { package-load-foot }
5307 {
5308   The ~ '#1' ~ package ~ is ~ loaded ~ with ~ the ~ option ~ '#2'.
5309 }

```

Message used in the creation of counters by `enumext` package.

```

5310 \msg_new:nnn { enumext } { counters }
5311 {
5312   The ~ counter ~ '#1' ~ is ~ already ~ defined ~ by ~ some ~ \
5313   package ~ or ~ macro, ~ it ~ cannot ~ be ~ continued.
5314 }

```

Message used by `align` and `mark-pos` keys.

```

5315 \msg_new:nnn { enumext } { unknown-choice }

```

```

5316 {
5317     The ~ value ~ '#3' ~ for ~ '#1' ~ key ~ is ~ invalid ~ use ~ ('#2').
5318 }

```

Message used by reserved **anskey*** environment by **enumext** package.

```

5319 \msg_new:nnnn { enumext } { anskey-env-error }
5320 {
5321     The ~ '#1' ~ environment ~is~ reserved ~ by ~\
5322     'enumext' ~ package, ~ It~ is~ already~ defined.
5323 }
5324 {
5325     The ~ anskey* ~ environment ~ is ~ defined ~ internally ~
5326     for ~ the ~ 'save-ans' ~ key.\
5327 }

```

Message used in the creation of *(prop list)* by **enumext** package.

```

5328 \msg_new:nnn { enumext } { store-prop }
5329 {
5330     * ~ Package ~ enumext: ~ Creating ~
5331     \c_backslash_str g__enumext_#1_prop ~ \msg_line_context:.
5332 }
5333 \msg_new:nnn { enumext } { store-seq }
5334 {
5335     * ~ Package ~ enumext: ~ Creating ~
5336     \c_backslash_str g__enumext_#1_seq ~ \msg_line_context:.
5337 }
5338 \msg_new:nnn { enumext } { store-int }
5339 {
5340     * ~ Package ~ enumext: ~ Creating ~
5341     \c_backslash_str g__enumext_resume_#1_int ~ \msg_line_context:.
5342 }
5343 \msg_new:nnn { enumext } { prop-seq-int-hook }
5344 {
5345     * ~ Package ~ enumext: ~ Elements ~ in ~
5346     \c_backslash_str g__enumext_#1_prop ~ = ~ #2.\
5347     * ~ Package ~ enumext: ~ Elements ~ in ~
5348     \c_backslash_str g__enumext_#1_seq ~ = ~ #3.\
5349     * ~ Package ~ enumext: ~ Value ~ off ~
5350     \c_backslash_str g__enumext_resume_#1_int ~ = ~ #4.
5351 }
5352 \msg_new:nnn { enumext } { item-answer-hook }
5353 {
5354     * ~ Package ~ enumext: ~ Value ~ off ~
5355     \c_backslash_str g__enumext_item_number_int ~ = ~ #1.\
5356     * ~ Package ~ enumext: ~ Value ~ off ~
5357     \c_backslash_str g__enumext_item_anskey_int ~ = ~ #2.\
5358     * ~ Package ~ enumext: ~ Difference ~ item_number_int ~ - ~ item_anskey_int ~ = ~ #3.
5359 }

```

Message used by *[(key = val)]* system and **\setenumext** command.

```

5360 \msg_new:nnn { enumext } { invalid-key }
5361 {
5362     The ~ key ~ '#1' ~ is ~ not ~ know ~ the ~ level ~ #2.
5363 }
5364 \msg_new:nnn { enumext } { unknown-key-family }
5365 {
5366     Unknown~key~family~`\l_keys_key_str'~for~enumext.
5367 }

```

Messages used in length calculation.

```

5368 \msg_new:nnn { enumext } { width-negative }
5369 {
5370     Ignoring ~ negative ~ value ~ '#1=#2' ~ \msg_line_context:.\\
5371     The ~ key ~ '#1'~ accepts ~ values ~ >= ~ 0pt.
5372 }
5373 \msg_new:nnn { enumext } { width-zero }
5374 {
5375     Invalid ~ '#1=#2' ~ \msg_line_context:.\\
5376     The ~ key ~ '#1'~ accepts ~ values ~ > ~ 0pt.
5377 }

```

Messages used by **show-length** key in **enumext**.

```

5378 \msg_new:nnn { enumext } { list-lengths }

```

```

5379 {
5380     **** ~ Lengths ~ used ~ by ~ 'enumext' ~ level ~ '#2' ~ \msg_line_context:~\c_space_tl ****\\
5381     \__enumext_show_length:nnn { dim } { labelsep } {#1}
5382     \__enumext_show_length:nnn { dim } { labelwidth } {#1}
5383     \__enumext_show_length:nnn { dim } { itemindent } {#1}
5384     \__enumext_show_length:nnn { dim } { leftmargin } {#1}
5385     \__enumext_show_length:nnn { dim } { rightmargin } {#1}
5386     \__enumext_show_length:nnn { dim } { listparindent } {#1}
5387     \__enumext_show_length:nnn { skip } { topsep } {#1}
5388     \__enumext_show_length:nnn { skip } { parsep } {#1}
5389     \__enumext_show_length:nnn { skip } { partopsep } {#1}
5390     \__enumext_show_length:nnn { skip } { itemsep } {#1}
5391     *****
5392 }

```

Messages used by `show-length` key in `enumext*`, `keyans*` and `keyans`.

```

5393 \msg_new:nnn { enumext } { list-lengths-not-nested }
5394 {
5395     **** ~ Lengths ~ used ~ by ~ '#2' ~ environment ~ \msg_line_context:~\c_space_tl ****\\
5396     \__enumext_show_length:nnn { dim } { labelsep } {#1}
5397     \__enumext_show_length:nnn { dim } { labelwidth } {#1}
5398     \__enumext_show_length:nnn { dim } { itemindent } {#1}
5399     \__enumext_show_length:nnn { dim } { leftmargin } {#1}
5400     \__enumext_show_length:nnn { dim } { rightmargin } {#1}
5401     \__enumext_show_length:nnn { dim } { listparindent } {#1}
5402     \__enumext_show_length:nnn { skip } { topsep } {#1}
5403     \__enumext_show_length:nnn { skip } { parsep } {#1}
5404     \__enumext_show_length:nnn { skip } { partopsep } {#1}
5405     \__enumext_show_length:nnn { skip } { itemsep } {#1}
5406     *****
5407 }

```

Messages used by `ref` key.

```

5408 \msg_new:nnn { enumext } { key-ref-empty }
5409 {
5410     Key ~ 'ref' ~ need ~ a ~ value ~ in ~ '#1'~ \msg_line_context:.
5411 }

```

Messages used by `save-ans` key.

```

5412 \msg_new:nnn { enumext } { save-ans-empty }
5413 {
5414     Key ~ 'save-ans' ~ need ~ a ~ value ~ in ~ '#1'~ \msg_line_context:.
5415 }
5416 \msg_new:nnn { enumext } { save-ans-log }
5417 {
5418     * ~ Package ~ enumext: ~ Start ~ #1\c_space_tl with ~ save-ans=#2 ~ \msg_line_context:.
5419 }
5420 \msg_new:nnn { enumext } { save-ans-log-hook }
5421 {
5422     * ~ Package ~ enumext: ~ Stop ~ #1\c_space_tl with ~ save-ans=#2 ~ \msg_line_context:.
5423 }
5424 \msg_new:nnn { enumext } { save-ans-hook }
5425 {
5426     Stop ~ storing ~ for ~ 'save-ans=#1' ~ \msg_line_context:.
5427 }

```

Messages used by the internal system to check answer used by `check-ans` key.

```

5428 \msg_new:nnn { enumext } { need-save-ans }
5429 {
5430     Key ~ '#1'~ works ~ only ~ with ~ the ~ 'save-ans' ~ key ~ in ~ '#2'~ \msg_line_context:.
5431 }
5432 \msg_new:nnn { enumext } { items-same-answer }
5433 {
5434     *****\\
5435     * ~ Package ~ enumext: ~ Checking ~ answers ~ in ~ '#1' ~
5436     for ~ \c_left_brace_str #2 \c_right_brace_str\\
5437     * ~ started ~ #3 ~ and ~ close ~ \msg_line_context: : ~
5438     'OK', ~ all ~ items ~ with ~ answer.\\
5439     *****
5440 }
5441 \msg_new:nnn { enumext } { item-greater-answer }
5442 {
5443     Checking ~ answers ~ in ~ '#1' ~ for ~ \c_left_brace_str #2 \c_right_brace_str\\

```



```

5444     started ~ #3 ~ and ~ close ~ \msg_line_context: : ~'NOT ~ OK'\
5445     Items ~ > ~ Answers.
5446 }
5447 \msg_new:nnn { enumext } { item-less-answer }
5448 {
5449     Checking ~ answers ~ in ~ '#1' ~ for ~ \c_left_brace_str #2 \c_right_brace_str\
5450     started ~ #3 ~ and ~ close ~ \msg_line_context: : ~'NOT ~ OK'\
5451     Items ~ < ~ Answers.
5452 }

```

Messages used by the internal system to check for “starred” `\item*` and `\anspic*` commands.

```

5453 \msg_new:nnn { enumext } { missing-starred }
5454 {
5455     Missing ~ '\c_backslash_str #1*' ~ #2.
5456 }
5457 \msg_new:nnn { enumext } { many-starred }
5458 {
5459     Many ~ '\c_backslash_str #1*' ~ #2.
5460 }

```

Messages used by `\printkeyans*` command.

```

5461 \msg_new:nnn { enumext } { print-starred }
5462 {
5463     \c_backslash_str printkeyans*:~ The ~ sequence ~ '#1' ~ already ~ contains ~
5464     #2 ~ environment ~ \msg_line_context:.
5465 }

```

Message for the nesting depth of the environment `enumext`.

```

5466 \msg_new:nnn { enumext } { list-too-deep }
5467 {
5468     Too ~ deep ~ nesting ~ for ~ 'enumext' ~ \msg_line_context::~ \
5469     The ~ maximum ~ level ~ of ~ nesting ~ is ~ 4.
5470 }

```

Messages used by `\anskey`, `anskey*` and `\anspic` commands.

```

5471 \msg_new:nnn { enumext } { anskey-unnumber-item }
5472 {
5473     Can't ~ store ~ with ~ a ~ unnumbered ~ \c_backslash_str item ~ \msg_line_context:.
5474 }
5475 \msg_new:nnn { enumext } { anskey-already-stored }
5476 {
5477     Content ~ already ~ stored ~ for ~ this ~ \c_backslash_str item ~ \msg_line_context:.
5478 }
5479 \msg_new:nnn { enumext } { anskey-empty-arg }
5480 {
5481     Can't ~ store ~ empty ~ content ~ \msg_line_context:.
5482 }
5483 \msg_new:nnn { enumext } { anskey-wrong-place }
5484 {
5485     Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context::~ \
5486     '\c_backslash_str #1' ~ works ~ in ~ the ~ environment ~ '#2'.
5487 }
5488 \msg_new:nnn { enumext } { anskey-nested }
5489 {
5490     The ~ command ~ \c_backslash_str anskey~ can't ~ be ~ nested ~ \msg_line_context:.
5491 }
5492 \msg_new:nnn { enumext } { anskey-math-mode }
5493 {
5494     #1 ~ can't ~ work ~ in ~ math ~ mode ~ \msg_line_context:.
5495 }
5496 \msg_new:nnn { enumext } { anskey-env-wrong }
5497 {
5498     The ~ environment ~ anskey* ~ cannot ~ use ~ in ~ '#1' ~ \msg_line_context:.
5499 }
5500 \msg_new:nnn { enumext } { anspic-wrong-place }
5501 {
5502     Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context::~ \
5503     '\c_backslash_str #1' ~ works ~ in ~ the ~ environment ~ '#2'.
5504 }
5505 \msg_new:nnn { enumext } { command-wrong-place }
5506 {
5507     Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context::~ \
5508     '\c_backslash_str #1' ~ works ~ outside ~ the ~ environment ~ '#2'.

```

```

5509     }
5510     \msg_new:nnnn { enumext } { anskey-env-key-unknown }
5511     {
5512         The ~ key ~ '#1' ~ is ~ unknown ~ by ~ environment~
5513         'anskey*' ~ and ~ is ~ being ~ ignored.
5514     }
5515     {
5516         The ~ environment ~ 'anskey*' ~ does ~ not ~ have ~ a ~ key ~ called ~'#1'.\\
5517         Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5518     }
5519     \msg_new:nnnn { enumext } { anskey-env-key-value-unknown }
5520     {
5521         The ~ key ~ '#1=#2' ~ is ~ unknown ~ by ~ environment ~
5522         'anskey*' ~ and ~ is ~ being ~ ignored.
5523     }
5524     {
5525         The ~ environment ~ 'anskey*' ~ does ~ not ~ have ~ a ~ key ~ called ~'#1'.\\
5526         Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5527     }
5528     \msg_new:nnnn { enumext } { anskey-cmd-key-unknown }
5529     { The ~ key ~ '#1' ~ is ~ unknown ~ by ~ '\c_backslash_str anskey' ~ and ~ is ~ being ~ ignored.}
5530     {
5531         The ~ command ~ '\c_backslash_str anskey' ~ does ~ not ~ have ~ a ~ key ~ called ~'#1'.\\
5532         Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5533     }
5534     \msg_new:nnnn { enumext } { anskey-cmd-key-value-unknown }
5535     { The ~ key ~ '#1=#2' ~ is ~ unknown ~ by ~ '\c_backslash_str anskey' ~ and ~ is ~ being ~ ignored.}
5536     {
5537         The ~ command ~ '\c_backslash_str anskey' ~ does ~ not ~ have ~ a ~ key ~ called ~'#1'.\\
5538         Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5539     }

```

Messages used by `keyans`, `keyans*` and `keyanspic` environment.

```

5540     \msg_new:nnn { enumext } { keyans-nested }
5541     {
5542         The ~ environment ~ 'keyans' ~ can't ~ be ~ nested ~ \msg_line_context:.
5543     }
5544     \msg_new:nnn { enumext } { keyans-wrong-level }
5545     {
5546         Wrong ~ level ~ position ~ for ~ 'keyans' ~ \msg_line_context:~ \\
5547         The ~ environment ~ 'keyans' ~ can ~ only ~ be ~ in ~ the ~ first ~ level.
5548     }
5549     \msg_new:nnn { enumext } { wrong-place }
5550     {
5551         Wrong ~ place ~ for ~ '#1' ~ environment ~\msg_line_context:~ \\
5552         '#1' ~ is ~ only ~ found ~ with ~ '#2' ~ in ~ 'enumext.
5553     }
5554     \msg_new:nnn { enumext } { keyanspic-nested }
5555     {
5556         The ~ environment ~ 'keyanspic' ~ can't ~ be ~ nested~ \msg_line_context:~.
5557     }
5558     \msg_new:nnn { enumext } { keyanspic-wrong-level }
5559     {
5560         Wrong ~ level ~ position ~ for ~ 'keyanspic' ~ \msg_line_context:~ \\
5561         The ~ environment ~ 'keyans' ~ can ~ only ~ be ~ in ~ the ~ first ~ level.
5562     }
5563     \msg_new:nnn { enumext } { keyanspic-item-cmd }
5564     {
5565         Can't ~ use ~ \c_backslash_str item ~ in ~ keyanspic ~ \msg_line_context:.
5566     }
5567     \msg_new:nnnn { enumext } { keyans-unknown-key }
5568     {
5569         The ~ key ~ '#1' ~ is ~ unknown ~ by ~ environment~
5570         '\l_enumext_envir_name_tl' ~ and ~ is ~ being ~ ignored.
5571     }
5572     {
5573         The ~ environment ~ '\l_enumext_envir_name_tl' ~ does ~ not
5574         ~ have ~ a ~ key ~ called ~'#1'.\\
5575         Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5576     }
5577     \msg_new:nnnn { enumext } { keyans-unknown-key-value }
5578     {

```

```

5579     The ~ key ~ '#1=#2' ~ is ~ unknown ~ by ~ environment ~
5580     '\l__enumext_envir_name_tl' ~ and ~ is ~ being ~ ignored.
5581   }
5582   {
5583     The ~ environment ~ '\l__enumext_envir_name_tl' ~ does ~ not
5584     ~ have ~ a ~ key ~ called ~ '#1'.\\
5585     Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5586   }

```

Message used by unknown $\langle keys \rangle$ in `enumext*`. environment.

```

5587 \msg_new:nnnn { enumext } { starred-unknown-key }
5588 {
5589   The ~ key ~ '#1' ~ is ~ unknown ~ by ~ environment~
5590   '\l__enumext_envir_name_tl' ~ and ~ is ~ being ~ ignored.
5591 }
5592 {
5593   The ~ environment ~ '\l__enumext_envir_name_tl' ~ does ~ not
5594   ~ have ~ a ~ key ~ called ~ '#1'.\\
5595   Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5596 }
5597 \msg_new:nnnn { enumext } { starred-unknown-key-value }
5598 {
5599   The ~ key ~ '#1=#2' ~ is ~ unknown ~ by ~ environment ~
5600   '\l__enumext_envir_name_tl' ~ and ~ is ~ being ~ ignored.
5601 }
5602 {
5603   The ~ environment ~ '\l__enumext_envir_name_tl' ~ does ~ not
5604   ~ have ~ a ~ key ~ called ~ '#1'.\\
5605   Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5606 }

```

Message used by unknown $\langle keys \rangle$ in `enumext` environment.

```

5607 \msg_new:nnnn { enumext } { standar-unknown-key }
5608 {
5609   The ~ key ~ '#1' ~ is ~ unknown ~ by ~ environment ~ '\l__enumext_envir_name_tl' \c_space_tl
5610   ~ on ~ level ~ \int_use:N \l__enumext_level_int \c_space_tl and ~ is ~ being ~ ignored.
5611 }
5612 {
5613   The ~ environment ~ '\l__enumext_envir_name_tl' ~ does ~ not
5614   ~ have ~ a ~ key ~ called ~ '#1' ~ on ~ level ~ \int_use:N \l__enumext_level_int.\\
5615   Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5616 }
5617 \msg_new:nnnn { enumext } { standar-unknown-key-value }
5618 {
5619   The ~ key ~ '#1=#2' ~ is ~ unknown ~ by ~ environment ~ '\l__enumext_envir_name_tl' \c_space_
5620   ~ on ~ level ~ \int_use:N \l__enumext_level_int \c_space_tl and ~ is ~ being ~ ignored.
5621 }
5622 {
5623   The ~ environment ~ '\l__enumext_envir_name_tl' ~ does ~ not
5624   ~ have ~ a ~ key ~ called ~ '#1' ~ on ~ level ~ \int_use:N \l__enumext_level_int.\\
5625   Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
5626 }

```

Message used by unknown $\langle keys \rangle$ in `\foreachkeyans`.

```

5627 \msg_new:nnnn { enumext } { for-key-unknown }
5628 { The~key~'#1'~is~unknown~by~'\c_backslash_str foreachkeyans'~and~is~being~ignored.}
5629 {
5630   The~command~'\c_backslash_str foreachkeyans'~does~not~have~a~key~called~'#1'.\\
5631   Check~that~you~have~spelled~the~key~name~correctly.
5632 }
5633 \msg_new:nnnn { enumext } { for-key-value-unknown }
5634 { The~key~'#1=#2'~is~unknown~by~'\c_backslash_str foreachkeyans'~and~is~being~ignored. }
5635 {
5636   The~command~'\c_backslash_str foreachkeyans'~does~not~have~a~key~called~'#1'.\\
5637   Check~that~you~have~spelled~the~key~name~correctly.
5638 }

```

Messages used by `\getkeyans` command.

```

5639 \msg_new:nnn { enumext } { undefined-storage-anskey }
5640 {
5641   Storage ~ named ~ '#1' ~ is ~ not ~ defined ~ \msg_line_context:.
5642 }

```

Messages used by `\miniright` command.

```

5643 \msg_new:nnn { enumext } { missing-miniright }
5644 {
5645   Missing ~ '\c_backslash_str miniright' ~ in ~ \msg_line_context:.\
5646   The ~ key ~ 'mini-env' ~ need ~ '\c_backslash_str miniright'.
5647 }
5648 \msg_new:nnn { enumext } { wrong-miniright-place }
5649 {
5650   Wrong ~ place ~ for ~ '\c_backslash_str miniright' ~ \msg_line_context:.\
5651   Works ~ in ~ 'enumext' ~ and ~ 'keyans' ~ with ~ key ~ 'mini-env'.
5652 }
5653 \msg_new:nnn { enumext } { wrong-miniright-use }
5654 {
5655   Wrong ~ use ~ for ~ '\c_backslash_str miniright' ~ \msg_line_context:.\
5656   '\c_backslash_str miniright' ~ need ~ a ~ key ~ 'mini-env'.
5657 }
5658 \msg_new:nnn { enumext } { wrong-miniright-starred }
5659 {
5660   Can't ~ use ~ \c_backslash_str miniright ~ in ~ starred ~ environments ~ \msg_line_context:.\
5661 }
5662 \msg_new:nnn { enumext } { many-miniright-used }
5663 {
5664   Can't ~ use ~ \c_backslash_str miniright ~ more ~ than ~ once ~ \msg_line_context:.\
5665 }

```

Messages used by `\setenumextmeta` command.

```

5666 \msg_new:nnn { enumext } { unknown-set }
5667 {
5668   Argument ~ [#1] ~ is ~ unknown ~ by ~ \c_backslash_str setenumextmeta ~ \msg_line_context:.\
5669 }
5670 \msg_new:nnn { enumext } { already-defined }
5671 {
5672   The ~ key ~ '#1' ~ is ~ already ~ defined ~ \msg_line_context:.\
5673 }
5674 \msg_new:nnn { enumext } { prohibited-unknown }
5675 {
5676   The ~ name ~ 'unknown' ~ can't ~ be ~ chosen~ for ~ a ~ meta ~ key ~ \msg_line_context:.\
5677 }

```

Messages used by `enumext*` and `keyans*` environments.

```

5678 \msg_new:nnn { enumext } { nested }
5679 {
5680   The ~ environment ~ \l__enumext_envir_name_tl \c_space_tl can't ~ be ~ nested ~ \msg_line_context:.\
5681 }
5682 \msg_new:nnn { enumext } { nested-horizontal }
5683 {
5684   The ~ environment ~ \l__enumext_envir_name_tl \c_space_tl can't ~ be ~ nested ~ in ~ '#1' ~ \
5685 }
5686 \msg_new:nnn { enumext } { item-joined }
5687 {
5688   Items ~ joined ~ (#1) ~ > ~ #2 ~ columns ~ \msg_line_context:.\
5689 }
5690 \msg_new:nnn { enumext } { item-joined-columns }
5691 {
5692   Not ~ space ~ to ~ join ~ items ~ (#1) ~ > ~ #2 ~ \msg_line_context:.\
5693 }

```

12.51 Finish package

Finish package implementation.

```

5694 \file_input_stop:
5695 </package>

```

13 Index of Implementation

The *italic* numbers denote the pages where the corresponding entry is described, the numbers underlined and all others indicate the line on which they are implemented in the package code.

Symbols	
<code>*</code>	226
<code>\+</code>	218
<code>\-</code>	218
<code>\\</code>	234, 2780, 4128, 5312, 5321, 5326, 5346, 5348, 5355, 5357, 5370, 5375, 5380, 5395, 5434, 5436, 5438, 5443, 5444, 5449, 5450, 5468, 5485, 5502, 5507, 5516, 5525, 5531, 5537, 5546, 5551, 5560, 5574, 5584, 5594, 5604, 5614, 5624, 5630, 5636, 5645, 5650, 5655
A	
<code>above</code>	<u>1595</u>
<code>above*</code>	<u>1595</u>
<code>\addvspace</code>	1164, 1193, 1236, 1239, 1407, 1410, 1507, 1513, 1548, 1554, 1575, 1581, 3642, 3782, 3800, 4000, 4003, 4333, 4348, 4394, 4408
<code>after</code>	<u>993</u>
<code>align</code>	<u>536</u>
<code>\Alph</code>	38, 42, 43
<code>\Alpha</code>	488, 606, 651, 719, 5020
<code>\alph</code>	38, 42, 43
<code>\alpha</code>	489, 604, 5012
<code>\anskey</code>	12, 76, 78, <u>2598</u>
<code>anskey*</code>	13, <u>2708</u>
<code>\anspic</code>	15, 104, 107, <u>4036</u>
<code>\anspic*</code>	70
<code>\arabic</code>	31, 38
<code>\arabic</code>	487, 603, 650, 5004, 5008, 5024
B	
<code>base-fix</code>	<u>849</u>
<code>\baselineskip</code>	<u>51</u>
<code>\baselineskip</code>	866, 877
<code>before</code>	<u>993</u>
<code>before*</code>	<u>993</u>
<code>below</code>	<u>1595</u>
<code>below*</code>	<u>1595</u>
bool commands:	
<code>\bool_gset_false:N</code>	357, 358, 359, 2884, 2886, 4350, 4354, 4410
<code>\bool_gset_true:N</code>	265, 275, 1096, 2088, 2094, 4319, 4351, 4383, 4411
<code>\bool_if:NTF</code>	427, 439, 456, 1529, 1617, 1631, 1644, 1655, 1666, 1677, 1688, 1699, 1748, 1765, 1770, 1778, 1805, 1843, 1848, 1855, 1859, 1881, 1886, 1894, 1901, 1932, 1940, 2033, 2231, 2241, 2320, 2344, 2351, 2375, 2473, 2495, 2535, 2548, 2552, 2602, 2621, 2645, 2699, 2710, 2799, 2836, 2900, 2933, 2948, 3023, 3034, 3038, 3057, 3070, 3112, 3146, 3189, 3208, 3350, 3365, 3427, 3437, 3469, 3474, 3575, 3623, 3651, 3710, 3765, 3790, 3936, 3998, 4038, 4057, 4103, 4312, 4328, 4334, 4377, 4391, 4395, 4519, 4529, 4612, 4619, 4635, 4654, 4677, 4735, 4745, 4852, 4856, 4882, 4889, 4908, 4920, 4939
<code>\bool_if:nTF</code>	1555, 1582, 3168, 3324, 3385, 3915, 4079, 5044, 5187
<code>\bool_if_p:N</code>	284, 299, 862, 863, 873, 874, 1912, 1913, 1921, 1922, 2046, 2072, 2085, 2086, 2091, 2092, 2408, 2418, 2430, 2445, 2446, 2480, 2521, 2522, 2822, 3010, 3011, 3048, 3049, 3548, 3550, 3561, 4086, 4087
<code>\bool_lazy_all:nTF</code>	282, 297, 2044, 2070, 2406, 2415, 2428, 2443, 3546, 3559
<code>\bool_lazy_and:nnTF</code>	261, 271, 861, 872, 1522, 1911, 1920, 2084, 2090, 2479, 2486, 2520, 2663, 2675, 2821, 2827, 3009
<code>\bool_lazy_or:nnTF</code>	1973, 1980, 3047, 4085, 5210
<code>\bool_new:N</code>	34, 35, 36, 37, 38, 39, 40, 41, 64, 73, 96, 101, 102, 107, 108, 111, 136, 137, 144, 151, 152, 157, 159, 160, 174, 186, 188
<code>\bool_not_p:n</code>	262, 272, 2417, 2481, 2487, 2823, 2828, 3549, 3562
<code>\bool_set_eq:NN</code>	3121, 3304, 4566, 4805
<code>\bool_set_false:N</code>	436, 883, 2018, 2019, 2051, 2056, 2060, 2064, 2077, 2763, 3523, 3668, 3718, 3805, 3933, 4005, 4487, 4514, 4563, 4751, 4802
<code>\bool_set_true:N</code>	289, 290, 304, 305, 416, 420, 529, 898, 1601, 1606, 1868, 1990, 1991, 2263, 2271, 2764, 3115, 3117, 3149, 3151, 3300, 3312, 3449, 3522, 3555, 3568, 3594, 3715, 3742, 3917, 4301, 4366, 4486, 4570, 4577, 4578, 4615, 4749, 4809, 4816, 4817
box commands:	
<code>\box_dp:N</code>	1453, 1454, 1457, 1464, 1477, 1485, 1491, 1499, 3946, 3951, 4000, 4114
<code>\box_ht:N</code>	1236, 1239, 1250, 1251, 1262, 1264, 1279, 1282, 1290, 1291, 1302, 1304, 1319, 1322, 1329, 1330, 1341, 1343, 1358, 1361, 1407, 1410, 1418, 1419, 1427, 1428, 1440, 1442
<code>\box_ht_plus_dp:N</code>	3942, 4066
<code>\box_new:N</code>	70, 147, 148, 181, 187
<code>\box_use_drop:N</code>	4345, 4406, 4674, 4936
<code>\box_wd:N</code>	495
C	
<code>\c</code>	226, 227, 756, 758, 770, 772
<code>\catcode</code>	2780
<code>\cB</code>	227
<code>\cE</code>	227
<code>\centering</code>	1557, 1584, 4026, 4338, 4399
<code>check-ans</code>	<u>2010</u>
Document class:	
<code>article</code>	44
clist commands:	
<code>\clist_const:Nn</code>	193
<code>\clist_map_function:nN</code>	4009
<code>\clist_map_inline:Nn</code>	535, 804, 992, 1007, 1088, 1611
<code>\clist_map_inline:nn</code>	49, 60, 78, 86, 98, 110, 139, 168, 192, 566, 586, 858, 903, 924, 1102, 1717, 1957, 2024, 2210, 2228, 2260, 2403, 2942, 3229, 3241, 3281, 3414, 3417, 3444, 3456, 3459, 3479, 5163
<code>\columnbreak</code>	76
<code>\columnbreak</code>	2483
<code>columns</code>	<u>1072</u>
<code>columns-sep</code>	<u>1072</u>
<code>\columnsep</code>	99
<code>\columnsep</code>	3618, 3763
<code>\columnseprule</code>	99
<code>\columnseprule</code>	3621, 3764
Commands provide by enumext :	
<code>\anskey</code>	29, 66, 67, 72, 73, 75, 77, 78, 85, 87, 97, 116, 125,

126, 134	
\anspic*	29, 30, 70, 73, 85, 86, 106, 107, 125, 126
\anspic	29, 73, 104, 106, 107, 134
\foreachkeyans	130, 136
\getkeyans	73, 125, 136
\item* 29, 30, 70, 73, 85, 86, 88, 89, 92, 117, 122, 123, 125, 126	
\item	88, 92, 110, 116–118, 121, 122
\miniright	28, 49, 57, 58, 98, 100, 137
\printkeyans*	126
\printkeyans	29, 73, 126
\setenumextmeta	129, 137
\setenumext	29, 126, 128, 129, 132
Counters defined by enumext :	
enumXiii	27, 37
enumXii	27, 37
enumXiv	27, 37
enumXi	27, 37
enumXviii	27, 37
enumXvii	27, 37, 117
enumXvi	27, 37
enumXv	27, 37
cs commands:	
\cs_generate_variant:Nn	198, 199, 497, 513, 762, 778, 2312, 2317, 2393, 2716, 3404, 4011, 5222
\cs_if_exist:NTF	467
\cs_if_free:NTF	2667, 2679
\cs_new:Nn	212
\cs_new:Npn	230, 1718, 1727, 1735, 2275, 2284, 2292, 5071, 5080, 5089
\cs_new_eq:NN	384, 385, 390, 391, 441, 442, 445, 446
\cs_new_protected:Nn	222, 254, 280, 313, 343, 349, 355, 361, 367, 375, 393, 411, 627, 690, 742, 859, 1008, 1012, 1016, 1020, 1024, 1028, 1032, 1036, 1040, 1044, 1048, 1052, 1056, 1060, 1064, 1068, 1103, 1115, 1148, 1166, 1177, 1195, 1221, 1242, 1367, 1393, 1413, 1446, 1468, 1503, 1509, 1612, 1626, 1640, 1651, 1662, 1673, 1684, 1695, 1776, 1879, 1892, 1909, 1930, 1958, 1963, 1988, 2029, 2039, 2082, 2097, 2104, 2113, 2118, 2123, 2128, 2137, 2142, 2147, 2318, 2342, 2349, 2373, 2380, 2394, 2619, 2638, 2654, 2717, 2753, 2784, 2819, 2861, 2882, 2890, 2931, 2946, 2974, 3007, 3043, 3055, 3068, 3154, 3164, 3175, 3183, 3199, 3320, 3336, 3344, 3358, 3498, 3515, 3544, 3573, 3580, 3602, 3632, 3649, 3691, 3708, 3732, 3749, 3774, 3788, 3931, 4007, 4012, 4123, 4131, 4162, 4291, 4310, 4356, 4375, 4415, 4419, 4438, 4473, 4501, 4508, 4517, 4527, 4548, 4692, 4733, 4764, 4770, 4787, 4844, 4954
\cs_new_protected:Npn	200, 204, 208, 236, 449, 465, 482, 492, 498, 607, 652, 724, 749, 763, 1539, 1568, 1744, 1763, 1833, 1866, 1968, 2152, 2229, 2239, 2261, 2269, 2304, 2313, 2469, 2532, 2546, 2584, 2588, 2708, 2739, 2743, 2774, 2910, 2984, 3028, 3108, 3127, 3242, 3246, 3260, 3264, 3282, 3286, 3296, 3308, 3373, 3407, 3447, 3526, 3728, 3907, 3924, 4055, 4075, 4099, 4193, 4242, 4490, 4554, 4561, 4575, 4583, 4588, 4598, 4757, 4793, 4800, 4814, 4822, 4839, 4976, 4989, 5037, 5160, 5172, 5196, 5208, 5246, 5256, 5264, 5286
\cs_new_protected_nopar:Nn	3841, 3883, 3891, 3899, 4537, 4541, 4668, 4776, 4780, 4930
\cs_new_protected_nopar:Npn	3833, 3849, 4604, 4643, 4872, 4897
\cs_set:Npn	2404, 2441, 4982
\cs_set_eq:NN	4463, 4464, 4645, 4722, 4723, 4899
\cs_set_protected:Nn	929, 945, 958, 971
\cs_set_protected:Npn	45, 54, 71, 79, 93, 99, 132, 164, 172, 514, 536, 571, 587, 634, 779, 805, 849, 885, 908, 984, 993, 1072, 1089, 1595, 1706, 1949, 2010, 2169, 2211, 2247, 2396, 2935, 3218, 3234, 3274, 3405, 3445
\cs_to_str:N	484, 507
\cs_undefine:N	2656, 2657, 2658, 2659
D	
\d	218
\DeclareDocumentEnvironment	397
dim commands:	
\dim_abs:n	3378, 3383
\dim_add:Nn	3950, 4156, 4187
\dim_compare:nNnTF	931, 947, 960, 973, 1254, 1266, 1294, 1306, 1333, 1345, 1422, 1430, 1541, 1570, 3375, 3380, 3386, 3392, 3394, 3396, 3585, 3607, 3736, 3753, 3926, 4133, 4149, 4164, 4180, 4293, 4358
\dim_compare:nTF	2505, 2849, 3504, 3697
\dim_eval:n	4110
\dim_gset_eq:NN	4302, 4367
\dim_gzero:N	2888, 4353, 4413
\dim_new:N	67, 74, 75, 76, 95, 141, 149, 150, 180, 182, 183, 189
\dim_set:Nn	495, 899, 3144, 3378, 3383, 3385, 3388, 3389, 3393, 3395, 3398, 3399, 3401, 3500, 3588, 3610, 3693, 3738, 3755, 3940, 4014, 4064, 4135, 4142, 4166, 4173, 4228, 4277, 4295, 4360, 4600
\dim_set_eq:NN	594, 641, 712, 716, 3059, 3060, 3072, 3073, 3139, 3416, 3458, 3618, 3763, 4235, 4238, 4239, 4284, 4287, 4288, 4593, 4664, 4918
\dim_sub:Nn	3509, 3702, 4151, 4182
\dim_use:N	932, 940, 1542, 1552, 2383, 2386, 2391, 3159, 3161, 3204, 3506, 3511, 3586, 3591, 3592, 3598, 3608, 3612, 3613, 3615
\dim_zero:N	3450, 3621, 3764, 3952, 3953, 3954
\dim_zero_new:N	464
\c_zero_dim	934, 948, 961, 974, 1542, 1570, 2507, 2851, 3375, 3380, 3386, 3393, 3506, 3586, 3608, 3699, 3736, 3753, 3926, 4133, 4149, 4164, 4180, 4293, 4358
\dimeval	2176
E	
\end	2346, 2377, 3639, 3779, 3994, 4028, 5046, 5056, 5063
end internal commands:	
\end__enumext__mini_page	1550, 1577, 3660, 3799, 4317, 4381, 4407
\endgroup	2780
\endlist	385
\endminipage	391
enumext	5, <u>3480</u>
enumext internal commands:	
\l__enumext__ref_the_count_tl	40
\l__enumext__resume_name_tl	62
__enumext_add_meta_key:nnn	129, <u>5174</u> , 5190, 5191, 5193, 5196
__enumext_add_pre_parsep:	50, 1113, <u>1115</u> , 1115
__enumext_after_args_exec:	47, <u>1008</u> , 1020, 3493
__enumext_after_args_exec_v:	<u>1024</u> , 1036, 3684
__enumext_after_args_exec_vii:	<u>1040</u> , 1064
__enumext_after_args_exec_viii:	1068
__enumext_after_env:nn	82–84, 100, 112, 120, <u>204</u> , 204, 2794, 3671, 4326, 4389, 4708
__enumext_after_hyperref:	35, 409, <u>411</u> , 411
__enumext_after_list:	99, 121, 3496, <u>3649</u> , 3649
\l__enumext_after_list_args_v_tl	1038

`\l__enumext_after_list_args_vii_tl` 1066, 4663
`\l__enumext_after_list_args_viii_tl` .. 1070, 4917
`__enumext_after_list_v` : ... 3689, 3732, 3788
`__enumext_after_list_vii`: 115, 4471, 4508, 4508
`__enumext_after_list_viii`: .. 4731, 4770, 4770
`__enumext_after_stop_list`: 47, 100, 1008, 1016, 3665
`__enumext_after_stop_list_v`: 1024, 1032, 3806
`\l__enumext_after_stop_list_v_tl` : ... 1034
`__enumext_after_stop_list_vii`: .. 115, 1040, 1056, 4511
`\l__enumext_after_stop_list_vii_tl` : ... 1058
`__enumext_after_stop_list_viii`: . 1060, 4773
`\l__enumext_after_stop_list_viii_tl` : ... 1062
`\l__enumext_align_label_pos_v_str` : ... 3362
`\l__enumext_align_label_pos_X_str` : ... 79
`\l__enumext_align_label_vii_str` : ... 4632
`\l__enumext_align_label_viii_str` : ... 4886
`\l__enumext_align_label_X_str` : ... 172
`\c__enumext_all_envs_clist` .. 193, 535, 804, 992, 1007, 1088, 1611
`\c__enumext_all_families_seq` .. 128, 5128, 5154
`\l__enumext_anskey_env_bool` 32, 81, 34, 290, 305, 2710
`__enumext_anskey_env_clean_vars`: . 84, 2815, 2819, 2882
`__enumext_anskey_env_define_keys`: 81, 2708, 2717, 2788
`__enumext_anskey_env_exec`: 82, 2713, 2784, 2784
`__enumext_anskey_env_make:n` 66, 81, 1993, 2708, 2708, 2716
`__enumext_anskey_env_reset_keys`: 82, 83, 2753, 2816
`__enumext_anskey_env_reset_keys:__enumext_rescan_anskey_env:n` : ... 2708
`__enumext_anskey_env_save_keys`: .. 83, 2796, 2819, 2819
`__enumext_anskey_env_store`: .. 83, 2812, 2819, 2861
`__enumext_anskey_env_unknown:n` 81, 2736, 2739
`__enumext_anskey_env_unknown:nn` . 2741, 2743
`\l__enumext_anskey_level_int` .. 28, 2640, 2641
`__enumext_anskey_safe_inner`: 79, 2613, 2619, 2638
`__enumext_anskey_safe_inner:n` : ... 78
`__enumext_anskey_safe_outer`: . 78, 2600, 2619, 2619
`__enumext_anskey_show_wrap_arg:n` . 77, 2532, 2532, 2550, 2565
`__enumext_anskey_show_wrap_left:n` 77, 2477, 2546, 2546
`__enumext_anskey_unknown:n` 78, 2568, 2582, 2584
`__enumext_anskey_unknown:nn` . 2568, 2586, 2588
`__enumext_anskey_wrapper:n` : ... 2173, 2544
`\l__enumext_anspic_body_box` : ... 140, 4063, 4066
`\l__enumext_anspic_body_htdp_dim` . 140, 4064, 4113
`__enumext_anspic_box_set_dim:n` .. 4055, 4055, 4102
`__enumext_anspic_label:nn` : ... 4075, 4105, 4119
`\l__enumext_anspic_label_box` .. 140, 3939, 3942
`\l__enumext_anspic_label_htdp_dim` . 105, 140, 3940, 3946, 4112
`__enumext_anspic_start_list_tag`: 3857, 3883, 4125
`__enumext_anspic_stop_list_tag`: . 3857, 3899, 4129
`__enumext_anspic_stop_start_list_tag`: 3857, 3891, 4127
`__enumext_at_begin_document:n` 34, 35, 200, 200, 382, 388
`\l__enumext_base_line_fix_bool` . 853, 863, 874, 883
`__enumext_before_args_exec`: . 47, 98, 115, 1008, 1008, 3583
`__enumext_before_args_exec_v`: 1024, 1024, 3735
`__enumext_before_args_exec_vii`: . 1040, 1040, 4505
`__enumext_before_args_exec_viii`: 1044, 4767
`__enumext_before_env:nn` 81, 204, 208, 2661, 2673, 2685, 2786
`__enumext_before_keys_exec`: .. 47, 1008, 1012, 3490
`__enumext_before_keys_exec_v`: 1024, 1028, 3681
`__enumext_before_keys_exec_vii` : ... 1040
`__enumext_before_keys_exec_vii`: . 1048, 4457
`__enumext_before_keys_exec_viii`: 1052, 4717
`__enumext_before_list`: ... 98, 3484, 3580, 3580
`__enumext_before_list_v`: ... 3676, 3732, 3732
`__enumext_before_list_vii`: ... 115, 4452, 4501, 4501
`__enumext_before_list_viii`: .. 121, 4713, 4764, 4764
`\l__enumext_before_no_starred_key_v_tl` 1030
`\l__enumext_before_no_starred_key_vii_tl` : ... 1050
`\l__enumext_before_no_starred_key_viii_tl` : ... 1054
`\l__enumext_before_starred_key_v_tl` : ... 1026
`\l__enumext_before_starred_key_vii_tl` . 1042
`\l__enumext_before_starred_key_viii_tl` 1046
`__enumext_calc_hspace:NNNNNNN` 94, 3373, 3373, 3404, 3409, 3451
`__enumext_check_ans_active`: . 67, 98, 115, 2029, 2029, 3584, 4504
`\g__enumext_check_ans_item_tl` : ... 86
`\g__enumext_check_ans_key_bool` 68, 69, 151, 357, 2088, 2094, 2900
`\l__enumext_check_ans_key_bool` 68, 2014, 2019, 2085, 2091
`__enumext_check_ans_key_hook`: .. 68, 100, 115, 2082, 2082, 3666, 4512
`__enumext_check_ans_level`: . 67, 68, 2029, 2035, 2039
`__enumext_check_ans_log`: 69, 84, 2128, 2128, 2904
`__enumext_check_ans_log_msg_greater`: 2128, 2134, 2147
`__enumext_check_ans_log_msg_less`: 2128, 2132, 2137
`__enumext_check_ans_log_msg_same_ok`: 2128, 2133, 2142
`__enumext_check_ans_msg_greater`: 2104, 2110, 2123
`__enumext_check_ans_msg_less`: 2104, 2108, 2113
`__enumext_check_ans_msg_same_ok`: 2104, 2109, 2118
`__enumext_check_ans_show`: .. 69, 84, 2104, 2104, 2902

`\l__enumext_check_answers_bool` [66](#), [67](#), [78](#), [88](#), [89](#),
[151](#), [1991](#), [2018](#), [2033](#), [2320](#), [2344](#), [2351](#), [2375](#), [2602](#),
[2799](#), [3023](#), [3112](#), [3146](#), [4612](#)
`__enumext_check_starred_cmd:n` [33](#), [70](#), [86](#), [120](#),
[2152](#), [2152](#), [3687](#), [3996](#), [4730](#)
`\g__enumext_check_starred_cmd_int` [151](#), [2155](#),
[2161](#), [2166](#), [3318](#), [4084](#), [4851](#)
`\l__enumext_check_start_line_env_tl` . [33](#), [151](#),
[320](#), [328](#), [336](#), [2158](#), [2164](#), [2167](#)
`\l__enumext_columns_sep_v_dim` [3753](#), [3755](#), [3763](#)
`\l__enumext_columns_sep_vii_dim` . . [4133](#), [4135](#),
[4144](#), [4156](#), [4232](#), [4689](#)
`\l__enumext_columns_sep_viii_dim` . [4164](#), [4166](#),
[4175](#), [4187](#), [4281](#), [4951](#)
`\l__enumext_columns_v_int` [1387](#), [1405](#), [1573](#), [3751](#),
[3759](#), [3771](#), [3776](#)
`\l__enumext_columns_vii_int` . . [4138](#), [4141](#), [4145](#),
[4154](#), [4196](#), [4200](#), [4203](#), [4209](#), [4215](#), [4219](#), [4683](#), [4697](#)
`\l__enumext_columns_viii_int` . [4169](#), [4172](#), [4176](#),
[4185](#), [4245](#), [4249](#), [4252](#), [4258](#), [4264](#), [4268](#), [4945](#), [4960](#)
`\l__enumext_counter_i_tl` [45](#), [474](#)
`\l__enumext_counter_ii_tl` [45](#), [475](#)
`\l__enumext_counter_iii_tl` [45](#), [476](#)
`\l__enumext_counter_iv_tl` [45](#), [477](#)
`\c__enumext_counter_style_tl` [31](#), [50](#), [224](#)
`\g__enumext_counter_styles_tl` . [27](#), [38](#), [67](#), [485](#),
[503](#)
`\l__enumext_counter_v_tl` [45](#), [478](#), [732](#)
`\l__enumext_counter_vi_tl` [45](#), [479](#)
`\l__enumext_counter_vii_tl` [45](#), [480](#), [662](#)
`\l__enumext_counter_viii_tl` [45](#), [481](#), [679](#)
`\l__enumext_current_widest_dim` [27](#), [67](#), [509](#), [595](#),
[642](#), [713](#), [717](#)
`__enumext_def_meta_key:nnn` . . . [129](#), [5174](#), [5202](#),
[5208](#), [5222](#)
`__enumext_default_item:n` . . . [3108](#), [3108](#), [3172](#)
`__enumext_define_counters:Nn` [27](#), [465](#), [465](#), [474](#),
[475](#), [476](#), [477](#), [478](#), [479](#), [480](#), [481](#)
`__enumext_endminipage:` . [35](#), [388](#), [391](#), [405](#), [4347](#),
[4670](#), [4932](#)
`\g__enumext_envir_name_tl` [33](#), [34](#), [291](#), [306](#), [365](#),
[1961](#), [1966](#), [1976](#), [2116](#), [2121](#), [2126](#), [2140](#), [2145](#), [2150](#)
`\l__enumext_envir_name_tl` . [32](#), [33](#), [34](#), [260](#), [270](#),
[319](#), [327](#), [335](#), [5570](#), [5573](#), [5580](#), [5583](#), [5590](#), [5593](#),
[5600](#), [5603](#), [5609](#), [5613](#), [5619](#), [5623](#), [5680](#), [5684](#)
`__enumext_execute_after_env:` [34](#), [65](#), [69](#), [80](#), [84](#),
[2890](#), [2890](#), [3671](#), [4708](#)
`__enumext_fake_item:` [929](#), [929](#), [3436](#)
`\l__enumext_fake_item_indent_v_dim` [948](#), [953](#)
`\l__enumext_fake_item_indent_v_tl` [950](#), [3301](#),
[3305](#), [3313](#)
`\l__enumext_fake_item_indent_vii_dim` [961](#), [966](#)
`\l__enumext_fake_item_indent_vii_tl` [963](#), [4666](#)
`\l__enumext_fake_item_indent_viii_dim` . [974](#),
[979](#), [4924](#)
`\l__enumext_fake_item_indent_viii_tl` . . [976](#),
[4922](#), [4927](#)
`\l__enumext_fake_item_indent_X_tl` [99](#)
`__enumext_fake_item_vii:` [929](#), [958](#), [3468](#)
`__enumext_fake_item_viii:` [929](#), [971](#), [3473](#)
`__enumext_fake_make_label_vii:n` . [117](#), [4604](#),
[4604](#), [4660](#)
`__enumext_fake_make_label_viii:n` [4872](#), [4872](#),
[4914](#)
`__enumext_filter_first_level:n` . . [127](#), [5071](#),
[5071](#), [5105](#), [5116](#)
`__enumext_filter_first_level_key:n` [127](#), [5071](#),
[5076](#), [5080](#)
`__enumext_filter_first_level_pair:nn` . [128](#),
[5071](#), [5077](#), [5089](#)
`__enumext_filter_save_key:n` . . [72](#), [2236](#), [2244](#),
[2267](#), [2273](#), [2275](#), [5002](#), [5006](#), [5010](#), [5014](#), [5018](#),
[5022](#)
`__enumext_filter_save_key_key:n` . . [72](#), [2275](#),
[2280](#), [2284](#)
`__enumext_filter_save_key_pair:nn` [73](#), [2275](#),
[2281](#), [2292](#)
`__enumext_filter_series:n` [61](#), [1718](#), [1718](#), [1756](#),
[1768](#), [1773](#)
`__enumext_filter_series_key:n` [61](#), [1718](#), [1723](#),
[1727](#)
`__enumext_filter_series_pair:nn` . . [61](#), [1718](#),
[1724](#), [1735](#)
`__enumext_first_item_tmp_vii:` [114](#), [116](#), [4463](#),
[4537](#), [4537](#)
`__enumext_first_item_tmp_viii:` [120](#), [121](#), [4722](#),
[4776](#), [4776](#)
`\g__enumext_footnote_arg_seq` . [169](#), [4421](#), [4434](#),
[4444](#)
`\g__enumext_footnote_int` . [169](#), [4428](#), [4431](#), [4433](#),
[4435](#)
`\g__enumext_footnote_int_seq` . [169](#), [4422](#), [4435](#),
[4440](#), [4443](#)
`__enumext_footnotes_key_bool` [35](#)
`\l__enumext_footnotes_key_bool` [30](#), [36](#), [118](#), [159](#),
[420](#), [427](#), [436](#), [4654](#), [4677](#), [4908](#), [4939](#)
`__enumext_footnotetext:nn` . . . [4415](#), [4415](#), [4445](#)
`__enumext_foreach_add_body:n` . [131](#), [5223](#), [5283](#),
[5286](#)
`\l__enumext_foreach_after_tl` [5227](#), [5295](#)
`\l__enumext_foreach_before_tl` [5225](#), [5290](#)
`\g__enumext_foreach_default_keys_tl` [130](#), [125](#),
[5245](#), [5266](#)
`__enumext_foreach_keyans:nn` . . [131](#), [5223](#), [5262](#),
[5264](#)
`\l__enumext_foreach_name_prop_tl` . [125](#), [5268](#),
[5293](#)
`\l__enumext_foreach_print_seq` [125](#), [5278](#), [5284](#),
[5288](#)
`\l__enumext_foreach_sep_tl` [5237](#), [5284](#)
`\l__enumext_foreach_start_int` [5229](#), [5280](#)
`\l__enumext_foreach_step_int` [5233](#), [5281](#)
`\l__enumext_foreach_stop_int` . [5231](#), [5273](#), [5275](#),
[5282](#)
`__enumext_foreach_wrapper:n` [5235](#), [5291](#)
`__enumext_getkeyans:nn` . . [125](#), [4985](#), [4989](#), [4989](#)
`__enumext_getkeyans_aux:n` [125](#), [4973](#), [4976](#), [4976](#)
`\l__enumext_hyperref_bool` . [30](#), [35](#), [36](#), [159](#), [416](#),
[439](#), [456](#), [2522](#), [3011](#)
`__enumext_hypertarget:nn` [36](#), [411](#), [441](#), [445](#), [461](#)
`__enumext_if_is_int:n` [216](#)
`__enumext_if_is_int:nTF` [216](#), [751](#), [765](#)
`__enumext_internal_mini_page:` [35](#), [97](#), [114](#), [393](#),
[393](#), [3517](#), [4475](#)
`__enumext_is_not_nested:` [27](#), [32](#), [97](#), [114](#), [254](#), [254](#),
[3518](#), [4476](#)
`__enumext_is_on_first_level:` . [27](#), [32](#), [97](#), [114](#),
[254](#), [280](#), [3524](#), [4488](#)

`\g__enumext_item_anskey_int` 78, 86, 151, 352, 379, 380, 2101, 2471, 3025
`__enumext_item_answer_diff:` 69, 84, 2097, 2097, 2897
`\g__enumext_item_answer_diff_int` 69, 151, 353, 2099, 2106, 2130
`\l__enumext_item_column_pos_vii_int` 116, 4203, 4209, 4215, 4219, 4226, 4544, 4683, 4686
`\l__enumext_item_column_pos_viii_int` .. 121, 4252, 4258, 4264, 4268, 4275, 4783, 4945, 4948
`\l__enumext_item_column_pos_X_int` 172
`\g__enumext_item_count_all_vii_int` 116, 4227, 4545, 4697, 4705
`\g__enumext_item_count_all_viii_int` 121, 4276, 4784, 4959, 4968
`\g__enumext_item_count_all_X_int` 172
`\g__enumext_item_number_bool` 151
`\l__enumext_item_number_bool` 68, 157, 2051, 2056, 2060, 2064, 2077, 2645, 2699, 3115, 3149, 4615
`\g__enumext_item_number_int` .. 68, 151, 351, 378, 380, 2050, 2055, 2059, 2063, 2076, 2101, 3114, 3148, 4614
`__enumext_item_peek_args_vii:` 116, 4546, 4548, 4548
`__enumext_item_peek_args_viii:` 121, 122, 4785, 4787, 4787
`__enumext_item_star_exec:` 89, 3127, 3154, 3191, 3210
`\l__enumext_item_starred_vii_bool` 4563, 4577, 4619
`\l__enumext_item_starred_viii_bool` 4802, 4816, 4882, 4920
`\l__enumext_item_starred_X_bool` 172
`__enumext_item_std:w` 35, 88, 89, 92, 382, 386, 3118, 3124, 3152, 3301, 3305, 3313
`\g__enumext_item_symbol_aux_tl` . 89, 129, 3132, 3135, 3160, 3196, 3214
`\g__enumext_item_symbol_aux_vii_tl` 4585, 4621, 4624, 4628, 4630
`\g__enumext_item_symbol_aux_X_tl` 172
`\l__enumext_item_symbol_sep_vii_dim` .. 4593, 4600, 4627, 4629
`\l__enumext_item_symbol_vii_tl` 4624
`\l__enumext_item_text_vii_box` 4646, 4674
`\l__enumext_item_text_viii_box` ... 4900, 4936
`\l__enumext_item_text_X_box` 172
`\l__enumext_item_width_vii_dim` ... 4142, 4151, 4230, 4238, 4239
`\l__enumext_item_width_viii_dim` .. 4173, 4182, 4279, 4287, 4288
`\l__enumext_item_width_X_dim` 172
`\l__enumext_itemindent_X_dim` 71
`\l__enumext_itemsep_i_skip` ... 1248, 1255, 1258, 1260, 1267, 1271, 1274, 1276, 1416, 1423, 1425, 1426, 1431, 1435, 1437, 1438
`\l__enumext_itemsep_ii_skip` .. 1288, 1295, 1298, 1300, 1307, 1311, 1314, 1316
`\l__enumext_itemsep_iii_skip` . 1327, 1334, 1337, 1339, 1346, 1350, 1353, 1355
`\l__enumext_itemsep_vii_skip` 4703
`\l__enumext_itemsep_viii_skip` 4966
`\l__enumext_joined_item_aux_vii_int` .. 4224, 4225, 4226, 4227, 4233
`\l__enumext_joined_item_aux_viii_int` . 4273, 4274, 4275, 4276, 4282
`\l__enumext_joined_item_aux_X_int` 172
`__enumext_joined_item_vii:w` .. 116, 4551, 4552, 4554, 4554
`\l__enumext_joined_item_vii_int` .. 4195, 4196, 4199, 4201, 4207, 4212, 4217, 4222, 4224, 4230
`__enumext_joined_item_viii:w` . 122, 4790, 4791, 4793, 4793
`\l__enumext_joined_item_viii_int` . 4244, 4245, 4248, 4250, 4256, 4261, 4266, 4271, 4273, 4279
`\l__enumext_joined_item_X_int` 172
`\l__enumext_joined_width_vii_dim` . 4228, 4235, 4238, 4648, 4662
`\l__enumext_joined_width_viii_dim` 4277, 4284, 4287, 4902, 4916
`\l__enumext_joined_width_X_dim` 172
`__enumext_keyans_addto_prop:n` 85, 2910, 2910, 3315, 4081
`__enumext_keyans_addto_seq:n` . 86, 2984, 2984, 3317, 4083
`__enumext_keyans_addto_seq_link:` 2984, 3005, 3007, 4850
`__enumext_keyans_anspic_code:nnn` 107, 4052, 4055, 4123
`__enumext_keyans_anspic_label:nnn` 4055, 4099, 4126
`__enumext_keyans_default_item:n` .. 92, 3296, 3296, 3332
`\l__enumext_keyans_env_bool` 34, 3549, 3562, 3715, 3805
`__enumext_keyans_fake_item:` .. 929, 945, 3426
`\l__enumext_keyans_level_h_int` .. 120, 28, 672, 699, 2629, 2691, 2962, 4482, 4739, 4740
`\l__enumext_keyans_level_int` .. 28, 1533, 2625, 2687, 2957, 3714, 3719, 4046
`__enumext_keyans_make_label:` 38, 93, 3336, 3336, 3424
`__enumext_keyans_make_label_box:` 3336, 3340, 3358
`__enumext_keyans_make_label_std:` 3336, 3342, 3344
`__enumext_keyans_mini_right_cmd:n` 58, 1535, 1568, 1568
`__enumext_keyans_mini_set_vskip:` 54
`__enumext_keyans_minipage_add_space:` 1367, 1393, 3744
`__enumext_keyans_minipage_set_skip:` . 1367, 1367, 1395
`__enumext_keyans_multi_addvspace:` 1166, 1177, 3768
`__enumext_keyans_multi_set_vskip:` 51, 1166, 1166, 1179
`__enumext_keyans_multicols_start:` 3732, 3747, 3749
`__enumext_keyans_multicols_stop:` 1572, 3732, 3774, 3803
`__enumext_keyans_name_and_start:` 27, 33, 120, 313, 313, 3716, 3914, 4744
`__enumext_keyans_parse_keys:n` 3675, 3728, 3728
`\l__enumext_keyans_pic_above_int` . 140, 4015, 4016, 4018
`__enumext_keyans_pic_arg_two:` 105, 3931, 3931, 3961
`\l__enumext_keyans_pic_below_int` . 140, 4015,

4016, 4019	
\l__enumext_keyans_pic_body_seq	106, 107, 140, 3987, 4027, 4050
__enumext_keyans_pic_do:n	106, 3987, 3989, 4007, 4007, 4011
\l__enumext_keyans_pic_label_pos_str	.. 104, 140, 3918, 3921, 4025
\l__enumext_keyans_pic_level_int	.. 28, 1517, 2633, 2695, 2913, 2952, 2987, 3075, 3909, 3910
\g__enumext_keyans_pic_parsep_skip	140, 3948, 4003
__enumext_keyans_pic_row:n	106, 107, 4009, 4012, 4012
__enumext_keyans_pic_safe_exec:n	104, 3907, 3907, 3960
__enumext_keyans_pic_skip_abs:N	.. 105, 3924, 3924, 3935
\l__enumext_keyans_pic_star_bool	.. 104, 140, 3917, 3936, 3998, 4057, 4103
\l__enumext_keyans_pic_width_dim	.. 140, 4014, 4025, 4077
__enumext_keyans_pre_itemsep_skip:	.. 1367, 1386, 1413
__enumext_keyans_redefine_item:	.. 93, 3320, 3320, 3423
__enumext_keyans_ref: 42, 724, 742, 3425
__enumext_keyans_ref:n 42, 721, 724, 724
__enumext_keyans_safe_exec:	.. 3674, 3708, 3708
__enumext_keyans_set_item_width:	100, 3683, 3691, 3691
__enumext_keyans_show_ans:	.. 3028, 3036, 3055
__enumext_keyans_show_item_opt:	.. 3028, 3043, 3313, 4096, 4923
__enumext_keyans_show_left:n	.. 92, 3028, 3028, 3311, 4090
__enumext_keyans_show_pos:	.. 3028, 3040, 3068
__enumext_keyans_starred_item:n	.. 92, 3308, 3308, 3328
__enumext_keyans_store_ref:	.. 85, 2931, 2931, 3316, 4082, 4848
__enumext_keyans_store_ref_aux_i:	85, 2931, 2943, 2946
__enumext_keyans_store_ref_aux_ii:	86, 2931, 2972, 2974
__enumext_keyans_unknown_keys:n	.. 3234, 3238, 3242
__enumext_keyans_unknown_keys:nn	3234, 3244, 3246
__enumext_keyans_wrapper_opt:n	.. 2179, 3051
\l__enumext_label_copy_i_tl	.. 2437, 2950, 2955, 2960, 2965
\l__enumext_label_copy_v_tl 2960
\l__enumext_label_copy_vi_tl 2955
\l__enumext_label_copy_vii_tl	2413, 2424, 2453, 2950
\l__enumext_label_copy_viii_tl 2965
\l__enumext_label_copy_X_tl 161
\l__enumext_label_fill_left_v_tl 3348
\l__enumext_label_fill_left_X_tl 99
\l__enumext_label_fill_right_v_tl 3355
\l__enumext_label_fill_right_X_tl 99
\l__enumext_label_font_style_v_tl	3349, 3364, 4094
\l__enumext_label_font_style_vii_tl	... 4634
\l__enumext_label_font_style_viii_tl	.. 4888
\l__enumext_label_i_tl 587
\l__enumext_label_ii_tl 587
\l__enumext_label_iii_tl 587
\l__enumext_label_iv_tl 587
__enumext_label_style:Nnn	27, 38, 498, 498, 513, 592, 639, 710, 714
\l__enumext_label_v_tl	.. 85, 86, 707, 2918, 2992, 3062, 3102, 3310, 3314, 3678, 3939, 4089, 4091
\l__enumext_label_vi_tl	.. 85, 86, 707, 2915, 2989, 4089, 4091, 4095
\l__enumext_label_vii_tl	.. 634, 4572, 4595, 4602
\l__enumext_label_viii_tl	634, 4811, 4842, 4846
\l__enumext_label_width_by_box	.. 67, 494, 495
__enumext_label_width_by_box:Nn	37, 492, 492, 497, 509, 775
\l__enumext_labelsep_i_dim	... 3060, 3065, 3073, 3105, 4854, 4869
\l__enumext_labelsep_v_dim 3758
\l__enumext_labelsep_vii_dim	.. 2537, 3060, 3073, 4137, 4147, 4231, 4539, 4593, 4641, 4650
\l__enumext_labelsep_viii_dim	4168, 4178, 4280, 4778, 4895, 4904, 4924
\l__enumext_labelwidth_i_dim	.. 3059, 3065, 3072, 3105, 4854, 4869
\l__enumext_labelwidth_v_dim 3362, 3758
\l__enumext_labelwidth_vii_dim	... 2537, 3059, 3072, 4137, 4146, 4231, 4539, 4632, 4649
\l__enumext_labelwidth_viii_dim	.. 4168, 4177, 4280, 4778, 4886, 4903
\l__enumext_leftmargin_tmp_v_bool	.. 105, 3933
\l__enumext_leftmargin_tmp_X_bool 71
\l__enumext_leftmargin_tmp_X_dim 71
\l__enumext_leftmargin_X_dim 71
__enumext_level:	212, 212, 616, 619, 620, 629, 631, 932, 936, 940, 1010, 1014, 1018, 1022, 1105, 1107, 1109, 1111, 1153, 1155, 1157, 1159, 1164, 1199, 1205, 1210, 1212, 1215, 1218, 1231, 1234, 1542, 1546, 1552, 1615, 1617, 1619, 1622, 1629, 1631, 1633, 1636, 2231, 2233, 2235, 2263, 2264, 2266, 2322, 2330, 2334, 2338, 2541, 2542, 3117, 3118, 3122, 3123, 3124, 3132, 3140, 3141, 3144, 3151, 3152, 3156, 3159, 3161, 3187, 3188, 3189, 3192, 3195, 3204, 3205, 3207, 3208, 3211, 3487, 3489, 3506, 3511, 3555, 3568, 3575, 3586, 3588, 3591, 3592, 3594, 3598, 3605, 3608, 3610, 3612, 3613, 3614, 3615, 3618, 3623, 3629, 3635, 3642, 3651
\l__enumext_level_h_int	114, 28, 263, 286, 300, 655, 692, 1524, 2047, 2067, 2432, 2665, 2677, 3563, 4477, 4478
\l__enumext_level_int	.. 97, 28, 214, 273, 285, 301, 395, 1117, 1244, 1523, 2041, 2073, 2409, 2419, 2425, 2431, 2438, 2447, 2452, 2664, 2676, 2892, 3439, 3519, 3520, 3531, 3539, 3553, 3566, 3619, 3723, 4042, 4521, 4531, 4752, 5610, 5614, 5620, 5624
__enumext_list_arg_two_i: 3405
__enumext_list_arg_two_ii: 3405
__enumext_list_arg_two_iii: 3405
__enumext_list_arg_two_iv: 3405
__enumext_list_arg_two_v:	.. 93, 3405, 3680, 3934
__enumext_list_arg_two_vii: 3445, 4456
__enumext_list_arg_two_viii:	... 3445, 4716
\l__enumext_listoffset_v_dim	.. 3699, 3704, 3760
\l__enumext_listparindent_vii_dim	... 4664
\l__enumext_listparindent_viii_dim	... 4918
__enumext_log_answer_vars:	.. 34, 367, 375, 2899

```

\__enumext_log_global_vars: . 34, 367, 367, 2898
\__enumext_make_label: . 38, 90, 3175, 3175, 3434
\__enumext_make_label_box: . . . 3175, 3179, 3199
\__enumext_make_label_std: . . . 3175, 3181, 3183
\l__enumext_mark_answer_sym_tl 74, 2185, 2388,
    2554, 3077, 3090, 4858
\l__enumext_mark_position_str 129, 2189, 2190,
    2216, 2217, 2386
\l__enumext_mark_ref_sym_tl . . 2202, 2527, 3019
\l__enumext_meta_path_tl . 125, 5198, 5199, 5201,
    5202
\c__enumext_meta_paths_prop . . . . . 129, 5174
\__enumext_mini_addvspace_vii: 56, 1503, 1503,
    4305
\__enumext_mini_addvspace_viii: 56, 1503, 1509,
    4370
__enumext_mini_env* . . . . . 393
\__enumext_mini_page 1552, 1579, 3598, 3745, 4307,
    4372, 4393
\__enumext_mini_right_cmd:n . 57, 58, 1537, 1539,
    1539
\__enumext_mini_set_vskip_vii: 55, 1446, 1446,
    1505
\__enumext_mini_set_vskip_viii: 55, 1446, 1468,
    1511
\__enumext_minipage:w 35, 388, 390, 399, 4330, 4662,
    4916
\l__enumext_minipage_active_v_bool 3742, 3765,
    3790
\g__enumext_minipage_active_vii_bool . . 112,
    4319, 4328, 4350
\l__enumext_minipage_active_vii_bool . 4301,
    4312
\g__enumext_minipage_active_viii_bool 4383,
    4391, 4410
\l__enumext_minipage_active_viii_bool 4366,
    4377
\g__enumext_minipage_active_X_bool . . . 172
\l__enumext_minipage_active_X_bool . . . . 87
\__enumext_minipage_add_space: . . 52, 98, 1195,
    1221, 3596
\g__enumext_minipage_after_skip 87, 1450, 1462,
    4348, 4408
\l__enumext_minipage_after_skip . . 51, 100, 87,
    1208, 1248, 1250, 1255, 1258, 1262, 1267, 1271, 1274,
    1278, 1290, 1295, 1298, 1302, 1307, 1311, 1314, 1318,
    1329, 1334, 1337, 1341, 1346, 1350, 1353, 1357, 1369,
    1383, 1416, 1418, 1423, 1425, 1427, 1431, 1435, 1437,
    1439, 1470, 1483, 1497, 1548, 1575, 3800
\g__enumext_minipage_center_vii_bool . 4334,
    4351
\g__enumext_minipage_center_viii_bool 4395,
    4411
\g__enumext_minipage_center_X_bool . . . 172
\l__enumext_minipage_hsep_v_dim . . . . . 3740
\l__enumext_minipage_hsep_vii_dim . . . . 4299
\l__enumext_minipage_hsep_viii_dim . . . 4364
\l__enumext_minipage_left_skip 87, 1370, 1448,
    1453, 1457, 1471, 1475, 1489, 1507, 1513
\l__enumext_minipage_left_v_dim . . 3738, 3745
\l__enumext_minipage_left_vii_dim 4295, 4307
\l__enumext_minipage_left_viii_dim 4360, 4372
\l__enumext_minipage_left_X_dim . . . . . 87
\g__enumext_minipage_right_skip 87, 1449, 1454,
    1458, 4333, 4394
\l__enumext_minipage_right_skip . 51, 87, 1197,
    1203, 1208, 1210, 1212, 1371, 1372, 1378, 1383, 1384,
    1385, 1390, 1472, 1479, 1493, 1554, 1581
\l__enumext_minipage_right_v_dim . 1570, 1579,
    3736, 3740
\g__enumext_minipage_right_vii_dim 111, 4303,
    4330, 4353
\l__enumext_minipage_right_vii_dim 111, 4293,
    4298, 4304
\g__enumext_minipage_right_viii_dim . . 4368,
    4393, 4413
\l__enumext_minipage_right_viii_dim . . 4358,
    4363, 4369
\g__enumext_minipage_right_X_dim . . . . . 172
\g__enumext_minipage_right_X_skip . . . . 172
\__enumext_minipage_set_skip: . 51, 1195, 1195,
    1223
\g__enumext_minipage_stat_int 98, 87, 1559, 1586,
    3595, 3653, 3658, 3743, 3792, 3797
\l__enumext_miniright_code_vii_box 4341, 4345
\g__enumext_miniright_code_vii_tl 112, 4336,
    4343, 4352
\l__enumext_miniright_code_viii_box . . 4402,
    4406
\g__enumext_miniright_code_viii_tl 4397, 4404,
    4412
\l__enumext_miniright_code_X_box . . . . . 172
\__enumext_multi_addvspace: . 50, 99, 1148, 1148,
    3626
\__enumext_multi_set_vskip: 49, 1103, 1103, 1150
\l__enumext_multicols_above_ii_skip . . . 1122
\l__enumext_multicols_above_iii_skip . . 1131
\l__enumext_multicols_above_iv_skip . . . 1140
\l__enumext_multicols_above_v_skip 1168, 1182,
    1193, 1384
\l__enumext_multicols_above_X_skip . . . . 79
\l__enumext_multicols_below_ii_skip . . 1251,
    1260, 1264, 1276, 1281
\l__enumext_multicols_below_iii_skip . 1291,
    1300, 1304, 1316, 1321
\l__enumext_multicols_below_iv_skip . . 1330,
    1339, 1343, 1355, 1360
\l__enumext_multicols_below_v_skip 1172, 1186,
    1385, 1419, 1426, 1428, 1438, 1441, 3782
\l__enumext_multicols_below_X_skip . . . . 79
\g__enumext_multicols_right_X_skip . . . . 79
\__enumext_multicols_start: . 98, 99, 3600, 3602,
    3602
\__enumext_multicols_stop: 99, 1544, 3632, 3632,
    3663
\__enumext_nested_base_line_fix: . 44, 97, 115,
    849, 859, 3535, 4498
\__enumext_newlabel:nn 30, 36, 76, 449, 449, 2463,
    2978
\l__enumext_newlabel_arg_one_tl 30, 36, 76, 85,
    161, 2456, 2464, 2526, 2967, 2979, 3017
\l__enumext_newlabel_arg_two_tl 30, 36, 75, 161,
    2412, 2422, 2435, 2450, 2465, 2954, 2959, 2964, 2980
\__enumext_parse_foreach_keys:n . . 5223, 5239,
    5256
\__enumext_parse_foreach_keys:nn . 5223, 5246,
    5258
\__enumext_parse_keys:n 44, 61, 3483, 3526, 3526

```

```

\__enumext_parse_keys_vii:n . 44, 61, 4451, 4490,
    4490
\__enumext_parse_keys_viii:n . 4712, 4757, 4757
\__enumext_parse_save_key:n 72, 2256, 2261, 2261
\__enumext_parse_save_key_vii:n 72, 2251, 2261,
    2269
\__enumext_parse_series:n 61, 97, 115, 1744, 1744,
    3534, 4496
\__enumext_parse_store_keys:n . . . . . 97
\l__enumext_parsep_i_skip . . . . . 1120, 1124
\l__enumext_parsep_ii_skip . . . . . 1129, 1133
\l__enumext_parsep_iii_skip . . . . . 1138, 1142
\l__enumext_parsep_vii_skip . . . . . 4665
\l__enumext_parsep_viii_skip . . . . . 4919
\l__enumext_partopsep_v_skip . 1184, 1188, 1380,
    1403
\l__enumext_partopsep_viii_skip . . . . . 1481
\__enumext_phantomsection: 36, 411, 442, 446, 462
\__enumext_pre_itemsep_skip: . . 52, 1213, 1242,
    1242
\__enumext_print_footnote: . . . 4415, 4438, 4679,
    4941
\__enumext_print_keyans_box:NN 74, 2380, 2380,
    2393, 2537, 2540, 3064, 3104, 4854, 4869
\l__enumext_print_keyans_i_tl . . . . 5007, 5029
\l__enumext_print_keyans_ii_tl . . . 5011, 5030
\l__enumext_print_keyans_iii_tl . . 5015, 5031
\l__enumext_print_keyans_iv_tl . . . 5019, 5032
\l__enumext_print_keyans_starred_tl 126, 127,
    129, 5003, 5051
\l__enumext_print_keyans_vii_tl 126, 5023, 5033
\l__enumext_print_keyans_X_tl . . . . . 129
\__enumext_printkeyans:nnn 126, 127, 5034, 5037,
    5037
\__enumext_redefine_item: . 89, 3164, 3164, 3433
\l__enumext_ref_key_arg_tl 40, 50, 227, 609, 610,
    623, 654, 657, 668, 674, 685, 726, 727, 738
\l__enumext_ref_the_count_tl . 40, 50, 616, 619,
    622, 662, 664, 667, 679, 681, 684, 732, 734, 737
\__enumext_regex_counter_style: . . 31, 40, 222,
    222, 617, 663, 680, 733
\__enumext_register_counter_style:Nn . . 482,
    482, 487, 488, 489, 490, 491
\__enumext_remove_extra_parsep_vii: . . 4470,
    4692, 4692
\__enumext_remove_extra_parsep_viii: . 4729,
    4954, 4954
\__enumext_renew_footnote: . . . 4415, 4419, 4656,
    4910
\l__enumext_renew_the_count_v_tl 735, 744, 746
\l__enumext_renew_the_count_vii_tl 665, 694,
    696
\l__enumext_renew_the_count_viii_tl 682, 701,
    703
\l__enumext_renew_the_count_X_tl . . . . . 50
\__enumext_rescan_anskey_env:n . . 82, 83, 2774,
    2869, 2877
\__enumext_reset_global_bool: . . 343, 346, 355
\__enumext_reset_global_int: . . . 343, 345, 349
\__enumext_reset_global_tl: . . . 343, 347, 361
\__enumext_reset_global_vars: . 34, 84, 343, 343,
    2907
\l__enumext_resume_active_bool 61, 64, 61, 1748,
    1868
\__enumext_resume_counter: . . 63, 64, 1866, 1872,
    1879
\__enumext_resume_counter:n . 61, 64, 1837, 1842,
    1866, 1866, 1936, 1944
\__enumext_resume_counter_save_ans: 64, 1866,
    1877, 1909
\__enumext_resume_counter_series: . 64, 1866,
    1875, 1892
\g__enumext_resume_int . . . 61, 1789, 1883, 1884
\__enumext_resume_last:n 61, 62, 1744, 1750, 1763
\l__enumext_resume_name_tl 61, 1785, 1793, 1796,
    1812, 1820, 1823, 1869, 1870, 1898, 1905
\__enumext_resume_save_counter: . 62, 100, 115,
    1776, 1776, 3669, 4515
\__enumext_resume_series:n . 63, 1712, 1833, 1833
\__enumext_resume_starred: . 65, 1713, 1930, 1930
\g__enumext_resume_vii_int 61, 1816, 1888, 1889
\l__enumext_rightmargin_vii_dim . . 4149, 4153,
    4158
\l__enumext_rightmargin_viii_dim . 4180, 4184,
    4189
\__enumext_safe_exec: . . 35, 97, 3482, 3515, 3515
\__enumext_safe_exec_vii: . 35, 4450, 4473, 4473
\__enumext_safe_exec_viii: 120, 4711, 4733, 4733
\l__enumext_series_name_tl . . . . . 64
\l__enumext_series_str . . 62, 97, 115, 1710, 1746,
    1754, 1755, 1757, 1759, 1780, 1783, 1787, 1807, 1810,
    1814, 3530, 4494
\__enumext_set_error:nn . . . . . 5160, 5170, 5172
\__enumext_set_item_width: . 96, 3492, 3498, 3498
\__enumext_set_parse:n . . . . . 5144, 5160, 5160
\l__enumext_setkey_tmpa_int . . . 120, 5137, 5141
\l__enumext_setkey_tmpa_seq . . 120, 5135, 5145,
    5151, 5153, 5155, 5167
\l__enumext_setkey_tmpa_tl . . . . 120, 5143, 5147
\l__enumext_setkey_tmpb_seq . . 120, 5136, 5139,
    5143, 5144
\l__enumext_setkey_tmpb_tl 120, 5162, 5164, 5165
\l__enumext_show_answer_bool . 2196, 2220, 2548,
    3034, 3048, 4086, 4852
\__enumext_show_length:nnn . . 46, 230, 230, 5381,
    5382, 5383, 5384, 5385, 5386, 5387, 5388, 5389, 5390,
    5396, 5397, 5398, 5399, 5400, 5401, 5402, 5403, 5404,
    5405
\l__enumext_show_position_bool . . 2199, 2223,
    2552, 3038, 3049, 4087, 4856
\g__enumext_standar_bool 32, 97, 34, 262, 265, 284,
    358, 1778, 1843, 1855, 1881, 1894, 1932, 2072, 2086,
    2417, 2430, 2445, 3550
\l__enumext_standar_bool 97, 100, 34, 2418, 3522,
    3668, 4487
\l__enumext_standar_first_bool 32, 97, 34, 289,
    862, 1765, 1912, 1974, 1981
\__enumext_standar_item_vii:w . 116, 117, 4559,
    4561, 4561
\__enumext_standar_item_viii:w 122, 4798, 4800,
    4800
\__enumext_standar_ref: . . . . 40, 607, 627, 3435
\__enumext_standar_ref:n . . . . 40, 599, 607, 607
\g__enumext_standar_series_tl . 61, 1767, 1768,
    1934, 1937
\__enumext_standar_unknown_keys:n 3274, 3278,
    3282
\__enumext_standar_unknown_keys:nn 3274, 3284,

```

```

    3286
\g__enumext_starred_bool 32, 114, 34, 272, 275, 299,
    359, 1805, 1848, 1859, 1886, 1901, 1940, 2046, 2092,
    2408, 2948, 4354
\l__enumext_starred_bool 114, 115, 120, 34, 1529,
    2446, 2481, 2487, 2535, 2823, 2828, 3057, 3070, 3523,
    4486, 4514, 4745, 4749
\__enumext_starred_columns_set_vii: .. 4131,
    4131, 4461
\__enumext_starred_columns_set_viii: . 4131,
    4162, 4720
\l__enumext_starred_first_bool 32, 114, 34, 304,
    873, 1770, 1921, 1974, 1981
\__enumext_starred_item:nn ... 3127, 3127, 3170
\__enumext_starred_item_exec: . 123, 4844, 4844,
    4884
\__enumext_starred_item_vii:w . 116, 117, 4558,
    4575, 4575
\__enumext_starred_item_vii_aux_i:w .. 4575,
    4580, 4583
\__enumext_starred_item_vii_aux_ii:w . 4575,
    4581, 4586, 4588
\__enumext_starred_item_vii_aux_iii:w 4575,
    4591, 4598
\__enumext_starred_item_viii:w 122, 4797, 4814,
    4814
\__enumext_starred_item_viii_aux_i:w .. 122,
    4814, 4819, 4822
\__enumext_starred_item_viii_aux_ii:w . 122,
    4814, 4820, 4837, 4839
\__enumext_starred_joined_item_vii:n 110, 116,
    4193, 4193, 4556
\__enumext_starred_joined_item_viii:n . 110,
    122, 4193, 4242, 4795
\__enumext_starred_ref: .... 41, 652, 690, 3465
\__enumext_starred_ref:n .... 40, 646, 652, 652
\g__enumext_starred_series_tl . 61, 1772, 1773,
    1942, 1945
\__enumext_starred_unknown_keys:n 3256, 3258,
    3260
\__enumext_starred_unknown_keys:nn 3256, 3262,
    3264
\__enumext_start_from:NNn 42, 749, 749, 762, 784,
    790
\l__enumext_start_i_int ..... 1884, 1896, 1915
\__enumext_start_item_tmp_vii: 114, 4464, 4541,
    4541
\__enumext_start_item_tmp_viii: .. 120, 4723,
    4780, 4780
\__enumext_start_item_vii:w 117, 118, 4567, 4572,
    4595, 4602, 4643, 4643
\__enumext_start_item_viii:w .. 122, 4806, 4811,
    4842, 4897, 4897
\g__enumext_start_line_tl 32, 34, 292, 307, 364,
    2116, 2121, 2126, 2140, 2145, 2150
\__enumext_start_list:nn . 35, 94, 382, 384, 3486,
    3677, 4454, 4714
\__enumext_start_list_tag:n .. 3809, 3833, 4659,
    4913
\__enumext_start_mini_vii: 115, 4291, 4291, 4506
\__enumext_start_mini_viii: ... 121, 4356, 4356,
    4768
\__enumext_start_save_ans_msg: .. 65, 66, 1958,
    1958, 1983
\__enumext_start_store_level: . 97, 3485, 3544,
    3544
\__enumext_start_store_level_vii: 116, 4453,
    4517, 4517
\l__enumext_start_vii_int ... 1889, 1903, 1924
\l__enumext_start_X_int ..... 99
\__enumext_stop_item_tmp_vii: .. 114, 116, 118,
    4463, 4469, 4543, 4645
\__enumext_stop_item_tmp_viii: 120, 121, 4722,
    4728, 4782, 4899
\__enumext_stop_item_vii: 118, 119, 4645, 4668,
    4668
\__enumext_stop_item_viii: 124, 4899, 4930, 4930
\__enumext_stop_list: .. 35, 382, 385, 3637, 3645,
    3688, 3778, 3785, 4314, 4322, 4379, 4386
\__enumext_stop_list_tag:n ... 3809, 3849, 4671,
    4933
\__enumext_stop_mini_vii: 112, 115, 4291, 4310,
    4510
\__enumext_stop_mini_viii: 121, 4356, 4375, 4772
\__enumext_stop_save_ans_msg: . 65, 1958, 1963,
    2896
\__enumext_stop_start_list_tag: .. 3809, 3841,
    4661, 4915
\__enumext_stop_store_level: .. 97, 3544, 3573,
    3638, 3646
\__enumext_stop_store_level_vii: . 116, 4315,
    4323, 4517, 4527
\l__enumext_store_active_bool 29, 66, 111, 1913,
    1922, 1990, 2621, 3548, 3561, 3710, 3718, 4005, 4038,
    4519, 4529, 4735, 4751
\__enumext_store_active_keys:n 71, 72, 97, 2229,
    2229, 3541
\__enumext_store_active_keys_vii:n 71, 72, 115,
    2229, 2239, 4497
\__enumext_store_addto_prop:n 73, 85, 2304, 2304,
    2312, 2472, 2929, 4847
\__enumext_store_addto_seq:n 73, 86, 2313, 2313,
    2317, 2324, 2338, 2346, 2355, 2369, 2377, 2530, 3022
\l__enumext_store_anskey_arg_tl 29, 76, 77, 111,
    2478, 2483, 2485, 2490, 2497, 2500, 2510, 2515, 2518,
    2524, 2530
\__enumext_store_anskey_code:n 76, 79, 83, 2469,
    2469, 2614, 2867, 2875
\l__enumext_store_anskey_env_tl .. 29, 82, 111,
    2797, 2801, 2807, 2869, 2877
\l__enumext_store_anskey_opt_tl .. 29, 83, 111,
    2798, 2825, 2831, 2838, 2844, 2854, 2864, 2873
\__enumext_store_anskey_safe_outer: .... 79
\g__enumext_store_columns_break_bool . 2721,
    2822, 2884
\l__enumext_store_columns_break_bool . 2480,
    2570
\l__enumext_store_current_label_tl 29, 85, 86,
    122, 111, 2912, 2915, 2918, 2925, 2927, 2929, 2986,
    2989, 2992, 2998, 3003, 3013, 3022, 4824, 4829, 4833,
    4846, 4847, 4849
\l__enumext_store_current_label_tmp_tl . 29,
    111, 3310, 3314
\l__enumext_store_current_opt_arg_tl 29, 122,
    111, 3032, 3045, 3051, 4835
\__enumext_store_internal_ref: .. 75, 76, 2394,
    2394, 2475
\g__enumext_store_item_join_int .. 2724, 2829,
    2833, 2885

```



```

\l__enumext_store_item_join_int .. 2488, 2492,
    2573
\g__enumext_store_item_star_bool .. 2726, 2836,
    2886
\l__enumext_store_item_star_bool .. 2495, 2575
\g__enumext_store_item_symbol_sep_dim 2731,
    2851, 2856, 2888
\l__enumext_store_item_symbol_sep_dim 2507,
    2512, 2580
\g__enumext_store_item_symbol_tl .. 2729, 2842,
    2846, 2887
\l__enumext_store_item_symbol_tl .. 2498, 2502,
    2578
\l__enumext_store_keyans_item_opt_sep_-
    tl .... 2182, 2923, 2925, 2996, 3000, 4827, 4831
\__enumext_store_level_close: .. 73, 2318, 2342,
    3577
\__enumext_store_level_close_vii: .. 74, 2349,
    2373, 4533
\__enumext_store_level_open: 73, 98, 2318, 2318,
    3556, 3569
\__enumext_store_level_open_vii: .. 74, 2349,
    2349, 4523
\g__enumext_store_name_tl 29, 66, 111, 363, 370,
    371, 372, 373, 1966, 1992, 2115, 2120, 2125, 2139,
    2144, 2149, 2894
\l__enumext_store_name_tl 29, 66, 67, 111, 1799,
    1802, 1826, 1829, 1917, 1926, 1961, 1970, 1971, 1992,
    1993, 1994, 1996, 1997, 1999, 2001, 2002, 2004, 2006,
    2007, 2031, 2306, 2308, 2315, 2458, 2459, 2560, 2803,
    2969, 2970, 3083, 3096, 4864
\l__enumext_store_ref_key_bool 76, 2205, 2473,
    2521, 2933, 3010
\l__enumext_store_save_key_vii_bool .. 2241,
    2271
\l__enumext_store_save_key_vii_tl 2243, 2244,
    2272, 2273, 2353, 2361, 2365, 2369
\l__enumext_store_save_key_X_bool .. 71, 129
\l__enumext_store_save_key_X_tl .. 71, 72, 129
\l__enumext_store_upper_level_X_bool .. 129
\__enumext_storing_exec: 66, 81, 1968, 1984, 1988
\__enumext_storing_set:n 65, 66, 1953, 1968, 1968
\l__enumext_the_counter_v_tl ..... 734
\l__enumext_the_counter_vii_tl ..... 664
\l__enumext_the_counter_viii_tl ..... 681
\l__enumext_the_counter_X_tl ..... 50
\__enumext_tmp:n 45, 49, 54, 60, 71, 78, 79, 86, 93, 98,
    99, 110, 132, 139, 164, 168, 172, 192, 849, 858, 1706,
    1717, 1949, 1957, 2010, 2028, 2169, 2210, 2211, 2228,
    2247, 2260, 2396, 2403, 2404, 2425, 2438, 2441, 2452,
    2935, 2942, 3234, 3241, 3274, 3281, 3405, 3444, 3445,
    3479
\__enumext_tmp:nn 514, 535, 536, 570, 571, 586, 779,
    804, 885, 907, 908, 928, 984, 992, 993, 1007, 1072,
    1088, 1089, 1102, 1595, 1611, 3218, 3233
\__enumext_tmp:nnn 587, 603, 604, 605, 606, 634, 650,
    651
\__enumext_tmp:nnnnnn 805, 830, 833, 836, 838, 840,
    843, 846
\__enumext_tmp:w ..... 4982, 4985
\l__enumext_tmpa_vii_int 4141, 4144, 4153, 4184
\l__enumext_tmpa_viii_int ..... 4172, 4175
\l__enumext_tmpa_X_dim ..... 172
\l__enumext_tmpa_X_int ..... 172
\l__enumext_topsep_v_skip ... 1170, 1174, 1374

\l__enumext_topsep_vii_skip .. 1451, 1460, 1464
\l__enumext_topsep_viii_skip .. 1473, 1495, 1499
\__enumext_undefine_anskey_env: .. 80, 84, 2654,
    2654, 2905
\__enumext_unskip_unkern: .. 32, 236, 236, 1162,
    1191, 1224, 1396, 3640, 3641, 3659, 3780, 3781, 3798
\l__enumext_vspace_a_star_v_bool ..... 1644
\l__enumext_vspace_a_star_vii_bool ... 1666
\l__enumext_vspace_a_star_viii_bool ... 1677
\l__enumext_vspace_a_star_X_bool ..... 99
\__enumext_vspace_above: 59, 98, 1612, 1612, 3582
\__enumext_vspace_above_v: .. 59, 1640, 1640, 3734
\l__enumext_vspace_above_v_skip .. 1642, 1646,
    1648
\__enumext_vspace_above_vii: 60, 115, 1662, 1662,
    4503
\l__enumext_vspace_above_vii_skip 1664, 1668,
    1670
\__enumext_vspace_above_viii: .. 60, 1662, 1673,
    4766
\l__enumext_vspace_above_viii_skip 1675, 1679,
    1681
\l__enumext_vspace_b_star_v_bool ..... 1655
\l__enumext_vspace_b_star_vii_bool ... 1688
\l__enumext_vspace_b_star_viii_bool ... 1699
\l__enumext_vspace_b_star_X_bool ..... 99
\__enumext_vspace_below: 59, 100, 1626, 1626, 3667
\__enumext_vspace_below_v: .. 59, 1651, 1651, 3807
\l__enumext_vspace_below_v_skip .. 1653, 1657,
    1659
\__enumext_vspace_below_vii: 60, 115, 1684, 1684,
    4513
\l__enumext_vspace_below_vii_skip 1686, 1690,
    1692
\__enumext_vspace_below_viii: .. 60, 1684, 1695,
    4774
\l__enumext_vspace_below_viii_skip 1697, 1701,
    1703
\__enumext_widest_from:nnnn .. 42, 763, 763, 778,
    797
\g__enumext_widest_label_tl 27, 38, 67, 502, 506,
    510
\l__enumext_wrap_label_opt_v_bool .... 3304
\l__enumext_wrap_label_opt_vii_bool 117, 4566
\l__enumext_wrap_label_opt_viii_bool .. 122,
    4805
\l__enumext_wrap_label_opt_X_bool ..... 99
\l__enumext_wrap_label_v_bool 3300, 3304, 3312,
    3350, 3365
\l__enumext_wrap_label_vii_bool .. 117, 4566,
    4570, 4578, 4635
\l__enumext_wrap_label_viii_bool .. 122, 4805,
    4809, 4817, 4889
\l__enumext_wrap_label_X_bool ..... 99
\__enumext_wrapper_label_v:n .. 3352, 3367, 4095
\__enumext_wrapper_label_vii:n ..... 4637
\__enumext_wrapper_label_viii:n ..... 4891
\l__enumext_write_aux_file_tl .. 30, 76, 86, 161,
    2461, 2467, 2976, 2982
enumext* ..... 5, 4448
enumXi ..... 474
enumXii ..... 474
enumXiii ..... 474
enumXiv ..... 474

```

enumXv 474

enumXvi 474

enumXvii 474

enumXviii 474

Environments provide by **enumext**:

anskey* 29, 66, 75, 77, 80–82, 84, 97, 116, 126, 132, 134

enumext* .. 26, 27, 30–32, 35, 37, 40, 41, 43–49, 55, 56, 60–63, 65–68, 70–76, 78, 80, 83–85, 90, 91, 95, 97, 98, 102, 103, 109, 110, 112, 113, 116, 118, 120, 121, 123, 124, 126, 127, 129, 133, 136, 137

enumext 26, 27, 31, 32, 35, 37–40, 42–51, 54, 57–63, 65–68, 70–73, 75, 76, 78, 80, 83–85, 88–90, 92, 94, 96, 98, 100, 101, 104, 109, 111, 114, 116, 120, 126, 127, 129, 132, 134, 136

keyans* 26, 27, 29–33, 37, 40–43, 45–49, 55, 56, 60, 66, 67, 70, 71, 73, 80, 85, 91, 95, 102, 103, 109, 110, 113, 120, 121, 133, 135, 137

keyanspic 26, 27, 29, 30, 33, 37, 38, 41, 66, 67, 70, 73, 80, 85–87, 102–107, 135

keyans 26, 27, 29, 30, 32, 33, 37, 38, 41, 43, 45–48, 51, 54, 57–59, 66, 67, 70, 71, 73, 80, 85–87, 91–94, 100, 101, 104, 105, 107, 111, 121, 133, 135

Environments:

list 31, 34, 35, 94, 96, 102, 104

lrbox 118

minipage 31, 35, 49, 51, 52, 104, 106, 107, 109, 112, 119, 124

multicols 49–52, 57, 98–100

scontents 81, 83

exp commands:

\exp_after:wN 4985

\exp_args:Ne 2866, 2874, 3538, 4973

\exp_args:NV ... 2586, 2741, 3244, 3262, 3284, 5258

\exp_not:N . 58, 505, 622, 667, 684, 737, 938, 952, 953, 965, 966, 978, 979, 2526, 2557, 2558, 3015, 3080, 3081, 3093, 3094, 4861, 4862, 4982

\exp_not:n 294, 309, 322, 330, 338, 561, 581, 622, 623, 667, 668, 684, 685, 737, 738, 939, 1733, 1742, 2193, 2290, 2302, 2464, 2492, 2502, 2512, 2526, 2527, 2833, 2846, 2856, 2979, 3017, 3019, 5087, 5097, 5290, 5295

F

\fbox 2176

\fboxrule 2176

\fboxsep 2176

file commands:

\file_input_stop: 5694

first 993

font 514

\footnote 113

\footnote 113, 4423

\footnotemark 4433

\footnotesize 2558, 3081, 3094, 4862

\footnotetext 4417

\foreachkeyans 16, 130, 5223

G

\getkeyans 16, 125, 4971

group commands:

\group_begin: .. 2556, 2601, 2776, 2863, 3079, 3092, 4860, 5028

\group_end: 2563, 2617, 2880, 3086, 3099, 4867, 5035

H

\hbadness 4673, 4935

hbox commands:

\hbox_overlap_left:n 3160, 4628

\hbox_set:Nn 494, 3939

\hbox_set_end: 4672, 4934

\hbox_set_to_wd:Nnw 4646, 4900

\hfill 544, 549, 555, 556, 1551, 1578, 2526, 3015, 4318, 4382

hook commands:

\hook_gput_code:nnn 9, 202, 206, 210, 409

\hook_gremove_code:nn 83, 2792

\hook_gset_rule:nnnn 410

\hook_if_empty:nTF 2790

\hyperlink 77, 86

\hyperlink 2526, 3015

\hypertarget 36

\hypertarget 441

I

\IfDocumentMetadataTF 3177, 3338, 3835, 3843, 3851, 3885, 3893, 3901, 3962, 3972, 3980, 3990, 3995, 4021, 4029, 4059, 4068, 4316, 4380, 4460, 4468, 4652, 4675, 4719, 4727, 4906, 4937, 5052

\IfHyperBoolean 417

\IfPackageLoadedTF 11, 19, 413, 429

\ignorespaces 941, 954, 967, 980, 4465, 4724

\inputlineno 294, 309, 322, 330, 338

int commands:

\int_add:Nn 4226, 4275

\int_case:nn ... 1117, 1244, 2041, 2067, 2106, 2130

\int_case:nnTF 238

\int_compare:nNnTF .. 395, 655, 672, 692, 699, 1214, 1233, 1387, 1405, 1517, 1533, 1545, 1573, 2154, 2160, 2625, 2629, 2633, 2641, 2687, 2691, 2695, 2892, 2913, 2952, 2957, 2962, 2987, 3075, 3520, 3531, 3553, 3566, 3604, 3619, 3634, 3653, 3719, 3723, 3751, 3776, 3792, 3910, 4042, 4046, 4196, 4206, 4222, 4245, 4255, 4271, 4478, 4482, 4521, 4531, 4682, 4694, 4740, 4752, 4944, 4956, 5141, 5273

\int_compare_p:nNn ... 263, 273, 285, 286, 300, 301, 1523, 1524, 2047, 2073, 2409, 2419, 2431, 2432, 2447, 2488, 2664, 2665, 2676, 2677, 2829, 3563

\int_decr:N 4225, 4274

\int_eval:n .. 380, 792, 2308, 2459, 2558, 2970, 3081, 3094, 3420, 3464, 4214, 4263, 4862

\int_from_alph:n 757, 771

\int_from_roman:n 759, 773

\int_gadd:Nn 4227, 4276

\int_gdecr:N 2050, 2055, 2059, 2063, 2076

\int_gincr:N 1883, 1888, 2471, 3025, 3114, 3148, 3318, 3595, 3743, 4084, 4545, 4614, 4784, 4851

\int_gset:Nn 2099, 4431

\int_gset_eq:NN 1782, 1789, 1795, 1801, 1809, 1816, 1822, 1828, 4428

\int_gzero:N . 351, 352, 353, 1559, 1586, 2166, 2885, 3658, 3797, 4705, 4968

\int_if_exist:Ntf 1757, 1793, 1799, 1820, 1826, 2004

\int_incr:N 2640, 3519, 3714, 3909, 4477, 4544, 4739, 4783

\int_mod:nn 4696, 4958

\int_new:N . 28, 29, 30, 31, 32, 33, 61, 62, 87, 103, 122, 142, 143, 154, 155, 156, 158, 169, 175, 176, 177, 178, 179, 1759, 2007

\int_set:Nn 753, 757, 759, 1896, 1903, 1915, 1924, 2777, 4015, 4016, 4141, 4172, 4195, 4201, 4217, 4244, 4250, 4266, 4673, 4935, 5137, 5275

\int_set_eq:NN 1884, 1889, 4224, 4273

\int_sign:n 2101

<code>\int_step_function:nnN</code>	2425, 2438, 2452
<code>\int_step_function:nnnN</code>	5279
<code>\int_step_inline:nn</code>	5189
<code>\int_step_inline:nnn</code>	4017
<code>\int_to_roman:n</code>	214, 2405, 2442
<code>\int_use:N</code>	373, 378, 379, 1215, 1234, 1546, 1898, 1905, 1917, 1926, 3420, 3439, 3464, 3539, 3605, 3614, 3629, 3635, 4199, 4200, 4212, 4248, 4249, 4261, 5610, 5614, 5620, 5624	
<code>\int_zero:N</code>	4686, 4948
<code>\item</code>	. 88, 92, 116, 118, 121, 124, 386, 2326, 2332, 2357, 2363, 2485, 2989, 2992, 3166, 3322, 3966, 3968, 4462, 4464, 4721, 4723, 4849	
<code>\item*</code>	6, 14, 70, 3320
<code>item-pos*</code>	3218
<code>item-sym*</code>	3218
<code>\itemindent</code>	95
<code>\itemindent</code>	94
<code>itemindent</code>	885
<code>\itemsep</code>	3956
<code>\itemwidth</code>	. 464, 2176, 3500, 3509, 3693, 3702, 4235, 4239, 4284, 4288	

K

<code>keyans</code>	14, 3672
<code>keyans*</code>	14, 4709
<code>keyanspic</code>	15, 3958

Keys for `\anskey` provide by [enumext](#):

<code>break-col</code>	76, 78, 81–83
<code>item-join</code>	76, 78, 81–83
<code>item-pos*</code>	77, 78, 81–83
<code>item-star</code>	77, 78, 81–83
<code>item-sym*</code>	77, 78, 81–83

Keys for `anskey*` provide by [enumext](#):

<code>break-col</code>	76, 78, 81–83
<code>item-join</code>	76, 78, 81–83
<code>item-pos*</code>	77, 78, 81–83
<code>item-star</code>	77, 78, 81–83
<code>item-sym*</code>	77, 78, 81–83

Keys for environments provide by [enumext](#):

<code>above*</code>	28, 58–60, 98, 115
<code>above</code>	28, 58–60, 98, 115, 121
<code>after</code>	47, 100, 115, 121
<code>align</code>	28, 38, 39, 90, 93, 118, 131
<code>base-fix</code>	44, 61, 72, 97, 115, 127
<code>before*</code>	47, 98, 115, 121
<code>before</code>	47
<code>below*</code>	28, 58–60, 100, 115
<code>below</code>	28, 58–60, 100, 115, 121
<code>check-ans</code>	30, 31, 33, 65–70, 73, 84, 86, 100, 115, 120, 133	
<code>columns-sep</code>	48, 99
<code>columns</code>	28, 48, 58, 99
<code>first</code>	47, 119
<code>font</code>	38, 90, 93, 118
<code>item-pos*</code>	89, 90
<code>item-sym*</code>	29, 89, 90
<code>itemindent</code>	28, 45, 46, 88, 89, 93, 119
<code>itemsep</code>	43, 96
<code>labelsep</code>	38, 94, 118
<code>labelwidth</code>	37–41, 43, 94, 117
<code>label</code>	27, 37–39, 42, 43, 105, 109
<code>lisparindent</code>	96
<code>list-indent</code>	28, 45, 105
<code>list-offset</code>	45, 96, 100
<code>listparindent</code>	45, 119

<code>mark-ans</code>	70, 73, 77
<code>mark-pos</code>	70, 71, 131
<code>mark-ref</code>	70, 73, 75, 77
<code>mini-env</code>	. . 28, 35, 48, 57, 58, 73, 98, 111, 112, 115, 121	
<code>mini-right*</code>	28, 31, 49, 73, 112, 115
<code>mini-right</code>	28, 31, 49, 56, 73, 111, 112, 115
<code>mini-sep</code>	28, 48, 73, 98
<code>no-store</code>	30, 65–67, 72, 78, 88, 89
<code>noitemsep</code>	43
<code>nosep</code>	43
<code>parindent</code>	96
<code>parsep</code>	43, 95, 96, 119
<code>partopsep</code>	43
<code>ref</code>	27, 31, 39–41, 133
<code>resume*</code>	27, 60, 61, 65, 66, 72, 100, 115, 127
<code>resume</code>	27, 34, 60–66, 72, 73, 100, 115, 127, 128
<code>rightmargin</code>	45, 109
<code>save-ans</code>	29, 34, 61–67, 69, 71–73, 78–81, 84–86, 92, 101, 107, 120, 121, 123, 125, 126, 128, 133	
<code>save-key</code>	29, 61, 72, 97, 115
<code>save-pos</code>	73
<code>save-ref</code>	30, 36, 70, 73, 75–77, 85, 86, 92, 123
<code>save-sep</code>	70, 73, 122
<code>series</code>	27, 60–65, 73, 97, 100, 115, 128
<code>show-ans</code>	70, 71, 73, 74, 76, 77, 92, 123
<code>show-length</code>	32, 46, 132, 133
<code>show-pos</code>	29, 70, 71, 74, 76, 77, 87, 92, 123
<code>start*</code>	28, 42, 43, 61
<code>start</code>	28, 31, 42, 43, 61
<code>store-key</code>	71
<code>topsep</code>	43
<code>widest</code>	27, 31, 42, 43
<code>wrap-ans</code>	37, 70, 73, 74, 77
<code>wrap-label*</code>	28, 38, 88, 90, 93, 117, 118, 122
<code>wrap-label</code>	28, 38, 88–90, 93, 105, 117, 118, 122
<code>wrap-opt</code>	70, 73

keys commands:

<code>\keys_define:nn</code>	516, 538, 573, 589, 636, 707, 781, 807, 851, 887, 910, 986, 995, 1074, 1091, 1597, 1708, 1951, 2012, 2171, 2213, 2249, 2254, 2568, 2719, 2755, 3220, 3236, 3256, 3276, 4999, 5099, 5215, 5223	
<code>\keys_if_exist_p:nn</code>	5211, 5212
<code>\l_keys_key_str</code>	78, 81, 2586, 2741, 3244, 3262, 3284, 5258, 5366	
<code>\keys_precompile:nnN</code>	. . 126, 198, 198, 5001, 5005, 5009, 5013, 5017, 5021, 5241	
<code>\keys_set:nn</code>	. 530, 867, 878, 1097, 1602, 1607, 1845, 1850, 1937, 1945, 2606, 3533, 3538, 3730, 4495, 4761, 5054, 5061, 5103, 5108, 5109, 5110, 5111, 5114, 5119, 5120, 5121, 5122, 5123, 5124, 5125, 5157, 5267	
<code>\keys_set_known:nn</code>	2873

keyval commands:

<code>\keyval_parse:NNn</code>	1722, 2279, 5075
--------------------------------	-------	------------------

L

<code>label</code>	587, 634, 707
Labels provide by enumext :		
<code>\Alph*</code>	37, 38
<code>\Roman*</code>	37, 38
<code>\alph*</code>	37, 38
<code>\arabic*</code>	31, 37, 38
<code>\roman*</code>	37, 38
<code>\labelsep</code>	3950, 3954
<code>labelsep</code>	514
<code>\labelwidth</code>	37

<code>\labelwidth</code>	3950, 3952
<code>labelwidth</code>	514
<code>\lastkern</code>	249
<code>\lastnodetype</code>	238
<code>\lastskip</code>	243
<code>\leftmargin</code>	95
<code>\leftmargin</code>	94, 3950
legacy commands:	
<code>\legacy_if:nTF</code>	4606, 4609, 4874, 4877
<code>\legacy_if_gset_false:n</code>	400, 4331
<code>\legacy_if_set_false:n</code>	4608, 4876
<code>\legacy_if_set_true:n</code>	4571, 4594, 4601, 4810, 4841
<code>\linewidth</code>	98
<code>\linewidth</code>	3502, 3590, 3695, 3740, 4014, 4144, 4175, 4297, 4362
<code>\list</code>	384
<code>list-indent</code>	885
<code>list-offset</code>	885
<code>\listparindent</code>	3953
<code>listparindent</code>	885

M

<code>\makebox</code>	109
<code>\makebox</code>	2384, 2386, 3203, 3362, 4077, 4632, 4886
<code>\makelabel</code>	88, 90, 93, 109
<code>\makelabel</code>	88, 92, 3185, 3201, 3346, 3360
<code>\makesavenoteenv</code>	435
<code>mark-ans</code>	2169
<code>mark-pos</code>	2169, 2211
<code>mark-ref</code>	2169
<code>mini-env</code>	1072
<code>mini-sep</code>	1072
<code>\minipage</code>	390
<code>\miniright</code>	10, 57, 1515, 1563, 1590, 3656, 3795

mode commands:

<code>\mode_if_math:TF</code>	2649, 2703
<code>\mode_if_vertical:TF</code>	1151, 1180, 1201, 1225, 1376, 1397
<code>\mode_leave_vertical:</code>	865, 876, 938, 952, 965, 978, 2382, 3158, 4626

msg commands:

<code>\msg_error:nn</code>	1565, 1592, 2610, 2643, 2647, 2701, 2809, 3721, 3725, 3912, 3970, 4044, 4480, 4742, 4754, 5126, 5185
<code>\msg_error:nnn</code>	612, 659, 676, 729, 1519, 1526, 1531, 1561, 1588, 1857, 1861, 1976, 2592, 2651, 2669, 2681, 2689, 2693, 2697, 2705, 2747, 3250, 3268, 3290, 4484, 4747, 4987, 4996, 5068, 5173, 5204, 5213, 5250, 5271
<code>\msg_error:nnnn</code>	2595, 2623, 2627, 2631, 2635, 2750, 3253, 3271, 3293, 3712, 4040, 4048, 4737, 5048, 5253
<code>\msg_error:nnnnn</code>	560, 580, 2192
<code>\msg_fatal:nn</code>	3521
<code>\msg_fatal:nnn</code>	468
<code>\msg_info:nnn</code>	13, 16, 21, 24, 415, 431
<code>\msg_line_context:</code>	5331, 5336, 5341, 5370, 5375, 5380, 5395, 5410, 5414, 5418, 5422, 5426, 5430, 5437, 5444, 5450, 5464, 5468, 5473, 5477, 5481, 5485, 5490, 5494, 5498, 5502, 5507, 5542, 5546, 5551, 5556, 5560, 5565, 5641, 5645, 5650, 5655, 5660, 5664, 5668, 5672, 5676, 5680, 5684, 5688, 5692
<code>\msg_log:nnn</code>	1996, 2001, 2006
<code>\msg_log:nnnnn</code>	377, 2139, 2144, 2149
<code>\msg_log:nnnnnn</code>	369
<code>\msg_new:nnn</code>	5298, 5302, 5306, 5310, 5315, 5328, 5333, 5338, 5343, 5352, 5360, 5364, 5368, 5373, 5378, 5393,

	5408, 5412, 5416, 5420, 5424, 5428, 5432, 5441, 5447, 5453, 5457, 5461, 5466, 5471, 5475, 5479, 5483, 5488, 5492, 5496, 5500, 5505, 5540, 5544, 5549, 5554, 5558, 5563, 5639, 5643, 5648, 5653, 5658, 5662, 5666, 5670, 5674, 5678, 5682, 5686, 5690
<code>\msg_new:nnnn</code>	5319, 5510, 5519, 5528, 5534, 5567, 5577, 5587, 5597, 5607, 5617, 5627, 5633
<code>\msg_term:nnnn</code>	1960, 1965, 3429, 3439, 3470, 3475
<code>\msg_term:nnnnn</code>	2120
<code>\msg_warning:nn</code>	3655, 3794
<code>\msg_warning:nnnn</code>	2157, 2163, 3377, 3382, 4198, 4211, 4247, 4260
<code>\msg_warning:nnnnn</code>	2115, 2125
<code>\multicolsep</code>	99
<code>\multicolsep</code>	1218, 1390, 3625, 3767

N

<code>\NeedsTeXFormat</code>	3
<code>\NewCommandCopy</code>	386
<code>\newcounter</code>	471
<code>\NewDocumentCommand</code>	1515, 2598, 4036, 4971, 5026, 5133, 5182, 5260
<code>\NewDocumentEnvironment</code>	3480, 3672, 3958, 4448, 4709
<code>\newenvsc</code>	2712
<code>\newlabel</code>	36
<code>\newlabel</code>	453
<code>no-store</code>	2010
<code>\noindent</code>	1227, 1230, 1399, 1402, 3597, 4306, 4371, 4685, 4947
<code>\nointerlineskip</code>	1227, 1230, 1399, 1402, 1553, 1580, 4306, 4371
<code>noitemsep</code>	805
<code>\nopagebreak</code>	1163, 1192, 1227, 1230, 1399, 1402, 1506, 1512
<code>\normalfont</code>	2557, 3080, 3093, 4861
<code>nosep</code>	805

P

Packages:

<code>caption</code>	112
<code>enumext</code>	26, 37, 39, 65, 94, 104, 131, 132
<code>enumitem</code>	37
<code>expl3</code>	109
<code>footnotehyper</code>	36
<code>hyperref</code>	30, 31, 35, 36, 77, 86, 131
<code>ltxcmd</code>	34
<code>lua-visual-debug</code>	51
<code>multicol</code>	26, 131
<code>scontents</code>	26, 80, 81
<code>shortlst</code>	109, 114, 118
<code>\par</code>	1163, 1192, 1230, 1402, 1506, 1512, 1548, 1553, 1575, 1580, 2534, 3642, 3782, 3800, 4000, 4003, 4034, 4333, 4348, 4394, 4408, 4685, 4947

para commands:

<code>\para_end:</code>	4702, 4965
<code>\parbox</code>	2176
<code>\parindent</code>	4664, 4918
<code>\parsep</code>	50, 105, 106
<code>\parsep</code>	3461, 3935, 3944, 3948
<code>parsep</code>	805
<code>\parskip</code>	4665, 4919
<code>\partopsep</code>	3462, 3955
<code>partopsep</code>	805

peek commands:

<code>\peek_meaning:NTF</code>	4550, 4564, 4579, 4590, 4789, 4803, 4818
<code>\peek_meaning_remove:NTF</code>	4557, 4796

\peek_remove_spaces:n	3326	\seq_item:Nn	2803, 4027
\phantomsection	36	\seq_map_function:NN	5144
\phantomsection	442	\seq_map_inline:Nn	5055, 5062, 5154, 5155
prg commands:		\seq_map_pairwise_function:NNN	4442
\prg_do_nothing:	446	\seq_new:N	123, 124, 126, 140, 170, 171, 2002
\prg_new_protected_conditional:Npnn	216	\seq_pop_left:NN	5143
\prg_replicate:nn	233	\seq_put_right:Nn	4050, 5151, 5167, 5288
\prg_return_false:	220	\seq_set_from_clist:Nn	5136
\prg_return_true:	219	\seq_set_map_e:NNn	5145
\printkeyans	17, 126, 5026	\seq_show:N	5043
prop commands:		\seq_use:Nn	198, 199, 5284
\prop_const_from_keyval:Nn	5174	series	1706
\prop_count:N	371, 2308, 2459, 2560, 2970, 3083, 3096, 4864, 5276	\setcounter	767, 771, 773, 3420, 3464, 3997
\prop_get:NnNTF	5200	\setenumext	6, 127, 5133
\prop_gput_if_not_in:Nnn	2306	\setenumextmeta	7, 129, 5174
\prop_if_exist:NTF	1994, 4991, 5269	show-ans	2169, 2211
\prop_item:Nn	4993, 5293	show-length	984
\prop_new:N	1997	show-pos	2211
\ProvidesExplPackage	4	skip commands:	
R			
\raggedcolumns	3628, 3770	\skip_add:Nn	1122, 1131, 1140, 1153, 1157, 1182, 1186, 1203, 1261, 1263, 1277, 1280, 1301, 1303, 1317, 1320, 1340, 1342, 1356, 1359, 1378, 1427, 1428, 1439, 1441, 3944, 3951
\raisebox	4108	\skip_gset:Nn	1454, 1458, 1462
\ref	75, 85	\skip_gset_eq:NN	3948
ref	587, 634, 707	\skip_gzero_new:N	1449, 1450
\refstepcounter	4611, 4879	\skip_horizontal:N	953, 966, 979, 4629, 4641, 4689, 4895, 4951
regex commands:		\skip_horizontal:n	939, 2383, 2391, 3159, 3161, 4539, 4627, 4778, 4924
\regex_match:nnTF	218, 756, 758, 770, 772, 2805	\skip_if_eq:nnTF	1120, 1129, 1138, 1247, 1287, 1327, 1415, 1451, 1473, 1614, 1628, 1642, 1653, 1664, 1675, 1686, 1697
\regex_replace_once:nnN	226	\skip_new:N	81, 82, 83, 88, 89, 90, 91, 92, 146, 190
\renewcommand	622, 667, 684, 737	\skip_set:Nn	1105, 1109, 1168, 1172, 1197, 1250, 1251, 1269, 1290, 1291, 1309, 1329, 1330, 1348, 1372, 1418, 1419, 1433, 1453, 1457, 1475, 1479, 1483, 1489, 1493, 1497, 3928
\RenewDocumentCommand	1563, 1590, 3166, 3185, 3201, 3322, 3346, 3360, 3968, 4423	\skip_set_eq:NN	1208, 1209, 1211, 1218, 1383, 1384, 1385, 1390, 3418, 3460, 3461, 4665, 4919
\RequirePackage	17, 25	\skip_sub:Nn	1257, 1259, 1273, 1275, 1297, 1299, 1313, 1315, 1336, 1338, 1352, 1354, 1425, 1426, 1437, 1438
resume	1706	\skip_use:N	1107, 1111, 1155, 1159, 1164, 1184, 1188, 1199, 1205, 1615, 1619, 1622, 1629, 1633, 1636, 3642
resume*	1706	\skip_vertical:N	401, 404, 4332, 4346, 4704, 4967
rightmargin	885	\skip_vertical:n	4703, 4966
\Roman	38, 42, 43	\skip_zero:N	1217, 1231, 1369, 1370, 1371, 1389, 1403, 3462, 3625, 3767, 3955, 3956
\Roman	490	\skip_zero_new:N	1448, 1470, 1471, 1472
\roman	38, 42, 43	\l_tmpa_skip	1269, 1279, 1282, 1309, 1319, 1322, 1348, 1358, 1361, 1433, 1440, 1442
\roman	491, 605, 5016	\c_zero_skip	401, 404, 1120, 1129, 1138, 1288, 1327, 1451, 1473, 1615, 1629, 1642, 1653, 1664, 1675, 1686, 1697, 4332, 4346, 4704, 4967
S			
\s	2806	\small	5004, 5008, 5012, 5016, 5020, 5024
save-ans	1949	socket commands:	
save-key	2247	\socket_assign_plug:nn	3837, 3845, 3853, 3887, 3895, 3903
save-ref	2169	\socket_new:nn	3809, 3857
save-sep	2169	\socket_new_plug:nnn	3810, 3817, 3825, 3858, 3865, 3874
scan commands:		\socket_use:n	3838, 3888
\scan_stop:	3966, 4462, 4721, 4982, 4985	\socket_use:nn	3846, 3854, 3896, 3904
scontents internal commands:		\star	3224
\l_scontents_fname_out_tl	2765	start	779
__scontents_parse_environment_keys:n	2771		
__scontents_rescan_tokens:n	2778		
\l_scontents_storing_bool	2763		
\l_scontents_writing_bool	2764		
seq commands:			
\seq_clear:N	5135, 5278		
\seq_const_from_clist:Nn	5128		
\seq_count:N	372, 3987, 5139		
\seq_gclear:N	4421, 4422		
\seq_gput_right:Nn	2315, 4434, 4435		
\seq_if_empty:NTF	4440, 5041, 5153		
\seq_if_exist:NTF	1999, 5039		
\seq_if_in:NnTF	5046		

start* 779

start-list-tags 3809, 3857

\stepcounter 3938, 4101, 4427

stop-list-tags 3809, 3857

stop-start-tags 3809, 3857

str commands:

 \c_backslash_str 2651, 5331, 5336, 5341, 5346, 5348, 5350, 5355, 5357, 5455, 5459, 5463, 5473, 5477, 5485, 5486, 5490, 5502, 5503, 5507, 5508, 5529, 5531, 5535, 5537, 5565, 5628, 5630, 5634, 5636, 5645, 5646, 5650, 5655, 5656, 5660, 5664, 5668

 \c_colon_str 2458, 2969, 4982

 \c_left_brace_str 5436, 5443, 5449

 \c_right_brace_str 5436, 5443, 5449

 \str_case:nn 256, 315

 \str_case:nnTF . 1729, 1737, 2286, 2294, 5082, 5091

 \str_clear:N 3530, 4494

 \str_count:n 233

 \str_if_empty:NTF 1746, 1787, 1814

 \str_if_eq:nnTF 3421, 3466, 5184

 \str_if_in:nnTF 4978

 \str_new:N 84, 130, 145, 185

 \str_set:Nn . 545, 551, 557, 576, 577, 578, 2189, 2190, 2216, 2217, 3918, 3921

 \str_use:N 3205

\string 435

\strutbox . 1236, 1239, 1250, 1251, 1262, 1264, 1279, 1282, 1290, 1291, 1302, 1304, 1319, 1322, 1329, 1330, 1341, 1343, 1358, 1361, 1407, 1410, 1418, 1419, 1427, 1428, 1440, 1442, 1453, 1454, 1457, 1464, 1477, 1485, 1491, 1499, 3946, 3951, 4000, 4114

T

tag commands:

 \tag_mc_begin:n 3815, 3863, 3872

 \tag_mc_end: 3819, 3867, 3876

 \tag_resume:n . 3812, 3860, 3974, 3982, 4031, 4070, 4316, 4380

 \tag_struct_begin:n . 3813, 3814, 3821, 3822, 3823, 3861, 3862, 3869, 3870, 3871, 3983

 \tag_struct_end: 3995, 4727

 \tag_struct_end:n 3820, 3827, 3828, 3829, 3830, 3868, 3877, 3878, 3879, 3880, 4468

 \tag_suspend:n . 3831, 3881, 3964, 3976, 3992, 4023, 4061, 4460, 4719

 \tag_tool:n 3975, 5052

TeX and L^AT_EX 2_ε commands:

 \@auxout 451

 \@currenvir 256, 315

 \protected@write 451

tex commands:

 \tex_newlinechar:D 2777

text commands:

 \text_expand:n 4974

\textasteriskcentered 2186, 2203

\the 243, 249

\thepage 457

tl commands:

 \c_space_tl 3051, 5380, 5395, 5418, 5422, 5609, 5610, 5619, 5620, 5680, 5684

 \tl_clear:N . 543, 550, 2167, 2233, 2243, 2264, 2272, 2478, 2797, 2798, 2912, 2986, 4824

 \tl_clear_new:N 500

 \tl_const:Nn 50, 484

 \tl_gclear:N . 363, 364, 365, 1767, 1772, 2887, 3196, 3214, 4352, 4412, 4630

 \tl_gclear_new:N 1754

 \tl_gput_right:Nn 485

 \tl_greplace_all:Nnn 506

 \tl_gset:Nn 291, 292, 306, 307, 1755, 1768, 1773, 1992, 2801, 3135, 4585

 \tl_gset_eq:NN 502, 3131, 4623

 \tl_if_blank:nTF 2590, 2608, 2745, 3248, 3266, 3288, 4621, 5248

 \tl_if_empty:NTF . 610, 629, 657, 674, 694, 701, 727, 744, 1780, 1785, 1807, 1812, 1870, 1934, 1942, 1971, 2031, 2322, 2353, 2498, 2842, 2864, 2894, 2923, 2996, 3045, 3156, 4827, 5165

 \tl_if_empty:nTF 1835

 \tl_if_exist:NTF 1840

 \tl_if_novalue:nTF . 2604, 2920, 2994, 3030, 3110, 3129, 3137, 3298, 3528, 3985, 4425, 4492, 4759, 4825

 \tl_map_inline:Nn 224, 503

 \tl_new:N 42, 43, 44, 47, 52, 53, 56, 57, 63, 65, 66, 68, 69, 104, 105, 106, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121, 125, 127, 128, 129, 131, 134, 135, 153, 161, 162, 163, 166, 184

 \tl_put_left::Ne 2831

 \tl_put_left:Nn 2330, 2361, 2483, 2825, 2838, 2844, 2854, 3062, 3102, 4336, 4397, 4846, 4849

 \tl_put_right:Nn 501, 620, 665, 682, 735, 2334, 2365, 2412, 2422, 2435, 2450, 2456, 2461, 2485, 2490, 2497, 2500, 2510, 2515, 2518, 2524, 2915, 2918, 2925, 2927, 2954, 2959, 2964, 2967, 2976, 2989, 2992, 2998, 3003, 3013, 4829, 4833

 \tl_remove_all:Nn 5164

 \tl_remove_once:Nn 2400, 2939

 \tl_replace_all:Nnn 505, 5199

 \tl_reverse:N 2399, 2401, 2938, 2940

 \tl_set:Nn . 58, 260, 270, 319, 320, 327, 328, 335, 336, 470, 544, 549, 555, 556, 609, 654, 726, 936, 950, 963, 976, 1869, 1970, 2234, 2244, 2265, 2273, 2554, 2765, 3032, 3077, 3090, 4835, 4858, 5162, 5198, 5268

 \tl_set_eq:NN 511, 615, 618, 662, 664, 679, 681, 732, 734, 2398, 2937, 2950, 3310, 3314, 4089, 4091

 \tl_to_str:n 1840, 1846, 1851, 4974

 \tl_trim_spaces:n . 501, 5151, 5162, 5168, 5184

 \tl_use:N 507, 510, 631, 696, 703, 746, 1010, 1014, 1018, 1022, 1026, 1030, 1034, 1038, 1042, 1046, 1050, 1054, 1058, 1062, 1066, 1070, 2388, 2405, 2413, 2424, 2437, 2442, 2453, 3118, 3124, 3152, 3187, 3188, 3195, 3207, 3301, 3305, 3313, 3348, 3349, 3355, 3364, 3487, 3678, 4094, 4343, 4404, 4634, 4663, 4666, 4888, 4917, 4922, 4927, 5029, 5030, 5031, 5032, 5033, 5051, 5147, 5266

token commands:

 \token_to_str:N 453

\topsep 3951

topsep 805

\topskip 1217, 1389

\typeout 242, 243, 248, 249, 419, 423, 434, 435

U

\u 227, 2806

\unkern 250

unknown 3234, 3256, 3274

\unskip 244

use commands:

 \use:N 234, 3192, 3211, 3489

 \use:n 1720, 2277, 4980, 5073

<code>\use_none:nn</code>	445, 5205		
<code>\usecounter</code>	3419, 3463		
V		W	
<code>\value</code>	1783, 1789, 1796, 1802, 1810, 1816, 1823, 1829	<code>widest</code>	<u>779</u>
vbox commands:		<code>wrap-ans</code>	<u>2169</u>
<code>\vbox_set:Nn</code>	4063	<code>wrap-label</code>	<u>514</u>
<code>\vbox_set_top:Nn</code>	4341, 4402	<code>wrap-label*</code>	<u>514</u>
<code>\vspace</code> .	866, 877, 1619, 1622, 1633, 1636, 1646, 1648, 1657, 1659, 1668, 1670, 1679, 1681, 1690, 1692, 1701, 1703	<code>wrap-opt</code>	<u>2169</u>
		Z	
		<code>\z</code>	2806