

# enumext

ENUMERATE EXERCISE SHEETS

V1.0 2024-05-24<sup>\*</sup>

©2024 by Pablo González<sup>†</sup>

CTAN: <https://www.ctan.org/pkg/enumext>

 <https://github.com/pablgonz/enumext>

## Abstract

This package provides “*enumerated list*” environments for creating “*simple exercise sheets*” along with “*multiple choice questions*”, storing the `(answers)` to these in memory using the `multicol` package and the `l3seq` and `l3prop` modules.

## Contents

|          |                                                      |          |           |                                                |            |
|----------|------------------------------------------------------|----------|-----------|------------------------------------------------|------------|
| <b>1</b> | <b>Introduction</b>                                  | <b>2</b> | <b>4</b>  | <b>The storage system</b>                      | <b>9</b>   |
| 1.1      | Description and usage                                | 3        | 4.1       | Keys for storage                               | 9          |
| 1.2      | The concept of left margin                           | 3        | 4.2       | Keys for internal label and ref                | 10         |
| 1.3      | User interface                                       | 3        | 4.3       | Keys for debugging and checking                | 10         |
| 1.3.1    | Internal counters                                    | 3        | 4.4       | The command <code>\anskey</code>               | 10         |
| 1.3.2    | Support for multicol                                 | 4        | 4.5       | The environment <code>keyans</code>            | 11         |
| 1.3.3    | Support for minipage                                 | 4        | 4.5.1     | The <code>\item*</code> in <code>keyans</code> | 11         |
| 1.3.4    | The <code>\label</code> and <code>\ref</code> system | 4        | 4.6       | The environment <code>keyanspic</code>         | 12         |
| 1.3.5    | Support for <code>\footnote</code>                   | 4        | 4.6.1     | The command <code>\anspic</code>               | 12         |
| <b>2</b> | <b>The environment <code>enumext</code></b>          | <b>4</b> | 4.7       | Printing stored content                        | 13         |
| 2.1      | The <code>\item*</code> in <code>enumext</code>      | 5        | 4.7.1     | The command <code>\getkeyans</code>            | 13         |
| 2.1.1    | Keys for <code>\item*</code> in <code>enumext</code> | 5        | 4.7.2     | The command <code>\printkeyans</code>          | 13         |
| <b>3</b> | <b>The command <code>\setenumext</code></b>          | <b>5</b> | <b>5</b>  | <b>Full examples</b>                           | <b>14</b>  |
| 3.1      | Keys for label and ref                               | 6        | <b>6</b>  | <b>The way of non-enumerated lists</b>         | <b>16</b>  |
| 3.2      | Keys for spaces                                      | 6        | <b>7</b>  | <b>References</b>                              | <b>18</b>  |
| 3.2.1    | Vertical spaces                                      | 7        | <b>8</b>  | <b>Change history</b>                          | <b>18</b>  |
| 3.2.2    | Horizontal spaces                                    | 7        | <b>9</b>  | <b>Index of Documentation</b>                  | <b>19</b>  |
| 3.3      | Keys for add code                                    | 8        | <b>10</b> | <b>Implementation</b>                          | <b>21</b>  |
| 3.4      | Keys for start, series and resume                    | 8        | <b>11</b> | <b>Index of Implementation</b>                 | <b>111</b> |
| 3.5      | Keys for multicol                                    | 9        |           |                                                |            |
| 3.6      | Keys for minipage                                    | 9        |           |                                                |            |
| 3.6.1    | The command <code>\miniright</code>                  | 9        |           |                                                |            |
| 3.6.2    | The key <code>miniright</code>                       | 9        |           |                                                |            |

## Motivation and acknowledgments

Usually it is enough to use the classic `enumerate` environment to generate “*simple exercise sheets*” or “*multiple choice questions*”, the basic idea behind `enumext` is to cover three points:

1. To have a simple interface to be able to write “*lists of exercises*” with “*answers*”.
2. To have a simple interface for writing “*multiple choice questions*”.
3. To have a simple interface for placing “*columns*” and “*drawings*” or “*tables*”.

This package would not be possible without Phelype Oleinik who has collaborated and adapted a large part of the code and all  $\text{\LaTeX}$  team for their great work and to the different members of the `TeX-SX` community who have provided great answers and ideas. Here a note of the main ones:

1. Answer given by Alan Munn in `\topsep`, `\itemsep`, `\partopsep`, `\parsep` - what do they each mean (and what about the bottom)?
2. Answer given by Enrico Gregorio in Understanding minipages - aligning at top
3. Answer given by Ulrich Diez in Different mechanics of hyperlink vs. hyperref
4. Answer given by Enrico Gregorio in Minipage and multicol, vertical alignment

<sup>\*</sup>This file describes a documentation for v1.0, last revised 2024-05-24.

<sup>†</sup>E-mail: [pablgonz@educarchile.cl](mailto:pablgonz@educarchile.cl).

## License and Requirements

Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License (l<sup>pp</sup>l), version 1.3 or later (<https://www.latex-project.org/l<sup>pp</sup>l.txt>). The software has the status “maintained”.

The `enumext` package loads and requires `multicol`[3] package, need to have a modern T<sub>E</sub>X distribution such as T<sub>E</sub>X Live or MiK<sub>T</sub>E<sub>X</sub>. It has been tested with the standard classes provided by L<sup>A</sup>T<sub>E</sub>X: `book`, `report`, `article` and `letter` on 10pt, 11pt and 12pt.

1 Introduction

In the  $\text{\LaTeX}$  world there are many useful packages and classes for creating “lists of exercises”, “worksheets” or “multiple choice questions”, classes like `exam`[1] and packages like `xsim`[2] do the job perfectly, but they don’t always fit the basic day to day needs.

In my work (and in the work of many teachers) it is common to use “simple exercise sheets” also known as “informal lists of exercises”, as an example:

1. Factor  $x^2 - 2x + 1$

2. Factor  $3x + 3y + 3z$

3. True False

(a)  $\alpha > \delta$

(b)  $\text{\LaTeX}$ 2e is cool?

4. Related to Linux
- (a) You use linux?

(b) Usually uses the package manager?

(c) Rate the following package and class

i. `xsim-exam`

ii. `xsim`

iii. `exsheets`

Sometimes we are also interested in showing the “answers” along with the questions:

1. Factor  $x^2 - 2x + 1$ 

\* `(x - 1)^2`

2. Factor  $3x + 3y + 3z$ 

\* `3(x + y + z)`

3. True False

(a)  $\alpha > \delta$ 

\* `False`

(b)  $\text{\LaTeX}$ 2e is cool?

\* `Very True!`

4. Related to Linux
- (a) You use linux?

\* `Yes`

(b) Usually uses the package manager?

\* `Yes, dnf`

(c) Rate the following package and class

i. `xsim-exam`

\* `doesn't exist for now :(`

ii. `xsim`

\* `very good`

iii. `exsheets`

\* `obsolete`

Or we are interested in referring to a specific question and its “answer”, for example:

The answer to 3.(b) is “Very True!” and the answer to 4.(c).ii is “very good”.

Or we are interested in printing all the “answers”:

1.  $(x - 1)^2$

2.  $3(x + y + z)$

3. (a) False

(b) Very True!

4. (a) Yes
- (b) Yes, dnf

(c) i. doesn't exist for now :(

ii. very good

iii. obsolete

Another very common thing to use in my work is “multiple choice questions”, for example:

1. First type of questions

(A) value

(B) correct

2. Second type of questions

I.  $2\alpha + 2\delta = 90^\circ$

II.  $\alpha = \delta$

III.  $\angle EDF = 45^\circ$

(A) I only

(B) II only

(C) I and II only

(D) I and III only

(E) I, II, and III

3. Third type of questions

(1)  $2\alpha + 2\delta = 90^\circ$

(2)  $\angle EDF = 45^\circ$

(A) value

(B) value

(C) value

(D) value

(E) value
4. Question with image and label below:

A

(A)

B


(B)

A

(C)

A

(D)



(E)

5. Question with image on left side:

(A) value

(B) value

(C) value

(D) correct

(E) value

B
- Where what we are interested in the `<label>` and a “short note” that we leave as an explanation, and then print them:
1. (B),  $x = 5$

2. (D)

3. (C), some note

4. (B)

5. (D), “other note”
- These “simple worksheets” or “multiple choice questions” appear to be easy to obtain using a combination of the `enumerate`, `minipage` and `multicols` environments, but like many things, what “looks simple” is not so simple.
- The `enumext` package was created and designed to meet these small requirements in the creation of “simple worksheets” and “multiple choice questions”.
- ©2024 by Pablo González L

3 / 123

1.1 Description and usage

The `enumext` package defines enumerated environments using the `list` environment provided by  $\text{\LaTeX}$ , but “does not redefine” any internal commands associated with it such as `\list`, `\endlist` or `\item` outside of the “scope” in which they are defined.

- This package is NOT intend to replace the `enumerate` environment nor replace the powerful `enumitem`[5], the approach is intended to work without hindering either of them.  
This package can be used with `xelatex`, `lualatex`, `pdflatex` and the classical `latex>dvips>ps2pdf` and is present in  $\text{\TeX}$  Live and  $\text{\MiKTeX}$ , use the package manager to install. For manual installation, download `enumext.zip` and unzip it, run `lualatex enumext.dtx` and move all files to appropriate locations, then run `mktxlsr`. To produce the documentation run `lualatex enumext.dtx` two times.

```
enumext.sty  » TDS:tex/latex/enumext/
enumext.pdf  » TDS:doc/latex/enumext/
README.md   » TDS:doc/latex/enumext/
enumext.dtx  » TDS:source/latex/enumext/
```

The package is loaded in the usual way:

```
\usepackage{enumext}
```

1.2 The concept of left margin

There is a direct relationship between the parameters `\leftmargin`, `\itemindent`, `\labelwidth` and `\labelsep` plus an “extra space” that makes it difficult to obtain the desired *horizontal spaces* in a `list` environment.

Usually we don’t want the `list` to go beyond the left margin of the page, but since these four values are related, that causes a problem. The `enumitem`[5] package adds the `\labelindent` parameter to solve some of these problems. A simplified representation of this in the figure 1.



Figure 1: Representation of horizontal lengths in `enumitem`.

The `enumext` package does NOT provide a user interface to set the values for `\leftmargin` and `\itemindent`, instead it provides the keys `list-offset` and `list-indent` which internally set the values for `\leftmargin` and `\itemindent`. The concepts of `\leftmargin` and `\itemindent` are different in `enumext`. The figure 2 shows the visual representation of idea.



Figure 2: Representation of horizontal lengths concept in `enumext`.

In this way we reduce a *little* the amount of parameters we have to pass. With the default values of keys `list-offset`, `list-indent`, `labelwidth` and `labelsep` the lists will have the (usually) expected output for “*simple worksheets*”. The figure 3 shows the visual representation.



Figure 3: Default horizontal lengths `list-offset=0pt`, `list-indent=\labelwidth+\labelsep` in `enumext`.

1.3 User interface

The user interface consists in `enumext`, `enumext*`, `keyans`, `keyans*` and `keyanspic` environments, `\anskey`, `\item*` and `\anspic*` commands to  $\langle$ stored content $\rangle$ , `\getkeyans` command to get the individual  $\langle$ stored content $\rangle$ , `\printkeyans` to print all  $\langle$ stored content $\rangle$ , `\miniright` for `minipage` and `\setenumext` to config all  $[\langle key = val \rangle]$  options.

1.3.1 Internal counters

The package `enumext` uses internally the `enumXi`, `enumXii`, `enumXiii`, `enumXiv` counters for the four nesting levels of the `enumext` environment, the `enumXv` counter for the `keyans` environment, the `enumXvi` counter for the `keyanspic` environment, the counter `enumXvii` for `enumext*` environment and the counter `enumXviii` for `keyans*` environment.

- If any package defines these counters or they are user-defined in the document, the package will return a missing error and abort the load.

1.3.2 Support for multicol

The package provides direct support for using the `multicol`[3] package. This allows to obtain directly a two-column output as shown in the figure 4.




Figure 4: Representation of the two column output for a nested level in `enumext` environment.

The “non starred” version of the `multicols` environment is always used together with the `\raggedcolumns` command and is controlled by `columns` and `columns-sep` keys. The environment is available for all nesting levels, and can can together with the `mini-env` key. If you need to force a start a new column `\columnbreak` must be used (see §3.5).

- The `\columnseprule` command is not available as a key and is set to “zero” for the inner levels and the `keyans` environment. If the value of this is set inside the document, it will affect “all environments” that use the `columns` key.

1.3.3 Support for minipage

The package provides direct support for `minipage` environment, this allows you to obtain an output like the one shown in figure 5.



Figure 5: Representation of the `mini-env` output for a nested level `enumext` environment.

The `minipage` environments (left and right) is always used with “aligned on top” [`t`], the `minipage` environment on the “right side” always starts with `\centering`. It can be used at all nesting levels and is controlled by `mini-env` and `mini-sep` keys. In order to switch from the “left” side `minipage` environment to the “right” side one must use the command `\miniright` (see §3.6).

1.3.4 The \label and \ref system

This package provides a user interface like the `enumitem`[5] package to customize the references which is activated by the `ref` key (§3.1), the standard  $\TeX$  `\label` and `\ref` commands work as usual. It also provides an “internal reference” system for the “stored content” by means of the key `save-ref` (§4.2) when the key `save-ans` (§4.1) is active.

- The implementation of `\label` and `\ref` together with the `save-ref` key are compatible with the `hyperref`[7] package.

1.3.5 Support for \footnote

This package provides an internal implementation for the `\footnote` command which is compatible with the `hyperref` package, but, it will not produce the expected links, and when using the `mini-env` key or the starred environments `enumext*` and `keyans*` the output will look like the classic way they are displayed in the `minipage` environment.

The best way to solve this is to use Jean-François Burnol `footnotehyper`[8] package, it will support keeping the links if `hyperref` is loaded with the `hyperfootnotes=true` option (default) and will show the output numbered at the bottom of the page (as opposed to how it is displayed in the `minipage` environment). The way to load it is as follows:

```
\usepackage{footnotehyper}
\makesavenoteenv{enumext}
\makesavenoteenv{enumext*}
```

2 The environment enumext

|                       |                                                          |                                                          |
|-----------------------|----------------------------------------------------------|----------------------------------------------------------|
| <code>enumext</code>  | <code>\begin{enumext} [⟨keyval list⟩]</code>             | <code>\begin{enumext*} [⟨keyval list⟩]</code>            |
| <code>enumext*</code> | <code>\item ⟨item content⟩</code>                        | <code>\item ⟨item content⟩</code>                        |
|                       | <code>\item [⟨custom⟩] ⟨item content⟩</code>             | <code>\item [⟨custom⟩] ⟨item content⟩</code>             |
|                       | <code>\item* [⟨symbol⟩] [⟨offset⟩] ⟨item content⟩</code> | <code>\item* [⟨symbol⟩] [⟨offset⟩] ⟨item content⟩</code> |
|                       | <code>\end{enumext}</code>                               | <code>\end{enumext*}</code>                              |

The `enumext` is an “*enumerated list*” environment that works in the same way as the standard `enumerate` environment provided by L<sup>A</sup>T<sub>E</sub>X, `\item` and `\item[⟨custom⟩]` commands work in the usual way.

The environment can be nested with at most “*four levels*” and the options can be configured globally using `\setenumext` command and locally using `[⟨key = val⟩]` in the environment.

### Example

1. This text is in the first level.
  - (a) This text is in the second level.
    - i. This text is in the third level.
      - A. This text is in the fourth level.
- X This text is in the first level.
- ★ 2. This text is in the first level.

```
\begin{enumext}
  \item This text is in the first level.
  \begin{enumext}
    \item This text is in the second level.
    \begin{enumext}
      \item This text is in the third level.
      \begin{enumext}
        \item This text is in the fourth level.
      \end{enumext}
    \end{enumext}
  \end{enumext}
  \item[X] This text is in the first level.
  \item* This text is in the first level.
\end{enumext}
```

## 2.1 The `\item*` in `enumext`

---

```
\item* \item*
\item*[⟨symbol⟩]
\item*[⟨symbol⟩][⟨offset⟩]
```

---

The `\item*`, `\item*[⟨symbol⟩]` and `\item*[⟨symbol⟩][⟨offset⟩]` works like the numbered `\item`, but placing a `⟨symbol⟩` to the “*left*” of the `⟨label⟩` separated from it by the value set by the `labelsep` key and can be `⟨offset⟩` using the second optional argument. The default values for `⟨symbol⟩` and `⟨offset⟩` are `$\star$` ‘★’ and the value set by `labelsep` key.

The *starred version* ‘★’ cannot be separated by spaces ‘`\` ’ from the command, i.e. `\item*` and the first optional argument does “*not support*” verbatim content. Can be configure with the keys `item-sym*` and `item-pos*` locally in the environment or globally using `\setenumext` command (§3).

🔗 The behavior of `\item*` in the `enumext` environment is NOT the same as in the `keyans` environment.

### 2.1.1 Keys for `\item*` in `enumext`

`item-sym*` = {`⟨symbol⟩`} default: `$\star$`  
 Sets the `symbol` to be displayed in the “*left*” of the box containing the current `⟨label⟩` set by `labelwidth` key for `\item*` in `enumext`. The `symbol` can be in text or math mode, for example `item-sym*={$\ast$}`.

`item-pos*` = {`⟨rigid length | dim expression⟩`} default: *by levels*  
 Sets the `offset` between the box containing the current `⟨label⟩` defined by `labelwidth` key and the `⟨symbol⟩` set by `item-sym*` key. The default values are set by `labelsep` key at each level. If positive values are passed it will *offset to the left* and if negative values are passed it will *offset to the right*.

## 3 The command `\setenumext`

---

```
\setenumext \setenumext[⟨enumext, level⟩]{⟨key = val⟩} \setenumext[⟨enumext*⟩]{⟨key = val⟩}
\setenumext[⟨print, level⟩]{⟨key = val⟩} \setenumext[⟨keyans*⟩]{⟨key = val⟩}
\setenumext[⟨keyans⟩]{⟨key = val⟩} \setenumext[⟨print*⟩]{⟨key = val⟩}
```

---

The command `\setenumext` sets the `⟨keys⟩` on a global basis for environment `enumext`, the `\printkeyans` command and the `keyans` environment. It can be used both in the preamble and in the body of the document as many times as desired.

The `⟨keys⟩` set in the optional arguments of environments and commands have the highest precedence, overriding both options passed by `\setenumext`. If the optional argument is not passed, the first level of the environment `enumext` will be taken by default.

- It should be kept in mind that using any *key* that sets a *rubber lengths* or *rigid lengths* for vertical or horizontal space on a level will influence the vertical and horizontal space for *inners levels* and *keyans* and *keyanspic* environments. All *keys* related to vertical or horizontal spacing accept a “*skip*” or “*dim*” expression if passed between braces, i.e. you do not need to use `\dimeval` or `\dimexpr` to perform calculations.

### 3.1 Keys for label and ref

`label = {⟨\alph* | \Alph* | \arabic* | \roman* | \Roman*⟩}` default: *by levels*

Sets the *label* that will be printed at the *current level*. The default value for first level are `\arabic*`, for second level are `(\alph*)`, for third level are `\roman*`, and for fourth level are `\Alph*`.

- This key is intended to give the basic structure with which the *label* will be displayed, and the form in which it is used by standard “*label and ref*” and the “*internal reference*” system with the *save-ref* key. You cannot use commands with *label* as an argument, for example `\emph{⟨\alph*⟩}` will return an error. For full customization of how *label* is displayed use the *font* or *wrap-label* keys.

`ref = {⟨code {⟨\alph* | \Alph* | \arabic* | \roman* | \Roman*⟩ more code⟩}` default: *empty*

Modifies the way *cross references* are displayed. The *label* key sets the default form of the *cross references*, by using this key you can define a different format, for example: `ref=\emph{⟨\alph*⟩}` is valid.

- Internally, it renews the command associated with each counter when it is executed, i.e., `\theenumXi` is modified when the key is executed at the first level, `\theenumXii` when it is executed at the second level and `\theenumXiii` together with `\theenumXiv` when it is executed at the third and fourth levels.

This must be kept in mind, since the values set by the *label* and *ref* keys are not cumulative by levels, so if you have used the *ref* key in the first level and then want to associate the counter with *label* or *ref* in the second level you must use the direct commands, i.e. `\arabic{enumXi}` to indicate the count of the first level instead of using `\theenumXi`.

`labelsep = {⟨rigid length⟩}` default: `0.3333em`

Sets the *horizontal space* between the box containing the current *label* defined by *label* key and the text of an item on the first line. Internally sets the value of `\labelsep` for the current level.

`labelwidth = {⟨rigid length⟩}` default: *by label*

Sets the *width* of the box containing the current *label* set by *label* key. Internally sets the value of `\labelwidth` for the current level. The default values are calculated by means of the *width* of a box by setting a *value* to the current counter using ‘0’ for `\arabic*`, ‘M’ for `\Alph*`, ‘m’ for `\alph*`, ‘VIII’ for `\Roman*` and ‘viii’ for `\roman*`.

`widest = {⟨integer | string⟩}` default: *empty*

Sets the *labelwidth* key pass the *integer* or converting the *string* of the form `\Alph`, `\alph`, `\Roman` or `\roman` to a *value* for the current counter defined by *label* key, then calculating the *width* by means of a box. For example `widest={XXIII}` or `widest={23}` are equivalent. This key is useful when the default values of the *labelwidth* key are smaller than those actually used.

`font = {⟨font commands⟩}` default: *empty*

Sets the *font style* for the current *label* defined by *label* key. For example `font={\bfseries\small}`.

`align = {⟨left | right | center⟩}` default: *left*

Sets the *aligned* of *label* defined by *label* key on the current level in the label box.

`wrap-label = {⟨code {#1} more code⟩}` default: *empty*

Wraps the current *label* defined by *label* key referenced by `{#1}`. The `{⟨code⟩}` must be passed between braces. This key does not modify the value set by the *labelwidth* key and is applied only on `\item` and `\item*`. When using it in the `\setenumext` command it is necessary to use the *double hash* ‘`{#1}`’. For example `wrap-label={\fbox{#1}}` or you can create a command:

```
\NewDocumentCommand \itembx { s +m }
{
  \%
  \IfBooleanTF{#1}
  {
    {\strut\smash{\parbox[t]{\labelwidth}{\raggedright{#2}}}}\%
    {\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{#2}}}}\%
  }
}
```

and then pass it through the key `wrap-label={\itembx{#1}}` or `wrap-label={\itembx*{#1}}`.

`wrap-label* = {⟨code {#1} more code⟩}` default: *empty*

The same as the *wrap-label* key but also applies on `\item[⟨custom⟩]`.

### 3.2 Keys for spaces

`show-length = {⟨true | false⟩}` default: *false*

Displays on the terminal the values for *all list parameters* at the current level. For *vertical spaces* show the values of `\topsep`, `\itemsep`, `\parsep` and `\partopsep`. For *horizontal spaces* show the values of `\labelwidth`, `\labelsep`, `\itemindent`, `\listparindent` and `\leftmargin`.



### 3.2.1 Vertical spaces

`topsep` = {*rubber length* | *rigid length*} default: *by levels*

Set the *vertical space* added to both the top and bottom of the list. Internally sets the value of `\topsep` for the current level. The default values for first level are 8.0pt plus 2.0pt minus 4.0pt, for second level are 4.0pt plus 2.0pt minus 1.0pt, for third and fourth level are 2.0pt plus 1.0pt minus 1.0pt.

`parsep` = {*rubber length* | *rigid length*} default: *by levels*

Set the *vertical space* between paragraphs within an item. Internally sets the value of `\parsep` for the current level. The default values for first level are 4.0pt plus 2.0pt minus 1.0pt, for second level are 2.0pt plus 1.0pt minus 1.0pt, for third and fourth level are 0pt.

`partopsep` = {*rubber length* | *rigid length*} default: *by levels*

Set the *vertical space* added, beyond `topsep`, to the “top” and “bottom” of the entire environment if the environment instance is preceded by a “blank line” or `\par` command. Internally sets the value of `\partopsep` for the current level. The default values for first and second level are 2.0pt plus 1.0pt minus 1.0pt, for third and fourth level are 1.0pt minus 1.0pt.

- The value of this parameter also affects the *inner levels* and the `keyans` environment. Caution should be taken with “blank lines” or `\par` command “before” each environment or nested level when formatting the source code of document.  $\TeX$  will enter *vertical mode* and apply this value to the “top” and “bottom” the environment or nested level.

`itemsep` = {*rubber length* | *rigid length*} default: *by levels*

Set the *vertical space* between items, beyond the `parsep`. Internally sets the value of `\itemsep` for the current level. The default values for first level are 4.0pt plus 2.0pt minus 1.0pt, for the rest of the levels are 2.0pt plus 1.0pt minus 1.0pt.

`noitemsep` *value forbidden* default: *not used*

This is a “meta-key” that does not receive an argument. Set `itemsep` and `parsep` equal to 0pt the entire level of environment.

`nosep` *value forbidden* default: *not used*

This is a “meta-key” that does not receive an argument. Sets all keys for vertical spacing equal to 0pt the entire level of environment.

- The following *keys* should be used with “caution”, they are intended to be used at the “top” and “bottom” of the environment when the `columns` or `mini-env` keys do not provide adequate *vertical spaces*. The values passed can be *rubber* or *rigid* lengths, the way they are applied is the way you differ, using the star ‘\*’ *keys* applies `\vspace*` so that  $\TeX$  does *not discard* this space at page break.

`above` = {*rubber length* | *rigid length*} default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the top of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “above” the environment without hindering the value of the `topsep` key. The space is added with `\vspace` so is “discardable”.

`above*` = {*rubber length* | *rigid length*} default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the top of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “above” the environment without hindering the value of the `topsep` key. The space is added with `\vspace*` so is “not discardable”.

`below` = {*rubber length* | *rigid length*} default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the bottom of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “below” the environment without hindering the value of the `topsep` key. The space is added with `\vspace` so is “discardable”.

`below*` = {*rubber length* | *rigid length*} default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the bottom of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “below” the environment without hindering the value of the `topsep` key. The space is added with `\vspace*` so is “not discardable”.

### 3.2.2 Horizontal spaces

`itemindent` = {*rigid length*} default: 0pt

Extra *horizontal indentation*, beyond `labelsep`, of the “first line” off each item. This value is applied internally using `\hspace` and does not modify the value of `\itemindent`.

`rightmargin` = {*rigid length*} default: 0pt

Set the *horizontal space* between the right margin of the environment and the right margin of the enclosing environment, the value it takes must be greater than or equal to 0pt. Internally sets the value of `\rightmargin` for the current level.

`listparindent` = {*rigid length*} default: 0pt

Sets the *horizontal space* indentation, beyond `list-indent`, for second and subsequent paragraphs within a list item. Internally sets the value of `\listparindent` for the current level.

`list-offset` = {*rigid length*} default: 0pt



Sets the *horizontal translation* of the entire environment level from the left edge of the box defined by the `labelwidth` key. Internally sets the values of `\leftmargin` and `\itemindent` for the current level.

`list-indent = {⟨rigid length⟩}` default: `labelwidth + labelsep`

Sets the *indentation* of the whole environment under the box defined by `labelwidth` and `labelsep` keys. Internally sets the value of `\leftmargin` and `\itemindent` for the current level.

- If `list-indent=0pt` the `⟨label⟩` will be part of the text, separated by the value of the `labelsep` key and the *first word*, in simple terms it will look like a “common paragraph”. This setting is equivalent (more or less) to the `wide` key provided by the `enumitem` package.

### 3.3 Keys for add code

- The following `⟨keys⟩` should be used with “caution”, they are intended to inject `{⟨code⟩}` into different parts of the defined environments. We must keep in mind that the defined environments are based on the `list` base environment provided by L<sup>A</sup>T<sub>E</sub>X which is defined (simplified) as plain form `\list{⟨arg one⟩}{⟨arg two⟩}`. Using the `before*` key does not allow access to the `list` parameters defined by `[⟨key = val⟩]`.

`before = {⟨code⟩}` default: *not used*

Execute `{⟨code⟩}` “before” the environment starts. The `{⟨code⟩}` must be passed between braces, is executed “after” performing all calculations related to the *list parameters* in the environment and the parameters sets by `[⟨key = val⟩]` that is, in the second argument of the list after setting all the parameters `\list{⟨arg one⟩}{⟨arg two⟩}{⟨code⟩}`.

`before* = {⟨code⟩}` default: *not used*

Execute `{⟨code⟩}` “before” the environment starts. The `{⟨code⟩}` must be passed between braces, is executed “before” performing all calculations related to the *list parameters* and `[⟨key = val⟩]` sets in the environment that is, before the arguments defining the environment are executed: `{⟨code⟩}\list{⟨arg one⟩}{⟨arg two⟩}`.

`first = {⟨code⟩}` default: *not used*

Executes `{⟨code⟩}` when “starting” the environment. The `{⟨code⟩}` must be passed between braces, is executed right “after” all *list parameters* are done, after the second argument of list, just before the first occurrence of `\item: \list{⟨arg one⟩}{⟨arg two⟩}{⟨code⟩}\item`.

- Keep in mind that the code set in this key will affect the entire “body” of the environment and therefore the inner levels of the list and the `keyans` environment. It is recommended to set this key per level.

`after = {⟨code⟩}` default: *not used*

Execute `{⟨code⟩}` “after” finishing the environment. The `{⟨code⟩}` must be passed between braces.

### 3.4 Keys for start, series and resume

`start = {⟨integer | string⟩}` default: `1`

Sets the *start value* of the numbering on the current level. Internally `⟨string⟩` is passed as value to the counter defined by `label` key on the current level, i.e. it is equivalent to enter `start=5`, `start=E` or `start=v`.

- The following `⟨keys⟩` are “only” available for the “first level” of `enumext` and `enumext*` and are ignored if set when nested inside each other.

`series = {⟨series name⟩}` default: *not used*

Stores the *keys* of the optional argument of the “first level” of the environment in which it is executed in `{⟨series name⟩}` which is used as an argument in the key `resume`. The `⟨keys⟩` stored in `{⟨series name⟩}` are not cumulative and are overwritten if the same `{⟨series name⟩}` is used again.

`resume = {⟨series name⟩}` default: *not used*

Sets the *start value* and *options* for the “first level” continuing the numbering of the environment in which the `series={⟨series name⟩}` key was executed. If passed *without value* this will only set *start value* continue the numbering from the last environment in which `series={⟨series name⟩}` or `resume={⟨series name⟩}` is not present and if the `save-ans` key is active it will continue the numbering from the last environment in which it was executed. The *start value* can be overwritten using the `start` key.

`resume* ⟨value forbidden⟩` default: *not used*

Sets the *start value* and *options* for the “first level” continuing the numbering of the environment in which the `series={⟨series name⟩}` or `resume={⟨series name⟩}` keys are NOT present, if the `save-ans` key is active it will continue the numbering from the last environment in which it was executed. The *start value* can be overwritten using the `start` key.

- For security reasons the `series` key will never save in `{⟨series name⟩}` the keys `series`, `resume`, `resume*`, `save-ans`, `save-key` and `start`. When using the key `resume={⟨series name⟩}` it will have hierarchy in the `⟨keys⟩` that are saved in `{⟨series name⟩}`, in order to establish the value of a `⟨key⟩` already saved in `{⟨series name⟩}` it must be placed to the “right” of `resume={⟨series name⟩}`, the same thing happens with the `resume*` key, the exception is the `save-ans` key that must be placed on the “left” if you want to start the numbering with its value. The `resume` key passed “without value” must be exactly “without value”, i.e. `resume=` cannot be used and if executed before `resume*` it will affect the *start value*.

### 3.5 Keys for multicols

`columns = {⟨integer⟩}` default: 1

Set the *number of columns* to be used by the `multicols` environment within the environment. The value must be a positive integer less than or equal to 10.

`columns-sep = {⟨rigid length⟩}` default: *by level*

Set the *space between columns* used by the `multicols` environment within the environment. Internally sets the value of `\columnsep`, by default its value is equal to the sum of the values set in the keys `labelwidth` and `labelsep` of the current level.

- The `\footnote{⟨text⟩}` command in the nested levels of `multicols` will not work as expected, prefer the use of `\footnotemark[⟨number⟩]` inside the environment and `\footnotetext[⟨number⟩]{⟨text⟩}` outside the environment or via the `after` key.

### 3.6 Keys for minipage

`mini-env = {⟨rigid length⟩}` default: *not used*

Sets the *width* of the `minipage` environment on the “right side”. This value added to the value set by the `mini-sep` key to determines the *width* of the `minipage` environment on the “left side”, taking `\linewidth` as the maximum reference value.

`mini-sep = {⟨rigid length⟩}` default: 0.3333em

Sets the *space between* the `minipage` environment on the “left side” and the `minipage` environment on the “right side”. This separation is applied together with `\hfill`.

#### 3.6.1 The command `\miniright`

`\miniright` The `\miniright` command close the `minipage` environment on the “left side” and opens the `minipage` environment on the “right side” by starting it with the `\centering` command. It must be placed “after” the last `\item` of the current environment and “before” starting the material to be placed on the “right side”. The starred version ‘`*`’ inhibits the use of `\centering` command i.e. the usual L<sup>A</sup>T<sub>E</sub>X justification is maintained in the `minipage` on the “right side”.

- The `\footnote{⟨text⟩}` command in `minipage` environment will work as usual. If you prefer the footnotes to be numbered (not lowercase) and outside the environment, use `\footnotemark[⟨number⟩]` inside the environment and `\footnotetext[⟨number⟩]{⟨text⟩}` outside the environment or via the `after` key.

#### 3.6.2 The key `miniright`

In the horizontal list environments `enumext*` and `keyans*` it is not possible to use the `\miniright` command and the `miniright` key must be used instead.

`miniright = {⟨code for drawing or tabular⟩}` default: *not used*

Set the *code* for the drawing or tabular to be placed in the `minipage` environment on the “right side” by starting it with `\centering`.

`miniright* = {⟨code for drawing or tabular⟩}` default: *not used*

Same as above, but *without* starting with `\centering`.

## 4 The storage system

The entire mechanism for “storing content” it is activated according to `save-ans` key on the “first level” of `enumext` or `enumext*` environments and it is ignored if they are established when they are nested inside each other. Only when this `⟨key⟩` is “active” the `\anskey` command and the environments `keyans`, `keyans*` and `keyanspic` are available.

|                                                                                                                              |                                                                                                                                    |
|------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| <pre>\begin{enumext}[save-ans={⟨store name⟩}]   \item Text     \begin{keyans}       ...     \end{keyans} \end{enumext}</pre> | <pre>\begin{enumext}[save-ans={⟨store name⟩}]   \item Text     \begin{keyanspic}       ...     \end{keyanspic} \end{enumext}</pre> |
|------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|

### 4.1 Keys for storage

`save-ans = {⟨store name⟩}` default: *not set*

Sets the *name* of the `⟨sequence⟩` and `⟨prop list⟩` in which the contents will be “stored” by `\anskey` in `enumext` and `enumext*` environments, `\item*` in `keyans` and `keyans*` environments and `\anspic*` in `keyanspic` environment. If the `⟨sequence⟩` or `⟨prop list⟩` does not exist, it will be created globally and will not be overwritten if the key is used again..

`wrap-ans = {⟨code {#1} more code⟩}` default: `\fbox{#1}`

Wraps the *current argument* passed `\anskey` command to referenced by `{#1}`. The `{⟨code⟩}` must be passed between braces and only affects the `⟨current argument⟩` passed to `\anskey` and NOT the “stored content” in the `⟨store name⟩` set by `save-ans` key. If this key is passed using the `\setenumext` command it is necessary to use double ‘`##1`’.

`wrap-opt = {⟨code {#1} more code⟩}` default: `[{#1}]`

Wraps the *optional argument* passed to the `\item*` and `\anspic*` commands referenced by `{#1}` in the `keyans`, `keyans*` and `keyanspic` environments. The `{code}` must be passed between braces and only affects the current *optional argument* and NOT the “stored content” in *store name* set by `save-ans` key. If this key is passed using the `\setenumext` command, it is necessary to use the double `{##1}`.

`save-sep = {text symbol}` default: { }  
Sets the *text symbol* that will separate the current *label* defined by the `label` key from the *optional argument* (if present), when storing them in the *store name* defined by the `save-ans` key for the `\item*` command in the `keyans` and `keyans*` environment and for the `\anspic` command in the `keyanspic` environment. The `{text symbol}` must always be passed between braces, whitespace ‘ ’ is preserved within the braces and only affects the “stored content” and not what is displayed when using the `show-ans` or `show-pos` keys.

`mark-ans = {symbol}` default: \textasteriskcentered  
Sets the *symbol* to be displayed in the left margin of the “stored content” in *store name* set by `save-ans` key when using `show-ans` key.

`mark-pos = {left | right}` default: left  
Sets the aligned of the *symbol* defined by `mark-ans` key. The “symbol” is aligned in a box with the same dimensions of the label box defined by `labelwidth` key on the current level and separated by the value of the `labelsep` key.

## 4.2 Keys for internal label and ref

`save-ref = {true | false}` default: false  
Activates the internal “label and ref” mechanism for referencing “stored content” in *store name* set by `save-ans` key. To reference the location of the “stored content” within the environment you must use `\ref{store name: position}`, where *position* corresponds to the position occupied by the “stored content” in the *store name* returned by the `show-pos` key. For example `\ref{test:4}` will return 3. (b) which corresponds to the location of the “stored content” at position 4 within the environment in which the key `save-ans=test` was set.

`mark-ref = {symbol}` default: \textasteriskcentered  
Sets the *symbol* that will be displayed by the `\printkeyans` command only if the `hyperref` package is detected and the `save-ref` key are active. This “symbol” is used as a “link” between the environment in which the `save-ans` key was used and the place where the command is executed.

## 4.3 Keys for debugging and checking

`show-ans = {true | false}` default: false  
Displays the *current argument* passed to `\anskey` in `enumext` environment, the current *label* for `\item*` in `keyans` environment and the current *label* for `\anspic*` in `keyanspic` environment at the place where it is executed. If the optional argument is present in `\item*` or `\anspic*` it will be shown in square brackets.

`show-pos = {true | false}` default: false  
Displays the *position* occupied by the “stored content” by `\anskey` in `enumext` environment, `\item*` in `keyans` environment and `\anspic*` in `keyanspic` environment in *store name* set by `save-ans` key. This position is used by the `\getkeyans` command and by the `\ref` command if the `save-ref` key is active.

`check-ans = {true | false}` default: false  
Enables the *checking answer* mechanism. This key works under the logic that each question will contain “only one answer”, it is intended to be used in conjunction with `no-store` key.

`no-store value forbidden` default: not used  
This is a *meta-key* that does not receive an argument. This key is used in conjunction with `check-ans` and is designed to be used with nested levels of `enumext` in which the `\anskey` command will not be used.

## 4.4 The command \anskey

`\anskey {content}`

The `\anskey` command takes a mandatory argument and is triggered by `save-ans` key. The “content” are “stored” in *store name* set by `save-ans` key. The command does “not support” verbatim content and must NOT be nested. By design it is assumed that each `\item` or `\item*` will have a “single” occurrence of the command unless a nested level is opened or the `no-store` key is used. If `save-ref` key are active and the `hyperref`[7] package is detected, `\hyperlink` and `\hypertarget` will be used, otherwise the usual “label and ref” system provided by L<sup>A</sup>T<sub>E</sub>X will be used.

### Example

- |                                                                                                                                                                                                                                          |                                                                                                                                                                                                                 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>* 1. Text containing our instructions or questions.</li> <li>* first answer</li> <li>2. Text containing our instructions or questions.</li> <li>(a) Question.</li> <li>* second answer</li> </ul> | <ul style="list-style-type: none"> <li>3. Text containing our instructions or questions.</li> <li>* third answer</li> <li>4. Text containing our instructions or questions.</li> <li>* fourth answer</li> </ul> |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

```
\begin{enumext}[save-ans=test,show-ans=true]
  \item* Text containing our instructions or questions. \anskey{\first answer}
  \item Text containing our instructions or questions.
    \begin{enumext}
      \item Question.\anskey{\second answer}
    \end{enumext}
  \item Text containing our instructions or questions. \anskey{\third answer}
  \item Text containing our instructions or questions. \anskey{\fourth answer}
\end{enumext}
```

## 4.5 The environment keyans

```
keyans \begin{keyans}[\key = val] \item \item[\langle custom \rangle] \item* \item*[\langle content \rangle] \end{keyans}
keyans* \begin{keyans*}[\key = val] \item \item[\langle custom \rangle] \item* \item*[\langle content \rangle] \end{keyans*}
```

The `keyans` is an “*enumerated list*” environment designed for “*multiple choice*” questions activated by the `save-ans` key. This environment can NOT be nested and must always be at the “*first level*” of the `enumext` environment, the commands `\item` and `\item[\langle custom \rangle]` work in the usual.

```
\begin{enumext}[save-ans=test]
  \item \langle item content \rangle
    \begin{keyans}[\key = val]
      \item \langle item content \rangle
      \item [\langle custom \rangle] \langle item content \rangle
      \item* \langle item content \rangle
      \item* [\langle content \rangle] \langle item content \rangle
    \end{keyans}
\end{enumext}
```

The `\keys` set in the optional argument of the environment are the same (almost) as those of the `enumext` environment and have higher precedence than those set by `\setenumext[\keys]{\key = val}`. If the optional argument is not passed or the `\keys` are not set by `\setenumext`, the default values will be the same as the second level of the `enumext` environment with the difference in the `\label` which will be set to `label=(\Alph*)`.

### 4.5.1 The `\item*` in `keyans`

```
\item* \item*
\item* [\langle content \rangle]
```

The `\item*` and `\item*[\langle content \rangle]` command store the current `\label` set by `label` key next to the `\content` (if it is present) in `\store name` set by `save-ans` key in the “*first level*” of the `enumext` environment.

The *starred version* ‘`*`’ cannot be separated by spaces ‘`␣`’ from the command, i.e. `\item*` and the optional argument does “*not support*” verbatim content. By design it is assumed that the *starred version* ‘`*`’ will only appear “*once*” within the environment.

🔗 The behavior of `\item*` in `keyans` environment is NOT the same as in the `enumext` environment.

### Example

```
\begin{enumext}[save-ans=test,columns=2,show-ans=true]
  \item Text containing a question.
    \begin{keyans}[nosep]
      \item Choice
      \item* Correct choice
      \item Choice
      \item Choice
    \end{keyans}

  \item Text containing a question and image.
    \begin{keyans}[nosep,mini-env={0.4\linewidth}]
      \item Choice
      \item Choice
      \item Choice
      \item Choice
      \item*[\note] Correct choice
      \miniright
      \includegraphics[scale=0.25]{example-image-a}

      Some text
    \end{keyans}
\end{enumext}
```

1. Text containing a question.

(A) Choice

\* (B) Correct choice

(C) Choice

(D) Choice
2. Text containing a question and image.

(A) Choice

(B) Choice

(C) Choice

(D) Choice

\* (E) [note] Correct choice



4.6 The environment keyanspic

keyanspic

`\begin{keyanspic}[\langle number above, number below \rangle]\anspic{\langle drawing \rangle}\anspic*[\langle content \rangle]{\langle drawing \rangle}`

The `keyanspic` is a “fake enumerated list” environment that which uses the `\anspic` command instead of `\item`. It is activated by the `save-ans` key and has the same settings as the `keyans` environment. It is intended for placing “drawings” or “tabular” with an in-line or *above* and *below* layout. A representation of the output can be seen in the figure 6.




Figure 6: Representation of the `keyanspic` environment with optional argument `[3,2]` in `enumext`.

The optional argument determines the number drawings or tabular “above” and “below” within the environment. The vertical separation between “above” and “below” is controlled by the values set by `parsep` and `itemsep` keys passed to `keyans` environment. If the optional argument or the second part of it is omitted the drawings or tabular will be put on a single line.

4.6.1 The command \anspic

\anspic

`\anspic{\langle drawing or tabular \rangle}`  
`\anspic*[\langle content \rangle]{\langle drawing or tabular \rangle}`


The `\anspic` command take three arguments, the *starred version* “\*” store the current `\label` next to the `\content` (if it is present) in `\store name` set by `save-ans` key.

The *starred version* “\*” cannot be separated by spaces “ ” from the command, i.e. `\anspic*` and the optional argument does “not support” verbatim content. By design it is assumed that the *starred version* “\*” will only appear “once” within the environment.

Example

```
\begin{enumext}[save-ans=test,show-ans,nosep]
  \item Question with images.
  \begin{keyanspic}[3,2]
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-b}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic*[note]{\includegraphics[scale=0.15]{example-image-a}}
  \end{keyanspic}
\end{enumext}
```

1. Question with images.



4.7 Printing stored content

4.7.1 The command \getkeyans

`\getkeyans` `\getkeyans{<store name> : <position>}`

The command `\getkeyans` prints the “only stored content” in `<store name>` defined by `save-ans` key in the `<position>` returned by the `show-pos` key.

The “content” can only be accessed “after” it is stored, if the `<store name>` does not exist the command will return an error. The form taken by the argument `<store name> : <position>` is the same as that used to generate the internal “label and ref” system when `save-ref` key are active, so to refer to a stored “content”. For example `\getkeyans{test:4}` will return the “stored content” at position 4 of the environment in which the key `save-ans=test` was set.

4.7.2 The command \printkeyans

`\printkeyans` `\printkeyans[<keys>]{<store name>}`

The command `\printkeyans` prints “all stored content” in `{<store name>}` defined by `save-ans` key. The “content” can only be accessed “after” it is stored, if `<store name>` does not exist the command will return an error.

Internally it places the “stored content” inside the `enumext` environment with default values for `label` key are the same as those of the `enumext` environment along with the keys: `nosep`, `first=\small`, `font=\small` for all levels, except for the first one that adds the `columns=2` key.

The optional argument allows to handle the `<keys>` “on the first level” of the `enumext` environment encapsulated by the command. If need to pass options for nested levels use `\setenumext[<print> , <level>]{<store name>}`.

Example

```
\begin{enumext}[save-ans=sample,columns=2,show-pos=true,nosep,save-ref=true]
  \item Factor  $3x+3y+3z$ . \anskey{$3(x+y+z)}
  \item True False

  \begin{enumext}[nosep]
    \item \LaTeXe is cool? \anskey{Very True!}
  \end{enumext}

  \item Related to Linux

  \begin{enumext}[nosep]
    \item You use linux? \anskey{Yes}
    \item Rate the following package and class
      \begin{enumext}[nosep]
        \item \texttt{xsim} \anskey{very good}
        \item \texttt{exsheets} \anskey{obsolete}
      \end{enumext}
    \end{enumext}
  \end{enumext}
```

The answer to `\ref{sample:4}` is `\getkeyans{sample:4}` and the answers to all the worksheets are as follows:

```
\printkeyans{sample}
```

1. Factor  $3x + 3y + 3z$ .

[1]  $3(x + y + z)$
2. True False

(a) ~~LaTeXe~~ is cool?

[2] Very True!
3. Related to Linux

(a) You use linux?
- [3] Yes

(b) Rate the following package and class

i. xsim

[4] very good

ii. exsheets

[5] obsolete

The answer to 3.(b).i is very good and the answers to all the worksheets are as follows:

1.  $3(x + y + z)$

2. (a) Very True!

3. (a) Yes

(b) i. very good

ii. obsolete
- \*

\*

\*

\*

\*



5 Full examples

Here I will leave as an example some adaptations questions taken from [TeX-SX](#). The examples are attached to this documentation and can be extracted from your PDF viewer or from the command line by running:

```
$ pdfdetach -saveall enumext.pdf
```

and then you can use the excellent [arara](#)<sup>1</sup> tool to compile them.

Example 1

Adapted from the response given by Enrico Gregorio in [Squares for answer choice options and perfect alignment to mathematical answers](#) .

1. La velocità di  $1,00 \times 10^2$  m/s espressa in km/h è:

A

 36 km/h.

B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$  km/h.
2. In fisica nucleare si usa l'angstrom (simbolo:  $1 \text{ \AA} = 1 \times 10^{-10}$  m) e il fermi o femtometro ( $1 \text{ fm} = 1 \times 10^{-15}$  m). Qual è la relazione tra queste due unità di misura?

A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$ .

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$ .

C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$ .

D

 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$ .
3. La velocità di  $1,00 \times 10^2$  m/s espressa in km/h è:

A

 36 km/h.

B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$  km/h.
4. In fisica nucleare si usa l'angstrom (simbolo:  $1 \text{ \AA} = 1 \times 10^{-10}$  m) e il fermi o femtometro ( $1 \text{ fm} = 1 \times 10^{-15}$  m). Qual è la relazione tra queste due unità di misura?

A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$ .

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$ .


C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$ .

D

 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$ .
1. B
2. A
3. B
4. A

Example 2

Adapted from the response given by Florent Rougon in [Multiple choice questions with proposed answers in random order — addition of automatic correction \(cross mark\)](#) .

1. La velocità di  $1,00 \times 10^2$  m/s espressa in km/h è:

A

 36 km/h.

☒ B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$  km/h.
2. In fisica nucleare si usa l'angstrom (simbolo:  $1 \text{ \AA} = 1 \times 10^{-10}$  m) e il fermi o femtometro ( $1 \text{ fm} = 1 \times 10^{-15}$  m). Qual è la relazione tra queste due unità di misura?

☒ A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$ .

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$ .

C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$ .

D

 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$ .
3. La velocità di  $1,00 \times 10^2$  m/s espressa in km/h è:

A

 36 km/h.

☒ B

 360 km/h.

C

 27,8 km/h.

D

 $3,60 \times 10^8$  km/h.
4. In fisica nucleare si usa l'angstrom (simbolo:  $1 \text{ \AA} = 1 \times 10^{-10}$  m) e il fermi o femtometro ( $1 \text{ fm} = 1 \times 10^{-15}$  m). Qual è la relazione tra queste due unità di misura?

☒ A

 $1 \text{ \AA} = 1 \times 10^5 \text{ fm}$ .

B

 $1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$ .

C

 $1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$ .

D

 $1 \text{ \AA} = 1 \times 10^3 \text{ fm}$ .
1. B
2. A
3. B
4. A
- \*
- \*
- \*
- \*

<sup>1</sup>The cool TeX automation tool: <https://www.ctan.org/pkg/arara>

©2024 by Pablo González L

15 / 123

Example 3

A “simple multiple choice” test 📄.

1. First type of questions
- A

 value
- B

 correct
- C

 value
- D

 value
2. Second type of questions
- I.  $2\alpha + 2\delta = 90^\circ$
- II.  $\alpha = \delta$
- III.  $\angle EDF = 45^\circ$
- A

 I only
- B

 II only
- C

 I and II only
3. Third type of questions
- (1)  $2\alpha + 2\delta = 90^\circ$
- (2)  $\angle EDF = 45^\circ$
- A

 value
- B

 value
- C

 value
4. Question with image and label below:



A




D




B



C



E



5. Question with image on left side:
- A

 value
- B

 value
- C

 value
- D

 correct
- E

 value

- D

 I and III only
- E

 I, II, and III

- D

 value
- E

 value

Test keys

1. B,  $x = 5$
2. D
3. C, some note

- \* 4. E, A duck
- \* 5. D, other note
- \*

\*

\*

\*

Example 4

A “simple worksheet” using ducks :) 📄.



Factor  $x^2 - 2x + 1$



Factor  $3x + 3y + 3z$

The following questions need to be cuaqtified :)



True False



- (a)  $\alpha > \delta$
- (b) ~~ETX~~ze is cool?



Related to Linux



- (a) You use linux?
- (b) Usually uses the package manager?
- (c) Rate the following package and class
- i. `xsim-exam`
- ii. `xsim`
- iii. `exsheets`

The answer to 1 is  $(x - 1)^2$  and the answer to 3.(a) is False.

1.  $(x - 1)^2$
2.  $3(x + y + z)$
3. (a) False
- (b) Very True!
4. (a) Yes

- \* (b) Yes, dnf
- \* (c) i. doesn't exist for now :(
- \* ii. very good
- \* iii. obsolete
- \*

\*

\*

\*

\*

Example 5

Adapted from the response given by Stephen in SAT like question format .

1

Which choice best describes what happens in the passage?

- A) One character argues with another character who intrudes on her home.
- B) One character receives a surprising request from another character.
- C) One character reminisces about choices she has made over the years.
- D) One character criticizes another character for pursuing an unexpected course of action.

2

Which choice best describes what happens in the passage?

- A) One character argues with another character who intrudes on her home.
- B) One character receives a surprising request from another character.
- C) One character reminisces about choices she has made over the years.
- D) One character criticizes another character for pursuing an unexpected course of action.

3

Which choice best describes what happens in the passage?

- A) One character argues with another character who intrudes on her home.
- B) One character receives a surprising request from another character.
- C) One character reminisces about choices she has made over the years.
- D) One character criticizes another character for pursuing an unexpected course of action.

4

Which choice best describes what happens in the passage?

- A) One character argues with another character who intrudes on her home.
- B) One character receives a surprising request from another character.
- C) One character reminisces about choices she has made over the years.
- D) One character criticizes another character for pursuing an unexpected course of action.

1. A)

2. C)

3. B)

4. D)

6 The way of non-enumerated lists

It is possible to use (or abuse) the enumext environment to mimic non-enumerated list environments such as itemize and description, clearly the <keys> to “store answers”, the keyans and keyanspic environments lose their sense and it is not the focus of the main of this package, but, why not to do it?. Here I leave as an example other uses of the enumext environment that can be helpful for specific purposes. The “trick” to generate these fake environments is set label={} or label={<some>} and play with the list-indent, list-offset, font and wrap-label keys.

Fake itemize environment

Here we set the label key using the default settings in L<sup>A</sup>T<sub>E</sub>X for the four levels \textbullet, \textendash, \textasteriskcentered and \textperiodcentered together with the nosepe key to reduce the vertical spaces in the left side example and set the label key in mathematical mode for the right side as \ast, \diamond, \circ and \star for the four levels together with the nosepe key

- First level item
    - Second level item
      - \* Third level item
        - Fourth level item
  - First level item
- \* First level item
    - ◇ Second level item
      - Third level item
        - ★ Fourth level item
  - \* First level item

Fake description environment

Here we set label={} and list-indent=2.5em, font=\bfseries.

- Something** A short one-line description.

This is an entry without a label.

**Something** A short one-line description text.

**Something long** A much longer description text may take more than one line or more than one paragraph.

    Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

If we add list-indent=0pt you get widest style:

- Something** A short one-line description.

This is an entry without a label.

**Something** A short one-line description text.

**Something long** A much *longer* description text may take more than one line or more than one paragraph. Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

- The small space at the beginning of the “unlabeled entry” corresponds to `\labelsep` and can be removed using `\hspace{-\labelsep}` at the beginning of the line.

Description indented by label

Here we set `label={}` and we will give a convenient value to `labelsep` and `labelwidth`, for example we can take as reference our *longest label* and pass it as value using:

```
\newlength{\descitemwd}
\settowidth{\descitemwd}{\textbf{Something long}}
```

and then use `labelsep=4pt, labelwidth=\descitemwd, font=\bfseries`.

**SomeThing** A short one-line description.  
This is an entry *without* a label.

**Something** A short one-line description.

**Something long** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

The environment can be translated so that the *(labels)* are on the left margin calculating the value passed to the `list-offset` key, in this case it will be equal to the sum of the values set by the `labelwidth` and `labelsep` keys finally resulting as `list-offset={-\descitemwd - 4pt}`.

**SomeThing** A short one-line description.  
This is an entry *without* a label.

**Something** A short one-line description.

**Something long** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

If we add `align=right` it will look like this:

**SomeThing** A short one-line description.  
This is an entry *without* a label.

**Something** A short one-line description.

**Something long** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

- At this point we have used `list-offset={-\descitemwd - 4pt}` instead of `list-offset={-\labelwidth - \labelsep}`, this is because the parameters `\labelwidth` and `\labelsep` take the default values, as if we had not set `label`.

Description with multi-line labels

The `label` key does not accept *multiline material*, this is where the `wrap-label*` key comes into play. Unlike the `enumitem` package, the `align` key only supports three options, so what we will do is create a command in the style `\parleft` of `enumitem` that allows us to place *multiline labels* using `\parbox`.

```
\NewDocumentCommand \itembx { s +m }
{%
  \IfBooleanTF{#1}
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedright{#2}}}}%
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{#2}}}}%
}
```

Now we just need to set `wrap-label*={\itembx{#1}}`.

**SomeThing** A short one-line description.  
This is an entry *without* a label.

**Something** A short one-line description.

**Something** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

**long** vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.  
Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

**SoMeThInG** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

**LoNg** vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

Final notes

The original implementation (if you can call it that) of the ideas that led to the creation of `enumext` were some macros using the `enumerate[4]` package for personal use created in early 2003, the code was quite questionable, but functional for these simple requirements.

With the great answers given by Christian Hupfer in [Create a fake label ref using list](#) and the answer given by David Carlisle in [Change the use of label ref by data save in an array \(list\)](#) I managed to create a more solid code than the original version, now using the `l3prop`[10] and `l3seq`[10] modules together with the `hyperref`[7] and `enumitem`[5] packages, which did the job, but with some limitations.

As time went by I took these limitations as a personal challenge which I called “*reinventing the wheel*”, since there were packages and classes that did more or less what I was looking for, but did not fit my simple requirements. This “*reinventing the wheel*” finally ended up becoming `enumext`.

### Why list environments?

The answer is simple, first I love the beauty of its syntax and many of what I had already written used the `enumerate` environment or lists created using the `enumitem` package. In my mind I thought: how complicated could it be to write a package that looked like `enumitem`? It seemed simple enough, of course I didn’t have in mind the mess I was getting into working with `list` environments, `minipage` and adding support for the `multicol` and `hyperref` packages.

Of course, seeing the final result of the experiment “*reinventing the wheel*” I am quite satisfied.

### Why not random questions and other utilities

The “*random*” type questions I love and hate them at the same time, although they simplify a lot the work when creating a multiple choice test, but you lose the beauty of typesetting a document with  $\text{\LaTeX}$ , that is to say the output does not always look as nice as it should, even if they are only alternatives these must follow a certain order when presented either numerical or presentation, that said handling that using *nested lists* is quite complicated so I do not classify to be implemented.

## 7 References

- [1] HIRSCHHORN, PHILIP. “Using the exam document class”. Available from CTAN, <https://www.ctan.org/pkg/exam>, 2023.
- [2] NIEDERBERGER, CLEMENS. “xsim – eXercise Sheets IMproved”. Available from CTAN, <https://www.ctan.org/pkg/xsim>, 2023.
- [3] MITTELBACH, FRANK. “An environment for multicolumn output”. Available from CTAN, <https://www.ctan.org/pkg/multicol>, 2024.
- [4] The  $\text{\LaTeX}$  Project. “enumerate – Enumerate with redefinable labels”. Available from CTAN, <https://www.ctan.org/pkg/enumerate>, 2024.
- [5] BEZOS, JAVIER. “Customizing lists with the enumitem package”. Available from CTAN, <https://www.ctan.org/pkg/enumitem>, 2019.
- [6] BERRY, KARL. “ $\text{\LaTeX}$  2<sub>ε</sub>: An Unofficial Reference Manual”. Available from CTAN, <https://ctan.org/pkg/latex2e-help-texinfo>, 2024.
- [7] The  $\text{\LaTeX}$  Project. “Extensive support for hypertext in  $\text{\LaTeX}$ ”. Available from CTAN, <https://www.ctan.org/pkg/hyperref>, 2024.
- [8] BURNOL, JEAN-FRANÇOIS. “The footnotehyper package”. Available from CTAN, <https://www.ctan.org/pkg/footnotehyper>, 2021.
- [9] The  $\text{\LaTeX}$  Project. “The expl3 package”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2024.
- [10] The  $\text{\LaTeX}$  Project. “The  $\text{\LaTeX}$ 3 Interfaces”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2024.
- [11] The  $\text{\LaTeX}$  Project. “The xparse package”. Available from CTAN, <https://www.ctan.org/pkg/xparse>, 2024.
- [12] GUNDLACH, PATRICK. “The lua-visual-debug package”. Available from CTAN, <https://www.ctan.org/pkg/lua-visual-debug>, 2023.
- [13] LEMVIG, MOGENS. “The shortlst package”. Available from CTAN, <https://www.ctan.org/pkg/shortlst>, 1998.
- [14] NIEDERBERGER, CLEMENS. “tasks – Horizontally columned lists”. Available from CTAN, <https://www.ctan.org/pkg/tasks>, 2022.

## 8 Change history

**v1.0** 2024-05-24 – First public release.

9 Index of Documentation

The italic numbers denote the pages where the corresponding entry is described.

C

Document class:

article2

book2

exam3

letter2

report2

\columnbreak5

\columnsep10

Commands provide by enumext:

\anskey4, 10–12

\anspic\*4, 10, 11, 13

\anspic11, 13

\getkeyans4, 11, 14

\item\*4–7, 10–12

\item6, 7, 9–12

\miniright4, 5, 10

\printkeyans4, 6, 11, 14

\setenumext4, 6, 7, 10–12, 14

Counters defined by enumext:

enumXiii4

enumXii4

enumXiv4

enumXi4

enumXviii4

enumXvii4

enumXvi4

enumXv4

E

Environments provide by enumext:

enumext\*4, 5, 9, 10

enumext4–6, 9–12, 14, 17

keyans\*4, 5, 10, 11

keyanspic4, 7, 10, 11, 13, 17

keyans4–13, 17

Environments:

enumerate1, 3, 4, 6, 19

list4, 9, 19

minipage3–5, 10, 19

multicols3, 5, 10

I

\item4, 5

\itemsep8

K

Keys for environments provide by enumext:

above\*8

above8

after9, 10

align7, 18

before\*9

before9

below\*8

below8

check-ans11

columns-sep5, 10

columns5, 8, 10

first9

font7

L

\label5

Labels provide by enumext:

\Alph\*7, 12

\Roman\*7

\alph\*7

\arabic\*7

\roman\*7

\labelsep4, 7

\labelwidth4, 7

\linewidth10

\listparindent8

P

Packages:

enumerate18

enumext1–4, 13, 18, 19

enumitem4, 5, 9, 18, 19



|                     |             |                      |   |
|---------------------|-------------|----------------------|---|
| footnotehyper ..... | 5           | <b>R</b>             |   |
| hyperref .....      | 5, 11, 19   | \raggedcolumns ..... | 5 |
| l3prop .....        | 1, 19       | \ref .....           | 5 |
| l3seq .....         | 1, 19       | \rightmargin .....   | 8 |
| multicol .....      | 1, 2, 5, 19 |                      |   |
| xsim .....          | 3           | <b>T</b>             |   |
| \parsep .....       | 8           | \topsep .....        | 8 |
| \partopsep .....    | 8           |                      |   |

## 10 Implementation

The most recent publicly released version of `enumext` is available at CTAN: <https://www.ctan.org/pkg/enumext>. While general feedback via email is welcomed, specific bugs or feature requests should be reported through the issue tracker: <https://github.com/pablgonz/enumext/issues>.

- The documentation presented here is far from professional, it contains a lot of obvious information that to the eye of a T<sub>E</sub>Xpert are superfluous, but, after so many years developing this project is the only way to remember what does what.

### 10.1 General conventions

Variables containing `i`, `ii`, `iii` and `iv` are associated by level with the `enumext` environment, variables containing `v` are associated with the `keyans` environment, variables containing `vi` are associated with the `keyanspic` environment, variables containing `vii` are associated with the `enumext*` environment and variables containing `viii` are associated with the `keyans*` environment.

To simplify writing and documentation some variables and functions that are common to the different levels of the environments are described using a capital “X”.

The temporary function `\__enumext_tmp:n` is used in different parts of the package code for variable creation or execution of other functions that are grouped into this one.

All variables and functions defined in this package are private and are NOT intended to work or be used by another package or module.

### 10.2 Initial set up

Start the DocStrip guards.

```
1 (*package)
```

Identify the internal prefix (L<sup>A</sup>T<sub>E</sub>X3 DocStrip convention) for l3doc class.

```
2 <@=enumext>
```

### 10.3 Declaration of the package

First we will make sure we have a minimum (super updated) version of L<sup>A</sup>T<sub>E</sub>X to work correctly.

```
3 \NeedsTeXFormat{LaTeX2e}[2023-11-01]
```

Now declare the `enumext` package.

```
4 \ProvidesExplPackage
5   {enumext}
6   {2024-05-24}
7   {1.0}
8   {Enumerate exercise sheets}
```

Finally check if the `multicol` package is loaded, if not we load it.

```
9 \hook_gput_code:nnn {begindocument} {enumext}
10 {
11   \IfPackageLoadedTF { multicol }
12   {
13     \msg_info:nnn { enumext } { package-load } { multicol }
14   }
15   {
16     \msg_info:nnn { enumext } { package-not-load } { multicol }
17     \RequirePackage{multicol}[2023-03-30]
18   }
19 }
```

### 10.4 Definition of variables

Variables that do not appear in this section are created by means of `\keys_define:nn` or some function described below.

Integer variables will control the nesting levels of the environments and boolean variables will be used to determine if they are present (nested) in each other. The boolean variables `\g__enumext_starred_bool` and `\g__enumext_standar_bool` will be set to “true” when the `enumext` and `enumext*` environments are not nested with each other.

```
20 \int_new:N \__enumext_level_int
21 \int_new:N \__enumext_level_h_int
22 \int_new:N \__enumext_keyans_level_int
23 \int_new:N \__enumext_keyans_level_h_int
24 \int_new:N \__enumext_keyans_pic_level_int
25 \bool_new:N \__enumext_starred_bool
26 \bool_new:N \g__enumext_starred_bool
```

```

27 \bool_new:N \l__enumext_starred_first_bool
28 \bool_new:N \l__enumext_standar_bool
29 \bool_new:N \g__enumext_standar_bool
30 \bool_new:N \l__enumext_standar_first_bool
31 \bool_new:N \l__enumext_keyans_env_bool

```

(End of definition for `\l__enumext_level_int` and others.)

Variables to store the “*name of the counters*” `enumXi`, `enumXii`, `enumXiii` and `enumXiv` for `enumext` environment, `enumXv` for `keyans` environment and `enumXvi` for the `keyanspic` environment.

The counters `enumXvii` and `enumXviii` are used by `enumext*` and `keyans*` environments.

The initial values of these variables are set by the function `\__enumext_define_counters:Nn` (§10.8) and then modified by the function `\__enumext_label_style:Nnn` used by `label` key (§10.11).

```

32 \cs_set_protected:Npn \__enumext_tmp:n #1
33 {
34   \tl_new:c { l__enumext_counter_#1_tl }
35 }
36 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_counter_i_tl` and others.)

Internal variables used by `ref` key (§10.11).

```

37 \tl_const:Nn \c__enumext_counter_style_tl
38 { { arabic } { roman } { Roman } { alph } { Alph } }
39 \tl_new:N \l__enumext_ref_key_arg_tl
40 \tl_new:N \l__enumext_ref_the_count_tl
41 \cs_set_protected:Npn \__enumext_tmp:n #1
42 {
43   \tl_new:c { l__enumext_renew_the_count_#1_tl }
44   \tl_new:c { l__enumext_the_counter_#1_tl }
45   \tl_set:ce { l__enumext_the_counter_#1_tl } { \exp_not:c { theenumX#1 } }
46 }
47 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\c__enumext_counter_style_tl` and others.)

Internal variables used by `resume`, `resume*` and `series` keys. The global token list `\g__enumext_item_symbol_tl` is used by `item-sym*` key (§10.26).

```

48 \int_new:N \g__enumext_resume_int
49 \int_new:N \g__enumext_resume_vii_int
50 \tl_new:N \l__enumext_resume_name_tl
51 \bool_new:N \l__enumext_resume_active_bool
52 \tl_new:N \g__enumext_item_symbol_tl
53 \tl_new:N \g__enumext_standar_series_tl
54 \tl_new:N \g__enumext_starred_series_tl

```

(End of definition for `\g__enumext_resume_int` and others.)

The variable `\l__enumext_current_widest_dim` stores the current label width, the variable `\g__enumext_counter_styles_tl` stores the default `<label style>` and the variable `\g__enumext_widest_label_tl` the label width. These variables are used by `widest` (§10.12) and `label` (§10.10) keys.

```

55 \dim_new:N \l__enumext_current_widest_dim
56 \tl_new:N \g__enumext_counter_styles_tl
57 \tl_new:N \g__enumext_widest_label_tl
58 \box_new:N \l__enumext_label_width_by_box

```

(End of definition for `\l__enumext_current_widest_dim` and others.)

The boolean variable `\l__enumext_leftmargin_tmp_X_bool` and the dimensional variable `\l__enumext_leftmargin_tmp_X_dim` are used by the `list-indent` key (§10.14).

The variables `\l__enumext_leftmargin_X_dim` and `\l__enumext_itemindent_X_dim` are used (and set) by the function `\__enumext_calc_hspace:NNNNNNNNNN` (§10.30.1) which determines the internal values for `\leftmargin` and `\itemindent`.

```

59 \cs_set_protected:Npn \__enumext_tmp:n #1
60 {
61   \bool_new:c { l__enumext_leftmargin_tmp_#1_bool }
62   \dim_new:c { l__enumext_leftmargin_tmp_#1_dim }
63   \dim_new:c { l__enumext_leftmargin_#1_dim }
64   \dim_new:c { l__enumext_itemindent_#1_dim }
65 }
66 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_leftmargin_tmp_X_bool` and others.)

```
\l__enumext_multicols_above_X_skip
\l__enumext_multicols_below_X_skip
```

Internal variables used by `columns` key §10.18).

```
67 \cs_set_protected:Npn \__enumext_tmp:n #1
68 {
69   \skip_new:c { \l__enumext_multicols_above_#1_skip }
70   \skip_new:c { \l__enumext_multicols_below_#1_skip }
71 }
72 \clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }
```

(End of definition for `\l__enumext_multicols_above_X_skip` and `\l__enumext_multicols_below_X_skip`.)

```
\g__enumext_minipage_stat_int
\l__enumext_minipage_left_skip
\l__enumext_minipage_right_skip
\l__enumext_minipage_after_skip
\g__enumext_minipage_right_skip
\g__enumext_minipage_after_skip
\l__enumext_minipage_left_X_dim
\l__enumext_minipage_active_X_bool
```

Internal variables used by `\miniright` command (§10.19.4) and the keys `miniright`, `miniright*`, `mini-env` and `mini-sep` (§10.17, §10.19).

```
73 \int_new:N \g__enumext_minipage_stat_int
74 \skip_new:N \l__enumext_minipage_left_skip
75 \skip_new:N \l__enumext_minipage_right_skip
76 \skip_new:N \l__enumext_minipage_after_skip
77 \skip_new:N \g__enumext_minipage_right_skip
78 \skip_new:N \g__enumext_minipage_after_skip
79 \cs_set_protected:Npn \__enumext_tmp:n #1
80 {
81   \dim_new:c { \l__enumext_minipage_left_#1_dim }
82   \bool_new:c { \l__enumext_minipage_active_#1_bool }
83 }
84 \clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\g__enumext_minipage_stat_int` and others.)

```
\l__enumext_wrap_label_X_bool
\l__enumext_wrap_label_opt_X_bool
\l__enumext_start_X_int
\l__enumext_fake_item_indent_X_tl
\l__enumext_label_fill_left_X_tl
\l__enumext_label_fill_right_X_tl
\l__enumext_vspace_a_star_X_bool
\l__enumext_vspace_b_star_X_bool
```

The integer variable `\l__enumext_start_X_int` are used by the `start` key (§10.12), the token list `\l__enumext_fake_item_indent_X_tl` is used by `itemindent` key, the variables `\l__enumext_label_fill_left_X_tl` and `\l__enumext_label_fill_right_X_tl` are used by the `align` key (§10.10). The boolean vars `\l__enumext_vspace_a_star_X_bool`, `\l__enumext_vspace_b_star_X_bool` are used by `above`, `above*`, `below` and `below*` keys

```
85 \cs_set_protected:Npn \__enumext_tmp:n #1
86 {
87   \bool_new:c { \l__enumext_wrap_label_#1_bool }
88   \bool_new:c { \l__enumext_wrap_label_opt_#1_bool }
89   \int_new:c { \l__enumext_start_#1_int }
90   \tl_new:c { \l__enumext_fake_item_indent_#1_tl }
91   \tl_new:c { \l__enumext_label_fill_left_#1_tl }
92   \tl_new:c { \l__enumext_label_fill_right_#1_tl }
93   \bool_new:c { \l__enumext_vspace_a_star_#1_bool }
94   \bool_new:c { \l__enumext_vspace_b_star_#1_bool }
95 }
96 \clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\l__enumext_wrap_label_X_bool` and others.)

```
\l__enumext_store_active_bool
\l__enumext_store_name_tl
\g__enumext_store_name_tl
\l__enumext_store_anskey_arg_tl
\l__enumext_store_columns_join_int
\l__enumext_store_keyans_label_tl
\l__enumext_store_keyans_item_opt_tl
\l__enumext_keyans_item_opt_tl
\l__enumext_keyans_tmpa_tl
```

The boolean variable `\l__enumext_store_active_bool` setting by `save-ans` key (§??) activates all the mechanism related to `\anskey`, `keyans`, `keyans*` and `keyanspic`.

The variable `\l__enumext_store_name_tl` sets the name for the storage in *sequence* and *prop list*, the variable `\g__enumext_store_name_tl` is just a copy of the storage name used by the `check-ans` key (§??).

The variable `\l__enumext_store_anskey_arg_tl` stores the contents of `\anskey` (§10.24) and the variable `\l__enumext_store_keyans_label_tl` stores the contents of `\item*` (§10.28.2) for the `keyans` and `keyans*` environments and the contents of `\anspic*` (§10.33.1) for the `keyanspic` environment.

The variable `\l__enumext_keyans_tmpa_tl` is a temporary variable used by `keyans` and `keyanspic` at various points.

```
97 \bool_new:N \l__enumext_store_active_bool
98 \tl_new:N \l__enumext_store_name_tl
99 \tl_new:N \g__enumext_store_name_tl
100 \tl_new:N \l__enumext_store_anskey_arg_tl
101 \int_new:N \l__enumext_store_columns_join_int
102 \tl_new:N \l__enumext_store_keyans_label_tl
103 \tl_new:N \l__enumext_store_keyans_item_opt_tl
104 \tl_new:N \l__enumext_keyans_item_opt_tl
105 \tl_new:N \l__enumext_keyans_tmpa_tl
```

(End of definition for `\l__enumext_store_active_bool` and others.)

Internal variables used by the command `\setenumext` (§10.38).

```
106 \tl_new:N \l__enumext_setkey_tmpa_tl
107 \tl_new:N \l__enumext_setkey_tmpb_tl
108 \int_new:N \l__enumext_setkey_tmpa_int
109 \seq_new:N \l__enumext_setkey_tmpa_seq
110 \seq_new:N \l__enumext_setkey_tmpb_seq
```

(End of definition for `\l__enumext_setkey_tmpa_tl` and others.)

Internal variables used by `[⟨key = val⟩]` in `enumext` and `enumext*` environment, the command `\printkeyans` (§10.37) and the keys `columns*` and `columns-sep*`.

```
111 \cs_set_protected:Npn \__enumext_tmp:n #1
112 {
113   \tl_new:c { l__enumext_store_opt_#1_tl }
114   \tl_new:c { l__enumext_print_keyans_#1_tl }
115   \bool_new:c { l__enumext_store_columns_#1_bool }
116   \int_new:c { l__enumext_store_columns_#1_int }
117   \bool_new:c { l__enumext_store_columns_sep_#1_bool }
118   \dim_new:c { l__enumext_store_columns_sep_#1_dim }
119   \bool_new:c { l__enumext_store_upper_level_#1_bool }
120 }
121 \clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\l__enumext_store_opt_X_tl` and others.)

Internal variables for “storage system” mechanism used by `\anskey` (§10.24), `keyans` and `keyanspic` environments. These variables are used by `show-ans`, `show-pos`, `mark-ans`, `save-key` and `mark-ref` keys (§10.23).

```
122 \bool_new:N \l__enumext_show_answer_bool
123 \bool_new:N \l__enumext_show_position_bool
124 \tl_new:N \l__enumext_mark_ref_sym_tl
125 \tl_new:N \l__enumext_mark_answer_sym_tl
126 \str_new:N \l__enumext_mark_position_str
```

(End of definition for `\l__enumext_show_answer_bool` and others.)

Internal variables used by `keyanspic` environment (§10.33.2).

```
127 \seq_new:N \l__enumext_keyans_pic_body_seq
128 \dim_new:N \l__enumext_keyans_pic_width_dim
129 \int_new:N \l__enumext_keyans_pic_above_int
130 \int_new:N \l__enumext_keyans_pic_below_int
131 \skip_new:N \l__enumext_keyans_pic_above_skip
```

(End of definition for `\l__enumext_keyans_pic_body_seq` and others.)

Internal variables used by “check answer” mechanism (§10.22.3) used by the `check-ans` and `no-store` keys and check for starred commands `\item*` in `keyans` and `keyans*` environments and `\anspic*` in `keyanspic` environment.

```
132 \bool_new:N \l__enumext_check_answers_bool
133 \bool_new:N \l__enumext_check_ans_key_bool
134 \bool_new:N \g__enumext_check_ans_key_bool
135 \tl_new:N \l__enumext_check_start_line_env_tl
136 \tl_new:N \g__enumext_start_line_tl
137 \tl_new:N \g__enumext_envir_name_tl
138 \int_new:N \g__enumext_check_starred_cmd_int
139 \int_new:N \g__enumext_item_anskey_int
140 \int_new:N \g__enumext_item_number_int
141 \int_new:N \g__enumext_item_answer_diff_int
```

(End of definition for `\l__enumext_check_answers_bool` and others.)

The boolean variable `\l__enumext_hyperref_bool` will determine if the `hyperref` package is present or load in memory (§10.7). The boolean variable `\l__enumext_footnotes_key_bool` determine if `hyperref` is load with `key hyperfootnotes=true`.

```
142 \bool_new:N \l__enumext_hyperref_bool
143 \bool_new:N \l__enumext_footnotes_key_bool
```

(End of definition for `\l__enumext_hyperref_bool` and `\l__enumext_footnotes_key_bool`.)

```

\l__enumext_newlabel_arg_one_tl
\l__enumext_newlabel_arg_two_tl
\l__enumext_store_write_aux_file_tl
\l__enumext_label_copy_X_tl

```

Internal variables are used when executing the `save-ref` key. The variables `\l__enumext_label_copy_X_tl` correspond to temporary copies of the labels defined by level on which operations will be performed.

The variables `\l__enumext_newlabel_arg_one_tl` and `\l__enumext_newlabel_arg_two_tl` will be used to form the arguments passed to the function `\__enumext_newlabel:nn` and the variable `\l__enumext_store_write_aux_file_tl` will be in charge of executing the writing code in the `.aux` file.

```

144 \tl_new:N \l__enumext_newlabel_arg_one_tl
145 \tl_new:N \l__enumext_newlabel_arg_two_tl
146 \tl_new:N \l__enumext_store_write_aux_file_tl
147 \cs_set_protected:Npn \__enumext_tmp:n #1
148 {
149   \tl_new:c { l__enumext_label_copy_#1_tl }
150 }
151 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_newlabel_arg_one_tl` and others.)

```

\g__enumext_footnote_int
\g__enumext_footnote_arg_seq
\g__enumext_footnote_int_seq

```

Internal variables used for redefinition of `\footnote`.

```

152 \int_new:N \g__enumext_footnote_int
153 \seq_new:N \g__enumext_footnote_arg_seq
154 \seq_new:N \g__enumext_footnote_int_seq

```

(End of definition for `\g__enumext_footnote_int`, `\g__enumext_footnote_arg_seq`, and `\g__enumext_footnote_int_seq`.)

```

\l__enumext_item_starred_X_bool
\l__enumext_item_column_pos_X_int
\g__enumext_item_count_all_X_int
\l__enumext_joined_item_X_int
\l__enumext_joined_item_aux_X_int
\l__enumext_tmpa_X_int
\l__enumext_item_text_X_box
\l__enumext_joined_width_X_dim
\l__enumext_item_width_X_dim
\g__enumext_item_symbol_aux_X_tl
\l__enumext_align_label_X_str
\g__enumext_minipage_active_X_bool
\g__enumext_miniright_code_X_tl
\g__enumext_minipage_center_X_bool
\g__enumext_minipage_right_X_dim
\g__enumext_minipage_right_X_skip

```

Internal variables used by `enumext*` and `keyans*` environments.

```

155 \cs_set_protected:Npn \__enumext_tmp:n #1
156 {
157   \bool_new:c { l__enumext_item_starred_#1_bool }
158   \int_new:c { l__enumext_item_column_pos_#1_int }
159   \int_new:c { g__enumext_item_count_all_#1_int }
160   \int_new:c { l__enumext_joined_item_#1_int }
161   \int_new:c { l__enumext_joined_item_aux_#1_int }
162   \int_new:c { l__enumext_tmpa_#1_int }
163   \box_new:c { l__enumext_item_text_#1_box }
164   \dim_new:c { l__enumext_joined_width_#1_dim }
165   \dim_new:c { l__enumext_item_width_#1_dim }
166   \tl_new:c { g__enumext_item_symbol_aux_#1_tl }
167   \str_new:c { l__enumext_align_label_#1_str }
168   \bool_new:c { g__enumext_minipage_active_#1_bool }
169   \tl_new:c { g__enumext_miniright_code_#1_tl }
170   \bool_new:c { g__enumext_minipage_center_#1_bool }
171   \dim_new:c { g__enumext_minipage_right_#1_dim }
172   \skip_new:c { g__enumext_minipage_right_#1_skip }
173 }
174 \clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_item_starred_X_bool` and others.)

```

\c__enumext_all_envs_clist

```

An internal `clist-var` variable to run with `\__enumext_tmp:n`.

```

175 \clist_const:Nn \c__enumext_all_envs_clist
176 {
177   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv},
178   {keyans}{v}, {enumext*}{vii}, {keyans*}{viii}
179 }

```

(End of definition for `\c__enumext_all_envs_clist`.)

## 10.5 Some utility functions

```

\__enumext_at_begin_document:n

```

A internal “hook” function used for copying plain `list` and `minipage` environments definition and `hyperref` detection.

```

180 \cs_new_protected:Npn \__enumext_at_begin_document:n #1
181 {
182   \hook_gput_code:nnn {begindocument} {enumext} { #1 }
183 }

```

(End of definition for `\__enumext_at_begin_document:n`.)



`\__enumext_after_env:nn` A internal “hook” function for execute code `minirigth` and `minirigth*` keys outside the `enumext*` and `keyans*` environments and print check-ans outside the `enumext` and `enumext*` environments.

```
184 \cs_new_protected:Npn \__enumext_after_env:nn #1 #2
185 {
186   \hook_gput_code:nnn {env/#1/after} {enumext} {#2}
187 }
```

(End of definition for `\__enumext_after_env:nn`.)

`\__enumext_level:` Function for check current level in `enumext`.

```
188 \cs_new:Nn \__enumext_level:
189 {
190   \int_to_roman:n { \__enumext_level_int }
191 }
```

(End of definition for `\__enumext_level:`.)

`\__enumext_if_is_int:nT` A conditional function to know if the variable we are passing is an integer used by `start` and `widest` keys. This function is taken directly from the answer given by Henri Menke in [How to test if an expl3 function argument is an integer expression?](#).  
`\__enumext_if_is_int:nF`  
`\__enumext_if_is_int:nTF`

```
192 \prg_new_protected_conditional:Npnn \__enumext_if_is_int:n #1 { T, F, TF }
193 {
194   \regex_match:nnTF { ^[\+|-]?[\d]+$ } {#1} % $
195   { \prg_return_true: }
196   { \prg_return_false: }
197 }
```

(End of definition for `\__enumext_if_is_int:nT`, `\__enumext_if_is_int:nF`, and `\__enumext_if_is_int:nTF`.)

`\__enumext_regex_counter_style:` The internal function `\__enumext_regex_counter_style:` replace the ‘\*’ with the actual counter of the running level and is used by the `ref` key. It loops through the defined counter styles in `\c__enumext_counter_style_tl` and replace ‘\*’ by real command, for example, looking for `\arabic*` and replacing that by `\arabic{<counter>}` defined on the current level.

```
198 \cs_new_protected:Nn \__enumext_regex_counter_style:
199 {
200   \tl_map_inline:Nn \c__enumext_counter_style_tl
201   {
202     \regex_replace_once:nnN { \c{##1}\* }
203     { \c{##1}\cB{\u{\__enumext_ref_the_count_tl}\cE} } \__enumext_ref_key_arg_tl
204   }
205 }
```

(End of definition for `\__enumext_regex_counter_style:`.)

`\__enumext_show_length:nnn` Internal function used by `show-length` key to show “all lengths” calculated and use in `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```
206 \cs_new:Npn \__enumext_show_length:nnn #1 #2 #3
207 {
208   * ~ #2
209   \prg_replicate:nn { 14 - \str_count:n {#2} } { ~ }
210   = ~ \use:c { #1_use:c } { \__enumext_#2_#3_#1 } \\
211 }
```

(End of definition for `\__enumext_show_length:nnn`.)

### 10.5.1 Utilities for environments and levels

`\__enumext_is_not_nested:` The function `\__enumext_is_not_nested:` set the variables `\g__enumext_standar_bool` and `\g__enumext_starred_bool` to “true” only if the environments `enumext` and `enumext*` are nested in each other.  
`\__enumext_is_on_first_level:`

```
212 \cs_new_protected:Nn \__enumext_is_not_nested:
213 {
214   \str_case:en { \@currentenv }
215   {
216     {enumext}
217     {
218       \bool_lazy_and:nnT
219       { \bool_not_p:n { \g__enumext_standar_bool } }
220       { \int_compare_p:nNn { \__enumext_level_h_int } = { 0 } }
221       {
222         \bool_gset_true:N \g__enumext_standar_bool
```

```

223     }
224   }
225   {enumext*}
226   {
227     \bool_lazy_and:nnT
228     { \bool_not_p:n { \g__enumext_starred_bool } }
229     { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
230     {
231       \bool_gset_true:N \g__enumext_starred_bool
232     }
233   }
234 }
235 }

```

The function `\__enumext_is_on_first_level:` will set the variables `\l__enumext_standard_first_bool` and `\l__enumext_starred_first_bool` to “true” only if the environment is not nested and we are in the “first level” of it. We will also save the start line number of each environment in the variable `\g__enumext_start_line_tl` and the name of each environment in the variable `\g__enumext_envir_name_tl` to use in messages related to the `check-ans` key and `.log` file.

```

236 \cs_new_protected:Nn \__enumext_is_on_first_level:
237 {
238   \bool_lazy_all:nT
239   {
240     { \bool_if_p:N \g__enumext_standar_bool }
241     { \int_compare_p:nNn { \l__enumext_level_int } = { 1 } }
242     { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
243   }
244   {
245     \bool_set_true:N \l__enumext_standar_first_bool
246     \tl_gset:Nn \g__enumext_envir_name_tl { enumext }
247     \tl_gset:Ne \g__enumext_start_line_tl
248     {
249       on ~ line ~ \exp_not:V \inputlineno
250     }
251   }
252   \bool_lazy_all:nT
253   {
254     { \bool_if_p:N \g__enumext_starred_bool }
255     { \int_compare_p:nNn { \l__enumext_level_h_int } = { 1 } }
256     { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
257   }
258   {
259     \bool_set_true:N \l__enumext_starred_first_bool
260     \tl_gset:Nn \g__enumext_envir_name_tl { enumext* }
261     \tl_gset:Ne \g__enumext_start_line_tl
262     {
263       on ~ line ~ \exp_not:V \inputlineno
264     }
265   }
266 }

```

(End of definition for `\__enumext_is_not_nested:` and `\__enumext_is_on_first_level:`)

`\__enumext_keyans_save_start_line:`

The function `\__enumext_keyans_save_start_line:` will save the start line number of the environments `keyans`, `keyans*` and `keyanspic` in the variable `\l__enumext_check_start_line_env_tl` to use in the `\__enumext_check_starred_cmd:n` function.

```

267 \cs_new_protected:Nn \__enumext_keyans_save_start_line:
268 {
269   \str_case:en { \@currenvir }
270   {
271     {keyans}
272     {
273       \tl_set:Ne \l__enumext_check_start_line_env_tl
274       {
275         in ~ 'keyans' ~ start ~ on ~ line ~ \exp_not:V \inputlineno
276       }
277     }
278     {keyans*}
279     {
280       \tl_set:Ne \l__enumext_check_start_line_env_tl
281       {

```

```

282             in ~ 'keyans*' ~ start ~ on ~ line ~ \exp_not:V \inputlineno
283         }
284     }
285     {keyanspic}
286     {
287         \tl_set:Nc \l__enumext_check_start_line_env_tl
288         {
289             in ~ 'keyanspic' ~ start ~ on ~ line ~ \exp_not:V \inputlineno
290         }
291     }
292 }
293 }

```

(End of definition for `\__enumext_keyans_save_start_line:`)

### 10.5.2 Utilities for log and terminal

The function `\__enumext_reset_global_vars:` will be passed to the function `\__enumext_execute_after_env:` and will return the global variables to their default values after being used.

```

294 \cs_new_protected:Nn \__enumext_reset_global_vars:
295 {
296     \__enumext_reset_global_int:
297     \__enumext_reset_global_bool:
298     \__enumext_reset_global_tl:
299 }
300 \cs_new_protected:Nn \__enumext_reset_global_int:
301 {
302     \int_gzero:N \g__enumext_item_number_int
303     \int_gzero:N \g__enumext_item_anskey_int
304     \int_gzero:N \g__enumext_item_answer_diff_int
305 }
306 \cs_new_protected:Nn \__enumext_reset_global_bool:
307 {
308     \bool_gset_false:N \g__enumext_check_ans_key_bool
309     \bool_gset_false:N \g__enumext_standar_bool
310     \bool_gset_false:N \g__enumext_starred_bool
311 }
312 \cs_new_protected:Nn \__enumext_reset_global_tl:
313 {
314     \tl_gclear:N \g__enumext_store_name_tl
315     \tl_gclear:N \g__enumext_start_line_tl
316     \tl_gclear:N \g__enumext_envir_name_tl
317 }

```

(End of definition for `\__enumext_reset_global_vars:` and others.)

The function `\__enumext_log_global_vars:` will be passed to the function `\__enumext_execute_after_env:` and write to the `.log` file the number of elements saved in the *prop list* and *sequence* created by the `save-ans` key along with the value of the integer variable created for the `resume` key.

```

318 \cs_new_protected:Nn \__enumext_log_global_vars:
319 {
320     \msg_log:nneeee { enumext } { prop-seq-int-hook }
321     { \g__enumext_store_name_tl }
322     { \prop_count:c { g__enumext_ \g__enumext_store_name_tl _prop } }
323     { \seq_count:c { g__enumext_ \g__enumext_store_name_tl _seq } }
324     { \int_use:c { g__enumext_resume_ \g__enumext_store_name_tl _int } }
325 }

```

The function `\__enumext_log_answer_vars:` will be passed to the function `\__enumext_execute_after_env:` and write to the `.log` file the number of items and answers along with the difference between them.

```

326 \cs_new_protected:Nn \__enumext_log_answer_vars:
327 {
328     \msg_log:nneee { enumext } { item-answer-hook }
329     { \int_use:N \g__enumext_item_number_int }
330     { \int_use:N \g__enumext_item_anskey_int }
331     { \int_eval:n { \g__enumext_item_number_int - \g__enumext_item_anskey_int } }
332 }

```

(End of definition for `\__enumext_log_global_vars:` and `\__enumext_log_answer_vars:`)

## 10.6 Copying list and minipage environments

The `list` environment provided by  $\text{\LaTeX}$  has the following plain form:

```
\list{⟨arg one⟩}{⟨arg two⟩}
  \item[⟨opt⟩]
\endlist
```

As a precaution we copy them using `\__enumext_at_begin_document:n` in case any package redefines the `list` environment or a related command.

```
\__enumext_start_list:nn
  \__enumext_stop_list:
  \__enumext_item_std:w
```

The functions `\__enumext_start_list:nn`, `\__enumext_stop_list:` and `\__enumext_item_std:w` correspond to copies of `\list`, `\endlist` and `\item` from plain definition of `list` environment.

```
333 \__enumext_at_begin_document:n
334 {
335   \cs_new_eq:NN \__enumext_start_list:nn \list
336   \cs_new_eq:NN \__enumext_stop_list: \endlist
337   \cs_new_eq:NN \__enumext_item_std:w \item
338 }
```

(End of definition for `\__enumext_start_list:nn`, `\__enumext_stop_list:`, and `\__enumext_item_std:w`.)

The `minipage` environment provided by  $\text{\LaTeX}$  has the following (simplified) plain form:

```
\minipage[⟨pos⟩][⟨height⟩][⟨inner-pos⟩]{⟨width⟩}
  ⟨internal implement⟩
\endminipage
```

As a precaution we copy them using `\__enumext_at_begin_document:n` in case any package redefines the `minipage` environment or a related command.

```
\__enumext_minipage:w
\__enumext_endminipage:
```

The functions `\__enumext_minipage:w`, `\__enumext_endminipage:` and correspond to copies of `\minipage`, `\endminipage` from plain definition of `minipage` environment.

```
339 \__enumext_at_begin_document:n
340 {
341   \cs_new_eq:NN \__enumext_minipage:w \minipage
342   \cs_new_eq:NN \__enumext_endminipage: \endminipage
343 }
```

(End of definition for `\__enumext_minipage:w` and `\__enumext_endminipage:.`)

## 10.7 Compatibility with hyperref and footnotehyper

First we define the necessary rules using “hooks” to determine if the `hyperref` package is loaded.

```
344 \hook_gput_code:nnn { begindocument } { enumext } { \__enumext_after_hyperref: }
345 \hook_gset_rule:nnnn { begindocument } { enumext } { after } { hyperref }
```

```
\__enumext_after_hyperref:
\__enumext_hypertarget:nn
\__enumext_phantomsection:
```

The function `\__enumext_after_hyperref:` sets the state of the boolean variable `\l__enumext_hyperref_bool` to “true” if the package is loaded. At this point we will use the public macro `\IfHyperBoolean` to determine if the `hyperfootnotes=true` key is present, if so, we set the state of the boolean variable `\__enumext_footnotes_key_bool` to “true”.

```
346 \cs_new_protected:Nn \__enumext_after_hyperref:
347 {
348   \IfPackageLoadedTF { hyperref }
349   {
350     \msg_info:nnn { enumext } { package-load } { hyperref }
351     \bool_set_true:N \l__enumext_hyperref_bool
352     \IfHyperBoolean{hyperfootnotes}
353     {
354       \typeout{hyperfootnotes=true}
355       \bool_set_true:N \l__enumext_footnotes_key_bool
356     }
357     { \typeout{hyperfootnotes=false} }
358   }
359   { }
```

If the state of the variable `\l__enumext_footnotes_key_bool` is true we will check if the package `footnotehyper` is loaded, in case it is not present, we will set the value of `\l__enumext_footnotes_key_bool` to false and we will redefine `\footnote`.

```
360   \bool_if:NT \l__enumext_footnotes_key_bool
361   {
362     \IfPackageLoadedTF { footnotehyper }
363     {
```

```

364         \msg_info:nnn { enumext } { package-load } { footnotehyper }
365     }
366     {
367         \typeout{No ~ footnotehyper ~ load}
368         \typeout{Load ~ and ~ use ~ \string\makesavenoteenv{enumext*}}
369         \bool_set_false:N \l__enumext_footnotes_key_bool
370     }
371 }

```

The functions `\__enumext_hypertarget:nn` and `\__enumext_phantomsection:` correspond to the internal copies of `\hypertarget` and `\phantomsection`. If the boolean variable `\l__enumext_hyperref_bool` is false the functions `\__enumext_hypertarget:nn` and `\__enumext_phantomsection:` will be disabled.

```

372     \bool_if:NTF \l__enumext_hyperref_bool
373     {
374         \cs_new_eq:NN \__enumext_hypertarget:nn \hypertarget
375         \cs_new_eq:NN \__enumext_phantomsection: \phantomsection
376     }
377     {
378         \cs_new_eq:NN \__enumext_hypertarget:nn \use_none:nn
379         \cs_new_eq:NN \__enumext_phantomsection: \prg_do_nothing:
380     }
381 }

```

(End of definition for `\__enumext_after_hyperref:`, `\__enumext_hypertarget:nn`, and `\__enumext_phantomsection:`.)

`\__enumext_newlabel:nn`

The function `\__enumext_newlabel:nn` write the information to the `.aux` file when using the `save-ref` key. The arguments taken by the function are:

- #1: `\l__enumext_newlabel_arg_one_tl`
- #2: `\l__enumext_newlabel_arg_two_tl`

🔗 The trick here is to manage the number of arguments passed to `\newlabel{#1}{#2}` according to the presence of the `hyperref` package.

```

382 \cs_new_protected:Npn \__enumext_newlabel:nn #1 #2
383 {
384     \protected@write \@auxout { }
385     {
386         \token_to_str:N \newlabel {#1}
387         {
388             {#2}
389             \bool_if:NT \l__enumext_hyperref_bool
390             { { \thepage } {#2} {#1} }
391             { }
392         }
393     }
394     \__enumext_hypertarget:nn {#1} { }
395     \__enumext_phantomsection:
396 }

```

(End of definition for `\__enumext_newlabel:nn`.)

## 10.8 Definition of counters

`\__enumext_define_counters:Nn`

`\__enumext_define_counters:cn`

To create the necessary “counters” we must first make sure that they are not already defined by the user or a package such as `enumitem`, otherwise a error will be returned and the package loading will be aborted. The arguments taken by the function are:

- #1: A token list `\l__enumext_counter_X_tl` for “store” the counter’s name.
- #2: The counter’s name.

```

397 \cs_new_protected:Npn \__enumext_define_counters:Nn #1 #2
398 {
399     \cs_if_exist:cTF { c@ #2 }
400     { \msg_fatal:nnn { enumext } { counters } { #2 } }
401     {
402         \tl_set:Nn #1 { #2 }
403         \newcounter { #2 }
404     }
405 }

```

(End of definition for `\__enumext_define_counters:Nn`.)

enumXi The counters created here are enumXi, enumXii, enumXiii and enumXiv for enumext environment,  
enumXii enumXv for keyans environment, enumXvi for keyanspic environment, enumXvii for enumext\* and  
enumXiii enumXviii for the keyans\* environments.

```
enumXiv 406 \__enumext_define_counters:Nn \__enumext_counter_i_tl { enumXi }
enumXv 407 \__enumext_define_counters:Nn \__enumext_counter_ii_tl { enumXii }
enumXvi 408 \__enumext_define_counters:Nn \__enumext_counter_iii_tl { enumXiii }
enumXvii 409 \__enumext_define_counters:Nn \__enumext_counter_iv_tl { enumXiv }
enumXviii 410 \__enumext_define_counters:Nn \__enumext_counter_v_tl { enumXv }
411 \__enumext_define_counters:Nn \__enumext_counter_vi_tl { enumXvi }
412 \__enumext_define_counters:Nn \__enumext_counter_vii_tl { enumXvii }
413 \__enumext_define_counters:Nn \__enumext_counter_viii_tl { enumXviii }
```

(End of definition for enumXi and others.)

## 10.9 Definition of labels

This part of the code is inspired by the `enumitem` package. The idea is to be able to access the counters using `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` to use them in the `label` key.

\\_\_enumext\_register\_counter\_style:Nn

These *⟨counters⟩* will be used as default *⟨labels⟩* if the `label` key is not used for the different levels of the `enumext` environment and the `keyans` environment, so it is necessary to get a default value for `labelwidth` from these *⟨labels⟩* at the same time.

```
414 \cs_new_protected:Npn \__enumext_register_counter_style:Nn #1 #2
415 {
416   \tl_const:cn { c__enumext_widest_ \cs_to_str:N #1 _tl } {#2}
417   \tl_gput_right:Nn \g__enumext_counter_styles_tl {#1}
418 }
419 \__enumext_register_counter_style:Nn \arabic { 0 }
420 \__enumext_register_counter_style:Nn \Alph { M }
421 \__enumext_register_counter_style:Nn \alph { m }
422 \__enumext_register_counter_style:Nn \Roman { VIII }
423 \__enumext_register_counter_style:Nn \roman { viii }
```

(End of definition for \\_\_enumext\_register\_counter\_style:Nn.)

\\_\_enumext\_label\_width\_by\_box:Nn

\\_\_enumext\_label\_width\_by\_box:cv

The function `\__enumext_label_width_by_box:Nn` set the default `\labelwidth` using a box width if no `labelwidth` key is passed.

```
424 \cs_new_protected:Npn \__enumext_label_width_by_box:Nn #1 #2
425 {
426   \hbox_set:Nn \l__enumext_label_width_by_box {#2}
427   \dim_set:Nn #1 { \box_wd:N \l__enumext_label_width_by_box }
428 }
429 \cs_generate_variant:Nn \__enumext_label_width_by_box:Nn { cv }
```

(End of definition for \\_\_enumext\_label\_width\_by\_box:Nn.)

\\_\_enumext\_label\_style:Nnn

\\_\_enumext\_label\_style:cvn

The function `\__enumext_label_style:Nnn` is used by the `label` key to creates the variables containing the *⟨label style⟩* and will allow to use `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` as arguments. It loops through the defined counter styles in `\g__enumext_counter_styles_tl` (`\arabic`, `\alph`, `\Alph`, `\roman`, and `\Roman`) for example, looking for `\roman*` and replacing that by `\roman{⟨counter⟩}`, and doing the same for the `\g__enumext_widest_label_tl` to keep both in sync.

```
430 \cs_new_protected:Npn \__enumext_label_style:Nnn #1 #2 #3
431 {
432   \tl_clear_new:N #1
433   \tl_put_right:Ne #1 { \tl_trim_spaces:n {#3} }
434   \tl_gset_eq:NN \g__enumext_widest_label_tl #1
435   \tl_map_inline:Nn \g__enumext_counter_styles_tl
436   {
437     \tl_replace_all:Nne #1 { ##1* } { \exp_not:N ##1 {#2} }
438     \tl_greplace_all:Nne \g__enumext_widest_label_tl { ##1* }
439     { \tl_use:c { c__enumext_widest_ \cs_to_str:N ##1 _tl } }
440   }
441   \__enumext_label_width_by_box:Nn \l__enumext_current_widest_dim
442   { \tl_use:N \g__enumext_widest_label_tl }
443   \tl_set_eq:cN { the #2 } #1
444 }
445 \cs_generate_variant:Nn \__enumext_label_style:Nnn { cvn }
```

(End of definition for \\_\_enumext\_label\_style:Nnn.)



## 10.10 Setting keys associated with label

font Definition of keys `font`, `labelsep`, `labelwidth`, `wrap-label` and `wrap-label*` keys for `enumext` and `keyans` environments.

```

446 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
447 {
448   \keys_define:nn { enumext / #1 }
449   {
450     font .tl_set:c = { l__enumext_label_font_style_#2_tl },
451     font .value_required:n = true,
452     labelsep .dim_set:c = { l__enumext_labelsep_#2_dim },
453     labelsep .initial:n = {0.3333em},
454     labelsep .value_required:n = true,
455     labelwidth .dim_set:c = { l__enumext_labelwidth_#2_dim },
456     labelwidth .value_required:n = true,
457     wrap-label .cs_set_protected:cp = { __enumext_wrapper_label_#2:n } ##1,
458     wrap-label .initial:n = {##1},
459     wrap-label .value_required:n = true,
460     wrap-label* .code:n = {
461       \bool_set_true:c { l__enumext_wrap_label_opt_#2_bool }
462       \keys_set:nn { enumext / #1 } { wrap-label = {##1} }
463     },
464     wrap-label* .value_required:n = true,
465   }
466 }
467 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `font` and others.)

- In this point, the following are set `\__enumext_wrapper_label_X:n` which will be used by `\__enumext_make_label:` for the different levels of the `enumext` environment and is set to `\__enumext_wrapper_label_v:n` which will be used by `\__enumext_keyans_make_label:` for `keyans` and `keyanspic` environments.

`align` The `align` key is implemented differently for “starred” and “non starred” environments.

```

468 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
469 {
470   \keys_define:nn { enumext / #1 }
471   {
472     align .choice:,
473     align / left .code:n =
474       {
475         \tl_clear:c { l__enumext_label_fill_left_#2_tl }
476         \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
477       },
478     align / right .code:n =
479       {
480         \tl_set:cn { l__enumext_label_fill_left_#2_tl } { \hfill }
481         \tl_clear:c { l__enumext_label_fill_right_#2_tl }
482       },
483     align / center .code:n =
484       {
485         \tl_set:cn { l__enumext_label_fill_left_#2_tl } { \hfill }
486         \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
487       },
488     align .initial:n = left,
489     align .value_required:n = true,
490   }
491 }
492 \clist_map_inline:nn
493 {
494   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {keyans}{v}
495 }
496 { \__enumext_tmp:nn #1 }

497 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
498 {
499   \keys_define:nn { enumext / #1 }
500   {
501     align .choice:,
502     align / left .code:n = \str_set:cn { l__enumext_align_label_#2_str } { l },
503     align / right .code:n = \str_set:cn { l__enumext_align_label_#2_str } { r },
504     align / center .code:n = \str_set:cn { l__enumext_align_label_#2_str } { c },

```

```

505         align .initial:n = left,
506         align .value_required:n = true,
507     }
508 }
509 \clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }

```

(End of definition for align.)

### 10.11 Setting label and ref keys

The implementation of the keys `label` and `ref` are part of the core of the package `enumext`, here the default values for `\label`, the value of the variables `\l__enumext_label_X_tl`, the default values for `\labelwidth` and the “label and ref” system.

#### 10.11.1 Define and set label and ref keys for enumext environment

Here we set the default (*labels*) of the *four levels* of `enumext` environment, along with the default value for `labelwidth` key and `ref` key.

```

\l__enumext_label_i_tl
\l__enumext_label_ii_tl
\l__enumext_label_iii_tl
\l__enumext_label_iv_tl
510 \cs_set_protected:Npn \__enumext_tmp:nnn #1 #2 #3
511 {
512     \keys_define:nn { enumext / #1 }
513     {
514         label .code:n = {
515             \__enumext_label_style:cnv { \l__enumext_label_#2_tl }
516             { \l__enumext_counter_#2_tl } {##1}
517             \dim_set_eq:cN { \l__enumext_labelwidth_#2_dim }
518             \l__enumext_current_widest_dim
519         },
520         label .initial:n = #3,
521         label .value_required:n = true,
522         ref .code:n = \__enumext_standar_ref:n {##1},
523         ref .value_required:n = true,
524     }
525 }
526 \__enumext_tmp:nnn { level-1 } { i } { \arabic*. }
527 \__enumext_tmp:nnn { level-2 } { ii } { (\alph*. ) }
528 \__enumext_tmp:nnn { level-3 } { iii } { \roman*. }
529 \__enumext_tmp:nnn { level-4 } { iv } { \Alph*. }

```

(End of definition for label and others.)

```

\__enumext_standar_ref:n
\__enumext_standar_ref:

```

The `\__enumext_standar_ref:n` first we will pass the key argument to `\l__enumext_ref_key_arg_tl` and we will analyze its state, if it is not *empty* we will make a copy of the current counter in `\l__enumext_ref_the_count_tl` and we will execute the function `\__enumext_regex_counter_style:` which will return the modified `\l__enumext_ref_key_arg_tl` and we make the value of `\l__enumext_ref_the_count_tl` the same as that `\l__enumext_the_counter_X_tl` which contains `\theenumX` and finally we set `\l__enumext_renew_the_count_X_tl` with the renewed command.

```

530 \cs_new_protected:Npn \__enumext_standar_ref:n #1
531 {
532     \tl_set:Nn \l__enumext_ref_key_arg_tl {#1}
533     \tl_if_empty:NTF \l__enumext_ref_key_arg_tl
534     {
535         \msg_error:nnn { enumext } { key-ref-empty } { enumext }
536     }
537     {
538         \tl_set_eq:Nc
539         \l__enumext_ref_the_count_tl { \l__enumext_counter_ \__enumext_level: _tl }
540         \__enumext_regex_counter_style:
541         \tl_set_eq:Nc
542         \l__enumext_ref_the_count_tl { \l__enumext_the_counter_ \__enumext_level: _tl }
543         \tl_put_right:ce { \l__enumext_renew_the_count_ \__enumext_level: _tl }
544         {
545             \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_the_count_tl }
546             { \exp_not:V \l__enumext_ref_key_arg_tl }
547         }
548     }
549 }

```

Finally the function `\__enumext_standar_ref:` will execute the modification for the reference system in the second argument of the environment definition `enumext`.

```

550 \cs_new_protected:Nn \__enumext_standar_ref:
551 {

```

```

552   \tl_if_empty:cF { \__enumext_renew_the_count_ \__enumext_level: _tl }
553   {
554     \tl_use:c { \__enumext_renew_the_count_ \__enumext_level: _tl }
555   }
556 }

```

(End of definition for `\__enumext_standar_ref:n` and `\__enumext_standar_ref:.`)

### 10.11.2 Define and set label and ref keys for enumext\* and keyans\* environments

Here we set the default *labels* for `enumext*` and `keyans*` environments, along with the default value for `labelwidth` key and `ref` key.

```

\__enumext_label_vii_tl
\__enumext_label_viii_tl
557 \cs_set_protected:Npn \__enumext_tmp:nnn #1 #2 #3
558 {
559   \keys_define:nn { enumext / #1 }
560   {
561     label .code:n = {
562       \__enumext_label_style:cvn { \__enumext_label_#2_tl }
563       { \__enumext_counter_#2_tl } {##1}
564       \dim_set_eq:cN { \__enumext_labelwidth_#2_dim }
565       \__enumext_current_widest_dim
566     },
567     label .initial:n = #3,
568     label .value_required:n = true,
569     ref .code:n = \__enumext_starred_ref:n {##1},
570     ref .value_required:n = true,
571   }
572 }
573 \__enumext_tmp:nnn { enumext* } { vii } { \arabic*.}
574 \__enumext_tmp:nnn { keyans* } { viii } { (\Alph*) }

```

(End of definition for `label` and others.)

```

\__enumext_starred_ref:n
\__enumext_starred_ref:

```

The implementation of `\__enumext_starred_ref:n` is the same as that used for the environment `enumext`.

```

575 \cs_new_protected:Npn \__enumext_starred_ref:n #1
576 {
577   \tl_set:Nn \__enumext_ref_key_arg_tl {#1}
578   \int_compare:nNnT { \__enumext_level_h_int } = { 1 }
579   {
580     \tl_if_empty:NTF \__enumext_ref_key_arg_tl
581     {
582       \msg_error:nnn { enumext } { key-ref-empty } { enumext* }
583     }
584     {
585       \tl_set_eq:NN \__enumext_ref_the_count_tl \__enumext_counter_vii_tl
586       \__enumext_regex_counter_style:
587       \tl_set_eq:NN \__enumext_ref_the_count_tl \__enumext_the_counter_vii_tl
588       \tl_put_right:Ne \__enumext_renew_the_count_vii_tl
589       {
590         \exp_not:N \renewcommand { \exp_not:V \__enumext_ref_the_count_tl }
591         { \exp_not:V \__enumext_ref_key_arg_tl }
592       }
593     }
594   }
595   \int_compare:nNnT { \__enumext_keyans_level_h_int } = { 1 }
596   {
597     \tl_if_empty:NTF \__enumext_ref_key_arg_tl
598     {
599       \msg_error:nnn { enumext } { key-ref-empty } { keyans* }
600     }
601     {
602       \tl_set_eq:NN \__enumext_ref_the_count_tl \__enumext_counter_viii_tl
603       \__enumext_regex_counter_style:
604       \tl_set_eq:NN \__enumext_ref_the_count_tl \__enumext_the_counter_viii_tl
605       \tl_put_right:Ne \__enumext_renew_the_count_viii_tl
606       {
607         \exp_not:N \renewcommand { \exp_not:V \__enumext_ref_the_count_tl }
608         { \exp_not:V \__enumext_ref_key_arg_tl }
609       }
610     }
611   }
612 }

```

Finally the function `\__enumext_starred_ref:` will execute the modification for the reference system in the second argument of the `enumext*` and `keyans*` environment definition.

```

613 \cs_new_protected:Nn \__enumext_starred_ref:
614 {
615   \int_compare:nNt { \__enumext_level_h_int } = { 1 }
616   {
617     \tl_if_empty:NF \__enumext_renew_the_count_vii_tl
618     {
619       \tl_use:N \__enumext_renew_the_count_vii_tl
620     }
621   }
622   \int_compare:nNt { \__enumext_keyans_level_h_int } = { 1 }
623   {
624     \tl_if_empty:NF \__enumext_renew_the_count_viii_tl
625     {
626       \tl_use:N \__enumext_renew_the_count_viii_tl
627     }
628   }
629 }

```

(End of definition for `\__enumext_starred_ref:n` and `\__enumext_starred_ref:`.)

### 10.11.3 Define and set label and ref keys for keyans and keyanspic environments

Here we set the default *label* for `keyans` and `keyanspic` environment, along with the default value for `labelwidth` and `ref` key. The `keyanspic` environment use the same *label* as the `keyans` environment.

```

\__enumext_label_v_tl
\__enumext_label_vi_tl
630 \keys_define:nn { enumext / keyans }
631 {
632   label .code:n = {
633     \__enumext_label_style:cvn { \__enumext_label_v_tl }
634     { \__enumext_counter_v_tl } {#1}
635     \dim_set_eq:cN { \__enumext_labelwidth_v_dim }
636     \__enumext_current_widest_dim
637     \__enumext_label_style:cvn { \__enumext_label_vi_tl }
638     { \__enumext_counter_vi_tl } {#1}
639     \dim_set_eq:cN { \__enumext_labelwidth_v_dim }
640     \__enumext_current_widest_dim
641   },
642   label .initial:n = (\Alph*),
643   label .value_required:n = true,
644   ref .code:n = \__enumext_keyans_ref:n {#1},
645   ref .value_required:n = true,
646 }

```

(End of definition for `label` and others.)

The implementation of `\__enumext_keyans_ref:n` is the same as that used for the environment `enumext`.

```

647 \cs_new_protected:Npn \__enumext_keyans_ref:n #1
648 {
649   \tl_set:Nn \__enumext_ref_key_arg_tl {#1}
650   \tl_if_empty:NTF \__enumext_ref_key_arg_tl
651   {
652     \msg_error:nnn { enumext } { key-ref-empty } { keyans }
653   }
654   {
655     \tl_set_eq:NN \__enumext_ref_the_count_tl \__enumext_counter_v_tl
656     \__enumext_regex_counter_style:
657     \tl_set_eq:NN \__enumext_ref_the_count_tl \__enumext_the_counter_v_tl
658     \tl_put_right:Ne \__enumext_renew_the_count_v_tl
659     {
660       \exp_not:N \renewcommand { \exp_not:V \__enumext_ref_the_count_tl }
661       { \exp_not:V \__enumext_ref_key_arg_tl }
662     }
663   }
664 }

```

Finally the function `\__enumext_keyans_ref:` will execute the modification for the reference system in the second argument of the `keyans*` environment definition.

```

665 \cs_new_protected:Nn \__enumext_keyans_ref:
666 {
667   \tl_if_empty:NF \__enumext_renew_the_count_v_tl

```

```

668     {
669         \tl_use:N \l__enumext_renew_the_count_v_tl
670     }
671 }

```

(End of definition for `\__enumext_keyans_ref:n` and `\__enumext_keyans_ref:.`)

## 10.12 Setting start and widest keys

```

\__enumext_start_from:NNn
\__enumext_start_from:ccn

```

The function `\__enumext_start_from:NNn` used by the `start` key take three arguments:

```

#1: \l__enumext_label_X_tl
#2: \l__enumext_start_X_int
#3: <integer or string>

```

The first argument of this function are the “counter style” set by `label` key, the second argument is returned by the function, the third argument can be an *<integer>* or *<string>* of the form `\Alph`, `\alph`, `\Roman` or `\roman`. This effectively allows `start=A` or `start=1` to be used.

```

672 \cs_new_protected:Npn \__enumext_start_from:NNn #1 #2 #3
673 {
674     \__enumext_if_is_int:nTF { #3 }
675     {
676         \int_set:Nn #2 {#3}
677     }
678     {
679         \regex_match:nVT { \c{Alph} | \c{alph} } {#1}
680         { \int_set:Nn #2 { \int_from_alph:n {#3} } }
681         \regex_match:nVT { \c{Roman} | \c{roman} } {#1}
682         { \int_set:Nn #2 { \int_from_roman:n {#3} } }
683     }
684 }
685 \cs_generate_variant:Nn \__enumext_start_from:NNn { ccn }

```

(End of definition for `\__enumext_start_from:NNn`.)

```

\__enumext_widest_from:nNNn
\__enumext_widest_from:nccn

```

The function `\__enumext_widest_from:nNNn` used by the `widest` key take four arguments:

```

#1: The counter associated with the environment level
#2: \l__enumext_label_X_tl
#3: \l__enumext_labelwidth_X_dim
#4: <integer or string>

```

The second and third arguments of this function are the values set by `label` and `labelwidth` keys, the four argument can be an *<integer>* or *<string>* of the form `\Alph`, `\alph`, `\Roman` or `\roman`. The value of the four argument is set temporarily for the identified counter in this point (level), then the value is expanded into a “box” and the “width” of the “box” is returned.

```

686 \cs_new_protected:Npn \__enumext_widest_from:nNNn #1 #2 #3 #4
687 {
688     \__enumext_if_is_int:nTF {#4}
689     {
690         \setcounter{enumX#1} { #4 }
691     }
692     {
693         \regex_match:nVT { \c{Alph} | \c{alph} } {#2}
694         { \setcounter{enumX#1} { \int_from_alph:n {#4} } }
695         \regex_match:nVT { \c{Roman} | \c{roman} } {#2}
696         { \setcounter{enumX#1} { \int_from_roman:n {#4} } }
697     }
698     \__enumext_label_width_by_box:cv
699     { \l__enumext_labelwidth_#1_dim } { \l__enumext_label_#1_tl }
700 }
701 \cs_generate_variant:Nn \__enumext_widest_from:nNNn { nccn }

```

(End of definition for `\__enumext_widest_from:nNNn`.)

```

start
widest
\l__enumext_start_X_int

```

Now define and set `start` and `widest` keys for `enumext` and `keyans` environments.

```

702 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
703 {
704     \keys_define:nn { enumext / #1 }
705     {
706         start .code:n = {
707             \__enumext_start_from:ccn
708             { \l__enumext_label_#2_tl }
709             { \l__enumext_start_#2_int } {#1}

```

```

710         },
711         start .initial:n = 1,
712         widest .code:n = {
713             \__enumext_widest_from:nccn {#2}
714             { \__enumext_label_#2_tl }
715             { \__enumext_labelwidth_#2_dim } {##1}
716         },
717         widest .value_required:n = true,
718         start .value_required:n = true,
719     }
720 }
721 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `start`, `widest`, and `\__enumext_start_X_int`.)

### 10.13 Setting keys for vertical spaces

Define and set `topsep`, `partopsep`, `parsep`, `itemsep`, `noitemsep` and `nosep` keys for `enumext` and `keyans` environments.

```

722 \cs_set_protected:Npn \__enumext_tmp:nnnnnn #1 #2 #3 #4 #5 #6
723 {
724     \keys_define:nn { enumext / #1 }
725     {
726         topsep .skip_set:c = { \__enumext_topsep_#2_skip },
727         topsep .initial:n = {#3},
728         topsep .value_required:n = true,
729         partopsep .skip_set:c = { \__enumext_partopsep_#2_skip },
730         partopsep .initial:n = {#4},
731         partopsep .value_required:n = true,
732         parsep .skip_set:c = { \__enumext_parsep_#2_skip },
733         parsep .initial:n = {#5},
734         parsep .value_required:n = true,
735         itemsep .skip_set:c = { \__enumext_itemsep_#2_skip },
736         itemsep .initial:n = {#6},
737         itemsep .value_required:n = true,
738         noitemsep .meta:n = { itemsep = 0pt, parsep = 0pt },
739         noitemsep .value_forbidden:n = true,
740         nosep .meta:n = {
741             itemsep = 0pt, parsep = 0pt,
742             topsep = 0pt, partopsep = 0pt,
743         },
744         nosep .value_forbidden:n = true,
745     }
746 }

```

Now we set the values based on standard `article` class in `10pt`.

```

747 \__enumext_tmp:nnnnnn { level-1 } { i } { 8.0pt plus 2.0pt minus 4.0pt }
748 { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
749 { 4.0pt plus 2.0pt minus 1.0pt }
750 \__enumext_tmp:nnnnnn { level-2 } { ii } { 4.0pt plus 2.0pt minus 1.0pt }
751 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
752 { 2.0pt plus 1.0pt minus 1.0pt }
753 \__enumext_tmp:nnnnnn { level-3 } { iii } { 2.0pt plus 1.0pt minus 1.0pt }
754 { 1.0pt minus 1.0pt } { 0pt } { 2.0pt plus 1.0pt minus 1.0pt }
755 \__enumext_tmp:nnnnnn { level-4 } { iv } { 2.0pt plus 1.0pt minus 1.0pt }
756 { 1.0pt minus 1.0pt } { 0pt } { 2.0pt plus 1.0pt minus 1.0pt }
757 \__enumext_tmp:nnnnnn { keyans } { v } { 4.0pt plus 2.0pt minus 1.0pt }
758 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
759 { 2.0pt plus 1.0pt minus 1.0pt }
760 \__enumext_tmp:nnnnnn { enumext* } { vii } { 8.0pt plus 2.0pt minus 4.0pt }
761 { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
762 { 4.0pt plus 2.0pt minus 1.0pt }
763 \__enumext_tmp:nnnnnn { keyans* } { viii } { 4.0pt plus 2.0pt minus 1.0pt }
764 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
765 { 2.0pt plus 1.0pt minus 1.0pt }

```

(End of definition for `topsep` and others.)

### 10.14 Setting keys for horizontal spaces

Define and set `itemindent`, `rightmargin`, `listparindent`, `list-offset` and `list-indent` keys for `enumext` and `keyans` environments.

©2024 by Pablo González L

```

766 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
767 {
768   \keys_define:nn { enumext / #1 }
769   {
770     itemindent .dim_set:c = { l__enumext_fake_item_indent_#2_dim },
771     itemindent .value_required:n = true,
772     rightmargin .dim_set:c = { l__enumext_rightmargin_#2_dim },
773     rightmargin .value_required:n = true,
774     listparindent .dim_set:c = { l__enumext_listparindent_#2_dim },
775     listparindent .value_required:n = true,
776     list-offset .dim_set:c = { l__enumext_listoffset_#2_dim },
777     list-offset .value_required:n = true,
778     list-indent .code:n =
779       \bool_set_true:c { l__enumext_leftmargin_tmp_#2_bool }
780       \dim_set:cn { l__enumext_leftmargin_tmp_#2_dim } {##1},
781     list-indent .value_required:n = true,
782   }
783 }
784 \clist_map_inline:Nn \__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `itemindent` and others.)

For `enumext*` and `keyans*` environments the situation is a bit different, the `list-indent` key behaves like the `list-offset` key.

```

785 \cs_set_protected:Npn \__enumext_tmp:n #1
786 {
787   \keys_define:nn { enumext / #1 } { list-indent .initial:n = 0pt, }
788 }
789 \clist_map_inline:nn { enumext*, keyans* } { \__enumext_tmp:n {##1} }

```

#### 10.14.1 Functions for setting the fake `itemindent`

The `itemindent` key does not set the value of `\itemindent`, it only sets the value of the *horizontal space* applied using `\skip_horizontal:N`. We will store this value in the variable and only apply it when it is greater than `0pt`. Here I will need to place `\mode_leave_vertical:` and the plain  $\TeX$  macro `\ignorespaces` to avoid unwanted extra space when using the `itemindent` key.

```

790 \cs_set_protected:Nn \__enumext_fake_item:
791 {
792   \dim_compare:nNnT
793     { \dim_use:c { l__enumext_fake_item_indent_ \__enumext_level: _dim } }
794     >
795     { \c_zero_dim }
796   {
797     \tl_set:ce { l__enumext_fake_item_indent_ \__enumext_level: _tl }
798     {
799       \exp_not:N \mode_leave_vertical:
800       \exp_not:n { \skip_horizontal:n {
801         { \dim_use:c { l__enumext_fake_item_indent_ \__enumext_level: _dim } }
802         \ignorespaces
803       }
804     }
805   }
806 \cs_set_protected:Nn \__enumext_keyans_fake_item:
807 {
808   \dim_compare:nNnT
809     { \l__enumext_fake_item_indent_v_dim } > { \c_zero_dim }
810     {
811       \tl_set:Nc \l__enumext_fake_item_indent_v_tl
812       {
813         \exp_not:N \mode_leave_vertical:
814         \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_v_dim
815       }
816     }
817 }
818 \cs_set_protected:Nn \__enumext_fake_item_vii:
819 {
820   \dim_compare:nNnT
821     { \l__enumext_fake_item_indent_vii_dim } > { \c_zero_dim }
822     {
823       \tl_set:Nc \l__enumext_fake_item_indent_vii_tl
824       {
825         \exp_not:N \mode_leave_vertical:

```



```

826         \exp_not:N \skip_horizontal:N \__enumext_fake_item_indent_vii_dim
827     }
828 }
829 }
830 \cs_set_protected:Nn \__enumext_fake_item_viii:
831 {
832     \dim_compare:nNnT
833     { \l__enumext_fake_item_indent_viii_dim } > { \c_zero_dim }
834     {
835         \tl_set:Nc \l__enumext_fake_item_indent_viii_tl
836         {
837             \exp_not:N \mode_leave_vertical:
838             \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_viii_dim
839         }
840     }
841 }

```

(End of definition for `\__enumext_fake_item:` and others.)

## 10.15 Setting show-length key

show-length

Define and set `show-length` key for `enumext`, `enumext*`, `keyans` and `keyans*` environments. The function sets the boolean variable `\l__enumext_show_length_X_bool` used in the definition of all environments to “true” and calls the function `\__enumext_show_length:nnn` which prints all the values of the “vertical” and “horizontal” parameters calculated and used.

```

842 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
843 {
844     \keys_define:nn { enumext / #1 }
845     {
846         show-length .bool_set:c = { \l__enumext_show_length_#2_bool },
847         show-length .initial:n = false,
848     }
849 }
850 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `show-length`.)

## 10.16 Setting before, after and first keys

before

Define and set `before`, `before*`, `after` and `first` keys for `enumext` and `keyans` environments.

before\*

after

first

```

851 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
852 {
853     \keys_define:nn { enumext / #1 }
854     {
855         before .tl_set:c = { \l__enumext_before_no_starred_key_#2_tl },
856         before .value_required:n = true,
857         before* .tl_set:c = { \l__enumext_before_starred_key_#2_tl },
858         before* .value_required:n = true,
859         after .tl_set:c = { \l__enumext_after_stop_list_#2_tl },
860         after .value_required:n = true,
861         first .tl_set:c = { \l__enumext_after_list_args_#2_tl },
862         first .value_required:n = true,
863     }
864 }
865 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `before` and others.)

### 10.16.1 Functions for before, after and first keys in enumext

`\__enumext_before_args_exec:`

The function `\__enumext_before_args_exec:` executes the `{⟨code⟩}` set by the `before*` key “before” the `enumext` environment is started. The `{⟨code⟩}` is executed “without” knowing any definition of the *second argument* of the list.

`\__enumext_before_keys_exec:`

`\__enumext_after_stop_list:`

`\__enumext_after_args_exec:`

```

866 \cs_new_protected:Nn \__enumext_before_args_exec:
867 {
868     \tl_use:c { \l__enumext_before_starred_key_ \__enumext_level: _tl }
869 }

```

The function `\__enumext_before_keys_exec:` executes the `{⟨code⟩}` set by the `before` key “before” the `enumext` environment is started in *second argument* of the list. The `{⟨code⟩}` is executed “knowing” all definition and values provides by `⟨keys⟩`.

```

870 \cs_new_protected:Nn \__enumext_before_keys_exec:
871 {

```

```

872     \tl_use:c { l__enumext_before_no_starred_key_ \__enumext_level: _tl }
873 }

```

The function `\__enumext_after_stop_list:` executes the `{⟨code⟩}` set by the `after` key “after” the `enumext` environment has finished.

```

874 \cs_new_protected:Nn \__enumext_after_stop_list:
875 {
876     \tl_use:c { l__enumext_after_stop_list_ \__enumext_level: _tl }
877 }

```

The function `\__enumext_after_args_exec:` executes the `{⟨code⟩}` set by the `first` key after the end of the second argument of the list defining the `enumext` environment, just before the first occurrence of `\item`.

```

878 \cs_new_protected:Nn \__enumext_after_args_exec:
879 {
880     \tl_use:c { l__enumext_after_list_args_ \__enumext_level: _tl }
881 }

```

(End of definition for `\__enumext_before_args_exec:` and others.)

### 10.16.2 Functions for before, after and first keys in keyans

`\__enumext_before_args_exec_v:` The function `\__enumext_before_args_exec_v:` executes the `{⟨code⟩}` set by the `before*` key “before” the `keyans` environment is started. The `{⟨code⟩}` is executed “without” knowing any definition of the `{⟨arg two⟩}` of the list.

```

882 \cs_new_protected:Nn \__enumext_before_args_exec_v:
883 {
884     \tl_use:N \l__enumext_before_starred_key_v_tl
885 }

```

The function `\__enumext_before_keys_exec_v:` executes the `{⟨code⟩}` set by the `before` key “before” the `keyans` environment is started in `{⟨arg two⟩}` of the list. The `{⟨code⟩}` is executed “knowing” all definition and values provides by `⟨keys⟩`.

```

886 \cs_new_protected:Nn \__enumext_before_keys_exec_v:
887 {
888     \tl_use:N \l__enumext_before_no_starred_key_v_tl
889 }

```

The function `\__enumext_after_stop_list_v:` executes the `{⟨code⟩}` set by the `after` key “after” the `keyans` environment has finished.

```

890 \cs_new_protected:Nn \__enumext_after_stop_list_v:
891 {
892     \tl_use:N \l__enumext_after_stop_list_v_tl
893 }

```

The function `\__enumext_after_args_exec_v:` executes the `{⟨code⟩}` set by the `first` key after the end of `{⟨arg two⟩}` of the list defining the `keyans` environment, just before the first occurrence of `\item`.

```

894 \cs_new_protected:Nn \__enumext_after_args_exec_v:
895 {
896     \tl_use:N \l__enumext_after_list_args_v_tl
897 }

```

(End of definition for `\__enumext_before_args_exec_v:` and others.)

### 10.16.3 Functions for before, after and first keys in enumext\* and keyans\*

`\__enumext_before_args_exec_vii:` The function `\__enumext_before_args_exec_v:` executes the `{⟨code⟩}` set by the `before*` key “before” the `keyans` environment is started. The `{⟨code⟩}` is executed “without” knowing any definition of the `{⟨arg two⟩}` of the list.

```

898 \cs_new_protected:Nn \__enumext_before_args_exec_vii:
899 {
900     \tl_use:N \l__enumext_before_starred_key_vii_tl
901 }
902 \cs_new_protected:Nn \__enumext_before_args_exec_viii:
903 {
904     \tl_use:N \l__enumext_before_starred_key_viii_tl
905 }

```

The functions `\__enumext_before_keys_exec_vii:` and `\__enumext_before_keys_exec_viii:` executes the `{⟨code⟩}` set by the `before` key “before” in `enumext*` and `keyans*` environments is started in `{⟨arg two⟩}` of the list. The `{⟨code⟩}` is executed “knowing” all definition and values provides by `⟨keys⟩`.

```

906 \cs_new_protected:Nn \__enumext_before_keys_exec_vii:
907 {
908     \tl_use:N \l__enumext_before_no_starred_key_vii_tl

```

```

909 }
910 \cs_new_protected:Nn \__enumext_before_keys_exec_viii:
911 {
912   \tl_use:N \l__enumext_before_no_starred_key_viii_tl
913 }

```

The function `\__enumext_after_stop_list:` executes the `{\code}` set by the `after` key “*after*” the `keyans` environment has finished.

```

914 \cs_new_protected:Nn \__enumext_after_stop_list_vii:
915 {
916   \tl_use:N \l__enumext_after_stop_list_vii_tl
917 }
918 \cs_new_protected:Nn \__enumext_after_stop_list_viii:
919 {
920   \tl_use:N \l__enumext_after_stop_list_viii_tl
921 }

```

The function `\__enumext_after_args_exec_v:` executes the `{\code}` set by the `first` key after the end of `{\arg two}` of the list defining the `keyans` environment, just before the first occurrence of `\item`.

```

922 \cs_new_protected:Nn \__enumext_after_args_exec_vii:
923 {
924   \tl_use:N \l__enumext_after_list_args_vii_tl
925 }
926 \cs_new_protected:Nn \__enumext_after_args_exec_viii:
927 {
928   \tl_use:N \l__enumext_after_list_args_viii_tl
929 }

```

(End of definition for `\__enumext_before_args_exec_vii:` and others.)

## 10.17 Setting keys for multicols and minipage

`mini-env` The default value of the `columns-sep` key is handled by the state of the boolean variable `\l__enumext_columns_sep_X_bool` which is handled in the internal definition of the `enumext` and `keyans` environments.

`mini-sep` Define and set `mini-env`, `mini-sep`, `columns-sep` and `columns` keys for `enumext` and `keyans` environments.

`columns-sep`

`columns`

```

930 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
931 {
932   \keys_define:nn { enumext / #1 }
933   {
934     mini-env .dim_set:c = { l__enumext_minipage_right_#2_dim },
935     mini-env .value_required:n = true,
936     mini-sep .dim_set:c = { l__enumext_minipage_hsep_#2_dim },
937     mini-sep .initial:n = 0.3333em,
938     mini-sep .value_required:n = true,
939     columns-sep .dim_set:c = { l__enumext_columns_sep_#2_dim },
940     columns-sep .value_required:n = true,
941     columns .int_set:c = { l__enumext_columns_#2_int },
942     columns .initial:n = 1,
943     columns .value_required:n = true,
944   }
945 }
946 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

For `enumext*` and `keyans*` environments the situation is a bit different, the default value for `columns` key are `2` and the command `\miniright` is not available, so we will add the keys `miniright` and `miniright*` to implement support for `minipage`.

```

947 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
948 {
949   \keys_define:nn { enumext / #1 }
950   {
951     columns .initial:n = 2,
952     miniright .tl_gset:c = { g__enumext_miniright_code_#2_tl },
953     miniright .value_required:n = true,
954     miniright* .code:n = {
955       \bool_gset_true:c { g__enumext_minipage_center_#2_bool }
956       \keys_set:nn { enumext / #1 } { miniright = {##1} }
957     },
958     miniright* .value_required:n = true,
959   }
960 }
961 \clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }

```

(End of definition for `mini-env` and others.)

## 10.18 Adjustment of vertical spaces for multicol

When nesting a “list environment” inside the `multicol` environment, the values of the “vertical spaces” are lost, basically the `multicol` environment takes control over them. Graphically it can be seen like in the figure 7.




Figure 7: Representation of the vertical space in `multicol` for a nested level.

To keep the desired spaces *above* and *below* in the “list environment” (`\topsep` + `[\partopsep]`) it is necessary to “adjust” the spaces added by the `multicol` environment. The most appropriate option in this case is to use a “context sensitive” vertical space with `\addvspace`.

I should make it clear that the implementation here is a “bit questionable”. At first glance doing `\multicolsep=\topsep` seemed right, but the results were not always as expected. An almost *imperceptible* detail is that in some cases the `\itemsep` values of are “stretched”, possibly due to the use of `\raggedcolumns` and this affects the lower space when closing the environment, which is “smaller” than expected. My attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

### 10.18.1 Adjustment of vertical spaces for multicol in enumext

`\__enumext_multi_set_vskip:`

The function `\__enumext_multi_set_vskip:` will take care of determining the “adjusted spaces” that we will apply “above” and “below” the `multicol` environment in `enumext`.

We will set the default values taking into account that  $\TeX$  is in (*horizontal mode*), then we will make the settings for the (*vertical mode*) in which `\partopsep` comes into play.

Set the values of `\l__enumext_multicol_above_X_skip` and `\l__enumext_multicol_below_X_skip` equal to the value of `\topsep` in the *current level*.

```

962 \cs_new_protected:Nn \__enumext_multi_set_vskip:
963 {
964   \skip_set:cn { \l__enumext_multicol_above_ \__enumext_level: } _skip {
965     {
966       \skip_use:c { \l__enumext_topsep_ \__enumext_level: } _skip {
967       }
968     }
969   \skip_set:cn { \l__enumext_multicol_below_ \__enumext_level: } _skip {
970     {
971       \skip_use:c { \l__enumext_topsep_ \__enumext_level: } _skip {
972       }
973   }
974   \__enumext_add_pre_parsep:
975 }

```

(End of definition for `\__enumext_multi_set_vskip:`)

`\__enumext_add_pre_parsep:`

The function `\__enumext_add_pre_parsep:` “adjusted” the value of `\l__enumext_multicol_above_X_skip` detecting the value of `\parsep` from the previous level. This is necessary since `\parsep` from the previous level affects the *vertical spaces*.

```

974 \cs_new_protected:Nn \__enumext_add_pre_parsep:
975 {
976   \int_case:nn { \l__enumext_level_int }
977   {
978     { 2 }{
979       \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip } {
980         {
981           \skip_add:Nn \l__enumext_multicol_above_ii_skip { \l__enumext_parsep_i_skip }
982         }
983       }
984     { 3 }{
985       \skip_if_eq:nnF { \l__enumext_parsep_ii_skip } { \c_zero_skip } {
986         {
987           \skip_add:Nn \l__enumext_multicol_above_iii_skip { \l__enumext_parsep_ii_skip }
988         }
989       }
990     { 4 }{
991       \skip_if_eq:nnF { \l__enumext_parsep_iii_skip } { \c_zero_skip } {
992         {
993           \skip_add:Nn \l__enumext_multicol_above_iv_skip { \l__enumext_parsep_iii_skip }

```

```

994         }
995     }
996 }
997 }

```

(End of definition for `\__enumext_add_pre_parsep:`)

`\__enumext_multi_addvspace:` The function `\__enumext_multi_addvspace:` will apply the spaces set using `\addvspace` “above” the `multicols` environment in `enumext`, taking into account whether  $\text{\TeX}$  is in *(horizontal mode)* or *(vertical mode)*.

```

998 \cs_new_protected:Nn \__enumext_multi_addvspace:
999 {
1000     \__enumext_multi_set_vskip:
1001     \mode_if_vertical:T
1002     {
1003         \skip_add:cn { l__enumext_multicols_above_ \__enumext_level: _skip }
1004         {
1005             \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
1006         }
1007         \skip_add:cn { l__enumext_multicols_below_ \__enumext_level: _skip }
1008         {
1009             \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
1010         }
1011     }
1012     \par\nopagebreak
1013     \addvspace{ \skip_use:c { l__enumext_multicols_above_ \__enumext_level: _skip } }
1014 }

```

(End of definition for `\__enumext_multi_addvspace:`)

### 10.18.2 Adjustment of vertical spaces for multicols in keyans

`\__enumext_keyans_multi_set_vskip:` The function `\__enumext_keyans_multi_set_vskip:` will take care of determining the “adjusted spaces” that we will apply “above” and “below” the `multicols` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

`\__enumext_keyans_multi_addvspace:`

```

1015 \cs_new_protected:Nn \__enumext_keyans_multi_set_vskip:
1016 {
1017     \skip_set:Nn \l__enumext_multicols_above_v_skip
1018     {
1019         \l__enumext_topsep_v_skip
1020     }
1021     \skip_set:Nn \l__enumext_multicols_below_v_skip
1022     {
1023         \l__enumext_topsep_v_skip
1024     }
1025 }
1026 \cs_new_protected:Nn \__enumext_keyans_multi_addvspace:
1027 {
1028     \__enumext_keyans_multi_set_vskip:
1029     \mode_if_vertical:T
1030     {
1031         \skip_add:Nn \l__enumext_multicols_above_v_skip
1032         {
1033             \skip_use:N \l__enumext_partopsep_v_skip
1034         }
1035         \skip_add:Nn \l__enumext_multicols_below_v_skip
1036         {
1037             \skip_use:N \l__enumext_partopsep_v_skip
1038         }
1039     }
1040     \par\nopagebreak
1041     \addvspace{ \l__enumext_multicols_above_v_skip }
1042 }


```

(End of definition for `\__enumext_keyans_multi_set_vskip:` and `\__enumext_keyans_multi_addvspace:`)

### 10.19 Adjustment of vertical spaces for minipage

When nesting a “list environment” within the `minipage` environment, the values of the “vertical spaces” are lost. Graphically it can be seen like in the figure 8.

Since we want to keep the “left” and “right” environments “aligned on top”, preserving the `\baselineskip` and keep the desired “spaces” (`\topsep` + `[\partopsep]`) it is necessary to “adjust” the “vertical spaces” for `minipage` environments.

Figure 8: Representation of the `minipage` spacing adjustment for a nested level.

Here there are several complications that we must circumvent, the `minipage` environment eliminates the “top” spaces, the `multicols` environment can be nested in the `minipage` environment, the “top” and “bottom” spaces are affected when `topsep=0pt` and to this is added the `\partopsep` parameter that comes into action according to whether  $\TeX$  is in *(horizontal mode)* or *(vertical mode)*. Depending on these cases, small adjustments must be made using `\vspace` and `\addvspace` to obtain the “desired vertical spacing”.

Again I must make clear that the implementation here is a “bit questionable”, but hunting the spaces (glue) produced by the `minipage` environment is quite complicated, even more if `multicols` it is nested. The setting of the values was more “trial and error” (aprox to `\strutbox`), using the help of the `lua-visual-debug`[12] package, again my attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

`__enumext_mini_env*` Creates a `__enumext_mini_env*` environment (custom version of `minipage`) setting the `\if@minipage` switch to “false” to allow spaces at the “above” of the environment, plus we will add `\vspace{0pt}` to maintain alignment on “top”. This environment will be used internally by the `mini-env` key, it is not documented in the user interface and is for internal use only.

```

1043 \DeclareDocumentEnvironment{__enumext_mini_env*}{ m }
1044 {
1045     \__enumext_minipage:w [ t ] { #1 }
1046     \legacy_if_gset_false:n { @minipage }
1047     \vspace { 0pt }
1048 }
1049 { \__enumext_endminipage: }
```

(End of definition for `__enumext_mini_env*`.)

#### 10.19.1 Adjustment of vertical spaces for minipage in enumext

`__enumext_mini_set_vskip:` The function `\__enumext_mini_set_vskip:` will take care of determining the “adjust” spaces that we will apply “above” and “below” the `__enumext_mini_env*` environment in `enumext`.

We will set the default values taking into account that  $\TeX$  is in *(horizontal mode)*, then we will make the settings for the *(vertical mode)* in which `\partopsep` comes into play.

First determine if the `multicols` environment is active by comparing the value of the `\l__enumext_columns_X_int` variable handled by the `columns` key, according to this comparison we set the adjusted values for `\l__enumext_minipage_left_skip`, `\l__enumext_minipage_right_skip` and `\l__enumext_minipage_after_skip`.

```

1050 \cs_new_protected:Nn \__enumext_mini_set_vskip:
1051 {
1052     \int_compare:nNnTF
1053     { \int_use:c { \l__enumext_columns_ \__enumext_level: _int } } > { 1 }
1054     {
```

If `multicols` environment is nested in `__enumext_mini_env*` environment, we will apply a correction factor to the vertical spaces taking into account the value of `\topsep` of the current level and the value of `\partopsep` of the previous level, if these are zero we will use `\strutbox` as the basis for the calculations.

```

1055     \skip_if_eq:nnTF
1056     { \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip } } { \c_zero_skip }
1057     {
1058         \skip_set:Nn \l__enumext_minipage_left_skip
1059         {
1060             -0.150\box_dp:N \strutbox
1061         }
1062         \skip_set:Nn \l__enumext_minipage_right_skip
1063         {
1064             0.695\box_dp:N \strutbox
1065         }
1066         \skip_set:Nn \l__enumext_minipage_after_skip
1067         {
1068             \box_dp:N \strutbox
1069         }
1070         \__enumext_zero_parsep:
1071     }
```

```

1072     {
1073       \skip_set:Nn \l__enumext_minipage_left_skip
1074       {
1075         \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
1076       }
1077       \skip_set:Nn \l__enumext_minipage_right_skip
1078       {
1079         0.695\box_dp:N \strutbox
1080       }
1081       \skip_set:Nn \l__enumext_minipage_after_skip
1082       {
1083         1.85\box_dp:N \strutbox
1084         + \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
1085       }
1086     }
1087   }
1088   {

```

If only `enumext` environment is nested in `__enumext_mini_env*` environment, we will apply a correction factor to the *vertical spaces* taking into account the value of `\topsep`, if this is zero we will use `\strutbox` as the basis for the calculations.

```

1089   \skip_if_eq:nnTF
1090   { \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip } } { \c_zero_skip }
1091   {
1092     \skip_set:Nn \l__enumext_minipage_left_skip
1093     {
1094       0.5\box_dp:N \strutbox
1095       - \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
1096     }
1097     \skip_set:Nn \l__enumext_minipage_right_skip
1098     {
1099       \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
1100     }
1101     \skip_set:Nn \l__enumext_minipage_after_skip
1102     {
1103       1.6\box_dp:N \strutbox
1104     }
1105   }
1106   {
1107     \skip_set:Nn \l__enumext_minipage_left_skip
1108     {
1109       0.5875\box_dp:N \strutbox
1110       - \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
1111     }
1112     \skip_set:Nn \l__enumext_minipage_right_skip
1113     {
1114       + \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
1115       + \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
1116     }
1117     \skip_set:Nn \l__enumext_minipage_after_skip
1118     {
1119       0.325\box_dp:N \strutbox
1120       + \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
1121     }
1122   }
1123 }
1124 }

```

(End of definition for `__enumext_mini_set_vskip:`)

`__enumext_zero_parsep:` The function `__enumext_zero_parsep:` “adjusted” the value of `\l__enumext_minipage_after_skip` detecting the value of `\parsep` from the previous level. This is necessary since `\parsep` from the previous level affects the *vertical spaces* and this is noticeable when using the `nosep` or `noitemsep` keys.

```

1125 \cs_new_protected:Nn \__enumext_zero_parsep:
1126 {
1127   \int_case:nn { \l__enumext_level_int }
1128   {
1129     { 2 }{
1130       \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip }
1131       {
1132         \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }

```



```

1133         }
1134     }
1135     { 3 }{
1136         \skip_if_eq:nnF { \l__enumext_parsep_ii_skip } { \c_zero_skip }
1137         {
1138             \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
1139         }
1140     }
1141     { 4 }{
1142         \skip_if_eq:nnF { \l__enumext_parsep_iii_skip } { \c_zero_skip }
1143         {
1144             \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
1145         }
1146     }
1147 }
1148 }

```

(End of definition for `\__enumext_zero_parsep:`.)

`\__enumext_mini_addvspace:` The function `\__enumext_mini_addvspace:` will apply the spaces set using `\addvspace` “above” the `\__enumext_mini_env*` environment in `enumext`, taking into account whether  $\text{\TeX}$  is in *horizontal mode* or *vertical mode*. For the latter we will make some adjustments since the `\partopsep` parameter comes into play and this affects the *vertical spacing*.

```

1149 \cs_new_protected:Nn \__enumext_mini_addvspace:
1150 {
1151     \__enumext_mini_set_vskip:
1152     \mode_if_vertical:T
1153     {
1154         \skip_add:Nn \l__enumext_minipage_left_skip
1155         {
1156             \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1157         }
1158         \skip_add:Nn \l__enumext_minipage_after_skip
1159         {
1160             \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1161         }
1162     }
1163     \par\nopagebreak
1164     \addvspace { \l__enumext_minipage_left_skip }
1165 }

```

(End of definition for `\__enumext_mini_addvspace:`.)

### 10.19.2 Adjustment of vertical spaces for minipage in keyans

`\__enumext_keyans_mini_set_vskip:` The function `\__enumext_keyans_mini_set_vskip:` will take care of determining the “adjusted” spaces that we will apply “above” and “below” the `\__enumext_mini_env*` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

```

1166 \cs_new_protected:Nn \__enumext_keyans_mini_set_vskip:
1167 {
1168     \skip_zero_new:N \l__enumext_minipage_after_skip
1169     \skip_zero_new:N \l__enumext_minipage_left_skip
1170     \skip_zero_new:N \l__enumext_minipage_right_skip
1171     \int_compare:nNnTF { \l__enumext_columns_v_int } > { 1 }
1172     {
1173         \skip_if_eq:nnTF { \l__enumext_topsep_v_skip } { \c_zero_skip }
1174         {
1175             \skip_set:Nn \l__enumext_minipage_left_skip { -0.25\box_dp:N \strutbox }
1176             \skip_set:Nn \l__enumext_minipage_right_skip { 0.705\box_dp:N \strutbox }
1177             \skip_set:Nn \l__enumext_minipage_after_skip { \box_dp:N \strutbox }
1178             \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip }
1179             {
1180                 \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
1181             }
1182         }
1183     }
1184     \skip_set:Nn \l__enumext_minipage_left_skip
1185     {
1186         \skip_use:N \l__enumext_topsep_v_skip
1187     }
1188     \skip_set:Nn \l__enumext_minipage_right_skip

```

```

1189         {
1190             0.705\box_dp:N \strutbox
1191         }
1192         \skip_set:Nn \l__enumext_minipage_after_skip
1193         {
1194             1.85\box_dp:N \strutbox + \l__enumext_topsep_v_skip
1195         }
1196     }
1197 }
1198 {
1199     \skip_if_eq:nnTF { \l__enumext_topsep_v_skip } { \c_zero_skip }
1200     {
1201         \skip_set:Nn \l__enumext_minipage_left_skip
1202         {
1203             0.5\box_dp:N \strutbox
1204             + \l__enumext_partopsep_v_skip
1205         }
1206         \skip_set:Nn \l__enumext_minipage_right_skip
1207         {
1208             \l__enumext_partopsep_v_skip
1209         }
1210         \skip_set:Nn \l__enumext_minipage_after_skip { 1.6\box_dp:N \strutbox }
1211     }
1212     {
1213         \skip_set:Nn \l__enumext_minipage_left_skip
1214         {
1215             0.5875\box_dp:N \strutbox - \l__enumext_partopsep_v_skip
1216         }
1217         \skip_set:Nn \l__enumext_minipage_right_skip
1218         {
1219             \l__enumext_topsep_v_skip + \l__enumext_partopsep_v_skip
1220         }
1221         \skip_set:Nn \l__enumext_minipage_after_skip
1222         {
1223             0.325\box_dp:N \strutbox + \l__enumext_topsep_v_skip
1224         }
1225     }
1226 }
1227 }

```

(End of definition for `\l__enumext_keyans_mini_set_vskip:`)

`\l__enumext_keyans_mini_addvspace:`

The function `\l__enumext_keyans_mini_addvspace:` will apply the spaces set using `\addvspace` “above” the `\l__enumext_mini_env*` environment in `keyans`, taking into account whether  $\text{\TeX}$  is in *horizontal mode* or *vertical mode*. For the latter we will make some adjustments since the `\partopsep` parameter comes into play and this affects the *vertical spacing*. The implementation of this function is the same as the one used in `enumext`.

```

1228 \cs_new_protected:Nn \l__enumext_keyans_mini_addvspace:
1229 {
1230     \l__enumext_keyans_mini_set_vskip:
1231     \mode_if_vertical:T
1232     {
1233         \skip_add:Nn \l__enumext_minipage_left_skip
1234         {
1235             \l__enumext_partopsep_v_skip
1236         }
1237         \skip_add:Nn \l__enumext_minipage_after_skip
1238         {
1239             \l__enumext_partopsep_v_skip
1240         }
1241     }
1242     \par\nopagebreak
1243     \addvspace { \l__enumext_minipage_left_skip }
1244 }

```

(End of definition for `\l__enumext_keyans_mini_addvspace:`)

### 10.19.3 Adjustment of vertical spaces for minipage in `enumext*` and `keyans*`

`\l__enumext_mini_set_vskip_vii:`

`\l__enumext_mini_set_vskip_viii:`

The functions `\l__enumext_mini_set_vskip_vii:` and `\l__enumext_mini_set_vskip_viii:` will take care of determining the “adjusted” spaces that we will apply “above” and “below” the `\l__enumext_mini_env*` environment in `enumext*` and `keyans*`.

```

1245 \cs_new_protected:Nn \__enumext_mini_set_vskip_vii:
1246 {
1247   \skip_zero_new:N \l__enumext_minipage_left_skip
1248   \skip_gzero_new:N \g__enumext_minipage_right_skip
1249   \skip_gzero_new:N \g__enumext_minipage_after_skip
1250   \skip_if_eq:nnTF { \l__enumext_topsep_vii_skip } { \c_zero_skip }
1251   {
1252     \skip_set:Nn \l__enumext_minipage_left_skip { 0.5\box_dp:N \strutbox }
1253     \skip_gset:Nn \g__enumext_minipage_right_skip { 0.325\box_dp:N \strutbox }
1254   }
1255   {
1256     \skip_set:Nn \l__enumext_minipage_left_skip { 0.5875\box_dp:N \strutbox }
1257     \skip_gset:Nn \g__enumext_minipage_right_skip
1258       {
1259         \l__enumext_topsep_vii_skip
1260       }
1261     \skip_gset:Nn \g__enumext_minipage_after_skip
1262       {
1263         0.325\box_dp:N \strutbox + \l__enumext_topsep_vii_skip
1264       }
1265   }
1266 }
1267 \cs_new_protected:Nn \__enumext_mini_set_vskip_viii:
1268 {
1269   \skip_zero_new:N \l__enumext_minipage_after_skip
1270   \skip_zero_new:N \l__enumext_minipage_left_skip
1271   \skip_zero_new:N \l__enumext_minipage_right_skip
1272   \skip_if_eq:nnTF { \l__enumext_topsep_viii_skip } { \c_zero_skip }
1273   {
1274     \skip_set:Nn \l__enumext_minipage_left_skip
1275       {
1276         0.5\box_dp:N \strutbox
1277       }
1278     \skip_set:Nn \l__enumext_minipage_right_skip
1279       {
1280         \l__enumext_partopsep_viii_skip
1281       }
1282     \skip_set:Nn \l__enumext_minipage_after_skip
1283       {
1284         1.6\box_dp:N \strutbox
1285       }
1286   }
1287   {
1288     \skip_set:Nn \l__enumext_minipage_left_skip
1289       {
1290         0.5875\box_dp:N \strutbox
1291       }
1292     \skip_set:Nn \l__enumext_minipage_right_skip
1293       {
1294         \l__enumext_topsep_viii_skip
1295       }
1296     \skip_set:Nn \l__enumext_minipage_after_skip
1297       {
1298         0.325\box_dp:N \strutbox + \l__enumext_topsep_viii_skip
1299       }
1300   }
1301 }

```

(End of definition for `\__enumext_mini_set_vskip_vii:` and `\__enumext_mini_set_vskip_viii:`.)

`\__enumext_mini_addvspace_vii:`  
`\__enumext_mini_addvspace_viii:`

The functions `\__enumext_mini_addvspace_vii:` and `\__enumext_mini_addvspace_viii:` will apply the vertical space “only above” the `\__enumext_mini_env*` environment on the *left side* when the `miniright` key is active in the `enumext*` and `keyans*` environments. Here we will NOT take into account whether T<sub>E</sub>X is in *horizontal mode* or *vertical mode*, since `\partopsep` is equal to `0pt` in both environments.

```

1302 \cs_new_protected:Nn \__enumext_mini_addvspace_vii:
1303 {
1304   \__enumext_mini_set_vskip_vii:
1305   \par\nopagebreak
1306   \addvspace { \l__enumext_minipage_left_skip }
1307 }

```

```

1308 \cs_new_protected:Nn \__enumext_mini_addvspace_viii:
1309 {
1310     \__enumext_mini_set_vskip_viii:
1311     \par\nopagebreak
1312     \addvspace { \l__enumext_minipage_left_skip }
1313 }

```

(End of definition for \\_\_enumext\_mini\_addvspace\_vii: and \\_\_enumext\_mini\_addvspace\_viii:.)

#### 10.19.4 The command \miniright

The command `\miniright` will close the `__enumext_mini_env*` environment on the “left side”, open the `__enumext_mini_env*` environment on the “right side” adding the *adjusted vertical space*. By default we will add `\centering` when starting the “right side” environment. The *starred version* ‘\*’ inhibits the use of `\centering` command i.e. the usual L<sup>A</sup>T<sub>E</sub>X justification is maintained in the `__enumext_mini_env*` on the “right side”.

`\miniright` First we will perform some checks to prevent the command from being executed outside the `enumext` environment or from being executed inside the `keyanspic` environment, then we call the internal functions for the `enumext` and `keyans` environments.

```

1314 \NewDocumentCommand \miniright { s }
1315 {
1316     \int_compare:nNnT { \l__enumext_keyans_pic_level_int } = { 1 }
1317     {
1318         \msg_error:nnn { enumext } { wrong-miniright-place }
1319     }
1320     \int_compare:nNnT { \l__enumext_level_int } = { 0 }
1321     {
1322         \msg_error:nnn { enumext } { wrong-miniright-place }
1323     }
1324     \int_compare:nNnTF { \l__enumext_keyans_level_int } = { 1 }
1325     {
1326         \__enumext_keyans_mini_right_cmd:n {#1}
1327     }
1328     { \__enumext_mini_right_cmd:n {#1} }
1329 }

```

(End of definition for \miniright. This function is documented on page 9.)

`\__enumext_mini_right_cmd:n` The function `\__enumext_mini_right_cmd:n` takes as argument the *starred version* ‘\*’ of the `\miniright` command in the `enumext` environment. We check if the `mini-env` key is active via the variable `\l__enumext_minipage_right_X_dim`, if so we close the `multicols` environment with the `__enumext__mini_env*` environment on the “left side”, then we open the `__enumext_mini_env*` environment on the “right side”, apply our adjusted “vertical spaces”, followed by adding the `\centering` command when the starred argument ‘\*’ is not present and set zero `\g__enumext_minipage_stat_int`, otherwise we return an error.

```

1330 \cs_new_protected:Npn \__enumext_mini_right_cmd:n #1
1331 {
1332     \dim_compare:nNnTF
1333     { \dim_use:c { \l__enumext_minipage_right_ \__enumext_level: _dim } } > { \c_zero_dim }
1334     {
1335         \__enumext_multicols_stop:
1336         \end{__enumext_mini_env*}
1337         \hfill
1338         \begin{__enumext_mini_env*}
1339         { \dim_use:c { \l__enumext_minipage_right_ \__enumext_level: _dim } }
1340         \par\addvspace { \l__enumext_minipage_right_skip }
1341         \bool_if:nF {#1}
1342         {
1343             \centering
1344         }
1345         \int_gzero:N \g__enumext_minipage_stat_int
1346     }
1347     { \msg_error:nnn { enumext } { wrong-miniright-use } }
1348 }

```

(End of definition for \\_\_enumext\_mini\_right\_cmd:n.)

\\\_enumext\_keyans\_mini\_right\_cmd:n

The function \\\_enumext\_keyans\_mini\_right\_cmd:n takes as argument the *starred version* ‘\*’ of the `\\mini\\right` command in the `keyans` environment. The implementation of this function is the same as that of the \\\_enumext\_mini\_right\_cmd:n function of the `enumext` environment.

```

1349 \\cs_new_protected:Npn \\_enumext_keyans_mini_right_cmd:n #1
1350 {
1351   \\dim_compare:nNnTF { \\_enumext_minipage_right_v_dim } > { \\c_zero_dim }
1352   {
1353     \\_enumext_keyans_multicols_stop:
1354     \\end{\\_enumext_mini_env*}
1355     \\hfill
1356     \\begin{\\_enumext_mini_env*}{ \\_enumext_minipage_right_v_dim }
1357     \\par\\addvspace { \\_enumext_minipage_right_skip }
1358     \\bool_if:nF {#1}
1359     {
1360       \\centering
1361     }
1362     \\int_gzero:N \\g__enumext_minipage_stat_int
1363   }
1364   { \\msg_error:nnn { enumext } { wrong-miniright-use } }
1365 }

```

(End of definition for \\\_enumext\_keyans\_mini\_right\_cmd:n.)

## 10.20 Setting above and below keys

While having controlled the *vertical spaces* within the `enumext` and `keyans` environments when using the `columns` or `mini-env` keys, sometimes the “*vertical spaces above*” or “*vertical spaces below*” the environments are not as expected and it is necessary to be able to apply a “*fine correction*” to these. As I have not been able to correct these *glitches*, the best option is to leave a couple of *keys* dedicated to this purpose, in this case it is best to use `\\vspace` or `\\vspace*` when convenient.

above Define above, above\*, below and below\* keys for `enumext` and `keyans` environments.

```

above* 1366 \\cs_set_protected:Npn \\_enumext_tmp:nn #1 #2
below 1367 {
below* 1368   \\keys_define:nn { enumext / #1 }
1369   {
1370     above .skip_set:c = { \\_enumext_vspace_above_#2_skip },
1371     above .value_required:n = true,
1372     above* .code:n = \\bool_set_true:c { \\_enumext_vspace_a_star_#2_bool }
1373               \\keys_set:nn { enumext / #1 } { above = {##1} },
1374     above* .value_required:n = true,
1375     below .skip_set:c = { \\_enumext_vspace_below_#2_skip },
1376     below .value_required:n = true,
1377     below* .code:n = \\bool_set_true:c { \\_enumext_vspace_b_star_#2_bool }
1378               \\keys_set:nn { enumext / #1 } { below = {##1} },
1379     below* .value_required:n = true,
1380   }
1381 }
1382 \\clist_map_inline:Nn \\c__enumext_all_envs_clist { \\_enumext_tmp:nn #1 }

```

(End of definition for above and others.)

### 10.20.1 Functions for above and below keys in enumext

\\\_enumext\_vspace\_above:

The function \\\_enumext\_vspace\_above: apply the *vertical space above* the `enumext` environment set by the `above*` and `above` keys.

```

1383 \\cs_new_protected:Nn \\_enumext_vspace_above:
1384 {
1385   \\skip_if_eq:nnF
1386   { \\skip_use:c { \\_enumext_vspace_above_ \\_enumext_level: _skip } } { \\c_zero_skip }
1387   {
1388     \\bool_if:cTF { \\_enumext_vspace_a_star_ \\_enumext_level: _bool }
1389     {
1390       \\vspace*{ \\skip_use:c { \\_enumext_vspace_above_ \\_enumext_level: _skip } }
1391     }
1392     {
1393       \\vspace { \\skip_use:c { \\_enumext_vspace_above_ \\_enumext_level: _skip } }
1394     }
1395   }
1396 }

```

(End of definition for \\\_enumext\_vspace\_above:.)

`\__enumext_vspace_below`: The function `\__enumext_vspace_below`: apply the *vertical space below* the `enumext` environment set by the `below*` and `below` keys.

```

1397 \cs_new_protected:Nn \__enumext_vspace_below:
1398 {
1399   \skip_if_eq:nnF
1400   { \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } } { \c_zero_skip }
1401   {
1402     \bool_if:cTF { \__enumext_vspace_b_star_ \__enumext_level: _bool }
1403     {
1404       \vspace*{ \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } }
1405     }
1406     {
1407       \vspace { \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } }
1408     }
1409   }
1410 }

```

(End of definition for `\__enumext_vspace_below`.)

### 10.20.2 Functions for above and below keys in keyans

`\__enumext_vspace_above_v`: The function `\__enumext_vspace_above_v`: apply the *vertical space above* the `keyans` environment set by the `above` and `above*` keys.

```

1411 \cs_new_protected:Nn \__enumext_vspace_above_v:
1412 {
1413   \skip_if_eq:nnF { \l__enumext_vspace_above_v_skip } { \c_zero_skip }
1414   {
1415     \bool_if:NTF \l__enumext_vspace_a_star_v_bool
1416     {
1417       \vspace*{ \l__enumext_vspace_above_v_skip }
1418     }
1419     { \vspace { \l__enumext_vspace_above_v_skip } }
1420   }
1421 }

```

(End of definition for `\__enumext_vspace_above_v`.)

`\__enumext_vspace_below_v`: The function `\__enumext_vspace_below_v`: apply the *vertical space below* the `keyans` environment set by the `below*` and `below` keys.

```

1422 \cs_new_protected:Nn \__enumext_vspace_below_v:
1423 {
1424   \skip_if_eq:nnF { \l__enumext_vspace_below_v_skip } { \c_zero_skip }
1425   {
1426     \bool_if:NTF \l__enumext_vspace_b_star_v_bool
1427     {
1428       \vspace*{ \l__enumext_vspace_below_v_skip }
1429     }
1430     { \vspace { \l__enumext_vspace_below_v_skip } }
1431   }
1432 }

```

(End of definition for `\__enumext_vspace_below_v`.)

### 10.20.3 Functions for above and below keys in enumext\* keyans\*

`\__enumext_vspace_above_vii`: The functions `\__enumext_vspace_above_vii`: and `\__enumext_vspace_above_viii`: apply the *vertical space above* the `enumext*` and `keyans*` environments set by the `above` and `above*` keys.

`\__enumext_vspace_above_viii`:

```

1433 \cs_new_protected:Nn \__enumext_vspace_above_vii:
1434 {
1435   \skip_if_eq:nnF { \l__enumext_vspace_above_vii_skip } { \c_zero_skip }
1436   {
1437     \bool_if:NTF \l__enumext_vspace_a_star_vii_bool
1438     {
1439       \vspace*{ \l__enumext_vspace_above_vii_skip }
1440     }
1441     { \vspace { \l__enumext_vspace_above_vii_skip } }
1442   }
1443 }
1444 \cs_new_protected:Nn \__enumext_vspace_above_viii:
1445 {
1446   \skip_if_eq:nnF { \l__enumext_vspace_above_viii_skip } { \c_zero_skip }
1447   {

```

```

1448         \bool_if:NTF \l__enumext_vspace_a_star_viii_bool
1449         {
1450             \vspace*{ \l__enumext_vspace_above_viii_skip }
1451         }
1452         { \vspace { \l__enumext_vspace_above_viii_skip } }
1453     }
1454 }

```

(End of definition for `\__enumext_vspace_above_vii:` and `\__enumext_vspace_above_viii:`)

`\__enumext_vspace_below_vii:` The functions `\__enumext_vspace_below_vii:` and `\__enumext_vspace_below_viii:` apply the *vertical space below* the `enumext*` and `keyans*` environments set by the `below*` and `below` keys.

```

1455 \cs_new_protected:Nn \__enumext_vspace_below_vii:
1456 {
1457     \skip_if_eq:nnF { \l__enumext_vspace_below_vii_skip } { \c_zero_skip }
1458     {
1459         \bool_if:NTF \l__enumext_vspace_b_star_vii_bool
1460         {
1461             \vspace*{ \l__enumext_vspace_below_vii_skip }
1462         }
1463         { \vspace { \l__enumext_vspace_below_vii_skip } }
1464     }
1465 }
1466 \cs_new_protected:Nn \__enumext_vspace_below_viii:
1467 {
1468     \skip_if_eq:nnF { \l__enumext_vspace_below_viii_skip } { \c_zero_skip }
1469     {
1470         \bool_if:NTF \l__enumext_vspace_b_star_viii_bool
1471         {
1472             \vspace*{ \l__enumext_vspace_below_viii_skip }
1473         }
1474         { \vspace { \l__enumext_vspace_below_viii_skip } }
1475     }
1476 }

```

(End of definition for `\__enumext_vspace_below_vii:` and `\__enumext_vspace_below_viii:`)

## 10.21 Setting series, resume and resume\* keys

The `series` key is responsible for the whole process of the `resume` and `resume*` keys. The idea behind this is to be able to absorb the *⟨keys⟩* passed to the optional argument of the “*first level*” of the environments `enumext` and `enumext*`, but, discarding some specific *⟨keys⟩*.

`series` We define the keys `series`, `resume` and `resume*` only for the “*first level*” of `enumext` and `enumext*`.

```

1477 \cs_set_protected:Npn \__enumext_tmp:n #1
1478 {
1479     \keys_define:nn { enumext / #1 }
1480     {
1481         series .str_set:N = \l__enumext_series_str,
1482         series .value_required:n = true,
1483         resume .code:n = \__enumext_resume_series:n {##1},
1484         resume* .code:n = \__enumext_resume_starred:,
1485         resume* .value_forbidden:n = true,
1486     }
1487 }
1488 \clist_map_inline:nn { level-1, enumext* } { \__enumext_tmp:n {#1} }

```

(End of definition for `series`, `resume`, and `resume*`.)

### 10.21.1 Internal functions for series key

`\__enumext_filter_series:n` The function `\__enumext_filter_series:n` will be in charge of filtering the *⟨keys⟩* we want to store where `{#1}` represents the optional value passed to the environment.

```

1489 \cs_new:Npn \__enumext_filter_series:n #1
1490 {
1491     \use:e
1492     {
1493         \keyval_parse:NNn
1494         \__enumext_filter_series_key:n
1495         \__enumext_filter_series_pair:nn {#1}
1496     }
1497 }

```



The function `\__enumext_filter_series_key:n` will be responsible for filtering the *⟨keys⟩* that are passed “without value” by excluding the `resume` and `resume*` keys.

```

1498 \cs_new:Npn \__enumext_filter_series_key:n #1
1499 {
1500   \str_case:nnF {#1}
1501   {
1502     { resume } {}
1503     { resume* } {}
1504   }
1505   { , { \exp_not:n {#1} } }
1506 }

```

The function `\__enumext_filter_series_pair:nn` will be responsible for filtering the *⟨keys⟩* that are passed “with value” by excluding the `series`, `resume`, `start`, `save-ans` and `save-key` keys.

```

1507 \cs_new:Npn \__enumext_filter_series_pair:nn #1#2
1508 {
1509   \str_case:nnF {#1}
1510   {
1511     { series } {}
1512     { resume } {}
1513     { start } {}
1514     { save-ans } {}
1515     { save-key } {}
1516   }
1517   { , { \exp_not:n {#1} } = { \exp_not:n {#2} } }
1518 }

```

(End of definition for `\__enumext_filter_series:n`, `\__enumext_filter_series_key:n`, and `\__enumext_filter_series_pair:nn`.)

```

__enumext_parse_series:n
__enumext_resume_last:n

```

The function `\__enumext_parse_series:n` will be responsible for storing the filtered *⟨keys⟩* in the global variable `\g__enumext_series_⟨series name⟩_tl` along with the creation of the integer variable `\g__enumext_series_⟨series name⟩_int` when the key is passed as an argument; otherwise, it will check the state of the boolean variable `\l__enumext_resume_active_bool` set by the keys `resume` and `resume*` and will call the function `\__enumext_resume_last:n`.

- The value of boolean variable `\l__enumext_resume_active_bool` is set to true by the function `\__enumext_resume_counter:n` which is used by the keys `resume` and `resume*`, in this case we must Make sure it is set to false so that it does not overwrite the default filtered *⟨keys⟩*. This function is passed to the function `\__enumext_parse_keys:n` in the `enumext` environment definition (§10.31) and to the function `\__enumext_parse_keys_vii:n` in the `enumext*` environment definition (§10.34).

```

1519 \cs_new_protected:Npn \__enumext_parse_series:n #1
1520 {
1521   \str_if_empty:NTF \l__enumext_series_str
1522   {
1523     \bool_if:NF \l__enumext_resume_active_bool
1524     {
1525       \__enumext_resume_last:n {#1}
1526     }
1527   }
1528   {
1529     \tl_gclear_new:c { g__enumext_series_ \l__enumext_series_str _tl }
1530     \tl_gset:ce { g__enumext_series_ \l__enumext_series_str _tl }
1531     { \__enumext_filter_series:n {#1} }
1532     \int_if_exist:cF { g__enumext_series_ \l__enumext_series_str _int }
1533     {
1534       \int_new:c { g__enumext_series_ \l__enumext_series_str _int }
1535     }
1536   }
1537 }

```

The function `\__enumext_resume_last:n` will be in charge of saving the filtering *⟨keys⟩* when the `series` key is *not used* and will save them in the variable `\g__enumext_standar_series_tl` for the `enumext` environment and in the variable `\g__enumext_starred_series_tl` for the `enumext*` environment. Here we must use `\bool_lazy_all:nT` to make sure that the default values are not overwritten when the environment is nested and the `series` key is not being used.

```

1538 \cs_new_protected:Npn \__enumext_resume_last:n #1
1539 {
1540   \bool_if:NT \l__enumext_standar_first_bool
1541   {
1542     \tl_gclear:N \g__enumext_standar_series_tl
1543     \tl_gset:Ne \g__enumext_standar_series_tl { \__enumext_filter_series:n {#1} }

```

```

1544     }
1545     \bool_if:NT \l__enumext_starred_first_bool
1546     {
1547         \tl_gclear:N \g__enumext_starred_series_tl
1548         \tl_gset:Ne \g__enumext_starred_series_tl { \__enumext_filter_series:n {#1} }
1549     }
1550 }

```

(End of definition for `\__enumext_parse_series:n` and `\__enumext_resume_last:n`)

### 10.21.2 Internal function to save counter value

`\__enumext_resume_save_counter:` The `\__enumext_resume_save_counter:` function will save the last counter value to `\g__enumext_series_⟨series name⟩_int` if the `series={⟨series name⟩}` key has been passed, to `\g__enumext_resume_int` if it has passed the key `resume without value` and the key `series` is not active, in `\g__enumext_series_⟨series name⟩_int` if the key `resume={⟨series name⟩}` has been passed and in `\g__enumext_series_⟨store name⟩_int` if the key has been passed `save-ans={⟨store name⟩}`.

• The variables `\l__enumext_series_str` and `\l__enumext__resume_name_tl` contain the same `{⟨series name⟩}` but are executed at different moments, the integer variable with `\l__enumext_series_str` sets the value when execute `series={⟨series name⟩}` and the integer variable with `\l__enumext__resume_name_tl` sets the subsequent values when use `resume={⟨series name⟩}`. This function is passed to the `enumext` environment definition (§10.31) and the `enumext*` environment definition (§10.34).

```

1551 \cs_new_protected:Nn \__enumext_resume_save_counter:
1552 {
1553     \bool_if:NT \g__enumext_standar_bool
1554     {
1555         \tl_if_empty:NF \l__enumext_series_str
1556         {
1557             \int_gset_eq:cN
1558             { g__enumext_series_ \l__enumext_series_str_int } \value{enumXi}
1559         }
1560         \tl_if_empty:NTF \l__enumext_resume_name_tl
1561         {
1562             \str_if_empty:NT \l__enumext_series_str
1563             {
1564                 \int_gset_eq:NN \g__enumext_resume_int \value{enumXi}
1565             }
1566         }
1567         {
1568             \int_if_exist:cT { g__enumext_series_ \l__enumext_resume_name_tl_int }
1569             {
1570                 \int_gset_eq:cN
1571                 { g__enumext_series_ \l__enumext_resume_name_tl_int } \value{enumXi}
1572             }
1573         }
1574         \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl_int }
1575         {
1576             \int_gset_eq:cN
1577             { g__enumext_resume_ \l__enumext_store_name_tl_int } \value{enumXi}
1578         }
1579     }
1580     \bool_if:NT \g__enumext_starred_bool
1581     {
1582         \tl_if_empty:NF \l__enumext_series_str
1583         {
1584             \int_gset_eq:cN
1585             { g__enumext_series_ \l__enumext_series_str_int } \value{enumXvii}
1586         }
1587         \tl_if_empty:NTF \l__enumext_resume_name_tl
1588         {
1589             \str_if_empty:NT \l__enumext_series_str
1590             {
1591                 \int_gset_eq:NN \g__enumext_resume_vii_int \value{enumXvii}
1592             }
1593         }
1594         {
1595             \int_if_exist:cT { g__enumext_series_ \l__enumext_resume_name_tl_int }
1596             {
1597                 \int_gset_eq:cN
1598                 { g__enumext_series_ \l__enumext_resume_name_tl_int } \value{enumXvii}
1599             }
1600         }
1601     }

```

```

1600     }
1601     \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl _int }
1602     {
1603         \int_gset_eq:cN
1604         { g__enumext_resume_ \l__enumext_store_name_tl _int } \value{enumXvii}
1605     }
1606 }
1607 }

```

(End of definition for \\_\_enumext\_resume\_save\_counter:.)

### 10.21.3 Internal functions for resume key

\\_\_enumext\_resume\_series:n

The function \\_\_enumext\_resume\_series:n will handle the argument passed to the `resume` key in `enumext` and `enumext*` environments. If the key is passed *without value* the function \\_\_enumext\_resume\_counter: is executed which will set the counter according to the numbering of the last `enumext` or `enumext*` environments in which `series={⟨series name⟩}` key is not present, if the `save-ans` key is active it will set the counter according to the value of the integer variable created by that key, otherwise it will verify that the `\g__enumext_series_⟨series name⟩_tl` variable set by the `series` key exists, if so it will pass these keys to the *first level* of the environment, otherwise it will return an error.

```

1608 \cs_new_protected:Npn \__enumext_resume_series:n #1
1609 {
1610     \tl_if_empty:NTF {#1}
1611     {
1612         \__enumext_resume_counter:n { }
1613     }
1614     {
1615         \tl_if_exist:cTF { g__enumext_series_ \tl_to_str:n {#1} _tl }
1616         {
1617             \__enumext_resume_counter:n {#1}
1618             \bool_if:NT \g__enumext_standar_bool
1619             {
1620                 \keys_set:nv { enumext / level-1 }
1621                 { g__enumext_series_ \tl_to_str:n {#1} _tl }
1622             }
1623             \bool_if:NT \g__enumext_starred_bool
1624             {
1625                 \keys_set:nv { enumext / enumext* }
1626                 { g__enumext_series_ \tl_to_str:n {#1} _tl }
1627             }
1628         }
1629         {
1630             \bool_if:NT \g__enumext_standar_bool
1631             {
1632                 \msg_error:nnn { enumext } { unknown-series } {#1}
1633             }
1634             \bool_if:NT \g__enumext_starred_bool
1635             {
1636                 \msg_error:nnn { enumext } { unknown-series } {#1}
1637             }
1638         }
1639     }
1640 }

```

(End of definition for \\_\_enumext\_resume\_series:n.)

\\_\_enumext\_resume\_counter:n

\\_\_enumext\_resume\_counter:

\\_\_enumext\_resume\_counter\_series:

\\_\_enumext\_resume\_counter\_save\_ans:

The function \\_\_enumext\_resume\_counter:n will set the variable \l\_\_enumext\_resume\_active\_bool to true and pass the value of the key `resume` to the variable \l\_\_enumext\_series\_name\_tl which will contain the `{⟨series name⟩}`. If the variable \l\_\_enumext\_series\_name\_tl is empty, that is, we are passing the key `resume` *without value*, we will execute the function \\_\_enumext\_resume\_counter: otherwise, when we pass `resume={⟨series name⟩}` we will execute the function \\_\_enumext\_resume\_counter\_series:, finally we will execute the function \\_\_enumext\_resume\_counter\_save\_ans: which is associated with the key `save-ans`.

```

1641 \cs_new_protected:Npn \__enumext_resume_counter:n #1
1642 {
1643     \bool_set_true:N \l__enumext_resume_active_bool
1644     \tl_set:Nn \l__enumext_resume_name_tl {#1}
1645     \tl_if_empty:NTF \l__enumext_resume_name_tl
1646     {
1647         \__enumext_resume_counter:
1648     }

```

```

1649     {
1650         \__enumext_resume_counter_series:
1651     }
1652     \__enumext_resume_counter_save_ans:
1653 }

```

The `\__enumext_resume_counter:` function is executed when the `resume` key is used *without value*, only the counters for the “*first level*” of the environments will be set.

```

1654 \cs_new_protected:Nn \__enumext_resume_counter:
1655 {
1656     \bool_if:NT \g__enumext_standar_bool
1657     {
1658         \int_gincr:N \g__enumext_resume_int
1659         \int_set_eq:NN \l__enumext_start_i_int \g__enumext_resume_int
1660     }
1661     \bool_if:NT \g__enumext_starred_bool
1662     {
1663         \int_gincr:N \g__enumext_resume_vii_int
1664         \int_set_eq:NN \l__enumext_start_vii_int \g__enumext_resume_vii_int
1665     }
1666 }

```

The function `\__enumext_resume_counter_series:` will be executed when the `resume={⟨series name⟩}` key is active, setting the counters for the “*first level*” of the environments according to the value of the integer variables created by the `series` key.

```

1667 \cs_new_protected:Nn \__enumext_resume_counter_series:
1668 {
1669     \bool_if:NT \g__enumext_standar_bool
1670     {
1671         \int_set:Nn \l__enumext_start_i_int
1672         {
1673             \int_use:c { g__enumext_series_ \l__enumext_resume_name_tl _int } + 1
1674         }
1675     }
1676     \bool_if:NT \g__enumext_starred_bool
1677     {
1678         \int_set:Nn \l__enumext_start_vii_int
1679         {
1680             \int_use:c { g__enumext_series_ \l__enumext_resume_name_tl _int } + 1
1681         }
1682     }
1683 }

```

The function `\__enumext_resume_counter_save_ans:` will be executed when the `save-ans` key is active along with the `resume` key, setting the counters for the “*first level*” of the environments according to the value of the integer variables created by the `save-ans` key.

```

1684 \cs_new_protected:Nn \__enumext_resume_counter_save_ans:
1685 {
1686     \bool_lazy_and:nnT
1687     { \bool_if_p:N \l__enumext_standar_first_bool }
1688     { \bool_if_p:N \l__enumext_store_active_bool }
1689     {
1690         \int_set:Nn \l__enumext_start_i_int
1691         {
1692             \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int } + 1
1693         }
1694     }
1695     \bool_lazy_and:nnT
1696     { \bool_if_p:N \l__enumext_starred_first_bool }
1697     { \bool_if_p:N \l__enumext_store_active_bool }
1698     {
1699         \int_set:Nn \l__enumext_start_vii_int
1700         {
1701             \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int } + 1
1702         }
1703     }
1704 }

```

(End of definition for `\__enumext_resume_counter:n` and others.)

#### 10.21.4 Internal function for resume\* key

`\__enumext_resume_starred:` The function `\__enumext_resume_starred:` will handle the `resume*` key in the `enumext` and `enumext*` environments. This function will execute the filtered `<keys>` in the last one and will continue with the numbering according to the last execution of the environment `enumext` or `enumext*` in which the keys `resume={<series name>}` or `series={<series name>}` were not active.

```

1705 \cs_new_protected:Nn \__enumext_resume_starred:
1706 {
1707   \bool_if:NT \g__enumext_standar_bool
1708   {
1709     \tl_if_empty:NF \g__enumext_standar_series_tl
1710     {
1711       \__enumext_resume_counter:n { }
1712       \keys_set:nV { enumext / level-1 } \g__enumext_standar_series_tl
1713     }
1714   }
1715   \bool_if:NT \g__enumext_starred_bool
1716   {
1717     \tl_if_empty:NF \g__enumext_starred_series_tl
1718     {
1719       \__enumext_resume_counter:n { }
1720       \keys_set:nV { enumext / enumext* } \g__enumext_starred_series_tl
1721     }
1722   }
1723 }

```

(End of definition for `\__enumext_resume_starred:`.)

### 10.22 Setting save-ans, check-ans and no-store keys

The key `save-ans` is directly associated with the keys `check-ans`, `no-store`, `resume` and `resume*`, this will activate the entire “storage system” in the `enumext` package.

#### 10.22.1 Setting save-ans key

`save-ans` We define the keys `save-ans` only for the “first level” of `enumext` and `enumext*`.

```

1724 \cs_set_protected:Npn \__enumext_tmp:n #1
1725 {
1726   \keys_define:nn { enumext / #1 }
1727   {
1728     save-ans .code:n = \__enumext_storing_set:n {##1},
1729     save-ans .value_required:n = true,
1730   }
1731 }
1732 \clist_map_inline:nn { level-1, enumext* } { \__enumext_tmp:n {#1} }

```

(End of definition for `save-ans`.)

#### 10.22.2 Internal functions for save-ans key

`\__enumext_start_save_ans_msg:`  
`\__enumext_stop_save_ans_msg:` The functions `\__enumext_start_save_ans_msg:` and `\__enumext_stop_save_ans_msg:` will display in the terminal and .log file the environment in which the `save-ans` key was executed along with the line at the beginning and end of it. The function `\__enumext_start_save_ans_msg:` will be passed to `\__enumext_storing_set:n` and the function `\__enumext_stop_save_ans_msg:` will be passed to the function `\__enumext_execute_after_env:`.

```

1733 \cs_new_protected:Nn \__enumext_start_save_ans_msg:
1734 {
1735   \msg_term:nnVV { enumext } { save-ans-log }
1736   \g__enumext_envir_name_tl \l__enumext_store_name_tl
1737 }
1738 \cs_new_protected:Nn \__enumext_stop_save_ans_msg:
1739 {
1740   \msg_term:nnVV { enumext } { save-ans-log-hook }
1741   \g__enumext_envir_name_tl \g__enumext_store_name_tl
1742 }

```

(End of definition for `\__enumext_start_save_ans_msg:` and `\__enumext_stop_save_ans_msg:`.)

`\__enumext_storing_set:n`  
`\__enumext_storing_exec:` The function `\__enumext_storing_set:n` first pass the value of the `save-ans` key to the variable `\l__enumext_store_name_tl` which will contain the “store name” of the `<sequence>` and `<prop list>` we will use. If `\l__enumext_store_name_tl` is *empty* we return an error message, otherwise will return the appropriate message `\__enumext_start_save_ans_msg:` and proceed to execute the function `\__enumext_storing_exec:` for `enumext` and `enumext*` environments.

```

1743 \cs_new_protected:Npn \__enumext_storing_set:n #1
1744 {
1745   \tl_set:Nx \l__enumext_store_name_tl {#1}
1746   \tl_if_empty:NTF \l__enumext_store_name_tl
1747   {
1748     \bool_lazy_or:nnT
1749     { \l__enumext_standar_first_bool } { \l__enumext_starred_first_bool }
1750     {
1751       \msg_error:nnV { enumext } { save-ans-empty } \g__enumext_envir_name_tl
1752     }
1753   }
1754   {
1755     \bool_lazy_or:nnT
1756     { \l__enumext_standar_first_bool } { \l__enumext_starred_first_bool }
1757     {
1758       \__enumext_start_save_ans_msg:
1759       \__enumext_storing_exec:
1760     }
1761   }
1762 }

```

The function `\__enumext_storing_exec:` will set to true the variable `\l__enumext_store_active_bool` which activates the use of the `\anskey` command and the `keyans`, `keyans*` and `keyanspic` environments and will set to true the variable `\l__enumext_check_answers_bool` used for checking answers by the `check-ans` and `no-store` keys. The `\prop list` `\g__enumext_series_{store name}_prop` and the `\sequence` `\g__enumext_series_{store name}_seq` will be created globally to “store content” in case they do not exist together with the integer variable `\g__enumext_series_{store name}_int` used by the keys `resume` and `resume*`.

```

1763 \cs_new_protected:Npn \__enumext_storing_exec:
1764 {
1765   \bool_set_true:N \l__enumext_store_active_bool
1766   \bool_set_true:N \l__enumext_check_answers_bool
1767   \tl_gset:Nx \g__enumext_store_name_tl \l__enumext_store_name_tl
1768   \prop_if_exist:cF { g__enumext_ \l__enumext_store_name_tl _prop }
1769   {
1770     \msg_log:nnV { enumext } { store-prop } \l__enumext_store_name_tl
1771     \prop_new:c { g__enumext_ \l__enumext_store_name_tl _prop }
1772   }
1773   \seq_if_exist:cF { g__enumext_ \l__enumext_store_name_tl _seq }
1774   {
1775     \msg_log:nnV { enumext } { store-seq } \l__enumext_store_name_tl
1776     \seq_new:c { g__enumext_ \l__enumext_store_name_tl _seq }
1777   }
1778   \int_if_exist:cF { g__enumext_resume_ \l__enumext_store_name_tl _int }
1779   {
1780     \msg_log:nnV { enumext } { store-int } \l__enumext_store_name_tl
1781     \int_new:c { g__enumext_resume_ \l__enumext_store_name_tl _int }
1782   }
1783 }

```

(End of definition for `\__enumext_storing_set:n` and `\__enumext_storing_exec:`)

### 10.22.3 The check answer mechanism

The mechanism for checking that all questions are answered follows this logic:

If the line begins with `\item` or `\item*` and does NOT *open a nested environment*, each `\item` or `\item*` must contain a *single* execution of the `\anskey` command, i.e. the counter of the executions of the `\anskey` command must be equal to the counter associated with the sum of executions of `\item` and `\item*`.

If the line begins with `\item` or `\item*` and *opens a nested environment* each `\item` or `\item*` in the nested environment must have a *single* execution of the `\anskey` command and the counter associated to the sum of `\item` and `\item*` executions must decrementing by “one” to maintain equality.

In order for the mechanism for the check-answer to work (not counting `keyans`, `keyans*` and `keyanspic`) we need:

1. We must keep track of the total number of `\item` and `\item*` (enumerated) that appear within the environment including the nested levels.
2. We must keep track of the total number of `\item` and `\item*` (enumerated) that appear per level of nesting.

### 3. Keeping track of the number of times the environment nests.

The integer variable associated to the sum of each `\item` and `\item*` in the environment `\g__enumext_item_number_int` must match the integer variable `\g__enumext_item_anskey_int` associated to the execution of the command `\anskey`. We analyze the cases:

- If the list only has one level the number of `\item` + `\item*` = `\anskey`
- If the list has *nested levels*, for each level of nesting we need to decrementing by one (for the `\item` or `\item*` that opens the nest) so that the account remains the same.

With `keyans`, `keyans*` and `keyanspic` it is enough to increase in one the integer of `\anskey`. The integers created must be global if they are not lost in the interior levels of nesting and to execute the test we will use a “hook” function after closing the first level of the environment.

#### 10.22.4 Setting check-ans and no-store keys

Now we define the keys `check-ans` and `no-store` for all levels of `enumext` and `enumext*` environments.

check-ans

no-store

```

1784 \cs_set_protected:Npn \__enumext_tmp:n #1
1785 {
1786   \keys_define:nn { enumext / #1 }
1787   {
1788     check-ans .bool_set:N = \l__enumext_check_ans_key_bool,
1789     check-ans .initial:n = false,
1790     check-ans .value_required:n = true,
1791     no-store .code:n = {
1792       \bool_set_false:N \l__enumext_check_answers_bool
1793       \bool_set_false:N \l__enumext_check_ans_key_bool
1794     },
1795     no-store .value_forbidden:n = true,
1796   }
1797 }
1798 \clist_map_inline:nn
1799 {
1800   level-1, level-2, level-3, level-4, enumext*
1801 }
1802 { \__enumext_tmp:n {#1} }
```

(End of definition for `check-ans` and `no-store`.)

#### 10.22.5 Set-up check answer mechanism

The function `\__enumext_check_ans_active:` will first check the state of the variable `\l__enumext_store_name_tl`, that is, the `save-ans` key is active, if so it will check the state of the variable `\l__enumext_check_answers_bool` handled by the key `no-store` and will execute the function `\__enumext_check_ans_level:` only if “true”, i.e. the key `no-store` is not active.

```

1803 \cs_new_protected:Nn \__enumext_check_ans_active:
1804 {
1805   \tl_if_empty:NF \l__enumext_store_name_tl
1806   {
1807     \bool_if:NT \l__enumext_check_answers_bool
1808     {
1809       \__enumext_check_ans_level:
1810     }
1811   }
1812 }
```

The function `\__enumext_check_ans_level:` will decrement by “one” the value of the variable `\g__enumext_item_number_int` which keeps track of the executions of `\item` and `\item*` for each level of nesting of the environment `enumext`, taking into account whether it is nested within `enumext*` or the opposite.

```

1813 \cs_new_protected:Nn \__enumext_check_ans_level:
1814 {
1815   \int_case:nn { \l__enumext_level_int }
1816   {
1817     { 1 }{
1818       \bool_lazy_all:nT
1819       {
1820         { \bool_if_p:N \g__enumext_starred_bool }
1821         { \int_compare_p:nNn { \l__enumext_level_h_int } = { 1 } }
1822       }
1823       {
1824         \int_gdecr:N \g__enumext_item_number_int
1825       }
1826     }
1827 }
```



```

1827         { 2 }{
1828             \int_gdecr:N \g__enumext_item_number_int
1829         }
1830         { 3 }{
1831             \int_gdecr:N \g__enumext_item_number_int
1832         }
1833         { 4 }{
1834             \int_gdecr:N \g__enumext_item_number_int
1835         }
1836     }
1837     \int_case:nn { \l__enumext_level_h_int }
1838     {
1839         { 1 }{
1840             \bool_if:NT \g__enumext_standar_bool
1841             {
1842                 \int_gdecr:N \g__enumext_item_number_int
1843             }
1844         }
1845     }
1846 }

```

(End of definition for \\_\_enumext\_check\_ans\_active: and \\_\_enumext\_check\_ans\_level:.)

\\_\_enumext\_check\_ans\_key\_hook:

The function \\_\_enumext\_check\_ans\_key\_hook: will *export* the status of the local variable \l\_\_enumext\_check\_ans\_key\_bool to the global variable \g\_\_enumext\_check\_ans\_key\_bool only if the key `check-ans` is active.

```

1847 \cs_new_protected:Nn \__enumext_check_ans_key_hook:
1848 {
1849     \bool_lazy_and:nnT
1850     { \bool_if_p:N \l__enumext_check_ans_key_bool }
1851     { \bool_if_p:N \g__enumext_standar_bool }
1852     {
1853         \bool_gset_true:N \g__enumext_check_ans_key_bool
1854     }
1855     \bool_lazy_and:nnT
1856     { \bool_if_p:N \l__enumext_check_ans_key_bool }
1857     { \bool_if_p:N \g__enumext_starred_bool }
1858     {
1859         \bool_gset_true:N \g__enumext_check_ans_key_bool
1860     }
1861 }

```

(End of definition for \\_\_enumext\_check\_ans\_key\_hook:.)

\\_\_enumext\_item\_answer\_diff:

The function \\_\_enumext\_item\_answer\_diff: will set the value of the variable \g\_\_enumext\_item\_answer\_diff\_int which is used by the functions \\_\_enumext\_check\_ans\_show: for the key `save-ans` and by the function \\_\_enumext\_check\_ans\_log: by the internal “*check answer*” mechanism. This function will be passed to the function \\_\_enumext\_execute\_after\_env:.

```

1862 \cs_new_protected:Nn \__enumext_item_answer_diff:
1863 {
1864     \int_gset:Nn \g__enumext_item_answer_diff_int
1865     {
1866         \int_sign:n { \g__enumext_item_number_int - \g__enumext_item_anskey_int }
1867     }
1868 }

```

(End of definition for \\_\_enumext\_item\_answer\_diff:.)

\\_\_enumext\_check\_ans\_show:

\\_\_enumext\_check\_ans\_msg\_less:  
\\_\_enumext\_check\_ans\_msg\_same\_ok:  
\\_\_enumext\_check\_ans\_msg\_greater:

The function \\_\_enumext\_check\_ans\_show: will be executed within the function \\_\_enumext\_execute\_after\_env: when the key `check-ans` is active, that is, when \g\_\_enumext\_check\_ans\_key\_bool is “*true*” and will return the appropriate message according to the value of \g\_\_enumext\_item\_answer\_diff\_int set by the function \\_\_enumext\_item\_answer\_diff:.

```

1869 \cs_new_protected:Nn \__enumext_check_ans_show:
1870 {
1871     \int_case:nn { \g__enumext_item_answer_diff_int }
1872     {
1873         { -1 }{ \__enumext_check_ans_msg_less: }
1874         { 0 }{ \__enumext_check_ans_msg_same_ok: }
1875         { 1 }{ \__enumext_check_ans_msg_greater: }
1876     }

```

```

1877     }
1878 \cs_new_protected:Nn \__enumext_check_ans_msg_less:
1879 {
1880     \msg_warning:nneee { enumext } { item-less-answer } { \g__enumext_store_name_tl }
1881     { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
1882 }
1883 \cs_new_protected:Nn \__enumext_check_ans_msg_same_ok:
1884 {
1885     \msg_term:nneee { enumext } { items-same-answer } { \g__enumext_store_name_tl }
1886     { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
1887 }
1888 \cs_new_protected:Nn \__enumext_check_ans_msg_greater:
1889 {
1890     \msg_warning:nneee { enumext } { item-greater-answer } { \g__enumext_store_name_tl }
1891     { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
1892 }

```

(End of definition for \\_\_enumext\_check\_ans\_show: and others.)

The function \\_\_enumext\_check\_ans\_log: will be executed within the function \\_\_enumext\_execute\_after\_env: when the key `check-ans` is not active, that is, when \g\_\_enumext\_check\_ans\_key\_bool is “false” and write in the log the appropriate message according to the value of \g\_\_enumext\_item\_answer\_diff\_int set by the function \\_\_enumext\_item\_answer\_diff:.

```

1893 \cs_new_protected:Nn \__enumext_check_ans_log:
1894 {
1895     \int_case:nn { \g__enumext_item_answer_diff_int }
1896     {
1897         { -1 } { \__enumext_check_ans_log_msg_less: }
1898         { 0 } { \__enumext_check_ans_log_msg_same_ok: }
1899         { 1 } { \__enumext_check_ans_log_msg_greater: }
1900     }
1901 }
1902 \cs_new_protected:Nn \__enumext_check_ans_log_msg_less:
1903 {
1904     \msg_log:nneee { enumext } { item-less-answer } { \g__enumext_store_name_tl }
1905     { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
1906 }
1907 \cs_new_protected:Nn \__enumext_check_ans_log_msg_same_ok:
1908 {
1909     \msg_log:nneee { enumext } { items-same-answer } { \g__enumext_store_name_tl }
1910     { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
1911 }
1912 \cs_new_protected:Nn \__enumext_check_ans_log_msg_greater:
1913 {
1914     \msg_log:nneee { enumext } { item-greater-answer } { \g__enumext_store_name_tl }
1915     { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
1916 }

```

(End of definition for \\_\_enumext\_check\_ans\_log: and others.)

### 10.22.6 Writing .log and executing the check-ans key

The \\_\_enumext\_execute\_after\_env: function will first return the appropriate message for the end of the environment in which the `save-ans` key is being executed, then call the \\_\_enumext\_item\_answer\_diff: function and then will write the values of the global variables used to the .log file. If the key `check-ans` is active it will execute the function \\_\_enumext\_check\_ans\_show: and show the result in the terminal, otherwise it will execute the function \\_\_enumext\_check\_ans\_log: and write the results in the .log file will finally execute the function \\_\_enumext\_reset\_global\_vars: returning the used variables to their original state. As this function is passed to the function \\_\_enumext\_after\_env:nn for the environments `enumext` and `enumext*` we must make sure that we are not nested at any level.

```

1917 \cs_new_protected:Nn \__enumext_execute_after_env:
1918 {
1919     \int_compare:nNtT { \l__enumext_level_int } = { 0 }
1920     {
1921         \tl_if_empty:NF \g__enumext_store_name_tl
1922         {
1923             \__enumext_stop_save_ans_msg:
1924             \__enumext_item_answer_diff:
1925             \__enumext_log_global_vars:
1926             \__enumext_log_answer_vars:
1927             \bool_if:NTF \g__enumext_check_ans_key_bool

```

```

1928         {
1929             \__enumext_check_ans_show:
1930         }
1931         { \__enumext_check_ans_log: }
1932     }
1933     \__enumext_reset_global_vars:
1934 }
1935 }

```

(End of definition for \\_\_enumext\_execute\_after\_env:.)

### 10.22.7 Check for \item\* and \anspic\* commands

\\_\_enumext\_check\_starred\_cmd:n

The function \\_\_enumext\_check\_starred\_cmd:n performs an extra check for the `keyans`, `keyans*` and `keyanspic` environments. Unlike the check executed by `check-ans` key this one is not controlled by any key, it is intended to prevent the forgetting of `\item*` or `\anspic*` in these environments.

```

1936 \cs_new_protected:Npn \__enumext_check_starred_cmd:n #1
1937 {
1938     \int_compare:nNtT
1939     { \g__enumext_check_starred_cmd_int } = { 0 }
1940     {
1941         \msg_warning:nnnV
1942         { enumext } { missing-starred }{ #1 } \l__enumext_check_start_line_env_tl
1943     }
1944     \int_compare:nNtT
1945     { \g__enumext_check_starred_cmd_int } > { 1 }
1946     {
1947         \msg_warning:nnnV
1948         { enumext } { many-starred }{ #1 } \l__enumext_check_start_line_env_tl
1949     }
1950     \int_gzero:N \g__enumext_check_starred_cmd_int
1951     \tl_clear:N \l__enumext_check_start_line_env_tl
1952 }

```

(End of definition for \\_\_enumext\_check\_starred\_cmd:n.)

### 10.23 Keys and functions associated with storage

We add the keys `wrap-ans`, `wrap-opt`, `save-sep`, `mark-ans`, `mark-pos`, `show-ans`, `show-pos`, `mark-ref` and `save-ref` related to the “storage system” and internal mechanism of “label and ref” only at the first level of `enumext` and `enumext*`.

```

1953 \cs_set_protected:Npn \__enumext_tmp:n #1
1954 {
1955     \keys_define:nn { enumext / #1 }
1956     {
1957         wrap-ans .cs_set_protected:Np = \__enumext_anskey_wrapper:n ##1,
1958         wrap-ans .initial:n = \fbox{##1},
1959         wrap-ans .value_required:n = true,
1960         wrap-opt .cs_set_protected:Np = \__enumext_keyans_wrapper_opt:n ##1,
1961         wrap-opt .initial:n = [{##1}],
1962         wrap-opt .value_required:n = true,
1963         save-sep .tl_set:N = \l__enumext_store_keyans_item_opt_sep_tl,
1964         save-sep .initial:n = {, ~ },
1965         save-sep .value_required:n = true,
1966         mark-ans .tl_set:N = \l__enumext_mark_answer_sym_tl,
1967         mark-ans .initial:n = \textasteriskcentered,
1968         mark-ans .value_required:n = true,
1969         mark-pos .choice:,
1970         mark-pos / left .code:n = \str_set:Nn \l__enumext_mark_position_str { l },
1971         mark-pos / right .code:n = \str_set:Nn \l__enumext_mark_position_str { r },
1972         mark-pos .initial:n = right,
1973         mark-pos .value_required:n = true,
1974         show-ans .bool_set:N = \l__enumext_show_answer_bool,
1975         show-ans .initial:n = false,
1976         show-ans .value_required:n = true,
1977         show-pos .bool_set:N = \l__enumext_show_position_bool,
1978         show-pos .initial:n = false,
1979         show-pos .value_required:n = true,
1980         mark-ref .tl_set:N = \l__enumext_mark_ref_sym_tl,
1981         mark-ref .initial:n = \textasteriskcentered,
1982         mark-ref .value_required:n = true,
1983         save-ref .bool_set:N = \l__enumext_store_ref_key_bool,

```

```

1984         save-ref .initial:n = false,
1985         save-ref .value_required:n = true,
1986     }
1987 }
1988 \clist_map_inline:nn { level-1, enumext* } { \__enumext_tmp:n {#1} }

```

(End of definition for *wrap-ans* and others.)

For the **keyans** and **keyans\*** environments we will only add the keys **mark-pos**, **show-ans** and **show-pos**.

```

1989 \cs_set_protected:Npn \__enumext_tmp:n #1
1990 {
1991     \keys_define:nn { enumext / #1 }
1992     {
1993         mark-pos .choice:,
1994         mark-pos / left .code:n = \str_set:Nn \l__enumext_mark_position_str { l },
1995         mark-pos / right .code:n = \str_set:Nn \l__enumext_mark_position_str { r },
1996         mark-pos .initial:n = right,
1997         mark-pos .value_required:n = true,
1998         show-ans .bool_set:N = \l__enumext_show_answer_bool,
1999         show-ans .initial:n = false,
2000         show-ans .value_required:n = true,
2001         show-pos .bool_set:N = \l__enumext_show_position_bool,
2002         show-pos .initial:n = false,
2003         show-pos .value_required:n = true,
2004     }
2005 }
2006 \clist_map_inline:nn { keyans, keyans* } { \__enumext_tmp:n {#1} }

```

(End of definition for *mark-pos*, *show-ans*, and *show-pos*.)

For the **enumext** and **enumext\*** environments we will only add the keys **columns\*** and **columns-sep\***. The values set by these keys will be passed as optional arguments to the “inner levels” of the **enumext** and **enumext\*** environments via the `\__enumext_store_level_open:` function used by the “storage system” to preserve the structure and then used by the `\printkeyans` command.

```

2007 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
2008 {
2009     \keys_define:nn { enumext / #1 }
2010     {
2011         columns* .code:n = \bool_set_true:c { l__enumext_store_columns_#2_bool }
2012         \int_set:cn { l__enumext_store_columns_#2_int } {##1}
2013         \tl_put_right:ce { l__enumext_store_opt_#2_tl }
2014             {
2015                 columns = \exp_not:v { l__enumext_store_columns_#2_int },
2016             },
2017         columns* .value_required:n = true,
2018         columns-sep* .code:n = \bool_set_true:c { l__enumext_store_columns_sep_#2_bool }
2019         \dim_set:cn { l__enumext_store_columns_sep_#2_dim } {##1}
2020         \tl_put_right:ce { l__enumext_store_opt_#2_tl }
2021             {
2022                 columns-sep = \exp_not:v { l__enumext_store_columns_sep_#2_dim },
2023             },
2024         columns-sep* .value_required:n = true,
2025     }
2026 }
2027 \clist_map_inline:nn
2028 {
2029     {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {enumext*}{vii}
2030 }
2031 { \__enumext_tmp:nn #1 }

```

(End of definition for **columns\*** and **columns-sep\***.)

### 10.23.1 Function for storing content in prop list

The function `\__enumext_store_addto_prop:n` stores the content in *(prop list)* defined by *save-ans* key. The “stored content” is retrieved by means of the `\getkeyans` command.

The form in which the content is “stored” in the *(prop list)* is  $\{\langle position \rangle\}\{\langle content \rangle\}$ . This function is used by `\anskey` in **enumext** and **enumext\*** environments, `\item*` in **keyans** and **keyans\*** environments and `\anspic` in **keyanspic** environment.

```

2032 \cs_new_protected:Npn \__enumext_store_addto_prop:n #1

```

```

2033 {
2034   \prop_gput_if_not_in:cen { g__enumext_ \l__enumext_store_name_tl _prop }
2035   {
2036     \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } + 1 }
2037   }
2038   { #1 }
2039 }
2040 \cs_generate_variant:Nn \__enumext_store_addto_prop:n { V }

```

(End of definition for `\__enumext_store_addto_prop:n`.)

### 10.23.2 Function for storing content in sequence

The function `\__enumext_store_addto_seq:n` stores the content in *sequence* defined by `save-ans` key. This function is used by `\anskey` in `enumext`, `\item*` in `keyans` and `\anspic` in `keyanspic`.

The form in which the content is stored in *sequence* is in a internal `enumext` or `enumext*` environments with the *same structure* in which the command was executed.

The “*stored content*” is retrieved by means of the `\printkeyans` command.

```

2041 \cs_new_protected:Npn \__enumext_store_addto_seq:n #1
2042 {
2043   \seq_gput_right:cn { g__enumext_ \l__enumext_store_name_tl _seq } { #1 }
2044 }
2045 \cs_generate_variant:Nn \__enumext_store_addto_seq:n { v, V }

```

(End of definition for `\__enumext_store_addto_seq:n`.)

### 10.23.3 Functions for storing the list structure in the sequence

The memorization structure of the list is handled by the functions `\__enumext_store_level_open:` and `\__enumext_store_level_close:` which are executed per level within the `enumext` environment. As this structure will be stored in the sequence set by the `save-ans` key, we will not be able to modify it locally, so it is better to take only two copies of the values set by the `columns` and `columns-sep` keys if they are present when changing levels within the `enumext` environment when executing `\anskey`. We will store these values in the variable `\l__enumext_store_columns_X_tl` if they are different from `0` and `0pt` and pass them as an optional argument to the environment stored in the sequence `enumext`.

```

2046 \cs_new_protected:Nn \__enumext_store_level_open:
2047 {
2048   \bool_if:NT \l__enumext_check_answers_bool
2049   {
2050     \tl_if_empty:cTF { l__enumext_store_opt_ \__enumext_level: _tl }
2051     {
2052       \__enumext_store_addto_seq:n
2053       {
2054         \item \begin{enumext}
2055       }
2056     }
2057     {
2058       \tl_put_left:cn { l__enumext_store_opt_ \__enumext_level: _tl }
2059       {
2060         \item \begin{enumext} [
2061         ]
2062       }
2063       \tl_put_right:cn { l__enumext_store_opt_ \__enumext_level: _tl }
2064       {
2065         ]
2066       }
2067       \__enumext_store_addto_seq:v { l__enumext_store_opt_ \__enumext_level: _tl }
2068     }
2069   }
2070 \cs_new_protected:Nn \__enumext_store_level_close:
2071 {
2072   \bool_if:NT \l__enumext_check_answers_bool
2073   {
2074     \__enumext_store_addto_seq:n { \end{enumext} }
2075   }
2076 }

```

(End of definition for `\__enumext_store_level_open:` and `\__enumext_store_level_close:.`)

```

\__enumext_store_level_open_vii:
\__enumext_store_level_close_vii:

```

When nesting the `enumext*` environment in `enumext` starting right after `\item` (without material between them) there is a problem with the alignment of the labels with the baseline between the two environments. One way to get around this problem is to place `\mode_leave_vertical:` and then apply `\vspace` taking

into account `\baselineskip`, the value of `\parsep` of the current level of `enumext` and the value of `\topsep` of the `enumext*` environment.

```

2077 \cs_new_protected:Nn \__enumext_store_level_open_vii:
2078 {
2079   \bool_if:NT \l__enumext_check_answers_bool
2080   {
2081     \tl_if_empty:NTF \l__enumext_store_opt_vii_tl
2082     {
2083       \__enumext_store_addto_seq:n
2084       {
2085         \item \mode_leave_vertical:
2086         \vspace { -\skip_eval:n { \baselineskip + \parsep } }
2087         \begin{enumext*}[before={\setlength{\topsep}{\opt}},]
2088       }
2089     }
2090     {
2091       \tl_put_left:Nn \l__enumext_store_opt_vii_tl
2092       {
2093         \item \mode_leave_vertical:
2094         \vspace { -\skip_eval:n { \baselineskip + \parsep } }
2095         \begin{enumext*}[before={\setlength{\topsep}{\opt}},
2096       ]
2097       \tl_put_right:Nn \l__enumext_store_opt_vii_tl
2098       {
2099         ]
2100       }
2101       \__enumext_store_addto_seq:V \l__enumext_store_opt_vii_tl
2102     }
2103   }
2104 }
2105 \cs_new_protected:Nn \__enumext_store_level_close_vii:
2106 {
2107   \bool_if:NT \l__enumext_check_answers_bool
2108   {
2109     \__enumext_store_addto_seq:n { \end{enumext*} }
2110   }
2111 }

```

(End of definition for `\__enumext_store_level_open_vii:` and `\__enumext_store_level_close_vii:`.)

#### 10.23.4 Function for show marks and position

```

\__enumext_print_keyans_box:NN
\__enumext_print_keyans_box:cc

```

The function `\__enumext_print_keyans_box:NN` print a box in the left margin with `\l__enumext_mark_answer_sym_tl` used by the `wrap-ans`, `show-ans` and `show-pos` keys. The function takes two arguments:

**#1:** `\l__enumext_labelwidth_X_dim`  
**#2:** `\l__enumext_labelsep_X_dim`

```

2112 \cs_new_protected:Nn \__enumext_print_keyans_box:NN
2113 {
2114   \mode_leave_vertical:
2115   \skip_horizontal:n { -\dim_use:N #2 }
2116   \makebox[\opt][ r ]
2117   {
2118     \makebox[ \dim_use:N #1 ][ \l__enumext_mark_position_str ]
2119     {
2120       \tl_use:N \l__enumext_mark_answer_sym_tl
2121     }
2122   }
2123   \skip_horizontal:n { \dim_use:N #2 }
2124 }
2125 \cs_generate_variant:Nn \__enumext_print_keyans_box:NN { cc }

```

(End of definition for `\__enumext_print_keyans_box:NN`.)

#### 10.24 The command `\anskey` and internal label and ref

Since we will be “*storing content*” in a list environment within *(sequences)* and can (more or less) manage the options passed to each level, it is necessary that we have a little more control over `\item` when storing. The `\anskey` command will cover this point and give it very similar behaviour to that of `\item` in the `enumext` and `enumext*` environments.

`\anskey` We want the command to be executed as follows: `\anskey(<number>)*[<key = val>]{<content>}` so first we'll add the keys `item-sym*`, `item-pos*` and `store-brk`.

```

2126 \keys_define:nn { enumext / anskey }
2127 {
2128   item-sym* .tl_set:N = \l__enumext_store_item_symbol_tl,
2129   item-sym* .value_required:n = true,
2130   item-pos* .dim_set:N = \l__enumext_store_item_symbol_sep_dim,
2131   item-pos* .value_required:n = true,
2132   store-brk .bool_set:N = \l__enumext_store_columns_break_bool,
2133   store-brk .default:n = true,
2134   store-brk .value_forbidden:n = true,
2135 }

```

This command `\anskey` will only be present when using the `save-ans` key in `enumext` and `enumext*` environments, otherwise it will return an error. If the `check-ans` key is active, increment `\g__enumext_count_item_with_ans_int`, then call internal function `\__enumext_store_anskey_code:nnnn` will “store content” in the `<sequence>` and in the `<prop list>`.

```

2136 \NewDocumentCommand \anskey { d() s o +m }
2137 {
2138   \bool_if:NF \l__enumext_store_active_bool
2139   {
2140     \msg_error:nnnn { enumext } { anskey-wrong-place }{ anskey }{ enumext }
2141   }
2142   \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
2143   {
2144     \msg_error:nnnn { enumext } { command-wrong-place }{ anskey }{ keyans }
2145   }
2146   \int_compare:nNnT { \l__enumext_keyans_pic_level_int } = { 1 }
2147   {
2148     \msg_error:nnnn { enumext } { command-wrong-place }{ anskey }{ keyanspic }
2149   }
2150   \group_begin:
2151     %\bool_if:NT \l__enumext_check_answers_bool
2152     % {
2153       \int_gincr:N \g__enumext_item_anskey_int
2154     % }
2155     \__enumext_store_anskey_code:nnnn {#1} {#2} {#3} {#4}
2156   \group_end:
2157 }

```

(End of definition for `\anskey`. This function is documented on page 10.)

`\__enumext_store_anskey_code:nnnn`

The internal function `\__enumext_store_anskey_code:nnnn` first we pass the command `<argument>` to the `<prop list>`, then checks the state of the variable `\l__enumext_store_ref_key_bool` handled by the `save-ref` key and will call the function `\__enumext_store_internal_ref:` for the internal “label and ref” system. Followed by this if the `show-ans` or `show-pos` keys are active we will show the “wrapped” `<argument>` passed to the command.

```

2158 \cs_new_protected:Npn \__enumext_store_anskey_code:nnnn #1 #2 #3 #4
2159 {
2160   \__enumext_store_addto_prop:n {#4}
2161   \bool_if:NT \l__enumext_store_ref_key_bool
2162   {
2163     \__enumext_store_internal_ref:
2164   }
2165   \__enumext_store_anskey_show_left:n { #4 }

```

Now we start processing the optional arguments passed to the command to build our `\item` in the variable `\l__enumext_store_anskey_arg_tl` which we will “store” in the `<sequence>`. First we clear the variable `\l__enumext_store_anskey_arg_tl` and process `[<key = val>]`, if the `store-brk` key is present and the command is running under `enumext` (not in the starred version) we will add `\columnbreak` and then `\item`.

```

2166   \tl_clear:N \l__enumext_store_anskey_arg_tl
2167   \tl_if_novalue:nF {#3}
2168   {
2169     \keys_set:nn { enumext / anskey } {#3}
2170   }
2171   \bool_lazy_and:nnT
2172   { \bool_if_p:N \l__enumext_store_columns_break_bool }
2173   { \bool_not_p:n { \l__enumext_starred_bool } }
2174   {
2175     \tl_put_left:Nn \l__enumext_store_anskey_arg_tl { \columnbreak }

```



```

2176     }
2177     \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { \item }

```

Now we will check the  $\langle\langle number \rangle\rangle$  argument and add it to `\l__enumext_store_anskey_arg_tl` if the command is running under `enumext*` (starred version).

```

2178     \tl_if_novalue:nF {#1}
2179     {
2180         \int_set:Nn \l__enumext_store_columns_join_int {#1}
2181         \bool_if:NT \l__enumext_starred_bool
2182         {
2183             \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2184             {
2185                 ( \exp_not:V \l__enumext_store_columns_join_int )
2186             }
2187         }
2188     }

```

And now we will review the starred argument `*` together with the keys `item-sym*` and `item-pos*` and pass them to `\l__enumext_store_anskey_arg_tl`.

```

2189     \bool_if:nTF {#2}
2190     {
2191         \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { * }
2192         \tl_if_empty:NF \l__enumext_store_item_symbol_tl
2193         {
2194             \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2195             {
2196                 [ \exp_not:V \l__enumext_store_item_symbol_tl ]
2197             }
2198         }
2199         \dim_compare:nT
2200         {
2201             \l__enumext_store_item_symbol_sep_dim != \c_zero_dim
2202         }
2203         {
2204             \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2205             {
2206                 [ \exp_not:V \l__enumext_store_item_symbol_sep_dim ]
2207             }
2208         }
2209         \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#4}
2210     }
2211     {
2212         \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#4}
2213     }

```

Finally we check if the `save-ref` key is active along with the `hyperref` package load, if both conditions are met, it will create the `\hyperlink` and then store in  $\langle sequence \rangle$ .

```

2214     \bool_lazy_and:nnT
2215     { \bool_if_p:N \l__enumext_store_ref_key_bool }
2216     { \bool_if_p:N \l__enumext_hyperref_bool }
2217     {
2218         \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2219         {
2220             \hfill \exp_not:N \hyperlink { \exp_not:V \l__enumext_newlabel_arg_one_tl }
2221             { \exp_not:V \l__enumext_mark_ref_sym_tl }
2222         }
2223     }
2224     \__enumext_store_addto_seq:V \l__enumext_store_anskey_arg_tl
2225 }

```

(End of definition for `\__enumext_store_anskey_code:nnnn`.)

`\__enumext_store_internal_ref:`

The function `\__enumext_store_internal_ref:` handles the internal “*label and ref*” system used by the `save-ref` and `mark-ref` keys for `\anskey` will allow to execute `\ref{⟨store name : position⟩}` and will return `1.(a).i.A`.

First we will remove the dots “.” from the current  $\langle labels \rangle$ , we do not want to get double dots in our references, then we will place this in the variable `\l__enumext_newlabel_arg_two_tl`.

```

2226 \cs_new_protected:Nn \__enumext_store_internal_ref:
2227 {
2228     \cs_set_protected:Npn \__enumext_tmp:n ##1
2229     {
2230         \tl_set_eq:cc { \l__enumext_label_copy_##1_tl } { \l__enumext_label_##1_tl }

```

```

2231     \tl_reverse:c { l__enumext_label_copy_##1_tl }
2232     \tl_remove_once:cn { l__enumext_label_copy_##1_tl } { . }
2233     \tl_reverse:c { l__enumext_label_copy_##1_tl }
2234   }
2235   \clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {##1} }
2236   \cs_set:Npn \__enumext_tmp:n ##1
2237     { . \tl_use:c { l__enumext_label_copy_ \int_to_roman:n {##1} _tl } }

```

Here we need to analyse the cases where the environment is started with `enumext*` and if `\anskey` is running alone in it or if it is running in a nested `enumext` environment within the starting environment.

```

2238   \bool_lazy_all:nT
2239   {
2240     { \bool_if_p:N \g__enumext_starred_bool }
2241     { \int_compare_p:nNn { \l__enumext_level_int } = { \c_zero_int } }
2242   }
2243   {
2244     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2245       { \tl_use:N \l__enumext_label_copy_vii_tl }
2246   }
2247   \bool_lazy_all:nT
2248   {
2249     { \bool_if_p:N \l__enumext_standar_bool }
2250     { \bool_if_p:N \g__enumext_starred_bool }
2251     { \int_compare_p:nNn { \l__enumext_level_int } > { \c_zero_int } }
2252   }
2253   {
2254     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2255       {
2256         \tl_use:N \l__enumext_label_copy_vii_tl
2257         \int_step_function:nnN { 1 } { \l__enumext_level_int } \__enumext_tmp:n
2258       }
2259   }

```

If started with `enumext` and if `\anskey` is running alone in it or if it is running in a nested `enumext*` environment within the starting environment.

```

2260   \bool_lazy_all:nT
2261   {
2262     { \bool_if_p:N \l__enumext_standar_bool }
2263     { \int_compare_p:nNn { \l__enumext_level_int } > { \c_zero_int } }
2264     { \int_compare_p:nNn { \l__enumext_level_h_int } = { \c_zero_int } }
2265     { \bool_not_p:n { \l__enumext_starred_bool } }
2266   }
2267   {
2268     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2269       {
2270         \tl_use:N \l__enumext_label_copy_i_tl
2271         \int_step_function:nnN { 2 } { \l__enumext_level_int } \__enumext_tmp:n
2272       }
2273   }
2274   \cs_set:Npn \__enumext_tmp:n ##1
2275     { \tl_use:c { l__enumext_label_copy_ \int_to_roman:n {##1} _tl } }
2276   \bool_lazy_all:nT
2277   {
2278     { \bool_if_p:N \l__enumext_standar_bool }
2279     { \int_compare_p:nNn { \l__enumext_level_int } > { \c_zero_int } }
2280     { \bool_not_p:n { \g__enumext_starred_bool } }
2281     { \int_compare_p:nNn { \l__enumext_level_h_int } > { \c_zero_int } }
2282   }
2283   {
2284     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2285       {
2286         \int_step_function:nnN { 1 } { \l__enumext_level_int } \__enumext_tmp:n
2287         . \tl_use:N \l__enumext_label_copy_vii_tl
2288       }
2289   }

```

Now we set the variable `\l__enumext_newlabel_arg_one_tl` which will contain  $\langle \textit{store name} : \textit{position} \rangle$ .

```

2290   \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
2291   {
2292     \l__enumext_store_name_tl \c_colon_str
2293     \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }

```

```
2294     }
```

Now execute the function `\__enumext_newlabel:n` and save the result in the variable `\l__enumext_store_write_aux_file_tl` and finally we write in the `.aux` file.

```
2295     \tl_put_right:Ne \l__enumext_store_write_aux_file_tl
2296     {
2297         \__enumext_newlabel:n
2298         { \exp_not:V \l__enumext_newlabel_arg_one_tl }
2299         { \l__enumext_newlabel_arg_two_tl }
2300     }
2301     \l__enumext_store_write_aux_file_tl
2302 }
```

(End of definition for `\__enumext_store_internal_ref:.`)

```
\__enumext_store_anskey_show_wrap:n
```

The function `\__enumext_store_anskey_show_wrap:n` “wraps” the *⟨argument⟩* passed to `\anskey` when using the `wrap-ans` key.

```
2303 \cs_new_protected:Npn \__enumext_store_anskey_show_wrap:n #1
2304 {
2305     \par
2306     \bool_if:NT \l__enumext_starred_bool
2307     {
2308         \cs_set:Nn \__enumext_level: { vii }
2309     }
2310     \__enumext_print_keyans_box:cc
2311     { \__enumext_labelwidth_ \__enumext_level: _dim }
2312     { \__enumext_labelsep_ \__enumext_level: _dim }
2313     \__enumext_anskey_wrapper:n { #1 }
2314 }
```

(End of definition for `\__enumext_store_anskey_show_wrap:n`.)

```
\__enumext_store_anskey_show_left:n
```

The function `\__enumext_store_anskey_show_left:n` will show the “mark” defined by the `mark-ans` key or the “position” of the content stored in the *⟨prop list⟩* when using the `show-pos` key on the left margin next to the “wraps” *⟨argument⟩* passed to `\anskey` on the right side when using the `show-ans` key.

```
2315 \cs_new_protected:Npn \__enumext_store_anskey_show_left:n #1
2316 {
2317     \bool_if:NT \l__enumext_show_answer_bool
2318     {
2319         \__enumext_store_anskey_show_wrap:n { #1 }
2320     }
2321     \bool_if:NT \l__enumext_show_position_bool
2322     {
2323         \tl_set:Ne \l__enumext_mark_answer_sym_tl
2324         {
2325             \group_begin:
2326             \exp_not:N \normalfont
2327             \exp_not:N \footnotesize [ \int_eval:n
2328             {
2329                 \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
2330             }
2331             ]
2332             \group_end:
2333         }
2334         \__enumext_store_anskey_show_wrap:n { #1 }
2335     }
2336 }
```

(End of definition for `\__enumext_store_anskey_show_left:n`.)

## 10.25 Common functions for keyans, keyans\* and keyanspic

### 10.25.1 Storing content in prop list

```
\__enumext_keyans_addto_prop:n
```

The function `\__enumext_keyans_addto_prop:n` will pass the contents of the current *⟨label⟩* `\l__enumext_label_v_tl` for the `keyans` environment and the current *⟨label⟩* `\l__enumext_label_vi_tl` for the `keyanspic` environment when using `\item*` and `\anspic*`, followed by the *contents* of the optional argument of both commands to the `\l__enumext_store_keyans_label_tl` variable, which will be passed to the *⟨prop list⟩* defined by the `save-ans` key using the `\__enumext_store_addto_prop:V`.

```
2337 \cs_new_protected:Npn \__enumext_keyans_addto_prop:n #1
```

```

2338 {
2339   \tl_clear:N \__enumext_store_keyans_label_tl
2340   \int_compare:nNnTF { \__enumext_keyans_pic_level_int } = { 1 }
2341   {
2342     \tl_put_right:Ne \__enumext_store_keyans_label_tl { \__enumext_label_vi_tl }
2343   }
2344   {
2345     \tl_put_right:Ne \__enumext_store_keyans_label_tl { \__enumext_label_v_tl }
2346   }
2347   \tl_if_novalue:nF { #1 }
2348   {
2349     % Set save-sep
2350     \tl_if_empty:NF \__enumext_store_keyans_item_opt_sep_tl
2351     {
2352       \tl_put_right:Ne \__enumext_store_keyans_label_tl { \__enumext_store_keyans_item_opt_sep_tl }
2353     }
2354     \tl_put_right:Ne \__enumext_store_keyans_label_tl { #1 }
2355   }
2356   \__enumext_store_addto_prop:V \__enumext_store_keyans_label_tl
2357 }

```

(End of definition for `\__enumext_keyans_addto_prop:n`.)

### 10.25.2 The save-ref key for keyans, keyans\* and keyanspic

The internal “*label and ref*” system for the `keyans`, `keyans*` and `keyanspic` environments has slight differences with the one implemented for the `\anskey` command, basically because in this environments we are interested in the current `\label`. The mechanism defined here will allow to execute `\ref{<store name : position>}` and will return `1`. (A).

```

\__enumext_keyans_store_ref:
  \__enumext_keyans_store_ref_aux_i:
  \__enumext_keyans_store_ref_aux_ii:

```

The function `\__enumext_keyans_store_ref:` handles the internal “*label and ref*” system used by the `save-ref` key for `\item*` and `\anspic*` commands. First we will create copies of the current `\labels` and remove the dots “.” from them, we do not want to get double dots in our references.

```

2358 \cs_new_protected:Nn \__enumext_keyans_store_ref:
2359 {
2360   \bool_if:NT \__enumext_store_ref_key_bool
2361   {
2362     \cs_set_protected:Npn \__enumext_tmp:n ##1
2363     {
2364       \tl_set_eq:cc { \__enumext_label_copy_##1_tl } { \__enumext_label_##1_tl }
2365       \tl_reverse:c { \__enumext_label_copy_##1_tl }
2366       \tl_remove_once:cn { \__enumext_label_copy_##1_tl } { . }
2367       \tl_reverse:c { \__enumext_label_copy_##1_tl }
2368     }
2369     \clist_map_inline:nn { i, v, vi, vii, viii } { \__enumext_tmp:n {##1} }
2370     \__enumext_keyans_store_ref_aux_i:
2371   }
2372 }

```

The auxiliary function `\__enumext_keyans_store_ref_aux_i:` set the variable `\__enumext_newlabel_arg_one_tl` which will contain `{<store name : position>}` analyzing whether the environment in which they are executed is `enumext*` or `enumext`.

```

2373 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_i:
2374 {
2375   \bool_if:NT \g__enumext_starred_bool
2376   {
2377     \tl_set_eq:NN \__enumext_label_copy_i_tl \__enumext_label_copy_vii_tl
2378   }
2379   \int_compare:nNnT { \__enumext_keyans_pic_level_int } = { 1 }
2380   {
2381     \tl_put_right:Ne \__enumext_newlabel_arg_two_tl
2382     { \__enumext_label_copy_i_tl . \__enumext_label_copy_vi_tl }
2383   }
2384   \int_compare:nNnT { \__enumext_keyans_level_int } = { 1 }
2385   {
2386     \tl_put_right:Ne \__enumext_newlabel_arg_two_tl
2387     { \__enumext_label_copy_i_tl . \__enumext_label_copy_v_tl }
2388   }
2389   \int_compare:nNnT { \__enumext_keyans_level_h_int } = { 1 }
2390   {
2391     \tl_put_right:Ne \__enumext_newlabel_arg_two_tl
2392     { \__enumext_label_copy_i_tl . \__enumext_label_copy_viii_tl }

```

```

2393     }
2394     \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
2395     {
2396         \l__enumext_store_name_tl \c_colon_str
2397         \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
2398     }
2399     \__enumext_keyans_store_ref_aux_ii:
2400 }

```

Now auxiliary function `\__enumext_keyans_store_ref_aux_ii:` save the result in the variable `\l__enumext_store_write_aux_file_tl` and finally we write in the `.aux` file.

```

2401 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_ii:
2402 {
2403     \tl_put_right:Ne \l__enumext_store_write_aux_file_tl
2404     {
2405         \__enumext_newlabel:nn
2406         { \exp_not:V \l__enumext_newlabel_arg_one_tl }
2407         { \l__enumext_newlabel_arg_two_tl }
2408     }
2409     \l__enumext_store_write_aux_file_tl
2410 }

```

(End of definition for `\__enumext_keyans_store_ref:`, `\__enumext_keyans_store_ref_aux_i:`, and `\__enumext_keyans_store_ref_aux_ii:`.)

### 10.25.3 Storing content in sequence

`\__enumext_keyans_addto_seq:n`  
`\__enumext_keyans_addto_seq_link:`

The function `\__enumext_keyans_addto_seq:n` will pass the contents of the current *⟨label⟩* `\l__enumext_label_v_tl` for the `keyans` environment and the `\l__enumext_label_vi_tl` for the `keyanspic` environment when using `\item*` and `\anspic*`, followed by the *⟨contents⟩* of the optional argument of both commands to the `\l__enumext_store_keyans_label_tl` variable to the sequence defined by the `save-ans` key.

```

2411 \cs_new_protected:Npn \__enumext_keyans_addto_seq:n #1
2412 {
2413     \tl_clear:N \l__enumext_store_keyans_label_tl
2414     \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
2415     {
2416         \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \item \l__enumext_label_vi_tl }
2417     }
2418     {
2419         \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \item \l__enumext_label_v_tl }
2420     }
2421     \tl_if_novalue:nF { #1 }
2422     {
2423         \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_tl
2424         {
2425             \tl_put_right:Ne \l__enumext_store_keyans_label_tl
2426             {
2427                 \l__enumext_store_keyans_item_opt_sep_tl
2428             }
2429         }
2430         \tl_put_right:Ne \l__enumext_store_keyans_label_tl { #1 }
2431     }
2432     \__enumext_keyans_addto_seq_link:
2433 }

```

Checks if the `save-ref` key is active along with the `hyperref` package load, if both conditions are met, it will create the `\hyperlink` and then store using the `\__enumext_store_addto_seq:V` function. Finally, copy the contents of the variable `\l__enumext_store_keyans_label_tl` into the global variable `\g__enumext_check_ans_item_tl` to be used by the function `\__enumext_check_starred_cmd:n` and increment the value of the integer variable `\g__enumext_item_anskey_int` handled by the `check-ans` key.

```

2434 \cs_new_protected:Nn \__enumext_keyans_addto_seq_link:
2435 {
2436     \bool_lazy_and:nnT
2437     { \bool_if_p:N \l__enumext_store_ref_key_bool }
2438     { \bool_if_p:N \l__enumext_hyperref_bool }
2439     {
2440         \tl_put_right:Ne \l__enumext_store_keyans_label_tl
2441         {
2442             \hfill \exp_not:N \hyperlink
2443             {

```

```

2444         \exp_not:V \l__enumext_newlabel_arg_one_tl
2445     }
2446     { \exp_not:V \l__enumext_mark_ref_sym_tl }
2447 }
2448 }
2449 \__enumext_store_addto_seq:V \l__enumext_store_keyans_label_tl
2450 \bool_if:NT \l__enumext_check_answers_bool
2451 {
2452     \int_gincr:N \g__enumext_item_anskey_int
2453 }
2454 }

```

(End of definition for `\__enumext_keyans_addto_seq:n` and `\__enumext_keyans_addto_seq_link:.`)

#### 10.25.4 The show-ans and show-pos keys for keyans and keyanspic

The code is very similar to the `\anskey` code, but, if I change the order of the operations the counter off `⟨label⟩` are incorrect.

Common function to show *starred commands* `\item*` and `⟨position⟩` of stored content in `⟨prop list⟩` for `keyans` and `keyanspic`. Need add `1` to `\g__enumext_⟨store name⟩_prop` for `show-pos` key.

```

\__enumext_keyans_show_left:n
\__enumext_keyans_show_ans:
\__enumext_keyans_show_pos:
\__enumext_keyans_show_item_opt:
2455 \cs_new_protected:Npn \__enumext_keyans_show_left:n #1
2456 {
2457     \tl_if_novalue:nF { #1 }
2458     {
2459         \tl_set:Nc \l__enumext_keyans_item_opt_tl { #1 }
2460     }
2461     \bool_if:NT \l__enumext_show_answer_bool
2462     {
2463         \__enumext_keyans_show_ans:
2464     }
2465     \bool_if:NT \l__enumext_show_position_bool
2466     {
2467         \__enumext_keyans_show_pos:
2468     }
2469 }
2470 \cs_new_protected:Nn \__enumext_keyans_show_item_opt:
2471 {
2472     \tl_if_empty:NF \l__enumext_keyans_item_opt_tl
2473     {
2474         \bool_lazy_or:nnT
2475         { \bool_if_p:N \l__enumext_show_answer_bool }
2476         { \bool_if_p:N \l__enumext_show_position_bool }
2477         {
2478             \__enumext_keyans_wrapper_opt:n { \l__enumext_keyans_item_opt_tl } \c_space_tl
2479         }
2480     }
2481 }
2482 \cs_new_protected:Nn \__enumext_keyans_show_ans:
2483 {
2484     \tl_put_left:Nn \l__enumext_label_v_tl
2485     {
2486         \__enumext_print_keyans_box:NN
2487         \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
2488     }
2489 }
2490 \cs_new_protected:Nn \__enumext_keyans_show_pos:
2491 {
2492     \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
2493     {
2494         \tl_set:Nc \l__enumext_mark_answer_sym_tl
2495         {
2496             \group_begin:
2497             \exp_not:N \normalfont
2498             \exp_not:N \footnotesize [ \int_eval:n
2499             {
2500                 \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
2501             }
2502             ]
2503             \group_end:
2504         }
2505     }

```

```

2506     {
2507         \tl_set:Nc \l__enumext_mark_answer_sym_tl
2508         {
2509             \group_begin:
2510             \exp_not:N \normalfont
2511             \exp_not:N \footnotesize [ \int_eval:n
2512             {
2513                 \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } + 1
2514             }
2515             ]
2516             \group_end:
2517         }
2518     }
2519     \tl_put_left:Nn \l__enumext_label_v_tl
2520     {
2521         \__enumext_print_keyans_box:NN
2522         \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
2523     }
2524 }

```

(End of definition for `\__enumext_keyans_show_left:n` and others.)

## 10.26 Setting `item-sym*` and `item-pos*` keys

In order to have a cleaner implementation of `\item*` it is best to define a couple of keys that allow us to control and set by default the *symbol* and its *offset*.

`item-sym*` Define and set `item-sym*` and `item-pos*` keys for `enumext` and `enumext*`.

```

2525 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
2526 {
2527     \keys_define:nn { enumext / #1 }
2528     {
2529         item-sym* .tl_set:c = { \l__enumext_item_symbol_#2_tl },
2530         item-sym* .value_required:n = true,
2531         item-sym* .initial:n = { $\star$ },
2532         item-pos* .dim_set:c = { \l__enumext_item_symbol_sep_#2_dim },
2533         item-pos* .value_required:n = true,
2534     }
2535 }
2536 \clist_map_inline:nn
2537 {
2538     {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {enumext*}{vii}
2539 }
2540 { \__enumext_tmp:nn #1 }

```

(End of definition for `item-sym*` and `item-pos*`.)

## 10.27 Redefining `\footnote` command

`\__enumext_footnotetext:nn` To keep the correct numbering of `\footnote` and to make it work correctly with the `mini-env` key and in the `enumext*` and `keyans*` environments, it is necessary to redefine the command. This implementation is adapted from the answer given by Clea F. Rees (@cfr) in [footnotes in boxes compatible with hyperref](#).

`\__enumext_renew_footnote:`

`\__enumext_print_footnote:`

```

2541 \cs_new_protected:Nn \__enumext_footnotetext:nn
2542 {
2543     \footnotetext[#1]{#2}
2544 }
2545 \cs_new_protected:Nn \__enumext_renew_footnote:
2546 {
2547     \seq_gclear:N \g__enumext_footnote_arg_seq
2548     \seq_gclear:N \g__enumext_footnote_int_seq
2549     \RenewDocumentCommand \footnote { o +m }
2550     {
2551         \tl_if_novalue:nTF {##1}
2552         {
2553             \stepcounter{footnote}
2554             \int_gset_eq:Nc \g__enumext_footnote_int { c@footnote }
2555         }
2556         {
2557             \int_gset:Nn \g__enumext_footnote_int { ##1 }
2558         }
2559         \footnotemark [ \g__enumext_footnote_int ]
2560         \seq_gput_right:Nn \g__enumext_footnote_arg_seq { ##2 }

```



```

2561     \seq_gput_right:NV \g__enumext_footnote_int_seq \g__enumext_footnote_int
2562   }
2563 }
2564 \cs_new_protected:Nn \__enumext_print_footnote:
2565 {
2566   \seq_if_empty:NF \g__enumext_footnote_int_seq
2567   {
2568     \seq_map_pairwise_function:NNN
2569       \g__enumext_footnote_int_seq
2570       \g__enumext_footnote_arg_seq
2571       \__enumext_footnotetext:nn
2572   }
2573 }

```

(End of definition for \\_\_enumext\_footnotetext:nn, \\_\_enumext\_renew\_footnote:, and \\_\_enumext\_print\_footnote:.)

## 10.28 Redefining \item command

Redefining the `\item` command is not as simple as I thought. This command works in conjunction with the `\makeatlabel` command so I have to redefine both of them, in addition to this, we will have to use a couple of *global* variables to pass the values from one command to the other.

### 10.28.1 The \item command in enumext

`\__enumext_default_item:n` The `\item` and `\item[⟨custom⟩]` commands work in the usual way on `enumext`.

First we will see if the optional argument is present, if it is NOT present we will check the state of the variable `\l__enumext_check_ans_key_bool` set by the key `check-ans`, set the boolean variable `\l__enumext_wrap_label_X_bool` to “true” and execute `\__enumext_item_std:w`.

Otherwise we will check the state of the boolean variable `\l__enumext_wrap_label_opt_X_bool` set by the key `wrap-label*` and execute `\__enumext_item_std:w` with the optional argument.

The boolean variable `\l__enumext_wrap_label_X_bool` is used by the function `\__enumext_make_label: (§10.29)`.

```

2574 \cs_new_protected:Npn \__enumext_default_item:n #1
2575 {
2576   \tl_if_novalue:nTF {#1}
2577   {
2578     \bool_if:NT \l__enumext_check_answers_bool
2579     {
2580       \int_gincr:N \g__enumext_item_number_int
2581     }
2582     \bool_set_true:c { \l__enumext_wrap_label_ \__enumext_level: _bool }
2583     \__enumext_item_std:w \tl_use:c { \l__enumext_fake_item_indent_ \__enumext_level: _tl }
2584   }
2585   {
2586     \bool_set_eq:cc
2587     { \l__enumext_wrap_label_ \__enumext_level: _bool }
2588     { \l__enumext_wrap_label_opt_ \__enumext_level: _bool }
2589     \__enumext_item_std:w [#1] \tl_use:c { \l__enumext_fake_item_indent_ \__enumext_level: _tl }
2590   }
2591 }

```

(End of definition for \\_\_enumext\_default\_item:n.)

`\__enumext_starred_item:nn` The `\item*`, `\item*[⟨symbol⟩]` and `\item*[⟨symbol⟩][⟨offset⟩]` works like the numbered `\item`, but placing a `[⟨symbol⟩]` to the “left” of the `⟨label⟩` separated from it by the value set by the `labelsep` key and can be *offset* using the second optional argument `[⟨offset⟩]`.

`#1: \l__enumext_item_symbol_X_tl`

`#2: \l__enumext_item_symbol_sep_X_dim`

First we will make a copy of `\l__enumext_item_symbol_X_tl` which is set by the key `item-sym*` or passed as optional argument in the global variable `\g__enumext_item_symbol_tl`, followed by setting the variable `\l__enumext_item_symbol_sep_X_dim` set by the key `item*-sep` or by the second optional argument.

Then we will see the state of the variable `\l__enumext_check_ans_key_bool` set by the key `check-ans`, set the boolean variable `\l__enumext_wrap_label_X_bool` to “true” and execute `\__enumext_item_std:w`.

In this function the optional argument of `\__enumext_item_std:w` is omitted, we only want it to be numbered.

The boolean variable `\l__enumext_wrap_label_X_bool` and the vars `\l__enumext_item_symbol_sep_X_dim`, `\g__enumext_item_symbol_tl` are used by the function `\__enumext_make_label:` (§10.29).

```

2592 \cs_new_protected:Npn \__enumext_starred_item:nn #1 #2
2593 {
2594   \tl_if_novalue:nF {#1}
2595   {
2596     \tl_set:cn { \l__enumext_item_symbol_ \__enumext_level: _tl } {#1}
2597   }
2598   \tl_gset_eq:Nc \g__enumext_item_symbol_tl { \l__enumext_item_symbol_ \__enumext_level: _tl }
2599   \tl_if_novalue:nTF {#2}
2600   {
2601     \dim_set_eq:cc
2602     { \l__enumext_item_symbol_sep_ \__enumext_level: _dim }
2603     { \l__enumext_labelsep_ \__enumext_level: _dim }
2604   }
2605   {
2606     \dim_set:cn { \l__enumext_item_symbol_sep_ \__enumext_level: _dim } {#2}
2607   }
2608   \bool_if:NT \l__enumext_check_answers_bool
2609   {
2610     \int_gincr:N \g__enumext_item_number_int
2611   }
2612   \bool_set_true:c { \l__enumext_wrap_label_ \__enumext_level: _bool }
2613   \__enumext_item_std:w \tl_use:c { \l__enumext_fake_item_indent_ \__enumext_level: _tl }
2614 }

```

(End of definition for `\__enumext_starred_item:nn`.)

`\__enumext_redefine_item:` The function `\__enumext_redefine_item:` will redefine the `\item` command in the `enumext` environment for the internal mechanism of check-answers for `check-ans` key and adding the starred `\item*` version.

This function is passed to `\__enumext_list_arg_two_X:` which is used in the definition of the `enumext` environment (§10.30.2).

```

2615 \cs_new_protected:Npn \__enumext_redefine_item:
2616 {
2617   \RenewDocumentCommand \item { s o o }
2618   {
2619     \bool_if:nTF {##1}
2620     {
2621       \__enumext_starred_item:nn {##2} {##3}
2622     }
2623     { \__enumext_default_item:n {##2} }
2624   }
2625 }

```

(End of definition for `\__enumext_redefine_item:.`)

### 10.28.2 The `\item` command in keyans

The `\item*` and `\item*[\langle content \rangle]` commands *store* the current *label* next to the `[\langle content \rangle]` if it is present in the *sequence* and *prop list* defined by `save-ans` key.

`\__enumext_keyans_default_item:n` The function `\__enumext_keyans_default_item:n` executes the original behavior of the `\item`.

```

2626 \cs_new_protected:Npn \__enumext_keyans_default_item:n #1
2627 {
2628   \tl_if_novalue:nTF { #1 }
2629   {
2630     \bool_set_true:N \l__enumext_wrap_label_v_bool
2631     \__enumext_item_std:w \tl_use:N \l__enumext_fake_item_indent_v_tl
2632   }
2633   {
2634     \bool_set_eq:NN \l__enumext_wrap_label_v_bool \l__enumext_wrap_label_opt_v_bool
2635     \__enumext_item_std:w [#1] \tl_use:N \l__enumext_fake_item_indent_v_tl
2636   }
2637 }

```

(End of definition for `\__enumext_keyans_default_item:n`.)

`\__enumext_keyans_starred_item:n`

The function `\__enumext_keyans_starred_item:n` which will make a temporary copy of the current `<label>`, execute the `show-ans` or `show-pos` keys using the function `\__enumext_keyans_show_left:n` and will display the contents of that item using the internal copy `\__enumext_item_std:w`, this is necessary to prevent incrementing the current “*counter*” of the original `<label>`.

```
2638 \cs_new_protected:Npn \__enumext_keyans_starred_item:n #1
2639 {
2640   \tl_set_eq:NN \l__enumext_keyans_tmpa_tl \l__enumext_label_v_tl
2641   \__enumext_keyans_show_left:n { #1 }
2642   \bool_set_true:N \l__enumext_wrap_label_v_bool
2643   \__enumext_item_std:w \tl_use:N \l__enumext_fake_item_indent_v_tl \__enumext_keyans_show_item:
```

Recover the original value of the current `<label>` and *store* it first in the `<prop list>` (including the optional argument), run the internal “*label and ref*” system if the `save-ref` key is active and finally *store* it in the `<sequence>`.

```
2644   \tl_set_eq:NN \l__enumext_label_v_tl \l__enumext_keyans_tmpa_tl
2645   \__enumext_keyans_addto_prop:n { #1 }
2646   \__enumext_keyans_store_ref:
2647   \__enumext_keyans_addto_seq:n { #1 }
2648   \int_gincr:N \g__enumext_check_starred_cmd_int
2649 }
```

(End of definition for `\__enumext_keyans_starred_item:n`.)

`\item*`  
`\__enumext_keyans_redefine_item:`

The function `\__enumext_keyans_redefine_item:` is responsible for adding the *starred* and *optional* argument by the `\__enumext_list_arg_two_v:` function in the definition of the `keyans` environment. Here we need to use `\peek_remove_spaces:n` to prevent an unwanted space when using `\item*` in conjunction with the `itemindent` key.

This function is passed to `\__enumext_list_arg_two_v:` which is used in the definition of the `keyans` environment (§10.30.2).

```
2650 \cs_new_protected:Npn \__enumext_keyans_redefine_item:
2651 {
2652   \RenewDocumentCommand \item { s o }
2653   {
2654     \bool_if:nTF {##1}
2655     {
2656       \peek_remove_spaces:n
2657       {
2658         \__enumext_keyans_starred_item:n {##2}
2659       }
2660     }
2661     {
2662       \__enumext_keyans_default_item:n {##2}
2663     }
2664   }
2665 }
```

(End of definition for `\item*` and `\__enumext_keyans_redefine_item:`. This function is documented on page 11.)

## 10.29 Redefining `\makeLabel` command

Redefine `\makeLabel` for the keys `align`, `font`, `wrap-label`, `wrap-label*` and `\item*` for `enumext` and `keyans` environments.

### 10.29.1 Redefining `\makeLabel` for `enumext`

`\__enumext_item_starred:`

The function `\__enumext_item_starred:` will be responsible for executing `\item*` for the `enumext` environment.

```
2666 \cs_new_protected:Npn \__enumext_item_starred:
2667 {
2668   \tl_if_empty:cF { \l__enumext_item_symbol_ \l__enumext_level: _tl }
2669   {
2670     \mode_leave_vertical:
2671     \skip_horizontal:n { -\dim_use:c { \l__enumext_item_symbol_sep_ \l__enumext_level: _dim } }
2672     \makebox[ \opt ][ r ]{ \g__enumext_item_symbol_tl }
2673     \skip_horizontal:n { \dim_use:c { \l__enumext_item_symbol_sep_ \l__enumext_level: _dim } }
2674   }
2675 }
```

(End of definition for `\__enumext_item_starred:`.)

`\__enumext_make_label:` The function `\__enumext_make_label:` redefine `\makelabel` for the `enumext` environment. This function is passed to `\__enumext_list_arg_two_X:` which is used in the definition of the `enumext` environment (§10.30.2).

```

2676 \cs_new_protected:Nn \__enumext_make_label:
2677 {
2678   \RenewDocumentCommand \makelabel { m }
2679   {
2680     \tl_use:c { \__enumext_label_fill_left_ \__enumext_level: _tl }
2681     \tl_use:c { \__enumext_label_font_style_ \__enumext_level: _tl }
2682     \bool_if:cTF { \__enumext_wrap_label_ \__enumext_level: _bool }
2683     {
2684       \__enumext_item_starred:
2685       \use:c { \__enumext_wrapper_label_ \__enumext_level: :n } { ##1 }
2686     }
2687     { ##1 }
2688     \tl_use:c { \__enumext_label_fill_right_ \__enumext_level: _tl }
2689     \tl_gclear:N \g__enumext_item_symbol_tl
2690   }
2691 }

```

(End of definition for `\__enumext_make_label:`)

### 10.29.2 Redefining `\makelabel` for `keyans`

`\__enumext_keyans_make_label:` The function `\__enumext_keyans_make_label:` redefine `\makelabel` for `keyans` environment. This function is passed to `\__enumext_list_arg_two_v:` which is used in the definition of the `keyans` environment (§10.30.2).

```

2692 \cs_new_protected:Nn \__enumext_keyans_make_label:
2693 {
2694   \RenewDocumentCommand \makelabel { m }
2695   {
2696     \tl_use:N \l__enumext_label_fill_left_v_tl
2697     \tl_use:N \l__enumext_label_font_style_v_tl
2698     \bool_if:NTF \l__enumext_wrap_label_v_bool
2699     {
2700       \__enumext_wrapper_label_v:n { ##1 }
2701     }
2702     { ##1 }
2703     \tl_use:N \l__enumext_label_fill_right_v_tl
2704   }
2705 }

```

(End of definition for `\__enumext_keyans_make_label:`)

## 10.30 Second argument of the lists

At this point of the code we have already programmed most the necessary tools to create a custom `list` environment, remember that the function `\__enumext_start_list:nn` takes two arguments, the first one we have ready, the second one we will define for all the levels of the environment `enumext` and the environment `keyans`.

### 10.30.1 Calculation of `\leftmargin` and `\itemindent`

Consider the figure 9 where the default margins (on the left) of a list are represented.






Figure 9: Representation of standard horizontal lengths in `list` environment.

The idea is to have control over these margins so that our list does not overlap the left margin of the page. The *key* relationship is that the right edge of the `\labelsep` equals the right edge of the `\itemindent`, so that the left edge of the *label box* is at  $\backslash\leftmargin + \backslash\itemindent$  minus  $\backslash\labelwidth + \backslash\labelsep$ . Thus, the handling of the margins by the package will be as shown in the figure 10. Where the default values will look like in the figure 11.

`\__enumext_calc_hspace:NNNNNNN` The function `\__enumext_calc_hspace:NNNNNNN` takes seven arguments to be able to determine horizontal spaces for all list environment:  
`\__enumext_calc_hspace:ccccccc`

Figure 10: Representation of horizontal lengths concept in list in `enumext`.Figure 11: Default horizontal lengths in `enumext`.

```

#1: \l__enumext_labelwidth_X_dim      #2: \l__enumext_labelsep_X_dim
#3: \l__enumext_listoffset_X_dim      #4: \l__enumext_leftmargin_tmp_X_dim
#5: \l__enumext_leftmargin_X_dim      #6: \l__enumext_itemindent_X_dim
#7: \l__enumext_leftmargin_tmp_X_bool

```

And returns the “adjusted” values of `\leftmargin` and `\itemindent`.

This function is passed to `\__enumext_list_arg_two_X`: which is used in the definition of the `enumext` and `keyans` environments (§10.30.2).

```

2706 \cs_new_protected:Npn \__enumext_calc_hspace:NNNNNN #1 #2 #3 #4 #5 #6 #7
2707 {
2708   \dim_compare:nNnT { #1 } < { \c_zero_dim }
2709   {
2710     \msg_warning:nnnV { enumext } { width-non-positive } { labelwidth } { #1 }
2711     \dim_set:Nn #1 { \dim_abs:n { #1 } }
2712   }
2713   \dim_compare:nNnT { #2 } < { \c_zero_dim }
2714   {
2715     \msg_warning:nnnV { enumext } { width-negative } { labelsep } { #2 }
2716     \dim_set:Nn #2 { \dim_abs:n { #2 } }
2717   }

```

If no value has been passed to the `labelwidth` and `labelsep` keys we set the default values for `\l__enumext_leftmargin_tmp_X_dim`.

```

2718   \bool_if:nF #7 { \dim_set:Nn #4 { #1 + #2 } }

```

We now analyze the cases and set the values for `\leftmargin` and `\itemindent`.

```

2719   \dim_compare:nNnTF { #4 } < { \c_zero_dim }
2720   {
2721     \dim_set:Nn #6 { #1 + #2 - #4 }
2722     \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
2723   }
2724   {
2725     \dim_compare:nNnT { #4 } = { #1 + #2 }
2726     { \dim_set:Nn #6 { \c_zero_dim } }
2727     \dim_compare:nNnT { #4 } < { #1 + #2 }
2728     { \dim_set:Nn #6 { #1 + #2 - #4 } }
2729     \dim_compare:nNnT { #4 } > { #1 + #2 }
2730     {
2731       \dim_set:Nn #6 { -#1 - #2 + #4 }
2732       \dim_set:Nn #6 { #6*-1 }
2733     }
2734     \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
2735   }
2736 }
2737 \cs_generate_variant:Nn \__enumext_calc_hspace:NNNNNN { ccccccc }

```

(End of definition for `\__enumext_calc_hspace:NNNNNN`.)

### 10.30.2 Setting second argument of the lists

We will “not set” `\leftmargini`, `\leftmarginii`, `\leftmarginiii` or `\leftmarginiv`, in this case, we will directly set the parameters for vertical and horizontal list spacing per level.

```

2738 \cs_set_protected:Npn \__enumext_tmp:n #1
2739 {
2740   \cs_new_protected:cpn { __enumext_list_arg_two_#1: }
2741   {
2742     \__enumext_calc_hspace:cccccc
2743     { \__enumext_labelwidth_#1_dim } { \__enumext_labelsep_#1_dim }
2744     { \__enumext_listoffset_#1_dim } { \__enumext_leftmargin_tmp_#1_dim }
2745     { \__enumext_leftmargin_#1_dim } { \__enumext_itemindent_#1_dim }
2746     { \__enumext_leftmargin_tmp_#1_bool }
2747     \clist_map_inline:nn
2748     { labelsep, labelwidth, itemindent, leftmargin, rightmargin, listparindent }
2749     { \dim_set_eq:cc {###1} { \__enumext_###1_#1_dim } }
2750     \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
2751     { \skip_set_eq:cc {###1} { \__enumext_###1_#1_skip } }
2752     \usecounter { enumX#1 }
2753     \setcounter { enumX#1 } { \int_eval:n { \int_use:c { \__enumext_start_#1_int } - 1 } }
2754     \str_if_eq:nnTF {#1} { v }
2755     {
2756       \__enumext_keyans_redefine_item:
2757       \__enumext_keyans_make_label:
2758       \__enumext_keyans_ref:
2759       \__enumext_keyans_fake_item:
2760       \bool_if:cT { \__enumext_show_length_#1_bool }
2761       {
2762         \msg_term:nnnn { enumext } { list-lengths-not-nested } { v } { keyans }
2763       }
2764     }
2765     {
2766       \__enumext_redefine_item:
2767       \__enumext_make_label:
2768       \__enumext_standar_ref:
2769       \__enumext_fake_item:
2770       \bool_if:cT { \__enumext_show_length_#1_bool }
2771       {
2772         \msg_term:nnne { enumext } { list-lengths } {#1} { \int_use:N \__enumext_level_int }
2773       }
2774     }
2775   }
2776 }
2777 \clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }

```

(End of definition for `\__enumext_list_arg_two_i:` and others.)

For the horizontal environments `enumext*` and `keyans*` the implementation is similar, but, the value of `\partopsep` is always `\opt`. At this point we will modify the `parsep` key to make it take the value of the `itemsep` key and later, in the environment definition, we will modify `parindent` to make it set the value of `\listparindent` and `parsep` to set the value of `\parskip` locally.

```

2778 \cs_set_protected:Npn \__enumext_tmp:n #1
2779 {
2780   \cs_new_protected:cpn { __enumext_list_arg_two_#1: }
2781   {
2782     \__enumext_calc_hspace:cccccc
2783     { \__enumext_labelwidth_#1_dim } { \__enumext_labelsep_#1_dim }
2784     { \__enumext_listoffset_#1_dim } { \__enumext_leftmargin_tmp_#1_dim }
2785     { \__enumext_leftmargin_#1_dim } { \__enumext_itemindent_#1_dim }
2786     { \__enumext_leftmargin_tmp_#1_bool }
2787     \clist_map_inline:nn
2788     { labelsep, labelwidth, itemindent, leftmargin, rightmargin, listparindent }
2789     { \dim_set_eq:cc {###1} { \__enumext_###1_#1_dim } }
2790     \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
2791     { \skip_set_eq:cc {###1} { \__enumext_###1_#1_skip } }
2792     \skip_set_eq:Nc \parsep { \__enumext_itemsep_#1_skip }
2793     \skip_zero:N \partopsep
2794     \usecounter { enumX#1 }
2795     \setcounter { enumX#1 } { \int_eval:n { \int_use:c { \__enumext_start_#1_int } - 1 } }
2796     \__enumext_starred_ref:
2797     \str_if_eq:nnTF {#1} { vii }

```

```

2798     {
2799         \__enumext_fake_item_vii:
2800         \bool_if:cT { l__enumext_show_length_vii_bool }
2801         { \msg_term:nnnn { enumext } { list-lengths-not-nested } { vii } { enumext* } }
2802     }
2803     {
2804         \__enumext_fake_item_viii:
2805         \bool_if:cT { l__enumext_show_length_#1_bool }
2806         { \msg_term:nnnn { enumext } { list-lengths-not-nested } { #1 } { keyans* } }
2807     }
2808 }
2809 }
2810 \clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for \\_\_enumext\_list\_arg\_two\_vii: and \\_\_enumext\_list\_arg\_two\_viii:.)

### 10.31 The environment enumext

**enumext** We create the **enumext** environment based on **list** environment by levels.

```

2811 \NewDocumentEnvironment{enumext}{0}{}
2812 {
2813     \__enumext_safe_exec:
2814     \__enumext_parse_keys:n {#1}
2815     \__enumext_before_list:
2816     \__enumext_start_store_level:
2817     \__enumext_start_list:nn
2818     { \tl_use:c { l__enumext_label_ \__enumext_level: _tl } }
2819     {
2820         \use:c { __enumext_list_arg_two_ \__enumext_level: : }
2821         \__enumext_before_keys_exec:
2822     }
2823     \__enumext_after_args_exec:
2824 }
2825 {
2826     \__enumext_stop_list:
2827     \__enumext_stop_store_level:
2828     \__enumext_after_list:
2829 }

```

(End of definition for enumext. This function is documented on page 4.)

**\\_\_enumext\_safe\_exec:** The **\\_\_enumext\_safe\_exec:** function first execute the function **\\_\_enumext\_is\_not\_nested:** which will set the variable **\g\_\_enumext\_standard\_bool** to “true” if the environment is not nested in **enumext\***, we increment the variable **\l\_\_enumext\_level\_int** for the nesting levels and set the **\l\_\_enumext\_standard\_bool** variable to “true”. Finally we set the variable **\l\_\_enumext\_standar\_first\_bool** to “true” only if the environment is not nested and we are at the “first level” of it using the function **\\_\_enumext\_is\_on\_first\_level:**.

```

2830 \cs_new_protected:Nn \__enumext_safe_exec:
2831 {
2832     \__enumext_is_not_nested:
2833     \int_incr:N \l__enumext_level_int
2834     \int_compare:nNnT { \l__enumext_level_int } > { 4 }
2835     { \msg_fatal:nn { enumext } { list-too-deep } }
2836     \bool_set_true:N \l__enumext_standar_bool
2837     \__enumext_is_on_first_level:
2838 }

```

(End of definition for \\_\_enumext\_safe\_exec:.)

**\\_\_enumext\_parse\_keys:n** The **\\_\_enumext\_parse\_store\_keys:n** function will parse the **<keys>** passed to the optional environment argument **enumext** by levels only if present. First we clear the variable **\l\_\_enumext\_series\_str** and then we check if we are at the first level, if so we process the **<keys>** and then execute the function **\\_\_enumext\_parse\_series:n** used by the key **series**, otherwise we will pass the **<keys>** to the inner levels of the environment and finally if the variable **\l\_\_enumext\_store\_active\_bool** established by the key **save-ans** is true we execute **\\_\_enumext\_parse\_store\_keys:n** used by the key **save-key**.

```

2839 \cs_new_protected:Npn \__enumext_parse_keys:n #1
2840 {
2841     \tl_if_novalue:nF {#1}
2842     {
2843         \str_clear:N \l__enumext_series_str
2844         \int_compare:nNnTF { \l__enumext_level_int } = { 1 }

```



```

2845     {
2846       \keys_set:nn { enumext / level-1 } {#1}
2847       \__enumext_parse_series:n {#1}
2848     }
2849     {
2850       \exp_args:Ne \keys_set:nn
2851       { enumext / level-\int_use:N \l__enumext_level_int } {#1}
2852     }
2853   \bool_if:NT \l__enumext_store_active_bool
2854   {
2855     \__enumext_parse_store_keys:n {#1}
2856   }
2857 }
2858 }

```

(End of definition for \\_\_enumext\_parse\_keys:n.)

\\_\_enumext\_parse\_store\_keys:n

The function \\_\_enumext\_parse\_store\_keys:n searches for the values of the `columns` and `columns-sep` keys in the optional arguments per-level in `enumext` environment as long as the starred versions of the `columns*` and `columns-sep*` keys are not active. The captured values are stored in the variable `\l__enumext_store_opt_X_tl` which is used by the function `\__enumext_store_level_open:`.

```

2859 \cs_new_protected:Npn \__enumext_parse_store_keys:n #1
2860 {
2861   \bool_if:cF { l__enumext_store_columns_ \__enumext_level: _bool }
2862   {
2863     \regex_match:nnT { \b columns\b } {#1}
2864     {
2865       \int_set_eq:cc
2866       { l__enumext_store_columns_ \__enumext_level: _int }
2867       { l__enumext_columns_ \__enumext_level: _int }
2868       \tl_put_right:ce { l__enumext_store_opt_ \__enumext_level: _tl }
2869       {
2870         columns = \exp_not:v { l__enumext_store_columns_ \__enumext_level: _int },
2871       }
2872     }
2873   }
2874   \bool_if:cF { l__enumext_store_columns_sep_ \__enumext_level: _bool }
2875   {
2876     \regex_match:nnT { \b columns-sep\b } {#1}
2877     {
2878       \dim_set_eq:cc
2879       { l__enumext_store_columns_sep_ \__enumext_level: _dim }
2880       { l__enumext_columns_sep_ \__enumext_level: _dim }
2881       \tl_put_right:ce { l__enumext_store_opt_ \__enumext_level: _tl }
2882       {
2883         columns-sep = \exp_not:v { l__enumext_store_columns_sep_ \__enumext_level: _dim }
2884       }
2885     }
2886   }
2887 }

```

(End of definition for \\_\_enumext\_parse\_store\_keys:n.)

\\_\_enumext\_start\_store\_level:

\\_\_enumext\_stop\_store\_level:

The `\__enumext_start_store_level:` and `\__enumext_stop_store_level:` functions activate the level saving mechanism for storage in *sequence* of the `\anskey` command.

If `enumext` are nested in `enumext*` add `\__enumext_store_level_open:` to preserve the stored structure.

```

2888 \cs_new_protected:Nn \__enumext_start_store_level:
2889 {
2890   \bool_lazy_all:nT
2891   {
2892     { \bool_if_p:N \l__enumext_store_active_bool }
2893     { \bool_not_p:n { \l__enumext_keyans_env_bool } }
2894     { \bool_not_p:n { \g__enumext_starred_bool } }
2895   }
2896   {
2897     \int_compare:nNnT { \l__enumext_level_int } > { 1 }
2898     {
2899       \bool_set_true:c { l__enumext_store_upper_level_ \__enumext_level: _bool }
2900       \__enumext_store_level_open:
2901     }
2902   }

```

```

2902     }
2903     \bool_lazy_all:nT
2904     {
2905         { \bool_if_p:N \l__enumext_store_active_bool }
2906         { \bool_not_p:n { \l__enumext_keyans_env_bool } }
2907         { \bool_if_p:N \g__enumext_starred_bool }
2908     }
2909     {
2910         \int_compare:nNnT { \l__enumext_level_int } > { 0 }
2911         {
2912             \bool_set_true:c { l__enumext_store_upper_level_ \__enumext_level: _bool }
2913             \__enumext_store_level_open:
2914         }
2915     }
2916 }
2917 \cs_new_protected:Nn \__enumext_stop_store_level:
2918 {
2919     \bool_if:cT { l__enumext_store_upper_level_ \__enumext_level: _bool }
2920     {
2921         \__enumext_store_level_close:
2922     }
2923 }

```

(End of definition for \\_\_enumext\_start\_store\_level: and \\_\_enumext\_stop\_store\_level:.)

`\__enumext_before_list:` The function `\__enumext_before_list:` will add the vertical spacing on the environment if the `above` key is active next to the `{\code}` defined by the `before*` key if it is active.

```

2924 \cs_new_protected:Nn \__enumext_before_list:
2925 {
2926     \__enumext_vspace_above:
2927     \__enumext_before_args_exec:

```

The function `\__enumext_check_ans_active:` will handle the check answer mechanism, which will be activated with the `check-ans` key.

```

2928     \__enumext_check_ans_active:

```

When the `mini-env` key is active it will set the value of the `\l__enumext_minipage_right_X_dim` to be the *width* of the `\__enumext_mini_env*` environment on the “right side”, using this value together with the value of the `\l__enumext_minipage_hsep_X_dim` set by the `mini-sep` key, the value of `\l__enumext_minipage_left_X_dim` will be set, which will be the *width* of `\__enumext_mini_env*` environment on the “left side”, always having a current `\linewidth` as *maximum width* between them.

```

2929     \dim_compare:nNnT
2930     { \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim } } > { \c_zero_dim }
2931     {
2932         \dim_set:cn { l__enumext_minipage_left_ \__enumext_level: _dim }
2933         {
2934             \linewidth
2935             - \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim }
2936             - \dim_use:c { l__enumext_minipage_hsep_ \__enumext_level: _dim }
2937         }

```

The boolean variable `\l__enumext_minipage_active_X_bool` will be activated and the integer variable `\g__enumext_minipage_stat_int` used by the `\mini-right` command will be incremented, then the function `\__enumext_mini_addvspace:` is called and the `\__enumext_mini_env*` environment on the “left side” will be initialized followed by the “vertical spacing” applied to preserve the “baseline” between the *left* and *right* side environments. After these actions, the function `\__enumext_multicols_start:` is called to handle the `multicols` environment.

Here we use the plain TeX macro `\nointerlineskip` to prevent baseline “glue” being added between the next pair of boxes in a *vertical list*.

```

2938     \bool_set_true:c { l__enumext_minipage_active_ \__enumext_level: _bool }
2939     \int_gincr:N \g__enumext_minipage_stat_int
2940     \__enumext_mini_addvspace:
2941     \nointerlineskip\noindent
2942     \begin{\__enumext_mini_env*}
2943     { \dim_use:c { l__enumext_minipage_left_ \__enumext_level: _dim } }
2944     }
2945     \__enumext_multicols_start:
2946 }

```

(End of definition for \\_\_enumext\_before\_list:.)

`\__enumext_multicols_start:` The function `\__enumext_multicols_start:` will start the `multicols` environment according to the value passed by the `columns` key, then set the default value for `\columnsep` when `columns-sep=opt` and set the value of `\multicolsep` equal to zero and leave `\columnseprule` equal to zero for inner levels.

```

2947 \cs_new_protected:Nn \__enumext_multicols_start:
2948 {
2949   \int_compare:nNt
2950     { \int_use:c { \__enumext_columns_ \__enumext_level: _int } } > { 1 }
2951   {
2952     \dim_compare:nNt
2953       { \dim_use:c { \__enumext_columns_sep_ \__enumext_level: _dim } } = { \c_zero_dim }
2954     {
2955       \dim_set:cn { \__enumext_columns_sep_ \__enumext_level: _dim }
2956       {
2957         ( \dim_use:c { \__enumext_labelwidth_ \__enumext_level: _dim }
2958           + \dim_use:c { \__enumext_labelsep_ \__enumext_level: _dim }
2959         ) / \int_use:c { \__enumext_columns_ \__enumext_level: _int }
2960         - \dim_use:c { \__enumext_listoffset_ \__enumext_level: _dim }
2961       }
2962     }
2963     \dim_set_eq:Nc \columnsep { \__enumext_columns_sep_ \__enumext_level: _dim }
2964     \skip_zero:N \multicolsep
2965     \int_compare:nNt { \__enumext_level_int } > { 1 }
2966     {
2967       \dim_zero:N \columnseprule
2968     }

```

We will calculate the *vertical spacing* settings for the `multicols` environment using the function `\__enumext_multi_addvspace:`, apply our “*vertical adjust spacing*”, then start the `multicols` environment.

```

2969   \bool_if:cF { \__enumext_minipage_active_ \__enumext_level: _bool }
2970   {
2971     \__enumext_multi_addvspace:
2972   }
2973   \raggedcolumns
2974   \begin{multicols}{ \int_use:c { \__enumext_columns_ \__enumext_level: _int } }
2975 }
2976 }

```

(End of definition for `\__enumext_multicols_start:`)

`\__enumext_multicols_stop:` The function `\__enumext_multicols_stop:` will stop the `multicols` environment. If the boolean variable `\__enumext_minipage_active_X_bool` is false (not nested in `\__enumext_mini_env*`) we will apply our “*vertical adjust*” spacing.

```

2977 \cs_new_protected:Nn \__enumext_multicols_stop:
2978 {
2979   \int_compare:nNt
2980     { \int_use:c { \__enumext_columns_ \__enumext_level: _int } } > { 1 }
2981   {
2982     \end{multicols}
2983     \bool_if:cF { \__enumext_minipage_active_ \__enumext_level: _bool }
2984     {
2985       \par\addvspace{ \skip_use:c { \__enumext_multicols_below_ \__enumext_level: _skip } }
2986     }
2987   }
2988 }

```

(End of definition for `\__enumext_multicols_stop:`)

`\__enumext_after_list:` The function `\__enumext_after_list:` will check the state of the boolean variable `\__enumext_minipage_active_X_bool`, if it is “true” a small test will be executed to check if we have omitted the use of `\miniright` (the `\__enumext_mini_env*` environment has not been closed), then close `\__enumext_mini_env*` and add the *adjusted vertical space* `\__enumext_minipage_after_skip`, otherwise we will close the `multicols` environment.

```

2989 \cs_new_protected:Nn \__enumext_after_list:
2990 {
2991   \bool_if:cTF { \__enumext_minipage_active_ \__enumext_level: _bool }
2992   {
2993     \int_compare:nNt { \__enumext_minipage_stat_int } = { 1 }
2994     {

```

```

2995         \msg_warning:nn { enumext } { missing-miniright }
2996         \miniright
2997     }
2998     \int_gzero:N \g__enumext_minipage_stat_int
2999     \end{__enumext_mini_env*}
3000     \par\addvspace { \l__enumext_minipage_after_skip }
3001 }
3002 { \__enumext_multicols_stop: }

```

If the `check-ans` key is active, we set the boolean variable `\g__enumext_check_ans_show_bool` to true and copy the “*store name*” to the variable `\g__enumext_store_name_tl`.

```

3003     \__enumext_check_ans_key_hook:

```

Now apply the `{<code>}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present, set `\l__enumext_standar_bool` to false and save the *current value* of the counter for `series`, `resume` and `resume*` keys.

```

3004     \__enumext_after_stop_list:
3005     \__enumext_vspace_below:
3006     \bool_set_false:N \l__enumext_standar_bool
3007     \__enumext_resume_save_counter:
3008 }

```

(End of definition for `\__enumext_after_list:.`)

As we don’t want our check to be executed `check-ans` by levels but on the complete list, we will take it out of the `enumext` environment using the “*hook*” function `\__enumext_after_env:nn`.

```

3009 \__enumext_after_env:nn {enumext} { \__enumext_execute_after_env: }

```

## 10.32 The environment `keyans`

The environment `keyans` also based on lists. The main differences with the `enumext` environment are the *nesting* and the way the *answers* (choice) will be stored and checked, this environment is intended exclusively for “*multiple choice questions*”.

`keyans` Now we define the environment `keyans` also based on lists.

```

3010 \NewDocumentEnvironment{keyans}{ 0{ } }
3011 {
3012     \__enumext_keyans_safe_exec:
3013     \__enumext_keyans_parse_keys:n {#1}
3014     \__enumext_before_list_v:
3015     \__enumext_start_list:nn
3016     { \tl_use:N \l__enumext_label_v_tl }
3017     {
3018         \__enumext_list_arg_two_v:
3019         \__enumext_before_keys_exec_v:
3020     }
3021     \__enumext_after_args_exec_v:
3022 }
3023 {
3024     \__enumext_check_starred_cmd:n { item }
3025     \__enumext_stop_list:
3026     \__enumext_after_list_v:
3027 }

```

(End of definition for `keyans`. This function is documented on page 11.)

`\__enumext_keyans_safe_exec:` The `keyans` environment will only be available if the `save-ans` key is active and can only be used at the first level within the `enumext` environment. We do not want the environment to be nested, so we will set a maximum at this point. If the conditions are not met, an error message will be returned.

```

3028 \cs_new_protected:Nn \__enumext_keyans_safe_exec:
3029 {
3030     \bool_if:NF \l__enumext_store_active_bool
3031     {
3032         \msg_error:nnnn { enumext } { wrong-place } { keyans } { save-ans }
3033     }
3034     \int_incr:N \l__enumext_keyans_level_int
3035     \bool_set_true:N \l__enumext_keyans_env_bool
3036     \__enumext_keyans_save_start_line:
3037     % Set false for interfering with enumext nested in keyans (yes, its possible and crayze)
3038     \bool_set_false:N \l__enumext_store_active_bool
3039     \int_compare:nNt { \l__enumext_keyans_level_int } > { 1 }
3040     {

```

```

3041         \msg_error:nn { enumext } { keyans-nested }
3042     }
3043     \int_compare:nNt { \l__enumext_level_int } > { 1 }
3044     {
3045         \msg_error:nn { enumext } { keyans-wrong-level }
3046     }
3047 }

```

(End of definition for `\__enumext_keyans_safe_exec:`)

`\__enumext_keyans_parse_keys:n` Parse [*key = val*] for `keyans` environment.

```

3048 \cs_new_protected:Npn \__enumext_keyans_parse_keys:n #1
3049 {
3050     \keys_set:nn { enumext / keyans } {#1}
3051 }

```

(End of definition for `\__enumext_keyans_parse_keys:n`)

`\__enumext_before_list_v:` The function `\__enumext_before_list_v:` will add the *vertical spacing* above the environment if the *above* key is active next to the *code* defined by the *before* key if it is active.

```

3052 \cs_new_protected:Nn \__enumext_before_list_v:
3053 {
3054     \__enumext_vspace_above_v:
3055     \__enumext_before_args_exec_v:

```

When the `mini-env` key is active it will set the value of the `\l__enumext_minipage_right_v_dim` to be the *width* of the `__enumext_mini_env*` environment on the *left side*, using this value together with the value of the `\l__enumext_minipage_hsep_v_dim` set by the `mini-sep` key, the value of `\l__enumext_minipage_left_v_dim` will be set, which will be the *width* of `__enumextt_mini_env*` environment on the *right side*, always having `\linewidth` as the maximum width between them.

```

3056     \dim_compare:nNt { \l__enumext_minipage_right_v_dim } > { \c_zero_dim }
3057     {
3058         \dim_set:Nn \l__enumext_minipage_left_v_dim
3059         {
3060             \linewidth - \l__enumext_minipage_right_v_dim - \l__enumext_minipage_hsep_v_dim
3061         }

```

The boolean variable `\l__enumext_minipage_active_v_bool` will be activated and the integer variable `\g__enumext_minipage_stat_int` used by the `\miniiright` command will be incremented, then the function `\__enumext_keyans_mini_addvspace:` is called and the `__enumext_mini_env*` environment on *left side* will be initialized followed by the *vertical spacing* `\l__enumext_minipage_left_skip`. Here we use the plain  $\TeX$  macro `\nointerlineskip` to prevent baseline “glue” being added between the next pair of boxes in a *vertical list*.

```

3062         \bool_set_true:N \l__enumext_minipage_active_v_bool
3063         \int_gincr:N \g__enumext_minipage_stat_int
3064         \__enumext_keyans_mini_addvspace:
3065         \nointerlineskip\noindent
3066         \begin{__enumext_mini_env*}{ \l__enumext_minipage_left_v_dim }
3067     }

```

After these actions, the `\__enumext_keyans_multicols_start:` function is called to handle the `multicols` environment.

```

3068     \__enumext_keyans_multicols_start:
3069 }

```

(End of definition for `\__enumext_before_list_v:`)

`\__enumext_keyans_multicols_start:` The function `\__enumext_keyans_multicols_start:` will start the `multicols` environment according to the value passed by the `columns` key.

```

3070 \cs_new_protected:Nn \__enumext_keyans_multicols_start:
3071 {
3072     \int_compare:nNt { \l__enumext_columns_v_int } > { 1 }
3073     {

```

Set the default value for `\columnsep` when `columns-sep` key is `opt`.

```

3074         \dim_compare:nNt { \l__enumext_columns_sep_v_dim } = { \c_zero_dim }
3075         {
3076             \dim_set:Nn \l__enumext_columns_sep_v_dim
3077             {
3078                 (
3079                     \l__enumext_labelwidth_v_dim + \l__enumext_labelsep_v_dim
3080                 ) / \l__enumext_columns_v_int

```

```

3081         - \l__enumext_listoffset_v_dim
3082     }
3083 }
3084 \dim_set_eq:NN \columnsep \l__enumext_columns_sep_v_dim

```

Then we will set the value of `\multicolsep` and `\columnseprule` equal to zero (we do not want a vertical rule in this environment).

```

3085 \skip_zero:N \multicolsep
3086 \dim_zero:N \columnseprule

```

We will calculate the *vertical spacing* settings for the `multicols` environment using the function `\__enumext_keyans_multi_addvspace:` and apply our “vertical adjust spacing”, then start the `multicols` environment.

```

3087 \bool_if:NF \l__enumext_minipage_active_v_bool
3088 {
3089     \__enumext_keyans_multi_addvspace:
3090 }
3091 \raggedcolumns
3092 \begin{multicols}{\l__enumext_columns_v_int }
3093 }
3094 }

```

(End of definition for `\__enumext_keyans_multicols_start:`)

`\__enumext_keyans_multicols_stop:`

The function `\__enumext_keyans_multicols_stop:` will stop the `multicols` environment. If the boolean variable `\l__enumext_minipage_active_v_bool` is false (not nested in `\__enumext_mini-env*`) we will apply our vertical “adjust” spacing.

```

3095 \cs_new_protected:Nn \__enumext_keyans_multicols_stop:
3096 {
3097     \int_compare:nNtT { \l__enumext_columns_v_int } > { 1 }
3098     {
3099         \end{multicols}
3100         \bool_if:NF \l__enumext_minipage_active_v_bool
3101         {
3102             \par\addvspace{ \l__enumext_multicols_below_v_skip }
3103         }
3104     }
3105 }

```

(End of definition for `\__enumext_keyans_multicols_stop:`)

`\__enumext_after_list_v:`

The function `\__enumext_after_list_v:` will check the state of the boolean variable `\l__enumext_minipage_active_v_bool`, if it is “true” a small test will be executed to check if we have omitted the use of `\miniright` (the `\__enumext_mini-env*` environment has not been closed), then close `\__enumext_mini-env*` and add the vertical adjustment space `\l__enumext_minipage_after_skip`, otherwise we will close the `multicols` environment.

```

3106 \cs_new_protected:Nn \__enumext_after_list_v:
3107 {
3108     \bool_if:NTF \l__enumext_minipage_active_v_bool
3109     {
3110         \int_compare:nNtT { \g__enumext_minipage_stat_int } = { 1 }
3111         {
3112             \msg_warning:nn { enumext } { missing-miniright }
3113             \miniright
3114         }
3115         \int_gzero:N \g__enumext_minipage_stat_int
3116         \end{\__enumext_mini-env*}
3117         \par\addvspace{ \l__enumext_minipage_after_skip }
3118     }
3119     { \__enumext_keyans_multicols_stop: }

```

Finally we will apply the `{\code}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```

3120 \bool_set_false:N \l__enumext_keyans_env_bool
3121 \__enumext_after_stop_list_v:
3122 \__enumext_vspace_below_v:
3123 }

```

(End of definition for `\__enumext_after_list_v:`)

### 10.33 The environment `keyanspic` and `\anspic`

The `keyanspic` environment is a list-based environment that uses the same configuration for “spacing” and `\label` as the `keyans` environment, but it does not use `\item`.

The contents are passed to the environment by means of the `\anspic` command and are placed inside `minipage` environments, with the `\label` underneath, adjusting widths according to the options passed to the environment.

Again it is necessary to “adjust” the spacing, both vertical and horizontal, to obtain an output like the one shown in the figure 12.




Figure 12: Representation of the `keyanspic` spacing in `enumext`.

This implementation is adapted from the answer given by Enrico Gregorio in [How to process the body of an environment and divide it by a \macro?](#).

#### 10.33.1 The command `\anspic`

`\anspic` The `\anspic` command take three arguments, the starred (\*) versions `\anspic*` and `\anspic*[\langle content \rangle]` store the current `\label` next to the `[\langle content \rangle]` if it is present in the `\langle sequence \rangle` and `\langle prop list \rangle` defined by `save-ans` key. This command is used as a replacement for `\item` in the `keyanspic` environment.

```
3124 \NewDocumentCommand \anspic { s o +m }
3125 {
```

We check that the command is active in the `keyanspic` environment only if the `save-ans` key is present, otherwise we return an error.

```
3126   \bool_if:NF \l__enumext_store_active_bool
3127   {
3128     \msg_error:nnnn { enumext } { wrong-place } { keyanspic } { save-ans }
3129   }
3130   \int_compare:nNt { \l__enumext_level_int } > { 1 }
3131   {
3132     \msg_error:nn { enumext } { keyanspic-wrong-level }
3133   }
3134   \int_compare:nNt { \l__enumext_keyans_level_int } = { 1 }
3135   {
3136     \msg_error:nnnn { enumext } { command-wrong-place } { anspic } { keyans }
3137   }
```

The three arguments are handled by the function `\__enumext_keyans_anspic_code:nnn` and stored in the sequence `\l__enumext_keyans_pic_body_seq` which is processed by the `keyanspic` environment.

```
3138   \seq_put_right:Nn \l__enumext_keyans_pic_body_seq
3139   {
3140     \__enumext_keyans_anspic_code:nnn { #1 } { #2 } { #3 }
3141   }
3142 }
```

(End of definition for `\anspic`. This function is documented on page 12.)

`\__enumext_keyans_anspic_code:nnn`

The function `\__enumext_keyans_anspic_code:nnn` will be in charge of handling the “counter” and `\label`, which will have the same configuration as the `keyans` environment.

```
3143 \cs_new_protected:Nn \__enumext_keyans_anspic_code:nnn
3144 {
3145   \stepcounter { enumXvi }
3146   #3 \\\
3147   \bool_if:nT { #1 }
3148   {
3149     \__enumext_keyans_addto_prop:n { #2 }
3150     \__enumext_keyans_store_ref:
3151     \__enumext_keyans_addto_seq:n { #2 }
3152     \int_gincr:N \g__enumext_check_starred_cmd_int
3153     \bool_lazy_or:nnT
3154     { \bool_if_p:N \l__enumext_show_answer_bool }
```



```

3155         { \bool_if_p:N \l__enumext_show_position_bool }
3156         {
3157             \tl_set_eq:NN \l__enumext_label_v_tl \l__enumext_label_vi_tl
3158             \__enumext_keyans_show_left:n { #2 }
3159             \tl_set_eq:NN \l__enumext_label_vi_tl \l__enumext_label_v_tl
3160         }
3161     }
3162     \tl_use:N \l__enumext_label_font_style_v_tl
3163     \__enumext_wrapper_label_v:n { \l__enumext_label_vi_tl } \__enumext_keyans_show_item_opt:
3164 }

```

(End of definition for `\__enumext_keyans_anspic_code:nnn`.)

### 10.33.2 The environment `keyanspic`

`keyanspic` Now we define the environment `keyanspic` based on list. The optional argument [*number above, number below*] will determine the number of `minipage` environments that will be above and below separated by `\parsep+\itemsep` within it.

```

3165 \NewDocumentEnvironment{keyanspic}{o}
3166 {
3167     \__enumext_keyans_pic_safe_exec:
3168     \__enumext_start_list:nn
3169     { }
3170     {
3171         \__enumext_keyans_pic_arg_two:
3172     }

```

We apply the “adjusted” vertical spacing above the environment

```

3173     \vspace { \l__enumext_keyans_pic_above_skip }
3174 }

```

If the optional argument is not present, the number of times the `\anspic` command appears will be counted from `\l__enumext_keyans_pic_body_seq` and placed in `minipage` environments on a single line. Finally we check if `\anspic*` has been used, set the counter to zero and apply our “adjusted” vertical space below the environment.

```

3175 {
3176     \tl_if_novalue:nTF { #1 }
3177     {
3178         \__enumext_keyans_pic_do:e { \seq_count:N \l__enumext_keyans_pic_body_seq }
3179     }
3180     { \__enumext_keyans_pic_do:n { #1 } }
3181     \__enumext_stop_list:
3182     \__enumext_check_starred_cmd:n { anspic }
3183     \setcounter { enumXvi } { 0 }
3184     \vspace { \l__enumext_topsep_v_skip }
3185     %\bool_set_false:N \l__enumext_store_active_bool
3186 }

```

(End of definition for `keyanspic`. This function is documented on page 12.)

`\__enumext_keyans_pic_safe_exec:` The function `\__enumext_keyans_pic_safe_exec:` check nested and level position inside the `enumext` environment.

```

3187 \cs_new_protected:Nn \__enumext_keyans_pic_safe_exec:
3188 {
3189     \int_incr:N \l__enumext_keyans_pic_level_int
3190     \int_compare:nNnT { \l__enumext_keyans_pic_level_int } > { 1 }
3191     {
3192         \msg_error:nn { enumext } { keyanspic-nested }
3193     }
3194     \__enumext_keyans_save_start_line:
3195 }

```

(End of definition for `\__enumext_keyans_pic_safe_exec:.`)

`\__enumext_keyans_pic_skip_abs:N` The function `\__enumext_keyans_pic_skip_abs:N` will return a positive value `\parsep`.

```

3196 \cs_new_protected:Npn \__enumext_keyans_pic_skip_abs:N #1
3197 {
3198     \dim_compare:nNnT { #1 } < { 0pt }
3199     { \skip_set:Nn #1 { -#1 } }
3200 }

```

(End of definition for `\__enumext_keyans_pic_skip_abs:N`.)

`\__enumext_keyans_pic_arg_two:` The function `\__enumext_keyans_pic_arg_two:` will be used in the second argument of the `\__enumext_start_list:nn` function that defines the `keyanspic` environment, it will handle the setting of spaces.

```
3201 \cs_new_protected:Nn \__enumext_keyans_pic_arg_two:
3202 {
```

The first thing to do is to set the boolean variable `\l__enumext_leftmargin_tmp_v_bool` handled by the `list-indent` key to false, then we copy the definition of the second list argument from the `keyans` environment.

```
3203 \bool_set_false:N \l__enumext_leftmargin_tmp_v_bool
3204 \__enumext_list_arg_two_v:
```

We will add the value of `\itemsep` to `\parsep` which we will use as vertical spacing between the above and below `minipage` environments. and adjust the value of `\leftmargin`, the label and counter are handled directly by the `\anspic` command. Then we make equal to zero `\labelwidth`, `\labelsep`, `\partopsep` and `\itemsep` so that the horizontal and vertical spacing is not affected.

```
3205 \skip_add:Nn \parsep { \itemsep }
3206 \dim_add:Nn \leftmargin { -\labelwidth - \labelsep }
3207 \dim_zero:N \labelwidth
3208 \dim_zero:N \listparindent
3209 \dim_zero:N \labelsep
3210 \skip_zero:N \partopsep
3211 \skip_zero:N \itemsep
```

We set the value of `\l__enumext_keyans_pic_above_skip` which we will use to apply our “adjust” space above `keyanspic`, finally we call `\__enumext_item_std:w` followed by `\scan_stop:` to prevent the error message returned by  $\text{\LaTeX}$  when not using the `\item` command.

```
3212 \__enumext_keyans_pic_skip_abs:N \parsep
3213 \skip_set:Nn \l__enumext_keyans_pic_above_skip
3214 {
3215     \box_dp:N \strutbox
3216     + \l__enumext_topsep_v_skip
3217     - \parsep
3218 }
3219 \__enumext_item_std:w \scan_stop:
3220 }
```

(End of definition for `\__enumext_keyans_pic_arg_two:.`)

`\__enumext_keyans_pic_do:n` The optional argument is split by comma and is handled directly by the function `\__enumext_keyans_pic_do:n` and passed to the function `\__enumext_keyans_pic_row:n`.

```
3221 \cs_new_protected:Nn \__enumext_keyans_pic_do:n
3222 {
3223     \clist_map_function:nN { #1 } \__enumext_keyans_pic_row:n
3224 }
3225 \cs_generate_variant:Nn \__enumext_keyans_pic_do:n { e }
```

(End of definition for `\__enumext_keyans_pic_do:n.`)

`\__enumext_keyans_pic_row:n` The function `\__enumext_keyans_pic_row:n` will set the widths for the `minipage` environments and place the content `\stored` by `\anspic*` in the `\l__enumext_keyans_pic_body_seq` sequence inside them.

```
3226 \cs_new_protected:Nn \__enumext_keyans_pic_row:n
3227 {
3228     \dim_set:Nn \l__enumext_keyans_pic_width_dim { \linewidth / #1 }
3229     \int_set:Nn \l__enumext_keyans_pic_above_int { \l__enumext_keyans_pic_below_int }
3230     \int_set:Nn \l__enumext_keyans_pic_below_int { \l__enumext_keyans_pic_above_int + #1 }
3231     \int_step_inline:nnn
3232     { \l__enumext_keyans_pic_above_int + 1 }
3233     { \l__enumext_keyans_pic_below_int }
3234     {
3235         \__enumext_minipage:w [ b ]{ \l__enumext_keyans_pic_width_dim }
3236         \centering
3237         \seq_item:Nn \l__enumext_keyans_pic_body_seq { ##1 }
3238         \__enumext_endminipage:
3239     }
3240     \par
3241 }
```

(End of definition for `\__enumext_keyans_pic_row:n.`)

### 10.34 The environment enumext\*

Generating horizontal list environments is NOT as simple as standard  $\text{\LaTeX}$  list environments. The fundamental part of the code is adapted from the `shortlst` package to a more modern version using `expl3`. It is not possible to redefine `\item` and `\makelabel` as in the non starred versions (at least I have not achieved it) and as we will make it behave differently, we have no other option than to define a cascade of functions.

To achieve the horizontal list environment we will capture the `\item` command and the content of this in a plain `lrbox` box using `\makebox` for the `label` and a `minipage` environment for the content passed to `\item`, we will also add the optional argument (`\langle number \rangle`) to `\item` to be able to *join columns* horizontally, in simple terms, we want `\item` to behave in the same way as in the `enumext` environment but adding an optional first argument (`\langle number \rangle`).

#### 10.34.1 Functions for item box width

We set the default value for the width of the box containing the content of the items and create `\itemwidth` in a public form.

```

3242 \cs_new_protected:Nn \__enumext_starred_columns_set_vii:
3243 {
3244   \dim_compare:nNt { \l__enumext_columns_sep_vii_dim } = { \c_zero_dim }
3245   {
3246     \dim_set:Nn \l__enumext_columns_sep_vii_dim
3247     {
3248       ( \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim )
3249       / \l__enumext_columns_vii_int
3250     }
3251   }
3252   \int_set:Nn \l__enumext_tmpa_vii_int { \l__enumext_columns_vii_int - \c_one_int }
3253   \dim_set:Nn \l__enumext_item_width_vii_dim
3254   {
3255     ( \linewidth - \l__enumext_columns_sep_vii_dim * \l__enumext_tmpa_vii_int )
3256     / \l__enumext_columns_vii_int - \l__enumext_labelwidth_vii_dim
3257     - \l__enumext_labelsep_vii_dim
3258   }
3259   \dim_zero_new:N \itemwidth
3260 }

```

(End of definition for `\__enumext_starred_columns_set_vii:`.)

The function `\__enumext_starred_joined_item_vii:n` will set the *width* of the box in which the content passed to `\item(\langle number \rangle)` will be stored together with the value of `\itemwidth`.

```

3261 \cs_new_protected:Npn \__enumext_starred_joined_item_vii:n #1
3262 {
3263   \int_set:Nn \l__enumext_joined_item_vii_int {#1}
3264   \int_compare:nNt { \l__enumext_joined_item_vii_int } > { \l__enumext_columns_vii_int }
3265   {
3266     \msg_warning:nnee { enumext } { item-joined }
3267     { \int_use:N \l__enumext_joined_item_vii_int }
3268     { \int_use:N \l__enumext_columns_vii_int }
3269     \int_set:Nn \l__enumext_joined_item_vii_int
3270     {
3271       \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int
3272     }
3273   }
3274   \int_compare:nNt
3275   { \l__enumext_joined_item_vii_int }
3276   >
3277   { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int }
3278   {
3279     \msg_warning:nnee { enumext } { item-joined-columns }
3280     { \int_use:N \l__enumext_joined_item_vii_int }
3281     {
3282       \int_eval:n
3283       { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int }
3284     }
3285     \int_set:Nn \l__enumext_joined_item_vii_int
3286     {
3287       \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int
3288     }
3289   }
}

```

Only need if #1 » 1 (default are set before).

```

3290 \int_compare:nNnTF { \l__enumext_joined_item_vii_int } > { \c_one_int }
3291 {
3292   \int_set_eq:NN \l__enumext_joined_item_aux_vii_int \l__enumext_joined_item_vii_int
3293   \int_decr:N \l__enumext_joined_item_aux_vii_int
3294   \int_add:Nn \l__enumext_item_column_pos_vii_int { \l__enumext_joined_item_aux_vii_int }
3295   \int_gadd:Nn \g__enumext_item_count_all_vii_int { \l__enumext_joined_item_aux_vii_int }
3296   \dim_set:Nn \l__enumext_joined_width_vii_dim
3297   {
3298     \l__enumext_item_width_vii_dim * \l__enumext_joined_item_vii_int
3299     + ( \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim
3300       + \l__enumext_columns_sep_vii_dim
3301       ) * \l__enumext_joined_item_aux_vii_int
3302   }
3303   \dim_set_eq:NN \itemwidth \l__enumext_joined_width_vii_dim
3304 }
3305 {
3306   \dim_set_eq:NN \l__enumext_joined_width_vii_dim \l__enumext_item_width_vii_dim
3307   \dim_set_eq:NN \itemwidth \l__enumext_item_width_vii_dim
3308 }
3309 }

```

(End of definition for \l\_\_enumext\_starred\_joined\_item\_vii:n.)

\\_\_enumext\_start\_mini\_vii:

The implementation of the `mini-env` key support is almost identical to the one used in the `enumext` and `keyans` environments, the difference is that the `__enumext_mini_env*` environment on the “*right side*” is executed “*after*” closing the environment, so it is necessary to make a global copy of the variable `\l__enumext_minipage_right_vii_dim` in the variable `\g__enumext_minipage_right_vii_dim`.

```

3310 \cs_new_protected:Nn \__enumext_start_mini_vii:
3311 {
3312   \dim_compare:nNnT { \l__enumext_minipage_right_vii_dim } > { \c_zero_dim }
3313   {
3314     \dim_set:Nn \l__enumext_minipage_left_vii_dim
3315     {
3316       \linewidth
3317       - \l__enumext_minipage_right_vii_dim
3318       - \l__enumext_minipage_hsep_vii_dim
3319     }
3320     \bool_set_true:N \l__enumext_minipage_active_vii_bool
3321     \dim_gset_eq:NN
3322       \g__enumext_minipage_right_vii_dim
3323       \l__enumext_minipage_right_vii_dim
3324     \__enumext_mini_addvspace_vii:
3325     \nointerlineskip\noindent
3326     \begin{__enumext_mini_env*}{ \l__enumext_minipage_left_vii_dim }
3327   }
3328 }

```

(End of definition for \\_\_enumext\_start\_mini\_vii:.)

\\_\_enumext\_stop\_mini\_vii:

The function `\__enumext_stop_mini_vii:` closes the `__enumext_mini_env*` environment on the left side, applies `\hfill` and sets the value of the variable `\g__enumext_minipage_active_vii_bool` to true which will be used in the function `\__enumext_after_star_env:nn` to execute the `__enumext_mini_env*` on the “*right side*”.

```

3329 \cs_new_protected:Nn \__enumext_stop_mini_vii:
3330 {
3331   \bool_if:NT \l__enumext_minipage_active_vii_bool
3332   {
3333     \end{__enumext_mini_env*}
3334     \hfill
3335     \bool_gset_true:N \g__enumext_minipage_active_vii_bool
3336   }
3337 }

```

Finally we execute code passed to the `miniright` key stored in the variable `\g__enumext_miniright_code_vii_tl` in the `__enumext_mini_env*` environment on the “*right side*”.

```

3338 \__enumext_after_env:nn {enumext*}
3339 {
3340   \bool_if:NT \g__enumext_minipage_active_vii_bool
3341   {

```

```

3342 \begin{__enumext_mini_env*}{ \g__enumext_minipage_right_vii_dim }
3343 \par\addvspace { \g__enumext_minipage_right_skip }
3344 \bool_if:NF \g__enumext_minipage_center_vii_bool
3345 {
3346   \centering
3347 }
3348 \tl_use:N \g__enumext_miniright_code_vii_tl % the code
3349 \end{__enumext_mini_env*}
3350 \par\addvspace{ \g__enumext_minipage_after_skip }
3351 }
3352 \bool_gset_false:N \g__enumext_minipage_active_vii_bool
3353 \bool_gset_true:N \g__enumext_minipage_center_vii_bool
3354 \tl_gclear:N \g__enumext_miniright_code_vii_tl
3355 \dim_gzero:N \g__enumext_minipage_right_vii_dim
3356 \bool_gset_false:N \g__enumext_starred_bool
3357 }

```

(End of definition for \\_\_enumext\_stop\_mini\_vii:.)

**enumext\*** First we will generate the environment and we will give a temporary definition to \\_\_enumext\_stop\_item\_tmp\_vii: equal to \noindent and next to \item equal to \\_\_enumext\_start\_item\_tmp\_vii: which we will redefine later.

```

3358 \NewDocumentEnvironment{enumext*}{ o }
3359 {
3360   \__enumext_safe_exec_vii:
3361   \__enumext_parse_keys_vii:n {#1}
3362   \__enumext_before_list_vii:
3363   \__enumext_start_store_level_vii:
3364   \__enumext_start_list:nn { }
3365   {
3366     \__enumext_list_arg_two_vii:
3367     \__enumext_before_keys_exec_vii:
3368   }
3369   \__enumext_starred_columns_set_vii:
3370   \item[] \scan_stop:
3371   \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \noindent
3372   \cs_set_eq:NN \item \__enumext_start_item_tmp_vii:
3373 }
3374 {
3375   \__enumext_stop_item_tmp_vii:
3376   \__enumext_remove_extra_parsep_vii:
3377   \__enumext_stop_list:
3378   \__enumext_stop_store_level_vii:
3379   \__enumext_after_list_vii:
3380 }

```

(End of definition for enumext\*. This function is documented on page 4.)

\\_\_enumext\_safe\_exec\_vii: First check the maximum nesting level for the **enumext\*** environment then set the vars \l\_\_enumext\_starred\_bool and \g\_\_enumext\_starred\_bool.

```

3381 \cs_new_protected:Nn \__enumext_safe_exec_vii:
3382 {
3383   \__enumext_is_not_nested:
3384   \int_incr:N \l__enumext_level_h_int
3385   \int_compare:nNnT { \l__enumext_level_h_int } > { 1 }
3386   {
3387     \msg_error:nn { enumext } { nested }
3388   }
3389   \bool_set_true:N \l__enumext_starred_bool
3390   \__enumext_is_on_first_level:
3391 }

```

(End of definition for \\_\_enumext\_safe\_exec\_vii:.)

\\_\_enumext\_parse\_keys\_vii:n Parse [*key = val*] for **enumext\***. If the variable \l\_\_enumext\_store\_active\_bool is true it will call the function \\_\_enumext\_parse\_store\_keys\_vii:n and reprocess the keys to pass them to the storage sequence.

```

3392 \cs_new_protected:Npn \__enumext_parse_keys_vii:n #1
3393 {
3394   \tl_if_novalue:nF {#1}
3395   {

```

```

3396     \str_clear:N \__enumext_series_str
3397     \keys_set:nn { enumext / enumext* } {#1}
3398     \__enumext_parse_series:n {#1}
3399     \bool_if:NT \__enumext_store_active_bool
3400     {
3401         \__enumext_parse_store_keys_vii:n {#1}
3402     }
3403 }
3404 }

```

(End of definition for \\_\_enumext\_parse\_keys\_vii:n.)

\\_\_enumext\_parse\_store\_keys\_vii:n

The function \\_\_enumext\_parse\_store\_keys\_vii:n searches for the values of the `columns` and `columns-sep` keys in the optional argument in `enumext*` environment as long as the starred versions of the `columns*` and `columns-sep*` keys are not active. The captured values are stored in the variable `\l__enumext_store_opt_vii_tl` which is used by the function `\__enumext_store_level_open_vii:`.

```

3405 \cs_new_protected:Npn \__enumext_parse_store_keys_vii:n #1
3406 {
3407     \bool_if:NF \__enumext_store_columns_vii_bool
3408     {
3409         \regex_match:nnT { \b columns\b } {#1}
3410         {
3411             \int_set_eq:NN
3412             \l__enumext_store_columns_vii_int
3413             \l__enumext_columns_vii_int
3414             \tl_put_right:Ne \l__enumext_store_opt_vii_tl
3415             {
3416                 columns = \exp_not:V \l__enumext_store_columns_vii_int ,
3417             }
3418         }
3419     }
3420     \bool_if:NF \__enumext_store_columns_sep_vii_bool
3421     {
3422         \regex_match:nnT { \b columns-sep\b } {#1}
3423         {
3424             \dim_set_eq:NN
3425             \l__enumext_store_columns_sep_vii_dim
3426             \l__enumext_columns_sep_vii_dim
3427             \tl_put_right:Ne \l__enumext_store_opt_vii_tl
3428             {
3429                 columns-sep = \exp_not:V \l__enumext_store_columns_sep_vii_dim,
3430             }
3431         }
3432     }
3433 }

```

(End of definition for \\_\_enumext\_parse\_store\_keys\_vii:n.)

\\_\_enumext\_before\_list\_vii:

The function \\_\_enumext\_before\_list\_vii: will add the vertical spacing on the environment if the `above` key is active next to the `{\code}` defined by the `before*` key if it is active, the call the function \\_\_enumext\_start\_mini\_vii: handle by `mini-env`.

```

3434 \cs_new_protected:Nn \__enumext_before_list_vii:
3435 {
3436     \__enumext_vspace_above_vii:
3437     \__enumext_check_ans_active:
3438     \__enumext_before_args_exec_vii:
3439     \__enumext_start_mini_vii:
3440 }

```

(End of definition for \\_\_enumext\_before\_list\_vii:.)

\\_\_enumext\_after\_list\_vii:

The function \\_\_enumext\_after\_list: first call the function \\_\_enumext\_stop\_mini\_vii:, then apply the `{\code}` handled by the `after` key together with the `vertical space` handled by the `below` key if they are present. Finally set false the vars `\g__enumext_starred_bool` and `\l__enumext_starred_bool`, save the *current value* of the counter in `\g__enumext_resume_vii_int` for the `resume` key. If the `save-ans` key is active, it will create the integer variable for the `resume` key, we only have to assign it the value of the current counter.

```

3441 \cs_new_protected:Nn \__enumext_after_list_vii:
3442 {

```

```

3443     \__enumext_stop_mini_vii:
3444     \__enumext_after_stop_list_vii:
3445     \__enumext_check_ans_key_hook:
3446     \__enumext_vspace_below_vii:
3447     \bool_set_false:N \__enumext_starred_bool
3448     \__enumext_resume_save_counter:
3449 }

```

(End of definition for \\_\_enumext\_after\_list\_vii:.)

```

\__enumext_start_store_level_vii:
\__enumext_stop_store_level_vii:

```

The \\_\_enumext\_start\_store\_level\_vii: and \\_\_enumext\_stop\_store\_level\_vii: functions activate the level saving mechanism for storage in *(sequence)* of the \anskey command if enumext\* are nested in enumext.

```

3450 \cs_new_protected:Nn \__enumext_start_store_level_vii:
3451 {
3452   \bool_if:NT \__enumext_store_active_bool
3453   {
3454     \int_compare:nNtT { \__enumext_level_int } > { \c_zero_int }
3455     {
3456       \__enumext_store_level_open_vii:
3457     }
3458   }
3459 }
3460 \cs_new_protected:Nn \__enumext_stop_store_level_vii:
3461 {
3462   \bool_if:NT \__enumext_store_active_bool
3463   {
3464     \int_compare:nNtT { \__enumext_level_int } > { \c_zero_int }
3465     {
3466       \__enumext_store_level_close_vii:
3467     }
3468   }
3469 }

```

(End of definition for \\_\_enumext\_start\_store\_level\_vii: and \\_\_enumext\_stop\_store\_level\_vii:.)

### 10.34.2 The command \item in enumext\*

```
\__enumext_start_item_tmp_vii:
```

First we will call the function \\_\_enumext\_stop\_item\_tmp\_vii: that we will redefine later, we will increment the value of \l\_\_enumext\_item\_column\_pos\_vii\_int that will count the item's by rows and the value of \g\_\_enumext\_item\_count\_all\_vii\_int that will count the total of item's in the environment. After that we will call the function \\_\_enumext\_item\_peek\_args\_vii: that will handle the arguments passed to \item.

```

3470 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_vii:
3471 {
3472   \__enumext_stop_item_tmp_vii:
3473   \int_incr:N \l__enumext_item_column_pos_vii_int
3474   \int_gincr:N \g__enumext_item_count_all_vii_int
3475   \__enumext_item_peek_args_vii:
3476 }

```

(End of definition for \\_\_enumext\_start\_item\_tmp\_vii:.)

```
\__enumext_item_peek_args_vii:
```

The function \\_\_enumext\_item\_peek\_args\_vii: will handle the \item(*number*). Look for the argument “(”, if it is present we will call the function \\_\_enumext\_joined\_item\_vii:w (*number*), which is in charge of joining the item's in the same row, in case they are not present we will set the default value (1).

```

3477 \cs_new_protected:Nn \__enumext_item_peek_args_vii:
3478 {
3479   \peek_meaning:NTF (
3480     { \__enumext_joined_item_vii:w }
3481     { \__enumext_joined_item_vii:w (1) }
3482   }

```

(End of definition for \\_\_enumext\_item\_peek\_args\_vii:.)

```
\__enumext_joined_item_vii:w
```

The function \\_\_enumext\_joined\_item\_vii:w will first call the function \\_\_enumext\_starred\_joined\_item\_vii:n in charge of setting the *width* of the box that will store the content passed to \item. Then we will look for the argument “\*”, if it is present we will call the function \\_\_enumext\_starred\_item\_vii:w otherwise we will call the function \\_\_enumext\_standard\_item\_vii:w.

```

3483 \cs_new_protected:Npn \__enumext_joined_item_vii:w (#1)

```

```

3484 {
3485     \__enumext_starred_joined_item_vii:n {#1}
3486     \peek_meaning_remove:NTF *
3487     { \__enumext_starred_item_vii:w }
3488     { \__enumext_standard_item_vii:w }
3489 }

```

(End of definition for \\_\_enumext\_joined\_item\_vii:w.)

\\_\_enumext\_standard\_item\_vii:w

The function \\_\_enumext\_standard\_item\_vii:w will first look for the argument “[”, if present it will set the state of the variable \l\_\_enumext\_wrap\_label\_opt\_vii\_bool equal to the state of the variable \l\_\_enumext\_wrap\_label\_opt\_vii\_bool handled by the key `wrap-label*` and finally execute the *non-enumerated* version \item[⟨*custom*⟩] by means of the function \\_\_enumext\_start\_item\_vii:w, otherwise we will set the value of the variable \l\_\_enumext\_wrap\_label\_vii\_bool handled by the `wrap-label` key to true and set the switch \if@noitemarg to true to execute the enumerated version of \item by means of the function \\_\_enumext\_start\_item\_vii:w [ \l\_\_enumext\_label\_vii\_tl ].

```

3490 \cs_new_protected:Npn \__enumext_standard_item_vii:w
3491 {
3492     \bool_set_false:N \l__enumext_item_starred_vii_bool
3493     \peek_meaning:NTF [
3494     {
3495         \bool_set_eq:NN
3496         \l__enumext_wrap_label_vii_bool
3497         \l__enumext_wrap_label_opt_vii_bool
3498         \__enumext_start_item_vii:w
3499     }
3500     {
3501         \bool_set_true:N \l__enumext_wrap_label_vii_bool
3502         \legacy_if_set_true:n { @noitemarg }
3503         \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
3504     }
3505 }

```

(End of definition for \\_\_enumext\_standard\_item\_vii:w.)

\\_\_enumext\_starred\_item\_vii:w

\\_\_enumext\_starred\_item\_vii\_aux\_i:w

\\_\_enumext\_starred\_item\_vii\_aux\_ii:w

\\_\_enumext\_starred\_item\_vii\_aux\_iii:w

The function \\_\_enumext\_starred\_item\_vii:w together with the specified auxiliary functions `aux_i:w`, `aux_ii:w`, and `aux_iii:w` execute \item\*, \item\*[⟨*symbol*⟩] and \item\*[⟨*symbol*⟩][⟨*offset*⟩].

```

3506 \cs_new_protected:Npn \__enumext_starred_item_vii:w
3507 {
3508     \bool_set_true:N \l__enumext_item_starred_vii_bool
3509     \bool_set_true:N \l__enumext_wrap_label_vii_bool
3510     \peek_meaning:NTF [
3511     { \__enumext_starred_item_vii_aux_i:w }
3512     { \__enumext_starred_item_vii_aux_ii:w }
3513 }
3514 \cs_new_protected:Npn \__enumext_starred_item_vii_aux_i:w {#1}
3515 {
3516     \tl_gset:Nn \g__enumext_item_symbol_aux_vii_tl {#1}
3517     \__enumext_starred_item_vii_aux_ii:w
3518 }
3519 \cs_new_protected:Npn \__enumext_starred_item_vii_aux_ii:w
3520 {
3521     \peek_meaning:NTF [
3522     { \__enumext_starred_item_vii_aux_iii:w }
3523     {
3524         \dim_set_eq:NN
3525         \l__enumext_item_symbol_sep_vii_dim
3526         \l__enumext_labelsep_vii_dim
3527         \legacy_if_set_true:n { @noitemarg }
3528         \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
3529     }
3530 }
3531 \cs_new_protected:Npn \__enumext_starred_item_vii_aux_iii:w {#1}
3532 {
3533     \dim_set:Nn \l__enumext_item_symbol_sep_vii_dim {#1}
3534     \legacy_if_set_true:n { @noitemarg }
3535     \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
3536 }

```

(End of definition for \\_\_enumext\_starred\_item\_vii:w and others.)



### 10.34.3 Real definition of `\item` in `enumext*`

`\__enumext_start_item_vii:w`

The functions `\__enumext_start_item_vii:w` and `\__enumext_stop_item_vii:` executing the true definition of `\item` inside the `enumext*` environment.

The first thing we will do is set the value of `\__enumext_stop_item_tmp_vii:` equal to the value of `\__enumext_stop_item_vii:` which we will define later and add the `hyperref` compatible `enumXvii` counter, after that we will start capturing the item content in a box. Here need setting the `\if@hyper@item` switch to “true” for `hyperref` compatible. The explanation for this is given by the master Heiko Oberdiek on `\refstepcounter{enumi}` twice (or more) creates destination with the same identifier.

```

3537 \cs_new_protected_nopar:Npn \__enumext_start_item_vii:w [#1]
3538 {
3539   \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \__enumext_stop_item_vii:
3540   \legacy_if:nT { @noitemarg }
3541   {
3542     \legacy_if_set_false:n { @noitemarg }
3543     \legacy_if:nT { @nmbrrlist }
3544     {
3545       \bool_if:NT \__enumext_hyperref_bool
3546       {
3547         \legacy_if_set_true:n { @hyper@item }
3548       }
3549       \refstepcounter{enumXvii}
3550       \bool_if:NT \__enumext_check_answers_bool
3551       {
3552         \int_gincr:N \g__enumext_item_number_int
3553       }
3554     }
3555   }

```

Here we start capturing `\item` and its contents into a group using the plain form of the `lrbox` environment. If the state of the variable `\l__enumext_footnotes_key_bool` is false, we will redefine the command `\footnote`, followed by printing the  $\langle symbol \rangle$  defined for `\item*` if it is present and open a new group inside which we execute `font` key next to `\item` and the keys `wrap-label`, `wrap-label*`, `align`, close the group and execute the key `labelsep` and then the key `first`. Finally we open the `minipage` environment and execute the `listparindent` key which will be equal to `\parindent`, the `parsep` key which will be equal to `\parskip` and the `itemindent` key.

```

3556 \group_begin:
3557   \lrbox{ \l__enumext_item_text_vii_box }
3558   \bool_if:NF \l__enumext_footnotes_key_bool
3559   {
3560     \__enumext_renew_footnote:
3561   }
3562   \bool_if:NT \l__enumext_item_starred_vii_bool
3563   {
3564     \tl_if_blank:VT \g__enumext_item_symbol_aux_vii_tl
3565     {
3566       \tl_gset_eq:NN
3567       \g__enumext_item_symbol_aux_vii_tl \l__enumext_item_symbol_vii_tl
3568     }
3569     \mode_leave_vertical:
3570     \skip_horizontal:n { -\l__enumext_item_symbol_sep_vii_dim }
3571     \makebox[ 0pt ][ r ]{ \g__enumext_item_symbol_aux_vii_tl }
3572     \skip_horizontal:N \l__enumext_item_symbol_sep_vii_dim
3573     \tl_gclear:N \g__enumext_item_symbol_aux_vii_tl
3574   }
3575   \group_begin:
3576   \tl_use:N \l__enumext_label_font_style_vii_tl
3577   \bool_if:NTF \l__enumext_wrap_label_vii_bool
3578   {
3579     \makebox[ \l__enumext_labelwidth_vii_dim ][ \l__enumext_align_label_vii_str ]
3580     { \__enumext_wrapper_label_vii:n {#1} }
3581   }
3582   {
3583     \makebox[ \l__enumext_labelwidth_vii_dim ][ \l__enumext_align_label_vii_str ]{ #1 }
3584   }
3585   \group_end:
3586   \skip_horizontal:N \l__enumext_labelsep_vii_dim
3587   \tl_use:N \l__enumext_after_list_args_vii_tl
3588   \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_vii_dim }
3589   \skip_set_eq:NN \parindent \l__enumext_listparindent_vii_dim
3590   \skip_set_eq:NN \parskip \l__enumext_parsep_vii_skip

```

```

3591         \tl_use:N \l__enumext_fake_item_indent_vii_tl
3592     }

```

(End of definition for `\__enumext_start_item_vii:w`.)

`\__enumext_stop_item_vii:` The function `\__enumext_stop_item_vii:` shall terminate with the capture of `\item` and its *contents*. Close the environments `minipage`, `lrbox` and the group. Then we only have to set the width of the box and print it next to `\footnote`, and add the horizontal and vertical separation between the boxes.

```

3593 \cs_new_protected_nopar:Nn \__enumext_stop_item_vii:
3594 {
3595     \__enumext_endminipage:
3596     \endlrbox
3597     \group_end:
3598     \box_set_wd:Nn \l__enumext_item_text_vii_box
3599     {
3600         \l__enumext_joined_width_vii_dim
3601         + \l__enumext_labelwidth_vii_dim
3602         + \l__enumext_labelsep_vii_dim
3603     }
3604     \int_set:Nn \hbadness { 10000 }
3605     \box_use:N \l__enumext_item_text_vii_box
3606     \bool_if:NF \l__enumext_footnotes_key_bool
3607     {
3608         \__enumext_print_footnote:
3609     }
3610     \int_compare:nNnTF { \l__enumext_item_column_pos_vii_int } = { \l__enumext_columns_vii_int }
3611     {
3612         \par\noindent
3613         \int_zero:N \l__enumext_item_column_pos_vii_int
3614     }
3615     { \hspace{ \l__enumext_columns_sep_vii_dim } }
3616 }

```

(End of definition for `\__enumext_stop_item_vii:`.)

`\__enumext_remove_extra_parsep_vii:` Finally we will remove the vertical space equal to `\parsep` when the total number of items is divisible by the number of items in the last row of the environment.

```

3617 \cs_new_protected:Nn \__enumext_remove_extra_parsep_vii:
3618 {
3619     \int_compare:nNnT
3620     {
3621         \int_mod:nn { \g__enumext_item_count_all_vii_int } { \l__enumext_columns_vii_int }
3622     }
3623     =
3624     { \c_zero_int }
3625     {
3626         \par
3627         \vspace{ -\l__enumext_itemsep_vii_skip }
3628         \int_gzero:N \g__enumext_item_count_all_vii_int
3629     }
3630 }

```

(End of definition for `\__enumext_remove_extra_parsep_vii:`.)

As we don't want our check to be executed `check-ans` by levels but on the complete list, we will take it out of the `enumext*` environment using the “hook” function `\__enumext_after_env:nn`.

```

3631 \__enumext_after_env:nn {enumext*} { \__enumext_execute_after_env: }

```

## 10.35 The environment `keyans*`

### 10.35.1 Functions for item box width

`\__enumext_starred_columns_set_viii:` We set the default value for the width of the box containing the content of the items and create `\itemwidth` in a public form.

```

3632 \cs_new_protected:Nn \__enumext_starred_columns_set_viii:
3633 {
3634     \dim_compare:nNnT { \l__enumext_columns_sep_viii_dim } = { \c_zero_dim }
3635     {
3636         \dim_set:Nn \l__enumext_columns_sep_viii_dim
3637         {
3638             ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim )
3639             / \l__enumext_columns_viii_int

```

```

3640     }
3641   }
3642   \int_set:Nn \l__enumext_tmpa_viii_int { \l__enumext_columns_viii_int - \c_one_int }
3643   \dim_set:Nn \l__enumext_item_width_viii_dim
3644   {
3645     ( \linewidth - \l__enumext_columns_sep_viii_dim * \l__enumext_tmpa_viii_int )
3646     / \l__enumext_columns_viii_int - \l__enumext_labelwidth_viii_dim
3647     - \l__enumext_labelsep_viii_dim
3648   }
3649   \dim_zero_new:N \itemwidth
3650 }

```

(End of definition for \\_\_enumext\_starred\_columns\_set\_viii:.)

\\_\_enumext\_starred\_joined\_item\_viii:n

The function \\_\_enumext\_starred\_joined\_item\_viii:n will set the *width* of the box in which the content passed to \item(<number>) will be stored together with the value of \itemwidth.

```

3651 \cs_new_protected:Npn \__enumext_starred_joined_item_viii:n #1
3652 {
3653   \int_set:Nn \l__enumext_joined_item_viii_int {#1}
3654   \int_compare:nNnT { \l__enumext_joined_item_viii_int } > { \l__enumext_columns_viii_int }
3655   {
3656     \msg_warning:nnee { enumext } { item-joined }
3657     { \int_use:N \l__enumext_joined_item_viii_int }
3658     { \int_use:N \l__enumext_columns_viii_int }
3659     \int_set:Nn \l__enumext_joined_item_viii_int
3660     {
3661       \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int
3662     }
3663   }
3664   \int_compare:nNnT
3665   { \l__enumext_joined_item_viii_int }
3666   >
3667   { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int }
3668   {
3669     \msg_warning:nnee { enumext } { item-joined-columns }
3670     { \int_use:N \l__enumext_joined_item_viii_int }
3671     {
3672       \int_eval:n
3673       { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int }
3674     }
3675     \int_set:Nn \l__enumext_joined_item_viii_int
3676     {
3677       \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int
3678     }
3679   }
3680   \int_compare:nNnTF { \l__enumext_joined_item_viii_int } > { \c_one_int }
3681   {
3682     \int_set_eq:NN \l__enumext_joined_item_aux_viii_int \l__enumext_joined_item_viii_int
3683     \int_decr:N \l__enumext_joined_item_aux_viii_int
3684     \int_add:Nn \l__enumext_item_column_pos_viii_int { \l__enumext_joined_item_aux_viii_int }
3685     \int_gadd:Nn \g__enumext_item_count_all_viii_int { \l__enumext_joined_item_aux_viii_int }
3686     \dim_set:Nn \l__enumext_joined_width_viii_dim
3687     {
3688       \l__enumext_item_width_viii_dim * \l__enumext_joined_item_viii_int
3689       + ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim
3690         + \l__enumext_columns_sep_viii_dim
3691         ) * \l__enumext_joined_item_aux_viii_int
3692     }
3693     \dim_set_eq:NN \itemwidth \l__enumext_joined_width_viii_dim
3694   }
3695   {
3696     \dim_set_eq:NN \l__enumext_joined_width_viii_dim \l__enumext_item_width_viii_dim
3697     \dim_set_eq:NN \itemwidth \l__enumext_item_width_viii_dim
3698   }
3699 }

```

(End of definition for \\_\_enumext\_starred\_joined\_item\_viii:n)

\\_\_enumext\_start\_mini\_viii:

The implementation of the mini-env key is identical to the one used in the enumext\* environment.

\\_\_enumext\_stop\_mini\_viii:

```

3700 \cs_new_protected:Nn \__enumext_start_mini_viii:
3701 {

```

```

3702 \dim_compare:nNt { \l__enumext_minipage_right_viii_dim } > { \c_zero_dim }
3703 {
3704   \dim_set:Nn \l__enumext_minipage_left_viii_dim
3705   {
3706     \linewidth
3707     - \l__enumext_minipage_right_viii_dim
3708     - \l__enumext_minipage_hsep_viii_dim
3709   }
3710   \bool_set_true:N \l__enumext_minipage_active_viii_bool
3711   \dim_gset_eq:NN
3712     \g__enumext_minipage_right_viii_dim
3713     \l__enumext_minipage_right_viii_dim
3714   \__enumext_mini_addvspace_viii:
3715   \nointerlineskip\noindent
3716   \begin{__enumext_mini_env*}{ \l__enumext_minipage_left_viii_dim }
3717 }
3718 }
3719 \cs_new_protected:Nn \__enumext_stop_mini_viii:
3720 {
3721   \bool_if:NT \l__enumext_minipage_active_viii_bool
3722   {
3723     \end{__enumext_mini_env*}
3724     \hfill
3725     \bool_gset_true:N \g__enumext_minipage_active_viii_bool
3726   }
3727 }
3728 \__enumext_after_env:nn {keyans*}
3729 {
3730   \bool_if:NT \g__enumext_minipage_active_viii_bool
3731   {
3732     \begin{__enumext_mini_env*}{ \g__enumext_minipage_right_viii_dim }
3733     \par\addvspace { \g__enumext_minipage_right_skip }
3734     \bool_if:NF \g__enumext_minipage_center_viii_bool
3735     {
3736       \centering
3737     }
3738     \tl_use:N \g__enumext_miniright_code_viii_tl % the code
3739     \end{__enumext_mini_env*}
3740     \par\addvspace{ \g__enumext_minipage_after_skip }
3741   }
3742   \bool_gset_false:N \g__enumext_minipage_active_viii_bool
3743   \bool_gset_true:N \g__enumext_minipage_center_viii_bool
3744   \tl_gclear:N \g__enumext_miniright_code_viii_tl
3745   \dim_gzero:N \g__enumext_minipage_right_viii_dim
3746 }

```

(End of definition for \\_\_enumext\_start\_mini\_viii: and \\_\_enumext\_stop\_mini\_viii:.)

**keyans\*** First we will generate the environment and we will give a temporary definition to \\_\_enumext\_stop\_item\_tmp\_viii: equal to \noindent and next to \item equal to \\_\_enumext\_start\_item\_tmp\_viii: which we will redefine later.

```

3747 \NewDocumentEnvironment{keyans*}{ o }
3748 {
3749   \__enumext_safe_exec_viii:
3750   \__enumext_parse_keys_viii:n {#1}
3751   \__enumext_before_list_viii:
3752   \__enumext_start_list:nn { }
3753   {
3754     \__enumext_list_arg_two_viii:
3755     \__enumext_before_keys_exec_viii:
3756   }
3757   \__enumext_starred_columns_set_viii:
3758   \item[] \scan_stop:
3759   \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \noindent
3760   \cs_set_eq:NN \item \__enumext_start_item_tmp_viii:
3761 }
3762 {
3763   \__enumext_stop_item_tmp_viii:
3764   \__enumext_remove_extra_parsep_viii:
3765   \__enumext_check_starred_cmd:n { item }
3766   \__enumext_stop_list:

```

```

3767   \__enumext_after_list_viii:
3768   }

```

(End of definition for `keyans*`. This function is documented on page 11.)

`\__enumext_safe_exec_viii:` First check the maximum nesting level for the `keyans*` environment.

```

3769 \cs_new_protected:Nn \__enumext_safe_exec_viii:
3770 {
3771   \int_incr:N \__enumext_keyans_level_h_int
3772   \int_compare:nNnT { \__enumext_keyans_level_h_int } > { 1 }
3773   {
3774     \msg_error:nn { enumext } { nested }
3775   }
3776   \__enumext_keyans_save_start_line:
3777   % Set false for interfering with enumext nested in keyans* (yes, its possible and crayze)
3778   \bool_set_false:N \__enumext_store_active_bool
3779   \int_compare:nNnT { \__enumext_level_int } > { 1 }
3780   {
3781     \msg_error:nn { enumext } { keyans-wrong-level }
3782   }
3783 }

```

(End of definition for `\__enumext_safe_exec_viii:`)

`\__enumext_parse_keys_viii:n` Parse [`<key = val>`] for `keyans*`.

```

3784 \cs_new_protected:Npn \__enumext_parse_keys_viii:n #1
3785 {
3786   \tl_if_novalue:nF {#1}
3787   {
3788     \keys_set:nn { enumext / keyans* } {#1}
3789   }
3790 }

```

(End of definition for `\__enumext_parse_keys_viii:n`)

`\__enumext_before_list_viii:` The function `\__enumext_before_list_viii:` will add the vertical spacing on the environment if the `above` key is active next to the `{<code>}` defined by the `before*` key if it is active, the call the function `\__enumext_start_mini_viii:` handle by `mini-env`.

```

3791 \cs_new_protected:Nn \__enumext_before_list_viii:
3792 {
3793   \__enumext_vspace_above_viii:
3794   \__enumext_before_args_exec_viii:
3795   \__enumext_start_mini_viii:
3796 }

```

(End of definition for `\__enumext_before_list_viii:`)

`\__enumext_after_list_viii:` The function `\__enumext_after_list:` first call the function `\__enumext_stop_mini_viii:`, then apply the `{<code>}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```

3797 \cs_new_protected:Nn \__enumext_after_list_viii:
3798 {
3799   \__enumext_stop_mini_viii:
3800   \__enumext_after_stop_list_viii:
3801   \__enumext_vspace_below_viii:
3802 }

```

(End of definition for `\__enumext_after_list_viii:`)

### 10.35.2 The command `\item` in `keyans*`

The idea here is to make the `\item` command behave in the same way as in the `keyans` environment with the difference of the optional argument (`<number>`) which works in the same way as in the `enumext*` environment. In simple terms we want to store the `<label>` next to the [`<content>`] if it is present in the `<sequence>` and `<prop list>` defined by `save-ans` key for `\item*`, `\item* [<content>]`, `\item(<number>)*` and `\item(<number>)* [<content>]` commands.

`\__enumext_start_item_tmp_viii:` First we will call the function `\__enumext_stop_item_tmp_viii:` that we will redefine later, we will increment the value of `\l__enumext_item_column_pos_viii_int` that will count the item's by rows and the value of `\g__enumext_item_count_all_viii_int` that will count the total of item's in the environment. After that we will call the function `\__enumext_item_peek_args_viii:` that will handle the arguments passed to `\item`.

```

3803 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_viii:
3804 {
3805   \__enumext_stop_item_tmp_viii:
3806   \int_incr:N \l__enumext_item_column_pos_viii_int
3807   \int_gincr:N \g__enumext_item_count_all_viii_int
3808   \__enumext_item_peek_args_viii:
3809 }

```

(End of definition for `\__enumext_start_item_tmp_viii:`.)

`\__enumext_item_peek_args_viii:` The function `\__enumext_item_peek_args_viii:` will handle the `\item(<number>)`. Look for the argument “(”, if it is present we will call the function `\__enumext_joined_item_viii:w (<number>)`, which is in charge of joining the item's in the same row, in case they are not present we will set the default value (1).

```

3810 \cs_new_protected:Nn \__enumext_item_peek_args_viii:
3811 {
3812   \peek_meaning:NTF (
3813     { \__enumext_joined_item_viii:w }
3814     { \__enumext_joined_item_viii:w (1) }
3815   }

```

(End of definition for `\__enumext_item_peek_args_viii:`.)

`\__enumext_joined_item_viii:w` The function `\__enumext_joined_item_viii:w` will first call the function `\__enumext_starred_joined_item_viii:n` in charge of setting the *width* of the box that will store the content passed to `\item`. Then we will look for the argument “\*”, if it is present we will call the function `\__enumext_starred_item_viii:w` otherwise we will call the function `\__enumext_standard_item_viii:w`.

```

3816 \cs_new_protected:Npn \__enumext_joined_item_viii:w (#1)
3817 {
3818   \__enumext_starred_joined_item_viii:n {#1}
3819   \peek_meaning_remove:NTF *
3820     { \__enumext_starred_item_viii:w }
3821     { \__enumext_standard_item_viii:w }
3822 }

```

(End of definition for `\__enumext_joined_item_viii:w`.)

`\__enumext_standard_item_viii:w` The function `\__enumext_standard_item_viii:w` will first look for the argument “[”, if present it will set the state of the variable `\l__enumext_wrap_label_opt_viii_bool` equal to the state of the variable `\l__enumext_wrap_label_opt_viii_bool` handled by the key `wrap-label*` and finally execute the *non-enumerated* version `\item[<custom>]` by means of the function `\__enumext_start_item_viii:w`, otherwise we will set the value of the variable `\l__enumext_wrap_label_viii_bool` handled by the `wrap-label` key to true and set the switch `\if@noitemarg` to true to execute the *enumerated* version of `\item` by means of the function `\__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ]`.

```

3823 \cs_new_protected:Npn \__enumext_standard_item_viii:w
3824 {
3825   \bool_set_false:N \l__enumext_item_starred_viii_bool
3826   \peek_meaning:NTF [
3827     {
3828       \bool_set_eq:NN
3829         \l__enumext_wrap_label_viii_bool
3830         \l__enumext_wrap_label_opt_viii_bool
3831       \__enumext_start_item_viii:w
3832     }
3833     {
3834       \bool_set_true:N \l__enumext_wrap_label_viii_bool
3835       \legacy_if_set_true:n { @noitemarg }
3836       \__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ]
3837     }
3838   }

```

(End of definition for `\__enumext_standard_item_viii:w`.)

```

\__enumext_starred_item_viii:w
\__enumext_starred_item_viii_aux_i:w
\__enumext_starred_item_viii_aux_ii:w

```

The function `\__enumext_starred_item_viii:w` together with the specified auxiliary functions `aux_i:w` and `aux_ii:w` execute `\item*` and `\item*[\langle content \rangle]`.

```

3839 \cs_new_protected:Npn \__enumext_starred_item_viii:w
3840 {
3841   \bool_set_true:N \l__enumext_item_starred_viii_bool
3842   \bool_set_true:N \l__enumext_wrap_label_viii_bool
3843   \peek_meaning:NTF [
3844     { \__enumext_starred_item_viii_aux_i:w }
3845     { \__enumext_starred_item_viii_aux_ii:w }
3846   ]

```

The function `\__enumext_starred_item_viii_aux_i:w` will save the optional argument to `\item*` in `\l__enumext_keyans_item_opt_tl` and will save this argument along with the spacing set by the key `save-sep` in variable `\l__enumext_store_keyans_label_tl` if present, then call the function `\__enumext_starred_item_viii_aux_ii:w`.

```

3847 \cs_new_protected:Npn \__enumext_starred_item_viii_aux_i:w [#1]
3848 {
3849   \tl_clear:N \l__enumext_store_keyans_label_tl
3850   \tl_if_novalue:nF { #1 }
3851   {
3852     \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_tl
3853     {
3854       \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \l__enumext_store_keyans_item_opt_sep_tl }
3855       \tl_put_right:Ne \l__enumext_store_keyans_label_tl { #1 }
3856     }
3857     \tl_set:Ne \l__enumext_keyans_item_opt_tl { #1 }
3858   }
3859   \__enumext_starred_item_viii_aux_ii:w
3860 }
3861 \cs_new_protected:Npn \__enumext_starred_item_viii_aux_ii:w
3862 {
3863   \legacy_if_set_true:n { @noitemarg }
3864   \__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ]
3865 }

```

(End of definition for `\__enumext_starred_item_viii:w`, `\__enumext_starred_item_viii_aux_i:w`, and `\__enumext_starred_item_viii_aux_ii:w`.)

```
\__enumext_starred_item_exec:
```

The function `\__enumext_starred_item_exec:` will be in charge of storing the current *label* for `\item*` followed by the `[\langle content \rangle]` for `\item*[\langle content \rangle]` if present in the *sequence* and *prop list* set by the `save-ans` key. In this same function the keys `show-ans`, `show-pos` and `save-ref` are implemented.

```

3866 \cs_new_protected:Nn \__enumext_starred_item_exec:
3867 {
3868   \tl_put_left:Ne \l__enumext_store_keyans_label_tl { \l__enumext_label_viii_tl }
3869   \__enumext_store_addto_prop:V \l__enumext_store_keyans_label_tl
3870   \__enumext_keyans_store_ref:
3871   \tl_put_left:Ne \l__enumext_store_keyans_label_tl { \item }
3872   \__enumext_keyans_addto_seq_link:
3873   \int_gincr:N \g__enumext_check_starred_cmd_int
3874   \bool_if:NT \l__enumext_show_answer_bool
3875   {
3876     \__enumext_print_keyans_box:NN \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
3877   }
3878   \bool_if:NT \l__enumext_show_position_bool
3879   {
3880     \tl_set:Ne \l__enumext_mark_answer_sym_tl
3881     {
3882       \group_begin:
3883       \exp_not:N \normalfont
3884       \exp_not:N \footnotesize [ \int_eval:n
3885         {
3886           \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
3887         }
3888       ]
3889       \group_end:
3890     }
3891     \__enumext_print_keyans_box:NN \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
3892   }
3893 }

```

(End of definition for `\__enumext_starred_item_exec:`.)

### Real definition of `\item` in `keyans`\*

The implementation at this point is very similar to that of the `enumext`\* environment.

```

3894 \cs_new_protected_nopar:Npn \__enumext_start_item_viii:w [#1]
3895 {
3896   \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \__enumext_stop_item_viii:
3897   \legacy_if:nT { @noitemarg }
3898   {
3899     \legacy_if_set_false:n { @noitemarg }
3900     \legacy_if:nT { @nmbrrlist }
3901     {
3902       \bool_if:NT \l__enumext_hyperref_bool
3903       {
3904         \legacy_if_set_true:n { @hyper@item }
3905       }
3906       \refstepcounter{enumXviii}
3907     }
3908   }

```

Here we start capturing `\item` and its contents into a group using the plain form of the `lrbox` environment.

```

3909   \group_begin:
3910   \lrbox{ \l__enumext_item_text_viii_box }
3911   \bool_if:NF \l__enumext_footnotes_key_bool
3912   {
3913     \__enumext_renew_footnote:
3914   }
3915   \bool_if:NT \l__enumext_item_starred_viii_bool
3916   {
3917     \__enumext_starred_item_exec:
3918   }
3919   \group_begin:
3920   \tl_use:N \l__enumext_label_font_style_viii_tl
3921   \bool_if:NTF \l__enumext_wrap_label_viii_bool
3922   {
3923     \makebox[ \l__enumext_labelwidth_viii_dim ][ \l__enumext_align_label_viii_str ]
3924     { \__enumext_wrapper_label_viii:n {#1} }
3925   }
3926   {
3927     \makebox[ \l__enumext_labelwidth_viii_dim ][ \l__enumext_align_label_viii_str ]{ #1 }
3928   }
3929   \group_end:
3930   \skip_horizontal:N \l__enumext_labelsep_viii_dim
3931   \tl_use:N \l__enumext_after_list_args_viii_tl
3932   \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_viii_dim }
3933   \skip_set_eq:NN \parindent \l__enumext_listparindent_viii_dim
3934   \skip_set_eq:NN \parskip \l__enumext_parsep_viii_skip
3935   \bool_if:NT \l__enumext_item_starred_viii_bool
3936   {
3937     \tl_use:N \l__enumext_fake_item_indent_viii_tl
3938     \__enumext_keyans_show_item_opt: \skip_horizontal:n { -\l__enumext_fake_item_indent.
3939   }
3940   {
3941     \tl_use:N \l__enumext_fake_item_indent_viii_tl
3942   }
3943 }

```

(End of definition for `\__enumext_start_item_viii:w`.)

`\__enumext_stop_item_viii:` The function `\__enumext_stop_item_viii:` shall terminate with the capture of `\item` and its *(contents)*. Close the environments `minipage`, `lrbox` and the group. Then we only have to set the width of the box and print it next to `\footnote`, and add the horizontal and vertical separation between the boxes.

```

3944 \cs_new_protected_nopar:Nn \__enumext_stop_item_viii:
3945 {
3946   \__enumext_endminipage:
3947   \endlrbox
3948   \group_end:
3949   \box_set_wd:Nn \l__enumext_item_text_viii_box
3950   {
3951     \l__enumext_joined_width_viii_dim
3952     + \l__enumext_labelwidth_viii_dim
3953     + \l__enumext_labelsep_viii_dim
3954   }

```



```

3955 \int_set:Nn \hbadness { 10000 }
3956 \box_use:N \l__enumext_item_text_viii_box
3957 \bool_if:NF \l__enumext_footnotes_key_bool
3958 {
3959   \__enumext_print_footnote:
3960 }
3961 \int_compare:nNnTF { \l__enumext_item_column_pos_viii_int } = { \l__enumext_columns_viii_int }
3962 {
3963   \par\noindent
3964   \int_zero:N \l__enumext_item_column_pos_viii_int
3965 }
3966 { \hspace{ \l__enumext_columns_sep_viii_dim } }
3967 }

```

(End of definition for `\__enumext_stop_item_viii:`)

`\__enumext_remove_extra_parsep_viii:`

Finally we will remove the vertical space equal to `\parsep` when the total number of items is divisible by the number of items in the last row of the environment.

```

3968 \cs_new_protected:Nn \__enumext_remove_extra_parsep_viii:
3969 {
3970   \int_compare:nNnT
3971   {
3972     \int_mod:nn { \g__enumext_item_count_all_viii_int } { \l__enumext_columns_viii_int }
3973   }
3974   =
3975   { \c_zero_int }
3976   {
3977     \par
3978     \vspace{ -\l__enumext_itemsep_viii_skip }
3979     \int_gzero:N \g__enumext_item_count_all_viii_int
3980   }
3981 }

```

(End of definition for `\__enumext_remove_extra_parsep_viii:`)

### 10.36 The command `\getkeyans`

`\getkeyans`

The `\getkeyans` command takes a mandatory argument of the form  $\langle store\ name : position \rangle$ . Retrieve a “single” content stored by `\anskey`, `\anspic*` and `\item*` from  $\langle prop\ list \rangle$  defined by `save-ans` key.

```

3982 \NewDocumentCommand \getkeyans { m }
3983 {
3984   \exp_args:Ne \__enumext_getkeyans_aux:n
3985   { \tl_to_str:e { \text_expand:n {#1} } }
3986 }

```

(End of definition for `\getkeyans`. This function is documented on page 13.)

`\__enumext_getkeyans_aux:n`

The internal function `\__enumext_getkeyans_aux:n` is in charge of *splitting* the  $\langle argument \rangle$  using “:”. If “:” is omitted it will return an error.

```

3987 \cs_new_protected:Npn \__enumext_getkeyans_aux:n #1
3988 {
3989   \str_if_in:nnTF {#1} { : }
3990   {
3991     \use:e
3992     {
3993       \cs_set:Npn \exp_not:N \__enumext_tmp:w ##1 \c_colon_str ##2 \scan_stop:
3994       { {##1} {##2} }
3995     }
3996     \exp_after:wN \__enumext_getkeyans:nn \__enumext_tmp:w #1 \scan_stop:
3997   }
3998   { \msg_error:nnn { enumext } { missing-colon } {#1} }
3999 }

```

(End of definition for `\__enumext_getkeyans_aux:n`)

`\__enumext_getkeyans:nn`

The internal function `\__enumext_getkeyans:nn` will check for the existence of the  $\langle prop\ list \rangle$ , if it does not exist it will return an error message, then it will fetch the content specified by the second  $\langle argument \rangle$  from  $\langle prop\ list \rangle$ .

```

4000 \cs_new_protected:Npn \__enumext_getkeyans:nn #1 #2
4001 {
4002   \prop_if_exist:cF { g__enumext_#1_prop }

```

```

4003     { \msg_error:nnn { enumext } { undefined-storage-anskey } {#1} }
4004 \group_begin:
4005     \prop_item:cn { g__enumext_#1_prop }{#2}
4006 \group_end:
4007 }

```

(End of definition for \\_\_enumext\_getkeyans:nn.)

### 10.37 The command \printkeyans

The `\printkeyans` command prints “all stored content” in the *sequence* defined by the `save-ans` key. The first thing we will do is to define a set of *keys* with which we will control the options of the different nesting levels for the `enumext` and `enumext*` environment by storing the values of these in the token list variables `\l__enumext_print_keyans_X_tl`.

```

4008 \keys_define:nn { keyanskey / print }
4009 {
4010     level-1 .code:n      = \tl_put_right:Nn \l__enumext_print_keyans_i_tl
4011                       {
4012                         \setenumext[level,1] {#1} \setenumext[print,1] {#1}
4013                       },
4014     level-1 .initial:n   = { label=\arabic*., nosep, columns=2, first=\small, font=\small },
4015     level-2 .code:n      = \tl_put_right:Nn \l__enumext_print_keyans_ii_tl
4016                       {
4017                         \setenumext[level,2] {#1} \setenumext[print,2] {#1}
4018                       },
4019     level-2 .initial:n   = { nosep, label=(\alph*), first=\small, font=\small },
4020     level-3 .code:n      = \tl_put_right:Nn \l__enumext_print_keyans_iii_tl
4021                       {
4022                         \setenumext[level,3] {#1} \setenumext[print,3] {#1}
4023                       },
4024     level-3 .initial:n   = { nosep, label=\roman*., first=\small, font=\small },
4025     level-4 .code:n      = \tl_put_right:Nn \l__enumext_print_keyans_iv_tl
4026                       {
4027                         \setenumext[level,4] {#1} \setenumext[print,4] {#1}
4028                       },
4029     level-4 .initial:n   = { nosep, label=\Alph*., first=\small, font=\small },
4030     level-* .code:n      = \tl_put_right:Nn \l__enumext_print_keyans_vii_tl % starred
4031                       {
4032                         \setenumext[enumext*] {#1} %%\setenumext[print,*] {#1}
4033                       },
4034     level-* .initial:n   = { label=\arabic*., nosep, columns=2, first=\small, font=\small },
4035 }

```

`\printkeyans` Create a user command to print “all stored content” in *sequence* for `\anskey`, `\item*` and `\anspic*`.

```

4036 \NewDocumentCommand \printkeyans { s O{} m }
4037 {
4038     \group_begin:
4039     \tl_use:N \l__enumext_print_keyans_i_tl
4040     \tl_use:N \l__enumext_print_keyans_ii_tl
4041     \tl_use:N \l__enumext_print_keyans_iii_tl
4042     \tl_use:N \l__enumext_print_keyans_iv_tl
4043     \tl_use:N \l__enumext_print_keyans_vii_tl
4044     \__enumext_printkeyans:nnn { #1 } { #2 } { #3 }
4045 \group_end:
4046 }

```

(End of definition for `\printkeyans`. This function is documented on page 13.)

`\__enumext_printkeyans:nnn` The internal function `\__enumext_printkeyans:nnn` will check for the existence of the *sequence*, if it does not exist it will return an error message, then it will fetch the content specified by the first argument mapping the *sequence*.

#1: starred  
#2: key-val  
#3: seq-name

```

4047 \cs_new_protected:Npn \__enumext_printkeyans:nnn #1 #2 #3
4048 {
4049     \seq_if_exist:cTF { g__enumext_#3_seq }
4050     {
4051         \seq_if_empty:cF { g__enumext_#3_seq }
4052         {

```

```

4053         %%\seq_show:c { g__enumext_#3_seq }
4054         \bool_if:nTF {#1}
4055         {
4056             \begin{enumext*}[#2]
4057             \seq_map_inline:cn { g__enumext_#3_seq } { ##1 }
4058             \end{enumext*}
4059         }
4060         {
4061             \begin{enumext}[#2]
4062             \seq_map_inline:cn { g__enumext_#3_seq } { ##1 }
4063             \end{enumext}
4064         }
4065     }
4066 }
4067 {
4068     \msg_error:nnn { enumext } { undefined-storage-anskey } {#3}
4069 }
4070 }

```

(End of definition for `\__enumext_printkeyans:nnn`.)

### 10.38 The command `\setenumext`

First we define a “*meta families*” of `(keys)` to access from `\setenumext`.

```

4071 \keys_define:nn { enumext / meta-families }
4072 {
4073     level-1 .code:n = { \keys_set:nn { enumext / level-1 } {#1} } ,
4074     level-2 .code:n = { \keys_set:nn { enumext / level-2 } {#1} } ,
4075     level-3 .code:n = { \keys_set:nn { enumext / level-3 } {#1} } ,
4076     level-4 .code:n = { \keys_set:nn { enumext / level-4 } {#1} } ,
4077     keyans .code:n = { \keys_set:nn { enumext / keyans } {#1} } ,
4078     enumext* .code:n = { \keys_set:nn { enumext / enumext* } {#1} } ,
4079     keyans* .code:n = { \keys_set:nn { enumext / keyans* } {#1} } ,
4080     print-1 .code:n = { \keys_set:nn { keyanskey / print } { level-1 = {#1} } } ,
4081     print-2 .code:n = { \keys_set:nn { keyanskey / print } { level-2 = {#1} } } ,
4082     print-3 .code:n = { \keys_set:nn { keyanskey / print } { level-3 = {#1} } } ,
4083     print-4 .code:n = { \keys_set:nn { keyanskey / print } { level-4 = {#1} } } ,
4084     print-* .code:n = { \keys_set:nn { keyanskey / print } { level-* = {#1} } } ,
4085     unknown .code:n = { \msg_error:nn { enumext } { unknown-key-family } } ,
4086 }

```

We store them in the constant sequence `\c__enumext_all_families_seq` separated by commas.

```

4087 \seq_const_from_clist:Nn \c__enumext_all_families_seq
4088 {
4089     level-1 , level-2 , level-3 , level-4 , keyans , enumext* ,
4090     keyans* , print-1 , print-2 , print-3 , print-4 , print-* ,
4091 }

```

`\setenumext` Now we define the user command `\setenumext`.

```

4092 \NewDocumentCommand \setenumext { o +m }
4093 {
4094     \tl_if_novalue:nTF {#1}
4095     {
4096         \seq_map_inline:Nn \c__enumext_all_families_seq
4097     }
4098     {
4099         \seq_clear:N \l__enumext_setkey_tmpa_seq
4100         \seq_set_from_clist:Nn \l__enumext_setkey_tmpb_seq {#1}
4101         \int_set:Nn \l__enumext_setkey_tmpa_int
4102         {
4103             \seq_count:N \l__enumext_setkey_tmpb_seq
4104         }
4105         \int_compare:nNnTF { \l__enumext_setkey_tmpa_int } > { 1 }
4106         {
4107             \seq_pop_left:NN \l__enumext_setkey_tmpb_seq \l__enumext_setkey_tmpa_tl
4108             \seq_map_function:NN \l__enumext_setkey_tmpb_seq \l__enumext_set_parse:n
4109             \seq_set_map_e:NNn \l__enumext_setkey_tmpa_seq \l__enumext_setkey_tmpa_seq
4110             {
4111                 \tl_use:N \l__enumext_setkey_tmpa_tl - ##1
4112             }
4113         }
4114     }

```

```

4115         \seq_put_right:Ne \l__enumext_setkey_tmpa_seq { \tl_trim_spaces:n {#1} }
4116     }
4117     \seq_if_empty:NTF \l__enumext_setkey_tmpa_seq
4118     { \seq_map_inline:Nn \c__enumext_all_families_seq }
4119     { \seq_map_inline:Nn \l__enumext_setkey_tmpa_seq }
4120 }
4121 {
4122     \keys_set:nn { enumext / meta-families } { ##1 = {#2} }
4123 }
4124 }

```

(End of definition for `\setenumext`. This function is documented on page 5.)

```

__enumext_set_parse:n
__enumext_set_error:nn

```

Internal functions used by the `\setenumext` command.

```

4125 \cs_new_protected:Npn \__enumext_set_parse:n #1
4126 {
4127     \tl_set:Ne \l__enumext_setkey_tmpb_tl { \tl_trim_spaces:n {#1} }
4128     \int_step_inline:nnn { 0 } { 4 } %<- max level
4129     { \tl_remove_all:Nn \l__enumext_setkey_tmpb_tl {##1} }
4130     \tl_if_empty:NTF \l__enumext_setkey_tmpb_tl
4131     {
4132         \seq_put_right:Ne \l__enumext_setkey_tmpa_seq
4133         { \tl_trim_spaces:n {#1} }
4134     }
4135     { \__enumext_set_error:nn {#1} { } }
4136 }
4137 \cs_new_protected:Npn \__enumext_set_error:nn #1 #2
4138 { \msg_error:nnn { enumext } { invalid-key } {#1} {#2} }

```

(End of definition for `\__enumext_set_parse:n` and `\__enumext_set_error:nn`.)

## 10.39 Messages

Message used by package-load for `multicol` and `hyperref` packages.

```

4139 \msg_new:nnn { enumext } { package-load }
4140 {
4141     The ~ '#1' ~ package ~ is ~ already ~ loaded.
4142 }
4143 \msg_new:nnn { enumext } { package-not-load }
4144 {
4145     The ~ '#1' ~ package ~ will ~ be ~ loaded ~ as ~ a ~ dependency.
4146 }
4147 \msg_new:nnn { enumext } { package-load-foot }
4148 {
4149     The ~ '#1' ~ package ~ is ~ loaded ~ with ~ the ~ option ~ '#2'.
4150 }

```

Message used in the creation of counters by `enumext` package.

```

4151 \msg_new:nnn { enumext } { counters }
4152 {
4153     The ~ counter ~ '#1' ~ is ~ already ~ defined ~ by ~ some ~ \\
4154     package ~ or ~ macro, ~ it ~ cannot ~ be ~ continued.
4155 }

```

Message used in the creation of *(prop list)* by `enumext` package. los valores seria save-name, prop-count, -seqcount, y int-val

```

4156 \msg_new:nnn { enumext } { store-prop }
4157 {
4158     * ~ Package ~ enumext: ~ Creating ~ \c_backslash_str g__enumext_#1_prop ~ \msg_line_context:.
4159 }
4160 \msg_new:nnn { enumext } { store-seq }
4161 {
4162     * ~ Package ~ enumext: ~ Creating ~ \c_backslash_str g__enumext_#1_seq ~ \msg_line_context:.
4163 }
4164 \msg_new:nnn { enumext } { store-int }
4165 {
4166     * ~ Package ~ enumext: ~ Creating ~ \c_backslash_str g__enumext_resume_#1_int ~ \msg_line_con
4167 }
4168 \msg_new:nnn { enumext } { prop-seq-int-hook }
4169 {
4170     * ~ Package ~ enumext: ~ Elements ~ in ~ \c_backslash_str g__enumext_#1_prop ~ = ~ #2.\\
4171     * ~ Package ~ enumext: ~ Elements ~ in ~ \c_backslash_str g__enumext_#1_seq ~ = ~ #3.\\
4172     * ~ Package ~ enumext: ~ Value ~ off ~ \c_backslash_str g__enumext_resume_#1_int ~ = ~ #4.

```

```

4173     }
4174 \msg_new:nnn { enumext } { item-answer-hook }
4175 {
4176     * ~ Package ~ enumext: ~ Value ~ off ~ \c_backslash_str g__enumext_item_number_int ~ = ~ #1.\
4177     * ~ Package ~ enumext: ~ Value ~ off ~ \c_backslash_str g__enumext_item_anskey_int ~ = ~ #2.\
4178     * ~ Package ~ enumext: ~ Difference ~ item_number_int ~ - ~ item_anskey_int ~ = ~ #3.
4179 }

```

Message used by [*key = val*] system and `\setenumext` command.

```

4180 \msg_new:nnn { enumext } { invalid-key }
4181 {
4182     The ~ key ~ '#1' ~ is ~ not ~ know ~ the ~ level ~ #2.
4183 }
4184 \msg_new:nnn { enumext } { unknown-key-family }
4185 {
4186     Unknown~key~family~`\l_keys_key_str'~for~enumext.
4187 }

```

Messages used in length calculation.

```

4188 \msg_new:nnn { enumext } { width-negative }
4189 {
4190     Ignoring ~ negative ~ value ~ '#1=#2' ~ \msg_line_context:.\
4191     The ~ key ~ '#1'~ accepts ~ values ~ >= ~ opt.
4192 }
4193 \msg_new:nnn { enumext } { width-zero }
4194 {
4195     Invalid ~ '#1=#2' ~ \msg_line_context:.\
4196     The ~ key ~ '#1'~ accepts ~ values ~ > ~ opt.
4197 }

```

Messages used by `show-length` key in `enumext`.

```

4198 \msg_new:nnn { enumext } { list-lengths }
4199 {
4200     **** ~ Lengths ~ used ~ by ~ 'enumext' ~ level ~ '#2' ~ \msg_line_context:~\c_space_tl ****\
4201     \__enumext_show_length:nnn { dim } { labelsep } {#1}
4202     \__enumext_show_length:nnn { dim } { labelwidth } {#1}
4203     \__enumext_show_length:nnn { dim } { itemindent } {#1}
4204     \__enumext_show_length:nnn { dim } { leftmargin } {#1}
4205     \__enumext_show_length:nnn { dim } { rightmargin } {#1}
4206     \__enumext_show_length:nnn { dim } { listparindent } {#1}
4207     \__enumext_show_length:nnn { skip } { topsep } {#1}
4208     \__enumext_show_length:nnn { skip } { parsep } {#1}
4209     \__enumext_show_length:nnn { skip } { partopsep } {#1}
4210     \__enumext_show_length:nnn { skip } { itemsep } {#1}
4211     ****
4212 }

```

Messages used by `show-length` key in `enumext*`, `keyans*` and `keyans`.

```

4213 \msg_new:nnn { enumext } { list-lengths-not-nested }
4214 {
4215     **** ~ Lengths ~ used ~ by ~ '#2' ~ environment ~ \msg_line_context:~\c_space_tl ****\
4216     \__enumext_show_length:nnn { dim } { labelsep } {#1}
4217     \__enumext_show_length:nnn { dim } { labelwidth } {#1}
4218     \__enumext_show_length:nnn { dim } { itemindent } {#1}
4219     \__enumext_show_length:nnn { dim } { leftmargin } {#1}
4220     \__enumext_show_length:nnn { dim } { rightmargin } {#1}
4221     \__enumext_show_length:nnn { dim } { listparindent } {#1}
4222     \__enumext_show_length:nnn { skip } { topsep } {#1}
4223     \__enumext_show_length:nnn { skip } { parsep } {#1}
4224     \__enumext_show_length:nnn { skip } { partopsep } {#1}
4225     \__enumext_show_length:nnn { skip } { itemsep } {#1}
4226     ****
4227 }

```

Messages used by `ref` key.

```

4228 \msg_new:nnn { enumext } { key-ref-empty }
4229 {
4230     Key ~ 'ref' ~ need ~ a ~ value ~ in ~ '#1'~ \msg_line_context:.
4231 }

```

Messages used by `save-ans` key.

```

4232 \msg_new:nnn { enumext } { save-ans-empty }
4233 {
4234     Key ~ 'save-ans' ~ need ~ a ~ value ~ in ~ '#1'~ \msg_line_context:.

```

```

4235     }
4236     \msg_new:nnn { enumext } { save-ans-log }
4237     {
4238         * ~ Package ~ enumext: ~ Start ~ \c_left_brace_str#1\c_right_brace_str \c_space_tl with ~ save-ans=#2 ~ \msg_line_context:.
4239     }
4240     \msg_new:nnn { enumext } { save-ans-log-hook }
4241     {
4242         * ~ Package ~ enumext: ~ Stop ~ \c_left_brace_str#1\c_right_brace_str \c_space_tl with ~ save-ans=#2 ~ \msg_line_context:.
4243     }
4244     \msg_new:nnn { enumext } { save-ans-hook }
4245     {
4246         Stop ~ storing ~ for ~ 'save-ans=#1' ~ \msg_line_context:.
4247     }

```

Messages used by the internal system to check answer used by `check-ans` key.

```

4248     \msg_new:nnn { enumext } { need-save-ans }
4249     {
4250         Key ~ '#1'~ works ~ only ~ with ~ the ~ 'save-ans' ~ key ~ in ~ '#2'~ \msg_line_context:.
4251     }
4252     \msg_new:nnn { enumext } { items-same-answer }
4253     {
4254         *****\\
4255         * ~ Package ~ enumext: ~ Checking ~ answers ~ in ~ '#1' ~ for ~ \c_left_brace_str #2 \c_right_brace_str
4256         * ~ started ~ #3 ~ and ~ close ~ \msg_line_context: : ~ 'OK', ~ all ~ items ~ with ~ answer.\\
4257         *****
4258     }
4259     \msg_new:nnn { enumext } { item-greater-answer }
4260     {
4261         Checking ~ answers ~ in ~ '#1' ~ for ~ \c_left_brace_str #2 \c_right_brace_str\\
4262         started ~ #3 ~ and ~ close ~ \msg_line_context: : ~'NOT ~ OK'\\
4263         Items ~ > ~ Answers.
4264     }
4265     \msg_new:nnn { enumext } { item-less-answer }
4266     {
4267         Checking ~ answers ~ in ~ '#1' ~ for ~ \c_left_brace_str #2 \c_right_brace_str\\
4268         started ~ #3 ~ and ~ close ~ \msg_line_context: : ~'NOT ~ OK'\\
4269         Items ~ < ~ Answers.
4270     }

```

Messages used by the internal system to check for “starred” `\item*` and `\anspic*` commands.

```

4271     \msg_new:nnn { enumext } { missing-starred }
4272     {
4273         Missing ~ '\c_backslash_str #1*' ~ #2.
4274     }
4275     \msg_new:nnn { enumext } { many-starred }
4276     {
4277         Many ~ '\c_backslash_str #1*' ~ #2.
4278     }

```

Message for the nesting depth of the environment `enumext`.

```

4279     \msg_new:nnn { enumext } { list-too-deep }
4280     {
4281         Too ~ deep ~ nesting ~ for ~ 'enumext' ~ \msg_line_context:~ \\
4282         The ~ maximum ~ level ~ of ~ nesting ~ is ~ 4.
4283     }

```

Messages used by `\anskey` and `\anspic` commands.

```

4284     \msg_new:nnn { enumext } { anskey-wrong-place }
4285     {
4286         Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
4287         '\c_backslash_str #1' ~ works ~ in ~ the ~ environment ~ '#2'.
4288     }
4289     \msg_new:nnn { enumext } { anspic-wrong-place }
4290     {
4291         Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
4292         '\c_backslash_str #1' ~ works ~ in ~ the ~ environment ~ '#2'.
4293     }
4294     \msg_new:nnn { enumext } { command-wrong-place }
4295     {
4296         Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
4297         '\c_backslash_str #1' ~ works ~ outside ~ the ~ environment ~ '#2'.

```

4298 }

Messages used by `keyans` and `keyanspic` environment.

```
4299 \msg_new:nnn { enumext } { keyans-nested }
4300 {
4301   The ~ environment ~ 'keyans' ~ can't ~ be ~ nested ~ \msg_line_context:.
4302 }
4303 \msg_new:nnn { enumext } { keyans-wrong-level }
4304 {
4305   Wrong ~ level ~ position ~ for ~ 'keyans' ~ \msg_line_context:~ \\
4306   The ~ environment ~ 'keyans' ~ can ~ only ~ be ~ in ~ the ~ first ~ level.
4307 }
4308 \msg_new:nnn { enumext } { wrong-place }
4309 {
4310   Wrong ~ place ~ for ~ '#1' ~ environment ~ \msg_line_context:~ \\
4311   '#1' ~ is ~ only ~ found ~ with ~ '#2' ~ in ~ 'enumext'.
4312 }
4313 \msg_new:nnn { enumext } { keyanspic-nested }
4314 {
4315   The ~ environment ~ 'keyanspic' ~ can't ~ be ~ nested ~ \msg_line_context:~.
4316 }
4317 \msg_new:nnn { enumext } { keyanspic-wrong-level }
4318 {
4319   Wrong ~ level ~ position ~ for ~ 'keyanspic' ~ \msg_line_context:~ \\
4320   The ~ environment ~ 'keyans' ~ can ~ only ~ be ~ in ~ the ~ first ~ level.
4321 }
```

Messages used by `\getkeyans` command.

```
4322 \msg_new:nnn { enumext } { undefined-storage-anskey }
4323 {
4324   Storage ~ named ~ '#1' ~ is ~ not ~ defined ~ \msg_line_context:.
4325 }
```

Messages used by `\miniright` command.

```
4326 \msg_new:nnn { enumext } { missing-miniright }
4327 {
4328   Missing ~ '\c_backslash_str miniright' ~ in ~ \msg_line_context:~ \\
4329   The ~ key ~ 'mini-env' ~ need ~ '\c_backslash_str miniright'.
4330 }
4331 \msg_new:nnn { enumext } { wrong-miniright-place }
4332 {
4333   Wrong ~ place ~ for ~ '\c_backslash_str miniright' ~ \msg_line_context:~ \\
4334   Works ~ in ~ 'enumext' ~ and ~ 'keyans' ~ with ~ key ~ 'mini-env'.
4335 }
4336 \msg_new:nnn { enumext } { wrong-miniright-use }
4337 {
4338   Wrong ~ use ~ for ~ '\c_backslash_str miniright' ~ \msg_line_context:~ \\
4339   '\c_backslash_str miniright' ~ need ~ a ~ key ~ 'mini-env'.
4340 }
```

Messages used by `enumext*` and `keyans*` environments.

```
4341 \msg_new:nnn { enumext } { nested }
4342 {
4343   The ~ starred ~ environment ~ can't ~ be ~ nested ~ \msg_line_context:.
4344 }
4345 \msg_new:nnn { enumext } { item-joined }
4346 {
4347   Items ~ joined ~ (#1) ~ > ~ #2 ~ columns ~ \msg_line_context:.
4348 }
4349 \msg_new:nnn { enumext } { item-joined-columns }
4350 {
4351   Not ~ space ~ to ~ join ~ items ~ (#1) ~ > ~ #2 ~ \msg_line_context:.
4352 }
```

## 10.40 Finish package

Finish package implementation.

```
4353 \file_input_stop:
4354 </package>
```

## 11 Index of Implementation

The italic numbers denote the pages where the corresponding entry is described, the numbers underlined and all others indicate the line on which they are implemented in the package code.

| Symbols                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\*</code>                     | 202                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>\+</code>                     | 194                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>\-</code>                     | 194                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>\\</code>                     | 210, 3146, 4153, 4170, 4171, 4176, 4177, 4190, 4195, 4200, 4215, 4254, 4255, 4256, 4261, 4262, 4267, 4268, 4281, 4286, 4291, 4296, 4305, 4310, 4319, 4328, 4333, 4338                                                                                                                                                                                                                                                                                                                                                                                   |
| A                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>above</code>                  | 1366                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>above*</code>                 | 1366                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>\addvspace</code>             | 1013, 1041, 1164, 1243, 1306, 1312, 1340, 1357, 2985, 3000, 3102, 3117, 3343, 3350, 3733, 3740                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>after</code>                  | 851                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>align</code>                  | 468                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>\Alph</code>                  | 32, 37                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>\Alph</code>                  | 420, 529, 574, 642, 4029                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>\alph</code>                  | 32, 37                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>\alph</code>                  | 421, 527, 4019                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>\anskey</code>                | 11, 66, 2126                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <code>\anspic</code>                | 13, 88, 3124                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <code>\anspic*</code>               | 63                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>\arabic</code>                | 27, 32                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>\arabic</code>                | 419, 526, 573, 4014, 4034                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| B                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>\b</code>                     | 2863, 2876, 3409, 3422                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>\baselineskip</code>          | 44                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>\baselineskip</code>          | 2086, 2094                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>before</code>                 | 851                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>before*</code>                | 851                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>below</code>                  | 1366                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>below*</code>                 | 1366                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| bool commands:                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>\bool_gset_false:N</code>     | 308, 309, 310, 3352, 3356, 3742                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>\bool_gset_true:N</code>      | 222, 231, 955, 1853, 1859, 3335, 3353, 3725, 3743                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>\bool_if:NTF</code>           | 360, 372, 389, 1388, 1402, 1415, 1426, 1437, 1448, 1459, 1470, 1523, 1540, 1545, 1553, 1580, 1618, 1623, 1630, 1634, 1656, 1661, 1669, 1676, 1707, 1715, 1807, 1840, 1927, 2048, 2072, 2079, 2107, 2138, 2151, 2161, 2181, 2306, 2317, 2321, 2360, 2375, 2450, 2461, 2465, 2578, 2608, 2682, 2698, 2760, 2770, 2800, 2805, 2853, 2861, 2874, 2919, 2969, 2983, 2991, 3030, 3087, 3100, 3108, 3126, 3331, 3340, 3344, 3399, 3407, 3420, 3452, 3462, 3545, 3550, 3558, 3562, 3577, 3606, 3721, 3730, 3734, 3874, 3878, 3902, 3911, 3915, 3921, 3935, 3957 |
| <code>\bool_if:nTF</code>           | 1341, 1358, 2189, 2619, 2654, 2718, 3147, 4054                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>\bool_if_p:N</code>           | 240, 254, 1687, 1688, 1696, 1697, 1820, 1850, 1851, 1856, 1857, 2172, 2215, 2216, 2240, 2249, 2250, 2262, 2278, 2437, 2438, 2475, 2476, 2892, 2905, 2907, 3154, 3155                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>\bool_lazy_all:nTF</code>     | 238, 252, 1818, 2238, 2247, 2260, 2276, 2890, 2903                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>\bool_lazy_and:nnTF</code>    | 218, 227, 1686, 1695, 1849, 1855, 2171, 2214, 2436                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>\bool_lazy_or:nnTF</code>     | 1748, 1755, 2474, 3153                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>\bool_new:N</code>            | 25, 26, 27, 28, 29, 30, 31, 51, 61, 82, 87, 88, 93, 94, 97, 115, 117, 119, 122, 123, 132, 133, 134, 142, 143, 157, 168, 170                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>\bool_not_p:n</code>          | 219, 228, 2173, 2265, 2280, 2893, 2894, 2906                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <code>\bool_set_eq:NN</code>        | 2586, 2634, 3495, 3828                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>\bool_set_false:N</code>      | 369, 1792, 1793, 3006, 3038, 3120, 3185, 3203, 3447, 3492, 3778, 3825                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>\bool_set_true:N</code>       | 245, 259, 351, 355, 461, 779, 1372, 1377, 1643, 1765, 1766, 2011, 2018, 2582, 2612, 2630, 2642, 2836, 2899, 2912, 2938, 3035, 3062, 3320, 3389, 3501, 3508, 3509, 3710, 3834, 3841, 3842                                                                                                                                                                                                                                                                                                                                                                |
| box commands:                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>\box_dp:N</code>              | 1060, 1064, 1068, 1079, 1083, 1094, 1103, 1109, 1119, 1132, 1138, 1144, 1175, 1176, 1177, 1180, 1190, 1194, 1203, 1210, 1215, 1223, 1252, 1253, 1256, 1263, 1276, 1284, 1290, 1298, 3215                                                                                                                                                                                                                                                                                                                                                                |
| <code>\box_new:N</code>             | 58, 163                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <code>\box_set_wd:Nn</code>         | 3598, 3949                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>\box_use:N</code>             | 3605, 3956                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>\box_wd:N</code>              | 427                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| C                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>\c</code>                     | 202, 203, 679, 681, 693, 695                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <code>\cB</code>                    | 203                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>\cE</code>                    | 203                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>\centering</code>             | 1343, 1360, 3236, 3346, 3736                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <code>check-ans</code>              | 1784                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Document class:                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>article</code>                | 38                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| clist commands:                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>\clist_const:Nn</code>        | 175                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>\clist_map_function:nN</code> | 3223                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>\clist_map_inline:Nn</code>   | 467, 721, 784, 850, 865, 946, 1382                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>\clist_map_inline:nn</code>   | 36, 47, 66, 72, 84, 96, 121, 151, 174, 492, 509, 789, 961, 1488, 1732, 1798, 1988, 2006, 2027, 2235, 2369, 2536, 2747, 2750, 2777, 2787, 2790, 2810                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>\columnbreak</code>           | 67                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>\columnbreak</code>           | 2175                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>columns</code>                | 930                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>columns*</code>               | 2007                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>columns-sep</code>            | 930                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>columns-sep*</code>           | 2007                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>\columnsep</code>             | 84, 86                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>\columnsep</code>             | 2963, 3084                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>\columnseprule</code>         | 84, 87                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>\columnseprule</code>         | 2967, 3086                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Commands provide by enumext:        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>\anskey</code>                | 24, 25, 59, 60, 64-71, 73, 82, 95, 105, 106, 110                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <code>\anspic*</code>               | 24, 25, 63, 70-72, 88-90, 105, 106                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>\anspic</code>                | 64, 65, 88-90, 110                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>\getkeyans</code>             | 64, 105, 111                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <code>\item*</code>                 | 24, 25, 63-65, 70-72, 75, 76, 96, 103, 105, 106                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>\itemwidth</code>             | 91, 98, 99                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>\item</code>                  | 75, 76, 91, 95-97, 99, 102                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>\miniright</code>             | 24, 42, 50, 51, 83, 84, 86, 87, 111                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>\printkeyans</code>           | 25, 65, 106                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>\setenumext</code>            | 25, 107-109                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |



Counters defined by `enumext`:

|                        |            |
|------------------------|------------|
| <code>enumXiii</code>  | 23, 32     |
| <code>enumXii</code>   | 23, 32     |
| <code>enumXiv</code>   | 23, 32     |
| <code>enumXi</code>    | 23, 32     |
| <code>enumXviii</code> | 23, 32     |
| <code>enumXvii</code>  | 23, 32, 97 |
| <code>enumXvi</code>   | 23, 32     |
| <code>enumXv</code>    | 23, 32     |

## cs commands:

|                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\cs_generate_variant:Nn</code>     | 429, 445, 685, 701, 2040, 2045, 2125, 2737, 3225                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>\cs_if_exist:NTF</code>            | 399                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>\cs_new:Nn</code>                  | 188                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>\cs_new:Npn</code>                 | 206, 1489, 1498, 1507                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>\cs_new_eq:NN</code>               | 335, 336, 337, 341, 342, 374, 375, 378, 379                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>\cs_new_protected:Nn</code>        | 198, 212, 236, 267, 294, 300, 306, 312, 318, 326, 346, 550, 613, 665, 866, 870, 874, 878, 882, 886, 890, 894, 898, 902, 906, 910, 914, 918, 922, 926, 962, 974, 998, 1015, 1026, 1050, 1125, 1149, 1166, 1228, 1245, 1267, 1302, 1308, 1383, 1397, 1411, 1422, 1433, 1444, 1455, 1466, 1551, 1654, 1667, 1684, 1705, 1733, 1738, 1763, 1803, 1813, 1847, 1862, 1869, 1878, 1883, 1888, 1893, 1902, 1907, 1912, 1917, 2046, 2070, 2077, 2105, 2112, 2226, 2358, 2373, 2401, 2434, 2470, 2482, 2490, 2541, 2545, 2564, 2615, 2650, 2666, 2676, 2692, 2830, 2888, 2917, 2924, 2947, 2977, 2989, 3028, 3052, 3070, 3095, 3106, 3143, 3187, 3201, 3221, 3226, 3242, 3310, 3329, 3381, 3434, 3441, 3450, 3460, 3477, 3617, 3632, 3700, 3719, 3769, 3791, 3797, 3810, 3866, 3968 |
| <code>\cs_new_protected:Npn</code>       | 180, 184, 382, 397, 414, 424, 430, 530, 575, 647, 672, 686, 1330, 1349, 1519, 1538, 1608, 1641, 1743, 1936, 2032, 2041, 2158, 2303, 2315, 2337, 2411, 2455, 2574, 2592, 2626, 2638, 2706, 2740, 2780, 2839, 2859, 3048, 3196, 3261, 3392, 3405, 3483, 3490, 3506, 3514, 3519, 3531, 3651, 3784, 3816, 3823, 3839, 3847, 3861, 3987, 4000, 4047, 4125, 4137                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>\cs_new_protected_nopar:Nn</code>  | 3470, 3593, 3803, 3944                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>\cs_new_protected_nopar:Npn</code> | 3537, 3894                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>\cs_set:Nn</code>                  | 2308                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>\cs_set:Npn</code>                 | 2236, 2274, 3993                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>\cs_set_eq:NN</code>               | 3371, 3372, 3539, 3759, 3760, 3896                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <code>\cs_set_protected:Nn</code>        | 790, 806, 818, 830                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <code>\cs_set_protected:Npn</code>       | 32, 41, 59, 67, 79, 85, 111, 147, 155, 446, 468, 497, 510, 557, 702, 722, 766, 785, 842, 851, 930, 947, 1366, 1477, 1724, 1784, 1953, 1989, 2007, 2228, 2362, 2525, 2738, 2778                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <code>\cs_to_str:N</code>                | 416, 439                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

## D

|                                          |      |
|------------------------------------------|------|
| <code>\d</code>                          | 194  |
| <code>\DeclareDocumentEnvironment</code> | 1043 |

## dim commands:

|                                 |                                                                                                                          |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| <code>\dim_abs:n</code>         | 2711, 2716                                                                                                               |
| <code>\dim_add:Nn</code>        | 3206                                                                                                                     |
| <code>\dim_compare:nNnTF</code> | 792, 808, 820, 832, 1332, 1351, 2708, 2713, 2719, 2725, 2727, 2729, 2929, 2952, 3056, 3074, 3198, 3244, 3312, 3634, 3702 |
| <code>\dim_compare:nTF</code>   | 2199                                                                                                                     |
| <code>\dim_gset_eq:NN</code>    | 3321, 3711                                                                                                               |
| <code>\dim_gzero:N</code>       | 3355, 3745                                                                                                               |
| <code>\dim_new:N</code>         | 55, 62, 63, 64, 81, 118, 128, 164, 165, 171                                                                              |

|                              |                                                                                                                                                                      |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\dim_set:Nn</code>     | 427, 780, 2019, 2606, 2711, 2716, 2718, 2721, 2722, 2726, 2728, 2731, 2732, 2734, 2932, 2955, 3058, 3076, 3228, 3246, 3253, 3296, 3314, 3533, 3636, 3643, 3686, 3704 |
| <code>\dim_set_eq:NN</code>  | 517, 564, 635, 639, 2601, 2749, 2789, 2878, 2963, 3084, 3303, 3306, 3307, 3424, 3524, 3693, 3696, 3697                                                               |
| <code>\dim_use:N</code>      | 793, 801, 1333, 1339, 2115, 2118, 2123, 2671, 2673, 2930, 2935, 2936, 2943, 2953, 2957, 2958, 2960                                                                   |
| <code>\dim_zero:N</code>     | 2967, 3086, 3207, 3208, 3209                                                                                                                                         |
| <code>\dim_zero_new:N</code> | 3259, 3649                                                                                                                                                           |
| <code>\c_zero_dim</code>     | 795, 809, 821, 833, 1333, 1351, 2201, 2708, 2713, 2719, 2726, 2930, 2953, 3056, 3074, 3244, 3312, 3634, 3702                                                         |

## E

|                           |                                                                                    |
|---------------------------|------------------------------------------------------------------------------------|
| <code>\end</code>         | 1336, 1354, 2074, 2109, 2982, 2999, 3099, 3116, 3333, 3349, 3723, 3739, 4058, 4063 |
| <code>\endlist</code>     | 30                                                                                 |
| <code>\endlist</code>     | 336                                                                                |
| <code>\endlrbox</code>    | 3596, 3947                                                                         |
| <code>\endminipage</code> | 30                                                                                 |
| <code>\endminipage</code> | 342                                                                                |
| <code>enumext</code>      | 5, <u>2811</u>                                                                     |

## enumext internal commands:

|                                                   |                                                      |
|---------------------------------------------------|------------------------------------------------------|
| <code>\l__enumext__check_start_line_env_tl</code> | 28                                                   |
| <code>\l__enumext__ref_the_count_tl</code>        | 34                                                   |
| <code>\l__enumext__resume_name_tl</code>          | 55                                                   |
| <code>__enumext_add_pre_parsep:</code>            | 43, 972, <u>974</u> , 974                            |
| <code>__enumext_after_args_exec:</code>           | 41, <u>866</u> , 878, 2823                           |
| <code>__enumext_after_args_exec_v:</code>         | 41, 42, <u>882</u> , 894, 3021                       |
| <code>__enumext_after_args_exec_vii:</code>       | 898, 922                                             |
| <code>__enumext_after_args_exec_viii:</code>      | 926                                                  |
| <code>__enumext_after_env:nn</code>               | 62, 85, 98, <u>184</u> , 184, 3009, 3338, 3631, 3728 |
| <code>__enumext_after_hyperref:</code>            | 30, 344, <u>346</u> , 346                            |
| <code>__enumext_after_list:</code>                | 84, 94, 101, 2828, <u>2989</u> , 2989                |
| <code>\l__enumext_after_list_args_v_tl</code>     | 896                                                  |
| <code>\l__enumext_after_list_args_vii_tl</code>   | 924, 3587                                            |
| <code>\l__enumext_after_list_args_viii_tl</code>  | 928, 3931                                            |
| <code>__enumext_after_list_v:</code>              | 87, 3026, <u>3106</u> , 3106                         |
| <code>__enumext_after_list_vii:</code>            | 3379, <u>3441</u> , 3441                             |
| <code>__enumext_after_list_viii:</code>           | 3767, <u>3797</u> , 3797                             |
| <code>__enumext_after_star_env:nn</code>          | 92                                                   |
| <code>__enumext_after_stop_list:</code>           | 41, 42, <u>866</u> , 874, 3004                       |
| <code>__enumext_after_stop_list_v:</code>         | 41, <u>882</u> , 890, 3121                           |
| <code>\l__enumext_after_stop_list_v_tl</code>     | 892                                                  |
| <code>__enumext_after_stop_list_vii:</code>       | <u>898</u> , 914, 3444                               |
| <code>\l__enumext_after_stop_list_vii_tl</code>   | 916                                                  |
| <code>__enumext_after_stop_list_viii:</code>      | 918, 3800                                            |
| <code>\l__enumext_after_stop_list_viii_tl</code>  | 920                                                  |
| <code>\l__enumext_align_label_vii_str</code>      | 3579, 3583                                           |
| <code>\l__enumext_align_label_viii_str</code>     | 3923, 3927                                           |
| <code>\l__enumext_align_label_X_str</code>        | <u>155</u>                                           |
| <code>\c__enumext_all_envs_clist</code>           | <u>175</u> , 467, 721, 784, 850, 865, 946, 1382      |
| <code>\c__enumext_all_families_seq</code>         | 107, 4087, 4096, 4118                                |
| <code>__enumext_anskey_wrapper:n</code>           | 1957, 2313                                           |
| <code>__enumext_at_begin_document:n</code>        | 30, <u>180</u> , 180, 333, 339                       |
| <code>__enumext_before_args_exec:</code>          | 40, <u>866</u> , 866, 2927                           |

```

\__enumext_before_args_exec_v: .. 41, 882, 882,
    3055
\__enumext_before_args_exec_vii: .. 898, 898,
    3438
\__enumext_before_args_exec_viii: 902, 3794
\__enumext_before_keys_exec: 40, 866, 870, 2821
\__enumext_before_keys_exec_v: .. 41, 882, 886,
    3019
\__enumext_before_keys_exec_vii: ..... 898
\__enumext_before_keys_exec_vii: 41, 906, 3367
\__enumext_before_keys_exec_viii: .. 41, 910,
    3755
\__enumext_before_list: ... 83, 2815, 2924, 2924
\__enumext_before_list_v: . 86, 3014, 3052, 3052
\__enumext_before_list_vii: 94, 3362, 3434, 3434
\__enumext_before_list_viii: .. 101, 3751, 3791,
    3791
\l__enumext_before_no_starred_key_v_tl 888
\l__enumext_before_no_starred_key_vii-
    tl ..... 908
\l__enumext_before_no_starred_key_viii-
    tl ..... 912
\l__enumext_before_starred_key_v_tl ... 884
\l__enumext_before_starred_key_vii_tl . 900
\l__enumext_before_starred_key_viii_tl 904
\__enumext_calc_hspace:NNNNNN 78, 2706, 2706,
    2737, 2742, 2782
\__enumext_check_ans_active: 60, 83, 1803, 1803,
    2928, 3437
\g__enumext_check_ans_item_tl ..... 72
\g__enumext_check_ans_key_bool 61, 62, 132, 308,
    1853, 1859, 1927
\l__enumext_check_ans_key_bool ... 61, 75, 132,
    1788, 1793, 1850, 1856
\__enumext_check_ans_key_hook: 61, 1847, 1847,
    3003, 3445
\__enumext_check_ans_level: 60, 1803, 1809, 1813
\__enumext_check_ans_log: 61, 62, 1893, 1893, 1931
\__enumext_check_ans_log_msg_greater: 1893,
    1899, 1912
\__enumext_check_ans_log_msg_less: 1893, 1897,
    1902
\__enumext_check_ans_log_msg_same_ok: 1893,
    1898, 1907
\__enumext_check_ans_msg_greater: 1869, 1875,
    1888
\__enumext_check_ans_msg_less: 1869, 1873, 1878
\__enumext_check_ans_msg_same_ok: 1869, 1874,
    1883
\__enumext_check_ans_show: .. 61, 62, 1869, 1869,
    1929
\g__enumext_check_ans_show_bool ..... 85
\l__enumext_check_answers_bool ... 59, 60, 132,
    1766, 1792, 1807, 2048, 2072, 2079, 2107, 2151, 2450,
    2578, 2608, 3550
\__enumext_check_starred_cmd:n 28, 63, 72, 1936,
    1936, 3024, 3182, 3765
\g__enumext_check_starred_cmd_int 132, 1939,
    1945, 1950, 2648, 3152, 3873
\l__enumext_check_start_line_env_tl 132, 273,
    280, 287, 1942, 1948, 1951
\l__enumext_columns_sep_v_dim 3074, 3076, 3084
\l__enumext_columns_sep_vii_dim .. 3244, 3246,
    3255, 3300, 3426, 3615
\l__enumext_columns_sep_viii_dim . 3634, 3636,
    3645, 3690, 3966
\l__enumext_columns_v_int 1171, 3072, 3080, 3092,
    3097
\l__enumext_columns_vii_int .. 3249, 3252, 3256,
    3264, 3268, 3271, 3277, 3283, 3287, 3413, 3610, 3621
\l__enumext_columns_viii_int . 3639, 3642, 3646,
    3654, 3658, 3661, 3667, 3673, 3677, 3961, 3972
\g__enumext_count_item_with_ans_int .... 67
\l__enumext_counter_i_tl ..... 32, 406
\l__enumext_counter_ii_tl ..... 32, 407
\l__enumext_counter_iii_tl ..... 32, 408
\l__enumext_counter_iv_tl ..... 32, 409
\c__enumext_counter_style_tl ..... 27, 37, 200
\g__enumext_counter_styles_tl . 23, 32, 55, 417,
    435
\l__enumext_counter_v_tl ..... 32, 410, 655
\l__enumext_counter_vi_tl ..... 32, 411
\l__enumext_counter_vii_tl ..... 32, 412, 585
\l__enumext_counter_viii_tl ..... 32, 413, 602
\l__enumext_current_widest_dim 23, 55, 441, 518,
    565, 636, 640
\__enumext_default_item:n ... 2574, 2574, 2623
\__enumext_define_counters:Nn 23, 397, 397, 406,
    407, 408, 409, 410, 411, 412, 413
\__enumext_endminipage: 30, 339, 342, 1049, 3238,
    3595, 3946
\g__enumext_envir_name_tl 28, 137, 246, 260, 316,
    1736, 1741, 1751, 1881, 1886, 1891, 1905, 1910, 1915
\__enumext_execute_after_env: .. 29, 58, 61, 62,
    1917, 1917, 3009, 3631
\__enumext_fake_item: ..... 790, 790, 2769
\l__enumext_fake_item_indent_v_dim 809, 814
\l__enumext_fake_item_indent_v_tl 811, 2631,
    2635, 2643
\l__enumext_fake_item_indent_vii_dim 821, 826
\l__enumext_fake_item_indent_vii_tl 823, 3591
\l__enumext_fake_item_indent_viii_dim . 833,
    838, 3938
\l__enumext_fake_item_indent_viii_tl .. 835,
    3937, 3941
\l__enumext_fake_item_indent_X_tl ..... 85
\__enumext_fake_item_vii: .... 790, 818, 2799
\__enumext_fake_item_viii: .... 790, 830, 2804
\__enumext_filter_series:n 53, 1489, 1489, 1531,
    1543, 1548
\__enumext_filter_series_key:n 54, 1489, 1494,
    1498
\__enumext_filter_series_pair:nn .. 54, 1489,
    1495, 1507
\g__enumext_footnote_arg_seq . 152, 2547, 2560,
    2570
\g__enumext_footnote_int . 152, 2554, 2557, 2559,
    2561
\g__enumext_footnote_int_seq . 152, 2548, 2561,
    2566, 2569
\__enumext_footnotes_key_bool ..... 30
\l__enumext_footnotes_key_bool 25, 30, 97, 142,
    355, 360, 369, 3558, 3606, 3911, 3957
\__enumext_footnotetext:nn ... 2541, 2541, 2571
\__enumext_getkeyans:nn .. 105, 3996, 4000, 4000
\__enumext_getkeyans_aux:n 105, 3984, 3987, 3987
\l__enumext_hyperref_bool . 25, 30, 31, 142, 351,
    372, 389, 2216, 2438, 3545, 3902

```

```

\__enumext_hypertarget:nn 31, 346, 374, 378, 394
\__enumext_if_is_int:n ..... 192
\__enumext_if_is_int:nTF ..... 192, 674, 688
\__enumext_is_not_nested: 27, 81, 212, 212, 2832,
3383
\__enumext_is_on_first_level: . 28, 81, 212, 236,
2837, 3390
\g__enumext_item_anskey_int .. 72, 132, 303, 330,
331, 1866, 2153, 2452
\__enumext_item_answer_diff: 61, 62, 1862, 1862,
1924
\g__enumext_item_answer_diff_int . 61, 62, 141,
304, 1864, 1871, 1895
\l__enumext_item_column_pos_vii_int 95, 3271,
3277, 3283, 3287, 3294, 3473, 3610, 3613
\l__enumext_item_column_pos_viii_int .. 102,
3661, 3667, 3673, 3677, 3684, 3806, 3961, 3964
l__enumext_item_column_pos_X_int ..... 155
\g__enumext_item_count_all_vii_int 95, 3295,
3474, 3621, 3628
\g__enumext_item_count_all_viii_int 102, 3685,
3807, 3972, 3979
\g__enumext_item_count_all_X_int ..... 155
\g__enumext_item_number_int .. 60, 132, 302, 329,
331, 1824, 1828, 1831, 1834, 1842, 1866, 2580, 2610,
3552
\__enumext_item_peek_args_vii: 95, 3475, 3477,
3477
\__enumext_item_peek_args_viii: .. 102, 3808,
3810, 3810
\__enumext_item_starred: .. 77, 2666, 2666, 2684
\l__enumext_item_starred_vii_bool 3492, 3508,
3562
\l__enumext_item_starred_viii_bool 3825, 3841,
3915, 3935
\l__enumext_item_starred_X_bool ..... 155
\__enumext_item_std:w 30, 75, 77, 90, 333, 337, 2583,
2589, 2613, 2631, 2635, 2643, 3219
\g__enumext_item_symbol_aux_vii_tl 3516, 3564,
3567, 3571, 3573
\g__enumext_item_symbol_aux_X_tl ..... 155
\l__enumext_item_symbol_sep_vii_dim .. 3525,
3533, 3570, 3572
\g__enumext_item_symbol_tl 23, 75, 48, 2598, 2672,
2689
\l__enumext_item_symbol_vii_tl ..... 3567
\l__enumext_item_text_vii_box 3557, 3598, 3605
\l__enumext_item_text_viii_box 3910, 3949, 3956
\l__enumext_item_text_X_box ..... 155
\l__enumext_item_width_vii_dim ... 3253, 3298,
3306, 3307
\l__enumext_item_width_viii_dim .. 3643, 3688,
3696, 3697
\l__enumext_item_width_X_dim ..... 155
\l__enumext_itemindent_X_dim ..... 59
\l__enumext_itemsep_vii_skip ..... 3627
\l__enumext_itemsep_viii_skip ..... 3978
\l__enumext_joined_item_aux_vii_int .. 3292,
3293, 3294, 3295, 3301
\l__enumext_joined_item_aux_viii_int . 3682,
3683, 3684, 3685, 3691
\l__enumext_joined_item_aux_X_int .... 155
\__enumext_joined_item_vii:w .. 95, 3480, 3481,
3483, 3483
\l__enumext_joined_item_vii_int .. 3263, 3264,
3267, 3269, 3275, 3280, 3285, 3290, 3292, 3298
\__enumext_joined_item_viii:w . 102, 3813, 3814,
3816, 3816
\l__enumext_joined_item_viii_int . 3653, 3654,
3657, 3659, 3665, 3670, 3675, 3680, 3682, 3688
\l__enumext_joined_item_X_int ..... 155
\l__enumext_joined_width_vii_dim . 3296, 3303,
3306, 3588, 3600
\l__enumext_joined_width_viii_dim 3686, 3693,
3696, 3932, 3951
\l__enumext_joined_width_X_dim ..... 155
\__enumext_keyans_addto_prop:n 70, 2337, 2337,
2645, 3149
\__enumext_keyans_addto_seq:n . 72, 2411, 2411,
2647, 3151
\__enumext_keyans_addto_seq_link: 2411, 2432,
2434, 3872
\__enumext_keyans_anspic_code:nnn . 88, 3140,
3143, 3143
\__enumext_keyans_default_item:n .. 76, 2626,
2626, 2662
\l__enumext_keyans_env_bool 20, 2893, 2906, 3035,
3120
\__enumext_keyans_fake_item: .. 790, 806, 2759
\l__enumext_keyans_item_opt_tl . 103, 97, 2459,
2472, 2478, 3857
\l__enumext_keyans_level_h_int .. 20, 595, 622,
2389, 3771, 3772
\l__enumext_keyans_level_int .. 20, 1324, 2142,
2384, 3034, 3039, 3134
\__enumext_keyans_make_label: 33, 78, 2692, 2692,
2757
\__enumext_keyans_mini_addvspace: 48, 86, 1228,
1228, 3064
\__enumext_keyans_mini_right_cmd:n 51, 1326,
1349, 1349
\__enumext_keyans_mini_set_vskip: . 47, 1166,
1166, 1230
\__enumext_keyans_multi_addvspace: 87, 1015,
1026, 3089
\__enumext_keyans_multi_set_vskip: 44, 1015,
1015, 1028
\__enumext_keyans_multicols_start: 86, 3068,
3070, 3070
\__enumext_keyans_multicols_stop: . 87, 1353,
3095, 3095, 3119
\__enumext_keyans_parse_keys:n 3013, 3048, 3048
\l__enumext_keyans_pic_above_int . 127, 3229,
3230, 3232
\l__enumext_keyans_pic_above_skip .. 90, 127,
3173, 3213
\__enumext_keyans_pic_arg_two: 90, 3171, 3201,
3201
\l__enumext_keyans_pic_below_int . 127, 3229,
3230, 3233
\l__enumext_keyans_pic_body_seq .. 88-90, 127,
3138, 3178, 3237
\__enumext_keyans_pic_do:n 90, 3178, 3180, 3221,
3221, 3225
\l__enumext_keyans_pic_level_int .. 20, 1316,
2146, 2340, 2379, 2414, 2492, 3189, 3190
\__enumext_keyans_pic_row:n 90, 3223, 3226, 3226
\__enumext_keyans_pic_safe_exec: .. 89, 3167,

```

[3187](#), [3187](#)  
`\__enumext_keyans_pic_skip_abs:N` .. [89](#), [3196](#),  
[3196](#), [3212](#)  
`\l__enumext_keyans_pic_width_dim` . [127](#), [3228](#),  
[3235](#)  
`\__enumext_keyans_redefine_item:` .. [77](#), [2650](#),  
[2650](#), [2756](#)  
`\__enumext_keyans_ref:` ..... [36](#), [647](#), [665](#), [2758](#)  
`\__enumext_keyans_ref:n` ..... [36](#), [644](#), [647](#), [647](#)  
`\__enumext_keyans_safe_exec:` . [3012](#), [3028](#), [3028](#)  
`\__enumext_keyans_save_start_line:` . [28](#), [267](#),  
[267](#), [3036](#), [3194](#), [3776](#)  
`\__enumext_keyans_show_ans:` .. [2455](#), [2463](#), [2482](#)  
`\__enumext_keyans_show_item_opt:` . [2455](#), [2470](#),  
[2643](#), [3163](#), [3938](#)  
`\__enumext_keyans_show_left:n` . [77](#), [2455](#), [2455](#),  
[2641](#), [3158](#)  
`\__enumext_keyans_show_pos:` .. [2455](#), [2467](#), [2490](#)  
`\__enumext_keyans_starred_item:n` .. [77](#), [2638](#),  
[2638](#), [2658](#)  
`\__enumext_keyans_store_ref:` .. [71](#), [2358](#), [2358](#),  
[2646](#), [3150](#), [3870](#)  
`\__enumext_keyans_store_ref_aux_i:` [71](#), [2358](#),  
[2370](#), [2373](#)  
`\__enumext_keyans_store_ref_aux_ii:` [72](#), [2358](#),  
[2399](#), [2401](#)  
`\l__enumext_keyans_tmpa_tl` .. [24](#), [97](#), [2640](#), [2644](#)  
`\__enumext_keyans_wrapper_opt:n` .. [1960](#), [2478](#)  
`\l__enumext_label_copy_i_tl` .. [2270](#), [2377](#), [2382](#),  
[2387](#), [2392](#)  
`\l__enumext_label_copy_v_tl` ..... [2387](#)  
`\l__enumext_label_copy_vi_tl` ..... [2382](#)  
`\l__enumext_label_copy_vii_tl` [2245](#), [2256](#), [2287](#),  
[2377](#)  
`\l__enumext_label_copy_viii_tl` ..... [2392](#)  
`\l__enumext_label_copy_X_tl` ..... [144](#)  
`\l__enumext_label_fill_left_v_tl` ..... [2696](#)  
`\l__enumext_label_fill_left_X_tl` ..... [85](#)  
`\l__enumext_label_fill_right_v_tl` .... [2703](#)  
`\l__enumext_label_fill_right_X_tl` ..... [85](#)  
`\l__enumext_label_font_style_v_tl` [2697](#), [3162](#)  
`\l__enumext_label_font_style_vii_tl` ... [3576](#)  
`\l__enumext_label_font_style_viii_tl` .. [3920](#)  
`\l__enumext_label_i_tl` ..... [510](#)  
`\l__enumext_label_ii_tl` ..... [510](#)  
`\l__enumext_label_iii_tl` ..... [510](#)  
`\l__enumext_label_iv_tl` ..... [510](#)  
`\__enumext_label_style:Nnn` [23](#), [32](#), [430](#), [430](#), [445](#),  
[515](#), [562](#), [633](#), [637](#)  
`\l__enumext_label_v_tl` .. [70](#), [72](#), [630](#), [2345](#), [2419](#),  
[2484](#), [2519](#), [2640](#), [2644](#), [3016](#), [3157](#), [3159](#)  
`\l__enumext_label_vi_tl` . [70](#), [72](#), [630](#), [2342](#), [2416](#),  
[3157](#), [3159](#), [3163](#)  
`\l__enumext_label_vii_tl` . [557](#), [3503](#), [3528](#), [3535](#)  
`\l__enumext_label_viii_tl` [557](#), [3836](#), [3864](#), [3868](#)  
`\l__enumext_label_width_by_box` .. [55](#), [426](#), [427](#)  
`\__enumext_label_width_by_box:Nn` [32](#), [424](#), [424](#),  
[429](#), [441](#), [698](#)  
`\l__enumext_labelsep_i_dim` ... [2487](#), [2522](#), [3876](#),  
[3891](#)  
`\l__enumext_labelsep_v_dim` ..... [3079](#)  
`\l__enumext_labelsep_vii_dim` . [3248](#), [3257](#), [3299](#),  
[3526](#), [3586](#), [3602](#)  
`\l__enumext_labelsep_viii_dim` [3638](#), [3647](#), [3689](#),  
[3930](#), [3953](#)  
`\l__enumext_labelwidth_i_dim` . [2487](#), [2522](#), [3876](#),  
[3891](#)  
`\l__enumext_labelwidth_v_dim` ..... [3079](#)  
`\l__enumext_labelwidth_vii_dim` ... [3248](#), [3256](#),  
[3299](#), [3579](#), [3583](#), [3601](#)  
`\l__enumext_labelwidth_viii_dim` .. [3638](#), [3646](#),  
[3689](#), [3923](#), [3927](#), [3952](#)  
`\l__enumext_leftmargin_tmp_v_bool` . [90](#), [3203](#)  
`\l__enumext_leftmargin_tmp_X_bool` ..... [59](#)  
`\l__enumext_leftmargin_tmp_X_dim` ..... [59](#)  
`\l__enumext_leftmargin_X_dim` ..... [59](#)  
`\__enumext_level:` [188](#), [188](#), [539](#), [542](#), [543](#), [552](#), [554](#),  
[793](#), [797](#), [801](#), [868](#), [872](#), [876](#), [880](#), [964](#), [966](#), [968](#), [970](#),  
[1003](#), [1005](#), [1007](#), [1009](#), [1013](#), [1053](#), [1056](#), [1075](#), [1084](#),  
[1090](#), [1095](#), [1099](#), [1110](#), [1114](#), [1115](#), [1120](#), [1156](#), [1160](#),  
[1333](#), [1339](#), [1386](#), [1388](#), [1390](#), [1393](#), [1400](#), [1402](#), [1404](#),  
[1407](#), [2050](#), [2058](#), [2062](#), [2066](#), [2308](#), [2311](#), [2312](#), [2582](#),  
[2583](#), [2587](#), [2588](#), [2589](#), [2596](#), [2598](#), [2602](#), [2603](#), [2606](#),  
[2612](#), [2613](#), [2668](#), [2671](#), [2673](#), [2680](#), [2681](#), [2682](#), [2685](#),  
[2688](#), [2818](#), [2820](#), [2861](#), [2866](#), [2867](#), [2868](#), [2870](#), [2874](#),  
[2879](#), [2880](#), [2881](#), [2883](#), [2899](#), [2912](#), [2919](#), [2930](#), [2932](#),  
[2935](#), [2936](#), [2938](#), [2943](#), [2950](#), [2953](#), [2955](#), [2957](#), [2958](#),  
[2959](#), [2960](#), [2963](#), [2969](#), [2974](#), [2980](#), [2983](#), [2985](#), [2991](#)  
`\l__enumext_level_h_int` .. [20](#), [220](#), [242](#), [255](#), [578](#),  
[615](#), [1821](#), [1837](#), [2264](#), [2281](#), [3384](#), [3385](#)  
`\l__enumext_level_int` . [81](#), [20](#), [190](#), [229](#), [241](#), [256](#),  
[976](#), [1127](#), [1320](#), [1815](#), [1919](#), [2241](#), [2251](#), [2257](#), [2263](#),  
[2271](#), [2279](#), [2286](#), [2772](#), [2833](#), [2834](#), [2844](#), [2851](#), [2897](#),  
[2910](#), [2965](#), [3043](#), [3130](#), [3454](#), [3464](#), [3779](#)  
`\__enumext_list_arg_two_i:` ..... [2738](#)  
`\__enumext_list_arg_two_ii:` ..... [2738](#)  
`\__enumext_list_arg_two_iii:` ..... [2738](#)  
`\__enumext_list_arg_two_iv:` ..... [2738](#)  
`\__enumext_list_arg_two_v:` . [77](#), [2738](#), [3018](#), [3204](#)  
`\__enumext_list_arg_two_vii:` ..... [2778](#), [3366](#)  
`\__enumext_list_arg_two_viii:` .... [2778](#), [3754](#)  
`\l__enumext_listoffset_v_dim` ..... [3081](#)  
`\l__enumext_listparindent_vii_dim` .... [3589](#)  
`\l__enumext_listparindent_viii_dim` ... [3933](#)  
`\__enumext_log_answer_vars:` . [29](#), [318](#), [326](#), [1926](#)  
`\__enumext_log_global_vars:` . [29](#), [318](#), [318](#), [1925](#)  
`\__enumext_make_label:` [33](#), [75](#), [76](#), [78](#), [2676](#), [2676](#),  
[2767](#)  
`\l__enumext_mark_answer_sym_tl` . [66](#), [122](#), [1966](#),  
[2120](#), [2323](#), [2494](#), [2507](#), [3880](#)  
`\l__enumext_mark_position_str` [122](#), [1970](#), [1971](#),  
[1994](#), [1995](#), [2118](#)  
`\l__enumext_mark_ref_sym_tl` .. [122](#), [1980](#), [2221](#),  
[2446](#)  
`\__enumext_mini_addvspace:` .. [47](#), [83](#), [1149](#), [1149](#),  
[2940](#)  
`\__enumext_mini_addvspace_vii:` [49](#), [1302](#), [1302](#),  
[3324](#)  
`\__enumext_mini_addvspace_viii:` [49](#), [1302](#), [1308](#),  
[3714](#)  
`\__enumext_mini_env*` ..... [1043](#)  
`\__enumext_mini_right_cmd:n` . [50](#), [51](#), [1328](#), [1330](#),  
[1330](#)  
`\__enumext_mini_set_vskip:` . [45](#), [1050](#), [1050](#), [1151](#)  
`\__enumext_mini_set_vskip_vii:` [48](#), [1245](#), [1245](#),  
[1304](#)  
`\__enumext_mini_set_vskip_viii:` [48](#), [1245](#), [1267](#),



```

1310
\__enumext_minipage:w . . 30, 339, 341, 1045, 3235,
3588, 3932
\l__enumext_minipage_active_v_bool . . 86, 87,
3062, 3087, 3100, 3108
\g__enumext_minipage_active_vii_bool . . . 92,
3335, 3340, 3352
\l__enumext_minipage_active_vii_bool . 3320,
3331
\g__enumext_minipage_active_viii_bool 3725,
3730, 3742
\l__enumext_minipage_active_viii_bool 3710,
3721
\g__enumext_minipage_active_X_bool . . . 155
\l__enumext_minipage_active_X_bool . . . 73
\g__enumext_minipage_after_skip 73, 1249, 1261,
3350, 3740
\l__enumext_minipage_after_skip 45, 46, 84, 87,
73, 1066, 1081, 1101, 1117, 1132, 1138, 1144, 1158,
1168, 1177, 1180, 1192, 1210, 1221, 1237, 1269, 1282,
1296, 3000, 3117
\g__enumext_minipage_center_vii_bool . 3344,
3353
\g__enumext_minipage_center_viii_bool 3734,
3743
\g__enumext_minipage_center_X_bool . . . 155
\l__enumext_minipage_hsep_v_dim . . . 86, 3060
\l__enumext_minipage_hsep_vii_dim . . . 3318
\l__enumext_minipage_hsep_viii_dim . . . 3708
\l__enumext_minipage_left_skip 45, 86, 73, 1058,
1073, 1092, 1107, 1154, 1164, 1169, 1175, 1184, 1201,
1213, 1233, 1243, 1247, 1252, 1256, 1270, 1274, 1288,
1306, 1312
\l__enumext_minipage_left_v_dim 86, 3058, 3066
\l__enumext_minipage_left_vii_dim 3314, 3326
\l__enumext_minipage_left_viii_dim 3704, 3716
\l__enumext_minipage_left_X_dim . . . . . 73
\g__enumext_minipage_right_skip 73, 1248, 1253,
1257, 3343, 3733
\l__enumext_minipage_right_skip . 45, 73, 1062,
1077, 1097, 1112, 1170, 1176, 1188, 1206, 1217, 1271,
1278, 1292, 1340, 1357
\l__enumext_minipage_right_v_dim . . 86, 1351,
1356, 3056, 3060
\g__enumext_minipage_right_vii_dim 92, 3322,
3342, 3355
\l__enumext_minipage_right_vii_dim 92, 3312,
3317, 3323
\g__enumext_minipage_right_viii_dim . . 3712,
3732, 3745
\l__enumext_minipage_right_viii_dim . . 3702,
3707, 3713
\g__enumext_minipage_right_X_dim . . . . . 155
\g__enumext_minipage_right_X_skip . . . 155
\g__enumext_minipage_stat_int . 83, 86, 73, 1345,
1362, 2939, 2993, 2998, 3063, 3110, 3115
\g__enumext_miniright_code_vii_tl . 92, 3348,
3354
\g__enumext_miniright_code_viii_tl 3738, 3744
\g__enumext_miniright_code_X_tl . . . . . 155
\__enumext_multi_addvspace: . . . 44, 84, 998, 998,
2971
\__enumext_multi_set_vskip: . 43, 962, 962, 1000
\l__enumext_multicols_above_ii_skip . . . 981
\l__enumext_multicols_above_iii_skip . . . 987
\l__enumext_multicols_above_iv_skip . . . 993
\l__enumext_multicols_above_v_skip 1017, 1031,
1041
\l__enumext_multicols_above_X_skip . . . . 67
\l__enumext_multicols_below_v_skip 1021, 1035,
3102
\l__enumext_multicols_below_X_skip . . . . 67
\__enumext_multicols_start: . 83, 84, 2945, 2947,
2947
\__enumext_multicols_stop: 84, 1335, 2977, 2977,
3002
\__enumext_newlabel:nn 26, 31, 70, 382, 382, 2297,
2405
\l__enumext_newlabel_arg_one_tl 26, 31, 69, 71,
144, 2220, 2290, 2298, 2394, 2406, 2444
\l__enumext_newlabel_arg_two_tl 26, 31, 68, 144,
2244, 2254, 2268, 2284, 2299, 2381, 2386, 2391, 2407
\__enumext_parse_keys:n . . . 54, 2814, 2839, 2839
\__enumext_parse_keys_vii:n 54, 3361, 3392, 3392
\__enumext_parse_keys_viii:n . 3750, 3784, 3784
\__enumext_parse_series:n . . 54, 81, 1519, 1519,
2847, 3398
\__enumext_parse_store_keys:n 81, 82, 2855, 2859,
2859
\__enumext_parse_store_keys_vii:n 93, 94, 3401,
3405, 3405
\l__enumext_parsep_i_skip 979, 981, 1130, 1178
\l__enumext_parsep_ii_skip . . . . 985, 987, 1136
\l__enumext_parsep_iii_skip . . . 991, 993, 1142
\l__enumext_parsep_vii_skip . . . . . 3590
\l__enumext_parsep_viii_skip . . . . . 3934
\l__enumext_partopsep_v_skip . 1033, 1037, 1204,
1208, 1215, 1219, 1235, 1239
\l__enumext_partopsep_viii_skip . . . . . 1280
\__enumext_phantomsection: 31, 346, 375, 379, 395
\__enumext_print_footnote: . . . 2541, 2564, 3608,
3959
\__enumext_print_keyans_box:NN 66, 2112, 2112,
2125, 2310, 2486, 2521, 3876, 3891
\l__enumext_print_keyans_i_tl . . . . 4010, 4039
\l__enumext_print_keyans_ii_tl . . . 4015, 4040
\l__enumext_print_keyans_iii_tl . . 4020, 4041
\l__enumext_print_keyans_iv_tl . . . 4025, 4042
\l__enumext_print_keyans_vii_tl . . 4030, 4043
\l__enumext_print_keyans_X_tl . . . . . 111
\__enumext_printkeyans:nnn 106, 4044, 4047, 4047
\__enumext_redefine_item: . 76, 2615, 2615, 2766
\l__enumext_ref_key_arg_tl 34, 37, 203, 532, 533,
546, 577, 580, 591, 597, 608, 649, 650, 661
\l__enumext_ref_the_count_tl . 34, 37, 539, 542,
545, 585, 587, 590, 602, 604, 607, 655, 657, 660
\__enumext_regex_counter_style: . . 27, 34, 198,
198, 540, 586, 603, 656
\__enumext_register_counter_style:Nn . . 414,
414, 419, 420, 421, 422, 423
\__enumext_remove_extra_parsep_vii: . . 3376,
3617, 3617
\__enumext_remove_extra_parsep_viii: . 3764,
3968, 3968
\__enumext_renew_footnote: . . . 2541, 2545, 3560,
3913
\l__enumext_renew_the_count_v_tl 658, 667, 669
\l__enumext_renew_the_count_vii_tl 588, 617,
619

```

```

\l__enumext_renew_the_count_viii_tl 605, 624,
    626
\l__enumext_renew_the_count_X_tl ..... 37
\__enumext_reset_global_bool: .. 294, 297, 306
\__enumext_reset_global_int: ... 294, 296, 300
\__enumext_reset_global_tl: .... 294, 298, 312
\__enumext_reset_global_vars: . 29, 62, 294, 294,
    1933
\l__enumext_resume_active_bool 54, 56, 48, 1523,
    1643
\__enumext_resume_counter: .. 56, 57, 1641, 1647,
    1654
\__enumext_resume_counter:n . 54, 56, 1612, 1617,
    1641, 1641, 1711, 1719
\__enumext_resume_counter_save_ans: .. 56, 57,
    1641, 1652, 1684
\__enumext_resume_counter_series: 56, 57, 1641,
    1650, 1667
\g__enumext_resume_int ... 48, 1564, 1658, 1659
\__enumext_resume_last:n .. 54, 1519, 1525, 1538
\l__enumext_resume_name_tl 48, 1560, 1568, 1571,
    1587, 1595, 1598, 1644, 1645, 1673, 1680
\__enumext_resume_save_counter: 55, 1551, 1551,
    3007, 3448
\__enumext_resume_series:n . 56, 1483, 1608, 1608
\__enumext_resume_starred: . 58, 1484, 1705, 1705
\g__enumext_resume_vii_int .. 94, 48, 1591, 1663,
    1664
\__enumext_safe_exec: ..... 81, 2813, 2830, 2830
\__enumext_safe_exec_vii: ... 3360, 3381, 3381
\__enumext_safe_exec_viii: ... 3749, 3769, 3769
\l__enumext_series_name_tl ..... 56
\l__enumext_series_str . 55, 81, 1481, 1521, 1529,
    1530, 1532, 1534, 1555, 1558, 1562, 1582, 1585, 1589,
    2843, 3396
\__enumext_set_error:nn ..... 4125, 4135, 4137
\__enumext_set_parse:n ..... 4108, 4125, 4125
\l__enumext_setkey_tmpa_int ... 106, 4101, 4105
\l__enumext_setkey_tmpa_seq .. 106, 4099, 4109,
    4115, 4117, 4119, 4132
\l__enumext_setkey_tmpa_tl .... 106, 4107, 4111
\l__enumext_setkey_tmpb_seq .. 106, 4100, 4103,
    4107, 4108
\l__enumext_setkey_tmpb_tl 106, 4127, 4129, 4130
\l__enumext_show_answer_bool . 122, 1974, 1998,
    2317, 2461, 2475, 3154, 3874
\__enumext_show_length:nnn .. 40, 206, 206, 4201,
    4202, 4203, 4204, 4205, 4206, 4207, 4208, 4209, 4210,
    4216, 4217, 4218, 4219, 4220, 4221, 4222, 4223, 4224,
    4225
\l__enumext_show_position_bool 122, 1977, 2001,
    2321, 2465, 2476, 3155, 3878
\g__enumext_standar_bool . 27, 20, 219, 222, 240,
    309, 1553, 1618, 1630, 1656, 1669, 1707, 1840, 1851
\l__enumext_standar_bool 85, 20, 2249, 2262, 2278,
    2836, 3006
\l__enumext_standar_first_bool ... 81, 20, 245,
    1540, 1687, 1749, 1756
\__enumext_standar_ref: .... 34, 530, 550, 2768
\__enumext_standar_ref:n .... 34, 522, 530, 530
\g__enumext_standar_series_tl . 48, 1542, 1543,
    1709, 1712
\g__enumext_standard_bool ..... 81
\l__enumext_standard_bool ..... 81
\l__enumext_standard_first_bool ..... 28
\__enumext_standard_item_vii:w .. 95, 96, 3488,
    3490, 3490
\__enumext_standard_item_viii:w .. 102, 3821,
    3823, 3823
\g__enumext_starred_bool 27, 93, 94, 20, 228, 231,
    254, 310, 1580, 1623, 1634, 1661, 1676, 1715, 1820,
    1857, 2240, 2250, 2280, 2375, 2894, 2907, 3356
\l__enumext_starred_bool . 93, 94, 20, 2173, 2181,
    2265, 2306, 3389, 3447
\__enumext_starred_columns_set_vii: .. 3242,
    3242, 3369
\__enumext_starred_columns_set_viii: . 3632,
    3632, 3757
\l__enumext_starred_first_bool ... 28, 20, 259,
    1545, 1696, 1749, 1756
\__enumext_starred_item:nn ... 2592, 2592, 2621
\__enumext_starred_item_exec: . 103, 3866, 3866,
    3917
\__enumext_starred_item_vii:w 95, 96, 3487, 3506,
    3506
\__enumext_starred_item_vii_aux_i:w .. 3506,
    3511, 3514
\__enumext_starred_item_vii_aux_ii:w . 3506,
    3512, 3517, 3519
\__enumext_starred_item_vii_aux_iii:w 3506,
    3522, 3531
\__enumext_starred_item_viii:w 102, 103, 3820,
    3839, 3839
\__enumext_starred_item_viii_aux_i:w .. 103,
    3839, 3844, 3847
\__enumext_starred_item_viii_aux_ii:w . 103,
    3839, 3845, 3859, 3861
\__enumext_starred_joined_item_vii:n . 91, 95,
    3261, 3261, 3485
\__enumext_starred_joined_item_viii:n .. 99,
    102, 3651, 3651, 3818
\__enumext_starred_ref: .... 36, 575, 613, 2796
\__enumext_starred_ref:n .... 35, 569, 575, 575
\g__enumext_starred_series_tl . 48, 1547, 1548,
    1717, 1720
\__enumext_start_from:NNn 37, 672, 672, 685, 707
\l__enumext_start_i_int ..... 1659, 1671, 1690
\__enumext_start_item_tmp_vii: 93, 3372, 3470,
    3470
\__enumext_start_item_tmp_viii: .. 100, 3760,
    3803, 3803
\__enumext_start_item_vii:w . 96, 97, 3498, 3503,
    3528, 3535, 3537, 3537
\__enumext_start_item_viii:w .. 102, 3831, 3836,
    3864, 3894, 3894
\g__enumext_start_line_tl 28, 132, 247, 261, 315,
    1881, 1886, 1891, 1905, 1910, 1915
\__enumext_start_list:nn 30, 78, 90, 333, 335, 2817,
    3015, 3168, 3364, 3752
\__enumext_start_mini_vii: . 94, 3310, 3310, 3439
\__enumext_start_mini_viii: ... 101, 3700, 3700,
    3795
\__enumext_start_save_ans_msg: 58, 1733, 1733,
    1758
\__enumext_start_store_level: . 82, 2816, 2888,
    2888
\__enumext_start_store_level_vii: . 95, 3363,
    3450, 3450

```

```

\l__enumext_start_vii_int ... 1664, 1678, 1699
\l__enumext_start_X_int ..... 85, 702
\__enumext_stop_item_tmp_vii: . 93, 95, 97, 3371,
    3375, 3472, 3539
\__enumext_stop_item_tmp_viii: 100, 102, 3759,
    3763, 3805, 3896
\__enumext_stop_item_vii: 97, 98, 3539, 3593, 3593
\__enumext_stop_item_viii: 104, 3896, 3944, 3944
\__enumext_stop_list: .. 30, 333, 336, 2826, 3025,
    3181, 3377, 3766
\__enumext_stop_mini_vii: 92, 94, 3329, 3329, 3443
\__enumext_stop_mini_viii: 101, 3700, 3719, 3799
\__enumext_stop_save_ans_msg: . 58, 1733, 1738,
    1923
\__enumext_stop_store_level: .. 82, 2827, 2888,
    2917
\__enumext_stop_store_level_vii: .. 95, 3378,
    3450, 3460
\l__enumext_store_active_bool 24, 59, 81, 93, 97,
    1688, 1697, 1765, 2138, 2853, 2892, 2905, 3030, 3038,
    3126, 3185, 3399, 3452, 3462, 3778
\__enumext_store_addto_prop:n 64, 70, 2032, 2032,
    2040, 2160, 2356, 3869
\__enumext_store_addto_seq:n 65, 72, 2041, 2041,
    2045, 2052, 2066, 2074, 2083, 2101, 2109, 2224, 2449
\l__enumext_store_anskey_arg_tl 24, 67, 68, 97,
    2166, 2175, 2177, 2183, 2191, 2194, 2204, 2209, 2212,
    2218, 2224
\__enumext_store_anskey_code:nnnn . 67, 2155,
    2158, 2158
\__enumext_store_anskey_show_left:n 70, 2165,
    2315, 2315
\__enumext_store_anskey_show_wrap:n 70, 2303,
    2303, 2319, 2334
\l__enumext_store_columns_break_bool . 2132,
    2172
\l__enumext_store_columns_join_int 97, 2180,
    2185
\l__enumext_store_columns_sep_vii_bool 3420
\l__enumext_store_columns_sep_vii_dim 3425,
    3429
\l__enumext_store_columns_sep_X_bool .. 111
l__enumext_store_columns_sep_X_dim ... 111
\l__enumext_store_columns_vii_bool ... 3407
\l__enumext_store_columns_vii_int 3412, 3416
\l__enumext_store_columns_X_bool ..... 111
\l__enumext_store_columns_X_int ..... 111
\__enumext_store_internal_ref: .. 67, 68, 2163,
    2226, 2226
\l__enumext_store_item_symbol_sep_dim 2130,
    2201, 2206
\l__enumext_store_item_symbol_tl . 2128, 2192,
    2196
\l__enumext_store_keyans_item_opt_sep_-
    tl .... 1963, 2350, 2352, 2423, 2427, 3852, 3854
\l__enumext_store_keyans_item_opt_tl ... 97
\l__enumext_store_keyans_label_tl 24, 70, 72,
    103, 97, 2339, 2342, 2345, 2352, 2354, 2356, 2413,
    2416, 2419, 2425, 2430, 2440, 2449, 3849, 3854, 3855,
    3868, 3869, 3871
\__enumext_store_level_close: . 65, 2046, 2070,
    2921
\__enumext_store_level_close_vii: 2077, 2105,
    3466
\__enumext_store_level_open: .. 64, 65, 82, 2046,
    2046, 2900, 2913
\__enumext_store_level_open_vii: .. 94, 2077,
    2077, 3456
\g__enumext_store_name_tl . 24, 85, 97, 314, 321,
    322, 323, 324, 1741, 1767, 1880, 1885, 1890, 1904,
    1909, 1914, 1921
\l__enumext_store_name_tl . 24, 58, 60, 97, 1574,
    1577, 1601, 1604, 1692, 1701, 1736, 1745, 1746, 1767,
    1768, 1770, 1771, 1773, 1775, 1776, 1778, 1780, 1781,
    1805, 2034, 2036, 2043, 2292, 2293, 2329, 2396, 2397,
    2500, 2513, 3886
\l__enumext_store_opt_vii_tl . 2081, 2091, 2097,
    2101, 3414, 3427
\l__enumext_store_opt_X_tl ..... 111
\l__enumext_store_ref_key_bool 67, 1983, 2161,
    2215, 2360, 2437
\l__enumext_store_upper_level_X_bool .. 111
\l__enumext_store_write_aux_file_tl 26, 70, 72,
    144, 2295, 2301, 2403, 2409
\__enumext_storing_exec: 58, 59, 1743, 1759, 1763
\__enumext_storing_set:n .. 58, 1728, 1743, 1743
\l__enumext_the_counter_v_tl ..... 657
\l__enumext_the_counter_vii_tl ..... 587
\l__enumext_the_counter_viii_tl ..... 604
\l__enumext_the_counter_X_tl ..... 37
\__enumext_tmp:n 32, 36, 41, 47, 59, 66, 67, 72, 79, 84,
    85, 96, 111, 121, 147, 151, 155, 174, 785, 789, 1477,
    1488, 1724, 1732, 1784, 1802, 1953, 1988, 1989, 2006,
    2228, 2235, 2236, 2257, 2271, 2274, 2286, 2362, 2369,
    2738, 2777, 2778, 2810
\__enumext_tmp:nn 446, 467, 468, 496, 497, 509, 702,
    721, 766, 784, 842, 850, 851, 865, 930, 946, 947, 961,
    1366, 1382, 2007, 2031, 2525, 2540
\__enumext_tmp:nnn 510, 526, 527, 528, 529, 557, 573,
    574
\__enumext_tmp:nnnnnn 722, 747, 750, 753, 755, 757,
    760, 763
\__enumext_tmp:w ..... 3993, 3996
\l__enumext_tmpa_vii_int ..... 3252, 3255
\l__enumext_tmpa_viii_int ..... 3642, 3645
\l__enumext_tmpa_X_int ..... 155
\l__enumext_topsep_v_skip 1019, 1023, 1173, 1186,
    1194, 1199, 1219, 1223, 3184, 3216
\l__enumext_topsep_vii_skip .. 1250, 1259, 1263
\l__enumext_topsep_viii_skip . 1272, 1294, 1298
\l__enumext_vspace_a_star_v_bool ..... 1415
\l__enumext_vspace_a_star_vii_bool ... 1437
\l__enumext_vspace_a_star_viii_bool ... 1448
\l__enumext_vspace_a_star_X_bool ..... 85
\__enumext_vspace_above: .. 51, 1383, 1383, 2926
\__enumext_vspace_above_v: . 52, 1411, 1411, 3054
\l__enumext_vspace_above_v_skip .. 1413, 1417,
    1419
\__enumext_vspace_above_vii: .. 52, 1433, 1433,
    3436
\l__enumext_vspace_above_vii_skip 1435, 1439,
    1441
\__enumext_vspace_above_viii: . 52, 1433, 1444,
    3793
\l__enumext_vspace_above_viii_skip 1446, 1450,
    1452
\l__enumext_vspace_b_star_v_bool ..... 1426
\l__enumext_vspace_b_star_vii_bool ... 1459
\l__enumext_vspace_b_star_viii_bool ... 1470

```

|                                                   |                                                                                                                        |
|---------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <code>\l__enumext_vspace_b_star_X_bool</code>     | 85                                                                                                                     |
| <code>\__enumext_vspace_below:</code>             | 52, 1397, 1397, 3005                                                                                                   |
| <code>\__enumext_vspace_below_v:</code>           | 52, 1422, 1422, 3122                                                                                                   |
| <code>\l__enumext_vspace_below_v_skip</code>      | 1424, 1428, 1430                                                                                                       |
| <code>\__enumext_vspace_below_vii:</code>         | 53, 1455, 1455, 3446                                                                                                   |
| <code>\l__enumext_vspace_below_vii_skip</code>    | 1457, 1461, 1463                                                                                                       |
| <code>\__enumext_vspace_below_viii:</code>        | 53, 1455, 1466, 3801                                                                                                   |
| <code>\l__enumext_vspace_below_viii_skip</code>   | 1468, 1472, 1474                                                                                                       |
| <code>\__enumext_widest_from:nNn</code>           | 37, 686, 686, 701, 713                                                                                                 |
| <code>\g__enumext_widest_label_tl</code>          | 23, 32, 55, 434, 438, 442                                                                                              |
| <code>\l__enumext_wrap_label_opt_v_bool</code>    | 2634                                                                                                                   |
| <code>\l__enumext_wrap_label_opt_vii_bool</code>  | 96, 3497                                                                                                               |
| <code>\l__enumext_wrap_label_opt_viii_bool</code> | 102, 3830                                                                                                              |
| <code>\l__enumext_wrap_label_opt_X_bool</code>    | 85                                                                                                                     |
| <code>\l__enumext_wrap_label_v_bool</code>        | 2630, 2634, 2642, 2698                                                                                                 |
| <code>\l__enumext_wrap_label_vii_bool</code>      | 96, 3496, 3501, 3509, 3577                                                                                             |
| <code>\l__enumext_wrap_label_viii_bool</code>     | 102, 3829, 3834, 3842, 3921                                                                                            |
| <code>\l__enumext_wrap_label_X_bool</code>        | 85                                                                                                                     |
| <code>\__enumext_wrapper_label_v:n</code>         | 2700, 3163                                                                                                             |
| <code>\__enumext_wrapper_label_vii:n</code>       | 3580                                                                                                                   |
| <code>\__enumext_wrapper_label_viii:n</code>      | 3924                                                                                                                   |
| <code>\__enumext_zero_parsep:</code>              | 46, 1070, 1125, 1125                                                                                                   |
| <code>enumext*</code>                             | 5, 3358                                                                                                                |
| <code>enumXi</code>                               | 406                                                                                                                    |
| <code>enumXii</code>                              | 406                                                                                                                    |
| <code>enumXiii</code>                             | 406                                                                                                                    |
| <code>enumXiv</code>                              | 406                                                                                                                    |
| <code>enumXv</code>                               | 406                                                                                                                    |
| <code>enumXvi</code>                              | 406                                                                                                                    |
| <code>enumXvii</code>                             | 406                                                                                                                    |
| <code>enumXviii</code>                            | 406                                                                                                                    |
| Environments provide by <b>enumext</b> :          |                                                                                                                        |
| <code>enumext*</code>                             | 22, 23, 25-27, 32, 35, 36, 39-42, 48, 49, 52-56, 58, 60, 62-69, 71, 74, 80-82, 93-95, 97-99, 101, 104, 106, 109, 111   |
| <code>enumext</code>                              | 22, 23, 25, 27, 32-38, 40-48, 50-56, 58, 60, 62-67, 69, 71, 74-79, 81, 82, 85, 89, 91, 92, 95, 106, 109, 110           |
| <code>keyans*</code>                              | 22-28, 32, 35, 36, 39-42, 48, 49, 52, 53, 59, 60, 63, 64, 71, 74, 80, 101, 109, 111                                    |
| <code>keyanspic</code>                            | 22-25, 28, 32, 33, 36, 50, 59, 60, 63-65, 70-73, 88-90, 111                                                            |
| <code>keyans</code>                               | 22-25, 27, 28, 32, 33, 36-38, 40-42, 44, 47, 48, 50-52, 59, 60, 63-65, 70-73, 77-79, 85, 86, 88, 90, 92, 101, 109, 111 |
| Environments:                                     |                                                                                                                        |
| <code>list</code>                                 | 26, 30, 78, 81                                                                                                         |
| <code>lrbox</code>                                | 91, 97, 98, 104                                                                                                        |
| <code>minipage</code>                             | 26, 30, 42, 44, 45, 88-91, 97, 98, 104                                                                                 |
| <code>multicols</code>                            | 43-45, 50, 83, 84, 86, 87                                                                                              |
| exp commands:                                     |                                                                                                                        |
| <code>\exp_after:wN</code>                        | 3996                                                                                                                   |
| <code>\exp_args:Ne</code>                         | 2850, 3984                                                                                                             |
| <code>\exp_not:N</code>                           | 45, 437, 545, 590, 607, 660, 799, 813, 814, 825, 826, 837, 838, 2220, 2326, 2327, 2442, 2497, 2498,                    |

|                                   |                                                                                                                                                                                                                                                                                                                    |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2510, 2511, 3883, 3884, 3993      |                                                                                                                                                                                                                                                                                                                    |
| <code>\exp_not:n</code>           | 249, 263, 275, 282, 289, 545, 546, 590, 591, 607, 608, 660, 661, 800, 1505, 1517, 2015, 2022, 2185, 2196, 2206, 2220, 2221, 2298, 2406, 2444, 2446, 2870, 2883, 3416, 3429                                                                                                                                         |
| F                                 |                                                                                                                                                                                                                                                                                                                    |
| <code>\fbox</code>                | 1958                                                                                                                                                                                                                                                                                                               |
| file commands:                    |                                                                                                                                                                                                                                                                                                                    |
| <code>\file_input_stop:</code>    | 4353                                                                                                                                                                                                                                                                                                               |
| <code>first</code>                | 851                                                                                                                                                                                                                                                                                                                |
| <code>font</code>                 | 446                                                                                                                                                                                                                                                                                                                |
| <code>\footnote</code>            | 74                                                                                                                                                                                                                                                                                                                 |
| <code>\footnote</code>            | 74, 2549                                                                                                                                                                                                                                                                                                           |
| <code>\footnotemark</code>        | 2559                                                                                                                                                                                                                                                                                                               |
| <code>\footnotesize</code>        | 2327, 2498, 2511, 3884                                                                                                                                                                                                                                                                                             |
| <code>\footnotetext</code>        | 2543                                                                                                                                                                                                                                                                                                               |
| G                                 |                                                                                                                                                                                                                                                                                                                    |
| <code>\getkeyans</code>           | 14, 105, 3982                                                                                                                                                                                                                                                                                                      |
| group commands:                   |                                                                                                                                                                                                                                                                                                                    |
| <code>\group_begin:</code>        | 2150, 2325, 2496, 2509, 3556, 3575, 3882, 3909, 3919, 4004, 4038                                                                                                                                                                                                                                                   |
| <code>\group_end:</code>          | 2156, 2332, 2503, 2516, 3585, 3597, 3889, 3929, 3948, 4006, 4045                                                                                                                                                                                                                                                   |
| H                                 |                                                                                                                                                                                                                                                                                                                    |
| <code>\hbadness</code>            | 3604, 3955                                                                                                                                                                                                                                                                                                         |
| hbox commands:                    |                                                                                                                                                                                                                                                                                                                    |
| <code>\hbox_set:Nn</code>         | 426                                                                                                                                                                                                                                                                                                                |
| <code>\hfill</code>               | 476, 480, 485, 486, 1337, 1355, 2220, 2442, 3334, 3724                                                                                                                                                                                                                                                             |
| hook commands:                    |                                                                                                                                                                                                                                                                                                                    |
| <code>\hook_gput_code:nnn</code>  | 9, 182, 186, 344                                                                                                                                                                                                                                                                                                   |
| <code>\hook_gset_rule:nnnn</code> | 345                                                                                                                                                                                                                                                                                                                |
| <code>\hspace</code>              | 3615, 3966                                                                                                                                                                                                                                                                                                         |
| <code>\hyperlink</code>           | 68, 72                                                                                                                                                                                                                                                                                                             |
| <code>\hyperlink</code>           | 2220, 2442                                                                                                                                                                                                                                                                                                         |
| <code>\hypertarget</code>         | 31                                                                                                                                                                                                                                                                                                                 |
| <code>\hypertarget</code>         | 374                                                                                                                                                                                                                                                                                                                |
| I                                 |                                                                                                                                                                                                                                                                                                                    |
| <code>\IfHyperBoolean</code>      | 352                                                                                                                                                                                                                                                                                                                |
| <code>\IfPackageLoadedTF</code>   | 11, 348, 362                                                                                                                                                                                                                                                                                                       |
| <code>\ignorespaces</code>        | 802                                                                                                                                                                                                                                                                                                                |
| <code>\inputlineno</code>         | 249, 263, 275, 282, 289                                                                                                                                                                                                                                                                                            |
| int commands:                     |                                                                                                                                                                                                                                                                                                                    |
| <code>\int_add:Nn</code>          | 3294, 3684                                                                                                                                                                                                                                                                                                         |
| <code>\int_case:nn</code>         | 976, 1127, 1815, 1837, 1871, 1895                                                                                                                                                                                                                                                                                  |
| <code>\int_compare:nNnTF</code>   | 578, 595, 615, 622, 1052, 1171, 1316, 1320, 1324, 1919, 1938, 1944, 2142, 2146, 2340, 2379, 2384, 2389, 2414, 2492, 2834, 2844, 2897, 2910, 2949, 2965, 2979, 2993, 3039, 3043, 3072, 3097, 3110, 3130, 3134, 3190, 3264, 3274, 3290, 3385, 3454, 3464, 3610, 3619, 3654, 3664, 3680, 3772, 3779, 3961, 3970, 4105 |
| <code>\int_compare_p:nNn</code>   | 220, 229, 241, 242, 255, 256, 1821, 2241, 2251, 2263, 2264, 2279, 2281                                                                                                                                                                                                                                             |
| <code>\int_decr:N</code>          | 3293, 3683                                                                                                                                                                                                                                                                                                         |
| <code>\int_eval:n</code>          | 331, 2036, 2293, 2327, 2397, 2498, 2511, 2753, 2795, 3282, 3672, 3884                                                                                                                                                                                                                                              |
| <code>\int_from_alph:n</code>     | 680, 694                                                                                                                                                                                                                                                                                                           |
| <code>\int_from_roman:n</code>    | 682, 696                                                                                                                                                                                                                                                                                                           |
| <code>\int_gadd:Nn</code>         | 3295, 3685                                                                                                                                                                                                                                                                                                         |
| <code>\int_gdecr:N</code>         | 1824, 1828, 1831, 1834, 1842                                                                                                                                                                                                                                                                                       |
| <code>\int_gincr:N</code>         | 1658, 1663, 2153, 2452, 2580, 2610, 2648, 2939, 3063, 3152, 3474, 3552, 3807, 3873                                                                                                                                                                                                                                 |



|                                     |                                                                                                                                 |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <code>\int_gset:Nn</code>           | 1864, 2557                                                                                                                      |
| <code>\int_gset_eq:NN</code>        | 1557, 1564, 1570, 1576, 1584, 1591, 1597, 1603, 2554                                                                            |
| <code>\int_gzero:N</code>           | 302, 303, 304, 1345, 1362, 1950, 2998, 3115, 3628, 3979                                                                         |
| <code>\int_if_exist:NTF</code>      | 1532, 1568, 1574, 1595, 1601, 1778                                                                                              |
| <code>\int_incr:N</code>            | 2833, 3034, 3189, 3384, 3473, 3771, 3806                                                                                        |
| <code>\int_mod:nn</code>            | 3621, 3972                                                                                                                      |
| <code>\int_new:N</code>             | 20, 21, 22, 23, 24, 48, 49, 73, 89, 101, 108, 116, 129, 130, 138, 139, 140, 141, 152, 158, 159, 160, 161, 162, 1534, 1781       |
| <code>\int_set:Nn</code>            | 676, 680, 682, 1671, 1678, 1690, 1699, 2012, 2180, 3229, 3230, 3252, 3263, 3269, 3285, 3604, 3642, 3653, 3659, 3675, 3955, 4101 |
| <code>\int_set_eq:NN</code>         | 1659, 1664, 2865, 3292, 3411, 3682                                                                                              |
| <code>\int_sign:n</code>            | 1866                                                                                                                            |
| <code>\int_step_function:nnN</code> | 2257, 2271, 2286                                                                                                                |
| <code>\int_step_inline:nnn</code>   | 3231, 4128                                                                                                                      |
| <code>\int_to_roman:n</code>        | 190, 2237, 2275                                                                                                                 |
| <code>\int_use:N</code>             | 324, 329, 330, 1053, 1673, 1680, 1692, 1701, 2753, 2772, 2795, 2851, 2950, 2959, 2974, 2980, 3267, 3268, 3280, 3657, 3658, 3670 |
| <code>\int_zero:N</code>            | 3613, 3964                                                                                                                      |
| <code>\c_one_int</code>             | 3252, 3271, 3277, 3283, 3287, 3290, 3642, 3661, 3667, 3673, 3677, 3680                                                          |
| <code>\c_zero_int</code>            | 2241, 2251, 2263, 2264, 2279, 2281, 3454, 3464, 3624, 3975                                                                      |
| <code>\item</code>                  | 30, 41, 42, 65, 75, 88, 90, 91, 93, 100                                                                                         |
| <code>\item</code>                  | 75, 76, 95, 97, 101, 104, 337, 2054, 2060, 2085, 2093, 2177, 2416, 2419, 2617, 2652, 3370, 3372, 3758, 3760, 3871               |
| <code>\item*</code>                 | 6, 12, 63, 2650                                                                                                                 |
| <code>item-pos*</code>              | 2525                                                                                                                            |
| <code>item-sym*</code>              | 2525                                                                                                                            |
| <code>\itemindent</code>            | 23, 79                                                                                                                          |
| <code>\itemindent</code>            | 78                                                                                                                              |
| <code>itemindent</code>             | 766                                                                                                                             |
| <code>\itemsep</code>               | 89, 90                                                                                                                          |
| <code>\itemsep</code>               | 3205, 3211                                                                                                                      |
| <code>\itemwidth</code>             | 3259, 3303, 3307, 3649, 3693, 3697                                                                                              |

K

|                                                            |                                                        |
|------------------------------------------------------------|--------------------------------------------------------|
| <code>keyans</code>                                        | 12, 3010                                               |
| <code>keyans*</code>                                       | 12, 3747                                               |
| <code>keyanspic</code>                                     | 13, 3165                                               |
| Keys for environments provide by <a href="#">enumext</a> : |                                                        |
| <code>above*</code>                                        | 24, 51, 52                                             |
| <code>above</code>                                         | 24, 51, 52, 83, 86, 94, 101                            |
| <code>after</code>                                         | 40-42, 85, 87, 94, 101                                 |
| <code>align</code>                                         | 24, 33, 77, 97                                         |
| <code>before*</code>                                       | 40, 41, 83, 94, 101                                    |
| <code>before</code>                                        | 40, 41, 86                                             |
| <code>below*</code>                                        | 24, 51-53                                              |
| <code>below</code>                                         | 24, 51-53, 85, 87, 94, 101                             |
| <code>check-ans</code>                                     | 24, 25, 27, 28, 58-63, 67, 72, 75, 76, 83, 85, 98, 110 |
| <code>columns-sep*</code>                                  | 25, 64, 82, 94                                         |
| <code>columns-sep</code>                                   | 42, 65, 82, 84, 86, 94                                 |
| <code>columns*</code>                                      | 25, 64, 82, 94                                         |
| <code>columns</code>                                       | 24, 42, 45, 51, 65, 82, 84, 86, 94                     |
| <code>first</code>                                         | 40-42, 97                                              |
| <code>font</code>                                          | 33, 77, 97                                             |
| <code>item-pos*</code>                                     | 67, 68, 74                                             |
| <code>item-sym*</code>                                     | 23, 67, 68, 74, 75                                     |
| <code>item*-sep</code>                                     | 75                                                     |
| <code>itemindent</code>                                    | 24, 38, 39, 77, 97                                     |

|                            |                                                                                       |
|----------------------------|---------------------------------------------------------------------------------------|
| <code>itemsep</code>       | 38, 80                                                                                |
| <code>labelsep</code>      | 33, 75, 79, 97                                                                        |
| <code>labelwidth</code>    | 32-37, 79                                                                             |
| <code>label</code>         | 23, 32, 34, 37, 91                                                                    |
| <code>lisparindent</code>  | 80                                                                                    |
| <code>list-indent</code>   | 23, 38, 39, 90                                                                        |
| <code>list-offset</code>   | 38, 39                                                                                |
| <code>listparindent</code> | 38, 97                                                                                |
| <code>mark-ans</code>      | 25, 63, 70                                                                            |
| <code>mark-pos</code>      | 63, 64                                                                                |
| <code>mark-ref</code>      | 25, 63, 68                                                                            |
| <code>mini-env</code>      | 24, 42, 45, 50, 51, 74, 83, 86, 92, 94, 99, 101                                       |
| <code>mini-sep</code>      | 24, 42, 83, 86                                                                        |
| <code>miniright*</code>    | 24, 42                                                                                |
| <code>miniright</code>     | 24, 42, 49, 92                                                                        |
| <code>minirigth*</code>    | 27                                                                                    |
| <code>minirigth</code>     | 27                                                                                    |
| <code>no-store</code>      | 25, 58-60                                                                             |
| <code>noitemsep</code>     | 38, 46                                                                                |
| <code>nosep</code>         | 38, 46                                                                                |
| <code>parindent</code>     | 80                                                                                    |
| <code>parsep</code>        | 38, 80, 97                                                                            |
| <code>partopsep</code>     | 38                                                                                    |
| <code>ref</code>           | 23, 27, 34-36, 109                                                                    |
| <code>resume*</code>       | 23, 53, 54, 58, 59, 85                                                                |
| <code>resume</code>        | 23, 29, 53-59, 85, 94                                                                 |
| <code>rightmargin</code>   | 38                                                                                    |
| <code>save-ans</code>      | 24, 29, 54-58, 60-62, 64, 65, 67, 70, 72, 76, 81, 85, 88, 94, 101, 103, 105, 106, 109 |
| <code>save-key</code>      | 25, 54, 81                                                                            |
| <code>save-ref</code>      | 26, 31, 63, 67, 68, 71, 72, 77, 103                                                   |
| <code>save-sep</code>      | 63, 103                                                                               |
| <code>series</code>        | 23, 53-58, 81, 85                                                                     |
| <code>show-ans</code>      | 25, 63, 64, 66, 67, 70, 77, 103                                                       |
| <code>show-length</code>   | 27, 40, 109                                                                           |
| <code>show-pos</code>      | 25, 63, 64, 66, 67, 70, 73, 77, 103                                                   |
| <code>start</code>         | 24, 27, 37, 54                                                                        |
| <code>store-brk</code>     | 67                                                                                    |
| <code>topsep</code>        | 38                                                                                    |
| <code>widest</code>        | 23, 27, 37                                                                            |
| <code>wrap-ans</code>      | 63, 66, 70                                                                            |
| <code>wrap-label*</code>   | 33, 75, 77, 96, 97, 102                                                               |
| <code>wrap-label</code>    | 33, 77, 96, 97, 102                                                                   |
| <code>wrap-opt</code>      | 63                                                                                    |

keys commands:

|                              |                                                                                                                                                                |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\keys_define:nn</code> | 448, 470, 499, 512, 559, 630, 704, 724, 768, 787, 844, 853, 932, 949, 1368, 1479, 1726, 1786, 1955, 1991, 2009, 2126, 2527, 4008, 4071                         |
| <code>\l_keys_key_str</code> | 4186                                                                                                                                                           |
| <code>\keys_set:nn</code>    | 462, 956, 1373, 1378, 1620, 1625, 1712, 1720, 2169, 2846, 2850, 3050, 3397, 3788, 4073, 4074, 4075, 4076, 4077, 4078, 4079, 4080, 4081, 4082, 4083, 4084, 4122 |

keyval commands:

|                                |      |
|--------------------------------|------|
| <code>\keyval_parse:NNn</code> | 1493 |
|--------------------------------|------|

L

|                                             |               |
|---------------------------------------------|---------------|
| <code>label</code>                          | 510, 557, 630 |
| Labels provide by <a href="#">enumext</a> : |               |
| <code>\Alph*</code>                         | 32            |
| <code>\Roman*</code>                        | 32            |
| <code>\alph*</code>                         | 32            |
| <code>\arabic*</code>                       | 27, 32        |
| <code>\roman*</code>                        | 32            |
| <code>\labelsep</code>                      | 90            |
| <code>\labelsep</code>                      | 3206, 3209    |

|                               |                                          |
|-------------------------------|------------------------------------------|
| labelsep .....                | 446                                      |
| \labelwidth .....             | 32, 90                                   |
| \labelwidth .....             | 3206, 3207                               |
| labelwidth .....              | 446                                      |
| \leftmargin .....             | 23, 79                                   |
| \leftmargin .....             | 78, 3206                                 |
| legacy commands:              |                                          |
| \legacy_if:nTF .....          | 3540, 3543, 3897, 3900                   |
| \legacy_if_gset_false:n ..... | 1046                                     |
| \legacy_if_set_false:n .....  | 3542, 3899                               |
| \legacy_if_set_true:n .....   | 3502, 3527, 3534, 3547, 3835, 3863, 3904 |
| \linewidth .....              | 83, 86                                   |
| \linewidth ....               | 2934, 3060, 3228, 3255, 3316, 3645, 3706 |
| \list .....                   | 30                                       |
| \list .....                   | 335                                      |
| list-indent .....             | 766                                      |
| list-offset .....             | 766                                      |
| \listparindent .....          | 3208                                     |
| listparindent .....           | 766                                      |
| \lrbox .....                  | 3557, 3910                               |

M

|                           |                                                                                                                                                                                                                                                            |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| \makebox .....            | 91                                                                                                                                                                                                                                                         |
| \makebox ..               | 2116, 2118, 2672, 3571, 3579, 3583, 3923, 3927                                                                                                                                                                                                             |
| \makelabel .....          | 75, 77, 78, 91                                                                                                                                                                                                                                             |
| \makelabel .....          | 77, 78, 2678, 2694                                                                                                                                                                                                                                         |
| \makesavenoteenv .....    | 368                                                                                                                                                                                                                                                        |
| mark-ans .....            | 1953                                                                                                                                                                                                                                                       |
| mark-pos .....            | 1953, 1989                                                                                                                                                                                                                                                 |
| mark-ref .....            | 1953                                                                                                                                                                                                                                                       |
| mini-env .....            | 930                                                                                                                                                                                                                                                        |
| mini-sep .....            | 930                                                                                                                                                                                                                                                        |
| \minipage .....           | 30                                                                                                                                                                                                                                                         |
| \minipage .....           | 341                                                                                                                                                                                                                                                        |
| \miniright .....          | 10, 50, 1314, 2996, 3113                                                                                                                                                                                                                                   |
| \miniright* .....         | 10                                                                                                                                                                                                                                                         |
| mode commands:            |                                                                                                                                                                                                                                                            |
| \mode_if_vertical:TF .... | 1001, 1029, 1152, 1231                                                                                                                                                                                                                                     |
| \mode_leave_vertical: ..  | 799, 813, 825, 837, 2085, 2093, 2114, 2670, 3569                                                                                                                                                                                                           |
| msg commands:             |                                                                                                                                                                                                                                                            |
| \msg_error:nn ..          | 3041, 3045, 3132, 3192, 3387, 3774, 3781, 4085                                                                                                                                                                                                             |
| \msg_error:nnn .....      | 535, 582, 599, 652, 1318, 1322, 1347, 1364, 1632, 1636, 1751, 3998, 4003, 4068, 4138                                                                                                                                                                       |
| \msg_error:nnnn .....     | 2140, 2144, 2148, 3032, 3128, 3136                                                                                                                                                                                                                         |
| \msg_fatal:nn .....       | 2835                                                                                                                                                                                                                                                       |
| \msg_fatal:nnn .....      | 400                                                                                                                                                                                                                                                        |
| \msg_info:nnn .....       | 13, 16, 350, 364                                                                                                                                                                                                                                           |
| \msg_line_context: ..     | 4158, 4162, 4166, 4190, 4195, 4200, 4215, 4230, 4234, 4238, 4242, 4246, 4250, 4256, 4262, 4268, 4281, 4286, 4291, 4296, 4301, 4305, 4310, 4315, 4319, 4324, 4328, 4333, 4338, 4343, 4347, 4351                                                             |
| \msg_log:nnn .....        | 1770, 1775, 1780                                                                                                                                                                                                                                           |
| \msg_log:nnnnn .....      | 328, 1904, 1909, 1914                                                                                                                                                                                                                                      |
| \msg_log:nnnnnn .....     | 320                                                                                                                                                                                                                                                        |
| \msg_new:nnn .....        | 4139, 4143, 4147, 4151, 4156, 4160, 4164, 4168, 4174, 4180, 4184, 4188, 4193, 4198, 4213, 4228, 4232, 4236, 4240, 4244, 4248, 4252, 4259, 4265, 4271, 4275, 4279, 4284, 4289, 4294, 4299, 4303, 4308, 4313, 4317, 4322, 4326, 4331, 4336, 4341, 4345, 4349 |
| \msg_term:nnnn ..         | 1735, 1740, 2762, 2772, 2801, 2806                                                                                                                                                                                                                         |
| \msg_term:nnnnn .....     | 1885                                                                                                                                                                                                                                                       |
| \msg_warning:nn .....     | 2995, 3112                                                                                                                                                                                                                                                 |

|                          |                                                |
|--------------------------|------------------------------------------------|
| \msg_warning:nnnn .....  | 1941, 1947, 2710, 2715, 3266, 3279, 3656, 3669 |
| \msg_warning:nnnnn ..... | 1880, 1890                                     |
| \multicolsep .....       | 84, 87                                         |
| \multicolsep .....       | 2964, 3085                                     |

N

|                            |                                                |
|----------------------------|------------------------------------------------|
| \NeedsTeXFormat .....      | 3                                              |
| \newcounter .....          | 403                                            |
| \NewDocumentCommand .....  | 1314, 2136, 3124, 3982, 4036, 4092             |
| \NewDocumentEnvironment .. | 2811, 3010, 3165, 3358, 3747                   |
| \newlabel .....            | 31                                             |
| \newlabel .....            | 386                                            |
| no-store .....             | 1784                                           |
| \noindent .....            | 93, 100                                        |
| \noindent ..               | 2941, 3065, 3325, 3371, 3612, 3715, 3759, 3963 |
| \nointerlineskip .....     | 2941, 3065, 3325, 3715                         |
| noitemsep .....            | 722                                            |
| \nopagebreak .....         | 1012, 1040, 1163, 1242, 1305, 1311             |
| \normalfont .....          | 2326, 2497, 2510, 3883                         |
| nosep .....                | 722                                            |

P

|                                         |                                                                                                                                    |
|-----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Packages:                               |                                                                                                                                    |
| enumext .....                           | 22, 34, 58, 79, 88, 108                                                                                                            |
| enumitem .....                          | 31, 32                                                                                                                             |
| expl3 .....                             | 91                                                                                                                                 |
| footnotehyper .....                     | 30                                                                                                                                 |
| hyperref .....                          | 25, 26, 30, 31, 68, 72, 97, 108                                                                                                    |
| lua-visual-debug .....                  | 45                                                                                                                                 |
| multicol .....                          | 22, 108                                                                                                                            |
| shortlst .....                          | 91                                                                                                                                 |
| \par ..                                 | 1012, 1040, 1163, 1242, 1305, 1311, 1340, 1357, 2305, 2985, 3000, 3102, 3117, 3240, 3343, 3350, 3612, 3626, 3733, 3740, 3963, 3977 |
| \parindent .....                        | 3589, 3933                                                                                                                         |
| \parsep .....                           | 43, 46, 89, 90                                                                                                                     |
| \parsep .....                           | 2086, 2094, 2792, 3205, 3212, 3217                                                                                                 |
| parsep .....                            | 722                                                                                                                                |
| \parskip .....                          | 3590, 3934                                                                                                                         |
| \partopsep .....                        | 90                                                                                                                                 |
| \partopsep .....                        | 2793, 3210                                                                                                                         |
| partopsep .....                         | 722                                                                                                                                |
| peek commands:                          |                                                                                                                                    |
| \peek_meaning:NTF .....                 | 3479, 3493, 3510, 3521, 3812, 3826, 3843                                                                                           |
| \peek_meaning_remove:NTF .....          | 3486, 3819                                                                                                                         |
| \peek_remove_spaces:n .....             | 2656                                                                                                                               |
| \phantomsection .....                   | 31                                                                                                                                 |
| \phantomsection .....                   | 375                                                                                                                                |
| prg commands:                           |                                                                                                                                    |
| \prg_do_nothing: .....                  | 379                                                                                                                                |
| \prg_new_protected_conditional:Npnn ... | 192                                                                                                                                |
| \prg_replicate:nn .....                 | 209                                                                                                                                |
| \prg_return_false: .....                | 196                                                                                                                                |
| \prg_return_true: .....                 | 195                                                                                                                                |
| \printkeyans .....                      | 14, 106, 4036                                                                                                                      |
| prop commands:                          |                                                                                                                                    |
| \prop_count:N .....                     | 322, 2036, 2293, 2329, 2397, 2500, 2513, 3886                                                                                      |
| \prop_gput_if_not_in:Nnn .....          | 2034                                                                                                                               |
| \prop_if_exist:NTF .....                | 1768, 4002                                                                                                                         |
| \prop_item:Nn .....                     | 4005                                                                                                                               |
| \prop_new:N .....                       | 1771                                                                                                                               |
| \ProvidesExplPackage .....              | 4                                                                                                                                  |

R

\raggedcolumns ..... 2973, 3091

\ref ..... 68, 71

ref ..... 510, 557, 630

\refstepcounter ..... 3549, 3906

regex commands:

    \regex\_match:nnTF 194, 679, 681, 693, 695, 2863, 2876, 3409, 3422

    \regex\_replace\_once:nnN ..... 202

\renewcommand ..... 545, 590, 607, 660

\RenewDocumentCommand ... 2549, 2617, 2652, 2678, 2694

\RequirePackage ..... 17

resume ..... 1477

resume\* ..... 1477

rightmargin ..... 766

\Roman ..... 32, 37

\Roman ..... 422

\roman ..... 32, 37

\roman ..... 423, 528, 4024

S

save-ans ..... 1724

save-ref ..... 1953

save-sep ..... 1953

scan commands:

    \scan\_stop: ..... 90, 3219, 3370, 3758, 3993, 3996

seq commands:

    \seq\_clear:N ..... 4099

    \seq\_const\_from\_clist:Nn ..... 4087

    \seq\_count:N ..... 323, 3178, 4103

    \seq\_gclear:N ..... 2547, 2548

    \seq\_gput\_right:Nn ..... 2043, 2560, 2561

    \seq\_if\_empty:NTF ..... 2566, 4051, 4117

    \seq\_if\_exist:NTF ..... 1773, 4049

    \seq\_item:Nn ..... 3237

    \seq\_map\_function:NN ..... 4108

    \seq\_map\_inline:Nn .. 4057, 4062, 4096, 4118, 4119

    \seq\_map\_pairwise\_function:NNN ..... 2568

    \seq\_new:N ..... 109, 110, 127, 153, 154, 1776

    \seq\_pop\_left:NN ..... 4107

    \seq\_put\_right:Nn ..... 3138, 4115, 4132

    \seq\_set\_from\_clist:Nn ..... 4100

    \seq\_set\_map\_e:NNn ..... 4109

    \seq\_show:N ..... 4053

series ..... 1477

\setcounter ..... 690, 694, 696, 2753, 2795, 3183

\setenumext . 6–9, 107, 4012, 4017, 4022, 4027, 4032, 4092

\setlength ..... 2087, 2095

show-ans ..... 1953, 1989

show-length ..... 842

show-pos ..... 1989

skip commands:

    \skip\_add:Nn . 981, 987, 993, 1003, 1007, 1031, 1035, 1132, 1138, 1144, 1154, 1158, 1180, 1233, 1237, 3205

    \skip\_eval:n ..... 2086, 2094

    \skip\_gset:Nn ..... 1253, 1257, 1261

    \skip\_gzero\_new:N ..... 1248, 1249

    \skip\_horizontal:N 814, 826, 838, 3572, 3586, 3930

    \skip\_horizontal:n ... 800, 2115, 2123, 2671, 2673, 3570, 3938

    \skip\_if\_eq:nnTF . 979, 985, 991, 1055, 1089, 1130, 1136, 1142, 1173, 1178, 1199, 1250, 1272, 1385, 1399, 1413, 1424, 1435, 1446, 1457, 1468

    \skip\_new:N ..... 69, 70, 74, 75, 76, 77, 78, 131, 172

    \skip\_set:Nn . 964, 968, 1017, 1021, 1058, 1062, 1066, 1073, 1077, 1081, 1092, 1097, 1101, 1107, 1112, 1117, 1175, 1176, 1177, 1184, 1188, 1192, 1201, 1206, 1210, 1213, 1217, 1221, 1252, 1256, 1274, 1278, 1282, 1288, 1292, 1296, 3199, 3213

    \skip\_set\_eq:NN 2751, 2791, 2792, 3589, 3590, 3933, 3934

    \skip\_use:N .. 966, 970, 1005, 1009, 1013, 1033, 1037, 1056, 1075, 1084, 1090, 1095, 1099, 1110, 1114, 1115, 1120, 1156, 1160, 1186, 1386, 1390, 1393, 1400, 1404, 1407, 2985

    \skip\_zero:N ..... 2793, 2964, 3085, 3210, 3211

    \skip\_zero\_new:N 1168, 1169, 1170, 1247, 1269, 1270, 1271

    \c\_zero\_skip . 979, 985, 991, 1056, 1090, 1130, 1136, 1142, 1173, 1178, 1199, 1250, 1272, 1386, 1400, 1413, 1424, 1435, 1446, 1457, 1468

\small ..... 4014, 4019, 4024, 4029, 4034

\star ..... 2531

start ..... 702

\stepcounter ..... 2553, 3145

str commands:

    \c\_backslash\_str 4158, 4162, 4166, 4170, 4171, 4172, 4176, 4177, 4273, 4277, 4286, 4287, 4291, 4292, 4296, 4297, 4328, 4329, 4333, 4338, 4339

    \c\_colon\_str ..... 2292, 2396, 3993

    \c\_left\_brace\_str .. 4238, 4242, 4255, 4261, 4267

    \c\_right\_brace\_str .. 4238, 4242, 4255, 4261, 4267

    \str\_case:nn ..... 214, 269

    \str\_case:nnTF ..... 1500, 1509

    \str\_clear:N ..... 2843, 3396

    \str\_count:n ..... 209

    \str\_if\_empty:NTF ..... 1521, 1562, 1589

    \str\_if\_eq:nnTF ..... 2754, 2797

    \str\_if\_in:nnTF ..... 3989

    \str\_new:N ..... 126, 167

    \str\_set:Nn ... 502, 503, 504, 1970, 1971, 1994, 1995

\string ..... 368

\strutbox . 1060, 1064, 1068, 1079, 1083, 1094, 1103, 1109, 1119, 1132, 1138, 1144, 1175, 1176, 1177, 1180, 1190, 1194, 1203, 1210, 1215, 1223, 1252, 1253, 1256, 1263, 1276, 1284, 1290, 1298, 3215

T

TeX and L<sup>A</sup>T<sub>E</sub>X commands:

    \@auxout ..... 384

    \@currenvir ..... 214, 269

    \protected@write ..... 384

text commands:

    \text\_expand:n ..... 3985

    \textasteriskcentered ..... 1967, 1981

    \thepage ..... 390

tl commands:

    \c\_space\_tl ..... 2478, 4200, 4215, 4238, 4242

    \tl\_clear:N .. 475, 481, 1951, 2166, 2339, 2413, 3849

    \tl\_clear\_new:N ..... 432

    \tl\_const:Nn ..... 37, 416

    \tl\_gclear:N . 314, 315, 316, 1542, 1547, 2689, 3354, 3573, 3744

    \tl\_gclear\_new:N ..... 1529

    \tl\_gput\_right:Nn ..... 417

    \tl\_greplace\_all:Nnn ..... 438

    \tl\_gset:Nn 246, 247, 260, 261, 1530, 1543, 1548, 1767, 3516

    \tl\_gset\_eq:NN ..... 434, 2598, 3566

|                                                                                                                                                                                                                                                                                                                                                                     |                                                |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| <code>\tl_if_blank:nTF</code> . . . . .                                                                                                                                                                                                                                                                                                                             | 3564                                           |
| <code>\tl_if_empty:NTF</code> . 533, 552, 580, 597, 617, 624, 650, 667, 1555, 1560, 1582, 1587, 1645, 1709, 1717, 1746, 1805, 1921, 2050, 2081, 2192, 2350, 2423, 2472, 2668, 3852, 4130                                                                                                                                                                            |                                                |
| <code>\tl_if_empty:nTF</code> . . . . .                                                                                                                                                                                                                                                                                                                             | 1610                                           |
| <code>\tl_if_exist:NTF</code> . . . . .                                                                                                                                                                                                                                                                                                                             | 1615                                           |
| <code>\tl_if_novalue:nTF</code> . . 2167, 2178, 2347, 2421, 2457, 2551, 2576, 2594, 2599, 2628, 2841, 3176, 3394, 3786, 3850, 4094                                                                                                                                                                                                                                  |                                                |
| <code>\tl_map_inline:Nn</code> . . . . .                                                                                                                                                                                                                                                                                                                            | 200, 435                                       |
| <code>\tl_new:N</code> 34, 39, 40, 43, 44, 50, 52, 53, 54, 56, 57, 90, 91, 92, 98, 99, 100, 102, 103, 104, 105, 106, 107, 113, 114, 124, 125, 135, 136, 137, 144, 145, 146, 149, 166, 169                                                                                                                                                                           |                                                |
| <code>\tl_put_left:Nn</code> 2058, 2091, 2175, 2484, 2519, 3868, 3871                                                                                                                                                                                                                                                                                               |                                                |
| <code>\tl_put_right:Nn</code> 433, 543, 588, 605, 658, 2013, 2020, 2062, 2097, 2177, 2183, 2191, 2194, 2204, 2209, 2212, 2218, 2244, 2254, 2268, 2284, 2290, 2295, 2342, 2345, 2352, 2354, 2381, 2386, 2391, 2394, 2403, 2416, 2419, 2425, 2430, 2440, 2868, 2881, 3414, 3427, 3854, 3855, 4010, 4015, 4020, 4025, 4030                                             |                                                |
| <code>\tl_remove_all:Nn</code> . . . . .                                                                                                                                                                                                                                                                                                                            | 4129                                           |
| <code>\tl_remove_once:Nn</code> . . . . .                                                                                                                                                                                                                                                                                                                           | 2232, 2366                                     |
| <code>\tl_replace_all:Nnn</code> . . . . .                                                                                                                                                                                                                                                                                                                          | 437                                            |
| <code>\tl_reverse:N</code> . . . . .                                                                                                                                                                                                                                                                                                                                | 2231, 2233, 2365, 2367                         |
| <code>\tl_set:Nn</code> . 45, 273, 280, 287, 402, 476, 480, 485, 486, 532, 577, 649, 797, 811, 823, 835, 1644, 1745, 2323, 2459, 2494, 2507, 2596, 3857, 3880, 4127                                                                                                                                                                                                 |                                                |
| <code>\tl_set_eq:NN</code> 443, 538, 541, 585, 587, 602, 604, 655, 657, 2230, 2364, 2377, 2640, 2644, 3157, 3159                                                                                                                                                                                                                                                    |                                                |
| <code>\tl_to_str:n</code> . . . . .                                                                                                                                                                                                                                                                                                                                 | 1615, 1621, 1626, 3985                         |
| <code>\tl_trim_spaces:n</code> . . . . .                                                                                                                                                                                                                                                                                                                            | 433, 4115, 4127, 4133                          |
| <code>\tl_use:N</code> . 439, 442, 554, 619, 626, 669, 868, 872, 876, 880, 884, 888, 892, 896, 900, 904, 908, 912, 916, 920, 924, 928, 2120, 2237, 2245, 2256, 2270, 2275, 2287, 2583, 2589, 2613, 2631, 2635, 2643, 2680, 2681, 2688, 2696, 2697, 2703, 2818, 3016, 3162, 3348, 3576, 3587, 3591, 3738, 3920, 3931, 3937, 3941, 4039, 4040, 4041, 4042, 4043, 4111 |                                                |
| token commands:                                                                                                                                                                                                                                                                                                                                                     |                                                |
| <code>\token_to_str:N</code> . . . . .                                                                                                                                                                                                                                                                                                                              | 386                                            |
| <code>\topsep</code> . . . . .                                                                                                                                                                                                                                                                                                                                      | 2087, 2095                                     |
| <code>topsep</code> . . . . .                                                                                                                                                                                                                                                                                                                                       | <u>722</u>                                     |
| <code>\typeout</code> . . . . .                                                                                                                                                                                                                                                                                                                                     | 354, 357, 367, 368                             |
| <b>U</b>                                                                                                                                                                                                                                                                                                                                                            |                                                |
| <code>\u</code> . . . . .                                                                                                                                                                                                                                                                                                                                           | 203                                            |
| use commands:                                                                                                                                                                                                                                                                                                                                                       |                                                |
| <code>\use:N</code> . . . . .                                                                                                                                                                                                                                                                                                                                       | 210, 2685, 2820                                |
| <code>\use:n</code> . . . . .                                                                                                                                                                                                                                                                                                                                       | 1491, 3991                                     |
| <code>\use_none:nn</code> . . . . .                                                                                                                                                                                                                                                                                                                                 | 378                                            |
| <code>\usecounter</code> . . . . .                                                                                                                                                                                                                                                                                                                                  | 2752, 2794                                     |
| <b>V</b>                                                                                                                                                                                                                                                                                                                                                            |                                                |
| <code>\value</code> . . . .                                                                                                                                                                                                                                                                                                                                         | 1558, 1564, 1571, 1577, 1585, 1591, 1598, 1604 |
| <code>\vspace</code> 1047, 1390, 1393, 1404, 1407, 1417, 1419, 1428, 1430, 1439, 1441, 1450, 1452, 1461, 1463, 1472, 1474, 2086, 2094, 3173, 3184, 3627, 3978                                                                                                                                                                                                       |                                                |
| <b>W</b>                                                                                                                                                                                                                                                                                                                                                            |                                                |
| <code>widest</code> . . . . .                                                                                                                                                                                                                                                                                                                                       | <u>702</u>                                     |
| <code>wrap-ans</code> . . . . .                                                                                                                                                                                                                                                                                                                                     | <u>1953</u>                                    |
| <code>wrap-label</code> . . . . .                                                                                                                                                                                                                                                                                                                                   | <u>446</u>                                     |
| <code>wrap-label*</code> . . . . .                                                                                                                                                                                                                                                                                                                                  | <u>446</u>                                     |
| <code>wrap-opt</code> . . . . .                                                                                                                                                                                                                                                                                                                                     | <u>1953</u>                                    |