

# enumext

ENUMERATE EXERCISE SHEETS

V1.0 2024-05-12<sup>\*</sup>

©2024 by Pablo González<sup>†</sup>

CTAN: <https://www.ctan.org/pkg/enumext>

 <https://github.com/pablgonz/enumext>

## Abstract

This package provides “*enumerated list*” environments for creating “*simple exercise sheets*” along with “*multiple choice questions*”, storing the `(answers)` to these in memory using the `multicol` package and the `l3seq` and `l3prop` modules.

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>	<b>4</b>	<b>The storage system</b>	<b>9</b>
1.1	Description and usage	3	4.1	Keys for storage	9
1.2	The concept of left margin	3	4.2	Keys for internal label and ref	10
1.3	User interface	3	4.3	Keys for debugging and checking	10
1.3.1	Internal counters	3	4.4	The command <code>\anskey</code>	10
1.3.2	Support for multicol	4	4.5	The environment <code>keyans</code>	10
1.3.3	Support for minipage	4	4.5.1	The <code>\item*</code> in <code>keyans</code>	11
1.3.4	The <code>\label</code> and <code>\ref</code> system	4	4.6	The environment <code>keyanspic</code>	11
1.3.5	Support for <code>\footnote</code>	4	4.6.1	The command <code>\anspic</code>	12
<b>2</b>	<b>The environment <code>enumext</code></b>	<b>4</b>	4.7	Printing stored content	12
2.1	The <code>\item*</code> in <code>enumext</code>	5	4.7.1	The command <code>\getkeyans</code>	12
2.1.1	Keys for <code>\item*</code> in <code>enumext</code>	5	4.7.2	The command <code>\printkeyans</code>	12
<b>3</b>	<b>The command <code>\setenumext</code></b>	<b>5</b>	<b>5</b>	<b>Full examples</b>	<b>13</b>
3.1	Keys for label and ref	6	<b>6</b>	<b>The way of non-enumerated lists</b>	<b>16</b>
3.2	Keys for spaces	6	<b>7</b>	<b>References</b>	<b>18</b>
3.2.1	Vertical spaces	7	<b>8</b>	<b>Change history</b>	<b>18</b>
3.2.2	Horizontal spaces	7	<b>9</b>	<b>Index of Documentation</b>	<b>19</b>
3.3	Keys for add code	8	<b>10</b>	<b>Implementation</b>	<b>21</b>
3.4	Keys for start and resume	8	<b>11</b>	<b>Index of Implementation</b>	<b>102</b>
3.5	Keys for multicol	8			
3.6	Keys for minipage	8			
3.6.1	The command <code>\miniright</code>	9			
3.6.2	The key <code>miniright</code>	9			

## Motivation and acknowledgments

Usually it is enough to use the classic `enumerate` environment to generate “*simple exercise sheets*” or “*multiple choice questions*”, the basic idea behind `enumext` is to cover three points:

1. To have a simple interface to be able to write “*lists of exercises*” with “*answers*”.
2. To have a simple interface for writing “*multiple choice questions*”.
3. To have a simple interface for placing “*columns*” and “*drawings*” or “*tables*”.

This package would not be possible without Phelype Oleinik who has collaborated and adapted a large part of the code and all  $\text{\LaTeX}$  team for their great work and to the different members of the `TeX-SX` community who have provided great answers and ideas. Here a note of the main ones:

1. Answer given by Alan Munn in `\topsep`, `\itemsep`, `\partopsep`, `\parsep` - what do they each mean (and what about the bottom)?
2. Answer given by Enrico Gregorio in Understanding minipages - aligning at top
3. Answer given by Ulrich Diez in Different mechanics of hyperlink vs. hyperref
4. Answer given by Enrico Gregorio in Minipage and multicol, vertical alignment

<sup>\*</sup>This file describes a documentation for v1.0, last revised 2024-05-12.

<sup>†</sup>E-mail: [pablgonz@educarchile.cl](mailto:pablgonz@educarchile.cl).

## License and Requirements

Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License (lpp), version 1.3 or later (<https://www.latex-project.org/lppl.txt>). The software has the status “maintained”.

The `enumext` package loads and requires `multicol`[3] package, need to have a modern TeX distribution such as TeX Live or MiKTeX. It has been tested with the standard classes provided by L<sup>A</sup>T<sub>E</sub>X: `book`, `report`, `article` and `letter` on 10pt, 11pt and 12pt.

1 Introduction

In the  $\text{\LaTeX}$  world there are many useful packages and classes for creating “lists of exercises”, “worksheets” or “multiple choice questions”, classes like `exam`[1] and packages like `xsim`[2] do the job perfectly, but they don’t always fit the basic day to day needs.

In my work (and in the work of many teachers) it is common to use “simple exercise sheets” also known as “informal lists of exercises”, as an example:

1. Factor  $x^2 - 2x + 1$

2. Factor  $3x + 3y + 3z$

3. True False

(a)  $\alpha > \delta$

(b)  $\text{\LaTeX}$ 2e is cool?

4. Related to Linux
- (a) You use linux?

(b) Usually uses the package manager?

(c) Rate the following package and class

i. `xsim-exam`

ii. `xsim`

iii. `exsheets`

Sometimes we are also interested in showing the “answers” along with the questions:

1. Factor  $x^2 - 2x + 1$ 

\* `(x - 1)^2`

2. Factor  $3x + 3y + 3z$ 

\* `3(x + y + z)`

3. True False

(a)  $\alpha > \delta$ 

\* `False`

(b)  $\text{\LaTeX}$ 2e is cool?

\* `Very True!`

4. Related to Linux
- (a) You use linux?

\* `Yes`

(b) Usually uses the package manager?

\* `Yes, dnf`

(c) Rate the following package and class

i. `xsim-exam`

\* `doesn't exist for now :(`

ii. `xsim`

\* `very good`

iii. `exsheets`

\* `obsolete`

Or we are interested in referring to a specific question and its “answer”, for example:

The answer to 3.(b) is “Very True!” and the answer to 4.(c).ii is “very good”.

Or we are interested in printing all the “answers”:

1.  $(x - 1)^2$

2.  $3(x + y + z)$

3. (a) False

(b) Very True!

4. (a) Yes
- (b) Yes, dnf

(c) i. doesn't exist for now :(

ii. very good

iii. obsolete

Another very common thing to use in my work is “multiple choice questions”, for example:

1. First type of questions

(A) value

(B) correct

2. Second type of questions

I.  $2\alpha + 2\delta = 90^\circ$

II.  $\alpha = \delta$

III.  $\angle EDF = 45^\circ$

(A) I only

(B) II only

(C) I and II only

(D) I and III only

(E) I, II, and III

★ 3. Third type of questions

(1)  $2\alpha + 2\delta = 90^\circ$

(2)  $\angle EDF = 45^\circ$


(A) value

(B) value


(C) value

(D) value


(E) value
4. Question with image and label below:




(A)




(B)



(C)



(D)



(E)

5. Question with image on left side:


(A) value

(B) value

(C) value

(D) correct

(E) value



Where what we are interested in the `<label>` and a “short note” that we leave as an explanation, and then print them:

1. (B),  $x = 5$

2. (D)

3. (C), some note
4. (B)

5. (D), “other note”

These “simple worksheets” or “multiple choice questions” appear to be easy to obtain using a combination of the `enumerate`, `minipage` and `multicols` environments, but like many things, what “looks simple” is not so simple.

The `enumext` package was created and designed to meet these small requirements in the creation of “simple worksheets” and “multiple choice questions”.

1.1 Description and usage

The `enumext` package defines enumerated environments using the `list` environment provided by  $\text{\LaTeX}$ , but “does not redefine” any internal commands associated with it such as `\list`, `\endlist` or `\item` outside of the “scope” in which they are defined.

- This package is NOT intend to replace the `enumerate` environment nor replace the powerful `enumitem`[5], the approach is intended to work without hindering either of them.  
This package can be used with `xelatex`, `lualatex`, `pdflatex` and the classical `latex>dvips>ps2pdf` and is present in  $\text{\TeX}$  Live and  $\text{\MiKTeX}$ , use the package manager to install. For manual installation, download `enumext.zip` and unzip it, run `lualatex enumext.dtx` and move all files to appropriate locations, then run `mktxlsr`. To produce the documentation run `lualatex enumext.dtx` two times.

```
enumext.sty  » TDS:tex/latex/enumext/
enumext.pdf  » TDS:doc/latex/enumext/
README.md   » TDS:doc/latex/enumext/
enumext.dtx  » TDS:source/latex/enumext/
```

The package is loaded in the usual way:

```
\usepackage{enumext}
```

1.2 The concept of left margin

There is a direct relationship between the parameters `\leftmargin`, `\itemindent`, `\labelwidth` and `\labelsep` plus an “extra space” that makes it difficult to obtain the desired *horizontal spaces* in a `list` environment.

Usually we don’t want the `list` to go beyond the left margin of the page, but since these four values are related, that causes a problem. The `enumitem`[5] package adds the `\labelindent` parameter to solve some of these problems. A simplified representation of this in the figure 1.




Figure 1: Representation of horizontal lengths in `enumitem`.

The `enumext` package does NOT provide a user interface to set the values for `\leftmargin` and `\itemindent`, instead it provides the keys `list-offset` and `list-indent` which internally set the values for `\leftmargin` and `\itemindent`. The concepts of `\leftmargin` and `\itemindent` are different in `enumext`. The figure 2 shows the visual representation of idea.




Figure 2: Representation of horizontal lengths concept in `enumext`.

In this way we reduce a *little* the amount of parameters we have to pass. With the default values of keys `list-offset`, `list-indent`, `labelwidth` and `labelsep` the lists will have the (usually) expected output for “*simple worksheets*”. The figure 3 shows the visual representation.



Figure 3: Default horizontal lengths `list-offset=0pt`, `list-indent=\labelwidth+\labelsep` in `enumext`.

1.3 User interface

The user interface consists in `enumext`, `enumext*`, `keyans`, `keyans*` and `keyanspic` environments, `\anskey`, `\item*` and `\anspic*` commands to  $\langle$ stored content $\rangle$ , `\getkeyans` command to get the individual  $\langle$ stored content $\rangle$ , `\printkeyans` to print all  $\langle$ stored content $\rangle$ , `\miniright` for `minipage` and `\setenumext` to config all  $[ \langle key = val \rangle ]$  options.

1.3.1 Internal counters

The package `enumext` uses internally the `enumXi`, `enumXii`, `enumXiii`, `enumXiv` counters for the four nesting levels of the `enumext` environment, the `enumXv` counter for the `keyans` environment, the `enumXvi` counter for the `keyanspic` environment, the counter `enumXvii` for `enumext*` environment and the counter `enumXviii` for `keyans*` environment.

- If any package defines these counters or they are user-defined in the document, the package will return a missing error and abort the load.

### 1.3.2 Support for multicols

The package provides direct support for using the `multicol`[3] package. This allows to obtain directly a two-column output as shown in the figure 4.




Figure 4: Representation of the two column output for a nested level in `enumext` environment.

The “non starred” version of the `multicols` environment is always used together with the `\raggedcolumns` command and is controlled by `columns` and `columns-sep` keys. The environment is available for all nesting levels, and can can together with the `mini-env` key. If you need to force a start a new column `\columnbreak` must be used (see §3.5).

- The `\columnseprule` command is not available as a key and is set to “zero” for the inner levels and the `keyans` environment. If the value of this is set inside the document, it will affect “all environments” that use the `columns` key.

### 1.3.3 Support for minipage

The package provides direct support for `minipage` environment, this allows you to obtain an output like the one shown in figure 5.



Figure 5: Representation of the `mini-env` output for a nested level `enumext` environment.

The `minipage` environments (left and right) is always used with “aligned on top” [`t`], the `minipage` environment on the “right side” always starts with `\centering`. It can be used at all nesting levels and is controlled by `mini-env` and `mini-sep` keys. In order to switch from the “left” side `minipage` environment to the “right” side one must use the command `\miniright` (see §3.6).

### 1.3.4 The \label and \ref system

This package provides a user interface like the `enumitem`[5] package to customize the references which is activated by the `ref` key (§3.1), the standard  $\TeX$  `\label` and `\ref` commands work as usual. It also provides an “internal reference” system for the “stored content” by means of the key `save-ref` (§4.2) when the key `save-ans`(§4.1) is active.

- The implementation of `\label` and `\ref` together with the `save-ref` key are compatible with the `hyperref`[7] package.

### 1.3.5 Support for \footnote

This package provides an internal implementation for the `\footnote` command which is compatible with the `hyperref` package, but, it will not produce the expected links, and when using the `mini-env` key or the starred environments `enumext*` and `keyans*` the output will look like the classic way they are displayed in the `minipage` environment.

The best way to solve this is to use Jean-François Burnol `footnotehyper`[8] package, it will support keeping the links if `hyperref` is loaded with the `hyperfootnotes=true` option (default) and will show the output numbered at the bottom of the page (as opposed to how it is displayed in the `minipage` environment). The way to load it is as follows:

```
\usepackage{footnotehyper}
\makesavenoteenv{enumext}
\makesavenoteenv{enumext*}
```

## 2 The environment enumext

```
enumext \begin{enumext} [⟨keyval list⟩]
enumext* \item ⟨item content⟩
          \item [⟨custom⟩] ⟨item content⟩
          \item* [⟨symbol⟩] [⟨offset⟩] ⟨item content⟩
          \end{enumext}
```

```
\begin{enumext*} [⟨keyval list⟩]
\item ⟨item content⟩
\item [⟨custom⟩] ⟨item content⟩
\item* [⟨symbol⟩] [⟨offset⟩] ⟨item content⟩
\end{enumext*}
```

The `enumext` is an “*enumerated list*” environment that works in the same way as the standard `enumerate` environment provided by L<sup>A</sup>T<sub>E</sub>X, `\item` and `\item[⟨custom⟩]` commands work in the usual way.

The environment can be nested with at most “*four levels*” and the options can be configured globally using `\setenumext` command and locally using `[⟨key = val⟩]` in the environment.

### Example

1. This text is in the first level.
  - (a) This text is in the second level.
    - i. This text is in the third level.
      - A. This text is in the fourth level.
- X This text is in the first level.
- ★ 2. This text is in the first level.

```
\begin{enumext}
  \item This text is in the first level.
  \begin{enumext}
    \item This text is in the second level.
    \begin{enumext}
      \item This text is in the third level.
      \begin{enumext}
        \item This text is in the fourth level.
      \end{enumext}
    \end{enumext}
  \end{enumext}
  \item[X] This text is in the first level.
  \item* This text is in the first level.
\end{enumext}
```

## 2.1 The \item\* in enumext

---

```
\item* \item*
\item*[⟨symbol⟩]
\item*[⟨symbol⟩][⟨offset⟩]
```

---

The `\item*`, `\item*[⟨symbol⟩]` and `\item*[⟨symbol⟩][⟨offset⟩]` works like the numbered `\item`, but placing a `⟨symbol⟩` to the “left” of the `⟨label⟩` separated from it by the value set by the `labelsep` key and can be `⟨offset⟩` using the second optional argument. The default values for `⟨symbol⟩` and `⟨offset⟩` are `$\star$ ‘★’` and the value set by `labelsep` key.

The *starred version* ‘★’ cannot be separated by spaces ‘’ from the command, i.e. `\item*` and the first optional argument does “*not support*” verbatim content. Can be configure with the keys `item-sym*` and `item-pos*` locally in the environment or globally using `\setenumext` command (§3).

🔗 The behavior of `\item*` in the `enumext` environment is NOT the same as in the `keyans` environment.

### 2.1.1 Keys for \item\* in enumext

`item-sym* = {⟨symbol⟩}` default: `$\star$`  
 Sets the `symbol` to be displayed in the “left” of the box containing the current `⟨label⟩` set by `labelwidth` key for `\item*` in `enumext`. The `symbol` can be in text or math mode, for example `item-sym*={\ast$}`.

`item-pos* = {⟨rigid length | dim expression⟩}` default: *by levels*  
 Sets the `offset` between the box containing the current `⟨label⟩` defined by `labelwidth` key and the `⟨symbol⟩` set by `item-sym*` key. The default values are set by `labelsep` key at each level. If positive values are passed it will *offset to the left* and if negative values are passed it will *offset to the right*.

## 3 The command \setenumext

---

```
\setenumext \setenumext[⟨enumext, level⟩]{⟨key = val⟩} \setenumext[⟨enumext*⟩]{⟨key = val⟩}
\setenumext[⟨print, level⟩]{⟨key = val⟩} \setenumext[⟨keyans*⟩]{⟨key = val⟩}
\setenumext[⟨keyans⟩]{⟨key = val⟩} \setenumext[⟨print*⟩]{⟨key = val⟩}
```

---

The command `\setenumext` sets the `⟨keys⟩` on a global basis for environment `enumext`, the `\printkeyans` command and the `keyans` environment. It can be used both in the preamble and in the body of the document as many times as desired.

The `⟨keys⟩` set in the optional arguments of environments and commands have the highest precedence, overriding both options passed by `\setenumext`. If the optional argument is not passed, the first level of the environment `enumext` will be taken by default.

- It should be kept in mind that using any *key* that sets a *rubber or rigid lengths* for vertical or horizontal space on a level will influence the vertical and horizontal space for *inners levels* and *keyans* and *keyanspic* environments. All *keys* related to vertical or horizontal spacing accept a “*skip*” or “*dim*” expression if passed between braces, i.e. you do not need to use `\dimexpr` or `\dimeval` to perform calculations.

### 3.1 Keys for label and ref

`label = {⟨\alph* | \Alph* | \arabic* | \roman* | \Roman*⟩}` default: *by levels*

Sets the *label* that will be printed at the *current level*. The default value for first level are `\arabic*`, for second level are `(\alph*)`, for third level are `\roman*`, and for fourth level are `\Alph*`.

- This key is intended to give the basic structure with which the *label* will be displayed, and the and the form in which it is used by standard “*label and ref*” and the “*internal reference*” system with the *save-ref* key. You cannot use commands with *label* as an argument, for example `\emph{⟨\alph*⟩}` will return an error. For full customization of how *label* is displayed use the *font* or *wrap-label* keys.

`ref = {⟨code {⟨\alph* | \Alph* | \arabic* | \roman* | \Roman*⟩ more code⟩}` default: *empty*

Modifies the way *cross references* are displayed. The *label* key sets the default form of the *cross references*, by using this key you can define a different format, for example: `ref=\emph{⟨\alph*⟩}` is valid.

- Internally, it renews the command associated with each counter when it is executed, i.e., `\theenumXi` is modified when the key is executed at the first level, `\theenumXii` when it is executed at the second level and `\theenumXiii` together with `\theenumXiv` when it is executed at the third and fourth levels.

This must be kept in mind, since the values set by the *label* and *ref* keys are not cumulative by levels, so if you have used the *ref* key in the first level and then want to associate the counter with *label* or *ref* in the second level you must use the direct commands, i.e. `\arabic{enumXi}` to indicate the count of the first level instead of using `\theenumXi`.

`labelsep = {⟨rigid length⟩}` default: `0.3333em`

Sets the *horizontal space* between the box containing the current *label* defined by *label* key and the text of an item on the first line. Internally sets the value of `\labelsep` for the current level.

`labelwidth = {⟨rigid length⟩}` default: *by label*

Sets the *width* of the box containing the current *label* set by *label* key. Internally sets the value of `\labelwidth` for the current level. The default values are calculated by means of the *width* of a box by setting a *value* to the current counter using ‘0’ for `\arabic*`, ‘M’ for `\Alph*`, ‘m’ for `\alph*`, ‘VIII’ for `\Roman*` and ‘viii’ for `\roman*`.

`widest = {⟨integer | string⟩}` default: *empty*

Sets the *labelwidth* key pass the *integer* or converting the *string* of the form `\Alph`, `\alph`, `\Roman` or `\roman` to a *value* for the current counter defined by *label* key, then calculating the *width* by means of a box. For example `widest={XXIII}` or `widest={23}` are equivalent. This key is useful when the default values of the *labelwidth* key are smaller than those actually used.

`font = {⟨font commands⟩}` default: *empty*

Sets the *font style* for the current *label* defined by *label* key. For example `font={\bfseries\small}`.

`align = {⟨left | right | center⟩}` default: *left*

Sets the *aligned* of *label* defined by *label* key on the current level in the label box.

`wrap-label = {⟨code {#1} more code⟩}` default: *empty*

Wraps the current *label* defined by *label* key referenced by `{#1}`. The `{⟨code⟩}` must be passed between braces. This key does not modify the value set by the *labelwidth* key and is applied only on `\item` and `\item*`. When using it in the `\setenumext` command it is necessary to use the *double hash* ‘`{#1}`’. For example `wrap-label={\fbox{#1}}` or you can create a command:

```
\NewDocumentCommand \itembx { s +m }
{%
  \IfBooleanTF{#1}
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedright{#2}}}}%
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{#2}}}}%
}
```

and then pass it through the key `wrap-label={\itembx{#1}}` or `wrap-label={\itembx*{#1}}`.

`wrap-label* = {⟨code {#1} more code⟩}` default: *empty*

The same as the *wrap-label* key but also applies on `\item[⟨custom⟩]`.

### 3.2 Keys for spaces

`show-length = {⟨true | false⟩}` default: *false*

Displays on the terminal the values for *all list parameters* at the current level. For *vertical spaces* show the values of `\topsep`, `\itemsep`, `\parsep` and `\partopsep`. For *horizontal spaces* show the values of `\labelwidth`, `\labelsep`, `\itemindent`, `\listparindent` and `\leftmargin`.



### 3.2.1 Vertical spaces

`topsep` = {*rubber length* | *rigid length*} default: *by levels*

Set the *vertical space* added to both the top and bottom of the list. Internally sets the value of `\topsep` for the current level. The default values for first level are 8.0pt plus 2.0pt minus 4.0pt, for second level are 4.0pt plus 2.0pt minus 1.0pt, for third and fourth level are 2.0pt plus 1.0pt minus 1.0pt.

`parsep` = {*rubber length* | *rigid length*} default: *by levels*

Set the *vertical space* between paragraphs within an item. Internally sets the value of `\parsep` for the current level. The default values for first level are 4.0pt plus 2.0pt minus 1.0pt, for second level are 2.0pt plus 1.0pt minus 1.0pt, for third and fourth level are 0pt.

`partopsep` = {*rubber length* | *rigid length*} default: *by levels*

Set the *vertical space* added, beyond `topsep`, to the “top” and “bottom” of the entire environment if the environment instance is preceded by a “blank line” or `\par` command. Internally sets the value of `\partopsep` for the current level. The default values for first and second level are 2.0pt plus 1.0pt minus 1.0pt, for third and fourth level are 1.0pt minus 1.0pt.

- The value of this parameter also affects the *inner levels* and the `keyans` environment. Caution should be taken with “blank lines” or `\par` command “before” each environment or nested level when formatting the source code of document. T<sub>E</sub>X will enter *vertical mode* and apply this value to the “top” and “bottom” the environment or nested level.

`itemsep` = {*rubber length* | *rigid length*} default: *by levels*

Set the *vertical space* between items, beyond the `parsep`. Internally sets the value of `\itemsep` for the current level. The default values for first level are 4.0pt plus 2.0pt minus 1.0pt, for the rest of the levels are 2.0pt plus 1.0pt minus 1.0pt.

`noitemsep` *value forbidden* default: *not used*

This is a “meta-key” that does not receive an argument. Set `itemsep` and `parsep` equal to 0pt the entire level of environment.

`nosep` *value forbidden* default: *not used*

This is a “meta-key” that does not receive an argument. Sets all keys for vertical spacing equal to 0pt the entire level of environment.

- The following *keys* should be used with “caution”, they are intended to be used at the “top” and “bottom” of the environment when the `columns` or `mini-env` keys do not provide adequate *vertical spaces*. The values passed can be *rubber* or *rigid* lengths, the way they are applied is the way you differ, using the star ‘\*’ *keys* applies `\vspace*` so that T<sub>E</sub>X does *not discard* this space at page break.

`above` = {*rubber length* | *rigid length*} default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the top of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “above” the environment without hindering the value of the `topsep` key. The space is added with `\vspace` so is “discardable”.

`above*` = {*rubber length* | *rigid length*} default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the top of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “above” the environment without hindering the value of the `topsep` key. The space is added with `\vspace*` so is “not discardable”.

`below` = {*rubber length* | *rigid length*} default: *not used*

Set the *extra vertical space* space added, beyond `topsep`, to the bottom of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “below” the environment without hindering the value of the `topsep` key. The space is added with `\vspace` so is “discardable”.

`below*` = {*rubber length* | *rigid length*} default: *not used*

Set the *extra vertical space* space added, beyond `topsep`, to the bottom of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “below” the environment without hindering the value of the `topsep` key. The space is added with `\vspace*` so is “not discardable”.

### 3.2.2 Horizontal spaces

`itemindent` = {*rigid length*} default: 0pt

Extra *horizontal indentation*, beyond `labelsep`, of the “first line” off each item. This value is applied internally using `\hspace` and does not modify the value of `\itemindent`.

`rightmargin` = {*rigid length*} default: 0pt

Set the *horizontal space* between the right margin of the environment and the right margin of the enclosing environment, the value it takes must be greater than or equal to 0pt. Internally sets the value of `\rightmargin` for the current level.

`listparindent` = {*rigid length*} default: 0pt

Sets the *horizontal space* indentation, beyond `list-indent`, for second and subsequent paragraphs within a list item. Internally sets the value of `\listparindent` for the current level.

`list-offset` = {*rigid length*} default: 0pt



Sets the *horizontal translation* of the entire environment level from the left edge of the box defined by the `labelwidth` key. Internally sets the values of `\leftmargin` and `\itemindent` for the current level.

`list-indent = {⟨rigid length⟩}` default: `labelwidth + labelsep`

Sets the *indentation* of the whole environment under the box defined by `labelwidth` and `labelsep` keys. Internally sets the value of `\leftmargin` and `\itemindent` for the current level.

- If `list-indent=0pt` the `⟨label⟩` will be part of the text, separated by the value of the `labelsep` key and the *first word*, in simple terms it will look like a “*common paragraph*”. This setting is equivalent (more or less) to the `wide` key provided by the `enumitem` package.

### 3.3 Keys for add code

- The following `⟨keys⟩` should be used with “*caution*”, they are intended to inject `{⟨code⟩}` into different parts of the defined environments. We must keep in mind that the defined environments are based on the `list` base environment provided by `ℒTEX` which is defined (simplified) as plain form `\list{⟨arg one⟩}{⟨arg two⟩}`. Using the `before*` key does not allow access to the `list` parameters defined by `[⟨key = val⟩]`.

`before = {⟨code⟩}` default: *not used*

Execute `{⟨code⟩}` “*before*” the environment starts. The `{⟨code⟩}` must be passed between braces, is executed “*after*” performing all calculations related to the *list parameters* in the environment and the parameters sets by `[⟨key = val⟩]` that is, in the second argument of the list after setting all the parameters `\list{⟨arg one⟩}{⟨arg two⟩}{⟨code⟩}`.

`before* = {⟨code⟩}` default: *not used*

Execute `{⟨code⟩}` “*before*” the environment starts. The `{⟨code⟩}` must be passed between braces, is executed “*before*” performing all calculations related to the *list parameters* and `[⟨key = val⟩]` sets in the environment that is, before the arguments defining the environment are executed: `{⟨code⟩}\list{⟨arg one⟩}{⟨arg two⟩}`.

`first = {⟨code⟩}` default: *not used*

Executes `{⟨code⟩}` when “*starting*” the environment. The `{⟨code⟩}` must be passed between braces, is executed right “*after*” all *list parameters* are done, after the second argument of list, just before the first occurrence of `\item`: `\list{⟨arg one⟩}{⟨arg two⟩}{⟨code⟩}\item`.

- Keep in mind that the code set in this key will affect the entire “*body*” of the environment and therefore the inner levels of the list and the `keyans` environment. It is recommended to set this key per level.

`after = {⟨code⟩}` default: *not used*

Execute `{⟨code⟩}` “*after*” finishing the environment. The `{⟨code⟩}` must be passed between braces.

### 3.4 Keys for start and resume

`start = {⟨integer | string⟩}` default: `1`

Sets the *start value* of the numbering on the current level. Internally `⟨string⟩` is passed as value to the counter defined by `label` key on the current level, i.e. it is equivalent to enter `start=5`, `start=E` or `start=v`.

`resume ⟨value forbidden⟩` default: *not used*

Sets the *start* to value from the previous of the counter defined by `label` key for the “*first level*”. This `⟨key⟩` does not receive an argument. The `⟨key⟩` can be overwritten using the `start` key. If the `save-ans` key is present and `{⟨store name⟩}` exist, the numbering will continue according to this key. This key is “*only*” available for the “*first level*” of `enumext`.

### 3.5 Keys for multicol

`columns = {⟨integer⟩}` default: `1`

Set the *number of columns* to be used by the `multicols` environment within the environment. The value must be a positive integer less than or equal to `10`.

`columns-sep = {⟨rigid length⟩}` default: *by level*

Set the *space between columns* used by the `multicols` environment within the environment. Internally sets the value of `\columnsep`, by default its value is equal to the sum of the values set in the keys `labelwidth` and `labelsep` of the current level.

- The `\footnote{⟨text⟩}` command in the nested levels of `multicols` will not work as expected, prefer the use of `\footnotemark[⟨number⟩]` inside the environment and `\footnotetext[⟨number⟩]{⟨text⟩}` outside the environment or via the `after` key.

### 3.6 Keys for minipage

`mini-env = {⟨rigid length⟩}` default: *not used*

Sets the *width* of the `minipage` environment on the “*right side*”. This value added to the value set by the `mini-sep` key to determines the *width* of the `minipage` environment on the “*left side*”, taking `\linewidth` as the maximum reference value.

`mini-sep = {⟨rigid length⟩}` default: `0.3333em`

Sets the *space between* the `minipage` environment on the “*left side*” and the `minipage` environment on the “*right side*”. This separation is applied together with `\hfill`.

### 3.6.1 The command `\miniright`

`\miniright` The `\miniright` command close the `minipage` environment on the “left side” and opens the `minipage` environment on the “right side” by starting it with the `\centering` command. It must be placed “after” the last `\item` of the current environment and “before” starting the material to be placed on the “right side”. The *starred version* ‘`*`’ inhibits the use of `\centering` command i.e. the usual L<sup>A</sup>T<sub>E</sub>X justification is maintained in the `minipage` on the “right side”.

- The `\footnote{⟨text⟩}` command in `minipage` environment will work as usual. If you prefer the footnotes to be numbered (not lowercase) and outside the environment, use `\footnotemark[⟨number⟩]` inside the environment and `\footnotetext[⟨number⟩]{⟨text⟩}` outside the environment or via the `after` key.

### 3.6.2 The key `miniright`

In the horizontal list environments `enumext*` and `keyans*` it is not possible to use the `\miniright` command and the `miniright` key must be used instead.

`miniright` = {⟨code for drawing or tabular⟩} default: not used

Set the *code* for the drawing or tabular to be placed in the `minipage` environment on the “right side” by starting it with the command `\centering`.

`miniright*` = {⟨code for drawing or tabular⟩} default: not used

Same as above, but *without* starting with the `\centering` command.

## 4 The storage system

The entire mechanism for “storing content” it is activated according to `save-ans` key on the “first level” of `enumext` environment. Only when this *key* is “active” the `\anskey` command and the environments `keyans` and `keyanspic` are available.

<pre>\begin{enumext}[save-ans={⟨store name⟩}]   \item Text     \begin{keyans}       ...     \end{keyans} \end{enumext}</pre>	<pre>\begin{enumext}[save-ans={⟨store name⟩}]   \item Text     \begin{keyanspic}       ...     \end{keyanspic} \end{enumext}</pre>
--	--

### 4.1 Keys for storage

`save-ans` = {⟨store name⟩} default: not set

Sets the *name* of the ⟨sequence⟩ and ⟨prop list⟩ in which the contents will be “stored” by `\anskey` in `enumext` environment, `\item*` in `keyans` and `keyans*` environments and `\anspic*` in `keyanspic` environment. If the ⟨sequence⟩ or ⟨prop list⟩ does not exist, it will be created globally.

`wrap-ans` = {⟨code {#1} more code⟩} default: \fbox{#1}

Wraps the *current argument* passed `\anskey` command to referenced by {#1}. The {⟨code⟩} must be passed between braces and only affects the ⟨current argument⟩ passed to `\anskey` and NOT the “stored content” in the ⟨store name⟩ set by `save-ans` key. If this key is passed using the `\setenumext` command it is necessary to use double ‘{##1}’.

`wrap-opt` = {⟨code {#1} more code⟩} default: [{#1}]

Wraps the *optional argument* passed to the `\item*` and `\anspic*` commands referenced by {#1} in the `keyans`, `keyans*` and `keyanspic` environments. The {⟨code⟩} must be passed between braces and only affects the current ⟨optional argument⟩ and NOT the “stored content” in ⟨store name⟩ set by `save-ans` key. If this key is passed using the `\setenumext` command, it is necessary to use the double ‘{##1}’.

`save-sep` = {⟨text symbol⟩} default: {, }

Sets the *text symbol* that will separate the current ⟨label⟩ defined by the `label` key from the ⟨optional argument⟩ (if present), when storing them in the ⟨store name⟩ defined by the `save-ans` key for the `\item*` command in the `keyans` and `keyans*` environment and for the `\anspic` command in the `keyanspic` environment. The {⟨text symbol⟩} must always be passed between braces, whitespace ‘`␣`’ is preserved within the braces and only affects the “stored content” and not what is displayed when using the `show-ans` or `show-pos` keys.

`mark-ans` = {⟨symbol⟩} default: \textasteriskcentered

Sets the *symbol* to be displayed in the left margin of the “stored content” in ⟨store name⟩ set by `save-ans` key when using `show-ans` key.

`mark-pos` = {⟨left | right⟩} default: left

Sets the aligned of the *symbol* defined by `mark-ans` key. The “symbol” is aligned in a box with the same dimensions of the label box defined by `labelwidth` key on the current level and separated by the value of the `labelsep` key.

## 4.2 Keys for internal label and ref

`save-ref = {⟨true | false⟩}`

default: *false*

Activates the internal “*label and ref*” mechanism for referencing “*stored content*” in ⟨*store name*⟩ set by `save-ans` key. To reference the location of the “*stored content*” within the environment you must use `\ref{⟨store name⟩:⟨position⟩}`, where ⟨*position*⟩ corresponds to the position occupied by the “*stored content*” in the ⟨*store name*⟩ returned by the `show-pos` key. For example `\ref{test:4}` will return 3.(b) which corresponds to the location of the “*stored content*” at position 4 within the environment in which the key `save-ans=test` was set.

`mark-ref = {⟨symbol⟩}`

default: *\textasteriskcentered*

Sets the *symbol* that will be displayed by the `\printkeyans` command only if the `hyperref` package is detected and the `save-ref` key are active. This “*symbol*” is used as a “*link*” between the environment in which the `save-ans` key was used and the place where the command is executed.

## 4.3 Keys for debugging and checking

`show-ans = {⟨true | false⟩}`

default: *false*

Displays the *current* ⟨*argument*⟩ passed to `\anskey` in `enumext` environment, the current ⟨*label*⟩ for `\item*` in `keyans` environment and the current ⟨*label*⟩ for `\anspic*` in `keyanspic` environment at the place where it is executed. If the optional argument is present in `\item*` or `\anspic*` it will be shown in square brackets.

`show-pos = {⟨true | false⟩}`

default: *false*

Displays the *position* occupied by the “*stored content*” by `\anskey` in `enumext` environment, `\item*` in `keyans` environment and `\anspic*` in `keyanspic` environment in ⟨*store name*⟩ set by `save-ans` key. This position is used by the `\getkeyans` command and by the `\ref` command if the `save-ref` key is active.

`check-ans = {⟨true | false⟩}`

default: *false*

Enables the *checking answer* mechanism. This key works under the logic that each question will contain “*only one answer*”, it is intended to be used in conjunction with `no-store` key.

`no-store` ⟨*value forbidden*⟩

default: *not used*

This is a *meta-key* that does not receive an argument. This key is used in conjunction with `check-ans` and is designed to be used with nested levels of `enumext` in which the `\anskey` command will not be used.

## 4.4 The command \anskey

`\anskey` `\anskey{⟨content⟩}`

The `\anskey` command takes a mandatory argument and is triggered by `save-ans` key. The “*content*” are “*stored*” in ⟨*store name*⟩ set by `save-ans` key. The command does “*not support*” verbatim content and must NOT be nested. By design it is assumed that each `\item` or `\item*` will have a “*single*” occurrence of the command unless a nested level is opened or the `no-store` key is used. If `save-ref` key are active and the `hyperref`[7] package is detected, `\hyperlink` and `\hypertarget` will be used, otherwise the usual “*label and ref*” system provided by L<sup>A</sup>T<sub>E</sub>X will be used.

### Example

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>★ 1. Text containing our instructions or questions.</li> <li style="margin-left: 20px;">* <span style="border: 1px solid black; padding: 2px;">first answer</span></li> <li>2. Text containing our instructions or questions.</li> <li style="margin-left: 20px;">(a) Question.</li> <li style="margin-left: 40px;">* <span style="border: 1px solid black; padding: 2px;">second answer</span></li> </ul> | <ul style="list-style-type: none"> <li>3. Text containing our instructions or questions.</li> <li style="margin-left: 20px;">* <span style="border: 1px solid black; padding: 2px;">third answer</span></li> <li>4. Text containing our instructions or questions.</li> <li style="margin-left: 20px;">* <span style="border: 1px solid black; padding: 2px;">fourth answer</span></li> </ul> |
|---|---|

```
\begin{enumext}[save-ans=test,show-ans=true]
  \item* Text containing our instructions or questions. \anskey{⟨first answer⟩}
  \item Text containing our instructions or questions.
    \begin{enumext}
      \item Question.\anskey{⟨second answer⟩}
    \end{enumext}
  \item Text containing our instructions or questions. \anskey{⟨third answer⟩}
  \item Text containing our instructions or questions. \anskey{⟨fourth answer⟩}
\end{enumext}
```

## 4.5 The environment keyans

`keyans` `\begin{keyans}[⟨key = val⟩] \item \item[⟨custom⟩] \item* \item*[⟨content⟩] \end{keyans}`

`keyans*` `\begin{keyans*}[⟨key = val⟩] \item \item[⟨custom⟩] \item* \item*[⟨content⟩] \end{keyans*}`

The `keyans` is an “*enumerated list*” environment designed for “*multiple choice*” questions activated by the `save-ans` key. This environment can NOT be nested and must always be at the “*first level*” of the `enumext` environment, the commands `\item` and `\item[⟨custom⟩]` work in the usual.

```
\begin{enumext}[save-ans=test]
  \item <item content>
  \begin{keyans}[<key = val>]
    \item <item content>
    \item [<custom>] <item content>
    \item* <item content>
    \item* [<content>] <item content>
  \end{keyans}
\end{enumext}
```

The  $\langle keys \rangle$  set in the optional argument of the environment are the same (almost) as those of the `enumext` environment and have higher precedence than those set by `\setenumext[<keyans>]{<key = val>}`. If the optional argument is not passed or the  $\langle keys \rangle$  are not set by `\setenumext`, the default values will be the same as the second level of the `enumext` environment with the difference in the  $\langle label \rangle$  which will be set to `label=(\Alph*)`.

4.5.1 The `\item*` in `keyans`

```
\item* \item*
\item* [<content>]
```

The `\item*` and `\item* [<content>]` command store the current  $\langle label \rangle$  set by `label` key next to the  $\langle content \rangle$  (if it is present) in  $\langle store name \rangle$  set by `save-ans` key in the “first level” of the `enumext` environment. The starred version ‘`*`’ cannot be separated by spaces ‘`␣`’ from the command, i.e. `\item*` and the optional argument does “not support” verbatim content. By design it is assumed that the starred version ‘`*`’ will only appear “once” within the environment.

🟡 The behavior of `\item*` in `keyans` environment is NOT the same as in the `enumext` environment.

Example

```
\begin{enumext}[save-ans=test,columns=2,show-ans=true]
  \item Text containing a question.
  \begin{keyans}[nosep]
    \item Choice
    \item* Correct choice
    \item Choice
    \item Choice
  \end{keyans}


  \item Text containing a question and image.
  \begin{keyans}[nosep,mini-env={0.4\linewidth}]
    \item Choice
    \item Choice
    \item Choice
    \item Choice
    \item* [<note>] Correct choice
    \miniright
    \includegraphics[scale=0.25]{example-image-a}

    Some text
  \end{keyans}
\end{enumext}
```

1. Text containing a question.

(A) Choice  
\* (B) Correct choice  
(C) Choice  
(D) Choice
2. Text containing a question and image.

(A) Choice  
(B) Choice  
(C) Choice  
(D) Choice  
\* (E) [note] Correct choice



Some text

4.6 The environment `keyanspic`

```
keyanspic \begin{keyanspic}[<number above, number below>]\anspic{<drawing>}\anspic* [<content>]{<drawing>}
```

The `keyanspic` is a “fake enumerated list” environment that which uses the `\anspic` command instead of `\item`. It is activated by the `save-ans` key and has the same settings as the `keyans` environment. It is intended for placing “drawings” or “tabular” with an in-line or *above* and *below* layout. A representation of the output can be seen in the figure 6.

The optional argument determines the number drawings or tabular “above” and “below” within the environment. The vertical separation between “above” and “below” is controlled by the values set by `parsep` and `itemsep` keys passed to `keyans` environment. If the optional argument or the second part of it is omitted the drawings or tabular will be put on a single line.




Figure 6: Representation of the `keyanspic` environment with optional argument `[3,2]` in `enumext`.

4.6.1 The command `\anspic`

```
\anspic \anspic{<drawing or tabular>}
\anspic* [<content>] {<drawing or tabular>}
```


The `\anspic` command take three arguments, the *starred version* ‘`*`’ store the current `<label>` next to the `<content>` (if it is present) in `<store name>` set by `save-ans` key.

The *starred version* ‘`*`’ cannot be separated by spaces ‘`␣`’ from the command, i.e. `\anspic*` and the optional argument does “*not support*” verbatim content. By design it is assumed that the *starred version* ‘`*`’ will only appear “*once*” within the environment.

Example

```
\begin{enumext}[save-ans=test,show-ans,nosep]
  \item Question with images.
  \begin{keyanspic}[3,2]
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-b}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic{\includegraphics[scale=0.15]{example-image-a}}
    \anspic*[note]{\includegraphics[scale=0.15]{example-image-a}}
  \end{keyanspic}
\end{enumext}
```

1. Question with images.



4.7 Printing stored content

4.7.1 The command `\getkeyans`

```
\getkeyans \getkeyans{<store name : position>}
```

The command `\getkeyans` prints the “*only stored content*” in `<store name>` defined by `save-ans` key in the `<position>` returned by the `show-pos` key.

The “*content*” can only be accessed “*after*” it is stored, if the `<store name>` does not exist the command will return an error. The form taken by the argument `<store name : position>` is the same as that used to generate the internal “*label and ref*” system when `save-ref` key are active, so to refer to a stored “*content*”. For example `\getkeyans[test:4]` will return the “*stored content*” at position 4 of the environment in which the key `save-ans=test` was set.

4.7.2 The command `\printkeyans`

```
\printkeyans \printkeyans [<keys>] {<store name>}
```

The command `\printkeyans` prints “*all stored content*” in `{<store name>}` defined by `save-ans` key. The “*content*” can only be accessed “*after*” it is stored, if `<store name>` does not exist the command will return an error.

Internally it places the “*stored content*” inside the `enumext` environment with default values for `label` key are the same as those of the `enumext` environment along with the keys: `nosep`, `first=\small`, `font=\small` for all levels, except for the first one that adds the `columns=2` key.

The optional argument allows to handle the *keys* “on the first level” of the `enumext` environment encapsulated by the command. If need to pass options for nested levels use `\setenumext[<print , level>]{<store name>}`.

Example

```
\begin{enumext}[save-ans=sample,columns=2,show-pos=true,nosep,save-ref=true]
  \item Factor  $3x+3y+3z$ . \anskey{ $3(x+y+z)$ }
  \item True False

  \begin{enumext}[nosep]
    \item \LaTeXe\ is cool? \anskey{Very True!}
  \end{enumext}

  \item Related to Linux

  \begin{enumext}[nosep]
    \item You use linux? \anskey{Yes}
    \item Rate the following package and class
      \begin{enumext}[nosep]
        \item \texttt{xsim} \anskey{very good}
        \item \texttt{exsheets} \anskey{obsolete}
      \end{enumext}
    \end{enumext}
  \end{enumext}

The answer to \ref{sample:4} is \getkeyans{sample:4} and the answers to
all the worksheets are as follows:

\printkeyans{sample}
```

1. Factor  $3x + 3y + 3z$ .

[1]  $3(x + y + z)$
2. True False

(a) ~~TeX~~e is cool?

[2] Very True!
3. Related to Linux

(a) You use linux?
- [3] Yes

(b) Rate the following package and class

i. ~~xsim~~

[4] very good

ii. ~~exsheets~~

[5] obsolete

The answer to 3.(b).i is very good and the answers to all the worksheets are as follows:

1.  $3(x + y + z)$

2. (a) Very True!

3. (a) Yes

(b) i. very good

ii. obsolete
- \*

\*

\*

\*

\*


5 Full examples

Here I will leave as an example some adaptations questions taken from `TeX-SX`. The examples are attached to this documentation and can be extracted from your PDF viewer or from the command line by running:

```
$ pdfdetach -saveall enumext.pdf
```

and then you can use the excellent `arara`<sup>1</sup> tool to compile them.

Example 1

Adapted from the response given by Enrico Gregorio in [Squares for answer choice options and perfect alignment to mathematical answers](#) .

1. La velocità di  $1,00 \times 10^2$  m/s espressa in km/h è:

A 36 km/h.

B 360 km/h.

C 27,8 km/h.

D  $3,60 \times 10^8$  km/h.
- A  $1 \text{ \AA} = 1 \times 10^5$  fm.

B  $1 \text{ \AA} = 1 \times 10^{-5}$  fm.

C  $1 \text{ \AA} = 1 \times 10^{-15}$  fm.

D  $1 \text{ \AA} = 1 \times 10^3$  fm.
3. La velocità di  $1,00 \times 10^2$  m/s espressa in km/h è:

A 36 km/h.

B 360 km/h.

C 27,8 km/h.

D  $3,60 \times 10^8$  km/h.
2. In fisica nucleare si usa l’angstrom (simbolo:  $1 \text{ \AA} = 1 \times 10^{-10}$  m) e il fermi o femtometro ( $1 \text{ fm} = 1 \times 10^{-15}$  m). Qual è la relazione tra queste due unità di misura?

<sup>1</sup>The cool `TeX` automation tool: <https://www.ctan.org/pkg/arara>



4. In fisica nucleare si usa l'angstrom (simbolo:  $1 \text{ \AA} = 1 \times 10^{-10} \text{ m}$ ) e il fermi o femtometro ( $1 \text{ fm} = 1 \times 10^{-15} \text{ m}$ ). Qual è la relazione tra queste due unità di misura?
- A

B

C

D

$1 \text{ \AA} = 1 \times 10^5 \text{ fm.}$


$1 \text{ \AA} = 1 \times 10^{-5} \text{ fm.}$

$1 \text{ \AA} = 1 \times 10^{-15} \text{ fm.}$

$1 \text{ \AA} = 1 \times 10^3 \text{ fm.}$

1. B
2. A
3. B
4. A

Example 2

Adapted from the response given by Florent Rougon in [Multiple choice questions with proposed answers in random order — addition of automatic correction \(cross mark\)](#) .

1. La velocità di  $1,00 \times 10^2 \text{ m/s}$  espressa in km/h è:
- A

B

C

D

$36 \text{ km/h.}$

$360 \text{ km/h.}$

$27,8 \text{ km/h.}$

$3,60 \times 10^8 \text{ km/h.}$
2. In fisica nucleare si usa l'angstrom (simbolo:  $1 \text{ \AA} = 1 \times 10^{-10} \text{ m}$ ) e il fermi o femtometro ( $1 \text{ fm} = 1 \times 10^{-15} \text{ m}$ ). Qual è la relazione tra queste due unità di misura?
- A

B

C

D

$1 \text{ \AA} = 1 \times 10^5 \text{ fm.}$

$1 \text{ \AA} = 1 \times 10^{-5} \text{ fm.}$

$1 \text{ \AA} = 1 \times 10^{-15} \text{ fm.}$

$1 \text{ \AA} = 1 \times 10^3 \text{ fm.}$
3. La velocità di  $1,00 \times 10^2 \text{ m/s}$  espressa in km/h è:
- A

B

C

D

$36 \text{ km/h.}$

$360 \text{ km/h.}$

$27,8 \text{ km/h.}$

$3,60 \times 10^8 \text{ km/h.}$
4. In fisica nucleare si usa l'angstrom (simbolo:  $1 \text{ \AA} = 1 \times 10^{-10} \text{ m}$ ) e il fermi o femtometro ( $1 \text{ fm} = 1 \times 10^{-15} \text{ m}$ ). Qual è la relazione tra queste due unità di misura?
- A

B

C

D

$1 \text{ \AA} = 1 \times 10^5 \text{ fm.}$

$1 \text{ \AA} = 1 \times 10^{-5} \text{ fm.}$

$1 \text{ \AA} = 1 \times 10^{-15} \text{ fm.}$

$1 \text{ \AA} = 1 \times 10^3 \text{ fm.}$

1. B
2. A
3. B
4. A
- \*

\*

\*

\*

Example 3

A “simple multiple choice” test 📄.

1. First type of questions
- A

 value

B

 correct

C

 value

D

 value
2. Second type of questions
- I.  $2\alpha + 2\delta = 90^\circ$

II.  $\alpha = \delta$

III.  $\angle EDF = 45^\circ$

A

 I only

B

 II only

C

 I and II only

D

 I and III only

E

 I, II, and III
3. Third type of questions
- (1)  $2\alpha + 2\delta = 90^\circ$

(2)  $\angle EDF = 45^\circ$

A

 value

B

 value

C

 value

D

 value

E

 value
4. Question with image and label below:



A




D



B



C



E



5. Question with image on left side:
- A

 value
- B

 value
- C

 value
- D

 correct
- E

 value

- Test keys
1. B,  $x = 5$

2. D

3. C, some note

4. E, A duck

5. D, other note

Example 4

A “simple worksheet” using ducks :) 📄.

- 1

 Factor  $x^2 - 2x + 1$
- 2

 Factor  $3x + 3y + 3z$
- The following questions need to be cuaqtified :)
- 3

 True False
- (a)

 $\alpha > \delta$
- (b)

~~ETX~~ze is cool?
- 4

 Related to Linux
- (a)

 You use linux?
- (b)

 Usually uses the package manager?
- (c)

 Rate the following package and class
- i.

 xsim-exam
- ii.

 xsim
- iii.

 exsheets

The answer to 1 is  $(x - 1)^2$  and the answer to 3.(a) is False.

1.

 $(x - 1)^2$
2.

 $3(x + y + z)$
3.

 (a) False
- (b)

 Very True!
4.

 (a) Yes
- (b)

 Yes, dnf
- (c)

 i. doesn't exist for now :(
- ii.

 very good
- iii.

 obsolete

Example 5

Adapted from the response given by Stephen in SAT like question format .

1	Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action.	3	Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action.
2	Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action.	4	Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action.

1. A)                                      2. C)                                      3. B)                                      4. D)

6 The way of non-enumerated lists

It is possible to use (or abuse) the enumext environment to mimic non-enumerated list environments such as itemize and description, clearly the <keys> to “store answers”, the keyans and keyanspic environments lose their sense and it is not the focus of the main of this package, but, why not to do it?. Here I leave as an example other uses of the enumext environment that can be helpful for specific purposes. The “trick” to generate these fake environments is set label={} or label={<some>} and play with the list-indent, list-offset, font and wrap-label keys.

Fake itemize environment

Here we set the label key using the default settings in L<sup>A</sup>T<sub>E</sub>X for the four levels \textbullet, \textendash, \textasteriskcentered and \textperiodcentered together with the nosepe key to reduce the vertical spaces in the left side example and set the label key in mathematical mode for the right side as \ast, \diamond, \circ and \star for the four levels together with the nosepe key

- First level item
    - Second level item
      - \* Third level item
        - Fourth level item
  - First level item
- \* First level item
    - ◇ Second level item
      - Third level item
        - ★ Fourth level item
  - \* First level item

Fake description environment

Here we set label={} and list-indent=2.5em, font=\bfseries.

- Something** A short one-line description.  
This is an entry without a label.

**Something** A short one-line description text.

**Something long** A much longer description text may take more than one line or more than one paragraph.  
Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

If we add list-indent=0pt you get widest style:

- Something** A short one-line description.  
This is an entry without a label.

**Something** A short one-line description text.

**Something long** A much *longer* description text may take more than one line or more than one paragraph. Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

- The small space at the beginning of the “*unlabeled entry*” corresponds to `\labelsep` and can be removed using `\hspace{-\labelsep}` at the beginning of the line.

Description indented by label

Here we set `label={}` and we will give a convenient value to `labelsep` and `labelwidth`, for example we can take as reference our *longest label* and pass it as value using:

```
\newlength{\descitemwd}
\settowidth{\descitemwd}{\textbf{Something long}}
```

and then use `labelsep=4pt, labelwidth=\descitemwd, font=\bfseries`.

**SomeThing** A short one-line description.  
This is an entry *without* a label.

**Something** A short one-line description.

**Something long** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

The environment can be translated so that the *(labels)* are on the left margin calculating the value passed to the `list-offset` key, in this case it will be equal to the sum of the values set by the `labelwidth` and `labelsep` keys finally resulting as `list-offset={-\descitemwd - 4pt}`.

**SomeThing** A short one-line description.  
This is an entry *without* a label.

**Something** A short one-line description.

**Something long** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

If we add `align=right` it will look like this:

**SomeThing** A short one-line description.  
This is an entry *without* a label.

**Something** A short one-line description.

**Something long** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

- At this point we have used `list-offset={-\descitemwd - 4pt}` instead of `list-offset={-\labelwidth - \labelsep}`, this is because the parameters `\labelwidth` and `\labelsep` take the default values, as if we had not set `label`.

Description with multi-line labels

The `label` key does not accept *multiline material*, this is where the `wrap-label*` key comes into play. Unlike the `enumitem` package, the `align` key only supports three options, so what we will do is create a command in the style `\parleft` of `enumitem` that allows us to place *multiline labels* using `\parbox`.

```
\NewDocumentCommand \itembx { s +m }
{%
  \IfBooleanTF{#1}
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedright{#2}}}}%
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{#2}}}}%
}
```

Now we just need to set `wrap-label*={\itembx{#1}}`.

**SomeThing** A short one-line description.  
This is an entry *without* a label.

**Something** A short one-line description.

**Something** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

**long** vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.  
Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

**SoMeThInG** A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

**LoNg** vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

Final notes

The original implementation (if you can call it that) of the ideas that led to the creation of `enumext` were some macros using the `enumerate[4]` package for personal use created in early 2003, the code was quite questionable, but functional for these simple requirements.

With the great answers given by Christian Hupfer in [Create a fake label ref using list](#) and the answer given by David Carlisle in [Change the use of label ref by data save in an array \(list\)](#) I managed to create a more solid code than the original version, now using the `l3prop`[10] and `l3seq`[10] modules together with the `hyperref`[7] and `enumitem`[5] packages, which did the job, but with some limitations.

As time went by I took these limitations as a personal challenge which I called “*reinventing the wheel*”, since there were packages and classes that did more or less what I was looking for, but did not fit my simple requirements. This “*reinventing the wheel*” finally ended up becoming `enumext`.

### Why list environments?

The answer is simple, first I love the beauty of its syntax and many of what I had already written used the `enumerate` environment or lists created using the `enumitem` package. In my mind I thought: how complicated could it be to write a package that looked like `enumitem`? It seemed simple enough, of course I didn’t have in mind the mess I was getting into working with `list` environments, `minipage` and adding support for the `multicol` and `hyperref` packages.

Of course, seeing the final result of the experiment “*reinventing the wheel*” I am quite satisfied.

### Why not random questions and other utilities

The “*random*” type questions I love and hate them at the same time, although they simplify a lot the work when creating a multiple choice test, but you lose the beauty of typesetting a document with  $\text{\LaTeX}$ , that is to say the output does not always look as nice as it should, even if they are only alternatives these must follow a certain order when presented either numerical or presentation, that said handling that using *nested lists* is quite complicated so I do not classify to be implemented.

## 7 References

- [1] HIRSCHHORN, PHILIP. “Using the exam document class”. Available from CTAN, <https://www.ctan.org/pkg/exam>, 2023.
- [2] NIEDERBERGER, CLEMENS. “xsim – eXercise Sheets IMproved”. Available from CTAN, <https://www.ctan.org/pkg/xsim>, 2023.
- [3] MITTELBACH, FRANK. “An environment for multicolumn output”. Available from CTAN, <https://www.ctan.org/pkg/multicol>, 2024.
- [4] The  $\text{\LaTeX}$  Project. “enumerate – Enumerate with redefinable labels”. Available from CTAN, <https://www.ctan.org/pkg/enumerate>, 2024.
- [5] BEZOS, JAVIER. “Customizing lists with the enumitem package”. Available from CTAN, <https://www.ctan.org/pkg/enumitem>, 2019.
- [6] BERRY, KARL. “ $\text{\LaTeX}$  2<sub>ε</sub>: An Unofficial Reference Manual”. Available from CTAN, <https://ctan.org/pkg/latex2e-help-texinfo>, 2024.
- [7] The  $\text{\LaTeX}$  Project. “Extensive support for hypertext in  $\text{\LaTeX}$ ”. Available from CTAN, <https://www.ctan.org/pkg/hyperref>, 2024.
- [8] BURNOL, JEAN-FRANÇOIS. “The footnotehyper package”. Available from CTAN, <https://www.ctan.org/pkg/footnotehyper>, 2021.
- [9] The  $\text{\LaTeX}$  Project. “The expl3 package”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2024.
- [10] The  $\text{\LaTeX}$  Project. “The  $\text{\LaTeX}$ 3 Interfaces”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2024.
- [11] The  $\text{\LaTeX}$  Project. “The xparse package”. Available from CTAN, <https://www.ctan.org/pkg/xparse>, 2024.
- [12] GUNDLACH, PATRICK. “The lua-visual-debug package”. Available from CTAN, <https://www.ctan.org/pkg/lua-visual-debug>, 2023.
- [13] LEMVIG, MOGENS. “The shortlst package”. Available from CTAN, <https://www.ctan.org/pkg/shortlst>, 1998.
- [14] NIEDERBERGER, CLEMENS. “tasks – Horizontally columned lists”. Available from CTAN, <https://www.ctan.org/pkg/tasks>, 2022.

## 8 Change history

**v1.0** 2024-05-12 – First public release.

9 Index of Documentation

The italic numbers denote the pages where the corresponding entry is described.

C

Document class:

article . . . . . 2

book . . . . . 2

exam . . . . . 3

letter . . . . . 2

report . . . . . 2

\columnbreak . . . . . 5

\columnsep . . . . . 9

Commands provide by enumext:

\anskey . . . . . 4, 10, 11

\anspic\* . . . . . 4, 10–13

\anspic . . . . . 10, 12, 13

\getkeyans . . . . . 4, 11, 13

\item\* . . . . . 4–7, 10–12

\item . . . . . 6, 7, 9–11

\miniright . . . . . 4, 5, 10

\printkeyans . . . . . 4, 6, 11, 13

\setenumext . . . . . 4, 6, 7, 10, 12, 14

Counters defined by enumext:

enumXiii . . . . . 4

enumXii . . . . . 4

enumXiv . . . . . 4

enumXi . . . . . 4

enumXviii . . . . . 4

enumXvii . . . . . 4

enumXvi . . . . . 4

enumXv . . . . . 4

E

Environments provide by enumext:

enumext\* . . . . . 4, 5, 10

enumext . . . . . 4–6, 9–14, 17

keyans\* . . . . . 4, 5, 10

keyanspic . . . . . 4, 7, 10–13, 17

keyans . . . . . 4–12, 17

Environments:

enumerate . . . . . 1, 3, 4, 6, 19

list . . . . . 4, 9, 19

minipage . . . . . 3–5, 9, 10, 19

multicols . . . . . 3, 5, 9

I

\item . . . . . 4, 5

\itemsep . . . . . 8

K

Keys for environments provide by enumext:

above\* . . . . . 8

above . . . . . 8

after . . . . . 9, 10

align . . . . . 7, 18

before\* . . . . . 9

before . . . . . 9

below\* . . . . . 8

below . . . . . 8

check-ans . . . . . 11

columns-sep . . . . . 5, 9

columns . . . . . 5, 8, 9

first . . . . . 9

font . . . . . 7

item-pos\* . . . . . 6

item-sym\* . . . . . 6

itemindent . . . . . 8

itemsep . . . . . 8, 12

labelsep . . . . . 4, 6–10, 18

labelwidth . . . . . 4, 6, 7, 9, 10, 18

label . . . . . 7, 9, 10, 12, 13, 17, 18

list-indent . . . . . 4, 8, 9

list-offset . . . . . 4, 8, 18

listparindent . . . . . 8

mark-ans . . . . . 10

mark-pos . . . . . 10

mark-ref . . . . . 11

mini-env . . . . . 5, 8, 9

mini-sep . . . . . 5, 9

miniright\* . . . . . 10

miniright . . . . . 10

no-store . . . . . 11

noitemsep . . . . . 8

nosep . . . . . 8, 17

parsep . . . . . 8, 12

partopsep . . . . . 8

ref . . . . . 5, 7

resume . . . . . 9

rightmargin . . . . . 8

save-ans . . . . . 5, 9–13

save-ref . . . . . 5, 7, 11, 13

save-sep . . . . . 10

show-ans . . . . . 10, 11

show-length . . . . . 7

show-pos . . . . . 10, 11, 13

start . . . . . 9

topsep . . . . . 8

widest . . . . . 7

wrap-ans . . . . . 10

wrap-label\* . . . . . 7, 18

wrap-label . . . . . 7

wrap-opt . . . . . 10

L

\label . . . . . 5

Labels provide by enumext:

\Alph\* . . . . . 7, 12

\Roman\* . . . . . 7

\alph\* . . . . . 7

\arabic\* . . . . . 7

\roman\* . . . . . 7

\labelsep . . . . . 4, 7

\labelwidth . . . . . 4, 7

\linewidth . . . . . 9

\listparindent . . . . . 8

P

Packages:

enumerate . . . . . 18

enumext . . . . . 1–4, 13, 18, 19

enumitem . . . . . 4, 5, 9, 18, 19

footnotehyper . . . . . 5

hyperref . . . . . 5, 11, 19

l3prop . . . . . 1, 19

l3seq . . . . . 1, 19

©2024 by Pablo González L

20 / 113



multicol .....	1, 2, 5, 19	\ref .....	5
xsim .....	3	\rightmargin .....	8
\parsep .....	8		
\partopsep .....	8		
<b>R</b>		<b>T</b>	
\raggedcolumns .....	5	\topsep .....	8

## 10 Implementation

The most recent publicly released version of `enumext` is available at CTAN: <https://www.ctan.org/pkg/enumext>. While general feedback via email is welcomed, specific bugs or feature requests should be reported through the issue tracker: <https://github.com/pablgonz/enumext/issues>.

- The documentation presented here is far from professional, it contains a lot of obvious information that to the eye of a T<sub>E</sub>Xpert are superfluous, but, after so many years developing this project is the only way to remember what does what.

### 10.1 General conventions

Variables containing `i`, `ii`, `iii` and `iv` are associated by level with the `enumext` environment, variables containing `v` are associated with the `keyans` environment, variables containing `vi` are associated with the `keyanspic` environment, variables containing `vii` are associated with the `enumext*` environment and variables containing `viii` are associated with the `keyans*` environment.

To simplify writing and documentation some variables and functions that are common to the different levels of the environments are described using a capital “X”.

The temporary function `\__enumext_tmp:n` is used in different parts of the package code for variable creation or execution of other functions that are grouped into this one.

All variables and functions defined in this package are private and are NOT intended to work or be used by another package or module.

### 10.2 Initial set up

Start the DocStrip guards.

```
1 (*package)
```

Identify the internal prefix (L<sup>A</sup>T<sub>E</sub>X3 DocStrip convention) for l3doc class.

```
2 (@@=enumext)
```

### 10.3 Declaration of the package

First we will make sure we have a minimum (super updated) version of L<sup>A</sup>T<sub>E</sub>X to work correctly.

```
3 \NeedsTeXFormat{LaTeX2e}[2023-11-01]
```

Now declare the `enumext` package.

```
4 \ProvidesExplPackage
5   {enumext}
6   {2024-05-12}
7   {1.0}
8   {Enumerate exercise sheets}
```

Finally check if the `multicol` package is loaded, if not we load it.

```
9 \hook_gput_code:nnn {begindocument} {enumext}
10 {
11   \IfPackageLoadedTF { multicol }
12   {
13     \msg_info:nnn { enumext } { package-load } { multicol }
14   }
15   {
16     \msg_info:nnn { enumext } { package-not-load } { multicol }
17     \RequirePackage{multicol}[2023-03-30]
18   }
19 }
```

### 10.4 Definition of variables

Variables that do not appear in this section are created by means of `\keys_define:nn` or some function described below.

Integer variables will control the nesting levels of the environments and boolean variables will be used to determine if they are present (nested) in each other. The boolean variables `\g__enumext_starred_bool` and `\g__enumext_standar_bool` will be set to “true” when the `enumext` and `enumext*` environments are not nested with each other.

```
20 \int_new:N \__enumext_level_int
21 \int_new:N \__enumext_level_h_int
22 \int_new:N \__enumext_keyans_level_int
23 \int_new:N \__enumext_keyans_level_h_int
24 \int_new:N \__enumext_keyans_pic_level_int
25 \bool_new:N \__enumext_starred_bool
26 \bool_new:N \g__enumext_starred_bool
```

```

27 \bool_new:N \l__enumext_standar_bool
28 \bool_new:N \g__enumext_standar_bool
29 \bool_new:N \l__enumext_keyans_env_bool

```

(End of definition for `\l__enumext_level_int` and others.)

```

\l__enumext_counter_i_tl
\l__enumext_counter_ii_tl
\l__enumext_counter_iii_tl
\l__enumext_counter_iv_tl
\l__enumext_counter_v_tl
\l__enumext_counter_vi_tl
\l__enumext_counter_vii_tl
\l__enumext_counter_viii_tl

```

Variables to store the “name of the counters” `enumXi`, `enumXii`, `enumXiii` and `enumXiv` for `enumext` environment, `enumXv` for `keyans` environment and `enumXvi` for the `keyanspic` environment.

The counters `enumXvii` and `enumXviii` are used by `enumext*` and `keyans*` environments.

The initial values of these variables are set by the function `\__enumext_define_counters:Nn` and then modified by the function `\__enumext_label_style:Nnn` used by `label` key (§10.8).

```

30 \cs_set_protected:Npn \__enumext_tmp:n #1
31 {
32   \tl_new:c { l__enumext_counter_#1_tl }
33 }
34 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_counter_i_tl` and others.)

```

\l__enumext_resume_bool
\g__enumext_resume_int
\l__enumext_resume_vii_bool
\g__enumext_resume_vii_int
\g__enumext_item_symbol_tl

```

The boolean variable `\l__enumext_resume_bool` is used by `resume` key, the value from which the environment’s will start is stored in the integer variable `\g__enumext_resume_int` (§10.21). The global token list `\g__enumext_item_symbol_tl` is used by `item-sym*` key (§10.26).

```

35 \bool_new:N \l__enumext_resume_bool
36 \int_new:N \g__enumext_resume_int
37 \bool_new:N \l__enumext_resume_vii_bool
38 \int_new:N \g__enumext_resume_vii_int
39 \tl_new:N \g__enumext_item_symbol_tl

```

(End of definition for `\l__enumext_resume_bool` and others.)

```

\l__enumext_current_widest_dim
\g__enumext_counter_styles_tl
\g__enumext_widest_label_tl
\l__enumext_label_width_by_box

```

The variable `\l__enumext_current_widest_dim` stores the current label width, the variable `\g__enumext_counter_styles_tl` stores the default *⟨label style⟩* and the variable `\g__enumext_widest_label_tl` the label width. These variables are used by `widest` (§10.12) and `label` (§10.10) keys.

```

40 \dim_new:N \l__enumext_current_widest_dim
41 \tl_new:N \g__enumext_counter_styles_tl
42 \tl_new:N \g__enumext_widest_label_tl
43 \box_new:N \l__enumext_label_width_by_box

```

(End of definition for `\l__enumext_current_widest_dim` and others.)

```

\l__enumext_leftmargin_tmp_X_bool
\l__enumext_leftmargin_tmp_X_dim
\l__enumext_leftmargin_X_dim
\l__enumext_itemindent_X_dim

```

The boolean variable `\l__enumext_leftmargin_tmp_X_bool` and the dimensional variable `\l__enumext_leftmargin_tmp_X_dim` are used by the `list-indent` key (§10.14).

The variables `\l__enumext_leftmargin_X_dim` and `\l__enumext_itemindent_X_dim` are used (and set) by the function `\__enumext_calc_hspace:NNNNNNNNNN` (§10.30) which determines the internal values for `\leftmargin` and `\itemindent`.

```

44 \cs_set_protected:Npn \__enumext_tmp:n #1
45 {
46   \bool_new:c { l__enumext_leftmargin_tmp_#1_bool }
47   \dim_new:c { l__enumext_leftmargin_tmp_#1_dim }
48   \dim_new:c { l__enumext_leftmargin_#1_dim }
49   \dim_new:c { l__enumext_itemindent_#1_dim }
50 }
51 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_leftmargin_tmp_X_bool` and others.)

```

\l__enumext_multicols_above_X_skip
\l__enumext_multicols_below_X_skip

```

Internal variables used by `columns` key §10.18).

```

52 \cs_set_protected:Npn \__enumext_tmp:n #1
53 {
54   \skip_new:c { l__enumext_multicols_above_#1_skip }
55   \skip_new:c { l__enumext_multicols_below_#1_skip }
56 }
57 \clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_multicols_above_X_skip` and `\l__enumext_multicols_below_X_skip`.)

```

\g__enumext_minipage_stat_int
\l__enumext_minipage_left_skip
\l__enumext_minipage_right_skip
\l__enumext_minipage_after_skip
\g__enumext_minipage_right_skip
\g__enumext_minipage_after_skip
\l__enumext_minipage_left_X_dim
\l__enumext_minipage_active_X_bool

```

Internal variables used by `\miniright` command (§10.19.4) and the keys `miniright`, `miniright*`, `mini-env` and `mini-sep` (§10.17, §10.19).

```

58 \int_new:N \g__enumext_minipage_stat_int
59 \skip_new:N \l__enumext_minipage_left_skip
60 \skip_new:N \l__enumext_minipage_right_skip
61 \skip_new:N \l__enumext_minipage_after_skip
62 \skip_new:N \g__enumext_minipage_right_skip
63 \skip_new:N \g__enumext_minipage_after_skip
64 \cs_set_protected:Npn \__enumext_tmp:n #1
65 {
66   \dim_new:c { \l__enumext_minipage_left_#1_dim }
67   \bool_new:c { \l__enumext_minipage_active_#1_bool }
68 }
69 \clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\g__enumext_minipage_stat_int` and others.)

```

\l__enumext_wrap_label_X_bool
\l__enumext_wrap_label_opt_X_bool
\l__enumext_start_X_int
\l__enumext_fake_item_indent_X_tl
\l__enumext_label_fill_left_X_tl
\l__enumext_label_fill_right_X_tl
\l__enumext_vspace_a_star_X_bool
\l__enumext_vspace_b_star_X_bool

```

The integer variable `\l__enumext_start_X_int` are used by the `start` key (§10.12), the token list `\l__enumext_fake_item_indent_X_tl` is used by `itemindent` key, the variables `\l__enumext_label_fill_left_X_tl` and `\l__enumext_label_fill_right_X_tl` are used by the `align` key (§10.10). The boolean vars `\l__enumext_vspace_a_star_X_bool`, `\l__enumext_vspace_b_star_X_bool` are used by `above`, `above*`, `below` and `below*` keys

```

70 \cs_set_protected:Npn \__enumext_tmp:n #1
71 {
72   \bool_new:c { \l__enumext_wrap_label_#1_bool }
73   \bool_new:c { \l__enumext_wrap_label_opt_#1_bool }
74   \int_new:c { \l__enumext_start_#1_int }
75   \tl_new:c { \l__enumext_fake_item_indent_#1_tl }
76   \tl_new:c { \l__enumext_label_fill_left_#1_tl }
77   \tl_new:c { \l__enumext_label_fill_right_#1_tl }
78   \bool_new:c { \l__enumext_vspace_a_star_#1_bool }
79   \bool_new:c { \l__enumext_vspace_b_star_#1_bool }
80 }
81 \clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_wrap_label_X_bool` and others.)

```

\l__enumext_store_active_bool
\l__enumext_store_name_tl
\g__enumext_store_name_tl
\l__enumext_store_anskey_arg_tl
\l__enumext_store_columns_join_int
\l__enumext_store_keyans_label_tl
\l__enumext_store_keyans_item_opt_tl
\l__enumext_keyans_item_opt_tl
\l__enumext_keyans_tmpa_tl
\l__enumext_keyans_tmpb_tl
\l__enumext_keyans_tmpa_dim

```

The boolean variable `\l__enumext_store_active_bool` setting by `save-ans` key (§10.21) activates all the mechanism related to `\anskey`, `keyans`, `keyans*` and `keyanspic`.

The variable `\l__enumext_store_name_tl` sets the name for the storage in `⟨sequence⟩` and `⟨prop list⟩`, the variable `\g__enumext_store_name_tl` is just a copy of the storage name used by the `check-ans` key (§10.21).

The variable `\l__enumext_store_anskey_arg_tl` stores the contents of `\anskey` (§10.24) and the variable `\l__enumext_store_keyans_label_tl` stores the contents of `\item*` (§10.28.2) for the `keyans` and `keyans*` environments and the contents of `\anspic*` (§10.34.1) for the `keyanspic` environment.

The variable `\l__enumext_keyans_tmpa_tl` is a temporary variable used by `keyans` and `keyanspic` at various points.

```

82 \bool_new:N \l__enumext_store_active_bool
83 \tl_new:N \l__enumext_store_name_tl
84 \tl_new:N \g__enumext_store_name_tl
85 \tl_new:N \l__enumext_store_anskey_arg_tl
86 \int_new:N \l__enumext_store_columns_join_int
87 \tl_new:N \l__enumext_store_keyans_label_tl
88 \tl_new:N \l__enumext_store_keyans_item_opt_tl
89 \tl_new:N \l__enumext_keyans_item_opt_tl
90 \tl_new:N \l__enumext_keyans_tmpa_tl
91 \tl_new:N \l__enumext_keyans_tmpb_tl
92 \dim_new:N \l__enumext_keyans_tmpa_dim

```

(End of definition for `\l__enumext_store_active_bool` and others.)

```

\l__enumext_setkey_tmpa_tl
\l__enumext_setkey_tmpb_tl
\l__enumext_setkey_tmpa_int
\l__enumext_setkey_tmpa_seq
\l__enumext_setkey_tmpb_seq

```

Internal variables used by the command `\setenumext` (§10.39).

```

93 \tl_new:N \l__enumext_setkey_tmpa_tl
94 \tl_new:N \l__enumext_setkey_tmpb_tl
95 \int_new:N \l__enumext_setkey_tmpa_int
96 \seq_new:N \l__enumext_setkey_tmpa_seq
97 \seq_new:N \l__enumext_setkey_tmpb_seq

```

(End of definition for `\l__enumext_setkey_tmpa_tl` and others.)

```
\l__enumext_store_opt_X_tl
\l__enumext_print_keyans_X_tl
\l__enumext_store_columns_X_bool
\l__enumext_store_columns_X_int
\l__enumext_store_columns_sep_X_bool
\l__enumext_store_columns_sep_X_dim
\l__enumext_store_upper_level_X_bool
```

Internal variables used by [ $\langle key = val \rangle$ ] in `enumext` and `enumext*` environment, the command `\printkeyans` (§10.38) and the keys `columns*` and `columns-sep*`.

```
98 \cs_set_protected:Npn \l__enumext_tmp:n #1
99 {
100   \tl_new:c { \l__enumext_store_opt_#1_tl }
101   \tl_new:c { \l__enumext_print_keyans_#1_tl }
102   \bool_new:c { \l__enumext_store_columns_#1_bool }
103   \int_new:c { \l__enumext_store_columns_#1_int }
104   \bool_new:c { \l__enumext_store_columns_sep_#1_bool }
105   \dim_new:c { \l__enumext_store_columns_sep_#1_dim }
106   \bool_new:c { \l__enumext_store_upper_level_#1_bool }
107 }
108 \clist_map_inline:nn { i, ii, iii, iv, vii } { \l__enumext_tmp:n {#1} }
```

(End of definition for `\l__enumext_store_opt_X_tl` and others.)

```
\l__enumext_show_answer_bool
\l__enumext_show_position_bool
\l__enumext_mark_ref_sym_tl
\l__enumext_mark_answer_sym_tl
\l__enumext_mark_position_str
```

Internal variables for “storage system” mechanism used by `\anskey` (§10.24), `keyans` and `keyanspic` environments. These variables are used by `show-ans`, `show-pos`, `mark-ans`, `save-key` and `mark-ref` keys (§10.23).

```
109 \bool_new:N \l__enumext_show_answer_bool
110 \bool_new:N \l__enumext_show_position_bool
111 \tl_new:N \l__enumext_mark_ref_sym_tl
112 \tl_new:N \l__enumext_mark_answer_sym_tl
113 \str_new:N \l__enumext_mark_position_str
```

(End of definition for `\l__enumext_show_answer_bool` and others.)

```
\l__enumext_keyans_pic_body_seq
\l__enumext_keyans_pic_width_dim
\l__enumext_keyans_pic_above_int
\l__enumext_keyans_pic_below_int
\l__enumext_keyans_pic_above_skip
```

Internal variables used by `keyanspic` environment (§10.34.2).

```
114 \seq_new:N \l__enumext_keyans_pic_body_seq
115 \dim_new:N \l__enumext_keyans_pic_width_dim
116 \int_new:N \l__enumext_keyans_pic_above_int
117 \int_new:N \l__enumext_keyans_pic_below_int
118 \skip_new:N \l__enumext_keyans_pic_above_skip
```

(End of definition for `\l__enumext_keyans_pic_body_seq` and others.)

```
\l__enumext_store_ans_bool
\l__enumext_check_ans_bool
\g__enumext_check_ans_show_bool
\g__enumext_check_ans_show_h_bool
\g__enumext_check_ans_item_tl
\g__enumext_count_item_anskey_int
\g__enumext_count_item_number_int
```

Internal variables used by “check answer” mechanism (§10.22) controlled by the `check-ans` and `no-store` keys.

```
119 \bool_new:N \l__enumext_store_ans_bool
120 \bool_new:N \l__enumext_check_ans_bool
121 \bool_new:N \g__enumext_check_ans_show_bool
122 \bool_new:N \g__enumext_check_ans_show_h_bool
123 \tl_new:N \g__enumext_check_ans_item_tl
124 \int_new:N \g__enumext_count_item_anskey_int
125 \int_new:N \g__enumext_count_item_number_int
126 \int_new:N \g__enumext_standar_star_env_int
127 \int_new:N \g__enumext_starred_star_env_int
128 \int_new:N \g__enumext_starred_keyans_star_env_int
129 \int_new:N \g__enumext_standar_keyans_star_env_int
130 \int_new:N \g__enumext_standar_keyans_pic_star_env_int
```

(End of definition for `\l__enumext_store_ans_bool` and others.)

```
\l__enumext_hyperref_bool
\l__enumext_footnotes_key_bool
```

The boolean variable `\l__enumext_hyperref_bool` will determine if the `hyperref` package is present or load in memory (§10.7). The boolean variable `\l__enumext_footnotes_key_bool` determine if `hyperref` is load with `key hyperfootnotes=true`.

```
131 \bool_new:N \l__enumext_hyperref_bool
132 \bool_new:N \l__enumext_footnotes_key_bool
```

(End of definition for `\l__enumext_hyperref_bool` and `\l__enumext_footnotes_key_bool`.)

```
\l__enumext_newlabel_arg_one_tl
\l__enumext_newlabel_arg_two_tl
\l__enumext_store_write_aux_file_tl
\l__enumext_label_copy_X_tl
```

Internal variables are used when executing the `save-ref` key. The variables `\l__enumext_label_copy_X_tl` correspond to temporary copies of the labels defined by level on which operations will be performed.

The variables `\l__enumext_newlabel_arg_one_tl` and `\l__enumext_newlabel_arg_two_tl` will be used to form the arguments passed to the function `\__enumext_newlabel:nn` and the variable `\l__enumext_store_write_aux_file_tl` will be in charge of executing the writing code in the `.aux` file.

```
133 \tl_new:N \l__enumext_newlabel_arg_one_tl
134 \tl_new:N \l__enumext_newlabel_arg_two_tl
```

```

135 \tl_new:N \l__enumext_store_write_aux_file_tl
136 \cs_set_protected:Npn \__enumext_tmp:n #1
137 {
138   \tl_new:c { l__enumext_label_copy_#1_tl }
139 }
140 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_newlabel_arg_one_tl` and others.)

`\g__enumext_footnote_int`

Internal variables used for redefinition of `\footnote`.

`\g__enumext_footnote_arg_seq`  
`\g__enumext_footnote_int_seq`

```

141 \int_new:N \g__enumext_footnote_int
142 \seq_new:N \g__enumext_footnote_arg_seq
143 \seq_new:N \g__enumext_footnote_int_seq

```

(End of definition for `\g__enumext_footnote_int`, `\g__enumext_footnote_arg_seq`, and `\g__enumext_footnote_int_seq`.)

`\c__enumext_counter_style_tl`  
`\l__enumext_ref_key_arg_tl`  
`\l__enumext_ref_aux_tl`  
`\l__enumext_the_counter_X_tl`  
`\l__enumext_counter_style_for_ref_X_tl`

Internal variables used by `ref` key (§10.17, §10.18).

```

144 \tl_const:Nn \c__enumext_counter_style_tl
145 { { arabic } { roman } { Roman } { alph } { Alph } }
146 \tl_new:N \l__enumext_ref_key_arg_tl
147 \tl_new:N \l__enumext_ref_aux_tl
148 \cs_set_protected:Npn \__enumext_tmp:n #1
149 {
150   \tl_new:c { l__enumext_counter_style_for_ref_#1_tl }
151   \tl_new:c { l__enumext_the_counter_#1_tl }
152   \tl_set:ce { l__enumext_the_counter_#1_tl } { \exp_not:c { theenumX#1 } }
153 }
154 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\c__enumext_counter_style_tl` and others.)

`\l__enumext_item_starred_X_bool`  
`\l__enumext_item_column_pos_X_int`  
`\g__enumext_item_count_all_X_int`  
`\l__enumext_joined_item_X_int`  
`\l__enumext_joined_item_aux_X_int`  
`\l__enumext_tmpa_X_int`  
`\l__enumext_item_text_X_box`  
`\l__enumext_joined_width_X_dim`  
`\l__enumext_item_width_X_dim`  
`\g__enumext_item_symbol_aux_X_tl`  
`\l__enumext_align_label_X_str`  
`\g__enumext_minipage_active_X_bool`  
`\g__enumext_miniright_code_X_tl`  
`\g__enumext_minipage_center_X_bool`  
`\g__enumext_minipage_right_X_dim`  
`\g__enumext_minipage_right_X_skip`

Internal variables used by `enumext*` and `keyans*` environments.

```

155 \cs_set_protected:Npn \__enumext_tmp:n #1
156 {
157   \bool_new:c { l__enumext_item_starred_#1_bool }
158   \int_new:c { l__enumext_item_column_pos_#1_int }
159   \int_new:c { g__enumext_item_count_all_#1_int }
160   \int_new:c { l__enumext_joined_item_#1_int }
161   \int_new:c { l__enumext_joined_item_aux_#1_int }
162   \int_new:c { l__enumext_tmpa_#1_int }
163   \box_new:c { l__enumext_item_text_#1_box }
164   \dim_new:c { l__enumext_joined_width_#1_dim }
165   \dim_new:c { l__enumext_item_width_#1_dim }
166   \tl_new:c { g__enumext_item_symbol_aux_#1_tl }
167   \str_new:c { l__enumext_align_label_#1_str }
168   \bool_new:c { g__enumext_minipage_active_#1_bool }
169   \tl_new:c { g__enumext_miniright_code_#1_tl }
170   \bool_new:c { g__enumext_minipage_center_#1_bool }
171   \dim_new:c { g__enumext_minipage_right_#1_dim }
172   \skip_new:c { g__enumext_minipage_right_#1_skip }
173 }
174 \clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_item_starred_X_bool` and others.)

`\c__enumext_all_envs_clist`

An internal `clist-var` variable to run with `\__enumext_tmp:n`.

```

175 \clist_const:Nn \c__enumext_all_envs_clist
176 {
177   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv},
178   {keyans}{v}, {enumext*}{vii}, {keyans*}{viii}
179 }

```

(End of definition for `\c__enumext_all_envs_clist`.)



## 10.5 Some utility functions

`\__enumext_at_begin_document:n`

A internal “hook” function used for copying plain `list` and `minipage` environments definition and `hyperref` detection.

```
180 \cs_new_protected:Npn \__enumext_at_begin_document:n #1
181 {
182   \hook_gput_code:nnn {begindocument} {enumext} { #1 }
183 }
```

(End of definition for `\__enumext_at_begin_document:n`.)

`\__enumext_after_env:nn`

A internal “hook” function for execute code `minirigth` and `minirigth*` keys outside the `enumext*` and `keyans*` environments and print check-ans outside the `enumext` and `enumext*` environments.

```
184 \cs_new_protected:Npn \__enumext_after_env:nn #1 #2
185 {
186   \hook_gput_code:nnn {env/#1/after} {enumext} {#2}
187 }
```

(End of definition for `\__enumext_after_env:nn`.)

`\__enumext_level:`

Function for check current level in `enumext`.

```
188 \cs_new:Nn \__enumext_level:
189 {
190   \int_to_roman:n { \l__enumext_level_int }
191 }
```

(End of definition for `\__enumext_level:.`)

`\__enumext_if_is_int:nT`

A conditional function to know if the variable we are passing is an integer used by `start` and `widest` keys. This function is taken directly from the answer given by Henri Menke in [How to test if an expl3 function argument is an integer expression?](#).

`\__enumext_if_is_int:nF`

`\__enumext_if_is_int:nTF`

```
192 \prg_new_protected_conditional:Npnn \__enumext_if_is_int:n #1 { T, F, TF }
193 {
194   \regex_match:nnTF { ^[\+|-]?[\d]+$ } {#1} % $
195   { \prg_return_true: }
196   { \prg_return_false: }
197 }
```

(End of definition for `\__enumext_if_is_int:nT`, `\__enumext_if_is_int:nF`, and `\__enumext_if_is_int:nTF`.)

`\__enumext_show_length:nnn`

Internal function used by `show-length` key to show “all lengths” calculated and use in `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```
198 \cs_new:Npn \__enumext_show_length:nnn #1 #2 #3
199 {
200   * ~ #2
201   \prg_replicate:nn { 14 - \str_count:n {#2} } { ~ }
202   = ~ \use:c { #1_use:c } { \l__enumext_#2_#3_#1 } \\
203 }
```

(End of definition for `\__enumext_show_length:nnn`.)

`\__enumext_zero_count_level:`

Internal function used by `check-ans` key.

```
204 \cs_set_protected:Nn \__enumext_zero_count_level:
205 {
206   \cs_set_protected:Npn \__enumext_tmp:n ##1
207   {
208     \int_gzero:c { g__enumext_count_level_##1_int }
209   }
210   \clist_map_inline:nn { i, ii, iii, iv, vii } { \l__enumext_tmp:n {##1} }
211 }
```

(End of definition for `\__enumext_zero_count_level:.`)

`\__enumext_current_env:`

The function `\__enumext_current_env:` will set the global variables `\g__enumext_standar_bool` and `\g__enumext_starred_bool` with which we will distinguish whether the environments `enumext` and `enumext*` are nested in each other.

```
212 \cs_new_protected:Nn \__enumext_current_env:
213 {
214   \str_case:en { \@currenenv }
215   {
216     {enumext}
```

```

217         {
218             \int_compare:nNtT { \__enumext_level_h_int } = { \c_zero_int }
219             {
220                 \bool_gset_true:N \g__enumext_standar_bool
221                 \int_gset:Nn \g__enumext_standar_star_env_int { \inputlineno }
222                 \typeout{working-on-enumext}
223             }
224         }
225     {enumext*}
226     {
227         \int_compare:nNtT { \__enumext_level_int } = { \c_zero_int }
228         {
229             \bool_gset_true:N \g__enumext_starred_bool
230             \int_gset:Nn \g__enumext_starred_star_env_int { \inputlineno }
231             \typeout{working-on-enumext*}
232         }
233     }
234 }
235 }

```

(End of definition for `\__enumext_current_env:`.)

## 10.6 Copying list and minipage environments

The `list` environment provided by  $\LaTeX$  has the following plain form:

```

\list{⟨arg one⟩}{⟨arg two⟩}
  \item[⟨opt⟩]
\endlist

```

As a precaution we copy them using `\__enumext_at_begin_document:n` in case any package redefines the `list` environment or a related command.

```

\__enumext_start_list:nn
\__enumext_stop_list:
\__enumext_item_std:w

```

The functions `\__enumext_start_list:nn`, `\__enumext_stop_list:` and `\__enumext_item_std:w` correspond to copies of `\list`, `\endlist` and `\item` from plain definition of `list` environment.

```

236 \__enumext_at_begin_document:n
237 {
238     \cs_new_eq:NN \__enumext_start_list:nn \list
239     \cs_new_eq:NN \__enumext_stop_list: \endlist
240     \cs_new_eq:NN \__enumext_item_std:w \item
241 }

```

(End of definition for `\__enumext_start_list:nn`, `\__enumext_stop_list:`, and `\__enumext_item_std:w`.)

The `minipage` environment provided by  $\LaTeX$  has the following (simplified) plain form:

```

\minipage[⟨pos⟩][⟨height⟩][⟨inner-pos⟩]{⟨width⟩}
  ⟨internal implement⟩
\endminipage

```

As a precaution we copy them using `\__enumext_at_begin_document:n` in case any package redefines the `minipage` environment or a related command.

```

\__enumext_minipage:w
\__enumext_endminipage:

```

The functions `\__enumext_minipage:w`, `\__enumext_endminipage:` and correspond to copies of `\minipage`, `\endminipage` from plain definition of `minipage` environment.

```

242 \__enumext_at_begin_document:n
243 {
244     \cs_new_eq:NN \__enumext_minipage:w \minipage
245     \cs_new_eq:NN \__enumext_endminipage: \endminipage
246 }

```

(End of definition for `\__enumext_minipage:w` and `\__enumext_endminipage:`.)

## 10.7 Compatibility with hyperref and footnotehyper

First we define the necessary rules using “hooks” to determine if the `hyperref` package is loaded.

```

247 \hook_gput_code:nnn { begindocument } { enumext } { \__enumext_after_hyperref: }
248 \hook_gset_rule:nnnn { begindocument } { enumext } { after } { hyperref }

```

```

\__enumext_after_hyperref:
\__enumext_hypertarget:nn
\__enumext_phantomsection:

```

The function `\__enumext_after_hyperref:` sets the state of the boolean variable `\l__enumext_hyperref_bool` to “true” if the package is loaded. At this point we will use the public macro `\IfHyperBoolean` to determine if the `hyperfootnotes=true` key is present, if so, we set the state of the boolean variable `\__enumext_footnotes_key_bool` to “true”.

```

249 \cs_new_protected:Nn \__enumext_after_hyperref:

```

```

250 {
251   \IfPackageLoadedTF { hyperref }
252   {
253     \msg_info:nnn { enumext } { package-load } { hyperref }
254     \bool_set_true:N \l__enumext_hyperref_bool
255     \IfHyperBoolean{hyperfootnotes}
256     {
257       \typeout{hyperfootnotes=true}
258       \bool_set_true:N \l__enumext_footnotes_key_bool
259     }
260     { \typeout{hyperfootnotes=false} }
261   }
262   { }

```

If the state of the variable `\l__enumext_footnotes_key_bool` is true we will check if the package `footnotehyper` is loaded, in case it is not present, we will set the value of `\l__enumext_footnotes_key_bool` to false and we will redefine `\footnote`.

```

263   \bool_if:NT \l__enumext_footnotes_key_bool
264   {
265     \IfPackageLoadedTF { footnotehyper }
266     {
267       \msg_info:nnn { enumext } { package-load } { footnotehyper }
268     }
269     {
270       \typeout{No ~ footnotehyper ~ load}
271       \typeout{Load ~ and ~ use ~ \string\makesavenoteenv{enumext*}}
272       \bool_set_false:N \l__enumext_footnotes_key_bool
273     }
274   }

```

The functions `\__enumext_hypertarget:nn` and `\__enumext_phantomsection:` correspond to the internal copies of `\hypertarget` and `\phantomsection`. If the boolean variable `\l__enumext_hyperref_bool` is false the functions `\__enumext_hypertarget:nn` and `\__enumext_phantomsection:` will be disabled.

```

275   \bool_if:NTF \l__enumext_hyperref_bool
276   {
277     \cs_new_eq:NN \__enumext_hypertarget:nn \hypertarget
278     \cs_new_eq:NN \__enumext_phantomsection: \phantomsection
279   }
280   {
281     \cs_new_eq:NN \__enumext_hypertarget:nn \use_none:nn
282     \cs_new_eq:NN \__enumext_phantomsection: \prg_do_nothing:
283   }
284 }

```

(End of definition for `\__enumext_after_hyperref:`, `\__enumext_hypertarget:nn`, and `\__enumext_phantomsection:`.)

`\__enumext_newlabel:nn` The function `\__enumext_newlabel:nn` write the information to the `.aux` file when using the `save-ref` key. The arguments taken by the function are:

#1: `\l__enumext_newlabel_arg_one_tl`

#2: `\l__enumext_newlabel_arg_two_tl`

The trick here is to manage the number of arguments passed to `\newlabel{#1}{#2}` according to the presence of the `hyperref` package.

```

285 \cs_new_protected:Npn \__enumext_newlabel:nn #1 #2
286 {
287   \protected@write \@auxout { }
288   {
289     \token_to_str:N \newlabel {#1}
290     {
291       {#2}
292       \bool_if:NT \l__enumext_hyperref_bool
293       { { \thepage } {#2} {#1} }
294       { }
295     }
296   }
297   \__enumext_hypertarget:nn {#1} { }
298   \__enumext_phantomsection:
299 }

```

(End of definition for `\__enumext_newlabel:nn`.)

## 10.8 Definition of counters

```
\__enumext_define_counters:Nn
\__enumext_define_counters:cn
```

To create the necessary “counters” we must first make sure that they are not already defined by the user or a package such as `enumitem`, otherwise an error will be returned and the package loading will be aborted. The arguments taken by the function are:

- #1 : A token list `\__enumext_counter_X_tl` for “store” the counter’s name.
- #2 : The counter’s name.

```
300 \cs_new_protected:Npn \__enumext_define_counters:Nn #1 #2
301 {
302   \cs_if_exist:cTF { c@ #2 }
303   { \msg_fatal:nnn { enumext } { counters }{ #2 } }
304   {
305     \tl_set:Nn #1 { #2 }
306     \newcounter { #2 }
307   }
308 }
```

(End of definition for `\__enumext_define_counters:Nn`.)

The counters created here are `enumXi`, `enumXii`, `enumXiii` and `enumXiv` for `enumext` environment, `enumXv` for `keyans` environment, `enumXvi` for `keyanspic` environment, `enumXvii` for `enumext*` and `enumXviii` for the `keyans*` environments.

```
enumXi      309 \__enumext_define_counters:Nn \__enumext_counter_i_tl { enumXi }
enumXii     310 \__enumext_define_counters:Nn \__enumext_counter_ii_tl { enumXii }
enumXiii    311 \__enumext_define_counters:Nn \__enumext_counter_iii_tl { enumXiii }
enumXiv     312 \__enumext_define_counters:Nn \__enumext_counter_iv_tl { enumXiv }
enumXv      313 \__enumext_define_counters:Nn \__enumext_counter_v_tl { enumXv }
enumXvii    314 \__enumext_define_counters:Nn \__enumext_counter_vii_tl { enumXvii }
enumXviii   315 \__enumext_define_counters:Nn \__enumext_counter_viii_tl { enumXviii }
316 \__enumext_define_counters:Nn \__enumext_counter_viii_tl { enumXviii }
```

(End of definition for `enumXi` and others.)

## 10.9 Definition of labels

This part of the code is inspired by the `enumitem` package. The idea is to be able to access the counters using `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` to use them in the `label` key.

```
\__enumext_register_counter_style:Nn
```

These *counters* will be used as default *labels* if the `label` key is not used for the different levels of the `enumext` environment and the `keyans` environment, so it is necessary to get a default value for `labelwidth` from these *labels* at the same time.

```
317 \cs_new_protected:Npn \__enumext_register_counter_style:Nn #1 #2
318 {
319   \tl_const:cn { c__enumext_widest_ \cs_to_str:N #1 _tl } {#2}
320   \tl_gput_right:Nn \g__enumext_counter_styles_tl {#1}
321 }
322 \__enumext_register_counter_style:Nn \arabic { 0 }
323 \__enumext_register_counter_style:Nn \Alph { M }
324 \__enumext_register_counter_style:Nn \alph { m }
325 \__enumext_register_counter_style:Nn \Roman { VIII }
326 \__enumext_register_counter_style:Nn \roman { viii }
```

(End of definition for `\__enumext_register_counter_style:Nn`.)

```
\__enumext_label_width_by_box:Nn
\__enumext_label_width_by_box:cv
```

The function `\__enumext_label_width_by_box:Nn` set the default `\labelwidth` using a box width if no `labelwidth` key is passed.

```
327 \cs_new_protected:Npn \__enumext_label_width_by_box:Nn #1 #2
328 {
329   \hbox_set:Nn \l__enumext_label_width_by_box {#2}
330   \dim_set:Nn #1 { \box_wd:N \l__enumext_label_width_by_box }
331 }
332 \cs_generate_variant:Nn \__enumext_label_width_by_box:Nn { cv }
```

(End of definition for `\__enumext_label_width_by_box:Nn`.)

```
\__enumext_label_style:Nnn
\__enumext_label_style:cvn
```

The function `\__enumext_label_style:Nnn` is used by the `label` key to creates the variables containing the *label style* and will allow to use `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` as arguments. It loops through the defined counter styles in `\g__enumext_counter_styles_tl` (`\arabic`, `\alph`, `\Alph`, `\roman`, and `\Roman`) for example, looking for `\roman*` and replacing that by `\roman{counter}`, and doing the same for the `\g__enumext_widest_label_tl` to keep both in sync.

```
333 \cs_new_protected:Npn \__enumext_label_style:Nnn #1 #2 #3
```

```

334 {
335   \tl_clear_new:N #1
336   \tl_put_right:Ne #1 { \tl_trim_spaces:n {#3} }
337   \tl_gset_eq:NN \g__enumext_widest_label_tl #1
338   \tl_map_inline:Nn \g__enumext_counter_styles_tl
339   {
340     \tl_replace_all:Nne #1 { ##1* } { \exp_not:N ##1 {#2} }
341     \tl_greplace_all:Nne \g__enumext_widest_label_tl { ##1* }
342     { \tl_use:c { c__enumext_widest_ \cs_to_str:N ##1 _tl } }
343   }
344   \__enumext_label_width_by_box:Nn \__enumext_current_widest_dim
345   { \tl_use:N \g__enumext_widest_label_tl }
346   \tl_set_eq:cN { the #2 } #1
347 }
348 \cs_generate_variant:Nn \__enumext_label_style:Nnn { cvn }

```

(End of definition for `\__enumext_label_style:Nnn`.)

## 10.10 Setting keys associated with label

font Definition of keys `font`, `labelsep`, `labelwidth`, `wrap-label` and `wrap-label*` keys for `enumext` and `keyans` environments.

```

labelsep
labelwidth
wrap-label
wrap-label*
349 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
350 {
351   \keys_define:nn { enumext / #1 }
352   {
353     font .tl_set:c = { l__enumext_label_font_style_#2_tl },
354     font .value_required:n = true,
355     labelsep .dim_set:c = { l__enumext_labelsep_#2_dim },
356     labelsep .initial:n = {0.3333em},
357     labelsep .value_required:n = true,
358     labelwidth .dim_set:c = { l__enumext_labelwidth_#2_dim },
359     labelwidth .value_required:n = true,
360     wrap-label .cs_set_protected:cp = { __enumext_wrapper_label_#2:n } ##1,
361     wrap-label .initial:n = {##1},
362     wrap-label .value_required:n = true,
363     wrap-label* .code:n = {
364       \bool_set_true:c { l__enumext_wrap_label_opt_#2_bool }
365       \keys_set:nn { enumext / #1 } { wrap-label = {##1} }
366     },
367     wrap-label* .value_required:n = true,
368   }
369 }
370 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `font` and others.)

- In this point, the following are set `\__enumext_wrapper_label_X:n` which will be used by `\__enumext_make_label:` for the different levels of the `enumext` environment and is set to `\__enumext_wrapper_label_v:n` which will be used by `\__enumext_keyans_make_label:` for `keyans` and `keyanspic` environments.

align The `align` key is implemented differently for “starred” and “non starred” environments.

```

371 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
372 {
373   \keys_define:nn { enumext / #1 }
374   {
375     align .choice:,
376     align / left .code:n =
377     {
378       \tl_clear:c { l__enumext_label_fill_left_#2_tl }
379       \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
380     },
381     align / right .code:n =
382     {
383       \tl_set:cn { l__enumext_label_fill_left_#2_tl } { \hfill }
384       \tl_clear:c { l__enumext_label_fill_right_#2_tl }
385     },
386     align / center .code:n =
387     {
388       \tl_set:cn { l__enumext_label_fill_left_#2_tl } { \hfill }
389       \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
390     },

```

```

391     align .initial:n = left,
392     align .value_required:n = true,
393   }
394 }
395 \clist_map_inline:nn
396 {
397   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {keyans}{v}
398 }
399 { \__enumext_tmp:nn #1 }

```

Definition of `align` key for `enumext*` and `keyans*` environments.

```

400 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
401 {
402   \keys_define:nn { enumext / #1 }
403   {
404     align .choice:,
405     align / left .code:n = \str_set:cn { l__enumext_align_label_#2_str } { l },
406     align / right .code:n = \str_set:cn { l__enumext_align_label_#2_str } { r },
407     align / center .code:n = \str_set:cn { l__enumext_align_label_#2_str } { c },
408     align .initial:n = left,
409     align .value_required:n = true,
410   }
411 }
412 \clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }

```

(End of definition for `align`.)

### 10.11 Setting label and ref keys

`\__enumext_regex_label_ref_key:`

The internal function `\__enumext_regex_label_ref_key:` replace the `*` with the actual counter of the running level and is used by the `\__enumext_set_label_ref:n` function.

It loops through the defined counter styles in `\c__enumext_counter_style_tl` and replace `*` by real command, for example, looking for `\arabic*` and replacing that by `\arabic{<counter>}` defined on the current level.

```

413 \cs_new_protected:Nn \__enumext_regex_label_ref_key:
414 {
415   \tl_map_inline:Nn \c__enumext_counter_style_tl
416   {
417     \regex_replace_once:nnN { \c{##1}}{*}
418     { \c{##1}\cB{\u{l__enumext_ref_aux_tl}\cE} } \l__enumext_ref_key_arg_tl
419   }
420 }

```

(End of definition for `\__enumext_regex_label_ref_key:`.)

`\__enumext_set_label_ref:n`

The `\__enumext_set_label_ref:n` function controlled by the `ref` key is in charge of handling the customization of the reference system.

First we will set the variable `\l__enumext_the_counter_X_tl` according to the command created for *each counter*, apply the `regex` function `\__enumext_regex_label_ref_key:` and then renew the command and save it in the variable `\l__enumext_counter_style_for_ref_X_tl`.

```

421 \cs_new_protected:Npn \__enumext_set_label_ref:n #1
422 {
423   \tl_set:Nn \l__enumext_ref_key_arg_tl {#1}
424   \tl_set_eq:Nc \l__enumext_ref_aux_tl { l__enumext_counter_ \__enumext_level: _tl }
425   \__enumext_regex_label_ref_key:
426   \tl_set_eq:Nc \l__enumext_ref_aux_tl { l__enumext_the_counter_ \__enumext_level: _tl }
427   \tl_put_right:ce { l__enumext_counter_style_for_ref_ \__enumext_level: _tl }
428   {
429     \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_aux_tl }
430     { \exp_not:V \l__enumext_ref_key_arg_tl }
431   }
432 }

```

(End of definition for `\__enumext_set_label_ref:n`.)

`\__enumext_use_key_ref:`

Finally the function `\__enumext_use_key_ref:` will execute the modification for the reference system in the second argument of the environment definition `enumext`.

```

433 \cs_new_protected:Nn \__enumext_use_key_ref:
434 {
435   \tl_if_empty:cF { l__enumext_counter_style_for_ref_ \__enumext_level: _tl }
436   {

```



```

437         \tl_use:c { l__enumext_counter_style_for_ref_ \__enumext_level: _tl }
438     }
439 }

```

(End of definition for `\__enumext_use_key_ref:`.)

For `enumext*` and `keyans*` environments the situation is a bit different since `hyperref` interferes here (I am not clear why), so we will define a new function to execute the task.

To handle that we will look at the nesting level of the starred environments, later I will run the constraint functions to make everything OK.

The `\__enumext_set_label_ref_h:n` function controlled by the `ref` key is in charge of handling the customization of the reference system.

First we will set the variable `\l__enumext_the_counter_X_tl` according to the command created for *each counter*, apply the `regex` function `\__enumext_regex_label_ref_key:` and then renew the command and save it in the variable `\l__enumext_counter_style_for_ref_X_tl`.

```

440 \cs_new_protected:Npn \__enumext_set_label_ref_h:n #1
441 {
442     \tl_set:Nn \l__enumext_ref_key_arg_tl {#1}
443     \int_compare:nNnTF { \l__enumext_level_h_int } = { 1 }
444     {
445         \tl_set_eq:NN \l__enumext_ref_aux_tl \l__enumext_counter_vii_tl
446         \__enumext_regex_label_ref_key:
447         \tl_set_eq:NN \l__enumext_ref_aux_tl \l__enumext_the_counter_vii_tl
448         \tl_put_right:Ne \l__enumext_counter_style_for_ref_vii_tl
449         {
450             \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_aux_tl }
451             { \exp_not:V \l__enumext_ref_key_arg_tl }
452         }
453     }
454     {
455         \tl_set_eq:NN \l__enumext_ref_aux_tl \l__enumext_counter_viii_tl
456         \__enumext_regex_label_ref_key:
457         \tl_set_eq:NN \l__enumext_ref_aux_tl \l__enumext_the_counter_viii_tl
458         \tl_put_right:Ne \l__enumext_counter_style_for_ref_vii_tl
459         {
460             \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_aux_tl }
461             { \exp_not:V \l__enumext_ref_key_arg_tl }
462         }
463     }
464 }

```

(End of definition for `\__enumext_set_label_ref_h:n`.)

Finally the function `\__enumext_use_key_ref_h:` will execute the modification for the reference system in the second argument of the environment definition `enumext*` and `keyans*`.

```

465 \cs_new_protected:Npn \__enumext_use_key_ref_h:
466 {
467     \int_compare:nNnTF { \l__enumext_level_h_int } = { 1 }
468     {
469         \tl_if_empty:NF \l__enumext_counter_style_for_ref_vii_tl
470         {
471             \tl_use:N \l__enumext_counter_style_for_ref_vii_tl
472         }
473     }
474     {
475         \tl_if_empty:NF \l__enumext_counter_style_for_ref_viii_tl
476         {
477             \tl_use:N \l__enumext_counter_style_for_ref_viii_tl
478         }
479     }
480 }

```

(End of definition for `\__enumext_use_key_ref_h:`.)

### 10.11.1 Define and set label key for enumext environment

Here we set the default *labels* of the four levels of `enumext` environment, along with the default value for `labelwidth` key.

```

\l__enumext_label_i_tl
\l__enumext_label_ii_tl
\l__enumext_label_iii_tl
\l__enumext_label_iv_tl
481 \cs_set_protected:Npn \__enumext_tmp:nnn #1 #2 #3
482 {
483     \keys_define:nn { enumext / #1 }

```

```

484     {
485       label .code:n = {
486         \__enumext_label_style:cvn { l__enumext_label_#2_tl }
487         { l__enumext_counter_#2_tl } {##1}
488         \dim_set_eq:cN { l__enumext_labelwidth_#2_dim }
489         \l__enumext_current_widest_dim
490       },
491       label .initial:n = #3,
492       label .value_required:n = true,
493       ref .code:n = \__enumext_set_label_ref:n {##1},
494       ref .value_required:n = true,
495     }
496   }
497   \__enumext_tmp:nnn { level-1 } { i } { \arabic*. }
498   \__enumext_tmp:nnn { level-2 } { ii } { (\alph*) }
499   \__enumext_tmp:nnn { level-3 } { iii } { \roman*. }
500   \__enumext_tmp:nnn { level-4 } { iv } { \Alph*. }

```

(End of definition for `label` and others.)

### 10.11.2 Define and set `label` key for `enumext*` and `keyans*` environments

Here we set the default `<label>` for `enumext*` and `keyans*` environments, along with the default value for `labelwidth` key.

```

\l__enumext_label_vii_tl
\l__enumext_label_viii_tl
501 \cs_set_protected:Npn \__enumext_tmp:nnn #1 #2 #3
502 {
503   \keys_define:nn { enumext / #1 }
504   {
505     label .code:n = {
506       \__enumext_label_style:cvn { l__enumext_label_#2_tl }
507       { l__enumext_counter_#2_tl } {##1}
508       \dim_set_eq:cN { l__enumext_labelwidth_#2_dim }
509       \l__enumext_current_widest_dim
510     },
511     label .initial:n = #3,
512     label .value_required:n = true,
513     ref .code:n = \__enumext_set_label_ref_h:n {##1},
514     ref .value_required:n = true,
515   }
516 }
517 \__enumext_tmp:nnn { enumext* } { vii } { \arabic*. }
518 \__enumext_tmp:nnn { keyans* } { viii } { (\Alph*) }

```

(End of definition for `label` and others.)

### 10.11.3 Define and set `label` key for `keyans` and `keyanspic` environment

Here we set the default `<label>` for `keyans` and `keyanspic` environment, along with the default value for `labelwidth`. The `keyanspic` environment use the same `<label>` as the `keyans` environment.

Define and set `label` key for `keyans` environment.

```

519 \keys_define:nn { enumext / keyans }
520 {
521   label .code:n = {
522     \__enumext_label_style:cvn { l__enumext_label_v_tl }
523     { l__enumext_counter_v_tl } {##1}
524     \dim_set_eq:cN { l__enumext_labelwidth_v_dim }
525     \l__enumext_current_widest_dim
526     \__enumext_label_style:cvn { l__enumext_label_vi_tl }
527     { l__enumext_counter_vi_tl } {##1}
528     \dim_set_eq:cN { l__enumext_labelwidth_v_dim }
529     \l__enumext_current_widest_dim
530   },
531   label .initial:n = (\Alph*),
532   label .value_required:n = true,
533 }

```

(End of definition for `label`, `\l__enumext_label_v_tl`, and `\l__enumext_label_vi_tl`.)

## 10.12 Setting start and widest keys

The function `\__enumext_start_from:NNn` used by the `start` key take three arguments:

```

#1: \l__enumext_label_X_tl
#2: \l__enumext_start_X_int

```

#3: *<integer or string>*

The first argument of this function are the “*counter style*” set by `label` key, the second argument is returned by the function, the third argument can be an *<integer>* or *<string>* of the form `\Alph`, `\alph`, `\Roman` or `\roman`. This effectively allows `start=A` or `start=1` to be used.

```

534 \cs_new_protected:Npn \__enumext_start_from:NNn #1 #2 #3
535 {
536   \__enumext_if_is_int:nTF { #3 }
537   {
538     \int_set:Nn #2 {#3}
539   }
540   {
541     \regex_match:nVT { \c{Alph} | \c{alph} } {#1}
542     { \int_set:Nn #2 { \int_from_alph:n {#3} } }
543     \regex_match:nVT { \c{Roman} | \c{roman} } {#1}
544     { \int_set:Nn #2 { \int_from_roman:n {#3} } }
545   }
546 }
547 \cs_generate_variant:Nn \__enumext_start_from:NNn { ccn }

```

(End of definition for `\__enumext_start_from:NNn`.)

```

\__enumext_widest_from:nNNn
\__enumext_widest_from:nccn

```

The function `\__enumext_widest_from:nNNn` used by the `widest` key take four arguments:

- #1: The counter associated with the environment level
- #2: `\l__enumext_label_X_tl`
- #3: `\l__enumext_labelwidth_X_dim`
- #4: *<integer or string>*

The second and third arguments of this function are the values set by `label` and `labelwidth` keys, the four argument can be an *<integer>* or *<string>* of the form `\Alph`, `\alph`, `\Roman` or `\roman`. The value of the four argument is set temporarily for the identified counter in this point (level), then the value is expanded into a “*box*” and the “*width*” of the “*box*” is returned.

```

548 \cs_new_protected:Npn \__enumext_widest_from:nNNn #1 #2 #3 #4
549 {
550   \__enumext_if_is_int:nTF {#4}
551   {
552     \setcounter{enumX#1} { #4 }
553   }
554   {
555     \regex_match:nVT { \c{Alph} | \c{alph} } {#2}
556     { \setcounter{enumX#1} { \int_from_alph:n {#4} } }
557     \regex_match:nVT { \c{Roman} | \c{roman} } {#2}
558     { \setcounter{enumX#1} { \int_from_roman:n {#4} } }
559   }
560   \__enumext_label_width_by_box:cv
561   { \__enumext_labelwidth_#1_dim } { \__enumext_label_#1_tl }
562 }
563 \cs_generate_variant:Nn \__enumext_widest_from:nNNn { nccn }

```

(End of definition for `\__enumext_widest_from:nNNn`.)

Now define and set `start` and `widest` keys for `enumext` and `keyans` environments.

```

start
widest
\l__enumext_start_X_int
564 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
565 {
566   \keys_define:nn { enumext / #1 }
567   {
568     start .code:n = {
569       \__enumext_start_from:ccn
570       { \__enumext_label_#2_tl }
571       { \__enumext_start_#2_int } {##1}
572     },
573     start .initial:n = 1,
574     widest .code:n = {
575       \__enumext_widest_from:nccn {#2}
576       { \__enumext_label_#2_tl }
577       { \__enumext_labelwidth_#2_dim } {##1}
578     },
579     widest .value_required:n = true,
580     start .value_required:n = true,
581   }
582 }
583 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `start`, `widest`, and `\l__enumext_start_X_int`.)

## 10.13 Setting keys for vertical spaces

Define and set `topsep`, `partopsep`, `parsep`, `itemsep`, `noitemsep` and `nosep` keys for `enumext` and `keyans` environments.

```

topsep
partopsep
parsep
noitemsep
nosep
584 \cs_set_protected:Npn \__enumext_tmp:nnnnnn #1 #2 #3 #4 #5 #6
585 {
586   \keys_define:nn { enumext / #1 }
587   {
588     topsep      .skip_set:c = { l__enumext_topsep_#2_skip },
589     topsep      .initial:n   = {#3},
590     topsep      .value_required:n = true,
591     partopsep   .skip_set:c = { l__enumext_partopsep_#2_skip },
592     partopsep   .initial:n   = {#4},
593     partopsep   .value_required:n = true,
594     parsep      .skip_set:c = { l__enumext_parsep_#2_skip },
595     parsep      .initial:n   = {#5},
596     parsep      .value_required:n = true,
597     itemsep     .skip_set:c = { l__enumext_itemsep_#2_skip },
598     itemsep     .initial:n   = {#6},
599     itemsep     .value_required:n = true,
600     noitemsep   .meta:n      = { itemsep = 0pt, parsep = 0pt },
601     noitemsep   .value_forbidden:n = true,
602     nosep       .meta:n      = {
603                                   itemsep = 0pt, parsep= 0pt,
604                                   topsep = 0pt, partopsep = 0pt,
605                                   },
606     nosep       .value_forbidden:n = true,
607   }
608 }
```

Now we set the values based on standard `article` class in `10pt`.

```

609 \__enumext_tmp:nnnnnn { level-1 } { i } { 8.0pt plus 2.0pt minus 4.0pt }
610 { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
611 { 4.0pt plus 2.0pt minus 1.0pt }
612 \__enumext_tmp:nnnnnn { level-2 } { ii } { 4.0pt plus 2.0pt minus 1.0pt }
613 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
614 { 2.0pt plus 1.0pt minus 1.0pt }
615 \__enumext_tmp:nnnnnn { level-3 } { iii } { 2.0pt plus 1.0pt minus 1.0pt }
616 { 1.0pt minus 1.0pt } { 0pt } { 2.0pt plus 1.0pt minus 1.0pt }
617 \__enumext_tmp:nnnnnn { level-4 } { iv } { 2.0pt plus 1.0pt minus 1.0pt }
618 { 1.0pt minus 1.0pt } { 0pt } { 2.0pt plus 1.0pt minus 1.0pt }
619 \__enumext_tmp:nnnnnn { keyans } { v } { 4.0pt plus 2.0pt minus 1.0pt }
620 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
621 { 2.0pt plus 1.0pt minus 1.0pt }
622 \__enumext_tmp:nnnnnn { enumext* } { vii } { 8.0pt plus 2.0pt minus 4.0pt }
623 { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
624 { 4.0pt plus 2.0pt minus 1.0pt }
625 \__enumext_tmp:nnnnnn { keyans* } { viii } { 4.0pt plus 2.0pt minus 1.0pt }
626 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
627 { 2.0pt plus 1.0pt minus 1.0pt }
```

(End of definition for `topsep` and others.)

## 10.14 Setting keys for horizontal spaces

Define and set `itemindent`, `rightmargin`, `listparindent`, `list-offset` and `list-indent` keys for `enumext` and `keyans` environments.

```

628 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
629 {
630   \keys_define:nn { enumext / #1 }
631   {
632     itemindent   .dim_set:c = { l__enumext_fake_item_indent_#2_dim },
633     itemindent   .value_required:n = true,
634     rightmargin  .dim_set:c = { l__enumext_rightmargin_#2_dim },
635     rightmargin  .value_required:n = true,
636     listparindent .dim_set:c = { l__enumext_listparindent_#2_dim },
637     listparindent .value_required:n = true,
638     list-offset  .dim_set:c = { l__enumext_listoffset_#2_dim },
639     list-offset  .value_required:n = true,
640     list-indent  .code:n      =
```

```

641         \bool_set_true:c { l__enumext_leftmargin_tmp_#2_bool }
642         \dim_set:cn { l__enumext_leftmargin_tmp_#2_dim } {##1},
643     list-indent .value_required:n = true,
644 }
645 }
646 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `itemindent` and others.)

For `enumext*` and `keyans*` environments the situation is a bit different, the `list-indent` key behaves like the `list-offset` key.

```

647 \cs_set_protected:Npn \__enumext_tmp:n #1
648 {
649     \keys_define:nn { enumext / #1 } { list-indent .initial:n = 0pt, }
650 }
651 \clist_map_inline:nn { enumext*, keyans* } { \__enumext_tmp:n {##1} }

```

#### 10.14.1 Functions for setting the fake `itemindent`

The `itemindent` key does not set the value of `\itemindent`, it only sets the value of the *horizontal space* applied using `\skip_horizontal:N`. We will store this value in the variable and only apply it when it is greater than `0pt`. Here I will need to place `\mode_leave_vertical:` and the plain  $\TeX$  macro `\ignorespaces` to avoid unwanted extra space when using the `itemindent` key.

```

652 \cs_set_protected:Nn \__enumext_fake_item:
653 {
654     \dim_compare:nNnT
655     { \dim_use:c { l__enumext_fake_item_indent_ \__enumext_level: _dim } }
656     >
657     { \c_zero_dim }
658     {
659         \tl_set:ce { l__enumext_fake_item_indent_ \__enumext_level: _tl }
660         {
661             \exp_not:N \mode_leave_vertical:
662             \exp_not:n { \skip_horizontal:n }
663             { \dim_use:c { l__enumext_fake_item_indent_ \__enumext_level: _dim } }
664             \ignorespaces
665         }
666     }
667 }
668 \cs_set_protected:Nn \__enumext_keyans_fake_item:
669 {
670     \dim_compare:nNnT
671     { \l__enumext_fake_item_indent_v_dim } > { \c_zero_dim }
672     {
673         \tl_set:Ne \l__enumext_fake_item_indent_v_tl
674         {
675             \exp_not:N \mode_leave_vertical:
676             \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_v_dim
677         }
678     }
679 }
680 \cs_set_protected:Nn \__enumext_fake_item_vii:
681 {
682     \dim_compare:nNnT
683     { \l__enumext_fake_item_indent_vii_dim } > { \c_zero_dim }
684     {
685         \tl_set:Ne \l__enumext_fake_item_indent_vii_tl
686         {
687             \exp_not:N \mode_leave_vertical:
688             \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_vii_dim
689         }
690     }
691 }
692 \cs_set_protected:Nn \__enumext_fake_item_viii:
693 {
694     \dim_compare:nNnT
695     { \l__enumext_fake_item_indent_viii_dim } > { \c_zero_dim }
696     {
697         \tl_set:Ne \l__enumext_fake_item_indent_viii_tl
698         {
699             \exp_not:N \mode_leave_vertical:
700             \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_viii_dim

```

```

701     }
702   }
703 }

```

(End of definition for `\__enumext_fake_item:` and others.)

### 10.15 Setting show-length key

show-length

Define and set `show-length` key for `enumext`, `enumext*`, `keyans` and `keyans*` environments. The function sets the boolean variable `\__enumext_show_length_X_bool` used in the definition of all environments to “*true*” and calls the function `\__enumext_show_length:nnn` which prints all the values of the “*vertical*” and “*horizontal*” parameters calculated and used.

```

704 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
705 {
706   \keys_define:nn { enumext / #1 }
707   {
708     show-length .bool_set:c = { l__enumext_show_length_#2_bool },
709     show-length .initial:n = false,
710   }
711 }
712 \clist_map_inline:Nn \__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `show-length`.)

### 10.16 Setting before, after and first keys

before  
before\*  
after  
first

Define and set `before`, `before*`, `after` and `first` keys for `enumext` and `keyans` environments.

```

713 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
714 {
715   \keys_define:nn { enumext / #1 }
716   {
717     before .tl_set:c = { l__enumext_before_no_starred_key_#2_tl },
718     before .value_required:n = true,
719     before* .tl_set:c = { l__enumext_before_starred_key_#2_tl },
720     before* .value_required:n = true,
721     after .tl_set:c = { l__enumext_after_stop_list_#2_tl },
722     after .value_required:n = true,
723     first .tl_set:c = { l__enumext_after_list_args_#2_tl },
724     first .value_required:n = true,
725   }
726 }
727 \clist_map_inline:Nn \__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `before` and others.)

#### 10.16.1 Functions for before, after and first keys in enumext

`\__enumext_before_args_exec:` The function `\__enumext_before_args_exec:` executes the `{⟨code⟩}` set by the `before*` key “*before*” the `enumext` environment is started. The `{⟨code⟩}` is executed “*without*” knowing any definition of the *second argument* of the list.

```

728 \cs_new_protected:Nn \__enumext_before_args_exec:
729 {
730   \tl_use:c { l__enumext_before_starred_key_ \__enumext_level: _tl }
731 }

```

The function `\__enumext_before_keys_exec:` executes the `{⟨code⟩}` set by the `before` key “*before*” the `enumext` environment is started in *second argument* of the list. The `{⟨code⟩}` is executed “*knowing*” all definition and values provides by `⟨keys⟩`.

```

732 \cs_new_protected:Nn \__enumext_before_keys_exec:
733 {
734   \tl_use:c { l__enumext_before_no_starred_key_ \__enumext_level: _tl }
735 }

```

The function `\__enumext_after_stop_list:` executes the `{⟨code⟩}` set by the `after` key “*after*” the `enumext` environment has finished.

```

736 \cs_new_protected:Nn \__enumext_after_stop_list:
737 {
738   \tl_use:c { l__enumext_after_stop_list_ \__enumext_level: _tl }
739 }

```

The function `\__enumext_after_args_exec`: executes the  $\{\langle code \rangle\}$  set by the `first` key after the end of the second argument of the list defining the `enumext` environment, just before the first occurrence of `\item`.

```
740 \cs_new_protected:Nn \__enumext_after_args_exec:
741 {
742   \tl_use:c { l__enumext_after_list_args_ \__enumext_level: _tl }
743 }
```

(End of definition for `\__enumext_before_args_exec`: and others.)

### 10.16.2 Functions for before, after and first keys in keyans

`\__enumext_before_args_exec_v`: The function `\__enumext_before_args_exec_v`: executes the  $\{\langle code \rangle\}$  set by the `before*` key “before” the `keyans` environment is started. The  $\{\langle code \rangle\}$  is executed “without” knowing any definition of the  $\{\langle arg two \rangle\}$  of the list.

```
\__enumext_before_keys_exec_v:
\__enumext_after_stop_list_v:
\__enumext_after_args_exec_v:
744 \cs_new_protected:Nn \__enumext_before_args_exec_v:
745 {
746   \tl_use:N \l__enumext_before_starred_key_v_tl
747 }
```

The function `\__enumext_before_keys_exec_v`: executes the  $\{\langle code \rangle\}$  set by the `before` key “before” the `keyans` environment is started in  $\{\langle arg two \rangle\}$  of the list. The  $\{\langle code \rangle\}$  is executed “knowing” all definition and values provides by  $\langle keys \rangle$ .

```
748 \cs_new_protected:Nn \__enumext_before_keys_exec_v:
749 {
750   \tl_use:N \l__enumext_before_no_starred_key_v_tl
751 }
```

The function `\__enumext_after_stop_list_v`: executes the  $\{\langle code \rangle\}$  set by the `after` key “after” the `keyans` environment has finished.

```
752 \cs_new_protected:Nn \__enumext_after_stop_list_v:
753 {
754   \tl_use:N \l__enumext_after_stop_list_v_tl
755 }
```

The function `\__enumext_after_args_exec_v`: executes the  $\{\langle code \rangle\}$  set by the `first` key after the end of  $\{\langle arg two \rangle\}$  of the list defining the `keyans` environment, just before the first occurrence of `\item`.

```
756 \cs_new_protected:Nn \__enumext_after_args_exec_v:
757 {
758   \tl_use:N \l__enumext_after_list_args_v_tl
759 }
```

(End of definition for `\__enumext_before_args_exec_v`: and others.)

### 10.16.3 Functions for before, after and first keys in enumext\* and keyans\*

`\__enumext_before_args_exec_vii`: The function `\__enumext_before_args_exec_v`: executes the  $\{\langle code \rangle\}$  set by the `before*` key “before” the `keyans` environment is started. The  $\{\langle code \rangle\}$  is executed “without” knowing any definition of the  $\{\langle arg two \rangle\}$  of the list.

```
\__enumext_before_keys_exec_vii:
\__enumext_after_stop_list_vii:
\__enumext_after_args_exec_vii:
760 \cs_new_protected:Nn \__enumext_before_args_exec_vii:
761 {
762   \tl_use:N \l__enumext_before_starred_key_vii_tl
763 }
764 \cs_new_protected:Nn \__enumext_before_args_exec_viii:
765 {
766   \tl_use:N \l__enumext_before_starred_key_viii_tl
767 }
```

The functions `\__enumext_before_keys_exec_vii`: and `\__enumext_before_keys_exec_viii`: executes the  $\{\langle code \rangle\}$  set by the `before` key “before” in `enumext*` and `keyans*` environments is started in  $\{\langle arg two \rangle\}$  of the list. The  $\{\langle code \rangle\}$  is executed “knowing” all definition and values provides by  $\langle keys \rangle$ .

```
768 \cs_new_protected:Nn \__enumext_before_keys_exec_vii:
769 {
770   \tl_use:N \l__enumext_before_no_starred_key_vii_tl
771 }
772 \cs_new_protected:Nn \__enumext_before_keys_exec_viii:
773 {
774   \tl_use:N \l__enumext_before_no_starred_key_viii_tl
775 }
```



The function `\__enumext_after_stop_list`: executes the `{(code)}` set by the `after` key “after” the `keyans` environment has finished.

```

776 \cs_new_protected:Nn \__enumext_after_stop_list_vii:
777 {
778   \tl_use:N \l__enumext_after_stop_list_vii_tl
779 }
780 \cs_new_protected:Nn \__enumext_after_stop_list_viii:
781 {
782   \tl_use:N \l__enumext_after_stop_list_viii_tl
783 }

```

The function `\__enumext_after_args_exec_v`: executes the `{(code)}` set by the `first` key after the end of `{(arg two)}` of the list defining the `keyans` environment, just before the first occurrence of `\item`.

```

784 \cs_new_protected:Nn \__enumext_after_args_exec_vii:
785 {
786   \tl_use:N \l__enumext_after_list_args_vii_tl
787 }
788 \cs_new_protected:Nn \__enumext_after_args_exec_viii:
789 {
790   \tl_use:N \l__enumext_after_list_args_viii_tl
791 }

```

(End of definition for `\__enumext_before_args_exec_vii`: and others.)

## 10.17 Setting keys for multicols and minipage

`mini-env`    The default value of the `columns-sep` key is handled by the state of the boolean variable `\l__enumext_columns_sep_X_bool` which is handled in the internal definition of the `enumext` and `keyans` environments.

`mini-sep`    Define and set `mini-env`, `mini-sep`, `columns-sep` and `columns` keys for `enumext` and `keyans` environments.

`columns-sep`

`columns`

```

792 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
793 {
794   \keys_define:nn { enumext / #1 }
795   {
796     mini-env   .dim_set:c = { l__enumext_minipage_right_#2_dim },
797     mini-env   .value_required:n = true,
798     mini-sep   .dim_set:c = { l__enumext_minipage_hsep_#2_dim },
799     mini-sep   .initial:n = 0.3333em,
800     mini-sep   .value_required:n = true,
801     columns-sep .dim_set:c = { l__enumext_columns_sep_#2_dim },
802     columns-sep .value_required:n = true,
803     columns    .int_set:c = { l__enumext_columns_#2_int },
804     columns    .initial:n = 1,
805     columns    .value_required:n = true,
806   }
807 }
808 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

For `enumext*` and `keyans*` environments the situation is a bit different, the default value for `columns` key are `2` and the command `\miniright` is not available, so we will add the keys `miniright` and `miniright*` to implement support for `minipage`.

```

809 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
810 {
811   \keys_define:nn { enumext / #1 }
812   {
813     columns    .initial:n = 2,
814     miniright  .tl_gset:c = { g__enumext_miniright_code_#2_tl },
815     miniright  .value_required:n = true,
816     miniright* .code:n = {
817       \bool_gset_true:c { g__enumext_minipage_center_#2_bool }
818       \keys_set:nn { enumext / #1 } { miniright = {##1} }
819     },
820     miniright* .value_required:n = true,
821   }
822 }
823 \clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }

```

(End of definition for `mini-env` and others.)

## 10.18 Adjustment of vertical spaces for multcols

When nesting a “list environment” inside the `multcols` environment, the values of the “vertical spaces” are lost, basically the `multcols` environment takes control over them. Graphically it can be seen like in the figure 7.




Figure 7: Representation of the vertical space in `multcols` for a nested level.

To keep the desired spaces *above* and *below* in the “list environment” (`\topsep` + `[\partopsep]`) it is necessary to “adjust” the spaces added by the `multcols` environment. The most appropriate option in this case is to use a “context sensitive” vertical space with `\addvspace`.

I should make it clear that the implementation here is a “bit questionable”. At first glance doing `\multicolsep=\topsep` seemed right, but the results were not always as expected. An almost *imperceptible* detail is that in some cases the `\itemsep` values of are “stretched”, possibly due to the use of `\raggedcolumns` and this affects the lower space when closing the environment, which is “smaller” than expected. My attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

### 10.18.1 Adjustment of vertical spaces for multcols in enumext

`\__enumext_multi_set_vskip:` The function `\__enumext_multi_set_vskip:` will take care of determining the “adjusted spaces” that we will apply “above” and “below” the `multcols` environment in `enumext`.

We will set the default values taking into account that  $\TeX$  is in (*horizontal mode*), then we will make the settings for the (*vertical mode*) in which `\partopsep` comes into play.

Set the values of `\__enumext_multicols_above_X_skip` and `\__enumext_multicols_below_X_skip` equal to the value of `\topsep` in the *current level*.

```

824 \cs_new_protected:Nn \__enumext_multi_set_vskip:
825 {
826   \skip_set:cn { \__enumext_multicols_above_ \__enumext_level: } _skip {
827     {
828       \skip_use:c { \__enumext_topsep_ \__enumext_level: } _skip {
829         }
830       \skip_set:cn { \__enumext_multicols_below_ \__enumext_level: } _skip {
831         {
832           \skip_use:c { \__enumext_topsep_ \__enumext_level: } _skip {
833             }
834           \__enumext_add_pre_parsep:
835         }

```

(End of definition for `\__enumext_multi_set_vskip:`)

`\__enumext_add_pre_parsep:` The function `\__enumext_add_pre_parsep:` “adjusted” the value of `\__enumext_multicols_above_X_skip` detecting the value of `\parsep` from the previous level. This is necessary since `\parsep` from the previous level affects the *vertical spaces*.

```

836 \cs_new_protected:Nn \__enumext_add_pre_parsep:
837 {
838   \int_case:nn { \__enumext_level_int }
839   {
840     { 2 }{
841       \skip_if_eq:nnF { \__enumext_parsep_i_skip } { \c_zero_skip } {
842         {
843           \skip_add:Nn \__enumext_multicols_above_ii_skip { \__enumext_parsep_i_skip }
844         }
845       }
846     { 3 }{
847       \skip_if_eq:nnF { \__enumext_parsep_ii_skip } { \c_zero_skip } {
848         {
849           \skip_add:Nn \__enumext_multicols_above_iii_skip { \__enumext_parsep_ii_skip }
850         }
851       }
852     { 4 }{
853       \skip_if_eq:nnF { \__enumext_parsep_iii_skip } { \c_zero_skip } {
854         {
855           \skip_add:Nn \__enumext_multicols_above_iv_skip { \__enumext_parsep_iii_skip }
856         }
857       }

```

```

858     }
859 }

```

(End of definition for `\__enumext_add_pre_parse:`)

`\__enumext_multi_addvspace:` The function `\__enumext_multi_addvspace:` will apply the spaces set using `\addvspace` “above” the `multicols` environment in `enumext`, taking into account whether TeX is in *(horizontal mode)* or *(vertical mode)*.

```

860 \cs_new_protected:Nn \__enumext_multi_addvspace:
861 {
862   \__enumext_multi_set_vskip:
863   \mode_if_vertical:T
864   {
865     \skip_add:cn { \__enumext_multicols_above_ \__enumext_level: _skip }
866     {
867       \skip_use:c { \__enumext_partopsep_ \__enumext_level: _skip }
868     }
869     \skip_add:cn { \__enumext_multicols_below_ \__enumext_level: _skip }
870     {
871       \skip_use:c { \__enumext_partopsep_ \__enumext_level: _skip }
872     }
873   }
874   \par\nopagebreak
875   \addvspace{ \skip_use:c { \__enumext_multicols_above_ \__enumext_level: _skip } }
876 }

```

(End of definition for `\__enumext_multi_addvspace:`)

### 10.18.2 Adjustment of vertical spaces for multicols in keyans

`\__enumext_keyans_multi_set_vskip:` The function `\__enumext_keyans_multi_set_vskip:` will take care of determining the “adjusted spaces” that we will apply “above” and “below” the `multicols` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

`\__enumext_keyans_multi_addvspace:`

```

877 \cs_new_protected:Nn \__enumext_keyans_multi_set_vskip:
878 {
879   \skip_set:Nn \__enumext_multicols_above_v_skip
880   {
881     \__enumext_topsep_v_skip
882   }
883   \skip_set:Nn \__enumext_multicols_below_v_skip
884   {
885     \__enumext_topsep_v_skip
886   }
887 }
888 \cs_new_protected:Nn \__enumext_keyans_multi_addvspace:
889 {
890   \__enumext_keyans_multi_set_vskip:
891   \mode_if_vertical:T
892   {
893     \skip_add:Nn \__enumext_multicols_above_v_skip
894     {
895       \skip_use:N \__enumext_partopsep_v_skip
896     }
897     \skip_add:Nn \__enumext_multicols_below_v_skip
898     {
899       \skip_use:N \__enumext_partopsep_v_skip
900     }
901   }
902   \par\nopagebreak
903   \addvspace{ \__enumext_multicols_above_v_skip }
904 }


```

(End of definition for `\__enumext_keyans_multi_set_vskip:` and `\__enumext_keyans_multi_addvspace:`)

### 10.19 Adjustment of vertical spaces for minipage

When nesting a “list environment” within the `minipage` environment, the values of the “vertical spaces” are lost. Graphically it can be seen like in the figure 8.

Since we want to keep the “left” and “right” environments “aligned on top”, preserving the `\baselineskip` and keep the desired “spaces” (`\topsep` + `[\partopsep]`) it is necessary to “adjust” the “vertical spaces” for `minipage` environments.

Figure 8: Representation of the `minipage` spacing adjustment for a nested level.

Here there are several complications that we must circumvent, the `minipage` environment eliminates the “top” spaces, the `multicols` environment can be nested in the `minipage` environment, the “top” and “bottom” spaces are affected when `topsep=0pt` and to this is added the `\partopsep` parameter that comes into action according to whether  $\TeX$  is in *(horizontal mode)* or *(vertical mode)*. Depending on these cases, small adjustments must be made using `\vspace` and `\addvspace` to obtain the “desired vertical spacing”.

Again I must make clear that the implementation here is a “bit questionable”, but hunting the spaces (glue) produced by the `minipage` environment is quite complicated, even more if `multicols` it is nested. The setting of the values was more “trial and error” (aprox to `\strutbox`), using the help of the `lua-visual-debug`[12] package, again my attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

`__enumext_mini_env*` Creates a `__enumext_mini_env*` environment (custom version of `minipage`) setting the `\if@minipage` switch to “false” to allow spaces at the “above” of the environment, plus we will add `\vspace{0pt}` to maintain alignment on “top”. This environment will be used internally by the `mini-env` key, it is not documented in the user interface and is for internal use only.

```

905 \DeclareDocumentEnvironment{__enumext_mini_env*}{ m }
906 {
907     \__enumext_minipage:w [ t ] { #1 }
908     \legacy_if_gset_false:n { @minipage }
909     \vspace { 0pt }
910 }
911 { \__enumext_endminipage: }
```

(End of definition for `__enumext_mini_env*`.)

#### 10.19.1 Adjustment of vertical spaces for minipage in enumext

`__enumext_mini_set_vskip:` The function `\__enumext_mini_set_vskip:` will take care of determining the “adjust” spaces that we will apply “above” and “below” the `__enumext_mini_env*` environment in `enumext`.

We will set the default values taking into account that  $\TeX$  is in *(horizontal mode)*, then we will make the settings for the *(vertical mode)* in which `\partopsep` comes into play.

First determine if the `multicols` environment is active by comparing the value of the `\l__enumext_columns_X_int` variable handled by the `columns` key, according to this comparison we set the adjusted values for `\l__enumext_minipage_left_skip`, `\l__enumext_minipage_right_skip` and `\l__enumext_minipage_after_skip`.

```

912 \cs_new_protected:Nn \__enumext_mini_set_vskip:
913 {
914     \int_compare:nNnTF
915     { \int_use:c { \l__enumext_columns_ \__enumext_level: _int } } > { 1 }
916     {
```

If `multicols` environment is nested in `__enumext_mini_env*` environment, we will apply a correction factor to the vertical spaces taking into account the value of `\topsep` of the current level and the value of `\partopsep` of the previous level, if these are zero we will use `\strutbox` as the basis for the calculations.

```

917     \skip_if_eq:nnTF
918     { \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip } } { \c_zero_skip }
919     {
920         \skip_set:Nn \l__enumext_minipage_left_skip
921         {
922             -0.150\box_dp:N \strutbox
923         }
924         \skip_set:Nn \l__enumext_minipage_right_skip
925         {
926             0.695\box_dp:N \strutbox
927         }
928         \skip_set:Nn \l__enumext_minipage_after_skip
929         {
930             \box_dp:N \strutbox
931         }
932         \__enumext_zero_parsep:
933     }
```

```

934     {
935         \skip_set:Nn \l__enumext_minipage_left_skip
936         {
937             \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip }
938         }
939         \skip_set:Nn \l__enumext_minipage_right_skip
940         {
941             0.695\box_dp:N \strutbox
942         }
943         \skip_set:Nn \l__enumext_minipage_after_skip
944         {
945             1.85\box_dp:N \strutbox
946             + \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip }
947         }
948     }
949 }
950 {

```

If only `enumext` environment is nested in `__enumext_mini_env*` environment, we will apply a correction factor to the *vertical spaces* taking into account the value of `\topsep`, if this is zero we will use `\strutbox` as the basis for the calculations.

```

951 \skip_if_eq:nnTF
952 { \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip } } { \c_zero_skip }
953 {
954     \skip_set:Nn \l__enumext_minipage_left_skip
955     {
956         0.5\box_dp:N \strutbox
957         - \skip_use:c { \l__enumext_partopsep_ \__enumext_level: _skip }
958     }
959     \skip_set:Nn \l__enumext_minipage_right_skip
960     {
961         \skip_use:c { \l__enumext_partopsep_ \__enumext_level: _skip }
962     }
963     \skip_set:Nn \l__enumext_minipage_after_skip
964     {
965         1.6\box_dp:N \strutbox
966     }
967 }
968 {
969     \skip_set:Nn \l__enumext_minipage_left_skip
970     {
971         0.5875\box_dp:N \strutbox
972         - \skip_use:c { \l__enumext_partopsep_ \__enumext_level: _skip }
973     }
974     \skip_set:Nn \l__enumext_minipage_right_skip
975     {
976         + \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip }
977         + \skip_use:c { \l__enumext_partopsep_ \__enumext_level: _skip }
978     }
979     \skip_set:Nn \l__enumext_minipage_after_skip
980     {
981         0.325\box_dp:N \strutbox
982         + \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip }
983     }
984 }
985 }
986 }

```

(End of definition for `\__enumext_mini_set_vskip:`)

`\__enumext_zero_parsep:` The function `\__enumext_zero_parsep:` “adjusted” the value of `\l__enumext_minipage_after_skip` detecting the value of `\parsep` from the previous level. This is necessary since `\parsep` from the previous level affects the *vertical spaces* and this is noticeable when using the `nosep` or `noitemsep` keys.

```

987 \cs_new_protected:Nn \__enumext_zero_parsep:
988 {
989     \int_case:nn { \l__enumext_level_int }
990     {
991         { 2 }{
992             \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip }
993             {
994                 \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }

```

```

995         }
996     }
997     { 3 }{
998         \skip_if_eq:nnF { \l__enumext_parsep_ii_skip } { \c_zero_skip }
999         {
1000             \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
1001         }
1002     }
1003     { 4 }{
1004         \skip_if_eq:nnF { \l__enumext_parsep_iii_skip } { \c_zero_skip }
1005         {
1006             \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
1007         }
1008     }
1009 }
1010 }

```

(End of definition for `\__enumext_zero_parsep:`.)

`\__enumext_mini_addvspace:` The function `\__enumext_mini_addvspace:` will apply the spaces set using `\addvspace` “above” the `\__enumext_mini_env*` environment in `enumext`, taking into account whether  $\text{\TeX}$  is in *horizontal mode* or *vertical mode*. For the latter we will make some adjustments since the `\partopsep` parameter comes into play and this affects the *vertical spacing*.

```

1011 \cs_new_protected:Nn \__enumext_mini_addvspace:
1012 {
1013     \__enumext_mini_set_vskip:
1014     \mode_if_vertical:T
1015     {
1016         \skip_add:Nn \l__enumext_minipage_left_skip
1017         {
1018             \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1019         }
1020         \skip_add:Nn \l__enumext_minipage_after_skip
1021         {
1022             \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1023         }
1024     }
1025     \par\nopagebreak
1026     \addvspace { \l__enumext_minipage_left_skip }
1027 }

```

(End of definition for `\__enumext_mini_addvspace:`.)

### 10.19.2 Adjustment of vertical spaces for minipage in keyans

`\__enumext_keyans_mini_set_vskip:` The function `\__enumext_keyans_mini_set_vskip:` will take care of determining the “adjusted” spaces that we will apply “above” and “below” the `\__enumext_mini_env*` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

```

1028 \cs_new_protected:Nn \__enumext_keyans_mini_set_vskip:
1029 {
1030     \skip_zero_new:N \l__enumext_minipage_after_skip
1031     \skip_zero_new:N \l__enumext_minipage_left_skip
1032     \skip_zero_new:N \l__enumext_minipage_right_skip
1033     \int_compare:nNnTF { \l__enumext_columns_v_int } > { 1 }
1034     {
1035         \skip_if_eq:nnTF { \l__enumext_topsep_v_skip } { \c_zero_skip }
1036         {
1037             \skip_set:Nn \l__enumext_minipage_left_skip { -0.25\box_dp:N \strutbox }
1038             \skip_set:Nn \l__enumext_minipage_right_skip { 0.705\box_dp:N \strutbox }
1039             \skip_set:Nn \l__enumext_minipage_after_skip { \box_dp:N \strutbox }
1040             \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip }
1041             {
1042                 \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
1043             }
1044         }
1045     }
1046     \skip_set:Nn \l__enumext_minipage_left_skip
1047     {
1048         \skip_use:N \l__enumext_topsep_v_skip
1049     }
1050     \skip_set:Nn \l__enumext_minipage_right_skip

```

```

1051         {
1052             0.705\box_dp:N \strutbox
1053         }
1054         \skip_set:Nn \l__enumext_minipage_after_skip
1055         {
1056             1.85\box_dp:N \strutbox + \l__enumext_topsep_v_skip
1057         }
1058     }
1059 }
1060 {
1061     \skip_if_eq:nnTF { \l__enumext_topsep_v_skip } { \c_zero_skip }
1062     {
1063         \skip_set:Nn \l__enumext_minipage_left_skip
1064         {
1065             0.5\box_dp:N \strutbox
1066             + \l__enumext_partopsep_v_skip
1067         }
1068         \skip_set:Nn \l__enumext_minipage_right_skip
1069         {
1070             \l__enumext_partopsep_v_skip
1071         }
1072         \skip_set:Nn \l__enumext_minipage_after_skip { 1.6\box_dp:N \strutbox }
1073     }
1074     {
1075         \skip_set:Nn \l__enumext_minipage_left_skip
1076         {
1077             0.5875\box_dp:N \strutbox - \l__enumext_partopsep_v_skip
1078         }
1079         \skip_set:Nn \l__enumext_minipage_right_skip
1080         {
1081             \l__enumext_topsep_v_skip + \l__enumext_partopsep_v_skip
1082         }
1083         \skip_set:Nn \l__enumext_minipage_after_skip
1084         {
1085             0.325\box_dp:N \strutbox + \l__enumext_topsep_v_skip
1086         }
1087     }
1088 }
1089 }

```

(End of definition for `\__enumext_keyans_mini_set_vskip:`)

`\__enumext_keyans_mini_addvspace:`

The function `\__enumext_keyans_mini_addvspace:` will apply the spaces set using `\addvspace` “above” the `\__enumext_mini_env*` environment in `keyans`, taking into account whether  $\TeX$  is in *horizontal mode* or *vertical mode*. For the latter we will make some adjustments since the `\partopsep` parameter comes into play and this affects the *vertical spacing*. The implementation of this function is the same as the one used in `enumext`.

```

1090 \cs_new_protected:Nn \__enumext_keyans_mini_addvspace:
1091 {
1092     \__enumext_keyans_mini_set_vskip:
1093     \mode_if_vertical:T
1094     {
1095         \skip_add:Nn \l__enumext_minipage_left_skip
1096         {
1097             \l__enumext_partopsep_v_skip
1098         }
1099         \skip_add:Nn \l__enumext_minipage_after_skip
1100         {
1101             \l__enumext_partopsep_v_skip
1102         }
1103     }
1104     \par\nopagebreak
1105     \addvspace { \l__enumext_minipage_left_skip }
1106 }

```

(End of definition for `\__enumext_keyans_mini_addvspace:`)

### 10.19.3 Adjustment of vertical spaces for minipage in `enumext*` and `keyans*`

`\__enumext_mini_set_vskip_vii:`

`\__enumext_mini_set_vskip_viii:`

The functions `\__enumext_mini_set_vskip_vii:` and `\__enumext_mini_set_vskip_viii:` will take care of determining the “adjusted” spaces that we will apply “above” and “below” the `\__enumext_mini_env*` environment in `enumext*` and `keyans*`.



```

1107 \cs_new_protected:Nn \__enumext_mini_set_vskip_vii:
1108 {
1109   \skip_zero_new:N \l__enumext_minipage_left_skip
1110   \skip_gzero_new:N \g__enumext_minipage_right_skip
1111   \skip_gzero_new:N \g__enumext_minipage_after_skip
1112   \skip_if_eq:nnTF { \l__enumext_topsep_vii_skip } { \c_zero_skip }
1113   {
1114     \skip_set:Nn \l__enumext_minipage_left_skip { 0.5\box_dp:N \strutbox }
1115     \skip_gset:Nn \g__enumext_minipage_right_skip { 0.325\box_dp:N \strutbox }
1116   }
1117   {
1118     \skip_set:Nn \l__enumext_minipage_left_skip { 0.5875\box_dp:N \strutbox }
1119     \skip_gset:Nn \g__enumext_minipage_right_skip
1120       {
1121         \l__enumext_topsep_vii_skip
1122       }
1123     \skip_gset:Nn \g__enumext_minipage_after_skip
1124       {
1125         0.325\box_dp:N \strutbox + \l__enumext_topsep_vii_skip
1126       }
1127   }
1128 }
1129 \cs_new_protected:Nn \__enumext_mini_set_vskip_viii:
1130 {
1131   \skip_zero_new:N \l__enumext_minipage_after_skip
1132   \skip_zero_new:N \l__enumext_minipage_left_skip
1133   \skip_zero_new:N \l__enumext_minipage_right_skip
1134   \skip_if_eq:nnTF { \l__enumext_topsep_viii_skip } { \c_zero_skip }
1135   {
1136     \skip_set:Nn \l__enumext_minipage_left_skip
1137       {
1138         0.5\box_dp:N \strutbox
1139       }
1140     \skip_set:Nn \l__enumext_minipage_right_skip
1141       {
1142         \l__enumext_partopsep_viii_skip
1143       }
1144     \skip_set:Nn \l__enumext_minipage_after_skip
1145       {
1146         1.6\box_dp:N \strutbox
1147       }
1148   }
1149   {
1150     \skip_set:Nn \l__enumext_minipage_left_skip
1151       {
1152         0.5875\box_dp:N \strutbox
1153       }
1154     \skip_set:Nn \l__enumext_minipage_right_skip
1155       {
1156         \l__enumext_topsep_viii_skip
1157       }
1158     \skip_set:Nn \l__enumext_minipage_after_skip
1159       {
1160         0.325\box_dp:N \strutbox + \l__enumext_topsep_viii_skip
1161       }
1162   }
1163 }

```

(End of definition for `\__enumext_mini_set_vskip_vii:` and `\__enumext_mini_set_vskip_viii:`.)

`\__enumext_mini_addvspace_vii:`  
`\__enumext_mini_addvspace_viii:`

The functions `\__enumext_mini_addvspace_vii:` and `\__enumext_mini_addvspace_viii:` will apply the vertical space “only above” the `\__enumext_mini_env*` environment on the *left side* when the `miniright` key is active in the `enumext*` and `keyans*` environments. Here we will NOT take into account whether T<sub>E</sub>X is in *horizontal mode* or *vertical mode*, since `\partopsep` is equal to `0pt` in both environments.

```

1164 \cs_new_protected:Nn \__enumext_mini_addvspace_vii:
1165 {
1166   \__enumext_mini_set_vskip_vii:
1167   \par\nopagebreak
1168   \addvspace { \l__enumext_minipage_left_skip }
1169 }

```

```

1170 \cs_new_protected:Nn \__enumext_mini_addvspace_viii:
1171 {
1172   \__enumext_mini_set_vskip_viii:
1173   \par\nopagebreak
1174   \addvspace { \__enumext_minipage_left_skip }
1175 }

```

(End of definition for \\_\_enumext\_mini\_addvspace\_vii: and \\_\_enumext\_mini\_addvspace\_viii:.)

#### 10.19.4 The command \miniright

The command `\miniright` will close the `__enumext_mini_env*` environment on the “left side”, open the `__enumext_mini_env*` environment on the “right side” adding the *adjusted vertical space*. By default we will add `\centering` when starting the “right side” environment. The *starred version* ‘\*’ inhibits the use of `\centering` command i.e. the usual L<sup>A</sup>T<sub>E</sub>X justification is maintained in the `__enumext_mini_env*` on the “right side”.

`\miniright` First we will perform some checks to prevent the command from being executed outside the `enumext` environment or from being executed inside the `keyanspic` environment, then we call the internal functions for the `enumext` and `keyans` environments.

```

1176 \NewDocumentCommand \miniright { s }
1177 {
1178   \int_compare:nNt { \__enumext_keyans_pic_level_int } = { 1 }
1179   {
1180     \msg_error:nnn { enumext } { wrong-miniright-place }
1181   }
1182   \int_compare:nNt { \__enumext_level_int } = { 0 }
1183   {
1184     \msg_error:nnn { enumext } { wrong-miniright-place }
1185   }
1186   \int_compare:nNtF { \__enumext_keyans_level_int } = { 1 }
1187   {
1188     \__enumext_keyans_mini_right_cmd:n {#1}
1189   }
1190   { \__enumext_mini_right_cmd:n {#1} }
1191 }

```

(End of definition for \miniright. This function is documented on page 9.)

`\__enumext_mini_right_cmd:n`

The function `\__enumext_mini_right_cmd:n` takes as argument the *starred version* ‘\*’ of the `\miniright` command in the `enumext` environment. We check if the `mini-env` key is active via the variable `\__enumext_minipage_right_X_dim`, if so we close the `multicols` environment with the `__enumext-mini_env*` environment on the “left side”, then we open the `__enumext_mini_env*` environment on the “right side”, apply our adjusted “vertical spaces”, followed by adding the `\centering` command when the starred argument ‘\*’ is not present and set zero `\g__enumext_minipage_stat_int`, otherwise we return an error.

```

1192 \cs_new_protected:Npn \__enumext_mini_right_cmd:n #1
1193 {
1194   \dim_compare:nNtF
1195   { \dim_use:c { \__enumext_minipage_right_ \__enumext_level: _dim } } > { \c_zero_dim }
1196   {
1197     \__enumext_multicols_stop:
1198     \end{__enumext_mini_env*}
1199     \hfill
1200     \begin{__enumext_mini_env*}
1201     { \dim_use:c { \__enumext_minipage_right_ \__enumext_level: _dim } }
1202     \par\addvspace { \__enumext_minipage_right_skip }
1203     \bool_if:nF {#1}
1204     {
1205       \centering
1206     }
1207     \int_gzero:N \g__enumext_minipage_stat_int
1208   }
1209   { \msg_error:nnn { enumext } { wrong-miniright-use } }
1210 }

```

(End of definition for \\_\_enumext\_mini\_right\_cmd:n.)

\\\_enumext\_keyans\_mini\_right\_cmd:n

The function \\\_enumext\_keyans\_mini\_right\_cmd:n takes as argument the *starred version* ‘\*’ of the `\\mini\\right` command in the `keyans` environment. The implementation of this function is the same as that of the \\\_enumext\_mini\_right\_cmd:n function of the `enumext` environment.

```

1211 \\cs_new_protected:Npn \\_enumext_keyans_mini_right_cmd:n #1
1212 {
1213   \\dim_compare:nNnTF { \\_enumext_minipage_right_v_dim } > { \\c_zero_dim }
1214   {
1215     \\_enumext_keyans_multicols_stop:
1216     \\end{\\_enumext_mini_env*}
1217     \\hfill
1218     \\begin{\\_enumext_mini_env*}{ \\_enumext_minipage_right_v_dim }
1219     \\par\\addvspace { \\_enumext_minipage_right_skip }
1220     \\bool_if:nF {#1}
1221     {
1222       \\centering
1223     }
1224     \\int_gzero:N \\g__enumext_minipage_stat_int
1225   }
1226   { \\msg_error:nnn { enumext } { wrong-miniright-use } }
1227 }

```

(End of definition for \\\_enumext\_keyans\_mini\_right\_cmd:n.)

## 10.20 Setting above and below keys

While having controlled the *vertical spaces* within the `enumext` and `keyans` environments when using the `columns` or `mini-env` keys, sometimes the “*vertical spaces above*” or “*vertical spaces below*” the environments are not as expected and it is necessary to be able to apply a “*fine correction*” to these. As I have not been able to correct these *glitches*, the best option is to leave a couple of *keys* dedicated to this purpose, in this case it is best to use `\\vspace` or `\\vspace*` when convenient.

above Define above, above\*, below and below\* keys for `enumext` and `keyans` environments.

```

above* 1228 \\cs_set_protected:Npn \\_enumext_tmp:nn #1 #2
below   1229 {
below*  1230   \\keys_define:nn { enumext / #1 }
        1231   {
        1232     above .skip_set:c = { \\_enumext_vspace_above_#2_skip },
        1233     above .value_required:n = true,
        1234     above* .code:n      = \\bool_set_true:c { \\_enumext_vspace_a_star_#2_bool }
        1235                   \\keys_set:nn { enumext / #1 } { above = {##1} },
        1236     above* .value_required:n = true,
        1237     below .skip_set:c = { \\_enumext_vspace_below_#2_skip },
        1238     below .value_required:n = true,
        1239     below* .code:n      = \\bool_set_true:c { \\_enumext_vspace_b_star_#2_bool }
        1240                   \\keys_set:nn { enumext / #1 } { below = {##1} },
        1241     below* .value_required:n = true,
        1242   }
        1243 }
        1244 \\clist_map_inline:Nn \\c__enumext_all_envs_clist { \\_enumext_tmp:nn #1 }

```

(End of definition for above and others.)

### 10.20.1 Functions for above and below keys in enumext

\\\_enumext\_vspace\_above:

The function \\\_enumext\_vspace\_above: apply the *vertical space above* the `enumext` environment set by the `above*` and `above` keys.

```

1245 \\cs_new_protected:Nn \\_enumext_vspace_above:
1246 {
1247   \\skip_if_eq:nnF
1248   { \\skip_use:c { \\_enumext_vspace_above_ \\_enumext_level: _skip } } { \\c_zero_skip }
1249   {
1250     \\bool_if:cTF { \\_enumext_vspace_a_star_ \\_enumext_level: _bool }
1251     {
1252       \\vspace*{ \\skip_use:c { \\_enumext_vspace_above_ \\_enumext_level: _skip } }
1253     }
1254     {
1255       \\vspace { \\skip_use:c { \\_enumext_vspace_above_ \\_enumext_level: _skip } }
1256     }
1257   }
1258 }

```

(End of definition for \\\_enumext\_vspace\_above:.)

`\__enumext_vspace_below`: The function `\__enumext_vspace_below`: apply the *vertical space below* the `enumext` environment set by the `below*` and `below` keys.

```

1259 \cs_new_protected:Nn \__enumext_vspace_below:
1260 {
1261   \skip_if_eq:nnF
1262     { \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } } { \c_zero_skip }
1263   {
1264     \bool_if:cTF { \__enumext_vspace_b_star_ \__enumext_level: _bool }
1265     {
1266       \vspace*{ \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } }
1267     }
1268     {
1269       \vspace { \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } }
1270     }
1271   }
1272 }

```

(End of definition for `\__enumext_vspace_below`.)

### 10.20.2 Functions for above and below keys in keyans

`\__enumext_vspace_above_v`: The function `\__enumext_vspace_above_v`: apply the *vertical space above* the `keyans` environment set by the `above` and `above*` keys.

```

1273 \cs_new_protected:Nn \__enumext_vspace_above_v:
1274 {
1275   \skip_if_eq:nnF { \l__enumext_vspace_above_v_skip } { \c_zero_skip }
1276   {
1277     \bool_if:NTF \l__enumext_vspace_a_star_v_bool
1278     {
1279       \vspace*{ \l__enumext_vspace_above_v_skip }
1280     }
1281     { \vspace { \l__enumext_vspace_above_v_skip } }
1282   }
1283 }

```

(End of definition for `\__enumext_vspace_above_v`.)

`\__enumext_vspace_below_v`: The function `\__enumext_vspace_below_v`: apply the *vertical space below* the `keyans` environment set by the `below*` and `below` keys.

```

1284 \cs_new_protected:Nn \__enumext_vspace_below_v:
1285 {
1286   \skip_if_eq:nnF { \l__enumext_vspace_below_v_skip } { \c_zero_skip }
1287   {
1288     \bool_if:NTF \l__enumext_vspace_b_star_v_bool
1289     {
1290       \vspace*{ \l__enumext_vspace_below_v_skip }
1291     }
1292     { \vspace { \l__enumext_vspace_below_v_skip } }
1293   }
1294 }

```

(End of definition for `\__enumext_vspace_below_v`.)

### 10.20.3 Functions for above and below keys in enumext\* keyans\*

`\__enumext_vspace_above_vii`: The functions `\__enumext_vspace_above_vii`: and `\__enumext_vspace_above_viii`: apply the *vertical space above* the `enumext*` and `keyans*` environments set by the `above` and `above*` keys.

`\__enumext_vspace_above_viii`:

```

1295 \cs_new_protected:Nn \__enumext_vspace_above_vii:
1296 {
1297   \skip_if_eq:nnF { \l__enumext_vspace_above_vii_skip } { \c_zero_skip }
1298   {
1299     \bool_if:NTF \l__enumext_vspace_a_star_vii_bool
1300     {
1301       \vspace*{ \l__enumext_vspace_above_vii_skip }
1302     }
1303     { \vspace { \l__enumext_vspace_above_vii_skip } }
1304   }
1305 }
1306 \cs_new_protected:Nn \__enumext_vspace_above_viii:
1307 {
1308   \skip_if_eq:nnF { \l__enumext_vspace_above_viii_skip } { \c_zero_skip }
1309   {

```

```

1310         \bool_if:NTF \l__enumext_vspace_a_star_viii_bool
1311         {
1312             \vspace*{ \l__enumext_vspace_above_viii_skip }
1313         }
1314         { \vspace { \l__enumext_vspace_above_viii_skip } }
1315     }
1316 }

```

(End of definition for \\_\_enumext\_vspace\_above\_vii: and \\_\_enumext\_vspace\_above\_viii:.)

The functions \\_\_enumext\_vspace\_below\_vii: and \\_\_enumext\_vspace\_below\_viii: apply the *vertical space below* the `enumext*` and `keyans*` environments set by the `below*` and `below` keys.

```

1317 \cs_new_protected:Nn \__enumext_vspace_below_vii:
1318 {
1319     \skip_if_eq:nnF { \l__enumext_vspace_below_vii_skip } { \c_zero_skip }
1320     {
1321         \bool_if:NTF \l__enumext_vspace_b_star_vii_bool
1322         {
1323             \vspace*{ \l__enumext_vspace_below_vii_skip }
1324         }
1325         { \vspace { \l__enumext_vspace_below_vii_skip } }
1326     }
1327 }
1328 \cs_new_protected:Nn \__enumext_vspace_below_viii:
1329 {
1330     \skip_if_eq:nnF { \l__enumext_vspace_below_viii_skip } { \c_zero_skip }
1331     {
1332         \bool_if:NTF \l__enumext_vspace_b_star_viii_bool
1333         {
1334             \vspace*{ \l__enumext_vspace_below_viii_skip }
1335         }
1336         { \vspace { \l__enumext_vspace_below_viii_skip } }
1337     }
1338 }

```

(End of definition for \\_\_enumext\_vspace\_below\_vii: and \\_\_enumext\_vspace\_below\_viii:.)

## 10.21 Setting save-ans and resume keys

The key `save-ans` is directly associated with the key `resume`, this will activate the entire “storage system” in the `enumext` package.

`save-ans` We define the keys `save-ans` and `resume` only for the “first level” of `enumext` and `enumext*`.

```

resume
resume*
1339 \keys_define:nn { enumext / level-1 }
1340 {
1341     save-ans .code:n = \__enumext_storing_set:n {#1},
1342     save-ans .value_required:n = true,
1343     resume .code:n = \__enumext_resume_counter:,
1344     resume .value_forbidden:n = true,
1345     resume* .code:n = \__enumext_resume_counter_star:,
1346     resume* .value_forbidden:n = true,
1347 }
1348 \keys_define:nn { enumext / enumext* }
1349 {
1350     save-ans .code:n = \__enumext_storing_set:n {#1},
1351     save-ans .value_required:n = true,
1352     resume .code:n = \__enumext_resume_counter_vii:,
1353     resume .value_forbidden:n = true,
1354 }

```

(End of definition for `save-ans`, `resume`, and `resume*`.)

`\__enumext_storing_set:n` The function `\__enumext_storing_set:n` executed by the `save-ans` key sets the parameters for the operation of `\anskey`, `keyans` and `keyanspic`. The variable `\l__enumext_store_name_tl` will have the “store name” with which the *⟨sequence⟩* and *⟨prop list⟩* will be created, if it does not exist it will create it globally.

The boolean var `\l__enumext_store_active_bool` will be set to true activating the entire internal *storage mechanism*, then the integer variable for the `resume` key will be created (if not exist), finally the function `\__enumext_check_ans_int:n` will be called to activate the internal mechanism for checking the answers if the boolean variable `\l__enumext_check_ans_bool` set by `check-ans` key are active.

```

1355 \cs_new_protected:Npn \__enumext_storing_set:n #1
1356 {
1357   \tl_set:Nx \l__enumext_store_name_tl {#1}
1358   \prop_if_exist:cF { g__enumext_ \l__enumext_store_name_tl _prop }
1359   {
1360     \prop_new:c { g__enumext_ \l__enumext_store_name_tl _prop }
1361   }
1362   \seq_if_exist:cF { g__enumext_ \l__enumext_store_name_tl _seq }
1363   {
1364     \seq_new:c { g__enumext_ \l__enumext_store_name_tl _seq }
1365   }
1366   \bool_set_true:N \l__enumext_store_active_bool
1367   \bool_set_true:N \l__enumext_store_ans_bool
1368   \int_if_exist:cF { g__enumext_resume_#1_int }
1369   {
1370     \int_new:c { g__enumext_resume_#1_int }
1371   }
1372 }

```

(End of definition for \\_\_enumext\_storing\_set:n.)

\\_\_enumext\_resume\_counter:  
 \\_\_enumext\_resume\_counter\_vii:

The functions \\_\_enumext\_resume\_counter: and \\_\_enumext\_resume\_counter\_vii: used by **resume** key in **enumext** and **enumext\***. If **save-ans** key present then set the start value from integer created by \\_\_enumext\_storing\_set:n.

```

1373 \cs_new_protected:Nn \__enumext_resume_counter:
1374 {
1375   \bool_if:NT \l__enumext_store_active_bool
1376   {
1377     \int_gset:Nn \g__enumext_resume_int
1378     {
1379       \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int }
1380     }
1381   }
1382   \bool_set_true:N \l__enumext_resume_bool
1383 }
1384 \cs_new_protected:Nn \__enumext_resume_counter_vii:
1385 {
1386   \bool_if:NT \l__enumext_store_active_bool
1387   {
1388     \int_gset:Nn \g__enumext_resume_int
1389     {
1390       \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int }
1391     }
1392   }
1393   \bool_set_true:N \l__enumext_resume_vii_bool
1394 }

```

(End of definition for \\_\_enumext\_resume\_counter: and \\_\_enumext\_resume\_counter\_vii:.)

## 10.22 The check answer mechanism

The mechanism for checking that all questions are answered follows this logic:

If the line begins with **\item** or **\item\*** and does NOT *open a nested environment*, each **\item** or **\item\*** must contain a *single* execution of the **\anskey** command, i.e. the counter of the executions of the **\anskey** command must be equal to the counter associated with the sum of executions of **\item** and **\item\***.

If the line begins with **\item** or **\item\*** and *opens a nested environment* each **\item** or **\item\*** in the nested environment must have a *single* execution of the **\anskey** command and the counter associated to the sum of **\item** and **\item\*** executions must decrementing by “one” to maintain equality.

In order for the mechanism for the check-answer to work (not counting **keyans**, **keyans\*** and **keyanspic**) we need:

1. We must keep track of the total number of **\item** and **\item\*** (enumerated) that appear within the environment including the nested levels.
2. We must keep track of the total number of **\item** and **\item\*** (enumerated) that appear per level of nesting.
3. Keeping track of the number of times the environment nests.

The integer variable associated to the sum of each `\item` and `\item*` in the environment `\g__enumext_count_item_number_int` must match the integer variable `\g__enumext_count_item_anskey_int` associated to the execution of the command `\anskey`. We analyze the cases:

- If the list only has one level the number of `\item` + `\item*` = `\anskey`
- If the list has *nested levels*, for each level of nesting we need to decrementing by one (for the `\item` or `\item*` that opens the nest) so that the account remains the same.

With `keyans`, `keyans*` and `keyanspic` it is enough to increase in one the integer of `\anskey`. The integers created must be global if they are not lost in the interior levels of nesting and to execute the test we will use a “hook” function after closing the first level of the environment.

### 10.22.1 Setting check-ans key

Now we define the keys `check-ans` and `no-store` for all levels of `enumext` and `enumext*` environments.

```

check-ans
no-store
1395 \cs_set_protected:Npn \__enumext_tmp:n #1
1396 {
1397   \keys_define:nn { enumext / #1 }
1398   {
1399     check-ans .bool_set:N = \__enumext_check_ans_bool,
1400     check-ans .initial:n = false,
1401     no-store .code:n = {
1402       \bool_set_false:N \__enumext_store_ans_bool
1403       \bool_set_false:N \__enumext_check_ans_bool
1404     },
1405     no-store .value_forbidden:n = true,
1406   }
1407 }
1408 \clist_map_inline:nn
1409 {
1410   level-1, level-2, level-3, level-4, enumext*
1411 }
1412 { \__enumext_tmp:n {#1} }
```

(End of definition for `check-ans` and `no-store`.)

### 10.22.2 Set-up check answer mechanism

`\__enumext_check_ans_set:` The function `\__enumext_check_ans_set:` will adjust the value of the variable `\g__enumext_count_item_number_int` by decrementing its value by one each time you open a nested level `enumext` environment.

```

1413 \cs_new_protected:Nn \__enumext_check_ans_set:
1414 {
1415   \int_case:nn { \__enumext_level_int }
1416   {
1417     { 1 }{
1418       \bool_lazy_all:nT
1419       {
1420         { \bool_if_p:N \g__enumext_starred_bool }
1421         { \int_compare_p:nNn { \__enumext_level_h_int } = { \c_one_int } }
1422       }
1423       {
1424         \int_gdecr:N \g__enumext_count_item_number_int
1425         \typeout{ENUMEXT ~ STANDAR ~ NEEEEEEEEEEEEESTED}
1426       }
1427     }
1428     { 2 }{
1429       \int_gdecr:N \g__enumext_count_item_number_int
1430     }
1431     { 3 }{
1432       \int_gdecr:N \g__enumext_count_item_number_int
1433     }
1434     { 4 }{
1435       \int_gdecr:N \g__enumext_count_item_number_int
1436     }
1437   }
1438   \int_case:nn { \__enumext_level_h_int }
1439   {
1440     { 1 }{
1441       \bool_if:NT \g__enumext_standar_bool
1442       {
1443         \int_gdecr:N \g__enumext_count_item_number_int
1444         \typeout{ENUMEXT ~ STARRED ~ NEEEEEEEEEEEEESTED}

```



```

1445         }
1446     }
1447 }
1448 }

```

(End of definition for `\__enumext_check_ans_set:`.)

`\__enumext_check_ans_exec:` The function `\__enumext_check_ans_exec:` will count the number of times the `\item` and `\item*` commands appears per level within the `enumext` environment. The boolean variable `\l__enumext_store_ans_bool` controlled by the `no-store` key will increment the integer variable of the level counter by 1 to preserve the equality that we will use in the final comparison of the process.

```

1449 \cs_new_protected:Nn \__enumext_check_ans_exec:
1450 {
1451     \bool_if:NT \l__enumext_check_ans_bool
1452     {
1453         \__enumext_check_ans_set:
1454     }
1455 }

```

(End of definition for `\__enumext_check_ans_exec:`.)

`\__enumext_check_ans_show:` The function `\__enumext_check_ans_show:` compares all executions of `\item` and `\item*` with the executions of `\anskey`. After the function is executed, we set the integer variables to zero.

```

1456 \cs_new_protected:Nn \__enumext_check_ans_show:
1457 {
1458     \int_compare:nNnTF
1459     { \g__enumext_count_item_number_int } = { \g__enumext_count_item_anskey_int }
1460     {
1461         \msg_term:nnV { enumext } { items-same-answer } \g__enumext_store_name_tl
1462     }
1463     {
1464         \msg_warning:nnV { enumext } { item-different-answer } \g__enumext_store_name_tl
1465     }
1466     \int_gzero:N \g__enumext_count_item_number_int
1467     \int_gzero:N \g__enumext_count_item_anskey_int
1468 }

```

(End of definition for `\__enumext_check_ans_show:`.)

## 10.23 Keys and functions associated with storage

We add the keys `wrap-ans`, `wrap-opt`, `save-sep`, `mark-ans`, `mark-pos`, `show-ans`, `show-pos`, `mark-ref` and `save-ref` related to the “*storage system*” and internal mechanism of “*label and ref*” only at the *first level* of `enumext` and `enumext*`.

```

1469 \cs_set_protected:Npn \__enumext_tmp:n #1
1470 {
1471     \keys_define:nn { enumext / #1 }
1472     {
1473         wrap-ans .cs_set_protected:Np = \__enumext_anskey_wrapper:n ##1,
1474         wrap-ans .initial:n = \fbox{##1},
1475         wrap-ans .value_required:n = true,
1476         wrap-opt .cs_set_protected:Np = \__enumext_keyans_wrapper_opt:n ##1,
1477         wrap-opt .initial:n = [{##1}],
1478         wrap-opt .value_required:n = true,
1479         save-sep .tl_set:N = \l__enumext_store_keyans_item_opt_sep_tl,
1480         save-sep .initial:n = {, ~ },
1481         save-sep .value_required:n = true,
1482         mark-ans .tl_set:N = \l__enumext_mark_answer_sym_tl,
1483         mark-ans .initial:n = \textasteriskcentered,
1484         mark-ans .value_required:n = true,
1485         mark-pos .choice:,
1486         mark-pos / left .code:n = \str_set:Nn \l__enumext_mark_position_str { l },
1487         mark-pos / right .code:n = \str_set:Nn \l__enumext_mark_position_str { r },
1488         mark-pos .initial:n = right,
1489         mark-pos .value_required:n = true,
1490         show-ans .bool_set:N = \l__enumext_show_answer_bool,
1491         show-ans .initial:n = false,
1492         show-ans .value_required:n = true,
1493         show-pos .bool_set:N = \l__enumext_show_position_bool,
1494         show-pos .initial:n = false,
1495         show-pos .value_required:n = true,

```

```

1496     mark-ref .tl_set:N = \l__enumext_mark_ref_sym_tl,
1497     mark-ref .initial:n = \textasteriskcentered,
1498     mark-ref .value_required:n = true,
1499     save-ref .bool_set:N = \l__enumext_store_ref_key_bool,
1500     save-ref .initial:n = false,
1501     save-ref .value_required:n = true,
1502   }
1503 }
1504 \clist_map_inline:nn { level-1, enumext* } { \l__enumext_tmp:n {#1} }

```

(End of definition for wrap-ans and others.)

mark-pos For the **keyans** and **keyans\*** environments we will only add the keys mark-pos, show-ans and show-  
show-ans pos.

```

1505 \cs_set_protected:Npn \l__enumext_tmp:n #1
1506 {
1507   \keys_define:nn { enumext / #1 }
1508   {
1509     mark-pos .choice:,
1510     mark-pos / left .code:n = \str_set:Nn \l__enumext_mark_position_str { l },
1511     mark-pos / right .code:n = \str_set:Nn \l__enumext_mark_position_str { r },
1512     mark-pos .initial:n = right,
1513     mark-pos .value_required:n = true,
1514     show-ans .bool_set:N = \l__enumext_show_answer_bool,
1515     show-ans .initial:n = false,
1516     show-ans .value_required:n = true,
1517     show-pos .bool_set:N = \l__enumext_show_position_bool,
1518     show-pos .initial:n = false,
1519     show-pos .value_required:n = true,
1520   }
1521 }
1522 \clist_map_inline:nn { keyans, keyans* } { \l__enumext_tmp:n {#1} }

```

(End of definition for mark-pos and show-ans.)

columns\* For the **enumext** and **enumext\*** environments we will only add the keys **columns\*** and **columns-sep\***.  
columns-sep\* The values set by these keys will be passed as optional arguments to the “inner levels” of the **enumext** and **enumext\*** environments via the `\l__enumext_store_level_open:` function used by the “storage system” to preserve the structure and then used by the `\printkeyans` command.

```

1523 \cs_set_protected:Npn \l__enumext_tmp:nn #1 #2
1524 {
1525   \keys_define:nn { enumext / #1 }
1526   {
1527     columns* .code:n = \bool_set_true:c { l__enumext_store_columns_#2_bool }
1528               \int_set:cn { l__enumext_store_columns_#2_int } {##1}
1529               \tl_put_right:ce { l__enumext_store_opt_#2_tl }
1530               {
1531                 columns = \exp_not:v { l__enumext_store_columns_#2_int },
1532               },
1533     columns* .value_required:n = true,
1534     columns-sep* .code:n = \bool_set_true:c { l__enumext_store_columns_sep_#2_bool }
1535               \dim_set:cn { l__enumext_store_columns_sep_#2_dim } {##1}
1536               \tl_put_right:ce { l__enumext_store_opt_#2_tl }
1537               {
1538                 columns-sep = \exp_not:v { l__enumext_store_columns_sep_#2_dim },
1539               },
1540     columns-sep* .value_required:n = true,
1541   }
1542 }
1543 \clist_map_inline:nn
1544 {
1545   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {enumext*}{vii}
1546 }
1547 { \l__enumext_tmp:nn #1 }

```

(End of definition for columns\* and columns-sep\*.)

### 10.23.1 Function for storing content in prop list

```
\__enumext_store_addto_prop:n
\__enumext_store_addto_prop:V
```

The function `\__enumext_store_addto_prop:n` stores the content in *⟨prop list⟩* defined by `save-ans` key. The “stored content” is retrieved by means of the `\getkeyans` command.

The form in which the content is “stored” in the *⟨prop list⟩* is  $\{\langle position \rangle\}\{\langle content \rangle\}$ . This function is used by `\anskey` in `enumext` and `enumext*` environments, `\item*` in `keyans` and `keyans*` environments and `\anspic` in `keyanspic` environment.

```
1548 \cs_generate_variant:Nn \prop_gput_if_not_in:Nnn { cen }
1549 \cs_new_protected:Npn \__enumext_store_addto_prop:n #1
1550 {
1551   \prop_gput_if_not_in:cen { g__enumext_ \l__enumext_store_name_tl _prop }
1552   {
1553     \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } + 1 }
1554   }
1555   { #1 }
1556 }
1557 \cs_generate_variant:Nn \__enumext_store_addto_prop:n { V }
```

(End of definition for `\__enumext_store_addto_prop:n`.)

### 10.23.2 Function for storing content in sequence

```
\__enumext_store_addto_seq:n
\__enumext_store_addto_seq:v
\__enumext_store_addto_seq:V
```

The function `\__enumext_store_addto_seq:n` stores the content in *⟨sequence⟩* defined by `save-ans` key. This function is used by `\anskey` in `enumext`, `\item*` in `keyans` and `\anspic` in `keyanspic`.

The form in which the content is stored in *⟨sequence⟩* is in a internal `enumext` or `enumext*` environments with the *same structure* in which the command was executed.

The “stored content” is retrieved by means of the `\printkeyans` command.

```
1558 \cs_new_protected:Npn \__enumext_store_addto_seq:n #1
1559 {
1560   \seq_gput_right:cn { g__enumext_ \l__enumext_store_name_tl _seq } { #1 }
1561 }
1562 \cs_generate_variant:Nn \__enumext_store_addto_seq:n { v, V }
```

(End of definition for `\__enumext_store_addto_seq:n`.)

### 10.23.3 Functions for storing the list structure in the sequence

```
\__enumext_store_level_open:
\__enumext_store_level_close:
```

The memorization structure of the list is handled by the functions `\__enumext_store_level_open:` and `\__enumext_store_level_close:` which are executed per level within the `enumext` environment. As this structure will be stored in the sequence set by the `save-ans` key, we will not be able to modify it locally, so it is better to take only two copies of the values set by the `columns` and `columns-sep` keys if they are present when changing levels within the `enumext` environment when executing `\anskey`. We will store these values in the variable `\l__enumext_store_columns_X_tl` if they are different from `0` and `0pt` and pass them as an optional argument to the environment stored in the sequence `enumext`.

```
1563 \cs_new_protected:Nn \__enumext_store_level_open:
1564 {
1565   \bool_if:NT \l__enumext_store_ans_bool
1566   {
1567     \tl_if_empty:cTF { l__enumext_store_opt_ \__enumext_level: _tl }
1568     {
1569       \__enumext_store_addto_seq:n
1570       {
1571         \item \begin{enumext}
1572       }
1573     }
1574     {
1575       \tl_put_left:cn { l__enumext_store_opt_ \__enumext_level: _tl }
1576       {
1577         \item \begin{enumext} [
1578       }
1579       \tl_put_right:cn { l__enumext_store_opt_ \__enumext_level: _tl }
1580       {
1581         ]
1582       }
1583       \__enumext_store_addto_seq:v { l__enumext_store_opt_ \__enumext_level: _tl }
1584     }
1585   }
1586 }
1587 \cs_new_protected:Nn \__enumext_store_level_close:
1588 {
1589   \bool_if:NT \l__enumext_store_ans_bool
1590   {
```

```

1591     \__enumext_store_addto_seq:n { \end{enumext} }
1592   }
1593 }

```

(End of definition for \\_\_enumext\_store\_level\_open: and \\_\_enumext\_store\_level\_close:.)

```

\__enumext_store_level_open_vii:
\__enumext_store_level_close_vii:

```

When nesting the `enumext*` environment in `enumext` starting right after `\item` (without material between them) there is a problem with the alignment of the labels with the baseline between the two environments. One way to get around this problem is to place `\mode_leave_vertical:` and then apply `\vspace` taking into account `\baselineskip`, the value of `\parsep` of the current level of `enumext` and the value of `\topsep` of the `enumext*` environment.

```

1594 \cs_new_protected:Nn \__enumext_store_level_open_vii:
1595 {
1596   \bool_if:NT \l__enumext_store_ans_bool
1597   {
1598     \tl_if_empty:NTF \l__enumext_store_opt_vii_tl
1599     {
1600       \__enumext_store_addto_seq:n
1601       {
1602         \item \mode_leave_vertical:
1603         \vspace { -\skip_eval:n { \baselineskip + \parsep } }
1604         \begin{enumext*}[before={\setlength{\topsep}{\opt}},]
1605       }
1606     }
1607     {
1608       \tl_put_left:Nn \l__enumext_store_opt_vii_tl
1609       {
1610         \item \mode_leave_vertical:
1611         \vspace { -\skip_eval:n { \baselineskip + \parsep } }
1612         \begin{enumext*}[before={\setlength{\topsep}{\opt}},
1613       ]
1614       \tl_put_right:Nn \l__enumext_store_opt_vii_tl
1615       {
1616     ]
1617     }
1618     \__enumext_store_addto_seq:V \l__enumext_store_opt_vii_tl
1619   }
1620 }
1621 }
1622 \cs_new_protected:Nn \__enumext_store_level_close_vii:
1623 {
1624   \bool_if:NT \l__enumext_store_ans_bool
1625   {
1626     \__enumext_store_addto_seq:n { \end{enumext*} }
1627   }
1628 }

```

(End of definition for \\_\_enumext\_store\_level\_open\_vii: and \\_\_enumext\_store\_level\_close\_vii:.)

#### 10.23.4 Function for show marks and position

```

\__enumext_print_keyans_box:NN
\__enumext_print_keyans_box:cc

```

The function `\__enumext_print_keyans_box:NN` print a box in the left margin with `\l__enumext_mark_answer_sym_tl` used by the `wrap-ans`, `show-ans` and `show-pos` keys. The function takes two arguments:

**#1:** `\l__enumext_labelwidth_X_dim`  
**#2:** `\l__enumext_labelsep_X_dim`

```

1629 \cs_new_protected:Nn \__enumext_print_keyans_box:NN
1630 {
1631   \mode_leave_vertical:
1632   \skip_horizontal:n { -\dim_use:N #2 }
1633   \makebox[\opt][ r ]
1634   {
1635     \makebox[ \dim_use:N #1 ][ \l__enumext_mark_position_str ]
1636     {
1637       \tl_use:N \l__enumext_mark_answer_sym_tl
1638     }
1639   }
1640   \skip_horizontal:n { \dim_use:N #2 }
1641 }
1642 \cs_generate_variant:Nn \__enumext_print_keyans_box:NN { cc }

```

(End of definition for \\_\_enumext\_print\_keyans\_box:NN.)

## 10.24 The command `\anskey` and internal label and ref

Since we will be “*storing content*” in a list environment within `\sequences` and can (more or less) manage the options passed to each level, it is necessary that we have a little more control over `\item` when storing. The `\anskey` command will cover this point and give it very similar behaviour to that of `\item` in the `enumext` and `enumext*` environments.

`\anskey` We want the command to be executed as follows: `\anskey(\langle number \rangle)*[\langle key = val \rangle]{\langle content \rangle}` so first we’ll add the keys `item-sym*`, `item-pos*` and `store-brk`.

```

1643 \keys_define:nn { enumext / anskey }
1644 {
1645   item-sym* .tl_set:N = \l__enumext_store_item_symbol_tl,
1646   item-sym* .value_required:n = true,
1647   item-pos* .dim_set:N = \l__enumext_store_item_symbol_sep_dim,
1648   item-pos* .value_required:n = true,
1649   store-brk .bool_set:N = \l__enumext_store_columns_break_bool,
1650   store-brk .default:n = true,
1651   store-brk .value_forbidden:n = true,
1652 }

```

This command `\anskey` will only be present when using the `save-ans` key in `enumext` and `enumext*` environments, otherwise it will return an error. If the `check-ans` key is active, increment `\g__enumext_count_item_with_ans_int`, then call internal function `\__enumext_store_anskey_code:nnnn` will “*store content*” in the `\sequence` and in the `\prop list`.

```

1653 \NewDocumentCommand \anskey { d() s o +m }
1654 {
1655   \bool_if:NF \l__enumext_store_active_bool
1656   {
1657     \msg_error:nnnn { enumext } { anskey-wrong-place } { anskey } { enumext }
1658   }
1659   \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
1660   {
1661     \msg_error:nnnn { enumext } { command-wrong-place } { anskey } { keyans }
1662   }
1663   \int_compare:nNnT { \l__enumext_keyans_pic_level_int } = { 1 }
1664   {
1665     \msg_error:nnnn { enumext } { command-wrong-place } { anskey } { keyanspic }
1666   }
1667   \group_begin:
1668     \bool_if:NT \l__enumext_store_ans_bool
1669     {
1670       \bool_if:NT \l__enumext_check_ans_bool
1671       {
1672         \int_gincr:N \g__enumext_count_item_anskey_int
1673       }
1674       \__enumext_store_anskey_code:nnnn {#1} {#2} {#3} {#4}
1675     }
1676   \group_end:
1677 }

```

(End of definition for `\anskey`. This function is documented on page 10.)

`\__enumext_store_anskey_code:nnnn`

The internal function `\__enumext_store_anskey_code:nnnn` first we pass the command `\argument` to the `\prop list`, then checks the state of the variable `\l__enumext_store_ref_key_bool` handled by the `save-ref` key and will call the function `\__enumext_store_internal_ref:` for the internal “*label and ref*” system. Followed by this if the `show-ans` or `show-pos` keys are active we will show the “*wrapped*” `\argument` passed to the command.

```

1678 \cs_new_protected:Npn \__enumext_store_anskey_code:nnnn #1 #2 #3 #4
1679 {
1680   \__enumext_store_addto_prop:n {#4}
1681   \bool_if:NT \l__enumext_store_ref_key_bool
1682   {
1683     \__enumext_store_internal_ref:
1684   }
1685   \__enumext_store_anskey_show_left:n { #4 }

```

Now we start processing the optional arguments passed to the command to build our `\item` in the variable `\l__enumext_store_anskey_arg_tl` which we will “*store*” in the `\sequence`. First we clear the variable `\l__enumext_store_anskey_arg_tl` and process `[\langle key = val \rangle]`, if the `store-brk` key is present and the command is running under `enumext` (not in the starred version) we will add `\columnbreak` and then `\item`.

```

1686 \tl_clear:N \l__enumext_store_anskey_arg_tl
1687 \tl_if_novalue:nF {#3}
1688 {
1689     \keys_set:nn { enumext / anskey } {#3}
1690 }
1691 \bool_lazy_and:nnT
1692 { \bool_if_p:N \l__enumext_store_columns_break_bool }
1693 { \bool_not_p:n { \l__enumext_starred_bool } }
1694 {
1695     \tl_put_left:Nn \l__enumext_store_anskey_arg_tl { \columnbreak }
1696 }
1697 \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { \item }

```

Now we will check the (*number*) argument and add it to `\l__enumext_store_anskey_arg_tl` if the command is running under `enumext*` (starred version).

```

1698 \tl_if_novalue:nF {#1}
1699 {
1700     \int_set:Nn \l__enumext_store_columns_join_int {#1}
1701     \bool_if:NT \l__enumext_starred_bool
1702     {
1703         \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
1704         {
1705             ( \exp_not:V \l__enumext_store_columns_join_int )
1706         }
1707     }
1708 }

```

And now we will review the starred argument `*` together with the keys `item-sym*` and `item-pos*` and pass them to `\l__enumext_store_anskey_arg_tl`.

```

1709 \bool_if:nTF {#2}
1710 {
1711     \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { * }
1712     \tl_if_empty:NF \l__enumext_store_item_symbol_tl
1713     {
1714         \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
1715         {
1716             [ \exp_not:V \l__enumext_store_item_symbol_tl ]
1717         }
1718     }
1719     \dim_compare:nT
1720     {
1721         \l__enumext_store_item_symbol_sep_dim != \c_zero_dim
1722     }
1723     {
1724         \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
1725         {
1726             [ \exp_not:V \l__enumext_store_item_symbol_sep_dim ]
1727         }
1728     }
1729     \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#4}
1730 }
1731 {
1732     \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#4}
1733 }

```

Finally we check if the `save-ref` key is active along with the `hyperref` package load, if both conditions are met, it will create the `\hyperlink` and then store in (*sequence*).

```

1734 \bool_lazy_and:nnT
1735 { \bool_if_p:N \l__enumext_store_ref_key_bool }
1736 { \bool_if_p:N \l__enumext_hyperref_bool }
1737 {
1738     \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
1739     {
1740         \hfill \exp_not:N \hyperlink { \exp_not:V \l__enumext_newlabel_arg_one_tl }
1741         { \exp_not:V \l__enumext_mark_ref_sym_tl }
1742     }
1743 }
1744 \l__enumext_store_addto_seq:V \l__enumext_store_anskey_arg_tl
1745 }

```

(End of definition for `\l__enumext_store_anskey_code:nnnn`.)

`\__enumext_store_internal_ref:` The function `\__enumext_store_internal_ref:` handles the internal “*label and ref*” system used by the `save-ref` and `mark-ref` keys for `\anskey` will allow to execute `\ref{\<store name>:\<position>}` and will return `1.(a).i.A`.

First we will remove the dots “.” from the current `\labels`, we do not want to get double dots in our references, then we will place this in the variable `\__enumext_newlabel_arg_two_tl`.

```

1746 \cs_new_protected:Nn \__enumext_store_internal_ref:
1747 {
1748   \cs_set_protected:Npn \__enumext_tmp:n ##1
1749   {
1750     \tl_set_eq:cc { \__enumext_label_copy_##1_tl } { \__enumext_label_##1_tl }
1751     \tl_reverse:c { \__enumext_label_copy_##1_tl }
1752     \tl_remove_once:cn { \__enumext_label_copy_##1_tl } { . }
1753     \tl_reverse:c { \__enumext_label_copy_##1_tl }
1754   }
1755   \clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {##1} }
1756   \cs_set:Npn \__enumext_tmp:n ##1
1757   { . \tl_use:c { \__enumext_label_copy_ \int_to_roman:n {##1} _tl } }

```

Here we need to analyse the cases where the environment is started with `enumext*` and if `\anskey` is running alone in it or if it is running in a nested `enumext` environment within the starting environment.

```

1758   \bool_lazy_all:nT
1759   {
1760     { \bool_if_p:N \g__enumext_starred_bool }
1761     { \int_compare_p:nNn { \__enumext_level_int } = { \c_zero_int } }
1762   }
1763   {
1764     \tl_put_right:Ne \__enumext_newlabel_arg_two_tl
1765     { \tl_use:N \__enumext_label_copy_vii_tl }
1766   }
1767   \bool_lazy_all:nT
1768   {
1769     { \bool_if_p:N \l__enumext_standar_bool }
1770     { \bool_if_p:N \g__enumext_starred_bool }
1771     { \int_compare_p:nNn { \__enumext_level_int } > { \c_zero_int } }
1772   }
1773   {
1774     \tl_put_right:Ne \__enumext_newlabel_arg_two_tl
1775     {
1776       \tl_use:N \__enumext_label_copy_vii_tl
1777       \int_step_function:nnN { 1 } { \__enumext_level_int } \__enumext_tmp:n
1778     }
1779   }

```

If started with `enumext` and if `\anskey` is running alone in it or if it is running in a nested `enumext*` environment within the starting environment.

```

1780   \bool_lazy_all:nT
1781   {
1782     { \bool_if_p:N \l__enumext_standar_bool }
1783     { \int_compare_p:nNn { \__enumext_level_int } > { \c_zero_int } }
1784     { \int_compare_p:nNn { \__enumext_level_h_int } = { \c_zero_int } }
1785     { \bool_not_p:n { \__enumext_starred_bool } }
1786   }
1787   {
1788     \tl_put_right:Ne \__enumext_newlabel_arg_two_tl
1789     {
1790       \tl_use:N \__enumext_label_copy_i_tl
1791       \int_step_function:nnN { 2 } { \__enumext_level_int } \__enumext_tmp:n
1792     }
1793   }
1794   \cs_set:Npn \__enumext_tmp:n ##1
1795   { \tl_use:c { \__enumext_label_copy_ \int_to_roman:n {##1} _tl } }
1796   \bool_lazy_all:nT
1797   {
1798     { \bool_if_p:N \l__enumext_standar_bool }
1799     { \int_compare_p:nNn { \__enumext_level_int } > { \c_zero_int } }
1800     { \bool_not_p:n { \g__enumext_starred_bool } }
1801     { \int_compare_p:nNn { \__enumext_level_h_int } > { \c_zero_int } }
1802   }
1803   {
1804     \tl_put_right:Ne \__enumext_newlabel_arg_two_tl
1805     {

```



```

1806         \int_step_function:nnN { 1 } { \l__enumext_level_int } \l__enumext_tmp:n
1807         . \tl_use:N \l__enumext_label_copy_vii_tl
1808     }
1809 }

```

Now we set the variable `\l__enumext_newlabel_arg_one_tl` which will contain  $\langle \textit{store name} : \textit{position} \rangle$ .

```

1810     \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
1811     {
1812         \l__enumext_store_name_tl \c_colon_str
1813         \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
1814     }

```

Now execute the function `\l__enumext_newlabel:nn` and save the result in the variable `\l__enumext_store_write_aux_file_tl` and finally we write in the `.aux` file.

```

1815     \tl_put_right:Ne \l__enumext_store_write_aux_file_tl
1816     {
1817         \l__enumext_newlabel:nn
1818         { \exp_not:V \l__enumext_newlabel_arg_one_tl }
1819         { \l__enumext_newlabel_arg_two_tl }
1820     }
1821     \l__enumext_store_write_aux_file_tl
1822 }

```

(End of definition for `\l__enumext_store_internal_ref:.`)

`\l__enumext_store_anskey_show_wrap:n`

The function `\l__enumext_store_anskey_show_wrap:n` “wraps” the  $\langle \textit{argument} \rangle$  passed to `\anskey` when using the `wrap-ans` key.

```

1823 \cs_new_protected:Npn \l__enumext_store_anskey_show_wrap:n #1
1824 {
1825     \par
1826     \bool_if:NT \l__enumext_starred_bool
1827     {
1828         \cs_set:Nn \l__enumext_level: { vii }
1829     }
1830     \l__enumext_print_keyans_box:cc
1831     { \l__enumext_labelwidth_ \l__enumext_level: _dim }
1832     { \l__enumext_labelsep_ \l__enumext_level: _dim }
1833     \l__enumext_anskey_wrapper:n { #1 }
1834 }

```

(End of definition for `\l__enumext_store_anskey_show_wrap:n`.)

`\l__enumext_store_anskey_show_left:n`

The function `\l__enumext_store_anskey_show_left:n` will show the “mark” defined by the `mark-ans` key or the “position” of the content stored in the  $\langle \textit{prop list} \rangle$  when using the `show-pos` key on the left margin next to the “wraps”  $\langle \textit{argument} \rangle$  passed to `\anskey` on the right side when using the `show-ans` key.

```

1835 \cs_new_protected:Npn \l__enumext_store_anskey_show_left:n #1
1836 {
1837     \bool_if:NT \l__enumext_show_answer_bool
1838     {
1839         \l__enumext_store_anskey_show_wrap:n { #1 }
1840     }
1841     \bool_if:NT \l__enumext_show_position_bool
1842     {
1843         \tl_set:Ne \l__enumext_mark_answer_sym_tl
1844         {
1845             \group_begin:
1846             \exp_not:N \normalfont
1847             \exp_not:N \footnotesize [ \int_eval:n
1848             {
1849                 \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
1850             }
1851             ]
1852             \group_end:
1853         }
1854         \l__enumext_store_anskey_show_wrap:n { #1 }
1855     }
1856 }

```

(End of definition for `\l__enumext_store_anskey_show_left:n`.)

## 10.25 Common functions for keyans, keyans\* and keyanspic

### 10.25.1 Storing content in prop list

`\__enumext_keyans_addto_prop:n`

The function `\__enumext_keyans_addto_prop:n` will pass the contents of the current  $\langle label \rangle$  `\__enumext_label_v_tl` for the `keyans` environment and the current  $\langle label \rangle$  `\__enumext_label_vi_tl` for the `keyanspic` environment when using `\item*` and `\anspic*`, followed by the *contents* of the optional argument of both commands to the `\__enumext_store_keyans_label_tl` variable, which will be passed to the  $\langle prop list \rangle$  defined by the `save-ans` key using the `\__enumext_store_addto_prop:V`.

```

1857 \cs_new_protected:Npn \__enumext_keyans_addto_prop:n #1
1858 {
1859   \tl_clear:N \__enumext_store_keyans_label_tl
1860   \int_compare:nNnTF { \__enumext_keyans_pic_level_int } = { 1 }
1861   {
1862     \tl_put_right:Ne \__enumext_store_keyans_label_tl { \__enumext_label_vi_tl }
1863   }
1864   {
1865     \tl_put_right:Ne \__enumext_store_keyans_label_tl { \__enumext_label_v_tl }
1866   }
1867   \tl_if_novalue:nF { #1 }
1868   {
1869     % Set save-sep
1870     \tl_if_empty:NF \__enumext_store_keyans_item_opt_sep_tl
1871     {
1872       \tl_put_right:Ne \__enumext_store_keyans_label_tl { \__enumext_store_keyans_item_opt_sep_tl }
1873     }
1874     \tl_put_right:Ne \__enumext_store_keyans_label_tl { #1 }
1875   }
1876   \__enumext_store_addto_prop:V \__enumext_store_keyans_label_tl
1877 }

```

(End of definition for `\__enumext_keyans_addto_prop:n`.)

### 10.25.2 The save-ref key for keyans, keyans\* and keyanspic

The internal “*label and ref*” system for the `keyans`, `keyans*` and `keyanspic` environments has slight differences with the one implemented for the `\anskey` command, basically because in this environments we are interested in the current  $\langle label \rangle$ . The mechanism defined here will allow to execute `\ref{⟨store name : position⟩}` and will return `1. (A)`.

`\__enumext_keyans_store_ref:`  
`\__enumext_keyans_store_ref_aux_i:`  
`\__enumext_keyans_store_ref_aux_ii:`

The function `\__enumext_keyans_store_ref:` handles the internal “*label and ref*” system used by the `save-ref` key for `\item*` and `\anspic*` commands. First we will create copies of the current  $\langle labels \rangle$  and remove the dots “.” from them, we do not want to get double dots in our references.

```

1878 \cs_new_protected:Nn \__enumext_keyans_store_ref:
1879 {
1880   \bool_if:NT \__enumext_store_ref_key_bool
1881   {
1882     \cs_set_protected:Npn \__enumext_tmp:n ##1
1883     {
1884       \tl_set_eq:cc { \__enumext_label_copy_##1_tl } { \__enumext_label_##1_tl }
1885       \tl_reverse:c { \__enumext_label_copy_##1_tl }
1886       \tl_remove_once:cn { \__enumext_label_copy_##1_tl } { . }
1887       \tl_reverse:c { \__enumext_label_copy_##1_tl }
1888     }
1889     \clist_map_inline:nn { i, v, vi, vii, viii } { \__enumext_tmp:n {##1} }
1890     \__enumext_keyans_store_ref_aux_i:
1891   }
1892 }

```

The auxiliary function `\__enumext_keyans_store_ref_aux_i:` set the variable `\__enumext_newlabel_arg_one_tl` which will contain  $\{ \langle store name : position \rangle \}$  analyzing whether the environment in which they are executed is `enumext*` or `enumext`.

```

1893 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_i:
1894 {
1895   \bool_if:NT \g__enumext_starred_bool
1896   {
1897     \tl_set_eq:NN \__enumext_label_copy_i_tl \__enumext_label_copy_vii_tl
1898   }
1899   \int_compare:nNnT { \__enumext_keyans_pic_level_int } = { 1 }
1900   {
1901     \tl_put_right:Ne \__enumext_newlabel_arg_two_tl

```

```

1902         { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_vi_tl }
1903     }
1904     \int_compare:nNt { \l__enumext_keyans_level_int } = { 1 }
1905     {
1906         \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
1907         { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_v_tl }
1908     }
1909     \int_compare:nNt { \l__enumext_keyans_level_h_int } = { 1 }
1910     {
1911         \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
1912         { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_viii_tl }
1913     }
1914     \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
1915     {
1916         \l__enumext_store_name_tl \c_colon_str
1917         \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
1918     }
1919     \__enumext_keyans_store_ref_aux_ii:
1920 }

```

Now auxiliary function `\__enumext_keyans_store_ref_aux_ii:` save the result in the variable `\l__enumext_store_write_aux_file_tl` and finally we write in the `.aux` file.

```

1921 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_ii:
1922 {
1923     \tl_put_right:Ne \l__enumext_store_write_aux_file_tl
1924     {
1925         \__enumext_newlabel:nn
1926         { \exp_not:V \l__enumext_newlabel_arg_one_tl }
1927         { \l__enumext_newlabel_arg_two_tl }
1928     }
1929     \l__enumext_store_write_aux_file_tl
1930 }

```

(End of definition for `\__enumext_keyans_store_ref:`, `\__enumext_keyans_store_ref_aux_i:`, and `\__enumext_keyans_store_ref_aux_ii:`.)

### 10.25.3 Storing content in sequence

`\__enumext_keyans_addto_seq:n`  
`\__enumext_keyans_addto_seq_link:`

The function `\__enumext_keyans_addto_seq:n` will pass the contents of the current *⟨label⟩* `\l__enumext_label_v_tl` for the `keyans` environment and the `\l__enumext_label_vi_tl` for the `keyanspic` environment when using `\item*` and `\anspic*`, followed by the *⟨contents⟩* of the optional argument of both commands to the `\l__enumext_store_keyans_label_tl` variable to the sequence defined by the `save-ans` key.

```

1931 \cs_new_protected:Npn \__enumext_keyans_addto_seq:n #1
1932 {
1933     \tl_clear:N \l__enumext_store_keyans_label_tl
1934     \int_compare:nNtF { \l__enumext_keyans_pic_level_int } = { 1 }
1935     {
1936         \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \item \l__enumext_label_vi_tl }
1937     }
1938     {
1939         \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \item \l__enumext_label_v_tl }
1940     }
1941     \tl_if_novalue:nF { #1 }
1942     {
1943         \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_tl
1944         {
1945             \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \l__enumext_store_keyans_item_opt_sep_tl }
1946         }
1947         \tl_put_right:Ne \l__enumext_store_keyans_label_tl { #1 }
1948     }
1949     \__enumext_keyans_addto_seq_link:
1950 }

```

Checks if the `save-ref` key is active along with the `hyperref` package load, if both conditions are met, it will create the `\hyperlink` and then store using the `\__enumext_store_addto_seq:V` function. Finally, copy the contents of the variable `\l__enumext_store_keyans_label_tl` into the global variable `\g__enumext_check_ans_item_tl` to be used by the function `\__enumext_keyans_check_ans:nn` and increment the value of the integer variable `\g__enumext_count_item_anskey_int` handled by the `check-ans` key.

```

1951 \cs_new_protected:Nn \__enumext_keyans_addto_seq_link:
1952 {

```

```

1953 \bool_lazy_and:nnT
1954 { \bool_if_p:N \l__enumext_store_ref_key_bool }
1955 { \bool_if_p:N \l__enumext_hyperref_bool }
1956 {
1957   \tl_put_right:Ne \l__enumext_store_keyans_label_tl
1958   {
1959     \hfill \exp_not:N \hyperlink
1960     {
1961       \exp_not:V \l__enumext_newlabel_arg_one_tl
1962     }
1963     { \exp_not:V \l__enumext_mark_ref_sym_tl }
1964   }
1965 }
1966 \__enumext_store_addto_seq:V \l__enumext_store_keyans_label_tl
1967 \tl_gset:NV \g__enumext_check_ans_item_tl \l__enumext_store_keyans_label_tl
1968 \bool_if:NT \l__enumext_check_ans_bool
1969 {
1970   \int_gincr:N \g__enumext_count_item_anskey_int
1971 }
1972 }

```

(End of definition for `\__enumext_keyans_addto_seq:n` and `\__enumext_keyans_addto_seq_link:.`)

#### 10.25.4 Check for starred commands

`\__enumext_keyans_check_ans:nn`

The function `\__enumext_keyans_check_ans:nn` performs an extra check for the `keyans` and `keyanspic` environments. Unlike the check executed by `check-ans` key this one is not controlled by any key, it is intended to prevent the forgetting of `\item*` or `\anspic*` in these environments.

```

1973 \cs_new_protected:Npn \__enumext_keyans_check_ans:nn #1 #2
1974 {
1975   \tl_if_empty:NTF \g__enumext_check_ans_item_tl
1976   {
1977     \msg_warning:nnnn { enumext } { missing-starred }{ #1 }{ #2 }
1978   }
1979   { \tl_gclear:N \g__enumext_check_ans_item_tl }
1980 }

```

(End of definition for `\__enumext_keyans_check_ans:nn`.)

#### 10.25.5 The show-ans and show-pos keys for keyans and keyanspic

The code is very similar to the `\anskey` code, but, if I change the order of the operations the counter off `⟨label⟩` are incorrect.

`\__enumext_keyans_show_left:n`  
`\__enumext_keyans_show_ans:`  
`\__enumext_keyans_show_pos:`  
`\__enumext_keyans_show_item_opt:`

Common function to show *starred commands* `\item*` and `⟨position⟩` of stored content in `⟨prop list⟩` for `keyans` and `keyanspic`. Need add `1` to `\g__enumext_` `\l__enumext_store_name_tl` `_prop` for `show-pos` key.

```

1981 \cs_new_protected:Npn \__enumext_keyans_show_left:n #1
1982 {
1983   \tl_if_novalue:nF { #1 }
1984   {
1985     \tl_set:Ne \l__enumext_keyans_item_opt_tl { #1 }
1986   }
1987   \bool_if:NT \l__enumext_show_answer_bool
1988   {
1989     \__enumext_keyans_show_ans:
1990   }
1991   \bool_if:NT \l__enumext_show_position_bool
1992   {
1993     \__enumext_keyans_show_pos:
1994   }
1995 }
1996 \cs_new_protected:Nn \__enumext_keyans_show_item_opt:
1997 {
1998   \tl_if_empty:NF \l__enumext_keyans_item_opt_tl
1999   {
2000     \bool_lazy_or:nnT
2001     { \bool_if_p:N \l__enumext_show_answer_bool }
2002     { \bool_if_p:N \l__enumext_show_position_bool }
2003     {
2004       \__enumext_keyans_wrapper_opt:n { \l__enumext_keyans_item_opt_tl } \c_space_tl
2005     }
2006   }

```

```

2007   }
2008   \cs_new_protected:Nn \__enumext_keyans_show_ans:
2009   {
2010     \tl_put_left:Nn \l__enumext_label_v_tl
2011     {
2012       \__enumext_print_keyans_box:NN \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
2013     }
2014   }
2015   \cs_new_protected:Nn \__enumext_keyans_show_pos:
2016   {
2017     \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
2018     {
2019       \tl_set:Nc \l__enumext_mark_answer_sym_tl
2020       {
2021         \group_begin:
2022         \exp_not:N \normalfont
2023         \exp_not:N \footnotesize [ \int_eval:n
2024         {
2025           \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
2026         }
2027         ]
2028         \group_end:
2029       }
2030     }
2031     {
2032       \tl_set:Nc \l__enumext_mark_answer_sym_tl
2033       {
2034         \group_begin:
2035         \exp_not:N \normalfont
2036         \exp_not:N \footnotesize [ \int_eval:n
2037         {
2038           \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } + 1
2039         }
2040         ]
2041         \group_end:
2042       }
2043     }
2044     \tl_put_left:Nn \l__enumext_label_v_tl
2045     {
2046       \__enumext_print_keyans_box:NN
2047       \l__enumext_labelwidth_i_dim
2048       \l__enumext_labelsep_i_dim
2049     }
2050   }

```

(End of definition for `\__enumext_keyans_show_left:n` and others.)

## 10.26 Setting `item-sym*` and `item-pos*` keys

In order to have a cleaner implementation of `\item*` it is best to define a couple of keys that allow us to control and set by default the *symbol* and its *offset*.

`item-sym*` Define and set `item-sym*` and `item-pos*` keys for `enumext` and `enumext*`.

```

item-pos* 2051 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
2052 {
2053   \keys_define:nn { enumext / #1 }
2054   {
2055     item-sym* .tl_set:c = { l__enumext_item_symbol_#2_tl },
2056     item-sym* .value_required:n = true,
2057     item-sym* .initial:n = {$\star$},
2058     item-pos* .dim_set:c = { l__enumext_item_symbol_sep_#2_dim },
2059     item-pos* .value_required:n = true,
2060   }
2061 }
2062 \clist_map_inline:nn
2063 {
2064   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {enumext*}{vii}
2065 }
2066 { \__enumext_tmp:nn #1 }

```

(End of definition for `item-sym*` and `item-pos*`.)

## 10.27 Redefining `\footnote` command

```

\__enumext_footnotetext:nn
\__enumext_renew_footnote:
\__enumext_print_footnote:

```

To keep the correct numbering of `\footnote` and to make it work correctly with the `mini-env` key and in the `enumext*` and `keyans*` environments, it is necessary to redefine the command. This implementation is adapted from the answer given by Clea F. Rees (@cfr) in [footnotes in boxes compatible with hyperref](#).

```

2067 \cs_new_protected:Nn \__enumext_footnotetext:nn
2068 {
2069   \footnotetext[#1]{#2}
2070 }
2071 \cs_new_protected:Nn \__enumext_renew_footnote:
2072 {
2073   \seq_gclear:N \g__enumext_footnote_arg_seq
2074   \seq_gclear:N \g__enumext_footnote_int_seq
2075   \RenewDocumentCommand \footnote { o +m }
2076   {
2077     \tl_if_novalue:nTF {##1}
2078     {
2079       \stepcounter{footnote}
2080       \int_gset_eq:Nc \g__enumext_footnote_int { c@footnote }
2081     }
2082     {
2083       \int_gset:Nn \g__enumext_footnote_int { ##1 }
2084     }
2085     \footnotemark [ \g__enumext_footnote_int ]
2086     \seq_gput_right:Nn \g__enumext_footnote_arg_seq { ##2 }
2087     \seq_gput_right:NV \g__enumext_footnote_int_seq \g__enumext_footnote_int
2088   }
2089 }
2090 \cs_new_protected:Nn \__enumext_print_footnote:
2091 {
2092   \seq_if_empty:NF \g__enumext_footnote_int_seq
2093   {
2094     \seq_map_pairwise_function:NNN
2095     \g__enumext_footnote_int_seq
2096     \g__enumext_footnote_arg_seq
2097     \__enumext_footnotetext:nn
2098   }
2099 }

```

(End of definition for `\__enumext_footnotetext:nn`, `\__enumext_renew_footnote:`, and `\__enumext_print_footnote:`)

## 10.28 Redefining `\item` command

Redefining the `\item` command is not as simple as I thought. This command works in conjunction with the `\makelabel` command so I have to redefine both of them, in addition to this, we will have to use a couple of *global* variables to pass the values from one command to the other.

### 10.28.1 The `\item` command in `enumext`

```

\__enumext_default_item:n

```

The `\item` and `\item[custom]` commands work in the usual way on `enumext`.

First we will see if the optional argument is present, if it is NOT present we will check the state of the variable `\l__enumext_check_ans_bool` set by the key `check-ans`, set the boolean variable `\l__enumext_wrap_label_X_bool` to “true” and execute `\__enumext_item_std:w`.

Otherwise we will check the state of the boolean variable `\l__enumext_wrap_label_opt_X_bool` set by the key `wrap-label*` and execute `\__enumext_item_std:w` with the optional argument.

The boolean variable `\l__enumext_wrap_label_X_bool` is used by the function `\__enumext_make_label:` (§10.29).

```

2100 \cs_new_protected:Npn \__enumext_default_item:n #1
2101 {
2102   \tl_if_novalue:nTF {#1}
2103   {
2104     \bool_if:NT \l__enumext_check_ans_bool
2105     {
2106       \int_gincr:N \g__enumext_count_item_number_int
2107     }
2108     \bool_set_true:c { l__enumext_wrap_label_ \__enumext_level: _bool }
2109     \__enumext_item_std:w \tl_use:c { l__enumext_fake_item_indent_ \__enumext_level: _tl }
2110   }
2111   {
2112     \bool_set_eq:cc
2113     { l__enumext_wrap_label_ \__enumext_level: _bool }

```

```

2114         { l__enumext_wrap_label_opt_ \__enumext_level: _bool }
2115     \__enumext_item_std:w [#1] \tl_use:c { l__enumext_fake_item_indent_ \__enumext_level: _tl
2116 }
2117 }

```

(End of definition for \\_\_enumext\_default\_item:n.)

\\_\_enumext\_starred\_item:nn

The `\item*`, `\item*[\langle symbol \rangle]` and `\item*[\langle symbol \rangle][\langle offset \rangle]` works like the numbered `\item`, but placing a `[\langle symbol \rangle]` to the “left” of the `\label` separated from it by the value set by the `labelsep` key and can be *offset* using the second optional argument `[\langle offset \rangle]`.

#1: \l\_\_enumext\_item\_symbol\_X\_tl

#2: \l\_\_enumext\_item\_symbol\_sep\_X\_dim

First we will make a copy of `\l__enumext_item_symbol_X_tl` which is set by the key `item-sym*` or passed as optional argument in the global variable `\g__enumext_item_symbol_tl`, followed by setting the variable `\l__enumext_item_symbol_sep_X_dim` set by the key `item*-sep` or by the second optional argument.

Then we will see the state of the variable `\l__enumext_check_ans_bool` set by the key `check-ans`, set the boolean variable `\l__enumext_wrap_label_X_bool` to “true” and execute `\__enumext_item_std:w`.

In this function the optional argument of `\__enumext_item_std:w` is omitted, we only want it to be numbered.

The boolean variable `\l__enumext_wrap_label_X_bool` and the vars `\l__enumext_item_symbol_sep_X_dim`, `\g__enumext_item_symbol_tl` are used by the function `\__enumext_make_label:` (§10.29).

```

2118 \cs_new_protected:Npn \__enumext_starred_item:nn #1 #2
2119 {
2120     \tl_if_novalue:nF {#1}
2121     {
2122         \tl_set:cn { l__enumext_item_symbol_ \__enumext_level: _tl } {#1}
2123     }
2124     \tl_gset_eq:Nc \g__enumext_item_symbol_tl { l__enumext_item_symbol_ \__enumext_level: _tl }
2125     \tl_if_novalue:nTF {#2}
2126     {
2127         \dim_set_eq:cc
2128         { l__enumext_item_symbol_sep_ \__enumext_level: _dim }
2129         { l__enumext_labelsep_ \__enumext_level: _dim }
2130     }
2131     {
2132         \dim_set:cn { l__enumext_item_symbol_sep_ \__enumext_level: _dim } {#2}
2133     }
2134     \bool_if:NT \l__enumext_check_ans_bool
2135     {
2136         \int_gincr:N \g__enumext_count_item_number_int
2137     }
2138     \bool_set_true:c { l__enumext_wrap_label_ \__enumext_level: _bool }
2139     \__enumext_item_std:w \tl_use:c { l__enumext_fake_item_indent_ \__enumext_level: _tl }
2140 }

```

(End of definition for \\_\_enumext\_starred\_item:nn.)

\\_\_enumext\_redefine\_item:

The function `\__enumext_redefine_item:` will redefine the `\item` command in the `enumext` environment for the internal mechanism of check-answers for `check-ans` key and adding the starred `\item*` version.

This function is passed to `\__enumext_list_arg_two_X:` which is used in the definition of the `enumext` environment (§10.31).

```

2141 \cs_new_protected:Npn \__enumext_redefine_item:
2142 {
2143     \RenewDocumentCommand \item { s o o }
2144     {
2145         \bool_if:nTF {##1}
2146         {
2147             \__enumext_starred_item:nn {##2} {##3}
2148         }
2149         { \__enumext_default_item:n {##2} }
2150     }
2151 }

```

(End of definition for \\_\_enumext\_redefine\_item:.)



### 10.28.2 The `\item` command in keyans

The `\item*` and `\item*[\langle content \rangle]` commands *store* the current  $\langle label \rangle$  next to the  $[\langle content \rangle]$  if it is present in the  $\langle sequence \rangle$  and  $\langle prop list \rangle$  defined by *save-ans* key.

`\__enumext_keyans_default_item:n`

The function `\__enumext_keyans_default_item:n` executes the original behavior of the `\item`.

```

2152 \cs_new_protected:Npn \__enumext_keyans_default_item:n #1
2153 {
2154   \tl_if_novalue:nTF { #1 }
2155   {
2156     \bool_set_true:N \__enumext_wrap_label_v_bool
2157     \__enumext_item_std:w \tl_use:N \__enumext_fake_item_indent_v_tl
2158   }
2159   {
2160     \bool_set_eq:NN \__enumext_wrap_label_v_bool \__enumext_wrap_label_opt_v_bool
2161     \__enumext_item_std:w [#1] \tl_use:N \__enumext_fake_item_indent_v_tl
2162   }
2163 }

```

(End of definition for `\__enumext_keyans_default_item:n`.)

`\__enumext_keyans_starred_item:n`

The function `\__enumext_keyans_starred_item:n` which will make a temporary copy of the current  $\langle label \rangle$ , execute the *show-ans* or *show-pos* keys using the function `\__enumext_keyans_show_left:n` and will display the contents of that item using the internal copy `\__enumext_item_std:w`, this is necessary to prevent incrementing the current “counter” of the original  $\langle label \rangle$ .

```

2164 \cs_new_protected:Npn \__enumext_keyans_starred_item:n #1
2165 {
2166   \tl_set_eq:NN \__enumext_keyans_tmpa_tl \__enumext_label_v_tl
2167   \__enumext_keyans_show_left:n { #1 }
2168   \bool_set_true:N \__enumext_wrap_label_v_bool
2169   \__enumext_item_std:w \tl_use:N \__enumext_fake_item_indent_v_tl \__enumext_keyans_show_item

```

Recover the original value of the current  $\langle label \rangle$  and *store* it first in the  $\langle prop list \rangle$  (including the optional argument), run the internal “*label and ref*” system if the *save-ref* key is active and finally *store* it in the  $\langle sequence \rangle$ .

```

2170   \tl_set_eq:NN \__enumext_label_v_tl \__enumext_keyans_tmpa_tl
2171   \__enumext_keyans_addto_prop:n { #1 }
2172   \__enumext_keyans_store_ref:
2173   \__enumext_keyans_addto_seq:n { #1 }
2174 }

```

(End of definition for `\__enumext_keyans_starred_item:n`.)

`\item*`

`\__enumext_keyans_redefine_item:`

The function `\__enumext_keyans_redefine_item:` is responsible for adding the *starred* and *optional* argument by the `\__enumext_list_arg_two_v:` function in the definition of the *keyans* environment. Here we need to use `\peek_remove_spaces:n` to prevent an unwanted space when using `\item*` in conjunction with the *itemindent* key.

This function is passed to `\__enumext_list_arg_two_v:` which is used in the definition of the *keyans* environment (§10.31).

```

2175 \cs_new_protected:Nn \__enumext_keyans_redefine_item:
2176 {
2177   \RenewDocumentCommand \item { s o }
2178   {
2179     \bool_if:nTF {##1}
2180     {
2181       \peek_remove_spaces:n
2182       {
2183         \__enumext_keyans_starred_item:n {##2}
2184       }
2185     }
2186     {
2187       \__enumext_keyans_default_item:n {##2}
2188     }
2189   }
2190 }

```

(End of definition for `\item*` and `\__enumext_keyans_redefine_item:`. This function is documented on page 11.)

## 10.29 Redefining `\makeLabel` command

Redefine `\makeLabel` for the keys *align*, *font*, *wrap-label*, *wrap-label\** and `\item*` for *enumext* and *keyans* environments.

### 10.29.1 Redefining \makelabel for enumext

`\__enumext_item_starred:` The function `\__enumext_item_starred:` will be responsible for executing `\item*` for the `enumext` environment.

```
2191 \cs_new_protected:Nn \__enumext_item_starred:
2192 {
2193   \tl_if_empty:cF { \__enumext_item_symbol_ \__enumext_level: _tl }
2194   {
2195     \mode_leave_vertical:
2196     \skip_horizontal:n { -\dim_use:c { \__enumext_item_symbol_sep_ \__enumext_level: _dim } }
2197     \makebox[0pt][r]{ \g__enumext_item_symbol_tl }
2198     \skip_horizontal:n { \dim_use:c { \__enumext_item_symbol_sep_ \__enumext_level: _dim } }
2199   }
2200 }
```

(End of definition for `\__enumext_item_starred:`.)

`\__enumext_make_label:` The function `\__enumext_make_label:` redefine `\makelabel` for the `enumext` environment. This function is passed to `\__enumext_list_arg_two_X:` which is used in the definition of the `enumext` environment (§10.31).

```
2201 \cs_new_protected:Nn \__enumext_make_label:
2202 {
2203   \RenewDocumentCommand \makelabel { m }
2204   {
2205     \tl_use:c { \__enumext_label_fill_left_ \__enumext_level: _tl }
2206     \tl_use:c { \__enumext_label_font_style_ \__enumext_level: _tl }
2207     \bool_if:cTF { \__enumext_wrap_label_ \__enumext_level: _bool }
2208     {
2209       \__enumext_item_starred:
2210       \use:c { __enumext_wrapper_label_ \__enumext_level: :n } { ##1 }
2211     }
2212     { ##1 }
2213     \tl_use:c { \__enumext_label_fill_right_ \__enumext_level: _tl }
2214     \tl_gclear:N \g__enumext_item_symbol_tl
2215   }
2216 }
```

(End of definition for `\__enumext_make_label:`.)

### 10.29.2 Redefining \makelabel for keyans

`\__enumext_keyans_make_label:` The function `\__enumext_keyans_make_label:` redefine `\makelabel` for `keyans` environment. This function is passed to `\__enumext_list_arg_two_v:` which is used in the definition of the `keyans` environment (§10.31).



```
2217 \cs_new_protected:Nn \__enumext_keyans_make_label:
2218 {
2219   \RenewDocumentCommand \makelabel { m }
2220   {
2221     \tl_use:N \l__enumext_label_fill_left_v_tl
2222     \tl_use:N \l__enumext_label_font_style_v_tl
2223     \bool_if:NTF \l__enumext_wrap_label_v_bool
2224     {
2225       \__enumext_wrapper_label_v:n { ##1 }
2226     }
2227     { ##1 }
2228     \tl_use:N \l__enumext_label_fill_right_v_tl
2229   }
2230 }
```

(End of definition for `\__enumext_keyans_make_label:`.)

## 10.30 Calculation of \leftmargin and \itemindent

Consider the figure 9 where the default margins (on the left) of a list are represented. The idea is to have control over these margins so that our list does not overlap the left margin of the page. The *key* relationship is that the right edge of the `\labelsep` equals the right edge of the `\itemindent`, so that the left edge of the *label box* is at `\leftmargin+\itemindent` minus `\labelwidth+\labelsep`. Thus, the handling of the margins by the package will be as shown in the figure 10. Where the default values will look like in the figure 11.

`\__enumext_calc_hspace:NNNNNNN` The function `\__enumext_calc_hspace:NNNNNNN` takes seven arguments to be able to determine horizontal spaces for all list environment:  
`\__enumext_calc_hspace:cccccc`

Figure 9: Representation of standard horizontal lengths in `list` environment.Figure 10: Representation of horizontal lengths concept in list in `enumext`.

```
#1: \l__enumext_labelwidth_X_dim      #2: \l__enumext_labelsep_X_dim
#3: \l__enumext_listoffset_X_dim      #4: \l__enumext_leftmargin_tmp_X_dim
#5: \l__enumext_leftmargin_X_dim      #6: \l__enumext_itemindent_X_dim
#7: \l__enumext_leftmargin_tmp_X_bool
```

And returns the “adjusted” values of `\leftmargin` and `\itemindent`.

This function is passed to `\__enumext_list_arg_two_X:` which is used in the definition of the `enumext` and `keyans` environments (§10.31).


```
2231 \cs_new_protected:Npn \__enumext_calc_hspace:NNNNNN #1 #2 #3 #4 #5 #6 #7
2232 {
2233   \dim_compare:nNnT { #1 } < { \c_zero_dim }
2234   {
2235     \msg_warning:nnnV { enumext } { width-non-positive } { labelwidth } { #1 }
2236     \dim_set:Nn #1 { \dim_abs:n { #1 } }
2237   }
2238   \dim_compare:nNnT { #2 } < { \c_zero_dim }
2239   {
2240     \msg_warning:nnnV { enumext } { width-negative } { labelsep } { #2 }
2241     \dim_set:Nn #2 { \dim_abs:n { #2 } }
2242   }
2243 }
```

If no value has been passed to the `labelwidth` and `labelsep` keys we set the default values for `\l__enumext_leftmargin_tmp_X_dim`.

```
2243 \bool_if:nF #7 { \dim_set:Nn #4 { #1 + #2 } }
```

We now analyze the cases and set the values for `\leftmargin` and `\itemindent`.

```
2244 \dim_compare:nNnTF { #4 } < { \c_zero_dim }
2245 {
2246   \dim_set:Nn #6 { #1 + #2 - #4 }
2247   \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
2248 }
2249 {
2250   \dim_compare:nNnT { #4 } = { #1 + #2 }
2251   { \dim_set:Nn #6 { \c_zero_dim } }
2252   \dim_compare:nNnT { #4 } < { #1 + #2 }
2253   { \dim_set:Nn #6 { #1 + #2 - #4 } }
2254   \dim_compare:nNnT { #4 } > { #1 + #2 }
2255   {
2256     \dim_set:Nn #6 { -#1 - #2 + #4 }
2257     \dim_set:Nn #6 { #6*-1 }
2258   }
2259 }
```

Figure 11: Default horizontal lengths in `enumext`.

```

2259         \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
2260     }
2261 }
2262 \cs_generate_variant:Nn \__enumext_calc_hspace:NNNNNNN { cccccc }

```

(End of definition for `\__enumext_calc_hspace:NNNNNNN`.)

### 10.31 Setting second argument of the lists

At this point of the code we have already programmed the necessary tools to create a custom `list` environment, remember that the function `\__enumext_start_list:n` takes two arguments, the first one we have ready, the second one we will define for all the levels of the environment `enumext` and the environment `keyans`.

In this function for the second list argument we will implement the keys `start`, `resume` and `show-length` together with the redefinition of `\item` for `enumext` and `keyans` environments.

We will “not set” `\leftmargini`, `\leftmarginii`, `\leftmarginiii` or `\leftmarginiv`, in this case, we will directly set the parameters for vertical and horizontal list spacing per level.

```

2263 \cs_set_protected:Npn \__enumext_tmp:n #1
2264 {
2265     \cs_new_protected:cpn { \__enumext_list_arg_two_#1: }
2266     {
2267         \__enumext_calc_hspace:ccccc
2268         { \__enumext_labelwidth_#1_dim } { \__enumext_labelsep_#1_dim }
2269         { \__enumext_listoffset_#1_dim } { \__enumext_leftmargin_tmp_#1_dim }
2270         { \__enumext_leftmargin_#1_dim } { \__enumext_itemindent_#1_dim }
2271         { \__enumext_leftmargin_tmp_#1_bool }
2272         \clist_map_inline:nn
2273         { labelsep, labelwidth, itemindent, leftmargin, rightmargin, listparindent }
2274         { \dim_set_eq:cc {####1} { \__enumext_####1_#1_dim } }
2275         \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
2276         { \skip_set_eq:cc {####1} { \__enumext_####1_#1_skip } }
2277         \usecounter { enumX#1 }
2278         \bool_lazy_and:nnTF
2279         { \str_if_eq_p:nn {#1} { i } }
2280         { \bool_if_p:N \__enumext_resume_bool }
2281         { \setcounter { enumXi } { \int_eval:n { \g__enumext_resume_int } } }
2282         {
2283             \setcounter { enumX#1 }
2284             { \int_eval:n { \int_use:c { \__enumext_start_#1_int } - 1 } }
2285         }
2286         \str_if_eq:nnTF {#1} { v }
2287         {
2288             \__enumext_keyans_redefine_item:
2289             \__enumext_keyans_make_label:
2290             \__enumext_keyans_fake_item:
2291             \bool_if:cT { \__enumext_show_length_#1_bool }
2292             {
2293                 \msg_term:nnnn { enumext } { list-lengths-not-nested } { v } { keyans }
2294             }
2295         }
2296         {
2297             \__enumext_redefine_item:
2298             \__enumext_make_label:
2299             \__enumext_use_key_ref:
2300             \__enumext_fake_item:
2301             \bool_if:cT { \__enumext_show_length_#1_bool }
2302             {
2303                 \msg_term:nnne { enumext } { list-lengths } {#1} { \int_use:N \__enumext_level_int }
2304             }
2305         }
2306     }
2307 }
2308 \clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }

```

(End of definition for `\__enumext_list_arg_two_i: and others`.)

For the horizontal environments `enumext*` and `keyans*` the implementation is similar, but, the value of `\partopsep` is always `\opt`. At this point we will modify the `parsep` key to make it take the value of the `itemsep` key and later, in the environment definition, we will modify `parindent` to make it set the value of `lisparindent` and `parsep` to set the value of `\parskip` locally.

```

2309 \cs_set_protected:Npn \__enumext_tmp:n #1
2310 {
2311   \cs_new_protected:cpn { __enumext_list_arg_two_#1: }
2312   {
2313     \__enumext_calc_hspace:ccccc
2314     { \__enumext_labelwidth_#1_dim } { \__enumext_labelsep_#1_dim }
2315     { \__enumext_listoffset_#1_dim } { \__enumext_leftmargin_tmp_#1_dim }
2316     { \__enumext_leftmargin_#1_dim } { \__enumext_itemindent_#1_dim }
2317     { \__enumext_leftmargin_tmp_#1_bool }
2318     \clist_map_inline:nn
2319     { labelsep, labelwidth, itemindent, leftmargin, rightmargin, listparindent }
2320     { \dim_set_eq:cc {####1} { \__enumext_####1_#1_dim } }
2321     \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
2322     { \skip_set_eq:cc {####1} { \__enumext_####1_#1_skip } }
2323     \skip_set_eq:Nc \parsep { \__enumext_itemsep_#1_skip }
2324     \skip_zero:N \partopsep
2325     \usecounter { enumX#1 }
2326     \bool_lazy_and:nnTF
2327     { \str_if_eq_p:nn {#1} { vii } } { \bool_if_p:N \__enumext_resume_vii_bool }
2328     { \setcounter { enumXvii } { \int_eval:n { \g__enumext_resume_vii_int } } }
2329     {
2330       \setcounter { enumX#1 }
2331       { \int_eval:n { \int_use:c { \__enumext_start_#1_int } - 1 } }
2332     }
2333     \__enumext_use_key_ref_h:
2334     \str_if_eq:nnTF {#1} { vii }
2335     {
2336       \__enumext_fake_item_vii:
2337       \bool_if:cT { \__enumext_show_length_vii_bool }
2338       { \msg_term:nnnn { enumext } { list-lengths-not-nested } { vii } { enumext* } }
2339     }
2340     {
2341       \__enumext_fake_item_viii:
2342       \bool_if:cT { \__enumext_show_length_#1_bool }
2343       { \msg_term:nnnn { enumext } { list-lengths-not-nested } { #1 } { keyans* } }
2344     }
2345   }
2346 }
2347 \clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for \\_\_enumext\_list\_arg\_two\_vii: and \\_\_enumext\_list\_arg\_two\_viii:.)

### 10.32 The environment enumext

**enumext** We create the **enumext** environment based on **list** environment by levels.

```

2348 \NewDocumentEnvironment{enumext}{0}{ }
2349 {
2350   \__enumext_current_env:
2351   \__enumext_safe_exec:
2352   \__enumext_parse_keys:n {#1}
2353   \__enumext_before_list:
2354   \__enumext_start_store_level:
2355   \__enumext_start_list:nn
2356   { \tl_use:c { \__enumext_label_ \__enumext_level: _tl } }
2357   {
2358     \use:c { __enumext_list_arg_two_ \__enumext_level: : }
2359     \__enumext_before_keys_exec:
2360   }
2361   \__enumext_after_args_exec:
2362 }
2363 {
2364   \__enumext_stop_list:
2365   \__enumext_stop_store_level:
2366   \__enumext_after_list:
2367 }

```

(End of definition for enumext. This function is documented on page 4.)

**\\_\_enumext\_safe\_exec:** First check the maximum nesting level for the **enumext** environment and set the state of the booleans **\\_\_enumext\_standar\_bool** and **\g\_\_enumext\_standar\_bool** to “true”, the latter only if the environment is NOT nested in the **enumext\*** environment.

```

2368 \cs_new_protected:Nn \__enumext_safe_exec:

```

```

2369 {
2370   \int_incr:N \l__enumext_level_int
2371   \int_compare:nNt { \l__enumext_level_int } > { 4 }
2372   { \msg_fatal:nn { enumext } { list-too-deep } }
2373   \bool_set_true:N \l__enumext_standar_bool
2374 }

```

(End of definition for `\__enumext_safe_exec:`)

`\__enumext_parse_keys:n` Parse [`<key = val>`] by levels in `enumext`. If the variable `\l__enumext_store_active_bool` is true it will call the function `\__enumext_parse_store_keys:n` and reprocess the `<keys>` to pass them to the storage sequence.

```

2375 \cs_new_protected:Npn \__enumext_parse_keys:n #1
2376 {
2377   \exp_args:Ne \keys_set:nn
2378   { enumext / level-\int_use:N \l__enumext_level_int } {#1}
2379   \bool_if:NT \l__enumext_store_active_bool
2380   {
2381     \__enumext_parse_store_keys:n {#1}
2382   }
2383 }

```

(End of definition for `\__enumext_parse_keys:n`)

`\__enumext_parse_store_keys:n` The function `\__enumext_parse_store_keys:n` searches for the values of the `columns` and `columns-sep` keys in the optional arguments per-level in `enumext` environment as long as the starred versions of the `columns*` and `columns-sep*` keys are not active. The captured values are stored in the variable `\l__enumext_store_opt_X_tl` which is used by the function `\__enumext_store_level_open:`.

```

2384 \cs_new_protected:Npn \__enumext_parse_store_keys:n #1
2385 {
2386   \bool_if:cF { \l__enumext_store_columns_ \__enumext_level: _bool }
2387   {
2388     \regex_match:nnT { \b columns\b } {#1}
2389     {
2390       \int_set_eq:cc
2391       { \l__enumext_store_columns_ \__enumext_level: _int }
2392       { \l__enumext_columns_ \__enumext_level: _int }
2393       \tl_put_right:ce { \l__enumext_store_opt_ \__enumext_level: _tl }
2394       {
2395         columns = \exp_not:v { \l__enumext_store_columns_ \__enumext_level: _int },
2396       }
2397     }
2398   }
2399   \bool_if:cF { \l__enumext_store_columns_sep_ \__enumext_level: _bool }
2400   {
2401     \regex_match:nnT { \b columns-sep\b } {#1}
2402     {
2403       \dim_set_eq:cc
2404       { \l__enumext_store_columns_sep_ \__enumext_level: _dim }
2405       { \l__enumext_columns_sep_ \__enumext_level: _dim }
2406       \tl_put_right:ce { \l__enumext_store_opt_ \__enumext_level: _tl }
2407       {
2408         columns-sep = \exp_not:v { \l__enumext_store_columns_sep_ \__enumext_level: _dim },
2409       }
2410     }
2411   }
2412 }

```

(End of definition for `\__enumext_parse_store_keys:n`)

`\__enumext_start_store_level:` The `\__enumext_start_store_level:` and `\__enumext_stop_store_level:` functions activate the level saving mechanism for storage in `<sequence>` of the `\anskey` command.

`\__enumext_stop_store_level:`

If `enumext` are nested in `enumext*` add `\__enumext_store_level_open:` to preserve the stored structure.

```

2413 \cs_new_protected:Nn \__enumext_start_store_level:
2414 {
2415   \bool_lazy_all:nT
2416   {
2417     { \bool_if_p:N \l__enumext_store_active_bool }
2418     { \bool_not_p:n { \l__enumext_keyans_env_bool } }

```

```

2419     { \bool_not_p:n { \g__enumext_starred_bool } }
2420   }
2421   {
2422     \int_compare:nNnT { \l__enumext_level_int } > { 1 }
2423     {
2424       \bool_set_true:c { l__enumext_store_upper_level_ \__enumext_level: _bool }
2425       \__enumext_store_level_open:
2426     }
2427   }
2428   \bool_lazy_all:nT
2429   {
2430     { \bool_if_p:N \l__enumext_store_active_bool }
2431     { \bool_not_p:n { \l__enumext_keyans_env_bool } }
2432     { \bool_if_p:N \g__enumext_starred_bool }
2433   }
2434   {
2435     \int_compare:nNnT { \l__enumext_level_int } > { 0 }
2436     {
2437       \bool_set_true:c { l__enumext_store_upper_level_ \__enumext_level: _bool }
2438       \__enumext_store_level_open:
2439     }
2440   }
2441 }
2442 \cs_new_protected:Nn \__enumext_stop_store_level:
2443 {
2444   \bool_if:cT { l__enumext_store_upper_level_ \__enumext_level: _bool }
2445   {
2446     \__enumext_store_level_close:
2447   }
2448 }

```

(End of definition for \\_\_enumext\_start\_store\_level: and \\_\_enumext\_stop\_store\_level:.)

`\__enumext_before_list:` The function `\__enumext_before_list:` will add the vertical spacing on the environment if the `above` key is active next to the `{\code}` defined by the `before*` key if it is active.

```

2449 \cs_new_protected:Nn \__enumext_before_list:
2450 {
2451   \__enumext_vspace_above:
2452   \__enumext_before_args_exec:

```

The function `\__enumext_check_ans_exec:` will handle the check answer mechanism, which will be activated with the `check-ans` key.

```

2453   \__enumext_check_ans_exec:

```

When the `mini-env` key is active it will set the value of the `\l__enumext_minipage_right_X_dim` to be the *width* of the `\__enumext_mini_env*` environment on the “right side”, using this value together with the value of the `\l__enumext_minipage_hsep_X_dim` set by the `mini-sep` key, the value of `\l__enumext_minipage_left_X_dim` will be set, which will be the *width* of `\__enumext_mini_env*` environment on the “left side”, always having a current `\linewidth` as *maximum width* between them.

```

2454   \dim_compare:nNnT
2455   { \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim } } > { \c_zero_dim }
2456   {
2457     \dim_set:cn { l__enumext_minipage_left_ \__enumext_level: _dim }
2458     {
2459       \linewidth
2460       - \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim }
2461       - \dim_use:c { l__enumext_minipage_hsep_ \__enumext_level: _dim }
2462     }

```

The boolean variable `\l__enumext_minipage_active_X_bool` will be activated and the integer variable `\g__enumext_minipage_stat_int` used by the `\mini-right` command will be incremented, then the function `\__enumext_mini_addvspace:` is called and the `\__enumext_mini_env*` environment on the “left side” will be initialized followed by the “vertical spacing” applied to preserve the “baseline” between the *left* and *right* side environments. After these actions, the function `\__enumext_multicols_start:` is called to handle the `multicols` environment.

Here we use the plain TeX macro `\nointerlineskip` to prevent baseline “glue” being added between the next pair of boxes in a *vertical list*.

```

2463   \bool_set_true:c { l__enumext_minipage_active_ \__enumext_level: _bool }
2464   \int_gincr:N \g__enumext_minipage_stat_int
2465   \__enumext_mini_addvspace:
2466   \nointerlineskip\noindent
2467   \begin{\__enumext_mini_env*}

```



```

2468         { \dim_use:c { l__enumext_minipage_left_ \__enumext_level: _dim } }
2469     }
2470     \__enumext_multicols_start:
2471 }

```

(End of definition for \\_\_enumext\_before\_list:.)

\\_\_enumext\_multicols\_start: The function \\_\_enumext\_multicols\_start: will start the `multicols` environment according to the value passed by the `columns` key, then set the default value for `\columnsep` when `columns-sep=opt` and set the value of `\multicolsep` equal to zero and leave `\columnseprule` equal to zero for inner levels.

```

2472 \cs_new_protected:Nn \__enumext_multicols_start:
2473 {
2474     \int_compare:nNnT
2475     { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
2476     {
2477         \dim_compare:nNnT
2478         { \dim_use:c { l__enumext_columns_sep_ \__enumext_level: _dim } } = { \c_zero_dim }
2479         {
2480             \dim_set:cn { l__enumext_columns_sep_ \__enumext_level: _dim }
2481             {
2482                 ( \dim_use:c { l__enumext_labelwidth_ \__enumext_level: _dim }
2483                   + \dim_use:c { l__enumext_labelsep_ \__enumext_level: _dim }
2484                   ) / \int_use:c { l__enumext_columns_ \__enumext_level: _int }
2485                   - \dim_use:c { l__enumext_listoffset_ \__enumext_level: _dim }
2486             }
2487         }
2488         \dim_set_eq:Nc \columnsep { l__enumext_columns_sep_ \__enumext_level: _dim }
2489         \skip_zero:N \multicolsep
2490         \int_compare:nNnT { \l__enumext_level_int } > { 1 }
2491         {
2492             \dim_zero:N \columnseprule
2493         }
2494     }
2495 }

```

We will calculate the *vertical spacing* settings for the `multicols` environment using the function `\__enumext_multi_addvspace:`, apply our “vertical adjust spacing”, then start the `multicols` environment.

```

2494     \bool_if:cF { l__enumext_minipage_active_ \__enumext_level: _bool }
2495     {
2496         \__enumext_multi_addvspace:
2497     }
2498     \raggedcolumns
2499     \begin{multicols}{ \int_use:c { l__enumext_columns_ \__enumext_level: _int } }
2500 }
2501 }

```

(End of definition for \\_\_enumext\_multicols\_start:.)

\\_\_enumext\_multicols\_stop: The function \\_\_enumext\_multicols\_stop: will stop the `multicols` environment. If the boolean variable `\l__enumext_minipage_active_X_bool` is false (not nested in `__enumext_mini_env*`) we will apply our “vertical adjust” spacing.

```

2502 \cs_new_protected:Nn \__enumext_multicols_stop:
2503 {
2504     \int_compare:nNnT
2505     { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
2506     {
2507         \end{multicols}
2508         \bool_if:cF { l__enumext_minipage_active_ \__enumext_level: _bool }
2509         {
2510             \par\addvspace{ \skip_use:c { l__enumext_multicols_below_ \__enumext_level: _skip } }
2511         }
2512     }
2513 }

```

If the `check-ans` key is active, we set the boolean variable `\g__enumext_check_ans_show_bool` to true and copy the stored name to the variable `\g__enumext_store_name_tl`. These variables will be used by the function `\__enumext_after_env:n` to display the result of the internal check answer mechanism in the terminal.

```

2513     \bool_lazy_and:nnT
2514     { \bool_if_p:N \l__enumext_check_ans_bool }
2515     { \bool_not_p:n { \g__enumext_starred_bool } }
2516     {

```

```

2517         \bool_gset_true:N \g__enumext_check_ans_show_bool
2518         \tl_gset:NV \g__enumext_store_name_tl \l__enumext_store_name_tl
2519     }
2520 }

```

(End of definition for `\__enumext_multicols_stop:`)

`\__enumext_after_list:` The function `\__enumext_after_list:` will check the state of the boolean variable `\l__enumext_minipage_active_X_bool`, if it is “true” a small test will be executed to check if we have omitted the use of `\miniright` (the `\__enumext_mini_env*` environment has not been closed), then close `\__enumext_mini_env*` and add the *adjusted vertical space* `\l__enumext_minipage_after_skip`, otherwise we will close the `\multicols` environment.

```

2521 \cs_new_protected:Nn \__enumext_after_list:
2522 {
2523     \bool_if:cTF { \l__enumext_minipage_active_ \__enumext_level: _bool }
2524     {
2525         \int_compare:nNnT { \g__enumext_minipage_stat_int } = { 1 }
2526         {
2527             \msg_warning:nn { enumext } { missing-miniright }
2528             \miniright
2529         }
2530         \int_gzero:N \g__enumext_minipage_stat_int
2531         \end{\__enumext_mini_env*}
2532         \par\addvspace { \l__enumext_minipage_after_skip }
2533     }
2534     { \__enumext_multicols_stop: }

```

Now apply the `{\code}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```

2535     \__enumext_after_stop_list:
2536     \__enumext_vspace_below:

```

Finally save the *current value* of the counter in `\g__enumext_resume_int` for the `resume` key. If the `save-ans` key is active, it will create the integer variable for the `resume` key, we only have to assign it the value of the current counter.

```

2537     \bool_set_false:N \l__enumext_standar_bool
2538     \int_gset_eq:NN \g__enumext_resume_int \value{enumXi}
2539     \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl _int }
2540     {
2541         \int_gset_eq:cN
2542         { g__enumext_resume_ \l__enumext_store_name_tl _int }
2543         { \value{enumXi} }
2544     }
2545 }

```

(End of definition for `\__enumext_after_list:`)

As we don’t want our check to be executed `check-ans` by levels but on the complete list, we will take it out of the `enumext` environment using the “hook” function `\__enumext_after_env:nn`.

```

2546 \__enumext_after_env:nn {enumext}
2547 {
2548     \int_compare:nNnT { \l__enumext_level_int } = { 0 }
2549     {
2550         \bool_if:NT \g__enumext_check_ans_show_bool
2551         {
2552             \__enumext_check_ans_show:
2553         }
2554         \bool_gset_false:N \g__enumext_standar_bool
2555         \bool_gset_false:N \g__enumext_check_ans_show_bool
2556         \tl_gclear:N \g__enumext_store_name_tl
2557     }
2558 }

```

### 10.33 The environment `keyans`

The environment `keyans` also based on lists. The main differences with the `enumext` environment are the *nesting* and the way the *answers* (choice) will be stored and checked, this environment is intended exclusively for “multiple choice questions”.

`keyans` Now we define the environment `keyans` also based on lists.

```

2559 \NewDocumentEnvironment{keyans}{0}{}
2560 {

```

```

2561   \__enumext_keyans_safe_exec:
2562   \__enumext_keyans_parse_keys:n {#1}
2563   \__enumext_before_list_v:
2564   \__enumext_start_list:nn
2565     { \tl_use:N \__enumext_label_v_tl }
2566     {
2567       \__enumext_list_arg_two_v:
2568       \__enumext_before_keys_exec_v:
2569     }
2570   \__enumext_after_args_exec_v:
2571 }
2572 {
2573   \__enumext_keyans_check_ans:nn { item }{ keyans }
2574   \__enumext_stop_list:
2575   \__enumext_after_list_v:
2576 }

```

(End of definition for `keyans`. This function is documented on page 10.)

`\__enumext_keyans_safe_exec:` The `keyans` environment will only be available if the `save-ans` key is active and can only be used at the first level within the `enumext` environment. We do not want the environment to be nested, so we will set a maximum at this point. If the conditions are not met, an error message will be returned.

```

2577 \cs_new_protected:Nn \__enumext_keyans_safe_exec:
2578 {
2579   \bool_if:NF \__enumext_store_active_bool
2580   {
2581     \msg_error:nnnn { enumext } { wrong-place }{ keyans }{ save-ans }
2582   }
2583   \int_incr:N \__enumext_keyans_level_int
2584   \bool_set_true:N \__enumext_keyans_env_bool
2585   % Set false for interfering with enumext nested in keyans (yes, its possible and crayze)
2586   \bool_set_false:N \__enumext_store_active_bool
2587   \int_compare:nNnT { \__enumext_keyans_level_int } > { 1 }
2588   {
2589     \msg_error:nn { enumext } { keyans-nested }
2590   }
2591   \int_compare:nNnT { \__enumext_level_int } > { 1 }
2592   {
2593     \msg_error:nn { enumext } { keyans-wrong-level }
2594   }
2595 }

```

(End of definition for `\__enumext_keyans_safe_exec:`.)

`\__enumext_keyans_parse_keys:n` Parse [`<key = val>`] for `keyans` environment.

```

2596 \cs_new_protected:Npn \__enumext_keyans_parse_keys:n #1
2597 {
2598   \keys_set:nn { enumext / keyans } {#1}
2599 }

```

(End of definition for `\__enumext_keyans_parse_keys:n`.)

`\__enumext_before_list_v:` The function `\__enumext_before_list_v:` will add the *vertical spacing above* the environment if the *above* key is active next to the `<code>` defined by the `before` key if it is active.

```

2600 \cs_new_protected:Nn \__enumext_before_list_v:
2601 {
2602   \__enumext_vspace_above_v:
2603   \__enumext_before_args_exec_v:

```

When the `mini-env` key is active it will set the value of the `\__enumext_minipage_right_v_dim` to be the *width* of the `__enumext_mini_env*` environment on the *left side*, using this value together with the value of the `\__enumext_minipage_hsep_v_dim` set by the `mini-sep` key, the value of `\__enumext_minipage_left_v_dim` will be set, which will be the *width* of `__enumextt_mini_env*` environment on the *right side*, always having `\linewidth` as the maximum width between them.

```

2604   \dim_compare:nNnT { \__enumext_minipage_right_v_dim } > { \c_zero_dim }
2605   {
2606     \dim_set:Nn \__enumext_minipage_left_v_dim
2607     {
2608       \linewidth - \__enumext_minipage_right_v_dim - \__enumext_minipage_hsep_v_dim
2609     }

```

The boolean variable `\l__enumext_minipage_active_v_bool` will be activated and the integer variable `\g__enumext_minipage_stat_int` used by the `\miniright` command will be incremented, then the function `\__enumext_keyans_mini_addvspace:` is called and the `__enumext_mini_env*` environment on *left side* will be initialized followed by the *vertical spacing* `\l__enumext_minipage_left_skip`. Here we use the plain TeX macro `\nointerlineskip` to prevent baseline “glue” being added between the next pair of boxes in a *vertical list*.

```

2610         \bool_set_true:N \l__enumext_minipage_active_v_bool
2611         \int_gincr:N \g__enumext_minipage_stat_int
2612         \__enumext_keyans_mini_addvspace:
2613         \nointerlineskip\noindent
2614         \begin{__enumext_mini_env*}{ \l__enumext_minipage_left_v_dim }
2615     }

```

After these actions, the `\__enumext_keyans_multicols_start:` function is called to handle the `multicols` environment.

```

2616     \__enumext_keyans_multicols_start:
2617 }

```

(End of definition for `\__enumext_before_list_v:`)

`\__enumext_keyans_multicols_start:`

The function `\__enumext_keyans_multicols_start:` will start the `multicols` environment according to the value passed by the `columns` key.

```

2618 \cs_new_protected:Nn \__enumext_keyans_multicols_start:
2619 {
2620     \int_compare:nNt { \l__enumext_columns_v_int } > { 1 }
2621     {

```

Set the default value for `\columnsep` when `columns-sep` key is `opt`.

```

2622         \dim_compare:nNt { \l__enumext_columns_sep_v_dim } = { \c_zero_dim }
2623         {
2624             \dim_set:Nn \l__enumext_columns_sep_v_dim
2625             {
2626                 (
2627                     \l__enumext_labelwidth_v_dim + \l__enumext_labelsep_v_dim
2628                 ) / \l__enumext_columns_v_int
2629                 - \l__enumext_listoffset_v_dim
2630             }
2631         }
2632         \dim_set_eq:NN \columnsep \l__enumext_columns_sep_v_dim

```

Then we will set the value of `\multicolsep` and `\columnseprule` equal to zero (we do not want a vertical rule in this environment).

```

2633         \skip_zero:N \multicolsep
2634         \dim_zero:N \columnseprule

```

We will calculate the *vertical spacing* settings for the `multicols` environment using the function `\__enumext_keyans_multi_addvspace:` and apply our “*vertical adjust spacing*”, then start the `multicols` environment.

```

2635         \bool_if:NF \l__enumext_minipage_active_v_bool
2636         {
2637             \__enumext_keyans_multi_addvspace:
2638         }
2639         \raggedcolumns
2640         \begin{multicols}{ \l__enumext_columns_v_int }
2641     }
2642 }

```

(End of definition for `\__enumext_keyans_multicols_start:`)

`\__enumext_keyans_multicols_stop:`

The function `\__enumext_keyans_multicols_stop:` will stop the `multicols` environment. If the boolean variable `\l__enumext_minipage_active_v_bool` is false (not nested in `__enumext_mini_env*`) we will apply our vertical “adjust” spacing.

```

2643 \cs_new_protected:Nn \__enumext_keyans_multicols_stop:
2644 {
2645     \int_compare:nNt { \l__enumext_columns_v_int } > { 1 }
2646     {
2647         \end{multicols}
2648         \bool_if:NF \l__enumext_minipage_active_v_bool
2649         {
2650             \par\addvspace{ \l__enumext_multicols_below_v_skip }
2651         }
2652     }
2653 }

```

(End of definition for `\__enumext_keyans_multicols_stop:`)

`\__enumext_after_list_v:` The function `\__enumext_after_list_v:` will check the state of the boolean variable `\l__enumext_minipage_active_v_bool`, if it is “true” a small test will be executed to check if we have omitted the use of `\miniright` (the `\__enumext_mini_env*` environment has not been closed), then close `\__enumext_mini_env*` and add the vertical adjustment space `\l__enumext_minipage_after_skip`, otherwise we will close the `\multicols` environment.

```

2654 \cs_new_protected:Nn \__enumext_after_list_v:
2655 {
2656   \bool_if:NTF \l__enumext_minipage_active_v_bool
2657   {
2658     \int_compare:nNt { \g__enumext_minipage_stat_int } = { 1 }
2659     {
2660       \msg_warning:nn { enumext } { missing-miniright }
2661       \miniright
2662     }
2663     \int_gzero:N \g__enumext_minipage_stat_int
2664     \end{__enumext_mini_env*}
2665     \par\addvspace{ \l__enumext_minipage_after_skip }
2666   }
2667   { \__enumext_keyans_multicols_stop: }

```

Finally we will apply the `{\code}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```

2668   \bool_set_false:N \l__enumext_keyans_env_bool
2669   \__enumext_after_stop_list_v:
2670   \__enumext_vspace_below_v:
2671 }

```

(End of definition for `\__enumext_after_list_v:`)

### 10.34 The environment `keyanspic` and `\anspic`

The `keyanspic` environment is a list-based environment that uses the same configuration for “spacing” and `\label` as the `keyans` environment, but it does not use `\item`.

The contents are passed to the environment by means of the `\anspic` command and are placed inside `minipage` environments, with the `\label` underneath, adjusting widths according to the options passed to the environment.

Again it is necessary to “adjust” the spacing, both vertical and horizontal, to obtain an output like the one shown in the figure 12.




Figure 12: Representation of the `keyanspic` spacing in `enumext`.

This implementation is adapted from the answer given by Enrico Gregorio in [How to process the body of an environment and divide it by a \macro?](#).

#### 10.34.1 The command `\anspic`

`\anspic` The `\anspic` command takes three arguments, the starred (\*) versions `\anspic*` and `\anspic*[\content]` store the current `\label` next to the `[\content]` if it is present in the `\sequence` and `\prop list` defined by `save-ans` key. This command is used as a replacement for `\item` in the `keyanspic` environment.

```

2672 \NewDocumentCommand \anspic { s o +m }
2673 {

```

We check that the command is active in the `keyanspic` environment only if the `save-ans` key is present, otherwise we return an error.

```

2674   \bool_if:NF \l__enumext_store_active_bool
2675   {
2676     \msg_error:nnnn { enumext } { wrong-place } { keyanspic } { save-ans }
2677   }
2678   \int_compare:nNt { \l__enumext_level_int } > { 1 }
2679   {

```

```

2680     \msg_error:nn { enumext } { keyanspic-wrong-level }
2681   }
2682   \int_compare:nNt { \__enumext_keyans_level_int } = { 1 }
2683   {
2684     \msg_error:nnnn { enumext } { command-wrong-place } { anspic } { keyans }
2685   }

```

The three arguments are handled by the function `\__enumext_keyans_anspic_code:nnn` and stored in the sequence `\__enumext_keyans_pic_body_seq` which is processed by the `keyanspic` environment.

```

2686   \seq_put_right:Nn \__enumext_keyans_pic_body_seq
2687   {
2688     \__enumext_keyans_anspic_code:nnn { #1 } { #2 } { #3 }
2689   }
2690 }

```

(End of definition for `\anspic`. This function is documented on page 12.)

`\__enumext_keyans_anspic_code:nnn`

The function `\__enumext_keyans_anspic_code:nnn` will be in charge of handling the “counter” and `<label>`, which will have the same configuration as the `keyans` environment.

```

2691 \cs_new_protected:Nn \__enumext_keyans_anspic_code:nnn
2692 {
2693   \stepcounter { enumXvi }
2694   #3 \
2695   \bool_if:nT { #1 }
2696   {
2697     \__enumext_keyans_addto_prop:n { #2 }
2698     \__enumext_keyans_store_ref:
2699     \__enumext_keyans_addto_seq:n { #2 }
2700     \bool_lazy_or:nnT
2701     { \bool_if_p:N \__enumext_show_answer_bool }
2702     { \bool_if_p:N \__enumext_show_position_bool }
2703     {
2704       \tl_set_eq:NN \__enumext_label_v_tl \__enumext_label_vi_tl
2705       \__enumext_keyans_show_left:n { #2 }
2706       \tl_set_eq:NN \__enumext_label_vi_tl \__enumext_label_v_tl
2707     }
2708   }
2709   \tl_use:N \__enumext_label_font_style_v_tl
2710   \__enumext_wrapper_label_v:n { \__enumext_label_vi_tl } \__enumext_keyans_show_item_opt:
2711 }

```

(End of definition for `\__enumext_keyans_anspic_code:nnn`.)

### 10.34.2 The environment `keyanspic`

`keyanspic` Now we define the environment `keyanspic` based on list. The optional argument [*number above, number below*] will determine the number of `minipage` environments that will be above and below separated by `\parsep+\itemsep` within it.

```

2712 \NewDocumentEnvironment{keyanspic}{o}
2713 {
2714   \__enumext_keyans_pic_safe_exec:
2715   \__enumext_start_list:nn
2716   { }
2717   {
2718     \__enumext_keyans_pic_arg_two:
2719   }

```

We apply the “adjusted” vertical spacing above the environment

```

2720   \vspace { \__enumext_keyans_pic_above_skip }
2721 }

```

If the optional argument is not present, the number of times the `\anspic` command appears will be counted from `\__enumext_keyans_pic_body_seq` and placed in `minipage` environments on a single line. Finally we check if `\anspic*` has been used, set the counter to zero and apply our “adjusted” vertical space below the environment.

```

2722 {
2723   \tl_if_novalue:nTF { #1 }
2724   {
2725     \__enumext_keyans_pic_do:e { \seq_count:N \__enumext_keyans_pic_body_seq }
2726   }
2727   { \__enumext_keyans_pic_do:n { #1 } }
2728   \__enumext_stop_list:
2729   \__enumext_keyans_check_ans:nn { anspic } { keyanspic }

```

```

2730 \setcounter { enumXvi } { 0 }
2731 \vspace { \l__enumext_topsep_v_skip }
2732 %\bool_set_false:N \l__enumext_store_active_bool
2733 }

```

(End of definition for `keyanspic`. This function is documented on page 11.)

`\__enumext_keyans_pic_safe_exec:` The function `\__enumext_keyans_pic_safe_exec:` check nested and level position inside the `enumext` environment.

```

2734 \cs_new_protected:Nn \__enumext_keyans_pic_safe_exec:
2735 {
2736   \int_incr:N \l__enumext_keyans_pic_level_int
2737   \int_compare:nNnT { \l__enumext_keyans_pic_level_int } > { 1 }
2738   {
2739     \msg_error:nn { enumext } { keyanspic-nested }
2740   }
2741 }

```

(End of definition for `\__enumext_keyans_pic_safe_exec:.`)

`\__enumext_keyans_pic_skip_abs:N` The function `\__enumext_keyans_pic_skip_abs:N` will return a positive value `\parsep`.

```

2742 \cs_new_protected:Npn \__enumext_keyans_pic_skip_abs:N #1
2743 {
2744   \dim_compare:nNnT { #1 } < { 0pt }
2745   { \skip_set:Nn #1 { -#1 } }
2746 }

```

(End of definition for `\__enumext_keyans_pic_skip_abs:N.`)

`\__enumext_keyans_pic_arg_two:` The function `\__enumext_keyans_pic_arg_two:` will be used in the second argument of the `\__enumext_start_list:nn` function that defines the `keyanspic` environment, it will handle the setting of spaces.

```

2747 \cs_new_protected:Nn \__enumext_keyans_pic_arg_two:
2748 {

```

The first thing to do is to set the boolean variable `\l__enumext_leftmargin_tmp_v_bool` handled by the `list-indent` key to false, then we copy the definition of the second list argument from the `keyans` environment.

```

2749 \bool_set_false:N \l__enumext_leftmargin_tmp_v_bool
2750 \__enumext_list_arg_two_v:

```

We will add the value of `\itemsep` to `\parsep` which we will use as vertical spacing between the above and below `minipage` environments. and adjust the value of `\leftmargin`, the label and counter are handled directly by the `\anspic` command. Then we make equal to zero `\labelwidth`, `\labelsep`, `\partopsep` and `\itemsep` so that the horizontal and vertical spacing is not affected.

```

2751 \skip_add:Nn \parsep { \itemsep }
2752 \dim_add:Nn \leftmargin { -\labelwidth - \labelsep }
2753 \dim_zero:N \labelwidth
2754 \dim_zero:N \listparindent
2755 \dim_zero:N \labelsep
2756 \skip_zero:N \partopsep
2757 \skip_zero:N \itemsep

```

We set the value of `\l__enumext_keyans_pic_above_skip` which we will use to apply our “adjust” space above `keyanspic`, finally we call `\__enumext_item_std:w` followed by `\scan_stop:` to prevent the error message returned by  $\TeX$  when not using the `\item` command.

```

2758 \__enumext_keyans_pic_skip_abs:N \parsep
2759 \skip_set:Nn \l__enumext_keyans_pic_above_skip
2760 {
2761   \box_dp:N \strutbox
2762   + \l__enumext_topsep_v_skip
2763   - \parsep
2764 }
2765 \__enumext_item_std:w \scan_stop:
2766 }

```

(End of definition for `\__enumext_keyans_pic_arg_two:.`)



`\__enumext_keyans_pic_do:n`  
`\__enumext_keyans_pic_do:e`

The optional argument is split by comma and is handled directly by the function `\__enumext_keyans_pic_do:n` and passed to the function `\__enumext_keyans_pic_row:n`.

```

2767 \cs_new_protected:Nn \__enumext_keyans_pic_do:n
2768 {
2769   \clist_map_function:nN { #1 } \__enumext_keyans_pic_row:n
2770 }
2771 \cs_generate_variant:Nn \__enumext_keyans_pic_do:n { e }

```

(End of definition for `\__enumext_keyans_pic_do:n`.)

`\__enumext_keyans_pic_row:n`

The function `\__enumext_keyans_pic_row:n` will set the widths for the `minipage` environments and place the content *stored* by `\anspic*` in the `\l__enumext_keyans_pic_body_seq` sequence inside them.

```

2772 \cs_new_protected:Nn \__enumext_keyans_pic_row:n
2773 {
2774   \dim_set:Nn \l__enumext_keyans_pic_width_dim { \linewidth / #1 }
2775   \int_set:Nn \l__enumext_keyans_pic_above_int { \l__enumext_keyans_pic_below_int }
2776   \int_set:Nn \l__enumext_keyans_pic_below_int { \l__enumext_keyans_pic_above_int + #1 }
2777   \int_step_inline:nnn
2778     { \l__enumext_keyans_pic_above_int + 1 }
2779     { \l__enumext_keyans_pic_below_int }
2780     {
2781       \__enumext_minipage:w [ b ]{ \l__enumext_keyans_pic_width_dim }
2782       \centering
2783       \seq_item:Nn \l__enumext_keyans_pic_body_seq { ##1 }
2784       \__enumext_endminipage:
2785     }
2786   \par
2787 }

```

(End of definition for `\__enumext_keyans_pic_row:n`.)

### 10.35 The enumext\* environment

Generating horizontal list environments is NOT as simple as standard  $\TeX$  list environments. The fundamental part of the code is adapted from the `shortlst` package to a more modern version using `expl3`. It is not possible to redefine `\item` and `\makelabel` as in the non starred versions (at least I have not achieved it) and as we will make it behave differently, we have no other option than to define a cascade of functions.

To achieve the horizontal list environment we will capture the `\item` command and the content of this in an plain `lrbox` box using `\makebox` for the `label` and a `minipage` environment for the content passed to `\item`, we will also add the optional argument (*number*) to `\item` to be able to *join columns* horizontally, in simple terms, we want `\item` to behave in the same way as in the `enumext` environment but adding an optional first argument (*number*).

#### 10.35.1 Functions for item box width

`\__enumext_starred_columns_set_vii:`

We set the default value for the width of the box containing the content of the items and create `\itemwidth` in a public form.

```

2788 \cs_new_protected:Nn \__enumext_starred_columns_set_vii:
2789 {
2790   \dim_compare:nNnT { \l__enumext_columns_sep_vii_dim } = { \c_zero_dim }
2791   {
2792     \dim_set:Nn \l__enumext_columns_sep_vii_dim
2793     {
2794       ( \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim )
2795       / \l__enumext_columns_vii_int
2796     }
2797   }
2798   \int_set:Nn \l__enumext_tmpa_vii_int { \l__enumext_columns_vii_int - \c_one_int }
2799   \dim_set:Nn \l__enumext_item_width_vii_dim
2800   {
2801     ( \linewidth - \l__enumext_columns_sep_vii_dim * \l__enumext_tmpa_vii_int )
2802     / \l__enumext_columns_vii_int - \l__enumext_labelwidth_vii_dim
2803     - \l__enumext_labelsep_vii_dim
2804   }
2805   \dim_zero_new:N \itemwidth
2806 }

```

(End of definition for `\__enumext_starred_columns_set_vii:.`)

\\_\_enumext\_starred\_joined\_item\_vii:n

The function \\_\_enumext\_starred\_joined\_item\_vii:n will set the *width* of the box in which the content passed to \item(<number>) will be stored together with the value of \itemwidth.

```

2807 \cs_new_protected:Npn \__enumext_starred_joined_item_vii:n #1
2808 {
2809   \int_set:Nn \l__enumext_joined_item_vii_int {#1}
2810   \int_compare:nNnT { \l__enumext_joined_item_vii_int } > { \l__enumext_columns_vii_int }
2811   {
2812     \msg_warning:nnee { enumext } { item-joined }
2813     { \int_use:N \l__enumext_joined_item_vii_int }
2814     { \int_use:N \l__enumext_columns_vii_int }
2815     \int_set:Nn \l__enumext_joined_item_vii_int
2816     {
2817       \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int
2818     }
2819   }
2820   \int_compare:nNnT
2821   { \l__enumext_joined_item_vii_int }
2822   >
2823   { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int }
2824   {
2825     \msg_warning:nnee { enumext } { item-joined-columns }
2826     { \int_use:N \l__enumext_joined_item_vii_int }
2827     {
2828       \int_eval:n
2829       { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int }
2830     }
2831     \int_set:Nn \l__enumext_joined_item_vii_int
2832     {
2833       \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + \c_one_int
2834     }
2835   }

```

Only need if #1 >> 1 (default are set before).

```

2836   \int_compare:nNnTF { \l__enumext_joined_item_vii_int } > { \c_one_int }
2837   {
2838     \int_set_eq:NN \l__enumext_joined_item_aux_vii_int \l__enumext_joined_item_vii_int
2839     \int_decr:N \l__enumext_joined_item_aux_vii_int
2840     \int_add:Nn \l__enumext_item_column_pos_vii_int { \l__enumext_joined_item_aux_vii_int }
2841     \int_gadd:Nn \g__enumext_item_count_all_vii_int { \l__enumext_joined_item_aux_vii_int }
2842     \dim_set:Nn \l__enumext_joined_width_vii_dim
2843     {
2844       \l__enumext_item_width_vii_dim * \l__enumext_joined_item_vii_int
2845       + ( \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim
2846         + \l__enumext_columns_sep_vii_dim
2847       ) * \l__enumext_joined_item_aux_vii_int
2848     }
2849     \dim_set_eq:NN \itemwidth \l__enumext_joined_width_vii_dim
2850   }
2851   {
2852     \dim_set_eq:NN \l__enumext_joined_width_vii_dim \l__enumext_item_width_vii_dim
2853     \dim_set_eq:NN \itemwidth \l__enumext_item_width_vii_dim
2854   }
2855 }

```

(End of definition for \\_\_enumext\_starred\_joined\_item\_vii:n.)

\\_\_enumext\_start\_mini\_vii:

The implementation of the mini-env key support is almost identical to the one used in the enumext and keyans environments, the difference is that the \_\_enumext\_mini\_env\* environment on the “right side” is executed “after” closing the environment, so it is necessary to make a global copy of the variable \l\_\_enumext\_minipage\_right\_vii\_dim in the variable \g\_\_enumext\_minipage\_right\_vii\_dim.

```

2856 \cs_new_protected:Nn \__enumext_start_mini_vii:
2857 {
2858   \dim_compare:nNnT { \l__enumext_minipage_right_vii_dim } > { \c_zero_dim }
2859   {
2860     \dim_set:Nn \l__enumext_minipage_left_vii_dim
2861     {
2862       \linewidth
2863       - \l__enumext_minipage_right_vii_dim
2864       - \l__enumext_minipage_hsep_vii_dim
2865     }
2866     \bool_set_true:N \l__enumext_minipage_active_vii_bool

```

```

2867         \dim_gset_eq:NN
2868         \g__enumext_minipage_right_vii_dim
2869         \l__enumext_minipage_right_vii_dim
2870         \__enumext_mini_addvspace_vii:
2871         \nointerlineskip\noindent
2872         \begin{__enumext_mini_env*}{ \l__enumext_minipage_left_vii_dim }
2873     }
2874 }

```

(End of definition for \\_\_enumext\_start\_mini\_vii:.)

`\__enumext_stop_mini_vii:` The function `\__enumext_stop_mini_vii:` closes the `__enumext_mini_env*` environment on the left side, applies `\hfill` and sets the value of the variable `\g__enumext_minipage_active_vii_bool` to true which will be used in the function `\__enumext_after_star_env:nn` to execute the `__enumext-mini_env*` on the “right side”.

```

2875 \cs_new_protected:Nn \__enumext_stop_mini_vii:
2876 {
2877     \bool_if:NT \l__enumext_minipage_active_vii_bool
2878     {
2879         \end{__enumext_mini_env*}
2880         \hfill
2881         \bool_gset_true:N \g__enumext_minipage_active_vii_bool
2882     }
2883 }

```

Finally we execute code passed to the `miniright` key stored in the variable `\g__enumext_miniright_code_vii_tl` in the `__enumext_mini_env*` environment on the “right side”.

```

2884 \__enumext_after_env:nn {enumext*}
2885 {
2886     \bool_if:NT \g__enumext_minipage_active_vii_bool
2887     {
2888         \begin{__enumext_mini_env*}{ \g__enumext_minipage_right_vii_dim }
2889         \par\addvspace { \g__enumext_minipage_right_skip }
2890         \bool_if:NF \g__enumext_minipage_center_vii_bool
2891         {
2892             \centering
2893         }
2894         \tl_use:N \g__enumext_miniright_code_vii_tl % the code
2895         \end{__enumext_mini_env*}
2896         \par\addvspace{ \g__enumext_minipage_after_skip }
2897     }
2898     \bool_gset_false:N \g__enumext_minipage_active_vii_bool
2899     \bool_gset_true:N \g__enumext_minipage_center_vii_bool
2900     \tl_gclear:N \g__enumext_miniright_code_vii_tl
2901     \dim_gzero:N \g__enumext_minipage_right_vii_dim
2902 }

```

(End of definition for \\_\_enumext\_stop\_mini\_vii:.)

**enumext\*** First we will generate the environment and we will give a temporary definition to `\__enumext_stop_item_tmp_vii:` equal to `\noindent` and next to `\item` equal to `\__enumext_start_item_tmp_vii:` which we will redefine later.

```

2903 \NewDocumentEnvironment{enumext*}{ o }
2904 {
2905     \__enumext_current_env:
2906     \__enumext_safe_exec_vii:
2907     \__enumext_parse_keys_vii:n {#1}
2908     \__enumext_before_list_vii:
2909     \__enumext_start_store_level_vii:
2910     \__enumext_start_list:nn { }
2911     {
2912         \__enumext_list_arg_two_vii:
2913         \__enumext_before_keys_exec_vii:
2914     }
2915     \__enumext_starred_columns_set_vii:
2916     \item[] \scan_stop:
2917     \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \noindent
2918     \cs_set_eq:NN \item \__enumext_start_item_tmp_vii:
2919 }
2920 {
2921     \__enumext_stop_item_tmp_vii:

```

```

2922     \__enumext_remove_extra_parsep_vii:
2923     \__enumext_stop_list:
2924     \__enumext_stop_store_level_vii:
2925     \__enumext_after_list_vii:
2926 }

```

(End of definition for enumext\*. This function is documented on page 4.)

\\_\_enumext\_safe\_exec\_vii: First check the maximum nesting level for the enumext\* environment then set the vars \l\_\_enumext\_starred\_bool and \g\_\_enumext\_starred\_bool.

```

2927 \cs_new_protected:Nn \__enumext_safe_exec_vii:
2928 {
2929     \int_incr:N \l__enumext_level_h_int
2930     \int_compare:nNnT { \l__enumext_level_h_int } > { 1 }
2931     {
2932         \msg_error:nn { enumext } { nested }
2933     }
2934     \bool_set_true:N \l__enumext_starred_bool
2935 }

```

(End of definition for \\_\_enumext\_safe\_exec\_vii:.)

\\_\_enumext\_parse\_keys\_vii:n Parse [*key = val*] for enumext\*. If the variable \l\_\_enumext\_store\_active\_bool is true it will call the function \\_\_enumext\_parse\_store\_keys\_vii:n and reprocess the keys to pass them to the storage sequence.

```

2936 \cs_new_protected:Npn \__enumext_parse_keys_vii:n #1
2937 {
2938     \tl_if_novalue:nF {#1}
2939     {
2940         \keys_set:nn { enumext / enumext* } {#1}
2941         \bool_if:NT \l__enumext_store_active_bool
2942         {
2943             \__enumext_parse_store_keys_vii:n {#1}
2944         }
2945     }
2946 }

```

(End of definition for \\_\_enumext\_parse\_keys\_vii:n.)

\\_\_enumext\_parse\_store\_keys\_vii:n The function \\_\_enumext\_parse\_store\_keys\_vii:n searches for the values of the columns and columns-sep keys in the optional argument in enumext\* environment as long as the starred versions of the columns\* and columns-sep\* keys are not active. The captured values are stored in the variable \l\_\_enumext\_store\_opt\_vii\_tl which is used by the function \\_\_enumext\_store\_level\_open\_vii:.

```

2947 \cs_new_protected:Npn \__enumext_parse_store_keys_vii:n #1
2948 {
2949     \bool_if:NF \l__enumext_store_columns_vii_bool
2950     {
2951         \regex_match:nnT { \b columns\b } {#1}
2952         {
2953             \int_set_eq:NN
2954             \l__enumext_store_columns_vii_int
2955             \l__enumext_columns_vii_int
2956             \tl_put_right:Ne \l__enumext_store_opt_vii_tl
2957             {
2958                 columns = \exp_not:V \l__enumext_store_columns_vii_int ,
2959             }
2960         }
2961     }
2962     \bool_if:NF \l__enumext_store_columns_sep_vii_bool
2963     {
2964         \regex_match:nnT { \b columns-sep\b } {#1}
2965         {
2966             \dim_set_eq:NN
2967             \l__enumext_store_columns_sep_vii_dim
2968             \l__enumext_columns_sep_vii_dim
2969             \tl_put_right:Ne \l__enumext_store_opt_vii_tl
2970             {
2971                 columns-sep = \exp_not:V \l__enumext_store_columns_sep_vii_dim,
2972             }
2973         }
2974     }
2975 }

```

```

2973     }
2974 }
2975 }

```

(End of definition for `\__enumext_parse_store_keys_vii:n`)

`\__enumext_before_list_vii:` The function `\__enumext_before_list_vii:` will add the vertical spacing on the environment if the `above` key is active next to the `{⟨code⟩}` defined by the `before*` key if it is active, then call the function `\__enumext_start_mini_vii:` handle by `mini-env`.

```

2976 \cs_new_protected:Nn \__enumext_before_list_vii:
2977 {
2978     \__enumext_vspace_above_vii:
2979     \__enumext_check_ans_exec: % need by chek-ans
2980     \__enumext_before_args_exec_vii:
2981     \__enumext_start_mini_vii:
2982 }

```

(End of definition for `\__enumext_before_list_vii:`)

`\__enumext_after_list_vii:` The function `\__enumext_after_list:` first call the function `\__enumext_stop_mini_vii:`, then apply the `{⟨code⟩}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present. Finally set false the vars `\g__enumext_starred_bool` and `\l__enumext_starred_bool`, save the *current value* of the counter in `\g__enumext_resume_vii_int` for the `resume` key. If the `save-ans` key is active, it will create the integer variable for the `resume` key, we only have to assign it the value of the current counter.

```

2983 \cs_new_protected:Nn \__enumext_after_list_vii:
2984 {
2985     \__enumext_stop_mini_vii:
2986     \__enumext_after_stop_list_vii:
2987     \__enumext_vspace_below_vii:
2988     \int_gset_eq:NN \g__enumext_resume_vii_int \value{enumXvii}
2989     \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl _int }
2990     {
2991         \int_gset_eq:cN
2992         { g__enumext_resume_ \l__enumext_store_name_tl _int }
2993         { \value{enumXvii} }
2994     }
2995     \bool_lazy_and:nnT
2996     { \bool_if_p:N \g__enumext_starred_bool }
2997     { \bool_if_p:N \l__enumext_check_ans_bool }
2998     {
2999         \bool_gset_true:N \g__enumext_check_ans_show_h_bool
3000         \tl_gset:NV \g__enumext_store_name_tl \l__enumext_store_name_tl
3001     }
3002     %\bool_gset_false:N \g__enumext_starred_bool
3003     \bool_set_false:N \l__enumext_starred_bool
3004 }

```

(End of definition for `\__enumext_after_list_vii:`)

`\__enumext_start_store_level_vii:` and `\__enumext_stop_store_level_vii:` functions activate the level saving mechanism for storage in `⟨sequence⟩` of the `\anskey` command if `enumext*` are nested in `enumext`.

```

3005 \cs_new_protected:Nn \__enumext_start_store_level_vii:
3006 {
3007     \bool_if:NT \l__enumext_store_active_bool
3008     {
3009         \int_compare:nNnT { \l__enumext_level_int } > { \c_zero_int }
3010         {
3011             \__enumext_store_level_open_vii:
3012         }
3013     }
3014 }
3015 \cs_new_protected:Nn \__enumext_stop_store_level_vii:
3016 {
3017     \bool_if:NT \l__enumext_store_active_bool
3018     {
3019         \int_compare:nNnT { \l__enumext_level_int } > { \c_zero_int }
3020         {
3021             \__enumext_store_level_close_vii:

```

```

3022     }
3023 }
3024 }

```

(End of definition for `\__enumext_start_store_level_vii:` and `\__enumext_stop_store_level_vii:`)

### 10.35.2 The command `\item` in `enumext`\*

`\__enumext_start_item_tmp_vii:`

First we will call the function `\__enumext_stop_item_tmp_vii:` that we will redefine later, we will increment the value of `\l__enumext_item_column_pos_vii_int` that will count the item's by rows and the value of `\g__enumext_item_count_all_vii_int` that will count the total of item's in the environment. After that we will call the function `\__enumext_item_peek_args_vii:` that will handle the arguments passed to `\item`.

```

3025 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_vii:
3026 {
3027   \__enumext_stop_item_tmp_vii:
3028   \int_incr:N \l__enumext_item_column_pos_vii_int
3029   \int_gincr:N \g__enumext_item_count_all_vii_int
3030   \__enumext_item_peek_args_vii:
3031 }

```

(End of definition for `\__enumext_start_item_tmp_vii:`)

`\__enumext_item_peek_args_vii:`

The function `\__enumext_item_peek_args_vii:` will handle the `\item(<number>)`. Look for the argument “(”, if it is present we will call the function `\__enumext_joined_item_vii:w (<number>)`, which is in charge of joining the item's in the same row, in case they are not present we will set the default value (1).

```

3032 \cs_new_protected:Nn \__enumext_item_peek_args_vii:
3033 {
3034   \peek_meaning:NTF (
3035     { \__enumext_joined_item_vii:w }
3036     { \__enumext_joined_item_vii:w (1) }
3037   }

```

(End of definition for `\__enumext_item_peek_args_vii:`)

`\__enumext_joined_item_vii:w`

The function `\__enumext_joined_item_vii:w` will first call the function `\__enumext_starred_joined_item_vii:n` in charge of setting the *width* of the box that will store the content passed to `\item`. Then we will look for the argument “\*”, if it is present we will call the function `\__enumext_starred_item_vii:w` otherwise we will call the function `\__enumext_standard_item_vii:w`.

```

3038 \cs_new_protected:Npn \__enumext_joined_item_vii:w (#1)
3039 {
3040   \__enumext_starred_joined_item_vii:n {#1}
3041   \peek_meaning_remove:NTF *
3042     { \__enumext_starred_item_vii:w }
3043     { \__enumext_standard_item_vii:w }
3044 }

```

(End of definition for `\__enumext_joined_item_vii:w`)

`\__enumext_standard_item_vii:w`

The function `\__enumext_standard_item_vii:w` will first look for the argument “[”, if present it will set the state of the variable `\l__enumext_wrap_label_opt_vii_bool` equal to the state of the variable `\l__enumext_wrap_label_opt_vii_bool` handled by the key `wrap-label*` and finally execute the *non-enumerated* version `\item[<custom>]` by means of the function `\__enumext_start_item_vii:w`, otherwise we will set the value of the variable `\l__enumext_wrap_label_vii_bool` handled by the `wrap-label` key to true and set the switch `\if@noitemarg` to true to execute the enumerated version of `\item` by means of the function `\__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]`.

```

3045 \cs_new_protected:Npn \__enumext_standard_item_vii:w
3046 {
3047   \bool_set_false:N \l__enumext_item_starred_vii_bool
3048   \peek_meaning:NTF [
3049     {
3050       \bool_set_eq:NN
3051       \l__enumext_wrap_label_vii_bool
3052       \l__enumext_wrap_label_opt_vii_bool
3053       \__enumext_start_item_vii:w
3054     }
3055     {
3056       \bool_set_true:N \l__enumext_wrap_label_vii_bool
3057       \legacy_if_set_true:n { @noitemarg }

```

```

3058         \__enumext_start_item_vii:w [ \__enumext_label_vii_tl ]
3059     }
3060 }

```

(End of definition for \\_\_enumext\_standard\_item\_vii:w.)

```

\__enumext_starred_item_vii:w
\__enumext_starred_item_vii_aux_i:w
\__enumext_starred_item_vii_aux_ii:w
\__enumext_starred_item_vii_aux_iii:w

```

The function \\_\_enumext\_starred\_item\_vii:w together with the specified auxiliary functions aux\_i:w, aux\_ii:w, and aux\_iii:w execute \item\*, \item\*[\symbol] and \item\*[\symbol][\offset].

```

3061 \cs_new_protected:Npn \__enumext_starred_item_vii:w
3062 {
3063     \bool_set_true:N \__enumext_item_starred_vii_bool
3064     \bool_set_true:N \__enumext_wrap_label_vii_bool
3065     \peek_meaning:NTF [
3066         { \__enumext_starred_item_vii_aux_i:w }
3067         { \__enumext_starred_item_vii_aux_ii:w }
3068     }
3069     \cs_new_protected:Npn \__enumext_starred_item_vii_aux_i:w [#1]
3070     {
3071         \tl_gset:Nn \__enumext_item_symbol_aux_vii_tl {#1}
3072         \__enumext_starred_item_vii_aux_ii:w
3073     }
3074     \cs_new_protected:Npn \__enumext_starred_item_vii_aux_ii:w
3075     {
3076         \peek_meaning:NTF [
3077             { \__enumext_starred_item_vii_aux_iii:w }
3078             {
3079                 \dim_set_eq:NN
3080                 \__enumext_item_symbol_sep_vii_dim
3081                 \__enumext_labelsep_vii_dim
3082                 \legacy_if_set_true:n { @noitemarg }
3083                 \__enumext_start_item_vii:w [ \__enumext_label_vii_tl ]
3084             }
3085         }
3086     \cs_new_protected:Npn \__enumext_starred_item_vii_aux_iii:w [#1]
3087     {
3088         \dim_set:Nn \__enumext_item_symbol_sep_vii_dim {#1}
3089         \legacy_if_set_true:n { @noitemarg }
3090         \__enumext_start_item_vii:w [ \__enumext_label_vii_tl ]
3091     }

```

(End of definition for \\_\_enumext\_starred\_item\_vii:w and others.)

### 10.35.3 Real definition of \item in enumext\*

```
\__enumext_start_item_vii:w
```

The functions \\_\_enumext\_start\_item\_vii:w and \\_\_enumext\_stop\_item\_vii: executing the true definition of \item inside the enumext\* environment.

The first thing we will do is set the value of \\_\_enumext\_stop\_item\_tmp\_vii: equal to the value of \\_\_enumext\_stop\_item\_vii: which we will define later and add the [hyperref](#) compatible `enumXvii` counter, after that we will start capturing the item content in a box. Here need setting the \if@hyper@item switch to “true” for [hyperref](#) compatible. The explanation for this is given by the master Heiko Oberdiek on `\refstepcounter{enumi}` twice (or more) creates destination with the same identifier.

```

3092 \cs_new_protected_nopar:Npn \__enumext_start_item_vii:w [#1]
3093 {
3094     \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \__enumext_stop_item_vii:
3095     \legacy_if:nT { @noitemarg }
3096     {
3097         \legacy_if_set_false:n { @noitemarg }
3098         \legacy_if:nT { @nmbrrlist }
3099         {
3100             \bool_if:NT \__enumext_hyperref_bool
3101             {
3102                 \legacy_if_set_true:n { @hyper@item }
3103             }
3104             \refstepcounter{enumXvii}
3105             \bool_if:NT \__enumext_check_ans_bool
3106             {
3107                 \int_gincr:N \__enumext_count_item_number_int
3108             }
3109         }
3110     }

```



Here we start capturing `\item` and its contents into a group using the plain form of the `lrbox` environment. If the state of the variable `\l__enumext_footnotes_key_bool` is false, we will redefine the command `\footnote`, followed by printing the  $\langle symbol \rangle$  defined for `\item*` if it is present and open a new group inside which we execute `font` key next to `\item` and the keys `wrap-label`, `wrap-label*`, `align`, close the group and execute the key `labelsep` and then the key `first`. Finally we open the `minipage` environment and execute the `listparindent` key which will be equal to `\parindent`, the `parsep` key which will be equal to `\parskip` and the `itemindent` key.

```

3111 \group_begin:
3112 \lrbox{ \l__enumext_item_text_vii_box }
3113 \bool_if:NF \l__enumext_footnotes_key_bool
3114 {
3115   \__enumext_renew_footnote:
3116 }
3117 \bool_if:NT \l__enumext_item_starred_vii_bool
3118 {
3119   \tl_if_blank:VT \g__enumext_item_symbol_aux_vii_tl
3120   {
3121     \tl_gset_eq:NN
3122     \g__enumext_item_symbol_aux_vii_tl \l__enumext_item_symbol_vii_tl
3123   }
3124   \mode_leave_vertical:
3125   \skip_horizontal:n { -\l__enumext_item_symbol_sep_vii_dim }
3126   \makebox[ 0pt ][ r ]{ \g__enumext_item_symbol_aux_vii_tl }
3127   \skip_horizontal:N \l__enumext_item_symbol_sep_vii_dim
3128   \tl_gclear:N \g__enumext_item_symbol_aux_vii_tl
3129 }
3130 \group_begin:
3131 \tl_use:N \l__enumext_label_font_style_vii_tl
3132 \bool_if:NTF \l__enumext_wrap_label_vii_bool
3133 {
3134   \makebox[ \l__enumext_labelwidth_vii_dim ][ \l__enumext_align_label_vii_str ]
3135   { \__enumext_wrapper_label_vii:n {#1} }
3136 }
3137 {
3138   \makebox[ \l__enumext_labelwidth_vii_dim ][ \l__enumext_align_label_vii_str ]{ #1 }
3139 }
3140 \group_end:
3141 \skip_horizontal:N \l__enumext_labelsep_vii_dim
3142 \tl_use:N \l__enumext_after_list_args_vii_tl
3143 \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_vii_dim }
3144 \skip_set_eq:NN \parindent \l__enumext_listparindent_vii_dim
3145 \skip_set_eq:NN \parskip \l__enumext_parsep_vii_skip
3146 \tl_use:N \l__enumext_fake_item_indent_vii_tl
3147 }

```

(End of definition for `\__enumext_start_item_vii:w`.)

`\__enumext_stop_item_vii:` The function `\__enumext_stop_item_vii:` shall terminate with the capture of `\item` and its  $\langle contents \rangle$ . Close the environments `minipage`, `lrbox` and the group. Then we only have to set the width of the box and print it next to `\footnote`, and add the horizontal and vertical separation between the boxes.

```

3148 \cs_new_protected_nopar:Nn \__enumext_stop_item_vii:
3149 {
3150   \__enumext_endminipage:
3151   \endlrbox
3152   \group_end:
3153   \box_set_wd:Nn \l__enumext_item_text_vii_box
3154   {
3155     \l__enumext_joined_width_vii_dim
3156     + \l__enumext_labelwidth_vii_dim
3157     + \l__enumext_labelsep_vii_dim
3158   }
3159   \int_set:Nn \hbadness { 10000 }
3160   \box_use:N \l__enumext_item_text_vii_box
3161   \bool_if:NF \l__enumext_footnotes_key_bool
3162   {
3163     \__enumext_print_footnote:
3164   }
3165   \int_compare:nNnTF { \l__enumext_item_column_pos_vii_int } = { \l__enumext_columns_vii_int }
3166   {
3167     \par\noindent

```

```

3168         \int_zero:N \l__enumext_item_column_pos_vii_int
3169     }
3170     { \hspace{ \l__enumext_columns_sep_vii_dim } }
3171 }

```

(End of definition for `\__enumext_stop_item_vii:`)

`\__enumext_remove_extra_parsep_vii:`

Finally we will remove the vertical space equal to `\parsep` when the total number of items is divisible by the number of items in the last row of the environment.

```

3172 \cs_new_protected:Nn \__enumext_remove_extra_parsep_vii:
3173 {
3174     \int_compare:nNnT
3175     {
3176         \int_mod:nn { \g__enumext_item_count_all_vii_int } { \l__enumext_columns_vii_int }
3177     }
3178     =
3179     { \c_zero_int }
3180     {
3181         \par
3182         \vspace{ -\l__enumext_itemsep_vii_skip }
3183         \int_gzero:N \g__enumext_item_count_all_vii_int
3184     }
3185 }

```

(End of definition for `\__enumext_remove_extra_parsep_vii:`)

As we don't want our check to be executed `check-ans` by levels but on the complete list, we will take it out of the `enumext*` environment using the “hook” function `\__enumext_after_env:nn`.

```

3186 \__enumext_after_env:nn {enumext*}
3187 {
3188     \int_compare:nNnT { \l__enumext_level_int } = { 0 }
3189     {
3190         \bool_if:NT \g__enumext_check_ans_show_h_bool
3191         {
3192             \__enumext_check_ans_show:
3193         }
3194         \bool_gset_false:N \g__enumext_starred_bool
3195         \bool_gset_false:N \g__enumext_check_ans_show_h_bool
3196         \tl_gclear:N \g__enumext_store_name_tl
3197     }
3198 }

```

## 10.36 The `keyans*` environment

### 10.36.1 Functions for item box width

`\__enumext_starred_columns_set_viii:`

We set the default value for the width of the box containing the content of the items and create `\itemwidth` in a public form.

```

3199 \cs_new_protected:Nn \__enumext_starred_columns_set_viii:
3200 {
3201     \dim_compare:nNnT { \l__enumext_columns_sep_viii_dim } = { \c_zero_dim }
3202     {
3203         \dim_set:Nn \l__enumext_columns_sep_viii_dim
3204         {
3205             ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim )
3206             / \l__enumext_columns_viii_int
3207         }
3208     }
3209     \int_set:Nn \l__enumext_tmpa_viii_int { \l__enumext_columns_viii_int - \c_one_int }
3210     \dim_set:Nn \l__enumext_item_width_viii_dim
3211     {
3212         ( \linewidth - \l__enumext_columns_sep_viii_dim * \l__enumext_tmpa_viii_int )
3213         / \l__enumext_columns_viii_int - \l__enumext_labelwidth_viii_dim
3214         - \l__enumext_labelsep_viii_dim
3215     }
3216     \dim_zero_new:N \itemwidth
3217 }

```

(End of definition for `\__enumext_starred_columns_set_viii:`)

\\_enumext\_starred\_joined\_item\_viii:n

The function \\_enumext\_starred\_joined\_item\_viii:n will set the *width* of the box in which the content passed to \item(<number>) will be stored together with the value of \itemwidth.

```

3218 \cs_new_protected:Npn \_enumext_starred_joined_item_viii:n #1
3219 {
3220   \int_set:Nn \l__enumext_joined_item_viii_int {#1}
3221   \int_compare:nNtT { \l__enumext_joined_item_viii_int } > { \l__enumext_columns_viii_int }
3222   {
3223     \msg_warning:nnee { enumext } { item-joined }
3224     { \int_use:N \l__enumext_joined_item_viii_int }
3225     { \int_use:N \l__enumext_columns_viii_int }
3226     \int_set:Nn \l__enumext_joined_item_viii_int
3227     {
3228       \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int
3229     }
3230   }
3231   \int_compare:nNtT
3232   { \l__enumext_joined_item_viii_int }
3233   >
3234   { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int }
3235   {
3236     \msg_warning:nnee { enumext } { item-joined-columns }
3237     { \int_use:N \l__enumext_joined_item_viii_int }
3238     {
3239       \int_eval:n
3240       { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int }
3241     }
3242     \int_set:Nn \l__enumext_joined_item_viii_int
3243     {
3244       \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + \c_one_int
3245     }
3246   }
3247   \int_compare:nNtTF { \l__enumext_joined_item_viii_int } > { \c_one_int }
3248   {
3249     \int_set_eq:NN \l__enumext_joined_item_aux_viii_int \l__enumext_joined_item_viii_int
3250     \int_decr:N \l__enumext_joined_item_aux_viii_int
3251     \int_add:Nn \l__enumext_item_column_pos_viii_int { \l__enumext_joined_item_aux_viii_int }
3252     \int_gadd:Nn \g__enumext_item_count_all_viii_int { \l__enumext_joined_item_aux_viii_int }
3253     \dim_set:Nn \l__enumext_joined_width_viii_dim
3254     {
3255       \l__enumext_item_width_viii_dim * \l__enumext_joined_item_viii_int
3256       + ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim
3257         + \l__enumext_columns_sep_viii_dim
3258         ) * \l__enumext_joined_item_aux_viii_int
3259     }
3260     \dim_set_eq:NN \itemwidth \l__enumext_joined_width_viii_dim
3261   }
3262   {
3263     \dim_set_eq:NN \l__enumext_joined_width_viii_dim \l__enumext_item_width_viii_dim
3264     \dim_set_eq:NN \itemwidth \l__enumext_item_width_viii_dim
3265   }
3266 }

```

(End of definition for \\_enumext\_starred\_joined\_item\_viii:n.)

\\_enumext\_start\_mini\_viii:

The implementation of the mini-env key is identical to the one used in the enumext\* environment.

\\_enumext\_stop\_mini\_viii:

```

3267 \cs_new_protected:Nn \_enumext_start_mini_viii:
3268 {
3269   \dim_compare:nNtT { \l__enumext_minipage_right_viii_dim } > { \c_zero_dim }
3270   {
3271     \dim_set:Nn \l__enumext_minipage_left_viii_dim
3272     {
3273       \linewidth
3274       - \l__enumext_minipage_right_viii_dim
3275       - \l__enumext_minipage_hsep_viii_dim
3276     }
3277     \bool_set_true:N \l__enumext_minipage_active_viii_bool
3278     \dim_gset_eq:NN
3279     \g__enumext_minipage_right_viii_dim
3280     \l__enumext_minipage_right_viii_dim
3281     \_enumext_mini_addvspace_viii:

```

```

3282         \nointerlineskip\noindent
3283         \begin{__enumext_mini_env*}{ \l__enumext_minipage_left_viii_dim }
3284     }
3285 }
3286 \cs_new_protected:Nn \__enumext_stop_mini_viii:
3287 {
3288     \bool_if:NT \l__enumext_minipage_active_viii_bool
3289     {
3290         \end{__enumext_mini_env*}
3291         \hfill
3292         \bool_gset_true:N \g__enumext_minipage_active_viii_bool
3293     }
3294 }
3295 \__enumext_after_env:nn {keyans*}
3296 {
3297     \bool_if:NT \g__enumext_minipage_active_viii_bool
3298     {
3299         \begin{__enumext_mini_env*}{ \g__enumext_minipage_right_viii_dim }
3300         \par\addvspace { \g__enumext_minipage_right_skip }
3301         \bool_if:NF \g__enumext_minipage_center_viii_bool
3302         {
3303             \centering
3304         }
3305         \tl_use:N \g__enumext_miniright_code_viii_tl % the code
3306         \end{__enumext_mini_env*}
3307         \par\addvspace{ \g__enumext_minipage_after_skip }
3308     }
3309     \bool_gset_false:N \g__enumext_minipage_active_viii_bool
3310     \bool_gset_true:N \g__enumext_minipage_center_viii_bool
3311     \tl_gclear:N \g__enumext_miniright_code_viii_tl
3312     \dim_gzero:N \g__enumext_minipage_right_viii_dim
3313 }

```

(End of definition for \\_\_enumext\_start\_mini\_viii: and \\_\_enumext\_stop\_mini\_viii:.)

**keyans\*** First we will generate the environment and we will give a temporary definition to \\_\_enumext\_stop\_item\_tmp\_viii: equal to \noindent and next to \item equal to \\_\_enumext\_start\_item\_tmp\_viii: which we will redefine later.

```

3314 \NewDocumentEnvironment{keyans*}{ o }
3315 {
3316     \__enumext_safe_exec_viii:
3317     \__enumext_parse_keys_viii:n {#1}
3318     \__enumext_before_list_viii:
3319     \__enumext_start_list:nn { }
3320     {
3321         \__enumext_list_arg_two_viii:
3322         \__enumext_before_keys_exec_viii:
3323     }
3324     \__enumext_starred_columns_set_viii:
3325     \item[] \scan_stop:
3326     \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \noindent
3327     \cs_set_eq:NN \item \__enumext_start_item_tmp_viii:
3328 }
3329 {
3330     \__enumext_stop_item_tmp_viii:
3331     \__enumext_remove_extra_parsep_viii:
3332     \__enumext_keyans_check_ans:nn { item }{ keyans* }
3333     \__enumext_stop_list:
3334     \__enumext_after_list_viii:
3335 }

```

(End of definition for keyans\*. This function is documented on page 10.)

\\_\_enumext\_safe\_exec\_viii: First check the maximum nesting level for the **keyans\*** environment.

```

3336 \cs_new_protected:Nn \__enumext_safe_exec_viii:
3337 {
3338     \int_incr:N \l__enumext_keyans_level_h_int
3339     \int_compare:nNtT { \l__enumext_keyans_level_h_int } > { 1 }
3340     {
3341         \msg_error:nn { enumext } { nested }
3342     }

```

```

3343 % Set false for interfering with enumext nested in keyans* (yes, its possible and crayze)
3344 \bool_set_false:N \l__enumext_store_active_bool
3345 \int_compare:nNnT { \l__enumext_level_int } > { 1 }
3346 {
3347     \msg_error:nn { enumext } { keyans-wrong-level }
3348 }
3349 }

```

(End of definition for `\__enumext_safe_exec_viii:`)

`\__enumext_parse_keys_viii:n` Parse [`<key = val>`] for `keyans*`.

```

3350 \cs_new_protected:Npn \__enumext_parse_keys_viii:n #1
3351 {
3352     \tl_if_novalue:nF {#1}
3353     {
3354         \keys_set:nn { enumext / keyans* } {#1}
3355     }
3356 }

```

(End of definition for `\__enumext_parse_keys_viii:n`)

`\__enumext_before_list_viii:` The function `\__enumext_before_list_viii:` will add the vertical spacing on the environment if the above key is active next to the `{<code>}` defined by the `before*` key if it is active, the call the function `\__enumext_start_mini_viii:` handle by `mini-env`.

```

3357 \cs_new_protected:Nn \__enumext_before_list_viii:
3358 {
3359     \__enumext_vspace_above_viii:
3360     \__enumext_before_args_exec_viii:
3361     \__enumext_start_mini_viii:
3362 }

```

(End of definition for `\__enumext_before_list_viii:`)

`\__enumext_after_list_viii:` The function `\__enumext_after_list:` first call the function `\__enumext_stop_mini_viii:`, then apply the `{<code>}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```

3363 \cs_new_protected:Nn \__enumext_after_list_viii:
3364 {
3365     \__enumext_stop_mini_viii:
3366     \__enumext_after_stop_list_viii:
3367     \__enumext_vspace_below_viii:
3368 }

```

(End of definition for `\__enumext_after_list_viii:`)

### 10.36.2 The command `\item` in `keyans*`

The idea here is to make the `\item` command behave in the same way as in the `keyans` environment with the difference of the optional argument (`<number>`) which works in the same way as in the `enumext*` environment. In simple terms we want to store the `<label>` next to the [`<content>`] if it is present in the `<sequence>` and `<prop list>` defined by `save-ans` key for `\item*`, `\item* [<content>]`, `\item(<number>)*` and `\item(<number>)* [<content>]` commands.

`\__enumext_start_item_tmp_viii:` First we will call the function `\__enumext_stop_item_tmp_viii:` that we will redefine later, we will increment the value of `\l__enumext_item_column_pos_viii_int` that will count the item's by rows and the value of `\g__enumext_item_count_all_viii_int` that will count the total of item's in the environment. After that we will call the function `\__enumext_item_peek_args_viii:` that will handle the arguments passed to `\item`.

```

3369 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_viii:
3370 {
3371     \__enumext_stop_item_tmp_viii:
3372     \int_incr:N \l__enumext_item_column_pos_viii_int
3373     \int_gincr:N \g__enumext_item_count_all_viii_int
3374     \__enumext_item_peek_args_viii:
3375 }

```

(End of definition for `\__enumext_start_item_tmp_viii:`)

`\__enumext_item_peek_args_viii:` The function `\__enumext_item_peek_args_viii:` will handle the `\item(<number>)`. Look for the argument “(”, if it is present we will call the function `\__enumext_joined_item_viii:w (<number>)`, which is in charge of joining the item’s in the same row, in case they are not present we will set the default value (1).

```

3376 \cs_new_protected:Nn \__enumext_item_peek_args_viii:
3377 {
3378   \peek_meaning:NTF (
3379     { \__enumext_joined_item_viii:w }
3380     { \__enumext_joined_item_viii:w (1) }
3381   }

```

(End of definition for `\__enumext_item_peek_args_viii:.`)

`\__enumext_joined_item_viii:w` The function `\__enumext_joined_item_viii:w` will first call the function `\__enumext_starred_joined_item_viii:n` in charge of setting the *width* of the box that will store the content passed to `\item`. Then we will look for the argument “\*”, if it is present we will call the function `\__enumext_starred_item_viii:w` otherwise we will call the function `\__enumext_standard_item_viii:w`.

```

3382 \cs_new_protected:Npn \__enumext_joined_item_viii:w (#1)
3383 {
3384   \__enumext_starred_joined_item_viii:n {#1}
3385   \peek_meaning_remove:NTF *
3386   { \__enumext_starred_item_viii:w }
3387   { \__enumext_standard_item_viii:w }
3388 }

```

(End of definition for `\__enumext_joined_item_viii:w.`)

`\__enumext_standard_item_viii:w` The function `\__enumext_standard_item_viii:w` will first look for the argument “[”, if present it will set the state of the variable `\l__enumext_wrap_label_opt_viii_bool` equal to the state of the variable `\l__enumext_wrap_label_opt_viii_bool` handled by the key `wrap-label*` and finally execute the *non-enumerated* version `\item[<custom>]` by means of the function `\__enumext_start_item_viii:w`, otherwise we will set the value of the variable `\l__enumext_wrap_label_viii_bool` handled by the `wrap-label` key to true and set the switch `\if@noitemarg` to true to execute the enumerated version of `\item` by means of the function `\__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ]`.

```

3389 \cs_new_protected:Npn \__enumext_standard_item_viii:w
3390 {
3391   \bool_set_false:N \l__enumext_item_starred_viii_bool
3392   \peek_meaning:NTF [
3393     {
3394       \bool_set_eq:NN
3395         \l__enumext_wrap_label_viii_bool
3396         \l__enumext_wrap_label_opt_viii_bool
3397       \__enumext_start_item_viii:w
3398     }
3399     {
3400       \bool_set_true:N \l__enumext_wrap_label_viii_bool
3401       \legacy_if_set_true:n { @noitemarg }
3402       \__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ]
3403     }
3404   }

```

(End of definition for `\__enumext_standard_item_viii:w.`)

`\__enumext_starred_item_viii:w` The function `\__enumext_starred_item_viii:w` together with the specified auxiliary functions `aux_i:w` and `aux_ii:w` execute `\item*` and `\item* [<content>]`.

```

\__enumext_starred_item_viii_aux_i:w
\__enumext_starred_item_viii_aux_ii:w
3405 \cs_new_protected:Npn \__enumext_starred_item_viii:w
3406 {
3407   \bool_set_true:N \l__enumext_item_starred_viii_bool
3408   \bool_set_true:N \l__enumext_wrap_label_viii_bool
3409   \peek_meaning:NTF [
3410     { \__enumext_starred_item_viii_aux_i:w }
3411     { \__enumext_starred_item_viii_aux_ii:w }
3412   }

```

The optional argument will be captured in the variables `\l__enumext_keyans_tmpa_tl` and `\l__enumext_keyans_tmpp_tl` which we will use later for the implementation of the `show-ans` and `show-pos` keys together with the stored in *(sequence)* and *(prop list)*.

```

3413 \cs_new_protected:Npn \__enumext_starred_item_viii_aux_i:w [#1]
3414 {

```

```

3415 \tl_clear:N \l__enumext_store_keyans_label_tl
3416 \tl_if_novalue:nF { #1 }
3417 {
3418   \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_tl
3419   {
3420     \tl_put_right:Ne \l__enumext_store_keyans_label_tl { \l__enumext_store_keyans_item_opt_sep_tl }
3421     \tl_put_right:Ne \l__enumext_store_keyans_label_tl { #1 }
3422   }
3423   \tl_set:Ne \l__enumext_keyans_item_opt_tl { #1 }
3424 }
3425 \__enumext_starred_item_viii_aux_ii:w
3426 }
3427 \cs_new_protected:Npn \__enumext_starred_item_viii_aux_ii:w
3428 {
3429   \legacy_if_set_true:n { @noitemarg }
3430   \__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ]
3431 }

```

(End of definition for `\__enumext_starred_item_viii:w`, `\__enumext_starred_item_viii_aux_i:w`, and `\__enumext_starred_item_viii_aux_ii:w`.)

`\__enumext_starred_item_exec:`

The function `\__enumext_starred_item_exec:` will be in charge of storing the current *label* for `\item*` followed by the `[content]` for `\item*[content]` if present in the *sequence* and *prop list* set by the `save-ans` key. In this same function the keys `show-ans`, `show-pos` and `save-ref` are implemented.

```

3432 \cs_new_protected:Nn \__enumext_starred_item_exec:
3433 {
3434   \tl_put_left:Ne \l__enumext_store_keyans_label_tl { \l__enumext_label_viii_tl }
3435   \__enumext_store_addto_prop:V \l__enumext_store_keyans_label_tl
3436   \__enumext_keyans_store_ref:
3437   \tl_put_left:Ne \l__enumext_store_keyans_label_tl { \item }
3438   \__enumext_keyans_addto_seq_link:
3439   \bool_if:NT \l__enumext_show_answer_bool
3440   {
3441     \__enumext_print_keyans_box:NN \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
3442   }
3443   \bool_if:NT \l__enumext_show_position_bool
3444   {
3445     \tl_set:Ne \l__enumext_mark_answer_sym_tl
3446     {
3447       \group_begin:
3448       \exp_not:N \normalfont
3449       \exp_not:N \footnotesize [ \int_eval:n
3450       {
3451         \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
3452       }
3453       ]
3454       \group_end:
3455     }
3456     \__enumext_print_keyans_box:NN \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
3457   }
3458 }

```

(End of definition for `\__enumext_starred_item_exec:`.)

### Real definition of `\item` in `keyans*`

The implementation at this point is very similar to that of the `enumext*` environment.

`\__enumext_start_item_viii:w`

```

3459 \cs_new_protected_nopar:Npn \__enumext_start_item_viii:w [#1]
3460 {
3461   \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \__enumext_stop_item_viii:
3462   \legacy_if:nT { @noitemarg }
3463   {
3464     \legacy_if_set_false:n { @noitemarg }
3465     \legacy_if:nT { @nmbrlist }
3466     {
3467       \bool_if:NT \l__enumext_hyperref_bool
3468       {
3469         \legacy_if_set_true:n { @hyper@item }
3470       }
3471     }
3472   }
3473 }

```

```

3471         \refstepcounter{enumXviii}
3472     }
3473 }

```

Here we start capturing `\item` and its contents into a group using the plain form of the `lrbox` environment.

```

3474 \group_begin:
3475 \lrbox{ \l__enumext_item_text_viii_box }
3476 \bool_if:NF \l__enumext_footnotes_key_bool
3477 {
3478     \__enumext_renew_footnote:
3479 }
3480 \bool_if:NT \l__enumext_item_starred_viii_bool
3481 {
3482     \__enumext_starred_item_exec:
3483 }
3484 \group_begin:
3485 \tl_use:N \l__enumext_label_font_style_viii_tl
3486 \bool_if:NTF \l__enumext_wrap_label_viii_bool
3487 {
3488     \makebox[ \l__enumext_labelwidth_viii_dim ][ \l__enumext_align_label_viii_str ]
3489     { \__enumext_wrapper_label_viii:n {#1} }
3490 }
3491 {
3492     \makebox[ \l__enumext_labelwidth_viii_dim ][ \l__enumext_align_label_viii_str ]{ #1
3493 }
3494 \group_end:
3495 \skip_horizontal:N \l__enumext_labelsep_viii_dim
3496 \tl_use:N \l__enumext_after_list_args_viii_tl
3497 \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_viii_dim }
3498 \skip_set_eq:NN \parindent \l__enumext_listparindent_viii_dim
3499 \skip_set_eq:NN \parskip \l__enumext_parsep_viii_skip
3500 \bool_if:NT \l__enumext_item_starred_viii_bool
3501 {
3502     \tl_use:N \l__enumext_fake_item_indent_viii_tl
3503     \__enumext_keyans_show_item_opt: \skip_horizontal:n { -\l__enumext_fake_item_indent.
3504 }
3505 {
3506     \tl_use:N \l__enumext_fake_item_indent_viii_tl
3507 }
3508 }

```

(End of definition for `\__enumext_start_item_viii:w`.)

`\__enumext_stop_item_viii:`

The function `\__enumext_stop_item_viii:` shall terminate with the capture of `\item` and its *contents*. Close the environments `minipage`, `lrbox` and the group. Then we only have to set the width of the box and print it next to `\footnote`, and add the horizontal and vertical separation between the boxes.

```

3509 \cs_new_protected_nopar:Nn \__enumext_stop_item_viii:
3510 {
3511     \__enumext_endminipage:
3512     \endlrbox
3513     \group_end:
3514     \box_set_wd:Nn \l__enumext_item_text_viii_box
3515     {
3516         \l__enumext_joined_width_viii_dim
3517         + \l__enumext_labelwidth_viii_dim
3518         + \l__enumext_labelsep_viii_dim
3519     }
3520     \int_set:Nn \hbadness { 10000 }
3521     \box_use:N \l__enumext_item_text_viii_box
3522     \bool_if:NF \l__enumext_footnotes_key_bool
3523     {
3524         \__enumext_print_footnote:
3525     }
3526     \int_compare:nNnTF { \l__enumext_item_column_pos_viii_int } = { \l__enumext_columns_viii_int }
3527     {
3528         \par\noindent
3529         \int_zero:N \l__enumext_item_column_pos_viii_int
3530     }
3531     { \hspace{ \l__enumext_columns_sep_viii_dim } }
3532 }

```

(End of definition for `\__enumext_stop_item_viii:`.)



`\__enumext_remove_extra_parsep_viii:`

Finally we will remove the vertical space equal to `\parsep` when the total number of items is divisible by the number of items in the last row of the environment.

```

3533 \cs_new_protected:Nn \__enumext_remove_extra_parsep_viii:
3534 {
3535   \int_compare:nNnT
3536   {
3537     \int_mod:nn { \g__enumext_item_count_all_viii_int } { \l__enumext_columns_viii_int }
3538   }
3539   =
3540   { \c_zero_int }
3541   {
3542     \par
3543     \vspace{ -\l__enumext_itemsep_viii_skip }
3544     \int_gzero:N \g__enumext_item_count_all_viii_int
3545   }
3546 }

```

(End of definition for `\__enumext_remove_extra_parsep_viii:`.)

### 10.37 The command `\getkeyans`

`\getkeyans`

The `\getkeyans` command takes a mandatory argument of the form `{⟨store name : position⟩}`. Retrieve a “single” content stored by `\anskey`, `\anspic*` and `\item*` from `⟨prop list⟩` defined by `save-ans` key.

```

3547 \NewDocumentCommand \getkeyans { m }
3548 {
3549   \exp_args:Ne \__enumext_getkeyans_aux:n
3550   { \tl_to_str:e { \text_expand:n {#1} } }
3551 }

```

(End of definition for `\getkeyans`. This function is documented on page 12.)

`\__enumext_getkeyans_aux:n`

The internal function `\__enumext_getkeyans_aux:n` is in charge of *splitting* the `⟨argument⟩` using `“:”`. If `“:”` is omitted it will return an error.

```

3552 \cs_new_protected:Npn \__enumext_getkeyans_aux:n #1
3553 {
3554   \str_if_in:nnTF {#1} { : }
3555   {
3556     \use:e
3557     {
3558       \cs_set:Npn \exp_not:N \__enumext_tmp:w ##1 \c_colon_str ##2 \scan_stop:
3559       { {##1} {##2} }
3560     }
3561     \exp_after:wN \__enumext_getkeyans:nn \__enumext_tmp:w #1 \scan_stop:
3562   }
3563   { \msg_error:nnn { enumext } { missing-colon } {#1} }
3564 }

```

(End of definition for `\__enumext_getkeyans_aux:n`.)

`\__enumext_getkeyans:nn`

The internal function `\__enumext_getkeyans:nn` will check for the existence of the `⟨prop list⟩`, if it does not exist it will return an error message, then it will fetch the content specified by the second `⟨argument⟩` from `⟨prop list⟩`.

```

3565 \cs_new_protected:Npn \__enumext_getkeyans:nn #1 #2
3566 {
3567   \prop_if_exist:cF { g__enumext_#1_prop }
3568   { \msg_error:nnn { enumext } { undefined-storage-anskey } {#1} }
3569   \group_begin:
3570   \prop_item:cn { g__enumext_#1_prop }{#2}
3571   \group_end:
3572 }

```

(End of definition for `\__enumext_getkeyans:nn`.)

### 10.38 The command \printkeyans

The `\printkeyans` command prints “all stored content” in the *sequence* defined by the `save-ans` key. The first thing we will do is to define a set of *keys* with which we will control the options of the different nesting levels for the `enumext` and `enumext*` environment by storing the values of these in the token list variables `\l__enumext_print_keyans_X_tl`.

```

3573 \keys_define:nn { keyanskey / print }
3574 {
3575   level-1 .code:n = \tl_put_right:Nn \l__enumext_print_keyans_i_tl
3576                 {
3577                   \setenumext[level,1] {#1} \setenumext[print,1] {#1}
3578                 },
3579   level-1 .initial:n = { label=\arabic*., nosep, columns=2, first=\small, font=\small },
3580   level-2 .code:n = \tl_put_right:Nn \l__enumext_print_keyans_ii_tl
3581                 {
3582                   \setenumext[level,2] {#1} \setenumext[print,2] {#1}
3583                 },
3584   level-2 .initial:n = { nosep, label=(\alph*), first=\small, font=\small },
3585   level-3 .code:n = \tl_put_right:Nn \l__enumext_print_keyans_iii_tl
3586                 {
3587                   \setenumext[level,3] {#1} \setenumext[print,3] {#1}
3588                 },
3589   level-3 .initial:n = { nosep, label=\roman*., first=\small, font=\small },
3590   level-4 .code:n = \tl_put_right:Nn \l__enumext_print_keyans_iv_tl
3591                 {
3592                   \setenumext[level,4] {#1} \setenumext[print,4] {#1}
3593                 },
3594   level-4 .initial:n = { nosep, label=\Alph*., first=\small, font=\small },
3595   level-* .code:n = \tl_put_right:Nn \l__enumext_print_keyans_vii_tl % starred
3596                 {
3597                   \setenumext[enumext*] {#1} %%\setenumext[print,*] {#1}
3598                 },
3599   level-* .initial:n = { label=\arabic*., nosep, columns=2, first=\small, font=\small },
3600 }

```

`\printkeyans` Create a user command to print “all stored content” in *sequence* for `\anskey`, `\item*` and `\anspic*`.

```

3601 \NewDocumentCommand \printkeyans { s O{} m }
3602 {
3603   \group_begin:
3604     \tl_use:N \l__enumext_print_keyans_i_tl
3605     \tl_use:N \l__enumext_print_keyans_ii_tl
3606     \tl_use:N \l__enumext_print_keyans_iii_tl
3607     \tl_use:N \l__enumext_print_keyans_iv_tl
3608     \tl_use:N \l__enumext_print_keyans_vii_tl
3609     \__enumext_printkeyans:nnn { #1 } { #2 } { #3 }
3610   \group_end:
3611 }

```

(End of definition for `\printkeyans`. This function is documented on page 12.)

`\__enumext_printkeyans:nnn` The internal function `\__enumext_printkeyans:nnn` will check for the existence of the *sequence*, if it does not exist it will return an error message, then it will fetch the content specified by the first argument mapping the *sequence*.

#1: starred  
#2: key-val  
#3: seq-name

```

3612 \cs_new_protected:Npn \__enumext_printkeyans:nnn #1 #2 #3
3613 {
3614   \seq_if_exist:cTF { g__enumext_#3_seq }
3615   {
3616     \seq_if_empty:cF { g__enumext_#3_seq }
3617     {
3618       %%\seq_show:c { g__enumext_#3_seq }
3619       \bool_if:nTF {#1}
3620       {
3621         \begin{enumext*}[#2]
3622         \seq_map_inline:cn { g__enumext_#3_seq } { ##1 }
3623         \end{enumext*}
3624       }
3625     }

```

```

3626         \begin{enumext}[#2]
3627         \seq_map_inline:cn { g__enumext_#3_seq } { ##1 }
3628         \end{enumext}
3629     }
3630 }
3631 }
3632 {
3633     \msg_error:nnn { enumext } { undefined-storage-anskey } {#3}
3634 }
3635 }

```

(End of definition for `\__enumext_printkeyans:nnn`.)

### 10.39 The command `\setenumext`

First we define a “meta families” of *(keys)* to access from `\setenumext`.

```

3636 \keys_define:nn { enumext / meta-families }
3637 {
3638     level-1 .code:n = { \keys_set:nn { enumext / level-1 } {#1} } ,
3639     level-2 .code:n = { \keys_set:nn { enumext / level-2 } {#1} } ,
3640     level-3 .code:n = { \keys_set:nn { enumext / level-3 } {#1} } ,
3641     level-4 .code:n = { \keys_set:nn { enumext / level-4 } {#1} } ,
3642     keyans .code:n = { \keys_set:nn { enumext / keyans } {#1} } ,
3643     enumext* .code:n = { \keys_set:nn { enumext / enumext* } {#1} } ,
3644     keyans* .code:n = { \keys_set:nn { enumext / keyans* } {#1} } ,
3645     print-1 .code:n = { \keys_set:nn { keyanskey / print } { level-1 = {#1} } } ,
3646     print-2 .code:n = { \keys_set:nn { keyanskey / print } { level-2 = {#1} } } ,
3647     print-3 .code:n = { \keys_set:nn { keyanskey / print } { level-3 = {#1} } } ,
3648     print-4 .code:n = { \keys_set:nn { keyanskey / print } { level-4 = {#1} } } ,
3649     print-* .code:n = { \keys_set:nn { keyanskey / print } { level-* = {#1} } } ,
3650     unknown .code:n = { \msg_error:nn { enumext } { unknown-key-family } } ,
3651 }

```

We store them in the constant sequence `\c__enumext_all_families_seq` separated by commas.

```

3652 \seq_const_from_clist:Nn \c__enumext_all_families_seq
3653 {
3654     level-1 , level-2 , level-3 , level-4 , keyans, enumext*,
3655     keyans* , print-1 , print-2 , print-3 , print-4 , print-*,
3656 }

```

`\setenumext` Now we define the user command `\setenumext`.

```

3657 \NewDocumentCommand \setenumext { o +m }
3658 {
3659     \tl_if_novalue:nTF {#1}
3660     {
3661         \seq_map_inline:Nn \c__enumext_all_families_seq
3662     }
3663     {
3664         \seq_clear:N \l__enumext_setkey_tmpa_seq
3665         \seq_set_from_clist:Nn \l__enumext_setkey_tmpb_seq {#1}
3666         \int_set:Nn \l__enumext_setkey_tmpa_int
3667         {
3668             \seq_count:N \l__enumext_setkey_tmpb_seq
3669         }
3670         \int_compare:nNnTF { \l__enumext_setkey_tmpa_int } > { 1 }
3671         {
3672             \seq_pop_left:NN \l__enumext_setkey_tmpb_seq \l__enumext_setkey_tmpa_tl
3673             \seq_map_function:NN \l__enumext_setkey_tmpb_seq \l__enumext_set_parse:n
3674             \seq_set_map_e:NNn \l__enumext_setkey_tmpa_seq \l__enumext_setkey_tmpa_seq
3675             {
3676                 \tl_use:N \l__enumext_setkey_tmpa_tl - ##1
3677             }
3678         }
3679         {
3680             \seq_put_right:Ne \l__enumext_setkey_tmpa_seq { \tl_trim_spaces:n {#1} }
3681         }
3682         \seq_if_empty:NTF \l__enumext_setkey_tmpa_seq
3683         { \seq_map_inline:Nn \c__enumext_all_families_seq }
3684         { \seq_map_inline:Nn \l__enumext_setkey_tmpa_seq }
3685     }
3686     {
3687         \keys_set:nn { enumext / meta-families } { ##1 = {#2} }

```

```

3688     }
3689 }

```

(End of definition for `\setenumext`. This function is documented on page 5.)

```

\__enumext_set_parse:n
\__enumext_set_error:nn

```

Internal functions used by the `\setenumext` command.

```

3690 \cs_new_protected:Npn \__enumext_set_parse:n #1
3691 {
3692   \tl_set:Nx \l__enumext_setkey_tmpb_tl { \tl_trim_spaces:n {#1} }
3693   \int_step_inline:nnn { 0 } { 4 } {%< max level
3694     { \tl_remove_all:Nn \l__enumext_setkey_tmpb_tl {##1} }
3695   \tl_if_empty:NTF \l__enumext_setkey_tmpb_tl
3696     {
3697       \seq_put_right:Nx \l__enumext_setkey_tmpa_seq
3698         { \tl_trim_spaces:n {#1} }
3699     }
3700     { \__enumext_set_error:nn {#1} { } }
3701   }
3702 \cs_new_protected:Npn \__enumext_set_error:nn #1 #2
3703 { \msg_error:nnn { enumext } { invalid-key } {#1} {#2} }

```

(End of definition for `\__enumext_set_parse:n` and `\__enumext_set_error:nn`.)

## 10.40 Messages

Message used by package-load for `multicol` and `hyperref` packages.

```

3704 \msg_new:nnn { enumext } { package-load }
3705 {
3706   The ~ '#1' ~ package ~ is ~ already ~ loaded.
3707 }
3708 \msg_new:nnn { enumext } { package-not-load }
3709 {
3710   The ~ '#1' ~ package ~ will ~ be ~ loaded ~ as ~ a ~ dependency.
3711 }
3712 \msg_new:nnn { enumext } { package-load-foot }
3713 {
3714   The ~ '#1' ~ package ~ is ~ loaded ~ with ~ the ~ option ~ '#2'.
3715 }

```

Message used in the creation of counters by `enumext` package.

```

3716 \msg_new:nnn { enumext } { counters }
3717 {
3718   The ~ counter ~ '#1' ~ is ~ already ~ defined ~ by ~ some ~ \
3719   package ~ or ~ macro, ~ it ~ cannot ~ be ~ continued.
3720 }

```

Message used by `[\langle key = val \rangle]` system and `\setenumext` command.

```

3721 \msg_new:nnn { enumext } { invalid-key }
3722 {
3723   The ~ key ~ '#1' ~ is ~ not ~ know ~ the ~ level ~ #2.
3724 }
3725 \msg_new:nnn { enumext } { unknown-key-family }
3726 {
3727   Unknown~key~family~`\l_keys_key_str'~for~enumext.
3728 }

```

Messages used in length calculation.

```

3729 \msg_new:nnn { enumext } { width-negative }
3730 {
3731   Ignoring ~ negative ~ value ~ '#1=#2' ~ \msg_line_context:.\
3732   The ~ key ~ '#1'~ accepts ~ values ~ >= ~ opt.
3733 }
3734 \msg_new:nnn { enumext } { width-zero }
3735 {
3736   Invalid ~ '#1=#2' ~ \msg_line_context:.\
3737   The ~ key ~ '#1'~ accepts ~ values ~ > ~ opt.
3738 }

```

Messages used by `show-length` key in `enumext`.

```

3739 \msg_new:nnn { enumext } { list-lengths }
3740 {
3741   **** ~ Lengths ~ used ~ by ~ 'enumext' ~ level ~ '#2' ~ \msg_line_context:~\c_space_tl ****\\
3742   \__enumext_show_length:nnn { dim } { labelsep } {#1}
3743   \__enumext_show_length:nnn { dim } { labelwidth } {#1}
3744   \__enumext_show_length:nnn { dim } { itemindent } {#1}
3745   \__enumext_show_length:nnn { dim } { leftmargin } {#1}
3746   \__enumext_show_length:nnn { dim } { rightmargin } {#1}
3747   \__enumext_show_length:nnn { dim } { listparindent } {#1}
3748   \__enumext_show_length:nnn { skip } { topsep } {#1}
3749   \__enumext_show_length:nnn { skip } { parsep } {#1}
3750   \__enumext_show_length:nnn { skip } { partopsep } {#1}
3751   \__enumext_show_length:nnn { skip } { itemsep } {#1}
3752   *****
3753 }

```

Messages used by `show-length` key in `enumext*`, `keyans*` and `keyans`.

```

3754 \msg_new:nnn { enumext } { list-lengths-not-nested }
3755 {
3756   **** ~ Lengths ~ used ~ by ~ '#2' ~ environment ~ \msg_line_context:~\c_space_tl ****\\
3757   \__enumext_show_length:nnn { dim } { labelsep } {#1}
3758   \__enumext_show_length:nnn { dim } { labelwidth } {#1}
3759   \__enumext_show_length:nnn { dim } { itemindent } {#1}
3760   \__enumext_show_length:nnn { dim } { leftmargin } {#1}
3761   \__enumext_show_length:nnn { dim } { rightmargin } {#1}
3762   \__enumext_show_length:nnn { dim } { listparindent } {#1}
3763   \__enumext_show_length:nnn { skip } { topsep } {#1}
3764   \__enumext_show_length:nnn { skip } { parsep } {#1}
3765   \__enumext_show_length:nnn { skip } { partopsep } {#1}
3766   \__enumext_show_length:nnn { skip } { itemsep } {#1}
3767   *****
3768 }

```

Messages used by the internal system to check answer used by `check-ans` key.

```

3769 \msg_new:nnn { enumext } { items-same-answer }
3770 {
3771   *****~Checking~answers~on~'#1'~OK~*****\\
3772   **~ All ~ items ~ stored ~ in ~ sequence ~ '#1' ~ have ~ an ~ answer. \\
3773   *****
3774   \prg_replicate:nn { 7 + \str_count:n {#1} } { * }
3775 }
3776 \msg_new:nnn { enumext } { item-different-answer }
3777 {
3778   Number ~ of ~ items ~ different ~ of ~ number ~ of ~
3779   answer ~ in ~ sequence ~ '#1'~ closed ~ \msg_line_context:.
3780 }

```

Messages used by the internal system to check for “starred” `\item*` commands.

```

3781 \msg_new:nnn { enumext } { missing-starred }
3782 {
3783   Missing ~ '\c_backslash_str #1*' ~ in ~ '#2' ~ \msg_line_context:.
3784 }

```

Message for the nesting depth of the environment `enumext`.

```

3785 \msg_new:nnn { enumext } { list-too-deep }
3786 {
3787   Too ~ deep ~ nesting ~ for ~ 'enumext' ~ \msg_line_context:.. \\
3788   The ~ maximum ~ level ~ of ~ nesting ~ is ~ 4.
3789 }

```

Messages used by `\anskey` and `\anspic` commands.

```

3790 \msg_new:nnn { enumext } { anskey-wrong-place }
3791 {
3792   Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:.. \\
3793   '\c_backslash_str #1' ~ works ~ in ~ the ~ environment ~ '#2'.
3794 }
3795 \msg_new:nnn { enumext } { anspic-wrong-place }
3796 {
3797   Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:.. \\
3798   '\c_backslash_str #1' ~ works ~ in ~ the ~ environment ~ '#2'.
3799 }
3800 \msg_new:nnn { enumext } { command-wrong-place }

```

```

3801 {
3802     Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
3803     '\c_backslash_str #1' ~ works ~ outside ~ the ~ environment ~ '#2'.
3804 }

```

Messages used by `keyans` and `keyanspic` environment.

```

3805 \msg_new:nnn { enumext } { keyans-nested }
3806 {
3807     The ~ environment ~ 'keyans' ~ can't ~ be ~ nested ~ \msg_line_context:.
3808 }
3809 \msg_new:nnn { enumext } { keyans-wrong-level }
3810 {
3811     Wrong ~ level ~ position ~ for ~ 'keyans' ~ \msg_line_context:~ \\
3812     The ~ environment ~ 'keyans' ~ can ~ only ~ be ~ in ~ the ~ first ~ level.
3813 }
3814 \msg_new:nnn { enumext } { wrong-place }
3815 {
3816     Wrong ~ place ~ for ~ '#1' ~ environment ~ \msg_line_context:~ \\
3817     '#1' ~ is ~ only ~ found ~ with ~ '#2' ~ in ~ 'enumext'.
3818 }
3819 \msg_new:nnn { enumext } { keyanspic-nested }
3820 {
3821     The ~ environment ~ 'keyanspic' ~ can't ~ be ~ nested ~ \msg_line_context:~.
3822 }
3823 \msg_new:nnn { enumext } { keyanspic-wrong-level }
3824 {
3825     Wrong ~ level ~ position ~ for ~ 'keyanspic' ~ \msg_line_context:~ \\
3826     The ~ environment ~ 'keyans' ~ can ~ only ~ be ~ in ~ the ~ first ~ level.
3827 }

```

Messages used by `\getkeyans` command.

```

3828 \msg_new:nnn { enumext } { undefined-storage-anskey }
3829 {
3830     Storage ~ named ~ '#1' ~ is ~ not ~ defined ~ \msg_line_context:.
3831 }

```

Messages used by `\miniright` command.

```

3832 \msg_new:nnn { enumext } { missing-miniright }
3833 {
3834     Missing ~ '\c_backslash_str miniright' ~ in ~ \msg_line_context:~ \\
3835     The ~ key ~ 'mini-env' ~ need ~ '\c_backslash_str miniright'.
3836 }
3837 \msg_new:nnn { enumext } { wrong-miniright-place }
3838 {
3839     Wrong ~ place ~ for ~ '\c_backslash_str miniright' ~ \msg_line_context:~ \\
3840     Works ~ in ~ 'enumext' ~ and ~ 'keyans' ~ with ~ key ~ 'mini-env'.
3841 }
3842 \msg_new:nnn { enumext } { wrong-miniright-use }
3843 {
3844     Wrong ~ use ~ for ~ '\c_backslash_str miniright' ~ \msg_line_context:~ \\
3845     '\c_backslash_str miniright' ~ need ~ a ~ key ~ 'mini-env'.
3846 }

```

Messages used by `enumext*` and `keyans*` environments.

```

3847 \msg_new:nnn { enumext } { nested }
3848 {
3849     The ~ starred ~ environment ~ can't ~ be ~ nested ~ \msg_line_context:.
3850 }
3851 \msg_new:nnn { enumext } { item-joined }
3852 {
3853     Items ~ joined ~ (#1) ~ > ~ #2 ~ columns ~ \msg_line_context:.
3854 }
3855 \msg_new:nnn { enumext } { item-joined-columns }
3856 {
3857     Not ~ space ~ to ~ join ~ items ~ (#1) ~ > ~ #2 ~ \msg_line_context:.
3858 }

```

## 10.41 Finish package

Finish package implementation.

```

3859 \file_input_stop:
3860 </package>

```

# 11 Index of Implementation

The italic numbers denote the pages where the corresponding entry is described, the numbers underlined and all others indicate the line on which they are implemented in the package code.

Symbols

\\*

.....

417

\+

.....

194

\-

.....

194

\\

202, 2694, 3718, 3731, 3736, 3741, 3756, 3771, 3772, 3787, 3792, 3797, 3802, 3811, 3816, 3825, 3834, 3839, 3844

A

above

.....

1228

above\*

.....

1228

\addvspace

875, 903, 1026, 1105, 1168, 1174, 1202, 1219, 2510, 2532, 2650, 2665, 2889, 2896, 3300, 3307

after

.....

713

align

.....

371

\Alph

.....

30, 35

\Alph

.....

323, 500, 518, 531, 3594

\alph

.....

30, 35

\alph

.....

324, 498, 3584

\anskey

.....

11, 58, 1643

\anspic

.....

13, 79, 2672

\arabic

.....

30, 32

\arabic

.....

322, 497, 517, 3579, 3599

B

\b

.....

2388, 2401, 2951, 2964

\baselineskip

.....

42

\baselineskip

.....

1603, 1611

before

.....

713

before\*

.....

713

below

.....

1228

below\*

.....

1228

bool commands:

\bool\_gset\_false:N

2554, 2555, 2898, 3002, 3194, 3195, 3309

\bool\_gset\_true:N

220, 229, 817, 2517, 2881, 2899, 2999, 3292, 3310

\bool\_if:NTF

263, 275, 292, 1250, 1264, 1277, 1288, 1299, 1310, 1321, 1332, 1375, 1386, 1441, 1451, 1565, 1589, 1596, 1624, 1655, 1668, 1670, 1681, 1701, 1826, 1837, 1841, 1880, 1895, 1968, 1987, 1991, 2104, 2134, 2207, 2223, 2291, 2301, 2337, 2342, 2379, 2386, 2399, 2444, 2494, 2508, 2523, 2550, 2579, 2635, 2648, 2656, 2674, 2877, 2886, 2890, 2941, 2949, 2962, 3007, 3017, 3100, 3105, 3113, 3117, 3132, 3161, 3190, 3288, 3297, 3301, 3439, 3443, 3467, 3476, 3480, 3486, 3500, 3522

\bool\_if:nTF

1203, 1220, 1709, 2145, 2179, 2243, 2695, 3619

\bool\_if\_p:N

1420, 1692, 1735, 1736, 1760, 1769, 1770, 1782, 1798, 1954, 1955, 2001, 2002, 2280, 2327, 2417, 2430, 2432, 2514, 2701, 2702, 2996, 2997

\bool\_lazy\_all:nTF

1418, 1758, 1767, 1780, 1796, 2415, 2428

\bool\_lazy\_and:nnTF

1691, 1734, 1953, 2278, 2326, 2513, 2995

\bool\_lazy\_or:nnTF

2000, 2700

\bool\_new:N

25, 26, 27, 28, 29, 35, 37, 46, 67, 72, 73, 78, 79, 82, 102, 104, 106, 109, 110, 119, 120, 121, 122, 131, 132, 157, 168, 170

\bool\_not\_p:n

1693, 1785, 1800, 2418, 2419, 2431, 2515

\bool\_set\_eq:NN

2112, 2160, 3050, 3394

\bool\_set\_false:N

272, 1402, 1403, 2537, 2586, 2668, 2732, 2749, 3003, 3047, 3344, 3391

\bool\_set\_true:N

254, 258, 364, 641, 1234, 1239, 1366, 1367, 1382, 1393, 1527, 1534, 2108, 2138, 2156, 2168, 2373, 2424, 2437, 2463, 2584, 2610, 2866, 2934, 3056, 3063, 3064, 3277, 3400, 3407, 3408

box commands:

\box\_dp:N

922, 926, 930, 941, 945, 956, 965, 971, 981, 994, 1000, 1006, 1037, 1038, 1039, 1042, 1052, 1056, 1065, 1072, 1077, 1085, 1114, 1115, 1118, 1125, 1138, 1146, 1152, 1160, 2761

\box\_new:N

43, 163

\box\_set\_wd:Nn

3153, 3514

\box\_use:N

3160, 3521

\box\_wd:N

330

C

\c

417, 418, 541, 543, 555, 557

\cB

418

\cE

418

\centering

1205, 1222, 2782, 2892, 3303

check-ans

1395

Document class:

article

36

clist commands:

\clist\_const:Nn

175

\clist\_map\_function:nN

2769

\clist\_map\_inline:Nn

370, 583, 646, 712, 727, 808, 1244

\clist\_map\_inline:nn

34, 51, 57, 69, 81, 108, 140, 154, 174, 210, 395, 412, 651, 823, 1408, 1504, 1522, 1543, 1755, 1889, 2062, 2272, 2275, 2308, 2318, 2321, 2347

\columnbreak

58

\columnbreak

1695

columns

792

columns\*

1523

columns-sep

792

columns-sep\*

1523

\columnsep

75, 78

\columnsep

2488, 2632

\columnseprule

75, 78

\columnseprule

2492, 2634

Commands provide by enumext:

\anskey

24, 25, 51, 53, 56, 58, 60–62, 64, 73, 86, 97, 98, 101

\anspic\*

24, 62–64, 79, 80, 82, 97, 98

\anspic

56, 79–81, 101

\getkeyans

56, 97, 102

\item\*

24, 56, 62–64, 67, 68, 88, 94, 95, 97, 98

\itemwidth

82, 83, 90, 91

\item

66, 68, 83, 87, 88, 91, 93, 94

\miniright

24, 40, 48, 49, 74, 76, 78, 79, 102

\printkeyans

25, 56, 98

\setenumext

24, 99, 100

Counters defined by enumext:

enumXiii

23, 30

enumXii

23, 30

enumXiv

23, 30

enumXi

23, 30

enumXviii

23, 30

©2024 by Pablo González L

103 / 113



enumXvii ..... 23, 30, 88  
enumXvi ..... 23, 30  
enumXv ..... 23, 30  
cs commands:  
\cs\_generate\_variant:Nn 332, 348, 547, 563, 1548,  
1557, 1562, 1642, 2262, 2771  
\cs\_if\_exist:NTF ..... 302  
\cs\_new:Nn ..... 188  
\cs\_new:Npn ..... 198  
\cs\_new\_eq:NN 238, 239, 240, 244, 245, 277, 278, 281,  
282  
\cs\_new\_protected:Nn . 212, 249, 413, 433, 465, 728,  
732, 736, 740, 744, 748, 752, 756, 760, 764, 768, 772,  
776, 780, 784, 788, 824, 836, 860, 877, 888, 912, 987,  
1011, 1028, 1090, 1107, 1129, 1164, 1170, 1245, 1259,  
1273, 1284, 1295, 1306, 1317, 1328, 1373, 1384, 1413,  
1449, 1456, 1563, 1587, 1594, 1622, 1629, 1746, 1878,  
1893, 1921, 1951, 1996, 2008, 2015, 2067, 2071, 2090,  
2141, 2175, 2191, 2201, 2217, 2368, 2413, 2442, 2449,  
2472, 2502, 2521, 2577, 2600, 2618, 2643, 2654, 2691,  
2734, 2747, 2767, 2772, 2788, 2856, 2875, 2927, 2976,  
2983, 3005, 3015, 3032, 3172, 3199, 3267, 3286, 3336,  
3357, 3363, 3376, 3432, 3533  
\cs\_new\_protected:Npn 180, 184, 285, 300, 317, 327,  
333, 421, 440, 534, 548, 1192, 1211, 1355, 1549, 1558,  
1678, 1823, 1835, 1857, 1931, 1973, 1981, 2100, 2118,  
2152, 2164, 2231, 2265, 2311, 2375, 2384, 2596, 2742,  
2807, 2936, 2947, 3038, 3045, 3061, 3069, 3074, 3086,  
3218, 3350, 3382, 3389, 3405, 3413, 3427, 3552, 3565,  
3612, 3690, 3702  
\cs\_new\_protected\_nopar:Nn ... 3025, 3148, 3369,  
3509  
\cs\_new\_protected\_nopar:Npn ..... 3092, 3459  
\cs\_set:Nn ..... 1828  
\cs\_set:Npn ..... 1756, 1794, 3558  
\cs\_set\_eq:NN .. 2917, 2918, 3094, 3326, 3327, 3461  
\cs\_set\_protected:Nn .... 204, 652, 668, 680, 692  
\cs\_set\_protected:Npn . 30, 44, 52, 64, 70, 98, 136,  
148, 155, 206, 349, 371, 400, 481, 501, 564, 584, 628,  
647, 704, 713, 792, 809, 1228, 1395, 1469, 1505, 1523,  
1748, 1882, 2051, 2263, 2309  
\cs\_to\_str:N ..... 319, 342

## D

\d ..... 194  
\DeclareDocumentEnvironment ..... 905  
dim commands:  
\dim\_abs:n ..... 2236, 2241  
\dim\_add:Nn ..... 2752  
\dim\_compare:nNnTF . 654, 670, 682, 694, 1194, 1213,  
2233, 2238, 2244, 2250, 2252, 2254, 2454, 2477, 2604,  
2622, 2744, 2790, 2858, 3201, 3269  
\dim\_compare:nTF ..... 1719  
\dim\_gset\_eq:NN ..... 2867, 3278  
\dim\_gzero:N ..... 2901, 3312  
\dim\_new:N 40, 47, 48, 49, 66, 92, 105, 115, 164, 165, 171  
\dim\_set:Nn .. 330, 642, 1535, 2132, 2236, 2241, 2243,  
2246, 2247, 2251, 2253, 2256, 2257, 2259, 2457, 2480,  
2606, 2624, 2774, 2792, 2799, 2842, 2860, 3088, 3203,  
3210, 3253, 3271  
\dim\_set\_eq:NN 488, 508, 524, 528, 2127, 2274, 2320,  
2403, 2488, 2632, 2849, 2852, 2853, 2966, 3079, 3260,  
3263, 3264  
\dim\_use:N 655, 663, 1195, 1201, 1632, 1635, 1640, 2196,  
2198, 2455, 2460, 2461, 2468, 2478, 2482, 2483, 2485  
\dim\_zero:N ..... 2492, 2634, 2753, 2754, 2755

\dim\_zero\_new:N ..... 2805, 3216  
\c\_zero\_dim 657, 671, 683, 695, 1195, 1213, 1721, 2233,  
2238, 2244, 2251, 2455, 2478, 2604, 2622, 2790, 2858,  
3201, 3269

## E

\end .. 1198, 1216, 1591, 1626, 2507, 2531, 2647, 2664, 2879,  
2895, 3290, 3306, 3623, 3628  
\endlist ..... 28  
\endlist ..... 239  
\endlrbox ..... 3151, 3512  
\endminipage ..... 28  
\endminipage ..... 245  
enumext ..... 5, 2348  
enumext internal commands:

\g\_\_enumext\_ \\_\_enumext\_store\_name\_tl  
\_prop ..... 64  
\\_\_enumext\_add\_pre\_parsep: ... 41, 834, 836, 836  
\\_\_enumext\_after\_args\_exec: . 39, 728, 740, 2361  
\\_\_enumext\_after\_args\_exec\_v: . 39, 40, 744, 756,  
2570  
\\_\_enumext\_after\_args\_exec\_vii: ... 760, 784  
\\_\_enumext\_after\_args\_exec\_viii: ..... 788  
\\_\_enumext\_after\_env:n ..... 75  
\\_\_enumext\_after\_env:nn .. 76, 90, 184, 184, 2546,  
2884, 3186, 3295  
\\_\_enumext\_after\_hyperref: ... 28, 247, 249, 249  
\\_\_enumext\_after\_list: 76, 86, 93, 2366, 2521, 2521  
\l\_\_enumext\_after\_list\_args\_v\_tl ..... 758  
\l\_\_enumext\_after\_list\_args\_vii\_tl 786, 3142  
\l\_\_enumext\_after\_list\_args\_viii\_tl 790, 3496  
\\_\_enumext\_after\_list\_v: .. 79, 2575, 2654, 2654  
\\_\_enumext\_after\_list\_vii: ... 2925, 2983, 2983  
\\_\_enumext\_after\_list\_viii: .. 3334, 3363, 3363  
\\_\_enumext\_after\_star\_env:nn ..... 84  
\\_\_enumext\_after\_stop\_list: ... 38, 40, 728, 736,  
2535  
\\_\_enumext\_after\_stop\_list\_v: 39, 744, 752, 2669  
\l\_\_enumext\_after\_stop\_list\_v\_tl ..... 754  
\\_\_enumext\_after\_stop\_list\_vii: 760, 776, 2986  
\l\_\_enumext\_after\_stop\_list\_vii\_tl ... 778  
\\_\_enumext\_after\_stop\_list\_viii: . 780, 3366  
\l\_\_enumext\_after\_stop\_list\_viii\_tl ... 782  
\l\_\_enumext\_align\_label\_vii\_str .. 3134, 3138  
\l\_\_enumext\_align\_label\_viii\_str . 3488, 3492  
\l\_\_enumext\_align\_label\_X\_str ..... 155  
\c\_\_enumext\_all\_envs\_clist .. 175, 370, 583, 646,  
712, 727, 808, 1244  
\c\_\_enumext\_all\_families\_seq .. 99, 3652, 3661,  
3683  
\\_\_enumext\_anskey\_wrapper:n ..... 1473, 1833  
\\_\_enumext\_at\_begin\_document:n .. 28, 180, 180,  
236, 242  
\\_\_enumext\_before\_args\_exec: 38, 728, 728, 2452  
\\_\_enumext\_before\_args\_exec\_v: .. 39, 744, 744,  
2603  
\\_\_enumext\_before\_args\_exec\_vii: .. 760, 760,  
2980  
\\_\_enumext\_before\_args\_exec\_viii: 764, 3360  
\\_\_enumext\_before\_keys\_exec: 38, 728, 732, 2359  
\\_\_enumext\_before\_keys\_exec\_v: .. 39, 744, 748,  
2568  
\\_\_enumext\_before\_keys\_exec\_vii ..... 760  
\\_\_enumext\_before\_keys\_exec\_vii: 39, 768, 2913



```

\__enumext_before_keys_exec_viii: .. 39, 772,
    3322
\__enumext_before_list: ... 74, 2353, 2449, 2449
\__enumext_before_list_v: . 77, 2563, 2600, 2600
\__enumext_before_list_vii: 86, 2908, 2976, 2976
\__enumext_before_list_viii: .. 93, 3318, 3357,
    3357
\l__enumext_before_no_starred_key_v_tl 750
\l__enumext_before_no_starred_key_vii_-
    tl ..... 770
\l__enumext_before_no_starred_key_viii_-
    tl ..... 774
\l__enumext_before_starred_key_v_tl ... 746
\l__enumext_before_starred_key_vii_tl . 762
\l__enumext_before_starred_key_viii_tl 766
\__enumext_calc_hspace:NNNNNNN 69, 2231, 2231,
    2262, 2267, 2313
\l__enumext_check_ans_bool 51, 66, 67, 119, 1399,
    1403, 1451, 1670, 1968, 2104, 2134, 2514, 2997, 3105
\__enumext_check_ans_exec: .. 54, 74, 1449, 1449,
    2453, 2979
\__enumext_check_ans_int:n ..... 51
\g__enumext_check_ans_item_tl .. 63, 119, 1967,
    1975, 1979
\__enumext_check_ans_set: . 53, 1413, 1413, 1453
\__enumext_check_ans_show: 54, 1456, 1456, 2552,
    3192
\g__enumext_check_ans_show_bool 75, 119, 2517,
    2550, 2555
\g__enumext_check_ans_show_h_bool 119, 2999,
    3190, 3195
\l__enumext_columns_sep_v_dim 2622, 2624, 2632
\l__enumext_columns_sep_vii_dim .. 2790, 2792,
    2801, 2846, 2968, 3170
\l__enumext_columns_sep_viii_dim . 3201, 3203,
    3212, 3257, 3531
\l__enumext_columns_v_int 1033, 2620, 2628, 2640,
    2645
\l__enumext_columns_vii_int .. 2795, 2798, 2802,
    2810, 2814, 2817, 2823, 2829, 2833, 2955, 3165, 3176
\l__enumext_columns_viii_int . 3206, 3209, 3213,
    3221, 3225, 3228, 3234, 3240, 3244, 3526, 3537
\g__enumext_count_item_anskey_int .. 63, 119,
    1459, 1467, 1672, 1970
\g__enumext_count_item_number_int 119, 1424,
    1429, 1432, 1435, 1443, 1459, 1466, 2106, 2136, 3107
\g__enumext_count_item_with_ans_int .... 58
\l__enumext_counter_i_tl ..... 30, 309
\l__enumext_counter_ii_tl ..... 30, 310
\l__enumext_counter_iii_tl ..... 30, 311
\l__enumext_counter_iv_tl ..... 30, 312
\l__enumext_counter_style_for_ref_vii_-
    tl ..... 448, 458, 469, 471
\l__enumext_counter_style_for_ref_viii_-
    tl ..... 475, 477
\l__enumext_counter_style_for_ref_X_tl 144
\c__enumext_counter_style_tl .... 32, 144, 415
\g__enumext_counter_styles_tl . 23, 30, 40, 320,
    338
\l__enumext_counter_v_tl ..... 30, 313
\l__enumext_counter_vi_tl ..... 30, 314
\l__enumext_counter_vii_tl ..... 30, 315, 445
\l__enumext_counter_viii_tl ..... 30, 316, 455
\__enumext_current_env: 27, 212, 212, 2350, 2905
\l__enumext_current_widest_dim 23, 40, 344, 489,
    509, 525, 529
\__enumext_default_item:n ... 2100, 2100, 2149
\__enumext_define_counters:Nn 23, 300, 300, 309,
    310, 311, 312, 313, 314, 315, 316
\__enumext_endminipage: . 28, 242, 245, 911, 2784,
    3150, 3511
\__enumext_fake_item: ..... 652, 652, 2300
\l__enumext_fake_item_indent_v_dim 671, 676
\l__enumext_fake_item_indent_v_tl 673, 2157,
    2161, 2169
\l__enumext_fake_item_indent_vii_dim 683, 688
\l__enumext_fake_item_indent_vii_tl 685, 3146
\l__enumext_fake_item_indent_viii_dim . 695,
    700, 3503
\l__enumext_fake_item_indent_viii_tl .. 697,
    3502, 3506
\l__enumext_fake_item_indent_X_tl ..... 70
\__enumext_fake_item_vii: .... 652, 680, 2336
\__enumext_fake_item_viii: .... 652, 692, 2341
\g__enumext_footnote_arg_seq . 141, 2073, 2086,
    2096
\g__enumext_footnote_int . 141, 2080, 2083, 2085,
    2087
\g__enumext_footnote_int_seq . 141, 2074, 2087,
    2092, 2095
\__enumext_footnotes_key_bool ..... 28
\l__enumext_footnotes_key_bool 25, 29, 89, 131,
    258, 263, 272, 3113, 3161, 3476, 3522
\__enumext_footnotetext:nn ... 2067, 2067, 2097
\__enumext_getkeyans:nn ... 97, 3561, 3565, 3565
\__enumext_getkeyans_aux:n . 97, 3549, 3552, 3552
\l__enumext_hyperref_bool . 25, 28, 29, 131, 254,
    275, 292, 1736, 1955, 3100, 3467
\__enumext_hypertarget:nn 29, 249, 277, 281, 297
\__enumext_if_is_int:n ..... 192
\__enumext_if_is_int:nTF ..... 192, 536, 550
\l__enumext_item_column_pos_vii_int 87, 2817,
    2823, 2829, 2833, 2840, 3028, 3165, 3168
\l__enumext_item_column_pos_viii_int ... 93,
    3228, 3234, 3240, 3244, 3251, 3372, 3526, 3529
\l__enumext_item_column_pos_X_int ..... 155
\g__enumext_item_count_all_vii_int 87, 2841,
    3029, 3176, 3183
\g__enumext_item_count_all_viii_int 93, 3252,
    3373, 3537, 3544
\g__enumext_item_count_all_X_int ..... 155
\__enumext_item_peek_args_vii: 87, 3030, 3032,
    3032
\__enumext_item_peek_args_viii: . 93, 94, 3374,
    3376, 3376
\__enumext_item_starred: .. 69, 2191, 2191, 2209
\l__enumext_item_starred_vii_bool 3047, 3063,
    3117
\l__enumext_item_starred_viii_bool 3391, 3407,
    3480, 3500
\l__enumext_item_starred_X_bool ..... 155
\__enumext_item_std:w 28, 66-68, 81, 236, 240, 2109,
    2115, 2139, 2157, 2161, 2169, 2765
\g__enumext_item_symbol_aux_vii_tl 3071, 3119,
    3122, 3126, 3128
\g__enumext_item_symbol_aux_X_tl ..... 155
\l__enumext_item_symbol_sep_vii_dim .. 3080,
    3088, 3125, 3127

```

`\g__enumext_item_symbol_tl` [23](#), [67](#), [35](#), [2124](#), [2197](#), [2214](#)  
`\l__enumext_item_symbol_vii_tl` [3122](#)  
`\l__enumext_item_text_vii_box` [3112](#), [3153](#), [3160](#)  
`\l__enumext_item_text_viii_box` [3475](#), [3514](#), [3521](#)  
`\l__enumext_item_text_X_box` [155](#)  
`\l__enumext_item_width_vii_dim` [2799](#), [2844](#), [2852](#), [2853](#)  
`\l__enumext_item_width_viii_dim` [3210](#), [3255](#), [3263](#), [3264](#)  
`\l__enumext_item_width_X_dim` [155](#)  
`\l__enumext_itemindent_X_dim` [44](#)  
`\l__enumext_itemsep_vii_skip` [3182](#)  
`\l__enumext_itemsep_viii_skip` [3543](#)  
`\l__enumext_joined_item_aux_vii_int` [2838](#), [2839](#), [2840](#), [2841](#), [2847](#)  
`\l__enumext_joined_item_aux_viii_int` [3249](#), [3250](#), [3251](#), [3252](#), [3258](#)  
`\l__enumext_joined_item_aux_X_int` [155](#)  
`\__enumext_joined_item_vii:w` [87](#), [3035](#), [3036](#), [3038](#), [3038](#)  
`\l__enumext_joined_item_vii_int` [2809](#), [2810](#), [2813](#), [2815](#), [2821](#), [2826](#), [2831](#), [2836](#), [2838](#), [2844](#)  
`\__enumext_joined_item_viii:w` [94](#), [3379](#), [3380](#), [3382](#), [3382](#)  
`\l__enumext_joined_item_viii_int` [3220](#), [3221](#), [3224](#), [3226](#), [3232](#), [3237](#), [3242](#), [3247](#), [3249](#), [3255](#)  
`\l__enumext_joined_item_X_int` [155](#)  
`\l__enumext_joined_width_vii_dim` [2842](#), [2849](#), [2852](#), [3143](#), [3155](#)  
`\l__enumext_joined_width_viii_dim` [3253](#), [3260](#), [3263](#), [3497](#), [3516](#)  
`\l__enumext_joined_width_X_dim` [155](#)  
`\__enumext_keyans_addto_prop:n` [62](#), [1857](#), [1857](#), [2171](#), [2697](#)  
`\__enumext_keyans_addto_seq:n` [63](#), [1931](#), [1931](#), [2173](#), [2699](#)  
`\__enumext_keyans_addto_seq_link:` [1931](#), [1949](#), [1951](#), [3438](#)  
`\__enumext_keyans_anspic_code:nnn` [80](#), [2688](#), [2691](#), [2691](#)  
`\__enumext_keyans_check_ans:nn` [63](#), [64](#), [1973](#), [1973](#), [2573](#), [2729](#), [3332](#)  
`\__enumext_keyans_default_item:n` [68](#), [2152](#), [2152](#), [2187](#)  
`\l__enumext_keyans_env_bool` [20](#), [2418](#), [2431](#), [2584](#), [2668](#)  
`\__enumext_keyans_fake_item:` [652](#), [668](#), [2290](#)  
`\l__enumext_keyans_item_opt_tl` [82](#), [1985](#), [1998](#), [2004](#), [3423](#)  
`\l__enumext_keyans_level_h_int` [20](#), [1909](#), [3338](#), [3339](#)  
`\l__enumext_keyans_level_int` [20](#), [1186](#), [1659](#), [1904](#), [2583](#), [2587](#), [2682](#)  
`\__enumext_keyans_make_label:` [31](#), [69](#), [2217](#), [2217](#), [2289](#)  
`\__enumext_keyans_mini_addvspace:` [46](#), [78](#), [1090](#), [1090](#), [2612](#)  
`\__enumext_keyans_mini_right_cmd:n` [49](#), [1188](#), [1211](#), [1211](#)  
`\__enumext_keyans_mini_set_vskip:` [45](#), [1028](#), [1028](#), [1092](#)  
`\__enumext_keyans_multi_addvspace:` [78](#), [877](#), [888](#), [2637](#)  
`\__enumext_keyans_multi_set_vskip:` [42](#), [877](#), [877](#), [890](#)  
`\__enumext_keyans_multicols_start:` [78](#), [2616](#), [2618](#), [2618](#)  
`\__enumext_keyans_multicols_stop:` [78](#), [1215](#), [2643](#), [2643](#), [2667](#)  
`\__enumext_keyans_parse_keys:n` [2562](#), [2596](#), [2596](#)  
`\l__enumext_keyans_pic_above_int` [114](#), [2775](#), [2776](#), [2778](#)  
`\l__enumext_keyans_pic_above_skip` [81](#), [114](#), [2720](#), [2759](#)  
`\__enumext_keyans_pic_arg_two:` [81](#), [2718](#), [2747](#), [2747](#)  
`\l__enumext_keyans_pic_below_int` [114](#), [2775](#), [2776](#), [2779](#)  
`\l__enumext_keyans_pic_body_seq` [80](#), [82](#), [114](#), [2686](#), [2725](#), [2783](#)  
`\__enumext_keyans_pic_do:n` [82](#), [2725](#), [2727](#), [2767](#), [2767](#), [2771](#)  
`\l__enumext_keyans_pic_level_int` [20](#), [1178](#), [1663](#), [1860](#), [1899](#), [1934](#), [2017](#), [2736](#), [2737](#)  
`\__enumext_keyans_pic_row:n` [82](#), [2769](#), [2772](#), [2772](#)  
`\__enumext_keyans_pic_safe_exec:` [81](#), [2714](#), [2734](#), [2734](#)  
`\__enumext_keyans_pic_skip_abs:N` [81](#), [2742](#), [2742](#), [2758](#)  
`\l__enumext_keyans_pic_width_dim` [114](#), [2774](#), [2781](#)  
`\__enumext_keyans_redefine_item:` [68](#), [2175](#), [2175](#), [2288](#)  
`\__enumext_keyans_safe_exec:` [2561](#), [2577](#), [2577](#)  
`\__enumext_keyans_show_ans:` [1981](#), [1989](#), [2008](#)  
`\__enumext_keyans_show_item_opt:` [1981](#), [1996](#), [2169](#), [2710](#), [3503](#)  
`\__enumext_keyans_show_left:n` [68](#), [1981](#), [1981](#), [2167](#), [2705](#)  
`\__enumext_keyans_show_pos:` [1981](#), [1993](#), [2015](#)  
`\__enumext_keyans_starred_item:n` [68](#), [2164](#), [2164](#), [2183](#)  
`\__enumext_keyans_store_ref:` [62](#), [1878](#), [1878](#), [2172](#), [2698](#), [3436](#)  
`\__enumext_keyans_store_ref_aux_i:` [62](#), [1878](#), [1890](#), [1893](#)  
`\__enumext_keyans_store_ref_aux_ii:` [63](#), [1878](#), [1919](#), [1921](#)  
`\l__enumext_keyans_tmpa_dim` [82](#)  
`\l__enumext_keyans_tmpa_tl` [24](#), [94](#), [82](#), [2166](#), [2170](#)  
`\l__enumext_keyans_tmpb_tl` [94](#), [82](#)  
`\__enumext_keyans_wrapper_opt:n` [1476](#), [2004](#)  
`\l__enumext_label_copy_i_tl` [1790](#), [1897](#), [1902](#), [1907](#), [1912](#)  
`\l__enumext_label_copy_v_tl` [1907](#)  
`\l__enumext_label_copy_vi_tl` [1902](#)  
`\l__enumext_label_copy_vii_tl` [1765](#), [1776](#), [1807](#), [1897](#)  
`\l__enumext_label_copy_viii_tl` [1912](#)  
`\l__enumext_label_copy_X_tl` [133](#)  
`\l__enumext_label_fill_left_v_tl` [2221](#)  
`\l__enumext_label_fill_left_X_tl` [70](#)  
`\l__enumext_label_fill_right_v_tl` [2228](#)  
`\l__enumext_label_fill_right_X_tl` [70](#)  
`\l__enumext_label_font_style_v_tl` [2222](#), [2709](#)  
`\l__enumext_label_font_style_vii_tl` [3131](#)  
`\l__enumext_label_font_style_viii_tl` [3485](#)

<code>\l__enumext_label_i_tl</code> . . . . .	<a href="#">481</a>
<code>\l__enumext_label_ii_tl</code> . . . . .	<a href="#">481</a>
<code>\l__enumext_label_iii_tl</code> . . . . .	<a href="#">481</a>
<code>\l__enumext_label_iv_tl</code> . . . . .	<a href="#">481</a>
<code>\__enumext_label_style:Nnn</code> <a href="#">23</a> , <a href="#">30</a> , <a href="#">333</a> , <a href="#">333</a> , <a href="#">348</a> , <a href="#">486</a> , <a href="#">506</a> , <a href="#">522</a> , <a href="#">526</a>	
<code>\l__enumext_label_v_tl</code> . . <a href="#">62</a> , <a href="#">63</a> , <a href="#">519</a> , <a href="#">1865</a> , <a href="#">1939</a> , <a href="#">2010</a> , <a href="#">2044</a> , <a href="#">2166</a> , <a href="#">2170</a> , <a href="#">2565</a> , <a href="#">2704</a> , <a href="#">2706</a>	
<code>\l__enumext_label_vi_tl</code> . <a href="#">62</a> , <a href="#">63</a> , <a href="#">519</a> , <a href="#">1862</a> , <a href="#">1936</a> , <a href="#">2704</a> , <a href="#">2706</a> , <a href="#">2710</a>	
<code>\l__enumext_label_vii_tl</code> . <a href="#">501</a> , <a href="#">3058</a> , <a href="#">3083</a> , <a href="#">3090</a>	
<code>\l__enumext_label_viii_tl</code> <a href="#">501</a> , <a href="#">3402</a> , <a href="#">3430</a> , <a href="#">3434</a>	
<code>\l__enumext_label_width_by_box</code> . . <a href="#">40</a> , <a href="#">329</a> , <a href="#">330</a>	
<code>\__enumext_label_width_by_box:Nn</code> <a href="#">30</a> , <a href="#">327</a> , <a href="#">327</a> , <a href="#">332</a> , <a href="#">344</a> , <a href="#">560</a>	
<code>\l__enumext_labelsep_i_dim</code> . . . <a href="#">2012</a> , <a href="#">2048</a> , <a href="#">3441</a> , <a href="#">3456</a>	
<code>\l__enumext_labelsep_v_dim</code> . . . . .	<a href="#">2627</a>
<code>\l__enumext_labelsep_vii_dim</code> . <a href="#">2794</a> , <a href="#">2803</a> , <a href="#">2845</a> , <a href="#">3081</a> , <a href="#">3141</a> , <a href="#">3157</a>	
<code>\l__enumext_labelsep_viii_dim</code> <a href="#">3205</a> , <a href="#">3214</a> , <a href="#">3256</a> , <a href="#">3495</a> , <a href="#">3518</a>	
<code>\l__enumext_labelwidth_i_dim</code> . <a href="#">2012</a> , <a href="#">2047</a> , <a href="#">3441</a> , <a href="#">3456</a>	
<code>\l__enumext_labelwidth_v_dim</code> . . . . .	<a href="#">2627</a>
<code>\l__enumext_labelwidth_vii_dim</code> . . . <a href="#">2794</a> , <a href="#">2802</a> , <a href="#">2845</a> , <a href="#">3134</a> , <a href="#">3138</a> , <a href="#">3156</a>	
<code>\l__enumext_labelwidth_viii_dim</code> . . <a href="#">3205</a> , <a href="#">3213</a> , <a href="#">3256</a> , <a href="#">3488</a> , <a href="#">3492</a> , <a href="#">3517</a>	
<code>\l__enumext_leftmargin_tmp_v_bool</code> . <a href="#">81</a> , <a href="#">2749</a>	
<code>\l__enumext_leftmargin_tmp_X_bool</code> . . . . .	<a href="#">44</a>
<code>\l__enumext_leftmargin_tmp_X_dim</code> . . . . .	<a href="#">44</a>
<code>\l__enumext_leftmargin_X_dim</code> . . . . .	<a href="#">44</a>
<code>\__enumext_level:</code> <a href="#">188</a> , <a href="#">188</a> , <a href="#">424</a> , <a href="#">426</a> , <a href="#">427</a> , <a href="#">435</a> , <a href="#">437</a> , <a href="#">655</a> , <a href="#">659</a> , <a href="#">663</a> , <a href="#">730</a> , <a href="#">734</a> , <a href="#">738</a> , <a href="#">742</a> , <a href="#">826</a> , <a href="#">828</a> , <a href="#">830</a> , <a href="#">832</a> , <a href="#">865</a> , <a href="#">867</a> , <a href="#">869</a> , <a href="#">871</a> , <a href="#">875</a> , <a href="#">915</a> , <a href="#">918</a> , <a href="#">937</a> , <a href="#">946</a> , <a href="#">952</a> , <a href="#">957</a> , <a href="#">961</a> , <a href="#">972</a> , <a href="#">976</a> , <a href="#">977</a> , <a href="#">982</a> , <a href="#">1018</a> , <a href="#">1022</a> , <a href="#">1195</a> , <a href="#">1201</a> , <a href="#">1248</a> , <a href="#">1250</a> , <a href="#">1252</a> , <a href="#">1255</a> , <a href="#">1262</a> , <a href="#">1264</a> , <a href="#">1266</a> , <a href="#">1269</a> , <a href="#">1567</a> , <a href="#">1575</a> , <a href="#">1579</a> , <a href="#">1583</a> , <a href="#">1828</a> , <a href="#">1831</a> , <a href="#">1832</a> , <a href="#">2108</a> , <a href="#">2109</a> , <a href="#">2113</a> , <a href="#">2114</a> , <a href="#">2115</a> , <a href="#">2122</a> , <a href="#">2124</a> , <a href="#">2128</a> , <a href="#">2129</a> , <a href="#">2132</a> , <a href="#">2138</a> , <a href="#">2139</a> , <a href="#">2193</a> , <a href="#">2196</a> , <a href="#">2198</a> , <a href="#">2205</a> , <a href="#">2206</a> , <a href="#">2207</a> , <a href="#">2210</a> , <a href="#">2213</a> , <a href="#">2356</a> , <a href="#">2358</a> , <a href="#">2386</a> , <a href="#">2391</a> , <a href="#">2392</a> , <a href="#">2393</a> , <a href="#">2395</a> , <a href="#">2399</a> , <a href="#">2404</a> , <a href="#">2405</a> , <a href="#">2406</a> , <a href="#">2408</a> , <a href="#">2424</a> , <a href="#">2437</a> , <a href="#">2444</a> , <a href="#">2455</a> , <a href="#">2457</a> , <a href="#">2460</a> , <a href="#">2461</a> , <a href="#">2463</a> , <a href="#">2468</a> , <a href="#">2475</a> , <a href="#">2478</a> , <a href="#">2480</a> , <a href="#">2482</a> , <a href="#">2483</a> , <a href="#">2484</a> , <a href="#">2485</a> , <a href="#">2488</a> , <a href="#">2494</a> , <a href="#">2499</a> , <a href="#">2505</a> , <a href="#">2508</a> , <a href="#">2510</a> , <a href="#">2523</a>	
<code>\l__enumext_level_h_int</code> . <a href="#">20</a> , <a href="#">218</a> , <a href="#">443</a> , <a href="#">467</a> , <a href="#">1421</a> , <a href="#">1438</a> , <a href="#">1784</a> , <a href="#">1801</a> , <a href="#">2929</a> , <a href="#">2930</a>	
<code>\l__enumext_level_int</code> <a href="#">20</a> , <a href="#">190</a> , <a href="#">227</a> , <a href="#">838</a> , <a href="#">989</a> , <a href="#">1182</a> , <a href="#">1415</a> , <a href="#">1761</a> , <a href="#">1771</a> , <a href="#">1777</a> , <a href="#">1783</a> , <a href="#">1791</a> , <a href="#">1799</a> , <a href="#">1806</a> , <a href="#">2303</a> , <a href="#">2370</a> , <a href="#">2371</a> , <a href="#">2378</a> , <a href="#">2422</a> , <a href="#">2435</a> , <a href="#">2490</a> , <a href="#">2548</a> , <a href="#">2591</a> , <a href="#">2678</a> , <a href="#">3009</a> , <a href="#">3019</a> , <a href="#">3188</a> , <a href="#">3345</a>	
<code>\__enumext_list_arg_two_i:</code> . . . . .	<a href="#">2263</a>
<code>\__enumext_list_arg_two_ii:</code> . . . . .	<a href="#">2263</a>
<code>\__enumext_list_arg_two_iii:</code> . . . . .	<a href="#">2263</a>
<code>\__enumext_list_arg_two_iv:</code> . . . . .	<a href="#">2263</a>
<code>\__enumext_list_arg_two_v:</code> . <a href="#">68</a> , <a href="#">2263</a> , <a href="#">2567</a> , <a href="#">2750</a>	
<code>\__enumext_list_arg_two_vii:</code> . . . . .	<a href="#">2309</a> , <a href="#">2912</a>
<code>\__enumext_list_arg_two_viii:</code> . . . . .	<a href="#">2309</a> , <a href="#">3321</a>
<code>\l__enumext_listoffset_v_dim</code> . . . . .	<a href="#">2629</a>
<code>\l__enumext_listparindent_vii_dim</code> . . . . .	<a href="#">3144</a>
<code>\l__enumext_listparindent_viii_dim</code> . . . . .	<a href="#">3498</a>
<code>\__enumext_make_label:</code> <a href="#">31</a> , <a href="#">66</a> , <a href="#">67</a> , <a href="#">69</a> , <a href="#">2201</a> , <a href="#">2201</a> , <a href="#">2298</a>	
<code>\l__enumext_mark_answer_sym_tl</code> . <a href="#">57</a> , <a href="#">109</a> , <a href="#">1482</a> , <a href="#">1637</a> , <a href="#">1843</a> , <a href="#">2019</a> , <a href="#">2032</a> , <a href="#">3445</a>	
<code>\l__enumext_mark_position_str</code> <a href="#">109</a> , <a href="#">1486</a> , <a href="#">1487</a> , <a href="#">1510</a> , <a href="#">1511</a> , <a href="#">1635</a>	
<code>\l__enumext_mark_ref_sym_tl</code> . . <a href="#">109</a> , <a href="#">1496</a> , <a href="#">1741</a> , <a href="#">1963</a>	
<code>\__enumext_mini_addvspace:</code> . . <a href="#">45</a> , <a href="#">74</a> , <a href="#">1011</a> , <a href="#">1011</a> , <a href="#">2465</a>	
<code>\__enumext_mini_addvspace_vii:</code> <a href="#">47</a> , <a href="#">1164</a> , <a href="#">1164</a> , <a href="#">2870</a>	
<code>\__enumext_mini_addvspace_viii:</code> <a href="#">47</a> , <a href="#">1164</a> , <a href="#">1170</a> , <a href="#">3281</a>	
<code>\__enumext_mini_env*</code> . . . . .	<a href="#">905</a>
<code>\__enumext_mini_right_cmd:n</code> . <a href="#">48</a> , <a href="#">49</a> , <a href="#">1190</a> , <a href="#">1192</a> , <a href="#">1192</a>	
<code>\__enumext_mini_set_vskip:</code> . . <a href="#">43</a> , <a href="#">912</a> , <a href="#">912</a> , <a href="#">1013</a>	
<code>\__enumext_mini_set_vskip_vii:</code> <a href="#">46</a> , <a href="#">1107</a> , <a href="#">1107</a> , <a href="#">1166</a>	
<code>\__enumext_mini_set_vskip_viii:</code> <a href="#">46</a> , <a href="#">1107</a> , <a href="#">1129</a> , <a href="#">1172</a>	
<code>\__enumext_minipage:w</code> <a href="#">28</a> , <a href="#">242</a> , <a href="#">244</a> , <a href="#">907</a> , <a href="#">2781</a> , <a href="#">3143</a> , <a href="#">3497</a>	
<code>\l__enumext_minipage_active_v_bool</code> . . <a href="#">78</a> , <a href="#">79</a> , <a href="#">2610</a> , <a href="#">2635</a> , <a href="#">2648</a> , <a href="#">2656</a>	
<code>\g__enumext_minipage_active_vii_bool</code> . . . <a href="#">84</a> , <a href="#">2881</a> , <a href="#">2886</a> , <a href="#">2898</a>	
<code>\l__enumext_minipage_active_vii_bool</code> . <a href="#">2866</a> , <a href="#">2877</a>	
<code>\g__enumext_minipage_active_viii_bool</code> <a href="#">3292</a> , <a href="#">3297</a> , <a href="#">3309</a>	
<code>\l__enumext_minipage_active_viii_bool</code> <a href="#">3277</a> , <a href="#">3288</a>	
<code>\g__enumext_minipage_active_X_bool</code> . . . <a href="#">155</a>	
<code>\l__enumext_minipage_active_X_bool</code> . . . . .	<a href="#">58</a>
<code>\g__enumext_minipage_after_skip</code> <a href="#">58</a> , <a href="#">1111</a> , <a href="#">1123</a> , <a href="#">2896</a> , <a href="#">3307</a>	
<code>\l__enumext_minipage_after_skip</code> <a href="#">43</a> , <a href="#">44</a> , <a href="#">76</a> , <a href="#">79</a> , <a href="#">58</a> , <a href="#">928</a> , <a href="#">943</a> , <a href="#">963</a> , <a href="#">979</a> , <a href="#">994</a> , <a href="#">1000</a> , <a href="#">1006</a> , <a href="#">1020</a> , <a href="#">1030</a> , <a href="#">1039</a> , <a href="#">1042</a> , <a href="#">1054</a> , <a href="#">1072</a> , <a href="#">1083</a> , <a href="#">1099</a> , <a href="#">1131</a> , <a href="#">1144</a> , <a href="#">1158</a> , <a href="#">2532</a> , <a href="#">2665</a>	
<code>\g__enumext_minipage_center_vii_bool</code> . <a href="#">2890</a> , <a href="#">2899</a>	
<code>\g__enumext_minipage_center_viii_bool</code> <a href="#">3301</a> , <a href="#">3310</a>	
<code>\g__enumext_minipage_center_X_bool</code> . . . <a href="#">155</a>	
<code>\l__enumext_minipage_hsep_v_dim</code> . . . <a href="#">77</a> , <a href="#">2608</a>	
<code>\l__enumext_minipage_hsep_vii_dim</code> . . . . .	<a href="#">2864</a>
<code>\l__enumext_minipage_hsep_viii_dim</code> . . . . .	<a href="#">3275</a>
<code>\l__enumext_minipage_left_skip</code> <a href="#">43</a> , <a href="#">78</a> , <a href="#">58</a> , <a href="#">920</a> , <a href="#">935</a> , <a href="#">954</a> , <a href="#">969</a> , <a href="#">1016</a> , <a href="#">1026</a> , <a href="#">1031</a> , <a href="#">1037</a> , <a href="#">1046</a> , <a href="#">1063</a> , <a href="#">1075</a> , <a href="#">1095</a> , <a href="#">1105</a> , <a href="#">1109</a> , <a href="#">1114</a> , <a href="#">1118</a> , <a href="#">1132</a> , <a href="#">1136</a> , <a href="#">1150</a> , <a href="#">1168</a> , <a href="#">1174</a>	
<code>\l__enumext_minipage_left_v_dim</code> <a href="#">77</a> , <a href="#">2606</a> , <a href="#">2614</a>	
<code>\l__enumext_minipage_left_vii_dim</code> <a href="#">2860</a> , <a href="#">2872</a>	
<code>\l__enumext_minipage_left_viii_dim</code> <a href="#">3271</a> , <a href="#">3283</a>	
<code>\l__enumext_minipage_left_X_dim</code> . . . . .	<a href="#">58</a>
<code>\g__enumext_minipage_right_skip</code> <a href="#">58</a> , <a href="#">1110</a> , <a href="#">1115</a> , <a href="#">1119</a> , <a href="#">2889</a> , <a href="#">3300</a>	
<code>\l__enumext_minipage_right_skip</code> . . <a href="#">43</a> , <a href="#">58</a> , <a href="#">924</a> , <a href="#">939</a> , <a href="#">959</a> , <a href="#">974</a> , <a href="#">1032</a> , <a href="#">1038</a> , <a href="#">1050</a> , <a href="#">1068</a> , <a href="#">1079</a> , <a href="#">1133</a> , <a href="#">1140</a> , <a href="#">1154</a> , <a href="#">1202</a> , <a href="#">1219</a>	
<code>\l__enumext_minipage_right_v_dim</code> . . <a href="#">77</a> , <a href="#">1213</a> , <a href="#">1218</a> , <a href="#">2604</a> , <a href="#">2608</a>	
<code>\g__enumext_minipage_right_vii_dim</code> <a href="#">83</a> , <a href="#">2868</a> , <a href="#">2888</a> , <a href="#">2901</a>	

`\l__enumext_minipage_right_vii_dim` 83, 2858, 2863, 2869  
`\g__enumext_minipage_right_viii_dim` .. 3279, 3299, 3312  
`\l__enumext_minipage_right_viii_dim` .. 3269, 3274, 3280  
`\g__enumext_minipage_right_X_dim` ..... 155  
`\g__enumext_minipage_right_X_skip` .... 155  
`\g__enumext_minipage_stat_int` . 74, 78, 58, 1207, 1224, 2464, 2525, 2530, 2611, 2658, 2663  
`\g__enumext_miniright_code_vii_tl` . 84, 2894, 2900  
`\g__enumext_miniright_code_viii_tl` 3305, 3311  
`\g__enumext_miniright_code_X_tl` ..... 155  
`\__enumext_multi_addvspace`: ... 42, 75, 860, 860, 2496  
`\__enumext_multi_set_vskip`: .. 41, 824, 824, 862  
`\l__enumext_multicols_above_ii_skip` ... 843  
`\l__enumext_multicols_above_iii_skip` .. 849  
`\l__enumext_multicols_above_iv_skip` ... 855  
`\l__enumext_multicols_above_v_skip` 879, 893, 903  
`\l__enumext_multicols_above_X_skip` .... 52  
`\l__enumext_multicols_below_v_skip` 883, 897, 2650  
`\l__enumext_multicols_below_X_skip` .... 52  
`\__enumext_multicols_start`: . 74, 75, 2470, 2472, 2472  
`\__enumext_multicols_stop`: 75, 1197, 2502, 2502, 2534  
`\__enumext_newlabel:nn` 25, 29, 61, 285, 285, 1817, 1925  
`\l__enumext_newlabel_arg_one_tl` 25, 29, 61, 62, 133, 1740, 1810, 1818, 1914, 1926, 1961  
`\l__enumext_newlabel_arg_two_tl` 25, 29, 60, 133, 1764, 1774, 1788, 1804, 1819, 1901, 1906, 1911, 1927  
`\__enumext_parse_keys:n` ..... 2352, 2375, 2375  
`\__enumext_parse_keys_vii:n` .. 2907, 2936, 2936  
`\__enumext_parse_keys_viii:n` . 3317, 3350, 3350  
`\__enumext_parse_store_keys:n` . 73, 2381, 2384, 2384  
`\__enumext_parse_store_keys_vii:n` . 85, 2943, 2947, 2947  
`\l__enumext_parsep_i_skip` . 841, 843, 992, 1040  
`\l__enumext_parsep_ii_skip` ..... 847, 849, 998  
`\l__enumext_parsep_iii_skip` ... 853, 855, 1004  
`\l__enumext_parsep_vii_skip` ..... 3145  
`\l__enumext_parsep_viii_skip` ..... 3499  
`\l__enumext_partopsep_v_skip` .. 895, 899, 1066, 1070, 1077, 1081, 1097, 1101  
`\l__enumext_partopsep_viii_skip` ..... 1142  
`\__enumext_phantomsection`: 29, 249, 278, 282, 298  
`\__enumext_print_footnote`: ... 2067, 2090, 3163, 3524  
`\__enumext_print_keyans_box:NN` 57, 1629, 1629, 1642, 1830, 2012, 2046, 3441, 3456  
`\l__enumext_print_keyans_i_tl` .... 3575, 3604  
`\l__enumext_print_keyans_ii_tl` ... 3580, 3605  
`\l__enumext_print_keyans_iii_tl` .. 3585, 3606  
`\l__enumext_print_keyans_iv_tl` ... 3590, 3607  
`\l__enumext_print_keyans_vii_tl` .. 3595, 3608  
`\l__enumext_print_keyans_X_tl` ..... 98  
`\__enumext_printkeyans:nnn` . 98, 3609, 3612, 3612  
`\__enumext_redefine_item`: . 67, 2141, 2141, 2297  
`\l__enumext_ref_aux_tl` 144, 424, 426, 429, 445, 447, 450, 455, 457, 460  
`\l__enumext_ref_key_arg_tl` .. 144, 418, 423, 430, 442, 451, 461  
`\__enumext_regex_label_ref_key`: .. 32, 33, 413, 413, 425, 446, 456  
`\__enumext_register_counter_style:Nn` .. 317, 317, 322, 323, 324, 325, 326  
`\__enumext_remove_extra_parsep_vii`: .. 2922, 3172, 3172  
`\__enumext_remove_extra_parsep_viii`: . 3331, 3533, 3533  
`\__enumext_renew_footnote`: ... 2067, 2071, 3115, 3478  
`\l__enumext_resume_bool` .... 23, 35, 1382, 2280  
`\__enumext_resume_counter`: . 52, 1343, 1373, 1373  
`\__enumext_resume_counter_star`: ..... 1345  
`\__enumext_resume_counter_vii`: 52, 1352, 1373, 1384  
`\g__enumext_resume_int` 23, 76, 35, 1377, 1388, 2281, 2538  
`\l__enumext_resume_vii_bool` ... 35, 1393, 2327  
`\g__enumext_resume_vii_int` .. 86, 35, 2328, 2988  
`\__enumext_safe_exec`: ..... 2351, 2368, 2368  
`\__enumext_safe_exec_vii`: ... 2906, 2927, 2927  
`\__enumext_safe_exec_viii`: ... 3316, 3336, 3336  
`\__enumext_set_error:nn` ..... 3690, 3700, 3702  
`\__enumext_set_label_ref:n` ... 32, 421, 421, 493  
`\__enumext_set_label_ref_h:n` . 33, 440, 440, 513  
`\__enumext_set_parse:n` ..... 3673, 3690, 3690  
`\l__enumext_setkey_tmpa_int` ... 93, 3666, 3670  
`\l__enumext_setkey_tmpa_seq` 93, 3664, 3674, 3680, 3682, 3684, 3697  
`\l__enumext_setkey_tmpa_tl` .... 93, 3672, 3676  
`\l__enumext_setkey_tmpb_seq` 93, 3665, 3668, 3672, 3673  
`\l__enumext_setkey_tmpb_tl` 93, 3692, 3694, 3695  
`\l__enumext_show_answer_bool` . 109, 1490, 1514, 1837, 1987, 2001, 2701, 3439  
`\__enumext_show_length:nnn` .. 38, 198, 198, 3742, 3743, 3744, 3745, 3746, 3747, 3748, 3749, 3750, 3751, 3757, 3758, 3759, 3760, 3761, 3762, 3763, 3764, 3765, 3766  
`\l__enumext_show_position_bool` 109, 1493, 1517, 1841, 1991, 2002, 2702, 3443  
`\g__enumext_standar_bool` 27, 20, 220, 1441, 2554  
`\l__enumext_standar_bool` . 20, 1769, 1782, 1798, 2373, 2537  
`\g__enumext_standar_keyans_pic_star_env_int` ..... 130  
`\g__enumext_standar_keyans_star_env_int` 129  
`\g__enumext_standar_star_env_int` .. 126, 221  
`\__enumext_standard_item_vii:w` 87, 3043, 3045, 3045  
`\__enumext_standard_item_viii:w` 94, 3387, 3389, 3389  
`\g__enumext_starred_bool` 27, 85, 86, 20, 229, 1420, 1760, 1770, 1800, 1895, 2419, 2432, 2515, 2996, 3002, 3194  
`\l__enumext_starred_bool` . 85, 86, 20, 1693, 1701, 1785, 1826, 2934, 3003  
`\__enumext_starred_columns_set_vii`: .. 2788, 2788, 2915  
`\__enumext_starred_columns_set_viii`: . 3199,



3199, 3324  
 \\_\_enumext\_starred\_item:nn ... 2118, 2118, 2147  
 \\_\_enumext\_starred\_item\_exec: . 95, 3432, 3432, 3482  
 \\_\_enumext\_starred\_item\_vii:w 87, 88, 3042, 3061, 3061  
 \\_\_enumext\_starred\_item\_vii\_aux\_i:w .. 3061, 3066, 3069  
 \\_\_enumext\_starred\_item\_vii\_aux\_ii:w . 3061, 3067, 3072, 3074  
 \\_\_enumext\_starred\_item\_vii\_aux\_iii:w 3061, 3077, 3086  
 \\_\_enumext\_starred\_item\_viii:w 94, 3386, 3405, 3405  
 \\_\_enumext\_starred\_item\_viii\_aux\_i:w . 3405, 3410, 3413  
 \\_\_enumext\_starred\_item\_viii\_aux\_ii:w 3405, 3411, 3425, 3427  
 \\_\_enumext\_starred\_joined\_item\_vii:n . 83, 87, 2807, 2807, 3040  
 \\_\_enumext\_starred\_joined\_item\_viii:n 91, 94, 3218, 3218, 3384  
 \g\_\_enumext\_starred\_keyans\_star\_env\_int 128  
 \g\_\_enumext\_starred\_star\_env\_int .. 127, 230  
 \\_\_enumext\_start\_from:NNn 34, 534, 534, 547, 569  
 \\_\_enumext\_start\_item\_tmp\_vii: 84, 2918, 3025, 3025  
 \\_\_enumext\_start\_item\_tmp\_viii: 92, 3327, 3369, 3369  
 \\_\_enumext\_start\_item\_vii:w . 87, 88, 3053, 3058, 3083, 3090, 3092, 3092  
 \\_\_enumext\_start\_item\_viii:w .. 94, 3397, 3402, 3430, 3459, 3459  
 \\_\_enumext\_start\_list:nn 28, 71, 81, 236, 238, 2355, 2564, 2715, 2910, 3319  
 \\_\_enumext\_start\_mini\_vii: . 86, 2856, 2856, 2981  
 \\_\_enumext\_start\_mini\_viii: 93, 3267, 3267, 3361  
 \\_\_enumext\_start\_store\_level: . 73, 2354, 2413, 2413  
 \\_\_enumext\_start\_store\_level\_vii: . 86, 2909, 3005, 3005  
 \l\_\_enumext\_start\_X\_int ..... 70, 564  
 \\_\_enumext\_stop\_item\_tmp\_vii: . 84, 87, 88, 2917, 2921, 3027, 3094  
 \\_\_enumext\_stop\_item\_tmp\_viii: .. 92, 93, 3326, 3330, 3371, 3461  
 \\_\_enumext\_stop\_item\_vii: 88, 89, 3094, 3148, 3148  
 \\_\_enumext\_stop\_item\_viii: . 96, 3461, 3509, 3509  
 \\_\_enumext\_stop\_list: .. 28, 236, 239, 2364, 2574, 2728, 2923, 3333  
 \\_\_enumext\_stop\_mini\_vii: 84, 86, 2875, 2875, 2985  
 \\_\_enumext\_stop\_mini\_viii: . 93, 3267, 3286, 3365  
 \\_\_enumext\_stop\_store\_level: .. 73, 2365, 2413, 2442  
 \\_\_enumext\_stop\_store\_level\_vii: .. 86, 2924, 3005, 3015  
 \l\_\_enumext\_store\_active\_bool 24, 51, 73, 85, 82, 1366, 1375, 1386, 1655, 2379, 2417, 2430, 2579, 2586, 2674, 2732, 2941, 3007, 3017, 3344  
 \\_\_enumext\_store\_addto\_prop:n 56, 62, 1548, 1549, 1557, 1680, 1876, 3435  
 \\_\_enumext\_store\_addto\_seq:n 56, 63, 1558, 1558, 1562, 1569, 1583, 1591, 1600, 1618, 1626, 1744, 1966  
 \l\_\_enumext\_store\_ans\_bool 119, 1367, 1402, 1565, 1589, 1596, 1624, 1668  
 \l\_\_enumext\_store\_anskey\_arg\_tl 24, 58, 59, 82, 1686, 1695, 1697, 1703, 1711, 1714, 1724, 1729, 1732, 1738, 1744  
 \\_\_enumext\_store\_anskey\_code:nnnn . 58, 1674, 1678, 1678  
 \\_\_enumext\_store\_anskey\_show\_left:n 61, 1685, 1835, 1835  
 \\_\_enumext\_store\_anskey\_show\_wrap:n 61, 1823, 1823, 1839, 1854  
 \l\_\_enumext\_store\_columns\_break\_bool . 1649, 1692  
 \l\_\_enumext\_store\_columns\_join\_int 82, 1700, 1705  
 \l\_\_enumext\_store\_columns\_sep\_vii\_bool 2962  
 \l\_\_enumext\_store\_columns\_sep\_vii\_dim 2967, 2971  
 \l\_\_enumext\_store\_columns\_sep\_X\_bool ... 98  
 \l\_\_enumext\_store\_columns\_sep\_X\_dim .... 98  
 \l\_\_enumext\_store\_columns\_vii\_bool ... 2949  
 \l\_\_enumext\_store\_columns\_vii\_int 2954, 2958  
 \l\_\_enumext\_store\_columns\_X\_bool ..... 98  
 \l\_\_enumext\_store\_columns\_X\_int ..... 98  
 \\_\_enumext\_store\_internal\_ref: .. 58, 60, 1683, 1746, 1746  
 \l\_\_enumext\_store\_item\_symbol\_sep\_dim 1647, 1721, 1726  
 \l\_\_enumext\_store\_item\_symbol\_tl . 1645, 1712, 1716  
 \l\_\_enumext\_store\_keyans\_item\_opt\_sep\_tl .... 1479, 1870, 1872, 1943, 1945, 3418, 3420  
 \l\_\_enumext\_store\_keyans\_item\_opt\_tl ... 82  
 \l\_\_enumext\_store\_keyans\_label\_tl 24, 62, 63, 82, 1859, 1862, 1865, 1872, 1874, 1876, 1933, 1936, 1939, 1945, 1947, 1957, 1966, 1967, 3415, 3420, 3421, 3434, 3435, 3437  
 \\_\_enumext\_store\_level\_close: . 56, 1563, 1587, 2446  
 \\_\_enumext\_store\_level\_close\_vii: 1594, 1622, 3021  
 \\_\_enumext\_store\_level\_open: .. 55, 56, 73, 1563, 1563, 2425, 2438  
 \\_\_enumext\_store\_level\_open\_vii: .. 85, 1594, 1594, 3011  
 \g\_\_enumext\_store\_name\_tl 24, 75, 82, 1461, 1464, 2518, 2556, 3000, 3196  
 \l\_\_enumext\_store\_name\_tl 24, 51, 82, 1357, 1358, 1360, 1362, 1364, 1379, 1390, 1551, 1553, 1560, 1812, 1813, 1849, 1916, 1917, 2025, 2038, 2518, 2539, 2542, 2989, 2992, 3000, 3451  
 \l\_\_enumext\_store\_opt\_vii\_tl . 1598, 1608, 1614, 1618, 2956, 2969  
 \l\_\_enumext\_store\_opt\_X\_tl ..... 98  
 \l\_\_enumext\_store\_ref\_key\_bool 58, 1499, 1681, 1735, 1880, 1954  
 \l\_\_enumext\_store\_upper\_level\_X\_bool ... 98  
 \l\_\_enumext\_store\_write\_aux\_file\_tl 25, 61, 63, 133, 1815, 1821, 1923, 1929  
 \\_\_enumext\_storing\_set:n 51, 52, 1341, 1350, 1355, 1355  
 \l\_\_enumext\_the\_counter\_vii\_tl ..... 447  
 \l\_\_enumext\_the\_counter\_viii\_tl ..... 457  
 \l\_\_enumext\_the\_counter\_X\_tl ..... 144  
 \\_\_enumext\_tmp:n 30, 34, 44, 51, 52, 57, 64, 69, 70, 81,

98, 108, 136, 140, 148, 154, 155, 174, 206, 210, 647,  
651, 1395, 1412, 1469, 1504, 1505, 1522, 1748, 1755,  
1756, 1777, 1791, 1794, 1806, 1882, 1889, 2263, 2308,  
2309, 2347

`\__enumext_tmp:nn` 349, 370, 371, 399, 400, 412, 564,  
583, 628, 646, 704, 712, 713, 727, 792, 808, 809, 823,  
1228, 1244, 1523, 1547, 2051, 2066

`\__enumext_tmp:nnn` 481, 497, 498, 499, 500, 501, 517,  
518

`\__enumext_tmp:nnnnn` 584, 609, 612, 615, 617, 619,  
622, 625

`\__enumext_tmp:w` ..... 3558, 3561

`\l__enumext_tmpa_vii_int` ..... 2798, 2801

`\l__enumext_tmpa_viii_int` ..... 3209, 3212

`\l__enumext_tmpa_X_int` ..... 155

`\l__enumext_topsep_v_skip` 881, 885, 1035, 1048,  
1056, 1061, 1081, 1085, 2731, 2762

`\l__enumext_topsep_vii_skip` .. 1112, 1121, 1125

`\l__enumext_topsep_viii_skip` . 1134, 1156, 1160

`\__enumext_use_key_ref:` .... 32, 433, 433, 2299

`\__enumext_use_key_ref_h:` .. 33, 465, 465, 2333

`\l__enumext_vspace_a_star_v_bool` ..... 1277

`\l__enumext_vspace_a_star_vii_bool` ... 1299

`\l__enumext_vspace_a_star_viii_bool` ... 1310

`\l__enumext_vspace_a_star_X_bool` ..... 70

`\__enumext_vspace_above:` .. 49, 1245, 1245, 2451

`\__enumext_vspace_above_v:` . 50, 1273, 1273, 2602

`\l__enumext_vspace_above_v_skip` .. 1275, 1279,  
1281

`\__enumext_vspace_above_vii:` .. 50, 1295, 1295,  
2978

`\l__enumext_vspace_above_vii_skip` 1297, 1301,  
1303

`\__enumext_vspace_above_viii:` . 50, 1295, 1306,  
3359

`\l__enumext_vspace_above_viii_skip` 1308, 1312,  
1314

`\l__enumext_vspace_b_star_v_bool` ..... 1288

`\l__enumext_vspace_b_star_vii_bool` ... 1321

`\l__enumext_vspace_b_star_viii_bool` ... 1332

`\l__enumext_vspace_b_star_X_bool` ..... 70

`\__enumext_vspace_below:` .. 50, 1259, 1259, 2536

`\__enumext_vspace_below_v:` . 50, 1284, 1284, 2670

`\l__enumext_vspace_below_v_skip` .. 1286, 1290,  
1292

`\__enumext_vspace_below_vii:` .. 51, 1317, 1317,  
2987

`\l__enumext_vspace_below_vii_skip` 1319, 1323,  
1325

`\__enumext_vspace_below_viii:` . 51, 1317, 1328,  
3367

`\l__enumext_vspace_below_viii_skip` 1330, 1334,  
1336

`\__enumext_widest_from:nNNn` .. 35, 548, 548, 563,  
575

`\g__enumext_widest_label_tl` 23, 30, 40, 337, 341,  
345

`\l__enumext_wrap_label_opt_v_bool` .... 2160

`\l__enumext_wrap_label_opt_vii_bool` 87, 3052

`\l__enumext_wrap_label_opt_viii_bool` 94, 3396

`\l__enumext_wrap_label_opt_X_bool` ..... 70

`\l__enumext_wrap_label_v_bool` 2156, 2160, 2168,  
2223

`\l__enumext_wrap_label_vii_bool` 87, 3051, 3056,

3064, 3132

`\l__enumext_wrap_label_viii_bool` .. 94, 3395,  
3400, 3408, 3486

`\l__enumext_wrap_label_X_bool` ..... 70

`\__enumext_wrapper_label_v:n` ..... 2225, 2710

`\__enumext_wrapper_label_vii:n` ..... 3135

`\__enumext_wrapper_label_viii:n` ..... 3489

`\__enumext_zero_count_level:` ..... 204, 204

`\__enumext_zero_parsep:` ..... 44, 932, 987, 987

`enumext*` ..... 5, 2903

`enumXi` ..... 309

`enumXii` ..... 309

`enumXiii` ..... 309

`enumXiv` ..... 309

`enumXv` ..... 309

`enumXvi` ..... 309

`enumXvii` ..... 309

`enumXviii` ..... 309

Environments provide by `enumext`:

`enumext*` 22, 23, 25–27, 30, 32–34, 37–40, 46, 47, 50–60,  
62, 65, 66, 71–73, 85, 86, 88, 90, 91, 93, 95, 98, 101, 102

`enumext` 22, 23, 25, 27, 30–33, 35, 36, 38–46, 48–58, 60, 62,  
65–73, 76, 77, 81–83, 86, 98, 101

`keyans*` 22–24, 26, 27, 30, 32–34, 37–40, 46, 47, 50–53, 55,  
56, 62, 66, 71, 92, 93, 101, 102

`keyanspic` 22–25, 30, 31, 34, 48, 51–53, 56, 62–64, 79–81,  
102

`keyans` 22–25, 27, 30, 31, 34–36, 38–40, 42, 45, 46, 48–53,  
55, 56, 62–64, 68–71, 76, 77, 79–81, 83, 93, 101, 102

Environments:

`list` ..... 27, 28, 70–72

`lrbox` ..... 82, 89, 96

`minipage` ..... 27, 28, 40, 42, 43, 79–82, 89, 96

`multicols` ..... 41–43, 48, 74–76, 78, 79

exp commands:

`\exp_after:wN` ..... 3561

`\exp_args:Ne` ..... 2377, 3549

`\exp_not:N` 152, 340, 429, 450, 460, 661, 675, 676, 687,  
688, 699, 700, 1740, 1846, 1847, 1959, 2022, 2023,  
2035, 2036, 3448, 3449, 3558

`\exp_not:n` 429, 430, 450, 451, 460, 461, 662, 1531, 1538,  
1705, 1716, 1726, 1740, 1741, 1818, 1926, 1961, 1963,  
2395, 2408, 2958, 2971

## F

`\fbox` ..... 1474

file commands:

`\file_input_stop:` ..... 3859

`first` ..... 713

`font` ..... 349

`\footnote` ..... 66

`\footnote` ..... 66, 2075

`\footnotemark` ..... 2085

`\footnotesize` ..... 1847, 2023, 2036, 3449

`\footnotetext` ..... 2069

## G

`\getkeyans` ..... 13, 97, 3547

group commands:

`\group_begin:` .. 1667, 1845, 2021, 2034, 3111, 3130,  
3447, 3474, 3484, 3569, 3603

`\group_end:` 1676, 1852, 2028, 2041, 3140, 3152, 3454,  
3494, 3513, 3571, 3610

## H

`\hbadness` ..... 3159, 3520  
`hbox` commands:  
     `\hbox_set:Nn` ..... 329  
`\hfill` 379, 383, 388, 389, 1199, 1217, 1740, 1959, 2880, 3291  
`hook` commands:  
     `\hook_gput_code:nnn` ..... 9, 182, 186, 247  
     `\hook_gset_rule:nnnn` ..... 248  
`\hspace` ..... 3170, 3531  
`\hyperlink` ..... 59, 63  
`\hyperlink` ..... 1740, 1959  
`\hypertarget` ..... 29  
`\hypertarget` ..... 277

## I

`\IfHyperBoolean` ..... 255  
`\IfPackageLoadedTF` ..... 11, 251, 265  
`\ignorespaces` ..... 664  
`\inputlineno` ..... 221, 230  
`int` commands:  
     `\int_add:Nn` ..... 2840, 3251  
     `\int_case:nn` ..... 838, 989, 1415, 1438  
     `\int_compare:nNnTF` .. 218, 227, 443, 467, 914, 1033, 1178, 1182, 1186, 1458, 1659, 1663, 1860, 1899, 1904, 1909, 1934, 2017, 2371, 2422, 2435, 2474, 2490, 2504, 2525, 2548, 2587, 2591, 2620, 2645, 2658, 2678, 2682, 2737, 2810, 2820, 2836, 2930, 3009, 3019, 3165, 3174, 3188, 3221, 3231, 3247, 3339, 3345, 3526, 3535, 3670  
     `\int_compare_p:nNn` .. 1421, 1761, 1771, 1783, 1784, 1799, 1801  
     `\int_decr:N` ..... 2839, 3250  
     `\int_eval:n` 1553, 1813, 1847, 1917, 2023, 2036, 2281, 2284, 2328, 2331, 2828, 3239, 3449  
     `\int_from_alph:n` ..... 542, 556  
     `\int_from_roman:n` ..... 544, 558  
     `\int_gadd:Nn` ..... 2841, 3252  
     `\int_gdecr:N` ..... 1424, 1429, 1432, 1435, 1443  
     `\int_gincr:N` 1672, 1970, 2106, 2136, 2464, 2611, 3029, 3107, 3373  
     `\int_gset:Nn` ..... 221, 230, 1377, 1388, 2083  
     `\int_gset_eq:NN` .... 2080, 2538, 2541, 2988, 2991  
     `\int_gzero:N` 208, 1207, 1224, 1466, 1467, 2530, 2663, 3183, 3544  
     `\int_if_exist:NnTF` ..... 1368, 2539, 2989  
     `\int_incr:N` 2370, 2583, 2736, 2929, 3028, 3338, 3372  
     `\int_mod:nn` ..... 3176, 3537  
     `\int_new:N` 20, 21, 22, 23, 24, 36, 38, 58, 74, 86, 95, 103, 116, 117, 124, 125, 126, 127, 128, 129, 130, 141, 158, 159, 160, 161, 162, 1370  
     `\int_set:Nn` 538, 542, 544, 1528, 1700, 2775, 2776, 2798, 2809, 2815, 2831, 3159, 3209, 3220, 3226, 3242, 3520, 3666  
     `\int_set_eq:NN` ..... 2390, 2838, 2953, 3249  
     `\int_step_function:nnN` ..... 1777, 1791, 1806  
     `\int_step_inline:nnn` ..... 2777, 3693  
     `\int_to_roman:n` ..... 190, 1757, 1795  
     `\int_use:N` .. 915, 1379, 1390, 2284, 2303, 2331, 2378, 2475, 2484, 2499, 2505, 2813, 2814, 2826, 3224, 3225, 3237  
     `\int_zero:N` ..... 3168, 3529  
     `\c_one_int` . 1421, 2798, 2817, 2823, 2829, 2833, 2836, 3209, 3228, 3234, 3240, 3244, 3247  
     `\c_zero_int` .. 218, 227, 1761, 1771, 1783, 1784, 1799, 1801, 3009, 3019, 3179, 3540  
`\item` ..... 28, 39, 40, 57, 66, 79, 81, 82, 84, 92

`\item` 66, 68, 87, 88, 93, 95, 240, 1571, 1577, 1602, 1610, 1697, 1936, 1939, 2143, 2177, 2916, 2918, 3325, 3327, 3437  
`\item*` ..... 6, 12, 2175  
`item-pos*` ..... 2051  
`item-sym*` ..... 2051  
`\itemindent` ..... 23, 70  
`\itemindent` ..... 69  
`itemindent` ..... 628  
`\itemsep` ..... 80, 81  
`\itemsep` ..... 2751, 2757  
`\itemwidth` ..... 2805, 2849, 2853, 3216, 3260, 3264

## K

`keyans` ..... 11, 2559  
`keyans*` ..... 11, 3314  
`keyanspic` ..... 12, 2712

Keys for environments provide by [enumext](#):

`above*` ..... 24, 49, 50  
`above` ..... 24, 49, 50, 74, 77, 86, 93  
`after` ..... 38–40, 76, 79, 86, 93  
`align` ..... 24, 31, 32, 68, 89  
`before*` ..... 38, 39, 74, 86, 93  
`before` ..... 38, 39, 77  
`below*` ..... 24, 49–51  
`below` ..... 24, 49–51, 76, 79, 86, 93  
`check-ans` 24, 25, 27, 51, 53, 58, 63, 64, 66, 67, 74–76, 90, 101  
`columns-sep*` ..... 25, 55, 73, 85  
`columns-sep` ..... 40, 56, 73, 75, 78, 85  
`columns*` ..... 25, 55, 73, 85  
`columns` ..... 23, 40, 43, 49, 56, 73, 75, 78, 85  
`first` ..... 38–40, 89  
`font` ..... 31, 68, 89  
`item-pos*` ..... 58, 59, 65  
`item-sym*` ..... 23, 58, 59, 65, 67  
`item*-sep` ..... 67  
`itemindent` ..... 24, 36, 37, 68, 89  
`itemsep` ..... 36, 71  
`labelsep` ..... 31, 67, 70, 89  
`labelwidth` ..... 30, 31, 33–35, 70  
`label` ..... 23, 30, 34, 35, 82  
`lisparindent` ..... 71  
`list-indent` ..... 23, 36, 37, 81  
`list-offset` ..... 36, 37  
`listparindent` ..... 36, 89  
`mark-ans` ..... 25, 54, 61  
`mark-pos` ..... 54, 55  
`mark-ref` ..... 25, 54, 60  
`mini-env` .. 24, 40, 43, 48, 49, 66, 74, 77, 83, 86, 91, 93  
`mini-sep` ..... 24, 40, 74, 77  
`miniright*` ..... 24, 40  
`miniright` ..... 24, 40, 47, 84  
`minirigth*` ..... 27  
`minirigth` ..... 27  
`no-store` ..... 25, 53, 54  
`noitemsep` ..... 36, 44  
`nosep` ..... 36, 44  
`parindent` ..... 71  
`parsep` ..... 36, 71, 89  
`partopsep` ..... 36  
`ref` ..... 26, 32, 33  
`resume` ..... 23, 51, 52, 71, 76, 86  
`rightmargin` ..... 36  
`save-ans` 24, 51, 52, 56, 58, 62, 63, 68, 76, 77, 79, 86, 93, 95, 97, 98

save-key	25
save-ref	25, 29, 54, 58–60, 62, 63, 68, 95
save-sep	54
show-ans	25, 54, 55, 57, 58, 61, 68, 94, 95
show-length	27, 38, 71, 101
show-pos	25, 54, 55, 57, 58, 61, 64, 68, 94, 95
start	24, 27, 34, 35, 71
store-brk	58
topsep	36
widest	23, 27, 35
wrap-ans	54, 57, 61
wrap-label*	31, 66, 68, 87, 89, 94
wrap-label	31, 68, 87, 89, 94
wrap-opt	54
keys commands:	
\keys_define:nn	351, 373, 402, 483, 503, 519, 566, 586, 630, 649, 706, 715, 794, 811, 1230, 1339, 1348, 1397, 1471, 1507, 1525, 1643, 2053, 3573, 3636
\l_keys_key_str	3727
\keys_set:nn	365, 818, 1235, 1240, 1689, 2377, 2598, 2940, 3354, 3638, 3639, 3640, 3641, 3642, 3643, 3644, 3645, 3646, 3647, 3648, 3649, 3687
<b>L</b>	
label	481, 501, 519
Labels provide by enumext:	
\Alph*	30
\Roman*	30
\alph*	30
\arabic*	30, 32
\roman*	30
\labelsep	81
\labelsep	2752, 2755
labelsep	349
\labelwidth	30, 81
\labelwidth	2752, 2753
labelwidth	349
\leftmargin	23, 70
\leftmargin	69, 2752
legacy commands:	
\legacy_if:nTF	3095, 3098, 3462, 3465
\legacy_if_gset_false:n	908
\legacy_if_set_false:n	3097, 3464
\legacy_if_set_true:n	3057, 3082, 3089, 3102, 3401, 3429, 3469
\linewidth	74, 77
\linewidth	2459, 2608, 2774, 2801, 2862, 3212, 3273
\list	28
\list	238
list-indent	628
list-offset	628
\listparindent	2754
listparindent	628
\lrbox	3112, 3475
<b>M</b>	
\makebox	82
\makebox	1633, 1635, 2197, 3126, 3134, 3138, 3488, 3492
\makelabel	66, 68, 69, 82
\makelabel	68, 69, 2203, 2219
\makesavenoteenv	271
mark-ans	1469
mark-pos	1469, 1505
mark-ref	1469
mini-env	792

mini-sep	792
\minipage	28
\minipage	244
\miniright	10, 48, 1176, 2528, 2661
\miniright*	10
mode commands:	
\mode_if_vertical:TF	863, 891, 1014, 1093
\mode_leave_vertical:	661, 675, 687, 699, 1602, 1610, 1631, 2195, 3124
msg commands:	
\msg_error:nn	2589, 2593, 2680, 2739, 2932, 3341, 3347, 3650
\msg_error:nnn	1180, 1184, 1209, 1226, 3563, 3568, 3633, 3703
\msg_error:nnnn	1657, 1661, 1665, 2581, 2676, 2684
\msg_fatal:nn	2372
\msg_fatal:nnn	303
\msg_info:nnn	13, 16, 253, 267
\msg_line_context:	3731, 3736, 3741, 3756, 3779, 3783, 3787, 3792, 3797, 3802, 3807, 3811, 3816, 3821, 3825, 3830, 3834, 3839, 3844, 3849, 3853, 3857
\msg_new:nnn	3704, 3708, 3712, 3716, 3721, 3725, 3729, 3734, 3739, 3754, 3769, 3776, 3781, 3785, 3790, 3795, 3800, 3805, 3809, 3814, 3819, 3823, 3828, 3832, 3837, 3842, 3847, 3851, 3855
\msg_term:nnn	1461
\msg_term:nnnn	2293, 2303, 2338, 2343
\msg_warning:nn	2527, 2660
\msg_warning:nnn	1464
\msg_warning:nnnn	1977, 2235, 2240, 2812, 2825, 3223, 3236
\multicolsep	75, 78
\multicolsep	2489, 2633
<b>N</b>	
\NeedsTeXFormat	3
\newcounter	306
\NewDocumentCommand	1176, 1653, 2672, 3547, 3601, 3657
\NewDocumentEnvironment	2348, 2559, 2712, 2903, 3314
\newlabel	29
\newlabel	289
no-store	1395
\noindent	84, 92
\noindent	2466, 2613, 2871, 2917, 3167, 3282, 3326, 3528
\nointerlineskip	2466, 2613, 2871, 3282
noitemsep	584
\nopagebreak	874, 902, 1025, 1104, 1167, 1173
\normalfont	1846, 2022, 2035, 3448
nosep	584
<b>P</b>	
Packages:	
enumext	22, 51, 70, 79, 100
enumitem	30
expl3	82
footnotehyper	29
hyperref	25, 27–29, 33, 59, 63, 88, 100
lua-visual-debug	43
multicol	22, 100
shortlst	82
\par	874, 902, 1025, 1104, 1167, 1173, 1202, 1219, 1825, 2510, 2532, 2650, 2665, 2786, 2889, 2896, 3167, 3181, 3300, 3307, 3528, 3542
\parindent	3144, 3498
\parsep	41, 44, 80, 81



<code>\parsep</code> . . . . .	1603, 1611, 2323, 2751, 2758, 2763
<code>parsep</code> . . . . .	584
<code>\parskip</code> . . . . .	3145, 3499
<code>\partopsep</code> . . . . .	81
<code>\partopsep</code> . . . . .	2324, 2756
<code>partopsep</code> . . . . .	584
peek commands:	
<code>\peek_meaning:N</code> NTF	3034, 3048, 3065, 3076, 3378, 3392, 3409
<code>\peek_meaning_remove:N</code> TF	3041, 3385
<code>\peek_remove_spaces:n</code>	2181
<code>\phantomsection</code> . . . . .	29
<code>\phantomsection</code> . . . . .	278
prg commands:	
<code>\prg_do_nothing:</code>	282
<code>\prg_new_protected_conditional:Npnn</code>	192
<code>\prg_replicate:nn</code>	201, 3774
<code>\prg_return_false:</code>	196
<code>\prg_return_true:</code>	195
<code>\printkeyans</code> . . . . .	13, 98, 3601
prop commands:	
<code>\prop_count:N</code>	1553, 1813, 1849, 1917, 2025, 2038, 3451
<code>\prop_gput_if_not_in:Nnn</code>	1548, 1551
<code>\prop_if_exist:N</code> TF	1358, 3567
<code>\prop_item:Nn</code>	3570
<code>\prop_new:N</code>	1360
<code>\ProvidesExplPackage</code> . . . . .	4
<b>R</b>	
<code>\raggedcolumns</code> . . . . .	2498, 2639
<code>\ref</code> . . . . .	60, 62
<code>ref</code> . . . . .	481, 501
<code>\refstepcounter</code> . . . . .	3104, 3471
regex commands:	
<code>\regex_match:nnTF</code>	194, 541, 543, 555, 557, 2388, 2401, 2951, 2964
<code>\regex_replace_once:nnN</code>	417
<code>\renewcommand</code> . . . . .	429, 450, 460
<code>\RenewDocumentCommand</code> . . . . .	2075, 2143, 2177, 2203, 2219
<code>\RequirePackage</code> . . . . .	17
<code>resume</code> . . . . .	1339
<code>resume*</code> . . . . .	1339
<code>rightmargin</code> . . . . .	628
<code>\Roman</code> . . . . .	30, 35
<code>\Roman</code> . . . . .	325
<code>\roman</code> . . . . .	30, 35
<code>\roman</code> . . . . .	326, 499, 3589
<b>S</b>	
<code>save-ans</code> . . . . .	1339
<code>save-ref</code> . . . . .	1469
<code>save-sep</code> . . . . .	1469
scan commands:	
<code>\scan_stop:</code>	81, 2765, 2916, 3325, 3558, 3561
seq commands:	
<code>\seq_clear:N</code>	3664
<code>\seq_const_from_clist:Nn</code>	3652
<code>\seq_count:N</code>	2725, 3668
<code>\seq_gclear:N</code>	2073, 2074
<code>\seq_gput_right:Nn</code>	1560, 2086, 2087
<code>\seq_if_empty:N</code> TF	2092, 3616, 3682
<code>\seq_if_exist:N</code> TF	1362, 3614
<code>\seq_item:Nn</code>	2783
<code>\seq_map_function:NN</code>	3673
<code>\seq_map_inline:Nn</code>	3622, 3627, 3661, 3683, 3684
<code>\seq_map_pairwise_function:NNN</code>	2094
<code>\seq_new:N</code>	96, 97, 114, 142, 143, 1364
<code>\seq_pop_left:NN</code>	3672
<code>\seq_put_right:Nn</code>	2686, 3680, 3697
<code>\seq_set_from_clist:Nn</code>	3665
<code>\seq_set_map_e:NNn</code>	3674
<code>\seq_show:N</code>	3618
<code>\setcounter</code> . . . . .	552, 556, 558, 2281, 2283, 2328, 2330, 2730
<code>\setenumext</code> . . . . .	6–9, 99, 3577, 3582, 3587, 3592, 3597, 3657
<code>\setlength</code> . . . . .	1604, 1612
<code>show-ans</code> . . . . .	1469, 1505
<code>show-length</code> . . . . .	704
skip commands:	
<code>\skip_add:Nn</code>	843, 849, 855, 865, 869, 893, 897, 994, 1000, 1006, 1016, 1020, 1042, 1095, 1099, 2751
<code>\skip_eval:n</code>	1603, 1611
<code>\skip_gset:Nn</code>	1115, 1119, 1123
<code>\skip_gzero_new:N</code>	1110, 1111
<code>\skip_horizontal:N</code>	676, 688, 700, 3127, 3141, 3495
<code>\skip_horizontal:n</code>	662, 1632, 1640, 2196, 2198, 3125, 3503
<code>\skip_if_eq:nnTF</code>	841, 847, 853, 917, 951, 992, 998, 1004, 1035, 1040, 1061, 1112, 1134, 1247, 1261, 1275, 1286, 1297, 1308, 1319, 1330
<code>\skip_new:N</code>	54, 55, 59, 60, 61, 62, 63, 118, 172
<code>\skip_set:Nn</code>	826, 830, 879, 883, 920, 924, 928, 935, 939, 943, 954, 959, 963, 969, 974, 979, 1037, 1038, 1039, 1046, 1050, 1054, 1063, 1068, 1072, 1075, 1079, 1083, 1114, 1118, 1136, 1140, 1144, 1150, 1154, 1158, 2745, 2759
<code>\skip_set_eq:NN</code>	2276, 2322, 2323, 3144, 3145, 3498, 3499
<code>\skip_use:N</code>	828, 832, 867, 871, 875, 895, 899, 918, 937, 946, 952, 957, 961, 972, 976, 977, 982, 1018, 1022, 1048, 1248, 1252, 1255, 1262, 1266, 1269, 2510
<code>\skip_zero:N</code>	2324, 2489, 2633, 2756, 2757
<code>\skip_zero_new:N</code>	1030, 1031, 1032, 1109, 1131, 1132, 1133
<code>\c_zero_skip</code>	841, 847, 853, 918, 952, 992, 998, 1004, 1035, 1040, 1061, 1112, 1134, 1248, 1262, 1275, 1286, 1297, 1308, 1319, 1330
<code>\small</code> . . . . .	3579, 3584, 3589, 3594, 3599
<code>\star</code> . . . . .	2057
<code>start</code> . . . . .	564
<code>\stepcounter</code> . . . . .	2079, 2693
str commands:	
<code>\c_backslash_str</code>	3783, 3792, 3793, 3797, 3798, 3802, 3803, 3834, 3835, 3839, 3844, 3845
<code>\c_colon_str</code>	1812, 1916, 3558
<code>\str_case:nn</code>	214
<code>\str_count:n</code>	201, 3774
<code>\str_if_eq:nnTF</code>	2286, 2334
<code>\str_if_eq_p:nn</code>	2279, 2327
<code>\str_if_in:nnTF</code>	3554
<code>\str_new:N</code>	113, 167
<code>\str_set:Nn</code>	405, 406, 407, 1486, 1487, 1510, 1511
<code>\string</code> . . . . .	271
<code>\strutbox</code> . . . . .	922, 926, 930, 941, 945, 956, 965, 971, 981, 994, 1000, 1006, 1037, 1038, 1039, 1042, 1052, 1056, 1065, 1072, 1077, 1085, 1114, 1115, 1118, 1125, 1138, 1146, 1152, 1160, 2761
<b>T</b>	
T <sub>E</sub> X and L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> commands:	
<code>\@auxout</code> . . . . .	287

widest	564
wrap-ans	1469
wrap-label	349
wrap-label*	349
wrap-opt	1469