

enumext

ENUMERATE EXERCISE SHEETS

V1.0 2024-06-13^{*}

©2024 by Pablo González[†]

CTAN: <https://www.ctan.org/pkg/enumext>

 <https://github.com/pablgonz/enumext>

Abstract

This package provides “*enumerated list*” environments for creating “*simple exercise sheets*” along with “*multiple choice questions*”, storing the `\answers` to these in memory using `multicol` and `scontents` packages and the `l3seq` and `l3prop` modules.

Contents

| | | | | | |
|----------|---|----------|-----------|---|------------|
| 1 | Introduction | 1 | 5 | The storage system | 10 |
| 1.1 | Description and usage | 2 | 5.1 | Keys for storage system | 10 |
| 1.2 | The concept of left margin | 3 | 5.1.1 | Keys for <code>label</code> and <code>ref</code> | 11 |
| 1.3 | User interface | 3 | 5.1.2 | Keys for <code>wrap</code> and <code>display</code> | 11 |
| 1.3.1 | Internal counters | 3 | 5.1.3 | Keys for <code>debug</code> and <code>checking</code> | 11 |
| 1.3.2 | Support for <code>multicol</code> | 3 | 5.2 | The command <code>\anskey</code> | 12 |
| 1.3.3 | Support for <code>minipage</code> | 3 | 5.2.1 | Keys for <code>\anskey</code> | 12 |
| 1.3.4 | The <code>\label</code> and <code>\ref</code> system | 4 | 5.3 | The environment <code>anskey*</code> | 13 |
| 1.3.5 | Support for <code>\footnote</code> | 4 | 5.4 | The environment <code>keyans</code> | 13 |
| 2 | The environments provided | 4 | 5.4.1 | The <code>\item*</code> in <code>keyans</code> | 14 |
| 2.1 | The environment <code>enumext</code> | 4 | 5.5 | The environment <code>keyanspic</code> | 14 |
| 2.2 | The environment <code>enumext*</code> | 5 | 5.5.1 | The command <code>\anspic</code> | 15 |
| 2.3 | The command <code>\item*</code> | 5 | 5.6 | Printing stored content | 15 |
| 2.3.1 | Keys for <code>\item*</code> | 5 | 5.6.1 | The command <code>\getkeyans</code> | 15 |
| 2.4 | The command <code>\item</code> in <code>enumext*</code> | 5 | 5.6.2 | The command <code>\printkeyans</code> | 16 |
| 3 | The command <code>\setenumext</code> | 6 | 6 | Full examples | 17 |
| 4 | The <code>keyval</code> system | 6 | 7 | The way of non-enumerated lists | 19 |
| 4.1 | Keys for <code>label</code> and <code>ref</code> | 6 | 8 | References | 21 |
| 4.2 | Keys for spaces | 7 | 9 | Change history | 22 |
| 4.2.1 | Vertical spaces | 7 | 10 | Index of Documentation | 23 |
| 4.2.2 | Horizontal spaces | 8 | 11 | Implementation | 25 |
| 4.3 | Keys for <code>add code</code> | 8 | 12 | Index of Implementation | 125 |
| 4.4 | Keys for <code>start</code> , <code>series</code> and <code>resume</code> | 9 | | | |
| 4.5 | Keys for <code>multicols</code> | 9 | | | |
| 4.6 | Keys for <code>minipage</code> | 9 | | | |
| 4.6.1 | The command <code>\miniright</code> | 10 | | | |
| 4.6.2 | The key <code>mini-right</code> | 10 | | | |

Motivation and acknowledgments

Usually it is enough to use the classic `enumerate` environment to generate “*simple exercise sheets*” or “*multiple choice questions*”, the basic idea behind `enumext` is to cover three points:

1. To have a simple interface to be able to write “*lists of exercises*” with “*answers*”.
2. To have a simple interface for writing “*multiple choice questions*”.
3. To have a simple interface for placing “*columns*” and “*drawings*” or “*tables*”.

This package would not be possible without Phelype Oleinik who has collaborated and adapted a large part of the code and all \LaTeX team for their great work and to the different members of the `TeX-SX` community who have provided great answers and ideas. Here a note of the main ones:

1. Answer given by Alan Munn in `\topsep`, `\itemsep`, `\partopsep`, `\parsep` - what do they each mean (and what about the bottom)?
2. Answer given by Enrico Gregorio in `Understanding minipages - aligning at top`
3. Answer given by Ulrich Diez in `Different mechanics of hyperlink vs. hyperref`
4. Answer given by Enrico Gregorio in `Minipage and multicols, vertical alignment`

^{*}This file describes a documentation for v1.0, last revised 2024-06-13.

[†]E-mail: pablgonz@educarchile.cl.

License and Requirements

Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License (lpl), version 1.3 or later (<https://www.latex-project.org/lpl.txt>). The software has the status “maintained”.
The enumext package loads and requires multicol[3] and scontents[4] packages, need to have a modern T_EX distribution such as T_EX Live or MiK_TE_X. It has been tested with the standard classes provided by L^AT_EX: book, report, article and letter on 10pt, 11pt and 12pt.

1 Introduction

In the L^AT_EX world there are many useful packages and classes for creating “lists of exercises”, “worksheets” or “multiple choice questions”, classes like exam[1] and packages like xsim[2] do the job perfectly, but they don’t always fit the basic day to day needs.
In my work (and in the work of many teachers) it is common to use “simple exercise sheets” also known as “informal lists of exercises”, as an example:

1. Factor $x^2 - 2x + 1$

2. Factor $3x + 3y + 3z$

3. True False

(a) $\alpha > \delta$

(b) L^AT_EXze is cool?

4. Related to Linux
- (a) You use linux?

(b) Usually uses the package manager?

(c) Rate the following package and class

i. xsim-exam

ii. xsim

iii. exsheets

Sometimes we are also interested in showing the “answers” along with the questions:

1. Factor $x^2 - 2x + 1$

* $(x - 1)^2$

2. Factor $3x + 3y + 3z$

* $3(x + y + z)$

3. True False

(a) $\alpha > \delta$

* False

(b) L^AT_EXze is cool?

* Very True!

4. Related to Linux
- (a) You use linux?

* Yes

(b) Usually uses the package manager?

* Yes, dnf

(c) Rate the following package and class

i. xsim-exam

* doesn't exist for now :(

ii. xsim

* very good

iii. exsheets

* obsolete

Or we are interested in referring to a specific question and its “answer”, for example:
The answer to 3.(b) is “Very True!” and the answer to 4.(c).ii is “very good”.
Or we are interested in printing all the “answers”:

1. $(x - 1)^2$

2. $3(x + y + z)$

3. (a) False

(b) Very True!

4. (a) Yes
- (b) Yes, dnf

(c) i. doesn't exist for now :(

ii. very good

iii. obsolete

Another very common thing to use in my work is “multiple choice questions”, for example:

1. First type of questions

A) value

B) correct

C) value

D) value

2. Second type of questions

I. $2\alpha + 2\delta = 90^\circ$

II. $\alpha = \delta$

III. $\angle EDF = 45^\circ$

A) I only

B) II only

C) I and II only

D) I and III only

E) I, II, and III

★ 3. Third type of questions

(1) $2\alpha + 2\delta = 90^\circ$

(2) $\angle EDF = 45^\circ$

A) value

B) value

C) value

D) value

E) value

4. Question with image and label below:

A

B

A

A) B) C)

A

duck

D) E)

5. Question with image on left side:

A) value

B) value

C) value

D) correct

E) value

B
- Where what we are interested in the <label> and a “short note” that we leave as an explanation, and then print them:
- ©2024 by Pablo González L

2 / 138

1. B), $x = 5$

2. D)

3. C), some note
- * 4. E), A duck

* 5. D), “other note”

*

These “*simple worksheets*” or “*multiple choice questions*” appear to be easy to obtain using a combination of the `enumerate`, `minipage` and `multicols` environments, but like many things, what “*looks simple*” is not so simple.

The `enumext` package was created and designed to meet these small requirements in the creation of “*simple worksheets*” and “*multiple choice questions*”.

1.1 Description and usage

The `enumext` package defines enumerated environments using the `list` environment provided by \LaTeX , but “*does not redefine*” any internal commands associated with it such as `\list`, `\endlist` or `\item` outside of the “*scope*” in which they are defined.

- This package is NOT intend to replace the `enumerate` environment nor replace the powerful `enumitem`[6], the approach is intended to work without hindering either of them.
- This package can be used with `xelatex`, `lualatex`, `pdflatex` and the classical `latex>dvips>ps2pdf` and is present in \TeX Live and \MiKTeX , use the package manager to install. For manual installation, download `enumext.zip` and unzip it, run `lualatex enumext.dtx` and move all files to appropriate locations, then run `mktexlsr`. To produce the documentation run `lualatex enumext.dtx` two times.

```
enumext.sty >> TDS:tex/latex/enumext/  
enumext.pdf >> TDS:doc/latex/enumext/  
README.md >> TDS:doc/latex/enumext/  
enumext.dtx >> TDS:source/latex/enumext/
```

The package is loaded in the usual way:

```
\usepackage{enumext}
```

1.2 The concept of left margin

There is a direct relationship between the parameters `\leftmargin`, `\itemindent`, `\labelwidth` and `\labelsep` plus an “*extra space*” that makes it difficult to obtain the desired *horizontal spaces* in a `list` environment.

Usually we don’t want the `list` to go beyond the left margin of the page, but since these four values are related, that causes a problem. The `enumitem`[6] package adds the `\labelindent` parameter to solve some of these problems. A simplified representation of this in the figure 1.



Figure 1: Representation of horizontal lengths in `enumitem`.

The `enumext` package does NOT provide a user interface to set the values for `\leftmargin` and `\itemindent`, instead it provides the keys `list-offset` and `list-indent` which internally set the values for `\leftmargin` and `\itemindent`. The concepts of `\leftmargin` and `\itemindent` are different in `enumext`. The figure 2 shows the visual representation of idea.



Figure 2: Representation of horizontal lengths concept in `enumext`.

In this way we reduce a *little* the amount of parameters we have to pass. With the default values of keys `list-offset`, `list-indent`, `labelwidth` and `labelsep` the lists will have the (usually) expected output for “*simple worksheets*”. The figure 3 shows the visual representation.



Figure 3: Default horizontal lengths `list-offset=0pt`, `list-indent=\labelwidth+\labelsep` in `enumext`.

1.3 User interface

The user interface consists of two main list environments `enumext` (vertical) and `enumext*` (horizontal), the environment `anskey*` and the command `\anskey` to “store content” and the environments `keyans`, `keyans*` and `keyanspic` for multiple choice. It also provides the commands `\getkeyans` to print individual *stored content*, `\printkeyans` to print all *stored content*, `\miniright` for `minipage` and `\setenumext` to config all [*key* = *val*] options.

1.3.1 Internal counters

The package `enumext` uses internally the `enumXi`, `enumXii`, `enumXiii`, `enumXiv` counters for the four nesting levels of the `enumext` environment, the `enumXv` counter for the `keyans` environment, the `enumXvi` counter for the `keyanspic` environment, the counter `enumXvii` for `enumext*` environment and the counter `enumXviii` for `keyans*` environment.

- If any package defines these counters or they are user-defined in the document, the package will return a fatal error and abort the load.

1.3.2 Support for multicol

The package provides direct support for using the `multicol`[3] package. This allows to obtain directly a two-column output as shown in the figure 4.




Figure 4: Representation of the two column output for a nested level in `enumext` environment.

The “non starred” version of the `multicols` environment is always used together with the `\raggedcolumns` command and is controlled by `columns` and `columns-sep` keys. It can be used in all nesting levels of the environment `enumext` and the environment `keyans` and can together with the `mini-env` key. If you need to force a start a new column `\columnbreak` must be used (see §4.5).

- The `\columnseprule` command is not available as a key and is set to “zero” for the inner levels and the `keyans` environment. If the value of this is set inside the document, it will affect “all environments” that use the `columns` key.

1.3.3 Support for minipage

The package provides direct support for `minipage` environment, this allows you to obtain an output like the one shown in figure 5.



Figure 5: Representation of the `mini-env` output for a nested level `enumext` environment.

The `minipage` environments on “left side” and “right side” is always used with “aligned on top” [`t`]. It can be used in all nesting levels of the environment `enumext` and the environment `keyans` and is controlled by `mini-env` and `mini-sep` keys. In order to switch from the “left” side `minipage` environment to the “right” side one must use the command `\miniright` (see §4.6).

1.3.4 The \label and \ref system

This package provides a user interface like the `enumitem`[6] package to customize the references which is activated by the `ref` key (§4.1), the standard \TeX `\label` and `\ref` commands work as usual. It also provides an “internal reference” system for the “stored content” by means of the key `save-ref` (§5.1.1) when the key `save-ans` (§5.1) is active.

- The implementation of `\label` and `\ref` together with the `save-ref` key are compatible with the `hyperref`[8] package.

1.3.5 Support for \footnote

This package provides an internal implementation for the `\footnote` command which is compatible with the `hyperref` package for the `enumext*` and `keyans*` environments, but will not produce the expected links, and if the `mini-env` key is used in `enumext` or `keyans` environments the output will look like the classic way they are displayed in the environment `minipage`.

The best way to solve this is to use Jean-François Burnol `footnotehyper`[9] package, it will support keeping the links if `hyperref` is loaded with the `hyperfootnotes=true` option (default) and will show the output numbered at the bottom of the page (as opposed to how it is displayed in the `minipage` environment). The way to load it is as follows:

```
\usepackage{footnotehyper}
\makesavenoteenv{enumext}
\makesavenoteenv{enumext*}
```

2 The environments provided

The package `enumext` provides two main list environments, the *vertical* environment `enumext` and the *horizontal* environment `enumext*`.

| | | |
|-----------------------|--|--|
| <code>enumext</code> | <code>\begin{enumext}[\langle keyval list \rangle]</code> | <code>\begin{enumext*}[\langle keyval list \rangle]</code> |
| <code>enumext*</code> | <code>\item \langle item content \rangle</code> | <code>\item \langle item content \rangle</code> |
| | <code>\item [\langle custom \rangle] \langle item content \rangle</code> | <code>\item [\langle custom \rangle] \langle item content \rangle</code> |
| | <code>\item* [\langle symbol \rangle] [\langle offset \rangle] \langle item content \rangle</code> | <code>\item* [\langle symbol \rangle] [\langle offset \rangle] \langle item content \rangle</code> |
| | <code>\end{enumext}</code> | <code>\end{enumext*}</code> |

2.1 The environment enumext

The `enumext` is an environment that works in the same way as the standard `enumerate` environment provided by \LaTeX , `\item` and `\item[\langle custom \rangle]` commands work in the usual way. The environment can be nested with at most “four levels” and the options can be configured globally using `\setenumext` command and locally using `[\langle key = val \rangle]` in the environment.

Example with columns=2

1. This text is in the first level.

(a) This text is in the second level.

i. This text is in the third level.
- A. This text is in the fourth level.

X This text is in the first level.

★ 2. This text is in the first level.

2.2 The environment enumext*

The `enumext*` is a *horizontal list environment* similar to the `enumerate*` environment provided by the `enumitem` package or `task` environment provided by the `task` package , `\item` and `\item[\langle custom \rangle]` work as usual. The options can be configured globally using `\setenumext` command and locally using `[\langle key = val \rangle]` in the environment.

Some considerations to take into account for this environment:

- The environment cannot be nested within itself, but it can be nested within `enumext` and can contain it nested within it.
- Each “item” in the environment is placed within a `minipage` environment whose *width* is stored in the dimension `\itemwidthdim` that includes `labelwidth`, `labelsep` plus the *width of the content*.
- You cannot have floating environments like `figure` or `table` but `\footnote` with `hyperref` support is supported if the `footnotehyper` package is loaded.

Example with columns=2

1. This text is in the first level.

X This text is in the first level.
2. This text is in the first level.

★ 3. This text is in the first level.

2.3 The command \item*

```
\item* \item*
\item* [\langle symbol \rangle]
\item* [\langle symbol \rangle] [\langle offset \rangle]
```

The `\item*`, `\item*[\langle symbol \rangle]` and `\item*[\langle symbol \rangle][\langle offset \rangle]` works like the numbered `\item`, but placing a `\langle symbol \rangle` to the “left” of the `\langle label \rangle` separated from it by the value set by the `labelsep` key and can be `\langle offset \rangle` using the second optional argument. The default values for `\langle symbol \rangle` and `\langle offset \rangle` are `\$ \star \$` ‘★’ and the value set by `labelsep` key.

The *starred argument* ‘★’ cannot be separated by spaces ‘`_`’ from the command, i.e. `\item*` and the first optional argument does “not support” verbatim content. Can be configure with the keys `item-sym*` and `item-pos*` locally in the environment or globally using `\setenumext` command (§3).

🔗 The behavior of `\item*` in the `enumext` and `enumext*` environments is NOT the same as in the `keyans` and `keyans*` environments.

2.3.1 Keys for `\item*`

`item-sym*` = { $\langle symbol \rangle$ } default: $\$star\$$
 Sets the *symbol* to be displayed in the “left” of the box containing the current $\langle label \rangle$ set by `labelwidth` key for `\item*` in `enumext` and `enumext*`. The *symbol* can be in text or math mode, for example `item-sym*={ $\$ast\$$ }`.

`item-pos*` = { $\langle rigid length \rangle$ } default: *by levels*
 Sets the *offset* between the box containing the current $\langle label \rangle$ defined by `labelwidth` key and the $\langle symbol \rangle$ set by `item-sym*` key. The default values are set by `labelsep` key at each level. If positive values are passed it will *offset to the left* and if negative values are passed it will *offset to the right*.

2.4 The command `\item` in `enumext*`

The `\item` command for the `enumext*` environment provides an optional “first argument” `\item($\langle columns \rangle$)` which “joins items” between columns. Let’s consider the following examples adapted directly from the `task` package:

```
\begin{enumext*}[widest=10,columns=4]
  \item The first
  \item* The second
  \item The third
  \item The fourth
  \item(3)* The fifth item is way too long for this and needs three columns
  \item The sixth
  \item the seventh
  \item(2)[X] The eighth item is way too long for this and needs two columns
  \item[Z] The ninth
  \item The tenth
\end{enumext*}
```

- | | | | |
|--|-----------------|--|---------------|
| 1. The first | ★ 2. The second | 3. The third | 4. The fourth |
| ★ 5. The fifth item is way too long for this and needs three columns | 6. The sixth | | |
| 7. the seventh | X | The eighth item is way too long for this and needs Z | The ninth |
| 8. The tenth | two columns | | |

3 The command `\setenumext`

| | | |
|--------------------------|---|---|
| <code>\setenumext</code> | <code>\setenumext{$\langle key = val \rangle$}</code> | <code>\setenumext[$\langle keyans* \rangle$]{$\langle key = val \rangle$}</code> |
| | <code>\setenumext[$\langle enumext, level \rangle$]{$\langle key = val \rangle$}</code> | <code>\setenumext[$\langle print, level \rangle$]{$\langle key = val \rangle$}</code> |
| | <code>\setenumext[$\langle enumext* \rangle$]{$\langle key = val \rangle$}</code> | <code>\setenumext[$\langle print, * \rangle$]{$\langle key = val \rangle$}</code> |
| | <code>\setenumext[$\langle keyans \rangle$]{$\langle key = val \rangle$}</code> | <code>\setenumext[$\langle print* \rangle$]{$\langle key = val \rangle$}</code> |

The command `\setenumext` sets the $\langle keys \rangle$ on a global basis for environments `enumext`, `enumext*`, `keyans`, `keyans*` and the `\printkeyans` command. It can be used both in the preamble and in the body of the document as many times as desired.

The $\langle keys \rangle$ set in the optional arguments of environments and commands have the *highest precedence*, overriding both options passed by `\setenumext`. If the optional argument is not passed, the first level of the environment `enumext` will be taken by default.

- 🔴 The key `save-ans` that activate the “storage system” must NOT be passed through this command and must be passed directly in the optional argument of the “first level” of the environment in which they are executed.

4 The keyval system

The $\langle key = val \rangle$ system used by the `enumext` package is implemented using `l3keys` so it must be taken into consideration that those keys marked as “value forbidden”, that is $\langle key \rangle$ is different from $\langle key= \rangle$.

All $\langle keys \rangle$ described in this section are available for the `enumext`, `enumext*`, `keyans` and `keyans*` environments with the exception of the keys `series`, `resume`, `resume*` which are only available for the “first level” of the environments `enumext` and `enumext*`; and the keys `mini-right`, `mini-right*` which are only available for the `enumext*` and `keyans*` environments.

All $\langle keys \rangle$ related to vertical or horizontal spacing accept a “skip” or “dim” expression if passed between braces, i.e. you do not need to use `\dimeval` or `\dimexpr` to perform calculations.

It should be kept in mind that using any $\langle key \rangle$ that sets a *rubber lengths* or *rigid lengths* for vertical or horizontal space on a level will influence the vertical and horizontal space for *inners levels* and `keyans`, `keyans*` and `keyanspic` environments.

4.1 Keys for label and ref

`label = {⟨\alph* | \Alph* | \arabic* | \roman* | \Roman*⟩}`

default: *by levels*

Sets the `⟨label⟩` that will be printed at the *current level*. The default value for the first level of the environments `enumext` and `enumext*` are `\arabic*`, for second level are `(\alph*)`, for third level are `\roman*`, and for fourth level are `\Alph*`. For `keyans` and `keyans*` environments the default value is `\Alph*`.

- This key is intended to give the basic structure with which the `⟨label⟩` will be displayed, and the form in which it is used by standard “*label and ref*” and the “*internal reference*” system with the `save-ref` key. You cannot use commands with `⟨label⟩` as an argument, for example `\emph{⟨\alph*⟩}` will return an error. For full customization of how `⟨label⟩` is displayed use the `font` or `wrap-label` keys.

`ref = {⟨code {⟨\alph* | \Alph* | \arabic* | \roman* | \Roman*⟩ more code⟩}`

default: *empty*

Modifies the way *cross references* are displayed. The `label` key sets the default form of the *cross references*, by using this key you can define a different format, for example: `ref=\emph{⟨\alph*⟩}` is valid.

Internally it renews the command associated with each counter when it is executed, i.e., in the environment `enumext` the command `\theenumxi` is modified when the key is executed at the first level, `\theenumxii` when it is executed at the second level and `\theenumxiii` together with `\theenumxiv` when it is executed at the third and fourth levels.

- This must be kept in mind, since the values set by the `label` and `ref` keys are not cumulative by levels, so if you have used the `ref` key in the first level and then want to associate the counter with `label` or `ref` in the second level you must use the direct commands, i.e. `\arabic{enumxi}` to indicate the count of the first level instead of using `\theenumxi`.

`labelsep = {⟨rigid length⟩}`

default: `0.3333em`

Sets the *horizontal space* between the box containing the current `⟨label⟩` defined by `label` key and the text of an item on the first line. Internally sets the value of `\labelsep` for the current level.

`labelwidth = {⟨rigid length⟩}`

default: *by label*

Sets the *width* of the box containing the current `⟨label⟩` set by `label` key. Internally sets the value of `\labelwidth` for the current level. The default values are calculated by means of the *width* of a box by setting a *value* to the current counter using ‘0’ for `\arabic*`, ‘M’ for `\Alph*`, ‘m’ for `\alph*`, ‘VIII’ for `\Roman*` and ‘viii’ for `\roman*`.

`widest = {⟨integer | string⟩}`

default: *empty*

Sets the `labelwidth` key pass the `⟨integer⟩` or converting the `⟨string⟩` of the form `\Alph`, `\alph`, `\Roman` or `\roman` to a *value* for the current counter defined by `label` key, then calculating the *width* by means of a box. For example `widest={XXIII}` or `widest={23}` are equivalent. This key is useful when the default values of the `labelwidth` key are smaller than those actually used.

`font = {⟨font commands⟩}`

default: *empty*

Sets the *font style* for the current `⟨label⟩` defined by `label` key. For example `font={\bfseries\small}`.

`align = {⟨left | right | center⟩}`

default: *left*

Sets the *aligned* of `⟨label⟩` defined by `label` key on the current level in the label box.

`wrap-label = {⟨code {#1} more code⟩}`

default: *empty*

Wraps the *current* `⟨label⟩` defined by `label` key referenced by `{#1}`. The `⟨code⟩` must be passed between braces. This key does not modify the value set by the `labelwidth` key and is applied only on `\item` and `\item*`. When using it in the `\setenumext` command it is necessary to use the *double hash* ‘`{#1}`’. For example `wrap-label={\fbox{#1}}` or you can create a command:

```
\NewDocumentCommand \labelbx { s +m }
{%
  \IfBooleanTF{#1}
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedright{#2}}}}%
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{#2}}}}%
}
```

and then pass it through the key `wrap-label={\labelbx{#1}}` or `wrap-label={\labelbx*{#1}}`.

`wrap-label* = {⟨code {#1} more code⟩}`

default: *empty*

The same as the `wrap-label` key but also applies on `\item[⟨custom⟩]`.

4.2 Keys for spaces

`show-length = {⟨true | false⟩}`

default: *false*

Displays on the terminal the values for *all list parameters* at the current level. For *vertical spaces* show the values of `\topsep`, `\itemsep`, `\parsep` and `\partopsep`. For *horizontal spaces* show the values of `\labelwidth`, `\labelsep`, `\itemindent`, `\listparindent` and `\leftmargin`.

4.2.1 Vertical spaces

`topsep` = { \langle rubber length | rigid length \rangle } default: *by levels*

Set the *vertical space* added to both the top and bottom of the list. Internally sets the value of `\topsep` for the current level. The default value for the first level of the environments `enumext` and `enumext*` are 8.0pt plus 2.0pt minus 4.0pt, for second level are 4.0pt plus 2.0pt minus 1.0pt, for third and fourth level are 2.0pt plus 1.0pt minus 1.0pt. For `keyans` and `keyans*` environments the default value is 4.0pt plus 2.0pt minus 1.0pt.

`parsep` = { \langle rubber length | rigid length \rangle } default: *by levels*

Set the *vertical space* between paragraphs within an item. Internally sets the value of `\parsep` for the current level. The default value for the first level of the environments `enumext` and `enumext*` are 4.0pt plus 2.0pt minus 1.0pt, for second level are 2.0pt plus 1.0pt minus 1.0pt, for third and fourth level are 0pt. For `keyans` and `keyans*` environments the default value is 2.0pt plus 1.0pt minus 1.0pt.

`partopsep` = { \langle rubber length | rigid length \rangle } default: *by levels*

Set the *vertical space* added, beyond `topsep`, to the “top” and “bottom” of the entire environment if the environment instance is preceded by a “blank line” or `\par` command. Internally sets the value of `\partopsep` for the current level. The default values for first and second level in environment `enumext` are 2.0pt plus 1.0pt minus 1.0pt, for third and fourth level are 1.0pt minus 1.0pt. For `keyans`, `keyans*` and `enumext*` environments the default value is 2.0pt plus 1.0pt minus 1.0pt.

- The value of this parameter also affects the *inner levels* and the environments `keyans`, `keyanspic` and `keyans*`. Caution should be taken with “blank lines” or `\par` command “before” each environment or nested level when formatting the source code of document. T_EX will enter \langle vertical mode \rangle and apply this value to the “top” and “bottom” the environment or nested level.

`itemsep` = { \langle rubber length | rigid length \rangle } default: *by levels*

Set the *vertical space* between items, beyond the `parsep`. Internally sets the value of `\itemsep` for the current level. The default value for the first level of the environments `enumext` and `enumext*` are 4.0pt plus 2.0pt minus 1.0pt, for the rest of the levels are 2.0pt plus 1.0pt minus 1.0pt. For `keyans` and `keyans*` environments the default value is 4.0pt plus 2.0pt minus 1.0pt.

`noitemsep` \langle value forbidden \rangle default: *not used*

This is a “meta-key” that does not receive an argument. Set `itemsep` and `parsep` equal to 0pt the entire level of environment.

`nosep` \langle value forbidden \rangle default: *not used*

This is a “meta-key” that does not receive an argument. Sets all keys for vertical spacing equal to 0pt the entire level of environment.

`base-fix` \langle value forbidden \rangle default: *not used*

This is a “meta-key” that does not receive an argument available only for the *first level* of environment `enumext` and environment `enumext*`. Fix the *baseline* when an environment `enumext` is nested in `enumext*` or vice versa and there is no material between the `\item` and the start of the environment for example `\item \begin{enumext*}` within the environment `enumext`. Internally sets the keys `topsep`, `above` and `above*` at 0pt.

- The following \langle keys \rangle should be used with “caution”, they are intended to be used at the “top” and “bottom” of the environment when the `columns` or `mini-env` keys do not provide adequate *vertical spaces*. The values passed can be *rubber* or *rigid* lengths, the way they are applied is the way you differ, using the star ‘*’ \langle keys \rangle applies `\vspace*` so that T_EX does *not discard* this space at page break.

`above` = { \langle rubber length | rigid length \rangle } default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the top of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “above” the environment without hindering the value of the `topsep` key. The space is added with `\vspace` so is “discordable”.

`above*` = { \langle rubber length | rigid length \rangle } default: *not used*

Set the *extra vertical space* added, beyond `topsep`, to the top of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “above” the environment without hindering the value of the `topsep` key. The space is added with `\vspace*` so is “not discordable”.

`below` = { \langle rubber length | rigid length \rangle } default: *not used*

Set the *extra vertical space* space added, beyond `topsep`, to the bottom of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “below” the environment without hindering the value of the `topsep` key. The space is added with `\vspace` so is “discordable”.

`below*` = { \langle rubber length | rigid length \rangle } default: *not used*

Set the *extra vertical space* space added, beyond `topsep`, to the bottom of the entire level of environment. This key is intended to give a “fine adjustment” of the vertical space on the “below” the environment without hindering the value of the `topsep` key. The space is added with `\vspace*` so is “not discordable”.

4.2.2 Horizontal spaces

- `itemindent` = { $\langle rigid length \rangle$ } default: 0pt
 Extra *horizontal indentation*, beyond `labelsep`, of the “*first line*” off each item. This value is applied internally using `\hspace` and does not modify the value of `\itemindent`.
- `rightmargin` = { $\langle rigid length \rangle$ } default: 0pt
 Set the *horizontal space* between the right margin of the environment and the right margin of the enclosing environment, the value it takes must be greater than or equal to 0pt. Internally sets the value of `\rightmargin` for the current level.
- `listparindent` = { $\langle rigid length \rangle$ } default: 0pt
 Sets the *horizontal space* indentation, beyond `list-indent`, for second and subsequent paragraphs within a list item. Internally sets the value of `\listparindent` for the current level.
- `list-offset` = { $\langle rigid length \rangle$ } default: 0pt
 Sets the *horizontal translation* of the entire environment level from the left edge of the box defined by the `labelwidth` key. Internally sets the values of `\leftmargin` and `\itemindent` for the current level.
- `list-indent` = { $\langle rigid length \rangle$ } default: labelwidth + labelsep
 Sets the *indentation* of the whole environment under the box defined by `labelwidth` and `labelsep` keys. Internally sets the value of `\leftmargin` and `\itemindent` for the current level.
- If `list-indent=0pt` is set in the environment `enumext` the $\langle label \rangle$ will be part of the text, separated by the value of the `labelsep` key and the *first word*, in simple terms it will look like a “*common paragraph*”. This setting is equivalent (more or less) to the `wide` key provided by the `enumitem` package.

For the `enumext*` and `keyans*` environments the keys `list-indent` and `list-offset` have the same effect.

4.3 Keys for add code

The following $\langle keys \rangle$ should be used with “*caution*”, they are intended to inject $\{\langle code \rangle\}$ into different parts of the defined environments. We must keep in mind that the defined environments are based on the `list` base environment provided by \LaTeX which is defined (simplified) as plain form `\list{\langle arg one \rangle}{\langle arg two \rangle}`. Using the `before*` key does not allow access to the `list` parameters defined by $[\langle key = val \rangle]$.

- `before` = { $\langle code \rangle$ } default: not used
 Execute $\{\langle code \rangle\}$ “*before*” the environment starts. The $\{\langle code \rangle\}$ must be passed between braces, is executed “*after*” performing all calculations related to the *list parameters* in the environment and the parameters sets by $[\langle key = val \rangle]$ that is, in the second argument of the list after setting all the parameters `\list{\langle arg one \rangle}{\langle arg two \rangle}{\langle code \rangle}`.
- `before*` = { $\langle code \rangle$ } default: not used
 Execute $\{\langle code \rangle\}$ “*before*” the environment starts. The $\{\langle code \rangle\}$ must be passed between braces, is executed “*before*” performing all calculations related to the *list parameters* and $[\langle key = val \rangle]$ sets in the environment that is, before the arguments defining the environment are executed: $\{\langle code \rangle\}\list{\langle arg one \rangle}{\langle arg two \rangle}$.
- `first` = { $\langle code \rangle$ } default: not used
 Executes $\{\langle code \rangle\}$ when “*starting*” the environment. The $\{\langle code \rangle\}$ must be passed between braces, is executed right “*after*” all *list parameters* are done, after the second argument of list, just before the first occurrence of `\item`: `\list{\langle arg one \rangle}{\langle arg two \rangle}{\langle code \rangle}\item`.
- Keep in mind that the code set in this key will affect the entire “*body*” of the environment and therefore the inner levels of the list and the `keyans` environment. It is recommended to set this key per level.
- `after` = { $\langle code \rangle$ } default: not used
 Execute $\{\langle code \rangle\}$ “*after*” finishing the environment. The $\{\langle code \rangle\}$ must be passed between braces.

4.4 Keys for start, series and resume

- `start` = { $\langle integer \mid string \rangle$ } default: 1
 Sets the *start value* of the numbering on the current level. Internally $\langle string \rangle$ is passed as value to the counter defined by `label` key on the current level, i.e. it is equivalent to enter `start=5`, `start=E` or `start=v`.
- The following $\langle keys \rangle$ are “*only*” available for the “*first level*” of `enumext` and `enumext*` and are ignored if set when nested inside each other.
- `series` = { $\langle series name \rangle$ } default: not used
 Stores the *keys* of the optional argument of the “*first level*” of the environment in which it is executed in $\{\langle series name \rangle\}$ which is used as an argument in the key `resume`. The $\langle keys \rangle$ stored in $\{\langle series name \rangle\}$ are not cumulative and are overwritten if the same $\{\langle series name \rangle\}$ is used again.
- `resume` = { $\langle series name \rangle$ } default: not used
 Sets the *start value* and *options* for the “*first level*” continuing the numbering of the environment in which the `series=\{\langle series name \rangle\}` key was executed. If passed *without value* this will only set *start value* continue the numbering from the last environment in which `series=\{\langle series name \rangle\}` or `resume=\{\langle series name \rangle\}` is not present and if the `save-ans` key is active it will continue the numbering from the last environment in which it was executed. The *start value* can be overwritten using the `start` key.

`resume*` $\langle \text{value forbidden} \rangle$ default: *not used*

Sets the *start value* and *options* for the “first level” continuing the numbering of the environment in which the `series={\series name}` or `resume={\series name}` keys are NOT present, if the `save-ans` key is active it will continue the numbering from the last environment in which it was executed. The *start value* can be overwritten using the `start` key.

- For security reasons the `series` key will never save in $\langle \text{series name} \rangle$ the keys `series`, `resume`, `resume*`, `save-ans`, `save-key` and `start`. When using the key `resume={\series name}` it will have hierarchy in the $\langle \text{keys} \rangle$ that are saved in $\langle \text{series name} \rangle$, in order to establish the value of a $\langle \text{key} \rangle$ already saved in $\langle \text{series name} \rangle$ it must be placed to the “right” of `resume={\series name}`, the same thing happens with the `resume*` key, the exception is the `save-ans` key that must be placed on the “left” if you want to start the numbering with its value. The `resume` key passed “without value” must be exactly “without value”, i.e. `resume=` cannot be used and if executed before `resume*` it will affect the *start value*.

4.5 Keys for multicol

`columns` = $\langle \text{integer} \rangle$ default: **1**

Set the *number of columns* to be used by the `multicol` environment within the environment. The value must be a positive integer less than or equal to **10**.

`columns-sep` = $\langle \text{rigid length} \rangle$ default: *by level*

Set the *space between columns* used by the `multicol` environment within the environment. Internally sets the value of `\columnsep`, by default its value is equal to the sum of the values set in the keys `labelwidth` and `labelsep` of the current level.

- The `\footnote{\text}` command in the nested levels of `multicol` will not work as expected, prefer the use of `\footnotemark[\number]` inside the environment and `\footnotetext[\number]{\text}` outside the environment or via the `after` key.

4.6 Keys for minipage

`mini-env` = $\langle \text{rigid length} \rangle$ default: *not used*

Sets the *width* of the `minipage` environment on the “right side”. This value added to the value set by the `mini-sep` key to determines the *width* of the `minipage` environment on the “left side”, taking `\linewidth` as the maximum reference value.

`mini-sep` = $\langle \text{rigid length} \rangle$ default: **0.3333em**

Sets the *space between* the `minipage` environment on the “left side” and the `minipage` environment on the “right side”. This separation is applied together with `\hfill`.

4.6.1 The command \miniright

```
\miniright \begin{enumext}[mini-env=\langle rigid length \rangle] \item's before \item \miniright \langle content \rangle \end{enumext}
\begin{enumext}[mini-env=\langle rigid length \rangle] \item's before \item \miniright* \langle content \rangle \end{enumext}
```

The `\miniright` command close the `minipage` environment on the “left side” and opens the `minipage` environment on the “right side” by starting it with the `\centering` command. It must be placed “after” the last `\item` of the current environment and “before” starting the material to be placed on the “right side”. The *starred argument* “*” inhibits the use of `\centering` command i.e. the usual L^AT_EX justification is maintained in the `minipage` on the “right side”.

- The `\footnote{\text}` command in `minipage` environment will work as usual. If you prefer the footnotes to be numbered (not lowercase) and outside the environment, use `\footnotemark[\number]` inside the environment and `\footnotetext[\number]{\text}` outside the environment or via the `after` key (see §1.3.5 for full support).

4.6.2 The key mini-right

In the horizontal list environments `enumext*` and `keyans*` it is not possible to use the `\miniright` command and the `mini-right` key must be used instead.

`mini-right` = $\langle \text{content} \rangle$ default: *not used*

Set the *content* for the drawing or tabular to be placed in the `minipage` environment on the “right side” by starting it with `\centering`. The $\langle \text{content} \rangle$ must be passed between braces.

`mini-right*` = $\langle \text{code for drawing or tabular} \rangle$ default: *not used*

Same as above, but *without* starting with `\centering`.

- The keys `mini-right` and `mini-right*` has a *slightly different* implementation, the argument $\langle \text{content} \rangle$ is saved in a box and then printed outside the environment using *hooks*.

5 The storage system

The entire mechanism for “*storing content*” it is activated according to `save-ans` key on the “*first level*” of `enumext` or `enumext*` environments and it is ignored if they are established when they are nested inside each other. Only when this $\langle key \rangle$ is “*active*” the `\anskey` command and the environments `anskey*`, `keyans`, `keyans*` and `keyanspic` are available.

```
\begin{enumext}[save-ans={\store name}]
  \item Text \anskey{answer}
  \item Text
    \begin{keyans}
      ...
    \end{keyans}
\end{enumext}
```

```
\begin{enumext}[save-ans={\store name}]
  \item Text \anskey{answer}
  \item Text
    \begin{keyanspic}
      ...
    \end{keyanspic}
\end{enumext}
```

By executing the key `save-ans={\store name}` the entire structure of the environment (excluding the first level) including the optional arguments passed to the inner levels or the environment nested in it, along with the content passed to `\anskey`, the current $\langle labels \rangle$ for `\item*` and `\anspic*` in the environments `keyans`, `keyans*` and `keyanspic` will be stored in a $\langle sequence \rangle$ and at the same time will be stored (without the environment structure or optional arguments) in a $\langle prop list \rangle$.

The optional arguments of the inner levels or the nested environment are filtered by excluding all $\langle keys \rangle$ related to the “*stored system*” along with the keys `series`, `resume` and `resume*` when storing in $\langle sequence \rangle$.

5.1 Keys for storage system

- The only $\langle keys \rangle$ available for all levels of the `enumext` environment and the `enumext*` environment are `no-store` and `save-key`, the rest of the $\langle keys \rangle$ described in this section must be passed directly in the optional argument of the “*first level*” of the environment in which the key `save-ans` is executed. The key `save-ans` should NOT be passed with the command `\setenumext`.

`save-ans = { \store name }` default: *not set*
Sets the *name* of the $\langle sequence \rangle$ and $\langle prop list \rangle$ in which the contents will be “*stored*” by `\anskey` and `anskey*` in `enumext` and `enumext*` environments, `\item*` in `keyans` and `keyans*` environments and `\anspic*` in `keyanspic` environment. If the $\langle sequence \rangle$ or $\langle prop list \rangle$ does not exist, it will be created globally and will not be overwritten if the key is used again.

`save-key = { \key list }` default: *not set*
This key *overrides* the default “*stored keys*” of the optional arguments of the inner levels or nested environment that will be passed to the $\langle sequence \rangle$. The $\langle key list \rangle$ passed to this key ignores any $\langle keys \rangle$ in the “*stored system*” and must be passed between braces. For example, if we execute at a second level:

```
\begin{enumext}[save-ans={\store name}]
  \item Text \anskey{answer}
  \item Text
    \begin{enumext}[nosep, columns=2, save-key={columns=3}]
      ...
    \end{enumext}
\end{enumext}
```

The $\langle keys \rangle$ that will be stored by default in the $\langle sequence \rangle$ would be `nosep`, `columns=2`, but using the key `save-key={columns=3}` will overwrite this and store it in the $\langle sequence \rangle$ only the key `columns=3` ignoring all the others.

`save-sep = { \text symbol }` default: `{,}`
Sets the *text symbol* that will separate the current $\langle label \rangle$ to the *optional argument* passed to the `\item*` and `\anspic*` in the `keyans`, `keyans*` and `keyanspic` environments and storing them in the $\langle store name \rangle$ defined by the `save-ans` key. The $\{ \langle text symbol \rangle \}$ must always be passed between braces, whitespace ‘’ is preserved within the braces and only affects the “*stored content*” and not what is displayed when using the `show-ans` or `show-pos` keys.

5.1.1 Keys for label and ref

`save-ref = { \true | \false }` default: *false*
Activates the “*internal label and ref*” mechanism for referencing “*stored content*” in $\langle store name \rangle$ set by `save-ans` key. To reference the location of the “*stored content*” within the environment you must use `\ref{\store name: position}`, where $\langle position \rangle$ corresponds to the position occupied by the “*stored content*” in the $\langle store name \rangle$ returned by the `show-pos` key. For example `\ref{test:4}` will return `3`. (b) which corresponds to the location of the “*stored content*” at position `4` within the environment in which the key `save-ans=test` was set.

`mark-ref = { \symbol }` default: `\textasteriskcentered`
Sets the *symbol* that will be displayed by the `\printkeyans` command only if the `hyperref` package is detected and the `save-ref` key are active. This “*symbol*” is used as a “*link*” between the environment in which the `save-ans` key was used and the place where the command is executed.

5.1.2 Keys for wrap and display

- `wrap-ans` = {`<code> {#1} more code`} default: `\fbox{#1}`
 Wraps the *argument* passed to the `\anskey` and the *body* in `anskey*` environment referenced by {#1} when using the `show-ans` or `show-pos` keys. The {`<code>`} must be passed between braces and only affects the *argument* or *body* and NOT the “stored content” in the *sequence* and *prop list* {`<store name>`} set by `save-ans` key. If this key is passed using `\setenumext` it is necessary to use double ‘{##1}’.
- `wrap-opt` = {`<code> {#1} more code`} default: `[{#1}]`
 Wraps the *optional argument* passed to the `\item*` and `\anspic*` referenced by {#1} in the `keyans`, `keyans*` and `keyanspic` environments when using the `show-ans` or `show-pos` keys. The {`<code>`} must be passed between braces and only affects the current *optional argument* and NOT the “stored content” in the *sequence* and *prop list* {`<store name>`} set by `save-ans` key. If this key is passed using `\setenumext` it is necessary to use double ‘{##1}’.
- `show-ans` = {`<true> | false`} default: `false`
 Displays the *argument* passed to the `\anskey`, the *body* for `anskey*` environment, the `<label>` for `\item*` and `\anspic*` at the place where it is executed. If the optional argument is present in `\item*` or `\anspic*` it will be shown using `wrap-opt` key.
- `mark-ans` = {`<symbol>`} default: `\textasteriskcentered`
 Sets the *symbol* to be displayed in the left margin for `\anskey`, `anskey*`, `\item*` and `\anspic*` in the place where they are executed when using the key `show-ans`.
- `mark-pos` = {`<left> | right`} default: `left`
 Sets the *aligned* of the symbol defined by `mark-ans` key. The “symbol” is aligned in a box with the same dimensions of the label box defined by `labelwidth` key on the current level and separated by the value of the `labelsep` key.

5.1.3 Keys for debug and checking

- `show-pos` = {`<true> | false`} default: `false`
 Displays the *position* occupied by the “stored content” by `\anskey`, `anskey*`, `\item*` and `\anspic*` in the *prop list* {`<store name>`} set by `save-ans` key. This position is used by the `\getkeyans` command and by the `\ref` command if the `save-ref` key is active.
- `check-ans` = {`<true> | false`} default: `false`
 Enables the *checking answer* mechanism displaying an appropriate message on the terminal. This key works under the logic that each `\item` or `\item*` that does not open an inner level or nested environment contains “only one answer” or “only one execution” of the `\anskey` or `anskey*`. It is intended to be used in conjunction with the `no-store` key.
- `no-store` `<value forbidden>` default: `not used`
 This is a *meta-key* that does not receive an argument and disables the structure stored in the *sequence* {`<store name>`} set by `save-ans` key at the entire level or a nested environment in which it runs. This key is intended for use in internal levels or nested `enumext` or `enumext*` environments in which you want to use `enumext` or `enumext*` but “without” using the `\anskey`, “without” use `anskey*`, “without” interfering with the `check-ans` key and “without” storing an unwanted structure in the *sequence* {`<store name>`}.

5.2 The command `\anskey`

`\anskey` `\anskey[<keys>]{<content>}`

The command `\anskey` takes a mandatory non empty argument {`<content>`} and “stores” it in the *sequence* and *prop list* {`<store name>`} set by `save-ans` key. By design the command cannot be nested or passed *verbatim material* in the argument and it is assumed that each *numbered* `\item` or `\item*` within the environment in which it is active it has a “single execution” of `\anskey` unless `\item` or `\item*` open a nested level or use the `no-store` key.

If `save-ref` key are active and the `hyperref`[8] package is detected, `\hyperlink` and `\hypertarget` will be used, otherwise the usual “label and ref” system provided by L^AT_EX will be used.

The `\anskey` command is available for all levels of the `enumext` environment and the `enumext*` environment, but is disabled for the `keyans`, `keyans*` and `keyanspic` environments.

5.2.1 Keys for `\anskey`

By default the {`<content>`} passed to `\anskey` when “storing” in the *sequence* {`<store name>`} has the form `\item <content>`, the following *keys* allow modifying the way in which it is “stored” in the *sequence*.

- `break-col` `<value forbidden>` default: `not used`
 Stores {`<content>`} in the *sequence* {`<store name>`} of the form `\columnbreak \item <content>`.
- `item-join` = {`<columns>`} default: `not set`
 Set the *number of columns* to be used for `\item(<columns>)` and stores {`<content>`} in the *sequence* {`<store name>`} of the form `\item(<columns>)<content>`.
- `item-star` `<value forbidden>` default: `not used`
 Stores {`<content>`} in the *sequence* {`<store name>`} of the form `\item* <content>`.

`item-sym*` = $\langle symbol \rangle$ default: $\$star$
 Sets the *symbol* for `\item*` when using the key `item-star` and stores $\langle content \rangle$ in the *sequence* $\langle store name \rangle$ of the form `\item* $\langle symbol \rangle$ $\langle content \rangle$` . The *symbol* can be in text or math mode, for example `item-sym*= $\$ast$` stores `\item* $\$ast$ $\langle content \rangle$` .

`item-pos*` = $\langle rigid length \rangle$ default: *not set*
 Sets the *offset* for `\item*` when using the keys `item-star` and `item-sym*` and stores $\langle content \rangle$ in the *sequence* $\langle store name \rangle$ of the form `\item* $\langle symbol \rangle$ $\langle offset \rangle$ $\langle content \rangle$` .

Example

```
\begin{enumext}[save-ans=test,show-ans=true]
  \item* Text containing our instructions or questions. \anskey{\first answer}
  \item Text containing our instructions or questions.
    \begin{enumext}
      \item Question.\anskey{\second answer}
    \end{enumext}
  \item Text containing our instructions or questions. \anskey{\third answer}
  \item Text containing our instructions or questions. \anskey{\fourth answer}
\end{enumext}
```

- | | |
|---|---|
| <ul style="list-style-type: none"> ★ 1. Text containing our instructions or questions. <li style="margin-left: 20px;">★ first answer 2. Text containing our instructions or questions. <li style="margin-left: 20px;">(a) Question. <li style="margin-left: 40px;">★ second answer | <ul style="list-style-type: none"> 3. Text containing our instructions or questions. <li style="margin-left: 20px;">★ third answer 4. Text containing our instructions or questions. <li style="margin-left: 20px;">★ fourth answer |
|---|---|

5.3 The environment `anskey*`

`anskey*` `\begin{anskey*}[\langle key = val \rangle] \langle body content \rangle \end{anskey*}`

The environment `anskey*` takes a mandatory $\langle body content \rangle$ and “stores” it in the *sequence* and *prop list* $\langle store name \rangle$ set by `save-ans` key. If `save-ref` key are active and the `hyperref`[8] package is detected, `\hyperlink` and `\hypertarget` will be used, otherwise the usual “*label and ref*” system provided by \LaTeX will be used.

By design the environment cannot be nested but full supports “*verbatim material*” in the body and it is assumed that each numbered `\item` or `\item*` within the environment in which it is active it has a “*single execution*” unless `\item` or `\item*` open a nested level or use the `no-store` key.

The `anskey*` environment is implemented using the `scontents` package, for the correct operation `\begin{anskey*}` and `\end{anskey*}` must be in different lines, all $\langle keys \rangle$ must be passed separated by commas and “without separation” of the start of the environment. Comments “%” or “any character” after `\begin{anskey*}` or `[\langle key = val \rangle]` on the same line are NOT supported, the package `scontents` will return an “error” message if this happens. In a similar way comments “%” or “any character” after `\end{anskey*}` on the same line the package `scontents` will return a “warning” message.

The `anskey*` environment uses the same $\langle keys \rangle$ as the `\anskey` command next to the keys `write-env`, `force-eol` and `overwrite` inherited from package `scontents`. The environment and is available for all levels of the `enumext` environment and the `enumext*` environment, but it is disabled for the `keyans`, `keyans*` and `keyanspic` environments.

- 🔒 For security reasons the keys `store-env`, `print-env` and `write-out` they have been left disabled. It is recommended that you review the `scontents`[4] documentation to understand how the keys described here work.

Example

```
\begin{enumext}[save-ans=test,show-pos=true,start=5]
  \item* Text containing our instructions or questions.
    \begin{anskey*}[item-star]
      \first answer
    \end{anskey*}
  \item Text containing our instructions or questions.
    \begin{enumext}
      \item Question.
        \begin{anskey*}
          \second answer
        \end{anskey*}
      \end{enumext}
  \item Text containing our instructions or questions.
    \begin{anskey*}
      \third answer
    \end{anskey*}
  \item Text containing our instructions or questions.
```



```

\begin{anskey*}
  \langle fourth answer \rangle
\end{anskey*}
\end{enumext}

```

- | | |
|---|--|
| <p>★ 5. Text containing our instructions or questions.</p> <p>[5] First answer with verbatim</p> <p>6. Text containing our instructions or questions.</p> <p style="padding-left: 20px;">(a) Question.</p> <p style="padding-left: 20px;">[6] second answer</p> | <p>7. Text containing our instructions or questions.</p> <p>[7] third answer</p> <p>8. Text containing our instructions or questions.</p> <p>[8] fourth answer</p> |
|---|--|

5.4 The environments `keyans` and `keyans*`

```

keyans \begin{keyans}[\langle key = val \rangle] \item \item[\langle custom \rangle] \item* \item*[\langle content \rangle] \end{keyans}
keyans* \begin{keyans*}[\langle key = val \rangle] \item \item[\langle custom \rangle] \item* \item*[\langle content \rangle] \end{keyans*}

```

The `keyans` and `keyans*` environments are “*enumerated list*” environments designed for “*multiple choice*” questions activated by the `save-ans` key. This environments can NOT be nested and must always be at the “*first level*” of the `enumext` environment, the commands `\item` and `\item[\langle custom \rangle]` work in the usual and the command `\item[\langle columns \rangle]` is available for the `keyans*` environment.

| | |
|--|--|
| <pre> \begin{enumext}[save-ans=test] \item \langle item content \rangle \begin{keyans}[\langle key = val \rangle] \item \langle item content \rangle \item[\langle custom \rangle] \langle item content \rangle \item* \langle item content \rangle \item*[\langle content \rangle] \langle item content \rangle \end{keyans} \end{enumext} </pre> | <pre> \begin{enumext}[save-ans=test] \item \langle item content \rangle \begin{keyans*}[\langle key = val \rangle] \item \langle item content \rangle \item[\langle custom \rangle] \langle item content \rangle \item* \langle item content \rangle \item*[\langle content \rangle] \langle item content \rangle \end{keyans*} \end{enumext} </pre> |
|--|--|

The `\langle keys \rangle` set in the optional argument of the environment are the same (almost) as those of the `enumext` and `enumext*` environments and have higher precedence than those set by `\setenumext[\langle keyans \rangle]{\langle key = val \rangle}` or `\setenumext[\langle keyans* \rangle]{\langle key = val \rangle}`. If the optional argument is not passed or the `\langle keys \rangle` are not set by `\setenumext`, the default values will be the same as the second level of the `enumext` environment with the difference in the `\langle label \rangle` which will be set to `label=\Alph*`.

5.4.1 The `\item*` in `keyans` and `keyans*`

```

\item* \item*
\item*[\langle content \rangle]

```

The `\item*` and `\item*[\langle content \rangle]` command “*store*” the current `\langle label \rangle` set by `label` key next to the `\langle content \rangle` (if it is present) in *sequence* and *prop list* `{\langle store name \rangle}` set by `save-ans` key in the “*first level*” of the `enumext` or `enumext*` environments.

The *starred argument* ‘`*`’ cannot be separated by spaces ‘`␣`’ from the command, i.e. `\item*` and the optional argument does “*not support*” verbatim content. By design it is assumed that the `\item*` will only appear “*once*” within the environment.

- The behavior of `\item*` in `keyans` and `keyans*` environments is NOT the same as in the `enumext` or `enumext*` environments.

Example

```

\begin{enumext}[save-ans=test,columns=2,show-ans=true]
  \item Text containing a question.
  \begin{keyans*}[nosep,columns=2]
    \item Choice
    \item* Correct choice
    \item Choice
    \item Choice
    \item Choice
  \end{keyans*}
  \item Text containing a question and image.
  \begin{keyans}[nosep,mini-env={0.4\linewidth}]
    \item Choice
    \item Choice
    \item Choice
    \item Choice
    \item*[\langle note \rangle] Correct choice
    \miniright
    \includegraphics[scale=0.25]{example-image-a}
    Some text
  \end{keyans}
\end{enumext}

```



```
\end{keyans}  
\end{enumext}
```

1. Text containing a question.
A) Choice
C) Choice
E) Choice

* B) Correct choice
D) Choice

2. Text containing a question and image.
A) Choice
B) Choice
C) Choice
D) Choice
* E) [note] Correct choice


Some text

5.5 The environment keyanspic

`keyanspic` `\begin{keyanspic} [⟨n° above, n° below⟩] \anspic{⟨drawing⟩} \anspic* [⟨content⟩] {⟨drawing⟩}`

The `keyanspic` is a “fake enumerated list” environment that which uses the `\anspic` command instead of `\item`. It is activated by the `save-ans` key and has the same settings as the `keyans` environment. It is intended for placing “drawings” or “tabular” with an in-line or *above* and *below* layout. A representation of the output can be seen in the figure 6.




Figure 6: Representation of the `keyanspic` environment with optional argument [3,2] in `enumext`.

The optional argument determines the number drawings or tabular “above” and “below” within the environment. The vertical separation between “above” and “below” is controlled by the values set by `parsep` and `itemsep` keys passed to `keyans` environment. If the optional argument or the second part of it is omitted the drawings or tabular will be put on a single line.

5.5.1 The command \anspic

`\anspic` `\anspic{⟨drawing or tabular⟩}`
`\anspic* [⟨content⟩] {⟨drawing or tabular⟩}`

The `\anspic` command take three arguments, the *starred argument* ‘*’ store the current `⟨label⟩` next to the `⟨content⟩` (if it is present) in *sequence* and *prop list* {`⟨store name⟩`} set by `save-ans` key.

The *starred argument* ‘*’ cannot be separated by spaces ‘`␣`’ from the command, i.e. `\anspic*` and the optional argument does “not support” verbatim content. By design it is assumed that the *starred argument* ‘*’ will only appear “once” within the environment.

Example

```
\begin{enumext}[save-ans=test,show-ans,nosep]  
  \item Question with images.  
    \begin{keyanspic}[3,2]  
      \anspic{\includegraphics[scale=0.15]{example-image-a}}  
      \anspic{\includegraphics[scale=0.15]{example-image-b}}  
      \anspic{\includegraphics[scale=0.15]{example-image-a}}  
      \anspic{\includegraphics[scale=0.15]{example-image-a}}  
      \anspic*[note]{\includegraphics[scale=0.15]{example-image-a}}  
    \end{keyanspic}  
  \end{enumext}
```

1. Question with images.


A)


B)


C)


D)


* E)[note]

5.6 Printing stored content

5.6.1 The command `\getkeyans`

```
\getkeyans <store name> <position>
```

The command `\getkeyans` prints the “stored content” in *prop list* `{<store name>}` defined by `save-ans` key in the `<position>` returned by the `show-pos` key. The “stored content” can only be accessed *after* it is stored, if `{<store name>}` does not exist the command will return an error.

The form taken by the argument `<store name> <position>` is the same as that used to generate the “internal label and ref” system when `save-ref` key are active, so to refer to a “stored content”. For example `\getkeyans{test:4}` will return the “stored content” at position 4 of the environment in which the key `save-ans=test` was set.

5.6.2 The command `\printkeyans`

```
\printkeyans [<keys>] {<store name>}
\printkeyans* [<keys>] {<store name>}
```

The command `\printkeyans` prints “all stored content” in *sequence* `{<store name>}` defined by `save-ans` key placing this inside the `enumext` environment or the `enumext*` environment if the *starred argument* ‘*’ is used. The “stored content” can only be accessed *after* it is stored in the *sequence*, if `{<store name>}` does not exist the command will return an error.

The optional argument allows managing the `<keys>` in the “first level” of the environment in which the “stored content” of the *sequence* `{<store name>}` will be printed, if the *starred argument* ‘*’ is used it will be `enumext*` otherwise `enumext`.

The default values for the “first level” are the same as the default values for the `enumext` and `enumext*` environments along with the keys `nosep`, `first=\small`, `font=\small` and `columns=2`. For the inner levels of the environment `enumext` saved in the *sequence* `{<store name>}` the default values are the same as those established for the second, third and fourth levels plus the keys `nosep`, `first=\small`, `font=\small`. If the environment `enumext*` is saved within the *sequence* `{<store name>}` it will have the same default values plus the keys `nosep`, `first=\small`, `font=\small`.

Since the command encapsulates by default the `enumext` environment or the `enumext*` environment, we must take some considerations:

- If we execute `\printkeyans*{<store name>}` and the *sequence* `{<store name>}` already contains any `enumext*` environment an error will be returned as we cannot nest.
- If we execute `\printkeyans*{<store name>}` and the *sequence* `{<store name>}` contains any `enumext` environments, they will start with the `<keys>` set for the first level unless they are set in the optional argument or `save-key` is used to modify it.
- If we execute `\printkeyans{<store name>}` and the *sequence* `{<store name>}` contains any environment `enumext*`, they will start with the `<keys>` set by default unless they are set in the optional argument or `save-key` is used to modify it.

The default values for the “first level” of `\printkeyans` commands and `\printkeyans*` are established using `\setenumext[<print>, 1]{<keys>}` and `\setenumext[<print*>]{<keys>}`. If we need to set the `<keys>` for the environment `enumext` “saved” in the *sequence* `{<store name>}` we will use `\setenumext[<print>, level]{<keys>}` and if we need to set the `<keys>` for the environment `enumext*` “saved” in the *sequence* `{<store name>}` we will use `\setenumext[<print>, *]{<keys>}`.

Example

```
\begin{enumext}[save-ans=sample,columns=2,show-pos=true,nosep,save-ref=true]
  \item Factor $3x+3y+3z$. \anskey{$3(x+y+z)}
  \item True False

  \begin{enumext}[nosep]
    \item \LaTeX2e\ is cool? \anskey{Very True!}
  \end{enumext}

  \item Related to Linux

  \begin{enumext}[nosep]
    \item You use linux? \anskey{Yes}
    \item Rate the following package and class
      \begin{enumext}[nosep]
        \item \texttt{xsim} \anskey{very good}
        \item \texttt{exsheets} \anskey{obsolete}
      \end{enumext}
    \end{enumext}
\end{enumext}
```

```
\end{enumext}

The answer to \ref{sample:4} is \getkeyans{sample:4} and the answers to
all the worksheets are as follows:

\printkeyans{sample}
```

1. Factor $3x + 3y + 3z$.

[1]
2. True False

(a) is cool?

[2]
3. Related to Linux

(a) You use linux?

[3]

(b) Rate the following package and class

i.

[4]

ii.

[5]

The answer to 3.(b).i is very good and the answers to all the worksheets are as follows:

1. $3(x + y + z)$

2. (a) Very True!

3. (a) Yes

(b) i. very good

ii. obsolete
- *

*

*

*

*

6 Full examples

Here I will leave as an example some adaptations questions taken from TeX-SX. The examples are attached to this documentation and can be extracted from your PDF viewer or from the command line by running:

```
$ pdftdetach -saveall enumext.pdf
```

and then you can use the excellent arara¹ tool to compile them.

Example 1

Adapted from the response given by Enrico Gregorio in Squares for answer choice options and perfect alignment to mathematical answers.

1. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

36 km/h.

360 km/h.

27,8 km/h.

$3,60 \times 10^8$ km/h.
2. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10} \text{ m}$) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15} \text{ m}$). Qual è la relazione tra queste due unità di misura?

$1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

$1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.

$1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

$1 \text{ \AA} = 1 \times 10^3 \text{ fm}$.

3. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

36 km/h.

360 km/h.

27,8 km/h.

$3,60 \times 10^8$ km/h.

4. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10} \text{ m}$) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15} \text{ m}$). Qual è la relazione tra queste due unità di misura?

$1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

$1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.

$1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

$1 \text{ \AA} = 1 \times 10^3 \text{ fm}$.

1. B

2. A

3. B

4. A

Example 2

Adapted from the response given by Florent Rougon in Multiple choice questions with proposed answers in random order — addition of automatic correction (cross mark).

1. La velocità di $1,00 \times 10^2$ m/s espressa in km/h è:

36 km/h.

360 km/h.

27,8 km/h.

$3,60 \times 10^8$ km/h.
2. In fisica nucleare si usa l'angstrom (simbolo: $1 \text{ \AA} = 1 \times 10^{-10} \text{ m}$) e il fermi o femtometro ($1 \text{ fm} = 1 \times 10^{-15} \text{ m}$). Qual è la relazione tra queste due unità di misura?

$1 \text{ \AA} = 1 \times 10^5 \text{ fm}$.

$1 \text{ \AA} = 1 \times 10^{-5} \text{ fm}$.

$1 \text{ \AA} = 1 \times 10^{-15} \text{ fm}$.

¹The cool TeX automation tool: <https://www.ctan.org/pkg/arara>

- D

$1\text{ \AA} = 1 \times 10^3\text{ fm.}$
3. La velocità di $1,00 \times 10^2\text{ m/s}$ espressa in km/h è:

A

36 km/h.

✓

B

360 km/h.

C

27,8 km/h.

D

$3,60 \times 10^8\text{ km/h.}$
4. In fisica nucleare si usa l'angstrom (simbolo: $1\text{ \AA} = 1 \times 10^{-10}\text{ m}$) e il fermi o femtometro ($1\text{ fm} = 1 \times 10^{-15}\text{ m}$). Qual è la relazione tra queste due unità di misura?

✓

A

$1\text{ \AA} = 1 \times 10^5\text{ fm.}$

B

$1\text{ \AA} = 1 \times 10^{-5}\text{ fm.}$

C

$1\text{ \AA} = 1 \times 10^{-15}\text{ fm.}$

D

$1\text{ \AA} = 1 \times 10^3\text{ fm.}$
1. B

2. A

3. B

4. A
- *

*

*

*

Example 3

A “simple multiple choice” test .

1. First type of questions

A

value

B

correct

C

value

D

value
2. Second type of questions

I.

$2\alpha + 2\delta = 90^\circ$

II.

$\alpha = \delta$

III.

$\angle EDF = 45^\circ$

A

I only

B

II only

C

I and II only

D

I and III only

E

I, II, and III
3. Third type of questions

(1)

$2\alpha + 2\delta = 90^\circ$

(2)

$\angle EDF = 45^\circ$

A

value

B

value

C

value

D

value

E

value
4. Question with image and label below:

A

A

D

B

B

A

C



E

B

5. Question with image on left side:

A

value

B

value

C

value

D

correct

E

value

Test keys

1. B, $x = 5$

2. D

3. C, some note

*


4. E, A duck


*

5. D, other note


*

Example 4

A “simple worksheet” using ducks :) .



Factor $x^2 - 2x + 1$



Factor $3x + 3y + 3z$

The following questions need to be cuaqtified :)

©2024 by Pablo González L

18 / 138



True False

- (a) $\alpha > \delta$
- (b) $\mathbb{E}\mathbb{T}\mathbb{E}\mathbb{X}$ ze is cool?



Related to Linux

- (a) You use linux?
- (b) Usually uses the package manager?
- (c) Rate the following package and class
 - i. `xsim-exam`
 - ii. `xsim`
 - iii. `exsheets`

The answer to 1 is $(x - 1)^2$ and the answer to 3.(a) is False.

- | | | | |
|-------------------|---|---------------------------------|---|
| 1. $(x - 1)^2$ | * | (b) Yes, dnf | * |
| 2. $3(x + y + z)$ | * | (c) i. doesn't exist for now :(| * |
| 3. (a) False | * | ii. very good | * |
| (b) Very True! | * | iii. obsolete | * |
| 4. (a) Yes | * | | |

Example 5

Adapted from the response given by Stephen in SAT like question format

| | | | |
|---|--|---|--|
| 1 | Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action. | 3 | Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action. |
| 2 | Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action. | 4 | Which choice best describes what happens in the passage? A) One character argues with another character who intrudes on her home. B) One character receives a surprising request from another character. C) One character reminisces about choices she has made over the years. D) One character criticizes another character for pursuing an unexpected course of action. |

1. A) 2. C) 3. B) 4. D)

7 The way of non-enumerated lists

It is possible to use (or abuse) the `enumext` environment to mimic *non-enumerated* list environments such as `itemize` and `description`, clearly the *keys* to “store answers”, the `keyans` and `keyanspic` environments lose their sense and it is not the focus of the main of this package, but, why not to do it?. Here I leave as an example other uses of the `enumext` environment that can be helpful for specific purposes. The “trick” to generate these *fake environments* is set `label={}` or `label={\some}` and play with the `list-indent`, `list-offset`, `font` and `wrap-label` keys.

Fake itemize environment

Here we set the `label` key using the default settings in $\mathbb{E}\mathbb{T}\mathbb{E}\mathbb{X}$ for the four levels `\textbullet`, `\textendash`, `\textasteriskcentered` and `\textperiodcentered` together with the `nosep` key to reduce the vertical spaces in the left side example and set the `label` key in *mathematical mode* for the right side as `\ast`, `\diamond`, `\circ` and `\star` for the four levels together with the `nosep` key

- First level item
 - Second level item
 - * Third level item
 - Fourth level item
 - First level item
- * First level item
 - ◇ Second level item
 - Third level item
 - ★ Fourth level item
 - * First level item

Fake description environment

Here we set `label={}` and `list-indent=2.5em`, `font=\bfseries`.

SomeThing A short one-line description.
This is an entry *without* a label.
Something A short *one-line* description text.
Something long A much *longer* description text may take more than one line or more than one paragraph.
Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

If we add `list-indent=0pt` you get *widest style*:

SomeThing A short one-line description.
This is an entry *without* a label.
Something A short *one-line* description text.
Something long A much *longer* description text may take more than one line or more than one paragraph.
Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

🔗 The small space at the beginning of the “*unlabeled entry*” corresponds to `\labelsep` and can be removed using `\hspace{-\labelsep}` at the beginning of the line.

Description indented by label

Here we set `label={}` and we will give a convenient value to `labelsep` and `labelwidth`, for example we can take as reference our *longest label* and pass it as value using:

```
\newlength{\descitemwd}  
\settowidth{\descitemwd}{\textbf{Something long}}
```

and then use `labelsep=4pt`, `labelwidth=\descitemwd`, `font=\bfseries`.

SomeThing A short one-line description.
This is an entry *without* a label.
Something A short one-line description.
Something long A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

The environment can be translated so that the *(labels)* are on the left margin calculating the value passed to the `list-offset` key, in this case it will be equal to the sum of the values set by the `labelwidth` and `labelsep` keys finally resulting as `list-offset={-\descitemwd - 4pt}`.

SomeThing A short one-line description.
This is an entry *without* a label.
Something A short one-line description.
Something long A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

If we add `align=right` it will look like this:

SomeThing A short one-line description.
This is an entry *without* a label.
Something A short one-line description.
Something long A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

🔗 At this point we have used `list-offset={-\descitemwd - 4pt}` instead of `list-offset={-\labelwidth - \labelsep}`, this is because the parameters `\labelwidth` and `\labelsep` take the default values, as if we had not set `label`.

Description with multi-line labels

The `label` key does not accept *multiline material*, this is where the `wrap-label*` key comes into play. Unlike the `enumitem` package, the `align` key only supports three options, so what we will do is create a command in the style `\parleft` of `enumitem` that allows us to place *multiline labels* using `\parbox`.


```
\NewDocumentCommand \labelbx { s +m }
{%
  \IfBooleanTF{#1}
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedright{#2}}}}%
  {\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{#2}}}}%
}
```

Now we just need to set `wrap-label*={\labelbx{#1}}`.

Something A short one-line description.

This is an entry *without* a label.

Something A short one-line description.

Something A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

long Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

SoMeThInG A much longer description. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

LoNg vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

Final notes

The original implementation (if you can call it that) of the ideas that led to the creation of `enumext` were some macros using the `enumerate[5]` package for personal use created in early 2003, the code was quite questionable, but functional for these simple requirements.

With the great answers given by Christian Hupfer in [Create a fake label ref using list](#) and the answer given by David Carlisle in [Change the use of label ref by data save in an array \(list\)](#) I managed to create a more solid code than the original version, now using the `l3prop[11]` and `l3seq[11]` modules together with the `hyperref[8]` and `enumitem[6]` packages, which did the job, but with some limitations.

As time went by I took these limitations as a personal challenge which I called “*reinventing the wheel*”, since there were packages and classes that did more or less what I was looking for, but did not fit my simple requirements. This “*reinventing the wheel*” finally ended up becoming `enumext`.

Why list environments?

The answer is simple, first I love the beauty of its syntax and many of what I had already written used the `enumerate` environment or lists created using the `enumitem` package. In my mind I thought: how complicated could it be to write a package that looked like `enumitem`? It seemed simple enough, of course I didn’t have in mind the mess I was getting into working with `list` environments, `minipage` and adding support for the `multicol` and `hyperref` packages.

Of course, seeing the final result of the experiment “*reinventing the wheel*” I am quite satisfied.

Why not random questions and other utilities

The “*random*” type questions I love and hate them at the same time, although they simplify a lot the work when creating a multiple choice test, but you lose the beauty of typesetting a document with \LaTeX , that is to say the output does not always look as nice as it should, even if they are only alternatives these must follow a certain order when presented either numerical or presentation, that said handling that using *nested lists* is quite complicated so I do not classify to be implemented.

8 References

- [1] HIRSCHHORN, PHILIP. “Using the exam document class”. Available from CTAN, <https://www.ctan.org/pkg/exam>, 2023.
- [2] NIEDERBERGER, CLEMENS. “xsim – eXercise Sheets IMproved”. Available from CTAN, <https://www.ctan.org/pkg/xsim>, 2023.
- [3] MITTELBACH, FRANK. “An environment for multicolumn output”. Available from CTAN, <https://www.ctan.org/pkg/multicol>, 2024.
- [4] GONZÁLEZ, PABLO. “scontents - Stores \LaTeX contents in memory or files”. Available from CTAN, <https://www.ctan.org/pkg/scontents>, 2022.
- [5] The \LaTeX Project. “enumerate – Enumerate with redefinable labels”. Available from CTAN, <https://www.ctan.org/pkg/enumerate>, 2024.
- [6] BEZOS, JAVIER. “Customizing lists with the enumitem package”. Available from CTAN, <https://www.ctan.org/pkg/enumitem>, 2019.
- [7] BERRY, KARL. “ $\text{\LaTeX} 2_{\epsilon}$: An Unofficial Reference Manual”. Available from CTAN, <https://ctan.org/pkg/latex2e-help-texinfo>, 2024.

- [8] The \LaTeX Project. “Extensive support for hypertext in \LaTeX ”. Available from CTAN, <https://www.ctan.org/pkg/hyperref>, 2024.
- [9] BURNOL, JEAN-FRANÇOIS. “The footnotehyper package”. Available from CTAN, <https://www.ctan.org/pkg/footnotehyper>, 2021.
- [10] The \LaTeX Project. “The expl3 package”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2024.
- [11] The \LaTeX Project. “The \LaTeX 3 Interfaces”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2024.
- [12] The \LaTeX Project. “The \LaTeX 2_ε sources”. Available from CTAN, <https://ctan.org/tex-archive/macros/latex/base>, 2024.
- [13] The \LaTeX Project. “ \LaTeX for authors current version”. Available from CTAN, <https://ctan.org/pkg/latex-base>, 2024.
- [14] GUNDLACH, PATRICK. “The lua-visual-debug package”. Available from CTAN, <https://www.ctan.org/pkg/lua-visual-debug>, 2023.
- [15] LEMVIG, MOGENS. “The shortlst package”. Available from CTAN, <https://www.ctan.org/pkg/shortlst>, 1998.
- [16] NIEDERBERGER, CLEMENS. “tasks – Horizontally columned lists”. Available from CTAN, <https://www.ctan.org/pkg/tasks>, 2022.

9 Change history

v1.0 2024-06-13 – First public release.

10 Index of Documentation

The italic numbers denote the pages where the corresponding entry is described.

C

Document class:

article 2

book 2

exam 2

letter 2

report 2

\columnbreak 4, 12

\columnsep 10

Commands provide by enumext:

\anskey 11-13

\anspic 11, 12, 15

\getkeyans 12, 16

\item* 5-7, 11, 12, 14

\item 5-7, 9, 10, 12, 14

\miniright 10

\printkeyans 6, 11, 16

\setenumext 5-7, 11, 12, 14, 16

Counters defined by enumext:

enumXiii 4

enumXii 4

enumXiv 4

enumXi 4

enumXviii 4

enumXvii 4

enumXvi 4

enumXv 4

E

Environments provide by enumext:

anskey* 11-13

enumext* 4-14, 16

enumext 4-9, 11-14, 16, 19

keyans* 4-14

keyanspic 4, 6, 8, 11-13, 15, 19

keyans 4-9, 11-15, 19

Environments:

enumerate 1, 3, 5, 21

figure 5

list 3, 9, 21

minipage 3-5, 10, 21

multicols 3, 4, 10

table 5

task 5

F

\footnote 5

I

\itemsep 8

K

Keys for command provide by enumext:

break-col 12

item-join 12

item-pos* 13

item-star 12, 13

item-sym* 13

Keys for environments provide by enumext:

above* 8

above 8

after 9, 10

L

\label 4

Labels provide by enumext:

\Alph* 7, 14

\Roman* 7

\alph* 7

\arabic* 7

align 7, 20

base-fix 8

before* 9

before 9

below* 8

below 8

check-ans 12

columns-sep 4, 10

columns 4, 8, 10

first 9

font 7

item-pos* 5, 6

item-sym* 5, 6

itemindent 9

itemsep 8, 15

labelsep 3, 5-7, 9, 10, 12, 20

labelwidth 3, 6, 7, 9, 10, 12, 20

labelwith 5

label 7, 9, 14, 19, 20

list-indent 3, 9

list-offset 3, 9, 20

listparindent 9

mark-ans 12

mark-pos 12

mark-ref 11

mini-env 4, 8, 10

mini-right* 6, 10

mini-right 6, 10

mini-sep 4, 10

no-store 11-13

noitemsep 8

nosep 8, 19

parsep 8, 15

partopsep 8

ref 4, 7

resume* 6, 10, 11

resume 6, 9-11

rightmargin 9

save-ans 4, 6, 9-16

save-key 10, 11, 16

save-ref 4, 7, 11-13, 16

save-sep 11

series 6, 9-11

show-ans 11, 12

show-length 7

show-pos 11, 12, 16

start 9, 10

topsep 8

widest 7

wrap-ans 12

wrap-label* 7, 20

wrap-label 7

wrap-opt 12

| | | | |
|----------------|-----------------|----------------|-------------|
| \roman* | 7 | l3seq | 1, 21 |
| \labelsep | 3, 7 | multicol | 1, 2, 4, 21 |
| \labelwidth | 3, 7 | scontents | 1, 2, 13 |
| \linewidth | 10 | task | 5, 6 |
| \listparindent | 9 | xsim | 2 |
| P | | \parsep | 8 |
| Packages: | | \partopsep | 8 |
| enumerate | 21 | R | |
| enumext | 1–6, 15, 21 | \raggedcolumns | 4 |
| enumitem | 3–5, 9, 20, 21 | \ref | 4 |
| footnotehyper | 4, 5 | \rightmargin | 9 |
| hyperref | 4, 5, 11–13, 21 | T | |
| l3keys | 6 | \topsep | 8 |
| l3prop | 1, 21 | | |

11 Implementation

The most recent publicly released version of `enumext` is available at CTAN: <https://www.ctan.org/pkg/enumext>. While general feedback via email is welcomed, specific bugs or feature requests should be reported through the issue tracker: <https://github.com/pablgonz/enumext/issues>.

- The documentation presented here is far from professional, it contains a lot of obvious information that to the eye of a \TeX pert are superfluous, but, after so many years developing this project is the only way to remember what does what.

11.1 General conventions

Variables containing `i`, `ii`, `iii` and `iv` are associated by level with the `enumext` environment, variables containing `v` are associated with the `keyans` environment, variables containing `vi` are associated with the `keyanspic` environment, variables containing `vii` are associated with the `enumext*` environment and variables containing `viii` are associated with the `keyans*` environment.

To simplify writing and documentation some variables and functions that are common to the different levels of the environments are described using a capital “X”.

The temporary function `__enumext_tmp:n` is used in different parts of the package code for variable creation or execution of other functions that are grouped into this one.

All variables and functions defined in this package are private and are NOT intended to work or be used by another package or module.

11.2 Initial set up

Start the DocStrip guards.

```
1 <*package>
```

Identify the internal prefix (\LaTeX 3 DocStrip convention) for `l3doc` class.

```
2 <@@=enumext>
```

11.3 Declaration of the package

First we will make sure we have a minimum (super updated) version of \LaTeX to work correctly.

```
3 \NeedsTeXFormat{LaTeX2e}[2024-06-01]
```

Now declare the `enumext` package.

```
4 \ProvidesExplPackage
5   {enumext}
6   {2024-06-13}
7   {1.0}
8   {Enumerate exercise sheets}
```

Finally check if the `multicol` and `scontents` packages are loaded, if not we load it.

```
9 \hook_gput_code:nnn {begindocument} {enumext}
10 {
11   \IfPackageLoadedTF { multicol }
12   {
13     \msg_info:nnn { enumext } { package-load } { multicol }
14   }
15   {
16     \msg_info:nnn { enumext } { package-not-load } { multicol }
17     \RequirePackage{multicol}[2024-05-23]
18   }
19   \IfPackageLoadedTF { scontents }
20   {
21     \msg_info:nnn { enumext } { package-load } { scontents }
22   }
23   {
24     \msg_info:nnn { enumext } { package-not-load } { scontents }
25     \RequirePackage{scontents}
26   }
27 }
```

11.4 Definition of variables

Variables that do not appear in this section are created by means of `\keys_define:nn` or some function described below.

```
\l__enumext_level_int
\l__enumext_level_h_int
\l__enumext_anskey_level_int
\l__enumext_keyans_level_int
\l__enumext_keyans_level_h_int
\l__enumext_keyans_pic_level_int
```

Integer variables will control the nesting levels of the environments and `\anskey` command.

```
28 \int_new:N \l__enumext_level_int
29 \int_new:N \l__enumext_level_h_int
30 \int_new:N \l__enumext_anskey_level_int
31 \int_new:N \l__enumext_keyans_level_int
32 \int_new:N \l__enumext_keyans_level_h_int
33 \int_new:N \l__enumext_keyans_pic_level_int
```

(End of definition for `\l__enumext_level_int` and others.)

```
\l__enumext_starred_bool
\g__enumext_starred_bool
\l__enumext_starred_first_bool
\l__enumext_standar_bool
\g__enumext_standar_bool
\l__enumext_standar_first_bool
\l__enumext_anskey_env_bool
\l__enumext_keyans_env_bool
\g__enumext_start_line_tl
\g__enumext_envir_name_tl
```

Internal variables used by functions `__enumext_is_not_nested:`, `__enumext_is_on_first_level:` and `__enumext_keyans_start_line:` (§11.6.1).

```
34 \bool_new:N \l__enumext_starred_bool
35 \bool_new:N \g__enumext_starred_bool
36 \bool_new:N \l__enumext_starred_first_bool
37 \bool_new:N \l__enumext_standar_bool
38 \bool_new:N \g__enumext_standar_bool
39 \bool_new:N \l__enumext_standar_first_bool
40 \bool_new:N \l__enumext_anskey_env_bool
41 \bool_new:N \l__enumext_keyans_env_bool
42 \tl_new:N \g__enumext_start_line_tl
43 \tl_new:N \g__enumext_envir_name_tl
```

(End of definition for `\l__enumext_starred_bool` and others.)

```
\l__enumext_counter_i_tl
\l__enumext_counter_ii_tl
\l__enumext_counter_iii_tl
\l__enumext_counter_iv_tl
\l__enumext_counter_v_tl
\l__enumext_counter_vi_tl
\l__enumext_counter_vii_tl
\l__enumext_counter_viii_tl
```

Variables to store the “*name of the counters*” `enumXi`, `enumXii`, `enumXiii` and `enumXiv` for `enumext` environment, `enumXv` for `keyans` environment and `enumXvi` for the `keyanspic` environment. The counters `enumXvii` and `enumXviii` are used by `enumext*` and `keyans*` environments.

The initial values of these variables are set by the function `__enumext_define_counters:Nn` (§11.10) and then modified by the function `__enumext_label_style:Nnn` used by `label` key (§11.13).

```
44 \cs_set_protected:Npn \__enumext_tmp:n #1
45 {
46   \tl_new:c { l__enumext_counter_#1_tl }
47 }
48 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\l__enumext_counter_i_tl` and others.)

```
\c__enumext_counter_style_tl
\l__enumext_ref_key_arg_tl
\l__enumext_ref_the_count_tl
\l__enumext_the_counter_X_tl
\l__enumext_renew_the_count_X_tl
```

Internal variables used by `ref` key (§11.13).

```
49 \tl_const:Nn \c__enumext_counter_style_tl
50 { { arabic } { roman } { Roman } { alph } { Alph } }
51 \tl_new:N \l__enumext_ref_key_arg_tl
52 \tl_new:N \l__enumext_ref_the_count_tl
53 \cs_set_protected:Npn \__enumext_tmp:n #1
54 {
55   \tl_new:c { l__enumext_renew_the_count_#1_tl }
56   \tl_new:c { l__enumext_the_counter_#1_tl }
57   \tl_set:ce { l__enumext_the_counter_#1_tl } { \exp_not:c { theenumX#1 } }
58 }
59 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\c__enumext_counter_style_tl` and others.)

```
\g__enumext_resume_int
\g__enumext_resume_vii_int
\l__enumext_resume_name_tl
\l__enumext_resume_active_bool
\g__enumext_starred_series_tl
\g__enumext_standar_series_tl
\g__enumext_item_symbol_tl
```

Internal variables used by `resume`, `resume*` and `series` keys (§11.24).

```
60 \int_new:N \g__enumext_resume_int
61 \int_new:N \g__enumext_resume_vii_int
62 \tl_new:N \l__enumext_resume_name_tl
63 \bool_new:N \l__enumext_resume_active_bool
64 \tl_new:N \g__enumext_standar_series_tl
65 \tl_new:N \g__enumext_starred_series_tl
```

(End of definition for `\g__enumext_resume_int` and others.)


```

\l__enumext_current_widest_dim
\g__enumext_counter_styles_tl
\g__enumext_widest_label_tl
\l__enumext_label_width_by_box

```

The variable `\l__enumext_current_widest_dim` stores the current label width, the variable `\g__enumext_counter_styles_tl` stores the default `<label style>` and the variable `\g__enumext_widest_label_tl` the label width. These variables are used by `widest` (§11.14) and `label` (§11.12) keys.

```

66 \dim_new:N \l__enumext_current_widest_dim
67 \tl_new:N \g__enumext_counter_styles_tl
68 \tl_new:N \g__enumext_widest_label_tl
69 \box_new:N \l__enumext_label_width_by_box

```

(End of definition for `\l__enumext_current_widest_dim` and others.)

```

\l__enumext_leftmargin_tmp_X_bool
\l__enumext_leftmargin_tmp_X_dim
\l__enumext_leftmargin_X_dim
\l__enumext_itemindent_X_dim

```

The boolean variable `\l__enumext_leftmargin_tmp_X_bool` and the dimensional variable `\l__enumext_leftmargin_tmp_X_dim` are used by the `list-indent` key (§11.17). The variables `\l__enumext_leftmargin_X_dim` and `\l__enumext_itemindent_X_dim` are used and set by the function `__enumext_calc_hspace:N` (§11.37.1).

```

70 \cs_set_protected:Npn \__enumext_tmp:n #1
71 {
72   \bool_new:c { l__enumext_leftmargin_tmp_#1_bool }
73   \dim_new:c { l__enumext_leftmargin_tmp_#1_dim }
74   \dim_new:c { l__enumext_leftmargin_#1_dim }
75   \dim_new:c { l__enumext_itemindent_#1_dim }
76 }
77 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_leftmargin_tmp_X_bool` and others.)

```

\l__enumext_multicols_above_X_skip
\l__enumext_multicols_below_X_skip

```

Internal variables used by `columns` key §11.21).

```

78 \cs_set_protected:Npn \__enumext_tmp:n #1
79 {
80   \skip_new:c { l__enumext_multicols_above_#1_skip }
81   \skip_new:c { l__enumext_multicols_below_#1_skip }
82 }
83 \clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_multicols_above_X_skip` and `\l__enumext_multicols_below_X_skip`.)

```

\g__enumext_minipage_stat_int
\l__enumext_minipage_left_skip
\l__enumext_minipage_right_skip
\l__enumext_minipage_after_skip
\g__enumext_minipage_right_skip
\g__enumext_minipage_after_skip
\l__enumext_minipage_left_X_dim
\l__enumext_minipage_active_X_bool

```

Internal variables used by `\miniright` command (§11.22.4) and the keys `mini-right`, `mini-right*`, `mini-env` and `mini-sep` (§11.20, §11.22).

```

84 \int_new:N \g__enumext_minipage_stat_int
85 \skip_new:N \l__enumext_minipage_left_skip
86 \skip_new:N \l__enumext_minipage_right_skip
87 \skip_new:N \l__enumext_minipage_after_skip
88 \skip_new:N \g__enumext_minipage_right_skip
89 \skip_new:N \g__enumext_minipage_after_skip
90 \cs_set_protected:Npn \__enumext_tmp:n #1
91 {
92   \dim_new:c { l__enumext_minipage_left_#1_dim }
93   \bool_new:c { l__enumext_minipage_active_#1_bool }
94 }
95 \clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\g__enumext_minipage_stat_int` and others.)

```

\l__enumext_wrap_label_X_bool
\l__enumext_wrap_label_opt_X_bool
\l__enumext_start_X_int
\l__enumext_fake_item_indent_X_tl
\l__enumext_label_fill_left_X_tl
\l__enumext_label_fill_right_X_tl
\l__enumext_vspace_a_star_X_bool
\l__enumext_vspace_b_star_X_bool

```

The integer variable `\l__enumext_start_X_int` are used by the `start` key (§11.14), the token list `\l__enumext_fake_item_indent_X_tl` is used by `itemindent` key (§11.17.1), the variables `\l__enumext_label_fill_left_X_tl` and `\l__enumext_label_fill_right_X_tl` are used by the `align` key (§11.12). The boolean vars `\l__enumext_vspace_a_star_X_bool`, `\l__enumext_vspace_b_star_X_bool` are used by `above`, `above*`, `below` and `below*` keys (§11.19).

```

96 \cs_set_protected:Npn \__enumext_tmp:n #1
97 {
98   \bool_new:c { l__enumext_wrap_label_#1_bool }
99   \bool_new:c { l__enumext_wrap_label_opt_#1_bool }
100   \int_new:c { l__enumext_start_#1_int }
101   \tl_new:c { l__enumext_fake_item_indent_#1_tl }
102   \tl_new:c { l__enumext_label_fill_left_#1_tl }
103   \tl_new:c { l__enumext_label_fill_right_#1_tl }
104   \bool_new:c { l__enumext_vspace_a_star_#1_bool }
105   \bool_new:c { l__enumext_vspace_b_star_#1_bool }
106 }
107 \clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_wrap_label_X_bool` and others.)

```
\l__enumext_store_active_bool
\l__enumext_store_name_tl
\g__enumext_store_name_tl
\l__enumext_store_anskey_arg_tl
\l__enumext_store_anskey_env_tl
\l__enumext_store_anskey_opt_tl
\l__enumext_store_current_label_tl
\l__enumext_store_current_opt_arg_tl
\l__enumext_store_current_label_tmp_tl
```

The variable `\l__enumext_store_active_bool` setting by `save-ans` key (§11.25.1) activates all the mechanism related to `\anskey`, `anskey*`, `keyans`, `keyans*` and `keyanspic` environments.

The variable `\l__enumext_store_name_tl` saves the $\langle\textit{store name}\rangle$ set by the `save-ans` key of the *sequence* and *prop list* in which we will store, the variable `\g__enumext_store_name_tl` it's just a global copy of $\langle\textit{store name}\rangle$ used by different functions.

The variable `\l__enumext_store_anskey_arg_tl` save the *argument* of `\anskey` (§11.29) and the variables `\l__enumext_store_anskey_env_tl` and `\l__enumext_store_anskey_opt_tl` save the $\langle\textit{body}\rangle$ and the $\langle\textit{keys}\rangle$ of the environment `anskey*` (§11.30).

The variables `\l__enumext_store_current_label_tl` and `\l__enumext_store_current_opt_arg_tl` save the *current label* and *optional argument* of `\item*` (§11.35.2) and `\anspic*` (§11.40.1) for the `keyans`, `keyans*` and `keyanspic` environments.

The variable `\l__enumext_store_current_label_tmp_tl` is a temporary variable used by `keyans`, `keyans*` and `keyanspic` at various points.

```
108 \bool_new:N \l__enumext_store_active_bool
109 \tl_new:N \l__enumext_store_name_tl
110 \tl_new:N \g__enumext_store_name_tl
111 \tl_new:N \l__enumext_store_anskey_arg_tl
112 \tl_new:N \l__enumext_store_anskey_env_tl
113 \tl_new:N \l__enumext_store_anskey_opt_tl
114 \tl_new:N \l__enumext_store_current_label_tl
115 \tl_new:N \l__enumext_store_current_opt_arg_tl
116 \tl_new:N \l__enumext_store_current_label_tmp_tl
```

(End of definition for `\l__enumext_store_active_bool` and others.)

```
\l__enumext_setkey_tmpa_tl
\l__enumext_setkey_tmpb_tl
\l__enumext_setkey_tmpa_int
\l__enumext_setkey_tmpa_seq
\l__enumext_setkey_tmpb_seq
```

Internal variables used by the command `\setenumext` (§11.46).

```
117 \tl_new:N \l__enumext_setkey_tmpa_tl
118 \tl_new:N \l__enumext_setkey_tmpb_tl
119 \int_new:N \l__enumext_setkey_tmpa_int
120 \seq_new:N \l__enumext_setkey_tmpa_seq
121 \seq_new:N \l__enumext_setkey_tmpb_seq
```

(End of definition for `\l__enumext_setkey_tmpa_tl` and others.)

```
\l__enumext_print_keyans_starred_tl
\l__enumext_mark_position_str
\g__enumext_item_symbol_tl
\l__enumext_print_keyans_X_tl
\l__enumext_store_save_key_X_tl
\l__enumext_store_save_key_X_bool
\l__enumext_store_upper_level_X_bool
```

Internal variables used by command `\printkeyans` (§11.45), `show-pos` key (§11.26), `item-sym*` key (§11.33), `save-key` key (§11.26.2) and “*storage level system*”.

```
122 \tl_new:N \l__enumext_print_keyans_starred_tl
123 \str_new:N \l__enumext_mark_position_str
124 \tl_new:N \g__enumext_item_symbol_tl
125 \cs_set_protected:Npn \__enumext_tmp:n #1
126 {
127   \tl_new:c { \l__enumext_print_keyans_#1_tl }
128   \tl_new:c { \l__enumext_store_save_key_#1_tl }
129   \bool_new:c { \l__enumext_store_save_key_#1_bool }
130   \bool_new:c { \l__enumext_store_upper_level_#1_bool }
131 }
132 \clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {#1} }
```

(End of definition for `\l__enumext_print_keyans_starred_tl` and others.)

```
\l__enumext_keyans_pic_body_seq
\l__enumext_keyans_pic_width_dim
\l__enumext_keyans_pic_above_int
\l__enumext_keyans_pic_below_int
\l__enumext_keyans_pic_above_skip
```

Internal variables used by `keyanspic` environment (§11.40.2).

```
133 \seq_new:N \l__enumext_keyans_pic_body_seq
134 \dim_new:N \l__enumext_keyans_pic_width_dim
135 \int_new:N \l__enumext_keyans_pic_above_int
136 \int_new:N \l__enumext_keyans_pic_below_int
137 \skip_new:N \l__enumext_keyans_pic_above_skip
```

(End of definition for `\l__enumext_keyans_pic_body_seq` and others.)

```
\l__enumext_check_answers_bool
\g__enumext_check_ans_key_bool
\l__enumext_check_start_line_env_tl
\g__enumext_check_starred_cmd_int
\g__enumext_item_anskey_int
\g__enumext_item_number_int
\g__enumext_item_number_bool
\g__enumext_item_answer_diff_int
```

Internal variables used by “*internal check answer*” mechanism (§11.25.3) used by the `check-ans` and `no-store` keys and check for starred commands `\item*` in `keyans` and `keyans*` environments and `\anspic*` in `keyanspic` environment.

```
138 \bool_new:N \l__enumext_check_answers_bool
139 \bool_new:N \g__enumext_check_ans_key_bool
140 \tl_new:N \l__enumext_check_start_line_env_tl
141 \int_new:N \g__enumext_check_starred_cmd_int
142 \int_new:N \g__enumext_item_anskey_int
```

```

143 \int_new:N \g__enumext_item_number_int
144 \bool_new:N \l__enumext_item_number_bool
145 \int_new:N \g__enumext_item_answer_diff_int

```

(End of definition for `\l__enumext_check_answers_bool` and others.)

```

\l__enumext_hyperref_bool
\l__enumext_footnotes_key_bool

```

The boolean variable `\l__enumext_hyperref_bool` will determine if the `hyperref` package is present or load in memory (§11.9). The boolean variable `\l__enumext_footnotes_key_bool` determine if `hyperref` is load with key `hyperfootnotes=true`.

```

146 \bool_new:N \l__enumext_hyperref_bool
147 \bool_new:N \l__enumext_footnotes_key_bool

```

(End of definition for `\l__enumext_hyperref_bool` and `\l__enumext_footnotes_key_bool`.)

```

\l__enumext_newlabel_arg_one_tl
\l__enumext_newlabel_arg_two_tl
\l__enumext_write_aux_file_tl
\l__enumext_label_copy_X_tl

```

Internal variables used by `save-ref` key (§11.26). The variables `\l__enumext_label_copy_X_tl` correspond to temporary copies of the *labels* defined by level on which operations will be performed.

The variables `\l__enumext_newlabel_arg_one_tl` and `\l__enumext_newlabel_arg_two_tl` will be used to form the arguments passed to the function `__enumext_newlabel:nn` (§11.9) and the variable `\l__enumext_write_aux_file_tl` will be in charge of executing the writing code in the `.aux` file.

```

148 \tl_new:N \l__enumext_newlabel_arg_one_tl
149 \tl_new:N \l__enumext_newlabel_arg_two_tl
150 \tl_new:N \l__enumext_write_aux_file_tl
151 \cs_set_protected:Npn \__enumext_tmp:n #1
152 {
153   \tl_new:c { \l__enumext_label_copy_#1_tl }
154 }
155 \clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_newlabel_arg_one_tl` and others.)

```

\g__enumext_footnote_int
\g__enumext_footnote_arg_seq
\g__enumext_footnote_int_seq

```

Internal variables used for redefinition of `\footnote` (§11.34).

```

156 \int_new:N \g__enumext_footnote_int
157 \seq_new:N \g__enumext_footnote_arg_seq
158 \seq_new:N \g__enumext_footnote_int_seq

```

(End of definition for `\g__enumext_footnote_int`, `\g__enumext_footnote_arg_seq`, and `\g__enumext_footnote_int_seq`.)

```

\l__enumext_item_starred_X_bool
\l__enumext_item_column_pos_X_int
\g__enumext_item_count_all_X_int
\l__enumext_joined_item_X_int
\l__enumext_joined_item_aux_X_int
\l__enumext_tmpa_X_int
\l__enumext_item_text_X_box
\l__enumext_joined_width_X_dim
\l__enumext_item_width_X_dim
\g__enumext_item_symbol_aux_X_tl
\l__enumext_align_label_X_str
\g__enumext_minipage_active_X_bool
\l__enumext_miniright_code_X_box
\g__enumext_minipage_center_X_bool
\g__enumext_minipage_right_X_dim
\g__enumext_minipage_right_X_skip

```

Internal variables used by `enumext*` and `keyans*` environments.

```

159 \cs_set_protected:Npn \__enumext_tmp:n #1
160 {
161   \bool_new:c { \l__enumext_item_starred_#1_bool }
162   \int_new:c { \l__enumext_item_column_pos_#1_int }
163   \int_new:c { \g__enumext_item_count_all_#1_int }
164   \int_new:c { \l__enumext_joined_item_#1_int }
165   \int_new:c { \l__enumext_joined_item_aux_#1_int }
166   \int_new:c { \l__enumext_tmpa_#1_int }
167   \box_new:c { \l__enumext_item_text_#1_box }
168   \dim_new:c { \l__enumext_joined_width_#1_dim }
169   \dim_new:c { \l__enumext_item_width_#1_dim }
170   \tl_new:c { \g__enumext_item_symbol_aux_#1_tl }
171   \str_new:c { \l__enumext_align_label_#1_str }
172   \bool_new:c { \g__enumext_minipage_active_#1_bool }
173   \box_new:c { \l__enumext_miniright_code_#1_box }
174   \bool_new:c { \g__enumext_minipage_center_#1_bool }
175   \dim_new:c { \g__enumext_minipage_right_#1_dim }
176   \skip_new:c { \g__enumext_minipage_right_#1_skip }
177 }
178 \clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `\l__enumext_item_starred_X_bool` and others.)

```
\c__enumext_all_envs_clist
```

An internal `clist-var` variable to run with `__enumext_tmp:n`.

```

179 \clist_const:Nn \c__enumext_all_envs_clist
180 {
181   {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv},
182   {keyans}{v}, {enumext*}{vii}, {keyans*}{viii}
183 }

```

(End of definition for `\c__enumext_all_envs_clist`.)

11.5 Public dimension

The package `enumext` only provides a single public dimension `\itemwidthdim` and is intended for user convenience only and is not for internal use as such. This dimension is set in all environments and is only used by the `wrap-ans` key at its default value.

```
184 \dim_zero_new:N \itemwidthdim
```

11.6 Some utility functions

`__enumext_at_begin_document:n` A internal “hook” function used for copying plain `list` and `minipage` environments definition and `hyperref` detection.

```
185 \cs_new_protected:Npn \__enumext_at_begin_document:n #1
186 {
187   \hook_gput_code:nnn {begindocument} {enumext} { #1 }
188 }
```

(End of definition for `__enumext_at_begin_document:n`.)

`__enumext_after_env:nn` A internal “hook” functions for execute code `mini-right` and `mini-right*` keys outside the `enumext*` and `keyans*` environments and print `check-ans` outside the `enumext` and `enumext*` environments.

`__enumext_before_env:nn`

```
189 \cs_new_protected:Npn \__enumext_after_env:nn #1 #2
190 {
191   \hook_gput_code:nnn {env/#1/after} {enumext} {#2}
192 }
193 \cs_new_protected:Npn \__enumext_before_env:nn #1 #2
194 {
195   \hook_gput_code:nnn {env/#1/before} {enumext} {#2}
196 }
```

(End of definition for `__enumext_after_env:nn` and `__enumext_before_env:nn`.)

`__enumext_level:` Function for check current level in `enumext`.

```
197 \cs_new:Nn \__enumext_level:
198 {
199   \int_to_roman:n { \l__enumext_level_int }
200 }
```

(End of definition for `__enumext_level:.`)

`__enumext_if_is_int:nT` A conditional function to know if the variable we are passing is an integer used by `start` and `widest` keys. This function is taken directly from the answer given by Henri Menke in [How to test if an expl3 function argument is an integer expression?](#)

`__enumext_if_is_int:nF`
`__enumext_if_is_int:nTF`

```
201 \prg_new_protected_conditional:Npnn \__enumext_if_is_int:n #1 { T, F, TF }
202 {
203   \regex_match:nnTF { ^[\+|-]?[\d]+$ } {#1} % $
204   { \prg_return_true: }
205   { \prg_return_false: }
206 }
```

(End of definition for `__enumext_if_is_int:nT`, `__enumext_if_is_int:nF`, and `__enumext_if_is_int:nTF`.)

`__enumext_regex_counter_style:` The internal function `__enumext_regex_counter_style:` replace the ‘*’ with the actual counter of the running level and is used by the `ref` key. It loops through the defined counter styles in `\c__enumext_counter_style_tl` and replace ‘*’ by real command, for example, looking for `\arabic*` and replacing that by `\arabic{<counter>}` defined on the current level.

```
207 \cs_new_protected:Nn \__enumext_regex_counter_style:
208 {
209   \tl_map_inline:Nn \c__enumext_counter_style_tl
210   {
211     \regex_replace_once:nnN { \c{##1}\* }
212     { \c{##1}\cB{\u{\l__enumext_ref_the_count_tl}\cE} } \l__enumext_ref_key_arg_tl
213   }
214 }
```

(End of definition for `__enumext_regex_counter_style:.`)

`__enumext_show_length:nnn`

Internal function used by `show-length` key to show “*all lengths*” calculated and use in `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```

215 \cs_new:Npn \__enumext_show_length:nnn #1 #2 #3
216 {
217   * ~ #2
218   \prg_replicate:nn { 14 - \str_count:n {#2} } { ~ }
219   = ~ \use:c { #1_use:c } { \__enumext_#2_#3_#1 } \\
220 }

```

(End of definition for `__enumext_show_length:nnn`.)

11.6.1 Utilities for environments and levels

`__enumext_is_not_nested:`
`__enumext_is_on_first_level:`

The function `__enumext_is_not_nested:` set the variables `\g__enumext_standar_bool` and `\g__enumext_starred_bool` to “*true*” only if the environments `enumext` and `enumext*` are nested in each other.

```

221 \cs_new_protected:Nn \__enumext_is_not_nested:
222 {
223   \str_case:en { \@currentenv }
224   {
225     {enumext}
226     {
227       \bool_lazy_and:nnT
228       { \bool_not_p:n { \g__enumext_standar_bool } }
229       { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
230       {
231         \bool_gset_true:N \g__enumext_standar_bool
232       }
233     }
234     {enumext*}
235     {
236       \bool_lazy_and:nnT
237       { \bool_not_p:n { \g__enumext_starred_bool } }
238       { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
239       {
240         \bool_gset_true:N \g__enumext_starred_bool
241       }
242     }
243   }
244 }

```

The function `__enumext_is_on_first_level:` will set the variables `\l__enumext_standar_first_bool` (§11.25.1), `\l__enumext_starred_first_bool` (§11.25.1) and `\l__enumext_anskey_env_bool` (§11.30) to “*true*” only if the environment is not nested and we are in the “*first level*” of it . We will also save the *start line number* of each environment in the variable `\g__enumext_start_line_tl` and the *name* of each environment in the variable `\g__enumext_envir_name_tl` to use in messages related to the `check-ans` key and `.log` file.

```

245 \cs_new_protected:Nn \__enumext_is_on_first_level:
246 {
247   \bool_lazy_all:nT
248   {
249     { \bool_if_p:N \g__enumext_standar_bool }
250     { \int_compare_p:nNn { \l__enumext_level_int } = { 1 } }
251     { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
252   }
253   {
254     \bool_set_true:N \l__enumext_standar_first_bool
255     \bool_set_true:N \l__enumext_anskey_env_bool
256     \tl_gset:Nn \g__enumext_envir_name_tl { enumext }
257     \tl_gset:Nn \g__enumext_start_line_tl
258     {
259       on ~ line ~ \exp_not:V \inputlineno
260     }
261   }
262   \bool_lazy_all:nT
263   {
264     { \bool_if_p:N \g__enumext_starred_bool }
265     { \int_compare_p:nNn { \l__enumext_level_h_int } = { 1 } }
266     { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
267   }
268   {
269     \bool_set_true:N \l__enumext_starred_first_bool

```

```

270         \bool_set_true:N \l__enumext_anskey_env_bool
271         \tl_gset:Nn \g__enumext_envir_name_tl { enumext* }
272         \tl_gset:Ne \g__enumext_start_line_tl
273         {
274             on ~ line ~ \exp_not:V \inputlineno
275         }
276     }
277 }

```

(End of definition for __enumext_is_not_nested: and __enumext_is_on_first_level:.)

__enumext_keyans_start_line:

The function __enumext_keyans_start_line: will save the start line number of the environments **keyans**, **keyans*** and **keyanspic** in the variable \l__enumext _check_start_line_env_tl to use in the __enumext_check_starred_cmd:n function.

```

278 \cs_new_protected:Nn \__enumext_keyans_start_line:
279 {
280     \str_case:en { \@currentenvir }
281     {
282         {keyans}
283         {
284             \tl_set:Ne \l__enumext_check_start_line_env_tl
285             {
286                 in ~ 'keyans' ~ start ~ on ~ line ~ \exp_not:V \inputlineno
287             }
288         }
289         {keyans*}
290         {
291             \tl_set:Ne \l__enumext_check_start_line_env_tl
292             {
293                 in ~ 'keyans*' ~ start ~ on ~ line ~ \exp_not:V \inputlineno
294             }
295         }
296         {keyanspic}
297         {
298             \tl_set:Ne \l__enumext_check_start_line_env_tl
299             {
300                 in ~ 'keyanspic' ~ start ~ on ~ line ~ \exp_not:V \inputlineno
301             }
302         }
303     }
304 }

```

(End of definition for __enumext_keyans_start_line:.)

11.6.2 Utilities for log and terminal

__enumext_reset_global_vars:

The function __enumext_reset_global_vars: will be passed to the function __enumext_execute_after_env: and will return the global variables to their default values after being used.

__enumext_reset_global_int:

__enumext_reset_global_bool:

__enumext_reset_global_tl:

```

305 \cs_new_protected:Nn \__enumext_reset_global_vars:
306 {
307     \__enumext_reset_global_int:
308     \__enumext_reset_global_bool:
309     \__enumext_reset_global_tl:
310 }
311 \cs_new_protected:Nn \__enumext_reset_global_int:
312 {
313     \int_gzero:N \g__enumext_item_number_int
314     \int_gzero:N \g__enumext_item_anskey_int
315     \int_gzero:N \g__enumext_item_answer_diff_int
316 }
317 \cs_new_protected:Nn \__enumext_reset_global_bool:
318 {
319     \bool_gset_false:N \g__enumext_check_ans_key_bool
320     \bool_gset_false:N \g__enumext_standar_bool
321     \bool_gset_false:N \g__enumext_starred_bool
322 }
323 \cs_new_protected:Nn \__enumext_reset_global_tl:
324 {
325     \tl_gclear:N \g__enumext_store_name_tl
326     \tl_gclear:N \g__enumext_start_line_tl
327     \tl_gclear:N \g__enumext_envir_name_tl
328 }

```


(End of definition for `__enumext_reset_global_vars:` and others.)

`__enumext_log_global_vars:` The function `__enumext_log_global_vars:` will be passed to the function `__enumext_execute_after_env:` and write to the `.log` file the number of elements saved in the *prop list* and *sequence* created by the `save-ans` key along with the value of the integer variable created for the `resume` key.

```

329 \cs_new_protected:Nn \__enumext_log_global_vars:
330 {
331   \msg_log:nneeee { enumext } { prop-seq-int-hook }
332   { \g__enumext_store_name_tl }
333   { \prop_count:c { g__enumext_ \g__enumext_store_name_tl _prop } }
334   { \seq_count:c { g__enumext_ \g__enumext_store_name_tl _seq } }
335   { \int_use:c { g__enumext_resume_ \g__enumext_store_name_tl _int } }
336 }

```

The function `__enumext_log_answer_vars:` will be passed to the function `__enumext_execute_after_env:` and write to the `.log` file the number of items and answers along with the difference between them.

```

337 \cs_new_protected:Nn \__enumext_log_answer_vars:
338 {
339   \msg_log:nneeee { enumext } { item-answer-hook }
340   { \int_use:N \g__enumext_item_number_int }
341   { \int_use:N \g__enumext_item_anskey_int }
342   { \int_eval:n { \g__enumext_item_number_int - \g__enumext_item_anskey_int } }
343 }

```

(End of definition for `__enumext_log_global_vars:` and `__enumext_log_answer_vars:`.)

11.7 Copying list and minipage environments

The `list` environment provided by L^AT_EX has the following plain form:

```

\list{⟨arg one⟩}{⟨arg two⟩}
  \item[⟨opt⟩]
\endlist

```

As a precaution we copy them using `__enumext_at_begin_document:n` in case any package redefines the `list` environment or a related command.

`__enumext_start_list:nn` The functions `__enumext_start_list:nn`, `__enumext_stop_list:` and `__enumext_item_std:w` correspond to copies of `\list`, `\endlist` and `\item` from plain definition of `list` environment.

```

344 \__enumext_at_begin_document:n
345 {
346   \cs_new_eq:NN \__enumext_start_list:nn \list
347   \cs_new_eq:NN \__enumext_stop_list: \endlist
348   \cs_new_eq:NN \__enumext_item_std:w \item
349 }

```

(End of definition for `__enumext_start_list:nn`, `__enumext_stop_list:`, and `__enumext_item_std:w`.)

The `minipage` environment provided by L^AT_EX has the following (simplified) plain form:

```

\minipage[⟨pos⟩][⟨height⟩][⟨inner-pos⟩]{⟨width⟩}
  ⟨internal implement⟩
\endminipage

```

As a precaution we copy them using `__enumext_at_begin_document:n` in case any package redefines the `minipage` environment or a related command.

`__enumext_minipage:w` The functions `__enumext_minipage:w`, `__enumext_endminipage:` and correspond to copies of `\minipage`, `\endminipage` from plain definition of `minipage` environment.

```

350 \__enumext_at_begin_document:n
351 {
352   \cs_new_eq:NN \__enumext_minipage:w \minipage
353   \cs_new_eq:NN \__enumext_endminipage: \endminipage
354 }

```

(End of definition for `__enumext_minipage:w` and `__enumext_endminipage:`.)

11.8 The internal minipage environment

```

\__enumext_internal_mini_page:
  __enumext_mini_env*

```

The function `__enumext_internal_mini_page:` creates a internal `__enumext_mini_env*` environment (*custom version of minipage*) setting the `\if@minipage` switch to “false” to allow spaces at the “above” of the environment, plus we will add `\vspace{0pt}` to maintain alignment on “top”. This environment will be used internally by the `mini-env` key, it is not documented in the user interface and is for internal use only. This function is passed to the function `__enumext_safe_exec:` in the `enumext` environment definition (§11.38) and `__enumext_safe_exec_vii:` in the `enumext*` environment definition (§11.42)

```

355 \cs_new_protected:Nn \__enumext_internal_mini_page:
356 {
357   \int_compare:nNnT { \__enumext_level_int } = { 0 }
358   {
359     \DeclareDocumentEnvironment{__enumext_mini_env*}{ m }
360     {
361       \__enumext_minipage:w [ t ] { ##1 }
362       \legacy_if_gset_false:n { @minipage }
363       \vspace { 0pt }
364     }
365     { \__enumext_endminipage: }
366   }
367 }

```

(End of definition for `__enumext_internal_mini_page:` and `__enumext_mini_env*`.)

11.9 Compatibility with hyperref and footnotehyper

First we define the necessary rules using “hooks” to determine if the `hyperref` package is loaded.

```

368 \hook_gput_code:nnn { begindocument } { enumext } { \__enumext_after_hyperref: }
369 \hook_gset_rule:nnnn { begindocument } { enumext } { after } { hyperref }

```

```

\__enumext_after_hyperref:
\__enumext_hypertarget:nn
\__enumext_phantomsection:

```

The function `__enumext_after_hyperref:` sets the state of the boolean variable `\l__enumext_hyperref_bool` to “true” if the package is loaded. At this point we will use the public macro `\IfHyperBoolean` to determine if the `hyperfootnotes=true` key is present, if so, we set the state of the boolean variable `\l__enumext_footnotes_key_bool` to “true”.

```

370 \cs_new_protected:Nn \__enumext_after_hyperref:
371 {
372   \IfPackageLoadedTF { hyperref }
373   {
374     \msg_info:nnn { enumext } { package-load } { hyperref }
375     \bool_set_true:N \l__enumext_hyperref_bool
376     \IfHyperBoolean{hyperfootnotes}
377     {
378       \typeout{hyperfootnotes=true}
379       \bool_set_true:N \l__enumext_footnotes_key_bool
380     }
381     { \typeout{hyperfootnotes=false} }
382   }
383   { }

```

If the state of the variable `\l__enumext_footnotes_key_bool` is true we will check if the package `footnotehyper` is loaded, in case it is not present, we will set the value of `\l__enumext_footnotes_key_bool` to false and we will redefine `\footnote`.

```

384 \bool_if:NT \l__enumext_footnotes_key_bool
385 {
386   \IfPackageLoadedTF { footnotehyper }
387   {
388     \msg_info:nnn { enumext } { package-load } { footnotehyper }
389   }
390   {
391     \typeout{No ~ footnotehyper ~ load}
392     \typeout{Load ~ and ~ use ~ \string\makesavenoteenv{enumext*}}
393     \bool_set_false:N \l__enumext_footnotes_key_bool
394   }
395 }

```

The functions `__enumext_hypertarget:nn` and `__enumext_phantomsection:` correspond to the internal copies of `\hypertarget` and `\phantomsection`. If the boolean variable `\l__enumext_hyperref_bool` is false the functions `__enumext_hypertarget:nn` and `__enumext_phantomsection:` will be disabled.

```

396 \bool_if:NTF \l__enumext_hyperref_bool
397 {
398   \cs_new_eq:NN \__enumext_hypertarget:nn \hypertarget
399   \cs_new_eq:NN \__enumext_phantomsection: \phantomsection
400 }
401 {
402   \cs_new_eq:NN \__enumext_hypertarget:nn \use_none:nn
403   \cs_new_eq:NN \__enumext_phantomsection: \prg_do_nothing:
404 }
405 }

```

(End of definition for `__enumext_after_hyperref:`, `__enumext_hypertarget:nn`, and `__enumext_phantomsection:`.)

`__enumext_newlabel:nn` The function `__enumext_newlabel:nn` write the information to the `.aux` file when using the `save-ref` key. The arguments taken by the function are:

#1: `\l__enumext_newlabel_arg_one_tl`

#2: `\l__enumext_newlabel_arg_two_tl`

The trick here is to manage the number of arguments passed to `\newlabel{#1}{#2}` according to the presence of the `hyperref` package.

```

406 \cs_new_protected:Npn \__enumext_newlabel:nn #1 #2
407 {
408   \protected@write \@auxout { }
409   {
410     \token_to_str:N \newlabel {#1}
411     {
412       {#2}
413       \bool_if:NT \l__enumext_hyperref_bool
414       { { \thepage } {#2} {#1} }
415       { }
416     }
417   }
418   \__enumext_hypertarget:nn {#1} { }
419   \__enumext_phantomsection:
420 }

```

(End of definition for `__enumext_newlabel:nn`.)

11.10 Definition of counters

`__enumext_define_counters:Nn` To create the necessary “counters” we must first make sure that they are not already defined by the user or a package such as `enumitem`, otherwise a error will be returned and the package loading will be aborted. The arguments taken by the function are:

#1: A token list `\l__enumext_counter_X_tl` for “store” the counter’s name.

#2: The counter’s name.

```

421 \cs_new_protected:Npn \__enumext_define_counters:Nn #1 #2
422 {
423   \cs_if_exist:cTF { c@ #2 }
424   { \msg_fatal:nnn { enumext } { counters } { #2 } }
425   {
426     \tl_set:Nn #1 { #2 }
427     \newcounter { #2 }
428   }
429 }

```

(End of definition for `__enumext_define_counters:Nn`.)

The counters created here are `enumXi`, `enumXii`, `enumXiii` and `enumXiv` for `enumext` environment, `enumXv` for `keyans` environment, `enumXvi` for `keyanspic` environment, `enumXvii` for `enumext*` and `enumXviii` for the `keyans*` environments.

```

enumXi   430 \__enumext_define_counters:Nn \l__enumext_counter_i_tl { enumXi }
enumXv   431 \__enumext_define_counters:Nn \l__enumext_counter_ii_tl { enumXii }
enumXvi  432 \__enumext_define_counters:Nn \l__enumext_counter_iii_tl { enumXiii }
enumXvii 433 \__enumext_define_counters:Nn \l__enumext_counter_iv_tl { enumXiv }
enumXviii 434 \__enumext_define_counters:Nn \l__enumext_counter_v_tl { enumXv }
          435 \__enumext_define_counters:Nn \l__enumext_counter_vi_tl { enumXvi }
          436 \__enumext_define_counters:Nn \l__enumext_counter_vii_tl { enumXvii }
          437 \__enumext_define_counters:Nn \l__enumext_counter_viii_tl { enumXviii }

```

(End of definition for `enumXi` and others.)

11.11 Definition of labels

This part of the code is inspired by the `enumitem` package. The idea is to be able to access the counters using `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` to use them in the `label` key.

`__enumext_register_counter_style:Nn`

These *counters* will be used as default *labels* if the `label` key is not used for the different levels of the `enumext` environment and the `keyans` environment, so it is necessary to get a default value for `labelwidth` from these *labels* at the same time.

```

438 \cs_new_protected:Npn \__enumext_register_counter_style:Nn #1 #2
439 {
440   \tl_const:cn { c__enumext_widest_ \cs_to_str:N #1 _tl } {#2}
441   \tl_gput_right:Nn \g__enumext_counter_styles_tl {#1}
442 }
443 \__enumext_register_counter_style:Nn \arabic { 0 }
444 \__enumext_register_counter_style:Nn \Alph { M }
445 \__enumext_register_counter_style:Nn \alph { m }
446 \__enumext_register_counter_style:Nn \Roman { VIII }
447 \__enumext_register_counter_style:Nn \roman { viii }

```

(End of definition for `__enumext_register_counter_style:Nn`.)

`__enumext_label_width_by_box:Nn`

`__enumext_label_width_by_box:cv`

The function `__enumext_label_width_by_box:Nn` set the default `\labelwidth` using a box width if no `labelwidth` key is passed.

```

448 \cs_new_protected:Npn \__enumext_label_width_by_box:Nn #1 #2
449 {
450   \hbox_set:Nn \l__enumext_label_width_by_box {#2}
451   \dim_set:Nn #1 { \box_wd:N \l__enumext_label_width_by_box }
452 }
453 \cs_generate_variant:Nn \__enumext_label_width_by_box:Nn { cv }

```

(End of definition for `__enumext_label_width_by_box:Nn`.)

`__enumext_label_style:Nnn`

`__enumext_label_style:cvn`

The function `__enumext_label_style:Nnn` is used by the `label` key to creates the variables containing the *label style* and will allow to use `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` as arguments. It loops through the defined counter styles in `\g__enumext_counter_styles_tl` (`\arabic`, `\alph`, `\Alph`, `\roman`, and `\Roman`) for example, looking for `\roman*` and replacing that by `\roman{<counter>}`, and doing the same for the `\g__enumext_widest_label_tl` to keep both in sync.

```

454 \cs_new_protected:Npn \__enumext_label_style:Nnn #1 #2 #3
455 {
456   \tl_clear_new:N #1
457   \tl_put_right:Ne #1 { \tl_trim_spaces:n {#3} }
458   \tl_gset_eq:NN \g__enumext_widest_label_tl #1
459   \tl_map_inline:Nn \g__enumext_counter_styles_tl
460   {
461     \tl_replace_all:Nne #1 { ##1* } { \exp_not:N ##1 {#2} }
462     \tl_greplace_all:Nne \g__enumext_widest_label_tl { ##1* }
463     { \tl_use:c { c__enumext_widest_ \cs_to_str:N ##1 _tl } }
464   }
465   \__enumext_label_width_by_box:Nn \l__enumext_current_widest_dim
466   { \tl_use:N \g__enumext_widest_label_tl }
467   \tl_set_eq:cN { the #2 } #1
468 }
469 \cs_generate_variant:Nn \__enumext_label_style:Nnn { cvn }

```

(End of definition for `__enumext_label_style:Nnn`.)

11.12 Setting keys associated with label

font
labelsep
labelwidth
wrap-label
wrap-label*

Definition of keys `font`, `labelsep`, `labelwidth`, `wrap-label` and `wrap-label*` keys for `enumext` and `keyans` environments.

```

470 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
471 {
472   \keys_define:nn { enumext / #1 }
473   {
474     font      .tl_set:c   = { l__enumext_label_font_style_#2_tl },
475     font      .value_required:n = true,
476     labelsep  .dim_set:c  = { l__enumext_labelsep_#2_dim },
477     labelsep  .initial:n  = {0.3333em},
478     labelsep  .value_required:n = true,
479     labelwidth .dim_set:c  = { l__enumext_labelwidth_#2_dim },
480     labelwidth .value_required:n = true,

```

```

481     wrap-label .cs_set_protected:cp = { __enumext_wrapper_label_#2:n } ##1,
482     wrap-label .initial:n = {##1},
483     wrap-label .value_required:n = true,
484     wrap-label* .code:n = {
485         \bool_set_true:c { l__enumext_wrap_label_opt_#2_bool }
486         \keys_set:nn { enumext / #1 } { wrap-label = {##1} }
487     },
488     wrap-label* .value_required:n = true,
489 }
490 }
491 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for font and others.)

- In this point, the following are set `__enumext_wrapper_label_X:n` which will be used by `__enumext_make_label:` for the different levels of the `enumext` environment and is set to `__enumext_wrapper_label_v:n` which will be used by `__enumext_keyans_make_label:` for `keyans` and `keyanspic` environments.

`align` The `align` key is implemented differently for “starred” and “non starred” environments.

```

492 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
493 {
494     \keys_define:nn { enumext / #1 }
495     {
496         align .choice:,
497         align / left .code:n =
498             {
499                 \tl_clear:c { l__enumext_label_fill_left_#2_tl }
500                 \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
501             },
502         align / right .code:n =
503             {
504                 \tl_set:cn { l__enumext_label_fill_left_#2_tl } { \hfill }
505                 \tl_clear:c { l__enumext_label_fill_right_#2_tl }
506             },
507         align / center .code:n =
508             {
509                 \tl_set:cn { l__enumext_label_fill_left_#2_tl } { \hfill }
510                 \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
511             },
512         align / unknown .code:n =
513             \msg_error:nneee { enumext } { unknown-choice }
514             { align } { left, ~ right, ~ center } { \exp_not:n {##1} },
515         align .initial:n = left,
516         align .value_required:n = true,
517     }
518 }
519 \clist_map_inline:nn
520 {
521     {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {keyans}{v}
522 }
523 { \__enumext_tmp:nn #1 }

524 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
525 {
526     \keys_define:nn { enumext / #1 }
527     {
528         align .choice:,
529         align / left .code:n = \str_set:cn { l__enumext_align_label_#2_str } { l },
530         align / right .code:n = \str_set:cn { l__enumext_align_label_#2_str } { r },
531         align / center .code:n = \str_set:cn { l__enumext_align_label_#2_str } { c },
532         align / unknown .code:n =
533             \msg_error:nneee { enumext } { unknown-choice }
534             { align } { left, ~ right, ~ center } { \exp_not:n {##1} },
535         align .initial:n = left,
536         align .value_required:n = true,
537     }
538 }
539 \clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }

```

(End of definition for align.)

11.13 Setting label and ref keys

The implementation of the keys `label` and `ref` are part of the core of the package `enumext`, here the default values for $\langle label \rangle$, the value of the variables `__enumext_label_X_tl`, the default values for `\labelwidth` and the “*label and ref*” system.

11.13.1 Define and set label and ref keys for enumext environment

Here we set the default $\langle labels \rangle$ of the *four levels* of `enumext` environment, along with the default value for `labelwidth` key and `ref` key.

```

label
ref
\__enumext_label_i_tl
\__enumext_label_ii_tl
\__enumext_label_iii_tl
\__enumext_label_iv_tl
540 \cs_set_protected:Npn \__enumext_tmp:nnn #1 #2 #3
541 {
542   \keys_define:nn { enumext / #1 }
543   {
544     label .code:n = {
545       \__enumext_label_style:cvn { \__enumext_label_#2_tl }
546       { \__enumext_counter_#2_tl } {##1}
547       \dim_set_eq:cN { \__enumext_labelwidth_#2_dim }
548       \__enumext_current_widest_dim
549     },
550     label .initial:n = #3,
551     label .value_required:n = true,
552     ref .code:n = \__enumext_standar_ref:n {##1},
553     ref .value_required:n = true,
554   }
555 }
556 \__enumext_tmp:nnn { level-1 } { i } { \arabic*. }
557 \__enumext_tmp:nnn { level-2 } { ii } { (\alph*. ) }
558 \__enumext_tmp:nnn { level-3 } { iii } { \roman*. }
559 \__enumext_tmp:nnn { level-4 } { iv } { \Alph*. }
```

(End of definition for `label` and others.)

```

\__enumext_standar_ref:n
\__enumext_standar_ref:
```

The `__enumext_standar_ref:n` first we will pass the key argument to `__enumext_ref_key_arg_tl` and we will analyze its state, if it is not *empty* we will make a copy of the current counter in `__enumext_ref_the_count_tl` and we will execute the function `__enumext_regex_counter_style:` which will return the modified `__enumext_ref_key_arg_tl` and we make the value of `__enumext_ref_the_count_tl` the same as that `__enumext_the_counter_X_tl` which contains `\theenumX` and finally we set `__enumext_renew_the_count_X_tl` with the renewed command.

```

560 \cs_new_protected:Npn \__enumext_standar_ref:n #1
561 {
562   \tl_set:Nn \__enumext_ref_key_arg_tl {#1}
563   \tl_if_empty:NTF \__enumext_ref_key_arg_tl
564   {
565     \msg_error:nnn { enumext } { key-ref-empty } { enumext }
566   }
567   {
568     \tl_set_eq:Nc
569     \__enumext_ref_the_count_tl { \__enumext_counter_ \__enumext_level: _tl }
570     \__enumext_regex_counter_style:
571     \tl_set_eq:Nc
572     \__enumext_ref_the_count_tl { \__enumext_the_counter_ \__enumext_level: _tl }
573     \tl_put_right:ce { \__enumext_renew_the_count_ \__enumext_level: _tl }
574     {
575       \exp_not:N \renewcommand { \exp_not:V \__enumext_ref_the_count_tl }
576       { \exp_not:V \__enumext_ref_key_arg_tl }
577     }
578   }
579 }
```

Finally the function `__enumext_standar_ref:` will execute the modification for the reference system in the second argument of the environment definition `enumext`.

```

580 \cs_new_protected:Npn \__enumext_standar_ref:
581 {
582   \tl_if_empty:cF { \__enumext_renew_the_count_ \__enumext_level: _tl }
583   {
584     \tl_use:c { \__enumext_renew_the_count_ \__enumext_level: _tl }
585   }
586 }
```

(End of definition for `__enumext_standar_ref:n` and `__enumext_standar_ref:`.)

11.13.2 Define and set label and ref keys for enumext* and keyans* environments

label Here we set the default $\langle labels \rangle$ for `enumext*` and `keyans*` environments, along with the default value for `labelwidth` key and `ref` key.

```

\l__enumext_label_vii_tl 587 \cs_set_protected:Npn \l__enumext_tmp:nnn #1 #2 #3
\l__enumext_label_viii_tl 588 {
589   \keys_define:nn { enumext / #1 }
590   {
591     label .code:n = {
592       \__enumext_label_style:cvn { l__enumext_label_#2_tl }
593       { l__enumext_counter_#2_tl } {##1}
594       \dim_set_eq:cN { l__enumext_labelwidth_#2_dim }
595       \l__enumext_current_widest_dim
596     },
597     label .initial:n = #3,
598     label .value_required:n = true,
599     ref .code:n = \l__enumext_starred_ref:n {##1},
600     ref .value_required:n = true,
601   }
602 }
603 \l__enumext_tmp:nnn { enumext* } { vii } { \arabic*.}
604 \l__enumext_tmp:nnn { keyans* } { viii } { \Alph*.}

```

(End of definition for label and others.)

\l__enumext_starred_ref:n The implementation of `\l__enumext_starred_ref:n` is the same as that used for the environment `enumext`.

```

605 \cs_new_protected:Npn \l__enumext_starred_ref:n #1
606 {
607   \tl_set:Nn \l__enumext_ref_key_arg_tl {#1}
608   \int_compare:nNnT { \l__enumext_level_h_int } = { 1 }
609   {
610     \tl_if_empty:NTF \l__enumext_ref_key_arg_tl
611     {
612       \msg_error:nnn { enumext } { key-ref-empty } { enumext* }
613     }
614     {
615       \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_counter_vii_tl
616       \__enumext_regex_counter_style:
617       \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_the_counter_vii_tl
618       \tl_put_right:Ne \l__enumext_renew_the_count_vii_tl
619       {
620         \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_the_count_tl }
621         { \exp_not:V \l__enumext_ref_key_arg_tl }
622       }
623     }
624   }
625   \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
626   {
627     \tl_if_empty:NTF \l__enumext_ref_key_arg_tl
628     {
629       \msg_error:nnn { enumext } { key-ref-empty } { keyans* }
630     }
631     {
632       \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_counter_viii_tl
633       \__enumext_regex_counter_style:
634       \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_the_counter_viii_tl
635       \tl_put_right:Ne \l__enumext_renew_the_count_viii_tl
636       {
637         \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_the_count_tl }
638         { \exp_not:V \l__enumext_ref_key_arg_tl }
639       }
640     }
641   }
642 }

```

Finally the function `\l__enumext_starred_ref:` will execute the modification for the reference system in the second argument of the `enumext*` and `keyans*` environment definition.

```

643 \cs_new_protected:Nn \l__enumext_starred_ref:
644 {
645   \int_compare:nNnT { \l__enumext_level_h_int } = { 1 }
646   {

```

```

647         \tl_if_empty:NF \l__enumext_renew_the_count_vii_tl
648         {
649             \tl_use:N \l__enumext_renew_the_count_vii_tl
650         }
651     }
652     \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
653     {
654         \tl_if_empty:NF \l__enumext_renew_the_count_viii_tl
655         {
656             \tl_use:N \l__enumext_renew_the_count_viii_tl
657         }
658     }
659 }

```

(End of definition for `__enumext_starred_ref:n` and `__enumext_starred_ref:.`)

11.13.3 Define and set label and ref keys for keyans and keyanspic environments

Here we set the default *label* for `keyans` and `keyanspic` environment, along with the default value for `labelwidth` and `ref` key. The `keyanspic` environment use the same *label* as the `keyans` environment.

```

\__enumext_label_v_tl
\__enumext_label_vi_tl
660 \keys_define:nn { enumext / keyans }
661 {
662     label .code:n      = {
663         \__enumext_label_style:cvn { \__enumext_label_v_tl }
664         { \__enumext_counter_v_tl } {#1}
665         \dim_set_eq:cN { \__enumext_labelwidth_v_dim }
666         \__enumext_current_widest_dim
667         \__enumext_label_style:cvn { \__enumext_label_vi_tl }
668         { \__enumext_counter_vi_tl } {#1}
669         \dim_set_eq:cN { \__enumext_labelwidth_v_dim }
670         \__enumext_current_widest_dim
671     },
672     label .initial:n = \Alph*,
673     label .value_required:n = true,
674     ref .code:n      = \__enumext_keyans_ref:n {#1},
675     ref .value_required:n = true,
676 }

```

(End of definition for `label` and others.)

The implementation of `__enumext_keyans_ref:n` is the same as that used for the environment `enumext`.

```

677 \cs_new_protected:Npn \__enumext_keyans_ref:n #1
678 {
679     \tl_set:Nn \l__enumext_ref_key_arg_tl {#1}
680     \tl_if_empty:NTF \l__enumext_ref_key_arg_tl
681     {
682         \msg_error:nnn { enumext } { key-ref-empty } { keyans }
683     }
684     {
685         \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_counter_v_tl
686         \__enumext_regex_counter_style:
687         \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_the_counter_v_tl
688         \tl_put_right:Ne \l__enumext_renew_the_count_v_tl
689         {
690             \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_the_count_tl }
691             { \exp_not:V \l__enumext_ref_key_arg_tl }
692         }
693     }
694 }

```

Finally the function `__enumext_keyans_ref:` will execute the modification for the reference system in the second argument of the `keyans*` environment definition.

```

695 \cs_new_protected:Nn \__enumext_keyans_ref:
696 {
697     \tl_if_empty:NF \l__enumext_renew_the_count_v_tl
698     {
699         \tl_use:N \l__enumext_renew_the_count_v_tl
700     }
701 }

```

(End of definition for `__enumext_keyans_ref:n` and `__enumext_keyans_ref:.`)

11.14 Setting start and widest keys

```
\__enumext_start_from:NNn
\__enumext_start_from:ccn
```

The function `__enumext_start_from:NNn` used by the `start` key take three arguments:

```
#1: \l__enumext_label_X_tl
#2: \l__enumext_start_X_int
#3: <integer or string>
```

The first argument of this function are the “counter style” set by `label` key, the second argument is returned by the function, the third argument can be an *<integer>* or *<string>* of the form `\Alph`, `\alph`, `\Roman` or `\roman`. This effectively allows `start=A` or `start=1` to be used.

```
702 \cs_new_protected:Npn \__enumext_start_from:NNn #1 #2 #3
703 {
704   \__enumext_if_is_int:nTF { #3 }
705   {
706     \int_set:Nn #2 {#3}
707   }
708   {
709     \regex_match:nVT { \c{Alph} | \c{alph} } {#1}
710     { \int_set:Nn #2 { \int_from_alph:n {#3} } }
711     \regex_match:nVT { \c{Roman} | \c{roman} } {#1}
712     { \int_set:Nn #2 { \int_from_roman:n {#3} } }
713   }
714 }
715 \cs_generate_variant:Nn \__enumext_start_from:NNn { ccn }
```

(End of definition for `__enumext_start_from:NNn`.)

```
\__enumext_widest_from:nNNn
\__enumext_widest_from:nccn
```

The function `__enumext_widest_from:nNNn` used by the `widest` key take four arguments:

```
#1: The counter associated with the environment level
#2: \l__enumext_label_X_tl
#3: \l__enumext_labelwidth_X_dim
#4: <integer or string>
```

The second and third arguments of this function are the values set by `label` and `labelwidth` keys, the four argument can be an *<integer>* or *<string>* of the form `\Alph`, `\alph`, `\Roman` or `\roman`. The value of the four argument is set temporarily for the identified counter in this point (level), then the value is expanded into a “box” and the “width” of the “box” is returned.

```
716 \cs_new_protected:Npn \__enumext_widest_from:nNNn #1 #2 #3 #4
717 {
718   \__enumext_if_is_int:nTF {#4}
719   {
720     \setcounter{enumX#1} { #4 }
721   }
722   {
723     \regex_match:nVT { \c{Alph} | \c{alph} } {#2}
724     { \setcounter{enumX#1} { \int_from_alph:n {#4} } }
725     \regex_match:nVT { \c{Roman} | \c{roman} } {#2}
726     { \setcounter{enumX#1} { \int_from_roman:n {#4} } }
727   }
728   \__enumext_label_width_by_box:cv
729   { \l__enumext_labelwidth_#1_dim } { \l__enumext_label_#1_tl }
730 }
731 \cs_generate_variant:Nn \__enumext_widest_from:nNNn { nccn }
```

(End of definition for `__enumext_widest_from:nNNn`.)

```
start
widest
\l__enumext_start_X_int
```

Now define and set `start` and `widest` keys for `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```
732 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
733 {
734   \keys_define:nn { enumext / #1 }
735   {
736     start .code:n = {
737       \__enumext_start_from:ccn
738       { \l__enumext_label_#2_tl }
739       { \l__enumext_start_#2_int } {##1}
740     },
741     start .initial:n = 1,
742     widest .code:n = {
743       \__enumext_widest_from:nccn {#2}
744       { \l__enumext_label_#2_tl }
745       { \l__enumext_labelwidth_#2_dim } {##1}
746     },

```

```

747         widest .value_required:n = true,
748         start .value_required:n = true,
749     }
750 }
751 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `start`, `widest`, and `__enumext_start_X_int`.)

11.15 Setting keys for vertical spaces

Define and set `topsep`, `partopsep`, `parsep`, `itemsep`, `noitemsep` and `nosep` keys for `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```

topsep
partopsep
parsep
noitemsep
nosep
752 \cs_set_protected:Npn \__enumext_tmp:nnnnnn #1 #2 #3 #4 #5 #6
753 {
754     \keys_define:nn { enumext / #1 }
755     {
756         topsep .skip_set:c = { l__enumext_topsep_#2_skip },
757         topsep .initial:n = {#3},
758         topsep .value_required:n = true,
759         partopsep .skip_set:c = { l__enumext_partopsep_#2_skip },
760         partopsep .initial:n = {#4},
761         partopsep .value_required:n = true,
762         parsep .skip_set:c = { l__enumext_parsep_#2_skip },
763         parsep .initial:n = {#5},
764         parsep .value_required:n = true,
765         itemsep .skip_set:c = { l__enumext_itemsep_#2_skip },
766         itemsep .initial:n = {#6},
767         itemsep .value_required:n = true,
768         noitemsep .meta:n = { itemsep = 0pt, parsep = 0pt },
769         noitemsep .value_forbidden:n = true,
770         nosep .meta:n = {
771             itemsep = 0pt, parsep = 0pt,
772             topsep = 0pt, partopsep = 0pt,
773         },
774         nosep .value_forbidden:n = true,
775     }
776 }

```

Now we set the values based on standard `article` class in `10pt`.

```

777 \__enumext_tmp:nnnnnn { level-1 } { i } { 8.0pt plus 2.0pt minus 4.0pt }
778 { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
779 { 4.0pt plus 2.0pt minus 1.0pt }
780 \__enumext_tmp:nnnnnn { level-2 } { ii } { 4.0pt plus 2.0pt minus 1.0pt }
781 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
782 { 2.0pt plus 1.0pt minus 1.0pt }
783 \__enumext_tmp:nnnnnn { level-3 } { iii } { 2.0pt plus 1.0pt minus 1.0pt }
784 { 1.0pt minus 1.0pt } { 0pt } { 2.0pt plus 1.0pt minus 1.0pt }
785 \__enumext_tmp:nnnnnn { level-4 } { iv } { 2.0pt plus 1.0pt minus 1.0pt }
786 { 1.0pt minus 1.0pt } { 0pt } { 2.0pt plus 1.0pt minus 1.0pt }
787 \__enumext_tmp:nnnnnn { keyans } { v } { 4.0pt plus 2.0pt minus 1.0pt }
788 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
789 { 2.0pt plus 1.0pt minus 1.0pt }
790 \__enumext_tmp:nnnnnn { enumext* } { vii } { 8.0pt plus 2.0pt minus 4.0pt }
791 { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
792 { 4.0pt plus 2.0pt minus 1.0pt }
793 \__enumext_tmp:nnnnnn { keyans* } { viii } { 4.0pt plus 2.0pt minus 1.0pt }
794 { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
795 { 2.0pt plus 1.0pt minus 1.0pt }

```

(End of definition for `topsep` and others.)

11.16 Setting base-fix key

When nesting starting right after `\item` (without material between them) there is a problem with the alignment of the baseline between the two environments. One way to get around this problem is to place `\mode_leave_vertical:` and then apply `\space{-\baselineskip}` and set `topsep=0pt` for the “first level” of the nested `enumext` or `enumext*` environments.

```

base-fix
\__enumext_nested_base_line_fix:
796 \cs_set_protected:Npn \__enumext_tmp:n #1
797 {
798     \keys_define:nn { enumext / #1 }

```

```

799     {
800         base-fix .bool_set:N = \l__enumext_base_line_fix_bool,
801         base-fix .initial:n = false,
802         base-fix .value_forbidden:n = true,
803     }
804 }
805 \clist_map_inline:nn { level-1, enumext* } { \__enumext_tmp:n {#1} }

```

The function `__enumext_nested_base_line_fix:` will be in charge of applying the baseline correction and adjusting the *⟨keys⟩*. This function is passed to the function `__enumext_parse_keys:n` in the `enumext` environment definition (§11.38) and to the function `__enumext_parse_keys_vii:n` in the `enumext*` environment definition (§11.42)

```

806 \cs_new_protected:Nn \__enumext_nested_base_line_fix:
807 {
808     \bool_lazy_and:nnT
809     { \bool_if_p:N \l__enumext_standar_first_bool }
810     { \bool_if_p:N \l__enumext_base_line_fix_bool }
811     {
812         \mode_leave_vertical:
813         \vspace { -\baselineskip }
814         \keys_set:nn { enumext / level-1 }
815         {
816             topsep = 0pt, above = 0pt, above* = 0pt,
817         }
818     }
819     \bool_lazy_and:nnT
820     { \bool_if_p:N \l__enumext_starred_first_bool }
821     { \bool_if_p:N \l__enumext_base_line_fix_bool }
822     {
823         \mode_leave_vertical:
824         \vspace { -\baselineskip }
825         \keys_set:nn { enumext / enumext* }
826         {
827             topsep = 0pt, above = 0pt, above* = 0pt,
828         }
829     }
830     \bool_set_false:N \l__enumext_base_line_fix_bool
831 }

```

• This key is enabled by default in the command `\printkeyans` (§11.45).

(End of definition for `base-fix` and `__enumext_nested_base_line_fix:`.)

11.17 Setting keys for horizontal spaces

Define and set `itemindent`, `rightmargin`, `listparindent`, `list-offset` and `list-indent` keys for `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```

832 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
833 {
834     \keys_define:nn { enumext / #1 }
835     {
836         itemindent .dim_set:c = { \l__enumext_fake_item_indent_#2_dim },
837         itemindent .value_required:n = true,
838         rightmargin .dim_set:c = { \l__enumext_rightmargin_#2_dim },
839         rightmargin .value_required:n = true,
840         listparindent .dim_set:c = { \l__enumext_listparindent_#2_dim },
841         listparindent .value_required:n = true,
842         list-offset .dim_set:c = { \l__enumext_listoffset_#2_dim },
843         list-offset .value_required:n = true,
844         list-indent .code:n =
845             \bool_set_true:c { \l__enumext_leftmargin_tmp_#2_bool }
846             \dim_set:cn { \l__enumext_leftmargin_tmp_#2_dim } {##1},
847         list-indent .value_required:n = true,
848     }
849 }
850 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `itemindent` and others.)

For `enumext*` and `keyans*` environments the situation is a bit different, the `list-indent` key behaves like the `list-offset` key.

```

851 \cs_set_protected:Npn \__enumext_tmp:n #1
852 {

```

```

853 \keys_define:nn { enumext / #1 } { list-indent .initial:n = 0pt, }
854 }
855 \clist_map_inline:nn { enumext*, keyans* } { \__enumext_tmp:n {#1} }

```

11.17.1 Functions for setting the fake itemindent

The `itemindent` key does not set the value of `\itemindent`, it only sets the value of the *horizontal space* applied using `\skip_horizontal:N`. We will store this value in the variable and only apply it when it is greater than `0pt`. Here I will need to place `\mode_leave_vertical:` and the plain TeX macro `\ignorespaces` to avoid unwanted extra space when using the `itemindent` key.

```

856 \cs_set_protected:Nn \__enumext_fake_item:
857 {
858   \dim_compare:nNnT
859     { \dim_use:c { \__enumext_fake_item_indent_ \__enumext_level: _dim } }
860     >
861     { \c_zero_dim }
862     {
863       \tl_set:ce { \__enumext_fake_item_indent_ \__enumext_level: _tl }
864       {
865         \exp_not:N \mode_leave_vertical:
866         \exp_not:n { \skip_horizontal:n
867           { \dim_use:c { \__enumext_fake_item_indent_ \__enumext_level: _dim } }
868         \ignorespaces
869       }
870     }
871   }
872 \cs_set_protected:Nn \__enumext_keyans_fake_item:
873 {
874   \dim_compare:nNnT
875     { \l__enumext_fake_item_indent_v_dim } > { \c_zero_dim }
876     {
877       \tl_set:Ne \l__enumext_fake_item_indent_v_tl
878       {
879         \exp_not:N \mode_leave_vertical:
880         \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_v_dim
881       }
882     }
883   }
884 \cs_set_protected:Nn \__enumext_fake_item_vii:
885 {
886   \dim_compare:nNnT
887     { \l__enumext_fake_item_indent_vii_dim } > { \c_zero_dim }
888     {
889       \tl_set:Ne \l__enumext_fake_item_indent_vii_tl
890       {
891         \exp_not:N \mode_leave_vertical:
892         \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_vii_dim
893       }
894     }
895   }
896 \cs_set_protected:Nn \__enumext_fake_item_viii:
897 {
898   \dim_compare:nNnT
899     { \l__enumext_fake_item_indent_viii_dim } > { \c_zero_dim }
900     {
901       \tl_set:Ne \l__enumext_fake_item_indent_viii_tl
902       {
903         \exp_not:N \mode_leave_vertical:
904         \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_viii_dim
905       }
906     }
907   }

```

(End of definition for `__enumext_fake_item:` and others.)

11.18 Setting show-length key

Define and set `show-length` key for `enumext`, `enumext*`, `keyans` and `keyans*` environments. The function sets the boolean variable `\l__enumext_show_length_X_bool` used in the definition of all environments to “true” and calls the function `__enumext_show_length:nnn` which prints all the values of the “vertical” and “horizontal” parameters calculated and used.

```

908 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2

```



```

909   {
910     \keys_define:nn { enumext / #1 }
911     {
912       show-length .bool_set:c = { l__enumext_show_length_#2_bool },
913       show-length .initial:n = false,
914     }
915   }
916   \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `show-length`.)

11.19 Setting before, after and first keys

Define and set `before`, `before*`, `after` and `first` keys for `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```

917 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
918 {
919   \keys_define:nn { enumext / #1 }
920   {
921     before .tl_set:c = { l__enumext_before_no_starred_key_#2_tl },
922     before .value_required:n = true,
923     before* .tl_set:c = { l__enumext_before_starred_key_#2_tl },
924     before* .value_required:n = true,
925     after .tl_set:c = { l__enumext_after_stop_list_#2_tl },
926     after .value_required:n = true,
927     first .tl_set:c = { l__enumext_after_list_args_#2_tl },
928     first .value_required:n = true,
929   }
930 }
931 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for `before` and others.)

11.19.1 Functions for before, after and first keys in enumext

The function `__enumext_before_args_exec:` executes the `{⟨code⟩}` set by the `before*` key “before” the `enumext` environment is started. The `{⟨code⟩}` is executed “without” knowing any definition of the *second argument* of the list.

```

932 \cs_new_protected:Nn \__enumext_before_args_exec:
933 {
934   \tl_use:c { l__enumext_before_starred_key_ \__enumext_level: _tl }
935 }

```

The function `__enumext_before_keys_exec:` executes the `{⟨code⟩}` set by the `before` key “before” the `enumext` environment is started in *second argument* of the list. The `{⟨code⟩}` is executed “knowing” all definition and values provides by `⟨keys⟩`.

```

936 \cs_new_protected:Nn \__enumext_before_keys_exec:
937 {
938   \tl_use:c { l__enumext_before_no_starred_key_ \__enumext_level: _tl }
939 }

```

The function `__enumext_after_stop_list:` executes the `{⟨code⟩}` set by the `after` key “after” the `enumext` environment has finished.

```

940 \cs_new_protected:Nn \__enumext_after_stop_list:
941 {
942   \tl_use:c { l__enumext_after_stop_list_ \__enumext_level: _tl }
943 }

```

The function `__enumext_after_args_exec:` executes the `{⟨code⟩}` set by the `first` key after the end of the *second argument* of the list defining the `enumext` environment, just before the first occurrence of `\item`.

```

944 \cs_new_protected:Nn \__enumext_after_args_exec:
945 {
946   \tl_use:c { l__enumext_after_list_args_ \__enumext_level: _tl }
947 }

```

(End of definition for `__enumext_before_args_exec:` and others.)

11.19.2 Functions for before, after and first keys in keyans

```

__enumext_before_args_exec_v:
__enumext_before_keys_exec_v:
__enumext_after_stop_list_v:
__enumext_after_args_exec_v:

```

The function `__enumext_before_args_exec_v`: executes the `{⟨code⟩}` set by the `before*` key “before” the `keyans` environment is started. The `{⟨code⟩}` is executed “without” knowing any definition of the `{⟨arg two⟩}` of the list.

```

948 \cs_new_protected:Nn __enumext_before_args_exec_v:
949 {
950     \tl_use:N \l__enumext_before_starred_key_v_tl
951 }

```

The function `__enumext_before_keys_exec_v`: executes the `{⟨code⟩}` set by the `before` key “before” the `keyans` environment is started in `{⟨arg two⟩}` of the list. The `{⟨code⟩}` is executed “knowing” all definition and values provides by `⟨keys⟩`.

```

952 \cs_new_protected:Nn __enumext_before_keys_exec_v:
953 {
954     \tl_use:N \l__enumext_before_no_starred_key_v_tl
955 }

```

The function `__enumext_after_stop_list_v`: executes the `{⟨code⟩}` set by the `after` key “after” the `keyans` environment has finished.

```

956 \cs_new_protected:Nn __enumext_after_stop_list_v:
957 {
958     \tl_use:N \l__enumext_after_stop_list_v_tl
959 }

```

The function `__enumext_after_args_exec_v`: executes the `{⟨code⟩}` set by the `first` key after the end of `{⟨arg two⟩}` of the list defining the `keyans` environment, just before the first occurrence of `\item`.

```

960 \cs_new_protected:Nn __enumext_after_args_exec_v:
961 {
962     \tl_use:N \l__enumext_after_list_args_v_tl
963 }

```

(End of definition for `__enumext_before_args_exec_v`: and others.)

11.19.3 Functions for before, after and first keys in enumext* and keyans*

```

__enumext_before_args_exec_vii:
__enumext_before_keys_exec_vii:
__enumext_after_stop_list_vii:
__enumext_after_args_exec_vii:

```

The function `__enumext_before_args_exec_v`: executes the `{⟨code⟩}` set by the `before*` key “before” the `keyans` environment is started. The `{⟨code⟩}` is executed “without” knowing any definition of the `{⟨arg two⟩}` of the list.

```

964 \cs_new_protected:Nn __enumext_before_args_exec_vii:
965 {
966     \tl_use:N \l__enumext_before_starred_key_vii_tl
967 }
968 \cs_new_protected:Nn __enumext_before_args_exec_viii:
969 {
970     \tl_use:N \l__enumext_before_starred_key_viii_tl
971 }

```

The functions `__enumext_before_keys_exec_vii:` and `__enumext_before_keys_exec_viii:` executes the `{⟨code⟩}` set by the `before` key “before” in `enumext*` and `keyans*` environments is started in `{⟨arg two⟩}` of the list. The `{⟨code⟩}` is executed “knowing” all definition and values provides by `⟨keys⟩`.

```

972 \cs_new_protected:Nn __enumext_before_keys_exec_vii:
973 {
974     \tl_use:N \l__enumext_before_no_starred_key_vii_tl
975 }
976 \cs_new_protected:Nn __enumext_before_keys_exec_viii:
977 {
978     \tl_use:N \l__enumext_before_no_starred_key_viii_tl
979 }

```

The function `__enumext_after_stop_list:` executes the `{⟨code⟩}` set by the `after` key “after” the `keyans` environment has finished.

```

980 \cs_new_protected:Nn __enumext_after_stop_list_vii:
981 {
982     \tl_use:N \l__enumext_after_stop_list_vii_tl
983 }
984 \cs_new_protected:Nn __enumext_after_stop_list_viii:
985 {
986     \tl_use:N \l__enumext_after_stop_list_viii_tl
987 }

```

The function `__enumext_after_args_exec_v:` executes the `{\code}` set by the `first` key after the end of `{\arg two}` of the list defining the `keyans` environment, just before the first occurrence of `\item`.

```

988 \cs_new_protected:Nn \__enumext_after_args_exec_vii:
989 {
990   \tl_use:N \l__enumext_after_list_args_vii_tl
991 }
992 \cs_new_protected:Nn \__enumext_after_args_exec_viii:
993 {
994   \tl_use:N \l__enumext_after_list_args_viii_tl
995 }

```

(End of definition for `__enumext_before_args_exec_vii:` and others.)

11.20 Setting keys for multicols and minipage

The default value of the `columns-sep` key is handled by the state of the boolean variable `\l__enumext_columns_sep_X_bool` which is handled in the internal definition of the `enumext` and `keyans` environments. Define and set `mini-env`, `mini-sep`, `columns-sep` and `columns` keys for `enumext*`, `keyans` and `keyans*` environments.

```

996 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
997 {
998   \keys_define:nn { enumext / #1 }
999   {
1000     mini-env .dim_set:c = { l__enumext_minipage_right_#2_dim },
1001     mini-env .value_required:n = true,
1002     mini-sep .dim_set:c = { l__enumext_minipage_hsep_#2_dim },
1003     mini-sep .initial:n = 0.3333em,
1004     mini-sep .value_required:n = true,
1005     columns-sep .dim_set:c = { l__enumext_columns_sep_#2_dim },
1006     columns-sep .value_required:n = true,
1007     columns .int_set:c = { l__enumext_columns_#2_int },
1008     columns .initial:n = 1,
1009     columns .value_required:n = true,
1010   }
1011 }
1012 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

For `enumext*` and `keyans*` environments the situation is a bit different, the command `\miniright` is not available, so we will add the keys `mini-right` and `mini-right*` to implement support for `minipage` environment.

```

1013 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
1014 {
1015   \keys_define:nn { enumext / #1 }
1016   {
1017     mini-right .tl_gset:c = { g__enumext_miniright_code_#2_tl },
1018     mini-right .value_required:n = true,
1019     mini-right* .code:n = {
1020       \bool_gset_true:c { g__enumext_minipage_center_#2_bool }
1021       \keys_set:nn { enumext / #1 } { mini-right = {##1} }
1022     },
1023     mini-right* .value_required:n = true,
1024   }
1025 }
1026 \clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }

```

(End of definition for `mini-env` and others.)

11.21 Adjustment of vertical spaces for multicols

When nesting a “list environment” inside the `multicols` environment, the values of the “vertical spaces” are lost, basically the `multicols` environment takes control over them. Graphically it can be seen like in the figure 7.




Figure 7: Representation of the vertical space in `multicols` for a nested level.

To keep the desired spaces *above* and *below* in the “list environment” (`\topsep` + `[\partopsep]`) it is necessary to “adjust” the spaces added by the `multicols` environment. The most appropriate option in this case is to use a “context sensitive” vertical space with `\addvspace`.

I should make it clear that the implementation here is a “bit questionable”. At first glance doing `\multicolsep=\topsep` seemed right, but the results were not always as expected. An almost *imperceptible* detail is that in some cases the `\itemsep` values are “stretched”, possibly due to the use of `\raggedcolumns` and this affects the lower space when closing the environment, which is “smaller” than expected. My attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

11.21.1 Adjustment of vertical spaces for multicols in enumext

`__enumext_multi_set_vskip:` The function `__enumext_multi_set_vskip:` will take care of determining the “adjusted spaces” that we will apply “above” and “below” the `multicols` environment in `enumext`.

We will set the default values taking into account that \TeX is in *horizontal mode*, then we will make the settings for the *vertical mode* in which `\partopsep` comes into play.

Set the values of `__enumext_multicols_above_X_skip` and `__enumext_multicols_below_X_skip` equal to the value of `\topsep` in the *current level*.

```

1027 \cs_new_protected:Nn \__enumext_multi_set_vskip:
1028 {
1029   \skip_set:cn { \__enumext_multicols_above_ \__enumext_level: } _skip {
1030     {
1031       \skip_use:c { \__enumext_topsep_ \__enumext_level: } _skip {
1032     }
1033   \skip_set:cn { \__enumext_multicols_below_ \__enumext_level: } _skip {
1034     {
1035       \skip_use:c { \__enumext_topsep_ \__enumext_level: } _skip {
1036     }
1037   \__enumext_add_pre_parsep:
1038 }
```

(End of definition for `__enumext_multi_set_vskip:`)

`__enumext_add_pre_parsep:` The function `__enumext_add_pre_parsep:` “adjusted” the value of `__enumext_multicols_above_X_skip` detecting the value of `\parsep` from the previous level. This is necessary since `\parsep` from the previous level affects the *vertical spaces*.

```

1039 \cs_new_protected:Nn \__enumext_add_pre_parsep:
1040 {
1041   \int_case:nn { \__enumext_level_int }
1042   {
1043     { 2 }{
1044       \skip_if_eq:nnF { \__enumext_parsep_i_skip } { \c_zero_skip }
1045       {
1046         \skip_add:Nn \__enumext_multicols_above_ii_skip { \__enumext_parsep_i_skip }
1047       }
1048     }
1049     { 3 }{
1050       \skip_if_eq:nnF { \__enumext_parsep_ii_skip } { \c_zero_skip }
1051       {
1052         \skip_add:Nn \__enumext_multicols_above_iii_skip { \__enumext_parsep_ii_skip }
1053       }
1054     }
1055     { 4 }{
1056       \skip_if_eq:nnF { \__enumext_parsep_iii_skip } { \c_zero_skip }
1057       {
1058         \skip_add:Nn \__enumext_multicols_above_iv_skip { \__enumext_parsep_iii_skip }
1059       }
1060     }
1061   }
1062 }
```

(End of definition for `__enumext_add_pre_parsep:`)

`__enumext_multi_addvspace:` The function `__enumext_multi_addvspace:` will apply the spaces set using `\addvspace` “above” the `multicols` environment in `enumext`, taking into account whether \TeX is in *horizontal mode* or *vertical mode*.

```

1063 \cs_new_protected:Nn \__enumext_multi_addvspace:
1064 {
1065   \__enumext_multi_set_vskip:
1066   \mode_if_vertical:T
1067   {
```

```

1068     \skip_add:cn { l__enumext_multicols_above_ \__enumext_level: _skip }
1069     {
1070         \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
1071     }
1072     \skip_add:cn { l__enumext_multicols_below_ \__enumext_level: _skip }
1073     {
1074         \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
1075     }
1076 }
1077 \par\nopagebreak
1078 \addvspace{ \skip_use:c { l__enumext_multicols_above_ \__enumext_level: _skip } }
1079 }

```

(End of definition for `__enumext_multi_addvspace:`)

11.21.2 Adjustment of vertical spaces for multicols in keyans

`__enumext_keyans_multi_set_vskip:`
`__enumext_keyans_multi_addvspace:`

The function `__enumext_keyans_multi_set_vskip:` will take care of determining the “adjusted spaces” that we will apply “above” and “below” the `multicols` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

```

1080 \cs_new_protected:Nn \__enumext_keyans_multi_set_vskip:
1081 {
1082     \skip_set:Nn \l__enumext_multicols_above_v_skip
1083     {
1084         \l__enumext_topsep_v_skip
1085     }
1086     \skip_set:Nn \l__enumext_multicols_below_v_skip
1087     {
1088         \l__enumext_topsep_v_skip
1089     }
1090 }
1091 \cs_new_protected:Nn \__enumext_keyans_multi_addvspace:
1092 {
1093     \__enumext_keyans_multi_set_vskip:
1094     \mode_if_vertical:T
1095     {
1096         \skip_add:Nn \l__enumext_multicols_above_v_skip
1097         {
1098             \skip_use:N \l__enumext_partopsep_v_skip
1099         }
1100         \skip_add:Nn \l__enumext_multicols_below_v_skip
1101         {
1102             \skip_use:N \l__enumext_partopsep_v_skip
1103         }
1104     }
1105     \par\nopagebreak
1106     \addvspace{ \l__enumext_multicols_above_v_skip }
1107 }

```

(End of definition for `__enumext_keyans_multi_set_vskip:` and `__enumext_keyans_multi_addvspace:`)

11.22 Adjustment of vertical spaces for minipage

When nesting a “list environment” within the `minipage` environment, the values of the “vertical spaces” are lost. Graphically it can be seen like in the figure 8.




Figure 8: Representation of the `minipage` spacing adjustment for a nested level.

Since we want to keep the “left” and “right” environments “aligned on top”, preserving the `\baselineskip` and keep the desired “spaces” (`\topsep` + `[\partopsep]`) it is necessary to “adjust” the “vertical spaces” for `minipage` environments.

Here there are several complications that we must circumvent, the `minipage` environment eliminates the “top” spaces, the `multicols` environment can be nested in the `minipage` environment, the “top” and “bottom” spaces are affected when `topsep=0pt` and to this is added the `\partopsep` parameter that comes into action according to whether \TeX is in *(horizontal mode)* or *(vertical mode)*. Depending on these cases, small adjustments must be made using `\vspace` and `\addvspace` to obtain the “desired vertical spacing”.

- Again I must make clear that the implementation here is a “*bit questionable*”, but hunting the spaces (glue) produced by the `minipage` environment is quite complicated, even more if `multicols` it is nested. The setting of the values was more “*trial and error*” (aprox to `\strutbox`), using the help of the `lua-visual-debug`[14] package, again my attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

11.22.1 Adjustment of vertical spaces for minipage in enumext

`__enumext_mini_set_vskip:` The function `__enumext_mini_set_vskip:` will take care of determining the “*adjust*” spaces that we will apply “*above*” and “*below*” the `__enumext_mini_env*` environment in `enumext`.

We will set the default values taking into account that \TeX is in (*horizontal mode*), then we will make the settings for the (*vertical mode*) in which `\partopsep` comes into play.

First determine if the `multicols` environment is active by comparing the value of the `\l__enumext_columns_X_int` variable handled by the `columns` key, according to this comparison we set the adjusted values for `\l__enumext_minipage_left_skip`, `\l__enumext_minipage_right_skip` and `\l__enumext_minipage_after_skip`.

```
1108 \cs_new_protected:Nn \__enumext_mini_set_vskip:
1109 {
1110     \int_compare:nNnTF
1111     { \int_use:c { \l__enumext_columns_ \__enumext_level: _int } } > { 1 }
1112     {
```

If `multicols` environment is nested in `__enumext_mini_env*` environment, we will apply a correction factor to the *vertical spaces* taking into account the value of `\topsep` of the current level and the value of `\parsep` of the previous level, if these are zero we will use `\strutbox` as the basis for the calculations.

```
1113     \skip_if_eq:nnTF
1114     { \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip } } { \c_zero_skip }
1115     {
1116         \skip_set:Nn \l__enumext_minipage_left_skip
1117         {
1118             -0.150\box_dp:N \strutbox
1119         }
1120         \skip_set:Nn \l__enumext_minipage_right_skip
1121         {
1122             0.695\box_dp:N \strutbox
1123         }
1124         \skip_set:Nn \l__enumext_minipage_after_skip
1125         {
1126             \box_dp:N \strutbox
1127         }
1128         \__enumext_zero_parsep:
1129     }
1130     {
1131         \skip_set:Nn \l__enumext_minipage_left_skip
1132         {
1133             \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip }
1134         }
1135         \skip_set:Nn \l__enumext_minipage_right_skip
1136         {
1137             0.695\box_dp:N \strutbox
1138         }
1139         \skip_set:Nn \l__enumext_minipage_after_skip
1140         {
1141             1.85\box_dp:N \strutbox
1142             + \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip }
1143         }
1144     }
1145 }
1146 {
```

If only `enumext` environment is nested in `__enumext_mini_env*` environment, we will apply a correction factor to the *vertical spaces* taking into account the value of `\topsep`, if this is zero we will use `\strutbox` as the basis for the calculations.

```
1147     \skip_if_eq:nnTF
1148     { \skip_use:c { \l__enumext_topsep_ \__enumext_level: _skip } } { \c_zero_skip }
1149     {
1150         \skip_set:Nn \l__enumext_minipage_left_skip
1151         {
1152             0.5\box_dp:N \strutbox
1153             - \skip_use:c { \l__enumext_partopsep_ \__enumext_level: _skip }
1154         }
1155         \skip_set:Nn \l__enumext_minipage_right_skip
```



```

1156         {
1157             \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1158         }
1159         \skip_set:Nn \l__enumext_minipage_after_skip
1160         {
1161             1.6\box_dp:N \strutbox
1162         }
1163     }
1164     {
1165         \skip_set:Nn \l__enumext_minipage_left_skip
1166         {
1167             0.5875\box_dp:N \strutbox
1168             - \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1169         }
1170         \skip_set:Nn \l__enumext_minipage_right_skip
1171         {
1172             + \skip_use:c { \l__enumext_topsep_ \l__enumext_level: _skip }
1173             + \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1174         }
1175         \skip_set:Nn \l__enumext_minipage_after_skip
1176         {
1177             0.325\box_dp:N \strutbox
1178             + \skip_use:c { \l__enumext_topsep_ \l__enumext_level: _skip }
1179         }
1180     }
1181 }
1182 }

```

(End of definition for \l__enumext_mini_set_vskip:.)

\l__enumext_zero_parsep: The function \l__enumext_zero_parsep: “adjusted” the value of \l__enumext_minipage_after_skip detecting the value of \l__enumext_minipage_after_skip from the previous level. This is necessary since \l__enumext_minipage_after_skip from the previous level affects the *vertical spaces* and this is noticeable when using the `nosep` or `noitemsep` keys.

```

1183 \cs_new_protected:Nn \l__enumext_zero_parsep:
1184 {
1185     \int_case:nn { \l__enumext_level_int }
1186     {
1187         { 2 }{
1188             \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip }
1189             {
1190                 \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
1191             }
1192         }
1193         { 3 }{
1194             \skip_if_eq:nnF { \l__enumext_parsep_ii_skip } { \c_zero_skip }
1195             {
1196                 \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
1197             }
1198         }
1199         { 4 }{
1200             \skip_if_eq:nnF { \l__enumext_parsep_iii_skip } { \c_zero_skip }
1201             {
1202                 \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
1203             }
1204         }
1205     }
1206 }

```

(End of definition for \l__enumext_zero_parsep:.)

\l__enumext_mini_addvspace: The function \l__enumext_mini_addvspace: will apply the spaces set using \l__enumext_mini_addvspace “above” the \l__enumext_mini_env* environment in enumext, taking into account whether TeX is in *horizontal mode* or *vertical mode*. For the latter we will make some adjustments since the \l__enumext_partopsep parameter comes into play and this affects the *vertical spacing*.

```

1207 \cs_new_protected:Nn \l__enumext_mini_addvspace:
1208 {
1209     \l__enumext_mini_set_vskip:
1210     \mode_if_vertical:T
1211     {
1212         \skip_add:Nn \l__enumext_minipage_left_skip
1213         {

```

```

1214         \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1215     }
1216     \skip_add:Nn \l__enumext_minipage_after_skip
1217     {
1218         \skip_use:c { \l__enumext_partopsep_ \l__enumext_level: _skip }
1219     }
1220 }
1221 \par\nopagebreak
1222 \addvspace { \l__enumext_minipage_left_skip }
1223 }

```

(End of definition for `\l__enumext_mini_addvspace:`.)

11.22.2 Adjustment of vertical spaces for minipage in keyans

`\l__enumext_keyans_mini_set_vskip:`

The function `\l__enumext_keyans_mini_set_vskip:` will take care of determining the “adjusted” spaces that we will apply “above” and “below” the `\l__enumext_mini_env*` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

```

1224 \cs_new_protected:Nn \l__enumext_keyans_mini_set_vskip:
1225 {
1226     \skip_zero_new:N \l__enumext_minipage_after_skip
1227     \skip_zero_new:N \l__enumext_minipage_left_skip
1228     \skip_zero_new:N \l__enumext_minipage_right_skip
1229     \int_compare:nNnTF { \l__enumext_columns_v_int } > { 1 }
1230     {
1231         \skip_if_eq:nnTF { \l__enumext_topsep_v_skip } { \c_zero_skip }
1232         {
1233             \skip_set:Nn \l__enumext_minipage_left_skip { -0.25\box_dp:N \strutbox }
1234             \skip_set:Nn \l__enumext_minipage_right_skip { 0.705\box_dp:N \strutbox }
1235             \skip_set:Nn \l__enumext_minipage_after_skip { \box_dp:N \strutbox }
1236             \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip }
1237             {
1238                 \skip_add:Nn \l__enumext_minipage_after_skip { 2.15\box_dp:N \strutbox }
1239             }
1240         }
1241     }
1242     \skip_set:Nn \l__enumext_minipage_left_skip
1243     {
1244         \skip_use:N \l__enumext_topsep_v_skip
1245     }
1246     \skip_set:Nn \l__enumext_minipage_right_skip
1247     {
1248         0.705\box_dp:N \strutbox
1249     }
1250     \skip_set:Nn \l__enumext_minipage_after_skip
1251     {
1252         1.85\box_dp:N \strutbox + \l__enumext_topsep_v_skip
1253     }
1254 }
1255 {
1256     \skip_if_eq:nnTF { \l__enumext_topsep_v_skip } { \c_zero_skip }
1257     {
1258         \skip_set:Nn \l__enumext_minipage_left_skip
1259         {
1260             0.5\box_dp:N \strutbox
1261             + \l__enumext_partopsep_v_skip
1262         }
1263         \skip_set:Nn \l__enumext_minipage_right_skip
1264         {
1265             \l__enumext_partopsep_v_skip
1266         }
1267         \skip_set:Nn \l__enumext_minipage_after_skip { 1.6\box_dp:N \strutbox }
1268     }
1269 }
1270 {
1271     \skip_set:Nn \l__enumext_minipage_left_skip
1272     {
1273         0.5875\box_dp:N \strutbox - \l__enumext_partopsep_v_skip
1274     }
1275     \skip_set:Nn \l__enumext_minipage_right_skip
1276     {
1277         \l__enumext_topsep_v_skip + \l__enumext_partopsep_v_skip

```

```

1278         }
1279         \skip_set:Nn \l__enumext_minipage_after_skip
1280         {
1281             0.325\box_dp:N \strutbox + \l__enumext_topsep_v_skip
1282         }
1283     }
1284 }
1285 }

```

(End of definition for `\l__enumext_keyans_mini_set_vskip:`)

`\l__enumext_keyans_mini_addvspace:`

The function `\l__enumext_keyans_mini_addvspace:` will apply the spaces set using `\addvspace` “above” the `\l__enumext_mini_env*` environment in `keyans`, taking into account whether \TeX is in *horizontal mode* or *vertical mode*. For the latter we will make some adjustments since the `\partopsep` parameter comes into play and this affects the *vertical spacing*. The implementation of this function is the same as the one used in `enumext`.

```

1286 \cs_new_protected:Nn \l__enumext_keyans_mini_addvspace:
1287 {
1288     \l__enumext_keyans_mini_set_vskip:
1289     \mode_if_vertical:T
1290     {
1291         \skip_add:Nn \l__enumext_minipage_left_skip
1292         {
1293             \l__enumext_partopsep_v_skip
1294         }
1295         \skip_add:Nn \l__enumext_minipage_after_skip
1296         {
1297             \l__enumext_partopsep_v_skip
1298         }
1299     }
1300     \par\nopagebreak
1301     \addvspace { \l__enumext_minipage_left_skip }
1302 }

```

(End of definition for `\l__enumext_keyans_mini_addvspace:`)

11.22.3 Adjustment of vertical spaces for minipage in `enumext*` and `keyans*`

`\l__enumext_mini_set_vskip_vii:`

`\l__enumext_mini_set_vskip_viii:`

The functions `\l__enumext_mini_set_vskip_vii:` and `\l__enumext_mini_set_vskip_viii:` will take care of determining the “adjusted” spaces that we will apply “above” and “below” the `\l__enumext_mini_env*` environment in `enumext*` and `keyans*`.

```

1303 \cs_new_protected:Nn \l__enumext_mini_set_vskip_vii:
1304 {
1305     \skip_zero_new:N \l__enumext_minipage_left_skip
1306     \skip_gzero_new:N \g__enumext_minipage_right_skip
1307     \skip_gzero_new:N \g__enumext_minipage_after_skip
1308     \skip_if_eq:nnTF { \l__enumext_topsep_vii_skip } { \c_zero_skip }
1309     {
1310         \skip_set:Nn \l__enumext_minipage_left_skip { 0.5\box_dp:N \strutbox }
1311         \skip_gset:Nn \g__enumext_minipage_right_skip { 0.325\box_dp:N \strutbox }
1312     }
1313     {
1314         \skip_set:Nn \l__enumext_minipage_left_skip { 0.5875\box_dp:N \strutbox }
1315         \skip_gset:Nn \g__enumext_minipage_right_skip
1316         {
1317             \l__enumext_topsep_vii_skip
1318         }
1319         \skip_gset:Nn \g__enumext_minipage_after_skip
1320         {
1321             0.325\box_dp:N \strutbox + \l__enumext_topsep_vii_skip
1322         }
1323     }
1324 }
1325 \cs_new_protected:Nn \l__enumext_mini_set_vskip_viii:
1326 {
1327     \skip_zero_new:N \l__enumext_minipage_after_skip
1328     \skip_zero_new:N \l__enumext_minipage_left_skip
1329     \skip_zero_new:N \l__enumext_minipage_right_skip
1330     \skip_if_eq:nnTF { \l__enumext_topsep_viii_skip } { \c_zero_skip }
1331     {
1332         \skip_set:Nn \l__enumext_minipage_left_skip

```

```

1333     {
1334         0.5\box_dp:N \strutbox
1335     }
1336     \skip_set:Nn \l__enumext_minipage_right_skip
1337     {
1338         \l__enumext_partopsep_viii_skip
1339     }
1340     \skip_set:Nn \l__enumext_minipage_after_skip
1341     {
1342         1.6\box_dp:N \strutbox
1343     }
1344 }
1345 {
1346     \skip_set:Nn \l__enumext_minipage_left_skip
1347     {
1348         0.5875\box_dp:N \strutbox
1349     }
1350     \skip_set:Nn \l__enumext_minipage_right_skip
1351     {
1352         \l__enumext_topsep_viii_skip
1353     }
1354     \skip_set:Nn \l__enumext_minipage_after_skip
1355     {
1356         0.325\box_dp:N \strutbox + \l__enumext_topsep_viii_skip
1357     }
1358 }
1359 }

```

(End of definition for `__enumext_mini_set_vskip_vii:` and `__enumext_mini_set_vskip_viii:`)

`__enumext_mini_addvspace_vii:`
`__enumext_mini_addvspace_viii:`

The functions `__enumext_mini_addvspace_vii:` and `__enumext_mini_addvspace_viii:` will apply the vertical space “only above” the `__enumext_mini_env*` environment on the *left side* when the `mini-right` key is active in the `enumext*` and `keyans*` environments.

Here we will NOT take into account whether \TeX is in *horizontal mode* or *vertical mode*, since `\partopsep` is equal to `0pt` in both environments.

```

1360 \cs_new_protected:Nn \__enumext_mini_addvspace_vii:
1361 {
1362     \__enumext_mini_set_vskip_vii:
1363     \par\nopagebreak
1364     \addvspace { \l__enumext_minipage_left_skip }
1365 }
1366 \cs_new_protected:Nn \__enumext_mini_addvspace_viii:
1367 {
1368     \__enumext_mini_set_vskip_viii:
1369     \par\nopagebreak
1370     \addvspace { \l__enumext_minipage_left_skip }
1371 }

```

(End of definition for `__enumext_mini_addvspace_vii:` and `__enumext_mini_addvspace_viii:`)

11.22.4 The command `\miniright`

The command `\miniright` will close the `__enumext_mini_env*` environment on the “left side”, open the `__enumext_mini_env*` environment on the “right side” adding the *adjusted vertical space*. By default we will add `\centering` when starting the “right side” environment. The *starred argument* ‘`*`’ inhibits the use of `\centering` command i.e. the usual \TeX justification is maintained in the `__enumext_mini_env*` on the “right side”.

`\miniright`

First we will perform some checks to prevent the command from being executed outside the `enumext` environment or from being executed inside the `keyanspic` environment, then we call the internal functions for the `enumext` and `keyans` environments.

```

1372 \NewDocumentCommand \miniright { s }
1373 {
1374     \int_compare:nNt { \l__enumext_keyans_pic_level_int } = { 1 }
1375     {
1376         \msg_error:nnn { enumext } { wrong-miniright-place }
1377     }
1378     \int_compare:nNt { \l__enumext_level_int } = { 0 }
1379     {
1380         \msg_error:nnn { enumext } { wrong-miniright-place }
1381     }

```

```

1382 \int_compare:nNnTF { \l__enumext_keyans_level_int } = { 1 }
1383 {
1384   \l__enumext_keyans_mini_right_cmd:n {#1}
1385 }
1386 { \l__enumext_mini_right_cmd:n {#1} }
1387 }

```

(End of definition for `\miniright`. This function is documented on page 10.)

`\l__enumext_mini_right_cmd:n`

The function `\l__enumext_mini_right_cmd:n` takes as argument the *starred* ‘*’ of the `\miniright` command in the `enumext` environment. We check if the `mini-env` key is active via the variable `\l__enumext_minipage_right_X_dim`, if so we close the `multicols` environment with the `\l__enumext_mini_env*` environment on the “left side”, then we open the `\l__enumext_mini_env*` environment on the “right side”, apply our adjusted “vertical spaces”, followed by adding the `\centering` command when the starred argument ‘*’ is not present and set zero `\g__enumext_minipage_stat_int`, otherwise we return an error.

```

1388 \cs_new_protected:Npn \l__enumext_mini_right_cmd:n #1
1389 {
1390   \dim_compare:nNnTF
1391   { \dim_use:c { \l__enumext_minipage_right_ \l__enumext_level: _dim } } > { \c_zero_dim }
1392   {
1393     \l__enumext_multicols_stop:
1394     \end{__enumext_mini_env*}
1395     \hfill
1396     \begin{__enumext_mini_env*}
1397     { \dim_use:c { \l__enumext_minipage_right_ \l__enumext_level: _dim } }
1398     \par\addvspace { \l__enumext_minipage_right_skip }
1399     \bool_if:nF {#1}
1400     {
1401       \centering
1402     }
1403     \int_gzero:N \g__enumext_minipage_stat_int
1404   }
1405   { \msg_error:nnn { enumext } { wrong-miniright-use } }
1406 }

```

(End of definition for `\l__enumext_mini_right_cmd:n`.)

`\l__enumext_keyans_mini_right_cmd:n`

The function `\l__enumext_keyans_mini_right_cmd:n` takes as argument the *starred* ‘*’ of the `\miniright` command in the `keyans` environment. The implementation of this function is the same as that of the `\l__enumext_mini_right_cmd:n` function of the `enumext` environment.

```

1407 \cs_new_protected:Npn \l__enumext_keyans_mini_right_cmd:n #1
1408 {
1409   \dim_compare:nNnTF { \l__enumext_minipage_right_v_dim } > { \c_zero_dim }
1410   {
1411     \l__enumext_keyans_multicols_stop:
1412     \end{__enumext_mini_env*}
1413     \hfill
1414     \begin{__enumext_mini_env*}{ \l__enumext_minipage_right_v_dim }
1415     \par\addvspace { \l__enumext_minipage_right_skip }
1416     \bool_if:nF {#1}
1417     {
1418       \centering
1419     }
1420     \int_gzero:N \g__enumext_minipage_stat_int
1421   }
1422   { \msg_error:nnn { enumext } { wrong-miniright-use } }
1423 }

```

(End of definition for `\l__enumext_keyans_mini_right_cmd:n`.)

11.23 Setting above and below keys

While having controlled the *vertical spaces* within the `enumext` and `keyans` environments when using the `columns` or `mini-env` keys, sometimes the “vertical spaces above” or “vertical spaces below” the environments are not as expected and it is necessary to be able to apply a “fine correction” to these. As I have not been able to correct these *glitches*, the best option is to leave a couple of `<keys>` dedicated to this purpose, in this case it is best to use `\vspace` or `\vspace*` when convenient.

above Define above, above*, below and below* keys for enumext and keyans environments.

```

1424 \cs_set_protected:Npn \__enumext_tmp:nn #1 #2
1425 {
1426   \keys_define:nn { enumext / #1 }
1427   {
1428     above .skip_set:c = { \__enumext_vspace_above_#2_skip },
1429     above .value_required:n = true,
1430     above* .code:n = \bool_set_true:c { \__enumext_vspace_a_star_#2_bool }
1431               \keys_set:nn { enumext / #1 } { above = {##1} },
1432     above* .value_required:n = true,
1433     below .skip_set:c = { \__enumext_vspace_below_#2_skip },
1434     below .value_required:n = true,
1435     below* .code:n = \bool_set_true:c { \__enumext_vspace_b_star_#2_bool }
1436               \keys_set:nn { enumext / #1 } { below = {##1} },
1437     below* .value_required:n = true,
1438   }
1439 }
1440 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }

```

(End of definition for above and others.)

11.23.1 Functions for above and below keys in enumext

__enumext_vspace_above: The function __enumext_vspace_above: apply the *vertical space above* the enumext environment set by the above* and above keys.

```

1441 \cs_new_protected:Nn \__enumext_vspace_above:
1442 {
1443   \skip_if_eq:nnF
1444   { \skip_use:c { \__enumext_vspace_above_ \__enumext_level: _skip } } { \c_zero_skip }
1445   {
1446     \bool_if:cTF { \__enumext_vspace_a_star_ \__enumext_level: _bool }
1447     {
1448       \vspace*{ \skip_use:c { \__enumext_vspace_above_ \__enumext_level: _skip } }
1449     }
1450     {
1451       \vspace { \skip_use:c { \__enumext_vspace_above_ \__enumext_level: _skip } }
1452     }
1453   }
1454 }

```

(End of definition for __enumext_vspace_above:.)

__enumext_vspace_below: The function __enumext_vspace_below: apply the *vertical space below* the enumext environment set by the below* and below keys.

```

1455 \cs_new_protected:Nn \__enumext_vspace_below:
1456 {
1457   \skip_if_eq:nnF
1458   { \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } } { \c_zero_skip }
1459   {
1460     \bool_if:cTF { \__enumext_vspace_b_star_ \__enumext_level: _bool }
1461     {
1462       \vspace*{ \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } }
1463     }
1464     {
1465       \vspace { \skip_use:c { \__enumext_vspace_below_ \__enumext_level: _skip } }
1466     }
1467   }
1468 }

```

(End of definition for __enumext_vspace_below:.)

11.23.2 Functions for above and below keys in keyans

__enumext_vspace_above_v: The function __enumext_vspace_above_v: apply the *vertical space above* the keyans environment set by the above and above* keys.

```

1469 \cs_new_protected:Nn \__enumext_vspace_above_v:
1470 {
1471   \skip_if_eq:nnF { \__enumext_vspace_above_v_skip } { \c_zero_skip }
1472   {
1473     \bool_if:NTF \__enumext_vspace_a_star_v_bool
1474     {
1475       \vspace*{ \__enumext_vspace_above_v_skip }

```



```

1476     }
1477     { \vspace { \l__enumext_vspace_above_v_skip } }
1478   }
1479 }

```

(End of definition for __enumext_vspace_above_v:.)

__enumext_vspace_below_v:

The function __enumext_vspace_below_v: apply the *vertical space below* the **keyans** environment set by the *below** and *below* keys.

```

1480 \cs_new_protected:Nn \__enumext_vspace_below_v:
1481 {
1482   \skip_if_eq:nnF { \l__enumext_vspace_below_v_skip } { \c_zero_skip }
1483   {
1484     \bool_if:NTF \l__enumext_vspace_b_star_v_bool
1485     {
1486       \vspace*{ \l__enumext_vspace_below_v_skip }
1487     }
1488     { \vspace { \l__enumext_vspace_below_v_skip } }
1489   }
1490 }

```

(End of definition for __enumext_vspace_below_v:.)

11.23.3 Functions for above and below keys in enumext* keyans*

__enumext_vspace_above_vii:

The functions __enumext_vspace_above_vii: and __enumext_vspace_above_viii: apply the *vertical space above* the **enumext*** and **keyans*** environments set by the *above* and *above** keys.

__enumext_vspace_above_viii:

```

1491 \cs_new_protected:Nn \__enumext_vspace_above_vii:
1492 {
1493   \skip_if_eq:nnF { \l__enumext_vspace_above_vii_skip } { \c_zero_skip }
1494   {
1495     \bool_if:NTF \l__enumext_vspace_a_star_vii_bool
1496     {
1497       \vspace*{ \l__enumext_vspace_above_vii_skip }
1498     }
1499     { \vspace { \l__enumext_vspace_above_vii_skip } }
1500   }
1501 }
1502 \cs_new_protected:Nn \__enumext_vspace_above_viii:
1503 {
1504   \skip_if_eq:nnF { \l__enumext_vspace_above_viii_skip } { \c_zero_skip }
1505   {
1506     \bool_if:NTF \l__enumext_vspace_a_star_viii_bool
1507     {
1508       \vspace*{ \l__enumext_vspace_above_viii_skip }
1509     }
1510     { \vspace { \l__enumext_vspace_above_viii_skip } }
1511   }
1512 }

```

(End of definition for __enumext_vspace_above_vii: and __enumext_vspace_above_viii:.)

__enumext_vspace_below_vii:

The functions __enumext_vspace_below_vii: and __enumext_vspace_below_viii: apply the *vertical space below* the **enumext*** and **keyans*** environments set by the *below** and *below* keys.

__enumext_vspace_below_viii:

```

1513 \cs_new_protected:Nn \__enumext_vspace_below_vii:
1514 {
1515   \skip_if_eq:nnF { \l__enumext_vspace_below_vii_skip } { \c_zero_skip }
1516   {
1517     \bool_if:NTF \l__enumext_vspace_b_star_vii_bool
1518     {
1519       \vspace*{ \l__enumext_vspace_below_vii_skip }
1520     }
1521     { \vspace { \l__enumext_vspace_below_vii_skip } }
1522   }
1523 }
1524 \cs_new_protected:Nn \__enumext_vspace_below_viii:
1525 {
1526   \skip_if_eq:nnF { \l__enumext_vspace_below_viii_skip } { \c_zero_skip }
1527   {
1528     \bool_if:NTF \l__enumext_vspace_b_star_viii_bool
1529     {
1530       \vspace*{ \l__enumext_vspace_below_viii_skip }

```

```

1531     }
1532     { \vspace { \l__enumext_vspace_below_viii_skip } }
1533   }
1534 }

```

(End of definition for `__enumext_vspace_below_vii:` and `__enumext_vspace_below_viii:`)

11.24 Setting series, resume and resume* keys

The `series` key is responsible for the whole process of the `resume` and `resume*` keys. The idea behind this is to be able to absorb the $\langle keys \rangle$ passed to the optional argument of the “first level” of the environments `enumext` and `enumext*`, but, discarding some specific $\langle keys \rangle$. This implementation is adapted directly from the code provided by Jonathan P. Spratte (@Skillmon) in [chat-Tex-SX](#)

```

series We define the keys series, resume and resume* only for the “first level” of enumext and enumext*.
resume
resume*
1535 \cs_set_protected:Npn \__enumext_tmp:n #1
1536 {
1537   \keys_define:nn { enumext / #1 }
1538   {
1539     series .str_set:N = \l__enumext_series_str,
1540     series .value_required:n = true,
1541     resume .code:n = \__enumext_resume_series:n {##1},
1542     resume* .code:n = \__enumext_resume_starred:,
1543     resume* .value_forbidden:n = true,
1544   }
1545 }
1546 \clist_map_inline:nn { level-1, enumext* } { \__enumext_tmp:n {#1} }

```

(End of definition for `series`, `resume`, and `resume*`.)

11.24.1 Internal functions for series key

The function `__enumext_filter_series:n` will be in charge of filtering the $\langle keys \rangle$ we want to store where `{#1}` represents the optional value passed to the environment.

```

1547 \cs_new:Npn \__enumext_filter_series:n #1
1548 {
1549   \use:e
1550   {
1551     \keyval_parse:NNn
1552     \__enumext_filter_series_key:n
1553     \__enumext_filter_series_pair:nn {#1}
1554   }
1555 }

```

The function `__enumext_filter_series_key:n` will be responsible for filtering the $\langle keys \rangle$ that are passed “without value” by excluding the `resume`, `resume*` and `base-fix` keys.

```

1556 \cs_new:Npn \__enumext_filter_series_key:n #1
1557 {
1558   \str_case:nnF {#1}
1559   {
1560     { resume } {}
1561     { resume* } {}
1562     { base-fix } {}
1563   }
1564   { , { \exp_not:n {#1} } }
1565 }

```

The function `__enumext_filter_series_pair:nn` will be responsible for filtering the $\langle keys \rangle$ that are passed “with value” by excluding the `series`, `resume`, `start`, `save-ans` and `save-key` keys.

```

1566 \cs_new:Npn \__enumext_filter_series_pair:nn #1#2
1567 {
1568   \str_case:nnF {#1}
1569   {
1570     { series } {}
1571     { resume } {}
1572     { start } {}
1573     { save-ans } {}
1574     { save-key } {}
1575   }
1576   { , { \exp_not:n {#1} } } = { \exp_not:n {#2} } }
1577 }

```

(End of definition for `__enumext_filter_series:n`, `__enumext_filter_series_key:n`, and `__enumext_filter_series_pair:nn`.)

```

__enumext_parse_series:n
__enumext_resume_last:n

```

The function `__enumext_parse_series:n` will be responsible for storing the filtered *(keys)* in the global variable `\g__enumext_series_⟨series name⟩_tl` along with the creation of the integer variable `\g__enumext_series_⟨series name⟩_int` when the key is passed as an argument; otherwise, it will check the state of the boolean variable `\l__enumext_resume_active_bool` set by the keys `resume` and `resume*` and will call the function `__enumext_resume_last:n`.

- The value of boolean variable `\l__enumext_resume_active_bool` is set to true by the function `__enumext_resume_counter:n` which is used by the keys `resume` and `resume*`, in this case we must Make sure it is set to false so that it does not overwrite the default filtered *(keys)*. This function is passed to the function `__enumext_parse_keys:n` in the `enumext` environment definition (§11.38) and to the function `__enumext_parse_keys_vii:n` in the `enumext*` environment definition (§11.42).

```

1578 \cs_new_protected:Npn \__enumext_parse_series:n #1
1579 {
1580   \str_if_empty:NTF \l__enumext_series_str
1581   {
1582     \bool_if:NF \l__enumext_resume_active_bool
1583     {
1584       \__enumext_resume_last:n {#1}
1585     }
1586   }
1587   {
1588     \tl_gclear_new:c { g__enumext_series_ \l__enumext_series_str_tl }
1589     \tl_gset:ce { g__enumext_series_ \l__enumext_series_str_tl }
1590     { \__enumext_filter_series:n {#1} }
1591     \int_if_exist:cF { g__enumext_series_ \l__enumext_series_str_int }
1592     {
1593       \int_new:c { g__enumext_series_ \l__enumext_series_str_int }
1594     }
1595   }
1596 }

```

The function `__enumext_resume_last:n` will be in charge of saving the filtering *(keys)* when the `series` key is *not used* and will save them in the variable `\g__enumext_standar_series_tl` for the `enumext` environment and in the variable `\g__enumext_starred_series_tl` for the `enumext*` environment. Here we must use `\bool_lazy_all:nT` to make sure that the default values are not overwritten when the environment is nested and the `series` key is not being used.

```

1597 \cs_new_protected:Npn \__enumext_resume_last:n #1
1598 {
1599   \bool_if:NT \l__enumext_standar_first_bool
1600   {
1601     \tl_gclear:N \g__enumext_standar_series_tl
1602     \tl_gset:Ne \g__enumext_standar_series_tl { \__enumext_filter_series:n {#1} }
1603   }
1604   \bool_if:NT \l__enumext_starred_first_bool
1605   {
1606     \tl_gclear:N \g__enumext_starred_series_tl
1607     \tl_gset:Ne \g__enumext_starred_series_tl { \__enumext_filter_series:n {#1} }
1608   }
1609 }

```

(End of definition for `__enumext_parse_series:n` and `__enumext_resume_last:n`)

11.24.2 Internal function to save counter value

```
__enumext_resume_save_counter:
```

The `__enumext_resume_save_counter:` function will save the last counter value to `\g__enumext_series_⟨series name⟩_int` if the `series={⟨series name⟩}` key has been passed, to `\g__enumext_resume_int` if it has passed the key `resume without value` and the key `series` is not active, in `\g__enumext_series_⟨series name⟩_int` if the key `resume={⟨series name⟩}` has been passed and in `\g__enumext_series_⟨store name⟩_int` if the key has been passed `save-ans={⟨store name⟩}`.

- The variables `\l__enumext_series_str` and `\l__enumext__resume_name_tl` contain the same *{⟨series name⟩}* but are executed at different moments, the integer variable with `\l__enumext_series_str` sets the value when execute `series={⟨series name⟩}` and the integer variable with `\l__enumext__resume_name_tl` sets the subsequent values when use `resume={⟨series name⟩}`. This function is passed to the `enumext` environment definition (§11.38) and the `enumext*` environment definition (§11.42).

```

1610 \cs_new_protected:Npn \__enumext_resume_save_counter:
1611 {
1612   \bool_if:NT \g__enumext_standar_bool
1613   {
1614     \tl_if_empty:NF \l__enumext_series_str
1615     {
1616       \int_gset_eq:cN

```

```

1617         { g__enumext_series_ \l__enumext_series_str _int } \value{enumXi}
1618     }
1619     \tl_if_empty:NTF \l__enumext_resume_name_tl
1620     {
1621         \str_if_empty:NT \l__enumext_series_str
1622         {
1623             \int_gset_eq:NN \g__enumext_resume_int \value{enumXi}
1624         }
1625     }
1626     {
1627         \int_if_exist:cT { g__enumext_series_ \l__enumext_resume_name_tl _int }
1628         {
1629             \int_gset_eq:cN
1630             { g__enumext_series_ \l__enumext_resume_name_tl _int } \value{enumXi}
1631         }
1632     }
1633     \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl _int }
1634     {
1635         \int_gset_eq:cN
1636         { g__enumext_resume_ \l__enumext_store_name_tl _int } \value{enumXi}
1637     }
1638 }
1639 \bool_if:NT \g__enumext_starred_bool
1640 {
1641     \tl_if_empty:NF \l__enumext_series_str
1642     {
1643         \int_gset_eq:cN
1644         { g__enumext_series_ \l__enumext_series_str _int } \value{enumXvii}
1645     }
1646     \tl_if_empty:NTF \l__enumext_resume_name_tl
1647     {
1648         \str_if_empty:NT \l__enumext_series_str
1649         {
1650             \int_gset_eq:NN \g__enumext_resume_vii_int \value{enumXvii}
1651         }
1652     }
1653     {
1654         \int_if_exist:cT { g__enumext_series_ \l__enumext_resume_name_tl _int }
1655         {
1656             \int_gset_eq:cN
1657             { g__enumext_series_ \l__enumext_resume_name_tl _int } \value{enumXvii}
1658         }
1659     }
1660     \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl _int }
1661     {
1662         \int_gset_eq:cN
1663         { g__enumext_resume_ \l__enumext_store_name_tl _int } \value{enumXvii}
1664     }
1665 }
1666 }

```

(End of definition for __enumext_resume_save_counter:.)

11.24.3 Internal functions for resume key

__enumext_resume_series:n

The function __enumext_resume_series:n will handle the argument passed to the `resume` key in `enumext` and `enumext*` environments. If the key is passed *without value* the function __enumext_resume_counter: is executed which will set the counter according to the numbering of the last `enumext` or `enumext*` environments in which `series={⟨series name⟩}` key is not present, if the `save-ans` key is active it will set the counter according to the value of the integer variable created by that key, otherwise it will verify that the `\g__enumext_series_⟨series name⟩_tl` variable set by the `series` key exists, if so it will pass these keys to the *first level* of the environment, otherwise it will return an error.

```

1667 \cs_new_protected:Npn \__enumext_resume_series:n #1
1668 {
1669     \tl_if_empty:NTF {#1}
1670     {
1671         \__enumext_resume_counter:n { }
1672     }
1673     {
1674         \tl_if_exist:cTF { g__enumext_series_ \tl_to_str:n {#1} _tl }
1675         {
1676             \__enumext_resume_counter:n {#1}

```

```

1677         \bool_if:NT \g__enumext_standar_bool
1678         {
1679             \keys_set:nv { enumext / level-1 }
1680             { g__enumext_series_ \tl_to_str:n {#1} _tl }
1681         }
1682         \bool_if:NT \g__enumext_starred_bool
1683         {
1684             \keys_set:nv { enumext / enumext* }
1685             { g__enumext_series_ \tl_to_str:n {#1} _tl }
1686         }
1687     }
1688     {
1689         \bool_if:NT \g__enumext_standar_bool
1690         {
1691             \msg_error:nnn { enumext } { unknown-series } {#1}
1692         }
1693         \bool_if:NT \g__enumext_starred_bool
1694         {
1695             \msg_error:nnn { enumext } { unknown-series } {#1}
1696         }
1697     }
1698 }
1699 }

```

(End of definition for __enumext_resume_series:n.)

```

\__enumext_resume_counter:n
\__enumext_resume_counter:
  \__enumext_resume_counter_series:
  \__enumext_resume_counter_save_ans:

```

The function `__enumext_resume_counter:n` will set the variable `\l__enumext_resume_active_bool` to true and pass the value of the key `resume` to the variable `\l__enumext_series_name_tl` which will contain the `{⟨series name⟩}`. If the variable `\l__enumext_series_name_tl` is empty, that is, we are passing the key `resume` *without value*, we will execute the function `__enumext_resume_counter:`; otherwise, when we pass `resume={⟨series name⟩}` we will execute the function `__enumext_resume_counter_series:`, finally we will execute the function `__enumext_resume_counter_save_ans:` which is associated with the key `save-ans`.

```

1700 \cs_new_protected:Npn \__enumext_resume_counter:n #1
1701 {
1702     \bool_set_true:N \l__enumext_resume_active_bool
1703     \tl_set:Nn \l__enumext_resume_name_tl {#1}
1704     \tl_if_empty:NTF \l__enumext_resume_name_tl
1705     {
1706         \__enumext_resume_counter:
1707     }
1708     {
1709         \__enumext_resume_counter_series:
1710     }
1711     \__enumext_resume_counter_save_ans:
1712 }

```

The `__enumext_resume_counter:` function is executed when the `resume` key is used *without value*, only the counters for the “first level” of the environments will be set.

```

1713 \cs_new_protected:Nn \__enumext_resume_counter:
1714 {
1715     \bool_if:NT \g__enumext_standar_bool
1716     {
1717         \int_gincr:N \g__enumext_resume_int
1718         \int_set_eq:NN \l__enumext_start_i_int \g__enumext_resume_int
1719     }
1720     \bool_if:NT \g__enumext_starred_bool
1721     {
1722         \int_gincr:N \g__enumext_resume_vii_int
1723         \int_set_eq:NN \l__enumext_start_vii_int \g__enumext_resume_vii_int
1724     }
1725 }

```

The function `__enumext_resume_counter_series:` will be executed when the `resume={⟨series name⟩}` key is active, setting the counters for the “first level” of the environments according to the value of the integer variables created by the `series` key.

```

1726 \cs_new_protected:Nn \__enumext_resume_counter_series:
1727 {
1728     \bool_if:NT \g__enumext_standar_bool
1729     {
1730         \int_set:Nn \l__enumext_start_i_int

```

```

1731         {
1732             \int_use:c { g__enumext_series_ \l__enumext_resume_name_tl _int } + 1
1733         }
1734     }
1735     \bool_if:NT \g__enumext_starred_bool
1736     {
1737         \int_set:Nn \l__enumext_start_vii_int
1738         {
1739             \int_use:c { g__enumext_series_ \l__enumext_resume_name_tl _int } + 1
1740         }
1741     }
1742 }

```

The function `__enumext_resume_counter_save_ans:` will be executed when the `save-ans` key is active along with the `resume` key, setting the counters for the “*first level*” of the environments according to the value of the integer variables created by the `save-ans` key.

```

1743 \cs_new_protected:Nn \__enumext_resume_counter_save_ans:
1744 {
1745     \bool_lazy_and:nnT
1746     { \bool_if_p:N \l__enumext_standar_first_bool }
1747     { \bool_if_p:N \l__enumext_store_active_bool }
1748     {
1749         \int_set:Nn \l__enumext_start_i_int
1750         {
1751             \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int } + 1
1752         }
1753     }
1754     \bool_lazy_and:nnT
1755     { \bool_if_p:N \l__enumext_starred_first_bool }
1756     { \bool_if_p:N \l__enumext_store_active_bool }
1757     {
1758         \int_set:Nn \l__enumext_start_vii_int
1759         {
1760             \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int } + 1
1761         }
1762     }
1763 }

```

(End of definition for `__enumext_resume_counter:n` and others.)

11.24.4 Internal function for `resume*` key

`__enumext_resume_starred:` The function `__enumext_resume_starred:` will handle the `resume*` key in the `enumext` and `enumext*` environments. This function will execute the filtered `<keys>` in the last one and will continue with the numbering according to the last execution of the environment `enumext` or `enumext*` in which the keys `resume={<series name>}` or `series={<series name>}` were not active.

```

1764 \cs_new_protected:Nn \__enumext_resume_starred:
1765 {
1766     \bool_if:NT \g__enumext_standar_bool
1767     {
1768         \tl_if_empty:NF \g__enumext_standar_series_tl
1769         {
1770             \__enumext_resume_counter:n { }
1771             \keys_set:nV { enumext / level-1 } \g__enumext_standar_series_tl
1772         }
1773     }
1774     \bool_if:NT \g__enumext_starred_bool
1775     {
1776         \tl_if_empty:NF \g__enumext_starred_series_tl
1777         {
1778             \__enumext_resume_counter:n { }
1779             \keys_set:nV { enumext / enumext* } \g__enumext_starred_series_tl
1780         }
1781     }
1782 }

```

(End of definition for `__enumext_resume_starred:`.)

11.25 Setting `save-ans`, `check-ans` and `no-store` keys

The key `save-ans` is directly associated with the keys `check-ans`, `no-store`, `resume` and `resume*`, this will activate the entire “*storage system*” in the `enumext` package.

11.25.1 Setting save-ans key

`save-ans` We define the keys `save-ans` only for the “*first level*” of `enumext` and `enumext*`.

```

1783 \cs_set_protected:Npn \__enumext_tmp:n #1
1784 {
1785   \keys_define:nn { enumext / #1 }
1786   {
1787     save-ans .code:n = \__enumext_storing_set:n {##1},
1788     save-ans .value_required:n = true,
1789   }
1790 }
1791 \clist_map_inline:nn { level-1, enumext* } { { \__enumext_tmp:n {#1} }

```

(End of definition for `save-ans`.)

11.25.2 Internal functions for save-ans key

`__enumext_start_save_ans_msg:` The functions `__enumext_start_save_ans_msg:` and `__enumext_stop_save_ans_msg:` will display in the terminal and `.log` file the environment in which the `save-ans` key was executed along with the line at the beginning and end of it. The function `__enumext_start_save_ans_msg:` will be passed to `__enumext_storing_set:n` and the function `__enumext_stop_save_ans_msg:` will be passed to the function `__enumext_execute_after_env:`.

```

1792 \cs_new_protected:Nn \__enumext_start_save_ans_msg:
1793 {
1794   \msg_term:nnVV { enumext } { save-ans-log }
1795   \g__enumext_envir_name_tl \l__enumext_store_name_tl
1796 }
1797 \cs_new_protected:Nn \__enumext_stop_save_ans_msg:
1798 {
1799   \msg_term:nnVV { enumext } { save-ans-log-hook }
1800   \g__enumext_envir_name_tl \g__enumext_store_name_tl
1801 }

```

(End of definition for `__enumext_start_save_ans_msg:` and `__enumext_stop_save_ans_msg:`.)

`__enumext_storing_set:n` The function `__enumext_storing_set:n` first pass the value of the `save-ans` key to the variable `\l__enumext_store_name_tl` which will contain the “*store name*” of the `<sequence>` and `<prop list>` we will use. If `\l__enumext_store_name_tl` is *empty* we return an error message, otherwise will return the appropriate message `__enumext_start_save_ans_msg:` and proceed to execute the function `__enumext_storing_exec:` for `enumext` and `enumext*` environments.

```

1802 \cs_new_protected:Npn \__enumext_storing_set:n #1
1803 {
1804   \tl_set:Nx \l__enumext_store_name_tl {#1}
1805   \tl_if_empty:NTF \l__enumext_store_name_tl
1806   {
1807     \bool_lazy_or:nnT
1808     { \l__enumext_standar_first_bool } { \l__enumext_starred_first_bool }
1809     {
1810       \msg_error:nnV { enumext } { save-ans-empty } \g__enumext_envir_name_tl
1811     }
1812   }
1813   {
1814     \bool_lazy_or:nnT
1815     { \l__enumext_standar_first_bool } { \l__enumext_starred_first_bool }
1816     {
1817       \__enumext_start_save_ans_msg:
1818       \__enumext_storing_exec:
1819     }
1820   }
1821 }

```

The function `__enumext_storing_exec:` will set to true the variable `\l__enumext_store_active_bool` which activates the use of the `\anskey` command and the `keyans`, `keyans*` and `keyanspic` environments and will set to true the variable `\l__enumext_check_answers_bool` used for checking answers by the `check-ans` and `no-store` keys, copy `{<store name>}` into the global variable `\g__enumext_store_name_tl` and execute the function `__enumext_anskey_env_make:V` creating the environment `anskey*` (§11.30). The `<prop list>` `\g__enumext_series_<store name>_prop` and the `<sequence>` `\g__enumext_series_<store name>_seq` will be created globally to “*store content*” in case they do not exist together with the integer variable `\g__enumext_series_<store name>_int` used by the keys `resume` and `resume*`.

```

1822 \cs_new_protected:Nn \__enumext_storing_exec:

```



```

1823 {
1824   \bool_set_true:N \__enumext_store_active_bool
1825   \bool_set_true:N \__enumext_check_answers_bool
1826   \tl_gset:NV \g__enumext_store_name_tl \__enumext_store_name_tl
1827   \__enumext_anskey_env_make:V \__enumext_store_name_tl
1828   \prop_if_exist:cF { g__enumext_ \__enumext_store_name_tl _prop }
1829   {
1830     \msg_log:nnV { enumext } { store-prop } \__enumext_store_name_tl
1831     \prop_new:c { g__enumext_ \__enumext_store_name_tl _prop }
1832   }
1833   \seq_if_exist:cF { g__enumext_ \__enumext_store_name_tl _seq }
1834   {
1835     \msg_log:nnV { enumext } { store-seq } \__enumext_store_name_tl
1836     \seq_new:c { g__enumext_ \__enumext_store_name_tl _seq }
1837   }
1838   \int_if_exist:cF { g__enumext_resume_ \__enumext_store_name_tl _int }
1839   {
1840     \msg_log:nnV { enumext } { store-int } \__enumext_store_name_tl
1841     \int_new:c { g__enumext_resume_ \__enumext_store_name_tl _int }
1842   }
1843 }

```

(End of definition for `__enumext_storing_set:n` and `__enumext_storing_exec:.`)

11.25.3 The check answer mechanism

The mechanism for checking that all questions are answered follows this logic:

If the line begins with `\item` or `\item*` and does NOT *open a nested environment*, each `\item` or `\item*` must contain a *single* execution of the `\anskey` command, i.e. the counter of the executions of the `\anskey` command must be equal to the counter associated with the sum of executions of `\item` and `\item*`.

If the line begins with `\item` or `\item*` and *opens a nested environment* each `\item` or `\item*` in the nested environment must have a *single* execution of the `\anskey` command and the counter associated to the sum of `\item` and `\item*` executions must decrementing by “one” to maintain equality.

In order for the mechanism for the check-answer to work (not counting `keyans`, `keyans*` and `keyanspic`) we need:

1. We must keep track of the total number of `\item` and `\item*` (enumerated) that appear within the environment including the nested levels.
2. We must keep track of the total number of `\item` and `\item*` (enumerated) that appear per level of nesting.
3. Keeping track of the number of times the environment nests.

The integer variable associated to the sum of each `\item` and `\item*` in the environment `\g__enumext_item_number_int` must match the integer variable `\g__enumext_item_anskey_int` associated to the execution of the command `\anskey`. We analyze the cases:

- a) If the list only has one level the number of `\item` + `\item*` = `\anskey`
- b) If the list has *nested levels*, for each level of nesting we need to decrementing by one (for the `\item` or `\item*` that opens the nest) so that the account remains the same.

With `keyans`, `keyans*` and `keyanspic` it is enough to increase in one the integer of `\anskey`. The integers created must be global if they are not lost in the interior levels of nesting and to execute the test we will use a “hook” function after closing the first level of the environment.

11.25.4 Setting check-ans and no-store keys

Now we define the keys `check-ans` and `no-store` for all levels of `enumext` and `enumext*` environments.

```

check-ans no-store 1844 \cs_set_protected:Npn \__enumext_tmp:n #1
1845 {
1846   \keys_define:nn { enumext / #1 }
1847   {
1848     check-ans .bool_set:N = \__enumext_check_ans_key_bool,
1849     check-ans .initial:n = false,
1850     check-ans .value_required:n = true,
1851     no-store .code:n = {
1852       \bool_set_false:N \__enumext_check_answers_bool
1853       \bool_set_false:N \__enumext_check_ans_key_bool
1854     },
1855     no-store .value_forbidden:n = true,

```

```

1856     }
1857 }
1858 \clist_map_inline:nn
1859 {
1860     level-1, level-2, level-3, level-4, enumext*
1861 }
1862 { \__enumext_tmp:n {#1} }

```

(End of definition for *check-ans* and *no-store*.)

11.25.5 Set-up check answer mechanism

The function `__enumext_check_ans_active:` will first check the state of the variable `\l__enumext_store_name_tl`, that is, the *save-ans* key is active, if so it will check the state of the variable `\l__enumext_check_answers_bool` handled by the key *no-store* and will execute the function `__enumext_check_ans_level:` only if “*true*”, i.e. the key *no-store* is not active.

```

1863 \cs_new_protected:Nn \__enumext_check_ans_active:
1864 {
1865     \tl_if_empty:NF \l__enumext_store_name_tl
1866     {
1867         \bool_if:NT \l__enumext_check_answers_bool
1868         {
1869             \__enumext_check_ans_level:
1870         }
1871     }
1872 }

```

The function `__enumext_check_ans_level:` will decrement by “*one*” the value of the variable `\g__enumext_item_number_int` which keeps track of the executions of `\item` and `\item*` for each level of nesting of the environment *enumext*, taking into account whether it is nested within *enumext** or the opposite and set `\l__enumext_item_number_bool` to “*false*”.

```

1873 \cs_new_protected:Nn \__enumext_check_ans_level:
1874 {
1875     \int_case:nn { \l__enumext_level_int }
1876     {
1877         { 1 }{
1878             \bool_lazy_all:nT
1879             {
1880                 { \bool_if_p:N \g__enumext_starred_bool }
1881                 { \int_compare_p:nNn { \l__enumext_level_h_int } = { 1 } }
1882             }
1883             {
1884                 \int_gdecr:N \g__enumext_item_number_int
1885                 \bool_set_false:N \l__enumext_item_number_bool
1886             }
1887         }
1888         { 2 }{
1889             \int_gdecr:N \g__enumext_item_number_int
1890             \bool_set_false:N \l__enumext_item_number_bool
1891         }
1892         { 3 }{
1893             \int_gdecr:N \g__enumext_item_number_int
1894             \bool_set_false:N \l__enumext_item_number_bool
1895         }
1896         { 4 }{
1897             \int_gdecr:N \g__enumext_item_number_int
1898             \bool_set_false:N \l__enumext_item_number_bool
1899         }
1900     }

```

We should only execute this if *enumext** is nested in the first level of *enumext*, for the rest of the cases the value of `\g__enumext_item_number_int` is already decreased.

```

1901     \int_case:nn { \l__enumext_level_h_int }
1902     {
1903         { 1 }{
1904             \bool_lazy_all:nT
1905             {
1906                 { \bool_if_p:N \g__enumext_standar_bool }
1907                 { \int_compare_p:nNn { \l__enumext_level_int } = { 1 } }
1908             }
1909             {
1910                 \int_gdecr:N \g__enumext_item_number_int

```

```

1911         \bool_set_false:N \l__enumext_item_number_bool
1912     }
1913 }
1914 }
1915 }

```

(End of definition for \l__enumext_check_ans_active: and \l__enumext_check_ans_level:.)

\l__enumext_check_ans_key_hook:

The function \l__enumext_check_ans_key_hook: will *export* the status of the local variable \l__enumext_check_ans_key_bool to the global variable \g__enumext_check_ans_key_bool only if the key `check-ans` is active.

```

1916 \cs_new_protected:Nn \l__enumext_check_ans_key_hook:
1917 {
1918     \bool_lazy_and:nnT
1919     { \bool_if_p:N \l__enumext_check_ans_key_bool }
1920     { \bool_if_p:N \g__enumext_standar_bool }
1921     {
1922         \bool_gset_true:N \g__enumext_check_ans_key_bool
1923     }
1924     \bool_lazy_and:nnT
1925     { \bool_if_p:N \l__enumext_check_ans_key_bool }
1926     { \bool_if_p:N \g__enumext_starred_bool }
1927     {
1928         \bool_gset_true:N \g__enumext_check_ans_key_bool
1929     }
1930 }

```

(End of definition for \l__enumext_check_ans_key_hook:.)

\l__enumext_item_answer_diff:

The function \l__enumext_item_answer_diff: will set the value of the variable \g__enumext_item_answer_diff_int which is used by the functions \l__enumext_check_ans_show: for the key `save-ans` and by the function \l__enumext_check_ans_log: by the internal “*check answer*” mechanism. This function will be passed to the function \l__enumext_execute_after_env:.

```

1931 \cs_new_protected:Nn \l__enumext_item_answer_diff:
1932 {
1933     \int_gset:Nn \g__enumext_item_answer_diff_int
1934     {
1935         \int_sign:n { \g__enumext_item_number_int - \g__enumext_item_anskey_int }
1936     }
1937 }

```

(End of definition for \l__enumext_item_answer_diff:.)

\l__enumext_check_ans_show:

\l__enumext_check_ans_msg_less:

\l__enumext_check_ans_msg_same_ok:

\l__enumext_check_ans_msg_greater:

The function \l__enumext_check_ans_show: will be executed within the function \l__enumext_execute_after_env: when the key `check-ans` is active, that is, when \g__enumext_check_ans_key_bool is “*true*” and will return the appropriate message according to the value of \g__enumext_item_answer_diff_int set by the function \l__enumext_item_answer_diff:.

```

1938 \cs_new_protected:Nn \l__enumext_check_ans_show:
1939 {
1940     \int_case:nn { \g__enumext_item_answer_diff_int }
1941     {
1942         { -1 } { \l__enumext_check_ans_msg_less: }
1943         { 0 } { \l__enumext_check_ans_msg_same_ok: }
1944         { 1 } { \l__enumext_check_ans_msg_greater: }
1945     }
1946 }
1947 \cs_new_protected:Nn \l__enumext_check_ans_msg_less:
1948 {
1949     \msg_warning:nneee { enumext } { item-less-answer } { \g__enumext_store_name_tl }
1950     { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
1951 }
1952 \cs_new_protected:Nn \l__enumext_check_ans_msg_same_ok:
1953 {
1954     \msg_term:nneee { enumext } { items-same-answer } { \g__enumext_store_name_tl }
1955     { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
1956 }
1957 \cs_new_protected:Nn \l__enumext_check_ans_msg_greater:
1958 {
1959     \msg_warning:nneee { enumext } { item-greater-answer } { \g__enumext_store_name_tl }
1960     { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
1961 }

```

(End of definition for `__enumext_check_ans_show:` and others.)

```
\__enumext_check_ans_log:
\__enumext_check_ans_log_msg_less:
\__enumext_check_ans_log_msg_same_ok:
\__enumext_check_ans_log_msg_greater:
```

The function `__enumext_check_ans_log:` will be executed within the function `__enumext_execute_after_env:` when the key `check-ans` is not active, that is, when `\g__enumext_check_ans_key_bool` is “*false*” and write in the log the appropriate message according to the value of `\g__enumext_item_answer_diff_int` set by the function `__enumext_item_answer_diff:`.

```
1962 \cs_new_protected:Nn \__enumext_check_ans_log:
1963 {
1964   \int_case:nn { \g__enumext_item_answer_diff_int }
1965   {
1966     { -1 } { \__enumext_check_ans_log_msg_less: }
1967     { 0 } { \__enumext_check_ans_log_msg_same_ok: }
1968     { 1 } { \__enumext_check_ans_log_msg_greater: }
1969   }
1970 }
1971 \cs_new_protected:Nn \__enumext_check_ans_log_msg_less:
1972 {
1973   \msg_log:nneee { enumext } { item-less-answer } { \g__enumext_store_name_tl }
1974   { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
1975 }
1976 \cs_new_protected:Nn \__enumext_check_ans_log_msg_same_ok:
1977 {
1978   \msg_log:nneee { enumext } { items-same-answer } { \g__enumext_store_name_tl }
1979   { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
1980 }
1981 \cs_new_protected:Nn \__enumext_check_ans_log_msg_greater:
1982 {
1983   \msg_log:nneee { enumext } { item-greater-answer } { \g__enumext_store_name_tl }
1984   { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
1985 }
```

(End of definition for `__enumext_check_ans_log:` and others.)

11.25.6 Check for `\item*` and `\anspic*` commands

```
\__enumext_check_starred_cmd:n
```

The function `__enumext_check_starred_cmd:n` performs an extra check for the `keyans`, `keyans*` and `keyanspic` environments. Unlike the check executed by `check-ans` key this one is not controlled by any key, it is intended to prevent the forgetting of `\item*` or `\anspic*` in these environments.

```
1986 \cs_new_protected:Npn \__enumext_check_starred_cmd:n #1
1987 {
1988   \int_compare:nNnT
1989   { \g__enumext_check_starred_cmd_int } = { 0 }
1990   {
1991     \msg_warning:nnnV
1992     { enumext } { missing-starred } { #1 } \l__enumext_check_start_line_env_tl
1993   }
1994   \int_compare:nNnT
1995   { \g__enumext_check_starred_cmd_int } > { 1 }
1996   {
1997     \msg_warning:nnnV
1998     { enumext } { many-starred } { #1 } \l__enumext_check_start_line_env_tl
1999   }
2000   \int_gzero:N \g__enumext_check_starred_cmd_int
2001   \tl_clear:N \l__enumext_check_start_line_env_tl
2002 }
```

(End of definition for `__enumext_check_starred_cmd:n`.)

11.26 Keys and functions associated with storage

We add the keys `wrap-ans`, `wrap-opt`, `save-sep`, `mark-ans`, `mark-pos`, `show-ans`, `show-pos`, `mark-ref` and `save-ref` related to the “*storage system*” and internal mechanism of “*label and ref*” only at the *first level* of `enumext` and `enumext*`.

```
2003 \cs_set_protected:Npn \__enumext_tmp:n #1
2004 {
2005   \keys_define:nn { enumext / #1 }
2006   {
2007     wrap-ans .cs_set_protected:Np = \__enumext_anskey_wrapper:n ##1,
2008     wrap-ans .initial:n = \fbox{##1},
2009     wrap-ans .value_required:n = true,
2010     wrap-opt .cs_set_protected:Np = \__enumext_keyans_wrapper_opt:n ##1,
2011     wrap-opt .initial:n = [{##1}],
```

```

2012     wrap-opt    .value_required:n = true,
2013     save-sep    .tl_set:N = \l__enumext_store_keyans_item_opt_sep_tl,
2014     save-sep    .initial:n = {, ~ },
2015     save-sep    .value_required:n = true,
2016     mark-ans    .tl_set:N = \l__enumext_mark_answer_sym_tl,
2017     mark-ans    .initial:n = \textasteriskcentered,
2018     mark-ans    .value_required:n = true,
2019     mark-pos    .choice:,
2020     mark-pos / left    .code:n = \str_set:Nn \l__enumext_mark_position_str { l },
2021     mark-pos / right   .code:n = \str_set:Nn \l__enumext_mark_position_str { r },
2022     mark-pos / unknown .code:n =
2023         \msg_error:nnee { enumext } { unknown-choice }
2024         { mark-pos } { left, ~ right } { \exp_not:n {#1} },
2025     mark-pos    .initial:n = right,
2026     mark-pos    .value_required:n = true,
2027     show-ans    .bool_set:N = \l__enumext_show_answer_bool,
2028     show-ans    .initial:n = false,
2029     show-ans    .value_required:n = true,
2030     show-pos    .bool_set:N = \l__enumext_show_position_bool,
2031     show-pos    .initial:n = false,
2032     show-pos    .value_required:n = true,
2033     mark-ref    .tl_set:N = \l__enumext_mark_ref_sym_tl,
2034     mark-ref    .initial:n = \textasteriskcentered,
2035     mark-ref    .value_required:n = true,
2036     save-ref    .bool_set:N = \l__enumext_store_ref_key_bool,
2037     save-ref    .initial:n = false,
2038     save-ref    .value_required:n = true,
2039 }
2040 }
2041 \clist_map_inline:nn { level-1, enumext* } { \l__enumext_tmp:n {#1} }

```

(End of definition for wrap-ans and others.)

mark-pos For the `keyans` and `keyans*` environments we will only add the keys mark-pos, show-ans and show-pos.
show-ans
show-pos

```

2042 \cs_set_protected:Npn \l__enumext_tmp:n #1
2043 {
2044     \keys_define:nn { enumext / #1 }
2045     {
2046         mark-pos .choice:,
2047         mark-pos / left .code:n = \str_set:Nn \l__enumext_mark_position_str { l },
2048         mark-pos / right .code:n = \str_set:Nn \l__enumext_mark_position_str { r },
2049         mark-pos .initial:n = right,
2050         mark-pos .value_required:n = true,
2051         show-ans .bool_set:N = \l__enumext_show_answer_bool,
2052         show-ans .initial:n = false,
2053         show-ans .value_required:n = true,
2054         show-pos .bool_set:N = \l__enumext_show_position_bool,
2055         show-pos .initial:n = false,
2056         show-pos .value_required:n = true,
2057     }
2058 }
2059 \clist_map_inline:nn { keyans, keyans* } { \l__enumext_tmp:n {#1} }

```

(End of definition for mark-pos, show-ans, and show-pos.)

11.26.1 Store optional arguments of the environments

The idea behind “storing” in the *⟨sequence⟩* is to have a copy of the structure of the environment in which the key `save-ans` is being executed so we must capture the optional arguments passed to the levels of the environment in which it is executed and “storing” them.

```

\l__enumext_store_active_keys:n
\l__enumext_store_active_keys_vii:n

```

The functions `\l__enumext_store_active_keys:n` and `\l__enumext_store_active_keys_vii:n` will be responsible for “storing” the *⟨keys⟩* filtered from the optional arguments of the environment in which the key `save-ans` is executed and the levels within this for the `enumext` and `enumext*` environments. We will execute this function only if the variable `\l__enumext_store_save_key_X_bool` is false, that is, the key `store-key` is not active, establishing the variable `\l__enumext_store_save_key_X_tl` with the filtered *⟨keys⟩*.

```

2060 \cs_new_protected:Npn \l__enumext_store_active_keys:n #1
2061 {
2062     \bool_if:cF { \l__enumext_store_save_key_ \l__enumext_level: _bool }

```

```

2063     {
2064         \tl_clear:c { l__enumext_save_key_ \__enumext_level: _tl }
2065         \tl_set:ce
2066             { l__enumext_store_save_key_ \__enumext_level: _tl }
2067             { \__enumext_filter_save_key:n {#1} }
2068     }
2069 }
2070 \cs_new_protected:Npn \__enumext_store_active_keys_vii:n #1
2071 {
2072     \bool_if:NF \__enumext_store_save_key_vii_bool
2073     {
2074         \tl_clear:N \__enumext_store_save_key_vii_tl
2075         \tl_set:Ne \__enumext_store_save_key_vii_tl { \__enumext_filter_save_key:n {#1} }
2076     }
2077 }

```

(End of definition for __enumext_store_active_keys:n and __enumext_store_active_keys_vii:n.)

11.26.2 Setting save-key key

Since this list structure will be stored in the *sequence* established by the `save-ans` key when executing `\anskey`, we will not be able to modify it. The best thing here is to have a key that allows you to modify the optional argument of the list stored in the *sequence*.

`save-key` The values set by this key passed in the optional arguments of the `enumext` and `enumext*` environments will override the values of the `__enumext_store_save_key_X_tl` variable set by the functions `__enumext_store_active_keys:n` and `__enumext_store_active_keys_vii:n`.

Define the key `save-key` for all levels of `enumext` and `enumext*` environments.

```

2078 \cs_set_protected:Npn \__enumext_tmp:n #1
2079 {
2080     \keys_define:nn { enumext / enumext* }
2081     {
2082         save-key .code:n = \__enumext_parse_save_key_vii:n {##1},
2083         save-key .value_required:n = true,
2084     }
2085     \keys_define:nn { enumext / #1 }
2086     {
2087         save-key .code:n = \__enumext_parse_save_key:n {##1},
2088         save-key .value_required:n = true,
2089     }
2090 }
2091 \clist_map_inline:nn { level-1, level-2, level-3, level-4 } { \__enumext_tmp:n {#1} }

```

(End of definition for `save-key`.)

`__enumext_parse_save_key:n` `__enumext_parse_save_key_vii:n` The functions `__enumext_parse_save_key:n` and `__enumext_parse_save_key_vii:n` will be responsible for storing the filtered *keys* in the variable `__enumext_store_save_key_X_tl` for `enumext` and `enumext*`.

```

2092 \cs_new_protected:Npn \__enumext_parse_save_key:n #1
2093 {
2094     \bool_set_true:c { l__enumext_store_save_key_ \__enumext_level: _bool }
2095     \tl_clear:c { l__enumext_save_key_ \__enumext_level: _tl }
2096     \tl_set:ce
2097         { l__enumext_store_save_key_ \__enumext_level: _tl }
2098         { \__enumext_filter_save_key:n {#1} }
2099 }
2100 \cs_new_protected:Npn \__enumext_parse_save_key_vii:n #1
2101 {
2102     \bool_set_true:N \__enumext_store_save_key_vii_bool
2103     \tl_clear:N \__enumext_store_save_key_vii_tl
2104     \tl_set:Ne \__enumext_store_save_key_vii_tl { \__enumext_filter_save_key:n {#1} }
2105 }

```

(End of definition for __enumext_parse_save_key:n and __enumext_parse_save_key_vii:n.)

11.26.3 Internal functions to store optional arguments

The function `__enumext_filter_save_key:n` will be in charge of filtering the *⟨keys⟩* we want to *store* in *⟨sequence⟩* where *{#1}* represents the optional value passed to the environment.

```

2106 \cs_new:Npn \__enumext_filter_save_key:n #1
2107 {
2108   \use:e
2109   {
2110     \keyval_parse:NNn
2111     \__enumext_filter_save_key_key:n
2112     \__enumext_filter_save_key_pair:nn {#1}
2113   }
2114 }
```

The function `__enumext_filter_save_key_key:n` will be responsible for filtering the *⟨keys⟩* that are passed “*without value*” by excluding the `resume`, `resume*`, `no-store` and `base-fix` keys.

```

2115 \cs_new:Npn \__enumext_filter_save_key_key:n #1
2116 {
2117   \str_case:nnF {#1}
2118   {
2119     { resume } {} { resume* } {} { no-store } {} { base-fix } {}
2120   }
2121   { , { \exp_not:n {#1} } }
2122 }
```

The function `__enumext_filter_save_key_pair:nn` will be responsible for filtering the *⟨keys⟩* that are passed “*with value*” by excluding the `series`, `resume`, `save-ans`, `save-ref`, `check-ans`, `show-ans`, `save-pos`, `wrap-ans`, `mark-ans`, `wrap-opt`, `save-sep`, `mark-ref`, `mini-env`, `mini-sep`, `mini-right` and `mini-right*` keys.

```

2123 \cs_new:Npn \__enumext_filter_save_key_pair:nn #1#2
2124 {
2125   \str_case:nnF {#1}
2126   {
2127     { series } {} { resume } {} { save-ans } {} { save-ref } {}
2128     { save-key } {} { check-ans } {} { show-ans } {} { show-pos } {}
2129     { wrap-ans } {} { mark-ans } {} { wrap-opt } {} { save-sep } {}
2130     { mark-ref } {} { mini-env } {} { mini-sep } {} { mini-right } {}
2131     { mini-right* } {}
2132   }
2133   { , { \exp_not:n {#1} } } = { \exp_not:n {#2} } }
2134 }
```

(End of definition for `__enumext_filter_save_key:n`, `__enumext_filter_save_key_key:n`, and `__enumext_filter_save_key_pair:nn`.)

11.26.4 Function for storing content in prop list

The function `__enumext_store_addto_prop:n` stores the content in *⟨prop list⟩* defined by `save-ans` key. The “*stored content*” is retrieved by means of the `\getkeyans` command.

The form in which the content is “*stored*” in the *⟨prop list⟩* is *{⟨position⟩}{⟨content⟩}*. This function is used by `\anskey` in `enumext` and `enumext*` environments, `\item*` in `keyans` and `keyans*` environments and `\anspic*` in `keyanspic` environment.

```

2135 \cs_new_protected:Npn \__enumext_store_addto_prop:n #1
2136 {
2137   \prop_gput_if_not_in:cen { g__enumext_ \l__enumext_store_name_tl _prop }
2138   {
2139     \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } + 1 }
2140   }
2141   { #1 }
2142 }
2143 \cs_generate_variant:Nn \__enumext_store_addto_prop:n { V, e }
```

(End of definition for `__enumext_store_addto_prop:n`.)

11.26.5 Function for storing content in sequence

The function `__enumext_store_addto_seq:n` stores the content in *⟨sequence⟩* defined by `save-ans` key. This function is used by `\anskey` in `enumext`, `\item*` in `keyans` and `\anspic` in `keyanspic`.

The form in which the content is stored in *⟨sequence⟩* is in a internal `enumext` or `enumext*` environments with the *same structure* in which the command was executed.

The “*stored content*” is retrieved by means of the `\printkeyans` command.

```

2144 \cs_new_protected:Npn \__enumext_store_addto_seq:n #1
2145 {
```



```

2146     \seq_gput_right:cn { g__enumext_ \l__enumext_store_name_tl _seq } { #1 }
2147   }
2148   \cs_generate_variant:Nn \__enumext_store_addto_seq:n { v, V, e }

```

(End of definition for __enumext_store_addto_seq:n.)

11.26.6 Functions for storing the list structure in the sequence

The memorization structure of the list is handled by the functions __enumext_store_level_open: and __enumext_store_level_close: which are executed per level within the enumext environment.

```

2149   \cs_new_protected:Nn \__enumext_store_level_open:
2150   {
2151     \bool_if:NT \l__enumext_check_answers_bool
2152     {
2153       \tl_if_empty:cTF { l__enumext_store_save_key_ \__enumext_level: _tl }
2154       {
2155         \__enumext_store_addto_seq:n
2156         {
2157           \item \begin{enumext}
2158         }
2159       }
2160       {
2161         \tl_put_left:cn { l__enumext_store_save_key_ \__enumext_level: _tl }
2162         {
2163           \item \begin{enumext} [
2164         }
2165         \tl_put_right:cn { l__enumext_store_save_key_ \__enumext_level: _tl }
2166         {
2167           ]
2168         }
2169         \__enumext_store_addto_seq:v { l__enumext_store_save_key_ \__enumext_level: _tl }
2170       }
2171     }
2172   }
2173   \cs_new_protected:Nn \__enumext_store_level_close:
2174   {
2175     \bool_if:NT \l__enumext_check_answers_bool
2176     {
2177       \__enumext_store_addto_seq:n { \end{enumext} }
2178     }
2179   }

```

(End of definition for __enumext_store_level_open: and __enumext_store_level_close:.)

The memorization structure of the list is handled by the functions __enumext_store_level_open_vii: and __enumext_store_level_close_vii: which are executed in the enumext* environment.

```

2180   \cs_new_protected:Nn \__enumext_store_level_open_vii:
2181   {
2182     \bool_if:NT \l__enumext_check_answers_bool
2183     {
2184       \tl_if_empty:NTF \l__enumext_store_save_key_vii_tl
2185       {
2186         \__enumext_store_addto_seq:n
2187         {
2188           \item \begin{enumext*}
2189         }
2190       }
2191       {
2192         \tl_put_left:Nn \l__enumext_store_save_key_vii_tl
2193         {
2194           \item \begin{enumext*}[
2195         }
2196         \tl_put_right:Nn \l__enumext_store_save_key_vii_tl
2197         {
2198           ]
2199         }
2200         \__enumext_store_addto_seq:V \l__enumext_store_save_key_vii_tl
2201       }
2202     }
2203   }
2204   \cs_new_protected:Nn \__enumext_store_level_close_vii:
2205   {

```

```

2206     \bool_if:NT \l__enumext_check_answers_bool
2207     {
2208         \__enumext_store_addto_seq:n { \end{enumext*} }
2209     }
2210 }

```

(End of definition for __enumext_store_level_open_vii: and __enumext_store_level_close_vii:.)

11.26.7 Function for show marks and position

__enumext_print_keyans_box:NN
__enumext_print_keyans_box:cc

The function __enumext_print_keyans_box:NN print a box in the left margin with \l__enumext_mark_answer_sym_tl used by the `wrap-ans`, `show-ans` and `show-pos` keys. The function takes two arguments:

#1: \l__enumext_labelwidth_X_dim
#2: \l__enumext_labelsep_X_dim

```

2211 \cs_new_protected:Nn \__enumext_print_keyans_box:NN
2212 {
2213     \mode_leave_vertical:
2214     \skip_horizontal:n { -\dim_use:N #2 }
2215     \makebox[0pt][ r ]
2216     {
2217         \makebox[ \dim_use:N #1 ] [ \l__enumext_mark_position_str ]
2218         {
2219             \tl_use:N \l__enumext_mark_answer_sym_tl
2220         }
2221     }
2222     \skip_horizontal:n { \dim_use:N #2 }
2223 }
2224 \cs_generate_variant:Nn \__enumext_print_keyans_box:NN { cc }

```

(End of definition for __enumext_print_keyans_box:NN.)

11.27 The internal label and ref

The function __enumext_store_internal_ref: handles the internal “*label and ref*” system used by the `save-ref` and `mark-ref` keys for \anskey will allow to execute \ref{<store name: position>} and will return 1.(a).i.A.

__enumext_store_internal_ref:

First we will remove the dots “.” from the current <labels>, we do not want to get double dots in our references, then we will place this in the variable \l__enumext_newlabel_arg_two_tl.

```

2225 \cs_new_protected:Nn \__enumext_store_internal_ref:
2226 {
2227     \cs_set_protected:Npn \__enumext_tmp:n ##1
2228     {
2229         \tl_set_eq:cc { l__enumext_label_copy_##1_tl } { l__enumext_label_##1_tl }
2230         \tl_reverse:c { l__enumext_label_copy_##1_tl }
2231         \tl_remove_once:cn { l__enumext_label_copy_##1_tl } { . }
2232         \tl_reverse:c { l__enumext_label_copy_##1_tl }
2233     }
2234     \clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {##1} }
2235     \cs_set:Npn \__enumext_tmp:n ##1
2236     { . \tl_use:c { l__enumext_label_copy_ \int_to_roman:n {##1} _tl } }

```

Here we need to analyse the cases where the environment is started with `enumext*` and if \anskey or `anskey*` is running alone in it or if it is running in a nested `enumext` environment within the starting environment.

```

2237 \bool_lazy_all:nT
2238 {
2239     { \bool_if_p:N \g__enumext_starred_bool }
2240     { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
2241 }
2242 {
2243     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2244     { \tl_use:N \l__enumext_label_copy_vii_tl }
2245 }
2246 \bool_lazy_all:nT
2247 {
2248     { \bool_if_p:N \l__enumext_standar_bool }
2249     { \bool_if_p:N \g__enumext_starred_bool }
2250     { \int_compare_p:nNn { \l__enumext_level_int } > { 0 } }
2251 }
2252 {

```

```

2253     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2254     {
2255         \tl_use:N \l__enumext_label_copy_vii_tl
2256         \int_step_function:nnN { 1 } { \l__enumext_level_int } \l__enumext_tmp:n
2257     }
2258 }

```

If started with `enumext` and if `\anskey` or `anskey*` is running alone in it or if it is running in a nested `enumext*` environment within the starting environment.

```

2259 \bool_lazy_all:nT
2260 {
2261     { \bool_if_p:N \l__enumext_standar_bool }
2262     { \int_compare_p:nNn { \l__enumext_level_int } > { 0 } }
2263     { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
2264     { \bool_not_p:n { \l__enumext_starred_bool } }
2265 }
2266 {
2267     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2268     {
2269         \tl_use:N \l__enumext_label_copy_i_tl
2270         \int_step_function:nnN { 2 } { \l__enumext_level_int } \l__enumext_tmp:n
2271     }
2272 }
2273 \cs_set:Npn \l__enumext_tmp:n ##1
2274 { \tl_use:c { l__enumext_label_copy_ \int_to_roman:n {##1} _tl } }
2275 \bool_lazy_all:nT
2276 {
2277     { \bool_if_p:N \l__enumext_standar_bool }
2278     { \int_compare_p:nNn { \l__enumext_level_int } > { 0 } }
2279     { \bool_not_p:n { \g__enumext_starred_bool } }
2280     { \int_compare_p:nNn { \l__enumext_level_h_int } > { 0 } }
2281 }
2282 {
2283     \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2284     {
2285         \int_step_function:nnN { 1 } { \l__enumext_level_int } \l__enumext_tmp:n
2286         . \tl_use:N \l__enumext_label_copy_vii_tl
2287     }
2288 }

```

Now we set the variable `\l__enumext_newlabel_arg_one_tl` which will contain $\langle \textit{store name} : \textit{position} \rangle$.

```

2289 \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
2290 {
2291     \l__enumext_store_name_tl \c_colon_str
2292     \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
2293 }

```

Now execute the function `\l__enumext_newlabel:nn` and save the result in the variable `\l__enumext_write_aux_file_tl` and finally we write in the `.aux` file.

```

2294 \tl_put_right:Ne \l__enumext_write_aux_file_tl
2295 {
2296     \l__enumext_newlabel:nn
2297     { \exp_not:V \l__enumext_newlabel_arg_one_tl }
2298     { \l__enumext_newlabel_arg_two_tl }
2299 }
2300 \l__enumext_write_aux_file_tl
2301 }

```

(End of definition for `\l__enumext_store_internal_ref:`)

11.28 Common functions for `\anskey` and `anskey*` environment

`\l__enumext_store_anskey_code:n` The internal function `\l__enumext_store_anskey_code:n` first we pass the $\langle \textit{argument} \rangle$ to the $\langle \textit{prop list} \rangle$, then checks the state of the variable `\l__enumext_store_ref_key_bool` handled by the `save-ref` key and will call the function `\l__enumext_store_internal_ref:` for the internal “*label and ref*” system. Followed by this if the `show-ans` or `show-pos` keys are active we will show the “*wrapped*” $\langle \textit{argument} \rangle$.

```

2302 \cs_new_protected:Npn \l__enumext_store_anskey_code:n #1
2303 {
2304     \int_gincr:N \g__enumext_item_anskey_int
2305     \l__enumext_store_addto_prop:n {#1}
2306     \bool_if:NT \l__enumext_store_ref_key_bool
2307     {

```

```

2308     \l__enumext_store_internal_ref:
2309   }
2310   \l__enumext_anskey_show_wrap_left:n { #1 }

```

Now we start processing the [$\langle key = val \rangle$] passed to the command to build our $\backslash item$ in the variable $\backslash l_enumext_store_anskey_arg_tl$ which we will “store” in the $\langle sequence \rangle$. First we clear the variable $\backslash l_enumext_store_anskey_arg_tl$ and process the $\langle keys \rangle$, if the `break-col` key is present and the command is running under `enumext` (not in `enumext*`) we will add $\backslash columnbreak$ and then $\backslash item$.

```

2311   \tl_clear:N \l__enumext_store_anskey_arg_tl
2312   \bool_lazy_and:nnT
2313     { \bool_if_p:N \l__enumext_store_columns_break_bool }
2314     { \bool_not_p:n { \l__enumext_starred_bool } }
2315   {
2316     \tl_put_left:Nn \l__enumext_store_anskey_arg_tl { \columnbreak }
2317   }
2318   \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { \item }

```

If the `item-join` key is present and the command is running under `enumext*` we will add ($\langle number \rangle$) to $\backslash l_enumext_store_anskey_arg_tl$.

```

2319   \bool_lazy_and:nnT
2320     { \bool_not_p:n { \l__enumext_starred_bool } }
2321     { \int_compare_p:nNn { \l__enumext_store_item_join_int } > { 1 } }
2322   {
2323     \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2324     {
2325       ( \exp_not:V \l__enumext_store_item_join_int )
2326     }
2327   }

```

And now we will review the keys `item-star`, `item-sym*` and `item-pos*` and pass them to $\backslash l_enumext_store_anskey_arg_tl$ along with the $\langle argument \rangle$ for $\backslash anskey$ or $\langle body \rangle$ for `anskey*`.

```

2328   \bool_if:NTF \l__enumext_store_item_star_bool
2329   {
2330     \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { * }
2331     \tl_if_empty:NF \l__enumext_store_item_symbol_tl
2332     {
2333       \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2334       {
2335         [ \exp_not:V \l__enumext_store_item_symbol_tl ]
2336       }
2337     }
2338     \dim_compare:nT
2339     {
2340       \l__enumext_store_item_symbol_sep_dim != \c_zero_dim
2341     }
2342     {
2343       \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2344       {
2345         [ \exp_not:V \l__enumext_store_item_symbol_sep_dim ]
2346       }
2347     }
2348     \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#1}
2349   }
2350   {
2351     \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#1}
2352   }

```

Finally we check if the `save-ref` key are active along with the `hyperref` package load, if both conditions are met, it will create the $\backslash hyperlink$ with `symbol` set by `mark-ref` key and then store in $\langle sequence \rangle$.

```

2353   \bool_lazy_and:nnT
2354     { \bool_if_p:N \l__enumext_store_ref_key_bool }
2355     { \bool_if_p:N \l__enumext_hyperref_bool }
2356   {
2357     \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
2358     {
2359       \hfill \exp_not:N \hyperlink { \exp_not:V \l__enumext_newlabel_arg_one_tl }
2360       { \exp_not:V \l__enumext_mark_ref_sym_tl }
2361     }
2362   }
2363   \l__enumext_store_addto_seq:V \l__enumext_store_anskey_arg_tl
2364 }

```

(End of definition for $\backslash l_enumext_store_anskey_code:n$.)

_enumext_anskey_show_wrap_arg:n

The function _enumext_anskey_show_wrap_arg:n “wraps” the $\langle argument \rangle$ passed to _anskey and the $\langle body \rangle$ for anskey* when using the wrap-ans key.

```

2365 \cs_new_protected:Npn \_enumext_anskey_show_wrap_arg:n #1
2366 {
2367   \par
2368   \bool_if:NT \l__enumext_starred_bool
2369   {
2370     \cs_set:Nn \_enumext_level: { vii }
2371   }
2372   \_enumext_print_keyans_box:cc
2373   { \_enumext_labelwidth_ \_enumext_level: _dim }
2374   { \_enumext_labelsep_ \_enumext_level: _dim }
2375   \_enumext_anskey_wrapper:n { #1 }
2376 }

```

(End of definition for _enumext_anskey_show_wrap_arg:n.)

_enumext_anskey_show_wrap_left:n

The function _enumext_anskey_show_wrap_left:n will show the “mark” defined by the mark-ans key or the “position” of the content stored in the $\langle prop list \rangle$ when using the show-pos key on the left margin next to the “wraps” $\langle argument \rangle$ passed to _anskey and the $\langle body \rangle$ in anskey* on the right side when using the show-ans key.

```

2377 \cs_new_protected:Npn \_enumext_anskey_show_wrap_left:n #1
2378 {
2379   \bool_if:NT \l__enumext_show_answer_bool
2380   {
2381     \_enumext_anskey_show_wrap_arg:n { #1 }
2382   }
2383   \bool_if:NT \l__enumext_show_position_bool
2384   {
2385     \tl_set:Nx \l__enumext_mark_answer_sym_tl
2386     {
2387       \group_begin:
2388       \exp_not:N \normalfont
2389       \exp_not:N \footnotesize [ \int_eval:n
2390       {
2391         \prop_count:c { g__enumext_ \_enumext_store_name_tl _prop }
2392       }
2393       ]
2394       \group_end:
2395     }
2396     \_enumext_anskey_show_wrap_arg:n { #1 }
2397   }
2398 }

```

(End of definition for _enumext_anskey_show_wrap_left:n.)

11.29 The command _anskey

Since we will be “storing content” in a list environment within $\langle sequences \rangle$ and can (more or less) manage the options passed to each level, it is necessary that we have a little more control over _item when storing.

The _anskey command will cover this point and give it similar behaviour to that of _item in the enumext and enumext* environments executed as follows _anskey[$\langle key = val \rangle$]{ $\langle content \rangle$ }.

_enumext_anskey_unknown:n

First we’ll add the keys break-col, item-join, item-star, item-sym* and item-pos*.

_enumext_anskey_unknown:n

```

2399 \keys_define:nn { enumext / anskey }
2400 {
2401   break-col .bool_set:N = \l__enumext_store_columns_break_bool,
2402   break-col .default:n = true,
2403   break-col .value_forbidden:n = true,
2404   item-join .int_set:N = \l__enumext_store_item_join_int,
2405   item-join .value_required:n = true,
2406   item-star .bool_set:N = \l__enumext_store_item_star_bool,
2407   item-star .default:n = true,
2408   item-star .value_forbidden:n = true,
2409   item-sym* .tl_set:N = \l__enumext_store_item_symbol_tl,
2410   item-sym* .value_required:n = true,
2411   item-pos* .dim_set:N = \l__enumext_store_item_symbol_sep_dim,
2412   item-pos* .value_required:n = true,
2413   unknown .code:n = { \_enumext_anskey_unknown:n {#1} },
2414 }

```

The `<keys>` are stored in `\l_keys_key_str` and the value (if any) is passed as an argument to the function `__enumext_anskey_unknown:n`.

```

2415 \cs_new_protected:Npn \__enumext_anskey_unknown:n #1
2416 {
2417   \exp_args:NV \__enumext_anskey_unknown:nn \l_keys_key_str {#1}
2418 }
2419 \cs_new_protected:Npn \__enumext_anskey_unknown:nn #1 #2
2420 {
2421   \tl_if_blank:nTF {#2}
2422   {
2423     \msg_error:nnn { enumext } { anskey-cmd-key-unknown } {#1}
2424   }
2425   {
2426     \msg_error:nnnn { enumext } { anskey-cmd-key-value-unknown } {#1} {#2}
2427   }
2428 }

```

(End of definition for `__enumext_anskey_unknown:n` and `__enumext_anskey_unknown:nn`.)

- The `\anskey` command will only be present when using the `save-ans` key in `enumext` and `enumext*` environments, otherwise it will return an error.

`\anskey` We will first call the function `__enumext_anskey_safe_outer:` to be sure where we execute the command, then we will check the state of the variable `\l__enumext_check_answers_bool` set by the key `no-store`, if is true we will increment `\g__enumext_item_anskey_int` for the internal “*check answer*” system and execute the function `__enumext_anskey_safe_inner:n` to ensure that the command is not nested and that the argument is not empty, finally search the `[<key = val>]` and call the function `__enumext_store_anskey_code:n`.

```

2429 \NewDocumentCommand \anskey { o +m }
2430 {
2431   \__enumext_anskey_safe_outer:
2432   \group_begin:
2433     \bool_if:NT \l__enumext_check_answers_bool
2434     {
2435       \tl_if_novalue:nF {#1}
2436       {
2437         \keys_set:nn { enumext / anskey } {#1}
2438       }
2439       \tl_if_blank:nTF {#2}
2440       {
2441         \msg_error:nn { enumext } { anskey-empty-arg }
2442       }
2443       {
2444         \__enumext_anskey_safe_inner:
2445         \__enumext_store_anskey_code:n {#2}
2446       }
2447     }
2448   \group_end:
2449 }

```

(End of definition for `\anskey`. This function is documented on page 12.)

11.29.1 Internal functions for the command

`__enumext_anskey_safe_outer:` The `__enumext_store_anskey_safe_outer:` function will return the appropriate messages when the command is executed outside the environment in which the `save-ans` key was activated.

`__enumext_anskey_safe_inner:`

```

2450 \cs_new_protected:Npn \__enumext_anskey_safe_outer:
2451 {
2452   \bool_if:NF \l__enumext_store_active_bool
2453   {
2454     \msg_error:nnnn { enumext } { anskey-wrong-place } { anskey } { enumext }
2455   }
2456   \int_compare:nNt { \l__enumext_keyans_level_int } = { 1 }
2457   {
2458     \msg_error:nnnn { enumext } { command-wrong-place } { anskey } { keyans }
2459   }
2460   \int_compare:nNt { \l__enumext_keyans_level_h_int } = { 1 }
2461   {
2462     \msg_error:nnnn { enumext } { command-wrong-place } { anskey } { keyans* }
2463   }
2464   \int_compare:nNt { \l__enumext_keyans_pic_level_int } = { 1 }
2465   {

```

```

2466         \msg_error:nnnn { enumext } { command-wrong-place }{ anskey }{ keyanspic }
2467     }
2468 }

```

The `__enumext_anskey_safe_inner:` function will first check if the command is nested, if preceded by a not numbered `\item` or if it is in *math mode* returning the appropriate messages.

```

2469 \cs_new_protected:Nn \__enumext_anskey_safe_inner:
2470 {
2471     \int_incr:N \__enumext_anskey_level_int
2472     \int_compare:nNt { \__enumext_anskey_level_int } > { 1 }
2473     {
2474         \msg_error:nn { enumext } { anskey-nested }
2475     }
2476     \bool_if:NF \__enumext_item_number_bool
2477     {
2478         \msg_error:nn { enumext } { anskey-unnumber-item }
2479     }
2480     \mode_if_math:T
2481     {
2482         \msg_error:nne { enumext } { anskey-math-mode } { \c_backslash_str anskey }
2483     }
2484 }

```

(End of definition for `__enumext_anskey_safe_outer:` and `__enumext_anskey_safe_inner:`.)

11.30 The environment anskey*

Managing *verbatim content* in an environment is quite complicated, I learned that when creating the `scontents` package, so to be able to have support at this point it is best to play a little with the internal code of `scontents` and *hooks*. Some considerations I should have here before implementing this:

- If some package, class or user has defined the environment with the same name somewhere in the document it would be a problem, you would not know what argument has been passed to `store-env`, if you are using the key `print-env` or the `write-out` key, sure, I can detect and modify it within the `enumext` and `enumext*` environments, but it would look strange not to have some keys available when running within these environments.
- A better (perhaps a bit paranoid) option is to define it within the environment in which the `save-ans` key is executed. and have it available only when that key is executed, here I would have absolute control of the *(keys)* and I make sure that `write-out` is not used, then using *hooks after* I undefine it and using *hook before* I check if it has been created by any package, class or user and I return a error, then the user will have to see how to solve the problem.

`__enumext_undefine_anskey_env:`

The function `__enumext_undefine_anskey_env:` will undefine the environment `anskey*` and will be passed to the function `__enumext_execute_after_env:` (§11.31) which is executed after the environment in which the key `save-ans` is active.

```

2485 \cs_new_protected:Nn \__enumext_undefine_anskey_env:
2486 {
2487     \cs_undefine:c { anskey* }
2488     \cs_undefine:c { endanskey* }
2489     \cs_undefine:c { __scontents_anskey*_env_begin: }
2490     \cs_undefine:c { __scontents_anskey*_env_end: }
2491 }

```

Detection of the `anskey*` environment outside the `enumext` and `enumext*` environments.

```

2492 \__enumext_before_env:nn { enumext }
2493 {
2494     \bool_lazy_and:nnT
2495     { \int_compare_p:nNn { \__enumext_level_int } = { 0 } }
2496     { \int_compare_p:nNn { \__enumext_level_h_int } = { 0 } }
2497     {
2498         \cs_if_free:cF { __scontents_anskey*_env_begin: }
2499         {
2500             \msg_error:nnn { enumext } { anskey-env-error } { anskey* }
2501         }
2502     }
2503 }
2504 \__enumext_before_env:nn { enumext* }
2505 {
2506     \bool_lazy_and:nnT
2507     { \int_compare_p:nNn { \__enumext_level_int } = { 0 } }
2508     { \int_compare_p:nNn { \__enumext_level_h_int } = { 0 } }
2509     {

```



```

2510         \cs_if_free:cf { __scontents_anskey*_env_begin: }
2511         {
2512             \msg_error:nnn { enumext } { anskey-env-error } { anskey* }
2513         }
2514     }
2515 }

```

Detection of the `anskey*` environment inside the `keyans`, `keyans*` and `keyanspic` environments, if preceded by a not numbered `\item` or if it is in *math mode* returning the appropriate messages.

```

2516 \__enumext_before_env:nn { anskey* }
2517 {
2518     \int_compare:nNt { \l__enumext_keyans_level_int } = { 1 }
2519     {
2520         \msg_error:nnn { enumext } { anskey-env-wrong } { keyans }
2521     }
2522     \int_compare:nNt { \l__enumext_keyans_level_h_int } = { 1 }
2523     {
2524         \msg_error:nnn { enumext } { anskey-env-wrong } { keyans* }
2525     }
2526     \int_compare:nNt { \l__enumext_keyans_pic_level_int } = { 1 }
2527     {
2528         \msg_error:nnn { enumext } { anskey-env-wrong } { keyanspic }
2529     }
2530     \bool_if:NF \l__enumext_item_number_bool
2531     {
2532         \msg_error:nn { enumext } { anskey-unnumber-item }
2533     }
2534     \mode_if_math:T
2535     {
2536         \msg_error:nnn { enumext } { anskey-math-mode } { anskey* }
2537     }
2538 }

```

(End of definition for `__enumext_undefine_anskey_env:`)

`anskey*`

The function `__enumext_anskey_env_make:n` creates the environment `anskey*` (*custom version of `scontents` environment*) by setting the initial keys `store-env={⟨store name⟩}` and `print-env=false`. To maintain the *scope* of the environment and that it is only active when the key `save-ans` is active we will pass this function to the function `__enumext_storing_exec: (§11.25.1)` and we will execute it only if the variable `\l__enumext_anskey_env_bool` is true, with this we prevent it from being executed again when the environment is nested and the key `save-ans` is active, which returns an error for part of the package `scontents`.

```

2539 \cs_new_protected:Npn \__enumext_anskey_env_make:n #1
2540 {
2541     \bool_if:NT \l__enumext_anskey_env_bool
2542     {
2543         \newenvsc{anskey*}[store-env=#1,print-env=false]
2544         \__enumext_anskey_env_exec:
2545     }
2546 }
2547 \cs_generate_variant:Nn \__enumext_anskey_env_make:n { V }

```

The function `__enumext_anskey_env_define_keys:` will add the keys `break-col`, `item-join`, `item-join`, `item-star`, `item-sym*` and `item-pos*` and will leave the keys `print-env`, `store-env` and `write-out` undefined. We will apply this function using the *hook* function `__enumext_before_env:nn`.

```

2548 \cs_new_protected:Nn \__enumext_anskey_env_define_keys:
2549 {
2550     \keys_define:nn { scontents / scontents }
2551     {
2552         break-col .bool_gset:N = \g__enumext_store_columns_break_bool,
2553         break-col .default:n = true,
2554         break-col .value_forbidden:n = true,
2555         item-join .int_gset:N = \g__enumext_store_item_join_int,
2556         item-join .value_required:n = true,
2557         item-star .bool_gset:N = \g__enumext_store_item_star_bool,
2558         item-star .default:n = true,
2559         item-star .value_forbidden:n = true,
2560         item-sym* .tl_gset:N = \g__enumext_store_item_symbol_tl,
2561         item-sym* .value_required:n = true,
2562         item-pos* .dim_gset:N = \g__enumext_store_item_symbol_sep_dim,

```

```

2563         item-pos* .value_required:n = true,
2564         print-env .undefine:,
2565         store-env .undefine:,
2566         write-out .undefine:,
2567         unknown .code:n = { \__enumext_anskey_env_unknown:n {##1} },
2568     }
2569 }

```

The *⟨keys⟩* are stored in `\l_keys_key_str` and the value (if any) is passed as an argument to the function `__enumext_anskey_env_unknown:n`.

```

2570 \cs_new_protected:Npn \__enumext_anskey_env_unknown:n #1
2571 {
2572     \exp_args:NV \__enumext_anskey_env_unknown:nn \l_keys_key_str {#1}
2573 }
2574 \cs_new_protected:Npn \__enumext_anskey_env_unknown:nn #1#2
2575 {
2576     \tl_if_blank:nTF {#2}
2577     {
2578         \msg_error:nnn { enumext } { anskey-env-key-unknown } {#1}
2579     }
2580     {
2581         \msg_error:nnnn { enumext } { anskey-env-key-value-unknown } {#1} {#2}
2582     }
2583 }

```

The function `__enumext_anskey_env_reset_keys:` will leave the keys `break-col`, `item-join`, `item-join`, `item-star`, `item-sym*` and `item-pos*` undefined. We will apply this function using the *hook* function `__enumext_after_env:nn`.

```

2584 \cs_new_protected:Nn \__enumext_anskey_env_reset_keys:
2585 {
2586     \keys_define:nn { scontents / scontents }
2587     {
2588         break-col .undefine:,
2589         item-join .undefine:,
2590         item-star .undefine:,
2591         item-sym* .undefine:,
2592         item-pos* .undefine:,
2593         write-out .code:n = {
2594             \bool_set_false:N \l__scontents_storing_bool
2595             \bool_set_true:N \l__scontents_writing_bool
2596             \tl_set:Nn \l__scontents_fname_out_tl {##1}
2597         },
2598         write-out .value_required:n = true,
2599         print-env .meta:nn = { scontents } { print-env = ##1 },
2600         print-env .default:n = true,
2601         store-env .meta:nn = { scontents } { store-env = ##1 },
2602         unknown .code:n = { \__scontents_parse_environment_keys:n {##1} },
2603     }
2604 }

```

The function `__enumext_rescan_anskey_env:n` will be responsible for bringing the *⟨body⟩* of the environment saved in the sequence `\g__scontents_name_⟨store name⟩_seq` to pass it to our *sequence* and *prop list*.

```

2605 \cs_new_protected:Npn \__enumext_rescan_anskey_env:n #1
2606 {
2607     \group_begin:
2608     \int_set:Nn \tex_newlinechar:D { `^^J }
2609     \__scontents_rescan_tokens:x
2610     {
2611         \endgroup % This assumes \catcode`\=0... Things might go off otherwise.
2612         #1
2613     }
2614 }

```

(End of definition for *anskey** and others. This function is documented on page 13.)

`__enumext_anskey_env_exec:` The function `__enumext_anskey_env_exec:` will be responsible for processing all the code necessary for the execution of the environment. The first thing will be to add our *⟨keys⟩*.

```

2615 \cs_new_protected:Nn \__enumext_anskey_env_exec:
2616 {
2617     \__enumext_before_env:nn { anskey* }
2618 }

```

```

2619     \__enumext_anskey_env_define_keys:
2620 }

```

Now we will execute our actions after the `anskey*` environment is closed. We'll fetch the contents of the *environment body* that is now saved in `\g__scontents_name_⟨store name⟩_seq` and store it in the variable `\l__enumext_store_anskey_env_tl` then we execute the rest of the functions.

```

2621 \hook_if_empty:nF {env/anskey*/after}
2622 {
2623     \hook_gremove_code:nn {env/anskey*/after} { * }
2624 }
2625 \__enumext_after_env:nn { anskey* }
2626 {
2627     \__enumext_anskey_env_save_keys:
2628     \tl_clear:N \l__enumext_store_anskey_env_tl
2629     \tl_clear:N \l__enumext_store_anskey_opt_tl
2630     \bool_if:NT \l__enumext_check_answers_bool
2631     {
2632         \tl_gset:Ne \l__enumext_store_anskey_env_tl
2633         {
2634             \seq_item:ce { g__scontents_name_ \l__enumext_store_name_tl _seq } { -1 }
2635         }
2636         \regex_match:nVTF
2637         { ^\s* \z | ^\s* \u{c__scontents_hidden_space_str} \z }
2638         \l__enumext_store_anskey_env_tl
2639         {
2640             \msg_error:nn { enumext } { anskey-empty-arg }
2641         }
2642         {
2643             \__enumext_anskey_env_store:
2644         }
2645     }
2646     \__enumext_anskey_env_clean_vars:
2647     \__enumext_anskey_env_reset_keys:
2648 }
2649 }

```

• The use of `\hook_gremove_code:nn` is necessary here, otherwise the `{⟨code⟩}` passed to `__enumext_after_env:nn{anskey*}` will be accumulated for each execution. The last function `__enumext_anskey_env_reset_keys:` is necessary so as not to hinder any `scontents` environment running within `enumext` or `enumext*`.

(End of definition for `__enumext_anskey_env_exec:.`)

```

\__enumext_anskey_env_save_keys:
\__enumext_anskey_env_store:
\__enumext_anskey_env_clean_vars:

```

The function `__enumext_anskey_env_save_keys:` processing the `[⟨key = val⟩]` passed to the environment and save this in the variable `\l__enumext_store_anskey_opt_tl`. If the `break-col` key is present and the environment is running under `enumext` (not in `enumext*`) we will add the key `break-col`.

```

2650 \cs_new_protected:Nn \__enumext_anskey_env_save_keys:
2651 {
2652     \bool_lazy_and:nnT
2653     { \bool_if_p:N \g__enumext_store_columns_break_bool }
2654     { \bool_not_p:n { \l__enumext_starred_bool } }
2655     {
2656         \tl_put_left:Ne \l__enumext_store_anskey_opt_tl { ,break-col, }
2657     }

```

If the `item-join` key is present and the command is running under `enumext*` we will add to `\l__enumext_store_anskey_opt_tl`.

```

2658     \bool_lazy_and:nnT
2659     { \bool_not_p:n { \l__enumext_starred_bool } }
2660     { \int_compare_p:nNn { \g__enumext_store_item_join_int } > { 1 } }
2661     {
2662         \tl_put_left:Ne \l__enumext_store_anskey_opt_tl
2663         {
2664             ,item-join = \exp_not:V \g__enumext_store_item_join_int,
2665         }
2666     }

```

And now we will review the keys `item-star`, `item-sym*` and `item-pos*` and pass them to `\l__enumext_store_anskey_opt_tl`.

```

2667     \bool_if:NT \g__enumext_store_item_star_bool
2668     {
2669         \tl_put_left:Ne \l__enumext_store_anskey_opt_tl
2670         {
2671             ,item-star,

```

```

2672     }
2673     \tl_if_empty:NF \g__enumext_store_item_symbol_tl
2674     {
2675         \tl_put_left:Ne \l__enumext_store_anskey_opt_tl
2676         {
2677             ,item-sym* = \exp_not:V \g__enumext_store_item_symbol_tl,
2678         }
2679     }
2680     \dim_compare:nT
2681     {
2682         \g__enumext_store_item_symbol_sep_dim != \c_zero_dim
2683     }
2684     {
2685         \tl_put_left:Ne \l__enumext_store_anskey_opt_tl
2686         {
2687             ,item-pos* = \exp_not:V \g__enumext_store_item_symbol_sep_dim,
2688         }
2689     }
2690 }
2691 }

```

The function `__enumext_anskey_env_store:` will be responsible for storing the content of the environment using the functions `__enumext_store_anskey_code:n` and `__enumext_rescan_anskey_env:n`.

```

2692 \cs_new_protected:Nn \__enumext_anskey_env_store:
2693 {
2694     \group_begin:
2695     \tl_if_empty:NTF \l__enumext_store_anskey_opt_tl
2696     {
2697         \exp_args:Ne
2698         \__enumext_store_anskey_code:n
2699         {
2700             \__enumext_rescan_anskey_env:n { \l__enumext_store_anskey_env_tl }
2701         }
2702     }
2703     {
2704         \keys_set_known:nV { enumext / anskey } \l__enumext_store_anskey_opt_tl
2705         \exp_args:Ne
2706         \__enumext_store_anskey_code:n
2707         {
2708             \__enumext_rescan_anskey_env:n { \l__enumext_store_anskey_env_tl }
2709         }
2710     }
2711     \group_end:
2712 }

```

The function `__enumext_anskey_env_clean_vars:` will return the global variables used by the `(keys)` to their initial state.

```

2713 \cs_new_protected:Nn \__enumext_anskey_env_clean_vars:
2714 {
2715     \bool_gset_false:N \g__enumext_store_columns_break_bool
2716     \int_gzero:N \g__enumext_store_item_join_int
2717     \bool_gset_false:N \g__enumext_store_item_star_bool
2718     \tl_gclear:N \g__enumext_store_item_symbol_tl
2719     \dim_gzero:N \g__enumext_store_item_symbol_sep_dim
2720 }

```

(End of definition for `__enumext_anskey_env_save_keys:`, `__enumext_anskey_env_store:`, and `__enumext_anskey_env_clean_vars:`.)

11.31 Executing anskey*, check-ans and write .log

`__enumext_execute_after_env:`

The `__enumext_execute_after_env:` function will first return the appropriate message for the end of the environment in which the `save-ans` key is being executed, then call the `__enumext_item_answer_diff:` function and then will write the values of the global variables used to the `.log` file. If the `check-ans` is active it will execute the function `__enumext_check_ans_show:` and show the result in the terminal, otherwise it will execute the function `__enumext_check_ans_log:` and write the results in the `.log` file, undefine the environment `anskey*` (§11.30) through the function `__enumext_undefine_anskey_env:` and finally we execute the function `__enumext_reset_global_vars:` returning the used variables to their original state.

```

2721 \cs_new_protected:Nn \__enumext_execute_after_env:
2722 {

```

```

2723 \int_compare:nNt { \l__enumext_level_int } = { 0 }
2724 {
2725   \tl_if_empty:NF \g__enumext_store_name_tl
2726   {
2727     \__enumext_stop_save_ans_msg:
2728     \__enumext_item_answer_diff:
2729     \__enumext_log_global_vars:
2730     \__enumext_log_answer_vars:
2731     \bool_if:NTF \g__enumext_check_ans_key_bool
2732     {
2733       \__enumext_check_ans_show:
2734     }
2735     { \__enumext_check_ans_log: }
2736     \__enumext_undefine_anskey_env:
2737   }
2738   \__enumext_reset_global_vars:
2739 }
2740 }

```

(End of definition for `__enumext_execute_after_env:`.)

- This function is passed to the function `__enumext_after_env:nn` for the environments `enumext` (§11.38) and `enumext*` (§11.42) and it is executed only when the environments are not nested or at some level of these..

11.32 Common functions for `keyans`, `keyans*` and `keyanspic`

11.32.1 Storing content in prop list

`__enumext_keyans_addto_prop:n`

The function `__enumext_keyans_addto_prop:n` will pass the contents of the current *label* `\l__enumext_label_v_tl` for the `keyans` environment and the current *label* `\l__enumext_label_vi_tl` for the `keyanspic` environment when using `\item*` and `\anspic*`, followed by the *contents* of the optional argument of both commands to the `\l__enumext_store_current_label_tl` variable, which will be passed to the *prop list* defined by the `save-ans` key using the `__enumext_store_addto_prop:V`.

```

2741 \cs_new_protected:Npn \__enumext_keyans_addto_prop:n #1
2742 {
2743   \tl_clear:N \l__enumext_store_current_label_tl
2744   \int_compare:nNtF { \l__enumext_keyans_pic_level_int } = { 1 }
2745   {
2746     \tl_put_right:Ne \l__enumext_store_current_label_tl { \l__enumext_label_vi_tl }
2747   }
2748   {
2749     \tl_put_right:Ne \l__enumext_store_current_label_tl { \l__enumext_label_v_tl }
2750   }
2751   \tl_if_novalue:NF { #1 }
2752   {
2753     % Set save-sep
2754     \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_tl
2755     {
2756       \tl_put_right:Ne \l__enumext_store_current_label_tl { \l__enumext_store_keyans_item_opt_sep_tl }
2757     }
2758     \tl_put_right:Ne \l__enumext_store_current_label_tl { #1 }
2759   }
2760   \__enumext_store_addto_prop:V \l__enumext_store_current_label_tl
2761 }

```

(End of definition for `__enumext_keyans_addto_prop:n`.)

11.32.2 The `save-ref` key for `keyans`, `keyans*` and `keyanspic`

The “*internal label and ref*” system for the `keyans`, `keyans*` and `keyanspic` environments has slight differences with the one implemented for the `\anskey` command, basically because in this environments we are interested in the current *label*. The mechanism defined here will allow to execute `\ref{<store name : position>}` and will return 1. (A).

`__enumext_keyans_store_ref:`
`__enumext_keyans_store_ref_aux_i:`
`__enumext_keyans_store_ref_aux_ii:`

The function `__enumext_keyans_store_ref:` handles the internal “*label and ref*” system used by the `save-ref` key for `\item*` and `\anspic*` commands. First we will create copies of the current *labels* and remove the dots “.” from them, we do not want to get double dots in our references.

```

2762 \cs_new_protected:Nn \__enumext_keyans_store_ref:
2763 {
2764   \bool_if:NT \l__enumext_store_ref_key_bool
2765   {
2766     \cs_set_protected:Npn \__enumext_tmp:n #1

```

```

2767     {
2768         \tl_set_eq:cc { l__enumext_label_copy_##1_tl } { l__enumext_label_##1_tl }
2769         \tl_reverse:c { l__enumext_label_copy_##1_tl }
2770         \tl_remove_once:cn { l__enumext_label_copy_##1_tl } { . }
2771         \tl_reverse:c { l__enumext_label_copy_##1_tl }
2772     }
2773     \clist_map_inline:nn { i, v, vi, vii, viii } { \__enumext_tmp:n {##1} }
2774     \__enumext_keyans_store_ref_aux_i:
2775 }
2776 }

```

The auxiliary function `__enumext_keyans_store_ref_aux_i:` set the variable `\l__enumext_newlabel_arg_one_tl` which will contain $\langle store\ name : position \rangle$ analyzing whether the environment in which they are executed is `enumext*` or `enumext`.

```

2777 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_i:
2778 {
2779     \bool_if:NT \g__enumext_starred_bool
2780     {
2781         \tl_set_eq:NN \l__enumext_label_copy_i_tl \l__enumext_label_copy_vii_tl
2782     }
2783     \int_compare:nNnT { \l__enumext_keyans_pic_level_int } = { 1 }
2784     {
2785         \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2786         { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_vi_tl }
2787     }
2788     \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
2789     {
2790         \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2791         { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_v_tl }
2792     }
2793     \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
2794     {
2795         \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
2796         { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_viii_tl }
2797     }
2798     \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
2799     {
2800         \l__enumext_store_name_tl \c_colon_str
2801         \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
2802     }
2803     \__enumext_keyans_store_ref_aux_ii:
2804 }

```

Now auxiliary function `__enumext_keyans_store_ref_aux_ii:` save the result in the variable `\l__enumext_write_aux_file_tl` and finally we write in the `.aux` file.

```

2805 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_ii:
2806 {
2807     \tl_put_right:Ne \l__enumext_write_aux_file_tl
2808     {
2809         \__enumext_newlabel:nn
2810         { \exp_not:V \l__enumext_newlabel_arg_one_tl }
2811         { \l__enumext_newlabel_arg_two_tl }
2812     }
2813     \l__enumext_write_aux_file_tl
2814 }

```

(End of definition for `__enumext_keyans_store_ref:`, `__enumext_keyans_store_ref_aux_i:`, and `__enumext_keyans_store_ref_aux_ii:`.)

11.32.3 Storing content in sequence

`__enumext_keyans_addto_seq:n`
`__enumext_keyans_addto_seq_link:`

The function `__enumext_keyans_addto_seq:n` will pass the contents of the current $\langle label \rangle$ `\l__enumext_label_v_tl` for the `keyans` environment and the `\l__enumext_label_vi_tl` for the `keyanspic` environment when using `\item*` and `\anspic*`, followed by the $\langle contents \rangle$ of the optional argument of both commands to the `\l__enumext_store_current_label_tl` variable to the sequence defined by the `save-ans` key.

```

2815 \cs_new_protected:Npn \__enumext_keyans_addto_seq:n #1
2816 {
2817     \tl_clear:N \l__enumext_store_current_label_tl
2818     \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
2819     {
2820         \tl_put_right:Ne \l__enumext_store_current_label_tl { \item \l__enumext_label_vi_tl }

```

```

2821     }
2822     {
2823         \tl_put_right:Ne \l__enumext_store_current_label_tl { \item \l__enumext_label_v_tl }
2824     }
2825     \tl_if_novalue:nF { #1 }
2826     {
2827         \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_tl
2828         {
2829             \tl_put_right:Ne \l__enumext_store_current_label_tl
2830             {
2831                 \l__enumext_store_keyans_item_opt_sep_tl
2832             }
2833         }
2834         \tl_put_right:Ne \l__enumext_store_current_label_tl { #1 }
2835     }
2836     \__enumext_keyans_addto_seq_link:
2837 }

```

Checks if the `save-ref` key is active along with the `hyperref` package load, if both conditions are met, it will create the `\hyperlink` and then store using the `__enumext_store_addto_seq:V` function. Finally, copy the contents of the variable `\l__enumext_store_current_label_tl` into the global variable `\g__enumext_check_ans_item_tl` to be used by the function `__enumext_check_starred_cmd:n` and increment the value of the integer variable `\g__enumext_item_anskey_int` handled by the `check-ans` key.

```

2838 \cs_new_protected:Nn \__enumext_keyans_addto_seq_link:
2839 {
2840     \bool_lazy_and:nnT
2841     { \bool_if_p:N \l__enumext_store_ref_key_bool }
2842     { \bool_if_p:N \l__enumext_hyperref_bool }
2843     {
2844         \tl_put_right:Ne \l__enumext_store_current_label_tl
2845         {
2846             \hfill \exp_not:N \hyperlink
2847             {
2848                 \exp_not:V \l__enumext_newlabel_arg_one_tl
2849             }
2850             { \exp_not:V \l__enumext_mark_ref_sym_tl }
2851         }
2852     }
2853     \__enumext_store_addto_seq:V \l__enumext_store_current_label_tl
2854     \bool_if:NT \l__enumext_check_answers_bool
2855     {
2856         \int_gincr:N \g__enumext_item_anskey_int
2857     }
2858 }

```

(End of definition for `__enumext_keyans_addto_seq:n` and `__enumext_keyans_addto_seq_link:.`)

11.32.4 The show-ans and show-pos keys for keyans and keyanspic

The code is very similar to the `\anskey` code, but, if I change the order of the operations the counter off `\label` are incorrect.

`__enumext_keyans_show_left:n` Common function to show *starred commands* `\item*` and *position* of stored content in *prop list* for `keyans` and `keyanspic`. Need add 1 to `\g__enumext_⟨store name⟩_prop` for `show-pos` key.

```

\__enumext_keyans_show_ans:
\__enumext_keyans_show_pos:
\__enumext_keyans_show_item_opt:
2859 \cs_new_protected:Npn \__enumext_keyans_show_left:n #1
2860 {
2861     \tl_if_novalue:nF { #1 }
2862     {
2863         \tl_set:Ne \l__enumext_store_current_opt_arg_tl { #1 }
2864     }
2865     \bool_if:NT \l__enumext_show_answer_bool
2866     {
2867         \__enumext_keyans_show_ans:
2868     }
2869     \bool_if:NT \l__enumext_show_position_bool
2870     {
2871         \__enumext_keyans_show_pos:
2872     }
2873 }
2874 \cs_new_protected:Nn \__enumext_keyans_show_item_opt:
2875 {

```



```

2876 \tl_if_empty:NF \l__enumext_store_current_opt_arg_tl
2877 {
2878   \bool_lazy_or:nnT
2879   { \bool_if_p:N \l__enumext_show_answer_bool }
2880   { \bool_if_p:N \l__enumext_show_position_bool }
2881   {
2882     \__enumext_keyans_wrapper_opt:n { \l__enumext_store_current_opt_arg_tl } \c_space_tl
2883   }
2884 }
2885 }
2886 \cs_new_protected:Nn \__enumext_keyans_show_ans:
2887 {
2888   \tl_put_left:Nn \l__enumext_label_v_tl
2889   {
2890     \__enumext_print_keyans_box:NN
2891     \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
2892   }
2893 }
2894 \cs_new_protected:Nn \__enumext_keyans_show_pos:
2895 {
2896   \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
2897   {
2898     \tl_set:Ne \l__enumext_mark_answer_sym_tl
2899     {
2900       \group_begin:
2901       \exp_not:N \normalfont
2902       \exp_not:N \footnotesize [ \int_eval:n
2903         {
2904           \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
2905         }
2906       ]
2907       \group_end:
2908     }
2909   }
2910   {
2911     \tl_set:Ne \l__enumext_mark_answer_sym_tl
2912     {
2913       \group_begin:
2914       \exp_not:N \normalfont
2915       \exp_not:N \footnotesize [ \int_eval:n
2916         {
2917           \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } + 1
2918         }
2919       ]
2920       \group_end:
2921     }
2922   }
2923   \tl_put_left:Nn \l__enumext_label_v_tl
2924   {
2925     \__enumext_print_keyans_box:NN
2926     \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
2927   }
2928 }

```

(End of definition for `__enumext_keyans_show_left:n` and others.)

11.33 Setting `item-sym*` and `item-pos*` keys

In order to have a cleaner implementation of `\item*` it is best to define a couple of keys that allow us to control and set by default the $\langle symbol \rangle$ and its $\langle offset \rangle$.

| | |
|--|--|
| <code>item-sym*</code> <code>item-pos*</code> | <p>Define and set <code>item-sym*</code> and <code>item-pos*</code> keys for <code>enumext</code> and <code>enumext*</code>.</p> <pre> 2929 \cs_set_protected:Npn __enumext_tmp:nn #1 #2 2930 { 2931 \keys_define:nn { enumext / #1 } 2932 { 2933 item-sym* .tl_set:c = { \l__enumext_item_symbol_#2_tl }, 2934 item-sym* .value_required:n = true, 2935 item-sym* .initial:n = { \$\star\$ }, 2936 item-pos* .dim_set:c = { \l__enumext_item_symbol_sep_#2_dim }, 2937 item-pos* .value_required:n = true, 2938 } </pre> |
|--|--|

```

2939   }
2940   \clist_map_inline:nn
2941   {
2942     {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {enumext*}{vii}
2943   }
2944   { \__enumext_tmp:nn #1 }

```

(End of definition for `item-sym*` and `item-pos*`.)

11.34 Redefining `\footnote` command

```

\__enumext_footnotetext:nn
\__enumext_renew_footnote:
\__enumext_print_footnote:

```

To keep the correct numbering of `\footnote` and to make it work correctly with the `mini-env` key and in the `enumext*` and `keyans*` environments, it is necessary to redefine the command. This implementation is adapted from the answer given by Clea F. Rees (@cfr) in [footnotes in boxes compatible with hyperref](#).

```

2945 \cs_new_protected:Nn \__enumext_footnotetext:nn
2946 {
2947   \footnotetext[#1]{#2}
2948 }
2949 \cs_new_protected:Nn \__enumext_renew_footnote:
2950 {
2951   \seq_gclear:N \g__enumext_footnote_arg_seq
2952   \seq_gclear:N \g__enumext_footnote_int_seq
2953   \RenewDocumentCommand \footnote { o +m }
2954   {
2955     \tl_if_novalue:nTF {##1}
2956     {
2957       \stepcounter{footnote}
2958       \int_gset_eq:Nc \g__enumext_footnote_int { c@footnote }
2959     }
2960     {
2961       \int_gset:Nn \g__enumext_footnote_int { ##1 }
2962     }
2963     \footnotemark [ \g__enumext_footnote_int ]
2964     \seq_gput_right:Nn \g__enumext_footnote_arg_seq { ##2 }
2965     \seq_gput_right:NV \g__enumext_footnote_int_seq \g__enumext_footnote_int
2966   }
2967 }
2968 \cs_new_protected:Nn \__enumext_print_footnote:
2969 {
2970   \seq_if_empty:NF \g__enumext_footnote_int_seq
2971   {
2972     \seq_map_pairwise_function:NNN
2973     \g__enumext_footnote_int_seq
2974     \g__enumext_footnote_arg_seq
2975     \__enumext_footnotetext:nn
2976   }
2977 }

```

(End of definition for `__enumext_footnotetext:nn`, `__enumext_renew_footnote:`, and `__enumext_print_footnote:`.)

11.35 Redefining `\item` command

Redefining the `\item` command is not as simple as I thought. This command works in conjunction with the `\makelabel` command so I have to redefine both of them, in addition to this, we will have to use a couple of *global* variables to pass the values from one command to the other.

11.35.1 The `\item` command in `enumext`

```

\__enumext_default_item:n

```

The `\item` and `\item[custom]` commands work in the usual way on `enumext`.

First we will see if the optional argument is present, if it is NOT present we will check the state of the variable `\l__enumext_check_ans_key_bool` set by the key `check-ans`, set the boolean variable `\l__enumext_wrap_label_X_bool` to “true” and execute `__enumext_item_std:w`.

Otherwise we will check the state of the boolean variable `\l__enumext_wrap_label_opt_X_bool` set by the key `wrap-label*` and execute `__enumext_item_std:w` with the optional argument.

The boolean variable `\l__enumext_wrap_label_X_bool` is used by the function `__enumext_make_label:` (§11.36).

```

2978 \cs_new_protected:Npn \__enumext_default_item:n #1
2979 {
2980   \tl_if_novalue:nTF {#1}
2981   {
2982     \bool_if:NT \l__enumext_check_answers_bool
2983     {

```

```

2984         \int_gincr:N \g__enumext_item_number_int
2985         \bool_set_true:N \l__enumext_item_number_bool
2986     }
2987     \bool_set_true:c { l__enumext_wrap_label_ \__enumext_level: _bool }
2988     \__enumext_item_std:w \tl_use:c { l__enumext_fake_item_indent_ \__enumext_level: _tl }
2989 }
2990 {
2991     \bool_set_eq:cc
2992     { l__enumext_wrap_label_ \__enumext_level: _bool }
2993     { l__enumext_wrap_label_opt_ \__enumext_level: _bool }
2994     \__enumext_item_std:w [#1] \tl_use:c { l__enumext_fake_item_indent_ \__enumext_level: _tl }
2995 }
2996 }

```

(End of definition for `__enumext_default_item:n`.)

`__enumext_starred_item:nn`

The `\item*`, `\item*[\langle symbol \rangle]` and `\item*[\langle symbol \rangle][\langle offset \rangle]` works like the numbered `\item`, but placing a `[\langle symbol \rangle]` to the “left” of the `\langle label \rangle` separated from it by the value set by the `labelsep` key and can be *offset* using the second optional argument `[\langle offset \rangle]`.

#1: `\l__enumext_item_symbol_X_tl`

#2: `\l__enumext_item_symbol_sep_X_dim`

First we will make a copy of `\l__enumext_item_symbol_X_tl` which is set by the key `item-sym*` or passed as optional argument in the global variable `\g__enumext_item_symbol_tl`, followed by setting the variable `\l__enumext_item_symbol_sep_X_dim` set by the key `item-pos*` or by the second optional argument.

Then we will see the state of the variable `\l__enumext_check_ans_key_bool` set by the key `check-ans`, set the boolean variable `\l__enumext_wrap_label_X_bool` to “true” and execute `__enumext_item_std:w`.

In this function the optional argument of `__enumext_item_std:w` is omitted, we only want it to be numbered.

The boolean variable `\l__enumext_wrap_label_X_bool` and the vars `\l__enumext_item_symbol_sep_X_dim`, `\g__enumext_item_symbol_tl` are used by the function `__enumext_make_label:` (§11.36).

```

2997 \cs_new_protected:Npn \__enumext_starred_item:nn #1 #2
2998 {
2999     \tl_if_novalue:nF {#1}
3000     {
3001         \tl_set:cn { l__enumext_item_symbol_ \__enumext_level: _tl } {#1}
3002     }
3003     \tl_gset_eq:Nc \g__enumext_item_symbol_tl { l__enumext_item_symbol_ \__enumext_level: _tl }
3004     \tl_if_novalue:nTF {#2}
3005     {
3006         \dim_set_eq:cc
3007         { l__enumext_item_symbol_sep_ \__enumext_level: _dim }
3008         { l__enumext_labelsep_ \__enumext_level: _dim }
3009     }
3010     {
3011         \dim_set:cn { l__enumext_item_symbol_sep_ \__enumext_level: _dim } {#2}
3012     }
3013     \bool_if:NT \l__enumext_check_answers_bool
3014     {
3015         \int_gincr:N \g__enumext_item_number_int
3016         \bool_set_true:N \l__enumext_item_number_bool
3017     }
3018     \bool_set_true:c { l__enumext_wrap_label_ \__enumext_level: _bool }
3019     \__enumext_item_std:w \tl_use:c { l__enumext_fake_item_indent_ \__enumext_level: _tl }
3020 }

```

(End of definition for `__enumext_starred_item:nn`.)

`__enumext_redefine_item:`

The function `__enumext_redefine_item:` will redefine the `\item` command in the `enumext` environment for the internal mechanism of check-answers for `check-ans` key and adding the starred `\item*` version.

This function is passed to `__enumext_list_arg_two_X:` which is used in the definition of the `enumext` environment (§11.37.2).

```

3021 \cs_new_protected:Nn \__enumext_redefine_item:
3022 {
3023     \RenewDocumentCommand \item { s o o }

```

```

3024     {
3025       \bool_if:nTF {##1}
3026       {
3027         \__enumext_starred_item:nn {##2} {##3}
3028       }
3029       { \__enumext_default_item:n {##2} }
3030     }
3031   }

```

(End of definition for `__enumext_redefine_item:`.)

11.35.2 The `\item` command in keyans

The `\item*` and `\item*[\langle content \rangle]` commands *store* the current $\langle label \rangle$ next to the `[\langle content \rangle]` if it is present in the $\langle sequence \rangle$ and $\langle prop list \rangle$ defined by `save-ans` key.

`__enumext_keyans_default_item:n`

The function `__enumext_keyans_default_item:n` executes the original behavior of the `\item`.

```

3032 \cs_new_protected:Npn \__enumext_keyans_default_item:n #1
3033 {
3034   \tl_if_novalue:nTF { #1 }
3035   {
3036     \bool_set_true:N \__enumext_wrap_label_v_bool
3037     \__enumext_item_std:w \tl_use:N \__enumext_fake_item_indent_v_tl
3038   }
3039   {
3040     \bool_set_eq:NN \__enumext_wrap_label_v_bool \__enumext_wrap_label_opt_v_bool
3041     \__enumext_item_std:w [#1] \tl_use:N \__enumext_fake_item_indent_v_tl
3042   }
3043 }

```

(End of definition for `__enumext_keyans_default_item:n`.)

`__enumext_keyans_starred_item:n`

The function `__enumext_keyans_starred_item:n` which will make a temporary copy of the current $\langle label \rangle$, execute the `show-ans` or `show-pos` keys using the function `__enumext_keyans_show_left:n` and will display the contents of that item using the internal copy `__enumext_item_std:w`, this is necessary to prevent incrementing the current “counter” of the original $\langle label \rangle$.

```

3044 \cs_new_protected:Npn \__enumext_keyans_starred_item:n #1
3045 {
3046   \tl_set_eq:NN \__enumext_store_current_label_tmp_tl \__enumext_label_v_tl
3047   \__enumext_keyans_show_left:n { #1 }
3048   \bool_set_true:N \__enumext_wrap_label_v_bool
3049   \__enumext_item_std:w \tl_use:N \__enumext_fake_item_indent_v_tl \__enumext_keyans_show_item:

```

Recover the original value of the current $\langle label \rangle$ and *store* it first in the $\langle prop list \rangle$ (including the optional argument), run the internal “*label and ref*” system if the `save-ref` key is active and finally *store* it in the $\langle sequence \rangle$.

```

3050   \tl_set_eq:NN \__enumext_label_v_tl \__enumext_store_current_label_tmp_tl
3051   \__enumext_keyans_addto_prop:n { #1 }
3052   \__enumext_keyans_store_ref:
3053   \__enumext_keyans_addto_seq:n { #1 }
3054   \int_gincr:N \g__enumext_check_starred_cmd_int
3055 }

```

(End of definition for `__enumext_keyans_starred_item:n`.)

`\item*`

`__enumext_keyans_redefine_item:`

The function `__enumext_keyans_redefine_item:` is responsible for adding the *starred* and *optional* argument by the `__enumext_list_arg_two_v:` function in the definition of the `keyans` environment. Here we need to use `\peek_remove_spaces:n` to prevent an unwanted space when using `\item*` in conjunction with the `itemindent` key.

This function is passed to `__enumext_list_arg_two_v:` which is used in the definition of the `keyans` environment (§11.37.2).

```

3056 \cs_new_protected:Nn \__enumext_keyans_redefine_item:
3057 {
3058   \RenewDocumentCommand \item { s o }
3059   {
3060     \bool_if:nTF {##1}
3061     {
3062       \peek_remove_spaces:n
3063       {
3064         \__enumext_keyans_starred_item:n {##2}
3065       }

```

```

3066         }
3067         {
3068             \__enumext_keyans_default_item:n {##2}
3069         }
3070     }
3071 }

```

(End of definition for `\item*` and `__enumext_keyans_redefine_item:`. This function is documented on page 14.)

11.36 Redefining `\makeLabel` command

Redefine `\makeLabel` for the keys `align`, `font`, `wrap-label`, `wrap-label*` and `\item*` for `enumext` and `keyans` environments.

11.36.1 Redefining `\makeLabel` for `enumext`

`__enumext_item_starred:` The function `__enumext_item_starred:` will be responsible for executing `\item*` for the `enumext` environment.

```

3072 \cs_new_protected:Nn \__enumext_item_starred:
3073 {
3074     \tl_if_empty:cF { \__enumext_item_symbol_ \__enumext_level: _tl }
3075     {
3076         \mode_leave_vertical:
3077         \skip_horizontal:n { -\dim_use:c { \__enumext_item_symbol_sep_ \__enumext_level: _dim } }
3078         \makebox[ 0pt ][ r ]{ \g__enumext_item_symbol_tl }
3079         \skip_horizontal:n { \dim_use:c { \__enumext_item_symbol_sep_ \__enumext_level: _dim } }
3080     }
3081 }

```

(End of definition for `__enumext_item_starred:`.)

`__enumext_make_label:` The function `__enumext_make_label:` redefine `\makeLabel` for the `enumext` environment. This function is passed to `__enumext_list_arg_two_X:` which is used in the definition of the `enumext` environment (§11.37.2).

```

3082 \cs_new_protected:Nn \__enumext_make_label:
3083 {
3084     \RenewDocumentCommand \makeLabel { m }
3085     {
3086         \tl_use:c { \__enumext_label_fill_left_ \__enumext_level: _tl }
3087         \tl_use:c { \__enumext_label_font_style_ \__enumext_level: _tl }
3088         \bool_if:cTF { \__enumext_wrap_label_ \__enumext_level: _bool }
3089         {
3090             \__enumext_item_starred:
3091             \use:c { __enumext_wrapper_label_ \__enumext_level: :n } { ##1 }
3092         }
3093         { ##1 }
3094         \tl_use:c { \__enumext_label_fill_right_ \__enumext_level: _tl }
3095         \tl_gclear:N \g__enumext_item_symbol_tl
3096     }
3097 }

```

(End of definition for `__enumext_make_label:`.)

11.36.2 Redefining `\makeLabel` for `keyans`

`__enumext_keyans_make_label:` The function `__enumext_keyans_make_label:` redefine `\makeLabel` for `keyans` environment. This function is passed to `__enumext_list_arg_two_v:` which is used in the definition of the `keyans` environment (§11.37.2).

```

3098 \cs_new_protected:Nn \__enumext_keyans_make_label:
3099 {
3100     \RenewDocumentCommand \makeLabel { m }
3101     {
3102         \tl_use:N \l__enumext_label_fill_left_v_tl
3103         \tl_use:N \l__enumext_label_font_style_v_tl
3104         \bool_if:NTF \l__enumext_wrap_label_v_bool
3105         {
3106             \__enumext_wrapper_label_v:n { ##1 }
3107         }
3108         { ##1 }
3109         \tl_use:N \l__enumext_label_fill_right_v_tl
3110     }
3111 }

```

(End of definition for `__enumext_keyans_make_label:`.)

11.37 Second argument of the lists

At this point of the code we have already programmed most the necessary tools to create a custom `list` environment, remember that the function `__enumext_start_list:nn` takes two arguments, the first one we have ready, the second one we will define for all the levels of the environment `enumext` and the environment `keyans`.

11.37.1 Calculation of `\leftmargin` and `\itemindent`

Consider the figure 9 where the default margins (on the left) of a list are represented.




Figure 9: Representation of standard horizontal lengths in `list` environment.

The idea is to have control over these margins so that our list does not overlap the left margin of the page. The key relationship is that the right edge of the `\labelsep` equals the right edge of the `\itemindent`, so that the left edge of the *label box* is at `\leftmargin + \itemindent` minus `\labelwidth + \labelsep`. Thus, the handling of the margins by the package will be as shown in the figure 10.




Figure 10: Representation of horizontal lengths concept in list in `enumext`.

Where the default values will look like in the figure 11.




Figure 11: Default horizontal lengths in `enumext`.

```
\__enumext_calc_hspace:NNNNNNN
\__enumext_calc_hspace:ccccccc
```

The function `__enumext_calc_hspace:NNNNNNN` takes seven arguments to be able to determine horizontal spaces for all list environment:

```
#1: \l__enumext_labelwidth_X_dim      #2: \l__enumext_labelsep_X_dim
#3: \l__enumext_listoffset_X_dim      #4: \l__enumext_leftmargin_tmp_X_dim
#5: \l__enumext_leftmargin_X_dim      #6: \l__enumext_itemindent_X_dim
#7: \l__enumext_leftmargin_tmp_X_bool
```

And returns the “adjusted” values of `\leftmargin` and `\itemindent`.

This function is passed to `__enumext_list_arg_two_X:` which is used in the definition of the `enumext` and `keyans` environments (§11.37.2).

```
3112 \cs_new_protected:Npn \__enumext_calc_hspace:NNNNNNN #1 #2 #3 #4 #5 #6 #7
3113 {
3114   \dim_compare:nNt { #1 } < { \c_zero_dim }
3115   {
3116     \msg_warning:nnnV { enumext } { width-non-positive } { labelwidth } { #1 }
3117     \dim_set:Nn #1 { \dim_abs:n { #1 } }
3118   }
3119   \dim_compare:nNt { #2 } < { \c_zero_dim }
3120   {
3121     \msg_warning:nnnV { enumext } { width-negative } { labelsep } { #2 }
3122     \dim_set:Nn #2 { \dim_abs:n { #2 } }
3123   }
3124 }
```

If no value has been passed to the `labelwidth` and `labelsep` keys we set the default values for `\l__enumext_leftmargin_tmp_X_dim`.

```
3124 \bool_if:nF #7 { \dim_set:Nn #4 { #1 + #2 } }
```

We now analyze the cases and set the values for `\leftmargin` and `\itemindent`.

```

3125 \dim_compare:nNnTF { #4 } < { \c_zero_dim }
3126 {
3127   \dim_set:Nn #6 { #1 + #2 - #4 }
3128   \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
3129 }
3130 {
3131   \dim_compare:nNnT { #4 } = { #1 + #2 }
3132   { \dim_set:Nn #6 { \c_zero_dim } }
3133   \dim_compare:nNnT { #4 } < { #1 + #2 }
3134   { \dim_set:Nn #6 { #1 + #2 - #4 } }
3135   \dim_compare:nNnT { #4 } > { #1 + #2 }
3136   {
3137     \dim_set:Nn #6 { -#1 - #2 + #4 }
3138     \dim_set:Nn #6 { #6*-1 }
3139   }
3140   \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
3141 }
3142 }
3143 \cs_generate_variant:Nn \__enumext_calc_hspace:NNNNNNN { cccccc }

```

(End of definition for `__enumext_calc_hspace:NNNNNNN`.)

11.37.2 Setting second argument of the lists

We will “not set” `\leftmargini`, `\leftmarginii`, `\leftmarginiii` or `\leftmarginiv`, in this case, we will directly set the parameters for vertical and horizontal list spacing per level.

```

3144 \cs_set_protected:Npn \__enumext_tmp:n #1
3145 {
3146   \cs_new_protected:cpn { \__enumext_list_arg_two_#1: }
3147   {
3148     \__enumext_calc_hspace:ccccc
3149     { \__enumext_labelwidth_#1_dim } { \__enumext_labelsep_#1_dim }
3150     { \__enumext_listoffset_#1_dim } { \__enumext_leftmargin_tmp_#1_dim }
3151     { \__enumext_leftmargin_#1_dim } { \__enumext_itemindent_#1_dim }
3152     { \__enumext_leftmargin_tmp_#1_bool }
3153     \clist_map_inline:nn
3154     { labelsep, labelwidth, itemindent, leftmargin, rightmargin, listparindent }
3155     { \dim_set_eq:cc {####1} { \__enumext_####1_#1_dim } }
3156     \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
3157     { \skip_set_eq:cc {####1} { \__enumext_####1_#1_skip } }
3158     \usecounter { enumX#1 }
3159     \setcounter { enumX#1 } { \int_eval:n { \int_use:c { \__enumext_start_#1_int } - 1 } }
3160     \str_if_eq:nnTF { #1 } { v }
3161     {
3162       \__enumext_keyans_redefine_item:
3163       \__enumext_keyans_make_label:
3164       \__enumext_keyans_ref:
3165       \__enumext_keyans_fake_item:
3166       \bool_if:cT { \__enumext_show_length_#1_bool }
3167       {
3168         \msg_term:nnnn { enumext } { list-lengths-not-nested } { v } { keyans }
3169       }
3170     }
3171     {
3172       \__enumext_redefine_item:
3173       \__enumext_make_label:
3174       \__enumext_standar_ref:
3175       \__enumext_fake_item:
3176       \bool_if:cT { \__enumext_show_length_#1_bool }
3177       {
3178         \msg_term:nnne { enumext } { list-lengths } { #1 } { \int_use:N \__enumext_level_int }
3179       }
3180     }
3181   }
3182 }
3183 \clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n { #1 } }

```

(End of definition for `__enumext_list_arg_two_i: and others`.)

`__enumext_list_arg_two_vii:` For the horizontal environments `enumext*` and `keyans*` the implementation is similar, but, the value of `\partopsep` is always `\opt`. At this point we will modify the `parsep` key to make it take the value of the

itemsep key and later, in the environment definition, we will modify `\parindent` to make it set the value of `\lisparindent` and `\parsep` to set the value of `\parskip` locally.

```

3184 \cs_set_protected:Npn \__enumext_tmp:n #1
3185 {
3186   \cs_new_protected:cpn { \__enumext_list_arg_two_#1: }
3187   {
3188     \__enumext_calc_hspace:ccccc
3189     { \__enumext_labelwidth_#1_dim } { \__enumext_labelsep_#1_dim }
3190     { \__enumext_listoffset_#1_dim } { \__enumext_leftmargin_tmp_#1_dim }
3191     { \__enumext_leftmargin_#1_dim } { \__enumext_itemindent_#1_dim }
3192     { \__enumext_leftmargin_tmp_#1_bool }
3193   \clist_map_inline:nn
3194     { labelsep, labelwidth, itemindent, leftmargin, rightmargin, listparindent }
3195     { \dim_set_eq:cc {###1} { \__enumext_###1_#1_dim } }
3196   \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
3197     { \skip_set_eq:cc {###1} { \__enumext_###1_#1_skip } }
3198   \skip_set_eq:Nc \parsep { \__enumext_itemsep_#1_skip }
3199   \skip_zero:N \partopsep
3200   \usecounter { enumX#1 }
3201   \setcounter { enumX#1 } { \int_eval:n { \int_use:c { \__enumext_start_#1_int } - 1 } }
3202   \__enumext_starred_ref:
3203   \str_if_eq:nnTF {#1} { vii }
3204   {
3205     \__enumext_fake_item_vii:
3206     \bool_if:cT { \__enumext_show_length_vii_bool }
3207       { \msg_term:nnnn { enumext } { list-lengths-not-nested } { vii } { enumext* } }
3208   }
3209   {
3210     \__enumext_fake_item_viii:
3211     \bool_if:cT { \__enumext_show_length_#1_bool }
3212       { \msg_term:nnnn { enumext } { list-lengths-not-nested } { #1 } { keyans* } }
3213   }
3214 }
3215 }
3216 \clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }

```

(End of definition for `__enumext_list_arg_two_vii:` and `__enumext_list_arg_two_viii:`)

11.38 The environment `enumext`

`enumext` We create the `enumext` environment based on `list` environment by levels.

```

3217 \NewDocumentEnvironment{enumext}{0}{}
3218 {
3219   \__enumext_safe_exec:
3220   \__enumext_parse_keys:n {#1}
3221   \__enumext_before_list:
3222   \__enumext_start_store_level:
3223   \__enumext_start_list:nn
3224     { \tl_use:c { \__enumext_label_ \__enumext_level: _tl } }
3225     {
3226       \use:c { \__enumext_list_arg_two_ \__enumext_level: : }
3227       \__enumext_before_keys_exec:
3228     }
3229   \__enumext_after_args_exec:
3230 }
3231 {
3232   \__enumext_stop_list:
3233   \__enumext_stop_store_level:
3234   \__enumext_after_list:
3235 }

```

(End of definition for `enumext`. This function is documented on page 4.)

`__enumext_safe_exec:` The `__enumext_safe_exec:` function first execute the function `__enumext_is_not_nested:` which will set the variable `\g__enumext_standar_bool` to “true” if the environment is not nested in `enumext*`, we increment the variable `__enumext_level_int` for the nesting levels and set the `__enumext_standar_bool` variable to “true”. Finally we set the variable `__enumext_standar_first_bool` to “true” only if the environment is not nested and we are at the “first level” of it using the function `__enumext_is_on_first_level:`.

```

3236 \cs_new_protected:Nn \__enumext_safe_exec:
3237 {

```

```

3238     \__enumext_internal_mini_page:
3239     \__enumext_is_not_nested:
3240     \int_incr:N \__enumext_level_int
3241     \int_compare:nNnT { \__enumext_level_int } > { 4 }
3242     { \msg_fatal:nn { enumext } { list-too-deep } }
3243     \bool_set_true:N \__enumext_standar_bool
3244     \__enumext_is_on_first_level:
3245 }

```

(End of definition for __enumext_safe_exec:.)

__enumext_parse_keys:n The __enumext_parse_store_keys:n function will parse the *⟨keys⟩* passed to the optional environment argument *enumext* by levels only if present. First we clear the variable __enumext_series_str and then we check if we are at the first level, if so we process the *⟨keys⟩* and then execute the function __enumext_parse_series:n used by the key *series*, otherwise we will pass the *⟨keys⟩* to the inner levels of the environment and finally if the variable __enumext_store_active_bool established by the key *save-ans* is true we execute __enumext_parse_store_keys:n used by the key *save-key*.

```

3246 \cs_new_protected:Npn \__enumext_parse_keys:n #1
3247 {
3248     \tl_if_novalue:nF {#1}
3249     {
3250         \str_clear:N \__enumext_series_str
3251         \int_compare:nNnTF { \__enumext_level_int } = { 1 }
3252         {
3253             \keys_set:nn { enumext / level-1 } {#1}
3254             \__enumext_parse_series:n {#1}
3255             \__enumext_nested_base_line_fix:
3256         }
3257         {
3258             \exp_args:Ne \keys_set:nn
3259             { enumext / level-\int_use:N \__enumext_level_int } {#1}
3260         }
3261         \__enumext_store_active_keys:n {#1}
3262     }
3263 }

```

(End of definition for __enumext_parse_keys:n.)

__enumext_start_store_level: The __enumext_start_store_level: and __enumext_stop_store_level: functions activate the level saving mechanism for storage in *⟨sequence⟩* for the command \anskey and the environment anskey*.

__enumext_stop_store_level:

```

3264 \cs_new_protected:Nn \__enumext_start_store_level:
3265 {
3266     \bool_lazy_all:nT
3267     {
3268         { \bool_if_p:N \__enumext_store_active_bool }
3269         { \bool_not_p:n { \__enumext_keyans_env_bool } }
3270         { \bool_if_p:N \__enumext_standar_bool }
3271     }
3272     {
3273         \int_compare:nNnT { \__enumext_level_int } > { 1 }
3274         {
3275             \bool_set_true:c { l__enumext_store_upper_level_ \__enumext_level: _bool }
3276             \__enumext_store_level_open:
3277         }
3278     }

```

If *enumext* are nested in *enumext** add __enumext_store_level_open: to preserve the stored structure.

```

3279     \bool_lazy_all:nT
3280     {
3281         { \bool_if_p:N \__enumext_store_active_bool }
3282         { \bool_not_p:n { \__enumext_keyans_env_bool } }
3283         { \int_compare_p:nNn { \__enumext_level_h_int } = { 1 } }
3284     }
3285     {
3286         \int_compare:nNnT { \__enumext_level_int } > { 0 }
3287         {
3288             \bool_set_true:c { l__enumext_store_upper_level_ \__enumext_level: _bool }
3289             \__enumext_store_level_open:
3290         }
3291     }

```

```

3292   }
3293   \cs_new_protected:Nn \__enumext_stop_store_level:
3294   {
3295     \bool_if:cT { l__enumext_store_upper_level_ \__enumext_level: _bool }
3296     {
3297       \__enumext_store_level_close:
3298     }
3299   }

```

(End of definition for __enumext_start_store_level: and __enumext_stop_store_level:.)

`__enumext_before_list:` The function `__enumext_before_list:` will add the vertical spacing on the environment if the `above` key is active next to the `{\code}` defined by the `before*` key if it is active.

```

3300 \cs_new_protected:Nn \__enumext_before_list:
3301 {
3302   \__enumext_vspace_above:
3303   \__enumext_before_args_exec:

```

The function `__enumext_check_ans_active:` will handle the check answer mechanism, which will be activated with the `check-ans` key.

```

3304   \__enumext_check_ans_active:

```

When the `mini-env` key is active it will set the value of the `\l__enumext_minipage_right_X_dim` to be the *width* of the `__enumext_mini_env*` environment on the “right side”, using this value together with the value of the `\l__enumext_minipage_hsep_X_dim` set by the `mini-sep` key, the value of `\l__enumext_minipage_left_X_dim` will be set, which will be the *width* of `__enumext_mini_env*` environment on the “left side”, always having a current `\linewidth` as *maximum width* between them.

```

3305   \dim_compare:nNnT
3306   { \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim } } > { \c_zero_dim }
3307   {
3308     \dim_set:cn { l__enumext_minipage_left_ \__enumext_level: _dim }
3309     {
3310       \linewidth
3311       - \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim }
3312       - \dim_use:c { l__enumext_minipage_hsep_ \__enumext_level: _dim }
3313     }

```

The boolean variable `\l__enumext_minipage_active_X_bool` will be activated and the integer variable `\g__enumext_minipage_stat_int` used by the `\miniright` command will be incremented, then the function `__enumext_mini_addvspace:` is called and the `__enumext_mini_env*` environment on the “left side” will be initialized followed by the “vertical spacing” applied to preserve the “baseline” between the *left* and *right* side environments. After these actions, the function `__enumext_multicols_start:` is called to handle the `multicols` environment.

Here we use the plain TeX macro `\nointerlineskip` to prevent baseline “glue” being added between the next pair of boxes in a *vertical list*.

```

3314     \bool_set_true:c { l__enumext_minipage_active_ \__enumext_level: _bool }
3315     \int_gincr:N \g__enumext_minipage_stat_int
3316     \__enumext_mini_addvspace:
3317     \nointerlineskip\noindent
3318     \begin{\__enumext_mini_env*}
3319     { \dim_use:c { l__enumext_minipage_left_ \__enumext_level: _dim } }
3320   }
3321   \__enumext_multicols_start:
3322 }

```

(End of definition for __enumext_before_list:.)

`__enumext_multicols_start:` The function `__enumext_multicols_start:` will start the `multicols` environment according to the value passed by the `columns` key, then set the default value for `\columnsep` when `columns-sep=0pt` and set the value of `\multicolsep` equal to zero and leave `\columnseprule` equal to zero for inner levels.

```

3323 \cs_new_protected:Nn \__enumext_multicols_start:
3324 {
3325   \int_compare:nNnT
3326   { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
3327   {
3328     \dim_compare:nNnT
3329     { \dim_use:c { l__enumext_columns_sep_ \__enumext_level: _dim } } = { \c_zero_dim }
3330     {
3331       \dim_set:cn { l__enumext_columns_sep_ \__enumext_level: _dim }
3332       {

```

```

3333         ( \dim_use:c { l__enumext_labelwidth_ \__enumext_level: _dim }
3334         + \dim_use:c { l__enumext_labelsep_ \__enumext_level: _dim }
3335         ) / \int_use:c { l__enumext_columns_ \__enumext_level: _int }
3336         - \dim_use:c { l__enumext_listoffset_ \__enumext_level: _dim }
3337     }
3338 }
3339 \dim_set_eq:Nc \columnsep { l__enumext_columns_sep_ \__enumext_level: _dim }
3340 \skip_zero:N \multicolsep
3341 \int_compare:nNnT { \l__enumext_level_int } > { 1 }
3342 {
3343     \dim_zero:N \columnseprule
3344 }

```

We will calculate the *vertical spacing* settings for the `multicols` environment using the function `__enumext_multi_addvspace:`, apply our “*vertical adjust spacing*”, then start the `multicols` environment.

```

3345 \bool_if:cF { l__enumext_minipage_active_ \__enumext_level: _bool }
3346 {
3347     \__enumext_multi_addvspace:
3348 }
3349 \raggedcolumns
3350 \begin{multicols}{ \int_use:c { l__enumext_columns_ \__enumext_level: _int } }
3351 }
3352 }

```

(End of definition for `__enumext_multicols_start:`)

`__enumext_multicols_stop:` The function `__enumext_multicols_stop:` will stop the `multicols` environment. If the boolean variable `\l__enumext_minipage_active_X_bool` is false (not nested in `__enumext_mini_env*`) we will apply our “*vertical adjust*” spacing.

```

3353 \cs_new_protected:Nn \__enumext_multicols_stop:
3354 {
3355     \int_compare:nNnT
3356     { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
3357     {
3358         \end{multicols}
3359         \bool_if:cF { l__enumext_minipage_active_ \__enumext_level: _bool }
3360         {
3361             \par\addvspace{ \skip_use:c { l__enumext_multicols_below_ \__enumext_level: _skip } }
3362         }
3363     }
3364 }

```

(End of definition for `__enumext_multicols_stop:`)

`__enumext_after_list:` The function `__enumext_after_list:` will check the state of the boolean variable `\l__enumext_minipage_active_X_bool`, if it is “true” a small test will be executed to check if we have omitted the use of `\miniright` (the `__enumext_mini_env*` environment has not been closed), then close `__enumext_mini_env*` and add the *adjusted vertical space* `\l__enumext_minipage_after_skip`, otherwise we will close the `multicols` environment.

```

3365 \cs_new_protected:Nn \__enumext_after_list:
3366 {
3367     \bool_if:cTF { l__enumext_minipage_active_ \__enumext_level: _bool }
3368     {
3369         \int_compare:nNnT { \g__enumext_minipage_stat_int } = { 1 }
3370         {
3371             \msg_warning:nn { enumext } { missing-miniright }
3372             \miniright
3373         }
3374         \int_gzero:N \g__enumext_minipage_stat_int
3375         \end{__enumext_mini_env*}
3376         \par\addvspace { \l__enumext_minipage_after_skip }
3377     }
3378     { \__enumext_multicols_stop: }

```

If the `check-ans` key is active, we set the boolean variable `\g__enumext_check_ans_show_bool` to true and copy the “*store name*” to the variable `\g__enumext_store_name_tl`.

```

3379     \__enumext_check_ans_key_hook:

```

Now apply the `{code}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present, set `\l__enumext_standar_bool` to false and save the *current value* of the counter for `series`, `resume` and `resume*` keys.

```

3380   \__enumext_after_stop_list:
3381   \__enumext_vspace_below:
3382   \bool_set_false:N \l__enumext_standar_bool
3383   \__enumext_resume_save_counter:
3384 }

```

(End of definition for `__enumext_after_list:`.)

As we don't want our check to be executed `check-ans` by levels but on the complete list, we will take it out of the `enumext` environment using the “hook” function `__enumext_after_env:nn`.

```

3385 \__enumext_after_env:nn {enumext} { \__enumext_execute_after_env: }

```

11.39 The environment `keyans`

The environment `keyans` also based on lists. The main differences with the `enumext` environment are the *nesting* and the way the *answers* (choice) will be stored and checked, this environment is intended exclusively for “multiple choice questions”.

`keyans` Now we define the environment `keyans` also based on lists.

```

3386 \NewDocumentEnvironment{keyans}{0}{ }
3387 {
3388   \__enumext_keyans_safe_exec:
3389   \__enumext_keyans_parse_keys:n {#1}
3390   \__enumext_before_list_v:
3391   \__enumext_start_list:nn
3392   { \tl_use:N \l__enumext_label_v_tl }
3393   {
3394     \__enumext_list_arg_two_v:
3395     \__enumext_before_keys_exec_v:
3396   }
3397   \__enumext_after_args_exec_v:
3398 }
3399 {
3400   \__enumext_check_starred_cmd:n { item }
3401   \__enumext_stop_list:
3402   \__enumext_after_list_v:
3403 }

```

(End of definition for `keyans`. This function is documented on page 13.)

`__enumext_keyans_safe_exec:` The `keyans` environment will only be available if the `save-ans` key is active and can only be used at the first level within the `enumext` environment. We do not want the environment to be nested, so we will set a maximum at this point. If the conditions are not met, an error message will be returned.

```

3404 \cs_new_protected:Nn \__enumext_keyans_safe_exec:
3405 {
3406   \bool_if:NF \l__enumext_store_active_bool
3407   {
3408     \msg_error:nnnn { enumext } { wrong-place } { keyans } { save-ans }
3409   }
3410   \int_incr:N \l__enumext_keyans_level_int
3411   \bool_set_true:N \l__enumext_keyans_env_bool
3412   \__enumext_keyans_start_line:
3413   % Set false for interfering with enumext nested in keyans (yes, its possible and crayze)
3414   \bool_set_false:N \l__enumext_store_active_bool
3415   \int_compare:nNtT { \l__enumext_keyans_level_int } > { 1 }
3416   {
3417     \msg_error:nn { enumext } { keyans-nested }
3418   }
3419   \int_compare:nNtT { \l__enumext_level_int } > { 1 }
3420   {
3421     \msg_error:nn { enumext } { keyans-wrong-level }
3422   }
3423 }

```

(End of definition for `__enumext_keyans_safe_exec:`.)

`__enumext_keyans_parse_keys:n` Parse [*key* = *val*] for *keyans* environment.

```

3424 \cs_new_protected:Npn \__enumext_keyans_parse_keys:n #1
3425 {
3426   \keys_set:nn { enumext / keyans } {#1}
3427 }

```

(End of definition for `__enumext_keyans_parse_keys:n`.)

`__enumext_before_list_v:` The function `__enumext_before_list_v:` will add the *vertical spacing* above the environment if the *above* key is active next to the *code* defined by the *before* key if it is active.

```

3428 \cs_new_protected:Nn \__enumext_before_list_v:
3429 {
3430   \__enumext_vspace_above_v:
3431   \__enumext_before_args_exec_v:

```

When the *mini-env* key is active it will set the value of the `\l__enumext_minipage_right_v_dim` to be the *width* of the `__enumext_mini_env*` environment on the *left side*, using this value together with the value of the `\l__enumext_minipage_hsep_v_dim` set by the *mini-sep* key, the value of `\l__enumext_minipage_left_v_dim` will be set, which will be the *width* of `__enumextt_mini_env*` environment on the *right side*, always having `\linewidth` as the maximum width between them.

```

3432   \dim_compare:nNnT { \l__enumext_minipage_right_v_dim } > { \c_zero_dim }
3433   {
3434     \dim_set:Nn \l__enumext_minipage_left_v_dim
3435     {
3436       \linewidth - \l__enumext_minipage_right_v_dim - \l__enumext_minipage_hsep_v_dim
3437     }

```

The boolean variable `\l__enumext_minipage_active_v_bool` will be activated and the integer variable `\g__enumext_minipage_stat_int` used by the `\miniright` command will be incremented, then the function `__enumext_keyans_mini_addvspace:` is called and the `__enumext_mini_env*` environment on *left side* will be initialized followed by the *vertical spacing* `\l__enumext_minipage_left_skip`. Here we use the plain TeX macro `\nointerlineskip` to prevent baseline “glue” being added between the next pair of boxes in a *vertical list*.

```

3438     \bool_set_true:N \l__enumext_minipage_active_v_bool
3439     \int_gincr:N \g__enumext_minipage_stat_int
3440     \__enumext_keyans_mini_addvspace:
3441     \nointerlineskip\noindent
3442     \begin{__enumext_mini_env*}{ \l__enumext_minipage_left_v_dim }
3443   }

```

After these actions, the `__enumext_keyans_multicols_start:` function is called to handle the *multicols* environment.

```

3444   \__enumext_keyans_multicols_start:
3445 }

```

(End of definition for `__enumext_before_list_v:`.)

`__enumext_keyans_multicols_start:` The function `__enumext_keyans_multicols_start:` will start the *multicols* environment according to the value passed by the *columns* key.

```

3446 \cs_new_protected:Nn \__enumext_keyans_multicols_start:
3447 {
3448   \int_compare:nNnT { \l__enumext_columns_v_int } > { 1 }
3449   {

```

Set the default value for `\columnsep` when *columns-sep* key is *opt*.

```

3450     \dim_compare:nNnT { \l__enumext_columns_sep_v_dim } = { \c_zero_dim }
3451     {
3452       \dim_set:Nn \l__enumext_columns_sep_v_dim
3453       {
3454         (
3455           \l__enumext_labelwidth_v_dim + \l__enumext_labelsep_v_dim
3456         ) / \l__enumext_columns_v_int
3457         - \l__enumext_listoffset_v_dim
3458       }
3459     }
3460     \dim_set_eq:NN \columnsep \l__enumext_columns_sep_v_dim

```

Then we will set the value of `\multicolsep` and `\columnseprule` equal to zero (we do not want a vertical rule in this environment).

```

3461     \skip_zero:N \multicolsep
3462     \dim_zero:N \columnseprule

```

We will calculate the *vertical spacing* settings for the `multicols` environment using the function `__enumext_keyans_multi_addvspace`: and apply our “*vertical adjust spacing*”, then start the `multicols` environment.

```

3463     \bool_if:NF \l__enumext_minipage_active_v_bool
3464     {
3465         \__enumext_keyans_multi_addvspace:
3466     }
3467     \raggedcolumns
3468     \begin{multicols}{\l__enumext_columns_v_int }
3469 }
3470 }
```

(End of definition for `__enumext_keyans_multicols_start:`)

`__enumext_keyans_multicols_stop:`

The function `__enumext_keyans_multicols_stop:` will stop the `multicols` environment. If the boolean variable `\l__enumext_minipage_active_v_bool` is false (not nested in `__enumext_mini-env*`) we will apply our vertical “adjust” spacing.

```

3471 \cs_new_protected:Nn \__enumext_keyans_multicols_stop:
3472 {
3473     \int_compare:nNt { \l__enumext_columns_v_int } > { 1 }
3474     {
3475         \end{multicols}
3476         \bool_if:NF \l__enumext_minipage_active_v_bool
3477         {
3478             \par\addvspace{ \l__enumext_multicols_below_v_skip }
3479         }
3480     }
3481 }
```

(End of definition for `__enumext_keyans_multicols_stop:`)

`__enumext_after_list_v:`

The function `__enumext_after_list_v:` will check the state of the boolean variable `\l__enumext_minipage_active_v_bool`, if it is “true” a small test will be executed to check if we have omitted the use of `\miniright` (the `__enumext_mini-env*` environment has not been closed), then close `__enumext_mini-env*` and add the vertical adjustment space `\l__enumext_minipage_after_skip`, otherwise we will close the `multicols` environment.

```

3482 \cs_new_protected:Nn \__enumext_after_list_v:
3483 {
3484     \bool_if:NTF \l__enumext_minipage_active_v_bool
3485     {
3486         \int_compare:nNt { \g__enumext_minipage_stat_int } = { 1 }
3487         {
3488             \msg_warning:nn { enumext } { missing-miniright }
3489             \miniright
3490         }
3491         \int_gzero:N \g__enumext_minipage_stat_int
3492         \end{\__enumext_mini-env*}
3493         \par\addvspace{ \l__enumext_minipage_after_skip }
3494     }
3495     { \__enumext_keyans_multicols_stop: }
```

Finally we will apply the `{\code}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```

3496     \bool_set_false:N \l__enumext_keyans_env_bool
3497     \__enumext_after_stop_list_v:
3498     \__enumext_vspace_below_v:
3499 }
```

(End of definition for `__enumext_after_list_v:`)


11.40 The environment `keyanspic` and `\anspic`

The `keyanspic` environment is a list-based environment that uses the same configuration for “*spacing*” and `\label` as the `keyans` environment, but it does not use `\item`.

The contents are passed to the environment by means of the `\anspic` command and are placed inside `minipage` environments, with the `\label` underneath, adjusting widths according to the options passed to the environment.

Again it is necessary to “adjust” the spacing, both vertical and horizontal, to obtain an output like the one shown in the figure 12.

This implementation is adapted from the answer given by Enrico Gregorio in [How to process the body of an environment and divide it by a \macro?](#).

Figure 12: Representation of the `keyanspic` spacing in `enumext`.

11.40.1 The command `\anspic`

`\anspic` The `\anspic` command take three arguments, the starred (*) versions `\anspic*` and `\anspic*[\langle content \rangle]` store the current `\label` next to the `[\langle content \rangle]` if it is present in the `\sequence` and `\prop list` defined by `save-ans` key. This command is used as a replacement for `\item` in the `keyanspic` environment.

```
3500 \NewDocumentCommand \anspic { s o +m }
3501 {
```

We check that the command is active in the `keyanspic` environment only if the `save-ans` key is present, otherwise we return an error.

```
3502   \bool_if:NF \l__enumext_store_active_bool
3503   {
3504     \msg_error:nnnn { enumext } { wrong-place } { keyanspic } { save-ans }
3505   }
3506   \int_compare:nNt { \l__enumext_level_int } > { 1 }
3507   {
3508     \msg_error:nn { enumext } { keyanspic-wrong-level }
3509   }
3510   \int_compare:nNt { \l__enumext_keyans_level_int } = { 1 }
3511   {
3512     \msg_error:nnnn { enumext } { command-wrong-place } { anspic } { keyans }
3513   }
```

The three arguments are handled by the function `__enumext_keyans_anspic_code:nnn` and stored in the sequence `\l__enumext_keyans_pic_body_seq` which is processed by the `keyanspic` environment.

```
3514   \seq_put_right:Nn \l__enumext_keyans_pic_body_seq
3515   {
3516     \__enumext_keyans_anspic_code:nnn { #1 } { #2 } { #3 }
3517   }
3518 }
```

(End of definition for `\anspic`. This function is documented on page 15.)

`__enumext_keyans_anspic_code:nnn`

The function `__enumext_keyans_anspic_code:nnn` will be in charge of handling the “counter” and `\label`, which will have the same configuration as the `keyans` environment.

```
3519 \cs_new_protected:Nn \__enumext_keyans_anspic_code:nnn
3520 {
3521   \stepcounter { enumXvi }
3522   #3 \\\
3523   \bool_if:nT { #1 }
3524   {
3525     \__enumext_keyans_addto_prop:n { #2 }
3526     \__enumext_keyans_store_ref:
3527     \__enumext_keyans_addto_seq:n { #2 }
3528     \int_gincr:N \g__enumext_check_starred_cmd_int
3529     \bool_lazy_or:nnT
3530     { \bool_if_p:N \l__enumext_show_answer_bool }
3531     { \bool_if_p:N \l__enumext_show_position_bool }
3532     {
3533       \tl_set_eq:NN \l__enumext_label_v_tl \l__enumext_label_vi_tl
3534       \__enumext_keyans_show_left:n { #2 }
3535       \tl_set_eq:NN \l__enumext_label_vi_tl \l__enumext_label_v_tl
3536     }
3537   }
3538   \tl_use:N \l__enumext_label_font_style_v_tl
3539   \__enumext_wrapper_label_v:n { \l__enumext_label_vi_tl } \__enumext_keyans_show_item_opt:
3540 }
```

(End of definition for `__enumext_keyans_anspic_code:nnn`.)

11.40.2 The environment keyanspic

`keyanspic` Now we define the environment `keyanspic` based on list. The optional argument [*number above, number below*] will determine the number of `minipage` environments that will be above and below separated by `\parsep+\itemsep` within it.

```

3541 \NewDocumentEnvironment{keyanspic}{ o }
3542 {
3543   \__enumext_keyans_pic_safe_exec:
3544   \__enumext_start_list:nn
3545   { }
3546   {
3547     \__enumext_keyans_pic_arg_two:
3548   }

```

We apply the “adjusted” vertical spacing above the environment

```

3549   \vspace { \__enumext_keyans_pic_above_skip }
3550 }

```

If the optional argument is not present, the number of times the `\anspic` command appears will be counted from `\l__enumext_keyans_pic_body_seq` and placed in `minipage` environments on a single line. Finally we check if `\anspic*` has been used, set the counter to zero and apply our “adjusted” vertical space below the environment.

```

3551 {
3552   \tl_if_novalue:nTF { #1 }
3553   {
3554     \__enumext_keyans_pic_do:e { \seq_count:N \l__enumext_keyans_pic_body_seq }
3555   }
3556   { \__enumext_keyans_pic_do:n { #1 } }
3557   \__enumext_stop_list:
3558   \__enumext_check_starred_cmd:n { anspic }
3559   \setcounter { enumXvi } { 0 }
3560   \vspace { \__enumext_topsep_v_skip }
3561   %\bool_set_false:N \l__enumext_store_active_bool
3562 }

```

(End of definition for `keyanspic`. This function is documented on page 14.)

`__enumext_keyans_pic_safe_exec:` The function `__enumext_keyans_pic_safe_exec:` check nested and level position inside the `enumext` environment.

```

3563 \cs_new_protected:Nn \__enumext_keyans_pic_safe_exec:
3564 {
3565   \int_incr:N \l__enumext_keyans_pic_level_int
3566   \int_compare:nNnT { \l__enumext_keyans_pic_level_int } > { 1 }
3567   {
3568     \msg_error:nn { enumext } { keyanspic-nested }
3569   }
3570   \__enumext_keyans_start_line:
3571 }

```

(End of definition for `__enumext_keyans_pic_safe_exec:.`)

`__enumext_keyans_pic_skip_abs:N` The function `__enumext_keyans_pic_skip_abs:N` will return a positive value `\parsep`.

```

3572 \cs_new_protected:Npn \__enumext_keyans_pic_skip_abs:N #1
3573 {
3574   \dim_compare:nNnT { #1 } < { 0pt }
3575   { \skip_set:Nn #1 { -#1 } }
3576 }

```

(End of definition for `__enumext_keyans_pic_skip_abs:N`.)

`__enumext_keyans_pic_arg_two:` The function `__enumext_keyans_pic_arg_two:` will be used in the second argument of the `__enumext_start_list:nn` function that defines the `keyanspic` environment, it will handle the setting of spaces.

```

3577 \cs_new_protected:Nn \__enumext_keyans_pic_arg_two:
3578 {

```

The first thing to do is to set the boolean variable `\l__enumext_leftmargin_tmp_v_bool` handled by the `list-indent` key to false, then we copy the definition of the second list argument from the `keyans` environment.

```

3579   \bool_set_false:N \l__enumext_leftmargin_tmp_v_bool
3580   \__enumext_list_arg_two_v:

```

We will add the value of `\itemsep` to `\parsep` which we will use as vertical spacing between the above and below `minipage` environments. and adjust the value of `\leftmargin`, the label and counter are handled directly by the `\anspic` command. Then we make equal to zero `\labelwidth`, `\labelsep`, `\partopsep` and `\itemsep` so that the horizontal and vertical spacing is not affected.

```

3581 \skip_add:Nn \parsep { \itemsep }
3582 \dim_add:Nn \leftmargin { -\labelwidth - \labelsep }
3583 \dim_zero:N \labelwidth
3584 \dim_zero:N \listparindent
3585 \dim_zero:N \labelsep
3586 \skip_zero:N \partopsep
3587 \skip_zero:N \itemsep

```

We set the value of `\l__enumext_keyans_pic_above_skip` which we will use to apply our “adjust” space above `keyanspic`, finally we call `__enumext_item_std:w` followed by `\scan_stop:` to prevent the error message returned by \TeX when not using the `\item` command.

```

3588 \__enumext_keyans_pic_skip_abs:N \parsep
3589 \skip_set:Nn \l__enumext_keyans_pic_above_skip
3590 {
3591   \box_dp:N \strutbox
3592   + \l__enumext_topsep_v_skip
3593   - \parsep
3594 }
3595 \__enumext_item_std:w \scan_stop:
3596 }

```

(End of definition for `__enumext_keyans_pic_arg_two:`)

```

\__enumext_keyans_pic_do:n
\__enumext_keyans_pic_do:e

```

The optional argument is split by comma and is handled directly by the function `__enumext_keyans_pic_do:n` and passed to the function `__enumext_keyans_pic_row:n`.

```

3597 \cs_new_protected:Nn \__enumext_keyans_pic_do:n
3598 {
3599   \clist_map_function:nN { #1 } \__enumext_keyans_pic_row:n
3600 }
3601 \cs_generate_variant:Nn \__enumext_keyans_pic_do:n { e }

```

(End of definition for `__enumext_keyans_pic_do:n`)

```
\__enumext_keyans_pic_row:n
```

The function `__enumext_keyans_pic_row:n` will set the widths for the `minipage` environments and place the content $\langle stored \rangle$ by `\anspic*` in the `\l__enumext_keyans_pic_body_seq` sequence inside them.

```

3602 \cs_new_protected:Nn \__enumext_keyans_pic_row:n
3603 {
3604   \dim_set:Nn \l__enumext_keyans_pic_width_dim { \linewidth / #1 }
3605   \int_set:Nn \l__enumext_keyans_pic_above_int { \l__enumext_keyans_pic_below_int }
3606   \int_set:Nn \l__enumext_keyans_pic_below_int { \l__enumext_keyans_pic_above_int + #1 }
3607   \int_step_inline:nnn
3608     { \l__enumext_keyans_pic_above_int + 1 }
3609     { \l__enumext_keyans_pic_below_int }
3610     {
3611       \__enumext_minipage:w [ b ]{ \l__enumext_keyans_pic_width_dim }
3612       \centering
3613       \seq_item:Nn \l__enumext_keyans_pic_body_seq { ##1 }
3614       \__enumext_endminipage:
3615     }
3616   \par
3617 }

```

(End of definition for `__enumext_keyans_pic_row:n`)

11.41 The horizontal environments

Generating horizontal list environments is NOT as simple as standard \TeX list environments. The fundamental part of the code is adapted from the `shortlst` package to a more modern version using `expl3`. It is not possible to redefine `\item` and `\makelabel` as in the non starred versions (at least I have not achieved it) and as we will make it behave differently, we have no other option than to define a cascade of functions.

To achieve the horizontal list environment we will capture the `\item` command and the content of this in an plain `lrbox` box using `\makebox` for the `label` and a `minipage` environment for the content passed to `\item`, we will also add the optional argument ($\langle number \rangle$) to `\item` to be able to *join columns* horizontally, in simple terms, we want `\item` to behave in the same way as in the `enumext` environment but adding an optional first argument ($\langle number \rangle$).

11.41.1 Functions for item box width

`__enumext_starred_columns_set_vii:`
`__enumext_starred_columns_set_viii:`

We set the default value for the width of the box containing the content of the items and create `\itemwidththdim` in a public form.

```

3618 \cs_new_protected:Nn \__enumext_starred_columns_set_vii:
3619 {
3620   \dim_compare:nNnT { \l__enumext_columns_sep_vii_dim } = { \c_zero_dim }
3621   {
3622     \dim_set:Nn \l__enumext_columns_sep_vii_dim
3623     {
3624       ( \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim )
3625       / \l__enumext_columns_vii_int
3626     }
3627   }
3628   \int_set:Nn \l__enumext_tmpa_vii_int { \l__enumext_columns_vii_int - 1 }
3629   \dim_set:Nn \l__enumext_item_width_vii_dim
3630   {
3631     ( \linewidth - \l__enumext_columns_sep_vii_dim * \l__enumext_tmpa_vii_int )
3632     / \l__enumext_columns_vii_int - \l__enumext_labelwidth_vii_dim
3633     - \l__enumext_labelsep_vii_dim
3634   }
3635   %%\dim_zero_new:N \itemwidththdim
3636 }
3637 \cs_new_protected:Nn \__enumext_starred_columns_set_viii:
3638 {
3639   \dim_compare:nNnT { \l__enumext_columns_sep_viii_dim } = { \c_zero_dim }
3640   {
3641     \dim_set:Nn \l__enumext_columns_sep_viii_dim
3642     {
3643       ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim )
3644       / \l__enumext_columns_viii_int
3645     }
3646   }
3647   \int_set:Nn \l__enumext_tmpa_viii_int { \l__enumext_columns_viii_int - 1 }
3648   \dim_set:Nn \l__enumext_item_width_viii_dim
3649   {
3650     ( \linewidth - \l__enumext_columns_sep_viii_dim * \l__enumext_tmpa_viii_int )
3651     / \l__enumext_columns_viii_int - \l__enumext_labelwidth_viii_dim
3652     - \l__enumext_labelsep_viii_dim
3653   }
3654   %%\dim_zero_new:N \itemwidththdim
3655 }
```

(End of definition for `__enumext_starred_columns_set_vii:` and `__enumext_starred_columns_set_viii:`.)

11.41.2 Functions for join item columns

`__enumext_starred_joined_item_vii:n`
`__enumext_starred_joined_item_viii:n`

The functions `__enumext_starred_joined_item_vii:n` and `__enumext_starred_joined_item_viii:n` will set the *width* of the box in which the content passed to `\item(columns)` will be stored together with the value of `\itemwidththdim`.

```

3656 \cs_new_protected:Npn \__enumext_starred_joined_item_vii:n #1
3657 {
3658   \int_set:Nn \l__enumext_joined_item_vii_int {#1}
3659   \int_compare:nNnT { \l__enumext_joined_item_vii_int } > { \l__enumext_columns_vii_int }
3660   {
3661     \msg_warning:nnee { enumext } { item-joined }
3662     { \int_use:N \l__enumext_joined_item_vii_int }
3663     { \int_use:N \l__enumext_columns_vii_int }
3664     \int_set:Nn \l__enumext_joined_item_vii_int
3665     {
3666       \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1
3667     }
3668   }
3669   \int_compare:nNnT
3670   { \l__enumext_joined_item_vii_int }
3671   >
3672   { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1 }
3673   {
3674     \msg_warning:nnee { enumext } { item-joined-columns }
3675     { \int_use:N \l__enumext_joined_item_vii_int }
3676     {
3677       \int_eval:n
```

```

3678         { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1 }
3679     }
3680     \int_set:Nn \l__enumext_joined_item_vii_int
3681     {
3682         \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1
3683     }
3684 }
3685 \int_compare:nNnTF { \l__enumext_joined_item_vii_int } > { 1 }
3686 {
3687     \int_set_eq:NN \l__enumext_joined_item_aux_vii_int \l__enumext_joined_item_vii_int
3688     \int_decr:N \l__enumext_joined_item_aux_vii_int
3689     \int_add:Nn \l__enumext_item_column_pos_vii_int { \l__enumext_joined_item_aux_vii_int }
3690     \int_gadd:Nn \g__enumext_item_count_all_vii_int { \l__enumext_joined_item_aux_vii_int }
3691     \dim_set:Nn \l__enumext_joined_width_vii_dim
3692     {
3693         \l__enumext_item_width_vii_dim * \l__enumext_joined_item_vii_int
3694         + ( \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim
3695             + \l__enumext_columns_sep_vii_dim
3696             )*\l__enumext_joined_item_aux_vii_int
3697     }
3698     \dim_set_eq:NN \itemwidthdim \l__enumext_joined_width_vii_dim
3699 }
3700 {
3701     \dim_set_eq:NN \l__enumext_joined_width_vii_dim \l__enumext_item_width_vii_dim
3702     \dim_set_eq:NN \itemwidthdim \l__enumext_item_width_vii_dim
3703 }
3704 }
3705 \cs_new_protected:Npn \__enumext_starred_joined_item_viii:n #1
3706 {
3707     \int_set:Nn \l__enumext_joined_item_viii_int {#1}
3708     \int_compare:nNnT { \l__enumext_joined_item_viii_int } > { \l__enumext_columns_viii_int }
3709     {
3710         \msg_warning:nnee { enumext } { item-joined }
3711         { \int_use:N \l__enumext_joined_item_viii_int }
3712         { \int_use:N \l__enumext_columns_viii_int }
3713         \int_set:Nn \l__enumext_joined_item_viii_int
3714         {
3715             \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1
3716         }
3717     }
3718     \int_compare:nNnT
3719     { \l__enumext_joined_item_viii_int }
3720     >
3721     { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1 }
3722     {
3723         \msg_warning:nnee { enumext } { item-joined-columns }
3724         { \int_use:N \l__enumext_joined_item_viii_int }
3725         {
3726             \int_eval:n
3727             { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1 }
3728         }
3729         \int_set:Nn \l__enumext_joined_item_viii_int
3730         {
3731             \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1
3732         }
3733     }
3734     \int_compare:nNnTF { \l__enumext_joined_item_viii_int } > { 1 }
3735     {
3736         \int_set_eq:NN \l__enumext_joined_item_aux_viii_int \l__enumext_joined_item_viii_int
3737         \int_decr:N \l__enumext_joined_item_aux_viii_int
3738         \int_add:Nn \l__enumext_item_column_pos_viii_int { \l__enumext_joined_item_aux_viii_int }
3739         \int_gadd:Nn \g__enumext_item_count_all_viii_int { \l__enumext_joined_item_aux_viii_int }
3740         \dim_set:Nn \l__enumext_joined_width_viii_dim
3741         {
3742             \l__enumext_item_width_viii_dim * \l__enumext_joined_item_viii_int
3743             + ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim
3744                 + \l__enumext_columns_sep_viii_dim
3745                 )*\l__enumext_joined_item_aux_viii_int
3746         }
3747         \dim_set_eq:NN \itemwidthdim \l__enumext_joined_width_viii_dim
3748     }

```

```

3749     {
3750         \dim_set_eq:NN \l__enumext_joined_width_viii_dim \l__enumext_item_width_viii_dim
3751         \dim_set_eq:NN \itemwidthdim \l__enumext_item_width_viii_dim
3752     }
3753 }

```

(End of definition for __enumext_starred_joined_item_vii:n and __enumext_starred_joined_item_viii:n)

11.41.3 Functions for mini-env, mini-right and mini-right* keys

The implementation of the `mini-env` key support is almost identical to the one used in the `enumext` and `keyans` environments, the difference is that the `__enumext_mini_env*` environment on the “right side” is executed “after” closing the environment, so it is necessary to make a global copy of the variable `\l__enumext_minipage_right_vii_dim` in the variable `\g__enumext_minipage_right_vii_dim`.

```

3754 \cs_new_protected:Nn \__enumext_start_mini_vii:
3755 {
3756     \dim_compare:nNnT { \l__enumext_minipage_right_vii_dim } > { \c_zero_dim }
3757     {
3758         \dim_set:Nn \l__enumext_minipage_left_vii_dim
3759         {
3760             \linewidth
3761             - \l__enumext_minipage_right_vii_dim
3762             - \l__enumext_minipage_hsep_vii_dim
3763         }
3764         \bool_set_true:N \l__enumext_minipage_active_vii_bool
3765         \dim_gset_eq:NN
3766             \g__enumext_minipage_right_vii_dim
3767             \l__enumext_minipage_right_vii_dim
3768         \__enumext_mini_addvspace_vii:
3769         \nointerlineskip\noindent
3770         \begin{__enumext_mini_env*}{ \l__enumext_minipage_left_vii_dim }
3771     }
3772 }

```

The function `__enumext_stop_mini_vii:` closes the `__enumext_mini_env*` environment on the left side, applies `\hfill` and sets the value of the variable `\g__enumext_minipage_active_vii_bool` to true which will be used in the function `__enumext_after_env:nn` to execute the `__enumext_mini_env*` on the “right side”.

```

3773 \cs_new_protected:Nn \__enumext_stop_mini_vii:
3774 {
3775     \bool_if:NT \l__enumext_minipage_active_vii_bool
3776     {
3777         \end{__enumext_mini_env*}
3778         \hfill
3779         \bool_gset_true:N \g__enumext_minipage_active_vii_bool
3780     }
3781 }

```

Finally we execute the `{\code}` passed to the `mini-right` or `mini-right*` keys stored in the variable `\g__enumext_miniright_code_vii_tl` in the `__enumext_mini_env*` environment on the “right side”. For compatibility with the `caption` package and possibly other `{\code}` passed to this key, we will pass it to a box and then print it.

```

3782 \__enumext_after_env:nn {enumext*}
3783 {
3784     \bool_if:NT \g__enumext_minipage_active_vii_bool
3785     {
3786         \begin{__enumext_mini_env*}{ \g__enumext_minipage_right_vii_dim }
3787         \par\addvspace { \g__enumext_minipage_right_skip }
3788         \bool_if:NF \g__enumext_minipage_center_vii_bool
3789         {
3790             \tl_put_left:Nn \g__enumext_miniright_code_vii_tl
3791             {
3792                 \centering
3793             }
3794         }
3795         \vbox_set_top:Nn \l__enumext_miniright_code_vii_box
3796         {
3797             \tl_use:N \g__enumext_miniright_code_vii_tl
3798         }
3799         \box_use_drop:N \l__enumext_miniright_code_vii_box
3800         \end{__enumext_mini_env*}
3801         \par\addvspace{ \g__enumext_minipage_after_skip }

```

```

3802     }
3803     \bool_gset_false:N \g__enumext_minipage_active_vii_bool
3804     \bool_gset_true:N \g__enumext_minipage_center_vii_bool
3805     \tl_gclear:N \g__enumext_miniright_code_vii_tl
3806     \dim_gzero:N \g__enumext_minipage_right_vii_dim
3807     \bool_gset_false:N \g__enumext_starred_bool
3808 }

```

(End of definition for `__enumext_start_mini_vii:` and `__enumext_stop_mini_vii:`)

`__enumext_start_mini_viii:` The implementation of the `mini-env`, `mini-right` and `mini-right*` keys is identical to the one used in the `enumext*` environment.

```

3809 \cs_new_protected:Nn \__enumext_start_mini_viii:
3810 {
3811     \dim_compare:nNnT { \l__enumext_minipage_right_viii_dim } > { \c_zero_dim }
3812     {
3813         \dim_set:Nn \l__enumext_minipage_left_viii_dim
3814         {
3815             \linewidth
3816             - \l__enumext_minipage_right_viii_dim
3817             - \l__enumext_minipage_hsep_viii_dim
3818         }
3819         \bool_set_true:N \l__enumext_minipage_active_viii_bool
3820         \dim_gset_eq:NN
3821             \g__enumext_minipage_right_viii_dim
3822             \l__enumext_minipage_right_viii_dim
3823         \__enumext_mini_addvspace_viii:
3824         \nointerlineskip\noindent
3825         \begin{__enumext_mini_env*}{ \l__enumext_minipage_left_viii_dim }
3826     }
3827 }
3828 \cs_new_protected:Nn \__enumext_stop_mini_viii:
3829 {
3830     \bool_if:NT \l__enumext_minipage_active_viii_bool
3831     {
3832         \end{__enumext_mini_env*}
3833         \hfill
3834         \bool_gset_true:N \g__enumext_minipage_active_viii_bool
3835     }
3836 }
3837 \__enumext_after_env:nn {keyans*}
3838 {
3839     \bool_if:NT \g__enumext_minipage_active_viii_bool
3840     {
3841         \begin{__enumext_mini_env*}{ \g__enumext_minipage_right_viii_dim }
3842         \par\addvspace { \g__enumext_minipage_right_skip }
3843         \bool_if:NF \g__enumext_minipage_center_viii_bool
3844         {
3845             \tl_put_left:Nn \g__enumext_miniright_code_viii_tl
3846             {
3847                 \centering
3848             }
3849         }
3850         \vbox_set_top:Nn \l__enumext_miniright_code_viii_box
3851         {
3852             \tl_use:N \g__enumext_miniright_code_viii_tl
3853         }
3854         \box_use_drop:N \l__enumext_miniright_code_viii_box
3855         \end{__enumext_mini_env*}
3856         \par\addvspace{ \g__enumext_minipage_after_skip }
3857     }
3858     \bool_gset_false:N \g__enumext_minipage_active_viii_bool
3859     \bool_gset_true:N \g__enumext_minipage_center_viii_bool
3860     \tl_gclear:N \g__enumext_miniright_code_viii_tl
3861     \dim_gzero:N \g__enumext_minipage_right_viii_dim
3862 }

```

(End of definition for `__enumext_start_mini_viii:` and `__enumext_stop_mini_viii:`)

11.42 The environment enumext*

enumext* First we will generate the environment and we will give a temporary definition to `__enumext_stop_item_tmp_vii`: equal to `\noindent` and next to `\item` equal to `__enumext_start_item_tmp_vii`: which we will redefine later.

```

3863 \NewDocumentEnvironment{enumext*}{ o }
3864 {
3865   \__enumext_safe_exec_vii:
3866   \__enumext_parse_keys_vii:n {#1}
3867   \__enumext_starred_columns_set_vii:
3868   \__enumext_before_list_vii:
3869   \__enumext_start_store_level_vii:
3870   \__enumext_start_list:nn { }
3871   {
3872     \__enumext_list_arg_two_vii:
3873     \__enumext_before_keys_exec_vii:
3874   }
3875   \item[] \scan_stop:
3876   \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \noindent
3877   \cs_set_eq:NN \item \__enumext_start_item_tmp_vii:
3878 }
3879 {
3880   \__enumext_stop_item_tmp_vii:
3881   \__enumext_remove_extra_parsep_vii:
3882   \__enumext_stop_list:
3883   \__enumext_stop_store_level_vii:
3884   \__enumext_after_list_vii:
3885 }
```

(End of definition for `enumext*`. This function is documented on page 4.)

`__enumext_safe_exec_vii:` First check the maximum nesting level for the `enumext*` environment then set the vars `\l__enumext_starred_bool` and `\g__enumext_starred_bool`.

```

3886 \cs_new_protected:Nn \__enumext_safe_exec_vii:
3887 {
3888   \__enumext_internal_mini_page:
3889   \__enumext_is_not_nested:
3890   \int_incr:N \l__enumext_level_h_int
3891   \int_compare:nNnT { \l__enumext_level_h_int } > { 1 }
3892   {
3893     \msg_error:nn { enumext } { nested }
3894   }
3895   \bool_set_true:N \l__enumext_starred_bool
3896   \__enumext_is_on_first_level:
3897 }
```

(End of definition for `__enumext_safe_exec_vii:.`)

`__enumext_parse_keys_vii:n` Parse `[⟨key = val⟩]` for `enumext*`. If the variable `\l__enumext_store_active_bool` is true it will call the functions `__enumext_parse_series:n` and `__enumext_store_active_keys_vii:n` and reprocess the `⟨keys⟩` to pass them to the storage `⟨sequence⟩`.

```

3898 \cs_new_protected:Npn \__enumext_parse_keys_vii:n #1
3899 {
3900   \tl_if_novalue:nF {#1}
3901   {
3902     \str_clear:N \l__enumext_series_str
3903     \keys_set:nn { enumext / enumext* } {#1}
3904     \__enumext_parse_series:n {#1}
3905     \__enumext_store_active_keys_vii:n {#1}
3906     \__enumext_nested_base_line_fix:
3907   }
3908 }
```

(End of definition for `__enumext_parse_keys_vii:n.`)

`__enumext_before_list_vii:` The function `__enumext_before_list_vii:` will add the vertical spacing on the environment if the `above` key is active next to the `{⟨code⟩}` defined by the `before*` key if it is active, the call the function `__enumext_start_mini_vii:` handle by `mini-env`.

```

3909 \cs_new_protected:Nn \__enumext_before_list_vii:
3910 {
3911   \__enumext_vspace_above_vii:
```

```

3912     \__enumext_check_ans_active:
3913     \__enumext_before_args_exec_vii:
3914     \__enumext_start_mini_vii:
3915 }

```

(End of definition for __enumext_before_list_vii:.)

__enumext_after_list_vii:

The function __enumext_after_list: first call the function __enumext_stop_mini_vii:, then apply the `{\code}` handled by the `after` key together with the *vertical space* handled by the `below` key if they are present. Finally set false the vars \g__enumext_starred_bool and \l__enumext_starred_bool, save the *current value* of the counter in \g__enumext_resume_vii_int for the `resume` key. If the `save-ans` key is active, it will create the integer variable for the `resume` key, we only have to assign it the value of the current counter.

```

3916 \cs_new_protected:Nn \__enumext_after_list_vii:
3917 {
3918     \__enumext_stop_mini_vii:
3919     \__enumext_after_stop_list_vii:
3920     \__enumext_check_ans_key_hook:
3921     \__enumext_vspace_below_vii:
3922     \bool_set_false:N \l__enumext_starred_bool
3923     \__enumext_resume_save_counter:
3924 }

```

(End of definition for __enumext_after_list_vii:.)

__enumext_start_store_level_vii:

__enumext_stop_store_level_vii:

The __enumext_start_store_level_vii: and __enumext_stop_store_level_vii: functions activate the level saving mechanism for storage in *sequence* of the `\anskey` command if `enumext*` are nested in `enumext`.

```

3925 \cs_new_protected:Nn \__enumext_start_store_level_vii:
3926 {
3927     \bool_if:NT \l__enumext_store_active_bool
3928     {
3929         \int_compare:nNt { \l__enumext_level_int } > { 0 }
3930         {
3931             \__enumext_store_level_open_vii:
3932         }
3933     }
3934 }
3935 \cs_new_protected:Nn \__enumext_stop_store_level_vii:
3936 {
3937     \bool_if:NT \l__enumext_store_active_bool
3938     {
3939         \int_compare:nNt { \l__enumext_level_int } > { 0 }
3940         {
3941             \__enumext_store_level_close_vii:
3942         }
3943     }
3944 }

```

(End of definition for __enumext_start_store_level_vii: and __enumext_stop_store_level_vii:.)

11.42.1 The command \item in enumext*

__enumext_start_item_tmp_vii:

First we will call the function __enumext_stop_item_tmp_vii: that we will redefine later, we will increment the value of \l__enumext_item_column_pos_vii_int that will count the item's by rows and the value of \g__enumext_item_count_all_vii_int that will count the total of item's in the environment. After that we will call the function __enumext_item_peek_args_vii: that will handle the arguments passed to `\item`.

```

3945 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_vii:
3946 {
3947     \__enumext_stop_item_tmp_vii:
3948     \int_incr:N \l__enumext_item_column_pos_vii_int
3949     \int_gincr:N \g__enumext_item_count_all_vii_int
3950     \__enumext_item_peek_args_vii:
3951 }

```

(End of definition for __enumext_start_item_tmp_vii:.)

`__enumext_item_peek_args_vii:` The function `__enumext_item_peek_args_vii:` will handle the `\item(<number>)`. Look for the argument “(”, if it is present we will call the function `__enumext_joined_item_vii:w (<number>)`, which is in charge of joining the item’s in the same row, in case they are not present we will set the default value (1).

```

3952 \cs_new_protected:Nn \__enumext_item_peek_args_vii:
3953 {
3954   \peek_meaning:NTF (
3955     { \__enumext_joined_item_vii:w }
3956     { \__enumext_joined_item_vii:w (1) }
3957   }

```

(End of definition for `__enumext_item_peek_args_vii:.`)

`__enumext_joined_item_vii:w` The function `__enumext_joined_item_vii:w` will first call the function `__enumext_starred_joined_item_vii:n` in charge of setting the *width* of the box that will store the content passed to `\item`. Then we will look for the argument “*”, if it is present we will call the function `__enumext_starred_item_vii:w` otherwise we will call the function `__enumext_standar_item_vii:w`.

```

3958 \cs_new_protected:Npn \__enumext_joined_item_vii:w (#1)
3959 {
3960   \__enumext_starred_joined_item_vii:n {#1}
3961   \peek_meaning_remove:NTF *
3962     { \__enumext_starred_item_vii:w }
3963     { \__enumext_standar_item_vii:w }
3964 }

```

(End of definition for `__enumext_joined_item_vii:w`.)

`__enumext_standar_item_vii:w` The function `__enumext_standar_item_vii:w` will first look for the argument “[”, if present it will set the state of the variable `\l__enumext_wrap_label_opt_vii_bool` equal to the state of the variable `\l__enumext_wrap_label_opt_vii_bool` handled by the key `wrap-label*` and finally execute the *non-enumerated* version `\item[<custom>]` by means of the function `__enumext_start_item_vii:w`, otherwise we will set the value of the variable `\l__enumext_wrap_label_vii_bool` handled by the `wrap-label` key to true and set the switch `\if@noitemarg` to true to execute the enumerated version of `\item` by means of the function `__enumext_start_item_vii:w [\l__enumext_label_vii_tl]`.

```

3965 \cs_new_protected:Npn \__enumext_standar_item_vii:w
3966 {
3967   \bool_set_false:N \l__enumext_item_starred_vii_bool
3968   \peek_meaning:NTF [
3969     {
3970       \bool_set_eq:NN
3971         \l__enumext_wrap_label_vii_bool
3972         \l__enumext_wrap_label_opt_vii_bool
3973       \__enumext_start_item_vii:w
3974     }
3975     {
3976       \bool_set_true:N \l__enumext_wrap_label_vii_bool
3977       \legacy_if_set_true:n { @noitemarg }
3978       \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
3979     }
3980   }

```

(End of definition for `__enumext_standar_item_vii:w`.)

`__enumext_starred_item_vii:w`
`__enumext_starred_item_vii_aux_i:w`
`__enumext_starred_item_vii_aux_ii:w`
`__enumext_starred_item_vii_aux_iii:w` The function `__enumext_starred_item_vii:w` together with the specified auxiliary functions `aux_i:w`, `aux_ii:w`, and `aux_iii:w` execute `\item*`, `\item* [<symbol>]` and `\item* [<symbol>] [<offset>]`.

```

3981 \cs_new_protected:Npn \__enumext_starred_item_vii:w
3982 {
3983   \bool_set_true:N \l__enumext_item_starred_vii_bool
3984   \bool_set_true:N \l__enumext_wrap_label_vii_bool
3985   \peek_meaning:NTF [
3986     { \__enumext_starred_item_vii_aux_i:w }
3987     { \__enumext_starred_item_vii_aux_ii:w }
3988   }
3989   \cs_new_protected:Npn \__enumext_starred_item_vii_aux_i:w [#1]
3990   {
3991     \tl_gset:Nn \g__enumext_item_symbol_aux_vii_tl {#1}
3992     \__enumext_starred_item_vii_aux_ii:w
3993   }
3994   \cs_new_protected:Npn \__enumext_starred_item_vii_aux_ii:w

```

```

3995 {
3996   \peek_meaning:NTF [
3997     { \__enumext_starred_item_vii_aux_iii:w }
3998     {
3999       \dim_set_eq:NN
4000       \l__enumext_item_symbol_sep_vii_dim
4001       \l__enumext_labelsep_vii_dim
4002       \legacy_if_set_true:n { @noitemarg }
4003       \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
4004     }
4005   }
4006   \cs_new_protected:Npn \__enumext_starred_item_vii_aux_iii:w [#1]
4007   {
4008     \dim_set:Nn \l__enumext_item_symbol_sep_vii_dim {#1}
4009     \legacy_if_set_true:n { @noitemarg }
4010     \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ]
4011   }

```

(End of definition for `__enumext_starred_item_vii:w` and others.)

11.42.2 Real definition of `\item` in `enumext*`

`__enumext_start_item_vii:w`

The functions `__enumext_start_item_vii:w` and `__enumext_stop_item_vii:` executing the true definition of `\item` inside the `enumext*` environment.

The first thing we will do is set the value of `__enumext_stop_item_tmp_vii:` equal to `__enumext_stop_item_vii:` which we will define later and add the `hyperref` compatible `enumXvii` counter, after that we will start capturing the item content in a box. Here need setting the `\if@hyper@item` switch to “true” for `hyperref` compatible. The explanation for this is given by the master Heiko Oberdiek on `\refstepcounter{enumi}` twice (or more) creates destination with the same identifier.

```

4012 \cs_new_protected_nopar:Npn \__enumext_start_item_vii:w [#1]
4013 {
4014   \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \__enumext_stop_item_vii:
4015   \legacy_if:nT { @noitemarg }
4016   {
4017     \legacy_if_set_false:n { @noitemarg }
4018     \legacy_if:nT { @nmbrrlist }
4019     {
4020       \bool_if:NT \l__enumext_hyperref_bool
4021       {
4022         \legacy_if_set_true:n { @hyper@item }
4023       }
4024       \refstepcounter{enumXvii}
4025       \bool_if:NT \l__enumext_check_answers_bool
4026       {
4027         \int_gincr:N \g__enumext_item_number_int
4028         \bool_set_true:N \l__enumext_item_number_bool
4029       }
4030     }
4031   }

```

Here we start capturing `\item` and its contents into a group using the plain form of the `lrbox` environment. If the state of the variable `\l__enumext_footnotes_key_bool` is false, we will redefine the command `\footnote`, followed by printing the `<symbol>` defined for `\item*` if it is present and open a new group inside which we execute `font key` next to `\item` and the keys `wrap-label`, `wrap-label*`, `align`, close the group and execute the key `labelsep` and then the key `first`. Finally we open the `minipage` environment and execute the `listparindent` key which will be equal to `\parindent`, the `parsep` key which will be equal to `\parskip` and the `itemindent` key.

```

4032 \group_begin:
4033   \lrbox{ \l__enumext_item_text_vii_box }
4034   \bool_if:NF \l__enumext_footnotes_key_bool
4035   {
4036     \__enumext_renew_footnote:
4037   }
4038   \bool_if:NT \l__enumext_item_starred_vii_bool
4039   {
4040     \tl_if_blank:VT \g__enumext_item_symbol_aux_vii_tl
4041     {
4042       \tl_gset_eq:NN
4043       \g__enumext_item_symbol_aux_vii_tl \l__enumext_item_symbol_vii_tl
4044     }
4045     \mode_leave_vertical:

```

```

4046         \skip_horizontal:n { -\l__enumext_item_symbol_sep_vii_dim }
4047         \makebox[ 0pt ][ r ]{ \g__enumext_item_symbol_aux_vii_tl }
4048         \skip_horizontal:N \l__enumext_item_symbol_sep_vii_dim
4049         \tl_gclear:N \g__enumext_item_symbol_aux_vii_tl
4050     }
4051     \group_begin:
4052     \tl_use:N \l__enumext_label_font_style_vii_tl
4053     \bool_if:NTF \l__enumext_wrap_label_vii_bool
4054     {
4055         \makebox[ \l__enumext_labelwidth_vii_dim ][ \l__enumext_align_label_vii_str ]
4056         { \__enumext_wrapper_label_vii:n {#1} }
4057     }
4058     {
4059         \makebox[ \l__enumext_labelwidth_vii_dim ][ \l__enumext_align_label_vii_str ]{ #1 }
4060     }
4061     \group_end:
4062     \skip_horizontal:N \l__enumext_labelsep_vii_dim
4063     \tl_use:N \l__enumext_after_list_args_vii_tl
4064     \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_vii_dim }
4065     \skip_set_eq:NN \parindent \l__enumext_listparindent_vii_dim
4066     \skip_set_eq:NN \parskip \l__enumext_parsep_vii_skip
4067     \tl_use:N \l__enumext_fake_item_indent_vii_tl
4068 }

```

(End of definition for __enumext_start_item_vii:w.)

__enumext_stop_item_vii: The function __enumext_stop_item_vii: shall terminate with the capture of \item and its *contents*. Close the environments minipage, lrbox and the group. Then we only have to set the width of the box and print it next to \footnote, and add the horizontal and vertical separation between the boxes.

```

4069 \cs_new_protected_nopar:Nn \__enumext_stop_item_vii:
4070 {
4071     \__enumext_endminipage:
4072     \endlrbox
4073     \group_end:
4074     \box_set_wd:Nn \l__enumext_item_text_vii_box
4075     {
4076         \l__enumext_joined_width_vii_dim
4077         + \l__enumext_labelwidth_vii_dim
4078         + \l__enumext_labelsep_vii_dim
4079     }
4080     \int_set:Nn \hbadness { 10000 }
4081     \box_use_drop:N \l__enumext_item_text_vii_box
4082     \bool_if:NF \l__enumext_footnotes_key_bool
4083     {
4084         \__enumext_print_footnote:
4085     }
4086     \int_compare:nNnTF { \l__enumext_item_column_pos_vii_int } = { \l__enumext_columns_vii_int }
4087     {
4088         \par\noindent
4089         \int_zero:N \l__enumext_item_column_pos_vii_int
4090     }
4091     { \hspace{ \l__enumext_columns_sep_vii_dim } }
4092 }

```

(End of definition for __enumext_stop_item_vii:.)

__enumext_remove_extra_parsep_vii: Finally we will remove the vertical space equal to \parsep when the total number of items is divisible by the number of items in the last row of the environment.

```

4093 \cs_new_protected:Nn \__enumext_remove_extra_parsep_vii:
4094 {
4095     \int_compare:nNnTF
4096     {
4097         \int_mod:nn { \g__enumext_item_count_all_vii_int } { \l__enumext_columns_vii_int }
4098     }
4099     =
4100     { 0 }
4101     {
4102         \par
4103         \vspace{ -\l__enumext_itemsep_vii_skip }
4104         \int_gzero:N \g__enumext_item_count_all_vii_int
4105     }
4106 }

```

(End of definition for `__enumext_remove_extra_parsep_viii:`)

As we don't want our check to be executed `check-ans` by levels but on the complete list, we will take it out of the `enumext*` environment using the “hook” function `__enumext_after_env:nn`.

```
4107 \__enumext_after_env:nn {enumext*} { \__enumext_execute_after_env: }
```

11.43 The environment `keyans*`

`keyans*` First we will generate the environment and we will give a temporary definition to `__enumext_stop_item_tmp_viii:` equal to `\noindent` and next to `\item` equal to `__enumext_start_item_tmp_viii:` which we will redefine later.

```
4108 \NewDocumentEnvironment{keyans*}{o }
4109 {
4110   \__enumext_safe_exec_viii:
4111   \__enumext_parse_keys_viii:n {#1}
4112   \__enumext_starred_columns_set_viii:
4113   \__enumext_before_list_viii:
4114   \__enumext_start_list:nn { }
4115   {
4116     \__enumext_list_arg_two_viii:
4117     \__enumext_before_keys_exec_viii:
4118   }
4119   \item[] \scan_stop:
4120   \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \noindent
4121   \cs_set_eq:NN \item \__enumext_start_item_tmp_viii:
4122 }
4123 {
4124   \__enumext_stop_item_tmp_viii:
4125   \__enumext_remove_extra_parsep_viii:
4126   \__enumext_check_starred_cmd:n { item }
4127   \__enumext_stop_list:
4128   \__enumext_after_list_viii:
4129 }
```

(End of definition for `keyans*`. This function is documented on page 13.)

`__enumext_safe_exec_viii:` First check the maximum nesting level for the `keyans*` environment.

```
4130 \cs_new_protected:Nn \__enumext_safe_exec_viii:
4131 {
4132   \int_incr:N \__enumext_keyans_level_h_int
4133   \int_compare:nNt { \__enumext_keyans_level_h_int } > { 1 }
4134   {
4135     \msg_error:nn { enumext } { nested }
4136   }
4137   \__enumext_keyans_start_line:
4138   % Set false for interfering with enumext nested in keyans* (yes, its possible and crayze)
4139   \bool_set_false:N \__enumext_store_active_bool
4140   \int_compare:nNt { \__enumext_level_int } > { 1 }
4141   {
4142     \msg_error:nn { enumext } { keyans-wrong-level }
4143   }
4144 }
```

(End of definition for `__enumext_safe_exec_viii:`)

`__enumext_parse_keys_viii:n` Parse [`key = val`] for `keyans*`.

```
4145 \cs_new_protected:Npn \__enumext_parse_keys_viii:n #1
4146 {
4147   \tl_if_no_value:nF {#1}
4148   {
4149     \keys_set:nn { enumext / keyans* } {#1}
4150   }
4151 }
```

(End of definition for `__enumext_parse_keys_viii:n`)

`__enumext_before_list_viii:` The function `__enumext_before_list_viii:` will add the vertical spacing on the environment if the `above` key is active next to the `{code}` defined by the `before*` key if it is active, the call the function `__enumext_start_mini_viii:` handle by `mini-env`.

```
4152 \cs_new_protected:Nn \__enumext_before_list_viii:
4153 {
4154   \__enumext_vspace_above_viii:
```

```

4155     \__enumext_before_args_exec_viii:
4156     \__enumext_start_mini_viii:
4157 }

```

(End of definition for __enumext_before_list_viii:.)

__enumext_after_list_viii: The function __enumext_after_list: first call the function __enumext_stop_mini_viii:, then apply the `{\code}` handled by the *after* key together with the *vertical space* handled by the *below* key if they are present.

```

4158 \cs_new_protected:Nn \__enumext_after_list_viii:
4159 {
4160     \__enumext_stop_mini_viii:
4161     \__enumext_after_stop_list_viii:
4162     \__enumext_vspace_below_viii:
4163 }

```

(End of definition for __enumext_after_list_viii:.)

11.43.1 The command \item in keyans*

The idea here is to make the `\item` command behave in the same way as in the *keyans* environment with the difference of the optional argument (*number*) which works in the same way as in the *enumext** environment. In simple terms we want to store the *label* next to the *[content]* if it is present in the *sequence* and *prop list* defined by *save-ans* key for `\item*`, `\item*[\content]`, `\item(\number)*` and `\item(\number)*[\content]` commands.

__enumext_start_item_tmp_viii: First we will call the function __enumext_stop_item_tmp_viii: that we will redefine later, we will increment the value of __enumext_item_column_pos_viii_int that will count the item's by rows and the value of \g__enumext_item_count_all_viii_int that will count the total of item's in the environment. After that we will call the function __enumext_item_peek_args_viii: that will handle the arguments passed to `\item`.

```

4164 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_viii:
4165 {
4166     \__enumext_stop_item_tmp_viii:
4167     \int_incr:N \__enumext_item_column_pos_viii_int
4168     \int_gincr:N \g__enumext_item_count_all_viii_int
4169     \__enumext_item_peek_args_viii:
4170 }

```

(End of definition for __enumext_start_item_tmp_viii:.)

__enumext_item_peek_args_viii: The function __enumext_item_peek_args_viii: will handle the `\item(\number)`. Look for the argument “(”, if it is present we will call the function __enumext_joined_item_viii:w (*number*), which is in charge of joining the item's in the same row, in case they are not present we will set the default value (1).

```

4171 \cs_new_protected:Nn \__enumext_item_peek_args_viii:
4172 {
4173     \peek_meaning:NTF (
4174     { \__enumext_joined_item_viii:w }
4175     { \__enumext_joined_item_viii:w (1) }
4176 }

```

(End of definition for __enumext_item_peek_args_viii:.)

__enumext_joined_item_viii:w The function __enumext_joined_item_viii:w will first call the function __enumext_starred_joined_item_viii:n in charge of setting the *width* of the box that will store the content passed to `\item`. Then we will look for the argument “*”, if it is present we will call the function __enumext_starred_item_viii:w otherwise we will call the function __enumext_standar_item_viii:w.

```

4177 \cs_new_protected:Npn \__enumext_joined_item_viii:w (#1)
4178 {
4179     \__enumext_starred_joined_item_viii:n {#1}
4180     \peek_meaning_remove:NTF *
4181     { \__enumext_starred_item_viii:w }
4182     { \__enumext_standar_item_viii:w }
4183 }

```

(End of definition for __enumext_joined_item_viii:w.)

_enumext_standar_item_viii:w

The function _enumext_standar_item_viii:w will first look for the argument “[”, if present it will set the state of the variable _enumext_wrap_label_opt_viii_bool equal to the state of the variable _enumext_wrap_label_opt_viii_bool handled by the key `wrap-label*` and finally execute the *non-enumerated* version `\item[⟨custom⟩]` by means of the function _enumext_start_item_viii:w, otherwise we will set the value of the variable _enumext_wrap_label_viii_bool handled by the `wrap-label` key to true and set the switch `\if@noitemarg` to true to execute the enumerated version of `\item` by means of the function _enumext_start_item_viii:w [_enumext_label_viii_tl].

```
4184 \cs_new_protected:Npn \_enumext_standar_item_viii:w
4185 {
4186   \bool_set_false:N \_enumext_item_starred_viii_bool
4187   \peek_meaning:NTF [
4188     {
4189       \bool_set_eq:NN
4190         \_enumext_wrap_label_viii_bool
4191         \_enumext_wrap_label_opt_viii_bool
4192       \_enumext_start_item_viii:w
4193     }
4194     {
4195       \bool_set_true:N \_enumext_wrap_label_viii_bool
4196       \legacy_if_set_true:n { @noitemarg }
4197       \_enumext_start_item_viii:w [ \_enumext_label_viii_tl ]
4198     }
4199   }
```

(End of definition for _enumext_standar_item_viii:w.)

_enumext_starred_item_viii:w

The function _enumext_starred_item_viii:w together with the specified auxiliary functions `aux_i:w` and `aux_ii:w` execute `\item*` and `\item*[⟨content⟩]`.

_enumext_starred_item_viii_aux_i:w

_enumext_starred_item_viii_aux_ii:w

```
4200 \cs_new_protected:Npn \_enumext_starred_item_viii:w
4201 {
4202   \bool_set_true:N \_enumext_item_starred_viii_bool
4203   \bool_set_true:N \_enumext_wrap_label_viii_bool
4204   \peek_meaning:NTF [
4205     { \_enumext_starred_item_viii_aux_i:w }
4206     { \_enumext_starred_item_viii_aux_ii:w }
4207   }
```

The function _enumext_starred_item_viii_aux_i:w will save the optional argument to `\item*` in `_enumext_store_current_opt_arg_tl` and will save this argument along with the spacing set by the key `save-sep` in variable `_enumext_store_current_label_tl` if present, then call the function _enumext_starred_item_viii_aux_ii:w.

```
4208 \cs_new_protected:Npn \_enumext_starred_item_viii_aux_i:w [#1]
4209 {
4210   \tl_clear:N \_enumext_store_current_label_tl
4211   \tl_if_no_value:nF { #1 }
4212   {
4213     \tl_if_empty:NF \_enumext_store_keyans_item_opt_sep_tl
4214     {
4215       \tl_put_right:Ne \_enumext_store_current_label_tl { \_enumext_store_keyans_item_opt_sep_tl }
4216       \tl_put_right:Ne \_enumext_store_current_label_tl { #1 }
4217     }
4218     \tl_set:Ne \_enumext_store_current_opt_arg_tl { #1 }
4219   }
4220   \_enumext_starred_item_viii_aux_ii:w
4221 }
4222 \cs_new_protected:Npn \_enumext_starred_item_viii_aux_ii:w
4223 {
4224   \legacy_if_set_true:n { @noitemarg }
4225   \_enumext_start_item_viii:w [ \_enumext_label_viii_tl ]
4226 }
```

(End of definition for _enumext_starred_item_viii:w, _enumext_starred_item_viii_aux_i:w, and _enumext_starred_item_viii_aux_ii:w.)

_enumext_starred_item_exec:

The function _enumext_starred_item_exec: will be in charge of storing the current *⟨label⟩* for `\item*` followed by the `[⟨content⟩]` for `\item*[⟨content⟩]` if present in the *⟨sequence⟩* and *⟨prop list⟩* set by the `save-ans` key. In this same function the keys `show-ans`, `show-pos` and `save-ref` are implemented.

```
4227 \cs_new_protected:Nn \_enumext_starred_item_exec:
```

```

4228 {
4229   \tl_put_left:Ne \l__enumext_store_current_label_tl { \l__enumext_label_viii_tl }
4230   \__enumext_store_addto_prop:V \l__enumext_store_current_label_tl
4231   \__enumext_keyans_store_ref:
4232   \tl_put_left:Ne \l__enumext_store_current_label_tl { \item }
4233   \__enumext_keyans_addto_seq_link:
4234   \int_gincr:N \g__enumext_check_starred_cmd_int
4235   \bool_if:NT \l__enumext_show_answer_bool
4236   {
4237     \__enumext_print_keyans_box:NN \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
4238   }
4239   \bool_if:NT \l__enumext_show_position_bool
4240   {
4241     \tl_set:Ne \l__enumext_mark_answer_sym_tl
4242     {
4243       \group_begin:
4244       \exp_not:N \normalfont
4245       \exp_not:N \footnotesize [ \int_eval:n
4246       {
4247         \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
4248       }
4249       ]
4250       \group_end:
4251     }
4252     \__enumext_print_keyans_box:NN \l__enumext_labelwidth_i_dim \l__enumext_labelsep_i_dim
4253   }
4254 }

```

(End of definition for `__enumext_starred_item_exec:`)

Real definition of `\item` in `keyans*`

The implementation at this point is very similar to that of the `enumext*` environment.

```

4255 \cs_new_protected_nopar:Npn \__enumext_start_item_viii:w [#1]
4256 {
4257   \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \__enumext_stop_item_viii:
4258   \legacy_if:nT { @noitemarg }
4259   {
4260     \legacy_if_set_false:n { @noitemarg }
4261     \legacy_if:nT { @nmbrrlist }
4262     {
4263       \bool_if:NT \l__enumext_hyperref_bool
4264       {
4265         \legacy_if_set_true:n { @hyper@item }
4266       }
4267       \refstepcounter{enumXviii}
4268     }
4269   }

```

Here we start capturing `\item` and its contents into a group using the plain form of the `lrbox` environment.

```

4270   \group_begin:
4271   \lrbox{ \l__enumext_item_text_viii_box }
4272   \bool_if:NF \l__enumext_footnotes_key_bool
4273   {
4274     \__enumext_renew_footnote:
4275   }
4276   \bool_if:NT \l__enumext_item_starred_viii_bool
4277   {
4278     \__enumext_starred_item_exec:
4279   }
4280   \group_begin:
4281   \tl_use:N \l__enumext_label_font_style_viii_tl
4282   \bool_if:NTF \l__enumext_wrap_label_viii_bool
4283   {
4284     \makebox[ \l__enumext_labelwidth_viii_dim ][ \l__enumext_align_label_viii_str ]
4285     { \__enumext_wrapper_label_viii:n {#1} }
4286   }
4287   {
4288     \makebox[ \l__enumext_labelwidth_viii_dim ][ \l__enumext_align_label_viii_str ]{ #1
4289   }
4290   \group_end:
4291   \skip_horizontal:N \l__enumext_labelsep_viii_dim

```

```

4292 \tl_use:N \l__enumext_after_list_args_viii_tl
4293 \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_viii_dim }
4294 \skip_set_eq:NN \parindent \l__enumext_listparindent_viii_dim
4295 \skip_set_eq:NN \parskip \l__enumext_parsep_viii_skip
4296 \bool_if:NT \l__enumext_item_starred_viii_bool
4297 {
4298   \tl_use:N \l__enumext_fake_item_indent_viii_tl
4299   \__enumext_keyans_show_item_opt:
4300   \skip_horizontal:n { -\l__enumext_fake_item_indent_viii_dim - \l__enumext_labelsep_viii_dim }
4301 }
4302 {
4303   \tl_use:N \l__enumext_fake_item_indent_viii_tl
4304 }
4305 }

```

(End of definition for `__enumext_start_item_viii:w`.)

`__enumext_stop_item_viii:` The function `__enumext_stop_item_viii:` shall terminate with the capture of `\item` and its *contents*. Close the environments `minipage`, `lrbox` and the group. Then we only have to set the width of the box and print it next to `\footnote`, and add the horizontal and vertical separation between the boxes.

```

4306 \cs_new_protected_nopar:Nn \__enumext_stop_item_viii:
4307 {
4308   \__enumext_endminipage:
4309   \endlrbox
4310   \group_end:
4311   \box_set_wd:Nn \l__enumext_item_text_viii_box
4312   {
4313     \l__enumext_joined_width_viii_dim
4314     + \l__enumext_labelwidth_viii_dim
4315     + \l__enumext_labelsep_viii_dim
4316   }
4317   \int_set:Nn \hbadness { 10000 }
4318   \box_use_drop:N \l__enumext_item_text_viii_box
4319   \bool_if:NF \l__enumext_footnotes_key_bool
4320   {
4321     \__enumext_print_footnote:
4322   }
4323   \int_compare:nNnTF
4324   { \l__enumext_item_column_pos_viii_int } = { \l__enumext_columns_viii_int }
4325   {
4326     \par\noindent
4327     \int_zero:N \l__enumext_item_column_pos_viii_int
4328   }
4329   { \hspace{ \l__enumext_columns_sep_viii_dim } }
4330 }

```

(End of definition for `__enumext_stop_item_viii:`.)

`__enumext_remove_extra_parsep_viii:` Finally we will remove the vertical space equal to `\parsep` when the total number of items is divisible by the number of items in the last row of the environment.

```

4331 \cs_new_protected:Nn \__enumext_remove_extra_parsep_viii:
4332 {
4333   \int_compare:nNnT
4334   {
4335     \int_mod:nn
4336     { \g__enumext_item_count_all_viii_int }
4337     { \l__enumext_columns_viii_int }
4338   }
4339   =
4340   { 0 }
4341   {
4342     \par
4343     \vspace{ -\l__enumext_itemsep_viii_skip }
4344     \int_gzero:N \g__enumext_item_count_all_viii_int
4345   }
4346 }

```

(End of definition for `__enumext_remove_extra_parsep_viii:`.)

11.44 The command \getkeyans

`\getkeyans` The `\getkeyans` command takes a mandatory argument of the form $\langle store\ name : position \rangle$. Retrieve a “single” content stored by `\anskey`, `\anspic*` and `\item*` from $\langle prop\ list \rangle$ defined by `save-ans` key.

```
4347 \NewDocumentCommand \getkeyans { m }
4348 {
4349   \exp_args:Ne \__enumext_getkeyans_aux:n
4350   { \tl_to_str:e { \text_expand:n {#1} } }
4351 }
```

(End of definition for `\getkeyans`. This function is documented on page 15.)

`__enumext_getkeyans_aux:n` The internal function `__enumext_getkeyans_aux:n` is in charge of *splitting* the $\langle argument \rangle$ using “:”. If “:” is omitted it will return an error.

```
4352 \cs_new_protected:Npn \__enumext_getkeyans_aux:n #1
4353 {
4354   \str_if_in:nnTF {#1} { : }
4355   {
4356     \use:e
4357     {
4358       \cs_set:Npn \exp_not:N \__enumext_tmp:w ##1 \c_colon_str ##2 \scan_stop:
4359       { {##1} {##2} }
4360     }
4361     \exp_after:wN \__enumext_getkeyans:nn \__enumext_tmp:w #1 \scan_stop:
4362   }
4363   { \msg_error:nnn { enumext } { missing-colon } {#1} }
4364 }
```

(End of definition for `__enumext_getkeyans_aux:n`.)

`__enumext_getkeyans:nn` The internal function `__enumext_getkeyans:nn` will check for the existence of the $\langle prop\ list \rangle$, if it does not exist it will return an error message, then it will fetch the content specified by the second $\langle argument \rangle$ from $\langle prop\ list \rangle$.

```
4365 \cs_new_protected:Npn \__enumext_getkeyans:nn #1 #2
4366 {
4367   \prop_if_exist:cF { g__enumext_#1_prop }
4368   { \msg_error:nnn { enumext } { undefined-storage-anskey } {#1} }
4369   \group_begin:
4370   \prop_item:cn { g__enumext_#1_prop }{#2}
4371   \group_end:
4372 }
```

(End of definition for `__enumext_getkeyans:nn`.)

11.45 The command \printkeyans

The `\printkeyans` command prints “all stored content” in the $\langle sequence \rangle$ defined by the `save-ans` key. The first thing we will do is define a set of $\langle filtered\ keys \rangle$ with which we will control the options of the different nesting levels for the environment `enumext` and `enumext*` by storing their values in the list of tokens `__enumext_print_keyans_X_tl`.

The variable `__enumext_print_keyans_starred_tl` will have the default $\langle keys \rangle$ for `\printkeyans*` and will be set by `\setenumext[$\langle print^* \rangle$]` and the variable `__enumext_print_keyans_vii_tl` will have the default keys for the environment `enumext*` nested within the $\langle sequence \rangle$ and will be set by `\setenumext[$\langle print,^* \rangle$]`, the rest of the variables will be for the environment `enumext` and will be set by `\setenumext[$\langle print, level \rangle$]`

```
4373 \cs_generate_variant:Nn \keys_precompile:nnN { neN }
4374 \keys_define:nn { enumext / print }
4375 {
4376   print* .code:n = \keys_precompile:neN { enumext / enumext* }
4377               { \__enumext_filter_save_key:n {#1} }
4378               \__enumext_print_keyans_starred_tl, % starred cmd
4379   print* .initial:n = { nosep, label=\arabic*., columns=2, first=\small, font=\small },
4380   print-1 .code:n = \keys_precompile:neN { enumext / level-1 }
4381                  { \__enumext_filter_save_key:n {#1} }
4382                  \__enumext_print_keyans_ii_tl,
4383   print-1 .initial:n = { nosep, label=\arabic*., columns=2, first=\small, font=\small },
4384   print-2 .code:n = \keys_precompile:neN { enumext / level-2 }
4385                  { \__enumext_filter_save_key:n {#1} }
4386                  \__enumext_print_keyans_ii_tl,
4387   print-2 .initial:n = { nosep, label=(\alph*), first=\small, font=\small },
4388   print-3 .code:n = \keys_precompile:neN { enumext / level-3 }
```

```

4389         { \__enumext_filter_save_key:n {#1} }
4390         \__enumext_print_keyans_iii_tl,
4391     print-3 .initial:n = { nosep, label=\roman*., first=\small, font=\small },
4392     print-4 .code:n    = \keys_precompile:neN { enumext / level-4 }
4393         { \__enumext_filter_save_key:n {#1} }
4394         \__enumext_print_keyans_iv_tl,
4395     print-4 .initial:n = { nosep, label=\Alph*., first=\small, font=\small },
4396     print-* .code:n    = \keys_precompile:neN { enumext / enumext* }
4397         { \__enumext_filter_save_key:n {#1} }
4398         \__enumext_print_keyans_vii_tl, % starred nested
4399     print-* .initial:n = { nosep, label=\arabic*., first=\small, font=\small },
4400 }

```

• The reason for storing $\langle keys \rangle$ in token lists using `\keys_precompile:neN` is because the keys are set via `\setenumext` but are later executed by running the command `\printkeyans` and they are not handled directly by its optional argument, except those related to the first opening level.

`\printkeyans` Create a user command to print “all stored content” in $\langle sequence \rangle$ for $\backslash anskey$, $anskey^*$, $\backslash item^*$ and $\backslash anspic^*$. Within a group we will run our “precompiled keys” and then call the internal function `__enumext_printkeyans:nnn`.

```

4401 \NewDocumentCommand \printkeyans { s O{ } m }
4402 {
4403     \group_begin:
4404         \tl_use:N \__enumext_print_keyans_i_tl
4405         \tl_use:N \__enumext_print_keyans_ii_tl
4406         \tl_use:N \__enumext_print_keyans_iii_tl
4407         \tl_use:N \__enumext_print_keyans_iv_tl
4408         \tl_use:N \__enumext_print_keyans_vii_tl
4409         \__enumext_printkeyans:nnn { #1 } { #2 } { #3 }
4410     \group_end:
4411 }

```

(End of definition for `\printkeyans`. This function is documented on page 16.)

`__enumext_printkeyans:nnn` The internal function `__enumext_printkeyans:nnn` will check for the existence of the $\langle sequence \rangle$, if it does not exist it will return an error message, then it will check if not empty.

```

4412 \cs_new_protected:Npn \__enumext_printkeyans:nnn #1 #2 #3
4413 {
4414     \seq_if_exist:cTF { g__enumext_#3_seq }
4415     {
4416         \seq_if_empty:cF { g__enumext_#3_seq }
4417         {
4418             %%\seq_show:c { g__enumext_#3_seq }

```

If the starred argument is present we will check that the environment `enumext^*` is not saved in the $\langle sequence \rangle$, then execute the variable `__enumext_print_keyans_starred_tl` that contains the default $\langle keys \rangle$ for the environment `enumext^*`, it will open the environment `enumext^*` passing the optional argument to the “first level”, set the key `base-fix` and then will map the $\langle sequence \rangle$.

```

4419         \bool_if:nTF {#1}
4420         {
4421             \seq_if_in:cnTF { g__enumext_#3_seq } { \end{enumext*} }
4422             {
4423                 \msg_error:nnnn { enumext } { print-starred } {#3} { enumext* }
4424             }
4425         }
4426         \tl_use:N \__enumext_print_keyans_starred_tl
4427         \begin{enumext*}[#2]
4428             \keys_set:nn { enumext / level-1 }{ base-fix }
4429             \seq_map_inline:cn { g__enumext_#3_seq } { ##1 }
4430             \end{enumext*}
4431         }
4432     }

```

Otherwise it will open the environment `enumext` passing the optional argument to the “first level”, set the key `base-fix` and then map the $\langle sequence \rangle$.

```

4433     {
4434         \begin{enumext}[#2]
4435             \keys_set:nn { enumext / enumext* }{ base-fix }
4436             \seq_map_inline:cn { g__enumext_#3_seq } { ##1 }
4437             \end{enumext}
4438     }

```

```

4439         }
4440     }
4441     {
4442         \msg_error:nnn { enumext } { undefined-storage-anskey } {#3}
4443     }
4444 }

```

(End of definition for `__enumext_printkeyans:nnn`.)

11.46 The command `\setenumext`

The command `\setenumext` will be in charge of managing the $\langle keys \rangle$ passed to all environments and to the `\printkeyans` command. We must take precautions with the `enumext*` environment and “first level” of the `enumext` environment so as not to capture $\langle keys \rangle$ that complicate us.

The function `__enumext_filter_first_level:n` will be in charge of filtering the $\langle keys \rangle$ passed to the environment `enumext*` and “first level” of the environment `enumext`.

```

\__enumext_filter_first_level:n
\__enumext_filter_first_level_key:n
\__enumext_filter_first_level_pair:nn
4445 \cs_new:Npn \__enumext_filter_first_level:n #1
4446 {
4447     \use:e
4448     {
4449         \keyval_parse:NNn
4450         \__enumext_filter_first_level_key:n
4451         \__enumext_filter_first_level_pair:nn {#1}
4452     }
4453 }

```

The function `__enumext_filter_first_level_key:n` will be responsible for filtering the $\langle keys \rangle$ that are passed “without value” by excluding the keys `resume` and `resume*`.

```

4454 \cs_new:Npn \__enumext_filter_first_level_key:n #1
4455 {
4456     \str_case:nnF {#1}
4457     {
4458         { resume } {}
4459         { resume* } {}
4460     }
4461     { , { \exp_not:n {#1} } } }
4462 }

```

The function `__enumext_filter_first_level_pair:nn` will be responsible for filtering the $\langle keys \rangle$ that are passed “with value” by excluding the `series`, `resume` and `save-ans` keys.

```

4463 \cs_new:Npn \__enumext_filter_first_level_pair:nn #1#2
4464 {
4465     \str_case:nnF {#1}
4466     {
4467         { series } {}
4468         { resume } {}
4469         { save-ans } {}
4470     }
4471     { , { \exp_not:n {#1} } = { \exp_not:n {#2} } } }
4472 }

```

(End of definition for `__enumext_filter_first_level:n`, `__enumext_filter_first_level_key:n`, and `__enumext_filter_first_level_pair:nn`.)

Now define a “meta families” of $\langle keys \rangle$ to access from `\setenumext`.

```

4473 \keys_define:nn { enumext / meta-families }
4474 {
4475     enumext-1 .code:n =
4476     {
4477         \keys_set:ne { enumext / level-1 }
4478         {
4479             \__enumext_filter_first_level:n {#1}
4480         }
4481     } ,
4482     enumext-2 .code:n = { \keys_set:nn { enumext / level-2 } {#1} } ,
4483     enumext-3 .code:n = { \keys_set:nn { enumext / level-3 } {#1} } ,
4484     enumext-4 .code:n = { \keys_set:nn { enumext / level-4 } {#1} } ,
4485     keyans .code:n = { \keys_set:nn { enumext / keyans } {#1} } ,
4486     enumext* .code:n =
4487     {
4488         \keys_set:ne { enumext / enumext* }
4489         {

```

```

4490         \__enumext_filter_first_level:n {#1}
4491     }
4492 },
4493 keyans* .code:n = { \keys_set:nn { enumext / keyans* } {#1} } ,
4494 print* .code:n = { \keys_set:nn { enumext / print } { print* = {#1} } } ,
4495 print-1 .code:n = { \keys_set:nn { enumext / print } { print-1 = {#1} } } ,
4496 print-2 .code:n = { \keys_set:nn { enumext / print } { print-2 = {#1} } } ,
4497 print-3 .code:n = { \keys_set:nn { enumext / print } { print-3 = {#1} } } ,
4498 print-4 .code:n = { \keys_set:nn { enumext / print } { print-4 = {#1} } } ,
4499 print-* .code:n = { \keys_set:nn { enumext / print } { print-* = {#1} } } ,
4500 unknown .code:n = { \msg_error:nn { enumext } { unknown-key-family } } ,
4501 }

```

We store them in the constant sequence `\c__enumext_all_families_seq` separated by commas.

```

4502 \seq_const_from_clist:Nn \c__enumext_all_families_seq
4503 {
4504     enumext-1, enumext-2, enumext-3, enumext-4, keyans, enumext*,
4505     keyans*, print-1, print-2, print-3, print-4, print-*, print*,
4506 }

```

`\setenumext` Now we define the user command `\setenumext`.

```

4507 \NewDocumentCommand \setenumext { 0{enumext,1} +m }
4508 {
4509     \tl_if_novalue:nTF {#1}
4510     {
4511         \seq_map_inline:Nn \c__enumext_all_families_seq
4512     }
4513     {
4514         \seq_clear:N \l__enumext_setkey_tmpa_seq
4515         \seq_set_from_clist:Nn \l__enumext_setkey_tmpb_seq {#1}
4516         \int_set:Nn \l__enumext_setkey_tmpa_int
4517         {
4518             \seq_count:N \l__enumext_setkey_tmpb_seq
4519         }
4520         \int_compare:nNnTF { \l__enumext_setkey_tmpa_int } > { 1 }
4521         {
4522             \seq_pop_left:NN \l__enumext_setkey_tmpb_seq \l__enumext_setkey_tmpa_tl
4523             \seq_map_function:NN \l__enumext_setkey_tmpb_seq \l__enumext_set_parse:n
4524             \seq_set_map_e:NNn \l__enumext_setkey_tmpa_seq \l__enumext_setkey_tmpa_seq
4525             {
4526                 \tl_use:N \l__enumext_setkey_tmpa_tl - ##1
4527             }
4528         }
4529         {
4530             \seq_put_right:Ne \l__enumext_setkey_tmpa_seq { \tl_trim_spaces:n {#1} }
4531         }
4532         \seq_if_empty:NTF \l__enumext_setkey_tmpa_seq
4533         { \seq_map_inline:Nn \c__enumext_all_families_seq }
4534         { \seq_map_inline:Nn \l__enumext_setkey_tmpa_seq }
4535     }
4536     {
4537         \keys_set:nn { enumext / meta-families } { ##1 = {#2} }
4538     }
4539 }

```

(End of definition for `\setenumext`. This function is documented on page 6.)

`__enumext_set_parse:n`
`__enumext_set_error:n`

Internal functions used by the `\setenumext` command.

```

4540 \cs_new_protected:Npn \__enumext_set_parse:n #1
4541 {
4542     \tl_set:Ne \l__enumext_setkey_tmpb_tl { \tl_trim_spaces:n {#1} }
4543     \clist_map_inline:nn { 0, 1, 2, 3, 4, * } % <- max level
4544     { \tl_remove_all:Nn \l__enumext_setkey_tmpb_tl {##1} }
4545     \tl_if_empty:NTF \l__enumext_setkey_tmpb_tl
4546     {
4547         \seq_put_right:Ne \l__enumext_setkey_tmpa_seq
4548         { \tl_trim_spaces:n {#1} }
4549     }
4550     { \__enumext_set_error:nn {#1} { } }
4551 }
4552 \cs_new_protected:Npn \__enumext_set_error:nn #1 #2
4553 { \msg_error:nnn { enumext } { invalid-key } {#1} {#2} }

```


(End of definition for `__enumext_set_parse:n` and `__enumext_set_error:nn`)

11.47 Messages

Message used by package-load for `multicol` and `hyperref` packages.

```
4554 \msg_new:nnn { enumext } { package-load }
4555 {
4556   The ~ '#1' ~ package ~ is ~ already ~ loaded.
4557 }
4558 \msg_new:nnn { enumext } { package-not-load }
4559 {
4560   The ~ '#1' ~ package ~ will ~ be ~ loaded ~ as ~ a ~ dependency.
4561 }
4562 \msg_new:nnn { enumext } { package-load-foot }
4563 {
4564   The ~ '#1' ~ package ~ is ~ loaded ~ with ~ the ~ option ~ '#2'.
4565 }
```

Message used in the creation of counters by `enumext` package.

```
4566 \msg_new:nnn { enumext } { counters }
4567 {
4568   The ~ counter ~ '#1' ~ is ~ already ~ defined ~ by ~ some ~ \\
4569   package ~ or ~ macro, ~ it ~ cannot ~ be ~ continued.
4570 }
```

Message used by `align` and `mark-pos` keys.

```
4571 \msg_new:nnn { enumext } { unknown-choice }
4572 {
4573   The ~ value ~ '#3' ~ for ~ '#1' ~ key ~ is ~ invalid ~ use ~ ('#2').
4574 }
```

Message used by reserved `anskey*` environment by `enumext` package.

```
4575 \msg_new:nnnn { enumext } { anskey-env-error }
4576 {
4577   The ~ '#1' ~ environment ~is~ reserved ~ by ~\\
4578   'enumext' ~ package, ~ It~ is~ already~ defined.
4579 }
4580 {
4581   The ~ anskey* ~ environment ~ is ~ defined ~ internally ~
4582   for ~ the ~ 'save-ans' ~ key.\\
4583 }
```

Message used in the creation of `(prop list)` by `enumext` package.

```
4584 \msg_new:nnn { enumext } { store-prop }
4585 {
4586   * ~ Package ~ enumext: ~ Creating ~
4587   \c_backslash_str g__enumext_#1_prop ~ \msg_line_context:.
4588 }
4589 \msg_new:nnn { enumext } { store-seq }
4590 {
4591   * ~ Package ~ enumext: ~ Creating ~
4592   \c_backslash_str g__enumext_#1_seq ~ \msg_line_context:.
4593 }
4594 \msg_new:nnn { enumext } { store-int }
4595 {
4596   * ~ Package ~ enumext: ~ Creating ~
4597   \c_backslash_str g__enumext_resume_#1_int ~ \msg_line_context:.
4598 }
4599 \msg_new:nnn { enumext } { prop-seq-int-hook }
4600 {
4601   * ~ Package ~ enumext: ~ Elements ~ in ~
4602   \c_backslash_str g__enumext_#1_prop ~ = ~ #2.\\
4603   * ~ Package ~ enumext: ~ Elements ~ in ~
4604   \c_backslash_str g__enumext_#1_seq ~ = ~ #3.\\
4605   * ~ Package ~ enumext: ~ Value ~ off ~
4606   \c_backslash_str g__enumext_resume_#1_int ~ = ~ #4.
4607 }
4608 \msg_new:nnn { enumext } { item-answer-hook }
4609 {
4610   * ~ Package ~ enumext: ~ Value ~ off ~
4611   \c_backslash_str g__enumext_item_number_int ~ = ~ #1.\\
4612   * ~ Package ~ enumext: ~ Value ~ off ~
4613   \c_backslash_str g__enumext_item_anskey_int ~ = ~ #2.\\
```

```

4614     * ~ Package ~ enumext: ~ Difference ~ item_number_int ~ - ~ item_anskey_int ~ = ~ #3.
4615 }

```

Message used by [*key = val*] system and `\setenumext` command.

```

4616 \msg_new:nnn { enumext } { invalid-key }
4617 {
4618     The ~ key ~ '#1' ~ is ~ not ~ know ~ the ~ level ~ #2.
4619 }
4620 \msg_new:nnn { enumext } { unknown-key-family }
4621 {
4622     Unknown~key~family~`\l_keys_key_str'~for~enumext.
4623 }

```

Messages used in length calculation.

```

4624 \msg_new:nnn { enumext } { width-negative }
4625 {
4626     Ignoring ~ negative ~ value ~ '#1=#2' ~ \msg_line_context:.\
4627     The ~ key ~ '#1'~ accepts ~ values ~ >= ~ 0pt.
4628 }
4629 \msg_new:nnn { enumext } { width-zero }
4630 {
4631     Invalid ~ '#1=#2' ~ \msg_line_context:.\
4632     The ~ key ~ '#1'~ accepts ~ values ~ > ~ 0pt.
4633 }

```

Messages used by `show-length` key in `enumext`.

```

4634 \msg_new:nnn { enumext } { list-lengths }
4635 {
4636     **** ~ Lengths ~ used ~ by ~ 'enumext' ~ level ~ '#2' ~ \msg_line_context:~\c_space_tl ****\
4637     \__enumext_show_length:nnn { dim } { labelsep } {#1}
4638     \__enumext_show_length:nnn { dim } { labelwidth } {#1}
4639     \__enumext_show_length:nnn { dim } { itemindent } {#1}
4640     \__enumext_show_length:nnn { dim } { leftmargin } {#1}
4641     \__enumext_show_length:nnn { dim } { rightmargin } {#1}
4642     \__enumext_show_length:nnn { dim } { listparindent } {#1}
4643     \__enumext_show_length:nnn { skip } { topsep } {#1}
4644     \__enumext_show_length:nnn { skip } { parsep } {#1}
4645     \__enumext_show_length:nnn { skip } { partopsep } {#1}
4646     \__enumext_show_length:nnn { skip } { itemsep } {#1}
4647     *****
4648 }

```

Messages used by `show-length` key in `enumext*`, `keyans*` and `keyans`.

```

4649 \msg_new:nnn { enumext } { list-lengths-not-nested }
4650 {
4651     **** ~ Lengths ~ used ~ by ~ '#2' ~ environment ~ \msg_line_context:~\c_space_tl ****\
4652     \__enumext_show_length:nnn { dim } { labelsep } {#1}
4653     \__enumext_show_length:nnn { dim } { labelwidth } {#1}
4654     \__enumext_show_length:nnn { dim } { itemindent } {#1}
4655     \__enumext_show_length:nnn { dim } { leftmargin } {#1}
4656     \__enumext_show_length:nnn { dim } { rightmargin } {#1}
4657     \__enumext_show_length:nnn { dim } { listparindent } {#1}
4658     \__enumext_show_length:nnn { skip } { topsep } {#1}
4659     \__enumext_show_length:nnn { skip } { parsep } {#1}
4660     \__enumext_show_length:nnn { skip } { partopsep } {#1}
4661     \__enumext_show_length:nnn { skip } { itemsep } {#1}
4662     *****
4663 }

```

Messages used by `ref` key.

```

4664 \msg_new:nnn { enumext } { key-ref-empty }
4665 {
4666     Key ~ 'ref' ~ need ~ a ~ value ~ in ~ '#1'~ \msg_line_context:.
4667 }

```

Messages used by `save-ans` key.

```

4668 \msg_new:nnn { enumext } { save-ans-empty }
4669 {
4670     Key ~ 'save-ans' ~ need ~ a ~ value ~ in ~ '#1'~ \msg_line_context:.
4671 }
4672 \msg_new:nnn { enumext } { save-ans-log }
4673 {
4674     * ~ Package ~ enumext: ~ Start ~ #1\c_space_tl with ~ save-ans=#2 ~ \msg_line_context:.
4675 }

```

```

4676 \msg_new:nnn { enumext } { save-ans-log-hook }
4677 {
4678   * ~ Package ~ enumext: ~ Stop ~ #1\c_space_tl with ~ save-ans=#2 ~ \msg_line_context:.
4679 }
4680 \msg_new:nnn { enumext } { save-ans-hook }
4681 {
4682   Stop ~ storing ~ for ~ 'save-ans=#1' ~ \msg_line_context:.
4683 }

```

Messages used by the internal system to check answer used by `check-ans` key.

```

4684 \msg_new:nnn { enumext } { need-save-ans }
4685 {
4686   Key ~ '#1'~ works ~ only ~ with ~ the ~ 'save-ans' ~ key ~ in ~ '#2'~ \msg_line_context:.
4687 }
4688 \msg_new:nnn { enumext } { items-same-answer }
4689 {
4690   *****\\
4691   * ~ Package ~ enumext: ~ Checking ~ answers ~ in ~ '#1' ~
4692   for ~ \c_left_brace_str #2 \c_right_brace_str\\
4693   * ~ started ~ #3 ~ and ~ close ~ \msg_line_context: : ~
4694   'OK', ~ all ~ items ~ with ~ answer.\\
4695   *****
4696 }
4697 \msg_new:nnn { enumext } { item-greater-answer }
4698 {
4699   Checking ~ answers ~ in ~ '#1' ~ for ~ \c_left_brace_str #2 \c_right_brace_str\\
4700   started ~ #3 ~ and ~ close ~ \msg_line_context: : ~'NOT ~ OK'\\
4701   Items ~ > ~ Answers.
4702 }
4703 \msg_new:nnn { enumext } { item-less-answer }
4704 {
4705   Checking ~ answers ~ in ~ '#1' ~ for ~ \c_left_brace_str #2 \c_right_brace_str\\
4706   started ~ #3 ~ and ~ close ~ \msg_line_context: : ~'NOT ~ OK'\\
4707   Items ~ < ~ Answers.
4708 }

```

Messages used by the internal system to check for “starred” `\item*` and `\anspic*` commands.

```

4709 \msg_new:nnn { enumext } { missing-starred }
4710 {
4711   Missing ~ '\c_backslash_str #1*' ~ #2.
4712 }
4713 \msg_new:nnn { enumext } { many-starred }
4714 {
4715   Many ~ '\c_backslash_str #1*' ~ #2.
4716 }

```

Messages used by `\printkeyans*` command.

```

4717 \msg_new:nnn { enumext } { print-starred }
4718 {
4719   \c_backslash_str printkeyans*:~ The ~ sequence ~ '#1' ~ already ~ contains ~
4720   #2 ~ environment ~ \msg_line_context:.
4721 }

```

Message for the nesting depth of the environment `enumext`.

```

4722 \msg_new:nnn { enumext } { list-too-deep }
4723 {
4724   Too ~ deep ~ nesting ~ for ~ 'enumext' ~ \msg_line_context:~ \\
4725   The ~ maximum ~ level ~ of ~ nesting ~ is ~ 4.
4726 }

```

Messages used by `\anskey`, `anskey*` and `\anspic` commands.

```

4727 \msg_new:nnn { enumext } { anskey-unnumber-item }
4728 {
4729   Can't ~ store ~ with ~ a ~ unnumbered ~ \c_backslash_str item ~ \msg_line_context:.
4730 }
4731 \msg_new:nnn { enumext } { anskey-already-stored }
4732 {
4733   Content ~ already ~ stored ~ for ~ this ~ \c_backslash_str item ~ \msg_line_context:.
4734 }
4735 \msg_new:nnn { enumext } { anskey-empty-arg }
4736 {
4737   Can't ~ store ~ empty ~ content ~ ~ \msg_line_context:.
4738 }

```

```

4739 \msg_new:nnn { enumext } { anskey-wrong-place }
4740 {
4741   Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
4742   '\c_backslash_str #1' ~ works ~ in ~ the ~ environment ~ '#2'.
4743 }
4744 \msg_new:nnn { enumext } { anskey-nested }
4745 {
4746   The ~ command ~ \c_backslash_str anskey~ can't ~ be ~ nested ~ \msg_line_context:.
4747 }
4748 \msg_new:nnn { enumext } { anskey-math-mode }
4749 {
4750   #1 ~ can't ~ work ~ in ~ math ~ mode ~ \msg_line_context:.
4751 }
4752 \msg_new:nnn { enumext } { anskey-env-wrong }
4753 {
4754   The ~ environment ~ anskey* ~ cannot ~ use ~ in ~ '#1' ~ \msg_line_context:.
4755 }
4756 \msg_new:nnn { enumext } { anspic-wrong-place }
4757 {
4758   Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
4759   '\c_backslash_str #1' ~ works ~ in ~ the ~ environment ~ '#2'.
4760 }
4761 \msg_new:nnn { enumext } { command-wrong-place }
4762 {
4763   Wrong ~ place ~ for ~ command ~ '\c_backslash_str #1' ~ \msg_line_context:~ \\
4764   '\c_backslash_str #1' ~ works ~ outside ~ the ~ environment ~ '#2'.
4765 }
4766 \msg_new:nnnn { enumext } { anskey-env-key-unknown }
4767 {
4768   The ~ key ~ '#1' ~ is ~ unknown ~ by ~ environment~
4769   'anskey*' ~ and ~ is ~ being ~ ignored.
4770 }
4771 {
4772   The ~ environment ~ 'anskey*' ~ does ~ not ~ have ~ a ~ key ~ called ~'#1'.\\
4773   Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
4774 }
4775 \msg_new:nnnn { enumext } { anskey-env-key-value-unknown }
4776 {
4777   The ~ key ~ '#1=#2' ~ is ~ unknown ~ by ~ environment ~
4778   'anskey*' ~ and ~ is ~ being ~ ignored.
4779 }
4780 {
4781   The ~ environment ~ 'anskey*' ~ does ~ not ~ have ~ a ~ key ~ called ~'#1'.\\
4782   Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
4783 }
4784 \msg_new:nnnn { enumext } { anskey-cmd-key-unknown }
4785 { The~key~'#1'~is~unknown~by~'\c_backslash_str anskey'~and~is~being~ignored.}
4786 {
4787   The~command~'\c_backslash_str anskey'~does~not~have~a~key~called~'#1'.\\
4788   Check~that~you~have~spelled~the~key~name~correctly.
4789 }
4790 \msg_new:nnnn { enumext } { anskey-cmd-key-value-unknown }
4791 { The ~ key ~ '#1=#2' ~ is ~ unknown ~ by ~ '\c_backslash_str anskey' ~ and ~ is ~ being ~ ignored.}
4792 {
4793   The ~ command ~ '\c_backslash_str anskey' ~ does ~ not ~ have ~ a ~ key ~ called ~'#1'.\\
4794   Check ~ that ~ you ~ have ~ spelled ~ the ~ key ~ name ~ correctly.
4795 }

```

Messages used by [keyans](#) and [keyanspic](#) environment.

```

4796 \msg_new:nnn { enumext } { keyans-nested }
4797 {
4798   The ~ environment ~ 'keyans' ~ can't ~ be ~ nested ~ \msg_line_context:.
4799 }
4800 \msg_new:nnn { enumext } { keyans-wrong-level }
4801 {
4802   Wrong ~ level ~ position ~ for ~ 'keyans' ~ \msg_line_context:~ \\
4803   The ~ environment ~ 'keyans' ~ can ~ only ~ be ~ in ~ the ~ first ~ level.
4804 }
4805 \msg_new:nnn { enumext } { wrong-place }
4806 {
4807   Wrong ~ place ~ for ~ '#1' ~ environment ~\msg_line_context:~ \\
4808   '#1' ~ is ~ only ~ found ~ with ~ '#2' ~ in ~ 'enumext.

```

```

4809     }
4810     \msg_new:nnn { enumext } { keyanspic-nested }
4811     {
4812         The ~ environment ~ 'keyanspic' ~ can't ~ be ~ nested~ \msg_line_context:~.
4813     }
4814     \msg_new:nnn { enumext } { keyanspic-wrong-level }
4815     {
4816         Wrong ~ level ~ position ~ for ~ 'keyanspic' ~ \msg_line_context:~ \\
4817         The ~ environment ~ 'keyans' ~ can ~ only ~ be ~ in ~ the ~ first ~ level.
4818     }

```

Messages used by `\getkeyans` command.

```

4819     \msg_new:nnn { enumext } { undefined-storage-anskey }
4820     {
4821         Storage ~ named ~ '#1' ~ is ~ not ~ defined ~ \msg_line_context:.
4822     }

```

Messages used by `\miniright` command.

```

4823     \msg_new:nnn { enumext } { missing-miniright }
4824     {
4825         Missing ~ '\c_backslash_str miniright' ~ in ~ \msg_line_context:~ \\
4826         The ~ key ~ 'mini-env' ~ need ~ '\c_backslash_str miniright'.
4827     }
4828     \msg_new:nnn { enumext } { wrong-miniright-place }
4829     {
4830         Wrong ~ place ~ for ~ '\c_backslash_str miniright' ~ \msg_line_context:~ \\
4831         Works ~ in ~ 'enumext' ~ and ~ 'keyans' ~ with ~ key ~ 'mini-env'.
4832     }
4833     \msg_new:nnn { enumext } { wrong-miniright-use }
4834     {
4835         Wrong ~ use ~ for ~ '\c_backslash_str miniright' ~ \msg_line_context:~ \\
4836         '\c_backslash_str miniright' ~ need ~ a ~ key ~ 'mini-env'.
4837     }

```

Messages used by `enumext*` and `keyans*` environments.

```

4838     \msg_new:nnn { enumext } { nested }
4839     {
4840         The ~ starred ~ environment ~ can't ~ be ~ nested ~ \msg_line_context:.
4841     }
4842     \msg_new:nnn { enumext } { item-joined }
4843     {
4844         Items ~ joined ~ (#1) ~ > ~ #2 ~ columns ~ \msg_line_context:.
4845     }
4846     \msg_new:nnn { enumext } { item-joined-columns }
4847     {
4848         Not ~ space ~ to ~ join ~ items ~ (#1) ~ > ~ #2 ~ \msg_line_context:.
4849     }

```

11.48 Finish package

Finish package implementation.

```

4850 \file_input_stop:
4851 </package>

```

12 Index of Implementation

The *italic* numbers denote the pages where the corresponding entry is described, the numbers underlined and all others indicate the line on which they are implemented in the package code.

Symbols

*

211

\+

203

\-

203

\\

219, 2611, 3522, 4568, 4577, 4582, 4602, 4604, 4611, 4613, 4626, 4631, 4636, 4651, 4690, 4692, 4694, 4699, 4700, 4705, 4706, 4724, 4741, 4758, 4763, 4772, 4781, 4787, 4793, 4802, 4807, 4816, 4825, 4830, 4835

A

above

1424

above*

1424

\addvspace

1078, 1106, 1222, 1301, 1364, 1370, 1398, 1415, 3361, 3376, 3478, 3493, 3787, 3801, 3842, 3856

after

917

align

492

\Alph

36, 41

\Alpha

444, 559, 604, 672, 4395

\alph

36, 41

\alpha

445, 557, 4387

\anskey

12, 73, 75, 2429

anskey*

13, 2539

\anspic

15, 98, 99, 3500

\anspic*

67

\arabic

30, 36

\arabic

443, 556, 603, 4379, 4383, 4399

B

base-fix

796

\baselineskip

49

\baselineskip

813, 824

before

917

before*

917

below

1424

below*

1424

bool commands:

\bool_gset_false:N

319, 320, 321, 2715, 2717, 3803, 3807, 3858

\bool_gset_true:N

231, 240, 1020, 1922, 1928, 3779, 3804, 3834, 3859

\bool_if:NTF

384, 396, 413, 1446, 1460, 1473, 1484, 1495, 1506, 1517, 1528, 1582, 1599, 1604, 1612, 1639, 1677, 1682, 1689, 1693, 1715, 1720, 1728, 1735, 1766, 1774, 1867, 2062, 2072, 2151, 2175, 2182, 2206, 2306, 2328, 2368, 2379, 2383, 2433, 2452, 2476, 2530, 2541, 2630, 2667, 2731, 2764, 2779, 2854, 2865, 2869, 2982, 3013, 3088, 3104, 3166, 3176, 3206, 3211, 3295, 3345, 3359, 3367, 3406, 3463, 3476, 3484, 3502, 3775, 3784, 3788, 3830, 3839, 3843, 3927, 3937, 4020, 4025, 4034, 4038, 4053, 4082, 4235, 4239, 4263, 4272, 4276, 4282, 4296, 4319

\bool_if:nTF

1399, 1416, 3025, 3060, 3124, 3523, 4419

\bool_if_p:N

249, 264, 809, 810, 820, 821, 1746, 1747, 1755, 1756, 1880, 1906, 1919, 1920, 1925, 1926, 2239, 2248, 2249, 2261, 2277, 2313, 2354, 2355, 2653, 2841, 2842, 2879, 2880, 3268, 3270, 3281, 3530, 3531

\bool_lazy_all:nTF

247, 262, 1878, 1904, 2237, 2246, 2259, 2275, 3266, 3279

\bool_lazy_and:nnTF

227, 236, 808, 819, 1745, 1754, 1918, 1924, 2312, 2319, 2353, 2494, 2506, 2652, 2658, 2840

\bool_lazy_or:nnTF

1807, 1814, 2878, 3529

\bool_new:N

34, 35, 36, 37, 38, 39, 40, 41, 63, 72, 93, 98, 99, 104, 105, 108, 129, 130, 138, 139, 144, 146, 147, 161, 172, 174

\bool_not_p:n

228, 237, 2264, 2279, 2314, 2320, 2654, 2659, 3269, 3282

\bool_set_eq:NN

2991, 3040, 3970, 4189

\bool_set_false:N

393, 830, 1852, 1853, 1885, 1890, 1894, 1898, 1911, 2594, 3382, 3414, 3496, 3561, 3579, 3922, 3967, 4139, 4186

\bool_set_true:N

254, 255, 269, 270, 375, 379, 485, 845, 1430, 1435, 1702, 1824, 1825, 2094, 2102, 2595, 2985, 2987, 3016, 3018, 3036, 3048, 3243, 3275, 3288, 3314, 3411, 3438, 3764, 3819, 3895, 3976, 3983, 3984, 4028, 4195, 4202, 4203

box commands:

\box_dp:N

1118, 1122, 1126, 1137, 1141, 1152, 1161, 1167, 1177, 1190, 1196, 1202, 1233, 1234, 1235, 1238, 1248, 1252, 1261, 1268, 1273, 1281, 1310, 1311, 1314, 1321, 1334, 1342, 1348, 1356, 3591

\box_new:N

69, 167, 173

\box_set_wd:Nn

4074, 4311

\box_use_drop:N

3799, 3854, 4081, 4318

\box_wd:N

451

C

\c

211, 212, 709, 711, 723, 725

\catcode

2611

\cB

212

\cE

212

\centering

1401, 1418, 3612, 3792, 3847

check-ans

1844

Document class:

article

42

clist commands:

\clist_const:Nn

179

\clist_map_function:nN

3599

\clist_map_inline:Nn

491, 751, 850, 916, 931, 1012, 1440

\clist_map_inline:nn

48, 59, 77, 83, 95, 107, 132, 155, 178, 519, 539, 805, 855, 1026, 1546, 1791, 1858, 2041, 2059, 2091, 2234, 2773, 2940, 3153, 3156, 3183, 3193, 3196, 3216, 4543

\columnbreak

74

\columnbreak

2316

columns

996

columns-sep

996

\columnsep

94, 97

\columnsep

3339, 3460

\columnseprule

94, 97

\columnseprule

3343, 3462

Commands provide by enumext:

\anskey

28, 63, 64, 69, 70, 72, 73, 75, 76, 82, 84, 93, 107, 116, 117, 122

\anspic*

28, 67, 70, 82, 83, 99–101, 116, 117

\anspic

70, 98–101, 122

\getkeyans

70, 116, 124

©2024 by Pablo González L

125 / 138

`\item*` 28, 67, 70, 82, 83, 87, 88, 108, 113, 116, 117
`\item` 86, 88, 102, 107–109, 112, 113
`\miniright` 27, 47, 54, 55, 94, 95, 97, 98, 124
`\printkeyans*` 116
`\printkeyans` 28, 70, 116, 117
`\setenumext` 28, 117–119, 121
 Counters defined by `enumext`:
`enumXiii` 26, 35
`enumXii` 26, 35
`enumXiv` 26, 35
`enumXi` 26, 35
`enumXviii` 26, 35
`enumXvii` 26, 35, 109
`enumXvi` 26, 35
`enumXv` 26, 35
 cs commands:
`\cs_generate_variant:Nn` 453, 469, 715, 731, 2143,
 2148, 2224, 2547, 3143, 3601, 4373
`\cs_if_exist:NTF` 423
`\cs_if_free:NTF` 2498, 2510
`\cs_new:Nn` 197
`\cs_new:Npn` . 215, 1547, 1556, 1566, 2106, 2115, 2123,
 4445, 4454, 4463
`\cs_new_eq:NN` 346, 347, 348, 352, 353, 398, 399, 402,
 403
`\cs_new_protected:Nn` . 207, 221, 245, 278, 305, 311,
 317, 323, 329, 337, 355, 370, 580, 643, 695, 806, 932,
 936, 940, 944, 948, 952, 956, 960, 964, 968, 972, 976,
 980, 984, 988, 992, 1027, 1039, 1063, 1080, 1091, 1108,
 1183, 1207, 1224, 1286, 1303, 1325, 1360, 1366, 1441,
 1455, 1469, 1480, 1491, 1502, 1513, 1524, 1610, 1713,
 1726, 1743, 1764, 1792, 1797, 1822, 1863, 1873, 1916,
 1931, 1938, 1947, 1952, 1957, 1962, 1971, 1976, 1981,
 2149, 2173, 2180, 2204, 2211, 2225, 2450, 2469, 2485,
 2548, 2584, 2615, 2650, 2692, 2713, 2721, 2762, 2777,
 2805, 2838, 2874, 2886, 2894, 2945, 2949, 2968, 3021,
 3056, 3072, 3082, 3098, 3236, 3264, 3293, 3300, 3323,
 3353, 3365, 3404, 3428, 3446, 3471, 3482, 3519, 3563,
 3577, 3597, 3602, 3618, 3637, 3754, 3773, 3809, 3828,
 3886, 3909, 3916, 3925, 3935, 3952, 4093, 4130, 4152,
 4158, 4171, 4227, 4331
`\cs_new_protected:Npn` 185, 189, 193, 406, 421, 438,
 448, 454, 560, 605, 677, 702, 716, 1388, 1407, 1578,
 1597, 1667, 1700, 1802, 1986, 2060, 2070, 2092, 2100,
 2135, 2144, 2302, 2365, 2377, 2415, 2419, 2539, 2570,
 2574, 2605, 2741, 2815, 2859, 2978, 2997, 3032, 3044,
 3112, 3146, 3186, 3246, 3424, 3572, 3656, 3705, 3898,
 3958, 3965, 3981, 3989, 3994, 4006, 4145, 4177, 4184,
 4200, 4208, 4222, 4352, 4365, 4412, 4540, 4552
`\cs_new_protected_nopar:Nn` . . . 3945, 4069, 4164,
 4306
`\cs_new_protected_nopar:Npn` 4012, 4255
`\cs_set:Nn` 2370
`\cs_set:Npn` 2235, 2273, 4358
`\cs_set_eq:NN` . . 3876, 3877, 4014, 4120, 4121, 4257
`\cs_set_protected:Nn` 856, 872, 884, 896
`\cs_set_protected:Npn` . 44, 53, 70, 78, 90, 96, 125,
 151, 159, 470, 492, 524, 540, 587, 732, 752, 796, 832,
 851, 908, 917, 996, 1013, 1424, 1535, 1783, 1844, 2003,
 2042, 2078, 2227, 2766, 2929, 3144, 3184
`\cs_to_str:N` 440, 463
`\cs_undefine:N` 2487, 2488, 2489, 2490

D

`\d` 203
`\DeclareDocumentEnvironment` 359

dim commands:

`\dim_abs:n` 3117, 3122
`\dim_add:Nn` 3582
`\dim_compare:nNnTF` . 858, 874, 886, 898, 1390, 1409,
 3114, 3119, 3125, 3131, 3133, 3135, 3305, 3328, 3432,
 3450, 3574, 3620, 3639, 3756, 3811
`\dim_compare:nTF` 2338, 2680
`\dim_gset_eq:NN` 3765, 3820
`\dim_gzero:N` 2719, 3806, 3861
`\dim_new:N` 66, 73, 74, 75, 92, 134, 168, 169, 175
`\dim_set:Nn` . . 451, 846, 3011, 3117, 3122, 3124, 3127,
 3128, 3132, 3134, 3137, 3138, 3140, 3308, 3331, 3434,
 3452, 3604, 3622, 3629, 3641, 3648, 3691, 3740, 3758,
 3813, 4008
`\dim_set_eq:NN` 547, 594, 665, 669, 3006, 3155, 3195,
 3339, 3460, 3698, 3701, 3702, 3747, 3750, 3751, 3999
`\dim_use:N` 859, 867, 1391, 1397, 2214, 2217, 2222, 3077,
 3079, 3306, 3311, 3312, 3319, 3329, 3333, 3334, 3336
`\dim_zero:N` 3343, 3462, 3583, 3584, 3585
`\dim_zero_new:N` 184, 3635, 3654
`\c_zero_dim` 861, 875, 887, 899, 1391, 1409, 2340, 2682,
 3114, 3119, 3125, 3132, 3306, 3329, 3432, 3450, 3620,
 3639, 3756, 3811

E

`\end` . . 1394, 1412, 2177, 2208, 3358, 3375, 3475, 3492, 3777,
 3800, 3832, 3855, 4421, 4430, 4437
`\endgroup` 2611
`\endlist` 347
`\endlrbox` 4072, 4309
`\endminipage` 353
`enumext` 5, [3217](#)
 enumext internal commands:

`\l__enumext__check_start_line_env_tl` . . . 32
`\l__enumext__ref_the_count_tl` 38
`\l__enumext__resume_name_tl` 59
`__enumext_add_pre_parsep:` . 48, 1037, [1039](#), 1039
`__enumext_after_args_exec:` . 45, [932](#), [944](#), [3229](#)
`__enumext_after_args_exec_v:` . 46, 47, [948](#), 960,
 3397
`__enumext_after_args_exec_vii:` . . . [964](#), 988
`__enumext_after_args_exec_viii:` 992
`__enumext_after_env:nn` . 79, 80, 82, 96, [104](#), [111](#),
[189](#), 189, 2625, 3385, 3782, 3837, 4107
`__enumext_after_hyperref:` . . . 34, 368, [370](#), 370
`__enumext_after_list:` . 95, [107](#), [112](#), 3234, [3365](#),
 3365
`\l__enumext_after_list_args_v_tl` 962
`\l__enumext_after_list_args_vii_tl` 990, 4063
`\l__enumext_after_list_args_viii_tl` 994, 4292
`__enumext_after_list_v:` . . 98, 3402, [3482](#), 3482
`__enumext_after_list_vii:` . . . 3884, 3916, 3916
`__enumext_after_list_viii:` . . 4128, [4158](#), 4158
`__enumext_after_stop_list:` . . . 45, 46, [932](#), 940,
 3380
`__enumext_after_stop_list_v:` 46, [948](#), 956, 3497
`\l__enumext_after_stop_list_v_tl` 958
`__enumext_after_stop_list_vii:` [964](#), 980, 3919
`\l__enumext_after_stop_list_vii_tl` . . . 982
`__enumext_after_stop_list_viii:` . 984, 4161
`\l__enumext_after_stop_list_viii_tl` . . . 986
`\l__enumext_align_label_vii_str` . . 4055, 4059
`\l__enumext_align_label_viii_str` . 4284, 4288
`\l__enumext_align_label_X_str` [159](#)


```

\c__enumext_all_envs_clist .. 179, 491, 751, 850,
    916, 931, 1012, 1440
\c__enumext_all_families_seq .. 119, 4502, 4511,
    4533
\l__enumext_anskey_env_bool 31, 78, 34, 255, 270,
    2541
\__enumext_anskey_env_clean_vars: . 81, 2646,
    2650, 2713
\__enumext_anskey_env_define_keys: 78, 2539,
    2548, 2619
\__enumext_anskey_env_exec: 79, 2544, 2615, 2615
\__enumext_anskey_env_make:n 63, 78, 1827, 2539,
    2539, 2547
\__enumext_anskey_env_reset_keys: 79, 80, 2584,
    2647
\__enumext_anskey_env_reset_keys:\__-
    enumext_rescan_anskey_env:n ..... 2539
\__enumext_anskey_env_save_keys: .. 80, 2627,
    2650, 2650
\__enumext_anskey_env_store: .. 81, 2643, 2650,
    2692
\__enumext_anskey_env_unknown:n 79, 2567, 2570
\__enumext_anskey_env_unknown:nn . 2572, 2574
\l__enumext_anskey_level_int .. 28, 2471, 2472
\__enumext_anskey_safe_inner: . 77, 2444, 2450,
    2469
\__enumext_anskey_safe_inner:n ..... 76
\__enumext_anskey_safe_outer: . 76, 2431, 2450,
    2450
\__enumext_anskey_show_wrap_arg:n . 75, 2365,
    2365, 2381, 2396
\__enumext_anskey_show_wrap_left:n 75, 2310,
    2377, 2377
\__enumext_anskey_unknown:n 76, 2399, 2413, 2415
\__enumext_anskey_unknown:nn . 2399, 2417, 2419
\__enumext_anskey_wrapper:n ..... 2007, 2375
\__enumext_at_begin_document:n .. 33, 185, 185,
    344, 350
\l__enumext_base_line_fix_bool . 800, 810, 821,
    830
\__enumext_before_args_exec: 45, 932, 932, 3303
\__enumext_before_args_exec_v: .. 46, 948, 948,
    3431
\__enumext_before_args_exec_vii: .. 964, 964,
    3913
\__enumext_before_args_exec_viii: 968, 4155
\__enumext_before_env:nn 78, 189, 193, 2492, 2504,
    2516, 2617
\__enumext_before_keys_exec: 45, 932, 936, 3227
\__enumext_before_keys_exec_v: .. 46, 948, 952,
    3395
\__enumext_before_keys_exec_vii ..... 964
\__enumext_before_keys_exec_vii: 46, 972, 3873
\__enumext_before_keys_exec_viii: .. 46, 976,
    4117
\__enumext_before_list: ... 94, 3221, 3300, 3300
\__enumext_before_list_v: . 97, 3390, 3428, 3428
\__enumext_before_list_vii: ... 106, 3868, 3909,
    3909
\__enumext_before_list_viii: .. 111, 4113, 4152,
    4152
\l__enumext_before_no_starred_key_v_tl 954
\l__enumext_before_no_starred_key_vii_-
    tl ..... 974
\l__enumext_before_no_starred_key_viii_-
    tl ..... 978
\l__enumext_before_starred_key_v_tl ... 950
\l__enumext_before_starred_key_vii_tl . 966
\l__enumext_before_starred_key_viii_tl 970
\__enumext_calc_hspace:NNNNNNN 90, 3112, 3112,
    3143, 3148, 3188
\__enumext_check_ans_active: 65, 94, 1863, 1863,
    3304, 3912
\g__enumext_check_ans_item_tl ..... 84
\g__enumext_check_ans_key_bool 66, 67, 138, 319,
    1922, 1928, 2731
\l__enumext_check_ans_key_bool 66, 86, 87, 1848,
    1853, 1919, 1925
\__enumext_check_ans_key_hook: 66, 1916, 1916,
    3379, 3920
\__enumext_check_ans_level: 65, 1863, 1869, 1873
\__enumext_check_ans_log: 66, 67, 81, 1962, 1962,
    2735
\__enumext_check_ans_log_msg_greater: 1962,
    1968, 1981
\__enumext_check_ans_log_msg_less: 1962, 1966,
    1971
\__enumext_check_ans_log_msg_same_ok: 1962,
    1967, 1976
\__enumext_check_ans_msg_greater: 1938, 1944,
    1957
\__enumext_check_ans_msg_less: 1938, 1942, 1947
\__enumext_check_ans_msg_same_ok: 1938, 1943,
    1952
\__enumext_check_ans_show: .. 66, 81, 1938, 1938,
    2733
\g__enumext_check_ans_show_bool ..... 95
\l__enumext_check_answers_bool 63, 65, 76, 138,
    1825, 1852, 1867, 2151, 2175, 2182, 2206, 2433, 2630,
    2854, 2982, 3013, 4025
\__enumext_check_starred_cmd:n 32, 67, 84, 1986,
    1986, 3400, 3558, 4126
\g__enumext_check_starred_cmd_int 138, 1989,
    1995, 2000, 3054, 3528, 4234
\l__enumext_check_start_line_env_tl 138, 284,
    291, 298, 1992, 1998, 2001
\l__enumext_columns_sep_v_dim 3450, 3452, 3460
\l__enumext_columns_sep_vii_dim .. 3620, 3622,
    3631, 3695, 4091
\l__enumext_columns_sep_viii_dim . 3639, 3641,
    3650, 3744, 4329
\l__enumext_columns_v_int 1229, 3448, 3456, 3468,
    3473
\l__enumext_columns_vii_int .. 3625, 3628, 3632,
    3659, 3663, 3666, 3672, 3678, 3682, 4086, 4097
\l__enumext_columns_viii_int . 3644, 3647, 3651,
    3708, 3712, 3715, 3721, 3727, 3731, 4324, 4337
\l__enumext_counter_i_tl ..... 44, 430
\l__enumext_counter_ii_tl ..... 44, 431
\l__enumext_counter_iii_tl ..... 44, 432
\l__enumext_counter_iv_tl ..... 44, 433
\c__enumext_counter_style_tl ..... 30, 49, 209
\g__enumext_counter_styles_tl . 27, 36, 66, 441,
    459
\l__enumext_counter_v_tl ..... 44, 434, 685
\l__enumext_counter_vi_tl ..... 44, 435
\l__enumext_counter_vii_tl ..... 44, 436, 615
\l__enumext_counter_viii_tl ..... 44, 437, 632
\l__enumext_current_widest_dim 27, 66, 465, 548,

```

595, 666, 670
 __enumext_default_item:n ... 2978, 2978, 3029
 __enumext_define_counters:Nn 26, 421, 421, 430,
 431, 432, 433, 434, 435, 436, 437
 __enumext_endminipage: . 33, 350, 353, 365, 3614,
 4071, 4308
 \g__enumext_envir_name_tl 31, 34, 256, 271, 327,
 1795, 1800, 1810, 1950, 1955, 1960, 1974, 1979, 1984
 __enumext_execute_after_env: 32, 33, 63, 66, 67,
 77, 81, 2721, 2721, 3385, 4107
 __enumext_fake_item: 856, 856, 3175
 \l__enumext_fake_item_indent_v_dim 875, 880
 \l__enumext_fake_item_indent_v_tl 877, 3037,
 3041, 3049
 \l__enumext_fake_item_indent_vii_dim 887, 892
 \l__enumext_fake_item_indent_vii_tl 889, 4067
 \l__enumext_fake_item_indent_viii_dim . 899,
 904, 4300
 \l__enumext_fake_item_indent_viii_tl . . 901,
 4298, 4303
 \l__enumext_fake_item_indent_X_tl 96
 __enumext_fake_item_vii: 856, 884, 3205
 __enumext_fake_item_viii: 856, 896, 3210
 __enumext_filter_first_level:n . . 118, 4445,
 4445, 4479, 4490
 __enumext_filter_first_level_key:n 118, 4445,
 4450, 4454
 __enumext_filter_first_level_pair:nn . 118,
 4445, 4451, 4463
 __enumext_filter_save_key:n . . 70, 2067, 2075,
 2098, 2104, 2106, 2106, 4377, 4381, 4385, 4389, 4393,
 4397
 __enumext_filter_save_key_key:n . . 70, 2106,
 2111, 2115
 __enumext_filter_save_key_pair:nn 70, 2106,
 2112, 2123
 __enumext_filter_series:n 58, 1547, 1547, 1590,
 1602, 1607
 __enumext_filter_series_key:n 58, 1547, 1552,
 1556
 __enumext_filter_series_pair:nn . . 58, 1547,
 1553, 1566
 \g__enumext_footnote_arg_seq . 156, 2951, 2964,
 2974
 \g__enumext_footnote_int . 156, 2958, 2961, 2963,
 2965
 \g__enumext_footnote_int_seq . 156, 2952, 2965,
 2970, 2973
 __enumext_footnotes_key_bool 34
 \l__enumext_footnotes_key_bool 29, 34, 109, 146,
 379, 384, 393, 4034, 4082, 4272, 4319
 __enumext_footnotetext:nn . . 2945, 2945, 2975
 __enumext_getkeyans:nn . . 116, 4361, 4365, 4365
 __enumext_getkeyans_aux:n 116, 4349, 4352, 4352
 \l__enumext_hyperref_bool 29, 34, 146, 375, 396,
 413, 2355, 2842, 4020, 4263
 __enumext_hypertarget:nn 34, 370, 398, 402, 418
 __enumext_if_is_int:n 201
 __enumext_if_is_int:nTF 201, 704, 718
 __enumext_internal_mini_page: . . 34, 355, 355,
 3238, 3888
 __enumext_is_not_nested: . 26, 31, 92, 221, 221,
 3239, 3889
 __enumext_is_on_first_level: . 26, 31, 92, 221,
 245, 3244, 3896
 \g__enumext_item_anskey_int 76, 84, 138, 314, 341,
 342, 1935, 2304, 2856
 __enumext_item_answer_diff: . . 66, 67, 81, 1931,
 1931, 2728
 \g__enumext_item_answer_diff_int . 66, 67, 138,
 315, 1933, 1940, 1964
 \l__enumext_item_column_pos_vii_int 107, 3666,
 3672, 3678, 3682, 3689, 3948, 4086, 4089
 \l__enumext_item_column_pos_viii_int . . 112,
 3715, 3721, 3727, 3731, 3738, 4167, 4324, 4327
 \l__enumext_item_column_pos_X_int 159
 \g__enumext_item_count_all_vii_int 107, 3690,
 3949, 4097, 4104
 \g__enumext_item_count_all_viii_int 112, 3739,
 4168, 4336, 4344
 \g__enumext_item_count_all_X_int 159
 \g__enumext_item_number_bool 138
 \l__enumext_item_number_bool 65, 144, 1885, 1890,
 1894, 1898, 1911, 2476, 2530, 2985, 3016, 4028
 \g__enumext_item_number_int . . 65, 138, 313, 340,
 342, 1884, 1889, 1893, 1897, 1910, 1935, 2984, 3015,
 4027
 __enumext_item_peek_args_vii: 107, 108, 3950,
 3952, 3952
 __enumext_item_peek_args_viii: . . 112, 4169,
 4171, 4171
 __enumext_item_starred: . . 89, 3072, 3072, 3090
 \l__enumext_item_starred_vii_bool 3967, 3983,
 4038
 \l__enumext_item_starred_viii_bool 4186, 4202,
 4276, 4296
 \l__enumext_item_starred_X_bool 159
 __enumext_item_std:w . . 33, 86–88, 101, 344, 348,
 2988, 2994, 3019, 3037, 3041, 3049, 3595
 \g__enumext_item_symbol_aux_vii_tl 3991, 4040,
 4043, 4047, 4049
 \g__enumext_item_symbol_aux_X_tl 159
 \l__enumext_item_symbol_sep_vii_dim . . 4000,
 4008, 4046, 4048
 \g__enumext_item_symbol_tl . . . 87, 60, 122, 3003,
 3078, 3095
 \l__enumext_item_symbol_vii_tl 4043
 \l__enumext_item_text_vii_box 4033, 4074, 4081
 \l__enumext_item_text_viii_box 4271, 4311, 4318
 \l__enumext_item_text_X_box 159
 \l__enumext_item_width_vii_dim . . 3629, 3693,
 3701, 3702
 \l__enumext_item_width_viii_dim . . 3648, 3742,
 3750, 3751
 \l__enumext_item_width_X_dim 159
 \l__enumext_itemindent_X_dim 70
 \l__enumext_itemsep_vii_skip 4103
 \l__enumext_itemsep_viii_skip 4343
 \l__enumext_joined_item_aux_vii_int . . 3687,
 3688, 3689, 3690, 3696
 \l__enumext_joined_item_aux_viii_int . 3736,
 3737, 3738, 3739, 3745
 \l__enumext_joined_item_aux_X_int 159
 __enumext_joined_item_vii:w . . 108, 3955, 3956,
 3958, 3958
 \l__enumext_joined_item_vii_int . . 3658, 3659,
 3662, 3664, 3670, 3675, 3680, 3685, 3687, 3693
 __enumext_joined_item_viii:w . 112, 4174, 4175,

[4177](#), [4177](#)
`\l__enumext_joined_item_viii_int` . [3707](#), [3708](#),
[3711](#), [3713](#), [3719](#), [3724](#), [3729](#), [3734](#), [3736](#), [3742](#)
`\l__enumext_joined_item_X_int` [159](#)
`\l__enumext_joined_width_vii_dim` . [3691](#), [3698](#),
[3701](#), [4064](#), [4076](#)
`\l__enumext_joined_width_viii_dim` [3740](#), [3747](#),
[3750](#), [4293](#), [4313](#)
`\l__enumext_joined_width_X_dim` [159](#)
`__enumext_keyans_addto_prop:n` [82](#), [2741](#), [2741](#),
[3051](#), [3525](#)
`__enumext_keyans_addto_seq:n` . [83](#), [2815](#), [2815](#),
[3053](#), [3527](#)
`__enumext_keyans_addto_seq_link:` [2815](#), [2836](#),
[2838](#), [4233](#)
`__enumext_keyans_anspic_code:nnn` . [99](#), [3516](#),
[3519](#), [3519](#)
`__enumext_keyans_default_item:n` . . [88](#), [3032](#),
[3032](#), [3068](#)
`\l__enumext_keyans_env_bool` [34](#), [3269](#), [3282](#), [3411](#),
[3496](#)
`__enumext_keyans_fake_item:` . . [856](#), [872](#), [3165](#)
`\l__enumext_keyans_level_h_int` . . [28](#), [625](#), [652](#),
[2460](#), [2522](#), [2793](#), [4132](#), [4133](#)
`\l__enumext_keyans_level_int` . . [28](#), [1382](#), [2456](#),
[2518](#), [2788](#), [3410](#), [3415](#), [3510](#)
`__enumext_keyans_make_label:` [37](#), [89](#), [3098](#), [3098](#),
[3163](#)
`__enumext_keyans_mini_addvspace:` [53](#), [97](#), [1286](#),
[1286](#), [3440](#)
`__enumext_keyans_mini_right_cmd:n` [55](#), [1384](#),
[1407](#), [1407](#)
`__enumext_keyans_mini_set_vskip:` . [52](#), [1224](#),
[1224](#), [1288](#)
`__enumext_keyans_multi_addvspace:` [98](#), [1080](#),
[1091](#), [3465](#)
`__enumext_keyans_multi_set_vskip:` [49](#), [1080](#),
[1080](#), [1093](#)
`__enumext_keyans_multicols_start:` [97](#), [3444](#),
[3446](#), [3446](#)
`__enumext_keyans_multicols_stop:` . [98](#), [1411](#),
[3471](#), [3471](#), [3495](#)
`__enumext_keyans_parse_keys:n` [3389](#), [3424](#), [3424](#)
`\l__enumext_keyans_pic_above_int` . [133](#), [3605](#),
[3606](#), [3608](#)
`\l__enumext_keyans_pic_above_skip` . [101](#), [133](#),
[3549](#), [3589](#)
`__enumext_keyans_pic_arg_two:` [100](#), [3547](#), [3577](#),
[3577](#)
`\l__enumext_keyans_pic_below_int` . [133](#), [3605](#),
[3606](#), [3609](#)
`\l__enumext_keyans_pic_body_seq` . [99](#)–[101](#), [133](#),
[3514](#), [3554](#), [3613](#)
`__enumext_keyans_pic_do:n` [101](#), [3554](#), [3556](#), [3597](#),
[3597](#), [3601](#)
`\l__enumext_keyans_pic_level_int` . . [28](#), [1374](#),
[2464](#), [2526](#), [2744](#), [2783](#), [2818](#), [2896](#), [3565](#), [3566](#)
`__enumext_keyans_pic_row:n` . . [101](#), [3599](#), [3602](#),
[3602](#)
`__enumext_keyans_pic_safe_exec:` . [100](#), [3543](#),
[3563](#), [3563](#)
`__enumext_keyans_pic_skip_abs:N` . [100](#), [3572](#),
[3572](#), [3588](#)
`\l__enumext_keyans_pic_width_dim` . [133](#), [3604](#),
[3611](#)
`__enumext_keyans_redefine_item:` . . [88](#), [3056](#),
[3056](#), [3162](#)
`__enumext_keyans_ref:` [40](#), [677](#), [695](#), [3164](#)
`__enumext_keyans_ref:n` [40](#), [674](#), [677](#), [677](#)
`__enumext_keyans_safe_exec:` . [3388](#), [3404](#), [3404](#)
`__enumext_keyans_show_ans:` . . [2859](#), [2867](#), [2886](#)
`__enumext_keyans_show_item_opt:` . [2859](#), [2874](#),
[3049](#), [3539](#), [4299](#)
`__enumext_keyans_show_left:n` . [88](#), [2859](#), [2859](#),
[3047](#), [3534](#)
`__enumext_keyans_show_pos:` . . [2859](#), [2871](#), [2894](#)
`__enumext_keyans_starred_item:n` . . [88](#), [3044](#),
[3044](#), [3064](#)
`__enumext_keyans_start_line:` . [26](#), [32](#), [278](#), [278](#),
[3412](#), [3570](#), [4137](#)
`__enumext_keyans_store_ref:` . . [82](#), [2762](#), [2762](#),
[3052](#), [3526](#), [4231](#)
`__enumext_keyans_store_ref_aux_i:` [83](#), [2762](#),
[2774](#), [2777](#)
`__enumext_keyans_store_ref_aux_ii:` [83](#), [2762](#),
[2803](#), [2805](#)
`__enumext_keyans_wrapper_opt:n` . . [2010](#), [2882](#)
`\l__enumext_label_copy_i_tl` . . [2269](#), [2781](#), [2786](#),
[2791](#), [2796](#)
`\l__enumext_label_copy_v_tl` [2791](#)
`\l__enumext_label_copy_vi_tl` [2786](#)
`\l__enumext_label_copy_vii_tl` [2244](#), [2255](#), [2286](#),
[2781](#)
`\l__enumext_label_copy_viii_tl` [2796](#)
`\l__enumext_label_copy_X_tl` [148](#)
`\l__enumext_label_fill_left_v_tl` [3102](#)
`\l__enumext_label_fill_left_X_tl` [96](#)
`\l__enumext_label_fill_right_v_tl` [3109](#)
`\l__enumext_label_fill_right_X_tl` [96](#)
`\l__enumext_label_font_style_v_tl` [3103](#), [3538](#)
`\l__enumext_label_font_style_vii_tl` . . [4052](#)
`\l__enumext_label_font_style_viii_tl` . . [4281](#)
`\l__enumext_label_i_tl` [540](#)
`\l__enumext_label_ii_tl` [540](#)
`\l__enumext_label_iii_tl` [540](#)
`\l__enumext_label_iv_tl` [540](#)
`__enumext_label_style:Nnn` [26](#), [36](#), [454](#), [454](#), [469](#),
[545](#), [592](#), [663](#), [667](#)
`\l__enumext_label_v_tl` . . [82](#), [83](#), [660](#), [2749](#), [2823](#),
[2888](#), [2923](#), [3046](#), [3050](#), [3392](#), [3533](#), [3535](#)
`\l__enumext_label_vi_tl` . [82](#), [83](#), [660](#), [2746](#), [2820](#),
[3533](#), [3535](#), [3539](#)
`\l__enumext_label_vii_tl` . [587](#), [3978](#), [4003](#), [4010](#)
`\l__enumext_label_viii_tl` [587](#), [4197](#), [4225](#), [4229](#)
`\l__enumext_label_width_by_box` . . [66](#), [450](#), [451](#)
`__enumext_label_width_by_box:Nn` [36](#), [448](#), [448](#),
[453](#), [465](#), [728](#)
`\l__enumext_labelsep_i_dim` . . [2891](#), [2926](#), [4237](#),
[4252](#)
`\l__enumext_labelsep_v_dim` [3455](#)
`\l__enumext_labelsep_vii_dim` . [3624](#), [3633](#), [3694](#),
[4001](#), [4062](#), [4078](#)
`\l__enumext_labelsep_viii_dim` [3643](#), [3652](#), [3743](#),
[4291](#), [4300](#), [4315](#)
`\l__enumext_labelwidth_i_dim` . [2891](#), [2926](#), [4237](#),
[4252](#)
`\l__enumext_labelwidth_v_dim` [3455](#)
`\l__enumext_labelwidth_vii_dim` . . [3624](#), [3632](#),

```

3694, 4055, 4059, 4077
\l__enumext_labelwidth_viii_dim .. 3643, 3651,
3743, 4284, 4288, 4314
\l__enumext_leftmargin_tmp_v_bool . 100, 3579
\l__enumext_leftmargin_tmp_X_bool ..... 70
\l__enumext_leftmargin_tmp_X_dim ..... 70
\l__enumext_leftmargin_X_dim ..... 70
\__enumext_level: 197, 197, 569, 572, 573, 582, 584,
859, 863, 867, 934, 938, 942, 946, 1029, 1031, 1033,
1035, 1068, 1070, 1072, 1074, 1078, 1111, 1114, 1133,
1142, 1148, 1153, 1157, 1168, 1172, 1173, 1178, 1214,
1218, 1391, 1397, 1444, 1446, 1448, 1451, 1458, 1460,
1462, 1465, 2062, 2064, 2066, 2094, 2095, 2097, 2153,
2161, 2165, 2169, 2370, 2373, 2374, 2987, 2988, 2992,
2993, 2994, 3001, 3003, 3007, 3008, 3011, 3018, 3019,
3074, 3077, 3079, 3086, 3087, 3088, 3091, 3094, 3224,
3226, 3275, 3288, 3295, 3306, 3308, 3311, 3312, 3314,
3319, 3326, 3329, 3331, 3333, 3334, 3335, 3336, 3339,
3345, 3350, 3356, 3359, 3361, 3367
\l__enumext_level_h_int 28, 229, 251, 265, 608, 645,
1881, 1901, 2263, 2280, 2496, 2508, 3283, 3890, 3891
\l__enumext_level_int . 92, 28, 199, 238, 250, 266,
357, 1041, 1185, 1378, 1875, 1907, 2240, 2250, 2256,
2262, 2270, 2278, 2285, 2495, 2507, 2723, 3178, 3240,
3241, 3251, 3259, 3273, 3286, 3341, 3419, 3506, 3929,
3939, 4140
\__enumext_list_arg_two_i: ..... 3144
\__enumext_list_arg_two_ii: ..... 3144
\__enumext_list_arg_two_iii: ..... 3144
\__enumext_list_arg_two_iv: ..... 3144
\__enumext_list_arg_two_v: . 88, 3144, 3394, 3580
\__enumext_list_arg_two_vii: ..... 3184, 3872
\__enumext_list_arg_two_viii: .... 3184, 4116
\l__enumext_listoffset_v_dim ..... 3457
\l__enumext_listparindent_vii_dim .... 4065
\l__enumext_listparindent_viii_dim ... 4294
\__enumext_log_answer_vars: . 33, 329, 337, 2730
\__enumext_log_global_vars: . 33, 329, 329, 2729
\__enumext_make_label: 37, 86, 87, 89, 3082, 3082,
3173
\l__enumext_mark_answer_sym_tl 72, 2016, 2219,
2385, 2898, 2911, 4241
\l__enumext_mark_position_str 122, 2020, 2021,
2047, 2048, 2217
\l__enumext_mark_ref_sym_tl .. 2033, 2360, 2850
\__enumext_mini_addvspace: .. 51, 94, 1207, 1207,
3316
\__enumext_mini_addvspace_vii: 54, 1360, 1360,
3768
\__enumext_mini_addvspace_viii: 54, 1360, 1366,
3823
__enumext_mini_env* ..... 355
\__enumext_mini_right_cmd:n 55, 1386, 1388, 1388
\__enumext_mini_set_vskip: . 50, 1108, 1108, 1209
\__enumext_mini_set_vskip_vii: 53, 1303, 1303,
1362
\__enumext_mini_set_vskip_viii: 53, 1303, 1325,
1368
\__enumext_minipage:w 33, 350, 352, 361, 3611, 4064,
4293
\l__enumext_minipage_active_v_bool .. 97, 98,
3438, 3463, 3476, 3484
\g__enumext_minipage_active_vii_bool .. 104,
3779, 3784, 3803
\l__enumext_minipage_active_vii_bool . 3764,
3775
\g__enumext_minipage_active_viii_bool 3834,
3839, 3858
\l__enumext_minipage_active_viii_bool 3819,
3830
\g__enumext_minipage_active_X_bool ... 159
\l__enumext_minipage_active_X_bool .... 84
\g__enumext_minipage_after_skip 84, 1307, 1319,
3801, 3856
\l__enumext_minipage_after_skip 50, 51, 95, 98,
84, 1124, 1139, 1159, 1175, 1190, 1196, 1202, 1216,
1226, 1235, 1238, 1250, 1268, 1279, 1295, 1327, 1340,
1354, 3376, 3493
\g__enumext_minipage_center_vii_bool . 3788,
3804
\g__enumext_minipage_center_viii_bool 3843,
3859
\g__enumext_minipage_center_X_bool ... 159
\l__enumext_minipage_hsep_v_dim ... 97, 3436
\l__enumext_minipage_hsep_vii_dim .... 3762
\l__enumext_minipage_hsep_viii_dim ... 3817
\l__enumext_minipage_left_skip 50, 97, 84, 1116,
1131, 1150, 1165, 1212, 1222, 1227, 1233, 1242, 1259,
1271, 1291, 1301, 1305, 1310, 1314, 1328, 1332, 1346,
1364, 1370
\l__enumext_minipage_left_v_dim 97, 3434, 3442
\l__enumext_minipage_left_vii_dim 3758, 3770
\l__enumext_minipage_left_viii_dim 3813, 3825
\l__enumext_minipage_left_X_dim ..... 84
\g__enumext_minipage_right_skip 84, 1306, 1311,
1315, 3787, 3842
\l__enumext_minipage_right_skip . 50, 84, 1120,
1135, 1155, 1170, 1228, 1234, 1246, 1264, 1275, 1329,
1336, 1350, 1398, 1415
\l__enumext_minipage_right_v_dim .. 97, 1409,
1414, 3432, 3436
\g__enumext_minipage_right_vii_dim 104, 3766,
3786, 3806
\l__enumext_minipage_right_vii_dim 104, 3756,
3761, 3767
\g__enumext_minipage_right_viii_dim .. 3821,
3841, 3861
\l__enumext_minipage_right_viii_dim .. 3811,
3816, 3822
\g__enumext_minipage_right_X_dim ..... 159
\g__enumext_minipage_right_X_skip .... 159
\g__enumext_minipage_stat_int . 94, 97, 84, 1403,
1420, 3315, 3369, 3374, 3439, 3486, 3491
\l__enumext_miniright_code_vii_box 3795, 3799
\g__enumext_miniright_code_vii_tl 104, 3790,
3797, 3805
\l__enumext_miniright_code_viii_box .. 3850,
3854
\g__enumext_miniright_code_viii_tl 3845, 3852,
3860
\l__enumext_miniright_code_X_box ..... 159
\__enumext_multi_addvspace: . 48, 95, 1063, 1063,
3347
\__enumext_multi_set_vskip: 48, 1027, 1027, 1065
\l__enumext_multicols_above_ii_skip ... 1046
\l__enumext_multicols_above_iii_skip .. 1052
\l__enumext_multicols_above_iv_skip ... 1058
\l__enumext_multicols_above_v_skip 1082, 1096,
1106

```

```

\l__enumext_multicols_above_X_skip .... 78
\l__enumext_multicols_below_v_skip 1086, 1100,
    3478
\l__enumext_multicols_below_X_skip .... 78
\__enumext_multicols_start: 94, 3321, 3323, 3323
\__enumext_multicols_stop: 95, 1393, 3353, 3353,
    3378
\__enumext_nested_base_line_fix: 43, 796, 806,
    3255, 3906
\__enumext_newlabel:nn 29, 35, 73, 406, 406, 2296,
    2809
\l__enumext_newlabel_arg_one_tl 29, 35, 73, 83,
    148, 2289, 2297, 2359, 2798, 2810, 2848
\l__enumext_newlabel_arg_two_tl 29, 35, 72, 148,
    2243, 2253, 2267, 2283, 2298, 2785, 2790, 2795, 2811
\__enumext_parse_keys:n 43, 59, 3220, 3246, 3246
\__enumext_parse_keys_vii:n . 43, 59, 3866, 3898,
    3898
\__enumext_parse_keys_viii:n . 4111, 4145, 4145
\__enumext_parse_save_key:n 69, 2087, 2092, 2092
\__enumext_parse_save_key_vii:n 69, 2082, 2092,
    2100
\__enumext_parse_serie:n ..... 106
\__enumext_parse_series:n .. 59, 93, 1578, 1578,
    3254, 3904
\__enumext_parse_store_keys:n ..... 93
\l__enumext_parsep_i_skip 1044, 1046, 1188, 1236
\l__enumext_parsep_ii_skip ... 1050, 1052, 1194
\l__enumext_parsep_iii_skip .. 1056, 1058, 1200
\l__enumext_parsep_vii_skip ..... 4066
\l__enumext_parsep_viii_skip ..... 4295
\l__enumext_partopsep_v_skip . 1098, 1102, 1262,
    1266, 1273, 1277, 1293, 1297
\l__enumext_partopsep_viii_skip ..... 1338
\__enumext_phantomsection: 34, 370, 399, 403, 419
\__enumext_print_footnote: ... 2945, 2968, 4084,
    4321
\__enumext_print_keyans_box:NN 72, 2211, 2211,
    2224, 2372, 2890, 2925, 4237, 4252
\l__enumext_print_keyans_i_tl .... 4382, 4404
\l__enumext_print_keyans_ii_tl ... 4386, 4405
\l__enumext_print_keyans_iii_tl .. 4390, 4406
\l__enumext_print_keyans_iv_tl ... 4394, 4407
\l__enumext_print_keyans_starred_tl 116, 117,
    122, 4378, 4426
\l__enumext_print_keyans_vii_tl 116, 4398, 4408
\l__enumext_print_keyans_X_tl ..... 122
\__enumext_printkeyans:nnn 117, 4409, 4412, 4412
\__enumext_redefine_item: . 87, 3021, 3021, 3172
\l__enumext_ref_key_arg_tl 38, 49, 212, 562, 563,
    576, 607, 610, 621, 627, 638, 679, 680, 691
\l__enumext_ref_the_count_tl . 38, 49, 569, 572,
    575, 615, 617, 620, 632, 634, 637, 685, 687, 690
\__enumext_regex_counter_style: .. 30, 38, 207,
    207, 570, 616, 633, 686
\__enumext_register_counter_style:Nn .. 438,
    438, 443, 444, 445, 446, 447
\__enumext_remove_extra_parsep_vii: .. 3881,
    4093, 4093
\__enumext_remove_extra_parsep_viii: . 4125,
    4331, 4331
\__enumext_renew_footnote: ... 2945, 2949, 4036,
    4274
\l__enumext_renew_the_count_v_tl 688, 697, 699
\l__enumext_renew_the_count_vii_tl 618, 647,
    649
\l__enumext_renew_the_count_viii_tl 635, 654,
    656
\l__enumext_renew_the_count_X_tl ..... 49
\__enumext_rescan_anskey_env:n .. 79, 81, 2605,
    2700, 2708
\__enumext_reset_global_bool: .. 305, 308, 317
\__enumext_reset_global_int: ... 305, 307, 311
\__enumext_reset_global_tl: .... 305, 309, 323
\__enumext_reset_global_vars: . 32, 81, 305, 305,
    2738
\l__enumext_resume_active_bool 59, 61, 60, 1582,
    1702
\__enumext_resume_counter: .. 60, 61, 1700, 1706,
    1713
\__enumext_resume_counter:n . 59, 61, 1671, 1676,
    1700, 1700, 1770, 1778
\__enumext_resume_counter_save_ans: .. 61, 62,
    1700, 1711, 1743
\__enumext_resume_counter_series: . 61, 1700,
    1709, 1726
\g__enumext_resume_int ... 60, 1623, 1717, 1718
\__enumext_resume_last:n .. 59, 1578, 1584, 1597
\l__enumext_resume_name_tl 60, 1619, 1627, 1630,
    1646, 1654, 1657, 1703, 1704, 1732, 1739
\__enumext_resume_save_counter: 59, 1610, 1610,
    3383, 3923
\__enumext_resume_series:n . 60, 1541, 1667, 1667
\__enumext_resume_starred: . 62, 1542, 1764, 1764
\g__enumext_resume_vii_int . 107, 60, 1650, 1722,
    1723
\__enumext_safe_exec: .. 34, 92, 3219, 3236, 3236
\__enumext_safe_exec_vii: . 34, 3865, 3886, 3886
\__enumext_safe_exec_viii: ... 4110, 4130, 4130
\l__enumext_series_name_tl ..... 61
\l__enumext_series_str . 59, 93, 1539, 1580, 1588,
    1589, 1591, 1593, 1614, 1617, 1621, 1641, 1644, 1648,
    3250, 3902
\__enumext_set_error:nn ..... 4540, 4550, 4552
\__enumext_set_parse:n ..... 4523, 4540, 4540
\l__enumext_setkey_tmpa_int ... 117, 4516, 4520
\l__enumext_setkey_tmpa_seq .. 117, 4514, 4524,
    4530, 4532, 4534, 4547
\l__enumext_setkey_tmpa_tl .... 117, 4522, 4526
\l__enumext_setkey_tmpb_seq .. 117, 4515, 4518,
    4522, 4523
\l__enumext_setkey_tmpb_tl 117, 4542, 4544, 4545
\l__enumext_show_answer_bool . 2027, 2051, 2379,
    2865, 2879, 3530, 4235
\__enumext_show_length:nnn .. 44, 215, 215, 4637,
    4638, 4639, 4640, 4641, 4642, 4643, 4644, 4645, 4646,
    4652, 4653, 4654, 4655, 4656, 4657, 4658, 4659, 4660,
    4661
\l__enumext_show_position_bool ... 2030, 2054,
    2383, 2869, 2880, 3531, 4239
\g__enumext_standar_bool 31, 92, 34, 228, 231, 249,
    320, 1612, 1677, 1689, 1715, 1728, 1766, 1906, 1920,
    3270
\l__enumext_standar_bool . 92, 96, 34, 2248, 2261,
    2277, 3243, 3382
\l__enumext_standar_first_bool 31, 92, 34, 254,
    809, 1599, 1746, 1808, 1815

```



```

\__enumext_standar_item_vii:w . 108, 3963, 3965,
    3965
\__enumext_standar_item_viii:w 112, 113, 4182,
    4184, 4184
\__enumext_standar_ref: . . . . 38, 560, 580, 3174
\__enumext_standar_ref:n . . . . 38, 552, 560, 560
\g__enumext_standar_series_tl . 60, 1601, 1602,
    1768, 1771
\g__enumext_starred_bool 31, 106, 107, 34, 237, 240,
    264, 321, 1639, 1682, 1693, 1720, 1735, 1774, 1880,
    1926, 2239, 2249, 2279, 2779, 3807
\l__enumext_starred_bool 106, 107, 34, 2264, 2314,
    2320, 2368, 2654, 2659, 3895, 3922
\__enumext_starred_columns_set_vii: . 3618,
    3618, 3867
\__enumext_starred_columns_set_viii: . 3618,
    3637, 4112
\l__enumext_starred_first_bool 31, 34, 269, 820,
    1604, 1755, 1808, 1815
\__enumext_starred_item:nn . . 2997, 2997, 3027
\__enumext_starred_item_exec: . 113, 4227, 4227,
    4278
\__enumext_starred_item_vii:w . 108, 3962, 3981,
    3981
\__enumext_starred_item_vii_aux_i:w . 3981,
    3986, 3989
\__enumext_starred_item_vii_aux_ii:w . 3981,
    3987, 3992, 3994
\__enumext_starred_item_vii_aux_iii:w 3981,
    3997, 4006
\__enumext_starred_item_viii:w 112, 113, 4181,
    4200, 4200
\__enumext_starred_item_viii_aux_i:w . 113,
    4200, 4205, 4208
\__enumext_starred_item_viii_aux_ii:w . 113,
    4200, 4206, 4220, 4222
\__enumext_starred_joined_item_vii:n 102, 108,
    3656, 3656, 3960
\__enumext_starred_joined_item_viii:n . 102,
    112, 3656, 3705, 4179
\__enumext_starred_ref: . . . . 39, 605, 643, 3202
\__enumext_starred_ref:n . . . . 39, 599, 605, 605
\g__enumext_starred_series_tl . 60, 1606, 1607,
    1776, 1779
\__enumext_start_from:NNn 41, 702, 702, 715, 737
\l__enumext_start_i_int . . . . 1718, 1730, 1749
\__enumext_start_item_tmp_vii: 106, 3877, 3945,
    3945
\__enumext_start_item_tmp_viii: . 111, 4121,
    4164, 4164
\__enumext_start_item_vii:w 108, 109, 3973, 3978,
    4003, 4010, 4012, 4012
\__enumext_start_item_viii:w . 113, 4192, 4197,
    4225, 4255, 4255
\g__enumext_start_line_tl 31, 34, 257, 272, 326,
    1950, 1955, 1960, 1974, 1979, 1984
\__enumext_start_list:nn . 33, 90, 100, 344, 346,
    3223, 3391, 3544, 3870, 4114
\__enumext_start_mini_vii: 106, 3754, 3754, 3914
\__enumext_start_mini_viii: . 111, 3809, 3809,
    4156
\__enumext_start_save_ans_msg: 63, 1792, 1792,
    1817
\__enumext_start_store_level: . 93, 3222, 3264,
    3264
\__enumext_start_store_level_vii: 107, 3869,
    3925, 3925
\l__enumext_start_vii_int . . 1723, 1737, 1758
\l__enumext_start_X_int . . . . . 96, 732
\__enumext_stop_item_tmp_vii: . 106, 107, 109,
    3876, 3880, 3947, 4014
\__enumext_stop_item_tmp_viii: 111, 112, 4120,
    4124, 4166, 4257
\__enumext_stop_item_vii: 109, 110, 4014, 4069,
    4069
\__enumext_stop_item_viii: 115, 4257, 4306, 4306
\__enumext_stop_list: . 33, 344, 347, 3232, 3401,
    3557, 3882, 4127
\__enumext_stop_mini_vii: 104, 107, 3754, 3773,
    3918
\__enumext_stop_mini_viii: 112, 3809, 3828, 4160
\__enumext_stop_save_ans_msg: . 63, 1792, 1797,
    2727
\__enumext_stop_store_level: . 93, 3233, 3264,
    3293
\__enumext_stop_store_level_vii: . 107, 3883,
    3925, 3935
\l__enumext_store_active_bool . 28, 63, 93, 106,
    108, 1747, 1756, 1824, 2452, 3268, 3281, 3406, 3414,
    3502, 3561, 3927, 3937, 4139
\__enumext_store_active_keys:n . 68, 69, 2060,
    2060, 3261
\__enumext_store_active_keys_vii:n 68, 69, 106,
    2060, 2070, 3905
\__enumext_store_addto_prop:n 70, 82, 2135, 2135,
    2143, 2305, 2760, 4230
\__enumext_store_addto_seq:n 70, 84, 2144, 2144,
    2148, 2155, 2169, 2177, 2186, 2200, 2208, 2363, 2853
\l__enumext_store_anskey_arg_tl . 28, 74, 108,
    2311, 2316, 2318, 2323, 2330, 2333, 2343, 2348, 2351,
    2357, 2363
\__enumext_store_anskey_code:n 73, 76, 81, 2302,
    2302, 2445, 2698, 2706
\l__enumext_store_anskey_env_tl . 28, 80, 108,
    2628, 2632, 2638, 2700, 2708
\l__enumext_store_anskey_opt_tl . 28, 80, 108,
    2629, 2656, 2662, 2669, 2675, 2685, 2695, 2704
\__enumext_store_anskey_safe_outer: . . . . 76
\g__enumext_store_columns_break_bool . 2552,
    2653, 2715
\l__enumext_store_columns_break_bool . 2313,
    2401
\l__enumext_store_current_label_tl 28, 82-84,
    113, 108, 2743, 2746, 2749, 2756, 2758, 2760, 2817,
    2820, 2823, 2829, 2834, 2844, 2853, 4210, 4215, 4216,
    4229, 4230, 4232
\l__enumext_store_current_label_tmp_tl . 28,
    108, 3046, 3050
\l__enumext_store_current_opt_arg_tl 28, 113,
    108, 2863, 2876, 2882, 4218
\__enumext_store_internal_ref: . 72, 73, 2225,
    2225, 2308
\g__enumext_store_item_join_int . 2555, 2660,
    2664, 2716
\l__enumext_store_item_join_int . 2321, 2325,
    2404
\g__enumext_store_item_star_bool . 2557, 2667,
    2717
\l__enumext_store_item_star_bool . 2328, 2406

```

`\g__enumext_store_item_symbol_sep_dim` 2562, 2682, 2687, 2719
`\l__enumext_store_item_symbol_sep_dim` 2340, 2345, 2411
`\g__enumext_store_item_symbol_tl` 2560, 2673, 2677, 2718
`\l__enumext_store_item_symbol_tl` 2331, 2335, 2409
`\l__enumext_store_keyans_item_opt_sep_tl` 2013, 2754, 2756, 2827, 2831, 4213, 4215
`__enumext_store_level_close:` 71, 2149, 2173, 3297
`__enumext_store_level_close_vii:` 71, 2180, 2204, 3941
`__enumext_store_level_open:` 71, 2149, 2149, 3276, 3289
`__enumext_store_level_open_vii:` 71, 2180, 2180, 3931
`\g__enumext_store_name_tl` 28, 63, 95, 108, 325, 332, 333, 334, 335, 1800, 1826, 1949, 1954, 1959, 1973, 1978, 1983, 2725
`\l__enumext_store_name_tl` 28, 63, 65, 108, 1633, 1636, 1660, 1663, 1751, 1760, 1795, 1804, 1805, 1826, 1827, 1828, 1830, 1831, 1833, 1835, 1836, 1838, 1840, 1841, 1865, 2137, 2139, 2146, 2291, 2292, 2391, 2634, 2800, 2801, 2904, 2917, 4247
`\l__enumext_store_ref_key_bool` 73, 2036, 2306, 2354, 2764, 2841
`\l__enumext_store_save_key_vii_bool` 2072, 2102
`\l__enumext_store_save_key_vii_tl` 2074, 2075, 2103, 2104, 2184, 2192, 2196, 2200
`\l__enumext_store_save_key_X_bool` 68, 122
`\l__enumext_store_save_key_X_tl` 68, 69, 122
`\l__enumext_store_upper_level_X_bool` 122
`__enumext_storing_exec:` 63, 78, 1802, 1818, 1822
`__enumext_storing_set:n` 63, 1787, 1802, 1802
`\l__enumext_the_counter_v_tl` 687
`\l__enumext_the_counter_vii_tl` 617
`\l__enumext_the_counter_viii_tl` 634
`\l__enumext_the_counter_X_tl` 49
`__enumext_tmp:n` 44, 48, 53, 59, 70, 77, 78, 83, 90, 95, 96, 107, 125, 132, 151, 155, 159, 178, 796, 805, 851, 855, 1535, 1546, 1783, 1791, 1844, 1862, 2003, 2041, 2042, 2059, 2078, 2091, 2227, 2234, 2235, 2256, 2270, 2273, 2285, 2766, 2773, 3144, 3183, 3184, 3216
`__enumext_tmp:nn` 470, 491, 492, 523, 524, 539, 732, 751, 832, 850, 908, 916, 917, 931, 996, 1012, 1013, 1026, 1424, 1440, 2929, 2944
`__enumext_tmp:nnn` 540, 556, 557, 558, 559, 587, 603, 604
`__enumext_tmp:nnnnn` 752, 777, 780, 783, 785, 787, 790, 793
`__enumext_tmp:w` 4358, 4361
`\l__enumext_tmpa_vii_int` 3628, 3631
`\l__enumext_tmpa_viii_int` 3647, 3650
`\l__enumext_tmpa_X_int` 159
`\l__enumext_topsep_v_skip` 1084, 1088, 1231, 1244, 1252, 1257, 1277, 1281, 3560, 3592
`\l__enumext_topsep_vii_skip` 1308, 1317, 1321
`\l__enumext_topsep_viii_skip` 1330, 1352, 1356
`__enumext_undefine_anskey_env:` 77, 81, 2485, 2485, 2736
`\l__enumext_vspace_a_star_v_bool` 1473
`\l__enumext_vspace_a_star_vii_bool` 1495
`\l__enumext_vspace_a_star_viii_bool` 1506
`\l__enumext_vspace_a_star_X_bool` 96
`__enumext_vspace_above:` 56, 1441, 1441, 3302
`__enumext_vspace_above_v:` 56, 1469, 1469, 3430
`\l__enumext_vspace_above_v_skip` 1471, 1475, 1477
`__enumext_vspace_above_vii:` 57, 1491, 1491, 3911
`\l__enumext_vspace_above_vii_skip` 1493, 1497, 1499
`__enumext_vspace_above_viii:` 57, 1491, 1502, 4154
`\l__enumext_vspace_above_viii_skip` 1504, 1508, 1510
`\l__enumext_vspace_b_star_v_bool` 1484
`\l__enumext_vspace_b_star_vii_bool` 1517
`\l__enumext_vspace_b_star_viii_bool` 1528
`\l__enumext_vspace_b_star_X_bool` 96
`__enumext_vspace_below:` 56, 1455, 1455, 3381
`__enumext_vspace_below_v:` 57, 1480, 1480, 3498
`\l__enumext_vspace_below_v_skip` 1482, 1486, 1488
`__enumext_vspace_below_vii:` 57, 1513, 1513, 3921
`\l__enumext_vspace_below_vii_skip` 1515, 1519, 1521
`__enumext_vspace_below_viii:` 57, 1513, 1524, 4162
`\l__enumext_vspace_below_viii_skip` 1526, 1530, 1532
`__enumext_widest_from:nnn` 41, 716, 716, 731, 743
`\g__enumext_widest_label_tl` 27, 36, 66, 458, 462, 466
`\l__enumext_wrap_label_opt_v_bool` 3040
`\l__enumext_wrap_label_opt_vii_bool` 108, 3972
`\l__enumext_wrap_label_opt_viii_bool` 113, 4191
`\l__enumext_wrap_label_opt_X_bool` 96
`\l__enumext_wrap_label_v_bool` 3036, 3040, 3048, 3104
`\l__enumext_wrap_label_vii_bool` 108, 3971, 3976, 3984, 4053
`\l__enumext_wrap_label_viii_bool` 113, 4190, 4195, 4203, 4282
`\l__enumext_wrap_label_X_bool` 96
`__enumext_wrapper_label_v:n` 3106, 3539
`__enumext_wrapper_label_vii:n` 4056
`__enumext_wrapper_label_viii:n` 4285
`\l__enumext_write_aux_file_tl` 29, 73, 83, 148, 2294, 2300, 2807, 2813
`__enumext_zero_parsep:` 51, 1128, 1183, 1183
enumext* 5, 3863
enumXi 430
enumXii 430
enumXiii 430
enumXiv 430
enumXv 430
enumXvi 430
enumXvii 430
enumXviii 430
Environments provide by enumext:
anskey* 28, 63, 72, 73, 75, 77, 78, 80, 81, 93, 117, 120, 122
enumext* 25, 26, 29-31, 34, 35, 39, 41-47, 53, 54, 57-60,

| | |
|---|--|
| 62–65, 67–77, 80, 82, 83, 85, 86, 91–93, 105–107, 109, 111, 112, 114, 116–118, 121, 124 | |
| enumext 25, 26, 30, 31, 34–45, 47–56, 58–60, 62–65, 67–77, 80, 82, 83, 85–87, 89, 90, 92, 93, 96, 100, 101, 104, 107, 116–118, 121, 122 | |
| keyans* 25, 26, 28–32, 35, 39–47, 53, 54, 57, 63, 64, 67, 68, 70, 78, 82, 86, 91, 111, 121, 124 | |
| keyanspic 25, 26, 28, 32, 35, 37, 40, 54, 63, 64, 67, 70, 78, 82–84, 98–101, 123 | |
| keyans 25, 26, 28, 31, 32, 35–37, 40–47, 49, 52–57, 63, 64, 67, 68, 70, 78, 82–84, 88–90, 96–100, 104, 112, 121, 123 | |
| Environments: | |
| list 30, 33, 90, 92 | |
| lrbox 101, 109, 110, 114, 115 | |
| minipage 30, 33, 34, 47, 49, 50, 98, 100, 101, 109, 110, 115 | |
| multicols 47–50, 55, 94, 95, 97, 98 | |
| scontents 78, 80 | |
| exp commands: | |
| \exp_after:wN 4361 | |
| \exp_args:Ne 2697, 2705, 3258, 4349 | |
| \exp_args:NV 2417, 2572 | |
| \exp_not:N 57, 461, 575, 620, 637, 690, 865, 879, 880, 891, 892, 903, 904, 2359, 2388, 2389, 2846, 2901, 2902, 2914, 2915, 4244, 4245, 4358 | |
| \exp_not:n 259, 274, 286, 293, 300, 514, 534, 575, 576, 620, 621, 637, 638, 690, 691, 866, 1564, 1576, 2024, 2121, 2133, 2297, 2325, 2335, 2345, 2359, 2360, 2664, 2677, 2687, 2810, 2848, 2850, 4461, 4471 | |
| F | |
| \fbox 2008 | |
| file commands: | |
| \file_input_stop: 4850 | |
| first 917 | |
| font 470 | |
| \footnote 86 | |
| \footnote 86, 2953 | |
| \footnotemark 2963 | |
| \footnotesize 2389, 2902, 2915, 4245 | |
| \footnotetext 2947 | |
| G | |
| \getkeyans 16, 116, 4347 | |
| group commands: | |
| \group_begin: 2387, 2432, 2607, 2694, 2900, 2913, 4032, 4051, 4243, 4270, 4280, 4369, 4403 | |
| \group_end: 2394, 2448, 2711, 2907, 2920, 4061, 4073, 4250, 4290, 4310, 4371, 4410 | |
| H | |
| \hbadness 4080, 4317 | |
| hbox commands: | |
| \hbox_set:Nn 450 | |
| \hfill 500, 504, 509, 510, 1395, 1413, 2359, 2846, 3778, 3833 | |
| hook commands: | |
| \hook_gput_code:nnn 9, 187, 191, 195, 368 | |
| \hook_gremove_code:nn 80, 2623 | |
| \hook_gset_rule:nnnn 369 | |
| \hook_if_empty:nTF 2621 | |
| \hspace 4091, 4329 | |
| \hyperlink 74, 84 | |
| \hyperlink 2359, 2846 | |
| \hypertarget 34 | |
| \hypertarget 398 | |
| I | |
| \IfHyperBoolean 376 | |

| | |
|--|--|
| \IfPackageLoadedTF 11, 19, 372, 386 | |
| \ignorespaces 868 | |
| \inputlineno 259, 274, 286, 293, 300 | |
| int commands: | |
| \int_add:Nn 3689, 3738 | |
| \int_case:nn 1041, 1185, 1875, 1901, 1940, 1964 | |
| \int_compare:nNnTF 357, 608, 625, 645, 652, 1110, 1229, 1374, 1378, 1382, 1988, 1994, 2456, 2460, 2464, 2472, 2518, 2522, 2526, 2723, 2744, 2783, 2788, 2793, 2818, 2896, 3241, 3251, 3273, 3286, 3325, 3341, 3355, 3369, 3415, 3419, 3448, 3473, 3486, 3506, 3510, 3566, 3659, 3669, 3685, 3708, 3718, 3734, 3891, 3929, 3939, 4086, 4095, 4133, 4140, 4323, 4333, 4520 | |
| \int_compare_p:nNn 229, 238, 250, 251, 265, 266, 1881, 1907, 2240, 2250, 2262, 2263, 2278, 2280, 2321, 2495, 2496, 2507, 2508, 2660, 3283 | |
| \int_decr:N 3688, 3737 | |
| \int_eval:n 342, 2139, 2292, 2389, 2801, 2902, 2915, 3159, 3201, 3677, 3726, 4245 | |
| \int_from_alph:n 710, 724 | |
| \int_from_roman:n 712, 726 | |
| \int_gadd:Nn 3690, 3739 | |
| \int_gdecr:N 1884, 1889, 1893, 1897, 1910 | |
| \int_gincr:N 1717, 1722, 2304, 2856, 2984, 3015, 3054, 3315, 3439, 3528, 3949, 4027, 4168, 4234 | |
| \int_gset:Nn 1933, 2961 | |
| \int_gset_eq:NN 1616, 1623, 1629, 1635, 1643, 1650, 1656, 1662, 2958 | |
| \int_gzero:N 313, 314, 315, 1403, 1420, 2000, 2716, 3374, 3491, 4104, 4344 | |
| \int_if_exist:NTF 1591, 1627, 1633, 1654, 1660, 1838 | |
| \int_incr:N 2471, 3240, 3410, 3565, 3890, 3948, 4132, 4167 | |
| \int_mod:nn 4097, 4335 | |
| \int_new:N 28, 29, 30, 31, 32, 33, 60, 61, 84, 100, 119, 135, 136, 141, 142, 143, 145, 156, 162, 163, 164, 165, 166, 1593, 1841 | |
| \int_set:Nn 706, 710, 712, 1730, 1737, 1749, 1758, 2608, 3605, 3606, 3628, 3647, 3658, 3664, 3680, 3707, 3713, 3729, 4080, 4317, 4516 | |
| \int_set_eq:NN 1718, 1723, 3687, 3736 | |
| \int_sign:n 1935 | |
| \int_step_function:nnN 2256, 2270, 2285 | |
| \int_step_inline:nnn 3607 | |
| \int_to_roman:n 199, 2236, 2274 | |
| \int_use:N 335, 340, 341, 1111, 1732, 1739, 1751, 1760, 3159, 3178, 3201, 3259, 3326, 3335, 3350, 3356, 3662, 3663, 3675, 3711, 3712, 3724 | |
| \int_zero:N 4089, 4327 | |
| \item 86, 88, 107, 109, 112, 114, 348, 2157, 2163, 2188, 2194, 2318, 2820, 2823, 3023, 3058, 3875, 3877, 4119, 4121, 4232 | |
| \item* 5, 14, 67, 3056 | |
| item-pos* 2929 | |
| item-sym* 2929 | |
| \itemindent 91 | |
| \itemindent 90 | |
| itemindent 832 | |
| \itemsep 100, 101 | |
| \itemsep 3581, 3587 | |
| \itemwidthdim 184, 3635, 3654, 3698, 3702, 3747, 3751 | |
| K | |
| keyans 14, 3386 | |
| keyans* 14, 4108 | |

| | |
|--|--|
| keyanspic | 15, 3541 |
| Keys for command provide by enumext : | |
| break-col | 74, 75, 78–80 |
| item-join | 74, 75, 78–80 |
| item-pos* | 74, 75, 78–80 |
| item-star | 74, 75, 78–80 |
| item-sym* | 74, 75, 78–80 |
| Keys for environments provide by enumext : | |
| above* | 27, 56 , 57 |
| above | 27, 56 , 57 , 94 , 97 , 106 , 111 |
| after | 45 , 46 , 96 , 98 , 107 , 112 |
| align | 27, 37 , 89 , 109 , 120 |
| base-fix | 42 , 58 , 70 , 117 |
| before* | 45 , 46 , 94 , 106 , 111 |
| before | 45 , 46 , 97 |
| below* | 27, 56 , 57 |
| below | 27, 56 , 57 , 96 , 98 , 107 , 112 |
| check-ans .. | 28 , 30 , 31 , 62–64 , 66 , 67 , 70 , 81 , 84 , 86 , 87 , 94–96 , 111 , 122 |
| columns-sep | 47 , 94 , 97 |
| columns | 27, 47 , 50 , 55 , 94 , 97 |
| first | 45–47 , 109 |
| font | 36 , 89 , 109 |
| item-pos* | 85 , 87 |
| item-sym* | 28 , 85 , 87 |
| itemindent | 27 , 43 , 44 , 88 , 109 |
| itemsep | 42 , 92 |
| labelsep | 36 , 87 , 90 , 109 |
| labelwidth | 36 , 38–41 , 90 |
| label | 26 , 27 , 36 , 38 , 41 , 101 |
| lisparindent | 92 |
| list-indent | 27, 43 , 100 |
| list-offset | 43 |
| listparindent | 43 , 109 |
| mark-ans | 67 , 70 , 75 |
| mark-pos | 67 , 68 , 120 |
| mark-ref | 67 , 70 , 72 , 74 |
| mini-env .. | 27 , 34 , 47 , 55 , 70 , 86 , 94 , 97 , 104–106 , 111 |
| mini-right* | 27, 30 , 47 , 70 , 104 , 105 |
| mini-right | 27, 30 , 47 , 54 , 70 , 104 , 105 |
| mini-sep | 27, 47 , 70 , 94 , 97 |
| no-store | 28 , 62–65 , 70 , 76 |
| noitemsep | 42 , 51 |
| nosep | 42 , 51 |
| parindent | 92 |
| parsep | 42 , 91 , 92 , 109 |
| partopsep | 42 |
| ref | 26 , 30 , 38–40 , 121 |
| resume* | 26 , 58 , 59 , 62 , 63 , 70 , 96 , 118 |
| resume | 26 , 33 , 58–63 , 70 , 96 , 107 , 118 |
| rightmargin | 43 |
| save-ans .. | 28 , 33 , 58–63 , 65 , 66 , 68–70 , 76–78 , 81–83 , 88 , 93 , 96 , 99 , 107 , 112 , 113 , 116 , 118 , 121 |
| save-key | 28 , 58 , 69 , 93 |
| save-pos | 70 |
| save-ref | 29 , 35 , 67 , 70 , 72–74 , 82 , 84 , 88 , 113 |
| save-sep | 67 , 70 , 113 |
| series | 26 , 58–62 , 70 , 93 , 96 , 118 |
| show-ans | 67 , 68 , 70 , 72 , 73 , 75 , 88 , 113 |
| show-length | 31 , 44 , 121 |
| show-pos | 28 , 67 , 68 , 72 , 73 , 75 , 84 , 88 , 113 |
| start | 27, 30 , 41 , 58 |
| store-key | 68 |
| topsep | 42 |
| widest | 27, 30 , 41 |

| | |
|--------------------------|---|
| wrap-ans | 30 , 67 , 70 , 72 , 75 |
| wrap-label* | 36 , 86 , 89 , 108 , 109 , 113 |
| wrap-label | 36 , 89 , 108 , 109 , 113 |
| wrap-opt | 67 , 70 |
| keys commands: | |
| \keys_define:nn | 472 , 494 , 526 , 542 , 589 , 660 , 734 , 754 , 798 , 834 , 853 , 910 , 919 , 998 , 1015 , 1426 , 1537 , 1785 , 1846 , 2005 , 2044 , 2080 , 2085 , 2399 , 2550 , 2586 , 2931 , 4374 , 4473 |
| \l_keys_key_str | 76 , 79 , 2417 , 2572 , 4622 |
| \keys_precompile:nnN .. | 117 , 4373 , 4376 , 4380 , 4384 , 4388 , 4392 , 4396 |
| \keys_set:nn .. | 486 , 814 , 825 , 1021 , 1431 , 1436 , 1679 , 1684 , 1771 , 1779 , 2437 , 3253 , 3258 , 3426 , 3903 , 4149 , 4428 , 4435 , 4477 , 4482 , 4483 , 4484 , 4485 , 4488 , 4493 , 4494 , 4495 , 4496 , 4497 , 4498 , 4499 , 4537 |
| \keys_set_known:nn | 2704 |
| keyval commands: | |
| \keyval_parse:NNn | 1551 , 2110 , 4449 |

L

| | |
|---|---|
| label | 540 , 587 , 660 |
| Labels provide by enumext : | |
| \Alph* | 36 |
| \Roman* | 36 |
| \alph* | 36 |
| \arabic* | 30 , 36 |
| \roman* | 36 |
| \labelsep | 101 |
| \labelsep | 3582 , 3585 |
| labelsep | 470 |
| \labelwidth | 36 , 101 |
| \labelwidth | 3582 , 3583 |
| labelwidth | 470 |
| \leftmargin | 91 |
| \leftmargin | 90 , 3582 |
| legacy commands: | |
| \legacy_if:nTF | 4015 , 4018 , 4258 , 4261 |
| \legacy_if_gset_false:n | 362 |
| \legacy_if_set_false:n | 4017 , 4260 |
| \legacy_if_set_true:n .. | 3977 , 4002 , 4009 , 4022 , 4196 , 4224 , 4265 |
| \linewidth | 94 , 97 |
| \linewidth | 3310 , 3436 , 3604 , 3631 , 3650 , 3760 , 3815 |
| \list | 346 |
| list-indent | 832 |
| list-offset | 832 |
| \listparindent | 3584 |
| listparindent | 832 |
| \lrbox | 4033 , 4271 |

M

| | |
|------------------------|---|
| \makebox | 101 |
| \makebox .. | 2215 , 2217 , 3078 , 4047 , 4055 , 4059 , 4284 , 4288 |
| \makelabel | 86 , 89 , 101 |
| \makelabel | 89 , 3084 , 3100 |
| \makesavenoteenv | 392 |
| mark-ans | 2003 |
| mark-pos | 2003 , 2042 |
| mark-ref | 2003 |
| mini-env | 996 |
| mini-sep | 996 |
| \minipage | 352 |
| \miniright | 10 , 54 , 1372 , 3372 , 3489 |

mode commands:

| | |
|------------------------------------|--|
| <code>\mode_if_math:TF</code> | 2480, 2534 |
| <code>\mode_if_vertical:TF</code> | 1066, 1094, 1210, 1289 |
| <code>\mode_leave_vertical:</code> | 812, 823, 865, 879, 891, 903, 2213, 3076, 4045 |

msg commands:

| | |
|---------------------------------|--|
| <code>\msg_error:nn</code> | 2441, 2474, 2478, 2532, 2640, 3417, 3421, 3508, 3568, 3893, 4135, 4142, 4500 |
| <code>\msg_error:nnn</code> | 565, 612, 629, 682, 1376, 1380, 1405, 1422, 1691, 1695, 1810, 2423, 2482, 2500, 2512, 2520, 2524, 2528, 2536, 2578, 4363, 4368, 4442, 4553 |
| <code>\msg_error:nnnn</code> | 2426, 2454, 2458, 2462, 2466, 2581, 3408, 3504, 3512, 4423 |
| <code>\msg_error:nnnnn</code> | 513, 533, 2023 |
| <code>\msg_fatal:nn</code> | 3242 |
| <code>\msg_fatal:nnn</code> | 424 |
| <code>\msg_info:nnn</code> | 13, 16, 21, 24, 374, 388 |
| <code>\msg_line_context:</code> | 4587, 4592, 4597, 4626, 4631, 4636, 4651, 4666, 4670, 4674, 4678, 4682, 4686, 4693, 4700, 4706, 4720, 4724, 4729, 4733, 4737, 4741, 4746, 4750, 4754, 4758, 4763, 4798, 4802, 4807, 4812, 4816, 4821, 4825, 4830, 4835, 4840, 4844, 4848 |
| <code>\msg_log:nnn</code> | 1830, 1835, 1840 |
| <code>\msg_log:nnnnn</code> | 339, 1973, 1978, 1983 |
| <code>\msg_log:nnnnnn</code> | 331 |
| <code>\msg_new:nnn</code> | 4554, 4558, 4562, 4566, 4571, 4584, 4589, 4594, 4599, 4608, 4616, 4620, 4624, 4629, 4634, 4649, 4664, 4668, 4672, 4676, 4680, 4684, 4688, 4697, 4703, 4709, 4713, 4717, 4722, 4727, 4731, 4735, 4739, 4744, 4748, 4752, 4756, 4761, 4796, 4800, 4805, 4810, 4814, 4819, 4823, 4828, 4833, 4838, 4842, 4846 |
| <code>\msg_new:nnnn</code> | 4575, 4766, 4775, 4784, 4790 |
| <code>\msg_term:nnnn</code> | 1794, 1799, 3168, 3178, 3207, 3212 |
| <code>\msg_term:nnnnn</code> | 1954 |
| <code>\msg_warning:nn</code> | 3371, 3488 |
| <code>\msg_warning:nnnn</code> | 1991, 1997, 3116, 3121, 3661, 3674, 3710, 3723 |
| <code>\msg_warning:nnnnn</code> | 1949, 1959 |
| <code>\multicolsep</code> | 94, 97 |
| <code>\multicolsep</code> | 3340, 3461 |

N

| | |
|--------------------------------------|--|
| <code>\NeedsTeXFormat</code> | 3 |
| <code>\newcounter</code> | 427 |
| <code>\NewDocumentCommand</code> | 1372, 2429, 3500, 4347, 4401, 4507 |
| <code>\NewDocumentEnvironment</code> | 3217, 3386, 3541, 3863, 4108 |
| <code>\newenvsc</code> | 2543 |
| <code>\newlabel</code> | 35 |
| <code>\newlabel</code> | 410 |
| <code>no-store</code> | 1844 |
| <code>\noindent</code> | 106, 111 |
| <code>\noindent</code> | 3317, 3441, 3769, 3824, 3876, 4088, 4120, 4326 |
| <code>\nointerlineskip</code> | 3317, 3441, 3769, 3824 |
| <code>noitemsep</code> | 752 |
| <code>\nopagebreak</code> | 1077, 1105, 1221, 1300, 1363, 1369 |
| <code>\normalfont</code> | 2388, 2901, 2914, 4244 |
| <code>nosep</code> | 752 |

P

Packages:

| | |
|----------------------------|----------------------------------|
| <code>caption</code> | 104 |
| <code>enumext</code> | 25, 30, 38, 62, 90, 99, 120 |
| <code>enumitem</code> | 35, 36 |
| <code>expl3</code> | 101 |
| <code>footnotehyper</code> | 34 |
| <code>hyperref</code> | 29, 30, 34, 35, 74, 84, 109, 120 |

| | |
|-------------------------------|--|
| <code>lua-visual-debug</code> | 50 |
| <code>multicol</code> | 25, 120 |
| <code>scontents</code> | 25, 77, 78 |
| <code>shortlst</code> | 101 |
| <code>\par</code> | 1077, 1105, 1221, 1300, 1363, 1369, 1398, 1415, 2367, 3361, 3376, 3478, 3493, 3616, 3787, 3801, 3842, 3856, 4088, 4102, 4326, 4342 |
| <code>\parindent</code> | 4065, 4294 |
| <code>\parsep</code> | 48, 51, 100, 101 |
| <code>\parsep</code> | 3198, 3581, 3588, 3593 |
| <code>parsep</code> | 752 |
| <code>\parskip</code> | 4066, 4295 |
| <code>\partopsep</code> | 101 |
| <code>\partopsep</code> | 3199, 3586 |
| <code>partopsep</code> | 752 |

peek commands:

| | |
|---------------------------------------|--|
| <code>\peek_meaning:NTF</code> | 3954, 3968, 3985, 3996, 4173, 4187, 4204 |
| <code>\peek_meaning_remove:NTF</code> | 3961, 4180 |
| <code>\peek_remove_spaces:n</code> | 3062 |
| <code>\phantomsection</code> | 34 |
| <code>\phantomsection</code> | 399 |

prg commands:

| | |
|--|---------------|
| <code>\prg_do_nothing:</code> | 403 |
| <code>\prg_new_protected_conditional:Npnn</code> | 201 |
| <code>\prg_replicate:nn</code> | 218 |
| <code>\prg_return_false:</code> | 205 |
| <code>\prg_return_true:</code> | 204 |
| <code>\printkeyans</code> | 16, 116, 4401 |

prop commands:

| | |
|---------------------------------------|---|
| <code>\prop_count:N</code> | 333, 2139, 2292, 2391, 2801, 2904, 2917, 4247 |
| <code>\prop_gput_if_not_in:Nnn</code> | 2137 |
| <code>\prop_if_exist:NTF</code> | 1828, 4367 |
| <code>\prop_item:Nn</code> | 4370 |
| <code>\prop_new:N</code> | 1831 |
| <code>\ProvidesExplPackage</code> | 4 |

R

| | |
|------------------------------|---------------|
| <code>\raggedcolumns</code> | 3349, 3467 |
| <code>\ref</code> | 72, 82 |
| <code>ref</code> | 540, 587, 660 |
| <code>\refstepcounter</code> | 4024, 4267 |

regex commands:

| | |
|--------------------------------------|-------------------------------|
| <code>\regex_match:nnTF</code> | 203, 709, 711, 723, 725, 2636 |
| <code>\regex_replace_once:nnN</code> | 211 |
| <code>\renewcommand</code> | 575, 620, 637, 690 |
| <code>\RenewDocumentCommand</code> | 2953, 3023, 3058, 3084, 3100 |
| <code>\RequirePackage</code> | 17, 25 |
| <code>resume</code> | 1535 |
| <code>resume*</code> | 1535 |
| <code>rightmargin</code> | 832 |
| <code>\Roman</code> | 36, 41 |
| <code>\Roman</code> | 446 |
| <code>\roman</code> | 36, 41 |
| <code>\roman</code> | 447, 558, 4391 |

S

| | |
|-----------------------|------|
| <code>\s</code> | 2637 |
| <code>save-ans</code> | 1783 |
| <code>save-key</code> | 2078 |
| <code>save-ref</code> | 2003 |
| <code>save-sep</code> | 2003 |

scan commands:

| | |
|--------------------------|-----------------------------------|
| <code>\scan_stop:</code> | 101, 3595, 3875, 4119, 4358, 4361 |
|--------------------------|-----------------------------------|

scontents internal commands:

\l_scontents_fname_out_tl 2596
 _scontents_parse_environment_keys:n . 2602
 _scontents_rescan_tokens:n 2609
 \l_scontents_storing_bool 2594
 \l_scontents_writing_bool 2595

seq commands:

\seq_clear:N 4514
 \seq_const_from_clist:Nn 4502
 \seq_count:N 334, 3554, 4518
 \seq_gclear:N 2951, 2952
 \seq_gput_right:Nn 2146, 2964, 2965
 \seq_if_empty:NTF 2970, 4416, 4532
 \seq_if_exist:NTF 1833, 4414
 \seq_if_in:NnTF 4421
 \seq_item:Nn 2634, 3613
 \seq_map_function:NN 4523
 \seq_map_inline:Nn . . 4429, 4436, 4511, 4533, 4534
 \seq_map_pairwise_function:NNN 2972
 \seq_new:N 120, 121, 133, 157, 158, 1836
 \seq_pop_left:NN 4522
 \seq_put_right:Nn 3514, 4530, 4547
 \seq_set_from_clist:Nn 4515
 \seq_set_map_e:NNn 4524
 \seq_show:N 4418

series 1535

\setcounter 720, 724, 726, 3159, 3201, 3559

\setenumext 6, 118, 4507

show-ans 2003, 2042

show-length 908

show-pos 2042

skip commands:

\skip_add:Nn 1046, 1052, 1058, 1068, 1072, 1096, 1100,
 1190, 1196, 1202, 1212, 1216, 1238, 1291, 1295, 3581
 \skip_gset:Nn 1311, 1315, 1319
 \skip_gzero_new:N 1306, 1307
 \skip_horizontal:N 880, 892, 904, 4048, 4062, 4291
 \skip_horizontal:n . . . 866, 2214, 2222, 3077, 3079,
 4046, 4300
 \skip_if_eq:nnTF 1044, 1050, 1056, 1113, 1147, 1188,
 1194, 1200, 1231, 1236, 1257, 1308, 1330, 1443, 1457,
 1471, 1482, 1493, 1504, 1515, 1526
 \skip_new:N 80, 81, 85, 86, 87, 88, 89, 137, 176
 \skip_set:Nn 1029, 1033, 1082, 1086, 1116, 1120, 1124,
 1131, 1135, 1139, 1150, 1155, 1159, 1165, 1170, 1175,
 1233, 1234, 1235, 1242, 1246, 1250, 1259, 1264, 1268,
 1271, 1275, 1279, 1310, 1314, 1332, 1336, 1340, 1346,
 1350, 1354, 3575, 3589
 \skip_set_eq:NN 3157, 3197, 3198, 4065, 4066, 4294,
 4295
 \skip_use:N 1031, 1035, 1070, 1074, 1078, 1098, 1102,
 1114, 1133, 1142, 1148, 1153, 1157, 1168, 1172, 1173,
 1178, 1214, 1218, 1244, 1444, 1448, 1451, 1458, 1462,
 1465, 3361
 \skip_zero:N 3199, 3340, 3461, 3586, 3587
 \skip_zero_new:N 1226, 1227, 1228, 1305, 1327, 1328,
 1329
 \c_zero_skip 1044, 1050, 1056, 1114, 1148, 1188, 1194,
 1200, 1231, 1236, 1257, 1308, 1330, 1444, 1458, 1471,
 1482, 1493, 1504, 1515, 1526
 \small 4379, 4383, 4387, 4391, 4395, 4399
 \star 2935
 start 732
 \stepcounter 2957, 3521

str commands:

\c_backslash_str 2482, 4587, 4592, 4597, 4602, 4604,
 4606, 4611, 4613, 4711, 4715, 4719, 4729, 4733, 4741,
 4742, 4746, 4758, 4759, 4763, 4764, 4785, 4787, 4791,
 4793, 4825, 4826, 4830, 4835, 4836
 \c_colon_str 2291, 2800, 4358
 \c_left_brace_str 4692, 4699, 4705
 \c_right_brace_str 4692, 4699, 4705
 \str_case:nn 223, 280
 \str_case:nnTF . 1558, 1568, 2117, 2125, 4456, 4465
 \str_clear:N 3250, 3902
 \str_count:n 218
 \str_if_empty:NTF 1580, 1621, 1648
 \str_if_eq:nnTF 3160, 3203
 \str_if_in:nnTF 4354
 \str_new:N 123, 171
 \str_set:Nn . . . 529, 530, 531, 2020, 2021, 2047, 2048
 \string 392
 \strutbox . 1118, 1122, 1126, 1137, 1141, 1152, 1161, 1167,
 1177, 1190, 1196, 1202, 1233, 1234, 1235, 1238, 1248,
 1252, 1261, 1268, 1273, 1281, 1310, 1311, 1314, 1321,
 1334, 1342, 1348, 1356, 3591

T

TeX and \TeX 2_ε commands:

\@auxout 408
 \@currenvir 223, 280
 \protected@write 408

tex commands:

\tex_newlinechar:D 2608

text commands:

\text_expand:n 4350
 \textasteriskcentered 2017, 2034
 \thepage 414

tl commands:

\c_space_tl 2882, 4636, 4651, 4674, 4678
 \tl_clear:N . . 499, 505, 2001, 2064, 2074, 2095, 2103,
 2311, 2628, 2629, 2743, 2817, 4210
 \tl_clear_new:N 456
 \tl_const:Nn 49, 440
 \tl_gclear:N . 325, 326, 327, 1601, 1606, 2718, 3095,
 3805, 3860, 4049
 \tl_gclear_new:N 1588
 \tl_gput_right:Nn 441
 \tl_greplace_all:Nnn 462
 \tl_gset:Nn 256, 257, 271, 272, 1589, 1602, 1607, 1826,
 2632, 3991
 \tl_gset_eq:NN 458, 3003, 4042
 \tl_if_blank:nTF 2421, 2439, 2576, 4040
 \tl_if_empty:NTF . 563, 582, 610, 627, 647, 654, 680,
 697, 1614, 1619, 1641, 1646, 1704, 1768, 1776, 1805,
 1865, 2153, 2184, 2331, 2673, 2695, 2725, 2754, 2827,
 2876, 3074, 4213, 4545
 \tl_if_empty:nTF 1669
 \tl_if_exist:NTF 1674
 \tl_if_novalue:nTF . . 2435, 2751, 2825, 2861, 2955,
 2980, 2999, 3004, 3034, 3248, 3552, 3900, 4147, 4211,
 4509
 \tl_map_inline:Nn 209, 459
 \tl_new:N . 42, 43, 46, 51, 52, 55, 56, 62, 64, 65, 67, 68,
 101, 102, 103, 109, 110, 111, 112, 113, 114, 115, 116,
 117, 118, 122, 124, 127, 128, 140, 148, 149, 150, 153,
 170
 \tl_put_left::Ne 2662
 \tl_put_left:Nn 2161, 2192, 2316, 2656, 2669, 2675,
 2685, 2888, 2923, 3790, 3845, 4229, 4232

| | |
|----------------------------------|--|
| <code>\tl_put_right:Nn</code> | 457, 573, 618, 635, 688, 2165, 2196, 2243, 2253, 2267, 2283, 2289, 2294, 2318, 2323, 2330, 2333, 2343, 2348, 2351, 2357, 2746, 2749, 2756, 2758, 2785, 2790, 2795, 2798, 2807, 2820, 2823, 2829, 2834, 2844, 4215, 4216 |
| <code>\tl_remove_all:Nn</code> | 4544 |
| <code>\tl_remove_once:Nn</code> | 2231, 2770 |
| <code>\tl_replace_all:Nnn</code> | 461 |
| <code>\tl_reverse:N</code> | 2230, 2232, 2769, 2771 |
| <code>\tl_set:Nn</code> | 57, 284, 291, 298, 426, 500, 504, 509, 510, 562, 607, 679, 863, 877, 889, 901, 1703, 1804, 2065, 2075, 2096, 2104, 2385, 2596, 2863, 2898, 2911, 3001, 4218, 4241, 4542 |
| <code>\tl_set_eq:NN</code> | 467, 568, 571, 615, 617, 632, 634, 685, 687, 2229, 2768, 2781, 3046, 3050, 3533, 3535 |
| <code>\tl_to_str:n</code> | 1674, 1680, 1685, 4350 |
| <code>\tl_trim_spaces:n</code> | 457, 4530, 4542, 4548 |
| <code>\tl_use:N</code> | 463, 466, 584, 649, 656, 699, 934, 938, 942, 946, 950, 954, 958, 962, 966, 970, 974, 978, 982, 986, 990, 994, 2219, 2236, 2244, 2255, 2269, 2274, 2286, 2988, 2994, 3019, 3037, 3041, 3049, 3086, 3087, 3094, 3102, 3103, 3109, 3224, 3392, 3538, 3797, 3852, 4052, 4063, 4067, 4281, 4292, 4298, 4303, 4404, 4405, 4406, 4407, 4408, 4426, 4526 |
| token commands: | |
| <code>\token_to_str:N</code> | 410 |
| <code>topsep</code> | 752 |
| <code>\typeout</code> | 378, 381, 391, 392 |
| U | |
| <code>\u</code> | 212, 2637 |
| use commands: | |
| <code>\use:N</code> | 219, 3091, 3226 |
| <code>\use:n</code> | 1549, 2108, 4356, 4447 |
| <code>\use_none:nn</code> | 402 |
| <code>\usecounter</code> | 3158, 3200 |
| V | |
| <code>\value</code> | 1617, 1623, 1630, 1636, 1644, 1650, 1657, 1663 |
| vbox commands: | |
| <code>\vbox_set_top:Nn</code> | 3795, 3850 |
| <code>\vspace</code> | 363, 813, 824, 1448, 1451, 1462, 1465, 1475, 1477, 1486, 1488, 1497, 1499, 1508, 1510, 1519, 1521, 1530, 1532, 3549, 3560, 4103, 4343 |
| W | |
| <code>widest</code> | 732 |
| <code>wrap-ans</code> | 2003 |
| <code>wrap-label</code> | 470 |
| <code>wrap-label*</code> | 470 |
| <code>wrap-opt</code> | 2003 |
| Z | |
| <code>\z</code> | 2637 |