enumext

ENUMERATE EXERCISE SHEETS

v2.3 2026-10-03*

©2024–2026 by Pablo González L†

CTAN: https://www.ctan.org/pkg/enumext
https://github.com/pablgonz/enumext

Abstract

This package provides enumerated list environments compatible with *tagging* PDF for creating *"simple exercise sheets"* along with *"multiple choice questions"*, storing the *"answers"* to these in memory using multicol package.

Contents

1 Introduction . . . 1
1.1 Description and usage . . . 2
1.2 The concept of left margin . . . 3
1.3 User interface . . . 3
1.3.1 Public counters . . . 3
1.3.2 Public dimension . . . 3
1.3.3 Support for multicol . . . 4
1.3.4 Support for minipage . . . 4
1.3.5 The \label and \ref system . . . 4
1.3.6 Support for \footnote . . . 4
2 The environments provided . . . 5
2.1 The environment enumext . . . 5
2.2 The environment enumext* . . . 5
2.3 The command \item* . . . 5
2.3.1 Keys for \item* . . . 5
2.4 The command \item in enumext* . . . 6
3 The command \setenumext . . . 6
4 The command \setenumextmeta . . . 6
5 The keyval system . . . 7
5.1 Keys for label and ref . . . 7
5.2 Keys for penalties . . . 8
5.3 Keys for spaces . . . 8
5.3.1 Vertical spaces . . . 8
5.3.2 Horizontal spaces . . . 9
5.4 Keys for add code . . . 10
5.5 Keys for start, series and resume . . . 10
5.6 Keys for reset . . . 11
5.6.1 The command \resetenumext . . . 11
5.7 Keys for multicols . . . 12
5.8 Keys for minipage . . . 12
5.8.1 The command \miniright . . . 12
5.8.2 The key mini-right . . . 12
6 The storage system . . . 12
6.1 Keys for storage system . . . 13
6.1.1 Keys for label and ref . . . 13
6.1.2 Keys for wrap and marks . . . 13
6.1.3 Keys for debug and checking . . . 14
6.2 The command \anskey . . . 15
6.2.1 Keys for \anskey . . . 15
6.3 The environment anskey* . . . 15
6.3.1 Keys for anskey* . . . 16
6.4 The environment keyans . . . 17
6.4.1 The \item* in keyans . . . 17
6.5 The environment keyanspic . . . 18
6.5.1 Keys for keyanspic . . . 18
6.5.2 The command \anspic . . . 18
6.6 Printing stored content . . . 20
6.6.1 The command \getkeyans . . . 20
6.6.2 The command \foreachkeyans . . . 20
6.6.3 The command \printkeyans . . . 20
7 Full examples . . . 22
8 Tagged PDF examples . . . 24
9 The way of non-enumerated lists . . . 25
10 References . . . 27
11 Change history . . . 28
12 Index of Documentation . . . 29
13 Implementation . . . 31
14 Index of Implementation . . . 160

Motivation and acknowledgments

Usually, it is enough to use the classic enumerate environment to generate *"simple exercise sheets"* or *"multiple choice questions"*, the basic idea behind enumext is to cover three points:

1. To have a simple interface to be able to write *"lists of exercises"* with *"answers"*.
2. To have a simple interface for writing *"multiple choice questions"*.
3. To have a simple interface for placing *"columns"* and *"drawings"* or *"tables"*.

This package would not be possible without Phelype Oleinik who has collaborated and adapted a large part of the code and all LaTeX team for their great work and to the different members of the TeX-SX community who have provided great answers and ideas. Here are notes on the main ones:

1. Answer given by Alan Munn in \topsep, \itemsep, \partopsep, \parsep - what do they each mean (and what about the bottom)?

*This file describes a documentation for v2.3, last revised 2026-10-03.

†E-mail: «pablgonz@educarchile.cl».

2. Answer given by Enrico Gregorio in Understanding minipages - aligning at top
3. Answer given by Ulrich Diez in Different mechanics of hyperlink vs. hyperref
4. Answer given by Enrico Gregorio in Minipage and multicols, vertical alignment

License and Requirements

Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License (lppl), version 1.3 or later (https://www.latex-project.org/lppl.txt). The software has the status "maintained".

The enumext package loads and requires multicol[3] package, need to have a modern TEX distribution such as TEX Live or MiKTEX. It has been tested with the standard classes provided by LATEX: book, report, article and letter on 10pt, 11pt and 12pt.

The minimum requirement is LATEX release 2026-11-01.

1 Introduction

In the LATEX world there are many useful packages and classes for creating *"lists of exercises"*, *"worksheets"* or *"multiple choice questions"*, classes like exam[1] and packages like xsim[2] do the job perfectly, but they don't always fit the basic day to day needs.

In the work of many teachers it is common to use *"simple exercise sheets"* also known as *"informal lists of exercises"*, for example:

1. Factor $x^2 - 2x + 1$
2. Factor $3x + 3y + 3z$
3. True False
   (a) $\alpha > \delta$
   (b) LATEX2e is cool?
4. Related to Linux
   (a) You use Linux?
   (b) Usually uses the package manager?
   (c) Rate the following package and class
      i. xsim-exam
      ii. xsim
      iii. exsheets

Sometimes it is also useful to show the *"answers"* along with the questions:

1. Factor $x^2 - 2x + 1$
   * $(x-1)^2$
2. Factor $3x + 3y + 3z$
   * $3(x+y+z)$
3. True False
   (a) $\alpha > \delta$
      * False
   (b) LATEX2e is cool?
      * Very True!
4. Related to Linux
   (a) You use Linux?
      * Yes
   (b) Usually uses the package manager?
      * Yes, dnf
   (c) Rate the following package and class
      i. xsim-exam
         * doesn't exist for now :(
      ii. xsim
         * very good
      iii. exsheets
         * obsolete

Or to refer to a specific question and its *"answer"*, for example:

The answer to 3.(b) is "Very True!" and the answer to 4.(c).ii is "very good".

Or to print all the *"answers"*:

1. $(x-1)^2$ ※
2. $3(x+y+z)$ ※
3. (a) False ※
   (b) Very True! ※
4. (a) Yes ※
   (b) Yes, dnf ※
   (c) i. doesn't exist for now :(※
      ii. very good ※
      iii. obsolete ※

Another very common thing to use is *"multiple choice questions"*, for example:

1. First type of questions

   A) value
   B) correct
   C) value
   D) value

2. Second type of questions

   I. $2\alpha + 2\delta = 90°$
   II. $\alpha = \delta$
   III. $\angle EDF = 45°$


   A) I only
   B) II only
   C) I and II only
   D) I and III only
   E) I, II, and III

⋆ 3. Third type of questions

   (1) $2\alpha + 2\delta = 90°$
   (2) $\angle EDF = 45°$


   A) value
   B) value
   C) value
   D) value
   E) value

4. Question with image and label below:



5. Question with image on right side:

   A) value
   B) value
   C) value
   D) correct
   E) value



Here the ⟨*label*⟩ and a *"short note"* left as an explanation are stored, and then printed:

1. B) $x = 5$ ※
2. D) ※
3. C) some note ※
4. E) A duck ※
5. D) "other note" ※

The enumext package was created and designed to meet these small requirements in the creation of *"simple worksheets"* and *"multiple choice questions"*.

These *"simple worksheets"* or *"multiple choice questions"* appear to be easy to obtain using a combination of the `enumerate`, `minipage` and `multicols` environments, but like many things, what *"looks simple"* is not so simple.

1.1 Description and usage

The enumext package defines enumerated environments using the `list` environment provided by LaTeX, but *"does not redefine"* any internal commands associated with it such as `\list`, `\endlist` or `\item` outside of the *"scope"* in which they are defined.

This package is NOT intended to replace the `enumerate` environment nor replace the powerful `enumitem`[6], the approach is intended to work without hindering either of them.

This package can be used with `xelatex`, `lualatex`, `pdflatex` and the classical `latex»dvips»ps2pdf` and is present in TeX Live and MiKTeX, use the package manager to install. For manual installation, download enumext.zip and unzip it, run `luatex enumext.ins` and move all files to appropriate locations, then run `mktexlsr`. To produce the documentation run `arara enumext.dtx`.

```
enumext.sty  »  TDS:tex/latex/enumext/
enumext.pdf  »  TDS:doc/latex/enumext/
README.md    »  TDS:doc/latex/enumext/
enumext.dtx  »  TDS:source/latex/enumext/
enumext.ins  »  TDS:source/latex/enumext/
```

The package is loaded in the usual way:

```
\usepackage{enumext}
```

1.2 The concept of left margin

There is a direct relationship between the parameters `\leftmargin`, `\itemindent`, `\labelwidth` and `\labelsep` plus an *"extra space"*, which makes it difficult to obtain the desired *horizontal spaces* in a `list` environment. Usually the `list` should not go beyond the left margin of the page, but since these four values are related, that causes a problem.

The `enumitem`[6] package adds the `\labelindent` parameter to solve some of these problems. A simplified representation of this in the figure 1.




Figure 1: Representation of horizontal lengths in `enumitem`.

The enumext package does NOT provide a user interface to set the values for `\leftmargin` and `\itemindent`, instead it provides the keys `list-offset` and `list-indent` which internally set the values for `\leftmargin` and `\itemindent`. The concepts of `\leftmargin` and `\itemindent` are different in enumext. The figure 2 shows the visual representation of idea.




Figure 2: Representation of horizontal lengths concept in enumext.

In this way the number of parameters to pass is reduced a *little*. With the default values of keys `list-offset`, `list-indent`, `labelwidth` and `labelsep` the lists will have the (usually) expected output for *"simple worksheets"*. The figure 3 shows the visual representation.




Figure 3: Default horizontal lengths `list-offset=0pt`, `list-indent=\labelwidth+\labelsep` in enumext.

1.3 User interface

The user interface consists of two main list environments `enumext` (vertical) and `enumext*` (horizontal), the environment `anskey*` and the command `\anskey` to *"store content"* and the environments `keyans`, `keyans*` and `keyanspic` for multiple choice. It also provides the commands `\getkeyans` to print individual *stored content*, `\printkeyans` to print all *stored content*, `\foreachkeyans` to print a range of *stored content*, `\miniright` for `minipage`, `\setenumext` to config [⟨*key* = *val*⟩], `\setenumextmeta` to add a *"meta-key"* and `\resetenumext` to reset counters.

1.3.1 Public counters

The package enumext uses the `enumXi`, `enumXii`, `enumXiii`, `enumXiv` counters for the *four* nesting levels of the `enumext` environment, the `enumXv` counter for the `keyans` environment, the `enumXvi` counter for the `keyanspic` environment, the counter `enumXvii` for `enumext*` environment and the counter `enumXviii` for `keyans*` environment.

If any package defines these *counters* or they are user-defined in the document, the package will return a *"fatal error"* and abort the load.

1.3.2 Public dimension

The package enumext only provides a *single public dimension* `\itemwidth` and is intended for user convenience only and is NOT for internal use as such. The dimension `\itemwidth` is a *rigid length* and contains the *"width of the content"* of each `\item` regardless of `labelwidth` and `labelsep`.

If any package defines `\itemwidth` or the user defines `\itemwidth` in the document, the package will overwrite it without warning.

1.3.3 Support for multicol

The package provides direct support for using the `multicol`[3] package. This allows for a two-column output as shown in the figure 4.




Figure 4: Representation of the two column output for a nested level in `enumext` environment.

The *"non starred"* version of the `multicols` environment is always used together with the `\raggedcolumns` command and is controlled by `columns` and `columns-sep` keys. It can be used in all nesting levels of the environment `enumext` and the environment `keyans` and can together with the `mini-env` key. If you need to force a start a new column `\columnbreak` must be used (see §5.7).

The `\columnseprule` command is not available as a key and is set to *"zero"* for the inner levels and the `keyans` environment. If the value of this is set inside the document, it will affect *"all environments"* that use the `columns` key.

1.3.4 Support for `minipage`

The package provides direct support for `minipage` environment, this allows you to obtain an output like the one shown in figure 5.



Figure 5: Representation of the `mini-env` output for a nested level `enumext` environment.

The `minipage` environments on the *"left side"* and *"right side"* are always used with *"aligned on top"* `[t]`. It can be used in all nesting levels of the environment `enumext` and the environment `keyans` and is controlled by `mini-env` and `mini-sep` keys. In order to switch from the *"left"* side `minipage` environment to the *"right"* side one must use the command `\miniright` (see §5.8).

©2024–2026 by Pablo González L

1.3.5 The `\label` and `\ref` system

This package provides a user interface like the enumitem[6] package to customize the references which is activated by the `ref` key (§5.1), the standard LaTeX `\label` and `\ref` commands work as usual. It also provides an *"internal reference"* system for the *"stored content"* by means of the key `save-ref` (§6.1.1) when the key `save-ans` is active (§6.1).

1.3.6 Support for `\footnote`

The `enumext*` and `keyans*` environments and the `mini-env` key use the `minipage` environment in their implementation but in a transparent way for the user, it is only used for typesetting. The implementation supports `\footnote` and is compatible with `hyperref` and works the same way as if used anywhere in the document.

Unfortunately, if `hyperref` is loaded and *tagged* PDF is not active, it will not produce the "links", the internal implementation uses `\footnotetext[`⟨*number*⟩`]` and `\footnotemark[`⟨*number*⟩`]{`⟨*text*⟩`}` and "links" for this are not supported by the `hyperref` package.

The best way to solve this if *tagged* PDF is NOT active is to use Jean-François Burnol's `footnotehyper`[9] package. It will support keeping the "links" if `hyperref` is loaded with the `hyperfootnotes=true` option (default). Load it is as follows:

```
\IfDocumentMetadataF
  {
    \usepackage{footnotehyper}
    \makesavenoteenv{enumext}
    \makesavenoteenv{enumext*}
  }
```

At the moment the `footnotehyper` package v1.1f (2025/11/15) is not compatible with *tagged* PDF.

2 The environments provided

The package enumext provides two main list environments, the *vertical* environment `enumext` and the *horizontal* environment `enumext*`.

`enumext`
`enumext*`

```
\begin{enumext}[⟨keyval list⟩]
  \item ⟨item content⟩
  \item [⟨custom⟩] ⟨item content⟩
  \item*[⟨symbol⟩][⟨offset⟩] ⟨item content⟩
\end{enumext}
```

```
\begin{enumext*}[⟨keyval list⟩]
  \item ⟨item content⟩
  \item [⟨custom⟩] ⟨item content⟩
  \item*[⟨symbol⟩][⟨offset⟩] ⟨item content⟩
\end{enumext*}
```

2.1 The environment `enumext`

The `enumext` is an environment that works in the same way as the standard `enumerate` environment provided by LaTeX, `\item` and `\item[`⟨*custom*⟩`]` commands work in the usual way. The environment can be nested with at most *"four levels"* and the options can be configured globally using `\setenumext` command and locally using `[`⟨*key* = *val*⟩`]` in the environment.

Example with `columns=2`

1. This text is in the first level.
   (a) This text is in the second level.
      i. This text is in the third level.

A. This text is in the fourth level.
X This text is in the first level.
⋆ 2. This text is in the first level.

2.2 The environment `enumext*`

The `enumext*` is a *horizontal list environment* similar to the `shortenumerate` or `tasks` environments provided by the `shortlst`[16] and `tasks`[17] packages, `\item` and `\item[`⟨*custom*⟩`]` work as usual. The options can be configured globally using `\setenumext` command and locally using `[`⟨*key* = *val*⟩`]` in the environment.

Some considerations to take into account for this environment:

- The environment cannot be nested within itself or in the environment `keyans*`, but it can be nested within `enumext` and vice versa.
- Each *"item content"* in the environment is placed within a `minipage` environment whose *width* is stored in the dimension `\itemwidth` does NOT include `labelwidth` and `labelsep`, only the *width of the content.*
- You cannot have floating environments like `figure` or `table` or `\marginpar` but `\footnote` with `hyperref` is supported. If you want to activate links *"without" tagged* PDF active you must load `footnotehyper` and `hyperref` packages (see §1.3.6).

©2024–2026 by Pablo González L

- You cannot have any standard list environments like `itemize`, `enumerate`, `description`, `quote`, `quotation`, `verse`, `center`, `flushleft`, `flushright`, `verbatim`, `tabbing`, `trivlist`, `list` and all environments created with `\newtheorem`.

Example with `columns=2`

1. This text is in the first level.
2. This text is in the first level.

X This text is in the first level.

⋆ 4. This text is in the first level.

2.3 The command `\item*`

`\item*` `\item*[⟨symbol⟩][⟨offset⟩]`

The `\item*`, `\item*[⟨symbol⟩]` and `\item*[⟨symbol⟩][⟨offset⟩]` work like the numbered `\item`, but places a ⟨*symbol*⟩ to the *"left"* of the ⟨*label*⟩ separated from it by the ⟨*offset*⟩ set by the *second optional argument*.

The *starred argument* '`*`' cannot be separated by spaces '␣' from the command, i.e. `\item*` and the *first optional argument* does NOT support *verbatim content*. It can be configured with the keys `item-sym*` and `item-pos*` locally in the environment or globally using `\setenumext` command (§3).

The behavior of `\item*` in the `enumext` and `enumext*` environments is NOT the same as in the `keyans` and `keyans*` environments.

2.3.1 Keys for `\item*`

`item-sym*` = {⟨*symbol*⟩} default: *\textborn*

Sets the *symbol* to be displayed to the *"left"* of the box containing the current ⟨*label*⟩ set by `labelwidth` key for `\item*` in `enumext` and `enumext*`. The *symbol* can be in *text* or *math* mode, for example `item-sym*={$\star$}`.

`item-pos*` = {⟨*rigid length*⟩} default: *by levels*

Sets the *offset* between the box containing the current ⟨*label*⟩ defined by `labelwidth` key and the ⟨*symbol*⟩ set by `item-sym*` key. The default values are set by `labelsep` key at each level. If positive values are passed, it will *offset to the left*; if negative values are passed it will *offset to the right*.

2.4 The command `\item` in `enumext*`

`\item` `\item(⟨columns⟩)`

The `\item` command for the `enumext*` environment provides a *"first optional argument"* `\item(⟨columns⟩)` which *"joins items"* between columns.

Let's consider the following examples adapted directly from the `tasks` package:

```
\begin{enumext*}[widest=10,columns=4]
  \item The first
  \item* The second
  \item The third
  \item The fourth
  \item(3)* The fifth item is way too long for this and needs three columns
  \item The sixth
  \item The seventh
  \item(2)[X] The eighth item is way too long for this and needs two columns
    (\the\itemwidth)
  \item The ninth
  \item[Z] The tenth (\the\itemwidth)
\end{enumext*}
```

1. The first
⋆ 2. The second
3. The third
4. The fourth
⋆ 5. The fifth item is way too long for this and needs three columns
6. The sixth
7. The seventh
X The eighth item is way too long for this and needs two columns (196.17749pt)
9. The ninth
Z The tenth (89.28171pt)

3 The command `\setenumext`

`\setenumext`

`\setenumext{⟨key = val⟩}`
`\setenumext[⟨enumext, level⟩]{⟨key = val⟩}`
`\setenumext[⟨enumext*⟩]{⟨key = val⟩}`
`\setenumext[⟨keyans⟩]{⟨key = val⟩}`
`\setenumext[⟨keyans*⟩]{⟨key = val⟩}`
`\setenumext[⟨print, level⟩]{⟨key = val⟩}`
`\setenumext[⟨print, *⟩]{⟨key = val⟩}`
`\setenumext[⟨print*⟩]{⟨key = val⟩}`

The command `\setenumext` sets the ⟨*keys*⟩ on a global basis for environments `enumext`, `enumext*`, `keyans`, `keyans*` and the `\printkeyans` command. It can be used both in the preamble and in the body of the document as many times as desired.

©2024–2026 by Pablo González L

The ⟨*keys*⟩ set in the *optional argument* of environments and commands have the *highest precedence*, overriding both options passed by \setenumext. If the *optional argument* is not passed, the *first level* of the environment enumext will be taken by default.

For security reasons the keys resume *"with value"*, resume*, reset, reset*, series and save-ans they can NOT be set by this command and are ignored. The key save-ans that activates the *"storage system"* must be passed directly in the *optional argument* of the *"first level"* of the environment in which they are executed.

4 The command \setenumextmeta

\setenumextmeta

```
\setenumextmeta[⟨1⟩]{⟨key name⟩}{⟨key-one = val, key-two = val, ...⟩}
\setenumextmeta[⟨2⟩]{⟨key name⟩}{⟨key-one = val, key-two = val, ...⟩}
\setenumextmeta[⟨3⟩]{⟨key name⟩}{⟨key-one = val, key-two = val, ...⟩}
\setenumextmeta[⟨4⟩]{⟨key name⟩}{⟨key-one = val, key-two = val, ...⟩}
\setenumextmeta[⟨*⟩]{⟨key name⟩}{⟨key-one = val, key-two = val, ...⟩}
\setenumextmeta*{⟨key name⟩}{⟨key-one = val, key-two = val, ...⟩}
```

The command \setenumextmeta adds a new *"meta-key"* for the environments enumext and enumext*, the {⟨*key name*⟩} must be different from those defined by the package. The *optional argument* of the form [1], [2], [3], [4] adds a new *"meta-key"* for levels 1, 2, 3 and 4 of the enumext environment, the form [*] adds a new *"meta-key"* for the enumext* environment. If it is run *without* the *optional argument*, it will adds a new *"meta-key"* for the *"first level"* of the enumext environment.

The *starred argument* '*' will create the new *"meta-key"* for the environment enumext* and for *"all levels"* of the environment enumext. For example: \setenumextmeta*{midsep}{topsep=3pt, partopsep=0pt} will create a new key midsep available for all levels of the enumext environment and the enumext* environment and it can be used like any other key so \begin{enumext}[midsep] and \begin{enumext*}[midsep] will be valid.

5 The keyval system

The ⟨*key = val*⟩ system used by the enumext package is implemented using l3keys so it must be noted that ⟨*keys*⟩ marked as *"value forbidden"*, that is ⟨*key*⟩ is different from ⟨*key=*⟩.

All ⟨*keys*⟩ described in this section are available for the enumext, enumext*, keyans and keyans* environments with the exception of the keys series, resume, resume*, reset and reset* which are only available for the enumext and enumext* environments; and the keys mini-right, mini-right* which are only available for the enumext* and keyans* environments.

All ⟨*keys*⟩ related to vertical or horizontal spacing accept a *"skip"* or *"dim"* expression if passed between braces, i.e. you do not need to use \dimeval or \dimexpr to perform calculations.

It should be kept in mind that using any ⟨*key*⟩ that sets *rubber lengths* or *rigid lengths* for vertical or horizontal space on a level will influence the vertical and horizontal space for *inner levels* and keyans, keyans* and keyanspic environments.

5.1 Keys for label and ref

mode-box ⟨*value forbidden*⟩ default: *not used*

This is a *"switch-key"* that does not receive an argument and is "only" available for the *"first level"* of the enumext environment and the enumext* environment. When this is set the label, font, wrap-label and wrap-label* keys are executed within \makebox for the enumext and keyans environments.

This key is intended for compatibility with *tagged* PDF and is forcibly *"enabled"* when \DocumentMetadata is present. If you want to get the same document output whether \DocumentMetadata is active or not, you must enable this key.

In the enumext* and keyans* environments \makelabel is redefined using \makebox by default. If enumext or keyans is used in the enumext* environment the key must be activated manually.

label = {⟨\alph* | \Alph* | \arabic* | \roman* | \Roman*⟩} default: *by levels*

Sets the ⟨*label*⟩ that will be printed at the *current level* and default value for labelwidth key. The default value for the first level of the environments enumext and enumext* is \arabic*., for second level are (\alph*), for third level are \roman*. and for fourth level is \Alph*.. For keyans and keyans* environments the default value is \Alph*).

This key is intended to give the basic structure with which the ⟨*label*⟩ will be displayed, and the form in which it is used by standard *"label and ref"* and the *"internal label and ref"* system with the save-ref key. You cannot use commands with ⟨*label*⟩ as an argument, for example \emph{⟨\alph*⟩} will return an error. For full customization of how ⟨*label*⟩ is displayed use the font, wrap-label and/or wrap-label* keys.

labelsep = {⟨*rigid length*⟩} default: 0.3333*em*

Sets the *horizontal space* between the box containing the current ⟨*label*⟩ defined by label key and the text of an item on the first line. Internally sets the value of \labelsep for the current level.

labelwidth = {⟨*rigid length*⟩} default: *by label*

©2024–2026 by Pablo González L

Sets the *width* of the label box containing the current ⟨*label*⟩ set by the `label` key. Internally sets the value of `\labelwidth` for the current level. The default values are calculated by means of the *width* of a box by setting a *value* to the current counter set by `label` key using '`0`' for `\arabic*`, '`M`' for `\Alph*`, '`m`' for `\alph*`, '`VIII`' for `\Roman*` and '`viii`' for `\roman*`.

`widest` = {⟨*integer* | *string*⟩} default: *empty*

Sets the `labelwidth` key passing the ⟨*integer*⟩ or converting the ⟨*string*⟩ of the form `\Alph`, `\alph`, `\Roman` or `\roman` to a *value* for the current counter defined by `label` key, then calculating the *width* by means of a box. For example `widest={XXIII}` or `widest={23}` are equivalent. This key is useful when the default values of the `labelwidth` key are smaller than those actually used.

`font` = {⟨*font commands*⟩} default: *empty*

Sets the *font style* for the current ⟨*label*⟩ defined by `label` key. You cannot use commands with an argument, for example `font={\small\textbf{#1}}` will return an error, but `font={\bfseries\small}` it will work. For full customization of how ⟨*label*⟩ is displayed use `wrap-label` and/or `wrap-label*` keys.

`align` = {⟨*left* | *right* | *center*⟩} default: *left*

Sets the *aligned* of ⟨*label*⟩ defined by `label` key on the current level in the label box of width set by `labelwidth`.

`wrap-label` = {⟨*code* `{#1}` *more code*⟩} default: *empty*

Wraps the *current* ⟨*label*⟩ defined by `label` key referenced by `{#1}` after executing the `align` and `font` keys. The {⟨*code*⟩} must be passed between braces and it does not modify the value set by the `labelwidth` key and is applied *only* on `\item` and `\item*`. When using it in the `\setenumext` command it is necessary to use the *double* '`{##1}`'. For example `wrap-label={\fbox{#1}}` or you can create a command:

```
\NewDocumentCommand \mywrap { s m }
  {
    \IfBooleanTF{#1}
      {\textcolor{red}{\textbf{Q}}\textcolor{blue}{\textbf{.}}\textcolor{gray}{#2}}
      {\textcolor{blue}{\textbf{Q}}\textcolor{red}{\textbf{.}}\textcolor{gray}{#2}}
  }
```

and then pass it through the key `wrap-label={\mywrap{#1}}` or `wrap-label={\mywrap*{#1}}`.

`wrap-label*` = {⟨*code* `{#1}` *more code*⟩} default: *empty*

The same as the `wrap-label` key but also applies on `\item`[⟨*custom*⟩].

`ref` = {⟨*code* {`\alph*`| `\Alph*`| `\arabic*`| `\roman*`| `\Roman*`} *more code*⟩} default: *empty*

Modifies the way *cross references* are displayed. The `label` key sets the default form of the *cross references*, by using this key you can define a different format, for example: `ref=\emph{⟨\alph*⟩}` is valid.

Internally it renews the command associated with each counter when it is executed, i.e., in the environment `enumext` the command `\theenumXi` is modified when the key is executed at the first level, `\theenumXii` when it is executed at the second level and `\theenumXiii` together with `\theenumXiv` when it is executed at the third and fourth levels.

This must be kept in mind, since the values set by the `label` and `ref` keys are not cumulative by levels, so if you have used the `ref` key in the first level and then want to associate the counter with `label` or `ref` in the second level you must use the direct commands, i.e. `\arabic{enumXi}` to indicate the count of the first level instead of using `\theenumXi`.

5.2 Keys for penalties

Page breaks in the provided environments are controlled by the following three parameters, which work together to ensure they look good, avoiding unsightly page breaks that could distort the output.

`beginpenalty` = {⟨*integer*⟩} default: *-51*

Set the *page breaking* penalty for breaking at the beginning of the `enumext`, `enumext*`, `keyans` and `keyans*` environments. Internally sets the value of `\@beginparpenalty`.

`midpenalty` = {⟨*integer*⟩} default: *-51*

Set the *page breaking* penalty for breaking between items of the `enumext`, `enumext*`, `keyans` and `keyans*` environments. Internally sets the value of `\@itempenalty`.

`endpenalty` = {⟨*integer*⟩} default: *-51*

Set the *page breaking* penalty for breaking at the end of the `enumext`, `enumext*`, `keyans` and `keyans*` environments. Internally sets the value of `\@endparpenalty`.

The values passed to these ⟨*keys*⟩ affect the nested environments in which they were set and cannot be reset. LaTeX default is `-\@lowpenalty`, that is, `-51`. Because it is negative, it somewhat encourages a page break at each spot. Change it with, e.g., `\@beginparpenalty=9999`; a value of `10000` prohibits a page break. Please, refer to your LaTeX or TeX manual about how penalties control page breaks.

©2024–2026 by Pablo González L

5.3 Keys for spaces

show-length = {⟨*true* | *false*⟩} default: *false*

Displays on the terminal the values for *all list parameters* at the current level. For *vertical spaces* show the values of `\topsep`, `\itemsep`, `\parsep` and `\partopsep`. For *horizontal spaces* show the values of `\labelwidth`, `\labelsep`, `\itemindent`, `\listparindent` and `\leftmargin`.

5.3.1 Vertical spaces

topsep = {⟨*rubber length* | *rigid length*⟩} default: *by levels*

Set the *vertical space* added to both the top and bottom of the list. Internally sets the value of `\topsep` for the current level. The default value for the first level of the environments `enumext` and `enumext*` are `8.0pt plus 2.0pt minus 4.0pt`, for second level are `4.0pt plus 2.0pt minus 1.0pt`, for third and fourth level are `2.0pt plus 1.0pt minus 1.0pt`. For `keyans` and `keyans*` environments the default value is `4.0pt plus 2.0pt minus 1.0pt`.

parsep = {⟨*rubber length* | *rigid length*⟩} default: *by levels*

Set the *vertical space* between paragraphs within an item. Internally sets the value of `\parsep` for the current level. The default value for the first level of the environments `enumext` and `enumext*` are `4.0pt plus 2.0pt minus 1.0pt`, for second level are `2.0pt plus 1.0pt minus 1.0pt`, for third and fourth level are `0pt`. For `keyans` and `keyans*` environments the default value is `2.0pt plus 1.0pt minus 1.0pt`.

In the `enumext*` and `keyans*` environments this value is passed to `\parskip` within the `minipage` environment where *"item content"* is placed.

partopsep = {⟨*rubber length* | *rigid length*⟩} default: *by levels*

Set the *vertical space* added, beyond `topsep`, to the "top" and "bottom" of the entire environment if the environment instance is preceded by a *"blank line"* or `\par` command. Internally sets the value of `\partopsep` for the current level. The default values for first and second level in environment `enumext` are `2.0pt plus 1.0pt minus 1.0pt`, for third and fourth level are `1.0pt minus 1.0pt`. For the `keyans` environment the default value is `2.0pt plus 1.0pt minus 1.0pt`, and for the `keyans*` and `enumext*` environments it is available but *without* effect.

The value of this parameter also affects the *inner levels* and the environments `keyans`, `keyanspic` and `keyans*`. Caution should be taken with *"blank lines"* or `\par` command *"before"* each environment or nested level when formatting the source code of document. TEX will enter ⟨*vertical mode*⟩ and apply this value to the "top" and "bottom" the environment or nested level.

itemsep = {⟨*rubber length* | *rigid length*⟩} default: *by levels*

Set the *vertical space* between items, beyond the `parsep`. Internally sets the value of `\itemsep` for the current level. The default value for the first level of the environments `enumext` and `enumext*` are `4.0pt plus 2.0pt minus 1.0pt`, for the rest of the levels are `2.0pt plus 1.0pt minus 1.0pt`. For `keyans` and `keyans*` environments the default value is `4.0pt plus 2.0pt minus 1.0pt`.

In the `enumext*` and `keyans*` environments this value corresponds to the separation between rows.

noitemsep ⟨*value forbidden*⟩ default: *not used*

This is a *"meta-key"* that does not receive an argument. Set `itemsep` and `parsep` equal to `0pt` the entire level of environment.

nosep ⟨*value forbidden*⟩ default: *not used*

This is a *"meta-key"* that does not receive an argument. Sets all keys for vertical spacing equal to `0pt` the entire level of environment.

base-fix ⟨*value forbidden*⟩ default: *not used*

This is a *"switch-key"* that does not receive an argument available *only* for the *"first level"* of environment `enumext`. Fix the *baseline* when an environment `enumext` is nested in `enumext*` and there is no material between the `\item` and the start of the environment for example `\item \begin{enumext}` within the environment `enumext*`. Internally sets the keys `topsep`, `above` and `above*` at `0pt`.

This key is provided as a way to work around this minor issue, but you should be aware that if for some reason you have the `itemindent` key set in the `enumext*` environment it will be lost and you will need to adjust it using the `list-offset` key in the `enumext` environment.

Extra vertical spaces

The following ⟨*keys*⟩ should be used with *"caution"*, they are intended to be used at the "top" and "bottom" of the environment when the `columns` or `mini-env` keys do not provide adequate *vertical spaces*. The values passed can be *rubber* or *rigid* lengths, the way they are applied is the way you differ, using the *star* '`*`' ⟨*keys*⟩ applies `\vspace*` so that LATEX does *not discard* this space at page break.

above = {⟨*rubber length* | *rigid length*⟩} default: *not used*

Set the *extra vertical space* added, beyond topsep, to the top of the entire level of environment. This key is intended to give a *"fine adjustment"* of the vertical space *"above"* the environment without hindering the value of the topsep key. The space is added with \vspace so is *"discardable"*.

above* = {⟨*rubber length* | *rigid length*⟩} default: *not used*

Set the *extra vertical space* added, beyond topsep, to the top of the entire level of environment. This key is intended to give a *"fine adjustment"* of the vertical space *"above"* the environment without hindering the value of the topsep key. The space is added with \vspace* so is *"not discardable"*.

below = {⟨*rubber length* | *rigid length*⟩} default: *not used*

Set the *extra vertical space* space added, beyond topsep, to the bottom of the entire level of environment. This key is intended to give a *"fine adjustment"* of the vertical space on the *"below"* the environment without hindering the value of the topsep key. The space is added with \vspace so is *"discardable"*.

below* = {⟨*rubber length* | *rigid length*⟩} default: *not used*

Set the *extra vertical space* space added, beyond topsep, to the bottom of the entire level of environment. This key is intended to give a *"fine adjustment"* of the vertical space on the *"below"* the environment without hindering the value of the topsep key. The space is added with \vspace* so is *"not discardable"*.

5.3.2 Horizontal spaces

list-offset = {⟨*rigid length*⟩} default: 0*pt*

Sets the *horizontal translation* of the entire environment level from the left edge of the box defined by the labelwidth key. Internally sets the values of \leftmargin and \itemindent for the current level.

list-indent = {⟨*rigid length*⟩} default: *labelwidth + labelsep*

Sets the *indentation* of the whole environment under the box defined by labelwidth and labelsep keys. Internally sets the value of \leftmargin and \itemindent for the current level. If list-indent=0pt is set in the environments enumext and keyans the ⟨*label*⟩ will be part of the text, separated by the value of the labelsep key and the *first word*, in simple terms it will look like a *"common paragraph"*.

The enumext* and keyans* environments are implemented using \makebox and minipage which causes *"list indent"* to always be equal to the value passed to labelwidth plus labelsep. Passing a value to this key is equivalent to setting the value for the list-offset key.

itemindent = {⟨*rigid length*⟩} default: 0*pt*

Sets the extra *horizontal indentation*, beyond labelsep, of the *"first line"* of each \item that is not followed by a *"blank line"* or the \par command . This value must be greater than or equal to 0pt and is applied internally using \hspace *without* modifying the value of \itemindent.

This key is intended for the enumext* and keyans* environments where, by their implementation, it is not possible to adjust labelwidth and list-indent *without* modifying the output. If you use enumext or keyans and want to get around the *blank line* limitation or the \par command followed by \item you can modify labelwidth and list-indent and get the same effect.

rightmargin = {⟨*rigid length*⟩} default: 0*pt*

Set the *horizontal space* between the right margin of the environment and the right margin of the enclosing environment, the value it takes must be greater than or equal to 0pt. Internally sets the value of \rightmargin for the current level.

listparindent = {⟨*rigid length*⟩} default: 0*pt*

Sets the *horizontal space* indentation, beyond list-indent, for second and subsequent paragraphs within a list item. Internally sets the value of \listparindent for the current level.

In the enumext* and keyans* environments this value is passed to \parindent within the minipage environment where *"item content"* is placed.

5.4 Keys for add code

The following ⟨*keys*⟩ should be used with *"caution"*, they are intended to inject {⟨*code*⟩} into different parts of the defined environments. It must be kept in mind that the defined environments are based on the list base environment provided by LaTeX which is defined (simplified) as plain form \list{⟨*arg one*⟩}{⟨*arg two*⟩}. Using the before* key does not allow access to the list parameters defined by [⟨*key = val*⟩].

before = {⟨*code*⟩} default: *not used*

Execute {⟨*code*⟩} *"before"* the environment starts. The {⟨*code*⟩} must be passed between braces, is executed *"after"* all calculations related to the *list parameters* in the environment and the ⟨*keys*⟩ sets by [⟨*key = val*⟩] have been performed, that is, in the *second argument* of the list: \begin{list}{⟨*arg one*⟩}{⟨*arg two*⟩{⟨*code*⟩}}.

before* = {⟨*code*⟩} default: *not used*

Execute {⟨*code*⟩} *"before"* the environment starts. The {⟨*code*⟩} must be passed between braces, is executed *"before"* performing all calculations related to the *list parameters* and the ⟨*keys*⟩ sets in [⟨*key = val*⟩] of the environment that is, *"before"* the arguments defining the list environment are executed: {⟨*code*⟩}\begin{list}{⟨*arg one*⟩}{⟨*arg two*⟩}.

©2024–2026 by Pablo González L

`first` = {⟨*code*⟩} default: *not used*

Executes {⟨*code*⟩} when *"starting"* the environment. The {⟨*code*⟩} must be passed between braces, is executed right *"after"* all *list parameters* are done, after the second argument of list, just before the first occurrence of `\item`: `\begin{list}{⟨arg one⟩}{⟨arg two⟩}{⟨code⟩}\item`.

Keep in mind that the {⟨*code*⟩} set in this ⟨*key*⟩ will affect the entire *"body"* of the environment and therefore the inner levels of the list and the `keyans`, `keyans*` and `keyanspic` environments. It is recommended to set this ⟨*key*⟩ per level. In the `enumext*` and `keyans*` environments this ⟨*key*⟩ is executed *"after"* the `listparindent`, `parsep` and `itemindent` ⟨*keys*⟩ within the `minipage` environment in which the *"item content"* is placed. Making modifications to `\setcounter` in these environments using this ⟨*key*⟩ will not have the expected effect.

`after` = {⟨*code*⟩} default: *not used*

Execute {⟨*code*⟩} *"after"* finishing the environment. The {⟨*code*⟩} must be passed between braces.

5.5 Keys for `start`, `series` and `resume`

`start` = {⟨*integer* | *integer expression*⟩} default: *1*

Sets the *start value* of the numbering on the *"current level"*. The {⟨*integer expression*⟩} must be passed between braces, internally is evaluated and pass to the *"counter"* defined by `label` key on the current level, i.e. it is equivalent to enter `start={\dimeval{100*\value{chapter}}}` or `start={100*\value{chapter}}`.

`start*` = {⟨*integer* | *string*⟩} default: *not used*

Sets the *start value* of the numbering on the *"current level"*. Internally ⟨*string*⟩ is converted and passed as value to the *"counter"* defined by `label` key on the current level, i.e. it is equivalent to enter `start*=5`, `start*=E` or `start*=v`.

The *start value* in `enumext` and `keyans` are set in the *second argument* of the `list` environment and *"before"* the execution of the keys `before` and `first`, but in the `enumext*` and `keyans*` it is set much later: `\begin{list}{⟨arg one⟩}{⟨arg two⟩}\setcounter`.

The following ⟨*keys*⟩ are available only for the `enumext` and `enumext*` environments.

`series` = {⟨*series name*⟩} default: *not used*

Stores the *keys* of the *optional argument* of the *"current level"* of the environment in which it is executed in {⟨*series name*⟩} which is used as an *argument* in the `resume` key. The ⟨*keys*⟩ stored in {⟨*series name*⟩} are NOT cumulative and are overwritten if the same {⟨*series name*⟩} is used again at the *"same level"* at which the key was executed.

For security reasons the `series` key will never save in {⟨*series name*⟩} the ⟨*keys*⟩ `series`, `resume`, `resume*`, `reset`, `reset*`, `save-ans`, `save-key`, `start*` and `start`.

`resume` = {⟨*series name*⟩} default: *not used*

Sets the *start value* and *options* for the *"current level"* continuing the numbering and *options* of the *"same level"* as the environment in which the `series={⟨series name⟩}` key was executed, the *start value* will continue numbering according to the last execution of `resume={⟨series name⟩}`. If passed *"without value"* this will only set *start value* continue the numbering of the *"same level"* from the last environment and level in which `series={⟨series name⟩}` or `resume={⟨series name⟩}` is NOT present and if the `save-ans` key is active (on the left) it will continue the numbering from the "last" environment in which it was executed. The *start value* can be overwritten using `start` or `start*` keys.

The `resume` key passed *"without value"* must be exactly *"without value"*, i.e. `resume=` cannot be used and if executed before `resume*` it will affect the *start value*.

`resume*` ⟨*value forbidden*⟩ default: *not used*

Sets the *start value* and *options* for the *"current level"* continuing the numbering and options of the *"same level"* as the last environment and level in which the `series={⟨series name⟩}` or `resume={⟨series name⟩}` keys are NOT present and if the `save-ans` key is active (on the left) it will continue the numbering and options from the "last" environment in which it was executed. The *start value* can be overwritten using `start` or `start*` keys.

When using the key `resume={⟨series name⟩}` or `resume*` you will have hierarchy in the ⟨*keys*⟩ that are stored in {⟨*series name*⟩} or in an internal version of {⟨*series name*⟩} in the case of `resume*`. If you want to *reset* the value of a ⟨*key*⟩ that is already stored in {⟨*series name*⟩} or in an internal version of {⟨*series name*⟩} this must be placed to the *right* of the key `resume={⟨series name⟩}` or `resume*`.

When the `resume*` key is executed consecutively, it does not rewrite the ⟨*keys*⟩ stored in the internal version of {⟨*series name*⟩} and if the environment that precedes it does not have the *optional argument*, it will just continue with the numbering.

5.6 Keys for `reset`

`reset` ⟨*value forbidden*⟩ default: *not used*

©2024–2026 by Pablo González L

Resets the *start value* of the *"counters"* in the enumext and enumext* environments along with the *"internal counters"* used by the resume *without value* and resume* keys at the *"level"* at which it is executed. The *start value* can be overwritten using the start or start* keys.

reset* ⟨*value forbidden*⟩ default: *not used*

Resets the *start value* of the *"counters"* in the enumext and enumext* environments along with the *"internal counters"* used by the resume *without value* and resume* keys at the *"level"* at which it is executed and in the *"levels below"* it in the case of the enumext environment. The *start value* can be overwritten using the start or start* keys.

These keys are intended to be used in cases where the \resetenumext command does not work, e.g. after an unnumbered chapter. It should preferably be set *only* on the *first level*, although it is available for all levels.

5.6.1 The command \resetenumext

\resetenumext
\resetenumext[⟨1⟩]{⟨*some counter*⟩}
\resetenumext[⟨2⟩]{⟨*some counter*⟩}
\resetenumext[⟨3⟩]{⟨*some counter*⟩}
\resetenumext[⟨4⟩]{⟨*some counter*⟩}
\resetenumext[⟨*⟩]{⟨*some counter*⟩}
\resetenumext*{⟨*some counter*⟩}

The \resetenumext command *"resets"* the *start value* of the *"counters"* for the enumext and enumext* environments along with the *"internal counters"* used by the keys resume *without value* and resume* according to the value of {⟨*some counter*⟩}. For example \resetenumext{chapter} will *"reset"* the numbering of *"all levels"* of the enumext environment for each execution of a *"numbered"* chapter.

The *optional argument* of the form [1], [2], [3], [4] *"reset"* the values for levels 1, 2, 3 and 4 of the enumext environment, the form [*] *"reset"* the values for the enumext* environment. If is run *without* the *optional argument*, it will *"reset"* the values for *"all levels"* of the enumext environment.

The *starred argument* '*' will *"reset"* the values for *"all levels"* of the enumext and enumext* environments.

5.7 Keys for multicols

columns = {⟨*integer*⟩} default: 1

Set the *number of columns* to be used by the multicols environment within the environments enumext and keyans. The value must be a positive integer less than or equal to 10. In the enumext* and keyans* environments they correspond to the default number of columns (without joining) and internally adjust the value of \itemwidth.

columns-sep = {⟨*rigid length*⟩} default: *by level*

Set the *space between* columns used by the multicols environment within the environments enumext and keyans. Internally sets the value of \columnsep, by default its value is equal to the sum of the values set in the keys labelwidth and labelsep of the current level. In the enumext* and keyans* environments they correspond to the *space between* columns (without joining) and internally adjust the value of \itemwidth.

5.8 Keys for minipage

mini-env = {⟨*rigid length*⟩} default: *not used*

Sets the *width* of the minipage environment on the *"right side"*. This value added to the value set by the mini-sep key to determines the *width* of the minipage environment on the *"left side"*, taking \linewidth as the maximum reference value.

mini-sep = {⟨*rigid length*⟩} default: 0.3333*em*

Sets the *space between* the minipage environment on the *"left side"* and the minipage environment on the *"right side"*. This separation is applied together with \hfill.

5.8.1 The command \miniright

\miniright
\begin{enumext}[mini-env={⟨*rigid length*⟩}] ⟨*items before*⟩ \item \miniright ⟨*content*⟩ \end{enumext}
\begin{enumext}[mini-env={⟨*rigid length*⟩}] ⟨*items before*⟩ \item \miniright*⟨*content*⟩ \end{enumext}

The \miniright command close the minipage environment on the *"left side"* and opens the minipage environment on the *"right side"* by starting it with the \centering command. It must be placed *"after"* the last \item of the current environment and *"before"* starting the material to be placed on the *"right side"*.

The *starred argument* '*' inhibits the use of \centering command i.e. the usual LaTeX justification is maintained in the minipage on the *"right side"*.

5.8.2 The key mini-right

In the *horizontal list environments* enumext* and keyans* it is not possible to use the \miniright command and the mini-right key must be used instead.

mini-right = {⟨*content*⟩} default: *not used*

©2024–2026 by Pablo González L

Set the *content* for the drawing or tabular to be placed in the minipage environment on the *"right side"* by starting it with \centering. The {⟨*content*⟩} must be passed between braces.

mini-right* = {⟨*content*⟩} default: *not used*

Same as above, but *without* starting with \centering.

6 The storage system

The entire mechanism for *"storing content"* it is activated according to save-ans key on the *"first level"* of enumext or enumext* environments and it is ignored if they are established when they are nested inside each other. Only when this ⟨*key*⟩ is *"active"* the \anskey command and the environments anskey*, keyans, keyans* and keyanspic are available.

```
\begin{enumext}[save-ans={⟨store name⟩}]
  \item Text \anskey{answer}
  \item Text
    \begin{keyans}
          ...
    \end{keyans}
\end{enumext}
```

```
\begin{enumext}[save-ans={⟨store name⟩}]
  \item Text \anskey{answer}
  \item Text
    \begin{keyanspic}
          ...
    \end{keyanspic}
\end{enumext}
```

By executing the key save-ans={⟨*store name*⟩} the entire *"structure"* of the environment (excluding the *first level*) including the *optional argument* passed to the inner levels or the environment nested in it, along with the ⟨*content*⟩ passed to \anskey or anskey*, the current ⟨*labels*⟩ for \item* and \anspic* in the environments keyans, keyans* and keyanspic will be *"stored"* in a *sequence* {⟨*store name*⟩} and at the same time will be *"stored"* (without the *"structure"* or *optional argument*) in a *prop list* {⟨*store name*⟩}.

For security reasons the *optional argument* of the inner levels or the nested environment are *filtered* by excluding all ⟨*keys*⟩ related to the *"storage system"* (§6.1) along with the keys mini-env, mini-sep, mini-right, mini-right*, series, resume and resume* when storing in *sequence* {⟨*store name*⟩} set by save-ans key.

6.1 Keys for storage system

The only ⟨*keys*⟩ available for all levels of the enumext environment and the enumext* environment are no-store and save-key, the rest of the ⟨*keys*⟩ described in this section must be passed directly in the *optional argument* of the *"first level"* of the environment in which the key save-ans is executed. The key save-ans should NOT be passed with the command \setenumext.

save-ans = {⟨*store name*⟩} default: *not set*

Sets the *name* of the *sequence* and *prop list* in which the {⟨*contents*⟩} will be *"stored"* by \anskey and anskey* in enumext and enumext* environments and the current ⟨*labels*⟩ for \item* and \anspic* in the environments keyans, keyans* and keyanspic. If the *sequence* or *prop list* {⟨*store name*⟩} does not exist, it will be created globally and will not be *overwritten* if the key is used again.

save-key = {⟨*key list*⟩} default: *not set*

This key *overrides* the default *"stored keys"* of the *optional argument* of the inner levels or nested environment that will be passed to the *sequence* {⟨*store name*⟩} set by save-ans key. The ⟨*key list*⟩ passed to this key ignores any ⟨*keys*⟩ in the *"stored structure"* and must be passed between braces. For example, if executed at a second level:

```
\begin{enumext}[save-ans={⟨store name⟩}]
  \item Text \anskey{answer}
  \item Text
    \begin{enumext}[nosep, columns=2, save-key={columns=3}]
          ...
    \end{enumext}
\end{enumext}
```

The *"stored keys"* by default in the *sequence* {⟨*store name*⟩} would be nosep and columns=2, but using the key save-key={columns=3} will overwrite and the *"stored key"* in the *sequence* {⟨*store name*⟩} are only columns=3 ignoring all the others.

save-sep = {⟨*text symbol*⟩} default: *{, }*

Sets the *text symbol* that will separate the current ⟨*label*⟩ to the *optional argument* passed to the \item* and \anspic* in the environments keyans, keyans* and keyanspic and storing them in the *sequence* and *prop list* {⟨*store name*⟩} set by save-ans key. The {⟨*text symbol*⟩} must always be passed between braces, whitespace '␣' is preserved within the braces and only affects the *"stored content"* and not what is displayed when using the show-ans or show-pos keys.

no-store ⟨*value forbidden*⟩ default: *not used*

This is a *"switch-key"* that does not receive an argument and disables the *"storing content"* in the *sequence* and *prop list* {⟨*store name*⟩} set by save-ans key at the entire level or a nested environment in which it runs. This key is intended for use in internal levels or nested enumext or enumext* environments in which you want

©2024–2026 by Pablo González L

to use enumext or enumext* but *"without"* using the \anskey command or use anskey* environment and *"without"* interfering with the check-ans key.

6.1.1 Keys for label and ref

save-ref = {⟨*true* | *false*⟩} default: *false*

Activates the *"internal label and ref"* mechanism for referencing *"stored content"* in *prop list* {⟨*store name*⟩} set by save-ans key. To reference the location of the *"stored content"* within the environment you must use \ref{⟨*store name* : *position*⟩}, where ⟨*position*⟩ corresponds to the position occupied by the *"stored content"* in the *prop list* {⟨*store name*⟩} returned by the show-pos key. For example \ref{test:4} will return 3.(b) which corresponds to the location of the *"stored content"* at position 4 in *prop list* test within the environment in which the key save-ans=test was set.

mark-ref = {⟨*symbol*⟩} default: *\textreferencemark*

Sets the *symbol* that will be displayed by the \printkeyans command only if the hyperref package is detected and the save-ref key are active. This *"symbol"* is used as a *"link"* between the environment in which the save-ans key was used and the place where the command is executed.

6.1.2 Keys for wrap and marks

The enumext package provides a set of ⟨*keys*⟩ to set and manipulate *"symbol marks"* associated with *"answers"* and how they are displayed and stored in the *sequence* and *prop list.*

The ⟨*keys*⟩ available for the \anskey command and the anskey* environment can be passed *"only"* in the *optional argument* in the *"first level"* of the enumext or enumext* environment.

The ⟨*keys*⟩ available for the keyans and keyans* environments can be passed locally in the *optional argument*, at the *"first level"* of the enumext or enumext* environment or via the \setenumext command with one minor difference, when ⟨*keys*⟩ are passed through the *"first level"* of the enumext or enumext* environment they are set in *"both"* environments, but when they are passed using the \setenumext command they are set *"individually"* in each environment.

show-ans = {⟨*true* | *false*⟩} default: *false*

Display the *symbol* set by the mark-ans key to the left of the *mandatory argument* ⟨*content*⟩ passed to the \anskey command and ⟨*body*⟩ for the anskey* environment using the wrap-ans key if set. For \item* and \anspic* the keyans, keyans* and keyanspic environments it will display the *symbol* set by the mark-ans* key to the left of the current ⟨*label*⟩ and *optional argument.* If the *optional argument* is present in \item* or \anspic* it will be shown using wrap-opt key.

Keys for \anskey and anskey*

mark-ans = {⟨*symbol*⟩} default: *\textasteriskcentered*

Sets the *symbol* to be displayed in the left margin for \anskey command and anskey* environment when using the key show-ans. The *"symbol"* is placed in a box of width equal to the value of labelwidth at the current level, separated by the value of the key mark-sep and aligned by the value of the key mark-pos. This key is not affected by the keys font or wrap-label so if you want to apply *styling* you have to do it directly, for example: mark-ans={\textcolor{red}{\textbf{\textasteriskcentered}}}.

mark-pos = {⟨*left* | *right* | *center*⟩} default: *left*

Sets the *aligned* of the *"symbol"* defined by mark-ans key for \anskey command and anskey* environment. The *"symbol"* is aligned in a box with the same dimensions of the label box defined by labelwidth key on the current level and separated by the value of the mark-sep key.

mark-sep = {⟨*rigid length*⟩} default: *labelsep*

Sets the *horizontal space* between the box containing the *"symbol"* defined by mark-ans key and the *mandatory argument* ⟨*content*⟩ passed to the \anskey command and the ⟨*body*⟩ in anskey* environment.

wrap-ans = {⟨*code* {#1} *more code*⟩} default: *\fbox+\parbox{#1}*

Wraps the *mandatory argument* ⟨*content*⟩ passed to the \anskey and the ⟨*body*⟩ in anskey* environment referenced by {#1} when using the show-ans or show-pos keys. The {⟨*code*⟩} must be passed between braces and only affects how the ⟨*content*⟩ or ⟨*body*⟩ is displayed and NOT the *"stored content"* in the *sequence* and *prop list* {⟨*store name*⟩} set by save-ans key. If this key is passed using \setenumext it is necessary to use double '{##1}'.

Keys for keyans, keyans* and keyanspic

mark-ans* = {⟨*symbol*⟩} default: *\textasteriskcentered*

Sets the *symbol* to be displayed in the left margin for \item* and \anspic* for the keyans, keyans* and keyanspic environments when using the key show-ans. The *"symbol"* is placed in a box of width equal to the value of labelwidth of the environment in which it is executed, separated by the value of the key mark-sep* and aligned by the value of the key mark-pos*. This key is not affected by the keys font or wrap-label so if you want to apply *styling* you have to do it directly, for example: mark-ans*={\textcolor{red}{\textbf{\textasteriskcentered}}}.

©2024–2026 by Pablo González L

mark-pos* = {⟨left | right | center⟩} default: *left*

Sets the *aligned* of the *"symbol"* defined by mark-ans* key for the keyans, keyans* and keyanspic environments. The *"symbol"* is aligned in a box with the same dimensions of the label box defined by labelwidth key of the environment in which it is executed and separated by the value of the mark-sep* key.

mark-sep* = {⟨rigid length⟩} default: *labelsep*

Sets the *horizontal space* between the box containing the *"symbol"* defined by mark-ans* key and the current ⟨label⟩ for \item* and \anspic* in the keyans, keyans* and keyanspic environments.

wrap-ans* = {⟨code {#1} more code⟩} default: *not used*

Wraps the *current* ⟨label⟩ when using the show-ans key for \item* and \anspic* referenced by {#1} in the keyans, keyans* and keyanspic environments after executing the align and font keys. The {⟨code⟩} must be passed between braces and *only* affects how the ⟨label⟩ is displayed and NOT the *"stored label"* in the *sequence* and *prop list* {⟨store name⟩} set by save-ans key. This key overwrites the key wrap-label and if is passed using \setenumext it is necessary to use double '{##1}'. For example, if you want the ⟨label⟩ to be displayed in red when using show-ans you just set wrap-ans*={\textcolor{red}{#1}}.

wrap-opt = {⟨code {#1} more code⟩} default: *[[#1]]*

Wraps the *optional argument* passed to the \item* and \anspic* referenced by {#1} in the keyans, keyans* and keyanspic environments when using the show-ans or show-pos keys. The {⟨code⟩} must be passed between braces and only affects the current *optional argument* and NOT the *"stored content"* in the *sequence* and *prop list* {⟨store name⟩} set by save-ans key. If this key is passed using \setenumext it is necessary to use double '{##1}'.

6.1.3 Keys for debug and checking

show-pos = {⟨true | false⟩} default: *false*

Displays the *position* occupied by the *"stored content"* by \anskey, anskey*, \item* and \anspic* in the *prop list* {⟨store name⟩} set by save-ans key. This position is used by the \getkeyans command and by the \ref command if the save-ref key is active.

check-ans = {⟨true | false⟩} default: *false*

Enables the *checking answer* mechanism displaying an appropriate message on the terminal. This key works under the logic that each \item or \item* that does not open an inner level or nested environment contains *"only one answer"* or *"only one execution"* of the \anskey or anskey*. It is intended to be used in conjunction with the no-store key.

6.2 The command \anskey

\anskey \anskey[⟨keys⟩]{⟨content⟩}

The command \anskey takes a mandatory non empty argument {⟨content⟩} and *"stores"* it in the *sequence* and *prop list* {⟨store name⟩} set by save-ans key. By design the command cannot be nested or passed *verbatim material* in the argument and it is assumed that each *numbered* \item or \item* within the environment in which it is active it has a *"single execution"* of \anskey unless \item or \item* open a nested level or use the no-store key.

If save-ref key are active and the hyperref[8] package is detected, \hyperlink and \hypertarget will be used, otherwise the usual *"label and ref"* system provided by LaTeX will be used.

The \anskey command is available for all levels of the enumext environment and the enumext* environment, but is disabled for the keyans, keyans* and keyanspic environments.

6.2.1 Keys for \anskey

By default the *mandatory argument* ⟨content⟩ passed to \anskey when *"storing"* in the *sequence* {⟨store name⟩} has the form \item ⟨content⟩, the following ⟨keys⟩ allow modifying the way in which it is *"stored"* in the *sequence*.

break-col ⟨value forbidden⟩ default: *not used*

Stores {⟨content⟩} in the *sequence* {⟨store name⟩} of the form \columnbreak \item ⟨content⟩.

item-join = {⟨columns⟩} default: *not set*

Set the *number of columns* to be used for \item(⟨columns⟩) and stores {⟨content⟩} in the *sequence* {⟨store name⟩} of the form \item(⟨columns⟩) ⟨content⟩.

item-star ⟨value forbidden⟩ default: *not used*

Stores {⟨content⟩} in the *sequence* {⟨store name⟩} of the form \item* ⟨content⟩.

item-sym* = {⟨symbol⟩} default: *not set*

Sets the *symbol* for \item* when using the key item-star and stores {⟨content⟩} in the *sequence* {⟨store name⟩} of the form \item*[⟨symbol⟩] ⟨content⟩. The *symbol* can be in text or math mode, for example item-sym*={$\ast$} stores \item*[$\ast$] ⟨content⟩.

©2024–2026 by Pablo González L

item-pos* = {⟨*rigid length*⟩} default: *not set*

Sets the *offset* for \item* when using the keys item-star and item-sym* and stores {⟨*content*⟩} in the *sequence* {⟨*store name*⟩} of the form \item*[⟨*symbol*⟩][⟨*offset*⟩] ⟨*content*⟩.

Example

```
\begin{enumext}[save-ans=test,show-ans=true]
  \item* Text containing our instructions or questions. \anskey{⟨first answer⟩}
  \item Text containing our instructions or questions.
    \begin{enumext}
      \item Question.\anskey{⟨second answer⟩}
    \end{enumext}
  \item Text containing our instructions or questions. \anskey{⟨third answer⟩}
  \item Text containing our instructions or questions. \anskey{⟨fourth answer⟩}
\end{enumext}
```

⋆ 1. Text containing our instructions or questions.
∗ first answer
2. Text containing our instructions or questions.
(a) Question.
∗ second answer
3. Text containing our instructions or questions.
∗ third answer
4. Text containing our instructions or questions.
∗ fourth answer

6.3 The environment anskey*

anskey* \begin{anskey*}[⟨*key = val*⟩] ⟨*body content*⟩ \end{anskey*}

The environment anskey* takes a mandatory {⟨*body content*⟩} and *"stores it"* in the *sequence* and *prop list* {⟨*store name*⟩} set by save-ans key. If save-ref key are active and the hyperref[8] package is detected \hyperlink and \hypertarget will be used, otherwise the usual *"label and ref"* system provided by LaTeX will be used.

By design the environment cannot be nested but full supports *"verbatim material"* in the ⟨*body*⟩ and it is assumed that *"each numbered"* \item or \item* within the environment in which it is active it has a *"single execution"* unless \item or \item* open a nested level or use the no-store key.

The anskey* environment is implemented using the new *"collect code"* c-type argument part of LaTeX release 2025-06-01[13]. \begin{anskey*} and \end{anskey*} must be in different lines and should not appear within verbatim environments or commands. All ⟨*keys*⟩ must be passed separated by commas and "without separation" of the start of the environment.

Comments '%' or *any character* after \begin{anskey*} or [⟨*key = val*⟩] on the same line are NOT supported, LaTeX will return an "error" message if this happens. In a similar way comments '%' or *any character* after \end{anskey*} on the same line LaTeX will return a "warning" message.

6.3.1 Keys for anskey*

The anskey* environment uses the same ⟨*keys*⟩ as the \anskey command next to the ⟨*keys*⟩ write-env, overwrite and force-eol. The environment is available for all levels of the enumext environment and the enumext* environment, but it is disabled for the keyans, keyans* and keyanspic environments.

write-env = {⟨*file.ext*⟩} default: *not used*

Sets the *name* of the ⟨*external file*⟩ in which the ⟨*contents*⟩ of the environment will be written. The ⟨*file.ext*⟩ will be created in the working directory, relative or absolute paths are not supported. If ⟨*file.ext*⟩ does not exist, it will be created or overwritten if the overwrite key is used.

overwrite = {⟨*true* | *false*⟩} default: *false*

Sets whether the ⟨*file.ext*⟩ generated by write-env from the anskey* environment will be rewritten.

force-eol = {⟨*true* | *false*⟩} default: *false*

Sets if the *last end of line* for the ⟨*stored content*⟩ is hidden or not. This key is necessary only if the last line is the closing of some environment defined by the fancyvrb package as \end{Verbatim} or another environment that does not support a comments '%' after closing \end{Verbatim}%.

Example

```
\begin{enumext}[save-ans=test,show-pos=true,start=5]
  \item* Text containing our instructions or questions.
    \begin{anskey*}[item-star]
      ⟨first answer⟩
    \end{anskey*}

  \item Text containing our instructions or questions.
    \begin{enumext}
```

©2024–2026 by Pablo González L

```
      \item Question.
        \begin{anskey*}
          ⟨second answer⟩
        \end{anskey*}
    \end{enumext}

  \item Text containing our instructions or questions.
    \begin{anskey*}
      ⟨third answer⟩
    \end{anskey*}

  \item Text containing our instructions or questions.
    \begin{anskey*}
      ⟨fourth answer⟩
    \end{anskey*}
\end{enumext}
```

⋆ 5. Text containing our instructions or questions.

[5] First answer with verbatim

6. Text containing our instructions or questions.

   (a) Question.

   [6] second answer

7. Text containing our instructions or questions.

[7] third answer

8. Text containing our instructions or questions.

[8] fourth answer

6.4 The environments keyans and keyans*

keyans `\begin{keyans}[⟨key = val⟩] \item \item[⟨custom⟩] \item* \item*[⟨content⟩] \end{keyans}`
keyans* `\begin{keyans*}[⟨key = val⟩] \item \item[⟨custom⟩] \item* \item*[⟨content⟩] \end{keyans*}`

The keyans and keyans* environments are *"enumerated list"* environments designed for *"multiple choice"* questions activated by the save-ans key.

This environments can NOT be nested and must always be at the *"first level"* of the enumext environment, the commands \item and \item[⟨custom⟩] work in the usual and the command \item(⟨columns⟩) is available for the keyans* environment.

The behavior of \item* in keyans and keyans* environments is NOT the same as in the enumext or enumext* environments.

```
\begin{enumext}[save-ans=test]
  \item ⟨item content⟩
    \begin{keyans}[⟨key = val⟩]
      \item ⟨item content⟩
      \item [⟨custom⟩] ⟨item content⟩
      \item* ⟨item content⟩
      \item*[⟨content⟩] ⟨item content⟩
    \end{keyans}
\end{enumext}
```

```
\begin{enumext}[save-ans=test]
  \item ⟨item content⟩
    \begin{keyans*}[⟨key = val⟩]
      \item ⟨item content⟩
      \item [⟨custom⟩] ⟨item content⟩
      \item* ⟨item content⟩
      \item*[⟨content⟩] ⟨item content⟩
    \end{keyans*}
\end{enumext}
```

The ⟨keys⟩ set in the *optional argument* of the environment are the same (almost) as those of the enumext and enumext* environments and have *higher precedence* than those set by \setenumext[⟨keyans⟩]{⟨key = val⟩} or \setenumext[⟨keyans*⟩]{⟨key = val⟩}. If the *optional argument* is not passed or the ⟨keys⟩ are not set by \setenumext, the default values will be the same as the *"second level"* of the enumext environment with the difference in the ⟨label⟩ which will be set to label=\Alph*).

The keys mark-ans*, mark-pos*, mark-sep*, save-sep, wrap-opt, wrap-ans*, show-ans and show-pos are available for both environments.

6.4.1 The \item* in keyans and keyans*

\item* `\item*`
`\item*[⟨content⟩]`

The \item* and \item*[⟨content⟩] command *"store"* the current ⟨label⟩ set by label key next to the *optional argument* ⟨content⟩ in *sequence* and *prop list* {⟨store name⟩} set by save-ans key in the *"first level"* of the enumext or enumext* environments.

The *starred argument* '*' cannot be separated by spaces '␣' from the command, i.e. \item* and the *optional argument* does "NOT" support *verbatim content.* By design it is assumed that the \item* will only appear *"once"* within the environment.

Example

```
\begin{enumext}[save-ans=test,columns=2,show-ans=true]
  \item Text containing a question.
```

```
    \begin{keyans*}[nosep,columns=2]
      \item Choice
      \item* Correct choice
      \item Choice
      \item Choice
      \item Choice
    \end{keyans*}

  \item Text containing a question and image.

    \begin{keyans}[nosep,mini-env={0.4\linewidth}]
      \item Choice
      \item Choice
      \item Choice
      \item Choice
      \item*[⟨note⟩] Correct choice
      \miniright
      \includegraphics[scale=0.25]{example-image-a}
      Some text
    \end{keyans}
\end{enumext}
```

1. Text containing a question.
   A) Choice
   ∗ B) Correct choice
   C) Choice
   D) Choice
   E) Choice

2. Text containing a question and image.
   A) Choice
   B) Choice
   C) Choice
   D) Choice
   ∗ E) [note] Correct choice



Some text

6.5 The environment keyanspic

keyanspic `\begin{keyanspic}[⟨key = val⟩] \anspic*[⟨content⟩]{⟨drawing or tabular⟩} \end{keyanspic}`

The keyanspic environment is an *"enumerated list"* environment activated by the save-ans key that has the same configuration for *"spacing"* and ⟨*label*⟩ as the keyans environment that uses the \anspic command instead of \item. It is intended for placing *drawings or tabular* with ⟨*label*⟩ centered *above* or *below* in a *single line* or *upper and lower* layout style.

When the keyanspic environment is used *without keys* the ⟨*labels*⟩ are centered *below* the *drawings or tabular* in a *single line* layout style.

A representation of the output can be seen in the figure 6.




Figure 6: Representation of the keyanspic environment with layout-sty={⟨3, 2⟩} in enumext.

This environment cannot be nested and must *always* be at the *"first level"* of the enumext environment, the \item command is disabled and ⟨*keys*⟩ cannot be set using \setenumext.

6.5.1 Keys for keyanspic

label-pos = {⟨*above* | *below*⟩} default: *below*

Set the *position* of ⟨*label*⟩ to be centered "above" or "below" *drawings* or *tabular* when the \anspic command is executed.

label-sep = {⟨*rubber length* | *rigid length*⟩} default: *internal adjustment*

Set the *vertical spacing* between the ⟨*label*⟩ centered "above" or "below" and *drawings* or *tabular* when running the \anspic command.

layout-sty = {⟨*n° upper* , *n° lower*⟩} default: *not set*

Set the *number* of *drawings* or *tabular* that will be distributed "upper" and "lower" within the environment when executing the \anspic command. The value must be passed in braces and if not set or the ⟨*n° lower*⟩ is omitted the *drawings* or *tabular* will be put on a *single line*.

layout-sep = {⟨*rubber length* | *rigid length*⟩} default: *adjusted parsep from keyans*

©2024–2026 by Pablo González L

Set the *vertical separation* between the number of *drawings* or *tabular* placed at the "upper" and "lower" within the environment when executing the `\anspic` command. Internally adjusts the `parsep` value taken from the `keyans` environment.

`layout-top` = {⟨*rubber length* | *rigid length*⟩} default: *adjusted topsep from keyans*

Set the *vertical space* added to both the top and bottom of the environment. Internally adjust the value of `topsep` taken from `keyans` environment.

The keys `mark-ans*`, `mark-pos*`, `mark-sep*`, `save-sep`, `wrap-opt`, `wrap-ans*`, `show-ans` and `show-pos` are available for this environment.

6.5.2 The command `\anspic`

`\anspic` `\anspic`{⟨*drawing or tabular*⟩}
`\anspic*`[⟨*content*⟩]{⟨*drawing or tabular*⟩}

The `\anspic` command takes three arguments, the *starred argument* '`*`' store the current ⟨*label*⟩ next to the *optional argument* ⟨*content*⟩ in *sequence* and *prop list* {⟨*store name*⟩} set by `save-ans` key.

The *starred argument* '`*`' cannot be separated by spaces '␣' from the command, i.e. `\anspic*` and the *optional argument* does "NOT" support *verbatim content.* By design it is assumed that the *starred argument* '`*`' will only appear *"once"* within the environment.

Example

```
\begin{enumext}[save-ans=test,show-ans=true,nosep]
  \item Question with images and labels below.

    \begin{keyanspic}[layout-sty={3,2}]
      \anspic{\includegraphics[scale=0.15]{example-image-a}}
      \anspic{\includegraphics[scale=0.15]{example-image-b}}
      \anspic{\includegraphics[scale=0.15]{example-image-a}}
      \anspic{\includegraphics[scale=0.15]{example-image-a}}
      \anspic*[note]{\includegraphics[scale=0.15]{example-image-a}}
    \end{keyanspic}

  \item Question with images and labels above.

    \begin{keyanspic}[label-pos=above, layout-sty={3,2},layout-sep=0.25cm]
      \anspic{\includegraphics[scale=0.15]{example-image-a}}
      \anspic{\includegraphics[scale=0.15]{example-image-b}}
      \anspic{\includegraphics[scale=0.15]{example-image-a}}
      \anspic{\includegraphics[scale=0.15]{example-image-a}}
      \anspic*[note]{\includegraphics[scale=0.15]{example-image-a}}
    \end{keyanspic}

  \item Question with images and labels below on a single line.

    \begin{keyanspic}
      \anspic{\includegraphics[scale=0.15]{example-image-a}}
      \anspic{\includegraphics[scale=0.15]{example-image-b}}
      \anspic{\includegraphics[scale=0.15]{example-image-a}}
      \anspic{\includegraphics[scale=0.15]{example-image-a}}
      \anspic*[note]{\includegraphics[scale=0.15]{example-image-a}}
    \end{keyanspic}

\end{enumext}
```

1. Question with images and labels below.



A)



B)



C)




D)



∗ E) [note]

2. Question with images and labels above.

A) B) C)



D) ∗ E) [note]



3. Question with images and labels below on a single line.



A) B) C) D) ∗ E) [note]

Remember to pass the `alt={`*description*`}` key to the `\includegraphics` command when creating a *tagged* PDF.

6.6 Printing stored content

6.6.1 The command `\getkeyans`

`\getkeyans` `\getkeyans{`*store name* : *position*`}`

The command `\getkeyans` prints the *"stored content"* in *prop list* `{`*store name*`}` defined by `save-ans` key in the ⟨*position*⟩ returned by the `show-pos` key.

The *"stored content"* can only be accessed *after* it is stored, if `{`*store name*`}` does not exist the command will return an error.

The form taken by the argument `{`*store name* : *position*`}` is the same as that used to generate the *"internal label and ref"* system when `save-ref` key are active, so to refer to a *"stored content"*. For example `\getkeyans{test:4}` will return the *"stored content"* at position `4` of the environment in which the key `save-ans=test` was set.

6.6.2 The command `\foreachkeyans`

`\foreachkeyans` `\foreachkeyans[`*key* = *val*`]{`*store name*`}`

The command `\foreachkeyans` goes through and executes the command `\getkeyans` on the contents in *prop list* `{`*store name*`}`. If you pass without options run `\getkeyans` on all contents in *prop list* `{`*store name*`}`.

Options for command

`sep` = `{`*code*`}` default: *{;}*

Establishes the *separation* between *"each"* `{`*content*`}` stored in *prop list* `{`*store name*`}`. For example, you can use `sep={\\[10pt]}` for vertical separation of stored contents.

`step` = `{`*integer*`}` default: *1*

Sets the *step* (increment) applied to the value set by key `start` for *"each"* `{`*content*`}` stored in *prop list* `{`*store name*`}`. The value must be a ⟨*positive integer*⟩.

`start` = `{`*integer*`}` default: *1*

Sets the *position* of the *prop list* `{`*store name*`}` from which execution will start. The value must be a ⟨*positive integer*⟩.

`stop` = `{`*integer*`}` default: `0`

Sets the *position* of the *prop list* `{`*store name*`}` from which execution will finish. The value must be a ⟨*positive integer*⟩.

`before` = `{`*code*`}` default: *empty*

Sets the `{`*code*`}` that will be executed ⟨*before*⟩ each `{`*content*`}` stored in *prop list* `{`*store name*`}`. The `{`*code*`}` must be passed between braces.

`after` = `{`*code*`}` default: *empty*

Sets the `{`*code*`}` that will be executed ⟨*after*⟩ each `{`*content*`}` stored in *prop list* `{`*store name*`}`. The `{`*code*`}` must be passed between braces.

`wrapper` = `{`*code* `{#1}` *more code*`}` default: *empty*

Wraps the `{`*content*`}` stored in *prop list* `{`*store name*`}` referenced by `{#1}`. The `{`*code*`}` must be passed between braces. For example `\foreachkeyans[wrapper={\makebox[1em][l]{#1}}]{`*store name*`}`.

©2024–2026 by Pablo González L

6.6.3 The command \printkeyans

\printkeyans

\printkeyans{⟨store name⟩}
\printkeyans[⟨keys⟩]{⟨store name⟩}
\printkeyans*[⟨keys⟩]{⟨store name⟩}

The command \printkeyans prints *"all stored content"* in *sequence* {⟨store name⟩} defined by save-ans key placing this inside the enumext or enumext* environment if the *starred argument* '*' is used.

The *"stored content"* can only be accessed *after* it is stored in the *sequence*, if {⟨store name⟩} does not exist the command will return an error.

The *optional argument* allows managing the ⟨keys⟩ in the *"first level"* of the environment in which the *"stored content"* of the *sequence* {⟨store name⟩} will be printed, if the *starred argument* '*' is used it will be enumext* otherwise enumext.

The default values for the *"first level"* are the same as the default values for the enumext and enumext* environments along with the keys nosep,first=\small,font=\small and columns=2. For the inner levels of the environment enumext saved in the *sequence* {⟨store name⟩} the default values are the same as those established for the second, third and fourth levels plus the keys nosep,first=\small,font=\small. If the environment enumext* is saved within the *sequence* {⟨store name⟩} it will have the same default values plus the keys nosep,first=\small, font=\small.

Since the command encapsulates by default the enumext environment or the enumext* environment, some considerations must be taken into account:

- If \printkeyans*{⟨store name⟩} is executed and the *sequence* {⟨store name⟩} already contains any enumext* environment an error will be returned, since nesting is not possible.
- If \printkeyans*{⟨store name⟩} is executed and the *sequence* {⟨store name⟩} contains any enumext environments, they will start with the ⟨keys⟩ set for the first level unless they are set in the *optional argument* or save-key is used to modify it.
- If \printkeyans{⟨store name⟩} is executed and the *sequence* {⟨store name⟩} contains any environment enumext*, they will start with the ⟨keys⟩ set by default unless they are set in the *optional argument* or save-key is used to modify it.

The default values for the *"first level"* of \printkeyans commands and \printkeyans* are established using \setenumext[⟨print , 1⟩]{⟨keys⟩} and \setenumext[⟨print*⟩]{⟨keys⟩}.

To set the ⟨keys⟩ for the environment enumext "saved" in the *sequence* {⟨store name⟩}, use \setenumext[⟨print , level⟩]{⟨keys⟩}, and to set the ⟨keys⟩ for the environment enumext* "saved" in the *sequence* {⟨store name⟩}, use \setenumext[⟨print , *⟩]{⟨keys⟩}.

Example

```
\begin{enumext}[save-ans=sample,columns=1,show-pos=true,nosep,save-ref=true]
  \item Factor $3x+3y+3z$. \anskey{$3(x+y+z)$}
  \item True False

    \begin{enumext}[nosep]
      \item \LaTeX2e\ is cool? \anskey{Very True!}
    \end{enumext}

  \item Related to Linux

    \begin{enumext}[nosep]
      \item You use Linux? \anskey{Yes}
      \item Rate the following package and class
        \begin{enumext}[nosep]
          \item \texttt{xsim} \anskey{very good}
          \item \texttt{exsheets} \anskey{obsolete}
        \end{enumext}
    \end{enumext}
\end{enumext}

The answer to \ref{sample:4} is \getkeyans{sample:4} and the answers to
all the worksheets are as follows:

\printkeyans{sample}
```

1. Factor $3x + 3y + 3z$.

[1] $3(x + y + z)$

©2024–2026 by Pablo González L

2. True False
   (a) LaTeX2e is cool?
   [2] Very True!

3. Related to Linux
   (a) You use Linux?
   [3] Yes
   (b) Rate the following package and class
      i. `xsim`
      [4] very good
      ii. `exsheets`
      [5] obsolete

The answer to 3.(b).i is very good and the answers to all the worksheets are as follows:

1. $3(x+y+z)$ ※
2. (a) Very True! ※
3. (a) Yes ※
   (b) i. very good ※
   ii. obsolete ※

7 Full examples

Some adapted questions taken from TeX-SX are included as an example. The source files of the examples can be compiled with the excellent arara[1] tool.

Example 1

Adapted from the response given by Enrico Gregorio in Squares for answer choice options and perfect alignment to mathematical answers. Source file.

1. La velocità di $1{,}00 \times 10^2$ m/s espressa in km/h è:
   A 36 km/h.
   B 360 km/h.
   C $27{,}8$ km/h.
   D $3{,}60 \times 10^8$ km/h.

2. In fisica nucleare si usa l'angstrom (simbolo: $1\,\text{Å} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1\,\text{fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?
   A $1\,\text{Å} = 1 \times 10^{5}$ fm.
   B $1\,\text{Å} = 1 \times 10^{-5}$ fm.
   C $1\,\text{Å} = 1 \times 10^{-15}$ fm.
   D $1\,\text{Å} = 1 \times 10^{3}$ fm.

3. La velocità di $1{,}00 \times 10^2$ m/s espressa in km/h è:
   A 36 km/h.
   B 360 km/h.
   C $27{,}8$ km/h.
   D $3{,}60 \times 10^8$ km/h.

4. In fisica nucleare si usa l'angstrom (simbolo: $1\,\text{Å} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1\,\text{fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?
   A $1\,\text{Å} = 1 \times 10^{5}$ fm.
   B $1\,\text{Å} = 1 \times 10^{-5}$ fm.
   C $1\,\text{Å} = 1 \times 10^{-15}$ fm.
   D $1\,\text{Å} = 1 \times 10^{3}$ fm.

1. B
2. A
3. B
4. A

Example 2

Adapted from the response given by Florent Rougon in Multiple choice questions with proposed answers in random order — addition of automatic correction (cross mark). Source file.

1. La velocità di $1{,}00 \times 10^2$ m/s espressa in km/h è:
   A 36 km/h.
   ✓ B 360 km/h.
   C $27{,}8$ km/h.
   D $3{,}60 \times 10^8$ km/h.

2. In fisica nucleare si usa l'angstrom (simbolo: $1\,\text{Å} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1\,\text{fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?
   ✓ A $1\,\text{Å} = 1 \times 10^{5}$ fm.
   B $1\,\text{Å} = 1 \times 10^{-5}$ fm.
   C $1\,\text{Å} = 1 \times 10^{-15}$ fm.
   D $1\,\text{Å} = 1 \times 10^{3}$ fm.

3. La velocità di $1{,}00 \times 10^2$ m/s espressa in km/h è:
   A 36 km/h.
   ✓ B 360 km/h.
   C $27{,}8$ km/h.
   D $3{,}60 \times 10^8$ km/h.

[1] The cool TeX automation tool: https://www.ctan.org/pkg/arara

©2024–2026 by Pablo González L

4. In fisica nucleare si usa l'angstrom (simbolo: $1\,\text{Å} = 1 \times 10^{-10}$ m) e il fermi o femtometro ($1\,\text{fm} = 1 \times 10^{-15}$ m). Qual è la relazione tra queste due unità di misura?
   - ✓ A $1\,\text{Å} = 1 \times 10^{5}$ fm.
   - B $1\,\text{Å} = 1 \times 10^{-5}$ fm.
   - C $1\,\text{Å} = 1 \times 10^{-15}$ fm.
   - D $1\,\text{Å} = 1 \times 10^{3}$ fm.

1. B ※ 2. A ※
3. B ※ 4. A ※

Example 3


A *"simple multiple choice"* test. Source file.

1. First type of questions
   - (A) value
   - (B) correct
   - (C) value
   - (D) value
2. Second type of questions
   I. $2\alpha + 2\delta = 90°$
   II. $\alpha = \delta$
   III. $\angle EDF = 45°$
   - (A) I only
   - (B) II only
   - (C) I and II only
   - (D) I and III only
   - (E) I, II, and III
3. Third type of questions
   (1) $2\alpha + 2\delta = 90°$
   (2) $\angle EDF = 45°$
   - (A) value
   - (B) value
   - (C) value
   - (D) value
   - (E) value
4. Question with image and label below:



(A) (B) (C) (D) (E)

5. Question with image on right side:
   - (A) value
   - (B) value
   - (C) value
   - (D) correct
   - (E) value



Test keys

1. B, $x = 5$ ※ 4. E, A duck ※
2. D ※ 5. D, other note ※
3. C, some note ※

Example 4

A *"simple worksheet"* using ducks :) Source file.

Factor $x^2 - 2x + 1$

Factor $3x + 3y + 3z$

The following questions need to be cuaqtified :)

True False

(a) $\alpha > \delta$

(b) LaTeX2e is cool?

Related to Linux

(a) You use Linux?

(b) Usually uses the package manager?

(c) Rate the following package and class

i. `xsim-exam`

ii. `xsim`

iii. `exsheets`

The answer to 1 is $(x-1)^2$ and the answer to 3.(a) is False.

1. $(x-1)^2$ ※
2. $3(x+y+z)$ ※
3. (a) False ※
   (b) Very True! ※
4. (a) Yes ※
   (b) Yes, `dnf` ※
   (c) i. doesn't exist for now :(※
   ii. very good ※
   iii. obsolete ※

Example 5

Adapted from the response given by Stephen in SAT like question format. Source file.

1

Which choice best describes what happens in the passage?

A) One character argues with another character who intrudes on her home.
B) One character receives a surprising request from another character.
C) One character reminisces about choices she has made over the years.
D) One character criticizes another character for pursuing an unexpected course of action.

2

Which choice best describes what happens in the passage?

A) One character argues with another character who intrudes on her home.
B) One character receives a surprising request from another character.
C) One character reminisces about choices she has made over the years.
D) One character criticizes another character for pursuing an unexpected course of action.

3

Which choice best describes what happens in the passage?

A) One character argues with another character who intrudes on her home.
B) One character receives a surprising request from another character.
C) One character reminisces about choices she has made over the years.
D) One character criticizes another character for pursuing an unexpected course of action.

4

Which choice best describes what happens in the passage?

A) One character argues with another character who intrudes on her home.
B) One character receives a surprising request from another character.
C) One character reminisces about choices she has made over the years.
D) One character criticizes another character for pursuing an unexpected course of action.

1. A) 2. C) 3. B) 4. D)

Example 6

Adapted from the response to Environment for enumerate environment. Source file.

8.5a, KSC **10.** sample

A sample
✓ **B** answer
C sample
D sample

9.5a, KSC **11.** sample

A sample
B sample
C sample
✓ **D** answer

12. sample

A sample
B answer
C sample
D sample

13. sample

A sample
B sample
C sample
D answer

©2024–2026 by Pablo González L

10. B (8.5a, KSC)
11. D (9.5a, KSC)
12. B (10.5a, KSC)
13. D (11.5a, KSC)

8 Tagged PDF examples

This section is just to show the compatibility of enumext with *tagged* PDF using lualatex. The files described below are just for testing and are intended as examples and, in a way, to simplify the time of Matthew Bertucci (@mbertucci) when he sees this excellent package and adds it to The LaTeX Tagged PDF repository.

To compile the tests with lualatex-dev the packages multicol, unicode-math, geometry, graphicx, luamml and hyperref are required along with the line:

```
\DocumentMetadata{lang = en-US, pdfversion = 2.0, pdfstandard = ua-2, tagging=on,}
```

All examples have been checked using veraPDF together with ngpdf.

- The file enumext-01.tex contains the basic tests for the enumext and enumext* environments and the nesting between them plus the use of the label, labelwidth, labelsep, ref, align and wrap-label keys.
- The file enumext-02.tex contains the tests for the enumext and enumext* environments and the support for minipage and multicols environments using the keys columns, columns-sep, mini-env, mini-right and \miniright command. Source file and *tagged* PDF.
- The file enumext-03.tex contains the tests for the enumext and keyanspic environments activated by the save-ans key together with the save-sep and save-ref keys and the \printkeyans command. Source file and *tagged* PDF.
- The file enumext-04.tex contains the tests for the \anskey command and the anskey* environment activated by the save-ans key along with the \getkeyans and \printkeyans commands. Source file and *tagged* PDF.
- The file enumext-05.tex contains the tests for the environments keyans, keyans* and keyanspic activated by the key save-ans together with the keys no-store and show-ans and the commands \setenumext, \setenumextmeta, \printkeyans and \foreachkeyans. Source file and *tagged* PDF.
- The file enumext-06.tex contains the tests for the environments enumext and enumext* for *fake* itemize and description. Source file and *tagged* PDF.
- The file enumext-07.tex contains the tests for starting the environments with \setenumext{resume}, the \resetenumext command and the series, resume, resume* and reset keys. Source file and *tagged* PDF.

9 The way of non-enumerated lists

It is possible to use (or abuse) the enumext and enumext* environments to mimic *non-enumerated* list environments such as itemize and description, clearly the ⟨*keys*⟩ to *"store answers"*, the keyans, keyans* and keyanspic environments lose their sense and it is not the focus of enumext package, but, why not to do it?.

Other uses of the enumext environment that can be helpful for specific purposes are shown as examples. The *trick* to generate these *"fake environments"* is to set label={} or label={⟨*some*⟩} and play with the list-indent, list-offset, font and wrap-label keys.

Fake itemize environment

The label key is set here using the default settings in LaTeX for the four levels \textbullet, \textendash, \textasteriskcentered and \textperiodcentered together with the nosep key to reduce the vertical spaces in the left side example and set the label key in *mathematical mode* for the right side as \ast, \diamond, \circ and \star for the four levels together with the nosep key

- First level item
  - Second level item
    - Third level item
      - Fourth level item
- First level item

∗ First level item
  ◇ Second level item
    ◦ Third level item
      ⋆ Fourth level item
∗ First level item

Fake description environment

Here label={} and list-indent=2.5em,font=\bfseries are set.

SomeThing A short one-line description.
This is an entry *without* a label.
Something A short *one-line* description text.
Something long A much *longer* description text may take more than one line or more than one paragraph.

©2024–2026 by Pablo González L

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

Adding `list-indent=0pt` gives the *widest style*:

SomeThing A short one-line description.
This is an entry *without* a label.
Something A short *one-line* description text.
Something long A much *longer* description text may take more than one line or more than one paragraph. Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

The small space at the beginning of the *"unlabeled entry"* corresponds to `\labelsep` and can be removed using `\hspace{-\labelsep}` at the beginning of the line.

When *tagged* PDF is active the default `description` style is NOT available due to the redefinition of `\makelabel` for the `align` key which uses `\makebox` in this case, meaning that `\item[⟨content⟩]` will not extend beyond `\labelwidth` which causes overlaps,

Description indented by label

Here `label={}` is set and a convenient value is given to `labelsep` and `labelwidth`, for example taking the *longest label* as reference and passing it as value using:

```
\newlength{\descitemwd}
\settowidth{\descitemwd}{\textbf{Something long}}
```

and then use `labelsep=4pt,labelwidth=\descitemwd,font=\bfseries`.

SomeThing A short one-line description.
This is an entry *without* a label.
Something A short one-line description.
Something long A much longer description. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

The environment can be translated so that the ⟨*labels*⟩ are on the left margin calculating the value passed to the `list-offset` key, in this case it will be equal to the sum of the values set by the `labelwidth` and `labelsep` keys finally resulting as `list-offset={-\descitemwd - 4pt}`.

SomeThing A short one-line description.
This is an entry *without* a label.
Something A short one-line description.
Something long A much longer description. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

Adding `align=right` gives:

SomeThing A short one-line description.
This is an entry *without* a label.
Something A short one-line description.
Something long A much longer description. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

At this point `list-offset={-\descitemwd - 4pt}` instead of `list-offset={-\labelwidth - \labelsep}`, this is because the parameters `\labelwidth` and `\labelsep` take the default values, as if `label` had not been set.

Description with multi-line labels

The `label` key does not accept *multiline material*, this is where the `wrap-label` and `wrap-label*` keys comes into play. Unlike the `enumitem` package, the `align` key only supports three options, so a command is created in the style `\parleft` of `enumitem` that allows placing *multiline labels* using `\parbox`.

```
\NewDocumentCommand \labelbx { s +m }
  {%
    \SuspendTagging{\parbox}%
    \IfBooleanTF{#1}
      {\strut\smash{\parbox[t]{\labelwidth}{\raggedright{#2}}}}%
      {\strut\smash{\parbox[t]{\labelwidth}{\raggedleft{#2}}}}%
    \ResumeTagging{\parbox}%
  }
```

Now it is only necessary to set `wrap-label*={\labelbx{#1}}`.

SomeThing A short one-line description.

©2024–2026 by Pablo González L

This is an entry *without* a label.

Something A short one-line description.

Something long A much longer description. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.
Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

SoMeThInG LoNg A much longer description. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris.

Final notes

The original implementation (if you can call it that) of the ideas that led to the creation of enumext were some macros using the `enumerate`[5] package for personal use created in early 2003, the code was quite questionable, but functional for these simple requirements.

With the great answers given by Christian Hupfer in Create a fake label ref using list and the answer given by David Carlisle in Change the use of label ref by data save in an array (list) I managed to create a more solid code than the original version, now using the `l3prop`[11] and `l3seq`[11] modules together with the `hyperref`[8] and `enumitem`[6] packages, which did the job, but with some limitations.

As time went by I took these limitations as a personal challenge which I called *"reinventing the wheel"*, since there were packages and classes that did more or less what I was looking for, but did not fit my simple requirements. This *"reinventing the wheel"* finally ended up becoming enumext.

Why list environments?

The answer is simple, first I love the beauty of its syntax and many of what I had already written used the `enumerate` environment or lists created using the `enumitem` package. In my mind I thought: how complicated could it be to write a package that looked like `enumitem`? It seemed simple enough, of course I didn't have in mind the mess I was getting into working with `list` environments, `minipage` and adding support for the `multicol` and `hyperref` packages.

Of course, seeing the final result of the experiment *"reinventing the wheel"* I am quite satisfied.

Why not random questions and other utilities

The *"random"* type questions I love and hate them at the same time, although they simplify a lot the work when creating a multiple choice test, but you lose the beauty of typesetting a document with LaTeX, that is to say the output does not always look as nice as it should, even if they are only alternatives these must follow a certain order when presented either numerical or presentation, that said handling that using *nested lists* is quite complicated so I do not classify to be implemented.

Why has it taken so long?

One of the setbacks, beyond my laziness, was including compatibility with *tagged* PDF. To be honest, it's something I never considered at any point, but I firmly believe that being able to create *accessible documents* provides a great opportunity in the world of mathematics education. From my perspective as a *high school* teacher, beyond theorems and deep mathematics, the use of exercise lists is one of the most common things. Being able to open the way to work in parallel with those who have different abilities is really important and I regret not having looked into this in the past. I hope that enumext serves this purpose and inspires more users and authors to follow this path.

10 References

[1] Hirschhorn, Philip. "Using the exam document class". Available from CTAN, `https://www.ctan.org/pkg/exam`, 2023.

[2] Niederberger, Clemens. "xsim – eXercise Sheets IMproved". Available from CTAN, `https://www.ctan.org/pkg/xsim`, 2023.

[3] Mittelbach, Frank. "An environment for multicolumn output". Available from CTAN, `https://www.ctan.org/pkg/multicol`, 2025.

[4] González, Pablo. "scontents - Stores LaTeX contents in memory or files". Available from CTAN, `https://www.ctan.org/pkg/scontents`, 2026.

[5] The LaTeX Project. "enumerate – Enumerate with redefinable labels". Available from CTAN, `https://www.ctan.org/pkg/enumerate`, 2025.

[6] Bezos, Javier. "Customizing lists with the enumitem package". Available from CTAN, `https://www.ctan.org/pkg/enumitem`, 2025.

©2024–2026 by Pablo González L

[7] Berry, Karl. "LaTeX 2ε: An Unofficial Reference Manual". Available from ctan, https://ctan.org/pkg/latex2e-help-texinfo, 2026.

[8] The LaTeX Project. "Extensive support for hypertext in LaTeX". Available from ctan, https://www.ctan.org/pkg/hyperref, 2026.

[9] Burnol, Jean-François. "The footnotehyper package". Available from ctan, https://www.ctan.org/pkg/footnotehyper, 2025.

[10] The LaTeX Project. "The expl3 package". Available from ctan, https://www.ctan.org/pkg/l3kernel, 2026.

[11] The LaTeX Project. "The LaTeX3 Interfaces". Available from ctan, https://www.ctan.org/pkg/l3kernel, 2026.

[12] The LaTeX Project. "The LaTeX 2ε sources". Available from ctan, https://ctan.org/tex-archive/macros/latex/base, 2026.

[13] The LaTeX Project. "LaTeX News, Issue 41, June 2025". Available from ctan, https://ctan.org/tex-archive/macros/latex/base, 2025.

[14] The LaTeX Project. "LaTeX for authors current version". Available from ctan, https://ctan.org/pkg/latex-base, 2026.

[15] Gundlach, Patrick. "The lua-visual-debug package". Available from ctan, https://www.ctan.org/pkg/lua-visual-debug, 2026.

[16] Lemvig, Mogens. "The shortlst package". Available from ctan, https://www.ctan.org/pkg/shortlst, 1998.

[17] Niederberger, Clemens. "tasks – Horizontally columned lists". Available from ctan, https://www.ctan.org/pkg/tasks, 2022.

[18] Fischer, Ulrike. "tagpdf – LaTeX kernel code for PDF tagging". Available from ctan, https://www.ctan.org/pkg/tagpdf, 2026.

[19] The LaTeX Project. "latex-lab – LaTeX laboratory". Available from ctan, https://www.ctan.org/pkg/latex-lab, 2026.

[20] Mittelbach, Frank. "LaTeX's socket management". Available from ctan, https://ctan.org/tex-archive/macros/latex/base, 2026.

11 Change history

v2.3 (ctan), 2026-10-03
- Update requirement to LaTeX release 2026-11-01.
- Cleanup warnings and details returned by `expltools`.
- Replace `\exp_after:wN` by `\exp_after:w`.
- Update code for *tagged* PDF.
- Adjustments in the documentation.

v2.2 (ctan), 2026-06-01
- Update requirement to LaTeX release 2026-06-01.
- Move `\setcounter` to `\begin{list}{⟨arg one⟩}{⟨arg two⟩\setcounter}` for `enumext*`.
- Adjustments in the documentation.

v2.1 (ctan), 2026-01-15
- Fixed bad interaction between `\setenumext` and the `ref` key.

v2.0 (ctan), 2025-12-02
- Update requirement to `multicol` release 2025-10-21.
- Adjustments in the documentation.

v1.9 (ctan), 2025-11-01
- Update requirement to LaTeX release 2025-11-01.
- Move `\setcounter` to `\begin{list}{⟨arg one⟩}{⟨arg two⟩\setcounter}`.
- Update code for *tagged* PDF.

v1.8 (ctan), 2025-10-04
- Replacing `\scantokens` (primitive) with `\tl_retokenize:n`.
- Cleanup warnings and details returned by `expltools`.

v1.7 (ctan), 2025-07-10
- Fixed `\setenumext{enumext*}{resume}`.
- Fixed bad interaction between `\setenumext` and the `resume` key.
- The behavior of the key `resume*` has been updated and documented.

v1.6 (ctan), 2025-07-04
- Syntax simplification for `\setenumextmeta`.
- Environments can be started with the key `resume` *without value*.
- Add `\resetenumext`, `reset` and `reset*` keys.
- The `resume`, `resume*` and `series` keys can now be set per level.
- Fixed bad interaction between `\printkeyans` and the `resume`, `resume*` keys.

v1.5 (ctan), 2025-06-11
- Replacing `\regex_match:` (deprecated) with `\regex_if_match:`.

©2024–2026 by Pablo González L

- Add keys `beginpenalty`, `midpenalty` and `endpenalty`.

v1.4 (ctan), 2025-06-09
- Improved implementation of the `start` key for *tagged* PDF.
- Improved implementation of the `ref` key.
- Fixed the behavior of the `save-sep` key.
- Fixed the behavior of the `resume*` key.

v1.3 (ctan), 2025-06-01
- Removed dependency on the `scontents` package.
- The `anskey*` environment has been rewritten using the new `c-type` argument.

v1.2 (ctan), 2025-03-28
- Replace signature (prevent expansion for optional argument).
- Solve Inconsistent local/global assignment.

v1.1 (ctan), 2024-11-14
- Fixed implementation for `font` and `base-fix` keys.
- Added new keys for symbol marks.
- Update and improvements in the internal code.
- Adjustments in the documentation.

v1.0 (ctan), 2024-11-01
- First public release.

©2024–2026 by Pablo González L

12 Index of Documentation

The italic numbers denote the pages where the corresponding entry is described.

C

Document class :
- article . . . 2
- book . . . 2
- exam . . . 2
- letter . . . 2
- report . . . 2

Commands provided by enumext:
- \anskey . . . 15, 16
- \anspic . . . 19
- \foreachkeyans . . . 20
- \getkeyans . . . 20
- \item* . . . 5, 6, 17, 18
- \item . . . 5, 6
- \miniright . . . 12
- \printkeyans . . . 21
- \resetenumext . . . 12
- \setenumextmeta . . . 7
- \setenumext . . . 6

Counters defined by enumext:
- enumXiii . . . 4
- enumXii . . . 4
- enumXiv . . . 4
- enumXi . . . 4
- enumXviii . . . 4
- enumXvii . . . 4
- enumXvi . . . 4
- enumXv . . . 4

D

Dimension defined by enumext:
- \itemwidth . . . 4

E

Environments provided by enumext:
- anskey* . . . 16
- enumext* . . . 4
- enumext . . . 4
- keyans* . . . 17
- keyanspic . . . 18
- keyans . . . 17

I

\itemwidth . . . 4

K

Keys for \anskey provided by enumext:
- break-col . . . 15
- item-join . . . 15
- item-pos* . . . 16
- item-star . . . 15, 16
- item-sym* . . . 15, 16

Keys for \foreachkeyans provided by enumext:
- after . . . 20
- before . . . 20
- sep . . . 20
- start . . . 20
- step . . . 20
- stop . . . 20
- wrapper . . . 20

Keys for anskey* provided by enumext:
- break-col . . . 15
- force-eol . . . 16
- item-join . . . 15
- item-pos* . . . 16
- item-star . . . 15, 16
- item-sym* . . . 15, 16
- overwrite . . . 16
- write-env . . . 16

Keys for environments provided by enumext:
- above* . . . 10
- above . . . 9
- after . . . 11
- align . . . 8
- base-fix . . . 9
- before* . . . 10
- before . . . 10
- beginpenalty . . . 8
- below* . . . 10
- below . . . 10
- check-ans . . . 15
- columns-sep . . . 12
- columns . . . 12
- endpenalty . . . 8
- first . . . 11
- font . . . 8
- item-pos* . . . 6
- item-sym* . . . 6
- itemindent . . . 10
- itemsep . . . 9
- label-pos . . . 18
- label-sep . . . 18
- labelsep . . . 7
- labelwidth . . . 7
- label . . . 7
- layout-sep . . . 18
- layout-sty . . . 18
- layout-top . . . 19
- list-indent . . . 10
- list-offset . . . 10
- listparindent . . . 10
- mark-ans* . . . 14
- mark-ans . . . 14
- mark-pos* . . . 15
- mark-pos . . . 14
- mark-ref . . . 14
- mark-sep* . . . 15
- mark-sep . . . 14
- midpenalty . . . 8
- mini-env . . . 12
- mini-right* . . . 13
- mini-right . . . 12
- mini-sep . . . 12
- mode-box . . . 7
- no-store . . . 13
- noitemsep . . . 9
- nosep . . . 9
- parsep . . . 9
- partopsep . . . 9
- ref . . . 8
- reset* . . . 12
- reset . . . 11

©2024–2026 by Pablo González L

resume* 11
resume 11
rightmargin 10
save-ans 13
save-key 13
save-ref 14
save-sep 13
series 11
show-ans 14
show-length 9
show-pos 15
start* 11
start 11
topsep 9
widest 8
wrap-ans* 15
wrap-ans 14
wrap-label* 8
wrap-label 8
wrap-opt 15

L

Labels provided by enumext:

\Alph* 7
\Roman* 7
\alph* 7
\arabic* 7
\roman* 7
\labelsep 4
\labelwidth 4

P

Packages :

enumerate 27
enumitem 3
fancyvrb 16
footnotehyper 5
geometry 25
graphicx 25
hyperref 5
l3keys 7
l3prop 27
l3seq 27
luamml 25
multicol 1
scontents 29
shortlst 5
tasks 5
unicode-math 25
xsim 2

©2024–2026 by Pablo González L

13 Implementation

The most recent publicly released version of enumext is available at CTAN: https://www.ctan.org/pkg/enumext. While general feedback via email is welcomed, specific bugs or feature requests should be reported through the issue tracker: https://github.com/pablgonz/enumext/issues.

The documentation presented here is far from professional, it contains a lot of obvious information that to the eye of a TEXpert are superfluous, but, after so many years developing this project is the only way to remember what does what.

13.1 General conventions

Variables containing i, ii, iii and iv are associated by level with the enumext environment, variables containing v are associated with the keyans environment, variables containing vi are associated with the keyanspic environment, variables containing vii are associated with the enumext* environment and variables containing viii are associated with the keyans* environment.

To simplify writing and documentation some variables and functions that are common to the different levels of the environments are described using a capital "X".

The temporary function __enumext_tmp:n is used in different parts of the package code for variable creation or execution of other functions that are grouped into this one.

All variables and functions defined in this package are private and are NOT intended to work or be used by another package or module.

13.2 Initial set up

Start the DocStrip guards.

```
⟨*package⟩
```

Identify the internal prefix (LaTeX3 DocStrip convention) for l3doc class.

```
⟨@@=enumext⟩
```

13.3 Declaration of the package

Checks for a minimum release version of LaTeX; otherwise it returns an "error".

```
\NeedsTeXFormat{LaTeX2e}[2026-11-01]
\IfFormatAtLeastF { 2026-11-01 }
  {
    \PackageError { enumext }
      { LaTeX~kernel~too~old~need~2026-11-01~or~later }
      {
        enumext~requires~a~LaTeX2e~release~2026-11-01~or~
        later.~Update~your~TeX~distribution.
      }
  }
```

Now declare the enumext package.

```
\ProvidesExplPackage {enumext} {2026-10-03} {2.3} {Enumerate exercise sheets}
```

Finally, check if the multicol package is loaded; if not, it is loaded.

```
\hook_gput_code:nnn {begindocument} {enumext}
  {
    \IfPackageLoadedTF { multicol }
      {
        \msg_info:nnn { enumext } { package-load } { multicol }
      }
      {
        \msg_info:nnn { enumext } { package-not-load } { multicol }
        \RequirePackage{multicol}[2025-10-21]
      }
  }
```

13.4 Definition of variables

Variables that do not appear in this section are created by means of \keys_define:nn or some function described below.

\l__enumext_level_int
\l__enumext_level_h_int
\l__enumext_anskey_level_int
\l__enumext_keyans_level_int
\l__enumext_keyans_level_h_int
\l__enumext_keyans_pic_level_int

Integer variables will control the nesting levels of the environments, anskey* environment and \anskey command.

```
\int_new:N  \l__enumext_level_int
\int_new:N  \l__enumext_level_h_int
```

```
\int_new:N  \l__enumext_anskey_level_int
\int_new:N  \l__enumext_keyans_level_int
\int_new:N  \l__enumext_keyans_level_h_int
\int_new:N  \l__enumext_keyans_pic_level_int
```

(*End of definition for* `\l__enumext_level_int` *and others.*)

`\l__enumext_starred_bool` `\g__enumext_starred_bool` `\l__enumext_starred_first_bool` `\l__enumext_standard_bool` `\g__enumext_standard_bool` `\l__enumext_standard_first_bool` `\l__enumext_keyans_env_bool` `\g__enumext_start_line_tl` `\g__enumext_envir_name_tl` `\l__enumext_envir_name_tl`

Internal variables used by functions `\__enumext_is_not_nested:`, `\__enumext_is_on_first_level:` and `\__enumext_keyans_name_and_start:` (§13.5.1).

```
\bool_new:N \l__enumext_starred_bool
\bool_new:N \g__enumext_starred_bool
\bool_new:N \l__enumext_starred_first_bool
\bool_new:N \l__enumext_standard_bool
\bool_new:N \g__enumext_standard_bool
\bool_new:N \l__enumext_standard_first_bool
\bool_new:N \l__enumext_keyans_env_bool
\tl_new:N   \g__enumext_start_line_tl
\tl_new:N   \g__enumext_envir_name_tl
\tl_new:N   \l__enumext_envir_name_tl
```

(*End of definition for* `\l__enumext_starred_bool` *and others.*)

`\l__enumext_counter_i_tl` `\l__enumext_counter_ii_tl` `\l__enumext_counter_iii_tl` `\l__enumext_counter_iv_tl` `\l__enumext_counter_v_tl` `\l__enumext_counter_vi_tl` `\l__enumext_counter_vii_tl` `\l__enumext_counter_viii_tl`

Variables to store the *"name of the counters"* `enumXi`, `enumXii`, `enumXiii` and `enumXiv` for `enumext` environment, `enumXv` for `keyans` environment and `enumXvi` for the `keyanspic` environment. The counters `enumXvii` and `enumXviii` are used by `enumext*` and `keyans*` environments.

The initial values of these variables are set by the function `\__enumext_define_counter:Nn` (§13.11) and then modified by the function `\__enumext_label_style:Nnn` used by `label` key (§13.14).

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \tl_new:c { l__enumext_counter_#1_tl }
  }
\clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }
```

(*End of definition for* `\l__enumext_counter_i_tl` *and others.*)

`\l__enumext_ref_key_arg_tl` `\l__enumext_ref_the_count_tl` `\l__enumext_renew_counter_X_tl` `\l__enumext_the_counter_X_tl`

Internal variables used by `ref` key (§13.14).

```
\tl_new:N \l__enumext_ref_key_arg_tl
\tl_new:N \l__enumext_ref_the_count_tl
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \tl_new:c  { l__enumext_renew_counter_#1_tl }
    \tl_new:c  { l__enumext_the_counter_#1_tl   }
    \tl_set:ce { l__enumext_the_counter_#1_tl   } { \exp_not:c { theenumX#1 } }
  }
\clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }
```

(*End of definition for* `\l__enumext_ref_key_arg_tl` *and others.*)

`\l__enumext_series_name_tl` `\l__enumext_resume_count_bool` `\l__enumext_resume_count_X_bool` `\l__enumext_resume_series_X_bool` `\l__enumext_resume_star_key_X_bool` `\g__enumext_resume_last_keys_X_tl`

Internal variables used by `resume`, `resume*` and `series` keys (§13.26).

```
\tl_new:N   \l__enumext_series_name_tl
\bool_new:N \l__enumext_resume_count_bool
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \bool_new:c { l__enumext_resume_count_#1_bool    }
    \bool_new:c { l__enumext_resume_series_#1_bool   }
    \bool_new:c { l__enumext_resume_star_key_#1_bool }
    \tl_new:c   { g__enumext_resume_last_keys_#1_tl  }
  }
\clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {#1} }
```

(*End of definition for* `\l__enumext_series_name_tl` *and others.*)

`\l__enumext_current_widest_dim` `\g__enumext_counter_styles_tl` `\g__enumext_widest_label_tl` `\l__enumext_label_width_by_box`

The variable `\l__enumext_current_widest_dim` stores the current label width, the variable `\g__enumext_counter_styles_tl` stores the default ⟨*label style*⟩ and the variable `\g__enumext_widest_label_tl` the label width. These variables are used by `widest` (§13.15) and `label` (§13.13) keys.

```
\dim_new:N \l__enumext_current_widest_dim
\tl_new:N  \g__enumext_counter_styles_tl
\tl_new:N  \g__enumext_widest_label_tl
\box_new:N \l__enumext_label_width_by_box
```

(*End of definition for* `\l__enumext_current_widest_dim` *and others.*)

`\l__enumext_leftmargin_tmp_X_bool` `\l__enumext_leftmargin_tmp_X_dim` `\l__enumext_leftmargin_X_dim` `\l__enumext_itemindent_X_dim`

The boolean variable `\l__enumext_leftmargin_tmp_X_bool` and the dimensional variable `\l__enumext_leftmargin_tmp_X_dim` are used by the `list-indent` key (§13.19). The variables `\l__enumext_leftmargin_X_dim` and `\l__enumext_itemindent_X_dim` are used and set by the function `\__enumext_calc_hspace:NNNNNNN` (§13.41.1).

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \bool_new:c { l__enumext_leftmargin_tmp_#1_bool }
    \dim_new:c  { l__enumext_leftmargin_tmp_#1_dim  }
    \dim_new:c  { l__enumext_leftmargin_#1_dim      }
    \dim_new:c  { l__enumext_itemindent_#1_dim      }
  }
\clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }
```

(*End of definition for* `\l__enumext_leftmargin_tmp_X_bool` *and others.*)

`\l__enumext_multicols_above_X_skip` `\l__enumext_multicols_below_X_skip` `\l__enumext_align_label_pos_X_str`

Internal variables used by `columns` key (§13.23) and `align` key (§13.13).

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \skip_new:c  { l__enumext_multicols_above_#1_skip }
    \skip_new:c  { l__enumext_multicols_below_#1_skip }
    \str_new:c   { l__enumext_align_label_pos_#1_str  }
  }
\clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }
```

(*End of definition for* `\l__enumext_multicols_above_X_skip`*,* `\l__enumext_multicols_below_X_skip`*, and* `\l__enumext_align_label_pos_X_str`*.*)

`\g__enumext_minipage_stat_int` `\l__enumext_minipage_temp_skip` `\l__enumext_minipage_left_skip` `\l__enumext_minipage_right_skip` `\l__enumext_minipage_after_skip` `\g__enumext_minipage_right_skip` `\g__enumext_minipage_after_skip` `\l__enumext_minipage_left_X_dim` `\l__enumext_minipage_active_X_bool`

Internal variables used by `\miniright` command (§13.24.4) and the keys `mini-right`, `mini-right*`, `mini-env` and `mini-sep` (§13.22, §13.24).

```
\int_new:N  \g__enumext_minipage_stat_int
\skip_new:N \l__enumext_minipage_temp_skip
\skip_new:N \l__enumext_minipage_left_skip
\skip_new:N \l__enumext_minipage_right_skip
\skip_new:N \l__enumext_minipage_after_skip
\skip_new:N \g__enumext_minipage_right_skip
\skip_new:N \g__enumext_minipage_after_skip
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \dim_new:c  { l__enumext_minipage_left_#1_dim    }
    \bool_new:c { l__enumext_minipage_active_#1_bool }
  }
\clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }
```

(*End of definition for* `\g__enumext_minipage_stat_int` *and others.*)

`\l__enumext_wrap_label_X_bool` `\l__enumext_wrap_label_opt_X_bool` `\l__enumext_start_X_int` `\l__enumext_fake_item_indent_X_tl` `\l__enumext_label_fill_left_X_tl` `\l__enumext_label_fill_right_X_tl` `\l__enumext_vspace_a_star_X_bool` `\l__enumext_vspace_b_star_X_bool`

The bool vars `\l__enumext_wrap_label_X_bool` and `\l__enumext_wrap_label_opt_X_bool` are used by `wrap-label` and `wrap-label*` keys (§13.13), the integer `\l__enumext_start_X_int` are used by the `start` and `start*` keys (§13.15), the token list `\l__enumext_fake_item_indent_X_tl` is used by `itemindent` key (§13.19.1), the variables `\l__enumext_label_fill_left_X_tl` and `\l__enumext_label_fill_left_X_tl` are used by the `align` key (§13.13). The boolean vars `\l__enumext_vspace_a_star_X_bool`, `\l__enumext_vspace_b_star_X_bool` are used by `above`, `above*`, `below` and `below*` keys (§13.21).

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \bool_new:c { l__enumext_wrap_label_#1_bool     }
    \bool_new:c { l__enumext_wrap_label_opt_#1_bool }
    \int_new:c  { l__enumext_start_#1_int           }
    \tl_new:c   { l__enumext_fake_item_indent_#1_tl }
    \tl_new:c   { l__enumext_label_fill_left_#1_tl  }
    \tl_new:c   { l__enumext_label_fill_right_#1_tl }
    \bool_new:c { l__enumext_vspace_a_star_#1_bool  }
    \bool_new:c { l__enumext_vspace_b_star_#1_bool  }
  }
\clist_map_inline:nn { i, ii, iii, iv, v, vii, viii } { \__enumext_tmp:n {#1} }
```

(*End of definition for* `\l__enumext_wrap_label_X_bool` *and others.*)

©2024–2026 by Pablo González L

\l__enumext_store_active_bool
\l__enumext_store_name_tl
\g__enumext_store_name_tl
\l__enumext_store_current_label_tl
\l__enumext_store_current_opt_arg_tl

The variable \l__enumext_store_active_bool setting by save-ans key (§13.29.1) activates all the mechanism related to \anskey, anskey*, keyans, keyans* and keyanspic environments.

The variable \l__enumext_store_name_tl saves the {⟨*store name*⟩} set by the save-ans key of the *sequence* and *prop list* where the content is stored. The variable \g__enumext_store_name_tl is just a global copy of {⟨*store name*⟩} used by different functions.

The variables \l__enumext_store_current_label_tl and \l__enumext_store_current_opt_arg_tl save the *current label* and *optional argument* of \item* (§13.40) and \anspic* (§13.45.2) for the keyans, keyans* and keyanspic environments.

```
\bool_new:N \l__enumext_store_active_bool
\tl_new:N   \l__enumext_store_name_tl
\tl_new:N   \g__enumext_store_name_tl
\tl_new:N   \l__enumext_store_current_label_tl
\tl_new:N   \l__enumext_store_current_opt_arg_tl
```

(*End of definition for* \l__enumext_store_active_bool *and others.*)

\l__enumext_store_anskey_arg_tl
\l__enumext_store_anskey_env_tl
\l__enumext_write_anskey_env_bool
\l__enumext_write_anskey_env_file_name_tl
\l__enumext_write_anskey_env_file_iow

The variable \l__enumext_store_anskey_arg_tl save the *argument* of \anskey (§13.33) and the variables \l__enumext_store_anskey_env_tl save the ⟨*body*⟩ of the environment anskey* (§13.34).

The variables \l__enumext_write_anskey_env_bool, \l__enumext_write_anskey_env_file_name_tl and \l__enumext_write_anskey_env_file_iow they are used by the write-env and overwrite keys in the anskey* environment implementation.

```
\tl_new:N   \l__enumext_store_anskey_arg_tl
\tl_new:N   \l__enumext_store_anskey_env_tl
\bool_new:N \l__enumext_write_anskey_env_bool
\tl_new:N   \l__enumext_write_anskey_env_file_name_tl
\iow_new:N  \l__enumext_write_anskey_env_file_iow
```

(*End of definition for* \l__enumext_store_anskey_arg_tl *and others.*)

\c__enumext_anskey_env_hidden_space_str

The \c__enumext_anskey_env_hidden_space_str is a constant *string* to used to hide the ⟨*forced space*⟩ added by TEX when recording content in a macro. This *string* contains the *reserved phrase* '%^^Aenumextheol%' which is added to the end of the argument stored in *sequence* and *prop list* when the key force-eol is false.

```
\str_const:Ne \c__enumext_anskey_env_hidden_space_str
  { \c_percent_str \c_circumflex_str \c_circumflex_str A enumextheol
    \c_percent_str }
```

(*End of definition for* \c__enumext_anskey_env_hidden_space_str.)

\l__enumext_setkey_tmpa_tl
\l__enumext_setkey_tmpb_tl
\l__enumext_setkey_tmpa_int
\l__enumext_setkey_tmpa_seq
\l__enumext_setkey_tmpb_seq

Internal variables used by the command \setenumext (§13.51).

```
\tl_new:N  \l__enumext_setkey_tmpa_tl
\tl_new:N  \l__enumext_setkey_tmpb_tl
\int_new:N \l__enumext_setkey_tmpa_int
\seq_new:N \l__enumext_setkey_tmpa_seq
\seq_new:N \l__enumext_setkey_tmpb_seq
```

(*End of definition for* \l__enumext_setkey_tmpa_tl *and others.*)

\l__enumext_meta_path_str
\l__enumext_foreach_print_seq
\l__enumext_foreach_name_prop_tl
\l__enumext_foreach_default_keys_tl

Internal variables used by the \setenumextmeta command (§13.52) and \foreachkeyans command (§13.53).

```
\str_new:N \l__enumext_meta_path_str
\seq_new:N \l__enumext_foreach_print_seq
\tl_new:N  \l__enumext_foreach_name_prop_tl
\tl_new:N  \l__enumext_foreach_default_keys_tl
```

(*End of definition for* \l__enumext_meta_path_str *and others.*)

\l__enumext_print_keyans_starred_tl
\l__enumext_print_keyans_star_bool
\l__enumext_print_keyans_cmd_bool
\l__enumext_mark_position_str
\l__enumext_mark_position_v_str
\l__enumext_mark_position_viii_str
\l__enumext_mark_sep_tmpa_dim
\l__enumext_mark_sep_tmpb_dim
\l__enumext_show_pos_tmp_int
\g__enumext_item_symbol_aux_tl
\l__enumext_print_keyans_X_tl
\l__enumext_store_save_key_X_tl

Internal variables used by command \printkeyans (§13.50), show-pos, show-ans, mark-pos, mark-sep keys (§13.30), item-sym* key (§13.38), save-key key (§13.30.3) and *"storing structure"*.

```
\tl_new:N   \l__enumext_print_keyans_starred_tl
\bool_new:N \l__enumext_print_keyans_star_bool
\bool_new:N \l__enumext_print_keyans_cmd_bool
\str_new:N  \l__enumext_mark_position_str
\str_new:N  \l__enumext_mark_position_v_str
\str_new:N  \l__enumext_mark_position_viii_str
\dim_new:N  \l__enumext_mark_sep_tmpa_dim
\dim_new:N  \l__enumext_mark_sep_tmpb_dim
\int_new:N  \l__enumext_show_pos_tmp_int
```

©2024–2026 by Pablo González L

```
\tl_new:N   \g__enumext_item_symbol_aux_tl
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \tl_new:c   { l__enumext_print_keyans_#1_tl        }
    \tl_new:c   { l__enumext_store_save_key_#1_tl      }
    \bool_new:c { l__enumext_store_save_key_#1_bool    }
    \bool_new:c { l__enumext_store_upper_level_#1_bool }
  }
\clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {#1} }
```

(*End of definition for* `\l__enumext_print_keyans_starred_tl` *and others.*)

`\l__enumext_anspic_args_seq` `\l__enumext_anspic_mini_width_dim` `\l__enumext_anspic_above_int` `\l__enumext_anspic_below_int` `\l__enumext_anspic_label_above_bool` `\l__enumext_anspic_mini_pos_str` `\l__enumext_anspic_label_box` `\l__enumext_anspic_body_box` `\l__enumext_anspic_label_htdp_dim` `\l__enumext_anspic_body_htdp_dim`

Internal variables used by `keyanspic` environment and `\anspic` command (§13.45.1).

```
\seq_new:N  \l__enumext_anspic_args_seq
\dim_new:N  \l__enumext_anspic_mini_width_dim
\int_new:N  \l__enumext_anspic_above_int
\int_new:N  \l__enumext_anspic_below_int
\bool_new:N \l__enumext_anspic_label_above_bool
\str_new:N  \l__enumext_anspic_mini_pos_str
\box_new:N  \l__enumext_anspic_label_box
\box_new:N  \l__enumext_anspic_body_box
\dim_new:N  \l__enumext_anspic_label_htdp_dim
\dim_new:N  \l__enumext_anspic_body_htdp_dim
```

(*End of definition for* `\l__enumext_anspic_args_seq` *and others.*)

`\l__enumext_check_answers_bool` `\g__enumext_check_ans_key_bool` `\l__enumext_check_start_line_env_tl` `\l__enumext_item_wrap_key_bool` `\g__enumext_check_starred_cmd_int` `\g__enumext_item_anskey_int` `\g__enumext_item_number_int` `\l__enumext_item_number_bool` `\g__enumext_item_answer_diff_int`

Internal variables used by *"internal check answer"* mechanism (§13.29.4) used by the `check-ans`, `no-store`, `wrap-ans*` keys and check for starred commands `\item*` in `keyans` and `keyans*` environments and `\anspic*` in `keyanspic` environment.

```
\bool_new:N \l__enumext_check_answers_bool
\bool_new:N \g__enumext_check_ans_key_bool
\tl_new:N   \l__enumext_check_start_line_env_tl
\bool_new:N \l__enumext_item_wrap_key_bool
\int_new:N  \g__enumext_check_starred_cmd_int
\int_new:N  \g__enumext_item_anskey_int
\int_new:N  \g__enumext_item_number_int
\bool_new:N \l__enumext_item_number_bool
\int_new:N  \g__enumext_item_answer_diff_int
```

(*End of definition for* `\l__enumext_check_answers_bool` *and others.*)

`\l__enumext_hyperref_bool` `\l__enumext_footnotes_key_bool`

The boolean variable `\l__enumext_hyperref_bool` will determine if the `hyperref` package is present or load in memory (§13.7). The boolean variable `\l__enumext_footnotes_key_bool` determine if `hyperref` is load with key `hyperfootnotes=true`.

```
\bool_new:N \l__enumext_hyperref_bool
\bool_new:N \l__enumext_footnotes_key_bool
```

(*End of definition for* `\l__enumext_hyperref_bool` *and* `\l__enumext_footnotes_key_bool`.)

`\l__enumext_newlabel_arg_one_tl` `\l__enumext_newlabel_arg_two_tl` `\l__enumext_write_aux_file_tl` `\l__enumext_label_copy_X_tl`

Internal variables used by `save-ref` key (§13.30). The variables `\l__enumext_label_copy_X_tl` correspond to temporary copies of the ⟨*labels*⟩ defined by level on which operations will be performed.

The variables `\l__enumext_newlabel_arg_one_tl` and `\l__enumext_newlabel_arg_two_tl` will be used to form the arguments passed to the function `\__enumext_newlabel:nn` (§13.7) and the variable `\l__enumext_write_aux_file_tl` will be in charge of executing the writing code in the `.aux` file.

```
\tl_new:N \l__enumext_newlabel_arg_one_tl
\tl_new:N \l__enumext_newlabel_arg_two_tl
\tl_new:N \l__enumext_write_aux_file_tl
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \tl_new:c { l__enumext_label_copy_#1_tl }
  }
\clist_map_inline:nn { i, ii, iii, iv, v, vi, vii, viii } { \__enumext_tmp:n {#1} }
```

(*End of definition for* `\l__enumext_newlabel_arg_one_tl` *and others.*)

`\g__enumext_footnote_standard_int` `\g__enumext_footnote_starred_int` `\g__enumext_footnote_standard_arg_seq` `\g__enumext_footnote_starred_arg_seq` `\g__enumext_footnote_standard_int_seq`

Internal variables used for redefinition of `\footnote` (§13.8).

```
\int_new:N \g__enumext_footnote_standard_int
\int_new:N \g__enumext_footnote_starred_int
```

```
\seq_new:N \g__enumext_footnote_standard_arg_seq
\seq_new:N \g__enumext_footnote_starred_arg_seq
\seq_new:N \g__enumext_footnote_standard_int_seq
\seq_new:N \g__enumext_footnote_starred_int_seq
```

(*End of definition for* `\g__enumext_footnote_standard_int` *and others.*)

`\l__enumext_item_starred_X_bool`
`l__enumext_item_column_pos_X_int`
`\g__enumext_item_count_all_X_int`
`\l__enumext_joined_item_X_int`
`\l__enumext_joined_item_aux_X_int`
`\l__enumext_tmpa_X_int`
`\l__enumext_item_text_X_box`
`\l__enumext_joined_width_X_dim`
`\l__enumext_item_width_X_dim`
`\g__enumext_item_symbol_aux_X_tl`
`\l__enumext_align_label_X_str`
`\g__enumext_minipage_active_X_bool`
`\l__enumext_miniright_code_X_box`
`\g__enumext_minipage_center_X_bool`
`\g__enumext_minipage_right_X_dim`

Internal variables used by `enumext*` and `keyans*` environments.

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \bool_new:c { l__enumext_item_starred_#1_bool    }
    \int_new:c  { l__enumext_item_column_pos_#1_int  }
    \int_new:c  { g__enumext_item_count_all_#1_int   }
    \int_new:c  { l__enumext_joined_item_#1_int      }
    \int_new:c  { l__enumext_joined_item_aux_#1_int  }
    \int_new:c  { l__enumext_tmpa_#1_int             }
    \box_new:c  { l__enumext_item_text_#1_box        }
    \dim_new:c  { l__enumext_joined_width_#1_dim     }
    \dim_new:c  { l__enumext_item_width_#1_dim       }
    \tl_new:c   { g__enumext_item_symbol_aux_#1_tl   }
    \str_new:c  { l__enumext_align_label_#1_str      }
    \bool_new:c { g__enumext_minipage_active_#1_bool }
    \box_new:c  { l__enumext_miniright_code_#1_box   }
    \bool_new:c { g__enumext_minipage_center_#1_bool }
    \dim_new:c  { g__enumext_minipage_right_#1_dim   }
  }
\clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }
```

(*End of definition for* `\l__enumext_item_starred_X_bool` *and others.*)

`\c__enumext_all_envs_clist`

An internal `clist-var` variable to run with `\__enumext_tmp:n`.

```
\clist_const:Nn \c__enumext_all_envs_clist
  {
    {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv},
    {keyans}{v}, {enumext*}{vii}, {keyans*}{viii}
  }
```

(*End of definition for* `\c__enumext_all_envs_clist`.)

13.5 Some utility functions

`\keys_precompile:neN`
`\seq_use:NV`

Non-standard kernel variants used by the `\printkeyans` command (§13.50) and `\foreachkeyans` command (§13.53).

```
\cs_generate_variant:Nn \keys_precompile:nnN { neN }
\cs_generate_variant:Nn \seq_use:Nn { NV }
```

(*End of definition for* `\keys_precompile:neN` *and* `\seq_use:NV`.)

`\__enumext_at_begin_document:n`

A internal *"hook"* function used for copying plain `list` and `minipage` environments definition and `hyperref` detection.

```
\cs_new_protected:Nn \__enumext_at_begin_document:n
  {
    \hook_gput_code:nnn {begindocument} {enumext} {#1}
  }
```

(*End of definition for* `\__enumext_at_begin_document:n`.)

`\__enumext_after_env:nn`

An internal *"hook"* function to execute code `mini-right` and `mini-right*` keys outside the `enumext*` and `keyans*` environments and print `check-ans` outside the `enumext` and `enumext*` environments.

```
\cs_new_protected:Nn \__enumext_after_env:nn
  {
    \hook_gput_code:nnn {env/#1/after} {enumext} {#2}
  }
```

(*End of definition for* `\__enumext_after_env:nn`.)

`\__enumext_level:`

Function for check current level in `enumext`.

```
\cs_new:Nn \__enumext_level:
  {
    \int_to_roman:n { \l__enumext_level_int }
  }
```

©2024–2026 by Pablo González L

(*End of definition for* `\__enumext_level:`.)

`\__enumext_if_is_int:nT` `\__enumext_if_is_int:nF` `\__enumext_if_is_int:nTF`

A conditional function to determine whether the variable being passed is an integer used by `start` and `widest` keys. This function is taken directly from the answer given by Henri Menke in How to test if an expl3 function argument is an integer expression?.

```
\prg_new_protected_conditional:Npnn \__enumext_if_is_int:n #1 { T, F, TF }
  {
    \regex_if_match:nnTF { ^[\+\-]?[\d]+$ } {#1} % $
      { \prg_return_true: }
      { \prg_return_false: }
  }
```

(*End of definition for* `\__enumext_if_is_int:nT`, `\__enumext_if_is_int:nF`, *and* `\__enumext_if_is_int:nTF`.)

`\__enumext_show_length:nnn`

Internal function used by `show-length` key to show *"all lengths"* calculated and used in `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```
\cs_new:Nn \__enumext_show_length:nnn
  {
    *~#2
    \prg_replicate:nn { 14 - \str_count:n {#2} } {~}
      =~\use:c { #1_use:c } { l__enumext_#2_#3_#1 } \\
  }
```

(*End of definition for* `\__enumext_show_length:nnn`.)

`\__enumext_unskip_unkern:`

The function `\__enumext_unskip_unkern:` will remove the last ⟨*skip*⟩ or ⟨*kern*⟩ at execution time using the values `11` and `12` of `\lastnodetype` to apply `\unskip` or `\unkern` depending on the case.

```
\cs_new_protected:Nn \__enumext_unskip_unkern:
  {
    \int_case:nnT { \lastnodetype }
      {
        { 11 }{ \unskip }
        { 12 }{ \unkern }
      }
  }
```

(*End of definition for* `\__enumext_unskip_unkern:`.)

13.5.1 Utilities for environments and levels

`\__enumext_is_not_nested:` `\__enumext_is_on_first_level:`

The function `\__enumext_is_not_nested:` sets the variables `\g__enumext_standard_bool` and `\g__enumext_starred_bool` to *"true"* only if the environments `enumext` and `enumext*` are NOT nested in each other and saves the environment name in `\l__enumext_envir_name_tl`.

```
\cs_new_protected:Nn \__enumext_is_not_nested:
  {
    \str_case:en { \@currenvir }
      {
        {enumext}
          {
            \tl_set:Ne \l__enumext_envir_name_tl { enumext }
            \bool_lazy_and:nnT
              { \bool_not_p:n { \g__enumext_standard_bool } }
              { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
              {
                \bool_gset_true:N \g__enumext_standard_bool
              }
          }
        {enumext*}
          {
            \tl_set:Ne \l__enumext_envir_name_tl { enumext* }
            \bool_lazy_and:nnT
              { \bool_not_p:n { \g__enumext_starred_bool } }
              { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
              {
                \bool_gset_true:N \g__enumext_starred_bool
              }
          }
      }
  }
```

The function __enumext_is_on_first_level: will sets the variables \l__enumext_standard_first_bool (§13.29.1), \l__enumext_starred_first_bool (§13.29.1) to *"true"* only if the environment is not nested and it is at the *"first level"*. They also save the *start line number* of each environment in the variable \g__enumext_start_line_tl and the *name* of each environment in the variable \g__enumext_envir_name_tl to use in messages related to the check-ans key and .log file.

```
\cs_new_protected:Nn \__enumext_is_on_first_level:
  {
    \bool_lazy_all:nT
      {
        { \bool_if_p:N \g__enumext_standard_bool }
        { \int_compare_p:nNn { \l__enumext_level_int } = { 1 } }
        { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
      }
      {
        \bool_set_true:N \l__enumext_standard_first_bool
        \tl_gset:Nn \g__enumext_envir_name_tl { enumext }
        \tl_gset:Ne \g__enumext_start_line_tl
          {
            on~line~\exp_not:V \inputlineno
          }
      }
    \bool_lazy_all:nT
      {
        { \bool_if_p:N \g__enumext_starred_bool }
        { \int_compare_p:nNn { \l__enumext_level_h_int } = { 1 } }
        { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
      }
      {
        \bool_set_true:N \l__enumext_starred_first_bool
        \tl_gset:Nn \g__enumext_envir_name_tl { enumext* }
        \tl_gset:Ne \g__enumext_start_line_tl
          {
            on~line~\exp_not:V \inputlineno
          }
      }
  }
```

(*End of definition for* `\__enumext_is_not_nested:` *and* `\__enumext_is_on_first_level:`.)

`\__enumext_keyans_name_and_start:`

The function __enumext_keyans_name_and_start: will save the start line number and name of the environments keyans, keyans* and keyanspic in the variables \l__enumext_check_start_line_env_tl and \l__enumext_envir_name_tl to use in the __enumext_check_starred_cmd:n function.

```
\cs_new_protected:Nn \__enumext_keyans_name_and_start:
  {
    \str_case:en { \@currenvir }
      {
        {keyans}
          {
            \tl_set:Ne \l__enumext_envir_name_tl { keyans }
            \tl_set:Ne \l__enumext_check_start_line_env_tl
              {
                in~'keyans'~start~on~line~\exp_not:V \inputlineno
              }
          }
        {keyans*}
          {
            \tl_set:Ne \l__enumext_envir_name_tl { keyans* }
            \tl_set:Ne \l__enumext_check_start_line_env_tl
              {
                in~'keyans*'~start~on~line~\exp_not:V \inputlineno
              }
          }
        {keyanspic}
          {
            \tl_set:Ne \l__enumext_envir_name_tl { keyanspic }
            \tl_set:Ne \l__enumext_check_start_line_env_tl
              {
                in~'keyanspic'~start~on~line~\exp_not:V \inputlineno
              }
          }
```

©2024–2026 by Pablo González L

```
      }
  }
```

(*End of definition for* `\__enumext_keyans_name_and_start:`.)

13.5.2 Utilities for log and terminal

`\__enumext_reset_global_vars:`
`\__enumext_reset_global_int:`
`\__enumext_reset_global_bool:`
`\__enumext_reset_global_tl:`

The function `\__enumext_reset_global_vars:` will be passed to the function `\__enumext_execute_after_env:` and will return the global variables to their default values after being used.

```
\cs_new_protected:Nn \__enumext_reset_global_vars:
  {
    \__enumext_reset_global_int:
    \__enumext_reset_global_bool:
    \__enumext_reset_global_tl:
  }
\cs_new_protected:Nn \__enumext_reset_global_int:
  {
    \int_gzero:N \g__enumext_item_number_int
    \int_gzero:N \g__enumext_item_anskey_int
    \int_gzero:N \g__enumext_item_answer_diff_int
  }
\cs_new_protected:Nn \__enumext_reset_global_bool:
  {
    \bool_gset_false:N \g__enumext_check_ans_key_bool
    \bool_gset_false:N \g__enumext_standard_bool
    \bool_gset_false:N \g__enumext_starred_bool
  }
\cs_new_protected:Nn \__enumext_reset_global_tl:
  {
    \tl_gclear:N \g__enumext_store_name_tl
    \tl_gclear:N \g__enumext_start_line_tl
    \tl_gclear:N \g__enumext_envir_name_tl
  }
```

(*End of definition for* `\__enumext_reset_global_vars:` *and others.*)

`\__enumext_log_global_vars:`
`\__enumext_log_answer_vars:`

The function `\__enumext_log_global_vars:` will be passed to the function `\__enumext_execute_after_env:` and write to the `.log` file the number of elements saved in the *prop list* and *sequence* created by the `save-ans` key along with the value of the integer variable created for the `resume` key.

```
\cs_new_protected:Nn \__enumext_log_global_vars:
  {
    \msg_log:nneeee { enumext } { prop-seq-int-hook }
      { \g__enumext_store_name_tl }
      { \prop_count:c { g__enumext_ \g__enumext_store_name_tl _prop } }
      { \seq_count:c { g__enumext_ \g__enumext_store_name_tl _seq } }
      { \int_use:c { g__enumext_resume_ \g__enumext_store_name_tl _int } }
  }
```

The function `\__enumext_log_answer_vars:` will be passed to the function `\__enumext_execute_after_env:` and write to the `.log` file the number of items and answers along with the difference between them.

```
\cs_new_protected:Nn \__enumext_log_answer_vars:
  {
    \msg_log:nneee { enumext } { item-answer-hook }
      { \int_use:N \g__enumext_item_number_int }
      { \int_use:N \g__enumext_item_anskey_int }
      { \int_eval:n { \g__enumext_item_number_int - \g__enumext_item_anskey_int} }
  }
```

(*End of definition for* `\__enumext_log_global_vars:` *and* `\__enumext_log_answer_vars:`.)

13.5.3 Definition of error messages

`prop-seq-int-hook`
`item-answer-hook`

Messages written to the `.log` file by the internal hooks that show the values of the global variables.

```
\msg_new:nnn { enumext } { prop-seq-int-hook }
  {
    *~Package~enumext:~Elements~in~
    \c_backslash_str g__enumext_#1_prop~=~#2.\\
    *~Package~enumext:~Elements~in~
    \c_backslash_str g__enumext_#1_seq~=~#3.\\
    *~Package~enumext:~Value~of~
```

```
    \c_backslash_str g__enumext_resume_#1_int~=~#4.
  }
\msg_new:nnn { enumext } { item-answer-hook }
  {
    *~Package~enumext:~Value~of~
    \c_backslash_str g__enumext_item_number_int~=~#1.\\
    *~Package~enumext:~Value~of~
    \c_backslash_str g__enumext_item_anskey_int~=~#2.\\
    *~Package~enumext:~Difference~item_number_int~-~item_anskey_int~=~#3.
  }
```

(*End of definition for* `prop-seq-int-hook` *and* `item-answer-hook`.)

13.6 Copying `list` and `minipage` environments

The `list` environment provided by LaTeX has the following plain form:

```
\list{⟨arg one⟩}{⟨arg two⟩}
  \item[⟨opt⟩]
\endlist
```

And `minipage` environment provided by LaTeX has the following (simplified) plain form:

```
\minipage[⟨pos⟩][⟨height⟩][⟨inner-pos⟩]{⟨width⟩}
  ⟨internal implement⟩
\endminipage
```

As a precaution they are copied using `\__enumext_at_begin_document:n` in case any package redefines the `list` environment or a related command.

For compatibility with *tagged* PDF, `\NewCommandCopy` should be used and not `\cs_new_eq:NN` for `\item`. When *tagged* PDF is active `\item` is redefined using `ltcmd` (see `latex-lab-block`[19]).

`\__enumext_start_list:nn`
`\__enumext_stop_list:`
`\__enumext_item_std:w`
`\__enumext_minipage:w`
`\__enumext_endminipage:`

The functions `\__enumext_start_list:nn` and `\__enumext_stop_list:` correspond to copies of `\list` and `\endlist` from plain definition of `list` environment, the function `\__enumext_item_std:w` is a copy of the `\item` command.

```
\__enumext_at_begin_document:n
  {
    \cs_new_eq:NN   \__enumext_start_list:nn \list
    \cs_new_eq:NN   \__enumext_stop_list: \endlist
    \NewCommandCopy \__enumext_item_std:w \item
  }
```

The functions `\__enumext_minipage:w` and `\__enumext_endminipage:` correspond to copies of `\minipage` and `\endminipage` from plain definition of `minipage` environment.

```
\__enumext_at_begin_document:n
  {
    \cs_new_eq:NN \__enumext_minipage:w \minipage
    \cs_new_eq:NN \__enumext_endminipage: \endminipage
  }
```

(*End of definition for* `\__enumext_start_list:nn` *and others.*)

13.7 Compatibility with hyperref and footnotehyper

`\__enumext_after_hyperref:`
`\__enumext_hypertarget:nn`
`\__enumext_phantomsection:`

First, the necessary rules are defined using *"hooks"* to determine if the `hyperref` package is loaded.

```
\hook_gput_code:nnn { begindocument } { enumext } { \__enumext_after_hyperref: }
\hook_gset_rule:nnnn { begindocument } { enumext } { after } { hyperref }
```

The function `\__enumext_after_hyperref:` sets the state of the boolean variable `\l__enumext_hyperref_bool` to "true" if the package is loaded. The public macro `\IfHyperBoolean` determines if the `hyperfootnotes=true` key is present, and if so, the boolean variable `\l__enumext_footnotes_key_bool` is set to "true".

```
\cs_new_protected:Nn \__enumext_after_hyperref:
  {
    \IfPackageLoadedT { hyperref }
      {
        \msg_info:nnn { enumext } { package-load } { hyperref }
        \bool_set_true:N \l__enumext_hyperref_bool
        \IfHyperBoolean{hyperfootnotes}
          {
            \bool_set_true:N \l__enumext_footnotes_key_bool
```

```
            }
            {  }
        }
```

If the variable \l__enumext_footnotes_key_bool is true, it checks whether the package footnotehyper is loaded; if it is not, \l__enumext_footnotes_key_bool is set to false and \footnote is redefined.

```
\bool_if:NT \l__enumext_footnotes_key_bool
  {
    \IfPackageLoadedTF { footnotehyper }
      {
        \msg_info:nnn { enumext } { package-load } { footnotehyper }
      }
      {
        \bool_set_false:N \l__enumext_footnotes_key_bool
      }
  }
```

The functions __enumext_hypertarget:nn and __enumext_phantomsection: correspond to the internal copies of \hypertarget and \phantomsection. If the boolean variable \l__enumext_hyperref_bool is false the functions __enumext_hypertarget:nn and __enumext_phantomsection: will be disabled.

```
    \bool_if:NTF \l__enumext_hyperref_bool
      {
        \cs_new_eq:NN \__enumext_hypertarget:nn \hypertarget
        \cs_new_eq:NN \__enumext_phantomsection: \phantomsection
      }
      {
        \cs_new_eq:NN \__enumext_hypertarget:nn \use_none:nn
        \cs_new_eq:NN \__enumext_phantomsection: \prg_do_nothing:
      }
  }
```

(*End of definition for* __enumext_after_hyperref:, __enumext_hypertarget:nn, *and* __enumext_phantomsection:.)

__enumext_newlabel:nn

The function __enumext_newlabel:nn write the information to the .aux file when using the save-ref key. The arguments taken by the function are:

#1 : \l__enumext_newlabel_arg_one_tl
#2 : \l__enumext_newlabel_arg_two_tl

The trick here is to manage the number of arguments passed to \newlabel{#1}{#2} according to the presence of the hyperref package.

```
\cs_new_protected:Nn \__enumext_newlabel:nn
  {
    \protected@write \@auxout { }
      {
        \token_to_str:N \newlabel {#1}
          {
            {#2}
            \bool_if:NT \l__enumext_hyperref_bool
              { { \thepage } {#2} {#1} }
            { }
          }
      }
    \__enumext_hypertarget:nn {#1} { }
    \__enumext_phantomsection:
  }
```

(*End of definition for* __enumext_newlabel:nn.)

13.8 Internal redefining \footnote command

To keep the correct numbering of \footnote and to make it work correctly in the enumext* and keyans* environments and mini-env key it is necessary to redefine the \footnote command. This implementation is adapted from the answer given by Clea F. Rees (@cfr) in footnotes in boxes compatible with hyperref.

__enumext_footnotetext:nn
__enumext_renew_footnote:
__enumext_print_footnote:
__enumext_renew_footnote_mini:
__enumext_print_footnote_mini:

Redefinition of the \footnote command using \footnotetext and \footnotemark for the mini-env key in the enumext and keyans environments.

```
\cs_new_protected:Nn \__enumext_footnotetext:nn
  {
    \footnotetext[#1]{#2}
```

```
  }
\cs_new_protected:Nn \__enumext_renew_footnote:
  {
    \RenewDocumentCommand \footnote { o +m }
      {
        \tl_if_novalue:nTF {##1}
          {
            \stepcounter{footnote}
            \int_gset_eq:Nc \g__enumext_footnote_standard_int { c@footnote }
          }
          {
            \int_gset:Nn \g__enumext_footnote_standard_int {##1}
          }
        \footnotemark [ \g__enumext_footnote_standard_int ]
        \seq_gput_right:Nn \g__enumext_footnote_standard_arg_seq {##2}
        \seq_gput_right:NV
          \g__enumext_footnote_standard_int_seq \g__enumext_footnote_standard_int
      }
  }
\cs_new_protected:Nn \__enumext_print_footnote:
  {
    \seq_if_empty:NF \g__enumext_footnote_standard_int_seq
      {
        \seq_map_pairwise_function:NNN
          \g__enumext_footnote_standard_int_seq
          \g__enumext_footnote_standard_arg_seq
          \__enumext_footnotetext:nn
      }
    \seq_gclear:N \g__enumext_footnote_standard_arg_seq
    \seq_gclear:N \g__enumext_footnote_standard_int_seq
  }
```

The `enumext*` and `keyans*` environments are implemented using `minipage`, so `\footnote` must also be redefined to keep these numbering as if it were part of the document.

```
\cs_new_protected:Nn \__enumext_renew_footnote_mini:
  {
    \RenewDocumentCommand \footnote { o +m }
      {
        \tl_if_novalue:nTF {##1}
          {
            \stepcounter{footnote}
            \int_gset_eq:Nc \g__enumext_footnote_starred_int { c@footnote }
          }
          {
            \int_gset:Nn \g__enumext_footnote_starred_int {##1}
          }
        \footnotemark [ \g__enumext_footnote_starred_int ]
        \seq_gput_right:Nn \g__enumext_footnote_starred_arg_seq {##2}
        \seq_gput_right:NV
          \g__enumext_footnote_starred_int_seq \g__enumext_footnote_starred_int
      }
  }
\cs_new_protected:Nn \__enumext_print_footnote_mini:
  {
    \seq_if_empty:NF \g__enumext_footnote_starred_int_seq
      {
        \seq_map_pairwise_function:NNN
          \g__enumext_footnote_starred_int_seq
          \g__enumext_footnote_starred_arg_seq
          \__enumext_footnotetext:nn
      }
    \seq_gclear:N \g__enumext_footnote_starred_arg_seq
    \seq_gclear:N \g__enumext_footnote_starred_int_seq
  }
```

(*End of definition for* `\__enumext_footnotetext:nn` *and others.*)

`\__enumext_renew_footnote_standard:`
`\__enumext_print_footnote_standard:`
`\__enumext_renew_footnote_starred:`
`\__enumext_print_footnote_starred:`

The redefinition of `\footnote` is encapsulated to pass it to the internal `\__enumext_mini_page` environment used by the `mini-env` key in the `enumext` and `keyans` environments. It is executed when *tagged* PDF is active or when the `footnotehyper` package is not loaded.

```
\cs_new_protected:Nn \__enumext_renew_footnote_standard:
```

```
  {
    \bool_if:NT \g__enumext_standard_bool
      {
        \IfDocumentMetadataTF
          {
            \__enumext_renew_footnote:
          }
          {
            \bool_if:NF \l__enumext_footnotes_key_bool
              {
                \__enumext_renew_footnote:
              }
          }
      }
  }
\cs_new_protected:Nn \__enumext_print_footnote_standard:
  {
    \bool_if:NT \g__enumext_standard_bool
      {
        \IfDocumentMetadataTF
          {
            \__enumext_print_footnote:
          }
          {
            \bool_if:NF \l__enumext_footnotes_key_bool
              {
                \__enumext_print_footnote:
              }
          }
      }
  }
```

The redefinition of `\footnote` is encapsulated to pass it to the `enumext*` and `keyans*` environments. It is executed when *tagged* PDF is active or when the `footnotehyper` package is not loaded.

```
\cs_new_protected:Nn \__enumext_renew_footnote_starred:
  {
    \IfDocumentMetadataTF
      {
        \__enumext_renew_footnote_mini:
      }
      {
        \bool_if:NF \l__enumext_footnotes_key_bool
          {
            \__enumext_renew_footnote_mini:
          }
      }
  }
\cs_new_protected:Nn \__enumext_print_footnote_starred:
  {
    \IfDocumentMetadataTF
      {
        \__enumext_print_footnote_mini:
      }
      {
        \bool_if:NF \l__enumext_footnotes_key_bool
          {
            \__enumext_print_footnote_mini:
          }
      }
  }
```

In `enumext*` and `keyans*` environments it is necessary to use *"hooks"* to print `\footnote` with support for *tagged* PDF.

```
\__enumext_after_env:nn { enumext* }
  {
    \__enumext_print_footnote_starred:
  }
\__enumext_after_env:nn { keyans* }
  {
    \__enumext_print_footnote_starred:
  }
```

©2024–2026 by Pablo González L

(*End of definition for* `\__enumext_renew_footnote_standard:` *and others.*)

13.9 The internal `minipage` environment

`\__enumext_internal_mini_page:`
`\__enumext_mini_page`

The function `\__enumext_internal_mini_page:` creates an internal `\__enumext_mini_page` environment (*custom version* of `minipage`) setting the `\if@minipage` switch to *"false"* to allow spaces at the *"above"* of the environment, plus `\skip_vertical:N \c_zero_skip` is added to maintain alignment on *"top"* in the first part and `\skip_vertical:N \c_zero_skip` in the second part to allow spaces *"below"*. This environment will be used internally by the `mini-env` key, it is NOT documented in the user interface and is for internal use only. Within this environment `\footnote` is redefined to make the notes look the same as if they were elsewhere in the document. This implementation is adapted from the answer given by Max Chernoff (`@MaxChernoff`) in Customize `minipage` to support spaces below it.

This function is passed to the function `\__enumext_safe_exec:` in the `enumext` environment definition (§13.42) and `\__enumext_safe_exec_vii:` in the `enumext*` environment definition (§13.47).

```
\cs_new_protected:Nn \__enumext_internal_mini_page:
  {
    \int_compare:nNnT { \l__enumext_level_int } = { 0 }
      {
        \DeclareDocumentEnvironment{__enumext_mini_page}{ m }
          {
            \__enumext_renew_footnote_standard:
            \__enumext_minipage:w [ t ] {##1}
              \legacy_if_gset_false:n { @minipage }
              \skip_vertical:N \c_zero_skip
          }
          {
              \skip_vertical:N \c_zero_skip
            \__enumext_endminipage:
            \__enumext_print_footnote_standard:
          }
      }
  }
```

(*End of definition for* `\__enumext_internal_mini_page:` *and* `\__enumext_mini_page`.)

13.10 Definition of public dimension

The package enumext only provides a single public dimension `\itemwidth` and is intended for user convenience only and is not for internal use as such. This dimension is set in all environments and is only used by the `wrap-ans` key at its default value.

```
\dim_zero_new:N \itemwidth
```

13.11 Definition of counters

`\__enumext_define_counter:Nn`
`enumXi`
`enumXii`
`enumXiii`
`enumXiv`
`enumXv`
`enumXvi`
`enumXvii`
`enumXviii`

To create the necessary *"counters"*, the function first checks that they are not already defined by the user or a package such as `enumitem`; otherwise it returns an error and aborts the package loading. The arguments taken by the function are:

`#1` : A token list `\l__enumext_counter_X_tl` for *"store"* the counter's name.
`#2` : The counter's name.

```
\cs_new_protected:Nn \__enumext_define_counter:Nn
  {
    \cs_if_exist:cTF { c@ #2 }
      { \msg_fatal:nnn { enumext } { counters }{#2} }
      {
        \tl_set:Nn #1 {#2}
        \newcounter {#2}
      }
  }
```

The counters created here are `enumXi`, `enumXii`, `enumXiii` and `enumXiv` for `enumext` environment, `enumXv` for `keyans` environment, `enumXvi` for `keyanspic` environment, `enumXvii` for `enumext*` and `enumXviii` for the `keyans*` environments.

```
\__enumext_define_counter:Nn \l__enumext_counter_i_tl    { enumXi    }
\__enumext_define_counter:Nn \l__enumext_counter_ii_tl   { enumXii   }
\__enumext_define_counter:Nn \l__enumext_counter_iii_tl  { enumXiii  }
\__enumext_define_counter:Nn \l__enumext_counter_iv_tl   { enumXiv   }
\__enumext_define_counter:Nn \l__enumext_counter_v_tl    { enumXv    }
\__enumext_define_counter:Nn \l__enumext_counter_vi_tl   { enumXvi   }
```

©2024–2026 by Pablo González L

```
\__enumext_define_counter:Nn \l__enumext_counter_vii_tl  { enumXvii  }
\__enumext_define_counter:Nn \l__enumext_counter_viii_tl { enumXviii }
```

(*End of definition for* `\__enumext_define_counter:Nn` *and others.*)

`\c@__enumext_resume_i_int` `\c@__enumext_resume_ii_int` `\c@__enumext_resume_iii_int` `\c@__enumext_resume_iv_int` `\c@__enumext_resume_vii_int`

In version 1.6 the command `\resetenumext` (§13.27) was added which internally uses `\counterwithin*` so for its correct operation, *"real counters"* are created instead of the *"integer variables"* for the keys `resume` and `resume*`.

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \cs_if_exist:cTF { c@ __enumext_resume_#1_int }
      { \msg_fatal:nne { enumext } { counters }{ __enumext_resume_#1_int } }
      {
        \newcounter { __enumext_resume_#1_int }
      }
  }
\clist_map_inline:nn {i,ii,iii,iv,vii} { \__enumext_tmp:n {#1} }
```

(*End of definition for* `\c@__enumext_resume_i_int` *and others.*)

13.11.1 Definition of error messages

`counters` Message used in the creation of counters by enumext package.

```
\msg_new:nnn { enumext } { counters }
  {
    The~counter~'#1'~is~already~defined~by~some\\
    package~or~macro,~it~cannot~be~continued.
  }
```

(*End of definition for* `counters`.)

13.12 Definition of labels

This part of the code is inspired by the `enumitem` package. The idea is to be able to access the counters using `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` to use them in the `label` key.

Direct support for this is provided since LaTeX release 2025-06-01[13], but the original implementation is kept so as not to hinder the internal *"label and ref"* system.

`\__enumext_register_default_label_wd:Nn` These ⟨*counters*⟩ will be used as default ⟨*labels*⟩ if the `label` key is not used for the different levels of the `enumext`, `enumext*`, `keyans` and `keyans*` environments, so it is necessary to get a default value for `labelwidth` from these ⟨*labels*⟩ at the same time.

```
\cs_new_protected:Nn \__enumext_register_default_label_wd:Nn
  {
    \tl_const:cn { c__enumext_widest_ \cs_to_str:N #1 _tl } {#2}
    \tl_gput_right:Nn \g__enumext_counter_styles_tl {#1}
  }
\__enumext_register_default_label_wd:Nn \arabic { 0 }
\__enumext_register_default_label_wd:Nn \Alph   { M }
\__enumext_register_default_label_wd:Nn \alph   { m }
\__enumext_register_default_label_wd:Nn \Roman  { VIII }
\__enumext_register_default_label_wd:Nn \roman  { viii }
```

(*End of definition for* `\__enumext_register_default_label_wd:Nn`.)

`\__enumext_label_width_by_box:Nn` `\__enumext_label_width_by_box:cv` The function `\__enumext_label_width_by_box:Nn` set the default `\labelwidth` using a box width if no `labelwidth` key is passed.

```
\cs_new_protected:Nn \__enumext_label_width_by_box:Nn
  {
    \hbox_set:Nn \l__enumext_label_width_by_box {#2}
    \dim_set:Nn #1 { \box_wd:N \l__enumext_label_width_by_box }
  }
\cs_generate_variant:Nn \__enumext_label_width_by_box:Nn { cv }
```

(*End of definition for* `\__enumext_label_width_by_box:Nn`.)

`\__enumext_label_style:Nnn` `\__enumext_label_style:cvn` The function `\__enumext_label_style:Nnn` is used by the `label` key to create the variables containing the ⟨*label style*⟩ and allows using `\arabic*`, `\Alph*`, `\alph*`, `\Roman*` and `\roman*` as arguments.

It loops through the defined counter styles in \g__enumext_counter_styles_tl (\arabic, \alph, \Alph, \roman and \Roman) for example, looking for \roman* and replacing that by \roman{⟨*counter*⟩}, and doing the same for the \g__enumext_widest_label_tl to keep both in sync.

```
\cs_new_protected:Nn \__enumext_label_style:Nnn
  {
    \tl_clear_new:N #1
    \tl_put_right:Ne #1 { \tl_trim_spaces:n {#3} }
    \tl_gset_eq:NN \g__enumext_widest_label_tl #1
    \tl_map_inline:Nn \g__enumext_counter_styles_tl
      {
        \tl_replace_all:Nne #1 { ##1* } { \exp_not:N ##1 {#2} }
        \tl_greplace_all:Nne \g__enumext_widest_label_tl { ##1* }
          { \tl_use:c { c__enumext_widest_ \cs_to_str:N ##1 _tl } }
      }
    \__enumext_label_width_by_box:Nn \l__enumext_current_widest_dim
      { \tl_use:N \g__enumext_widest_label_tl }
    \tl_set_eq:cN { the #2 } #1
  }
\cs_generate_variant:Nn \__enumext_label_style:Nnn { cvn }
```

(*End of definition for* __enumext_label_style:Nnn.)

13.13 Setting keys associated with label

When *tagged* PDF is active \makelabel is redefined using \makebox to work correctly (§13.37). From the user side it is convenient to have a key that allows using this redefinition with \makebox without having \IfDocumentMetadataTF active.

mode-box Defines the key mode-box only for the *"first level"* of enumext and enumext* environments.

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \keys_define:nn { enumext /  #1 }
      {
        mode-box .bool_set:N = \l__enumext_mode_box_bool,
        mode-box .initial:n = false,
        mode-box .value_forbidden:n = true,
      }
  }
\clist_map_inline:nn { level-1, enumext* } { \__enumext_tmp:n {#1} }
```

(*End of definition for* mode-box.)

font
labelsep
labelwidth
wrap-label
wrap-label* Definition of keys font, labelsep, labelwidth, wrap-label and wrap-label* keys for enumext and keyans environments.

```
\cs_set_protected:Nn \__enumext_tmp:nn
  {
    \keys_define:nn { enumext / #1 }
      {
        font        .tl_set:c = { l__enumext_label_font_style_#2_tl },
        font        .value_required:n = true,
        labelsep    .dim_set:c = { l__enumext_labelsep_#2_dim },
        labelsep    .initial:n = {0.3333em},
        labelsep    .value_required:n = true,
        labelwidth  .dim_set:c = { l__enumext_labelwidth_#2_dim },
        labelwidth  .value_required:n = true,
        wrap-label  .cs_set_protected:cp = { __enumext_wrapper_label_#2:n } ##1,
        wrap-label  .initial:n = {##1},
        wrap-label  .value_required:n = true,
        wrap-label* .code:n =
          {
            \bool_set_true:c { l__enumext_wrap_label_opt_#2_bool }
            \keys_set:nn { enumext / #1 } { wrap-label = {##1} }
          },
        wrap-label* .value_required:n = true,
      }
  }
\clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }
```

(*End of definition for* font *and others.*)

©2024–2026 by Pablo González L

align The align key is implemented differently for *"starred"* and *"non starred"* environments. For compatibility with *tagged* PDF it is necessary to set \l__enumext_align_label_pos_X_str.

```
\cs_set_protected:Nn \__enumext_tmp:nn
  {
    \keys_define:nn { enumext / #1 }
      {
        align .choices:nn =
          { left , right , center }
          {
            \int_case:nn { \l_keys_choice_int }
              {
                {1}
                  {
                    \tl_clear:c { l__enumext_label_fill_left_#2_tl  }
                    \tl_set:cn  { l__enumext_label_fill_right_#2_tl } { \hfill }
                    \str_set:cn { l__enumext_align_label_pos_#2_str } { l }
                  }
                {2}
                  {
                    \tl_set:cn  { l__enumext_label_fill_left_#2_tl  } { \hfill }
                    \tl_clear:c { l__enumext_label_fill_right_#2_tl }
                    \str_set:cn { l__enumext_align_label_pos_#2_str } { r }
                  }
                {3}
                  {
                    \tl_set:cn { l__enumext_label_fill_left_#2_tl  } { \hfill }
                    \tl_set:cn { l__enumext_label_fill_right_#2_tl } { \hfill }
                    \str_set:cn { l__enumext_align_label_pos_#2_str } { c }
                  }
              }
          },
        align .initial:n = left,
        align .value_required:n = true,
        align / unknown .code:n =
          \msg_error:nneee { enumext } { unknown-choice }
            { align } { left,~right,~ center } { \exp_not:n {##1} },
      }
  }
\clist_map_inline:nn
  {
    {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {keyans}{v}
  }
  { \__enumext_tmp:nn #1 }

\cs_set_protected:Nn \__enumext_tmp:nn
  {
    \keys_define:nn { enumext / #1 }
      {
        align .choices:nn =
          { left , right , center }
          {
            \int_case:nn { \l_keys_choice_int }
              {
                {1} { \str_set:cn { l__enumext_align_label_#2_str } { l } }
                {2} { \str_set:cn { l__enumext_align_label_#2_str } { r } }
                {3} { \str_set:cn { l__enumext_align_label_#2_str } { c } }
              }
          },
        align .initial:n = left,
        align .value_required:n = true,
        align / unknown .code:n =
          \msg_error:nneee { enumext } { unknown-choice }
            { align } { left,~right,~ center } { \exp_not:n {##1} },
      }
  }
\clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }
```

(*End of definition for* align.)

13.14 Setting `label` and `ref` keys

The implementation of the keys `label` and `ref` are part of the core of the package enumext, here the default values for ⟨*label*⟩, the value of the variables `\l__enumext_label_X_tl`, the default values for `\labelwidth` and the *"label and ref"* system.

13.14.1 Define and set `label` and `ref` keys for `enumext` environment

`label` `ref` `\l__enumext_label_i_tl` `\l__enumext_label_ii_tl` `\l__enumext_label_iii_tl` `\l__enumext_label_iv_tl`

Sets the default ⟨*labels*⟩ of the *four levels* of enumext environment, along with the default values for `labelwidth`, `widest` and `ref` keys.

```
\cs_set_protected:Nn \__enumext_tmp:nnn
  {
    \keys_define:nn { enumext / #1 }
      {
        label .code:n =
          {
            \__enumext_label_style:cvn { l__enumext_label_#2_tl }
              { l__enumext_counter_#2_tl } {##1}
            \dim_set_eq:cN  { l__enumext_labelwidth_#2_dim }
              \l__enumext_current_widest_dim
          },
        label .initial:n = #3,
        label .value_required:n = true,
        ref   .code:n = { \__enumext_standard_ref:nn {#2} {##1} },
        ref   .value_required:n = true,
      }
  }
\__enumext_tmp:nnn { level-1 } {   i } { \arabic*.}
\__enumext_tmp:nnn { level-2 } {  ii } { (\alph*) }
\__enumext_tmp:nnn { level-3 } { iii } { \roman*. }
\__enumext_tmp:nnn { level-4 } {  iv } { \Alph*.  }
```

(*End of definition for* `label` *and others.*)

`\__enumext_standard_ref:nn` `\__enumext_standard_ref:`

The `\__enumext_standard_ref:nn` function will first pass the key *argument* `ref` to the variable `\l__enumext_ref_key_arg_tl` and analyze its state, if it is not *empty* it will set a copy of of the *current counter style* save in `\l__enumext_the_counter_X_tl` to `\l__enumext_ref_the_count_tl` and then set the variable `\l__enumext_renew_counter_X_tl` which will modify `\theenumX`.

```
\cs_new_protected:Nn \__enumext_standard_ref:nn
  {
    \tl_set:Nn \l__enumext_ref_key_arg_tl {#2}
    \tl_if_empty:NTF \l__enumext_ref_key_arg_tl
      {
        \msg_error:nnn { enumext } { key-ref-empty } { enumext }
      }
      {
        \tl_set_eq:Nc \l__enumext_ref_the_count_tl { l__enumext_the_counter_#1_tl }
        \tl_set:ce { l__enumext_renew_counter_#1_tl }
          {
            \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_the_count_tl }
              { \exp_not:V \l__enumext_ref_key_arg_tl }
          }
      }
  }
```

Finally the function `\__enumext_standard_ref:` will execute the modification for the reference system in the second argument of the environment definition enumext.

```
\cs_new_protected:Nn \__enumext_standard_ref:
  {
    \tl_if_empty:cF { l__enumext_renew_counter_ \__enumext_level: _tl }
      {
        \tl_use:c { l__enumext_renew_counter_ \__enumext_level: _tl }
      }
  }
```

(*End of definition for* `\__enumext_standard_ref:nn` *and* `\__enumext_standard_ref:`.)

13.14.2 Define and set `label` and `ref` keys for `enumext*` and `keyans*` environments

`label` `ref` `\l__enumext_label_vii_tl` `\l__enumext_label_viii_tl`

Sets the default ⟨*labels*⟩ for enumext* and keyans* environments, along with the default value for `labelwidth` key and `ref` key.

```
\cs_set_protected:Nn \__enumext_tmp:nnn
```

```
  {
    \keys_define:nn { enumext / #1 }
      {
        label .code:n =
          {
            \__enumext_label_style:cvn { l__enumext_label_#2_tl }
              { l__enumext_counter_#2_tl } {##1}
            \dim_set_eq:cN  { l__enumext_labelwidth_#2_dim }
                \l__enumext_current_widest_dim
          },
        label .initial:n = #3,
        label .value_required:n = true,
        ref   .code:n = { \__enumext_starred_ref:n {##1} },
        ref   .value_required:n = true,
      }
  }
\__enumext_tmp:nnn { enumext* } {  vii } { \arabic*.}
\__enumext_tmp:nnn { keyans*  } { viii } { \Alph*) }
```

(*End of definition for* `label` *and others.*)

`\__enumext_starred_ref:n`
`\__enumext_starred_ref:`

The implementation of `\__enumext_starred_ref:n` is the same as that used for the environment `enumext`.

```
\cs_new_protected:Nn \__enumext_starred_ref:n
  {
    \tl_set:Nn \l__enumext_ref_key_arg_tl {#1}
    \int_compare:nNnT { \l__enumext_level_h_int } = { 1 }
      {
        \tl_if_empty:NTF \l__enumext_ref_key_arg_tl
          {
            \msg_error:nnn { enumext } { key-ref-empty } { enumext* }
          }
          {
            \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_the_counter_vii_tl
            \tl_set:Ne \l__enumext_renew_counter_vii_tl
              {
                \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_the_count_tl }
                  { \exp_not:V \l__enumext_ref_key_arg_tl }
              }
          }
      }
    \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
      {
        \tl_if_empty:NTF \l__enumext_ref_key_arg_tl
          {
            \msg_error:nnn { enumext } { key-ref-empty } { keyans* }
          }
          {
            \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_the_counter_viii_tl
            \tl_set:Ne \l__enumext_renew_counter_viii_tl
              {
                \exp_not:N \renewcommand  { \exp_not:V \l__enumext_ref_the_count_tl }
                  { \exp_not:V \l__enumext_ref_key_arg_tl }
              }
          }
      }
  }
```

Finally the function `\__enumext_starred_ref:` will execute the modification for the reference system in the second argument of the `enumext*` and `keyans*` environment definition.

```
\cs_new_protected:Nn \__enumext_starred_ref:
  {
    \int_compare:nNnT { \l__enumext_level_h_int } = { 1 }
      {
        \tl_if_empty:NF \l__enumext_renew_counter_vii_tl
          {
            \tl_use:N \l__enumext_renew_counter_vii_tl
          }
      }
    \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
      {
        \tl_if_empty:NF \l__enumext_renew_counter_viii_tl
```

```
862           {
863             \tl_use:N \l__enumext_renew_counter_viii_tl
864           }
865       }
866   }
```

(*End of definition for* `\__enumext_starred_ref:n` *and* `\__enumext_starred_ref:`.)

13.14.3 Define and set `label` and `ref` keys for `keyans` and `keyanspic` environments

`label` `ref` `\l__enumext_label_v_tl` `\l__enumext_label_vi_tl`

Sets the default ⟨*label*⟩ for `keyans` and `keyanspic` environment, along with the default value for `labelwidth` if it has not been established and `ref` key. The `keyanspic` environment use the same ⟨*label*⟩ as the `keyans` environment.

```
867 \keys_define:nn { enumext / keyans }
868   {
869     label .code:n =
870       {
871         \__enumext_label_style:cvn { l__enumext_label_v_tl }
872           { l__enumext_counter_v_tl } {#1}
873         \__enumext_label_style:cvn { l__enumext_label_vi_tl }
874           { l__enumext_counter_vi_tl } {#1}
875         \dim_set_eq:NN
876           \l__enumext_labelwidth_v_dim \l__enumext_current_widest_dim
877       },
878     label .initial:n = \Alph*),
879     label .value_required:n = true,
880     ref   .code:n = { \__enumext_keyans_ref:n {#1} },
881     ref   .value_required:n = true,
882   }
```

(*End of definition for* `label` *and others.*)

`\__enumext_keyans_ref:n` `\__enumext_keyans_ref:`

The implementation of `\__enumext_keyans_ref:n` is the same as that used for the environment `enumext`.

```
883 \cs_new_protected:Nn \__enumext_keyans_ref:n
884   {
885     \tl_set:Nn \l__enumext_ref_key_arg_tl {#1}
886     \tl_if_empty:NTF \l__enumext_ref_key_arg_tl
887       {
888         \msg_error:nnn { enumext } { key-ref-empty } { keyans }
889       }
890       {
891         \tl_set_eq:NN \l__enumext_ref_the_count_tl \l__enumext_the_counter_v_tl
892         \tl_put_right:Ne \l__enumext_renew_counter_v_tl
893           {
894             \exp_not:N \renewcommand { \exp_not:V \l__enumext_ref_the_count_tl }
895               { \exp_not:V \l__enumext_ref_key_arg_tl }
896           }
897       }
898   }
```

Finally the function `\__enumext_keyans_ref:` will execute the modification for the reference system in the second argument of the `keyans*` environment definition.

```
899 \cs_new_protected:Nn \__enumext_keyans_ref:
900   {
901     \tl_if_empty:NF \l__enumext_renew_counter_v_tl
902       {
903         \tl_use:N \l__enumext_renew_counter_v_tl
904       }
905   }
```

(*End of definition for* `\__enumext_keyans_ref:n` *and* `\__enumext_keyans_ref:`.)

13.14.4 Definition of error messages

`key-ref-empty`

Messages used by `ref` key.

```
906 \msg_new:nnn { enumext } { key-ref-empty }
907   {
908     Key~'ref'~needs~a~value~in~'#1'~\msg_line_context:.
909   }
```

(*End of definition for* `key-ref-empty`.)

©2024–2026 by Pablo González L

13.15 Setting `start`, `start*` and `widest` keys

`\__enumext_start_from:NNn`
`\__enumext_start_from:ccn`
`\__enumext_start_from:cce`

The function `\__enumext_start_from:NNn` used by `start` and `start*` keys take three arguments:

`#1:` `\l__enumext_label_X_tl`
`#2:` `\l__enumext_start_X_int`
`#3:` ⟨*integer or string*⟩

The first argument of this function are the *"counter style"* set by `label` key, the second argument is returned by the function, the third argument can be an ⟨*integer*⟩ or ⟨*string*⟩ of the form `\Alph`, `\alph`, `\Roman` or `\roman`. This effectively allows `start*=A` or `start=1` to be used.

In version 1.6 it is allowed to pass the `resume` key *without value* by means of the command `\setenumext`, for the correct operation of this, the boolean variable `\l__enumext_resume_count_bool` set by the `resume` key *without value* must be set to *"false"* (§13.26). This is necessary to be able to "reset" the *start value* by means of the `start` or `start*` keys.

```
\cs_new_protected:Nn \__enumext_start_from:NNn
  {
    \bool_set_false:N \l__enumext_resume_count_bool
    \__enumext_if_is_int:nTF {#3}
      {
        \int_set:Nn #2 {#3}
      }
      {
        \regex_if_match:nVT { \c{Alph} | \c{alph} } #1
          { \int_set:Nn #2 { \int_from_alph:n {#3} } }
        \regex_if_match:nVT { \c{Roman} | \c{roman} } #1
          { \int_set:Nn #2  { \int_from_roman:n {#3} } }
      }
  }
\cs_generate_variant:Nn \__enumext_start_from:NNn { ccn, cce }
```

(*End of definition for* `\__enumext_start_from:NNn`.)

`\__enumext_widest_from:nNNn`
`\__enumext_widest_from:nccn`

The function `\__enumext_widest_from:nNNn` used by the `widest` key take four arguments:

`#1:` The counter associated with the environment level
`#2:` `\l__enumext_label_X_tl`
`#3:` `\l__enumext_labelwidth_X_dim`
`#4:` ⟨*integer or string*⟩

The second and third arguments of this function are the values set by `label` and `labelwidth` keys, the four argument can be an ⟨*integer*⟩ or ⟨*string*⟩ of the form `\Alph`, `\alph`, `\Roman` or `\roman`. The value of the four argument is set temporarily for the identified counter in this point (level), then the value is expanded into a *"box"* and the *"width"* of the *"box"* is returned.

```
\cs_new_protected:Nn \__enumext_widest_from:nNNn
  {
    \__enumext_if_is_int:nTF {#4}
      {
        \setcounter{enumX#1} {#4}
      }
      {
        \regex_if_match:nVT { \c{Alph} | \c{alph} } #2
          { \setcounter{enumX#1} { \int_from_alph:n {#4} } }
        \regex_if_match:nVT { \c{Alph} | \c{alph} } #2
          { \setcounter{enumX#1} { \int_from_roman:n {#4} } }
      }
    \__enumext_label_width_by_box:cv
      { l__enumext_labelwidth_#1_dim } { l__enumext_label_#1_tl }
  }
\cs_generate_variant:Nn \__enumext_widest_from:nNNn { nccn }
```

(*End of definition for* `\__enumext_widest_from:nNNn`.)

`start`
`start*`
`widest`

Now define and set `start*`, `start` and `widest` keys for `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```
\cs_set_protected:Nn \__enumext_tmp:nn
  {
    \keys_define:nn { enumext / #1 }
      {
        start* .code:n =
          {
```

```
            \__enumext_start_from:ccn
              { l__enumext_label_#2_tl }
              { l__enumext_start_#2_int } {##1}
          },
        start* .value_required:n = true,
        start  .code:n =
          {
            \__enumext_start_from:cce
              { l__enumext_label_#2_tl }
              { l__enumext_start_#2_int } { \int_eval:n {##1} }
          },
        start  .initial:n = 1,
        start  .value_required:n = true,
        widest .code:n =
          {
            \__enumext_widest_from:nccn {#2}
              { l__enumext_label_#2_tl }
              { l__enumext_labelwidth_#2_dim } {##1}
          },
        widest .value_required:n = true,
      }
  }
\clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }
```

(*End of definition for* `start`, `start*`, *and* `widest`.)

13.16 Setting keys for penalties

beginpenalty
midpenalty
endpenalty

The three parameters \@beginparpenalty, \@itempenalty and \@endparpenalty work together to ensure that list environments look good, avoiding unsightly page breaks that can break the flow of the list, so it's a good idea to have a ⟨*keys*⟩ to access these.

```
\cs_set_protected:Nn \__enumext_tmp:nn
  {
    \keys_define:nn { enumext / #1 }
      {
        beginpenalty .int_set:c = { l__enumext_beginparpenalty_#2_int },
        beginpenalty .initial:n = -51,
        beginpenalty .value_required:n = true,
        midpenalty   .int_set:c = { l__enumext_itempenalty_#2_int },
        midpenalty   .initial:n = -51,
        midpenalty   .value_required:n = true,
        endpenalty   .int_set:c = { l__enumext_endparpenalty_#2_int },
        endpenalty   .initial:n = -51,
        endpenalty   .value_required:n = true,
      }
  }
\clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }
```

(*End of definition for* `beginpenalty`, `midpenalty`, *and* `endpenalty`.)

13.17 Setting keys for vertical spaces

topsep
partopsep
parsep
itemsep
noitemsep
nosep

Define and set topsep, partopsep, parsep, itemsep, noitemsep and nosep keys for enumext, enumext*, keyans and keyans* environments.

```
\cs_set_protected:Nn \__enumext_tmp:nnnnnn
  {
    \keys_define:nn { enumext / #1 }
      {
        topsep    .skip_set:c = { l__enumext_topsep_#2_skip },
        topsep    .initial:n = {#3},
        topsep    .value_required:n = true,
        partopsep .skip_set:c = { l__enumext_partopsep_#2_skip },
        partopsep .initial:n = {#4},
        partopsep .value_required:n = true,
        parsep    .skip_set:c = { l__enumext_parsep_#2_skip },
        parsep    .initial:n = {#5},
        parsep    .value_required:n = true,
        itemsep   .skip_set:c = { l__enumext_itemsep_#2_skip },
        itemsep   .initial:n = {#6},
        itemsep   .value_required:n = true,
```

```
      noitemsep .meta:n = { itemsep = 0pt, parsep = 0pt },
      noitemsep .value_forbidden:n = true,
      nosep     .meta:n =
        { itemsep = 0pt, parsep = 0pt, topsep = 0pt, partopsep = 0pt },
      nosep     .value_forbidden:n = true,
    }
}
```

Now the values are set based on the standard `article` class in `10pt`.

```
\__enumext_tmp:nnnnnn { level-1 } { i } { 8.0pt plus 2.0pt minus 4.0pt }
  { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
  { 4.0pt plus 2.0pt minus 1.0pt }
\__enumext_tmp:nnnnnn { level-2 } { ii } { 4.0pt plus 2.0pt minus 1.0pt }
  { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
  { 2.0pt plus 1.0pt minus 1.0pt }
\__enumext_tmp:nnnnnn { level-3 } { iii } { 2.0pt plus 1.0pt minus 1.0pt }
  { 1.0pt minus 1.0pt }{ 0pt }{ 2.0pt plus 1.0pt minus 1.0pt }
\__enumext_tmp:nnnnnn { level-4 } { iv } { 2.0pt plus 1.0pt minus 1.0pt }
  { 1.0pt minus 1.0pt }{ 0pt }{ 2.0pt plus 1.0pt minus 1.0pt }
\__enumext_tmp:nnnnnn { keyans  } { v }{ 4.0pt plus 2.0pt minus 1.0pt }
  { 2.0pt plus 1.0pt minus 1.0pt }{ 2.0pt plus 1.0pt minus 1.0pt }
  { 2.0pt plus 1.0pt minus 1.0pt }
\__enumext_tmp:nnnnnn { enumext* } { vii } { 8.0pt plus 2.0pt minus 4.0pt }
  { 2.0pt plus 1.0pt minus 1.0pt } { 4.0pt plus 2.0pt minus 1.0pt }
  { 4.0pt plus 2.0pt minus 1.0pt }
\__enumext_tmp:nnnnnn { keyans* } { viii } { 4.0pt plus 2.0pt minus 1.0pt }
  { 2.0pt plus 1.0pt minus 1.0pt } { 2.0pt plus 1.0pt minus 1.0pt }
  { 2.0pt plus 1.0pt minus 1.0pt }
```

(*End of definition for* `topsep` *and others.*)

13.18 Setting `base-fix` key

When nesting starting right after `\item` (without material between them) there is a problem with the alignment of the *baseline* between the two environments. One way to get around this problem is to place `\mode_leave_vertical:` apply `\vspace{-\baselineskip}` and set `\topsep=0pt` for the *"first level"* of the nested `enumext` environment.

`base-fix` Defines the key `base-fix` only for the *"first level"* of `enumext` environment.

`\__enumext_nested_base_line_fix:`

```
\keys_define:nn { enumext /  level-1 }
  {
    base-fix .bool_set:N = \l__enumext_base_line_fix_bool,
    base-fix .initial:n = false,
    base-fix .value_forbidden:n = true,
  }
```

The function `\__enumext_nested_base_line_fix:` passed to the `\__enumext_parse_keys:n` function in the definition of the `enumext` environment (§13.42) will be responsible for applying the *baseline correction* and adjusting the ⟨*keys*⟩ for the `enumext` environment and the `\printkeyans` with *starred argument* '`*`' (§13.50).

First, the function code is implemented from the user side of the `base-fix` key, that is, only the user knows when it is necessary to apply it within the document in which case the variable `\l__enumext_print_keyans_star_bool` set by the `\printkeyans` command is false and the variable `\l__enumext_base_line_fix_bool` is true.

Sets the values of the keys `topsep`, `above` and `above*` for the *"first level"* of `enumext` environment equal to `0pt` and finally sets the variable `\l__enumext_base_line_fix_bool` to false.

```
\cs_new_protected:Nn \__enumext_nested_base_line_fix:
  {
    \bool_lazy_all:nT
      {
        { \bool_if_p:N \l__enumext_starred_first_bool }
        { \bool_if_p:N \l__enumext_base_line_fix_bool }
        { \bool_not_p:n { \l__enumext_print_keyans_star_bool } }
      }
      {
        \mode_leave_vertical:
        \vspace { -\dim_eval:n { \baselineskip + \parsep } }
        \keys_set:nn { enumext / level-1 }
          {
```

```
            topsep = 0pt, above = 0pt, above* = 0pt,
          }
      }
```

When the \printkeyans command is run with the *starred argument* '*' the variable \l__enumext_print_keyans_sta is true and a simplified version of \vspace can be run using \skip_vertical:n.

```
    \bool_lazy_and:nnT
      { \bool_if_p:N \l__enumext_starred_first_bool }
      { \bool_if_p:N \l__enumext_print_keyans_star_bool }
      {
        \mode_leave_vertical:
        \skip_vertical:n { -\baselineskip }
        \skip_vertical:N \c_zero_skip
        \keys_set:nn { enumext / level-1 }
          {
            topsep = 0pt, above = 0pt, above* = 0pt,
          }
      }
    \bool_set_false:N \l__enumext_base_line_fix_bool
  }
```

(*End of definition for* base-fix *and* __enumext_nested_base_line_fix:.)

13.19 Setting keys for horizontal spaces

itemindent
rightmargin
listparindent
list-offset
list-indent

Define and set itemindent, rightmargin, listparindent, list-offset and list-indent keys for enumext, enumext*, keyans and keyans* environments.

```
\cs_set_protected:Nn \__enumext_tmp:nn
  {
    \keys_define:nn { enumext / #1 }
      {
        itemindent    .dim_set:c = { l__enumext_fake_item_indent_#2_dim },
        itemindent    .value_required:n = true,
        rightmargin   .dim_set:c = { l__enumext_rightmargin_#2_dim },
        rightmargin   .value_required:n = true,
        listparindent .dim_set:c = { l__enumext_listparindent_#2_dim },
        listparindent .value_required:n = true,
        list-offset   .dim_set:c = { l__enumext_listoffset_#2_dim },
        list-offset   .value_required:n = true,
        list-indent   .code:n =
          {
            \bool_set_true:c { l__enumext_leftmargin_tmp_#2_bool }
            \dim_set:cn { l__enumext_leftmargin_tmp_#2_dim } {##1}
          },
        list-indent   .value_required:n = true,
      }
  }
\clist_map_inline:nn
  {
    {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {keyans}{v}
  }
  { \__enumext_tmp:nn #1 }
```

For enumext* and keyans* environments the situation is a bit different, the list-indent key behaves like the list-offset key.

```
\cs_set_protected:Nn \__enumext_tmp:nn
  {
    \keys_define:nn { enumext / #1 }
      {
        itemindent    .dim_set:c = { l__enumext_fake_item_indent_#2_dim },
        itemindent    .value_required:n = true,
        rightmargin   .dim_set:c = { l__enumext_rightmargin_#2_dim },
        rightmargin   .value_required:n = true,
        listparindent .dim_set:c = { l__enumext_listparindent_#2_dim },
        listparindent .value_required:n = true,
        list-offset   .dim_set:c = { l__enumext_listoffset_#2_dim },
        list-offset   .value_required:n = true,
        list-indent   .meta:n = { list-offset = ##1 },
        list-indent   .value_required:n = true,
      }
  }
```

©2024–2026 by Pablo González L

```
\clist_map_inline:nn
  {
    {enumext*}{vii}, {keyans*}{viii}
  }
  { \__enumext_tmp:nn #1 }
```

(*End of definition for* `itemindent` *and others.*)

13.19.1 Functions for setting the fake `itemindent`

`\__enumext_fake_item_indent:`
`\__enumext_keyans_fake_item_indent:`
`\__enumext_fake_item_indent_vii:`
`\__enumext_fake_item_indent_viii:`

The `itemindent` key does not set the value of `\itemindent`, it only sets the value of the *horizontal space* applied using `\skip_horizontal:N`. This value is stored in the variable and only applied when it is greater than `0pt`. Here it is necessary to place `\mode_leave_vertical:` and the plain TEX macro `\ignorespaces` to avoid unwanted extra space when using the `itemindent` key.

```
\cs_set_protected:Nn \__enumext_fake_item_indent:
  {
    \dim_compare:nNnT
      { \dim_use:c { l__enumext_fake_item_indent_ \__enumext_level: _dim } }
      >
      { \c_zero_dim }
      {
        \tl_set:ce { l__enumext_fake_item_indent_ \__enumext_level: _tl }
          {
            \exp_not:N \mode_leave_vertical:
            \exp_not:n { \skip_horizontal:n }
              { \dim_use:c { l__enumext_fake_item_indent_ \__enumext_level: _dim } }
            \exp_not:N \ignorespaces
          }
      }
  }
\cs_set_protected:Nn \__enumext_keyans_fake_item_indent:
  {
    \dim_compare:nNnT
      { \l__enumext_fake_item_indent_v_dim } > { \c_zero_dim }
      {
        \tl_set:Ne \l__enumext_fake_item_indent_v_tl
          {
            \exp_not:N \mode_leave_vertical:
            \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_v_dim
            \exp_not:N \ignorespaces
          }
      }
  }
\cs_set_protected:Nn \__enumext_fake_item_indent_vii:
  {
    \dim_compare:nNnT
      { \l__enumext_fake_item_indent_vii_dim } > { \c_zero_dim }
      {
        \tl_set:Ne \l__enumext_fake_item_indent_vii_tl
          {
            \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_vii_dim
            \exp_not:N \ignorespaces
          }
      }
  }
\cs_set_protected:Nn \__enumext_fake_item_indent_viii:
  {
    \dim_compare:nNnT
      { \l__enumext_fake_item_indent_viii_dim } > { \c_zero_dim }
      {
        \tl_set:Ne \l__enumext_fake_item_indent_viii_tl
          {
            \exp_not:N \skip_horizontal:N \l__enumext_fake_item_indent_viii_dim
            \exp_not:N \ignorespaces
          }
      }
  }
```

(*End of definition for* `\__enumext_fake_item_indent:` *and others.*)

13.20 Setting show-length key

show-length

Define and set show-length key for enumext, enumext*, keyans and keyans* environments. The function sets the boolean variable \l__enumext_show_length_X_bool used in the definition of all environments to *"true"* and calls the function __enumext_show_length:nnn which prints all the values of the *"vertical"* and *"horizontal"* parameters calculated and used.

```
\cs_set_protected:Nn \__enumext_tmp:nn
  {
    \keys_define:nn { enumext / #1 }
      {
        show-length .bool_set:c = { l__enumext_show_length_#2_bool },
        show-length .initial:n = false,
      }
  }
\clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }
```

(*End of definition for* show-length.)

13.21 Setting before, after and first keys

before
before*
after
first

Define and set before, before*, after and first keys for enumext, enumext*, keyans and keyans* environments.

```
\cs_set_protected:Nn \__enumext_tmp:nn
  {
    \keys_define:nn { enumext / #1 }
      {
        before  .tl_set:c = { l__enumext_before_no_starred_key_#2_tl },
        before  .value_required:n = true,
        before* .tl_set:c = { l__enumext_before_starred_key_#2_tl },
        before* .value_required:n = true,
        after   .tl_set:c = { l__enumext_after_stop_list_#2_tl },
        after   .value_required:n = true,
        first   .tl_set:c = { l__enumext_after_list_args_#2_tl },
        first   .value_required:n = true,
      }
  }
\clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }
```

(*End of definition for* before *and others.*)

13.21.1 Functions for before, after and first keys in enumext

__enumext_before_args_exec:
__enumext_before_keys_exec:
__enumext_after_stop_list:
__enumext_after_args_exec:

The function __enumext_before_args_exec: executes the {⟨*code*⟩} set by the before* key *"before"* the enumext environment is started. The {⟨*code*⟩} is executed *"without"* knowing any definition of the {⟨*arg two*⟩} of the list: {⟨*code*⟩}\list{⟨*arg one*⟩}{⟨*arg two*⟩}.

```
\cs_new_protected:Nn \__enumext_before_args_exec:
  {
    \tl_use:c { l__enumext_before_starred_key_ \__enumext_level: _tl }
  }
```

The function __enumext_before_keys_exec: executes the {⟨*code*⟩} set by the before key *"before"* the enumext environment is started in *second argument* of the list. The {⟨*code*⟩} is executed *"knowing"* all definition and values provides by ⟨*keys*⟩: \list{⟨*arg one*⟩}{⟨*arg two*⟩{⟨*code*⟩}}

```
\cs_new_protected:Nn \__enumext_before_keys_exec:
  {
    \tl_use:c { l__enumext_before_no_starred_key_ \__enumext_level: _tl }
  }
```

The function __enumext_after_stop_list: executes the {⟨*code*⟩} set by the after key *"after"* the enumext environment has finished: \endlist{⟨*code*⟩}.

```
\cs_new_protected:Nn \__enumext_after_stop_list:
  {
    \tl_use:c { l__enumext_after_stop_list_ \__enumext_level: _tl }
  }
```

The function __enumext_after_args_exec: executes the {⟨*code*⟩} set by the first key after the end of the second argument of the list defining the enumext environment, just before the first occurrence of \item: \list{⟨*arg one*⟩}{⟨*arg two*⟩}{⟨*code*⟩}\item.

```
\cs_new_protected:Nn \__enumext_after_args_exec:
```

```
    {
      \tl_use:c { l__enumext_after_list_args_ \__enumext_level: _tl }
    }
```

(*End of definition for* `\__enumext_before_args_exec:` *and others.*)

13.21.2 Functions for `before`, `after` and `first` keys in `keyans`

`\__enumext_before_args_exec_v:`
`\__enumext_before_keys_exec_v:`
`\__enumext_after_stop_list_v:`
`\__enumext_after_args_exec_v:`

Same implementation as the one used in the `enumext` environment.

```
\cs_new_protected:Nn \__enumext_before_args_exec_v:
  {
    \tl_use:N \l__enumext_before_starred_key_v_tl
  }
\cs_new_protected:Nn \__enumext_before_keys_exec_v:
  {
    \tl_use:N \l__enumext_before_no_starred_key_v_tl
  }
\cs_new_protected:Nn \__enumext_after_stop_list_v:
  {
    \tl_use:N \l__enumext_after_stop_list_v_tl
  }
\cs_new_protected:Nn \__enumext_after_args_exec_v:
  {
    \tl_use:N \l__enumext_after_list_args_v_tl
  }
```

(*End of definition for* `\__enumext_before_args_exec_v:` *and others.*)

13.21.3 Functions for `before`, `after` and `first` keys in `enumext*` and `keyans*`

`\__enumext_before_args_exec_vii:`
`\__enumext_before_args_exec_viii:`
`\__enumext_before_keys_exec_vii:`
`\__enumext_before_keys_exec_viii:`
`\__enumext_after_stop_list_vii:`
`\__enumext_after_stop_list_viii:`

Same implementation as the one used in the `enumext` environment, except that there are no `\__enumext_after_args_exec_vii:` and `\__enumext_after_args_exec_viii:` functions: the {⟨*code*⟩} set by the `first` key is used directly by `\__enumext_start_item_vii:w` and `\__enumext_start_item_viii:w`, inside the `minipage` of each `\item`.

```
\cs_new_protected:Nn \__enumext_before_args_exec_vii:
  {
    \tl_use:N \l__enumext_before_starred_key_vii_tl
  }
\cs_new_protected:Nn \__enumext_before_args_exec_viii:
  {
    \tl_use:N \l__enumext_before_starred_key_viii_tl
  }
\cs_new_protected:Nn \__enumext_before_keys_exec_vii:
  {
    \tl_use:N \l__enumext_before_no_starred_key_vii_tl
  }
\cs_new_protected:Nn \__enumext_before_keys_exec_viii:
  {
    \tl_use:N \l__enumext_before_no_starred_key_viii_tl
  }
\cs_new_protected:Nn \__enumext_after_stop_list_vii:
  {
    \tl_use:N \l__enumext_after_stop_list_vii_tl
  }
\cs_new_protected:Nn \__enumext_after_stop_list_viii:
  {
    \tl_use:N \l__enumext_after_stop_list_viii_tl
  }
```

(*End of definition for* `\__enumext_before_args_exec_vii:` *and others.*)

13.22 Setting keys for `multicols` and `minipage`

`mini-env`
`mini-sep`
`columns-sep`
`columns`
`mini-right`
`mini-right*`

The default value of the `columns-sep` key is handled by the state of the boolean variable `\l__enumext_columns_sep_X_bool` which is handled in the internal definition of the `enumext` and `keyans` environments. Define and set `mini-env`, `mini-sep`, `columns-sep` and `columns` keys for `enumext`, `enumext*`, `keyans` and `keyans*` environments.

```
\cs_set_protected:Nn \__enumext_tmp:nn
  {
    \keys_define:nn { enumext / #1 }
      {
```

```
      mini-env     .dim_set:c = { l__enumext_minipage_right_#2_dim },
      mini-env     .value_required:n = true,
      mini-sep     .dim_set:c = { l__enumext_minipage_hsep_#2_dim },
      mini-sep     .initial:n = 0.3333em,
      mini-sep     .value_required:n = true,
      columns-sep  .dim_set:c = { l__enumext_columns_sep_#2_dim },
      columns-sep  .value_required:n = true,
      columns      .int_set:c = { l__enumext_columns_#2_int },
      columns      .initial:n = 1,
      columns      .value_required:n = true,
    }
  }
\clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }
```

For `enumext*` and `keyans*` environments the situation is a bit different, the command `\miniright` is not available, so the keys `mini-right` and `mini-right*` are added to implement support for `minipage` environment.

```
\cs_set_protected:Nn \__enumext_tmp:nn
  {
    \keys_define:nn { enumext / #1 }
      {
        mini-right  .tl_gset:c = { g__enumext_miniright_code_#2_tl },
        mini-right  .value_required:n = true,
        mini-right* .code:n =
          {
            \bool_gset_true:c { g__enumext_minipage_center_#2_bool }
            \keys_set:nn { enumext / #1 } { mini-right = {##1} }
          },
        mini-right* .value_required:n = true,
      }
  }
\clist_map_inline:nn { {enumext*}{vii}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }
```

(*End of definition for* `mini-env` *and others.*)

13.23 Adjustment of vertical spaces for `multicols`

When nesting a *"list environment"* inside the `multicols` environment, the values of the *"vertical spaces"* are lost, basically the `multicols` environment takes control over them. Graphically, this can be seen in figure 7.



Figure 7: Representation of the vertical space in `multicols` for a nested level.

To keep the desired spaces *above* and *below* in the *"list environment"* (`\topsep` + `[\partopsep]`) it is necessary to *"adjust"* the spaces added by the `multicols` environment. The most appropriate option in this case is to use a *"context sensitive"* vertical space with `\addvspace`.

It should be made clear that the implementation here is a *"bit questionable"*. At first glance doing `\multicolsep=\topsep` seemed right, but the results were not always as expected. An almost *imperceptible* detail is that in some cases the `\itemsep` values of are *"stretched"*, possibly due to the use of `\raggedcolumns` and this affects the lower space when closing the environment, which is *"smaller"* than expected. My attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

13.23.1 Adjustment of vertical spaces for `multicols` in `enumext`

`\__enumext_multi_set_vskip:`

The function `\__enumext_multi_set_vskip:` will take care of determining the *"adjusted spaces"* applied *"above"* and *"below"* the `multicols` environment in `enumext`.

The default values are set taking into account that TEX is in ⟨*horizontal mode*⟩, then the settings for the ⟨*vertical mode*⟩, in which `\partopsep` comes into play, are made.

Set the values of `\l__enumext_multicols_above_X_skip` and `\l__enumext_multicols_below_X_skip` equal to the value of `\topsep` in the *current level.*

```
\cs_new_protected:Nn \__enumext_multi_set_vskip:
  {
    \skip_set:cn { l__enumext_multicols_above_ \__enumext_level: _skip }
      {
        \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
```

```
    }
  \skip_set:cn { l__enumext_multicols_below_ \__enumext_level: _skip }
    {
      \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
    }
  \__enumext_add_pre_parsep:
}
```

(*End of definition for* `\__enumext_multi_set_vskip:`.)

`\__enumext_add_pre_parsep:` The function `\__enumext_add_pre_parsep:` *"adjusted"* the value of `\l__enumext_multicols_above_X_skip` detecting the value of `\parsep` from the previous level. This is necessary since `\parsep` from the previous level affects the *vertical spaces*.

```
\cs_new_protected:Nn \__enumext_add_pre_parsep:
  {
    \int_case:nn { \l__enumext_level_int }
      {
        { 2 }{
               \skip_if_eq:nnF { \l__enumext_parsep_i_skip } { \c_zero_skip }
                 {
                   \skip_add:Nn \l__enumext_multicols_above_ii_skip
                     {
                       \l__enumext_parsep_i_skip
                     }
                 }
        }
        { 3 }{
               \skip_if_eq:nnF { \l__enumext_parsep_ii_skip } { \c_zero_skip }
                 {
                   \skip_add:Nn \l__enumext_multicols_above_iii_skip
                     {
                       \l__enumext_parsep_ii_skip
                     }
                 }
        }
        { 4 }{
               \skip_if_eq:nnF { \l__enumext_parsep_iii_skip } { \c_zero_skip }
                 {
                   \skip_add:Nn \l__enumext_multicols_above_iv_skip
                     {
                       \l__enumext_parsep_iii_skip
                     }
                 }
        }
      }
  }
```

(*End of definition for* `\__enumext_add_pre_parsep:`.)

`\__enumext_multi_addvspace:` The function `\__enumext_multi_addvspace:` will apply the spaces set using `\addvspace` *"above"* the `multicols` environment in `enumext`, taking into account whether TEX is in ⟨*horizontal mode*⟩ or ⟨*vertical mode*⟩.

```
\cs_new_protected:Nn \__enumext_multi_addvspace:
  {
    \__enumext_multi_set_vskip:
    \mode_if_vertical:T
      {
        \skip_add:cn { l__enumext_multicols_above_ \__enumext_level: _skip }
          {
            \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
          }
        \skip_add:cn { l__enumext_multicols_below_ \__enumext_level: _skip }
          {
            \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
          }
      }
    \par\nopagebreak
    \addvspace{ \skip_use:c { l__enumext_multicols_above_ \__enumext_level: _skip } }
  }
```

(*End of definition for* `\__enumext_multi_addvspace:`.)

©2024–2026 by Pablo González L

13.23.2 Adjustment of vertical spaces for `multicols` in `keyans`

__enumext_keyans_multi_set_vskip:
__enumext_keyans_multi_addvspace:

The function `\__enumext_keyans_multi_set_vskip:` will take care of determining the *"adjusted spaces"* applied *"above"* and *"below"* the `multicols` environment in `keyans`. The implementation of this function is the same as the one used in `enumext`.

```
\cs_new_protected:Nn \__enumext_keyans_multi_set_vskip:
  {
    \skip_set:Nn \l__enumext_multicols_above_v_skip
      {
        \l__enumext_topsep_v_skip
      }
    \skip_set:Nn \l__enumext_multicols_below_v_skip
      {
        \l__enumext_topsep_v_skip
      }
  }
\cs_new_protected:Nn \__enumext_keyans_multi_addvspace:
  {
    \__enumext_keyans_multi_set_vskip:
    \mode_if_vertical:T
      {
        \skip_add:Nn \l__enumext_multicols_above_v_skip
          {
            \skip_use:N \l__enumext_partopsep_v_skip
          }
        \skip_add:Nn \l__enumext_multicols_below_v_skip
          {
            \skip_use:N \l__enumext_partopsep_v_skip
          }
      }
    \par\nopagebreak
    \addvspace{ \l__enumext_multicols_above_v_skip }
  }
```

(*End of definition for* `\__enumext_keyans_multi_set_vskip:` *and* `\__enumext_keyans_multi_addvspace:`.)

13.24 Adjustment of vertical spaces for `minipage`

When nesting a *"list environment"* within the `minipage` environment, the values of the *"vertical spaces"* are lost. Graphically it can be seen like in the figure 8.



Figure 8: Representation of the `minipage` spacing adjustment for a nested level.

To keep the *"left"* and *"right"* environments *"aligned on top"*, preserving the `\baselineskip` and keeping the desired *"spaces"* (`\topsep + [\partopsep]`) it is necessary to *"adjust"* the *"vertical spaces"* for `minipage` environments.

Here there are several complications that must be circumvented: the `minipage` environment eliminates the "top" spaces, the `multicols` environment can be nested in the `minipage` environment, the "top" and "bottom" spaces are affected when `topsep=0pt` and to this is added the `\partopsep` parameter that comes into action according to whether TEX is in ⟨*horizontal mode*⟩ or ⟨*vertical mode*⟩. Depending on these cases, small adjustments must be made using `\vspace` and `\addvspace` to obtain the *"desired vertical spacing"*.

Again, it must be made clear that the implementation here is a *"bit questionable"*, but hunting the spaces (`glue`) produced by the `minipage` environment is quite complicated, even more if `multicols` it is nested. The setting of the values was more *"trial and error"* (approx to `\strutbox`), using the help of the `lua-visual-debug`[15] package, again the attempts to find the correct values using `\showoutput` and `\showboxdepth` absolutely failed.

13.24.1 Adjustment of vertical spaces for `minipage` in `enumext`

__enumext_minipage_set_skip:
__enumext_minipage_add_space:

The function `\__enumext_minipage_set_skip:` will take care of determining the *"adjust"* spaces applied *"above"* and *"below"* the `\__enumext_mini_page` environment in `enumext`.

First it sets the value of `\l__enumext_minipage_right_skip` equal to `\topsep`, then checks if TEX is in ⟨*vertical mode*⟩ and, if so, adds `\partopsep`, followed by setting the value of `\l__enumext_minipage_after_skip`.

```
\cs_new_protected:Nn \__enumext_minipage_set_skip:
```

```
  {
    \skip_set:Nn \l__enumext_minipage_right_skip
      {
        \skip_use:c { l__enumext_topsep_ \__enumext_level: _skip }
      }
    \mode_if_vertical:T
      {
        \skip_add:Nn \l__enumext_minipage_right_skip
          {
            \skip_use:c { l__enumext_partopsep_ \__enumext_level: _skip }
          }
      }
    \skip_set_eq:NN \l__enumext_minipage_after_skip \l__enumext_minipage_right_skip
```

Adjusts the values `\l__enumext_multicols_above_X_skip` and `\l__enumext_multicols_below_X_skip` and calls the function `\__enumext_pre_itemsep_skip:`.

```
    \skip_set_eq:cN
      { l__enumext_multicols_above_ \__enumext_level: _skip } \l__enumext_minipage_right_skip
    \skip_set_eq:cN
      { l__enumext_multicols_below_ \__enumext_level: _skip } \l__enumext_minipage_right_skip
    \__enumext_pre_itemsep_skip:
```

If the environment `multicols` is active, it sets `\topskip=0pt` and then makes `\multicolsep` have the same value as `\l__enumext_multicols_above_X_skip`.

```
    \int_compare:nNnT
      { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
      {
        \skip_zero:N \topskip
        \skip_set_eq:Nc \multicolsep { l__enumext_multicols_above_ \__enumext_level: _skip }
      }
  }
```

The function `\__enumext_minipage_add_space:` will apply the spaces on the *"left side"* using `\addvspace` *"above"* the `\__enumext_mini_page` environment, taking into account whether TEX is in ⟨*horizontal mode*⟩ or ⟨*vertical mode*⟩. Here the plain TEX macro `\nointerlineskip` is used to prevent baseline *"glue"* being added between the next pair of boxes in a *vertical list.* For the latter some adjustments are made since the `\partopsep` parameter comes into play and this affects the *vertical spacing.*

```
\cs_new_protected:Nn \__enumext_minipage_add_space:
  {
    \__enumext_minipage_set_skip:
    \__enumext_unskip_unkern:
    \mode_if_vertical:TF
      {
        \nopagebreak\nointerlineskip
      }
      {
        \par\nopagebreak\nointerlineskip
        \skip_zero:c { l__enumext_partopsep_ \__enumext_level: _skip }
      }
    \int_compare:nNnTF
      { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
      {
        \addvspace{ 0.445\box_ht:N \strutbox }
      }
      {
        \addvspace{ 0.250\box_ht:N \strutbox }
      }
  }
```

(*End of definition for* `\__enumext_minipage_set_skip:` *and* `\__enumext_minipage_add_space:`.)

`\__enumext_pre_itemsep_skip:`

The function `\__enumext_pre_itemsep_skip:` will adjust the spaces below the environment `minipage` and the environment `multicols` if it is nested in it, taking into account the value of `\itemsep` from the previous level.

```
\cs_new_protected:Nn \__enumext_pre_itemsep_skip:
  {
    \int_case:nn { \l__enumext_level_int }
      {
        { 2 }{
              \skip_if_eq:nnTF
```

©2024–2026 by Pablo González L

```
                { \l__enumext_itemsep_i_skip } { \l__enumext_minipage_after_skip }
                {
                  \skip_set:Nn \l__enumext_minipage_after_skip
                    { 0.150\box_ht:N \strutbox }
                  \skip_set:Nn \l__enumext_multicols_below_ii_skip
                    { 0.350\box_ht:N \strutbox }
                }
                {
                  \dim_compare:nNnT
                    { \l__enumext_itemsep_i_skip } < { \l__enumext_minipage_after_skip }
                    {
                      \skip_sub:Nn
                        \l__enumext_minipage_after_skip { \l__enumext_itemsep_i_skip }
                      \skip_sub:Nn
                        \l__enumext_multicols_below_ii_skip { \l__enumext_itemsep_i_skip }
                      \skip_add:Nn
                        \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
                      \skip_add:Nn
                        \l__enumext_multicols_below_ii_skip
                          { 0.350\box_ht:N \strutbox }
                    }
                  \dim_compare:nNnT
                    { \l__enumext_itemsep_i_skip } > { \l__enumext_minipage_after_skip }
                    {
                      \skip_set:Nn \l__enumext_minipage_temp_skip
                        {
                          \l__enumext_itemsep_i_skip - \l__enumext_minipage_after_skip
                        }
                      \skip_sub:Nn
                        \l__enumext_minipage_after_skip { \l__enumext_itemsep_i_skip }
                      \skip_sub:Nn
                        \l__enumext_multicols_below_ii_skip { \l__enumext_itemsep_i_skip }
                      \skip_add:Nn
                        \l__enumext_minipage_after_skip
                        { 0.150\box_ht:N \strutbox + \l__enumext_minipage_temp_skip }
                      \skip_add:Nn
                        \l__enumext_multicols_below_ii_skip
                        { 0.350\box_ht:N \strutbox + \l__enumext_minipage_temp_skip }
                    }
                }
        }
        { 3 }{
                \skip_if_eq:nnTF
                  { \l__enumext_itemsep_ii_skip } { \c_zero_skip }
                  {
                    \skip_set:Nn \l__enumext_minipage_after_skip
                      { 0.150\box_ht:N \strutbox }
                    \skip_set:Nn \l__enumext_multicols_below_iii_skip
                      { 0.350\box_ht:N \strutbox }
                  }
                  {
                    \dim_compare:nNnT
                      { \l__enumext_itemsep_ii_skip } < { \l__enumext_minipage_after_skip }
                      {
                        \skip_sub:Nn
                          \l__enumext_minipage_after_skip { \l__enumext_itemsep_ii_skip }
                        \skip_sub:Nn
                          \l__enumext_multicols_below_iii_skip
                            { \l__enumext_itemsep_ii_skip }
                        \skip_add:Nn
                          \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
                        \skip_add:Nn
                          \l__enumext_multicols_below_iii_skip
                            { 0.350\box_ht:N \strutbox }
                      }
                    \dim_compare:nNnT
                      { \l__enumext_itemsep_ii_skip } > { \l__enumext_minipage_after_skip }
                      {
                        \skip_set:Nn \l__enumext_minipage_temp_skip
                          {
                            \l__enumext_itemsep_ii_skip - \l__enumext_minipage_after_skip
```

```
                    }
                  \skip_sub:Nn
                    \l__enumext_minipage_after_skip { \l__enumext_itemsep_ii_skip }
                  \skip_sub:Nn
                    \l__enumext_multicols_below_iii_skip
                      { \l__enumext_itemsep_ii_skip }
                  \skip_add:Nn
                    \l__enumext_minipage_after_skip
                    { 0.150\box_ht:N \strutbox + \l__enumext_minipage_temp_skip }
                  \skip_add:Nn
                    \l__enumext_multicols_below_iii_skip
                    { 0.350\box_ht:N \strutbox + \l__enumext_minipage_temp_skip }
                }
            }
        }
        { 4 }{
              \skip_if_eq:nnTF { \l__enumext_itemsep_iii_skip } { \c_zero_skip }
                {
                  \skip_set:Nn \l__enumext_minipage_after_skip
                    { 0.150\box_ht:N \strutbox }
                  \skip_set:Nn \l__enumext_multicols_below_iv_skip
                    { 0.350\box_ht:N \strutbox }
                }
                {
                  \dim_compare:nNnT
                    { \l__enumext_itemsep_iii_skip } < { \l__enumext_minipage_after_skip }
                    {
                      \skip_sub:Nn
                        \l__enumext_minipage_after_skip { \l__enumext_itemsep_iii_skip }
                      \skip_sub:Nn
                        \l__enumext_multicols_below_iv_skip
                          { \l__enumext_itemsep_iii_skip }
                      \skip_add:Nn
                        \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
                      \skip_add:Nn
                        \l__enumext_multicols_below_iv_skip
                          { 0.350\box_ht:N \strutbox }
                    }
                  \dim_compare:nNnT
                    { \l__enumext_itemsep_iii_skip } > { \l__enumext_minipage_after_skip }
                    {
                      \skip_set:Nn \l__enumext_minipage_temp_skip
                        {
                          \l__enumext_itemsep_iii_skip - \l__enumext_minipage_after_skip
                        }
                      \skip_sub:Nn
                        \l__enumext_minipage_after_skip { \l__enumext_itemsep_iii_skip }
                      \skip_sub:Nn
                        \l__enumext_multicols_below_iv_skip
                          { \l__enumext_itemsep_iii_skip }
                      \skip_add:Nn
                        \l__enumext_minipage_after_skip
                        { 0.150\box_ht:N \strutbox + \l__enumext_minipage_temp_skip }
                      \skip_add:Nn
                        \l__enumext_multicols_below_iv_skip
                        { 0.350\box_ht:N \strutbox + \l__enumext_minipage_temp_skip }
                    }
                }
        }
      }
  }
```

(*End of definition for* `\__enumext_pre_itemsep_skip:`.)

13.24.2 Adjustment of vertical spaces for `minipage` in keyans

`\__enumext_keyans_minipage_set_skip:`
`\__enumext_keyans_minipage_add_space:`
`\__enumext_keyans_pre_itemsep_skip:`

The function `\__enumext_keyans_mini_set_vskip:` will take care of determining the "adjusted" spaces applied *"above"* and *"below"* the `\__enumext_mini_page` environment in keyans. The implementation of this function is the same as the one used in enumext.

```
\cs_new_protected:Nn \__enumext_keyans_minipage_set_skip:
  {
```

```
    \skip_zero:N \l__enumext_minipage_after_skip
    \skip_zero:N \l__enumext_minipage_left_skip
    \skip_zero:N \l__enumext_minipage_right_skip
    \skip_set:Nn \l__enumext_minipage_right_skip
      {
        \l__enumext_topsep_v_skip
      }
    \mode_if_vertical:T
      {
        \skip_add:Nn \l__enumext_minipage_right_skip
          {
            \l__enumext_partopsep_v_skip
          }
      }
    \skip_set_eq:NN \l__enumext_minipage_after_skip \l__enumext_minipage_right_skip
    \skip_set_eq:NN \l__enumext_multicols_above_v_skip \l__enumext_minipage_right_skip
    \skip_set_eq:NN \l__enumext_multicols_below_v_skip \l__enumext_minipage_right_skip
    \__enumext_keyans_pre_itemsep_skip:
    \int_compare:nNnT { \l__enumext_columns_v_int } > { 1 }
      {
        \skip_zero:N \topskip
        \skip_set_eq:NN \multicolsep \l__enumext_minipage_right_skip
      }
  }
\cs_new_protected:Nn \__enumext_keyans_minipage_add_space:
  {
    \__enumext_keyans_minipage_set_skip:
    \__enumext_unskip_unkern:
    \mode_if_vertical:TF
      {
        \nopagebreak\nointerlineskip
      }
      {
        \par\nopagebreak\nointerlineskip
        \skip_zero:N \l__enumext_partopsep_v_skip
      }
    \int_compare:nNnTF { \l__enumext_columns_v_int } > { 1 }
      {
        \addvspace{ 0.445\box_ht:N \strutbox }
      }
      {
        \addvspace{ 0.250\box_ht:N \strutbox }
      }
  }
\cs_new_protected:Nn \__enumext_keyans_pre_itemsep_skip:
  {
    \skip_if_eq:nnTF
      { \l__enumext_itemsep_i_skip } { \l__enumext_minipage_after_skip }
      {
        \skip_set:Nn \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
        \skip_set:Nn \l__enumext_multicols_below_v_skip { 0.350\box_ht:N \strutbox }
      }
      {
        \dim_compare:nNnT
          { \l__enumext_itemsep_i_skip } < { \l__enumext_minipage_after_skip }
          {
            \skip_sub:Nn \l__enumext_minipage_after_skip { \l__enumext_itemsep_i_skip }
            \skip_sub:Nn \l__enumext_multicols_below_v_skip { \l__enumext_itemsep_i_skip }
            \skip_add:Nn \l__enumext_minipage_after_skip { 0.150\box_ht:N \strutbox }
            \skip_add:Nn \l__enumext_multicols_below_v_skip
              { 0.350\box_ht:N \strutbox }
          }
        \dim_compare:nNnT
          { \l__enumext_itemsep_i_skip } > { \l__enumext_minipage_after_skip }
          {
            \skip_set:Nn \l__enumext_minipage_temp_skip
              {
                \l__enumext_itemsep_i_skip - \l__enumext_minipage_after_skip
              }
            \skip_sub:Nn \l__enumext_minipage_after_skip { \l__enumext_itemsep_i_skip }
            \skip_sub:Nn \l__enumext_multicols_below_v_skip { \l__enumext_itemsep_i_skip }
```

```
            \skip_add:Nn \l__enumext_minipage_after_skip
              { 0.150\box_ht:N \strutbox + \l__enumext_minipage_temp_skip }
            \skip_add:Nn \l__enumext_multicols_below_v_skip
              { 0.350\box_ht:N \strutbox + \l__enumext_minipage_temp_skip }
          }
      }
  }
```

(*End of definition for* `\__enumext_keyans_minipage_set_skip:`, `\__enumext_keyans_minipage_add_space:`, *and* `\__enumext_keyans_pre_itemsep_skip:`.)

13.24.3 Adjustment of vertical spaces for `minipage` in `enumext*` and `keyans*`

`\__enumext_mini_set_vskip_vii:`
`\__enumext_mini_set_vskip_viii:`

The functions `\__enumext_mini_set_vskip_vii:` and `\__enumext_mini_set_vskip_viii:` will take care of determining the "adjusted" spaces applied *"above"* and *"below"* the `\__enumext_mini_page` environment in `enumext*` and `keyans*`.

```
\cs_new_protected:Nn \__enumext_mini_set_vskip_vii:
  {
    \skip_zero:N \l__enumext_minipage_left_skip
    \skip_gzero:N \g__enumext_minipage_right_skip
    \skip_gzero:N \g__enumext_minipage_after_skip
    \skip_if_eq:nnTF { \l__enumext_topsep_vii_skip } { \c_zero_skip }
      {
        \skip_set:Nn \l__enumext_minipage_left_skip { 0.5\box_dp:N \strutbox }
        \skip_gset:Nn \g__enumext_minipage_right_skip { 0.325\box_dp:N \strutbox }
      }
      {
        \skip_set:Nn \l__enumext_minipage_left_skip { 0.5875\box_dp:N \strutbox }
        \skip_gset:Nn \g__enumext_minipage_right_skip
          {
            \l__enumext_topsep_vii_skip
          }
        \skip_gset:Nn \g__enumext_minipage_after_skip
          {
            0.325\box_dp:N \strutbox + \l__enumext_topsep_vii_skip
          }
      }
  }
\cs_new_protected:Nn \__enumext_mini_set_vskip_viii:
  {
    \skip_zero:N \l__enumext_minipage_after_skip
    \skip_zero:N \l__enumext_minipage_left_skip
    \skip_zero:N \l__enumext_minipage_right_skip
    \skip_if_eq:nnTF { \l__enumext_topsep_viii_skip } { \c_zero_skip }
      {
        \skip_set:Nn \l__enumext_minipage_left_skip
          {
            0.5\box_dp:N \strutbox
          }
        \skip_set:Nn \l__enumext_minipage_right_skip
          {
            \l__enumext_partopsep_viii_skip
          }
        \skip_set:Nn \l__enumext_minipage_after_skip
          {
            1.6\box_dp:N \strutbox
          }
      }
      {
        \skip_set:Nn \l__enumext_minipage_left_skip
          {
            0.5875\box_dp:N \strutbox
          }
        \skip_set:Nn \l__enumext_minipage_right_skip
          {
            \l__enumext_topsep_viii_skip
          }
        \skip_set:Nn \l__enumext_minipage_after_skip
          {
            0.325\box_dp:N \strutbox + \l__enumext_topsep_viii_skip
          }
      }
```

```
1686   }
```

(*End of definition for* `\__enumext_mini_set_vskip_vii:` *and* `\__enumext_mini_set_vskip_viii:`.)

`\__enumext_mini_addvspace_vii:`
`\__enumext_mini_addvspace_viii:`

The functions `\__enumext_mini_addvspace_vii:` and `\__enumext_mini_addvspace_viii:` will apply the vertical space *"only above"* the `\__enumext_mini_page` environment on the *left side* when the `mini-right` key is active in the `enumext*` and `keyans*` environments.

Here it does NOT take into account whether TEX is in ⟨*horizontal mode*⟩ or ⟨*vertical mode*⟩, since `\partopsep` is equal to `0pt` in both environments.

```
1687 \cs_new_protected:Nn \__enumext_mini_addvspace_vii:
1688   {
1689     \__enumext_mini_set_vskip_vii:
1690     \par\nopagebreak
1691     \addvspace { \l__enumext_minipage_left_skip }
1692   }
1693 \cs_new_protected:Nn \__enumext_mini_addvspace_viii:
1694   {
1695     \__enumext_mini_set_vskip_viii:
1696     \par\nopagebreak
1697     \addvspace { \l__enumext_minipage_left_skip }
1698   }
```

(*End of definition for* `\__enumext_mini_addvspace_vii:` *and* `\__enumext_mini_addvspace_viii:`.)

13.24.4 The command `\miniright`

The command `\miniright` will close the `\__enumext_mini_page` environment on the *"left side"*, open the `\__enumext_mini_page` environment on the *"right side"* adding the *adjusted vertical space*. By default `\centering` is added when starting the *"right side"* environment. The *starred argument* '`*`' inhibits the use of `\centering` command i.e. the usual LATEX justification is maintained in the `\__enumext_mini_page` on the *"right side"*.

`\miniright`

First, some checks prevent the command from being executed outside the `enumext` environment or somewhere inappropriate; then the internal functions are called to execute it in the `enumext` and `keyans` environments.

```
1699 \NewDocumentCommand \miniright { s }
1700   {
1701     \int_compare:nNnT { \l__enumext_keyans_pic_level_int } = { 1 }
1702       {
1703         \msg_error:nnn { enumext } { wrong-miniright-place }
1704       }
1705     % outside
1706     \bool_lazy_and:nnT
1707       { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
1708       { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
1709       {
1710         \msg_error:nnn { enumext } { wrong-miniright-place }
1711       }
1712     % starred env
1713     \bool_lazy_and:nnT
1714       { \bool_if_p:N \g__enumext_starred_bool }
1715       { \bool_not_p:n { \l__enumext_standard_bool } }
1716       {
1717         \msg_error:nnn { enumext } { wrong-miniright-starred }
1718       }
1719     % exec
1720     \int_compare:nNnTF { \l__enumext_keyans_level_int } = { 1 }
1721       {
1722         \__enumext_keyans_mini_right_cmd:n {#1}
1723       }
1724       { \__enumext_mini_right_cmd:n {#1} }
1725   }
```

(*End of definition for* `\miniright`. *This function is documented on page* 12.)

`\__enumext_mini_right_cmd:n`

The function `\__enumext_mini_right_cmd:n` takes as argument the *starred* '`*`' of the `\miniright` command in the `enumext` environment. It checks if the `mini-env` key is active via the variable `\l__enumext_minipage_right_X_dim`; if so, it closes the `multicols` environment with the `\__enumext_mini_page` environment on the *"left side"*, then opens the `\__enumext_mini_page` environment on the *"right side"*, applies the adjusted *"vertical spaces"*, followed by adding the `\centering` command

when the *starred argument* '*' is not present, and sets \g__enumext_minipage_stat_int to zero; otherwise it returns an error.

```
\cs_new_protected:Nn \__enumext_mini_right_cmd:n
  {
    \dim_compare:nNnTF
      { \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim } } > { \c_zero_dim }
      {
        \__enumext_multicols_stop:
        \int_compare:nNnT
          { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } = { 1 }
          {
            \par\addvspace{ \l__enumext_minipage_after_skip }
          }
        \end__enumext_mini_page
        \hfill
        \__enumext_mini_page{ \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim } }
          \par\nointerlineskip
          \addvspace { \l__enumext_minipage_right_skip }
          \bool_if:nF {#1}
            {
              \centering
            }
          \int_gzero:N \g__enumext_minipage_stat_int
      }
      { \msg_error:nnn { enumext } { wrong-miniright-use } }
    % paranoia
    \RenewDocumentCommand \miniright { s }
      {
        \msg_error:nn { enumext } { many-miniright-used }
      }
  }
```

(*End of definition for* __enumext_mini_right_cmd:n.)

__enumext_keyans_mini_right_cmd:n

The function __enumext_keyans_mini_right_cmd:n takes as argument the *starred* '*' of the \miniright command in the keyans environment. The implementation of this function is the same as that of the __enumext_mini_right_cmd:n function of the enumext environment.

```
\cs_new_protected:Nn \__enumext_keyans_mini_right_cmd:n
  {
    \dim_compare:nNnTF { \l__enumext_minipage_right_v_dim } > { \c_zero_dim }
      {
        \__enumext_keyans_multicols_stop:
        \int_compare:nNnT { \l__enumext_columns_v_int } = { 1 }
          {
            \par\addvspace{ \l__enumext_minipage_after_skip }
          }
        \end__enumext_mini_page
        \hfill
        \__enumext_mini_page{ \l__enumext_minipage_right_v_dim }
          \par\nointerlineskip
          \addvspace { \l__enumext_minipage_right_skip }
          \bool_if:nF {#1}
            {
              \centering
            }
          \int_gzero:N \g__enumext_minipage_stat_int
      }
      { \msg_error:nnn { enumext } { wrong-miniright-use } }
    % paranoia
    \RenewDocumentCommand \miniright { s }
      {
        \msg_error:nn { enumext } { many-miniright-used }
      }
  }
```

(*End of definition for* __enumext_keyans_mini_right_cmd:n.)

13.24.5 Definition of error messages

wrong-miniright-place
wrong-miniright-use
wrong-miniright-starred
many-miniright-used

Messages used by \miniright command.

```
\msg_new:nnn { enumext } { wrong-miniright-place }
```

©2024–2026 by Pablo González L

```
1783   {
1784     Wrong~place~for~'\c_backslash_str miniright'~\msg_line_context:.\\
1785     Works~in~'enumext'~and~'keyans'~with~key~'mini-env'.
1786   }
1787 \msg_new:nnn { enumext } { wrong-miniright-use }
1788   {
1789     Wrong~use~for~'\c_backslash_str miniright'~\msg_line_context:.\\
1790     '\c_backslash_str miniright'~needs~a~key~'mini-env'.
1791   }
1792 \msg_new:nnn { enumext } { wrong-miniright-starred }
1793   {
1794     Can't~use~\c_backslash_str miniright~in~starred~environments~
1795     \msg_line_context:.
1796   }
1797 \msg_new:nnn { enumext } { many-miniright-used }
1798   {
1799     Can't~use~\c_backslash_str miniright~more~than~once~\msg_line_context:.
1800   }
```

(*End of definition for* `wrong-miniright-place` *and others.*)

13.25 Setting `above` and `below` keys

While having controlled the *vertical spaces* within the `enumext` and `keyans` environments when using the `columns` or `mini-env` keys, sometimes the *"vertical spaces above"* or *"vertical spaces below"* the environments are not as expected and it is necessary to be able to apply a *"fine correction"* to these. Since these *glitches* cannot be corrected completely, the best option is to provide a couple of ⟨*keys*⟩ dedicated to this purpose, in this case it is best to use `\vspace` or `\vspace*` when convenient.

above
above*
below
below*

Define `above`, `above*`, `below` and `below*` keys for `enumext` and `keyans` environments.

```
1801 \cs_set_protected:Nn \__enumext_tmp:nn
1802   {
1803     \keys_define:nn { enumext / #1 }
1804       {
1805         above  .skip_set:c = { l__enumext_vspace_above_#2_skip },
1806         above  .value_required:n = true,
1807         above* .code:n =
1808           {
1809             \bool_set_true:c { l__enumext_vspace_a_star_#2_bool }
1810               \keys_set:nn { enumext / #1 } { above = {##1} }
1811           },
1812         above* .value_required:n = true,
1813         below  .skip_set:c = { l__enumext_vspace_below_#2_skip },
1814         below  .value_required:n = true,
1815         below* .code:n =
1816           {
1817             \bool_set_true:c { l__enumext_vspace_b_star_#2_bool }
1818               \keys_set:nn { enumext / #1 } { below = {##1} }
1819           },
1820         below* .value_required:n = true,
1821       }
1822   }
1823 \clist_map_inline:Nn \c__enumext_all_envs_clist { \__enumext_tmp:nn #1 }
```

(*End of definition for* `above` *and others.*)

13.25.1 Functions for `above` and `below` keys in `enumext`

__enumext_vspace_above:

The function `\__enumext_vspace_above:` apply the *vertical space above* the `enumext` environment set by the `above*` and `above` keys.

```
1824 \cs_new_protected:Nn \__enumext_vspace_above:
1825   {
1826     \skip_if_eq:nnF
1827       { \skip_use:c { l__enumext_vspace_above_ \__enumext_level: _skip } } { \c_zero_skip }
1828       {
1829         \bool_if:cTF { l__enumext_vspace_a_star_ \__enumext_level: _bool }
1830           {
1831             \vspace*{ \skip_use:c { l__enumext_vspace_above_ \__enumext_level: _skip } }
1832           }
1833           {
1834             \vspace { \skip_use:c { l__enumext_vspace_above_ \__enumext_level: _skip } }
```

```
            }
        }
    }
```

(*End of definition for* `\__enumext_vspace_above:`.)

`\__enumext_vspace_below:` The function `\__enumext_vspace_below:` apply the *vertical space below* the `enumext` environment set by the `below*` and `below` keys.

```
\cs_new_protected:Nn \__enumext_vspace_below:
  {
    \skip_if_eq:nnF
      { \skip_use:c { l__enumext_vspace_below_ \__enumext_level: _skip } } { \c_zero_skip }
      {
        \bool_if:cTF { l__enumext_vspace_b_star_ \__enumext_level: _bool }
          {
            \vspace*{ \skip_use:c { l__enumext_vspace_below_ \__enumext_level: _skip } }
          }
          {
            \vspace { \skip_use:c { l__enumext_vspace_below_ \__enumext_level: _skip } }
          }
      }
  }
```

(*End of definition for* `\__enumext_vspace_below:`.)

13.25.2 Functions for `above` and `below` keys in `keyans`

`\__enumext_vspace_above_v:` The function `\__enumext_vspace_above_v:` apply the *vertical space above* the `keyans` environment set by the `above` and `above*` keys.

```
\cs_new_protected:Nn \__enumext_vspace_above_v:
  {
    \skip_if_eq:nnF { \l__enumext_vspace_above_v_skip } { \c_zero_skip }
      {
        \bool_if:NTF \l__enumext_vspace_a_star_v_bool
          {
            \vspace*{ \l__enumext_vspace_above_v_skip }
          }
          { \vspace { \l__enumext_vspace_above_v_skip } }
      }
  }
```

(*End of definition for* `\__enumext_vspace_above_v:`.)

`\__enumext_vspace_below_v:` The function `\__enumext_vspace_below_v:` apply the *vertical space below* the `keyans` environment set by the `below*` and `below` keys.

```
\cs_new_protected:Nn \__enumext_vspace_below_v:
  {
    \skip_if_eq:nnF { \l__enumext_vspace_below_v_skip } { \c_zero_skip }
      {
        \bool_if:NTF \l__enumext_vspace_b_star_v_bool
          {
            \vspace*{ \l__enumext_vspace_below_v_skip }
          }
          { \vspace { \l__enumext_vspace_below_v_skip } }
      }
  }
```

(*End of definition for* `\__enumext_vspace_below_v:`.)

13.25.3 Functions for `above` and `below` keys in `enumext*` `keyans*`

`\__enumext_vspace_above_vii:` `\__enumext_vspace_above_viii:` The functions `\__enumext_vspace_above_vii:` and `\__enumext_vspace_above_viii:` apply the *vertical space above* the `enumext*` and `keyans*` environments set by the `above` and `above*` keys.

```
\cs_new_protected:Nn \__enumext_vspace_above_vii:
  {
    \skip_if_eq:nnF { \l__enumext_vspace_above_vii_skip } { \c_zero_skip }
      {
        \bool_if:NTF \l__enumext_vspace_a_star_vii_bool
          {
            \vspace*{ \l__enumext_vspace_above_vii_skip }
```

```
            }
            { \vspace { \l__enumext_vspace_above_vii_skip } }
        }
    }
\cs_new_protected:Nn \__enumext_vspace_above_viii:
    {
      \skip_if_eq:nnF { \l__enumext_vspace_above_viii_skip } { \c_zero_skip }
        {
          \bool_if:NTF \l__enumext_vspace_a_star_viii_bool
            {
              \vspace*{ \l__enumext_vspace_above_viii_skip }
            }
            { \vspace { \l__enumext_vspace_above_viii_skip } }
        }
    }
```

(*End of definition for* `\__enumext_vspace_above_vii:` *and* `\__enumext_vspace_above_viii:`.)

`\__enumext_vspace_below_vii:` `\__enumext_vspace_below_viii:`

The functions `\__enumext_vspace_below_vii:` and `\__enumext_vspace_below_viii:` apply the *vertical space below* the `enumext*` and `keyans*` environments set by the `below*` and `below` keys.

```
\cs_new_protected:Nn \__enumext_vspace_below_vii:
    {
      \skip_if_eq:nnF { \l__enumext_vspace_below_vii_skip } { \c_zero_skip }
        {
          \bool_if:NTF \l__enumext_vspace_b_star_vii_bool
            {
              \vspace*{ \l__enumext_vspace_below_vii_skip }
            }
            { \vspace { \l__enumext_vspace_below_vii_skip } }
        }
    }
\cs_new_protected:Nn \__enumext_vspace_below_viii:
    {
      \skip_if_eq:nnF { \l__enumext_vspace_below_viii_skip } { \c_zero_skip }
        {
          \bool_if:NTF \l__enumext_vspace_b_star_viii_bool
            {
              \vspace*{ \l__enumext_vspace_below_viii_skip }
            }
            { \vspace { \l__enumext_vspace_below_viii_skip } }
        }
    }
```

(*End of definition for* `\__enumext_vspace_below_vii:` *and* `\__enumext_vspace_below_viii:`.)

13.26 Setting `series`, `resume` and `resume*` keys

The `series` key is responsible for the whole process of the `resume` and `resume*` keys. The idea behind this is to be able to absorb the ⟨*keys*⟩ passed to the *optional argument* of the environments `enumext` and `enumext*`, but, discarding some specific ⟨*keys*⟩.

`series` `resume` `resume*`

Defines the keys `series`, `resume` and `resume*` for the *"all levels"* of `enumext` and `enumext*`. It is not necessary to make sure that `\printkeyans` is not running otherwise the *start value* of the environments would be increased when using `resume` or `resume*` keys.

In version 1.6 it is allowed to pass the key `resume` *without value* by means of the command `\setenumext`, for the correct operation of this, the boolean variable `\l__enumext_resume_count_bool` set by the key `resume` *without value* must be set to "true" to be later processed by the function `\__enumext_parse_series:n` in the definition of the environments `enumext` and `enumext*`.

```
\cs_set_protected:Nn \__enumext_tmp:nn
    {
      \keys_define:nn { enumext / #1 }
        {
          series  .str_set:N = \l__enumext_series_name_str,
          series  .value_required:n = true,
          resume  .code:n =
            {
              \bool_if:NF \l__enumext_print_keyans_cmd_bool
                {
                  \tl_set:Nn \l__enumext_series_name_tl {##1}
                  \tl_if_empty:NTF \l__enumext_series_name_tl
```

```
                    {
                      \bool_set_true:c { l__enumext_resume_count_#2_bool }
                      \bool_set_eq:Nc
                        \l__enumext_resume_count_bool
                        { l__enumext_resume_count_#2_bool }
                    }
                    {
                      \__enumext_resume:n {##1}
                    }
                }
            },
          resume* .code:n =
            {
              \bool_if:NF \l__enumext_print_keyans_cmd_bool
                {
                  \bool_set_true:c { l__enumext_resume_count_#2_bool }
                  \bool_set_eq:Nc
                    \l__enumext_resume_count_bool { l__enumext_resume_count_#2_bool }
                  \bool_set_true:c { l__enumext_resume_star_key_#2_bool }
                  \__enumext_resume_star:
                }
            },
          resume* .value_forbidden:n = true,
        }
    }
\clist_map_inline:nn
    {
      {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv},{enumext*}{vii},
    }
    { \__enumext_tmp:nn #1 }
```

(*End of definition for* `series` , `resume` , *and* `resume*`.)

13.26.1 Internal function to save counter and integer values

__enumext_standard_save_counter:
__enumext_standard_save_counter_aux:
__enumext_starred_save_counter:
__enumext_starred_save_counter_aux:

The __enumext_standard_save_counter: and __enumext_starred_save_counter: functions will save the last counter value to \g__enumext_series_#1_int if the series={⟨*series name*⟩} key has been passed, to \c@ __enumext_resume_X_int if it has passed the key resume *without value* and the key series is not active, in \g__enumext_series_#1_X_int if the key resume={⟨*series name*⟩} has been passed and in \g__enumext_series_#1_X_int if the key has been passed save-ans={⟨*store name*⟩}.

The variables \l__enumext_series_name_str and \l__enumext_series_name_tl contain the same {⟨*series name*⟩} but are executed at different moments, the integer variable with \l__enumext_series_name_str sets the value when execute series={⟨*series name*⟩} and the integer variable with \l__enumext_series_name_tl sets the subsequent values when use resume={⟨*series name*⟩}. This function is passed to the enumext environment definition (§13.42) and the enumext* environment definition (§13.47).

```
\cs_new_protected:Nn \__enumext_standard_save_counter:
  {
    \bool_if:NTF \g__enumext_standard_bool
      {
        \__enumext_standard_save_counter_aux:
        \int_compare:nNnT { \l__enumext_level_int } = { 1 }
          {
            \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl _int }
              {
                \int_gset_eq:cN
                  { g__enumext_resume_ \l__enumext_store_name_tl _int } \value{enumXi}
              }
          }
      }
      {
        \__enumext_standard_save_counter_aux:
      }
  }
\cs_new_protected:Nn \__enumext_standard_save_counter_aux:
  {
    \str_if_empty:NF \l__enumext_series_name_str
      {
        \int_gset_eq:cc
          { g__enumext_series_ \l__enumext_series_name_str _ \__enumext_level: _int }
          { c@enumX \__enumext_level: }
```

```
      }
    \tl_if_empty:NTF \l__enumext_series_name_tl
      {
        \str_if_empty:NT \l__enumext_series_name_str
          {
            \tl_if_empty:NT \l__enumext_store_name_tl
              {
                \int_gset_eq:cc
                  { c@ __enumext_resume_ \__enumext_level: _int } { c@enumX \__enumext_level: }
              }
          }
      }
      {
        \int_if_exist:cT
          { g__enumext_series_ \l__enumext_series_name_tl _ \__enumext_level: _int }
          {
            \int_gset_eq:cc
              { g__enumext_series_ \l__enumext_series_name_tl _ \__enumext_level: _int }
              { c@enumX \__enumext_level: }
          }
      }
  }
\cs_new_protected:Nn \__enumext_starred_save_counter:
  {
    \bool_if:NTF \g__enumext_starred_bool
      {
        \__enumext_starred_save_counter_aux:
        \int_if_exist:cT { g__enumext_resume_ \l__enumext_store_name_tl _int }
          {
            \int_gset_eq:cN
              { g__enumext_resume_ \l__enumext_store_name_tl _int } \value{enumXvii}
          }
      }
      {
        \__enumext_starred_save_counter_aux:
      }
  }
\cs_new_protected:Nn \__enumext_starred_save_counter_aux:
  {
    \str_if_empty:NF \l__enumext_series_name_str
      {
        \int_gset_eq:cN
          { g__enumext_series_ \l__enumext_series_name_str _vii_int } \value{enumXvii}
      }
    \tl_if_empty:NTF \l__enumext_series_name_tl
      {
        \str_if_empty:NT \l__enumext_series_name_str
          {
            \tl_if_empty:NT \l__enumext_store_name_tl
              {
                \int_gset_eq:cc { c@ __enumext_resume_vii_int } { c@enumXvii }
              }
          }
      }
      {
        \int_if_exist:cT { g__enumext_series_ \l__enumext_series_name_tl _vii_int }
          {
            \int_gset_eq:cN
              { g__enumext_series_ \l__enumext_series_name_tl _vii_int } \value{enumXvii}
          }
      }
  }
```

(*End of definition for* `\__enumext_standard_save_counter:` *and others.*)

13.26.2 Internal function for resume counters

`\__enumext_resume_counter:`

The `\__enumext_resume_counter:` function is executed by the `resume*` key and `resume` key *without value*, only the *"counters"* for the *"levels"* of the environments in which it is executed will be set. If the `save-ans` key is active it will set the *"counter"* according to the value of the integer variable created by that key.

```
\cs_new_protected:Nn \__enumext_resume_counter:
```

```
{
  \cs_set:Nn \__enumext_tmp:n
    {
      \bool_if:cT { l__enumext_resume_count_ \int_to_roman:n {##1} _bool }
        {
          \exp_args:Ne \int_set:cn { l__enumext_start_ \int_to_roman:n {##1} _int }
            {
              \int_use:c { c@ __enumext_resume_ \int_to_roman:n {##1} _int } + 1
            }
        }
    }
  \int_compare:nNnT { \l__enumext_level_int } > { 0 }
    {
      \bool_lazy_and:nnTF
         { \bool_if_p:N \l__enumext_standard_first_bool }
         { \bool_if_p:N \l__enumext_store_active_bool }
         {
           \int_set:Nn \l__enumext_start_i_int
             {
               \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int } + 1
             }
         }
         {
           \int_step_function:nN { \l__enumext_level_int } \__enumext_tmp:n
         }
    }
  \int_compare:nNnT { \l__enumext_level_h_int } = { 1 }
    {
      \bool_lazy_and:nnTF
        { \bool_if_p:N \l__enumext_starred_first_bool }
        { \bool_if_p:N \l__enumext_store_active_bool }
        {
          \int_set:Nn \l__enumext_start_vii_int
            {
              \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int } + 1
            }
        }
        {
          \bool_if:NT \l__enumext_resume_count_vii_bool
            {
              \int_set:Nn \l__enumext_start_vii_int
                {
                  \int_use:c { c@ __enumext_resume_vii_int } + 1
                }
            }
        }
    }
}
```

(*End of definition for* `\__enumext_resume_counter:`.)

13.26.3 Definition of error messages

unknown-series-starred
unknown-series-standard

Messages used by `resume` key.

```
\msg_new:nnn { enumext } { unknown-series-starred }
  {
    The~series~'#1'~for~the~resume~key~does~not~exist~in~the~
    enumext*~environment~\msg_line_context:.
  }
\msg_new:nnn { enumext } { unknown-series-standard }
  {
    The~series~'#1'~for~the~resume~key~does~not~exist~at~level~
    \int_use:N \l__enumext_level_int
    \c_space_tl of~enumext~environment~\msg_line_context:.
  }
```

(*End of definition for* `unknown-series-starred` *and* `unknown-series-standard`.)

13.26.4 Internal functions for `series` key

__enumext_filter_series:n
__enumext_filter_series_key:n
__enumext_filter_series_pair:nn

The function `\__enumext_filter_series:n` will be in charge of filtering the ⟨*keys*⟩ to be stored, where `#1` represents the *optional argument* passed to the environment. This implementation is adapted directly from the

code provided by Jonathan P. Spratte (@Skillmon) in chat-TeX-SX

```
\cs_new:Nn \__enumext_filter_series:n
  {
    \use:e
      {
        \keyval_parse:NNn
          \__enumext_filter_series_key:n
          \__enumext_filter_series_pair:nn {#1}
      }
  }
```

The function `\__enumext_filter_series_key:n` will be responsible for filtering the ⟨*keys*⟩ that are passed *"without value"* by excluding the `resume`, `resume*`, `reset`, `reset*` and `base-fix` keys.

```
\cs_new:Nn \__enumext_filter_series_key:n
  {
    \str_case:nnF {#1}
      {
        { resume } {} { resume* } {} { reset } {} { reset* } {} { base-fix } {}
      }
      { , { \exp_not:n {#1} } }
  }
```

The function `\__enumext_filter_series_pair:nn` will be responsible for filtering the ⟨*keys*⟩ that are passed *"with value"* by excluding the `series`, `resume`, `start`, `start*`, `save-ans` and `save-key` keys.

```
\cs_new:Nn \__enumext_filter_series_pair:nn
  {
    \str_case:nnF {#1}
      {
        { series } {} { resume } {} { start } {}
        { start* } {}  { save-ans } {} { save-key } {}
      }
      { , { \exp_not:n {#1} } = { \exp_not:n {#2} } }
  }
```

(*End of definition for* `\__enumext_filter_series:n`, `\__enumext_filter_series_key:n`, *and* `\__enumext_filter_series_pair:nn`.)

`\__enumext_save_last_keys:n`
`\__enumext_resume_last_counter:`

The function `\__enumext_save_last_keys:n` will be in charge of saving the filtering ⟨*keys*⟩ when the keys `series={`⟨*series name*⟩`}` or `resume={`⟨*series name*⟩`}` or `resume*` are NOT active and will save them in the variable `\g__enumext_resume_last_keys_X_tl` for the `enumext` environment and in the variable `\g__enumext_resume_last_keys_vii_tl` for the `enumext*` environment.

The boolean variable `\l__enumext_resume_series_X_bool` is set to "true" by the key `resume={`⟨*series name*⟩`}`, the boolean variable `\l__enumext_resume_star_key_X_bool` is set to "true" by the key `resume*`, in this case both variables must be set to ""false"" so that they don't override the default filtered ⟨*keys*⟩.

```
\cs_new_protected:Nn \__enumext_save_last_keys:n
  {
    \int_compare:nNnT { \l__enumext_level_int } > { 0 }
      {
        \bool_if:cF { l__enumext_resume_series_ \__enumext_level: _bool }
          {
            \bool_if:cF { l__enumext_resume_star_key_ \__enumext_level: _bool }
              {
                \tl_gclear:c { g__enumext_resume_last_keys_ \__enumext_level: _tl }
                \tl_gset:ce
                  { g__enumext_resume_last_keys_ \__enumext_level: _tl }
                  { \__enumext_filter_series:n {#1} }
              }
          }
      }
    \int_compare:nNnT { \l__enumext_level_h_int } = { 1 }
      {
        \bool_if:NF \l__enumext_resume_series_vii_bool
          {
            \tl_gclear:N \g__enumext_resume_last_keys_vii_tl
            \tl_gset:Ne \g__enumext_resume_last_keys_vii_tl
              { \__enumext_filter_series:n {#1} }
          }
      }
  }
```

©2024–2026 by Pablo González L

The __enumext_resume_last_counter: function will be in charge of setting the *"counters"* when the keys series={⟨*series name*⟩} or resume={⟨*series name*⟩} are NOT active and the resume key is being used *without value* either in the *optional argument* of the environments or through the \setenumext command.

The boolean variable \l__enumext_resume_count_bool is set to "true" by the keys resume *without value* and resume*; and set to "false" by the keys start and start* (§13.15).

```
\cs_new_protected:Nn \__enumext_resume_last_counter:
  {
    \bool_lazy_and:nnT
      { \bool_if_p:N \l__enumext_resume_count_bool }
      { \tl_if_empty_p:N \l__enumext_series_name_tl }
      {
        \__enumext_resume_counter:
      }
  }
```

(*End of definition for* __enumext_save_last_keys:n *and* __enumext_resume_last_counter:.)

__enumext_parse_series:n

The __enumext_parse_series:n function handled by the series key will be responsible for *storing* the *filtered* ⟨*keys*⟩ from the *optional arguments* of the enumext and enumext* environments for the resume and resume* keys. If the series key is NOT active it will call the __enumext_save_last_keys:n function to *store* the *filtered* ⟨*keys*⟩ that will be used by the resume* key and then the __enumext_resume_last_counter: function used by the resume key *without value* if it is active, otherwise *store* the *filtered* ⟨*keys*⟩ in the global variable \g__enumext_series_#1_X_tl along with the creation of the integer variable \g__enumext_series_#1_X_int used by the resume key *with value*.

This function is passed to the function __enumext_parse_keys:n in the enumext environment definition (§13.42) and to the function __enumext_parse_keys_vii:n in the enumext* environment definition (§13.47).

```
\cs_new_protected:Nn \__enumext_parse_series:n
  {
    \str_if_empty:NTF \l__enumext_series_name_str
      {
        \int_compare:nNnT { \l__enumext_level_int } > { 0 }
          {
            \__enumext_save_last_keys:n {#1}
            \__enumext_resume_last_counter:
          }
        \int_compare:nNnT { \l__enumext_level_h_int } = { 1 }
          {
            \__enumext_save_last_keys:n {#1}
            \__enumext_resume_last_counter:
          }
      }
      {
        \int_compare:nNnT { \l__enumext_level_int } > { 0 }
          {
            \tl_gclear_new:c
              { g__enumext_series_ \l__enumext_series_name_str _ \__enumext_level: _tl }
            \tl_gset:ce
              { g__enumext_series_ \l__enumext_series_name_str _ \__enumext_level: _tl }
              { \__enumext_filter_series:n {#1} }
            \int_if_exist:cF
              { g__enumext_series_ \l__enumext_series_name_str _ \__enumext_level: _int }
              {
                \int_new:c
                  { g__enumext_series_ \l__enumext_series_name_str _ \__enumext_level: _int }
              }
          }
        \int_compare:nNnT { \l__enumext_level_h_int } = { 1 }
          {
            \tl_gclear_new:c { g__enumext_series_ \l__enumext_series_name_str _vii_tl }
            \tl_gset:ce
              { g__enumext_series_ \l__enumext_series_name_str _vii_tl }
              { \__enumext_filter_series:n {#1} }
            \int_if_exist:cF { g__enumext_series_ \l__enumext_series_name_str _vii_int }
              {
                \int_new:c { g__enumext_series_ \l__enumext_series_name_str _vii_int }
              }
          }
      }
  }
```

(*End of definition for* `\__enumext_parse_series:n`.)

13.26.5 Internal functions for `resume` key with value

`\__enumext_resume:n`

The function `\__enumext_resume:n` will handle the *argument* {⟨*series name*⟩} passed to the `resume` key in `enumext` and `enumext*` environments. First it checks if the global variable `\g__enumext_series_#1_X_tl` exists; if so, it calls the function `\__enumext_resume_series:n` and passes the ⟨*keys*⟩ stored in `\g__enumext_series_#1_X_tl` to the environments, otherwise it returns an error.

```
\cs_new_protected:Nn \__enumext_resume:n
  {
    \int_compare:nNnT { \l__enumext_level_int } > { 0 }
      {
        \tl_if_exist:cTF { g__enumext_series_ \tl_to_str:n {#1} _ \__enumext_level: _tl }
          {
            \__enumext_resume_series:n {#1}
            \exp_args:Ne \keys_set:nv { enumext /
              level-\int_use:N \l__enumext_level_int }
              { g__enumext_series_ \tl_to_str:n {#1} _ \__enumext_level: _tl }
          }
          {
            \msg_error:nnn { enumext } { unknown-series-standard } {#1}
          }
      }
    \int_compare:nNnT { \l__enumext_level_h_int } = { 1 }
      {
        \tl_if_exist:cTF { g__enumext_series_ \tl_to_str:n {#1} _vii_tl }
          {
            \__enumext_resume_series:n {#1}
            \keys_set:nv { enumext / enumext* }
              { g__enumext_series_ \tl_to_str:n {#1} _vii_tl }
          }
          {
            \msg_error:nnn { enumext } { unknown-series-starred } {#1}
          }
      }
  }
```

(*End of definition for* `\__enumext_resume:n`.)

`\__enumext_resume_series:n`
`\__enumext_resume_integer_series:`

The function `\__enumext_resume_series:n` will set the variable `\l__enumext_resume_series_X_bool` to "true" and pass the {⟨*argument*⟩} to the variable `\l__enumext_series_name_tl` then call the function `\__enumext_resume_integer_series:`.

```
\cs_new_protected:Nn \__enumext_resume_series:n
  {
    \int_compare:nNnT { \l__enumext_level_int } > { 0 }
      {
        \bool_set_true:c { l__enumext_resume_series_ \__enumext_level: _bool }
        \tl_clear:N \l__enumext_series_name_tl
        \tl_set:Nn \l__enumext_series_name_tl {#1}
        \__enumext_resume_integer_series:
      }
    \int_compare:nNnT { \l__enumext_level_h_int } = { 1 }
      {
        \bool_set_true:N \l__enumext_resume_series_vii_bool
        \tl_clear:N \l__enumext_series_name_tl
        \tl_set:Nn \l__enumext_series_name_tl {#1}
        \__enumext_resume_integer_series:
      }
  }
```

The function `\__enumext_resume_integer_series:` will be executed when the `resume`={⟨*series name*⟩} key is active, setting the *start value* for the *"counter"* of the *"current level"* of the environments in which it is run according to the value of the *"integer variables"* created by the `series` key. If the `save-ans` key is active it will set the *start value* for the *"counter"* according to the value of the integer variable created by that key.

```
\cs_new_protected:Nn \__enumext_resume_integer_series:
  {
    \cs_set:Nn \__enumext_tmp:n
      {
        \int_if_exist:cT { g__enumext_series_ \l__enumext_series_name_tl _
          \int_to_roman:n {##1} _int }
```

```
          {
            \exp_args:Ne \int_set:cn { l__enumext_start_ \int_to_roman:n {##1} _int }
              {
                \int_use:c { g__enumext_series_ \l__enumext_series_name_tl _
                  \int_to_roman:n {##1} _int } + 1
              }
          }
      }
    \int_compare:nNnT { \l__enumext_level_int } > { 0 }
      {
        \bool_lazy_and:nnTF
          { \bool_if_p:N \l__enumext_standard_first_bool }
          { \bool_if_p:N \l__enumext_store_active_bool }
          {
            \int_set:Nn \l__enumext_start_i_int
              {
                \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int } + 1
              }
          }
          {
            \int_step_function:nN { \l__enumext_level_int } \__enumext_tmp:n
          }
      }
    \int_compare:nNnT { \l__enumext_level_h_int } = { 1 }
      {
        \bool_lazy_and:nnTF
          { \bool_if_p:N \l__enumext_starred_first_bool }
          { \bool_if_p:N \l__enumext_store_active_bool }
          {
            \int_set:Nn \l__enumext_start_vii_int
              {
                \int_use:c { g__enumext_resume_ \l__enumext_store_name_tl _int } + 1
              }
          }
          {
            \int_set:Nn \l__enumext_start_vii_int
              {
                \int_use:c { g__enumext_series_ \l__enumext_series_name_tl _vii_int } + 1
              }
          }
      }
  }
```

(*End of definition for* `\__enumext_resume_series:n` *and* `\__enumext_resume_integer_series:`.)

13.26.6 Internal function for `resume*` key

`\__enumext_resume_star:`

The function `\__enumext_resume_star:` will handle the `resume*` key in the `enumext` and `enumext*` environments. This function will execute the filtered ⟨*keys*⟩ in the last one and will continue with the numbering and ⟨*keys*⟩ according to the last execution of the environment `enumext` or `enumext*` in which the keys `resume=`{⟨*series name*⟩} or `series=`{⟨*series name*⟩} were NOT active.

```
\cs_new_protected:Nn \__enumext_resume_star:
  {
    \cs_set:Nn \__enumext_tmp:n
      {
        \tl_if_empty:cTF { g__enumext_resume_last_keys_ \int_to_roman:n {##1} _tl }
          {
            \__enumext_resume_counter:
          }
          {
            \__enumext_resume_counter:
            \exp_args:Ne \keys_set:nv
              { enumext / level-\int_use:N \l__enumext_level_int }
              { g__enumext_resume_last_keys_ \int_to_roman:n {##1} _tl }
          }
      }
    \int_compare:nNnT { \l__enumext_level_int } > { 0 }
      {
        \int_step_function:nN { \l__enumext_level_int } \__enumext_tmp:n
      }
    \int_compare:nNnT { \l__enumext_level_h_int } = { 1 }
```

```
      {
        \tl_if_empty:NTF \g__enumext_resume_last_keys_vii_tl
          {
            \__enumext_resume_counter:
          }
          {
            \__enumext_resume_counter:
            \keys_set:nV { enumext / enumext* } \g__enumext_resume_last_keys_vii_tl
          }
      }
  }
```

(*End of definition for* `\__enumext_resume_star:`.)

13.27 The `\resetenumext` command

Sometimes it is necessary to be able to reset the *"counters"* of the environments according to some value, for example `\chapter`. Since *"internal counters"* are used for the `resume` and `resume*` keys which set the *start value*, but are not accessible by the user, it is necessary to provide a public command for this. This implementation is an adaptation of the answers given by Clea F. Rees (`@cfr`) and Jonathan P. Spratte (`@Skillmon`) in Correct implementation of optional argument (comma-separated) in expl3.

`\resetenumext`
`\__enumext_standard_reset:nn`
`\__enumext_starred_reset:n`
`\__enumext_reset_count_resume:nn`
`\__enumext_reset_count_resume:en`
`\__enumext_reset_count_resume_all:n`
`\__enumext_reset_count_resume_levels:n`

The `\resetenumext` command *"resets"* the *start value* of the *"counters"* for the `enumext` and `enumext*` environments along with the *"internal counters"* used by the keys `resume` *without value* and `resume*` according to the value of {⟨*some counter*⟩}.

```
\NewDocumentCommand \resetenumext { s o m }
  {
    \bool_if:nTF {#1}
      {
        \__enumext_reset_count_resume_all:n {#3}
      }
      {
        \tl_if_novalue:nTF {#2}
          {
            \__enumext_reset_count_resume_levels:n {#3}
          }
          {
            \str_if_eq:nnTF {#2} { * }
              { \__enumext_starred_reset:n {#3} }
              {
                \bool_lazy_and:nnTF
                  { \int_compare_p:nNn {#2} > { 0 } }
                  { \int_compare_p:nNn {#2} < { 5 } }
                  { \__enumext_standard_reset:nn {#2} {#3} }
                  {
                    \msg_error:nne { enumext } { out-of-range }
                      { \int_eval:n {#2} }
                  }
              }
          }
      }
  }
\cs_new_protected:Npn \__enumext_standard_reset:nn #1 %#2
  {
    \__enumext_reset_count_resume:en { \int_to_roman:n {#1} } %{#2}
  }
\cs_new_protected:Nn \__enumext_starred_reset:n
  {
    \__enumext_reset_count_resume:nn { vii } {#1}
  }
\cs_new_protected:Nn \__enumext_reset_count_resume:nn
  {
    \counterwithin*{enumX#1}{#2}
    \counterwithin*{__enumext_resume_#1_int}{#2}
  }
\cs_generate_variant:Nn \__enumext_reset_count_resume:nn { e }
\cs_new_protected:Nn \__enumext_reset_count_resume_all:n
  {
    \clist_map_inline:nn { i,ii,iii,iv,vii }
      {
        \__enumext_reset_count_resume:nn {##1} {#1}
```

```
      }
  }
\cs_new_protected:Nn \__enumext_reset_count_resume_levels:n
  {
    \clist_map_inline:nn { i,ii,iii,iv }
      {
        \__enumext_reset_count_resume:nn {##1} {#1}
      }
  }
```

(*End of definition for* `\resetenumext` *and others. This function is documented on page 11.*)

13.27.1 Definition of error messages for `\resetenumext`

out-of-range Message used by `\resetenumext` command.

```
\msg_new:nnnn { enumext } { out-of-range }
  {
    The~number~must~be~exactly~1,~2,~3~or~4.
  }
  {
    Received:~'#1'.
  }
```

(*End of definition for* `out-of-range`.)

13.28 The `reset` and `reset*` keys

The `\resetenumext` command does not work, for example, after an unnumbered chapter, so it is preferable to provide a pair of ⟨*keys*⟩ that adjust the internal variables if necessary.

reset
reset* Defines the keys `reset` and `reset*` for the *"all levels"* of `enumext` and `enumext*`.

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \keys_define:nn { enumext / #1 }
      {
        reset  .code:n = { \__enumext_standard_reset_key: },
        reset  .value_forbidden:n = true,
        reset* .code:n = { \__enumext_standard_reset_key_star: },
        reset* .value_forbidden:n = true,
      }
  }
\clist_map_inline:nn {level-1, level-2, level-3, level-4} { \__enumext_tmp:n {#1} }
\keys_define:nn { enumext / enumext* }
  {
    reset  .code:n = { \__enumext_starred_reset_key: },
    reset  .value_forbidden:n = true,
    reset* .code:n = { \__enumext_starred_reset_key: },
    reset* .value_forbidden:n = true,
  }
```

(*End of definition for* `reset` *and* `reset*`.)

13.28.1 Internal functions for `reset` and `reset*` keys

__enumext_standard_reset_key:
__enumext_standard_reset_key_star:
__enumext_starred_reset_key: The function `\__enumext_standard_reset_key:` will be handled by the `reset` key and will *"reset"* the counter `\c@ __enumext_resume_X_int` to *"zero"* according to the *level* at which it is executed within the `enumext` environment.

```
\cs_new_protected:Nn \__enumext_standard_reset_key:
  {
    \int_compare:nNnT { \l__enumext_level_int } > { 0 }
      {
        \int_if_exist:cT { c@ __enumext_resume_ \int_to_roman:n { \l__enumext_level_int }
          _int }
          {
            \int_gzero:c { c@ __enumext_resume_ \int_to_roman:n { \l__enumext_level_int }
              _int }
          }
      }
  }
```

The function __enumext_standard_reset_key_star: will be handled by the reset* key and will *"reset"* the counters \c@ __enumext_resume_X_int to *"zero"* from the *level* at which it is executed within the enumext environment to the *lower levels*.

```
\cs_new_protected:Nn \__enumext_standard_reset_key_star:
  {
    \cs_set:Nn \__enumext_tmp:n
      {
        \int_if_exist:cT { c@ __enumext_resume_ \int_to_roman:n {##1} _int }
          {
            \int_gzero:c { c@ __enumext_resume_ \int_to_roman:n {##1} _int }
          }
      }
    \int_compare:nNnT { \l__enumext_level_int } > { 0 }
      {
        \int_step_function:nnN { \l__enumext_level_int } { 4 } \__enumext_tmp:n
      }
  }
```

The function __enumext_starred_reset_key: will be handled by reset keys and reset* will *"reset"* the counter \c@ __enumext_resume_vii_int to *"zero"* when executed in the enumext* environment.

```
\cs_new_protected:Nn \__enumext_starred_reset_key:
  {
    \int_gzero:c { c@ __enumext_resume_vii_int }
  }
```

(*End of definition for* __enumext_standard_reset_key:, __enumext_standard_reset_key_star:, *and* __enumext_starred_reset_key:.)

13.29 Setting save-ans, check-ans and no-store keys

The key save-ans is directly associated with the keys check-ans, no-store, resume and resume*, this will activate the entire *"storage system"* in the enumext package.

13.29.1 Setting save-ans key

save-ans Defines the key save-ans only for the *"first level"* of enumext and enumext*.

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \keys_define:nn { enumext / #1 }
      {
        save-ans .code:n = { \__enumext_storing_set:n {##1} },
        save-ans .value_required:n = true,
      }
  }
\clist_map_inline:nn { level-1, enumext* } { \__enumext_tmp:n {#1} }
```

(*End of definition for* save-ans.)

13.29.2 Definition of error messages

save-ans-empty
save-ans-log
save-ans-log-hook

Messages used by save-ans key.

```
\msg_new:nnn { enumext } { save-ans-empty }
  {
    Key~'save-ans'~needs~a~value~in~'#1'~\msg_line_context:.
  }
\msg_new:nnn { enumext } { save-ans-log }
  {
    *~Package~enumext:~Start~#1~with~save-ans=#2~\msg_line_context:.
  }
\msg_new:nnn { enumext } { save-ans-log-hook }
  {
    *~Package~enumext:~Stop~#1~with~save-ans=#2~\msg_line_context:.
  }
```

(*End of definition for* save-ans-empty, save-ans-log, *and* save-ans-log-hook.)

items-same-answer
item-greater-answer
item-less-answer

Messages used by the internal system to check answer used by check-ans key.

```
\msg_new:nnn { enumext } { items-same-answer }
  {
    ****************************************\\
```

```
    *~Package~enumext:~Checking~answers~in~'#1'~
    for~\c_left_brace_str #2 \c_right_brace_str\\
    *~started~#3~and~close~\msg_line_context: :~
    'OK',~all~items~with~answer.\\
    ************************************
  }
\msg_new:nnn { enumext } { item-greater-answer }
  {
    Checking~answers~in~'#1'~for~\c_left_brace_str #2 \c_right_brace_str\\
    started~#3~and~close~\msg_line_context: :~'NOT~OK'\\
    Items~>~Answers.
  }
\msg_new:nnn { enumext } { item-less-answer }
  {
    Checking~answers~in~'#1'~for~\c_left_brace_str #2 \c_right_brace_str\\
    started~#3~and~close~\msg_line_context: :~'NOT~OK'\\
    Items~<~Answers.
  }
```

(*End of definition for* `items-same-answer`, `item-greater-answer`, *and* `item-less-answer`.)

missing-starred
many-starred

Messages used by the internal system to check for *"starred"* `\item*` and `\anspic*` commands.

```
\msg_new:nnn { enumext } { missing-starred }
  {
    Missing~'\c_backslash_str #1*'~#2.
  }
\msg_new:nnn { enumext } { many-starred }
  {
    Many~'\c_backslash_str #1*'~#2.
  }
```

(*End of definition for* `missing-starred` *and* `many-starred`.)

store-prop
store-seq
store-int

Messages written to the `.log` file when the *prop list*, *sequence* and integer variables used by the `save-ans` key are created.

```
\msg_new:nnn { enumext } { store-prop }
  {
    *~Package~enumext:~Creating~
    \c_backslash_str g__enumext_#1_prop~\msg_line_context:.
  }
\msg_new:nnn { enumext } { store-seq }
  {
    *~Package~enumext:~Creating~
    \c_backslash_str g__enumext_#1_seq~\msg_line_context:.
  }
\msg_new:nnn { enumext } { store-int }
  {
    *~Package~enumext:~Creating~
    \c_backslash_str g__enumext_resume_#1_int~\msg_line_context:.
  }
```

(*End of definition for* `store-prop`, `store-seq`, *and* `store-int`.)

13.29.3 Internal functions for `save-ans` key

__enumext_start_save_ans_msg:
__enumext_stop_save_ans_msg:

The functions `\__enumext_start_save_ans_msg:` and `\__enumext_stop_save_ans_msg:` will display in the terminal and `.log` file the environment in which the `save-ans` key was executed along with the line at the beginning and end of it. The function `\__enumext_start_save_ans_msg:` will be passed to `\__enumext_storing_set:n` and the function `\__enumext_stop_save_ans_msg:` will be passed to the function `\__enumext_execute_after_env:`.

```
\cs_new_protected:Nn \__enumext_start_save_ans_msg:
  {
    \msg_term:nnVV { enumext } { save-ans-log }
      \g__enumext_envir_name_tl \l__enumext_store_name_tl
  }
\cs_new_protected:Nn \__enumext_stop_save_ans_msg:
  {
    \msg_term:nnVV { enumext } { save-ans-log-hook }
      \g__enumext_envir_name_tl \g__enumext_store_name_tl
  }
```

(*End of definition for* `\__enumext_start_save_ans_msg:` *and* `\__enumext_stop_save_ans_msg:`.)

`\__enumext_storing_set:n`
`\__enumext_storing_exec:`

The function `\__enumext_storing_set:n` first passes the value of the save-ans key to the variable `\l__enumext_store_name_tl` which contains the {⟨*store name*⟩} of the *sequence* and *prop list* to be used. If `\l__enumext_store_name_tl` is *empty* it returns an error message, otherwise it returns the appropriate message `\__enumext_start_save_ans_msg:` and proceed to execute the function `\__enumext_storing_exec:` for `enumext` and `enumext*` environments.

```
\cs_new_protected:Nn \__enumext_storing_set:n
  {
    \tl_set:Ne \l__enumext_store_name_tl {#1}
    \tl_if_empty:NTF \l__enumext_store_name_tl
      {
        \bool_lazy_or:nnT
          { \l__enumext_standard_first_bool } { \l__enumext_starred_first_bool }
          {
            \msg_error:nnV { enumext } { save-ans-empty } \g__enumext_envir_name_tl
          }
      }
      {
        \bool_lazy_or:nnT
          { \l__enumext_standard_first_bool } { \l__enumext_starred_first_bool }
          {
            \__enumext_start_save_ans_msg:
            \__enumext_storing_exec:
          }
      }
  }
```

The function `\__enumext_storing_exec:` will set to true the variable `\l__enumext_store_active_bool` which activates the use of the `\anskey` command and the `anskey*`, `keyans`, `keyans*` and `keyanspic` environments and will set to "true" the variable `\l__enumext_check_answers_bool` used for internal checking answers mechanism set by the `check-ans` and `no-store` keys, copy {⟨*store name*⟩} into the variable `\g__enumext_store_name_tl`.

```
\cs_new_protected:Nn \__enumext_storing_exec:
  {
    \bool_set_true:N \l__enumext_store_active_bool
    \bool_set_true:N \l__enumext_check_answers_bool
    \tl_gset:NV \g__enumext_store_name_tl \l__enumext_store_name_tl
```

The *prop list* `\g__enumext_series_#1_prop` and the *sequence* `\g__enumext_series_#1_seq` will be created globally to *"store content"* in case they do not exist together with the integer variable `\g__enumext_series_#1_int` used by the keys `resume` and `resume*`.

```
    \prop_if_exist:cF { g__enumext_ \l__enumext_store_name_tl _prop }
      {
        \msg_log:nnV { enumext } { store-prop } \l__enumext_store_name_tl
        \prop_new:c { g__enumext_ \l__enumext_store_name_tl _prop }
      }
    \seq_if_exist:cF { g__enumext_ \l__enumext_store_name_tl _seq }
      {
        \msg_log:nnV { enumext } { store-seq } \l__enumext_store_name_tl
        \seq_new:c { g__enumext_ \l__enumext_store_name_tl _seq }
      }
    \int_if_exist:cF { g__enumext_resume_ \l__enumext_store_name_tl _int }
      {
        \msg_log:nnV { enumext } { store-int } \l__enumext_store_name_tl
        \int_new:c { g__enumext_resume_ \l__enumext_store_name_tl _int }
      }
  }
```

(*End of definition for* `\__enumext_storing_set:n` *and* `\__enumext_storing_exec:`.)

13.29.4 The check answer mechanism

The internal mechanism for *"checking answers"* follows this logic:

> If the line begins with `\item` or `\item*` and does NOT *open a nested environment*, each `\item` or `\item*` must contain a *single* execution of the `\anskey` command, i.e. the counter of the executions of the `\anskey` command must be equal to the counter associated with the sum of executions of `\item` and `\item*`.

If the line begins with \item or \item* and *opens a nested environment* each \item or \item* in the nested environment must have a *single* execution of the \anskey command and the counter associated to the sum of \item and \item* executions must decrementing by *"one"* to maintain equality.

In order for the mechanism for the check-answer to work (not counting keyans, keyans* and keyanspic) it is necessary to:

1. Keep track of the total number of \item and \item* (enumerated) that appear within the environment including the nested levels.
2. Keep track of the total number of \item and \item* (enumerated) that appear per level of nesting.
3. Keep track of the number of times the environment nests.

The integer variable associated to the sum of each \item and \item* in the environment \g__enumext_item_number_int must match the integer variable \g__enumext_item_anskey_int associated to the execution of the command \anskey. The cases are analyzed below:

a) If the list only has one level the number of \item + \item* = \anskey
b) If the list has *nested levels*, for each level of nesting the count is decremented by one (for the \item or \item* that opens the nest) so that the account remains the same.

With keyans, keyans* and keyanspic it is enough to increase in one the integer of \anskey. The integers created must be global if they are not lost in the interior levels of nesting and to execute the test a *"hook"* function is used after closing the *first level* of the environment.

13.29.5 Setting check-ans and no-store keys

check-ans
no-store

Defines the keys check-ans and no-store for all levels of enumext and enumext* environments.

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \keys_define:nn { enumext / #1 }
      {
        check-ans .bool_set:N = \l__enumext_check_ans_key_bool,
        check-ans .initial:n = false,
        check-ans .value_required:n = true,
        no-store  .code:n =
          {
            \bool_set_false:N \l__enumext_check_answers_bool
            \bool_set_false:N \l__enumext_check_ans_key_bool
          },
        no-store  .value_forbidden:n = true,
      }
  }
\clist_map_inline:nn
  {
    level-1, level-2, level-3, level-4, enumext*
  }
  { \__enumext_tmp:n {#1} }
```

(*End of definition for* check-ans *and* no-store.)

13.29.6 Set-up check answer mechanism

__enumext_check_ans_active:
__enumext_check_ans_level:

The function __enumext_check_ans_active: will first check the state of the variable \l__enumext_store_name_t that is, the save-ans key is active, if so it will check the state of the variable \l__enumext_check_answers_bool handled by the key no-store and will execute the function __enumext_check_ans_level: only if *"true"*, i.e. the key no-store is not active.

```
\cs_new_protected:Nn \__enumext_check_ans_active:
  {
    \tl_if_empty:NF \l__enumext_store_name_tl
      {
        \bool_if:NT \l__enumext_check_answers_bool
          {
            \__enumext_check_ans_level:
          }
      }
  }
```

The function __enumext_check_ans_level: will decrement by *"one"* the value of the variable \g__enumext_item_number_int which keeps track of the executions of \item and \item* for each

level of nesting of the environment enumext, taking into account whether it is nested within enumext* or the opposite and set \l__enumext_item_number_bool to *"false"* .

```
\cs_new_protected:Nn \__enumext_check_ans_level:
  {
    \int_case:nn { \l__enumext_level_int }
      {
        { 1 }{
                \bool_lazy_all:nT
                  {
                    { \bool_if_p:N \g__enumext_starred_bool }
                    { \int_compare_p:nNn { \l__enumext_level_h_int } = { 1 } }
                  }
                  {
                    \int_gdecr:N \g__enumext_item_number_int
                    \bool_set_false:N \l__enumext_item_number_bool
                  }
        }
        { 2 }{
                \int_gdecr:N \g__enumext_item_number_int
                \bool_set_false:N \l__enumext_item_number_bool
        }
        { 3 }{
                \int_gdecr:N \g__enumext_item_number_int
                \bool_set_false:N \l__enumext_item_number_bool
        }
        { 4 }{
                \int_gdecr:N \g__enumext_item_number_int
                \bool_set_false:N \l__enumext_item_number_bool
        }
      }
```

This is executed only if enumext* is nested in the *"first level"* of enumext, for the rest of the cases the value of \g__enumext_item_number_int is already decreased.

```
    \int_case:nn { \l__enumext_level_h_int }
      {
        { 1 }{
                \bool_lazy_all:nT
                  {
                    { \bool_if_p:N \g__enumext_standard_bool }
                    { \int_compare_p:nNn { \l__enumext_level_int } = { 1 } }
                  }
                  {
                    \int_gdecr:N \g__enumext_item_number_int
                    \bool_set_false:N \l__enumext_item_number_bool
                  }
        }
      }
  }
```

(*End of definition for* __enumext_check_ans_active: *and* __enumext_check_ans_level:.)

__enumext_check_ans_key_hook:

The function __enumext_check_ans_key_hook: will *export* the status of the local variable \l__enumext_check_ans_key_bool to the global variable \g__enumext_check_ans_key_bool only if the key check-ans is active.

```
\cs_new_protected:Nn \__enumext_check_ans_key_hook:
  {
    \bool_lazy_and:nnT
      { \bool_if_p:N \l__enumext_check_ans_key_bool }
      { \bool_if_p:N \g__enumext_standard_bool }
      {
        \bool_gset_true:N \g__enumext_check_ans_key_bool
      }
    \bool_lazy_and:nnT
      { \bool_if_p:N \l__enumext_check_ans_key_bool }
      { \bool_if_p:N \g__enumext_starred_bool }
      {
        \bool_gset_true:N \g__enumext_check_ans_key_bool
      }
  }
```

(*End of definition for* `\__enumext_check_ans_key_hook:`.)

`\__enumext_item_answer_diff:`

The function `\__enumext_item_answer_diff:` will set the value of the variable `\g__enumext_item_answer_diff_` which is used by the functions `\__enumext_check_ans_show:` for the key `save-ans` and by the function `\__enumext_check_ans_log:` by the internal *"check answer"* mechanism. This function will be passed to the function `\__enumext_execute_after_env:`.

```
\cs_new_protected:Nn \__enumext_item_answer_diff:
  {
    \int_gset:Nn \g__enumext_item_answer_diff_int
      {
        \int_sign:n { \g__enumext_item_number_int - \g__enumext_item_anskey_int }
      }
  }
```

(*End of definition for* `\__enumext_item_answer_diff:`.)

`\__enumext_check_ans_show:`
`\__enumext_check_ans_msg_less:`
`\__enumext_check_ans_msg_same_ok:`
`\__enumext_check_ans_msg_greater:`

The function `\__enumext_check_ans_show:` will be executed within the function `\__enumext_execute_after_env` when the key `check-ans` is active, that is, when `\g__enumext_check_ans_key_bool` is *"true"* and will return the appropriate message according to the value of `\g__enumext_item_answer_diff_int` set by the function `\__enumext_item_answer_diff:`.

```
\cs_new_protected:Nn \__enumext_check_ans_show:
  {
    \int_case:nn { \g__enumext_item_answer_diff_int }
      {
        { -1 }{ \__enumext_check_ans_msg_less:    }
        {  0 }{ \__enumext_check_ans_msg_same_ok: }
        {  1 }{ \__enumext_check_ans_msg_greater: }
      }
  }
\cs_new_protected:Nn \__enumext_check_ans_msg_less:
  {
    \msg_warning:nneee { enumext } { item-less-answer } { \g__enumext_store_name_tl }
      { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
  }
\cs_new_protected:Nn \__enumext_check_ans_msg_same_ok:
  {
    \msg_term:nneee { enumext } { items-same-answer } { \g__enumext_store_name_tl }
      { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
  }
\cs_new_protected:Nn \__enumext_check_ans_msg_greater:
  {
    \msg_warning:nneee { enumext } { item-greater-answer }
      { \g__enumext_store_name_tl }
      { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
  }
```

(*End of definition for* `\__enumext_check_ans_show:` *and others.*)

`\__enumext_check_ans_log:`
`\__enumext_check_ans_log_msg_less:`
`\__enumext_check_ans_log_msg_same_ok:`
`\__enumext_check_ans_log_msg_greater:`

The function `\__enumext_check_ans_log:` will be executed within the function `\__enumext_execute_after_env` when the key `check-ans` is not active, that is, when `\g__enumext_check_ans_key_bool` is *"false"* and write in the log the appropriate message according to the value of `\g__enumext_item_answer_diff_int` set by the function `\__enumext_item_answer_diff:`.

```
\cs_new_protected:Nn \__enumext_check_ans_log:
  {
    \int_case:nn { \g__enumext_item_answer_diff_int }
      {
        { -1 }{ \__enumext_check_ans_log_msg_less:    }
        {  0 }{ \__enumext_check_ans_log_msg_same_ok: }
        {  1 }{ \__enumext_check_ans_log_msg_greater: }
      }
  }
\cs_new_protected:Nn \__enumext_check_ans_log_msg_less:
  {
    \msg_log:nneee { enumext } { item-less-answer } { \g__enumext_store_name_tl }
      { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
  }
\cs_new_protected:Nn \__enumext_check_ans_log_msg_same_ok:
  {
    \msg_log:nneee { enumext } { items-same-answer }  { \g__enumext_store_name_tl }
```

```
      { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
  }
\cs_new_protected:Nn \__enumext_check_ans_log_msg_greater:
  {
    \msg_log:nneee { enumext } { item-greater-answer } { \g__enumext_store_name_tl }
      { \g__enumext_envir_name_tl } { \g__enumext_start_line_tl }
  }
```

(*End of definition for* `\__enumext_check_ans_log:` *and others.*)

13.29.7 Check for `\item*` and `\anspic*` commands

`\__enumext_check_starred_cmd:n`

The function `\__enumext_check_starred_cmd:n` performs an *extra check* for the keyans, keyans* and keyanspic environments. Unlike the *check* executed by check-ans key this one is not controlled by any key, it is intended to prevent the forgetting of `\item*` or `\anspic*` in these environments.

```
\cs_new_protected:Nn \__enumext_check_starred_cmd:n
  {
    \int_compare:nNnT
      { \g__enumext_check_starred_cmd_int } = { 0 }
      {
        \msg_warning:nnnV
          { enumext } { missing-starred }{#1} \l__enumext_check_start_line_env_tl
      }
    \int_compare:nNnT
      { \g__enumext_check_starred_cmd_int } > { 1 }
      {
        \msg_warning:nnnV
          { enumext } { many-starred }{#1} \l__enumext_check_start_line_env_tl
      }
    \int_gzero:N \g__enumext_check_starred_cmd_int
    \tl_clear:N \l__enumext_check_start_line_env_tl
  }
```

(*End of definition for* `\__enumext_check_starred_cmd:n`.)

13.30 Keys and functions associated with storage

13.30.1 Keys for `marks`, `wrap` and `show`

The enumext package provides a set of ⟨*keys*⟩ for manipulating *"symbol marks"* associated with *"answers"* and how they are displayed and stored in the *sequence* and *prop list* as well as an internal *"label and ref"* system.

mark-ans*
mark-pos*
mark-sep*
wrap-ans*
wrap-opt
save-sep
show-ans
show-pos

For the keyans and keyans* environments only the keys mark-ans*, mark-pos*, mark-sep*, wrap-ans*, wrap-opt, save-sep, show-ans and show-pos are added.

```
\cs_set_protected:Nn \__enumext_tmp:nn
  {
    \keys_define:nn { enumext / #1 }
      {
        mark-ans* .tl_set:c = { l__enumext_mark_answer_sym_#2_tl },
        mark-ans* .initial:n = \textasteriskcentered,
        mark-ans* .value_required:n = true,
        mark-pos* .choices:nn =
          { left , right , center }
          {
            \int_case:nn { \l_keys_choice_int }
              {
                {1} { \str_set:cn { l__enumext_mark_position_#2_str } { l } }
                {2} { \str_set:cn { l__enumext_mark_position_#2_str } { r } }
                {3} { \str_set:cn { l__enumext_mark_position_#2_str } { c } }
              }
          },
        mark-pos* .initial:n = right,
        mark-pos* .value_required:n = true,
        mark-pos* / unknown .code:n =
          \msg_error:nneee { enumext } { unknown-choice }
            { mark-pos } { left,~right,~center } { \exp_not:n {##1} },
        mark-sep* .dim_set:c = { l__enumext_mark_sym_sep_#2_dim },
        mark-sep* .value_required:n = true,
        wrap-ans* .cs_set_protected:cp = { __enumext_keyans_wrapper_item_#2:n } ##1,
        wrap-ans* .value_required:n = true,
        wrap-opt  .cs_set_protected:cp = { __enumext_keyans_wrapper_opt_#2:n } ##1,
```

```
        wrap-opt  .initial:n = [{##1}],
        wrap-opt  .value_required:n = true,
        save-sep  .tl_set:c = { l__enumext_store_keyans_item_opt_sep_#2_tl },
        save-sep  .initial:n = {,~},
        save-sep  .value_required:n = true,
        show-ans  .bool_set:N = \l__enumext_show_answer_bool,
        show-ans  .initial:n = false,
        show-ans  .value_required:n = true,
        show-pos  .bool_set:N = \l__enumext_show_position_bool,
        show-pos  .initial:n = false,
        show-pos  .value_required:n = true,
      }
  }
\clist_map_inline:nn { {keyans}{v}, {keyans*}{viii} } { \__enumext_tmp:nn #1 }
```

(*End of definition for* `mark-ans*` *and others.*)

`mark-ref` `save-ref` `show-ans` `show-pos` `mark-ans` `mark-pos` `mark-sep` `wrap-ans` `mark-ans*` `mark-pos*` `mark-sep*` `wrap-ans*` `wrap-opt` `save-sep`

Adds the ⟨*keys*⟩ `mark-ref` and `save-ref` related to the *"storage system"* and internal mechanism of *"label and ref"* along with the ⟨*keys*⟩ `show-ans`, `show-pos` and the ⟨*keys*⟩ `mark-ans`, `mark-pos`, `mark-sep` and `wrap-ans` for the command `\anskey`, the environment `anskey*` and the ⟨*keys*⟩ for environments `keyans` and `keyans*` only at the *first level* of `enumext` and `enumext*`.

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \keys_define:nn { enumext / #1 }
      {
        mark-ref .tl_set:N = \l__enumext_mark_ref_sym_tl,
        mark-ref .initial:n = \textreferencemark,
        mark-ref .value_required:n = true,
        save-ref .bool_set:N = \l__enumext_store_ref_key_bool,
        save-ref .initial:n = false,
        save-ref .value_required:n = true,
        show-ans .bool_set:N = \l__enumext_show_answer_bool,
        show-ans .initial:n = false,
        show-ans .value_required:n = true,
        show-pos .bool_set:N = \l__enumext_show_position_bool,
        show-pos .initial:n = false,
        show-pos .value_required:n = true,
        mark-ans .tl_set:N = \l__enumext_mark_answer_sym_tl,
        mark-ans .initial:n = \textasteriskcentered,
        mark-ans .value_required:n = true,
        mark-sep .dim_set:N = \l__enumext_mark_sym_sep_dim,
        mark-sep .value_required:n = true,
        mark-pos .choices:nn =
          { left , right , center }
          {
            \int_case:nn { \l_keys_choice_int }
              {
                {1} { \str_set:Nn \l__enumext_mark_position_str { l } }
                {2} { \str_set:Nn \l__enumext_mark_position_str { r } }
                {3} { \str_set:Nn \l__enumext_mark_position_str { c } }
              }
          },
        mark-pos .initial:n = right,
        mark-pos .value_required:n = true,
        mark-pos / unknown .code:n =
          \msg_error:nneee { enumext } { unknown-choice }
            { mark-pos } { left,~right,~center } { \exp_not:n {##1} },

        wrap-ans  .cs_set_protected:Np = \__enumext_anskey_wrapper:n ##1,
        wrap-ans  .initial:n =
                    {
                      \fbox{\parbox[t]{\dimeval{\itemwidth -2\fboxsep
                        -2\fboxrule}}{##1}}
                    },
        wrap-ans  .value_required:n = true,
        mark-ans* .code:n =
          {
            \keys_set:nn { enumext / keyans  } { mark-ans* = {##1} }
            \keys_set:nn { enumext / keyans* } { mark-ans* = {##1} }
          },
        mark-ans* .value_required:n = true,
```

```
2812          mark-pos* .code:n =
2813            {
2814              \keys_set:nn { enumext / keyans  } { mark-pos* = {##1} }
2815              \keys_set:nn { enumext / keyans* } { mark-pos* = {##1} }
2816            },
2817          mark-pos* .value_required:n = true,
2818          mark-sep* .code:n =
2819            {
2820              \keys_set:nn { enumext / keyans  } { mark-sep* = {##1} }
2821              \keys_set:nn { enumext / keyans* } { mark-sep* = {##1} }
2822            },
2823          mark-sep* .value_required:n = true,
2824          wrap-ans* .code:n =
2825            {
2826              \keys_set:nn { enumext / keyans  } { wrap-ans* = {##1} }
2827              \keys_set:nn { enumext / keyans* } { wrap-ans* = {##1} }
2828            },
2829          wrap-ans* .value_required:n = true,
2830          wrap-opt  .code:n =
2831            {
2832              \keys_set:nn { enumext / keyans  } { wrap-opt = {##1} }
2833              \keys_set:nn { enumext / keyans* } { wrap-opt = {##1} }
2834            },
2835          wrap-opt  .value_required:n = true,
2836          save-sep  .code:n =
2837            {
2838              \keys_set:nn { enumext / keyans  } { save-sep = {##1} }
2839              \keys_set:nn { enumext / keyans* } { save-sep = {##1} }
2840            },
2841          save-sep  .value_required:n = true,
2842        }
2843    }
2844  \clist_map_inline:nn { level-1, enumext* } { \__enumext_tmp:n {#1} }
```

(*End of definition for* `mark-ref` *and others.*)

13.30.2 Storing structure of the environments

The idea behind *"storing structure"* in the *sequence* is to have a copy of the *structure of the environment* in which the key `save-ans` is being executed, so the *optional argument* passed to the levels of the environment in which it is executed must be captured and *"stored"* in the *sequence*.

`\__enumext_store_active_keys:n`
`\__enumext_store_active_keys_vii:n`

The functions `\__enumext_store_active_keys:n` and `\__enumext_store_active_keys_vii:n` will be responsible for the *"storing keys"* filtered from the *optional argument* of the environment in which the key `save-ans` is executed and the levels within this for the `enumext` and `enumext*` environments. This function is executed only if the variable `\l__enumext_store_save_key_X_bool` is false, that is, the key `store-key` is not active, establishing the variable `\l__enumext_store_save_key_X_tl` with the filtered ⟨*keys*⟩.

```
2845  \cs_new_protected:Nn \__enumext_store_active_keys:n
2846    {
2847      \bool_if:cF { l__enumext_store_save_key_ \__enumext_level: _bool }
2848        {
2849          \tl_clear:c { l__enumext_store_save_key_ \__enumext_level: _tl }
2850          \tl_set:ce
2851            { l__enumext_store_save_key_ \__enumext_level: _tl }
2852            { \__enumext_filter_save_key:n {#1} }
2853        }
2854    }
2855  \cs_new_protected:Nn \__enumext_store_active_keys_vii:n
2856    {
2857      \bool_if:NF \l__enumext_store_save_key_vii_bool
2858        {
2859          \tl_clear:N \l__enumext_store_save_key_vii_tl
2860          \tl_set:Ne \l__enumext_store_save_key_vii_tl { \__enumext_filter_save_key:n {#1} }
2861        }
2862    }
```

(*End of definition for* `\__enumext_store_active_keys:n` *and* `\__enumext_store_active_keys_vii:n`.)

13.30.3 Setting `save-key` key

Since this *"storing structure"* in the *sequence* established by the `save-ans` key when executing `\anskey` or `anskey*`, it cannot be modified. The best option here is to have a key that allows modifying the *optional*

argument of the *"storing structure"* in the *sequence*.

save-key

The values set by this key passed in the *optional argument* of the `enumext` and `enumext*` environments will override the values of the `\l__enumext_store_save_key_X_tl` variable set by the functions `\__enumext_store_active_keys:n` and `\__enumext_store_active_keys_vii:n`. Now define the key `save-key` for all levels of `enumext` and `enumext*` environments.

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \keys_define:nn { enumext / enumext* }
      {
        save-key .code:n = { \__enumext_parse_save_key_vii:n {##1} },
        save-key .value_required:n = true,
      }
    \keys_define:nn { enumext / #1 }
      {
        save-key .code:n = { \__enumext_parse_save_key:n {##1} },
        save-key .value_required:n = true,
      }
  }
\clist_map_inline:nn { level-1, level-2, level-3, level-4 } { \__enumext_tmp:n {#1} }
```

(*End of definition for* `save-key`.)

`\__enumext_parse_save_key:n`
`\__enumext_parse_save_key_vii:n`

The functions `\__enumext_parse_save_key:n` and `\__enumext_parse_save_key_vii:n` will be responsible for *"storing keys"* in the variable `\l__enumext_store_save_key_X_tl` for `enumext` and `enumext*`.

```
\cs_new_protected:Nn \__enumext_parse_save_key:n
  {
    \bool_set_true:c { l__enumext_store_save_key_ \__enumext_level: _bool }
    \tl_clear:c { l__enumext_save_key_ \__enumext_level: _tl }
    \tl_set:ce
      { l__enumext_store_save_key_ \__enumext_level: _tl }
      { \__enumext_filter_save_key:n {#1} }
  }
\cs_new_protected:Nn \__enumext_parse_save_key_vii:n
  {
    \bool_set_true:N \l__enumext_store_save_key_vii_bool
    \tl_clear:N \l__enumext_store_save_key_vii_tl
    \tl_set:Ne \l__enumext_store_save_key_vii_tl { \__enumext_filter_save_key:n {#1} }
  }
```

(*End of definition for* `\__enumext_parse_save_key:n` *and* `\__enumext_parse_save_key_vii:n`.)

13.30.4 Internal functions to store optional arguments

`\__enumext_filter_save_key:n`
`\__enumext_filter_save_key_key:n`
`\__enumext_filter_save_key_pair:nn`

The function `\__enumext_filter_save_key:n` will be in charge of *"filtering keys"* to be *stored* in *sequence* where `{#1}` represents the *optional argument* passed to the environment.

```
\cs_new:Nn \__enumext_filter_save_key:n
  {
    \use:e
      {
        \keyval_parse:NNn
          \__enumext_filter_save_key_key:n
          \__enumext_filter_save_key_pair:nn {#1}
      }
  }
```

The function `\__enumext_filter_save_key_key:n` will be responsible for *"filtering keys"* that are passed *"without value"* by excluding the `resume`, `resume*`, `reset`, `reset*`, `no-store` and `base-fix` keys.

```
\cs_new:Nn \__enumext_filter_save_key_key:n
  {
    \str_case:nnF {#1}
      {
        { resume } {} { resume* } {} { reset } {} { reset* } {} { no-store } {}
          { base-fix } {}
      }
      { , { \exp_not:n {#1} } }
  }
```

The function `\__enumext_filter_save_key_pair:nn` will be responsible for *"filtering keys"* that are passed *"with value"* by excluding the `series`, `resume`, `save-ans`, `save-ref`, `save-key`, `check-ans`, `show-ans`,

save-pos, mark-ans, mark-pos, mark-sep, wrap-ans, mark-ans*, mark-pos*, mark-sep*, wrap-ans*, wrap-opt, save-sep, mark-ref, mini-env, mini-sep, mini-right and mini-right* keys.

```
\cs_new:Nn \__enumext_filter_save_key_pair:nn
  {
    \str_case:nnF {#1}
      {
        { series    } {} { resume     } {} { save-ans    } {} { save-ref  } {}
        { save-key  } {} { check-ans  } {} { show-ans    } {} { show-pos  } {}
        { mark-ans  } {} { mark-pos   } {} { mark-sep    } {} { wrap-ans  } {}
        { mark-ans* } {} { mark-pos*  } {} { mark-sep*   } {} { wrap-ans* } {}
        { wrap-opt  } {} { save-sep   } {} { mark-ref    } {} { mini-env  } {}
        { mini-sep  } {} { mini-right } {} { mini-right* } {}
      }
      { , { \exp_not:n {#1} } = { \exp_not:n {#2} } }
  }
```

(*End of definition for* `\__enumext_filter_save_key:n`, `\__enumext_filter_save_key_key:n`, *and* `\__enumext_filter_save_key_pair:nn`.)

13.30.5 Function for storing content in prop list

`\__enumext_store_addto_prop:n`
`\__enumext_store_addto_prop:V`

The function `\__enumext_store_addto_prop:n` stores the {⟨*content*⟩} in *prop list* defined by save-ans key. The *"stored content"* is retrieved by means of the `\getkeyans` command.

The form in which the {⟨*content*⟩} is *"stored"* in the *prop list* is {⟨*position*⟩}{⟨*content*⟩}. This function is used by `\anskey` in enumext and enumext* environments, `\item*` in keyans and keyans* environments and `\anspic*` in keyanspic environment.

```
\cs_new_protected:Nn \__enumext_store_addto_prop:n
  {
    \prop_gput_if_not_in:cen { g__enumext_ \l__enumext_store_name_tl _prop }
      {
        \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } + 1 }
      }
      {#1}
  }
\cs_generate_variant:Nn \__enumext_store_addto_prop:n { V }
```

(*End of definition for* `\__enumext_store_addto_prop:n`.)

13.30.6 Function for storing content in sequence

`\__enumext_store_addto_seq:n`
`\__enumext_store_addto_seq:v`
`\__enumext_store_addto_seq:V`

The function `\__enumext_store_addto_seq:n` stores the {⟨*content*⟩} in *sequence* defined by save-ans key. This function is used by `\anskey` in enumext, `\item*` in keyans and `\anspic` in keyanspic.

The form in which the {⟨*content*⟩} is stored in *sequence* is in an internal enumext or enumext* environments with the *"same structure"* in which the command was executed.

The *"stored content"* is retrieved by means of the `\printkeyans` command.

```
\cs_new_protected:Nn \__enumext_store_addto_seq:n
  {
    \seq_gput_right:cn { g__enumext_ \l__enumext_store_name_tl _seq } {#1}
  }
\cs_generate_variant:Nn \__enumext_store_addto_seq:n { v, V }
```

(*End of definition for* `\__enumext_store_addto_seq:n`.)

13.30.7 Functions for storing structure in the sequence

`\__enumext_store_level_open:`
`\__enumext_store_level_close:`

The *"storing structure"* is handled by the functions `\__enumext_store_level_open:` and `\__enumext_store_level_close:` which are executed per level within the enumext environment.

```
\cs_new_protected:Nn \__enumext_store_level_open:
  {
    \bool_if:NT \l__enumext_check_answers_bool
      {
        \tl_if_empty:cTF { l__enumext_store_save_key_ \__enumext_level: _tl }
          {
            \__enumext_store_addto_seq:n
              {
                \item \begin{enumext}
              }
          }
          {
```

```
            \tl_put_left:cn { l__enumext_store_save_key_ \__enumext_level: _tl }
              {
                \item \begin{enumext} [
              }
            \tl_put_right:cn { l__enumext_store_save_key_ \__enumext_level: _tl }
              {
                ]
              }
            \__enumext_store_addto_seq:v { l__enumext_store_save_key_ \__enumext_level: _tl }
          }
      }
  }
\cs_new_protected:Nn \__enumext_store_level_close:
  {
    \bool_if:NT \l__enumext_check_answers_bool
      {
        \__enumext_store_addto_seq:n { \end{enumext} }
      }
  }
```

(*End of definition for* `\__enumext_store_level_open:` *and* `\__enumext_store_level_close:`.)

`\__enumext_store_level_open_vii:` `\__enumext_store_level_close_vii:`

The *"storing structure"* is handled by the functions `\__enumext_store_level_open_vii:` and `\__enumext_store_level_close_vii:` which are executed in the `enumext*` environment.

```
\cs_new_protected:Nn \__enumext_store_level_open_vii:
  {
    \bool_if:NT \l__enumext_check_answers_bool
      {
        \tl_if_empty:NTF \l__enumext_store_save_key_vii_tl
          {
            \__enumext_store_addto_seq:n
              {
                \item \begin{enumext*}
              }
          }
          {
            \tl_put_left:Nn \l__enumext_store_save_key_vii_tl
              {
                \item \begin{enumext*}[
              }
            \tl_put_right:Nn \l__enumext_store_save_key_vii_tl
              {
                ]
              }
            \__enumext_store_addto_seq:V \l__enumext_store_save_key_vii_tl
          }
      }
  }
\cs_new_protected:Nn \__enumext_store_level_close_vii:
  {
    \bool_if:NT \l__enumext_check_answers_bool
      {
        \__enumext_store_addto_seq:n { \end{enumext*} }
      }
  }
```

(*End of definition for* `\__enumext_store_level_open_vii:` *and* `\__enumext_store_level_close_vii:`.)

13.30.8 Function for show marks and position

`\__enumext_print_keyans_box:NN` `\__enumext_print_keyans_box:cc`

The function `\__enumext_print_keyans_box:NN` print a box in the left margin with `\l__enumext_mark_answer_s` used by the `wrap-ans`, `show-ans` and `show-pos` keys. The function takes two arguments:

`#1:` `\l__enumext_labelwidth_X_dim`
`#2:` `\l__enumext_labelsep_X_dim`

```
\cs_new_protected:Nn \__enumext_print_keyans_box:NN
  {
    \mode_leave_vertical:
    \skip_horizontal:n { -\dim_use:N #2 }
    \hbox_overlap_left:n
      {
```

```
3004          \makebox[ \dim_use:N #1 ][ \l__enumext_mark_position_str ]
3005            {
3006              \tl_use:N \l__enumext_mark_answer_sym_tl
3007            }
3008        }
3009      \skip_horizontal:n { \dim_use:N #2 }
3010    }
3011  \cs_generate_variant:Nn \__enumext_print_keyans_box:NN { cc }
```

(*End of definition for* `\__enumext_print_keyans_box:NN`.)

13.31 The internal label and ref

The function `\__enumext_store_internal_ref:` handles the *"internal label and ref"* system used by the `save-ref` and `mark-ref` keys for `\anskey` allow executing `\ref{`⟨*store name* : *position*⟩`}` and will return `1.(a).i.A`.

`\__enumext_store_internal_ref:` First the dots "." are removed from the current ⟨*labels*⟩, since double dots in references are not wanted, then the result is placed in the variable `\l__enumext_newlabel_arg_two_tl`.

```
3012  \cs_new_protected:Nn \__enumext_store_internal_ref:
3013    {
3014      \cs_set_protected:Nn \__enumext_tmp:n
3015        {
3016          \tl_set_eq:cc { l__enumext_label_copy_##1_tl } { l__enumext_label_##1_tl }
3017          \tl_reverse:c { l__enumext_label_copy_##1_tl }
3018          \tl_remove_once:cn { l__enumext_label_copy_##1_tl } { . }
3019          \tl_reverse:c { l__enumext_label_copy_##1_tl }
3020        }
3021      \clist_map_inline:nn { i, ii, iii, iv, vii } { \__enumext_tmp:n {##1} }
3022      \cs_set:Nn \__enumext_tmp:n
3023        { . \tl_use:c { l__enumext_label_copy_ \int_to_roman:n {##1} _tl } }
```

Here it is necessary to analyze the cases where the environment is started with `enumext*` and if `\anskey` or `anskey*` is running alone in it or if it is running in a nested `enumext` environment within the starting environment.

```
3024      \bool_lazy_all:nT
3025        {
3026          { \bool_if_p:N \g__enumext_starred_bool }
3027          { \int_compare_p:nNn { \l__enumext_level_int } = { 0 } }
3028        }
3029        {
3030          \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
3031            { \tl_use:N \l__enumext_label_copy_vii_tl }
3032        }
3033      \bool_lazy_all:nT
3034        {
3035          { \bool_not_p:n { \g__enumext_standard_bool } }
3036          { \bool_if_p:N \l__enumext_standard_bool }
3037          { \int_compare_p:nNn { \l__enumext_level_int } > { 0 } }
3038        }
3039        {
3040          \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
3041            {
3042              \tl_use:N \l__enumext_label_copy_vii_tl
3043              \int_step_function:nnN { 1 } { \l__enumext_level_int } \__enumext_tmp:n
3044            }
3045        }
```

If started with `enumext` and if `\anskey` or `anskey*` is running alone in it or if it is running in a nested `enumext*` environment within the starting environment.

```
3046      \bool_lazy_all:nT
3047        {
3048          { \bool_if_p:N \g__enumext_standard_bool }
3049          { \int_compare_p:nNn { \l__enumext_level_int } > { 0 } }
3050          { \int_compare_p:nNn { \l__enumext_level_h_int } = { 0 } }
3051        }
3052        {
3053          \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
3054            {
3055              \tl_use:N \l__enumext_label_copy_i_tl
```

```
3056              \int_step_function:nnN { 2 } { \l__enumext_level_int } \__enumext_tmp:n
3057            }
3058        }
3059      \cs_set:Nn \__enumext_tmp:n
3060        { \tl_use:c { l__enumext_label_copy_ \int_to_roman:n {##1} _tl } . }
3061      \bool_lazy_all:nT
3062        {
3063          { \bool_if_p:N \g__enumext_standard_bool }
3064          { \bool_if_p:N \l__enumext_starred_bool }
3065          { \int_compare_p:nNn { \l__enumext_level_int } > { 0 } }
3066        }
3067        {
3068          \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
3069            {
3070              \int_step_function:nnN { 1 } { \l__enumext_level_int } \__enumext_tmp:n
3071              \tl_use:N \l__enumext_label_copy_vii_tl
3072            }
3073        }
```

Now the variable `\l__enumext_newlabel_arg_one_tl` is set, which contains {⟨*store name* : *position*⟩}.

```
3074      \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
3075        {
3076          \l__enumext_store_name_tl \c_colon_str
3077          \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
3078        }
```

Now execute the function `\__enumext_newlabel:nn` and save the result in the variable `\l__enumext_write_aux_file_tl` and finally write it in the `.aux` file.

```
3079      \tl_put_right:Ne \l__enumext_write_aux_file_tl
3080        {
3081          \__enumext_newlabel:nn
3082            { \exp_not:V \l__enumext_newlabel_arg_one_tl }
3083            { \l__enumext_newlabel_arg_two_tl }
3084        }
3085      \l__enumext_write_aux_file_tl
3086    }
```

(*End of definition for* `\__enumext_store_internal_ref:`.)

13.32 Common functions for `\anskey` and `anskey*` environment

`\__enumext_store_anskey_arg:n`

The internal function `\__enumext_store_anskey_arg:n` first passes the {⟨*argument*⟩} to the *prop list*, then checks the state of the variable `\l__enumext_store_ref_key_bool` handled by the `save-ref` key and calls the function `\__enumext_store_internal_ref:` for the *"internal label and ref"* system. After this, if the `show-ans` or `show-pos` keys are active, it shows the *"wrapped"* {⟨*argument*⟩}.

```
3087  \cs_new_protected:Nn \__enumext_store_anskey_arg:n
3088    {
3089      \int_gincr:N \g__enumext_item_anskey_int
3090      \__enumext_store_addto_prop:n {#1}
3091      \bool_if:NT \l__enumext_store_ref_key_bool
3092        {
3093          \__enumext_store_internal_ref:
3094        }
3095      \__enumext_anskey_show_wrap_left:n {#1}
```

Now the processing of the [⟨*key* = *val*⟩] passed to the command starts, building the `\item` in the variable `\l__enumext_store_anskey_arg_tl` which is *"stored"* in the *sequence*. First the variable `\l__enumext_store_anskey_arg_tl` is cleared and the ⟨*keys*⟩ are processed; if the `break-col` key is present and the command is running under `enumext` (not in `enumext*`), `\columnbreak` and then `\item` are added.

```
3096      \tl_clear:N \l__enumext_store_anskey_arg_tl
3097      \bool_lazy_and:nnT
3098        { \bool_if_p:N \l__enumext_store_columns_break_bool }
3099        { \bool_not_p:n { \l__enumext_starred_bool } }
3100        {
3101          \tl_put_left:Nn \l__enumext_store_anskey_arg_tl { \columnbreak }
3102        }
3103      \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { \item }
```

If the item-join key is present and the command is running under enumext*, (⟨number⟩) is added to \l__enumext_store_anskey_arg_tl.

```
    \bool_lazy_and:nnT
      { \bool_not_p:n { \l__enumext_starred_bool } }
      { \int_compare_p:nNn { \l__enumext_store_item_join_int } > { 1 } }
      {
        \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
          {
            ( \exp_not:V \l__enumext_store_item_join_int )
          }
      }
```

Then the keys item-star, item-sym* and item-pos* are reviewed and passed to \l__enumext_store_anskey_arg along with the {⟨argument⟩} for \anskey or ⟨body⟩ for anskey*.

```
    \bool_if:NTF \l__enumext_store_item_star_bool
      {
        \tl_put_right:Nn \l__enumext_store_anskey_arg_tl { * }
        \tl_if_empty:NF \l__enumext_store_item_symbol_tl
          {
            \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
              {
                [ \exp_not:V \l__enumext_store_item_symbol_tl ]
              }
          }
        \dim_compare:nT
          {
            \l__enumext_store_item_symbol_sep_dim != \c_zero_dim
          }
          {
            \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
              {
                [ \exp_not:V \l__enumext_store_item_symbol_sep_dim ]
              }
          }
        \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#1}
      }
      {
        \tl_put_right:Nn \l__enumext_store_anskey_arg_tl {#1}
      }
```

Finally it checks if the save-ref key is active along with the hyperref package load, if both conditions are met, it will create the \hyperlink with *"symbol"* set by mark-ref key and then store in *sequence*.

```
    \bool_lazy_and:nnT
      { \bool_if_p:N \l__enumext_store_ref_key_bool }
      { \bool_if_p:N \l__enumext_hyperref_bool }
      {
        \tl_put_right:Ne \l__enumext_store_anskey_arg_tl
          {
            \hfill \exp_not:N \hyperlink
              { \exp_not:V \l__enumext_newlabel_arg_one_tl }
                 { \exp_not:V \l__enumext_mark_ref_sym_tl }
          }
      }
    \__enumext_store_addto_seq:V \l__enumext_store_anskey_arg_tl
  }
```

(*End of definition for* __enumext_store_anskey_arg:n.)

__enumext_anskey_show_wrap_arg:n

The function __enumext_anskey_show_wrap_arg:n *"wraps"* the {⟨argument⟩} passed to \anskey and the ⟨body⟩ for anskey* when using the wrap-ans and wrap-sep keys.

```
\cs_new_protected:Nn \__enumext_anskey_show_wrap_arg:n
  {
    \par
    \bool_if:NTF \l__enumext_starred_bool
      {
        \dim_compare:nNnT { \l__enumext_mark_sym_sep_dim } = { \c_zero_dim }
          {
             \dim_set:Nn \l__enumext_mark_sym_sep_dim { \l__enumext_labelsep_vii_dim }
          }
        \__enumext_print_keyans_box:NN
```

```
3161            \l__enumext_labelwidth_vii_dim \l__enumext_mark_sym_sep_dim
3162        }
3163        {
3164          \dim_compare:nNnT { \l__enumext_mark_sym_sep_dim } = { \c_zero_dim }
3165            {
3166              \dim_set:Nn \l__enumext_mark_sym_sep_dim
3167                {
3168                  \dim_use:c {l__enumext_labelsep_ \__enumext_level: _dim }
3169                }
3170            }
3171          \__enumext_print_keyans_box:cc
3172            { l__enumext_labelwidth_ \__enumext_level: _dim } { l__enumext_mark_sym_sep_dim }
3173        }
3174      \__enumext_anskey_wrapper:n {#1}
3175    }
```

(*End of definition for* `\__enumext_anskey_show_wrap_arg:n`.)

`\__enumext_anskey_show_wrap_left:n`

The function `\__enumext_anskey_show_wrap_left:n` will show the *"mark"* defined by the `mark-ans` key or the *"position"* of the {⟨*content*⟩} stored in the *prop list* when using the `show-pos` key on the left margin next to the *"wraps"* {⟨*argument*⟩} passed to `\anskey` and the ⟨*body*⟩ in `anskey*` on the right side when using the `show-ans` key.

```
3176 \cs_new_protected:Nn \__enumext_anskey_show_wrap_left:n
3177   {
3178     \bool_if:NT \l__enumext_show_answer_bool
3179       {
3180         \__enumext_anskey_show_wrap_arg:n {#1}
3181       }
3182     \bool_if:NT \l__enumext_show_position_bool
3183       {
3184         \tl_set:Ne \l__enumext_mark_answer_sym_tl
3185           {
3186             \group_begin:
3187             \exp_not:N \normalfont
3188             \exp_not:N \footnotesize [ \int_eval:n
3189               {
3190                 \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
3191               }
3192               ]
3193             \group_end:
3194           }
3195         \__enumext_anskey_show_wrap_arg:n {#1}
3196       }
3197   }
```

(*End of definition for* `\__enumext_anskey_show_wrap_left:n`.)

13.32.1 Definition of error messages

`anskey-unnumber-item`
`anskey-empty-arg`
`anskey-math-mode`

Messages used by `\anskey` and `anskey*`.

```
3198 \msg_new:nnn { enumext } { anskey-unnumber-item }
3199   {
3200     Can't~store~with~an~unnumbered~\c_backslash_str item~\msg_line_context:.
3201   }
3202 \msg_new:nnn { enumext } { anskey-empty-arg }
3203   {
3204     Can't~store~empty~content~\msg_line_context:.
3205   }
3206 \msg_new:nnn { enumext } { anskey-math-mode }
3207   {
3208     #1~can't~work~in~math~mode~\msg_line_context:.
3209   }
```

(*End of definition for* `anskey-unnumber-item`, `anskey-empty-arg`, *and* `anskey-math-mode`.)

13.33 The command \anskey

Since *"content"* is stored in a `list` environment within *sequences* and the options passed to each level can be managed (more or less), it is necessary to have a little more control over `\item` when storing.

The `\anskey` command will cover this point and give it similar behaviour to that of `\item` in the `enumext` and `enumext*` environments executed as follows `\anskey`[⟨*key* = *val*⟩]{⟨*content*⟩}.

break-col
item-join
item-star
item-sym*
item-pos*
unknown
__enumext_anskey_unknown:n
__enumext_anskey_unknown:nn

First, the keys `break-col`, `item-join`, `item-star`, `item-sym*` and `item-pos*` are added.

```
\keys_define:nn { enumext / anskey }
  {
    break-col .bool_set:N = \l__enumext_store_columns_break_bool,
    break-col .default:n = true,
    break-col .value_forbidden:n = true,
    item-join .int_set:N = \l__enumext_store_item_join_int,
    item-join .value_required:n = true,
    item-star .bool_set:N = \l__enumext_store_item_star_bool,
    item-star .default:n = true,
    item-star .value_forbidden:n = true,
    item-sym* .tl_set:N = \l__enumext_store_item_symbol_tl,
    item-sym* .value_required:n = true,
    item-pos* .dim_set:N = \l__enumext_store_item_symbol_sep_dim,
    item-pos* .value_required:n = true,
    unknown   .code:n = { \__enumext_anskey_unknown:n {#1} },
  }
```

The ⟨*keys*⟩ are stored in `\l_keys_key_str` and the value (if any) is passed as an argument to the function `\__enumext_anskey_unknown:n`.

```
\cs_new_protected:Nn \__enumext_anskey_unknown:n
  {
    \exp_args:NV \__enumext_anskey_unknown:nn \l_keys_key_str {#1}
  }
\cs_new_protected:Nn \__enumext_anskey_unknown:nn
  {
    \tl_if_blank:nTF {#2}
      {
        \msg_error:nnn { enumext } { anskey-cmd-key-unknown } {#1}
      }
      {
        \msg_error:nnnn { enumext } { anskey-cmd-key-value-unknown } {#1} {#2}
      }
  }
```

(*End of definition for* `break-col` *and others.*)

The `\anskey` command will only be present when using the `save-ans` key in `enumext` and `enumext*` environments, otherwise it will return an error.

\anskey

The function `\__enumext_anskey_safe_outer:` is called first to be sure where the command is executed, then the state of the variable `\l__enumext_check_answers_bool` set by the key `no-store` is checked; if it is true, `\g__enumext_item_anskey_int` is incremented for the internal *"check answer"* system and execute the function `\__enumext_anskey_safe_inner:n` to ensure that the command is not nested and that the argument is not empty, finally search the `[`⟨*key* = *val*⟩`]` and call the function `\__enumext_store_anskey_arg:n`.

```
\NewDocumentCommand \anskey { o +m }
  {
    \__enumext_anskey_safe_outer:
    \group_begin:
      \bool_if:NT \l__enumext_check_answers_bool
        {
          \tl_if_novalue:nF {#1}
            {
              \keys_set:nn { enumext / anskey } {#1}
            }
          \tl_if_blank:nTF {#2}
            {
              \msg_error:nn { enumext } { anskey-empty-arg }
            }
            {
              \__enumext_anskey_safe_inner:
              \__enumext_store_anskey_arg:n {#2}
            }
        }
    \group_end:
  }
```

(*End of definition for* `\anskey`. *This function is documented on page 15.*)

13.33.1 Definition of error messages for \anskey

anskey-wrong-place
anskey-nested
anskey-cmd-key-unknown
anskey-cmd-key-value-unknown

Messages used by \anskey command.

```
\msg_new:nnn { enumext } { anskey-wrong-place }
  {
    Wrong~place~for~command~'\c_backslash_str #1'~\msg_line_context:.\\
    '\c_backslash_str #1'~works~in~the~environment~'#2'.
  }
\msg_new:nnn { enumext } { anskey-nested }
  {
    The~command~\c_backslash_str anskey~can't~be~nested~\msg_line_context:.
  }
\msg_new:nnnn { enumext } { anskey-cmd-key-unknown }
  {
    The~key~'#1'~is~unknown~by~'\c_backslash_str anskey'~and~is~being~ignored~
    \msg_line_context:.
  }
  {
    The~command~'\c_backslash_str anskey'~does~not~have~a~key~called~'#1'.\\
    Check~that~you~have~spelled~the~key~name~correctly.
  }
\msg_new:nnnn { enumext } { anskey-cmd-key-value-unknown }
  {
    The~key~'#1=#2'~is~unknown~by~'\c_backslash_str anskey'~and~is~being~
    ignored~\msg_line_context:.
  }
  {
    The~command~'\c_backslash_str anskey'~does~not~have~a~key~called~'#1'.\\
    Check~that~you~have~spelled~the~key~name~correctly.
  }
```

(*End of definition for* `anskey-wrong-place` *and others.*)

13.33.2 Internal functions for the command

__enumext_anskey_safe_outer:
__enumext_anskey_safe_inner:

The __enumext_store_anskey_safe_outer: function will return the appropriate messages when the command is executed outside the environment in which the save-ans key was activated.

```
\cs_new_protected:Nn \__enumext_anskey_safe_outer:
  {
    \bool_if:NF \l__enumext_store_active_bool
      {
        \msg_error:nnnn { enumext } { anskey-wrong-place }{ anskey }{ enumext }
      }
    \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
      {
        \msg_error:nnnn { enumext } { command-wrong-place }{ anskey }{ keyans }
      }
    \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
      {
        \msg_error:nnnn { enumext } { command-wrong-place }{ anskey }{ keyans* }
      }
    \int_compare:nNnT { \l__enumext_keyans_pic_level_int } = { 1 }
      {
        \msg_error:nnnn { enumext }
          { command-wrong-place }{ anskey }{ keyanspic }
      }
  }
```

The __enumext_anskey_safe_inner: function will first check if the command is nested, if preceded by a not numbered \item or if it is in *math mode* returning the appropriate messages.

```
\cs_new_protected:Nn \__enumext_anskey_safe_inner:
  {
    \int_incr:N \l__enumext_anskey_level_int
    \int_compare:nNnT { \l__enumext_anskey_level_int } > { 1 }
      {
        \msg_error:nn { enumext } { anskey-nested }
      }
    \bool_if:NF \l__enumext_item_number_bool
      {
        \msg_error:nn { enumext } { anskey-unnumber-item }
      }
```

```
    \mode_if_math:T
      {
        \msg_error:nne { enumext } { anskey-math-mode }
          { \c_backslash_str anskey }
      }
  }
```

(*End of definition for* `\__enumext_anskey_safe_outer:` *and* `\__enumext_anskey_safe_inner:`.)

13.34 The environment anskey*

The original implementation of the anskey* environment used non-public functions from the scontents[4] package, which was not the best approach. Fortunately LaTeX release 2025-06-01 implemented the new `c-type` argument in the ltcmd[13], with which the ⟨*body*⟩ of the environment can be recorded in *verbatim mode*, and `\tl_retokenize:n` (wrapper around the `\scantokens`) provided by LaTeX3 release 2025-07-08 does the work as the original implementation.

break-col
item-join
item-star
item-sym*
item-pos*
force-eol
write-env
overwrite
unknown

First, the same keys from the `\anskey` command are added along with the `force-eol`, `write-env` and `overwrite` keys that were in the original implementation that used the scontents support package for these.

```
\keys_define:nn { enumext / anskey* }
  {
    break-col .bool_set:N = \l__enumext_store_columns_break_bool,
    break-col .default:n = true,
    break-col .value_forbidden:n = true,
    item-join .int_set:N = \l__enumext_store_item_join_int,
    item-join .value_required:n = true,
    item-star .bool_set:N = \l__enumext_store_item_star_bool,
    item-star .default:n = true,
    item-star .value_forbidden:n = true,
    item-sym* .tl_set:N = \l__enumext_store_item_symbol_tl,
    item-sym* .value_required:n = true,
    item-pos* .dim_set:N = \l__enumext_store_item_symbol_sep_dim,
    item-pos* .value_required:n = true,
    force-eol .bool_set:N = \l__enumext_anskey_env_force_eol_bool,
    force-eol .initial:n = false,
    force-eol .default:n = true,
    write-env .code:n =
      {
        \bool_set_true:N \l__enumext_write_anskey_env_bool
        \tl_set:Nn \l__enumext_write_anskey_env_file_name_tl {#1}
      },
    write-env .value_required:n = true,
    overwrite .bool_set:N = \l__enumext_anskey_env_overwrite_bool,
    overwrite .initial:n = false,
    overwrite .default:n = true,
    unknown   .code:n = { \__enumext_anskey_env_unknown:n {#1} },
  }
```

(*End of definition for* `break-col` *and others.*)

__enumext_anskey_env_unknown:n
__enumext_anskey_env_unknown:nn

The ⟨*keys*⟩ are stored in `\l_keys_key_str` and the value (if any) is passed as an argument to the function `\__enumext_anskey_env_unknown:n`.

```
\cs_new_protected:Nn \__enumext_anskey_env_unknown:n
  {
    \exp_args:NV \__enumext_anskey_env_unknown:nn \l_keys_key_str {#1}
  }
\cs_new_protected:Nn \__enumext_anskey_env_unknown:nn
  {
    \tl_if_blank:nTF {#2}
      {
        \msg_error:nnn { enumext } { anskey-env-key-unknown } {#1}
      }
      {
        \msg_error:nnnn { enumext } { anskey-env-key-value-unknown } {#1} {#2}
      }
  }
```

(*End of definition for* `\__enumext_anskey_env_unknown:n` *and* `\__enumext_anskey_env_unknown:nn`.)

__enumext_anskey_env_file_if_writable:n
__enumext_anskey_env_file_if_writable:nT
__enumext_anskey_env_file_if_writable:nF
__enumext_anskey_env_file_if_writable:nTF
__enumext_anskey_env_file_write:nn
__enumext_anskey_env_file_write:VV

The conditional function `\__enumext_anskey_env_file_if_writable:n` used by the `write-env` and `overwrite` keys in the `anskey*` environment to determine whether the output file is written or overwritten.

```
\prg_new_protected_conditional:Npnn \__enumext_anskey_env_file_if_writable:n #1
  { T, F, TF }
  {
    \bool_if:NTF \l__enumext_write_anskey_env_bool
      {
        \file_if_exist:nTF {#1}
          {
            \bool_if:NTF \l__enumext_anskey_env_overwrite_bool
              {
                \msg_warning:nne { enumext } { overwrite-file } {#1}
                \prg_return_true:
              }
              {
                \msg_warning:nne { enumext } { not-writing } {#1}
                \prg_return_false:
              }
          }
          {
            \msg_warning:nne { enumext } { writing-file } {#1}
            \prg_return_true:
          }
      }
      { \prg_return_false: }
  }
```

The `\__enumext_anskey_env_file_write:nn` function is used by the `write-env` key in the `anskey*` environment to write the output file with the ⟨*body*⟩ of the environment.

```
\cs_new_protected:Nn \__enumext_anskey_env_file_write:nn
  {
    \__enumext_anskey_env_file_if_writable:nT {#1}
      {
        \iow_open:Nn \l__enumext_write_anskey_env_file_iow {#1}
        \iow_now:Nn  \l__enumext_write_anskey_env_file_iow {#2}
        \iow_close:N \l__enumext_write_anskey_env_file_iow
      }
  }
\cs_generate_variant:Nn \__enumext_anskey_env_file_write:nn { VV }
```

(*End of definition for* `\__enumext_anskey_env_file_if_writable:n` *and others.*)

anskey*

First, the function `\__enumext_anskey_env_safe_outer:` is called to make sure where the environment is running, then the state of the variable `\l__enumext_check_answers_bool` set by the key `no-store` is checked. If it is true, it looks for [⟨*key* = *val*⟩] and verifies that the *argument* `c-type` ⟨*body*⟩ is not empty. Finally, it runs the internal check function `\__enumext_anskey_env_safe_inner:n` and call the function `\__enumext_store_anskey_arg:n`.

```
\NewDocumentEnvironment{anskey*}{ o c }
  {
    \__enumext_anskey_env_safe_outer:
    \bool_if:NT \l__enumext_check_answers_bool
      {
        \tl_if_novalue:nF {#1}
          {
            \keys_set:nn { enumext / anskey* } {#1}
          }
        \tl_if_blank:nTF {#2}
          {
            \msg_error:nn { enumext } { anskey-empty-arg }
          }
          {
            \__enumext_anskey_env_safe_inner:
            \__enumext_store_anskey_env:n {#2}
          }
      }
  } { }
```

(*End of definition for* `anskey*`. *This function is documented on page* 15.)

©2024–2026 by Pablo González L

13.34.1 Definition of error messages for anskey*

anskey-env-error

Message used by reserved anskey* environment by enumext package.

```
\msg_new:nnnn { enumext } { anskey-env-error }
  {
    The~environment~'#1'~is~reserved~by\\
    'enumext'~package,~It~is~already~defined.
  }
  {
    The~environment~'#1'~is~defined~internally~
    for~the~'save-ans'~key~with~save-ans~key~active.~See~documentation.\\
  }
```

(*End of definition for* anskey-env-error.)

anskey-env-wrong
anskey-env-key-unknown
anskey-env-key-value-unknown
overwrite-file
writing-file
not-writing

Messages used by anskey* environment.

```
\msg_new:nnn { enumext } { anskey-env-wrong }
  {
    The~environment~anskey*~cannot~be~used~in~'#1'~\msg_line_context:.
  }
\msg_new:nnnn { enumext } { anskey-env-key-unknown }
  {
    The~key~'#1'~is~unknown~by~environment~
    'anskey*'~and~is~being~ignored~\msg_line_context:.
  }
  {
    The~environment~'anskey*'~does~not~have~a~key~called~'#1'.\\
    Check~that~you~have~spelled~the~key~name~correctly.
  }
\msg_new:nnnn { enumext } { anskey-env-key-value-unknown }
  {
    The~key~'#1=#2'~is~unknown~by~environment~
    'anskey*'~and~is~being~ignored~\msg_line_context:.
  }
  {
    The~environment~'anskey*'~does~not~have~a~key~called~'#1'.\\
    Check~that~you~have~spelled~the~key~name~correctly.
  }
\msg_new:nnn { enumext } { overwrite-file }
  {
    Overwriting~file~'#1'.
  }
\msg_new:nnn { enumext } { writing-file }
  {
    Writing~file~'#1'.
  }
\msg_new:nnn { enumext } { not-writing }
  {
    File~'#1'~already~exists.~Not~writing.
  }
```

(*End of definition for* anskey-env-wrong *and others.*)

13.34.2 Internal functions for the environment

__enumext_anskey_env_safe_outer:
__enumext_anskey_env_safe_inner:
__enumext_store_anskey_env:n

The function __enumext_store_anskey_safe_outer: will return the appropriate messages when anskey* is executed outside the environment in which the save-ans key was activated or within the keyans, keyans* or keyanspic environments.

```
\cs_new_protected:Nn \__enumext_anskey_env_safe_outer:
  {
    \bool_if:NF \l__enumext_store_active_bool
      {
        \msg_error:nnn { enumext } { anskey-env-error } { anskey* }
      }
    \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
      {
        \msg_error:nnn { enumext } { anskey-env-wrong }{ keyans }
      }
    \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
      {
```

```
3475          \msg_error:nnn { enumext } { anskey-env-wrong } { keyans* }
3476        }
3477      \int_compare:nNnT { \l__enumext_keyans_pic_level_int } = { 1 }
3478        {
3479          \msg_error:nnn { enumext } { anskey-env-wrong } { keyanspic }
3480        }
3481    }
```

The function `\__enumext_anskey_env_safe_inner:` will first check if preceded by a not numbered `\item` or if it is in *math mode* returning the appropriate messages.

```
3482 \cs_new_protected:Nn \__enumext_anskey_env_safe_inner:
3483   {
3484     \bool_if:NF \l__enumext_item_number_bool
3485       {
3486         \msg_error:nn { enumext } { anskey-unnumber-item }
3487       }
3488     \mode_if_math:T
3489       {
3490         \msg_error:nnn { enumext } { anskey-math-mode } { anskey* }
3491       }
3492   }
```

The `\__enumext_store_anskey_env:n` function will first pass the `c`-type argument ⟨*body*⟩ to the variable `\l__enumext_store_anskey_env_tl` and replace the macro `\obeyedline` with `^^J` and then execute the `write-env` and `overwrite` keys, check the state of the variable `\l__enumext_anskey_env_force_eol_bool` managed by the `force-eol` key, and adds `\c__enumext_anskey_env_hidden_space_str` if necessary. Finally it uses `\exp_args:Ne` on the `\__enumext_store_anskey_arg:n` to expand the `\tl_retokenize:n` function which rescans the `\l__enumext_store_anskey_env_tl` variable before processing it.

```
3493 \cs_new_protected:Nn \__enumext_store_anskey_env:n
3494   {
3495     \tl_set:Nn \l__enumext_store_anskey_env_tl {#1}
3496     \RenewDocumentCommand \obeyedline { } { \iow_char:N \^^J }
3497     \tl_replace_all:Nee \l__enumext_store_anskey_env_tl { \obeyedline }
3498       { \iow_char:N \^^J }
3499     \__enumext_anskey_env_file_write:VV
3500       \l__enumext_write_anskey_env_file_name_tl \l__enumext_store_anskey_env_tl
3501     \bool_if:NF \l__enumext_anskey_env_force_eol_bool
3502       {
3503         \tl_put_right:Ne \l__enumext_store_anskey_env_tl
3504           {
3505             \c__enumext_anskey_env_hidden_space_str
3506           }
3507       }
3508     \exp_args:Ne
3509       \__enumext_store_anskey_arg:n
3510         {
3511           \tl_retokenize:n { \l__enumext_store_anskey_env_tl }
3512         }
3513   }
```

Since `\obeyedline` can be redefined by the user, for example to `\mbox{}\par`, it is necessary to redefine it to `^^J` in order to use `\tl_replace_all:Nee` otherwise it returns an error.

(*End of definition for* `\__enumext_anskey_env_safe_outer:`, `\__enumext_anskey_env_safe_inner:`, *and* `\__enumext_store_anskey_env:n`.)

13.35 Executing `check-ans` system and write `.log`

`\__enumext_execute_after_env:`

The `\__enumext_execute_after_env:` function will first return the appropriate message for the end of the environment in which the `save-ans` key is being executed, then call the `\__enumext_item_answer_diff:` function and then writes the values of the global variables used to the `.log` file. If the key `check-ans` is active, it executes the function `\__enumext_check_ans_show:` and shows the result in the terminal, otherwise it executes the function `\__enumext_check_ans_log:` and writes the results in the `.log` file, and finally executes the function `\__enumext_reset_global_vars:` returning the used variables to their original state.

```
3514 \cs_new_protected:Nn \__enumext_execute_after_env:
3515   {
3516     \int_compare:nNnT { \l__enumext_level_int } = { 0 }
3517       {
3518         \tl_if_empty:NF \g__enumext_store_name_tl
```

©2024–2026 by Pablo González L

```
3519            {
3520              \__enumext_stop_save_ans_msg:
3521              \__enumext_item_answer_diff:
3522              \__enumext_log_global_vars:
3523              \__enumext_log_answer_vars:
3524              \bool_if:NTF \g__enumext_check_ans_key_bool
3525                {
3526                  \__enumext_check_ans_show:
3527                }
3528                { \__enumext_check_ans_log: }
3529            }
3530          \__enumext_reset_global_vars:
3531        }
3532    }
```

This function is passed to the function `\__enumext_after_env:nn` for the environments `enumext` (§13.42) and `enumext*` (§13.47) and it is executed only when the environments are not nested or at some level of these.

(*End of definition for* `\__enumext_execute_after_env:`.)

13.36 Common functions for keyans, keyans* and keyanspic

13.36.1 Storing content in prop list

`\__enumext_keyans_addto_prop:n`

The function `\__enumext_keyans_addto_prop:n` will pass the current ⟨*label*⟩ for `\item*` in `keyans` environment and the current ⟨*label*⟩ for `\anspic*` in `keyanspic` environment followed by the ⟨*contents*⟩ of the *optional argument* of both commands to the `\l__enumext_store_current_label_tl` variable, which will be stored to the *prop list* defined by the `save-ans` key using the function `\__enumext_store_addto_prop:V`.

```
3533 \cs_new_protected:Nn \__enumext_keyans_addto_prop:n
3534   {
3535     \tl_clear:N \l__enumext_store_current_label_tl
3536     \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
3537       {
3538         \tl_put_right:Ne \l__enumext_store_current_label_tl { \l__enumext_label_vi_tl }
3539       }
3540       {
3541         \tl_put_right:Ne \l__enumext_store_current_label_tl { \l__enumext_label_v_tl }
3542       }
```

If the *optional argument* is present and the `save-sep` key is not empty, it is saved.

```
3543     \tl_if_novalue:nF {#1}
3544       {
3545         \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_v_tl
3546           {
3547             \tl_put_right:NV \l__enumext_store_current_label_tl
3548               \l__enumext_store_keyans_item_opt_sep_v_tl
3549           }
3550         \tl_put_right:Nn \l__enumext_store_current_label_tl {#1}
3551       }
3552     \__enumext_store_addto_prop:V \l__enumext_store_current_label_tl
3553   }
```

(*End of definition for* `\__enumext_keyans_addto_prop:n`.)

13.36.2 The save-ref key for keyans, keyans* and keyanspic

The *"internal label and ref"* system for the `keyans`, `keyans*` and `keyanspic` environments has *slight differences* with the one implemented for `\anskey` basically because in this environments the interest is in the current ⟨*label*⟩ for `\item*` and `\anspic*` with the ⟨*contents*⟩ of the *optional argument*. The mechanism defined here allows executing `\ref{`⟨*store name : position*⟩`}` and will return `1.(A)`.

`\__enumext_keyans_store_ref:`
`\__enumext_keyans_store_ref_aux_i:`
`\__enumext_keyans_store_ref_aux_ii:`

The function `\__enumext_keyans_store_ref:` handles the *"internal label and ref"* system used by the `save-ref` key for `\item*` and `\anspic*` commands. First, copies of the current ⟨*labels*⟩ are created and the dots "`.`" are removed from them, since double dots in references are not wanted.

```
3554 \cs_new_protected:Nn \__enumext_keyans_store_ref:
3555   {
3556     \bool_if:NT \l__enumext_store_ref_key_bool
3557       {
3558         \cs_set_protected:Nn \__enumext_tmp:n
3559           {
3560             \tl_set_eq:cc { l__enumext_label_copy_##1_tl } { l__enumext_label_##1_tl }
```

```
3561              \tl_reverse:c { l__enumext_label_copy_##1_tl }
3562              \tl_remove_once:cn { l__enumext_label_copy_##1_tl } { . }
3563              \tl_reverse:c { l__enumext_label_copy_##1_tl }
3564            }
3565          \clist_map_inline:nn { i, v, vi, vii, viii } { \__enumext_tmp:n {##1} }
3566          \__enumext_keyans_store_ref_aux_i:
3567        }
3568    }
```

The auxiliary function `\__enumext_keyans_store_ref_aux_i:` set the variable `\l__enumext_newlabel_arg_one` which will contain {⟨*store name : position*⟩} analyzing whether the environment in which they are executed is `enumext*` or `enumext`.

```
3569 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_i:
3570   {
3571     \bool_if:NT \g__enumext_starred_bool
3572       {
3573         \tl_set_eq:NN \l__enumext_label_copy_i_tl \l__enumext_label_copy_vii_tl
3574       }
3575     \int_compare:nNnT { \l__enumext_keyans_pic_level_int } = { 1 }
3576       {
3577         \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
3578           { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_vi_tl }
3579       }
3580     \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
3581       {
3582         \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
3583           { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_v_tl }
3584       }
3585     \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
3586       {
3587         \tl_put_right:Ne \l__enumext_newlabel_arg_two_tl
3588           { \l__enumext_label_copy_i_tl . \l__enumext_label_copy_viii_tl }
3589       }
3590     \tl_put_right:Ne \l__enumext_newlabel_arg_one_tl
3591       {
3592         \l__enumext_store_name_tl \c_colon_str
3593         \int_eval:n { \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop } }
3594       }
3595     \__enumext_keyans_store_ref_aux_ii:
3596   }
```

Now the auxiliary function `\__enumext_keyans_store_ref_aux_ii:` saves the result in the variable `\l__enumext_write_aux_file_tl` and finally writes it in the `.aux` file.

```
3597 \cs_new_protected:Nn \__enumext_keyans_store_ref_aux_ii:
3598   {
3599     \tl_put_right:Ne \l__enumext_write_aux_file_tl
3600       {
3601         \__enumext_newlabel:nn
3602           { \exp_not:V \l__enumext_newlabel_arg_one_tl }
3603           { \l__enumext_newlabel_arg_two_tl }
3604       }
3605     \l__enumext_write_aux_file_tl
3606   }
```

(*End of definition for* `\__enumext_keyans_store_ref:` , `\__enumext_keyans_store_ref_aux_i:` , *and* `\__enumext_keyans_store_ref_aux_ii:`.)

13.36.3 Storing content in sequence

`\__enumext_keyans_addto_seq:n`
`\__enumext_keyans_addto_seq_link:`

The function `\__enumext_keyans_addto_seq:n` will pass the contents of the current ⟨*label*⟩ `\l__enumext_label_v_tl` for the `keyans` environment and the `\l__enumext_label_vi_tl` for the `keyanspic` environment when using `\item*` and `\anspic*`, followed by the ⟨*contents*⟩ of the *optional argument* of both commands to the `\l__enumext_store_current_label_tl` variable to the sequence defined by the `save-ans` key.

```
3607 \cs_new_protected:Nn \__enumext_keyans_addto_seq:n
3608   {
3609     \tl_clear:N \l__enumext_store_current_label_tl
3610     \int_compare:nNnTF { \l__enumext_keyans_pic_level_int } = { 1 }
3611       {
3612         \tl_put_right:Ne \l__enumext_store_current_label_tl
3613           { \item \l__enumext_label_vi_tl }
```

```
      }
      {
        \tl_put_right:Ne \l__enumext_store_current_label_tl { \item \l__enumext_label_v_tl }
      }
    \tl_if_novalue:nF {#1}
      {
        \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_v_tl
          {
            \tl_put_right:NV \l__enumext_store_current_label_tl
              \l__enumext_store_keyans_item_opt_sep_v_tl
          }
        \tl_put_right:Nn \l__enumext_store_current_label_tl {#1}
      }
    \__enumext_keyans_addto_seq_link:
  }
```

Checks if the save-ref key is active along with the hyperref package load, if both conditions are met, it will create the \hyperlink and then store using the __enumext_store_addto_seq:V function. Finally, copy the contents of the variable \l__enumext_store_current_label_tl into the global variable \g__enumext_check_ans_item_tl to be used by the function __enumext_check_starred_cmd:n and increment the value of the integer variable \g__enumext_item_anskey_int handled by the check-ans key.

```
\cs_new_protected:Nn \__enumext_keyans_addto_seq_link:
  {
    \bool_lazy_and:nnT
      { \bool_if_p:N \l__enumext_store_ref_key_bool }
      { \bool_if_p:N \l__enumext_hyperref_bool }
      {
        \tl_put_right:Ne \l__enumext_store_current_label_tl
          {
            \hfill \exp_not:N \hyperlink
              {
                \exp_not:V \l__enumext_newlabel_arg_one_tl
              }
              { \exp_not:V \l__enumext_mark_ref_sym_tl }
          }
      }
    \__enumext_store_addto_seq:V \l__enumext_store_current_label_tl
    \bool_if:NT \l__enumext_check_answers_bool
      {
        \int_gincr:N \g__enumext_item_anskey_int
      }
  }
```

(*End of definition for* __enumext_keyans_addto_seq:n *and* __enumext_keyans_addto_seq_link:.)

13.36.4 The show-ans and show-pos keys for keyans and keyanspic

__enumext_keyans_save_item_opt:n
__enumext_keyans_show_item_opt:
__enumext_keyans_show_item_opt_viii:

The function __enumext_keyans_save_item_opt:n will save the optional argument of \item* and \anspic* in the variable \l__enumext_store_current_opt_arg_tl.

```
\cs_new_protected:Nn \__enumext_keyans_save_item_opt:n
  {
    \tl_if_novalue:nF {#1}
      {
        \tl_set:Nn \l__enumext_store_current_opt_arg_tl {#1}
      }
  }
```

The function __enumext_keyans_show_item_opt: will print the optional arguments of \item* and \anspic* when the show-ans or show-pos keys are set next to the key wrap-opt in keyans and keyanspic environments.

```
\cs_new_protected:Nn \__enumext_keyans_show_item_opt:
  {
    \tl_if_empty:NF \l__enumext_store_current_opt_arg_tl
      {
        \bool_lazy_or:nnT
          { \bool_if_p:N \l__enumext_show_answer_bool }
          { \bool_if_p:N \l__enumext_show_position_bool }
          {
            \__enumext_keyans_wrapper_opt_v:n
              { \l__enumext_store_current_opt_arg_tl } \c_space_tl
```

```
            }
        }
    }
```

The function __enumext_keyans_show_item_opt_viii: will print the optional argument of \item* when the show-ans or show-pos keys are set next to the key wrap-opt in keyans* environment.

```
\cs_new_protected:Nn \__enumext_keyans_show_item_opt_viii:
  {
    \tl_if_empty:NF \l__enumext_store_current_opt_arg_tl
      {
        \bool_lazy_or:nnT
          { \bool_if_p:N \l__enumext_show_answer_bool }
          { \bool_if_p:N \l__enumext_show_position_bool }
          {
            \__enumext_keyans_wrapper_opt_viii:n
              { \l__enumext_store_current_opt_arg_tl } \c_space_tl
          }
      }
  }
```

(*End of definition for* __enumext_keyans_save_item_opt:n, __enumext_keyans_show_item_opt:, *and* __enumext_keyans_show_item_opt_viii:.)

__enumext_keyans_pos_mark_set:
__enumext_keyans_show_ans:
__enumext_keyans_show_pos:

The function __enumext_keyans_pos_mark_set: adjusts the horizontal spaces for the mark-sep* key taking into account the value of the align key and the width of ⟨*label*⟩.

```
\cs_new_protected:Nn \__enumext_keyans_pos_mark_set:
  {
    \__enumext_label_width_by_box:Nn
      \l__enumext_mark_sep_tmpa_dim { \l__enumext_label_v_tl }
    \str_case:Vn \l__enumext_align_label_pos_v_str
      {
        { l }
            {
              \dim_set:Nn \l__enumext_mark_sep_tmpb_dim { \c_zero_dim }
            }
        { r }
            {
              \dim_set:Nn \l__enumext_mark_sep_tmpb_dim
                { \l__enumext_labelwidth_v_dim - \l__enumext_mark_sep_tmpa_dim }
            }
        { c }
            {
              \dim_set:Nn \l__enumext_mark_sep_tmpb_dim
                { 0.5\l__enumext_labelwidth_v_dim - 0.5\l__enumext_mark_sep_tmpa_dim }
            }
      }
```

Sets the default values for the keys mark-ans*, mark-sep* and mark-pos*.

```
    \dim_compare:nNnT { \l__enumext_mark_sym_sep_v_dim } = { \c_zero_dim }
      {
        \dim_set:Nn \l__enumext_mark_sym_sep_v_dim { \l__enumext_labelsep_v_dim }
      }
    \tl_set_eq:NN \l__enumext_mark_answer_sym_tl \l__enumext_mark_answer_sym_v_tl
    \dim_add:Nn \l__enumext_mark_sym_sep_v_dim { \l__enumext_mark_sep_tmpb_dim }
    \str_set_eq:NN \l__enumext_mark_position_str \l__enumext_mark_position_v_str
  }
```

The function __enumext_keyans_show_ans: will print the ⟨*symbol*⟩ set by the mark-ans* key when the show-ans key is active.

```
\cs_new_protected:Nn \__enumext_keyans_show_ans:
  {
    \bool_lazy_all:nT
      {
        { \bool_if_p:N \l__enumext_show_answer_bool   }
        { \bool_if_p:N \l__enumext_item_wrap_key_bool }
      }
      {
        \__enumext_keyans_pos_mark_set:
        \__enumext_print_keyans_box:NN
          \l__enumext_labelwidth_v_dim \l__enumext_mark_sym_sep_v_dim
```

©2024–2026 by Pablo González L

```
      }
  }
```

The function `\__enumext_keyans_show_pos:` will print the ⟨*position*⟩ of the stored content in *prop list*. Need add `1` to `\g__enumext_#1_prop` for `keyans` environment.

```
\cs_new_protected:Nn \__enumext_keyans_show_pos:
  {
    \int_compare:nNnTF { \l__enumext_keyans_level_int } = { 1 }
      {
        \int_incr:N \l__enumext_show_pos_tmp_int
      }
      {
        \int_zero:N \l__enumext_show_pos_tmp_int
      }
    \bool_lazy_all:nT
      {
        { \bool_if_p:N \l__enumext_show_position_bool }
        { \bool_if_p:N \l__enumext_item_wrap_key_bool }
      }
      {
        \tl_set:Ne \l__enumext_mark_answer_sym_v_tl
          {
            \group_begin:
              \exp_not:N \normalfont
              \exp_not:N \footnotesize [ \int_eval:n
                {
                  \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
                  + \l__enumext_show_pos_tmp_int
                }
              ]
            \group_end:
          }
        \__enumext_keyans_pos_mark_set:
        \__enumext_print_keyans_box:NN
          \l__enumext_labelwidth_v_dim \l__enumext_mark_sym_sep_v_dim
      }
  }
```

(*End of definition for* `\__enumext_keyans_pos_mark_set:`, `\__enumext_keyans_show_ans:`, *and* `\__enumext_keyans_show_pos:`.)

13.36.5 Definition of error messages

`keyans-wrong-level`
`wrong-place`

Messages used by `keyans`, `keyans*` and `keyanspic` environments.

```
\msg_new:nnn { enumext } { keyans-wrong-level }
  {
    Wrong~level~position~for~'keyans'~\msg_line_context:.\\
    The~environment~'keyans'~can~only~be~in~the~first~level.
  }
\msg_new:nnn { enumext } { wrong-place }
  {
    Wrong~place~for~'#1'~environment~\msg_line_context:.\\
    '#1'~is~only~found~with~'#2'~in~'enumext'.
  }
```

(*End of definition for* `keyans-wrong-level` *and* `wrong-place`.)

13.37 Redefining `\item` and `\makelabel` in `enumext`

Redefining the `\item` command is not as simple as it seems. This command works in conjunction with the `\makelabel` command, so both of them have to be redefined; in addition, a couple of *global* variables are needed to pass the values from one command to the other.

When *labeling* PDF is active `\makelabel` is redefined as `\hss #1` and the only way to get the `align` key to work correctly is to redefine `\makelabel` using `\makebox`. The best way to implement this is to use the conditional command `\IfDocumentMetadataTF` to force this redefinition and the dedicated `mode-box` key to manually activate it by the user.

The `\item` and `\item[`⟨*custom*⟩`]` commands work in the usual way on `enumext`, and `\item*`, `\item*[`⟨*symbol*⟩`]` and `\item*[`⟨*symbol*⟩`][`⟨*offset*⟩`]` are added.

`\__enumext_default_item:n`

First it checks if the *optional argument* is present; if it is NOT present, it checks the state of the variable `\l__enumext_check_answers_bool` set by the key `no-store`, sets the boolean

variable \l__enumext_wrap_label_X_bool to "true" for the key wrap-label and executes __enumext_item_std:w and the key itemindent; otherwise it checks the state of the boolean variable \l__enumext_wrap_label_opt_X_bool set by the key wrap-label* and executes __enumext_item_std:w with the *optional argument* and the key itemindent.

```
\cs_new_protected:Nn \__enumext_default_item:n
  {
    \tl_if_novalue:nTF {#1}
      {
        \bool_if:NT \l__enumext_check_answers_bool
          {
            \int_gincr:N \g__enumext_item_number_int
            \bool_set_true:N \l__enumext_item_number_bool
          }
        \bool_set_true:c { l__enumext_wrap_label_ \__enumext_level: _bool }
        \__enumext_item_std:w \tl_use:c { l__enumext_fake_item_indent_ \__enumext_level: _tl }
      }
      {
        \bool_set_eq:cc
          { l__enumext_wrap_label_ \__enumext_level: _bool }
          { l__enumext_wrap_label_opt_ \__enumext_level: _bool }
        \__enumext_item_std:w [#1] \tl_use:c { l__enumext_fake_item_indent_ \__enumext_level: _tl
      }
  }
```

(*End of definition for* __enumext_default_item:n.)

__enumext_item_starred_exec:nn
__enumext_item_starred_exec:

The \item*, \item*[⟨*symbol*⟩] and \item*[⟨*symbol*⟩][⟨*offset*⟩] work like the *numbered* \item, but placing a ⟨*symbol*⟩ to the *"left"* of the ⟨*label*⟩ separated from it by the value the second *optional argument* ⟨*offset*⟩.

#1 : \l__enumext_item_symbol_X_tl
#2 : \l__enumext_item_symbol_sep_X_dim

First a copy of \l__enumext_item_symbol_X_tl is made, which is set by the key item-sym* or passed as *"first" optional argument* in the global variable \g__enumext_item_symbol_aux_tl, followed by setting the variable \l__enumext_item_symbol_sep_X_dim set by the key item-pos* or by the *"second" optional argument*, then the state of the variable \l__enumext_check_answers_bool set by the key no-store is checked, the boolean variable \l__enumext_wrap_label_X_bool is set to "true" for the key wrap-label and __enumext_item_std:w and the key itemindent are executed.

```
\cs_new_protected:Nn \__enumext_item_starred_exec:nn
  {
    \tl_if_novalue:nTF {#1}
      {
        \tl_gset_eq:Nc
          \g__enumext_item_symbol_aux_tl { l__enumext_item_symbol_ \__enumext_level: _tl }
      }
      {
        \tl_gset:Nn \g__enumext_item_symbol_aux_tl {#1}
      }
    \tl_if_novalue:nTF {#2}
      {
        \dim_set_eq:cc
          { l__enumext_item_symbol_sep_ \__enumext_level: _dim }
          { l__enumext_labelsep_ \__enumext_level: _dim }
      }
      {
        \dim_set:cn { l__enumext_item_symbol_sep_ \__enumext_level: _dim } {#2}
      }
    \bool_if:NT \l__enumext_check_answers_bool
      {
        \int_gincr:N \g__enumext_item_number_int
        \bool_set_true:N \l__enumext_item_number_bool
      }
    \bool_set_true:c { l__enumext_wrap_label_ \__enumext_level: _bool }
    \__enumext_item_std:w \tl_use:c { l__enumext_fake_item_indent_ \__enumext_level: _tl }
  }
```

The function __enumext_item_starred_exec: will be responsible for executing \item* for the enumext environment.

```
\cs_new_protected:Nn \__enumext_item_starred_exec:
  {
    \tl_if_empty:cF { l__enumext_item_symbol_ \__enumext_level: _tl }
```

©2024–2026 by Pablo González L

```
      {
        \mode_leave_vertical:
        \skip_horizontal:n { -\dim_use:c { l__enumext_item_symbol_sep_
          \__enumext_level: _dim } }
        \hbox_overlap_left:n { \g__enumext_item_symbol_aux_tl }
        \skip_horizontal:n { \dim_use:c { l__enumext_item_symbol_sep_
          \__enumext_level: _dim } }
      }
  }
```

(*End of definition for* `\__enumext_item_starred_exec:nn` *and* `\__enumext_item_starred_exec:`.)

`\__enumext_redefine_item:`

The function `\__enumext_redefine_item:` will redefine the `\item` command in the `enumext` environment adding `\item*`. This function is passed to `\__enumext_list_arg_two_X:` used in the definition of the `enumext` environment (§13.42).

```
\cs_new_protected:Nn \__enumext_redefine_item:
  {
    \RenewDocumentCommand \item { s o o }
      {
        \bool_if:nTF {##1}
          {
            \__enumext_item_starred_exec:nn {##2} {##3}
          }
          { \__enumext_default_item:n {##2} }
      }
  }
```

(*End of definition for* `\__enumext_redefine_item:`.)

`\__enumext_make_label:`
`\__enumext_make_label_std:`
`\__enumext_make_label_box:`

The function `\__enumext_make_label:` redefines `\makelabel` for the keys `mode-box`, `align`, `font`, `wrap-label`, `wrap-label*` and `\item*` for `enumext` environment. This function is passed to `\__enumext_list_arg_two_X:` used in the definition of the `enumext` environment (§13.42).

```
\cs_new_protected:Nn \__enumext_make_label:
  {
    \IfDocumentMetadataTF
      {
        \__enumext_make_label_box:
      }
      {
        \bool_if:NTF \l__enumext_mode_box_bool
          {
             \__enumext_make_label_box:
          }
          {
             \__enumext_make_label_std:
          }
      }
  }
```

Standard definition when `\DocumentMetadata` is not active.

```
\cs_new_protected:Nn \__enumext_make_label_std:
  {
    \RenewDocumentCommand \makelabel { m }
      {
        \tl_use:c { l__enumext_label_fill_left_ \__enumext_level: _tl }
        \__enumext_item_starred_exec:
        \tl_use:c { l__enumext_label_font_style_ \__enumext_level: _tl }
        \bool_if:cTF { l__enumext_wrap_label_ \__enumext_level: _bool }
          {
            \use:c { __enumext_wrapper_label_ \__enumext_level: :n } {##1}
          }
          {##1}
        \tl_use:c { l__enumext_label_fill_right_ \__enumext_level: _tl }
        \tl_gclear:N \g__enumext_item_symbol_aux_tl
      }
  }
```

Definition using `\makebox` when `\DocumentMetadata` is active or `mode-box` is active.

Here it is necessary to use \strut\smash to maintain text *alignment* in case the user wants to use \labelbx for example. In experiments with *mimicking* the description environment it was the only way out and it seems to have no adverse effects and may serve in the future as a basis for a more generic list environment package than enumext.

```
\cs_new_protected:Nn \__enumext_make_label_box:
  {
    \RenewDocumentCommand \makelabel { m }
      {
        \strut\smash
          {
            \makebox
              [ \dim_use:c { l__enumext_labelwidth_ \__enumext_level: _dim } ]
              [ \str_use:c { l__enumext_align_label_pos_ \__enumext_level: _str } ]
              {
                \__enumext_item_starred_exec:
                \tl_use:c { l__enumext_label_font_style_ \__enumext_level: _tl }
                \bool_if:cTF { l__enumext_wrap_label_ \__enumext_level: _bool }
                  {
                    \use:c { __enumext_wrapper_label_ \__enumext_level: :n } {##1}
                  }
                  {##1}
                \tl_gclear:N \g__enumext_item_symbol_aux_tl
              }
          } % close smash
      }
  }
```

(*End of definition for* __enumext_make_label:, __enumext_make_label_std:, *and* __enumext_make_label_box:.)

13.38 Setting item-sym* and item-pos* keys

In order to have a cleaner implementation of \item* for the enumext and enumext* environments it is best to define a couple of keys that allow controlling and setting by default the ⟨*symbol*⟩ and its ⟨*offset*⟩.

item-sym*
item-pos*

Define and set item-sym* and item-pos* keys for enumext and enumext*.

```
\cs_set_protected:Nn \__enumext_tmp:nn
  {
    \keys_define:nn { enumext / #1 }
      {
        item-sym* .tl_set:c = { l__enumext_item_symbol_#2_tl },
        item-sym* .value_required:n = true,
        item-sym* .initial:n = {\textborn},
        item-pos* .dim_set:c = { l__enumext_item_symbol_sep_#2_dim },
        item-pos* .value_required:n = true,
      }
  }
\clist_map_inline:nn
  {
    {level-1}{i}, {level-2}{ii}, {level-3}{iii}, {level-4}{iv}, {enumext*}{vii}
  }
  { \__enumext_tmp:nn #1 }
```

(*End of definition for* item-sym* *and* item-pos*.)

13.39 Handling unknown keys

At this point in the code no more ⟨*keys*⟩ will be added. Since the definitions of environments and commands have already been quite *restrictive*, the only thing left to do is to be equally strict with the ⟨*keys*⟩ (consistency matters).

Well, the paragraph above did not hold entirely: more ⟨*keys*⟩ had to be added than planned, and not everything turns out as expected.

13.39.1 Handling unknown keys for keyans, keyans* and keyanspic

unknown
__enumext_keyans_unknown_keys:n
__enumext_keyans_unknown_keys:nn

Define and set unknown key for keyans, keyans* and keyanspic environments. Here it is necessary to set \l__enumext_envir_name_tl in case an unknown key is passed using \setenumext.

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \keys_define:nn { enumext / #1 }
      {
        unknown .code:n =
```

```
3911            {
3912              \tl_set:Nn \l__enumext_envir_name_tl {#1}
3913              \__enumext_keyans_unknown_keys:n {##1}
3914            },
3915        }
3916    }
3917 \clist_map_inline:nn { keyans, keyans*, keyanspic } { \__enumext_tmp:n {#1} }
```

Internal functions for handling unknown key.

```
3918 \cs_new_protected:Nn \__enumext_keyans_unknown_keys:n
3919   {
3920     \exp_args:NV \__enumext_keyans_unknown_keys:nn \l_keys_key_str {#1}
3921   }
3922 \cs_new_protected:Nn \__enumext_keyans_unknown_keys:nn
3923   {
3924     \tl_if_blank:nTF {#2}
3925       {
3926         \msg_error:nne { enumext } { keyans-unknown-key } {#1}
3927       }
3928       {
3929         \msg_error:nnee { enumext } { keyans-unknown-key-value } {#1} {#2}
3930       }
3931   }
```

(*End of definition for* unknown , __enumext_keyans_unknown_keys:n , *and* __enumext_keyans_unknown_keys:nn.)

13.39.2 Handling unknown keys for enumext*

unknown
__enumext_starred_unknown_keys:n
__enumext_starred_unknown_keys:nn

Define and set unknown key for enumext* environment.

```
3932 \keys_define:nn { enumext / enumext* }
3933   {
3934     unknown .code:n =
3935       {
3936         \tl_set:Ne \l__enumext_envir_name_tl { enumext* }
3937         \__enumext_starred_unknown_keys:n {#1}
3938       },
3939   }
```

Internal functions for handling unknown key.

```
3940 \cs_new_protected:Nn \__enumext_starred_unknown_keys:n
3941   {
3942     \exp_args:NV \__enumext_starred_unknown_keys:nn \l_keys_key_str {#1}
3943   }
3944 \cs_new_protected:Nn \__enumext_starred_unknown_keys:nn
3945   {
3946     \tl_if_blank:nTF {#2}
3947       {
3948         \msg_error:nne { enumext } { starred-unknown-key } {#1}
3949       }
3950       {
3951         \msg_error:nnee { enumext } { starred-unknown-key-value } {#1} {#2}
3952       }
3953   }
```

(*End of definition for* unknown , __enumext_starred_unknown_keys:n , *and* __enumext_starred_unknown_keys:nn.)

13.39.3 Handling unknown keys for enumext

unknown
__enumext_standard_unknown_keys:n
__enumext_standard_unknown_keys:nn

Defines and set the key unknown for enumext environment.

```
3954 \cs_set_protected:Nn \__enumext_tmp:n
3955   {
3956     \keys_define:nn { enumext / level-#1 }
3957       {
3958         unknown .code:n =
3959           {
3960             \int_set:Nn \l__enumext_level_int {#1}
3961             \tl_set:Ne \l__enumext_envir_name_tl { enumext }
3962             \__enumext_standard_unknown_keys:n {##1}
3963           },
3964       }
3965   }
3966 \clist_map_inline:nn {1, 2, 3, 4} { \__enumext_tmp:n {#1} }
```

©2024–2026 by Pablo González L

Internal functions for handling unknown key.

```
\cs_new_protected:Nn \__enumext_standard_unknown_keys:n
  {
    \exp_args:NV \__enumext_standard_unknown_keys:nn \l_keys_key_str {#1}
  }
\cs_new_protected:Nn \__enumext_standard_unknown_keys:nn
  {
    \tl_if_blank:nTF {#2}
      {
        \msg_error:nne { enumext } { standard-unknown-key } {#1}
      }
      {
        \msg_error:nnee { enumext } { standard-unknown-key-value } {#1} {#2}
      }
  }
```

(*End of definition for* unknown , __enumext_standard_unknown_keys:n , *and* __enumext_standard_unknown_keys:nn.)

13.39.4 Definition of error messages

starred-unknown-key
starred-unknown-key-value

Message used by unknown ⟨*keys*⟩ in enumext*. environment.

```
\msg_new:nnnn { enumext } { starred-unknown-key }
  {
    The~key~'#1'~is~unknown~by~environment~
    '\l__enumext_envir_name_tl'~and~is~being~ignored~\msg_line_context:.
  }
  {
    The~environment~'\l__enumext_envir_name_tl'~does~not~
    have~a~key~called~'#1'.\\
    Check~that~you~have~spelled~the~key~name~correctly.
  }
\msg_new:nnnn { enumext } { starred-unknown-key-value }
  {
    The~key~'#1=#2'~is~unknown~by~environment~
    '\l__enumext_envir_name_tl'~and~is~being~ignored~\msg_line_context:.
  }
  {
    The~environment~'\l__enumext_envir_name_tl'~does~not~
    have~a~key~called~'#1'.\\
    Check~that~you~have~spelled~the~key~name~correctly.
  }
```

(*End of definition for* starred-unknown-key *and* starred-unknown-key-value.)

standard-unknown-key
standard-unknown-key-value

Message used by unknown ⟨*keys*⟩ in enumext environment.

```
\msg_new:nnnn { enumext } { standard-unknown-key }
  {
    The~key~'#1'~is~unknown~by~environment~'\l__enumext_envir_name_tl'~on~level~
    \int_use:N \l__enumext_level_int \c_space_tl and~is~being~ignored~
    \msg_line_context:.
  }
  {
    The~environment~'\l__enumext_envir_name_tl'~does~not~
    have~a~key~called~'#1'~on~level~\int_use:N \l__enumext_level_int.\\
    Check~that~you~have~spelled~the~key~name~correctly.
  }
\msg_new:nnnn { enumext } { standard-unknown-key-value }
  {
    The~key~'#1=#2'~is~unknown~by~environment~'\l__enumext_envir_name_tl'~on~level~
    \int_use:N \l__enumext_level_int \c_space_tl and~is~being~ignored~
    \msg_line_context:.
  }
  {
    The~environment~'\l__enumext_envir_name_tl'~does~not~
    have~a~key~called~'#1'~on~level~\int_use:N \l__enumext_level_int.\\
    Check~that~you~have~spelled~the~key~name~correctly.
  }
```

(*End of definition for* standard-unknown-key *and* standard-unknown-key-value.)

©2024–2026 by Pablo González L

keyans-unknown-key
keyans-unknown-key-value

Message used by unknown ⟨*keys*⟩ in keyans, keyans* and keyanspic environments.

```
\msg_new:nnnn { enumext } { keyans-unknown-key }
  {
    The~key~'#1'~is~unknown~by~environment~
    '\l__enumext_envir_name_tl'~and~is~being~ignored~\msg_line_context:.
  }
  {
    The~environment~'\l__enumext_envir_name_tl'~does~not~
    have~a~key~called~'#1'.\\
    Check~that~you~have~spelled~the~key~name~correctly.
  }
\msg_new:nnnn { enumext } { keyans-unknown-key-value }
  {
    The~key~'#1=#2'~is~unknown~by~environment~
    '\l__enumext_envir_name_tl'~and~is~being~ignored~\msg_line_context:.
  }
  {
    The~environment~'\l__enumext_envir_name_tl'~does~not~
    have~a~key~called~'#1'.\\
    Check~that~you~have~spelled~the~key~name~correctly.
  }
```

(*End of definition for* keyans-unknown-key *and* keyans-unknown-key-value.)

13.40 Redefining \item and \makelabel in keyans

The \item and \item[⟨*custom*⟩] commands work in the usual way in keyans, but the \item* and \item*[⟨*content*⟩] commands *store* the current ⟨*label*⟩ next to the ⟨*content*⟩ if it is present in the *sequence* and *prop list* defined by save-ans key.

__enumext_keyans_default_item:n

The function __enumext_keyans_default_item:n executes the original behavior of the \item along with the keys wrap-label, wrap-label* and itemindent.

```
\cs_new_protected:Nn \__enumext_keyans_default_item:n
  {
    \tl_if_novalue:nTF {#1}
      {
        \bool_set_true:N \l__enumext_wrap_label_v_bool
        \__enumext_item_std:w \tl_use:N \l__enumext_fake_item_indent_v_tl
      }
      {
        \bool_set_eq:NN \l__enumext_wrap_label_v_bool \l__enumext_wrap_label_opt_v_bool
        \__enumext_item_std:w [#1] \tl_use:N \l__enumext_fake_item_indent_v_tl
      }
  }
```

(*End of definition for* __enumext_keyans_default_item:n.)

__enumext_keyans_starred_item:n

The function __enumext_keyans_starred_item:n will take as argument #1 the *optional argument* [⟨*content*⟩] passed to \item* and save it via the __enumext_keyans_save_item_opt:n function, then activate the wrap-label key, execute \item using __enumext_item_std:w, the itemindent key and print the *optional argument* using the __enumext_keyans_show_item_opt: function handled by the wrap-opt key.

```
\cs_new_protected:Nn \__enumext_keyans_starred_item:n
  {
    \__enumext_keyans_save_item_opt:n {#1}
    \bool_set_true:N \l__enumext_wrap_label_v_bool
    \__enumext_item_std:w \tl_use:N \l__enumext_fake_item_indent_v_tl
    \__enumext_keyans_show_item_opt:
```

Now *store* the current ⟨*label*⟩ first in the *prop list* (including the *optional argument*), run the internal *"label and ref"* system if the save-ref key is active, then *store* in the *sequence* and finally increments \g__enumext_check_starred_cmd_int for internal check system.

```
    \__enumext_keyans_addto_prop:n {#1}
    \__enumext_keyans_store_ref:
    \__enumext_keyans_addto_seq:n {#1}
    \int_gincr:N \g__enumext_check_starred_cmd_int
  }
```

(*End of definition for* __enumext_keyans_starred_item:n.)

\item*
__enumext_keyans_redefine_item:

The function __enumext_keyans_redefine_item: is responsible for adding the *starred argument* and *optional argument* by the __enumext_list_arg_two_v: function in the definition of the keyans environment. Here the variable \l__enumext_item_wrap_key_bool used by the wrap-ans* key is set to true only when \item* is executed and, additionally, it is necessary to use \peek_remove_spaces:n to avoid an unwanted space when using \item* together with the itemindent key. This function is passed to __enumext_list_arg_two_v: used in the definition of the keyans environment (§13.41).

```
\cs_new_protected:Nn \__enumext_keyans_redefine_item:
  {
    \RenewDocumentCommand \item { s o }
      {
        \bool_if:nTF {##1}
          {
            \bool_set_true:N \l__enumext_item_wrap_key_bool % wrap-ans*
            \peek_remove_spaces:n
              {
                \__enumext_keyans_starred_item:n {##2}
              }
          }
          {
            \bool_set_false:N \l__enumext_item_wrap_key_bool
            \__enumext_keyans_default_item:n {##2}
          }
      }
  }
```

(*End of definition for* \item* *and* __enumext_keyans_redefine_item:. *This function is documented on page* 17.)

__enumext_keyans_make_label:
__enumext_keyans_wrapper_label:n
__enumext_keyans_make_label_std:
__enumext_keyans_make_label_box:
__enumext_wrapper_label_v:n

The function __enumext_keyans_make_label: redefines \makelabel for the keys mode-box, align, font, wrap-label, wrap-label*, wrap-ans* and \item* for keyans environment. This function is passed to __enumext_list_arg_two_v: used in the definition of the keyans environment (§13.41).

```
\cs_new_protected:Nn \__enumext_keyans_make_label:
  {
    \IfDocumentMetadataTF
      {
        \__enumext_keyans_make_label_box:
      }
      {
        \bool_if:NTF \l__enumext_mode_box_bool
          {
            \__enumext_keyans_make_label_box:
          }
          {
            \__enumext_keyans_make_label_std:
          }
      }
  }
```

Conditionals are added to the __enumext_keyans_wrapper_label:n function to handle the keys wrap-ans*, wrap-label and wrap-label*.

```
\cs_new_protected:Nn \__enumext_keyans_wrapper_label:n
  {
    \bool_lazy_all:nT
      {
        { \bool_if_p:N \l__enumext_wrap_label_v_bool         }
        { \bool_if_p:N \l__enumext_show_answer_bool          }
        { \bool_if_p:N \l__enumext_item_wrap_key_bool        }
        { \cs_if_exist_p:N \__enumext_keyans_wrapper_item_v:n }
      }
      {
        \cs_set_eq:NN \__enumext_wrapper_label_v:n \__enumext_keyans_wrapper_item_v:n
      }
    \bool_if:NTF \l__enumext_wrap_label_v_bool
      {
        \__enumext_wrapper_label_v:n {#1}
      }
      {#1}
  }
```

Standard definition when \DocumentMetadata is not active.

```
\cs_new_protected:Nn \__enumext_keyans_make_label_std:
```

```
{
  \RenewDocumentCommand \makelabel { m }
    {
      \tl_use:N \l__enumext_label_fill_left_v_tl
      \__enumext_keyans_show_ans:
      \__enumext_keyans_show_pos:
      \tl_use:N \l__enumext_label_font_style_v_tl
      \__enumext_keyans_wrapper_label:n {##1}
      \tl_use:N \l__enumext_label_fill_right_v_tl
    }
}
```

Definition using \makebox when \DocumentMetadata is active or mode-box is active.

```
\cs_new_protected:Nn \__enumext_keyans_make_label_box:
  {
    \RenewDocumentCommand \makelabel { m }
      {
        \strut\smash
          {
            \makebox[ \l__enumext_labelwidth_v_dim ][ \l__enumext_align_label_pos_v_str ]
              {
                \__enumext_keyans_show_ans:
                \__enumext_keyans_show_pos:
                \tl_use:N \l__enumext_label_font_style_v_tl
                \__enumext_keyans_wrapper_label:n {##1}
              }
          }
      }
  }
```

(*End of definition for* `\__enumext_keyans_make_label:` *and others.*)

13.41 Second argument of the lists

At this point in the code most of the tools needed to create a *custom* `list` environment have already been programmed. Remember that the `\__enumext_start_list:nn` function takes two arguments: the "first" one is ready, and the "second" one is defined for all levels of the `enumext` environment, the `keyans` environment and the `enumext*` and `keyans*` environments.

Here the `\__enumext_list_arg_two_X:` function is implemented, which is responsible for setting all the list parameters, the counter, the redefinition of `\item`, `\makelabel` along with the keys `ref`, `itemindent` and `show-length`.

13.41.1 Calculation of `\leftmargin` and `\itemindent`

Consider the figure 9 where the default margins (on the left) of a list are represented.




Figure 9: Representation of standard horizontal lengths in `list` environment.

The idea is to have control over these margins so that the list does not overlap the left margin of the page. The *key* relationship is that the *"right edge"* of the `\labelsep` equals the *"right edge"* of the `\itemindent`, so that the left edge of the *"label box"* is at `\leftmargin`+`\itemindent` minus `\labelwidth`+`\labelsep`. Thus, the handling of the margins by the package will be as shown in the figure 10.




Figure 10: Representation of horizontal lengths concept in list in enumext.

Where the default values will look like in the figure 11.

`\__enumext_calc_hspace:NNNNNNN`
`\__enumext_calc_hspace:ccccccc`

The function `\__enumext_calc_hspace:NNNNNNN` takes seven arguments to be able to determine horizontal spaces for all list environment:




Figure 11: Default horizontal lengths in enumext.

```
#1: \l__enumext_labelwidth_X_dim       #2: \l__enumext_labelsep_X_dim
#3: \l__enumext_listoffset_X_dim       #4: \l__enumext_leftmargin_tmp_X_dim
#5: \l__enumext_leftmargin_X_dim       #6: \l__enumext_itemindent_X_dim
#7: \l__enumext_leftmargin_tmp_X_bool
```

And returns the *"adjusted"* values of \leftmargin and \itemindent.

```
\cs_new_protected:Nn \__enumext_calc_hspace:NNNNNNN
  {
    \dim_compare:nNnT {#1} < { \c_zero_dim }
      {
        \msg_warning:nnnV { enumext } { width-negative }{ labelwidth } #1
        \dim_set:Nn #1 { \dim_abs:n {#1} }
      }
    \dim_compare:nNnT {#2} < { \c_zero_dim }
      {
        \msg_warning:nnnV { enumext } { width-negative }{ labelsep }  #2
        \dim_set:Nn #2 { \dim_abs:n {#2} }
      }
```

If no value has been passed to the labelwidth and labelsep keys, the default values are set for \l__enumext_leftmargin_tmp_X_dim.

```
    \bool_if:NF #7 { \dim_set:Nn #4 { #1 + #2} }
```

The cases are now analyzed and the values for \leftmargin and \itemindent are set.

```
    \dim_compare:nNnTF {#4} < { \c_zero_dim }
      {
        \dim_set:Nn #6 { #1 + #2 - #4}
        \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
      }
      {
        \dim_compare:nNnT {#4} = { #1 + #2 }
          { \dim_set:Nn #6 { \c_zero_dim } }
        \dim_compare:nNnT {#4} < { #1 + #2 }
          { \dim_set:Nn #6 { #1 + #2 - #4} }
        \dim_compare:nNnT {#4} > { #1 + #2 }
          {
            \dim_set:Nn #6 { -#1 - #2 + #4}
            \dim_set:Nn #6 { #6*-1}
          }
        \dim_set:Nn #5 { #1 + #2 + #3 - #6 }
      }
  }
\cs_generate_variant:Nn \__enumext_calc_hspace:NNNNNNN { ccccccc }
```

(*End of definition for* __enumext_calc_hspace:NNNNNNN.)

13.41.2 Setting second argument of the lists

__enumext_list_arg_two_i:
__enumext_list_arg_two_ii:
__enumext_list_arg_two_iii:
__enumext_list_arg_two_iv:
__enumext_list_arg_two_v:

\leftmargini, \leftmarginii, \leftmarginiii and \leftmarginiv are "not set"; in this case, the parameters for vertical and horizontal list spacing per level are set directly.

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \cs_new_protected:cpn { __enumext_list_arg_two_#1: }
      {
        \__enumext_calc_hspace:ccccccc
          { l__enumext_labelwidth_#1_dim } { l__enumext_labelsep_#1_dim }
          { l__enumext_listoffset_#1_dim } { l__enumext_leftmargin_tmp_#1_dim }
          { l__enumext_leftmargin_#1_dim } { l__enumext_itemindent_#1_dim }
          { l__enumext_leftmargin_tmp_#1_bool }
        \clist_map_inline:nn
```

©2024–2026 by Pablo González L

```
          { labelsep, labelwidth, itemindent, leftmargin, rightmargin,
            listparindent }
          { \dim_set_eq:cc {####1} { l__enumext_####1_#1_dim } }
        \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
          { \skip_set_eq:cc {####1} { l__enumext_####1_#1_skip } }
        \clist_map_inline:nn { beginparpenalty, itempenalty, endparpenalty }
          { \int_set_eq:cc {@####1} { l__enumext_####1_#1_int } }
        \usecounter { enumX#1 }
        \setcounter { enumX#1 }
          { \int_eval:n { \int_use:c { l__enumext_start_#1_int } - 1 } }
        \str_if_eq:nnTF {#1} { v }
          {
            \__enumext_keyans_redefine_item:
            \__enumext_keyans_make_label:
            \__enumext_keyans_ref:
            \__enumext_keyans_fake_item_indent:
            \bool_if:cT { l__enumext_show_length_#1_bool }
              {
                \msg_term:nnnn { enumext } { list-lengths-not-nested } { v }
                  { keyans }
              }
          }
          {
            \__enumext_redefine_item:
            \__enumext_make_label:
            \__enumext_standard_ref:
            \__enumext_fake_item_indent:
            \bool_if:cT { l__enumext_show_length_#1_bool }
              {
                \msg_term:nnne { enumext } { list-lengths } {#1}
                  { \int_use:N \l__enumext_level_int }
              }
          }
      }
  }
\clist_map_inline:nn { i, ii, iii, iv, v } { \__enumext_tmp:n {#1} }
```

(*End of definition for* `\__enumext_list_arg_two_i:` *and others.*)

`\__enumext_list_arg_two_vii:`
`\__enumext_list_arg_two_viii:`

For the horizontal environments `enumext*` and `keyans*` the implementation is similar, but, the value of `\partopsep` is always `0pt`. At this point the `parsep` key is modified to make it take the value of the `itemsep` key and later, in the environment definition, `parindent` is modified to make it set the value of `listparindent` and `parsep` to set the value of `\parskip` locally.

For compatibility with *tagged* PDF and LaTeX release 2026-06-01, `\setcounter` is moved to `\begin{list}{⟨arg one⟩}{⟨arg two⟩}\setcounter` in the definition of the environments `enumext*` and `keyans*` (see §13.47 and §13.48). This resolves the nesting problem reported by `@teepeemm` in enumext* nested in enumext starts at 2 with DocumentMetadata this was caused by the `latex-lab-block`[19] update in this release.

```
\cs_set_protected:Nn \__enumext_tmp:n
  {
    \cs_new_protected:cpn { __enumext_list_arg_two_#1: }
      {
        \bool_set_true:c { l__enumext_leftmargin_tmp_#1_bool }
        \dim_zero:c { l__enumext_leftmargin_tmp_#1_dim }
        \__enumext_calc_hspace:ccccccc
          { l__enumext_labelwidth_#1_dim } { l__enumext_labelsep_#1_dim }
          { l__enumext_listoffset_#1_dim } { l__enumext_leftmargin_tmp_#1_dim }
          { l__enumext_leftmargin_#1_dim } { l__enumext_itemindent_#1_dim }
          { l__enumext_leftmargin_tmp_#1_bool }
        \clist_map_inline:nn
          { labelsep, labelwidth, itemindent, leftmargin, rightmargin,
            listparindent }
          { \dim_set_eq:cc {####1} { l__enumext_####1_#1_dim } }
        \clist_map_inline:nn { topsep, parsep, partopsep, itemsep }
          { \skip_set_eq:cc {####1} { l__enumext_####1_#1_skip } }
        \clist_map_inline:nn { beginparpenalty, itempenalty, endparpenalty }
          { \int_set_eq:cc {@####1} { l__enumext_####1_#1_int } }
        \skip_set_eq:Nc \parsep  { l__enumext_itemsep_#1_skip }
        \skip_zero:N \partopsep
        \usecounter { enumX#1 }
        % \setcounter { enumX#1 } { \int_eval:n { \int_use:c { l__enumext_start_#1_int } - 1 } }
```

```
      \__enumext_starred_ref:
      \str_if_eq:nnTF {#1} { vii }
        {
          \__enumext_fake_item_indent_vii:
          \bool_if:cT { l__enumext_show_length_vii_bool }
            { \msg_term:nnnn { enumext } { list-lengths-not-nested } { vii }
              { enumext* } }
        }
        {
          \__enumext_fake_item_indent_viii:
          \bool_if:cT { l__enumext_show_length_#1_bool }
            { \msg_term:nnnn { enumext } { list-lengths-not-nested } {#1}
              { keyans* } }
        }
    }
  }
\clist_map_inline:nn { vii, viii } { \__enumext_tmp:n {#1} }
```

(*End of definition for* `\__enumext_list_arg_two_vii:` *and* `\__enumext_list_arg_two_viii:`.)

13.41.3 Definition of error messages

`width-negative` Messages used in length calculation.

```
\msg_new:nnn { enumext } { width-negative }
  {
    Ignoring~negative~value~'#1=#2'~\msg_line_context:.\\
    The~key~'#1'~accepts~values~>=~0pt.
  }
```

(*End of definition for* `width-negative`.)

`list-lengths` Messages used by `show-length` key in `enumext`.

```
\msg_new:nnn { enumext } { list-lengths }
  {
    ****~Lengths~used~by~'enumext'~level~'#2'~\msg_line_context:~\c_space_tl ****\\
    \__enumext_show_length:nnn { dim  } { labelsep      } {#1}
    \__enumext_show_length:nnn { dim  } { labelwidth    } {#1}
    \__enumext_show_length:nnn { dim  } { itemindent    } {#1}
    \__enumext_show_length:nnn { dim  } { leftmargin    } {#1}
    \__enumext_show_length:nnn { dim  } { rightmargin   } {#1}
    \__enumext_show_length:nnn { dim  } { listparindent } {#1}
    \__enumext_show_length:nnn { skip } { topsep    } {#1}
    \__enumext_show_length:nnn { skip } { parsep    } {#1}
    \__enumext_show_length:nnn { skip } { partopsep } {#1}
    \__enumext_show_length:nnn { skip } { itemsep   } {#1}
    **************************************************
  }
```

(*End of definition for* `list-lengths`.)

`list-lengths-not-nested` Messages used by `show-length` key in `enumext*`, `keyans*` and `keyans`.

```
\msg_new:nnn { enumext } { list-lengths-not-nested }
  {
    ****~Lengths~used~by~'#2'~environment~\msg_line_context:~\c_space_tl ****\\
    \__enumext_show_length:nnn { dim  } { labelsep      } {#1}
    \__enumext_show_length:nnn { dim  } { labelwidth    } {#1}
    \__enumext_show_length:nnn { dim  } { itemindent    } {#1}
    \__enumext_show_length:nnn { dim  } { leftmargin    } {#1}
    \__enumext_show_length:nnn { dim  } { rightmargin   } {#1}
    \__enumext_show_length:nnn { dim  } { listparindent } {#1}
    \__enumext_show_length:nnn { skip } { topsep    } {#1}
    \__enumext_show_length:nnn { skip } { parsep    } {#1}
    \__enumext_show_length:nnn { skip } { partopsep } {#1}
    \__enumext_show_length:nnn { skip } { itemsep   } {#1}
    **************************************************
  }
```

(*End of definition for* `list-lengths-not-nested`.)

13.42 The environment enumext

__enumext_safe_exec:

The __enumext_safe_exec: function first calls the function __enumext_is_not_nested: which sets \g__enumext_standard_bool to *"true"* if it is NOT nested within enumext*, then calls the function __enumext_internal_mini_page: to create the environment __enumext_mini_page, increments \l__enumext_level_int to restrict nesting of the environment, sets \l__enumext_standard_bool to *"true"* and finally calls the function __enumext_is_on_first_level: which sets \l__enumext_standard_first_ to *"true"* only if the environment is NOT nested and is at the *"first level"*.

```
\cs_new_protected:Nn \__enumext_safe_exec:
  {
    \__enumext_is_not_nested:
    \__enumext_internal_mini_page:
    \int_incr:N \l__enumext_level_int
    \int_compare:nNnT { \l__enumext_level_int } > { 4 }
      { \msg_fatal:nn { enumext } { list-too-deep } }
    \bool_set_true:N \l__enumext_standard_bool
    \bool_set_false:N \l__enumext_starred_bool
    \__enumext_is_on_first_level:
  }
```

(*End of definition for* __enumext_safe_exec:.)

__enumext_parse_keys:n

The __enumext_parse_store_keys:n function first clears the variable \l__enumext_series_name_str used by the key series and then checks if it is at the *"first level"*; if so, it processes the ⟨*keys*⟩ and then executes the function __enumext_parse_series:n used by the key series and calls the function __enumext_nested_base_line_fix: used by the key base-fix; otherwise it passes the ⟨*keys*⟩ to the inner levels of the environment, then executes the function __enumext_store_active_keys:n and reprocesses the ⟨*keys*⟩ to pass them to the *sequence* if the key save-key is not active.

```
\cs_new_protected:Nn \__enumext_parse_keys:n
  {
    \tl_if_novalue:nF {#1}
      {
        \str_clear:N \l__enumext_series_name_str
        \int_compare:nNnTF { \l__enumext_level_int } = { 1 }
          {
            \keys_set:nn { enumext / level-1 } {#1}
            \bool_if:NF \l__enumext_print_keyans_cmd_bool
              {
                \__enumext_parse_series:n {#1}
              }
            \__enumext_nested_base_line_fix:
          }
          {
            \exp_args:Ne \keys_set:nn
              { enumext / level-\int_use:N \l__enumext_level_int } {#1}
            \bool_if:NF \l__enumext_print_keyans_cmd_bool
              {
                \__enumext_parse_series:n {#1}
              }
          }
        \__enumext_store_active_keys:n {#1}
      }
  }
```

(*End of definition for* __enumext_parse_keys:n.)

__enumext_start_store_level:

The __enumext_start_store_level: function activates the *"storing structure"* mechanism in the *sequence* for the command \anskey and the environment anskey*.

```
\cs_new_protected:Nn \__enumext_start_store_level:
  {
    \bool_lazy_all:nT
      {
        { \bool_if_p:N \l__enumext_store_active_bool }
        { \bool_not_p:n { \l__enumext_keyans_env_bool } }
        { \bool_if_p:N \g__enumext_standard_bool }
      }
      {
        \int_compare:nNnT { \l__enumext_level_int } > { 1 }
          {
```

```
4346              \bool_set_true:c { l__enumext_store_upper_level_ \__enumext_level: _bool }
4347              \__enumext_store_level_open:
4348            }
4349        }
```

If `enumext` are nested in `enumext*` add `\__enumext_store_level_open:` to preserve the *"storing structure"*.

```
4350      \bool_lazy_all:nT
4351        {
4352          { \bool_if_p:N \l__enumext_store_active_bool }
4353          { \bool_not_p:n { \l__enumext_keyans_env_bool } }
4354          { \int_compare_p:nNn { \l__enumext_level_h_int } = { 1 } }
4355        }
4356        {
4357          \int_compare:nNnT { \l__enumext_level_int } > { 0 }
4358            {
4359              \bool_set_true:c { l__enumext_store_upper_level_ \__enumext_level: _bool }
4360              \__enumext_store_level_open:
4361            }
4362        }
4363    }
```

(*End of definition for* `\__enumext_start_store_level:`.)

`\__enumext_stop_store_level:` The `\__enumext_stop_store_level:` function stops the *"storing structure"* mechanism in the *sequence* for the command `\anskey` and the environment `anskey*`.

```
4364 \cs_new_protected:Nn \__enumext_stop_store_level:
4365   {
4366     \bool_if:cT { l__enumext_store_upper_level_ \__enumext_level: _bool }
4367       {
4368         \__enumext_store_level_close:
4369       }
4370   }
```

(*End of definition for* `\__enumext_stop_store_level:`.)

`\__enumext_multicols_start:` The function `\__enumext_multicols_start:` will start the `multicols` environment according to the value passed by the `columns` key, then set the default value for `\columnsep` when `columns-sep=0pt` and set the value of `\multicolsep` equal to zero and leave `\columnseprule` equal to zero for inner levels.

```
4371 \cs_new_protected:Nn \__enumext_multicols_start:
4372   {
4373     \int_compare:nNnT
4374       { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
4375       {
4376         \dim_compare:nNnT
4377           { \dim_use:c { l__enumext_columns_sep_ \__enumext_level: _dim } } = { \c_zero_dim }
4378           {
4379             \dim_set:cn { l__enumext_columns_sep_ \__enumext_level: _dim }
4380               {
4381                 ( \dim_use:c { l__enumext_labelwidth_ \__enumext_level: _dim }
4382                   + \dim_use:c { l__enumext_labelsep_ \__enumext_level: _dim }
4383                 ) / \int_use:c { l__enumext_columns_ \__enumext_level: _int }
4384                 - \dim_use:c { l__enumext_listoffset_ \__enumext_level: _dim }
4385               }
4386           }
4387         \dim_set_eq:Nc \columnsep { l__enumext_columns_sep_ \__enumext_level: _dim  }
4388         \int_compare:nNnT { \l__enumext_level_int } > { 1 }
4389           {
4390             \dim_zero:N \columnseprule
4391           }
```

The *vertical spacing* settings for the `multicols` environment are calculated using the function `\__enumext_multi_addvspace:`, the *"vertical adjust spacing"* is applied, and then the `multicols` environment is started.

```
4392         \bool_if:cF { l__enumext_minipage_active_ \__enumext_level: _bool }
4393           {
4394             \skip_zero:N \multicolsep
4395             \__enumext_multi_addvspace:
4396           }
4397         \raggedcolumns
4398         \begin{multicols}{ \int_use:c { l__enumext_columns_ \__enumext_level: _int } }
```

```
      }
  }
```

(*End of definition for* `\__enumext_multicols_start:`.)

`\__enumext_multicols_stop:` The function `\__enumext_multicols_stop:` will stop the `multicols` environment and apply the *"vertical adjust"* spacing. For compatibility with *tagged* PDF, the closing of the `list` environment is executed here along with `\__enumext_stop_store_level:`.

```
\cs_new_protected:Nn \__enumext_multicols_stop:
  {
    \int_compare:nNnTF
      { \int_use:c { l__enumext_columns_ \__enumext_level: _int } } > { 1 }
      {
        \__enumext_stop_list:
        \__enumext_stop_store_level:
        \end{multicols}
        \__enumext_unskip_unkern:
        \__enumext_unskip_unkern:
        \par\addvspace{ \skip_use:c { l__enumext_multicols_below_ \__enumext_level: _skip } }
      }
      {
        \__enumext_stop_list:
        \__enumext_stop_store_level:
      }
  }
```

(*End of definition for* `\__enumext_multicols_stop:`.)

`\__enumext_before_list:` The function `\__enumext_before_list:` first calls the function `\__enumext_vspace_above:` used by the keys `above` and `above*`, then calls the function `\__enumext_before_args_exec:` used by the key `before*` and finally execute the function `\__enumext_check_ans_active:` for the check answer mechanism.

```
\cs_new_protected:Nn \__enumext_before_list:
  {
    \__enumext_vspace_above:
    \__enumext_before_args_exec:
    \__enumext_check_ans_active:
```

When the `mini-env` key is active it will set the value of the `\l__enumext_minipage_right_X_dim` to be the *width* of the `\__enumext_mini_page` environment on the *"right side"*, using this value together with the value of the `\l__enumext_minipage_hsep_X_dim` set by the `mini-sep` key, the value of `\l__enumext_minipage_left_X_dim` will be set, which will be the *width* of `\__enumext_mini_page` environment on the *"left side"*, always having a current `\linewidth` as *maximum width* between them.

```
    \dim_compare:nNnT
      { \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim } } > { \c_zero_dim }
      {
        \dim_set:cn { l__enumext_minipage_left_ \__enumext_level: _dim }
          {
            \linewidth
            - \dim_use:c { l__enumext_minipage_right_ \__enumext_level: _dim }
            - \dim_use:c { l__enumext_minipage_hsep_ \__enumext_level: _dim }
          }
```

The boolean variable `\l__enumext_minipage_active_X_bool` will be activated and the integer variable `\g__enumext_minipage_stat_int` used by the `\miniright` command will be incremented, then the function `\__enumext_minipage_add_space:` is called and the `\__enumext_mini_page` environment on the *"left side"* will be initialized followed by the *"vertical spacing"* applied to preserve the *"baseline"* between the *left* and *right* side environments. After these actions, the function `\__enumext_multicols_start:` is called to handle the `multicols` environment.

```
        \bool_set_true:c { l__enumext_minipage_active_ \__enumext_level: _bool }
        \int_gincr:N \g__enumext_minipage_stat_int
        \__enumext_minipage_add_space:
        \noindent
        \__enumext_mini_page{ \dim_use:c { l__enumext_minipage_left_ \__enumext_level: _dim } }
      }
    \__enumext_multicols_start:
  }
```

(*End of definition for* `\__enumext_before_list:`.)

©2024–2026 by Pablo González L

__enumext_second_part:

The function __enumext_second_part: first checks the state of the boolean variable \l__enumext_minipage_acti if it is "true", a small test is executed to check if the use of \miniright was omitted (the __enumext_mini_page environment has not been closed), then it closes __enumext_mini_page and adds the *adjusted vertical space* \l__enumext_minipage_after_skip, otherwise it closes the multicols environment.

```
\cs_new_protected:Nn \__enumext_second_part:
  {
    \bool_if:cTF { l__enumext_minipage_active_ \__enumext_level: _bool }
      {
        \int_compare:nNnT { \g__enumext_minipage_stat_int } = { 1 }
          {
            \msg_warning:nn { enumext } { missing-miniright }
            \miniright
          }
        \int_gzero:N \g__enumext_minipage_stat_int
        \__enumext_unskip_unkern: % remove topsep + [partopsep]
        \end__enumext_mini_page
      }
      {
        \__enumext_multicols_stop:
      }
```

Now the functions __enumext_after_stop_list: used by the key after, __enumext_check_ans_key_hook: used by the key check-ans, and __enumext_vspace_below: used by the keys below and below* are executed. Finally it sets \l__enumext_standard_bool to false and calls the function __enumext_resume_save_counter: used by the series, resume and resume* keys.

```
    \__enumext_after_stop_list:
    \__enumext_check_ans_key_hook:
    \__enumext_vspace_below:
    \bool_set_false:N \l__enumext_standard_bool
    \bool_if:NF \l__enumext_print_keyans_cmd_bool
      {
        \__enumext_standard_save_counter:
      }
  }
```

(*End of definition for* __enumext_second_part:.)

__enumext_set_item_width:

The function __enumext_set_item_width: will set the value of \itemwidth taking into account the value established by the list-offset key for each level of the environment.

```
\cs_new_protected:Nn \__enumext_set_item_width:
  {
    \dim_set:Nn \itemwidth { \linewidth }
    \dim_compare:nT
      {
        \dim_use:c { l__enumext_listoffset_ \__enumext_level: _dim } != \c_zero_dim
      }
      {
        \dim_sub:Nn \itemwidth
          {
            \dim_use:c { l__enumext_listoffset_ \__enumext_level: _dim }
          }
      }
  }
```

(*End of definition for* __enumext_set_item_width:.)

enumext

Now create the enumext environment based on list environment by levels.

```
\NewDocumentEnvironment{enumext}{ O{} }
  {
    \__enumext_safe_exec:
    \__enumext_parse_keys:n {#1}
    \__enumext_before_list:
    \__enumext_start_store_level:
    \__enumext_start_list:nn
      { \tl_use:c { l__enumext_label_ \__enumext_level: _tl } }
      {
        \use:c { __enumext_list_arg_two_ \__enumext_level: : }
        \__enumext_before_keys_exec:
```

©2024–2026 by Pablo González L

```
      }
    \__enumext_set_item_width:
    \__enumext_after_args_exec:
  }
  {
    \__enumext_second_part:
  }
```

(*End of definition for* `enumext`. *This function is documented on page 5.*)

Since the `check-ans` check must not be executed by levels but on the complete list, it is taken out of the `enumext` environment using the *"hook"* function `\__enumext_after_env:nn`.

```
\__enumext_after_env:nn {enumext}
  {
    \__enumext_execute_after_env:
  }
```

13.42.1 Definition of error messages for `enumext`

`list-too-deep` Message for the nesting depth of the environment `enumext`.

```
\msg_new:nnn { enumext } { list-too-deep }
  {
    Too~deep~nesting~for~'enumext'~\msg_line_context:.\\
    The~maximum~level~of~nesting~is~4.
  }
```

(*End of definition for* `list-too-deep`.)

13.43 The environment `keyans`

The environment `keyans` also based on lists. The main differences with the `enumext` environment are the *nesting* and the way the *answers* (choice) will be stored and checked, this environment is intended exclusively for *"multiple choice questions"*.

`\__enumext_keyans_safe_exec:` The `keyans` environment will only be available if the `save-ans` key is active and can only be used at the *"first level"* within the `enumext` environment. The environment must not be nested, so a maximum is set at this point. If the conditions are not met, an error message is returned.

```
\cs_new_protected:Nn \__enumext_keyans_safe_exec:
  {
    \bool_if:NF \l__enumext_store_active_bool
      {
        \msg_error:nnnn { enumext } { wrong-place }{ keyans }{ save-ans }
      }
    \int_incr:N \l__enumext_keyans_level_int
    \bool_set_true:N \l__enumext_keyans_env_bool
    \__enumext_keyans_name_and_start:
    % Set false for interfering with enumext nested in keyans (yes, its possible and crayze)
    \bool_set_false:N \l__enumext_store_active_bool
    \int_compare:nNnT { \l__enumext_keyans_level_int } > { 1 }
      {
        \msg_error:nn { enumext } { keyans-nested }
      }
    \int_compare:nNnT { \l__enumext_level_int } > { 1 }
      {
        \msg_error:nn { enumext } { keyans-wrong-level }
      }
  }
```

(*End of definition for* `\__enumext_keyans_safe_exec:`.)

`\__enumext_keyans_parse_keys:n` Parse [⟨*key* = *val*⟩] for `keyans` environment.

```
\cs_new_protected:Nn \__enumext_keyans_parse_keys:n
  {
    \keys_set:nn { enumext / keyans } {#1}
  }
```

(*End of definition for* `\__enumext_keyans_parse_keys:n`.)

`\__enumext_before_list_v:` Same implementation as the one used in the `enumext` environment.

`\__enumext_keyans_multicols_start:`
`\__enumext_keyans_multicols_stop:`
`\__enumext_second_part_v:`

```
\cs_new_protected:Nn \__enumext_before_list_v:
```

©2024–2026 by Pablo González L

```
  {
    \__enumext_vspace_above_v:
    \__enumext_before_args_exec_v:
    \dim_compare:nNnT { \l__enumext_minipage_right_v_dim } > { \c_zero_dim }
      {
        \dim_set:Nn \l__enumext_minipage_left_v_dim
          {
            \linewidth - \l__enumext_minipage_right_v_dim - \l__enumext_minipage_hsep_v_dim
          }
        \bool_set_true:N \l__enumext_minipage_active_v_bool
        \int_gincr:N \g__enumext_minipage_stat_int
        \__enumext_keyans_minipage_add_space:
        \__enumext_mini_page{ \l__enumext_minipage_left_v_dim }
      }
    \__enumext_keyans_multicols_start:
  }
\cs_new_protected:Nn \__enumext_keyans_multicols_start:
  {
    \int_compare:nNnT { \l__enumext_columns_v_int } > { 1 }
      {
        \dim_compare:nNnT { \l__enumext_columns_sep_v_dim } = { \c_zero_dim }
          {
            \dim_set:Nn \l__enumext_columns_sep_v_dim
              {
                (
                  \l__enumext_labelwidth_v_dim + \l__enumext_labelsep_v_dim
                ) / \l__enumext_columns_v_int
               - \l__enumext_listoffset_v_dim
              }
          }
        \dim_set_eq:NN \columnsep \l__enumext_columns_sep_v_dim
        \dim_zero:N \columnseprule % no rule here
        \bool_if:NF \l__enumext_minipage_active_v_bool
          {
            \skip_zero:N \multicolsep
            \__enumext_keyans_multi_addvspace:
          }
        \raggedcolumns
        \begin{multicols}{ \l__enumext_columns_v_int }
      }
  }
\cs_new_protected:Nn \__enumext_keyans_multicols_stop:
  {
    \int_compare:nNnTF { \l__enumext_columns_v_int } > { 1 }
      {
        \__enumext_stop_list:
        \end{multicols}
        \__enumext_unskip_unkern:
        \__enumext_unskip_unkern:
        \par\addvspace{ \l__enumext_multicols_below_v_skip }
      }
      {
        \__enumext_stop_list:
      }
  }
\cs_new_protected:Nn \__enumext_second_part_v:
  {
    \bool_if:NTF \l__enumext_minipage_active_v_bool
      {
        \int_compare:nNnT { \g__enumext_minipage_stat_int } = { 1 }
          {
            \msg_warning:nn { enumext } { missing-miniright }
            \miniright
          }
        \int_gzero:N \g__enumext_minipage_stat_int
        \__enumext_unskip_unkern: % remove \topsep + [\partopsep]
        \end__enumext_mini_page
        \par\addvspace{ \l__enumext_minipage_after_skip }
      }
      {
        \__enumext_keyans_multicols_stop:
```

```
      }
    \bool_set_false:N \l__enumext_keyans_env_bool
    \__enumext_after_stop_list_v:
    \__enumext_vspace_below_v:
  }
```

(*End of definition for* `\__enumext_before_list_v:` *and others.*)

`\__enumext_keyans_set_item_width:` The function `\__enumext_keyans_set_item_width:` will set the value of `\itemwidth` taking into account the value established by the `list-offset` key.

```
\cs_new_protected:Nn \__enumext_keyans_set_item_width:
  {
    \dim_set:Nn \itemwidth { \linewidth }
    \dim_compare:nT
      {
        \l__enumext_listoffset_v_dim != \c_zero_dim
      }
      {
        \dim_sub:Nn \itemwidth { \l__enumext_listoffset_v_dim }
      }
  }
```

(*End of definition for* `\__enumext_keyans_set_item_width:`.)

`keyans` Defines the environment `keyans`, also based on lists.

```
\NewDocumentEnvironment{keyans}{ O{} }
  {
    \__enumext_keyans_safe_exec:
    \__enumext_keyans_parse_keys:n {#1}
    \__enumext_before_list_v:
    \__enumext_start_list:nn
      { \tl_use:N \l__enumext_label_v_tl }
      {
        \__enumext_list_arg_two_v:
        \__enumext_before_keys_exec_v:
      }
    \__enumext_keyans_set_item_width:
    \__enumext_after_args_exec_v:
  }
  {
    \__enumext_check_starred_cmd:n { item }
    \__enumext_second_part_v:
  }
```

(*End of definition for* `keyans`. *This function is documented on page 17.*)

13.43.1 Definition of error messages for `keyans`

`keyans-nested` Message used by `keyans` environment.

```
\msg_new:nnn { enumext } { keyans-nested }
  {
    The~environment~'keyans'~can't~be~nested~\msg_line_context:.
  }
```

(*End of definition for* `keyans-nested`.)

13.44 Tagging PDF support for non-standard list environments

The LaTeX release 2022-06-01 brings automatic support for *tagged* PDF in several aspects, including the standard *list environments* and the `list` environment. Unfortunately non-standard *list environments* like `keyanspic` or the horizontal list environments `enumext*` and `keyans*` are not structured in a nice way, i.e. the expected result in the PDF file is the expected one, but the underlying structure is not correct. In simple terms, for *tagged* PDF a `list` environment is a `list` environment, no matter what it looks like in the PDF file.

To maintain a correct `list` structure when `\DocumentMetadata` is active, it is necessary to do some things manually using `tagpdf`[18] and `ltsockets`[20]. This implementation is an adaptation of the answer given by Pablo González thanks to Ulrike Fischer's comments in How can I modify my `\item` redefinition to be compatible with `tagging-pdf`.

13.44.1 Socket for tagging support in enumext* and keyans*

start-list-tags
stop-start-tags
stop-list-tags
__enumext_start_list_tag:n
__enumext_stop_start_list_tag:
__enumext_stop_list_tag:n

First, the necessary sockets and their behavior are defined for enumext* and keyans*.

```
\socket_new:nn {tagsupport/__enumext/starred}{ 1 }
\socket_new_plug:nnn {tagsupport/__enumext/starred} {start-list-tags}
  {
    \tag_resume:n {#1}
      \tag_struct_begin:n {tag=LI}
        \tag_struct_begin:n {tag=Lbl}
           \tag_mc_begin:n {tag=Lbl}
  }
\socket_new_plug:nnn {tagsupport/__enumext/starred} {stop-start-tags}
  {
           \tag_mc_end:
        \tag_struct_end:n {tag=Lbl}
        \tag_struct_begin:n {tag=LBody}
          \tag_struct_begin:n {tag=semantic-para} % {tag=text-unit} now "semantic-para" (https://github.
            \tag_struct_begin:n {tag=text-block} % {tag=text} now "text-block"
  }
\socket_new_plug:nnn {tagsupport/__enumext/starred} {stop-list-tags}
  {
           \tag_struct_end:n {tag=text-block}
         \tag_struct_end:n {tag=semantic-para} % {tag=text-unit}
        \tag_struct_end:n {tag=LBody}
      \tag_struct_end:n {tag=LI}
    \tag_suspend:n {#1}
  }
```

And now they are wrapped so that they are only active when \DocumentMetadata is present.

```
\cs_new_protected_nopar:Nn \__enumext_start_list_tag:n
  {
    \IfDocumentMetadataT
      {
        \socket_assign_plug:nn {tagsupport/__enumext/starred} {start-list-tags}
        \socket_use:nn {tagsupport/__enumext/starred} {#1}
      }
  }
\cs_new_protected_nopar:Nn \__enumext_stop_start_list_tag:
  {
    \IfDocumentMetadataT
      {
        \socket_assign_plug:nn {tagsupport/__enumext/starred} {stop-start-tags}
        \socket_use:nn {tagsupport/__enumext/starred} { }
      }
  }
\cs_new_protected_nopar:Nn \__enumext_stop_list_tag:n
  {
    \IfDocumentMetadataT
      {
        \socket_assign_plug:nn {tagsupport/__enumext/starred} {stop-list-tags}
        \socket_use:nn {tagsupport/__enumext/starred} {#1}
      }
  }
```

(*End of definition for* start-list-tags *and others.*)

13.44.2 Socket for tagging support in keyanspic

start-list-tags
stop-start-tags
stop-list-tags
__enumext_anspic_start_list_tag:
__enumext_anspic_stop_start_list_tag:
__enumext_anspic_stop_list_tag:

First, the necessary sockets and their behavior are defined for the keyanspic environment.

```
\socket_new:nn {tagsupport/__enumext/keyanspic}{ 0 }
\socket_new_plug:nnn {tagsupport/__enumext/keyanspic} {start-list-tags}
  {
    \tag_resume:n {keyanspic}
      \tag_struct_begin:n {tag=LI}
        \tag_struct_begin:n {tag=Lbl}
          \tag_mc_begin:n {tag=Lbl}
  }
\socket_new_plug:nnn {tagsupport/__enumext/keyanspic} {stop-start-tags}
  {
           \tag_mc_end:
        \tag_struct_end:n {tag=Lbl}
```

©2024–2026 by Pablo González L

```
        \tag_struct_begin:n {tag=LBody}
          \tag_struct_begin:n {tag=semantic-para}
            \tag_struct_begin:n {tag=text-block}
              \tag_mc_begin:n {tag=text-block}
  }
\socket_new_plug:nnn {tagsupport/__enumext/keyanspic} {stop-list-tags}
  {
              \tag_mc_end:
            \tag_struct_end:n {tag=text-block}
          \tag_struct_end:n {tag=semantic-para}
        \tag_struct_end:n {tag=LBody}
      \tag_struct_end:n {tag=LI}
    \tag_suspend:n {keyanspic}
  }
```

And now they are wrapped so that they are only active when `\DocumentMetadata` is present.

```
\cs_new_protected_nopar:Nn \__enumext_anspic_start_list_tag:
  {
    \IfDocumentMetadataT
      {
        \socket_assign_plug:nn {tagsupport/__enumext/keyanspic} {start-list-tags}
        \socket_use:n {tagsupport/__enumext/keyanspic}
      }
  }
\cs_new_protected_nopar:Nn \__enumext_anspic_stop_start_list_tag:
  {
    \IfDocumentMetadataT
      {
        \socket_assign_plug:nn {tagsupport/__enumext/keyanspic} {stop-start-tags}
        \socket_use:n {tagsupport/__enumext/keyanspic}
      }
  }
\cs_new_protected_nopar:Nn \__enumext_anspic_stop_list_tag:
  {
    \IfDocumentMetadataT
      {
        \socket_assign_plug:nn {tagsupport/__enumext/keyanspic} {stop-list-tags}
        \socket_use:n {tagsupport/__enumext/keyanspic}
      }
  }
```

(*End of definition for* `start-list-tags` *and others.*)

13.45 The environment `keyanspic` and `\anspic`

The `keyanspic` environment is a `list` based environment that uses the same configuration for *"spacing"* and ⟨*label*⟩ as the `keyans` environment, but it does not use `\item`. The ⟨*contents*⟩ are passed to the environment by means of the `\anspic` command as replacement for `\item` command and placed inside `minipage` environments, with the ⟨*label*⟩ centered *"above"* or *"below"*, adjusting *widths* and *position* according to the options passed to the environment.




Figure 12: Representation of the `keyanspic` spacing in enumext.

In order for the `keyanspic` environment and the `\anspic` command to work correctly, some variables must be set and exported in the first part of the environment definition and pass them to `\anspic` which is executed in the second part of the environment. This implementation is adapted from the answer given by Enrico Gregorio (`@egreg`) in How to process the body of an environment and divide it by a \macro?.

13.45.1 The environment `keyanspic`

label-pos
label-sep
layout-sty
layout-sep

First the keys are defined. The position of the ⟨*label*⟩ centered "above" or "below" is handled by `label-pos`, and its vertical separation from the *drawing or tabular* by the key `label-sep`. The *"layout style"* is handled

by the key layout-sty, which takes two values separated by comma {⟨n° upper, n° lower⟩} and determines the number of minipage environments in which all arguments of \anspic are printed at the "upper" and "lower" within the environments separated by the value of the key layout-sep. The vertical space "top" and "bottom" of the environment is handled by the key layout-top.

```
\keys_define:nn { enumext / keyanspic }
  {
    label-pos  .choices:nn =
      { above , below }
      {
        \int_case:nn { \l_keys_choice_int }
          {
            {1}
              {
                \bool_set_true:N \l__enumext_anspic_label_above_bool
                \str_set:Nn \l__enumext_anspic_mini_pos_str { t }
              }
            {2}
              {
                \bool_set_false:N \l__enumext_anspic_label_above_bool
                \str_set:Nn \l__enumext_anspic_mini_pos_str { b }
              }
          }
      },
    label-pos  .initial:n = below,
    label-pos  .value_required:n = true,
    label-pos / unknown .code:n =
      \msg_error:nneee { enumext } { unknown-choice }
        { label-pos } { above,~ below } { \exp_not:n {#1} },
    label-sep  .skip_set:N = \l__enumext_anspic_label_sep_skip,
    label-sep  .value_required:n = true,
    layout-sty .tl_set:N = \l__enumext_anspic_layout_style_tl,
    layout-sty .value_required:n = true,
    layout-sep .meta:nn = { enumext / keyans } { parsep = {#1} },
    layout-sep .value_required:n = true,
    layout-top .meta:nn = { enumext / keyans } { topsep = {#1} },
    layout-top .value_required:n = true,
    mark-ans   .meta:nn = { enumext / keyans } { mark-ans = {#1} },
    mark-ans   .value_required:n = true,
    mark-pos   .meta:nn = { enumext / keyans } { mark-pos = {#1} },
    mark-pos   .value_required:n = true,
    mark-sep   .meta:nn = { enumext / keyans } { mark-sep = {#1} },
    mark-sep   .value_required:n = true,
    save-sep   .meta:nn = { enumext / keyans } { save-sep = {#1} },
    save-sep   .value_required:n = true,
    wrap-opt   .meta:nn = { enumext / keyans } { wrap-opt = {#1} },
    wrap-opt   .value_required:n = true,
    wrap-ans*  .meta:nn = { enumext / keyans } { wrap-ans* = {#1} },
    wrap-ans*  .value_required:n = true,
    show-ans   .meta:nn = { enumext / keyans } { show-ans = {#1} },
    show-ans   .value_required:n = true,
    show-pos   .meta:nn = { enumext / keyans } { show-pos = {#1} },
    show-pos   .value_required:n = true,
    unknown    .code:n =
      {
        \tl_set:Ne \l__enumext_envir_name_tl { keyanspic }
        \__enumext_keyans_unknown_keys:n {#1}
      },
  }
```

(*End of definition for* label-pos *and others.*)

__enumext_keyans_pic_safe_exec:
__enumext_keyans_pic_parse_keys:n
__enumext_keyans_pic_skip_abs:N
__enumext_keyans_pic_arg_two:

The function __enumext_keyans_pic_safe_exec: check the nested level position inside the enumext environment.

```
\cs_new_protected:Nn \__enumext_keyans_pic_safe_exec:
  {
    \int_incr:N \l__enumext_keyans_pic_level_int
    \int_compare:nNnT { \l__enumext_keyans_pic_level_int } > { 1 }
      {
        \msg_error:nn { enumext } { keyanspic-nested }
      }
```

```
    \__enumext_keyans_name_and_start:
  }
```

Parse [⟨*key* = *val*⟩] for keyanspic environment.

```
\cs_new_protected:Nn \__enumext_keyans_pic_parse_keys:n
  {
    \tl_if_novalue:nF {#1}
      {
        \keys_set:nn { enumext / keyanspic } {#1}
      }
  }
```

The function __enumext_keyans_pic_skip_abs:N will return a positive value \parsep from keyans environment.

```
\cs_new_protected:Nn \__enumext_keyans_pic_skip_abs:N
  {
    \dim_compare:nNnT {#1} < { \c_zero_dim }
      {
        \skip_set:Nn #1 { -#1 }
      }
  }
```

The __enumext_keyans_pic_arg_two: function is used in the *second argument* of the list environment that defines the keyanspic environment, taking the configuration of the *"spaces"* and the keys label, wrap-label, parsep and topsep from the keyans environment. The first step is to set the boolean variable \l__enumext_leftmargin_tmp_v_bool handled by the list-indent key to "false", then copy the definition of the second list argument from the keyans environment definition and make sure that \parsep does not have a negative value.

```
\cs_new_protected:Nn \__enumext_keyans_pic_arg_two:
  {
    \bool_set_false:N \l__enumext_leftmargin_tmp_v_bool
    \__enumext_list_arg_two_v:
    \__enumext_keyans_pic_skip_abs:N \parsep
```

Now the counter enumXv of the keyans environment is incremented and the *total height* of the ⟨*label*⟩ is saved in \l__enumext_anspic_label_htdp_dim used by \anspic, and the values of \parsep are adjusted only if the key label-pos is set to *below*.

```
    \bool_if:NF \l__enumext_anspic_label_above_bool
      {
        \stepcounter { enumXv }
        \hbox_set:Nn \l__enumext_anspic_label_box { \l__enumext_label_v_tl }
        \dim_set:Nn \l__enumext_anspic_label_htdp_dim
          {
            \box_ht_plus_dp:N \l__enumext_anspic_label_box
          }
        \skip_add:Nn \parsep
          {
            \l__enumext_anspic_label_htdp_dim
            + \box_dp:N \strutbox
            + \l__enumext_anspic_label_sep_skip
          }
      }
```

Finally the value of \leftmargin and \topsep is *adjusted*, then \listparindent, \partopsep and \itemsep are set to zero so that the *horizontal* and *vertical* space is not affected.

```
    \dim_add:Nn \leftmargin { -\l__enumext_labelwidth_v_dim - \l__enumext_labelsep_v_dim }
    \ignorespaces
    \skip_add:Nn \topsep { 0.5\box_dp:N \strutbox }
    \dim_zero:N  \listparindent
    \skip_zero:N \partopsep
    \skip_zero:N \itemsep
  }
```

(*End of definition for* __enumext_keyans_pic_safe_exec: *and others.*)

keyanspic Defines the environment keyanspic. For compatibility with *tagged* PDF the \begin{list} form must be used, along with a lot of conditional code using \IfDocumentMetadataTF. First, the code for automatic *tagged* PDF for list environments is stopped, \item is redefined so that it cannot be used, and the code for automatic *tagged* PDF is stopped for the keyanspic environment.

```
\NewDocumentEnvironment{keyanspic}{ o }
```

```
{
  \__enumext_keyans_pic_safe_exec:
  \__enumext_keyans_pic_parse_keys:n {#1}
  \begin{list} { } { \__enumext_keyans_pic_arg_two: }
  \IfDocumentMetadataT
    {
      \tag_suspend:n {list}
    }
  \item[] \scan_stop:
  \RenewDocumentCommand \item {}
    {
      \msg_error:nn { enumext } { keyanspic-item-cmd }
    }
  \IfDocumentMetadataT
    {
      \tag_resume:n {keyanspic}
      \tag_tool:n {para/tagging=false} % no socket for this now
      \tag_suspend:n {keyanspic}
    }
}
```

In the second part of the environment definition, the code for *tagged* PDF is placed manually and the command is executed: `\anspic` is run using the `\__enumext_anspic_exec:` function.

```
{
  \IfDocumentMetadataT
    {
      \tag_resume:n {keyanspic}
    }
  \__enumext_anspic_exec:
  \IfDocumentMetadataT
    {
      \tag_suspend:n {keyanspic}
    }
  \end{list}
  \IfDocumentMetadataT
    {
      \tag_struct_end:n {tag=L}
    }
```

Finally it checks if `\anspic*` has been used, sets the counter `enumXvi` to zero and applies the "adjusted" vertical space at the bottom.

```
  \__enumext_check_starred_cmd:n { anspic }
  \setcounter { enumXvi } { 0 }
  \bool_if:NTF \l__enumext_anspic_label_above_bool
    {
      \par\addvspace{ 0.5\box_dp:N \strutbox }
    }
    {
      \par
      \addvspace
        {
          \dim_eval:n
            {
              \l__enumext_anspic_label_htdp_dim + \box_ht_plus_dp:N \strutbox
              + \l__enumext_anspic_label_sep_skip + \l__enumext_topsep_v_skip
            }
        }
    }
}
```

(*End of definition for* `keyanspic`. *This function is documented on page* 18.)

13.45.2 The command `\anspic`

The `\anspic` command takes three arguments, the *starred versions* `\anspic*`[⟨*content*⟩] *store* the current ⟨*label*⟩ next to the *optional argument* [⟨*content*⟩] in the *sequence* and *prop list* defined by `save-ans` key. The third *mandatory argument* {⟨*drawing or tabular*⟩} is NOT *stored* in the *sequence* or *prop list*.

One of the complications here to make the `keyanspic` environment compatible with *tagged* PDF is the position of ⟨*label*⟩, the `\anspic` command processes the arguments in order, where `#1` and `#2` correspond to ⟨*label*⟩ and `#3` to the mandatory argument and puts all this inside a `minipage` environment. If `#1` and `#2`, that is ⟨*label*⟩, is above `#3` there are no problems with *tagged* PDF, but if `#3` comes first the list created with *tagged* PDF will not be correct.

©2024–2026 by Pablo González L

__enumext_anspic_body_dim:n
__enumext_anspic_label:nn
__enumext_anspic_label_pos:nnn
__enumext_anspic_args:nnn
__enumext_anspic_print:n
__enumext_anspic_print:e
__enumext_anspic_print:V
__enumext_anspic_row:n
__enumext_anspic_exec:

The `\__enumext_anspic_body_dim:n` function will set the value of `\l__enumext_anspic_body_htdp_dim` equal to the "height plus depth" of the *mandatory argument* if the key `label-pos` is set "below".

```
\cs_new_protected:Nn \__enumext_anspic_body_dim:n
  {
    \bool_if:NF \l__enumext_anspic_label_above_bool
      {
        \IfDocumentMetadataT
          {
            \tag_suspend:n {keyanspic}
          }
        \vbox_set:Nn \l__enumext_anspic_body_box {#1}
        \dim_set:Nn \l__enumext_anspic_body_htdp_dim
          {
            \box_ht_plus_dp:N \l__enumext_anspic_body_box
          }
        \IfDocumentMetadataT
          {
            \tag_resume:n {keyanspic}
          }
      }
  }
```

The `\__enumext_anspic_label:nn` function will process inside `\makebox` the *starred argument* '`*`' and *optional argument* passed to the command. Here the ⟨*label*⟩ and *optional argument* are stored in *prop list* and *sequence* and the `show-ans`, `show-pos`, `font`, `wrap-label`, `wrap-ans*` and `wrap-opt` keys are executed.

```
\cs_new_protected:Nn \__enumext_anspic_label:nn
  {
    \makebox[ \l__enumext_anspic_mini_width_dim ][ c ]
      {
        \bool_if:nTF {#1}
          {
            \bool_set_true:N \l__enumext_item_wrap_key_bool
            \bool_set_true:N \l__enumext_wrap_label_v_bool
            \__enumext_keyans_save_item_opt:n {#2}
            \__enumext_keyans_addto_prop:n {#2}
            \__enumext_keyans_store_ref:
            \__enumext_keyans_addto_seq:n {#2}
            \int_gincr:N \g__enumext_check_starred_cmd_int
            \__enumext_keyans_show_ans:
            \__enumext_keyans_show_pos:
            \makebox[ \l__enumext_labelwidth_v_dim ][c]
              {
                \tl_use:N \l__enumext_label_font_style_v_tl
                \__enumext_keyans_wrapper_label:n { \l__enumext_label_vi_tl }
              }
            \skip_horizontal:n { \l__enumext_labelsep_v_dim }
            \__enumext_keyans_show_item_opt:
          }
          {
            \bool_set_false:N \l__enumext_item_wrap_key_bool
            \tl_use:N \l__enumext_label_font_style_v_tl
            \__enumext_wrapper_label_v:n { \l__enumext_label_vi_tl }
          }
      }
  }
```

The function `\__enumext_anspic_label_pos:nnn` will be in charge of handling the *"counter"* and the position of the ⟨*label*⟩, set by `label-pos` key which will have the same configuration as the `keyans` environment.

```
\cs_new_protected:Nn \__enumext_anspic_label_pos:nnn
  {
    \stepcounter { enumXvi }
    \__enumext_anspic_body_dim:n {#3}
    \bool_if:NTF \l__enumext_anspic_label_above_bool
      {
        \__enumext_anspic_label:nn {#1} {#2}
      }
      {
        \raisebox
          {
            -\dim_eval:n
```

```
4957                {
4958                  \l__enumext_anspic_label_htdp_dim
4959                  + \l__enumext_anspic_body_htdp_dim
4960                  + \box_dp:N \strutbox
4961                  + \l__enumext_anspic_label_sep_skip
4962                }
4963            }
4964            [ 0pt ] [ 0pt ]
4965            {
4966              \__enumext_anspic_label:nn {#1} {#2}
4967            }
4968        }
4969    }
4970  %
```

The `\__enumext_anspic_args:nnn` function will be responsible for placing the code compatible with *tagged* PDF and the arguments within the `\l__enumext_anspic_args_seq` sequence which will be processed by the `\__enumext_anspic_print:n` function in the second part of the definition of the `keyanspic` environment.

```
4971  \cs_new_protected:Nn \__enumext_anspic_args:nnn
4972    {
4973      \__enumext_anspic_start_list_tag:
4974      \__enumext_anspic_label_pos:nnn {#1} {#2} {#3}
4975      \__enumext_anspic_stop_start_list_tag:
4976      \bool_if:NTF \l__enumext_anspic_label_above_bool
4977        {
4978          \\[\l__enumext_anspic_label_sep_skip] #3
4979        }
4980        {
4981          \\ #3
4982        }
4983      \__enumext_anspic_stop_list_tag:
4984    }
```

The value {⟨*n° upper, n° lower*⟩} passed to the `layout-sty` key is split by comma and is handled directly by the function `\__enumext_anspic_print:n` and passed to the function `\__enumext_anspic_row:n`.

```
4985  \cs_new_protected:Nn \__enumext_anspic_print:n
4986    {
4987      \clist_map_function:nN {#1} \__enumext_anspic_row:n
4988    }
4989  \cs_generate_variant:Nn \__enumext_anspic_print:n { e, V }
```

The function `\__enumext_anspic_row:n` will set the *widths* for the `minipage` environments and place *all arguments* passed to `\anspic` *saved* in the `\l__enumext_anspic_args_seq` sequence inside them.

```
4990  \cs_new_protected:Nn \__enumext_anspic_row:n
4991    {
4992      \dim_set:Nn \l__enumext_anspic_mini_width_dim { \linewidth / #1 }
4993      \int_set:Nn \l__enumext_anspic_above_int { \l__enumext_anspic_below_int }
4994      \int_set:Nn \l__enumext_anspic_below_int { \l__enumext_anspic_above_int + #1 }
4995      \int_step_inline:nnn
4996        { \l__enumext_anspic_above_int + 1 }
4997        { \l__enumext_anspic_below_int }
4998        {
4999          \IfDocumentMetadataT
5000            {
5001              \tag_suspend:n {minipage}
5002            }
5003          \begin{minipage}[ \l__enumext_anspic_mini_pos_str ]{
5004            \l__enumext_anspic_mini_width_dim }
5005            \centering
5006            \seq_item:Nn \l__enumext_anspic_args_seq {##1}
5007          \end{minipage}
5008          \IfDocumentMetadataT
5009            {
5010              \tag_resume:n {minipage}
5011            }
5012        }
5013      \par
5014    }
```

The `\__enumext_anspic_exec:` function will execute all the code in the `\anspic` command in the second argument of the `keyanspic` environment definition. If the key `layout-sty` is not set, everything will be

printed on a *single line*.

```
\cs_new_protected:Nn \__enumext_anspic_exec:
  {
    \tl_if_empty:NTF \l__enumext_anspic_layout_style_tl
      {
        \__enumext_anspic_print:e { \seq_count:N \l__enumext_anspic_args_seq }
      }
      {
        \__enumext_anspic_print:V \l__enumext_anspic_layout_style_tl
      }
  }
```

(*End of definition for* `\__enumext_anspic_body_dim:n` *and others.*)

`\anspic` The command is active in the `keyanspic` environment only if the `save-ans` key is present, otherwise an error is returned. The three arguments are handled by the function `\__enumext_anspic_args:nnn` and stored in the sequence `\l__enumext_anspic_args_seq` which is processed by the `keyanspic` environment.

```
\NewDocumentCommand \anspic { s o +m }
  {
    \bool_if:NF \l__enumext_store_active_bool
      {
        \msg_error:nnnn { enumext } { wrong-place }{ keyanspic }{ save-ans }
      }
    \int_compare:nNnT { \l__enumext_level_int } > { 1 }
      {
        \msg_error:nn { enumext } { keyanspic-wrong-level }
      }
    \int_compare:nNnT { \l__enumext_keyans_level_int } = { 1 }
      {
        \msg_error:nnnn { enumext } { command-wrong-place }{ anspic }{ keyans }
      }
    \seq_put_right:Nn \l__enumext_anspic_args_seq
      {
        \__enumext_anspic_args:nnn {#1} {#2} {#3}
      }
  }
```

(*End of definition for* `\anspic`. *This function is documented on page 18.*)

13.45.3 Definition of error messages for `keyanspic`

`keyanspic-nested` `keyanspic-wrong-level` `keyanspic-item-cmd` Messages used by `keyanspic` environment.

```
\msg_new:nnn { enumext } { keyanspic-nested }
  {
    The~environment~'keyanspic'~can't~be~nested~\msg_line_context:.
  }
\msg_new:nnn { enumext } { keyanspic-wrong-level }
  {
    Wrong~level~position~for~'keyanspic'~\msg_line_context:.\\
    The~environment~'keyanspic'~can~only~be~in~the~first~level.
  }
\msg_new:nnn { enumext } { keyanspic-item-cmd }
  {
    Can't~use~\c_backslash_str item~in~keyanspic~\msg_line_context:.
  }
```

(*End of definition for* `keyanspic-nested`, `keyanspic-wrong-level`, *and* `keyanspic-item-cmd`.)

13.46 The horizontal environments

Generating *horizontal list environments* is NOT as simple as standard LaTeX list environments. The fundamental part of the code is adapted from the `shortlst` package to a more modern version using `expl3`. It is not possible to redefine `\item` and `\makelabel` using `\RenewDocumentCommand` as in the vertical *non starred* versions.

To achieve the *horizontal list environments*, the `\item` command and its ⟨*content*⟩ are captured in a *horizontal box* using `\makebox` for the `label` and a `minipage` environment for the ⟨*content*⟩ passed to `\item`; the *optional argument* (⟨*number*⟩) is also added to `\item` to be able to *join columns* horizontally. In simple terms, the goal is for `\item` to behave in the same way as in the `enumext` environment but with an additional *first optional argument* (⟨*number*⟩).

A side effect is the limitation of using `\item` in this way *without* using `\RenewDocumentCommand`, which loses the original definition and affects the *standard list environments* provided by LaTeX and any environment defined using base `list` environment, including: `itemize`, `enumerate`, `description`, `quote`, `quotation`, `verse`, `center`, `flushleft`, `flushright`, `verbatim`, `tabbing`, `trivlist`, `list` and all environments created with `\newtheorem`.

One way to get around this is to use something like:

```
\AddToHook{env/enumerate/before}{recover original \item definition}
```

inside `minipage`, but in partial tests this does not have the desired effect and the vertical and horizontal spacing is distorted. For now this remains a limitation, and its implementation may be reconsidered in the future.

For compatibility with the *tagged* PDF, the environments are closed according to the presence or not of the `mini-env` key.

13.46.1 Functions for item box width

`\__enumext_starred_columns_set_vii:`
`\__enumext_starred_columns_set_viii:`

Sets the default value for the *width of the box* containing the ⟨*content*⟩ of the items for `enumext*` environment.

```
\cs_new_protected:Nn \__enumext_starred_columns_set_vii:
  {
    \dim_compare:nNnT { \l__enumext_columns_sep_vii_dim } = { \c_zero_dim }
      {
        \dim_set:Nn \l__enumext_columns_sep_vii_dim
          {
            ( \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim )
            / \l__enumext_columns_vii_int
          }
      }
    \int_set:Nn \l__enumext_tmpa_vii_int { \l__enumext_columns_vii_int - 1 }
    \dim_set:Nn \l__enumext_item_width_vii_dim
      {
        ( \linewidth - \l__enumext_columns_sep_vii_dim * \l__enumext_tmpa_vii_int )
        / \l__enumext_columns_vii_int
        - \l__enumext_labelwidth_vii_dim
        - \l__enumext_labelsep_vii_dim
      }
```

When the key `rightmargin` is active the values must be adjusted.

```
    \dim_compare:nNnT { \l__enumext_rightmargin_vii_dim } > { \c_zero_dim }
      {
        \dim_sub:Nn \l__enumext_item_width_vii_dim
          {
            ( \l__enumext_rightmargin_vii_dim * \l__enumext_tmpa_vii_int )
            / \l__enumext_columns_vii_int
          }
        \dim_add:Nn \l__enumext_columns_sep_vii_dim
          {
            \l__enumext_rightmargin_vii_dim
          }
      }
  }
```

Same implementation for the `keyans*` environment.

```
\cs_new_protected:Nn \__enumext_starred_columns_set_viii:
  {
    \dim_compare:nNnT { \l__enumext_columns_sep_viii_dim } = { \c_zero_dim }
      {
        \dim_set:Nn \l__enumext_columns_sep_viii_dim
          {
            ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim )
            / \l__enumext_columns_viii_int
          }
      }
    \int_set:Nn \l__enumext_tmpa_viii_int { \l__enumext_columns_viii_int - 1 }
    \dim_set:Nn \l__enumext_item_width_viii_dim
      {
        ( \linewidth - \l__enumext_columns_sep_viii_dim * \l__enumext_tmpa_viii_int )
        / \l__enumext_columns_viii_int
        - \l__enumext_labelwidth_viii_dim
        - \l__enumext_labelsep_viii_dim
      }
    \dim_compare:nNnT { \l__enumext_rightmargin_viii_dim } > { \c_zero_dim }
```

```
      {
        \dim_sub:Nn \l__enumext_item_width_viii_dim
          {
            ( \l__enumext_rightmargin_viii_dim * \l__enumext_tmpa_viii_int )
            / \l__enumext_columns_viii_int
          }
        \dim_add:Nn \l__enumext_columns_sep_viii_dim
          {
            \l__enumext_rightmargin_viii_dim
          }
      }
  }
```

(*End of definition for* `\__enumext_starred_columns_set_vii:` *and* `\__enumext_starred_columns_set_viii:`.)

13.46.2 Functions for join item columns

`\__enumext_starred_joined_item_vii:n`
`\__enumext_starred_joined_item_viii:n`

The functions `\__enumext_starred_joined_item_vii:n` and `\__enumext_starred_joined_item_viii:n` will set the *width* of the box in which the ⟨*content*⟩ passed to `\item`(⟨*columns*⟩) will be stored together with the value of `\itemwidth` for the `enumext*` environment.

```
\cs_new_protected:Nn \__enumext_starred_joined_item_vii:n
  {
    \int_set:Nn \l__enumext_joined_item_vii_int {#1}
    \int_compare:nNnT { \l__enumext_joined_item_vii_int } > { \l__enumext_columns_vii_int }
      {
        \msg_warning:nnee { enumext } { item-joined }
          { \int_use:N \l__enumext_joined_item_vii_int }
          { \int_use:N \l__enumext_columns_vii_int }
        \int_set:Nn \l__enumext_joined_item_vii_int
          {
            \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1
          }
      }
    \int_compare:nNnT
      { \l__enumext_joined_item_vii_int }
        >
      { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1 }
      {
        \msg_warning:nnee { enumext } { item-joined-columns }
          { \int_use:N \l__enumext_joined_item_vii_int }
          {
            \int_eval:n
              { \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1 }
          }
        \int_set:Nn \l__enumext_joined_item_vii_int
          {
            \l__enumext_columns_vii_int - \l__enumext_item_column_pos_vii_int + 1
          }
      }
    \int_compare:nNnTF { \l__enumext_joined_item_vii_int } > { 1 }
      {
        \int_set_eq:NN \l__enumext_joined_item_aux_vii_int \l__enumext_joined_item_vii_int
        \int_decr:N \l__enumext_joined_item_aux_vii_int
        \int_add:Nn \l__enumext_item_column_pos_vii_int
          { \l__enumext_joined_item_aux_vii_int }
        \int_gadd:Nn \g__enumext_item_count_all_vii_int
          { \l__enumext_joined_item_aux_vii_int }
        \dim_set:Nn \l__enumext_joined_width_vii_dim
          {
            \l__enumext_item_width_vii_dim * \l__enumext_joined_item_vii_int
            + (  \l__enumext_labelwidth_vii_dim + \l__enumext_labelsep_vii_dim
               + \l__enumext_columns_sep_vii_dim
              )*\l__enumext_joined_item_aux_vii_int
          }
        \dim_set_eq:NN \itemwidth \l__enumext_joined_width_vii_dim
      }
      {
        \dim_set_eq:NN \l__enumext_joined_width_vii_dim \l__enumext_item_width_vii_dim
        \dim_set_eq:NN \itemwidth \l__enumext_item_width_vii_dim
      }
  }
```

Same implementation for the keyans* environment.

```
\cs_new_protected:Nn \__enumext_starred_joined_item_viii:n
  {
    \int_set:Nn \l__enumext_joined_item_viii_int {#1}
    \int_compare:nNnT { \l__enumext_joined_item_viii_int } >
      { \l__enumext_columns_viii_int }
      {
        \msg_warning:nnee { enumext } { item-joined }
          { \int_use:N \l__enumext_joined_item_viii_int }
          { \int_use:N \l__enumext_columns_viii_int }
        \int_set:Nn \l__enumext_joined_item_viii_int
          {
            \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1
          }
      }
    \int_compare:nNnT
      { \l__enumext_joined_item_viii_int }
        >
      { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1 }
      {
        \msg_warning:nnee { enumext } { item-joined-columns }
          { \int_use:N \l__enumext_joined_item_viii_int }
          {
            \int_eval:n
              { \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1 }
          }
        \int_set:Nn \l__enumext_joined_item_viii_int
          {
            \l__enumext_columns_viii_int - \l__enumext_item_column_pos_viii_int + 1
          }
      }
    \int_compare:nNnTF { \l__enumext_joined_item_viii_int } > { 1 }
      {
        \int_set_eq:NN \l__enumext_joined_item_aux_viii_int \l__enumext_joined_item_viii_int
        \int_decr:N \l__enumext_joined_item_aux_viii_int
        \int_add:Nn \l__enumext_item_column_pos_viii_int
          { \l__enumext_joined_item_aux_viii_int }
        \int_gadd:Nn \g__enumext_item_count_all_viii_int
          { \l__enumext_joined_item_aux_viii_int }
        \dim_set:Nn \l__enumext_joined_width_viii_dim
          {
            \l__enumext_item_width_viii_dim * \l__enumext_joined_item_viii_int
            + ( \l__enumext_labelwidth_viii_dim + \l__enumext_labelsep_viii_dim
                + \l__enumext_columns_sep_viii_dim
              )*\l__enumext_joined_item_aux_viii_int
          }
        \dim_set_eq:NN \itemwidth \l__enumext_joined_width_viii_dim
      }
      {
        \dim_set_eq:NN \l__enumext_joined_width_viii_dim \l__enumext_item_width_viii_dim
        \dim_set_eq:NN \itemwidth \l__enumext_item_width_viii_dim
      }
  }
```

(*End of definition for* __enumext_starred_joined_item_vii:n *and* __enumext_starred_joined_item_viii:n.)

13.46.3 Functions for mini-env, mini-right and mini-right* keys

__enumext_start_mini_vii:
__enumext_stop_mini_vii:

The implementation of the mini-env key support is almost identical to the one used in the enumext and keyans environments, the difference is that the __enumext_mini_page environment on the *"right side"* is executed *"after"* closing the environment, so it is necessary to make a global copy of the variable \l__enumext_minipage_right_vii_dim in the variable \g__enumext_minipage_right_vii_dim.

```
\cs_new_protected:Nn \__enumext_start_mini_vii:
  {
    \dim_compare:nNnT { \l__enumext_minipage_right_vii_dim } > { \c_zero_dim }
      {
        \dim_set:Nn \l__enumext_minipage_left_vii_dim
          {
            \linewidth
            - \l__enumext_minipage_right_vii_dim
            - \l__enumext_minipage_hsep_vii_dim
```

```
      }
    \bool_set_true:N \l__enumext_minipage_active_vii_bool
    \dim_gset_eq:NN
      \g__enumext_minipage_right_vii_dim
      \l__enumext_minipage_right_vii_dim
    \__enumext_mini_addvspace_vii:
    \nointerlineskip\noindent
    \__enumext_mini_page{ \l__enumext_minipage_left_vii_dim }
  }
}
```

The function `\__enumext_stop_mini_vii:` closes the `\__enumext_mini_page` environment on the *"left side"*, applies `\hfill` and sets the variable `\g__enumext_minipage_active_vii_bool` to *"true"* which will be used in the function `\__enumext_after_env:nn` to execute the `minipage` on the *"right side"*. At this point the `\__enumext_stop_list:` and `\__enumext_stop_store_level_vii:` functions are executed, stopping the `list` environment and the level saving mechanism for storage in *sequence* of the `\anskey` command and `anskey*` environment. This function is passed to the `\__enumext_after_list_vii:` function in the second part of the `enumext*` environment definition (§13.47).

```
\cs_new_protected:Nn \__enumext_stop_mini_vii:
  {
    \bool_if:NTF \l__enumext_minipage_active_vii_bool
      {
        \__enumext_stop_list:
        \__enumext_stop_store_level_vii:
        \IfDocumentMetadataT { \tag_resume:n {enumext*} }
        \end__enumext_mini_page
        \hfill
        \bool_gset_true:N \g__enumext_minipage_active_vii_bool
      }
      {
        \__enumext_stop_list:
        \__enumext_stop_store_level_vii:
      }
  }
```

(*End of definition for* `\__enumext_start_mini_vii:` *and* `\__enumext_stop_mini_vii:`.)

Finally the {⟨*code*⟩} passed to the `mini-right` or `mini-right*` keys stored in the variable `\g__enumext_miniright_code_vii_tl` in the `minipage` environment on the *"right side"* is executed. For compatibility with the `caption` package and possibly other {⟨*code*⟩} passed to this key, it is passed to a box and then printed.

```
\__enumext_after_env:nn {enumext*}
  {
    \bool_if:NT \g__enumext_minipage_active_vii_bool
      {
        \__enumext_minipage:w [ t ] { \g__enumext_minipage_right_vii_dim }
          \legacy_if_gset_false:n { @minipage }
          \skip_vertical:N \c_zero_skip
          \par\addvspace { \g__enumext_minipage_right_skip }
          \bool_if:NF \g__enumext_minipage_center_vii_bool
            {
              \tl_gput_left:Nn \g__enumext_miniright_code_vii_tl
                {
                  \centering
                }
            }
          \vbox_set_top:Nn \l__enumext_miniright_code_vii_box
            {
              \tl_use:N \g__enumext_miniright_code_vii_tl
            }
          \box_use_drop:N \l__enumext_miniright_code_vii_box
          \skip_vertical:N \c_zero_skip
        \__enumext_endminipage:
        \par\addvspace{ \g__enumext_minipage_after_skip }
      }
    \bool_gset_false:N \g__enumext_minipage_active_vii_bool
    \bool_gset_true:N \g__enumext_minipage_center_vii_bool
    \tl_gclear:N \g__enumext_miniright_code_vii_tl
    \dim_gzero:N \g__enumext_minipage_right_vii_dim
    \bool_gset_false:N \g__enumext_starred_bool
  }
```

©2024–2026 by Pablo González L

__enumext_start_mini_viii:
__enumext_stop_mini_viii:

The implementation of the mini-env, mini-right and mini-right* keys is identical to the one used in the enumext* environment.

```
\cs_new_protected:Nn \__enumext_start_mini_viii:
  {
    \dim_compare:nNnT { \l__enumext_minipage_right_viii_dim } > { \c_zero_dim }
      {
        \dim_set:Nn \l__enumext_minipage_left_viii_dim
          {
            \linewidth
            - \l__enumext_minipage_right_viii_dim
            - \l__enumext_minipage_hsep_viii_dim
          }
        \bool_set_true:N \l__enumext_minipage_active_viii_bool
        \dim_gset_eq:NN
          \g__enumext_minipage_right_viii_dim
          \l__enumext_minipage_right_viii_dim
        \__enumext_mini_addvspace_viii:
        \nointerlineskip\noindent
        \__enumext_mini_page{ \l__enumext_minipage_left_viii_dim }
      }
  }
\cs_new_protected:Nn \__enumext_stop_mini_viii:
  {
    \bool_if:NTF \l__enumext_minipage_active_viii_bool
      {
        \__enumext_stop_list:
        \IfDocumentMetadataT { \tag_resume:n {keyans*} }
        \end__enumext_mini_page
        \hfill
        \bool_gset_true:N \g__enumext_minipage_active_viii_bool
      }
      {
        \__enumext_stop_list:
      }
  }
\__enumext_after_env:nn {keyans*}
  {
    \bool_if:NT \g__enumext_minipage_active_viii_bool
      {
        \__enumext_mini_page{ \g__enumext_minipage_right_viii_dim }
          \par\addvspace { \g__enumext_minipage_right_skip }
          \bool_if:NF \g__enumext_minipage_center_viii_bool
            {
              \tl_gput_left:Nn \g__enumext_miniright_code_viii_tl
                {
                  \centering
                }
            }
          \vbox_set_top:Nn \l__enumext_miniright_code_viii_box
            {
              \tl_use:N \g__enumext_miniright_code_viii_tl
            }
          \box_use_drop:N \l__enumext_miniright_code_viii_box
        \end__enumext_mini_page
        \par\addvspace{ \g__enumext_minipage_after_skip }
      }
    \bool_gset_false:N \g__enumext_minipage_active_viii_bool
    \bool_gset_true:N \g__enumext_minipage_center_viii_bool
    \tl_gclear:N \g__enumext_miniright_code_viii_tl
    \dim_gzero:N \g__enumext_minipage_right_viii_dim
  }
```

(*End of definition for* __enumext_start_mini_viii: *and* __enumext_stop_mini_viii:.)

13.46.4 Definition of error messages

nested-horizontal
item-joined
item-joined-columns

Messages used by enumext* and keyans* environments.

```
\msg_new:nnn { enumext } { nested-horizontal }
  {
    The~environment~\__enumext_envir_name_tl \c_space_tl can't~be~nested~in~'#1'~
    \msg_line_context:.
```

```
  }
\msg_new:nnn { enumext } { item-joined }
  {
    Items~joined~(#1)~>~#2~columns~\msg_line_context:.
  }
\msg_new:nnn { enumext } { item-joined-columns }
  {
    Not~enough~space~to~join~items~(#1)~>~#2~\msg_line_context:.
  }
```

(*End of definition for* `nested-horizontal` , `item-joined` , *and* `item-joined-columns`.)

13.47 The environment `enumext*`

enumext* First the environment is generated and a temporary definition is given to `\__enumext_stop_item_tmp_vii:` equal to `\__enumext_first_item_tmp_vii:` and next to `\item` equal to `\__enumext_start_item_tmp_vii:` which are redefined later. Unlike the implementation used by the `shortlst` package, the values of `\rightskip` and `\@rightskip` are not set equal to `\@flushglue`, whose value is `0.0pt plus 1.0 fil`; in the tests performed this fails in some circumstances and different results are obtained when using pdfTEX and LuaTEX.

```
\NewDocumentEnvironment{enumext*}{ o }
  {
    \__enumext_safe_exec_vii:
    \__enumext_parse_keys_vii:n {#1}
    \__enumext_before_list_vii:
    \__enumext_start_store_level_vii:
    \__enumext_start_list:nn { }
      {
        \__enumext_list_arg_two_vii:
        \__enumext_before_keys_exec_vii:
      }
    \IfDocumentMetadataT { \tag_suspend:n {enumext*} }
    \__enumext_starred_columns_set_vii:
    \item[] \scan_stop:
```

For compatibility with *tagged* PDF in LATEX release 2026-06-01, `\setcounter` is set at this point in the environment definition, thereby avoiding the problem reported by `@teepeemm` in enumext* nested in enumext starts at 2 with DocumentMetadata this was caused by the `latex-lab-block`[19] update in this release.

```
    \setcounter { enumXvii }
      { \int_eval:n { \int_use:c { l__enumext_start_vii_int } - 1 } }
    \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \__enumext_first_item_tmp_vii:
    \cs_set_eq:NN \item \__enumext_start_item_tmp_vii:
    \ignorespaces
  }
  {
    \IfDocumentMetadataT { \tag_struct_end:n {tag=semantic-para} } % {tag=text-unit}
    \__enumext_stop_item_tmp_vii:
    \__enumext_remove_extra_parsep_vii:
    \__enumext_after_list_vii:
  }
```

(*End of definition for* `enumext*`. *This function is documented on page* 5.)

__enumext_safe_exec_vii: The function `\__enumext_is_not_nested:` is called first, which sets `\g__enumext_starred_bool` to true if it is NOT nested within `enumext`; then the function `\__enumext_internal_mini_page:` is called to create the environment `\__enumext_mini_page`, `\l__enumext_level_h_int` is incremented to restrict nesting of the environment, `\l__enumext_starred_bool` is set to true, and finally the function `\__enumext_is_on_first_level:` is called, which sets `\l__enumext_starred_first_bool` to true if it is not nested, allowing the *"storage system"* to be used.

```
\cs_new_protected:Nn \__enumext_safe_exec_vii:
  {
    \__enumext_is_not_nested:
    \__enumext_internal_mini_page:
    \int_incr:N \l__enumext_level_h_int
    \int_compare:nNnT { \l__enumext_level_h_int } > { 1 }
      {
        \msg_error:nn { enumext } { nested }
      }
    \int_compare:nNnT { \l__enumext_keyans_level_h_int } = { 1 }
      {
```

```
5396          \msg_error:nnn { enumext } { nested-horizontal } { keyans*}
5397        }
5398      \bool_set_true:N \l__enumext_starred_bool
5399      \bool_set_false:N \l__enumext_standard_bool
5400      \__enumext_is_on_first_level:
5401    }
```

(*End of definition for* `\__enumext_safe_exec_vii:`.)

`\__enumext_parse_keys_vii:n`

It first checks the state of the variable `\l__enumext_resume_count_vii_bool` set by the key `resume` and calls the function `\__enumext_resume_last_counter:` if it is "true", then clears the variable `\l__enumext_series_name_str` used by the key `series`, processes the environment [⟨*key* = *val*⟩] and executes the function `\__enumext_parse_series:n` used by the key `series`, then executes the function `\__enumext_store_active_keys_vii:n` and reprocesses the ⟨*keys*⟩ to pass them to the storage *sequence* if the key `save-key` is not active.

Here it is necessary to check the status of `\l__enumext_resume_count_vii_bool` in case the key `resume` is set using `\setenumext{enumext*}{resume}`.

```
5402 \cs_new_protected:Nn \__enumext_parse_keys_vii:n
5403   {
5404     \bool_if:NT \l__enumext_resume_count_vii_bool
5405       {
5406         \__enumext_resume_last_counter:
5407       }
5408     \tl_if_novalue:nF {#1}
5409       {
5410          \str_clear:N \l__enumext_series_name_str
5411          \keys_set:nn { enumext / enumext* } {#1}
5412          \bool_if:NF \l__enumext_print_keyans_cmd_bool
5413            {
5414              \__enumext_parse_series:n {#1}
5415            }
5416          \__enumext_store_active_keys_vii:n {#1}
5417       }
5418   }
```

(*End of definition for* `\__enumext_parse_keys_vii:n`.)

`\__enumext_before_list_vii:`

The function `\__enumext_before_list_vii:` first calls the function `\__enumext_vspace_above_vii:` used by the keys `above` and `above*`, then calls the function `\__enumext_check_ans_active:` for the check answer mechanism and finally calls the functions `\__enumext_before_args_exec_vii:` and `\__enumext_start_mini_vii:` used by the keys `before*`, `mini-env`, `mini-right` and `mini-right*`.

```
5419 \cs_new_protected:Nn \__enumext_before_list_vii:
5420   {
5421     \__enumext_vspace_above_vii:
5422     \__enumext_check_ans_active:
5423     \__enumext_before_args_exec_vii:
5424     \__enumext_start_mini_vii:
5425   }
```

(*End of definition for* `\__enumext_before_list_vii:`.)

`\__enumext_after_list_vii:`

The function `\__enumext_after_list_vii:` first calls the function `\__enumext_stop_mini_vii:` which internally calls `\__enumext_stop_list:` and `\__enumext_stop_store_level_vii:` (§13.46.3) used by the keys `mini-env`, `mini-right` and `mini-right*`, then to the functions `\__enumext_after_stop_list_vii:` used by the key `after`, `\__enumext_check_ans_key_hook:` used by the key `check-ans`, `\__enumext_vspace_below_vii:` used by the keys `below` and `below*`. Finally set `\l__enumext_starred_bool` to false and call the `\__enumext_resume_save_counter:` function used by the `series`, `resume` and `resume*` keys.

```
5426 \cs_new_protected:Nn \__enumext_after_list_vii:
5427   {
5428     \__enumext_stop_mini_vii:
5429     \__enumext_after_stop_list_vii:
5430     \__enumext_check_ans_key_hook:
5431     \__enumext_vspace_below_vii:
5432     \bool_set_false:N \l__enumext_starred_bool
5433     \bool_if:NF \l__enumext_print_keyans_cmd_bool
5434       {
```

```
      \__enumext_starred_save_counter:
    }
  }
```

(*End of definition for* `\__enumext_after_list_vii:`.)

`\__enumext_start_store_level_vii:`
`\__enumext_stop_store_level_vii:`

The `\__enumext_start_store_level_vii:` and `\__enumext_stop_store_level_vii:` functions activate the *"storing structure"* mechanism in *sequence* for `\anskey` command and `anskey*` environment if `enumext*` are nested in `enumext`.

```
\cs_new_protected:Nn \__enumext_start_store_level_vii:
  {
    \bool_if:NT \l__enumext_store_active_bool
      {
        \int_compare:nNnT { \l__enumext_level_int } > { 0 }
          {
            \__enumext_store_level_open_vii:
          }
      }
  }
\cs_new_protected:Nn \__enumext_stop_store_level_vii:
  {
    \bool_if:NT \l__enumext_store_active_bool
      {
        \int_compare:nNnT { \l__enumext_level_int } > { 0 }
          {
            \__enumext_store_level_close_vii:
          }
      }
  }
```

(*End of definition for* `\__enumext_start_store_level_vii:` *and* `\__enumext_stop_store_level_vii:`.)

13.47.1 The command `\item` in `enumext*`

`\__enumext_first_item_tmp_vii:`

The `\__enumext_first_item_tmp_vii:` function will remove horizontal space equal to `\labelwidth` plus `\labelsep` to the left of the *"first"* `\item` in the environment at the point of execution of this function, where it is equal to the `\__enumext_stop_item_tmp_vii:` function inside the environment body definition.

```
\cs_new_protected_nopar:Nn \__enumext_first_item_tmp_vii:
  {
    \skip_horizontal:n
      {
        -\l__enumext_labelwidth_vii_dim - \l__enumext_labelsep_vii_dim
      }
    \ignorespaces
  }
```

(*End of definition for* `\__enumext_first_item_tmp_vii:`.)

`\__enumext_start_item_tmp_vii:`
`\__enumext_item_peek_args_vii:`
`\__enumext_joined_item_vii:w`
`\__enumext_standard_item_vii:w`
`\__enumext_starred_item_vii:w`
`\__enumext_starred_item_vii_aux_i:w`
`\__enumext_starred_item_vii_aux_ii:w`
`\__enumext_starred_item_vii_aux_iii:w`

First the function `\__enumext_stop_item_tmp_vii:` is called, which is redefined later, then the value of `\l__enumext_item_column_pos_vii_int`, which counts the items by rows, and the value of `\g__enumext_item_count_all_vii_int`, which counts the total of items in the environment, are incremented. After that the function `\__enumext_item_peek_args_vii:` is called, which handles the arguments passed to `\item`.

```
\cs_new_protected_nopar:Nn \__enumext_start_item_tmp_vii:
  {
    \__enumext_stop_item_tmp_vii:
    \int_incr:N \l__enumext_item_column_pos_vii_int
    \int_gincr:N \g__enumext_item_count_all_vii_int
    \__enumext_item_peek_args_vii:
  }
```

The function `\__enumext_item_peek_args_vii:` handles the `\item(`⟨*number*⟩`)`. It looks for the argument "`(`"; if it is present, it calls the function `\__enumext_joined_item_vii:w (`⟨*number*⟩`)`, which is in charge of joining the items in the same row; if it is not present, it sets the default value `(1)`.

```
\cs_new_protected:Nn \__enumext_item_peek_args_vii:
  {
    \peek_meaning:NTF (
      { \__enumext_joined_item_vii:w }
      { \__enumext_joined_item_vii:w (1) }
  }
```

The function __enumext_joined_item_vii:w will first call the function __enumext_starred_joined_item_vi in charge of setting the *width* of the box that stores the content passed to \item. Then it looks for the argument "*"; if it is present, it calls the function __enumext_starred_item_vii:w, otherwise it calls the function __enumext_standard_item_vii:w.

```
\cs_new_protected:Npn \__enumext_joined_item_vii:w (#1)
  {
    \__enumext_starred_joined_item_vii:n {#1}
    \peek_meaning_remove:NTF *
      { \__enumext_starred_item_vii:w  }
      { \__enumext_standard_item_vii:w }
  }
```

The function __enumext_standard_item_vii:w will first look for the argument "[", if present it will set the state of the variable \l__enumext_wrap_label_opt_vii_bool equal to the state of the variable \l__enumext_wrap_label_opt_vii_bool handled by the key wrap-label* and finally execute the *non-enumerated* version \item[⟨*custom*⟩] by means of the function __enumext_start_item_vii:w; otherwise it sets the value of the variable \l__enumext_wrap_label_vii_bool handled by the wrap-label key to true and set the switch \if@noitemarg to true to execute the enumerated version of \item by means of the function __enumext_start_item_vii:w [\l__enumext_label_vii_tl].

```
\cs_new_protected:Npn \__enumext_standard_item_vii:w
  {
    \bool_set_false:N \l__enumext_item_starred_vii_bool
    \peek_meaning:NTF [
      {
        \bool_set_eq:NN \l__enumext_wrap_label_vii_bool \l__enumext_wrap_label_opt_vii_bool
        \__enumext_start_item_vii:w
      }
      {
        \bool_set_true:N \l__enumext_wrap_label_vii_bool
        \legacy_if_set_true:n { @noitemarg }
        \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ] \ignorespaces
      }
  }
```

The function __enumext_starred_item_vii:w together with the specified auxiliary functions aux_i:w, aux_ii:w, and aux_iii:w execute \item*, \item*[⟨*symbol*⟩] and \item*[⟨*symbol*⟩][⟨*offset*⟩].

```
\cs_new_protected:Npn \__enumext_starred_item_vii:w
  {
    \bool_set_true:N \l__enumext_item_starred_vii_bool
    \bool_set_true:N \l__enumext_wrap_label_vii_bool
    \peek_meaning:NTF [
      { \__enumext_starred_item_vii_aux_i:w }
      { \__enumext_starred_item_vii_aux_ii:w }
  }
\cs_new_protected:Npn \__enumext_starred_item_vii_aux_i:w [#1]
  {
    \tl_gset:Nn \g__enumext_item_symbol_aux_vii_tl {#1}
    \__enumext_starred_item_vii_aux_ii:w
  }
\cs_new_protected:Npn \__enumext_starred_item_vii_aux_ii:w
  {
    \peek_meaning:NTF [
      { \__enumext_starred_item_vii_aux_iii:w }
      {
        \dim_set_eq:NN \l__enumext_item_symbol_sep_vii_dim \l__enumext_labelsep_vii_dim
        \legacy_if_set_true:n { @noitemarg }
        \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ] \ignorespaces
      }
  }
\cs_new_protected:Npn \__enumext_starred_item_vii_aux_iii:w [#1]
  {
    \dim_set:Nn \l__enumext_item_symbol_sep_vii_dim {#1}
    \legacy_if_set_true:n { @noitemarg }
    \__enumext_start_item_vii:w [ \l__enumext_label_vii_tl ] \ignorespaces
  }
```

(*End of definition for* __enumext_start_item_tmp_vii: *and others.*)

__enumext_fake_make_label_vii:n

The __enumext_fake_make_label_vii:n function will be in charge of handling the definition of \item. First it increments the counter enumXvii for the enumerated items and activates support for the *check answers*

mechanism, followed by support for \item*[⟨symbol⟩][⟨offset⟩] if present, then the wrap-label and wrap-label* keys, executed using \makebox whose width is given by the labelwidth key and position by the align key; inside its argument it executes the font key together with the function defined by the wrap-label or wrap-label* keys. Finally it executes the labelsep key applying a \skip_horizontal:N and \ignorespaces.

For compatibility with *tagged* PDF and hyperref when an environment enumext is nested in enumext* and the key save-ans is not active need setting the \if@hyper@item switch to *"true"*. The explanation for this is given by the master Heiko Oberdiek on \refstepcounter{enumi} twice (or more) creates destination with the same identifier. This patch is only needed if you are running pdflatex and not if you are running lualatex

```
\cs_new_protected_nopar:Nn \__enumext_fake_make_label_vii:n
  {
    \legacy_if:nT { @noitemarg }
      {
        \legacy_if_set_false:n { @noitemarg }
        \legacy_if:nT { @nmbrlist }
          {
            \IfDocumentMetadataT
              {
                \bool_if:NT \l__enumext_hyperref_bool
                  {
                    \legacy_if_set_true:n { @hyper@item }
                  }
              }
            \refstepcounter{enumXvii}
            \bool_if:NT \l__enumext_check_answers_bool
              {
                \int_gincr:N \g__enumext_item_number_int
                \bool_set_true:N \l__enumext_item_number_bool
              }
          }
      }
    \bool_if:NT \l__enumext_item_starred_vii_bool
      {
        \tl_if_blank:VT \g__enumext_item_symbol_aux_vii_tl
          {
            \tl_gset_eq:NN
              \g__enumext_item_symbol_aux_vii_tl \l__enumext_item_symbol_vii_tl
          }
        \mode_leave_vertical:
        \skip_horizontal:n { -\l__enumext_item_symbol_sep_vii_dim }
        \hbox_overlap_left:n { \g__enumext_item_symbol_aux_vii_tl }
        \skip_horizontal:N \l__enumext_item_symbol_sep_vii_dim
        \tl_gclear:N \g__enumext_item_symbol_aux_vii_tl
      }
    \makebox[ \l__enumext_labelwidth_vii_dim ][ \l__enumext_align_label_vii_str ]
      {
        \tl_use:N \l__enumext_label_font_style_vii_tl
        \bool_if:NTF \l__enumext_wrap_label_vii_bool
          {
            \__enumext_wrapper_label_vii:n {#1}
          }
          {#1}
      }
    \skip_horizontal:N \l__enumext_labelsep_vii_dim \ignorespaces
  }
```

(*End of definition for* __enumext_fake_make_label_vii:n.)

13.47.2 Real definition of \item in enumext*

The functions __enumext_start_item_vii:w and __enumext_stop_item_vii: executing the true definition of \item inside the enumext* environment, unlike the implementation in shortlst, an extra group is NOT used and the plain form of the lrbox environment.

__enumext_start_item_vii:w
__enumext_stop_item_vii:

First the value of __enumext_stop_item_tmp_vii: is set equal to __enumext_stop_item_vii:, which is defined later; after that it starts capturing \item and *"item content"* in a *horizontal box* where the width will be \itemwidth plus \labelwidth plus \labelsep.

```
\cs_new_protected_nopar:Npn \__enumext_start_item_vii:w [#1]
  {
```

```
    \cs_set_eq:NN \__enumext_stop_item_tmp_vii: \__enumext_stop_item_vii:
    \hbox_set_to_wd:Nnw \l__enumext_item_text_vii_box
      {
        \l__enumext_joined_width_vii_dim
        + \l__enumext_labelwidth_vii_dim
        + \l__enumext_labelsep_vii_dim
      }
```

Redefine the \footnote command.

```
      \__enumext_renew_footnote_starred:
```

Now the *sockets* for *tagging* PDF support are inserted and \item is run.

```
      \__enumext_start_list_tag:n {enumext*}
      \__enumext_fake_make_label_vii:n {#1}
      \__enumext_stop_start_list_tag:
```

Finally the minipage environment is opened, the *"item content"* is captured, \parindent takes the value of the key listparindent and \parskip takes the value of the key parsep, then the keys itemindent and first are executed.

Here the use of \unskip and \skip_horizontal:n with the value of listparindent is necessary, otherwise an unwanted space is created when using \item[⟨*opt*⟩] and the value passed to the key itemindent is incremented.

```
      \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_vii_dim }
        \dim_set_eq:NN \parindent \l__enumext_listparindent_vii_dim
        \skip_set_eq:NN \parskip \l__enumext_parsep_vii_skip
        \__enumext_unskip_unkern:
        \__enumext_unskip_unkern:
        \skip_horizontal:n { -\l__enumext_listparindent_vii_dim } \ignorespaces
        \tl_use:N \l__enumext_fake_item_indent_vii_tl
        \tl_use:N \l__enumext_after_list_args_vii_tl
  }
```

The __enumext_stop_item_vii: function will finish fetching \item and *"item content"* by closing the minipage environment, the *sockets* for *tagging* PDF and the *horizontal box*.

```
\cs_new_protected_nopar:Nn \__enumext_stop_item_vii:
  {
      \__enumext_endminipage:
    \__enumext_stop_list_tag:n {enumext*}
    \hbox_set_end:
```

Here the *warnings* are reduced a bit by setting the value of \hbadness to 10000, print \item and *"item content"* from the *horizontal box*.

```
    \int_set:Nn \hbadness { 10000 }
    \box_use_drop:N \l__enumext_item_text_vii_box
```

Finally apply the *vertical space* between rows set by itemsep key passed to \parsep using \par\noindent and *horizontal space* between columns set by columns-sep key using \skip_horizontal:N.

```
    \int_compare:nNnTF
      { \l__enumext_item_column_pos_vii_int } = { \l__enumext_columns_vii_int }
      {
        \par\noindent
        \int_zero:N \l__enumext_item_column_pos_vii_int
      }
      {
        \skip_horizontal:N \l__enumext_columns_sep_vii_dim
      }
  }
```

(*End of definition for* __enumext_start_item_vii:w *and* __enumext_stop_item_vii:.)

__enumext_remove_extra_parsep_vii:

Remove the extra *vertical space* equal to \parsep=\itemsep when the total number of \item is divisible by the number of \item in the last row of the environment. Here the use of \unskip or \removelastskip fails and does not obtain the expected result; using \vspace is the option and in this case a simplified version can be used since it is always in ⟨*vertical mode*⟩.

```
\cs_new_protected:Nn \__enumext_remove_extra_parsep_vii:
  {
    \int_compare:nNnT
      {
        \int_mod:nn
```

```
          {  \g__enumext_item_count_all_vii_int } { \l__enumext_columns_vii_int }
      }
      =
      { 0 }
      {
        \para_end:
        \skip_vertical:n { -\l__enumext_itemsep_vii_skip }
        \skip_vertical:N \c_zero_skip
        \int_gzero:N \g__enumext_item_count_all_vii_int
      }
  }
```

(*End of definition for* `\__enumext_remove_extra_parsep_vii:`.)

Since the `check-ans` check must not be executed by levels but on the complete list, it is taken out of the `enumext*` environment using the *"hook"* function `\__enumext_after_env:nn`.

```
\__enumext_after_env:nn {enumext*}
  {
    \__enumext_execute_after_env:
  }
```

13.48 The environment keyans*

keyans*

The implementation of `keyans*` environment is the similar as that used by the `enumext*` environment except for the `\__enumext_check_starred_cmd:n` function added in the second part.

```
\NewDocumentEnvironment{keyans*}{ o }
  {
    \__enumext_safe_exec_viii:
    \__enumext_parse_keys_viii:n {#1}
    \__enumext_before_list_viii:
    \__enumext_start_list:nn { }
      {
        \__enumext_list_arg_two_viii:
        \__enumext_before_keys_exec_viii:
      }
    \IfDocumentMetadataT { \tag_suspend:n {keyans*} }
    \__enumext_starred_columns_set_viii:
    \item[] \scan_stop:
    % Set start counter
    \setcounter { enumXviii }
      { \int_eval:n { \int_use:c { l__enumext_start_viii_int } - 1 } }
    \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \__enumext_first_item_tmp_viii:
    \cs_set_eq:NN \item \__enumext_start_item_tmp_viii:
    \ignorespaces
  }
  {
    \IfDocumentMetadataT { \tag_struct_end:n {tag=semantic-para} } % {tag=text-unit}
    \__enumext_stop_item_tmp_viii:
    \__enumext_remove_extra_parsep_viii:
    \__enumext_check_starred_cmd:n { item }
    \__enumext_after_list_viii:
  }
```

(*End of definition for* `keyans*`. *This function is documented on page 17.*)

`\__enumext_safe_exec_viii:`

The `\__enumext_safe_exec_viii:` function first checks if the `save-ans` key is active; only when this is true is the environment available. It increments the value of `\l__enumext_keyans_level_h_int` and returns an error message when the environment is nested, then calls the `\__enumext_keyans_name_and_start:` function in charge of saving the name of the environment and the line it is running on, then checks if `keyans*` is being nested in `enumext*`, returning an error, and sets `\l__enumext_starred_bool` to true; finally it checks if it is at the appropriate level within the `enumext` environment.

```
\cs_new_protected:Nn \__enumext_safe_exec_viii:
  {
    \bool_if:NF \l__enumext_store_active_bool
      {
        \msg_error:nnnn { enumext } { wrong-place }{ keyans* }{ save-ans }
      }
    \int_incr:N \l__enumext_keyans_level_h_int
    \int_compare:nNnT { \l__enumext_keyans_level_h_int } > { 1 }
      {
```

```
      \msg_error:nn { enumext } { nested }
    }
  \__enumext_keyans_name_and_start:
  \bool_if:NT \l__enumext_starred_bool
    {
      \msg_error:nnn { enumext } { nested-horizontal } { enumext* }
    }
  \bool_set_true:N \l__enumext_starred_bool
  % Set false for interfering with enumext nested in keyans* (yes, its possible and crayze)
  \bool_set_false:N \l__enumext_store_active_bool
  \int_compare:nNnT { \l__enumext_level_int } > { 1 }
    {
      \msg_error:nn { enumext } { keyans-wrong-level }
    }
}
```

(*End of definition for* `\__enumext_safe_exec_viii:`.)

`\__enumext_parse_keys_viii:n` Parse [⟨*key* = *val*⟩] for `keyans*`.

```
\cs_new_protected:Nn \__enumext_parse_keys_viii:n
  {
    \tl_if_novalue:nF {#1}
      {
        \keys_set:nn { enumext / keyans* } {#1}
      }
  }
```

(*End of definition for* `\__enumext_parse_keys_viii:n`.)

`\__enumext_before_list_viii:` The function `\__enumext_before_list_viii:` will add the vertical spacing on the environment if the `above` key is active next to the {⟨*code*⟩} defined by the `before*` key if it is active (function `\__enumext_before_args_exec_viii:`), then call the function `\__enumext_start_mini_viii:` handled by `mini-env`.

```
\cs_new_protected:Nn \__enumext_before_list_viii:
  {
    \__enumext_vspace_above_viii:
    \__enumext_before_args_exec_viii:
    \__enumext_start_mini_viii:
  }
```

(*End of definition for* `\__enumext_before_list_viii:`.)

`\__enumext_after_list_viii:` The function `\__enumext_after_list_viii:` first calls the function `\__enumext_stop_mini_viii:`, then apply the {⟨*code*⟩} handled by the `after` key together with the *vertical space* handled by the `below` key if they are present.

```
\cs_new_protected:Nn \__enumext_after_list_viii:
  {
    \__enumext_stop_mini_viii:
    \__enumext_after_stop_list_viii:
    \__enumext_vspace_below_viii:
  }
```

(*End of definition for* `\__enumext_after_list_viii:`.)

13.48.1 The command `\item` in `keyans*`

The idea here is to make the `\item` command behave in the same way as in the `keyans` environment with the difference of the *optional argument* (⟨*number*⟩) which works in the same way as in the `enumext*` environment.

In simple terms, the goal is to store the ⟨*label*⟩ next to the [⟨*content*⟩] if it is present in the *sequence* and *prop list* defined by `save-ans` key for `\item*`, `\item*`[⟨*content*⟩], `\item`(⟨*number*⟩)`*` and `\item`(⟨*number*⟩)`*`[⟨*content*⟩] commands.

`\__enumext_first_item_tmp_viii:` The `\__enumext_first_item_tmp_viii:` function will remove horizontal space equal to `\labelwidth` plus `\labelsep` to the left of the *"first"* `\item` in the environment at the point of execution of this function, where it is equal to the `\__enumext_stop_item_tmp_viii:` function inside the environment body definition.

```
\cs_new_protected_nopar:Nn \__enumext_first_item_tmp_viii:
  {
    \skip_horizontal:n
```

```
5707        {
5708          -\l__enumext_labelwidth_viii_dim - \l__enumext_labelsep_viii_dim
5709        }
5710      \ignorespaces
5711    }
```

(*End of definition for* `\__enumext_first_item_tmp_viii:`.)

`\__enumext_start_item_tmp_viii:` `\__enumext_item_peek_args_viii:` `\__enumext_joined_item_viii:w` `\__enumext_standard_item_viii:w`

First the function `\__enumext_stop_item_tmp_viii:` is called, which is redefined later, then the value of `\l__enumext_item_column_pos_viii_int`, which counts the items by rows, and the value of `\g__enumext_item_count_all_viii_int`, which counts the total of items in the environment, are incremented. After that the function `\__enumext_item_peek_args_viii:` is called, which handles the arguments passed to `\item`.

```
5712 \cs_new_protected_nopar:Nn \__enumext_start_item_tmp_viii:
5713   {
5714     \__enumext_stop_item_tmp_viii:
5715     \int_incr:N \l__enumext_item_column_pos_viii_int
5716     \int_gincr:N \g__enumext_item_count_all_viii_int
5717     \__enumext_item_peek_args_viii:
5718   }
```

The function `\__enumext_item_peek_args_viii:` handles the `\item(`⟨*number*⟩`)`. It looks for the argument "`(`"; if it is present, it calls the function `\__enumext_joined_item_viii:w (`⟨*number*⟩`)`, which is in charge of joining the items in the same row; if it is not present, it sets the default value `(1)`.

```
5719 \cs_new_protected:Nn \__enumext_item_peek_args_viii:
5720   {
5721     \peek_meaning:NTF (
5722       { \__enumext_joined_item_viii:w }
5723       { \__enumext_joined_item_viii:w (1) }
5724   }
```

The function `\__enumext_joined_item_viii:w` will first call the function `\__enumext_starred_joined_item_v` in charge of setting the *width* of the box that stores the content passed to `\item`. Then it looks for the argument "`*`"; if it is present, it calls the function `\__enumext_starred_item_viii:w`, otherwise it calls the function `\__enumext_standard_item_viii:w`.

```
5725 \cs_new_protected:Npn \__enumext_joined_item_viii:w (#1)
5726   {
5727     \__enumext_starred_joined_item_viii:n {#1}
5728     \peek_meaning_remove:NTF *
5729       { \__enumext_starred_item_viii:w }
5730       { \__enumext_standard_item_viii:w }
5731   }
```

The function `\__enumext_standard_item_viii:w` will first look for the argument "`[`", if present it will set the state of the variable `\l__enumext_wrap_label_opt_viii_bool` equal to the state of the variable `\l__enumext_wrap_label_opt_viii_bool` handled by the key `wrap-label*` and finally execute the *non-enumerated* version `\item[`⟨*custom*⟩`]` by means of the function `\__enumext_start_item_viii:w`; otherwise it sets the value of the variable `\l__enumext_wrap_label_viii_bool` handled by the `wrap-label` key to true and set the switch `\if@noitemarg` to true to execute the enumerated version of `\item` by means of the function `\__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ]`.

```
5732 \cs_new_protected:Npn \__enumext_standard_item_viii:w
5733   {
5734     \bool_set_false:N \l__enumext_item_starred_viii_bool
5735     \bool_set_false:N \l__enumext_item_wrap_key_bool
5736     \peek_meaning:NTF [
5737       {
5738         \bool_set_eq:NN \l__enumext_wrap_label_viii_bool
5739           \l__enumext_wrap_label_opt_viii_bool
5740         \__enumext_start_item_viii:w
5741       }
5742       {
5743         \bool_set_true:N \l__enumext_wrap_label_viii_bool
5744         \legacy_if_set_true:n { @noitemarg }
5745         \__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ] \ignorespaces
5746       }
5747   }
```

(*End of definition for* `\__enumext_start_item_tmp_viii:` *and others.*)

__enumext_starred_item_viii:w
__enumext_starred_item_viii_aux_i:w
__enumext_starred_item_viii_aux_ii:w
__enumext_keyans_starred_item_star:

The function `\__enumext_starred_item_viii:w` together with the specified auxiliary functions `aux_i:w` and `aux_ii:w` execute `\item*` and `\item*[`⟨*content*⟩`]`.

```
\cs_new_protected:Npn \__enumext_starred_item_viii:w
  {
    \bool_set_true:N \l__enumext_item_starred_viii_bool
    \bool_set_true:N \l__enumext_item_wrap_key_bool
    \bool_set_true:N \l__enumext_wrap_label_viii_bool
    \peek_meaning:NTF [
      { \__enumext_starred_item_viii_aux_i:w }
      { \__enumext_starred_item_viii_aux_ii:w }
  }
```

The function `\__enumext_starred_item_viii_aux_i:w` will save the *optional argument* to `\item*` in `\l__enumext_store_current_opt_arg_tl` and will save this argument along with the spacing set by the key `save-sep` in variable `\l__enumext_store_current_label_tl` if present, then call the function `\__enumext_starred_item_viii_aux_ii:w`.

```
\cs_new_protected:Npn \__enumext_starred_item_viii_aux_i:w [#1]
  {
    \tl_clear:N \l__enumext_store_current_label_tl
    \tl_if_novalue:nF {#1}
      {
        \tl_if_empty:NF \l__enumext_store_keyans_item_opt_sep_viii_tl
          {
            \tl_put_right:NV \l__enumext_store_current_label_tl
              \l__enumext_store_keyans_item_opt_sep_viii_tl
            \tl_put_right:Nn \l__enumext_store_current_label_tl {#1}
          }
        \tl_set:Nn \l__enumext_store_current_opt_arg_tl {#1}
      }
    \__enumext_starred_item_viii_aux_ii:w
  }
\cs_new_protected:Npn \__enumext_starred_item_viii_aux_ii:w
  {
    \legacy_if_set_true:n { @noitemarg }
    \__enumext_start_item_viii:w [ \l__enumext_label_viii_tl ] \ignorespaces
  }
```

The function `\__enumext_keyans_starred_item_star:` will be in charge of storing the current ⟨*label*⟩ for `\item*` followed by the `[`⟨*content*⟩`]` for `\item*[`⟨*content*⟩`]` if present in the *sequence* and *prop list* set by the `save-ans` key. In this same function the keys `show-ans`, `show-pos`, `mark-sep` and `save-ref` are implemented.

```
\cs_new_protected:Nn \__enumext_keyans_starred_item_star:
  {
    \tl_put_left:Ne \l__enumext_store_current_label_tl { \l__enumext_label_viii_tl }
    \__enumext_store_addto_prop:V \l__enumext_store_current_label_tl
    \__enumext_keyans_store_ref:
    \tl_put_left:Nn \l__enumext_store_current_label_tl { \item }
    \__enumext_keyans_addto_seq_link:
    \int_gincr:N \g__enumext_check_starred_cmd_int
    \dim_compare:nNnT { \l__enumext_mark_sym_sep_viii_dim } = { \c_zero_dim }
      {
        \dim_set:Nn \l__enumext_mark_sym_sep_viii_dim { \l__enumext_labelsep_viii_dim }
      }
    \bool_if:NT \l__enumext_show_answer_bool
      {
        \tl_set_eq:NN \l__enumext_mark_answer_sym_tl \l__enumext_mark_answer_sym_viii_tl
        \str_set_eq:NN \l__enumext_mark_position_str \l__enumext_mark_position_viii_str
        \__enumext_print_keyans_box:NN
          \l__enumext_labelwidth_viii_dim \l__enumext_mark_sym_sep_viii_dim
      }
    \bool_if:NT \l__enumext_show_position_bool
      {
        \tl_set:Ne \l__enumext_mark_answer_sym_tl
          {
            \group_begin:
              \exp_not:N \normalfont
              \exp_not:N \footnotesize [ \int_eval:n
                {
                  \prop_count:c { g__enumext_ \l__enumext_store_name_tl _prop }
                }
```

```
                ]
              \group_end:
            }
          \str_set_eq:NN \l__enumext_mark_position_str \l__enumext_mark_position_viii_str
          \__enumext_print_keyans_box:NN
            \l__enumext_labelwidth_viii_dim \l__enumext_mark_sym_sep_viii_dim
        }
    }
```

(*End of definition for* `\__enumext_starred_item_viii:w` *and others.*)

`\__enumext_keyans_wrapper_label_viii:n`
`\__enumext_fake_make_label_viii:n`
`\__enumext_wrapper_label_viii:n`

The implementation at this point is very similar to that of the `enumext*` environment.

```
\cs_new_protected:Nn \__enumext_keyans_wrapper_label_viii:n
  {
    \bool_lazy_all:nT
      {
        { \bool_if_p:N \l__enumext_wrap_label_viii_bool         }
        { \bool_if_p:N \l__enumext_show_answer_bool             }
        { \bool_if_p:N \l__enumext_item_wrap_key_bool           }
        { \cs_if_exist_p:N \__enumext_keyans_wrapper_item_viii:n }
      }
      {
        \cs_set_eq:NN
          \__enumext_wrapper_label_viii:n \__enumext_keyans_wrapper_item_viii:n
      }
    \bool_if:NTF \l__enumext_wrap_label_viii_bool
      {
        \__enumext_wrapper_label_viii:n {#1}
      }
      {#1}
  }
\cs_new_protected_nopar:Nn \__enumext_fake_make_label_viii:n
  {
    \legacy_if:nT { @noitemarg }
      {
        \legacy_if_set_false:n { @noitemarg }
        \legacy_if:nT { @nmbrlist }
          {
            \refstepcounter{enumXviii}
          }
      }
    \bool_if:NT \l__enumext_item_starred_viii_bool
      {
        \__enumext_keyans_starred_item_star:
      }
    \makebox[ \l__enumext_labelwidth_viii_dim ][ \l__enumext_align_label_viii_str ]
      {
        \tl_use:N \l__enumext_label_font_style_viii_tl
        \__enumext_keyans_wrapper_label_viii:n {#1}
      }
    \skip_horizontal:N \l__enumext_labelsep_viii_dim \ignorespaces
  }
```

(*End of definition for* `\__enumext_keyans_wrapper_label_viii:n`*,* `\__enumext_fake_make_label_viii:n`*, and* `\__enumext_wrapper_label_viii:n`*.*)

13.48.2 Real definition of `\item` in keyans*

`\__enumext_start_item_viii:w`
`\__enumext_stop_item_viii:`

The implementation at this point is very similar to that of the `enumext*` environment.

```
\cs_new_protected_nopar:Npn \__enumext_start_item_viii:w [#1]
  {
    \cs_set_eq:NN \__enumext_stop_item_tmp_viii: \__enumext_stop_item_viii:
    \hbox_set_to_wd:Nnw \l__enumext_item_text_viii_box
      {
        \l__enumext_joined_width_viii_dim
        + \l__enumext_labelwidth_viii_dim
        + \l__enumext_labelsep_viii_dim
      }
      \__enumext_renew_footnote_starred:
      \__enumext_start_list_tag:n {keyans*}
      \__enumext_fake_make_label_viii:n {#1}
```

```
      \__enumext_stop_start_list_tag:
      \__enumext_minipage:w [ t ]{ \l__enumext_joined_width_viii_dim  }
        \dim_set_eq:NN \parindent \l__enumext_listparindent_viii_dim
        \skip_set_eq:NN \parskip \l__enumext_parsep_viii_skip
        \__enumext_unskip_unkern:
        \__enumext_unskip_unkern:
        \skip_horizontal:n { -\l__enumext_listparindent_viii_dim } \ignorespaces
        \tl_use:N \l__enumext_fake_item_indent_viii_tl
        \bool_if:NT \l__enumext_item_starred_viii_bool
          {
            \__enumext_keyans_show_item_opt_viii:
          }
        \tl_use:N \l__enumext_after_list_args_viii_tl
  }
\cs_new_protected_nopar:Nn \__enumext_stop_item_viii:
  {
      \__enumext_endminipage:
    \__enumext_stop_list_tag:n {keyans*}
    \hbox_set_end:
    \int_set:Nn \hbadness { 10000 }
    \box_use_drop:N \l__enumext_item_text_viii_box
    \int_compare:nNnTF
      { \l__enumext_item_column_pos_viii_int } = { \l__enumext_columns_viii_int }
      {
        \par\noindent
        \int_zero:N \l__enumext_item_column_pos_viii_int
      }
      {
        \skip_horizontal:N \l__enumext_columns_sep_viii_dim
      }
  }
```

(*End of definition for* `\__enumext_start_item_viii:w` *and* `\__enumext_stop_item_viii:`.)

`\__enumext_remove_extra_parsep_viii:`

The implementation at this point is very similar to that of the `enumext*` environment.

```
\cs_new_protected:Nn \__enumext_remove_extra_parsep_viii:
  {
    \int_compare:nNnT
      {
        \int_mod:nn
          { \g__enumext_item_count_all_viii_int }
          { \l__enumext_columns_viii_int }
      }
      =
      { 0 }
      {
        \para_end:
        \skip_vertical:n { -\l__enumext_itemsep_viii_skip }
        \skip_vertical:N \c_zero_skip
        \int_gzero:N \g__enumext_item_count_all_viii_int
      }
  }
```

(*End of definition for* `\__enumext_remove_extra_parsep_viii:`.)

13.49 The command \getkeyans

13.49.1 Definition of error messages for \getkeyans

`missing-colon`

Message used by `\getkeyans` command.

```
\msg_new:nnnn { enumext } { missing-colon }
  {
    The~argument~'#1'~has~no~colon~\msg_line_context:.
  }
  {
    The~argument~of~'\token_to_str:N \getkeyans'~must~have~the~form~
    'store~name:position'.
  }
```

(*End of definition for* `missing-colon`.)

13.49.2 Internal functions for \getkeyans

__enumext_getkeyans_aux:n
__enumext_getkeyans:nn

The internal function __enumext_getkeyans_aux:n is in charge of *splitting* the *mandatory argument* using ":". If ":" is omitted it will return an error.

```
\cs_new_protected:Nn \__enumext_getkeyans_aux:n
  {
    \str_if_in:nnTF {#1} { : }
      {
        \use:e
          {
            \cs_set:Npn \exp_not:N \__enumext_tmp:w ##1 \c_colon_str ##2 \scan_stop:
              { {##1} {##2} }
          }
        \exp_after:w \__enumext_getkeyans:nn \__enumext_tmp:w #1 \scan_stop:
      }
      { \msg_error:nnn { enumext } { missing-colon } {#1} }
  }
```

The internal function __enumext_getkeyans:nn will check for the existence of the *prop list*, if it does not exist it will return an error message, then it will fetch the content specified by the *second argument* from *prop list*.

```
\cs_new_protected:Nn \__enumext_getkeyans:nn
  {
    \prop_if_exist:cTF { g__enumext_#1_prop }
      {
        \prop_item:cn { g__enumext_#1_prop }{#2}
      }
      {
        \msg_error:nnn { enumext } { undefined-storage-anskey } {#1}
      }
  }
```

(*End of definition for* __enumext_getkeyans_aux:n *and* __enumext_getkeyans:nn.)

\getkeyans

The \getkeyans command takes a *mandatory argument* of the form {⟨*store name* : *position*⟩}. Retrieve a *"single content"* stored by \anskey, \anspic* and \item* and anskey* from *prop list* defined by save-ans key.

```
\NewDocumentCommand \getkeyans { m }
  {
    \exp_args:Ne \__enumext_getkeyans_aux:n
      { \tl_to_str:e { \text_expand:n {#1} } }
  }
```

(*End of definition for* \getkeyans. *This function is documented on page* 20.)

13.50 The command \printkeyans

The \printkeyans command prints *"all stored content"* in the *sequence* defined by the save-ans key.

print*
print-*
print-1
print-2
print-3
print-4

First a set of ⟨*filtered keys*⟩ is defined, with which the options of the different nesting levels are controlled for the environments enumext and enumext* by storing their values in the list of tokens \l__enumext_print_keyans_X_tl.

The variable \l__enumext_print_keyans_starred_tl will have the default ⟨*keys*⟩ for \printkeyans* and will be set by \setenumext[⟨*print**⟩] and the variable \l__enumext_print_keyans_vii_tl will have the default keys for the environment enumext* nested within the *sequence* and will be set by \setenumext[⟨*print* ,*⟩], the rest of the variables will be for the environment enumext and will be set by \setenumext[⟨*print* , *level*⟩].

```
\keys_define:nn  { enumext / print }
  {
    print*  .code:n =
      {
        \keys_precompile:neN { enumext / enumext* }
          { \__enumext_filter_save_key:n {#1} }
          \l__enumext_print_keyans_starred_tl
      }, % starred cmd
    print*  .initial:n =
      { labelwidth=0pt, labelsep=0.3333em, itemindent=0pt, list-offset=0pt,
                        rightmargin=0pt, listparindent=0pt, nosep,
                          label=\arabic*.,
```

©2024–2026 by Pablo González L

```
                          columns=2, first=\small, font=\small },
    print-1 .code:n =
      {
        \keys_precompile:neN { enumext / level-1 }
          { \__enumext_filter_save_key:n {#1} }
          \l__enumext_print_keyans_i_tl
      },
    print-1 .initial:n =
      { labelwidth=0pt, labelsep=0.3333em, itemindent=0pt, list-offset=0pt,
                          rightmargin=0pt, listparindent=0pt, nosep,
                            label=\arabic*.,
                          columns=2, first=\small, font=\small },
    print-2 .code:n =
      {
        \keys_precompile:neN { enumext / level-2 }
          { \__enumext_filter_save_key:n {#1} }
          \l__enumext_print_keyans_ii_tl
      },
    print-2 .initial:n =
      { labelwidth=0pt, labelsep=0.3333em, itemindent=0pt, list-offset=0pt,
                          rightmargin=0pt, listparindent=0pt,  nosep,
                            label=(\alph*),
                          first=\small, font=\small },
    print-3 .code:n =
      {
        \keys_precompile:neN { enumext / level-3 }
          { \__enumext_filter_save_key:n {#1} }
          \l__enumext_print_keyans_iii_tl
      },
    print-3 .initial:n =
      { labelwidth=0pt, labelsep=0.3333em, itemindent=0pt, list-offset=0pt,
                          rightmargin=0pt, listparindent=0pt, nosep,
                            label=\roman*.,
                          first=\small, font=\small },
    print-4 .code:n =
      {
        \keys_precompile:neN { enumext / level-4 }
          { \__enumext_filter_save_key:n {#1} }
          \l__enumext_print_keyans_iv_tl
      },
    print-4 .initial:n =
      { labelwidth=0pt, labelsep=0.3333em, itemindent=0pt, list-offset=0pt,
                          rightmargin=0pt, listparindent=0pt, nosep,
                            label=\Alph*.,
                          first=\small, font=\small },
    print-* .code:n =
      {
        \keys_precompile:neN { enumext / enumext* }
          { \__enumext_filter_save_key:n {#1} }
          \l__enumext_print_keyans_vii_tl
      }, % starred nested
    print-* .initial:n =
      { labelwidth=0pt, labelsep=0.3333em, itemindent=0pt, list-offset=0pt,
                          rightmargin=0pt, listparindent=0pt, nosep,
                            label=\arabic*.,
                          first=\small, font=\small },
  }
```

(*End of definition for* `print*` *and others.*)

The reason for storing ⟨*keys*⟩ in token lists using `\keys_precompile:neN` is because the keys are set via `\setenumext` but are later executed by running the command `\printkeyans` and they are not handled directly by its *optional argument*, except those related to the *first* opening level.

13.50.1 Definition of error messages for `\printkeyans`

print-starred Messages used by `\printkeyans*` command.

```
\msg_new:nnn { enumext } { print-starred }
  {
    \c_backslash_str printkeyans*:~The~sequence~'#1'~already~contains~
    #2~environment~\msg_line_context:.
  }
```

(*End of definition for* `print-starred`.)

13.50.2 Internal functions for `\printkeyans`

`\__enumext_printkeyans:nnn`

The internal function `\__enumext_printkeyans:nnn` will check for the existence of the *sequence*, if it does not exist it will return an error message, then it will check if not empty.

```
\cs_new_protected:Nn \__enumext_printkeyans:nnn
  {
    \seq_if_exist:cTF { g__enumext_#3_seq }
      {
        \seq_if_empty:cF { g__enumext_#3_seq }
          {
```

If the *starred argument* '`*`' is present, it checks that the environment `enumext*` is not saved in the *sequence*, then executes the variable `\l__enumext_print_keyans_starred_tl` that contains the default ⟨*keys*⟩ for the environment `enumext*`, sets `\l__enumext_base_line_fix_bool` and `\l__enumext_print_keyans_star_bool` to true for *baseline correction*, opens the `enumext*` environment passing the *optional argument* and maps the *sequence*, then sets `\l__enumext_base_line_fix_bool` and `\l__enumext_print_keyans_star_bool` to false.

```
            \bool_if:nTF {#1}
              {
                \seq_if_in:cnTF { g__enumext_#3_seq } { \end{enumext*} }
                  {
                    \msg_error:nnnn { enumext } { print-starred } {#3}
                      { enumext* }
                  }
                  {
                    \tl_use:N \l__enumext_print_keyans_starred_tl
                    \bool_set_true:N \l__enumext_base_line_fix_bool
                    \bool_set_true:N \l__enumext_print_keyans_star_bool
                    \begin{enumext*}[#2]
                      \seq_map_inline:cn { g__enumext_#3_seq } {##1}
                    \end{enumext*}
                    \bool_set_false:N \l__enumext_base_line_fix_bool
                    \bool_set_false:N \l__enumext_print_keyans_star_bool
                  }
              }
```

Otherwise it will open the environment `enumext` passing the *optional argument* to the *"first level"* then map the *sequence*.

```
              {
                \begin{enumext}[#2]
                  \seq_map_inline:cn { g__enumext_#3_seq } {##1}
                \end{enumext}
              }
          }
      }
      {
        \msg_error:nnn { enumext } { undefined-storage-anskey } {#3}
      }
  }
```

(*End of definition for* `\__enumext_printkeyans:nnn`.)

`\printkeyans`

Create a user command to print *"all stored content"* in *sequence* for `\anskey`, `anskey*`, `\item*` and `\anspic*`. Within a group the *"precompiled keys"* are run and then the internal function `\__enumext_printkeyans:nnn` is called.

```
\NewDocumentCommand \printkeyans { s O{} m }
  {
    \group_begin:
      \bool_set_true:N \l__enumext_print_keyans_cmd_bool
      \tl_use:N \l__enumext_print_keyans_i_tl
      \tl_use:N \l__enumext_print_keyans_ii_tl
      \tl_use:N \l__enumext_print_keyans_iii_tl
      \tl_use:N \l__enumext_print_keyans_iv_tl
      \tl_use:N \l__enumext_print_keyans_vii_tl
      \__enumext_printkeyans:nnn {#1} {#2} {#3}
      \bool_set_false:N \l__enumext_print_keyans_cmd_bool
    \group_end:
  }
```

(*End of definition for* `\printkeyans`. *This function is documented on page* 20.)

©2024–2026 by Pablo González L

13.51 The command \setenumext

The command \setenumext is in charge of managing the ⟨*keys*⟩ passed to all environments and to the \printkeyans command. Precautions must be taken with the enumext* and enumext environments so as not to capture ⟨*keys*⟩ that cause problems.

__enumext_filter_level:n
__enumext_filter_level_key:n
__enumext_filter_level_pair:nn

The function __enumext_filter_level:n will be in charge of filtering the ⟨*keys*⟩ passed to the enumext and enumext* environments.

```
\cs_new:Nn \__enumext_filter_level:n
  {
    \use:e
      {
        \keyval_parse:NNn
          \__enumext_filter_level_key:n
          \__enumext_filter_level_pair:nn {#1}
      }
  }
```

The function __enumext_filter_level_key:n will be responsible for filtering the ⟨*keys*⟩ that are passed *"without value"* by excluding the keys resume*, reset and reset* passed to the enumext and enumext* environments.

```
\cs_new:Nn \__enumext_filter_level_key:n
  {
    \str_case:nnF {#1}
      {
        { resume* } {} { reset } {} { reset* } {}
      }
      { , { \exp_not:n {#1} } }
  }
```

The function __enumext_filter_level_pair:nn will be responsible for filtering the ⟨*keys*⟩ that are passed *"with value"* by excluding the series, resume and save-ans keys passed to the enumext and enumext* environments.

```
\cs_new:Nn \__enumext_filter_level_pair:nn
  {
    \str_case:nnF {#1}
      {
        { series } {}  { save-ans } {} { resume } {}
      }
      { , { \exp_not:n {#1} } = { \exp_not:n {#2} } }
  }
```

(*End of definition for* __enumext_filter_level:n, __enumext_filter_level_key:n, *and* __enumext_filter_level_pair:nn.)

enumext-1
enumext-2
enumext-3
enumext-4
enumext*
keyans
keyans*
print*
print-1
print-2
print-3
print-4
print-*
unknown

Now define a *"meta families"* of ⟨*keys*⟩ to access from \setenumext.

```
\keys_define:nn { enumext / meta-families }
  {
    enumext-1 .code:n =
      {
        \keys_set:ne { enumext / level-1 }
          {
            \__enumext_filter_level:n {#1}
          }
      },
    enumext-2 .code:n =
      {
        \keys_set:ne { enumext / level-2 }
          {
            \__enumext_filter_level:n {#1}
          }
      },
    enumext-3 .code:n =
      {
        \keys_set:ne { enumext / level-3 }
          {
            \__enumext_filter_level:n {#1}
          }
      },
    enumext-4 .code:n =
```

©2024–2026 by Pablo González L

```
      {
        \keys_set:ne { enumext / level-4 }
          {
            \__enumext_filter_level:n {#1}
          }
      },
    enumext*  .code:n =
      {
        \keys_set:ne { enumext / enumext* }
         {
           \__enumext_filter_level:n {#1}
         }
      },
    keyans    .meta:nn = { enumext / keyans } {#1},
    keyans*   .meta:nn = { enumext / keyans* } {#1},
    print*    .meta:nn = { enumext / print } { print* = {#1} },
    print-1   .meta:nn = { enumext / print } { print-1 = {#1} },
    print-2   .meta:nn = { enumext / print } { print-2 = {#1} },
    print-3   .meta:nn = { enumext / print } { print-3 = {#1} },
    print-4   .meta:nn = { enumext / print } { print-4 = {#1} },
    print-*   .meta:nn = { enumext / print } { print-* = {#1} },
    unknown   .code:n = { \msg_error:nn { enumext } { unknown-key-family } },
  }
```

(*End of definition for* `enumext-1` *and others.*)

`\c__enumext_all_families_seq` They are stored in the constant sequence `\c__enumext_all_families_seq` separated by commas.

```
\seq_const_from_clist:Nn \c__enumext_all_families_seq
  {
    enumext-1, enumext-2, enumext-3, enumext-4, keyans, enumext*,
    keyans*, print-1, print-2, print-3, print-4, print-*, print*,
  }
```

(*End of definition for* `\c__enumext_all_families_seq`.)

`\__enumext_set_parse:n` `\__enumext_set_error:nn` Internal functions used by the `\setenumext` command.

```
\cs_new_protected:Nn \__enumext_set_parse:n
  {
    \tl_set:Ne \l__enumext_setkey_tmpb_tl { \tl_trim_spaces:n {#1} }
    \clist_map_inline:nn { 0, 1, 2, 3, 4, * } % <- max level
      { \tl_remove_all:Nn \l__enumext_setkey_tmpb_tl {##1} }
    \tl_if_empty:NTF \l__enumext_setkey_tmpb_tl
      {
        \seq_put_right:Ne \l__enumext_setkey_tmpa_seq
          { \tl_trim_spaces:n {#1} }
      }
      { \__enumext_set_error:nn {#1} { } }
  }
\cs_new_protected:Nn \__enumext_set_error:nn
  { \msg_error:nnnn { enumext } { invalid-key } {#1} {#2} }
```

(*End of definition for* `\__enumext_set_parse:n` *and* `\__enumext_set_error:nn`.)

`\setenumext` Defines the user command `\setenumext`.

```
\NewDocumentCommand \setenumext { O{enumext,1} +m }
  {
    \seq_clear:N \l__enumext_setkey_tmpa_seq
    \seq_set_from_clist:Nn \l__enumext_setkey_tmpb_seq {#1}
    \int_set:Nn \l__enumext_setkey_tmpa_int
      {
        \seq_count:N \l__enumext_setkey_tmpb_seq
      }
    \int_compare:nNnTF { \l__enumext_setkey_tmpa_int } > { 1 }
      {
        \seq_pop_left:NN \l__enumext_setkey_tmpb_seq \l__enumext_setkey_tmpa_tl
        \seq_map_function:NN \l__enumext_setkey_tmpb_seq \__enumext_set_parse:n
        \seq_set_map_e:NNn \l__enumext_setkey_tmpa_seq \l__enumext_setkey_tmpa_seq
          {
            \tl_use:N \l__enumext_setkey_tmpa_tl - ##1
          }
```

```
      }
      {
        \seq_put_right:Ne \l__enumext_setkey_tmpa_seq { \tl_trim_spaces:n {#1} }
      }
    \seq_if_empty:NTF \l__enumext_setkey_tmpa_seq
      { \seq_map_inline:Nn \c__enumext_all_families_seq }
      { \seq_map_inline:Nn \l__enumext_setkey_tmpa_seq }
      {
        \keys_set:nn { enumext / meta-families } { ##1 = {#2} }
      }
  }
```

(*End of definition for* `\setenumext`. *This function is documented on page* 6.)

13.51.1 Definition of error messages for `\setenumext`

invalid-key
unknown-key-family

Message used by [⟨*key* = *val*⟩] system and `\setenumext` command.

```
\msg_new:nnn { enumext } { invalid-key }
  {
    The~key~'#1'~is~not~known~at~level~#2~\msg_line_context:.
  }
\msg_new:nnn { enumext } { unknown-key-family }
  {
    Unknown~key~family~'\l_keys_key_str'~for~enumext~\msg_line_context:.
  }
```

(*End of definition for* `invalid-key` *and* `unknown-key-family`.)

13.52 The command `\setenumextmeta`

The command `\setenumextmeta` will be responsible for adding new *"meta-keys"* for the `enumext` and `enumext*` environments. The implementation code was given by Jonathan P. Spratte (`@Skillmon`) answer in Simplify syntax for command that adds `.meta` key to existing keys (l3keys).

13.52.1 Definition of error messages for `\setenumextmeta`

already-defined
prohibited-unknown

Messages used by `\setenumextmeta` command.

```
\msg_new:nnn { enumext } { already-defined }
  {
    The~key~'#1'~is~already~defined~\msg_line_context:.
  }
\msg_new:nnn { enumext } { prohibited-unknown }
  {
    The~name~'unknown'~can't~be~chosen~for~a~meta~key~\msg_line_context:.
  }
```

(*End of definition for* `already-defined` *and* `prohibited-unknown`.)

13.52.2 Internal functions for `\setenumextmeta`

__enumext_key_set_meta:nnn
__enumext_key_def_meta:nnn
__enumext_key_def_meta:Vnn

First, ⟨*keys*⟩ of type `.code:n` are created for *"all levels"* of the `enumext` environment.

```
\int_step_inline:nn { 4 }
  {
    \keys_define:nn { enumext }
      {
         #1 .code:n = { \str_set:Nn \l__enumext_meta_path_str { level-#1 } }
        ,#1 .value_forbidden:n = true
      }
  }
```

And now the ⟨*keys*⟩ are defined for the environments using `.code:n` for the `enumext` environment and `.meta:n` for the `enumext*` environment.

```
\clist_map_inline:nn { enumext }
  {
    \keys_define:nn { enumext }
      {
         #1  .code:n = { } % ignored for now, might do something useful in the future
        ,#1  .value_forbidden:n = true
        ,#1* .code:n = { \str_set:Nn \l__enumext_meta_path_str { #1* } }
        ,#1* .value_forbidden:n = true
      }
```

```
  }
\keys_define:nn { enumext }
  {
     * .meta:n = enumext*
    ,* .value_forbidden:n = true
  }
```

The internal functions `\__enumext_key_set_meta:nnn` and `\__enumext_key_def_meta:nnn` will check the *optional argument* and create the *"meta-key"*.

```
\cs_new_protected:Npn \__enumext_key_set_meta:nnn #1
  {
    \keys_set:nn { enumext } {#1}
    \__enumext_key_def_meta:Vnn \l__enumext_meta_path_str
  }
\cs_new_protected:Nn \__enumext_key_def_meta:nnn
  {
    \bool_lazy_or:nnTF
      { \keys_if_exist_p:nn { enumext / #1} {#2} }
      { \keys_if_exist_p:nn { enumext / enumext* } {#2} }
      { \msg_error:nnn { enumext } { already-defined } {#2} }
      {
        \keys_define:nn { enumext / #1 }
          {
            #2 .meta:n = {#3},
            #2 .value_forbidden:n = true
          }
      }
  }
\cs_generate_variant:Nn \__enumext_key_def_meta:nnn { V }
```

(*End of definition for* `\__enumext_key_set_meta:nnn` *and* `\__enumext_key_def_meta:nnn`.)

`\setenumextmeta` Now the user command is created, taking care that unknown cannot be passed as an argument.

```
\NewDocumentCommand \setenumextmeta { s O{enumext,1} m +m }
  {
    \str_if_eq:eeTF { \tl_trim_spaces:n {#3} } { unknown }
      { \msg_error:nn { enumext } { prohibited-unknown } }
      {
        \bool_if:nTF {#1}
          {
            \int_step_inline:nn { 4 }
              { \__enumext_key_set_meta:nnn { enumext, ##1 } {#3} {#4} }
            \__enumext_key_set_meta:nnn { enumext* } {#3} {#4}
          }
          { \__enumext_key_set_meta:nnn {#2} {#3} {#4} }
      }
  }
```

(*End of definition for* `\setenumextmeta`. *This function is documented on page* 6.)

13.53 The command `\foreachkeyans`

The command `\foreachkeyans` will execute a *loop* over the *prop list* and return its contents. The implementation code is adapted from the answer provided by Enrico Gregorio (`@egreg`) in Expand a `.cs` defined by key inside the function.

13.53.1 Definition of error messages for `\foreachkeyans`

`for-key-unknown` Message used by unknown ⟨*keys*⟩ in `\foreachkeyans`.

`for-key-value-unknown`

```
\msg_new:nnnn { enumext } { for-key-unknown }
  {
    The~key~'#1'~is~unknown~by~'\c_backslash_str foreachkeyans'~and~is~being~
    ignored~\msg_line_context:.
  }
  {
    The~command~'\c_backslash_str foreachkeyans'~does~not~have~a~key~called~
    '#1'.\\
    Check~that~you~have~spelled~the~key~name~correctly.
  }
\msg_new:nnnn { enumext } { for-key-value-unknown }
  {
```

```
    The~key~'#1=#2'~is~unknown~by~'\c_backslash_str foreachkeyans'~and~is~
    being~ignored~\msg_line_context:.
  }
  {
    The~command~'\c_backslash_str foreachkeyans'~does~not~have~a~key~called~
    '#1'.\\
    Check~that~you~have~spelled~the~key~name~correctly.
  }
```

(*End of definition for* `for-key-unknown` *and* `for-key-value-unknown`.)

13.53.2 Internal functions for `\foreachkeyans`

`\__enumext_parse_foreach_keys:nn`
`\__enumext_parse_foreach_keys:n`
`\__enumext_foreach_keyans:nn`
`\__enumext_foreach_add_body:n`
`before`
`after`
`sep`
`start`
`step`
`stop`
`wrapper`
`unknown`

A set of ⟨*keys*⟩ is defined for the command and the default values of these are saved in `\g__enumext_foreach_default_keys_tl` to avoid the use of a group.

```
\keys_define:nn { enumext / foreach }
  {
    before  .tl_set:N = \l__enumext_foreach_before_tl,
    before  .value_required:n = true,
    after   .tl_set:N = \l__enumext_foreach_after_tl,
    after   .value_required:n = true,
    start   .int_set:N = \l__enumext_foreach_start_int,
    start   .value_required:n = true,
    stop    .int_set:N = \l__enumext_foreach_stop_int,
    stop    .value_required:n = true,
    step    .int_set:N = \l__enumext_foreach_step_int,
    step    .value_required:n = true,
    wrapper .cs_set_protected:Np = \__enumext_foreach_wrapper:n #1,
    wrapper .value_required:n = true,
    sep     .tl_set:N = \l__enumext_foreach_sep_tl,
    sep     .value_required:n = true,
    unknown .code:n = { \__enumext_parse_foreach_keys:n {#1} }
  }
\keys_precompile:nnN { enumext / foreach }
  {
    before={},after={},start=1,step=1,stop=0,wrapper=#1,sep={; }
  }
  \l__enumext_foreach_default_keys_tl
```

Functions for handling unknown ⟨*keys*⟩.

```
\cs_new_protected:Nn \__enumext_parse_foreach_keys:nn
  {
    \tl_if_blank:nTF {#2}
      {
        \msg_error:nnn { enumext } { for-key-unknown } {#1}
      }
      {
        \msg_error:nnnn { enumext } { for-key-value-unknown } {#1} {#2}
      }
  }
\cs_new_protected:Nn \__enumext_parse_foreach_keys:n
  {
    \exp_args:NV \__enumext_parse_foreach_keys:nn \l_keys_key_str {#1}
  }
```

Finally the internal functions `\__enumext_foreach_keyans:nn` and `\__enumext_foreach_add_body:n` will loop through the prop list and print the contents.

```
\cs_new_protected:Nn \__enumext_foreach_keyans:nn
  {
    \tl_use:N \l__enumext_foreach_default_keys_tl
    \keys_set:nn { enumext / foreach } {#1}
    \tl_set:Nn \l__enumext_foreach_name_prop_tl {#2}
    \prop_if_exist:cF { g__enumext_#2_prop }
      {
        \msg_error:nnn { enumext } { undefined-storage-anskey } {#2}
      }
    \int_compare:nNnT { \l__enumext_foreach_stop_int } = { 0 }
      {
        \int_set:Nn \l__enumext_foreach_stop_int
          { \prop_count:c { g__enumext_#2_prop } }
      }
```

```
    \seq_clear:N \l__enumext_foreach_print_seq
    \int_step_function:nnnN
      { \l__enumext_foreach_start_int }
      { \l__enumext_foreach_step_int }
      { \l__enumext_foreach_stop_int }
      \__enumext_foreach_add_body:n
      \seq_use:NV \l__enumext_foreach_print_seq \l__enumext_foreach_sep_tl
  }
\cs_new_protected:Nn \__enumext_foreach_add_body:n
  {
    \seq_put_right:Ne \l__enumext_foreach_print_seq
      {
        \exp_not:V \l__enumext_foreach_before_tl
        \__enumext_foreach_wrapper:n
          {
            \prop_item:cn { g__enumext_ \l__enumext_foreach_name_prop_tl _prop }{#1}
          }
        \exp_not:V \l__enumext_foreach_after_tl
      }
  }
```

(*End of definition for* `\__enumext_parse_foreach_keys:nn` *and others.*)

`\foreachkeyans` The command is created.

```
\NewDocumentCommand \foreachkeyans { +O{} m }
  {
    \__enumext_foreach_keyans:nn {#1} {#2}
  }
```

(*End of definition for* `\foreachkeyans`. *This function is documented on page* 20.)

13.54 General messages

Messages shared by several sections of the implementation; the messages used by only one command, key or environment are defined in its own section.

`package-load` `package-not-load` Message used by package-load for `multicol` and `hyperref` packages.

```
\msg_new:nnn { enumext } { package-load }
  {
    The~'#1'~package~is~already~loaded.
  }
\msg_new:nnn { enumext } { package-not-load }
  {
    The~'#1'~package~will~be~loaded~as~a~dependency.
  }
```

(*End of definition for* `package-load` *and* `package-not-load`.)

`unknown-choice` Message used by `align`, `mark-pos` and `label-pos` keys.

```
\msg_new:nnn { enumext } { unknown-choice }
  {
    Invalid~value~'#3'~for~key~'#1';~use~one~of:~#2~\msg_line_context:.
  }
```

(*End of definition for* `unknown-choice`.)

`command-wrong-place` Message used by `\anskey` and `\anspic` commands when they are used in the wrong place.

```
\msg_new:nnn { enumext } { command-wrong-place }
  {
    Wrong~place~for~command~'\c_backslash_str #1'~\msg_line_context:.\\
    '\c_backslash_str #1'~works~outside~the~environment~'#2'.
  }
```

(*End of definition for* `command-wrong-place`.)

`undefined-storage-anskey` Message used by `\getkeyans`, `\printkeyans` and `\foreachkeyans` commands when the storage is not defined.

```
\msg_new:nnn { enumext } { undefined-storage-anskey }
  {
    Storage~named~'#1'~is~not~defined~\msg_line_context:.
  }
```

©2024–2026 by Pablo González L

(*End of definition for* `undefined-storage-anskey`.)

`missing-miniright` Message used by `enumext` and `keyans` when the key `mini-env` needs `\miniright`.

```
\msg_new:nnn { enumext } { missing-miniright }
  {
    Missing~'\c_backslash_str miniright'~\msg_line_context:.\\
    The~key~'mini-env'~needs~'\c_backslash_str miniright'.
  }
```

(*End of definition for* `missing-miniright`.)

`nested` Message used when an environment is nested in itself.

```
\msg_new:nnn { enumext } { nested }
  {
    The~environment~\l__enumext_envir_name_tl \c_space_tl can't~be~nested~
    \msg_line_context:.
  }
```

(*End of definition for* `nested`.)

13.55 Finish package

Finish package implementation.

```
\file_input_stop:
⟨/package⟩
```

©2024–2026 by Pablo González L

14 Index of Implementation

The italic numbers denote the pages where the corresponding entry is described, the numbers underlined and all others indicate the line on which they are implemented in the package code.

A

above 1801
above* 1801
after 1172, 6283
align 690
already-defined 6198
\anskey *15*, *94*, *96*, 3240
anskey* *16*, 3401
anskey-cmd-key-unknown 3261
anskey-cmd-key-value-unknown 3261
anskey-empty-arg 3198
anskey-env-error 3420
anskey-env-key-unknown 3429
anskey-env-key-value-unknown 3429
anskey-env-wrong 3429
anskey-math-mode 3198
anskey-nested 3261
anskey-unnumber-item 3198
anskey-wrong-place 3261
\anspic *19*, *127*, *130*, 5025
\anspic* *87*

B

base-fix 1028
before 1172, 6283
before* 1172
beginpenalty 970
below 1801
below* 1801
break-col 3210, 3325

C

c@ internal commands:
\c@__enumext_resume_i_int 611
\c@__enumext_resume_ii_int 611
\c@__enumext_resume_iii_int 611
\c@__enumext_resume_iv_int 611
\c@__enumext_resume_vii_int 611
check-ans 2560
Document class :
article *54*
l3doc *32*
columns 1243
columns-sep 1243
command-wrong-place 6370
Commands provided by enumext:
\anskey *35*
\anspic* *35*
\anspic *36*
\foreachkeyans *157*
\getkeyans *151*
\item* *35*
\item *107*
\miniright *34*
\printkeyans* *151*
\printkeyans *35*
\resetenumext *79*
\setenumextmeta *156*
\setenumext *155*
Counters defined by enumext:
enumXiii *33*
enumXii *33*
enumXiv *33*
enumXi *33*
enumXviii *33*
enumXvii *33*
enumXvi *33*
enumXv *33*
counters 620

E

endpenalty 970
enumext *5*, 4479
enumext internal commands:
__enumext_add_pre_parsep: 1287
__enumext_after_args_exec: 1187
__enumext_after_args_exec_v: 1203
__enumext_after_env:nn 214
__enumext_after_hyperref: 396
__enumext_after_list_vii: 5426
__enumext_after_list_viii: 5698
__enumext_after_stop_list: 1187
__enumext_after_stop_list_v: 1203
__enumext_after_stop_list_vii: 1219
__enumext_after_stop_list_viii: 1219
\l__enumext_align_label_pos_X_str 77
\l__enumext_align_label_X_str 184
\c__enumext_all_envs_clist 203
\c__enumext_all_families_seq 6144
__enumext_anskey_env_file_if_-
writable:n 3367
__enumext_anskey_env_file_if_-
writable:nTF 3367
__enumext_anskey_env_file_write:nn . . . 3367
\c__enumext_anskey_env_hidden_space_str 119
__enumext_anskey_env_safe_inner: 3463
__enumext_anskey_env_safe_outer: 3463
__enumext_anskey_env_unknown:n 3353
__enumext_anskey_env_unknown:nn 3353
\l__enumext_anskey_level_int 25
__enumext_anskey_safe_inner: 3288
__enumext_anskey_safe_outer: 3288
__enumext_anskey_show_wrap_arg:n 3151
__enumext_anskey_show_wrap_left:n . . . 3176
__enumext_anskey_unknown:n 3210
__enumext_anskey_unknown:nn 3210
\l__enumext_anspic_above_int 149
__enumext_anspic_args:nnn 4896
\l__enumext_anspic_args_seq 149
\l__enumext_anspic_below_int 149
\l__enumext_anspic_body_box 149
__enumext_anspic_body_dim:n 4896
\l__enumext_anspic_body_htdp_dim 149
__enumext_anspic_exec: 4896
__enumext_anspic_label:nn 4896

©2024–2026 by Pablo González L

\l__enumext_anspic_label_above_bool ... 149
\l__enumext_anspic_label_box 149
\l__enumext_anspic_label_htdp_dim 149
__enumext_anspic_label_pos:nnn 4896
\l__enumext_anspic_mini_pos_str 149
\l__enumext_anspic_mini_width_dim 149
__enumext_anspic_print:n 4896
__enumext_anspic_row:n 4896
__enumext_anspic_start_list_tag: 4688
__enumext_anspic_stop_list_tag: 4688
__enumext_anspic_stop_start_list_tag: 4688
__enumext_at_begin_document:n 210
__enumext_before_args_exec: 1187
__enumext_before_args_exec_v: 1203
__enumext_before_args_exec_vii: 1219
__enumext_before_args_exec_viii: 1219
__enumext_before_keys_exec: 1187
__enumext_before_keys_exec_v: 1203
__enumext_before_keys_exec_vii: 1219
__enumext_before_keys_exec_viii: 1219
__enumext_before_list: 4418
__enumext_before_list_v: 4530
__enumext_before_list_vii: 5419
__enumext_before_list_viii: 5692
__enumext_calc_hspace:NNNNNNN 4146
__enumext_check_ans_active: 2580
\g__enumext_check_ans_key_bool 159
__enumext_check_ans_key_hook: 2633
__enumext_check_ans_level: 2580
__enumext_check_ans_log: 2680
__enumext_check_ans_log_msg_greater: . 2680
__enumext_check_ans_log_msg_less: ... 2680
__enumext_check_ans_log_msg_same_ok: . 2680
__enumext_check_ans_msg_greater: 2655
__enumext_check_ans_msg_less: 2655
__enumext_check_ans_msg_same_ok: 2655
__enumext_check_ans_show: 2655
\l__enumext_check_answers_bool 159
__enumext_check_starred_cmd:n 2704
\g__enumext_check_starred_cmd_int 159
\l__enumext_check_start_line_env_tl ... 159
\l__enumext_counter_i_tl 41
\l__enumext_counter_ii_tl 41
\l__enumext_counter_iii_tl 41
\l__enumext_counter_iv_tl 41
\g__enumext_counter_styles_tl 65
\l__enumext_counter_v_tl 41
\l__enumext_counter_vi_tl 41
\l__enumext_counter_vii_tl 41
\l__enumext_counter_viii_tl 41
\l__enumext_current_widest_dim 65
__enumext_default_item:n 3767
__enumext_define_counter:Nn 594
__enumext_endminipage: 385
\g__enumext_envir_name_tl 31
\l__enumext_envir_name_tl 31
__enumext_execute_after_env: 3514
__enumext_fake_item_indent: 1110
__enumext_fake_item_indent_vii: 1110
__enumext_fake_item_indent_viii: 1110
\l__enumext_fake_item_indent_X_tl 97
__enumext_fake_make_label_vii:n 5529
__enumext_fake_make_label_viii:n 5814
__enumext_filter_level:n 6072
__enumext_filter_level_key:n 6072
__enumext_filter_level_pair:nn 6072
__enumext_filter_save_key:n 2891
__enumext_filter_save_key_key:n 2891
__enumext_filter_save_key_pair:nn ... 2891
__enumext_filter_series:n 2107
__enumext_filter_series_key:n 2107
__enumext_filter_series_pair:nn 2107
__enumext_first_item_tmp_vii: 5458
__enumext_first_item_tmp_viii: 5704
\g__enumext_footnote_standard_arg_seq . 178
\g__enumext_footnote_standard_int 178
\g__enumext_footnote_standard_int_seq . 178
\g__enumext_footnote_starred_arg_seq .. 178
\g__enumext_footnote_starred_int 178
\g__enumext_footnote_starred_int_seq .. 178
\l__enumext_footnotes_key_bool 168
__enumext_footnotetext:nn 445
__enumext_foreach_add_body:n 6283
\l__enumext_foreach_default_keys_tl ... 127
__enumext_foreach_keyans:nn 6283
\l__enumext_foreach_name_prop_tl 127
\l__enumext_foreach_print_seq 127
__enumext_getkeyans:nn 5922
__enumext_getkeyans_aux:n 5922
\l__enumext_hyperref_bool 168
__enumext_hypertarget:nn 396
__enumext_if_is_int:nTF 222
__enumext_internal_mini_page: 575
__enumext_is_not_nested: 242
__enumext_is_on_first_level: 242
\g__enumext_item_anskey_int 159
__enumext_item_answer_diff: 2648
\g__enumext_item_answer_diff_int 159
l__enumext_item_column_pos_X_int 184
\g__enumext_item_count_all_X_int 184
\l__enumext_item_number_bool 159
\g__enumext_item_number_int 159
__enumext_item_peek_args_vii: 5466
__enumext_item_peek_args_viii: 5712
__enumext_item_starred_exec: 3786
__enumext_item_starred_exec:nn 3786
\l__enumext_item_starred_X_bool 184
__enumext_item_std:w 385
\g__enumext_item_symbol_aux_tl 131
\g__enumext_item_symbol_aux_X_tl 184
\l__enumext_item_text_X_box 184
\l__enumext_item_width_X_dim 184
\l__enumext_item_wrap_key_bool 159
\l__enumext_itemindent_X_dim 69
\l__enumext_joined_item_aux_X_int 184
__enumext_joined_item_vii:w 5466
__enumext_joined_item_viii:w 5712
\l__enumext_joined_item_X_int 184
\l__enumext_joined_width_X_dim 184
__enumext_key_def_meta:nnn 6206
__enumext_key_set_meta:nnn 6206
__enumext_keyans_addto_prop:n 3533
__enumext_keyans_addto_seq:n 3607

©2024–2026 by Pablo González L

__enumext_keyans_addto_seq_link: 3607
__enumext_keyans_default_item:n 4043
\l__enumext_keyans_env_bool 31
__enumext_keyans_fake_item_indent: ... 1110
\l__enumext_keyans_level_h_int 25
\l__enumext_keyans_level_int 25
__enumext_keyans_make_label: 4084
__enumext_keyans_make_label_box: 4084
__enumext_keyans_make_label_std: 4084
__enumext_keyans_mini_right_cmd:n ... 1755
__enumext_keyans_minipage_add_space: . 1550
__enumext_keyans_minipage_set_skip: .. 1550
__enumext_keyans_multi_addvspace: ... 1337
__enumext_keyans_multi_set_vskip: ... 1337
__enumext_keyans_multicols_start: ... 4530
__enumext_keyans_multicols_stop: 4530
__enumext_keyans_name_and_start: 299
__enumext_keyans_parse_keys:n 4526
__enumext_keyans_pic_arg_two: 4792
\l__enumext_keyans_pic_level_int 25
__enumext_keyans_pic_parse_keys:n ... 4792
__enumext_keyans_pic_safe_exec: 4792
__enumext_keyans_pic_skip_abs:N 4792
__enumext_keyans_pos_mark_set: 3683
__enumext_keyans_pre_itemsep_skip: ... 1550
__enumext_keyans_redefine_item: 4066
__enumext_keyans_ref: 883
__enumext_keyans_ref:n 883
__enumext_keyans_safe_exec: 4506
__enumext_keyans_save_item_opt:n 3650
__enumext_keyans_set_item_width: 4607
__enumext_keyans_show_ans: 3683
__enumext_keyans_show_item_opt: 3650
__enumext_keyans_show_item_opt_viii: . 3650
__enumext_keyans_show_pos: 3683
__enumext_keyans_starred_item:n 4055
__enumext_keyans_starred_item_star: .. 5748
__enumext_keyans_store_ref: 3554
__enumext_keyans_store_ref_aux_i: ... 3554
__enumext_keyans_store_ref_aux_ii: ... 3554
__enumext_keyans_unknown_keys:n 3906
__enumext_keyans_unknown_keys:nn 3906
__enumext_keyans_wrapper_label:n 4084
__enumext_keyans_wrapper_label_viii:n 5814
\l__enumext_label_copy_X_tl 170
\l__enumext_label_fill_left_X_tl 97
\l__enumext_label_fill_right_X_tl 97
\l__enumext_label_i_tl 753
\l__enumext_label_ii_tl 753
\l__enumext_label_iii_tl 753
\l__enumext_label_iv_tl 753
__enumext_label_style:Nnn 641
\l__enumext_label_v_tl 867
\l__enumext_label_vi_tl 867
\l__enumext_label_vii_tl 797
\l__enumext_label_viii_tl 797
\l__enumext_label_width_by_box 65
__enumext_label_width_by_box:Nn 635
\l__enumext_leftmargin_tmp_X_bool 69
\l__enumext_leftmargin_tmp_X_dim 69
\l__enumext_leftmargin_X_dim 69
__enumext_level: 218
\l__enumext_level_h_int 25
\l__enumext_level_int 25
__enumext_list_arg_two_i: 4178
__enumext_list_arg_two_ii: 4178
__enumext_list_arg_two_iii: 4178
__enumext_list_arg_two_iv: 4178
__enumext_list_arg_two_v: 4178
__enumext_list_arg_two_vii: 4224
__enumext_list_arg_two_viii: 4224
__enumext_log_answer_vars: 353
__enumext_log_global_vars: 353
__enumext_make_label: 3836
__enumext_make_label_box: 3836
__enumext_make_label_std: 3836
\l__enumext_mark_position_str 131
\l__enumext_mark_position_v_str 131
\l__enumext_mark_position_viii_str ... 131
\l__enumext_mark_sep_tmpa_dim 131
\l__enumext_mark_sep_tmpb_dim 131
\l__enumext_meta_path_str 127
__enumext_mini_addvspace_vii: 1687
__enumext_mini_addvspace_viii: 1687
__enumext_mini_page 575
__enumext_mini_right_cmd:n 1726
__enumext_mini_set_vskip_vii: 1630
__enumext_mini_set_vskip_viii: 1630
__enumext_minipage:w 385
\g__enumext_minipage_active_X_bool ... 184
\l__enumext_minipage_active_X_bool 84
__enumext_minipage_add_space: 1365
\g__enumext_minipage_after_skip 84
\l__enumext_minipage_after_skip 84
\g__enumext_minipage_center_X_bool ... 184
\l__enumext_minipage_left_skip 84
\l__enumext_minipage_left_X_dim 84
\g__enumext_minipage_right_skip 84
\l__enumext_minipage_right_skip 84
\g__enumext_minipage_right_X_dim 184
__enumext_minipage_set_skip: 1365
\g__enumext_minipage_stat_int 84
\l__enumext_minipage_temp_skip 84
\l__enumext_miniright_code_X_box 184
__enumext_multi_addvspace: 1320
__enumext_multi_set_vskip: 1275
\l__enumext_multicols_above_X_skip 77
\l__enumext_multicols_below_X_skip 77
__enumext_multicols_start: 4371
__enumext_multicols_stop: 4401
__enumext_nested_base_line_fix: 1028
__enumext_newlabel:nn 430
\l__enumext_newlabel_arg_one_tl 170
\l__enumext_newlabel_arg_two_tl 170
__enumext_parse_foreach_keys:n 6283
__enumext_parse_foreach_keys:nn 6283
__enumext_parse_keys:n 4310
__enumext_parse_keys_vii:n 5402
__enumext_parse_keys_viii:n 5685
__enumext_parse_save_key:n 2877
__enumext_parse_save_key_vii:n 2877
__enumext_parse_series:n 2167
__enumext_phantomsection: 396

©2024–2026 by Pablo González L

__enumext_pre_itemsep_skip: 1412
__enumext_print_footnote: 445
__enumext_print_footnote_mini: 445
__enumext_print_footnote_standard: . . . 509
__enumext_print_footnote_starred: . . . 509
__enumext_print_keyans_box:NN 2998
\l__enumext_print_keyans_cmd_bool 131
\l__enumext_print_keyans_star_bool . . . 131
\l__enumext_print_keyans_starred_tl . . . 131
\l__enumext_print_keyans_X_tl 131
__enumext_printkeyans:nnn 6024
__enumext_redefine_item: 3825
\l__enumext_ref_key_arg_tl 46
\l__enumext_ref_the_count_tl 46
__enumext_register_default_label_wd:Nn 625
__enumext_remove_extra_parsep_vii: . . . 5614
__enumext_remove_extra_parsep_viii: . . 5897
\l__enumext_renew_counter_X_tl 46
__enumext_renew_footnote: 445
__enumext_renew_footnote_mini: 445
__enumext_renew_footnote_standard: . . . 509
__enumext_renew_footnote_starred: . . . 509
__enumext_reset_count_resume:nn 2334
__enumext_reset_count_resume_all:n . . . 2334
__enumext_reset_count_resume_levels:n 2334
__enumext_reset_global_bool: 329
__enumext_reset_global_int: 329
__enumext_reset_global_tl: 329
__enumext_reset_global_vars: 329
__enumext_resume:n 2210
\l__enumext_resume_count_bool 55
\l__enumext_resume_count_X_bool 55
__enumext_resume_counter: 2047
__enumext_resume_integer_series: 2238
__enumext_resume_last_counter: 2133
\g__enumext_resume_last_keys_X_tl 55
__enumext_resume_series:n 2238
\l__enumext_resume_series_X_bool 55
__enumext_resume_star: 2303
\l__enumext_resume_star_key_X_bool 55
__enumext_safe_exec: 4299
__enumext_safe_exec_vii: 5385
__enumext_safe_exec_viii: 5661
__enumext_save_last_keys:n 2133
__enumext_second_part: 4440
__enumext_second_part_v: 4530
\l__enumext_series_name_tl 55
__enumext_set_error:nn 6149
__enumext_set_item_width: 4465
__enumext_set_parse:n 6149
\l__enumext_setkey_tmpa_int 122
\l__enumext_setkey_tmpa_seq 122
\l__enumext_setkey_tmpa_tl 122
\l__enumext_setkey_tmpb_seq 122
\l__enumext_setkey_tmpb_tl 122
__enumext_show_length:nnn 228
\l__enumext_show_pos_tmp_int 131
\g__enumext_standard_bool 31
\l__enumext_standard_bool 31
\l__enumext_standard_first_bool 31
__enumext_standard_item_vii:w 5466
__enumext_standard_item_viii:w 5712
__enumext_standard_ref: 774
__enumext_standard_ref:nn 774
__enumext_standard_reset:nn 2334
__enumext_standard_reset_key: 2414
__enumext_standard_reset_key_star: . . . 2414
__enumext_standard_save_counter: 1960
__enumext_standard_save_counter_aux: . 1960
__enumext_standard_unknown_keys:n . . . 3954
__enumext_standard_unknown_keys:nn . . . 3954
\g__enumext_starred_bool 31
\l__enumext_starred_bool 31
__enumext_starred_columns_set_vii: . . . 5057
__enumext_starred_columns_set_viii: . . 5057
\l__enumext_starred_first_bool 31
__enumext_starred_item_vii:w 5466
__enumext_starred_item_vii_aux_i:w . . . 5466
__enumext_starred_item_vii_aux_ii:w . . 5466
__enumext_starred_item_vii_aux_iii:w . 5466
__enumext_starred_item_viii:w 5748
__enumext_starred_item_viii_aux_i:w . . 5748
__enumext_starred_item_viii_aux_ii:w . 5748
__enumext_starred_joined_item_vii:n . . 5119
__enumext_starred_joined_item_viii:n . 5119
__enumext_starred_ref: 816
__enumext_starred_ref:n 816
__enumext_starred_reset:n 2334
__enumext_starred_reset_key: 2414
__enumext_starred_save_counter: 1960
__enumext_starred_save_counter_aux: . . 1960
__enumext_starred_unknown_keys:n 3932
__enumext_starred_unknown_keys:nn . . . 3932
__enumext_start_from:NNn 910
__enumext_start_item_tmp_vii: 5466
__enumext_start_item_tmp_viii: 5712
__enumext_start_item_vii:w 5575
__enumext_start_item_viii:w 5854
\g__enumext_start_line_tl 31
__enumext_start_list:nn 385
__enumext_start_list_tag:n 4640
__enumext_start_mini_vii: 5222
__enumext_start_mini_viii: 5287
__enumext_start_save_ans_msg: 2509
__enumext_start_store_level: 4335
__enumext_start_store_level_vii: 5438
\l__enumext_start_X_int 97
__enumext_stop_item_vii: 5575
__enumext_stop_item_viii: 5854
__enumext_stop_list: 385
__enumext_stop_list_tag:n 4640
__enumext_stop_mini_vii: 5222
__enumext_stop_mini_viii: 5287
__enumext_stop_save_ans_msg: 2509
__enumext_stop_start_list_tag: 4640
__enumext_stop_store_level: 4364
__enumext_stop_store_level_vii: 5438
\l__enumext_store_active_bool 109
__enumext_store_active_keys:n 2845
__enumext_store_active_keys_vii:n . . . 2845
__enumext_store_addto_prop:n 2922
__enumext_store_addto_seq:n 2931

©2024–2026 by Pablo González L

__enumext_store_anskey_arg:n 3087
\l__enumext_store_anskey_arg_tl 114
__enumext_store_anskey_env:n 3463
\l__enumext_store_anskey_env_tl 114
\l__enumext_store_current_label_tl . . . 109
\l__enumext_store_current_opt_arg_tl . . 109
__enumext_store_internal_ref: 3012
__enumext_store_level_close: 2936
__enumext_store_level_close_vii: 2967
__enumext_store_level_open: 2936
__enumext_store_level_open_vii: 2967
\g__enumext_store_name_tl 109
\l__enumext_store_name_tl 109
\l__enumext_store_save_key_X_bool 131
\l__enumext_store_save_key_X_tl 131
\l__enumext_store_upper_level_X_bool . . 131
__enumext_storing_exec: 2519
__enumext_storing_set:n 2519
\l__enumext_the_counter_X_tl 46
\l__enumext_tmpa_X_int 184
__enumext_unskip_unkern: 234
\l__enumext_vspace_a_star_X_bool 97
__enumext_vspace_above: 1824
__enumext_vspace_above_v: 1852
__enumext_vspace_above_vii: 1874
__enumext_vspace_above_viii: 1874
\l__enumext_vspace_b_star_X_bool 97
__enumext_vspace_below: 1838
__enumext_vspace_below_v: 1863
__enumext_vspace_below_vii: 1896
__enumext_vspace_below_viii: 1896
__enumext_widest_from:nNNn 925
\g__enumext_widest_label_tl 65
\l__enumext_wrap_label_opt_X_bool 97
\l__enumext_wrap_label_X_bool 97
__enumext_wrapper_label_v:n 4084
__enumext_wrapper_label_viii:n 5814
\l__enumext_write_anskey_env_bool 114
\l__enumext_write_anskey_env_file_iow . 114
\l__enumext_write_anskey_env_file_name_-
tl 114
\l__enumext_write_aux_file_tl 170
enumext* 5, 5359, 6097
enumext-1 6097
enumext-2 6097
enumext-3 6097
enumext-4 6097
enumXi 594
enumXii 594
enumXiii 594
enumXiv 594
enumXv 594
enumXvi 594
enumXvii 594
enumXviii 594
Environments provided by enumext:
anskey* 32
enumext* 32
enumext 122
keyans* 145
keyanspic 127, 129
keyans 125

F

first 1172
font 667
\footnote 42
for-key-unknown 6263
for-key-value-unknown 6263
force-eol 3325
\foreachkeyans 20, 157, 6354

G

\getkeyans 20, 150, 5945

I

invalid-key 6190
\item 6, 58, 107, 113, 141, 143, 146, 149
\item* 6, 17, 87, 4066
item-answer-hook 368
item-greater-answer 2465
item-join 3210, 3325
item-joined 5346
item-joined-columns 5346
item-less-answer 2465
item-pos* 3210, 3325, 3890
item-star 3210, 3325
item-sym* 3210, 3325, 3890
\itemindent 115
itemindent 1064
items-same-answer 2465
itemsep 986

K

key-ref-empty 906
keyans 17, 4618, 6097
keyans* 17, 5634, 6097
keyans-nested 4636
keyans-unknown-key 4023
keyans-unknown-key-value 4023
keyans-wrong-level 3757
keyanspic 18, 4842
keyanspic-item-cmd 5044
keyanspic-nested 5044
keyanspic-wrong-level 5044
Keys for \anskey provided by enumext:
break-col 94, 97
force-eol 99
item-join 95, 97
item-pos* 95, 97, 108, 110
item-star 95, 97
item-sym* 95, 97, 108, 110
overwrite 99
write-env 99
Keys for \foreachkeyans provided by enumext:
after 57, 122, 140, 146
before 57
start 38, 52, 75, 76
Keys for anskey* provided by enumext:
break-col 94, 97
force-eol 99
item-join 95, 97
item-pos* 95, 97, 108, 110
item-star 95, 97
item-sym* 95, 97, 108, 110

©2024–2026 by Pablo González L

overwrite 99, 100
write-env 99, 100
Keys for environments provided by enumext:
above* 54, 69, 70, 121, 140
above 54, 69, 70, 121, 140, 146
after 57, 122, 140, 146
align 48, 106, 109, 114, 143, 159
base-fix 54, 75, 90, 119
before* 57, 121, 140, 146
before 57
below* 69–71, 122, 140
below 69–71, 122, 140, 146
check-ans 37, 39, 81, 83–87, 90, 102, 105, 122, 140
columns-sep 58, 120, 144
columns 58, 120
first 57, 58, 144
font 47, 109, 114, 131, 143
item-pos* 108, 110
item-sym* 108, 110
itemindent 55, 56, 108, 113, 114, 144
itemsep 53, 117, 144
label-pos 127, 129, 131, 159
label-sep 127
labelsep 47, 116, 143
labelwidth 46, 47, 49, 51, 52, 116, 143
label 46, 52, 129
layout-sep 128
layout-sty 128, 132
layout-top 128
list-indent 55, 129
list-offset 55, 122, 125
listparindent 55, 117, 144
mark-ans* 87, 91, 106
mark-ans 88, 91, 96
mark-pos* 87, 91, 106
mark-pos 88, 91, 159
mark-ref 88, 91, 95
mark-sep* 87, 91, 106
mark-sep 88, 91, 148
mini-env 42, 43, 45, 58, 67, 91, 121, 136, 138, 140, 146, 160
mini-right* 37, 59, 91, 138, 140
mini-right 37, 59, 67, 91, 138, 140
mini-sep 58, 91, 121
mode-box 47, 109, 114
no-store 83, 84, 90, 97, 100, 107, 108
noitemsep 53
nosep 53
parsep 53, 117, 129, 144
partopsep 53
ref 49, 51
reset* 75, 80, 81, 90, 154
reset 75, 80, 90, 154
resume* 46, 71, 73, 75, 76, 78, 79, 83, 90, 122, 140, 154
resume 40, 46, 52, 71–79, 83, 90, 122, 140, 154
rightmargin 55, 134
save-ans 40, 72, 73, 75, 77, 81–84, 86, 89–91, 98, 101–104, 123, 133, 143, 145, 148, 151, 154
save-key 75, 90, 119, 140
save-ref 42, 88, 90, 94, 103, 105, 113, 148
save-sep 87, 91, 103, 148
series 71, 72, 75–78, 90, 119, 122, 140, 154
show-ans 87, 88, 90, 92, 94, 96, 105, 106, 131, 148
show-length 38, 57, 118
show-pos 87, 88, 92, 94, 96, 105, 131, 148
start* 52, 75, 76
start 38, 52, 75, 76
topsep 53, 54, 129
widest 38, 49, 52
wrap-ans* 87, 91, 114, 131
wrap-ans 88, 91, 92, 95
wrap-label* 47, 108, 109, 113, 114, 142, 143, 147
wrap-label 47, 108, 109, 113, 114, 129, 131, 142, 143, 147
wrap-opt 87, 91, 105, 113, 131
keys commands:
\l_keys_key_str 97, 99
\keys_precompile:nnN 152, 208

L

label 753, 797, 867
label-pos 4738
label-sep 4738
Labels provided by enumext:
\Alph* 46
\Roman* 46
\alph* 46
\arabic* 46
\roman* 46
labelsep 667
labelwidth 667
layout-sep 4738
layout-sty 4738
layout-top 4738
\leftmargin 115
list-indent 1064
list-lengths 4269
list-lengths-not-nested 4284
list-offset 1064
list-too-deep 4501
listparindent 1064

M

\makelabel 107, 113
many-miniright-used 1782
many-starred 2486
mark-ans 2762, 4738
mark-ans* 2721, 2762
mark-pos 2762, 4738
mark-pos* 2721, 2762
mark-ref 2762
mark-sep 2762, 4738
mark-sep* 2721, 2762
midpenalty 970
mini-env 1243
mini-right 1243
mini-right* 1243
mini-sep 1243
\miniright 12, 67, 1699
missing-colon 5914
missing-miniright 6379
missing-starred 2486
mode-box 657

N

nested 6384
nested-horizontal 5346
no-store 2560
noitemsep 986
nosep 986

©2024–2026 by Pablo González L

not-writing 3429

O

out-of-range 2389
overwrite 3325
overwrite-file 3429

P

package-load 6358
package-not-load 6358
Packages :
caption 137
enumitem 45
expl3 133
footnotehyper 42
hyperref 36
latex-lab-block 41
ltcmd 41
ltsockets 125
lua-visual-debug 61
multicol 32
scontents 99
shortlst 133
tagpdf 125
parsep 986
partopsep 986
print* 5950, 6097
print-* 5950, 6097
print-1 . . . . . 5950, 6097
print-2 . . . . . 5950, 6097
print-3 . . . . . 5950, 6097
print-4 . . . . . 5950, 6097
print-starred 6019
\printkeyans 21, 151, 6059
prohibited-unknown 6198
prop-seq-int-hook 368

R

ref 753, 797, 867
reset 2396
reset* 2396
\resetenumext 12, 79, 2334
resume 1918
resume* 1918
rightmargin 1064

S

save-ans 2444
save-ans-empty 2453
save-ans-log 2453
save-ans-log-hook 2453
save-key 2863
save-ref 2762
save-sep 2721, 2762, 4738
sep 6283
seq commands:
\seq_use:Nn 208
series 1918
\setenumext 6, 154, 6163
\setenumextmeta 7, 156, 6249
show-ans 2721, 2762, 4738
show-length 1163
show-pos 2721, 2762, 4738
standard-unknown-key 4001
standard-unknown-key-value 4001
starred-unknown-key 3981
starred-unknown-key-value 3981
start 941, 6283
start* 941
start-list-tags 4640, 4688
step 6283
stop 6283
stop-list-tags 4640, 4688
stop-start-tags 4640, 4688
store-int 2494
store-prop 2494
store-seq 2494

T

topsep 986

U

undefined-storage-anskey 6375
unknown . . . 3210, 3325, 3906, 3932, 3954, 4738, 6097, 6283
unknown-choice 6366
unknown-key-family 6190
unknown-series-standard 2096
unknown-series-starred 2096

W

widest 941
width-negative 4264
wrap-ans 2762
wrap-ans* 2721, 2762, 4738
wrap-label 667
wrap-label* 667
wrap-opt 2721, 2762, 4738
wrapper 6283
write-env 3325
writing-file 3429
wrong-miniright-place 1782
wrong-miniright-starred 1782
wrong-miniright-use 1782
wrong-place 3757

©2024–2026 by Pablo González L