Nothing:
Verbatim (hey blub): `hey blub`

Math-mode (*blob*): *blob*
Verbatim (hey): `hey`

Math-mode (*blob*): *blob*
Verbatim (hey blub): `hey blub`

Nothing:
Verbatim (`\begin`...): `\begin{scontents}[store-env=nowhere]  hello \end{scontents}`

Multi-line verbatim (`\begin`...):

```
\begin{scontents}[store-env=nowhere]
  hello
\end{scontents}
```

Nothing (+error):
Nothing:
Multi-line verbatim (hello):

```
  hello
```

Should be 1: `\1`
Should raise an error about ‘ bzzz’:
Should be 2: `\2`
Should raise an error about ‘ [store-env=nowhere]’: Should still be 2: `\2`
Should be 2: `\2` But this should be “[store-env=nowhere] 4”: `[store-env=nowhere] \4`
Should be 5: `\5`
Should still be 5: `\5` And this should be empty: [ ]

XXWrite in one line LaTeX: $E = mc^2$, no space after dot.YY
XXOther in one line, no space after dot.YY
XXOther in one line, no space after dot.YY

```
1 Write in one line \LaTeX : $E=mc^2$, no space after dot.
```

```
1 Other in one line, no space after dot.
```

```
1 Other in one line, no space after dot.
```

```
1 Other in one line, no space after dot.
```

```
1 Other  in  one  line,  no  space  after  dot.
```

```
1 Other   in   one   line,   no   space   after   dot.
```

```
1 Other    in    one    line,    no    space    after    dot.
```

```
1 TODO: Tab after comma:, .
```

```
Write in one line \LaTeX : $E=mc^2$, no space after dot.
Other in one line, no space after dot.
Other in one line, no space after dot.
Other in one line, no space after dot.
Other  in  one  line,  no  space  after  dot.
Other   in   one   line,   no   space   after   dot.
```

Other in one line, no space after dot.
TODO: Tab after comma:, .
FIRST
This Ω is normal Ω text. This is from the verb command. This␣is␣from␣the␣verb*␣command. This is normal text.

This is from the verbatim environment:
&%{}~
Soy un ^^J Soy un ^^M text.

SECOND
This Ω is normal Ω text. This is from the verb command. This␣is␣from␣the␣verb*␣command. This is normal text.

This is from the verbatim environment:
&%{}~
Soy un ^^J Soy un ^^M text.

This text is removed from the output because it is on the same line. THIRD
This Ω is normal Ω text. This is from the verb command. This␣is␣from␣the␣verb*␣command. This is normal text.

This is from the verbatim environment:
&%{}~
Soy un ^^J Soy un ^^M text.

MEANINGSC
This ^^J is normal ^^J text. \verb|This is from the verb command.| \verb*|This is from the verb* command.| This is normal text. \begin{verbatim} This is from the verbatim environment: &%{}~ Soy un ^^J Soy un ^^M text. \end{verbatim}
This text is removed from the output because it is on the same line.

```
This ^^J is normal ^^J text.
\verb|This is from the verb command.|
\verb*|This is from the verb* command.|
This is normal text.
\begin{verbatim}
This is from the verbatim environment:
&%{}~
Soy un ^^J Soy un ^^M text.
\end{verbatim}
```

1 Test \Scontents[key=val]

Test \Scontents[print-cmd=false]
Test \Scontents[print-cmd=true]
Using \Scontents command, no environment verbatim support, but fvextra inline yes and lstinline yes, save in seq contents with index 2.
Test \Scontents[store-cmd=testcmd]

1.1 Test \getstored[index]{seq name}

Test \getstored[1]{contents}:
Using \Scontents command,
no environment verbatim support,
but fvextra inline yes and lstinline yes, save in seq contents with index 1.

Test \getstored[2]{contents}:
Using \Scontents command, no environment verbatim support, but fvextra inline yes and lstinline yes, save in seq contents with index 2.

Test \getstored[1]{testcmd}:
Using \Scontents command, no environment verbatim support, but fvextra inline yes and lstinline yes, save in seq testcmd with index 1.

1.2 Test \meaningsc[index]{seq name}

Test \meaningsc[1]{contents}:
```
Using \texttt {\textbackslash Scontents} command, \par no environment verbatim support,\par
but \Verb {fvextra inline yes} and \lstinline [basicstyle=\ttfamily ]|lstinline yes|, save
in seq \texttt {contents} with index $1$.
```

Test \meaningsc[2]{contents}:
```
Using \texttt {\textbackslash Scontents} command, no environment verbatim support, but \Verb
{fvextra inline yes} and \lstinline [basicstyle=\ttfamily ]|lstinline yes|, save in seq \texttt
{contents} with index $2$.
```

Test \meaningsc[1]{testcmd}:
```
Using \texttt {\textbackslash Scontents} command, no environment verbatim support, but \Verb
{fvextra inline yes} and \lstinline [basicstyle=\ttfamily ]|lstinline yes|, save in seq \texttt
{testcmd} with index 1.
```

---

2 Test \Scontents*[key=val]

Test \setupsc{store-cmd=testcmdvrb}
Test \Scontents*[print-cmd=false]
Test \Scontents*[print-cmd=true]
Using \Scontents*[print-cmd=true]+...+ command, with verbatim support,

```
more verbatim environment
```

And fvextra inline yes, save in seq testcmdvrb with index 2.
Test \Scontents[store-cmd=othervrb]

2.1 Test \getstored[index]{seq name}

Test \getstored[1]{testcmdvrb}:
Using \Scontents* command,
with verbatim support.

```
␣␣␣␣␣␣verbatim
␣␣␣␣␣␣␣␣␣␣␣␣␣␣environment
```

fvextra inline yes, save in seq testcmdvrb with index 1.

Test \getstored[2]{testcmdvrb}:
Using \Scontents*[print-cmd=true]+...+ command, with verbatim support,

```
more verbatim environment
```

And fvextra inline yes, save in seq testcmdvrb with index 2.

Test \getstored[1]{othervrb}:
Using \Scontents* command, with verbatim support,

```
other verbatim  environment
```

And fvextra inline yes, save in seq othervrb with index 1.

2.2 Test \meaningsc[index]{seq name}

Test \meaningsc[1]{testcmdvrb}:

```
Using \texttt{\textbackslash Scontents*} command,  with verbatim support.    \begin{verbatim*}
verbatim               environment \end{verbatim*}  \Verb{fvextra inline yes}, save in seq
\texttt{testcmdvrb} with index 1.
```

Test \meaningsc[2]{testcmdvrb}:

```
Using \verb/\Scontents*[print-cmd=true]+...+/ command, with verbatim support,  \begin{verbatim}
more verbatim environment \end{verbatim}  And \Verb{fvextra inline yes}, save in seq \texttt{testcmdvrb}
with index $2$.
```

Test \meaningsc[1]{othervrb}:

```
Using \texttt{\textbackslash Scontents*} command, with verbatim support,  \begin{verbatim}
other verbatim  environment \end{verbatim}  And \Verb{fvextra inline yes}, save in seq \texttt{othervrb}
with index $1$.
```

2.3 Test \typestored[index]{seq name}

Test \typestored[1]{testcmdvrb}:

```
Using \texttt{\textbackslash Scontents*} command,

with verbatim support.

\begin{verbatim*}
      verbatim
               environment
\end{verbatim*}

\Verb{fvextra inline yes}, save in seq \texttt{testcmdvrb} with index 1.
```

Test \typestored[2]{testcmdvrb}:

```
Using \verb/\Scontents*[print-cmd=true]+...+/ command, with verbatim support,

\begin{verbatim}
      more verbatim environment
\end{verbatim}

And \Verb{fvextra inline yes}, save in seq \texttt{testcmdvrb} with index $2$.
```

Test \typestored[1]{othervrb}:

```

Using \texttt{\textbackslash Scontents*} command, with verbatim support,

\begin{verbatim}
      other verbatim  environment
\end{verbatim}

And \Verb{fvextra inline yes}, save in seq \texttt{othervrb} with index $1$.
```

3 Test \Scontents* and \Scontents back to default

Using \Scontents command with braces, save in seq contents with index 3.
Using \Scontents* command (verbatimized), save in seq testcmdvrb with index 3.

4 Test on mobile arguments

Test \subsection{\getstored[3]{testcmdvrb}}:

4.1 Using \Scontents* command (verbatimized), save in seq testcmdvrb with index 3.

Test \subsection{\getstored[3]{contents}}:

4.2 Using \Scontents command with braces, save in seq contents with index 3.

---

5 Test {scontents} environment

5.1 no [key=val]

Test scontents no [key=val]
Using scontents env, [force-eol], save in seq testenv index 1.
We have coded this in LaTeX: $E = mc^2$.
Prove new ␣verbatim␣from␣fvextra␣with␣braces␣ and environment Verbatim*.

```
␣␣␣␣␣␣(A)␣verbatim
␣␣␣␣␣␣␣␣␣␣environment
```

5.1.1 \getstored[1]{testenv}

XXUsing scontents env, [force-eol], save in seq testenv index 1.
We have coded this in LaTeX: $E = mc^2$.
Prove new ␣verbatim␣from␣fvextra␣with␣braces␣ and environment Verbatim*.

```
␣␣␣␣␣␣(A)␣verbatim
␣␣␣␣␣␣␣␣␣␣environment
```

YY

5.1.2 \meaningsc[1]{testenv}

```
Using \verb+scontents+ env, \verb+[force-eol]+, save in seq \verb+testenv+ index 1.\par We
have coded this in \LaTeX: $E=mc^2$.    Prove new \Verb*{ verbatim from fvextra with braces
} and environment \verb+Verbatim*+.  \begin{Verbatim*}       (A) verbatim           environment
\end{Verbatim*}
```

5.1.3 \typestored[1]{testenv}

```
1  Using \verb+scontents+ env, \verb+[force-eol]+, save in seq \verb+testenv+ index 1.\par
2  We have coded this in \LaTeX: $E=mc^2$.
3
4  Prove new \Verb*{ verbatim from fvextra with braces } and environment \verb+Verbatim*+.
5  \begin{Verbatim*}
6        (A) verbatim
7            environment
8  \end{Verbatim*}
```

5.2 with [key=val]

5.2.1 [write-env=\jobname.tsc]

Using scontents env with [write-env=\jobname.tsc], save in seq testenv with index 2 and write env body in file \jobname.tsc.
We have coded this in LaTeX: $E = mc^2$.

␣␣␣␣␣␣(B)␣verbatim
␣␣␣␣␣␣␣␣␣␣environment

5.2.2 \getstored[2]{testenv}

Using scontents env with [write-env=\jobname.tsc], save in seq testenv with index 2 and write env body in file \jobname.tsc.
We have coded this in LaTeX: $E = mc^2$.

␣␣␣␣␣␣(B)␣verbatim
␣␣␣␣␣␣␣␣␣␣environment

5.2.3 \meaningsc[2]{testenv}

```
Using \verb+scontents+ env with \verb+[write-env=\jobname.tsc]+, save in seq \verb+testenv+
with index 2 and write env body in file \verb+\jobname.tsc+.    We have coded this in \LaTeX:
$E=mc^2$.\par \begin{verbatim*}       (B) verbatim           environment \end{verbatim*}
```

5.2.4 \typestored[2]{testenv}

```
1  Using \verb+scontents+ env with \verb+[write-env=\jobname.tsc]+, save in
2  seq \verb+testenv+ with index 2 and write env body in file \verb+\jobname.tsc+.
3
4  We have coded this in \LaTeX: $E=mc^2$.\par
5  \begin{verbatim*}
6        (B) verbatim
7            environment
8  \end{verbatim*}
```

5.2.5 \VerbatimInput{\jobname.tsc}

```
1  Using \verb+scontents+ env with \verb+[write-env=\jobname.tsc]+, save in
2  seq \verb+testenv+ with index 2 and write env body in file \verb+\jobname.tsc+.
3
4  We have coded this in \LaTeX: $E=mc^2$.\par
5  \begin{verbatim*}
6        (B) verbatim
7            environment
8  \end{verbatim*}
```

5.2.6 [print-env=true]

Using scontents env with [print-env=true], save in seq testenv with index 3.
We have coded this in LaTeX: $E = mc^2$.

␣␣␣␣␣␣(C)␣verbatim
␣␣␣␣␣␣␣␣␣␣environment

\getstored[3]{testenv}
Using scontents env with [print-env=true], save in seq testenv with index 3.
We have coded this in LaTeX: $E = mc^2$.

␣␣␣␣␣␣(C)␣verbatim
␣␣␣␣␣␣␣␣␣␣environment

```
\meaningsc[3]{testenv}
Using \verb+scontents+ env with \verb+[print-env=true]+, save in seq \verb+testenv+ with index
3.    We have coded this in \LaTeX: $E=mc^2$.\par \begin{verbatim*}       (C) verbatim           enviro
\end{verbatim*}
\typestored[3]{testenv}
```

```
Using \verb+scontents+ env with \verb+[print-env=true]+, save in
seq \verb+testenv+ with index 3.

We have coded this in \LaTeX: $E=mc^2$.\par
\begin{verbatim*}
      (C) verbatim
          environment
\end{verbatim*}
```

5.2.7 [print-env=true,write-env=\jobname-1.tsc]

Using scontents env with [print-env=true,write-env=\jobname-1.tsc], save in seq testenv with index 4.
We have coded this in LaTeX: $E = mc^2$.

␣␣␣␣␣␣(D)␣verbatim
␣␣␣␣␣␣␣␣␣␣environment

```
\getstored[4]{testenv}
```

Using scontents env with [print-env=true,write-env=\jobname-1.tsc], save in seq testenv with index 4.
We have coded this in LaTeX: $E = mc^2$.

␣␣␣␣␣␣(D)␣verbatim
␣␣␣␣␣␣␣␣␣␣environment

```
\meaningsc[4]{testenv}
Using \verb+scontents+ env with \verb+[print-env=true,write-env=\jobname-1.tsc]+, save in seq
\verb+testenv+ with index 4.    We have coded this in \LaTeX: $E=mc^2$.\par \begin{verbatim*}
(D) verbatim           environment \end{verbatim*}
\typestored[4]{testenv}
```

```
Using \verb+scontents+ env with \verb+[print-env=true,write-env=\jobname-1.tsc]+, save in
seq \verb+testenv+ with index 4.

We have coded this in \LaTeX: $E=mc^2$.\par
\begin{verbatim*}
      (D) verbatim
          environment
\end{verbatim*}
```

```
\VerbatimInput{\jobname-1.tsc}
```

```
Using \verb+scontents+ env with \verb+[print-env=true,write-env=\jobname-1.tsc]+, save in
seq \verb+testenv+ with index 4.

We have coded this in \LaTeX: $E=mc^2$.\par
\begin{verbatim*}
      (D) verbatim
          environment
\end{verbatim*}
```

5.3 [write-out=\jobname-2.tsc]

\VerbatimInput{\jobname-2.tsc}

```
Using \verb+scontents+ env with \verb+[write-out=\jobname-2.tsc]+,
not added to seq, only write a external file
We have coded this in \LaTeX: $E=mc^2$.\par
\begin{verbatim}
      (E) verbatim
          environment
\end{verbatim}
```

5.3.1 [print-env=true,store-env=other]

Using scontents env with [print-env=true,store-env=other], save in seq other with index 1.
We have coded this in LaTeX: $E = mc^2$.

␣␣␣␣␣␣(F)␣verbatim
␣␣␣␣␣␣␣␣␣␣environment

\getstored[1]{other}
Using scontents env with [print-env=true,store-env=other], save in seq other with index 1.
We have coded this in LaTeX: $E = mc^2$.

␣␣␣␣␣␣(F)␣verbatim
␣␣␣␣␣␣␣␣␣␣environment

\meaningsc[1]{other}
Using \verb+scontents+ env with \verb+[print-env=true,store-env=other]+, save in seq \verb+other+ with index 1. We have coded this in \LaTeX: $E=mc^2$.\par \begin{verbatim*} (F) verbatim environment \end{verbatim*}
\typestored[1]{other}

```
Using \verb+scontents+ env with \verb+[print-env=true,store-env=other]+, save in
seq \verb+other+ with index 1.

We have coded this in \LaTeX: $E=mc^2$.\par
\begin{verbatim*}
      (F) verbatim
          environment
\end{verbatim*}
```

6 A simple application

6.1 Exercises

This is exercise 1
This is the answer to exercise 1, the shebang line for a Perl script

```
#!/usr/bin/env perl
```

YYYYYYYYYYxxx

```
This is the answer to exercise 1, the shebang line for a Perl script

\begin{Verbatim}
#!/usr/bin/env perl
\end{Verbatim}
```

YYYThis is the answer to exercise 1, the shebang line for a Perl script

```
#!/usr/bin/env perl
```

XXX
This is exercise 2
This is exercise 3

6.2 Answers

Answer 1:This is the answer to exercise 1, the shebang line for a Perl script

```
#!/usr/bin/env perl
```

Answer 2:This is the answer to exercise 2
Answer 3:This is the answer to exercise 3

6.3 typestored

```
1  This is the answer to exercise 1, the shebang line for a Perl script
2
3  \begin{Verbatim}
4  #!/usr/bin/env perl
5  \end{Verbatim}
```

```
1  This is the answer to exercise 2
```

6.4 Nested

6.4.1 getstored

This text is in the outermost environment (before nested). This text is in the outermost environment (after nested).
This text is found in the most inner environment.

6.4.2 count

Number of items stored in `outer` 1
Number of items stored in `inner` 1

6.5 newenvsc

This text is in the outermost environment (before nested). This text is in the outermost environment (after nested).
This text is found in the most inner environment.

6.6 write-cmd

Text Text Number of items stored in `writekey` 2.
Something `B`.

Something `C`. Something `B`.
Something `C`.

6.7 envname=maybePrint

START TEXT
START TEXT
START TEXT

6.8 mergesc

7 First annswer

Preamble's addition

```
1  \usepackage{amsmath}
```

Code snippet

```
\begin{align}
  0 & \neq 1 \\
  1 & \neq 0
\end{align}
```

MCE

```
\documentclass[french]{article}
\usepackage[T1]{fontenc}
\usepackage[utf8]{inputenc}
\usepackage{lmodern}
\usepackage[a4paper]{geometry}
\usepackage{amsmath}
\usepackage{babel}
\begin{document}
\begin{align}
  0 & \neq 1 \\
  1 & \neq 0
\end{align}
\end{document}
```

8 Second annswer

Preamble's addition

```
\usepackage{amsmath}
```

Code snippet

```
\begin{flalign}
  0 & \neq 1 \\
  1 & \neq 0
\end{flalign}
```

MCE

```
\documentclass[french]{article}
\usepackage[T1]{fontenc}
\usepackage[utf8]{inputenc}
\usepackage{lmodern}
\usepackage[a4paper]{geometry}
\usepackage{amsmath}
\usepackage{babel}
\begin{document}
\begin{flalign}
  0 & \neq 1 \\
  1 & \neq 0
\end{flalign}
\end{document}
```