

spintent

SPANISH PARSE INTENTS

V0.99 2026-09-13*

©2026 by Pablo González L[†]

CTAN: <https://www.ctan.org/pkg/spintent>

 <https://github.com/pablgonz/spintent>

Resumen

El paquete **spintent** proporciona una serie de utilidades para docentes de educación primaria y secundaria que necesiten crear documentos PDF *accesibles* (*tagged* PDF) en español usando Lua[†] $\TeX$.

Índice

1	Descripción	1	3.3	El comando <code>\spmoney</code>	6
1.1	Carga del paquete	1	3.3.1	Llaves para <code>\spmoney</code>	7
1.2	El paquete <code>babel</code>	2	3.3.2	Monedas y alias para <code>\spmoney</code>	7
1.3	Fuentes tipográficas	2	3.4	El comando <code>\spshort</code>	7
1.4	El paquete <code>hyperref</code>	2	3.4.1	Llaves para <code>\spshort</code>	9
2	El comando <code>\setspintent</code>	3	3.4.2	Argumentos para <code>\spshort</code>	9
3	The big four	3	4	Utilidades generales	11
3.1	El comando <code>\spnum</code>	3	5	Utilidades para símbolos	11
3.1.1	Llaves para <code>\spnum</code>	3	6	Utilidades para números	13
3.2	El comando <code>\spunit</code>	4	7	Utilidades para geometría	17
3.2.1	Llaves para <code>\spunit</code>	4	8	Referencias	25
3.2.2	Argumentos para <code>\spunit</code>	4	9	Change history	26
3.2.3	El comando <code>\spnewunit</code>	6	10	Índice de la Documentación	27
3.2.4	El comando <code>\spunitalias</code>	6	11	Implementation	29
			12	Índice de la Implementación	135

Motivación y agradecimientos

Desde que desarrollé `scontents`[7] en 2019 y, más tarde, `enumext`[8] en 2024, me he ido interesando cada vez más por la accesibilidad en los documentos PDF. Al principio era un tema prácticamente desconocido para mí, pero a medida que fui aprendiendo sobre él comprendí la importancia que tiene, especialmente en el ámbito educativo.

El equipo del proyecto de $\TeX$ [19] ha realizado un trabajo extraordinario en este campo. Hoy es posible generar documentos etiquetados, validarlos con herramientas como `veraPDF`[20] o inspeccionar su estructura con `ngpdf`[21]. Sin embargo, siempre me quedó una duda: cuando un estudiante utiliza NVDA[11] junto con MathCAT[12], ¿realmente escucha lo que el o la docente quiso expresar?

Basta con generar un documento accesible siguiendo las recomendaciones de `The LaTeX Tagged PDF Project` y escucharlo con NVDA/MathCAT para darse cuenta de que, en muchos casos, la *verbalización* no coincide con lo que uno espera. Esto no resulta extraño: las reglas del español, y en particular el lenguaje matemático, dependen en gran medida del contexto en que se utilizan.

El objetivo de **spintent** nace precisamente de esta necesidad: proporcionar herramientas para que el o la docente pueda indicar explícitamente el contexto de determinadas expresiones matemáticas desde el propio código fuente de $\TeX$, de modo que el documento PDF resultante no solo sea *accesible*, sino que también produzca una *verbalización más natural* y adecuada para el estudiante al utilizar NVDA/MathCAT.

El nuevo estándar PDF 2.0[14, 18, 16], las especificaciones de WTPDF[15] y la guía más reciente de la PDF Association, «Best Practice Guide: Math in PDF»[17], coinciden en que el camino hacia una accesibilidad matemática de calidad pasa por el uso de MathML. En ese contexto, Lua[†] $\TeX$ ofrece una plataforma especialmente adecuada para incorporar esta tecnología.

*Este archivo describe la documentación para la versión v0.99 revisada por última vez el 2026-09-13.

[†]E-mail: «pablgonz@educarchile.cl».

Licencia y requerimientos

El paquete `spintent` carga y requiere el paquete `unicode-math`[1] y que se ejecute bajo Lua $\TeX$ por lo que es necesario contar con una distribución moderna de $\TeX$ como $\TeX$ Live 2026. Ha sido probado con las clases estándar proporcionadas por $\LaTeX$: `book`, `report`, `article` y `letter` en tamaños `10pt`, `11pt` y `12pt`.

Se otorga permiso para copiar, distribuir y/o modificar este paquete bajo los términos de $\LaTeX$ Project Public License (LPPL), versión 1.3 o posterior (<https://www.latex-project.org/lppl.txt>). El paquete tiene la condición de mantenido al estilo «*A Work in Progress*»¹.

- El requerimiento mínimo es $\LaTeX$ release 2026-11-01.

Este paquete solo se puede utilizar solo con Lua $\TeX$ y *tagged* PDF activo. Está presente en $\TeX$ Live y MiK $\TeX$, para instalarlo, utilice el gestor de paquetes de su distribución. Si desea una instalación manual, descargue `spintent.zip` y descomprímalo, luego ejecute `luatex spintent.ins`, mueva todos los archivos a las ubicaciones correspondientes y luego ejecute `mktexlsr`. Para generar la documentación, ejecute `arara spintent.dtx`.

```
spintent.sty  ⇒ TDS:tex/luatex/spintent/
spintent.lua  ⇒ TDS:tex/luatex/spintent/
spintent.pdf  ⇒ TDS:doc/luatex/spintent/
README.md    ⇒ TDS:doc/luatex/spintent/
spintent.dtx  ⇒ TDS:source/luatex/spintent/
spintent.ins  ⇒ TDS:source/luatex/spintent/
```

1 Descripción

El nombre `spintent` puede entenderse como «*Spanish Parse Intent*» o también como «*School Parse Intent*». Ambas interpretaciones reflejan el objetivo del paquete y el público para el que fue diseñado: docentes de educación primaria y secundaria.

Está pensado para crear «*apuntes*», «*hojas de ejercicios*», «*clases escritas*» enfocadas en el estudiante. Solo un docente sabe cual es el nivel de aprendizaje del estudiante. El paquete intenta sobrescribir muchas de las reglas dictadas por la heurística de NVDA/MathCAT teniendo esto presente.

- El paquete `spintent` usa y abusa del atributo `:intent` de MathML por medio del comando `\MathMLintent` definido en `latex-lab-mathintent`[30], un encapsulado de `\luamml_attribute:een` proveída por `luamml`[2]. ¡Gracias Marcel!

1.1 Carga del paquete

El paquete `spintent` trabaja solo con Lua $\TeX$ y *tagged* PDF activo usando `tagging=on` dentro del comando `\DocumentMetadata` al inicio del archivo. Las llaves («*keys*») aceptadas por `\DocumentMetadata` y en general para el código de *tagged* PDF están documentadas en los paquetes y `tagpdf`[29] `documentmetadata-support`[30], es deber del usuario revisar la documentación asociada a ellos.

```
\DocumentMetadata
{
  lang=es-CL,
  pdfversion=2.0,
  pdfstandard=ua-2,
  tagging=on,
  tagging-setup={math/setup={mathml-SE}},
}
\documentclass{article}
\usepackage[spanish]{babel}
\usepackage{spintent}
```

1.2 El paquete babel

El paquete `babel-spanish`[10] está marcado como «parcialmente compatible» para *tagged* PDF, pero, es absolutamente necesario para la creación de documentos en español. En caso de encontrar problemas de compatibilidad con otros paquetes se puede desactivar usando:

```
\usepackage[spanish,shorthands=off]{babel}
```

Muchas de las «shorthands» proveídas por `babel-spanish` hoy no son necesarias, más allá de `\sptext` para las abreviaturas y ordinales el resto son solo atajos de teclas para escritura que hoy en día no se ocupan. El paquete `spintent` provee el comando `\spshort` (§3.4) que cubre estos casos, de esta manera podemos cargar `babel`[9] con todas sus funcionalidades sin problemas.

¹A *Work in Progress* es un álbum en vivo de Neil Peart (* 1952–† 2020), baterista y principal letrista de Rush. El nombre no pretende formar parte de la terminología de la LPPL; simplemente describe el estado permanente de este paquete mientras sigo aprendiendo sobre *accesibilidad* en PDF.

1.3 Fuentes tipográficas

Como `spintent` es un paquete Lua $\TeX$ debemos distinguir entre las fuentes tipográficas OpenType/TrueType versus las fuentes de 8bit estándar usadas por $\TeX$ para el *modo texto* y el *modo matemático*. Para evitar problemas con *tagged* PDF preferiremos no combinar fuentes OpenType/TrueType con fuentes 8bit y trabajaremos solo con fuentes OpenType/TrueType que tengan soporte para matemáticas.

La carga de las fuentes tipográficas para Lua $\TeX$ se maneja por medio del paquete `fontspec`[3], si no se especifica ninguna se usarán las fuentes Latin Modern para el *modo texto* y Latin Modern Math para el *modo matemático*.

El tipo de fuente tipográfica escogida es preferencia de cada usuario, en lo personal utilizo las fuente Libertinus para el *modo texto* por medio del paquete `libertinus-otf`[4] y la fuente Erewhon-Math para el modo matemático cargada por el paquete `fourier-otf`[5]. Adicionalmente cargo la fuente Source Code Pro para el texto tipo «máquina de escribir» por medio del paquete `sourcecodepro`[6].

```
% \DocumentMetadata{...}
\documentclass{article}
\usepackage[spanish]{babel}
\usepackage[osf,nomath,mono=false]{libertinus-otf}
\usepackage[osf,semibold]{sourcecodepro}
\usepackage[no-text]{fourier-otf}
\usepackage{spintent}
```

1.4 El paquete hyperref

El paquete `hyperref`[23] es «casi obligatorio» cuando se crean documentos *tagged* PDF, se encarga de las referencias cruzadas `\label` y `\ref`, las notas al pie `\footnote`, los hipervínculos `\href` y muchos otros elementos como marcadores, índices y metadatos.

```
\DocumentMetadata
{
  lang=es-CL,
  pdfversion=2.0,
  pdfstandard=ua-2,
  tagging=on,
  tagging-setup={math/setup={mathml-SE}},
}
\documentclass{article}
\usepackage[spanish]{babel}
\usepackage[osf,nomath,mono=false]{libertinus-otf}
\usepackage[osf,semibold]{sourcecodepro}
\usepackage[no-text]{fourier-otf}
\setmathfont{Erewhon-Math}[range={cal,bfcal},StylisticSet=1]
\usepackage{spintent, hyperref}
\hypersetup
{
  colorlinks      = true,
  pdfstartview    = FitH,
  pdfdisplaydoctitle = true,
  pdftitle        = {Test para el paquete spintent},
  pdfinfo         =
  {
    Title   = {Test},
    Subject = {spintent},
  },
}
```

2 El comando \setspintent

`\setspintent` `\setspintent{⟨comando⟩}{⟨key-uno = valor, key-dos = valor, key-tres = valor, ...⟩}`

El comando `\setspintent` establece las llaves (*⟨keys⟩*) de forma global para los comandos provistos por `spintent`. Puede utilizarse tanto en el preámbulo como en el cuerpo del documento tantas veces como se desee. Las llaves (*⟨keys⟩*) definidas en el *argumento opcional* [*⟨key = val⟩*] de los comandos tienen prioridad sobre las establecidas por este, anulando las configuraciones globales de `\setspintent`.

Muchas de las utilidades que provee el paquete `spintent` implementan el sistema [*⟨key = val⟩*] y están pensadas para ser utilizadas en la generación de «*hojas de ejercicios*» o «*clases escritas*». Se recomienda usar `\setspintent` y establecerlas de manera global para cada documento, para mantener la coherencia en la verbalización de NVDA/MathCAT a lo largo del mismo.

El sistema [*⟨key = val⟩*] utilizado por `spintent` se implementa usando el módulo `l3keys` de `expl3`[24]. Por diseño, las llaves que reciben un *valor* después del signo '=' NO aceptan *valores vacíos* y es obligatorio pasar uno valido; las llaves documentadas como *⟨valor prohibido⟩* no reciben *ningun valor*. En caso de omitir un *valor* valido o pasar un *valor vacío* a una llave que acepte *valor* o pasar un *valor* a una llave del tipo *⟨valor prohibido⟩* se devolverá un "error" y se detendrá la compilación del documento.

3 The big four

El paquete `spintent` provee cuatro grandes comandos («*the big four*²»): `\spnum` para el manejo de números, `\spunit` para el manejo de unidades, `\spmoney` para el manejo de dinero y `\spshort` para el manejo de abreviaturas, acrónimos y números ordinales.

- También se incluyen las utilidades `\spnewunit` y `\spunitalias` asociadas a al comando `\spunit`.

3.1 El comando \spnum

`\spnum` `\spnum{⟨número⟩}` `\spnum[⟨key = val⟩]{⟨número,número;número⟩}`
`\spnum[⟨key = val⟩]{⟨+número⟩}` `\spnum[⟨key = val⟩]{⟨número.número;número⟩}`
`\spnum[⟨key = val⟩]{⟨-número⟩}` `\spnum[⟨key = val⟩]{⟨número;número⟩}`
`\spnum[⟨key = val⟩]{⟨número,número⟩}` `\spnum[⟨key = val⟩]{⟨número e exponente⟩}`
`\spnum[⟨key = val⟩]{⟨número.número⟩}` `\spnum[⟨key = val⟩]{⟨número E exponente⟩}`

El comando `\spnum` trabaja en *modo matemático* y recibe el *argumento obligatorio* {*⟨número⟩*}, donde la «*parte entera*» puede iniciar con los signos '+' o '-', la «*parte decimal finita*» **debe** iniciar con una coma ',' o con un punto '.', y la «*parte decimal infinita (periódica)*» **debe** iniciar con un punto y coma '; '.

Si no se proporciona el *argumento opcional* [*⟨key = val⟩*] y se ejecuta `\spnum{+23}` se imprimirá '+23' en la salida PDF y NVDA/MathCAT verbalizará «*más veintitrés*», si se ejecuta `\spnum{3,14}` se imprimirá '3,14' en la salida PDF y NVDA/MathCAT verbalizará «*tres coma catorce*», si se ejecuta `\spnum{3,1;4}` se imprimirá '3,14' en la salida PDF y NVDA/MathCAT verbalizará «*tres coma uno con cuatro periódico*».

Además, el *argumento obligatorio* {*⟨número⟩*} admite al final de este un sufijo de «*notación científica*». Este se indica mediante las letras 'e' o 'E', acompañadas de los signos opcionales '+' o '-' seguido por los dígitos del exponente. Por ejemplo `\spnum{3,14e3}` imprimirá '3,14 · 10³' en la salida PDF y NVDA/MathCAT verbalizará «*tres coma catorce por diez al cubo*».

- La coma ',' o el punto '.' son *separadores decimales* y NO de millares, por lo tanto solo pueden aparecer una «única vez» dentro del {*⟨argumento⟩*}. El {*⟨argumento⟩*} puede contener espacios matemáticos validos, pero, NO puede contener comandos con o sin argumentos como `\textstyle`, `\mathrm{#1}` o `\mathbf{#1}` por ejemplo. Cualquier entrada fuera de esta sintaxis devolverá un "error" deteniendo la compilación del documento.

3.1.1 Llaves para \spnum

`cifras-sep = {⟨true | false⟩}`

default: *true*

Establece el *espaciado* utilizado para agrupar los dígitos en bloques de tres, tanto en la parte entera como en la parte decimal finita. Si se establece en *true* se siguen las normas de la RAE y se utiliza un *espacio fino* '\,' entre las cifras; si se establece en *false*, se respetan los espacios matemáticos introducidos en el argumento. Por ejemplo `\spnum{100000}` imprimirá '100 000' en la salida PDF y `\spnum[cifras-sep=false]{10\,00\,00}` imprimirá '10 00 00' en la salida PDF.

`read-sign = {⟨terse | clear⟩}`

default: *terse*

Establece la *forma* en la que NVDA/MathCAT verbalizará los signos '+' o '-'. Si se establece en *terse*, NVDA/MathCAT verbalizará «*más*» o «*menos*» **antes** de leer el número; si se establece en *clear*, NVDA/MathCAT verbalizará «*positivo*» o «*negativo*» **después** de leer el número. Por ejemplo `\spnum{-23}` imprimirá '-23' en la salida PDF y NVDA/MathCAT verbalizará «*menos veintitrés*» y `\spnum[read-sign=clear]{-23}` imprimirá '-23' en la salida PDF y NVDA/MathCAT verbalizará «*veintitrés negativo*».

`read-period-sep = {⟨coma | punto⟩}`

default: *coma*

²Los «*cuatro grandes*» del Thrash Metal: Metallica, Megadeth, Slayer y Anthrax, que me acompañan mientras desarrollo `spintent`.

Establece la *forma* en la que NVDA/MathCAT verbalizará e imprimirá el signo de separación ‘;’ de la «*parte decimal infinita (periódica)*» cuando no se tiene la «*parte decimal finita*». Si se establece en *coma*, se imprimirá ‘,’ en la salida PDF y NVDA/MathCAT verbalizará «*coma*»; si se establece en *punto*, se imprimirá ‘.’ en la salida PDF y NVDA/MathCAT verbalizará «*punto*». Por ejemplo `\spnum{3;4}` imprimirá ‘3,4’ en la salida PDF y NVDA/MathCAT verbalizará «*tres coma cuatro periódico*» y `\spnum[read-period-sep=punto]{3;4}` imprimirá ‘3.4’ en la salida PDF y NVDA/MathCAT verbalizará «*tres punto cuatro periódico*»

- Esta llave es necesaria SOLO cuando se utilizan «*decimales periódicos puros*», es decir, cuando no se ha incluido en el `{(argumento)}` una *coma* ‘,’ o un *punto* ‘.’ antes del signo de separación ‘;’ periódica.

`notation-sym = {(times | cdot)}`

default: *cdot*

Establece el *símbolo* que se utilizará para imprimir la «*notación científica*» al usar ‘e’ o ‘E’. Si se establece en *times* imprimirá ‘×’ en la salida PDF y NVDA/MathCAT verbalizará «*por*»; si se establece en *cdot* imprimirá ‘·’ en la salida PDF y NVDA/MathCAT verbalizará «*por*». Por ejemplo `\spnum{3,14e3}` imprimirá ‘3,14 · 10³’ en la salida PDF y NVDA/MathCAT verbalizará «*tres coma catorce por diez al cubo*» y `\spnum[notation-sym=times]{3,14e3}` imprimirá ‘3,14 × 10³’ en la salida PDF y NVDA/MathCAT verbalizará «*tres coma catorce por diez al cubo*».

- Decir «*notación científica*» aquí es un poco exagerado, en realidad es «*multiplicación por potencias de 10*», no se verifica si la entrada cumple o no con la condición de estar escrita en «*notación científica*».

3.2 El comando \spunit

<code>\spunit{(unidad)}</code>	<code>\spunit[key = val]{(número unidad*unidad)}</code>
<code>\spunit[key = val]{(unidad)}</code>	<code>\spunit[key = val]{(número unidad*unidad/unidad)}</code>
<code>\spunit[key = val]{(número unidad)}</code>	<code>\spunit[key = val]{(número unidad*unidad/unidad*unidad)}</code>

El comando `\spunit` trabaja en *modo matemático* y recibe el *argumento obligatorio* `{(unidad)}`, el cual puede contener una «*parte numérica*» opcional la cual se procesa internamente por el comando `\spnum` al inicio del `{(argumento)}` seguido de una `{(unidad)}` o un `{(alias)}` valido descritos en §3.2.2 o una `{(unidad)}` creada por el comando `\spnewunit` (§3.2.3) o un `{(alias)}` creado por el comando `\spunitalias` (§3.2.4).

Si no se proporciona el *argumento opcional* `[key = val]` y se ejecuta `\spunit{23 m}` se imprimirá ‘23 m’ en la salida PDF y NVDA/MathCAT verbalizará «*veintitrés metros*».

La multiplicación entre las `{(unidades)}` se realiza mediante un *asterisco* ‘*’ y las potencias de estas se indican con un *circunflejo seguido del exponente entre llaves* ‘^`{(exponente)}`’. Por ejemplo si se ejecuta `\spunit{23 m*s^2}` se imprimirá ‘23 m s²’ en la salida PDF y NVDA/MathCAT verbalizará «*veintitrés metros segundos al cuadrado*».

Se pueden usar *fracciones lineales* con las `{(unidades)}` utilizando una «*única barra* ‘/’ para la separación entre las `{(unidades)}` del numerador y el denominador, teniendo presente que el denominador NO puede contener números de ningún tipo. Por ejemplo si se ejecuta `\spunit{23 m/s^2}` se imprimirá ‘23 m/s²’ en la salida PDF y NVDA/MathCAT verbalizará «*veintitrés metros por segundos al cuadrado*».

- Solo imprimiremos *fracciones lineales*, si se requiere otra forma fraccionaria para explicaciones y otros usos se debe usar el comando por separado. El `{(argumento)}` puede contener espacios matemáticos validos, pero, NO puede contener comandos con o sin argumentos como `\textstyle`, `\mathrm{#1}` o `\mathbf{#1}` por ejemplo, NO puede contener más de una «*única barra* ‘/’ y NO puede contener números en el denominador. Cualquier entrada fuera de esta sintaxis devolverá un “error” deteniendo la compilación del documento.

3.2.1 Llaves para \spunit

El comando `\spunit` posee las *meta-keys* `cifras-sep`, `read-period-sep` y `notation-sym` pasadas al comando `\spnum` (§3.1.1).

`print-cdot = {(true | false)}`

default: *false*

Establece si se *imprime* `\cdot` ‘·’ o un *espacio fino* ‘\,’ para la multiplicación de `{(unidades)}`. Si se establece en *true*, se imprimirá ‘·’ entre las `{(unidades)}` en la salida PDF; si se establece en *false* se imprimirá un *espacio fino* ‘\,’ entre las `{(unidades)}` en la salida PDF.

`read-cdot = {(true | false)}`

default: *false*

Establece la *forma* en la que NVDA/MathCAT verbalizará la multiplicación de `{(unidades)}`. Si se establece en *true*, NVDA/MathCAT verbalizará «*por*» entre las `{(unidades)}`; si se establece en *false*, NVDA/MathCAT no verbalizará nada entre las `{(unidades)}`.

`read-slash = {(por | partido-por)}`

default: *por*

Establece la *forma* en la que NVDA/MathCAT verbalizará la «*barra* ‘/’ de separación entre el numerador y el denominador. Si se establece en *por*, NVDA/MathCAT verbalizará «*por*»; si se establece en *partido-por*, NVDA/MathCAT verbalizará «*partido por*».

3.2.2 Argumentos para \spunit

Resumen de `{(unidades)}` y `{(alias)}` soportados por `\spunit`.

Entrada	Alias soportados	Nombre unidad	Salida	NVDA/MathCAT
m	metro, metros	Metro	m	«metro»
g	gramo, gramos	Gramo	g	«gramo»
s	segundo, segundos	Segundo (Tiempo)	s	«segundo (Tiempo)»
l	litro, l-litro	Litro (minúscula)	l	«litro (minúscula)»
h	hora, horas	Hora	h	«hora»
d	dia, dias	Día	d	«día»
A	amperio, ampere	Amperio	A	«amperio»
V	voltio, volt	Voltio	V	«voltio»
W	vatio, watt	Vatio	W	«vatio»
J	julio, joule	Julio	J	«julio»
N	newton	Newton	N	«newton»
Pa	pascal	Pascal	Pa	«pascal»
Hz	hercio, hertz	Hercio	Hz	«hercio»
Ω	ohmio, ohm, Omega	Ohmio	Ω	«Ohmio»
F	faradio	Faradio	F	«Faradio»
C	culombio	Culombio	C	«Culombio»
K	kelvin, Kelvin	Kelvin	K	«Kelvin»
°C	celsius, degC, °C	Grados Celsius	°C	«Grados Celsius»
°F	fahrenheit, degF, °F	Grados Fahrenheit	°F	«Grados Fahrenheit»
cal	caloria, calorías	Caloría	cal	«Caloría»
b	bit	Bit	b	«Bit»
B	byte, bytes	Byte	B	«Byte»
in	pulgada, pulgadas	Pulgada	in	«Pulgada»
ft	pie, pies	Pie	ft	«Pie»
yd	yarda, yardas	Yarda	yd	«Yarda»
mi	milla, millas	Milla	mi	«Milla»
lb	libra, libras	Libra	lb	«Libra»
oz	onza, onzas	Onza	oz	«Onza»
gal	galon, galones	Galón	gal	«Galón»
Å	angstrom	Angstrom	Å	«Angstrom»
μ	micro	Micro (Prefijo)	μ	«Micro (Prefijo)»
Ω	mho	Mho / Siemens	Ω	«Mho / Siemens»
'	minmin	Minuto (Arco)	'	«Minuto (Arco)»
"	segseg	Segundo (Arco)	"	«Segundo (Arco)»
u	u-masa	Unidad masa atómica	u	«Unidad masa atómica»

Unidades directas (sin alias):

L	-	Litro (Mayúscula)	L	«Litro (Mayúscula)»
ℓ	-	Litro (Cursiva)	ℓ	«Litro (Cursiva)»
w	-	Vatio (Minúscula)	w	«Vatio (Minúscula)»
°K	-	Grado Kelvin	°K	«Grado Kelvin»
Bq	-	Becquerel	Bq	«Becquerel»
Da	-	Dalton	Da	«Dalton»
Gy	-	Gray	Gy	«Gray»
S	-	Siemens	S	«Siemens»
Sv	-	Sievert	Sv	«Sievert»
T	-	Tesla	T	«Tesla»
Wb	-	Weber	Wb	«Weber»
atm	-	Atmósfera	atm	«Atmósfera»
au	-	Unidad astronómica	au	«Unidad astronómica»
bar	-	Bar	bar	«Bar»
cd	-	Candela	cd	«Candela»
dB	-	Decibelio	dB	«Decibelio»
dyn	-	Dina	dyn	«Dina»
eV	-	Electronvoltio	eV	«Electronvoltio»
erg	-	Ergio	erg	«Ergio»
ha	-	Hectárea	ha	«Hectárea»
kat	-	Katal	kat	«Katal»
kg	-	Kilogramo	kg	«Kilogramo»
km	-	Kilómetro	km	«Kilómetro»
lm	-	Lumen	lm	«Lumen»

Continúa en la siguiente página...

Continuación de la tabla 1

Entrada	Alias soportados	Nombre unidad	Salida	MathCAT
lx	-	Lux	lx	« <i>Lux</i> »
cm	-	Centímetro	cm	« <i>Centímetro</i> »
min	-	Minuto (Tiempo)	min	« <i>Minuto (Tiempo)</i> »
mm	-	Milímetro	mm	« <i>Milímetro</i> »
mol	-	Mol	mol	« <i>Mol</i> »
pc	-	Pársec	pc	« <i>Pársec</i> »
rad	-	Radián	rad	« <i>Radián</i> »
rpm	-	Rev. por minuto	rpm	« <i>Rev. por minuto</i> »
sr	-	Estereorradián	sr	« <i>Estereorradián</i> »
t	-	Tonelada	t	« <i>Tonelada</i> »
a	-	Año / Área (are)	a	« <i>Año / Área (are)</i> »
y	-	Año (Year)	y	« <i>Año (Year)</i> »
°	-	Grado (Arco)	°	« <i>Grado (Arco)</i> »

3.2.3 El comando \spnewunit

```
\spnewunit \spnewunit{\nueva unidad}\{verbalización NVDA}
```

El comando `\spnewunit` trabaja en *modo texto* y recibe dos *argumentos obligatorios*: $\langle\textit{nueva unidad}\rangle$ que establece lo que se imprimirá en la salida PDF y $\langle\textit{verbalización NVDA}\rangle$ que establece como NVDA/MathCAT verbalizará la $\langle\textit{nueva unidad}\rangle$.

La `{\nueva unidad}` no debe estar registrada como `{\unidad}` o `{\alias}` para `\spunit` descritos en §3.2.2. Si la `{\nueva unidad}` ya está registrada se devolverá un “error” y se detendrá la compilación del documento.

La declaración de la $\{\langle\textit{nueva unidad}\rangle\}$ es «global» y se almacena en el módulo `spintent.lua` como una $\{\langle\textit{unidad}\rangle\}$ válida para pasar como $\{\langle\textit{argumento}\rangle\}$ a `\spunit`. Por ejemplo: `\spnewunit{px}{píxeles}` creará la $\{\langle\textit{nueva unidad}\rangle\}$ ‘px’ y cuando se utilice `\spunit{100 px}` se imprimirá ‘100 px’ en la salida PDF y NVDA/MathCAT verbalizará «cien píxeles».

3.2.4 El comando \spunitalias

`\spunitalias \spunitalias{⟨nuevo alias⟩}{⟨expresión de unidades⟩}`

El comando `\spunitalias` trabaja en *modo texto* y recibe dos *argumentos obligatorios*: $\{\langle \text{nuevo alias} \rangle\}$ que establece es el nuevo $\{\langle \text{alias} \rangle\}$ de $\{\langle \text{argumento} \rangle\}$ para `\spunit` y $\{\langle \text{expresión de unidades} \rangle\}$ que puede contener multiplicación o división de $\{\langle \text{unidades} \rangle\}$ ya registradas que se imprimirán en la salida PDF.

El `{\nuevo alias}` no debe estar registrado como `{\unidad}` o `{\alias}` para `\spunit` descritos en §3.2.2 o estar definido como `{\unidad}` por medio del comando `\spnewunit`. Si el `{\nuevo alias}` ya está registrado se devolverá un “error” y se detendrá la compilación del documento.

La declaración de un `{\nuevo alias}` es «global» y se almacena en el módulo `spintent`. Lua como una `{\alias}` valido para pasar como `{\argumento}` a `\spunit`. Por ejemplo: `\spunitalias{caudal}{m^3/s}` creará el `{\alias}` ‘caudal’ y cuando se utilice `\spunit{50 caudal}` se imprimirá ‘50 m³/s’ en la salida PDF y NVDA/MathCAT verbalizará «cincuenta metros al cubo por segundos».

3.3 El comando \spmoney

<code>\spmoney</code>	<code>\spmoney{< cifra >}</code>
	<code>\spmoney{< cifra moneda >}</code>
	<code>\spmoney[< key = val >]{< cifra moneda >}</code>

El comando `\spmoney` trabaja en *modo matemático* y recibe el *argumento obligatorio* $\{ \langle \text{cifra} \rangle \}$ que contiene la «cifra numérica» positiva o negativa la se cual procesa internamente por el comando `\sprnum` al inicio del $\{ \langle \text{argumento} \rangle \}$ acompañada de un «símbolo de moneda» o «alias de moneda» opcional descritos en §3.3.2.

Si no se proporciona el *argumento opcional* `[key = val]` y se ejecuta `\$ \spmoney{500} \$` se imprimirá ‘\$500’ en la salida PDF y NVDA/MathCAT verbalizará «quinientos pesos».

- El comportamiento de `\spmoney` depende de como se pase el *argumento obligatorio* que tiene prioridad por sobre los valores por defecto. Por ejemplo: `\$ \spmoney{500 dolares}` imprimirá ‘\$500’ en la salida PDF y NVDA/MathCAT verbalizará «*quinientos dolares*» aunque la moneda por defecto sean pesos.

Si se pasa un «*alias de moneda*» del tipo ISO (código de divisas) como CLP o USD (mayúsculas) se modifica la verbalización en NVDA/MathCAT agregando el país y se ajusta la salida PDF al estandar ISO. Por ejemplo: $\$ \spmone{500} \text{ CLP}$ imprimirá ‘CLP500’ en la salida PDF y NVDA/MathCAT verbalizará «*quinientos pesos chilenos*».

Si se pasa un «alias de moneda» del tipo ISO (código de divisas) como `clp` o `usd` (minúsculas) se modifica la verbalización en **NVDA/MathCAT** agregando el país, pero, NO se modifica la salida PDF imprimiendo el

«*símbolo de moneda*» correspondiente. Por ejemplo: `\$ \spmoney{500 c\p}` imprimirá '\$500' en la salida PDF y NVDA/MathCAT verbalizará «quinientos pesos chilenos»

Pasar de manera directa en el *argumento obligatorio* un «*símbolo de moneda*» como '\$', '€', '£' o un «*alias de moneda*» como peso, euro o libra produce la salida PDF y verbalización estándar esperada para NVDA/MathCAT.

- La posición del «*símbolo de moneda*» a la izquierda o a la derecha de la «*cifra numérica*» y la verbalización para NVDA/MathCAT se manejan desde el módulo Lua `spintent.lua` y no se proveen llaves para modificar este comportamiento.
- El «*símbolo de moneda*» es tomado de la fuente tipográfica definida para el *modo matemático* al momento de ejecutar el comando, se debe tener presente en caso de querer usar un «*símbolo de moneda*» poco habitual que esté soportada por `spintent`. El `{(argumento)}` puede contener espacios matemáticos válidos, pero, NO puede contener comandos con o sin argumentos como `\textstyle`, `\mathrm{#1}` o `\mathbf{#1}` por ejemplo. La coma ',' o el punto '.' como *separador decimal* solo pueden aparecer una «única vez». Cualquier entrada fuera de esta sintaxis devolverá un "error" deteniendo la compilación del documento.

3.3.1 Llaves para \spmoney

El comando `\spmoney` posee la *meta-key* `cifras-sep` pasada al comando `\spnum` (§3.1.1).

`currency = {(moneda | alias)}`

default: peso

Establece el *símbolo de moneda* por defecto que se imprimirá en la salida PDF y cómo lo verbalizará NVDA/MathCAT cuando SOLO se pasa una «*cifra numérica*» como `{(argumento)}` al comando `\spmoney`. El «*símbolo de moneda*» o el «*alias de moneda*» pasado a esta llave debe ser alguno de los descritos en §3.3.2.

`sub-units = {(true | false)}`

default: false

Establece si se usarán *subunidades* de la moneda en curso para la verbalización en NVDA/MathCAT. La moneda en curso debe aceptar *subunidades*. Por ejemplo: `\$ \spmoney[sub-units=true]{100,5 dolares}` imprimirá '\$100,5' en la salida PDF y NVDA/MathCAT verbalizará «*cient dólares con cincuenta centavos*».

`dolar-math = {(true | false)}`

default: true

Establece si el *símbolo* '\$' se imprimirá en *modo texto* o en *modo matemático*. Si se establece en `true`, se usará la fuente tipográfica definida para el *modo matemático* en curso para imprimir '\$' en la salida PDF; si se establece en `false`, se usará la fuente tipográfica definida para el *modo texto* para imprimir '\$' en la salida PDF.

3.3.2 Monedas y alias para \spmoney

Resumen de los `{(símbolos de moneda)}` y `{(alias de moneda)}` soportados como `{(argumento)}` para `\spmoney`.

3.4 El comando \spshort

`\spshort {(abreviaturas | acrónimos | números ordinales)}`
`\spshort[key = val]{(abreviaturas | acrónimos | números ordinales)}`
`\spshort[read-arg={verbalización del argumento para NVDA}]{(comandos LATEX)}`

El comando `\spshort` trabaja *solo en modo texto* y recibe un *argumento obligatorio* del tipo `{(abreviaturas)}`, `{(acrónimos)}` o `{(números ordinales)}` descritos en §3.4.2.

Si no se proporciona el *argumento opcional* `[key = val]` y se ejecuta `\spshort{dr. a}` se imprimirá 'Dr.^a' en la salida PDF y NVDA/MathCAT verbalizará «*doctora*»; si se ejecuta `\spshort{onu}` se imprimirá 'ONU' en la salida PDF y NVDA/MathCAT verbalizará «*organización de las naciones unidas*» y si se ejecuta `\spshort{mineduc}` se imprimirá 'Mineduc' en la salida PDF y NVDA/MathCAT verbalizará «*ministerio de educación*».

Para la escritura de `{(números ordinales)}` se puede ejecutar `\spshort{1. a}` que imprimirá '1.^a' en la salida PDF y NVDA/MathCAT verbalizará «*primera*»; si se ejecuta `\spshort{1. o}` imprimirá '1.^o' en la salida PDF y NVDA/MathCAT verbalizará «*primero*».

Para crear una nueva `{(abreviatura)}`, `{(acrónimo)}` o `{(número ordinal)}` que no se encuentre registrada por `spintent` dentro del módulo Lua `spintent.lua` descritas en §3.4.2 se debe utilizar la llave `read-arg` y definir esta dentro del *argumento obligatorio* que puede contener `{(comandos LATEX)}` en *modo texto* los cuales se imprimirán en salida PDF.

- Para la escritura de `{(números ordinales)}` se debe tener cuidado y no confundir la «*letra o voladita*» 'o' con el símbolo de grado '°'. Si la fuente tipográfica del *modo texto* está utilizando `Numbers=OldStyle` los números pueden quedar muy separados de la «*letra voladita*», la solución para esto es agregar `\addfontfeatures{Numbers=Lining}` dentro de un grupo junto al comando: `{\addfontfeatures{Numbers=Lining}\spshort{1. o}}`.
- El comando `\spshort` está pensado como un reemplazo para *shorthands* y el comando `\sptext` provistos por el paquete `babel` en español compatible con *tagged* PDF. Es de las pocas utilidades que provee el paquete `spintent` que trabaja *solo en modo texto*. Internamente utiliza la llave `E` (*expansion text*) proveída por el paquete `tagpdf`[29].

Entrada	Alias	Nombre	Salida	NVDA/MathCAT
\$	peso, pesos	peso	\$	«peso / pesos»
€	euro, euros	euro	€	«euro / euros»
£	libra, libras	libra	£	«libra / libras»
¥	yen, yenes	yen	¥	«yen / yenes»
¥	yuan, yuanes	yuan	¥	«yuan / yuanes»
₩	won, wons	won	₩	«won / wons»
₪	shekel, shekels, sequel, sequeles	séquel	₪	«séquel / séqueles»
₹	rupia, rupias	rupia	₹	«rupia / rupias»
₽	rublo, rublos	rublo	₽	«rublo / rublos»
₺	lira, liras	lira	₺	«lira / liras»
₴	grivna, grivnas	grivna	₴	«grivna / grivnas»
¢	centavo, centavos	centavo	¢	«centavo / centavos»

Divisas en formato ISO (Mayúsculas)

CLP	—	peso chileno	CLP	«peso chileno / pesos chilenos»
MXN	—	peso mexicano	MXN	«peso mexicano / pesos mexicanos»
USD	—	dólar	USD	«dólar estadounidense / dólares estadounidenses»
EUR	—	euro	EUR	«euro / euros»
GBP	—	libra	GBP	«libra / libras»
JPY	—	yen	JPY	«yen / yenes»
CNY	—	yuan	CNY	«yuan / yuanes»
KRW	—	won	KRW	«won / wons»
ILS	—	séquel	ILS	«séquel / séqueles»
INR	—	rupia	INR	«rupia / rupias»
RUB	—	rublo	RUB	«rublo / rublos»
TRY	—	lira	TRY	«lira / liras»
UAH	—	grivna	UAH	«grivna / grivnas»

Códigos ISO en minúsculas

clp	—	peso chileno	\$	«peso chileno / pesos chilenos»
mxn	—	peso mexicano	\$	«peso mexicano / pesos mexicanos»
usd	dolar, dolares	dólar	\$	«dólar estadounidense / dólares estadounidenses»
eur	—	euro	€	«euro / euros»
gbp	—	libra	£	«libra / libras»
jpy	—	yen	¥	«yen / yenes»
cny	—	yuan	¥	«yuan / yuanes»
krw	—	won	₩	«won / wons»
ils	—	séquel	₪	«séquel / séqueles»
inr	—	rupia	₹	«rupia / rupias»
rub	—	rublo	₽	«rublo / rublos»
try	—	lira	₺	«lira / liras»
uah	—	grivna	₴	«grivna / grivnas»

3.4.1 Llaves para \spshort

`read-arg = {⟨verbalización NVDA⟩}` default: no usado

Establece la verbalización del argumento {⟨comandos $\LaTeX$ ⟩} de la nueva {⟨abreviatura⟩}, {⟨acrónimo⟩} o {⟨número ordinal⟩} para NVDA. El valor de esta llave siempre debe pasarse entre '{ }'. Por ejemplo: `\spshort[read-arg={octavo}]{8.\textsuperscript{\emph{avo}}}` creará una nueva {⟨abreviatura⟩} que imprimirá '8.^{avo}' en la salida PDF y NVDA verbalizará «octavo».

`small-caps = {⟨true | false⟩}` default: false

Establece si se usarán versalitas para imprimir {⟨acrónimos⟩} y para la «letra volada» en {⟨abreviaturas⟩} y {⟨números ordinales⟩} respetando las reglas de la RAE para el uso de estas. Si se establece en `true`, las abreviaturas con mayúscula como EE. UU. y los acrónimos de cinco o más letras como Unicef no se verán afectados; si se establece en `false`, no se aplicarán versalitas. Por ejemplo: `\spshort[small-caps=true]{dr.a}` imprimirá 'Dr.^a' en la salida PDF y NVDA verbalizará «doctora».

3.4.2 Argumentos para \spshort

El cuadro 2 resume las abreviaturas, expresiones latinas y títulos registrados en el módulo Lua `spintent.lua`.

Cuadro 2: Abreviaturas soportadas

Entrada	Alias / Variantes	Salida PDF	Lectura NVDA
Abreviaturas con letras voladas			
dr.a	dr. ^a	Dr. ^a	«doctora»
dr.as	—	Dr. ^{as}	«doctoras»
prof.a	—	Prof. ^a	«profesora»
d.a	d. ^a	D. ^a	«doña»
m.a	—	M. ^a	«maría»
n.o	n. ^o	N. ^o	«número»
n.os	—	N. ^{os}	«números»
c.ia	—	C. ^{ia}	«compañía»
Abreviaturas comunes y expresiones latinas			
pág.	pag.	pág.	«página»
vol.	—	vol.	«volumen»
etc.	—	etc.	«etcétera»
et al.	et. al.	et al.	«y otros»
ibíd.	ibíd.	ibíd.	«ibídem»
op. cit.	op.cit.	op. cit.	«obra citada»
loc. cit.	loc.cit.	loc. cit.	«lugar citado»
v. gr.	v.gr.	v. gr.	«verbigracia»
i. e.	i.e.	i. e.	«esto es»
e. g.	e.g.	e. g.	«por ejemplo»
p. ej.	p.ej.	p. ej.	«por ejemplo»
Títulos, profesiones y cargos			
sr.	—	Sr.	«señor»
sra.	—	Sra.	«señora»
srta.	—	Srta.	«señorita»
dr.	—	Dr.	«doctor»
dra.	—	Dra.	«doctora»
dres.	—	Dres.	«doctores»
dras.	—	Dras.	«doctoras»
prof.	—	Prof.	«profesor»
profa.	—	Profa.	«profesora»
profs.	—	Profs.	«profesores»
ing.	—	Ing.	«ingeniero»
ings.	—	Ings.	«ingenieros»
lic.	—	Lic.	«licenciado»
v. b.	v.b.	V. B.	«visto bueno»
Abreviaturas compuestas e institucionales			
s. a.	s.a.	S. A.	«sociedad anónima»
ee. uu.	ee.uu.	EE. UU.	«estados unidos»
dd. hh.	dd.hh.	DD. HH.	«derechos humanos»
jj. oo.	jj.oo.	JJ. OO.	«juegos olímpicos»

Continúa en la siguiente página...

Cuadro 2: (Continuación - Abreviaturas soportadas)

Entrada	Alias / Variantes	Salida PDF	Lectura NVDA
ff. aa.	ff.aa.	FF. AA.	«fuerzas armadas»
rr. ee.	rr.ee.	RR. EE.	«relaciones exteriores»
cc. aa.	cc.aa.	CC. AA.	«comunidades autónomas»
p. d.	p.d.	P. D.	«posdata»
a. c.	a.c.	a. C.	«antes de Cristo»
d. c.	d.c.	d. C.	«después de Cristo»
d. n. i.	d.n.i.	D. N. I.	«documento nacional de identidad»
r. u. t.	r.u.t.	R. U. T.	«rol único tributario»
r. u. n.	r.u.n.	R. U. N.	«rol único nacional»

El cuadro 3 detalla las siglas y acrónimos registrados en el módulo Lua `spintent.lua`.

Cuadro 3: Siglas y acrónimos soportados

Entrada	Alias / Variantes	Salida PDF	Lectura NVDA
Siglas (Deletreo o lectura expandida)			
dni	—	DNI	«documento nacional de identidad»
rut	—	RUT	«rol único tributario»
run	—	RUN	«rol único nacional»
onu	—	ONU	«organización de las naciones unidas»
rae	—	RAE	«real academia española»
ong	ongs	ONG	«organización no gubernamental»
urss	—	URSS	«unión de repúblicas socialistas soviéticas»
oea	—	OEA	«organización de los estados americanos»
oms	—	OMS	«organización mundial de la salud»
fmi	—	FMI	«fondo monetario internacional»
bid	—	BID	«banco interamericano de desarrollo»
otan	—	OTAN	«organización del tratado del atlántico norte»
ue	—	UE	«unión europea»
ru	—	RU	«reino unido»
Acrónimos silábicos			
unicef	—	Unicef	«fondo de las naciones unidas para la infancia»
unesco	—	Unesco	«organización de las naciones unidas para la educación, la ciencia y la cultura»
mercosur	—	Mercosur	«mercado común del sur»
cepal	—	Cepal	«comisión económica para américa latina»
mineduc	—	Mineduc	«ministerio de educación»
conicet	—	Conicet	«consejo nacional de investigaciones»

El cuadro 4 muestra ejemplos de números ordinales registrados en el módulo Lua `spintent.lua`.

Cuadro 4: Números ordinales soportados

Entrada	Alias / Variantes	Salida PDF	Lectura NVDA
Sufijos para ordinales (Ejemplos)			
1.a	1. ^a	1. ^a	«primera»
2.o	2. ^o	2. ^o	«segundo»
3.er	—	3. ^{er}	«tercer»
4.os	—	4. ^{os}	«cuartos»
5.as	—	5. ^{as}	«quintas»

4 Utilidades generales

Además de los «cuatro grandes» y sus asociados, el paquete **spintent** provee tres utilidades de uso general: `\spsiglo` para la escritura y lectura de siglos, `\sptime` para la escritura y lectura de tiempo y `\spdate` para la escritura y lectura de fechas.

El comando `\spsiglo`

`\spsiglo`

`\spsiglo{⟨siglo⟩}`
`\spsiglo[⟨key = val⟩]{⟨siglo⟩}`

El comando `\spsiglo` trabaja en *modo texto* y en *modo matemático*, recibe el *argumento obligatorio* `{⟨siglo⟩}`, el cual puede ser un *número arábigo* ‘21’ o un *número romano* ‘XXI’ mayor que ‘0’ y menor que ‘4000’.

Si no se proporciona el *argumento opcional* `[⟨key = val⟩]` y se ejecuta `\spsiglo{21}` o `\spsiglo{XXI}` se imprimirá ‘xxi’ en la salida PDF y NVDA/MathCAT verbalizará «veintiuno».

- El *argumento obligatorio* `{⟨siglo⟩}` «siempre» es convertido a *número romano en versalitas* y es verbalizado por NVDA/MathCAT como *número arábigo*. Esta es la única utilidad que provee el paquete **spintent** que trabaja en *modo texto* y en *modo matemático*. Internamente utiliza la llave `alt` proveída por el paquete **tagpdf** en *modo texto* y usa `\MathMLintent` para el *modo matemático*.

Llaves para `\spsiglo`

`print-era = {⟨ac | dc | none⟩}`

default: none

Establece si se *imprime* o no la abreviatura después de imprimir el argumento `{⟨siglo⟩}`. Si se establece en `ac`, `\spsiglo[print-era=ac]{XXI}` imprimirá ‘xī a. C.’ en la salida PDF y NVDA/MathCAT verbalizará «veintiuno antes de cristo»; si se establece en `dc`, `\spsiglo[print-era=dc]{XXI}` imprimirá ‘xī d. C.’ en la salida PDF y NVDA/MathCAT verbalizará «veintiuno después de cristo»; si se establece en `none`, `\spsiglo[print-era=none]{XXI}` imprimirá ‘xī’ en la salida PDF y NVDA/MathCAT verbalizará «veintiuno».

El comando `\sptime`

`\sptime`

`\sptime{⟨horas : minutos⟩}`
`\sptime{⟨horas : minutos : segundos⟩}`

El comando `\sptime` trabaja en *modo matemático* y recibe el *argumento obligatorio* `{⟨horas : minutos⟩}` o `{⟨horas : minutos : segundos⟩}`. Por ejemplo: `$\sptime{23:45}$` imprimirá ‘23:45’ en *modo texto* la salida PDF y NVDA/MathCAT verbalizará «las veintitrés y cuarenta y cinco minutos».

El comando `\spdate`

`\spdate`

`\spdate{⟨DD/ MM/YYYY⟩}`
`\spdate{⟨YYYY/ MM/DD⟩}`

`\spdate{⟨DD- MM-YYYY⟩}`
`\spdate{⟨YYYY- MM-DD⟩}`

El comando `\spdate` trabaja en *modo matemático* y recibe el *argumento obligatorio* `{⟨DD/MM/YYYY⟩}`, `{⟨DD-MM-YYYY⟩}` o `{⟨YYYY-MM-DD⟩}`. Por ejemplo: `$\spdate{1981-01-02}$` y `$\spdate{02/01/1981}$` imprimirán en *modo texto* la salida PDF ‘1981-01-02’ y ‘02/01/1981’ respectivamente y en ambos casos, NVDA/MathCAT verbalizará «dos de enero de mil novecientos ochenta y uno».

- Si se pasa el argumento `{⟨YYYY/MM/DD⟩}`, internamente se convertirá en `{⟨DD/MM/YYYY⟩}` y se imprimirá de esa forma por compatibilidad con NVDA/MathCAT.

5 Utilidades para símbolos

El paquete **spintent** provee tres comandos `\spread`, `\spdsym` y `\spmsym` para trabajar con «símbolos matemáticos» descritos en esta sección. Están pensando desde el punto de vista docente, para situaciones donde la lectura de un «símbolo» (acorde al contexto) es relevante.

- A diferencia de las otras utilidades implementados por **spintent** (que analizan y dan formato a la salida), estos no procesan los «símbolos matemáticos», solo afectan la *forma* (semántica) en que serán verbalizados por NVDA/MathCAT.

El comando `\spread`

`\spread`

`\spread{⟨verbalización NVDA⟩}{⟨símbolo matemático⟩}`

El comando `\spread` trabaja en *modo matemático* y recibe dos *argumentos obligatorios*: El primer *argumento* `{⟨verbalización NVDA⟩}` establece la «forma» en la cual NVDA/MathCAT verbalizará al segundo *argumento* `{⟨símbolo matemático⟩}`. Por ejemplo: `$\spread{es-paralela}{\parallel}$` imprimirá ‘||’ en la salida PDF y NVDA/MathCAT verbalizará «es paralela»; `$\spread{es-paralelo}{\parallel}$` imprimirá ‘||’ en la salida PDF y NVDA/MathCAT verbalizará «es paralelo».

El comando `\spusep`

```
\spusep <separador>
\spusep[<key = val>]{<separador>}
```

El comando `\spusep` trabaja en *modo matemático* y recibe el *argumento obligatorio* `{<separador>}`, el cual debe ser uno de los «*delimitadores*» soportados: ‘(’, ‘)’, ‘[’, ‘]’, ‘{’, ‘}’ o ‘\’. Imprime el *delimitador* indicado con el tamaño establecido por la llave `size` y controla si NVDA/MathCAT lo verbaliza o no mediante la llave `silent`.

Si no se proporciona el *argumento opcional* `[<key = val>]`, `$\spusep{< >}` imprimirá ‘(’ en la salida PDF y NVDA/MathCAT verbalizará «*paréntesis izquierdo*».

- El motivo de existencia de `\spusep` es que los comandos `\left`, `\right`, `\Uleft` y `\Uright` provistos por LuaTeX crean un *grupo* implícito que dificulta el código para *tagged* PDF cuando se necesita interrumpir algo entre ellos, por ejemplo al construir expresiones complejas con `\spnZ`, `\spmQ` o `\spdiv`. El comando `\spusep` imprime el *delimitador* sin crear ningún grupo.

Llaves para `\spusep`

```
size = {<none | big | Big | bigg | Bigg>} default: none
```

Establece el *tamaño* del `{<delimitador>}` que se imprimirá en la salida PDF. Los valores corresponden a los cuatro tamaños fijos provistos por L^AT_EX: si se establece en `none`, el `{<delimitador>}` se imprime en el tamaño por defecto del modo matemático en curso; si se establece en `big`, se usa `\bigl/\bigr`; si se establece en `Big`, se usa `\Bigl/\Bigr`; si se establece en `bigg`, se usa `\biggl/\biggr`; y si se establece en `Bigg`, se usa `\Biggl/\Biggr`. El tamaño se aplica automáticamente en el lado correcto (izquierdo o derecho) según el `{<delimitador>}` pasado.

```
silent = {<true | false>} default: false
```

Establece si NVDA/MathCAT verbalizará el `{<delimitador>}` impreso por `\spusep`. Si se establece en `true`, el `{<delimitador>}` se marcará con el *intent* `:silent` y NVDA/MathCAT no lo verbalizará; si se establece en `false`, NVDA/MathCAT verbalizará el `{<delimitador>}` de forma normal.

El comando `\spdsym`

```
\spdsym
\spdsym[<key = val>]
```

El comando `\spdsym` trabaja en *modo matemático* y recibe el *argumento opcional* `[<key = val>]` mediante el cual se establece la «*forma*» en la que se imprimirá el *símbolo de división* y como se verbalizará en NVDA/MathCAT.

Si no se proporciona el *argumento opcional* `[<key = val>]`, `$\spdsym$` imprimirá ‘÷’ en la salida PDF y NVDA/MathCAT verbalizará «*dividido*».

Llaves para `\spdsym`

```
prefix = {<prefijo>} default: no usado
```

Establece el *prefijo* que será verbalizado por NVDA/MathCAT «*antes*» de verbalizar el `{<valor>}` establecido por la llave `read-sym`. El valor de esta llave *siempre* debe pasarse entre llaves ‘{ }’.

```
suffix = {<sufijo>} default: no usado
```

Establece el *sufijo* que será verbalizado por NVDA/MathCAT «*después*» de verbalizar el `{<valor>}` establecido por la llave `read-sym`. El valor de esta llave *siempre* debe pasarse entre llaves ‘{ }’.

```
set-sym = {<old-style | two-dots | slash>} default: two-dots
```

Establece el *símbolo de división* que se imprimirá en la salida PDF. Si se establece en `old-style`, imprimirá ‘÷’; si se establece en `two-dots`, imprimirá ‘⋮’ y si se establece `slash`, imprimirá ‘/’.

```
read-sym = {<dividido | dividido-por | dividido-entre>} default: dividido
```

Establece la *forma* con la cual NVDA/MathCAT verbalizará el *símbolo de división*. Si se establece en `dividido`, NVDA/MathCAT verbalizará «*dividido*»; si se establece en `dividido-por`, NVDA/MathCAT verbalizará «*dividido por*» y si se establece en `dividido-entre`, NVDA/MathCAT verbalizará «*dividido entre*».

El comando `\spmsym`

```
\spmsym
\spmsym[<key = val>]
```

El comando `\spmsym` trabaja en *modo matemático* y recibe el *argumento opcional* `[<key = val>]` mediante el cual se establece la «*forma*» en la que se imprimirá el *símbolo de multiplicación* y como se verbalizará en NVDA/MathCAT.

Si no se proporciona el *argumento opcional* `[<key = val>]`, `$\spmsym$` imprimirá ‘⋅’ en la salida PDF y NVDA/MathCAT verbalizará «*por*».

Llaves para `\spmsym`

`prefix = {\langle prefijo \rangle}` default: no usado

Establece el *prefijo* que será verbalizado por NVDA/MathCAT «antes» de verbalizar el `\{ \langle valor \rangle \}` establecido por la llave `read-sym`. El valor de esta llave *siempre* debe pasarse entre llaves `{ }`.

`suffix = {\langle sufijo \rangle}` default: no usado

Establece el *sufijo* que será verbalizado por NVDA/MathCAT «después» de verbalizar el `\{ \langle valor \rangle \}` establecido por la llave `read-sym`. El valor de esta llave *siempre* debe pasarse entre llaves `{ }`.

`set-sym = {\langle cross | dot | asterisk \rangle}` default: dot

Establece el *símbolo de multiplicación* que se imprimirá en la salida PDF. Si se establece en `cross`, imprimirá `×`; si se establece en `dot`, imprimirá `·` y si se establece en `asterisk`, imprimirá `*`.

`read-sym = {\langle por | multiplicado-por | veces \rangle}` default: por

Establece la *forma* con la cual NVDA/MathCAT verbalizará el *símbolo de multiplicación*. Si se establece en `por`, NVDA/MathCAT verbalizará «por»; si se establece en `multiplicado-por`, NVDA/MathCAT verbalizará «multiplicado por» y si se establece en `veces`, NVDA/MathCAT verbalizará «veces».

`not-print = {\langle true | false \rangle}` default: false

Deshabilita la *impresión* del *símbolo de multiplicación*. Cuando se establece esta llave, NVDA/MathCAT verbalizará el *símbolo de multiplicación* acorde al valor establecido por la llave `read-sym`, pero, no se imprimirá este en la salida PDF.

6 Utilidades para números

El paquete `spintent` provee utilidades para trabajar con números descritas en esta sección.

El comando `\spdiv`

`\spdiv` `\spdiv{\langle dividendo \rangle}{\langle divisor \rangle}`
`\spdiv[\langle key = val \rangle]{\langle dividendo \rangle}{\langle divisor \rangle}`

El comando `\spdiv` trabaja en *modo matemático* y recibe dos *argumentos obligatorios* `\{ \langle dividendo \rangle \}` y `\{ \langle divisor \rangle \}`.

Si no se proporciona el *argumento opcional* `[\langle key = val \rangle]`, `\$ \spdiv{20}{26} \$` imprimirá `20 : 26` en la salida PDF y NVDA/MathCAT verbalizará «veinte dividido veinte y seis»

Llaves para `\spdiv`

El comando `\spdiv` posee las *meta-keys* `cifras-sep`, `read-sign`, `read-period-sep` y `notation-sym` pasadas al comando `\spnum` (§3.1.1) junto a las *meta-keys* `set-sym` y `read-sym` pasadas al comando `\spmsym` (pág. 12).

`wrap-parens = {\langle true | false \rangle}` default: false

Establece si se *imprimen* paréntesis redondos `(...)` alrededor de los *argumentos* `\{ \langle dividendo \rangle \}` y `\{ \langle divisor \rangle \}` pasados a `\spdiv`. Si se establece en `true`, se imprimirán paréntesis redondos alrededor de ambos *argumentos*; si se establece en `false`, no se imprimirán los paréntesis.

`read-parens = {\langle true | false \rangle}` default: true

Establece si NVDA/MathCAT verbalizará los paréntesis redondos `(...)` alrededor de los *argumentos* `\{ \langle dividendo \rangle \}` y `\{ \langle divisor \rangle \}` pasados a `\spdiv`. Si se establece en `true`, NVDA/MathCAT verbalizará la lectura de los paréntesis; si se establece en `false`, NVDA/MathCAT no los verbalizará.

El comando `\spmul`

`\spmul` `\spmul{\langle factor \rangle}{\langle factor \rangle}`
`\spmul[\langle key = val \rangle]{\langle factor \rangle}{\langle factor \rangle}`

El comando `\spmul` trabaja en *modo matemático* y recibe dos *argumentos obligatorios* `\{ \langle factor \rangle \}` y `\{ \langle factor \rangle \}`.

Si no se proporciona el *argumento opcional* `[\langle key = val \rangle]`, `\$ \spmul{20}{26} \$` imprimirá `20 · 26` en la salida PDF y NVDA/MathCAT verbalizará «veinte por veinte y seis».

Llaves para `\spmul`

El comando `\spmul` posee las *meta-keys* `cifras-sep`, `read-sign`, `read-period-sep` y `notation-sym` pasadas al comando `\spnum` (§3.1.1) junto a las *meta-keys* `set-sym` y `read-sym` pasadas al comando `\spmsym` (pág. 13).

`wrap-parens = {\langle true | false \rangle}` default: false

Establece si se *imprimen* paréntesis redondos `(...)` alrededor de los *argumentos* `\{ \langle factor \rangle \}` y `\{ \langle factor \rangle \}` pasados a `\spmul`. Si se establece en `true`, se imprimirán paréntesis redondos alrededor de ambos *argumentos*; si se establece en `false`, no se imprimirán los paréntesis.

`read-parens = {\langle true | false \rangle}` default: true

Establece si NVDA/MathCAT verbalizará los paréntesis redondos ‘(…)’ alrededor de los *argumentos* $\{ \langle \textit{factor} \rangle \}$ y $\{ \langle \textit{factor} \rangle \}$ pasados a `\spmul`. Si se establece en `true`, NVDA/MathCAT verbalizará la lectura de los paréntesis; si se establece en `false`, NVDA/MathCAT no los verbalizará.

El comando `\spnD`

```
\spnD \spnD
\spnD(\<número natural>)
\spnD[key = val](\<número natural>)
```

El comando `\spnD` trabaja en *modo matemático* y recibe el *argumento delimitado por paréntesis* $(\langle \textit{número natural} \rangle)$, por ejemplo: ‘(6)’. Si se usa sin $(\langle \textit{argumento} \rangle)$, `\spnD` imprimirá ‘D(*n*)’ en la salida PDF y NVDA/MathCAT verbalizará «divisores de *n*».

Si se usa con $(\langle \textit{argumento} \rangle)$, por ejemplo, `\spnD(6)`, imprimirá ‘D(6)’ en la salida PDF y NVDA/MathCAT verbalizará «divisores de seis».

Llaves para `\spnD`

`prefix = { \<prefijo> }` default: no usado

Establece el *prefijo* que será verbalizado por NVDA/MathCAT «antes» de verbalizar `\spnD(\<argumento>)`. El valor de esta llave *siempre* debe pasarse entre llaves ‘{ }’.

`result = { \<true | false> }` default: false

Establece si se *imprime* el resultado de calcular los *divisores* del $(\langle \textit{número natural} \rangle)$ pasado a `\spnD`. Si se establece en `true`, `\spnD[result=true](6)` imprimirá ‘D(6) = {1, 2, 3, 6}’ en la salida PDF y NVDA/MathCAT verbalizará «los divisores de seis son uno, dos, tres y seis»; si se establece en `false`, no se imprimirá en la salida PDF el resultado de calcular los *divisores*.

`result-num = { \<número natural> }` default: 5

Establece la *cantidad* de números que se mostrarán en la salida PDF al activar `result=true`. Si se establece en `2`, solo se imprimirán dos valores en la salida PDF; si no se establece, se imprimirán como máximo `5` valores y luego se añadirá ‘...’ en la salida PDF.

`sample-arg = { \<true | false> }` default: false

Desactiva la *validación* interna del $(\langle \textit{argumento} \rangle)$ pasado a `\spnD`, permitiendo usar ejemplos «no numéricos» como entrada. Si se establece en `true`, `\spnD[sample-arg=true](m)` imprimirá ‘D(*m*)’ en la salida PDF y NVDA/MathCAT verbalizará «divisores de *m*»; si se establece en `false`, el $(\langle \textit{argumento} \rangle)$ debe ser un número natural, en caso contrario se devolverá un “error”.

`silent-cmd = { \<true | false> }` default: false

Establece si se *silencia* la verbalización para NVDA/MathCAT de `\spnD(\<argumento>)` cuando se establece `sample-arg=true` o cuando `\spnD` se usa sin $(\langle \textit{argumento} \rangle)$. Si se establece en `true` NVDA/MathCAT NO lo verbalizará; si se establece en `false`, NVDA/MathCAT SÍ lo verbalizará.

El comando `\spnM`

```
\spnM \spnM
\spnM(\<número natural>)
\spnM[key = val](\<número natural>)
```

El comando `\spnM` trabaja en *modo matemático* y recibe el *argumento delimitado por paréntesis* $(\langle \textit{número natural} \rangle)$, por ejemplo: ‘(6)’. Si se usa sin $(\langle \textit{argumento} \rangle)$, `\spnM` imprimirá ‘M(*n*)’ en la salida PDF y NVDA/MathCAT verbalizará «múltiplos de *n*».

Si se usa con $(\langle \textit{argumento} \rangle)$, por ejemplo, `\spnM(6)`, imprimirá ‘M(6)’ en la salida PDF y NVDA/MathCAT verbalizará «múltiplos de seis».

Llaves para `\spnM`

`prefix = { \<prefijo> }` default: no usado

Establece el *prefijo* que será verbalizado por NVDA/MathCAT «antes» de verbalizar `\spnM(\<argumento>)`. El valor de esta llave *siempre* debe pasarse entre llaves ‘{ }’.

`result = { \<true | false> }` default: false

Establece si se *imprime* el resultado de calcular los *múltiplos* del $(\langle \textit{número natural} \rangle)$ pasado a `\spnM`. Si se establece en `true`, `\spnM[result=true](6)` imprimirá ‘M(6) = {6, 12, 18, 24, 30, ...}’ en la salida PDF y NVDA/MathCAT verbalizará «los múltiplos de seis son seis, doce, dieciocho, veinticuatro, treinta puntos suspensivos»; si se establece en `false`, no se imprimirá en la salida PDF el resultado de calcular los *múltiplos*.

`result-num = { \<número natural> }` default: 5

Establece la *cantidad* de números que se mostrarán en la salida PDF al activar `result=true`. Si se establece en `2`, solo se imprimirán dos valores en la salida PDF seguidos de ‘...’; si no se establece, se imprimirán por defecto los `5` primeros valores y luego se añadirá ‘...’ en la salida PDF.

`sample-arg = { \<true | false> }` default: false

Desactiva la *validación* interna del (*argumento*) pasado a `\spnM`, permitiendo usar ejemplos «no numéricos» como entrada. Si se establece en `true`, `\spnM[sample-arg=true](m)` imprimirá ‘M(*m*)’ en la salida PDF y NVDA/MathCAT verbalizará «múltiplos de *m*»; si se establece en `false`, el (*argumento*) debe ser un número natural, en caso contrario se devolverá un “error”.

`silent-cmd = { (true | false) }`

default: `false`

Establece si se *silencia* la verbalización en NVDA/MathCAT de `\spnM`(*argumento*) cuando se establece `sample-arg=true` o cuando `\spnM` se usa sin (*argumento*). Si se establece en `true` NVDA/MathCAT NO lo verbalizará; si se establece en `false` NVDA/MathCAT lo verbalizará.

El comando `\spmc`

```
\spmc \spmc
\spmc( (números separados por coma) )
\spmc[ (key = val) ] ( (números separados por coma) )
```

El comando `\spmc` trabaja en *modo matemático* y recibe el *argumento delimitado por paréntesis* (*números separados por coma*), el cual debe ser una lista de *números naturales*, por ejemplo: ‘(2, 3, 6)’. Si se usa sin (*argumento*) `\spmc` imprimirá ‘mcd’ en la salida PDF, y NVDA/MathCAT verbalizará «máximo común divisor» o «*m c d*», acorde al {*valor*} establecido por la llave `read-cmd`.

Si se usa con (*argumento*) `\spmc(2, 3, 6)` imprimirá ‘mcd(2, 3, 6)’ en la salida PDF, y NVDA/MathCAT verbalizará «máximo común divisor entre dos, tres y seis» o «*m c d* entre dos, tres y seis» acorde al {*valor*} establecido por la llave `read-cmd`.

Llaves para `\spmc`

`upper-case = { (true | false) }`

default: `false`

Establece si se usarán *mayúsculas* o *minúsculas* en la salida PDF para el comando `\spmc`. Si se establece en `true`, se imprimirá ‘MCD’ en la salida PDF; si se establece en `false`, se imprimirá ‘mcd’ en la salida PDF.

`read-cmd = { (terse | clear) }`

default: `clear`

Establece la *forma* en la que NVDA/MathCAT verbalizará el comando `\spmc`. Si se establece en `terse`, NVDA/MathCAT verbalizará «*m c d*»; si se establece en `clear`, NVDA/MathCAT verbalizará «máximo común divisor».

`prefix = { (prefijo) }`

default: `no usado`

Establece el *prefijo* que será verbalizado por NVDA/MathCAT «antes» de verbalizar el valor establecido por la llave `read-cmd`. El valor de esta llave *siempre* debe pasarse entre llaves ‘{ }’.

`result = { (true | false) }`

default: `false`

Establece si se *imprime* el resultado de calcular el «máximo común divisor» del (*argumento*) pasado a `\spmc`. Si se establece en `true`: `\spmc[result=true](2, 3, 6)` imprimirá ‘mcd(2, 3, 6) = 1’ en la salida PDF y NVDA/MathCAT verbalizará «máximo común divisor entre dos, tres y seis es igual a uno»; si se establece en `false` no se imprimirá en la salida PDF el resultado de calcular el «máximo común divisor».

`sample-arg = { (true | false) }`

default: `false`

Desactiva la *validación* interna del (*argumento*) pasado a `\spmc`, permitiendo usar ejemplos «no numéricos» como entrada. Si se establece en `true`: `\spmc[sample-arg=true](m, n)`, imprimirá ‘mcd(*m*, *n*)’ en la salida PDF y NVDA/MathCAT verbalizará «máximo común divisor entre *m* y *n*»; si se establece en `false` el (*argumento*) debe ser una lista de *números naturales*, en caso contrario se devolverá un “error”.

`silent-cmd = { (true | false) }`

default: `false`

Establece si se *silencia* la verbalización en NVDA/MathCAT de `\spmc`(*argumento*) cuando se establece `sample-arg=true` o cuando `\spmc` se usa sin (*argumento*). Si se establece en `true` NVDA/MathCAT NO lo verbalizará; si se establece en `false`, NVDA/MathCAT SÍ lo verbalizará.

El comando `\spmc`

```
\spmc \spmc
\spmc( (números separados por coma) )
\spmc[ (key = val) ] ( (números separados por coma) )
```

El comando `\spmc` trabaja en *modo matemático* y recibe el *argumento delimitado por paréntesis* (*números separados por coma*), el cual debe ser una lista de *números naturales*, por ejemplo: ‘(2, 3, 6)’. Si se usa sin (*argumento*) `\spmc` imprimirá ‘mcm’ en la salida PDF, y NVDA/MathCAT verbalizará «mínimo común múltiplo» o «*m c m*», acorde al {*valor*} establecido por la llave `read-cmd`.

Si se usa con (*argumento*) `\spmc(2, 3, 6)` imprimirá ‘mcm(2, 3, 6)’ en la salida PDF, y NVDA/MathCAT verbalizará «mínimo común múltiplo entre dos, tres y seis» o «*m c m* entre dos, tres y seis» acorde al {*valor*} establecido por la llave `read-cmd`.

Llaves para `\spmc`

<code>upper-case = {⟨true false⟩}</code>	default: <i>false</i>
Establece si se usarán <i>mayúsculas</i> o <i>minúsculas</i> en la salida PDF para el comando <code>\spmc</code> . Si se establece en <i>true</i> se imprimirá ‘MCM’ en la salida PDF; si se establece en <i>false</i> se imprimirá ‘mcm’ en la salida PDF.	
<code>read-cmd = {⟨terse clear⟩}</code>	default: <i>clear</i>
Establece la <i>forma</i> en la que NVDA/MathCAT verbalizará el comando <code>\spmc</code> . Si se establece en <i>terse</i> , NVDA/MathCAT verbalizará « <i>m c m</i> »; si se establece en <i>clear</i> , NVDA/MathCAT verbalizará « <i>mínimo común múltiplo</i> ».	
<code>prefix = {⟨prefijo⟩}</code>	default: <i>no usado</i>
Establece el <i>prefijo</i> que será verbalizado por NVDA/MathCAT « <i>antes</i> » de verbalizar el valor establecido por la llave <code>read-cmd</code> . El valor de esta llave <i>siempre</i> debe pasarse entre llaves ‘{ }’.	
<code>result = {⟨true false⟩}</code>	default: <i>false</i>
Establece si se <i>imprime</i> el resultado de calcular el « <i>mínimo común múltiplo</i> » del (⟨ <i>argumento</i> ⟩) pasado a <code>\spmc</code> . Si se establece en <i>true</i> : <code>\$\spmc[result=true](2, 3, 6)\$</code> imprimirá ‘mcm(2, 3, 6) = 6’ en la salida PDF y NVDA/MathCAT verbalizará « <i>mínimo común múltiplo entre dos, tres y seis es igual a seis</i> »; si se establece en <i>false</i> no se imprimirá en la salida PDF el resultado de calcular el « <i>mínimo común múltiplo</i> ».	
<code>sample-arg = {⟨true false⟩}</code>	default: <i>false</i>
Desactiva la <i>validación</i> interna del (⟨ <i>argumento</i> ⟩) pasado a <code>\spmc</code> , permitiendo usar ejemplos « <i>no numéricos</i> » como entrada. Si se establece en <i>true</i> : <code>\$\spmc[sample-arg=true](m, n)\$</code> , imprimirá ‘mcm(<i>m</i> , <i>n</i>)’ en la salida PDF y NVDA/MathCAT verbalizará « <i>mínimo común múltiplo entre m y n</i> »; si se establece en <i>false</i> el (⟨ <i>argumento</i> ⟩) debe ser una lista de <i>números naturales</i> , en caso contrario se devolverá un “error”.	
<code>silent-cmd = {⟨true false⟩}</code>	default: <i>false</i>
Establece si se <i>silencia</i> la verbalización en NVDA/MathCAT de <code>\spmc(⟨argumento⟩)</code> cuando se establece <code>sample-arg=true</code> o cuando <code>\spmc</code> se usa sin (⟨ <i>argumento</i> ⟩). Si se establece en <i>true</i> NVDA/MathCAT NO lo verbalizará; si se establece en <i>false</i> NVDA/MathCAT SÍ lo verbalizará.	

El comando `\spnZ`

`\spnZ` `\spnZ{⟨número entero⟩}`
`\spnZ[⟨key = val⟩]{⟨número entero⟩}`

El comando `\spnZ` trabaja en *modo matemático* y recibe el *argumento* obligatorio {⟨*número entero*⟩} el cual se procesa internamente bajo el comando `\spnum`. Este comando está dedicado exclusivamente al manejo de «*números enteros*», y añade algunas utilidades prácticas para el demarcado e interacción con NVDA/MathCAT.

Llaves para `\spnZ`

El comando `\spnZ` posee las ⟨*meta-keys*⟩ *cifras-sep* y *read-sign* pasadas al comando `\spnum` (§3.1.1).

<code>wrap-parens = {⟨true false⟩}</code>	default: <i>false</i>
Establece si se <i>imprimen</i> paréntesis redondos ‘(…)’ alrededor del argumento {⟨ <i>número entero</i> ⟩} pasado a <code>\spnZ</code> . Si se establece en <i>true</i> , se imprimirán paréntesis redondos alrededor del {⟨ <i>número entero</i> ⟩}; si se establece en <i>false</i> , no se imprimirán los paréntesis.	
<code>read-parens = {⟨true false⟩}</code>	default: <i>false</i>
Establece si NVDA/MathCAT <i>verbalizará</i> los paréntesis redondos ‘(…)’ alrededor del <i>argumento</i> {⟨ <i>número entero</i> ⟩} pasado a <code>\spnZ</code> . Si se establece en <i>true</i> , NVDA/MathCAT verbalizará la lectura del paréntesis ‘(…)’; si se establece en <i>false</i> , NVDA/MathCAT no los verbalizará.	

El comando `\spmQ`

`\spmQ` `\spmQ{⟨número entero⟩}{⟨numerador⟩}{⟨denominador⟩}`
`\spmQ[⟨key = val⟩]{⟨número entero⟩}{⟨numerador⟩}{⟨denominador⟩}`

El comando `\spmQ` trabaja en *modo matemático* y recibe *tres argumentos obligatorios*: {⟨*número entero*⟩}, {⟨*numerador*⟩} y {⟨*denominador*⟩}, los procesa internamente y devuelve un «*número mixto*».

Si no se proporciona el *argumento opcional* [⟨*key = val*⟩], `$\spmQ{2}{5}{7}$` imprimirá ‘2⁵/₇’ en la salida PDF y NVDA/MathCAT verbalizará «*dos y cinco séptimos*».

- En el caso de las fracciones, y en especial con los «*números mixtos*», no se pueden manejar muchas cosas desde el lado de *spintent*. Por ejemplo, la entrada `$3\frac{5}{7}$` con *tagged* PDF se verbaliza por NVDA/MathCAT como «*tres más cinco séptimos*», lo cual no está mal, pero pedagógicamente hablando no es del todo correcto.

Llaves para `\spmQ`

`join-word = {⟨entero | enteros | y⟩}`

default: `y`

Establece la *forma* en la que NVDA/MathCAT verbaliza la conexión entre el entero y la fracción que forman el *número mixto*. Si se establece en `entero`, al usar `\spmQ[join-word=entero]{1}{5}{7}` imprimirá $1\frac{5}{7}$ en la salida PDF, y NVDA/MathCAT verbalizará «un entero cinco séptimos»; si se establece en `enteros`, al usar `\spmQ[join-word=enteros]{2}{5}{7}` imprimirá $2\frac{5}{7}$ en la salida PDF, y NVDA/MathCAT verbalizará «dos enteros cinco séptimos»; si se establece en `y`, al usar `\spmQ[join-word=y]{2}{5}{7}` imprimirá $2\frac{5}{7}$ en la salida PDF, y NVDA/MathCAT verbalizará «dos y cinco séptimos».

`use-spnZ = {⟨true | false⟩}`

default: `true`

Establece si el `{⟨numerador⟩}` y el `{⟨denominador⟩}` que forman la fracción del *número mixto* se procesan internamente bajo el comando `\spnZ`, añadiendo así *semántica de entero* en la estructura MathML de la salida PDF. Si se establece en `true`, `{⟨numerador⟩}` y `{⟨denominador⟩}` se pasarán a `\spnZ` y NVDA/MathCAT los verbalizará correctamente como *números ordinales*; si se establece en `false`, los argumentos se tipografían directamente sin procesamiento semántico adicional.

`print-dfrac = {⟨true | false⟩}`

default: `false`

Establece si la fracción del *número mixto* se imprime usando `\dfrac` en lugar de `\frac`. Si se establece en `true`, al usar `\spmQ[print-dfrac=true]{2}{5}{7}` imprimirá la fracción en tamaño *display* $2\frac{5}{7}$ en la salida PDF; si se establece en `false`, la fracción se imprime con `\frac` siguiendo el tamaño matemático del contexto en curso.

`wrap-parens = {⟨true | false⟩}`

default: `false`

Establece si se *imprimen* paréntesis redondos ‘(...)’ alrededor del *número mixto* completo devuelto por `\spmQ`. Si se establece en `true`, se imprimirán paréntesis redondos cuyo tamaño se ajusta automáticamente al estilo matemático en curso; si se establece en `false`, no se imprimirán los paréntesis.

`read-parens = {⟨true | false⟩}`

default: `true`

Establece si NVDA/MathCAT verbalizará los paréntesis redondos ‘(...)’ alrededor del *número mixto* cuando la llave `wrap-parens` está activa. Si se establece en `true`, NVDA/MathCAT verbalizará la lectura de los paréntesis; si se establece en `false`, NVDA/MathCAT no los verbalizará.

7 Utilidades para geometría

El paquete `spintent` provee comandos para trabajar con los objetos y medidas de la *geometría plana* descritos en esta sección. Todos los comandos trabajan en *modo matemático* y comparten el mismo módulo `spintent.lua` para construir la verbalización correcta.

- Todos los comandos de esta sección aceptan como puntos solo *letras mayúsculas* como base, con modificadores opcionales de subíndice ‘`_{\dots}`’ o prima ‘`’`’. La única excepción es `\sprecta` cuando el *argumento* es de la forma `{⟨letra⟩}`, que acepta *letras minúsculas*. Los subíndices siempre deben escribirse de la forma correcta usando `_{\dots}` como `A_{\dots}` y nunca como `A_n` sin llaves que funciona solo por coincidencia.

El comando `\spPoint`

`\spPoint {⟨punto⟩}`

`\spPoint [⟨key = val⟩] {⟨punto⟩}`

El comando `\spPoint` trabaja en *modo matemático* y recibe el *argumento obligatorio* `{⟨punto⟩}` el cual es una *única letra mayúscula* con un modificador opcional de subíndice ‘`_{\dots}`’ o prima ‘`’`’.

Si no se proporciona el *argumento opcional* `[⟨key = val⟩]`, `\spPoint{A}` imprimirá ‘A’ en la salida PDF y NVDA/MathCAT verbalizará «punto A»; `\spPoint{A_{1}}` imprimirá ‘A₁’ y verbalizará «punto A sub uno».

- El comando `\spPoint` solo acepta *un punto*. Para pares o listas de puntos (rectas, rayos, lados, ángulos, arcos, polígonos), véanse los comandos correspondientes de esta sección.

Llaves para `\spPoint`

`read-cmd = {⟨school | mathcat⟩}`

default: `school`

Establece la *forma* en la que NVDA/MathCAT verbalizará el argumento `{⟨punto⟩}`. Si se establece en `school`, NVDA/MathCAT verbalizará el argumento `{⟨punto⟩}` sin el prefijo «mayúscula», `\spPoint{A}` se verbaliza «punto A»; si se establece en `mathcat`, NVDA/MathCAT aplica sus propias reglas, que pueden incluir el prefijo «mayúscula» dependiendo de la configuración del usuario.

`prefix = {⟨prefijo⟩}`

default: `no usado`

Establece el *prefijo* que será verbalizado por NVDA/MathCAT *antes* de verbalizar el término «punto». El valor de esta llave *siempre* debe pasarse entre llaves ‘`{ }`’.

`concept = {⟨true | false⟩}`

default: `true`

Establece si se *silencia* la verbalización en NVDA/MathCAT del concepto «punto» al ejecutar el comando sin modificar la impresión de este. Si se establece en `true`, NVDA/MathCAT verbalizará el concepto; si se establece en `false`, NVDA/MathCAT solo verbalizará el `{⟨argumento⟩}` acorde al valor establecido por la llave `read-cmd`.

`silent-cmd = { <punto | false> }`

default: `false`

Establece si se *silencia* la verbalización en NVDA/MathCAT del concepto «punto» y del {<argumento>} pasado al comando sin modificar la impresión de este. Si se establece en `true`, NVDA/MathCAT NO verbalizará la salida del comando; si se establece en `false`, NVDA/MathCAT sí verbalizará la salida del comando.

El comando `\sprecta`

`\sprecta`

`\sprecta{<punto, punto>}`

`\sprecta{<letra>}`

`\sprecta[<key = val>]{<punto, punto>}`

`\sprecta[<key = val>]{<letra>}`

El comando `\sprecta` trabaja en *modo matemático* y recibe un *argumento obligatorio* el cual puede ser de la forma {<letra>} o {<punto, punto>}. Si el *argumento* es de la forma {<punto, punto>} se aplica `\overleftrightharrow` en la impresión; si el *argumento* no contiene coma y es de la forma {<letra>} (mayúscula o minúscula), se imprimirá solo la {<letra>} sin aplicar `\overleftrightharrow`.

Si no se proporciona el *argumento opcional* [`<key = val>`], `\sprecta{AB}` imprimirá $\overleftrightarrow{AB}$ en la salida PDF y NVDA/MathCAT verbalizará «recta A B»; `\sprecta{m}` imprimirá m en la salida PDF y NVDA/MathCAT verbalizará «recta m».

Llaves para `\sprecta`

`read-cmd = { <school | mathcat> }`

default: `school`

Establece la *forma* en la que NVDA/MathCAT verbalizará el argumento {<punto, punto>} y el argumento {<letra>} cuando está en mayúscula. Si se establece en `school`, NVDA/MathCAT verbaliza las letras del argumento sin el prefijo «mayúscula»: `\sprecta{AB}` se verbaliza «recta A B»; si se establece en `mathcat`, NVDA/MathCAT aplica sus propias reglas, que pueden incluir el prefijo «mayúscula» dependiendo de la configuración del usuario.

`prefix = { <prefijo> }`

default: `no usado`

Establece el *prefijo* que será verbalizado por NVDA/MathCAT *antes* de verbalizar el concepto «recta». El valor de esta llave *siempre* debe pasarse entre llaves '{ }'.

`concept = { <true | false> }`

default: `true`

Establece si se *silencia* la verbalización en NVDA/MathCAT del concepto «recta» al ejecutar el comando sin modificar la impresión de este. Si se establece en `true`, NVDA/MathCAT verbalizará el concepto; si se establece en `false`, NVDA/MathCAT solo verbalizará el {<argumento>} acorde al valor establecido por la llave `read-cmd`.

`silent-cmd = { <true | false> }`

default: `false`

Establece si se *silencia* la verbalización en NVDA/MathCAT del concepto «recta» y del {<argumento>} pasado al comando sin modificar la impresión de este. Si se establece en `true`, NVDA/MathCAT NO verbalizará la salida del comando; si se establece en `false`, NVDA/MathCAT sí verbalizará la salida del comando.

El comando `\sprayo`

`\sprayo`

`\sprayo{<punto, punto>}`

`\sprayo[<key = val>]{<punto, punto>}`

El comando `\sprayo` trabaja en *modo matemático* y recibe el *argumento obligatorio* {<punto, punto>}. Representa un *rayo* o *semirrecta* con origen en el primer punto y dirección hacia el segundo, aplicando `\overrightarrow` en la impresión.

Si no se proporciona el *argumento opcional* [`<key = val>`], `\sprayo{AB}` imprimirá $\overrightarrow{AB}$ en la salida PDF y NVDA/MathCAT verbalizará «rayo A B».

Llaves para `\sprayo`

`read-cmd = { <school | mathcat> }`

default: `school`

Establece la *forma* en la que NVDA/MathCAT verbalizará el argumento {<punto, punto>}. Si se establece en `school`, NVDA/MathCAT verbaliza las letras del argumento sin el prefijo «mayúscula»: `\sprayo{AB}` se verbaliza «rayo A B»; si se establece en `mathcat`, NVDA/MathCAT aplica sus propias reglas, que pueden incluir el prefijo «mayúscula» dependiendo de la configuración del usuario.

`read-sty = { <rayo | semirrecta> }`

default: `rayo`

Establece el *concepto* que verbalizará NVDA/MathCAT el ejecutar el comando sin modificar la impresión de este. Si se utiliza `\sprayo[read-sty=rayo]{AB}`, NVDA/MathCAT verbalizará «rayo A B»; si se utiliza `\sprayo[read-sty=semirrecta]{AB}`, NVDA/MathCAT verbalizará «semirrecta A B».

`prefix = { <prefijo> }`

default: `no usado`

Establece el *prefijo* que será verbalizado por NVDA/MathCAT *antes* de verbalizar el «concepto» establecido por la llave `read-sty`. El valor de esta llave *siempre* debe pasarse entre llaves '{ }'.

`concept = { <true | false> }`

default: `true`

Establece si se *silencia* la verbalización en NVDA/MathCAT del «concepto» establecido por la llave `read-sty` al ejecutar el comando sin modificar la impresión de este. Si se establece en `true`, NVDA/MathCAT verbalizará el

concepto; si se establece en `false`, NVDA/MathCAT solo verbalizará el $\{\langle \text{argumento} \rangle\}$ acorde al valor establecido por la llave `read-cmd`.

`silent-cmd` = $\{\langle \text{true} \mid \text{false} \rangle\}$ default: `false`

Establece si se *silencia* la verbalización en NVDA/MathCAT del «concepto» establecido por la llave `read-sty` y del $\{\langle \text{argumento} \rangle\}$ pasado al comando sin modificar la impresión de este. Si se establece en `true`, NVDA/MathCAT NO verbalizará la salida del comando; si se establece en `false`, NVDA/MathCAT sí verbalizará la salida del comando.

- La impresión ' $\overline{AB}$ ' en la salida PDF es idéntica en ambos casos. La elección depende de la terminología del libro de texto o del currículo nacional: en Chile y España se prefiere «semirrecta»; en México y otros países de América Latina se usa «rayo».

El comando `\spside`

`\spside` $\{\langle \text{punto}, \text{punto} \rangle\}$
 $\{\langle \text{key} = \text{val} \rangle\} \{\langle \text{punto}, \text{punto} \rangle\}$

El comando `\spside` trabaja en *modo matemático* y recibe el *argumento obligatorio* $\{\langle \text{punto}, \text{punto} \rangle\}$. Representa un *lado*, *segmento* o *trazo* determinado por dos puntos, aplicando `\overline{\phantom{x}}` en la impresión.

Si no se proporciona el *argumento opcional* $[\langle \text{key} = \text{val} \rangle]$, $\$ \backslash \text{spside}\{AB\} \$$ imprimirá ' $\overline{AB}$ ' en la salida PDF y NVDA/MathCAT verbalizará «lado A B».

Llaves para `\spside`

`read-cmd` = $\{\langle \text{school} \mid \text{mathcat} \rangle\}$ default: `school`

Establece la *forma* en la que NVDA/MathCAT verbalizará al argumento $\{\langle \text{punto}, \text{punto} \rangle\}$. Si se establece en `school`, NVDA/MathCAT verbaliza las letras del argumento sin el prefijo «mayúscula»: $\$ \backslash \text{spside}\{AB\} \$$ se verbaliza «lado A B»; si se establece en `mathcat`, NVDA/MathCAT aplica sus propias reglas, que pueden incluir el prefijo «mayúscula» dependiendo de la configuración del usuario.

`read-sty` = $\{\langle \text{lado} \mid \text{segmento} \mid \text{trazo} \rangle\}$ default: `lado`

Establece el *concepto* que verbalizará NVDA/MathCAT al ejecutar el comando sin modificar la impresión de este. Si se utiliza $\$ \backslash \text{spside}[\text{read-sty}=\text{lado}]\{AB\} \$$, NVDA/MathCAT verbalizará «lado A B»; si se utiliza $\$ \backslash \text{spside}[\text{read-sty}=\text{segmento}]\{AB\} \$$, NVDA/MathCAT verbalizará «segmento A B» y si se utiliza $\$ \backslash \text{spside}[\text{read-sty}=\text{trazo}]\{AB\} \$$, NVDA/MathCAT verbalizará «trazo A B».

`prefix` = $\{\langle \text{prefijo} \rangle\}$ default: `no usado`

Establece el *prefijo* que será verbalizado por NVDA/MathCAT *antes* de verbalizar el «concepto» establecido por la llave `read-sty`. El valor de esta llave *siempre* debe pasarse entre llaves '{ }'.

`concept` = $\{\langle \text{true} \mid \text{false} \rangle\}$ default: `true`

Establece si se *silencia* la verbalización en NVDA/MathCAT del «concepto» establecido por la llave `read-sty` al ejecutar el comando sin modificar la impresión de este. Si se establece en `true`, NVDA/MathCAT verbalizará el concepto; si se establece en `false`, NVDA/MathCAT solo verbalizará el $\{\langle \text{argumento} \rangle\}$ acorde al valor establecido por la llave `read-cmd`.

`read-arg` = $\{\langle \text{verbalización NVDA} \rangle\}$ default: `no usado`

Sobrescribe el *concepto* establecido por la llave `read-sty` que será verbalizado por NVDA/MathCAT al ejecutar el comando sin modificar la impresión de este. El valor de esta llave *siempre* debe pasarse entre llaves '{ }'. Por ejemplo: $\$ \backslash \text{spside}[\text{read-arg}=\{\text{hipotenusa}\}]\{AB\} \$$ imprimirá ' $\overline{AB}$ ' en la salida PDF y NVDA/MathCAT verbalizará «hipotenusa A B».

`silent-cmd` = $\{\langle \text{true} \mid \text{false} \rangle\}$ default: `false`

Establece si se *silencia* la verbalización en NVDA/MathCAT del «concepto» establecido por la llave `read-sty` y del $\{\langle \text{argumento} \rangle\}$ pasado al comando sin modificar la impresión de este. Si se establece en `true`, NVDA/MathCAT NO verbalizará la salida del comando; si se establece en `false`, NVDA/MathCAT sí verbalizará la salida del comando.

El comando `\spmside`

`\spmside` $\{\langle \text{punto}, \text{punto} \rangle\}$
 $\{\langle \text{key} = \text{val} \rangle\} \{\langle \text{punto}, \text{punto} \rangle\}$

El comando `\spmside` trabaja en *modo matemático* y recibe el *argumento obligatorio* $\{\langle \text{punto}, \text{punto} \rangle\}$. Representa la *medida* del *lado*, *segmento* o *trazo* determinado por dos puntos. La distinción entre `\spside` y `\spmside` es semántica: `\spside` representa el *objeto geométrico* ' $\overline{AB}$ '; `\spmside` representa su *medida* (un número real positivo).

Si no se proporciona el *argumento opcional* $[\langle \text{key} = \text{val} \rangle]$, $\$ \backslash \text{spmside}\{AB\} \$$ imprimirá ' AB ' en la salida PDF y NVDA/MathCAT verbalizará «medida del lado A B».

Llaves para `\spmside`

`read-cmd` = { `<punto | mathcat>` } default: `school`

Establece la *forma* en la que NVDA/MathCAT verbalizará al argumento { `<punto, punto>` }. Si se establece en `school`, NVDA/MathCAT verbaliza las letras del argumento sin el prefijo «mayúscula»: `\spmside{AB}` se verbaliza «medida del lado A B»; si se establece en `mathcat`, NVDA/MathCAT aplica sus propias reglas, que pueden incluir el prefijo «mayúscula» dependiendo de la configuración del usuario.

`read-sty` = { `<lado | segmento | trazo>` } default: `lado`

Establece el *concepto* que verbalizará NVDA/MathCAT después de verbalizar el término «medida del» al ejecutar el comando sin modificar la impresión de este. Si se utiliza `\spmside[read-sty=lado]{AB}`, NVDA/MathCAT verbalizará «medida del lado A B»; si se utiliza `\spmside[read-sty=segmento]{AB}`, NVDA/MathCAT verbalizará «medida del segmento A B» y si se utiliza `\spmside[read-sty=trazo]{AB}`, NVDA/MathCAT verbalizará «medida del trazo A B».

`prefix` = { `<prefijo>` } default: `no usado`

Establece el *prefijo* que será verbalizado por NVDA/MathCAT antes de verbalizar el término «medida del» seguido por el «concepto» establecido por la llave `read-sty`. El valor de esta llave *siempre* debe pasarse entre llaves '{ }'.

`concept` = { `<true | false>` } default: `true`

Establece si se *silencia* la verbalización en NVDA/MathCAT del término «medida del» y del «concepto» establecido por la llave `read-sty` al ejecutar el comando sin modificar la impresión de este. Si se establece en `true`, NVDA/MathCAT verbalizará el término «medida del» antes del concepto; si se establece en `false`, NVDA/MathCAT solo verbalizará el { `<argumento>` } acorde al valor establecido por la llave `read-cmd`.

`read-arg` = { `<verbalización NVDA>` } default: `no usado`

Sobrescribe el *concepto* establecido por la llave `read-sty` que será verbalizado por NVDA/MathCAT al ejecutar el comando sin modificar la impresión de este. El valor de esta llave *siempre* debe pasarse entre llaves '{ }' y se debe usar en conjunto con la llave `concept`.

Por ejemplo: `\spmside[concept=false,read-arg={medida de la cuerda}]{AB}` imprimirá ' $\overline{AB}$ ' en la salida PDF y NVDA/MathCAT verbalizará «medida de la cuerda A B».

`print-m` = { `<true | false>` } default: `false`

Establece si se *imprime* la notación visual 'm' antes aplicar `\overline` al { `<argumento>` }. Si se establece en `true`, `\spmside[print-m=true]{AB}` imprimirá ' $m\overline{AB}$ ' en la salida PDF, si se establece en `false` imprimirá ' $\overline{AB}$ ' en la salida PDF. En ambos casos NVDA/MathCAT verbalizará «medida del lado A B».

`silent-cmd` = { `<true | false>` } default: `false`

Establece si se *silencia* la verbalización en NVDA/MathCAT del término «medida del», del «concepto» establecido por la llave `read-sty` y del { `<argumento>` } pasado al comando sin modificar la impresión de este. Si se establece en `true`, NVDA/MathCAT NO verbalizará la salida del comando; si se establece en `false`, NVDA/MathCAT sí verbalizará la salida del comando.

El comando `\spangle`

<u><code>\spangle</code></u>	<code>\spangle{<punto letra griega número>}</code>	<code>\spangle{<punto, punto, punto>}</code>
	<code>\spangle[<key = val>]{<punto letra griega número>}</code>	<code>\spangle[<key = val>]{<punto, punto, punto>}</code>

El comando `\spangle` trabaja en *modo matemático* y recibe un *argumento obligatorio* el cual puede ser de la forma { `<punto | letra griega | número>` } o { `<punto, punto, punto>` } aplicando `\angle` o `\rightangle` en la impresión.

Si no se proporciona el *argumento opcional* [`<key = val>`], `\spangle{A}` imprimirá ' $\angle A$ ' en la salida PDF y NVDA/MathCAT verbalizará «ángulo en A»; `\spangle{\alpha}` imprimirá ' $\angle \alpha$ ' en la salida PDF y NVDA/MathCAT verbalizará «ángulo alfa» y `\spangle{A, 0, B}` imprimirá ' $\angle AOB$ ' en la salida PDF y NVDA/MathCAT verbalizará «ángulo A O B».

Llaves para `\spangle`

`read-cmd` = { `<school | mathcat>` } default: `school`

Establece la *forma* en la que NVDA/MathCAT verbalizará al argumento { `<punto>` } o { `<punto, punto, punto>` }. Si se establece en `school`, NVDA/MathCAT verbaliza las letras del argumento sin el prefijo «mayúscula»: `\spangle{A, 0, B}` se verbaliza «ángulo A O B»; si se establece en `mathcat`, NVDA/MathCAT aplica sus propias reglas, que pueden incluir el prefijo «mayúscula» dependiendo de la configuración del usuario.

`prefix` = { `<prefijo>` } default: `no usado`

Establece el *prefijo* que será verbalizado por NVDA/MathCAT antes de verbalizar el término «ángulo». El valor de esta llave *siempre* debe pasarse entre llaves '{ }'.

`silent-cmd` = { `<true | false>` } default: `false`

Establece si se *silencia* la verbalización en NVDA/MathCAT del término «ángulo». Si se establece en `true`, NVDA/MathCAT NO verbalizará el término; si se establece en `false`, NVDA/MathCAT SÍ lo verbalizará.

recto = {true | false} default: false

Establece si se usará `\rightangle` en la impresión añadiendo el término «recto» a la verbalización en NVDA/MathCAT. Si se establece en `true`, `\spangle[recto=true]{A}` imprimirá ‘ $\angle A$ ’ en la salida PDF y NVDA/MathCAT verbalizará «ángulo recto en A»; `\spangle[recto=true]{A, O, B}` imprimirá ‘ $\angle AOB$ ’ en la salida PDF y NVDA/MathCAT verbalizará «ángulo recto A O B»; si se establece en `false`, imprimirá usando `\angle` en la salida PDF y NVDA/MathCAT omitirá el término «recto».

El comando `\spmangle`

`\spmangle` `\spmangle{<punto | letra griega | número>}` `\spmangle{<punto, punto, punto>}`
`\spmangle[<key = val>]{<punto | letra griega | número>}` `\spmangle[<key = val>]{<punto, punto, punto>}`

El comando `\spmangle` trabaja en *modo matemático* y recibe un *argumento obligatorio* el cual puede ser de la forma `{<punto | letra griega | número>}` o `{<punto, punto, punto>}` aplicando `\measuredangle` o `\measuredrightangle` en la impresión. La distinción entre `\spangle` y `\spmangle` es semántica: `\spangle` representa el *objeto geométrico* ‘ $\angle AOB$ ’; `\spmangle` representa su *medida* (un valor en grados).

Si no se proporciona el *argumento opcional* `[<key = val>]`, `\spmangle{A}` imprimirá ‘ $\angle A$ ’ en la salida PDF y NVDA/MathCAT verbalizará «medida del ángulo en A»; `\spmangle{\alpha}` imprimirá ‘ $\angle \alpha$ ’ en la salida PDF y NVDA/MathCAT verbalizará «medida del ángulo alfa» y `\spmangle{A, O, B}` imprimirá ‘ $\angle AOB$ ’ en la salida PDF y NVDA/MathCAT verbalizará «medida del ángulo A O B».

Llaves para `\spmangle`

read-cmd = {<school | mathcat>} default: school

Establece la *forma* en la que NVDA/MathCAT verbalizará al argumento `{<punto>}` o `{<punto, punto, punto>}`. Si se establece en `school`, NVDA/MathCAT verbaliza las letras del argumento sin el prefijo «mayúscula»: `\spmangle{A, O, B}` se verbaliza «medida del ángulo A O B»; si se establece en `mathcat`, NVDA/MathCAT aplica sus propias reglas, que pueden incluir el prefijo «mayúscula» dependiendo de la configuración del usuario.

prefix = {<prefijo>} default: no usado

Establece el *prefijo* que será verbalizado por NVDA/MathCAT *antes* de verbalizar el término «medida del ángulo». El valor de esta llave *siempre* debe pasarse entre llaves ‘{ }’.

silent-cmd = {<true | false>} default: false

Establece si se *silencia* la verbalización en NVDA/MathCAT del término «medida del ángulo». Si se establece en `true`, NVDA/MathCAT NO verbalizará el término; si se establece en `false`, NVDA/MathCAT SÍ lo verbalizará.

recto = {<true | false>} default: false

Establece si se usará `\measuredrightangle` en la impresión añadiendo el término «recto» a la verbalización en NVDA/MathCAT. Si se establece en `true`, `\spmangle[recto=true]{A}` imprimirá ‘ $\angle A$ ’ en la salida PDF y NVDA/MathCAT verbalizará «medida del ángulo recto en A»; `\spmangle[recto=true]{A, O, B}` imprimirá ‘ $\angle AOB$ ’ en la salida PDF y NVDA/MathCAT verbalizará «medida del ángulo recto A O B»; si se establece en `false`, imprimirá usando `\measuredangle` en la salida PDF y NVDA/MathCAT omitirá el término «recto».

print-m = {<true | false>} default: false

Establece *si se imprime* la notación visual ‘m’ antes del argumento. Si se establece en `true`, `\spmangle[print-m=true]{A}`, imprimirá ‘ $m\angle AOB$ ’ en la salida PDF, si se establece en `false` imprimirá ‘ $\angle AOB$ ’ en la salida PDF. En ambos casos NVDA/MathCAT verbalizará «medida del ángulo A O B».

El comando `\spang`

`\spang` `\spang{<grados>}`
`\spang{<grados : minutos>}`
`\spang{<grados : minutos : segundos>}`

El comando `\spang` trabaja en *modo matemático* y recibe el *argumento obligatorio* `{<grados>}`, `{<grados : minutos>}` o `{<grados : minutos : segundos>}`. Los procesa internamente bajo los comandos `\spnum` y `\spunit` para imprimir y verbalizar el «ángulo sexagesimal». Por ejemplo, `\spang{45:30:15}` imprimirá ‘45°30’15” en la salida PDF y NVDA/MathCAT verbalizará «cuarenta y cinco grados treinta minutos quince segundos».

El comando `\sparc`

`\sparc` `\sparc{<punto, punto>}` `\sparc{<punto, punto, punto>}`
`\sparc[<key = val>]{<punto, punto>}` `\sparc[<key = val>]{<punto, punto, punto>}`

El comando `\sparc` trabaja en *modo matemático* y recibe un *argumento obligatorio* el cual puede ser de la forma `{<punto, punto>}` o `{<punto, punto, punto>}`. Representa un arco determinado por dos o tres puntos aplicando `\widearc` en la impresión.

Si no se proporciona el *argumento opcional* `[<key = val>]`, `\sparc{A, B}` imprimirá ‘ $\widehat{AB}$ ’ en la salida PDF y NVDA/MathCAT verbalizará «arco A B».

Llaves para `\sparc`

`read-cmd` = { `<school | mathcat>` } default: `school`

Establece la *forma* en la que NVDA/MathCAT verbalizará al argumento { `<punto, punto>` } o { `<punto, punto, punto>` }. Si se establece en `school`, NVDA/MathCAT verbaliza las letras del argumento sin el prefijo «mayúscula»: `\sparc{A, B}` se verbaliza «arco A B»; si se establece en `mathcat`, NVDA/MathCAT aplica sus propias reglas, que pueden incluir el prefijo «mayúscula» dependiendo de la configuración del usuario.

`prefix` = { `<prefijo>` } default: `no usado`

Establece el *prefijo* que será verbalizado por NVDA/MathCAT *antes* de verbalizar el término «arco». El valor de esta llave *siempre* debe pasarse entre llaves '{ }'.

`silent-cmd` = { `<true | false>` } default: `false`

Establece si se *silencia* la verbalización en NVDA/MathCAT del término «arco». Si se establece en `true`, NVDA/MathCAT NO verbalizará el término; si se establece en `false`, NVDA/MathCAT SÍ lo verbalizará.

El comando `\sparc`

<code>\sparc</code>	<code>\sparc{<punto, punto>}</code>	<code>\sparc{<punto, punto, punto>}</code>
	<code>\sparc[<key = val>]{<punto, punto>}</code>	<code>\sparc[<key = val>]{<punto, punto, punto>}</code>

El comando `\sparc` trabaja en *modo matemático* y recibe un *argumento obligatorio* el cual puede ser de la forma { `<punto, punto>` } o { `<punto, punto, punto>` }. Representa la *medida* del arco determinado por dos o tres puntos. La distinción entre `\sparc` y `\spmarc` es semántica: `\sparc` representa el *objeto geométrico* $\widehat{AB}$; `\spmarc` representa su *medida* (un valor en grados).

Si no se proporciona el *argumento opcional* [`<key = val>`], `\sparc{A, B}` imprimirá ' $\widehat{AB}$ ' en la salida PDF y NVDA/MathCAT verbalizará «medida del arco A B».

Llaves para `\spmarc`

`read-cmd` = { `<school | mathcat>` } default: `school`

Establece la *forma* en la que NVDA/MathCAT verbalizará al argumento { `<punto, punto>` } o { `<punto, punto, punto>` }. Si se establece en `school`, NVDA/MathCAT verbaliza las letras del argumento sin el prefijo «mayúscula»: `\spmarc{A, B}` se verbaliza «medida del arco A B»; si se establece en `mathcat`, NVDA/MathCAT aplica sus propias reglas, que pueden incluir el prefijo «mayúscula» dependiendo de la configuración del usuario.

`prefix` = { `<prefijo>` } default: `no usado`

Establece el *prefijo* que será verbalizado por NVDA/MathCAT *antes* de verbalizar el término «medida del arco». El valor de esta llave *siempre* debe pasarse entre llaves '{ }'.

`silent-cmd` = { `<true | false>` } default: `false`

Establece si se *silencia* la verbalización en NVDA/MathCAT del término «medida del arco». Si se establece en `true`, NVDA/MathCAT NO verbalizará el término; si se establece en `false`, NVDA/MathCAT SÍ lo verbalizará.

El comando `\spPoly`

<code>\spPoly</code>	<code>\spPoly{<punto, punto, punto, ...>}</code>
	<code>\spPoly[<key = val>]{<punto, punto, punto, ...>}</code>

El comando `\spPoly` trabaja en *modo matemático* y recibe el *argumento obligatorio* { `<punto, punto, punto, ...>` }, una lista de al menos tres { `<puntos>` } separados por comas. El tipo de *símbolo* en la impresión y la verbalización se determinan acorde al número de puntos en el argumento: Si son tres puntos se aplica `\triangle` y añade el término «triángulo» a la verbalización; si son cuatro puntos se aplica `\mdlgwhtsquare` y añade el término «cuadrado» a la verbalización; si son cinco o más puntos no se aplica ningún símbolo ni se añade verbalización.

Si no se proporciona el *argumento opcional* [`<key = val>`], `\spPoly{A, B, C}` imprimirá ' $\triangle ABC$ ' en la salida PDF y NVDA/MathCAT verbalizará «triángulo A B C»; `\spPoly{A, B, C, D}` imprimirá ' $\square ABCD$ ' y verbalizará «cuadrado A B C D»; `\spPoly{A, B, C, D, E}` imprimirá ' $ABCDE$ ' y verbalizará «A B C D E».

Llaves para `\spPoly`

`read-cmd` = { `<school | mathcat>` } default: `school`

Establece la *forma* en la que NVDA/MathCAT verbalizará al argumento { `<punto, punto, punto, ...>` }. Si se establece en `school`, NVDA/MathCAT verbaliza las letras del argumento sin el prefijo «mayúscula»: `\spPoly{A, B, C}` se verbaliza «triángulo A B C»; si se establece en `mathcat`, NVDA/MathCAT aplica sus propias reglas, que pueden incluir el prefijo «mayúscula» dependiendo de la configuración del usuario.

`prefix` = { `<prefijo>` } default: `no usado`

Establece el *prefijo* que será verbalizado por NVDA/MathCAT *antes* de verbalizar el argumento o los términos «triángulo» y «cuadrado» establecido por la llave `print-sym`. El valor de esta llave *siempre* debe pasarse entre llaves '{ }'.

`print-sym` = { `<true | false>` } default: `true`

Establece si se usará `\triangle` o `\mdlgwhtsquare` en la impresión añadiendo el término correspondiente a la verbalización en NVDA/MathCAT. Si se establece en `true`, `\spPoly[print-sym=true]{A, B, C}` imprimirá ' $\triangle ABC$ ' en la salida PDF y NVDA/MathCAT verbalizará «*triángulo A B C*»; si se establece en `false`, imprimirá ' ABC ' en la salida PDF y NVDA/MathCAT omitirá el término «*triángulo*», verbalizando solo «*A B C*».

`silent-cmd = {\true | false}`

default: `false`

Alias de `print-sym=false`, incluido por consistencia con el resto de los comandos de geometría plana.

El comando `\spAfig`

`\spAfig` `\spAfig`
`\spAfig((punto, punto, punto, ...))`
`\spAfig(número | letra | letra_{número})`
`\spAfig[key = val]((punto, punto, punto, ...))`

El comando `\spAfig` trabaja en *modo matemático* y recibe el *argumento delimitado por paréntesis*, el cual es *completamente opcional*, representando el área de una figura poligonal en la impresión aplicando `\mathcal{A}`.

El argumento admite tres formas: una *lista de vértices* (`(punto, punto, punto, ...)`) (al menos tres); un *número o letra sueltos* (`(1)`), (`(n)`); o una *letra de una tabla fija* (F, P, B, L) con subíndice numérico opcional, (`(F)`), (`(F_{1})`).

Si no se proporciona el *argumento opcional* [`key = val`] ni el argumento delimitado por paréntesis, `\spAfig` imprimirá ' $\mathcal{A}$ ' en la salida PDF y NVDA/MathCAT verbalizará «*área*». Con vértices, `\spAfig(A, B, C)` imprimirá ' $\mathcal{A}_{ABC}$ ' y verbalizará «*área del triángulo A B C*». Con un número o letra sueltos, `\spAfig(1)` imprimirá ' $\mathcal{A}_1$ ' y verbalizará «*área uno*»; `\spAfig(n)` imprimirá ' $\mathcal{A}_n$ ' y verbalizará «*área n*». Con una letra de la tabla, `\spAfig(F)` imprimirá ' $\mathcal{A}_F$ ' y verbalizará «*área de la figura*»; `\spAfig(F_{1})` imprimirá ' $\mathcal{A}_{F_1}$ ' y verbalizará «*área de la figura uno*».

Llaves para `\spAfig`

`read-cmd = {school | mathcat}`

default: `school`

Establece la *forma* en la que NVDA/MathCAT verbalizará al argumento. Si se establece en `school`, NVDA/MathCAT verbaliza las letras del argumento sin el prefijo «mayúscula»: `\spAfig(A, B, C)` se verbaliza «*área del triángulo A B C*»; si se establece en `mathcat`, NVDA/MathCAT aplica sus propias reglas, que pueden incluir el prefijo «mayúscula» dependiendo de la configuración del usuario.

`prefix = {prefijo}`

default: `no usado`

Establece el *prefijo* que será verbalizado por NVDA/MathCAT *antes* de verbalizar el término «*área*». El valor de esta llave *siempre* debe pasarse entre llaves '{ }'.

`print-sym = {auto | triangle | square | none}`

default: `auto`

Establece si se usará `\triangle` o `\mdlgwhtsquare` en la impresión. Con vértices, `auto` infiere el símbolo según el número de puntos (tres o cuatro); `none` lo omite y NVDA/MathCAT verbaliza solo los vértices sin nombrar la figura: `\spAfig[print-sym=none](A, B, C)` imprimirá ' $\mathcal{A}_{ABC}$ ' y verbalizará «*área A B C*». Forzar `triangle/square` exige que coincida con el número real de vértices; en caso contrario se produce un error. Con un número o letra sueltos, `auto` y `none` se comportan igual (sin símbolo); `triangle/square` anida el argumento bajo el símbolo: `\spAfig[print-sym=triangle](1)` imprimirá ' $\mathcal{A}_{\triangle_1}$ ' y verbalizará «*área del triángulo uno*». Esta llave no puede combinarse con una letra de la tabla (F, P, B, L).

`read-sub = {true | false}`

default: `false`

Establece si NVDA/MathCAT antepone la palabra «sub» al verbalizar el número o letra del argumento único. Si se establece en `true`, `\spAfig[read-sub=true](1)` verbaliza «*área sub uno*»; si se establece en `false`, verbaliza «*área uno*». No tiene efecto en la notación de vértices ni cuando el argumento es una letra de la tabla sin subíndice.

`silent-cmd = {true | false}`

default: `false`

Establece si se *silencia por completo* la verbalización en NVDA/MathCAT, sin afectar la impresión. Si se establece en `true`, NVDA/MathCAT NO verbalizará nada; si se establece en `false`, NVDA/MathCAT verbalizará normalmente.

`read-arg = {nombre}`

default: `no usado`

Sobrescribe el *nombre de la figura* determinado automáticamente por el número de puntos en el argumento, que será verbalizado por NVDA/MathCAT al ejecutar el comando sin modificar la impresión de este. El valor de esta llave *siempre* debe pasarse entre llaves '{ }'. Por ejemplo: `\spAfig[read-arg={trapezio}](A, B, C, D)` imprimirá ' $\square_{ABCD}$ ' en la salida PDF y NVDA/MathCAT verbalizará «*área del trapecio A B C D*».

El comando `\spPfig`

```
\spPfig \spPfig
\spPfig(<punto, punto, punto, ...>)
\spPfig(<número | letra | letra_{número}>)
\spPfig[<key = val>](<punto, punto, punto, ...>)
```

El comando `\spPfig` trabaja en *modo matemático* y recibe el *argumento delimitado por paréntesis*, el cual es *completamente opcional*, representando el *perímetro* de una figura poligonal en la impresión aplicando `\mathcal{P}`.

El argumento admite las mismas tres formas que `\spAfig` (§7): una *lista de vértices*, un *número o letra sueltos*, o una *letra de la tabla fija* (F, P, B, L) con subíndice numérico opcional.

Si no se proporciona el *argumento opcional* [`<key = val>`] ni el argumento delimitado por paréntesis, `\spPfig` imprimirá ‘ $\mathcal{P}$ ’ en la salida PDF y NVDA/MathCAT verbalizará «*perímetro*». Con vértices, `\spPfig(A, B, C)` imprimirá ‘ $\mathcal{P}_{\triangle ABC}$ ’ y verbalizará «*perímetro del triángulo A B C*». Con un número o letra sueltos, `\spPfig(2)` imprimirá ‘ $\mathcal{P}_2$ ’ y verbalizará «*perímetro dos*». Con una letra de la tabla, `\spPfig(P_{2})` imprimirá ‘ $\mathcal{P}_{P_2}$ ’ y verbalizará «*perímetro del polígono dos*».

Llaves para `\spPfig`

```
read-cmd = {<school | mathcat>} default: school
```

Establece la *forma* en la que NVDA/MathCAT verbalizará al argumento. Si se establece en `school`, NVDA/MathCAT verbaliza las letras del argumento sin el prefijo «mayúscula»: `\spPfig(A, B, C)` se verbaliza «*perímetro del triángulo A B C*»; si se establece en `mathcat`, NVDA/MathCAT aplica sus propias reglas, que pueden incluir el prefijo «mayúscula» dependiendo de la configuración del usuario.

```
prefix = {<prefijo>} default: no usado
```

Establece el *prefijo* que será verbalizado por NVDA/MathCAT *antes* de verbalizar el término «*perímetro*». El valor de esta llave *siempre* debe pasarse entre llaves ‘{ }’.

```
print-sym = {<auto | triangle | square | none>} default: auto
```

Establece si se usará `\triangle` o `\mdlgwhtsquare` en la impresión, con la misma semántica que en `\spAfig` (§7).

```
read-sub = {<true | false>} default: false
```

Establece si NVDA/MathCAT antepone la palabra «sub» al verbalizar el número o letra del argumento único, con la misma semántica que en `\spAfig` (§7).

```
silent-cmd = {<true | false>} default: false
```

Establece si se *silencia por completo* la verbalización en NVDA/MathCAT, sin afectar la impresión. Si se establece en `true`, NVDA/MathCAT NO verbalizará nada; si se establece en `false`, NVDA/MathCAT verbalizará normalmente.

```
read-arg = {<nombre>} default: no usado
```

Sobrescribe el *nombre de la figura* determinado automáticamente por el número de puntos en el argumento, que será verbalizado por NVDA/MathCAT al ejecutar el comando sin modificar la impresión de este. El valor de esta llave *siempre* debe pasarse entre llaves ‘{ }’. Por ejemplo: `\spPfig[read-arg={trapecio}](A, B, C, D)` imprimirá ‘ $\mathcal{P}_{\square ABCD}$ ’ en la salida PDF y NVDA/MathCAT verbalizará «*perímetro del trapecio A B C D*».

8 Referencias

- [1] ROBERTSON, WILL . “unicode-math - Unicode mathematics support for X_YTeX and LuaTeX”. Available from CTAN, <https://www.ctan.org/pkg/unicode-math>, 2023.
- [2] KRUEGER, MARCEL. “LuaMML - Automatically generate MathML from LuaTeX math mode material”. Available from CTAN, <https://ctan.org/pkg/luamml>, 2026.
- [3] The L^AT_EX Project. “fontspec - Advanced font selection for X_YL^AT_EX and LuaTeX”. Available from CTAN, <https://www.ctan.org/pkg/fontspec>, 2025.
- [4] VOß, HERBERT. “libertinus-otf - Support for Libertinus OpenType”. Available from CTAN, <https://www.ctan.org/pkg/libertinus-otf>, 2025.
- [5] FLIPO, DANIEL. “erewhon-math - Utopia based OpenType Math font”. Available from CTAN, <https://ctan.org/pkg/erewhon-math>, 2026.
- [6] HOFSTRA, SILKE. “sourcecodepro - Use SourceCodePro with T_EX(-alike) systems”. Available from CTAN, <https://ctan.org/pkg/sourcecodepro>, 2025.
- [7] GONZÁLEZ, PABLO. “scontents - Stores L^AT_EX contents in memory or files”. Available from CTAN, <https://www.ctan.org/pkg/scontents>, 2026.
- [8] GONZÁLEZ, PABLO. “enumext - Enumerate exercise sheets”. Available from CTAN, <https://www.ctan.org/pkg/enumext>, 2026.
- [9] BRAAMS, JOHANNES AND BEZOS, JAVIER. “babel - Multilingual support for L^AT_EX, LuaL^AT_EX, X_YL^AT_EX, and Plain T_EX”. Available from CTAN, <https://www.ctan.org/pkg/babel>, 2026.
- [10] BEZOS, JAVIER. “babel-spanish - Babel support for Spanish”. Available from CTAN, <https://www.ctan.org/pkg/babel-spanish>, 2026.
- [11] NV ACCESS. “NVDA - NonVisual Desktop Access screen reader”. Available from NV ACCESS, <https://www.nvaccess.org/>, 2026.
- [12] SOIFFER, NEIL. “MathCAT - Math to speech and braille translation”. Available from GITHUB, <https://nsoiffer.github.io/MathCAT/>, 2026.
- [13] ADOBE INC. “Adobe Acrobat Reader - Reliable PDF viewer”. Available from ADOBE, <https://get.adobe.com/reader/>, 2026.
- [14] ISO. “ISO 32000-2:2020 - Portable Document Format (PDF 2.0)”. Available from PDF ASSOCIATION, <https://pdfa.org/resource/iso-32000-2/>, 2020.
- [15] PDF ASSOCIATION. “WTPDF - Well-Tagged PDF specification”. Available from PDFA, <https://pdfa.org/wtpdf/>, 2024.
- [16] PDF ASSOCIATION. “PDF 2.0 Errata Collection 3”. Available from PDFA, <https://pdfa.org/PDF-2-0-errata-collection-3-now-available/>, 2026.
- [17] L^AT_EX PROJECT LWG. “Best Practice Guide: Math in PDF”. Available from PDFA, <https://pdfa.org/resource/best-practice-guide-math-in-PDF/>, 2026.
- [18] JOHNSON, DUFF. “PDF 2.0: New Features, Real-World Impact”. Available from PDFA, <https://pdfa.org/PDF-2-0-new-features-real-world-impact/>, 2026.
- [19] The L^AT_EX Project. “LaTeX Tagged PDF Project - Documentation and resources”. Available from L^AT_EX PROJECT, <https://latex3.github.io/tagging-project/>, 2026.
- [20] VERAPDF CONSORTIUM. “veraPDF - Industry supported PDF/A and PDF/UA validator”. Available from VERAPDF, <https://verapdf.org/>, 2026.
- [21] DUAL LAB. “ngPDF - Next Generation PDF demonstrator and validator”. Available from NGPDF, <https://ngpdf.com/>, 2026.
- [22] BERRY, KARL. “L^AT_EX 2_ε: An Unofficial Reference Manual”. Available from CTAN, <https://ctan.org/pkg/latex2e-help-texinfo>, 2026.
- [23] The L^AT_EX Project. “Extensive support for hypertext in L^AT_EX”. Available from CTAN, <https://www.ctan.org/pkg/hyperref>, 2026.
- [24] The L^AT_EX Project. “The expl3 package”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2026.

- [25] The $\text{\LaTeX}$ Project. “The $\text{\LaTeX}$ 3 Interfaces”. Available from CTAN, <https://www.ctan.org/pkg/l3kernel>, 2026.
- [26] The $\text{\LaTeX}$ Project. “The $\text{\LaTeX}$ 2 ϵ sources”. Available from CTAN, <https://ctan.org/tex-archive/macros/latex/base>, 2026.
- [27] The $\text{\LaTeX}$ Project. “ $\text{\LaTeX}$ News, Issue 41, June 2025”. Available from CTAN, <https://ctan.org/tex-archive/macros/latex/base>, 2025.
- [28] The $\text{\LaTeX}$ Project. “ $\text{\LaTeX}$ for authors current version”. Available from CTAN, <https://ctan.org/pkg/latex-base>, 2026.
- [29] FISCHER, ULRIKE. “tagpdf – $\text{\LaTeX}$ kernel code for PDF tagging”. Available from CTAN, <https://www.ctan.org/pkg/tagpdf>, 2026.
- [30] The $\text{\LaTeX}$ Project. “latex-lab – $\text{\LaTeX}$ laboratory”. Available from CTAN, <https://www.ctan.org/pkg/latex-lab>, 2026.

9 Change history

v0.99 (ctan), 2026-09-13 – First public release.

10 Índice de la Documentación

Los números en cursiva indican las páginas donde se describe la entrada correspondiente.

C	
Document class:	
article	1
book	1
letter	1
report	1
Commands provide by spintent :	
\setspintent	3
\spAfig	23
\spPfig	24
\spPoint	17
\spPoly	22
\spangle	20
\spang	21
\sparc	21
\spdate	11
\spdiv	13
\spdsym	12
\spmQ	16
\spmangle	21
\spmarc	22
\spmcd	15
\spmcm	15
\spmoney	6
\spmside	19
\spmsym	12
\spm μ l	13
\spnD	14
\spnM	14
\spnZ	16
\spnewunit	6
\spnum	3
\sprayo	18
\spread	11
\sprecta	18
\spshort	7
\spside	19
\spsiglo	11
\sptime	11
\spunitalias	6
\spunit	4
\spusep	12
K	
Keys for \spAfig provide by spintent :	
prefix	23
print-sym	23
read-arg	23
read-cmd	23
read-sub	23
silent-cmd	23
Keys for \spangle provide by spintent :	
prefix	20
read-cmd	20
recto	21
silent-cmd	20
Keys for \sparc provide by spintent :	
prefix	22
read-cmd	22
silent-cmd	22
Keys for \spdiv provide by spintent :	
read-parens	13
wrap-parens	13
Keys for \spdsym provide by spintent :	
prefix	12
read-sym	12
set-sym	12
suffix	12
Keys for \spmangle provide by spintent :	
prefix	21
print-m	21
read-cmd	21
recto	21
silent-cmd	21
Keys for \spmarc provide by spintent :	
prefix	22
read-cmd	22
silent-cmd	22
Keys for \spmcd provide by spintent :	
prefix	15
read-cmd	15
result	15
sample-arg	15
silent-cmd	15
upper-case	15
Keys for \spmcm provide by spintent :	
prefix	16
read-cmd	16
result	16
sample-arg	16
silent-cmd	16
upper-case	16
Keys for \spmoney provide by spintent :	
currency	7
dolar-math	7
sub-units	7
Keys for \spmQ provide by spintent :	
join-word	17
print-dfrac	17
read-parens	17
use-sp n Z	17
wrap-parens	17
Keys for \spmside provide by spintent :	
concept	20
prefix	20
print-m	20
read-arg	20
read-cmd	20
read-sty	20
silent-cmd	20
Keys for \spmsym provide by spintent :	
not-print	13
prefix	13
read-sym	13
set-sym	13
suffix	13
Keys for \spm μ l provide by spintent :	
read-parens	13
wrap-parens	13
Keys for \spnD provide by spintent :	
prefix	14

result-num	14	size	12
result	14	Keys for \spdiv provide by spintent :	
sample-arg	14	cifras-sep	13
silent-cmd	14	notation-sym	13
Keys for \spnM provide by spintent :		read-period-sep	13
prefix	14	read-sign	13
result-num	14	read-sym	13
result	14	set-sym	13
sample-arg	14	Keys for \spdsym provide by spintent :	
silent-cmd	15	read-sym	12
Keys for \spnum provide by spintent :		Keys for \spmcd provide by spintent :	
cifras-sep	3	read-cmd	15
notation-sym	4	Keys for \spmcm provide by spintent :	
read-period-sep	3	read-cmd	16
read-sign	3	Keys for \spmoney provide by spintent :	
Keys for \spnZ provide by spintent :		cifras-sep	7
read-parens	16	Keys for \spmQ provide by spintent :	
wrap-parens	16	wrap-parens	17
Keys for \spPfig provide by spintent :		Keys for \spmsym provide by spintent :	
prefix	24	read-sym	13
print-sym	24	Keys for \spm\ provide by spintent :	
read-arg	24	cifras-sep	13
read-cmd	24	notation-sym	13
read-sub	24	read-period-sep	13
silent-cmd	24	read-sign	13
Keys for \spPoint provide by spintent :		read-sym	13
concept	17	set-sym	13
prefix	17	Keys for \spnZ provide by spintent :	
read-cmd	17	cifras-sep	16
silent-cmd	18	read-sign	16
Keys for \spPoly provide by spintent :		Keys for \spPoly provide by spintent :	
prefix	22	print-sym	23
print-sym	22	Keys for \spside provide by spintent :	
read-cmd	22	read-sty	19, 20
silent-cmd	23	Keys for \spunit provide by spintent :	
Keys for \sprayo provide by spintent :		cifras-sep	4
concept	18	notation-sym	4
prefix	18	read-period-sep	4
read-cmd	18	Keys for \spusep provide by spintent :	
read-sty	18	silent	12
silent-cmd	19	size	12
Keys for \sprecta provide by spintent :			
concept	18		
prefix	18		
read-cmd	18		
silent-cmd	18		
Keys for \spshort provide by spintent :			
read-arg	9		
small-caps	9		
Keys for \spside provide by spintent :			
concept	19		
prefix	19		
read-arg	19		
read-cmd	19		
read-sty	19		
silent-cmd	19		
Keys for \spsiglo provide by spintent :			
print-era	11		
Keys for \spunit provide by spintent :			
print-cdot	4		
read-cdot	4		
read-slash	4		
Keys for \spusep provide by spintent :			
silent	12		

M

Lua module provide by **spintent**:

spintent.lua 6, 7, 9, 10, 17

P

Packages :

babel-spanish 2

babel 2, 7

documentmetadata-support 1

enumext 1

expl3 3

fontspec 2

fourier-otf 2

hyperref 2

l3keys 3

latex-lab-mathintent 1

libertinus-otf 2

luamml 1

scontents 1

sourcecodepro 2

tagpdf 1, 7, 11

unicode-math 1

11 Implementation

The most recent publicly released version of `spintent` is available at CTAN: <https://www.ctan.org/pkg/spintent>. While general feedback via email is welcomed, specific bugs or feature requests should be reported through the issue tracker: <https://github.com/pablgonz/spintent/issues>.

- The documentation presented here is far from professional, it contains a lot of obvious information that to the eye of a TeXpert are superfluous, but, after so many years developing this project is the only way to remember what does what.

11.1 General conventions

Functions of the form `\__spintent_luafun_some:n` or `\__spintent_luafun_some:nn` are defined (created) in the Lua module `spintent.lua` and only their variants are declared in `expl3`.

Similarly, variables of the form `\l__spintent_luaset_some_tl` or `\l__spintent_luaset_some_str` are defined in the Lua module `spintent.lua` and only declared in `expl3`.

- All variables and functions defined in this package are private and are NOT intended to work or be used by another package or module.

11.2 Initial set up

Start the DocStrip guards.

```
1 (*package)
```

Identify the internal prefix (L^AT_EX3 DocStrip convention) for `l3doc` class.

```
2 (@@=spintent)
```

11.3 Declaration of the package

First we will make sure we have a minimum (super updated) release version of L^AT_EX to work correctly, otherwise, we will return an “error”.

```
3 \NeedsTeXFormat{LaTeX2e}[2026-11-01]
4 \IfFormatAtLeastF { 2026-11-01 }
5 {
6   \PackageError { spintent }
7     { LaTeX~kernel~too~old~need~2026-11-01~or~later }
8     {
9       spintent~requires~a~LaTeX2e~release~2026-11-01~or~
10      later.~Update~your~TeX~distribution.
11     }
12 }
```

Now declare the `spintent` package and we will add the only key `mathcal` that can be passed as a package option.

```
13 \ProvidesExplPackage {spintent} {2026-09-13} {0.99} {Spanish parse intents}
14 \keys_define:nn { spintent }
15 {
16   mathcal .usage:n    = load,
17   mathcal .bool_set:N = \l__spintent_mathcal_bool,
18   mathcal .initial:n  = true,
19   mathcal .value_required:n = true,
20 }
21 \ProcessKeyOptions [ spintent ]
```

We check if the requirements for running the `spintent` package are met; that is: `\DocumentMetadata` must be active, Lua_T_EX must be running, and the `unicode-math` or `lua-unicode-math` package must be loaded. If neither is present, we will load `unicode-math`. If the conditions cannot be met, we will return a “fatal error”.

```
22 \IfDocumentMetadataTF
23 {
24   \sys_if_engine luatex:TF
25   {
26     \msg_new:nnn { spintent } { package-not-load }
27     {
28       The~'#1'~package~will~be~loaded~as~a~dependency.
29     }
30     \IfPackageLoadedF { unicode-math }
31     {
32       \IfPackageLoadedF { lua-unicode-math }
33       {
34         \msg_info:nnn { spintent } { package-not-load } { unicode-math }
35         \RequirePackage{unicode-math}
36       }
37     }
38     \msg_new:nnn { spintent } { env-success }
39     { Everything~looks~correct,~spintent~will~make~the~intent! }
```

```

40     \msg_info:nn { spintent } { env-success }
41   }
42   {
43     \msg_new:nnnn { spintent } { fatal-engine-requires-luatex }
44     { The~spintent~package~requires~LuaLaTeX. }
45     { This~package~relies~on~Lua~module.~Compile~with~lualatex. }
46     \msg_fatal:nn { spintent } { fatal-engine-requires-luatex }
47   }
48 }
49 {
50   \msg_new:nnnn { spintent } { fatal-metadata-missing }
51   { \token_to_str:N \DocumentMetadata \c_space_tl is~missing. }
52   {
53     The~spintent~package~requires~tagged~PDF~active.\\
54     You~must~declare~\token_to_str:N \DocumentMetadata { tagging=on } ~
55   }
56   \msg_fatal:nn { spintent } { fatal-metadata-missing }
57 }

```

11.4 Some kernel variants

```

\str_if_eq:nVTF
\str_if_eq:nVF
\str_uppercase:V
\str_lowercase:V
\seq_set_from_clist:Ne

```

Non-standard kernel variants.

```

58 \cs_generate_variant:Nn \str_if_eq:nnTF { V }
59 \cs_generate_variant:Nn \str_if_eq:nnF { V }
60 \cs_generate_variant:Nn \str_uppercase:n { V }
61 \cs_generate_variant:Nn \str_lowercase:n { V }
62 \cs_generate_variant:Nn \seq_set_from_clist:Nn { Ne }

```

(End of definition for `\str_if_eq:nVTF` and others.)

11.5 Variables for the key `\mathcal` and `\rightanglesqr`

```

\l__spintent_luaset_cal_fam_ok_str
\l__spintent_luaset_sym_fam_ok_str

```

First, we declare the variables `\l__spintent_luaset_cal_fam_ok_str` and `\l__spintent_luaset_sym_fam_ok_str` before loading the module `spintent.lua`. This is necessary because of the implementation of the functions `\__spintent_luafun_classic_mathcal:nn` and `\__spintent_luafun_right_angle_sqr:` within the Lua module; otherwise, `expl3` will complain about duplicate variable declarations.

```

63 \str_new:N \l__spintent_luaset_cal_fam_ok_str
64 \str_new:N \l__spintent_luaset_sym_fam_ok_str

```

(End of definition for `\l__spintent_luaset_cal_fam_ok_str` and `\l__spintent_luaset_sym_fam_ok_str`.)

11.6 Loading the Lua module and functions

Now we load the Lua module `spintent.lua` and generate the variants for the functions `\__spintent_luafun_spunit_lookup_alias:V` used by `\spunit` (§11.15), `\__spintent_luafun_spmoney_lookup_data:V` used by `\spmoney` (§11.17), `\__spintent_luafun_spmQ_scale_int:Vn` used by `\spmQ` (§11.30) and `\__spintent_luafun_clean_split_and_set:V` used by `\spnum` (§11.14) defined in it.

```

65 \lua_load_module:n { spintent.lua }
66 \cs_generate_variant:Nn \__spintent_luafun_spunit_lookup_alias:n { V }
67 \cs_generate_variant:Nn \__spintent_luafun_spmoney_lookup_data:n { V }
68 \cs_generate_variant:Nn \__spintent_luafun_spmQ_scale_int:nn { Vn }
69 \cs_generate_variant:Nn \__spintent_luafun_clean_split_and_set:n { V }

```

(End of definition for `\__spintent_luafun_spunit_lookup_alias:V` and others.)

11.7 Internal implementation for `\mathcal` and `\rightanglesqr`

To simplify user configuration and obtain the expected output style pdf_TTeX for `\mathcal`, we will provide a fallback to the font NewCMMath-Regular.otf, which contains the glyphs for these characters. Using this same font, we will obtain the symbol `\rightanglesqr` for the key `recto`.

```

mathcal-fallback
right-angle-sqr-fallback

```

First, we'll define two error messages in case our fallback fails.

```

70 \hook_gput_code:nnn { begindocument } { spintent }
71   {
72     \__spintent_luafun_init_math_fallbacks:
73   }
74 \msg_new:nnn { spintent } { mathcal-fallback }
75   {
76     Using~classic~\token_to_str:N \mathcal \c_space_tl as~fallback~(font~not~found~or~
77     no~free~math~family~available).~\msg_line_context:
78   }
79 \msg_new:nnn { spintent } { right-angle-sqr-fallback }
80   {
81     Using~\token_to_str:N \rightangle \c_space_tl as~fallback~for~the~right-angle~

```

```

82     glyph.~\msg_line_context:
83 }

```

(End of definition for `mathcal-fallback` and `right-angle-sqr-fallback`.)

`\__spintent_mathcal:n`

Now we define the internal function `\__spintent_mathcal:n` for `\mathcal` which checks the state of the variable `\__spintent_mathcal_bool` set by the package key `mathcal`; if its state is true, we check the string variable `\__spintent_luaset_cal_fam_ok_str` and if the latter has the value true, we call the function `\__spintent_luafun_classic_mathcal:n` and otherwise (we cannot find the source in the system) we return a warning message and directly use `\mathcal`. Otherwise, that is, `mathcal=false` we simply use `\mathcal`.

```

84 \cs_new_protected:Nn \__spintent_mathcal:n
85 {
86     \bool_if:NTF \__spintent_mathcal_bool
87     {
88         \str_if_eq:VnTF \__spintent_luaset_cal_fam_ok_str { true }
89         { \__spintent_luafun_classic_mathcal:n {#1} }
90         {
91             \msg_warning:nn { spintent } { mathcal-fallback }
92             \mathcal {#1}
93         }
94     }
95     { \mathcal {#1} }
96 }

```

(End of definition for `\__spintent_mathcal:n`.)

`\__spintent_right_angle_sqr:`

The internal function `\__spintent_right_angle_sqr:` establishes the internal copy of the command `\rightanglesqr`. First, we check the string variable `\__spintent_luaset_sym_fam_ok_str`. If it is true, we call the function `\__spintent__luafun_right_angle_sqr:`; otherwise (we do not find the font in the system), we return a warning message and use `\rightangle` instead.

```

97 \cs_new_protected:Nn \__spintent_right_angle_sqr:
98 {
99     \str_if_eq:VnTF \__spintent_luaset_sym_fam_ok_str { true }
100     { \__spintent_luafun_right_angle_sqr: }
101     {
102         \msg_warning:nn { spintent } { right-angle-sqr-fallback }
103         \rightangle
104     }
105 }

```

(End of definition for `\__spintent_right_angle_sqr:`.)

11.8 Internal copy of the unicode invisible separator

`\__spintent_invisible_sep:`
`\c__spintent_invisible_sep_tl`

The function `\__spintent_invisible_sep:` is an internal copy of the Unicode invisible separator U-2063 that uses `\luamml_annotate:en` from the package `luamml[2]` and let `<mo>...</mo>` in the MathML structure embedded in the PDF output.

```

106 \cs_new_protected:Nn \__spintent_invisible_sep:
107 {
108     \__spintent_luafun_invisible_sep:
109 }

```

The token list constant `\c__spintent_invisible_sep_tl` is an internal copy of the Unicode invisible separator U-2063 using the primitive `\Umathchardef` from LuaTeX which leaves `<mi>...</mi>` in the structure MathML embedded in the output PDF.

```

110 \hook_gput_code:nnn { begindocument } { spintent }
111 {
112     \Umathchardef \c__spintent_invisible_sep_tl = "0 "0 "2063
113 }

```

- Both copies are used for different purposes, the function `\__spintent_invisible_sep:` will be used to force the start of a `<mrow>` in the structure MathML, the token list constant `\c__spintent_invisible_sep_tl` will be used to inject text into the structure MathML when we use `\MathMLintent{<text>}`.

(End of definition for `\__spintent_invisible_sep:` and `\c__spintent_invisible_sep_tl`.)

11.9 Normalize argument and affixes

We normalize the `{⟨argument⟩}` to support affixes (prefixes/suffixes) by trimming leading and trailing spaces, converting internal spaces to hyphens, collapsing consecutive hyphens, and removing leading or trailing hyphens.

`\__spintent_collapse_hyphens:N` A recursive helper to collapse multiple hyphens into a single one.

```

114 \cs_new_protected:Nn \__spintent_collapse_hyphens:N
115   {
116     \tl_if_in:NnT #1 { -- }
117     {
118       \tl_replace_all:Nnn #1 { -- } { - }
119       \__spintent_collapse_hyphens:N #1
120     }
121   }

```

(End of definition for `\__spintent_collapse_hyphens:N`.)

`\__spintent_sanitize_affix:Nn` The function `\__spintent_sanitize_affix:Nn` checks if the `{⟨argument⟩}` passed in ‘#2’ is *blank*. If so, it clears the target token list variable passed in ‘#1’. Otherwise, trimming bounds, converting spaces ‘ ’ to hyphens ‘-’, collapsing multiple hyphens, and safely stripping leading/trailing hyphens. For example, if you pass a target variable and raw text:

```
\__spintent_sanitize_affix:Nn \l__spintent_spsomesym_prefix_tl{ foo bar baz }
```

The function will “store” the normalized string `foo-bar-baz` inside `\l__spintent_spsomesym_prefix_tl`, ready to be conditionally appended.

```

122 \cs_new_protected:Nn \__spintent_sanitize_affix:Nn
123   {
124     \tl_if_blank:nTF {#2}
125     { \tl_clear:N #1 }
126     {
127       \tl_set:Ne #1 {#2}
128       \tl_trim_spaces:N #1
129       \tl_replace_all:Nnn #1 { ~ } { - }
130       \__spintent_collapse_hyphens:N #1
131       \tl_put_left:Nn #1 { \q_mark }
132       \tl_put_right:Nn #1 { \q_stop }
133       \tl_replace_all:Nnn #1 { \q_mark - } { \q_mark }
134       \tl_replace_all:Nnn #1 { - \q_stop } { \q_stop }
135       \tl_remove_all:Nn #1 { \q_mark }
136       \tl_remove_all:Nn #1 { \q_stop }
137     }
138   }
139 \cs_generate_variant:Nn \__spintent_sanitize_affix:Nn { cn }

```

(End of definition for `\__spintent_sanitize_affix:Nn`.)

11.10 The command `\setspintent`

The `\setspintent` command is used to configure `⟨keys⟩` “globally” for the utilities provided by `spintent`.

11.10.1 Internal variables and error messages for `\setspintent`

`\l__spintent_setspintent_input_arg_cmd_tl` The variable `\l__spintent_setspintent_input_arg_cmd_tl` will *store* the command or command name passed to the “first” `{⟨argument⟩}` ‘#1’ of the command `\setspintent`.

```
140 \tl_new:N \l__spintent_setspintent_input_arg_cmd_tl
```

Error message if the `{⟨argument⟩}` ‘#1’ passed to `\setspintent` is a “non-existent” command.

```

141 \msg_new:nnnn { spintent } { unknown-command-setup }
142   {
143     Cannot~configure~unknown~command~'\exp_not:c{#1}'.
144   }
145   {
146     You~attempted~to~use~\token_to_str:N \setspintent{#1}{...},~but~the~
147     command~\exp_not:c{#1}~is~not~defined.~Please~check~for~typos.
148   }

```

(End of definition for `\l__spintent_setspintent_input_arg_cmd_tl` and `unknown-command-setup`.)

```

__spintent_setspintent_set_keys:nn
__spintent_setspintent_set_keys:en

```

The function `__spintent_setspintent_set_keys:nn` will check if the command passed as `{⟨argument⟩}` exists in ‘#1’ and set the `⟨keys⟩` passed as `{⟨argument⟩}` in ‘#2’ to the correct path; otherwise, it will return an error.

```

149 \cs_new_protected:Nn __spintent_setspintent_set_keys:nn
150 {
151   \cs_if_exist:cTF { #1 }
152   {
153     \keys_set:nn { spintent / #1 } { #2 }
154   }
155   {
156     \msg_error:nnn { spintent } { unknown-command-setup } { #1 }
157   }
158 }
159 \cs_generate_variant:Nn __spintent_setspintent_set_keys:nn { en }

```

(End of definition for `__spintent_setspintent_set_keys:nn`.)

```

__spintent_setspintent_parse_args:nn
__spintent_setspintent_parse_args:Vn

```

The function `__spintent_setspintent_parse_args:nn` will check if the argument passed in #1 begins with ‘\’ or is just a *command name*. If it begins with ‘\’, it will remove it using `\cs_to_str:N` and then execute `__spintent_setspintent_set_keys:en`. Otherwise, i.e., if ‘\’ was not passed, it will directly execute `__spintent_setspintent_set_keys:nn`.

```

160 \cs_new_protected:Nn __spintent_setspintent_parse_args:nn
161 {
162   \tl_if_single:nTF { #1 }
163   {
164     \token_if_cs:NTF #1
165     {
166       __spintent_setspintent_set_keys:en { \cs_to_str:N #1 } { #2 }
167     }
168     {
169       __spintent_setspintent_set_keys:nn { #1 } { #2 }
170     }
171   }
172   {
173     __spintent_setspintent_set_keys:nn { #1 } { #2 }
174   }
175 }
176 \cs_generate_variant:Nn __spintent_setspintent_parse_args:nn { Vn }

```

(End of definition for `__spintent_setspintent_parse_args:nn`.)

`\setspintent`

Now we define the user command `\setspintent`.

```

177 \NewDocumentCommand \setspintent { m m }
178 {
179   \tl_if_blank:nTF { #1 }
180   {
181     \msg_error:nnn { spintent } { unknown-command-setup } { <empty> }
182   }
183   {
184     \tl_set:Nn \l__spintent_setspintent_input_arg_cmd_tl { #1 }
185     \tl_trim_spaces:N \l__spintent_setspintent_input_arg_cmd_tl
186     __spintent_setspintent_parse_args:Vn \l__spintent_setspintent_input_arg_cmd_tl { #2 }
187   }
188 }

```

(End of definition for `\setspintent`. This function is documented on page 3.)

11.11 Handling unknown keys

```

\l__spintent_command_name_str
unknown-choice
cmd-key-unknown
cmd-key-value-unknown

```

We define the variable `\l__spintent_command_name_str` which will *store* the “name” of each command within the implementation along with the messages `unknown-choice` used by `⟨keys⟩` that use `.choice:n` in their implementation and the messages `cmd-key-unknown`, `cmd-key-value-unknown` used by the `⟨key⟩` `unknown` in commands that use `[⟨key = val⟩]`.

```

189 \str_new:N \l__spintent_command_name_str
190 \msg_new:nnn { spintent } { unknown-choice }
191 {
192   The~value~'~#3'~for~'~#1'~key~is~invalid~use~('~#2').
193 }
194 \msg_new:nnnn { spintent } { cmd-key-unknown }
195 {
196   The~key~'~#1'~is~unknown~by~command~

```

```

197     \c_backslash_str \l__spintent_command_name_str \c_space_tl
198     and~is~being~ignored~\msg_line_context:.
199   }
200   {
201     The~command~\c_backslash_str \l__spintent_command_name_str \c_space_tl
202     does~not~have~a~key~called~'#1'.\\
203     Check~that~you~have~spelled~the~key~name~correctly.
204   }
205   \msg_new:nnnn { spintent } { cmd-key-value-unknown }
206   {
207     The~key~'#1=#2'~is~unknown~by~command~
208     \c_backslash_str \l__spintent_command_name_str \c_space_tl
209     and~is~being~ignored~\msg_line_context:.
210   }
211   {
212     The~command~\c_backslash_str \l__spintent_command_name_str \c_space_tl
213     does~not~have~a~key~called~'#1'.\\
214     Check~that~you~have~spelled~the~key~name~correctly.
215   }

```

(End of definition for `\l__spintent_command_name_str` and others.)

```

\__spintent_unknown_keys:n
\__spintent_unknown_keys:nn

```

The internal functions `\__spintent_unknown_keys:n` and `\__spintent_unknown_keys:nn` used by the *<key>* unknown.

```

216 \cs_new_protected:Nn \__spintent_unknown_keys_cmd:n
217   {
218     \exp_args:NV \__spintent_unknown_keys_cmd:nn \l_keys_key_str {#1}
219   }
220 \cs_new_protected:Nn \__spintent_unknown_keys_cmd:nn
221   {
222     \tl_if_blank:nTF {#2}
223     { \msg_error:nnn { spintent } { cmd-key-unknown } {#1} }
224     { \msg_error:nnnn { spintent } { cmd-key-value-unknown } {#1} {#2} }
225   }

```

(End of definition for `\__spintent_unknown_keys:n` and `\__spintent_unknown_keys:nn`.)

11.12 Definition of core base variables

```

\__spintent_luafun_clean_split_and_set:n
\__spintent_luafun_clean_split_and_set:V

```

The function `\__spintent_luafun_clean_split_and_set:n` defined in the Lua module `spintent.lua`, is common to several commands in this implementation. It analyzes, processes, cleans and splits the *{<argument>}* passed to commands using internal functions defined in the Lua module `spintent.lua`. It isolates signs, integer components, decimal separators, decimal parte, decimal periodic part, exponents and final physical “units”, assigning them directly to `expl3` variables.

This function assigns the states of the variables ‘_str’ or ‘_tl’ described below to `true`, `false`, `error` or *stores* information according to the role it fulfills within the implementation.

(End of definition for `\__spintent_luafun_clean_split_and_set:n`.)

```

\l__spintent_luaset_sign_tl
\l__spintent_luaset_part_int_tl
\l__spintent_luaset_dec_sep_tl
\l__spintent_luaset_part_dec_tl
\l__spintent_luaset_part_period_tl
\l__spintent_luaset_has_integer_str
\l__spintent_luaset_has_natural_str

```

The variable `\l__spintent_luaset_sign_tl` stores the explicit ‘+’ or ‘−’ sign if present. The variable `\l__spintent_luaset_part_int_tl` stores the raw digit sequence of the “integer part”. The variable `\l__spintent_luaset_dec_sep_tl` stores the matched ‘,’ or ‘.’ used as the decimal separator. The variable `\l__spintent_luaset_part_dec_tl` stores the raw digits of the “finite decimal part” that follow the separator, and the variable `\l__spintent_luaset_part_period_tl` stores the digits of the “infinite periodic decimal part” that follow a semicolon ‘;’.

The variable `\l__spintent_luaset_has_integer_str` store the state `true` when it is *only* an “integer”. The variable `\l__spintent_luaset_has_natural_str` store the state `true` when it is *only* an “natural number”.

```

226 \tl_new:N \l__spintent_luaset_sign_tl
227 \tl_new:N \l__spintent_luaset_part_int_tl
228 \tl_new:N \l__spintent_luaset_dec_sep_tl
229 \tl_new:N \l__spintent_luaset_part_dec_tl
230 \tl_new:N \l__spintent_luaset_part_period_tl
231 \str_new:N \l__spintent_luaset_has_integer_str
232 \str_new:N \l__spintent_luaset_has_natural_str

```

(End of definition for `\l__spintent_luaset_sign_tl` and others.)

```

\l__spintent_luaset_only_part_int_str
\l__spintent_luaset_only_part_dec_str
\l__spintent_luaset_only_part_period_str
\l__spintent_luaset_format_part_int_str
\l__spintent_luaset_format_part_dec_str

```

The literal entries of the numbers that we will pass to the *intent function* :number of `\MathMLintent` are *stored* in `\l__spintent_luaset_only_part_int_str` for the “*integer part*”, in `\l__spintent_luaset_only_part_dec_str` for the “*finite decimal part*”, and in `\l__spintent_luaset_only_part_period_str` for the “*infinite periodic decimal part*”.

Formatted versions (`cifras-sep=true`) are *stored* in `\l__spintent_luaset_format_part_int_str` for the “*integer part*” and `\l__spintent_luaset_format_part_dec_str` for the “*finite decimal part*”.

```

233 \str_new:N \l__spintent_luaset_only_part_int_str
234 \str_new:N \l__spintent_luaset_only_part_dec_str
235 \str_new:N \l__spintent_luaset_only_part_period_str
236 \str_new:N \l__spintent_luaset_format_part_int_str
237 \str_new:N \l__spintent_luaset_format_part_dec_str

```

(End of definition for `\l__spintent_luaset_only_part_int_str` and others.)

```

\l__spintent_luaset_millions_str
\l__spintent_luaset_decimal_period_str
\l__spintent_luaset_not_decimal_period_str
\l__spintent_luaset_not_decimal_not_period_str
\l__spintent_luaset_dec_is_all_zeros_str
\l__spintent_luaset_has_exponent_str
\l__spintent_luaset_exponent_tl

```

The flag variable `\l__spintent_luaset_millions_str` indicates whether the integer part translates exactly to a multiple of one million when passed to `\MathMLintent`. To properly structure the reading and writing of numbers in MathML, we use the flag variables `\l__spintent_luaset_decimal_period_str`, `\l__spintent_luaset_not_decimal_period_str`, and `\l__spintent_luaset_not_decimal_not_period_str`. The flag variable `\l__spintent_luaset_dec_is_all_zeros_str` monitors whether the “*finite decimal part*” is completely zero (useful for “*pure periodic decimals*”).

The flag variable `\l__spintent_luaset_has_exponent_str` indicates whether active “*scientific notation*” was detected at the end of the entered number, passed with ‘e’ or ‘E’. If true, it will store the digits of the exponent in `\l__spintent_luaset_exponent_tl`.

```

238 \str_new:N \l__spintent_luaset_millions_str
239 \str_new:N \l__spintent_luaset_decimal_period_str
240 \str_new:N \l__spintent_luaset_not_decimal_period_str
241 \str_new:N \l__spintent_luaset_not_decimal_not_period_str
242 \str_new:N \l__spintent_luaset_dec_is_all_zeros_str
243 \str_new:N \l__spintent_luaset_has_exponent_str
244 \tl_new:N \l__spintent_luaset_exponent_tl

```

(End of definition for `\l__spintent_luaset_millions_str` and others.)

```

\l__spintent_luaset_has_units_str
\l__spintent_luaset_status_str
\l__spintent_luaset_arg_above_tl
\l__spintent_luaset_arg_below_tl
\l__spintent_luaset_denom_has_number_str

```

Since the function `\__spintent_luafun_clean_split_and_set:n` is common to `\spnum` (§11.14) and `\spunit` (§11.15) (as well as others), it determines the following unit-related variables after processing the `{⟨arguments⟩}` via the Lua module `spintent.lua`.

First, it checks if there is any residual text *after* the processed number that is a candidate for physical “*units*”. It sets the flag variable `\l__spintent_luaset_has_units_str` accordingly. Following this, it verifies if this text contains more than one “/”. It then sets the variable `\l__spintent_luaset_status_str` to `valid` or `multislash`. If the structure is `valid`, it splits the unit into `\l__spintent_luaset_arg_above_tl` and `\l__spintent_luaset_arg_below_tl`. Finally, it analyzes `\l__spintent_luaset_arg_below_tl`; if the denominator starts with a number, it sets `\l__spintent_luaset_denom_has_number_str` to `true`, otherwise to `false`.

```

245 \str_new:N \l__spintent_luaset_has_units_str
246 \str_new:N \l__spintent_luaset_status_str
247 \tl_new:N \l__spintent_luaset_arg_above_tl
248 \tl_new:N \l__spintent_luaset_arg_below_tl
249 \str_new:N \l__spintent_luaset_denom_has_number_str

```

(End of definition for `\l__spintent_luaset_has_units_str` and others.)

11.13 Common messages for text mode and math mode

Messages shared by the different commands for text mode or math mode.

```

250 \msg_new:nnnn { spintent } { need-math-mode }
251 {
252   Math~mode~required~for~'#1'~\msg_line_context:.
253 }
254 {
255   Use~inside~$...$~or~in~math~environment.
256 }
257 \msg_new:nnnn { spintent } { need-text-mode }
258 {
259   Text~mode~required~for~'#1'~\msg_line_context:.
260 }
261 {
262   Use~outside~of~$...$~or~math~environment.
263 }

```

11.14 The command `\spnum`

The user command `\spnum` is *first* of “the big four” provided by the `spintent` package and is fundamental to the implementation of other commands. It handles the processing of numerical input, scientific notation, and units of measurement, using the Lua module `spintent.lua`, which is responsible for separating and assigning variables defined in `expl3`.

From the `expl3` side, we handle the printing logic and the *intent functions* passed to `\MathMLintent` to achieve a valid MathML structure that is accepted by MathCAT.

11.14.1 Definition of keys and variables for `\spnum`

The variable `\l__spintent_spnum_read_terse_bool` handled by the key `read-sign`, controls the *intent* passed to `\MathMLintent` to spoken the ‘+’ or ‘-’. If set to `clear`, it will say “*positivo*” or “*negativo*” after reading the number; if set to `terse`, it will say “*más*” or “*menos*” before reading the number.

The variable `\l__spintent_spnum_read_period_sep_str` handled by the key `read-period-sep`, controls how the decimal separator ‘.’ (periodic part) is printed and spoken when the `{(argument)}` is a *pure decimal periodic* and is passed the *intent* to `\MathMLintent`. If set to `coma`, it will say “*coma*” and print ‘.’, if set to `punto` it will say “*punto*” and print ‘.’.

The variable `\l__spintent_spnum__notation_sym_tl`, handled by the key `notation-sym`, determines whether ‘x’ will be printed when set to `times` or ‘.’ when set to `cdot`.

The variable `\l__spintent_spnum_intent_read_sign_str` will *store* the spoken translation used in the *intent* function passed to `\MathMLintent` for the ‘+’ or ‘-’ according to the value passed to the key `read-sign`.

The variable `\l__spintent_spnum_intent_read_dec_sep_str` *stores* the spoken translation that will be used in the *intent* function passed to `\MathMLintent` for reading the decimal separation as a “*coma*” or a “*punto*” according to the value found in the variable `\l__spintent_luaset_dec_sep_tl`.

```
264 \bool_new:N \l__spintent_spnum_read_terse_bool
265 \str_new:N \l__spintent_spnum_read_period_sep_str
266 \tl_new:N \l__spintent_spnum_notation_sym_tl
267 \str_new:N \l__spintent_spnum_intent_read_sign_str
268 \str_new:N \l__spintent_spnum_intent_read_dec_sep_str
```

(End of definition for `\l__spintent_spnum_read_terse_bool` and others.)

```
cifras-sep  Now we add the keys cifras-sep, read-sign, read-period-sep and notation-sym.
read-sign
read-period-sep
notation-sym

269 \keys_define:nn { spintent/spnum }
270 {
271   cifras-sep                .bool_set:N = \l__spintent_spnum_cifras_sep_bool,
272   cifras-sep                .initial:n = true,
273   cifras-sep                .value_required:n = true,
274   read-sign                 .choices:nn =
275     { terse , clear }
276     {
277       \int_case:nn { \l_keys_choice_int }
278       {
279         {1} { \bool_set_true:N \l__spintent_spnum_read_terse_bool }
280         {2} { \bool_set_false:N \l__spintent_spnum_read_terse_bool }
281       }
282     },
283   read-sign                 .initial:n = terse,
284   read-sign                 .value_required:n = true,
285   read-sign / unknown       .code:n =
286     \msg_error:nneee { spintent } { unknown-choice }
287     { read-sign } { terse , ~clear } { \exp_not:n {#1} },
288   read-period-sep           .choices:nn =
289     { coma , punto }
290     {
291       \int_case:nn { \l_keys_choice_int }
292       {
293         {1} { \str_set:Nn \l__spintent_spnum_read_period_sep_str { coma } }
294         {2} { \str_set:Nn \l__spintent_spnum_read_period_sep_str { punto } }
295       }
296     },
297   read-period-sep           .initial:n = coma,
298   read-period-sep           .value_required:n = true,
299   read-period-sep / unknown .code:n =
300     \msg_error:nneee { spintent } { unknown-choice }
301     { read-period-sep } { coma , ~punto } { \exp_not:n {#1} },
302   notation-sym              .choices:nn =
303     { times , cdot }
```

```

304     {
305       \int_case:nn { \l_keys_choice_int }
306       {
307         {1} { \tl_set:Nn \__spintent_snum_notation_sym_tl { \times } }
308         {2} { \tl_set:Nn \__spintent_snum_notation_sym_tl { \cdot } }
309       }
310     },
311     notation-sym .initial:n = cdot,
312     notation-sym .value_required:n = true,
313     notation-sym / unknown .code:n =
314       \msg_error:nneee { spintent } { unknown-choice }
315       { notation-sym } { times , ~ cdot } { \exp_not:n {#1} },
316     unknown .code:n =
317       {
318         \str_set:Nn \__spintent_command_name_str { snum }
319         \__spintent_unknown_keys_cmd:n {#1}
320       },
321   }

```

(End of definition for *cifras-sep* and others.)

11.14.2 Internal functions for \snum

`\__spintent_snum_render_part:n` The function `\__spintent_snum_render_part:n` processes the $\langle argument \rangle$ passed in ‘#1’ used by the functions `\__spintent_snum_render_int:` and `\__spintent_snum_render_dec:` to define the *intent function* :number for the integer and decimal part passed to `\MathMLintenc`. It evaluates whether the key *cifras-sep* is active or not.

```

322 \cs_new_protected:Nn \__spintent_snum_render_part:n
323 {
324   \MathMLintenc { \str_use:c { l__spintenc_luaset_only_part_#1_str } :number }
325   {
326     \bool_if:NTF \__spintenc_snum_cifras_sep_bool
327     { \str_use:c { l__spintenc_luaset_format_part_#1_str } }
328     { \tl_use:c { l__spintenc_luaset_part_#1_tl } }
329   }
330 }
331 \cs_new_protected:Nn \__spintenc_snum_render_int:
332 {
333   \__spintenc_snum_render_part:n { int }
334 }
335 \cs_new_protected:Nn \__spintenc_snum_render_dec:
336 {
337   \__spintenc_snum_render_part:n { dec }
338 }

```

(End of definition for `\__spintenc_snum_render_part:n`, `\__spintenc_snum_render_int:`, and `\__spintenc_snum_render_dec:`.)

`\__spintenc_snum_render_only_period:` The function `\__spintenc_snum_render_only_period:` isolates the “infinite periodic decimal part” from the “finite decimal part”, assigning the *intent function* :number passed to `\MathMLintenc` which will be used by `\MathMLarg` in the function `\__spintenc_snum_print_period_bar:`.

```

339 \cs_new_protected:Nn \__spintenc_snum_render_only_period:
340 {
341   \MathMLintenc { \l__spintenc_luaset_only_part_period_str :number }
342   {
343     \l__spintenc_luaset_part_period_tl
344   }
345 }

```

The function `\__spintenc_snum_print_period_bar:` inserts the function `\__spintenc_snum_render_only_period:` as an argument within the *intent function* `_periódico:postfix($dp)` passed to `\MathMLintenc`, generating the correct spoken for the “infinite periodic decimal part”.

```

346 \cs_new_protected:Nn \__spintenc_snum_print_period_bar:
347 {
348   \MathMLintenc { _periódico:postfix($dp) }
349   {
350     {
351       \overline
352       {
353         \MathMLarg { dp } { \__spintenc_snum_render_only_period: }
354       }
355     }
356 }

```

```
357 }
```

The function `\__spintent_snum_render_period_sep:` sets how the decimal separator handled by the key `read-period-sep` will be printed and spoken when a “*pure periodic decimal*” is passed.

```
358 \cs_new_protected:Nn \__spintent_snum_render_period_sep:
359 {
360   \str_if_eq:VnTF \l__spintent_snum_read_period_sep_str { coma }
361   {
362     \MathMLintent { _coma:prefix($pp) }
363     {
364       \mathord{,}
365       \MathMLarg { pp } { \__spintent_snum_print_period_bar: }
366     }
367   }
368   {
369     \MathMLintent { _punto:prefix($pp) }
370     {
371       \mathord{.}
372       \MathMLarg { pp } { \__spintent_snum_print_period_bar: }
373     }
374   }
375 }
```

(End of definition for `\__spintent_snum_render_only_period:`, `\__spintent_snum_print_period_bar:`, and `\__spintent_snum_render_period_sep:`.)

```
\__spintent_snum_render_decimal_sep:
```

The function `\__spintent_snum_render_decimal_sep:` parses the value of the variable `\l__spintent_luaset` and sets the variable `\l__spintent_snum_intent_read_dec_sep_str` with the function `_coma:prefix($dp)` for reading a “*coma*” or `_punto:prefix($dp)` for reading a “*punto*” to `\MathMLintent`. We print the decimal separator stored in `\l__spintent_luaset_dec_sep_tl` using `\mathord` to remove spaces around it and then use the command `\MathMLarg` where we insert `\__spintent_invisible_sep:` for compatibility with MathML and finally call the function `\__spintent_snum_render_dec:` to print the finite decimal part.

```
376 \cs_new_protected:Nn \__spintent_snum_render_decimal_sep:
377 {
378   \str_if_eq:VnTF \l__spintent_luaset_dec_sep_tl { , }
379   { \str_set:Nn \l__spintent_snum_intent_read_dec_sep_str { _coma } }
380   { \str_set:Nn \l__spintent_snum_intent_read_dec_sep_str { _punto } }
381   \MathMLintent { \l__spintent_snum_intent_read_dec_sep_str :prefix($dp) }
382   {
383     \mathord { \l__spintent_luaset_dec_sep_tl }
384     \MathMLarg { dp }
385     {
386       \__spintent_invisible_sep:
387       \__spintent_snum_render_dec:
388     }
389   }
390   % period part
391   \str_if_eq:VnTF \l__spintent_luaset_decimal_period_str { true }
392   {
393     \str_if_eq:VnTF \l__spintent_luaset_dec_is_all_zeros_str { true }
394     {
395       \__spintent_invisible_sep:
396       \__spintent_snum_print_period_bar:
397     }
398     {
399       \MathMLintent { _con:prefix($pnum) }
400       {
401         \__spintent_invisible_sep:
402         \MathMLarg { pnum }
403         {
404           \__spintent_snum_print_period_bar:
405         }
406       }
407     }
408   }
409 }
```

(End of definition for `\__spintent_snum_render_decimal_sep:`.)

```
\__spintent_snum_print_part_dec:
\__spintent_snum_print_part_period:
```

The function `\__spintent_snum_print_part_dec:` checks if a decimal part exists. If it does, it determines whether the decimal separator is a comma or a period to set the correct speech intent (“*coma*” or “*punto*”).

It then prints the separator, renders the decimal digits, and if a periodic sequence follows, it decides how to attach the periodic bar.

The function `\__spintent_snum_print_part_period:` handles cases where a periodic part exists. It evaluates if it should render the periodic separator directly, particularly when the number has a periodic part but lacks a standard decimal part.

```

410 \cs_new_protected:Nn \__spintent_snum_print_part_dec:
411 {
412   \tl_if_empty:NF \__spintent_luaset_part_dec_tl
413   {
414     \__spintent_snum_render_decimal_sep:
415   }
416 }
417 \cs_new_protected:Nn \__spintent_snum_print_part_period:
418 {
419   \tl_if_empty:NF \__spintent_luaset_part_period_tl
420   {
421     \str_if_eq:VnTF \__spintent_luaset_not_decimal_period_str { true }
422     { \__spintent_snum_render_period_sep: }
423     {
424       \tl_if_empty:NT \__spintent_luaset_part_dec_tl
425       {
426         \__spintent_snum_render_period_sep:
427       }
428     }
429   }
430 }

```

(End of definition for `\__spintent_snum_print_part_dec:` and `\__spintent_snum_print_part_period:`.)

`\__spintent_snum_print_integer:`
`\__spintent_snum_print_num_start:`
`\__spintent_snum_print_number_core:`

The function `\__spintent_snum_print_integer:` checks if the number consists only of an integer. If so, it simply renders it. If a decimal or periodic part exists, it sets up a `MathML` intent to link the integer part (respecting digit separators if enabled) to the subsequent decimal or periodic functions.

The function `\__spintent_snum_print_num_start:` checks if an explicit sign is present. If it finds one, it evaluates the terse reading flag to decide whether the sign should be read as a prefix (“*más*” or “*menos*”) or as a postfix (“*positivo*” or “*negativo*”), and wraps the intent around the rest of the number.

The function `\__spintent_snum_print_number_core:` acts as the main wrapper. It triggers the sign and base number evaluation, and then checks if a scientific exponent is present. If it is, it appends the correct base-10 notation symbol and exponent to complete the sequence.

📌 Note for `\__spintent_invisible_sep:`.

```

431 \cs_new_protected:Nn \__spintent_snum_print_integer:
432 {
433   \str_if_eq:VnTF \__spintent_luaset_not_decimal_not_period_str { true }
434   { \__spintent_snum_render_int: }
435   {
436     \MathMLintent { \__spintent_luaset_only_part_int_str :number:prefix($next) }
437     {
438       \bool_if:NTF \__spintent_snum_cifras_sep_bool
439       { \__spintent_luaset_format_part_int_str }
440       { \__spintent_luaset_part_int_tl }
441       \MathMLarg { next }
442       {
443         \tl_if_empty:NTF \__spintent_luaset_part_dec_tl
444         { \__spintent_snum_print_part_period: }
445         { \__spintent_snum_print_part_dec: }
446       }
447     }
448   }
449 }
450 \cs_new_protected:Nn \__spintent_snum_print_num_start:
451 {
452   \tl_if_empty:NTF \__spintent_luaset_sign_tl
453   {
454     \__spintent_invisible_sep: % need
455     \__spintent_snum_print_integer:
456   }
457   {
458     \bool_if:NTF \__spintent_snum_read_terse_bool
459     {
460       \str_if_eq:VnTF \__spintent_luaset_sign_tl { + }

```

```

461         { \str_set:Nn \l__spintrent_snum_intent_read_sign_str { _más:prefix($n)} }
462         { \str_set:Nn \l__spintrent_snum_intent_read_sign_str { _menos:prefix($n)} }
463     }
464     {
465         \str_if_eq:VnTF \l__spintrent_luaset_sign_tl { + }
466         { \str_set:Nn \l__spintrent_snum_intent_read_sign_str { _positivo:postfix($n) } }
467         { \str_set:Nn \l__spintrent_snum_intent_read_sign_str { _negativo:postfix($n) } }
468     }
469     \__spintrent_invisible_sep: % need
470     \MathMLintent { \l__spintrent_snum_intent_read_sign_str }
471     {
472         \l__spintrent_luaset_sign_tl
473         \MathMLarg { n } { \__spintrent_snum_print_integer: }
474     }
475 }
476 }
477 \cs_new_protected:Nn \__spintrent_snum_print_number_core:
478 {
479     \__spintrent_snum_print_num_start:
480     \str_if_eq:VnT \l__spintrent_luaset_has_exponent_str { true }
481     {
482         \MathMLintent { _por } { \l__spintrent_snum_notation_sym_tl }
483         10^{\l__spintrent_luaset_exponent_tl}
484     }
485 }

```

(End of definition for `\__spintrent_snum_print_integer:`, `\__spintrent_snum_print_num_start:`, and `\__spintrent_snum_print_number_core:`.)

11.14.3 Definition of error messages

spnum-has-units
spnum-no-digits

We define two error messages for the `\spnum` command. The first “error” triggers if the user includes “units” in the $\langle argument \rangle$ passed in ‘#1’, advising them to use the `\spunit` command instead. The second “error” is raised if the provided $\langle argument \rangle$ contains no numerical digits.

```

486 \msg_new:nnnn { spintrent } { spnum-has-units }
487 {
488     The~\token_to_str:N \spnum \c_space_tl command~does~not~accept~units~(''#1'').
489 }
490 {
491     Use~\token_to_str:N \spunit \c_space_tl if~you~need~to~print~numbers~with~units.
492 }
493 \msg_new:nnnn { spintrent } { spnum-no-digits }
494 {
495     The~\token_to_str:N \spnum \c_space_tl command~requires~a~valid~numerical~value.
496 }
497 {
498     You~provided~''#1',~which~contains~no~digits.
499 }

```

(End of definition for `spnum-has-units` and `spnum-no-digits`.)

11.14.4 Implementation of the `\spum` command

`\spnum` The public user command `\spnum` accepts an optional $[(key = val)]$ argument in ‘#1’ and a mandatory $\langle rational\ number \rangle$ in ‘#2’. It first checks if it is executed inside math mode, raising an error if it is not. If correct, it opens a local group to apply the options and passes the input to Lua for parsing via `\__spintrent_luafun_clean_split_and_set:n`.

Before printing, it validates the extracted data. It throws an error if it finds trailing units in the input or if the integer part is completely empty (no valid digits). If all checks pass, it calls `\__spintrent_snum_print_number_core:` to render the final number, and finally closes the group.

```

500 \NewDocumentCommand \spnum { O{} m }
501 {
502     \mode_if_math:TF
503     {
504         \group_begin:
505         \keys_set:nn { spintrent/spnum } { #1 }
506         \__spintrent_luafun_clean_split_and_set:n { \exp_not:n { #2 } }
507         \str_if_eq:VnTF \l__spintrent_luaset_has_units_str { true }
508         { \msg_error:nnn { spintrent } { spnum-has-units } { #2 } }
509         {
510             \tl_if_empty:NTF \l__spintrent_luaset_part_int_tl
511             { \msg_error:nnn { spintrent } { spnum-no-digits } { #2 } }
512             { \__spintrent_snum_print_number_core: }

```

```

513     }
514     \group_end:
515 }
516 { \msg_error:nnn { spintent } { need-math-mode } { \spnum } }
517 }

```

(End of definition for `\spnum`. This function is documented on page 3.)

11.15 The command `\spunit`

The user command `\spunit` is the *second* of “the big four” provided by the `spintent` package and is used to parse and print physical units and angular systems. It sends the $\langle argument \rangle$ to Lua module `spintent.lua` via `__spintent_luafun_clean_split_and_set:n` to separate and clean the $\langle argument \rangle$.

This ensures that all “units” (such as SI fractions, products, or sexagesimal angles) are processed consistently by the `spintent.lua`.

11.15.1 Definition of variables

```

\__spintent_spunit_luaset_canonical_str
\__spintent_spunit_luaset_lookup_status_str
\__spintent_spunit_luaset_read_str
\__spintent_spunit_luaset_is_compact_str
\__spintent_spunit_luaset_compact_exp_str
\__spintent_spunit_luaset_is_sexagesimal_str
\__spintent_spunit_luaset_status_str

```

These string variables store the data returned by the Lua module `spintent.lua`. They hold the canonical “unit symbol”, the dictionary lookup status, the correct speech text for NVDA/MathCAT, and specific flags that indicate if the “unit” is compact or represents a sexagesimal angle.

```

518 \str_new:N \__spintent_spunit_luaset_canonical_str
519 \str_new:N \__spintent_spunit_luaset_lookup_status_str
520 \str_new:N \__spintent_spunit_luaset_read_str
521 \str_new:N \__spintent_spunit_luaset_is_compact_str
522 \str_new:N \__spintent_spunit_luaset_compact_exp_str
523 \str_new:N \__spintent_spunit_luaset_is_sexagesimal_str
524 \str_new:N \__spintent_spunit_luaset_status_str

```

(End of definition for `\__spintent_spunit_luaset_canonical_str` and others.)

```

\__spintent_spunit_exponent_tl
\__spintent_spunit_unit_name_tl
\__spintent_spunit_read_slash_str
\__spintent_spunit_exp_seq
\__spintent_spunit_mult_seq
\__spintent_spunit_is_mult_bool
\__spintent_spunit_read_cdot_bool

```

These variables are used to process and format the “unit”. The sequences `\__spintent_spunit_mult_seq` and `\__spintent_spunit_exp_seq` split compound “units” at multiplication ‘`*`’ or exponent ‘`^`’ boundaries.

The boolean variables control specific rendering options, such as whether the multiplication dot ‘`\cdot`’ is explicitly read aloud or silently skipped.

```

525 \tl_new:N \__spintent_spunit_exponent_tl
526 \tl_new:N \__spintent_spunit_unit_name_tl
527 \str_new:N \__spintent_spunit_read_slash_str
528 \seq_new:N \__spintent_spunit_exp_seq
529 \seq_new:N \__spintent_spunit_mult_seq
530 \bool_new:N \__spintent_spunit_is_mult_bool
531 \bool_new:N \__spintent_spunit_read_cdot_bool

```

(End of definition for `\__spintent_spunit_exponent_tl` and others.)

11.15.2 Definition of error messages

```

spunit-invalid-unit
spunit-no-units
inline-numeric-denominator

```

We define three error messages for the `\spunit` command. The first “error” triggers if the “unit expression” provided in ‘`#1`’ is unknown or malformed. The second “error” occurs if no “units” are found in the $\langle argument \rangle$, advising the user to use `\spnum` for pure numbers. The third “error” is raised if a numeric coefficient is illegally placed in the denominator of an inline fraction (after a slash).

```

532 \msg_new:nnnn { spintent } { spunit-invalid-unit }
533 {
534   The~expression~'#1'~contains~an~unknown~or~malformed~unit~structure.
535 }
536 {
537   Check~spelling~or~verify~the~unit~is~defined~in~the~dictionary.
538 }
539 \msg_new:nnnn { spintent } { spunit-no-units }
540 {
541   The~\token_to_str:N \spunit \c_space_tl command~requires~at~least~one~unit~('#1').
542 }
543 {
544   Use~\token_to_str:N \spnum \c_space_tl if~you~only~need~to~format~a~pure~number.
545 }
546 \msg_new:nnnn { spintent } { inline-numeric-denominator }
547 {
548   Illegal~numeric~coefficient~in~inline~denominator~'#1'.
549 }
550 {
551   The~inline~mode~of~\token_to_str:N \spunit \c_space_tl
552   does~not~allow~numbers~after~the~slash~(/).
553 }

```

(End of definition for `spunit-invalid-unit`, `spunit-no-units`, and `inline-numeric-denominator`.)

11.15.3 Definition of keys for \spunit

Now we add the keys `print-cdot`, `read-cdot`, `read-slash`, `cifras-sep`, `read-period-sep` and `notation-sym`.

```

554 \keys_define:nn { spintent/spunit }
555 {
556   print-cdot      .bool_set:N = \l__spintent_spunit_print_cdot_bool,
557   print-cdot      .initial:n = false,
558   print-cdot      .value_required:n = true,
559   read-cdot       .bool_set:N = \l__spintent_spunit_read_cdot_bool,
560   read-cdot       .initial:n = false,
561   read-cdot       .value_required:n = true,
562   read-slash      .choices:nn =
563     { por , partido-por }
564   {
565     \int_case:nn { \l_keys_choice_int }
566     {
567       {1} { \str_set:Nn \l__spintent_spunit_read_slash_str { por } }
568       {2} { \str_set:Nn \l__spintent_spunit_read_slash_str { partido-por } }
569     }
570   },
571   read-slash      .initial:n = por,
572   read-slash      .value_required:n = true,
573   read-slash / unknown .code:n =
574     \msg_error:nneee { spintent } { unknown-choice }
575     { read-slash } { por, ~partido-por } { \exp_not:n {#1} },
576   cifras-sep      .meta:nn = { spintent/spnum } { cifras-sep = {#1} },
577   cifras-sep      .value_required:n = true,
578   read-period-sep .meta:nn = { spintent/spnum } { read-period-sep = {#1} },
579   read-period-sep .value_required:n = true,
580   notation-sym    .meta:nn = { spintent/spnum } { notation-sym = {#1} },
581   notation-sym    .value_required:n = true,
582   unknown         .code:n =
583     {
584       \str_set:Nn \l__spintent_command_name_str { spunit }
585       \__spintent_unknown_keys_cmd:n {#1}
586     },
587 }

```

(End of definition for `read-cdot` and others.)

11.15.4 Internal functions for \spunit

`\__spintent_spunit_format_canonical:` The function `\__spintent_spunit_format_canonical:` handles the visual formatting of the “unit symbol”. It specifically checks for the *liter symbol* ‘*ℓ*’ to print it as `\ell`, and formats all other valid “units” in standard upright text using `\mathrm`.

The function `\__spintent_spunit_process_base_exp:n` evaluates a “single unit” along with its exponent. It first looks up the unit ‘*#1*’ in the dictionary. If the “unit” is not found, it flags it as invalid. If found, it handles the spacing and multiplication dot ‘`\cdot`’ intents, and then renders the base unit and its exponent (either using a pre-defined compact exponent from Lua or by manually splitting the string at the ‘`^`’ symbol).

```

588 \cs_new_protected:Nn \__spintent_spunit_format_canonical:
589 {
590   \str_case:VnF \l__spintent_spunit_luaset_canonical_str
591   {
592     { ℓ } { \ell }
593   }
594   { \mathrm { \l__spintent_spunit_luaset_canonical_str } }
595 }
596 \cs_new_protected:Nn \__spintent_spunit_process_base_exp:n
597 {
598   \tl_clear:N \l__spintent_spunit_exponent_tl
599   \__spintent_luafun_spunit_lookup_alias:n { #1 }
600   \str_if_eq:VnTF \l__spintent_spunit_luaset_lookup_status_str { notfound }
601   {
602     \str_set:Nn \l__spintent_luaset_status_str { invalid }
603   }
604   {
605     \bool_if:NF \l__spintent_spunit_is_mult_bool
606     {
607       \bool_if:NTF \l__spintent_spunit_print_cdot_bool
608       {
609         \bool_if:NTF \l__spintent_spunit_read_cdot_bool

```

```

610         { \MathMLintent { por } { \cdot } }
611         { \MathMLintent { :silent } { \cdot } }
612     }
613     {
614         \bool_if:NTF \l__spintent_spunit_read_cdott_bool
615         { \MathMLintent { por } { \, } }
616         { \, }
617     }
618 }
619 \str_if_eq:VnTF \l__spintent_spunit_luaset_is_compact_str { true }
620 {
621     {
622         \MathMLintent { \l__spintent_spunit_luaset_read_str }
623         {
624             \__spintent_spunit_format_canonical:
625         }
626     }
627     ^ { \l__spintent_spunit_luaset_compact_exp_str }
628 }
629 {
630     \seq_set_split:Nnn \l__spintent_spunit_exp_seq { ^ } { #1 }
631     \seq_pop_left:NN \l__spintent_spunit_exp_seq \l__spintent_spunit_unit_name_tl
632     \seq_if_empty:NF \l__spintent_spunit_exp_seq
633     {
634         \seq_pop_left:NN \l__spintent_spunit_exp_seq \l__spintent_spunit_exponent_tl
635     }
636     \MathMLintent { \l__spintent_spunit_luaset_read_str }
637     {
638         \__spintent_spunit_format_canonical:
639     }
640     \tl_if_empty:NF \l__spintent_spunit_exponent_tl
641     {
642         ^ { \l__spintent_spunit_exponent_tl }
643     }
644 }
645 \bool_set_false:N \l__spintent_spunit_is_mult_bool
646 }
647 }

```

(End of definition for `\__spintent_spunit_format_canonical:` and `\__spintent_spunit_process_base_exp:n`.)

`\__spintent_spunit_process_mult:n`
`\__spintent_spunit_process_mult:V`

The function `\__spintent_spunit_process_mult:n` handles compound “units” joined by an explicit multiplication star ‘*’. It splits the `{\argument}` at each “star symbol” and applies `\__spintent_spunit_process_base_exp:n` to evaluate and render each resulting unit individually.

```

648 \cs_new_protected:Nn \__spintent_spunit_process_mult:n
649 {
650     \bool_set_true:N \l__spintent_spunit_is_mult_bool
651     \seq_set_split:Nnn \l__spintent_spunit_mult_seq { * } { #1 }
652     \seq_map_function:NN \l__spintent_spunit_mult_seq \__spintent_spunit_process_base_exp:n
653 }
654 \cs_generate_variant:Nn \__spintent_spunit_process_mult:n { V }

```

(End of definition for `\__spintent_spunit_process_mult:n`.)

`\__spintent_print_spunit_hierarchy:`

The function `\__spintent_print_spunit_hierarchy:` handles the layout of inline “unit” fractions. It first processes the “units” before the slash (the numerator). If a denominator exists, it prints the slash / ‘/’ with its corresponding speech intent, and then processes the remaining “units”.

```

655 \cs_new_protected:Nn \__spintent_print_spunit_hierarchy:
656 {
657     \tl_if_empty:NF \l__spintent_luaset_arg_above_tl
658     {
659         \__spintent_spunit_process_mult:V \l__spintent_luaset_arg_above_tl
660         \tl_if_empty:NF \l__spintent_luaset_arg_below_tl
661         {
662             \MathMLintent { \l__spintent_spunit_read_slash_str } { / }
663             \__spintent_spunit_process_mult:V \l__spintent_luaset_arg_below_tl
664         }
665     }
666 }

```

(End of definition for `\__spintent_print_spunit_hierarchy:`.)

`\__spintent_spunit_safe_exec:n`

The function `\__spintent_spunit_safe_exec:n` performs the main validation and layout for “units”. It first checks if the `{⟨argument⟩}` has units, is a valid expression, and does not contain illegal numbers in the denominator, throwing the appropriate “errors” if any check fails.

If the unit is valid, it checks if it is a sexagesimal angle (degrees, minutes, or seconds). For sexagesimal “units”, it prints the number and the symbol “*without any space in between*”, applying a slight negative space ‘\!’ for arcseconds. For standard units, it prints the number followed by a thin space ‘\,’ and then processes the unit sequence.

```

667 \cs_new_protected:Nn \__spintent_spunit_safe_exec:n
668 {
669   \str_if_eq:VnTF \l__spintent_luaset_has_units_str { false }
670   { \msg_error:nnn { spintent } { spunit-no-units } { #1 } }
671   {
672     \str_if_eq:VnTF \l__spintent_luaset_status_str { valid }
673     {
674       \str_if_eq:VnTF
675       \l__spintent_luaset_denom_has_number_str { true }
676       {
677         \msg_error:nnn { spintent }
678         { inline-numeric-denominator } { #1 }
679       }
680       {
681         \__spintent_luafun_spunit_lookup_alias:V \l__spintent_luaset_arg_above_tl
682         \str_if_eq:VnTF \l__spintent_spunit_luaset_is_sexagesimal_str { true }
683         {
684           \tl_if_empty:NF \l__spintent_luaset_part_int_tl
685           {
686             \__spintent_spnum_print_number_core:
687           }
688           \MathMLintent { \l__spintent_spunit_luaset_read_str }
689           {
690             \mathord
691             {
692               \str_case:Vn \l__spintent_spunit_luaset_canonical_str
693               {
694                 { " } { \prime \! \prime }
695                 { ' } { \prime }
696                 { ° } { ° }
697               }
698             }
699           }
700         }
701         {
702           \tl_if_empty:NF \l__spintent_luaset_part_int_tl
703           {
704             \__spintent_spnum_print_number_core: \,
705           }
706           \__spintent_print_spunit_hierarchy:
707         }
708       }
709     }
710     { \msg_error:nnn { spintent } { spunit-invalid-unit } { #1 } }
711   }
712 }

```

(End of definition for `\__spintent_spunit_safe_exec:n`.)

11.15.5 Implementation of the `\spunit` command

`\spunit`

The public user command `\spunit` accepts an optional `[⟨key = val⟩]` argument in ‘#1’ and a mandatory `{⟨unit expression⟩}` in ‘#2’. It first checks if it is executed inside *math mode*, raising an “error” if it is not. If correct, it opens a local group to apply the options and passes the `{⟨argument⟩}` to Lua module for parsing via `\__spintent_luafun_clean_split_and_set:n` function.

Finally, it delegates the execution to the function `\__spintent_spunit_safe_exec:n` to perform the safety checks and render the parsed data, before closing the group.

```

713 \NewDocumentCommand \spunit { O{} m }
714 {
715   \mode_if_math:TF
716   {
717     \group_begin:
718     \keys_set:nn { spintent/spunit } { #1 }
719     \__spintent_luafun_clean_split_and_set:n { \exp_not:n { #2 } }

```

```

720         \__spintent_spunit_safe_exec:n { #2 }
721     \group_end:
722 }
723 { \msg_error:nnn { spintent } { need-math-mode } { \spunit } }
724 }

```

(End of definition for `\spunit`. This function is documented on page 4.)

11.16 The commands `\spnewunit` and `\spunitalias`

The user commands `\spnewunit` and `\spunitalias` allow users to add new custom “units” or “aliases” to the package’s dictionary. Similar to `\spunit`, these commands delegate the processing and validation to the `spintent.lua` via `\__spintent_luafun_define_custom_unit:nn` and `\__spintent_luafun_define_spunit`. During the definition, the Lua module checks if the new “unit” or “alias” is valid and ensures it does not conflict with existing “units”. It returns the result of this operation to TeX using the `\l__spintent_spunit_luaset_status_str` variable. If a collision is detected or the `{⟨argument⟩}` is invalid, the package throws the corresponding “error” message.

11.16.1 Definition of error messages

```

spnewunit-duplicate
spunitalias-duplicate
spunitalias-invalid-expr

```

We define three error messages for the creation of “units” and “aliases”. The first two “errors” trigger if the user attempts to define a “new unit” or alias passed in ‘#1’ that already exists in the dictionary. The third “error” is raised by `\spunitalias` if the target expression provided in ‘#2’ is invalid (for example, if it contains unknown “units” or incorrect syntax).

```

725 \msg_new:nnnn { spintent } { spnewunit-duplicate }
726 {
727     The~unit~symbol~or~alias~'#1'~is~already~defined!
728 }
729 {
730     You~cannot~redefine~with~\token_to_str:N \spnewunit.
731 }
732 \msg_new:nnnn { spintent } { spunitalias-duplicate }
733 {
734     The~alias~'#1'~is~already~defined~or~reserved!
735 }
736 {
737     You~cannot~redefine~an~existing~unit~or~another~alias.
738 }
739 \msg_new:nnnn { spintent } { spunitalias-invalid-expr }
740 {
741     The~expression~'#2'~for~alias~'#1'~is~invalid.
742 }
743 {
744     It~must~contain~only~defined~units,~exponents~and~one~'/'~.
745 }

```

(End of definition for `spnewunit-duplicate`, `spunitalias-duplicate`, and `spunitalias-invalid-expr`.)

`\spnewunit`

The public command `\spnewunit` defines a new custom unit. It passes the new unit symbol ‘#1’ and its speech text ‘#2’ to Lua via `\__spintent_luafun_define_custom_unit:nn`. If the module reports that the unit already exists, it throws the corresponding duplicate error.

```

746 \NewDocumentCommand \spnewunit { m m }
747 {
748     \mode_if_math:TF
749     {
750         \msg_error:nnn { spintent } { need-text-mode } { \spnewunit }
751     }
752     {
753         \__spintent_luafun_define_custom_unit:nn { #1 } { #2 }
754         \str_if_eq:VnT \l__spintent_spunit_luaset_status_str { duplicate }
755         {
756             \msg_error:nnn { spintent } { spnewunit-duplicate } { #1 }
757         }
758     }
759 }

```

(End of definition for `\spnewunit`. This function is documented on page 6.)

`\spunitalias`

The public command `\spunitalias` creates a shortcut for a complex unit expression. It passes the new alias name ‘#1’ and the target expression ‘#2’ to Lua via `\__spintent_luafun_define_spunit_alias:nn`. It throws an error if the alias already exists, or if the provided target expression contains invalid syntax or unknown units.

```

760 \NewDocumentCommand \spunitalias { m m }

```

```

761 {
762   \mode_if_math:TF
763   {
764     \msg_error:nnn { spintent } { need-text-mode } { \spunitalias }
765   }
766   {
767     \__spintent_luafun_define_spunit_alias:nn { #1 } { #2 }
768     \str_if_eq:VnT \l__spintent_spunit_luaset_status_str { duplicate }
769     {
770       \msg_error:nnn { spintent } { spunitalias-duplicate } { #1 }
771     }
772     \str_if_eq:VnT \l__spintent_spunit_luaset_status_str { invalid-expr }
773     {
774       \msg_error:nnnn { spintent } { spunitalias-invalid-expr } { #1 } { #2 }
775     }
776   }
777 }

```

(End of definition for `\spunitalias`. This function is documented on page 6.)

11.17 The command `\spmoney`

The user command `\spmoney` is the *third* of “the big four” provided by the `spintent` package, designed to format monetary values and currencies. It delegates `{\argument}` parsing to the Lua module `spintent.lua` via `\__spintent_luafun_clean_split_and_set:n`. The module then retrieves the correct “currency symbol”, pluralization rules, and layout structures from the database.

The command accepts *optional arguments* to override the default “currency symbol” or enable “subunit” rendering. Finally, it constructs the MathML intent for MathCAT.

These string variables store the currency data returned by the Lua module `spintent.lua`. Upon a successful database lookup, the module populates these variables with the “currency symbol”, its layout position (pre or post), the appropriate singular and plural names for both the main unit and subunits, and the execution status flags. T_EX then uses this information to render the visual layout and construct the correct MathML speech intents.

```

778 \str_new:N \l__spintent_spmoney_luaset_symbol_str
779 \str_new:N \l__spintent_spmoney_luaset_position_str
780 \str_new:N \l__spintent_spmoney_luaset_sing_str
781 \str_new:N \l__spintent_spmoney_luaset_plur_str
782 \str_new:N \l__spintent_spmoney_luaset_conde_str
783 \str_new:N \l__spintent_spmoney_luaset_subsing_str
784 \str_new:N \l__spintent_spmoney_luaset_subplur_str
785 \str_new:N \l__spintent_spmoney_luaset_print_iso_str
786 \str_new:N \l__spintent_spmoney_luaset_currency_arg_str
787 \str_new:N \l__spintent_spmoney_luaset_status_str

```

(End of definition for `\l__spintent_spmoney_luaset_symbol_str` and others.)

The boolean variable tracks whether subunit rendering is enabled. The string variables assemble the specific speech text (intents) for NVDA/MathCAT, including the sign, the main currency, and the subunits. Finally, the remaining variables temporarily store the numeric value and currency code extracted from the user’s input.

```

788 \bool_new:N \l__spintent_spmoney_sub_units_bool
789 \str_new:N \l__spintent_spmoney_intent_money_str
790 \str_new:N \l__spintent_spmoney_intent_sign_str
791 \str_new:N \l__spintent_spmoney_intent_sub_unit_str
792 \str_new:N \l__spintent_spmoney_res_main_voice_str
793 \int_new:N \l__spintent_spmoney_subnum_int
794 \str_new:N \l__spintent_spmoney_extracted_curr_str
795 \tl_new:N \l__spintent_spmoney_extracted_num_tl

```

(End of definition for `\l__spintent_spmoney_sub_units_bool` and others.)

11.17.1 Definition of error messages

We define two messages to handle invalid currency configurations. The first “error” warns the user if subunit rendering is requested for a currency that does not support fractional divisions (such as JPY or CLP), safely ignoring the flag. The second “error” is triggered if the provided currency identifier is not registered in the Lua database.

```

796 \msg_new:nnnn { spintent } { currency-no-subunits }
797 {
798   The~currency~'#1'~does~not~support~subunits.~
799   The~option~'sub-units=true'~is~ignored.
800 }

```

```

801 {
802     Monies~like~the~Japanese~Yen~(JPY)~or~Chilean~Peso~(CLP)~
803     do~not~have~fractional~subunits~registered~in~Lua~module.~
804 }
805 \msg_new:nnnn { spintent } { invalid-currency }
806 {
807     Invalid~currency~identifier~'#1'~in~\token_to_str:N \spmoney .
808 }
809 {
810     The~provided~symbol,~alias,~or~ISO~code~does~not~exist~in~
811     the~Lua~module.
812 }

```

(End of definition for `currency-no-subunits` and `invalid-currency`.)

11.17.2 Auxiliary functions for \spmoney

```

__spintent_spmoney_set_currency:n
__spintent_spmoney_normalize_key:n
__spintent_spmoney_normalize_key:V

```

The function `\__spintent_spmoney_set_currency:n` validates the currency identifier provided in ‘`#1`’ against the database. It delegates the lookup to the helper function `\__spintent_spmoney_normalize_key:n`, which interfaces with the Lua module `spintent.lua`. If the module returns a not found status, an “error” is triggered. Otherwise, it stores the valid currency identifier in `\__spintent_spmoney_luaset_currency_arg_str` for subsequent processing.

```

813 \cs_new_protected:Nn __spintent_spmoney_set_currency:n
814 {
815     __spintent_spmoney_normalize_key:n {#1}
816     \str_if_eq:VnTF \__spintent_spmoney_luaset_status_str { notfound }
817     {
818         \msg_error:nnn { spintent } { invalid-currency } {#1}
819     }
820     { \str_set:Nn \__spintent_spmoney_luaset_currency_arg_str {#1} }
821 }
822 \cs_new_protected:Nn __spintent_spmoney_normalize_key:n
823 {
824     __spintent_luafun_spmoney_normalize_key:n { #1 }
825 }
826 \cs_generate_variant:Nn __spintent_spmoney_normalize_key:n { V }

```

(End of definition for `\__spintent_spmoney_set_currency:n` and `\__spintent_spmoney_normalize_key:n`.)

11.17.3 Definition of keys for \spmoney

```

currency
sub-units
dolar-math
cifras-sep

```

Now we add the keys `currency`, `sub-units`, `dolar-math` and `cifras-sep`.

```

827 \keys_define:nn { spintent / spmoney }
828 {
829     currency .code:n = { \__spintent_spmoney_set_currency:n {#1} },
830     currency .initial:n = { pesos },
831     currency .value_required:n = true,
832     sub-units .bool_set:N = \__spintent_spmoney_sub_units_bool,
833     sub-units .value_required:n = true,
834     dolar-math .bool_set:N = \__spintent_spmoney_dolar_math_bool,
835     dolar-math .initial:n = { true },
836     dolar-math .value_required:n = true,
837     cifras-sep .meta:nn = { spintent/spnum } { cifras-sep = {#1} },
838     cifras-sep .value_required:n = true,
839     unknown .code:n =
840     {
841         \str_set:Nn \__spintent_command_name_str { spmoney }
842         \__spintent_unknown_keys_cmd:n {#1}
843     },
844 }

```

(End of definition for `currency` and others.)

11.17.4 Internal functions for \spmoney

```

__spintent_spmoney_validate_money:

```

The function `\__spintent_spmoney_validate_money:` verifies if the parsed input contains an embedded currency identifier by checking `\__spintent_luaset_has_units_str`. If a currency is detected, it extracts and normalizes the key from `\__spintent_luaset_arg_above_tl`. It throws an “error” if the currency is not found in the database. If valid, it updates `\__spintent_spmoney_luaset_currency_arg_str` and retrieves the full currency metadata from the `spintent.lua` via `\__spintent_luafun_spmoney_lookup_data:V`.

```

845 \cs_new_protected:Nn __spintent_spmoney_validate_money:
846 {
847     \str_if_eq:VnT \__spintent_luaset_has_units_str { true }
848     {

```

```

849     \__spintent_spmoney_normalize_key:V \__spintent_luaset_arg_above_tl
850     \str_if_eq:VnTF \__spintent_spmoney_luaset_status_str { notfound }
851     { \msg_error:nne { spintent } { invalid-currency } { \__spintent_luaset_arg_above_tl } }
852     {
853         \str_set:NV
854         \__spintent_spmoney_luaset_currency_arg_str
855         \__spintent_luaset_arg_above_tl
856     }
857 }
858 \str_set:Nc \__spintent_spmoney_luaset_status_str { found }
859 \__spintent_luafun_spmoney_lookup_data:V \__spintent_spmoney_luaset_currency_arg_str
860 }

```

(End of definition for `\__spintent_spmoney_validate_money:`.)

`\__spintent_spmoney_print_symbol:`

The function `\__spintent_spmoney_print_symbol:` renders the “*currency symbol*”. If `\__spintent_spmoney_luaset_print_iso_str` is `true`, it outputs the ISO code using `\mathrm`. Otherwise, it prints the “*standard symbol*”. For dollar signs ‘\$’, it checks `\__spintent_spmoney_dolar_math_bool` to determine whether to render it directly as a math character ‘\$’ or wrap it inside `\text`.

```

861 \cs_new_protected:Nn \__spintent_spmoney_print_symbol:
862 {
863     \str_if_eq:VnTF \__spintent_spmoney_luaset_print_iso_str { true }
864     { \mathrm { \__spintent_spmoney_luaset_currency_arg_str } }
865     {
866         \str_if_eq:VnTF \__spintent_spmoney_luaset_symbol_str { $ }
867         {
868             \bool_if:NTF \__spintent_spmoney_dolar_math_bool
869             { \$ } { \text { \$ } }
870         }
871         { \__spintent_spmoney_luaset_symbol_str }
872     }
873 }

```

(End of definition for `\__spintent_spmoney_print_symbol:`.)

`\__spintent_spmoney_render_layout:`

The function `\__spintent_spmoney_render_layout:` determines the layout order of the “*currency symbol*” relative to the numeric value. It evaluates `\__spintent_spmoney_luaset_position_str`; if set to `pre`, it renders the “*currency symbol*” *before* the number node. Otherwise, it places the number first, followed by the “*currency symbol*”.

```

874 \cs_new_protected:Nn \__spintent_spmoney_render_layout:
875 {
876     \str_if_eq:VnTF \__spintent_spmoney_luaset_position_str { pre }
877     {
878         \__spintent_spmoney_print_symbol:
879         \MathMLarg { n } { \__spintent_spmoney_render_number_node: }
880     }
881     {
882         \MathMLarg { n } { \__spintent_spmoney_render_number_node: }
883         \__spintent_spmoney_print_symbol:
884     }
885 }

```

(End of definition for `\__spintent_spmoney_render_layout:`.)

`\__spintent_spmoney_render_number_node:`
`\__spintent_spmoney_render_only_integer_node:`

The function `\__spintent_spmoney_render_number_node:` renders the full numeric value, encompassing both the integer and decimal components. Conversely, the function `\__spintent_spmoney_render_only_integer_node:` outputs exclusively the integer portion, omitting any decimal data.

```

886 \cs_new_protected:Nn \__spintent_spmoney_render_number_node:
887 {
888     \__spintent_spnum_render_int:
889     \__spintent_spnum_print_part_dec:
890 }
891 \cs_new_protected:Nn \__spintent_spmoney_render_only_integer_node:
892 {
893     \__spintent_spnum_render_int:
894 }

```

(End of definition for `\__spintent_spmoney_render_number_node:` and `\__spintent_spmoney_render_only_integer_node:`.)

`\__spintent_spmoney_print_int:`
`\__spintent_spmoney_intent_int:`

The function `\__spintent_spmoney_print_int:` evaluates the presence of an explicit sign in `\l__spintent_luaset_sign_tl`. If a sign is detected, it assigns a prefix speech intent ‘más’ or ‘menos’ and embeds the sign and subsequent layout inside a `\MathMLintent`. If no sign is present, it routes execution based on whether subunits are enabled.

The function `\__spintent_spmoney_intent_int:` determines the correct grammatical inflection for the currency string (singular, plural, or the prepositional ‘de’ variant for exact millions). It evaluates the integer component, decimal boundaries, and zero-fills to select the appropriate string register, applying it as a postfix `MathML` intent over the layout rendered by `\__spintent_spmoney_render_layout:`.

```

895 \cs_new_protected:Nn \__spintent_spmoney_print_int:
896 {
897   \tl_if_empty:NTF \l__spintent_luaset_sign_tl
898   {
899     \bool_if:NTF \l__spintent_spmoney_sub_units_bool
900     { \__spintent_spmoney_set_and_print_sub_units: }
901     { \__spintent_spmoney_intent_int: }
902   }
903   {
904     \str_if_eq:VnTF \l__spintent_luaset_sign_tl { + }
905     {
906       \str_set:Nn \l__spintent_spmoney_intent_sign_str { _más:prefix ($n) }
907     }
908     {
909       \str_set:Nn \l__spintent_spmoney_intent_sign_str { _menos:prefix ($n) }
910     }
911     \__spintent_invisible_sep:
912     \MathMLintent { \l__spintent_spmoney_intent_sign_str }
913     {
914       \l__spintent_luaset_sign_tl
915       \MathMLarg { n }
916       {
917         \bool_if:NTF \l__spintent_spmoney_sub_units_bool
918         { \__spintent_spmoney_set_and_print_sub_units: }
919         { \__spintent_spmoney_intent_int: }
920       }
921     }
922   }
923 }
924 \cs_new_protected:Nn \__spintent_spmoney_intent_int:
925 {
926   \tl_if_empty:NTF \l__spintent_luaset_dec_sep_tl
927   {
928     \str_if_eq:VnTF \l__spintent_luaset_only_part_int_str { 1 }
929     {
930       \str_set:NV \l__spintent_spmoney_intent_money_str \l__spintent_spmoney_luaset_sing_str
931     }
932     {
933       \str_set:NV \l__spintent_spmoney_intent_money_str \l__spintent_spmoney_luaset_plur_str
934     }
935     \str_if_eq:VnT \l__spintent_luaset_millions_str { true }
936     {
937       \str_set:NV \l__spintent_spmoney_intent_money_str \l__spintent_spmoney_luaset_conde_s
938     }
939   }
940   {
941     \str_set:NV \l__spintent_spmoney_intent_money_str \l__spintent_spmoney_luaset_plur_str
942     \str_if_eq:VnT \l__spintent_luaset_millions_str { true }
943     {
944       \str_if_eq:VnTF \l__spintent_luaset_dec_is_all_zeros_str { true }
945       {
946         \str_set:NV \l__spintent_spmoney_intent_money_str \l__spintent_spmoney_luaset_conde
947       }
948       {
949         \str_set:NV \l__spintent_spmoney_intent_money_str \l__spintent_spmoney_luaset_plur
950       }
951     }
952   }
953   \__spintent_invisible_sep: % need for MathCAT
954   \MathMLintent { \l__spintent_spmoney_intent_money_str :postfix($n) }
955   {
956     \__spintent_spmoney_render_layout:

```

```

957     }
958 }

```

(End of definition for `\__spintent_spmoney_print_int:` and `\__spintent_spmoney_intent_int:`)

```

\__spintent_spmoney_check_sub_units:
spintent_spmoney_set_and_print_sub_units:

```

The function `\__spintent_spmoney_check_sub_units:` verifies whether the selected currency supports “*subunits*”. If the database returns empty subunit data, it triggers a warning and automatically disables the “*subunit*” rendering flag.

The function `\__spintent_spmoney_set_and_print_sub_units:` processes and formats the speech intents when “*subunits*” are active. It normalizes the decimal component (for instance, padding a single-digit decimal like ‘5’ to ‘50’), evaluates the correct singular or plural inflections for both the main “*currency*” and the “*subunits*”, and delegates the final MathML tree assembly to `\__spintent_spmoney_build_tree:`.

```

959 \cs_new_protected:Nn \__spintent_spmoney_check_sub_units:
960 {
961   \str_if_empty:NT \__spintent_spmoney_luaset_subsing_str
962   {
963     \msg_warning:nne { spintent } { currency-no-subunits }
964     { \__spintent_spmoney_luaset_currency_arg_str }
965     \bool_set_false:N \__spintent_spmoney_sub_units_bool
966   }
967 }
968 \cs_new_protected:Nn \__spintent_spmoney_set_and_print_sub_units:
969 {
970   \int_compare:nTF { \str_count:N \__spintent_luaset_only_part_dec_str == 1 }
971   {
972     \int_set:Nn \__spintent_spmoney_subnum_int
973     { \__spintent_luaset_only_part_dec_str * 10 }
974     \str_set:Ne \__spintent_luaset_only_part_dec_str
975     { \__spintent_luaset_only_part_dec_str 0 }
976   }
977   {
978     \int_set:Nn \__spintent_spmoney_subnum_int
979     { \__spintent_luaset_only_part_dec_str }
980   }
981   \int_compare:nTF { \__spintent_spmoney_subnum_int == 1 }
982   {
983     \str_set:Ne \__spintent_spmoney_intent_sub_unit_str
984     { \__spintent_spmoney_luaset_subsing_str :postfix($sub) }
985   }
986   {
987     \str_set:Ne \__spintent_spmoney_intent_sub_unit_str
988     { \__spintent_spmoney_luaset_subplur_str :postfix($sub) }
989   }
990   \str_if_eq:VnTF \__spintent_luaset_only_part_int_str { 1 }
991   {
992     \str_set:NV \__spintent_spmoney_res_main_voice_str
993     \__spintent_spmoney_luaset_sing_str
994   }
995   {
996     \str_set:NV \__spintent_spmoney_res_main_voice_str
997     \__spintent_spmoney_luaset_plur_str
998   }
999   \str_if_eq:VnT \__spintent_luaset_millions_str { true }
1000   {
1001     \str_set:NV \__spintent_spmoney_res_main_voice_str
1002     \__spintent_spmoney_luaset_conde_str
1003   }
1004   \__spintent_spmoney_build_tree:
1005 }

```

(End of definition for `\__spintent_spmoney_check_sub_units:` and `\__spintent_spmoney_set_and_print_sub_units:`)

```

\__spintent_spmoney_build_tree:
\__spintent_spmoney_print_sep_con:
\__spintent_spmoney_print_dec_sub_unit:

```

The function `\__spintent_spmoney_build_tree:` structures the final MathML tree assembly for fractional “*currencies*”. It arranges the integer component, the decimal separator, and the “*subunit*” component based on the layout position (pre or post) of the “*currency symbol*”.

Furthermore, `\__spintent_spmoney_print_sep_con:` applies the specific speech intent ‘con’ to the decimal separator, while `\__spintent_spmoney_print_dec_sub_unit:` binds the computed “*subunit*” intent to the decimal digits, ensuring accurate accessibility output.

```

1006 \cs_new_protected:Nn \__spintent_spmoney_build_tree:
1007 {

```

```

1008 \str_if_eq:VnTF \l__spintent_spmoney_luaset_position_str { pre }
1009 {
1010   \MathMLintent { \l__spintent_spmoney_res_main_voice_str :postfix($n) }
1011   {
1012     \__spintent_spmoney_print_symbol:
1013     \MathMLarg { n } { \__spintent_spmoney_render_only_integer_node: }
1014   }
1015   \__spintent_spmoney_print_sep_con:
1016   \__spintent_spmoney_print_dec_sub_unit:
1017 }
1018 {
1019   \MathMLintent { \l__spintent_spmoney_res_main_voice_str :postfix($n) }
1020   {
1021     \__spintent_invisible_sep:
1022     \MathMLarg { n } { \__spintent_spmoney_render_only_integer_node: }
1023   }
1024   \__spintent_spmoney_print_sep_con:
1025   \__spintent_spmoney_print_dec_sub_unit:
1026   \MathMLintent { :silent } { \__spintent_spmoney_print_symbol: }
1027 }
1028 }
1029 %^^A \cs_new_protected:Nn \__spintent_spmoney_print_integer_continue:
1030 %^^A {
1031 %^^A   \MathMLintent { \l__spintent_spmoney_res_main_voice_str :postfix($n) }
1032 %^^A   {
1033 %^^A     \MathMLarg { n } { \__spintent_spmoney_render_only_integer_node: }
1034 %^^A   }
1035 %^^A }
1036 \cs_new_protected:Nn \__spintent_spmoney_print_sep_con:
1037 {
1038   \MathMLintent { con }
1039   {
1040     \mathord { \l__spintent_luaset_dec_sep_tl }
1041   }
1042 }
1043 \cs_new_protected:Nn \__spintent_spmoney_print_dec_sub_unit:
1044 {
1045   \MathMLintent { \l__spintent_spmoney_intent_sub_unit_str }
1046   {
1047     \__spintent_invisible_sep:
1048     \MathMLarg { sub }
1049     {
1050       \__spintent_spmoney_render_dec:
1051     }
1052   }
1053 }

```

(End of definition for `\__spintent_spmoney_build_tree:`, `\__spintent_spmoney_print_sep_con:`, and `\__spintent_spmoney_print_dec_sub_unit:`.)

`\__spintent_spmoney_parse_and_route:n`

The internal function `\__spintent_spmoney_parse_and_route:n` processes the `{(argument)}` passed in ‘#1’ using Lua module to extract the numeric value and any “currency” identifier. If a “currency” is found (`\l__spintent_spmoney_extracted_curr_str`), it sets the corresponding variables. It then calls `\__spintent_spmoney_validate_money:` to verify the “currency”. If “subunit” rendering is enabled (`\l__spintent_spmoney_sub_units_bool`), it calls `\__spintent_spmoney_check_sub_units:`. Finally, it calls `\__spintent_spmoney_print_int:` to format the output.

```

1054 \cs_new_protected:Nn \__spintent_spmoney_parse_and_route:n
1055 {
1056   \__spintent_luafun_spmoney_prepare_input:n { #1 }
1057   \__spintent_luafun_clean_split_and_set:V \l__spintent_spmoney_extracted_num_tl
1058   \str_if_empty:NF \l__spintent_spmoney_extracted_curr_str
1059   {
1060     \str_set:Ne \l__spintent_luaset_has_units_str { true }
1061     \str_set:NV \l__spintent_luaset_arg_above_tl \l__spintent_spmoney_extracted_curr_str
1062   }
1063   \__spintent_spmoney_validate_money:
1064   \bool_if:NT \l__spintent_spmoney_sub_units_bool
1065   { \__spintent_spmoney_check_sub_units: }
1066   \__spintent_spmoney_print_int:
1067 }

```

(End of definition for `\__spintent_spmoney_parse_and_route:n`.)

`\spmoney` The public document command `\spmoney` formats monetary values with accessible speech intents. It accepts an optional argument ‘#1’ for local key-value configurations and a mandatory argument ‘#2’ containing the numeric value and optional embedded currency identifier. It first evaluates the typesetting context, triggering a fatal error if executed outside of math mode. Upon validation, it establishes a local $\TeX$ group to safely isolate the key assignments, delegates the raw input string to `\__spintent_spmoney_parse_and_route:n` for parsing and rendering, and subsequently closes the group to prevent scope leakage.

```

1068 \NewDocumentCommand \spmoney { 0{ } m }
1069 {
1070   \mode_if_math:TF
1071   {
1072     \group_begin:
1073     \keys_set:nn { spintent / spmoney } { #1 }
1074     \__spintent_spmoney_parse_and_route:n { #2 }
1075     \group_end:
1076   }
1077   { \msg_error:nnn { spintent } { need-math-mode } { \spmoney } }
1078 }

```

(End of definition for `\spmoney`. This function is documented on page 6.)

11.18 The command `\spshort`

The user command `\spshort` is the *fourth* and *final* of “the big four”. It manages the semantic injection and typographical formatting of *text mode* abbreviations, ordinals, and acronyms. Unlike *math mode* commands, which rely on MathML attributes, this command uses the PDF *tagging tools* provided by the `tagpdf`[29] package. Specifically, it uses the `E` (expanded) key to ensure that NVDA interpret the full form of the abbreviation, ordinal, or acronym in *text mode*.

These internal string variables serve as the primary data interface with the Lua module `spintent.lua`. During processing, the Lua module “stores” within these registers the execution status, the targeted typographical layout parameters, the phonetic replacement text for the `E` key intended for NVDA, the final sanitized output string, and the isolated structural components for ordinals (base and suffix).

```

1079 \str_new:N \__spintent_spshort_luaset_status_str
1080 \str_new:N \__spintent_spshort_luaset_layout_str
1081 \str_new:N \__spintent_spshort_luaset_expanded_str
1082 \str_new:N \__spintent_spshort_luaset_output_str
1083 \str_new:N \__spintent_spshort_luaset_base_str
1084 \str_new:N \__spintent_spshort_luaset_suffix_str

```

(End of definition for `\__spintent_spshort_luaset_status_str` and others.)

11.18.1 Definition of error messages for `\spshort`

unknown-abbreviation The internal “error” message `unknown-abbreviation` is triggered when the command `\spshort` encounters an invalid lookup state from the Lua module. It acts as a strict fallback exception when the provided `{\argument}` cannot be mapped to any registered database entry in `spintent.lua` nor successfully resolved through the grammatical ordinal expansion rules.

```

1085 \msg_new:nnnn { spintent } { unknown-abbreviation }
1086 { The~abbreviation~or~ordinal~'~#1'~is~invalid~or~not~recognized. }
1087 { Verify~the~spelling~or~check~the~grammar~rules~for~ordinals. }

```

(End of definition for `unknown-abbreviation`.)

11.18.2 Accessibility interface

`\__spintent_spshort_tag_span:nn` The internal function `\__spintent_spshort_tag_span:nn` processes the `{\argument}` passed in ‘#2’ using the tools provided by `tagpdf`. By utilizing the `tag` and `E` keys, it creates a native PDF `/E ( #1 )` structure and expands the `{\argument}` passed in ‘#1’ for proper reading with NVDA.

```

1088 \cs_new_protected:Nn \__spintent_spshort_tag_span:nn
1089 {
1090   \tag_mc_end_push:
1091   \tag_struct_begin:n { tag=Span, E={ #1 } }
1092   \tag_mc_begin:n { tag=Span }
1093   \tag_suspend:n { \spshort }
1094   #2
1095   \tag_resume:n { \spshort }
1096   \tag_mc_end:
1097   \tag_struct_end:
1098   \tag_mc_begin_pop:n {}
1099 }
1100 \cs_generate_variant:Nn \__spintent_spshort_tag_span:nn { en }

```

(End of definition for `\__spintent_spshort_tag_span:nn`.)

11.18.3 Definition of keys for \spshort

small-caps Now we add the keys `small-caps` and `read-arg`.

```
read-arg 1101 \keys_define:nn { spintent / spshort }
1102 {
1103     small-caps .bool_set:N = \l__spintent_spshort_smallcaps_bool,
1104     small-caps .initial:n = false,
1105     small-caps .value_required:n = true,
1106     read-arg .str_set:N = \l__spintent_spshort_read_arg_str,
1107     read-arg .initial:n = {},
1108     read-arg .value_required:n = true,
1109     unknown .code:n =
1110     {
1111         \str_set:Nn \l__spintent_command_name_str { spshort }
1112         \__spintent_unknown_keys_cmd:n {#1}
1113     },
1114 }
```

(End of definition for `small-caps` and `read-arg`.)

11.18.4 Internal functions for \spshort

`\__spintent_spshort_print:nn` The internal function `\__spintent_spshort_print:nn` acts as the primary formatter for text abbreviations. It clears the string variable `\l__spintent_spshort_read_arg_str` and evaluates the optional `<keys>` passed in `'#1'`. It then checks if a manual reading override was provided via those keys. If that string variable remains empty, it calls `\__spintent_spshort_process_and_render:n` to process the `{<argument>}` passed in `'#2'`. Otherwise, if an override is detected, it directly delegates the execution to `\__spintent_spshort_render_bypass:n`.

```
1115 \cs_new_protected:Nn \__spintent_spshort_print:nn
1116 {
1117     \str_clear:N \l__spintent_spshort_read_arg_str
1118     \keys_set:nn { spintent / spshort } {#1}
1119     \str_if_empty:NTF \l__spintent_spshort_read_arg_str
1120     {
1121         \__spintent_spshort_process_and_render:n {#2}
1122     }
1123     {
1124         \__spintent_spshort_render_bypass:n {#2}
1125     }
1126 }
```

(End of definition for `\__spintent_spshort_print:nn`.)

`\__spintent_spshort_process_and_render:n` The internal function `\__spintent_spshort_process_and_render:n` interfaces with the Lua module `spintent.lua` function `\__spintent_luafun_spshort_process:n` to resolve the abbreviation or ordinal `{<argument>}` passed in `'#1'`.

It subsequently evaluates the execution state stored within the string variable `\l__spintent_spshort_luaset_status` and dynamically routes execution to the corresponding rendering subroutine success, fallback or `error`. Any unrecognized status automatically defaults to the “error” handler.

```
1127 \cs_new_protected:Nn \__spintent_spshort_process_and_render:n
1128 {
1129     \__spintent_luafun_spshort_process:n {#1}
1130     \str_case:NnF \l__spintent_spshort_luaset_status_str
1131     {
1132         { success } { \__spintent_spshort_render_success: }
1133         { fallback } { \__spintent_spshort_render_fallback: }
1134         { error } { \__spintent_spshort_render_error:n {#1} }
1135     }
1136     { \__spintent_spshort_render_error:n {#1} }
1137 }
```

(End of definition for `\__spintent_spshort_process_and_render:n`.)

`\__spintent_spshort_render_success:` The function `\__spintent_spshort_render_success:` injects the key `E` and executes the targeted typographical layout. The `\__spintent_spshort_render_fallback:` function handles default cases, applying optional formatting such as `SMALL CAPS` to unrecognized or partially resolved terms.

`\__spintent_spshort_render_fallback:` Conversely, the function `\__spintent_spshort_render_bypass:n` directly maps the user-defined “speech” to the `{<argument>}`, bypassing the automated lookup Lua module. Finally, the function `\__spintent_spshort_render_error:n` triggers a structural exception while yielding the unformatted `{<argument>}` to prevent fatal compilation.

```
1138 \cs_new_protected:Nn \__spintent_spshort_render_success:
1139 {
```

```

1140     \__spintent_spshort_tag_span:en
1141     { \__spintent_spshort_luaset_expanded_str }
1142     { \__spintent_spshort_execute_layout: }
1143   }
1144   \cs_new_protected:Nn \__spintent_spshort_render_fallback:
1145   {
1146     \__spintent_spshort_tag_span:en
1147     { \__spintent_spshort_luaset_expanded_str }
1148     {
1149       \bool_if:NTF \__spintent_spshort_smallcaps_bool
1150       { \textsc{ \__spintent_spshort_luaset_output_str } }
1151       { \__spintent_spshort_luaset_output_str }
1152     }
1153   }
1154   \cs_new_protected:Nn \__spintent_spshort_render_bypass:n
1155   {
1156     \__spintent_spshort_tag_span:en { \__spintent_spshort_read_arg_str } { #1 }
1157   }
1158   \cs_new_protected:Nn \__spintent_spshort_render_error:n
1159   {
1160     \msg_error:nnn { spintent } { unknown-abbreviation } {#1}
1161   }

```

(End of definition for __spintent_spshort_render_success: and others.)

__spintent_spshort_execute_layout:

The internal function `\__spintent_spshort_execute_layout:` executes the typographical layout. It evaluates the descriptor “*stored*” within the string variable `\__spintent_spshort_luaset_layout_str` (such as `linear_regular`, `superscript`, or `small_caps_pure`) and maps it to the corresponding $\TeX$ formatting. Furthermore, it manages complex nested configurations, dynamically applying combinations such as superscripts integrated with conditional SMALL CAPS based on the active boolean variables.

```

1162   \cs_new_protected:Nn \__spintent_spshort_execute_layout:
1163   {
1164     \str_case:VnF \__spintent_spshort_luaset_layout_str
1165     {
1166       { linear_regular }
1167       {
1168         \bool_if:NTF \__spintent_spshort_smallcaps_bool
1169         { \textsc{ \__spintent_spshort_luaset_output_str } }
1170         { \__spintent_spshort_luaset_output_str }
1171       }
1172       { linear_caps }
1173       { \__spintent_spshort_luaset_output_str }
1174       { linear_mixed }
1175       { \__spintent_spshort_luaset_output_str }
1176       { superscript }
1177       {
1178         \__spintent_spshort_luaset_base_str
1179         \bool_if:NTF \__spintent_spshort_smallcaps_bool
1180         {
1181           \textsuperscript{
1182             \textsc{
1183               \str_lowercase:V \__spintent_spshort_luaset_suffix_str
1184             }
1185           }
1186         }
1187         {
1188           \textsuperscript{ \__spintent_spshort_luaset_suffix_str }
1189         }
1190       }
1191       { small_caps_pure }
1192       {
1193         \bool_if:NTF \__spintent_spshort_smallcaps_bool
1194         {
1195           \textsc{
1196             \str_lowercase:V \__spintent_spshort_luaset_output_str
1197           }
1198         }
1199         { \__spintent_spshort_luaset_output_str }
1200       }
1201       { acronym_long }
1202       { \__spintent_spshort_luaset_output_str }

```

```

1203     }
1204     { \l__spintent_spsshort_luaset_output_str }
1205 }

```

(End of definition for \l__spintent_spsshort_execute_layout:.)

\spsshort The public document command **\spsshort** manages the accessible formatting of *text mode* abbreviations, acronyms, and ordinals. It first triggers an error if invoked within a *math mode*, upon validation, puts **\mode_leave_vertical:** and establishes a local group to call the function **__spintent_spsshort_print:nn** for processing and printing.

```

1206 \NewDocumentCommand \spsshort { 0{} m }
1207 {
1208     \mode_if_math:TF
1209     {
1210         \msg_error:nnn { spintent } { need-text-mode } { \spsshort }
1211     }
1212     {
1213         \mode_leave_vertical:
1214         \group_begin:
1215         \__spintent_spsshort_print:nn {#1} {#2}
1216         \group_end:
1217     }
1218 }

```

(End of definition for \spsshort. This function is documented on page 7.)

11.19 The command \spsiglo

The public document command **\spsiglo** provides a semantic interface for typesetting century designations (e.g., siglo XXI). It accepts both Arabic and Roman numerals as $\langle \textit{argument} \rangle$, interfacing with the Lua module **spintent.lua** to validate, parse, and normalize chronological values.

This command work in dual-mode context awareness, operating uniformly across both *text mode* and *math mode*. When executed within *math mode*, it constructs an accessible **MathML** intent expression tree. Conversely, when invoked in standard *text mode*, it encapsulates the rendered output within a native PDF tagging structure (such as `/Alt (#1)`) containing an **alt** key.

\l__spintent_spsiglo_luaset_error_str These internal string variables handle data transfer and synchronization with the Lua module **spintent.lua**.
 \l__spintent_spsiglo_luaset_arabic_str They isolate the exception evaluation states, the Arabic numeral required for speech synthesis, the lowercase
 \l__spintent_spsiglo_luaset_roman_min_str Roman numeral designated for small caps typesetting via `\textsc`, and the localized chronological era modifier.
 \l__spintent_spsiglo_print_era_str

```

1219 \str_new:N \l__spintent_spsiglo_luaset_error_str
1220 \str_new:N \l__spintent_spsiglo_luaset_arabic_str
1221 \str_new:N \l__spintent_spsiglo_luaset_roman_min_str
1222 \str_new:N \l__spintent_spsiglo_print_era_str

```

(End of definition for \l__spintent_spsiglo_luaset_error_str and others.)

11.19.1 Definition of error messages for \spsiglo

invalid-century-format This internal error message is issued when the provided century identifier fails both Arabic and Roman numeral validation. It is triggered when the Lua module **spintent.lua** cannot map the $\langle \textit{argument} \rangle$ to an integer within the valid range of 1 to 4000, preventing incorrect speech synthesis.

```

1223 \msg_new:nnnn { spintent } { invalid-century-format }
1224 {
1225     Invalid~century~format~in~'#1'.
1226 }
1227 {
1228     The~argument~'#2'~is~not~a~valid~Arabic~or~Roman~numeral.~
1229     Ensure~the~value~is~between~1~and~4000.
1230 }

```

(End of definition for invalid-century-format.)

11.19.2 Definition of keys for \spsiglo

print-era Now we add the key **print-era**. User configuration determining if an era designation is appended, available values are **none**, **ac** (antes de cristo) and **dc** (después de cristo).

```

1231 \keys_define:nn { spintent / spsiglo }
1232 {
1233     print-era .choices:nn =
1234     { none , ac , dc }
1235     {
1236         \int_case:nn { \l_keys_choice_int }
1237         {

```

```

1238         {1} { \str_set:Nn \l__spintent_spsiglo_print_era_str { none } }
1239         {2} { \str_set:Nn \l__spintent_spsiglo_print_era_str { ac } }
1240         {3} { \str_set:Nn \l__spintent_spsiglo_print_era_str { dc } }
1241     }
1242 },
1243 print-era .initial:n = none,
1244 print-era .value_required:n = true,
1245 print-era / unknown .code:n =
1246     \msg_error:nneee { spintent } { unknown-choice }
1247     { print-era } { none, ~ac, ~dc } { \exp_not:n {#1} },
1248 unknown .code:n =
1249     {
1250         \str_set:Nn \l__spintent_command_name_str { spsiglo }
1251         \__spintent_unknown_keys_cmd:n {#1}
1252     },
1253 }

```

(End of definition for `print-era`)

11.19.3 Internal functions for \spsiglo

The functions `\__spintent_spsiglo_render_simple:nn` and `\__spintent_spsiglo_render_with_era:nnn` generate MathML structures when century designations are evaluated within *math mode*. They construct MathML intent structures, mapping the Arabic numerals to their phonetic equivalents. Furthermore, `\__spintent_spsiglo_render_with_era:nnn` integrates the era modifiers `ac` or `dc`. It adds invisible spacing and postfix intents to ensure correct NVDA/MathCAT pronunciation.

```

1254 \cs_new_protected:Nn \__spintent_spsiglo_render_simple:nn
1255 {
1256     \MathMLintent { #1:number } { \text { \textsc {#2} } } }
1257 }
1258 \cs_generate_variant:Nn \__spintent_spsiglo_render_simple:nn { VV }
1259 \cs_new_protected:Nn \__spintent_spsiglo_render_with_era:nnn
1260 {
1261     \str_if_eq:nnTF { #1 } { ac }
1262     {
1263         \MathMLintent { antes-de-cristo:postfix($z) }
1264         {
1265             \__spintent_invisible_sep:
1266             \MathMLarg { z }
1267             {
1268                 \MathMLintent { #2:number }
1269                 {
1270                     \text { \textsc {#3}~a.~C. }
1271                 }
1272             }
1273         }
1274     }
1275     {
1276         \MathMLintent { después-de-cristo:postfix($z) }
1277         {
1278             \__spintent_invisible_sep:
1279             \MathMLarg { z }
1280             {
1281                 \MathMLintent { #2:number }
1282                 {
1283                     \text { \textsc {#3}~d.~C. }
1284                 }
1285             }
1286         }
1287     }
1288 }
1289 \cs_generate_variant:Nn \__spintent_spsiglo_render_with_era:nnn { VVV }

```

(End of definition for `\__spintent_spsiglo_render_simple:nn` and `\__spintent_spsiglo_render_with_era:nnn`.)

The function `\__spintent_spsiglo_tag_span:nn` handles century formatting within *text mode*. It utilizes the `tagpdf` package to enclose the content inside a PDF /Alt (#1) structure. By passing the `{⟨argument⟩}` to the `alt` key, it embeds the chronological value directly into the PDF, ensuring correct NVDA/MathCAT pronunciation without relying on MathML intents.

```

1290 \cs_new_protected:Nn \__spintent_spsiglo_tag_span:nn
1291 {
1292     \tag_mc_end_push:

```

```

1293     \tag_struct_begin:n { tag=Span, alt={ #1 } }
1294     \tag_mc_begin:n { tag=Span }
1295     \tag_suspend:n { \spsiglo }
1296     #2
1297     \tag_resume:n { \spsiglo }
1298     \tag_mc_end:
1299     \tag_struct_end:
1300     \tag_mc_begin_pop:n {}
1301   }
1302   \cs_generate_variant:Nn \__spintent_spsiglo_tag_span:nn { en }

(End of definition for \__spintent_spsiglo_tag_span:nn.)

```

```

\__spintent_spsiglo_print_math:n
\__spintent_spsiglo_print_text:n

```

The functions `\__spintent_spsiglo_print_math:n` and `\__spintent_spsiglo_print_text:n` format century designations based on the active mode. Both first check the “error” status in the variable `\l__spintent_spsiglo_luaset_error_str` returned by the Lua module `spintent.lua` and issue an “error” if validation fails.

If the `{⟨argument⟩}` is valid, the function `\__spintent_spsiglo_print_math:n` operates in *math mode*, applying MathML structures depending on whether an era modifier is present. Conversely, the function `\__spintent_spsiglo_print_text:n` operates in *text mode*, utilizing the `tag` and `alt` keys to expand the value of the `print-era` option into full text (e.g., “antes de cristo”) for NVDA/MathCAT.

```

1303   \cs_new_protected:Nn \__spintent_spsiglo_print_math:n
1304   {
1305     \str_if_eq:VnTF \l__spintent_spsiglo_luaset_error_str { true }
1306     {
1307       \msg_error:nnnn { spintent } { invalid-century-format }
1308       { \spsiglo } { #1 }
1309     }
1310     {
1311       \str_if_eq:VnTF \l__spintent_spsiglo_print_era_str { none }
1312       {
1313         \__spintent_spsiglo_render_simple:VV
1314         \l__spintent_spsiglo_luaset_arabic_str
1315         \l__spintent_spsiglo_luaset_roman_min_str
1316       }
1317       {
1318         \__spintent_spsiglo_render_with_era:VVV
1319         \l__spintent_spsiglo_print_era_str
1320         \l__spintent_spsiglo_luaset_arabic_str
1321         \l__spintent_spsiglo_luaset_roman_min_str
1322       }
1323     }
1324   }
1325   \cs_new_protected:Nn \__spintent_spsiglo_print_text:n
1326   {
1327     \str_if_eq:VnTF \l__spintent_spsiglo_luaset_error_str { true }
1328     {
1329       \msg_error:nnnn { spintent } { invalid-century-format }
1330       { \spsiglo } { #1 }
1331     }
1332     {
1333       \str_case:Vn \l__spintent_spsiglo_print_era_str
1334       {
1335         { none }
1336         {
1337           \__spintent_spsiglo_tag_span:en
1338           { \l__spintent_spsiglo_luaset_arabic_str }
1339           { \textsc { \l__spintent_spsiglo_luaset_roman_min_str } }
1340         }
1341         { ac }
1342         {
1343           \__spintent_spsiglo_tag_span:en
1344           { \l__spintent_spsiglo_luaset_arabic_str ~ antes ~ de ~ cristo }
1345           { \textsc { \l__spintent_spsiglo_luaset_roman_min_str } ~ a.~C. }
1346         }
1347         { dc }
1348         {
1349           \__spintent_spsiglo_tag_span:en
1350           { \l__spintent_spsiglo_luaset_arabic_str ~ después ~ de ~ cristo }
1351           { \textsc { \l__spintent_spsiglo_luaset_roman_min_str } ~ d.~C. }
1352         }
1353       }
1354     }
1355   }

```

```

1353     }
1354   }
1355 }

```

(End of definition for `\__spintent_spsiglo_print_math:n` and `\__spintent_spsiglo_print_text:n`)

`\spsiglo` The public command `\spsiglo` is the main interface for century typesetting. It opens a local group and evaluates any optional `(keys)` passed in ‘#1’, then executes the function `\__spintent_luafun_spsiglo_parse:n` defined in the Lua module `spintent.lua` passed in ‘#2’ and formats the output for *math mode* or *text mode*.

```

1356 \NewDocumentCommand \spsiglo { 0{} m }
1357 {
1358   \group_begin:
1359     \keys_set:nn { spintent / spsiglo } { #1 }
1360     \__spintent_luafun_spsiglo_parse:n { #2 }
1361     \mode_if_math:TF
1362       { \__spintent_spsiglo_print_math:n { #2 } }
1363       {
1364         \mode_leave_vertical:
1365         \__spintent_spsiglo_print_text:n { #2 }
1366       }
1367   \group_end:
1368 }

```

(End of definition for `\spsiglo`. This function is documented on page 11.)

11.20 The command `\sptime`

The command `\sptime` is the main public interface for typesetting and tagging time expressions. It parses time string formats (such as HH:MM or HH:MM:SS) using the Lua function `\__spintent_luafun_sptime_parse:n`. This separates the hours, minutes, seconds, and fractions to construct a MathML *intent* tree for NVDA/MathCAT.

```

\__spintent_sptime_luaset_seconds_str
\__spintent_sptime_luaset_has_seconds_str
\__spintent_sptime_luaset_error_str
\__spintent_sptime_luaset_is_fraction_str
\__spintent_sptime_luaset_base_str

```

These internal string variables store the values returned from the Lua module `spintent.lua`. They hold the extracted time units, error flags, and boolean indicators (such as the presence of seconds or decimal fractions) used during formatting.

```

1369 \str_new:N \__spintent_sptime_luaset_seconds_str
1370 \str_new:N \__spintent_sptime_luaset_has_seconds_str
1371 \str_new:N \__spintent_sptime_luaset_error_str
1372 \str_new:N \__spintent_sptime_luaset_is_fraction_str
1373 \str_new:N \__spintent_sptime_luaset_base_str

```

(End of definition for `\__spintent_sptime_luaset_seconds_str` and others.)

11.20.1 Definition of error messages

`invalid-time-format`

The error message `invalid-time-format` defines the text displayed when an invalid time input is detected. It is triggered when an argument fails the format checks or contains values outside normal ranges, such as hours exceeding 23 or minutes and seconds exceeding 59.

```

1374 \msg_new:nnnn { spintent } { invalid-time-format }
1375 {
1376   Invalid~time~format~in~#1. \\\
1377   The~argument~'~#2'~does~not~match~any~supported~time~format.
1378 }
1379 {
1380   Allowed~formats:~HH:MM,~HH:MM:SS,~or~HH:MM:SS.ss. \\\
1381   Please~verify~that~hours~are~0-23~and~minutes/seconds~are~0-59.
1382 }

```

(End of definition for `invalid-time-format`.)

11.20.2 Internal functions for `\sptime`

`\__spintent_sptime_build_seconds:nn`

The internal function `\__spintent_sptime_build_seconds:nn` builds the MathML structure for the seconds component of a time expression. It wraps the numeric value ‘#2’ in speech intent tags, applying a connector prefix (passed in ‘#1’) and the “segundos” postfix so it is read correctly by NVDA/MathCAT.

```

1383 \cs_new_protected:Nn \__spintent_sptime_build_seconds:nn
1384 {
1385   \MathMLintent { #1:prefix($z) }
1386   {
1387     \text { : }
1388     \MathMLarg { z }
1389     {
1390       \MathMLintent { segundos:postfix($m) }
1391       {

```

```

1392         \__spintent_invisible_sep:
1393         \MathMLLarg { m }
1394         {
1395             \text { #2 }
1396         }
1397     }
1398 }
1399 }
1400 }

```

(End of definition for __spintent_sptime_build_seconds:nn.)

__spintent_sptime_build_tree: The internal function __spintent_sptime_build_tree: builds the complete MathML structure for the time expression. It checks the string variables \l__spintent_sptime_luaset_has_seconds_str and \l__spintent_sptime_luaset_is_fraction_str to determine if the time includes seconds or decimal fractions. Based on these values, it inserts the base time string and either calls __spintent_sptime_build_seconds: with the appropriate prefix ('con' or 'minutos-con'), or simply appends the 'minutos' intent tag if no seconds are present.

```

1401 \cs_new_protected:Nn \__spintent_sptime_build_tree:
1402 {
1403     \str_if_eq:VnTF \l__spintent_sptime_luaset_has_seconds_str { true }
1404     {
1405         \MathMLintent { :time }
1406         {
1407             \text { \l__spintent_sptime_luaset_base_str }
1408         }
1409         \str_if_eq:VnTF \l__spintent_sptime_luaset_is_fraction_str { true }
1410         {
1411             \__spintent_sptime_build_seconds:nn { con }
1412             { \l__spintent_sptime_luaset_seconds_str }
1413         }
1414         {
1415             \__spintent_sptime_build_seconds:nn { minutos-con }
1416             { \l__spintent_sptime_luaset_seconds_str }
1417         }
1418     }
1419     {
1420         \MathMLintent { :time }
1421         {
1422             \text { \l__spintent_sptime_luaset_base_str }
1423         }
1424         \str_if_eq:VnTF \l__spintent_sptime_luaset_is_fraction_str { false }
1425         {
1426             \MathMLintent { minutos }
1427             {
1428                 \__spintent_invisible_sep:
1429             }
1430         }
1431     }
1432 }

```

(End of definition for __spintent_sptime_build_tree:.)

\sptime The command \sptime is the public interface for formatting time expressions. It first checks if it is being used in math mode, issuing an error if not. Inside a local group, it parses the input using __spintent_luafun_sptime_parse:n and checks the error status in \l__spintent_sptime_luaset_error_str. If an invalid format is detected, it issues the invalid-time-format error; otherwise, it calls __spintent_sptime_build_tree: to assemble the MathML output.

```

1433 \NewDocumentCommand \sptime { m }
1434 {
1435     \mode_if_math:TF
1436     {
1437         \group_begin:
1438         \__spintent_luafun_sptime_parse:n { #1 }
1439         \str_if_eq:VnTF \l__spintent_sptime_luaset_error_str { true }
1440         {
1441             \msg_error:nnnn { spintent } { invalid-time-format }
1442             { \sptime } { #1 }
1443         }
1444         {
1445             \__spintent_sptime_build_tree:

```

```

1446         }
1447     \group_end:
1448 }
1449 { \msg_error:nnn { spintent } { need-math-mode } { \sptime } }
1450 }

```

(End of definition for `\sptime`. This function is documented on page 11.)

11.21 The command `\spdate`

The command `\spdate` is the main public command for typesetting and tagging date expressions. It parses date string formats (such as DD/MM/YYYY or YYYY-MM-DD) using the Lua function `\__spintent_luafun_spdate_parse:n`. This verifies the input and constructs a MathML `intent` tree for NVDA/MathCAT.

```

\__spintent_spdate_luaset_output_str
\__spintent_spdate_luaset_error_str

```

These internal string variables store the values returned from the Lua module `spintent.lua`. They hold the formatted date string and the error status used during formatting.

```

1451 \str_new:N \__spintent_spdate_luaset_output_str
1452 \str_new:N \__spintent_spdate_luaset_error_str

```

(End of definition for `\__spintent_spdate_luaset_output_str` and `\__spintent_spdate_luaset_error_str`.)

11.21.1 Definition of error messages

```
invalid-date-format
```

The error message `invalid-date-format` defines the text displayed when an invalid date input is detected. It is triggered when an argument fails the format checks or represents an invalid calendar date, such as `31/02/2024` or using an unsupported pattern like `YYYY/MM/DD`.

```

1453 \msg_new:nnnn { spintent } { invalid-date-format }
1454 {
1455     Invalid~date~or~unsupported~format~in~#1. \\\
1456     The~argument~'#2'~does~not~match~a~supported~format.
1457 }
1458 {
1459     Allowed~formats:~DD\slash MM\slash YYYY,~DD-MM-YYYY,~or~YYYY-MM-DD. \\\
1460     Ensure~the~day~and~month~are~valid~(e.g.,~avoid~31\slash 02\slash 2024).
1461 }

```

(End of definition for `invalid-date-format`.)

11.21.2 Internal functions for `\spdate`

```
\__spintent_spdate_process:n
```

The internal function `\__spintent_spdate_process:n` parses the input using `\__spintent_luafun_spdate_parse:n` and checks the error status in `\__spintent_spdate_luaset_error_str`. If an invalid format is detected, it issues the `invalid-date-format` error. Otherwise, it builds the MathML `intent` structure using the formatted date stored in `\__spintent_spdate_luaset_output_str`.

```

1462 \cs_new_protected:Nn \__spintent_spdate_process:n
1463 {
1464     \__spintent_luafun_spdate_parse:n { #1 }
1465     \str_if_eq:VnTF \__spintent_spdate_luaset_error_str { true }
1466     {
1467         \msg_error:nnnn { spintent } { invalid-date-format }
1468         { \spdate } { #1 }
1469     }
1470     {
1471         \MathMLintent { :date }
1472         {
1473             \text { \__spintent_spdate_luaset_output_str }
1474         }
1475     }
1476 }

```

(End of definition for `\__spintent_spdate_process:n`.)

```
\spdate
```

The command `\spdate` is the public interface for formatting date expressions. It first checks if it is being used in math mode, issuing an error if not. Inside a local group, it calls `\__spintent_spdate_process:n` to process the input.

```

1477 \NewDocumentCommand \spdate { m }
1478 {
1479     \mode_if_math:TF
1480     {
1481         \group_begin:
1482         \__spintent_spdate_process:n { #1 }
1483         \group_end:
1484     }
1485     { \msg_error:nnn { spintent } { need-math-mode } { \spdate } }
1486 }

```

(End of definition for `\spdate`. This function is documented on page 11.)

11.22 Semantic Operators

This section provides purely semantic operators. Unlike their formatting counterparts (which parse and format numbers), these commands do not process mandatory arguments. Instead, they solely inject a mathematical glyph wrapped in its corresponding regional `MathCAT` intent. This grants teachers absolute control when building complex algebraic expressions, mixed numbers, or fraction divisions.

11.23 The command `\spusep`

For the use of parentheses, we will provide the command `\spusep` with only two `(keys)` `size` and `silent`. Most of the time we can use `\left` and `\right` or `\Uleft` and `\Uright`, but both forms create a group, and this hinders the code for *tagged* PDF when we want to interrupt something between them.

spusep-empty-arg
spusep-invalid-arg

The first “error” message `spusep-empty-arg` is raised when `\spusep` receives an empty or blank `{(argument)}`, the second this is when an input is invalid.

```
1487 \msg_new:nnnn { spintent } { spusep-empty-arg }
1488 {
1489   Empty~argument~'#1'~for~\token_to_str:N \spusep.
1490 }
1491 {
1492   \token_to_str:N \spusep~requires~a~non-empty~argument.
1493 }
1494 \msg_new:nnn { spintent } { spusep-invalid-arg }
1495 {
1496   Invalid~argument~'#1'~for~\token_to_str:N \spusep.
1497 }
```

(End of definition for `spusep-empty-arg` and `spusep-invalid-arg`.)

__spintent_spusep_arg_tl
__spintent_spusep_left_tl
__spintent_spusep_right_tl

The variable `\__spintent_spusep_arg_tl` stores the `{(argument)}`, the variable `\__spintent_spusep_left_tl` and `\__spintent_spusep_right_tl` stores the parentheses.

```
1498 \tl_new:N \__spintent_spusep_arg_tl
1499 \tl_new:N \__spintent_spusep_left_tl
1500 \tl_new:N \__spintent_spusep_right_tl
```

(End of definition for `\__spintent_spusep_arg_tl`, `\__spintent_spusep_left_tl`, and `\__spintent_spusep_right_tl`.)

size
silent
unknown

We define the `(keys)` `size` and `silent`.

```
1501 \keys_define:nn { spintent / spusep }
1502 {
1503   size .choices:nn =
1504     { none , big , Big, bigg, Bigg }
1505     {
1506       \int_case:nn { \_keys_choice_int }
1507       {
1508         { 1 }
1509         {
1510           \tl_clear:N \__spintent_spusep_left_tl
1511           \tl_clear:N \__spintent_spusep_right_tl
1512         }
1513         { 2 }
1514         {
1515           \tl_set:Nn \__spintent_spusep_left_tl { \bigl }
1516           \tl_set:Nn \__spintent_spusep_right_tl { \bigr }
1517         }
1518         { 3 }
1519         {
1520           \tl_set:Nn \__spintent_spusep_left_tl { \Bigl }
1521           \tl_set:Nn \__spintent_spusep_right_tl { \Bigr }
1522         }
1523         { 4 }
1524         {
1525           \tl_set:Nn \__spintent_spusep_left_tl { \biggl }
1526           \tl_set:Nn \__spintent_spusep_right_tl { \biggr }
1527         }
1528         { 5 }
1529         {
1530           \tl_set:Nn \__spintent_spusep_left_tl { \Biggl }
1531           \tl_set:Nn \__spintent_spusep_right_tl { \Biggr }
1532         }
1533       }
1534     }
1535 }
```

```

1534     },
1535     size          .initial:n = none,
1536     size          .value_required:n = true,
1537     size / unknown .code:n =
1538       \msg_error:nneee { spintent } { unknown-choice }
1539     { size } { none,~big,~Big,~bigg,~Bigg } { \exp_not:n {#1} },
1540     silent        .bool_set:N = \__spintent_spusep_silent_bool,
1541     silent        .initial:n = false,
1542     silent        .value_required:n = true,
1543     unknown       .code:n =
1544       {
1545         \str_set:Nn \__spintent_command_name_str { spusep }
1546         \__spintent_unknown_keys_cmd:n {#1}
1547       },
1548   }

```

(End of definition for `size`, `silent`, and `unknown`.)

`\__spintent_spusep_set_parens:nn`

The function `\__spintent_spusep_set_parens:nn` will place the argument passed in ‘#2’ to the right of the variables `\__spintent_spusep_left_tl` and `\__spintent_spusep_right_tl` and then check the state of the variable `\__spintent_spusep_silent_bool` handled by the key `silent` to print.

```

1549 \cs_new_protected:Nn \__spintent_spusep_set_parens:nn
1550 {
1551   \tl_put_right:cn { \__spintent_spusep_ #1 _tl } { #2 }
1552   \bool_if:NTF \__spintent_spusep_silent_bool
1553   {
1554     \MathMLintent { :silent } { \tl_use:c { \__spintent_spusep_ #1 _tl } }
1555   }
1556   {
1557     \tl_use:c { \__spintent_spusep_ #1 _tl }
1558   }
1559 }

```

(End of definition for `\__spintent_spusep_set_parens:nn`.)

`\__spintent_spusep_convert:n`

The function `\__spintent_spusep_convert:n` captures and stores the $\langle argument \rangle$ passed in ‘#1’ in the variable `\__spintent_spusep_arg_tl`, validates the cases by converting them to the macros provided by `unicode-math`, and passes them to the function `\__spintent_spusep_set_parens:nn` for printing. If the input is not supported or is empty, we return an “error”.

```

1560 \cs_new_protected:Nn \__spintent_spusep_convert:n
1561 {
1562   \tl_set:Ne \__spintent_spusep_arg_tl { \tl_trim_spaces:n {#1} }
1563   \tl_if_empty:NT \__spintent_spusep_arg_tl
1564   {
1565     \msg_error:nnn { spintent } { spusep-empty-arg } {#1}
1566   }
1567   \str_case:VnF \__spintent_spusep_arg_tl
1568   {
1569     { ( }
1570     {
1571       \__spintent_spusep_set_parens:nn { left } { \lparen }
1572     }
1573     { ) }
1574     {
1575       \__spintent_spusep_set_parens:nn { right } { \rparen }
1576     }
1577     { [ ]
1578     {
1579       \__spintent_spusep_set_parens:nn { left } { \lbrack }
1580     }
1581     { ] }
1582     {
1583       \__spintent_spusep_set_parens:nn { right } { \rbrack }
1584     }
1585     { \{ }
1586     {
1587       \__spintent_spusep_set_parens:nn { left } { \lbrace }
1588     }
1589     { \} }
1590     {
1591       \__spintent_spusep_set_parens:nn { right } { \rbrace }
1592     }

```

```

1592     }
1593   }
1594   {
1595     \msg_error:nnn { spintent } { spusep-invalid-arg } {#1}
1596   }
1597 }

```

(End of definition for `\__spintent_spusep_convert:n`.)

\spusep The command `\spusep` checks that it is running in math mode, opens a local group, sets the keys passed in ‘#1’ and processes the $\langle argument \rangle$ passed in ‘#2’ by means of the function `\__spintent_spusep_convert:n`.

```

1598 \NewDocumentCommand \spusep { O{} m }
1599 {
1600   \mode_if_math:TF
1601   {
1602     \group_begin:
1603     \keys_set:nn { spintent / spusep } {#1}
1604     \__spintent_spusep_convert:n {#2}
1605     \group_end:
1606   }
1607   { \msg_error:nnn { spintent } { need-math-mode } { \spusep } }
1608 }

```

(End of definition for `\spusep`. This function is documented on page 12.)

11.23.1 The command `\spread`

The command `\spread` provides a semantic read for **MathCAT** of mathematical symbols for situations in which it is necessary to specify gender or plurality in Spanish.

spread-empty-args The error message `spread-empty-args` is raised when `\spread` receives an empty or blank $\langle argument \rangle$.

```

1609 \msg_new:nnnn { spintent } { spread-empty-args }
1610 { Empty~argument~in~\token_to_str:N \spread. }
1611 { \token_to_str:N \spread~requires~two~non-empty~arguments. }

```

(End of definition for `spread-empty-args`.)

__spintent_spread_intent_tl The variable `\__spintent_spread_intent_tl` stores the sanitized semantic reading $\langle argument \rangle$ for symbol to be injected into the `\MathMLintent`.

```

1612 \tl_new:N \__spintent_spread_intent_tl

```

(End of definition for `\__spintent_spread_intent_tl`.)

__spintent_spread_exec:nn The function `\__spintent_spread_exec:nn` implements the core logic for `\spread`. It verifies that neither $\langle argument \rangle$ is empty or blank. If valid, it evaluates the *reading* $\langle argument \rangle$ ‘#1’ using `\__spintent_sanitize_affix:Nn` and embeds it via `\MathMLintent` into the *math symbol* ‘#2’.

```

1613 \cs_new_protected:Nn \__spintent_spread_exec:nn
1614 {
1615   \bool_lazy_or:nnTF { \tl_if_blank_p:n { #1 } } { \tl_if_blank_p:n { #2 } }
1616   { \msg_error:nn { spintent } { spread-empty-args } }
1617   {
1618     \__spintent_sanitize_affix:Nn \__spintent_spread_intent_tl { #1 }
1619     \MathMLintent { \__spintent_spread_intent_tl } { #2 }
1620   }
1621 }

```

(End of definition for `\__spintent_spread_exec:nn`.)

\spread The command `\spread` assigns a custom semantic *reading* ‘#1’ to any mathematical *symbol* ‘#2’. It enforces math mode and passes execution to `\__spintent_spread_exec:nn`.

```

1622 \NewDocumentCommand \spread { m m }
1623 {
1624   \mode_if_math:TF
1625   {
1626     \group_begin:
1627     \__spintent_spread_exec:nn { #1 } { #2 }
1628     \group_end:
1629   }
1630   { \msg_error:nnn { spintent } { need-math-mode } { \spread } }
1631 }

```

(End of definition for `\spread`. This function is documented on page 11.)

11.23.2 The command \spdsym

Variables to store the regional reading string, the visual operator, and the optional semantic affixes specifically for `\spdsym`.

```
\l__spintent_spdsym_read_sym_tl
\l__spintent_spdsym_symbol_tl
\l__spintent_spdsym_prefix_tl
\l__spintent_spdsym_suffix_tl
```

(End of definition for `\l__spintent_spdsym_read_sym_tl` and others.)

```
prefix We define the (keys) prefix, suffix, set-sym and read-sym for \spdsym.
suffix
set-sym
read-sym
unknown
```

```
1636 \keys_define:nn { spintent / spdsym }
1637 {
1638   prefix .code:n =
1639   { \l__spintent_sanitize_affix:Nn \l__spintent_spdsym_prefix_tl {#1} },
1640   prefix .initial:n = ,
1641   prefix .value_required:n = true,
1642   suffix .code:n =
1643   { \l__spintent_sanitize_affix:Nn \l__spintent_spdsym_suffix_tl {#1} },
1644   suffix .initial:n = ,
1645   suffix .value_required:n = true,
1646   set-sym .choices:nn =
1647   { old-style , two-dots , slash }
1648   {
1649     \int_case:nn { \l_keys_choice_int }
1650     {
1651       {1} { \tl_set:Nn \l__spintent_spdsym_symbol_tl { \div } }
1652       {2} { \tl_set:Nn \l__spintent_spdsym_symbol_tl { : } }
1653       {3} { \tl_set:Nn \l__spintent_spdsym_symbol_tl { / } }
1654     }
1655   },
1656   set-sym .initial:n = two-dots,
1657   set-sym .value_required:n = true,
1658   set-sym / unknown .code:n =
1659   \msg_error:nneee { spintent } { unknown-choice }
1660   { set-sym } { old-style, ~two-dots, ~slash } { \exp_not:n {#1} },
1661   read-sym .choices:nn =
1662   { dividido , dividido-por , dividido-entre }
1663   {
1664     \int_case:nn { \l_keys_choice_int }
1665     {
1666       {1} { \tl_set:Nn \l__spintent_spdsym_read_sym_tl { dividido } }
1667       {2} { \tl_set:Nn \l__spintent_spdsym_read_sym_tl { dividido-por } }
1668       {3} { \tl_set:Nn \l__spintent_spdsym_read_sym_tl { dividido-entre } }
1669     }
1670   },
1671   read-sym .initial:n = dividido,
1672   read-sym .value_required:n = true,
1673   read-sym / unknown .code:n =
1674   \msg_error:nneee { spintent } { unknown-choice }
1675   { read-sym } { dividido, ~dividido-por, ~dividido-entre }
1676   { \exp_not:n {#1} },
1677   unknown .code:n =
1678   {
1679     \str_set:Nn \l__spintent_command_name_str { spdsym }
1680     \l__spintent_unknown_keys_cmd:n {#1}
1681   },
1682 }
```

(End of definition for `prefix` and others.)

`\spdsym` Defines the `\spdsym` operator. It takes a single optional argument for local setup and outputs the configured intent structure, safely attaching prefixes and suffixes if present.

```
1683 \NewDocumentCommand \spdsym { 0{} }
1684 {
1685   \mode_if_math:TF
1686   {
1687     \group_begin:
1688     \keys_set:nn { spintent / spdsym } { #1 }
1689     \MathMLintent
1690     {
```

```

1691         \tl_if_empty:NF \l__spinttent_spdsym_prefix_tl
1692         { \l__spinttent_spdsym_prefix_tl - }
1693         \l__spinttent_spdsym_read_sym_tl
1694         \tl_if_empty:NF \l__spinttent_spdsym_suffix_tl
1695         { - \l__spinttent_spdsym_suffix_tl }
1696     }
1697     { \l__spinttent_spdsym_symbol_tl }
1698 \group_end:
1699 }
1700 { \msg_error:nnn { spintent } { need-math-mode } { \spdsym } }
1701 }

```

(End of definition for `\spdsym`. This function is documented on page 12.)

11.23.3 The command `\spmsym`

Variables to store the regional reading string, the visual operator, and the optional semantic affixes specifically for `\spmsym`.

```

\l__spinttent_spmsym_read_sym_tl
\l__spinttent_spmsym_symbol_tl
\l__spinttent_spmsym_prefix_tl
\l__spinttent_spmsym_suffix_tl
1702 \tl_new:N \l__spinttent_spmsym_read_sym_tl
1703 \tl_new:N \l__spinttent_spmsym_symbol_tl
1704 \tl_new:N \l__spinttent_spmsym_prefix_tl
1705 \tl_new:N \l__spinttent_spmsym_suffix_tl

```

(End of definition for `\l__spinttent_spmsym_read_sym_tl` and others.)

```

prefix    We define the (keys) prefix, suffix, set-sym, read-sym and not-print for \spmsym.
suffix
set-sym   1706 \keys_define:nn { spintent / spmsym }
          {
read-sym   1707   prefix                .code:n =
          { \l__spinttent_sanitizize_affix:Nn \l__spinttent_spmsym_prefix_tl {#1} },
not-print  1708   prefix                .initial:n = ,
          1709   prefix                .value_required:n = true,
unknown    1710   suffix                .code:n =
          1711   { \l__spinttent_sanitizize_affix:Nn \l__spinttent_spmsym_suffix_tl {#1} },
          1712   suffix                .initial:n = ,
          1713   suffix                .value_required:n = true,
          1714   set-sym                .choices:nn =
          1715   { cross , dot , asterisk }
          1716   {
          1717       \int_case:nn { \l_keys_choice_int }
          1718       {
          1719           {1} { \tl_set:Nn \l__spinttent_spmsym_symbol_tl { \times } }
          1720           {2} { \tl_set:Nn \l__spinttent_spmsym_symbol_tl { \cdot } }
          1721           {3} { \tl_set:Nn \l__spinttent_spmsym_symbol_tl { \ast } }
          1722       }
          1723   },
          1724   set-sym                .initial:n = dot,
          1725   set-sym                .value_required:n = true,
          1726   set-sym / unknown .code:n =
          1727   { \msg_error:nneee { spintent } { unknown-choice }
          1728   { set-sym } { cross, ~dot, ~asterisk } { \exp_not:n {#1} } },
          1729   read-sym                .choices:nn =
          1730   { por , multiplicado-por , veces }
          1731   {
          1732       \int_case:nn { \l_keys_choice_int }
          1733       {
          1734           {1} { \tl_set:Nn \l__spinttent_spmsym_read_sym_tl { por } }
          1735           {2} { \tl_set:Nn \l__spinttent_spmsym_read_sym_tl { multiplicado-por } }
          1736           {3} { \tl_set:Nn \l__spinttent_spmsym_read_sym_tl { veces } }
          1737       }
          1738   },
          1739   read-sym                .initial:n = por,
          1740   read-sym                .value_required:n = true,
          1741   read-sym / unknown .code:n =
          1742   { \msg_error:nneee { spintent } { unknown-choice }
          1743   { read-sym } { por, ~multiplicado-por, ~veces } { \exp_not:n {#1} } },
          1744   not-print                .bool_set:N = \l__spinttent_spmsym_not_print_bool,
          1745   not-print                .initial:n = false,
          1746   not-print                .value_required:n = true,
          1747   unknown                .code:n =
          1748   {
          1749       \str_set:Nn \l__spinttent_command_name_str { spmsym }
          1750       \__spinttent_unknown_keys_cmd:n {#1}
          1751
          1752

```

```

1753     },
1754 }

```

(End of definition for *prefix* and others.)

\spmsym Defines the **\spmsym** operator. Similar to **\spdsym**, it outputs the correct mathematical glyph based on the local *⟨keys⟩*, safely attaching prefixes and suffixes if present.

```

1755 \NewDocumentCommand \spmsym { 0{} }
1756 {
1757   \mode_if_math:TF
1758   {
1759     \group_begin:
1760     \keys_set:nn { spintent / spmsym } { #1 }
1761     \MathMLintent
1762     {
1763       \tl_if_empty:NF \l__spintent_spmsym_prefix_tl
1764       { \l__spintent_spmsym_prefix_tl - }
1765       \l__spintent_spmsym_read_sym_tl
1766       \tl_if_empty:NF \l__spintent_spmsym_suffix_tl
1767       { - \l__spintent_spmsym_suffix_tl }
1768     }
1769     {
1770       \bool_if:NTF \l__spintent_spmsym_not_print_bool
1771       {
1772         \invisibletimes
1773       }
1774       { \l__spintent_spmsym_symbol_tl }
1775     }
1776     \group_end:
1777   }
1778   { \msg_error:nnn { spintent } { need-math-mode } { \spmsym } }
1779 }

```

(End of definition for *\spmsym*. This function is documented on page 12.)

11.24 The command **\spdiv**

The user-level command **\spdiv** formats division representations. It takes two mandatory arguments: the *⟨dividend⟩* and the *⟨divisor⟩*. Both *⟨arguments⟩* are internally processed by the **\spnum** command to ensure proper digit separation. This command enforces strict validation, ensuring that neither the *⟨dividend⟩* nor the *⟨divisor⟩* is *blank*.

11.24.1 Definition of keys for **\spdiv**

We define the *⟨keys⟩* **wrap-parens** and **read-parens** for **\spdiv** command. Number-related *⟨keys⟩* **cifras-sep**, **read-sign**, **read-period-sep** and **notation-sym** are forwarded to **\spnum** command using **.meta:nn**, while semantic operator *⟨keys⟩* **set-sym** and **read-sym** are forwarded to the **\spdsym** command using **.meta:nn**.

```

1780 \keys_define:nn { spintent / spdiv }
1781 {
1782   cifras-sep      .meta:nn = { spintent / spnum } { cifras-sep      = {#1} },
1783   read-sign       .meta:nn = { spintent / spnum } { read-sign       = {#1} },
1784   read-period-sep .meta:nn = { spintent / spnum } { read-period-sep = {#1} },
1785   notation-sym    .meta:nn = { spintent / spnum } { notation-sym    = {#1} },
1786   set-sym         .meta:nn = { spintent / spdsym } { set-sym         = {#1} },
1787   read-sym        .meta:nn = { spintent / spdsym } { read-sym        = {#1} },
1788   wrap-parens     .bool_set:N = \l__spintent_spdiv_wrap_parens_bool,
1789   wrap-parens     .initial:n = false,
1790   wrap-parens     .value_required:n = true,
1791   read-parens     .bool_set:N = \l__spintent_spdiv_read_parens_bool,
1792   read-parens     .initial:n = true,
1793   read-parens     .value_required:n = true,
1794   unknown         .code:n =
1795   {
1796     \str_set:Nn \l__spintent_command_name_str { spdiv }
1797     \l__spintent_unknown_keys_cmd:n {#1}
1798   },
1799 }

```

(End of definition for *cifras-sep* and others.)

11.24.2 Definition of error messages

spdiv-empty-argument

Raised when either the $\langle\textit{dividend}\rangle$ or the $\langle\textit{divisor}\rangle$ is missing or *blank*.

```

1800 \msg_new:nnnn { spintent } { spdiv-empty-argument }
1801 { The~arguments~for~\token_to_str:N \spdiv~cannot~be~empty. }
1802 {
1803   You~must~provide~both~a~dividend~and~a~divisor.\\
1804 }

```

(End of definition for spdiv-empty-argument.)

11.24.3 Internal functions for \spdiv

__spintent_spdiv_render_op:nn

The function `\__spintent_spdiv_render_op:nn` parses both $\langle\textit{arguments}\rangle$ through the `\spnum` command and embeds the semantic operator from `\spdsym`.

```

1805 \cs_new_protected:Nn \__spintent_spdiv_render_op:nn
1806 {
1807   \spnum {#1}
1808   \MathMLintent { \__spintent_spdsym_read_sym_tl }
1809   {
1810     \__spintent_spdsym_symbol_tl
1811   }
1812   \spnum {#2}
1813 }

```

(End of definition for __spintent_spdiv_render_op:nn.)

__spintent_spdiv_render_parens:nn

The function `\__spintent_spdiv_render_parens:nn` handles the structural parentheses around the division.

```

1814 \cs_new_protected:Nn \__spintent_spdiv_render_parens:nn
1815 {
1816   \bool_if:NTF \__spintent_spdiv_read_parens_bool
1817   {
1818     ( \__spintent_spdiv_render_op:nn {#1} {#2} )
1819   }
1820   {
1821     \MathMLintent { :silent } { ( }
1822     \__spintent_spdiv_render_op:nn {#1} {#2}
1823     \MathMLintent { :silent } { ) }
1824   }
1825 }

```

(End of definition for __spintent_spdiv_render_parens:nn.)

__spintent_spdiv_process:nnn

The function `\__spintent_spdiv_process:nnn` sets $\langle\textit{keys}\rangle$, validates $\langle\textit{arguments}\rangle$, and decides on parenthesis wrapping.

```

1826 \cs_new_protected:Nn \__spintent_spdiv_process:nnn
1827 {
1828   \keys_set:nn { spintent / spdiv } { #1 }
1829   \tl_if_blank:nTF { #2 }
1830   { \msg_error:nnn { spintent } { spdiv-empty-argument } }
1831   {
1832     \tl_if_blank:nTF { #3 }
1833     { \msg_error:nnn { spintent } { spdiv-empty-argument } }
1834     {
1835       \bool_if:NTF \__spintent_spdiv_wrap_parens_bool
1836       { \__spintent_spdiv_render_parens:nn {#2} {#3} }
1837       { \__spintent_spdiv_render_op:nn {#2} {#3} }
1838     }
1839   }
1840 }

```

(End of definition for __spintent_spdiv_process:nnn.)

\spdiv

Defines the user command `\spdiv`. It strictly relies on *math mode*.

```

1841 \NewDocumentCommand \spdiv { O{} m m }
1842 {
1843   \mode_if_math:TF
1844   {
1845     \group_begin:
1846     \__spintent_spdiv_process:nnn { #1 } { #2 } { #3 }
1847     \group_end:
1848   }
1849   { \msg_error:nnn { spintent } { need-math-mode } { \spdiv } }
1850 }

```

(End of definition for `\spd\div`. This function is documented on page 13.)

11.25 The command `\spmul`

The user-level command `\spmul` formats multiplication representations. It takes two mandatory arguments: the `{\langle first factor \rangle}` and the `{\langle second factor \rangle}`. Both `{\langle arguments \rangle}` are internally processed by the `\spnum` command to ensure proper digit separation. This command enforces strict validation, ensuring that neither the `{\langle first factor \rangle}` nor the `{\langle second factor \rangle}` is *blank*.

11.25.1 Definition of keys for `\spmul`

We define the `\keys` wrap-parens and read-parens for `\spmul` command. Number-related `\keys` `cifras-sep`, `read-sign`, `read-period-sep` and `notation-sym` are forwarded to `\spnum` command using `.meta:nn`, while semantic operator `\keys` `set-sym` and `read-sym` are forwarded to the `\spmsym` command using `.meta:nn`.

```

1851 \keys_define:nn { spintent / spmul }
1852 {
1853   cifras-sep      .meta:nn = { spintent / spnum } { cifras-sep      = {#1} },
1854   read-sign       .meta:nn = { spintent / spnum } { read-sign       = {#1} },
1855   read-period-sep .meta:nn = { spintent / spnum } { read-period-sep = {#1} },
1856   notation-sym    .meta:nn = { spintent / spnum } { notation-sym    = {#1} },
1857   set-sym         .meta:nn = { spintent / spmsym } { set-sym         = {#1} },
1858   read-sym        .meta:nn = { spintent / spmsym } { read-sym        = {#1} },
1859   wrap-parens     .bool_set:N = \l__spintent_spmul_wrap_parens_bool,
1860   wrap-parens     .initial:n  = false,
1861   wrap-parens     .value_required:n = true,
1862   read-parens     .bool_set:N = \l__spintent_spmul_read_parens_bool,
1863   read-parens     .initial:n  = true,
1864   read-parens     .value_required:n = true,
1865   unknown         .code:n =
1866     {
1867       \str_set:Nn \l__spintent_command_name_str { spmul }
1868       \__spintent_unknown_keys_cmd:n {#1}
1869     },
1870 }

```

(End of definition for `cifras-sep` and others.)

11.25.2 Definition of error messages

`spmul-empty-argument` Raised when either the `{\langle first factor \rangle}` or the `{\langle second factor \rangle}` is missing or *blank*.

```

1871 \msg_new:nnnn { spintent } { spmul-empty-argument }
1872 { The~arguments~for~\token_to_str:N \spmul~cannot~be~empty. }
1873 {
1874   You~must~provide~both~first~factor~and~second~factor.\\
1875 }

```

(End of definition for `spmul-empty-argument`.)

11.25.3 Internal functions for `\spmul`

`\__spintent_spmul_render_op:nn` The function `\__spintent_spmul_render_op:nn` parses both `{\langle arguments \rangle}` through the `\spnum` command and embeds the semantic operator from `\spmsym`.

```

1876 \cs_new_protected:Nn \__spintent_spmul_render_op:nn
1877 {
1878   \spnum {#1}
1879   \MathMLintent { \l__spintent_spmsym_read_sym_tl }
1880   {
1881     \l__spintent_spmsym_symbol_tl
1882   }
1883   \spnum {#2}
1884 }

```

(End of definition for `\__spintent_spmul_render_op:nn`.)

`\__spintent_spmul_render_parens:nn` The function `\__spintent_spmul_render_parens:nn` handles the structural parentheses around the multiplication.

```

1885 \cs_new_protected:Nn \__spintent_spmul_render_parens:nn
1886 {
1887   \bool_if:NTF \l__spintent_spmul_read_parens_bool
1888   {
1889     ( \__spintent_spmul_render_op:nn {#1} {#2} )
1890   }
1891   {
1892     \MathMLintent { :silent } { ( ) }

```

```

1893     \__spintent_spmul_render_op:nn {#1} {#2}
1894     \MathMLintent { :silent } { ) }
1895   }
1896 }

```

(End of definition for __spintent_spmul_render_parens:nn.)

__spintent_spmul_process:nnn

The function `\__spintent_spmul_process:nnn` sets $\langle keys \rangle$, validates $\langle arguments \rangle$, and decides on parenthesis wrapping.

```

1897 \cs_new_protected:Nn \__spintent_spmul_process:nnn
1898 {
1899   \keys_set:nn { spintent / spmul } { #1 }
1900   \tl_if_blank:nTF { #2 }
1901   { \msg_error:nnn { spintent } { spmul-empty-argument } }
1902   {
1903     \tl_if_blank:nTF { #3 }
1904     { \msg_error:nnn { spintent } { spmul-empty-argument } }
1905     {
1906       \bool_if:NTF \__spintent_spmul_wrap_parens_bool
1907       { \__spintent_spmul_render_parens:nn {#2} {#3} }
1908       { \__spintent_spmul_render_op:nn {#2} {#3} }
1909     }
1910   }
1911 }

```

(End of definition for __spintent_spmul_process:nnn.)

\spmul

Defines the user command `\spmul`. It strictly relies on *math mode*.

```

1912 \NewDocumentCommand \spmul { O{} m m }
1913 {
1914   \mode_if_math:TF
1915   {
1916     \group_begin:
1917     \__spintent_spmul_process:nnn { #1 } { #2 } { #3 }
1918     \group_end:
1919   }
1920   { \msg_error:nnn { spintent } { need-math-mode } { \spmul } }
1921 }

```

(End of definition for `\spmul`. This function is documented on page 13.)

11.26 The commands `\spgcd` and `\spmcn`

The user-level commands `\spgcd` and `\spmcn` provide a semantic interface for the Greatest Common Divisor (MCD in Spanish) and the Least Common Multiple (MCM in Spanish). They delegate argument validation and calculation to the Lua module `spintent.lua`, constructing a valid `MathCAT` intent.

11.26.1 Variables for `\spgcd` and `\spmcn`

Internal variables generated dynamically via a comma-separated list to avoid code duplication for both symmetric commands.

```

\__spintent_spmcm_spmcd_luaset_error_str
\__spintent_mc_args_seq
\__spintent_spmcd_print_result_bool
\__spintent_spmcm_print_result_bool
\__spintent_spmcd_read_terse_bool
\__spintent_spmcm_read_terse_bool
\__spintent_spmcd_print_upper_bool
\__spintent_spmcm_print_upper_bool
\__spintent_spmcd_prefix_tl
\__spintent_spmcm_prefix_tl
\__spintent_spmcd_suffix_tl
\__spintent_spmcm_suffix_tl

```

```

1922 \str_new:N \__spintent_spmcm_spmcd_luaset_error_str
1923 \seq_new:N \__spintent_mc_args_seq
1924 \clist_map_inline:nn { mcd , mcm }
1925 {
1926   \tl_new:c { \__spintent_sp #1 _luaset_ #1 _value_tl }
1927   \bool_new:c { \__spintent_sp #1 _print_result_bool }
1928   \bool_new:c { \__spintent_sp #1 _read_terse_bool }
1929   \bool_new:c { \__spintent_sp #1 _print_upper_bool }
1930   \tl_new:c { \__spintent_sp #1 _prefix_tl }
1931   \tl_new:c { \__spintent_sp #1 _suffix_tl }
1932 }

```

(End of definition for `\__spintent_spmcm_spmcd_luaset_error_str` and others.)

11.26.2 Definition of error messages

mc-invalid-arguments

Exception triggered when the comma-separated sequence contains negative integers, floats, or alphabetical characters.

```

1933 \msg_new:nnnn { spintent } { mc-invalid-arguments }
1934 {
1935   Invalid~arguments~provided~to~#1.
1936 }
1937 {
1938   The~arguments~must~be~a~comma-separated~list. \\\
1939 }

```

(End of definition for `mc-invalid-arguments`.)

11.26.3 Keys for `\spmc`d and `\spmc`m

We define the shared *(keys)* `result`, `prefix`, `read-cmd`, `upper-case`, `sample-arg` and `silent-cmd`.

```

1940 \clist_map_inline:nn { mcd , mcm }
1941 {
1942   \keys_define:nn { spintent / sp #1 }
1943   {
1944     result      .bool_set:c = { l__spintent_sp #1 _print_result_bool },
1945     result      .initial:n = false,
1946     result      .value_required:n = true,
1947     prefix      .code:n =
1948       { \__spintent_sanitise_affix:cn { l__spintent_sp #1 _prefix_tl } {##1} },
1949     prefix      .initial:n = ,
1950     prefix      .value_required:n = true,
1951     read-cmd    .choices:nn =
1952       { terse , clear }
1953       {
1954         \int_case:nn { \_keys_choice_int }
1955         {
1956           {1} { \bool_set_true:c { l__spintent_sp #1 _read_terse_bool } }
1957           {2} { \bool_set_false:c { l__spintent_sp #1 _read_terse_bool } }
1958         }
1959       },
1960     read-cmd    .initial:n = clear,
1961     read-cmd    .value_required:n = true,
1962     read-cmd / unknown .code:n =
1963       \msg_error:nneee { spintent } { unknown-choice }
1964       { read-cmd } { terse , ~clear } { \exp_not:n {##1} },
1965     upper-case  .bool_set:c = { l__spintent_sp #1 _print_upper_bool },
1966     upper-case  .initial:n = false,
1967     upper-case  .value_required:n = true,
1968     sample-arg  .bool_set:c = { l__spintent_sp #1 _sample_arg_bool },
1969     sample-arg  .initial:n = false,
1970     sample-arg  .value_required:n = true,
1971     silent-cmd  .bool_set:c = { l__spintent_sp #1 _silent_cmd_bool },
1972     silent-cmd  .initial:n = false,
1973     silent-cmd  .value_required:n = true,
1974     unknown     .code:n =
1975       {
1976         \str_set:Nn \__spintent_command_name_str { sp #1 }
1977         \__spintent_unknown_keys_cmd:n {##1}
1978       },
1979   }
1980 }

```

(End of definition for `result` and others.)

11.26.4 Internal functions for `\spmc`d and `\spmc`m

`\__spintent_mc_process_args:nn` The function `\__spintent_mc_process_args:nn` parses the operation ‘#1’ and its arguments ‘#2’, injecting MathML intents.

```

1981 \cs_new_protected:Nn \__spintent_mc_process_args:nn
1982 {
1983   \seq_set_from_clist:Nn \l__spintent_mc_args_seq {#2}
1984   \bool_if:cTF { l__spintent_sp #1 _silent_cmd_bool }
1985   {
1986     \seq_set_map:Nnn \l__spintent_mc_args_seq \l__spintent_mc_args_seq
1987     { \MathMLintent { :silent } { ##1 } }
1988     \MathMLintent { entre:silent } { ( }
1989     \seq_use:Nnnn \l__spintent_mc_args_seq
1990     { \MathMLintent { _y:silent } { , } }
1991     { \MathMLintent { :silent } { , } }
1992     { \MathMLintent { _y:silent } { , } }
1993   }
1994   {
1995     \MathMLintent { entre } { ( }
1996     \seq_use:Nnnn \l__spintent_mc_args_seq
1997     { \MathMLintent { _y } { , } }
1998     { \MathMLintent { :silent } { , } }
1999     { \MathMLintent { _y } { , } }
2000   }

```

```

2001   \MathMLintent { :silent } { } }
2002 }

```

(End of definition for `\__spintent_mc_process_args:nn`.)

`\__spintent_spmc_process:nnnn`

The internal function `\__spintent_spmc_process:nnnn` serves as a shared central handler for both the `\spmc`d and `\spmc`m commands. It takes the command identifier ‘#1’, its full reading string ‘#2’, the local *(keys)* ‘#3’, and the optional values ‘#4’. It dynamically resolves variables using the identifier to build the `MathMLintent` string (including any prefixes or suffixes) and prints the math operator. If values are provided in ‘#4’, it calculates the result using the Lua backend. If an error occurs, it throws the `mc-invalid-arguments` error; otherwise, it processes the arguments and conditionally prints the calculated result.

```

2003 \cs_new_protected:Nn \__spintent_spmc_process:nnnn
2004 {
2005   \keys_set:nn { spintent / sp #1 } { #3 }
2006   \MathMLintent
2007   {
2008     \tl_if_empty:cF { l__spintent_sp #1 _prefix_tl }
2009     { \tl_use:c { l__spintent_sp #1 _prefix_tl } - }
2010     \bool_if:cTF { l__spintent_sp #1 _read_terse_bool }
2011     { #1 } { #2 }
2012     \bool_if:cT { l__spintent_sp #1 _silent_cmd_bool }
2013     {
2014       \tl_if_novalue:nTF {#4}
2015       { :silent }
2016       { \bool_if:cT { l__spintent_sp #1 _sample_arg_bool } { :silent } }
2017     }
2018   }
2019   {
2020     \operatorname
2021     {
2022       \bool_if:cTF { l__spintent_sp #1 _print_upper_bool }
2023       { \text_uppercase:n {#1} } { #1 }
2024     }
2025   }
2026   \tl_if_novalue:nF { #4 }
2027   {
2028     \bool_if:cTF { l__spintent_sp #1 _sample_arg_bool }
2029     {
2030       \__spintent_mc_process_args:nn {#1} {#4}
2031     }
2032     {
2033       \use:c { __spintent_luafun_calculate_ #1 :n } { #4 }
2034       \str_if_eq:VnTF \l__spintent_spmcm_spmcd_luaset_error_str { true }
2035       {
2036         \msg_error:nne { spintent } { mc-invalid-arguments } { \exp_not:c { sp #1 } }
2037       }
2038       {
2039         \__spintent_mc_process_args:nn {#1} {#4}
2040         \bool_if:cT { l__spintent_sp #1 _print_result_bool }
2041         {
2042           \MathMLintent { es-igual-a } { = }
2043           \tl_use:c { l__spintent_sp #1 _luaset_ #1 _value_tl }
2044         }
2045       }
2046     }
2047   }
2048 }

```

(End of definition for `\__spintent_spmc_process:nnnn`.)

`\spmc`d The commands `\spmc`d and `\spmc`m act as the public interface wrappers for typesetting the greatest common divisor and least common multiple. They enforce math mode, open a local group, and defer execution to the main processing macro `\__spintent_spmc_process:nnnn`, passing along the appropriate reading strings and arguments.

```

2049 \NewDocumentCommand \spmc { 0{ } d() }
2050 {
2051   \mode_if_math:TF
2052   {
2053     \group_begin:
2054     \__spintent_spmc_process:nnnn { mcd } { máximo-común-divisor } {#1} {#2}
2055     \group_end:

```

```

2056     }
2057     { \msg_error:nnn { spintent } { need-math-mode } { \spmc } }
2058 }
2059 \NewDocumentCommand \spmc { 0{} d() }
2060 {
2061     \mode_if_math:TF
2062     {
2063         \group_begin:
2064             \__spintent_spmc_process:nnnn { mcm } { mínimo-común-múltiplo } {#1} {#2}
2065         \group_end:
2066     }
2067     { \msg_error:nnn { spintent } { need-math-mode } { \spmc } }
2068 }

```

(End of definition for `\spmc` and `\spmc`. These functions are documented on page 15.)

11.27 The commands `\spnM` and `\spnD`

The user-level commands `\spnM` and `\spnD` provide a semantic interface for the Multiples of a number (“*múltiplos*” in Spanish) and the Divisors of a number (“*divisores*” in Spanish). They delegate argument validation and calculation to the Lua module `spintent.lua`, constructing a valid MathCAT intent.

11.27.1 Variables for `\spnM` and `\spnD`

Internal variables generated dynamically for multiples and divisors.

```

\__spintent_md_out_seq
\__spintent_spnM_luaset_result_tl
\__spintent_spnD_luaset_result_tl
\__spintent_spnM_luaset_is_truncated_str
\__spintent_spnD_luaset_is_truncated_str
\__spintent_spnM_print_result_bool
\__spintent_spnD_print_result_bool
\__spintent_spnM_silent_cmd_bool
\__spintent_spnD_silent_cmd_bool
\__spintent_spnM_prefix_tl
\__spintent_spnD_prefix_tl
\__spintent_spnM_print_result_num_tl
\__spintent_spnD_print_result_num_tl
2069 \seq_new:N \__spintent_md_out_seq
2070 \clist_map_inline:nn { nM , nD }
2071 {
2072     \tl_new:c { \__spintent_sp #1 _luaset_result_tl }
2073     \str_new:c { \__spintent_sp #1 _luaset_is_truncated_str }
2074     \bool_new:c { \__spintent_sp #1 _print_result_bool }
2075     \bool_new:c { \__spintent_sp #1 _silent_cmd_bool }
2076     \tl_new:c { \__spintent_sp #1 _prefix_tl }
2077     \tl_new:c { \__spintent_sp #1 _print_result_num_tl }
2078 }

```

(End of definition for `\__spintent_md_out_seq` and others.)

11.27.2 Keys for `\spnM` and `\spnD`

We define the shared *(keys)* `result`, `silent-cmd`, `result-num` and `prefix`.

```

result
silent-cmd
result-num
prefix
sample-arg
2079 \clist_map_inline:nn { nM , nD }
2080 {
2081     \keys_define:nn { spintent / sp #1 }
2082     {
2083         result .bool_set:c = { \__spintent_sp #1 _print_result_bool },
2084         result .initial:n = false,
2085         result .value_required:n = true,
2086         silent-cmd .bool_set:c = { \__spintent_sp #1 _silent_cmd_bool },
2087         silent-cmd .initial:n = false,
2088         silent-cmd .value_required:n = true,
2089         result-num .tl_set:c = { \__spintent_sp #1 _print_result_num_tl },
2090         result-num .initial:n = ,
2091         prefix .code:n =
2092             { \__spintent_sanitize_affix:cn { \__spintent_sp #1 _prefix_tl } {##1} },
2093         prefix .initial:n = ,
2094         prefix .value_required:n = true,
2095         sample-arg .bool_set:c = { \__spintent_sp #1 _sample_arg_bool },
2096         sample-arg .initial:n = false,
2097         sample-arg .value_required:n = true,
2098         unknown .code:n =
2099             {
2100                 \str_set:Nn \__spintent_command_name_str { sp #1 }
2101                 \__spintent_unknown_keys_cmd:n {##1}
2102             },
2103     }
2104 }

```

(End of definition for `result` and others.)

11.27.3 Definition of error messages for \spnM and \spnD

md-invalid-argument Exception triggered when the argument for multiples or divisors is invalid.

```
2105 \msg_new:nnnn { spintent } { md-invalid-argument }
2106 { Invalid~argument~provided~to~#1. }
2107 {
2108   The~argument~must~be~a~single~positive~integer. \
2109 }
```

(End of definition for md-invalid-argument.)

11.27.4 Internal functions for \spnM and \spnD

__spintent_spnM_spnD_process:nnnn

The internal function `\__spintent_spnM_spnD_process:nnnn` acts as the primary entry point for the multiples and divisors commands. It takes the command identifier ‘#1’, its printed mathematical symbol ‘#2’, its base reading string ‘#3’, the local key-value options ‘#4’, and the optional argument ‘#5’. Its sole purpose is to evaluate and set the provided keys within the current scope before delegating the core branching and typesetting logic to `\__spintent_spnM_and_D_exec:nnnn`.

```
2110 \cs_new_protected:Nn \__spintent_spnM_spnD_process:nnnn
2111 {
2112   \keys_set:nn { spintent / sp #1 } { #4 }
2113   \__spintent_spnM_spnD_exec:nnnn { #1 } { #2 } { #3 } { #5 }
2114 }
```

(End of definition for __spintent_spnM_spnD_process:nnnn.)

__spintent_spnM_spnD_intent:nn

The internal function `\__spintent_spnM_spnD_intent:nn` resolves the main reading intent string. It takes the command identifier ‘#1’ (such as “nM” or “nD”) and the base reading string ‘#2’. It automatically prepends the localized prefix if defined and handles specific string normalizations, such as ensuring the correct accentuation for “múltiplos”.

```
2115 \cs_new:Nn \__spintent_spnM_spnD_intent:nn
2116 {
2117   \tl_if_empty:cF { l__spintent_sp #1 _prefix_tl }
2118   { \tl_use:c { l__spintent_sp #1 _prefix_tl } - }
2119   \str_case:nnF { #2 }
2120   { { múltiplos } { múltiplos } }
2121   { #2 }
2122 }
```

(End of definition for __spintent_spnM_spnD_intent:nn.)

__spintent_spnM_spnD_silent:nn

The internal function `\__spintent_spnM_and_D_silent:nn` prints the atomized notation structure in full silent mode. It takes the mathematical symbol ‘#1’ (such as “D” or “M”) and the variable or explicit argument ‘#2’. Every component is wrapped in a silent intent, and an invisible separator is injected between the parentheses to prevent assistive technologies from applying default contextual reading rules like “de”.

```
2123 \cs_new_protected:Nn \__spintent_spnM_spnD_silent:nn
2124 {
2125   \MathMLintent { :silent } { \operatorname { #1 } }
2126   \MathMLintent { :silent } { ( }
2127   \MathMLintent { :silent } { \__spintent_invisible_sep: }
2128   \MathMLintent { :silent } { #2 }
2129   \MathMLintent { :silent } { ) }
2130 }
```

(End of definition for __spintent_spnM_spnD_silent:nn.)

__spintent_spnM_spnD_result:n

The internal function `\__spintent_spnM_and_D_result:n` handles the calculation and accessible formatting of the computed mathematical set. It takes the command identifier ‘#1’. It invokes the corresponding Lua backend calculation, maps the resulting clist into a sequence, and formats the final printed output utilizing custom accessibility intents for both separators and conjunctions. It also safely manages truncation indicators.

```
2131 \cs_new_protected:Nn \__spintent_spnM_spnD_result:n
2132 {
2133   \use:c { __spintent_luafun_calcular_ #1 :nn }
2134   { \l__spintent_luaset_part_int_tl }
2135   { \tl_use:c { l__spintent_sp #1 _print_result_num_tl } }
2136   \MathMLintent { son } { = \{ }
2137   \seq_set_from_clist:Ne
2138   \l__spintent_md_out_seq { \tl_use:c { l__spintent_sp #1 _luaset_result_tl } }
2139   \seq_use:Nnnn \l__spintent_md_out_seq
2140   { \MathMLintent { _y } { , } }
2141   { \MathMLintent { :silent } { , } }
2142   { \MathMLintent { _y } { , } }
```

```

2143 \str_if_eq:vnT
2144 { \__spintent_sp #1 \luaset_is_truncated_str } { true }
2145 {
2146   \MathMLintent { :silent } { , } ~ \dots
2147 }
2148 \MathMLintent { :silent } { \} }
2149 }

```

(End of definition for `\__spintent_spnM_spnD_result:n`.)

`\__spintent_spnM_spnD_exec:nnnn`

The function `\__spintent_spnM_and_D_exec:nnnn` implements the multiples and divisors commands. It takes the `{\langle argument \rangle}` ‘#1’ (the command name), the `{\langle argument \rangle}` ‘#2’ (the mathematical symbol), the base reading `{\langle argument \rangle}` ‘#3’, and the optional `{\langle argument \rangle}` ‘#4’. If no `{\langle argument \rangle}` is provided, it evaluates the key `silent-cmd` using the default token ‘n’. If an `{\langle argument \rangle}` is given, it evaluates the key `sample-arg`. If true, it processes the `{\langle argument \rangle}` directly and evaluates the key `silent-cmd`. If false, it bypasses the *silent mode*, validates the `{\langle argument \rangle}` as a natural number, and evaluates the key `result` optionally calculate and append the resulting set.

```

2150 \cs_new_protected:Nn \__spintent_spnM_spnD_exec:nnnn
2151 {
2152   \tl_if_novalue:nTF { #4 }
2153   {
2154     \bool_if:cTF { \__spintent_sp #1 _silent_cmd_bool }
2155     { \__spintent_spnM_spnD_silent:nn { #2 } { n } }
2156     {
2157       \MathMLintent
2158       { \__spintent_spnM_spnD_intent:nn { #1 } { #3 } }
2159       { \operatorname { #2 } ( n ) }
2160     }
2161   }
2162   {
2163     \bool_if:cTF { \__spintent_sp #1 _sample_arg_bool }
2164     {
2165       \bool_if:cTF { \__spintent_sp #1 _silent_cmd_bool }
2166       { \__spintent_spnM_spnD_silent:nn { #2 } { #4 } }
2167       {
2168         \MathMLintent
2169         { \__spintent_spnM_spnD_intent:nn { #1 } { #3 } }
2170         { \operatorname { #2 } } ( #4 )
2171       }
2172     }
2173     {
2174       \__spintent_luafun_clean_split_and_set:n { \exp_not:n { #4 } }
2175       \str_if_eq:VnTF \__spintent_luaset_has_natural_str { true }
2176       {
2177         \MathMLintent
2178         { \__spintent_spnM_spnD_intent:nn { #1 } { #3 } }
2179         { \operatorname { #2 } } ( #4 )
2180         \bool_if:cT { \__spintent_sp #1 _print_result_bool }
2181         { \__spintent_spnM_spnD_result:n { #1 } }
2182       }
2183       {
2184         \msg_error:nne { spintent } { md-invalid-argument } { \exp_not:c { sp #1 } }
2185       }
2186     }
2187   }
2188 }

```

(End of definition for `\__spintent_spnM_spnD_exec:nnnn`.)

`\spnM` The commands `\spnM` and `\spnD` act as the public interface wrappers for typesetting multiples and divisors, respectively. They enforce math mode, open a local group, and defer execution to the function `\__spintent_spnM_spnD_process:nnnnn`, passing along the optional `\keys` ‘#1’ and the numeric `{\langle argument \rangle}` ‘#2’.

```

2189 \NewDocumentCommand \spnM { O{} d() }
2190 {
2191   \mode_if_math:TF
2192   {
2193     \group_begin:
2194     \__spintent_spnM_spnD_process:nnnnn { nM } { M } { multiplos } { #1 } { #2 }
2195     \group_end:
2196   }

```

```

2197     { \msg_error:nnn { spintent } { need-math-mode } { \spnM } }
2198   }
2199   \NewDocumentCommand \spnD { 0{} d() }
2200   {
2201     \mode_if_math:TF
2202     {
2203       \group_begin:
2204       \__spintent_spnM_spnD_process:nnnnn { nD } { D } { divisores } {#1} {#2}
2205       \group_end:
2206     }
2207     { \msg_error:nnn { spintent } { need-math-mode } { \spnD } }
2208   }

```

(End of definition for `\spnM` and `\spnD`. These functions are documented on page 14.)

11.28 The command `\spang`

The command `\spang` is the main public command for typesetting and tagging sexagesimal angle expressions (degrees, minutes, and seconds). It parses the input using the Lua function `\__spintent_luafun_spang_parse:n`. This separates the degrees, minutes, and seconds to construct a MathML `intent` tree with the correct postfixes for NVDA/MathCAT.

```

\l__spintent_spang_luaset_grado_str
\l__spintent_spang_luaset_minuto_str
\l__spintent_spang_luaset_segundo_str
\l__spintent_spang_luaset_error_str

```

These internal string variables store the values returned from the Lua module `spintent.lua`. They hold the extracted numerical values for degrees, minutes, and seconds, as well as the error status used during formatting.

```

2209 \str_new:N \l__spintent_spang_luaset_grado_str
2210 \str_new:N \l__spintent_spang_luaset_minuto_str
2211 \str_new:N \l__spintent_spang_luaset_segundo_str
2212 \str_new:N \l__spintent_spang_luaset_error_str

```

(End of definition for `\l__spintent_spang_luaset_grado_str` and others.)

11.28.1 Definition of error messages for `\spang`

invalid-angle-format

The error message `invalid-angle-format` defines the text displayed when an invalid angle input is detected. It is triggered when an argument fails the format checks, does not match the expected sexagesimal pattern, or contains invalid measurement symbols.

```

2213 \msg_new:nnnn { spintent } { invalid-angle-format }
2214 { Invalid~angle~format~in~#1. }
2215 {
2216   The~argument~'#2'~could~not~be~parsed. \
2217 }

```

(End of definition for `invalid-angle-format`.)

11.28.2 Internal functions for `\spang`

__spintent_spang_process:n

The internal function `\__spintent_spang_process:n` parses the angle input using `\__spintent_luafun_spang_parse:n` after resetting the error flag in `\l__spintent_spang_luaset_error_str`. If an invalid format is detected, it issues the `invalid-angle-format` error. Otherwise, it checks the extracted string variables `\l__spintent_spang_luaset_grado_str`, `\l__spintent_spang_luaset_minuto_str`, and `\l__spintent_spang_luaset_segundo_str`. For each non-empty variable, it constructs the corresponding MathML `intent` structure with the correct measurement symbols and postfixes for NVDA/MathCAT.

```

2218 \cs_new_protected:Nn \__spintent_spang_process:n
2219 {
2220   \str_set:Nn \l__spintent_spang_luaset_error_str { false }
2221   \__spintent_luafun_spang_parse:n { #1 }
2222   \str_if_eq:VnTF \l__spintent_spang_luaset_error_str { true }
2223   {
2224     \msg_error:nnnn { spintent } { invalid-angle-format } { \spang } { #1 }
2225   }
2226   {
2227     \str_if_empty:NF \l__spintent_spang_luaset_grado_str
2228     {
2229       \spunit{ \l__spintent_spang_luaset_grado_str °}
2230     }
2231     \str_if_empty:NF \l__spintent_spang_luaset_minuto_str
2232     {
2233       \MathMLintent { minutos : postfix($m) }
2234       {
2235         \MathMLarg { m }
2236         {
2237           \spunit{ \l__spintent_spang_luaset_minuto_str ' }

```

```

2238         }
2239     }
2240 }
2241 \str_if_empty:NF \l__spintent_spang_luaset_segundo_str
2242 {
2243     \MathMLintent { segundos : postfix($s) }
2244     {
2245         \MathMLarg { s }
2246         {
2247             \spunit { \l__spintent_spang_luaset_segundo_str " }
2248         }
2249     }
2250 }
2251 }
2252 }

```

(End of definition for `\__spintent_spang_process:n`.)

\spang The command `\spang` is the public interface for formatting sexagesimal angle expressions. It first checks if it is being used in math mode, issuing an error if not. Inside a local group, it calls `\__spintent_spang_process:n` to process the $\langle argument \rangle$.

```

2253 \NewDocumentCommand \spang { m }
2254 {
2255     \mode_if_math:TF
2256     {
2257         \group_begin:
2258         \__spintent_spang_process:n { #1 }
2259         \group_end:
2260     }
2261     { \msg_error:nnn { spintent } { need-math-mode } { \spang } }
2262 }

```

(End of definition for `\spang`. This function is documented on page 21.)

11.29 The command `\spnZ`

The user-level command `\spnZ` formats integers (the set $\mathbb{Z}$). It includes specific options to automatically enclose numbers (particularly negative ones) in visual parentheses and allows you to control whether these parentheses are read by MathCAT.

This command verifies that the $\langle argument \rangle$ is indeed an *integer*, checking for the complete absence of decimal separators or attached units of measurement.

11.29.1 Definition of keys for `\spnZ`

Now we define the $\langle keys \rangle$ `cifras-sep` and `read-sign`. These are `.meta:nn` $\langle keys \rangle$ passed directly to the `\spnum` command. We also introduce `wrap-parens`, which determines whether the number is enclosed in parentheses, and `read-parens`, which controls if these parentheses are read by MathCAT.

```

2263 \keys_define:nn { spintent / spnZ }
2264 {
2265     cifras-sep .meta:nn = { spintent / spnum } { cifras-sep = {#1} },
2266     read-sign .meta:nn = { spintent / spnum } { read-sign = {#1} },
2267     wrap-parens .bool_set:N = \l__spintent_spnz_wrap_parens_bool,
2268     wrap-parens .initial:n = false,
2269     wrap-parens .value_required:n = true,
2270     read-parens .bool_set:N = \l__spintent_spnz_read_parens_bool,
2271     read-parens .initial:n = true,
2272     read-parens .value_required:n = true,
2273     unknown .code:n =
2274     {
2275         \str_set:Nn \l__spintent_command_name_str { spnZ }
2276         \__spintent_unknown_keys_cmd:n {#1}
2277     },
2278 }

```

(End of definition for `cifras-sep` and others.)

11.29.2 Definition of error messages

spnz-not-integer Raised when the $\langle argument \rangle$ contains decimal separators or attached units, which conflict with the constraints of a pure integer representation.

```

2279 \msg_new:nnnn { spintent } { spnz-not-integer }
2280 { The~value~'~#1'~is~not~a~valid~integer. }
2281 {

```

```

2282 Command~\token_to_str:N \spnZ~only~accepts~integers.\
2283 }

```

(End of definition for `spnz-not-integer`.)

11.29.3 Internal functions for `\spnZ`

`\__spintent_spnz_render_parens:`

The function `\__spintent_spnz_render_parens:` first checks the state of the boolean variable `\l__spintent_spnz` (controlled by the `read-parens` key). If it is `true`, it prints the number surrounded by parentheses. Otherwise, it applies the `:silent function intent` to the parentheses while printing the number.

```

2284 \cs_new_protected:Nn \__spintent_spnz_render_parens:
2285 {
2286   \bool_if:NTF \l__spintent_spnz_read_parens_bool
2287   {
2288     ( \__spintent_spnz_print_num_start: )
2289   }
2290   {
2291     \MathMLintent { :silent } { ( }
2292     \__spintent_spnz_print_num_start:
2293     \MathMLintent { :silent } { ) }
2294   }
2295 }

```

(End of definition for `\__spintent_spnz_render_parens:`.)

`\__spintent_spnz_process:nn`

The function `\__spintent_spnz_process:nn` first processes the `<keys>` passed in ‘#1’ and then calls `\__spintent_luafun_clean_split_and_set:n` on ‘#2’. It verifies that the input is a valid integer by checking if the variable `\l__spintent_luaset_has_integer_str` is `true`. If not `true`, an “error” is raised.

If it is `true`, it checks whether `\l__spintent_luaset_part_int_tl` is *empty* and raises an “error” if so. Otherwise, it checks `\l__spintent_spnz_wrap_parens_bool` set by `wrap-parens` and calls either the function `\__spintent_spnz_render_parens:` or `\__spintent_spnz_print_num_start:`.

```

2296 \cs_new_protected:Nn \__spintent_spnz_process:nn
2297 {
2298   \keys_set:nn { spintent / spnZ } {#1}
2299   \__spintent_luafun_clean_split_and_set:n { \exp_not:n {#2} }
2300   \str_if_eq:VnTF \l__spintent_luaset_has_integer_str { true }
2301   {
2302     \tl_if_empty:NTF \l__spintent_luaset_part_int_tl
2303     { \msg_error:nnn { spintent } { spnum-no-digits } {#2} }
2304     {
2305       \bool_if:NTF \l__spintent_spnz_wrap_parens_bool
2306       { \__spintent_spnz_render_parens: }
2307       { \__spintent_spnz_print_num_start: }
2308     }
2309   }
2310   { \msg_error:nnn { spintent } { spnz-not-integer } {#2} }
2311 }

```

(End of definition for `\__spintent_spnz_process:nn`.)

`\spnZ` Defines the user command `\spnZ`, which is executed within a *group* and strictly enforces *math mode*.

```

2312 \NewDocumentCommand \spnZ { O{} m }
2313 {
2314   \mode_if_math:TF
2315   {
2316     \group_begin:
2317     \__spintent_spnz_process:nn { #1 } { #2 }
2318     \group_end:
2319   }
2320   { \msg_error:nnn { spintent } { need-math-mode } { \spnZ } }
2321 }

```

(End of definition for `\spnZ`. This function is documented on page 16.)

11.30 The command `\spmQ`

The command `\spmQ` typesets “mixed numbers” within Spanish mathematical contexts (e.g., $3\frac{1}{2}$). It delegates the scaling of the integer part to the Lua module `spintent.lua` via `\__spintent_luafun_spmQ_scale_int:Vn`, which measures both the integer glyph and the fraction box at the node level and computes a scaling factor to align their heights visually. Finally, it constructs the correct MathML intent for MathCAT.

11.30.1 Definition of variables for \spmQ

The variable `\__spintent_spmQ_join_word_str` stores the value set by the key `join-word` which will be verbalized by MathCAT as a grammatical connector between the integer and fractional parts.

The variable `\__spintent_spmQ_intent_read_sign_str` stores the `:intent` passed to `\MathMLintent` when the signs ‘+’ or ‘−’ are present in the integer part, used by the function `\__spintent_spmQ_print_scale_int:n`.

The variables `\__spintent_spmQ_wrap_parens_l_tl` and `\__spintent_spmQ_wrap_parens_r_tl` store the sized parentheses set by the function `\__spintent_spmQ_set_wrap_parens_size:` and used by the key `wrap-parens`.

The integer variable `\__spintent_saved_luamml_flag_int` temporarily stores the current value of `\__luamml_flag_int` before disabling it during the injection of the scaled integer node, and restores it afterwards. This prevents `luamml` from generating a spurious `<math>` element around the `sub_box` processed in isolation, before `\frac` has expanded.

```

2322 \str_new:N \__spintent_spmQ_join_word_str
2323 \str_new:N \__spintent_spmQ_intent_read_sign_str
2324 \tl_new:N \__spintent_spmQ_wrap_parens_l_tl
2325 \tl_new:N \__spintent_spmQ_wrap_parens_r_tl
2326 \int_new:N \__spintent_saved_luamml_flag_int

```

(End of definition for `\__spintent_spmQ_join_word_str` and others.)

11.30.2 Definition of error messages for \spmQ

The error message `spmQ-zero-denominator` is raised when a zero denominator is passed to `\spmQ`. The second error `spmQ-not-integer` is returned when the integer part passed in `{\langle argument \rangle}` is not actually an integer.

```

2327 \msg_new:nnnn { spintent } { spmQ-zero-denominator }
2328 {
2329   Zero~denominator~in~\token_to_str:N \spmQ~\msg_line_context:.
2330 }
2331 {
2332   The~denominator~of~a~fraction~cannot~be~zero.\\
2333 }
2334 \msg_new:nnnn { spintent } { spmQ-not-integer }
2335 {
2336   The~value~'#1'~is~not~a~valid~integer~\msg_line_context:.
2337 }
2338 {
2339   Command~\token_to_str:N \spmQ \c_space_tl only~accepts~integers.\\
2340 }

```

(End of definition for `spmQ-zero-denominator` and `spmQ-not-integer`.)

11.30.3 Definition of keys for \spmQ

Now we add the keys `join-word`, `use-spnZ`, `wrap-parens`, `read-parens` and `print-dfrac`.

```

join-word      2341 \keys_define:nn { spintent / spmQ }
use-spnZ      2342 {
wrap-parens   2343   join-word          .choices:nn =
read-parens   2344   { entero , enteros , y }
print-dfrac   2345   {
unknown       2346     \int_case:nn { \l_keys_choice_int }
                2347     {
                2348       {1} { \str_set:Nn \__spintent_spmQ_join_word_str { entero } }
                2349       {2} { \str_set:Nn \__spintent_spmQ_join_word_str { enteros } }
                2350       {3} { \str_set:Nn \__spintent_spmQ_join_word_str { y } }
                2351     }
                2352   },
join-word      2353   join-word          .initial:n = y,
join-word      2354   join-word          .value_required:n = true,
join-word/unknown 2355   join-word/unknown .code:n =
                2356   \msg_error:nnnee { spintent } { unknown-choice }
                2357   { join-word } { entero, ~enteros, ~y } { \exp_not:n {#1} },
use-spnZ      2358   use-spnZ          .bool_set:N = \__spintent_spmQ_use_spnZ_bool,
use-spnZ      2359   use-spnZ          .initial:n = true,
use-spnZ      2360   use-spnZ          .value_required:n = true,
print-dfrac   2361   print-dfrac       .bool_set:N = \__spintent_spmQ_print_dfrac_bool,
print-dfrac   2362   print-dfrac       .initial:n = false,
print-dfrac   2363   print-dfrac       .value_required:n = true,
wrap-parens   2364   wrap-parens      .bool_set:N = \__spintent_spmQ_wrap_parens_bool,
wrap-parens   2365   wrap-parens      .initial:n = false,
wrap-parens   2366   wrap-parens      .value_required:n = true,

```

```

2367     read-parens      .bool_set:N = \__spintent_spmQ_read_parens_bool,
2368     read-parens      .initial:n = true,
2369     read-parens      .value_required:n = true,
2370     unknown          .code:n =
2371     {
2372         \str_set:Nn \__spintent_command_name_str { spmQ }
2373         \__spintent_unknown_keys_cmd:n {#1}
2374     },
2375 }

```

(End of definition for join-word and others.)

11.30.4 Internal functions for \spmQ

The function `\__spintent_spmQ_set_wrap_parens_size:` captures the current mathematical style using the primitive `\mathstyle` from LaTeX and sets the variables `\__spintent_spmQ_wrap_parens_l_tl` and `\__spintent_spmQ_wrap_parens_r_tl` with the appropriate size for the parentheses. Display styles (0 and 1) receive `\Bigl\lparen` and `\Bigr\rparen`; text styles (2 and 3) receive `\bigl\lparen` and `\bigr\rparen`; any other style falls back to `\lparen` and `\rparen`.

If the key `print-dfrac` is active, the size is always forced to `\Bigl\lparen`/`\Bigr\rparen` regardless of the current mathematical style, since `\dfrac` always produces a display-height fraction.

```

2376 \cs_new_protected:Nn \__spintent_spmQ_set_wrap_parens_size:
2377 {
2378     \int_case:nnF { \mathstyle }
2379     {
2380         { 0 }
2381         {
2382             \tl_set:Nn \__spintent_spmQ_wrap_parens_l_tl { \Bigl \lparen }
2383             \tl_set:Nn \__spintent_spmQ_wrap_parens_r_tl { \Bigr \rparen }
2384         }
2385         { 1 }
2386         {
2387             \tl_set:Nn \__spintent_spmQ_wrap_parens_l_tl { \Bigl \lparen }
2388             \tl_set:Nn \__spintent_spmQ_wrap_parens_r_tl { \Bigr \rparen }
2389         }
2390         { 2 }
2391         {
2392             \tl_set:Nn \__spintent_spmQ_wrap_parens_l_tl { \bigl \lparen }
2393             \tl_set:Nn \__spintent_spmQ_wrap_parens_r_tl { \bigr \rparen }
2394         }
2395         { 3 }
2396         {
2397             \tl_set:Nn \__spintent_spmQ_wrap_parens_l_tl { \bigl \lparen }
2398             \tl_set:Nn \__spintent_spmQ_wrap_parens_r_tl { \bigr \rparen }
2399         }
2400     }
2401     {
2402         \tl_set:Nn \__spintent_spmQ_wrap_parens_l_tl { \lparen }
2403         \tl_set:Nn \__spintent_spmQ_wrap_parens_r_tl { \rparen }
2404     }

```

If the key `print-dfrac` is active, we must reset the variables `\__spintent_spmQ_wrap_parens_l_tl` and `\__spintent_spmQ_wrap_parens_r_tl` to `\Bigl\lparen`/`\Bigr\rparen` unconditionally.

```

2405     \bool_if:NT \__spintent_spmQ_print_dfrac_bool
2406     {
2407         \tl_set:Nn \__spintent_spmQ_wrap_parens_l_tl { \Bigl \lparen }
2408         \tl_set:Nn \__spintent_spmQ_wrap_parens_r_tl { \Bigr \rparen }
2409     }
2410 }

```

(End of definition for `\__spintent_spmQ_set_wrap_parens_size:`)

The functions `\__spintent_spmQ_start_wrap_parens:` and `\__spintent_spmQ_stop_wrap_parens:` open and close the parentheses around the “mixed number” when the key `wrap-parens` is active. They first call `\__spintent_spmQ_set_wrap_parens_size:` to determine the correct size for the current mathematical style, then print the appropriate parenthesis stored in `\__spintent_spmQ_wrap_parens_l_tl` or `\__spintent_spmQ_wrap_parens_r_tl`.

If the variable `\__spintent_spmQ_read_parens_bool`, controlled by the key `read-parens`, is *false*, each parenthesis is wrapped inside `\MathMLintent{:silent}` so that NVDA/MathCAT does not verbalize them.

```

2411 \cs_new_protected:Nn \__spintent_spmQ_start_wrap_parens:
2412 {

```

```

2413 \bool_if:NT \l__spinttent_spmQ_wrap_parens_bool
2414 {
2415   \__spinttent_spmQ_set_wrap_parens_size:
2416   \bool_if:NTF \l__spinttent_spmQ_read_parens_bool
2417     { \l__spinttent_spmQ_wrap_parens_l_tl }
2418     { \MathMLintent { :silent } { \l__spinttent_spmQ_wrap_parens_l_tl } }
2419 }
2420 }
2421 \cs_new_protected:Nn \__spinttent_spmQ_stop_wrap_parens:
2422 {
2423   \bool_if:NT \l__spinttent_spmQ_wrap_parens_bool
2424   {
2425     \__spinttent_spmQ_set_wrap_parens_size:
2426     \bool_if:NTF \l__spinttent_spmQ_read_parens_bool
2427       { \l__spinttent_spmQ_wrap_parens_r_tl }
2428       { \MathMLintent { :silent } { \l__spinttent_spmQ_wrap_parens_r_tl } }
2429   }
2430 }

```

(End of definition for `\__spinttent_spmQ_start_wrap_parens:` and `\__spinttent_spmQ_stop_wrap_parens:`.)

`\__spinttent_spmQ_set_join_word:`

The function `\__spinttent_spmQ_set_join_word:` injects the grammatical connector between the integer part and the fraction by dispatching on the value stored in `\l__spinttent_spmQ_join_word_str`, set by the key `join-word`. In all three cases the visual output is the Unicode invisible separator U+2063 via `\c__spinttent_invisible_sep_tl`, which produces a `<mi>` node in the MathML structure; what differs is the `:intent` text attached to it via `\MathMLintent`, which NVDA/MathCAT will verbalize as «entero», «enteros» or «y» respectively.

```

2431 \cs_new_protected:Nn \__spinttent_spmQ_set_join_word:
2432 {
2433   \str_case:Nn \l__spinttent_spmQ_join_word_str
2434   {
2435     { entero } { \MathMLintent { _entero } { \c__spinttent_invisible_sep_tl } }
2436     { enteros } { \MathMLintent { _enteros } { \c__spinttent_invisible_sep_tl } }
2437     { y } { \MathMLintent { _y- } { \c__spinttent_invisible_sep_tl } }
2438   }
2439 }

```

(End of definition for `\__spinttent_spmQ_set_join_word:`.)

`\__spinttent_spmQ_print_scale_int:`

The function `\__spinttent_spmQ_print_scale_int:` prints the integer part of the “mixed number” scaled to match the visual height of the accompanying fraction. Before calling the Lua function `\__spinttent_luafun_spmQ_scale_int` it temporarily disables `luamml` by saving the current value of `\l__luamml_flag_int` into `\l__spinttent_saved_luamml_flag_int` and setting it to `0` (skip completely). This prevents `luamml` from generating a spurious `<math>` wrapper around the `sub_box` node that holds the scaled integer, which is processed in isolation before `\frac` has expanded. Once the Lua function returns, the original flag value is restored via `\l__spinttent_saved_luamml_flag_int`.

The Lua function receives the integer digits from `\l__spinttent_luaset_part_int_tl` and the fraction command name (`\frac` or `\dfrac`, determined by the key `print-dfrac`) as its two arguments, and inserts the appropriately scaled `sub_box` node directly into the current horizontal list.

```

2440 \cs_new_protected:Nn \__spinttent_spmQ_print_scale_int:
2441 {
2442   \int_set_eq:Nc \l__spinttent_saved_luamml_flag_int { \l__luamml_flag_int }
2443   \int_set:Nn \l__luamml_flag_int { 0 }
2444   \bool_if:NTF \l__spinttent_spmQ_print_dfrac_bool
2445     { \__spinttent_luafun_spmQ_scale_int:Nn \l__spinttent_luaset_part_int_tl { dfraction } }
2446     { \__spinttent_luafun_spmQ_scale_int:Nn \l__spinttent_luaset_part_int_tl { fraction } }
2447   \int_set_eq:cN { \l__luamml_flag_int } \l__spinttent_saved_luamml_flag_int
2448 }

```

(End of definition for `\__spinttent_spmQ_print_scale_int:`.)

`\__spinttent_spmQ_print_scale_int:n`

The function `\__spinttent_spmQ_print_scale_int:n` takes the integer part of the “mixed number” passed in ‘#1’. It first calls `\__spinttent_luafun_clean_split_and_set:n` on ‘#1’ to parse and populate the shared Lua variables, then checks the status of `\l__spinttent_luaset_has_integer_str`.

If the status is `true`, it inspects `\l__spinttent_luaset_sign_tl`. When the sign is *empty*, it delegates directly to `\__spinttent_spmQ_print_scale_int:` to render the scaled integer. When a sign is present, it sets `\l__spinttent_spmQ_intent_read_sign_str` to either `_más:prefix($e)` or `_menos:prefix($e)` and wraps the sign glyph together with a MathML argument (`$e`) containing the scaled integer inside a `\MathMLintent`, so that NVDA/MathCAT verbalizes the sign as a prefix before the integer value. An

`\__spintent_invisible_sep`: call between the sign and the `MathMLarg` forces the opening of a new `<mrow>` in the MathML structure, which is required for the intent tree to be well-formed.

If the status is `false`, the `spmQ-not-integer` “error” is raised immediately.

```

2449 \cs_new_protected:Nn \__spintent_spmQ_print_scale_int:n
2450 {
2451   \__spintent_luafun_clean_split_and_set:n { \exp_not:n {#1} }
2452   \str_if_eq:VnTF \l__spintent_luaset_has_integer_str { true }
2453   {
2454     \tl_if_empty:NTF \l__spintent_luaset_sign_tl
2455     {
2456       \__spintent_spmQ_print_scale_int:
2457     }
2458     {
2459       \str_if_eq:VnTF \l__spintent_luaset_sign_tl { + }
2460       {
2461         \str_set:Nn
2462           \l__spintent_spmQ_intent_read_sign_str { _más:prefix($e) }
2463       }
2464       {
2465         \str_set:Nn
2466           \l__spintent_spmQ_intent_read_sign_str { _menos:prefix($e) }
2467       }
2468       \MathMLintent { \l__spintent_spmQ_intent_read_sign_str }
2469       {
2470         \l__spintent_luaset_sign_tl \__spintent_invisible_sep:
2471         \MathMLarg { e } { \__spintent_spmQ_print_scale_int: }
2472       }
2473     }
2474   }
2475   { \msg_error:nnn { spintent } { spmQ-not-integer } { #1 } }
2476 }

```

(End of definition for `\__spintent_spmQ_print_scale_int:n`.)

`\__spintent_spmQ_print_spmZ_dfrac:nn`

The function `\__spintent_spmQ_print_spmZ_dfrac:nn` typesets the fractional part of the “mixed number”. It takes the numerator in ‘`#1`’ and the denominator in ‘`#2`’. It first calls `\__spintent_luafun_clean_split_and_set:` on ‘`#1`’ to validate that the numerator is an integer; if `\l__spintent_luaset_has_integer_str` is `false`, the `spmQ-not-integer` “error” is raised immediately.

If the validation passes, the function dispatches on the two boolean variables `\l__spintent_spmQ_use_spmZ_bool` and `\l__spintent_spmQ_print_dfrac_bool`, controlled respectively by the keys `use-spmZ` and `print-dfrac`. When `use-spmZ` is `true`, both the numerator and denominator are passed through `\spnZ` to gain MathML integer semantics; otherwise, the raw token lists ‘`#1`’ and ‘`#2`’ are used directly. In both branches, the fraction command is selected dynamically via `\use:c`: if `print-dfrac` is `true`, `dfrac` is assembled; otherwise, `frac` is used.

```

2477 \cs_new_protected:Nn \__spintent_spmQ_print_spmZ_dfrac:nn
2478 {
2479   \__spintent_luafun_clean_split_and_set:n { \exp_not:n {#1} }
2480   \str_if_eq:VnTF \l__spintent_luaset_has_integer_str { false }
2481   {
2482     \msg_error:nnn { spintent } { spmQ-not-integer } { #1 }
2483   }
2484   \bool_if:NTF \l__spintent_spmQ_use_spmZ_bool
2485   {
2486     \use:c { \bool_if:NT \l__spintent_spmQ_print_dfrac_bool { d } frac }
2487     { \spnZ { #1 } } { \spnZ { #2 } }
2488   }
2489   {
2490     \use:c { \bool_if:NT \l__spintent_spmQ_print_dfrac_bool { d } frac }
2491     { #1 } { #2 }
2492   }
2493 }

```

(End of definition for `\__spintent_spmQ_print_spmZ_dfrac:nn`.)

`\__spintent_spmQ_print:nnn`

The function `\__spintent_spmQ_print:nnn` is the main rendering orchestrator for `\spmQ`. It takes three arguments: the integer part ‘`#1`’, the numerator ‘`#2`’, and the denominator ‘`#3`’. It opens the optional parentheses via `\__spintent_spmQ_start_wrap_parens:`, then calls `\__spintent_spmQ_print_scale_int:n` to scale and render the integer part. Next, it injects the grammatical connector between the integer and the fraction via `\__spintent_spmQ_set_join_word:`. Then it calls `\__spintent_spmQ_print_spmZ_dfrac:nn` to

typeset the fraction using the keys `print-dfrac` and `use-spnZ`. Finally, it closes the optional parentheses via `\\_spinttent_spmQ_stop_wrap_parens:`.

```

2494 \cs_new_protected:Nn \\_spinttent_spmQ_print:nnn
2495 {
2496   \\_spinttent_spmQ_start_wrap_parens:
2497   \\_spinttent_spmQ_print_scale_int:n { #1 }
2498   \\_spinttent_spmQ_set_join_word:
2499   \\_spinttent_spmQ_print_spnZ_dfrac:nn { #2 } { #3 }
2500   \\_spinttent_spmQ_stop_wrap_parens:
2501 }

```

(End of definition for `\\_spinttent_spmQ_print:nnn`.)

`\\_spinttent_spmQ_exec:nnnn`

The internal function `\\_spinttent_spmQ_exec:nnnn` takes four arguments: the optional *⟨keys⟩* ‘#1’, the integer ‘#2’, the numerator ‘#3’, and the denominator ‘#4’. First sets the optional *⟨keys⟩* from ‘#1’, then processes the denominator input in ‘#4’ using `\\_spinttent_luafun_clean_split_and_set:n` to validate it is a non-zero integer.

It checks the status of `\\_spinttent_luaaset_has_integer_str`. If `true` and the integer part is exactly zero, it issues the `spmQ-zero-denominator` “error”. Otherwise, whether the status is `false` or the integer part is *non-zero*, it calls `\\_spinttent_spmQ_print:nnn` to format the “mixed number”.

```

2502 \cs_new_protected:Nn \\_spinttent_spmQ_exec:nnnn
2503 {
2504   \keys_set:nn { spinttent / spmQ } { #1 }
2505   \\_spinttent_luafun_clean_split_and_set:n { \exp_not:n { #4 } }
2506   \str_if_eq:VnTF \\_spinttent_luaaset_has_integer_str { true }
2507   {
2508     \int_compare:nNnTF { \\_spinttent_luaaset_part_int_tl } = { 0 }
2509     { \msg_error:nn { spinttent } { spmQ-zero-denominator } }
2510     { \\_spinttent_spmQ_print:nnn { #2 } { #3 } { #4 } }
2511   }
2512   { \\_spinttent_spmQ_print:nnn { #2 } { #3 } { #4 } }
2513 }

```

(End of definition for `\\_spinttent_spmQ_exec:nnnn`.)

`\spmQ`

The command `\spmQ` is the public interface for formatting “mixed numbers”. It first checks if it is being used in *math mode*, issuing an “error” if not. Inside a local group, it calls `\\_spinttent_spmQ_exec:nnnn` to process the optional *⟨keys⟩* and the *⟨arguments⟩*.

```

2514 \NewDocumentCommand \spmQ { O{} m m m }
2515 {
2516   \mode_if_math:TF
2517   {
2518     \group_begin:
2519     \\_spinttent_spmQ_exec:nnnn { #1 } { #2 } { #3 } { #4 }
2520     \group_end:
2521   }
2522   { \msg_error:nnn { spinttent } { need-math-mode } { \spmQ } }
2523 }

```

(End of definition for `\spmQ`. This function is documented on page 16.)

11.31 The commands of the geo family

The commands described in this section provide a semantic interface for geometric objects in Spanish mathematical contexts. They all delegate parsing to `spinttent.lua`, sharing the variables `\\_spinttent_geo_luaaset_error_str`, `\\_spinttent_geo_luaaset_intent_str` and `\\_spinttent_geo_luaaset_print_tl`, constructing a valid MathCAT intent.

11.31.1 Definition of shared variables

Internal variables shared across all commands of the family to avoid repeated calls into Lua.

```

\\_spinttent_geo_luaaset_error_str
\\_spinttent_geo_luaaset_intent_str
\\_spinttent_geo_luaaset_print_tl
st \\_spinttent_geo_luaaset_is_name_str
\\_spinttent_geo_luaaset_poly_sym_str
\\_spinttent_geo_luaaset_angulo_case_str
\\_spinttent_geo_luaaset_concept_str
\\_spinttent_geo_luaaset_letra_word_str
\\_spinttent_geo_luaaset_sub_spoken_str
\\_spinttent_geo_luaaset_nombre_es_num_str
\\_spinttent_geo_luaaset_letra_str
\\_spinttent_geo_luaaset_sub_str
\\_spinttent_geo_luaaset_tipo_str
2524 \str_new:N \\_spinttent_geo_luaaset_error_str
2525 \str_new:N \\_spinttent_geo_luaaset_intent_str
2526 \tl_new:N \\_spinttent_geo_luaaset_print_tl
2527 \clist_new:N \\_spinttent_geo_luaaset_points_clist
2528 \str_new:N \\_spinttent_geo_luaaset_is_name_str
2529 \str_new:N \\_spinttent_geo_luaaset_poly_sym_str
2530 \str_new:N \\_spinttent_geo_luaaset_angulo_case_str
2531 \str_new:N \\_spinttent_geo_luaaset_concept_str
2532 \str_new:N \\_spinttent_geo_luaaset_letra_word_str
2533 \str_new:N \\_spinttent_geo_luaaset_sub_spoken_str
2534 \str_new:N \\_spinttent_geo_luaaset_nombre_es_num_str

```

```

2535 \str_new:N \l__spintent_geo_luaset_letra_str
2536 \str_new:N \l__spintent_geo_luaset_sub_str
2537 \str_new:N \l__spintent_geo_luaset_tipo_str

```

(End of definition for `\l__spintent_geo_luaset_error_str` and others.)

11.32 The command `\spcoord`

The user command `\spcoord` typesets an ordered pair (x,y) , with the comma (or semicolon) between them carrying its own `:infix` intent, and each side wrapped with `:prefix($vp)/:prefix($vn)` when it starts with $+/-$, so the sign is always read as más/menos — never positivo/negativo, which is not how MathCAT reads a bare sign in this position.

11.32.1 Definition of variables for `\spcoord`

Set by `\__spintent_luafun_spcoord_parse_and_set:n`. `\l__spintent_spcoord_luaset_sep_str` is `,` or `;`, whichever the argument actually used. For each side, `\l__spintent_spcoord_luaset_ #1 _sign_str` is `+`, `-`, or empty; `\l__spintent_spcoord_luaset_ #1 _type_str` is `number` or `raw`; `\l__spintent_spcoord_luaset_ #1 _value_str` is the value with the sign already removed; `\l__spintent_spcoord_luaset_ #1 _has_frac_str` is `none`, `frac`, or `dfrac`.

```

2538 \str_new:N \l__spintent_spcoord_luaset_error_str
2539 \str_new:N \l__spintent_spcoord_luaset_sep_str
2540 \str_new:N \l__spintent_spcoord_luaset_x_sign_str
2541 \str_new:N \l__spintent_spcoord_luaset_x_type_str
2542 \str_new:N \l__spintent_spcoord_luaset_x_value_str
2543 \str_new:N \l__spintent_spcoord_luaset_x_has_frac_str % "none" / "frac" / "dfrac"
2544 \str_new:N \l__spintent_spcoord_luaset_y_sign_str
2545 \str_new:N \l__spintent_spcoord_luaset_y_type_str
2546 \str_new:N \l__spintent_spcoord_luaset_y_value_str
2547 \str_new:N \l__spintent_spcoord_luaset_y_has_frac_str % "none" / "frac" / "dfrac"

```

(End of definition for `\l__spintent_spcoord_luaset_error_str` and others.)

`\l__spintent_spcoord_raw_arg_tl` holds the argument exactly as given, for `silent-cmd`. `\l__spintent_spcoord_intent_str` holds the `:infix` word for the separator (`_coma:infix` or `_punto-y-coma:infix`). `\l__spintent_spcoord_wrap_l_tl` and `\l__spintent_spcoord_wrap_r_tl` hold the opening/closing delimiter, sized by `\__spintent_spcoord_set_wrap_parens_size:`.

```

2548 \tl_new:N \l__spintent_spcoord_raw_arg_tl
2549 \str_new:N \l__spintent_spcoord_intent_str % ,;:infix
2550 \tl_new:N \l__spintent_spcoord_wrap_parens_l_tl
2551 \tl_new:N \l__spintent_spcoord_wrap_parens_r_tl

```

(End of definition for `\l__spintent_spcoord_raw_arg_tl` and others.)

11.32.2 Definition of error messages for `\spcoord`

`spcoord-invalid-arg`

```

2552 \msg_new:nnn { spintent } { spcoord-invalid-arg }
2553 {
2554   Invalid~argument~'#1'~for~\token_to_str:N \spcoord.
2555 }

```

(End of definition for `spcoord-invalid-arg`.)

11.32.3 Definition of keys for `\spcoord`

`silent-cmd`

We define the key `silent-cmd`.

```

2556 \bool_new:N \l__spintent_spPoint_coord_silent_cmd_bool
2557 \keys_define:nn { spintent / spcoord }
2558 {
2559   silent-cmd .bool_set:N = \l__spintent_spcoord_silent_cmd_bool,
2560   silent-cmd .initial:n = false,
2561   silent-cmd .value_required:n = true,
2562   unknown .code:n =
2563     {
2564       \str_set:Nn \l__spintent_command_name_str { spcoord }
2565       \__spintent_unknown_keys_cmd:n {#1}
2566     },
2567 }

```

(End of definition for `silent-cmd`.)

11.32.4 Internal functions for \spcoord

__spintenc_spcoord_set_wrap_parens_size:

With neither side carrying a fraction, the parentheses stay unsized. Otherwise, `\mathstyle` picks `\Bigl/\Bigr` for display, `\bigl/\bigr` for text — same mechanism as `\__spintenc_spmQ_set_wrap_parens_size:`. When either side is `\dfrac`, the parentheses are forced to `\Bigl/\Bigr` regardless of `\mathstyle`, since `\dfrac` always renders at display height — same criterion as `print-dfrac` in `\spnQ`.

```

2568 \cs_new_protected:Nn \__spintenc_spcoord_set_wrap_parens_size:
2569 {
2570   \tl_set:Nn \l__spintenc_spcoord_wrap_parens_l_tl { \lparen }
2571   \tl_set:Nn \l__spintenc_spcoord_wrap_parens_r_tl { \rparen }
2572   \bool_if:nT
2573   {
2574     \bool_lazy_or_p:nn
2575     { \bool_not_p:n { \str_if_eq_p:Vn \l__spintenc_spcoord_luaset_x_has_frac_str { none } } }
2576     { \bool_not_p:n { \str_if_eq_p:Vn \l__spintenc_spcoord_luaset_y_has_frac_str { none } } }
2577   }
2578   {
2579     \int_case:nnF { \mathstyle }
2580     {
2581       { 0 }
2582       {
2583         \tl_set:Nn \l__spintenc_spcoord_wrap_parens_l_tl { \Bigl \lparen }
2584         \tl_set:Nn \l__spintenc_spcoord_wrap_parens_r_tl { \Bigr \rparen }
2585       }
2586       { 1 }
2587       {
2588         \tl_set:Nn \l__spintenc_spcoord_wrap_parens_l_tl { \Bigl \lparen }
2589         \tl_set:Nn \l__spintenc_spcoord_wrap_parens_r_tl { \Bigr \rparen }
2590       }
2591       { 2 }
2592       {
2593         \tl_set:Nn \l__spintenc_spcoord_wrap_parens_l_tl { \bigl \lparen }
2594         \tl_set:Nn \l__spintenc_spcoord_wrap_parens_r_tl { \bigr \rparen }
2595       }
2596       { 3 }
2597       {
2598         \tl_set:Nn \l__spintenc_spcoord_wrap_parens_l_tl { \bigl \lparen }
2599         \tl_set:Nn \l__spintenc_spcoord_wrap_parens_r_tl { \bigr \rparen }
2600       }
2601     }
2602   }
2603   \bool_if:nT
2604   {
2605     \bool_lazy_or_p:nn
2606     { \str_if_eq_p:Vn \l__spintenc_spcoord_luaset_x_has_frac_str { \dfrac } }
2607     { \str_if_eq_p:Vn \l__spintenc_spcoord_luaset_y_has_frac_str { \dfrac } }
2608   }
2609   {
2610     \tl_set:Nn \l__spintenc_spcoord_wrap_parens_l_tl { \Bigl \lparen }
2611     \tl_set:Nn \l__spintenc_spcoord_wrap_parens_r_tl { \Bigr \rparen }
2612   }
2613 }
2614 }

```

(End of definition for __spintenc_spcoord_set_wrap_parens_size:.)

__spintenc_spcoord_value:n

With `\l__spintenc_spcoord_luaset_ #1 _type_str` equal to `number`, calls `\spnum` on `\l__spintenc_spcoord_value:n`. Otherwise, typesets it as given — a `\frac/\dfrac` or a letter expression, untouched. Receives `x` or `y` in `'#1'`.

```

2615 \cs_new_protected:Nn \__spintenc_spcoord_value:n
2616 {
2617   \str_if_eq:eeTF { \str_use:c { \l__spintenc_spcoord_luaset_ #1 _type_str } } { number }
2618   { \exp_args:Ne \spnum { \str_use:c { \l__spintenc_spcoord_luaset_ #1 _value_str } } }
2619   { \str_use:c { \l__spintenc_spcoord_luaset_ #1 _value_str } }
2620 }

```

(End of definition for __spintenc_spcoord_value:n.)

__spintenc_spcoord_print:n

With `\l__spintenc_spcoord_luaset_ #1 _sign_str` equal to `+` or `-`, wraps the sign and `\__spintenc_spcoord_value:n` together with `_más:prefix($vp)/_menos:prefix($vn)`, referencing the value through `read as más/menos`, never positive/negativo. With no sign, delegates directly to `\__spintenc_spcoord_value:n`. Receives `x` or `y` in `'#1'`.

```

2621 \cs_new_protected:Nn \__spintenc_spcoord_print:n

```

```

2622 {
2623   \str_case:enF { \str_use:c { l__spintent_spcoord_luaset_ #1 _sign_str } }
2624   {
2625     { + }
2626     {
2627       \MathMLintent { _más:prefix ($vp) }
2628       {
2629         \str_use:c { l__spintent_spcoord_luaset_ #1 _sign_str }
2630         \MathMLarg{ vp } { \__spintent_spcoord_value:n { #1 } }
2631       }
2632     }
2633     { - }
2634     {
2635       \MathMLintent { _menos :prefix($vn) }
2636       {
2637         \str_use:c { l__spintent_spcoord_luaset_ #1 _sign_str }
2638         \MathMLarg{ vn } { \__spintent_spcoord_value:n { #1 } }
2639       }
2640     }
2641   }
2642   { \__spintent_spcoord_value:n { #1 } }
2643 }

```

(End of definition for `\__spintent_spcoord_print:n`.)

`\__spintent_spcoord_intent_infix:` Sets `\__spintent_spcoord_intent_str` to `_coma:infix` or `_punto-y-coma:infix`, per `\l__spintent_spcoord_intent_infix:choice`. Then wraps both sides — each referenced through with it, `$x/$y` standing for `\__spintent_spcoord_print:n`'s own output.

```

2644 \cs_new_protected:Nn \__spintent_spcoord_intent_infix:
2645 {
2646   \str_if_eq:VnTF \l__spintent_spcoord_luaset_sep_str { ; }
2647   { \str_set:Nn \l__spintent_spcoord_intent_str { _punto-y-coma:infix } }
2648   { \str_set:Nn \l__spintent_spcoord_intent_str { _coma:infix } }
2649   \MathMLintent{ \l__spintent_spcoord_intent_str ($x, $y)}
2650   {
2651     \MathMLarg{x}{ \__spintent_spcoord_print:n { x } }
2652     \MathMLintent { :silent } { \l__spintent_spcoord_luaset_sep_str }
2653     \MathMLarg{y}{ \__spintent_spcoord_print:n { y } }
2654   }
2655 }

```

(End of definition for `\__spintent_spcoord_intent_infix:`.)

`\__spintent_spcoord_mathml:` With `silent-cmd` true, everything — parentheses and argument alike — is wrapped in a single `_-`, reading nothing at all: `\l__spintent_spcoord_raw_arg_tl` is typeset exactly as given, untouched by `\__spintent_spcoord_print:n/\__spintent_spcoord_intent_infix:`. Otherwise, the parentheses are silenced individually and `\__spintent_spcoord_intent_infix:` provides the reading in between.

```

2656 \cs_new_protected:Nn \__spintent_spcoord_mathml:
2657 {
2658   \bool_if:NTF \l__spintent_spcoord_silent_cmd_bool
2659   {
2660     \MathMLintent { _- }
2661     {
2662       \l__spintent_spcoord_wrap_parens_l_tl
2663       \l__spintent_spcoord_raw_arg_tl
2664       \l__spintent_spcoord_wrap_parens_r_tl
2665     }
2666   }
2667   {
2668     \MathMLintent { :silent } { \l__spintent_spcoord_wrap_parens_l_tl }
2669     \__spintent_spcoord_intent_infix:
2670     \MathMLintent { :silent } { \l__spintent_spcoord_wrap_parens_r_tl }
2671   }
2672 }

```

(End of definition for `\__spintent_spcoord_mathml:`.)

`\__spintent_spcoord_exec:nn` Sets the *(keys)* in `#1` and `\l__spintent_spcoord_raw_arg_tl` to `#2`. Calls `\__spintent_luafun_spcoord_parse` either way — even with `silent-cmd` true, since `\__spintent_spcoord_set_wrap_parens_size:` still needs `\l__spintent_spcoord_luaset_ #1 _has_frac_str` — but with `silent-cmd` true, forces `\l__spintent_spcoord_luaset_error_str` back to `false` rather than reporting it: the raw argument is

typeset regardless of whether it parsed. Otherwise, reports `spcoord-invalid-arg` on error. Either way, sizes the parentheses, then delegates to `\__spintent_spcoord_mathml:` unless there was an error.

```

2673 \cs_new_protected:Nn \__spintent_spcoord_exec:nn
2674 {
2675   \keys_set:nn { spintent / spcoord } {#1}
2676   \tl_set:Nn \l__spintent_spcoord_raw_arg_tl {#2}
2677   \bool_if:NTF \l__spintent_spcoord_silent_cmd_bool
2678   {
2679     \__spintent_luafun_spcoord_parse_and_set:n { \exp_not:n {#2} }
2680     \str_set:Nn \l__spintent_spcoord_luaset_error_str { false }
2681   }
2682   {
2683     \__spintent_luafun_spcoord_parse_and_set:n { \exp_not:n {#2} }
2684     \str_if_eq:VnT \l__spintent_spcoord_luaset_error_str { true }
2685     { \msg_error:nnn { spintent } { spcoord-invalid-arg } { \exp_not:n {#2} } }
2686   }
2687   \__spintent_spcoord_set_wrap_parens_size:
2688   \str_if_eq:VnF \l__spintent_spcoord_luaset_error_str { true }
2689   { \__spintent_spcoord_mathml: }
2690 }

```

(End of definition for `\__spintent_spcoord_exec:nn`.)

`\spcoord` The public command enforces *math mode*, opens a local group, and delegates to `\__spintent_spcoord_exec:nn`.

```

2691 \NewDocumentCommand \spcoord { 0{ } m }
2692 {
2693   \mode_if_math:TF
2694   {
2695     \group_begin:
2696     \__spintent_spcoord_exec:nn {#1} {#2}
2697     \group_end:
2698   }
2699   { \msg_error:nnn { spintent } { need-math-mode } { \spcoord } }
2700 }

```

(End of definition for `\spcoord`. This function is documented on page ??.)

11.33 The function `\__spintent_mathmlarg_point:nnn`

Annotates one point (`#3`) with `arg` and, when applicable, a literal *intent*, without wrapping it in its own `<mrow>`. `#1` is the reference name (`arg="#1"`); `#2` is the calling command's name, used to look up its own `silent-cmd/read-cmd` variables. Same kv logic as `\__spintent_spPoint_mathml:`. Concept *intent* is passed empty on purpose: the caller applies it once, externally, via a native `\MathMLintent`.

With `\l__spintent_geo_luaset_tipo_str` equal to `sub` (a genuine subscript, not a prime), the letter alone (`\l__spintent_geo_luaset_letra_str`) is wrapped through `\__spintent_luafun_wrap_mrow_intent_arg:n` — the shared queue only ever claims the base of an `<msub>`, never its own subscript (confirmed with `\spPoint{A_{1}}\spPoint{B}`: the visual subscript was left bare, and a later command's own queue entry landed on it instead of its intended target) — and the visual subscript (`\l__spintent_geo_luaset_sub_str`) is appended separately, as a real `\c_math_subscript_token`, silenced with a native `\MathMLintent`: it is already spoken as part of the combined literal on the base, so reading it again natively would repeat it. Otherwise (no subscript, or a prime — which is not a genuine `<msub>` at all), the combined `\l__spintent_geo_luaset_print_tl` is wrapped as a whole, exactly as before.

```

2701 \tl_new:N \l__spintent_mathmlarg_point_ref_tl
2702 \str_new:N \l__spintent_mathmlarg_point_mode_str
2703 \tl_new:N \l__spintent_mathmlarg_point_kv_tl
2704 \bool_new:N \l__spintent_mathmlarg_point_silent_bool
2705 \cs_new_protected:Nn \__spintent_mathmlarg_point:nnn
2706 {
2707   \tl_set:Nn \l__spintent_mathmlarg_point_ref_tl {#1}
2708   \__spintent_luafun_geo_point_parse_and_set:n { \exp_not:n {#3} }
2709   \bool_set_eq:Nc \l__spintent_mathmlarg_point_silent_bool { \l__spintent_#2_silent_cmd_bool }
2710   \str_set_eq:Nc \l__spintent_mathmlarg_point_mode_str { \l__spintent_#2_mode_str }
2711   \__spintent_invisible_sep:
2712   \bool_if:NTF \l__spintent_mathmlarg_point_silent_bool
2713   {
2714     \tl_set:Ne \l__spintent_mathmlarg_point_kv_tl
2715     { arg = "\l__spintent_mathmlarg_point_ref_tl", intent = "-" }
2716   }
2717   {
2718     \str_if_eq:VnTF \l__spintent_mathmlarg_point_mode_str { school }
2719     {

```

```

2720         \tl_set:Nc \l__spintent_mathmlarg_point_kv_tl
2721         { arg = "\l__spintent_mathmlarg_point_ref_tl", intent = "_ \l__spintent_geo_luaset_"
2722     }
2723     {
2724         \tl_set:Nc \l__spintent_mathmlarg_point_kv_tl { arg = "\l__spintent_mathmlarg_point_r
2725     }
2726 }
2727 \str_if_eq:VnTF \l__spintent_geo_luaset_tipo_str { sub }
2728 {
2729     \__spintent_luafun_wrap_mrow_intent_arg:nn
2730     { } % debe ir vacío
2731     { \l__spintent_mathmlarg_point_kv_tl }
2732     { \l__spintent_geo_luaset_letra_str }
2733     \c_math_subscript_token
2734     {
2735         \MathMLintent { :silent } { \l__spintent_geo_luaset_sub_str }
2736     }
2737 }
2738 {
2739     \__spintent_luafun_wrap_mrow_intent_arg:nn
2740     { } % debe ir vacío
2741     { \l__spintent_mathmlarg_point_kv_tl }
2742     { \l__spintent_geo_luaset_print_tl }
2743 }
2744 }
2745 \cs_generate_variant:Nn \__spintent_mathmlarg_point:nnn { nnV }

```

(End of definition for `\l__spintent_mathmlarg_point:nnn` and others.)

11.34 The command `\spPoint`

The user-level command `\spPoint` provides a semantic interface for a single geometric point. It delegates argument validation to the Lua module `spintent.lua`, constructing a valid MathCAT intent.

11.34.1 Definition of variables for `\spPoint`

Internal variables holding the values set by `read-cmd` and `prefix`.

```

\l__spintent_spPoint_silent_cmd_bool
\l__spintent_spPoint_mode_str
\l__spintent_spPoint_prefix_tl
\l__spintent_spPoint_intent_arg_tl
\l__spintent_spPoint_kv_tl
2746 \bool_new:N \l__spintent_spPoint_silent_cmd_bool
2747 \str_new:N \l__spintent_spPoint_mode_str
2748 \tl_new:N \l__spintent_spPoint_prefix_tl
2749 \tl_new:N \l__spintent_spPoint_intent_arg_tl
2750 \tl_new:N \l__spintent_spPoint_kv_tl

```

(End of definition for `\l__spintent_spPoint_silent_cmd_bool` and others.)

11.34.2 Definition of error messages for `\spPoint`

`spPoint-invalid-point`

The “error” `spPoint-invalid-point` is raised when the argument passed in ‘`#1`’ is not a single uppercase letter with an optional subscript or prime modifier.

```

2751 \msg_new:nnnn { spintent } { spPoint-invalid-point }
2752 {
2753     Invalid~point~format~in~\token_to_str:N \spPoint:~'~#1'.
2754 }
2755 {
2756     The~argument~must~be~a~single~uppercase~letter~with~an~optional~
2757     subscript~(\_{...})~or~prime~(').\\
2758 }

```

(End of definition for `spPoint-invalid-point`.)

11.34.3 Definition of keys for `\spPoint`

`read-cmd`
`prefix`
`silent-cmd`
`unknown`

We define the *(keys)* `read-cmd`, `prefix`, `silent-cmd` and `concept`.

```

2759 \keys_define:nn { spintent / spPoint }
2760 {
2761     read-cmd .choices:nn = { school , mathcat }
2762     {
2763         \int_case:nn { \l_keys_choice_int }
2764         {
2765             {1} { \str_set:Nn \l__spintent_spPoint_mode_str { school } }
2766             {2} { \str_set:Nn \l__spintent_spPoint_mode_str { mathcat } }
2767         }
2768     },
2769     read-cmd .initial:n = school,
2770     read-cmd .value_required:n = true,

```

```

2771   read-cmd / unknown .code:n =
2772     \msg_error:nneee { spintent } { unknown-choice }
2773     { read-cmd } { school,~mathcat } { \exp_not:n {#1} },
2774   prefix .code:n =
2775     { \__spintent_sanitizize_affix:Nn \__spintent_spPoint_prefix_tl {#1} },
2776   prefix .initial:n = ,
2777   prefix .value_required:n = true,
2778   _silent_point .bool_set:N = \__spintent_spPoint_silent_cmd_bool,
2779   _silent_point .value_required:n = true,
2780   _silent_coord .bool_set:N = \__spintent_spPoint_coord_silent_cmd_bool,
2781   _silent_coord .value_required:n = true,
2782   silent-cmd .meta:n = { _silent_point = #1, _silent_coord = #1 },
2783   silent-cmd .initial:n = false,
2784   silent-cmd .value_required:n = true,
2785   concept .bool_set:N = \__spintent_spPoint_concept_bool,
2786   concept .initial:n = true,
2787   concept .value_required:n = true,
2788   unknown .code:n =
2789     {
2790       \str_set:Nn \__spintent_command_name_str { spPoint }
2791       \__spintent_unknown_keys_cmd:n {#1}
2792     },
2793 }

```

(End of definition for `read-cmd` and others.)

11.34.4 Internal functions for `\spPoint`

`\__spintent_spPoint_print:n`

The internal function `\__spintent_spPoint_print:n` process the $\langle argument \rangle$ passed in ‘#1’. First, call the function `\__spintent_luafun_geo_parse_and_set:n` to process the $\langle argument \rangle$, returning an “error” if the input is invalid. Then, if `silent-cmd` is `true` or `concept` is `false`, set `\__spintent_spPoint_intent_arg` to `:silent($pt)`; otherwise set it to `punto:prefix($pt)`, prefixed with `prefix` when given. Finally, call `\__spintent_spPoint_mathml:`.

```

2794 \cs_new_protected:Nn \__spintent_spPoint_print:n
2795 {
2796   \__spintent_luafun_geo_point_parse_and_set:n { \exp_not:n {#1} }
2797   \str_if_eq:VnT \__spintent_geo_luaaset_error_str { true }
2798   {
2799     \msg_error:nne { spintent } { spPoint-invalid-point } { \exp_not:n {#1} }
2800   }
2801   \bool_if:nTF
2802   {
2803     \bool_lazy_or_p:nn
2804     { \__spintent_spPoint_silent_cmd_bool }
2805     { ! \__spintent_spPoint_concept_bool }
2806   }
2807   {
2808     \tl_set:Nn \__spintent_spPoint_intent_arg_tl { :silent($pt) }
2809   }
2810   {
2811     \tl_set:Ne \__spintent_spPoint_intent_arg_tl
2812     {
2813       \tl_if_empty:NF \__spintent_spPoint_prefix_tl
2814       {
2815         \tl_use:N \__spintent_spPoint_prefix_tl -
2816       }
2817       punto:prefix($pt)
2818     }
2819   }
2820   \__spintent_spPoint_mathml:
2821 }

```

(End of definition for `\__spintent_spPoint_print:n`.)

`\__spintent_spPoint_mathml:`

The function `\__spintent_spPoint_mathml:` generates the `<mrow>` and prints `\__spintent_geo_luaaset_print`. `\__spintent_invisible_sep:` is called first (luamml issue #26).

The kv string is `arg="pt"`, `intent="_-"` when `silent-cmd` is `true`; otherwise, for `read-cmd=school` it is `arg="pt"`, `intent="_body-"` (literal spelling); for `read-cmd=mathcat` it is `arg="pt"` alone.

With `\__spintent_geo_luaaset_tipo_str` equal to `sub`, a native `\MathMLintent` wraps the base (tagged `arg="pt"` through `\__spintent_luafun_wrap_mrow_intent_arg:nn`) and the subscript (silenced) together, with `\__spintent_spPoint_intent_arg_tl` as its intent — the shared queue only ever covers the base of an `<msub>`. Otherwise, a single call to `\__spintent_luafun_wrap_mrow_intent_arg:nn` applies

the kv string to the whole `\l__spintent_geo_luaset_print_tl`, with `\l__spintent_spPoint_intent_arg_tl` as the concept `intent`.

```

2822 \cs_new_protected:Nn \l__spintent_spPoint_mathml:
2823 {
2824   \l__spintent_invisible_sep:
2825   \bool_if:NTF \l__spintent_spPoint_silent_cmd_bool
2826   {
2827     \tl_set:Nn \l__spintent_spPoint_kv_tl { arg = "pt", intent = "-" }
2828   }
2829   {
2830     \str_if_eq:VnTF \l__spintent_spPoint_mode_str { school }
2831     {
2832       \tl_set:Ne \l__spintent_spPoint_kv_tl
2833       { arg = "pt", intent = "-" \l__spintent_geo_luaset_intent_str -" }
2834     }
2835     {
2836       \tl_set:Nn \l__spintent_spPoint_kv_tl { arg = "pt" }
2837     }
2838   }
2839   \str_if_eq:VnTF \l__spintent_geo_luaset_tipo_str { sub }
2840   {
2841     \MathMLintent { \l__spintent_spPoint_intent_arg_tl }
2842     {
2843       \l__spintent_luafun_inner_sep:
2844       \l__spintent_luafun_wrap_mrow_intent_arg:nn
2845       { } { \l__spintent_spPoint_kv_tl }
2846       { \l__spintent_geo_luaset_letra_str }
2847       \c_math_subscript_token
2848       { \MathMLintent { :silent } { \l__spintent_geo_luaset_sub_str } }
2849     }
2850   }
2851   {
2852     \l__spintent_luafun_wrap_mrow_intent_arg:nn
2853     { \l__spintent_spPoint_intent_arg_tl }
2854     { \l__spintent_spPoint_kv_tl }
2855     { \l__spintent_geo_luaset_print_tl }
2856   }
2857 }

```

(End of definition for `\l__spintent_spPoint_mathml:`)

`\l__spintent_spPoint_exec:nn`

The function `\l__spintent_spPoint_exec:nn` receives the optional *(keys)* passed in ‘#1’ and the *(argument)* passed in ‘#2’ delegating the rendering of the latter to `\l__spintent_spPoint_print:n`.

```

2858 \cs_new_protected:Nn \l__spintent_spPoint_exec:nn
2859 {
2860   \keys_set:nn { spintent / spPoint } { #1 }
2861   \l__spintent_spPoint_print:n { #2 }
2862 }

```

(End of definition for `\l__spintent_spPoint_exec:nn`)

`\spPoint`

The public command `\spPoint` enforces *math mode*, opens a local group, and delegates execution to `\l__spintent_spPoint_exec:nn`.

```

2863 \NewDocumentCommand \spPoint { 0{} m }
2864 {
2865   \mode_if_math:TF
2866   {
2867     \group_begin:
2868     \l__spintent_spPoint_exec:nn { #1 } { #2 }
2869     \group_end:
2870   }
2871   { \msg_error:nnn { spintent } { need-math-mode } { \spPoint } }
2872 }

```

(End of definition for `\spPoint`. This function is documented on page 17.)

11.35 The command `\sprecta`

The user command `\sprecta` supports two types of notation for the input *(argument)*: when the argument contains two points (separated by an optional comma), `\overleftarrow` is applied; when the argument is a single point (without comma) or a lowercase letter, it is formatted without any visual decorator. Both notations are automatically detected by the Lua module.

11.35.1 Definition of variables for \sprecta

The variable `\__spintent_sprecta_mode_str` store the values set by the key `read-cmd` and the variable `\__spintent_sprayo_prefix_tl` store the value set by the key `prefix`.

```
2873 \str_new:N \__spintent_sprecta_mode_str
2874 \tl_new:N \__spintent_sprecta_prefix_tl
2875 \seq_new:N \__spintent_sprecta_pt_seq
2876 \tl_new:N \__spintent_sprecta_refs_tl
2877 \tl_new:N \__spintent_sprecta_intent_arg_tl
2878 \tl_new:N \__spintent_sprecta_kv_tl
2879 \int_new:N \__spintent_sprecta_pt_idx_int
```

(End of definition for `\__spintent_sprecta_mode_str` and others.)

11.35.2 Definition of error messages for \sprecta

The “error” `sprecta-invalid-points` is raised when the argument matches neither the two-point notation nor the name notation.

```
2880 \msg_new:nnnn { spintent } { sprecta-invalid-points }
2881 {
2882   Invalid~format~in~\token_to_str:N \sprecta:~'#1'~\msg_line_context:.
2883 }
2884 {
2885   See~the~documentation~of~\token_to_str:N \sprecta~for~the~accepted~argument~forms.
2886 }
```

(End of definition for `sprecta-invalid-points`.)

11.35.3 Definition of keys for \sprecta

We define the *(keys)* `read-cmd`, `prefix` and `silent-cmd`.

```
read-cmd 2887 \keys_define:nn { spintent / sprecta }
prefix    2888 {
silent-cmd 2889   read-cmd           .choices:nn = { school , mathcat }
unknown   2890   {
2891     \int_case:nn { \_keys_choice_int }
2892     {
2893       {1} { \str_set:Nn \__spintent_sprecta_mode_str { school } }
2894       {2} { \str_set:Nn \__spintent_sprecta_mode_str { mathcat } }
2895     }
2896   },
2897   read-cmd           .initial:n = school,
2898   read-cmd           .value_required:n = true,
2899   read-cmd / unknown .code:n =
2900     \msg_error:nnee { spintent } { unknown-choice }
2901     { read-cmd } { school,~mathcat } { \exp_not:n {#1} },
2902   prefix             .code:n =
2903     { \__spintent_sanitize_affix:Nn \__spintent_sprecta_prefix_tl {#1} },
2904   prefix             .initial:n = ,
2905   prefix             .value_required:n = true,
2906   silent-cmd         .bool_set:N = \__spintent_sprecta_silent_cmd_bool,
2907   silent-cmd         .initial:n = false,
2908   silent-cmd         .value_required:n = true,
2909   concept            .bool_set:N = \__spintent_sprecta_concept_bool,
2910   concept            .initial:n = true,
2911   concept            .value_required:n = true,
2912   unknown            .code:n =
2913     {
2914       \str_set:Nn \__spintent_command_name_str { sprecta }
2915       \__spintent_unknown_keys_cmd:n {#1}
2916     },
2917 }
```

(End of definition for `read-cmd` and others.)

11.35.4 Internal functions for \sprecta

The internal function `\__spintent_sprecta_print:n` process the *{(argument)}* passed in ‘#1’. It calls `\__spintent_luafun_geo_parse_and_set:n` to process the *{(argument)}*, returning an “error” if the input is invalid, then calls `\__spintent_sprecta_mathml:`. Unlike `\spPoint`, no `intent` is built here: both branches of `\__spintent_sprecta_mathml:` build their own, since a proper name (m, l, ...) and a list of points need different amounts of it (a single `$pt` versus `$pt1`, `$pt2`, `\ldots`).

```
2918 \cs_new_protected:Nn \__spintent_sprecta_print:n
2919 {
```

```

2920     \__spintent_luafun_geo_parse_and_set:n { \exp_not:n {#1} }
2921     \str_if_eq:VnT \__spintent_geo_luaset_error_str { true }
2922     {
2923         \msg_error:nne { spintent } { sprecta-invalid-points } { \exp_not:n {#1} }
2924     }
2925     \__spintent_sprecta_mathml:
2926 }

```

(End of definition for __spintent_sprecta_print:n.)

__spintent_sprecta_mathml: The function __spintent_sprecta_mathml: branches on __spintent_geo_luaset_is_name_str. For a proper name (m, l, ...), the concept intent is :silent(\$pt) when silent-cmd is true or concept is false; otherwise recta:prefix(\$pt), prefixed with prefix when given. The kv string depends only on silent-cmd: arg="pt", intent="-" when silent; otherwise arg="pt" plus a literal intent for read-cmd=school, or arg="pt" alone for read-cmd=mathcat. With __spintent_geo_luaset_tipo_str equal to sub, a native \MathMLintent wraps the base (tagged via __spintent_luafun_wrap_mrow_intent_arg:n) and the subscript (silenced) together — the shared queue only ever covers the base of an <msub>. Otherwise, a single call to __spintent_luafun_wrap_mrow_intent_arg:nn applies the kv string to the whole __spintent_geo_luaset_print_tl.

For a list of points, __spintent_geo_luaset_points_clist is split into __spintent_sprecta_pt_seq and walked to build __spintent_sprecta_refs_tl, the \$pt1,\$pt2,... reference list. The concept intent is _:nofix(refs) or recta:prefix(refs), same conditions as above, applied with a native \MathMLintent wrapping \overleftarrow{\@@luafun_inner_sep: first, luamml issue #26). The sequence is walked again, calling __spintent_mathmlarg_point:nnn per point — already protected against a subscripted point.

```

2927 \cs_new_protected:Nn \__spintent_sprecta_mathml:
2928 {
2929     \str_if_eq:VnTF \__spintent_geo_luaset_is_name_str { true }
2930     {
2931         \__spintent_invisible_sep:
2932         \bool_if:nTF
2933         {
2934             \bool_lazy_or_p:nn
2935             { \__spintent_sprecta_silent_cmd_bool }
2936             { ! \__spintent_sprecta_concept_bool }
2937         }
2938         {
2939             \tl_set:Nn \__spintent_sprecta_intent_arg_tl { :silent($pt) }
2940         }
2941         {
2942             \tl_set:Ne \__spintent_sprecta_intent_arg_tl
2943             {
2944                 \tl_if_empty:NF \__spintent_sprecta_prefix_tl
2945                 { \tl_use:N \__spintent_sprecta_prefix_tl - }
2946                 recta:prefix($pt)
2947             }
2948         }
2949         \bool_if:NTF \__spintent_sprecta_silent_cmd_bool
2950         {
2951             \tl_set:Nn \__spintent_sprecta_kv_tl { arg = "pt", intent = "-" }
2952         }
2953         {
2954             \str_if_eq:VnTF \__spintent_sprecta_mode_str { school }
2955             {
2956                 \tl_set:Ne \__spintent_sprecta_kv_tl
2957                 { arg = "pt", intent = "_ \__spintent_geo_luaset_intent_str -" }
2958             }
2959             {
2960                 \tl_set:Nn \__spintent_sprecta_kv_tl { arg = "pt" }
2961             }
2962         }
2963         \str_if_eq:VnTF \__spintent_geo_luaset_tipo_str { sub }
2964         {
2965             \MathMLintent { \__spintent_sprecta_intent_arg_tl }
2966             {
2967                 \__spintent_luafun_inner_sep:
2968                 \__spintent_luafun_wrap_mrow_intent_arg:nn
2969                 { } { \__spintent_sprecta_kv_tl }
2970                 { \__spintent_geo_luaset_letra_str }
2971                 \c_math_subscript_token

```

```

2972         { \MathMLintent { :silent } { \l__spintenc_geo_luaset_sub_str } }
2973     }
2974 }
2975 {
2976     \l__spintenc_luafun_wrap_mrow_intent_arg:nn
2977     { \l__spintenc_sprecta_intent_arg_tl }
2978     { \l__spintenc_sprecta_kv_tl }
2979     { \l__spintenc_geo_luaset_print_tl }
2980 }
2981 }
2982 {
2983     \seq_set_from_clist:NN \l__spintenc_sprecta_pt_seq \l__spintenc_geo_luaset_points_clist
2984     \tl_clear:N \l__spintenc_sprecta_refs_tl
2985     \int_zero:N \l__spintenc_sprecta_pt_idx_int
2986     \seq_map_inline:Nn \l__spintenc_sprecta_pt_seq
2987     {
2988         \int_incr:N \l__spintenc_sprecta_pt_idx_int
2989         \tl_if_empty:NF \l__spintenc_sprecta_refs_tl
2990         { \tl_put_right:Nn \l__spintenc_sprecta_refs_tl { , } }
2991         \tl_put_right:Ne \l__spintenc_sprecta_refs_tl { $ pt \int_use:N \l__spintenc_sprecta_pt_idx_int }
2992     }
2993     \bool_if:nTF
2994     {
2995         \bool_lazy_or_p:nn
2996         { \l__spintenc_sprecta_silent_cmd_bool }
2997         { ! \l__spintenc_sprecta_concept_bool }
2998     }
2999     {
3000         \tl_set:Ne \l__spintenc_sprecta_intent_arg_tl { _-:nofix( \l__spintenc_sprecta_refs_tl ) }
3001     }
3002     {
3003         \tl_set:Ne \l__spintenc_sprecta_intent_arg_tl
3004         {
3005             \tl_if_empty:NF \l__spintenc_sprecta_prefix_tl
3006             { \tl_use:N \l__spintenc_sprecta_prefix_tl - }
3007             recta:prefix( \l__spintenc_sprecta_refs_tl )
3008         }
3009     }
3010     \l__spintenc_invisible_sep:
3011     \MathMLintent { \l__spintenc_sprecta_intent_arg_tl }
3012     {
3013         \l__spintenc_luafun_inner_sep:
3014         \overleftrightharrow
3015         {
3016             \int_zero:N \l__spintenc_sprecta_pt_idx_int
3017             \seq_map_inline:Nn \l__spintenc_sprecta_pt_seq
3018             {
3019                 \int_incr:N \l__spintenc_sprecta_pt_idx_int
3020                 \l__spintenc_mathmlarg_point:nnn
3021                 { pt \int_use:N \l__spintenc_sprecta_pt_idx_int }
3022                 { sprecta }
3023                 { ##1 }
3024             }
3025         }
3026     }
3027 }
3028 }

```

(End of definition for \l__spintenc_sprecta_mathml:.)

\l__spintenc_sprecta_exec:nn

The function `\l__spintenc_sprecta_exec:nn` receives the optional *(keys)* passed in ‘#1’ and the *{(argument)}* passed in ‘#2’ delegating the rendering of the latter to `\l__spintenc_sprecta_print:n`.

```

3029 \cs_new_protected:Nn \l__spintenc_sprecta_exec:nn
3030 {
3031     \keys_set:nn { spintenc / sprecta } { #1 }
3032     \l__spintenc_sprecta_print:n { #2 }
3033 }

```

(End of definition for \l__spintenc_sprecta_exec:nn.)

\sprecta

The public command `\sprecta` enforces *math mode*, opens a local group, and delegates execution to `\l__spintenc_sprecta_exec:nn`.

```

3034 \NewDocumentCommand \sprecta { 0{} m }

```

```

3035 {
3036   \mode_if_math:TF
3037   {
3038     \group_begin:
3039     \__spintent_sprecta_exec:nn { #1 } { #2 }
3040     \group_end:
3041   }
3042   { \msg_error:nnn { spintent } { need-math-mode } { \sprecta } }
3043 }

```

(End of definition for `\sprecta`. This function is documented on page 18.)

11.36 The command `\sprayo`

The user command `\sprayo` provides a semantic interface for a ray. The key `read-sty` selects the verbalized term, `rayo` or `semirrecta`, both rendered identically with `\overrightarrow`.

11.36.1 Definition of variables for `\sprayo`

The variable `\__spintent_sprayo_mode_str` store the values set by the key `read-cmd`; the variable `\__spintent_sprayo_prefix_tl` store the value set by the key `prefix` and the variable `\__spintent_sprayo_read_sty_str` stores the value set by the key `read-sty`.

The variables defined here are assigned using `.choices:nn` or `.code:n` within `\keys_define:nn`.

```

3044 \str_new:N \__spintent_sprayo_mode_str
3045 \tl_new:N \__spintent_sprayo_prefix_tl
3046 \str_new:N \__spintent_sprayo_read_sty_str

```

(End of definition for `\__spintent_sprayo_mode_str`, `\__spintent_sprayo_prefix_tl`, and `\__spintent_sprayo_read_sty_str`.)

11.36.2 Definition of error messages for `\sprayo`

`sprayo-invalid-points` Raised when the argument is not a comma-separated pair of uppercase letters.

```

3047 \msg_new:nnnn { spintent } { sprayo-invalid-points }
3048 {
3049   Invalid~point~format~in~\token_to_str:N \sprayo:~'#1'~\msg_line_context:.
3050 }
3051 {
3052   See~the~documentation~of~\token_to_str:N \sprayo~for~the~accepted~point~formats.
3053 }

```

(End of definition for `sprayo-invalid-points`.)

11.36.3 Definition of keys for `\sprayo`

We define the `(keys)` `read-cmd`, `prefix`, `silent-cmd`, `concept` and `read-sty`.

```

3054 \keys_define:nn { spintent / sprayo }
3055 {
3056   read-cmd .choices:nn = { school , mathcat }
3057   {
3058     \int_case:nn { \l_keys_choice_int }
3059     {
3060       {1} { \str_set:Nn \__spintent_sprayo_mode_str { school } }
3061       {2} { \str_set:Nn \__spintent_sprayo_mode_str { mathcat } }
3062     }
3063   },
3064   read-cmd .initial:n = school,
3065   read-cmd .value_required:n = true,
3066   read-cmd / unknown .code:n =
3067     \msg_error:nnee { spintent } { unknown-choice }
3068     { read-cmd } { school,~mathcat } { \exp_not:n {#1} },
3069   prefix .code:n =
3070     { \__spintent_sanitize_affix:Nn \__spintent_sprayo_prefix_tl {#1} },
3071   prefix .initial:n = ,
3072   prefix .value_required:n = true,
3073   silent-cmd .bool_set:N = \__spintent_sprayo_silent_cmd_bool,
3074   silent-cmd .initial:n = false,
3075   silent-cmd .value_required:n = true,
3076   concept .bool_set:N = \__spintent_sprayo_concept_bool,
3077   concept .initial:n = true,
3078   concept .value_required:n = true,
3079   read-sty .choices:nn = { rayo , semirrecta }
3080   {
3081     \int_case:nn { \l_keys_choice_int }
3082     {

```

```

3083         {1} { \str_set:Nn \l__spintent_sprayo_read_sty_str { rayo          } }
3084         {2} { \str_set:Nn \l__spintent_sprayo_read_sty_str { semirrecta    } }
3085     }
3086 },
3087 read-sty          .initial:n = rayo,
3088 read-sty          .value_required:n = true,
3089 read-sty / unknown .code:n =
3090     \msg_error:nneee { spintent } { unknown-choice }
3091     { read-sty } { rayo,~semirrecta } { \exp_not:n {#1} },
3092 unknown          .code:n =
3093     {
3094         \str_set:Nn \l__spintent_command_name_str { sprayo }
3095         \l__spintent_unknown_keys_cmd:n {#1}
3096     },
3097 }

```

(End of definition for `read-cmd` and others.)

11.36.4 Internal functions for `\sprayo`

`\l__spintent_sprayo_pt_seq` Auxiliary variables used by `\l__spintent_sprayo_mathml:` to split `\l__spintent_geo_luaset_points_clist` and build the `$pts1, $pts2, ...` reference list.

```

\l__spintent_sprayo_refs_tl
\l__spintent_sprayo_intent_arg_tl
\l__spintent_sprayo_pt_idx_int
3098 \seq_new:N \l__spintent_sprayo_pt_seq
3099 \tl_new:N \l__spintent_sprayo_refs_tl
3100 \tl_new:N \l__spintent_sprayo_intent_arg_tl
3101 \int_new:N \l__spintent_sprayo_pt_idx_int

```

(End of definition for `\l__spintent_sprayo_pt_seq` and others.)

`\l__spintent_sprayo_print:n` The internal function `\l__spintent_sprayo_print:n` process the `{(argument)}` passed in ‘#1’. It calls `\l__spintent_luafun_geo_parse_and_set:n` to process the `{(argument)}`, returning an “error” if the input is invalid, then calls `\l__spintent_sprayo_mathml:`. Unlike `\sprecta`, `\sprayo` has no proper-name argument: it always takes a list of points, so no `intent` is built here.

```

3102 \cs_new_protected:Nn \l__spintent_sprayo_print:n
3103 {
3104     \l__spintent_luafun_geo_parse_and_set:n { \exp_not:n {#1} }
3105     \str_if_eq:VnT \l__spintent_geo_luaset_error_str { true }
3106     {
3107         \msg_error:nne { spintent } { sprayo-invalid-points } { \exp_not:n {#1} }
3108     }
3109     \l__spintent_sprayo_mathml:
3110 }

```

(End of definition for `\l__spintent_sprayo_print:n`.)

`\l__spintent_sprayo_mathml:` The function `\l__spintent_sprayo_mathml:` splits `\l__spintent_geo_luaset_points_clist` (set by Lua, one raw point per element) into `\l__spintent_sprayo_pt_seq` and walks it once to build `\l__spintent_sprayo_refs_tl`, the comma-separated `$pts1, $pts2, ...` reference list, naming each point by position.

The concept `intent` is `_:-nofix(refs)` when `silent-cmd` is `true` or `concept` is `false`; otherwise it is `\l__spintent_sprayo_read_sty_str:prefix(refs)` — the concept word itself (`rayo` or `semirrecta`) comes from the `read-sty` key, not a literal, since `\sprayo` verbalizes under two names — prefixed with `prefix` when given. It is applied with a native `\MathMLintent` wrapping `\overrightarrow`, preceded by `\l__spintent_luafun_inner_sep:` (a second sibling so the sole `<mrow>` does not collapse into `<math>`, `luamml` issue #26). The sequence is walked a second time, calling `\l__spintent_mathmlarg_point:nnn` once per point with its `ptsn` reference name and `silent-cmd/read-cmd` looked up under `sprayo:` it alone decides arg/literal `intent` per point, so concept plays no role at that level.

```

3111 \cs_new_protected:Nn \l__spintent_sprayo_mathml:
3112 {
3113     \seq_set_from_clist:NN \l__spintent_sprayo_pt_seq \l__spintent_geo_luaset_points_clist
3114     \tl_clear:N \l__spintent_sprayo_refs_tl
3115     \int_zero:N \l__spintent_sprayo_pt_idx_int
3116     \seq_map_inline:Nn \l__spintent_sprayo_pt_seq
3117     {
3118         \int_incr:N \l__spintent_sprayo_pt_idx_int
3119         \tl_if_empty:NF \l__spintent_sprayo_refs_tl
3120         { \tl_put_right:Nn \l__spintent_sprayo_refs_tl { , } }
3121         \tl_put_right:Ne \l__spintent_sprayo_refs_tl { $ pts \int_use:N \l__spintent_sprayo_pt_idx_int }
3122     }
3123     \bool_if:nTF
3124     {

```

```

3125     \bool_lazy_or_p:nn
3126     { \l__spintent_sprayo_silent_cmd_bool }
3127     { ! \l__spintent_sprayo_concept_bool }
3128   }
3129   {
3130     \tl_set:Nx \l__spintent_sprayo_intent_arg_tl { _-:nofix( \l__spintent_sprayo_refs_tl ) }
3131   }
3132   {
3133     \tl_set:Nx \l__spintent_sprayo_intent_arg_tl
3134     {
3135       \tl_if_empty:NF \l__spintent_sprayo_prefix_tl
3136       { \tl_use:N \l__spintent_sprayo_prefix_tl - }
3137       \l__spintent_sprayo_read_sty_str :prefix( \l__spintent_sprayo_refs_tl )
3138     }
3139   }
3140   \__spintent_invisible_sep:
3141   \MathMLintent { \l__spintent_sprayo_intent_arg_tl }
3142   {
3143     \__spintent_luafun_inner_sep:
3144     \overrightarrow
3145     {
3146       \int_zero:N \l__spintent_sprayo_pt_idx_int
3147       \seq_map_inline:Nn \l__spintent_sprayo_pt_seq
3148       {
3149         \int_incr:N \l__spintent_sprayo_pt_idx_int
3150         \__spintent_mathmlarg_point:nnn
3151         { pts \int_use:N \l__spintent_sprayo_pt_idx_int }
3152         { sprayo }
3153         { ##1 }
3154       }
3155     }
3156   }
3157 }

```

(End of definition for `\__spintent_sprayo_mathml:`.)

`\__spintent_sprayo_exec:nn` The function `\__spintent_sprayo_exec:nn` receives the optional $\langle keys \rangle$ passed in ‘#1’ and the $\{\langle argument \rangle\}$ passed in ‘#2’ delegating the rendering of the latter to `\__spintent_sprayo_print:n`.

```

3158 \cs_new_protected:Nn \__spintent_sprayo_exec:nn
3159 {
3160   \keys_set:nn { spintent / sprayo } { #1 }
3161   \__spintent_sprayo_print:n { #2 }
3162 }

```

(End of definition for `\__spintent_sprayo_exec:nn`.)

`\sprayo` The public command `\sprayo` enforces *math mode*, opens a local group, and delegates execution to `\__spintent_sprayo_exec:nn`.

```

3163 \NewDocumentCommand \sprayo { O{} m }
3164 {
3165   \mode_if_math:TF
3166   {
3167     \group_begin:
3168     \__spintent_sprayo_exec:nn { #1 } { #2 }
3169     \group_end:
3170   }
3171   { \msg_error:nnn { spintent } { need-math-mode } { \sprayo } }
3172 }

```

(End of definition for `\sprayo`. This function is documented on page 18.)

11.37 The commands `\spside` and `\spmside`

The user commands `\spside` and `\spmside` provide a semantic interface for a side, segment or trace determined by two points. The key `read-sty` selects the verbalized term — `lado`, `segmento`, or `trazo`, the latter used in straightedge-and-compass constructions — and the key `read-arg` overrides that term entirely with a free-form string. Additionally, the command `\spmside` provides the key `print-m`, controlling whether `\operatorname{m}` is typeset before the argument.

11.37.1 Definition of variables for \spside and \spmside

Each pair of variables is declared once for both `\spside` and `\spmside` via `\clist_map_inline:nn`. The variables `\__spintent_spside_mode_str` and `\__spintent_spside_mode_str` store the values set by the key `read-cmd`; the variables `\__spintent_spside_prefix_tl` and `\__spintent_spmside_prefix_tl` store the values set by the key `prefix`.

The variables `\__spintent_spside_read_sty_str` and `\__spintent_spmside_read_sty_str` stores the value set by the key `read-sty`.

The variables `\__spintent_spside_read_arg_tl` and `\__spintent_spmside_read_arg_tl` stores the value set by the key `read-arg`.

- The variables are defined here as they are assigned using `.choices:nn` or `.code:n` rather than a direct property within `\keys_define:nn`.

```

3173 \clist_map_inline:nn { side , mside }
3174 {
3175     \str_new:c { \__spintent_sp #1 _mode_str      }
3176     \tl_new:c { \__spintent_sp #1 _prefix_tl     }
3177     \str_new:c { \__spintent_sp #1 _read_sty_str  }
3178     \tl_new:c { \__spintent_sp #1 _read_arg_tl   }
3179 }

```

(End of definition for `\__spintent_spside_mode_str` and others.)

11.37.2 Definition of error messages for \spside and \spmside

We define an error message for the commands `\spside` and `\spmside`. The “error” is triggered if the user includes a invalid “point” in the `{\argument}` passed in ‘#1’ to the command.

```

3180 \clist_map_inline:nn { side , mside }
3181 {
3182     \msg_new:nnnn { spintent } { sp #1 -invalid-points }
3183     {
3184         Invalid~point~format~in~##1:~'##2'~\msg_line_context:.
3185     }
3186     {
3187         See~the~documentation~of~##1~for~the~accepted~point~formats.
3188     }
3189 }

```

(End of definition for `spside-invalid-points` and `spmside-invalid-points`.)

11.37.3 Definition of keys for \spside and \spmside

We define the shared `\keys` `read-cmd`, `prefix`, `silent-cmd`, `concept`, `read-sty`, `read-arg` and `print-m`.

```

read-cmd  \clist_map_inline:nn { side , mside }
prefix    {
silent-cmd 3191 {
concept    3192 \keys_define:nn { spintent / sp #1 }
read-sty   3193 {
read-arg   3194     read-cmd          .choices:nn = { school , mathcat }
print-m    3195     {
unknown    3196         \int_case:nn { \l_keys_choice_int }
3197         {
3198             {1} { \str_set:cn { \__spintent_sp #1 _mode_str } { school } }
3199             {2} { \str_set:cn { \__spintent_sp #1 _mode_str } { mathcat } }
3200         }
3201     },
3202     read-cmd          .initial:n = school,
3203     read-cmd          .value_required:n = true,
3204     read-cmd / unknown .code:n =
3205         \msg_error:nneee { spintent } { unknown-choice }
3206         { read-cmd } { school,~mathcat } { \exp_not:n {##1} },
3207     prefix            .code:n =
3208         { \__spintent_sanitiz Affix:cn { \__spintent_sp #1 _prefix_tl } {##1} },
3209     prefix            .initial:n = ,
3210     prefix            .value_required:n = true,
3211     silent-cmd        .bool_set:c = { \__spintent_sp #1 _silent_cmd_bool },
3212     silent-cmd        .initial:n = false,
3213     silent-cmd        .value_required:n = true,
3214     concept           .bool_set:c = { \__spintent_sp #1 _concept_bool },
3215     concept           .initial:n = true,
3216     concept           .value_required:n = true,
3217     read-sty          .choices:nn = { lado , segmento , trazo }
3218     {
3219         \int_case:nn { \l_keys_choice_int }

```

```

3220         {
3221             {1} { \str_set:cn { l__spintent_sp #1 _read_sty_str } { lado      } }
3222             {2} { \str_set:cn { l__spintent_sp #1 _read_sty_str } { segmento  } }
3223             {3} { \str_set:cn { l__spintent_sp #1 _read_sty_str } { trazo     } }
3224         }
3225     },
3226     read-sty          .initial:n = lado,
3227     read-sty          .value_required:n = true,
3228     read-sty / unknown .code:n =
3229         \msg_error:nneee { spintent } { unknown-choice }
3230         { read-sty } { lado,~segmento,~trazo } { \exp_not:n {##1} },
3231     read-arg          .code:n =
3232         {
3233             \__spintent_sanitizate_affix:cn { l__spintent_sp #1 _read_arg_tl } {##1}
3234         },
3235     read-arg          .initial:n = ,
3236     read-arg          .value_required:n = true,
3237     print-m           .bool_set:c = { l__spintent_sp #1 _print_m_bool },
3238     print-m           .initial:n = false,
3239     print-m           .value_required:n = true,
3240     unknown           .code:n =
3241         {
3242             \str_set:Nn \l__spintent_command_name_str { sp #1 }
3243             \__spintent_unknown_keys_cmd:n {##1}
3244         },
3245     }
3246 }

```

• The keys `print-m` and `concept` are defined for both commands for simplicity, but has no effect on `\spside`.

(End of definition for `read-cmd` and others.)

```

\l__spintent_spside_intent_tl \l__spintent_spside_pt_seq \l__spintent_spside_refs_tl
\l__spintent_spside_intent_arg_tl \l__spintent_spside_pt_idx_int
3247 \tl_new:N \l__spintent_spside_intent_tl
3248 \seq_new:N \l__spintent_spside_pt_seq
3249 \tl_new:N \l__spintent_spside_refs_tl
3250 \tl_new:N \l__spintent_spside_intent_arg_tl
3251 \int_new:N \l__spintent_spside_pt_idx_int

```

(End of definition for `\l__spintent_spside_intent_tl` and others.)

```
\__spintent_spside_process:nn
```

The internal function `\__spintent_spside_process:nn` receives the short name of the command (side or mside) in ‘#1’ and the $\langle argument \rangle$ in ‘#2’. It calls `\__spintent_luafun_geo_parse_and_set:n` to process ‘#2’, returning an “error” if invalid, then builds `\l__spintent_spside_intent_tl`. When `read-arg` is empty, it is set from `read-sty`, prefixed with ‘medida-del-’ for `\spmside`. When `read-arg` is given, it is used as is, and ‘medida-del-’ is prepended only if `concept` is `true`: with `concept=false`, `read-arg` is the verbatim escape hatch for a full user-written phrase (e.g. `read-arg={medida de la hipotenusa}`), gender and article left to the user. No `intent` is built here: it needs the reference list, which `\__spintent_spside_math` builds after splitting the points.

```

3252 \cs_new_protected:Nn \__spintent_spside_process:nn
3253 {
3254     \__spintent_luafun_geo_parse_and_set:n { \exp_not:n {#2} }
3255     \str_if_eq:VnT \l__spintent_geo_luaseta_error_str { true }
3256     {
3257         \msg_error:nnee { spintent } { sp #1 -invalid-points }
3258         { \c_backslash_str sp #1 } { \exp_not:n {#2} }
3259     }
3260     \tl_if_empty:cTF { l__spintent_sp #1 _read_arg_tl }
3261     {
3262         \tl_set:Ne \l__spintent_spside_intent_tl { \str_use:c { l__spintent_sp #1 _read_sty_str } }
3263         \str_if_eq:eeT {#1} { mside }
3264         {
3265             \tl_put_left:Nn \l__spintent_spside_intent_tl { medida-del- }
3266         }
3267     }
3268     {
3269         \tl_set:Ne \l__spintent_spside_intent_tl { \tl_use:c { l__spintent_sp #1 _read_arg_tl } }
3270         \bool_if:cT { l__spintent_sp #1 _concept_bool }
3271         {
3272             \str_if_eq:eeT {#1} { mside }

```

```

3273         {
3274             \tl_put_left:Nn \l__spintent_spside_intent_tl { medida-del- }
3275         }
3276     }
3277 }
3278 \__spintent_spside_mathml:n { #1 }
3279 }

```

(End of definition for `\__spintent_spside_process:nn`.)

`\__spintent_spside_mathml:n` The function `\__spintent_spside_mathml:n` receives the short command name in ‘#1’. It splits `\l__spintent_geo_luaset_points_clist` into `\l__spintent_spside_pt_seq` and walks it once to build `\l__spintent_spside_refs_tl`, the comma-separated `$pts1,$pts2,...` reference list, naming each point by position.

The concept `intent` is `_(refs)` when `silent-cmd` is `true`; otherwise, if `read-arg` is empty, it is `_(refs)` when `concept` is `false` or `\l__spintent_spside_intent_tl:prefix(refs)` when `true`; if `read-arg` is given, it is always `\l__spintent_spside_intent_tl:prefix(refs)` — `concept` never silences a user-given `read-arg` (see `\__spintent_spside_process:nn`). The `:prefix(...)` form is prefixed with `prefix` when given. It is applied with a native `\MathMLintent`, preceded by `\__spintent_luafun_inner_sep:` (a second sibling so the sole `<mrow>` does not collapse into `<math>`, `luamml` issue #26).

Inside, for `#1=side` the points are always wrapped in `\overline`; for `#1=mside`, when `print-m` is `true` a silent `\operatorname{m}` precedes the `\overline`-wrapped points; when `false`, the points are typeset bare, with no `\overline` at all — the recursive lookup in the shared `mathml_filter` callback finds each point either way, whether nested inside `\overline` or sitting directly in the `\MathMLintent` group. In every case the sequence is walked a second time, calling `\__spintent_mathmlarg_point:nnn` once per point with its `ptsn` reference name and `silent-cmd/read-cmd` looked up under `sp#1`: it alone decides `arg/literal intent` per point, so `concept` plays no role at that level.

```

3280 \cs_new_protected:Nn \__spintent_spside_mathml:n
3281 {
3282     \seq_set_from_clist:NN \l__spintent_spside_pt_seq \l__spintent_geo_luaset_points_clist
3283     \tl_clear:N \l__spintent_spside_refs_tl
3284     \int_zero:N \l__spintent_spside_pt_idx_int
3285     \seq_map_inline:Nn \l__spintent_spside_pt_seq
3286     {
3287         \int_incr:N \l__spintent_spside_pt_idx_int
3288         \tl_if_empty:NF \l__spintent_spside_refs_tl
3289         { \tl_put_right:Nn \l__spintent_spside_refs_tl { , } }
3290         \tl_put_right:Ne \l__spintent_spside_refs_tl { $ pts \int_use:N \l__spintent_spside_pt_idx_int
3291     }
3292     \bool_if:cTF { l__spintent_sp #1 _silent_cmd_bool }
3293     {
3294         \tl_set:Ne \l__spintent_spside_intent_arg_tl { _( \l__spintent_spside_refs_tl ) }
3295     }
3296     {
3297         \tl_if_empty:cTF { l__spintent_sp #1 _read_arg_tl }
3298         {
3299             \bool_if:cTF { l__spintent_sp #1 _concept_bool }
3300             {
3301                 \tl_set:Ne \l__spintent_spside_intent_arg_tl
3302                 {
3303                     \tl_if_empty:cF { l__spintent_sp #1 _prefix_tl }
3304                     { \tl_use:c { l__spintent_sp #1 _prefix_tl } - }
3305                     \l__spintent_spside_intent_tl :prefix( \l__spintent_spside_refs_tl )
3306                 }
3307             }
3308             {
3309                 \tl_set:Ne \l__spintent_spside_intent_arg_tl { _( \l__spintent_spside_refs_tl ) }
3310             }
3311         }
3312         {
3313             \tl_set:Ne \l__spintent_spside_intent_arg_tl
3314             {
3315                 \tl_if_empty:cF { l__spintent_sp #1 _prefix_tl }
3316                 { \tl_use:c { l__spintent_sp #1 _prefix_tl } - }
3317                 \l__spintent_spside_intent_tl :prefix( \l__spintent_spside_refs_tl )
3318             }
3319         }
3320     }
3321     \__spintent_invisible_sep: % (luamml issues #26)
3322     \MathMLintent { \l__spintent_spside_intent_arg_tl }

```

```

3323 {
3324   \__spintent_luafun_inner_sep:
3325   \str_if_eq:eeTF {#1} { side }
3326   {
3327     \overline { \__spintent_spside_points_loop:n {#1} }
3328   }
3329   {
3330     \bool_if:cTF { l__spintent_sp #1 _print_m_bool }
3331     {
3332       \__spintent_luafun_wrap_mrow_intent_arg:nn
3333       { } { intent = ":silent" }
3334       { \operatorname { m } }
3335       \overline { \__spintent_spside_points_loop:n {#1} }
3336     }
3337     {
3338       \__spintent_spside_points_loop:n {#1}
3339     }
3340   }
3341 }
3342 }

```

(End of definition for `\__spintent_spside_mathml:n`.)

`\__spintent_spside_points_loop:n`

Walks `\__spintent_spside_pt_seq` a second time, calling `\__spintent_mathmlarg_point:nnn` once per point. Factored out of `\__spintent_spside_mathml:n` since it is needed identically in three places there (side, mside with and without `print-m`); it takes the short command name in ‘#1’ again since a separate macro does not inherit its caller’s own #1.

```

3343 \cs_new_protected:Nn \__spintent_spside_points_loop:n
3344 {
3345   \int_zero:N \__spintent_spside_pt_idx_int
3346   \seq_map_inline:Nn \__spintent_spside_pt_seq
3347   {
3348     \int_incr:N \__spintent_spside_pt_idx_int
3349     \__spintent_mathmlarg_point:nnn
3350     { pts \int_use:N \__spintent_spside_pt_idx_int }
3351     { sp #1 }
3352     { ##1 }
3353   }
3354 }

```

(End of definition for `\__spintent_spside_points_loop:n`.)

`\__spintent_spside_exec:nnn`

The function `\__spintent_spside_exec:nnn` receives the *short name* of the command passed in ‘#1’, the optional *keys* passed in ‘#2’ and the *{argument}* passed in ‘#3’, delegating the rendering to `\__spintent_spside_process:nn`.

```

3355 \cs_new_protected:Nn \__spintent_spside_exec:nnn
3356 {
3357   \keys_set:nn { spintent / sp #1 } { #2 }
3358   \__spintent_spside_process:nn { #1 } { #3 }
3359 }

```

(End of definition for `\__spintent_spside_exec:nnn`.)

`\spside`
`\spmside`

Both public commands `\spside` and `\spmside` enforces *math mode*, opens a local group, and delegates execution to `\__spintent_spside_exec:nnn`.

```

3360 \NewDocumentCommand \spside { O{} m }
3361 {
3362   \mode_if_math:TF
3363   {
3364     \group_begin:
3365     \__spintent_spside_exec:nnn { side } { #1 } { #2 }
3366     \group_end:
3367   }
3368   { \msg_error:nnn { spintent } { need-math-mode } { \spside } }
3369 }
3370 \NewDocumentCommand \spmside { O{} m }
3371 {
3372   \mode_if_math:TF
3373   {
3374     \group_begin:
3375     \__spintent_spside_exec:nnn { mside } { #1 } { #2 }

```

```

3376     \group_end:
3377   }
3378   { \msg_error:nnn { spintent } { need-math-mode } { \spmside } }
3379 }

```

(End of definition for `\spside` and `\spmside`. These functions are documented on page 19.)

11.38 The commands `\spangle` and `\spmangle`

The user commands `\spangle` and `\spmangle`, provide a semantic interface for angles, following the same generic pattern as `\spside`/`\spmside`. The key `print-m` chooses between the `\angle`/`\rightanglesqr` pair, typeset together with an explicit `\operatorname{m}`, and the `\measuredangle`/`\measuredrightangle` pair, which already conveys the notion of measure on its own; the key `recto` independently chooses the right-angle variant of whichever pair is active.

11.38.1 Definition of variables for `\spangle` and `\spmangle`

```

\__spintent_spangle_mode_str
\__spintent_spmangle_mode_str
\__spintent_spangle_prefix_tl
\__spintent_spmangle_prefix_tl

```

Each pair of variables is declared once for both `\spangle` and `\spmangle` via `\clist_map_inline:nn`. The variables `\__spintent_spangle_mode_str` and `\__spintent_spmangle_mode_str` store the values set by the key `read-cmd`; the variables `\__spintent_spangle_prefix_tl` and `\__spintent_spmangle_prefix_tl` store the values set by the key `prefix`.

• The variables defined here are assigned using `.choices:nn` or `.code:n` within `\keys_define:nn`.

```

3380 \clist_map_inline:nn { angle , mangle }
3381   {
3382     \str_new:c { \__spintent_sp #1 _mode_str }
3383     \tl_new:c { \__spintent_sp #1 _prefix_tl }
3384   }

```

(End of definition for `\__spintent_spangle_mode_str` and others.)

11.38.2 Definition of error messages for `\spangle` and `\spmangle`

```

spangle-invalid-arg
spmangle-invalid-arg

```

We define an “error” message for the commands `\spangle` and `\spmangle`. The “error” is triggered if the user includes a invalid `{\langle argument \rangle}` passed in ‘#1’ to the command.

```

3385 \clist_map_inline:nn { angle , mangle }
3386   {
3387     \msg_new:nnnn { spintent } { sp #1 -invalid-arg }
3388     {
3389       Invalid~format~in~##1:~'##2'~\msg_line_context:.
3390     }
3391     {
3392       See~the~documentation~of~##1~for~the~accepted~argument~forms.
3393     }
3394   }

```

(End of definition for `spangle-invalid-arg` and `spmangle-invalid-arg`.)

11.38.3 Definition of keys for `\spangle` and `\spmangle`

```

read-cmd  We define the shared \keys read-cmd, prefix, recto, print-m, silent-cmd and concept,
prefix
recto
print-m
silent-cmd
concept
unknown

```

```

3395 \clist_map_inline:nn { angle , mangle }
3396   {
3397     \keys_define:nn { spintent / sp #1 }
3398     {
3399       read-cmd .choices:nn = { school , mathcat }
3400       {
3401         \int_case:nn { \l_keys_choice_int }
3402           {
3403             {1} { \str_set:cn { \__spintent_sp #1 _mode_str } { school } }
3404             {2} { \str_set:cn { \__spintent_sp #1 _mode_str } { mathcat } }
3405           }
3406       },
3407       read-cmd .initial:n = school,
3408       read-cmd .value_required:n = true,
3409       read-cmd / unknown .code:n =
3410         \msg_error:nneee { spintent } { unknown-choice }
3411         { read-cmd } { school,~mathcat } { \exp_not:n {##1} },
3412       prefix .code:n =
3413         { \__spintent_sanitizize_affix:cn { \__spintent_sp #1 _prefix_tl } {##1} },
3414       prefix .initial:n = ,
3415       prefix .value_required:n = true,
3416       recto .bool_set:c = { \__spintent_sp #1 _recto_bool },
3417       recto .initial:n = false,
3418       recto .value_required:n = true,

```

```

3419     print-m           .bool_set:c = { l__spintent_sp #1 _print_m_bool },
3420     print-m           .initial:n  = false,
3421     print-m           .value_required:n = true,
3422     silent-cmd        .bool_set:c = { l__spintent_sp #1 _silent_cmd_bool },
3423     silent-cmd        .initial:n  = false,
3424     silent-cmd        .value_required:n = true,
3425     concept           .bool_set:c = { l__spintent_sp #1 _concept_bool },
3426     concept           .initial:n  = true,
3427     concept           .value_required:n = true,
3428     unknown           .code:n =
3429     {
3430         \str_set:Nn \l__spintent_command_name_str { sp #1 }
3431         \__spintent_unknown_keys_cmd:n {##1}
3432     },
3433 }
3434 }

```

• The keys `print-m` and `concept` are defined for both commands for simplicity, but has no effect on `\spangle`.

(End of definition for `read-cmd` and others.)

11.38.4 Internal functions for `\spangle` and `\spmangle`

`\__spintent_spangle_sym:n`

The internal function `\__spintent_spangle_sym:n` dispatches on `#1`, `print-m` and `recto` to select one of four symbols: `\angle/\rightanglesqr` when `print-m` is true; `\measuredangle/\measuredrightangle` otherwise. When `#1` is `angle`, only `recto` applies, choosing between `\angle` and `\rightangle`.

```

3435 \cs_new_protected:Nn \__spintent_spangle_sym:n
3436 {
3437     \str_if_eq:eeTF {#1} { mangle }
3438     {
3439         \bool_if:cTF { l__spintent_sp #1 _print_m_bool }
3440         {
3441             \bool_if:cTF { l__spintent_sp #1 _recto_bool }
3442             { \__spintent_right_angle_sqr: } { \angle }
3443         }
3444         {
3445             \bool_if:cTF { l__spintent_sp #1 _recto_bool }
3446             { \measuredrightangle } { \measuredangle }
3447         }
3448     }
3449     {
3450         \bool_if:cTF { l__spintent_sp #1 _recto_bool }
3451         { \__spintent_right_angle_sqr: } { \angle }
3452     }
3453 }

```

(End of definition for `\__spintent_spangle_sym:n`.)

`\l__spintent_spangle_intent_tl`
`\l__spintent_spangle_pt_seq`
`\l__spintent_spangle_refs_tl`
`\l__spintent_spangle_intent_arg_tl`
`\l__spintent_spangle_pt_idx_int`
`\l__spintent_spangle_print_m_now_bool`

`\l__spintent_spangle_intent_tl` holds the concept word (ángulo or medida-del-ángulo, ‘-recto’-suffixed when `recto` is true). The rest are scratch variables shared by both commands to split `\l__spintent_geo_lua` and build the reference list – used only in the tres-puntos and un-punto cases (see `\__spintent_spangle_mathml:`).

```

3454 \tl_new:N \l__spintent_spangle_intent_tl
3455 \seq_new:N \l__spintent_spangle_pt_seq
3456 \tl_new:N \l__spintent_spangle_refs_tl
3457 \tl_new:N \l__spintent_spangle_intent_arg_tl
3458 \int_new:N \l__spintent_spangle_pt_idx_int
3459 \str_new:N \l__spintent_spangle_kv_tl
3460 \bool_new:N \l__spintent_spangle_print_m_now_bool

```

(End of definition for `\l__spintent_spangle_intent_tl` and others.)

`\__spintent_spangle_process:nn`

The internal function `\__spintent_spangle_process:nn` receives the short name of the command (`angle` or `mangle`) in ‘`#1`’ and the $\langle argument \rangle$ in ‘`#2`’. It calls `\__spintent_luafun_geo_angulo_parse_and_set:n` to process ‘`#2`’, returning an “error” if invalid, then sets `\l__spintent_spangle_intent_tl` to ángulo (or medida-del-ángulo for `\spmangle`), suffixed with ‘-recto’ when `recto` is true. No intent is built here: it depends on `\l__spintent_geo_luaaset_angulo_case_str` (tres-puntos, un-punto or nombre), which `\__spintent_spangle_mathml:n` branches on.

```

3461 \cs_new_protected:Nn \__spintent_spangle_process:nn
3462 {
3463     \__spintent_luafun_geo_angulo_parse_and_set:n { \exp_not:n {#2} }
3464     \str_if_eq:VnT \l__spintent_geo_luaaset_error_str { true }
3465     {
3466         \msg_error:nnee { spintent } { sp #1 -invalid-arg }

```

```

3467         { \c_backslash_str sp #1 } { \exp_not:n {#2} }
3468     }
3469     \str_if_eq:eeTF {#1} { mangle }
3470     {
3471         \tl_set:Nn \l__spintent_spangle_intent_tl { medida-del-ángulo }
3472     }
3473     {
3474         \tl_set:Nn \l__spintent_spangle_intent_tl { ángulo }
3475     }
3476     \bool_if:cT { l__spintent_sp #1 _recto_bool }
3477     {
3478         \tl_put_right:Nn \l__spintent_spangle_intent_tl { -recto }
3479     }
3480     \__spintent_spangle_mathml:n {#1}
3481 }

```

(End of definition for `\__spintent_spangle_process:nn`.)

`\__spintent_spangle_mathml:n` For tres-puntos/un-punto, a single native `\MathMLintent` wraps the symbol and the points together, with `\l__spintent_spangle_intent_tl:prefix(refs)` — the same shape as `\__spintent_spside_mathml:n`. The earlier split into two sibling `\MathMLintent` calls worked around a MathCAT bug with several explicit `$`-references in `:prefix(...)` that only affects the demo build; the stable NVDA/updated Acrobat Reader combination reads this shape correctly, so the split is no longer needed and both commands now share the same structure.

For `\spmangle` with `print-m true`, a silent `\operatorname{m}` precedes `\__spintent_spangle_sym:n` inside the same `\MathMLintent`, exactly as `\__spintent_spside_mathml:n` does for its own `m`. `nombre` is unchanged (see below): it never references more than one thing, so it was never affected by the bug this simplifies away from.

```

3482 \cs_new_protected:Nn \__spintent_spangle_mathml:n
3483 {
3484     \__spintent_invisible_sep: % (luamml issues #26)
3485     \str_if_eq:VnTF \l__spintent_geo_luaset_angulo_case_str { nombre }
3486     {
3487         \bool_if:cTF { l__spintent_sp #1 _silent_cmd_bool }
3488         {
3489             \tl_set:Nn \l__spintent_spangle_intent_arg_tl { _- }
3490         }
3491         {
3492             \bool_if:cTF { l__spintent_sp #1 _concept_bool }
3493             {
3494                 \tl_set:Nn \l__spintent_spangle_intent_arg_tl
3495                 {
3496                     \tl_if_empty:cF { l__spintent_sp #1 _prefix_tl }
3497                     { \tl_use:c { l__spintent_sp #1 _prefix_tl } - }
3498                     \l__spintent_spangle_intent_tl :prefix
3499                 }
3500             }
3501             {
3502                 \tl_set:Nn \l__spintent_spangle_intent_arg_tl { _- }
3503             }
3504         }
3505         \tl_set:Nn \l__spintent_spangle_kv_tl
3506         { intent = "\l__spintent_spangle_intent_arg_tl" }
3507         \__spintent_luafun_wrap_mrow_intent_arg:nn
3508         { } { \l__spintent_spangle_kv_tl }
3509         { \__spintent_spangle_sym:n {#1} }
3510         \bool_if:cTF { l__spintent_sp #1 _silent_cmd_bool }
3511         {
3512             \__spintent_luafun_wrap_mrow_intent_arg:nn { } { intent = "_-" }
3513             { \l__spintent_geo_luaset_print_tl }
3514         }
3515         {
3516             \str_if_eq:VnTF \l__spintent_geo_luaset_nombre_es_num_str { true }
3517             {
3518                 \tl_set:Nn \l__spintent_spangle_kv_tl
3519                 { intent = "_ \l__spintent_geo_luaset_intent_str -" }
3520                 \__spintent_luafun_wrap_mrow_intent_arg:nn
3521                 { } { \l__spintent_spangle_kv_tl }
3522                 { \l__spintent_geo_luaset_print_tl }
3523             }
3524             { \l__spintent_geo_luaset_print_tl }

```

```

3525     }
3526   }
3527   {
3528     \seq_set_from_clist:Nn \l__spintent_spangle_pt_seq \l__spintent_geo_luaset_points_clist
3529     \tl_clear:N \l__spintent_spangle_refs_tl
3530     \int_zero:N \l__spintent_spangle_pt_idx_int
3531     \seq_map_inline:Nn \l__spintent_spangle_pt_seq
3532       {
3533         \int_incr:N \l__spintent_spangle_pt_idx_int
3534         \tl_if_empty:NF \l__spintent_spangle_refs_tl
3535           { \tl_put_right:Nn \l__spintent_spangle_refs_tl { , } }
3536         \tl_put_right:Ne \l__spintent_spangle_refs_tl { $ pt \int_use:N \l__spintent_spangle_
3537       }
3538     \bool_if:cTF { l__spintent_sp #1 _silent_cmd_bool }
3539     {
3540       \tl_set:Nn \l__spintent_spangle_intent_arg_tl { _- }
3541     }
3542     {
3543       \bool_if:cTF { l__spintent_sp #1 _concept_bool }
3544       {
3545         \tl_set:Ne \l__spintent_spangle_intent_arg_tl
3546           {
3547             \tl_if_empty:cF { l__spintent_sp #1 _prefix_tl }
3548             { \tl_use:c { l__spintent_sp #1 _prefix_tl } - }
3549             \l__spintent_spangle_intent_tl :prefix( \l__spintent_spangle_refs_tl )
3550           }
3551       }
3552       {
3553         \tl_set:Nn \l__spintent_spangle_intent_arg_tl { _- }
3554       }
3555     }
3556     \bool_set_false:N \l__spintent_spangle_print_m_now_bool
3557     \str_if_eq:eeT {#1} { mangle }
3558     {
3559       \bool_if:cT { l__spintent_sp #1 _print_m_bool }
3560       { \bool_set_true:N \l__spintent_spangle_print_m_now_bool }
3561     }
3562     \MathMLintent { \l__spintent_spangle_intent_arg_tl }
3563     {
3564       \__spintent_luafun_inner_sep:
3565       \bool_if:NT \l__spintent_spangle_print_m_now_bool
3566       {
3567         \__spintent_luafun_wrap_mrow_intent_arg:nn
3568           { } { intent = ":silent" }
3569         { \operatorname { m } }
3570       }
3571       \__spintent_luafun_wrap_mrow_intent_arg:nn
3572         { } { intent = ":silent" }
3573       { \__spintent_spangle_sym:n {#1} }
3574       \int_zero:N \l__spintent_spangle_pt_idx_int
3575       \seq_map_inline:Nn \l__spintent_spangle_pt_seq
3576         {
3577           \int_incr:N \l__spintent_spangle_pt_idx_int
3578           \__spintent_mathmlarg_point:nnn
3579             { pt \int_use:N \l__spintent_spangle_pt_idx_int }
3580             { sp#1 }
3581             { ##1 }
3582         }
3583     }
3584   }
3585 }

```

(End of definition for `\__spintent_spangle_mathml:n`.)

`\__spintent_spangle_exec:nnn` The function `\__spintent_spangle_exec:nnn` receives the *short name* of the command passed in ‘#1’, the optional *⟨keys⟩* passed in ‘#2’ and the *⟨argument⟩* passed in ‘#3’, delegating the rendering to `\__spintent_spangle_process:nn`.

```

3586 \cs_new_protected:Nn \__spintent_spangle_exec:nnn
3587 {
3588   \keys_set:nn { spintent / sp #1 } { #2 }
3589   \__spintent_spangle_process:nn { #1 } { #3 }
3590 }

```

(End of definition for `\__spintent_spangle_exec:nnn`.)

`\spangle` Both public commands `\spangle` and `\spmangle` enforces *math mode*, opens a local group, and delegates execution to `\__spintent_spangle_exec:nnn`.

```

3591 \NewDocumentCommand \spangle { 0{} m }
3592 {
3593   \mode_if_math:TF
3594   {
3595     \group_begin:
3596     \__spintent_spangle_exec:nnn { angle } { #1 } { #2 }
3597     \group_end:
3598   }
3599   { \msg_error:nnn { spintent } { need-math-mode } { \spangle } }
3600 }
3601 \NewDocumentCommand \spmangle { 0{} m }
3602 {
3603   \mode_if_math:TF
3604   {
3605     \group_begin:
3606     \__spintent_spangle_exec:nnn { mangle } { #1 } { #2 }
3607     \group_end:
3608   }
3609   { \msg_error:nnn { spintent } { need-math-mode } { \spmangle } }
3610 }

```

(End of definition for `\spangle` and `\spmangle`. These functions are documented on page 20.)

11.39 The commands `\sparc` and `\spmarc`

The user commands `\sparc` and `\spmarc` provide a semantic interface for arcs. Unlike `\spmside` and `\spmangle`, `\spmarc` has no `print-m` key: `\operatorname{m}` is always present, since $m\widehat{AB}$ is the only standard notation for the measure of an arc.

11.39.1 Definition of variables for `\sparc` and `\spmarc`

Each pair of variables is declared once for both `\sparc` and `\spmarc` via `\clist_map_inline:nn`. The variables `\__spintent_sparc_mode_str` and `\__spintent_spmarc_mode_str` store the values set by the key `read-cmd`; the variables `\__spintent_sparc_prefix_tl` and `\__spintent_spmarc_prefix_tl` store the values set by the key `prefix`.

```

3611 \clist_map_inline:nn { arc , marc }
3612 {
3613   \str_new:c { \__spintent_sp #1 _mode_str }
3614   \tl_new:c { \__spintent_sp #1 _prefix_tl }
3615 }

```

(End of definition for `\__spintent_sparc_mode_str` and others.)

11.39.2 Definition of error messages for `\sparc` and `\spmarc`

We define an “error” message for the commands `\sparc` and `\spmarc`. The “error” is triggered if the user includes a invalid `{⟨argument⟩}` passed in ‘#1’ to the command.

```

3616 \clist_map_inline:nn { arc , marc }
3617 {
3618   \msg_new:nnnn { spintent } { sp #1 -invalid-points }
3619   {
3620     Invalid~point~format~in~##1:~'##2'~\msg_line_context:.
3621   }
3622   {
3623     See~the~documentation~of~##1~for~the~accepted~point~formats.
3624   }
3625 }

```

(End of definition for `sparc-invalid-points` and `spmarc-invalid-points`.)

11.39.3 Definition of keys for `\sparc` and `\spmarc`

We define the shared `⟨keys⟩` `read-cmd`, `prefix`, `silent-cmd` and `concept`.

```

read-cmd 3626 \clist_map_inline:nn { arc , marc }
prefix   3627 {
silent-cmd 3628   \keys_define:nn { spintent / sp #1 }
concept    3629   {
unknown    3630     read-cmd           .choices:nn = { school , mathcat }
           3631     {
           3632       \int_case:nn { \l_keys_choice_int }
           3633       {

```

```

3634         {1} { \str_set:cn { \__spintent_sp #1 _mode_str } { school } }
3635         {2} { \str_set:cn { \__spintent_sp #1 _mode_str } { mathcat } }
3636     }
3637 },
3638 read-cmd          .initial:n = school,
3639 read-cmd          .value_required:n = true,
3640 read-cmd / unknown .code:n =
3641     \msg_error:nneee { spintent } { unknown-choice }
3642     { read-cmd } { school,~mathcat } { \exp_not:n {##1} },
3643 prefix           .code:n =
3644     { \__spintent_sanitize_affix:cn { \__spintent_sp #1 _prefix_tl } {##1} },
3645 prefix           .initial:n = ,
3646 prefix           .value_required:n = true,
3647 silent-cmd       .bool_set:c = { \__spintent_sp #1 _silent_cmd_bool },
3648 silent-cmd       .initial:n = false,
3649 silent-cmd       .value_required:n = true,
3650 concept          .bool_set:c = { \__spintent_sp #1 _concept_bool },
3651 concept          .initial:n = true,
3652 concept          .value_required:n = true,
3653 unknown          .code:n =
3654     {
3655         \str_set:Nn \__spintent_command_name_str { sp #1 }
3656         \__spintent_unknown_keys_cmd:n {##1}
3657     },
3658 }
3659 }

```

• The key `print-m` is defined for both commands for simplicity, but has no effect on `\sparc`.

(End of definition for `read-cmd` and others.)

11.39.4 Internal functions for `\sparc` and `\sparmrc`

`\__spintent_sparc_wide_arc:n`

The function `\__spintent_sparc_wide_arc:n` acts as a fallback when the mathematical font used in the document does not provide the command `\widearc`. The definition of this function is a direct adaptation of a response given by Clea F. Rees (@cfr) to a query in the chat room of TeX-SX.

```

3660 \cs_new_protected_nopar:Nn \__spintent_sparc_wide_arc:n
3661 {
3662     \Umathaccent 7 \symoperators "023DC \scan_stop: {#1}
3663 }

```

(End of definition for `\__spintent_sparc_wide_arc:n`.)

`\__spintent_sparc_print_arc:n`

The function `\__spintent_sparc_print_arc:n` applies the command `\widearc` to the argument passed to `\sparc` or `\sparmrc`. If the mathematical font set in the document does not provide the command `\widearc`, we will use the built-in function `\__spintent_sparc_wide_arc:n`.

```

3664 \cs_new_protected:Nn \__spintent_sparc_print_arc:n
3665 {
3666     \cs_if_exist:NTF \widearc
3667     { \widearc {#1} }
3668     { \__spintent_sparc_wide_arc:n {#1} }
3669 }

```

(End of definition for `\__spintent_sparc_print_arc:n`.)

`\__spintent_sparc_intent_tl`

`\__spintent_sparc_intent_tl` holds the concept word (arco or medida-del-arco). The rest are scratch variables to split `\__spintent_geo_luasets_points_clist` and build the `$pt1, $pt2, ...` reference list used in the concept `intent`.

```

3670 \tl_new:N \__spintent_sparc_intent_tl
3671 \seq_new:N \__spintent_sparc_pt_seq
3672 \tl_new:N \__spintent_sparc_refs_tl
3673 \tl_new:N \__spintent_sparc_intent_arg_tl
3674 \int_new:N \__spintent_sparc_pt_idx_int

```

(End of definition for `\__spintent_sparc_intent_tl` and others.)

`\__spintent_sparc_process:nn`

The internal function `\__spintent_sparc_process:nn` receives the short name of the command (arc or marc) in ‘#1’ and the `{(argument)}` in ‘#2’. It calls `\__spintent_luafun_geo_parse_and_set:n` to process ‘#2’, returning an “error” if invalid, then sets `\__spintent_sparc_intent_tl` to arco (or medida-del-arco for `\sparmrc`). No `intent` is built here: it needs the reference list, which `\__spintent_sparc_math` builds after splitting the points.

```

3675 \cs_new_protected:Nn \__spintent_sparc_process:nn
3676 {

```

```

3677   \__spintent_luafun_geo_parse_and_set:n { \exp_not:n {#2} }
3678   \str_if_eq:VnT \__spintent_geo_luaseta_error_str { true }
3679   {
3680     \msg_error:nnee { spintent } { sp #1 -invalid-points }
3681     { \c_backslash_str sp #1 } { \exp_not:n {#2} }
3682   }
3683   \str_if_eq:eeTF {#1} { marc }
3684   { \tl_set:Nn \__spintent_sparc_intent_tl { medida-del-arco } }
3685   { \tl_set:Nn \__spintent_sparc_intent_tl { arco } }
3686   \__spintent_sparc_mathml:n {#1}
3687 }

```

(End of definition for __spintent_sparc_process:nn.)

__spintent_sparc_mathml:n

The function `\__spintent_sparc_mathml:n` receives the short command name in ‘#1’. It splits `\__spintent_geo_` into `\__spintent_sparc_pt_seq` and walks it once to build `\__spintent_sparc_refs_tl`, the comma-separated `$pt1, $pt2, ...` reference list, naming each point by position.

The concept `intent` is `_` - when `silent-cmd` is `true` or `concept` is `false`; otherwise `\__spintent_sparc_intent_` prefixed with `prefix` when given. It is applied with a single native `\MathMLintent` wrapping `\__spintent_sparc_` directly (same shape as `\__spintent_spside_mathml:n`), preceded by `\__spintent_luafun_inner_sep:` (a second sibling so the sole `<mrow>` does not collapse into `<math>`, luamml issue #26). A silent `\operatorname{m}` precedes it for `\spmarc` (always, no `print-m` key here). The sequence is walked a second time, calling `\__spintent_mathmlarg_point:nnn` once per point with its `ptn` reference name, looked up under `sp#1`.

```

3688 \cs_new_protected:Nn \__spintent_sparc_mathml:n
3689 {
3690   \seq_set_from_clist:NN \__spintent_sparc_pt_seq \__spintent_geo_luaseta_points_clist
3691
3692   \tl_clear:N \__spintent_sparc_refs_tl
3693   \int_zero:N \__spintent_sparc_pt_idx_int
3694   \seq_map_inline:Nn \__spintent_sparc_pt_seq
3695   {
3696     \int_incr:N \__spintent_sparc_pt_idx_int
3697     \tl_if_empty:NF \__spintent_sparc_refs_tl
3698     { \tl_put_right:Nn \__spintent_sparc_refs_tl { , } }
3699     \tl_put_right:Ne \__spintent_sparc_refs_tl { $ pt \int_use:N \__spintent_sparc_pt_idx_int
3700   }
3701
3702   \bool_if:cTF { \__spintent_sp #1 _silent_cmd_bool }
3703   {
3704     \tl_set:Nn \__spintent_sparc_intent_arg_tl { _- }
3705   }
3706   {
3707     \bool_if:cTF { \__spintent_sp #1 _concept_bool }
3708     {
3709       \tl_set:Ne \__spintent_sparc_intent_arg_tl
3710       {
3711         \tl_if_empty:cF { \__spintent_sp #1 _prefix_tl }
3712         { \tl_use:c { \__spintent_sp #1 _prefix_tl } - }
3713         \__spintent_sparc_intent_tl :prefix( \__spintent_sparc_refs_tl )
3714       }
3715     }
3716     {
3717       \tl_set:Nn \__spintent_sparc_intent_arg_tl { _- }
3718     }
3719   }
3720
3721   \__spintent_invisible_sep: % need by MathCAT (bug in luamml issues #26)
3722   \MathMLintent { \__spintent_sparc_intent_arg_tl }
3723   {
3724     \__spintent_luafun_inner_sep:
3725     \str_if_eq:eeT {#1} { marc }
3726     {
3727       \__spintent_luafun_wrap_mrow_intent_arg:nn
3728       { } { intent = ":silent" }
3729       { \operatorname { m } } }
3730   }
3731   \__spintent_sparc_print_arc:n
3732   {
3733     \int_zero:N \__spintent_sparc_pt_idx_int
3734     \seq_map_inline:Nn \__spintent_sparc_pt_seq

```

```

3735         {
3736             \int_incr:N \__spintent_sparc_pt_idx_int
3737             \__spintent_mathmlarg_point:nnn
3738             { pt \int_use:N \__spintent_sparc_pt_idx_int }
3739             { sp #1 }
3740             { ##1 }
3741         }
3742     }
3743 }
3744 }

```

(End of definition for `\__spintent_sparc_mathml:n`.)

`\__spintent_sparc_exec:nnn`

The function `\__spintent_sparc_exec:nnn` receives the *short name* of the command passed in ‘#1’, the optional *⟨keys⟩* passed in ‘#2’ and the *⟨argument⟩* passed in ‘#3’, delegating the rendering to `\__spintent_sparc_process:nn`.

```

3745 \cs_new_protected:Nn \__spintent_sparc_exec:nnn
3746 {
3747     \keys_set:nn { spintent / sp #1 } { #2 }
3748     \__spintent_sparc_process:nn { #1 } { #3 }
3749 }

```

(End of definition for `\__spintent_sparc_exec:nnn`.)

`\sparc` Both public commands `\sparc` and `\spmarc` enforces *math mode*, opens a local group, and delegates execution to `\__spintent_sparc_exec:nnn`.

```

3750 \NewDocumentCommand \sparc { O{} m }
3751 {
3752     \mode_if_math:TF
3753     {
3754         \group_begin:
3755         \__spintent_sparc_exec:nnn { arc } { #1 } { #2 }
3756         \group_end:
3757     }
3758     { \msg_error:nnn { spintent } { need-math-mode } { \sparc } }
3759 }
3760 \NewDocumentCommand \spmarc { O{} m }
3761 {
3762     \mode_if_math:TF
3763     {
3764         \group_begin:
3765         \__spintent_sparc_exec:nnn { marc } { #1 } { #2 }
3766         \group_end:
3767     }
3768     { \msg_error:nnn { spintent } { need-math-mode } { \spmarc } }
3769 }

```

(End of definition for `\sparc` and `\spmarc`. These functions are documented on page 21.)

11.40 The command `\spPoly`

The user command `\spPoly` typesets a polygon defined by its vertices. The figure type and its visual symbol are inferred from the vertex count: three points produce a triangle, four a square, five or more a generic polygon with no symbol. It never sends a boolean to Lua: `\l__spintent_geo_luaset_intent_str` (the full *intent*, with the figure name).

11.40.1 Definition of variables for `\spPoly`

`\l__spintent_spPoly_mode_str`
`\l__spintent_spPoly_prefix_tl`

The variable `\l__spintent_spPoly_mode_str` stores the value set by the key `read-cmd`; the variable `\l__spintent_spPoly_prefix_tl` stores the value set by the key `prefix`.

```

3770 \str_new:N \l__spintent_spPoly_mode_str
3771 \tl_new:N \l__spintent_spPoly_prefix_tl

```

(End of definition for `\l__spintent_spPoly_mode_str` and `\l__spintent_spPoly_prefix_tl`.)

11.40.2 Definition of error messages for `\spPoly`

`spPoly-invalid-points`

Raised when the argument is not a comma-separated list of at least three uppercase letters.

```

3772 \msg_new:nnnn { spintent } { spPoly-invalid-points }
3773 {
3774     Invalid~point~format~in~\token_to_str:N \spPoly:~'~#1'~\msg_line_context:.
3775 }
3776 {
3777     See~the~documentation~of~\token_to_str:N \spPoly~for~the~accepted~point~formats.
3778 }

```

(End of definition for `spPoly-invalid-points`.)

11.40.3 Definition of keys for `\spPoly`

We define the *(keys)* `read-cmd`, `prefix`, `print-sym`, `silent-cmd` and `concept`.

```

read-cmd 3779 \keys_define:nn { spintent / spPoly }
prefix    3780 {
print-sym 3781   read-cmd           .choices:nn = { school , mathcat }
silent-cmd 3782   {
concept    3783     \int_case:nn { \l_keys_choice_int }
unknown    3784       {
3785         {1} { \str_set:Nn \l__spintent_spPoly_mode_str { school } }
3786         {2} { \str_set:Nn \l__spintent_spPoly_mode_str { mathcat } }
3787       }
3788     },
3789     read-cmd           .initial:n = school,
3790     read-cmd           .value_required:n = true,
3791     read-cmd / unknown .code:n =
3792       \msg_error:nneee { spintent } { unknown-choice }
3793       { read-cmd } { school,~mathcat } { \exp_not:n {#1} },
3794     prefix             .code:n =
3795     { \__spintent_sanitize_affix:Nn \l__spintent_spPoly_prefix_tl {#1} },
3796     prefix             .initial:n = ,
3797     prefix             .value_required:n = true,
3798     print-sym          .bool_set:N = \l__spintent_spPoly_print_sym_bool,
3799     print-sym          .initial:n = true,
3800     print-sym          .value_required:n = true,
3801     silent-cmd         .bool_set:N = \l__spintent_spPoly_silent_cmd_bool,
3802     silent-cmd         .initial:n = false,
3803     silent-cmd         .value_required:n = true,
3804     concept            .bool_set:N = \l__spintent_spPoly_concept_bool,
3805     concept            .initial:n = true,
3806     concept            .value_required:n = true,
3807     unknown            .code:n =
3808     {
3809       \str_set:Nn \l__spintent_command_name_str { spPoly }
3810       \__spintent_unknown_keys_cmd:n {#1}
3811     },
3812   }

```

(End of definition for `read-cmd` and others.)

11.40.4 Internal functions for `\spPoly`

`\l__spintent_spPoly_pt_seq` Scratch variables to split `\l__spintent_geo_luaset_points_clist` and build the `$pt1`, `$pt2`, ... reference list, and to hold the final concept intent once built.

```

\l__spintent_spPoly_refs_tl
\l__spintent_spPoly_intent_arg_tl
\l__spintent_spPoly_pt_idx_int
3813 \seq_new:N \l__spintent_spPoly_pt_seq
3814 \tl_new:N \l__spintent_spPoly_refs_tl
3815 \tl_new:N \l__spintent_spPoly_intent_arg_tl
3816 \int_new:N \l__spintent_spPoly_pt_idx_int

```

(End of definition for `\l__spintent_spPoly_pt_seq` and others.)

`\__spintent_spPoly_sym:` Unchanged: reads `\l__spintent_geo_luaset_poly_sym_str` and typesets the corresponding symbol.

```

3817 \cs_new_protected:Nn \__spintent_spPoly_sym:
3818 {
3819   \str_case:Vn \l__spintent_geo_luaset_poly_sym_str
3820   {
3821     { triangle } { \triangle }
3822     { square } { \mdlgwhtsquare }
3823   }
3824 }

```

(End of definition for `\__spintent_spPoly_sym:`.)

`\__spintent_spPoly_build_refs:` Splits `\l__spintent_geo_luaset_points_clist` into `\l__spintent_spPoly_pt_seq` and walks it once to build `\l__spintent_spPoly_refs_tl`, the comma-separated `$pt1`, `$pt2`, ... reference list, naming each vertex by position.

```

3825 \cs_new_protected:Nn \__spintent_spPoly_build_refs:
3826 {
3827   \seq_set_from_clist:NN \l__spintent_spPoly_pt_seq \l__spintent_geo_luaset_points_clist
3828   \tl_clear:N \l__spintent_spPoly_refs_tl
3829   \int_zero:N \l__spintent_spPoly_pt_idx_int

```

```

3830 \seq_map_inline:Nn \l__spintent_spPoly_pt_seq
3831 {
3832   \int_incr:N \l__spintent_spPoly_pt_idx_int
3833   \tl_if_empty:NF \l__spintent_spPoly_refs_tl
3834   { \tl_put_right:Nn \l__spintent_spPoly_refs_tl { , } }
3835   \tl_put_right:Ne \l__spintent_spPoly_refs_tl { $ pt \int_use:N \l__spintent_spPoly_pt_idx_int }
3836 }
3837 }

```

(End of definition for `\l__spintent_spPoly_build_refs:`)

`\l__spintent_spPoly_build_concept:`

Builds `\l__spintent_spPoly_intent_arg_tl`, independently of `print-sym:_(refs)` when `silent-cmd` is `true` or `concept` is `false`; otherwise `\l__spintent_geo_luaset_concept_str:prefix(refs)`, prefixed with `prefix` when given. Must be called after `\l__spintent_spPoly_build_refs:`.

```

3838 \cs_new_protected:Nn \l__spintent_spPoly_build_concept:
3839 {
3840   \bool_if:NTF \l__spintent_spPoly_silent_cmd_bool
3841   {
3842     \tl_set:Ne \l__spintent_spPoly_intent_arg_tl { _ ( \l__spintent_spPoly_refs_tl ) }
3843   }
3844   {
3845     \bool_if:NTF \l__spintent_spPoly_concept_bool
3846     {
3847       \tl_set:Ne \l__spintent_spPoly_intent_arg_tl
3848       {
3849         \tl_if_empty:NF \l__spintent_spPoly_prefix_tl
3850         { \tl_use:N \l__spintent_spPoly_prefix_tl - }
3851         \l__spintent_geo_luaset_concept_str :prefix( \l__spintent_spPoly_refs_tl )
3852       }
3853     }
3854     {
3855       \tl_set:Ne \l__spintent_spPoly_intent_arg_tl { _ ( \l__spintent_spPoly_refs_tl ) }
3856     }
3857   }
3858 }

```

(End of definition for `\l__spintent_spPoly_build_concept:`)

`\l__spintent_spPoly_points_loop:`

Walks `\l__spintent_spPoly_pt_seq` a second time, calling `\l__spintent_mathmlarg_point:nnn` once per vertex with its `ptn` reference name, looked up under `spPoly`: it alone decides `arg/literal intent` per vertex — replacing the single combined `\MathMLarg{pts}{...}` that lost `arg` on any vertex with a subscript or prime (the same `annotate_attribute/sub-sup` limitation already found and worked around for `\spPoint`).

```

3859 \cs_new_protected:Nn \l__spintent_spPoly_points_loop:
3860 {
3861   \int_zero:N \l__spintent_spPoly_pt_idx_int
3862   \seq_map_inline:Nn \l__spintent_spPoly_pt_seq
3863   {
3864     \int_incr:N \l__spintent_spPoly_pt_idx_int
3865     \l__spintent_mathmlarg_point:nnn
3866     { pt \int_use:N \l__spintent_spPoly_pt_idx_int }
3867     { spPoly }
3868     { ##1 }
3869   }
3870 }

```

(End of definition for `\l__spintent_spPoly_points_loop:`)

`\l__spintent_spPoly_process:n`

Calls `\l__spintent_luafun_geo_poly_parse_and_set:n`, reports `spPoly-invalid-points` on failure, then delegates to `\l__spintent_spPoly_mathml:`. No `intent` is built here: it needs the reference list, which `\l__spintent_spPoly_mathml:` builds after splitting the vertices.

```

3871 \cs_new_protected:Nn \l__spintent_spPoly_process:n
3872 {
3873   \l__spintent_luafun_geo_poly_parse_and_set:n { \exp_not:n {##1} }
3874   \str_if_eq:VnT \l__spintent_geo_luaset_error_str { true }
3875   {
3876     \msg_error:nne { spintent } { spPoly-invalid-points }
3877     { \exp_not:n {##1} }
3878   }
3879   \l__spintent_spPoly_mathml:
3880 }

```

(End of definition for `\l__spintent_spPoly_process:n`)

`\__spintent_spPoly_mathml:` Builds the reference list and the concept `\__spintent_spPoly_build_refs:`, `\__spintent_spPoly_build_concept:` then wraps everything in a single native `\MathMLintent`, preceded by `\__spintent_luafun_inner_sep:` (a second sibling so the sole `<mrow>` does not collapse into `<math>`, `luamml` issue #26). `print-sym` and `concept/silent-cmd` are independent: the former only decides whether the glyph (`\__spintent_spPoly_sym:`, silenced with `\__spintent_luafun_wrap_mrow_intent_arg:nn`) is attempted — it is skipped anyway when `\l__spintent_geo_luaset_poly_sym_str` is empty (no symbol defined for that vertex count, e.g. pentagon and above) — and never affects whether the concept word itself is spoken.

```

3881 \cs_new_protected:Nn \__spintent_spPoly_mathml:
3882 {
3883   \__spintent_invisible_sep: % (luamml issues #26)
3884   \__spintent_spPoly_build_refs:
3885   \__spintent_spPoly_build_concept:
3886   \MathMLintent { \l__spintent_spPoly_intent_arg_tl }
3887   {
3888     \__spintent_luafun_inner_sep:
3889     \bool_if:NT \l__spintent_spPoly_print_sym_bool
3890     {
3891       \str_if_empty:NF \l__spintent_geo_luaset_poly_sym_str
3892       {
3893         \__spintent_luafun_wrap_mrow_intent_arg:nn
3894         { } { intent = ":silent" }
3895         { \__spintent_spPoly_sym: }
3896       }
3897     }
3898     \__spintent_spPoly_points_loop:
3899   }
3900 }
```

(End of definition for `\__spintent_spPoly_mathml:`.)

`\__spintent_spPoly_exec:nn` The function `\__spintent_spPoly_exec:nn` receives the optional keys in #1 and the argument in #2, delegating the rendering to `\__spintent_spPoly_process:n`.

```

3901 \cs_new_protected:Nn \__spintent_spPoly_exec:nn
3902 {
3903   \keys_set:nn { spintent / spPoly } { #1 }
3904   \__spintent_spPoly_process:n { #2 }
3905 }
```

(End of definition for `\__spintent_spPoly_exec:nn`.)

`\spPoly` The public command `\spPoly` enforces *math mode*, opens a local group, and delegates execution to `\__spintent_spPoly_exec:nn`.

```

3906 \NewDocumentCommand \spPoly { O{} m }
3907 {
3908   \mode_if_math:TF
3909   {
3910     \group_begin:
3911     \__spintent_spPoly_exec:nn { #1 } { #2 }
3912     \group_end:
3913   }
3914   { \msg_error:nnn { spintent } { need-math-mode } { \spPoly } }
3915 }
```

(End of definition for `\spPoly`. This function is documented on page 22.)

11.41 The commands `\spAfig` and `\spPfig`

The user commands `\spAfig` and `\spPfig` typeset the area and the perimeter of a polygonal figure, using the delimited-optional argument syntax `d()` already established by `\spmcld/\spmcm`. The key `print-sym` is never sent to Lua: the symbol type is returned unconditionally in `\l__spintent_geo_luaset_poly_sym_str`, and `expl3` decides whether to wrap it in `\MathMLintent{<:silent>}` — the same mechanism already used by `\spPoly`.

11.41.1 Definition of variables for `\spAfig` and `\spPfig`

`\l__spintent_geo_final_print_tl` Scratch variables used by `\__spintent_spfig_process:nn` to assemble the visual and the `intent`. `\l__spintent_geo_final_print_tl` holds the final visual placed under `\mathcal`'s subscript. The final literal `intent` and the concept forwarded when `read-cmd` is `mathcat`.

```

3916 \tl_new:N \l__spintent_geo_final_print_tl
```

(End of definition for `\l__spintent_geo_final_print_tl`.)

```

\__spintent_spAfig_mode_str
\__spintent_spPfig_mode_str
  \__spintent_spAfig_print_sym_str
  \__spintent_spPfig_print_sym_str
    \__spintent_spAfig_prefix_tl
    \__spintent_spPfig_prefix_tl
  \__spintent_spAfig_read_arg_tl
  \__spintent_spPfig_read_arg_tl

```

These variables store the value set by each corresponding key: `read-cmd`, `print-sym`, `prefix` and `read-arg`, respectively. The value set by `read-arg` overrides the figure name inferred from the vertex count, independently of `print-sym`.

```

3917 \clist_map_inline:nn { Afig , Pfig }
3918 {
3919   \str_new:c { \__spintent_sp #1 _mode_str }
3920   \str_new:c { \__spintent_sp #1 _print_sym_str }
3921   \tl_new:c { \__spintent_sp #1 _prefix_tl }
3922   \tl_new:c { \__spintent_sp #1 _read_arg_tl }
3923 }

```

(End of definition for `\__spintent_spAfig_mode_str` and others.)

11.41.2 Definition of error messages for `\spAfig` and `\spPfig`

All eight messages are generated by the same map, using the same `##1/##2` doubling convention as `\spside/\spmside`. `sp #1-invalid-points` is currently unused by `\__spintent_spfig_process:nn`, which raises only `sp #1-invalid-arg` for any parse failure, regardless of whether a comma was present. `sp #1-sym-letra-conflict` and `sp #1-sym-cardinality-conflict` are raised when `print-sym` is forced to a value incompatible with the actual argument.

```

3924 \clist_map_inline:nn { Afig , Pfig }
3925 {
3926   \msg_new:nnnn { spintent } { sp #1 -invalid-points }
3927   {
3928     Invalid~point~format~in~##1:~'##2'~\msg_line_context:.
3929   }
3930   {
3931     See~the~documentation~of~##1~for~the~accepted~point~formats.
3932   }
3933   \msg_new:nnnn { spintent } { sp #1 -invalid-arg }
3934   {
3935     Invalid~argument~format~in~##1:~'##2'~\msg_line_context:.
3936   }
3937   {
3938     See~the~documentation~of~##1~for~the~accepted~argument~forms.
3939   }
3940   \msg_new:nnnn { spintent } { sp #1 -sym-letra-conflict }
3941   {
3942     print-sym~cannot~be~combined~with~a~lettered~argument~in~'##1'~\msg_line_context:.
3943   }
3944   {
3945     See~the~documentation~of~##1~for~details~on~print-sym.
3946   }
3947   \msg_new:nnnn { spintent } { sp #1 -sym-cardinality-conflict }
3948   {
3949     print-sym~does~not~match~the~vertex~count~in~'##1'~\msg_line_context:.
3950   }
3951   {
3952     See~the~documentation~of~##1~for~details~on~print-sym.
3953   }
3954 }

```

(End of definition for `spAfig-invalid-points` and others.)

11.41.3 Definition of keys for `\spAfig` and `\spPfig`

```

read-cmd
prefix
print-sym
read-arg
read-sub
silent-cmd
concept
unknown

```

The key `print-sym` chooses the visual symbol: `auto` (default) infers it from the vertex count (three points give `\triangle`, four give `\mdlgwhtsquare`, five or more give none); `triangle/square` force one, requiring the vertex count to match; `none` omits it, even with vertices. With a bare number/letter argument, `auto` and `none` behave the same (no symbol); `triangle/square` nest the argument under the forced symbol instead, and cannot be combined with a table letter (F/P/B/L). The key `read-arg` overrides the spoken figure name for real vertices, independently of `print-sym`. The key `read-sub` controls whether the bare number/letter argument is read with the word «sub» or as a plain number.

```

3955 \clist_map_inline:nn { Afig , Pfig }
3956 {
3957   \keys_define:nn { spintent / sp #1 }
3958   {
3959     read-cmd .choices:nn = { school , mathcat }
3960     {
3961       \int_case:nn { \l_keys_choice_int }
3962       {
3963         {1} { \str_set:cn { \__spintent_sp #1 _mode_str } { school } }

```

```

3964         {2} { \str_set:cn { \__spintent_sp #1 _mode_str } { mathcat } }
3965     }
3966 },
3967 read-cmd          .initial:n = school,
3968 read-cmd          .value_required:n = true,
3969 read-cmd / unknown .code:n =
3970     \msg_error:nneee { spintent } { unknown-choice }
3971     { read-cmd } { school,~mathcat } { \exp_not:n {##1} },
3972 prefix           .code:n =
3973     { \__spintent_sanitize_affix:cn { \__spintent_sp #1 _prefix_tl } {##1} },
3974 prefix           .initial:n = ,
3975 prefix           .value_required:n = true,
3976 print-sym        .choices:nn = { auto , triangle , square , none }
3977     {
3978         \int_case:nn { \l_keys_choice_int }
3979         {
3980             {1} { \str_set:cn { \__spintent_sp #1 _print_sym_str } { auto } }
3981             {2} { \str_set:cn { \__spintent_sp #1 _print_sym_str } { triangle } }
3982             {3} { \str_set:cn { \__spintent_sp #1 _print_sym_str } { square } }
3983             {4} { \str_set:cn { \__spintent_sp #1 _print_sym_str } { none } }
3984         }
3985     },
3986 print-sym        .initial:n = auto,
3987 print-sym        .value_required:n = true,
3988 print-sym / unknown .code:n =
3989     \msg_error:nneee { spintent } { unknown-choice }
3990     { print-sym } { auto,~triangle,~square,~none } { \exp_not:n {##1} },
3991 read-arg         .code:n =
3992     { \__spintent_sanitize_affix:cn { \__spintent_sp #1 _read_arg_tl } {##1} },
3993 read-arg         .initial:n = ,
3994 read-arg         .value_required:n = true,
3995 read-sub         .bool_set:c = { \__spintent_sp #1 _read_sub_bool },
3996 read-sub         .initial:n = false,
3997 read-sub         .value_required:n = true,
3998 silent-cmd      .bool_set:c = { \__spintent_sp #1 _silent_cmd_bool },
3999 silent-cmd      .initial:n = false,
4000 silent-cmd      .value_required:n = true,
4001 concept         .bool_set:c = { \__spintent_sp #1 _concept_bool },
4002 concept         .initial:n = true,
4003 concept         .value_required:n = true,
4004 unknown         .code:n =
4005     {
4006         \str_set:Nn \__spintent_command_name_str { sp #1 }
4007         \__spintent_unknown_keys_cmd:n {##1}
4008     },
4009 }
4010 }

```

(End of definition for read-cmd and others.)

11.41.4 Internal functions for \spAfig and \spPfig

`\__spintent_spfig_sym:` The function `\__spintent_spfig_sym:` reads `\__spintent_geo_print_sym_str` and typesets the corresponding symbol: `\triangle` for the value `triangle`, `\mdlgwhtsquare` for the value `square`.

```

4011 \cs_new_protected:Nn \__spintent_spfig_sym:
4012 {
4013     \str_case:Vn \__spintent_geo_print_sym_str
4014     {
4015         { triangle } { \triangle }
4016         { square } { \mdlgwhtsquare }
4017     }
4018 }

```

(End of definition for `\__spintent_spfig_sym:`.)

`\__spintent_spfig_op_tl` holds área or perímetro. `\__spintent_spfig_intent_tl` holds the concept word for the vertices case (read-arg or the auto-detected figure name). The rest are scratch variables to split `\__spintent_geo_luasets_points_clist` and build the `$pt1, $pt2, \dots` reference list.

```

4019 \tl_new:N \__spintent_spfig_op_tl
4020 \tl_new:N \__spintent_spfig_intent_tl
4021 \tl_new:N \__spintent_spfig_desc_tl
4022 \tl_new:N \__spintent_spfig_symbol_tl

```

```

4023 \seq_new:N \__spintent_sfig_pt_seq
4024 \tl_new:N \__spintent_sfig_refs_tl
4025 \tl_new:N \__spintent_sfig_intent_arg_tl
4026 \int_new:N \__spintent_sfig_pt_idx_int
4027 \str_new:N \__spintent_geo_print_sym_str

```

(End of definition for `\__spintent_sfig_op_tl` and others.)

`\__spintent_sfig_process:nn`

Receives the short command name (Afig or Pfig) in ‘#1’ and the $\{\langle argument \rangle\}$ in ‘#2’. Calls `\__spintent_luafun_geo` or `\__spintent_luafun_geo_pfig_parse_and_set:n`, reports `sp#1-invalid-arg` on failure, sets `\__spintent_sfig_op_tl` to `área/perímetro`, then delegates to `\__spintent_sfig_mathml:n`.

```

4028 \cs_new_protected:Nn \__spintent_sfig_process:nn
4029 {
4030   \str_if_eq:eeTF {#1} { Afig }
4031   { \__spintent_luafun_geo_afig_parse_and_set:n { \exp_not:n {#2} } }
4032   { \__spintent_luafun_geo_pfig_parse_and_set:n { \exp_not:n {#2} } }
4033   \str_if_eq:VnT \__spintent_geo_luaset_error_str { true }
4034   {
4035     \msg_error:nnee { spintent } { sp #1 -invalid-arg }
4036     { \c_backslash_str sp #1 } { \exp_not:n {#2} }
4037   }
4038   \str_if_eq:eeTF {#1} { Afig }
4039   { \tl_set:Nn \__spintent_sfig_op_tl { área } }
4040   { \tl_set:Nn \__spintent_sfig_op_tl { perímetro } }
4041   \str_set:Ne \__spintent_geo_print_sym_str { \str_use:c { \__spintent_sp #1 _print_sym_str } }
4042   \__spintent_sfig_mathml:n {#1}
4043 }

```

(End of definition for `\__spintent_sfig_process:nn`.)

`\__spintent_sfig_build_simple:n`

Handles the argument-less, table-letter and bare number/letter cases (no vertices). Builds `\__spintent_geo_final_print` and `\__spintent_sfig_desc_tl` (the descriptive part, without `área/perímetro`). `\__spintent_sfig_intent` is `\__spintent_sfig_op_tl-\__spintent_sfig_desc_tl`. `silent-cmd` overrides `\__spintent_sfig_op_tl` with `_`; with `silent-cmd=false` and `concept false`, it becomes `\__spintent_sfig_desc_tl` (the descriptive part alone, literally, without `área/perímetro`); with `concept true` it is `\__spintent_sfig_intent_tl`. Preserves the sym- letra-conflict check (a table letter cannot combine with a forced `print-sym`). Receives the short command name in ‘#1’.

```

4044 \cs_new_protected:Nn \__spintent_sfig_build_simple:n
4045 {
4046   \tl_if_empty:nTF { \__spintent_geo_luaset_print_tl }
4047   {
4048     \str_case:VnF \__spintent_geo_print_sym_str
4049     {
4050       { auto }
4051       {
4052         \tl_clear:N \__spintent_geo_final_print_tl
4053         \tl_clear:N \__spintent_sfig_desc_tl
4054       }
4055       { none }
4056       {
4057         \tl_clear:N \__spintent_geo_final_print_tl
4058         \tl_clear:N \__spintent_sfig_desc_tl
4059       }
4060     }
4061     {
4062       \tl_set:Nn \__spintent_geo_final_print_tl { \__spintent_sfig_sym: }
4063       \tl_set:Ne \__spintent_sfig_desc_tl
4064       {
4065         \str_if_eq:VnTF \__spintent_geo_print_sym_str { triangle }
4066         { triángulo } { cuadrado }
4067       }
4068     }
4069   }
4070   {
4071     \str_if_empty:NTF \__spintent_geo_luaset_letra_word_str
4072     {
4073       \str_case:VnF \__spintent_geo_print_sym_str
4074       {
4075         { auto } { \tl_set:Nn \__spintent_geo_final_print_tl { \__spintent_geo_luaset_p }
4076         { none } { \tl_set:Nn \__spintent_geo_final_print_tl { \__spintent_geo_luaset_p }
4077       }

```

```

4078         {
4079             \tl_set:Nn \l__spinttent_geo_final_print_tl
4080             {
4081                 \__spinttent_spfig_sym:
4082                 \c_math_subscript_token { \l__spinttent_geo_luaset_print_tl }
4083             }
4084         }
4085     \str_case:VnF \l__spinttent_geo_print_sym_str
4086     {
4087         { auto }
4088         {
4089             \tl_set:Ne \l__spinttent_spfig_desc_tl
4090             {
4091                 \bool_if:cT { \l__spinttent_sp #1 _read_sub_bool } { sub - }
4092                 \l__spinttent_geo_luaset_sub_spoken_str
4093             }
4094         }
4095         { none }
4096         {
4097             \tl_set:Ne \l__spinttent_spfig_desc_tl
4098             {
4099                 \bool_if:cT { \l__spinttent_sp #1 _read_sub_bool } { sub - }
4100                 \l__spinttent_geo_luaset_sub_spoken_str
4101             }
4102         }
4103     }
4104     {
4105         \tl_set:Ne \l__spinttent_spfig_desc_tl
4106         {
4107             \str_if_eq:VnTF \l__spinttent_geo_print_sym_str { triangle }
4108             { triángulo } { cuadrado }
4109             -
4110             \bool_if:cT { \l__spinttent_sp #1 _read_sub_bool } { sub - }
4111             \l__spinttent_geo_luaset_sub_spoken_str
4112         }
4113     }
4114 }
4115 {
4116     \str_case:VnF \l__spinttent_geo_print_sym_str
4117     {
4118         { auto } { }
4119         { none } { }
4120     }
4121     {
4122         \msg_error:nne { spinttent } { sp #1 -sym-letra-conflict }
4123         { \c_backslash_str sp #1 }
4124     }
4125     \tl_set:Nn \l__spinttent_geo_final_print_tl { \l__spinttent_geo_luaset_print_tl }
4126     \tl_set:Ne \l__spinttent_spfig_desc_tl
4127     {
4128         \str_if_empty:NF \l__spinttent_geo_luaset_letra_conector_str
4129         { \l__spinttent_geo_luaset_letra_conector_str - }
4130         \l__spinttent_geo_luaset_letra_word_str
4131         \str_if_empty:NF \l__spinttent_geo_luaset_sub_spoken_str
4132         {
4133             -
4134             \bool_if:cT { \l__spinttent_sp #1 _read_sub_bool } { sub - }
4135             \l__spinttent_geo_luaset_sub_spoken_str
4136         }
4137     }
4138 }
4139 }
4140 \tl_set:Ne \l__spinttent_spfig_intent_tl
4141 {
4142     \tl_if_empty:NTF \l__spinttent_spfig_desc_tl
4143     { \l__spinttent_spfig_op_tl }
4144     { \l__spinttent_spfig_op_tl - \l__spinttent_spfig_desc_tl }
4145 }
4146 \bool_if:cTF { \l__spinttent_sp #1 _silent_cmd_bool }
4147 { \tl_set:Nn \l__spinttent_spfig_intent_arg_tl { _- } }
4148 {

```

```

4149         \bool_if:cTF { l__spintent_sp #1 _concept_bool }
4150         { \tl_set:Ne \l__spintent_spfig_intent_arg_tl { \l__spintent_spfig_intent_tl } }
4151         { \tl_set:Ne \l__spintent_spfig_intent_arg_tl { _ \l__spintent_spfig_desc_tl - } }
4152     }
4153 }

```

(End of definition for `\l__spintent_spfig_build_simple:n`.)

`\l__spintent_spfig_build_refs:`

Splits `\l__spintent_geo_luaset_points_clist` into `\l__spintent_spfig_pt_seq` and walks it once to build `\l__spintent_spfig_refs_tl`, the comma-separated `$pt1, $pt2, ...` reference list, naming each vertex by position.

```

4154 \cs_new_protected:Nn \l__spintent_spfig_build_refs:
4155 {
4156     \seq_set_from_clist:NN \l__spintent_spfig_pt_seq \l__spintent_geo_luaset_points_clist
4157     \tl_clear:N \l__spintent_spfig_refs_tl
4158     \int_zero:N \l__spintent_spfig_pt_idx_int
4159     \seq_map_inline:Nn \l__spintent_spfig_pt_seq
4160     {
4161         \int_incr:N \l__spintent_spfig_pt_idx_int
4162         \tl_if_empty:NF \l__spintent_spfig_refs_tl
4163         { \tl_put_right:Nn \l__spintent_spfig_refs_tl { , } }
4164         \tl_put_right:Ne \l__spintent_spfig_refs_tl { $ \pt \int_use:N \l__spintent_spfig_pt_idx_int
4165     }
4166 }

```

(End of definition for `\l__spintent_spfig_build_refs:`.)

`\l__spintent_spfig_build_concept_vertices:n`

Handles the vertices case. `read-arg`, when given, overrides the auto-detected figure name; with `concept true` it is still prefixed with `área-del-/perímetro-del-`, with `concept false` it is used verbatim, and never silenced (only `silent-cmd` silences when `read-arg` is given — same convention as `\l__spintent_spside_process:nn`). With `read-arg` empty, `concept` controls silencing as usual. Also determines `\l__spintent_spfig_symbol_tl` (empty when none applies), preserving the sym-cardinality-conflict check (a forced `print-sym` must match the actual vertex count). Receives the short command name in ‘#1’. Must be called after `\l__spintent_spfig_build_refs:`.

```

4167 \cs_new_protected:Nn \l__spintent_spfig_build_concept_vertices:n
4168 {
4169     \tl_if_empty:cTF { l__spintent_sp #1 _read_arg_tl }
4170     { \tl_set:Ne \l__spintent_spfig_intent_tl { \l__spintent_geo_luaset_concept_str } }
4171     {
4172         \bool_if:cTF { l__spintent_sp #1 _concept_bool }
4173         {
4174             \tl_set:Ne \l__spintent_spfig_intent_tl
4175             {
4176                 \l__spintent_spfig_op_tl -del-
4177                 \tl_use:c { l__spintent_sp #1 _read_arg_tl }
4178             }
4179         }
4180         {
4181             \tl_set:Ne \l__spintent_spfig_intent_tl { \tl_use:c { l__spintent_sp #1 _read_arg_tl } }
4182         }
4183     }
4184
4185     \str_case:VnF \l__spintent_geo_print_sym_str
4186     {
4187         { auto }
4188         {
4189             \str_case:Vn \l__spintent_geo_luaset_poly_sym_str
4190             {
4191                 { triangle } { \tl_set:Nn \l__spintent_spfig_symbol_tl { \triangle } }
4192                 { square } { \tl_set:Nn \l__spintent_spfig_symbol_tl { \mdlgwhtsquare } }
4193             }
4194             \str_if_empty:NT \l__spintent_geo_luaset_poly_sym_str
4195             { \tl_clear:N \l__spintent_spfig_symbol_tl }
4196         }
4197         { none }
4198         { \tl_clear:N \l__spintent_spfig_symbol_tl }
4199     }
4200     {
4201         \str_if_eq:VVTF \l__spintent_geo_print_sym_str \l__spintent_geo_luaset_poly_sym_str
4202         { \tl_set:Nn \l__spintent_spfig_symbol_tl { \l__spintent_spfig_sym: } }
4203         {

```

```

4204         \msg_error:nne { spintrent } { sp #1 -sym-cardinality-conflict }
4205         { \c_backslash_str sp #1 }
4206     }
4207 }
4208
4209 \bool_if:cTF { l__spintrent_sp #1 _silent_cmd_bool }
4210 {
4211     \tl_set:Ne \l__spintrent_spfig_intent_arg_tl { _ ( \l__spintrent_spfig_refs_tl ) }
4212 }
4213 {
4214     \tl_if_empty:cTF { l__spintrent_sp #1 _read_arg_tl }
4215     {
4216         \bool_if:cTF { l__spintrent_sp #1 _concept_bool }
4217         {
4218             \tl_set:Ne \l__spintrent_spfig_intent_arg_tl
4219             {
4220                 \tl_if_empty:cF { l__spintrent_sp #1 _prefix_tl }
4221                 { \tl_use:c { l__spintrent_sp #1 _prefix_tl } - }
4222                 \l__spintrent_spfig_intent_tl :prefix( \l__spintrent_spfig_refs_tl )
4223             }
4224         }
4225         {
4226             \tl_set:Ne \l__spintrent_spfig_intent_arg_tl { _ ( \l__spintrent_spfig_refs_tl ) }
4227         }
4228     }
4229     {
4230         \tl_set:Ne \l__spintrent_spfig_intent_arg_tl
4231         {
4232             \tl_if_empty:cF { l__spintrent_sp #1 _prefix_tl }
4233             { \tl_use:c { l__spintrent_sp #1 _prefix_tl } - }
4234             \l__spintrent_spfig_intent_tl :prefix( \l__spintrent_spfig_refs_tl )
4235         }
4236     }
4237 }
4238 }

```

(End of definition for `\l__spintrent_spfig_build_concept_vertices:n`)

`\l__spintrent_spfig_points_loop:n` Walks `\l__spintrent_spfig_pt_seq` a second time, calling `\l__spintrent_mathmlarg_point:nnn` once per vertex with its `ptn` reference name, looked up under `sp#1`. Receives the short command name in `'#1'`.

```

4239 \cs_new_protected:Nn \l__spintrent_spfig_points_loop:n
4240 {
4241     \int_zero:N \l__spintrent_spfig_pt_idx_int
4242     \seq_map_inline:Nn \l__spintrent_spfig_pt_seq
4243     {
4244         \int_incr:N \l__spintrent_spfig_pt_idx_int
4245         \l__spintrent_mathmlarg_point:nnn
4246         { pt \int_use:N \l__spintrent_spfig_pt_idx_int }
4247         { sp #1 }
4248         { ##1 }
4249     }
4250 }

```

(End of definition for `\l__spintrent_spfig_points_loop:n`)

`\l__spintrent_spfig_mathml:n` Receives the short command name in `'#1'`. Branches on whether `\l__spintrent_geo_luaset_points_clist` is empty.

Without vertices, `\l__spintrent_spfig_build_simple:n` builds the content; a `\MathMLintent` wraps it only when `concept` is `true` — with `concept=false` the content is typeset directly, with no intent at all. With vertices, `\l__spintrent_spfig_build_refs:` then `\l__spintrent_spfig_build_concept_vertices:n` build the reference list and the concept intent, applied with a single native `\MathMLintent`. Inside, `\l__spintrent_mathcal:n{⟨A|P⟩}` is silenced with `\l__spintrent_luafun_wrap_mrow_intent_arg:nn` (it would otherwise be claimed by the queue meant for the symbol/vertices, the same ordering issue already found and fixed for `\spangle`'s own symbol); `\l__spintrent_spfig_symbol_tl` is silenced the same way when non-empty; the sequence is then walked by `\l__spintrent_spfig_points_loop:n`. All of this sits nested inside a subscript (`\c_math_subscript_token`), reached by the shared `mathml_filter` callback's recursive lookup through a noad's sub field, not just its nucleus.

`\l__spintrent_invisible_sep:` precedes both branches (a second sibling so the sole `<mrow>` does not collapse into `<math>`, `luamm` issue #26).

```

4251 \cs_new_protected:Nn \l__spintrent_spfig_mathml:n

```

```

4252 {
4253   \__spintent_invisible_sep: % (luamml issues #26)
4254   \clist_if_empty:NTF \__spintent_geo_luaset_points_clist
4255   {
4256     \__spintent_spfig_build_simple:n {#1}
4257     \MathMLintent { \__spintent_spfig_intent_arg_tl }
4258     {
4259       \__spintent_luafun_inner_sep:
4260       \str_if_eq:eeTF {#1} { Afig } { \__spintent_mathcal:n { A } } { \__spintent_mathcal:n
4261       \tl_if_empty:NF \__spintent_geo_final_print_tl
4262       {
4263         \c_math_subscript_token { \__spintent_geo_final_print_tl }
4264       }
4265     }
4266   }
4267   {
4268     \__spintent_spfig_build_refs:
4269     \__spintent_spfig_build_concept_vertices:n {#1}
4270     \MathMLintent { \__spintent_spfig_intent_arg_tl }
4271     {
4272       \__spintent_luafun_inner_sep:
4273       \__spintent_luafun_wrap_mrow_intent_arg:nn
4274       { } { intent = ":silent" }
4275       {
4276         \str_if_eq:eeTF {#1} { Afig } { \__spintent_mathcal:n { A } } { \__spintent_mathcal
4277       }
4278       \c_math_subscript_token
4279       {
4280         \tl_if_empty:NF \__spintent_spfig_symbol_tl
4281         {
4282           \__spintent_luafun_wrap_mrow_intent_arg:nn
4283           { } { intent = ":silent" }
4284           { \tl_use:N \__spintent_spfig_symbol_tl }
4285         }
4286         \__spintent_spfig_points_loop:n {#1}
4287       }
4288     }
4289   }
4290 }

```

(End of definition for __spintent_spfig_mathml:n.)

__spintent_spfig_exec:nnn

The function __spintent_spfig_exec:nnn receives the short name of the command in #1, the optional keys in #2, and the argument in #3, delegating the rendering to __spintent_spfig_process:nn.

```

4291 \cs_new_protected:Nn \__spintent_spfig_exec:nnn
4292 {
4293   \keys_set:nn { spintent / sp #1 } { #2 }
4294   \__spintent_spfig_process:nn { #1 } { #3 }
4295 }

```

(End of definition for __spintent_spfig_exec:nnn.)

\spAfig

Both public commands \spAfig and \spPfig enforce math mode, open a local group, and delegate execution

\spPfig

to __spintent_spfig_exec:nnn.

```

4296 \NewDocumentCommand \spAfig { 0{} d() }
4297 {
4298   \mode_if_math:TF
4299   {
4300     \group_begin:
4301     \tl_if_novalue:nTF {#2}
4302     { \__spintent_spfig_exec:nnn { Afig } { #1 } { } }
4303     { \__spintent_spfig_exec:nnn { Afig } { #1 } { #2 } }
4304     \group_end:
4305   }
4306   { \msg_error:nnn { spintent } { need-math-mode } { \spAfig } }
4307 }
4308 \NewDocumentCommand \spPfig { 0{} d() }
4309 {
4310   \mode_if_math:TF
4311   {
4312     \group_begin:
4313     \tl_if_novalue:nTF {#2}

```

```

4314         { \__spintent_spfig_exec:nnn { Pfig } { #1 } { } }
4315         { \__spintent_spfig_exec:nnn { Pfig } { #1 } { #2 } }
4316     \group_end:
4317 }
4318 { \msg_error:nnn { spintent } { need-math-mode } { \spPfig } }
4319 }

```

(End of definition for `\spAfig` and `\spPfig`. These functions are documented on page 23.)

11.42 The commands `\sprad` and `\spdiam`

The user-level commands `\sprad` and `\spdiam` provide a semantic interface for the radius and diameter of a circle. They delegate argument validation to the Lua module `spintent.lua`, thereby constructing a valid intent for `MathCAT`.

11.42.1 Definition of variables for `\sprad` and `\spdiam`

Each pair of variables is declared once for both `\sprad` and `\spdiam` via `\clist_map_inline:nn`.

```

\__spintent_sprad_mode_str 4320 \clist_map_inline:nn { rad , diam }
\__spintent_spdiam_mode_str 4321 {
  \__spintent_sprad_upper_case_bool 4322   \str_new:c { \__spintent_sp #1 _mode_str }
  \__spintent_spdiam_upper_case_bool 4323   \str_new:c { \__spintent_sp #1 _sub_index_str }
  \__spintent_sprad_sub_index_str 4324   \tl_new:c { \__spintent_sp #1 _read_arg_tl }
  \__spintent_spdiam_sub_index_str 4325   }

```

(End of definition for `\__spintent_sprad_mode_str` and others.)

Scratch variables used by the function `\__spintent_sp_rad_diam_print:n`.

```

\__spintent_sp_rad_diam_letra_tl 4326 \tl_new:N \__spintent_sp_rad_diam_letra_tl
\__spintent_sp_rad_diam_word_tl 4327 \tl_new:N \__spintent_sp_rad_diam_word_tl

```

(End of definition for `\__spintent_sp_rad_diam_letra_tl` and `\__spintent_sp_rad_diam_word_tl`.)

11.42.2 Definition of keys for `\sprad` and `\spdiam`

We define the shared *(keys)* `read-cmd`, `upper-case`, `sub-index`, `read-sub`, `read-arg`, `concept`, `silent-cmd` and `print-sym`.

```

read-cmd 4328 \clist_map_inline:nn { rad , diam }
upper-case 4329 {
sub-index 4330   \keys_define:nn { spintent / sp #1 }
read-sub 4331   {
read-arg 4332     read-cmd .choices:nn = { school , mathcat }
concept 4333     {
silent-cmd 4334       \int_case:nn { \l_keys_choice_int }
print-sym 4335       {
unknown 4336         {1} { \str_set:cn { \__spintent_sp #1 _mode_str } { school } }
4337         {2} { \str_set:cn { \__spintent_sp #1 _mode_str } { mathcat } }
4338       }
4339     },
4340     read-cmd .initial:n = school,
4341     read-cmd .value_required:n = true,
4342     read-cmd / unknown .code:n =
4343       \msg_error:nneee { spintent } { unknown-choice }
4344       { read-cmd } { school,~mathcat } { \exp_not:n {##1} },
4345     upper-case .bool_set:c = { \__spintent_sp #1 _upper_case_bool },
4346     upper-case .initial:n = false,
4347     upper-case .value_required:n = true,
4348     sub-index .code:n =
4349       { \str_set:cn { \__spintent_sp #1 _sub_index_str } {##1} },
4350     sub-index .initial:n = ,
4351     sub-index .value_required:n = true,
4352     read-sub .bool_set:c = { \__spintent_sp #1 _read_sub_bool },
4353     read-sub .initial:n = false,
4354     read-sub .value_required:n = true,
4355     read-arg .code:n =
4356       { \__spintent_sanitiz_e_affix:cn { \__spintent_sp #1 _read_arg_tl } {##1} },
4357     read-arg .initial:n = ,
4358     read-arg .value_required:n = true,
4359     concept .bool_set:c = { \__spintent_sp #1 _concept_bool },
4360     concept .initial:n = true,
4361     concept .value_required:n = true,
4362     silent-cmd .bool_set:c = { \__spintent_sp #1 _silent_cmd_bool },
4363     silent-cmd .initial:n = false,
4364     silent-cmd .value_required:n = true,

```

```

4365     print-sym .bool_set:c = { l__spintent_sp #1 _print_sym_bool },
4366     print-sym .initial:n = false,
4367     print-sym .value_required:n = true,
4368     unknown .code:n =
4369     {
4370         \str_set:Nn \l__spintent_command_name_str { sp #1 }
4371         \__spintent_unknown_keys_cmd:n {##1}
4372     },
4373 }
4374 }

```

• The keys `print-sym` are defined for both commands for simplicity, but has no effect on `\sprad`.

(End of definition for `read-cmd` and others.)

11.42.3 Internal functions for `\sprad` and `\spdiam`

`\__spintent_sp_rad_diam_print:n`

The function `\__spintent_sp_rad_diam_print:n` sets `\l__spintent_sp_rad_diam_letra_tl` to the bare letter — `r/R` for `\sprad`, `d/D` for `\spdiam` — per `upper-case`.

With `silent-cmd true`, the intent is `_-`. Otherwise, with `concept true` (the default), it verbalizes `radio/diámetro` (`read-arg` replaces this word when given), with `sub-index`, if present, appended right after (`read-sub` choosing `sub-⟨value⟩` or `⟨value⟩` alone) — the letter itself is never read here.

With `concept false`, the letter itself is read instead — but only when `read-cmd` is `school`, built the same way from the letter. With `read-cmd mathcat`, the intent is left empty: MathCAT applies its own rules to the letter and its subscript, unmarked by us.

With `sub-index` given and a non-empty intent, the letter and the `⟨value⟩` are wrapped together in one native `\MathMLintent`, subscript silenced — an unmarked `<msub>` gets MathCAT's own narration otherwise. With the intent empty, both stay bare. Receives the short command name in `'#1'` (`rad/diam`).

```

4375 \cs_new_protected:Nn \__spintent_sp_rad_diam_print:n
4376 {
4377     \bool_if:cTF { l__spintent_sp #1 _upper_case_bool }
4378     {
4379         \str_if_eq:eeTF {#1} { rad }
4380         { \tl_set:Nn \l__spintent_sp_rad_diam_letra_tl { R } }
4381         { \tl_set:Nn \l__spintent_sp_rad_diam_letra_tl { D } }
4382     }
4383     {
4384         \str_if_eq:eeTF {#1} { rad }
4385         { \tl_set:Nn \l__spintent_sp_rad_diam_letra_tl { r } }
4386         { \tl_set:Nn \l__spintent_sp_rad_diam_letra_tl { d } }
4387     }
4388     \__spintent_invisible_sep:
4389     \str_if_eq:eeT {#1} { diam }
4390     {
4391         \bool_if:NT \__spintent_spdiam_print_sym_bool
4392         { \MathMLintent { :silent } { ∅ } }
4393     }
4394     \bool_if:cTF { l__spintent_sp #1 _silent_cmd_bool }
4395     {
4396         \str_if_empty:cTF { l__spintent_sp #1 _sub_index_str }
4397         {
4398             \__spintent_luafun_wrap_mrow_intent_arg:nn
4399             { } { intent = "_-" }
4400             { \l__spintent_sp_rad_diam_letra_tl }
4401         }
4402         {
4403             \MathMLintent { _- }
4404             {
4405                 \__spintent_luafun_inner_sep:
4406                 \l__spintent_sp_rad_diam_letra_tl
4407                 \c_math_subscript_token
4408                 {
4409                     \MathMLintent { :silent }
4410                     { \str_use:c { l__spintent_sp #1 _sub_index_str } }
4411                 }
4412             }
4413         }
4414     }
4415     {
4416         \bool_if:cTF { l__spintent_sp #1 _concept_bool }
4417         {

```

```

4418 \tl_if_empty:cTF { \__spintent_sp #1 _read_arg_tl }
4419 {
4420   \str_if_eq:eeTF {#1} { rad }
4421   { \tl_set:Nn \__spintent_sp_rad_diam_word_tl { radio } }
4422   { \tl_set:Nn \__spintent_sp_rad_diam_word_tl { diámetro } }
4423 }
4424 { \tl_set:Nn \__spintent_sp_rad_diam_word_tl { \tl_use:c { \__spintent_sp #1 _read
4425 \str_if_empty:cTF { \__spintent_sp #1 _sub_index_str }
4426 {
4427   \__spintent_luafun_wrap_mrow_intent_arg:nn
4428   { } { intent = "_ \__spintent_sp_rad_diam_word_tl - :prefix" }
4429   { \__spintent_sp_rad_diam_letra_tl }
4430 }
4431 {
4432   \str_if_eq:eeTF
4433   { \str_use:c { \__spintent_sp #1 _mode_str } } { school }
4434   {
4435     \MathMLintent
4436     {
4437       _ \__spintent_sp_rad_diam_word_tl -
4438       \bool_if:cT { \__spintent_sp #1 _read_sub_bool } { sub- }
4439       \str_use:c { \__spintent_sp #1 _sub_index_str }
4440       :prefix
4441     }
4442     {
4443       \__spintent_luafun_inner_sep:
4444       \__spintent_sp_rad_diam_letra_tl
4445       \c_math_subscript_token
4446       {
4447         \MathMLintent { :silent }
4448         { \str_use:c { \__spintent_sp #1 _sub_index_str } }
4449       }
4450     }
4451   }
4452   {
4453     \__spintent_luafun_wrap_mrow_intent_arg:nn
4454     { } { intent = "_ \__spintent_sp_rad_diam_word_tl - :prefix" }
4455     { \__spintent_sp_rad_diam_letra_tl }
4456     \c_math_subscript_token
4457     { \str_use:c { \__spintent_sp #1 _sub_index_str } }
4458   }
4459 }
4460 }
4461 {
4462   \str_if_empty:cTF { \__spintent_sp #1 _sub_index_str }
4463   {
4464     \str_if_eq:eeTF
4465     { \str_use:c { \__spintent_sp #1 _mode_str } } { school }
4466     {
4467       \__spintent_luafun_wrap_mrow_intent_arg:nn
4468       { } { intent = "_ \__spintent_sp_rad_diam_letra_tl - :prefix" }
4469       { \__spintent_sp_rad_diam_letra_tl }
4470     }
4471     { \__spintent_sp_rad_diam_letra_tl }
4472   }
4473   {
4474     \str_if_eq:eeTF
4475     { \str_use:c { \__spintent_sp #1 _mode_str } } { school }
4476     {
4477       \MathMLintent
4478       {
4479         _ \__spintent_sp_rad_diam_letra_tl -
4480         \bool_if:cT { \__spintent_sp #1 _read_sub_bool } { sub- }
4481         \str_use:c { \__spintent_sp #1 _sub_index_str }
4482         :prefix
4483       }
4484       {
4485         \__spintent_luafun_inner_sep:
4486         \__spintent_sp_rad_diam_letra_tl
4487         \c_math_subscript_token
4488         {

```

```

4489         \MathMLintent { :silent }
4490         { \str_use:c { l__spinttent_sp #1 _sub_index_str } }
4491     }
4492 }
4493 }
4494 {
4495     \l__spinttent_sp_rad_diam_letra_tl
4496     \c_math_subscript_token
4497     { \str_use:c { l__spinttent_sp #1 _sub_index_str } }
4498 }
4499 }
4500 }
4501 }
4502 }

```

(End of definition for `\__spinttent_sp_rad_diam_print:n`.)

`\__spinttent_sp_rad_diam_exec:nn` The function `\__spinttent_sp_rad_diam_exec:nn` receives the *short name* of the command passed in ‘#1’ and the optional *(keys)* passed in ‘#2’ then delegating the rendering to `\__spinttent_sp_rad_diam_print:n`.

```

4503 \cs_new_protected:Nn \__spinttent_sp_rad_diam_exec:nn
4504 {
4505     \keys_set:nn { spinttent / sp #1 } {#2}
4506     \__spinttent_sp_rad_diam_print:n {#1}
4507 }

```

(End of definition for `\__spinttent_sp_rad_diam_exec:nn`.)

`\sprad` Both public commands `\sprad` and `\spdiam` enforces *math mode*, opens a local group, and delegates execution to `\__spinttent_sp_rad_diam_exec:nn`.

```

4508 \NewDocumentCommand \sprad { 0{} }
4509 {
4510     \mode_if_math:TF
4511     {
4512         \group_begin:
4513         \__spinttent_sp_rad_diam_exec:nn { rad } {#1}
4514         \group_end:
4515     }
4516     { \msg_error:nnn { spinttent } { need-math-mode } { \sprad } }
4517 }
4518 \NewDocumentCommand \spdiam { 0{} }
4519 {
4520     \mode_if_math:TF
4521     {
4522         \group_begin:
4523         \__spinttent_sp_rad_diam_exec:nn { diam } {#1}
4524         \group_end:
4525     }
4526     { \msg_error:nnn { spinttent } { need-math-mode } { \spdiam } }
4527 }

```

(End of definition for `\sprad` and `\spdiam`. These functions are documented on page ??.)

11.43 The command `\spcirc`

The user command `\spcirc` provides a semantic interface for a circle or a circumference, using the delimited-optional argument syntax `d()` already established by `\spmcd/\spmc` and `\spAfig/\spPfig`. The argument holds a required center point and an optional radius, separated by a comma. The radius is never required to declare its own kind via a key: its shape alone decides whether it is a pure number, a measure (number + unit), a bare letter, or a two-letter segment — reusing, respectively, `\spnum`, `\spunit`, and `\spside/\spmside` directly as sub-commands, rather than reimplementing any of their parsing.

11.43.1 Definition of variables for `\spcirc`

Shared outputs of `\__spinttent_luafun_geo_circ_parse_and_set:n`. `\l__spinttent_geo_luaset_circ_radio_type_str` holds one of *number*, *measure*, *label*, *segment*, or an empty string when no radius was given. `\l__spinttent_geo_luaset_circ_radio_raw_str` holds the corresponding raw text, ready to be forwarded to the sub-command that renders it.

```

4528 \str_new:N \l__spinttent_geo_luaset_circ_radio_type_str
4529 \str_new:N \l__spinttent_geo_luaset_circ_radio_raw_str

```

(End of definition for `\l__spinttent_geo_luaset_circ_radio_type_str` and `\l__spinttent_geo_luaset_circ_radio_raw_str`.)

```

\l__spintent_spcirc_mode_str
\l__spintent_spcirc_prefix_tl
\l__spintent_spcirc_print_sym_str
\l__spintent_spcirc_read_sty_str
\l__spintent_spcirc_radio_sty_str
\l__spintent_spcirc_sub_index_str
\l__spintent_spcirc_articulo_str

```

The variable `\l__spintent_spcirc_mode_str` stores the value set by the key `read-cmd`; the variable `\l__spintent_spcirc_prefix_tl` stores the value set by the key `prefix`. The variable `\l__spintent_spcirc_print_sym_str` stores the value set by the key `print-sym` (usual or odot). The variable `\l__spintent_spcirc_read_sty_str` stores the value set by the key `read-sty` (circun or circle). The variable `\l__spintent_spcirc_radio_sty_str` stores the value set by the key `radio-sty`, only meaningful when the radius is a segment. The variable `\l__spintent_spcirc_sub_index_str` stores the value set by the key `sub-index`. The variable `\l__spintent_spcirc_articulo_str` is set internally by `\__spintent_spcirc_word_and_article:` to `la` or `el`, matching the grammatical gender of the chosen word.

```

4530 \str_new:N \l__spintent_spcirc_mode_str
4531 \tl_new:N \l__spintent_spcirc_prefix_tl
4532 \str_new:N \l__spintent_spcirc_print_sym_str
4533 \str_new:N \l__spintent_spcirc_read_sty_str
4534 \str_new:N \l__spintent_spcirc_radio_sty_str
4535 \str_new:N \l__spintent_spcirc_sub_index_str
4536 \str_new:N \l__spintent_spcirc_articulo_str
4537 \tl_new:N \l__spintent_spcirc_read_arg_tl

```

(End of definition for `\l__spintent_spcirc_mode_str` and others.)

```
\l__spintent_spcirc_word_tl
```

Scratch variables used by `\__spintent_spcirc_process:n` to assemble the chosen word (circunferencia/círculo or the `read-arg` override) and the final literal `intent` string.

```
4538 \tl_new:N \l__spintent_spcirc_word_tl
```

(End of definition for `\l__spintent_spcirc_word_tl`.)

11.43.2 Definition of error messages for `\spcirc`

```
spcirc-invalid-arg
```

Raised when the argument does not match a single center point, optionally followed by a comma and a valid radius shape.

```

4539 \msg_new:nnnn { spintent } { spcirc-invalid-arg }
4540 {
4541   Invalid~argument~format~in~\token_to_str:N \spcirc:~'!'\msg_line_context:.
4542 }
4543 {
4544   See~the~documentation~of~\token_to_str:N \spcirc~for~the~accepted~argument~forms.
4545 }

```

(End of definition for `spcirc-invalid-arg`.)

11.43.3 Definition of keys for `\spcirc`

```

read-cmd
prefix
print-sym
read-sty
diameter
radio-sty
sub-index
read-sub
read-arg
silent-cmd
concept
spside
spmside
unknown

```

The key `print-sym` chooses the visual symbol: usual for a plain C, odot (default) for `\odot`. The key `read-sty` chooses the verbalized word and its article: `circun` (default) for «*la circunferencia*», `circle` for «*el círculo*». The key `radio-sty` chooses, only when the radius is a two-letter segment, whether it is rendered as the *object* (side, via `\spside`) or its *measure* (mside, default, via `\spmside`). The key `sub-index` sets a subscript on the symbol; the key `read-sub` controls whether it is read with the word «sub» or as a plain number, matching the same convention as `\spAfig`.

```

4546 \keys_define:nn { spintent / spcirc }
4547 {
4548   read-cmd      .choices:nn = { school , mathcat }
4549   {
4550     \int_case:nn { \l_keys_choice_int }
4551     {
4552       {1} { \str_set:Nn \l__spintent_spcirc_mode_str { school } }
4553       {2} { \str_set:Nn \l__spintent_spcirc_mode_str { mathcat } }
4554     }
4555   },
4556   read-cmd      .initial:n = school,
4557   read-cmd      .value_required:n = true,
4558   prefix        .code:n =
4559     { \__spintent_sanitize_affix:Nn \l__spintent_spcirc_prefix_tl {#1} },
4560   prefix        .initial:n = ,
4561   prefix        .value_required:n = true,
4562   print-sym     .choices:nn = { usual , odot }
4563   {
4564     \int_case:nn { \l_keys_choice_int }
4565     {
4566       {1} { \str_set:Nn \l__spintent_spcirc_print_sym_str { usual } }
4567       {2} { \str_set:Nn \l__spintent_spcirc_print_sym_str { odot } }
4568     }
4569   },
4570   print-sym     .initial:n = odot,

```

```

4571     print-sym      .value_required:n = true,
4572     read-sty       .choices:nn = { circun , circle }
4573     {
4574         \int_case:nn { \l_keys_choice_int }
4575         {
4576             {1} { \str_set:Nn \l__spintent_spcirc_read_sty_str { circun } }
4577             {2} { \str_set:Nn \l__spintent_spcirc_read_sty_str { circle } }
4578         }
4579     },
4580     read-sty       .initial:n = circun,
4581     read-sty       .value_required:n = true,
4582     diameter       .bool_set:N = \l__spintent_spcirc_diameter_bool,
4583     diameter       .initial:n = false,
4584     diameter       .value_required:n = true,
4585     radio-sty      .choices:nn = { side , mside }
4586     {
4587         \int_case:nn { \l_keys_choice_int }
4588         {
4589             {1} { \str_set:Nn \l__spintent_spcirc_radio_sty_str { side } }
4590             {2} { \str_set:Nn \l__spintent_spcirc_radio_sty_str { mside } }
4591         }
4592     },
4593     radio-sty      .initial:n = mside,
4594     radio-sty      .value_required:n = true,
4595     sub-index      .code:n =
4596     { \str_set:Nn \l__spintent_spcirc_sub_index_str {#1} },
4597     sub-index      .initial:n = ,
4598     sub-index      .value_required:n = true,
4599     read-sub       .bool_set:N = \l__spintent_spcirc_read_sub_bool,
4600     read-sub       .initial:n = false,
4601     read-sub       .value_required:n = true,
4602     read-arg       .code:n =
4603     { \__spintent_sanitize_affix:Nn \l__spintent_spcirc_read_arg_tl {#1} },
4604     read-arg       .initial:n = ,
4605     read-arg       .value_required:n = true,
4606     silent-cmd     .bool_set:N = \l__spintent_spcirc_silent_cmd_bool,
4607     silent-cmd     .initial:n = false,
4608     silent-cmd     .value_required:n = true,
4609     concept        .bool_set:N = \l__spintent_spcirc_concept_bool,
4610     concept        .initial:n = true,
4611     concept        .value_required:n = true,
4612     spside         .meta:nn = { spintent / spside } { #1 },
4613     spside         .value_required:n = true,
4614     spmside        .meta:nn = { spintent / spmside } { #1 },
4615     spmside        .value_required:n = true,
4616     unknown        .code:n =
4617     {
4618         \str_set:Nn \l__spintent_command_name_str { spcirc }
4619         \__spintent_unknown_keys_cmd:n {#1}
4620     },
4621 }

```

(End of definition for read-cmd and others.)

11.43.4 Internal functions for \spcirc

```

\l__spintent_spcirc_has_arg_bool
\l__spintent_spcirc_intent_tl
\l__spintent_spcirc_intent_arg_tl
\l__spintent_spcirc_connector_tl
\l__spintent_spcirc_connector_arg_tl
\l__spintent_spcirc_radio_arg_tl

```

`\l__spintent_spcirc_has_arg_bool` records whether the `d()` argument was given at all (`\spcirc` with no `(...)` at all has neither a center nor a radius). `\l__spintent_spcirc_intent_tl` holds the word (circunferencia or círculo, with an optional `sub-index` suffix) paired with the symbol. `\l__spintent_spcirc_connector_tl` holds de-centro-en, paired with the (center) group; the center is read through `\__spintent_mathmlarg_point:nnn`, referenced as `$pt`, not concatenated into either word — it can be subscripted or primed (e.g. O_{1}), as in the Euler circle) without breaking anything. The `_arg_tl` variables hold each word's final wrapped form; a third, `\l__spintent_spcirc_radio_arg_tl`, is spoken directly on the , delimiter after the center, replacing its own reading rather than pairing with a group.

```

4622 \bool_new:N \l__spintent_spcirc_has_arg_bool
4623 \tl_new:N \l__spintent_spcirc_intent_tl
4624 \tl_new:N \l__spintent_spcirc_intent_arg_tl
4625 \tl_new:N \l__spintent_spcirc_connector_tl
4626 \tl_new:N \l__spintent_spcirc_connector_arg_tl
4627 \tl_new:N \l__spintent_spcirc_radio_arg_tl

```

(End of definition for `\l__spintent_spcirc_has_arg_bool` and others.)

`\__spintent_spcirc_sym:` Typesets `\bigodot` or the plain letter C, according to `print-sym`.

```

4628 \cs_new_protected:Nn \__spintent_spcirc_sym:
4629 {
4630   \str_if_eq:VnTF \__spintent_spcirc_print_sym_str { odot }
4631   {
4632     \group_begin:
4633     \textstyle\bigodot
4634     \group_end:
4635   }
4636   { C }
4637 }

```

(End of definition for `\__spintent_spcirc_sym:`.)

`\__spintent_spcirc_word_and_article:` Sets `\l__spintent_spcirc_word_tl` to `read-arg` or `circunferencia/círculo` from `read-sty`, and `\l__spintent_spcirc_articulo_str` to the matching article, which always follows `read-sty` even when `read-arg` overrides the word.

```

4638 \cs_new_protected:Nn \__spintent_spcirc_word_and_article:
4639 {
4640   \tl_if_empty:NTF \__spintent_spcirc_read_arg_tl
4641   {
4642     \str_if_eq:VnTF \__spintent_spcirc_read_sty_str { circun }
4643     {
4644       \tl_set:Nn \l__spintent_spcirc_word_tl { circunferencia }
4645       \str_set:Nn \l__spintent_spcirc_articulo_str { la }
4646     }
4647     {
4648       \tl_set:Nn \l__spintent_spcirc_word_tl { círculo }
4649       \str_set:Nn \l__spintent_spcirc_articulo_str { el }
4650     }
4651   }
4652   {
4653     \tl_set:Nn \l__spintent_spcirc_word_tl { \__spintent_spcirc_read_arg_tl }
4654     \str_if_eq:VnTF \__spintent_spcirc_read_sty_str { circun }
4655     { \str_set:Nn \l__spintent_spcirc_articulo_str { la } }
4656     { \str_set:Nn \l__spintent_spcirc_articulo_str { el } }
4657   }
4658 }

```

(End of definition for `\__spintent_spcirc_word_and_article:`.)

`\__spintent_spcirc_radio_print:` Dispatches on `\l__spintent_geo_luaset_circ_radio_type_str`, reusing `\spnum/\spunit/\spside/\spmside` directly rather than reimplementing any parsing.

```

4659 \cs_new_protected:Nn \__spintent_spcirc_radio_print:
4660 {
4661   \str_case:Vn \__spintent_geo_luaset_circ_radio_type_str
4662   {
4663     { number } { \exp_args:No \spnum { \l__spintent_geo_luaset_circ_radio_raw_str } }
4664     { measure } { \exp_args:No \spunit { \l__spintent_geo_luaset_circ_radio_raw_str } }
4665     { label } { \l__spintent_geo_luaset_circ_radio_raw_str }
4666     { segment }
4667     {
4668       \str_if_eq:VnTF \__spintent_spcirc_radio_sty_str { side }
4669       { \exp_args:No \spside { \l__spintent_geo_luaset_circ_radio_raw_str } }
4670       { \exp_args:No \spmside { \l__spintent_geo_luaset_circ_radio_raw_str } }
4671     }
4672   }
4673 }

```

(End of definition for `\__spintent_spcirc_radio_print:`.)

`\__spintent_spcirc_build_concept:` Builds two words: `\l__spintent_spcirc_intent_tl` (via `\__spintent_spcirc_word_and_article:`, plus an optional `sub-index` suffix), paired with the symbol, and `\l__spintent_spcirc_connector_tl` (`de-centro-en`), paired with the (center) group — built even when `\l__spintent_spcirc_has_arg_bool` is `false`, though `\__spintent_spcirc_mathml:` never uses it in that case. Neither carries the center’s own text: it is read separately, by reference, through `\__spintent_mathmlarg_point:nnn` — so a subscripted or primed center (e.g. $O_{\{1\}}$, as in the Euler circle) is never an issue. `\l__spintent_spcirc_intent_arg_tl` (the symbol’s word) is bare — the group it wraps has nothing to reference, only a silenced symbol — while `\l__spintent_spcirc_connector_arg_tl` (the connector word) is `:prefix($pt)`: both when `concept` is `true`, prefixed with `prefix` when given. `\__spintent_spcirc_radio_arg` — spoken directly on the , delimiter, replacing its own reading rather than pairing with any group — is

the literal `_y-radio-`, or `_y-diámetro-` when `diameter` is `true`, read as its own phrase right before `\__spintent_spcirc_radio_print:`'s independent reading follows as the next sibling. `silent-cmd true` overrides all three with `_-` (the connector with `_( $pt)` instead — the center is always read), regardless of `read-arg`. With `concept false` and `read-arg` empty, the same `_-` (`$pt`) silencing applies; with `read-arg` given, none of the three is silenced instead — the connector and `y-radio/y-diámetro` words are fixed structural pieces, not customized by `read-arg`, but once a real word is being spoken there is nothing left to silence around it (same convention as `\__spintent_spside_process:nn`).

```

4674 \cs_new_protected:Nn \__spintent_spcirc_build_concept:
4675 {
4676   \__spintent_spcirc_word_and_article:
4677   \tl_set:Nc \__spintent_spcirc_intent_tl { \__spintent_spcirc_word_tl }
4678   \str_if_empty:NF \__spintent_spcirc_sub_index_str
4679   {
4680     \tl_put_right:Nc \__spintent_spcirc_intent_tl
4681     {
4682       -
4683       \bool_if:NT \__spintent_spcirc_read_sub_bool { sub - }
4684       \__spintent_spcirc_sub_index_str
4685     }
4686   }
4687   \tl_set:Nn \__spintent_spcirc_connector_tl { de-centro-en }
4688   \bool_if:NTF \__spintent_spcirc_silent_cmd_bool
4689   {
4690     \tl_set:Nn \__spintent_spcirc_intent_arg_tl { _- }
4691     \tl_set:Nc \__spintent_spcirc_connector_arg_tl { _( $ pt ) }
4692     \tl_set:Nn \__spintent_spcirc_radio_arg_tl { _- }
4693   }
4694   {
4695     \bool_if:NTF \__spintent_spcirc_concept_bool
4696     {
4697       \tl_set:Nc \__spintent_spcirc_intent_arg_tl
4698       {
4699         \tl_if_empty:NF \__spintent_spcirc_prefix_tl
4700         { \tl_use:N \__spintent_spcirc_prefix_tl - }
4701         \__spintent_spcirc_intent_tl :prefix
4702       }
4703       \tl_set:Nc \__spintent_spcirc_connector_arg_tl
4704       { \__spintent_spcirc_connector_tl :prefix( $ pt ) }
4705       \bool_if:NTF \__spintent_spcirc_diameter_bool
4706       { \tl_set:Nn \__spintent_spcirc_radio_arg_tl { _y-diámetro- } }
4707       { \tl_set:Nn \__spintent_spcirc_radio_arg_tl { _y-radio- } }
4708     }
4709     {
4710       \tl_if_empty:NF \__spintent_spcirc_read_arg_tl
4711       {
4712         \tl_set:Nn \__spintent_spcirc_intent_arg_tl { _- }
4713         \tl_set:Nc \__spintent_spcirc_connector_arg_tl { _( $ pt ) }
4714         \tl_set:Nn \__spintent_spcirc_radio_arg_tl { _- }
4715       }
4716       {
4717         \tl_set:Nc \__spintent_spcirc_intent_arg_tl { \__spintent_spcirc_intent_tl }
4718         \tl_set:Nc \__spintent_spcirc_connector_arg_tl
4719         { \__spintent_spcirc_connector_tl :prefix( $ pt ) }
4720         \bool_if:NTF \__spintent_spcirc_diameter_bool
4721         { \tl_set:Nn \__spintent_spcirc_radio_arg_tl { _y-diámetro- } }
4722         { \tl_set:Nn \__spintent_spcirc_radio_arg_tl { _y-radio- } }
4723       }
4724     }
4725   }
4726 }

```

(End of definition for `\__spintent_spcirc_build_concept:`)

`\__spintent_spcirc_process:n` Receives the `d()` argument in `'#1'`, an explicit empty group when omitted (`\spcirc` itself converts `-NoValue-` to `{ }` before calling `\__spintent_spcirc_exec:nn`) — `\__spintent_spcirc_has_arg_bool` set to `false` in that case, and `\__spintent_luafun_geo_circ_parse_and_set:n` never called at all — there is nothing to parse. Otherwise calls it, reports `spcirc-invalid-arg` on failure, then delegates to `\__spintent_spcirc_mathml:`, which calls `\__spintent_spcirc_build_concept:` itself.

```

4727 \cs_new_protected:Nn \__spintent_spcirc_process:n
4728 {

```

```

4729 \tl_if_empty:nTF {#1}
4730 {
4731   \bool_set_false:N \l__spintenc_spcirc_has_arg_bool
4732 }
4733 {
4734   \bool_set_true:N \l__spintenc_spcirc_has_arg_bool
4735   \__spintenc_luafun_geo_circ_parse_and_set:n { \exp_not:n {#1} }
4736   \str_if_eq:VnT \l__spintenc_geo_luasets_error_str { true }
4737   {
4738     \msg_error:nne { spintenc } { spirc-invalid-arg } { \exp_not:n {#1} }
4739   }
4740 }
4741 \__spintenc_spcirc_mathml:
4742 }

```

(End of definition for `\__spintenc_spcirc_process:n`.)

`\__spintenc_spcirc_mathml:` Calls `\__spintenc_spcirc_build_concept:`, then wraps the symbol (`\l__spintenc_spcirc_intent_arg_tl`) in its own native `\MathMLintent` — this alone is the whole result when `\l__spintenc_spcirc_has_arg_bool` is `false` (`\spirc` with no `(...)` at all: no center, no radius).

Otherwise, the `(center)` group (`\l__spintenc_spcirc_connector_arg_tl`) follows as a separate sibling, never nested inside the symbol's own `\MathMLintent` — or MathCAT falls back to its own structural reading of the underlying `<mover>/<msub>` instead, the same problem already found for `\spangle`'s symbol and `\sparc`'s accent. When a radius is present, the `,` delimiter after the center carries `\l__spintenc_spcirc_radio_arg_tl` directly (replacing its own reading, not paired with any group), and `\__spintenc_spcirc_radio_print:` follows as an ordinary sibling right after — wrapping it in another `\MathMLintent` would lose the reading of whatever it produces (itself a native `\MathMLintent`, from `\spnum/\spunit`, nested inside another one does not compose).

The symbol and, when `sub-index` is given, its subscript number are each silenced with `\__spintenc_luafun_wrap_mrow_intent_arg_tl` *separately* — one queue entry per leaf. The two are reached differently by the shared `mathml_filter` call-back's recursive lookup (the symbol via `nucleus`, the subscript via `sub`), so a single entry covering both leaves nothing registered for the second one, which the recursion then assigns whatever comes next in the queue instead — shifting every claim after it by one. The `(` delimiter is silenced the same way, but *without* the usual `{...}` around the character: `luamml` only keeps a delimiter's own math class (giving `<mo>` instead of `<mi>`, needed for MathCAT to read the group at all) when it is not itself sitting inside a brace group.

The final `)` — following `\__spintenc_spcirc_radio_print:`, whose own output the shared queue does not reliably skip over — is typeset as `\rparen` inside its own native `\MathMLintent{:silent}` instead of a bare `)`: `\rparen` keeps its own math class through the wrapping, unlike a bare delimiter character, and this sits outside the shared queue entirely, so nothing in between can claim an entry meant for it.

The center itself is read through `\__spintenc_mathmlarg_point:nnn`, referenced as `$pt`.

```

4743 \cs_new_protected:Nn \__spintenc_spcirc_mathml:
4744 {
4745   \__spintenc_invisible_sep: % (luamml issues #26)
4746   \__spintenc_spcirc_build_concept:
4747   \MathMLintent { \l__spintenc_spcirc_intent_arg_tl }
4748   {
4749     \__spintenc_luafun_inner_sep:
4750     \__spintenc_luafun_wrap_mrow_intent_arg:nn
4751     { } { intent = ":silent" }
4752     { \__spintenc_spcirc_sym: }
4753     \str_if_empty:NF \l__spintenc_spcirc_sub_index_str
4754     {
4755       \c_math_subscript_token
4756       {
4757         \__spintenc_luafun_wrap_mrow_intent_arg:nn
4758         { } { intent = ":silent" }
4759         { \l__spintenc_spcirc_sub_index_str }
4760       }
4761     }
4762   }
4763   \bool_if:NT \l__spintenc_spcirc_has_arg_bool
4764   {
4765     \str_if_empty:NTF \l__spintenc_geo_luasets_circ_radio_type_str
4766     {
4767       \MathMLintent { \l__spintenc_spcirc_connector_arg_tl }
4768       {
4769         \__spintenc_luafun_inner_sep:
4770         \__spintenc_luafun_wrap_mrow_intent_arg:nn { } { intent = ":silent" } (
4771         \__spintenc_mathmlarg_point:nnV { pt } { spirc } \l__spintenc_geo_luasets_points_

```

```

4772         \__spintent_luafun_wrap_mrow_intent_arg:nn { } { intent = ":silent" } )
4773     }
4774 }
4775 {
4776     \MathMLintent { \__spintent_spcirc_connector_arg_tl }
4777     {
4778         \__spintent_luafun_inner_sep:
4779         \__spintent_luafun_wrap_mrow_intent_arg:nn { } { intent = ":silent" } (
4780             \__spintent_mathmlarg_point:nnV { pt } { spcirc } \__spintent_geo_luaseta_points_
4781         )
4782         \MathMLintent { \__spintent_spcirc_radio_arg_tl } { , }
4783         \__spintent_spcirc_radio_print:
4784         \MathMLintent { :silent } { \rparen }
4785     }
4786 }
4787 }

```

(End of definition for `\__spintent_spcirc_mathml:`.)

`\__spintent_spcirc_exec:nn` The function `\__spintent_spcirc_exec:nn` receives the optional keys in #1 and the argument in #2, delegating the rendering to `\__spintent_spcirc_print:n`.

```

4788 \cs_new_protected:Nn \__spintent_spcirc_exec:nn
4789 {
4790     \keys_set:nn { spintent / spcirc } { #1 }
4791     \__spintent_spcirc_process:n { #2 }
4792 }

```

(End of definition for `\__spintent_spcirc_exec:nn`.)

`\spcirc` The public command `\spcirc` enforces math mode, opens a local group, and delegates execution to `\__spintent_spcirc_exec:nn`. It follows the same `d()`-argument pattern as `\spmcld/\spmcm` and `\spAfig/\spPfig`; an omitted radius forwards an explicit empty group rather than the `-NoValue-` marker.

```

4793 \NewDocumentCommand \spcirc { 0{ } d() }
4794 {
4795     \mode_if_math:TF
4796     {
4797         \group_begin:
4798         \tl_if_no_value:nTF {#2}
4799         { \__spintent_spcirc_exec:nn { #1 } { } }
4800         { \__spintent_spcirc_exec:nn { #1 } { #2 } }
4801         \group_end:
4802     }
4803     { \msg_error:nnn { spintent } { need-math-mode } { \spcirc } }
4804 }

```

(End of definition for `\spcirc`. This function is documented on page ??.)

11.44 The commands `\spAcirc` and `\spPcirc`

The user commands `\spAcirc` and `\spPcirc` typeset the area and the perimeter of a circle or a circumference. The argument follows `\spcirc`'s own point-and-radius grammar for a real center (with an optional radius); when no comma is present and no valid center is found, it falls back to a bare number/letter shortcut, reusing the same Lua entry point as `\spAfig/\spPfig`. A table letter matched by that fallback is rejected, since it has no meaning for a circle.

11.44.1 Definition of variables for `\spAcirc` and `\spPcirc`

These variables store the value set by each corresponding key: `read-cmd`, `print-sym`, `read-sty`, `radio-sty`, `sub-index`, `prefix` and `read-arg`, respectively.

```

\__spintent_spAcirc_mode_str
\__spintent_spPcirc_mode_str
\__spintent_spAcirc_print_sym_str
\__spintent_spPcirc_print_sym_str
\__spintent_spAcirc_read_sty_str
\__spintent_spPcirc_read_sty_str
\__spintent_spAcirc_radio_sty_str
\__spintent_spPcirc_radio_sty_str
\__spintent_spAcirc_sub_index_str
\__spintent_spPcirc_sub_index_str
\__spintent_spAcirc_prefix_tl
\__spintent_spPcirc_prefix_tl
\__spintent_spAcirc_read_arg_tl
\__spintent_spPcirc_read_arg_tl

```

(End of definition for `\__spintent_spAcirc_mode_str` and others.)

`\l__spintent_geo_circfig_mode_str` The variable `\l__spintent_geo_circfig_mode_str` stores whether the argument was resolved as a real circle (`circle`) or as the bare number/letter shortcut (`bare`).

```
4815 \str_new:N \l__spintent_geo_circfig_mode_str
```

(End of definition for `\l__spintent_geo_circfig_mode_str`.)

11.44.2 Definition of error messages for `\spAcirc` and `\spPcirc`

`spAcirc-invalid-arg` The error message shown when the argument does not match any of the accepted forms: empty, a center point (optionally followed by a comma and a radius), or a bare number/letter.

`spPcirc-invalid-arg`

```
4816 \clist_map_inline:nn { Acirc , Pcirc }
4817 {
4818   \msg_new:nnnn { spintent } { sp #1 -invalid-arg }
4819   {
4820     Invalid~argument~in~##1:~'##2'~\msg_line_context:.
4821   }
4822   {
4823     See~the~documentation~of~##1~for~the~accepted~argument.
4824   }
}
```

(End of definition for `spAcirc-invalid-arg` and `spPcirc-invalid-arg`.)

11.44.3 Definition of keys for `\spAcirc` and `\spPcirc`

`read-cmd` We define the shared (*keys*) `read-cmd`, `prefix`, `print-sym`, `read-sty`, `concept`, `sub-index`, `read-sub`, `read-arg` and `silent-cmd`.

`prefix`

```
4825 \keys_define:nn { spintent / sp #1 }
4826 {
4827   read-cmd .choices:nn = { school , mathcat }
4828   {
4829     \int_case:nn { \l_keys_choice_int }
4830     {
4831       {1} { \str_set:cn { \l__spintent_sp #1 _mode_str } { school } }
4832       {2} { \str_set:cn { \l__spintent_sp #1 _mode_str } { mathcat } }
4833     }
4834   },
4835   read-cmd .initial:n = school,
4836   read-cmd .value_required:n = true,
4837   read-cmd / unknown .code:n =
4838     \msg_error:nnee { spintent } { unknown-choice }
4839     { read-cmd } { school,~mathcat } { \exp_not:n {##1} },
4840   prefix .code:n =
4841     { \l__spintent_sanitize_affix:cn { \l__spintent_sp #1 _prefix_tl } {##1} },
4842   prefix .initial:n = ,
4843   prefix .value_required:n = true,
4844   print-sym .choices:nn = { usual , odot }
4845   {
4846     \int_case:nn { \l_keys_choice_int }
4847     {
4848       {1} { \str_set:cn { \l__spintent_sp #1 _print_sym_str } { usual } }
4849       {2} { \str_set:cn { \l__spintent_sp #1 _print_sym_str } { odot } }
4850     }
4851   },
4852   print-sym .initial:n = odot,
4853   print-sym .value_required:n = true,
4854   print-sym / unknown .code:n =
4855     \msg_error:nnee { spintent } { unknown-choice }
4856     { print-sym } { usual,~odot } { \exp_not:n {##1} },
4857   read-sty .choices:nn = { circun , circle }
4858   {
4859     \int_case:nn { \l_keys_choice_int }
4860     {
4861       {1} { \str_set:cn { \l__spintent_sp #1 _read_sty_str } { circun } }
4862       {2} { \str_set:cn { \l__spintent_sp #1 _read_sty_str } { circle } }
4863     }
4864   },
4865   read-sty .initial:n = circun,
4866   read-sty .value_required:n = true,
4867   concept .bool_set:c = { \l__spintent_sp #1 _concept_bool },
4868   concept .initial:n = true,
4869   concept .value_required:n = true,
4870   sub-index .code:n =
4871     { \str_set:cn { \l__spintent_sp #1 _sub_index_str } {##1} },
```

```

4872     sub-index          .initial:n = ,
4873     sub-index          .value_required:n = true,
4874     read-sub           .bool_set:c = { l__spintent_sp #1 _read_sub_bool },
4875     read-sub           .initial:n = false,
4876     read-sub           .value_required:n = true,
4877     read-arg           .code:n =
4878       { l__spintent_sanitize_affix:cn { l__spintent_sp #1 _read_arg_tl } {##1} },
4879     read-arg           .initial:n = ,
4880     read-arg           .value_required:n = true,
4881     silent-cmd         .bool_set:c = { l__spintent_sp #1 _silent_cmd_bool },
4882     silent-cmd         .initial:n = false,
4883     silent-cmd         .value_required:n = true,
4884     unknown            .code:n =
4885       {
4886         \str_set:Nn \l__spintent_command_name_str { sp #1 }
4887         \__spintent_unknown_keys_cmd:n {##1}
4888       },
4889   }
4890 }

```

(End of definition for read-cmd and others.)

`\l__spintent_spcircfig_short_bool` `\l__spintent_spcircfig_op_tl` `\l__spintent_spcircfig_intent_tl` `\l__spintent_spcircfig_intent_arg_tl`

`\l__spintent_spcircfig_short_bool` records whether the argument resolved as the short number/letter form (via `\__spintent_luafun_geo_afig_parse_and_set:n/\__spintent_luafun_geo_pfig_parse_and_set:n`) the same entry point (`\spAfig/\spPfig` use) rather than a real circle. `\l__spintent_spcircfig_op_tl` holds `área` or `perímetro`. `\l__spintent_spcircfig_intent_tl` holds the full spoken phrase: `\l__spintent_spcircfig_del_word_tl` (via `\__spintent_spcircfig_del_word:n`: the word, contracted with `del-/de-la-`, or `read-arg`), an optional `sub-index` suffix, and, when a center is given, `-con-centro-en` — the center itself is never concatenated into it: it is read separately, by reference, through `\__spintent_mathmlarg_point:nnn`, so a subscripted or primed center (e.g. `O_{1}`), as in the Euler circle) is never an issue.

```

4891 \bool_new:N \l__spintent_spcircfig_short_bool
4892 \tl_new:N \l__spintent_spcircfig_op_tl
4893 \tl_new:N \l__spintent_spcircfig_del_word_tl
4894 \tl_new:N \l__spintent_spcircfig_intent_tl
4895 \tl_new:N \l__spintent_spcircfig_intent_arg_tl

```

(End of definition for `\l__spintent_spcircfig_short_bool` and others.)

`\__spintent_spcircfig_sym:n` Typesets `\bigodot` or the plain letter C, according to `print-sym`. Receives the short command name in ‘`#1`’.

```

4896 \cs_new_protected:Nn \__spintent_spcircfig_sym:n
4897 {
4898   \str_if_eq:vnTF { l__spintent_sp #1 _print_sym_str } { odot }
4899   { \bigodot }
4900   { C }
4901 }

```

(End of definition for `\__spintent_spcircfig_sym:n`.)

`\__spintent_spcircfig_word_and_article:n` Sets `\l__spintent_spcirc_word_tl` to `read-arg` or `circunferencia/círculo` from `read-sty`, and `\l__spintent_spcirc_articulo_str` to the matching article, which always follows `read-sty` even when `read-arg` overrides the word. Receives the short command name in ‘`#1`’.

```

4902 \cs_new_protected:Nn \__spintent_spcircfig_word_and_article:n
4903 {
4904   \str_if_eq:vnTF { l__spintent_sp #1 _read_sty_str } { circun }
4905   { \str_set:Nn \l__spintent_spcirc_articulo_str { la } }
4906   { \str_set:Nn \l__spintent_spcirc_articulo_str { el } }
4907   \tl_if_empty:cTF { l__spintent_sp #1 _read_arg_tl }
4908   {
4909     \str_if_eq:vnTF { l__spintent_sp #1 _read_sty_str } { circun }
4910     { \tl_set:Nn \l__spintent_spcirc_word_tl { circunferencia } }
4911     { \tl_set:Nn \l__spintent_spcirc_word_tl { círculo } }
4912   }
4913   {
4914     \tl_set:Ne \l__spintent_spcirc_word_tl
4915     {
4916       \tl_use:c { l__spintent_sp #1 _read_arg_tl }
4917     }
4918   }
4919 }

```

(End of definition for `\__spintent_spcircfig_word_and_article:n`.)

`\__spintent_spcircfig_del_word:n` Sets `\__spintent_spcircfig_del_word_tl` to `\__spintent_spcircfig_word_and_article:n`'s word, prefixed with `del-` or `de-la-` — contracted, not `de-el-`, since a screen reader does not contract that on its own. Receives the short command name in `#1`.

```

4920 \cs_new_protected:Nn \__spintent_spcircfig_del_word:n
4921 {
4922   \__spintent_spcircfig_word_and_article:n {#1}
4923   \str_if_eq:VnTF \__spintent_spcirc_articulo_str { el }
4924   {
4925     \tl_set:Ne \__spintent_spcircfig_del_word_tl { del- \__spintent_spcirc_word_tl }
4926   }
4927   {
4928     \tl_set:Ne \__spintent_spcircfig_del_word_tl { de-la- \__spintent_spcirc_word_tl }
4929   }
4930 }

```

(End of definition for `\__spintent_spcircfig_del_word:n`.)

`\__spintent_spcircfig_build_short:n` Handles the short number/letter case: builds `\__spintent_spcircfig_intent_arg_tl` as `\__spintent_spcircfig_intent_arg_tl` (`ber word`), wrapped in bare `:prefix` (no reference — there is nothing to point to), or `-` when `silent-cmd` is `true` or `concept` is `false`. Receives the short command name in `#1`.

```

4931 \cs_new_protected:Nn \__spintent_spcircfig_build_short:n
4932 {
4933   \bool_if:cTF { \__spintent_sp #1 _silent_cmd_bool }
4934   {
4935     \tl_set:Nn \__spintent_spcircfig_intent_arg_tl { - }
4936   }
4937   {
4938     \bool_if:cTF { \__spintent_sp #1 _concept_bool }
4939     {
4940       \__spintent_spcircfig_del_word:n {#1}
4941       \tl_set:Ne \__spintent_spcircfig_intent_arg_tl
4942       {
4943         \__spintent_spcircfig_op_tl - \__spintent_spcircfig_del_word_tl -
4944         \bool_if:cT { \__spintent_sp #1 _read_sub_bool } { sub- }
4945         \__spintent_geo_luaset_sub_spoken_str :prefix
4946       }
4947     }
4948     {
4949       \tl_set:Nn \__spintent_spcircfig_intent_arg_tl { - }
4950     }
4951   }
4952 }

```

(End of definition for `\__spintent_spcircfig_build_short:n`.)

`\__spintent_spcircfig_finish_intent:nn` Appends an optional `sub-index` suffix and, when `#2` is non-empty, `-con-centro-en` to `\__spintent_spcircfig_intent_arg_tl` — shared by both branches of `\__spintent_spcircfig_build_concept:nn`, after either one has set the word itself. Receives the short command name in `#1` and the argument in `#2`.

```

4953 \cs_new_protected:Nn \__spintent_spcircfig_finish_intent:nn
4954 {
4955   \str_if_empty:cF { \__spintent_sp #1 _sub_index_str }
4956   {
4957     \tl_put_right:Ne \__spintent_spcircfig_intent_tl
4958     {
4959       -
4960       \bool_if:cT { \__spintent_sp #1 _read_sub_bool } { sub- }
4961       \str_use:c { \__spintent_sp #1 _sub_index_str }
4962     }
4963   }
4964   \tl_if_empty:nF {#2}
4965   {
4966     \tl_put_right:Nn \__spintent_spcircfig_intent_tl { -con-centro-en }
4967   }
4968 }

```

(End of definition for `\__spintent_spcircfig_finish_intent:nn`.)

`\__spintent_spcircfig_build_concept:nn` Builds `\__spintent_spcircfig_intent_arg_tl`. `-` when `silent-cmd` is `true`, or when `false` and `concept` is `false` with `read-arg` empty (`( $\$pt$ )` instead when `#2` is non-empty — the center is still read either way). Otherwise `\__spintent_spcircfig_intent_tl:prefix` — with (`$\$pt$`) appended when `#2` is non-empty — prefixed with `prefix` when given, where `\__spintent_spcircfig_intent_tl` is:

with `concept true`, `\l__spintent_spcircfig_op_tl`- `\l__spintent_spcircfig_del_word_tl` (via `\l__spintent_spcircfig_del_word:n`: the word, contracted with `del-/de-la-`, or `read-arg` the same way); with `false` and `read-arg` given, `read-arg` verbatim instead, with `\l__spintent_spcircfig_op_tl` dropped entirely — `área/perímetro` is itself the concept `concept` toggles, not the `-con-centro-en` that follows, which always stays (it identifies which figure, not the concept). No automatic article either — the word (and any article it needs) is the user's to write, same convention as `\l__spintent_spcirc_process:n`. Either way, an optional `sub-index` suffix and, when `#2` is non-empty, `-con-centro-en` follow. Receives the short command name in `'#1'` and the argument in `'#2'`.

```

4969 \cs_new_protected:Nn \l__spintent_spcircfig_build_concept:nn
4970 {
4971   \bool_if:cTF { \l__spintent_sp #1 _silent_cmd_bool }
4972   {
4973     \tl_if_empty:nTF {#2}
4974     { \tl_set:Nn \l__spintent_spcircfig_intent_arg_tl { _- } }
4975     { \tl_set:Ne \l__spintent_spcircfig_intent_arg_tl { _ ( $ pt ) } }
4976   }
4977   {
4978     \bool_if:cTF { \l__spintent_sp #1 _concept_bool }
4979     {
4980       \l__spintent_spcircfig_del_word:n {#1}
4981       \tl_set:Ne \l__spintent_spcircfig_intent_tl
4982       {
4983         \l__spintent_spcircfig_op_tl - \l__spintent_spcircfig_del_word_tl
4984       }
4985       \l__spintent_spcircfig_finish_intent:nn {#1} {#2}
4986       \tl_set:Ne \l__spintent_spcircfig_intent_arg_tl
4987       {
4988         \tl_if_empty:cF { \l__spintent_sp #1 _prefix_tl }
4989         {
4990           \tl_use:c { \l__spintent_sp #1 _prefix_tl } -
4991         }
4992         \l__spintent_spcircfig_intent_tl :prefix
4993         \tl_if_empty:nF {#2} { ( $ pt ) }
4994       }
4995     }
4996     {
4997       \tl_if_empty:cTF { \l__spintent_sp #1 _read_arg_tl }
4998       {
4999         \tl_if_empty:nTF {#2}
5000         { \tl_set:Nn \l__spintent_spcircfig_intent_arg_tl { _- } }
5001         { \tl_set:Ne \l__spintent_spcircfig_intent_arg_tl { _ ( $ pt ) } }
5002       }
5003       {
5004         \tl_set:Ne \l__spintent_spcircfig_intent_tl
5005         { \tl_use:c { \l__spintent_sp #1 _read_arg_tl } }
5006         \l__spintent_spcircfig_finish_intent:nn {#1} {#2}
5007         \tl_set:Ne \l__spintent_spcircfig_intent_arg_tl
5008         {
5009           \l__spintent_spcircfig_intent_tl :prefix
5010           \tl_if_empty:nF {#2} { ( $ pt ) }
5011         }
5012       }
5013     }
5014   }
5015 }

```

(End of definition for `\l__spintent_spcircfig_build_concept:nn`.)

`\l__spintent_spcircfig_process:nn`

Receives the short command name in `'#1'` and the argument in `'#2'`. Sets `\l__spintent_spcircfig_op_tl` to `área/perímetro`. With `#2` empty, `\l__spintent_spcircfig_short_bool` is set `false` and nothing else is parsed. With a comma in `#2`, reports `sp#1-invalid-arg` immediately — `\@@_luafun_geo_circ_parse_and_set:` (shared with `\spcirc`) still accepts a second, comma-separated part as a generic `label`-type radius, matching almost any text, so it would never itself report an error for a comma-containing argument here, where a comma is never meaningful at all. Without a comma, calls `\l__spintent_luafun_geo_circ_parse_and_set:n`; on error, retries through `\l__spintent_luafun_geo_afig_parse_and_set:n/\l__spintent_luafun_geo_pfig_parse_and_set:n` (the same entry point `\spAfig/\spPfig` use) for the short number/letter form, rejecting a table-letter match (not meaningful for a circle) back to an error. Reports `sp#1-invalid-arg` on failure either way, then delegates to `\l__spintent_spcircfig_build_short:n/\l__spintent_spcircfig_build_concept:nn` and `\l__spintent_spcircfig_mathml:nn`.

- Unlike `\spcirt`, there is no radius/diameter here at all: a formula's left-hand side (`A_0`) names the figure, it does not carry the values needed to compute it — those belong on the right-hand side, elsewhere in the document.

```

5016 \cs_new_protected:Nn \__spinttent_spcircfig_process:nn
5017 {
5018   \str_if_eq:eeTF {#1} { Acirc }
5019   { \tl_set:Nn \__spinttent_spcircfig_op_tl { área } }
5020   { \tl_set:Nn \__spinttent_spcircfig_op_tl { perímetro } }
5021   \tl_if_empty:nTF {#2}
5022   {
5023     \bool_set_false:N \__spinttent_spcircfig_short_bool
5024   }
5025   {
5026     \bool_set_false:N \__spinttent_spcircfig_short_bool
5027     \tl_if_in:nnTF {#2} { , }
5028     {
5029       \msg_error:nnee { spinttent } { sp #1 -invalid-arg }
5030       { \c_backslash_str sp #1 } { \exp_not:n {#2} }
5031     }
5032     {
5033       \__spinttent_luafun_geo_circ_parse_and_set:n { \exp_not:n {#2} }
5034       \str_if_eq:VnT \__spinttent_geo_luaaset_error_str { true }
5035       {
5036         \str_if_eq:eeTF {#1} { Acirc }
5037         { \__spinttent_luafun_geo_afig_parse_and_set:n { \exp_not:n {#2} } }
5038         { \__spinttent_luafun_geo_pfig_parse_and_set:n { \exp_not:n {#2} } }
5039         \str_if_eq:VnF \__spinttent_geo_luaaset_error_str { true }
5040         {
5041           \str_if_empty:NTF \__spinttent_geo_luaaset_letra_word_str
5042           { \bool_set_true:N \__spinttent_spcircfig_short_bool }
5043           { \str_set:Nn \__spinttent_geo_luaaset_error_str { true } }
5044         }
5045       }
5046       \bool_if:NF \__spinttent_spcircfig_short_bool
5047       {
5048         \str_if_eq:VnT \__spinttent_geo_luaaset_error_str { true }
5049         {
5050           \msg_error:nnee { spinttent } { sp #1 -invalid-arg }
5051           { \c_backslash_str sp #1 } { \exp_not:n {#2} }
5052         }
5053       }
5054     }
5055   }
5056   \bool_if:NTF \__spinttent_spcircfig_short_bool
5057   { \__spinttent_spcircfig_build_short:n {#1} }
5058   { \__spinttent_spcircfig_build_concept:nn {#1} {#2} }
5059   \__spinttent_spcircfig_mathml:nn { #1 } { #2 }
5060 }

```

(End of definition for `\__spinttent_spcircfig_process:nn`.)

`\__spinttent_spcircfig_mathml:nn` Renders `\__spinttent_spcircfig_intent_arg_tl`, already built by `\__spinttent_spcircfig_process:nn`. Three cases: the short case prints the symbol with the short value as its own subscript; an empty `#2` prints the symbol alone; a real center prints the symbol (plus optional `sub-index` subscript) and the center between parentheses. In every case a single native `\MathMLintent` wraps `\__spinttent_mathcal:n{⟨A | P⟩}` and the whole subscript together — splitting the symbol and the center into separate `\MathMLintent` siblings inside the same subscript was tried and reads as `<msub>`'s own native structural narration instead. The center is read through `\__spinttent_mathmlarg_point:nnn`, referenced as `$pt` (same convention as `\spcirt`). Receives the short command name in `#1` and the argument in `#2`.

```

5061 \cs_new_protected:Nn \__spinttent_spcircfig_mathml:nn
5062 {
5063   \__spinttent_invisible_sep: % (luamml issues #26)
5064   \MathMLintent { \__spinttent_spcircfig_intent_arg_tl }
5065   {
5066     \__spinttent_luafun_inner_sep:
5067     \__spinttent_luafun_wrap_mrow_intent_arg:nn
5068     { } { intent = ":silent" }
5069   }
5070   \str_if_eq:eeTF {#1} { Acirc } { \__spinttent_mathcal:n { A } } { \__spinttent_mathcal:n {
5071   }
5072   \bool_if:NTF \__spinttent_spcircfig_short_bool
5073   {

```

```

5074         \c_math_subscript_token
5075         {
5076             \__spintenc_spcircfig_sym:n {#1}
5077             \c_math_subscript_token { \__spintenc_geo_luaset_print_tl }
5078         }
5079     }
5080     {
5081         \c_math_subscript_token
5082         {
5083             \MathMLintenc { :silent } { \__spintenc_spcircfig_sym:n {#1} }
5084             \str_if_empty:cF { \__spintenc_sp #1 _sub_index_str }
5085             {
5086                 \c_math_subscript_token
5087                 {
5088                     \MathMLintenc { :silent }
5089                     { \str_use:c { \__spintenc_sp #1 _sub_index_str } }
5090                 }
5091             }
5092             \tl_if_empty:nF {#2}
5093             {
5094                 \MathMLintenc { :silent } { \lparen }
5095                 \__spintenc_mathmlarg_point:nnV { pt } { sp #1 } \__spintenc_geo_luaset_point
5096                 \MathMLintenc { :silent } { \rparen }
5097             }
5098         }
5099     }
5100 }
5101 }

```

(End of definition for __spintenc_spcircfig_mathml:nn.)

__spintenc_spcircfig_exec:nnn

The function __spintenc_spcircfig_exec:nnn receives the short name of the command in #1, the optional keys in #2, and the argument in #3, delegating the rendering to __spintenc_spcircfig_process:nn.

```

5102 \cs_new_protected:Nn \__spintenc_spcircfig_exec:nnn
5103 {
5104     \keys_set:nn { spintenc / sp #1 } { #2 }
5105     \__spintenc_spcircfig_process:nn { #1 } { #3 }
5106 }

```

(End of definition for __spintenc_spcircfig_exec:nnn.)

\spAcirc

Both public commands \spAcirc and \spPcirc enforce math mode, open a local group, and delegate execution to __spintenc_spcircfig_exec:nnn.

\spPcirc

```

5107 \NewDocumentCommand \spAcirc { 0{} d() }
5108 {
5109     \mode_if_math:TF
5110     {
5111         \group_begin:
5112         \tl_if_novalue:nTF {#2}
5113         { \__spintenc_spcircfig_exec:nnn { Acirc } { #1 } { } }
5114         { \__spintenc_spcircfig_exec:nnn { Acirc } { #1 } { #2 } }
5115         \group_end:
5116     }
5117     { \msg_error:nnn { spintenc } { need-math-mode } { \spAcirc } }
5118 }
5119 \NewDocumentCommand \spPcirc { 0{} d() }
5120 {
5121     \mode_if_math:TF
5122     {
5123         \group_begin:
5124         \tl_if_novalue:nTF {#2}
5125         { \__spintenc_spcircfig_exec:nnn { Pcirc } { #1 } { } }
5126         { \__spintenc_spcircfig_exec:nnn { Pcirc } { #1 } { #2 } }
5127         \group_end:
5128     }
5129     { \msg_error:nnn { spintenc } { need-math-mode } { \spPcirc } }
5130 }

```

(End of definition for \spAcirc and \spPcirc. These functions are documented on page ??.)

11.45 Finish package

Finish package implementation.

```
5131 \file_input_stop:  
5132 \endpackage
```

12 Índice de la Implementación

The *italic* numbers denote the pages where the corresponding entry is described, the numbers underlined and all others indicate the line on which they are implemented in the package code.

A	
<code>\angle</code>	<u>101</u>
C	
<code>cifras-sep</code>	<u>269</u> , <u>554</u> , <u>827</u> , <u>1780</u> , <u>1851</u> , <u>2263</u>
Document class:	
<code>l3doc</code>	<u>29</u>
<code>cmd-key-unknown</code>	<u>189</u>
<code>cmd-key-value-unknown</code>	<u>189</u>
Commands provide by spintent :	
<code>\setspintent</code>	<u>32</u>
<code>\spmoney</code>	<u>46</u>
<code>\spnum</code>	<u>36</u>
<code>\spsiglo</code>	<u>55</u> , <u>58</u>
<code>\spunit</code>	<u>41</u>
<code>concept</code> ...	<u>3190</u> , <u>3395</u> , <u>3626</u> , <u>3779</u> , <u>3955</u> , <u>4328</u> , <u>4546</u> , <u>4825</u>
<code>currency</code>	<u>827</u>
<code>currency-no-subunits</code>	<u>796</u>
D	
<code>diameter</code>	<u>4546</u>
<code>dolar-math</code>	<u>827</u>
I	
<code>inline-numeric-denominator</code>	<u>532</u>
<code>invalid-angle-format</code>	<u>2213</u>
<code>invalid-century-format</code>	<u>1223</u>
<code>invalid-currency</code>	<u>796</u>
<code>invalid-date-format</code>	<u>1453</u>
<code>invalid-time-format</code>	<u>1374</u>
J	
<code>join-word</code>	<u>2341</u>
K	
Keys for <code>\spAcirc</code> provide by spintent :	
<code>concept</code>	<u>128</u>
<code>prefix</code>	<u>127</u> , <u>128</u>
<code>print-sym</code>	<u>127</u> – <u>129</u>
<code>radio-sty</code>	<u>127</u>
<code>read-arg</code>	<u>127</u> , <u>128</u>
<code>read-cmd</code>	<u>127</u> , <u>128</u>
<code>read-sty</code>	<u>127</u> , <u>128</u>
<code>read-sub</code>	<u>128</u>
<code>silent-cmd</code>	<u>128</u>
<code>sub-index</code>	<u>127</u> , <u>128</u>
Keys for <code>\spAfig</code> provide by spintent :	
<code>prefix</code>	<u>111</u>
<code>print-sym</code>	<u>110</u> , <u>111</u>
<code>read-arg</code>	<u>111</u>
<code>read-cmd</code>	<u>110</u> , <u>111</u>
<code>read-sub</code>	<u>111</u>
Keys for <code>\spangle</code> provide by spintent :	
<code>concept</code>	<u>100</u>
<code>prefix</code>	<u>100</u>
<code>print-m</code>	<u>100</u>
<code>read-cmd</code>	<u>100</u>
<code>recto</code>	<u>100</u>
<code>silent-cmd</code>	<u>100</u>
Keys for <code>\sparc</code> provide by spintent :	
<code>concept</code>	<u>104</u>
<code>prefix</code>	<u>104</u>
<code>read-cmd</code>	<u>104</u>
<code>silent-cmd</code>	<u>104</u>
Keys for <code>\spcirc</code> provide by spintent :	
<code>prefix</code>	<u>122</u>
<code>print-sym</code>	<u>122</u> , <u>124</u>
<code>radio-sty</code>	<u>122</u>
<code>read-arg</code>	<u>122</u>
<code>read-cmd</code>	<u>122</u>
<code>read-sty</code>	<u>122</u>
<code>read-sub</code>	<u>122</u>
<code>sub-index</code>	<u>122</u>
Keys for <code>\spcoord</code> provide by spintent :	
<code>silent-cmd</code>	<u>83</u>
Keys for <code>\spdiam</code> provide by spintent :	
<code>concept</code>	<u>118</u>
<code>read-arg</code>	<u>118</u>
<code>read-cmd</code>	<u>118</u>
<code>read-sub</code>	<u>118</u>
<code>silent-cmd</code>	<u>118</u>
<code>sub-index</code>	<u>118</u>
<code>upper-case</code>	<u>118</u>
Keys for <code>\spdiv</code> provide by spintent :	
<code>cifras-sep</code>	<u>66</u>
<code>notation-sym</code>	<u>66</u>
<code>read-parens</code>	<u>66</u>
<code>read-period-sep</code>	<u>66</u>
<code>read-sign</code>	<u>66</u>
<code>read-sym</code>	<u>66</u>
<code>set-sym</code>	<u>66</u>
<code>wrap-parens</code>	<u>66</u>
Keys for <code>\spdsym</code> provide by spintent :	
<code>prefix</code>	<u>64</u>
<code>read-sym</code>	<u>64</u>
<code>set-sym</code>	<u>64</u>
<code>suffix</code>	<u>64</u>
Keys for <code>\spmangle</code> provide by spintent :	
<code>concept</code>	<u>100</u>
<code>prefix</code>	<u>100</u>
<code>print-m</code>	<u>100</u>
<code>read-cmd</code>	<u>100</u>
<code>recto</code>	<u>100</u>
<code>silent-cmd</code>	<u>100</u>
Keys for <code>\sparc</code> provide by spintent :	
<code>concept</code>	<u>104</u>
<code>prefix</code>	<u>104</u>
<code>read-cmd</code>	<u>104</u>
<code>silent-cmd</code>	<u>104</u>
Keys for <code>\spmcd</code> provide by spintent :	
<code>prefix</code>	<u>70</u> , <u>72</u>
<code>read-cmd</code>	<u>70</u>
<code>result-num</code>	<u>72</u>
<code>result</code>	<u>70</u>
<code>sample-arg</code>	<u>70</u>
<code>silent-cmd</code>	<u>70</u>
<code>upper-case</code>	<u>70</u>
Keys for <code>\spmcm</code> provide by spintent :	
<code>prefix</code>	<u>70</u> , <u>72</u>

read-cmd	70	read-sub	128
result-num	72	silent-cmd	128
result	70	sub-index	127, 128
sample-arg	70	Keys for \spPfig provide by spintent:	
silent-cmd	70	prefix	111
upper-case	70	print-sym	110, 111
Keys for \spmoney provide by spintent:		read-arg	111
cifras-sep	47	read-cmd	110, 111
currency	47	read-sub	111
dolar-math	47	Keys for \spPoint provide by spintent:	
sub-units	47	concept	87
Keys for \spmQ provide by spintent:		prefix	87
join-word	78, 80	read-cmd	87
print-dfrac	78–82	silent-cmd	87
read-parens	78, 79	Keys for \spPoly provide by spintent:	
use-spnZ	78, 81, 82	concept	108
wrap-parens	78, 79	prefix	107, 108
Keys for \spmside provide by spintent:		print-sym	108
concept	96	read-cmd	107, 108
prefix	96	silent-cmd	108
print-m	95, 96	Keys for \sprad provide by spintent:	
print-sym	118	concept	118
read-arg	96	read-arg	118
read-cmd	96, 98	read-cmd	118
read-sty	96	read-sub	118
silent-cmd	96, 98	silent-cmd	118
Keys for \spmsym provide by spintent:		sub-index	118
not-print	65	upper-case	118
prefix	65	Keys for \sprayo provide by spintent:	
read-sym	65	concept	93
set-sym	65	prefix	93
suffix	65	read-cmd	93, 94
Keys for \spmul provide by spintent:		read-sty	93
cifras-sep	68	silent-cmd	93, 94
notation-sym	68	Keys for \sprecta provide by spintent:	
read-parens	68	prefix	90
read-period-sep	68	read-cmd	90
read-sign	68	silent-cmd	90
read-sym	68	Keys for \spshort provide by spintent:	
set-sym	68	read-arg	53
wrap-parens	68	small-caps	53
Keys for \spnD provide by spintent:		Keys for \spside provide by spintent:	
result	72	concept	96
silent-cmd	72	prefix	96
Keys for \spnM provide by spintent:		read-arg	95, 96
result	72	read-cmd	96, 98
silent-cmd	72	read-sty	95, 96
Keys for \spnum provide by spintent:		silent-cmd	96, 98
cifras-sep	35–37	Keys for \spsiglo provide by spintent:	
notation-sym	36	print-era	55, 57
read-period-sep	36, 38	Keys for \spunit provide by spintent:	
read-sign	36	cifras-sep	42
Keys for \spnZ provide by spintent:		notation-sym	42
cifras-sep	76	print-cdot	42
read-parens	76, 77	read-cdot	42
read-sign	76	read-period-sep	42
wrap-parens	76, 77	read-slash	42
Keys for \spPcirc provide by spintent:		Keys for \spusep provide by spintent:	
concept	128	silent	61
prefix	127, 128	size	61
print-sym	127–129		
radio-sty	127		
read-arg	127, 128		
read-cmd	127, 128		
read-sty	127, 128		

M	
mathcal-fallback	70
\MathMLintent	102
mc-invalid-arguments	1933
md-invalid-argument	2105

Lua module provide by [spintent](#):

`spintent.lua` [29](#), [30](#), [34–36](#), [41](#), [45–47](#), [52](#), [53](#), [55](#), [57](#), [58](#),
[60](#), [69](#), [72](#), [75](#), [77](#), [82](#), [87](#), [118](#)

N

`not-print` [1706](#)
`notation-sym` [269](#), [554](#), [1780](#), [1851](#)

P

Packages :

`expl3` [34](#), [36](#)
`lua-unicode-math` [29](#)
`luamml` [31](#), [78](#), [80](#)
`tagpdf` [52](#), [56](#)
`unicode-math` [29](#), [62](#)
`prefix` [1636](#), [1706](#), [1940](#), [2079](#), [2759](#), [2887](#), [3054](#), [3190](#), [3395](#),
[3626](#), [3779](#), [3955](#), [4546](#), [4825](#)
`print-dfrac` [2341](#)
`print-era` [1231](#)
`print-m` [3190](#), [3395](#)
`print-sym` [3779](#), [3955](#), [4328](#), [4546](#), [4825](#)

R

`radio-sty` [4546](#)
`read-arg` [1101](#), [3190](#), [3955](#), [4328](#), [4546](#), [4825](#)
`read-cdot` [554](#)
`read-cmd` .. [1940](#), [2759](#), [2887](#), [3054](#), [3190](#), [3395](#), [3626](#), [3779](#),
[3955](#), [4328](#), [4546](#), [4825](#)
`read-parens` [1780](#), [1851](#), [2263](#), [2341](#)
`read-period-sep` [269](#), [554](#), [1780](#), [1851](#)
`read-sign` [269](#), [1780](#), [1851](#), [2263](#)
`read-slash` [554](#)
`read-sty` [3054](#), [3190](#), [4546](#), [4825](#)
`read-sub` [3955](#), [4328](#), [4546](#), [4825](#)
`read-sym` [1636](#), [1706](#), [1780](#), [1851](#)
`recto` [3395](#)
`result` [1940](#), [2079](#)
`result-num` [2079](#)
`right-angle-sqr-fallback` [70](#)
`\rightangle` [101](#)

S

`sample-arg` [1940](#), [2079](#)
seq commands:
`\seq_set_from_clist:Nn` [58](#)
`set-sym` [1636](#), [1706](#), [1780](#), [1851](#)
`\setspintent` [3](#), [32](#), [177](#)
`silent` [1501](#)
`silent-cmd` [1940](#), [2079](#), [2556](#), [2759](#), [2887](#), [3054](#), [3190](#), [3395](#),
[3626](#), [3779](#), [3955](#), [4328](#), [4546](#), [4825](#)
`size` [1501](#)
`small-caps` [1101](#)
`\spAcirc` [127](#), [5107](#)
`spAcirc-invalid-arg` [4816](#)
`\spAfig` [23](#), [110](#), [4296](#)
`spAfig-invalid-arg` [3924](#)
`spAfig-invalid-points` [3924](#)
`spAfig-sym-cardinality-conflict` [3924](#)
`spAfig-sym-letra-conflict` [3924](#)
`\spang` [21](#), [75](#), [2253](#)
`\spangle` [20](#), [100](#), [3591](#)
`spangle-invalid-arg` [3385](#)
`\sparc` [21](#), [104](#), [3750](#)

`sparc-invalid-points` [3616](#)
`\spcirc` [121](#), [4793](#)
`spcirc-invalid-arg` [4539](#)
`\spcoord` [83](#), [2691](#)
`spcoord-invalid-arg` [2552](#)
`\spdate` [11](#), [60](#), [1477](#)
`\spdiam` [118](#), [4508](#)
`\spdiv` [13](#), [66](#), [1841](#)
`spdiv-empty-argument` [1800](#)
`\spdsym` [12](#), [64](#), [1683](#)
spintent internal commands:
`\__spintent_collapse_hyphens:N` [114](#)
`\l__spintent_command_name_str` [189](#)
`\l__spintent_geo_circfig_mode_str` [4815](#)
`\l__spintent_geo_final_print_tl` [3916](#)
`\l__spintent_geo_luaaset_angulo_case_-`
`str` [2524](#)
`\l__spintent_geo_luaaset_circ_radio_raw_-`
`str` [4528](#)
`\l__spintent_geo_luaaset_circ_radio_type_-`
`str` [4528](#)
`\l__spintent_geo_luaaset_concept_str` ... [2524](#)
`\l__spintent_geo_luaaset_error_str` . [82](#), [2524](#)
`\l__spintent_geo_luaaset_intent_str` [82](#), [2524](#)
`\l__spintent_geo_luaaset_letra_str` [2524](#)
`\l__spintent_geo_luaaset_letra_word_str` [2524](#)
`\l__spintent_geo_luaaset_nombre_es_num_-`
`str` [2524](#)
`\l__spintent_geo_luaaset_points_-`
`clist_{uuuu}\l__spintent_geo_luaaset_is_-`
`name_str` [2524](#)
`\l__spintent_geo_luaaset_poly_sym_str` .. [2524](#)
`\l__spintent_geo_luaaset_print_tl` .. [82](#), [2524](#)
`\l__spintent_geo_luaaset_sub_spoken_str` [2524](#)
`\l__spintent_geo_luaaset_sub_str` [2524](#)
`\l__spintent_geo_luaaset_tipo_str` [2524](#)
`\l__spintent_geo_print_sym_str` [4019](#)
`\__spintent_invisible_sep:` [106](#)
`\c__spintent_invisible_sep_tl` [80](#), [106](#)
`\__spintent_luafun_clean_split_and_set:n` [65](#),
[226](#)
`\__spintent_luafun_spang_parse:n` [75](#)
`\__spintent_luafun_spdate_parse:n` [60](#)
`\__spintent_luafun_spmoney_lookup_data:n` [65](#)
`\__spintent_luafun_spmQ_scale_int:n` ... [65](#)
`\__spintent_luafun_sptime_parse:n` [59](#)
`\__spintent_luafun_spunit_lookup_alias:n` [65](#)
`\l__spintent_luaaset_arg_above_tl` [245](#)
`\l__spintent_luaaset_arg_below_tl` [245](#)
`\l__spintent_luaaset_cal_fam_ok_str` [63](#)
`\l__spintent_luaaset_dec_is_all_zeros_-`
`str` [238](#)
`\l__spintent_luaaset_dec_sep_tl` [226](#)
`\l__spintent_luaaset_decimal_period_str` [238](#)
`\l__spintent_luaaset_denom_has_number_-`
`str` [245](#)
`\l__spintent_luaaset_exponent_tl` [238](#)
`\l__spintent_luaaset_format_part_dec_str` [233](#)
`\l__spintent_luaaset_format_part_int_str` [233](#)
`\l__spintent_luaaset_has_exponent_str` .. [238](#)
`\l__spintent_luaaset_has_integer_str` .. [80–82](#),
[226](#)
`\l__spintent_luaaset_has_natural_str` ... [226](#)

<code>\l__spintent_luaset_has_units_str</code>	245	<code>__spintent_spangle_process:nn</code>	3461
<code>\l__spintent_luaset_millions_str</code>	238	<code>\l__spintent_spangle_pt_idx_int</code>	3454
<code>\l__spintent_luaset_not_decimal_not-</code> <code>period_str</code>	238	<code>\l__spintent_spangle_pt_seq</code>	3454
<code>\l__spintent_luaset_not_decimal_period-</code> <code>str</code>	238	<code>\l__spintent_spangle_refs_tl</code>	3454
<code>\l__spintent_luaset_only_part_dec_str</code> .	233	<code>__spintent_spangle_sym:n</code>	3435
<code>\l__spintent_luaset_only_part_int_str</code> .	233	<code>__spintent_sparc_exec:nnn</code>	3745
<code>\l__spintent_luaset_only_part_period-</code> <code>str</code>	233	<code>\l__spintent_sparc_intent_arg_tl</code>	3670
<code>\l__spintent_luaset_part_dec_tl</code>	226	<code>\l__spintent_sparc_intent_tl</code>	3670
<code>\l__spintent_luaset_part_int_tl</code>	80, 226	<code>__spintent_sparc_mathml:n</code>	3688
<code>\l__spintent_luaset_part_period_tl</code> ...	226	<code>\l__spintent_sparc_mode_str</code>	3611
<code>\l__spintent_luaset_sign_tl</code>	80, 226	<code>\l__spintent_sparc_prefix_tl</code>	3611
<code>\l__spintent_luaset_status_str</code>	245	<code>__spintent_sparc_print_arc:n</code>	3664
<code>\l__spintent_luaset_sym_fam_ok_str</code>	63	<code>__spintent_sparc_process:nn</code>	3675
<code>__spintent_mathcal:n</code>	84	<code>\l__spintent_sparc_pt_idx_int</code>	3670
<code>__spintent_mathmlarg_point:nnn</code>	2701	<code>\l__spintent_sparc_pt_seq</code>	3670
<code>\l__spintent_mathmlarg_point_kv_tl</code> ...	2701	<code>\l__spintent_sparc_refs_tl</code>	3670
<code>\l__spintent_mathmlarg_point_mode_str</code> .	2701	<code>__spintent_sparc_wide_arc:n</code>	3660
<code>\l__spintent_mathmlarg_point_ref_tl</code> ...	2701	<code>\l__spintent_spcirc_articulo_str</code>	4530
<code>\l__spintent_mathmlarg_point_silent-</code> <code>bool</code>	2701	<code>__spintent_spcirc_build_concept:</code>	4674
<code>\l__spintent_mc_args_seq</code>	1922	<code>\l__spintent_spcirc_connector_arg_tl</code> ..	4622
<code>__spintent_mc_process_args:nn</code>	1981	<code>\l__spintent_spcirc_connector_tl</code>	4622
<code>\l__spintent_md_out_seq</code>	2069	<code>__spintent_spcirc_exec:nn</code>	4788
<code>__spintent_print_spunit_hierarchy:</code> ...	655	<code>\l__spintent_spcirc_has_arg_bool</code>	4622
<code>__spintent_right_angle_sqr:</code>	97	<code>\l__spintent_spcirc_intent_arg_tl</code>	4622
<code>__spintent_sanitize_affix:Nn</code>	122	<code>\l__spintent_spcirc_intent_tl</code>	4622
<code>\l__spintent_saved_luamml_flag_int</code> 80, 2322		<code>__spintent_spcirc_mathml:</code>	4743
<code>\l__spintent_setspintent_input_arg_cmd-</code> <code>tl</code>	140	<code>\l__spintent_spcirc_mode_str</code>	4530
<code>__spintent_setspintent_parse_args:nn</code> .	160	<code>\l__spintent_spcirc_prefix_tl</code>	4530
<code>__spintent_setspintent_set_keys:nn</code> ...	149	<code>\l__spintent_spcirc_print_sym_str</code>	4530
<code>\l__spintent_smparc_prefix_tl</code>	3611	<code>__spintent_spcirc_process:n</code>	4727
<code>__spintent_sp_rad_diam_exec:nn</code>	4503	<code>\l__spintent_spcirc_radio_arg_tl</code>	4622
<code>\l__spintent_sp_rad_diam_letra_tl</code>	4326	<code>__spintent_spcirc_radio_print:</code>	4659
<code>__spintent_sp_rad_diam_print:n</code>	4375	<code>\l__spintent_spcirc_radio_sty_str</code>	4530
<code>\l__spintent_sp_rad_diam_word_tl</code>	4326	<code>\l__spintent_spcirc_read_sty_str</code>	4530
<code>\l__spintent_spAcirc_mode_str</code>	4805	<code>\l__spintent_spcirc_sub_index_str</code>	4530
<code>\l__spintent_spAcirc_prefix_tl</code>	4805	<code>__spintent_spcirc_sym:</code>	4628
<code>\l__spintent_spAcirc_print_sym_str</code> ...	4805	<code>__spintent_spcirc_word_and_article:</code> ..	4638
<code>\l__spintent_spAcirc_radio_sty_str</code> ...	4805	<code>\l__spintent_spcirc_word_tl</code>	4538
<code>\l__spintent_spAcirc_read_arg_tl</code>	4805	<code>__spintent_spcircfig_build_concept:nn</code>	4969
<code>\l__spintent_spAcirc_read_sty_str</code>	4805	<code>__spintent_spcircfig_build_short:n</code> ...	4931
<code>\l__spintent_spAcirc_sub_index_str</code> ...	4805	<code>__spintent_spcircfig_del_word:n</code>	4920
<code>\l__spintent_spAfig_mode_str</code>	3917	<code>__spintent_spcircfig_exec:nnn</code>	5102
<code>\l__spintent_spAfig_prefix_tl</code>	3917	<code>__spintent_spcircfig_finish_intent:nn</code>	4953
<code>\l__spintent_spAfig_print_sym_str</code>	3917	<code>\l__spintent_spcircfig_intent_arg_tl</code> ..	4891
<code>\l__spintent_spAfig_read_arg_tl</code>	3917	<code>\l__spintent_spcircfig_intent_tl</code>	4891
<code>\l__spintent_spang_luaset_error_str</code> ...	2209	<code>__spintent_spcircfig_mathml:nn</code>	5061
<code>\l__spintent_spang_luaset_grado_str</code> ...	2209	<code>\l__spintent_spcircfig_op_tl</code>	4891
<code>\l__spintent_spang_luaset_minuto_str</code> ..	2209	<code>__spintent_spcircfig_process:nn</code>	5016
<code>\l__spintent_spang_luaset_segundo_str</code> .	2209	<code>\l__spintent_spcircfig_short_bool</code>	4891
<code>__spintent_spang_process:n</code>	2218	<code>__spintent_spcircfig_sym:n</code>	4896
<code>__spintent_spangle_exec:nnn</code>	3586	<code>__spintent_spcircfig_word_and-</code> <code>article:n</code>	4902
<code>\l__spintent_spangle_intent_arg_tl</code> ...	3454	<code>__spintent_spcord_exec:nn</code>	2673
<code>\l__spintent_spangle_intent_tl</code>	3454	<code>__spintent_spcord_intent_infix:</code>	2644
<code>__spintent_spangle_mathml:n</code>	3482	<code>\l__spintent_spcord_intent_str</code>	2548
<code>\l__spintent_spangle_mode_str</code>	3380	<code>\l__spintent_spcord_luaset_error_str</code> .	2538
<code>\l__spintent_spangle_prefix_tl</code>	3380	<code>\l__spintent_spcord_luaset_sep_str</code> ...	2538
<code>\l__spintent_spangle_print_m_now_bool</code> .	3454	<code>\l__spintent_spcord_luaset_x_has_frac-</code> <code>str</code>	2538
		<code>\l__spintent_spcord_luaset_x_sign_str</code>	2538
		<code>\l__spintent_spcord_luaset_x_type_str</code>	2538

<code>\l__spintent_spcoord_luaset_x_value_-str</code>	2538	<code>__spintent_spmoney_check_sub_units:</code> ..	959
<code>\l__spintent_spcoord_luaset_y_has_frac_-str</code>	2538	<code>\l__spintent_spmoney_extracted_curr_str</code>	788
<code>\l__spintent_spcoord_luaset_y_sign_str</code>	2538	<code>\l__spintent_spmoney_extracted_num_tl</code> .	788
<code>\l__spintent_spcoord_luaset_y_type_str</code>	2538	<code>__spintent_spmoney_intent_int:</code>	895
<code>\l__spintent_spcoord_luaset_y_value_-str</code>	2538	<code>\l__spintent_spmoney_intent_money_str</code> .	788
<code>__spintent_spcoord_mathml:</code>	2656	<code>\l__spintent_spmoney_intent_sign_str</code> ..	788
<code>__spintent_spcoord_print:n</code>	2621	<code>\l__spintent_spmoney_intent_sub_unit_-str</code>	788
<code>\l__spintent_spcoord_raw_arg_tl</code>	2548	<code>\l__spintent_spmoney_luaset_conde_str</code> .	778
<code>__spintent_spcoord_set_wrap_parens_-size:</code>	2568	<code>\l__spintent_spmoney_luaset_currency_arg_-str</code>	778
<code>__spintent_spcoord_value:n</code>	2615	<code>\l__spintent_spmoney_luaset_plur_str</code> ..	778
<code>\l__spintent_spcoord_wrap_parens_l_tl</code> .	2548	<code>\l__spintent_spmoney_luaset_position_-str</code>	778
<code>\l__spintent_spcoord_wrap_parens_r_tl</code> .	2548	<code>\l__spintent_spmoney_luaset_print_iso_-str</code>	778
<code>\l__spintent_spdate_luaset_error_str</code> ..	1451	<code>\l__spintent_spmoney_luaset_sing_str</code> ..	778
<code>\l__spintent_spdate_luaset_output_str</code> .	1451	<code>\l__spintent_spmoney_luaset_status_str</code>	778
<code>__spintent_spdate_process:n</code>	60, 1462	<code>\l__spintent_spmoney_luaset_subplur_str</code>	778
<code>\l__spintent_spdiam_mode_str</code>	4320	<code>\l__spintent_spmoney_luaset_subsing_str</code>	778
<code>\l__spintent_spdiam_sub_index_str</code>	4320	<code>\l__spintent_spmoney_luaset_symbol_str</code>	778
<code>\l__spintent_spdiam_upper_case_bool</code> ...	4320	<code>__spintent_spmoney_normalize_key:n</code> ...	813
<code>__spintent_spdiv_process:nnn</code>	1826	<code>__spintent_spmoney_parse_and_route:n</code> .	1054
<code>__spintent_spdiv_render_op:nn</code>	1805	<code>__spintent_spmoney_print_dec_sub_-unit:</code>	1006
<code>__spintent_spdiv_render_parens:nn</code> ...	1814	<code>__spintent_spmoney_print_int:</code>	895
<code>\l__spintent_spdsym_prefix_tl</code>	1632	<code>__spintent_spmoney_print_sep_con:</code> ...	1006
<code>\l__spintent_spdsym_read_sym_tl</code>	1632	<code>__spintent_spmoney_print_symbol:</code>	861
<code>\l__spintent_spdsym_suffix_tl</code>	1632	<code>__spintent_spmoney_render_layout:</code> ...	874
<code>\l__spintent_spdsym_symbol_tl</code>	1632	<code>__spintent_spmoney_render_number_node:</code>	886
<code>__spintent_spfig_build_concept_-vertices:n</code>	4167	<code>__spintent_spmoney_render_only_integer_-node:</code>	886
<code>__spintent_spfig_build_refs:</code>	4154	<code>\l__spintent_spmoney_res_main_voice_str</code>	788
<code>__spintent_spfig_build_simple:n</code>	4044	<code>__spintent_spmoney_set_and_print_sub_-units:</code>	959
<code>__spintent_spfig_exec:nnn</code>	4291	<code>__spintent_spmoney_set_currency:n</code> ...	813
<code>\l__spintent_spfig_intent_arg_tl</code>	4019	<code>\l__spintent_spmoney_sub_units_bool</code> ...	788
<code>\l__spintent_spfig_intent_tl</code>	4019	<code>\l__spintent_spmoney_subnum_int</code>	788
<code>__spintent_spfig_mathml:n</code>	4251	<code>__spintent_spmoney_validate_money:</code> ...	845
<code>\l__spintent_spfig_op_tl</code>	4019	<code>__spintent_spmQ_exec:nnnn</code>	2502
<code>__spintent_spfig_points_loop:n</code>	4239	<code>\l__spintent_spmQ_join_word_str</code> ...	80, 2322
<code>__spintent_spfig_process:nn</code>	4028	<code>__spintent_spmQ_print:nnn</code>	2494
<code>\l__spintent_spfig_pt_idx_int</code>	4019	<code>\l__spintent_spmQ_print_dfrac_bool</code>	81
<code>\l__spintent_spfig_pt_seq</code>	4019	<code>__spintent_spmQ_print_scale_int:</code>	2440
<code>\l__spintent_spfig_refs_tl</code>	4019	<code>__spintent_spmQ_print_scale_int:n</code> ...	2449
<code>__spintent_spfig_sym:</code>	4011	<code>__spintent_spmQ_print_spnZ_dfrac:nn</code> ..	2477
<code>\l__spintent_spfig_symbol_tl</code>	4019	<code>__spintent_spmQ_set_join_word:</code>	2431
<code>\l__spintent_spmangle_mode_str</code>	3380	<code>__spintent_spmQ_set_wrap_parens_size:</code>	2376
<code>\l__spintent_spmangle_prefix_tl</code>	3380	<code>__spintent_spmQ_start_wrap_parens:</code> ...	2411
<code>\l__spintent_spmarc_mode_str</code>	3611	<code>__spintent_spmQ_stop_wrap_parens:</code> ...	2411
<code>__spintent_spmc_process:nnnn</code>	2003	<code>\l__spintent_spmQ_use_spnZ_bool</code>	81
<code>\l__spintent_spmcd_prefix_tl</code>	1922	<code>\l__spintent_spm_side_mode_str</code>	3173
<code>\l__spintent_spmcd_print_result_bool</code> ..	1922	<code>\l__spintent_spm_side_prefix_tl</code>	3173
<code>\l__spintent_spmcd_print_upper_bool</code> ...	1922	<code>\l__spintent_spm_side_read_arg_tl</code>	3173
<code>\l__spintent_spmcd_read_terse_bool</code> ...	1922	<code>\l__spintent_spm_side_read_sty_str</code>	3173
<code>\l__spintent_spmcd_suffix_tl</code>	1922	<code>\l__spintent_spm_sym_prefix_tl</code>	1702
<code>\l__spintent_spmcm_prefix_tl</code>	1922	<code>\l__spintent_spm_sym_read_sym_tl</code>	1702
<code>\l__spintent_spmcm_print_result_bool</code> ..	1922	<code>\l__spintent_spm_sym_suffix_tl</code>	1702
<code>\l__spintent_spmcm_print_upper_bool</code> ...	1922	<code>\l__spintent_spm_sym_symbol_tl</code>	1702
<code>\l__spintent_spmcm_read_terse_bool</code> ...	1922	<code>__spintent_spmul_process:nnn</code>	1897
<code>\l__spintent_spmcm_spmcd_luaset_error_-str</code>	1922	<code>__spintent_spmul_render_op:nn</code>	1876
<code>\l__spintent_spmcm_suffix_tl</code>	1922	<code>__spintent_spmul_render_parens:nn</code> ...	1885
<code>__spintent_spmoney_build_tree:</code>	1006		

<code>\l__spintent_spnD_luaset_is_truncated_-str</code>	2069	<code>\l__spintent_spPoint_prefix_tl</code>	2746
<code>\l__spintent_spnD_luaset_result_tl</code> ...	2069	<code>__spintent_spPoint_print:n</code>	2794
<code>\l__spintent_spnD_prefix_tl</code>	2069	<code>\l__spintent_spPoint_silent_cmd_bool</code> ..	2746
<code>\l__spintent_spnD_print_result_bool</code> ...	2069	<code>__spintent_spPoly_build_concept:</code>	3838
<code>\l__spintent_spnD_print_result_num_tl</code> .	2069	<code>__spintent_spPoly_build_refs:</code>	3825
<code>\l__spintent_spnD_silent_cmd_bool</code>	2069	<code>__spintent_spPoly_exec:nn</code>	3901
<code>\l__spintent_spnM_luaset_is_truncated_-str</code>	2069	<code>\l__spintent_spPoly_intent_arg_tl</code>	3813
<code>\l__spintent_spnM_luaset_result_tl</code> ...	2069	<code>__spintent_spPoly_mathml:</code>	3881
<code>\l__spintent_spnM_prefix_tl</code>	2069	<code>\l__spintent_spPoly_mode_str</code>	3770
<code>\l__spintent_spnM_print_result_bool</code> ...	2069	<code>__spintent_spPoly_points_loop:</code>	3859
<code>\l__spintent_spnM_print_result_num_tl</code> .	2069	<code>\l__spintent_spPoly_prefix_tl</code>	3770
<code>\l__spintent_spnM_silent_cmd_bool</code>	2069	<code>__spintent_spPoly_process:n</code>	3871
<code>__spintent_spnM_spnD_exec:nnnn</code>	2150	<code>\l__spintent_spPoly_pt_idx_int</code>	3813
<code>__spintent_spnM_spnD_intent:nn</code>	2115	<code>\l__spintent_spPoly_pt_seq</code>	3813
<code>__spintent_spnM_spnD_process:nnnn</code> ...	2110	<code>\l__spintent_spPoly_refs_tl</code>	3813
<code>__spintent_spnM_spnD_result:n</code>	2131	<code>__spintent_spPoly_sym:</code>	3817
<code>__spintent_spnM_spnD_silent:nn</code>	2123	<code>\l__spintent_sprad_mode_str</code>	4320
<code>\l__spintent_spnQ_intent_read_sign_str</code>	2322	<code>\l__spintent_sprad_sub_index_str</code>	4320
<code>\l__spintent_spnQ_read_parens_bool</code>	79	<code>\l__spintent_sprad_upper_case_bool</code> ...	4320
<code>\l__spintent_spnQ_wrap_parens_l_tl</code> 79, 2322		<code>__spintent_sprayo_exec:nn</code>	3158
<code>\l__spintent_spnQ_wrap_parens_r_tl</code> 79, 2322		<code>\l__spintent_sprayo_intent_arg_tl</code>	3098
<code>\l__spintent_spnnum__notation_sym_tl</code>	36	<code>__spintent_sprayo_mathml:</code>	3111
<code>\l__spintent_spnnum_intent_read_dec_sep_-str</code>	36, 38, 264	<code>\l__spintent_sprayo_mode_str</code>	3044
<code>\l__spintent_spnnum_intent_read_sign_str</code>	36, 264	<code>\l__spintent_sprayo_prefix_tl</code>	3044
<code>\l__spintent_spnnum_notation_sym_tl</code> ...	264	<code>__spintent_sprayo_print:n</code>	3102
<code>__spintent_spnnum_print_integer:</code>	431	<code>\l__spintent_sprayo_pt_idx_int</code>	3098
<code>__spintent_spnnum_print_num_start:</code> ...	431	<code>\l__spintent_sprayo_pt_seq</code>	3098
<code>__spintent_spnnum_print_number_core:</code> ..	431	<code>\l__spintent_sprayo_read_sty_str</code>	3044
<code>__spintent_spnnum_print_part_dec:</code>	410	<code>\l__spintent_sprayo_refs_tl</code>	3098
<code>__spintent_spnnum_print_part_period:</code> ..	410	<code>__spintent_spread_exec:nn</code>	1613
<code>__spintent_spnnum_print_period_bar:</code> ...	339	<code>\l__spintent_spread_intent_tl</code>	1612
<code>\l__spintent_spnnum_read_period_sep_str</code> .	36, 264	<code>__spintent_sprecta_exec:nn</code>	3029
<code>\l__spintent_spnnum_read_terse_bool</code> .	36, 264	<code>\l__spintent_sprecta_intent_arg_tl</code> ...	2873
<code>__spintent_spnnum_render_dec:</code>	322	<code>\l__spintent_sprecta_kv_tl</code>	2873
<code>__spintent_spnnum_render_decimal_sep:</code> .	376	<code>__spintent_sprecta_mathml:</code>	2927
<code>__spintent_spnnum_render_int:</code>	322	<code>\l__spintent_sprecta_mode_str</code>	2873
<code>__spintent_spnnum_render_only_period:</code> .	339	<code>\l__spintent_sprecta_prefix_tl</code>	2873
<code>__spintent_spnnum_render_part:n</code>	322	<code>__spintent_sprecta_print:n</code>	2918
<code>__spintent_spnnum_render_period_sep:</code> ..	339	<code>\l__spintent_sprecta_pt_idx_int</code>	2873
<code>__spintent_spnz_process:nn</code>	2296	<code>\l__spintent_sprecta_pt_seq</code>	2873
<code>__spintent_spnz_render_parens:</code>	2284	<code>\l__spintent_sprecta_refs_tl</code>	2873
<code>\l__spintent_spPcirc_mode_str</code>	4805	<code>__spintent_spsshort_execute_layout:</code> ...	1162
<code>\l__spintent_spPcirc_prefix_tl</code>	4805	<code>\l__spintent_spsshort_luaset_base_str</code> ..	1079
<code>\l__spintent_spPcirc_print_sym_str</code> ...	4805	<code>\l__spintent_spsshort_luaset_expanded_-str</code>	1079
<code>\l__spintent_spPcirc_radio_sty_str</code> ...	4805	<code>\l__spintent_spsshort_luaset_layout_str</code>	1079
<code>\l__spintent_spPcirc_read_arg_tl</code>	4805	<code>\l__spintent_spsshort_luaset_output_str</code>	1079
<code>\l__spintent_spPcirc_read_sty_str</code>	4805	<code>\l__spintent_spsshort_luaset_status_str</code>	1079
<code>\l__spintent_spPcirc_sub_index_str</code> ...	4805	<code>\l__spintent_spsshort_luaset_suffix_str</code>	1079
<code>\l__spintent_spPfig_mode_str</code>	3917	<code>__spintent_spsshort_print:nn</code>	1115
<code>\l__spintent_spPfig_prefix_tl</code>	3917	<code>__spintent_spsshort_process_and_-render:n</code>	1127
<code>\l__spintent_spPfig_print_sym_str</code>	3917	<code>__spintent_spsshort_render_bypass:n</code> ...	1138
<code>\l__spintent_spPfig_read_arg_tl</code>	3917	<code>__spintent_spsshort_render_error:n</code> ...	1138
<code>__spintent_spPoint_exec:nn</code>	2858	<code>__spintent_spsshort_render_fallback:</code> ..	1138
<code>\l__spintent_spPoint_intent_arg_tl</code> ...	2746	<code>__spintent_spsshort_render_success:</code> ...	1138
<code>\l__spintent_spPoint_kv_tl</code>	2746	<code>__spintent_spsshort_tag_span:nn</code>	1088
<code>__spintent_spPoint_mathml:</code>	2822	<code>__spintent_spside_exec:nnn</code>	3355
<code>\l__spintent_spPoint_mode_str</code>	2746	<code>\l__spintent_spside_intent_arg_tl</code>	3247
		<code>\l__spintent_spside_intent_tl</code>	3247
		<code>__spintent_spside_mathml:n</code>	3280

<code>\l__spintent_spside_mode_str</code>	3173	<code>\spmarc</code>	22 , 104 , 3750
<code>__spintent_spside_points_loop:n</code>	3343	<code>spmarc-invalid-points</code>	3616
<code>\l__spintent_spside_prefix_tl</code>	3173	<code>\spmcd</code>	15 , 69 , 2049
<code>__spintent_spside_process:nn</code>	3252	<code>\spmcm</code>	15 , 69 , 2049
<code>\l__spintent_spside_pt_idx_int</code>	3247	<code>\spmoney</code>	6 , 46 , 1068
<code>\l__spintent_spside_pt_seq</code>	3247	<code>\spmQ</code>	16 , 77 , 2514
<code>\l__spintent_spside_read_arg_tl</code>	3173	<code>spmQ-not-integer</code>	2327
<code>\l__spintent_spside_read_sty_str</code>	3173	<code>spmQ-zero-denominator</code>	2327
<code>\l__spintent_spside_refs_tl</code>	3247	<code>\spmside</code>	19 , 95 , 3360
<code>\l__spintent_spsiglo_luaset_arabic_str</code>	1219	<code>spmside</code>	4546
<code>\l__spintent_spsiglo_luaset_error_str</code>	1219	<code>spmside-invalid-points</code>	3180
<code>\l__spintent_spsiglo_luaset_roman_min_- str</code>	1219	<code>\spmsym</code>	12 , 65 , 1755
<code>\l__spintent_spsiglo_print_era_str</code> ...	1219	<code>\spmUL</code>	13 , 68 , 1912
<code>__spintent_spsiglo_print_math:n</code>	1303	<code>spmUL-empty-argument</code>	1871
<code>__spintent_spsiglo_print_text:n</code>	1303	<code>\spnD</code>	14 , 72 , 2189
<code>__spintent_spsiglo_render_simple:nn</code> ..	1254	<code>\spnewunit</code>	6 , 45 , 746
<code>__spintent_spsiglo_render_with_- era:nnn</code>	1254	<code>spnewunit-duplicate</code>	725
<code>__spintent_spsiglo_tag_span:nn</code>	1290	<code>\spnM</code>	14 , 72 , 2189
<code>__spintent_sptime_build_seconds:nn</code> ...	1383	<code>\spnum</code>	3 , 36 , 37 , 500
<code>__spintent_sptime_build_tree:</code>	59 , 1401	<code>spnum-has-units</code>	486
<code>\l__spintent_sptime_luaset_base_str</code> ...	1369	<code>spnum-no-digits</code>	486
<code>\l__spintent_sptime_luaset_error_str</code> ..	1369	<code>\spnZ</code>	16 , 76 , 2312
<code>\l__spintent_sptime_luaset_has_seconds_- str</code>	1369	<code>spnz-not-integer</code>	2279
<code>\l__spintent_sptime_luaset_is_fraction_- str</code>	1369	<code>\spPcirc</code>	127 , 5107
<code>\l__spintent_sptime_luaset_seconds_str</code> ..	1369	<code>spPcirc-invalid-arg</code>	4816
<code>\l__spintent_spunit_exp_seq</code>	525	<code>\spPfig</code>	24 , 110 , 4296
<code>\l__spintent_spunit_exponent_tl</code>	525	<code>spPfig-invalid-arg</code>	3924
<code>__spintent_spunit_format_canonical:</code> ..	588	<code>spPfig-invalid-points</code>	3924
<code>\l__spintent_spunit_is_mult_bool</code>	525	<code>spPfig-sym-cardinality-conflict</code>	3924
<code>\l__spintent_spunit_luaset_canonical_- str</code>	518	<code>spPfig-sym-letra-conflict</code>	3924
<code>\l__spintent_spunit_luaset_compact_exp_- str</code>	518	<code>\spPoint</code>	17 , 87 , 2863
<code>\l__spintent_spunit_luaset_is_compact_- str</code>	518	<code>spPoint-invalid-point</code>	2751
<code>\l__spintent_spunit_luaset_is_- sexagesimal_str</code>	518	<code>\spPoly</code>	22 , 107 , 3906
<code>\l__spintent_spunit_luaset_lookup_status_- str</code>	518	<code>spPoly-invalid-points</code>	3772
<code>\l__spintent_spunit_luaset_read_str</code> ...	518	<code>\sprad</code>	118 , 4508
<code>\l__spintent_spunit_luaset_status_str</code> ..	518	<code>\sprayo</code>	18 , 93 , 3163
<code>\l__spintent_spunit_mult_seq</code>	525	<code>sprayo-invalid-points</code>	3047
<code>__spintent_spunit_process_base_exp:n</code> ..	588	<code>\spread</code>	11 , 63 , 1622
<code>__spintent_spunit_process_mult:n</code>	648	<code>spread-empty-args</code>	1609
<code>\l__spintent_spunit_read_cdot_bool</code> ...	525	<code>\sprecta</code>	18 , 89 , 3034
<code>\l__spintent_spunit_read_slash_str</code> ...	525	<code>sprecta-invalid-points</code>	2880
<code>__spintent_spunit_safe_exec:n</code>	667	<code>\spshort</code>	7 , 52 , 1206
<code>\l__spintent_spunit_unit_name_tl</code>	525	<code>\spside</code>	19 , 95 , 3360
<code>\l__spintent_spusep_arg_tl</code>	61 , 62 , 1498	<code>spside</code>	4546
<code>__spintent_spusep_convert:n</code>	1560	<code>spside-invalid-points</code>	3180
<code>\l__spintent_spusep_left_tl</code>	61 , 62 , 1498	<code>\spsiglo</code>	11 , 55 , 1356
<code>\l__spintent_spusep_right_tl</code>	61 , 62 , 1498	<code>\sptime</code>	11 , 58 , 1433
<code>__spintent_spusep_set_parens:nn</code>	1549	<code>\spunit</code>	4 , 41 , 42 , 44 , 713
<code>\l__spintent_spusep_silent_bool</code>	62	<code>spunit-invalid-unit</code>	532
<code>__spintent_unknown_keys:n</code>	216	<code>spunit-no-units</code>	532
<code>__spintent_unknown_keys:nn</code>	216	<code>\spunitalias</code>	6 , 45 , 760
<code>\spmangle</code>	21 , 100 , 3591	<code>spunitalias-duplicate</code>	725
<code>spmangle-invalid-arg</code>	3385	<code>spunitalias-invalid-expr</code>	725
		<code>\spusep</code>	12 , 61 , 1598
		<code>spusep-empty-arg</code>	1487
		<code>spusep-invalid-arg</code>	1487
		<code>str commands:</code>	
		<code>\str_if_eq:nnTF</code>	58
		<code>\str_lowercase:n</code>	58
		<code>\str_uppercase:n</code>	58
		<code>sub-index</code>	4328 , 4546 , 4825

sub-units	827	unknown-choice	189
suffix	1636 , 1706	unknown-command-setup	140
U			
unknown	1501 , 1636 , 1706 , 2341 , 2759 , 2887 , 3054 , 3190 , 3395 , 3626 , 3779 , 3955 , 4328 , 4546 , 4825	upper-case	1940 , 4328
unknown-abbreviation	1085	use-spnz	2341
W			
		wrap-parens	1780 , 1851 , 2263 , 2341