

Pablo Esteban Castellon Cerritos

Redes de Computadoras

Parcial 2

R1. En este apartado está la configuración de los puertos del router y las IPs asignadas.

```
R1#show ip interface brief
Interface                IP-Address      OK? Method Status      Protocol
FastEthernet0/0          10.22.0.1       YES manual up          up
FastEthernet1/0          10.22.0.65      YES manual up          up
FastEthernet1/1          unassigned      YES unset  administratively down down
Serial2/0                10.22.0.129     YES manual up          up
Serial2/1                unassigned      YES unset  administratively down down
Serial2/2                unassigned      YES unset  administratively down down
Serial2/3                unassigned      YES unset  administratively down down
R1#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

    10.0.0.0/8 is variably subnetted, 6 subnets, 4 masks
C       10.22.0.0/26 is directly connected, FastEthernet0/0
C       10.22.0.64/27 is directly connected, FastEthernet1/0
S       10.22.0.112/28 [1/0] via 10.22.0.130
S       10.22.0.96/28 [1/0] via 10.22.0.130
S       10.22.0.132/30 [1/0] via 10.22.0.130
C       10.22.0.128/30 is directly connected, Serial2/0
```

R2. En este apartado está la configuración de los puertos del router y las IPs asignadas.

```
R2#show ip interface brief
Interface                IP-Address      OK? Method Status      Protocol
FastEthernet0/0          10.22.0.97      YES manual up          up
FastEthernet1/0          unassigned      YES unset  administratively down down
FastEthernet1/1          unassigned      YES unset  administratively down down
Serial2/0                10.22.0.130     YES manual up          up
Serial2/1                10.22.0.133     YES manual up          up
Serial2/2                unassigned      YES unset  administratively down down
Serial2/3                unassigned      YES unset  administratively down down
R2#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

    10.0.0.0/8 is variably subnetted, 6 subnets, 4 masks
S       10.22.0.0/26 [1/0] via 10.22.0.129
S       10.22.0.64/27 [1/0] via 10.22.0.129
S       10.22.0.112/28 [1/0] via 10.22.0.134
C       10.22.0.96/28 is directly connected, FastEthernet0/0
C       10.22.0.132/30 is directly connected, Serial2/1
C       10.22.0.128/30 is directly connected, Serial2/0
```

R3. En este apartado está la configuración de los puertos del router y las IPs asignadas.

```
R300190622#show ip interface brief
Interface                IP-Address      OK? Method Status        Protocol
FastEthernet0/0          unassigned      YES unset  administratively down down
FastEthernet1/0          unassigned      YES unset  administratively down down
FastEthernet1/1          unassigned      YES unset  administratively down down
Serial2/0                unassigned      YES unset  administratively down down
Serial2/1                unassigned      YES unset  administratively down down
Serial2/2                unassigned      YES unset  administratively down down
Serial2/3                unassigned      YES unset  administratively down down
R300190622#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
        ia - IS-IS inter area, * - candidate default, U - per-user static route
        o - ODR, P - periodic downloaded static route

Gateway of last resort is not set
```

PC1.

```
PC1> show ip
NAME       : PC1[1]
IP/MASK    : 10.22.0.2/26
GATEWAY    : 10.22.0.1
DNS        :
MAC        : 00:50:79:66:68:00
LPORT     : 10032
RHOST:PORT : 127.0.0.1:10033
MTU:       : 1500
```

PC2.

```
PC2> show ip
NAME       : PC2[1]
IP/MASK    : 10.22.0.66/27
GATEWAY    : 10.22.0.65
DNS        :
MAC        : 00:50:79:66:68:01
LPORT     : 10034
RHOST:PORT : 127.0.0.1:10035
MTU:       : 1500
```

PC3.

```
PC3> show ip  
NAME       : PC3[1]  
IP/MASK     : 10.22.0.98/28  
GATEWAY     : 10.22.0.97  
DNS         :  
MAC         : 00:50:79:66:68:02  
LPORT       : 10036  
RHOST:PORT  : 127.0.0.1:10037  
MTU         : 1500
```

PC4.

```
PC4> show ip  
NAME       : PC4[1]  
IP/MASK     : 10.22.0.114/28  
GATEWAY     : 10.22.0.113  
DNS         :  
MAC         : 00:50:79:66:68:03  
LPORT       : 10038  
RHOST:PORT  : 127.0.0.1:10039  
MTU         : 1500
```

Topologia en GNS3.

