

Feb 10, 2025 13:48

test.py

Page 1/2

```

1  from PySide6.QtWidgets import (QApplication, QTableView,
2      QWidget,
3      QVBoxLayout, QPushButton)
4  from PySide6.QtCore import QModelIndex, Qt, QAbstractTableModel
5
6  class MyTableModel(QAbstractTableModel):
7      def __init__(self, data):
8          super().__init__()
9          self._data = data
10
11     def rowCount(self, parent=QModelIndex()):
12         return len(self._data)
13
14     def columnCount(self, parent=QModelIndex()):
15         return len(self._data[0]) if self._data else 0
16
17     def data(self, index, role=Qt.DisplayRole):
18         if not index.isValid():
19             return None
20         if role == Qt.DisplayRole:
21             return self._data[index.row()][index.column()]
22         return None
23
24     def insertRows(self, position, rows=1, parent=QModelIndex(), *args, **kwargs):
25         self.beginInsertRows(parent, position, position + rows - 1)
26         for _ in range(rows):
27             self._data.insert(position, [""] * self.columnCount())
28         self.endInsertRows()
29         return True
30
31     def setData(self, index, value, role=Qt.EditRole):
32         if role == Qt.EditRole:
33             self._data[index.row()][index.column()] = value
34             self.dataChanged.emit(index, index, [role])
35             return True
36         return False
37
38     def flags(self, index):
39         return Qt.ItemIsSelectable | Qt.ItemIsEnabled | Qt.ItemIsEditable
40
41
42     class MyTableView(QWidget):
43         def __init__(self, data):
44             super().__init__()
45             self.table_model = MyTableModel(data)
46             self.table_view = QTableView()
47             self.table_view.setModel(self.table_model)
48             self.add_row_button = QPushButton("Add Row")
49             self.add_row_button.clicked.connect(self.add_row)
50
51             layout = QVBoxLayout()
52             layout.addWidget(self.table_view)
53             layout.addWidget(self.add_row_button)
54             self.setLayout(layout)
55
56         def add_row(self):
57             row_position = self.table_model.rowCount()

```

Feb 10, 2025 13:48

test.py

Page 2/2

```
58         self.table_model.insertRow(row_position)
59
60
61 if __name__ == "__main__":
62     app = QApplication([])
63     initial_data = [ ["Row 1, Column 1", "Row 1, Column 2"],
64                     ["Row 2, Column 1", "Row 2, Column 2"] ]
65     table_widget = MyTableView(initial_data)
66     table_widget.show()
67     app.exec()
```