

# Scanning object storage that uses S3 protocol

**Cloud Manager** 

Tom Onacki July 01, 2021

This PDF was generated from https://docs.netapp.com/us-en/occm/task\_scanning\_object\_storage.html on September 09, 2021. Always check docs.netapp.com for the latest.

## **Table of Contents**

| Sc | canning object storage that uses S3 protocol                      |
|----|---|
|    | Quick start   |
|    | Reviewing object storage requirements                             |
|    | Adding the object storage service to Cloud Data Sense             |
|    | Enabling and disabling compliance scans on object storage buckets |

## Scanning object storage that uses S3 protocol

Complete a few steps to start scanning data within object storage directly with Cloud Data Sense. Data Sense can scan data from any Object Storage service which uses the Simple Storage Service (S3) protocol. This includes NetApp StorageGRID, IBM Cloud Object Store, Azure Blob (using MinIO), Linode, B2 Cloud Storage, and more.

## **Quick start**

Get started quickly by following these steps, or scroll down to the remaining sections for full details.



## Review object storage prerequisites

You need to have the endpoint URL to connect with the object storage service.

You need to have the Access Key and Secret Key from the object storage provider so that Cloud Data Sense can access the buckets.



## **Deploy the Cloud Data Sense instance**

Deploy Cloud Data Sense if there isn't already an instance deployed.



## Add the Object Storage Service

Add the object storage service to Cloud Data Sense.



## Select the buckets to scan

Select the buckets that you'd like to scan and Cloud Data Sense will start scanning them.

## Reviewing object storage requirements

Review the following prerequisites to make sure that you have a supported configuration before you enable Cloud Data Sense.

- You need to have the endpoint URL to connect with the object storage service.
- You need to have the Access Key and Secret Key from the object storage provider so that Data Sense can access the buckets.
- Support for Azure Blob requires that you use the MinIO service.


## Adding the object storage service to Cloud Data Sense

You must have deployed an instance of Cloud Data Sense in Cloud Manager already.


Add the object storage service.

#### **Steps**

1. From the Working Environments Configuration page, click **Add Data Source > Add Object Storage Service**.



- 2. In the Add Object Storage Service dialog, enter the details for the object storage service and click **Continue**.
  - a. Enter the name you want to use for the Working Environment. This name should reflect the name of the object storage service to which you are connecting.
  - b. Enter the Endpoint URL to access the object storage service.
  - c. Enter the Access Key and Secret Key so that Cloud Data Sense can access the buckets in the object storage.



#### Result

The new Object Storage Service is added to the list of working environments.


## Enabling and disabling compliance scans on object storage buckets

After you enable Cloud Data Sense on your Object Storage Service, the next step is to configure the buckets


that you want to scan. Data Sense discovers those buckets and displays them in the working environment you created.

## **Steps**

1. In the Configuration page, click **Configuration** from the Object Storage Service working environment.



2. Enable mapping-only scans, or mapping and classification scans, on your buckets.



## Result

Cloud Data Sense starts scanning the buckets that you enabled. If there are any errors, they'll appear in the Status column, alongside the required action to fix the error.

#### **Copyright Information**

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

#### **Trademark Information**

NETAPP, the NETAPP logo, and the marks listed at <a href="http://www.netapp.com/TM">http://www.netapp.com/TM</a> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.