

Window Object Properties

closed	Returns a Boolean value indicating whether a window has been closed or not
console	Returns a reference to the Console object, which provides methods for logging information to the browser's console (See Console object)
defaultStatus	Sets or returns the default text in the statusbar of a window
document	Returns the Document object for the window (See Document object)
frameElement	Returns the <iframe> element in which the current window is inserted
frames	Returns all <iframe> elements in the current window
history	Returns the History object for the window (See History object)
innerHeight	Returns the height of the window's content area (viewport) including scrollbars
innerWidth	Returns the width of a window's content area (viewport) including scrollbars
length	Returns the number of <iframe> elements in the current window
localStorage	Allows to save key/value pairs in a web browser. Stores the data with no expiration date
location	Returns the Location object for the window (See Location object)
name	Sets or returns the name of a window
navigator	Returns the Navigator object for the window (See Navigator object)
opener	Returns a reference to the window that created the window
outerHeight	Returns the height of the browser window, including toolbars/scrollbars
outerWidth	Returns the width of the browser window, including toolbars/scrollbars
pageXOffset	Returns the pixels the current document has been scrolled (horizontally) from the upper left corner of the window
pageYOffset	Returns the pixels the current document has been scrolled (vertically) from the upper left corner of the window
parent	Returns the parent window of the current window
screen	Returns the Screen object for the window (See Screen object)
screenLeft	Returns the horizontal coordinate of the window relative to the screen
screenTop	Returns the vertical coordinate of the window relative to the screen
screenX	Returns the horizontal coordinate of the window relative to the screen
screenY	Returns the vertical coordinate of the window relative to the screen
sessionStorage	Allows to save key/value pairs in a web browser. Stores the data for one session
scrollX	An alias of pageXOffset
scrollY	An alias of pageYOffset
self	Returns the current window
status	Sets or returns the text in the statusbar of a window
top	Returns the topmost browser window

Window Object Methods

Method	Description
alert()	Displays an alert box with a message and an OK button
atob()	Decodes a base-64 encoded string
blur()	Removes focus from the current window
btoa()	Encodes a string in base-64
clearInterval()	Clears a timer set with setInterval()
clearTimeout()	Clears a timer set with setTimeout()
close()	Closes the current window
confirm()	Displays a dialog box with a message and an OK and a Cancel button
focus()	Sets focus to the current window
getComputedStyle()	Gets the current computed CSS styles applied to an element
getSelection()	Returns a Selection object representing the range of text selected by the user
matchMedia()	Returns a MediaQueryList object representing the specified CSS media query string
moveBy()	Moves a window relative to its current position
moveTo()	Moves a window to the specified position
open()	Opens a new browser window
print()	Prints the content of the current window
prompt()	Displays a dialog box that prompts the visitor for input
requestAnimationFrame()	Requests the browser to call a function to update an animation before the next repaint
resizeBy()	Resizes the window by the specified pixels
resizeTo()	Resizes the window to the specified width and height
scroll()	Deprecated. This method has been replaced by the scrollTo() method.
scrollBy()	Scrolls the document by the specified number of pixels

<u>scrollTo()</u>	Scrolls the document to the specified coordinates
<u>setInterval()</u>	Calls a function or evaluates an expression at specified intervals (in milliseconds)
<u>setTimeout()</u>	Calls a function or evaluates an expression after a specified number of milliseconds
<u>stop()</u>	Stops the window from loading