

skfda.preprocessing.registration.shift_registration

```
skfda.preprocessing.registration.shift_registration(fd, *, maxiter=5, tol=0.01,  
restrict_domain=False, extrapolation=None, step_size=1, initial=None, eval_points=None, **kwargs)  
\[source\]
```

Perform shift registration of the curves.

Realizes a registration of the curves, using shift alignment, as is defined in [\[RS05-7-2\]](#).
Calculates δ_i for each sample such that $x_i(t + \delta_i)$ minimizes the least squares
criterion:

$$\text{REGSSE} = \sum_{i=1}^N \int_{\mathcal{T}} [x_i(t + \delta_i) - \hat{\mu}(t)]^2 ds$$

Estimates the shift parameter δ_i iteratively by using a modified Newton-Raphson
algorithm, updating the mean in each iteration, as is described in detail in [\[RS05-7-9-1\]](#).

- Parameters:**
- **fd** (`FData`) – Functional data object to be registered.
 - **maxiter** (*int, optional*) – Maximum number of iterations. Defaults to 5.
 - **tol** (*float, optional*) – Tolerance allowable. The process will stop if $\max_i |\delta_i^{(\nu)} - \delta_i^{(\nu-1)}| < tol$. Default sets to 1e-2.
 - **restrict_domain** (*bool, optional*) – If True restricts the domain to avoid evaluate points outside the domain using extrapolation. Defaults uses extrapolation.
 - **extrapolation** (str or `Extrapolation`, optional) – Controls the extrapolation mode for elements outside the domain range. By default uses the method defined in fd. See :module: *extrapolation* to obtain more information.
 - **step_size** (*int or float, optional*) – Parameter to adjust the rate of convergence in the Newton-Raphson algorithm, see [\[RS05-7-9-1\]](#). Defaults to 1.
 - **initial** (*array_like, optional*) – Initial estimation of shifts. Default uses a list of zeros for the initial shifts.
 - **eval_points** (*array_like, optional*) – Set of points where the functions are evaluated to obtain the discrete representation of the object to integrate. If None is passed it calls `numpy.linspace` in `FDataBasis` and uses the *sample_points* in `FDataGrids`.
 - ****kwargs** – Keyword arguments to be passed to `shift()`.

Returns: `FData` A `FData` object with the curves registered.

Raises: `ValueError` – If the initial array has different length than the number of samples.

Examples

```
>>> from skfda.datasets import make_sinusoidal_process
>>> from skfda.representation.basis import Fourier
>>> from skfda.preprocessing.registration import shift_registration
>>> fd = make_sinusoidal_process(n_samples=2, error_std=0, random_state=1)
```

Registration of data in discretized form:

```
>>> shift_registration(fd)
FDataGrid(...)
```

Registration of data in basis form:

```
>>> fd = fd.to_basis(Fourier())
>>> shift_registration(fd)
FDataBasis(...)
```

References

- [RS05-7-2] Ramsay, J., Silverman, B. W. (2005). Shift registration. In *Functional Data Analysis* (pp. 129-132). Springer.
- [RS05-7-9-1] (1, 2) Ramsay, J., Silverman, B. W. (2005). Shift registration by the Newton-Raphson algorithm. In *Functional Data Analysis* (pp. 142-144). Springer.