API Reference

Authentication Endpoints
Card Endpoints
Card Checkout Endpoints
Transaction Endpoints
Merchant Endpoints
Webhook Endpoints
Error Handling
Rate Limiting
Pagination
Idempotency
Changelog

SCTSH-02 Courierwork API Reference

API Overview

Base URL: `https://api.sctsh-02.courierwork.com/v1`

Authentication: Bearer token via `Authorization` header

Content-Type: `application/json` for all request bodies

Rate Limit: 120 requests per minute per API key. Exceeding returns `429 Too Many Requests`.

> **Sandbox Mode:** Append `?sandbox=true` to any request URL to use the sandbox environment. Sandbox keys begin with `sk_test_`. Sandbox transactions do not move real funds.

Authentication Endpoints

POST `/auth/login`

Exchange credentials for a session token.

Request Body

```
{
  "email": "string",
  "password": "string",
  "mfa_code": "string | null"
}
```

Response `200 OK`

```
{
  "token": "string",
  "expires_at": "2026-04-19T14:32:00Z",
  "refresh_token": "string"
}
```

Response `401 Unauthorized`

```
{
  "error": "invalid_credentials",
  "message": "Email or password is incorrect."
}
```

POST `/auth/refresh`

Refresh an expired session token.

Request Body

```
{
  "refresh_token": "string"
}
```

Response `200 OK`

```
{
  "token": "string",
  "expires_at": "2026-04-19T14:32:00Z"
}
```

POST `/auth/logout`

Invalidate the current session token.

Response `204 No Content`

GET `/auth/me`

Return the profile of the authenticated user.

Response `200 OK`

```
{
  "id": "usr_8f2a1c",
  "email": "string",
  "name": "string",
  "role": "admin | operator | viewer",
  "created_at": "2026-04-19T14:32:00Z"
}
```

Card Endpoints

GET `/cards`

List all cards issued under the account.

Query Parameters

Parameter	Type	Description
`status`	string	Filter by `active`, `frozen`, or `cancelled`
`limit`	integer	Max results per page (default 50, max 200)
`cursor`	string	Pagination cursor from previous response

Response `200 OK`

```
{
  "data": [
    {
      "id": "crd_3b9e4f",
      "last4": "4821",
      "status": "active",
      "spend_limit_cents": 50000,
      "created_at": "2026-04-19T14:32:00Z"
    }
  ],
  "next_cursor": "string | null"
}
```

POST `/cards`

Issue a new card.

Request Body

```
{
  "spend_limit_cents": 50000,
  "label": "string | null"
}
```

Response `201 Created`

```
{
  "id": "crd_3b9e4f",
  "last4": "4821",
  "status": "active",
  "spend_limit_cents": 50000,
  "label": "string | null",
  "created_at": "2026-04-19T14:32:00Z"
}
```

GET `/cards/{card_id}`

Retrieve a single card by ID.

Response `200 OK`

```
{
  "id": "crd_3b9e4f",
  "last4": "4821",
  "status": "active",
  "spend_limit_cents": 50000,
  "label": "string | null",
  "created_at": "2026-04-19T14:32:00Z"
}
```

PATCH `/cards/{card_id}`

Update a card's status or spend limit.

Request Body

```
{
  "status": "active | frozen | cancelled",
  "spend_limit_cents": 75000
}
```

Response `200 OK`

```
{
  "id": "crd_3b9e4f",
  "last4": "4821",
  "status": "frozen",
  "spend_limit_cents": 75000,
  "label": "string | null",
  "created_at": "2026-04-19T14:32:00Z"
}
```

DELETE `/cards/{card_id}`

Cancel a card permanently. Equivalent to `PATCH` with `status: "cancelled"`.

Response `204 No Content`

Card Checkout Endpoints

GET `/checkout/sessions`

List checkout sessions for the account.

Query Parameters

Parameter	Type	Description
`status`	string	Filter by `open`, `complete`, `expired`
`limit`	integer	Max results per page (default 50, max 200)
`cursor`	string	Pagination cursor from previous response

Response `200 OK`

```
{
  "data": [
    {
      "id": "cs_9d1f2a",
      "status": "open",
      "amount_cents": 12500,
      "currency": "usd",
      "created_at": "2026-04-19T14:32:00Z"
    }
  ],
  "next_cursor": "string | null"
}
```

POST `/checkout/sessions`

Create a new checkout session.

Request Body

```
{
  "amount_cents": 12500,
  "currency": "usd",
  "success_url": "https://example.com/success",
  "cancel_url": "https://example.com/cancel",
  "metadata": {}
}
```

Response `201 Created`

```
{
  "id": "cs_9d1f2a",
  "status": "open",
  "amount_cents": 12500,
  "currency": "usd",
  "success_url": "https://example.com/success",
  "cancel_url": "https://example.com/cancel",
  "metadata": {},
  "created_at": "2026-04-19T14:32:00Z"
}
```

GET `/checkout/sessions/{session_id}`

Retrieve a checkout session by ID.

Response `200 OK`

```
{
  "id": "cs_9d1f2a",
  "status": "open",
  "amount_cents": 12500,
  "currency": "usd",
  "success_url": "https://example.com/success",
  "cancel_url": "https://example.com/cancel",
  "metadata": {},
  "created_at": "2026-04-19T14:32:00Z"
}
```

POST `/checkout/sessions/{session_id}/expire`

Expire a checkout session before it is completed.

Response `200 OK`

```
{
  "id": "cs_9d1f2a",
  "status": "expired",
  "amount_cents": 12500,
  "currency": "usd",
  "success_url": "https://example.com/success",
  "cancel_url": "https://example.com/cancel",
  "metadata": {},
  "created_at": "2026-04-19T14:32:00Z"
}
```

Transaction Endpoints

GET `/transactions`

List transactions, newest first.

Query Parameters

Parameter	Type	Description
`card_id`	string	Filter by card
`merchant_id`	string	Filter by merchant
`status`	string	`pending`, `settled`, `declined`, `refunded`
`from`	ISO 8601	Start of date range
`to`	ISO 8601	End of date range
`limit`	integer	Max results per page (default 50, max 200)
`cursor`	string	Pagination cursor from previous response

Response `200 OK`

```
{
  "data": [
    {
      "id": "txn_7c4d2e",
      "card_id": "crd_3b9e4f",
      "merchant_id": "mer_1a8b",
      "amount_cents": 4299,
      "currency": "USD",
      "status": "settled",
      "created_at": "2026-04-19T14:32:00Z"
    }
  ],
  "next_cursor": "string | null"
}
```

GET `/transactions/{txn_id}`

Retrieve a single transaction by ID.

Response `200 OK`

```
{
  "id": "txn_7c4d2e",
  "card_id": "crd_3b9e4f",
  "merchant_id": "mer_1a8b",
  "amount_cents": 4299,
  "currency": "USD",
  "status": "settled",
  "created_at": "2026-04-19T14:32:00Z"
}
```

POST `/transactions/{txn_id}/refund`

Refund a settled transaction. Omit `amount_cents` for a full refund.

Request Body

```
{
  "amount_cents": 4299,
  "reason": "string | null"
}
```

Response `200 OK`

```
{
  "id": "txn_7c4d2e",
  "card_id": "crd_3b9e4f",
  "merchant_id": "mer_1a8b",
  "amount_cents": 4299,
  "currency": "USD",
  "status": "refunded",
  "created_at": "2026-04-19T14:32:00Z"
}
```

Merchant Endpoints

GET `/merchants`

List merchants the account has transacted with.

Response `200 OK`

```
{
  "data": [
    {
      "id": "mer_1a8b",
      "name": "string",
      "mcc": "5411",
      "city": "string",
      "country": "US"
    }
  ],
  "next_cursor": "string | null"
}
```

GET `/merchants/{merchant_id}`

Retrieve a single merchant by ID.

Response `200 OK`

```
{
  "id": "mer_1a8b",
  "name": "string",
  "mcc": "5411",
  "city": "string",
  "country": "US"
}
```

Webhook Endpoints

POST `/webhooks`

Register a webhook endpoint.

Request Body

```
{
  "url": "https://example.com/hooks",
  "events": ["transaction.settled", "card.frozen"]
}
```

Response `201 Created`

```
{
  "id": "wh_5e3a1b",
  "url": "https://example.com/hooks",
  "events": ["transaction.settled", "card.frozen"],
  "secret": "whsec_...",
  "created_at": "2026-04-19T14:32:00Z"
}
```

GET `/webhooks`

List registered webhook endpoints.

Response `200 OK`

```
{
  "data": [
    {
      "id": "wh_5e3a1b",
      "url": "https://example.com/hooks",
      "events": ["transaction.settled", "card.frozen"],
      "created_at": "2026-04-19T14:32:00Z"
    }
  ]
}
```

DELETE `/webhooks/{webhook_id}`

Remove a webhook endpoint.

Response `204 No Content`

Error Handling

All errors return a consistent envelope:

```
{
  "error": "machine_readable_code",
  "message": "Human-readable explanation.",
  "request_id": "req_..."
}
```

Include `request_id` when contacting support.

HTTP Status Codes

Code	Meaning	When it's Used
`200`	OK	Successful GET, PATCH, or POST
`201`	Created	Resource successfully created
`204`	No Content	Successful DELETE
`400`	Bad Request	Malformed JSON or missing required field
`401`	Unauthorized	Missing or invalid token
`403`	Forbidden	Valid token but insufficient permissions
`404`	Not Found	Resource does not exist
`409`	Conflict	Duplicate idempotency key
`422`	Unprocessable Entity	Validation failed
`429`	Too Many Requests	Rate limit exceeded
`500`	Internal Server Error	Something went wrong on our side

Rate Limiting

Responses include `X-RateLimit-Remaining` and `X-RateLimit-Reset` headers. Back off until the reset timestamp when remaining reaches zero.

Pagination

All list endpoints use cursor pagination. Pass `next_cursor` from the previous response as `cursor` to fetch the next page. Omit `cursor` for the first page.

Idempotency

Send `Idempotency-Key: <uuid>` on any `POST` request. Retries with the same key return the original response for 24 hours.

Changelog

2026-04-19
- Added `/checkout/sessions` endpoints
- Added `/transactions/{txn_id}/refund`
- Added `/webhooks` endpoints

2026-03-02
- Added `/merchants` endpoints
- Added `/auth/me`

2026-01-15
- Initial release