

Welcome To Presentate!

Tools for creating integrated dynamic slides.

@pacaunt | 2025-11-22

Outline


Outline

1	Introduction	5
1.1	Presentation by Coding?	6
1.2	A note about animating PDFs	7
1.3	Integration of Tools	8
1.4	About Presentate	11
1.5	Acknowledgement	12
2	Usage	13
2.1	Getting Started	14
2.2	Dynamic Components	19
2.3	<code>#pause</code> function	20
2.4	<code>#fragments</code> function	21
2.5	The <code>#step-item</code> function	22
2.6	The <code>#hider</code> argument	24


2.7	<code>#only</code> and <code>#uncover</code>	26
2.8	Relative Indices	30
2.9	Varying Timeline	33
2.10	Animated Decorations	37
2.11	Rendering Stuffs	40
2.12	Animate the inanimate	50
2.13	Modes and Utility	53
2.14	Themes	54

1 Introduction


1.1 Presentation by Coding?



Presentation's objective is to convey information to the audiences. **Slide deck** is one of visual media we can use for such tasks.



1.1 Presentation by Coding?





Presentation's objective is to convey information to the audiences. **Slide deck** is one of visual media we can use for such tasks.

Often, using visual tools is easy, as you can modify what you want. However, we have to admit that sometimes creating visual media is *easier in code*.



1.1 Presentation by Coding?





Presentation's objective is to convey information to the audiences. **Slide deck** is one of visual media we can use for such tasks.

Often, using visual tools is easy, as you can modify what you want. However, we have to admit that sometimes creating visual media is *easier in code*.

Imagine creating visual graphs that update directly from your source project.

1.1 Presentation by Coding?





Presentation's objective is to convey information to the audiences. **Slide deck** is one of visual media we can use for such tasks.

Often, using visual tools is easy, as you can modify what you want. However, we have to admit that sometimes creating visual media is *easier in code*.

Imagine creating visual graphs that update directly from your source project.

So you don't have to update them manually.

1.1 Presentation by Coding?



Presentation's objective is to convey information to the audiences. **Slide deck** is one of visual media we can use for such tasks.

Often, using visual tools is easy, as you can modify what you want. However, we have to admit that sometimes creating visual media is *easier in code*.

Imagine creating visual graphs that update directly from your source project.

So you *don't have to update them manually*.

1.2 A note about animating PDFs

Creating presentation in Typst, especially in PDF format, cannot provide the *actual animated* scenes like videos.

1.2 A note about animating PDFs

Creating presentation in Typst, especially in PDF format, cannot provide the *actual animated* scenes like videos.

However, the *dynamic* contents on the following examples are generated by *repeatedly printed* each page, which contains slightly different components.

1.2 A note about animating PDFs

Creating presentation in Typst, especially in PDF format, cannot provide the *actual animated* scenes like videos.

However, the *dynamic* contents on the following examples are generated by *repeatedly printed* each page, which contains slightly different components.



So that when you see on the screen, it *looks like* the contents are changing.

1.3 Integration of Tools

Presentate is another package written in Typst for creating slides.

1.3 Integration of Tools

Presentate is another package written in Typst for creating slides.

We already have other powerful presentation packages! So it rises a question:

1.3 Integration of Tools

Presentate is another package written in Typst for creating slides.

We already have other powerful presentation packages! So it rises a question:

Why creating another?

1.3 Integration of Tools

Presentate is another package written in Typst for creating slides.

We already have other powerful presentation packages! So it rises a question:

Why creating another?

The answer is **Package Integrations**.

1.3 Integration of Tools

Slide animation requires information in type content; however, most packages for creating visual data output requires *non-content* input, such as

1.3 Integration of Tools

Slide animation requires information in type content; however, most packages for creating visual data output requires *non-content* input, such as

- CeTZ: arrays of functions

1.3 Integration of Tools

Slide animation requires information in type content; however, most packages for creating visual data output requires *non-content* input, such as

- CeTZ: arrays of functions
- Fletcher: special metadata

1.3 Integration of Tools


Slide animation requires information in type content; however, most packages for creating visual data output requires *non-content* input, such as

- CeTZ: arrays of functions
- Fletcher: special metadata
- Alchemist: arrays of dictionary

1.3 Integration of Tools

Slide animation requires information in type content; however, most packages for creating visual data output requires *non-content* input, such as


- CeTZ: arrays of functions
- Fletcher: special metadata
- Alchemist: arrays of dictionary



1.3 Integration of Tools

Slide animation requires information in type content; however, most packages for creating visual data output requires *non-content* input, such as

- CeTZ: arrays of functions
- Fletcher: special metadata
- Alchemist: arrays of dictionary



So to create animation with those packages, we need some functionality to be able to *hide* the information *without* content generation.

1.3 Integration of Tools

Here is when presentate comes in.

¹<https://typst.app/universe/package/alchemy>

1.3 Integration of Tools

Here is when presentate comes in.

Presentate provides a framework for rendering input and output of *any kind*.

Like the following molecule drawing animation from [Alchemist](#)¹ package:


¹<https://typst.app/universe/package/alchemist>

1.3 Integration of Tools

Here is when presentate comes in.

Presentate provides a framework for rendering input and output of *any kind*.

Like the following molecule drawing animation from [Alchemist](#)¹ package:




¹<https://typst.app/universe/package/alchemist>

1.3 Integration of Tools

Here is when presentate comes in.

Presentate provides a framework for rendering input and output of *any kind*.

Like the following molecule drawing animation from [Alchemist](#)¹ package:




¹<https://typst.app/universe/package/alchemist>

1.3 Integration of Tools

Here is when presentate comes in.

Presentate provides a framework for rendering input and output of *any kind*.

Like the following molecule drawing animation from [Alchemist](#)¹ package:




¹<https://typst.app/universe/package/alchemist>

1.3 Integration of Tools

Here is when presentate comes in.

Presentate provides a framework for rendering input and output of *any kind*.

Like the following molecule drawing animation from [Alchemist](#)¹ package:





¹<https://typst.app/universe/package/alchemist>

1.3 Integration of Tools

Here is when presentate comes in.

Presentate provides a framework for rendering input and output of *any kind*.

Like the following molecule drawing animation from [Alchemist](#)¹ package:





¹<https://typst.app/universe/package/alchemist>

1.3 Integration of Tools

Here is when presentate comes in.

Presentate provides a framework for rendering input and output of *any kind*.

Like the following molecule drawing animation from [Alchemist](#)¹ package:





¹<https://typst.app/universe/package/alchemist>

1.3 Integration of Tools

Here is when presentate comes in.

Presentate provides a framework for rendering input and output of *any kind*.

Like the following molecule drawing animation from [Alchemist](#)¹ package:



¹<https://typst.app/universe/package/alchemist>

1.4 About Presentate

Presentate is a package aiming to provide a *framework* for creating dynamic presentation animations that are *flexible* enough to be used with any packages.

1.4 About Presentate

Presentate is a package aiming to provide a *framework* for creating dynamic presentation animations that are *flexible* enough to be used with any packages.

The package provides:

1.4 About Presentate

Presentate is a package aiming to provide a *framework* for creating dynamic presentation animations that are *flexible* enough to be used with any packages.

The package provides:

- revealing content step-by-step from
`#show: pause,`

1.4 About Presentate

Presentate is a package aiming to provide a *framework* for creating dynamic presentation animations that are *flexible* enough to be used with any packages.

The package provides:

- revealing content step-by-step from
`#show: pause,`
- revealing content specifically from
`#uncover(..)` and `#only(..),`

1.4 About Presentate

Presentate is a package aiming to provide a *framework* for creating dynamic presentation animations that are *flexible* enough to be used with any packages.

The package provides:

- revealing content step-by-step from `#show: pause`,
- revealing content specifically from `#uncover(...)` and `#only(...)`,
- transform content by `#transform(...)`,

1.4 About Presentate

Presentate is a package aiming to provide a *framework* for creating dynamic presentation animations that are *flexible* enough to be used with any packages.

The package provides:

- revealing content step-by-step from `#show: pause`,
- revealing content specifically from `#uncover(...)` and `#only(...)`,
- transform content by `#transform(...)`,
- relative index like `#auto` and `#none`,

1.4 About Presentate

Presentate is a package aiming to provide a *framework* for creating dynamic presentation animations that are *flexible* enough to be used with any packages.

The package provides:

- revealing content step-by-step from `#show: pause`,
- revealing content specifically from `#uncover(...)` and `#only(...)`,
- transform content by `#transform(...)`,
- relative index like `#auto` and `#none`,
- render frame for package integration, with `#animation` module.

1.5 Acknowledgement

The package was created by mixing my original motivation and inspirations from many existing presentation packages.

Thanks to: [Polylux](#)² for `subslide` implementation and `pdfpc` support, [Touying](#)³ for idea of render frame, fake frozen states, and [Minideck](#)⁴ for `#only`, and `#uncover` functions.

²<https://github.com/polylux-typ/polylux>

³<https://github.com/touying-typ/touying>

⁴<https://github.com/knuesel/typst-minideck>

2 Usage

2.1 Getting Started

Start with the following snippets:

```
1 #import "@preview/presentate:0.2.2": *
2 #set text(size: 25pt) // of your choice
3
4 #slide[
5   Hello World!
6   #show: pause;
7
8   This is `presentate`.
9 ]
```

2.1 Getting Started

Then you will have:

Hello World!

Hello World!

This is presentate.

2.1 Getting Started

You may styling the way you want, for example:

```
1 #import "@preview/presentate:0.2.2": *
2 #set page(paper: "presentation-16-9")
3 #set text(size: 25pt, font: "FiraCode Nerd Font Mono")
4 #set align(horizon)
5 #slide[
6   = Welcome to Presentate!
7   \ A lazy author \
8   #datetime.today().display()
9 ]
```

2.1 Getting Started

(continued)

```
10 #set align(top)
11 #slide[
12   == Tips for Typst.
13   #set align(horizon)
14   Do you know that  $\pi \neq$ 
15   3.141592?
16   #show: pause
17   Yeah. Certainly.
```

```
18
19   #show: pause
20   Also  $\pi \neq 22/7$ .
21 ]
```

2.1 Getting Started

(continued)

```
10 #set align(top)
11 #slide[
12   == Tips for Typst.
13   #set align(horizon)
14   Do you know that  $\pi \neq 3.141592$ ?
15
16   #show: pause
17   Yeah. Certainly.
```

```
18
19   #show: pause
20   Also  $\pi \neq 22/7$ .
21 ]
```

Presentate does not interfere Typst styling systems, so you can set and unset anything freely.

The results are on the next slide:

2.1 Getting Started

<p>Welcome to Presentate!</p> <p>A lazy author 2025-08-11</p>	<p>Tips for Typst.</p> <p>Do you know that $\pi \neq 3.141592$?</p>
<p>Tips for Typst.</p> <p>Do you know that $\pi \neq 3.141592$? Yeah. Certainly.</p>	<p>Tips for Typst.</p> <p>Do you know that $\pi \neq 3.141592$? Yeah. Certainly. Also $\pi \neq \frac{22}{7}$.</p>

2.2 Dynamic Components

`#slide[...]` function provides a workspace for creating *animations*.
As the example showing the use of `#show: pause` functionality.

2.2 Dynamic Components

`#slide[...]` function provides a workspace for creating *animations*.

As the example showing the use of `#show: pause` functionality.

Presentate provides the following functions for creating dynamic slides:

2.2 Dynamic Components

`#slide[...]` function provides a workspace for creating *animations*.

As the example showing the use of `#show: pause` functionality.

Presentate provides the following functions for creating dynamic slides:

1. `#pause(...)` for basic reveal of content in chunks.

2.2 Dynamic Components

`#slide[...]` function provides a workspace for creating *animations*.

As the example showing the use of `#show: pause` functionality.

Presentate provides the following functions for creating dynamic slides:

1. `#pause(...)` for basic reveal of content in chunks.
2. `#uncover(...)` and `#only(...)` for precise steps of revealing content.

2.2 Dynamic Components

`#slide[...]` function provides a workspace for creating *animations*.

As the example showing the use of `#show: pause` functionality.

Presentate provides the following functions for creating dynamic slides:

1. `#pause(...)` for basic reveal of content in chunks.
2. `#uncover(...)` and `#only(...)` for precise steps of revealing content.
3. `#fragments(...)` for revealing content one-by-one.

2.2 Dynamic Components

`#slide[...]` function provides a workspace for creating *animations*.

As the example showing the use of `#show: pause` functionality.

Presentate provides the following functions for creating dynamic slides:

1. `#pause(...)` for basic reveal of content in chunks.
2. `#uncover(...)` and `#only(...)` for precise steps of revealing content.
3. `#fragments(...)` for revealing content one-by-one.
4. `#transform(...)` for transform the content by functions.

2.2 Dynamic Components

`#slide[...]` function provides a workspace for creating *animations*.

As the example showing the use of `#show: pause` functionality.

Presentate provides the following functions for creating dynamic slides:

1. `#pause(...)` for basic reveal of content in chunks.
2. `#uncover(...)` and `#only(...)` for precise steps of revealing content.
3. `#fragments(...)` for revealing content one-by-one.
4. `#transform(...)` for transform the content by functions.
5. `#render(...)` and `#animate(...)` for handling non-content type data.

2.3 #pause function

Basic usage of `#pause(. .)` is usually in the form `#show: pause`.

Apart from that, you can put any content in the `(. .)`, e.g. math equations.

2.3 #pause function

Basic usage of `#pause(. .)` is usually in the form `#show: pause`.

Apart from that, you can put any content in the `(. .)`, e.g. math equations.

$$(x + y)^2$$

2.3 #pause function

Basic usage of `#pause(. .)` is usually in the form `#show: pause`.

Apart from that, you can put any content in the `(. .)`, e.g. math equations.

$$(x + y)^2 = (x + y)(x + y)$$

2.3 #pause function

Basic usage of `#pause(. .)` is usually in the form `#show: pause`.

Apart from that, you can put any content in the `(. .)`, e.g. math equations.

$$\begin{aligned}(x + y)^2 &= (x + y)(x + y) \\ &= x^2 + 2xy + y^2\end{aligned}$$

2.3 #pause function

Basic usage of `#pause(. .)` is usually in the form `#show: pause`.

Apart from that, you can put any content in the `(. .)`, e.g. math equations.

$$\begin{aligned}(x + y)^2 &= (x + y)(x + y) \\ &= x^2 + 2xy + y^2\end{aligned}$$

as from

```
1 $ (x + y)^2 #pause(&= (x + y)(x + y)) \  
2           #pause(&= x^2 + 2 x y + y^2) $
```

2.4 #fragments function

Imagine having to type

```
1 #pause[+ A]  
2 #pause[+ B]  
3 #pause[+ C]
```

to reveal A to C consecutively;

2.4 #fragments function

Imagine having to type

```
1 #pause[+ A]  
2 #pause[+ B]  
3 #pause[+ C]
```

to reveal A to C consecutively; however,
we have a better way.

2.4 #fragments function

Imagine having to type

```
1 #pause[+ A]
2 #pause[+ B]
3 #pause[+ C]
```

to reveal A to C consecutively; however,
we have a better way.

Introducing #fragments(...):

```
1 #fragments[+ A][+ B][+ C]
```

2.4 #fragments function

Imagine having to type

```
1 #pause[+ A]
2 #pause[+ B]
3 #pause[+ C]
```

to reveal A to C consecutively; however, we have a better way.

Introducing #fragments(...):

```
1 #fragments[+ A][+ B][+ C]
```

Output:

```
1.
2.
3.
```

2.4 #fragments function

Imagine having to type

```
1 #pause[+ A]
2 #pause[+ B]
3 #pause[+ C]
```

to reveal A to C consecutively; however, we have a better way.

Introducing #fragments(...):

```
1 #fragments[+ A][+ B][+ C]
```

Output:

```
1. A
2.
3.
```


2.4 #fragments function

Imagine having to type

```
1 #pause[+ A]
2 #pause[+ B]
3 #pause[+ C]
```

to reveal A to C consecutively; however, we have a better way.

Introducing #fragments(...):

```
1 #fragments[+ A][+ B][+ C]
```

Output:

```
1. A
2. B
3.
```

2.4 #fragments function

Imagine having to type

```
1 #pause[+ A]
2 #pause[+ B]
3 #pause[+ C]
```

to reveal A to C consecutively; however, we have a better way.

Introducing #fragments(...):

```
1 #fragments[+ A][+ B][+ C]
```

Output:

```
1. A
2. B
3. C
```

2.4 #fragments function

Imagine having to type

```
1 #pause[+ A]
2 #pause[+ B]
3 #pause[+ C]
```

to reveal A to C consecutively; however, we have a better way.

Introducing `#fragments(...)`:

```
1 #fragments[+ A][+ B][+ C]
```

Output:

```
1. A
2. B
3. C
```

Note: default `#hide` function cannot hide the number or list markers. To solve this, we will introduce the alternative way to 'hide' them.

2.5 The `#step-item` function


This function was created specifically for step-by-step revealing lists and enums, with ability to hide the markers and numbers.

2.5 The `#step-item` function

This function was created specifically for step-by-step revealing lists and enums, with ability to hide the markers and numbers.

```
1 #step-item[  
2   + First Item  
3   + Second Item  
4   + Third Item  
5 ]
```

Output:



2.5 The `#step-item` function

This function was created specifically for step-by-step revealing lists and enums, with ability to hide the markers and numbers.

```
1 #step-item[  
2   + First Item  
3   + Second Item  
4   + Third Item  
5 ]
```

Output:

1. First Item

2.5 The `#step-item` function

This function was created specifically for step-by-step revealing lists and enums, with ability to hide the markers and numbers.

```
1 #step-item[  
2   + First Item  
3   + Second Item  
4   + Third Item  
5 ]
```

Output:

1. First Item
2. Second Item

2.5 The `#step-item` function

This function was created specifically for step-by-step revealing lists and enums, with ability to hide the markers and numbers.

```
1 #step-item[  
2   + First Item  
3   + Second Item  
4   + Third Item  
5 ]
```

Output:


1. First Item
2. Second Item
3. Third Item

2.5 The `#step-item` function

It can be nested as long as you like.

```
1 #step-item[  
2   + First Item  
3   #step-item[  
4     - Sub-First  
5     - Sub-First-Second  
6   ]  
7   + Second Item  
8   + Third Item  
9 ]
```

Output:



2.5 The `#step-item` function

It can be nested as long as you like.

```
1 #step-item[
2   + First Item
3   #step-item[
4     - Sub-First
5     - Sub-First-Second
6   ]
7 + Second Item
8 + Third Item
9 ]
```

Output:

1. First Item

2.5 The `#step-item` function

It can be nested as long as you like.

```
1 #step-item[
2   + First Item
3   #step-item[
4     - Sub-First
5     - Sub-First-Second
6   ]
7 + Second Item
8 + Third Item
9 ]
```

Output:

1. First Item
 - Sub-First

2.5 The `#step-item` function

It can be nested as long as you like.

```
1 #step-item[  
2   + First Item  
3   #step-item[  
4     - Sub-First  
5     - Sub-First-Second  
6   ]  
7   + Second Item  
8   + Third Item  
9 ]
```

Output:

1. First Item
 - Sub-First
 - Sub-First-Second

2.5 The `#step-item` function

It can be nested as long as you like.

```
1 #step-item[
2   + First Item
3   #step-item[
4     - Sub-First
5     - Sub-First-Second
6   ]
7 + Second Item
8 + Third Item
9 ]
```

Output:

1. First Item
 - Sub-First
 - Sub-First-Second
2. Second Item

2.5 The `#step-item` function

It can be nested as long as you like.

```
1 #step-item[
2   + First Item
3   #step-item[
4     - Sub-First
5     - Sub-First-Second
6   ]
7 + Second Item
8 + Third Item
9 ]
```

Output:

1. First Item
 - Sub-First
 - Sub-First-Second
2. Second Item
3. Third Item

2.5 The `#step-item` function

It can be nested as long as you like.

```
1 #step-item[
2   + First Item
3   #step-item[
4     - Sub-First
5     - Sub-First-Second
6   ]
7 + Second Item
8 + Third Item
9 ]
```

Output:

1. First Item
 - Sub-First
 - Sub-First-Second
2. Second Item
3. Third Item

It works by modifying `item` input and the markers with varying timeline of `#pause`.

2.6 The `#hider` argument

Every function that can ‘hide’ and reveal content has a named argument called `#hider`. This argument has a default value of Typst’s native `#hide()` function.

2.6 The `#hider` argument

Every function that can ‘hide’ and reveal content has a named argument called `#hider`. This argument has a default value of Typst’s native `#hide()` function.

However, if you want other modes of *hiding* something? E.g. make it *transparent*. You can modify this with `#text.with(fill: gray.transparentize(50%))`:

2.6 The `#hider` argument

```
1 #let lg = gray.transparentize(50%)
2 #let pause = pause.with(hider: text.with(lg))
3
4 Hello!
5 #show: pause
6
7 It's gray
```

Output:

Hello!

It's gray

2.6 The `#hider` argument

```
1 #let lg = gray.transparentize(50%)
2 #let pause = pause.with(hider: text.with(lg))
3
4 Hello!
5 #show: pause
6
7 It's gray
```

Output:

Hello!
It's gray

2.7 #only and #uncover

So far, #pause and #fragments examples only show you to reveal the content *step-by-step*. How about *absolutely* reveal content? Say, at a given number of frames?

2.7 #only and #uncover

So far, #pause and #fragments examples only show you to reveal the content *step-by-step*. How about *absolutely* reveal content? Say, at a given number of frames?

A **frame** or **subslide** is a page that contains fragments of slides' content, so that when all pages are viewed consecutively, we can see the *change* of content.

2.7 **#only** and **#uncover**

So far, **#pause** and **#fragments** examples only show you to reveal the content *step-by-step*. How about *absolutely* reveal content? Say, at a given number of frames?

A **frame** or **subslide** is a page that contains fragments of slides' content, so that when all pages are viewed consecutively, we can see the *change* of content.

For a more complex animation, **#only** and **#uncover** functions can control when the content will be shown based on given number of frames, or *subslide number*.

2.7 #only and #uncover

```
1 Content Before
2
3 #only(2, 4)[
4   This is _only_ shown on
   subslide 2 and 4.
5 ]
6
7 Content After
```

Output: on subslide 1

Content Before

Content After

2.7 #only and #uncover

```
1 Content Before
2
3 #only(2, 4)[
4   This is _only_ shown on
   subslide 2 and 4.
5 ]
6
7 Content After
```

Output: on subslide 2

Content Before

This is *only* shown on subslide 2 and 4.

Content After

`#only(..n, body)` shows the `#body` *only* at the given subslide numbers `#n`.
For other frames, the content is vanished, with no preserved space.

2.7 #only and #uncover

```
1 Content Before
2
3 #only(2, 4)[
4   This is _only_ shown on
5   subslide 2 and 4.
6 ]
7 Content After
```

Output: on subslide 3

Content Before

Content After

`#only(..n, body)` shows the `#body only` at the given subslide numbers `#n`.
For other frames, the content is vanished, with no preserved space.

2.7 #only and #uncover

```
1 Content Before
2
3 #only(2, 4)[
4   This is _only_ shown on
   subslide 2 and 4.
5 ]
6
7 Content After
```

Output: on subslide 4

Content Before

This is *only* shown on subslide 2 and 4.

Content After

`#only(..n, body)` shows the `#body` *only* at the given subslide numbers `#n`.
For other frames, the content is vanished, with no preserved space.

2.7 #only and #uncover

```
1 Content Before
2
3 #uncover(2, from: 4)[
4   This is _uncovered_ on
5   subslide 2 and 4 onwards.
6 ]
7 Content After
```

Output: on subslide 1

Content Before

Content After

2.7 #only and #uncover

```
1 Content Before
2
3 #uncover(2, from: 4)[
4   This is _uncovered_ on
5   subslide 2 and 4 onwards.
6 ]
7 Content After
```

Output: on subslide 2

Content Before

This is *uncovered* on subslide 2 and 4
onwards.

Content After

`#uncover(..n, from: int, body)` uncovers the `#body` in the same condition as `#only`, with an exception of having *space preserved*.

2.7 #only and #uncover

```
1 Content Before
2
3 #uncover(2, from: 4)[
4   This is uncovered on
5   subslide 2 and 4 onwards.
6 ]
7 Content After
```

Output: on subslide 3

Content Before

Content After

`#uncover(..n, from: int, body)` uncovers the `#body` in the same condition as `#only`, with an exception of having *space preserved*.

2.7 #only and #uncover

```
1 Content Before
2
3 #uncover(2, from: 4)[
4   This is _uncovered_ on
5   subslide 2 and 4 onwards.
6 ]
7 Content After
```

Output: on subslide 4

Content Before

This is *uncovered* on subslide 2 and 4
onwards.

Content After

`#uncover(..n, from: int, body)` uncovers the `#body` in the same condition as `#only`, with an exception of having *space preserved*.

2.7 #only and #uncover

If you noticed the last example carefully, you will see the argument `#from` being introduced in the `#uncover(from: int, ..)`.

2.7 #only and #uncover

If you noticed the last example carefully, you will see the argument `#from` being introduced in the `#uncover(from: int, ..)`.

Both `#only` and `#uncover` can take the `#from` as integer to start revealing the content only after that subslide number `#from`.

2.7 `#only` and `#uncover`

If you noticed the last example carefully, you will see the argument `#from` being introduced in the `#uncover(from: int, ..)`.

Both `#only` and `#uncover` can take the `#from` as integer to start revealing the content only after that subslide number `#from`.

Not only integers can you use as subslide number, `#auto` and `#none` also can be used. What do they do?

2.8 Relative Indices

If you want to reveal a yellow box once in a frame after some stream of content, say the following code:

```
1 Content #show: pause; Content
2
3 #uncover(3, rect(
4   fill: yellow, [BOX]
5 ))
```

Output: on subslide 1

Content

2.8 Relative Indices

If you want to reveal a yellow box once in a frame after some stream of content, say the following code:

```
1 Content #show: pause; Content  
2  
3 #uncover(3, rect(  
4   fill: yellow, [BOX]  
5 ))
```

Output: on subslide 2

Content Content

2.8 Relative Indices

If you want to reveal a yellow box once in a frame after some stream of content, say the following code:

```
1 Content #show: pause; Content
2
3 #uncover(3, rect(
4   fill: yellow, [BOX]
5 ))
```

Output: on subslide 3

Content Content

BOX

You must know the current number of `#pauses` to determine the subslide number where the BOX must be shown.

2.8 Relative Indices

If you want to reveal a yellow box once in a frame after some stream of content, say the following code:

```
1 Content #show: pause; Content
2
3 #uncover(3, rect(
4   fill: yellow, [BOX]
5 ))
```

Output: on subslide 4



Content Content

You must know the current number of `#pauses` to determine the subslide number where the BOX must be shown. Is there an alternative? [Yes: Relative Indices](#)

2.8 Relative Indices

Index (plural: Indices) is subslide number.

Index specified in **#uncover**, **#only**, and other arguments that requires it has 2 types:

2.8 Relative Indices

Index (plural: Indices) is subslide number.

Index specified in **#uncover**, **#only**, and other arguments that requires it has 2 types:

1. **Absolute** index: the actual integer subslide number, and

2.8 Relative Indices

Index (plural: Indices) is subslide number.

Index specified in *#uncover*, *#only*, and other arguments that requires it has 2 types:

1. **Absolute** index: the actual integer subslide number, and
2. **Relative** index: *#auto* and *#none*, relative to *number of pauses*

2.8 Relative Indices

Index (plural: Indices) is subslide number.

Index specified in *#uncover*, *#only*, and other arguments that requires it has 2 types:

1. **Absolute** index: the actual integer subslide number, and
2. **Relative** index: *#auto* and *#none*, relative to *number of pauses*
 - *#auto* means index *after* the current number of pauses.

2.8 Relative Indices

Index (plural: Indices) is subslide number.

Index specified in *#uncover*, *#only*, and other arguments that requires it has 2 types:

1. **Absolute** index: the actual integer subslide number, and
2. **Relative** index: *#auto* and *#none*, relative to *number of pauses*
 - *#auto* means index *after* the current number of pauses.
 - *#none* means index *as same as* the current number of pauses.

2.8 Relative Indices

Example: Uncover the yellow box on subslide 5 and after current pauses state, together with only show X on the same subslide as the current pauses.

```
1 Content #show: pause; Content
2
3 #uncover(auto, 5, rect(
4   fill: yellow, [BOX]
5 ))
6
7 After Content #only(none, [X])
```

Output: on subslide 1

Content

2.8 Relative Indices

Example: Uncover the yellow box on subslide 5 and after current pauses state, together with only show X on the same subslide as the current pauses.

```
1 Content #show: pause; Content
2
3 #uncover(auto, 5, rect(
4   fill: yellow, [BOX]
5 ))
6
7 After Content #only(none, [X])
```

Output: on subslide 2

Content Content

After Content X

2.8 Relative Indices

Example: Uncover the yellow box on subslide 5 and after current pauses state, together with only show X on the same subslide as the current pauses.

```
1 Content #show: pause; Content
2
3 #uncover(auto, 5, rect(
4   fill: yellow, [BOX]
5 ))
6
7 After Content #only(none, [X])
```

Output: on subslide 3

Content Content

BOX

After Content

2.8 Relative Indices

Example: Uncover the yellow box on subslide 5 and after current pauses state, together with only show X on the same subslide as the current pauses.

```
1 Content #show: pause; Content
2
3 #uncover(auto, 5, rect(
4   fill: yellow, [BOX]
5 ))
6
7 After Content #only(none, [X])
```

Output: on subslide 4

Content Content

After Content

2.8 Relative Indices

Example: Uncover the yellow box on subslide 5 and after current pauses state, together with only show X on the same subslide as the current pauses.

```
1 Content #show: pause; Content
2
3 #uncover(auto, 5, rect(
4   fill: yellow, [BOX]
5 ))
6
7 After Content #only(none, [X])
```

Output: on subslide 5

Content Content

BOX

After Content

2.9 Varying Timeline

If you look at the last example carefully, it is noticeable that when After Content appears, it follows the `#show: pause` function, as if there were no `#uncover` in between.

2.9 Varying Timeline

If you look at the last example carefully, it is noticeable that when After Content appears, it follows the `#show: pause` function, as if there were no `#uncover` in between.

However, what if we want to reveal some content afterwards, after every animation, without the need of specifying the subslide number?

2.9 Varying Timeline

If you look at the last example carefully, it is noticeable that when `After Content` appears, it follows the `#show: pause` function, as if there were no `#uncover` in between.

However, what if we want to reveal some content afterwards, after every animation, without the need of specifying the subslide number?

If only the `#pause` 'sees' the `#uncover`'s presence, it would be good, right?

Yes, it can, by set the argument `#uncover` (update-pause: `true`).

2.9 Varying Timeline

Example: The yellow box is revealed on subslide 5 and after the current pauses, with After Content appears after every animation.

```
1 Content #show: pause; Content
2
3 #uncover(auto, 5, rect(
4   fill: yellow, [BOX]
5 ), update-pause: true)
6
7 #pause[After Content]
```

Output: on subslide 1

Content

2.9 Varying Timeline

Example: The yellow box is revealed on subslide 5 and after the current pauses, with After Content appears after every animation.

```
1 Content #show: pause; Content
2
3 #uncover(auto, 5, rect(
4   fill: yellow, [BOX]
5 ), update-pause: true)
6
7 #pause[After Content]
```

Output: on subslide 2

Content Content

2.9 Varying Timeline

Example: The yellow box is revealed on subslide 5 and after the current pauses, with After Content appears after every animation.

```
1 Content #show: pause; Content
2
3 #uncover(auto, 5, rect(
4   fill: yellow, [BOX]
5 ), update-pause: true)
6
7 #pause[After Content]
```

Output: on subslide 3

Content Content

BOX

2.9 Varying Timeline

Example: The yellow box is revealed on subslide 5 and after the current pauses, with After Content appears after every animation.

```
1 Content #show: pause; Content
2
3 #uncover(auto, 5, rect(
4   fill: yellow, [BOX]
5 ), update-pause: true)
6
7 #pause[After Content]
```

Output: on subslide 4

Content Content

2.9 Varying Timeline

Example: The yellow box is revealed on subslide 5 and after the current pauses, with After Content appears after every animation.

```
1 Content #show: pause; Content
2
3 #uncover(auto, 5, rect(
4   fill: yellow, [BOX]
5 ), update-pause: true)
6
7 #pause[After Content]
```

Output: on subslide 5

Content Content

BOX

2.9 Varying Timeline

Example: The yellow box is revealed on subslide 5 and after the current pauses, with After Content appears after every animation.

```
1 Content #show: pause; Content
2
3 #uncover(auto, 5, rect(
4   fill: yellow, [BOX]
5 ), update-pause: true)
6
7 #pause[After Content]
```

Output: on subslide 6

Content Content

After Content

2.9 Varying Timeline

`#update-pause` argument updates the current pauses to the maximum index. In the example, `#auto` resolves to 3, so 5 is the maximum.

2.9 Varying Timeline

`#update-pause` argument updates the current pauses to the maximum index. In the example, `#auto` resolves to 3, so 5 is the maximum.

Both `#only` and `#uncover` have `#update-pause` argument, but they are set to be `#false` by default. So these functions reveal the content *independently* from `#pause(..)`.

2.9 Varying Timeline

`#update-pause` argument updates the current pauses to the maximum index. In the example, `#auto` resolves to 3, so 5 is the maximum.

Both `#only` and `#uncover` have `#update-pause` argument, but they are set to be `#false` by default. So these functions reveal the content *independently* from `#pause(..)`.

However, the ability to affect the `#pause(..)` progress unlocks one powerful key:

2.9 Varying Timeline

`#update-pause` argument updates the current pauses to the maximum index. In the example, `#auto` resolves to 3, so 5 is the maximum.

Both `#only` and `#uncover` have `#update-pause` argument, but they are set to be `#false` by default. So these functions reveal the content *independently* from `#pause(..)`.

However, the ability to affect the `#pause(..)` progress unlocks one powerful key:

Number of pauses can be varied and independent from actual number of `#pauses`.

If we use `#only` or `#uncover` to change them, for example:

2.9 Varying Timeline

Content can be revealed parallel on side by side.

```
1 #grid(columns: (1fr, 1fr))[  
2   First \ #show: pause;  
3   A #show: pause; B  
4 ][ // `[ ]` is a dummy content.  
5 #uncover(1, [], update-pause: true)  
6   Second \ #show: pause;  
7   A #show: pause; B  
8 ]
```

Output: on subslide 1

First	Second
-------	--------

The content on both columns are shown synchronously, because the pauses are `set` to 1 (first subslide) by `#uncover`.

2.9 Varying Timeline

Content can be revealed parallel on side by side.

```
1 #grid(columns: (1fr, 1fr))[  
2   First \ #show: pause;  
3   A #show: pause; B  
4 ][ // `[ ]` is a dummy content.  
5 #uncover(1, [], update-pause: true)  
6   Second \ #show: pause;  
7   A #show: pause; B  
8 ]
```

Output: on subslide 2

First	Second
A	A

The content on both columns are shown synchronously, because the pauses are `set` to 1 (first subslide) by `#uncover`.

2.9 Varying Timeline

Content can be revealed parallel on side by side.

```
1 #grid(columns: (1fr, 1fr))[  
2   First \ #show: pause;  
3   A #show: pause; B  
4 ][ // `[ ]` is a dummy content.  
5 #uncover(1, [], update-pause: true)  
6   Second \ #show: pause;  
7   A #show: pause; B  
8 ]
```

Output: on subslide 3

First	Second
A B	A B

The content on both columns are shown synchronously, because the pauses are `set` to 1 (first subslide) by `#uncover`.

2.10 Animated Decorations

Most of the functions we provide up until now can only create animations of hiding and showing stuff. How about *changing* its appearance? e.g. color?

2.10 Animated Decorations

Most of the functions we provide up until now can only create animations of hiding and showing stuff. How about *changing* its appearance? e.g. color?

You can emphasize your words by using `#alert` like in this sentence.

`#alert` can alert the audience by wrapping the input with its `#func` argument, which is `#emph` function by default.

2.10 Animated Decorations

Most of the functions we provide up until now can only create animations of hiding and showing stuff. How about *changing* its appearance? e.g. color?

You can *emphasize* your words by using `#alert` like in this sentence.

`#alert` can *alert* the audience by wrapping the input with its `#func` argument, which is `#emph` function by default.

```
1 Please #alert(auto) [FOCUS] me  
2 and  
3 #alert(auto, func: text.with(red)) [Warn]  
4 them.
```

Output:

Please FOCUS me
and Warn them.

2.10 Animated Decorations

Most of the functions we provide up until now can only create animations of hiding and showing stuff. How about *changing* its appearance? e.g. color?

You can emphasize your words by using `#alert` like in this sentence.

`#alert` can alert the audience by wrapping the input with its `#func` argument, which is `#emph` function by default.

```
1 Please #alert(auto) [FOCUS] me
2 and
3 #alert(auto, func: text.with(red)) [Warn]
4 them.
```

Output:

Please **FOCUS** me and
Warn them.

2.10 Animated Decorations

Another functions for creating multiple *alerts* is called `#transform`.
This function wraps the content and change its through a series of functions.

2.10 Animated Decorations


Another functions for creating multiple *alerts* is called `#transform`.

This function wraps the content and change its through a series of functions.

This is very useful for creating step-by-step list alerts or make the content dynamically changing its appearance. For example,

```
1 #let no(body) = body // original apperance
2 #let yes(body) = text(fill: red, body)
3 #transform([- First Item], yes, no)
4 #transform(start: none, [- Second Item], yes, no)
5 #transform(start: none, [- Third Item], yes, no)
```

Output:



2.10 Animated Decorations

Another functions for creating multiple *alerts* is called `#transform`.

This function wraps the content and change its through a series of functions.

This is very useful for creating step-by-step list alerts or make the content dynamically changing its appearance. For example,

```
1 #let no(body) = body // original apperance
2 #let yes(body) = text(fill: red, body)
3 #transform([- First Item], yes, no)
4 #transform(start: none, [- Second Item], yes, no)
5 #transform(start: none, [- Third Item], yes, no)
```

Output:

- First Item
-
-

2.10 Animated Decorations

Another functions for creating multiple *alerts* is called `#transform`.

This function wraps the content and change its through a series of functions.

This is very useful for creating step-by-step list alerts or make the content dynamically changing its appearance. For example,

```
1 #let no(body) = body // original apperance
2 #let yes(body) = text(fill: red, body)
3 #transform([- First Item], yes, no)
4 #transform(start: none, [- Second Item], yes, no)
5 #transform(start: none, [- Third Item], yes, no)
```

Output:

- First Item
- Second Item
-

2.10 Animated Decorations

Another functions for creating multiple *alerts* is called `#transform`.

This function wraps the content and change its through a series of functions.

This is very useful for creating step-by-step list alerts or make the content dynamically changing its appearance. For example,

```
1 #let no(body) = body // original apperance
2 #let yes(body) = text(fill: red, body)
3 #transform([- First Item], yes, no)
4 #transform(start: none, [- Second Item], yes, no)
5 #transform(start: none, [- Third Item], yes, no)
```

Output:

- First Item
- Second Item
- **Third Item**

2.10 Animated Decorations

Another functions for creating multiple *alerts* is called `#transform`.

This function wraps the content and change its through a series of functions.

This is very useful for creating step-by-step list alerts or make the content dynamically changing its appearance. For example,

```
1 #let no(body) = body // original apperance
2 #let yes(body) = text(fill: red, body)
3 #transform([- First Item], yes, no)
4 #transform(start: none, [- Second Item], yes, no)
5 #transform(start: none, [- Third Item], yes, no)
```

Output:

- First Item
- Second Item
- Third Item

2.10 Animated Decorations

```
1 #transform(  
2     codly(highlighted-lines: (1,)),  
3     codly(highlighted-lines: (4,)) )  
4 ```python  
5 n = input("Number: ")  
6 n = int(n)  
7 for i in range(n):  
8     print("Hello World!")  
9 ```
```

You can use this to highlight different lines of code with **Codly**⁵.
Output: on subslide 1

```
1 n = input("Number: ")  
2 n = int(n)  
3 for i in range(n):  
4     print("Hello World!")
```

⁵<https://typst.app/universe/package/codly/>

2.10 Animated Decorations

```
1 #transform(  
2     codly(highlighted-lines: (1,)),  
3     codly(highlighted-lines: (4,)) )  
4 ```python  
5 n = input("Number: ")  
6 n = int(n)  
7 for i in range(n):  
8     print("Hello World!")  
9 ```
```

You can use this to highlight different lines of code with **Codly**⁵.
Output: on subslide 2

```
1 n = input("Number: ")  
2 n = int(n)  
3 for i in range(n):  
4     print("Hello World!")
```

⁵<https://typst.app/universe/package/codly/>

2.11 Rendering Stuffs

Here comes the most powerful, but most complex utilization of Presentate: `#render` function and `#animation` module.

2.11 Rendering Stuffs

Here comes the most powerful, but most complex utilization of Presentate: `#render` function and `#animation` module.

As we have told, package integration on presentation animation is sometimes tricky, as they are not happy with `content` input data.

2.11 Rendering Stuffs

Here comes the most powerful, but most complex utilization of Presentate: `#render` function and `#animation` module.

As we have told, package integration on presentation animation is sometimes tricky, as they are not happy with `content` input data.

So presentate provides a `workspace` for rendering stuffs that are not necessary to be in content type, with `non-content updates` for number of frames needed.

2.11 Rendering Stuffs

Here comes the most powerful, but most complex utilization of Presentate: `#render` function and `#animation` module.

As we have told, package integration on presentation animation is sometimes tricky, as they are not happy with `content` input data.

So presentate provides a `workspace` for rendering stuffs that are not necessary to be in content type, with `non-content updates` for number of frames needed.

So you can focus on the animation, without worrying about number of subslides.

2.11 Rendering Stuffs

Structure of `#render`

```
1 #render(s => ({  
2   import animation: *  
3   // your stuff goes here.  
4 }, s))
```


2.11 Rendering Stuffs

Structure of `#render`

```
1 #render(s => ({  
2   import animation: *  
3   // your stuff goes here.  
4 }, s))
```

`#render` only accepts one positional argument: **a function**.

2.11 Rendering Stuffs

Structure of `#render`

```
1 #render(s => ({
2   import animation: *
3   // your stuff goes here.
4 }, s))
```

`#render` only accepts one positional argument: a function.

This function accepts the current animation states, and returns *an array*, of length 2 which

- **first** member is the shown output,
- **second** member is the updated states.

2.11 Rendering Stuffs

Structure of `#render`

```
1 #render(s => ({  
2   import animation: *  
3   // your stuff goes here.  
4 }, s))
```

`#render` only accepts one positional argument: **a function**.

This way, Presentate can both show your output, and update the states, so the other elements on the slide react automatically.

This function accepts the current animation states, and returns *an array*, of length 2 which

- **first** member is the shown output,
- **second** member is the updated states.

2.11 Rendering Stuffs

The first member's area only accepts `content`, intended for updating internal states.

However, to create animation with `#render` without generating `content` during the way, Presentate provides the same set of functionality like `#pause`, `#only`, `#fragments`, `#alert`, `#uncover`, and so on, with some key differences:

2.11 Rendering Stuffs

The first member's area only accepts `content`, intended for updating internal states.

However, to create animation with `#render` without generating `content` during the way, Presentate provides the same set of functionality like `#pause`, `#only`, `#fragments`, `#alert`, `#uncover`, and so on, with some key differences:

1. These functions must be imported from `#animation` module.

2.11 Rendering Stuffs

The first member's area only accepts `content`, intended for updating internal states.

However, to create animation with `#render` without generating `content` during the way, Presentate provides the same set of functionality like `#pause`, `#only`, `#fragments`, `#alert`, `#uncover`, and so on, with some key differences:

1. These functions must be imported from `#animation` module.
2. The functions will always accepts the `state` (`#s`) as first positional argument.

2.11 Rendering Stuffs

The first member's area only accepts `content`, intended for updating internal states.

However, to create animation with `#render` without generating `content` during the way, Presentate provides the same set of functionality like `#pause`, `#only`, `#fragments`, `#alert`, `#uncover`, and so on, with some key differences:

1. These functions must be imported from `#animation` module.
2. The functions will always accepts the `state (#s)` as first positional argument.
3. **You have to update the state variable (`#s`) manually.**

2.11 Rendering Stuffs

Example 1: Animated `CeTZ`⁶ diagram. Create an animation drawing two circles, in green and red.


```
1  #import "@preview/cetz:0.4.2":  
    canvas, draw  
2  #render(s => ({  
3    import animation: *  
4    canvas({  
5      import draw: *
```

```
6      pause(s, circle((0, 0),  
    fill: green,))  
7      s.push(auto) // update s  
8      pause(s, circle((1, 0),  
    fill: red))  
9    })  
10 }, s))
```

⁶<https://typst.app/universe/package/cetz>

2.11 Rendering Stuffs

Output: on subslide 1



2.11 Rendering Stuffs

Output: on subslide 2



2.11 Rendering Stuffs

Output: on subslide 3



2.11 Rendering Stuffs

Output: on subslide 4



The default hider of `animation.pause` is
it => `none`, so it *does not* preserve space.

2.11 Rendering Stuffs

Output: on subslide 5



The default hider of `animation.pause` is `it => none`, so it *does not* preserve space.

However, you can change this by the `#draw.hide.with(bounds: true)` from native CeTZ to preserve space, by adding the following line before `#canvas`:

```
1 let pause = pause.with(hider: draw.hide.with(bounds: true))
```

Similarly, you can change the default hider functions to suit your package.

2.11 Rendering Stuffs

You can change the default `#hider` by using `#settings` functions, which will return a dictionary containing the functions:

```
1 // import "@preview/cetz:0.4.2": canvas, draw
2 let (uncover, pause) = settings(hider: draw.hide.with(bounds: true))
```

For this change, the last example would become the Output:




2.11 Rendering Stuffs

You can change the default `#hider` by using `#settings` functions, which will return a dictionary containing the functions:

```
1 // import "@preview/cetz:0.4.2": canvas, draw
2 let (uncover, pause) = settings(hider: draw.hide.with(bounds: true))
```

For this change, the last example would become the Output:




2.11 Rendering Stuffs

You can change the default `#hider` by using `#settings` functions, which will return a dictionary containing the functions:

```
1 // import "@preview/cetz:0.4.2": canvas, draw
2 let (uncover, pause) = settings(hider: draw.hide.with(bounds: true))
```

For this change, the last example would become the Output:



2.11 Rendering Stuffs

Updating States: In render function, the state variable `#s` is the sole information about the number of subslides needed to render all of the animations.

2.11 Rendering Stuffs

Updating States: In render function, the state variable `#s` is the sole information about the number of subslides needed to render all of the animations.

So updating it is crucial to produce the correct number of subslides. But how?

2.11 Rendering Stuffs

Updating States: In render function, the state variable `#s` is the sole information about the number of subslides needed to render all of the animations.

So updating it is crucial to produce the correct number of subslides. But how?

The state variable `s` is an *array*, so updating it is basically *push* the new information to it. The information added determine the current animation states as

2.11 Rendering Stuffs

Updating States: In render function, the state variable `#s` is the sole information about the number of subslides needed to render all of the animations.

So updating it is crucial to produce the correct number of subslides. But how?

The state variable `s` is an `array`, so updating it is basically `push` the new information to it. The information added determine the current animation states as

- `#auto` is pushed to **increase the number of pauses by 1**.

2.11 Rendering Stuffs

Updating States: In render function, the state variable `#s` is the sole information about the number of subslides needed to render all of the animations.

So updating it is crucial to produce the correct number of subslides. But how?

The state variable `s` is an `array`, so updating it is basically `push` the new information to it. The information added determine the current animation states as

- `#auto` is pushed to **increase the number of pauses by 1**.
- `1, 2, 3, ...` integers are pushed to set the **current number of pauses**.

2.11 Rendering Stuffs

Updating States: In render function, the state variable `#s` is the sole information about the number of subslides needed to render all of the animations.

So updating it is crucial to produce the correct number of subslides. But how?

The state variable `s` is an *array*, so updating it is basically *push* the new information to it. The information added determine the current animation states as

- `#auto` is pushed to **increase the number of pauses by 1**.
- `1, 2, 3, ..` integers are pushed to set the **current number of pauses**.
- `(1, 2, ..)` array of integers are pushed to set the **minimum number of subslides**, *without* updating pauses.

2.11 Rendering Stuffs

Example 2: CeTZ drawings with `#uncover` and `#only`

```
1  #import "@preview/cetz:0.4.2":  
    canvas, draw  
2  #render(s => ({  
3    import animation: *  
4    canvas({  
5      import draw: *  
6      let (uncover, pause) =  
        settings(hider:  
          draw.hide.with(bounds:  
            true))
```

```
7      pause(s, circle((0, 0)))  
8      s.push(auto)  
9      uncover(s, 3,  
10         rect((-1, -1), (1, 1)))  
11     s.push((3,))  
12     only(s, 4, circle((1, 1)))  
13     s.push(4)  
14   })  
15 }, s))
```

2.11 Rendering Stuffs

Output: on subslide 1



Notice that the circle produced by `only()` does not preserve space, as it uses it => `none` as hider.

2.11 Rendering Stuffs

Output: on subslide 2



Notice that the circle produced by `only()` does not preserve space, as it uses it => `none` as hider.

2.11 Rendering Stuffs


Output: on subslide 3



Notice that the circle produced by `only()` does not preserve space, as it uses it => `none` as hider.

2.11 Rendering Stuffs

Output: on subslide 4



Notice that the circle produced by `only()` does not preserve space, as it uses it => `none` as hider.

2.11 Rendering Stuffs

Output: on subslide 5



Notice that the circle produced by `only()` does not preserve space, as it uses it => `none` as hider.

The updates: The first `#auto increments` the pauses, the second `#(3,)` set the *minimum subslides* to at least 3 and `#4` set the number of *pauses* to 4.

2.11 Rendering Stuffs

Output: on subslide 6



Notice that the circle produced by `only()` does not preserve space, as it uses it => `none` as hider.

The updates: The first `#auto increments` the pauses, the second `#(3,)` set the `minimum subslides` to at least 3 and `#4` set the number of `pauses` to 4.


All you need to do is to update the `#s` for each animation.

For total number of subslides needed, Presentate will do the job *automatically*.

2.11 Rendering Stuffs

Example 3: Fletcher in math mode diagram, with `it => none` as hider.

Output: on subslide 1




```
1 #render(s => ({
2   import animation: *
3   diagram($
4     pause(#s, A edge(->)) #s.push(auto)
5     & pause(#s, B edge(->)) #s.push(auto)
6     pause(#s, edge(->, "d") & C) \
7     & pause(#s, D)
8   $,)
9 }, s,))
```

2.11 Rendering Stuffs

Example 3: Fletcher in math mode diagram, with `it => none` as hider.

Output: on subslide 2




```
1 #render(s => ({
2   import animation: *
3   diagram($
4     pause(#s, A edge(->)) #s.push(auto)
5     & pause(#s, B edge(->)) #s.push(auto)
6     pause(#s, edge(->, "d") & C) \
7     & pause(#s, D)
8   $,)
9 }, s,))
```

2.11 Rendering Stuffs

Example 3: Fletcher in math mode diagram, with `it => none` as hider.

Output: on subslide 3




```
1 #render(s => ({
2   import animation: *
3   diagram($
4     pause(#s, A edge(->)) #s.push(auto)
5     & pause(#s, B edge(->)) #s.push(auto)
6     pause(#s, edge(->, "d") & C) \
7     & pause(#s, D)
8   $,)
9 }, s,))
```


2.11 Rendering Stuffs

Example 3: Fletcher in math mode diagram, with `it => none` as hider.

Output: on subslide 4




```
1 #render(s => ({
2   import animation: *
3   diagram($
4     pause(#s, A edge(->)) #s.push(auto)
5     & pause(#s, B edge(->)) #s.push(auto)
6     pause(#s, edge(->, "d") & C) \
7     & pause(#s, D)
8   $,)
9 }, s,))
```

2.11 Rendering Stuffs

Example 3: Fletcher in math mode diagram, with `it => none` as hider.

Output: on subslide 5



Although not perfect, it is doable.

```

1 #render(s => ({
2   import animation: *
3   diagram($
4     pause(#s, A edge(->)) #s.push(auto)
5     & pause(#s, B edge(->)) #s.push(auto)
6     pause(#s, edge(->, "d") & C) \
7     & pause(#s, D)
8   $,)
9 }, s,))
  
```

2.12 Animate the inanimate

Last examples show us how to hack for drawing stuff that has its own `#hider`, either provided by the package or we created it.

⁷<https://typst.app/universe/package/alchemist/>

2.12 Animate the inanimate

Last examples show us how to hack for drawing stuff that has its own `#hider`, either provided by the package or we created it.

However, I admitted that using `#pause(s, ..)` a lot is tedious, do we have a better way?

⁷<https://typst.app/universe/package/chemist/>

2.12 Animate the inanimate

Last examples show us how to hack for drawing stuff that has its own `#hider`, either provided by the package or we created it.

However, I admitted that using `#pause(s, ..)` a lot is tedious, do we have a better way? How about making the input *reactive* to the states?

⁷<https://typst.app/universe/package/chemist/>

2.12 Animate the inanimate

Last examples show us how to hack for drawing stuff that has its own `#hider`, either provided by the package or we created it.

However, I admitted that using `#pause(s, ..)` a lot is tedious, do we have a better way? How about making the input *reactive* to the states?

Introducing `#animation.animate` function, together with a package for drawing molecular structure: `Alchemist`⁷.

⁷<https://typst.app/universe/package/alchemist/>

2.12 Animate the inanimate

Alchemist does not provide any hider functions to hide the structure. However, we came up with an idea: setting the hidden bond's stroke to `#0pt` should effectively hide the bonds, right?

2.12 Animate the inanimate

Alchemist does not provide any hider functions to hide the structure. However, we came up with an idea: setting the hidden bond's stroke to `#0pt` should effectively hide the bonds, right?

So we use the hider as a `#modifier` the function's argument.

```
1 #import "@preview/alchemist:0.1.8": *  
2 #let (single,) = animation.animate(  
3   single, modifier: (func, ..args) => func(stroke: 0pt, ..args)  
4 )
```

Note! The animated functions require `#s` as the first positional argument.

2.12 Animate the inanimate

Output: on subslide 1



```
1  #render(s => ({
2    skeletize({
3      single(s) // Note the `s`!
4      branch({
5        s.push(auto)
6        single(s, angle: -1)
7      })
8      s.push(auto)
9      single(s, angle: 1)
10   })
11 }, s))
```

2.12 Animate the inanimate

Output: on subslide 2



```
1  #render(s => ({
2    skeletize({
3      single(s) // Note the `s`!
4      branch({
5        s.push(auto)
6        single(s, angle: -1)
7      })
8      s.push(auto)
9      single(s, angle: 1)
10   })
11 }, s))
```

2.12 Animate the inanimate

Output: on subslide 3



```
1  #render(s => ({
2    skeletize({
3      single(s) // Note the `s`!
4      branch({
5        s.push(auto)
6        single(s, angle: -1)
7      })
8      s.push(auto)
9      single(s, angle: 1)
10   })
11 }, s))
```

2.12 Animate the inanimate

Output: on subslide 4



```
1  #render(s => ({
2    skeletize({
3      single(s) // Note the `s`!
4      branch({
5        s.push(auto)
6        single(s, angle: -1)
7      })
8      s.push(auto)
9      single(s, angle: 1)
10   })
11 }, s))
```

2.12 Animate the inanimate

Output: on subslide 5



Now the molecule is drawn!

```
1  #render(s => ({
2    skeletize({
3      single(s) // Note the `s`!
4      branch({
5        s.push(auto)
6        single(s, angle: -1)
7      })
8      s.push(auto)
9      single(s, angle: 1)
10   })
11 }, s))
```

2.12 Animate the inanimate

Output: on subslide 6



Now the molecule is drawn!

The `#animate` is like `modifier` to make the function `aware` to the `#s` updates.

```
1  #render(s => ({
2    skeletize({
3      single(s) // Note the `s`!
4      branch({
5        s.push(auto)
6        single(s, angle: -1)
7      })
8      s.push(auto)
9      single(s, angle: 1)
10   })
11 }, s))
```

2.13 Modes and Utility

Presentate provides three modes for different purposes:

2.13 Modes and Utility

Presentate provides three modes for different purposes:

- **Normal** for animated slides. [Default]

2.13 Modes and Utility

Presentate provides three modes for different purposes:

- **Normal** for animated slides. [Default]
- **Handout** for disabling all animations.

2.13 Modes and Utility

Presentate provides three modes for different purposes:

- **Normal** for animated slides. [Default]
- **Handout** for disabling all animations.
- **Drafted** for showing the subslide number.

2.13 Modes and Utility

Presentate provides three modes for different purposes:

- **Normal** for animated slides. [Default]
- **Handout** for disabling all animations.
- **Drafted** for showing the subslide number.

Normal mode is to do nothing, for the last two options, you can set them via

```
1 #set-options(handout: true, drafted: true)
```

2.14 Themes

The slide you are viewing is the *simple* theme of Presentate. You can use it by typing the following lines:

```
1 #import themes.simple: *  
2 #show: template.with(  
3   author: [Pacaunt], // change to yours!  
4   title: [Welcome To Presentate!],  
5   subtitle: [Slides Tools.],  
6 )
```

2.14 Themes

The theme provides the following slides:

- `#slide(title, body)` which if no title, it will repeat the last topic.
- `#empty-slide(body)` which is empty and has no margin, header, and footer.
- `#focus-slide(body)` which is colored, vibrant slide for getting attention.

The preview is on the next slide:

2.14 Themes

<p>Welcome To Presentate!</p> <hr/> <p><i>Slides Tools.</i> Pacaunt 2025-08-15</p>	<p>New Section</p>	<p>New Section Hello</p> <hr/> <p>This is Simple theme slide.</p> <p>Pacaunt 1</p>
<p>New Section Hello</p> <hr/> <p>Slide with no title will continue from the last title.</p> <p>Pacaunt 2</p>	<p><i>This should be focus!</i></p>	<p>#empty-slide is the slide with nothing, even the header and footer.</p>

2.14 Themes

```
1  = New Section
2  #slide[Hello][
3      This is Simple theme slide.
4  ]
5
6  #slide[
7      Slide with no title will
        continue from the last title.
8  ]
9
```

```
10 #focus-slide[
11     This should be focus!
12 ]
13
14 #empty-slide[
15     #set align(center + horizon)
16     `#empty-slide` is the slide
        with nothing, \
17     even the `header` and
        `footer`.
18 ]
```

2.14 Themes

Another theme is *default* theme. It is very minimal, as it sets the paper and text font and sizes, provided with new section slides.

2.14 Themes

Another theme is *default* theme. It is very minimal, as it sets the paper and text font and sizes, provided with new section slides.

You can import it with

```
1 #import themes.default: *  
2 #show: template.with(  
3   aspect-ratio: "16-9"  
4 )
```

2.14 Themes

Another theme is `default` theme. It is very minimal, as it sets the paper and text font and sizes, provided with new section slides.

You can import it with

```
1 #import themes.default: *  
2 #show: template.with(  
3   aspect-ratio: "16-9"  
4 )
```

and then you will have `#slide`(body), which are normal slide function, and `#empty-slide`(body) for a slide with no header, footer, and margins.

2.14 Themes

Some example of the Default theme.

New Section	Hello This is default theme slide.	<code>#empty-slide</code> is the slide with nothing, even the header and footer.
-------------	--	---

2.14 Themes

```
1  = New Section
2
3  #slide[
4      == Hello
5      This is default theme slide.
6  ]
7
```

```
8  #empty-slide[
9      #set align(center + horizon)
10     `#empty-slide` is the slide
    with nothing, \
11     even the `header` and
    `footer`.
12 ]
```

2.14 Themes

By default Presentate is still young and does not provide more themes currently, but the integration of Typst styling in Presentate should be seamless, and convenient enough to create by yourself :)

For more information, you can contact us at
Presentate's github
(<https://github.com/pacaunt/typst-presentate/>)

Enjoy making presentation!