

Guide: Progressive Outline

1 Function documentation

This section details all the parameters available for the `progressive-outline` function.

Option	Type	Effect & Expected Values
<code>level-X-mode</code>	string	Defines the visibility of level X (1, 2, or 3). Values: "all", "current", "current-parent", "none".
<code>text-styles</code>	dict	Styles passed to <code>#text</code> (fill, weight, etc.). You can also use a float (e.g., 0.5) as a shortcut to inherit the active style with that opacity.
<code>spacing</code>	dict	Controls vertical space (<code>v-between-X-Y</code>) and horizontal indentation (<code>indent-X</code>) between elements.
<code>show-numbering</code>	bool	Enables or disables the display of heading numbering.
<code>numbering-format</code>	str func	Typst numbering format (e.g., "1.1") or custom function (<code>..n</code>) => ...
<code>match-page-only</code>	bool	If true, considers a heading active if it is on the same page, regardless of its Y position. Useful for sidebars.
<code>filter</code>	func	A callback function (<code>heading</code>) => bool to programmatically include or exclude headings.
<code>clickable</code>	bool	Enables clickable links on headings. Defaults to true.

2 Navigation & Interactivity

By default, the outline is interactive: clicking on a section title navigates directly to the corresponding slide in the PDF.

`progressive-outline()`

Non-clickable Outline

Function documentation

Navigation & Interactivity

Visibility

Style Customization

Fine-grained spacing management

Numbering system

Filtering Content

Advanced Behavior

Additional information

In some print-focused or strict layout scenarios, you might want to disable this interactivity.

```
progressive-outline(  
  clickable: false  
)
```

Non-clickable Outline

Function documentation

Navigation & Interactivity

Visibility

Style Customization

Fine-grained spacing management

Numbering system

Filtering Content

Advanced Behavior

Additional information

3 Visibility

This section covers the level-X-mode parameters.

3.1 The 'current-parent' mode

The current-parent mode is the most powerful: it only displays the “siblings” of the current element. This allows you to see the plan of the current section without being distracted by other chapters.

```
progressive-outline(  
  level-1-mode: 'all',  
  level-2-mode: 'current-parent'  
)
```

Visibility Demonstration H2

Function documentation

Navigation & Interactivity

Visibility

The 'current-parent' mode

Isolation via 'current' mode

Deep nesting (Level 3)

Style Customization

Fine-grained spacing management

Numbering system

Filtering Content

Advanced Behavior

Additional information

3.2 Isolation via 'current' mode

If you want an ultra-minimalist rendering, the current mode hides everything except the exact entry where you are located.

```
progressive-outline(  
  level-1-mode: 'current',  
  level-2-mode: 'none'  
)
```

Isolated Visibility Demonstration

Visibility

3.3 Deep nesting (Level 3)

For complex structures, you can enable Level 3. Using current-parent will show siblings at the current depth.

3.3.1 Deep Component A

3.3.2 Deep navigation test

```
progressive-outline(  
  level-2-mode: 'all',  
  level-3-mode: 'current-parent'  
)
```

Level 3 Siblings

Function documentation

Navigation & Interactivity

Visibility

The 'current-parent' mode

Isolation via 'current' mode

Deep nesting (Level 3)

Deep Component A

Deep navigation test

Style Customization

The 3-state system

Advanced Opacity & Inheritance

The anti-jitter mechanism

Colors and decorations

Fine-grained spacing management

Inter-level spacing

Horizontal indentation

Numbering system

Complex hierarchical formats

Advanced textual prefixes

Filtering Content

Label-based filtering

Logic-based filtering

Recursive filtering

Advanced Behavior

Page-based matching

Additional information

4 Style Customization

The function allows you to modify the appearance of headings based on their state (**completed**, **active**, or **inactive**).

4.1 The 3-state system

By default, headings can be in one of three states:

- **completed**: The heading has already been passed.
- **active**: This is the current heading.
- **inactive**: The heading is yet to come.

```
text-styles: (
  level-1: (
    active: (fill: eastern, weight:
'bold'),
    completed: (fill: gray.lighten(50%)),
    inactive: (fill: black)
  )
)
```

Past, Present, Future

Function documentation

Navigation & Interactivity

Visibility

Style Customization

Fine-grained spacing management

Numbering system

Filtering Content

Advanced Behavior

Additional information

4.2 Advanced Opacity & Inheritance

Instead of redefining the full style for inactive or completed states, you can use smart inheritance to adapt the active style.

4.2.1 The Float Shortcut (Clone & Fade)

Pass a number (0.0 to 1.0) to automatically clone the active style and apply transparency. 0.2 means 20% opacity (very faint), 1.0 means fully opaque.

```
text-styles: (
  level-1: (
    active: (fill: red, weight: 'black'),
    inactive: 0.2,    // Future: very faint
(20%)
    completed: 0.5   // Past: semi-
transparent (50%)
  )
)
```

Auto-Fade Shortcut

Function documentation

Navigation & Interactivity

Visibility

Style Customization

Fine-grained spacing management

Numbering system

Filtering Content

Advanced Behavior

Additional information

4.2.2 Partial Inheritance (Mix & Match)

You can also use a dictionary with an opacity key. This allows you to inherit the active color (faded) while overriding other properties (like weight).

```
text-styles: (  
  level-1: (  
    active: (fill: blue, weight: 'black'),  
    inactive: (  
      opacity: 0.5,      // 50% of active  
color  
      weight: 'regular' // But force  
regular weight  
    )  
  )  
)
```

Fade + Weight Change

[Function documentation](#)

[Navigation & Interactivity](#)

[Visibility](#)

[Style Customization](#)

[Fine-grained spacing management](#)

[Numbering system](#)

[Filtering Content](#)

[Advanced Behavior](#)

[Additional information](#)

4.3 The anti-jitter mechanism

Anti-jitter ensures that switching from a thin font to a bold one doesn't move the text. We use a ghost box to reserve the maximum space required.

```
text-styles: (  
  level-1: (  
    active: (weight: 'black', fill:  
eastern, size: 1.2em),  
    inactive: (weight: 'light', fill:  
gray, size: 1.2em)  
  )  
)
```

Stability Test H1

[Function documentation](#)

[Navigation & Interactivity](#)

[Visibility](#)

[Style Customization](#)

[Fine-grained spacing management](#)

[Numbering system](#)

[Filtering Content](#)

[Advanced Behavior](#)

[Additional information](#)

4.4 Colors and decorations

Each level can have its own rules for colors, italics, or bold.

```
text-styles: (  
  level-2: (  
    active: (style: 'italic', fill: blue,  
weight: 'bold'),  
    inactive: (fill: luma(200))  
  )  
)
```

Creative Style H2

Function documentation

Navigation & Interactivity

Visibility

The 'current-parent' mode

Isolation via 'current' mode

Deep nesting (Level 3)

Style Customization

The 3-state system

Advanced Opacity & Inheritance

The anti-jitter mechanism

Colors and decorations

Fine-grained spacing management

Inter-level spacing

Horizontal indentation

Numbering system

Complex hierarchical formats

Advanced textual prefixes

Filtering Content

Label-based filtering

Logic-based filtering

Recursive filtering

Advanced Behavior

Page-based matching

Additional information

5 Fine-grained spacing management

The spacing dictionary sculpts the rhythm.

5.1 Inter-level spacing

You can define the exact space between an H1 heading and an H2 heading, or between two headings of the same level.

```
spacing: (  
  v-between-1-1: 2em,  
  v-between-1-2: 1.2em,  
  v-between-2-2: 0.8em,  
  v-between-2-1: 1.5em  
)
```

Airy Vertical Rhythm

Function documentation

Navigation & Interactivity

Visibility

The 'current-parent' mode
Isolation via 'current' mode
Deep nesting (Level 3)

Style Customization

The 3-state system
Advanced Opacity & Inheritance
The anti-jitter mechanism
Colors and decorations

Fine-grained spacing management

Inter-level spacing

Horizontal indentation

Numbering system

Complex hierarchical formats
Advanced textual prefixes

Filtering Content

Label-based filtering
Logic-based filtering
Recursive filtering

Advanced Behavior

Page-based matching

Additional information

5.2 Horizontal indentation

Indentation defines the offset to the right for each depth level.

```
spacing: (  
  indent-2: 3em,  
  indent-3: 6em  
)
```

Marked Indentation

Function documentation

Navigation & Interactivity

Visibility

- The 'current-parent' mode

- Isolation via 'current' mode

- Deep nesting (Level 3)

 - Deep Component A

 - Deep navigation test

Style Customization

- The 3-state system

- Advanced Opacity & Inheritance

 - The Float Shortcut (Clone & Fade)

 - Partial Inheritance (Mix & Match)

- The anti-jitter mechanism

- Colors and decorations

Fine-grained spacing management

- Inter-level spacing

Horizontal indentation

Numbering system

- Complex hierarchical formats

- Advanced textual prefixes

Filtering Content

- Label-based filtering

- Logic-based filtering

- Recursive filtering

Advanced Behavior

- Page-based matching

Additional information

6 Numbering system

The function relies on Typst's native engine.

6.1 Complex hierarchical formats

The `numbering-format` parameter accepts all standard Typst models (1, a, i, I, A).


```
show-numbering: true,  
numbering-format: 'I.a.1. '
```

Legal Format

I. Function documentation

II. Navigation & Interactivity

III. Visibility

III.a. The 'current-parent' mode

III.b. Isolation via 'current' mode

III.c. Deep nesting (Level 3)

III.c.1. Deep Component A

III.c.2. Deep navigation test

IV. Style Customization

IV.a. The 3-state system

IV.b. Advanced Opacity & Inheritance

IV.b.1. The Float Shortcut (Clone & Fade)

IV.b.2. Partial Inheritance (Mix & Match)

IV.c. The anti-jitter mechanism

IV.d. Colors and decorations

V. Fine-grained spacing management

V.a. Inter-level spacing

V.b. Horizontal indentation

VI. Numbering system

VI.a. Complex hierarchical formats

VI.b. Advanced textual prefixes

VII. Filtering Content

VII.a. Label-based filtering

VII.b. Logic-based filtering

VII.c. Recursive filtering

VIII. Advanced Behavior

VIII.a. Page-based matching

IX. Additional information

6.2 Advanced textual prefixes

To use long words like "Chapter" without errors, pass a function. This prevents Typst from interpreting letters like 'a' or 'i' as numbering models.

```
show-numbering: true,  
numbering-format: (..n) => 'Chapter ' +  
numbering('1', ..n) + ' : '
```

Secure 'Chapter' Prefix

Chapter 1 : Function documentation

Chapter 2 : Navigation & Interactivity

Chapter 3 : Visibility

Chapter 4 : Style Customization

Chapter 5 : Fine-grained spacing management

Chapter 6 : Numbering system

Chapter 7 : Filtering Content

Chapter 8 : Advanced Behavior

Chapter 9 : Additional information

7 Filtering Content

The `filter` parameter allows you to programmatically include or exclude headings from the outline. It expects a callback function (`heading`) => `boolean`.

The heading object passed to the filter contains standard properties (`level`, `body`, `label`, `counter`) as well as context properties: `parent-h1` and `parent-h2`.

7.1 Label-based filtering

In this document, the current section “Filtering Content” has been tagged with the label `<hidden>`.

```
progressive-outline(level-2-mode: 'none')
```

Standard Outline (No Filter)

Function documentation

Navigation & Interactivity

Visibility

Style Customization

Fine-grained spacing management

Numbering system

Filtering Content

Advanced Behavior

Additional information

```
progressive-outline(  
  level-2-mode: 'none',  
  filter: h => h.label !== <hidden>  
)
```

Filtered Outline (Label)

Function documentation

Navigation & Interactivity

Visibility

Style Customization

Fine-grained spacing management

Numbering system

Advanced Behavior

Additional information

7.2 Logic-based filtering

You can also filter based on any heading property. Here, we filter the list to **keep only** the section named “Visibility”.

```
progressive-outline(  
  level-2-mode: 'none',  
  // Keep only the heading named  
  'Visibility'  
  filter: h => h.body == [Visibility]  
)
```

Filtered Outline (Content)

Visibility

Here, we create a custom rule: show all Level 1 headings, but show Level 2 headings **only** if they belong to the “Visibility” section.

```

progressive-outline(
  level-2-mode: 'all',
  filter: h => h.level == 1 or
    (h.level == 2 and h.parent-h1.body ==
[Visibility])
)

```

Conditional Depth

Function documentation

Navigation & Interactivity

Visibility

The 'current-parent' mode

Isolation via 'current' mode

Deep nesting (Level 3)

Style Customization

Fine-grained spacing management

Numbering system

Filtering Content

Advanced Behavior

Additional information

7.3 Recursive filtering

The filtering logic is recursive: if a parent heading (e.g., a Section) is excluded by the filter, all its children (Subsections and Sub-subsections) are automatically hidden as well, even if they would have passed the filter individually.

```

// Hiding a parent automatically hides its
children
progressive-outline(
  level-2-mode: 'all',
  filter: h => h.label != <hidden>
)

```

Recursive Hiding

Function documentation

Navigation & Interactivity

Visibility

The 'current-parent' mode

Isolation via 'current' mode

Deep nesting (Level 3)

Style Customization

The 3-state system

Advanced Opacity & Inheritance

The anti-jitter mechanism

Colors and decorations

Fine-grained spacing management

Inter-level spacing

Horizontal indentation

Numbering system

Complex hierarchical formats

Advanced textual prefixes

Advanced Behavior

Page-based matching

Additional information

8 Advanced Behavior

8.1 Page-based matching

In contexts like sidebars, the outline is rendered in the page margin or background before the slide content. This can cause the active heading detection to fail because the content is technically "after" the sidebar in the document flow.

Setting `match-page-only: true` solves this by considering any heading on the current page as "active", ignoring precise vertical positioning.

match-page-only: true

Sidebar Logic

Function documentation

Navigation & Interactivity

Visibility

Style Customization

Fine-grained spacing management

Numbering system

Filtering Content

Advanced Behavior

Additional information

9 Additional information

It is optimized to work within presentation themes (like progressive-outline), but can be used in any standard Typst document.