

Presentate: Structured Themes Manual

A guide for hierarchy-aware themes

Contents

1	Introduction	1
2	Global Configuration for Structured Themes	2
2.1	Common Parameters	2
2.2	Structural Mapping	3
2.3	Important Note: Heading Placement	3
2.4	Navigation and Long Titles	3
2.4.1	Short Titles (Labels)	3
2.4.2	Automatic Truncation	3
3	The Unified Transition Engine	4
3.1	Configuration Options	4
3.2	Transition Style	4
3.3	Visibility Logic	4
4	Theme Reference	5
4.1	Sidebar Theme	5
4.1.1	Theme Parameters	5
4.1.1.1	Outline Configuration	5
4.2	Miniframes Theme	5
4.2.1	Navigation Dictionary	5
4.3	Split Theme	6
4.3.1	Theme Parameters	6
4.4	Progressive Outline Theme	6
4.4.1	Theme Parameters	6
4.5	Minimal Theme	6
4.5.1	Theme Parameters	6
5	Hooks API	7

1 Introduction

Presentate provides two categories of themes:

1. **Basic Layouts:** Minimalist themes like `simple` and `default` that focus on content without managing complex document hierarchy.
2. **Structured Themes:** A suite of themes (`sidebar`, `miniframes`, `split`, `progressive-outline`, and `minimal`) designed to automatically handle document structure, navigation, and transitions.

This manual focuses exclusively on the Structured Themes category. These themes share a common core API and a **Unified Transition Engine** to generate roadmap slides between content blocks.

2 Global Configuration for Structured Themes

All structured themes follow a consistent API pattern and are located in the `themes.structured` namespace. They are invoked using a `template` function through a `show` rule.

```
#import "@preview/presentate:0.2.6": themes
#show: themes.structured.sidebar.template.with(
  title: [My Presentation],
  author: [John Doe],
  // ... options
)
```

2.1 Common Parameters

The following parameters are supported by all five structured themes:

Parameter	Type	Description
<code>title</code>	<code>content</code>	The main title displayed on the title slide and often in the navigation bar.
<code>subtitle</code>	<code>content</code>	Displayed below the title on the title slide (optional).
<code>author</code>	<code>content</code>	The name of the presenter.
<code>date</code>	<code>content</code>	Presentation date. Defaults to current date.
<code>text-font</code>	<code>string</code>	Font family family for the whole document. Default: "Lato".
<code>text-size</code>	<code>length</code>	Base text size. Default: 20pt.
<code>mapping</code>	<code>dictionary</code>	Maps logical roles to Typst heading levels. Default: (section: 1, subsection: 2). Supports part, section, subsection.
<code>auto-title</code>	<code>bool</code>	If <code>true</code> , slides without a manual title will automatically display the current heading body. Default: <code>false</code> .
<code>max-length</code>	<code>dict none</code>	Allows truncating titles in navigation bars per level. Example: (level-1: 15, level-2: 10). Default: <code>none</code> .
<code>use-short-title</code>	<code>bool</code>	If <code>true</code> , themes will prioritize alternative titles defined via the <code><short></code> label for navigation components. Default: <code>false</code> .
<code>show-heading-numbering</code>	<code>bool</code>	Global toggle for heading numbering. Default: <code>true</code> .
<code>numbering-format</code>	<code>str auto</code>	Typst numbering format string (e.g., "1.1", "I.a"). If set to <code>auto</code> , it respects the global <code>#set heading(numbering: ...)</code> setting. Default: <code>auto</code> .
<code>show-outline</code>	<code>bool</code>	If <code>true</code> , displays an outline slide after the title slide. Default: <code>false</code> .

Parameter	Type	Description
outline-title	content	The title of the automatic outline slide. Default: [Outline].
outline-depth	int	The maximum depth of headings shown in the outline slide. Default: 2.
show-all-sections-in-transition	bool	If true, displays the full presentation outline during roadmap slides. Default: false.
transitions	dictionary	Configuration for the transition engine (see Section 3).

2.2 Structural Mapping

The mapping dictionary is crucial as it tells the theme which headings should trigger transitions and navigation updates.

- part: Typically mapped to level 1 (=).
- section: Typically mapped to level 1 or 2.
- subsection: Typically mapped to level 2 or 3.

Example:

```
mapping: (part: 1, section: 2, subsection: 3)
```

2.3 Important Note: Heading Placement

To ensure that transitions and navigation work correctly, structural headings (=, ==, etc.) must always be placed at the **top level** of your document.

Do not place these headings inside a #slide[...] block. Headings nested inside slides will not trigger transitions and will cause the compilation to fail.

2.4 Navigation and Long Titles

To handle complex document structures in limited space (like sidebars or breadcrumbs), Presentate offers two complementary mechanisms:

2.4.1 Short Titles (Labels)

You can define an alternative short title for any heading by placing a #metadata block with the <short> label immediately after the heading.

```
= This is a very long section title that might overflow
#metadata("Short Title") <short>
```

When use-short-title: true is enabled in the template configuration, navigation components will automatically use “Short Title” instead of the full heading body.

2.4.2 Automatic Truncation

The max-length parameter allows you to enforce a character limit on navigation items. If a title exceeds the specified length, it will be truncated with an ellipsis (...).

```
max-length: (level-1: 15, level-2: 10)
```

3 The Unified Transition Engine

The transition engine automatically generates roadmap slides when your structure changes. It is highly configurable via the `transitions` argument.

3.1 Configuration Options

The `transitions` dictionary accepts the following keys:

Key	Type	Description
<code>enabled</code>	<code>bool</code>	Global switch for transitions. Default: <code>true</code> .
<code>max-level</code>	<code>int</code>	The maximum Typst heading level (1-3) that triggers a transition. Default: 3.
<code>show-numbering</code>	<code>bool</code>	Display heading numbers in transition outlines using the <code>global-numbering-format</code> . Default: <code>true</code> .
<code>background</code>	<code>color str</code>	Background of transition slides. "theme" (primary color), "none" (white), or an explicit color.
<code>filter</code>	<code>function</code>	A callback <code>(heading) => bool</code> . Headings returning <code>false</code> will not trigger slides and will be hidden from outlines.
<code>style</code>	<code>dictionary</code>	Global styling for the transition outline (see below).
<code>parts</code>	<code>dictionary</code>	Override settings for Part transitions. Accepts <code>enabled</code> (<code>bool</code>), <code>visibility</code> (<code>dict</code>), and <code>background</code> (<code>color str</code>).
<code>sections</code>	<code>dictionary</code>	Override settings for Section transitions. Accepts <code>enabled</code> (<code>bool</code>), <code>visibility</code> (<code>dict</code>), and <code>background</code> (<code>color str</code>).
<code>subsections</code>	<code>dictionary</code>	Override settings for Subsection transitions. Accepts <code>enabled</code> (<code>bool</code>), <code>visibility</code> (<code>dict</code>), and <code>background</code> (<code>color str</code>).

3.2 Transition Style

The `transitions.style` dictionary controls the typography of the roadmap:

- `active-color`: Color of the current heading. Defaults to theme accent.
- `active-weight`: Font weight of the active heading. Default: `"bold"`.
- `inactive-opacity`: Opacity (0.0 to 1.0) for future headings. Default: 0.3.
- `completed-opacity`: Opacity for past headings. Default: 0.6.

3.3 Visibility Logic

For each roadmap type (`parts`, `sections`, `subsections`), you can define which levels are visible via the `visibility` key:

- `"all"`: Show all headings at this level.
- `"current"`: Only show the active heading at this level.
- `"current-parent"`: Show siblings of the active heading (e.g., all subsections of the current section).
- `"none"`: Hide this level.

Default Behavior:

- Part transitions: Show all Parts, hide Sections/Subsections.
- Section transitions: Show current Part, all Sections, current Subsections.

4 Theme Reference

4.1 Sidebar Theme

The sidebar theme provides a persistent navigation bar on the left or right side. It now automatically displays the presentation title at the top of the bar for better branding.

4.1.1 Theme Parameters

side	string	"left" or "right". Default: "left".
width	ratio	Width of the sidebar. Default: 22%.
sidebar-color	color	Background color of the sidebar.
main-color	color	Background color of the content area. Default: white.
active-color	color	Highlight color for the current item in the sidebar.
logo	content	An image or shape to display in the sidebar above the title.
logo-position	string	"top" or "bottom". Default: "top".
outline-options	dictionary	See "Outline Configuration" below. Customizes visibility, spacing, and styling.

4.1.1.1 Outline Configuration

The outline-options dictionary allows fine-grained control over the sidebar navigation menu. It merges with the theme defaults to customize the progressive-outline component.

level- $\{n\}$ -mode	Visibility for level n (1-3). Options: "all", "current", "current-parent", "none".
spacing	Dictionary for layout. Keys include indent- $\{n\}$ (e.g., indent-2) and v-between- $\{prev\}$ - $\{curr\}$ (e.g., v-between-1-2) defining vertical gaps between specific level transitions.
text-styles	Dictionary defining font styles. Keys: level- $\{n\}$ containing sub-keys active, inactive, completed (each accepting text parameters like fill, weight).
match-page-only	Bool. If true (default), the outline highlights only the heading exactly on the current page. If false, it maintains the highlight on the current logical section even on subsequent slides.

4.2 Miniframes Theme

Inspired by the Beamer Berlin theme, it uses dots to show progress within sections. It features a specific separator | when three levels of hierarchy are used. It fully supports max-length truncation and <short> titles for its section names.

4.2.1 Navigation Dictionary

The navigation parameter is a dictionary containing:

position	string	"top" or "bottom". Default: "top".
style	string	"compact" (one row) or "grid" (one row per subsection).
marker-shape	string	"circle" or "square".
marker-size	length	Size of the dots. Default: 4pt.
fill	color	Color of the navigation bar block.
show-level1-titles	bool	Show names of sections in the bar. Default: true.

4.3 Split Theme

Features a horizontal header divided into two contrasting areas for Section and Subsection titles. It also supports `max-length` and `<short>` titles for both blocks.

4.3.1 Theme Parameters

primary	color	Background color for the Section block.
secondary	color	Background color for the Subsection block.
navigation-style	string	"all" (show all siblings) or "current".
header-columns	tuple	Width ratios for the header blocks. Default: (1fr, 1fr).
section-align	alignment	Horizontal alignment for section text. Default: right.

4.4 Progressive Outline Theme

A clean theme focused on document progression with a breadcrumb-style header. It supports dynamic fil-d'ariane based on the active mapping, and automatically integrates `max-length` and `short` titles.

4.4.1 Theme Parameters

header	content auto	Override the top breadcrumb navigation.
footer	content auto	Override the bottom page number area.

4.5 Minimal Theme

A content-first theme with zero distractions. It has no persistent headers or sidebars, providing the maximum possible area for your content while still supporting automatic roadmap transitions.

It features a discrete breadcrumb-style navigation in the footer by default, providing a sense of progression without cluttering the slide.

4.5.1 Theme Parameters

header	content none	Optional header content. Default: none.
footer	content auto	Optional footer content. Displays a breadcrumb navigation with author and page number by default.

5 Hooks API

If you need to generate a transition slide that doesn't fit the roadmap pattern (e.g., a full-page image), use hooks. They take precedence over the transition engine.

- on-part-change(heading)
- on-section-change(heading)
- on-subsection-change(heading)

Example:

```
#show: template.with(  
  on-section-change: (h) => {  
    empty-slide(fill: black)[  
      #set align(center + horizon)  
      #text(white, size: 2em)[Next Chapter: #h.body]  
    ]  
  }  
)
```