G

```
(
  target: "good",
  name: "once",
  func: auto,
  hider: auto,
  active: true,
  inherited: true,
  leftover: false,
) (
  target: "good",
  name: "apply",
  func: auto,
  hider: auto,
  active: auto,
  inherited: true,
  leftover: true,
)
```

COMMAND

```
(
  target: "good",
  name: "once",
  func: (..) => ..,
  hider: auto,
  active: true,
  inherited: true,
  leftover: false,
) (
  target: "good",
  name: "start",
  func: text,
  hider: auto,
  active: true,
  inherited: true,
  leftover: true,
)
```

RULE

```
(
  (
    target: "good",
    name: "once",
    func: auto,
    hider: auto,
    active: true,
    inherited: true,
```

```
    leftover: false,
  ),
) (
  (
    target: "good",
    name: "apply",
    func: text,
    hider: auto,
    active: auto,
    inherited: true,
    leftover: true,
  ),
) (
  (
    target: "good",
    name: "stop",
    func: auto,
    hider: hide,
    active: false,
    inherited: false,
    leftover: false,
  ),
) (
  (
    target: "good",
    name: "revert",
    func: auto,
    hider: auto,
    active: auto,
    inherited: false,
    leftover: true,
  ),
) (
  (
    target: "good",
    name: "apply",
    func: hide,
    hider: auto,
    active: auto,
    inherited: true,
    leftover: true,
  ),
  (
    target: "bad",
    name: "apply",
    func: figure,
    hider: auto,
    active: auto,
    inherited: true,
    leftover: true,
```

```
  ),
)
```

RESOLVE

```
(
  (
    c: (
      visible: true,
      history: (auto,),
      func: (auto,),
      hider: auto,
    ),
    d: (
      visible: true,
      history: (auto,),
      func: (auto,),
      hider: auto,
    ),
  ),
  (
    c: (
      visible: true,
      history: (auto, figure),
      func: (auto, figure),
      hider: auto,
    ),
    d: (
      visible: true,
      history: (auto, text),
      func: (auto, text),
      hider: auto,
    ),
  ),
)
```