

G



G

```
(
  target: "good",
  name: "once",
  func: auto,
  hider: auto,
  active: true,
  inherited: true,
  leftover: false,
) (
  target: "good",
  name: "apply",
  func: auto,
  hider: auto,
  active: auto,
  inherited: true,
  leftover: true,
)
```

COMMAND

```
(
  target: "good",
  name: "once",
  func: (..) => ..,
  hider: auto,
  active: true,
  inherited: true,
  leftover: false,
) (
  target: "good",
  name: "start",
  func: text,
  hider: auto,
  active: true,
  inherited: true,
  leftover: true,
)
```

RULE

```
(
  (
    target: "good",
    name: "once",
    func: auto,
    hider: auto,
    active: true,
    inherited: true,
```

```
    leftover: false,
  ),
) (
  (
    target: "good",
    name: "apply",
    func: text,
    hider: auto,
    active: auto,
    inherited: true,
    leftover: true,
  ),
) (
  (
    target: "good",
    name: "stop",
    func: auto,
    hider: hide,
    active: false,
    inherited: false,
    leftover: false,
  ),
) (
  (
    target: "good",
    name: "revert",
    func: auto,
    hider: auto,
    active: auto,
    inherited: false,
    leftover: true,
  ),
) (
  (
    target: "good",
    name: "apply",
    func: hide,
    hider: auto,
    active: auto,
    inherited: true,
    leftover: true,
  ),
  (
    target: "bad",
    name: "apply",
    func: figure,
    hider: auto,
    active: auto,
    inherited: true,
    leftover: true,
  )
)
```

```
    ),  
  )  
}
```

RESOLVE

```
(  
  (  
    c: (  
      visible: true,  
      history: (auto,),  
      func: (auto,),  
      hider: auto,  
    ),  
    d: (  
      visible: true,  
      history: (auto,),  
      func: (auto,),  
      hider: auto,  
    ),  
  ),  
(  
  c: (  
    visible: true,  
    history: (auto, figure),  
    func: (auto, figure),  
    hider: auto,  
  ),  
  d: (  
    visible: true,  
    history: (auto, text),  
    func: (auto, text),  
    hider: auto,  
  ),  
)  
)
```