

PacketBench QA Workbook

Repository	packetloss404/PackageBench
Commit reviewed by the audit	2f4a10c384508af75a792604fff91b55a16dee26
Commit this workbook was built from	f3421a4ba3a34e532a1df5963febb2f98e998e3a
Date built	2026-09-05
Run it locally (exact command)	pnpm install && pnpm tauri dev
Then run the gates	pnpm gates:fast (format, lint, typecheck, vitest) and cd src-tauri && cargo test --lib
Smoke test	node smoke-test.mjs (live mode: set PACKETBENCH_MCP_URL and PACKETBENCH_MCP_TOKEN from Settings > MCP > MCP Provider)
Exact URL in prod	none (desktop app; no hosted URL). Installed via the NSIS installer PacketBench_<version>_x64-setup.exe. The only HTTP endpoint is the loopback MCP server: http://127.0.0.1:<port>/health
Log file	%LOCALAPPDATA%\PackageBench\logs\packetbench.log.<YYYY-MM-DD>
Data dir	%USERPROFILE%\.\packetbench
Audit report	docs/audit-2026-09-04.md (findings F01-F20, patches P01-P12, unresolved U01-U07)

How to use: every checklist row has an empty checkbox cell (tick when done) and a P/F cell (write P or F). Failure signatures are the literal strings the app or the log prints. Where a browser cannot make the request, the literal curl is given with <TOKEN> as the placeholder for the bearer shown in Settings > MCP > MCP Provider.

Manual IPC calls: run `pnpm tauri dev`, press Ctrl+Shift+I in the app window, and in the devtools console call `await window.\_\_TAURI\_INTERNALS\_\_.invoke('<command>', {<camelCase args>})`. Release builds do not expose devtools; that is expected.

Surface inventory with negative cases

Reprinted from audit deliverable 2 and scanned live from src-tauri/src. Four negative cases per IPC row: UNAUTH = call from outside the webview (there is no path: Tauri IPC is reachable only from the app's own webview; record N/A unless you find one). ROLE = call from the read-only Monitor window (open one via Flight Deck > attempt tile > 'Monitor' or the conversation header menu 'Send to Monitor', then devtools in that window): expected rejection string is exactly "This read-only Monitor cannot invoke that application command." for every command except the five marked 'main, monitor'. ID = substitute a foreign/absent id (session id, flight id, conversation id): expected an error string naming the missing entity (e.g. "PTY session <id> not found", "unknown flightId", "Conversation id cannot traverse paths"). BODY = omit a required argument or send the wrong type: Tauri returns "invalid args `<arg>` for command `<name>`" before the handler runs.

ID	Command	Roles	Mutates / reaches	Location	UNAUTH	ROLE	ID	BODY	[]	P/F
C001	analyze_code_quality	main only	Reads project; may call aux LLM	src-tauri/src/commands/code_quality.rs:330						
C002	archive_project_memory	main only	Archives a note	src-tauri/src/commands/project_memory.rs:917						
C003	ask_agent_chat_stream	main only	Aux LLM stream (spend)	src-tauri/src/commands/insights.rs:72						
C004	ask_side_chat_stream	main only	Aux LLM stream (spend)	src-tauri/src/commands/side_chat.rs:107						
C005	cancel_api_agent_session	main only	Cancels a turn	src-tauri/src/commands/api_agent.rs:1414						
C006	cancel_flight_attempt	main only	Cancels an attempt	src-tauri/src/commands/flight_attempts.rs:1016						
C007	cancel_pending_tools	main only	Denies pending prompts	src-tauri/src/commands/api_agent.rs:1616						
C008	cancel_quality_fix	main only	Cancels a running task	src-tauri/src/commands/code_quality_autofix.rs:554						
C009	cancel_quality_run	main only	Cancels a running task	src-tauri/src/commands/quality_runner.rs:1053						
C010	cancel_recording	main only	Stops capture	src-tauri/src/commands/dictation/audio.rs:814						
C011	cancel_side_chat_stream	main only	Cancels a running task	src-tauri/src/commands/side_chat.rs:304						
C012	change_model	main only	Changes model	src-tauri/src/commands/api_agent.rs:1432						
C013	cleanup_attempt_worktree_ssh	main only	Removes remote worktree over SSH	src-tauri/src/commands/flight_attempts.rs:1092						
C014	cleanup_flight_integration_worktree	main only	Removes local integration worktree	src-tauri/src/commands/flight_attempts.rs:1058						
C015	clear_dictation_history	main only	Deletes SQLite rows	src-tauri/src/commands/dictation/history.rs:312						
C016	cli_launch_diagnostics	main only	Resolves launch path	src-tauri/src/commands/agent.rs:277						
C017	clone_repo_remote	main only	git clone over SSH (URL/branch validated)	src-tauri/src/commands/git.rs:930						
C018	close_api_agent_session	main only	Ends a session	src-tauri/src/commands/api_agent.rs:1719						
C019	close_monitor_window	main, monitor	Closes monitor window	src-tauri/src/commands/monitor_windows.rs:162						
C020	code_quality_ai_explain	main only	Aux LLM (spend)	src-tauri/src/commands/code_quality.rs:652						
C021	code_quality_ai_summarize	main only	Aux LLM (spend)	src-tauri/src/commands/code_quality.rs:735						
C022	code_quality_probe_fixers	main only	Probes project (read)	src-tauri/src/commands/code_quality_autofix.rs:254						
C023	code_quality_run_fix	main only	Spawns eslint --fix / prettier / cargo fix / pnpm audit --fix	src-tauri/src/commands/code_quality_autofix.rs:319						
C024	create_conversation_worktree	main only	git worktree add	src-tauri/src/commands/git.rs:393						
C025	create_issue_worktree	main only	git worktree add	src-tauri/src/commands/git.rs:466						
C026	create_project_memory	main only	Writes a note in the project memory dir	src-tauri/src/commands/project_memory.rs:901						
C027	create_pty_session	main only	Spawns allowlisted CLI/shell in a PTY with caller args+env	src-tauri/src/commands/pty.rs:604						
C028	delete_api_key	main only	Keyring delete	src-tauri/src/commands/api_keys.rs:219						
C029	delete_conversation_file	main only	Deletes a conversation file	src-tauri/src/commands/conversations.rs:93						
C030	delete_crash	main only	Deletes a crash log (confined)	src-tauri/src/commands/crashes.rs:88						
C031	delete_dictation_entry	main only	Deletes one row	src-tauri/src/commands/dictation/history.rs:285						
C032	delete_mcp_server	main only	Removes an mcpServers entry	src-tauri/src/commands/mcp.rs:404						
C033	delete_packet_agent_token	main only	Keyring delete	src-tauri/src/commands/packet_agent.rs:247						
C034	delete_ssh_password	main only	Keyring delete	src-tauri/src/commands/ssh_keys.rs:220						
C035	delete_whisper_model	main only	Deletes a model file	src-tauri/src/commands/dictation/models.rs:539						
C036	deliver_dictation_text	main only	Sets clipboard; optional Ctrl+V into foreground app	src-tauri/src/commands/dictation/delivery.rs:31						
C037	detect_agent	main only	Spawns <cli> --version	src-tauri/src/commands/agent.rs:142						
C038	detect_cli_catalog	main only	Spawns each CLI --version	src-tauri/src/commands/agent.rs:151						
C039	detect_quality_checks	main only	None (read)	src-tauri/src/commands/quality_runner.rs:899						
C040	diagnose_mcp_server	main only	Spawns the configured stdio MCP server	src-tauri/src/commands/mcp.rs:224						
C041	download_whisper_model	main only	Downloads pinned-SHA256 model from huggingface.co	src-tauri/src/commands/dictation/models.rs:278						
C042	export_conversation_markdown	main only	None (pure render)	src-tauri/src/commands/conversations.rs:107						
C043	extract_patterns	main only	Aux LLM (spend)	src-tauri/src/commands/memory.rs:185						

ID	Command	Roles	Mutates / reaches	Location	UNAUT H	ROLE	ID	BODY	[]	P/F
C044	focus_monitor_route_in_main	main, monitor	Focuses main window	src-tauri/src/commands/monitor_windows.rs:185						
C045	get_api_key_exists	main only	Keyring read	src-tauri/src/commands/api_keys.rs:192						
C046	get_app_known_hosts_path	main only	None (read)	src-tauri/src/commands/pty.rs:1304						
C047	get_aux_provider_options	main only	None (read)	src-tauri/src/commands/aux_routing.rs:106						
C048	get_aux_route_resolutions	main only	None (read)	src-tauri/src/commands/aux_routing.rs:72						
C049	get_custom_compat_base_url	main only	None (read)	src-tauri/src/commands/custom_compat.rs:11						
C050	get_custom_compat_models	main only	None (read)	src-tauri/src/commands/custom_compat.rs:31						
C051	get_cwd	main only	None	src-tauri/src/commands/fs.rs:23						
C052	get_dictation_analytics	main only	None (read)	src-tauri/src/commands/dictation/analytics.rs:674						
C053	get_dictation_history	main only	None (read)	src-tauri/src/commands/dictation/history.rs:214						
C054	get_dictation_settings	main only	None (read)	src-tauri/src/commands/dictation/config.rs:110						
C055	get_file_head_content	main only	None (read)	src-tauri/src/commands/git.rs:221						
C056	get_git_branch	main only	None (read)	src-tauri/src/commands/git.rs:9						
C057	get_git_branch_remote	main only	None (read)	src-tauri/src/commands/git.rs:542						
C058	get_git_review_evidence	main only	None (read)	src-tauri/src/commands/git.rs:674						
C059	get_git_status	main only	None (read)	src-tauri/src/commands/git.rs:19						
C060	get_git_status_remote	main only	None (read)	src-tauri/src/commands/git.rs:557						
C061	get_minimax_base_url	main only	None (read)	src-tauri/src/commands/minimax.rs:14						
C062	get_monitor_window_route	main, monitor	Read	src-tauri/src/commands/monitor_windows.rs:146						
C063	get_ollama_base_url	main only	None (read)	src-tauri/src/commands/ollama.rs:87						
C064	get_ollama_runtime_options	main only	None (read)	src-tauri/src/commands/ollama.rs:131						
C065	get_packet_agent_token_exists	main only	Keyring read	src-tauri/src/commands/packet_agent.rs:238						
C066	get_provider_auth_status	main only	Reads CLI credential files	src-tauri/src/commands/provider_auth.rs:463						
C067	get_provider_auth_status_for_dir	main only	Reads credential files in a dir	src-tauri/src/commands/provider_auth.rs:563						
C068	get_provider_launch_stats	main only	None (read)	src-tauri/src/commands/provider_stats.rs:172						
C069	get_sidecar_status	main only	None (read)	src-tauri/src/commands/agent_sidecar/mod.rs:206						
C070	get_ssh_password_exists	main only	Keyring read	src-tauri/src/commands/ssh_keys.rs:167						
C071	git_commit	main only	git commit (staged only)	src-tauri/src/commands/git.rs:234						
C072	git_commit_remote	main only	git commit over SSH	src-tauri/src/commands/git.rs:993						
C073	git_create_branch	main only	git branch (name validated)	src-tauri/src/commands/git.rs:296						
C074	git_create_branch_remote	main only	git branch over SSH	src-tauri/src/commands/git.rs:1068						
C075	git_diff_file_remote	main only	git diff over SSH (read)	src-tauri/src/commands/git.rs:1023						
C076	git_get_origin_url	main only	Read	src-tauri/src/commands/git.rs:365						
C077	git_host_add_connection	main only	Writes git-hosts.json + keyring token (P05 https unless local)	src-tauri/src/commands/github.rs:942						
C078	git_host_has_token	main only	Read	src-tauri/src/commands/github.rs:1059						
C079	git_host_list_connections	main only	Read	src-tauri/src/commands/github.rs:872						
C080	git_host_probe_credential	main only	HTTPS to pasted instance URL with pasted token (P05)	src-tauri/src/commands/git_host_probe.rs:348						
C081	git_host_remove_connection	main only	Deletes connection + token	src-tauri/src/commands/github.rs:1004						
C082	git_host_set_active	main only	Switches active host	src-tauri/src/commands/github.rs:379						
C083	git_host_set_token	main only	Keyring rewrite	src-tauri/src/commands/github.rs:1041						
C084	git_host_update_connection	main only	Rename/rotate after live probe	src-tauri/src/commands/github.rs:1312						
C085	git_pull	main only	git pull	src-tauri/src/commands/git.rs:286						
C086	git_pull_remote	main only	git pull over SSH	src-tauri/src/commands/git.rs:1055						
C087	git_push	main only	git push	src-tauri/src/commands/git.rs:276						
C088	git_push_branch	main only	git push -u origin <branch> [--force-with-lease]	src-tauri/src/commands/git.rs:346						
C089	git_push_remote	main only	git push over SSH	src-tauri/src/commands/git.rs:1042						
C090	git_safety_check	main only	Read	src-tauri/src/commands/git.rs:375						
C091	git_stage_files	main only	git add --	src-tauri/src/commands/git.rs:314						
C092	git_stage_files_remote	main only	git add over SSH	src-tauri/src/commands/git.rs:958						
C093	git_unstage_files	main only	git restore --staged --	src-tauri/src/commands/git.rs:329						
C094	git_unstage_files_remote	main only	git restore over SSH	src-tauri/src/commands/git.rs:976						
C095	github_ai_catch_up	main only	GitHub read + aux LLM (spend)	src-tauri/src/commands/github.rs:2869						
C096	github_ai_pr_description	main only	GitHub read + aux LLM (spend)	src-tauri/src/commands/github.rs:2242						
C097	github_ai_pr_review	main only	GitHub read + aux LLM (spend)	src-tauri/src/commands/github.rs:2362						
C098	github_ai_triage	main only	GitHub read + aux LLM (spend)	src-tauri/src/commands/github.rs:3126						
C099	github_clear_token	main only	Keyring delete	src-tauri/src/commands/github.rs:525						
C100	github_close_issue	main only	Mutates remote repo via git-host API (close issue)	src-tauri/src/commands/github.rs:1767						
C101	github_close_pr	main only	Mutates remote repo via git-host API (close pr)	src-tauri/src/commands/github.rs:3416						
C102	github_convert_pr_to_draft	main only	Mutates remote repo via git-host API (convert pr to draft)	src-tauri/src/commands/github.rs:3440						

ID	Command	Roles	Mutates / reaches	Location	UNAUTH	ROLE	ID	BODY	[]	P/F
C103	github_create_issue	main only	Mutates remote repo via git-host API (create issue)	src-tauri/src/commands/github.rs:1499						
C104	github_create_pr	main only	Mutates remote repo via git-host API (create pr)	src-tauri/src/commands/github.rs:1561						
C105	github_create_repo_milestone	main only	Mutates remote repo via git-host API (create repo milestone)	src-tauri/src/commands/github.rs:1932						
C106	github_device_flow_commit	main only	Keyring write	src-tauri/src/commands/github.rs:837						
C107	github_device_flow_discard	main only	Drops parked token	src-tauri/src/commands/github.rs:854						
C108	github_device_flow_poll	main only	Polls github.com; parks token	src-tauri/src/commands/github.rs:751						
C109	github_device_flow_probe_pending	main only	Probes parked token	src-tauri/src/commands/github.rs:819						
C110	github_device_flow_start	main only	github.com device endpoint (needs PACKETBENCH_GITHUB_CLIENT_ID)	src-tauri/src/commands/github.rs:570						
C111	github_get_authenticated_user	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1400						
C112	github_get_issue	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1485						
C113	github_get_pr_checks	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:3619						
C114	github_get_pr_diff	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1602						
C115	github_has_token	main only	Read	src-tauri/src/commands/github.rs:535						
C116	github_investigate_issue	main only	GitHub read + aux LLM (spend)	src-tauri/src/commands/github.rs:2051						
C117	github_list_branches	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:2473						
C118	github_list_repo_comments	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1687						
C119	github_list_issues	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1448						
C120	github_list_issues_page	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1975						
C121	github_list_notifications	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:4259						
C122	github_list_pr_review_comments	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:3991						
C123	github_list_pr_reviews	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:3962						
C124	github_list_prs	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1586						
C125	github_list_prs_page	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:2018						
C126	github_list_releases	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1432						
C127	github_list_repo_assignable_users	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1959						
C128	github_list_repo_labels	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1900						
C129	github_list_repo_milestones	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1916						
C130	github_list_repos	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1379						
C131	github_list_repos_page	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:2036						
C132	github_mark_notification_read	main only	PATCH notification thread	src-tauri/src/commands/github.rs:4286						
C133	github_merge_pr	main only	Mutates remote repo via git-host API (merge pr)	src-tauri/src/commands/github.rs:3326						
C134	github_oauth_configured	main only	Read	src-tauri/src/commands/github.rs:616						
C135	github_post_issue_comment	main only	Mutates remote repo via git-host API (post issue comment)	src-tauri/src/commands/github.rs:1710						
C136	github_post_pr_review_comment	main only	Mutates remote repo via git-host API (post pr review comment)	src-tauri/src/commands/github.rs:4024						
C137	github_reopen_issue	main only	Mutates remote repo via git-host API (reopen issue)	src-tauri/src/commands/github.rs:1780						
C138	github_reopen_pr	main only	Mutates remote repo via git-host API (reopen pr)	src-tauri/src/commands/github.rs:3427						
C139	github_reply_to_pr_review_comment	main only	Mutates remote repo via git-host API (reply to pr review comment)	src-tauri/src/commands/github.rs:4094						
C140	github_set_issue_assignees	main only	Mutates remote repo via git-host API (set issue assignees)	src-tauri/src/commands/github.rs:1793						
C141	github_set_issue_labels	main only	Mutates remote repo via git-host API (set issue labels)	src-tauri/src/commands/github.rs:1815						
C142	github_set_issue_milestone	main only	Mutates remote repo via git-host API (set issue milestone)	src-tauri/src/commands/github.rs:1886						
C143	github_set_pr_labels	main only	Mutates remote repo via git-host API (set pr labels)	src-tauri/src/commands/github.rs:2550						
C144	github_set_pr_milestone	main only	Mutates remote repo via git-host API (set pr milestone)	src-tauri/src/commands/github.rs:2602						
C145	github_set_pr_reviewers	main only	Mutates remote repo via git-host API (set pr reviewers)	src-tauri/src/commands/github.rs:2516						
C146	github_set_token	main only	Probes GitHub then keyring write github-token	src-tauri/src/commands/github.rs:507						
C147	github_update_issue	main only	Mutates remote repo via git-host API (update issue)	src-tauri/src/commands/github.rs:1530						
C148	inspect_cli_launch	main only	Resolves launch path	src-tauri/src/commands/agent.rs:244						
C149	inspect_packetcode_installation	main only	Spawns packetcode --version	src-tauri/src/commands/agent.rs:318						
C150	integrate_flight_attempt	main only	Merges attempt into integration	src-tauri/src/commands/git.rs:836						
C151	issues_extract_from_spec	main only	Aux LLM (spend)	src-tauri/src/commands/issues.rs:127						
C152	kill_pty	main only	Kills a PTY process tree	src-tauri/src/commands/pty.rs:950						
C153	kill_pty_and_wait	main only	Kills a PTY tree and waits	src-tauri/src/commands/pty.rs:980						
C154	land_flight_integration	main only	Merges integration into root	src-tauri/src/commands/git.rs:881						
C155	launch_flight_async	main only	Creates worktrees (local/SSH), starts agent sessions (spend)	src-tauri/src/commands/flight_attempts.rs:625						
C156	list_audio_devices	main only	Read	src-tauri/src/commands/dictation/audio.rs:160						
C157	list_crashes	main only	None (read)	src-tauri/src/commands/crashes.rs:44						
C158	list_directory	main only	Read inside workspace	src-tauri/src/commands/fs.rs:44						
C159	list_ollama_models	main only	GET Ollama base URL (no secret)	src-tauri/src/commands/ollama.rs:163						

ID	Command	Roles	Mutates / reaches	Location	UNAUT H	ROLE	ID	BODY	[]	P/F
C160	list_project_files	main only	Read	src-tauri/src/commands/fs.rs:375						
C161	list_project_memory	main only	Read	src-tauri/src/commands/project_memory.rs:896						
C162	list_provider_models	main only	GET provider catalogs with keyring key	src-tauri/src/commands/provider_models.rs:760						
C163	list_pty_sessions	main only	None (read)	src-tauri/src/commands/pty.rs:972						
C164	list_skills	main only	None (read)	src-tauri/src/commands/skills.rs:164						
C165	list_slash_commands	main only	None (read)	src-tauri/src/commands/slash_commands.rs:111						
C166	list_subdirectories	main only	Read any absolute dir	src-tauri/src/commands/fs.rs:160						
C167	list_whisper_models	main only	Read	src-tauri/src/commands/dictation/models.rs:241						
C168	list_wsl_distributions	main only	Spawns wsl.exe --list	src-tauri/src/commands/pty.rs:301						
C169	load_conversations	main, monitor	None (read)	src-tauri/src/commands/conversations.rs:53						
C170	load_persisted_state	main, monitor	None (read)	src-tauri/src/commands/state.rs:12						
C171	load_webview_storage_mirror	main only	Read	src-tauri/src/commands/webview_storage_mirror.rs:79						
C172	mark_attempt_status	main only	Rewrites attempt status	src-tauri/src/commands/flight_attempts.rs:1230						
C173	mcp_server_available_tools	main only	Read	src-tauri/src/mcp_server/mod.rs:314						
C174	mcp_server_recent_activity	main only	Read	src-tauri/src/mcp_server/mod.rs:297						
C175	mcp_server_start	main only	Binds 127.0.0.1:<port>, mints bearer, serves MCP	src-tauri/src/mcp_server/mod.rs:226						
C176	mcp_server_status	main only	Read (returns token)	src-tauri/src/mcp_server/mod.rs:284						
C177	mcp_server_stop	main only	Stops MCP server	src-tauri/src/mcp_server/mod.rs:271						
C178	merge_conversation_branch	main only	git squash-merge into HEAD	src-tauri/src/commands/git.rs:433						
C179	open_monitor_window	main only	Creates monitor-main window	src-tauri/src/commands/monitor_windows.rs:95						
C180	packet_agent_request	main only	HTTPS to PacketAgent endpoint with keyring bearer; POST/PUT mutate deployments	src-tauri/src/commands/packet_agent.rs:255						
C181	parse_spec_to_flight	main only	Aux LLM (spend)	src-tauri/src/commands/spec.rs:89						
C182	parse_spec_to_tickets	main only	Aux LLM (spend)	src-tauri/src/commands/spec.rs:104						
C183	path_is_dir	main only	Existence probe, any path	src-tauri/src/commands/fs.rs:37						
C184	prepare_flight_integration_branch	main only	Creates integration branch	src-tauri/src/commands/git.rs:800						
C185	probe_packetcode_integration	main only	Spawns packetcode --version / doctor --json	src-tauri/src/commands/agent.rs:362						
C186	probe_terminal_shell	main only	Spawns <shell> --version	src-tauri/src/commands/pty.rs:252						
C187	read_codex_statusline_states	main only	None (read)	src-tauri/src/commands/statusline/codex.rs:257						
C188	read_crash	main only	Read (confined)	src-tauri/src/commands/crashes.rs:82						
C189	read_file_contents	main only	Read inside workspace (2 MB cap)	src-tauri/src/commands/fs.rs:221						
C190	read_file_for_diff	main only	Read (confined)	src-tauri/src/commands/fs.rs:418						
C191	read_mcp_servers	main only	Read both files	src-tauri/src/commands/mcp.rs:364						
C192	read_opencode_statusline_states	main only	None (read)	src-tauri/src/commands/statusline/opencode.rs:23						
C193	read_prompt_history	main only	None (read)	src-tauri/src/commands/history.rs:33						
C194	read_pty_transcript	main only	None (read)	src-tauri/src/commands/pty.rs:1014						
C195	read_statusline_states	main only	None (read)	src-tauri/src/commands/statusline/claude.rs:29						
C196	read_usage_analytics	main only	None (read)	src-tauri/src/commands/analytics.rs:72						
C197	remove_conversation_worktree	main only	git worktree remove	src-tauri/src/commands/git.rs:409						
C198	resize_pty	main only	Resizes a PTY	src-tauri/src/commands/pty.rs:924						
C199	resolve_agents_md	main only	Reads AGENTS.md chain	src-tauri/src/commands/agents_md.rs:12						
C200	respond_edit	main only	Applies/declines a pending edit	src-tauri/src/commands/api_agent.rs:1575						
C201	respond_permission	main only	Resolves a risky-tool prompt	src-tauri/src/commands/api_agent.rs:1507						
C202	retry_last_turn	main only	Re-runs last turn (spend)	src-tauri/src/commands/api_agent.rs:1646						
C203	run_quality_checks	main only	Spawns detected lint/typecheck/test/cargo	src-tauri/src/commands/quality_runner.rs:911						
C204	save_agents_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:55						
C205	save_cli_accounts_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:104						
C206	save_conversation	main only	Writes conversations/<id>.json (id validated)	src-tauri/src/commands/conversations.rs:42						
C207	save_flights_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:50						
C208	save_issues_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:74						
C209	save_memory_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:84						
C210	save_persisted_state	main only	Rewrites state.v1.json (not issues/retros)	src-tauri/src/commands/state.rs:28						
C211	save_servers_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:92						
C212	save_settings_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:60						
C213	save_ui_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:69						
C214	save_webview_storage_mirror	main only	Rewrites webview-storage-mirror.json (8 MB cap)	src-tauri/src/commands/webview_storage_mirror.rs:120						
C215	save_workspaces_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:79						
C216	scan_codebase_memory	main only	Reads project + aux LLM (spend)	src-tauri/src/commands/memory.rs:93						

ID	Command	Roles	Mutates / reaches	Location	UNAUT H	ROLE	ID	BODY	[]	P/F
C217	search_dictation_history	main only	SQLite read	src-tauri/src/commands/dictation/history.rs:252						
C218	seed_cli_account_config_dir	main only	Copies settings.json/config.toml between abs dirs (never credentials)	src-tauri/src/commands/cli_account.rs:90						
C219	send_api_agent_message	main only	Continues a turn (LLM spend)	src-tauri/src/commands/api_agent.rs:1343						
C220	set_api_key	main only	Keyring write api-key-<provider>	src-tauri/src/commands/api_keys.rs:169						
C221	set_approve_writes	main only	Toggles edit gate	src-tauri/src/commands/api_agent.rs:1542						
C222	set_attempt_draft_pr	main only	Records PR URL	src-tauri/src/commands/flight_attempts.rs:1125						
C223	set_attempt_review_gate	main only	Records review verdict	src-tauri/src/commands/flight_attempts.rs:1195						
C224	set_aux_routing_overrides	main only	Updates in-memory routing map	src-tauri/src/commands/aux_routing.rs:50						
C225	set_custom_compat_base_url	main only	Writes provider-settings.v1.json (P05)	src-tauri/src/commands/custom_compat.rs:18						
C226	set_custom_compat_models	main only	Writes model list	src-tauri/src/commands/custom_compat.rs:38						
C227	set_dictation_settings	main only	Writes dictation config	src-tauri/src/commands/dictation/config.rs:156						
C228	set_flight_publish_attempts_as_prs	main only	Flight flag	src-tauri/src/commands/flight_attempts.rs:1158						
C229	set_minimax_base_url	main only	Writes provider-settings.v1.json (P05 https unless local)	src-tauri/src/commands/minimax.rs:19						
C230	set_ollama_base_url	main only	Writes provider-settings.v1.json (http allowed; no secret)	src-tauri/src/commands/ollama.rs:92						
C231	set_ollama_runtime_options	main only	Writes num_ctx/keep_alive	src-tauri/src/commands/ollama.rs:138						
C232	set_packet_agent_token	main only	Keyring write packet-agent-token	src-tauri/src/commands/packet_agent.rs:227						
C233	set_permission_mode	main only	Changes gate posture	src-tauri/src/commands/api_agent.rs:1481						
C234	set_plan_mode	main only	Toggles plan mode	src-tauri/src/commands/api_agent.rs:1455						
C235	set_ssh_password	main only	Keyring write ssh-<serverid>	src-tauri/src/commands/ssh_keys.rs:187						
C236	sign_out_provider	main only	Deletes ~/.claude/.credentials.json or ~/.codex/auth.json	src-tauri/src/commands/provider_auth.rs:436						
C237	ssh_check_remote_path	main only	Spawns ssh to probe a remote path	src-tauri/src/commands/pty.rs:1356						
C238	ssh_exec	main only	Spawns local ssh with caller argv (P08 denylist); password via askpass/stdin	src-tauri/src/commands/pty.rs:1070						
C239	ssh_fetch_fingerprint	main only	Spawns ssh-keyscan + ssh-keygen	src-tauri/src/commands/pty.rs:1153						
C240	ssh_pin_host	main only	Appends to ~/.packetbench/ssh/known_hosts	src-tauri/src/commands/pty.rs:1264						
C241	start_api_agent_session	main only	Starts agent loop: keyring key, gated tools (P02 default ask), MCP, hooks; LLM spend	src-tauri/src/commands/api_agent.rs:1051						
C242	start_packet_agent_stream	main only	Opens SSE stream to PacketAgent (bearer)	src-tauri/src/commands/packet_agent_stream.rs:176						
C243	start_recording	main only	Opens microphone	src-tauri/src/commands/dictation/audio.rs:458						
C244	stop_packet_agent_stream	main only	Stops SSE task	src-tauri/src/commands/packet_agent_stream.rs:220						
C245	stop_recording	main only	Stops capture, runs whisper	src-tauri/src/commands/dictation/audio.rs:855						
C246	summarize_flight	main only	Aux LLM (spend)	src-tauri/src/commands/memory.rs:223						
C247	summarize_session	main only	Aux LLM (spend)	src-tauri/src/commands/memory.rs:164						
C248	test_audio_device	main only	Opens a device	src-tauri/src/commands/dictation/audio.rs:294						
C249	toggle_pinned_pattern	main only	Flips a memory pattern flag	src-tauri/src/commands/memory.rs:278						
C250	update_project_memory	main only	Rewrites a note (revision check)	src-tauri/src/commands/project_memory.rs:909						
C251	watch_project_memory	main only	Starts fs watcher	src-tauri/src/commands/project_memory.rs:974						
C252	write_file_contents	main only	Writes a file inside workspace	src-tauri/src/commands/fs.rs:246						
C253	write_mcp_server	main only	Upserts mcpServers in ~/.claude/settings.json or <project>/mcp.json	src-tauri/src/commands/mcp.rs:381						
C254	write_pty	main only	Writes keystrokes to a PTY (64 KB cap)	src-tauri/src/commands/pty.rs:899						

ID	Route	Auth	Mutates	Location	[]	P/F
N001	GET /health on 127.0.0.1:<port> (MCP server)	any local process; Origin must be absent or loopback	None	src-tauri/src/mcp_server/transport.rs		
N002	POST/GET/DELETE /mcp (MCP Streamable HTTP)	bearer + loopback Origin + Host allowlist	tools M008-M010, M013-M016 mutate (allow_writes only)	src-tauri/src/mcp_server/transport.rs:69-100		
M001-M016	MCP tools ping, get_active_flight, list_runnable_tasks, read_task_details, read_memory_context, search_project_memory, read_project_memory, create/update/archive_project_memory, list_workspaces, read_coordination_inbox, append_handoff, escalate, post_coordination_message, acknowledge_coordination_message	bearer; writes need Allow writes	see audit 2b	src-tauri/src/mcp_server/mod.rs:582-836		

ID	Route	Auth	Mutates	Location	[]	P/F
R001-R002	MCP resources packetbench://project{flights}flights/{id}flights/{id}/tasks{flights/{id}/inbox{issues}reviews{workspace}memory/patterns{memory/project/{ws}}packetcode/health	bearer; gated by the tool allowlist (P07)	packetcode/health spawns a process	src-tauri/src/mcp_server/mod.rs:923-1030		

Shot list

There are no URLs: PacketBench is a desktop window. Each shot names the in-app location, the state to be in, and the one question the shot answers. Dev builds are served from `http://localhost:1420` inside the window (`tauri.conf.json build.devUrl`).


#	Location + state	Question the shot answers	[]	P/F
S1	Agents view, new API conversation in a repo NOT listed in <code>trusted-projects.json</code> ; provider 'Claude (API)'; anthropic key present	Does the mode chip read 'Manual' (not 'Default') on a fresh conversation? (P02)		
S2	Same conversation; ask 'run `git status` with the bash tool'	Does the Allow once / Always allow / Deny prompt appear before anything runs? (P02)		
S3	Log viewer: Select-String <code>packetbench::trust</code> in today's log after S1	Is 'project is not trusted: repo-supplied hooks, .mcp.json servers, and .claude/agents are ignored' present? (P01)		
S4	Settings > MCP > MCP Provider card, Enable MCP Provider on, Allow writes off, all tools ticked	Are port, bearer token, and served tool list visible? (baseline for S5)		
S5	Same card with only <code>get_active_flight</code> ticked, server re-enabled; terminal running the curl from test T-MCP-07	Does <code>resources/read</code> of <code>packetbench://memory/patterns</code> return the allowlist error? (P07)		
S6	Settings > GitHub > Connect a git host wizard, Gitea, instance URL <code>http://gitea.example.com</code> , any token	Is the error 'Instance URL must use <code>https:// ...</code> ' shown before any request? (P05)		
S7	Settings > Providers > API Keys card	Are keys shown only as present/absent, never as values? (I8)		
S8	Log viewer: Select-String <code>packetbench::boot</code> on app start	Does 'boot check done' appear with <code>issues=0</code> , and is the <code>trust-file</code> line present? (P09)		

Screenshot slots

S1 - Agents view, new API conversation in a repo NOT listed in trusted-projects.json; provider 'Claude (API)'; anthropic key present
Q: Does the mode chip read 'Manual' (not 'Default') on a fresh conversation? (P02)




S2 - Same conversation; ask 'run `git status` with the bash tool'
Q: Does the Allow once / Always allow / Deny prompt appear before anything runs? (P02)




S3 - Log viewer: Select-String packetbench::trust in today's log after S1

Q: Is 'project is not trusted: repo-supplied hooks, .mcp.json servers, and .claude/agents are ignored' present? (P01)

A large, empty rectangular box with a black border, intended for recording the results of the S3 test.

S4 - Settings > MCP > MCP Provider card, Enable MCP Provider on, Allow writes off, all tools ticked

Q: Are port, bearer token, and served tool list visible? (baseline for S5)

A large, empty rectangular box with a black border, intended for recording the results of the S4 test.

S5 - Same card with only get_active_flight ticked, server re-enabled; terminal running the curl from test T-MCP-07
Q: Does resources/read of packetbench://memory/patterns return the allowlist error? (P07)

S6 - Settings > GitHub > Connect a git host wizard, Gitea, instance URL <http://gitea.example.com>, any token
Q: Is the error 'Instance URL must use https:// ...' shown before any request? (P05)

S7 - Settings > Providers > API Keys card

Q: Are keys shown only as present/absent, never as values? (I8)

S8 - Log viewer: Select-String packetbench::boot on app start

Q: Does 'boot check done' appear with issues=0, and is the trust-file line present? (P09)

Test sheets

MCP server (N001/N002) - every row is a literal curl; replace <port> and <TOKEN> from Settings > MCP > MCP Provider

ID	Case	Command	Expected	Failure signature	[]	P/F
T-MCP-01	Health	curl -s -i http://127.0.0.1:<port>/health	HTTP 200; body {"ok":true,"app":"PacketBench","version":"0.13.2","service":"mcp"}	404 (P07 not applied) or connection refused (server not enabled)		
T-MCP-02	No token	curl -s -o /dev/null -w '%{http_code}' -X POST http://127.0.0.1:<port>/mcp -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":1,"method":"initialize","params":{"protocolVersion":"2025-03-26","capabilities":{"clientInfo":{"name":"qa","version":"0"}}}}'	401	200 = bearer layer missing; log has no 'MCP request rejected: bearer token missing or wrong'		
T-MCP-03	Wrong token	curl -s -o /dev/null -w '%{http_code}' -X POST http://127.0.0.1:<port>/mcp -H 'authorization: Bearer nope' -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":1,"method":"initialize","params":{"protocolVersion":"2025-03-26","capabilities":{"clientInfo":{"name":"qa","version":"0"}}}}'	401; log line outcome=bad_token	200		
T-MCP-04	Non-loopback Origin (webhook analogue)	curl -s -o /dev/null -w '%{http_code}' -X POST http://127.0.0.1:<port>/mcp -H 'origin: https://evil.example.com' -H 'authorization: Bearer <TOKEN>' -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":1,"method":"initialize","params":{"protocolVersion":"2025-03-26","capabilities":{"clientInfo":{"name":"qa","version":"0"}}}}'	403; log line outcome=forbidden_origin	200		
T-MCP-05	Origin guard on /health	curl -s -o /dev/null -w '%{http_code}' http://127.0.0.1:<port>/health -H 'origin: https://evil.example.com'	403	200		
T-MCP-06	Login	curl -s -i -X POST http://127.0.0.1:<port>/mcp -H 'authorization: Bearer <TOKEN>' -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":1,"method":"initialize","params":{"protocolVersion":"2025-03-26","capabilities":{"clientInfo":{"name":"qa","version":"0"}}}}'	200; response header mcp-session-id present	401		
T-MCP-07	Resource denied by allowlist (server enabled with only get_active_flight ticked)	after T-MCP-06 and notifications/initialized: curl -s -X POST http://127.0.0.1:<port>/mcp -H 'authorization: Bearer <TOKEN>' -H 'mcp-session-id: <SID>' -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":5,"method":"resources/read","params":{"uri":"packetbench://memory/patterns"}}'	JSON-RPC error 'resource is not permitted by this server's tool allowlist'	a result with 'patterns'		
T-MCP-08	Authenticated write (Allow writes ON, a Flight selected)	same session: -d '{"jsonrpc":"2.0","id":6,"method":"tools/call","params":{"name":"append_handoff","arguments":{"flightId":"<flight_id from get_active_flight>","summary":"qa note"}}}'	'Posted to the flight timeline.; Flight Deck timeline shows actor mcp	'writes are disabled; enable them in PacketBench's MCP Provider settings' (means Allow writes is off = documented failure path)		
T-MCP-09	Bad flight id	same as T-MCP-08 with flightId 'nope'	JSON-RPC error 'unknown flightId'	success		
T-MCP-10	Webhooks	n/a - PacketBench has no inbound webhooks (audit section 3)	record N/A	-		

Paid outbound calls (every LLM spend path)

ID	Path	Steps (real values)	Expected	Failure signature	[]	P/F
T-PAY-01	Anthropic in-process (Claude (API) row)	Settings > Providers > API Keys: anthropic key set. Start a conversation, send 'say hi'.	log: packetbench::egress service=anthropic 'LLM request' then 'LLM response' status=200; usage.jsonl gains a row	'No API key configured for anthropic. Set one in Settings > API Keys.' (key missing) or status=401		
T-PAY-02	OpenAI-compatible (OpenAI / MiniMax / OpenRouter / Ollama / Custom rows)	Same with the row's key. For Ollama no key.	log: service=openai-compat base_url=<url> 'LLM response' status=200	status=401/403 or 'Ollama not reachable at http://localhost:11434'		
T-PAY-03	Sidecar rows (Claude Agent SDK (API), OpenAI Agents SDK (API))	Start a conversation on each row.	Sidecar status chip 'ready'; turn completes; usage row written	'Sidecar crashed and could not restart' -> restart app		
T-PAY-04	Cost guardrail hard stop	Settings > Agents > Budget Guardrails: Daily cap \$ = 0.01, Hard stop at % = 100. Start a new conversation after spend exceeds it.	Launch refused with the guardrail dialog (assertCostGuardrailsAllowLaunch)	conversation starts anyway		
T-PAY-05	Aux LLM features are NOT guardrail-checked (known gap)	With the cap from T-PAY-04 still exceeded, use Side chat or GitHub > AI PR description.	Expected today: the call proceeds (documented gap, audit section 3 'Rate limiting')	record actual; not a regression		

ID	Path	Steps (real values)	Expected	Failure signature	[]	P/F
T-PAY-06	Custom endpoint over public http refused	Settings > Providers > Provider Endpoints: custom endpoint http://lm.example.com/v1	'Custom endpoint URL must use https:// - plain http:// is only allowed for localhost, private-network, or .local/.lan/.internal hosts...'	'Saved.'		
T-PAY-07	PacketAgent	Settings > PacketAgent: endpoint https://agent.example.test, token set; press the health probe in the card	log: service=packetagent operation=health status=<code>	'PacketAgent requires HTTPS; HTTP is allowed only for a loopback endpoint.' when http:// is entered		

Background jobs

ID	Job	Steps	Expected	Failure signature	[]	P/F
T-JOB-01	Sidecar restart cap	taskkill /IM node.exe /F three times within 60 s while a sidecar conversation is open	Chip cycles restarting (1/3..3/3) then 'Sidecar crashed and could not restart'	no chip change; conversation hangs silently		
T-JOB-02	PTY orphan reap	Open a terminal pane running `claude`; taskkill /IM packetbench.exe /F; relaunch	Log line from core::pty::reap_orphaned_pty_children; no stray claude.exe in Task Manager	claude.exe survives		
T-JOB-03	PacketAgent SSE reconnect	Start a stream (Flight with a PacketAgent deployment); disconnect network 10 s	packet-agent:stream-status 'reconnecting' then 'connected'; cursor preserved	state 'error' with no retry		
T-JOB-04	Auth credential watcher	Run `claude login` in a terminal pane	AuthBadge flips to ready without reopening the picker (provider-auth:changed)	badge stale until restart		
T-JOB-05	Flight recovery on startup	Launch an attempt, force-kill the app, relaunch	Attempt shows Failed; worktree swept (log 'sweep_interrupted_attempts')	attempt stuck Running		

Secret loading (every keyring account and file)

ID	Secret	Steps	Expected	Failure signature	[]	P/F
T-SEC-01	api-key-anthropic / openai / minimax / openrouter	Delete the key in Settings > Providers > API Keys ('Delete API key?'), start a conversation	'No API key configured for <provider>. Set one in Settings > API Keys.'; log outcome=missing	turn starts		
T-SEC-02	github-token	Settings > GitHub > Remove git host, then open GitHub view	'Sign in with GitHub, or add a token with repo scope' prompt; cmdkey /list no longer lists github-token.packetbench	token still listed		
T-SEC-03	git-host-token-<id>	Add a Gitea host (https), then Remove	cmdkey /list shows git-host-token-<id>.packetbench before, not after	entry remains		
T-SEC-04	ssh-<serverId>	Settings > Servers > Add password-auth server, Save; Delete remote host	entry ssh-<serverId>.packetbench appears then disappears	entry remains		
T-SEC-05	packet-agent-token	Settings > PacketAgent: save token; 'Remove stored token'	'PacketAgent token removed from the credential store.'	requests still authenticate		
T-SEC-06	Boot keyring probe	Start the app; Select-String packetbench::boot	'OS credential store is reachable'	'OS credential store failed a read ...'		
T-SEC-07	Plaintext token file is inert	Create %USERPROFILE%\packetbench\github-token containing 'x'; ask an agent to use gh_list_issues with the GitHub connection removed	'GitHub token not configured. Run `github_set_token` first.'	the file's value is used (P06 not applied)		
T-SEC-08	Trust file	Delete %USERPROFILE%\packetbench\trusted-projects.json; start a conversation in a repo with .claude/settings.json hooks	hooks do not run; log 'project hooks ignored: project is not in the trusted-projects list'	hook side effect observed		
T-SEC-09	Trust file malformed	Write '{ not json' to trusted-projects.json; repeat T-SEC-08	'trusted-projects file is not valid JSON; treating every project as untrusted'	hook runs		

Patch verification (one test per patch, keyed to docs/audit/patches)

Patch	Manual test (real values)	Expected	Nothing adjacent broke	Automated / log line	[]	P/F
P01	Untrusted repo: add .claude/settings.json with <code>{ "hooks": [{"event": "SessionStart", "command": "echo HOOKRAN > %TEMP%\hook.txt"}] }</code> ; start a conversation; then add the repo to trusted-projects.json and start another	First: no hook.txt, log 'project hooks ignored'. Second: hook.txt exists	Adjacent: global ~/.claude/settings.json hooks still run in both cases	cargo test --lib -- project_trust merge_mcp_entries_for_sidecar_drops		
P02	New conversation, no posture chosen; send 'run `dir` via bash'	Chip 'Manual'; Allow once / Always allow / Deny prompt appears	Adjacent: choosing Default (auto) from the chip runs bash unprompted; Plan blocks bash entirely	cargo test --lib -- permission_n_mode_defaults_to_askin_g; vitest agentModeChipUtils.test.ts		
P03	Ask: 'use spawn_subagent to run `whoami` with bash'	Sub-agent result contains 'Error: tool 'bash' is not available to this sub-agent.'; log 'sub-agent requested a tool outside its allowlist; refused'	Adjacent: spawn_subagent can still read_file/grep	cargo test --lib -- subagent_allowlist denied_tools_stay custom_agents_cannot		
P03b	In Manual mode ask the agent to create a pull request	Permission prompt for create_pull_request before any git push	Adjacent: Deny refuses it; plan mode disables it	cargo test --lib -- create_pull_request_is_a_risky_tool		
P04	mklink /D <workspace>\link C:\Users\<you>\.ssh (needs Developer Mode or admin); ask the agent to grep for 'Host'	No lines from the link; only workspace files	Adjacent: grep still finds matches in real subdirectories	cargo test --lib -- grep_does_not_follow_symlinks		
P05	Settings > GitHub > Connect a git host > Gitea, http://gitea.example.com	'Gitea base URL must use https:// ...'; also http://gitea.local and http://192.168.1.5:3000 are accepted	Adjacent: Ollama base URL http://<lan-ip>:11434 still accepted (no secret)	cargo test --lib -- tls_guard		
P06	T-SEC-07	as T-SEC-07	Adjacent: keyring token still works for gh_list_issues	grep -n 'github-token' src-tauri/src/core/tool_github.rs shows keyring reads only		
P07	T-MCP-01, T-MCP-05, T-MCP-07	as those rows	Adjacent: with no allowlist every resource still reads; tools/call still works	node smoke-test.mjs (fallback runs the transport tests)		
P08	In devtools: await window.__TAURI_INTERNALS.__.invoke('ssh_exec', {commandArgs: ['-o', 'ProxyCommand=calc.exe', 'u@h'], password:null})	rejects with exactly "ssh option 'ProxyCommand=calc.exe' is not permitted"; calc does not open	Adjacent: Settings > Servers connect to a real key-auth host still works	cargo test --lib -- ssh_exec_refuses_local_execution_options		
P09	Set \$env:PACKETBENCH_SIDEDECAR_PTH='x' and launch	log 'PACKETBENCH_SIDEDECAR_PTH is set but is not a variable PacketBench reads (typo? ...)' and 'boot check done issues=1'	Adjacent: app starts normally	cargo test --lib -- boot_check		
P10	Right-click a path in a conversation > Open in VS Code	VS Code opens the file	Adjacent: 'Show in Explorer' still fails with a console warn (known, H07)	grep plugins src-tauri/tauri.conf.json		
P11	Is -la .dockerignore	file absent	Adjacent: nothing depends on it	git log --oneline -1 -- .dockerignore		
P12	pnpm tauri build from a non-interactive shell	prune-sidecar prints 'pruned node_modules' and the build reaches the bundler	Adjacent: pnpm lint and pnpm build still work afterwards - root devDeps intact	grep -n ignore-workspace scripts/prune-sidecar.js		

Unresolved experiments (audit section 7)

ID	Question	Procedure (cold)	How to read the result	[]	P/F
U01	Windows password-auth SSH	Settings > Servers > Add: Host <a linux host allowing password auth>, Authentication: password, Save, then Connect. Watch the 'Connecting via SSH...' step.	Connected within 8 s = stdin path works (F12 void). Timeout/'Permission denied' = stdin path dead -> handoff Task 3.		
U02	xterm link handler	SETTLED 2026-09-05: window.open() returns null in this webview, so the add-on logs 'Opening link blocked as opener could not be cleared' and does nothing when a terminal URL is clicked.	Settled - benign, no action. Re-check only if xterm or the webview is upgraded.		
U03	Key inheritance by MCP stdio servers under the Agent SDK	SETTLED 2026-09-05: the MCP SDK spawns stdio servers with a fixed 12-name env allowlist that excludes ANTHROPIC_API_KEY; a probe child received 15 vars, none of them the key or a sentinel.	Settled - F11 refuted, no leak. Re-run after an MCP SDK bump.		
U04	Sidecar-only audit	cd agent-sidecar && pnpm --ignore-workspace audit --json	SETTLED 2026-09-05: 37 advisories (10 high, 24 moderate, 3 low, 0 critical), almost all in the MCP SDK HTTP-server half the sidecar never starts. Recorded in the dependency snapshot.		
U05	Packaged shell open scope	SETTLED 2026-09-05. Dev build: the scope rejected a bare path and file:// quoting the P10 regex, and allowed vscode://file/ (VS Code opened) and https:// (Edge opened). Packaged build: the release exe contains the scope regex once, byte-identical to tauri.conf.json line 14; the 2026-08-30 release exe contains it zero times. Installed build: the conversation menu's Open in VS Code launched VS Code cold onto the conversation project, and Open project folder in OS (a bare path) opened nothing.	Settled both ways. To re-check after a config change: strings the built exe for vscode://file/ before shipping, then click both menu items - Open in VS Code must work and the bare-path one must not.		
U06	Vitest stability	pnpm test twice on an idle machine	Both runs 2743 passed; any single non-reproducing failure is CPU contention.		
U07	Real-hardware acceptance	dev/acceptance.md sections 3-5 with the headset	Rows ticked in that file.		

Ops pages (from docs/runbooks.md)

Task	Command	Success looks like	[]	P/F
Build installers	export PATH="/c/Users/ianwalmsley/.rustup/toolchains/stable-x86_64-pc-windows-msvc/bin:\$PATH" pnpm gates:full pnpm run release:gate pnpm tauri build pnpm run release:readiness --skip-gates pnpm sidecar:install	C:/Users/ianwalmsley/packetbench-build/release/bundle/nsis/PackageBench_<version>_x64-setup.exe exists		
Roll back app	Windows Settings > Apps > PacketBench > Uninstall; run the previous -setup.exe from the bundle dir	Version shown in Settings > Advanced matches the previous release		
Roll back a patch	git apply -R docs/audit/patches/<name>.diff (revert P09 before P01)	cargo test --lib passes		
Restart app	taskkill /IM packetbench.exe /F	Next launch logs boot check done and reaps orphan PTYs		
Restart MCP server	Settings > MCP > MCP Provider > Enable MCP Provider off/on	New bearer token shown; /health answers		
Tail logs	Get-Content -Wait -Tail 50 "\$env:LOCALAPPDATA\PacketBench\logs\packetbench.log.\$(Get-Date -Format yyyy-MM-dd)"	lines stream		
Security lines only	Select-String -Path "\$env:LOCALAPPDATA\PacketBench\logs\packetbench.log.*" -Pattern 'packetbench::(auth egress trust boot)'	matches listed		
List secrets	cmdkey /list findstr packetbench	targets <account>.packetbench listed		
Rotate API key	Settings > Providers > API Keys: paste new key, save (old one overwritten in api-key-<provider>.packetbench)	next turn logs outcome=found		
Rotate git-host token	Settings > GitHub > host row > Edit > paste token > save (live-probed first)	'Rotated the token for git-host connection' in log		
Rotate PacketAgent token	Settings > PacketAgent > Remove stored token, then save the new one	'PacketAgent token removed from the credential store.' then requests succeed		
Restore state	taskkill /IM packetbench.exe /F; Copy-Item "\$env:USERPROFILE\.packetbench\state.v1.json.bak" "\$env:USERPROFILE\.packetbench\state.v1.json" -Force	app launches with the previous flights/workspaces		
Full backup	robocopy "\$env:USERPROFILE\.packetbench" "D:\backups\packetbench-<date>" /E /XD pty-transcripts	folder copied; secrets must be re-entered on restore		
Health	curl -s http://127.0.0.1:<port>/health	{"ok":true,"app":"PacketBench",...}		

Bug log

[illegible]

Day-31 backlog (fill on the first day access returns)

Seed items, from docs/handoff.md section 4: (1) trust-list UI, (2) cargo update -p h2 -p rustls-webpki -p quinn-proto, (3) Windows askpass for password SSH, (4) reveal_in_file_manager command, (5) restart_sidecar + turn-level cost guardrail.

[illegible]