

PacketBench QA Workbook

Repository	packetloss404/PackageBench
Commit reviewed by the audit	2f4a10c384508af75a792604fff91b55a16dee26
Commit this workbook was built from	835e1d45094f45e12aa596fa71a408d66b379483
Date built	2026-09-05
Run it locally (exact command)	pnpm install && pnpm tauri dev
Then run the gates	pnpm gates:fast (format, lint, typecheck, vitest) and cd src-tauri && cargo test --lib
Smoke test	node smoke-test.mjs (live mode: set PACKETBENCH_MCP_URL and PACKETBENCH_MCP_TOKEN from Settings > MCP > MCP Provider)
Exact URL in prod	none (desktop app; no hosted URL). Installed via the NSIS installer PacketBench_<version>_x64-setup.exe. The only HTTP endpoint is the loopback MCP server: http://127.0.0.1:<port>/health
Log file	%LOCALAPPDATA%\PackageBench\logs\packetbench.log.<YYYY-MM-DD>
Data dir	%USERPROFILE%\.\packetbench
Audit report	docs/audit-2026-09-04.md (findings F01-F19, patches P01-P11, unresolved U01-U07)

How to use: every checklist row has an empty checkbox cell (tick when done) and a P/F cell (write P or F). Failure signatures are the literal strings the app or the log prints. Where a browser cannot make the request, the literal curl is given with <TOKEN> as the placeholder for the bearer shown in Settings > MCP > MCP Provider.

Manual IPC calls: run `pnpm tauri dev`, press Ctrl+Shift+I in the app window, and in the devtools console call `await window.\_\_TAURI\_INTERNALS\_\_.invoke('<command>', {<camelCase args>})`. Release builds do not expose devtools; that is expected.

Surface inventory with negative cases

Reprinted from audit deliverable 2 and scanned live from src-tauri/src. Four negative cases per IPC row: UNAUTH = call from outside the webview (there is no path: Tauri IPC is reachable only from the app's own webview; record N/A unless you find one). ROLE = call from the read-only Monitor window (open one via Flight Deck > attempt tile > 'Monitor' or the conversation header menu 'Send to Monitor', then devtools in that window): expected rejection string is exactly "This read-only Monitor cannot invoke that application command." for every command except the five marked 'main, monitor'. ID = substitute a foreign/absent id (session id, flight id, conversation id): expected an error string naming the missing entity (e.g. "PTY session <id> not found", "unknown flightId", "Conversation id cannot traverse paths"). BODY = omit a required argument or send the wrong type: Tauri returns "invalid args `<arg>` for command `<name>`" before the handler runs.

ID	Command	Roles	Mutates / reaches	Location	UNAUTH	ROLE	ID	BODY	[]	P/F
C001	analyze_code_quality	main only	Reads project; may call aux LLM	src-tauri/src/commands/code_quality.rs:330						
C002	archive_project_memory	main only	Archives a note	src-tauri/src/commands/project_memory.rs:917						
C003	ask_agent_chat_stream	main only	Aux LLM stream (spend)	src-tauri/src/commands/insights.rs:72						
C004	ask_side_chat_stream	main only	Aux LLM stream (spend)	src-tauri/src/commands/side_chat.rs:107						
C005	cancel_api_agent_session	main only	Cancels a turn	src-tauri/src/commands/api_agent.rs:1414						
C006	cancel_flight_attempt	main only	Cancels an attempt	src-tauri/src/commands/flight_attempts.rs:1016						
C007	cancel_pending_tools	main only	Denies pending prompts	src-tauri/src/commands/api_agent.rs:1616						
C008	cancel_quality_fix	main only	Cancels a running task	src-tauri/src/commands/code_quality_autofix.rs:554						
C009	cancel_quality_run	main only	Cancels a running task	src-tauri/src/commands/quality_runner.rs:1053						
C010	cancel_recording	main only	Stops capture	src-tauri/src/commands/dictation/audio.rs:814						
C011	cancel_side_chat_stream	main only	Cancels a running task	src-tauri/src/commands/side_chat.rs:304						
C012	change_model	main only	Changes model	src-tauri/src/commands/api_agent.rs:1432						
C013	cleanup_attempt_worktree_ssh	main only	Removes remote worktree over SSH	src-tauri/src/commands/flight_attempts.rs:1092						
C014	cleanup_flight_integration_worktree	main only	Removes local integration worktree	src-tauri/src/commands/flight_attempts.rs:1058						
C015	clear_dictation_history	main only	Deletes SQLite rows	src-tauri/src/commands/dictation/history.rs:312						
C016	cli_launch_diagnostics	main only	Resolves launch path	src-tauri/src/commands/agent.rs:277						
C017	clone_repo_remote	main only	git clone over SSH (URL/branch validated)	src-tauri/src/commands/git.rs:930						
C018	close_api_agent_session	main only	Ends a session	src-tauri/src/commands/api_agent.rs:1719						
C019	close_monitor_window	main, monitor	Closes monitor window	src-tauri/src/commands/monitor_windows.rs:162						
C020	code_quality_ai_explain	main only	Aux LLM (spend)	src-tauri/src/commands/code_quality.rs:652						
C021	code_quality_ai_summarize	main only	Aux LLM (spend)	src-tauri/src/commands/code_quality.rs:735						
C022	code_quality_probe_fixers	main only	Probes project (read)	src-tauri/src/commands/code_quality_autofix.rs:254						
C023	code_quality_run_fix	main only	Spawns eslint --fix / prettier / cargo fix / pnpm audit --fix	src-tauri/src/commands/code_quality_autofix.rs:319						
C024	create_conversation_worktree	main only	git worktree add	src-tauri/src/commands/git.rs:393						
C025	create_issue_worktree	main only	git worktree add	src-tauri/src/commands/git.rs:466						
C026	create_project_memory	main only	Writes a note in the project memory dir	src-tauri/src/commands/project_memory.rs:901						
C027	create_pty_session	main only	Spawns allowlisted CLI/shell in a PTY with caller args+env	src-tauri/src/commands/pty.rs:604						
C028	delete_api_key	main only	Keyring delete	src-tauri/src/commands/api_keys.rs:219						
C029	delete_conversation_file	main only	Deletes a conversation file	src-tauri/src/commands/conversations.rs:93						
C030	delete_crash	main only	Deletes a crash log (confined)	src-tauri/src/commands/crashes.rs:88						
C031	delete_dictation_entry	main only	Deletes one row	src-tauri/src/commands/dictation/history.rs:285						
C032	delete_mcp_server	main only	Removes an mcpServers entry	src-tauri/src/commands/mcp.rs:404						
C033	delete_packet_agent_token	main only	Keyring delete	src-tauri/src/commands/packet_agent.rs:247						
C034	delete_ssh_password	main only	Keyring delete	src-tauri/src/commands/ssh_keys.rs:220						
C035	delete_whisper_model	main only	Deletes a model file	src-tauri/src/commands/dictation/models.rs:539						
C036	deliver_dictation_text	main only	Sets clipboard; optional Ctrl+V into foreground app	src-tauri/src/commands/dictation/delivery.rs:31						
C037	detect_agent	main only	Spawns <cli> --version	src-tauri/src/commands/agent.rs:142						
C038	detect_cli_catalog	main only	Spawns each CLI --version	src-tauri/src/commands/agent.rs:151						
C039	detect_quality_checks	main only	None (read)	src-tauri/src/commands/quality_runner.rs:899						
C040	diagnose_mcp_server	main only	Spawns the configured stdio MCP server	src-tauri/src/commands/mcp.rs:224						
C041	download_whisper_model	main only	Downloads pinned-SHA256 model from huggingface.co	src-tauri/src/commands/dictation/models.rs:278						
C042	export_conversation_markdown	main only	None (pure render)	src-tauri/src/commands/conversations.rs:107						
C043	extract_patterns	main only	Aux LLM (spend)	src-tauri/src/commands/memory.rs:185						

ID	Command	Roles	Mutates / reaches	Location	UNAUT H	ROLE	ID	BODY	[]	P/F
C044	focus_monitor_route_in_main	main, monitor	Focuses main window	src-tauri/src/commands/monitor_windows.rs:185						
C045	get_api_key_exists	main only	Keyring read	src-tauri/src/commands/api_keys.rs:192						
C046	get_app_known_hosts_path	main only	None (read)	src-tauri/src/commands/pty.rs:1304						
C047	get_aux_provider_options	main only	None (read)	src-tauri/src/commands/aux_routing.rs:106						
C048	get_aux_route_resolutions	main only	None (read)	src-tauri/src/commands/aux_routing.rs:72						
C049	get_custom_compat_base_url	main only	None (read)	src-tauri/src/commands/custom_compat.rs:11						
C050	get_custom_compat_models	main only	None (read)	src-tauri/src/commands/custom_compat.rs:31						
C051	get_cwd	main only	None	src-tauri/src/commands/fs.rs:23						
C052	get_dictation_analytics	main only	None (read)	src-tauri/src/commands/dictation/analytics.rs:674						
C053	get_dictation_history	main only	None (read)	src-tauri/src/commands/dictation/history.rs:214						
C054	get_dictation_settings	main only	None (read)	src-tauri/src/commands/dictation/config.rs:110						
C055	get_file_head_content	main only	None (read)	src-tauri/src/commands/git.rs:221						
C056	get_git_branch	main only	None (read)	src-tauri/src/commands/git.rs:9						
C057	get_git_branch_remote	main only	None (read)	src-tauri/src/commands/git.rs:542						
C058	get_git_review_evidence	main only	None (read)	src-tauri/src/commands/git.rs:674						
C059	get_git_status	main only	None (read)	src-tauri/src/commands/git.rs:19						
C060	get_git_status_remote	main only	None (read)	src-tauri/src/commands/git.rs:557						
C061	get_minimax_base_url	main only	None (read)	src-tauri/src/commands/minimax.rs:14						
C062	get_monitor_window_route	main, monitor	Read	src-tauri/src/commands/monitor_windows.rs:146						
C063	get_ollama_base_url	main only	None (read)	src-tauri/src/commands/ollama.rs:87						
C064	get_ollama_runtime_options	main only	None (read)	src-tauri/src/commands/ollama.rs:131						
C065	get_packet_agent_token_exists	main only	Keyring read	src-tauri/src/commands/packet_agent.rs:238						
C066	get_provider_auth_status	main only	Reads CLI credential files	src-tauri/src/commands/provider_auth.rs:463						
C067	get_provider_auth_status_for_dir	main only	Reads credential files in a dir	src-tauri/src/commands/provider_auth.rs:563						
C068	get_provider_launch_stats	main only	None (read)	src-tauri/src/commands/provider_stats.rs:172						
C069	get_sidecar_status	main only	None (read)	src-tauri/src/commands/agent_sidecar/mod.rs:206						
C070	get_ssh_password_exists	main only	Keyring read	src-tauri/src/commands/ssh_keys.rs:167						
C071	git_commit	main only	git commit (staged only)	src-tauri/src/commands/git.rs:234						
C072	git_commit_remote	main only	git commit over SSH	src-tauri/src/commands/git.rs:993						
C073	git_create_branch	main only	git branch (name validated)	src-tauri/src/commands/git.rs:296						
C074	git_create_branch_remote	main only	git branch over SSH	src-tauri/src/commands/git.rs:1068						
C075	git_diff_file_remote	main only	git diff over SSH (read)	src-tauri/src/commands/git.rs:1023						
C076	git_get_origin_url	main only	Read	src-tauri/src/commands/git.rs:365						
C077	git_host_add_connection	main only	Writes git-hosts.json + keyring token (P05 https unless local)	src-tauri/src/commands/github.rs:942						
C078	git_host_has_token	main only	Read	src-tauri/src/commands/github.rs:1059						
C079	git_host_list_connections	main only	Read	src-tauri/src/commands/github.rs:872						
C080	git_host_probe_credential	main only	HTTPS to pasted instance URL with pasted token (P05)	src-tauri/src/commands/git_host_probe.rs:348						
C081	git_host_remove_connection	main only	Deletes connection + token	src-tauri/src/commands/github.rs:1004						
C082	git_host_set_active	main only	Switches active host	src-tauri/src/commands/github.rs:379						
C083	git_host_set_token	main only	Keyring rewrite	src-tauri/src/commands/github.rs:1041						
C084	git_host_update_connection	main only	Rename/rotate after live probe	src-tauri/src/commands/github.rs:1312						
C085	git_pull	main only	git pull	src-tauri/src/commands/git.rs:286						
C086	git_pull_remote	main only	git pull over SSH	src-tauri/src/commands/git.rs:1055						
C087	git_push	main only	git push	src-tauri/src/commands/git.rs:276						
C088	git_push_branch	main only	git push -u origin <branch> [--force-with-lease]	src-tauri/src/commands/git.rs:346						
C089	git_push_remote	main only	git push over SSH	src-tauri/src/commands/git.rs:1042						
C090	git_safety_check	main only	Read	src-tauri/src/commands/git.rs:375						
C091	git_stage_files	main only	git add --	src-tauri/src/commands/git.rs:314						
C092	git_stage_files_remote	main only	git add over SSH	src-tauri/src/commands/git.rs:958						
C093	git_unstage_files	main only	git restore --staged --	src-tauri/src/commands/git.rs:329						
C094	git_unstage_files_remote	main only	git restore over SSH	src-tauri/src/commands/git.rs:976						
C095	github_ai_catch_up	main only	GitHub read + aux LLM (spend)	src-tauri/src/commands/github.rs:2869						
C096	github_ai_pr_description	main only	GitHub read + aux LLM (spend)	src-tauri/src/commands/github.rs:2242						
C097	github_ai_pr_review	main only	GitHub read + aux LLM (spend)	src-tauri/src/commands/github.rs:2362						
C098	github_ai_triage	main only	GitHub read + aux LLM (spend)	src-tauri/src/commands/github.rs:3126						
C099	github_clear_token	main only	Keyring delete	src-tauri/src/commands/github.rs:525						
C100	github_close_issue	main only	Mutates remote repo via git-host API (close issue)	src-tauri/src/commands/github.rs:1767						
C101	github_close_pr	main only	Mutates remote repo via git-host API (close pr)	src-tauri/src/commands/github.rs:3416						
C102	github_convert_pr_to_draft	main only	Mutates remote repo via git-host API (convert pr to draft)	src-tauri/src/commands/github.rs:3440						

ID	Command	Roles	Mutates / reaches	Location	UNAUTH	ROLE	ID	BODY	[]	P/F
C103	github_create_issue	main only	Mutates remote repo via git-host API (create issue)	src-tauri/src/commands/github.rs:1499						
C104	github_create_pr	main only	Mutates remote repo via git-host API (create pr)	src-tauri/src/commands/github.rs:1561						
C105	github_create_repo_milestone	main only	Mutates remote repo via git-host API (create repo milestone)	src-tauri/src/commands/github.rs:1932						
C106	github_device_flow_commit	main only	Keyring write	src-tauri/src/commands/github.rs:837						
C107	github_device_flow_discard	main only	Drops parked token	src-tauri/src/commands/github.rs:854						
C108	github_device_flow_poll	main only	Polls github.com; parks token	src-tauri/src/commands/github.rs:751						
C109	github_device_flow_probe_pending	main only	Probes parked token	src-tauri/src/commands/github.rs:819						
C110	github_device_flow_start	main only	github.com device endpoint (needs PACKETBENCH_GITHUB_CLIENT_ID)	src-tauri/src/commands/github.rs:570						
C111	github_get_authenticated_user	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1400						
C112	github_get_issue	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1485						
C113	github_get_pr_checks	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:3619						
C114	github_get_pr_diff	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1602						
C115	github_has_token	main only	Read	src-tauri/src/commands/github.rs:535						
C116	github_investigate_issue	main only	GitHub read + aux LLM (spend)	src-tauri/src/commands/github.rs:2051						
C117	github_list_branches	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:2473						
C118	github_list_repo_comments	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1687						
C119	github_list_issues	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1448						
C120	github_list_issues_page	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1975						
C121	github_list_notifications	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:4259						
C122	github_list_pr_review_comments	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:3991						
C123	github_list_pr_reviews	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:3962						
C124	github_list_prs	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1586						
C125	github_list_prs_page	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:2018						
C126	github_list_releases	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1432						
C127	github_list_repo_assignable_users	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1959						
C128	github_list_repo_labels	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1900						
C129	github_list_repo_milestones	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1916						
C130	github_list_repos	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:1379						
C131	github_list_repos_page	main only	GitHub/Gitea read with keyring token	src-tauri/src/commands/github.rs:2036						
C132	github_mark_notification_read	main only	PATCH notification thread	src-tauri/src/commands/github.rs:4286						
C133	github_merge_pr	main only	Mutates remote repo via git-host API (merge pr)	src-tauri/src/commands/github.rs:3326						
C134	github_oauth_configured	main only	Read	src-tauri/src/commands/github.rs:616						
C135	github_post_issue_comment	main only	Mutates remote repo via git-host API (post issue comment)	src-tauri/src/commands/github.rs:1710						
C136	github_post_pr_review_comment	main only	Mutates remote repo via git-host API (post pr review comment)	src-tauri/src/commands/github.rs:4024						
C137	github_reopen_issue	main only	Mutates remote repo via git-host API (reopen issue)	src-tauri/src/commands/github.rs:1780						
C138	github_reopen_pr	main only	Mutates remote repo via git-host API (reopen pr)	src-tauri/src/commands/github.rs:3427						
C139	github_reply_to_pr_review_comment	main only	Mutates remote repo via git-host API (reply to pr review comment)	src-tauri/src/commands/github.rs:4094						
C140	github_set_issue_assignees	main only	Mutates remote repo via git-host API (set issue assignees)	src-tauri/src/commands/github.rs:1793						
C141	github_set_issue_labels	main only	Mutates remote repo via git-host API (set issue labels)	src-tauri/src/commands/github.rs:1815						
C142	github_set_issue_milestone	main only	Mutates remote repo via git-host API (set issue milestone)	src-tauri/src/commands/github.rs:1886						
C143	github_set_pr_labels	main only	Mutates remote repo via git-host API (set pr labels)	src-tauri/src/commands/github.rs:2550						
C144	github_set_pr_milestone	main only	Mutates remote repo via git-host API (set pr milestone)	src-tauri/src/commands/github.rs:2602						
C145	github_set_pr_reviewers	main only	Mutates remote repo via git-host API (set pr reviewers)	src-tauri/src/commands/github.rs:2516						
C146	github_set_token	main only	Probes GitHub then keyring write github-token	src-tauri/src/commands/github.rs:507						
C147	github_update_issue	main only	Mutates remote repo via git-host API (update issue)	src-tauri/src/commands/github.rs:1530						
C148	inspect_cli_launch	main only	Resolves launch path	src-tauri/src/commands/agent.rs:244						
C149	inspect_packetcode_installation	main only	Spawns packetcode --version	src-tauri/src/commands/agent.rs:318						
C150	integrate_flight_attempt	main only	Merges attempt into integration	src-tauri/src/commands/git.rs:836						
C151	issues_extract_from_spec	main only	Aux LLM (spend)	src-tauri/src/commands/issues.rs:127						
C152	kill_pty	main only	Kills a PTY process tree	src-tauri/src/commands/pty.rs:950						
C153	kill_pty_and_wait	main only	Kills a PTY tree and waits	src-tauri/src/commands/pty.rs:980						
C154	land_flight_integration	main only	Merges integration into root	src-tauri/src/commands/git.rs:881						
C155	launch_flight_async	main only	Creates worktrees (local/SSH), starts agent sessions (spend)	src-tauri/src/commands/flight_attempts.rs:625						
C156	list_audio_devices	main only	Read	src-tauri/src/commands/dictation/audio.rs:160						
C157	list_crashes	main only	None (read)	src-tauri/src/commands/crashes.rs:44						
C158	list_directory	main only	Read inside workspace	src-tauri/src/commands/fs.rs:44						
C159	list_ollama_models	main only	GET Ollama base URL (no secret)	src-tauri/src/commands/ollama.rs:163						

ID	Command	Roles	Mutates / reaches	Location	UNAUT H	ROLE	ID	BODY	[]	P/F
C160	list_project_files	main only	Read	src-tauri/src/commands/fs.rs:375						
C161	list_project_memory	main only	Read	src-tauri/src/commands/project_memory.rs:896						
C162	list_provider_models	main only	GET provider catalogs with keyring key	src-tauri/src/commands/provider_models.rs:760						
C163	list_pty_sessions	main only	None (read)	src-tauri/src/commands/pty.rs:972						
C164	list_skills	main only	None (read)	src-tauri/src/commands/skills.rs:164						
C165	list_slash_commands	main only	None (read)	src-tauri/src/commands/slash_commands.rs:111						
C166	list_subdirectories	main only	Read any absolute dir	src-tauri/src/commands/fs.rs:160						
C167	list_whisper_models	main only	Read	src-tauri/src/commands/dictation/models.rs:241						
C168	list_wsl_distributions	main only	Spawns wsl.exe --list	src-tauri/src/commands/pty.rs:301						
C169	load_conversations	main, monitor	None (read)	src-tauri/src/commands/conversations.rs:53						
C170	load_persisted_state	main, monitor	None (read)	src-tauri/src/commands/state.rs:12						
C171	load_webview_storage_mirror	main only	Read	src-tauri/src/commands/webview_storage_mirror.rs:79						
C172	mark_attempt_status	main only	Rewrites attempt status	src-tauri/src/commands/flight_attempts.rs:1230						
C173	mcp_server_available_tools	main only	Read	src-tauri/src/mcp_server/mod.rs:314						
C174	mcp_server_recent_activity	main only	Read	src-tauri/src/mcp_server/mod.rs:297						
C175	mcp_server_start	main only	Binds 127.0.0.1:<port>, mints bearer, serves MCP	src-tauri/src/mcp_server/mod.rs:226						
C176	mcp_server_status	main only	Read (returns token)	src-tauri/src/mcp_server/mod.rs:284						
C177	mcp_server_stop	main only	Stops MCP server	src-tauri/src/mcp_server/mod.rs:271						
C178	merge_conversation_branch	main only	git squash-merge into HEAD	src-tauri/src/commands/git.rs:433						
C179	open_monitor_window	main only	Creates monitor-main window	src-tauri/src/commands/monitor_windows.rs:95						
C180	packet_agent_request	main only	HTTPS to PacketAgent endpoint with keyring bearer; POST/PUT mutate deployments	src-tauri/src/commands/packet_agent.rs:255						
C181	parse_spec_to_flight	main only	Aux LLM (spend)	src-tauri/src/commands/spec.rs:89						
C182	parse_spec_to_tickets	main only	Aux LLM (spend)	src-tauri/src/commands/spec.rs:104						
C183	path_is_dir	main only	Existence probe, any path	src-tauri/src/commands/fs.rs:37						
C184	prepare_flight_integration_branch	main only	Creates integration branch	src-tauri/src/commands/git.rs:800						
C185	probe_packetcode_integration	main only	Spawns packetcode --version / doctor --json	src-tauri/src/commands/agent.rs:362						
C186	probe_terminal_shell	main only	Spawns <shell> --version	src-tauri/src/commands/pty.rs:252						
C187	read_codex_statusline_states	main only	None (read)	src-tauri/src/commands/statusline/codex.rs:257						
C188	read_crash	main only	Read (confined)	src-tauri/src/commands/crashes.rs:82						
C189	read_file_contents	main only	Read inside workspace (2 MB cap)	src-tauri/src/commands/fs.rs:221						
C190	read_file_for_diff	main only	Read (confined)	src-tauri/src/commands/fs.rs:418						
C191	read_mcp_servers	main only	Read both files	src-tauri/src/commands/mcp.rs:364						
C192	read_opencode_statusline_states	main only	None (read)	src-tauri/src/commands/statusline/opencode.rs:23						
C193	read_prompt_history	main only	None (read)	src-tauri/src/commands/history.rs:33						
C194	read_pty_transcript	main only	None (read)	src-tauri/src/commands/pty.rs:1014						
C195	read_statusline_states	main only	None (read)	src-tauri/src/commands/statusline/claude.rs:29						
C196	read_usage_analytics	main only	None (read)	src-tauri/src/commands/analytics.rs:72						
C197	remove_conversation_worktree	main only	git worktree remove	src-tauri/src/commands/git.rs:409						
C198	resize_pty	main only	Resizes a PTY	src-tauri/src/commands/pty.rs:924						
C199	resolve_agents_md	main only	Reads AGENTS.md chain	src-tauri/src/commands/agents_md.rs:12						
C200	respond_edit	main only	Applies/declines a pending edit	src-tauri/src/commands/api_agent.rs:1575						
C201	respond_permission	main only	Resolves a risky-tool prompt	src-tauri/src/commands/api_agent.rs:1507						
C202	retry_last_turn	main only	Re-runs last turn (spend)	src-tauri/src/commands/api_agent.rs:1646						
C203	run_quality_checks	main only	Spawns detected lint/typecheck/test/cargo	src-tauri/src/commands/quality_runner.rs:911						
C204	save_agents_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:55						
C205	save_cli_accounts_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:104						
C206	save_conversation	main only	Writes conversations/<id>.json (id validated)	src-tauri/src/commands/conversations.rs:42						
C207	save_flights_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:50						
C208	save_issues_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:74						
C209	save_memory_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:84						
C210	save_persisted_state	main only	Rewrites state.v1.json (not issues/retros)	src-tauri/src/commands/state.rs:28						
C211	save_servers_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:92						
C212	save_settings_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:60						
C213	save_ui_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:69						
C214	save_webview_storage_mirror	main only	Rewrites webview-storage-mirror.json (8 MB cap)	src-tauri/src/commands/webview_storage_mirror.rs:120						
C215	save_workspaces_slice	main only	Rewrites one slice of state.v1.json	src-tauri/src/commands/state.rs:79						
C216	scan_codebase_memory	main only	Reads project + aux LLM (spend)	src-tauri/src/commands/memory.rs:93						

ID	Command	Roles	Mutates / reaches	Location	UNAUT H	ROLE	ID	BODY	[]	P/F
C217	search_dictation_history	main only	SQLite read	src-tauri/src/commands/dictation/history.rs:252						
C218	seed_cli_account_config_dir	main only	Copies settings.json/config.toml between abs dirs (never credentials)	src-tauri/src/commands/cli_account.rs:90						
C219	send_api_agent_message	main only	Continues a turn (LLM spend)	src-tauri/src/commands/api_agent.rs:1343						
C220	set_api_key	main only	Keyring write api-key-<provider>	src-tauri/src/commands/api_keys.rs:169						
C221	set_approve_writes	main only	Toggles edit gate	src-tauri/src/commands/api_agent.rs:1542						
C222	set_attempt_draft_pr	main only	Records PR URL	src-tauri/src/commands/flight_attempts.rs:1125						
C223	set_attempt_review_gate	main only	Records review verdict	src-tauri/src/commands/flight_attempts.rs:1195						
C224	set_aux_routing_overrides	main only	Updates in-memory routing map	src-tauri/src/commands/aux_routing.rs:50						
C225	set_custom_compat_base_url	main only	Writes provider-settings.v1.json (P05)	src-tauri/src/commands/custom_compat.rs:18						
C226	set_custom_compat_models	main only	Writes model list	src-tauri/src/commands/custom_compat.rs:38						
C227	set_dictation_settings	main only	Writes dictation config	src-tauri/src/commands/dictation/config.rs:156						
C228	set_flight_publish_attempts_as_prs	main only	Flight flag	src-tauri/src/commands/flight_attempts.rs:1158						
C229	set_minimax_base_url	main only	Writes provider-settings.v1.json (P05 https unless local)	src-tauri/src/commands/minimax.rs:19						
C230	set_ollama_base_url	main only	Writes provider-settings.v1.json (http allowed; no secret)	src-tauri/src/commands/ollama.rs:92						
C231	set_ollama_runtime_options	main only	Writes num_ctx/keep_alive	src-tauri/src/commands/ollama.rs:138						
C232	set_packet_agent_token	main only	Keyring write packet-agent-token	src-tauri/src/commands/packet_agent.rs:227						
C233	set_permission_mode	main only	Changes gate posture	src-tauri/src/commands/api_agent.rs:1481						
C234	set_plan_mode	main only	Toggles plan mode	src-tauri/src/commands/api_agent.rs:1455						
C235	set_ssh_password	main only	Keyring write ssh-<serverid>	src-tauri/src/commands/ssh_keys.rs:187						
C236	sign_out_provider	main only	Deletes ~/.claude/.credentials.json or ~/.codex/auth.json	src-tauri/src/commands/provider_auth.rs:436						
C237	ssh_check_remote_path	main only	Spawns ssh to probe a remote path	src-tauri/src/commands/pty.rs:1356						
C238	ssh_exec	main only	Spawns local ssh with caller argv (P08 denylist); password via askpass/stdin	src-tauri/src/commands/pty.rs:1070						
C239	ssh_fetch_fingerprint	main only	Spawns ssh-keyscan + ssh-keygen	src-tauri/src/commands/pty.rs:1153						
C240	ssh_pin_host	main only	Appends to ~/.packetbench/ssh/known_hosts	src-tauri/src/commands/pty.rs:1264						
C241	start_api_agent_session	main only	Starts agent loop: keyring key, gated tools (P02 default ask), MCP, hooks; LLM spend	src-tauri/src/commands/api_agent.rs:1051						
C242	start_packet_agent_stream	main only	Opens SSE stream to PacketAgent (bearer)	src-tauri/src/commands/packet_agent_stream.rs:176						
C243	start_recording	main only	Opens microphone	src-tauri/src/commands/dictation/audio.rs:458						
C244	stop_packet_agent_stream	main only	Stops SSE task	src-tauri/src/commands/packet_agent_stream.rs:220						
C245	stop_recording	main only	Stops capture, runs whisper	src-tauri/src/commands/dictation/audio.rs:855						
C246	summarize_flight	main only	Aux LLM (spend)	src-tauri/src/commands/memory.rs:223						
C247	summarize_session	main only	Aux LLM (spend)	src-tauri/src/commands/memory.rs:164						
C248	test_audio_device	main only	Opens a device	src-tauri/src/commands/dictation/audio.rs:294						
C249	toggle_pinned_pattern	main only	Flips a memory pattern flag	src-tauri/src/commands/memory.rs:278						
C250	update_project_memory	main only	Rewrites a note (revision check)	src-tauri/src/commands/project_memory.rs:909						
C251	watch_project_memory	main only	Starts fs watcher	src-tauri/src/commands/project_memory.rs:974						
C252	write_file_contents	main only	Writes a file inside workspace	src-tauri/src/commands/fs.rs:246						
C253	write_mcp_server	main only	Upserts mcpServers in ~/.claude/settings.json or <project>/mcp.json	src-tauri/src/commands/mcp.rs:381						
C254	write_pty	main only	Writes keystrokes to a PTY (64 KB cap)	src-tauri/src/commands/pty.rs:899						

ID	Route	Auth	Mutates	Location	[]	P/F
N001	GET /health on 127.0.0.1:<port> (MCP server)	any local process; Origin must be absent or loopback	None	src-tauri/src/mcp_server/transport.rs		
N002	POST/GET/DELETE /mcp (MCP Streamable HTTP)	bearer + loopback Origin + Host allowlist	tools M008-M010, M013-M016 mutate (allow_writes only)	src-tauri/src/mcp_server/transport.rs:69-100		
M001-M016	MCP tools ping, get_active_flight, list_runnable_tasks, read_task_details, read_memory_context, search_project_memory, read_project_memory, create/update/archive_project_memory, list_workspaces, read_coordination_inbox, append_handoff, escalate, post_coordination_message, acknowledge_coordination_message	bearer; writes need Allow writes	see audit 2b	src-tauri/src/mcp_server/mod.rs:582-836		

ID	Route	Auth	Mutates	Location	[]	P/F
R001-R002	MCP resources packetbench://project{flights}flights/{id}flights/{id}/tasks{flights/{id}/inbox{issues}reviews{workspace}memory/patterns{memory/project/{ws}}packetcode/health	bearer; gated by the tool allowlist (P07)	packetcode/health spawns a process	src-tauri/src/mcp_server/mod.rs:923-1030		

Shot list

There are no URLs: PacketBench is a desktop window. Each shot names the in-app location, the state to be in, and the one question the shot answers. Dev builds are served from `http://localhost:1420` inside the window (`tauri.conf.json build.devUrl`).


#	Location + state	Question the shot answers	[]	P/F
S1	Agents view, new API conversation in a repo NOT listed in <code>trusted-projects.json</code> ; provider 'Claude (API)'; anthropic key present	Does the mode chip read 'Manual' (not 'Default') on a fresh conversation? (P02)		
S2	Same conversation; ask 'run `git status` with the bash tool'	Does the Allow once / Always allow / Deny prompt appear before anything runs? (P02)		
S3	Log viewer: Select-String <code>packetbench::trust</code> in today's log after S1	Is 'project is not trusted: repo-supplied hooks, .mcp.json servers, and .claude/agents are ignored' present? (P01)		
S4	Settings > MCP > MCP Provider card, Enable MCP Provider on, Allow writes off, all tools ticked	Are port, bearer token, and served tool list visible? (baseline for S5)		
S5	Same card with only <code>get_active_flight</code> ticked, server re-enabled; terminal running the curl from test T-MCP-07	Does <code>resources/read</code> of <code>packetbench://memory/patterns</code> return the allowlist error? (P07)		
S6	Settings > GitHub > Connect a git host wizard, Gitea, instance URL <code>http://gitea.example.com</code> , any token	Is the error 'Instance URL must use https:// ...' shown before any request? (P05)		
S7	Settings > Providers > API Keys card	Are keys shown only as present/absent, never as values? (I8)		
S8	Log viewer: Select-String <code>packetbench::boot</code> on app start	Does 'boot check done' appear with <code>issues=0</code> , and is the trust-file line present? (P09)		

Screenshot slots

S1 - Agents view, new API conversation in a repo NOT listed in trusted-projects.json; provider 'Claude (API)'; anthropic key present
Q: Does the mode chip read 'Manual' (not 'Default') on a fresh conversation? (P02)




S2 - Same conversation; ask 'run `git status` with the bash tool'
Q: Does the Allow once / Always allow / Deny prompt appear before anything runs? (P02)




S3 - Log viewer: Select-String packetbench::trust in today's log after S1

Q: Is 'project is not trusted: repo-supplied hooks, .mcp.json servers, and .claude/agents are ignored' present? (P01)



S4 - Settings > MCP > MCP Provider card, Enable MCP Provider on, Allow writes off, all tools ticked

Q: Are port, bearer token, and served tool list visible? (baseline for S5)



S5 - Same card with only get_active_flight ticked, server re-enabled; terminal running the curl from test T-MCP-07
Q: Does resources/read of packetbench://memory/patterns return the allowlist error? (P07)

S6 - Settings > GitHub > Connect a git host wizard, Gitea, instance URL <http://gitea.example.com>, any token
Q: Is the error 'Instance URL must use https:// ...' shown before any request? (P05)

S7 - Settings > Providers > API Keys card

Q: Are keys shown only as present/absent, never as values? (I8)

S8 - Log viewer: Select-String packetbench::boot on app start

Q: Does 'boot check done' appear with issues=0, and is the trust-file line present? (P09)

Test sheets

MCP server (N001/N002) - every row is a literal curl; replace <port> and <TOKEN> from Settings > MCP > MCP Provider

ID	Case	Command	Expected	Failure signature	[]	P/F
T-MCP-01	Health	curl -s -i http://127.0.0.1:<port>/health	HTTP 200; body {"ok":true,"app":"PacketBench","version":"0.13.2","service":"mcp"}	404 (P07 not applied) or connection refused (server not enabled)		
T-MCP-02	No token	curl -s -o /dev/null -w '%{http_code}' -X POST http://127.0.0.1:<port>/mcp -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":1,"method":"initialize","params":{"protocolVersion":"2025-03-26","capabilities":{"clientInfo":{"name":"qa","version":"0"}}}}'	401	200 = bearer layer missing; log has no 'MCP request rejected: bearer token missing or wrong'		
T-MCP-03	Wrong token	curl -s -o /dev/null -w '%{http_code}' -X POST http://127.0.0.1:<port>/mcp -H 'authorization: Bearer nope' -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":1,"method":"initialize","params":{"protocolVersion":"2025-03-26","capabilities":{"clientInfo":{"name":"qa","version":"0"}}}}'	401; log line outcome=bad_token	200		
T-MCP-04	Non-loopback Origin (webhook analogue)	curl -s -o /dev/null -w '%{http_code}' -X POST http://127.0.0.1:<port>/mcp -H 'origin: https://evil.example.com' -H 'authorization: Bearer <TOKEN>' -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":1,"method":"initialize","params":{"protocolVersion":"2025-03-26","capabilities":{"clientInfo":{"name":"qa","version":"0"}}}}'	403; log line outcome=forbidden_origin	200		
T-MCP-05	Origin guard on /health	curl -s -o /dev/null -w '%{http_code}' http://127.0.0.1:<port>/health -H 'origin: https://evil.example.com'	403	200		
T-MCP-06	Login	curl -s -i -X POST http://127.0.0.1:<port>/mcp -H 'authorization: Bearer <TOKEN>' -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":1,"method":"initialize","params":{"protocolVersion":"2025-03-26","capabilities":{"clientInfo":{"name":"qa","version":"0"}}}}'	200; response header mcp-session-id present	401		
T-MCP-07	Resource denied by allowlist (server enabled with only get_active_flight ticked)	after T-MCP-06 and notifications/initialized: curl -s -X POST http://127.0.0.1:<port>/mcp -H 'authorization: Bearer <TOKEN>' -H 'mcp-session-id: <SID>' -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":5,"method":"resources/read","params":{"uri":"packetbench://memory/patterns"}}'	JSON-RPC error 'resource is not permitted by this server's tool allowlist'	a result with 'patterns'		
T-MCP-08	Authenticated write (Allow writes ON, a Flight selected)	same session: -d '{"jsonrpc":"2.0","id":6,"method":"tools/call","params":{"name":"append_handoff","arguments":{"flightId":"<flight_id from get_active_flight>","summary":"qa note"}}}'	'Posted to the flight timeline.; Flight Deck timeline shows actor mcp	'writes are disabled; enable them in PacketBench's MCP Provider settings' (means Allow writes is off = documented failure path)		
T-MCP-09	Bad flight id	same as T-MCP-08 with flightId 'nope'	JSON-RPC error 'unknown flightId'	success		
T-MCP-10	Webhooks	n/a - PacketBench has no inbound webhooks (audit section 3)	record N/A	-		

Paid outbound calls (every LLM spend path)

ID	Path	Steps (real values)	Expected	Failure signature	[]	P/F
T-PAY-01	Anthropic in-process (Claude (API) row)	Settings > Providers > API Keys: anthropic key set. Start a conversation, send 'say hi'.	log: packetbench::egress service=anthropic 'LLM request' then 'LLM response' status=200; usage.jsonl gains a row	'No API key configured for anthropic. Set one in Settings > API Keys.' (key missing) or status=401		
T-PAY-02	OpenAI-compatible (OpenAI / MiniMax / OpenRouter / Ollama / Custom rows)	Same with the row's key. For Ollama no key.	log: service=openai-compat base_url=<url> 'LLM response' status=200	status=401/403 or 'Ollama not reachable at http://localhost:11434'		
T-PAY-03	Sidecar rows (Claude Agent SDK (API), OpenAI Agents SDK (API))	Start a conversation on each row.	Sidecar status chip 'ready'; turn completes; usage row written	'Sidecar crashed and could not restart' -> restart app		
T-PAY-04	Cost guardrail hard stop	Settings > Agents > Budget Guardrails: Daily cap \$ = 0.01, Hard stop at % = 100. Start a new conversation after spend exceeds it.	Launch refused with the guardrail dialog (assertCostGuardrailsAllowLaunch)	conversation starts anyway		
T-PAY-05	Aux LLM features are NOT guardrail-checked (known gap)	With the cap from T-PAY-04 still exceeded, use Side chat or GitHub > AI PR description.	Expected today: the call proceeds (documented gap, audit section 3 'Rate limiting')	record actual; not a regression		

ID	Path	Steps (real values)	Expected	Failure signature	[]	P/F
T-PAY-06	Custom endpoint over public http refused	Settings > Providers > Provider Endpoints: custom endpoint http://lm.example.com/v1	'Custom endpoint URL must use https:// - plain http:// is only allowed for localhost, private-network, or .local/.lan/.internal hosts...'	'Saved.'		
T-PAY-07	PacketAgent	Settings > PacketAgent: endpoint https://agent.example.test, token set; press the health probe in the card	log: service=packetagent operation=health status=<code>	'PacketAgent requires HTTPS; HTTP is allowed only for a loopback endpoint.' when http:// is entered		

Background jobs

ID	Job	Steps	Expected	Failure signature	[]	P/F
T-JOB-01	Sidecar restart cap	taskkill /IM node.exe /F three times within 60 s while a sidecar conversation is open	Chip cycles restarting (1/3..3/3) then 'Sidecar crashed and could not restart'	no chip change; conversation hangs silently		
T-JOB-02	PTY orphan reap	Open a terminal pane running `claude`; taskkill /IM packetbench.exe /F; relaunch	Log line from core::pty::reap_orphaned_pty_children; no stray claude.exe in Task Manager	claude.exe survives		
T-JOB-03	PacketAgent SSE reconnect	Start a stream (Flight with a PacketAgent deployment); disconnect network 10 s	packet-agent:stream-status 'reconnecting' then 'connected'; cursor preserved	state 'error' with no retry		
T-JOB-04	Auth credential watcher	Run `claude login` in a terminal pane	AuthBadge flips to ready without reopening the picker (provider-auth:changed)	badge stale until restart		
T-JOB-05	Flight recovery on startup	Launch an attempt, force-kill the app, relaunch	Attempt shows Failed; worktree swept (log 'sweep_interrupted_attempts')	attempt stuck Running		

Secret loading (every keyring account and file)

ID	Secret	Steps	Expected	Failure signature	[]	P/F
T-SEC-01	api-key-anthropic / openai / minimax / openrouter	Delete the key in Settings > Providers > API Keys ('Delete API key?'), start a conversation	'No API key configured for <provider>. Set one in Settings > API Keys.'; log outcome=missing	turn starts		
T-SEC-02	github-token	Settings > GitHub > Remove git host, then open GitHub view	'Sign in with GitHub, or add a token with repo scope' prompt; cmdkey /list no longer lists github-token.packetbench	token still listed		
T-SEC-03	git-host-token-<id>	Add a Gitea host (https), then Remove	cmdkey /list shows git-host-token-<id>.packetbench before, not after	entry remains		
T-SEC-04	ssh-<serverId>	Settings > Servers > Add password-auth server, Save; Delete remote host	entry ssh-<serverId>.packetbench appears then disappears	entry remains		
T-SEC-05	packet-agent-token	Settings > PacketAgent: save token; 'Remove stored token'	'PacketAgent token removed from the credential store.'	requests still authenticate		
T-SEC-06	Boot keyring probe	Start the app; Select-String packetbench::boot	'OS credential store is reachable'	'OS credential store failed a read ...'		
T-SEC-07	Plaintext token file is inert	Create %USERPROFILE%\packetbench\github-token containing 'x'; ask an agent to use gh_list_issues with the GitHub connection removed	'GitHub token not configured. Run `github_set_token` first.'	the file's value is used (P06 not applied)		
T-SEC-08	Trust file	Delete %USERPROFILE%\packetbench\trusted-projects.json; start a conversation in a repo with .claude/settings.json hooks	hooks do not run; log 'project hooks ignored: project is not in the trusted-projects list'	hook side effect observed		
T-SEC-09	Trust file malformed	Write '{ not json' to trusted-projects.json; repeat T-SEC-08	'trusted-projects file is not valid JSON; treating every project as untrusted'	hook runs		

Patch verification (one test per patch, keyed to docs/audit/patches)

Patch	Manual test (real values)	Expected	Nothing adjacent broke	Automated / log line	[]	P/F
P01	Untrusted repo: add .claude/settings.json with <code>{ "hooks": [{"event": "SessionStart", "command": "echo HOOKRAN > %TEMP%\hook.txt"}] }</code> ; start a conversation; then add the repo to trusted-projects.json and start another	First: no hook.txt, log 'project hooks ignored'. Second: hook.txt exists	Adjacent: global ~/.claude/settings.json hooks still run in both cases	cargo test --lib -- project_trust merge_mcp_entries_for_sidecar_drops		
P02	New conversation, no posture chosen; send 'run `dir` via bash'	Chip 'Manual'; Allow once / Always allow / Deny prompt appears	Adjacent: choosing Default (auto) from the chip runs bash unprompted; Plan blocks bash entirely	cargo test --lib -- permission_mode_defaults_to_askin_g; vitest agentModeChipUtils.test.ts		
P03	Ask: 'use spawn_subagent to run `whoami` with bash'	Sub-agent result contains 'Error: tool 'bash' is not available to this sub-agent.'; log 'sub-agent requested a tool outside its allowlist; refused'	Adjacent: spawn_subagent can still read_file/grep	cargo test --lib -- subagent_allowlist denied_tools_stay custom_agents_cannot		
P03b	In Manual mode ask the agent to create a pull request	Permission prompt for create_pull_request before any git push	Adjacent: Deny refuses it; plan mode disables it	cargo test --lib -- create_pull_request_is_a_risky_tool		
P04	mklink /D <workspace>\link C:\Users\<you>\.ssh (needs Developer Mode or admin); ask the agent to grep for 'Host'	No lines from the link; only workspace files	Adjacent: grep still finds matches in real subdirectories	cargo test --lib -- grep_does_not_follow_symlinks		
P05	Settings > GitHub > Connect a git host > Gitea, http://gitea.example.com	'Gitea base URL must use https:// ...'; also http://gitea.local and http://192.168.1.5:3000 are accepted	Adjacent: Ollama base URL http://<lan-ip>:11434 still accepted (no secret)	cargo test --lib -- tls_guard		
P06	T-SEC-07	as T-SEC-07	Adjacent: keyring token still works for gh_list_issues	grep -n 'github-token' src-tauri/src/core/tool_github.rs shows keyring reads only		
P07	T-MCP-01, T-MCP-05, T-MCP-07	as those rows	Adjacent: with no allowlist every resource still reads; tools/call still works	node smoke-test.mjs (fallback runs the transport tests)		
P08	In devtools: await window.__TAURI_INTERNALS.__.invoke('ssh_exec', {commandArgs: ['-o', 'ProxyCommand=calc.exe', 'u@h'], password: null})	rejects with exactly "ssh option 'ProxyCommand=calc.exe' is not permitted"; calc does not open	Adjacent: Settings > Servers connect to a real key-auth host still works	cargo test --lib -- ssh_exec_refuses_local_execution_options		
P09	Set \$env:PACKETBENCH_SIDEAR_PTH='x' and launch	log 'PACKETBENCH_SIDEAR_PTH is set but is not a variable PacketBench reads (typo? ...)' and 'boot check done issues=1'	Adjacent: app starts normally	cargo test --lib -- boot_check		
P10	Right-click a path in a conversation > Open in VS Code	VS Code opens the file	Adjacent: 'Show in Explorer' still fails with a console warn (known, H07)	grep plugins src-tauri/tauri.conf.json		
P11	Is -la .dockerignore	file absent	Adjacent: nothing depends on it	git log --oneline -1 -- .dockerignore		

Unresolved experiments (audit section 7)

ID	Question	Procedure (cold)	How to read the result	[]	P/F
U01	Windows password-auth SSH	Settings > Servers > Add: Host <a linux host allowing password auth>, Authentication: password, Save, then Connect. Watch the 'Connecting via SSH...' step.	Connected within 8 s = stdin path works (F12 void). Timeout/'Permission denied' = stdin path dead -> handoff Task 3.		
U02	xterm link handler	Terminal pane: `echo https://example.com`, click the link.	Browser opens = route through shell.open (P10 regex). Nothing = no action.		
U03	Key inheritance by MCP stdio servers under the Agent SDK	Settings > MCP > MCP Hub: add global server 'envdump' command `cmd` args `/c set > %TEMP%\mcp-env.txt`; start one Claude Agent SDK (API) conversation; open the file; delete the server.	ANTHROPIC_API_KEY present = F11 confirmed (SDK limitation). Absent = downgrade F11 to info.		
U04	Sidecar-only audit	cd agent-sidecar && pnpm --ignore-workspace audit --json	0 vulnerabilities expected; otherwise add to the dependency snapshot.		
U05	Packaged shell open scope	pnpm tauri build; install; right-click a path > Open in VS Code	VS Code opens. Failure: RUST_LOG=debug log shows 'open()' command called but the plugin configuration denies calls from JavaScript'.		
U06	Vitest stability	pnpm test twice on an idle machine	Both runs 2743 passed; any single non-reproducing failure is CPU contention.		
U07	Real-hardware acceptance	dev/acceptance.md sections 3-5 with the headset	Rows ticked in that file.		

Ops pages (from docs/runbooks.md)

Task	Command	Success looks like	[]	P/F
Build installers	export PATH="/c/Users/ianwalmsley/.rustup/toolchains/stable-x86_64-pc-windows-msvc/bin:\$PATH" pnpm gates:full pnpm run release:gate pnpm tauri build pnpm run release:readiness --skip-gates pnpm sidecar:install	C:/Users/ianwalmsley/packetbench-build/release/bundle/nsis/PackageBench_<version>_x64-setup.exe exists		
Roll back app	Windows Settings > Apps > PacketBench > Uninstall; run the previous -setup.exe from the bundle dir	Version shown in Settings > Advanced matches the previous release		
Roll back a patch	git apply -R docs/audit/patches/<name>.diff (revert P09 before P01)	cargo test --lib passes		
Restart app	taskkill /IM packetbench.exe /F	Next launch logs boot check done and reaps orphan PTYs		
Restart MCP server	Settings > MCP > MCP Provider > Enable MCP Provider off/on	New bearer token shown; /health answers		
Tail logs	Get-Content -Wait -Tail 50 "\$env:LOCALAPPDATA\PacketBench\logs\packetbench.log.\$(Get-Date -Format yyyy-MM-dd)"	lines stream		
Security lines only	Select-String -Path "\$env:LOCALAPPDATA\PacketBench\logs\packetbench.log.*" -Pattern 'packetbench::(auth egress trust boot)'	matches listed		
List secrets	cmdkey /list findstr packetbench	targets <account>.packetbench listed		
Rotate API key	Settings > Providers > API Keys: paste new key, save (old one overwritten in api-key-<provider>.packetbench)	next turn logs outcome=found		
Rotate git-host token	Settings > GitHub > host row > Edit > paste token > save (live-probed first)	'Rotated the token for git-host connection' in log		
Rotate PacketAgent token	Settings > PacketAgent > Remove stored token, then save the new one	'PacketAgent token removed from the credential store.' then requests succeed		
Restore state	taskkill /IM packetbench.exe /F; Copy-Item "\$env:USERPROFILE\.packetbench\state.v1.json.bak" "\$env:USERPROFILE\.packetbench\state.v1.json" -Force	app launches with the previous flights/workspaces		
Full backup	robocopy "\$env:USERPROFILE\.packetbench" "D:\backups\packetbench-<date>" /E /XD pty-transcripts	folder copied; secrets must be re-entered on restore		
Health	curl -s http://127.0.0.1:<port>/health	{"ok":true,"app":"PacketBench",...}		

Bug log

[illegible]

