

## PacketBench QA Workbook

|                                     |                                                                                                                                                                                            |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Repository                          | packetloss404/PackageBench                                                                                                                                                                 |
| Commit reviewed by the audit        | 2f4a10c384508af75a792604fff91b55a16dee26                                                                                                                                                   |
| Commit this workbook was built from | 16f84db7a7edb1ec98e94d0c2bf75e7ca40305e4                                                                                                                                                   |
| Date built                          | 2026-09-05                                                                                                                                                                                 |
| Run it locally (exact command)      | pnpm install && pnpm tauri dev                                                                                                                                                             |
| Then run the gates                  | pnpm gates:fast (format, lint, typecheck, vitest) and cd src-tauri && cargo test --lib                                                                                                     |
| Smoke test                          | node smoke-test.mjs (live mode: set PACKETBENCH_MCP_URL and PACKETBENCH_MCP_TOKEN from Settings > MCP > MCP Provider)                                                                      |
| Exact URL in prod                   | none (desktop app; no hosted URL). Installed via the NSIS installer PacketBench_<version>_x64-setup.exe. The only HTTP endpoint is the loopback MCP server: http://127.0.0.1:<port>/health |
| Log file                            | %LOCALAPPDATA%\PackageBench\logs\packetbench.log.<YYYY-MM-DD>                                                                                                                              |
| Data dir                            | %USERPROFILE%\.\packetbench                                                                                                                                                                |
| Audit report                        | docs/audit-2026-09-04.md (findings F01-F23, patches P01-P15, unresolved U01-U07)                                                                                                           |

How to use: every checklist row has an empty checkbox cell (tick when done) and a P/F cell (write P or F). Failure signatures are the literal strings the app or the log prints. Where a browser cannot make the request, the literal curl is given with <TOKEN> as the placeholder for the bearer shown in Settings > MCP > MCP Provider.

Manual IPC calls: run `pnpm tauri dev`, press Ctrl+Shift+I in the app window, and in the devtools console call `await window.\_\_TAURI\_INTERNALS\_\_.invoke('<command>', {<camelCase args>})`. Release builds do not expose devtools; that is expected.

## Surface inventory with negative cases

Reprinted from audit deliverable 2 and scanned live from src-tauri/src. Four negative cases per IPC row: UNAUTH = call from outside the webview (there is no path: Tauri IPC is reachable only from the app's own webview; record N/A unless you find one). ROLE = call from the read-only Monitor window (open one via Flight Deck > attempt tile > 'Monitor' or the conversation header menu 'Send to Monitor', then devtools in that window): expected rejection string is exactly "This read-only Monitor cannot invoke that application command." for every command except the five marked 'main, monitor'. ID = substitute a foreign/absent id (session id, flight id, conversation id): expected an error string naming the missing entity (e.g. "PTY session <id> not found", "unknown flightId", "Conversation id cannot traverse paths"). BODY = omit a required argument or send the wrong type: Tauri returns "invalid args `<arg>` for command `<name>`" before the handler runs.

| ID   | Command                             | Roles         | Mutates / reaches                                             | Location                                           | UNAUTH | ROLE | ID | BODY | [] | P/F |
|------|-------------------------------------|---------------|---------------------------------------------------------------|----------------------------------------------------|--------|------|----|------|----|-----|
| C001 | analyze_code_quality                | main only     | Reads project; may call aux LLM                               | src-tauri/src/commands/code_quality.rs:330         |        |      |    |      |    |     |
| C002 | archive_project_memory              | main only     | Archives a note                                               | src-tauri/src/commands/project_memory.rs:917       |        |      |    |      |    |     |
| C003 | ask_agent_chat_stream               | main only     | Aux LLM stream (spend)                                        | src-tauri/src/commands/insights.rs:72              |        |      |    |      |    |     |
| C004 | ask_side_chat_stream                | main only     | Aux LLM stream (spend)                                        | src-tauri/src/commands/side_chat.rs:107            |        |      |    |      |    |     |
| C005 | cancel_api_agent_session            | main only     | Cancels a turn                                                | src-tauri/src/commands/api_agent.rs:1414           |        |      |    |      |    |     |
| C006 | cancel_flight_attempt               | main only     | Cancels an attempt                                            | src-tauri/src/commands/flight_attempts.rs:1016     |        |      |    |      |    |     |
| C007 | cancel_pending_tools                | main only     | Denies pending prompts                                        | src-tauri/src/commands/api_agent.rs:1616           |        |      |    |      |    |     |
| C008 | cancel_quality_fix                  | main only     | Cancels a running task                                        | src-tauri/src/commands/code_quality_autofix.rs:554 |        |      |    |      |    |     |
| C009 | cancel_quality_run                  | main only     | Cancels a running task                                        | src-tauri/src/commands/quality_runner.rs:1053      |        |      |    |      |    |     |
| C010 | cancel_recording                    | main only     | Stops capture                                                 | src-tauri/src/commands/dictation/audio.rs:814      |        |      |    |      |    |     |
| C011 | cancel_side_chat_stream             | main only     | Cancels a running task                                        | src-tauri/src/commands/side_chat.rs:304            |        |      |    |      |    |     |
| C012 | change_model                        | main only     | Changes model                                                 | src-tauri/src/commands/api_agent.rs:1432           |        |      |    |      |    |     |
| C013 | cleanup_attempt_worktree_ssh        | main only     | Removes remote worktree over SSH                              | src-tauri/src/commands/flight_attempts.rs:1092     |        |      |    |      |    |     |
| C014 | cleanup_flight_integration_worktree | main only     | Removes local integration worktree                            | src-tauri/src/commands/flight_attempts.rs:1058     |        |      |    |      |    |     |
| C015 | clear_dictation_history             | main only     | Deletes SQLite rows                                           | src-tauri/src/commands/dictation/history.rs:312    |        |      |    |      |    |     |
| C016 | cli_launch_diagnostics              | main only     | Resolves launch path                                          | src-tauri/src/commands/agent.rs:277                |        |      |    |      |    |     |
| C017 | clone_repo_remote                   | main only     | git clone over SSH (URL/branch validated)                     | src-tauri/src/commands/git.rs:930                  |        |      |    |      |    |     |
| C018 | close_api_agent_session             | main only     | Ends a session                                                | src-tauri/src/commands/api_agent.rs:1719           |        |      |    |      |    |     |
| C019 | close_monitor_window                | main, monitor | Closes monitor window                                         | src-tauri/src/commands/monitor_windows.rs:162      |        |      |    |      |    |     |
| C020 | code_quality_ai_explain             | main only     | Aux LLM (spend)                                               | src-tauri/src/commands/code_quality.rs:652         |        |      |    |      |    |     |
| C021 | code_quality_ai_summarize           | main only     | Aux LLM (spend)                                               | src-tauri/src/commands/code_quality.rs:735         |        |      |    |      |    |     |
| C022 | code_quality_probe_fixers           | main only     | Probes project (read)                                         | src-tauri/src/commands/code_quality_autofix.rs:254 |        |      |    |      |    |     |
| C023 | code_quality_run_fix                | main only     | Spawns eslint --fix / prettier / cargo fix / pnpm audit --fix | src-tauri/src/commands/code_quality_autofix.rs:319 |        |      |    |      |    |     |
| C024 | create_conversation_worktree        | main only     | git worktree add                                              | src-tauri/src/commands/git.rs:393                  |        |      |    |      |    |     |
| C025 | create_issue_worktree               | main only     | git worktree add                                              | src-tauri/src/commands/git.rs:466                  |        |      |    |      |    |     |
| C026 | create_project_memory               | main only     | Writes a note in the project memory dir                       | src-tauri/src/commands/project_memory.rs:901       |        |      |    |      |    |     |
| C027 | create_pty_session                  | main only     | Spawns allowlisted CLI/shell in a PTY with caller args+env    | src-tauri/src/commands/pty.rs:604                  |        |      |    |      |    |     |
| C028 | delete_api_key                      | main only     | Keyring delete                                                | src-tauri/src/commands/api_keys.rs:219             |        |      |    |      |    |     |
| C029 | delete_conversation_file            | main only     | Deletes a conversation file                                   | src-tauri/src/commands/conversations.rs:93         |        |      |    |      |    |     |
| C030 | delete_crash                        | main only     | Deletes a crash log (confined)                                | src-tauri/src/commands/crashes.rs:88               |        |      |    |      |    |     |
| C031 | delete_dictation_entry              | main only     | Deletes one row                                               | src-tauri/src/commands/dictation/history.rs:285    |        |      |    |      |    |     |
| C032 | delete_mcp_server                   | main only     | Removes an mcpServers entry                                   | src-tauri/src/commands/mcp.rs:404                  |        |      |    |      |    |     |
| C033 | delete_packet_agent_token           | main only     | Keyring delete                                                | src-tauri/src/commands/packet_agent.rs:247         |        |      |    |      |    |     |
| C034 | delete_ssh_password                 | main only     | Keyring delete                                                | src-tauri/src/commands/ssh_keys.rs:220             |        |      |    |      |    |     |
| C035 | delete_whisper_model                | main only     | Deletes a model file                                          | src-tauri/src/commands/dictation/models.rs:539     |        |      |    |      |    |     |
| C036 | deliver_dictation_text              | main only     | Sets clipboard; optional Ctrl+V into foreground app           | src-tauri/src/commands/dictation/delivery.rs:31    |        |      |    |      |    |     |
| C037 | detect_agent                        | main only     | Spawns <cli> --version                                        | src-tauri/src/commands/agent.rs:142                |        |      |    |      |    |     |
| C038 | detect_cli_catalog                  | main only     | Spawns each CLI --version                                     | src-tauri/src/commands/agent.rs:151                |        |      |    |      |    |     |
| C039 | detect_quality_checks               | main only     | None (read)                                                   | src-tauri/src/commands/quality_runner.rs:899       |        |      |    |      |    |     |
| C040 | diagnose_mcp_server                 | main only     | Spawns the configured stdio MCP server                        | src-tauri/src/commands/mcp.rs:224                  |        |      |    |      |    |     |
| C041 | download_whisper_model              | main only     | Downloads pinned-SHA256 model from huggingface.co             | src-tauri/src/commands/dictation/models.rs:278     |        |      |    |      |    |     |
| C042 | export_conversation_markdown        | main only     | None (pure render)                                            | src-tauri/src/commands/conversations.rs:107        |        |      |    |      |    |     |
| C043 | extract_patterns                    | main only     | Aux LLM (spend)                                               | src-tauri/src/commands/memory.rs:185               |        |      |    |      |    |     |

| ID   | Command                          | Roles            | Mutates / reaches                                              | Location                                          | UNAUT<br>H | ROLE | ID | BODY | [ ] | P/F |
|------|----------------------------------|------------------|----------------------------------------------------------------|---------------------------------------------------|------------|------|----|------|-----|-----|
| C044 | focus_monitor_route_in_main      | main,<br>monitor | Focuses main window                                            | src-tauri/src/commands/monitor_windows.rs:185     |            |      |    |      |     |     |
| C045 | get_api_key_exists               | main only        | Keyring read                                                   | src-tauri/src/commands/api_keys.rs:192            |            |      |    |      |     |     |
| C046 | get_app_known_hosts_path         | main only        | None (read)                                                    | src-tauri/src/commands/pty.rs:1304                |            |      |    |      |     |     |
| C047 | get_aux_provider_options         | main only        | None (read)                                                    | src-tauri/src/commands/aux_routing.rs:106         |            |      |    |      |     |     |
| C048 | get_aux_route_resolutions        | main only        | None (read)                                                    | src-tauri/src/commands/aux_routing.rs:72          |            |      |    |      |     |     |
| C049 | get_custom_compat_base_url       | main only        | None (read)                                                    | src-tauri/src/commands/custom_compat.rs:11        |            |      |    |      |     |     |
| C050 | get_custom_compat_models         | main only        | None (read)                                                    | src-tauri/src/commands/custom_compat.rs:31        |            |      |    |      |     |     |
| C051 | get_cwd                          | main only        | None                                                           | src-tauri/src/commands/fs.rs:23                   |            |      |    |      |     |     |
| C052 | get_dictation_analytics          | main only        | None (read)                                                    | src-tauri/src/commands/dictation/analytics.rs:674 |            |      |    |      |     |     |
| C053 | get_dictation_history            | main only        | None (read)                                                    | src-tauri/src/commands/dictation/history.rs:214   |            |      |    |      |     |     |
| C054 | get_dictation_settings           | main only        | None (read)                                                    | src-tauri/src/commands/dictation/config.rs:110    |            |      |    |      |     |     |
| C055 | get_file_head_content            | main only        | None (read)                                                    | src-tauri/src/commands/git.rs:221                 |            |      |    |      |     |     |
| C056 | get_git_branch                   | main only        | None (read)                                                    | src-tauri/src/commands/git.rs:9                   |            |      |    |      |     |     |
| C057 | get_git_branch_remote            | main only        | None (read)                                                    | src-tauri/src/commands/git.rs:542                 |            |      |    |      |     |     |
| C058 | get_git_review_evidence          | main only        | None (read)                                                    | src-tauri/src/commands/git.rs:674                 |            |      |    |      |     |     |
| C059 | get_git_status                   | main only        | None (read)                                                    | src-tauri/src/commands/git.rs:19                  |            |      |    |      |     |     |
| C060 | get_git_status_remote            | main only        | None (read)                                                    | src-tauri/src/commands/git.rs:557                 |            |      |    |      |     |     |
| C061 | get_minimax_base_url             | main only        | None (read)                                                    | src-tauri/src/commands/minimax.rs:14              |            |      |    |      |     |     |
| C062 | get_monitor_window_route         | main,<br>monitor | Read                                                           | src-tauri/src/commands/monitor_windows.rs:146     |            |      |    |      |     |     |
| C063 | get_ollama_base_url              | main only        | None (read)                                                    | src-tauri/src/commands/ollama.rs:87               |            |      |    |      |     |     |
| C064 | get_ollama_runtime_options       | main only        | None (read)                                                    | src-tauri/src/commands/ollama.rs:131              |            |      |    |      |     |     |
| C065 | get_packet_agent_token_exists    | main only        | Keyring read                                                   | src-tauri/src/commands/packet_agent.rs:238        |            |      |    |      |     |     |
| C066 | get_provider_auth_status         | main only        | Reads CLI credential files                                     | src-tauri/src/commands/provider_auth.rs:463       |            |      |    |      |     |     |
| C067 | get_provider_auth_status_for_dir | main only        | Reads credential files in a dir                                | src-tauri/src/commands/provider_auth.rs:563       |            |      |    |      |     |     |
| C068 | get_provider_launch_stats        | main only        | None (read)                                                    | src-tauri/src/commands/provider_stats.rs:172      |            |      |    |      |     |     |
| C069 | get_sidecar_status               | main only        | None (read)                                                    | src-tauri/src/commands/agent_sidecar/mod.rs:206   |            |      |    |      |     |     |
| C070 | get_ssh_password_exists          | main only        | Keyring read                                                   | src-tauri/src/commands/ssh_keys.rs:167            |            |      |    |      |     |     |
| C071 | git_commit                       | main only        | git commit (staged only)                                       | src-tauri/src/commands/git.rs:234                 |            |      |    |      |     |     |
| C072 | git_commit_remote                | main only        | git commit over SSH                                            | src-tauri/src/commands/git.rs:993                 |            |      |    |      |     |     |
| C073 | git_create_branch                | main only        | git branch (name validated)                                    | src-tauri/src/commands/git.rs:296                 |            |      |    |      |     |     |
| C074 | git_create_branch_remote         | main only        | git branch over SSH                                            | src-tauri/src/commands/git.rs:1068                |            |      |    |      |     |     |
| C075 | git_diff_file_remote             | main only        | git diff over SSH (read)                                       | src-tauri/src/commands/git.rs:1023                |            |      |    |      |     |     |
| C076 | git_get_origin_url               | main only        | Read                                                           | src-tauri/src/commands/git.rs:365                 |            |      |    |      |     |     |
| C077 | git_host_add_connection          | main only        | Writes git-hosts.json + keyring token (P05 https unless local) | src-tauri/src/commands/github.rs:942              |            |      |    |      |     |     |
| C078 | git_host_has_token               | main only        | Read                                                           | src-tauri/src/commands/github.rs:1059             |            |      |    |      |     |     |
| C079 | git_host_list_connections        | main only        | Read                                                           | src-tauri/src/commands/github.rs:872              |            |      |    |      |     |     |
| C080 | git_host_probe_credential        | main only        | HTTPS to pasted instance URL with pasted token (P05)           | src-tauri/src/commands/git_host_probe.rs:348      |            |      |    |      |     |     |
| C081 | git_host_remove_connection       | main only        | Deletes connection + token                                     | src-tauri/src/commands/github.rs:1004             |            |      |    |      |     |     |
| C082 | git_host_set_active              | main only        | Switches active host                                           | src-tauri/src/commands/github.rs:379              |            |      |    |      |     |     |
| C083 | git_host_set_token               | main only        | Keyring rewrite                                                | src-tauri/src/commands/github.rs:1041             |            |      |    |      |     |     |
| C084 | git_host_update_connection       | main only        | Rename/rotate after live probe                                 | src-tauri/src/commands/github.rs:1312             |            |      |    |      |     |     |
| C085 | git_pull                         | main only        | git pull                                                       | src-tauri/src/commands/git.rs:286                 |            |      |    |      |     |     |
| C086 | git_pull_remote                  | main only        | git pull over SSH                                              | src-tauri/src/commands/git.rs:1055                |            |      |    |      |     |     |
| C087 | git_push                         | main only        | git push                                                       | src-tauri/src/commands/git.rs:276                 |            |      |    |      |     |     |
| C088 | git_push_branch                  | main only        | git push -u origin <branch> [--force-with-lease]               | src-tauri/src/commands/git.rs:346                 |            |      |    |      |     |     |
| C089 | git_push_remote                  | main only        | git push over SSH                                              | src-tauri/src/commands/git.rs:1042                |            |      |    |      |     |     |
| C090 | git_safety_check                 | main only        | Read                                                           | src-tauri/src/commands/git.rs:375                 |            |      |    |      |     |     |
| C091 | git_stage_files                  | main only        | git add --                                                     | src-tauri/src/commands/git.rs:314                 |            |      |    |      |     |     |
| C092 | git_stage_files_remote           | main only        | git add over SSH                                               | src-tauri/src/commands/git.rs:958                 |            |      |    |      |     |     |
| C093 | git_unstage_files                | main only        | git restore --staged --                                        | src-tauri/src/commands/git.rs:329                 |            |      |    |      |     |     |
| C094 | git_unstage_files_remote         | main only        | git restore over SSH                                           | src-tauri/src/commands/git.rs:976                 |            |      |    |      |     |     |
| C095 | github_ai_catch_up               | main only        | GitHub read + aux LLM (spend)                                  | src-tauri/src/commands/github.rs:2869             |            |      |    |      |     |     |
| C096 | github_ai_pr_description         | main only        | GitHub read + aux LLM (spend)                                  | src-tauri/src/commands/github.rs:2242             |            |      |    |      |     |     |
| C097 | github_ai_pr_review              | main only        | GitHub read + aux LLM (spend)                                  | src-tauri/src/commands/github.rs:2362             |            |      |    |      |     |     |
| C098 | github_ai_triage                 | main only        | GitHub read + aux LLM (spend)                                  | src-tauri/src/commands/github.rs:3126             |            |      |    |      |     |     |
| C099 | github_clear_token               | main only        | Keyring delete                                                 | src-tauri/src/commands/github.rs:525              |            |      |    |      |     |     |
| C100 | github_close_issue               | main only        | Mutates remote repo via git-host API (close issue)             | src-tauri/src/commands/github.rs:1767             |            |      |    |      |     |     |
| C101 | github_close_pr                  | main only        | Mutates remote repo via git-host API (close pr)                | src-tauri/src/commands/github.rs:3416             |            |      |    |      |     |     |
| C102 | github_convert_pr_to_draft       | main only        | Mutates remote repo via git-host API (convert pr to draft)     | src-tauri/src/commands/github.rs:3440             |            |      |    |      |     |     |

| ID   | Command                           | Roles     | Mutates / reaches                                                 | Location                                      | UNAUTH | ROLE | ID | BODY | [] | P/F |
|------|-----------------------------------|-----------|-------------------------------------------------------------------|-----------------------------------------------|--------|------|----|------|----|-----|
| C103 | github_create_issue               | main only | Mutates remote repo via git-host API (create issue)               | src-tauri/src/commands/github.rs:1499         |        |      |    |      |    |     |
| C104 | github_create_pr                  | main only | Mutates remote repo via git-host API (create pr)                  | src-tauri/src/commands/github.rs:1561         |        |      |    |      |    |     |
| C105 | github_create_repo_milestone      | main only | Mutates remote repo via git-host API (create repo milestone)      | src-tauri/src/commands/github.rs:1932         |        |      |    |      |    |     |
| C106 | github_device_flow_commit         | main only | Keyring write                                                     | src-tauri/src/commands/github.rs:837          |        |      |    |      |    |     |
| C107 | github_device_flow_discard        | main only | Drops parked token                                                | src-tauri/src/commands/github.rs:854          |        |      |    |      |    |     |
| C108 | github_device_flow_poll           | main only | Polls github.com; parks token                                     | src-tauri/src/commands/github.rs:751          |        |      |    |      |    |     |
| C109 | github_device_flow_probe_pending  | main only | Probes parked token                                               | src-tauri/src/commands/github.rs:819          |        |      |    |      |    |     |
| C110 | github_device_flow_start          | main only | github.com device endpoint (needs PACKETBENCH_GITHUB_CLIENT_ID)   | src-tauri/src/commands/github.rs:570          |        |      |    |      |    |     |
| C111 | github_get_authenticated_user     | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:1400         |        |      |    |      |    |     |
| C112 | github_get_issue                  | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:1485         |        |      |    |      |    |     |
| C113 | github_get_pr_checks              | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:3619         |        |      |    |      |    |     |
| C114 | github_get_pr_diff                | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:1602         |        |      |    |      |    |     |
| C115 | github_has_token                  | main only | Read                                                              | src-tauri/src/commands/github.rs:535          |        |      |    |      |    |     |
| C116 | github_investigate_issue          | main only | GitHub read + aux LLM (spend)                                     | src-tauri/src/commands/github.rs:2051         |        |      |    |      |    |     |
| C117 | github_list_branches              | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:2473         |        |      |    |      |    |     |
| C118 | github_list_repo_comments         | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:1687         |        |      |    |      |    |     |
| C119 | github_list_issues                | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:1448         |        |      |    |      |    |     |
| C120 | github_list_issues_page           | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:1975         |        |      |    |      |    |     |
| C121 | github_list_notifications         | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:4259         |        |      |    |      |    |     |
| C122 | github_list_pr_review_comments    | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:3991         |        |      |    |      |    |     |
| C123 | github_list_pr_reviews            | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:3962         |        |      |    |      |    |     |
| C124 | github_list_prs                   | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:1586         |        |      |    |      |    |     |
| C125 | github_list_prs_page              | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:2018         |        |      |    |      |    |     |
| C126 | github_list_releases              | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:1432         |        |      |    |      |    |     |
| C127 | github_list_repo_assignable_users | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:1959         |        |      |    |      |    |     |
| C128 | github_list_repo_labels           | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:1900         |        |      |    |      |    |     |
| C129 | github_list_repo_milestones       | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:1916         |        |      |    |      |    |     |
| C130 | github_list_repos                 | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:1379         |        |      |    |      |    |     |
| C131 | github_list_repos_page            | main only | GitHub/Gitea read with keyring token                              | src-tauri/src/commands/github.rs:2036         |        |      |    |      |    |     |
| C132 | github_mark_notification_read     | main only | PATCH notification thread                                         | src-tauri/src/commands/github.rs:4286         |        |      |    |      |    |     |
| C133 | github_merge_pr                   | main only | Mutates remote repo via git-host API (merge pr)                   | src-tauri/src/commands/github.rs:3326         |        |      |    |      |    |     |
| C134 | github_oauth_configured           | main only | Read                                                              | src-tauri/src/commands/github.rs:616          |        |      |    |      |    |     |
| C135 | github_post_issue_comment         | main only | Mutates remote repo via git-host API (post issue comment)         | src-tauri/src/commands/github.rs:1710         |        |      |    |      |    |     |
| C136 | github_post_pr_review_comment     | main only | Mutates remote repo via git-host API (post pr review comment)     | src-tauri/src/commands/github.rs:4024         |        |      |    |      |    |     |
| C137 | github_reopen_issue               | main only | Mutates remote repo via git-host API (reopen issue)               | src-tauri/src/commands/github.rs:1780         |        |      |    |      |    |     |
| C138 | github_reopen_pr                  | main only | Mutates remote repo via git-host API (reopen pr)                  | src-tauri/src/commands/github.rs:3427         |        |      |    |      |    |     |
| C139 | github_reply_to_pr_review_comment | main only | Mutates remote repo via git-host API (reply to pr review comment) | src-tauri/src/commands/github.rs:4094         |        |      |    |      |    |     |
| C140 | github_set_issue_assignees        | main only | Mutates remote repo via git-host API (set issue assignees)        | src-tauri/src/commands/github.rs:1793         |        |      |    |      |    |     |
| C141 | github_set_issue_labels           | main only | Mutates remote repo via git-host API (set issue labels)           | src-tauri/src/commands/github.rs:1815         |        |      |    |      |    |     |
| C142 | github_set_issue_milestone        | main only | Mutates remote repo via git-host API (set issue milestone)        | src-tauri/src/commands/github.rs:1886         |        |      |    |      |    |     |
| C143 | github_set_pr_labels              | main only | Mutates remote repo via git-host API (set pr labels)              | src-tauri/src/commands/github.rs:2550         |        |      |    |      |    |     |
| C144 | github_set_pr_milestone           | main only | Mutates remote repo via git-host API (set pr milestone)           | src-tauri/src/commands/github.rs:2602         |        |      |    |      |    |     |
| C145 | github_set_pr_reviewers           | main only | Mutates remote repo via git-host API (set pr reviewers)           | src-tauri/src/commands/github.rs:2516         |        |      |    |      |    |     |
| C146 | github_set_token                  | main only | Probes GitHub then keyring write github-token                     | src-tauri/src/commands/github.rs:507          |        |      |    |      |    |     |
| C147 | github_update_issue               | main only | Mutates remote repo via git-host API (update issue)               | src-tauri/src/commands/github.rs:1530         |        |      |    |      |    |     |
| C148 | inspect_cli_launch                | main only | Resolves launch path                                              | src-tauri/src/commands/agent.rs:244           |        |      |    |      |    |     |
| C149 | inspect_packetcode_installation   | main only | Spawns packetcode --version                                       | src-tauri/src/commands/agent.rs:318           |        |      |    |      |    |     |
| C150 | integrate_flight_attempt          | main only | Merges attempt into integration                                   | src-tauri/src/commands/git.rs:836             |        |      |    |      |    |     |
| C151 | issues_extract_from_spec          | main only | Aux LLM (spend)                                                   | src-tauri/src/commands/issues.rs:127          |        |      |    |      |    |     |
| C152 | kill_pty                          | main only | Kills a PTY process tree                                          | src-tauri/src/commands/pty.rs:950             |        |      |    |      |    |     |
| C153 | kill_pty_and_wait                 | main only | Kills a PTY tree and waits                                        | src-tauri/src/commands/pty.rs:980             |        |      |    |      |    |     |
| C154 | land_flight_integration           | main only | Merges integration into root                                      | src-tauri/src/commands/git.rs:881             |        |      |    |      |    |     |
| C155 | launch_flight_async               | main only | Creates worktrees (local/SSH), starts agent sessions (spend)      | src-tauri/src/commands/flight_attempts.rs:625 |        |      |    |      |    |     |
| C156 | list_audio_devices                | main only | Read                                                              | src-tauri/src/commands/dictation/audio.rs:160 |        |      |    |      |    |     |
| C157 | list_crashes                      | main only | None (read)                                                       | src-tauri/src/commands/crashes.rs:44          |        |      |    |      |    |     |
| C158 | list_directory                    | main only | Read inside workspace                                             | src-tauri/src/commands/fs.rs:44               |        |      |    |      |    |     |
| C159 | list_ollama_models                | main only | GET Ollama base URL (no secret)                                   | src-tauri/src/commands/ollama.rs:163          |        |      |    |      |    |     |

| ID   | Command                           | Roles            | Mutates / reaches                                                              | Location                                             | UNAUT<br>H | ROLE | ID | BODY | [ ] | P/F |
|------|-----------------------------------|------------------|--------------------------------------------------------------------------------|------------------------------------------------------|------------|------|----|------|-----|-----|
| C160 | list_project_files                | main only        | Read                                                                           | src-tauri/src/commands/fs.rs:375                     |            |      |    |      |     |     |
| C161 | list_project_memory               | main only        | Read                                                                           | src-tauri/src/commands/project_memory.rs:896         |            |      |    |      |     |     |
| C162 | list_provider_models              | main only        | GET provider catalogs with keyring key                                         | src-tauri/src/commands/provider_models.rs:760        |            |      |    |      |     |     |
| C163 | list_pty_sessions                 | main only        | None (read)                                                                    | src-tauri/src/commands/pty.rs:972                    |            |      |    |      |     |     |
| C164 | list_skills                       | main only        | None (read)                                                                    | src-tauri/src/commands/skills.rs:164                 |            |      |    |      |     |     |
| C165 | list_slash_commands               | main only        | None (read)                                                                    | src-tauri/src/commands/slash_commands.rs:111         |            |      |    |      |     |     |
| C166 | list_subdirectories               | main only        | Read any absolute dir                                                          | src-tauri/src/commands/fs.rs:160                     |            |      |    |      |     |     |
| C167 | list_whisper_models               | main only        | Read                                                                           | src-tauri/src/commands/dictation/models.rs:241       |            |      |    |      |     |     |
| C168 | list_wsl_distributions            | main only        | Spawns wsl.exe --list                                                          | src-tauri/src/commands/pty.rs:301                    |            |      |    |      |     |     |
| C169 | load_conversations                | main,<br>monitor | None (read)                                                                    | src-tauri/src/commands/conversations.rs:53           |            |      |    |      |     |     |
| C170 | load_persisted_state              | main,<br>monitor | None (read)                                                                    | src-tauri/src/commands/state.rs:12                   |            |      |    |      |     |     |
| C171 | load_webview_storage_mirror       | main only        | Read                                                                           | src-tauri/src/commands/webview_storage_mirror.rs:79  |            |      |    |      |     |     |
| C172 | mark_attempt_status               | main only        | Rewrites attempt status                                                        | src-tauri/src/commands/flight_attempts.rs:1230       |            |      |    |      |     |     |
| C173 | mcp_server_available_tools        | main only        | Read                                                                           | src-tauri/src/mcp_server/mod.rs:314                  |            |      |    |      |     |     |
| C174 | mcp_server_recent_activity        | main only        | Read                                                                           | src-tauri/src/mcp_server/mod.rs:297                  |            |      |    |      |     |     |
| C175 | mcp_server_start                  | main only        | Binds 127.0.0.1:<port>, mints bearer, serves MCP                               | src-tauri/src/mcp_server/mod.rs:226                  |            |      |    |      |     |     |
| C176 | mcp_server_status                 | main only        | Read (returns token)                                                           | src-tauri/src/mcp_server/mod.rs:284                  |            |      |    |      |     |     |
| C177 | mcp_server_stop                   | main only        | Stops MCP server                                                               | src-tauri/src/mcp_server/mod.rs:271                  |            |      |    |      |     |     |
| C178 | merge_conversation_branch         | main only        | git squash-merge into HEAD                                                     | src-tauri/src/commands/git.rs:433                    |            |      |    |      |     |     |
| C179 | open_monitor_window               | main only        | Creates monitor-main window                                                    | src-tauri/src/commands/monitor_windows.rs:95         |            |      |    |      |     |     |
| C180 | packet_agent_request              | main only        | HTTPS to PacketAgent endpoint with keyring bearer; POST/PUT mutate deployments | src-tauri/src/commands/packet_agent.rs:255           |            |      |    |      |     |     |
| C181 | parse_spec_to_flight              | main only        | Aux LLM (spend)                                                                | src-tauri/src/commands/spec.rs:89                    |            |      |    |      |     |     |
| C182 | parse_spec_to_tickets             | main only        | Aux LLM (spend)                                                                | src-tauri/src/commands/spec.rs:104                   |            |      |    |      |     |     |
| C183 | path_is_dir                       | main only        | Existence probe, any path                                                      | src-tauri/src/commands/fs.rs:37                      |            |      |    |      |     |     |
| C184 | prepare_flight_integration_branch | main only        | Creates integration branch                                                     | src-tauri/src/commands/git.rs:800                    |            |      |    |      |     |     |
| C185 | probe_packetcode_integration      | main only        | Spawns packetcode --version / doctor --json                                    | src-tauri/src/commands/agent.rs:362                  |            |      |    |      |     |     |
| C186 | probe_terminal_shell              | main only        | Spawns <shell> --version                                                       | src-tauri/src/commands/pty.rs:252                    |            |      |    |      |     |     |
| C187 | read_codex_statusline_states      | main only        | None (read)                                                                    | src-tauri/src/commands/statusline/codex.rs:257       |            |      |    |      |     |     |
| C188 | read_crash                        | main only        | Read (confined)                                                                | src-tauri/src/commands/crashes.rs:82                 |            |      |    |      |     |     |
| C189 | read_file_contents                | main only        | Read inside workspace (2 MB cap)                                               | src-tauri/src/commands/fs.rs:221                     |            |      |    |      |     |     |
| C190 | read_file_for_diff                | main only        | Read (confined)                                                                | src-tauri/src/commands/fs.rs:418                     |            |      |    |      |     |     |
| C191 | read_mcp_servers                  | main only        | Read both files                                                                | src-tauri/src/commands/mcp.rs:364                    |            |      |    |      |     |     |
| C192 | read_opencode_statusline_states   | main only        | None (read)                                                                    | src-tauri/src/commands/statusline/opencode.rs:23     |            |      |    |      |     |     |
| C193 | read_prompt_history               | main only        | None (read)                                                                    | src-tauri/src/commands/history.rs:33                 |            |      |    |      |     |     |
| C194 | read_pty_transcript               | main only        | None (read)                                                                    | src-tauri/src/commands/pty.rs:1014                   |            |      |    |      |     |     |
| C195 | read_statusline_states            | main only        | None (read)                                                                    | src-tauri/src/commands/statusline/claude.rs:29       |            |      |    |      |     |     |
| C196 | read_usage_analytics              | main only        | None (read)                                                                    | src-tauri/src/commands/analytics.rs:72               |            |      |    |      |     |     |
| C197 | remove_conversation_worktree      | main only        | git worktree remove                                                            | src-tauri/src/commands/git.rs:409                    |            |      |    |      |     |     |
| C198 | resize_pty                        | main only        | Resizes a PTY                                                                  | src-tauri/src/commands/pty.rs:924                    |            |      |    |      |     |     |
| C199 | resolve_agents_md                 | main only        | Reads AGENTS.md chain                                                          | src-tauri/src/commands/agents_md.rs:12               |            |      |    |      |     |     |
| C200 | respond_edit                      | main only        | Applies/declines a pending edit                                                | src-tauri/src/commands/api_agent.rs:1575             |            |      |    |      |     |     |
| C201 | respond_permission                | main only        | Resolves a risky-tool prompt                                                   | src-tauri/src/commands/api_agent.rs:1507             |            |      |    |      |     |     |
| C202 | retry_last_turn                   | main only        | Re-runs last turn (spend)                                                      | src-tauri/src/commands/api_agent.rs:1646             |            |      |    |      |     |     |
| C203 | run_quality_checks                | main only        | Spawns detected lint/typecheck/test/cargo                                      | src-tauri/src/commands/quality_runner.rs:911         |            |      |    |      |     |     |
| C204 | save_agents_slice                 | main only        | Rewrites one slice of state.v1.json                                            | src-tauri/src/commands/state.rs:55                   |            |      |    |      |     |     |
| C205 | save_cli_accounts_slice           | main only        | Rewrites one slice of state.v1.json                                            | src-tauri/src/commands/state.rs:104                  |            |      |    |      |     |     |
| C206 | save_conversation                 | main only        | Writes conversations/<id>.json (id validated)                                  | src-tauri/src/commands/conversations.rs:42           |            |      |    |      |     |     |
| C207 | save_flights_slice                | main only        | Rewrites one slice of state.v1.json                                            | src-tauri/src/commands/state.rs:50                   |            |      |    |      |     |     |
| C208 | save_issues_slice                 | main only        | Rewrites one slice of state.v1.json                                            | src-tauri/src/commands/state.rs:74                   |            |      |    |      |     |     |
| C209 | save_memory_slice                 | main only        | Rewrites one slice of state.v1.json                                            | src-tauri/src/commands/state.rs:84                   |            |      |    |      |     |     |
| C210 | save_persisted_state              | main only        | Rewrites state.v1.json (not issues/retros)                                     | src-tauri/src/commands/state.rs:28                   |            |      |    |      |     |     |
| C211 | save_servers_slice                | main only        | Rewrites one slice of state.v1.json                                            | src-tauri/src/commands/state.rs:92                   |            |      |    |      |     |     |
| C212 | save_settings_slice               | main only        | Rewrites one slice of state.v1.json                                            | src-tauri/src/commands/state.rs:60                   |            |      |    |      |     |     |
| C213 | save_ui_slice                     | main only        | Rewrites one slice of state.v1.json                                            | src-tauri/src/commands/state.rs:69                   |            |      |    |      |     |     |
| C214 | save_webview_storage_mirror       | main only        | Rewrites webview-storage-mirror.json (8 MB cap)                                | src-tauri/src/commands/webview_storage_mirror.rs:120 |            |      |    |      |     |     |
| C215 | save_workspaces_slice             | main only        | Rewrites one slice of state.v1.json                                            | src-tauri/src/commands/state.rs:79                   |            |      |    |      |     |     |
| C216 | scan_codebase_memory              | main only        | Reads project + aux LLM (spend)                                                | src-tauri/src/commands/memory.rs:93                  |            |      |    |      |     |     |

| ID   | Command                            | Roles     | Mutates / reaches                                                                    | Location                                          | UNAUT<br>H | ROLE | ID | BODY | [ ] | P/F |
|------|------------------------------------|-----------|--------------------------------------------------------------------------------------|---------------------------------------------------|------------|------|----|------|-----|-----|
| C217 | search_dictation_history           | main only | SQLite read                                                                          | src-tauri/src/commands/dictation/history.rs:252   |            |      |    |      |     |     |
| C218 | seed_cli_account_config_dir        | main only | Copies settings.json/config.toml between abs dirs (never credentials)                | src-tauri/src/commands/cli_account.rs:90          |            |      |    |      |     |     |
| C219 | send_api_agent_message             | main only | Continues a turn (LLM spend)                                                         | src-tauri/src/commands/api_agent.rs:1343          |            |      |    |      |     |     |
| C220 | set_api_key                        | main only | Keyring write api-key-<provider>                                                     | src-tauri/src/commands/api_keys.rs:169            |            |      |    |      |     |     |
| C221 | set_approve_writes                 | main only | Toggles edit gate                                                                    | src-tauri/src/commands/api_agent.rs:1542          |            |      |    |      |     |     |
| C222 | set_attempt_draft_pr               | main only | Records PR URL                                                                       | src-tauri/src/commands/flight_attempts.rs:1125    |            |      |    |      |     |     |
| C223 | set_attempt_review_gate            | main only | Records review verdict                                                               | src-tauri/src/commands/flight_attempts.rs:1195    |            |      |    |      |     |     |
| C224 | set_aux_routing_overrides          | main only | Updates in-memory routing map                                                        | src-tauri/src/commands/aux_routing.rs:50          |            |      |    |      |     |     |
| C225 | set_custom_compat_base_url         | main only | Writes provider-settings.v1.json (P05)                                               | src-tauri/src/commands/custom_compat.rs:18        |            |      |    |      |     |     |
| C226 | set_custom_compat_models           | main only | Writes model list                                                                    | src-tauri/src/commands/custom_compat.rs:38        |            |      |    |      |     |     |
| C227 | set_dictation_settings             | main only | Writes dictation config                                                              | src-tauri/src/commands/dictation/config.rs:156    |            |      |    |      |     |     |
| C228 | set_flight_publish_attempts_as_prs | main only | Flight flag                                                                          | src-tauri/src/commands/flight_attempts.rs:1158    |            |      |    |      |     |     |
| C229 | set_minimax_base_url               | main only | Writes provider-settings.v1.json (P05 https unless local)                            | src-tauri/src/commands/minimax.rs:19              |            |      |    |      |     |     |
| C230 | set_ollama_base_url                | main only | Writes provider-settings.v1.json (http allowed; no secret)                           | src-tauri/src/commands/ollama.rs:92               |            |      |    |      |     |     |
| C231 | set_ollama_runtime_options         | main only | Writes num_ctx/keep_alive                                                            | src-tauri/src/commands/ollama.rs:138              |            |      |    |      |     |     |
| C232 | set_packet_agent_token             | main only | Keyring write packet-agent-token                                                     | src-tauri/src/commands/packet_agent.rs:227        |            |      |    |      |     |     |
| C233 | set_permission_mode                | main only | Changes gate posture                                                                 | src-tauri/src/commands/api_agent.rs:1481          |            |      |    |      |     |     |
| C234 | set_plan_mode                      | main only | Toggles plan mode                                                                    | src-tauri/src/commands/api_agent.rs:1455          |            |      |    |      |     |     |
| C235 | set_ssh_password                   | main only | Keyring write ssh-<serverid>                                                         | src-tauri/src/commands/ssh_keys.rs:187            |            |      |    |      |     |     |
| C236 | sign_out_provider                  | main only | Deletes ~/.claude/.credentials.json or ~/.codex/auth.json                            | src-tauri/src/commands/provider_auth.rs:436       |            |      |    |      |     |     |
| C237 | ssh_check_remote_path              | main only | Spawns ssh to probe a remote path                                                    | src-tauri/src/commands/pty.rs:1356                |            |      |    |      |     |     |
| C238 | ssh_exec                           | main only | Spawns local ssh with caller argv (P08 denylist); password via askpass/stdin         | src-tauri/src/commands/pty.rs:1070                |            |      |    |      |     |     |
| C239 | ssh_fetch_fingerprint              | main only | Spawns ssh-keyscan + ssh-keygen                                                      | src-tauri/src/commands/pty.rs:1153                |            |      |    |      |     |     |
| C240 | ssh_pin_host                       | main only | Appends to ~/.packetbench/ssh/known_hosts                                            | src-tauri/src/commands/pty.rs:1264                |            |      |    |      |     |     |
| C241 | start_api_agent_session            | main only | Starts agent loop: keyring key, gated tools (P02 default ask), MCP, hooks; LLM spend | src-tauri/src/commands/api_agent.rs:1051          |            |      |    |      |     |     |
| C242 | start_packet_agent_stream          | main only | Opens SSE stream to PacketAgent (bearer)                                             | src-tauri/src/commands/packet_agent_stream.rs:176 |            |      |    |      |     |     |
| C243 | start_recording                    | main only | Opens microphone                                                                     | src-tauri/src/commands/dictation/audio.rs:458     |            |      |    |      |     |     |
| C244 | stop_packet_agent_stream           | main only | Stops SSE task                                                                       | src-tauri/src/commands/packet_agent_stream.rs:220 |            |      |    |      |     |     |
| C245 | stop_recording                     | main only | Stops capture, runs whisper                                                          | src-tauri/src/commands/dictation/audio.rs:855     |            |      |    |      |     |     |
| C246 | summarize_flight                   | main only | Aux LLM (spend)                                                                      | src-tauri/src/commands/memory.rs:223              |            |      |    |      |     |     |
| C247 | summarize_session                  | main only | Aux LLM (spend)                                                                      | src-tauri/src/commands/memory.rs:164              |            |      |    |      |     |     |
| C248 | test_audio_device                  | main only | Opens a device                                                                       | src-tauri/src/commands/dictation/audio.rs:294     |            |      |    |      |     |     |
| C249 | toggle_pinned_pattern              | main only | Flips a memory pattern flag                                                          | src-tauri/src/commands/memory.rs:278              |            |      |    |      |     |     |
| C250 | update_project_memory              | main only | Rewrites a note (revision check)                                                     | src-tauri/src/commands/project_memory.rs:909      |            |      |    |      |     |     |
| C251 | watch_project_memory               | main only | Starts fs watcher                                                                    | src-tauri/src/commands/project_memory.rs:974      |            |      |    |      |     |     |
| C252 | write_file_contents                | main only | Writes a file inside workspace                                                       | src-tauri/src/commands/fs.rs:246                  |            |      |    |      |     |     |
| C253 | write_mcp_server                   | main only | Upserts mcpServers in ~/.claude/settings.json or <project>/mcp.json                  | src-tauri/src/commands/mcp.rs:381                 |            |      |    |      |     |     |
| C254 | write_pty                          | main only | Writes keystrokes to a PTY (64 KB cap)                                               | src-tauri/src/commands/pty.rs:899                 |            |      |    |      |     |     |

| ID        | Route                                                                                                                                                                                                                                                                                                             | Auth                                                 | Mutates                                               | Location                                     | [ ] | P/F |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|-------------------------------------------------------|----------------------------------------------|-----|-----|
| N001      | GET /health on 127.0.0.1:<port> (MCP server)                                                                                                                                                                                                                                                                      | any local process; Origin must be absent or loopback | None                                                  | src-tauri/src/mcp_server/transport.rs        |     |     |
| N002      | POST/GET/DELETE /mcp (MCP Streamable HTTP)                                                                                                                                                                                                                                                                        | bearer + loopback Origin + Host allowlist            | tools M008-M010, M013-M016 mutate (allow_writes only) | src-tauri/src/mcp_server/transport.rs:69-100 |     |     |
| M001-M016 | MCP tools ping, get_active_flight, list_runnable_tasks, read_task_details, read_memory_context, search_project_memory, read_project_memory, create/update/archive_project_memory, list_workspaces, read_coordination_inbox, append_handoff, escalate, post_coordination_message, acknowledge_coordination_message | bearer; writes need Allow writes                     | see audit 2b                                          | src-tauri/src/mcp_server/mod.rs:582-836      |     |     |

| ID        | Route                                                                                                                                                                        | Auth                                      | Mutates                            | Location                                 | [ ] | P/F |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|------------------------------------|------------------------------------------|-----|-----|
| R001-R002 | MCP resources packetbench://project{flights}flights/{id}flights/{id}/tasks{flights/{id}/inbox{issues}reviews{workspace}memory/patterns{memory/project/{ws}}packetcode/health | bearer; gated by the tool allowlist (P07) | packetcode/health spawns a process | src-tauri/src/mcp_server/mod.rs:923-1030 |     |     |

## Shot list

There are no URLs: PacketBench is a desktop window. Each shot names the in-app location, the state to be in, and the one question the shot answers. Dev builds are served from `http://localhost:1420` inside the window (`tauri.conf.json build.devUrl`).

| #  | Location + state                                                                                                                              | Question the shot answers                                                                                          | [ ] | P/F |
|----|-----------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|-----|-----|
| S1 | Agents view, new API conversation in a repo NOT listed in <code>trusted-projects.json</code> ; provider 'Claude (API)'; anthropic key present | Does the mode chip read 'Manual' (not 'Default') on a fresh conversation? (P02)                                    |     |     |
| S2 | Same conversation; ask 'run `git status` with the bash tool'                                                                                  | Does the Allow once / Always allow / Deny prompt appear before anything runs? (P02)                                |     |     |
| S3 | Log viewer: Select-String <code>packetbench::trust</code> in today's log after S1                                                             | Is 'project is not trusted: repo-supplied hooks, .mcp.json servers, and .claude/agents are ignored' present? (P01) |     |     |
| S4 | Settings > MCP > MCP Provider card, Enable MCP Provider on, Allow writes off, all tools ticked                                                | Are port, bearer token, and served tool list visible? (baseline for S5)                                            |     |     |
| S5 | Same card with only <code>get_active_flight</code> ticked, server re-enabled; terminal running the curl from test T-MCP-07                    | Does <code>resources/read</code> of <code>packetbench://memory/patterns</code> return the allowlist error? (P07)   |     |     |
| S6 | Settings > GitHub > Connect a git host wizard, Gitea, instance URL <code>http://gitea.example.com</code> , any token                          | Is the error 'Instance URL must use https:// ...' shown before any request? (P05)                                  |     |     |
| S7 | Settings > Providers > API Keys card                                                                                                          | Are keys shown only as present/absent, never as values? (I8)                                                       |     |     |
| S8 | Log viewer: Select-String <code>packetbench::boot</code> on app start                                                                         | Does 'boot check done' appear with <code>issues=0</code> , and is the <code>trust-file</code> line present? (P09)  |     |     |




## Screenshot slots

S1 - Agents view, new API conversation in a repo NOT listed in trusted-projects.json; provider 'Claude (API)'; anthropic key present  
Q: Does the mode chip read 'Manual' (not 'Default') on a fresh conversation? (P02)



S2 - Same conversation; ask 'run `git status` with the bash tool'  
Q: Does the Allow once / Always allow / Deny prompt appear before anything runs? (P02)



S3 - Log viewer: Select-String packetbench::trust in today's log after S1

Q: Is 'project is not trusted: repo-supplied hooks, .mcp.json servers, and .claude/agents are ignored' present? (P01)

S4 - Settings > MCP > MCP Provider card, Enable MCP Provider on, Allow writes off, all tools ticked

Q: Are port, bearer token, and served tool list visible? (baseline for S5)

S5 - Same card with only get\_active\_flight ticked, server re-enabled; terminal running the curl from test T-MCP-07  
Q: Does resources/read of packetbench://memory/patterns return the allowlist error? (P07)

S6 - Settings > GitHub > Connect a git host wizard, Gitea, instance URL <http://gitea.example.com>, any token  
Q: Is the error 'Instance URL must use https:// ...' shown before any request? (P05)

S7 - Settings > Providers > API Keys card

Q: Are keys shown only as present/absent, never as values? (I8)

S8 - Log viewer: Select-String packetbench::boot on app start

Q: Does 'boot check done' appear with issues=0, and is the trust-file line present? (P09)

## Test sheets

**MCP server (N001/N002) - every row is a literal curl; replace <port> and <TOKEN> from Settings > MCP > MCP Provider**

| ID       | Case                                                                             | Command                                                                                                                                                                                                                                                                                                                                                                                          | Expected                                                                          | Failure signature                                                                                                               | [] | P/F |
|----------|----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|----|-----|
| T-MCP-01 | Health                                                                           | curl -s -i http://127.0.0.1:<port>/health                                                                                                                                                                                                                                                                                                                                                        | HTTP 200; body {"ok":true,"app":"PacketBench","version":"0.13.2","service":"mcp"} | 404 (P07 not applied) or connection refused (server not enabled)                                                                |    |     |
| T-MCP-02 | No token                                                                         | curl -s -o /dev/null -w '%{http_code}' -X POST http://127.0.0.1:<port>/mcp -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":1,"method":"initialize","params":{"protocolVersion":"2025-03-26","capabilities":{"clientInfo":{"name":"qa","version":"0"}}}}'                                                                          | 401                                                                               | 200 = bearer layer missing; log has no 'MCP request rejected: bearer token missing or wrong'                                    |    |     |
| T-MCP-03 | Wrong token                                                                      | curl -s -o /dev/null -w '%{http_code}' -X POST http://127.0.0.1:<port>/mcp -H 'authorization: Bearer nope' -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":1,"method":"initialize","params":{"protocolVersion":"2025-03-26","capabilities":{"clientInfo":{"name":"qa","version":"0"}}}}'                                          | 401; log line outcome=bad_token                                                   | 200                                                                                                                             |    |     |
| T-MCP-04 | Non-loopback Origin (webhook analogue)                                           | curl -s -o /dev/null -w '%{http_code}' -X POST http://127.0.0.1:<port>/mcp -H 'origin: https://evil.example.com' -H 'authorization: Bearer <TOKEN>' -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":1,"method":"initialize","params":{"protocolVersion":"2025-03-26","capabilities":{"clientInfo":{"name":"qa","version":"0"}}}}' | 403; log line outcome=forbidden_origin                                            | 200                                                                                                                             |    |     |
| T-MCP-05 | Origin guard on /health                                                          | curl -s -o /dev/null -w '%{http_code}' http://127.0.0.1:<port>/health -H 'origin: https://evil.example.com'                                                                                                                                                                                                                                                                                      | 403                                                                               | 200                                                                                                                             |    |     |
| T-MCP-06 | Login                                                                            | curl -s -i -X POST http://127.0.0.1:<port>/mcp -H 'authorization: Bearer <TOKEN>' -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":1,"method":"initialize","params":{"protocolVersion":"2025-03-26","capabilities":{"clientInfo":{"name":"qa","version":"0"}}}}'                                                                   | 200; response header mcp-session-id present                                       | 401                                                                                                                             |    |     |
| T-MCP-07 | Resource denied by allowlist (server enabled with only get_active_flight ticked) | after T-MCP-06 and notifications/initialized: curl -s -X POST http://127.0.0.1:<port>/mcp -H 'authorization: Bearer <TOKEN>' -H 'mcp-session-id: <SID>' -H 'content-type: application/json' -H 'accept: application/json, text/event-stream' -d '{"jsonrpc":"2.0","id":5,"method":"resources/read","params":{"uri":"packetbench://memory/patterns"}}'                                            | JSON-RPC error 'resource is not permitted by this server's tool allowlist'        | a result with 'patterns'                                                                                                        |    |     |
| T-MCP-08 | Authenticated write (Allow writes ON, a Flight selected)                         | same session: -d '{"jsonrpc":"2.0","id":6,"method":"tools/call","params":{"name":"append_handoff","arguments":{"flightId":"<flight_id from get_active_flight>","summary":"qa note"}}}'                                                                                                                                                                                                           | 'Posted to the flight timeline.; Flight Deck timeline shows actor mcp             | 'writes are disabled; enable them in PacketBench's MCP Provider settings' (means Allow writes is off = documented failure path) |    |     |
| T-MCP-09 | Bad flight id                                                                    | same as T-MCP-08 with flightId 'nope'                                                                                                                                                                                                                                                                                                                                                            | JSON-RPC error 'unknown flightId'                                                 | success                                                                                                                         |    |     |
| T-MCP-10 | Webhooks                                                                         | n/a - PacketBench has no inbound webhooks (audit section 3)                                                                                                                                                                                                                                                                                                                                      | record N/A                                                                        | -                                                                                                                               |    |     |

## Paid outbound calls (every LLM spend path)

| ID       | Path                                                                     | Steps (real values)                                                                                                                | Expected                                                                                                         | Failure signature                                                                                  | [] | P/F |
|----------|--------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|----|-----|
| T-PAY-01 | Anthropic in-process (Claude (API) row)                                  | Settings > Providers > API Keys: anthropic key set. Start a conversation, send 'say hi'.                                           | log: packetbench::egress service=anthropic 'LLM request' then 'LLM response' status=200; usage.jsonl gains a row | 'No API key configured for anthropic. Set one in Settings > API Keys.' (key missing) or status=401 |    |     |
| T-PAY-02 | OpenAI-compatible (OpenAI / MiniMax / OpenRouter / Ollama / Custom rows) | Same with the row's key. For Ollama no key.                                                                                        | log: service=openai-compat base_url=<url> 'LLM response' status=200                                              | status=401/403 or 'Ollama not reachable at http://localhost:11434'                                 |    |     |
| T-PAY-03 | Sidecar rows (Claude Agent SDK (API), OpenAI Agents SDK (API))           | Start a conversation on each row.                                                                                                  | Sidecar status chip 'ready'; turn completes; usage row written                                                   | 'Sidecar crashed and could not restart' -> restart app                                             |    |     |
| T-PAY-04 | Cost guardrail hard stop                                                 | Settings > Agents > Budget Guardrails: Daily cap \$ = 0.01, Hard stop at % = 100. Start a new conversation after spend exceeds it. | Launch refused with the guardrail dialog (assertCostGuardrailsAllowLaunch)                                       | conversation starts anyway                                                                         |    |     |
| T-PAY-05 | Aux LLM features are NOT guardrail-checked (known gap)                   | With the cap from T-PAY-04 still exceeded, use Side chat or GitHub > AI PR description.                                            | Expected today: the call proceeds (documented gap, audit section 3 'Rate limiting')                              | record actual; not a regression                                                                    |    |     |

| ID       | Path                                     | Steps (real values)                                                                                        | Expected                                                                                                                                  | Failure signature                                                                                   | [ ] | P/F |
|----------|------------------------------------------|------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-----|-----|
| T-PAY-06 | Custom endpoint over public http refused | Settings > Providers > Provider Endpoints: custom endpoint http://lm.example.com/v1                        | 'Custom endpoint URL must use https:// - plain http:// is only allowed for localhost, private-network, or .local/.lan/.internal hosts...' | 'Saved.'                                                                                            |     |     |
| T-PAY-07 | PacketAgent                              | Settings > PacketAgent: endpoint https://agent.example.test, token set; press the health probe in the card | log: service=packetagent operation=health status=<code>                                                                                   | 'PacketAgent requires HTTPS; HTTP is allowed only for a loopback endpoint.' when http:// is entered |     |     |

## Background jobs

| ID       | Job                        | Steps                                                                                 | Expected                                                                                 | Failure signature                           | [ ] | P/F |
|----------|----------------------------|---------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|---------------------------------------------|-----|-----|
| T-JOB-01 | Sidecar restart cap        | taskkill /IM node.exe /F three times within 60 s while a sidecar conversation is open | Chip cycles restarting (1/3..3/3) then 'Sidecar crashed and could not restart'           | no chip change; conversation hangs silently |     |     |
| T-JOB-02 | PTY orphan reap            | Open a terminal pane running `claude`; taskkill /IM packetbench.exe /F; relaunch      | Log line from core::pty::reap_orphaned_pty_children; no stray claude.exe in Task Manager | claude.exe survives                         |     |     |
| T-JOB-03 | PacketAgent SSE reconnect  | Start a stream (Flight with a PacketAgent deployment); disconnect network 10 s        | packet-agent:stream-status 'reconnecting' then 'connected'; cursor preserved             | state 'error' with no retry                 |     |     |
| T-JOB-04 | Auth credential watcher    | Run `claude login` in a terminal pane                                                 | AuthBadge flips to ready without reopening the picker (provider-auth:changed)            | badge stale until restart                   |     |     |
| T-JOB-05 | Flight recovery on startup | Launch an attempt, force-kill the app, relaunch                                       | Attempt shows Failed; worktree swept (log 'sweep_interrupted_attempts')                  | attempt stuck Running                       |     |     |

## Secret loading (every keyring account and file)

| ID       | Secret                                            | Steps                                                                                                                               | Expected                                                                                                            | Failure signature                          | [ ] | P/F |
|----------|---------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|--------------------------------------------|-----|-----|
| T-SEC-01 | api-key-anthropic / openai / minimax / openrouter | Delete the key in Settings > Providers > API Keys ('Delete API key?'), start a conversation                                         | 'No API key configured for <provider>. Set one in Settings > API Keys.'; log outcome=missing                        | turn starts                                |     |     |
| T-SEC-02 | github-token                                      | Settings > GitHub > Remove git host, then open GitHub view                                                                          | 'Sign in with GitHub, or add a token with repo scope' prompt; cmdkey /list no longer lists github-token.packetbench | token still listed                         |     |     |
| T-SEC-03 | git-host-token-<id>                               | Add a Gitea host (https), then Remove                                                                                               | cmdkey /list shows git-host-token-<id>.packetbench before, not after                                                | entry remains                              |     |     |
| T-SEC-04 | ssh-<serverId>                                    | Settings > Servers > Add password-auth server, Save; Delete remote host                                                             | entry ssh-<serverId>.packetbench appears then disappears                                                            | entry remains                              |     |     |
| T-SEC-05 | packet-agent-token                                | Settings > PacketAgent: save token; 'Remove stored token'                                                                           | 'PacketAgent token removed from the credential store.'                                                              | requests still authenticate                |     |     |
| T-SEC-06 | Boot keyring probe                                | Start the app; Select-String packetbench::boot                                                                                      | 'OS credential store is reachable'                                                                                  | 'OS credential store failed a read ...'    |     |     |
| T-SEC-07 | Plaintext token file is inert                     | Create %USERPROFILE%\packetbench\github-token containing 'x'; ask an agent to use gh_list_issues with the GitHub connection removed | 'GitHub token not configured. Run `github_set_token` first.'                                                        | the file's value is used (P06 not applied) |     |     |
| T-SEC-08 | Trust file                                        | Delete %USERPROFILE%\packetbench\trusted-projects.json; start a conversation in a repo with .claude/settings.json hooks             | hooks do not run; log 'project hooks ignored: project is not in the trusted-projects list'                          | hook side effect observed                  |     |     |
| T-SEC-09 | Trust file malformed                              | Write '{ not json' to trusted-projects.json; repeat T-SEC-08                                                                        | 'trusted-projects file is not valid JSON; treating every project as untrusted'                                      | hook runs                                  |     |     |

## Patch verification (one test per patch, keyed to docs/audit/patches)

| Patch | Manual test (real values)                                                                                                                                                                                                                 | Expected                                                                                                                                            | Nothing adjacent broke                                                                                                   | Automated / log line                                                                         | [ ] | P/F |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|-----|-----|
| P01   | Untrusted repo: add .claude/settings.json with <code>{ "hooks": [{"event": "SessionStart", "command": "echo HOOKRAN &gt; %TEMP%\hook.txt"}] }</code> ; start a conversation; then add the repo to trusted-projects.json and start another | First: no hook.txt, log 'project hooks ignored'. Second: hook.txt exists                                                                            | Adjacent: global ~/.claude/settings.json hooks still run in both cases                                                   | cargo test --lib -- project_trust merge_mcp_entries_for_sidecar_drops                        |     |     |
| P02   | New conversation, no posture chosen; send 'run `dir` via bash'                                                                                                                                                                            | Chip 'Manual'; Allow once / Always allow / Deny prompt appears                                                                                      | Adjacent: choosing Default (auto) from the chip runs bash unprompted; Plan blocks bash entirely                          | cargo test --lib -- permission_n_mode_defaults_to_askin g; vitest agentModeChipUtils.test.ts |     |     |
| P03   | Ask: 'use spawn_subagent to run `whoami` with bash'                                                                                                                                                                                       | Sub-agent result contains 'Error: tool 'bash' is not available to this sub-agent.'; log 'sub-agent requested a tool outside its allowlist; refused' | Adjacent: spawn_subagent can still read_file/grep                                                                        | cargo test --lib -- subagent_allowlist denied_tools_stay custom_agents_cannot                |     |     |
| P03b  | In Manual mode ask the agent to create a pull request                                                                                                                                                                                     | Permission prompt for create_pull_request before any git push                                                                                       | Adjacent: Deny refuses it; plan mode disables it                                                                         | cargo test --lib -- create_pull_request_is_a_risky_tool                                      |     |     |
| P04   | mklink /D <workspace>\link C:\Users\<you>\.ssh (needs Developer Mode or admin); ask the agent to grep for 'Host'                                                                                                                          | No lines from the link; only workspace files                                                                                                        | Adjacent: grep still finds matches in real subdirectories                                                                | cargo test --lib -- grep_does_not_follow_symlinks                                            |     |     |
| P05   | Settings > GitHub > Connect a git host > Gitea, http://gitea.example.com                                                                                                                                                                  | 'Gitea base URL must use https:// ...'; also http://gitea.local and http://192.168.1.5:3000 are accepted                                            | Adjacent: Ollama base URL http://<lan-ip>:11434 still accepted (no secret)                                               | cargo test --lib -- tls_guard                                                                |     |     |
| P06   | T-SEC-07                                                                                                                                                                                                                                  | as T-SEC-07                                                                                                                                         | Adjacent: keyring token still works for gh_list_issues                                                                   | grep -n 'github-token' src-tauri/src/core/tool_github.rs shows keyring reads only            |     |     |
| P07   | T-MCP-01, T-MCP-05, T-MCP-07                                                                                                                                                                                                              | as those rows                                                                                                                                       | Adjacent: with no allowlist every resource still reads; tools/call still works                                           | node smoke-test.mjs (fallback runs the transport tests)                                      |     |     |
| P08   | In devtools: await window.__TAURI_INTERNALS.__.invoke('ssh_exec', {commandArgs: ['-o', 'ProxyCommand=calc.exe', 'u@h'], password: null})                                                                                                  | rejects with exactly "ssh option 'ProxyCommand=calc.exe' is not permitted"; calc does not open                                                      | Adjacent: Settings > Servers connect to a real key-auth host still works                                                 | cargo test --lib -- ssh_exec_refuses_local_execution_options                                 |     |     |
| P09   | Set \$env:PACKETBENCH_SIDEAR_PTH='x' and launch                                                                                                                                                                                           | log 'PACKETBENCH_SIDEAR_PTH is set but is not a variable PacketBench reads (typo? ...)' and 'boot check done issues=1'                              | Adjacent: app starts normally                                                                                            | cargo test --lib -- boot_check                                                               |     |     |
| P10   | Right-click a path in a conversation > Open in VS Code                                                                                                                                                                                    | VS Code opens the file                                                                                                                              | Adjacent: 'Show in Explorer' still fails with a console warn (known, H07)                                                | grep plugins src-tauri/tauri.conf.json                                                       |     |     |
| P11   | Is -la .dockerignore                                                                                                                                                                                                                      | file absent                                                                                                                                         | Adjacent: nothing depends on it                                                                                          | git log --oneline -1 -- .dockerignore                                                        |     |     |
| P12   | pnpm tauri build from a non-interactive shell                                                                                                                                                                                             | prune-sidecar prints 'pruned node_modules' and the build reaches the bundler                                                                        | Adjacent: pnpm lint and pnpm build still work afterwards - root devDeps intact                                           | grep -n ignore-workspace scripts/prune-sidecar.js                                            |     |     |
| P13   | pnpm run release:readiness --skip-gates                                                                                                                                                                                                   | the pnpm run check line reads 'not evaluated because some were not executed', NOT 'cannot be derived'                                               | Adjacent: bundle artifact detection still passes; summary still 0 fail                                                   | grep -n remoteagents:check scripts/release-readiness.mjs                                     |     |     |
| P14   | pnpm run remoteagents:build, then pnpm run lint:src                                                                                                                                                                                       | exits 0 and lints 7 files under remoteagents/, none of them under a dist/ directory                                                                 | Adjacent: src and e2e still linted; eslint remoteagents alone still clean                                                | npmx eslint remoteagents --format json   count the entries                                   |     |     |
| P15   | Add a file under src/ that imports @/stores/remoteAgentsSettingsStore, then run pnpm run lint:src                                                                                                                                         | no-restricted-imports error pointing at @/lib/remoteAgentsGate                                                                                      | Adjacent: re-add the workspaceStore import to agentTaskStore.ts - the tile-program store-isolation error must still fire | vitest src/lib/__tests__/remoteAgentsGate.test.ts                                            |     |     |

## Unresolved experiments (audit section 7)

| ID  | Question                                                 | Procedure (cold)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | How to read the result                                                                                                                                                                                 | [ ] | P/F |
|-----|----------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-----|
| U01 | Windows password-auth SSH                                | Settings > Servers > Add: Host <a linux host allowing password auth>, Authentication: password, Save, then Connect. Watch the 'Connecting via SSH...' step.                                                                                                                                                                                                                                                                                                                                                     | Connected within 8 s = stdin path works (F12 void). Timeout/'Permission denied' = stdin path dead -> handoff Task 3.                                                                                   |     |     |
| U02 | xterm link handler                                       | SETTLED 2026-09-05: window.open() returns null in this webview, so the addon logs 'Opening link blocked as opener could not be cleared' and does nothing when a terminal URL is clicked.                                                                                                                                                                                                                                                                                                                        | Settled - benign, no action. Re-check only if xterm or the webview is upgraded.                                                                                                                        |     |     |
| U03 | Key inheritance by MCP stdio servers under the Agent SDK | SETTLED 2026-09-05: the MCP SDK spawns stdio servers with a fixed 12-name env allowlist that excludes ANTHROPIC_API_KEY; a probe child received 15 vars, none of them the key or a sentinel.                                                                                                                                                                                                                                                                                                                    | Settled - F11 refuted, no leak. Re-run after an MCP SDK bump.                                                                                                                                          |     |     |
| U04 | Sidecar-only audit                                       | cd agent-sidecar && pnpm --ignore-workspace audit --json                                                                                                                                                                                                                                                                                                                                                                                                                                                        | SETTLED 2026-09-05: 37 advisories (10 high, 24 moderate, 3 low, 0 critical), almost all in the MCP SDK HTTP-server half the sidecar never starts. Recorded in the dependency snapshot.                 |     |     |
| U05 | Packaged shell open scope                                | SETTLED 2026-09-05. Dev build: the scope rejected a bare path and file:// quoting the P10 regex, and allowed vscode://file/ (VS Code opened) and https:// (Edge opened). Packaged build: the release exe contains the scope regex once, byte-identical to tauri.conf.json line 14; the 2026-08-30 release exe contains it zero times. Installed build: the conversation menu's Open in VS Code launched VS Code cold onto the conversation project, and Open project folder in OS (a bare path) opened nothing. | Settled both ways. To re-check after a config change: strings the built exe for vscode://file/ before shipping, then click both menu items - Open in VS Code must work and the bare-path one must not. |     |     |
| U06 | Vitest stability                                         | pnpm test twice on an idle machine                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Both runs 2743 passed; any single non-reproducing failure is CPU contention.                                                                                                                           |     |     |
| U07 | Real-hardware acceptance                                 | dev/acceptance.md sections 3-5 with the headset                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Rows ticked in that file.                                                                                                                                                                              |     |     |



## Ops pages (from docs/runbooks.md)

| Task                     | Command                                                                                                                                                                                                                           | Success looks like                                                                                     | [ ] | P/F |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|-----|-----|
| Build installers         | export PATH="/c/Users/ianwalmsley/.rustup/toolchains/stable-x86_64-pc-windows-msvc/bin:\$PATH"<br>pnpm gates:full<br>pnpm run release:gate<br>pnpm tauri build<br>pnpm run release:readiness --skip-gates<br>pnpm sidecar:install | C:/Users/ianwalmsley/packetbench-build/release/bundle/nsis/PackageBench_<version>_x64-setup.exe exists |     |     |
| Roll back app            | Windows Settings > Apps > PacketBench > Uninstall; run the previous -setup.exe from the bundle dir                                                                                                                                | Version shown in Settings > Advanced matches the previous release                                      |     |     |
| Roll back a patch        | git apply -R docs/audit/patches/<name>.diff (revert P09 before P01)                                                                                                                                                               | cargo test --lib passes                                                                                |     |     |
| Restart app              | taskkill /IM packetbench.exe /F                                                                                                                                                                                                   | Next launch logs boot check done and reaps orphan PTYs                                                 |     |     |
| Restart MCP server       | Settings > MCP > MCP Provider > Enable MCP Provider off/on                                                                                                                                                                        | New bearer token shown; /health answers                                                                |     |     |
| Tail logs                | Get-Content -Wait -Tail 50<br>"\$env:LOCALAPPDATA\PacketBench\logs\packetbench.log.\$(Get-Date -Format yyyy-MM-dd)"                                                                                                               | lines stream                                                                                           |     |     |
| Security lines only      | Select-String -Path<br>"\$env:LOCALAPPDATA\PacketBench\logs\packetbench.log.*" -Pattern<br>'packetbench::(auth egress trust boot)'                                                                                                | matches listed                                                                                         |     |     |
| List secrets             | cmdkey /list   findstr packetbench                                                                                                                                                                                                | targets <account>.packetbench listed                                                                   |     |     |
| Rotate API key           | Settings > Providers > API Keys: paste new key, save (old one overwritten in api-key-<provider>.packetbench)                                                                                                                      | next turn logs outcome=found                                                                           |     |     |
| Rotate git-host token    | Settings > GitHub > host row > Edit > paste token > save (live-probed first)                                                                                                                                                      | 'Rotated the token for git-host connection' in log                                                     |     |     |
| Rotate PacketAgent token | Settings > PacketAgent > Remove stored token, then save the new one                                                                                                                                                               | 'PacketAgent token removed from the credential store.' then requests succeed                           |     |     |
| Restore state            | taskkill /IM packetbench.exe /F; Copy-Item<br>"\$env:USERPROFILE\.packetbench\state.v1.json.bak"<br>"\$env:USERPROFILE\.packetbench\state.v1.json" -Force                                                                         | app launches with the previous flights/workspaces                                                      |     |     |
| Full backup              | robocopy "\$env:USERPROFILE\.packetbench" "D:\backups\packetbench-<date>" /E /XD pty-transcripts                                                                                                                                  | folder copied; secrets must be re-entered on restore                                                   |     |     |
| Health                   | curl -s http://127.0.0.1:<port>/health                                                                                                                                                                                            | {"ok":true,"app":"PacketBench",...}                                                                    |     |     |

## Bug log

[illegible]

