



CFDS® – Chartered Financial Data Scientist Introduction to Python

Prof. Dr. Natalie Packham

27 November 2024

Table of Contents

- ▼ [1 Data types and structures](#)
 - [1.1 First examples](#)
 - [1.2 Variables](#)
 - [1.3 Basic Data Types](#)
 - [1.4 Basic Data Structures](#)
 - [1.5 Control flow](#)
 - [1.6 Functions](#)

1 Data types and structures

1.1 First examples

First examples

- Printing to the standard output:

In []:

```
print("Hello World")
```

First examples

- A calculator:

In []:

```
2+4
```

In []:

```
2-4
```

In []:

```
2**12
```

- A double asterisk (`**`) is the operator for taking powers.
- The code in a cell is executed by clicking on "Run" or via the shortcut `Shift + Enter`.

1.2 Variables

Variables

- The kernel stores data in variables. The assignment operator `=` assigns a variable name (left-hand side) a value (right-hand side).

In []:

```
a = 5  
b = 2  
a*b
```

In []:

```
savings = 50
```

In []:

```
savings
```

Variables

- Calculate the savings value in seven years, given an interest rate of 7%.

In []:

```
r = 0.07  
future_value = savings*(1+r)**7  
future_value
```

Built-in functions

- A number of built-in functions are available ([link \(https://docs.python.org/3/library/functions.html\)](https://docs.python.org/3/library/functions.html)):

		Built-in Functions		
abs()	delattr()	hash()	memoryview()	set()
all()	dict()	help()	min()	setattr()
any()	dir()	hex()	next()	slice()
ascii()	divmod()	id()	object()	sorted()
bin()	enumerate()	input()	oct()	staticmethod()
bool()	eval()	int()	open()	str()
breakpoint()	exec()	isinstance()	ord()	sum()
bytearray()	filter()	issubclass()	pow()	super()
bytes()	float()	iter()	print()	tuple()
callable()	format()	len()	property()	type()
chr()	frozenset()	list()	range()	vars()
classmethod()	getattr()	locals()	repr()	zip()
compile()	globals()	map()	reversed()	__import__()
complex()	hasattr()	max()	round()	

Built-in functions

In []:

```
round(future_value, 4)
```

Use `help()` to learn more about functions:

In []:

```
help(round)
```

1.3 Basic Data Types

Basic Data Types

	Object type	Meaning	Used for
	int	Integer value	Natural numbers
	float	Floating-point number	Real numbers
	bool	Boolean value	Something true or false
	str	String object	Character, word, text

Integers

- Zero, natural numbers and their negative counterparts, i.e., $\mathbb{Z} = \{ \dots, -3, -2, -1, 0, 1, 2, 3, \dots \}$

In []:

```
a = 4  
type(a)
```

Floating point numbers ("floats")

- Computer representation of real numbers, i.e., \mathbb{R}

In []:

```
1.6 / 4
```

In []:

```
type(1.6/4)
```

Integers and floats

In []:

```
int(5)
```

In []:

```
float(5)
```

In []:

```
type(5)
```

In []:

```
type(5.)
```

Boolean: True or False

- Data type associated with logical expressions
- A Boolean is either `True` or `False`

In []:

```
type(5>4)
```

In []:

```
5 == 3
```

In []:

```
5 != 3
```

Booleans

```
In [ ]:
```

```
5 < 3
```

```
In [ ]:
```

```
5 > 3
```

```
In [ ]:
```

```
5 >= 3
```

```
In [ ]:
```

```
5 <= 3
```

Integer representation of Booleans

```
In [ ]:
```

```
int(True)
```

```
In [ ]:
```

```
int(False)
```

Logical operators: and, or

```
In [ ]:
```

```
True and True
```

```
In [ ]:
```

```
True and False
```

```
In [ ]:
```

```
False and False
```

```
In [ ]:
```

```
True or False
```

Strings

- Strings represent text, i.e., a string is a sequence of characters.
- The basic object to represent strings is `str`.
- A string object is defined by wrapping its contents in in single or double quotation marks.

In []:

```
t = 'this is a string object'
```

In []:

```
t
```

In []:

```
t = "this is a string object"
t
```

- Simple operations can be achieved with built-in string functions:

In []:

```
t.capitalize()
```

In []:

```
t.split()
```

- `\n` is used to force a new line.
- Note: Writing `t.` and hitting the `TAB` key shows the available built-in functions.

Useful string methods

Method	Arguments	Returns/result
<code>capitalize</code>	<code>()</code>	Copy of the string with first letter capitalized
<code>count</code>	<code>(sub[, start[, end]])</code>	Count of the number of occurrences of substring
<code>decode</code>	<code>([encoding[, errors]])</code>	Decoded version of the string, using <i>encoding</i> (e.g., UTF-8)
<code>encode</code>	<code>([encoding+[, errors]])</code>	Encoded version of the string
<code>find</code>	<code>(sub[, start[, end]])</code>	(Lowest) index where substring is found
<code>join</code>	<code>(seq)</code>	Concatenation of strings in sequence <i>seq</i>
<code>replace</code>	<code>(old, new[, count])</code>	Replaces <i>old</i> by <i>new</i> the first <i>count</i> times
<code>split</code>	<code>([sep[, maxsplit]])</code>	List of words in string with <i>sep</i> as separator
<code>splitlines</code>	<code>([keepends])</code>	Separated lines with line ends/breaks if <i>keepends</i> is <code>True</code>
<code>strip</code>	<code>(chars)</code>	Copy of string with leading/trailing characters in <i>chars</i> removed
<code>upper</code>	<code>()</code>	Copy with all letters capitalized

Source: Python for Finance, 2nd ed.

Printing

- Use `print()` to print strings and other objects.

In []:

```
print('Python for Finance')
```

In []:

```
print(t)
```

Printing

In []:

```
i = 0
while i < 4:
    print(i)
    i += 1
```

In []:

```
i = 0
while i < 4:
    print(i, end='|')
    i += 1
```

Formatted printing

- The syntax with curly braces ({}) was introduced in Python 3.7.

In []:

```
'this is an integer %d' % 15
```

In []:

```
'this is an integer {:d}'.format(15)
```

In []:

```
'this is an integer {:4d}'.format(15)
```

Formatted printing

In []:

```
'this is a float %f' % 15.3456
```

In []:

```
'this is a float %.2f' % 15.3456
```

In []:

```
'this is a float {:.f}'.format(15.3456)
```

In []:

```
'this is a float {:.2f}'.format(15.3456)
```

Another useful way to print is to concatenate strings with a + sign:

In []:

```
'this is a float ' + str(15.3456)
```

1.4 Basic Data Structures

Basic Data Structures

	Object type	Meaning	Used for
	tuple	Immutable container	Fixed set of objects, record
	list	Mutable container	Changing set of objects
	dict	Mutable container	Key-value store
	set	Mutable container	Collection of unique objects

- We shall skip dictionaries and sets here as they will be rarely used (if at all) once we have introduced `pandas`.
- Similarly, we shall just skim over lists as they are often used as an auxiliary data structure, e.g. in loops.

Tuples

- The elements of a tuple are written between parentheses, or just separated by commas.
- Tuples are immutable.

In []:

```
t = 1, 2, 3, 'Tom'  
t
```

In []:

```
t = (1, 2, 3, 'Tom')  
t
```

In []:

```
t[3]
```


NOTE: Indices start at 0, not at 1.

Lists

- A list is created by listing its elements within square brackets, separated by commas.

```
In [ ]:
```

```
l = [1.2, "john", "timmy", "helena"]
```

```
l
```

```
In [ ]:
```

```
l[2]
```

```
In [ ]:
```

```
type(l)
```

NOTE: Indices start at 0, not at 1.

Lists

- Negative indices: Count from the end

```
In [ ]:
```

```
l
```

```
In [ ]:
```

```
l[-1]
```

```
In [ ]:
```

```
l[-2]
```

Lists

- Extract elements using `[from:to]` :

```
In [ ]:
```

```
l
```

```
In [ ]:
```

```
l[1:3]
```

NOTE: `names[from:to]` contains the elements from "from" to ("to"-1).

Lists

- Extract sublists, e.g. from index 2 or until index 2:

In []:

```
l[2:]
```

In []:

```
l[:2]
```

Lists

- Extract sublists by using `[from:to:step]`, e.g. every second element or all elements from index 2:

In []:

```
l
```

In []:

```
l[::2]
```

In []:

```
l[2::]
```

Lists

- Use `[from:to:step]` to reverse a list:

In []:

```
l[::-1]
```

Lists

- Use `*` and `+` to repeat and join lists:

In []:

```
l*2
```

In []:

```
l + l[::-1]
```

Lists

- Lists are mutable

In []:

```
l
```

In []:

```
l[0] = "thomas"
```

In []:

```
l
```

In []:

```
l[2:4] = ["hannah", "laura"]
```

In []:

```
l.append([4, 3])
```

In []:

```
l
```

List methods

- To view the methods available to a list, type the list name with a full-stop (e.g. `l.`) and press the `Tab` button.

Method	Arguments	Returns/result
<code>l[i] = x</code>	<code>[i]</code>	Replaces i -th element by x
<code>l[i:j:k] = s</code>	<code>[i:j:k]</code>	Replaces every k -th element from i to $j - 1$ by s
<code>append</code>	<code>(x)</code>	Appends x to object
<code>count</code>	<code>(x)</code>	Number of occurrences of object x
<code>del l[i:j:k]</code>	<code>[i:j:k]</code>	Deletes elements with index values i to $j - 1$
<code>extend</code>	<code>(s)</code>	Appends all elements of s to object
<code>index</code>	<code>(x[, i[, j]])</code>	First index of x between elements i and $j - 1$
<code>insert</code>	<code>(i, x)</code>	Inserts x at/before index i
<code>remove</code>	<code>(i)</code>	Removes element with index i
<code>pop</code>	<code>(i)</code>	Removes element with index i and returns it
<code>reverse</code>	<code>()</code>	Reverses all items in place
<code>sort</code>	<code>([cmp[, key[, reverse]]])</code>	Sorts all items in place

Source: Python for Finance, 2nd ed.

1.5 Control flow

Control flow

- Control flow refers to control structures such as `if`-statements and `for`-loops that control the order in which code is executed.

Control flow: `if`-statements

- The `if/elif/else` statement executes code based on whether a condition is true or false:

In []:

```
if 2+2 == 4:
    print("I am a math genius!")
```

- The condition `2+2==4` resolves to true, so the indented code following the condition is executed.
- Code blocks are delimited by indentation.

Control flow: `if`-statements

- In the code below the conditions are checked and the first block matching a `TRUE` condition is executed:

In []:

```
x = 100
if x == 1:
    print(x)
elif x == 2:
    print(x)
elif x == 3:
    print(x)
elif x == 4:
    print(x)
else:
    print("{} > 4".format(x))
```

Control flow: for-loops

A `for` loop iterates over a sequence of values and executes the respective code block:

In []:

```
names = ["John", "Alina", "Timmy", "Helena"]
for participant in (names):
    print('{} is taking this lecture.'.format(participant))
```

- If the sequence is a counter, i.e., a sequence of numbers, then the function `range()` is useful:

In []:

```
for (i) in range(4):
    print(i)
```

List comprehension allows to generate lists in a one-line `for` statement:

In []:

```
l=[i for i in range(4)]
l
```

Control flow: while -statement

- The `while` loop repeatedly executes a block of statements provided the condition remains `TRUE` :

In []:

```
a = 4
i = 0
while i < a:
    print("{} is smaller than {}".format(i, a))
    i = i+1
```

- The `break` keyword interrupts control flow:

In []:

```
for i in range(5):  
    print("{} is smaller than {}".format(i, 3))  
    if i == 2:  
        break
```

1.6 Functions

Functions

- It is useful to group code that is repeatedly used in **functions**.
- A `function`-block consists of the function header and the function body.
- As with other code blocks, the function body must be indentend.

In []:

```
def circle_circumference(radius):  
    return 2 * 3.14159 * radius * 2
```

In []:

```
circle_circumference(5)
```

Function syntax

- The syntax for writing a function is:
 - keyword `def` followed by
 - function's name followed by
 - the arguments of the function, separated by commas, in parentheses followed by a colon (:)
 - function body (indented)
 - optional: within the function body the `return` keyword can be used to return an object or value

Function syntax

- Function arguments are passed "by reference" meaning that changes to an object can be made within a function:

In []:

```
def try_to_modify(x, y, z):  
    x = 23  
    y.append(42)  
    z = [99] # new reference  
    print(x)  
    print(y)  
    print(z)  
  
a = 77 # immutable variable  
b = [99] # mutable variable  
c = [28]  
  
try_to_modify(a, b, c)  
print(a)  
print(b)  
print(c)
```

Function syntax

- Function arguments can be given default values:

In []:

```
def plus10(x = 50):  
    return x + 10
```

In []:

```
plus10()
```

In []:

```
plus10(20)
```