YR9700 125Khz+2.4G Active Transponder

(125 kHz Trigger+ 2.4GHz receiver)

The Active RFID reader is specialized in sporting events, and can use in indoor & outdoor environment , with working in wide temperature range, excellence reading performance , super network stability and so on characteristics, unique reading algorithm of anti collision tag, can read 1-300 tags at the same time , read tags 100%.

Typical Applications:

Marathon timing systems

Triathlon timing systems

Physical training coaching systems

Kart racing systems

Motorcycle,bike ,MTB race

Skiing timing systems

Other active systems management

Parameter：

Model	YR9700
Name	Active Transponder
Size	230*210*27mm
Frequency	Two channel 125K trigger，two channel 2.45G receive
Read range	1-3m(depend on application tag and antenna)
Read tag	Multiple tag reading ,1- 300 tags at the same time (depend on antenna/tag and application)
Interface(connector)	RS232 ,TCP/IP Ethernet(RJ45)
Identify Speed	200 km/h
Weight	1.9KG
Humidity	< 95% (+ 25 ° C)
Shell Material	aluminum alloy

Operating temperature	- 20 ° C - + 55 ° C
Storage temperature	- 20 ° C - + 85 ° C
Power consumption standard	Working power milliwatt(mW)

Working pattern:

The reader uninterruptedly sending the low frequency 125 KHZ signal, any active tags into the low frequency coverage will receive low frequency ID code, and parse out 125 KHZ signal and then immediately back to reader with 2.4 GHz signal , and transmit the received data to the background management system.

Reading distance:

The read rang 0-3 meters which can be adjusted through power regulator device ;also can Extend the launch distance of low frequency through connect external 2 routes 125 KHZ low frequency antenna , can connect external the carpet antenna of 1 meters, 3 meters, 6 meters, 10 meters carpet, with excellent strong penetrating ability and 100% reading advantage.

Identification tags speed and ability:

Tags speed with 200 km/h,the reader also can stably to Identify the tags .

The reader can read more than 300 active tags at the same time; can read all the tags in the short time

Communications security:

The active reader and tags with special communication protocol, and have strictly verified the legitimacy of the equipment, using encryption algorithms to make sure the security of the communication data.