

The wind area of a sectional door is based on the size of a single panel, usually no more than 24" deep, and the width of the door.

Dual Pressure Zones

A common placement for a garage door is near a corner of a residence, which would put a portion of the door in zone 5, leaving the remainder in zone 4. You can select the door based on the zone 5 pressure, or you may use a weighted average. For example, if you have a 10-ft wide door and 2-ft are in zone 5, the zone 5 suction is -50 and the zone 4 suction is -42: $((2 \times 50) + (10-2) \times 42) / 10 = (100 + 336) / 10 = 436 / 10 = -43.6$ psf. (Round up to -44 psf)

If a window is placed in zone 4 and zone 5, use the zone 5 pressure.

A_{eff} (ft²)	15 ft Mean Roof Height				20 ft Mean Roof Height				25 ft Mean Roof height				30 ft Mean Roof Height			
	Zone 4		Zone 5		Zone 4		Zone 5		Zone 4		Zone 5		Zone 4		Zone 5	
	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-
10	40	43	40	54	43	46	43	57	45	48	45	60	46	50	46	62
20	38	42	38	50	41	44	41	53	43	46	43	56	44	48	44	58
50	36	39	36	45	38	42	38	48	40	44	40	50	42	45	42	52
100	34	37	34	42	36	40	36	44	38	42	38	46	39	43	39	48
500	30	33	30	33	32	35	32	35	33	37	33	37	35	38	35	38

Wind analysis per MecaWind Pro V2335