


CONFIG APACHE VIRTUAL HOST

Note : CentOS 7.

vHost / 192.168.100.30


client / 192.168.100.7

1. install apache.




```
padli@centos7:/  
padli@cavs: ~ x padli@centos7:/ x  
[root@centos7 /]# yum -y install httpd
```

2. enable & start apache service.



```
padli@centos7:/  
padli@cavs: ~ x padli@centos7:/ x  
[root@centos7 /]# systemctl enable httpd  
[root@centos7 /]# systemctl start httpd  
[root@centos7 /]#
```

3. create dir "mkdir -p /var/www/centos7.com/public_html".



```
padli@centos7:/var/www  
padli@cavs: ~ x padli@centos7:/var/www x  
[root@centos7 /]# cd /var/www/  
[root@centos7 www]# mkdir -p centos7.com/public_html/
```

4. create dir "mkdir -p /var/www/raisa.com/public_html".

```
padli@centos7:/var/www
padli@cavs: ~ x padli@centos7:/var/www x
[root@centos7 www]# mkdir -p raisa.com/public_html/
```

5. cek dir.

```
padli@centos7:/var/www
padli@cavs: ~ x padli@centos7:/var/www x
[root@centos7 www]# ls
centos7.com cgi-bin html raisa.com
[root@centos7 www]#
```


6. change owner, group & rwx.

```
padli@centos7:/var/www
padli@cavs: ~ x padli@centos7:/var/www x
[root@centos7 www]# chown -R $USER:$USER /var/www/centos7.com/public_html/
[root@centos7 www]# chown -R $USER:$USER /var/www/raisa.com/public_html/
[root@centos7 www]# chmod -R 755 /var/www/
[root@centos7 www]#
```

7. create file "vi /var/www/centos7.com/public_html/index.html".

```
padli@centos7:/var/www
padli@cavs: ~ x padli@centos7:/var/www x
<html>
  <head>
    <title>www.centos7.com</title>
  </head>
  <body>
    <h1>Success: You Have Set Up a Virtual Host</h1>
  </body>
</html>
~
~
"centos7.com/public_html/index.html" 8L, 141C
```

8. create file "vi /var/www/raisa.com/public_html/index.html".




The screenshot shows a terminal window with the title bar "padli@centos7:/var/www". There are two tabs: "padli@cavs: ~" and "padli@centos7:/var/www". The terminal content shows the following HTML code being entered:

```
<html>
  <head>
    <title>www.raisa.com</title>
  </head>
  <body>
    <h1>Success: You Have Set Up a Virtual Host</h1>
  </body>
</html>
```

Below the code, there is a tilde symbol (~) and a status line: "raisa.com/public_html/index.html" 9L, 140C.


9. create dir.



The screenshot shows a terminal window with the title bar "padli@centos7:/". There are two tabs: "padli@cavs: ~" and "padli@centos7:/". The terminal content shows the command:

```
[root@centos7 /]# mkdir /etc/httpd/sites-available/
```


10. create dir.



The screenshot shows a terminal window with the title bar "padli@centos7:/". There are two tabs: "padli@cavs: ~" and "padli@centos7:/". The terminal content shows the command:


```
[root@centos7 /]# mkdir /etc/httpd/sites-enabled/
```

11. set "vi /etc/httpd/conf/httpd.conf" & add this line.




```
padli@centos7:/  
padli@cavs: ~ x padli@centos7:/  
# Defaults if commented: EnableMMAP On, EnableSendfile Off  
#  
#EnableMMAP off  
EnableSendfile on  
  
# Supplemental configuration  
#  
# Load config files in the "/etc/httpd/conf.d" directory, if any.  
IncludeOptional conf.d/*.conf  
IncludeOptional sites-enabled/*.conf
```

12. create file "vi /etc/httpd/sites-available/centos7.com.conf" & set like this.



```
padli@centos7:/  
padli@cavs: ~ x padli@centos7:/  
<VirtualHost *:80>  
    ServerName www.centos7.com  
    ServerAlias centos7.com  
    DocumentRoot /var/www/centos7.com/public_html  
    ErrorLog /var/www/centos7.com/error.log  
    CustomLog /var/www/centos7.com/requests.log combined  
</VirtualHost>  
~  
"/etc/httpd/sites-available/centos7.com.conf" 7L, 244C
```

13. create file "vi /etc/httpd/sites-available/raisa.com.conf" & set like this.



```
padli@centos7:/  
padli@cavs: ~ x padli@centos7:/  
<VirtualHost *:80>  
    ServerName www.raisa.com  
    ServerAlias raisa.com  
    DocumentRoot /var/www/raisa.com/public_html  
    ErrorLog /var/www/raisa.com/error.log  
    CustomLog /var/www/raisa.com/requests.log combined  
</VirtualHost>  
~  
"/etc/httpd/sites-available/raisa.com.conf" 7L, 234C
```

14. create shortcut.

```
padli@centos7:/  
padli@cavs: ~ x padli@centos7:/ x  
[root@centos7 /]# ln -s /etc/httpd/sites-available/centos7.com.conf /etc/httpd/sites-enabled/centos7.com.conf
```

15. create shortcut.

```
padli@centos7:/  
padli@cavs: ~ x padli@centos7:/ x  
[root@centos7 /]# ln -s /etc/httpd/sites-available/raisa.com.conf /etc/httpd/sites-enabled/raisa.com.conf
```


16. restart apache.

```
padli@centos7:/  
padli@cavs: ~ x padli@centos7:/ x  
[root@centos7 /]# systemctl restart httpd  
[root@centos7 /]#
```

17. set "vi /etc/hosts" on client.

```
padli@cavs: ~  
padli@cavs: ~ x padli@centos7:/ x  
GNU nano 2.2.6 File: /etc/hosts Modified  
127.0.0.1 localhost  
127.0.1.1 cavs.com  
192.168.100.30 www.centos7.com www  
192.168.100.30 www.raisa.com www  
# The following lines are desirable for IPv6 capable hosts  
::1 ip6-localhost ip6-loopback  
fe00::0 ip6-localnet  
ff00::0 ip6-mcastprefix  
ff02::1 ip6-allnodes  
^G Get Help ^O WriteOut ^R Read File ^Y Prev Page ^K Cut Text ^C Cur Pos  
^X Exit ^J Justify ^W Where Is ^V Next Page ^U UnCut Text ^T To Spell
```

18. tes browsing on client.



Dok 28/07/2015 padliyulian@ymail.com