



1 / 1
point

1. You are working on a spam classification system using regularized logistic regression. "Spam" is a positive class ($y = 1$) and "not spam" is the negative class ($y = 0$). You have trained your classifier and there are $m = 1000$ examples in the cross-validation set. The chart of predicted class vs. actual class is:

	Actual Class: 1	Actual Class: 0
Predicted Class: 1	85	890
Predicted Class: 0	15	10

For reference:

- Accuracy = (true positives + true negatives) / (total examples)
- Precision = (true positives) / (true positives + false positives)
- Recall = (true positives) / (true positives + false negatives)
- F_1 score = $(2 * \text{precision} * \text{recall}) / (\text{precision} + \text{recall})$

What is the classifier's F_1 score (as a value from 0 to 1)?

Enter your answer in the box below. If necessary, provide at least two values after the decimal point.

Correct Response

Precision is 0.087 and recall is 0.85, so F_1 score is $(2 * \text{precision} * \text{recall}) / (\text{precision} + \text{recall}) = 0.158$.

2. Suppose a massive dataset is available for training a learning algorithm. Training on a lot of data is likely to give good performance when two of the following conditions hold true.

Which are the two?

- ☐ When we are willing to include high order polynomial features of x (such as x_1^2 , x_2^2 , x_1x_2 , etc.).

Un-selected is correct

- ☐ The classes are not too skewed.

Un-selected is correct

- ☒ A human expert on the application domain can confidently predict y when given only the features x (or more generally, if we have some way to be confident that x contains sufficient information to predict y accurately).

Correct

It is important that the features contain sufficient information, as otherwise no amount of data can solve a learning problem in which the features do not contain enough information to make an accurate prediction.

- ☒ Our learning algorithm is able to represent fairly complex functions (for example, if we train a neural network or other model with a large number of parameters).

Correct

You should use a complex, "low bias" algorithm, as it will be able to make use of the large dataset provided. If the model is too simple, it will underfit the large training set.



3. Suppose you have trained a logistic regression classifier which is outputting $h_{\theta}(x)$.

Currently, you predict 1 if $h_{\theta}(x) \geq \text{threshold}$, and predict 0 if $h_{\theta}(x) < \text{threshold}$, where currently the threshold is set to 0.5.

Suppose you **increase** the threshold to 0.7. Which of the following are true? Check all that apply.

- ☒ The classifier is likely to now have higher precision.

Correct

Increasing the threshold means more $y = 0$ predictions. This will decrease both true and false positives, so precision will increase.

- ☐ The classifier is likely to have unchanged precision and recall, and thus the same F_1 score.

Un-selected is correct

- ☐ The classifier is likely to have unchanged precision and recall, but higher accuracy.

Un-selected is correct

- ☐ The classifier is likely to now have higher recall.

Un-selected is correct

1 / 1
point



1 / 1
point

4. Suppose you are working on a spam classifier, where spam emails are positive examples ($y = 1$) and non-spam emails are negative examples ($y = 0$). You have a training set of emails in which 99% of the emails are non-spam and the other 1% is spam. Which of the following statements are true? Check all that apply.

- ☒ If you always predict non-spam (output $y = 0$), your classifier will have an accuracy of 99%.

Correct

Since 99% of the examples are $y = 0$, always predicting 0 gives an accuracy of 99%. Note, however, that this is not a good spam system, as you will never catch any spam.

- ☒ If you always predict non-spam (output $y = 0$), your classifier will have 99% accuracy on the training set, and it will likely perform similarly on the cross validation set.

Correct

The classifier achieves 99% accuracy on the training set because of how skewed the classes are. We can expect that the cross-validation set will be skewed in the same fashion, so the classifier will have approximately the same accuracy.

- ☒ A good classifier should have both a high precision and high recall on the cross validation set.

Correct

For data with skewed classes like these spam data, we want to achieve a high F_1 score, which requires high precision and high recall.

- ☐ If you always predict non-spam (output $y = 0$), your classifier will have 99% accuracy on the training set, but it will do much worse on the cross validation set because it has overfit the training data.

Un-selected is correct



1 / 1
point

5. Which of the following statements are true? Check all that apply.

- ☐ If your model is underfitting the training set, then obtaining more data is likely to help.

Un-selected is correct

- ☒ Using a **very large** training set makes it unlikely for model to overfit the training data.

Correct

A sufficiently large training set will not be overfit, as the model cannot overfit some of the examples without doing poorly on the others.

- ☐ After training a logistic regression classifier, you **must** use 0.5 as your threshold for predicting whether an example is positive or negative.

Un-selected is correct

- ☒ On skewed datasets (e.g., when there are more positive examples than negative examples), accuracy is not a good measure of performance and you should instead use F_1 score based on the precision and recall.

Correct

You can always achieve high accuracy on skewed datasets by predicting the most the same output (the most common one) for every input. Thus the F_1 score is a better way to measure performance.

- ☐ It is a good idea to spend a lot of time collecting a **large** amount of data before building your first version of a learning algorithm.

Un-selected is correct