

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum

Neurons

Quantum

Hopfield Model

Structure

Working

Illustrations

Experiments

Updating

Strategy

Effective

Capacity

Issues

Discussion

References

Quantum Hopfield Networks

Rajarsi Pal

Indian Institute of Technology Madras

Term Project

ID5841 Quantum Lab

But what is a Hopfield network ?

[1]

Rajarsi Pal

Introduction
Classical HAM

Working
Applications

Quantum
Neurons
Quantum
Hopfield Model

Structure

Working

Illustrations

Experiments

Updating
Strategy
Effective
Capacity


Issues

Discussion

References

A Hopfield Network is a type of recurrent neural network. They were introduced by J.Hopfield in 1982 as a model for associative memory.

Network architecture :



How does it work ?

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum

Neurons

Quantum
Hopfield Model

Structure

Working

Illustrations

Experiments

Updating

Strategy

Effective


Capacity

Issues

Discussion

References

- define **Energy** as, $E(X) = -\frac{1}{2N} \sum_{i,j} X_i W_{i,j} X_j + \sum_i b_i X_i$
- Neuron activation ;
 $X_i(t+1) = g_\beta(-\frac{\partial E}{\partial X_i}) = g_\beta(\frac{1}{2N} \sum_j W_{i,j} X_j - b_i)$, g_β is the activation function



- *Claim:* Energy decreases monotonically with iterations !

Applications

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum

Neurons

Quantum

Hopfield Model

Structure

Working

Illustrations

Experiments

Updating

Strategy


Effective

Capacity

Issues

Discussion

References



But how to make neurons Quantum ?

[3], [2]

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum
Neurons

Quantum
Hopfield Model

Structure

Working

Illustrations

Experiments

Updating
Strategy

Effective
Capacity

Issues

Discussion

References

Non-linearity is an issue !

- Non-linear activation functions are necessary for neural networks.
- Quantum evolution is Unitary \implies inherently **linear**!

Possible ways !

■ Measurement based approach

Measurements are not unitary : Trace out part of the system on each iteration.

■ Basis Encoding

This involves transformations of the form, $|s\rangle|0\rangle \rightarrow |s\rangle|\phi(s)\rangle$, where $\phi(s)$: non-linear function. Using *Quine McClusky* method

■ Rotation Encoding

What we will be using.

Introduction

Classical HAM

Applications

Quantum

Neurons

Hopfield Model

Experiments

Updating

Capacity

Issues

Discussion

References

Miller's Model

[QHAM]

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum

Neurons

Quantum
Hopfield Model

Structure

Working

Illustrations

Experiments

Updating

Strategy

Effective

Capacity

Issues

Discussion

References

Encoding $\{\pm 1\}$ states into $|kets\rangle$

$$|\psi(x_i)\rangle = \cos\left(\frac{\pi}{4}x_i + \frac{\pi}{4}\right)|0\rangle + \sin\left(\frac{\pi}{4}x_i + \frac{\pi}{4}\right)|1\rangle$$

$$\text{Thus, } \vec{x} = \{x_1, x_2, x_3..\} \implies |\psi(x_1, x_2..\rangle = |\psi(x_1)\rangle|\psi(x_2)...\rangle$$

Encoding W_{ij} into $R_y(\phi_{i,j})$

Idea: encode elements of W_{ij} as arguments to CR_y




Figure: Rotation Encoding

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum

Neurons

Quantum

Hopfield Model

Structure

Working

Illustrations

Experiments

Updating

Strategy


Effective

Capacity

Issues

Discussion

References



Miller's Model

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum

Neurons

Quantum

Hopfield Model

Structure

Working

Illustrations

Experiments

Updating

Strategy

Effective

Capacity

Issues

Discussion

References

Updating the system

Idea:

- Use CR_y to update the $|ancilla\rangle$ initialised at $|0\rangle$.
- **SWAP** $|ancilla\rangle$ with the qubit to be updated.





Figure: Updating qubit $|s_3\rangle$ and $|s_2\rangle$

Miller's Model

Effective Non-linearity



But how to get back the classical states ?

Idea: Use Majority voting

- Basically, run the circuit a number of times and estimate $P(|1\rangle)$ and $P(|0\rangle)$ by measuring it.
- Interpret the state as $(+1)$ if $P(|1\rangle) > 0.5$ else as (-1)

Illustrations

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum

Neurons

Quantum

Hopfield Model

Structure

Working

Illustrations

Experiments

Updating

Strategy

Effective

Capacity

Issues

Discussion

References






Figure: Stored-Patterns



Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum

Neurons

Quantum

Hopfield Model

Structure

Working

Illustrations

Experiments

Updating
Strategy

Effective

Capacity

Issues

Discussion

References

Best way to update states ?

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum

Neurons

Quantum
Hopfield Model

Structure

Working

Illustrations

Experiments

Updating
Strategy

Effective
Capacity

Issues

Discussion

References

Repeated vs. Final Measurement

- Measure all qubits after every updating step.
- Results are more accurate
- But involves mid-circuit measurements
- Measure all qubits only at the end.
- Results are often ambiguous.
- Avoids mid-circuit measurements. Evolution is more quantum in nature.

Best way to update states ?

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum

Neurons

Quantum Hopfield Model

Structure

Working

Illustrations

Experiments

Updating

Strategy

Effective

Capacity

Issues

Discussion

References




Figure: n = 4




Figure: n = 5




Figure: n = 8

How well can it retrieve the patterns ?

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum

Neurons

Quantum
Hopfield Model

Structure

Working

Illustrations

Experiments

Updating

Strategy

Effective
Capacity



Issues

Discussion

References

Scaling of Eff. Capacity

- Check variation of **Density Accuracy** of the network against **(m/n)**, where **m** is the no. of patterns, **n** is the no. of qubits, tuning **no.of updates** to n and $2n$ respectively.
- Check variation of **Density Accuracy** of the network against **no.of updates**, for different cases of **m** and **n** .



How well can it retrieve the patterns ?

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum
Neurons

Quantum
Hopfield Model

Structure

Working

Illustrations

Experiments




Updating
Strategy

Effective
Capacity

Issues

Discussion

References



Where does it go wrong ?

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum

Neurons

Quantum
Hopfield Model

Structure

Working

Illustrations

Experiments

Updating

Strategy

Effective

Capacity

Issues

Discussion

References

Majority Voting

- Unjustly collapses the state to the computational basis \implies loses essential quantum information.
- Loses all information on the phase of the state.
- Density accuracy falls drastically with no. of (m/n) ratio.

Repeated Updates

- Sequence of updates affect trajectory as update operators are non-commuting.
- Postponing the measurements to the end lead to states where $P(|0\rangle) = P(|1\rangle) = 0.5$ for all qubits.

Things to do better..

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum

Neurons

Quantum

Hopfield Model

Structure

Working

Illustrations

Experiments

Updating

Strategy

Effective

Capacity

Issues

Discussion

References

- This model is not truly Quantum as it does not incorporate effects like superposition and entanglement into its design.
- There is no way to probe into the dynamics of the system i.e to find metrics like current **Energy**, **Hamming distance** to stored configurations.
- Capacity of the network indicates that it barely manages to satisfy the classical limit. No real quantum advantage !

References

Rajarsi Pal

Introduction

Classical HAM

Working

Applications

Quantum

Neurons

Quantum
Hopfield Model

Structure

Working

Illustrations

Experiments

Updating

Strategy

Effective

Capacity

Issues

Discussion

References

- [1] J J Hopfield. “Neural networks and physical systems with emergent collective computational abilities.”. In: *Proceedings of the National Academy of Sciences* 79.8 (1982), pp. 2554–2558. DOI: 10.1073/pnas.79.8.2554. eprint: <https://www.pnas.org/doi/pdf/10.1073/pnas.79.8.2554>. URL: <https://www.pnas.org/doi/abs/10.1073/pnas.79.8.2554>.
- [2] Florian Marquardt. “Machine Learning and Quantum Devices”. In: *SciPost Phys. Lect. Notes* (2021), p. 29. DOI: 10.21468/SciPostPhysLectNotes.29. URL: <https://scipost.org/10.21468/SciPostPhysLectNotes.29>.
- [3] Maria Schuld and Francesco Petruccione. *Supervised Learning with Quantum Computers*. 1st. Springer Publishing Company, Incorporated, 2018. ISBN: 3319964232.