Database management system

P.Madeena-192211011

Experiment-9: Trigger:-

```
| id | code  | name    | subject | marks | phone     |
+----+-------+---------+---------+-------+-----------+
|  1 | csa02 | pooji   | maths   |    98 | 79818243  |
|  2 | csa04 | madeena | ps      |    97 | 99818243  |
|  3 | csa05 | harini  | chem    |    99 | 998567243 |
|  4 | csa07 | deepa   | biology |   100 | 95502042  |
+----+-------+---------+---------+-------+-----------+
4 rows in set (0.00 sec)

mysql> DELIMITER &&
mysql> create trigger after_insert_details
    -> AFTER INSERT ON student_info FOR EACH ROW
    -> BEGIN
    -> INSERT INTO student_details values(new.id,new.code,new.name,new.subject,new.marks,new.phone,CURTIME());
    -> END &&
Query OK, 0 rows affected (0.03 sec)

mysql> INSERT INTO student_info values(10,"csa07","rajitha","software",75,9108965);
    -> INSERT INTO student_info values(10,"csa07","rajitha","software",75,9108965);
    -> end$$
    ->  end $$
    ->
    -> INSERT INTO student_info values
    -> (10,"csa07","rajitha","software",75,9108965);
    -> $$
    -> &&
Query OK, 1 row affected (0.01 sec)

ERROR 1062 (23000): Duplicate entry '10' for key 'student_info.PRIMARY'
mysql> select*from student_details;
    -> &&
+----+-------+---------+----------+-------+---------+------------+
| id | code  | name    | subject  | marks | phone   | lasinserted |
+----+-------+---------+----------+-------+---------+------------+
| 10 | csa07 | rajitha | software |    75 | 9108965 | 21:42:44   |
+----+-------+---------+----------+-------+---------+------------+
1 row in set (0.00 sec)

mysql> DELIMITER $$
mysql>
```